APPENDIX I

ORANGE COUNTY GUIDELINES FOR EVALUATING VMT UNDER CEQA



2020 UPDATED TRANSPORTATION IMPLEMENTATION MANUAL

COUNTY OF ORANGE OC PUBLIC WORKS OC INFRASTRUCTURE PROGRAMS

FINAL

2020 UPDATED TRANSPORTATION IMPLEMENTATION MANUAL

COUNTY OF ORANGE OC PUBLIC WORKS OC INFRASTRUCTURE PROGRAMS

Adopted by the Orange County Board of Supervisors

March 15, 1994

Amended October 2, 2012 (Reso. No. 12-148)

Amended November 17, 2020 (Reso. No. 20-162)

TABLE OF CONTENTS

CHA	PTER 1 - INTRODUCTION	1
CHA	PTER 2 – DEFINITIONS	2
A.	CRITICAL MOVEMENT	2
B.	DEFICIENT INTERSECTION FUND (DIF)	2
C.	DEFICIENT INTERSECTION LIST (DIL	2
D.	EXEMPT INTERSECTION	2
E.	LEVEL OF SERVICE (LOS)	3
F.	MAXIMUM FEASIBLE INTERSECTION (MFI)	3
G.	MEASURABLE TRAFFIC	3
H.	SPHERE OF IMPACT	3
I.	TRAFFIC LEVEL OF SERVICE POLICY	3
CHA	PTER 3 – PROJECTS EXEMPT FROM THE GM REQUIREMENTS	4
CHA	PTER 4 – TRAFFIC ANALYSIS METHODOLOGIES	6
A.	LEVELS OF SERVICE	6
B.	FLOW RATES AND ADJUSTMENT FACTORS	7
C.	LOST TIME	7
D.	LANE DISTRIBUTION	7
E.	RIGHT TURNING TRAFFIC	7
F.	SIGNAL PHASING	8
G.	SANTIAGO CANYON ROAD	8
CHA	PTER 5.0 – MINIMUM REQUIREMENTS OF GM ELEMENT TRAFFIC	
	ANALYSIS	9
A.	GENERAL	9
CHA	PTER 6.0 – DEFICIENT INTERSECTION LIST1	.3
A.	GENERAL 1	.3
B.	DEFICIENT INTERSECTIONS	4
C.	PROCEDURE TO MODIFY DEFICIENT INTERSECTIONS LIST 1	4
CHA	PTER 7.0 –COUNTRY TRAFFIC MONITORING PROGRAM 1	.5
CHA	PTER 8.0 –VEHICLE MILES TRAVELED 1	.6

A. DEFINITION OF REGION	16
B. PROJECT SCREENING	17
C. SIGNIFICANCE THRESHOLDS FOR LAND DEVELOPMENT PROJECTS \dots	22
D. SIGNIFICANCE THRESHOLDS FOR TRANSPORTATION PROJECTS	26
E. SIGNIFICANCE THRESHOLDS FOR LAND PLANS	29
F. MITIGATION STRATEGIES	30

LIST OF ATTACHMENTS

- A County of Orange Fair-Share Formula For Traffic Impacts
- $\mbox{\bf B}$ Guidelines for Evaluating Vehicle Miles Traveled (September 2020)

CHAPTER 1 - INTRODUCTION

The Transportation Implementation Manual is intended to clarify the intent of the "Traffic Level of Service Policies" of the Growth Management (GM) Element. The manual describes how the "Traffic Level of Service Policies" of the GM Element are to be implemented on a site or project specific basis. It includes a listing of projects which are exempt from GM Element traffic requirements, acceptable traffic analysis methodologies, minimum requirements of GM traffic reports, and the traffic monitoring surveys the County will conduct to determine system performance.

This manual and the provisions contained in the GM Element apply to Santiago Canyon Road and the Circulation Plan intersections under the sole control of the County.

CHAPTER 2 – DEFINITIONS

In addition to those terms defined in the GM Element, for the purposes of this manual, the following terms are defined below:

- **A. CRITICAL MOVEMENT**: In the case of signalized intersections, any of the conflicting through or turning movements which determine the allocation of green signal time. In the case of Santiago Canyon Road, that direction of any two way peak hour flow which is greater.
- **B. DEFICIENT INTERSECTION FUND (DIF)**: A trust fund established to collect fees and implement the maximum improvements deemed feasible by the County to existing signalized intersections which do not meet the Traffic Level of Service Policy for reasons beyond the County's control. All projects contributing measurable traffic to intersections on the Deficient Intersection List shall contribute to this fund on a pro-rata basis.
- C. **DEFICIENT INTERSECTION LIST (DIL**): A list of intersections within the jurisdiction of the County which currently do not meet the Traffic Level of Service Policy for reasons which are beyond the control of the County (e.g., ramp metering effects, traffic generated outside the County's jurisdiction, etc.), and where there are seemingly no opportunities for making any conventional geometric improvement within the current seven-year "measure M" Growth Management Program's Capital improvement Program which will achieve the LOS standards. The current list is included as Section VI of this manual. Additional intersections may be added by the County only as a result of conditions which are beyond the control of the County and after a public hearing.
- **D. EXEMPT INTERSECTION**: An unsignalized intersection or an intersection not under the sole control or jurisdiction of the County of Orange or on the Deficient Intersection List.

- **E. LEVEL OF SERVICE (LOS)**: A measure of the operational quality of a road or intersection ranging from Level of Service A (best) to Level of Service F (worst).
- **F. MAXIMUM FEASIBLE INTERSECTION (MFI)**: The maximum condition an existing intersection may be widened or improved to, while still providing reasonable operational characteristics, given the nature of the surrounding land use. The MFI concept will apply specifically to the DIL and the determination will be made by the County.
- **G. MEASURABLE TRAFFIC**: A traffic volume resulting in a 1% increase in the volume/capacity ratio of the sum of all critical movements.

Example: If the V/C of an intersection is 0.860, measurable traffic will be any addition of trips which will raise the V/C to 0.860+(0.01 x 0.860), i.e., 0.869. For an intersection operating at V/C = 0.860 (C= 1700), measurable traffic would then be any increase in traffic which adds (0.869 - 0.860) x 1700 = 15.3 or 15 or more vehicles to the critical movements.

- **H. SPHERE OF IMPACT**: That area to which a project contributes measurable traffic.
- I. TRAFFIC LEVEL OF SERVICE POLICY: Within three years of the issuance of the first use and occupancy permit for a development project or within five years of the issuance of a finished grading permit or building permit for said project, whichever occurs first, all necessary improvements to the highway system within the County's jurisdiction to which the project contributes measurable traffic shall be constructed and completed to attain Level of Service (LOS) "D" or better. LOS "C" shall be maintained on all uninterrupted links of three miles in length or more on Santiago Canyon Road until such time as uninterrupted segments (i.e. between major signalized intersections) are reduced to less than three miles.

CHAPTER 3 – PROJECTS EXEMPT FROM THE GM REQUIREMENTS

The following development projects have been deemed to have significant public benefit or little traffic impact and are exempt from the requirements of the GM Element:

A. Any development on an existing lot resulting in a total daily traffic generation of less than 200 trips. The following amounts of land use will each generate 200 trips. For other land uses, see "Daily Vehicle Trip Generation Rates" prepared by Orange County.

Multifamily residential	29 Dwelling Units
Single Family Detached	17 Dwelling Units
Single Family Detached-Estate	13 Dwelling Units
Mobile Home	40 Dwelling Units
Light Industrial	15,400 square feet

Hotel/Motel 20 Rooms

General Office 13,300 square feet
Medical Office 2,600 square feet
Neighborhood Commercial 1,480 square feet
Convenience Market 360 square feet
Fast Food Restaurant 222 square feet

- B. Any agricultural, open space, conservation, or passive park use.
- C. Any rebuilding of an existing development damaged or destroyed by fire or natural disaster if uses and square footage remain substantially the same.
- D. Public health & safety facilities such as hospitals, police, fire & safety facilities, and schools.
- E. Government-owned facilities or utilities shall be exempt to the extent the facilities will not be used for generating revenue or commercial purposes. Examples of exempt public uses are city halls, park buildings, and other public buildings. Privately

PROJECTS EXEMPT FROM THE GM REQUIREMENTS

owned utilities will not be exempt from growth management requirements. Notwithstanding property tax exemptions, governmental-owned or constructed facilities (including but not limited to counties, cities and redevelopment agencies) which will generate revenue or be leased for commercial purposes shall be required to prepare the necessary reports and mitigate impacts as appropriate. Examples of this include the revenue generating portions of airports, train stations, stadiums, sports arenas, convention centers, bus terminals, hotels, or concessions on public lands.

- F. Minor alterations and remodeling of existing structures resulting in no substantial change in traffic generation as determined by the Director, OC Public Works or designee.
- G. Places of worship, colleges, welfare, etc. to the extent such facilities are exempt from property tax levies.

CHAPTER 4 – TRAFFIC ANALYSIS METHODOLOGIES

There are a wide variety of traffic analysis methodologies available to traffic engineers. They range from specific procedures required by individual municipalities to standardized techniques used nationwide. In order to ensure all GM Element analyses are consistent, accurate, and generally reproducible, the County of Orange has adopted a set of procedures and acceptable methodologies that are representative of travel behavior in Southern California. For the analysis of GM Element traffic impacts at intersections, the County of Orange requires that the Intersection Capacity Utilization (ICU) methodology be used.

This manual assumes traffic engineers are familiar with the analysis techniques and need only be provided with the necessary assumptions regarding flow rates, clearance times, adjustment factors, etc., to calculate level of service.

The following is a list of the assumptions to be used for GM Element intersection analysis. Any individuals attempting a GM Element traffic analysis without a full understanding of the procedure or assumptions are urged to contact RDMD/Transportation Review Section for clarification prior to performing any work.

A. LEVELS OF SERVICE

The Level Of Service (LOS) of a signalized intersection shall be based upon the sum of the volume-capacity ratios (V/C) of the critical movements. The County's definition of the overall LOS of an intersection is as follows:

<u>Level Of Service</u>	V/C Range
A	0.00 - 0.60
В	0.61 - 0.70
C	0.71 - 0.80
D	0.81 - 0.90
<u>Level Of Service</u>	V/C Range
E	0.91 - 1.00
F	1.00+

B. FLOW RATES AND ADJUSTMENT FACTORS

The saturation flow rate for intersections (also known as lane capacity) shall be 1700 vehicles per hour of green time per lane. This rate is the result of research done on intersections in Orange County during peak periods. This rate may be utilized on left, through, and right turn lanes. Generally, no adjustment will be necessary for dual left turn lanes. However, the County reserves the right to require the use of adjustment factors where, in the County's opinion, unusual conditions exist. In these cases, the adjustment factors for such items as lane width, trucks, grade, or pedestrian activity shall be as stated in the 1997 "Highway Capacity Manual" or any subsequent revisions.

C. LOST TIME

Lost time (also known as "yellow time" or "clearance interval" in some analyses) is given a value of 0.05 (five percent) in GM analyses.

D. LANE DISTRIBUTION

In most cases, approach traffic may be assumed to be distributed evenly among all lanes serving a given movement (i.e., left, through, or right). An exception to this may occur in the case of split signal phasing which is further discussed below. In certain locations where unusual attractions may occur such as a freeway ramp entrance or entrance to a shopping center, an unusually skewed distribution may occur. In such cases, the County shall specify the distribution to be used.

E. RIGHT TURNING TRAFFIC

If the distance from the inside edge of the outside through travel lane is at least 19 feet and no observable parking demand exists during the peak period, or parking is prohibited, right turning vehicles may be assumed to utilize this "unofficial" right turn lane. Otherwise, all right turn traffic shall be assigned to the outside through lane. If an exclusive right turn lane exists and right turn on red is permitted at that location, a 15 percent increase in capacity of the right turn lane may be assumed. If a free right turn exists (right turns do not have to stop for the signal) a flow rate of 1700 vehicles per hour may be assumed for it. The analysis shall account for all right turning traffic, none shall be ignored. Any need for signal overlaps shall be clearly stated.

F. SIGNAL PHASING

At some intersections, split signal phasing may exist. At such locations optional through/left or through/right lanes may be present. Any analysis done for these situations must reflect the true distribution of the approach traffic into these optional lanes. This type of operation is often more difficult to analyze and additional care should be taken to ensure correct results.

G. SANTIAGO CANYON ROAD

For Growth Management Element traffic analyses of Santiago Canyon Road, the traffic level of service policy shall be implemented by evaluating peak hour volumes in relation to the physical capacity of the roadway, using the Volume-to-Capacity methodology. A lane volume of 1,360 vehicles per hour, which is 0.80 times the maximum directional lane capacity of 1,700 vehicles per hour, represents Level of Service "C". These lane capacity guidelines shall be used to ensure that the Level of Service "C" capacity of 1,360 vehicles per hour per lane will be maintained.

CHAPTER 5.0 – MINIMUM REQUIREMENTS OF GM ELEMENT TRAFFIC ANALYSIS

In order to ensure adequate information is provided to the County to judge the impacts of new development, the following minimum requirements are set forth for all traffic analyses of GM Element traffic impacts. While the County does not seek to cause preparation of volumes of unnecessary reports, each application must pass a test of timeliness and content. Reports prepared at earlier levels of review may be used only if the information they contain is still representative of the project under consideration.

A. GENERAL

The report shall be prepared by, or under the supervision of, a Traffic Engineer registered by the State of California. The report shall bear the stamp of the responsible Traffic Engineer. No report shall be accepted for review if it does not bear the appropriate signature, stamp and expiration date. The report shall be divided into the following sections:

- 1. Project Description
- 2. Existing Conditions
- 3. Future Conditions
- 4. Project Trip Generation
- 5. Project Trip Distribution
- 6. Intersection Analysis
- 7. Santiago Canyon Road Analysis (if applicable)
- 8. Summary of Impacts
- 9. Mitigation

The following is an elaboration of each section describing in more detail what should be covered.

1. PROJECT DESCRIPTION

The project should be clearly described, stating the acreage, number of units or gross and net floor area, points of access, and planned usage. A location map should be included

DEFICIENT INTERSECTION LIST

showing the project's relationship to the regional and local circulation systems. A feature plan, plot plan or site plan showing detail commensurate with the level of approval sought, including all pertinent transportation elements (e.g. arterials, streets, access locations, parking, driveways, etc.) must be part of the project description.

2. EXISTING CONDITIONS

All existing traffic conditions within the project's sphere of impact must be clearly described and presented in a graphical manner. Base condition traffic volumes, levels of service, critical movements, and Deficient Intersections will be available from the County. Tabular presentations may be used in addition to the graphical displays. These include:

- AM and PM peak hour, and daily traffic volumes.
- AM and PM peak level of service of all signalized intersections and identification of all critical movements.
- Deficient intersections.

3. FUTURE CONDITIONS

The future conditions within the project's sphere of impact shall be described in a graphical manner consistent with the level of entitlements for project plus existing, and project plus an interim year projection as directed by the County. In addition, a buildout evaluation to establish general plan consistency when appropriate will be required. The County will direct and assist the project applicant to establish the necessary background volume projections.

The traffic projections shall be based upon the level of information available for the levels of service of all signalized intersections will be presented. Any planned road or intersection improvements scheduled within the upcoming five years time included in the analysis shall be described and accounted for in the analysis.

4. PROJECT TRIP GENERATION

DEFICIENT INTERSECTION LIST

The AM and PM peak hour and daily total traffic generation of the project shall be calculated using rates as specified by the County of Orange. In the event a land use is proposed for which no reliable generation rate is available from the County, the generation rate used may be derived from independent empirical studies subject to approval by the County. If the proposed project contains mixed land uses (such as commercial, residential, office or industrial) resulting in expected trips wholly internal to the project, the percentage of internal trips shall be approved by the County prior to proceeding with the analysis.

5. PROJECT TRIP DISTRIBUTION

The project's trip distribution shall be presented in graphical form showing both the number of trips generated by the project and the percentage of the project's total generation on each arterial link to the limit of the project's sphere of impact. In the case of a project containing mixed land uses, a separate distribution shall be presented for each land use, in addition to the summation of the individual distributions.

6. INTERSECTION ANALYSIS

Any intersection to which the project contributes measurable traffic, either in the present or in the interim year projections, must be further analyzed using the methodologies previously discussed. The levels of service for such impacted intersections shall be calculated and reviewed to determine if any mitigation is required under the conditions of the GME.

If a project contributes measurable traffic to a Deficient Intersection, the analysis should show the project's total daily traffic contribution to the Deficient Intersection as well as the total traffic entering that intersection.

7. SANTIAGO CANYON ROAD ANALYSIS

Projects which increase the existing (at the time the project is proposed) critical movement (the higher of the two directional movements) by one percent or more during the AM or PM peak hour on Santiago Canyon Road shall perform a level of service analysis using the previously specified methodology. The analysis shall address project

DEFICIENT INTERSECTION LIST

plus existing, project plus an interim year projection, as determined by the County, in addition to buildout analyses required for general plan consistency evaluation.

8. SUMMARY OF IMPACTS

The report shall contain a listing of all adverse impacts created by the project. These include intersections presently operating at better than LOS D and projected to operate at worse than LOS D as a result of the project, intersections already operating at LOS D to which additional traffic is added by the project, and traffic added to Deficient Intersections.

9. MITIGATION MEASURES

If mitigations are required, their implementation feasibility shall be determined. It is important to classify which mitigations:

- are solely in the control of the project proponent (such as widening adjacent to the proposed project);
- require approval of others or participation in a program (such as FCPP intersection widenings) or intersections within other jurisdictions or shared with them);
- require participation or regulatory action on the part of the County (such as prohibiting parking for intersection restripings);
- require development participation in mitigation cost (see attachment A).

The last section of the report shall contain a detailed description of mitigation measures proposed by the project. A list of these measures shall also be included in a summary at the beginning of the report. The rough cost estimates and potential funding sources of all the mitigation measures (either within the County or outside the County's jurisdiction) shall be provided in the report.

CHAPTER 6.0 – DEFICIENT INTERSECTION LIST

A. GENERAL

A deficient intersection is one that is under the sole control of the County which is currently operating at worse than LOS "D" as a result of factors outside the control of the County and where there are seemingly no opportunities for making any conventional geometric improvements within the current seven-year measure "M" Growth Management Program's Capital Improvement Program (CIP). Each intersection must be studied to determine the Maximum Feasible Intersection (MFI) that could be reasonably expected to be built at the location if funding were available. This will serve as the basis for a cost estimate and the associated fee to be paid by development which contributes measurable traffic to the intersection. The MFI is anticipated to be an at-grade intersection for purposes of this analysis.

As part of the MFI study for each of the intersections on the Deficient Intersection List, the County will prepare cost estimates to modify the existing intersection to its MFI configuration. Any non-exempt development contributing measurable traffic to an intersection on the Deficient Intersection List shall contribute to the Deficient Intersection Fund in an amount equal to the amount of the project's traffic entering the intersection divided by the total traffic entering the intersection as measured in the 1990 Baseline traffic counts, multiplied by the estimated cost to improve the intersection to its MFI condition as shown below:

(Project Traffic I 1990 Baseline Traffic Volume) x (Total Improvement Cost)

The collected fees could be spent on either the deficient intersection or alternative mitigation measures that will relieve congestion on the impacted deficient intersection(s).

B. DEFICIENT INTERSECTIONS

There are no deficient intersections at this time.

C. PROCEDURE TO MODIFY DEFICIENT INTERSECTIONS LIST

Any additional intersections may be placed on the Deficient Intersection List through a noticed public hearing by the Board of Supervisors. The Board will be asked to make specific findings with respect to intersections proposed for inclusion on or exclusion from the list.

Those findings will require that:

- 1. The intersection operates at level of service E or F as defined by the County traffic level of service policy.
- 2. The contribution to the critical movement(s) which determines the level of service at the intersection is a direct result of actions or factors over which the County has no control (e.g., ramp metering, adverse signal timing by state or neighboring city, city trip generation which uses County roadways as primary access routes, emergency services activities, etc.). Such contribution shall be identified by traffic counts and origin/destination data as appropriate.
- 3. The intersection has been annexed or incorporated and is no longer within unincorporated County area.

Removal of an intersection from the Deficient Intersection List requires the Board of Supervisors find that one of the three above conditions no longer exists and is not expected to resume.

CHAPTER 7.0 – COUNTRY TRAFFIC MONITORING PROGRAM

In addition to the County's administration of the GME, the County will be an active participant of the GME by providing base condition traffic counts and levels of service. The County will also make available forecasts as part of the Development Monitoring Program (DMP).

Biennially; from January through April, the OCPW/ Infrastructure Programs/Traffic and Development Support will take AM and PM peak hour turning movement counts at all intersections that may be considered by the GME. These will be analyzed to determine the base level of service and critical movements for the upcoming calendar year.

The OCPW/ Infrastructure Programs/Traffic and Development Support will also take 24 hour directional traffic counts on Santiago Canyon Road. Due to the sensitivity of this road and the rapidly increasing traffic volumes, counts will be taken every six months, in April and October. After completion of all traffic counts, they will be incorporated into the County's latest Development Monitoring Report each January. The DMP will include existing volumes and levels of service and projections of traffic volumes and levels of service for an interim period from present. It is from this basis project proponents should proceed with their analyses of the traffic impacts of their projects.

CHAPTER 8.0 – VEHICLE MILES TRAVELED

This section is intended to serve as a guide, along with the Guidelines for Evaluating Vehicle Miles Traveled Under CEQA prepared by LSA Associates, Inc. (September 2020), for application of Vehicle Miles Traveled (VMT) in CEQA documents. This section describes how VMT is to be implemented on a site or project specific basis, and is modeled after the Governor's Office of Planning and Research (OPR) Technical Advisory (TA) on Evaluating Transportation Impacts in CEQA. The County will continue to use Level of Service (LOS) or another traditional metrics to ensure conformity with County planning documents and policies. Also, as in previous CEQA practice, the applicant/project proponent will still be required to provide traffic analysis that is specific to the proposed project to be reviewed and approved by the County.

These guidelines apply to all projects for which the County is the Lead Agency for certification or adoption of CEQA documents. If the County is the Lead Agency, but the project is located in another jurisdiction, these guidelines would apply. However, if the County is not the Lead Agency, and the project is located in another jurisdiction, the Lead Agency would determine which VMT guidelines should be used for analysis.

A. DEFINITION OF REGION

The "region" for Orange County is the entire county area.

According to the Orange County Transportation Analysis Model (OCTAM 5.0), of the total trips in and out of Orange County, about 21 percent originate and are destined within the unincorporated county area. Another 67 percent of trips originate or are destined within the municipal jurisdictions (cities) in Orange County. The remaining 12 percent of Orange County trips have a trip end in the other counties of the SCAG region or beyond. Because the majority of the unincorporated county trips are contained within the entirety of Orange County (approximately 88 percent) and many other large urbanized areas are defining their region as their counties, the use of Orange County in its entirety is defined as the region for CEQA land development transportation analyses.

It should be recognized the use of Orange County as the region defines the comparative (i.e., baseline), or the denominator, in the identification of project-related impact. The

numerator is the project's VMT contribution. The project-related/generated VMT profile may go beyond the county boundary and not be truncated by a jurisdictional boundary.

VMT is a regional effect not defined by roadway, intersection, or pathway. The OPR acknowledges that lead agencies should not truncate any VMT analysis because of jurisdictional or other boundaries by failing to count the portion of a trip that falls outside the jurisdiction or by discounting the VMT from a trip that crosses a jurisdictional boundary. In that case, it would be the responsibility of the applicant and their traffic study consultant to include the project VMT, regardless of geographical limit. To the satisfaction of County staff. The project-related VMT profile would be compared against the County regional baseline.

B. PROJECT SCREENING

Certain activities and projects may result in a less than significant impact to transportation and circulation. A variety of projects may be screened out of a VMT analysis as follows:

1. LAND DEVELOPMENT PROJECTS

The OPR TA and Guidelines for Evaluating Vehicle Miles Traveled Under CEQA (September 2020) acknowledges that conditions may exist under which a land development project would have a less than significant impact on transportation and circulation. These may be size, location, proximity to transit, or trip-making potential.

Land development projects that have one or more of the following attributes may be presumed to create a less than significant impact on transportation and circulation.

• **Project in High-Quality Transit Area (HQTA):** The project is within 0.5 mile (mi) of a Transit Priority Area (TPA) or an HQTA, unless the project is inconsistent with the RTP/SCS, has a floor to-area ratio (FAR) less than 0.75, provides an excessive amount of parking, or reduces the number of affordable residential units. In accordance with SB 743, "Transit Priority Areas" are defined as "an area within one-half mile of a major transit stop that is existing or

planned, if the planned stop is scheduled to be completed within the planning horizon included in a Transportation Improvement Program. A Major Transit Stop means: "a site containing an existing rail transit station, a ferry terminal served by either a bus or rail transit service, or the intersection of two or more major bus routes with a frequency of service of 15 minutes or less during the morning and afternoon peak commute periods." An HQTA or Corridor is a corridor with fixed route bus service with service intervals no longer than 15 minutes during peak commute hours.

Figure 4 of the Guidelines for Evaluating Vehicle Miles Traveled Under CEQA prepared by LSA Associates, Inc. (September 2020) depicts TPAs within unincorporated Orange County¹, including HQTA corridors served by the Orange County Transportation Authority with service intervals of 15 minutes or less and major transit stops along the Metrolink2 system. Although the figure shows the San Clemente Pier Metrolink station, it does not qualify as a major transit stop because service is limited to weekends. Projects proposed in these areas would be presumed to have a less than significant transportation impact unless the project is inconsistent with the RTP/SCS, has an FAR less than 0.75, provides an excessive amount of parking, or reduces the number of affordable residential units.

- **Neighborhood Retail Project:** The project involves local-serving retail space of less than 50,000 square feet.
- Affordable Housing Project: The project is 100 percent affordable-housing units.
- **Low VMT Area**¹ **Project:** The project is in low VMT areas. The applicant may submit data from the most recent OCTAM version showing the proposed project is within a low VMT area, which may be used, at the discretion of staff, to screen out the project.

_

¹ Orange County's land area may be described in terms of low, medium and high VMT areas based on thresholds described in Chapter 4. These descriptions are Low: less 85 percent of the regional average; Medium: equal to or more than 85 percent of the regional average and less than or equal to 117 percent of regional average; and High: greater than 117 percent of regional average.

TA recommends a volume of 110 ADT as the low volume that would allow the project to be screened out. This recommendation is not based on any analysis of GHG reduction, but was instead based on the potential trip generation of an office project that would already be categorically exempt under CEQA. LSA prepared a deeper analysis and used the California Emissions Estimator Model (CalEEMod, version 2016.3.2) to correlate the effect of changes in project-related ADT to the resulting GHG emissions. This model was selected because it is provided by the California Air Resources Board (CARB) to be used statewide for determining project-level GHG emissions. CalEEMod was used with the built-in default trip lengths and types to show the vehicular GHG emissions from incremental amounts of ADT. Table 3 of the Guidelines for Evaluating Vehicle Miles Traveled Under CEQA (September 2020) shows the resulting annual VMT and GHG emissions from the incremental ADT.

A common GHG emissions threshold is 3,000 metric tons (MT) of carbon dioxide equivalent² (CO2e) per year. Vehicle emissions are typically more than 50 percent of the total project GHG emissions. Thus, a project with 500 ADT would generally have total project emissions that could be less than 1,300 MT CO2e/year (i.e., 50 percent or 643 MT CO2e/year coming from vehicle emissions and the other 50 percent coming from other project activities). As this level of GHG emissions would be less than 3,000 MT CO2e/year, the emissions of GHG from a project up to 500 ADT would typically be less than significant.

Based on this qualitative analysis, the County establishes a screening criteria for small projects of up to 500 ADT.

 Public Facilities: The development of institutional/government and public service uses that support community health, safety or welfare are also screened from subsequent CEQA VMT analysis. The following includes some examples and

² Carbon dioxide equivalent (CO2e) is a concept developed to provide one metric that includes the effects of numerous GHGs. The global warming potential (GWP) of each GHG characterizes the ability of each GHG to trap heat in the atmosphere relative to another GHG. The GWPs of all GHGs are combined to derive the CO2e.

is not an exhaustive list of public facilities that are screened from subsequent CEQA VMT analysis: police/sheriff stations, fire stations, community centers, refuse stations, jails, and landfills. These facilities are already part of the community and, as a public service, the VMT is accounted for in the existing regional average. Many of these facilities also generate fewer than 500 ADT and/or use vehicles other than passenger-cars or light duty trucks. These other vehicle fleets are subject to regulation outside of CEQA, such as the California Air Resources Board (CARB) and the South Coast Air Quality Management District.

2. TRANSPORTATION PROJECTS

The primary attribute to consider with transportation projects is the potential to increase vehicle travel. While the County has discretion to continue to use delay analysis for CEQA disclosure of transportation projects, changes in vehicle travel must also be quantified.

The OPR TA and Guidelines for Evaluating Vehicle Miles Traveled Under CEQA (September 2020) also lists a series of projects that would not likely lead to a substantial or measurable increase in vehicle travel and that, therefore, would generally not require an induced travel analysis. The current list of projects, includes but not limited to are the following examples:

- Rehabilitation, maintenance, replacement, safety, and repair projects designed to improve the condition of existing transportation assets (e.g., highways; roadways; bridges; culverts; Transportation Management System field elements such as cameras, message signs, detection, or signals; tunnels; transit systems; and assets that serve bicycle and pedestrian facilities) and that do not add additional motor vehicle capacity
- Roadside safety devices or hardware installation such median barriers and guardrails
- Roadway shoulder enhancements to provide "breakdown space," dedicated space for use only by transit vehicles, to provide bicycle access, or to otherwise improve safety, but which will not be used as automobile vehicle travel lanes

- Addition of an auxiliary lane of less than one (1) mile in length designed to improve roadway safety
- Installation, removal, or reconfiguration of traffic lanes that are not for through traffic, such as left-, right-, and U-turn pockets, two-way left-turn lanes, or emergency breakdown lanes that are not utilized as through lanes
- Addition of roadway capacity on local or collector streets, provided the project also substantially improves conditions for pedestrians, cyclists, and, if applicable, transit
- Conversion of existing general-purpose lanes (including ramps) to managed lanes or transit lanes, or changing lane management in a manner that would not substantially increase vehicle travel
- Addition of a new lane that is permanently restricted to use only by transit vehicles
- Reduction in the number of through lanes
- Grade separation to separate vehicles from rail, transit, pedestrians, or bicycles, or to replace a lane in order to separate preferential vehicles (e.g., highoccupancy vehicles [HOVs], high occupancy toll [HOT] lane traffic, or trucks) from general vehicles
- Installation, removal, or reconfiguration of traffic control devices, including Transit Signal Priority (TSP) features
- Installation of traffic metering systems, detection systems, cameras, changeable message signs, and other electronics designed to optimize vehicle, bicycle, or pedestrian flow
- Timing of signals to optimize vehicle, bicycle, or pedestrian flow
- Installation of roundabouts or traffic circles
- Installation or reconfiguration of traffic calming devices •
- Adoption of or increase in tolls
- Addition of tolled lanes, where tolls are sufficient to mitigate VMT increase
- Initiation of a new transit service
- Conversion of streets from one-way to two-way operation with no net increase in the number of traffic lanes
- Removal or relocation of off-street or on-street parking spaces

- Adoption or modification of on-street parking or loading restrictions (including meters, time limits, accessible spaces, and preferential/reserved parking permit programs)
- Addition of traffic wayfinding signage
- Rehabilitation and maintenance projects that do not add motor vehicle capacity
- Addition of new or enhanced bike or pedestrian facilities on existing streets/highways or within existing public rights-of-way
- Addition of Class I bike paths, trails, multi-use paths, or other off-road facilities
 that serve nonmotorized travel which provide completely separated rights-of-way
 (Streets and Highway Code, Division 1, Chapter 8, Article 3, Section 890.4).
- Installation of publicly available alternative fuel/charging infrastructure
- Addition of passing lanes, truck climbing lanes, or truck brake-check lanes in rural areas that do not increase overall vehicle capacity along the corridor

Additionally, transit and active transportation projects generally reduce VMT and are, therefore, presumed to cause a less than significant impact on transportation. This presumption may apply to all passenger rail projects, bus and bus rapid-transit projects, and bicycle and pedestrian infrastructure projects.

C. SIGNIFICANCE THRESHOLDS FOR LAND DEVELOPMENT PROJECTS

The TA states that SB 743 and all CEQA VMT transportation analyses refer to automobiles. Here, the term automobile refers to on-road passenger vehicles, specifically cars and light-duty trucks. Heavy-duty trucks can be addressed in other CEQA sections and are subject to regulation in a separate collection of rules under CARB jurisdiction.

The OPR has identified the subject of the thresholds as the primary trips in the home-based typology: specifically, home-based work trips. This includes residential uses, office uses, and retail uses. The home-based work trip type is the primary tripmaking during the peak hours of commuter traffic in the morning and evening periods.

The focus of analyzing transportation impacts has shifted from congestion to climate change, and the purpose of the CEQA analysis is to disclose and ultimately reduce GHG emissions by reducing the number and length of automobile trips. This change in CEQA analysis does not diminish the County's ability to require an LOS analysis to confirm accessibility to a project site, conformance with General Plan policies, or as a function of their general health, safety, and welfare discretion and authority. As part of the SB 375 land use/transportation integration process and the GHG goal setting, most metropolitan planning organizations and regional transportation planning agencies have agreed to reduce GHG through integrated land use and transportation planning by approximately 15 percent by 2035. Furthermore, in its 2017 Scoping Plan-Identified VMT Reductions and Relationship to State Climate Goals, the CARB recommends total VMT per capita rates approximately 15 percent below existing conditions.

The TA therefore recommends:

A proposed (residential) project exceeding a level of 15 percent below existing regional average VMT per capita may indicate a significant transportation impact.

A similar threshold would apply to office projects (15 percent below existing regional average VMT per employee).

VMT generated by retail projects would indicate a significant impact for any net increase in total VMT.

While regional planning documents such as the RTP/SCS calculate a single VMT rate by dividing total VMT for the SCAG region by the total service population, it should be noted that the TA identifies a different denominator for the residential and office comparison rates. If regional average VMT per capita and VMT per employee were calculated using the service population (population plus employment), the denominator would be the same, which would be inconsistent with the TA. Furthermore, using service population to calculate regional average rates would complicate future project analyses.

The environmental document for a proposed land use project will identify population for a residential project and employment for an office project. These values should be used in the transportation analysis to calculate the project's VMT per capita or VMT per employee. If a project's VMT per capita (VMT/project population) or VMT per employee (VMT/project employment) is compared to a regional average based on service rate (VMT/[regional population + employment]), the comparison is not equivalent.

According to the Orange County Transportation Authority calculations using OCTAM 5.0, the average VMT/capita in Orange County is 17.9. The average VMT/employee in Orange County is 24.1.

Mixed-use projects should be evaluated for each component of the project independently, or the County may use the predominant land use type for the analysis. Credit for internal trip capture should be accounted for. No discrete land use types other than residential, office, or retail are identified for threshold development in the TA.

The OPR TA suggests that the County may, but is not required to, develop thresholds for any other use. One approach is to review the County General Plan and/or Countywide Long-Range Transportation Plan (LRTP) and identify whether the implementation of the plan would result in a reduction of VMT and GHGs. If it does, the County may conclude the implementation of the plan, including all the other land use types to achieve the regional climate change goals. Therefore, consistency with the plan and no net change in VMT per employee is a rational threshold for the other land use types. This approach would require disclosure of substantial evidence, including the General Plan or LRTP findings, and other supporting traffic and air quality forecasting support.

In summary, the County's thresholds of significance for the following land uses are:

- Residential: 15 percent below existing regional average VMT per capita (17.9 X 0.85 = 15.2)
- **Office:** 15 percent below existing regional average VMT per employee (24.1 X 0.85 = 20.5)
- Retail: no net change in total VMT

- Mixed Use: consider each component of the project separately based on the threshold for residential, office, retail, etc. and take credit for internal capture
- Other Land Uses: no net change in VMT per employee if consistent with the General Plan or 15 percent below regional average if seeking a General Plan Amendment

Figure 5 of the Guidelines for Evaluating Vehicle Miles Traveled Under CEQA (September 2020) demonstrates the potential land development entitlement process to comply with the Guidelines related to VMT and transportation impacts. It provides the path from application filing through determination of impacts. It is presented as the standard process; each development application is considered unique and may create alternative or modified steps through the process. Each step that diverges from this standard process should be accompanied with substantial evidence demonstrating compliance with other climate change and GHG emission reduction laws and regulations.

Project VMT analysis

The first step is to identify the project land use type and the appropriate efficiency rate to use. If the project is residential, use the per capita (or residential population) efficiency rate. If the project is commercial office (or a similar trip generator), use the per employee efficiency rate. For retail projects, use the total VMT generated by the project. For mixed use projects, report each land use after generating trips, taking credit for internal trip capture, to arrive at the VMT. As an alternative, the predominant use may be reported for mixed-use projects. For all other uses, use the VMT per employee as the comparative.

1. Medium Project VMT Analysis

For medium-sized projects (projects generating less than 1,000 ADT) or those with one predominant use, the determination of project VMT may be identified manually as the product of the daily trip generation (land use density/intensity multiplied by the County-approved trip generation rates, usually the ITE Trip Generation Manual) and the trip length in miles for that specific land use. Trip lengths can be found in other related air quality tools, such as CalEEMod, or may be derived from OCTAM.

2. Large Project VMT Analysis

For large or multi-use projects, use of the OCTAM traffic forecasting tool is required. For purposes of County review, a project generating 1,000 ADT or more should use the OCTAM traffic forecasting tool. At this level of trip generating, the probability of trip fulfilment expands to an area greater than the immediate project location and may include a greater regional attraction. The OCTAM traffic forecasting tool can more accurately define the select links used and the total VMT generated by the project.

Next, the project generated efficiency rate, or total VMT, depending on project type, is compared to the appropriate significance threshold. This is either 85 percent of the existing regional average per capita or employment (for the County) for residential and office uses, or no net increase in total VMT for retail or other uses that are consistent with the General Plan. For those projects that require a General Plan Amendment, 85 percent of existing regional average is appropriate, as the project has yet to be evaluated as part of the County's ultimate land development vision.

If the project VMT (expressed as a per capita or per employee rate or total number) is at or less than the significance threshold, the project is presumed to create a less than significant impact. No further analysis is required. If the project is greater than the significance threshold, mitigation measures are required.

D. SIGNIFICANCE THRESHOLDS FOR TRANSPORTATION PROJECTS

The County may continue to use delay and LOS for transportation projects as long as impacts related to "other applicable requirements" are disclosed. This has generally been interpreted as VMT impacts and other State climate change objectives. These other applicable requirements may be found in other parts of an environmental document (i.e., air quality, GHG), or may be provided in greater detail in the transportation section.

For projects on the State highway system, Caltrans will use and will require sponsoring agencies to use VMT as the CEQA metric, and Caltrans will evaluate the VMT

"attributable to the project" (Caltrans Draft VMT-Focused Transportation Impact Study Guide, February 28, 2020). Caltrans'

Intergovernmental Review will review environmental documents for capacity-enhancing projects for the County's analysis of VMT change.

The assessment of a transportation project's VMT should disclose the VMT without the project and the difference in VMT with the project. According to the OPR TA and the County's Guidelines for Evaluating Vehicle Miles Traveled Under CEQA prepared by LSA Associates, Inc. (September 2020) any growth in VMT attributable to the transportation project would result in a significant impact.

The primary difference in these two scenarios (without the project and with the project) to OPR is related to induced growth. Current traffic models have limited abilities to forecast induced growth, as their land use or socioeconomic databases are fixed to a horizon date. OPR

In particular, the OPR TA presents one method to identify the induced growth. This method may be used in Orange County to estimate induced growth attributable to a new roadway capacity. To estimate VMT impacts from roadway expansion projects:

- 1. Determine the total lane-miles over an area that fully captures travel behavior changes resulting from the project (generally the region, but for projects affecting interregional travel look at all affected regions).
- 2. Determine the percentage change in total lane miles that will result from the project.
- 3. Determine the total existing VMT over that same area.
- 4. Multiply the percentage increase in lane miles by the existing VMT, and then multiply that by the elasticity from the induced travel literature:

[% increase in lane miles] x [existing VMT] x [elasticity] = [VMT resulting from the project]

It should be pointed out that OPR assigns this induced growth to induced land use.

As an alternative method, Caltrans has identified a computerized tool that estimates VMT generation from transportation projects. It was developed at the University of California, Davis, and is based on elasticities and the relationship of lane mile additions and growth in VMT. It uses Federal Highway Administration definitions of facility type and ascribes VMT increases to each facility. Output includes increases on million vehicle miles per year. Caltrans is investigating its use for all its VMT analyses of capital projects. It is available for use by local agencies and applicants, and the County may recommend utilization of this tool for calculations.

The TA provides other options to identify induced growth- and project-related VMT. These include:

- 1. Employ an expert panel. An expert panel could assess changes to land use development that would likely result from the project. This assessment could then be analyzed by the travel demand model to assess effects on vehicle travel. Induced vehicle travel assessed via this approach should be verified using elasticities found in the academic literature.
- 2. Adjust model results to align with the empirical research. If the travel demand model analysis is performed without incorporating projected land use changes resulting from the project, the assessed vehicle travel should be adjusted upward to account for those land use changes. The assessed VMT after adjustment should fall within the range found in the academic literature.
- 3. Employ a land use model, running it iteratively with a travel demand model. A land use model can be used to estimate the land use effects of a roadway capacity increase, and the traffic patterns that result from the land use change can then be fed back into the travel demand model. The land use model and travel demand model can be iterated to produce an accurate result.

The TA provides additional guidance, below:

Whenever employing a travel demand model to assess induced vehicle travel, any limitation or known lack of sensitivity in the analysis that might cause substantial errors in the VMT estimate (for example, model insensitivity to one of the components of induced VMT described above) should be disclosed and characterized, and a description should be provided on how it could influence the analysis results. A discussion of the potential error or bias should be carried into analyses that rely on the VMT analysis, such as greenhouse gas emissions, air quality, energy, and noise.

The threshold for significance for a capacity-enhancing roadway project is any additional VMT generated by the project either due to the increased roadway use or as a result of induced growth attributable to the project.

E. SIGNIFICANCE THRESHOLDS FOR LAND PLANS

In the TA, the OPR provided guidance on the treatment of CEQA traffic analyses for land use plans. The TA reiterates previous direction regarding individual land use assessments:

- Analyze the VMT outcomes over the full area over which the plan may substantively affect travel patterns (the definition of region).
- VMT should be counted in full rather than split between origins and destinations (the full impact of the project VMT)

The TA provides a single sentence as consideration for land use plans. It states, "A general plan, area plan, or community plan may have a significant impact on transportation if proposed new residential, office or retail land uses would in aggregate exceed the respective thresholds recommended above." This recommendation refers to 85 percent of the existing city or regional average, and no net gain for residential, office, and retail land uses.

OPR is recommending a focus on specific trip purposes (i.e., home-based trips for residential projects and work-based trips for office projects). Depending on the modeling

platform, at least four other trip types are recognized as contributors to large-scale plan-level analyses. Home-based origins will have interactions with other non-work-based destinations. Therefore, if home-based trips are the focus of a plan-level assessment, a great deal of VMT would not be accounted for in the estimation of total VMT.

To assess a land plan, use of a traffic-forecasting tool is recommended. The total VMT for the plan should be identified for all trip types and all potential VMT contributors within the plan area. Similar traffic model runs should be conducted for the existing base year and the horizon year with No Project.

Guidelines Section 15064.3(b)(4) states (in part) the following:

A lead agency has discretion to choose the most appropriate methodology to evaluate a project's vehicle miles traveled, including whether to express the change in absolute terms, per capita, per household, or in any other measure.

Therefore, the recommended methodology for conducting VMT assessments for land plans is to compare the existing VMT per capita for the land plan area with the expected horizon year VMT per service population (population and employment). The recommended target is to achieve a lower VMT per service population in the horizon year with the proposed land plan than occurs for the existing condition.

F.MITIGATION STRATEGIES

The applicant is required, per CEQA, to identify feasible mitigation to mitigate the impact created by the project, to a level that is less than significant. Attachment B list some ideas for potential mitigation strategies. This is not an exhaustive list of feasible mitigation measures that may be applied to the project. As in previous CEQA practice, the applicant/project proponent will be required to identify mitigation measures to reduce, avoid, or offset the specific project-related impacts identified in an individual environmental document. Thus, the applicant should submit other creative, feasible mitigation for their project. The mitigation measures suggested and the related VMT percentage reduction must be reviewed and either approved or rejected by the County.

If the mitigation measures mitigate the project impact to a less than significant level, no further analysis is required. If the project's VMT impact cannot be fully mitigated, the County may: 1) request the project be redesigned, relocated, or realigned to reduce the VMT impact, or 2) prepare an Environmental Impact Report (EIR) with Statement of Overriding Considerations (SOC) for the transportation impacts associated with the project. All feasible mitigation measures must be assigned to and carried out by the project, even if a SOC is prepared.

When a significant CEQA impact is identified according to the thresholds described above, the project proponent will be required to identify feasible mitigation measures in order to reduce, avoid, or offset the impact. Although previous vehicle LOS impacts could be mitigated with locations specific vehicle level of service improvements, VMT impacts likely require mitigation of regional impacts through more behavioral changes. Enforcement of mitigation measures will still be subject to the mitigation monitoring requirements of CEQA, as well as the regular land use police powers of the County. These measures can also be incorporated as a part of plans, policies, regulations, or project designs.

VMT mitigations are not necessarily physical improvements; rather, they are complex in nature and will significantly depend on changes in human behavior.

Mitigation Measures and Project Alternatives

Land Development Projects and Community/General Plans: Mitigations and project alternatives for VMT impacts have been suggested by the OPR and are included in the TA. VMT mitigation can be extremely diverse and can be classified under several categories such as land use/location, road pricing, transit improvements, commute trip reduction strategies, and parking pricing/policy. Improvements related to VMT reduction strategies have been quantified in sources such as the California Air Pollution Control Officers Association (CAPCOA) report Quantifying Greenhouse Gas Mitigation Measures (CAPCOA Green Book) and CARB sources and are generally presented in wide ranges of potential VMT reduction percentages.

VEHICLE MILES TRAVELED

Appendix B of the Guidelines for Evaluating Vehicle Miles Traveled Under CEQA (September 2020) provides a brief menu of the different potentially applicable VMT mitigation measures and project alternatives stated in the CAPCOA Green Book (only those strategies directly attributed to transportation) and the OPR TA for land development projects. This discussion does not present an exhaustive list of feasible mitigation measures that may be applied to a project. As in previous CEQA practice, the applicant/project proponent will be required to identify mitigation measures to the County to reduce, avoid, or offset the specific project-related impacts identified in an individual environmental document.

Transportation Projects: Although OPR provides detailed guidance on how to assess induced-growth impacts associated with transportation projects, it leaves the subject of mitigation measures vague. Only four strategies are suggested as mitigation measures:

- Tolling new lanes to encourage carpools and fund transit improvements
 Converting existing general-purpose lanes to HOV or HOT lanes
- Implementing or funding off-site travel demand management
- Implementing Intelligent Transportation Systems strategies to improve passenger throughput on existing lanes

ATTACHMENT A

COUNTY OF ORANGE: FAIR-SHARE FORMULA FOR TRAFFIC IMPACTS

One of the goals of the County's Transportation Element and the Growth Management Program is to ensure that new development pays its fair share for transportation improvements commensurate with the impacts created by said development. In order to ensure that a uniform method is applied to assess traffic impacts of each development, a Task Force consisting of representatives of the development community and traffic engineers was established to develop a fair share formula to assess traffic impacts of a development. The Task Force acknowledged that there was a need to establish not only a fair—share formula but also a procedure to implement it. The procedure should allow for flexibility in the implementation of any mitigation. After working for more than a year, the Task Force developed a fair share formula with the following goals and procedure. This fair-share formula is to be applied to all development in the County unincorporated areas.

Goals

- 1. It should be consistent with County's GMP in that it uses Intersection Capacity Utilization (ICU) methodology to identify impacted intersections and is consistent with the County's level of service (LOS) "D" policy
- 2. It should provide positive values not exceeding 100%.

Procedure

- 1. Identify intersections that will experience a significant adverse impact by a proposed project (> 1% change in AM or PM Peak hour LOS). This should be done by comparing the with and without project impact for the near-term and long-term horizon years pursuant to the County GMP. This analysis should use the ICU methodology.
- 2. Determine a project's share of the intersection improvement(s). This is based on a project's total trips approaching an intersection, in the peak hour most impacted, as a percentage of new trips (Future- Existing) at that location. To determine a project's

ATTACHMENT A

approach trips, at any location a 'select zone' analysis (modeled or manual) as appropriate, should be utilized.

- 3. Project proponent and the County shall cooperate in determining a feasible mitigation program and associated cost. The project's share of the mitigation cost shall be based on the cost of the mitigations needed to bring the intersection condition to LOS 'D' or better.
- 4. A cost cap of a project's total obligation should be established, once all the fair share mitigation costs of a project are determined.
- 5. County and project proponent shall cooperate in developing a mitigation implementation program. In recognition of possible operational and/or financial constraints of implementing an improvement at a specific location, the County and the project proponent can mutually agree on implementing an equivalent improvement, at another location impacted by the project, to satisfy the project's obligation.





GUIDELINES FOR EVALUATING VEHICLE MILES TRAVELED UNDER CEQA

for the COUNTY OF ORANGE

SEPTEMBER 17, 2020

FINAL

GUIDELINES FOR EVALUATING VEHICLE MILES TRAVELED UNDER CEQA

COUNTY OF ORANGE

Submitted to:

Joanna Chang Land Use Manager OC Public Works 601 North Ross Street Santa Ana, California 92701

Prepared by:

LSA 20 Executive Park, Suite 200 Irvine, California 92614 (949) 553-0666

Project No. OCY1701.19

TABLE OF CONTENTS

TABL	E OF	CONTENTS	i
FIGU	RES A	ND TABLES	iii
LIST	OF AE	BBREVIATIONS AND ACRONYMS	v
1.0	INTI	RODUCTION	1
2.0	DEF	INITION OF REGION: VEHICLE MILES TRAVELED CONTEXT AND	
	DET	ERMINING THE BASELINE	5
3.0	PRO	DJECT SCREENING	9
	3.1	Land Development Projects	9
	3.2	Transportation Projects	
4.0	SIGI	NIFICANCE THRESHOLDS FOR LAND DEVELOPMENT PROJECTS	17
	4.1	Summary	18
	4.2	Agency Communication	
	4.3	Project Screening	19
	4.4	Project VMT Analysis	19
		4.4.1 Medium Project VMT Analysis	19
		4.4.2 Large Project VMT Analysis	23
	4.5	Mitigation Measures	23
5.0	SIGI	NIFICANCE THRESHOLDS FOR TRANSPORTATION PROJECTS	25
6.0	SIGI	NIFICANCE THRESHOLDS FOR LAND PLANS	29
7.0	MIT	IGATION STRATEGIES	31
	7.1	Definition of Mitigation	31
	7.2	Mitigation Measures and Project Alternatives	
		7.2.1 Land Development Projects and Community/General Plans	
		7.2.2. Transportation Projects	32

APPENDICES

- A: TECHNICAL ADVISORY ON EVALUATING TRANSPORTATION IMPACTS IN CEQA (OPR, DECEMBER 2018)
- B: PROPOSED MITIGATION STRATEGIES FOR IMPLEMENTATION OF SB 743



ii

FIGURES AND TABLES

FIGURES

Figure 1: 2017 GHG Emissions in California by Scoping Plan Sector and Sub-Sector Category Figure 2: California Statewide Population and VMT Trends	
Figure 3: SCAG Region Total Number of Daily Walking Trips by Distance	
Figure 4: Orange County Transit Priority Areas	
Figure 5: Transportation Impacts Flow Chart for Development Projects	
TABLES	
Table A: County of Orange Unincorporated Vehicle Miles Traveled Data (Using OCTAM Base Year 2016)	6
Table B: Representative Vehicle VMT and GHG Emissions from CalFEMod	13



LIST OF ABBREVIATIONS AND ACRONYMS

ADT average daily trips

CalEEMod California Emissions Estimator Model

Caltrans California Department of Transportation

CAPCOA California Air Pollution Control Officers Association

CARB California Air Resources Board

CEQA California Environmental Quality Act

CO₂e carbon dioxide equivalent

County County of Orange

EO Executive Order

FAR floor-to-area ratio

Guidelines 2020 State CEQA Guidelines, 14 California Code of Regulations, Section

15000, et. seq.

GWP global warming potential

HOT high-occupancy toll

HOV high-occupancy vehicle

HQTA High-Quality Transit Area

LOS level of service

LRTP Long-Range Transportation Plan

mi mile

MT metric ton

MPO Metropolitan Planning Organizations

OCTAM Orange County Transportation Analysis Model

OPR Governor's Office of Planning and Research

PRC Public Resources Code

RTP/SCS Regional Transportation Plan/Sustainable Communities Strategy

RTPA Regional Transportation Planning Agency

SB Senate Bill

SCAG Southern California Association of Government

SOC Statement of Overriding Considerations

TA Technical Advisory

TDM transportation demand management

TPA Transit Priority Area

TSP Transit Signal Priority

VMT vehicle miles traveled

1.0 INTRODUCTION

Senate Bill (SB) 743, signed in 2013, changed the way transportation studies are conducted in California Environmental Quality Act (CEQA) documents. Vehicle miles traveled (VMT) replaces motorist delay and level of service (LOS) as the metric for impact determination. For land development projects, VMT is simply the product of the daily trips generated by a new development and the distance those trips travel to their destinations. For capital projects, impacts are identified as the new VMT attributable to the added capital project, both from the installation of the facility and the induced growth.

This document serves as a guide for application and substantial evidence for the County of Orange's (County) adopted project screenings, significance thresholds, and mitigation strategies, modeled after the Governor's Office of Planning and Research's (OPR) Technical Advisory (TA) for CEQA transportation studies; however, as in previous CEQA practice, the applicant/project proponent will still be required to provide traffic analysis that is specific to the proposed project to be reviewed and approved by the County.¹ These guidelines apply to all projects for which the County is the Lead Agency for certification or adoption of CEQA documents. If the County is the Lead Agency, but the project is located in another jurisdiction, these guidelines would apply. However, if the County is not the Lead Agency, and the project is located in another jurisdiction, the Lead Agency would determine which VMT guidelines should be used for analysis.

In January 2019, the Natural Resources Agency and the OPR codified SB 743 into the Public Resources Code (PRC) and the *State CEQA Guidelines*.

The State CEQA Guidelines, included in Title 14 of the California Code of Regulations, Section 15064.3 subdivision (b)—hereafter referred to as the Guidelines—states the following criteria for analyzing transportation impacts:

- 1. Land Use Projects. Vehicle miles traveled exceeding an applicable threshold of significance may indicate a significant impact. Generally, projects within one-half mile of either an existing major transit stop or a stop along an existing high quality transit corridor should be presumed to cause a less than significant transportation impact. Projects that decrease vehicle miles traveled in the project area compared to existing conditions should be presumed to have a less than significant transportation impact.
- 2. Transportation Projects. Transportation projects that reduce, or have no impact on, vehicle miles traveled should be presumed to cause a less than significant transportation impact. For roadway capacity projects, agencies have discretion to determine the appropriate measure of transportation impact consistent with CEQA and other applicable requirements. To the extent that such impacts have already been adequately addressed at a programmatic level, such as in a


The County will review Public Resources Code Section 21166 to determine whether VMT analysis is required for the later-prepared environmental documents, including subsequent and supplemental EIRs and addendums. Absent facts or legal requirements to the contrary, the County will not, as a matter of course, require VMT analysis for later-prepared documents. (See, e.g., *CREED v. San Diego* [2011] 196 Cal. App. 4th 515; *Concerned Dublin Citizens v. City of Dublin* [2013] 214 Cal. App. 4th 1301, 1320.)

regional transportation plan EIR, a lead agency may tier from that analysis as provided in Section 15152.

- **3. Qualitative Analysis.** If existing models or methods are not available to estimate the vehicle miles traveled for the particular project being considered, a lead County may analyze the project's vehicle miles traveled qualitatively. Such a qualitative analysis would evaluate factors such as the availability of transit, proximity to other destinations, etc. For many projects, a qualitative analysis of construction traffic may be appropriate.
- 4. Methodology. A lead agency has discretion to choose the most appropriate methodology to evaluate a project's vehicle miles traveled, including whether to express the change in absolute terms, per capita, per household, or in any other measure. A lead agency may use models to estimate a project's vehicle miles traveled, and may revise those estimates to reflect professional judgment based on substantial evidence. Any assumptions used to estimate vehicle miles traveled and any revisions to model outputs should be documented and explained in the environmental document prepared for the project. The standard of adequacy in Section 15151 shall apply to the analysis described in this section.


The OPR provides a TA (see Appendix A) as a guidance document to establish thresholds under this new VMT metric. The laws and rules governing the CEQA process are contained in the CEQA statute (PRC Section 21000 and following), the Guidelines (California Code of Regulations, Title 14, Section 15000 and following), published court decisions interpreting CEQA, and locally adopted CEQA procedures. The TA is intended as a reference document; it does not have the weight of law, but is intended by OPR to provide substantial evidence for the thresholds proposed therein. Thus, deviating from the TA is best undertaken with substantial evidence to support the County action.

The State of California has committed to reducing greenhouse gas (GHG) emissions and achieving long-term climate change goals. To achieve these climate change goals, the State has determined that overall VMT needs to be reduced. As Figure 1 shows, transportation is the single largest sector contributing to the State's GHG emissions. More than 40 percent of the GHG emissions come from the transportation sector, primarily passenger cars and light-duty trucks. According to the State, removing these vehicle trips and/or reducing the length of existing trips is expected to result in reduced VMT and reduced GHG emissions. As illustrated in Figure 2, over the last 40 years, VMT has grown faster than population growth. According to the OPR and the State, the new Guidelines and the establishment of VMT thresholds for CEQA analyses are linked to GHG reduction strategies and overall statewide climate change goals.



Source: California Greenhouse Gas Emissions for 2000 to 2017 Trends of Emissions and Other Indicators (California Air Resources Board Report)

Figure 1: 2017 GHG Emissions in California by Scoping Plan Sector and Sub-Sector Category



Source: https://ca50million.ca.gov/transportation/

Figure 2: California Statewide Population and VMT Trends

The State and the Southern California Association of Governments (SCAG), the metropolitan planning organization for Southern California, have provided guidance that the number of vehicle trips and the length of vehicle trips can be reduced by locating new development near available transit and a mix of other land uses. This is one example of a strategy to reduce project related VMT. SB 743 is intended to promote infill development, encourage multimodal transportation networks, and reduce GHG emissions.



In one example, SCAG's Draft Regional Transportation Plan/Sustainable Communities Strategy (RTP/SCS) (SCAG 2019) includes data showing that the number of walking trips greatly diminishes for distances longer than 2 miles (Figure 3). If a person's destination or a transit station are within 2 miles of a person's home, the person may choose a non-vehicle travel mode.

This document provides a guide for application and substantial evidence for the County's adopted thresholds of significance, modeled after OPR's suggestions, for CEQA transportation studies. It is divided into chapters, including:



Sources: SCAG Connect Socal: The 2020-2045 RTP/SCS Active Transportation Technical Appendix, Page 30; California Household Travel Survey (2012).

- Chapter 2 Definition of Region: Here, the document describes what the comparative region is for analysis purposes. Each project will be compared to an existing regional average. The geographical area that defines the region is defined and described.
- Chapter 3 Project Screening: This chapter provides criteria, and, where applicable, substantial evidence for screening out certain types of projects that, by their nature, or by virtue of other factors, would result in less than significant transportation impacts. This is consistent with the OPR's acknowledgment that certain projects are either low VMT generators, or by virtue of their location would have a less than significant impact.
- Chapter 4 Significance Thresholds for Land Development Projects: In this chapter, the
 threshold that would define a significant CEQA impact for land use projects is identified. This
 threshold is linked to a specific travel mode and a set of trip purposes. The actual VMT metric
 (either an efficiency rate or total VMT) is described.
- Chapter 5 Significant Thresholds for Transportation Projects: This chapter describes the
 method to evaluate significant CEQA impacts associated with transportation projects. Many
 non-vehicular capital projects are presumed to have a less than significant impact. Capacityenhancing projects may have significant impacts and will be subject to a detailed analysis that
 will include measuring induced travel.
- Chapter 6 Significance Thresholds for Land Plans: This chapter provides guidance and substantial evidence to support the County's treatment of land use plans and their CEQA transportation analysis.
- Chapter 7 Mitigation Strategies: This chapter provides examples of potential mitigation strategies. It is noted that this discussion does not present an exhaustive list of feasible mitigation measures that may be applied to a project. As in previous CEQA practice, the applicant/project proponent will be required to identify mitigation measures to reduce, avoid, or offset the specific project-related impacts identified in an individual environmental document.

2.0 DEFINITION OF REGION: VEHICLE MILES TRAVELED CONTEXT AND DETERMINING THE BASELINE

The question of context defines the scope of the VMT analysis. The common term for this in previous delay-based LOS analyses is *project study area*. In the delay-based LOS analyses, a project study area is generally determined based on the incremental increase in traffic from the project and its potential to create a significant LOS impact. This generally includes intersections and roadway segments where the project would add a prescribed number of peak-hour trips. Many times, lead agencies stop study area boundaries at their jurisdictional borders.

Based on the evidence and analysis provided below, the "Region" for Orange County is the entire county area.

Region is not defined in the TA. Instead, the OPR offers the following suggestions:

In cases where the region is substantially larger than the geography over which most workers would be expected to live, it might be appropriate to refer to a smaller geography, such as **county**, that includes the area over which nearly all workers would be expected to live (page 16).

1. For residential projects in unincorporated county areas, the local County can compare a residential project's VMT to (1) the region's VMT per capita, or (2) the aggregate population weighted VMT per capita of all cities in the region.

The TA bases recommendations for thresholds for the primary land use types (residential and office) on a comparison to a *regional average*. The County will utilize the region's VMT per capita approach. The OPR guidance recommends consistency in approach; once a region is established, that region should be used for all subsequent traffic analyses.

Other large or urbanized areas around the State have been surveyed to identify what region has been established for VMT thresholds. In most cases, the county boundary has been identified as the region selected for VMT analysis. In some cases, this county boundary has other names, such as the Council of Governments boundary.

County is a common and reoccurring context for CEQA VMT analyses throughout the State. According to the Orange County Transportation Analysis Model (OCTAM 5.0), of the total trips in and out of Orange County, about 21 percent originate and are destined within the unincorporated county area. Another 67 percent of trips originate or are destined within the municipal jurisdictions (cities) in Orange County. The remaining 12 percent of Orange County trips have a trip end in the other counties of the SCAG region or beyond. Because the majority of the unincorporated county trips are contained within the entirety of Orange County (approximately 88 percent) and many other large urbanized areas are defining their region as their counties, the use of Orange County in its entirety is defined as the region for CEQA land development transportation analyses.



Table A: County of Orange Unincorporated Vehicle Miles Traveled Data (Using OCTAM Base Year 2016)

Table 1 - San Diego Trips

Region	Total Trips	Trips to/from San Diego	Percent San Diego Trips
Unincorporated Orange County	668,689	3,165	0.5%
Total Orange County (including			
unincorporated Orange)	19,004,260	69,830	0.4%

Table 2 - Percent County of Orange Trips with Orange County as region

Trips within Unincorporated Orange County	
+ Trips between Unincorporated and	
Incorporated Orange County	525,288
Total Trips within Entire Orange County	
(Internal - Internal)	8,559,626
Percent County of Orange Trips within	
Orange County	6.1%

Table 3 - Percent County of Orange Trips with Orange County + 10 mile buffer as region

Trips within Unincorporated Orange County	
+ Trips between Unincorporated and	
Incorporated Orange County, and 10-mile	
buffer around Orange County (parts of LA,	
Riverside, and San Bernadino County)	575,922
Total Trips within Entire Orange County + 10-	
Mile Buffer around Orange County (Internal -	
Internal)	14,800,711
Percent County of Orange Trips within	
Orange County + 10-mile Buffer	3.9%

Table 3a - Percent County of Orange Trips with Orange County + 10 mile buffer as region

Total Trips to/from Entire Orange County	
(includes unincorporated Orange County +	
external trips)	9,451,544
Trips within Entire Modeling area (Orange,	
LA, Ventura, Riverside, and San Bernadino	
Counties + External Stations)	48,342,620
Percent Orange County Trips in Entire	
Modeling Area	19.6%

Table 4 - VMT Per Capita

Region	Total Homebased VMT	Total Household Population	VMT/Capita
Unincorporated Orange County	3,477,242	145,121	24.0
Total Orange County (including			
unincorporated Orange)	56,757,571	3,179,626	17.9
Total Orange County + Part LA, Riverside,			
and SB Counties (10 miles from county			
boundary)	116,115,946	6,241,508	18.6

Table 5 - VMT Per Employee

	Total Homebased		
Region	Work VMT	Total Employment	VMT/Employee
Unincorporated Orange County	1,348,364	33,312	40.5
Total Orange County (including			
unincorporated Orange)	41,174,971	1,710,147	24.1
Total Orange County + Part LA, Riverside,			
and SB Counties (10 miles from county			
boundary)	66,768,783	2,766,068	24.1

Source: OCTAM5 Base Year model run (2016)

It should be recognized the use of Orange County as the region defines the comparative (i.e., baseline), or the denominator, in the identification of project-related impact. The numerator is the project's VMT contribution. The project-related/generated VMT profile may go beyond the county boundary and not be truncated by a jurisdictional boundary. For example, a new, large land development proposed near Orange County's eastern boundary may include VMT from as far away as Corona or other communities in Riverside and San Bernardino counties. In that case, it would be the responsibility of the applicant and their traffic study preparer to include the project VMT, regardless of geographical limit, to the satisfaction of the County staff. This project-related VMT profile would be compared against the County regional baseline.

Unlike delay-based LOS analyses, VMT is a regional effect not defined by roadway, intersection, or pathway. The OPR acknowledges this in its TA (page 6), which states,

Lead agencies should not truncate any VMT analysis because of jurisdictional or other boundaries by failing to count the portion of a trip that falls outside the jurisdiction or by discounting the VMT from a trip that crosses a jurisdictional boundary.

Table A is used as the current 2020 calculations to demonstrate what calculations should be applied. Tables 2, 4, and 5, in Table A identify the relevant VMT baselines for the region. These baselines will be revised as the OCTAM is revised beyond version 5.0. Applicants should use the most up-to-date version of the OCTAM in setting the baseline and analyzing their project.²

² CEQA allows, variances to the baseline may be presented as part of the methodology for review and approval to the County by project applicants pursuant to CEQA Guidelines Section 15064.3(b)(4). Such alternate baselines must be supported by substantial evidence as defined by Section 15384(b) of the CEQA Guidelines.



3.0 PROJECT SCREENING

The TA acknowledges that certain activities and projects may result in a less than significant impact to transportation and circulation. A variety of projects may be screened out of a complicated VMT analysis due to the presumption described in the TA regarding the occurrence of less than significant impacts.

3.1 Land Development Projects

The TA acknowledges that conditions may exist under which a land development project would have a less than significant impact on transportation and circulation. These may be size, location, proximity to transit, or trip-making potential.

Land development projects that have one or more of the following attributes may be presumed to create a less than significant impact on transportation and circulation.

• Project in High-Quality Transit Area (HQTA): The project is within 0.5 mile (mi) of a Transit Priority Area (TPA) or an HQTA, unless the project is inconsistent with the RTP/SCS, has a floor-to-area ratio (FAR) less than 0.75, provides an excessive amount of parking, or reduces the number of affordable residential units. In accordance with SB 743, "Transit priority areas" are defined as "an area within one-half mile of a major transit stop that is existing or planned, if the planned stop is scheduled to be completed within the planning horizon included in a Transportation Improvement Program. A Major Transit Stop means: "a site containing an existing rail transit station, a ferry terminal served by either a bus or rail transit service, or the intersection of two or more major bus routes with a frequency of service of 15 minutes or less during the morning and afternoon peak commute periods." An HQTA or Corridor is a corridor with fixed route bus service with service intervals no longer than 15 minutes during peak commute hours.


Figure 4 depicts TPAs within unincorporated Orange County³, including HQTA corridors served by the Orange County Transportation Authority with service intervals of 15 minutes or less and major transit stops along the Metrolink⁴ system. Although the figure shows the San Clemente Pier Metrolink station, it does not qualify as a major transit stop because service is limited to weekends. Projects proposed in these areas would be presumed to have a less than significant transportation impact unless the project is inconsistent with the RTP/SCS, has an FAR less than 0.75, provides an excessive amount of parking, or reduces the number of affordable residential units.


- Neighborhood Retail Project: The project involves local-serving retail space of less than 50,000 square feet.
- Affordable Housing Project: The project is 100 percent affordable-housing units.

⁴ Amtrak runs along Metrolink's Orange County route and stops at many Orange County Metrolink stations.



Figure 4 may be updated periodically as necessary.





- Low VMT Area⁵ Project: The project is in low VMT areas. The applicant may submit data from the most recent OCTAM version showing the proposed project is within a low VMT area, which may be used, at the discretion of staff, to screen out the project.
- Small Project: A project generates 500 or fewer average daily trips (ADT). The TA recommends a volume of 110 ADT as the low volume that would allow the project to be screened out. This recommendation is not based on any analysis of GHG reduction, but was instead based on the potential trip generation of an office project that would already be categorically exempt under CEQA. LSA prepared a deeper analysis and used the California Emissions Estimator Model (CalEEMod, version 2016.3.2) to correlate the effect of changes in project-related ADT to the resulting GHG emissions. This model was selected because it is provided by the California Air Resources Board (CARB) to be used statewide for determining project-level GHG emissions. CalEEMod was used with the built-in default trip lengths and types to show the vehicular GHG emissions from incremental amounts of ADT. Table B shows the resulting annual VMT and GHG emissions from the incremental ADT.

Table B: Representative Vehicle VMT and GHG Emissions from CalEEMod

Average Daily Trips	Annual Vehicle Miles Traveled	GHG Emissions (metric tons CO₂e per year)
200	683,430	258
300	1,021,812	386
400	1,386,416	514
500	1,703,020	643
600	2,043,623	771

Source: CalEEMod version 2016.3.2. Example project used: 50 single-family Homes in Orange County.

CalEEMod = California Emissions Estimator Model

CO₂e = carbon dioxide equivalent

GHG = greenhouse gas

A common GHG emissions threshold is 3,000 metric tons (MT) of carbon dioxide equivalent⁶ (CO_2e) per year. Vehicle emissions are typically more than 50 percent of the total project GHG emissions. Thus, a project with 500 ADT would generally have total project emissions that could be less than 1,300 MT CO_2e /year (i.e., 50 percent or 643 MT CO_2e /year coming from vehicle emissions and the other 50 percent coming from other project activities). As this level of GHG

⁶ Carbon dioxide equivalent (CO₂e) is a concept developed to provide one metric that includes the effects of numerous GHGs. The global warming potential (GWP) of each GHG characterizes the ability of each GHG to trap heat in the atmosphere relative to another GHG. The GWPs of all GHGs are combined to derive the CO₂e.



Orange County's land area may be described in terms of low, medium and high VMT areas based on thresholds described in Chapter 4. These descriptions are Low: less 85 percent of the regional average; Medium: equal to or more than 85 percent of the regional average and less than or equal to 117 percent of regional average; and High: greater than 117 percent of regional average.

emissions would be less than 3,000 MT CO₂e/year, the emissions of GHG from a project up to 500 ADT would typically be less than significant.

The County's current Transportation Implementation Manual establishes screening criteria of 200 ADT. However, based on the analysis in Table B, projects with fewer than 500 ADT are unlikely to result in significant impacts.

Based on this qualitative analysis, the County establishes screening criteria for small projects of up to 500 ADT.

• Public Facilities: The development of institutional/government and public service uses that support community health, safety or welfare are also screened from subsequent CEQA VMT analysis. The following includes some examples and is not an exhaustive list of public facilities that are screened from subsequent CEQA VMT analysis: police/sheriff stations, fire stations, community centers, refuse stations, jails, and landfills. These facilities are already part of the community and, as a public service, the VMT is accounted for in the existing regional average. Many of these facilities also generate fewer than 500 ADT and/or use vehicles other than passenger-cars or light duty trucks. These other vehicle fleets are subject to regulation outside of CEQA, such as CARB and the South Coast Air Quality Management District.

3.2 Transportation Projects

The primary attribute to consider with transportation projects is the potential to increase vehicle travel. While the County has discretion to continue to use delay analysis for CEQA disclosure of transportation projects, changes in vehicle travel must also be quantified.

The TA lists a series of projects that would not likely lead to a substantial or measurable increase in vehicle travel and that, therefore, would generally not require an induced travel analysis. The current list of projects, which is not intended to be exhaustive, includes the following examples:

- Rehabilitation, maintenance, replacement, safety, and repair projects designed to improve the
 condition of existing transportation assets (e.g., highways; roadways; bridges; culverts;
 Transportation Management System field elements such as cameras, message signs, detection,
 or signals; tunnels; transit systems; and assets that serve bicycle and pedestrian facilities) and
 that do not add additional motor vehicle capacity
- Roadside safety devices or hardware installation such median barriers and guardrails
- Roadway shoulder enhancements to provide "breakdown space," dedicated space for use only
 by transit vehicles, to provide bicycle access, or to otherwise improve safety, but which will not
 be used as automobile vehicle travel lanes
- Addition of an auxiliary lane of less than 1 mile in length designed to improve roadway safety

- Installation, removal, or reconfiguration of traffic lanes that are not for through traffic, such as left-, right-, and U-turn pockets, two-way left-turn lanes, or emergency breakdown lanes that are not utilized as through lanes
- Addition of roadway capacity on local or collector streets, provided the project also substantially improves conditions for pedestrians, cyclists, and, if applicable, transit
- Conversion of existing general-purpose lanes (including ramps) to managed lanes or transit lanes, or changing lane management in a manner that would not substantially increase vehicle travel
- Addition of a new lane that is permanently restricted to use only by transit vehicles
- Reduction in the number of through lanes
- Grade separation to separate vehicles from rail, transit, pedestrians, or bicycles, or to replace a
 lane in order to separate preferential vehicles (e.g., high-occupancy vehicles [HOVs], highoccupancy toll [HOT] lane traffic, or trucks) from general vehicles
- Installation, removal, or reconfiguration of traffic control devices, including Transit Signal Priority (TSP) features
- Installation of traffic metering systems, detection systems, cameras, changeable message signs, and other electronics designed to optimize vehicle, bicycle, or pedestrian flow
- Timing of signals to optimize vehicle, bicycle, or pedestrian flow
- Installation of roundabouts or traffic circles
- Installation or reconfiguration of traffic calming devices
- Adoption of or increase in tolls
- Addition of tolled lanes, where tolls are sufficient to mitigate VMT increase
- Initiation of a new transit service
- Conversion of streets from one-way to two-way operation with no net increase in the number of traffic lanes
- Removal or relocation of off-street or on-street parking spaces
- Adoption or modification of on-street parking or loading restrictions (including meters, time limits, accessible spaces, and preferential/reserved parking permit programs)
- Addition of traffic wayfinding signage



- Rehabilitation and maintenance projects that do not add motor vehicle capacity
- Addition of new or enhanced bike or pedestrian facilities on existing streets/highways or within existing public rights-of-way
- Addition of Class I bike paths, trails, multi-use paths, or other off-road facilities that serve nonmotorized travel
- Installation of publicly available alternative fuel/charging infrastructure
- Addition of passing lanes, truck climbing lanes, or truck brake-check lanes in rural areas that do not increase overall vehicle capacity along the corridor

Additionally, transit and active transportation projects generally reduce VMT and are, therefore, presumed to cause a less than significant impact on transportation. This presumption may apply to all passenger rail projects, bus and bus rapid-transit projects, and bicycle and pedestrian infrastructure projects.

If the proposed project is consistent with the build out of the Orange County Master Plan of Arterial Highways (MPAH) network, then the project may have a less than significant impact.

4.0 SIGNIFICANCE THRESHOLDS FOR LAND DEVELOPMENT PROJECTS

The TA states that SB 743 and all CEQA VMT transportation analyses refer to automobiles. Here, the term automobile refers to on-road passenger vehicles, specifically cars and light-duty trucks (page. 4). Heavy-duty trucks can be addressed in other CEQA sections and are subject to regulation in a separate collection of rules under CARB jurisdiction. This approach was amplified by Chris Ganson, Chief Planner at OPR in a recent presentation at the Fresno Council of Governments (October 23, 2019) and by Ellen Greenberg, California Department of Transportation (Caltrans) Deputy Director for Sustainability, at the San Joaquin Valley Regional Planning Association meeting (January 9, 2020).

The OPR has identified the subject of the thresholds as the primary trips in the home-based typology: specifically, home-based work trips. This includes residential uses, office uses, and retail uses. The home-based work trip type is the primary tripmaking during the peak hours of commuter traffic in the morning and evening periods.

The focus of analyzing transportation impacts has shifted from congestion to climate change, and the purpose of the CEQA analysis is to disclose and ultimately reduce GHG emissions by reducing the number and length of automobile trips. This change in CEQA analysis does not diminish the County's ability to require an LOS analysis to confirm accessibility to a project site, conformance with General Plan policies, or as a function of their general health, safety, and welfare discretion and authority. As part of the SB 375 land use/transportation integration process and the GHG goal setting, most metropolitan planning organizations and regional transportation planning agencies have agreed to reduce GHG through integrated land use and transportation planning by approximately 15 percent by 2035. Furthermore, in its 2017 Scoping Plan-Identified VMT Reductions and Relationship to State Climate Goals, the CARB recommends total VMT per capita rates approximately 15 percent below existing conditions.

The TA therefore recommends:

A proposed (residential) project exceeding a level of 15 percent below existing regional average VMT per capita may indicate a significant transportation impact.

A similar threshold would apply to office projects (15 percent below existing regional average VMT per employee).

VMT generated by retail projects would indicate a significant impact for any net increase in total VMT.

While regional planning documents such as the RTP/SCS calculate a single VMT rate by dividing total VMT for the SCAG region by the total service population, it should be noted that the TA identifies a different denominator for the residential and office comparison rates. If regional average VMT per capita and VMT per employee were calculated using the service population (population plus employment), the denominator would be the same, which would be inconsistent with the TA. Furthermore, using service population to calculate regional average rates would complicate future project analyses.



The environmental document for a proposed land use project will identify population for a residential project and employment for an office project. These values should be used in the transportation analysis to calculate the project's VMT per capita or VMT per employee. If a project's VMT per capita (VMT/project population) or VMT per employee (VMT/project employment) is compared to a regional average based on service rate (VMT/[regional population + employment]), the comparison is not equivalent.

According to the Orange County Transportation Authority calculations using OCTAM 5.0, the average VMT/capita in Orange County is 17.9. The average VMT/employee in Orange County is 24.1.

Mixed-use projects should be evaluated for each component of the project independently, or the County may use the predominant land use type for the analysis. Credit for internal trip capture should be accounted for. No discrete land use types other than residential, office, or retail are identified for threshold development in the TA.

The TA suggests that the County may, but is not required to, develop thresholds for any other use. One approach is to review the County General Plan and/or Countywide Long-Range Transportation Plan (LRTP) and identify whether the implementation of the plan would result in a reduction of VMT and GHGs. If it does, the County may conclude the implementation of the plan, including all the other land use types to achieve the regional climate change goals. Therefore, consistency with the plan and no net change in VMT per employee is a rational threshold for the other land use types. This approach would require disclosure of substantial evidence, including the General Plan or LRTP findings, and other supporting traffic and air quality forecasting support.

4.1 Summary

In summary, the County's thresholds of significance for the following land uses are:

- Residential 15 percent below existing regional average VMT per capita (17.9 X 0.85 = 15.2)
- Office 15 percent below existing regional average VMT per employee (24.1 X 0.85 = 20.5)
- Retail no net change in total VMT
- **Mixed Use:** consider each component of the project separately based on the threshold for residential, office, retail, etc. and take credit for internal capture
- Other Land Uses no net change in VMT per employee if consistent with the General Plan or 15 percent below regional average if seeking a General Plan Amendment

Figure 5 demonstrates the potential land development entitlement process to comply with the Guidelines related to VMT and transportation impacts. It provides the path from application filing through determination of impacts. It is presented as the standard process; each development application is considered unique and may create alternative or modified steps through the process. Each step that diverges from this standard process should be accompanied with substantial

evidence demonstrating compliance with other climate change and GHG emission reduction laws and regulations.

4.2 Agency Communication

At the outset of the project development process, the applicant should seek a meeting with County staff to discuss the project description, the transportation study content, and the analysis methodology. Key elements to address include describing the project in sufficient detail to generate trips and identify the potential catchment area (i.e., trip lengths, if no modeling is being undertaken), estimating project VMT, discussing project design features that may reduce the VMT from the project development, and discussing the project location and associated existing regional VMT percentages. As a result of the meeting, the applicant or their consultant shall prepare a transportation analysis scope of work for review and approval by the County.

4.3 Project Screening

Once a development application is filed, project screening is conducted as the initial step. If the project meets any one of the screening criteria for VMT, the project may be presumed to create a less than significant impact in the area of transportation and circulation and no further analysis as to this topical environmental area is necessary. The CEQA document should enumerate the screening criteria and how the project meets or exceeds that threshold. If project screening does not apply, a VMT analysis may be required, in accordance with CEQA. The extent of this analysis may be a simple algebraic demonstration or a more sophisticated traffic modeling exercise.


4.4 Project VMT Analysis

The first step is to identify the project land use type and the appropriate efficiency rate to use. If the project is residential, use the per capita (or residential population) efficiency rate. If the project is commercial office (or a similar trip generator), use the per employee efficiency rate. For retail projects, use the total VMT generated by the project. For mixed use projects, report each land use after generating trips, taking credit for internal trip capture, to arrive at the VMT. As an alternative, the predominant use may be reported for mixed-use projects. For all other uses, use the VMT per employee as the comparative.

4.4.1 Medium Project VMT Analysis

For medium-sized projects (projects generating greater than 500 ADT but less than 1,000 ADT) or those with one predominant use, the determination of project VMT may be identified manually as the product of the daily trip generation (land use density/intensity multiplied by the County-approved trip generation rates, usually the ITE Trip Generation Manual) and the trip length in miles for that specific land use. Trip lengths can be found in other related air quality tools, such as CalEEMod, or may be derived from OCTAM.

20



22

4.4.2 Large Project VMT Analysis

For large or multi-use projects, use of the OCTAM traffic forecasting tool is required. For purposes of County review, a project generating 1,000 ADT or more should use the OCTAM traffic forecasting tool. At this level of trip generating, the probability of trip fulfilment expands to an area greater than the immediate project location and may include a greater regional attraction. The OCTAM traffic forecasting tool can more accurately define the select links used and the total VMT generated by the project.

Next, the project generated efficiency rate, or total VMT, depending on project type, is compared to the appropriate significance threshold. This is either 85 percent of the existing regional average per capita or employment (for the County) for residential and office uses, or no net increase in total VMT for retail or other uses that are consistent with the General Plan. For those projects that require a General Plan Amendment, 85 percent of existing regional average is appropriate, as the project has yet to be evaluated as part of the County's ultimate land development vision.

If the project VMT (expressed as a per capita or per employee rate or total number) is at or less than the significance threshold, the project is presumed to create a less than significant impact. No further analysis is required. If the project is greater than the significance threshold, mitigation measures are required.

4.5 Mitigation Measures

The applicant is required, per CEQA, to identify feasible mitigation to mitigate the impact created by the project, to a level that is less than significant. Appendices A and B list some ideas for potential mitigation strategies. This is not an exhaustive list of feasible mitigation measures that may be applied to the project. As in previous CEQA practice, the applicant/project proponent will be required to identify mitigation measures to reduce, avoid, or offset the specific project-related impacts identified in an individual environmental document. Thus, the applicant should submit other creative, feasible mitigation for their project. The mitigation measures suggested and the related VMT percentage reduction must be reviewed and either approved or rejected by the County.

If the mitigation measures mitigate the project impact to a less than significant level, no further analysis is required. If the project's VMT impact cannot be fully mitigated, the County may: 1) request the project be redesigned, relocated, or realigned to reduce the VMT impact, or 2) prepare a Statement of Overriding Considerations (SOC) for the transportation impacts associated with the project. All feasible mitigation measures must be assigned to and carried out by the project, even if a SOC is prepared.

This page intentionally left blank

24

5.0 SIGNIFICANCE THRESHOLDS FOR TRANSPORTATION PROJECTS

Section 15064.3.b.(2) of the Guidelines reads in part:

For roadway capacity projects, agencies have the discretion to determine the appropriate measure of transportation impact consistent with CEQA and other applicable requirements.

The County may continue to use delay and LOS for transportation projects as long as impacts related to "other applicable requirements" are disclosed. This has generally been interpreted as VMT impacts and other State climate change objectives. These other applicable requirements may be found in other parts of an environmental document (i.e., air quality, GHG), or may be provided in greater detail in the transportation section.

For projects on the State highway system, Caltrans will use and will require sponsoring agencies to use VMT as the CEQA metric, and Caltrans will evaluate the VMT "attributable to the project" (Caltrans Draft VMT-Focused Transportation Impact Study Guide, February 28, 2020). Caltrans' Intergovernmental Review will review environmental documents for capacity-enhancing projects for the County's analysis of VMT change.

The assessment of a transportation project's VMT should disclose the VMT without the project and the difference in VMT with the project. According to the TA, any growth in VMT attributable to the transportation project would result in a significant impact.

The primary difference in these two scenarios (without the project and with the project) to OPR is related to induced growth. Current traffic models have limited abilities to forecast induced growth, as their land use or socioeconomic databases are fixed to a horizon date. OPR refers to a limited set of reports that would indicate elasticities. The most recent major study (Duranton & Turner 2011, p. 24) estimates an elasticity of 1.0, meaning that every 1 percent change in lane miles results in a 1 percent increase in VMT.

The TA presents one method to identify the induced growth, as shown below. This method may be used in Orange County to estimate induced growth attributable to new roadway capacity.

To estimate VMT impacts from roadway expansion projects:

- Determine the total lane-miles over an area that fully captures travel behavior changes resulting from the project (generally the region, but for projects affecting interregional travel look at all affected regions).
- 2. Determine the percentage change in total lane miles that will result from the project.
- 3. Determine the total existing VMT over that same area.
- 4. Multiply the percentage increase in lane miles by the existing VMT, and then multiply that by the elasticity from the induced travel literature:

[% increase in lane miles] x [existing VMT] x [elasticity] = [VMT resulting from the project]



It should be pointed out that OPR assigns this induced growth to induced land use.

As an alternative method, Caltrans has identified a computerized tool that estimates VMT generation from transportation projects. It was developed at the University of California, Davis, and is based on elasticities and the relationship of lane mile additions and growth in VMT. It uses Federal Highway Administration definitions of facility type and ascribes VMT increases to each facility. Output includes increases on million vehicle miles per year. Caltrans is investigating its use for all its VMT analyses of capital projects. It is available for use by local agencies and applicants, and the County may recommend utilization of this tool for calculations.

The TA provides other options to identify induced growth- and project-related VMT. These include:

- 1. Employ an expert panel. An expert panel could assess changes to land use development that would likely result from the project. This assessment could then be analyzed by the travel demand model to assess effects on vehicle travel. Induced vehicle travel assessed via this approach should be verified using elasticities found in the academic literature.
- 2. Adjust model results to align with the empirical research. If the travel demand model analysis is performed without incorporating projected land use changes resulting from the project, the assessed vehicle travel should be adjusted upward to account for those land use changes. The assessed VMT after adjustment should fall within the range found in the academic literature.
- 3. Employ a land use model, running it iteratively with a travel demand model. A land use model can be used to estimate the land use effects of a roadway capacity increase, and the traffic patterns that result from the land use change can then be fed back into the travel demand model. The land use model and travel demand model can be iterated to produce an accurate result.

The TA provides additional guidance, below:

Whenever employing a travel demand model to assess induced vehicle travel, any limitation or known lack of sensitivity in the analysis that might cause substantial errors in the VMT estimate (for example, model insensitivity to one of the components of induced VMT described above) should be disclosed and characterized, and a description should be provided on how it could influence the analysis results. A discussion of the potential error or bias should be carried into analyses that rely on the VMT analysis, such as greenhouse gas emissions, air quality, energy, and noise.

The threshold for significance for a capacity-enhancing roadway project or new roadway project is any additional VMT generated by the project either due to the increased roadway use or as a result of induced growth attributable to the project.⁷

Long-term effects may include induced growth due to more desirable travel opportunities and/or increased land development and new trip generation. The net project effect takes into consideration the changes in the whole system as opposed to what happens on the proposed facility in question.



Overall new roadway projects are general capacity-enhancing. However these project may show a short-term VMT reduction due to intervening paths or reduced travel times.

This page intentionally left blank

28

6.0 SIGNIFICANCE THRESHOLDS FOR LAND PLANS

In the TA, the OPR provided guidance on the treatment of CEQA traffic analyses for land use plans. The TA reiterates previous direction regarding individual land use assessments:

- Analyze the VMT outcomes over the full area over which the plan may substantively affect travel patterns (the definition of region).
- VMT should be counted in full rather than split between origins and destinations (the full impact of the project VMT).

The TA provides a single sentence as consideration for land use plans. It states, "A general plan, area plan, or community plan may have a significant impact on transportation if proposed new residential, office or retail land uses would in aggregate exceed the respective thresholds recommended above." This recommendation refers to 85 percent of the existing city or regional average, and no net gain for residential, office, and retail land uses.

OPR is recommending a focus on specific trip purposes (i.e., home-based trips for residential projects and work-based trips for office projects). Depending on the modeling platform, at least four other trip types are recognized as contributors to large-scale plan-level analyses. Home-based origins will have interactions with other non-work-based destinations. Therefore, if home-based trips are the focus of a plan-level assessment, a great deal of VMT would not be accounted for in the estimation of total VMT.

To assess a land plan, use of a traffic-forecasting tool is recommended. The total VMT for the plan should be identified for all trip types and all potential VMT contributors within the plan area. Similar traffic model runs should be conducted for the existing base year and the horizon year with No Project.

The SB 375 process and the Regional Targets Advisory Committee GHG goal setting has established a baseline GHG emissions reduction that local Metropolitan Planning Organizations (MPOs) and Regional Transportation Planning Agencies (RTPAs) can achieve. These achievements are provided in the integration of land use planning and transportation, not solely through the imposition of regulation on passenger cars and light-duty trucks. The CARB reviews the GHG reduction strategies and has approved the most recent round of GHG emission reductions for MPOs and RTPAs around the State.

Other legislative mandates and State policies speak to GHG reduction targets. A sample of these include:

- Assembly Bill 32 (2006) requires statewide GHG emissions reductions to 1990 levels by 2020 and continued reductions beyond 2020.
- SB 32 (2016) requires at least a 40 percent reduction in GHG emissions from 1990 levels by 2030.



- Executive Order (EO) B-30-15 (2015) sets a GHG emissions reduction target of 40 percent below 1990 levels by 2030.
- EO S-3-05 (2005) sets a GHG emissions reduction target of 80 percent below 1990 levels by 2050.
- EO B-16-12 (2012) specifies a GHG emissions reduction target of 80 percent below 1990 levels by 2050 specifically for transportation.

Guidelines Section 15064.3(b)(4) states (in part) the following:

A lead agency has discretion to choose the most appropriate methodology to evaluate a project's vehicle miles traveled, including whether to express the change in absolute terms, per capita, per household, or in any other measure.

Therefore, the recommended methodology for conducting VMT assessments for land plans is to compare the existing VMT per capita for the land plan area with the expected horizon year VMT per service population (population and employment). The recommended target is to achieve a lower VMT per service population in the horizon year with the proposed land plan than occurs for the existing condition.

7.0 MITIGATION STRATEGIES

When a significant CEQA impact is identified according to the thresholds described above, the project proponent will be required to identify feasible mitigation measures in order to reduce, avoid, or offset the impact. Although previous vehicle LOS impacts could be mitigated with location-specific vehicle level of service improvements, VMT impacts likely require mitigation of regional impacts through more behavioral changes. Enforcement of mitigation measures will still be subject to the mitigation monitoring requirements of CEQA, as well as the regular police powers of the County. These measures can also be incorporated as a part of plans, policies, regulations, or project designs.

7.1 Definition of Mitigation

Section 15370 of the Guidelines defines mitigations as follows:

"Mitigation" includes:

- a. Avoiding the impact altogether by not taking a certain action or parts of an action.
- b. Minimizing impacts by limiting the degree or magnitude of the action and its implementation.
- c. Rectifying the impact by repairing, rehabilitating, or restoring the impacted environment.
- d. Reducing or eliminating the impact over time by preservation and maintenance operations during the life of the action.
- e. Compensating for the impact by replacing or providing substitute resources or environments, including through permanent protection of such resources in the form of conservation easements.

Section 15097 of the Guidelines states that "the public agency shall adopt a program for monitoring or reporting on the revisions which it has required in the project and the measures it has imposed to mitigate or avoid significant environmental effects."

VMT mitigations are not necessarily physical improvements; rather, they are complex in nature and will significantly depend on changes in human behavior.

Section 21099 (b) (4) of the PRC states, "This subdivision [requiring a new transportation metric under CEQA] does not preclude the application of local general plan policies, zoning codes, conditions of approval, thresholds, or any other planning requirements pursuant to the police power or any other authority." Thus, despite the fact that automobile delay will no longer be considered a significant impact under CEQA, the County can still require projects to meet the LOS standards designated in its zoning code or general plan. Many projects will likely still be required to propose LOS improvements for congestion relief in addition to VMT strategies as CEQA mitigation measures.

7.2 Mitigation Measures and Project Alternatives

7.2.1 Land Development Projects and Community/General Plans

Mitigations and project alternatives for VMT impacts have been suggested by the OPR and are included in the TA. VMT mitigation can be extremely diverse and can be classified under several categories such as land use/location, road pricing, transit improvements, commute trip reduction strategies, and parking pricing/policy. Improvements related to VMT reduction strategies have been quantified in sources such as the California Air Pollution Control Officers Association (CAPCOA) report *Quantifying Greenhouse Gas Mitigation Measures* (CAPCOA Green Book) and CARB sources and are generally presented in wide ranges of potential VMT reduction percentages.

Appendix B provides a brief menu of the different potentially applicable VMT mitigation measures and project alternatives stated in the CAPCOA Green Book (only those strategies directly attributed to transportation) and the OPR TA for land development projects. This discussion does not present an exhaustive list of feasible mitigation measures that may be applied to a project. As in previous CEQA practice, the applicant/project proponent will be required to identify mitigation measures to the County to reduce, avoid, or offset the specific project-related impacts identified in an individual environmental document.

As additional mitigation measures are developed to offset VMT impacts in the future for the Guidelines process, linkages between the strategy and the incremental effect and quantified offset must be made. This can be based on other sources' observations and measurements or County experience in these practices. The key to mitigation is to base its efficacy on real and substantial evidence.

7.2.2 Transportation Projects

Although OPR provides detailed guidance on how to assess induced-growth impacts associated with transportation projects, it leaves the subject of mitigation measures vague. Only four strategies are suggested as mitigation measures:

- Tolling new lanes to encourage carpools and fund transit improvements
- Converting existing general-purpose lanes to HOV or HOT lanes
- Implementing or funding off-site travel demand management
- Implementing Intelligent Transportation Systems strategies to improve passenger throughput on existing lanes

No quantified reduction percentage is allocated to these strategies, and LSA could find no substantial evidence that would provide guidance to levels of significance after implementation of these strategies. Review of the four recommended strategies suggests that OPR is directing strategies away from general-purpose mixed-flow lanes on expressways, freeways, and arterial highways. Inasmuch as these are the project descriptions and Purpose and Need, the project intent and the project mitigation may be at odds. The County may be subject to an SOC for the capital project VMT impact.

APPENDIX A

TECHNICAL ADVISORY ON EVALUATING TRANSPORTATION IMPACTS IN CEQA (OPR, DECEMBER 2018)

This page intentionally left blank

TECHNICAL ADVISORY

ON EVALUATING TRANSPORTATION IMPACTS IN CEQA



Contents

A.	Introduction	. 1
В.	Background	. 2
C.	Technical Considerations in Assessing Vehicle Miles Traveled	4
1	. Recommendations Regarding Methodology	4
D.	General Principles to Guide Consideration of VMT	. 7
E.	Recommendations Regarding Significance Thresholds	8
1	Screening Thresholds for Land Use Projects	L2
2	. Recommended Numeric Thresholds for Residential, Office, and Retail Projects	L5
3	. Recommendations Regarding Land Use Plans	18
4	Other Considerations	١9
F.	Considering the Effects of Transportation Projects on Vehicle Travel	١9
1	. Recommended Significance Threshold for Transportation Projects	22
2	Estimating VMT Impacts from Transportation Projects	23
G.	Analyzing Other Impacts Related to Transportation	25
Н.	VMT Mitigation and Alternatives	26
Арр	Appendix 1. Considerations About Which VMT to Count29	
Арре	endix 2. Induced Travel: Mechanisms, Research, and Additional Assessment Approaches	32

A. Introduction

This technical advisory is one in a series of advisories provided by the Governor's Office of Planning and Research (OPR) as a service to professional planners, land use officials, and CEQA practitioners. OPR issues technical assistance on issues that broadly affect the practice of land use planning and the California Environmental Quality Act (CEQA) (Pub. Resources Code, § 21000 et seq.). (Gov. Code, § 65040, subds. (g), (l), (m).) The purpose of this document is to provide advice and recommendations, which agencies and other entities may use at their discretion. This document does not alter lead agency discretion in preparing environmental documents subject to CEQA. This document should not be construed as legal advice.

Senate Bill 743 (Steinberg, 2013), which was codified in Public Resources Code section 21099, required changes to the guidelines implementing CEQA (CEQA Guidelines) (Cal. Code Regs., Title 14, Div. 6, Ch. 3, § 15000 et seq.) regarding the analysis of transportation impacts. As one appellate court recently explained: "During the last 10 years, the Legislature has charted a course of long-term sustainability based on denser infill development, reduced reliance on individual vehicles and improved mass transit, all with the goal of reducing greenhouse gas emissions. Section 21099 is part of that strategy " (Covina Residents for Responsible Development v. City of Covina (2018) 21 Cal. App. 5th 712, 729.) Pursuant to Section 21099, the criteria for determining the significance of transportation impacts must "promote the reduction of greenhouse gas emissions, the development of multimodal transportation networks, and a diversity of land uses." (Id., subd. (b)(1); see generally, adopted CEQA Guidelines, § 15064.3, subd. (b) [Criteria for Analyzing Transportation Impacts].) To that end, in developing the criteria, OPR has proposed, and the California Natural Resources Agency (Agency) has certified and adopted, changes to the CEQA Guidelines that identify vehicle miles traveled (VMT) as the most appropriate metric to evaluate a project's transportation impacts. With the California Natural Resources Agency's certification and adoption of the changes to the CEQA Guidelines, automobile delay, as measured by "level of service" and other similar metrics, generally no longer constitutes a significant environmental effect under CEQA. (Pub. Resources Code, § 21099, subd. (b)(3).)

This advisory contains technical recommendations regarding assessment of VMT, thresholds of significance, and mitigation measures. Again, OPR provides this Technical Advisory as a resource for the public to use at their discretion. OPR is not enforcing or attempting to enforce any part of the recommendations contained herein. (Gov. Code, § 65035 ["It is not the intent of the Legislature to vest in the Office of Planning and Research any direct operating or regulatory powers over land use, public works, or other state, regional, or local projects or programs."].)

This December 2018 technical advisory is an update to the advisory it published in April 2018. OPR will continue to monitor implementation of these new provisions and may update or supplement this advisory in response to new information and advancements in modeling and methods.

B. Background

VMT and Greenhouse Gas Emissions Reduction. Senate Bill 32 (Pavley, 2016) requires California to reduce greenhouse gas (GHG) emissions 40 percent below 1990 levels by 2030, and Executive Order B-16-12 provides a target of 80 percent below 1990 emissions levels for the transportation sector by 2050. The transportation sector has three major means of reducing GHG emissions: increasing vehicle efficiency, reducing fuel carbon content, and reducing the amount of vehicle travel. The California Air Resources Board (CARB) has provided a path forward for achieving these emissions reductions from the transportation sector in its 2016 Mobile Source Strategy. CARB determined that it will not be possible to achieve the State's 2030 and post-2030 emissions goals without reducing VMT growth. Further, in its 2018 Progress Report on California's Sustainable Communities and Climate Protection Act, CARB found that despite the State meeting its 2020 climate goals, "emissions from statewide passenger vehicle travel per capita [have been] increasing and going in the wrong direction," and "California cannot meet its [long-term] climate goals without curbing growth in single-occupancy vehicle activity." ARB also found that "[w]ith emissions from the transportation sector continuing to rise despite increases in fuel efficiency and decreases in the carbon content of fuel, California will not achieve the necessary greenhouse gas emissions reductions to meet mandates for 2030 and beyond without significant changes to how communities and transportation systems are planned, funded, and built."2

Thus, to achieve the State's long-term climate goals, California needs to reduce per capita VMT. This can occur under CEQA through VMT mitigation. Half of California's GHG emissions come from the transportation sector³, therefore, reducing VMT is an effective climate strategy, which can also result in co-benefits.⁴ Furthermore, without early VMT mitigation, the state may follow a path that meets GHG targets in the early years, but finds itself poorly positioned to meet more stringent targets later. For example, in absence of VMT analysis and mitigation in CEQA, lead agencies might rely upon verifiable offsets for GHG mitigation, ignoring the longer-term climate change impacts resulting from land use development and infrastructure investment decisions. As stated in CARB's 2017 Scoping Plan:

"California's future climate strategy will require increased focus on integrated land use planning to support livable, transit-connected communities, and conservation of agricultural and other lands. Accommodating population and economic growth through travel- and energy-efficient land use provides GHG-efficient growth, reducing GHGs from both transportation and building energy use. GHGs can be further reduced at the project level through implementing energy-efficient construction and travel demand management approaches." 5 (Id. at p. 102.)

¹ California Air Resources Board (Nov. 2018) *2018 Progress Report on California's Sustainable Communities and Climate Protection Act*, pp. 4, 5, available at https://ww2.arb.ca.gov/sites/default/files/2018-11/Final2018Report_SB150_112618_02_Report.pdf. ² *Id.*, p. 28.

³ See https://ca50million.ca.gov/transportation/

⁴ Fang et al. (2017) Cutting Greenhouse Gas Emissions Is Only the Beginning: A Literature Review of the Co-Benefits of Reducing Vehicle Miles Traveled.

⁵ California Air Resources Board (Nov. 2017) *California's 2017 Climate Change Scoping Plan*, p. 102, available at https://www.arb.ca.gov/cc/scopingplan/scoping plan 2017.pdf.

In light of this, the 2017 Scoping Plan describes and quantifies VMT reductions needed to achieve our long-term GHG emissions reduction goals, and specifically points to the need for statewide deployment of the VMT metric in CEQA:

"Employing VMT as the metric of transportation impact statewide will help to ensure GHG reductions planned under SB 375 will be achieved through on-the-ground development, and will also play an important role in creating the additional GHG reductions needed beyond SB 375 across the State. Implementation of this change will rely, in part, on local land use decisions to reduce GHG emissions associated with the transportation sector, both at the project level, and in long-term plans (including general plans, climate action plans, specific plans, and transportation plans) and supporting sustainable community strategies developed under SB 375."6

VMT and Other Impacts to Health and Environment. VMT mitigation also creates substantial benefits (sometimes characterized as "co-benefits" to GHG reduction) in both in the near-term and the long-term. Beyond GHG emissions, increases in VMT also impact human health and the natural environment. Human health is impacted as increases in vehicle travel lead to more vehicle crashes, poorer air quality, increases in chronic diseases associated with reduced physical activity, and worse mental health. Increases in vehicle travel also negatively affect other road users, including pedestrians, cyclists, other motorists, and many transit users. The natural environment is impacted as higher VMT leads to more collisions with wildlife and fragments habitat. Additionally, development that leads to more vehicle travel also tends to consume more energy, water, and open space (including farmland and sensitive habitat). This increase in impermeable surfaces raises the flood risk and pollutant transport into waterways.⁷

VMT and Economic Growth. While it was previously believed that VMT growth was a necessary component of economic growth, data from the past two decades shows that economic growth is possible without a concomitant increase in VMT. (Figure 1.) Recent research shows that requiring development projects to mitigate LOS may actually reduce accessibility to destinations and impede economic growth.^{8,9}

⁶ *Id.* at p. 76.

⁷ Fang et al. (2017) *Cutting Greenhouse Gas Emissions Is Only the Beginning: A Literature Review of the Co-Benefits of Reducing Vehicle Miles Traveled*, available at https://ncst.ucdavis.edu/wp-content/uploads/2017/03/NCST-VMT-Co-Benefits-White-Paper Fang March-2017.pdf.

⁸ Haynes et al. (Sept. 2015) *Congested Development: A Study of Traffic Delays, Access, and Economic Activity in Metropolitan Los Angeles*, available at http://www.its.ucla.edu/wp-content/uploads/sites/6/2015/11/Haynes Congested-Development 1-Oct-2015 final.pdf.

⁹ Osman et al. (Mar. 2016) *Not So Fast: A Study of Traffic Delays, Access, and Economic Activity in the San Francisco Bay Area*, available at http://www.its.ucla.edu/wp-content/uploads/sites/6/2016/08/Taylor-Not-so-Fast-04-01-2016 final.pdf.




Figure 1. Kooshian and Winkelman (2011) VMT and Gross Domestic Product (GDP), 1960-2010.

C. Technical Considerations in Assessing Vehicle Miles Traveled

Many practitioners are familiar with accounting for VMT in connection with long-range planning, or as part of the CEQA analysis of a project's greenhouse gas emissions or energy impacts. This document provides technical information on how to assess VMT as part of a transportation impacts analysis under CEQA. Appendix 1 provides a description of which VMT to count and options on how to count it. Appendix 2 provides information on induced travel resulting from roadway capacity projects, including the mechanisms giving rise to induced travel, the research quantifying it, and information on additional approaches for assessing it.

1. Recommendations Regarding Methodology

Proposed Section 15064.3 explains that a "lead agency may use models to estimate a project's vehicle miles traveled" CEQA generally defers to lead agencies on the choice of methodology to analyze impacts. (Santa Monica Baykeeper v. City of Malibu (2011) 193 Cal.App.4th 1538, 1546; see Laurel Heights Improvement Assn. v. Regents of University of California (1988) 47 Cal.3d 376, 409 ["the issue is not whether the studies are irrefutable or whether they could have been better" ... rather, the "relevant issue is only whether the studies are sufficiently credible to be considered" as part of the lead agency's overall evaluation].) This section provides suggestions to lead agencies regarding methodologies to analyze VMT associated with a project.

Vehicle Types. Proposed Section 15064.3, subdivision (a), states, "For the purposes of this section, 'vehicle miles traveled' refers to the amount and distance of automobile travel attributable to a project." Here, the term "automobile" refers to on-road passenger vehicles, specifically cars and light trucks. Heavy-duty truck VMT could be included for modeling convenience and ease of calculation (for example, where models or data provide combined auto and heavy truck VMT). For an apples-to-apples

comparison, vehicle types considered should be consistent across project assessment, significance thresholds, and mitigation.

Residential and Office Projects. Tour- and trip-based approaches ¹⁰ offer the best methods for assessing VMT from residential/office projects and for comparing those assessments to VMT thresholds. These approaches also offer the most straightforward methods for assessing VMT reductions from mitigation measures for residential/office projects. When available, tour-based assessment is ideal because it captures travel behavior more comprehensively. But where tour-based tools or data are not available for all components of an analysis, a trip-based assessment of VMT serves as a reasonable proxy.

Models and methodologies used to calculate thresholds, estimate project VMT, and estimate VMT reduction due to mitigation should be comparable. For example:

- A tour-based assessment of project VMT should be compared to a tour-based threshold, or a trip-based assessment to a trip-based VMT threshold.
- Where a travel demand model is used to determine thresholds, the same model should also be used to provide trip lengths as part of assessing project VMT.
- Where only trip-based estimates of VMT reduction from mitigation are available, a trip-based threshold should be used, and project VMT should be assessed in a trip-based manner.

When a trip-based method is used to analyze a residential project, the focus can be on home-based trips. Similarly, when a trip-based method is used to analyze an office project, the focus can be on home-based work trips.

When tour-based models are used to analyze an office project, either employee work tour VMT or VMT from all employee tours may be attributed to the project. This is because workplace location influences overall travel. For consistency, the significance threshold should be based on the same metric: either employee work tour VMT or VMT from all employee tours.

For office projects that feature a customer component, such as a government office that serves the public, a lead agency can analyze the customer VMT component of the project using the methodology for retail development (see below).

Retail Projects. Generally, lead agencies should analyze the effects of a retail project by assessing the change in total VMT¹¹ because retail projects typically re-route travel from other retail destinations. A retail project might lead to increases or decreases in VMT, depending on previously existing retail travel patterns.

¹⁰ See Appendix 1, Considerations About Which VMT to Count, for a description of these approaches.

¹¹ See Appendix 1, *Considerations About Which VMT to Count, "*Assessing Change in Total VMT" section, for a description of this approach.

Considerations for All Projects. Lead agencies should not truncate any VMT analysis because of jurisdictional or other boundaries, for example, by failing to count the portion of a trip that falls outside the jurisdiction or by discounting the VMT from a trip that crosses a jurisdictional boundary. CEQA requires environmental analyses to reflect a "good faith effort at full disclosure." (CEQA Guidelines, § 15151.) Thus, where methodologies exist that can estimate the full extent of vehicle travel from a project, the lead agency should apply them to do so. Where those VMT effects will grow over time, analyses should consider both a project's short-term and long-term effects on VMT.

Combining land uses for VMT analysis is not recommended. Different land uses generate different amounts of VMT, so the outcome of such an analysis could depend more on the mix of uses than on their travel efficiency. As a result, it could be difficult or impossible for a lead agency to connect a significance threshold with an environmental policy objective (such as a target set by law), inhibiting the CEQA imperative of identifying a project's significant impacts and providing mitigation where feasible. Combining land uses for a VMT analysis could streamline certain mixes of uses in a manner disconnected from policy objectives or environmental outcomes. Instead, OPR recommends analyzing each use separately, or simply focusing analysis on the dominant use, and comparing each result to the appropriate threshold. Recommendations for methods of analysis and thresholds are provided below. In the analysis of each use, a mixed-use project should take credit for internal capture.

Any project that includes in its geographic bounds a portion of an existing or planned Transit Priority Area (i.e., the project is within a ½ mile of an existing or planned major transit stop or an existing stop along a high quality transit corridor) may employ VMT as its primary metric of transportation impact for the entire project. (See Pub. Resources Code, § 21099, subds. (a)(7), (b)(1).)

Cumulative Impacts. A project's cumulative impacts are based on an assessment of whether the "incremental effects of an individual project are considerable when viewed in connection with the effects of past projects, the effects of other current projects, and the effects of probable future projects." (Pub. Resources Code, § 21083, subd. (b)(2); see CEQA Guidelines, § 15064, subd. (h)(1).) When using an absolute VMT metric, i.e., total VMT (as recommended below for retail and transportation projects), analyzing the combined impacts for a cumulative impacts analysis may be appropriate. However, metrics such as VMT per capita or VMT per employee, i.e., metrics framed in terms of efficiency (as recommended below for use on residential and office projects), cannot be summed because they employ a denominator. A project that falls below an efficiency-based threshold that is aligned with long-term environmental goals and relevant plans would have no cumulative impact distinct from the project impact. Accordingly, a finding of a less-than-significant project impact would imply a less than significant cumulative impact, and vice versa. This is similar to the analysis typically conducted for greenhouse gas emissions, air quality impacts, and impacts that utilize plan compliance as a threshold of significance. (See *Center for Biological Diversity v. Department of Fish & Wildlife* (2015) 62 Cal.4th 204, 219, 223; CEQA Guidelines, § 15064, subd. (h)(3).)

D. General Principles to Guide Consideration of VMT

SB 743 directs OPR to establish specific "criteria for determining the significance of transportation impacts of projects[.]" (Pub. Resources Code, § 21099, subd. (b)(1).) In establishing this criterion, OPR was guided by the general principles contained within CEQA, the CEQA Guidelines, and applicable case law.

To assist in the determination of significance, many lead agencies rely on "thresholds of significance." The CEQA Guidelines define a "threshold of significance" to mean "an identifiable quantitative, qualitative¹² or performance level of a particular environmental effect, non-compliance with which means the effect will *normally* be determined to be significant by the agency and compliance with which means the effect *normally* will be determined to be less than significant." (CEQA Guidelines, § 15064.7, subd. (a) (emphasis added).) Lead agencies have discretion to develop and adopt their own, or rely on thresholds recommended by other agencies, "provided the decision of the lead agency to adopt such thresholds is supported by substantial evidence." (*Id.* at subd. (c); *Save Cuyama Valley v. County of Santa Barbara* (2013) 213 Cal.App.4th 1059, 1068.) Substantial evidence means "enough relevant information and reasonable inferences from this information that a fair argument can be made to support a conclusion, even though other conclusions might also be reached." (*Id.* at § 15384 (emphasis added); *Protect the Historic Amador Waterways v. Amador Water Agency* (2004) 116 Cal.App.4th 1099, 1108-1109.)

Additionally, the analysis leading to the determination of significance need not be perfect. The CEQA Guidelines describe the standard for adequacy of environmental analyses:

An EIR should be prepared with a sufficient degree of analysis to provide decision makers with information which enables them to make a decision which intelligently takes account of environmental consequences. An evaluation of the environmental effects of a proposed project need not be exhaustive, but the sufficiency of an EIR is to be reviewed in the light of what is reasonably feasible. Disagreement among experts does not make an EIR inadequate, but the EIR should summarize the main points of disagreement among the experts. The courts have looked not for perfection but for adequacy, completeness, and a good faith effort at full disclosure.

(CEQA Guidelines, § 15151 (emphasis added).)

These general principles guide OPR's recommendations regarding thresholds of significance for VMT set forth below.

¹² Generally, qualitative analyses should only be conducted when methods do not exist for undertaking a quantitative analysis.

E. Recommendations Regarding Significance Thresholds

As noted above, lead agencies have the discretion to set or apply their own thresholds of significance. (*Center for Biological Diversity v. California Dept. of Fish & Wildlife* (2015) 62 Cal.4th 204, 218-223 [lead agency had discretion to use compliance with AB 32's emissions goals as a significance threshold]; *Save Cuyama Valley v. County of Santa Barbara* (2013) 213 Cal.App.4th at p. 1068.) However, Section 21099 of the Public Resources Code states that the criteria for determining the significance of transportation impacts must promote: (1) reduction of greenhouse gas emissions; (2) development of multimodal transportation networks; and (3) a diversity of land uses. It further directed OPR to prepare and develop criteria for determining significance. (Pub. Resources Code, § 21099, subd. (b)(1).) This section provides OPR's suggested thresholds, as well as considerations for lead agencies that choose to adopt their own thresholds.

The VMT metric can support the three statutory goals: "the reduction of greenhouse gas emissions, the development of multimodal transportation networks, <u>and</u> a diversity of land uses." (Pub. Resources Code, § 21099, subd. (b)(1), emphasis added.) However, in order for it to promote and support all three, lead agencies should select a significance threshold that aligns with state law on all three. State law concerning the development of multimodal transportation networks and diversity of land uses requires planning for and prioritizing increases in complete streets and infill development, but does not mandate a particular depth of implementation that could translate into a particular threshold of significance. Meanwhile, the State has clear quantitative targets for GHG emissions reduction set forth in law and based on scientific consensus, and the depth of VMT reduction needed to achieve those targets has been quantified. Tying VMT thresholds to GHG reduction also supports the two other statutory goals. Therefore, to ensure adequate analysis of transportation impacts, OPR recommends using quantitative VMT thresholds linked to GHG reduction targets when methods exist to do so.

Various legislative mandates and state policies establish quantitative greenhouse gas emissions reduction targets. For example:

- Assembly Bill 32 (2006) requires statewide GHG emissions reductions to 1990 levels by 2020 and continued reductions beyond 2020.
- <u>Senate Bill 32</u> (2016) requires at least a 40 percent reduction in GHG emissions from 1990 levels by 2030.
- Pursuant to <u>Senate Bill 375</u> (2008), the California Air Resources Board GHG emissions reduction targets for metropolitan planning organizations (MPOs) to achieve based on land use patterns and transportation systems specified in Regional Transportation Plans and Sustainable Community Strategies (RTP/SCS). Current targets for the State's largest MPOs call for a 19 percent reduction in GHG emissions from cars and light trucks from 2005 emissions levels by 2035.
- Executive Order B-30-15 (2015) sets a GHG emissions reduction target of 40 percent below 1990 levels by 2030.

- Executive Order S-3-05 (2005) sets a GHG emissions reduction target of 80 percent below 1990 levels by 2050.
- Executive Order B-16-12 (2012) specifies a GHG emissions reduction target of 80 percent below 1990 levels by 2050 specifically for transportation.
- Executive Order B-55-18 (2018) established an additional statewide goal of achieving carbon neutrality as soon as possible, but no later than 2045, and maintaining net negative emissions thereafter. It states, "The California Air Resources Board shall work with relevant state agencies to develop a framework for implementation and accounting that tracks progress toward this goal."
- <u>Senate Bill 391</u> requires the <u>California Transportation Plan</u> to support 80 percent reduction in GHGs below 1990 levels by 2050.
- The <u>California Air Resources Board Mobile Source Strategy</u> (2016) describes California's strategy for containing air pollutant emissions from vehicles, and quantifies VMT growth compatible with achieving state targets.
- The California Air Resources Board's <u>2017 Climate Change Scoping Plan Update: The Strategy for Achieving California's 2030 Greenhouse Gas Target</u> describes California's strategy for containing GHG emissions from vehicles, and quantifies VMT growth compatible with achieving state targets.

Considering these various targets, the California Supreme Court observed:

Meeting our statewide reduction goals does not preclude all new development. Rather, the Scoping Plan ... assumes continued growth and depends on increased efficiency and conservation in land use and transportation from all Californians.

(Center for Biological Diversity v. California Dept. of Fish & Wildlife, supra, 62 Cal.4th at p. 220.) Indeed, the Court noted that when a lead agency uses consistency with climate goals as a way to determine significance, particularly for long-term projects, the lead agency must consider the project's effect on meeting long-term reduction goals. (*Ibid.*) And more recently, the Supreme Court stated that "CEQA requires public agencies . . . to ensure that such analysis stay in step with evolving scientific knowledge and state regulatory schemes." (Cleveland National Forest Foundation v. San Diego Assn. of Governments (2017) 3 Cal.5th 497, 504.)

Meeting the targets described above will require substantial reductions in existing VMT per capita to curb GHG emissions and other pollutants. But targets for overall GHG emissions reduction do not translate directly into VMT thresholds for individual projects for many reasons, including:

Some, but not all, of the emissions reductions needed to achieve those targets could be
accomplished by other measures, including increased vehicle efficiency and decreased fuel
carbon content. The CARB's First Update to the Climate Change Scoping Plan explains:

"Achieving California's long-term criteria pollutant and GHG emissions goals will require four strategies to be employed: (1) improve vehicle efficiency and develop zero emission technologies, (2) reduce the carbon content of fuels and provide market support to get these lower-carbon fuels into the marketplace, (3) plan and build communities to reduce vehicular GHG emissions and provide more transportation options, and (4) improve the efficiency and throughput of existing transportation systems." CARB's 2018 Progress Report on California's Sustainable Communities and Climate Protection Act states on page 28 that "California cannot meet its climate goals without curbing growth in single-occupancy vehicle activity." In other words, vehicle efficiency and better fuels are necessary, but insufficient, to address the GHG emissions from the transportation system. Land use patterns and transportation options also will need to change to support reductions in vehicle travel/VMT.

- New land use projects alone will not sufficiently reduce per-capita VMT to achieve those targets, nor are they expected to be the sole source of VMT reduction.
- Interactions between land use projects, and also between land use and transportation projects, existing and future, together affect VMT.
- Because location within the region is the most important determinant of VMT, in some cases, streamlining CEQA review of projects in travel efficient locations may be the most effective means of reducing VMT.
- When assessing climate impacts of some types of land use projects, use of an efficiency metric (e.g., per capita, per employee) may provide a better measure of impact than an absolute numeric threshold. (*Center for Biological Diversity, supra.*)

Public Resources Code section 21099 directs OPR to propose criteria for determining the significance of transportation impacts. In this Technical Advisory, OPR provides its recommendations to assist lead agencies in selecting a significance threshold that may be appropriate for their particular projects. While OPR's Technical Advisory is not binding on public agencies, CEQA allows lead agencies to "consider thresholds of significance . . . recommended by other public agencies, provided the decision to adopt those thresholds is supported by substantial evidence." (CEQA Guidelines, § 15064.7, subd. (c).) Based on OPR's extensive review of the applicable research, and in light of an assessment by the California Air Resources Board quantifying the need for VMT reduction in order to meet the State's long-term climate goals, OPR recommends that a per capita or per employee VMT that is fifteen percent below that of existing development may be a reasonable threshold.

Fifteen percent reductions in VMT are achievable at the project level in a variety of place types. 14

Moreover, a fifteen percent reduction is consistent with SB 743's direction to OPR to select a threshold that will help the State achieve its climate goals. As described above, section 21099 states that the

¹³ California Air Resources Board (May 2014) *First Update to the Climate Change Scoping Plan*, p. 46 (emphasis added).

¹⁴ CAPCOA (2010) *Quantifying Greenhouse Gas Mitigation Measures*, p. 55, available at http://www.capcoa.org/wp-content/uploads/2010/11/CAPCOA-Quantification-Report-9-14-Final.pdf.

criteria for determining significance must "promote the reduction in greenhouse gas emissions." In its document California Air Resources Board 2017 Scoping Plan-Identified VMT Reductions and Relationship to State Climate Goals¹⁵, CARB assesses VMT reduction per capita consistent with its evidence-based modeling scenario that would achieve State climate goals of 40 percent GHG emissions reduction from 1990 levels by 2030 and 80 percent GHG emissions reduction levels from 1990 by 2050. Applying California Department of Finance population forecasts, CARB finds per-capita light-duty vehicle travel would need to be approximately 16.8 percent lower than existing, and overall per-capita vehicle travel would need to be approximately 14.3 percent lower than existing levels under that scenario. Below these levels, a project could be considered low VMT and would, on that metric, be consistent with 2017 Scoping Plan Update assumptions that achieve climate state climate goals.

CARB finds per capita vehicle travel would need to be kept below what today's policies and plans would achieve.

CARB's assessment is based on data in the 2017 Scoping Plan Update and 2016 Mobile Source Strategy. In those documents, CARB previously examined the relationship between VMT and the state's GHG emissions reduction targets. The Scoping Plan finds:

"While the State can do more to accelerate and incentivize these local decisions, local actions that reduce VMT are also necessary to meet transportation sector-specific goals and achieve the 2030 target under SB 32. Through developing the Scoping Plan, CARB staff is more convinced than ever that, in addition to achieving GHG reductions from cleaner fuels and vehicles, California must also reduce VMT. Stronger SB 375 GHG reduction targets will enable the State to make significant progress toward needed reductions, but alone will not provide the VMT growth reductions needed; there is a gap between what SB 375 can provide and what is needed to meet the State's 2030 and 2050 goals." ¹⁶

Note that, at present, consistency with RTP/SCSs does not necessarily lead to a less-than-significant VMT impact. 17 As the Final 2017 Scoping Plan Update states,

VMT reductions are necessary to achieve the 2030 target and must be part of any strategy evaluated in this Plan. Stronger SB 375 GHG reduction targets will enable the State to make significant progress toward this goal, but alone will not provide all of the VMT growth reductions that will be needed. There is a gap between what SB 375 can provide and what is needed to meet the State's 2030 and 2050 goals." 18

¹⁵ California Air Resources Board (Jan. 2019) California Air Resources Board 2017 Scoping Plan-Identified VMT Reductions and Relationship to State Climate Goals, available at https://ww2.arb.ca.gov/resources/documents/carb-2017-scoping-plan-identified-vmt-reductions-andrelationship-state-climate.

¹⁶ California Air Resources Board (Nov. 2017) California's 2017 Climate Change Scoping Plan, p. 101.

¹⁷ California Air Resources Board (Feb. 2018) Updated Final Staff Report: Proposed Update to the SB 375 Greenhouse Gas Emission Reduction Targets, Figure 3, p. 35, available at https://www.arb.ca.gov/cc/sb375/sb375 target update final staff report feb2018.pdf.

¹⁸ California Air Resources Board (Nov. 2017) California's 2017 Climate Change Scoping Plan, p. 75.

Also, in order to capture the full effects of induced travel resulting from roadway capacity projects, an RTP/SCS would need to include an assessment of land use effects of those projects, and the effects of those land uses on VMT. (See section titled "Estimating VMT Impacts from Transportation Projects" below.) RTP/SCSs typically model VMT using a collaboratively-developed land use "vision" for the region's land use, rather than studying the effects on land use of the proposed transportation investments.

In summary, achieving 15 percent lower per capita (residential) or per employee (office) VMT than existing development is both generally achievable and is supported by evidence that connects this level of reduction to the State's emissions goals.

1. Screening Thresholds for Land Use Projects

Many agencies use "screening thresholds" to quickly identify when a project should be expected to cause a less-than-significant impact without conducting a detailed study. (See e.g., CEQA Guidelines, §§ 15063(c)(3)(C), 15128, and Appendix G.) As explained below, this technical advisory suggests that lead agencies may screen out VMT impacts using project size, maps, transit availability, and provision of affordable housing.

Screening Threshold for Small Projects

Many local agencies have developed screening thresholds to indicate when detailed analysis is needed. Absent substantial evidence indicating that a project would generate a potentially significant level of VMT, or inconsistency with a Sustainable Communities Strategy (SCS) or general plan, projects that generate or attract fewer than 110 trips per day¹⁹ generally may be assumed to cause a less-than-significant transportation impact.

Map-Based Screening for Residential and Office Projects

Residential and office projects that locate in areas with low VMT, and that incorporate similar features (i.e., density, mix of uses, transit accessibility), will tend to exhibit similarly low VMT. Maps created with VMT data, for example from a travel survey or a travel demand model, can illustrate areas that are

¹⁹ CEQA provides a categorical exemption for existing facilities, including additions to existing structures of up to 10,000 square feet, so long as the project is in an area where public infrastructure is available to allow for maximum planned development and the project is not in an environmentally sensitive area. (CEQA Guidelines, § 15301, subd. (e)(2).) Typical project types for which trip generation increases relatively linearly with building footprint (i.e., general office building, single tenant office building, office park, and business park) generate or attract an additional 110-124 trips per 10,000 square feet. Therefore, absent substantial evidence otherwise, it is reasonable to conclude that the addition of 110 or fewer trips could be considered not to lead to a significant impact.

currently below threshold VMT (see recommendations below). Because new development in such locations would likely result in a similar level of VMT, such maps can be used to screen out residential and office projects from needing to prepare a detailed VMT analysis.




Figure 2. Example map of household VMT that could be used to delineate areas eligible to receive streamlining for VMT analysis. (Source: City of San José, Department of Transportation, draft output of City Transportation Model.)

Presumption of Less Than Significant Impact Near Transit Stations

Proposed CEQA Guideline Section 15064.3, subdivision (b)(1), states that lead agencies generally should presume that certain projects (including residential, retail, and office projects, as well as projects that are a mix of these uses) proposed within ½ mile of an existing major transit stop²⁰ or an existing stop

²⁰ Pub. Resources Code, § 21064.3 ("'Major transit stop' means a site containing an existing rail transit station, a ferry terminal served by either a bus or rail transit service, or the intersection of two or more major bus routes with a frequency of service interval of 15 minutes or less during the morning and afternoon peak commute periods.").

along a high quality transit corridor²¹ will have a less-than-significant impact on VMT. This presumption would not apply, however, if project-specific or location-specific information indicates that the project will still generate significant levels of VMT. For example, the presumption might not be appropriate if the project:

- Has a Floor Area Ratio (FAR) of less than 0.75
- Includes more parking for use by residents, customers, or employees of the project than required by the jurisdiction (if the jurisdiction requires the project to supply parking)
- Is inconsistent with the applicable Sustainable Communities Strategy (as determined by the lead agency, with input from the Metropolitan Planning Organization)
- Replaces affordable residential units with a smaller number of moderate- or high-income residential units

A project or plan near transit which replaces affordable residential units²² with a smaller number of moderate- or high-income residential units may increase overall VMT because the increase in VMT of displaced residents could overwhelm the improvements in travel efficiency enjoyed by new residents.²³

If any of these exceptions to the presumption might apply, the lead agency should conduct a detailed VMT analysis to determine whether the project would exceed VMT thresholds (see below).

Presumption of Less Than Significant Impact for Affordable Residential Development

Adding affordable housing to infill locations generally improves jobs-housing match, in turn shortening commutes and reducing VMT.^{24,25} Further, "... low-wage workers in particular would be more likely to choose a residential location close to their workplace, if one is available."²⁶ In areas where existing jobshousing match is closer to optimal, low income housing nevertheless generates less VMT than market-

²¹ Pub. Resources Code, § 21155 ("For purposes of this section, a high-quality transit corridor means a corridor with fixed route bus service with service intervals no longer than 15 minutes during peak commute hours.").

²² Including naturally-occurring affordable residential units.

²³ Chapple et al. (2017) *Developing a New Methodology for Analyzing Potential Displacement,* Chapter 4, pp. 159-160, available at https://www.arb.ca.gov/research/apr/past/13-310.pdf.

²⁴ Karner and Benner (2016) *The convergence of social equity and environmental sustainability: Jobshousing fit and commute distance* ("[P]olicies that advance a more equitable distribution of jobs and housing by linking the affordability of locally available housing with local wage levels are likely to be associated with reduced commuting distances").

²⁵ Karner and Benner (2015) *Low-wage jobs-housing fit: identifying locations of affordable housing shortages.*

²⁶ Karner and Benner (2015) *Low-wage jobs-housing fit: identifying locations of affordable housing shortages.*

rate housing.^{27,28} Therefore, a project consisting of a high percentage of affordable housing may be a basis for the lead agency to find a less-than-significant impact on VMT. Evidence supports a presumption of less than significant impact for a 100 percent affordable residential development (or the residential component of a mixed-use development) in infill locations. Lead agencies may develop their own presumption of less than significant impact for residential projects (or residential portions of mixed use projects) containing a particular amount of affordable housing, based on local circumstances and evidence. Furthermore, a project which includes any affordable residential units may factor the effect of the affordability on VMT into the assessment of VMT generated by those units.

2. Recommended Numeric Thresholds for Residential, Office, and Retail Projects

Recommended threshold for residential projects: A proposed project exceeding a level of 15 percent below existing VMT per capita may indicate a significant transportation impact. Existing VMT per capita may be measured as regional VMT per capita or as city VMT per capita. Proposed development referencing a threshold based on city VMT per capita (rather than regional VMT per capita) should not cumulatively exceed the number of units specified in the SCS for that city, and should be consistent with the SCS.

Residential development that would generate vehicle travel that is 15 or more percent below the existing residential VMT per capita, measured against the region or city, may indicate a less-than-significant transportation impact. In MPO areas, development measured against city VMT per capita (rather than regional VMT per capita) should not cumulatively exceed the population or number of units specified in the SCS for that city because greater-than-planned amounts of development in areas above the region-based threshold would undermine the VMT containment needed to achieve regional targets under SB 375.

For residential projects in unincorporated county areas, the local agency can compare a residential project's VMT to (1) the region's VMT per capita, or (2) the aggregate population-weighted VMT per capita of all cities in the region. In MPO areas, development in unincorporated areas measured against aggregate city VMT per capita (rather than regional VMT per capita) should not cumulatively exceed the population or number of units specified in the SCS for that city because greater-than-planned amounts of development in areas above the regional threshold would undermine achievement of regional targets under SB 375.

²⁷ Chapple et al. (2017) *Developing a New Methodology for Analyzing Potential Displacement*, available at https://www.arb.ca.gov/research/apr/past/13-310.pdf.

²⁸ CAPCOA (2010) *Quantifying Greenhouse Gas Mitigation Measures*, pp. 176-178, available at http://www.capcoa.org/wp-content/uploads/2010/11/CAPCOA-Quantification-Report-9-14-Final.pdf.

These thresholds can be applied to either household (i.e., tour-based) VMT or home-based (i.e., trip-based) VMT assessments.²⁹ It is critical, however, that the agency be consistent in its VMT measurement approach throughout the analysis to maintain an "apples-to-apples" comparison. For example, if the agency uses a home-based VMT for the threshold, it should also be use home-based VMT for calculating project VMT and VMT reduction due to mitigation measures.

Recommended threshold for office projects: A proposed project exceeding a level of 15 percent below existing regional VMT per employee may indicate a significant transportation impact.

Office projects that would generate vehicle travel exceeding 15 percent below existing VMT per employee for the region may indicate a significant transportation impact. In cases where the region is substantially larger than the geography over which most workers would be expected to live, it might be appropriate to refer to a smaller geography, such as the county, that includes the area over which nearly all workers would be expected to live.

Office VMT screening maps can be developed using tour-based data, considering either total employee VMT or employee work tour VMT. Similarly, tour-based analysis of office project VMT could consider either total employee VMT or employee work tour VMT. Where tour-based information is unavailable for threshold determination, project assessment, or assessment of mitigation, home-based work trip VMT should be used throughout all steps of the analysis to maintain an "apples-to-apples" comparison.

Recommended threshold for retail projects: A net increase in total VMT may indicate a significant transportation impact.

Because new retail development typically redistributes shopping trips rather than creating new trips,³⁰ estimating the total change in VMT (i.e., the difference in total VMT in the area affected with and without the project) is the best way to analyze a retail project's transportation impacts.

By adding retail opportunities into the urban fabric and thereby improving retail destination proximity, local-serving retail development tends to shorten trips and reduce VMT. Thus, lead agencies generally may presume such development creates a less-than-significant transportation impact. Regional-serving retail development, on the other hand, which can lead to substitution of longer trips for shorter ones, may tend to have a significant impact. Where such development decreases VMT, lead agencies should consider the impact to be less-than-significant.

Many cities and counties define local-serving and regional-serving retail in their zoning codes. Lead agencies may refer to those local definitions when available, but should also consider any project-

²⁹ See Appendix 1 for a description of these approaches.

³⁰ Lovejoy, et al. (2013) Measuring the impacts of local land-use policies on vehicle miles of travel: The case of the first big-box store in Davis, California, The Journal of Transport and Land Use.

specific information, such as market studies or economic impacts analyses that might bear on customers' travel behavior. Because lead agencies will best understand their own communities and the likely travel behaviors of future project users, they are likely in the best position to decide when a project will likely be local-serving. Generally, however, retail development including stores larger than 50,000 square feet might be considered regional-serving, and so lead agencies should undertake an analysis to determine whether the project might increase or decrease VMT.

Mixed-Use Projects

Lead agencies can evaluate each component of a mixed-use project independently and apply the significance threshold for each project type included (e.g., residential and retail). Alternatively, a lead agency may consider only the project's dominant use. In the analysis of each use, a project should take credit for internal capture. Combining different land uses and applying one threshold to those land uses may result in an inaccurate impact assessment.

Other Project Types

Of land use projects, residential, office, and retail projects tend to have the greatest influence on VMT. For that reason, OPR recommends the quantified thresholds described above for purposes of analysis and mitigation. Lead agencies, using more location-specific information, may develop their own more specific thresholds, which may include other land use types. In developing thresholds for other project types, or thresholds different from those recommended here, lead agencies should consider the purposes described in section 21099 of the Public Resources Code and regulations in the CEQA Guidelines on the development of thresholds of significance (e.g., CEQA Guidelines, § 15064.7).

Strategies and projects that decrease local VMT but increase total VMT should be avoided. Agencies should consider whether their actions encourage development in a less travel-efficient location by limiting development in travel-efficient locations.

Redevelopment Projects

Where a project replaces existing VMT-generating land uses, if the replacement leads to a net overall decrease in VMT, the project would lead to a less-than-significant transportation impact. If the project leads to a net overall increase in VMT, then the thresholds described above should apply.

As described above, a project or plan near transit which replaces affordable³¹ residential units with a smaller number of moderate- or high-income residential units may increase overall VMT, because

³¹ Including naturally-occurring affordable residential units.

displaced residents' VMT may increase.³² A lead agency should analyze VMT for such a project even if it otherwise would have been presumed less than significant. The assessment should incorporate an estimate of the aggregate VMT increase experienced by displaced residents. That additional VMT should be included in the numerator of the VMT per capita assessed for the project.

If a residential or office project leads to a net increase in VMT, then the project's VMT per capita (residential) or per employee (office) should be compared to thresholds recommended above. Per capita and per employee VMT are efficiency metrics, and, as such, apply only to the existing project without regard to the VMT generated by the previously existing land use.

If the project leads to a net increase in provision of locally-serving retail, transportation impacts from the retail portion of the development should be presumed to be less than significant. If the project consists of regionally-serving retail, and increases overall VMT compared to with existing uses, then the project would lead to a significant transportation impact.

RTP/SCS Consistency (All Land Use Projects)

Section 15125, subdivision (d), of the CEQA Guidelines provides that lead agencies should analyze impacts resulting from inconsistencies with regional plans, including regional transportation plans. For this reason, if a project is inconsistent with the Regional Transportation Plan and Sustainable Communities Strategy (RTP/SCS), the lead agency should evaluate whether that inconsistency indicates a significant impact on transportation. For example, a development may be inconsistent with an RTP/SCS if the development is outside the footprint of development or within an area specified as open space as shown in the SCS.

3. Recommendations Regarding Land Use Plans

As with projects, agencies should analyze VMT outcomes of land use plans across the full area over which the plan may substantively affect travel patterns, including beyond the boundary of the plan or jurisdiction's geography. And as with projects, VMT should be counted in full rather than split between origin and destination. (Emissions inventories have sometimes spit cross-boundary trips in order to sum to a regional total, but CEQA requires accounting for the full impact without truncation or discounting). Analysis of specific plans may employ the same thresholds described above for projects. A general plan, area plan, or community plan may have a significant impact on transportation if proposed new residential, office, or retail land uses would in aggregate exceed the respective thresholds recommended above. Where the lead agency tiers from a general plan EIR pursuant to CEQA Guidelines sections 15152 and 15166, the lead agency generally focuses on the environmental impacts that are specific to the later project and were not analyzed as significant impacts in the prior EIR. (Pub. Resources Code, § 21068.5; Guidelines, § 15152, subd. (a).) Thus, in analyzing the later project, the lead agency

³² Chapple et al. (2017) *Developing a New Methodology for Analyzing Potential Displacement,* Chapter 4, pp. 159-160, available at https://www.arb.ca.gov/research/apr/past/13-310.pdf.

would focus on the VMT impacts that were not adequately addressed in the prior EIR. In the tiered document, the lead agency should continue to apply the thresholds recommended above.

Thresholds for plans in non-MPO areas may be determined on a case-by-case basis.

4. Other Considerations

Rural Projects Outside of MPOs

In rural areas of non-MPO counties (i.e., areas not near established or incorporated cities or towns), fewer options may be available for reducing VMT, and significance thresholds may be best determined on a case-by-case basis. Note, however, that clustered small towns and small town main streets may have substantial VMT benefits compared to isolated rural development, similar to the transit oriented development described above.

Impacts to Transit

Because criteria for determining the significance of transportation impacts must promote "the development of multimodal transportation networks" pursuant to Public Resources Code section 21099, subd. (b)(1), lead agencies should consider project impacts to transit systems and bicycle and pedestrian networks. For example, a project that blocks access to a transit stop or blocks a transit route itself may interfere with transit functions. Lead agencies should consult with transit agencies as early as possible in the development process, particularly for projects that are located within one half mile of transit stops.

When evaluating impacts to multimodal transportation networks, lead agencies generally should not treat the addition of new transit users as an adverse impact. An infill development may add riders to transit systems and the additional boarding and alighting may slow transit vehicles, but it also adds destinations, improving proximity and accessibility. Such development also improves regional vehicle flow by adding less vehicle travel onto the regional network.

Increased demand throughout a region may, however, cause a cumulative impact by requiring new or additional transit infrastructure. Such impacts may be adequately addressed through a fee program that fairly allocates the cost of improvements not just to projects that happen to locate near transit, but rather across a region to all projects that impose burdens on the entire transportation system, since transit can broadly improve the function of the transportation system.

F. Considering the Effects of Transportation Projects on Vehicle Travel

Many transportation projects change travel patterns. A transportation project which leads to additional vehicle travel on the roadway network, commonly referred to as "induced vehicle travel," would need to quantify the amount of additional vehicle travel in order to assess air quality impacts, greenhouse gas emissions impacts, energy impacts, and noise impacts. Transportation projects also are required to

examine induced growth impacts under CEQA. (See generally, Pub. Resources Code, §§ 21065 [defining "project" under CEQA as an activity as causing either a direct or reasonably foreseeable indirect physical change], 21065.3 [defining "project-specific effect" to mean all direct or indirect environmental effects], 21100, subd. (b) [required contents of an EIR].) For any project that increases vehicle travel, explicit assessment and quantitative reporting of the amount of additional vehicle travel should not be omitted from the document; such information may be useful and necessary for a full understanding of a project's environmental impacts. (See Pub. Resources Code, §§ 21000, 21001, 21001.1, 21002, 21002.1 [discussing the policies of CEQA].) A lead agency that uses the VMT metric to assess the transportation impacts of a transportation project may simply report that change in VMT as the impact. When the lead agency uses another metric to analyze the transportation impacts of a roadway project, changes in amount of vehicle travel added to the roadway network should still be analyzed and reported.³³

While CEQA does not require perfection, it is important to make a reasonably accurate estimate of transportation projects' effects on vehicle travel in order to make reasonably accurate estimates of GHG emissions, air quality emissions, energy impacts, and noise impacts. (See, e.g., California Clean Energy Com. v. City of Woodland (2014) 225 Cal.App.4th 173, 210 [EIR failed to consider project's transportation energy impacts]; Ukiah Citizens for Safety First v. City of Ukiah (2016) 248 Cal.App.4th 256, 266.) Appendix 2 describes in detail the causes of induced vehicle travel, the robust empirical evidence of induced vehicle travel, and how models and research can be used in conjunction to quantitatively assess induced vehicle travel with reasonable accuracy.

If a project would likely lead to a measurable and substantial increase in vehicle travel, the lead agency should conduct an analysis assessing the amount of vehicle travel the project will induce. Project types that would likely lead to a measurable and substantial increase in vehicle travel generally include:

 Addition of through lanes on existing or new highways, including general purpose lanes, HOV lanes, peak period lanes, auxiliary lanes, or lanes through grade-separated interchanges

Projects that would not likely lead to a substantial or measurable increase in vehicle travel, and therefore generally should not require an induced travel analysis, include:

- Rehabilitation, maintenance, replacement, safety, and repair projects designed to improve the
 condition of existing transportation assets (e.g., highways; roadways; bridges; culverts;
 Transportation Management System field elements such as cameras, message signs, detection,
 or signals; tunnels; transit systems; and assets that serve bicycle and pedestrian facilities) and
 that do not add additional motor vehicle capacity
- Roadside safety devices or hardware installation such as median barriers and guardrails

³³ See, e.g., California Department of Transportation (2006) *Guidance for Preparers of Growth-related, Indirect Impact Analyses*, available at http://www.dot.ca.gov/ser/Growth-related IndirectImpactAnalysis/GRI guidance06May files/gri guidance.pdf.

- Roadway shoulder enhancements to provide "breakdown space," dedicated space for use only
 by transit vehicles, to provide bicycle access, or to otherwise improve safety, but which will not
 be used as automobile vehicle travel lanes
- Addition of an auxiliary lane of less than one mile in length designed to improve roadway safety
- Installation, removal, or reconfiguration of traffic lanes that are not for through traffic, such as left, right, and U-turn pockets, two-way left turn lanes, or emergency breakdown lanes that are not utilized as through lanes
- Addition of roadway capacity on local or collector streets provided the project also substantially improves conditions for pedestrians, cyclists, and, if applicable, transit
- Conversion of existing general purpose lanes (including ramps) to managed lanes or transit lanes, or changing lane management in a manner that would not substantially increase vehicle travel
- Addition of a new lane that is permanently restricted to use only by transit vehicles
- Reduction in number of through lanes
- Grade separation to separate vehicles from rail, transit, pedestrians or bicycles, or to replace a lane in order to separate preferential vehicles (e.g., HOV, HOT, or trucks) from general vehicles
- Installation, removal, or reconfiguration of traffic control devices, including Transit Signal Priority (TSP) features
- Installation of traffic metering systems, detection systems, cameras, changeable message signs and other electronics designed to optimize vehicle, bicycle, or pedestrian flow
- Timing of signals to optimize vehicle, bicycle, or pedestrian flow
- Installation of roundabouts or traffic circles
- Installation or reconfiguration of traffic calming devices
- Adoption of or increase in tolls
- Addition of tolled lanes, where tolls are sufficient to mitigate VMT increase
- Initiation of new transit service
- Conversion of streets from one-way to two-way operation with no net increase in number of traffic lanes
- Removal or relocation of off-street or on-street parking spaces
- Adoption or modification of on-street parking or loading restrictions (including meters, time limits, accessible spaces, and preferential/reserved parking permit programs)
- Addition of traffic wayfinding signage
- Rehabilitation and maintenance projects that do not add motor vehicle capacity
- Addition of new or enhanced bike or pedestrian facilities on existing streets/highways or within existing public rights-of-way
- Addition of Class I bike paths, trails, multi-use paths, or other off-road facilities that serve nonmotorized travel
- Installation of publicly available alternative fuel/charging infrastructure
- Addition of passing lanes, truck climbing lanes, or truck brake-check lanes in rural areas that do not increase overall vehicle capacity along the corridor

1. Recommended Significance Threshold for Transportation Projects

As noted in Section 15064.3 of the CEQA Guidelines, lead agencies for roadway capacity projects have discretion, consistent with CEQA and planning requirements, to choose which metric to use to evaluate transportation impacts. This section recommends considerations for evaluating impacts using vehicle miles traveled. Lead agencies have discretion to choose a threshold of significance for transportation projects as they do for other types of projects. As explained above, Public Resources Code section 21099, subdivision (b)(1), provides that criteria for determining the significance of transportation impacts must promote the reduction of greenhouse gas emissions, the development of multimodal transportation networks, and a diversity of land uses. (<u>Id.;</u> see generally, adopted CEQA Guidelines, § 15064.3, subd. (b) [Criteria for Analyzing Transportation Impacts].) With those goals in mind, OPR prepared and the Agency adopted an appropriate transportation metric.

Whether adopting a threshold of significance, or evaluating transportation impacts on a case-by-case basis, a lead agency should ensure that the analysis addresses:

- Direct, indirect and cumulative effects of the transportation project (CEQA Guidelines, § 15064, subds. (d), (h))
- Near-term and long-term effects of the transportation project (CEQA Guidelines, §§ 15063, subd. (a)(1), 15126.2, subd. (a))
- The transportation project's consistency with state greenhouse gas reduction goals (Pub. Resources Code, § 21099)³⁴
- The impact of the transportation project on the development of multimodal transportation networks (Pub. Resources Code, § 21099)
- The impact of the transportation project on the development of a diversity of land uses (Pub. Resources Code, § 21099)

The CARB Scoping Plan and the CARB Mobile Source Strategy delineate VMT levels required to achieve legally mandated GHG emissions reduction targets. A lead agency should develop a project-level threshold based on those VMT levels, and may apply the following approach:

1. Propose a fair-share allocation of those budgets to their jurisdiction (e.g., by population);

³⁴ The California Air Resources Board has ascertained the limits of VMT growth compatible with California containing greenhouse gas emissions to levels research shows would allow for climate stabilization. (See *The 2017 Climate Change Scoping Plan: The Strategy for Achieving California's 2030 Greenhouse Gas Target* (p. 78, p. 101); *Mobile Source Strategy* (p. 37).) CARB's *Updated Final Staff Report on Proposed Update to the SB 375 Greenhouse Gas Emission Reduction Targets* illustrates that the current Regional Transportation Plans and Sustainable Communities Strategies will fall short of achieving the necessary on-road transportation-related GHG emissions reductions called for in the 2017 Scoping Plan (Figure 3, p. 35). Accordingly, OPR recommends not basing GHG emissions or transportation impact analysis for a transportation project solely on consistency with an RTP/SCS.

- 2. Determine the amount of VMT growth likely to result from background population growth, and subtract that from their "budget";
- 3. Allocate their jurisdiction's share between their various VMT-increasing transportation projects, using whatever criteria the lead agency prefers.

2. Estimating VMT Impacts from Transportation Projects

CEQA requires analysis of a project's potential growth-inducing impacts. (Pub. Resources Code, § 21100, subd. (b)(5); CEQA Guidelines, § 15126.2, subd. (d).) Many agencies are familiar with the analysis of growth inducing impacts associated with water, sewer, and other infrastructure. This technical advisory addresses growth that may be expected from roadway expansion projects.

Because a roadway expansion project can induce substantial VMT, incorporating quantitative estimates of induced VMT is critical to calculating both transportation and other impacts of these projects. Induced travel also has the potential to reduce or eliminate congestion relief benefits. An accurate estimate of induced travel is needed to accurately weigh costs and benefits of a highway capacity expansion project.

The effect of a transportation project on vehicle travel should be estimated using the "change in total VMT" method described in *Appendix 1*. This means that an assessment of total VMT without the project and an assessment with the project should be made; the difference between the two is the amount of VMT attributable to the project. The assessment should cover the full area in which driving patterns are expected to change. As with other types of projects, the VMT estimation should not be truncated at a modeling or jurisdictional boundary for convenience of analysis when travel behavior is substantially affected beyond that boundary.

Transit and Active Transportation Projects

Transit and active transportation projects generally reduce VMT and therefore are presumed to cause a less-than-significant impact on transportation. This presumption may apply to all passenger rail projects, bus and bus rapid transit projects, and bicycle and pedestrian infrastructure projects. Streamlining transit and active transportation projects aligns with each of the three statutory goals contained in SB 743 by reducing GHG emissions, increasing multimodal transportation networks, and facilitating mixed use development.

Roadway Projects

Reducing roadway capacity (for example, by removing or repurposing motor vehicle travel lanes) will generally reduce VMT and therefore is presumed to cause a less-than-significant impact on transportation. Generally, no transportation analysis is needed for such projects.

Building new roadways, adding roadway capacity in congested areas, or adding roadway capacity to areas where congestion is expected in the future, typically induces additional vehicle travel. For the types of projects previously indicated as likely to lead to additional vehicle travel, an estimate should be made of the change in vehicle travel resulting from the project.

For projects that increase roadway capacity, lead agencies can evaluate induced travel quantitatively by applying the results of existing studies that examine the magnitude of the increase of VMT resulting from a given increase in lane miles. These studies estimate the percent change in VMT for every percent change in miles to the roadway system (i.e., "elasticity"). ³⁵ Given that lead agencies have discretion in choosing their methodology, and the studies on induced travel reveal a range of elasticities, lead agencies may appropriately apply professional judgment in studying the transportation effects of a particular project. The most recent major study, estimates an elasticity of 1.0, meaning that every percent change in lane miles results in a one percent increase in VMT. ³⁶

To estimate VMT impacts from roadway expansion projects:

- 1. Determine the total lane-miles over an area that fully captures travel behavior changes resulting from the project (generally the region, but for projects affecting interregional travel look at all affected regions).
- 2. Determine the percent change in total lane miles that will result from the project.
- 3. Determine the total existing VMT over that same area.
- 4. Multiply the percent increase in lane miles by the existing VMT, and then multiply that by the elasticity from the induced travel literature:

[% increase in lane miles] x [existing VMT] x [elasticity] = [VMT resulting from the project]

A National Center for Sustainable Transportation tool can be used to apply this method: https://ncst.ucdavis.edu/research/tools

This method would not be suitable for rural (non-MPO) locations in the state which are neither congested nor projected to become congested. It also may not be suitable for a new road that provides new connectivity across a barrier (e.g., a bridge across a river) if it would be expected to substantially

³⁵ See U.C. Davis, Institute for Transportation Studies (Oct. 2015) *Increasing Highway Capacity Unlikely to Relieve Traffic Congestion*; Boarnet and Handy (Sept. 2014) *Impact of Highway Capacity and Induced Travel on Passenger Vehicle Use and Greenhouse Gas Emissions*, California Air Resources Board Policy Brief, available at https://www.arb.ca.gov/cc/sb375/policies/hwycapacity/highway_capacity_brief.pdf. ³⁶ See Duranton and Turner (2011) *The Fundamental Law of Road Congestion: Evidence from US cities*, available at http://www.nber.org/papers/w15376.

shorten existing trips. If it is likely to be substantial, the trips-shortening effect should be examined explicitly.

The effects of roadway capacity on vehicle travel can also be applied at a programmatic level. For example, in a regional planning process the lead agency can use that program-level analysis to streamline later project-level analysis. (See CEQA Guidelines, § 15168.) A program-level analysis of VMT should include effects of the program on land use patterns, and the VMT that results from those land use effects. In order for a program-level document to adequately analyze potential induced demand from a project or program of roadway capacity expansion, lead agencies cannot assume a fixed land use pattern (i.e., a land use pattern that does not vary in response to the provision of roadway capacity). A proper analysis should account for land use investment and development pattern changes that react in a reasonable manner to changes in accessibility created by transportation infrastructure investments (whether at the project or program level).

Mitigation and Alternatives

Induced VMT has the potential to reduce or eliminate congestion relief benefits, increase VMT, and increase other environmental impacts that result from vehicle travel.³⁷ If those effects are significant, the lead agency will need to consider mitigation or alternatives. In the context of increased travel that is induced by capacity increases, appropriate mitigation and alternatives that a lead agency might consider include the following:

- Tolling new lanes to encourage carpools and fund transit improvements
- Converting existing general purpose lanes to HOV or HOT lanes
- Implementing or funding off-site travel demand management
- Implementing Intelligent Transportation Systems (ITS) strategies to improve passenger throughput on existing lanes

Tolling and other management strategies can have the additional benefit of preventing congestion and maintaining free-flow conditions, conferring substantial benefits to road users as discussed above.

G. Analyzing Other Impacts Related to Transportation

While requiring a change in the methodology of assessing transportation impacts, Public Resources Code section 21099 notes that this change "does not relieve a public agency of the requirement to analyze a project's potentially significant transportation impacts related to air quality, noise, safety, or any other impact associated with transportation." OPR expects that lead agencies will continue to

³⁷ See National Center for Sustainable Transportation (Oct. 2015) *Increasing Highway Capacity Unlikely to Relieve Traffic Congestion*, available at http://www.dot.ca.gov/newtech/researchreports/reports/2015/10-12-2015-http://www.dot.ca.gov/newtech/researchreports/reports/2015/10-12-2015-http://www.dot.ca.gov/newtech/researchreports/reports/2015/10-12-2015-http://www.dot.ca.gov/newtech/researchreports/reports/2015/10-12-2015-http://www.dot.ca.gov/newtech/researchreports/reports/2015/10-12-2015-http://www.dot.ca.gov/newtech/researchreports/reports/2015/10-12-2015-http://www.newtech/researchreports/reports/reports/2015/10-12-2015-http://www.newtech/researchreports/reports/reports/reports/reports/reports/reports/2015/10-12-2015-http://www.newtech/researchreports/re

address mobile source emissions in the air quality and noise sections of an environmental document and the corresponding studies that support the analysis in those sections. Lead agencies should continue to address environmental impacts of a proposed project pursuant to CEQA's requirements, using a format that is appropriate for their particular project.

Because safety concerns result from many different factors, they are best addressed at a programmatic level (i.e., in a general plan or regional transportation plan) in cooperation with local governments, metropolitan planning organizations, and, where the state highway system is involved, the California Department of Transportation. In most cases, such an analysis would not be appropriate on a project-by-project basis. Increases in traffic volumes at a particular location resulting from a project typically cannot be estimated with sufficient accuracy or precision to provide useful information for an analysis of safety concerns. Moreover, an array of factors affect travel demand (e.g., strength of the local economy, price of gasoline), causing substantial additional uncertainty. Appendix B of OPR's General Plan Guidelines summarizes research which could be used to guide a programmatic analysis under CEQA. Lead agencies should note that automobile congestion or delay does not constitute a significant environmental impact (Pub. Resources Code, §21099(b)(2)), and safety should not be used as a proxy for road capacity.

H. VMT Mitigation and Alternatives

When a lead agency identifies a significant impact, it must identify feasible mitigation measures that could avoid or substantially reduce that impact. (Pub. Resources Code, § 21002.1, subd. (a).)

Additionally, CEQA requires that an environmental impact report identify feasible alternatives that could avoid or substantially reduce a project's significant environmental impacts.

Indeed, the California Court of Appeal recently held that a long-term regional transportation plan was deficient for failing to discuss an alternative which could significantly reduce total vehicle miles traveled. In *Cleveland National Forest Foundation v. San Diego Association of Governments, et al.* (2017) 17 Cal.App.5th 413, the court found that omission "inexplicable" given the lead agency's "acknowledgment in its Climate Action Strategy that the state's efforts to reduce greenhouse gas emissions from on-road transportation will not succeed if the amount of driving, or vehicle miles traveled, is not significantly reduced." (*Cleveland National Forest Foundation, supra,* 17 Cal.App.5th at p. 436.) Additionally, the court noted that the project alternatives focused primarily on congestion relief even though "the [regional] transportation plan is a long-term and congestion relief is not necessarily an effective long-term strategy." (*Id.* at p. 437.) The court concluded its discussion of the alternatives analysis by stating: "Given the acknowledged long-term drawbacks of congestion relief alternatives, there is not substantial evidence to support the EIR's exclusion of an alternative focused primarily on significantly reducing vehicle trips." (*Ibid.*)

Several examples of potential mitigation measures and alternatives to reduce VMT are described below. However, the selection of particular mitigation measures and alternatives are left to the discretion of

the lead agency, and mitigation measures may vary, depending on the proposed project and significant impacts, if any. Further, OPR expects that agencies will continue to innovate and find new ways to reduce vehicular travel.

Potential measures to reduce vehicle miles traveled include, but are not limited to:

- Improve or increase access to transit.
- Increase access to common goods and services, such as groceries, schools, and daycare.
- Incorporate affordable housing into the project.
- Incorporate neighborhood electric vehicle network.
- Orient the project toward transit, bicycle and pedestrian facilities.
- Improve pedestrian or bicycle networks, or transit service.
- Provide traffic calming.
- Provide bicycle parking.
- Limit or eliminate parking supply.
- Unbundle parking costs.
- Provide parking cash-out programs.
- Implement roadway pricing.
- Implement or provide access to a commute reduction program.
- Provide car-sharing, bike sharing, and ride-sharing programs.
- Provide transit passes.
- Shifting single occupancy vehicle trips to carpooling or vanpooling, for example providing ridematching services.
- Providing telework options.
- Providing incentives or subsidies that increase the use of modes other than single-occupancy vehicle.
- Providing on-site amenities at places of work, such as priority parking for carpools and vanpools, secure bike parking, and showers and locker rooms.
- Providing employee transportation coordinators at employment sites.
- Providing a guaranteed ride home service to users of non-auto modes.

Notably, because VMT is largely a regional impact, regional VMT-reduction programs may be an appropriate form of mitigation. In lieu fees have been found to be valid mitigation where there is both a commitment to pay fees and evidence that mitigation will actually occur. (*Save Our Peninsula Committee v. Monterey County Bd. of Supervisors* (2001) 87 Cal.App.4th 99, 140-141; *Gentry v. City of Murrieta* (1995) 36 Cal.App.4th 1359; *Kings County Farm Bureau v. City of Hanford* (1990) 221 Cal.App.3d 692, 727–728.) Fee programs are particularly useful to address cumulative impacts. (CEQA Guidelines, § 15130, subd. (a)(3) [a "project's incremental contribution is less than cumulatively considerable if the project is required to implement or fund its fair share of a mitigation measure or measures designed to alleviate the cumulative impact"].) The mitigation program must undergo CEQA evaluation, either on the program as a whole, or the in-lieu fees or other mitigation must be evaluated

on a project-specific basis. (*California Native Plant Society v. County of El Dorado* (2009) 170 Cal.App.4th 1026.) That CEQA evaluation could be part of a larger program, such as a regional transportation plan, analyzed in a Program EIR. (CEQA Guidelines, § 15168.)

Examples of project alternatives that may reduce vehicle miles traveled include, but are not limited to:

- Locate the project in an area of the region that already exhibits low VMT.
- Locate the project near transit.
- Increase project density.
- Increase the mix of uses within the project or within the project's surroundings.
- Increase connectivity and/or intersection density on the project site.
- Deploy management strategies (e.g., pricing, vehicle occupancy requirements) on roadways or roadway lanes.

Appendix 1. Considerations About Which VMT to Count

Consistent with the obligation to make a good faith effort to disclose the environmental consequences of a project, lead agencies have discretion to choose the most appropriate methodology to evaluate project impacts.³⁸ A lead agency can evaluate a project's effect on VMT in numerous ways. The purpose of this document is to provide technical considerations in determining which methodology may be most useful for various project types.

Background on Estimating Vehicle Miles Traveled

Before discussing specific methodological recommendations, this section provides a brief overview of modeling and counting VMT, including some key terminology.

Here is an illustrative example of some methods of estimating vehicle miles traveled. Consider the following hypothetical travel day (all by automobile):

- 1. Residence to Coffee Shop
- 2. Coffee Shop to Work
- 3. Work to Sandwich Shop
- 4. Sandwich Shop to Work
- 5. Work to Residence
- 6. Residence to Store
- 7. Store to Residence

Trip-based assessment of a project's effect on travel behavior counts VMT from individual trips to and from the project. It is the most basic, and traditionally the most common, method of counting VMT. A trip-based VMT assessment of the residence in the above example would consider segments 1, 5, 6 and 7. For residential projects, the sum of home-based trips is called *home-based* VMT.

A *tour-based* assessment counts the entire home-back-to-home tour that includes the project. A tour-based VMT assessment of the residence in the above example would consider segments 1, 2, 3, 4, and 5 in one tour, and 6 and 7 in a second tour. A tour-based assessment of the workplace would include segments 1, 2, 3, 4, and 5. Together, all tours comprise *household* VMT.

³⁸ The California Supreme Court has explained that when an agency has prepared an environmental impact report:

[T]he issue is not whether the [lead agency's] studies are irrefutable or whether they could have been better. The relevant issue is only whether the studies are sufficiently credible to be considered as part of the total evidence that supports the [lead agency's] finding[.]

(Laurel Heights Improvement Assn. v. Regents of the University of California (1988) 47 Cal.3d 376, 409; see also Eureka Citizens for Responsible Gov't v. City of Eureka (2007) 147 Cal.App.4th 357, 372.)

Both trip- and tour-based assessments can be used as measures of transportation efficiency, using denominators such as per capita, per employee, or per person-trip.

Trip- and Tour-based Assessment of VMT

As illustrated above, a tour-based assessment of VMT is a more complete characterization of a project's effect on VMT. In many cases, a project affects travel behavior beyond the first destination. The location and characteristics of the home and workplace will often be the main drivers of VMT. For example, a residential or office development located near high quality transit will likely lead to some commute trips utilizing transit, affecting mode choice on the rest of the tour.

Characteristics of an office project can also affect an employee's VMT beyond the work tour. For example, a workplace located at the urban periphery, far from transit, can require an employee to own a car, which in turn affects the entirety of an employee's travel behavior and VMT. For this reason, when estimating the effect of an office development on VMT, it may be appropriate to consider total employee VMT if data and tools, such as tour-based models, are available. This is consistent with CEQA's requirement to evaluate both direct and *indirect* effects of a project. (See CEQA Guidelines, § 15064, subd. (d)(2).)

Assessing Change in Total VMT

A third method, estimating the *change in total VMT* with and without the project, can evaluate whether a project is likely to divert existing trips, and what the effect of those diversions will be on total VMT. This method answers the question, "What is the net effect of the project on area VMT?" As an illustration, assessing the total change in VMT for a grocery store built in a food desert that diverts trips from more distant stores could reveal a net VMT reduction. The analysis should address the full area over which the project affects travel behavior, even if the effect on travel behavior crosses political boundaries.

Using Models to Estimate VMT

Travel demand models, sketch models, spreadsheet models, research, and data can all be used to calculate and estimate VMT (see Appendix F of the <u>preliminary discussion draft</u>). To the extent possible, lead agencies should choose models that have sensitivity to features of the project that affect VMT. Those tools and resources can also assist in establishing thresholds of significance and estimating VMT reduction attributable to mitigation measures and project alternatives. When using models and tools for those various purposes, agencies should use comparable data and methods, in order to set up an "apples-to-apples" comparison between thresholds, VMT estimates, and VMT mitigation estimates.

Models can work together. For example, agencies can use travel demand models or survey data to estimate existing trip lengths and input those into sketch models such as CalEEMod to achieve more

accurate results. Whenever possible, agencies should input localized trip lengths into a sketch model to tailor the analysis to the project location. However, in doing so, agencies should be careful to avoid double counting if the sketch model includes other inputs or toggles that are proxies for trip length (e.g., distance to city center). Generally, if an agency changes any sketch model defaults, it should record and report those changes for transparency of analysis. Again, trip length data should come from the same source as data used to calculate thresholds to be sure of an "apples-to-apples" comparison.

Additional background information regarding travel demand models is available in the California Transportation Commission's "2010 Regional Transportation Plan Guidelines," beginning at page 35.

Appendix 2. Induced Travel: Mechanisms, Research, and Additional Assessment Approaches

Induced travel occurs where roadway capacity is expanded in an area of present or projected future congestion. The effect typically manifests over several years. Lower travel times make the modified facility more attractive to travelers, resulting in the following trip-making changes:

- **Longer trips.** The ability to travel a long distance in a shorter time increases the attractiveness of destinations that are farther away, increasing trip length and vehicle travel.
- Changes in mode choice. When transportation investments are devoted to reducing automobile travel time, travelers tend to shift toward automobile use from other modes, which increases vehicle travel.
- Route changes. Faster travel times on a route attract more drivers to that route from other
 routes, which can increase or decrease vehicle travel depending on whether it shortens or
 lengthens trips.
- Newly generated trips. Increasing travel speeds can induce additional trips, which increases
 vehicle travel. For example, an individual who previously telecommuted or purchased goods on
 the internet might choose to accomplish those tasks via automobile trips as a result of increased
 speeds.
- Land Use Changes. Faster travel times along a corridor lead to land development farther along that corridor; that new development generates and attracts longer trips, which increases vehicle travel. Over several years, this induced growth component of induced vehicle travel can be substantial, making it critical to include in analyses.

Each of these effects has implications for the total amount of vehicle travel. These effects operate over different time scales. For example, changes in mode choice might occur immediately, while land use changes typically take a few years or longer. CEQA requires lead agencies to analyze both short-term and long-term effects.

Evidence of Induced Vehicle Travel. A large number of peer reviewed studies³⁹ have demonstrated a causal link between highway capacity increases and VMT increases. Many provide quantitative estimates of the magnitude of the induced VMT phenomenon. Collectively, they provide high quality evidence of the existence and magnitude of the induced travel effect.

http://www.dot.ca.gov/research/researchreports/reports/2015/10-12-2015-NCST Brief InducedTravel CS6 v3.pdf.

³⁹ See, e.g., Boarnet and Handy (Sept. 2014) Impact of Highway Capacity and Induced Travel on Passenger Vehicle Use and Greenhouse Gas Emissions, California Air Resources Board Policy Brief, available at https://www.arb.ca.gov/cc/sb375/policies/hwycapacity/highway_capacity_brief.pdf; National Center for Sustainable Transportation (Oct. 2015) *Increasing Highway Capacity Unlikely to Relieve Traffic Congestion*, available at

Most of these studies express the amount of induced vehicle travel as an "elasticity," which is a multiplier that describes the additional vehicle travel resulting from an additional lane mile of roadway capacity added. For example, an elasticity of 0.6 would signify an 0.6 percent increase in vehicle travel for every 1.0 percent increase in lane miles. Many of these studies distinguish "short run elasticity" (increase in vehicle travel in the first few years) from "long run elasticity" (increase in vehicle travel beyond the first few years). Long run elasticity is larger than short run elasticity, because as time passes, more of the components of induced vehicle travel materialize. Generally, short run elasticity can be thought of as excluding the effects of land use change, while long run elasticity includes them. Most studies find a long run elasticity between 0.6 and just over 1.0,40 meaning that every increase in lanes miles of one percent leads to an increase in vehicle travel of 0.6 to 1.0 percent. The most recent major study finds the elasticity of vehicle travel by lanes miles added to be 1.03; in other words, each percent increase in lane miles results in a 1.03 percent increase in vehicle travel. ⁴¹ (An elasticity greater than 1.0 can occur because new lanes induce vehicle travel that spills beyond the project location.) In CEQA analysis, the long-run elasticity should be used, as it captures the full effect of the project rather than just the early-stage effect.

Quantifying Induced Vehicle Travel Using Models. Lead agencies can generally achieve the most accurate assessment of induced vehicle travel resulting from roadway capacity increasing projects by applying elasticities from the academic literature, because those estimates include vehicle travel resulting from induced land use. If a lead agency chooses to use a travel demand model, additional analysis would be needed to account for induced land use. This section describes some approaches to undertaking that additional analysis.

Proper use of a travel demand model can capture the following components of induced VMT:

- Trip length (generally increases VMT)
- Mode shift (generally shifts from other modes toward automobile use, increasing VMT)
- Route changes (can act to increase or decrease VMT)
- Newly generated trips (generally increases VMT)
 - Note that not all travel demand models have sensitivity to this factor, so an off-model estimate may be necessary if this effect could be substantial.

However, estimating long-run induced VMT also requires an estimate of the project's effects on land use. This component of the analysis is important because it has the potential to be a large component of

⁴⁰ See Boarnet and Handy (Sept. 2014) <u>Impact of Highway Capacity and Induced Travel on Passenger</u>
<u>Vehicle Use and Greenhouse Gas Emissions</u>, California Air Resources Board Policy Brief, p. 2, available at https://www.arb.ca.gov/cc/sb375/policies/hwycapacity/highway capacity brief.pdf.

⁴¹ Duranton and Turner (2011) *The Fundamental Law of Road Congestion: Evidence from US cities,* available at http://www.nber.org/papers/w15376.

the overall induced travel effect. Options for estimating and incorporating the VMT effects that are caused by the subsequent land use changes include:

- 1. *Employ an expert panel*. An expert panel could assess changes to land use development that would likely result from the project. This assessment could then be analyzed by the travel demand model to assess effects on vehicle travel. Induced vehicle travel assessed via this approach should be verified using elasticities found in the academic literature.
- 2. Adjust model results to align with the empirical research. If the travel demand model analysis is performed without incorporating projected land use changes resulting from the project, the assessed vehicle travel should be adjusted upward to account for those land use changes. The assessed VMT after adjustment should fall within the range found in the academic literature.
- 3. Employ a land use model, running it iteratively with a travel demand model. A land use model can be used to estimate the land use effects of a roadway capacity increase, and the traffic patterns that result from the land use change can then be fed back into the travel demand model. The land use model and travel demand model can be iterated to produce an accurate result.

A project which provides new connectivity across a barrier, such as a new bridge across a river, may provide a shortened path between existing origins and destinations, thereby shortening existing trips. In rare cases, this trip-shortening effect might be substantial enough to reduce the amount of vehicle travel resulting from the project below the range found in the elasticities in the academic literature, or even lead a net reduction in vehicle travel overall. In such cases, the trip-shortening effect could be examined explicitly.

Whenever employing a travel demand model to assess induced vehicle travel, any limitation or known lack of sensitivity in the analysis that might cause substantial errors in the VMT estimate (for example, model insensitivity to one of the components of induced VMT described above) should be disclosed and characterized, and a description should be provided on how it could influence the analysis results. A discussion of the potential error or bias should be carried into analyses that rely on the VMT analysis, such as greenhouse gas emissions, air quality, energy, and noise.

APPENDIX B

PROPOSED MITIGATION STRATEGIES FOR IMPLEMENTATION OF SB 743

This page intentionally left blank

Proposed Mitigation Strategies for Implementation of SB 743

Categories	Mitigation Strategies	Proposed Language
Tier 1 - On-Site Improvements	Pedestrian Network Improvements Incorporate Bike Lane Street Design	1. Pedestrian Network Improvements shall be incorporated into a project site plan that provide pedestrian walkway access from a building entrance/exit to other buildings on the project site and a
On-Site Improvements	'	project site plan that provide pedestrian walkway access from a

Proposed Mitigation Strategies for Implementation of SB 743

Categories	Mitigation Strategies	Proposed Language
Tier 2 -	9. Project contributions to infrastructure improvement projects	9. Should a program be adopted in the future, this will be an option for Applicants. ⁶
Financial Incentives	10. School pool program	
	11. Subsidize vanpool for housing developments	10 . Each residential project would provide new homebuyers with a flyer describing the time and cost savings of carpooling. ⁷
	12. Provide car-sharing, bike-sharing or ride-sharing programs	11. Each residential project would provide new homebuyers or resale homebuyers with vouchers for each applicable commercial
	13. Provide subsidized transit passes	vanpool service for the period of time they own the home. 8
		12. Each residential project would provide new homebuyers or resale homebuyers with flyers detailing the car-sharing, bikesharing, or ride-sharing programs, documenting the time and cost savings of each. Non-residential projects would provide each employee with this flyer and post the flyer in a lunch room or break room location. 8
		13 . Each residential project would provide new homebuyers or resale homebuyers with transit subsidies for the period of time they own the home. Non-residential projects would provide each employee with access to transit subsidies. 8

Notes:

- 1. The Pedestrian Network Improvements should provide intra-project connectivity and connectivity off-site.
- 2. A Class II bike lane represents a minimum standard. Class I off-street bike paths or Class IV bike boulevards could also be included and may result in greater usage and a greater reduction in VMTs.
- 3. TCMs are going to vary significantly among project types (residential v. commercial, etc.) and the size of the project envelope, and the types of TCMs that could be included. Project applicants should ensure measures are appropriate for the proposed project.
- 4. The density bonus in the Zoning Code applies to residential. However, appropriate measures may be applied to a non-residential project at the discretion of the County where VMT reduction may result.
- 5. In accordance with the 2019 California Green Building Standards Code for non-residential developments, short-term bicycle parking will require 5% of motorized vehicle parking spaces with a minimum of one two-bike rack. Long-term bicycle parking will require 5% of tenant-occupant vehicular parking spaces with a minimum of one bike parking facility.
- 6. The particular type of infrastructure project should be determined, as some would be more applicable than others. Also, the fee increment would have to be calculated.
- 7. Actual metrics on how much time and money would be saved should be provided that are specific to the project area.
- 8. Coordination would be the responsibility of the project applicant.

This page intentionally left blank

