
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International
5 Hutton Centre Drive, Suite 500
Santa Ana, CA 92707

***** DESCRIPTION OF STUDY *****
* SAN JUAN CREEK WATERSHED STUDY - RATIONAL METHOD *
* REGIONAL WATERSHED S19- FREE DRAINING *
* 100-YR RM EV MARCH 2019 FKAZI *

FILE NAME: RU00EV19.DAT
TIME/DATE OF STUDY: 11:52 03/29/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 100.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 6.126
- 2) 10.00; 3.913
- 3) 15.00; 3.013
- 4) 20.00; 2.470
- 5) 25.00; 2.132
- 6) 30.00; 1.903
- 7) 40.00; 1.647
- 8) 50.00; 1.421
- 9) 60.00; 1.323
- 10) 90.00; 1.122
- 11) 120.00; 0.987
- 12) 180.00; 0.829
- 13) 360.00; 0.620
- 14) 1200.00; 0.273

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 11900.00 TO NODE 11901.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 295.79
ELEVATION DATA: UPSTREAM(FEET) = 2369.48 DOWNSTREAM(FEET) = 2332.92

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 7.203
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 5.151
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
RESIDENTIAL ".4 DWELLING/ACRE"	-	1.62	0.30	0.999	0	7.20

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999
SUBAREA RUNOFF(CFS) = 7.07
TOTAL AREA(ACRES) = 1.62 PEAK FLOW RATE(CFS) = 7.07

FLOW PROCESS FROM NODE 11901.00 TO NODE 11902.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2332.92 DOWNSTREAM(FEET) = 2297.70
CHANNEL LENGTH THRU SUBAREA(FEET) = 664.26 CHANNEL SLOPE = 0.0530
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.61
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.842
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.35	0.30	0.906	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.906
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 20.64
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.47
AVERAGE FLOW DEPTH(FEET) = 0.54 TRAVEL TIME(MIN.) = 3.19
Tc(MIN.) = 10.39
SUBAREA AREA(ACRES) = 8.35 SUBAREA RUNOFF(CFS) = 26.83
EFFECTIVE AREA(ACRES) = 9.97 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 10.0 PEAK FLOW RATE(CFS) = 32.00
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.69

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.69 FLOW VELOCITY(FEET/SEC.) = 4.07
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11902.00 = 960.05 FEET.

FLOW PROCESS FROM NODE 11902.00 TO NODE 11902.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2297.70 DOWNSTREAM(FEET) = 2263.40
CHANNEL LENGTH THRU SUBAREA(FEET) = 928.77 CHANNEL SLOPE = 0.0369
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 1.37
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.267

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	34.48	0.30	0.904	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.904
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 78.78
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.84
AVERAGE FLOW DEPTH(FEET) = 1.29 TRAVEL TIME(MIN.) = 3.20
Tc(MIN.) = 13.59

SUBAREA AREA(ACRES) = 34.48 SUBAREA RUNOFF(CFS) = 92.97
EFFECTIVE AREA(ACRES) = 44.45 AREA-AVERAGED Fm(INCH/HR) = 0.27
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.91
TOTAL AREA(ACRES) = 44.5 PEAK FLOW RATE(CFS) = 119.81
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.64

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.64 FLOW VELOCITY(FEET/SEC.) = 5.52
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11902.50 = 1888.82 FEET.

FLOW PROCESS FROM NODE 11902.50 TO NODE 11903.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2263.40 DOWNSTREAM(FEET) = 2252.14
CHANNEL LENGTH THRU SUBAREA(FEET) = 895.50 CHANNEL SLOPE = 0.0126
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 2.49
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.763

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	23.65	0.30	0.958	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.958
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 146.20
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.02
AVERAGE FLOW DEPTH(FEET) = 2.44 TRAVEL TIME(MIN.) = 3.71

Tc(MIN.) = 17.30
SUBAREA AREA(ACRES) = 23.65 SUBAREA RUNOFF(CFS) = 52.69
EFFECTIVE AREA(ACRES) = 68.10 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 68.1 PEAK FLOW RATE(CFS) = 152.33
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.50

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.50 FLOW VELOCITY(FEET/SEC.) = 4.06
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11903.00 = 2784.32 FEET.

FLOW PROCESS FROM NODE 11903.00 TO NODE 11904.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2252.14 DOWNSTREAM(FEET) = 2186.04
CHANNEL LENGTH THRU SUBAREA(FEET) = 1924.35 CHANNEL SLOPE = 0.0343
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 2.38
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.315

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	68.53	0.30	0.961	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.961
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 215.00
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.43
AVERAGE FLOW DEPTH(FEET) = 2.29 TRAVEL TIME(MIN.) = 4.99
Tc(MIN.) = 22.29

SUBAREA AREA(ACRES) = 68.53 SUBAREA RUNOFF(CFS) = 125.00
EFFECTIVE AREA(ACRES) = 136.63 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94
TOTAL AREA(ACRES) = 136.6 PEAK FLOW RATE(CFS) = 249.87
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.49

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.49 FLOW VELOCITY(FEET/SEC.) = 6.70
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11904.00 = 4708.67 FEET.

FLOW PROCESS FROM NODE 11904.00 TO NODE 11905.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2186.04 DOWNSTREAM(FEET) = 1957.34
CHANNEL LENGTH THRU SUBAREA(FEET) = 1926.87 CHANNEL SLOPE = 0.1187
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 1.99

* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.122
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 63.15 0.30 1.000 -
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 301.67
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 10.98
 AVERAGE FLOW DEPTH (FEET) = 1.97 TRAVEL TIME (MIN.) = 2.93
 Tc (MIN.) = 25.22
 SUBAREA AREA (ACRES) = 63.15 SUBAREA RUNOFF (CFS) = 103.55
 EFFECTIVE AREA (ACRES) = 199.78 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
 TOTAL AREA (ACRES) = 199.8 PEAK FLOW RATE (CFS) = 329.70
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 2.07

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 2.07 FLOW VELOCITY (FEET/SEC.) = 11.26
 LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11905.00 = 6635.54 FEET.

FLOW PROCESS FROM NODE 11905.00 TO NODE 11906.00 IS CODE = 56

 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 1957.34 DOWNSTREAM (FEET) = 1244.16
 CHANNEL LENGTH THRU SUBAREA (FEET) = 2498.96 CHANNEL SLOPE = 0.2854
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 1.81
 * 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.004
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 84.87 0.30 1.000 -
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 394.80
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 16.18
 AVERAGE FLOW DEPTH (FEET) = 1.80 TRAVEL TIME (MIN.) = 2.57
 Tc (MIN.) = 27.79
 SUBAREA AREA (ACRES) = 84.87 SUBAREA RUNOFF (CFS) = 130.16
 EFFECTIVE AREA (ACRES) = 284.65 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA (ACRES) = 284.6 PEAK FLOW RATE (CFS) = 438.66
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 1.90

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 1.90 FLOW VELOCITY (FEET/SEC.) = 16.70
 LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11906.00 = 9134.50 FEET.

FLOW PROCESS FROM NODE 11906.00 TO NODE 11920.00 IS CODE = 56

 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 1244.16 DOWNSTREAM (FEET) = 873.95
 CHANNEL LENGTH THRU SUBAREA (FEET) = 3370.75 CHANNEL SLOPE = 0.1098
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 2.89
 * 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.848
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 199.43 0.30 1.000 -
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 577.66
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 12.91
 AVERAGE FLOW DEPTH (FEET) = 2.85 TRAVEL TIME (MIN.) = 4.35
 Tc (MIN.) = 32.15
 SUBAREA AREA (ACRES) = 199.43 SUBAREA RUNOFF (CFS) = 277.86
 EFFECTIVE AREA (ACRES) = 484.08 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
 TOTAL AREA (ACRES) = 484.1 PEAK FLOW RATE (CFS) = 676.56
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 3.10

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 3.10 FLOW VELOCITY (FEET/SEC.) = 13.47
 LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11920.00 = 12505.25 FEET.

FLOW PROCESS FROM NODE 11906.00 TO NODE 11920.00 IS CODE = 1

 >>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
 TIME OF CONCENTRATION (MIN.) = 32.15
 RAINFALL INTENSITY (INCH/HR) = 1.85
 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.98
 EFFECTIVE STREAM AREA (ACRES) = 484.08
 TOTAL STREAM AREA (ACRES) = 484.08
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 676.56

FLOW PROCESS FROM NODE 11910.00 TO NODE 11911.00 IS CODE = 21

 >>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH (FEET) = 517.62
 ELEVATION DATA: UPSTREAM (FEET) = 2531.88 DOWNSTREAM (FEET) = 2441.33

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
 SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 12.185
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.520
 SUBAREA Tc AND LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)
 NATURAL FAIR COVER
 "CHAPARRAL,BROADLEAF" - 3.46 0.30 1.000 0 12.19
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA RUNOFF(CFS) = 10.03
 TOTAL AREA(ACRES) = 3.46 PEAK FLOW RATE(CFS) = 10.03

 FLOW PROCESS FROM NODE 11911.00 TO NODE 11912.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2441.33 DOWNSTREAM(FEET) = 2382.20
 CHANNEL LENGTH THRU SUBAREA(FEET) = 397.30 CHANNEL SLOPE = 0.1488
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 0.37
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.259
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 5.79 0.30 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 17.75
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.58
 AVERAGE FLOW DEPTH(FEET) = 0.36 TRAVEL TIME(MIN.) = 1.45
 Tc(MIN.) = 13.63
 SUBAREA AREA(ACRES) = 5.79 SUBAREA RUNOFF(CFS) = 15.42
 EFFECTIVE AREA(ACRES) = 9.25 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 9.2 PEAK FLOW RATE(CFS) = 24.64
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 0.44

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 0.44 FLOW VELOCITY(FEET/SEC.) = 5.18
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11912.00 = 914.92 FEET.

 FLOW PROCESS FROM NODE 11912.00 TO NODE 11913.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2382.20 DOWNSTREAM(FEET) = 2263.77
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1891.47 CHANNEL SLOPE = 0.0626
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 1.25

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.579
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 54.30 0.30 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 81.10
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.88
 AVERAGE FLOW DEPTH(FEET) = 1.13 TRAVEL TIME(MIN.) = 5.36
 Tc(MIN.) = 19.00
 SUBAREA AREA(ACRES) = 54.30 SUBAREA RUNOFF(CFS) = 111.38
 EFFECTIVE AREA(ACRES) = 63.55 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 63.5 PEAK FLOW RATE(CFS) = 130.36
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 1.48

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 1.48 FLOW VELOCITY(FEET/SEC.) = 6.81
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11913.00 = 2806.39 FEET.

 FLOW PROCESS FROM NODE 11913.00 TO NODE 11914.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2263.77 DOWNSTREAM(FEET) = 1845.23
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1957.31 CHANNEL SLOPE = 0.2138
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 1.32
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.349
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 65.14 0.30 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 190.50
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.69
 AVERAGE FLOW DEPTH(FEET) = 1.29 TRAVEL TIME(MIN.) = 2.79
 Tc(MIN.) = 21.79
 SUBAREA AREA(ACRES) = 65.14 SUBAREA RUNOFF(CFS) = 120.15
 EFFECTIVE AREA(ACRES) = 128.69 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 128.7 PEAK FLOW RATE(CFS) = 237.36
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 1.47

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 1.47 FLOW VELOCITY(FEET/SEC.) = 12.50
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11914.00 = 4763.70 FEET.

FLOW PROCESS FROM NODE 11914.00 TO NODE 11915.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1845.23 DOWNSTREAM(FEET) = 1557.21
CHANNEL LENGTH THRU SUBAREA(FEET) = 1686.78 CHANNEL SLOPE = 0.1708
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 1.81
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.198

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 78.52 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 304.43

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.52

AVERAGE FLOW DEPTH(FEET) = 1.79 TRAVEL TIME(MIN.) = 2.24

Tc(MIN.) = 24.03

SUBAREA AREA(ACRES) = 78.52 SUBAREA RUNOFF(CFS) = 134.10

EFFECTIVE AREA(ACRES) = 207.21 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 207.2 PEAK FLOW RATE(CFS) = 353.89

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 1.95

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.95 FLOW VELOCITY(FEET/SEC.) = 13.07

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11915.00 = 6450.48 FEET.

FLOW PROCESS FROM NODE 11915.00 TO NODE 11916.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1557.21 DOWNSTREAM(FEET) = 1403.38
CHANNEL LENGTH THRU SUBAREA(FEET) = 1909.39 CHANNEL SLOPE = 0.0806
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 2.60
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.037

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 70.48 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 409.00

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.45

AVERAGE FLOW DEPTH(FEET) = 2.58 TRAVEL TIME(MIN.) = 3.05

Tc(MIN.) = 27.08

SUBAREA AREA(ACRES) = 70.48 SUBAREA RUNOFF(CFS) = 110.18

EFFECTIVE AREA(ACRES) = 277.69 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 277.7 PEAK FLOW RATE(CFS) = 434.11
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.66

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.66 FLOW VELOCITY(FEET/SEC.) = 10.65

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11916.00 = 8359.87 FEET.

FLOW PROCESS FROM NODE 11916.00 TO NODE 11917.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1403.38 DOWNSTREAM(FEET) = 1079.99
CHANNEL LENGTH THRU SUBAREA(FEET) = 1945.82 CHANNEL SLOPE = 0.1662
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 2.64
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.939

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 232.20 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 605.42

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 15.15

AVERAGE FLOW DEPTH(FEET) = 2.62 TRAVEL TIME(MIN.) = 2.14

Tc(MIN.) = 29.22

SUBAREA AREA(ACRES) = 232.20 SUBAREA RUNOFF(CFS) = 342.51

EFFECTIVE AREA(ACRES) = 509.89 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 509.9 PEAK FLOW RATE(CFS) = 752.12

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 2.94

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.94 FLOW VELOCITY(FEET/SEC.) = 16.11

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11917.00 = 10305.69 FEET.

FLOW PROCESS FROM NODE 11917.00 TO NODE 11920.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1079.99 DOWNSTREAM(FEET) = 873.95
CHANNEL LENGTH THRU SUBAREA(FEET) = 2563.91 CHANNEL SLOPE = 0.0804
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 3.74

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.837

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

USER-DEFINED - 110.82 0.30 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 828.79
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.74
 AVERAGE FLOW DEPTH(FEET) = 3.73 TRAVEL TIME(MIN.) = 3.36
 Tc(MIN.) = 32.57
 SUBAREA AREA(ACRES) = 110.82 SUBAREA RUNOFF(CFS) = 153.32
 EFFECTIVE AREA(ACRES) = 620.71 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 620.7 PEAK FLOW RATE(CFS) = 858.76
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 3.80

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 3.80 FLOW VELOCITY(FEET/SEC.) = 12.86
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11920.00 = 12869.60 FEET.

 FLOW PROCESS FROM NODE 11917.00 TO NODE 11920.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
 TIME OF CONCENTRATION(MIN.) = 32.57
 RAINFALL INTENSITY(INCH/HR) = 1.84
 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 1.00
 EFFECTIVE STREAM AREA(ACRES) = 620.71
 TOTAL STREAM AREA(ACRES) = 620.71
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 858.76

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	676.56	32.15	1.848	0.30(0.30)	0.98	484.1	11900.00
2	858.76	32.57	1.837	0.30(0.30)	1.00	620.7	11910.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1530.12	32.15	1.848	0.30(0.30)	0.99	1096.7	11900.00
2	1530.59	32.57	1.837	0.30(0.30)	0.99	1104.8	11910.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 1530.59 Tc(MIN.) = 32.57
 EFFECTIVE AREA(ACRES) = 1104.79 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 1104.8
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11920.00 = 12869.60 FEET.

 FLOW PROCESS FROM NODE 11920.00 TO NODE 11921.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 873.95 DOWNSTREAM(FEET) = 827.94
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1417.25 CHANNEL SLOPE = 0.0325
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 6.45
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.782

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	107.47	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1602.24
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.86
 AVERAGE FLOW DEPTH(FEET) = 6.44 TRAVEL TIME(MIN.) = 2.17
 Tc(MIN.) = 34.75

SUBAREA AREA(ACRES) = 107.47 SUBAREA RUNOFF(CFS) = 143.30
 EFFECTIVE AREA(ACRES) = 1212.26 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 1212.3 PEAK FLOW RATE(CFS) = 1618.54
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 6.47

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 6.47 FLOW VELOCITY(FEET/SEC.) = 10.89
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11921.00 = 14286.85 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1619.54	34.32	1.792	0.30(0.30)	0.99	1204.2	11900.00
2	1618.54	34.75	1.782	0.30(0.30)	0.99	1212.3	11910.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 1619.54 Tc(MIN.) = 34.32
 AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 1204.17

 FLOW PROCESS FROM NODE 11921.00 TO NODE 11922.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 827.94 DOWNSTREAM(FEET) = 753.55
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1886.43 CHANNEL SLOPE = 0.0394
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 6.59
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.726

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	107.47	0.30	1.000	-

LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 344.27 0.30 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1840.46
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.10
 AVERAGE FLOW DEPTH(FEET) = 6.57 TRAVEL TIME(MIN.) = 2.60
 Tc(MIN.) = 36.92
 SUBAREA AREA(ACRES) = 344.27 SUBAREA RUNOFF(CFS) = 441.81
 EFFECTIVE AREA(ACRES) = 1548.44 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 1556.5 PEAK FLOW RATE(CFS) = 1989.26
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 6.82

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 6.82 FLOW VELOCITY(FEET/SEC.) = 12.35
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11922.00 = 16173.28 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1989.26	36.92	1.726	0.30(0.30)	0.99	1548.4	11900.00
2	1984.41	37.34	1.715	0.30(0.30)	1.00	1556.5	11910.00

NEW PEAK FLOW DATA ARE:
 PEAK FLOW RATE(CFS) = 1989.26 Tc(MIN.) = 36.92
 AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 1548.44

 FLOW PROCESS FROM NODE 11922.00 TO NODE 11923.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 753.55 DOWNSTREAM(FEET) = 641.58
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2860.88 CHANNEL SLOPE = 0.0391
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 7.00
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.630
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	165.18	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2088.15
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.47
 AVERAGE FLOW DEPTH(FEET) = 6.99 TRAVEL TIME(MIN.) = 3.82
 Tc(MIN.) = 40.74
 SUBAREA AREA(ACRES) = 165.18 SUBAREA RUNOFF(CFS) = 197.76
 EFFECTIVE AREA(ACRES) = 1713.62 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 1721.7 PEAK FLOW RATE(CFS) = 2053.72
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 6.93

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 6.93 FLOW VELOCITY(FEET/SEC.) = 12.42
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11923.00 = 19034.16 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2053.72	40.74	1.630	0.30(0.30)	1.00	1713.6	11900.00
2	2048.46	41.17	1.621	0.30(0.30)	1.00	1721.7	11910.00

NEW PEAK FLOW DATA ARE:
 PEAK FLOW RATE(CFS) = 2053.72 Tc(MIN.) = 40.74
 AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 1.00 EFFECTIVE AREA(ACRES) = 1713.62

 FLOW PROCESS FROM NODE 11923.00 TO NODE 11924.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 641.58 DOWNSTREAM(FEET) = 579.89
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1844.02 CHANNEL SLOPE = 0.0335
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 7.60
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.573

S19-24

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	433.73	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2302.13
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.07
 AVERAGE FLOW DEPTH(FEET) = 7.58 TRAVEL TIME(MIN.) = 2.55
 Tc(MIN.) = 43.29
 SUBAREA AREA(ACRES) = 433.73 SUBAREA RUNOFF(CFS) = 496.81
 EFFECTIVE AREA(ACRES) = 2147.35 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 2155.4 PEAK FLOW RATE(CFS) = 2461.77
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 7.82

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 7.82 FLOW VELOCITY(FEET/SEC.) = 12.27
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11924.00 = 20878.18 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2461.77	43.29	1.573	0.30(0.30)	1.00	2147.4	11900.00
2	2452.21	43.72	1.563	0.30(0.30)	1.00	2155.4	11910.00

NEW PEAK FLOW DATA ARE:
 PEAK FLOW RATE(CFS) = 2461.77 Tc(MIN.) = 43.29
 AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 1.00 EFFECTIVE AREA(ACRES) = 2147.35

FLOW PROCESS FROM NODE 11924.00 TO NODE 11925.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 579.89 DOWNSTREAM(FEET) = 494.12
CHANNEL LENGTH THRU SUBAREA(FEET) = 2756.15 CHANNEL SLOPE = 0.0311
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 8.18
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.487

S19-25

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 265.42 0.30 1.000 -

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2603.57
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.12
AVERAGE FLOW DEPTH(FEET) = 8.16 TRAVEL TIME(MIN.) = 3.79
Tc(MIN.) = 47.08

SUBAREA AREA(ACRES) = 265.42 SUBAREA RUNOFF(CFS) = 283.56
EFFECTIVE AREA(ACRES) = 2412.77 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 2420.9 PEAK FLOW RATE(CFS) = 2579.81
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 8.13

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 8.13 FLOW VELOCITY(FEET/SEC.) = 12.09
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11925.00 = 23634.33 FEET.

** PEAK FLOW RATE TABLE **

STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 2579.81 47.08 1.487 0.30(0.30) 1.00 2412.8 11900.00
2 2567.11 47.51 1.477 0.30(0.30) 1.00 2420.9 11910.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2579.81 Tc(MIN.) = 47.08
AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 1.00 EFFECTIVE AREA(ACRES) = 2412.77

FLOW PROCESS FROM NODE 11925.00 TO NODE 11926.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 494.12 DOWNSTREAM(FEET) = 458.40
CHANNEL LENGTH THRU SUBAREA(FEET) = 1922.70 CHANNEL SLOPE = 0.0186
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 9.23
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.418

S19-26

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 97.46 0.30 1.000 -

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2628.86
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.03
AVERAGE FLOW DEPTH(FEET) = 9.22 TRAVEL TIME(MIN.) = 3.20
Tc(MIN.) = 50.28

SUBAREA AREA(ACRES) = 97.46 SUBAREA RUNOFF(CFS) = 98.10
EFFECTIVE AREA(ACRES) = 2510.23 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 2518.3 PEAK FLOW RATE(CFS) = 2579.81
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 9.14

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 9.14 FLOW VELOCITY(FEET/SEC.) = 9.98
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11926.00 = 25557.03 FEET.

** PEAK FLOW RATE TABLE **

STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 2579.81 50.28 1.418 0.30(0.30) 1.00 2510.2 11900.00
2 2567.11 50.71 1.414 0.30(0.30) 1.00 2518.3 11910.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2579.81 Tc(MIN.) = 50.28
AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 1.00 EFFECTIVE AREA(ACRES) = 2510.23

FLOW PROCESS FROM NODE 11926.00 TO NODE 11927.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 458.40 DOWNSTREAM(FEET) = 399.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 2170.13 CHANNEL SLOPE = 0.0274
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 8.41
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.388

S19-27

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 53.83 0.30 1.000 -

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2606.16
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.55
AVERAGE FLOW DEPTH(FEET) = 8.41 TRAVEL TIME(MIN.) = 3.13
Tc(MIN.) = 53.41

SUBAREA AREA(ACRES) = 53.83 SUBAREA RUNOFF(CFS) = 52.70
EFFECTIVE AREA(ACRES) = 2564.06 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA (ACRES) = 2572.1 PEAK FLOW RATE (CFS) = 2579.81
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 8.37

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 8.37 FLOW VELOCITY (FEET/SEC.) = 11.52
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 27727.16 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2579.81	53.41	1.388	0.30 (0.30)	1.00	2564.1	11900.00
2	2567.11	53.85	1.383	0.30 (0.30)	1.00	2572.1	11910.00

NEW PEAK FLOW DATA ARE:
 PEAK FLOW RATE (CFS) = 2579.81 Tc (MIN.) = 53.41
 AREA-AVERAGED Fm (INCH/HR) = 0.30 AREA-AVERAGED Fp (INCH/HR) = 0.30
 AREA-AVERAGED Ap = 1.00 EFFECTIVE AREA (ACRES) = 2564.06

 FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<<
 =====

 FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<<
 =====

PEAK FLOWRATE TABLE FILE NAME: P401XXCE.DNA
 MEMORY BANK # 1 DEFINED AS FOLLOWS:

HZ-401

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	944.38	25.32	0.30 (0.30)	1.00	624.3	40130.00
2	939.28	27.13	0.30 (0.30)	1.00	654.2	40100.00
TOTAL AREA (ACRES) = 654.2						

 FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<<
 =====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2579.81	53.41	1.388	0.30 (0.30)	1.00	2564.1	11900.00
2	2567.11	53.85	1.383	0.30 (0.30)	1.00	2572.1	11910.00
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 27727.16 FEET.							

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	944.38	25.32	2.118	0.30 (0.30)	1.00	624.3	40130.00
2	939.28	27.13	2.034	0.30 (0.30)	1.00	654.2	40100.00
LONGEST FLOWPATH FROM NODE 40100.00 TO NODE 11927.00 = 10245.00 FEET.							

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2987.26	25.32	2.118	0.30 (0.30)	1.00	1839.8	40130.00
2	3028.60	27.13	2.034	0.30 (0.30)	1.00	1956.9	40100.00
3	3168.88	53.41	1.388	0.30 (0.30)	1.00	3218.3	11900.00
4	3153.84	53.85	1.383	0.30 (0.30)	1.00	3226.4	11910.00
TOTAL AREA (ACRES) = 3226.4							

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
 PEAK FLOW RATE (CFS) = 3168.88 Tc (MIN.) = 53.406
 EFFECTIVE AREA (ACRES) = 3218.26 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 3226.4
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 27727.16 FEET.

 FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<<
 =====

 FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<<
 =====

ELEVATION DATA: UPSTREAM (FEET) = 399.00 DOWNSTREAM (FEET) = 384.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 986.26 CHANNEL SLOPE = 0.0152
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 10.49
 CHANNEL FLOW THRU SUBAREA (CFS) = 3168.88
 FLOW VELOCITY (FEET/SEC.) = 9.76 FLOW DEPTH (FEET) = 10.49
 TRAVEL TIME (MIN.) = 1.68 Tc (MIN.) = 55.09
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.50 = 28713.42 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2987.26	27.03	2.039	0.30 (0.30)	1.00	1839.8	40130.00
2	3028.60	28.84	1.956	0.30 (0.30)	1.00	1956.9	40100.00
3	3168.88	55.09	1.371	0.30 (0.30)	1.00	3218.3	11900.00
4	3153.84	55.53	1.367	0.30 (0.30)	1.00	3226.4	11910.00

NEW PEAK FLOW DATA ARE:
 PEAK FLOW RATE (CFS) = 3168.88 Tc (MIN.) = 55.09
 AREA-AVERAGED Fm (INCH/HR) = 0.30 AREA-AVERAGED Fp (INCH/HR) = 0.30
 AREA-AVERAGED Ap = 1.00 EFFECTIVE AREA (ACRES) = 3218.26

 FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<
 =====

MAINLINE Tc (MIN.) = 55.09
 * 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.371

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	2.40	0.30	1.000	65
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	1.70	0.30	1.000	65
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	1.50	0.30	1.000	65
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.30	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.90	0.30	1.000	66
NATURAL FAIR COVER					
"GRASS"	B	0.60	0.30	1.000	69

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 8.40 SUBAREA RUNOFF (CFS) = 8.10
EFFECTIVE AREA (ACRES) = 3226.66 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 3234.8 PEAK FLOW RATE (CFS) = 3168.88
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 55.09
* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.371

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.30	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.10	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.10	0.30	1.000	65

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 0.50 SUBAREA RUNOFF (CFS) = 0.48
EFFECTIVE AREA (ACRES) = 3227.16 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 3235.2 PEAK FLOW RATE (CFS) = 3168.88
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 55.09
* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.371

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					

"WOODLAND, GRASS"	B	0.80	0.30	1.000	65
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.70	0.30	1.000	65
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.20	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.20	0.30	1.000	65
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.10	0.30	1.000	66

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 2.00 SUBAREA RUNOFF (CFS) = 1.93
EFFECTIVE AREA (ACRES) = 3229.16 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 3237.2 PEAK FLOW RATE (CFS) = 3168.88
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 11927.50 TO NODE 11928.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 384.00 DOWNSTREAM (FEET) = 359.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 647.19 CHANNEL SLOPE = 0.0386
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT (FEET) = 8.55
* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.363

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	78.01	0.30	0.984	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.984
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 3206.39
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 13.86
AVERAGE FLOW DEPTH (FEET) = 8.54 TRAVEL TIME (MIN.) = 0.78
Tc (MIN.) = 55.87
SUBAREA AREA (ACRES) = 78.01 SUBAREA RUNOFF (CFS) = 75.01
EFFECTIVE AREA (ACRES) = 3307.17 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 3315.3 PEAK FLOW RATE (CFS) = 3168.88
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 8.50

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 8.50 FLOW VELOCITY (FEET/SEC.) = 13.82
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11928.00 = 29360.61 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap (DECIMAL)	Ae (ACRES)	HEADWATER NODE
1	2987.26	27.82	2.003	0.30 (0.30)	1.00	1928.7	40130.00
2	3028.60	29.63	1.920	0.30 (0.30)	1.00	2045.8	40100.00
3	3168.88	55.87	1.363	0.30 (0.30)	1.00	3307.2	11900.00

4 3162.81 56.31 1.359 0.30(0.30) 1.00 3315.3 11910.00
NEW PEAK FLOW DATA ARE:
PEAK FLOW RATE(CFS) = 3168.88 Tc(MIN.) = 55.87
AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 1.00 EFFECTIVE AREA(ACRES) = 3307.17

FLOW PROCESS FROM NODE 11928.00 TO NODE 11928.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 55.87 **S19-38**

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.363

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL FAIR COVER "WOODLAND,GRASS"	B	1.10	0.30	1.000	65
--	---	------	------	-------	----

NATURAL FAIR COVER "OPEN BRUSH"	B	0.60	0.30	1.000	66
------------------------------------	---	------	------	-------	----

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 1.70 SUBAREA RUNOFF(CFS) = 1.63

EFFECTIVE AREA(ACRES) = 3308.87 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 3317.0 PEAK FLOW RATE(CFS) = 3169.66

FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 359.00 DOWNSTREAM(FEET) = 341.63

CHANNEL LENGTH THRU SUBAREA(FEET) = 1322.66 CHANNEL SLOPE = 0.0131

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 10.84 **S19-29**

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.340

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

USER-DEFINED	-	8.18	0.30	0.890	-
--------------	---	------	------	-------	---

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.890

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3173.61

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.24

AVERAGE FLOW DEPTH(FEET) = 10.84 TRAVEL TIME(MIN.) = 2.38

Tc(MIN.) = 58.25

SUBAREA AREA(ACRES) = 8.18 SUBAREA RUNOFF(CFS) = 7.90

EFFECTIVE AREA(ACRES) = 3317.05 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 3325.1 PEAK FLOW RATE(CFS) = 3169.66

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 10.84

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 10.84 FLOW VELOCITY(FEET/SEC.) = 9.23
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11929.00 = 30683.27 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2987.26	30.24	1.897	0.30(0.30)	1.00	1938.6	40130.00
2	3028.60	32.04	1.851	0.30(0.30)	1.00	2055.7	40100.00
3	3169.66	58.25	1.340	0.30(0.30)	1.00	3317.1	11900.00
4	3164.43	58.70	1.336	0.30(0.30)	1.00	3325.1	11910.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 3169.66 Tc(MIN.) = 58.25

AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 1.00 EFFECTIVE AREA(ACRES) = 3317.05

FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 58.25 **S19-39**

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.340

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL FAIR COVER "OPEN BRUSH"	B	1.90	0.30	1.000	66
------------------------------------	---	------	------	-------	----

NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.60	0.30	1.000	65
--	---	------	------	-------	----

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 2.50 SUBAREA RUNOFF(CFS) = 2.34

EFFECTIVE AREA(ACRES) = 3319.55 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 3327.6 PEAK FLOW RATE(CFS) = 3169.66

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 3 <<<<<

FLOW PROCESS FROM NODE 11841.00 TO NODE 12527.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: S18X00.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22054.84	36.58	0.30(0.30)	1.00	7926.9	11831.00
2	22725.41	39.13	0.30(0.30)	1.00	8505.3	11801.00
3	25134.97	47.53	0.30(0.30)	1.00	10691.9	11500.00
4	25502.09	49.16	0.30(0.30)	1.00	11329.9	11530.00
5	26360.19	53.71	0.30(0.30)	1.00	13011.5	11701.00

6	26779.09	55.76	0.30	(0.30)	1.00	13818.6	11000.00
7	29291.04	65.53	0.30	(0.30)	1.00	18866.7	11330.00
8	30114.29	72.03	0.30	(0.30)	1.00	22317.4	11130.00
9	29645.18	80.38	0.30	(0.30)	1.00	25368.4	11620.00
10	29500.26	82.66	0.30	(0.30)	1.00	26144.7	11600.00
11	29052.00	88.60	0.30	(0.30)	1.00	27897.1	11111.00
12	28910.69	90.07	0.30	(0.30)	1.00	28280.6	11101.00
13	28571.47	94.86	0.30	(0.30)	1.00	29290.8	10710.00
14	28361.22	96.69	0.30	(0.30)	1.00	29594.6	10410.00
15	27934.24	101.05	0.30	(0.30)	1.00	30249.2	10700.00
16	27383.49	107.91	0.30	(0.30)	1.00	31215.0	10400.00
17	27137.20	109.87	0.30	(0.30)	1.00	31440.4	10200.00
18	26251.80	115.74	0.30	(0.30)	1.00	32001.9	10300.00
19	25289.37	121.31	0.30	(0.30)	1.00	32223.4	10210.00
20	23048.07	146.70	0.30	(0.30)	1.00	32916.6	10100.00

TOTAL AREA (ACRES) = 32916.6

FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: S25X00.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:

S25

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	7548.90	65.18	0.30 (0.30)	0.99	6431.3	12500.00
2	8477.91	78.32	0.30 (0.30)	0.99	8413.1	12300.00
3	8593.88	79.61	0.30 (0.30)	0.98	8691.0	12330.00
4	8774.49	82.20	0.30 (0.30)	0.98	9202.6	12410.00
5	9008.69	86.22	0.30 (0.29)	0.98	9924.8	12400.00
6	9221.87	90.84	0.30 (0.29)	0.98	10622.1	12211.00
7	9347.17	94.81	0.30 (0.29)	0.98	11209.1	12201.00
8	9384.46	98.70	0.30 (0.29)	0.98	11677.0	12111.00
9	9366.85	101.16	0.30 (0.29)	0.98	11977.9	12231.00
10	9319.62	103.97	0.30 (0.29)	0.98	12282.5	12101.10
11	9299.62	104.81	0.30 (0.29)	0.98	12363.8	12261.00
12	8916.90	115.67	0.30 (0.29)	0.98	13112.3	12010.00
13	8576.29	123.92	0.30 (0.29)	0.98	13237.1	12000.00

TOTAL AREA (ACRES) = 13237.1

FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	7548.90	65.18	0.30 (0.30)	0.99	6431.3	12500.00
2	8477.91	78.32	0.30 (0.30)	0.99	8413.1	12300.00
3	8593.88	79.61	0.30 (0.30)	0.98	8691.0	12330.00
4	8774.49	82.20	0.30 (0.30)	0.98	9202.6	12410.00
5	9008.69	86.22	0.30 (0.29)	0.98	9924.8	12400.00
6	9221.87	90.84	0.30 (0.29)	0.98	10622.1	12211.00
7	9347.17	94.81	0.30 (0.29)	0.98	11209.1	12201.00
8	9384.46	98.70	0.30 (0.29)	0.98	11677.0	12111.00

9	9366.85	101.16	0.30	(0.29)	0.98	11977.9	12231.00
10	9319.62	103.97	0.30	(0.29)	0.98	12282.5	12101.10
11	9299.62	104.81	0.30	(0.29)	0.98	12363.8	12261.00
12	8916.90	115.67	0.30	(0.29)	0.98	13112.3	12010.00
13	8576.29	123.92	0.30	(0.29)	0.98	13237.1	12000.00

TOTAL AREA (ACRES) = 13237.1

FLOW PROCESS FROM NODE 11841.00 TO NODE 12527.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	7548.90	65.18	1.288	0.30 (0.30)	0.99	6431.3	12500.00
2	8477.91	78.32	1.200	0.30 (0.30)	0.99	8413.1	12300.00
3	8593.88	79.61	1.192	0.30 (0.30)	0.98	8691.0	12330.00
4	8774.49	82.20	1.174	0.30 (0.30)	0.98	9202.6	12410.00
5	9008.69	86.22	1.147	0.30 (0.29)	0.98	9924.8	12400.00
6	9221.87	90.84	1.118	0.30 (0.29)	0.98	10622.1	12211.00
7	9347.17	94.81	1.100	0.30 (0.29)	0.98	11209.1	12201.00
8	9384.46	98.70	1.083	0.30 (0.29)	0.98	11677.0	12111.00
9	9366.85	101.16	1.072	0.30 (0.29)	0.98	11977.9	12231.00
10	9319.62	103.97	1.059	0.30 (0.29)	0.98	12282.5	12101.10
11	9299.62	104.81	1.055	0.30 (0.29)	0.98	12363.8	12261.00
12	8916.90	115.67	1.006	0.30 (0.29)	0.98	13112.3	12010.00
13	8576.29	123.92	0.977	0.30 (0.29)	0.98	13237.1	12000.00

LONGEST FLOWPATH FROM NODE 12000.00 TO NODE 12527.00 = 77156.98 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22054.84	36.58	1.735	0.30 (0.30)	1.00	7926.9	11831.00
2	22725.41	39.13	1.669	0.30 (0.30)	1.00	8505.3	11801.00
3	25134.97	47.53	1.477	0.30 (0.30)	1.00	10691.9	11500.00
4	25502.09	49.16	1.440	0.30 (0.30)	1.00	11329.9	11530.00
5	26360.19	53.71	1.385	0.30 (0.30)	1.00	13011.5	11701.00
6	26779.09	55.76	1.365	0.30 (0.30)	1.00	13818.6	11000.00
7	29291.04	65.53	1.286	0.30 (0.30)	1.00	18866.7	11330.00
8	30114.29	72.03	1.242	0.30 (0.30)	1.00	22317.4	11130.00
9	29645.18	80.38	1.186	0.30 (0.30)	1.00	25368.4	11620.00
10	29500.26	82.66	1.171	0.30 (0.30)	1.00	26144.7	11600.00
11	29052.00	88.60	1.131	0.30 (0.30)	1.00	27897.1	11111.00
12	28910.69	90.07	1.122	0.30 (0.30)	1.00	28280.6	11101.00
13	28571.47	94.86	1.100	0.30 (0.30)	1.00	29290.8	10710.00
14	28361.22	96.69	1.092	0.30 (0.30)	1.00	29594.6	10410.00
15	27934.24	101.05	1.072	0.30 (0.30)	1.00	30249.2	10700.00
16	27383.49	107.91	1.041	0.30 (0.30)	1.00	31215.0	10400.00
17	27137.20	109.87	1.033	0.30 (0.30)	1.00	31440.4	10200.00
18	26251.80	115.74	1.006	0.30 (0.30)	1.00	32001.9	10300.00
19	25289.37	121.31	0.984	0.30 (0.30)	1.00	32223.4	10210.00
20	23048.07	146.70	0.917	0.30 (0.30)	1.00	32916.6	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12527.00 = 97868.13 FEET.

** PEAK FLOW RATE TABLE **

STREAM	Q	Tc	Intensity	Fp (Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	---------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	28196.41	36.58	1.735	0.30 (0.30)	0.99	11536.0 11831.00
2	28997.24	39.13	1.669	0.30 (0.30)	0.99	12366.4 11801.00
3	31685.73	47.53	1.477	0.30 (0.30)	0.99	15382.2 11500.00
4	32066.13	49.16	1.440	0.30 (0.30)	0.99	16181.3 11530.00
5	33185.00	53.71	1.385	0.30 (0.30)	0.99	18311.7 11701.00
6	33733.33	55.76	1.365	0.30 (0.30)	0.99	19320.5 11000.00
7	36747.98	65.18	1.288	0.30 (0.30)	0.99	25113.1 12500.00
8	36865.25	65.53	1.286	0.30 (0.30)	0.99	25351.9 11330.00
9	38148.02	72.03	1.242	0.30 (0.30)	0.99	29783.0 11130.00
10	38239.23	78.32	1.200	0.30 (0.30)	0.99	33026.2 12300.00
11	38282.50	79.61	1.192	0.30 (0.30)	0.99	33776.9 12330.00
12	38292.96	80.38	1.186	0.30 (0.30)	0.99	34212.1 11620.00
13	38303.77	82.20	1.174	0.30 (0.30)	0.99	35191.7 12410.00
14	38301.27	82.66	1.171	0.30 (0.30)	0.99	35429.0 11600.00
15	38240.18	86.22	1.147	0.30 (0.30)	0.99	37120.1 12400.00
16	38170.52	88.60	1.131	0.30 (0.30)	0.99	38181.1 11111.00
17	38097.30	90.07	1.122	0.30 (0.30)	0.99	38787.4 11101.00
18	38078.45	90.84	1.118	0.30 (0.30)	0.99	39063.9 12211.00
19	37922.34	94.81	1.100	0.30 (0.30)	0.99	40488.9 12201.00
20	37919.14	94.86	1.100	0.30 (0.30)	0.99	40506.2 10710.00
21	37726.41	96.69	1.092	0.30 (0.30)	0.99	41029.8 10410.00
22	37548.75	98.70	1.083	0.30 (0.30)	0.99	41573.6 12111.00
23	37301.90	101.05	1.072	0.30 (0.30)	0.99	42213.4 10700.00
24	37292.05	101.16	1.072	0.30 (0.30)	0.99	42243.0 12231.00
25	37019.30	103.97	1.059	0.30 (0.30)	0.99	42943.0 12101.10
26	36931.54	104.81	1.055	0.30 (0.30)	0.99	43143.1 12261.00
27	36574.05	107.91	1.041	0.30 (0.30)	0.99	43792.1 10400.00
28	36258.75	109.87	1.033	0.30 (0.30)	0.99	44152.4 10200.00
29	35179.73	115.67	1.006	0.30 (0.30)	0.99	45107.2 12010.00
30	35165.68	115.74	1.006	0.30 (0.30)	0.99	45115.3 10300.00
31	33973.56	121.31	0.984	0.30 (0.30)	0.99	45420.9 10210.00
32	33634.95	123.92	0.977	0.30 (0.30)	0.99	45531.8 12000.00
33	30871.16	146.70	0.917	0.30 (0.30)	0.99	46153.7 10100.00
TOTAL AREA (ACRES) =		46153.7				

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 38303.77 Tc(MIN.) = 82.200
EFFECTIVE AREA(ACRES) = 35191.74 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 46153.7
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12527.00 = 97868.13 FEET.

FLOW PROCESS FROM NODE 12527.00 TO NODE 11929.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 347.47 DOWNSTREAM(FEET) = 341.63
CHANNEL LENGTH THRU SUBAREA(FEET) = 532.38 CHANNEL SLOPE = 0.0110
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 9.79
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.170

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

19-29.5

USER-DEFINED - 14.37 0.30 0.987 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.987
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 38309.42
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 15.73
AVERAGE FLOW DEPTH(FEET) = 9.79 TRAVEL TIME(MIN.) = 0.56
Tc(MIN.) = 82.76
SUBAREA AREA(ACRES) = 14.37 SUBAREA RUNOFF(CFS) = 11.31
EFFECTIVE AREA(ACRES) = 35206.11 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 46168.0 PEAK FLOW RATE(CFS) = 38303.77
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 9.79

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 9.79 FLOW VELOCITY(FEET/SEC.) = 15.72
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28196.41	37.20	1.719	0.30 (0.30)	0.99	11550.4	11831.00
2	28997.24	39.75	1.653	0.30 (0.30)	0.99	12380.8	11801.00
3	31685.73	48.13	1.463	0.30 (0.30)	0.99	15396.6	11500.00
4	32066.13	49.76	1.426	0.30 (0.30)	0.99	16195.7	11530.00
5	33185.00	54.30	1.379	0.30 (0.30)	0.99	18326.0	11701.00
6	33733.33	56.35	1.359	0.30 (0.30)	0.99	19334.9	11000.00
7	36747.98	65.75	1.284	0.30 (0.30)	0.99	25127.5	12500.00
8	36865.25	66.10	1.282	0.30 (0.30)	0.99	25366.3	11330.00
9	38148.02	72.60	1.239	0.30 (0.30)	0.99	29797.3	11130.00
10	38239.23	78.88	1.197	0.30 (0.30)	0.99	33040.6	12300.00
11	38282.50	80.17	1.188	0.30 (0.30)	0.99	33791.3	12330.00
12	38292.96	80.95	1.183	0.30 (0.30)	0.99	34226.1	11620.00
13	38303.77	82.76	1.170	0.30 (0.30)	0.99	35206.1	12410.00
14	38301.27	83.22	1.167	0.30 (0.30)	0.99	35443.4	11600.00
15	38240.18	86.78	1.144	0.30 (0.30)	0.99	37134.5	12400.00
16	38170.52	89.16	1.128	0.30 (0.30)	0.99	38195.5	11111.00
17	38097.30	90.64	1.119	0.30 (0.30)	0.99	38801.7	11101.00
18	38078.45	91.40	1.116	0.30 (0.30)	0.99	39078.2	12211.00
19	37922.34	95.38	1.098	0.30 (0.30)	0.99	40503.2	12201.00
20	37919.14	95.43	1.098	0.30 (0.30)	0.99	40520.6	10710.00
21	37726.41	97.26	1.089	0.30 (0.30)	0.99	41044.2	10410.00
22	37548.75	99.27	1.080	0.30 (0.30)	0.99	41587.9	12111.00
23	37301.90	101.62	1.070	0.30 (0.30)	0.99	42227.7	10700.00
24	37292.05	101.73	1.069	0.30 (0.30)	0.99	42257.4	12231.00
25	37019.30	104.54	1.057	0.30 (0.30)	0.99	42957.4	12101.10
26	36931.54	105.38	1.053	0.30 (0.30)	0.99	43157.5	12261.00
27	36574.05	108.48	1.039	0.30 (0.30)	0.99	43806.5	10400.00
28	36258.75	110.44	1.030	0.30 (0.30)	0.99	44166.8	10200.00
29	35179.73	116.25	1.004	0.30 (0.30)	0.99	45121.6	12010.00
30	35165.68	116.32	1.004	0.30 (0.30)	0.99	45129.7	10300.00
31	33973.56	121.90	0.982	0.30 (0.30)	0.99	45435.3	10210.00
32	33634.95	124.51	0.975	0.30 (0.30)	0.99	45546.2	12000.00
33	30871.16	147.31	0.915	0.30 (0.30)	0.99	46168.0	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 38303.77 Tc(MIN.) = 82.76

AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 35206.11

FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28196.41	37.20	1.719	0.30(0.30)	0.99	11550.4	11831.00
2	28997.24	39.75	1.653	0.30(0.30)	0.99	12380.8	11801.00
3	31685.73	48.13	1.463	0.30(0.30)	0.99	15396.6	11500.00
4	32066.13	49.76	1.426	0.30(0.30)	0.99	16195.7	11530.00
5	33185.00	54.30	1.379	0.30(0.30)	0.99	18326.0	11701.00
6	33733.33	56.35	1.359	0.30(0.30)	0.99	19334.9	11000.00
7	36747.98	65.75	1.284	0.30(0.30)	0.99	25127.5	12500.00
8	36865.25	66.10	1.282	0.30(0.30)	0.99	25366.3	11330.00
9	38148.02	72.60	1.239	0.30(0.30)	0.99	29797.3	11130.00
10	38239.23	78.88	1.197	0.30(0.30)	0.99	33040.6	12300.00
11	38282.50	80.17	1.188	0.30(0.30)	0.99	33791.3	12330.00
12	38292.96	80.95	1.183	0.30(0.30)	0.99	34226.5	11620.00
13	38303.77	82.76	1.170	0.30(0.30)	0.99	35206.1	12410.00
14	38301.27	83.22	1.167	0.30(0.30)	0.99	35443.4	11600.00
15	38240.18	86.78	1.144	0.30(0.30)	0.99	37134.5	12400.00
16	38170.52	89.16	1.128	0.30(0.30)	0.99	38195.5	11111.00
17	38097.30	90.64	1.119	0.30(0.30)	0.99	38801.7	11101.00
18	38078.45	91.40	1.116	0.30(0.30)	0.99	39078.2	12211.00
19	37922.34	95.38	1.098	0.30(0.30)	0.99	40503.2	12201.00
20	37919.14	95.43	1.098	0.30(0.30)	0.99	40520.6	10710.00
21	37726.41	97.26	1.089	0.30(0.30)	0.99	41044.2	10410.00
22	37548.75	99.27	1.080	0.30(0.30)	0.99	41587.9	12111.00
23	37301.90	101.62	1.070	0.30(0.30)	0.99	42227.7	10700.00
24	37292.05	101.73	1.069	0.30(0.30)	0.99	42257.4	12231.00
25	37019.30	104.54	1.057	0.30(0.30)	0.99	42957.4	12101.10
26	36931.54	105.38	1.053	0.30(0.30)	0.99	43157.5	12261.00
27	36574.05	108.48	1.039	0.30(0.30)	0.99	43806.5	10400.00
28	36258.75	110.44	1.030	0.30(0.30)	0.99	44166.8	10200.00
29	35179.73	116.25	1.004	0.30(0.30)	0.99	45121.6	12010.00
30	35165.68	116.32	1.004	0.30(0.30)	0.99	45129.7	10300.00
31	33973.56	121.90	0.982	0.30(0.30)	0.99	45435.3	10210.00
32	33634.95	124.51	0.975	0.30(0.30)	0.99	45546.2	12000.00
33	30871.16	147.31	0.915	0.30(0.30)	0.99	46168.0	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2987.26	30.24	1.897	0.30(0.30)	1.00	1941.1	40130.00
2	3028.60	32.04	1.851	0.30(0.30)	1.00	2058.2	40100.00
3	3169.66	58.25	1.340	0.30(0.30)	1.00	3319.6	11900.00
4	3164.43	58.70	1.336	0.30(0.30)	1.00	3327.6	11910.00

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11929.00 = 30683.27 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
---------------	---	----	-----------	--------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	28781.04	30.24	1.897	0.30(0.30)	0.99	11329.6 40130.00
2	29570.59	32.04	1.851	0.30(0.30)	0.99	12005.8 40100.00
3	31252.79	37.20	1.719	0.30(0.30)	0.99	13857.0 11831.00
4	32067.32	39.75	1.653	0.30(0.30)	0.99	14809.9 11801.00
5	34800.94	48.13	1.463	0.30(0.30)	0.99	18229.2 11500.00
6	35190.11	49.76	1.426	0.30(0.30)	0.99	19106.7 11530.00
7	36333.41	54.30	1.379	0.30(0.30)	0.99	21455.5 11701.00
8	36892.72	56.35	1.359	0.30(0.30)	0.99	22562.6 11000.00
9	37514.99	58.25	1.340	0.30(0.30)	0.99	23830.4 11900.00
10	37652.28	58.70	1.336	0.30(0.30)	0.99	24112.3 11910.00
11	39755.94	65.75	1.284	0.30(0.30)	0.99	28455.1 12500.00
12	39865.90	66.10	1.282	0.30(0.30)	0.99	28694.0 11330.00
13	41015.88	72.60	1.239	0.30(0.30)	0.99	33125.0 11130.00
14	40978.60	78.88	1.197	0.30(0.30)	0.99	36368.2 12300.00
15	40995.41	80.17	1.188	0.30(0.30)	0.99	37118.9 12330.00
16	40990.07	80.95	1.183	0.30(0.30)	0.99	37554.1 11620.00
17	40963.71	82.76	1.170	0.30(0.30)	0.99	38533.8 12410.00
18	40951.90	83.22	1.167	0.30(0.30)	0.99	38771.0 11600.00
19	40817.93	86.78	1.144	0.30(0.30)	0.99	40462.1 12400.00
20	40699.58	89.16	1.128	0.30(0.30)	0.99	41523.1 11111.00
21	40600.48	90.64	1.119	0.30(0.30)	0.99	42129.4 11101.00
22	40571.13	91.40	1.116	0.30(0.30)	0.99	42405.9 12211.00
23	40360.44	95.38	1.098	0.30(0.30)	0.99	43830.9 12201.00
24	40356.51	95.43	1.098	0.30(0.30)	0.99	43848.2 10710.00
25	40138.69	97.26	1.089	0.30(0.30)	0.99	44371.8 10410.00
26	39933.41	99.27	1.080	0.30(0.30)	0.99	44915.6 12111.00
27	39654.30	101.62	1.070	0.30(0.30)	0.99	45555.4 10700.00
28	39642.91	101.73	1.069	0.30(0.30)	0.99	45585.0 12231.00
29	39331.55	104.54	1.057	0.30(0.30)	0.99	46285.0 12101.10
30	39232.20	105.38	1.053	0.30(0.30)	0.99	46485.2 12261.00
31	38832.19	108.48	1.039	0.30(0.30)	0.99	47134.1 10400.00
32	38489.96	110.44	1.030	0.30(0.30)	0.99	47494.5 10200.00
33	37331.12	116.25	1.004	0.30(0.30)	0.99	48449.2 12010.00
34	37316.06	116.32	1.004	0.30(0.30)	0.99	48457.4 10300.00
35	36058.22	121.90	0.982	0.30(0.30)	0.99	48763.0 10210.00
36	35698.59	124.51	0.975	0.30(0.30)	0.99	48873.8 12000.00
37	32751.58	147.31	0.915	0.30(0.30)	0.99	49495.7 10100.00

TOTAL AREA(ACRES) = 49495.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 41015.88 Tc(MIN.) = 72.598
 EFFECTIVE AREA(ACRES) = 33124.96 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 49495.7
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 49495.7 TC(MIN.) = 72.60
 EFFECTIVE AREA(ACRES) = 33124.96 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.994
 PEAK FLOW RATE(CFS) = 41015.88

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
1	28781.04	30.24	1.897	0.30(0.30)	0.99	11329.6	40130.00
2	29570.59	32.04	1.851	0.30(0.30)	0.99	12005.8	40100.00

3	31252.79	37.20	1.719	0.30	(0.30)	0.99	13857.0	11831.00
4	32067.32	39.75	1.653	0.30	(0.30)	0.99	14809.9	11801.00
5	34800.94	48.13	1.463	0.30	(0.30)	0.99	18229.2	11500.00
6	35190.11	49.76	1.426	0.30	(0.30)	0.99	19106.7	11530.00
7	36333.41	54.30	1.379	0.30	(0.30)	0.99	21455.5	11701.00
8	36892.72	56.35	1.359	0.30	(0.30)	0.99	22562.6	11000.00
9	37514.99	58.25	1.340	0.30	(0.30)	0.99	23830.4	11900.00
10	37652.28	58.70	1.336	0.30	(0.30)	0.99	24112.3	11910.00
11	39755.94	65.75	1.284	0.30	(0.30)	0.99	28455.1	12500.00
12	39865.90	66.10	1.282	0.30	(0.30)	0.99	28694.0	11330.00
13	41015.88	72.60	1.239	0.30	(0.30)	0.99	33125.0	11130.00
14	40978.60	78.88	1.197	0.30	(0.30)	0.99	36368.2	12300.00
15	40995.41	80.17	1.188	0.30	(0.30)	0.99	37118.9	12330.00
16	40990.07	80.95	1.183	0.30	(0.30)	0.99	37554.1	11620.00
17	40963.71	82.76	1.170	0.30	(0.30)	0.99	38533.8	12410.00
18	40951.90	83.22	1.167	0.30	(0.30)	0.99	38771.0	11600.00
19	40817.93	86.78	1.144	0.30	(0.30)	0.99	40462.1	12400.00
20	40699.58	89.16	1.128	0.30	(0.30)	0.99	41523.1	11111.00
21	40600.48	90.64	1.119	0.30	(0.30)	0.99	42129.4	11101.00
22	40571.13	91.40	1.116	0.30	(0.30)	0.99	42405.9	12211.00
23	40360.44	95.38	1.098	0.30	(0.30)	0.99	43830.9	12201.00
24	40356.51	95.43	1.098	0.30	(0.30)	0.99	43848.2	10710.00
25	40138.69	97.26	1.089	0.30	(0.30)	0.99	44371.8	10410.00
26	39933.41	99.27	1.080	0.30	(0.30)	0.99	44915.6	12111.00
27	39654.30	101.62	1.070	0.30	(0.30)	0.99	45555.4	10700.00
28	39642.91	101.73	1.069	0.30	(0.30)	0.99	45585.0	12231.00
29	39331.55	104.54	1.057	0.30	(0.30)	0.99	46285.0	12101.10
30	39232.20	105.38	1.053	0.30	(0.30)	0.99	46485.2	12261.00
31	38832.19	108.48	1.039	0.30	(0.30)	0.99	47134.1	10400.00
32	38489.96	110.44	1.030	0.30	(0.30)	0.99	47494.5	10200.00
33	37331.12	116.25	1.004	0.30	(0.30)	0.99	48449.2	12010.00
34	37316.06	116.32	1.004	0.30	(0.30)	0.99	48457.4	10300.00
35	36058.22	121.90	0.982	0.30	(0.30)	0.99	48763.0	10210.00
36	35698.59	124.51	0.975	0.30	(0.30)	0.99	48873.8	12000.00
37	32751.58	147.31	0.915	0.30	(0.30)	0.99	49495.7	10100.00

=====
 END OF RATIONAL METHOD ANALYSIS
 =====

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 126 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 100-YR EV FEB 2023 ROKAMOTO *

FILE NAME: RU00EV26.DAT
TIME/DATE OF STUDY: 14:17 02/07/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 100.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 6.101
- 2) 10.00; 3.900
- 3) 15.00; 3.005
- 4) 20.00; 2.465
- 5) 25.00; 2.128
- 6) 30.00; 1.900
- 7) 40.00; 1.644
- 8) 50.00; 1.419
- 9) 60.00; 1.320
- 10) 90.00; 1.119
- 11) 120.00; 0.983
- 12) 180.00; 0.826
- 13) 360.00; 0.617
- 14) 1200.00; 0.271

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES WIDTH (FT)	LIKE HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<<

PEAK FLOWRATE TABLE FILE NAME: RU00EV19.DNA

S19

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	29570.59	32.04	0.30 (0.30)	0.99	12005.8	40100.00
2	31252.79	37.20	0.30 (0.30)	0.99	13857.0	11831.00
3	32067.32	39.75	0.30 (0.30)	0.99	14809.9	11801.00
4	35190.11	49.76	0.30 (0.30)	0.99	19106.7	11530.00
5	37652.28	58.70	0.30 (0.30)	0.99	24112.3	11910.00
6	39865.90	66.10	0.30 (0.30)	0.99	28694.0	11330.00
7	41015.88	72.60	0.30 (0.30)	0.99	33125.0	11130.00
8	40995.41	80.17	0.30 (0.30)	0.99	37118.9	12330.00
9	40963.71	82.76	0.30 (0.30)	0.99	38533.8	12410.00
10	40817.93	86.78	0.30 (0.30)	0.99	40462.1	12400.00
11	40699.58	89.16	0.30 (0.30)	0.99	41523.1	11111.00
12	40360.44	95.38	0.30 (0.30)	0.99	43830.9	12201.00
13	39933.41	99.27	0.30 (0.30)	0.99	44915.6	12111.00
14	39654.30	101.62	0.30 (0.30)	0.99	45555.4	10700.00
15	39331.55	104.54	0.30 (0.30)	0.99	46285.0	12101.10
16	38832.19	108.48	0.30 (0.30)	0.99	47134.1	10400.00
17	37331.12	116.25	0.30 (0.30)	0.99	48449.2	12010.00
18	36058.22	121.90	0.30 (0.30)	0.99	48763.0	10210.00
19	35698.59	124.51	0.30 (0.30)	0.99	48873.8	12000.00
20	32751.58	147.31	0.30 (0.30)	0.99	49495.7	10100.00
TOTAL AREA (ACRES) =						49495.7

FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	29570.59	32.04	0.30 (0.30)	0.99	12005.8	40100.00
2	31252.79	37.20	0.30 (0.30)	0.99	13857.0	11831.00
3	32067.32	39.75	0.30 (0.30)	0.99	14809.9	11801.00
4	35190.11	49.76	0.30 (0.30)	0.99	19106.7	11530.00
5	37652.28	58.70	0.30 (0.30)	0.99	24112.3	11910.00
6	39865.90	66.10	0.30 (0.30)	0.99	28694.0	11330.00
7	41015.88	72.60	0.30 (0.30)	0.99	33125.0	11130.00
8	40995.41	80.17	0.30 (0.30)	0.99	37118.9	12330.00
9	40963.71	82.76	0.30 (0.30)	0.99	38533.8	12410.00
10	40817.93	86.78	0.30 (0.30)	0.99	40462.1	12400.00
11	40699.58	89.16	0.30 (0.30)	0.99	41523.1	11111.00
12	40360.44	95.38	0.30 (0.30)	0.99	43830.9	12201.00
13	39933.41	99.27	0.30 (0.30)	0.99	44915.6	12111.00

14	39654.30	101.62	0.30	(0.30)	0.99	45555.4	10700.00
15	39331.55	104.54	0.30	(0.30)	0.99	46285.0	12101.10
16	38832.19	108.48	0.30	(0.30)	0.99	47134.1	10400.00
17	37331.12	116.25	0.30	(0.30)	0.99	48449.2	12010.00
18	36058.22	121.90	0.30	(0.30)	0.99	48763.0	10210.00
19	35698.59	124.51	0.30	(0.30)	0.99	48873.8	12000.00
20	32751.58	147.31	0.30	(0.30)	0.99	49495.7	10100.00

TOTAL AREA (ACRES) = 49495.7

FLOW PROCESS FROM NODE 11929.00 TO NODE 12601.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 341.63 DOWNSTREAM (FEET) = 325.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 1467.93 CHANNEL SLOPE = 0.0113
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT (FEET) = 8.56

S26-3-1

* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.227

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.40	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.50	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	C	0.90	0.25	1.000	75
NATURAL FAIR COVER					
"GRASS"	B	0.50	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	C	11.50	0.25	1.000	77
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.30	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.26

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 41022.04

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 19.73

AVERAGE FLOW DEPTH (FEET) = 8.56 TRAVEL TIME (MIN.) = 1.24

Tc (MIN.) = 73.84

SUBAREA AREA (ACRES) = 14.10 SUBAREA RUNOFF (CFS) = 12.33

EFFECTIVE AREA (ACRES) = 33139.07 AREA-AVERAGED Fm (INCH/HR) = 0.30

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA (ACRES) = 49509.8 PEAK FLOW RATE (CFS) = 41015.88

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT (FEET) = 8.56

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 8.56 FLOW VELOCITY (FEET/SEC.) = 19.73

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 3000EVRL.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	117.77	16.39	0.30 (0.29)	0.98	51.1	600.00

TOTAL AREA (ACRES) = 51.1

FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	29570.59	33.42	1.812	0.30 (0.30)	0.99	12019.9	40100.00
2	31252.79	38.56	1.681	0.30 (0.30)	0.99	13871.1	11831.00
3	32067.32	41.09	1.619	0.30 (0.30)	0.99	14824.0	11801.00
4	35190.11	51.07	1.408	0.30 (0.30)	0.99	19120.8	11530.00
5	37652.28	59.97	1.320	0.30 (0.30)	0.99	24126.4	11910.00
6	39865.90	67.36	1.271	0.30 (0.30)	0.99	28708.1	11330.00
7	41015.88	73.84	1.227	0.30 (0.30)	0.99	33139.1	11130.00
8	40995.41	81.41	1.177	0.30 (0.30)	0.99	37133.0	12330.00
9	40963.71	84.01	1.159	0.30 (0.30)	0.99	38547.9	12410.00
10	40817.93	88.03	1.132	0.30 (0.30)	0.99	40476.2	12400.00
11	40699.58	90.41	1.117	0.30 (0.30)	0.99	41537.2	11111.00
12	40360.44	96.63	1.089	0.30 (0.30)	0.99	43845.0	12201.00
13	39933.41	100.52	1.071	0.30 (0.30)	0.99	44929.7	12111.00
14	39654.30	102.87	1.061	0.30 (0.30)	0.99	45569.5	10700.00
15	39331.55	105.80	1.047	0.30 (0.30)	0.99	46299.1	12101.10
16	38832.19	109.74	1.029	0.30 (0.30)	0.99	47148.2	10400.00
17	37331.12	117.53	0.994	0.30 (0.30)	0.99	48463.4	12010.00
18	36058.22	123.19	0.975	0.30 (0.30)	0.99	48777.1	10210.00
19	35698.59	125.81	0.968	0.30 (0.30)	0.99	48887.9	12000.00
20	32751.58	148.64	0.908	0.30 (0.30)	0.99	49509.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	117.77	16.39	2.855	0.30 (0.29)	0.98	51.1	600.00

LONGEST FLOWPATH FROM NODE 600.00 TO NODE 12601.00 = 4850.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24601.76	16.39	2.855	0.30 (0.30)	0.99	5946.4	600.00
2	29640.42	33.42	1.812	0.30 (0.30)	0.99	12071.0	40100.00
3	31316.57	38.56	1.681	0.30 (0.30)	0.99	13922.2	11831.00
4	32128.28	41.09	1.619	0.30 (0.30)	0.99	14875.1	11801.00
5	35241.36	51.07	1.408	0.30 (0.30)	0.99	19171.9	11530.00
6	37699.48	59.97	1.320	0.30 (0.30)	0.99	24177.5	11910.00
7	39910.82	67.36	1.271	0.30 (0.30)	0.99	28759.2	11330.00
8	41058.80	73.84	1.227	0.30 (0.30)	0.99	33190.2	11130.00
9	41036.00	81.41	1.177	0.30 (0.30)	0.99	37184.1	12330.00

10	41003.50	84.01	1.159	0.30	(0.30)	0.99	38599.0	12410.00
11	40856.48	88.03	1.132	0.30	(0.30)	0.99	40527.3	12400.00
12	40737.44	90.41	1.117	0.30	(0.30)	0.99	41588.3	11111.00
13	40397.00	96.63	1.089	0.30	(0.30)	0.99	43896.1	12201.00
14	39969.16	100.52	1.071	0.30	(0.30)	0.99	44980.8	12111.00
15	39689.56	102.87	1.061	0.30	(0.30)	0.99	45620.6	10700.00
16	39366.20	105.80	1.047	0.30	(0.30)	0.99	46350.2	12101.10
17	38866.02	109.74	1.029	0.30	(0.30)	0.99	47199.3	10400.00
18	37363.33	117.53	0.994	0.30	(0.30)	0.99	48514.5	12010.00
19	36089.53	123.19	0.975	0.30	(0.30)	0.99	48828.2	10210.00
20	35729.58	125.81	0.968	0.30	(0.30)	0.99	48939.0	12000.00
21	32779.82	148.64	0.908	0.30	(0.30)	0.99	49560.9	10100.00

TOTAL AREA (ACRES) = 49560.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 41058.80 Tc (MIN.) = 73.838
EFFECTIVE AREA (ACRES) = 33190.17 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 49560.9
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

FLOW PROCESS FROM NODE 12601.00 TO NODE 12603.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 325.00 DOWNSTREAM (FEET) = 310.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 1690.00 CHANNEL SLOPE = 0.0089
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 9.18
CHANNEL FLOW THRU SUBAREA (CFS) = 41058.80
FLOW VELOCITY (FEET/SEC.) = 18.18 FLOW DEPTH (FEET) = 9.18
TRAVEL TIME (MIN.) = 1.55 Tc (MIN.) = 75.39
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.45 FEET.

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 4E00EVRL.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	557.65	9.11	0.30 (0.16)	0.52	148.3	800.00
2	502.46	12.67	0.30 (0.17)	0.57	168.2	818.00
3	475.51	13.76	0.30 (0.17)	0.58	171.0	810.00

TOTAL AREA (ACRES) = 171.0

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24601.76	18.23	2.656	0.30 (0.30)	0.99	5946.4	600.00
2	29640.42	35.15	1.768	0.30 (0.30)	0.99	12071.0	40100.00
3	31316.57	40.25	1.638	0.30 (0.30)	0.99	13922.2	11831.00
4	32128.28	42.77	1.582	0.30 (0.30)	0.99	14875.1	11801.00
5	35241.36	52.70	1.392	0.30 (0.30)	0.99	19171.9	11530.00
6	37699.48	61.57	1.309	0.30 (0.30)	0.99	24177.5	11910.00
7	39910.82	68.92	1.260	0.30 (0.30)	0.99	28759.2	11330.00
8	41058.80	75.39	1.217	0.30 (0.30)	0.99	33190.2	11130.00
9	41036.00	82.96	1.166	0.30 (0.30)	0.99	37184.1	12330.00
10	41003.50	85.55	1.149	0.30 (0.30)	0.99	38599.0	12410.00
11	40856.48	89.58	1.122	0.30 (0.30)	0.99	40527.3	12400.00
12	40737.44	91.96	1.110	0.30 (0.30)	0.99	41588.3	11111.00
13	40397.00	98.18	1.082	0.30 (0.30)	0.99	43896.1	12201.00
14	39969.16	102.08	1.064	0.30 (0.30)	0.99	44980.8	12111.00
15	39689.56	104.44	1.054	0.30 (0.30)	0.99	45620.6	10700.00
16	39366.20	107.37	1.040	0.30 (0.30)	0.99	46350.2	12101.10
17	38866.02	111.32	1.022	0.30 (0.30)	0.99	47199.3	10400.00
18	37363.33	119.13	0.987	0.30 (0.30)	0.99	48514.5	12010.00
19	36089.53	124.81	0.970	0.30 (0.30)	0.99	48828.2	10210.00
20	35729.58	127.43	0.964	0.30 (0.30)	0.99	48939.0	12000.00
21	32779.82	150.31	0.904	0.30 (0.30)	0.99	49560.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.45 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	557.65	9.11	4.292	0.30 (0.16)	0.52	148.3	800.00
2	502.46	12.67	3.422	0.30 (0.17)	0.57	168.2	818.00
3	475.51	13.76	3.227	0.30 (0.17)	0.58	171.0	810.00

LONGEST FLOWPATH FROM NODE 810.00 TO NODE 12603.00 = 3814.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21378.32	9.11	4.292	0.30 (0.29)	0.97	3119.7	800.00
2	23152.96	12.67	3.422	0.30 (0.29)	0.98	4300.3	818.00
3	23539.06	13.76	3.227	0.30 (0.29)	0.98	4659.0	810.00
4	24988.33	18.23	2.656	0.30 (0.29)	0.98	6117.4	600.00
5	29888.71	35.15	1.768	0.30 (0.30)	0.99	12242.0	40100.00
6	31544.63	40.25	1.638	0.30 (0.30)	0.99	14093.2	11831.00
7	32347.51	42.77	1.582	0.30 (0.30)	0.99	15046.1	11801.00
8	35431.11	52.70	1.392	0.30 (0.30)	0.99	19342.9	11530.00
9	37876.33	61.57	1.309	0.30 (0.30)	0.99	24348.5	11910.00
10	40080.00	68.92	1.260	0.30 (0.30)	0.99	28930.2	11330.00
11	41221.23	75.39	1.217	0.30 (0.30)	0.99	33361.2	11130.00
12	41190.53	82.96	1.166	0.30 (0.30)	0.99	37355.1	12330.00
13	41155.32	85.55	1.149	0.30 (0.30)	0.99	38770.0	12410.00
14	41004.10	89.58	1.122	0.30 (0.30)	0.99	40698.3	12400.00
15	40883.23	91.96	1.110	0.30 (0.30)	0.99	41759.3	11111.00
16	40538.40	98.18	1.082	0.30 (0.30)	0.99	44067.1	12201.00

17	40107.81	102.08	1.064	0.30	(0.30)	0.99	45151.8	12111.00
18	39826.55	104.44	1.054	0.30	(0.30)	0.99	45791.6	10700.00
19	39501.12	107.37	1.040	0.30	(0.30)	0.99	46521.2	12101.10
20	38998.15	111.32	1.022	0.30	(0.30)	0.99	47370.3	10400.00
21	37489.94	119.13	0.987	0.30	(0.30)	0.99	48685.5	12010.00
22	36213.57	124.81	0.970	0.30	(0.30)	0.99	48999.2	10210.00
23	35852.55	127.43	0.964	0.30	(0.30)	0.99	49110.0	12000.00
24	32893.47	150.31	0.904	0.30	(0.30)	0.99	49731.9	10100.00

TOTAL AREA (ACRES) = 49731.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 41221.23 Tc (MIN.) = 75.387
EFFECTIVE AREA (ACRES) = 33361.17 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 49731.9
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.45 FEET.

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 75.39 **S26.3-2**

* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.217
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.20	0.30	1.000	65
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.30	0.30	1.000	66
PUBLIC PARK	B	1.30	0.30	0.850	56
COMMERCIAL	B	1.40	0.30	0.100	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	1.70	0.30	0.900	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	12.40	0.30	1.000	66

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.911
SUBAREA AREA (ACRES) = 18.30 SUBAREA RUNOFF (CFS) = 15.54
EFFECTIVE AREA (ACRES) = 33379.47 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 49750.2 PEAK FLOW RATE (CFS) = 41221.23
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 75.39 **S26.3-2**

* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.217
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	26.90	0.30	1.000	65

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 26.90 SUBAREA RUNOFF (CFS) = 22.20
EFFECTIVE AREA (ACRES) = 33406.37 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 49777.1 PEAK FLOW RATE (CFS) = 41221.23
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 75.39 **S26.3-3**

* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.217
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	0.50	0.30	1.000	63
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.40	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL, NARROWLEAF"	B	0.40	0.30	1.000	72
NATURAL FAIR COVER					
"GRASS"	B	0.60	0.30	1.000	69
PUBLIC PARK	B	0.70	0.30	0.850	56
NATURAL FAIR COVER					
"CHAPARRAL, NARROWLEAF"	B	0.70	0.30	1.000	72

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.968
SUBAREA AREA (ACRES) = 3.30 SUBAREA RUNOFF (CFS) = 2.75
EFFECTIVE AREA (ACRES) = 33409.67 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 49780.4 PEAK FLOW RATE (CFS) = 41221.23
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 75.39 **S26.3-3**

* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.217
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.00	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.20	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	1.70	0.30	0.900	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.90	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	2.10	0.30	0.900	56
NATURAL FAIR COVER					
"CHAPARRAL, NARROWLEAF"	B	2.90	0.30	1.000	72

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.965
 SUBAREA AREA(ACRES) = 10.80 SUBAREA RUNOFF(CFS) = 9.01
 EFFECTIVE AREA(ACRES) = 33420.47 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 49791.2 PEAK FLOW RATE(CFS) = 41221.23
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 75.39 **S26.3-3**

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.217

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL FAIR COVER "WOODLAND,GRASS"	B	5.60	0.30	1.000	65
--	---	------	------	-------	----

NATURAL FAIR COVER "WOODLAND,GRASS"	B	9.00	0.30	1.000	65
--	---	------	------	-------	----

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 14.60 SUBAREA RUNOFF(CFS) = 12.05
 EFFECTIVE AREA(ACRES) = 33435.07 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 49805.8 PEAK FLOW RATE(CFS) = 41221.23
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12603.00 TO NODE 12605.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 310.00 DOWNSTREAM(FEET) = 305.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 885.00 CHANNEL SLOPE = 0.0056

GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT(FEET) = 10.46

CHANNEL FLOW THRU SUBAREA(CFS) = 41221.23

FLOW VELOCITY(FEET/SEC.) = 15.63 FLOW DEPTH(FEET) = 10.46

TRAVEL TIME(MIN.) = 0.94 Tc(MIN.) = 76.33

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.00 = 102443.45 FEET.

 FLOW PROCESS FROM NODE 12605.00 TO NODE 12605.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 76.33 **S26.3-5**

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.211

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

AGRICULTURAL POOR COVER "ROW CROPS,STRAIGHT ROW"	B	0.50	0.30	1.000	81
---	---	------	------	-------	----

NATURAL FAIR COVER
 "WOODLAND,GRASS" B 0.70 0.30 1.000 65
 PUBLIC PARK B 1.30 0.30 0.850 56
 RESIDENTIAL
 ".4 DWELLING/ACRE" B 1.30 0.30 0.900 56
 AGRICULTURAL POOR COVER
 "ROW CROPS,STRAIGHT ROW" B 1.90 0.30 1.000 81
 PUBLIC PARK B 2.10 0.30 0.850 56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.918
 SUBAREA AREA(ACRES) = 7.80 SUBAREA RUNOFF(CFS) = 6.57
 EFFECTIVE AREA(ACRES) = 33442.87 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 49813.6 PEAK FLOW RATE(CFS) = 41221.23
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12605.00 TO NODE 12605.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 76.33 **S26.3-5**

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.211

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL FAIR COVER "OPEN BRUSH"	B	3.20	0.30	1.000	66
------------------------------------	---	------	------	-------	----

NATURAL FAIR COVER "WOODLAND,GRASS"	B	3.50	0.30	1.000	65
--	---	------	------	-------	----

PUBLIC PARK	B	6.10	0.30	0.850	56
-------------	---	------	------	-------	----

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.929
 SUBAREA AREA(ACRES) = 12.80 SUBAREA RUNOFF(CFS) = 10.74
 EFFECTIVE AREA(ACRES) = 33455.67 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 49826.4 PEAK FLOW RATE(CFS) = 41221.23
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12605.00 TO NODE 12606.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 305.00 DOWNSTREAM(FEET) = 286.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 2159.47 CHANNEL SLOPE = 0.0088

GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT(FEET) = 9.23

CHANNEL FLOW THRU SUBAREA(CFS) = 41221.23

FLOW VELOCITY(FEET/SEC.) = 18.15 FLOW DEPTH(FEET) = 9.23

TRAVEL TIME(MIN.) = 1.98 Tc(MIN.) = 78.31

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104602.91 FEET.

 FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 4F00EVRL.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1276.24	9.90	0.30 (0.24)	0.79	382.4	940.00
2	1276.37	10.13	0.30 (0.24)	0.79	389.7	930.00
3	1319.64	12.80	0.30 (0.25)	0.82	465.0	910.00
4	1294.78	16.16	0.30 (0.25)	0.85	548.0	920.00
5	1265.04	16.96	0.30 (0.25)	0.85	553.7	950.00
6	1224.20	17.72	0.30 (0.25)	0.85	553.8	900.00
TOTAL AREA (ACRES) =						553.8

F

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21378.32	12.75	3.407	0.30 (0.29)	0.97	3214.2	800.00
2	23152.96	16.21	2.874	0.30 (0.29)	0.98	4394.8	818.00
3	23539.06	17.28	2.758	0.30 (0.29)	0.98	4753.4	810.00
4	24988.33	21.69	2.351	0.30 (0.29)	0.98	6211.9	600.00
5	29888.71	38.40	1.685	0.30 (0.30)	0.99	12336.5	40100.00
6	31544.63	43.45	1.566	0.30 (0.30)	0.99	14187.7	11831.00
7	32347.51	45.94	1.510	0.30 (0.30)	0.99	15140.6	11801.00
8	35431.11	55.77	1.362	0.30 (0.30)	0.99	19437.4	11530.00
9	37876.33	64.58	1.289	0.30 (0.30)	0.99	24443.0	11910.00
10	40080.00	71.87	1.240	0.30 (0.30)	0.99	29024.7	11330.00
11	41221.23	78.31	1.197	0.30 (0.30)	0.99	33455.7	11130.00
12	41190.53	85.89	1.147	0.30 (0.30)	0.99	37449.6	12330.00
13	41155.32	88.48	1.129	0.30 (0.30)	0.99	38864.5	12410.00
14	41004.10	92.51	1.108	0.30 (0.30)	0.99	40792.8	12400.00
15	40883.23	94.89	1.097	0.30 (0.30)	0.99	41853.8	11111.00
16	40538.40	101.12	1.069	0.30 (0.30)	0.99	44161.6	12201.00
17	40107.81	105.04	1.051	0.30 (0.30)	0.99	45246.3	12111.00
18	39826.55	107.40	1.040	0.30 (0.30)	0.99	45886.1	10700.00
19	39501.12	110.33	1.027	0.30 (0.30)	0.99	46615.7	12101.10
20	38998.15	114.30	1.009	0.30 (0.30)	0.99	47464.8	10400.00
21	37489.94	122.15	0.977	0.30 (0.30)	0.99	48780.0	12010.00
22	36213.57	127.86	0.962	0.30 (0.30)	0.99	49093.7	10210.00
23	35852.55	130.50	0.956	0.30 (0.30)	0.99	49204.5	12000.00
24	32893.47	153.46	0.895	0.30 (0.30)	0.99	49826.4	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104602.91 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1276.24	9.90	3.945	0.30 (0.24)	0.79	382.4	940.00
2	1276.37	10.13	3.877	0.30 (0.24)	0.79	389.7	930.00
3	1319.64	12.80	3.399	0.30 (0.25)	0.82	465.0	910.00
4	1294.78	16.16	2.880	0.30 (0.25)	0.85	548.0	920.00
5	1265.04	16.96	2.793	0.30 (0.25)	0.85	553.7	950.00
6	1224.20	17.72	2.711	0.30 (0.25)	0.85	553.8	900.00

LONGEST FLOWPATH FROM NODE 920.00 TO NODE 12606.00 = 6933.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20731.33	9.90	3.945	0.30 (0.28)	0.95	2876.9	940.00
2	20817.08	10.13	3.877	0.30 (0.28)	0.95	2943.0	930.00
3	22697.24	12.75	3.407	0.30 (0.29)	0.95	3678.0	800.00
4	22720.98	12.80	3.399	0.30 (0.29)	0.95	3694.6	910.00
5	24420.83	16.16	2.880	0.30 (0.29)	0.96	4924.9	920.00
6	24445.80	16.21	2.874	0.30 (0.29)	0.96	4943.2	818.00
7	24687.95	16.96	2.793	0.30 (0.29)	0.96	5199.3	950.00
8	24786.81	17.28	2.758	0.30 (0.29)	0.96	5307.2	810.00
9	24907.80	17.72	2.711	0.30 (0.29)	0.96	5452.7	900.00
10	26033.36	21.69	2.351	0.30 (0.29)	0.97	6765.7	600.00
11	30601.55	38.40	1.685	0.30 (0.29)	0.98	12890.3	40100.00
12	32198.41	43.45	1.566	0.30 (0.29)	0.98	14741.5	11831.00
13	32973.32	45.94	1.510	0.30 (0.29)	0.98	15694.4	11801.00
14	35982.94	55.77	1.362	0.30 (0.30)	0.99	19991.2	11530.00
15	38392.01	64.58	1.289	0.30 (0.30)	0.99	24996.8	11910.00
16	40571.31	71.87	1.240	0.30 (0.30)	0.99	29578.5	11330.00
17	41691.03	78.31	1.197	0.30 (0.30)	0.99	34009.5	11130.00
18	41635.03	85.89	1.147	0.30 (0.30)	0.99	38003.4	12330.00
19	41591.16	88.48	1.129	0.30 (0.30)	0.99	39418.3	12410.00
20	41429.21	92.51	1.108	0.30 (0.30)	0.99	41346.6	12400.00
21	41302.96	94.89	1.097	0.30 (0.30)	0.99	42407.6	11111.00
22	40944.05	101.12	1.069	0.30 (0.30)	0.99	44715.4	12201.00
23	40504.62	105.04	1.051	0.30 (0.30)	0.99	45800.1	12111.00
24	40218.02	107.40	1.040	0.30 (0.30)	0.99	46439.9	10700.00
25	39885.96	110.33	1.027	0.30 (0.30)	0.99	47169.5	12101.10
26	39374.02	114.30	1.009	0.30 (0.30)	0.99	48018.6	10400.00
27	37850.14	122.15	0.977	0.30 (0.30)	0.99	49333.8	12010.00
28	36566.32	127.86	0.962	0.30 (0.30)	0.99	49647.5	10210.00
29	36201.86	130.50	0.956	0.30 (0.30)	0.99	49758.3	12000.00
30	33212.82	153.46	0.895	0.30 (0.30)	0.99	50380.2	10100.00
TOTAL AREA (ACRES) =						50380.2	

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 41691.03 Tc(MIN.) = 78.314
EFFECTIVE AREA(ACRES) = 34009.47 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
TOTAL AREA (ACRES) = 50380.2
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104602.91 FEET.

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
MAINLINE Tc(MIN.) = 78.31 S26.3-6					
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.197					
SUBAREA LOSS RATE DATA(AMC II):					
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	0.30	0.30	1.000	63
NATURAL FAIR COVER					
"GRASS"	B	0.30	0.30	1.000	69

PUBLIC PARK B 0.40 0.30 0.850 56
 NATURAL FAIR COVER
 "CHAPARRAL,NARROWLEAF" B 0.60 0.30 1.000 72
 COMMERCIAL B 1.10 0.30 0.100 56
 PUBLIC PARK B 0.80 0.30 0.850 56
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.666
 SUBAREA AREA(ACRES) = 3.50 SUBAREA RUNOFF(CFS) = 3.14
 EFFECTIVE AREA(ACRES) = 34012.97 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 50383.7 PEAK FLOW RATE(CFS) = 41691.03
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 78.31 **S26.3-6**
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.197
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 NATURAL FAIR COVER
 "GRASS" B 0.80 0.30 1.000 69
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 0.90 0.30 1.000 65
 AGRICULTURAL POOR COVER
 "ROW CROPS,STRAIGHT ROW" B 1.50 0.30 1.000 81
 NATURAL FAIR COVER
 "OPEN BRUSH" B 1.60 0.30 1.000 66
 NATURAL FAIR COVER
 "OPEN BRUSH" B 1.80 0.30 1.000 66
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 1.90 0.30 1.000 65
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 8.50 SUBAREA RUNOFF(CFS) = 6.86
 EFFECTIVE AREA(ACRES) = 34021.47 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 50392.2 PEAK FLOW RATE(CFS) = 41691.03
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 78.31 **S26.3-6**
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.197
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 NATURAL FAIR COVER
 "OPEN BRUSH" B 3.30 0.30 1.000 66
 PUBLIC PARK B 3.70 0.30 0.850 56
 NATURAL FAIR COVER
 "CHAPARRAL,NARROWLEAF" B 3.90 0.30 1.000 72

PUBLIC PARK B 5.90 0.30 0.850 56
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 9.10 0.30 1.000 65
 NATURAL FAIR COVER
 "OPEN BRUSH" B 20.60 0.30 1.000 66
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.969
 SUBAREA AREA(ACRES) = 46.50 SUBAREA RUNOFF(CFS) = 37.94
 EFFECTIVE AREA(ACRES) = 34067.97 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 50438.7 PEAK FLOW RATE(CFS) = 41691.03
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

=====
 END OF STUDY SUMMARY:
 TOTAL AREA(ACRES) = 50438.7 TC(MIN.) = 78.31
 EFFECTIVE AREA(ACRES) = 34067.97 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.990
 PEAK FLOW RATE(CFS) = 41691.03

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20731.33	9.90	3.945	0.30(0.28)	0.95	2935.4	940.00
2	20817.08	10.13	3.877	0.30(0.28)	0.95	3001.5	930.00
3	22697.24	12.75	3.407	0.30(0.29)	0.95	3736.5	800.00
4	22720.98	12.80	3.399	0.30(0.29)	0.95	3753.1	910.00
5	24420.83	16.16	2.880	0.30(0.29)	0.96	4983.4	920.00
6	24445.80	16.21	2.874	0.30(0.29)	0.96	5001.7	818.00
7	24687.95	16.96	2.793	0.30(0.29)	0.96	5257.8	950.00
8	24786.81	17.28	2.758	0.30(0.29)	0.96	5365.7	810.00
9	24907.80	17.72	2.711	0.30(0.29)	0.96	5511.2	900.00
10	26033.36	21.69	2.351	0.30(0.29)	0.97	6824.2	600.00
11	30601.55	38.40	1.685	0.30(0.29)	0.98	12948.8	40100.00
12	32198.41	43.45	1.566	0.30(0.29)	0.98	14800.0	11831.00
13	32973.32	45.94	1.510	0.30(0.29)	0.98	15752.9	11801.00
14	35982.94	55.77	1.362	0.30(0.30)	0.99	20049.7	11530.00
15	38392.01	64.58	1.289	0.30(0.30)	0.99	25055.3	11910.00
16	40571.31	71.87	1.240	0.30(0.30)	0.99	29637.0	11330.00
17	41691.03	78.31	1.197	0.30(0.30)	0.99	34068.0	11130.00
18	41635.03	85.89	1.147	0.30(0.30)	0.99	38061.9	12330.00
19	41591.16	88.48	1.129	0.30(0.30)	0.99	39476.8	12410.00
20	41429.21	92.51	1.108	0.30(0.30)	0.99	41405.1	12400.00
21	41302.96	94.89	1.097	0.30(0.30)	0.99	42466.1	11111.00
22	40944.05	101.12	1.069	0.30(0.30)	0.99	44773.9	12201.00
23	40504.62	105.04	1.051	0.30(0.30)	0.99	45858.6	12111.00
24	40218.02	107.40	1.040	0.30(0.30)	0.99	46498.4	10700.00
25	39885.96	110.33	1.027	0.30(0.30)	0.99	47228.0	12101.10
26	39374.02	114.30	1.009	0.30(0.30)	0.99	48077.1	10400.00
27	37850.14	122.15	0.977	0.30(0.30)	0.99	49392.3	12010.00
28	36566.32	127.86	0.962	0.30(0.30)	0.99	49706.0	10210.00
29	36201.86	130.50	0.956	0.30(0.30)	0.99	49816.8	12000.00
30	33212.82	153.46	0.895	0.30(0.30)	0.99	50438.7	10100.00

=====
 END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 127 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 100-YR EV FEB 2023 ROKAMOTO *

FILE NAME: RU00EV27.DAT
TIME/DATE OF STUDY: 14:20 02/07/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 100.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 6.046
- 2) 10.00; 3.873
- 3) 15.00; 2.987
- 4) 20.00; 2.453
- 5) 25.00; 2.121
- 6) 30.00; 1.894
- 7) 40.00; 1.637
- 8) 50.00; 1.414
- 9) 60.00; 1.313
- 10) 90.00; 1.111
- 11) 120.00; 0.975
- 12) 180.00; 0.818
- 13) 360.00; 0.610
- 14) 1200.00; 0.267

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES WIDTH (FT)	LIKE HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: RU00EV26.DNA

S26

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22720.98	12.80	0.30 (0.29)	0.95	3753.1	910.00
2	24907.80	17.72	0.30 (0.29)	0.96	5511.2	900.00
3	26033.36	21.69	0.30 (0.29)	0.97	6824.2	600.00
4	30601.55	38.40	0.30 (0.29)	0.98	12948.8	40100.00
5	32973.32	45.94	0.30 (0.29)	0.98	15752.9	11801.00
6	35982.94	55.77	0.30 (0.30)	0.99	20049.7	11530.00
7	38392.01	64.58	0.30 (0.30)	0.99	25055.3	11910.00
8	40571.31	71.87	0.30 (0.30)	0.99	29637.0	11330.00
9	41691.03	78.31	0.30 (0.30)	0.99	34068.0	11130.00
10	41635.03	85.89	0.30 (0.30)	0.99	38061.9	12330.00
11	41591.16	88.48	0.30 (0.30)	0.99	39476.8	12410.00
12	41429.21	92.51	0.30 (0.30)	0.99	41405.1	12400.00
13	40944.05	101.12	0.30 (0.30)	0.99	44773.9	12201.00
14	40504.62	105.04	0.30 (0.30)	0.99	45858.6	12111.00
15	39885.96	110.33	0.30 (0.30)	0.99	47228.0	12101.10
16	39374.02	114.30	0.30 (0.30)	0.99	48077.1	10400.00
17	37850.14	122.15	0.30 (0.30)	0.99	49392.3	12010.00
18	36566.32	127.86	0.30 (0.30)	0.99	49706.0	10210.00
19	36201.86	130.50	0.30 (0.30)	0.99	49816.8	12000.00
20	33212.82	153.46	0.30 (0.30)	0.99	50438.7	10100.00
TOTAL AREA (ACRES) =						50438.7

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22720.98	12.80	0.30 (0.29)	0.95	3753.1	910.00
2	24907.80	17.72	0.30 (0.29)	0.96	5511.2	900.00
3	26033.36	21.69	0.30 (0.29)	0.97	6824.2	600.00
4	30601.55	38.40	0.30 (0.29)	0.98	12948.8	40100.00
5	32973.32	45.94	0.30 (0.29)	0.98	15752.9	11801.00
6	35982.94	55.77	0.30 (0.30)	0.99	20049.7	11530.00
7	38392.01	64.58	0.30 (0.30)	0.99	25055.3	11910.00
8	40571.31	71.87	0.30 (0.30)	0.99	29637.0	11330.00
9	41691.03	78.31	0.30 (0.30)	0.99	34068.0	11130.00
10	41635.03	85.89	0.30 (0.30)	0.99	38061.9	12330.00
11	41591.16	88.48	0.30 (0.30)	0.99	39476.8	12410.00
12	41429.21	92.51	0.30 (0.30)	0.99	41405.1	12400.00
13	40944.05	101.12	0.30 (0.30)	0.99	44773.9	12201.00

14 40504.62 105.04 0.30(0.30) 0.99 45858.6 12111.00
 15 39885.96 110.33 0.30(0.30) 0.99 47228.0 12101.10
 16 39374.02 114.30 0.30(0.30) 0.99 48077.1 10400.00
 17 37850.14 122.15 0.30(0.30) 0.99 49392.3 12010.00
 18 36566.32 127.86 0.30(0.30) 0.99 49706.0 10210.00
 19 36201.86 130.50 0.30(0.30) 0.99 49816.8 12000.00
 20 33212.82 153.46 0.30(0.30) 0.99 50438.7 10100.00
 TOTAL AREA (ACRES) = 50438.7

FLOW PROCESS FROM NODE 12606.00 TO NODE 12701.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 286.00 DOWNSTREAM(FEET) = 276.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1260.19 CHANNEL SLOPE = 0.0079
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 9.56
 * 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.182

S27.3-1

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

RESIDENTIAL					
"5-7 DWELLINGS/ACRE"	B	0.70	0.30	0.500	56
PUBLIC PARK	B	0.90	0.30	0.850	56
COMMERCIAL	B	3.40	0.30	0.100	56
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	3.60	0.30	1.000	65
PUBLIC PARK	B	10.10	0.30	0.850	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	17.40	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.860

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 41706.04

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 17.60

AVERAGE FLOW DEPTH(FEET) = 9.56 TRAVEL TIME (MIN.) = 1.19

Tc (MIN.) = 79.51

SUBAREA AREA (ACRES) = 36.10 SUBAREA RUNOFF (CFS) = 30.01

EFFECTIVE AREA (ACRES) = 34104.07 AREA-AVERAGED Fm (INCH/HR) = 0.30

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA (ACRES) = 50474.8 PEAK FLOW RATE (CFS) = 41691.03

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT (FEET) = 9.56

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 9.56 FLOW VELOCITY (FEET/SEC.) = 17.59

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12701.00 = 105863.10 FEET.

FLOW PROCESS FROM NODE 12701.00 TO NODE 12720.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 276.00 DOWNSTREAM(FEET) = 275.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 147.65 CHANNEL SLOPE = 0.0068
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 10.00
 CHANNEL FLOW THRU SUBAREA(CFS) = 41691.03
 FLOW VELOCITY (FEET/SEC.) = 16.68 FLOW DEPTH (FEET) = 10.00
 TRAVEL TIME (MIN.) = 0.15 Tc (MIN.) = 79.65
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.00 = 106010.75 FEET.

FLOW PROCESS FROM NODE 12701.00 TO NODE 12720.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
 TIME OF CONCENTRATION (MIN.) = 79.65
 RAINFALL INTENSITY (INCH/HR) = 1.18
 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.99
 EFFECTIVE STREAM AREA (ACRES) = 34104.07
 TOTAL STREAM AREA (ACRES) = 50474.79
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 41691.03

FLOW PROCESS FROM NODE 12710.00 TO NODE 12711.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH (FEET) = 943.56
 ELEVATION DATA: UPSTREAM(FEET) = 940.78 DOWNSTREAM(FEET) = 657.79

Tc = K * [(LENGTH** 3.00) / (ELEVATION CHANGE)] ** 0.20

SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 13.910

* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 3.180

SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------	--------------

NATURAL FAIR COVER						
"GRASS"	B	6.56	0.30	1.000	69	13.91
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30						
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000						
SUBAREA RUNOFF (CFS) = 17.00						
TOTAL AREA (ACRES) = 6.56 PEAK FLOW RATE (CFS) = 17.00						

FLOW PROCESS FROM NODE 12711.00 TO NODE 12712.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 657.79 DOWNSTREAM(FEET) = 585.63
 CHANNEL LENGTH THRU SUBAREA(FEET) = 766.00 CHANNEL SLOPE = 0.0942
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT (FEET) = 0.78
* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.862 **S27-12**

SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"OPEN BRUSH" B 26.94 0.30 1.000 66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 48.14
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.64
AVERAGE FLOW DEPTH (FEET) = 0.74 TRAVEL TIME (MIN.) = 2.26
Tc (MIN.) = 16.17
SUBAREA AREA (ACRES) = 26.94 SUBAREA RUNOFF (CFS) = 62.11
EFFECTIVE AREA (ACRES) = 33.50 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 33.5 PEAK FLOW RATE (CFS) = 77.24
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.97

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.97 FLOW VELOCITY (FEET/SEC.) = 6.64
LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12712.00 = 1709.56 FEET.

FLOW PROCESS FROM NODE 12712.00 TO NODE 12713.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 585.63 DOWNSTREAM (FEET) = 463.75
CHANNEL LENGTH THRU SUBAREA (FEET) = 1025.79 CHANNEL SLOPE = 0.1188
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT (FEET) = 1.03 **S27-13**
* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.622

SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"OPEN BRUSH" B 14.73 0.30 1.000 66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 92.63
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.61
AVERAGE FLOW DEPTH (FEET) = 1.01 TRAVEL TIME (MIN.) = 2.25
Tc (MIN.) = 18.42
SUBAREA AREA (ACRES) = 14.73 SUBAREA RUNOFF (CFS) = 30.78
EFFECTIVE AREA (ACRES) = 48.23 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 48.2 PEAK FLOW RATE (CFS) = 100.79
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 1.07

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 1.07 FLOW VELOCITY (FEET/SEC.) = 7.80

LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12713.00 = 2735.35 FEET.

FLOW PROCESS FROM NODE 12713.00 TO NODE 12714.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 463.75 DOWNSTREAM (FEET) = 360.30
CHANNEL LENGTH THRU SUBAREA (FEET) = 1148.54 CHANNEL SLOPE = 0.0901
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT (FEET) = 1.74 **S27-14**
* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.414

SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"OPEN BRUSH" B 105.64 0.30 1.000 66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 201.40
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.81
AVERAGE FLOW DEPTH (FEET) = 1.70 TRAVEL TIME (MIN.) = 2.17
Tc (MIN.) = 20.59
SUBAREA AREA (ACRES) = 105.64 SUBAREA RUNOFF (CFS) = 200.98
EFFECTIVE AREA (ACRES) = 153.87 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 153.9 PEAK FLOW RATE (CFS) = 292.73
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 2.09

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 2.09 FLOW VELOCITY (FEET/SEC.) = 9.89
LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12714.00 = 3883.89 FEET.

FLOW PROCESS FROM NODE 12714.00 TO NODE 12720.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 360.30 DOWNSTREAM (FEET) = 275.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 1314.99 CHANNEL SLOPE = 0.0649
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT (FEET) = 2.75 **S27-15**
* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.263

SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"OPEN BRUSH" B 127.13 0.30 1.000 66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 405.08
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 9.65

AVERAGE FLOW DEPTH (FEET) = 2.72 TRAVEL TIME (MIN.) = 2.27
 Tc (MIN.) = 22.86
 SUBAREA AREA (ACRES) = 127.13 SUBAREA RUNOFF (CFS) = 224.61
 EFFECTIVE AREA (ACRES) = 281.00 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 281.0 PEAK FLOW RATE (CFS) = 496.45
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 3.03

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 3.03 FLOW VELOCITY (FEET/SEC.) = 10.22
 LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12720.00 = 5198.88 FEET.

 FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====
 TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
 TIME OF CONCENTRATION (MIN.) = 22.86
 RAINFALL INTENSITY (INCH/HR) = 2.26
 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30
 AREA-AVERAGED Ap = 1.00
 EFFECTIVE STREAM AREA (ACRES) = 281.00
 TOTAL STREAM AREA (ACRES) = 281.00
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 496.45

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22720.98	14.44	3.086	0.30 (0.29)	0.95	3789.2	910.00
1	24907.80	19.31	2.526	0.30 (0.29)	0.96	5547.3	900.00
1	26033.36	23.25	2.237	0.30 (0.29)	0.97	6860.3	600.00
1	30601.55	39.89	1.640	0.30 (0.29)	0.98	12984.9	40100.00
1	32973.32	47.39	1.472	0.30 (0.29)	0.98	15789.0	11801.00
1	35982.94	57.18	1.341	0.30 (0.30)	0.99	20085.8	11530.00
1	38392.01	65.95	1.273	0.30 (0.30)	0.99	25091.4	11910.00
1	40571.31	73.23	1.224	0.30 (0.30)	0.99	29673.1	11330.00
1	41691.03	79.65	1.181	0.30 (0.30)	0.99	34104.1	11130.00
1	41635.03	87.23	1.130	0.30 (0.30)	0.99	38098.0	12330.00
1	41591.16	89.82	1.112	0.30 (0.30)	0.99	39512.9	12410.00
1	41429.21	93.85	1.094	0.30 (0.30)	0.99	41441.2	12400.00
1	40944.05	102.47	1.054	0.30 (0.30)	0.99	44810.0	12201.00
1	40504.62	106.39	1.037	0.30 (0.30)	0.99	45894.7	12111.00
1	39885.96	111.70	1.013	0.30 (0.30)	0.99	47264.1	12101.10
1	39374.02	115.67	0.995	0.30 (0.30)	0.99	48113.2	10400.00
1	37850.14	123.53	0.966	0.30 (0.30)	0.99	49428.4	12010.00
1	36566.32	129.26	0.951	0.30 (0.30)	0.99	49742.1	10210.00
1	36201.86	131.90	0.944	0.30 (0.30)	0.99	49852.9	12000.00
1	33212.82	154.91	0.884	0.30 (0.30)	0.99	50474.8	10100.00
2	496.45	22.86	2.263	0.30 (0.30)	1.00	281.0	12710.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23166.06	14.44	3.086	0.30 (0.29)	0.95	3966.6	910.00
2	25383.47	19.31	2.526	0.30 (0.29)	0.97	5784.7	900.00
3	26417.65	22.86	2.263	0.30 (0.29)	0.97	7010.5	12710.00
4	26523.22	23.25	2.237	0.30 (0.29)	0.97	7141.3	600.00
5	30940.42	39.89	1.640	0.30 (0.29)	0.98	13265.9	40100.00
6	33269.76	47.39	1.472	0.30 (0.29)	0.98	16070.0	11801.00
7	36246.33	57.18	1.341	0.30 (0.30)	0.99	20366.8	11530.00
8	38638.06	65.95	1.273	0.30 (0.30)	0.99	25372.4	11910.00
9	40804.98	73.23	1.224	0.30 (0.30)	0.99	29954.1	11330.00
10	41913.75	79.65	1.181	0.30 (0.30)	0.99	34385.1	11130.00
11	41844.84	87.23	1.130	0.30 (0.30)	0.99	38379.0	12330.00
12	41796.57	89.82	1.112	0.30 (0.30)	0.99	39793.9	12410.00
13	41629.89	93.85	1.094	0.30 (0.30)	0.99	41722.2	12400.00
14	41134.85	102.47	1.054	0.30 (0.30)	0.99	45091.0	12201.00
15	40690.93	106.39	1.037	0.30 (0.30)	0.99	46175.7	12111.00
16	40066.19	111.70	1.013	0.30 (0.30)	0.99	47545.1	12101.10
17	39549.70	115.67	0.995	0.30 (0.30)	0.99	48394.2	10400.00
18	38018.51	123.53	0.966	0.30 (0.30)	0.99	49709.4	12010.00
19	36730.90	129.26	0.951	0.30 (0.30)	0.99	50023.1	10210.00
20	36364.69	131.90	0.944	0.30 (0.30)	0.99	50133.9	12000.00
21	33360.43	154.91	0.884	0.30 (0.30)	0.99	50755.8	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
 PEAK FLOW RATE (CFS) = 41913.75 Tc (MIN.) = 79.65
 EFFECTIVE AREA (ACRES) = 34385.07 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 50755.8
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.00 = 10610.75 FEET.

 FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====
 ELEVATION DATA: UPSTREAM (FEET) = 275.00 DOWNSTREAM (FEET) = 258.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 2669.21 CHANNEL SLOPE = 0.0064
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT (FEET) = 10.20
 * 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.162

S27.3-3

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.20	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.30	0.30	1.000	65
COMMERCIAL	B	0.30	0.30	0.100	56
NATURAL FAIR COVER					

"MEADOWS" B 0.50 0.30 1.000 70
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.841
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 41914.45
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 16.37
 AVERAGE FLOW DEPTH (FEET) = 10.20 TRAVEL TIME (MIN.) = 2.72
 Tc (MIN.) = 82.37
 SUBAREA AREA (ACRES) = 1.70 SUBAREA RUNOFF (CFS) = 1.39
 EFFECTIVE AREA (ACRES) = 34386.77 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 50757.5 PEAK FLOW RATE (CFS) = 41913.75
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT (FEET) = 10.20

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 10.20 FLOW VELOCITY (FEET/SEC.) = 16.36
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108679.96 FEET.

 FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 82.37 **S27.3-3**
 * 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.162
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 PUBLIC PARK B 0.50 0.30 0.850 56
 NATURAL FAIR COVER
 "WOODLAND, GRASS" B 0.70 0.30 1.000 65
 NATURAL FAIR COVER
 "OPEN BRUSH" B 1.50 0.30 1.000 66
 COMMERCIAL B 1.40 0.30 0.100 56
 COMMERCIAL B 2.30 0.30 0.100 56
 NATURAL FAIR COVER
 "GRASS" B 9.30 0.30 1.000 69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.783
 SUBAREA AREA (ACRES) = 15.70 SUBAREA RUNOFF (CFS) = 13.10
 EFFECTIVE AREA (ACRES) = 34402.47 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 50773.2 PEAK FLOW RATE (CFS) = 41913.75
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 82.37 **S27.3-3**
 * 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.162
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 NATURAL FAIR COVER

"WOODLAND, GRASS" B 11.20 0.30 1.000 65
 NATURAL FAIR COVER
 "WOODLAND, GRASS" B 11.40 0.30 1.000 65
 NATURAL FAIR COVER
 "CHAPARRAL, NARROWLEAF" B 11.80 0.30 1.000 72
 NATURAL FAIR COVER
 "OPEN BRUSH" B 27.70 0.30 1.000 66
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 62.10 SUBAREA RUNOFF (CFS) = 48.20
 EFFECTIVE AREA (ACRES) = 34464.57 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 50835.3 PEAK FLOW RATE (CFS) = 41913.75
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 3C00EVRL.DNA **C**
 MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2587.27	12.43	0.30 (0.13)	0.42	866.7	410.00
2	2620.20	13.81	0.30 (0.13)	0.42	948.0	420.00
3	2688.04	17.65	0.30 (0.13)	0.42	1158.3	310.00
4	2683.83	17.96	0.30 (0.13)	0.42	1171.6	400.00
5	2574.38	20.61	0.30 (0.13)	0.42	1248.0	430.00
6	2557.64	21.17	0.30 (0.13)	0.42	1263.6	300.00
7	2553.07	21.34	0.30 (0.13)	0.42	1267.8	320.00
8	2212.77	26.96	0.30 (0.13)	0.43	1292.3	390.00
TOTAL AREA (ACRES) =			1292.3			

 FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23166.06	17.75	2.694	0.30 (0.29)	0.95	4046.1	910.00
2	25383.47	22.52	2.286	0.30 (0.29)	0.97	5864.2	900.00
3	26417.65	26.02	2.074	0.30 (0.29)	0.97	7090.0	12710.00
4	26523.22	26.41	2.057	0.30 (0.29)	0.97	7220.8	600.00
5	30940.42	42.89	1.573	0.30 (0.29)	0.98	13345.4	40100.00
6	33269.76	50.32	1.411	0.30 (0.29)	0.98	16149.5	11801.00
7	36246.33	60.03	1.313	0.30 (0.30)	0.99	20446.3	11530.00
8	38638.06	68.74	1.254	0.30 (0.30)	0.99	25451.9	11910.00
9	40804.98	75.97	1.205	0.30 (0.30)	0.99	30033.6	11330.00
10	41913.75	82.37	1.162	0.30 (0.30)	0.99	34464.6	11130.00
11	41844.84	89.95	1.111	0.30 (0.30)	0.99	38458.5	12330.00
12	41796.57	92.55	1.099	0.30 (0.30)	0.99	39873.4	12410.00
13	41629.89	96.58	1.081	0.30 (0.30)	0.99	41801.7	12400.00
14	41134.85	105.21	1.042	0.30 (0.30)	0.99	45170.5	12201.00
15	40690.93	109.13	1.024	0.30 (0.30)	0.99	46255.2	12111.00

16 40066.19 114.45 1.000 0.30(0.30) 0.99 47624.6 12101.10
 17 39549.70 118.44 0.982 0.30(0.30) 0.99 48473.7 10400.00
 18 38018.51 126.33 0.958 0.30(0.30) 0.99 49788.9 12010.00
 19 36730.90 132.10 0.943 0.30(0.30) 0.99 50102.6 10210.00
 20 36364.69 134.75 0.936 0.30(0.30) 0.99 50213.4 12000.00
 21 33360.43 157.83 0.876 0.30(0.30) 0.99 50835.3 10100.00
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108679.96 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2587.27	12.43	3.443	0.30(0.13)	0.42	866.7	410.00
2	2620.20	13.81	3.197	0.30(0.13)	0.42	948.0	420.00
3	2688.04	17.65	2.703	0.30(0.13)	0.42	1158.3	310.00
4	2683.83	17.96	2.671	0.30(0.13)	0.42	1171.6	400.00
5	2574.38	20.61	2.412	0.30(0.13)	0.42	1248.0	430.00
6	2557.64	21.17	2.375	0.30(0.13)	0.42	1263.6	300.00
7	2553.07	21.34	2.364	0.30(0.13)	0.42	1267.8	320.00
8	2212.77	26.96	2.032	0.30(0.13)	0.43	1292.3	390.00

LONGEST FLOWPATH FROM NODE 390.00 TO NODE 12720.50 = 13248.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23857.40	12.43	3.443	0.30(0.25)	0.83	3700.1	410.00
2	24423.79	13.81	3.197	0.30(0.25)	0.83	4097.8	420.00
3	25828.25	17.65	2.703	0.30(0.25)	0.83	5183.7	310.00
4	25852.86	17.75	2.694	0.30(0.25)	0.83	5208.4	910.00
5	25950.50	17.96	2.671	0.30(0.25)	0.84	5300.2	400.00
6	27071.35	20.61	2.412	0.30(0.26)	0.86	6385.3	430.00
7	27313.48	21.17	2.375	0.30(0.26)	0.86	6613.2	300.00
8	27388.29	21.34	2.364	0.30(0.26)	0.86	6682.5	320.00
9	27865.07	22.52	2.286	0.30(0.26)	0.87	7137.1	900.00
10	28687.23	26.02	2.074	0.30(0.27)	0.89	8378.2	12710.00
11	28769.32	26.41	2.057	0.30(0.27)	0.89	8510.7	600.00
12	28883.63	26.96	2.032	0.30(0.27)	0.89	8717.8	390.00
13	32619.02	42.89	1.573	0.30(0.28)	0.93	14637.7	40100.00
14	34760.14	50.32	1.411	0.30(0.28)	0.94	17441.8	11801.00
15	37622.79	60.03	1.313	0.30(0.29)	0.95	21738.6	11530.00
16	39946.27	68.74	1.254	0.30(0.29)	0.96	26744.2	11910.00
17	42056.61	75.97	1.205	0.30(0.29)	0.97	31325.9	11330.00
18	43115.23	82.37	1.162	0.30(0.29)	0.97	35756.9	11130.00
19	42986.96	89.95	1.111	0.30(0.29)	0.97	39750.8	12330.00
20	42924.89	92.55	1.099	0.30(0.29)	0.97	41165.7	12410.00
21	42736.96	96.58	1.081	0.30(0.29)	0.97	43094.0	12400.00
22	42196.41	105.21	1.042	0.30(0.29)	0.97	46462.8	12201.00
23	41731.79	109.13	1.024	0.30(0.29)	0.97	47547.5	12111.00
24	41079.00	114.45	1.000	0.30(0.29)	0.97	48916.9	12101.10
25	40541.52	118.44	0.982	0.30(0.29)	0.97	49766.0	10400.00
26	38982.80	126.33	0.958	0.30(0.29)	0.97	51081.2	12010.00
27	37677.66	132.10	0.943	0.30(0.29)	0.98	51394.9	10210.00
28	37303.38	134.75	0.936	0.30(0.29)	0.98	51505.7	12000.00
29	34228.86	157.83	0.876	0.30(0.29)	0.98	52127.6	10100.00

TOTAL AREA (ACRES) = 52127.6

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 43115.23 Tc (MIN.) = 82.373
 EFFECTIVE AREA (ACRES) = 35756.88 AREA-AVERAGED Fm (INCH/HR) = 0.29

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.89
 TOTAL AREA (ACRES) = 52127.6
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108679.96 FEET.

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

FLOW PROCESS FROM NODE 12720.50 TO NODE 12722.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 258.00 DOWNSTREAM (FEET) = 255.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1269.00 CHANNEL SLOPE = 0.0024
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT (FEET) = 13.66
 * 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.150

S27.3-4

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	0.10	0.30	0.850	56
NATURAL FAIR COVER					
"GRASS"	B	0.10	0.30	1.000	69
NATURAL FAIR COVER					
"GRASS"	B	0.20	0.30	1.000	69
NATURAL FAIR COVER					
"GRASS"	B	0.30	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.30	0.30	1.000	66
COMMERCIAL	B	0.40	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.732
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 43115.81
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 11.76
 AVERAGE FLOW DEPTH (FEET) = 13.66 TRAVEL TIME (MIN.) = 1.80
 Tc (MIN.) = 84.17
 SUBAREA AREA (ACRES) = 1.40 SUBAREA RUNOFF (CFS) = 1.17
 EFFECTIVE AREA (ACRES) = 35758.27 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA (ACRES) = 52129.0 PEAK FLOW RATE (CFS) = 43115.23
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT (FEET) = 13.66

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 13.66 FLOW VELOCITY (FEET/SEC.) = 11.76
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12722.00 = 109948.96 FEET.

FLOW PROCESS FROM NODE 12722.00 TO NODE 12722.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 84.17 S27.3-4
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.150
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	0.50	0.30	0.100	56
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.60	0.30	1.000	65
NATURAL POOR COVER					
"BARREN"	B	0.60	0.30	1.000	86
COMMERCIAL	B	0.60	0.30	0.100	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.90	0.30	1.000	66
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	1.00	0.30	1.000	63

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.764
 SUBAREA AREA(ACRES) = 4.20 SUBAREA RUNOFF(CFS) = 3.48
 EFFECTIVE AREA(ACRES) = 35762.47 AREA-AVERAGED Fm(INCH/HR) = 0.29
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA(ACRES) = 52133.2 PEAK FLOW RATE(CFS) = 43115.23
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12722.00 TO NODE 12722.00 IS CODE = 81

 >>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
 =====

MAINLINE Tc(MIN.) = 84.17 S27.3-4
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.150
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	1.30	0.30	1.000	65
NATURAL FAIR COVER					
"MEADOWS"	B	3.20	0.30	1.000	70
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	3.70	0.30	1.000	65
NATURAL FAIR COVER					
"OPEN BRUSH"	B	12.00	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 20.20 SUBAREA RUNOFF(CFS) = 15.46
 EFFECTIVE AREA(ACRES) = 35782.67 AREA-AVERAGED Fm(INCH/HR) = 0.29
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA(ACRES) = 52153.4 PEAK FLOW RATE(CFS) = 43115.23
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12722.00 TO NODE 12740.00 IS CODE = 56

 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<
 =====

ELEVATION DATA: UPSTREAM(FEET) = 255.00 DOWNSTREAM(FEET) = 252.10
 CHANNEL LENGTH THRU SUBAREA(FEET) = 624.00 CHANNEL SLOPE = 0.0046

GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 11.32 S27.3-5
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.146
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS,STRAIGHT ROW"	B	0.10	0.30	1.000	81
PUBLIC PARK	B	0.50	0.30	0.850	56
NATURAL FAIR COVER					
"GRASS"	B	0.50	0.30	1.000	69
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.80	0.30	1.000	63
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	1.20	0.30	1.000	65
COMMERCIAL	B	1.50	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.690
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 43117.17
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 14.84
 AVERAGE FLOW DEPTH(FEET) = 11.32 TRAVEL TIME(MIN.) = 0.70
 Tc(MIN.) = 84.87
 SUBAREA AREA(ACRES) = 4.60 SUBAREA RUNOFF(CFS) = 3.89
 EFFECTIVE AREA(ACRES) = 35787.27 AREA-AVERAGED Fm(INCH/HR) = 0.29
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA(ACRES) = 52158.0 PEAK FLOW RATE(CFS) = 43115.23
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 11.32

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 11.32 FLOW VELOCITY(FEET/SEC.) = 14.84
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12740.00 = 110572.96 FEET.

 FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
 =====

MAINLINE Tc(MIN.) = 84.87 S27.3-5
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.146
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	2.50	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	2.60	0.30	1.000	69
NATURAL FAIR COVER					
"GRASS"	B	2.80	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	5.40	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	6.20	0.30	1.000	65
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	6.50	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.913
SUBAREA AREA(ACRES) = 26.00 SUBAREA RUNOFF(CFS) = 20.39
EFFECTIVE AREA(ACRES) = 35813.27 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 52184.0 PEAK FLOW RATE(CFS) = 43115.23
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 84.87
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.146 **S27.3-5**

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"OPEN BRUSH" B 6.70 0.30 1.000 66
NATURAL FAIR COVER
"OPEN BRUSH" B 12.00 0.30 1.000 66
NATURAL FAIR COVER
"CHAPARRAL,BROADLEAF" B 20.30 0.30 1.000 63
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 39.00 SUBAREA RUNOFF(CFS) = 29.68
EFFECTIVE AREA(ACRES) = 35852.27 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 52223.0 PEAK FLOW RATE(CFS) = 43115.23
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION(MIN.) = 84.87
RAINFALL INTENSITY(INCH/HR) = 1.15
AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.97
EFFECTIVE STREAM AREA(ACRES) = 35852.27
TOTAL STREAM AREA(ACRES) = 52222.99
PEAK FLOW RATE(CFS) AT CONFLUENCE = 43115.23

FLOW PROCESS FROM NODE 12730.00 TO NODE 12731.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH(FEET) = 561.54
ELEVATION DATA: UPSTREAM(FEET) = 613.29 DOWNSTREAM(FEET) = 551.75

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 13.823

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.196 **S27-31**
SUBAREA Tc AND LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)
NATURAL FAIR COVER
"CHAPARRAL,BROADLEAF" B 6.33 0.30 1.000 63 13.82
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 16.50
TOTAL AREA(ACRES) = 6.33 PEAK FLOW RATE(CFS) = 16.50

FLOW PROCESS FROM NODE 12731.00 TO NODE 12732.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 551.75 DOWNSTREAM(FEET) = 494.40
CHANNEL LENGTH THRU SUBAREA(FEET) = 971.91 CHANNEL SLOPE = 0.0590
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.98 **S27-32**
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.771

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"OPEN BRUSH" B 34.62 0.30 1.000 66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 55.18
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.06
AVERAGE FLOW DEPTH(FEET) = 0.92 TRAVEL TIME(MIN.) = 3.20
Tc(MIN.) = 17.02
SUBAREA AREA(ACRES) = 34.62 SUBAREA RUNOFF(CFS) = 76.99
EFFECTIVE AREA(ACRES) = 40.95 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 40.9 PEAK FLOW RATE(CFS) = 91.07
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.23

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.23 FLOW VELOCITY(FEET/SEC.) = 5.97
LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12732.00 = 1533.45 FEET.

FLOW PROCESS FROM NODE 12732.00 TO NODE 12733.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 494.40 DOWNSTREAM(FEET) = 431.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1156.41 CHANNEL SLOPE = 0.0548
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.70
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.468

S27-33

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"OPEN BRUSH" B 59.52 0.30 1.000 66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 149.24
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.79
AVERAGE FLOW DEPTH(FEET) = 1.65 TRAVEL TIME(MIN.) = 2.84
Tc(MIN.) = 19.86
SUBAREA AREA(ACRES) = 59.52 SUBAREA RUNOFF(CFS) = 116.12
EFFECTIVE AREA(ACRES) = 100.47 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 100.5 PEAK FLOW RATE(CFS) = 196.02
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.92

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.92 FLOW VELOCITY(FEET/SEC.) = 7.38
LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12733.00 = 2689.86 FEET.

FLOW PROCESS FROM NODE 12733.00 TO NODE 12734.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 431.00 DOWNSTREAM(FEET) = 367.10
CHANNEL LENGTH THRU SUBAREA(FEET) = 1654.48 CHANNEL SLOPE = 0.0386
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.45
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.201

S27-34

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"OPEN BRUSH" B 64.05 0.30 1.000 66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 250.87
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.00
AVERAGE FLOW DEPTH(FEET) = 2.42 TRAVEL TIME(MIN.) = 3.94
Tc(MIN.) = 23.80
SUBAREA AREA(ACRES) = 64.05 SUBAREA RUNOFF(CFS) = 109.57
EFFECTIVE AREA(ACRES) = 164.52 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 164.5 PEAK FLOW RATE(CFS) = 281.43
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.57

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 2.57 FLOW VELOCITY(FEET/SEC.) = 7.24
LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12734.00 = 4344.34 FEET.

FLOW PROCESS FROM NODE 12734.00 TO NODE 12740.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 367.11 DOWNSTREAM(FEET) = 252.10
CHANNEL LENGTH THRU SUBAREA(FEET) = 1880.98 CHANNEL SLOPE = 0.0611
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.37
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.011

S27-35

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"OPEN BRUSH" B 26.02 0.30 1.000 66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 301.48
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.68
AVERAGE FLOW DEPTH(FEET) = 2.36 TRAVEL TIME(MIN.) = 3.61
Tc(MIN.) = 27.41
SUBAREA AREA(ACRES) = 26.02 SUBAREA RUNOFF(CFS) = 40.08
EFFECTIVE AREA(ACRES) = 190.54 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 190.5 PEAK FLOW RATE(CFS) = 293.49
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.32

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 2.32 FLOW VELOCITY(FEET/SEC.) = 8.62
LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12740.00 = 6225.32 FEET.

FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 27.41
RAINFALL INTENSITY(INCH/HR) = 2.01
AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 1.00
EFFECTIVE STREAM AREA(ACRES) = 190.54
TOTAL STREAM AREA(ACRES) = 190.54
PEAK FLOW RATE(CFS) AT CONFLUENCE = 293.49

** CONFLUENCE DATA **
Table with 7 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 3 rows of data.

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 85.93

* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.138

S27.3-6

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL FAIR COVER

"GRASS" B 3.90 0.30 1.000 69

NATURAL FAIR COVER

"GRASS" B 8.70 0.30 1.000 69

NATURAL FAIR COVER

"WOODLAND,GRASS" B 10.30 0.30 1.000 65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 22.90 SUBAREA RUNOFF(CFS) = 17.28

EFFECTIVE AREA(ACRES) = 36072.11 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97

TOTAL AREA(ACRES) = 52442.8 PEAK FLOW RATE(CFS) = 43260.22

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 52442.8 TC(MIN.) = 85.93

EFFECTIVE AREA(ACRES) = 36072.11 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.970

PEAK FLOW RATE(CFS) = 43260.22

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24112.43	16.73	2.802	0.30(0.25)	0.84	3932.2	410.00
2	24686.02	18.09	2.657	0.30(0.25)	0.84	4339.3	420.00
3	26100.55	21.85	2.330	0.30(0.25)	0.84	5451.5	310.00
4	26125.57	21.94	2.324	0.30(0.25)	0.84	5476.9	910.00
5	26224.18	22.15	2.310	0.30(0.25)	0.84	5570.2	400.00
6	27353.71	24.74	2.138	0.30(0.26)	0.86	6673.4	430.00
7	27596.96	25.29	2.108	0.30(0.26)	0.86	6905.1	300.00
8	27672.05	25.46	2.100	0.30(0.26)	0.86	6975.6	320.00
9	28151.49	26.61	2.048	0.30(0.26)	0.87	7438.3	900.00
10	28636.54	28.63	1.956	0.30(0.26)	0.88	8173.9	12730.00
11	28969.39	30.08	1.892	0.30(0.27)	0.89	8693.4	12710.00
12	29048.49	30.46	1.882	0.30(0.27)	0.89	8826.0	600.00
13	29158.53	31.01	1.868	0.30(0.27)	0.89	9033.1	390.00
14	32826.82	46.78	1.486	0.30(0.28)	0.93	14952.9	40100.00
15	34945.99	54.13	1.372	0.30(0.28)	0.94	17757.0	11801.00
16	37793.46	63.74	1.288	0.30(0.29)	0.95	22053.8	11530.00
17	40106.93	72.39	1.230	0.30(0.29)	0.96	27059.5	11910.00
18	42208.98	79.55	1.181	0.30(0.29)	0.97	31641.1	11330.00
19	43260.22	85.93	1.138	0.30(0.29)	0.97	36072.1	11130.00
20	43124.12	93.51	1.095	0.30(0.29)	0.97	40066.1	12330.00
21	43060.04	96.11	1.083	0.30(0.29)	0.97	41480.9	12410.00
22	42868.98	100.14	1.065	0.30(0.29)	0.97	43409.3	12400.00
23	42321.71	108.79	1.026	0.30(0.29)	0.97	46778.0	12201.00
24	41854.03	112.73	1.008	0.30(0.29)	0.97	47862.7	12111.00
25	41197.10	118.07	0.984	0.30(0.29)	0.97	49232.2	12101.10
26	40656.83	122.06	0.970	0.30(0.29)	0.97	50081.2	10400.00

27	39094.55	130.01	0.949	0.30(0.29)	0.97	51396.4	12010.00
28	37786.81	135.81	0.934	0.30(0.29)	0.98	51710.1	10210.00
29	37411.34	138.47	0.927	0.30(0.29)	0.98	51821.0	12000.00
30	34326.43	161.66	0.866	0.30(0.29)	0.98	52442.8	10100.00

END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 128 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 100-YR EV FEB 2023 ROKAMOTO *

FILE NAME: RU00EV28.DAT
TIME/DATE OF STUDY: 14:20 02/07/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 100.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 6.046
- 2) 10.00; 3.873
- 3) 15.00; 2.987
- 4) 20.00; 2.453
- 5) 25.00; 2.121
- 6) 30.00; 1.894
- 7) 40.00; 1.637
- 8) 50.00; 1.414
- 9) 60.00; 1.313
- 10) 90.00; 1.111
- 11) 120.00; 0.975
- 12) 180.00; 0.818
- 13) 360.00; 0.610
- 14) 1200.00; 0.267

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:

- 1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: RU00EV27.DNA

S27

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24686.02	18.09	0.30 (0.25)	0.84	4339.3	420.00
2	26224.18	22.15	0.30 (0.25)	0.84	5570.2	400.00
3	29158.53	31.01	0.30 (0.27)	0.89	9033.1	390.00
4	32826.82	46.78	0.30 (0.28)	0.93	14952.9	40100.00
5	34945.99	54.13	0.30 (0.28)	0.94	17757.0	11801.00
6	37793.46	63.74	0.30 (0.29)	0.95	22053.8	11530.00
7	40106.93	72.39	0.30 (0.29)	0.96	27059.5	11910.00
8	42208.98	79.55	0.30 (0.29)	0.97	31641.1	11330.00
9	43260.22	85.93	0.30 (0.29)	0.97	36072.1	11130.00
10	43124.12	93.51	0.30 (0.29)	0.97	40066.1	12330.00
11	43060.04	96.11	0.30 (0.29)	0.97	41480.9	12410.00
12	42868.98	100.14	0.30 (0.29)	0.97	43409.3	12400.00
13	42321.71	108.79	0.30 (0.29)	0.97	46778.0	12201.00
14	41854.03	112.73	0.30 (0.29)	0.97	47862.7	12111.00
15	41197.10	118.07	0.30 (0.29)	0.97	49232.2	12101.10
16	40656.83	122.06	0.30 (0.29)	0.97	50081.2	10400.00
17	39094.55	130.01	0.30 (0.29)	0.97	51396.4	12010.00
18	37786.81	135.81	0.30 (0.29)	0.98	51710.1	10210.00
19	37411.34	138.47	0.30 (0.29)	0.98	51821.0	12000.00
20	34326.43	161.66	0.30 (0.29)	0.98	52442.8	10100.00
TOTAL AREA (ACRES) =						52442.8

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P501XXCE.DNA

HZ-501

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	411.92	13.14	0.30 (0.25)	0.84	174.7	50110.00
2	436.73	17.51	0.30 (0.26)	0.85	223.2	50100.00
TOTAL AREA (ACRES) =						223.2

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
------------------	------------	--------------	----------------------	----	---------------	-------------------

```

1      411.92  13.14  0.30( 0.25) 0.84      174.7  50110.00
2      436.73  17.51  0.30( 0.26) 0.85      223.2  50100.00
TOTAL AREA (ACRES) =          223.2

```

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

```

STREAM      Q      Tc      Intensity      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.) (INCH/HR) (INCH/HR)  (ACRES)  NODE
1      411.92  13.14   3.317  0.30( 0.25) 0.84      174.7  50110.00
2      436.73  17.51   2.719  0.30( 0.26) 0.85      223.2  50100.00
LONGEST FLOWPATH FROM NODE 50100.00 TO NODE 12800.00 = 4170.00 FEET.

```

** MEMORY BANK # 1 CONFLUENCE DATA **

```

STREAM      Q      Tc      Intensity      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.) (INCH/HR) (INCH/HR)  (ACRES)  NODE
1      24686.02 18.09   2.657  0.30( 0.25) 0.84      4339.3  420.00
2      26224.18 22.15   2.310  0.30( 0.25) 0.84      5570.2  400.00
3      29158.53 31.01   1.868  0.30( 0.27) 0.89      9033.1  390.00
4      32826.82 46.78   1.486  0.30( 0.28) 0.93     14952.9 40100.00
5      34945.99 54.13   1.372  0.30( 0.28) 0.94     17757.0 11801.00
6      37793.46 63.74   1.288  0.30( 0.29) 0.95     22053.8 11530.00
7      40106.93 72.39   1.230  0.30( 0.29) 0.96     27059.5 11910.00
8      42208.98 79.55   1.181  0.30( 0.29) 0.97     31641.1 11330.00
9      43260.22 85.93   1.138  0.30( 0.29) 0.97     36072.1 11130.00
10     43124.12 93.51   1.095  0.30( 0.29) 0.97     40066.1 12330.00
11     43060.04 96.11   1.083  0.30( 0.29) 0.97     41480.9 12410.00
12     42868.98 100.14  1.065  0.30( 0.29) 0.97     43409.3 12400.00
13     42321.71 108.79  1.026  0.30( 0.29) 0.97     46778.0 12201.00
14     41854.03 112.73  1.008  0.30( 0.29) 0.97     47862.7 12111.00
15     41197.10 118.07  0.984  0.30( 0.29) 0.97     49232.2 12101.10
16     40656.83 122.06  0.970  0.30( 0.29) 0.97     50081.2 10400.00
17     39094.55 130.01  0.949  0.30( 0.29) 0.97     51396.4 12010.00
18     37786.81 135.81  0.934  0.30( 0.29) 0.98     51710.1 10210.00
19     37411.34 138.47  0.927  0.30( 0.29) 0.98     51821.0 12000.00
20     34326.43 161.66  0.866  0.30( 0.29) 0.98     52442.8 10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111792.96 FEET.

```

** PEAK FLOW RATE TABLE **

```

STREAM      Q      Tc      Intensity      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.) (INCH/HR) (INCH/HR)  (ACRES)  NODE
1      23259.74 13.14   3.317  0.30( 0.25) 0.84      3327.0  50110.00
2      24948.14 17.51   2.719  0.30( 0.25) 0.84      4424.7  50100.00
3      25111.87 18.09   2.657  0.30( 0.25) 0.84      4562.5  420.00
4      26588.50 22.15   2.310  0.30( 0.25) 0.84      5793.4  400.00
5      29444.48 31.01   1.868  0.30( 0.27) 0.89      9256.3  390.00
6      33045.01 46.78   1.486  0.30( 0.28) 0.93     15176.1 40100.00
7      35144.04 54.13   1.372  0.30( 0.28) 0.94     17980.2 11801.00
8      37976.53 63.74   1.288  0.30( 0.29) 0.95     22277.0 11530.00
9      40279.69 72.39   1.230  0.30( 0.29) 0.96     27282.7 11910.00
10     42373.18 79.55   1.181  0.30( 0.29) 0.97     31864.3 11330.00
11     43416.81 85.93   1.138  0.30( 0.29) 0.97     36295.3 11130.00
12     43273.03 93.51   1.095  0.30( 0.29) 0.97     40289.3 12330.00
13     43206.86 96.11   1.083  0.30( 0.29) 0.97     41704.1 12410.00

```

```

14     43012.56 100.14  1.065  0.30( 0.29) 0.97     43632.5 12400.00
15     42458.34 108.79  1.026  0.30( 0.29) 0.97     47001.2 12201.00
16     41987.50 112.73  1.008  0.30( 0.29) 0.97     48085.9 12111.00
17     41326.27 118.07  0.984  0.30( 0.29) 0.97     49455.4 12101.10
18     40783.49 122.06  0.970  0.30( 0.29) 0.97     50304.4 10400.00
19     39217.53 130.01  0.949  0.30( 0.29) 0.97     51619.6 12010.00
20     37907.10 135.81  0.934  0.30( 0.29) 0.97     51933.3 10210.00
21     37530.39 138.47  0.927  0.30( 0.29) 0.97     52044.2 12000.00
22     34434.72 161.66  0.866  0.30( 0.29) 0.97     52666.0 10100.00
TOTAL AREA (ACRES) =          52666.0

```

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

```

PEAK FLOW RATE(CFS) = 43416.81 Tc(MIN.) = 85.931
EFFECTIVE AREA(ACRES) = 36295.31 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 52666.0
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111792.96 FEET.

```

=====
END OF STUDY SUMMARY:

```

TOTAL AREA(ACRES) = 52666.0 TC(MIN.) = 85.93
EFFECTIVE AREA(ACRES) = 36295.31 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.969
PEAK FLOW RATE(CFS) = 43416.81

```

** PEAK FLOW RATE TABLE **

```

STREAM      Q      Tc      Intensity      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.) (INCH/HR) (INCH/HR)  (ACRES)  NODE
1      23259.74 13.14   3.317  0.30( 0.25) 0.84      3327.0  50110.00
2      24948.14 17.51   2.719  0.30( 0.25) 0.84      4424.7  50100.00
3      25111.87 18.09   2.657  0.30( 0.25) 0.84      4562.5  420.00
4      26588.50 22.15   2.310  0.30( 0.25) 0.84      5793.4  400.00
5      29444.48 31.01   1.868  0.30( 0.27) 0.89      9256.3  390.00
6      33045.01 46.78   1.486  0.30( 0.28) 0.93     15176.1 40100.00
7      35144.04 54.13   1.372  0.30( 0.28) 0.94     17980.2 11801.00
8      37976.53 63.74   1.288  0.30( 0.29) 0.95     22277.0 11530.00
9      40279.69 72.39   1.230  0.30( 0.29) 0.96     27282.7 11910.00
10     42373.18 79.55   1.181  0.30( 0.29) 0.97     31864.3 11330.00
11     43416.81 85.93   1.138  0.30( 0.29) 0.97     36295.3 11130.00
12     43273.03 93.51   1.095  0.30( 0.29) 0.97     40289.3 12330.00
13     43206.86 96.11   1.083  0.30( 0.29) 0.97     41704.1 12410.00
14     43012.56 100.14  1.065  0.30( 0.29) 0.97     43632.5 12400.00
15     42458.34 108.79  1.026  0.30( 0.29) 0.97     47001.2 12201.00
16     41987.50 112.73  1.008  0.30( 0.29) 0.97     48085.9 12111.00
17     41326.27 118.07  0.984  0.30( 0.29) 0.97     49455.4 12101.10
18     40783.49 122.06  0.970  0.30( 0.29) 0.97     50304.4 10400.00
19     39217.53 130.01  0.949  0.30( 0.29) 0.97     51619.6 12010.00
20     37907.10 135.81  0.934  0.30( 0.29) 0.97     51933.3 10210.00
21     37530.39 138.47  0.927  0.30( 0.29) 0.97     52044.2 12000.00
22     34434.72 161.66  0.866  0.30( 0.29) 0.97     52666.0 10100.00

```

=====
END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 129 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 100-YR EV FEB 2023 ROKAMOTO *

FILE NAME: RU00EV29.DAT
TIME/DATE OF STUDY: 14:21 02/07/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 100.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 6.006
- 2) 10.00; 3.853
- 3) 15.00; 2.975
- 4) 20.00; 2.445
- 5) 25.00; 2.115
- 6) 30.00; 1.889
- 7) 40.00; 1.632
- 8) 50.00; 1.411
- 9) 60.00; 1.307
- 10) 90.00; 1.106
- 11) 120.00; 0.969
- 12) 180.00; 0.813
- 13) 360.00; 0.605
- 14) 1200.00; 0.265

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<<

PEAK FLOWRATE TABLE FILE NAME: RU00EV28.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

S28

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23259.74	13.14	0.30 (0.25)	0.84	3327.0	50110.00
2	25111.87	18.09	0.30 (0.25)	0.84	4562.5	420.00
3	26588.50	22.15	0.30 (0.25)	0.84	5793.4	400.00
4	29444.48	31.01	0.30 (0.27)	0.89	9256.3	390.00
5	33045.01	46.78	0.30 (0.28)	0.93	15176.1	40100.00
6	35144.04	54.13	0.30 (0.28)	0.94	17980.2	11801.00
7	37976.53	63.74	0.30 (0.29)	0.95	22277.0	11530.00
8	40279.69	72.39	0.30 (0.29)	0.96	27282.7	11910.00
9	42373.18	79.55	0.30 (0.29)	0.97	31864.3	11330.00
10	43416.81	85.93	0.30 (0.29)	0.97	36295.3	11130.00
11	43273.03	93.51	0.30 (0.29)	0.97	40289.3	12330.00
12	43012.56	100.14	0.30 (0.29)	0.97	43632.5	12400.00
13	42458.34	108.79	0.30 (0.29)	0.97	47001.2	12201.00
14	41987.50	112.73	0.30 (0.29)	0.97	48085.9	12111.00
15	41326.27	118.07	0.30 (0.29)	0.97	49455.4	12101.10
16	40783.49	122.06	0.30 (0.29)	0.97	50304.4	10400.00
17	39217.53	130.01	0.30 (0.29)	0.97	51619.6	12010.00
18	37907.10	135.81	0.30 (0.29)	0.97	51933.3	10210.00
19	37530.39	138.47	0.30 (0.29)	0.97	52044.2	12000.00
20	34434.72	161.66	0.30 (0.29)	0.97	52666.0	10100.00
TOTAL AREA (ACRES) =		52666.0				

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23259.74	13.14	0.30 (0.25)	0.84	3327.0	50110.00
2	25111.87	18.09	0.30 (0.25)	0.84	4562.5	420.00
3	26588.50	22.15	0.30 (0.25)	0.84	5793.4	400.00
4	29444.48	31.01	0.30 (0.27)	0.89	9256.3	390.00
5	33045.01	46.78	0.30 (0.28)	0.93	15176.1	40100.00
6	35144.04	54.13	0.30 (0.28)	0.94	17980.2	11801.00
7	37976.53	63.74	0.30 (0.29)	0.95	22277.0	11530.00
8	40279.69	72.39	0.30 (0.29)	0.96	27282.7	11910.00
9	42373.18	79.55	0.30 (0.29)	0.97	31864.3	11330.00
10	43416.81	85.93	0.30 (0.29)	0.97	36295.3	11130.00
11	43273.03	93.51	0.30 (0.29)	0.97	40289.3	12330.00
12	43012.56	100.14	0.30 (0.29)	0.97	43632.5	12400.00
13	42458.34	108.79	0.30 (0.29)	0.97	47001.2	12201.00

14	41987.50	112.73	0.30	(0.29)	0.97	48085.9	12111.00
15	41326.27	118.07	0.30	(0.29)	0.97	49455.4	12101.10
16	40783.49	122.06	0.30	(0.29)	0.97	50304.4	10400.00
17	39217.53	130.01	0.30	(0.29)	0.97	51619.6	12010.00
18	37907.10	135.81	0.30	(0.29)	0.97	51933.3	10210.00
19	37530.39	138.47	0.30	(0.29)	0.97	52044.2	12000.00
20	34434.72	161.66	0.30	(0.29)	0.97	52666.0	10100.00
TOTAL AREA (ACRES) =							52666.0

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 12800.00 TO NODE 12901.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 240.00 DOWNSTREAM (FEET) = 216.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 3120.28 CHANNEL SLOPE = 0.0077
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT (FEET) = 9.87
 CHANNEL FLOW THRU SUBAREA (CFS) = 43416.81
 FLOW VELOCITY (FEET/SEC.) = 17.65 FLOW DEPTH (FEET) = 9.87
 TRAVEL TIME (MIN.) = 2.95 Tc (MIN.) = 88.88
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12901.00 = 114913.24 FEET.

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 88.88 **G**
 * 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.114
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	14.30	0.30	0.100	56
PUBLIC PARK	B	9.40	0.30	0.850	56

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.397
 SUBAREA AREA (ACRES) = 23.70 SUBAREA RUNOFF (CFS) = 21.21
 EFFECTIVE AREA (ACRES) = 36319.01 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA (ACRES) = 52689.7 PEAK FLOW RATE (CFS) = 43416.81
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 88.88
 * 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.114

S29.2-1

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	0.20	0.30	0.100	56
RESIDENTIAL					
"5-7 DWELLINGS/ACRE"	B	0.40	0.30	0.500	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.50	0.30	0.900	56
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.60	0.30	1.000	65
COMMERCIAL	B	0.70	0.30	0.100	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.70	0.30	0.900	56

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.635
 SUBAREA AREA (ACRES) = 3.10 SUBAREA RUNOFF (CFS) = 2.57
 EFFECTIVE AREA (ACRES) = 36322.11 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA (ACRES) = 52692.8 PEAK FLOW RATE (CFS) = 43416.81
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 88.88
 * 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.114 **S29.2-1**
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	0.70	0.30	0.850	56
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	1.00	0.30	1.000	65
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.40	0.30	1.000	66
NATURAL FAIR COVER					
"GRASS"	B	1.50	0.30	1.000	69
COMMERCIAL	B	1.70	0.30	0.100	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.90	0.30	1.000	66

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.822
 SUBAREA AREA (ACRES) = 9.20 SUBAREA RUNOFF (CFS) = 7.18
 EFFECTIVE AREA (ACRES) = 36331.31 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA (ACRES) = 52702.0 PEAK FLOW RATE (CFS) = 43416.81
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 88.88
 * 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.114
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

S29.2-1

LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
NATURAL FAIR COVER "WOODLAND, GRASS"	B	3.60	0.30	1.000	65
RESIDENTIAL "5-7 DWELLINGS/ACRE"	B	3.70	0.30	0.500	56
RESIDENTIAL "5-7 DWELLINGS/ACRE"	B	4.10	0.30	0.500	56
RESIDENTIAL ".4 DWELLING/ACRE"	B	5.40	0.30	0.900	56
NATURAL FAIR COVER "OPEN BRUSH"	B	6.70	0.30	1.000	66
NATURAL POOR COVER "BARREN"	B	12.00	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.875
SUBAREA AREA (ACRES) = 35.50 SUBAREA RUNOFF (CFS) = 27.19
EFFECTIVE AREA (ACRES) = 36366.81 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA (ACRES) = 52737.5 PEAK FLOW RATE (CFS) = 43416.81
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 88.88
* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.114

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "GRASS"	B	12.90	0.30	1.000	69
PUBLIC PARK	B	38.60	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.888
SUBAREA AREA (ACRES) = 51.50 SUBAREA RUNOFF (CFS) = 39.27
EFFECTIVE AREA (ACRES) = 36418.31 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA (ACRES) = 52789.0 PEAK FLOW RATE (CFS) = 43416.81
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

S29.2-1

FLOW PROCESS FROM NODE 12901.00 TO NODE 12902.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 216.00 DOWNSTREAM (FEET) = 215.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 122.04 CHANNEL SLOPE = 0.0082
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 9.69
CHANNEL FLOW THRU SUBAREA (CFS) = 43416.81
FLOW VELOCITY (FEET/SEC.) = 18.03 FLOW DEPTH (FEET) = 9.69
TRAVEL TIME (MIN.) = 0.11 Tc (MIN.) = 88.99
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115035.28 FEET.

FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P503XXCE.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

HZ-503

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1954.61	18.51	0.30 (0.22)	0.74	1037.1	50320.00
2	1958.52	19.18	0.30 (0.22)	0.74	1065.7	50240.00
3	1953.83	20.19	0.30 (0.22)	0.74	1103.3	50330.00
4	1953.14	23.39	0.30 (0.22)	0.74	1204.8	50280.00
5	1934.70	24.58	0.30 (0.22)	0.74	1235.7	50300.00
6	1911.74	25.74	0.30 (0.22)	0.74	1257.1	50220.00
7	1820.38	28.97	0.30 (0.22)	0.74	1290.9	50260.00
8	1712.34	32.40	0.30 (0.22)	0.74	1298.6	50200.00
TOTAL AREA (ACRES) =		1298.6				

FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23259.74	16.90	2.773	0.30 (0.25)	0.84	3450.0	50110.00
2	25111.87	21.76	2.329	0.30 (0.25)	0.84	4685.5	420.00
3	26588.50	25.75	2.081	0.30 (0.25)	0.84	5916.4	400.00
4	29444.48	34.49	1.774	0.30 (0.27)	0.89	9379.3	390.00
5	33045.01	50.12	1.410	0.30 (0.28)	0.93	15299.1	40100.00
6	35144.04	57.41	1.334	0.30 (0.28)	0.94	18103.2	11801.00
7	37976.53	66.94	1.260	0.30 (0.29)	0.95	22400.0	11530.00
8	40279.69	75.52	1.203	0.30 (0.29)	0.96	27405.7	11910.00
9	42373.18	82.64	1.155	0.30 (0.29)	0.96	31987.3	11330.00
10	43416.81	88.99	1.113	0.30 (0.29)	0.97	36418.3	11130.00
11	43273.03	96.58	1.076	0.30 (0.29)	0.97	40412.3	12330.00
12	43012.56	103.21	1.046	0.30 (0.29)	0.97	43755.5	12400.00
13	42458.34	111.87	1.006	0.30 (0.29)	0.97	47124.2	12201.00
14	41987.50	115.82	0.988	0.30 (0.29)	0.97	48208.9	12111.00
15	41326.27	121.17	0.966	0.30 (0.29)	0.97	49578.4	12101.10
16	40783.49	125.19	0.956	0.30 (0.29)	0.97	50427.4	10400.00
17	39217.53	133.17	0.935	0.30 (0.29)	0.97	51742.6	12010.00
18	37907.10	139.01	0.920	0.30 (0.29)	0.97	52056.3	10210.00
19	37530.39	141.68	0.913	0.30 (0.29)	0.97	52167.2	12000.00
20	34434.72	164.97	0.852	0.30 (0.29)	0.97	52789.0	10100.00
LONGEST FLOWPATH FROM NODE		10100.00 TO NODE 12902.00 = 115035.28 FEET.					

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1954.61	18.51	2.603	0.30 (0.22)	0.74	1037.1	50320.00
2	1958.52	19.18	2.532	0.30 (0.22)	0.74	1065.7	50240.00
3	1953.83	20.19	2.432	0.30 (0.22)	0.74	1103.3	50330.00
4	1953.14	23.39	2.221	0.30 (0.22)	0.74	1204.8	50280.00
5	1934.70	24.58	2.142	0.30 (0.22)	0.74	1235.7	50300.00

6 1911.74 25.74 2.082 0.30(0.22) 0.74 1257.1 50220.00
7 1820.38 28.97 1.936 0.30(0.22) 0.74 1290.9 50260.00
8 1712.34 32.40 1.827 0.30(0.22) 0.74 1298.6 50200.00
LONGEST FLOWPATH FROM NODE 50220.00 TO NODE 12902.00 = 17597.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25172.42	16.90	2.773	0.30(0.24)	0.82	4397.1	50110.00
2	25826.95	18.51	2.603	0.30(0.24)	0.82	4895.7	50320.00
3	26086.52	19.18	2.532	0.30(0.24)	0.82	5094.9	50240.00
4	26469.01	20.19	2.432	0.30(0.24)	0.82	5390.7	50330.00
5	27065.37	21.76	2.329	0.30(0.25)	0.82	5838.4	420.00
6	27670.66	23.39	2.221	0.30(0.25)	0.82	6395.2	50280.00
7	28092.08	24.58	2.142	0.30(0.25)	0.82	6792.8	50300.00
8	28496.06	25.74	2.082	0.30(0.25)	0.82	7170.0	50220.00
9	28499.92	25.75	2.081	0.30(0.25)	0.82	7173.6	400.00
10	29461.48	28.97	1.936	0.30(0.25)	0.84	8483.6	50260.00
11	30474.84	32.40	1.827	0.30(0.26)	0.86	9851.0	50200.00
12	31099.61	34.49	1.774	0.30(0.26)	0.87	10677.9	390.00
13	34311.76	50.12	1.410	0.30(0.27)	0.92	16597.7	40100.00
14	36329.92	57.41	1.334	0.30(0.28)	0.93	19401.8	11801.00
15	39084.07	66.94	1.260	0.30(0.28)	0.94	23698.6	11530.00
16	41325.88	75.52	1.203	0.30(0.28)	0.95	28704.3	11910.00
17	43368.51	82.64	1.155	0.30(0.29)	0.96	33285.9	11330.00
18	44366.72	88.99	1.113	0.30(0.29)	0.96	37716.9	11130.00
19	44183.68	96.58	1.076	0.30(0.29)	0.96	41710.9	12330.00
20	43890.88	103.21	1.046	0.30(0.29)	0.97	45054.1	12400.00
21	43294.46	111.87	1.006	0.30(0.29)	0.97	48422.8	12201.00
22	42804.37	115.82	0.988	0.30(0.29)	0.97	49507.5	12111.00
23	42119.54	121.17	0.966	0.30(0.29)	0.97	50877.0	12101.10
24	41565.62	125.19	0.956	0.30(0.29)	0.97	51726.0	10400.00
25	39977.51	133.17	0.935	0.30(0.29)	0.97	53041.2	12010.00
26	38650.89	139.01	0.920	0.30(0.29)	0.97	53354.9	10210.00
27	38266.77	141.68	0.913	0.30(0.29)	0.97	53465.8	12000.00
28	35106.50	164.97	0.852	0.30(0.29)	0.97	54087.6	10100.00

TOTAL AREA (ACRES) = 54087.6

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 44366.72 Tc(MIN.) = 88.991
EFFECTIVE AREA(ACRES) = 37716.91 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
TOTAL AREA(ACRES) = 54087.6
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115035.28 FEET.

FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 12902.00 TO NODE 12903.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 215.00 DOWNSTREAM(FEET) = 214.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 895.53 CHANNEL SLOPE = 0.0011
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.300
*ESTIMATED CHANNEL HEIGHT(FEET) = 17.02
CHANNEL FLOW THRU SUBAREA(CFS) = 44366.72
FLOW VELOCITY(FEET/SEC.) = 9.15 FLOW DEPTH(FEET) = 17.02
TRAVEL TIME(MIN.) = 1.63 Tc(MIN.) = 90.62
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115930.81 FEET.

FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P504XXCE.DNA

HZ-504

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	159.82	13.14	0.30(0.28)	0.94	70.7	50400.00	

TOTAL AREA(ACRES) = 70.7

FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25172.42	18.85	2.567	0.30(0.24)	0.82	4397.1	50110.00
2	25826.95	20.44	2.416	0.30(0.24)	0.82	4895.7	50320.00
3	26086.52	21.10	2.372	0.30(0.24)	0.82	5094.9	50240.00
4	26469.01	22.10	2.306	0.30(0.24)	0.82	5390.7	50330.00
5	27065.37	23.66	2.204	0.30(0.25)	0.82	5838.4	420.00
6	27670.66	25.28	2.102	0.30(0.25)	0.82	6395.2	50280.00
7	28092.08	26.46	2.049	0.30(0.25)	0.82	6792.8	50300.00
8	28496.06	27.61	1.997	0.30(0.25)	0.82	7170.0	50220.00
9	28499.92	27.62	1.997	0.30(0.25)	0.82	7173.6	400.00
10	29461.48	30.82	1.868	0.30(0.25)	0.84	8483.6	50260.00
11	30474.84	34.23	1.780	0.30(0.26)	0.86	9851.0	50200.00
12	31099.61	36.30	1.727	0.30(0.26)	0.87	10677.9	390.00
13	34311.76	51.89	1.391	0.30(0.27)	0.92	16597.7	40100.00
14	36329.92	59.15	1.316	0.30(0.28)	0.93	19401.8	11801.00
15	39084.07	68.64	1.249	0.30(0.28)	0.94	23698.6	11530.00
16	41325.88	77.19	1.192	0.30(0.28)	0.95	28704.3	11910.00
17	43368.51	84.28	1.144	0.30(0.29)	0.96	33285.9	11330.00
18	44366.72	90.62	1.103	0.30(0.29)	0.96	37716.9	11130.00
19	44183.68	98.21	1.068	0.30(0.29)	0.96	41710.9	12330.00
20	43890.88	104.85	1.038	0.30(0.29)	0.97	45054.1	12400.00
21	43294.46	113.52	0.999	0.30(0.29)	0.97	48422.8	12201.00
22	42804.37	117.47	0.981	0.30(0.29)	0.97	49507.5	12111.00
23	42119.54	122.83	0.962	0.30(0.29)	0.97	50877.0	12101.10
24	41565.62	126.85	0.951	0.30(0.29)	0.97	51726.0	10400.00
25	39977.51	134.86	0.930	0.30(0.29)	0.97	53041.2	12010.00
26	38650.89	140.71	0.915	0.30(0.29)	0.97	53354.9	10210.00
27	38266.77	143.39	0.908	0.30(0.29)	0.97	53465.8	12000.00
28	35106.50	166.72	0.848	0.30(0.29)	0.97	54087.6	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115930.81 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	159.82	13.14	3.301	0.30 (0.28)	0.94	70.7	50400.00

LONGEST FLOWPATH FROM NODE 50400.00 TO NODE 12903.00 = 3607.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23259.82	13.14	3.301	0.30 (0.25)	0.82	3137.0	50400.00
2	25293.40	18.85	2.567	0.30 (0.25)	0.82	4467.8	50110.00
3	25939.94	20.44	2.416	0.30 (0.25)	0.82	4966.4	50320.00
4	26197.19	21.10	2.372	0.30 (0.25)	0.82	5165.6	50240.00
5	26576.16	22.10	2.306	0.30 (0.25)	0.82	5461.4	50330.00
6	27167.11	23.66	2.204	0.30 (0.25)	0.82	5909.1	420.00
7	27767.04	25.28	2.102	0.30 (0.25)	0.82	6465.9	50280.00
8	28185.63	26.46	2.049	0.30 (0.25)	0.82	6863.5	50300.00
9	28586.87	27.61	1.997	0.30 (0.25)	0.82	7240.7	50220.00
10	28590.70	27.62	1.997	0.30 (0.25)	0.82	7244.3	400.00
11	29545.45	30.82	1.868	0.30 (0.25)	0.84	8554.3	50260.00
12	30554.17	34.23	1.780	0.30 (0.26)	0.86	9921.7	50200.00
13	31176.12	36.30	1.727	0.30 (0.26)	0.87	10748.6	390.00
14	34370.51	51.89	1.391	0.30 (0.27)	0.92	16668.4	40100.00
15	36384.67	59.15	1.316	0.30 (0.28)	0.93	19472.5	11801.00
16	39135.29	68.64	1.249	0.30 (0.28)	0.94	23769.3	11530.00
17	41374.06	77.19	1.192	0.30 (0.28)	0.95	28775.0	11910.00
18	43414.18	84.28	1.144	0.30 (0.29)	0.96	33356.6	11330.00
19	44410.22	90.62	1.103	0.30 (0.29)	0.96	37787.6	11130.00
20	44225.34	98.21	1.068	0.30 (0.29)	0.96	41781.6	12330.00
21	43930.93	104.85	1.038	0.30 (0.29)	0.97	45124.8	12400.00
22	43332.42	113.52	0.999	0.30 (0.29)	0.97	48493.5	12201.00
23	42841.38	117.47	0.981	0.30 (0.29)	0.97	49578.2	12111.00
24	42155.54	122.83	0.962	0.30 (0.29)	0.97	50947.7	12101.10
25	41601.08	126.85	0.951	0.30 (0.29)	0.97	51796.7	10400.00
26	40011.86	134.86	0.930	0.30 (0.29)	0.97	53111.9	12010.00
27	38684.44	140.71	0.915	0.30 (0.29)	0.97	53425.6	10210.00
28	38299.94	143.39	0.908	0.30 (0.29)	0.97	53536.5	12000.00
29	35136.47	166.72	0.848	0.30 (0.29)	0.97	54158.3	10100.00

TOTAL AREA (ACRES) = 54158.3

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 44410.22 Tc (MIN.) = 90.623
EFFECTIVE AREA (ACRES) = 37787.61 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA (ACRES) = 54158.3
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115930.81 FEET.

FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

FLOW PROCESS FROM NODE 12903.00 TO NODE 12904.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 214.00 DOWNSTREAM (FEET) = 213.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 767.57 CHANNEL SLOPE = 0.0013
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 16.33
CHANNEL FLOW THRU SUBAREA (CFS) = 44410.22
FLOW VELOCITY (FEET/SEC.) = 9.66 FLOW DEPTH (FEET) = 16.33
TRAVEL TIME (MIN.) = 1.32 Tc (MIN.) = 91.95
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116698.38 FEET.

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 3B00EVRL.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	475.90	16.32	0.30 (0.13)	0.43	0.43	195.5	203.00
2	468.45	18.88	0.30 (0.13)	0.43	0.43	213.7	210.00

TOTAL AREA (ACRES) = 213.7

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23259.82	14.76	3.017	0.30 (0.25)	0.82	3137.0	50400.00
2	25293.40	20.42	2.417	0.30 (0.25)	0.82	4467.8	50110.00
3	25939.94	22.00	2.313	0.30 (0.25)	0.82	4966.4	50320.00
4	26197.19	22.66	2.270	0.30 (0.25)	0.82	5165.6	50240.00
5	26576.16	23.66	2.204	0.30 (0.25)	0.82	5461.4	50330.00
6	27167.11	25.20	2.106	0.30 (0.25)	0.82	5909.1	420.00
7	27767.04	26.81	2.033	0.30 (0.25)	0.82	6465.9	50280.00
8	28185.63	27.98	1.980	0.30 (0.25)	0.82	6863.5	50300.00
9	28586.87	29.12	1.929	0.30 (0.25)	0.82	7240.7	50220.00
10	28590.70	29.13	1.928	0.30 (0.25)	0.82	7244.3	400.00
11	29545.45	32.32	1.829	0.30 (0.25)	0.84	8554.3	50260.00
12	30554.17	35.71	1.742	0.30 (0.26)	0.86	9921.7	50200.00
13	31176.12	37.78	1.689	0.30 (0.26)	0.87	10748.6	390.00
14	34370.51	53.32	1.376	0.30 (0.27)	0.92	16668.4	40100.00
15	36384.67	60.55	1.303	0.30 (0.28)	0.93	19472.5	11801.00
16	39135.29	70.01	1.240	0.30 (0.28)	0.94	23769.3	11530.00
17	41374.06	78.54	1.183	0.30 (0.28)	0.95	28775.0	11910.00
18	43414.18	85.61	1.135	0.30 (0.29)	0.96	33356.6	11330.00
19	44410.22	91.95	1.097	0.30 (0.29)	0.96	37787.6	11130.00
20	44225.34	99.54	1.062	0.30 (0.29)	0.96	41781.6	12330.00
21	43930.93	106.18	1.032	0.30 (0.29)	0.97	45124.8	12400.00
22	43332.42	114.85	0.993	0.30 (0.29)	0.97	48493.5	12201.00
23	42841.38	118.81	0.974	0.30 (0.29)	0.97	49578.2	12111.00

24	42155.54	124.18	0.958	0.30	(0.29)	0.97	50947.7	12101.10
25	41601.08	128.20	0.948	0.30	(0.29)	0.97	51796.7	10400.00
26	40011.86	136.22	0.927	0.30	(0.29)	0.97	53111.9	12010.00
27	38684.44	142.09	0.912	0.30	(0.29)	0.97	53425.6	10210.00
28	38299.94	144.77	0.905	0.30	(0.29)	0.97	53536.5	12000.00
29	35136.47	168.14	0.844	0.30	(0.29)	0.97	54158.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116698.38 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	475.90	16.32	2.835	0.30 (0.13)	0.43	195.5	203.00
2	468.45	18.88	2.564	0.30 (0.13)	0.43	213.7	210.00

LONGEST FLOWPATH FROM NODE 210.00 TO NODE 12904.00 = 7986.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23719.21	14.76	3.017	0.30 (0.24)	0.80	3313.8	50400.00
2	24295.70	16.32	2.835	0.30 (0.24)	0.80	3699.0	203.00
3	25208.16	18.88	2.564	0.30 (0.24)	0.80	4319.2	210.00
4	25733.67	20.42	2.417	0.30 (0.24)	0.80	4681.5	50110.00
5	26360.19	22.00	2.313	0.30 (0.24)	0.80	5180.1	50320.00
6	26609.08	22.66	2.270	0.30 (0.24)	0.80	5379.3	50240.00
7	26975.38	23.66	2.204	0.30 (0.24)	0.80	5675.1	50330.00
8	27547.57	25.20	2.106	0.30 (0.24)	0.81	6122.8	420.00
9	28133.47	26.81	2.033	0.30 (0.24)	0.81	6679.6	50280.00
10	28541.86	27.98	1.980	0.30 (0.24)	0.81	7077.2	50300.00
11	28933.21	29.12	1.929	0.30 (0.24)	0.81	7454.4	50220.00
12	28936.93	29.13	1.928	0.30 (0.24)	0.81	7458.0	400.00
13	29872.69	32.32	1.829	0.30 (0.25)	0.83	8768.0	50260.00
14	30864.63	35.71	1.742	0.30 (0.26)	0.85	10135.4	50200.00
15	31476.36	37.78	1.689	0.30 (0.26)	0.87	10962.3	390.00
16	34610.64	53.32	1.376	0.30 (0.27)	0.91	16882.1	40100.00
17	36610.73	60.55	1.303	0.30 (0.28)	0.92	19686.2	11801.00
18	39349.16	70.01	1.240	0.30 (0.28)	0.93	23983.0	11530.00
19	41576.93	78.54	1.183	0.30 (0.28)	0.95	28988.7	11910.00
20	43607.94	85.61	1.135	0.30 (0.29)	0.95	33570.3	11330.00
21	44596.62	91.95	1.097	0.30 (0.29)	0.96	38001.3	11130.00
22	44405.07	99.54	1.062	0.30 (0.29)	0.96	41995.3	12330.00
23	44104.83	106.18	1.032	0.30 (0.29)	0.96	45338.5	12400.00
24	43498.70	114.85	0.993	0.30 (0.29)	0.96	48707.2	12201.00
25	43004.18	118.81	0.974	0.30 (0.29)	0.96	49791.9	12111.00
26	42315.21	124.18	0.958	0.30 (0.29)	0.96	51161.4	12101.10
27	41758.73	128.20	0.948	0.30 (0.29)	0.97	52010.4	10400.00
28	40165.51	136.22	0.927	0.30 (0.29)	0.97	53325.6	12010.00
29	38835.15	142.09	0.912	0.30 (0.29)	0.97	53639.3	10210.00
30	38449.31	144.77	0.905	0.30 (0.29)	0.97	53750.2	12000.00
31	35274.16	168.14	0.844	0.30 (0.29)	0.97	54372.0	10100.00

TOTAL AREA (ACRES) = 54372.0

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 44596.62 Tc (MIN.) = 91.948
EFFECTIVE AREA (ACRES) = 38001.31 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
TOTAL AREA (ACRES) = 54372.0
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116698.38 FEET.

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====

MAINLINE Tc (MIN.) = 91.95 S29.2-4

* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.097

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL					
" .4 DWELLING/ACRE"	B	0.10	0.30	0.900	56
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.20	0.30	1.000	65
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.80	0.30	1.000	65
COMMERCIAL	B	1.20	0.30	0.100	56
COMMERCIAL	B	1.50	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	3.00	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.641
SUBAREA AREA (ACRES) = 6.80 SUBAREA RUNOFF (CFS) = 5.54
EFFECTIVE AREA (ACRES) = 38008.11 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA (ACRES) = 54378.8 PEAK FLOW RATE (CFS) = 44596.62
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====

MAINLINE Tc (MIN.) = 91.95 S29.2-4

* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.097

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	3.60	0.30	1.000	69
PUBLIC PARK	B	15.10	0.30	0.850	56
NATURAL FAIR COVER					
"GRASS"	B	20.00	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.941
SUBAREA AREA (ACRES) = 38.70 SUBAREA RUNOFF (CFS) = 28.37
EFFECTIVE AREA (ACRES) = 38046.81 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA (ACRES) = 54417.5 PEAK FLOW RATE (CFS) = 44596.62
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 54417.5 TC (MIN.) = 91.95
EFFECTIVE AREA (ACRES) = 38046.81 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.957
PEAK FLOW RATE (CFS) = 44596.62

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23719.21	14.76	3.017	0.30(0.24)	0.80	3359.3	50400.00
2	24295.70	16.32	2.835	0.30(0.24)	0.80	3744.5	203.00
3	25208.16	18.88	2.564	0.30(0.24)	0.80	4364.7	210.00
4	25733.67	20.42	2.417	0.30(0.24)	0.80	4727.0	50110.00
5	26360.19	22.00	2.313	0.30(0.24)	0.80	5225.6	50320.00
6	26609.08	22.66	2.270	0.30(0.24)	0.80	5424.8	50240.00
7	26975.38	23.66	2.204	0.30(0.24)	0.80	5720.6	50330.00
8	27547.57	25.20	2.106	0.30(0.24)	0.81	6168.3	420.00
9	28133.47	26.81	2.033	0.30(0.24)	0.81	6725.1	50280.00
10	28541.86	27.98	1.980	0.30(0.24)	0.81	7122.7	50300.00
11	28933.21	29.12	1.929	0.30(0.24)	0.81	7499.9	50220.00
12	28936.93	29.13	1.928	0.30(0.24)	0.81	7503.5	400.00
13	29872.69	32.32	1.829	0.30(0.25)	0.83	8813.5	50260.00
14	30864.63	35.71	1.742	0.30(0.26)	0.85	10180.9	50200.00
15	31476.36	37.78	1.689	0.30(0.26)	0.87	11007.8	390.00
16	34610.64	53.32	1.376	0.30(0.27)	0.91	16927.6	40100.00
17	36610.73	60.55	1.303	0.30(0.28)	0.92	19731.7	11801.00
18	39349.16	70.01	1.240	0.30(0.28)	0.93	24028.5	11530.00
19	41576.93	78.54	1.183	0.30(0.28)	0.95	29034.2	11910.00
20	43607.94	85.61	1.135	0.30(0.29)	0.95	33615.8	11330.00
21	44596.62	91.95	1.097	0.30(0.29)	0.96	38046.8	11130.00
22	44405.07	99.54	1.062	0.30(0.29)	0.96	42040.8	12330.00
23	44104.83	106.18	1.032	0.30(0.29)	0.96	45384.0	12400.00
24	43498.70	114.85	0.993	0.30(0.29)	0.96	48752.7	12201.00
25	43004.18	118.81	0.974	0.30(0.29)	0.96	49837.4	12111.00
26	42315.21	124.18	0.958	0.30(0.29)	0.96	51206.9	12101.10
27	41758.73	128.20	0.948	0.30(0.29)	0.97	52055.9	10400.00
28	40165.51	136.22	0.927	0.30(0.29)	0.97	53371.1	12010.00
29	38835.15	142.09	0.912	0.30(0.29)	0.97	53684.8	10210.00
30	38449.31	144.77	0.905	0.30(0.29)	0.97	53795.7	12000.00
31	35274.16	168.14	0.844	0.30(0.29)	0.97	54417.5	10100.00

=====
 END OF RATIONAL METHOD ANALYSIS
 =====

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 133C FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 100-YR EV FEB 2023 ROKAMOTO *

FILE NAME: RU00EV33.DAT
TIME/DATE OF STUDY: 14:35 02/07/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 100.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.875
- 2) 10.00; 3.789
- 3) 15.00; 2.933
- 4) 20.00; 2.419
- 5) 25.00; 2.096
- 6) 30.00; 1.872
- 7) 40.00; 1.617
- 8) 50.00; 1.400
- 9) 60.00; 1.290
- 10) 90.00; 1.088
- 11) 120.00; 0.951
- 12) 180.00; 0.795
- 13) 360.00; 0.588
- 14) 1200.00; 0.256

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL: IN- / OUT-/PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13112.00 TO NODE 13222.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: S31X00.DNA S31
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3200.10	33.81	0.30 (0.24)	0.81	2538.8	13100.00
2	3223.67	57.47	0.30 (0.24)	0.81	3777.0	13000.00
3	3120.61	59.66	0.30 (0.24)	0.81	3796.8	13010.00
TOTAL AREA (ACRES) =						3796.8

FLOW PROCESS FROM NODE 13221.00 TO NODE 13222.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: S32X00.DNA S32
MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1444.32	32.09	0.30 (0.25)	0.83	1115.4	13210.00
2	1446.69	32.62	0.30 (0.25)	0.83	1127.6	13200.00
TOTAL AREA (ACRES) =						1127.6

FLOW PROCESS FROM NODE 13221.00 TO NODE 13222.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1444.32	32.09	0.30 (0.25)	0.83	1115.4	13210.00
2	1446.69	32.62	0.30 (0.25)	0.83	1127.6	13200.00
TOTAL AREA (ACRES) =						1127.6

FLOW PROCESS FROM NODE 13112.00 TO NODE 13222.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

=====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1444.32	32.09	1.819	0.30 (0.25)	0.83	1115.4	13210.00
2	1446.69	32.62	1.805	0.30 (0.25)	0.83	1127.6	13200.00
LONGEST FLOWPATH FROM NODE 13200.00 TO NODE 13222.00 =							16821.05 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3200.10	33.81	1.775	0.30 (0.24)	0.81	2538.8	13100.00
2	3223.67	57.47	1.318	0.30 (0.24)	0.81	3777.0	13000.00
3	3120.61	59.66	1.294	0.30 (0.24)	0.81	3796.8	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13222.00 = 32126.49 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4568.37	32.09	1.819	0.30 (0.24)	0.82	3524.7	13210.00
2	4595.02	32.62	1.805	0.30 (0.24)	0.82	3576.6	13200.00
3	4618.44	33.81	1.775	0.30 (0.24)	0.82	3666.4	13100.00
4	4217.51	57.47	1.318	0.30 (0.24)	0.81	4904.6	13000.00
5	4092.02	59.66	1.294	0.30 (0.24)	0.81	4924.4	13010.00

TOTAL AREA (ACRES) = 4924.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 4618.44 Tc(MIN.) = 33.814
EFFECTIVE AREA(ACRES) = 3666.43 AREA-AVERAGED Fm(INCH/HR) = 0.24
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82
TOTAL AREA (ACRES) = 4924.4
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13222.00 = 32126.49 FEET.

FLOW PROCESS FROM NODE 13222.00 TO NODE 13222.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 13222.00 TO NODE 13222.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

FLOW PROCESS FROM NODE 13222.00 TO NODE 13301.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 427.51 DOWNSTREAM(FEET) = 382.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 2533.33 CHANNEL SLOPE = 0.0180
GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 5.38
* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.692

S33-01

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	1.40	0.30	0.100	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	15.60	0.30	1.000	66
RESIDENTIAL					
"3-4 DWELLINGS/ACRE"	B	0.10	0.30	0.600	56
AGRICULTURAL POOR COVER					

"ROW CROPS, CONTOURED"	B	5.30	0.30	1.000	79
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86
COMMERCIAL	B	22.60	0.30	0.100	56

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.521
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 4649.68
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 13.04
AVERAGE FLOW DEPTH(FEET) = 5.39 TRAVEL TIME(MIN.) = 3.24
Tc(MIN.) = 37.05
SUBAREA AREA(ACRES) = 45.20 SUBAREA RUNOFF(CFS) = 62.48
EFFECTIVE AREA(ACRES) = 3711.63 AREA-AVERAGED Fm(INCH/HR) = 0.24
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81
TOTAL AREA(ACRES) = 4969.6 PEAK FLOW RATE(CFS) = 4839.42
GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 5.51

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 5.51 FLOW VELOCITY(FEET/SEC.) = 13.21
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 37.05
* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.692 S33-01

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	1.00	0.30	1.000	79
NATURAL POOR COVER					
"BARREN"	B	0.50	0.30	1.000	86
COMMERCIAL	B	7.40	0.30	0.100	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	4.70	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	2.90	0.30	1.000	65

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.596
SUBAREA AREA(ACRES) = 16.50 SUBAREA RUNOFF(CFS) = 22.47
EFFECTIVE AREA(ACRES) = 3728.13 AREA-AVERAGED Fm(INCH/HR) = 0.24
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81
TOTAL AREA(ACRES) = 4986.1 PEAK FLOW RATE(CFS) = 4861.90

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 37.05
* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.692
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					

HZ-31111

NATURAL POOR COVER
"BARREN" B 1.30 0.30 1.000 86
COMMERCIAL B 0.20 0.30 0.100 56
AGRICULTURAL POOR COVER
"ROW CROPS,CONTOURED" B 5.30 0.30 1.000 79
NATURAL FAIR COVER
"WOODLAND,GRASS" B 0.30 0.30 1.000 65
NATURAL FAIR COVER
"CHAPARRAL,BROADLEAF" B 0.20 0.30 1.000 63
NATURAL FAIR COVER
"OPEN BRUSH" B 0.60 0.30 1.000 66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.977
SUBAREA AREA (ACRES) = 7.90 SUBAREA RUNOFF(CFS) = 9.95
EFFECTIVE AREA(ACRES) = 3736.03 AREA-AVERAGED Fm(INCH/HR) = 0.24
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81
TOTAL AREA (ACRES) = 4994.0 PEAK FLOW RATE(CFS) = 4871.84

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 37.05 HZ-31111

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.692

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include AGRICULTURAL POOR COVER, "ROW CROPS,CONTOURED", NATURAL FAIR COVER, "WOODLAND,GRASS", "CHAPARRAL,BROADLEAF", "OPEN BRUSH", AGRICULTURAL POOR COVER, "ROW CROPS,CONTOURED", NATURAL FAIR COVER, "WOODLAND,GRASS".

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 22.00 SUBAREA RUNOFF(CFS) = 27.57
EFFECTIVE AREA(ACRES) = 3758.03 AREA-AVERAGED Fm(INCH/HR) = 0.24
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81
TOTAL AREA (ACRES) = 5016.0 PEAK FLOW RATE(CFS) = 4899.41

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 37.05 HZ-31111

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.692

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Row includes NATURAL FAIR COVER, "CHAPARRAL,BROADLEAF".

"OPEN BRUSH" B 0.40 0.30 1.000 66
AGRICULTURAL POOR COVER
"ROW CROPS,CONTOURED" B 14.60 0.30 1.000 79
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 15.00 SUBAREA RUNOFF(CFS) = 18.79
EFFECTIVE AREA(ACRES) = 3773.03 AREA-AVERAGED Fm(INCH/HR) = 0.24
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81
TOTAL AREA (ACRES) = 5031.0 PEAK FLOW RATE(CFS) = 4918.20

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1<<<<

FLOW PROCESS FROM NODE 31100.00 TO NODE 31101.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH(FEET) = 317.00
ELEVATION DATA: UPSTREAM(FEET) = 801.00 DOWNSTREAM(FEET) = 685.00

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20 HZ-31111
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 8.641

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 4.356

SUBAREA Tc AND LOSS RATE DATA(AMC II):

Table with 7 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN, Tc (MIN.). Rows include NATURAL FAIR COVER, "CHAPARRAL,BROADLEAF", "OPEN BRUSH", NATURAL FAIR COVER, "OPEN BRUSH".

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 4.02
TOTAL AREA (ACRES) = 1.10 PEAK FLOW RATE(CFS) = 4.02

FLOW PROCESS FROM NODE 31101.00 TO NODE 31102.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 685.00 DOWNSTREAM(FEET) = 655.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 135.00 CHANNEL SLOPE = 0.2222
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 4.224

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Row includes NATURAL FAIR COVER, "CHAPARRAL,BROADLEAF".

HZ-31101

NATURAL FAIR COVER
 "OPEN BRUSH" B 0.10 0.30 1.000 66
 NATURAL FAIR COVER
 "OPEN BRUSH" B 0.70 0.30 1.000 66
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 6.31
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.09
 AVERAGE FLOW DEPTH(FEET) = 0.54 TRAVEL TIME(MIN.) = 0.32
 Tc(MIN.) = 8.96
 SUBAREA AREA(ACRES) = 1.30 SUBAREA RUNOFF(CFS) = 4.59
 EFFECTIVE AREA(ACRES) = 2.40 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 2.4 PEAK FLOW RATE(CFS) = 8.48

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 0.61 FLOW VELOCITY(FEET/SEC.) = 7.66
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31102.00 = 452.00 FEET.

 FLOW PROCESS FROM NODE 31102.00 TO NODE 31103.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 655.00 DOWNSTREAM(FEET) = 630.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 203.00 CHANNEL SLOPE = 0.1232
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 10.00
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 4.054

HZ-31102

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.30	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.10	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.90	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 12.36
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.30
 AVERAGE FLOW DEPTH(FEET) = 0.70 TRAVEL TIME(MIN.) = 0.41
 Tc(MIN.) = 9.37
 SUBAREA AREA(ACRES) = 2.30 SUBAREA RUNOFF(CFS) = 7.77
 EFFECTIVE AREA(ACRES) = 4.70 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 4.7 PEAK FLOW RATE(CFS) = 15.88

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 0.77 FLOW VELOCITY(FEET/SEC.) = 8.85
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31103.00 = 655.00 FEET.

 FLOW PROCESS FROM NODE 31103.00 TO NODE 31104.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 630.00 DOWNSTREAM(FEET) = 605.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 321.00 CHANNEL SLOPE = 0.0779
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.757

HZ-31104

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.10	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.50	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 21.48
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.52
 AVERAGE FLOW DEPTH(FEET) = 1.05 TRAVEL TIME(MIN.) = 0.82
 Tc(MIN.) = 10.19
 SUBAREA AREA(ACRES) = 3.60 SUBAREA RUNOFF(CFS) = 11.20
 EFFECTIVE AREA(ACRES) = 8.30 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 8.3 PEAK FLOW RATE(CFS) = 25.82

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 1.12 FLOW VELOCITY(FEET/SEC.) = 6.81
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31104.00 = 976.00 FEET.

 FLOW PROCESS FROM NODE 31104.00 TO NODE 31105.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 605.00 DOWNSTREAM(FEET) = 585.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 288.00 CHANNEL SLOPE = 0.0694
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.641

HZ-31105

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.70	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.60	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	3.00	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.10	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 35.45
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.08
 AVERAGE FLOW DEPTH(FEET) = 1.29 TRAVEL TIME(MIN.) = 0.68
 Tc(MIN.) = 10.86
 SUBAREA AREA(ACRES) = 6.40 SUBAREA RUNOFF(CFS) = 19.24

EFFECTIVE AREA(ACRES) = 14.70 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 14.7 PEAK FLOW RATE(CFS) = 44.20

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.41 FLOW VELOCITY(FEET/SEC.) = 7.45
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31105.00 = 1264.00 FEET.

FLOW PROCESS FROM NODE 31105.00 TO NODE 31106.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 585.00 DOWNSTREAM(FEET) = 560.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 344.00 CHANNEL SLOPE = 0.0727
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.521 **HZ-31105**
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.60	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	2.80	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.60	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.10	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.60	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	4.10	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 59.86
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.19
AVERAGE FLOW DEPTH(FEET) = 1.56 TRAVEL TIME(MIN.) = 0.70
Tc(MIN.) = 11.57
SUBAREA AREA(ACRES) = 10.80 SUBAREA RUNOFF(CFS) = 31.31
EFFECTIVE AREA(ACRES) = 25.50 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 25.5 PEAK FLOW RATE(CFS) = 73.92

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.69 FLOW VELOCITY(FEET/SEC.) = 8.64
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31106.00 = 1608.00 FEET.

FLOW PROCESS FROM NODE 31106.00 TO NODE 31107.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 560.00 DOWNSTREAM(FEET) = 530.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 619.00 CHANNEL SLOPE = 0.0485
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.297 **HZ-31106**
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.80	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	1.90	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.50	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	8.20	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.70	0.30	1.000	66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000					
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 94.29					
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.89					
AVERAGE FLOW DEPTH(FEET) = 2.00 TRAVEL TIME(MIN.) = 1.31					
Tc(MIN.) = 12.87					
SUBAREA AREA(ACRES) = 15.10 SUBAREA RUNOFF(CFS) = 40.73					
EFFECTIVE AREA(ACRES) = 40.60 AREA-AVERAGED Fm(INCH/HR) = 0.30					
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00					
TOTAL AREA(ACRES) = 40.6 PEAK FLOW RATE(CFS) = 109.52					

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 2.11 FLOW VELOCITY(FEET/SEC.) = 8.20
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31107.00 = 2227.00 FEET.

FLOW PROCESS FROM NODE 31107.00 TO NODE 31108.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 530.00 DOWNSTREAM(FEET) = 515.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 377.00 CHANNEL SLOPE = 0.0398
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.163 **HZ-31107**
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.50	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	6.50	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	1.30	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.10	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	5.50	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	3.40	0.30	1.000	66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000					

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 133.09
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.00
AVERAGE FLOW DEPTH(FEET) = 2.35 TRAVEL TIME(MIN.) = 0.79
Tc(MIN.) = 13.66
SUBAREA AREA(ACRES) = 18.30 SUBAREA RUNOFF(CFS) = 47.15
EFFECTIVE AREA(ACRES) = 58.90 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 58.9 PEAK FLOW RATE(CFS) = 151.75

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 2.48 FLOW VELOCITY(FEET/SEC.) = 8.25
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31108.00 = 2604.00 FEET.

FLOW PROCESS FROM NODE 31108.00 TO NODE 31109.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 515.00 DOWNSTREAM(FEET) = 490.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 520.00 CHANNEL SLOPE = 0.0481
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.000

HZ-31108

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"CHAPARRAL,BROADLEAF" B 0.70 0.30 1.000 63
NATURAL FAIR COVER
"GRASS" B 2.20 0.30 1.000 69
NATURAL FAIR COVER
"OPEN BRUSH" B 3.10 0.30 1.000 66
NATURAL FAIR COVER
"WOODLAND,GRASS" B 0.90 0.30 1.000 65
NATURAL FAIR COVER
"CHAPARRAL,BROADLEAF" B 7.40 0.30 1.000 63
NATURAL FAIR COVER
"GRASS" B 0.30 0.30 1.000 69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 169.49
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.10
AVERAGE FLOW DEPTH(FEET) = 2.49 TRAVEL TIME(MIN.) = 0.95
Tc(MIN.) = 14.61
SUBAREA AREA(ACRES) = 14.60 SUBAREA RUNOFF(CFS) = 35.47
EFFECTIVE AREA(ACRES) = 73.50 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 73.5 PEAK FLOW RATE(CFS) = 178.58

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 2.54 FLOW VELOCITY(FEET/SEC.) = 9.24
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31109.00 = 3124.00 FEET.

FLOW PROCESS FROM NODE 31109.00 TO NODE 31109.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 14.61
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.000 HZ-31108

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

NATURAL FAIR COVER
"OPEN BRUSH" B 11.40 0.30 1.000 66
NATURAL FAIR COVER
"WOODLAND,GRASS" B 8.90 0.30 1.000 65
NATURAL FAIR COVER
"CHAPARRAL,BROADLEAF" B 1.90 0.30 1.000 63
NATURAL FAIR COVER
"OPEN BRUSH" B 9.20 0.30 1.000 66
NATURAL FAIR COVER
"WOODLAND,GRASS" B 1.40 0.30 1.000 65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 32.80 SUBAREA RUNOFF(CFS) = 79.69
EFFECTIVE AREA(ACRES) = 106.30 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 106.3 PEAK FLOW RATE(CFS) = 258.27

FLOW PROCESS FROM NODE 31109.00 TO NODE 31110.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 490.00 DOWNSTREAM(FEET) = 432.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1420.00 CHANNEL SLOPE = 0.0408
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.720

HZ-31109

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"GRASS" B 0.80 0.30 1.000 69
NATURAL FAIR COVER
"OPEN BRUSH" B 0.60 0.30 1.000 66
RESIDENTIAL
".4 DWELLING/ACRE" B 0.10 0.30 0.900 56
AGRICULTURAL POOR COVER
"ROW CROPS,CONTOURED" B 1.30 0.30 1.000 79
NATURAL FAIR COVER
"WOODLAND,GRASS" B 4.00 0.30 1.000 65
NATURAL FAIR COVER
"CHAPARRAL,BROADLEAF" B 1.50 0.30 1.000 63

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 267.31
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.60
AVERAGE FLOW DEPTH(FEET) = 3.05 TRAVEL TIME(MIN.) = 2.47
Tc(MIN.) = 17.08
SUBAREA AREA(ACRES) = 8.30 SUBAREA RUNOFF(CFS) = 18.08
EFFECTIVE AREA(ACRES) = 114.60 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA (ACRES) = 114.6 PEAK FLOW RATE (CFS) = 258.27
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 3.01 FLOW VELOCITY (FEET/SEC.) = 9.51
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31110.00 = 4544.00 FEET.

FLOW PROCESS FROM NODE 31110.00 TO NODE 31110.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 17.08 **HZ-31109**
* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.720

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	0.30	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	9.60	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.40	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	6.20	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	3.90	0.30	1.000	65
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	1.40	0.30	1.000	79

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.998
SUBAREA AREA (ACRES) = 21.80 SUBAREA RUNOFF (CFS) = 47.48
EFFECTIVE AREA (ACRES) = 136.40 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 136.4 PEAK FLOW RATE (CFS) = 297.03

FLOW PROCESS FROM NODE 31110.00 TO NODE 13301.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM (FEET) = 432.00 DOWNSTREAM (FEET) = 382.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 1847.00 CHANNEL SLOPE = 0.0271
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 10.00 **HZ-31110**
* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.375

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	4.90	0.30	1.000	86
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	1.50	0.30	1.000	79
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.60	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	2.50	0.30	1.000	79

AGRICULTURAL POOR COVER
"ROW CROPS, CONTOURED" B 5.30 0.30 1.000 79
AGRICULTURAL POOR COVER
"ROW CROPS, CONTOURED" B 3.30 0.30 1.000 79
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.997
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 313.95
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.56
AVERAGE FLOW DEPTH (FEET) = 3.50 TRAVEL TIME (MIN.) = 3.60
Tc (MIN.) = 20.67

SUBAREA AREA (ACRES) = 18.10 SUBAREA RUNOFF (CFS) = 33.83
EFFECTIVE AREA (ACRES) = 154.50 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 154.5 PEAK FLOW RATE (CFS) = 297.03
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 3.42 FLOW VELOCITY (FEET/SEC.) = 8.45
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 13301.00 = 6391.00 FEET.

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	297.03	20.67	2.375	0.30 (0.30)	1.00	154.5	31100.00

LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 13301.00 = 6391.00 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4876.06	35.34	1.736	0.30 (0.24)	0.81	3631.3	13210.00
2	4901.77	35.86	1.723	0.30 (0.24)	0.81	3683.2	13200.00
3	4918.20	37.05	1.692	0.30 (0.24)	0.81	3773.0	13100.00
4	4697.25	60.80	1.285	0.30 (0.24)	0.81	5011.2	13000.00
5	4648.21	63.02	1.270	0.30 (0.24)	0.81	5031.0	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4372.56	20.67	2.375	0.30 (0.25)	0.83	2278.9	31100.00
2	5081.57	35.34	1.736	0.30 (0.25)	0.82	3785.8	13210.00
3	5105.38	35.86	1.723	0.30 (0.25)	0.82	3837.7	13200.00
4	5117.46	37.05	1.692	0.30 (0.25)	0.82	3927.5	13100.00
5	4838.18	60.80	1.285	0.30 (0.24)	0.82	5165.7	13000.00
6	4787.00	63.02	1.270	0.30 (0.24)	0.82	5185.5	13010.00

TOTAL AREA (ACRES) = 5185.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
PEAK FLOW RATE (CFS) = 5117.46 Tc (MIN.) = 37.052
EFFECTIVE AREA (ACRES) = 3927.53 AREA-AVERAGED Fm (INCH/HR) = 0.25
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82
TOTAL AREA (ACRES) = 5185.5

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 13301.00 TO NODE 13302.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 382.00 DOWNSTREAM(FEET) = 375.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 1141.09 CHANNEL SLOPE = 0.0061

GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 7.62

S33-02

* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.640

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL POOR COVER

"BARREN" B 1.20 0.30 1.000 86

AGRICULTURAL POOR COVER

"ROW CROPS, STRAIGHT ROW" B 0.60 0.30 1.000 81

NATURAL POOR COVER

"BARREN" B 0.90 0.30 1.000 86

NATURAL FAIR COVER

"OPEN BRUSH" B 4.80 0.30 1.000 66

AGRICULTURAL POOR COVER

"ROW CROPS, STRAIGHT ROW" B 1.90 0.30 1.000 81

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 5123.13

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 9.23

AVERAGE FLOW DEPTH (FEET) = 7.62 TRAVEL TIME (MIN.) = 2.06

Tc (MIN.) = 39.11

SUBAREA AREA (ACRES) = 9.40 SUBAREA RUNOFF (CFS) = 11.33

EFFECTIVE AREA (ACRES) = 3936.93 AREA-AVERAGED Fm (INCH/HR) = 0.25

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82

TOTAL AREA (ACRES) = 5194.9 PEAK FLOW RATE (CFS) = 5117.46

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE (FEET) = 50.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT (FEET) = 7.61

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 7.61 FLOW VELOCITY (FEET/SEC.) = 9.23

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13302.00 = 35800.91 FEET.

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 39.11

* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.640

HZ-31112

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL POOR COVER

"BARREN" B 13.80 0.30 1.000 86

NATURAL POOR COVER

"BARREN" B 2.60 0.30 1.000 86

COMMERCIAL

B 1.10 0.30 0.100 56

RESIDENTIAL

".4 DWELLING/ACRE" B 3.50 0.30 0.900 56

AGRICULTURAL POOR COVER

"ROW CROPS, CONTOURED" B 6.90 0.30 1.000 79

NATURAL POOR COVER

"BARREN" B 0.20 0.30 1.000 86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.952

SUBAREA AREA (ACRES) = 28.10 SUBAREA RUNOFF (CFS) = 34.24

EFFECTIVE AREA (ACRES) = 3965.03 AREA-AVERAGED Fm (INCH/HR) = 0.25

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82

TOTAL AREA (ACRES) = 5223.0 PEAK FLOW RATE (CFS) = 5117.46

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 39.11

HZ-31112

* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.640

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

AGRICULTURAL POOR COVER

"ROW CROPS, CONTOURED" B 0.10 0.30 1.000 79

COMMERCIAL

B 0.10 0.30 0.100 56

RESIDENTIAL

".4 DWELLING/ACRE" B 2.40 0.30 0.900 56

AGRICULTURAL POOR COVER

"ROW CROPS, CONTOURED" B 0.50 0.30 1.000 79

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.894

SUBAREA AREA (ACRES) = 3.10 SUBAREA RUNOFF (CFS) = 3.83

EFFECTIVE AREA (ACRES) = 3968.13 AREA-AVERAGED Fm (INCH/HR) = 0.25

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82

TOTAL AREA (ACRES) = 5226.1 PEAK FLOW RATE (CFS) = 5117.46

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 39.11

* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.640

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

HZ-206

NATURAL POOR COVER
"BARREN" B 0.10 0.30 1.000 86
NATURAL FAIR COVER
"OPEN BRUSH" B 2.60 0.30 1.000 66
AGRICULTURAL POOR COVER
"ROW CROPS, CONTOURED" B 3.10 0.30 1.000 79
NATURAL FAIR COVER
"WOODLAND, GRASS" B 0.40 0.30 1.000 65
NATURAL FAIR COVER
"CHAPARRAL, BROADLEAF" B 0.20 0.30 1.000 63
NATURAL FAIR COVER
"OPEN BRUSH" B 13.80 0.30 1.000 66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 20.20 SUBAREA RUNOFF (CFS) = 24.35
EFFECTIVE AREA (ACRES) = 3988.33 AREA-AVERAGED Fm (INCH/HR) = 0.25
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82
TOTAL AREA (ACRES) = 5246.3 PEAK FLOW RATE (CFS) = 5117.46
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 39.11
* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.640 HZ-206

SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
AGRICULTURAL POOR COVER
"ROW CROPS, CONTOURED" B 34.60 0.30 1.000 79
NATURAL FAIR COVER
"WOODLAND, GRASS" B 2.40 0.30 1.000 65
NATURAL FAIR COVER
"OPEN BRUSH" B 22.60 0.30 1.000 66
AGRICULTURAL POOR COVER
"ROW CROPS, CONTOURED" B 11.60 0.30 1.000 79
APARTMENTS B 0.40 0.30 0.200 56
NATURAL FAIR COVER
"CHAPARRAL, BROADLEAF" B 4.80 0.30 1.000 63
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.996
SUBAREA AREA (ACRES) = 76.40 SUBAREA RUNOFF (CFS) = 92.20
EFFECTIVE AREA (ACRES) = 4064.73 AREA-AVERAGED Fm (INCH/HR) = 0.25
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
TOTAL AREA (ACRES) = 5322.7 PEAK FLOW RATE (CFS) = 5117.46
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 39.11
* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.640
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS

HZ-206

LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"GRASS" B 1.60 0.30 1.000 69
NATURAL FAIR COVER
"OPEN BRUSH" B 46.40 0.30 1.000 66
RESIDENTIAL
"11+ DWELLINGS/ACRE" B 0.10 0.30 0.200 56
AGRICULTURAL POOR COVER
"ROW CROPS, CONTOURED" B 60.70 0.30 1.000 79
NATURAL FAIR COVER
"WOODLAND, GRASS" B 5.80 0.30 1.000 65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999
SUBAREA AREA (ACRES) = 114.60 SUBAREA RUNOFF (CFS) = 138.19
EFFECTIVE AREA (ACRES) = 4179.33 AREA-AVERAGED Fm (INCH/HR) = 0.25
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
TOTAL AREA (ACRES) = 5437.3 PEAK FLOW RATE (CFS) = 5230.29

FLOW PROCESS FROM NODE 13302.00 TO NODE 13303.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 375.00 DOWNSTREAM (FEET) = 355.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 2193.96 CHANNEL SLOPE = 0.0091
GIVEN CHANNEL BASE (FEET) = 50.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT (FEET) = 6.92
CHANNEL FLOW THRU SUBAREA (CFS) = 5230.29
FLOW VELOCITY (FEET/SEC.) = 10.68 FLOW DEPTH (FEET) = 6.92
TRAVEL TIME (MIN.) = 3.43 Tc (MIN.) = 42.54
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13303.00 = 37994.87 FEET.

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 42.54 HZ-207

* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.562
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL POOR COVER
"BARREN" B 0.20 0.30 1.000 86
NATURAL FAIR COVER
"WOODLAND, GRASS" B 0.40 0.30 1.000 65
NATURAL POOR COVER
"BARREN" B 0.80 0.30 1.000 86
COMMERCIAL B 1.40 0.30 0.100 56
NATURAL FAIR COVER
"GRASS" B 2.60 0.30 1.000 69
NATURAL FAIR COVER
"OPEN BRUSH" B 2.20 0.30 1.000 66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.834
SUBAREA AREA (ACRES) = 7.60 SUBAREA RUNOFF (CFS) = 8.97

EFFECTIVE AREA(ACRES) = 4186.93 AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
TOTAL AREA(ACRES) = 5444.9 PEAK FLOW RATE(CFS) = 5230.29
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 42.54
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.562 **HZ-207**

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

AGRICULTURAL POOR COVER					
-------------------------	--	--	--	--	--

"ROW CROPS,CONTOURED"	B	3.10	0.30	1.000	79
-----------------------	---	------	------	-------	----

NATURAL FAIR COVER					
--------------------	--	--	--	--	--

"WOODLAND,GRASS"	B	3.40	0.30	1.000	65
------------------	---	------	------	-------	----

NATURAL POOR COVER					
--------------------	--	--	--	--	--

"BARREN"	B	0.50	0.30	1.000	86
----------	---	------	------	-------	----

NATURAL FAIR COVER					
--------------------	--	--	--	--	--

"CHAPARRAL,BROADLEAF"	B	0.20	0.30	1.000	63
-----------------------	---	------	------	-------	----

COMMERCIAL	B	3.60	0.30	0.100	56
------------	---	------	------	-------	----

NATURAL FAIR COVER					
--------------------	--	--	--	--	--

"GRASS"	B	4.00	0.30	1.000	69
---------	---	------	------	-------	----

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.781

SUBAREA AREA(ACRES) = 14.80 SUBAREA RUNOFF(CFS) = 17.68

EFFECTIVE AREA(ACRES) = 4201.73 AREA-AVERAGED Fm(INCH/HR) = 0.25

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83

TOTAL AREA(ACRES) = 5459.7 PEAK FLOW RATE(CFS) = 5230.29

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 42.54
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.562 **HZ-207**

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL FAIR COVER					
--------------------	--	--	--	--	--

"OPEN BRUSH"	B	14.60	0.30	1.000	66
--------------	---	-------	------	-------	----

AGRICULTURAL POOR COVER					
-------------------------	--	--	--	--	--

"ROW CROPS,CONTOURED"	B	6.30	0.30	1.000	79
-----------------------	---	------	------	-------	----

NATURAL FAIR COVER					
--------------------	--	--	--	--	--

"WOODLAND,GRASS"	B	3.70	0.30	1.000	65
------------------	---	------	------	-------	----

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 24.60 SUBAREA RUNOFF(CFS) = 27.94

EFFECTIVE AREA(ACRES) = 4226.33 AREA-AVERAGED Fm(INCH/HR) = 0.25

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83

TOTAL AREA(ACRES) = 5484.3 PEAK FLOW RATE(CFS) = 5230.29

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 42.54
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.562 **HZ-31113**

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL POOR COVER					
--------------------	--	--	--	--	--

"BARREN"	B	0.50	0.30	1.000	86
----------	---	------	------	-------	----

COMMERCIAL	B	0.30	0.30	0.100	56
------------	---	------	------	-------	----

NATURAL FAIR COVER					
--------------------	--	--	--	--	--

"OPEN BRUSH"	B	0.20	0.30	1.000	66
--------------	---	------	------	-------	----

RESIDENTIAL					
-------------	--	--	--	--	--

".4 DWELLING/ACRE"	B	0.80	0.30	0.900	56
--------------------	---	------	------	-------	----

AGRICULTURAL POOR COVER					
-------------------------	--	--	--	--	--

"ROW CROPS,CONTOURED"	B	1.60	0.30	1.000	79
-----------------------	---	------	------	-------	----

NATURAL POOR COVER					
--------------------	--	--	--	--	--

"BARREN"	B	31.90	0.30	1.000	86
----------	---	-------	------	-------	----

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.990

SUBAREA AREA(ACRES) = 35.30 SUBAREA RUNOFF(CFS) = 40.19

EFFECTIVE AREA(ACRES) = 4261.63 AREA-AVERAGED Fm(INCH/HR) = 0.25

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83

TOTAL AREA(ACRES) = 5519.6 PEAK FLOW RATE(CFS) = 5230.29

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 42.54
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.562 **HZ-31113**

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

COMMERCIAL	B	1.70	0.30	0.100	56
------------	---	------	------	-------	----

NATURAL FAIR COVER					
--------------------	--	--	--	--	--

"OPEN BRUSH"	B	0.30	0.30	1.000	66
--------------	---	------	------	-------	----

RESIDENTIAL					
-------------	--	--	--	--	--

".4 DWELLING/ACRE"	B	2.60	0.30	0.900	56
--------------------	---	------	------	-------	----

AGRICULTURAL POOR COVER					
-------------------------	--	--	--	--	--

"ROW CROPS,CONTOURED"	B	5.50	0.30	1.000	79
-----------------------	---	------	------	-------	----

NATURAL FAIR COVER					
--------------------	--	--	--	--	--

"WOODLAND,GRASS"	B	0.20	0.30	1.000	65
------------------	---	------	------	-------	----

NATURAL FAIR COVER					
--------------------	--	--	--	--	--

"OPEN BRUSH"	B	0.20	0.30	1.000	66
--------------	---	------	------	-------	----

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.830

SUBAREA AREA(ACRES) = 10.50 SUBAREA RUNOFF(CFS) = 12.41

EFFECTIVE AREA(ACRES) = 4272.13 AREA-AVERAGED Fm(INCH/HR) = 0.25

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83

TOTAL AREA(ACRES) = 5530.1 PEAK FLOW RATE(CFS) = 5230.29

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 42.54
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.562

HZ-31113

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL ".4 DWELLING/ACRE"	B	1.30	0.30	0.900	56
NATURAL POOR COVER "BARREN"	B	0.30	0.30	1.000	86

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL NATURAL FAIR COVER "OPEN BRUSH"	B	0.20	0.30	0.100	56
RESIDENTIAL ".4 DWELLING/ACRE"	B	0.30	0.30	1.000	66

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL ".4 DWELLING/ACRE"	B	6.50	0.30	0.900	56

AGRICULTURAL POOR COVER
"ROW CROPS,CONTOURED"

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.917

SUBAREA AREA(ACRES) = 11.60 SUBAREA RUNOFF(CFS) = 13.43
EFFECTIVE AREA(ACRES) = 4283.73 AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83

TOTAL AREA(ACRES) = 5541.7 PEAK FLOW RATE(CFS) = 5230.29
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13303.00 TO NODE 13304.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 355.00 DOWNSTREAM(FEET) = 350.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 925.40 CHANNEL SLOPE = 0.0054

GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 7.97
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.524

S33-05.5

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER "BARREN"	B	0.20	0.30	1.000	86

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "ROW CROPS,STRAIGHT ROW"	B	0.50	0.30	1.000	81

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "WOODLAND,GRASS"	B	1.10	0.30	1.000	65

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER "BARREN"	B	0.30	0.30	1.000	86

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "GRASS"	B	1.10	0.30	1.000	69

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	3.50	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5233.98

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.89

AVERAGE FLOW DEPTH(FEET) = 7.97 TRAVEL TIME(MIN.) = 1.74

Tc(MIN.) = 44.27

SUBAREA AREA(ACRES) = 6.70 SUBAREA RUNOFF(CFS) = 7.38

EFFECTIVE AREA(ACRES) = 4290.43 AREA-AVERAGED Fm(INCH/HR) = 0.25

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83

TOTAL AREA(ACRES) = 5548.4 PEAK FLOW RATE(CFS) = 5230.29

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 7.97

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 7.97 FLOW VELOCITY(FEET/SEC.) = 8.88

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13304.00 = 38920.27 FEET.

FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 44.27

S33-05.5

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.524

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "ROW CROPS,STRAIGHT ROW"	B	1.40	0.30	1.000	81

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	4.80	0.30	1.000	66

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "ROW CROPS,STRAIGHT ROW"	B	0.90	0.30	1.000	81

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 7.10 SUBAREA RUNOFF(CFS) = 7.82

EFFECTIVE AREA(ACRES) = 4297.53 AREA-AVERAGED Fm(INCH/HR) = 0.25

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83

TOTAL AREA(ACRES) = 5555.5 PEAK FLOW RATE(CFS) = 5230.29

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 44.27

HZ-31114

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.524

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER "BARREN"	B	7.80	0.30	1.000	86

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	1.70	0.30	1.000	79

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER "BARREN"	B	9.40	0.30	1.000	86

NATURAL FAIR COVER

"OPEN BRUSH" B 1.20 0.30 1.000 66
 RESIDENTIAL
 ".4 DWELLING/ACRE" B 0.10 0.30 0.900 56
 AGRICULTURAL POOR COVER
 "ROW CROPS,CONTOURED" B 2.60 0.30 1.000 79
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 22.80 SUBAREA RUNOFF(CFS) = 25.13
 EFFECTIVE AREA(ACRES) = 4320.33 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
 TOTAL AREA(ACRES) = 5578.3 PEAK FLOW RATE(CFS) = 5230.29
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 44.27
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.524 **HZ-31114**

SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

NATURAL FAIR COVER
 "WOODLAND,GRASS" B 0.20 0.30 1.000 65
 NATURAL FAIR COVER
 "OPEN BRUSH" B 0.30 0.30 1.000 66
 RESIDENTIAL
 ".4 DWELLING/ACRE" B 0.20 0.30 0.900 56
 AGRICULTURAL POOR COVER
 "ROW CROPS,CONTOURED" B 2.70 0.30 1.000 79
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.994
 SUBAREA AREA(ACRES) = 3.40 SUBAREA RUNOFF(CFS) = 3.75
 EFFECTIVE AREA(ACRES) = 4323.73 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
 TOTAL AREA(ACRES) = 5581.7 PEAK FLOW RATE(CFS) = 5230.29
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13304.00 TO NODE 13305.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 350.00 DOWNSTREAM(FEET) = 315.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2966.27 CHANNEL SLOPE = 0.0118
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 6.46
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.432 **S33-05.6**

SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 NATURAL POOR COVER
 "BARREN" B 1.70 0.30 1.000 86
 NATURAL FAIR COVER
 "GRASS" B 0.60 0.30 1.000 69

NATURAL FAIR COVER
 "OPEN BRUSH" B 0.10 0.30 1.000 66
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 0.40 0.30 1.000 65
 NATURAL POOR COVER
 "BARREN" B 2.20 0.30 1.000 86
 NATURAL FAIR COVER
 "GRASS" B 4.20 0.30 1.000 69
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5234.98
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.69
 AVERAGE FLOW DEPTH(FEET) = 6.46 TRAVEL TIME(MIN.) = 4.23
 Tc(MIN.) = 48.50

SUBAREA AREA(ACRES) = 9.20 SUBAREA RUNOFF(CFS) = 9.38
 EFFECTIVE AREA(ACRES) = 4332.93 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
 TOTAL AREA(ACRES) = 5590.9 PEAK FLOW RATE(CFS) = 5230.29
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 6.45

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 6.45 FLOW VELOCITY(FEET/SEC.) = 11.69
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 48.50
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.432 **S33-05.6**

SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

NATURAL FAIR COVER
 "OPEN BRUSH" C 8.10 0.25 1.000 77
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 2.30 0.30 1.000 65
 NATURAL FAIR COVER
 "GRASS" B 0.20 0.30 1.000 69
 NATURAL FAIR COVER
 "OPEN BRUSH" B 6.90 0.30 1.000 66
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 0.70 0.30 1.000 65
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.28
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 18.20 SUBAREA RUNOFF(CFS) = 18.91
 EFFECTIVE AREA(ACRES) = 4351.13 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
 TOTAL AREA(ACRES) = 5609.1 PEAK FLOW RATE(CFS) = 5230.29
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 48.50
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.432 **HZ-31115**
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	18.40	0.30	1.000	86
NATURAL FAIR COVER					
"MEADOWS"	B	1.20	0.30	1.000	70
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.10	0.30	1.000	65
NATURAL POOR COVER					
"BARREN"	B	26.60	0.30	1.000	86
COMMERCIAL	B	3.90	0.30	0.100	56
AGRICULTURAL POOR COVER					
"FALLOW"	B	3.00	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.934
 SUBAREA AREA(ACRES) = 53.20 SUBAREA RUNOFF(CFS) = 55.17
 EFFECTIVE AREA(ACRES) = 4404.33 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
 TOTAL AREA(ACRES) = 5662.3 PEAK FLOW RATE(CFS) = 5230.29
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 48.50
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.432 **HZ-31115**
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	1.10	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.20	0.30	1.000	65
NATURAL POOR COVER					
"BARREN"	B	14.00	0.30	1.000	86
COMMERCIAL	B	4.30	0.30	0.100	56
AGRICULTURAL POOR COVER					
"FALLOW"	B	5.30	0.30	1.000	86
NATURAL FAIR COVER					
"GRASS"	B	2.70	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.860
 SUBAREA AREA(ACRES) = 27.60 SUBAREA RUNOFF(CFS) = 29.18
 EFFECTIVE AREA(ACRES) = 4431.93 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
 TOTAL AREA(ACRES) = 5689.9 PEAK FLOW RATE(CFS) = 5230.29
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 48.50
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.432 **HZ-31115**
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"MEADOWS"	B	3.20	0.30	1.000	70
NATURAL FAIR COVER					
"OPEN BRUSH"	B	6.10	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	7.50	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	5.40	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	1.60	0.30	1.000	65
NATURAL POOR COVER					
"BARREN"	B	1.90	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.971
 SUBAREA AREA(ACRES) = 25.70 SUBAREA RUNOFF(CFS) = 26.40
 EFFECTIVE AREA(ACRES) = 4457.63 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
 TOTAL AREA(ACRES) = 5715.6 PEAK FLOW RATE(CFS) = 5230.29
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 48.50
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.432 **HZ-31115**
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	2.00	0.30	0.100	56
AGRICULTURAL POOR COVER					
"FALLOW"	B	3.70	0.30	1.000	86
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.10	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	2.60	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	0.20	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.10	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.807
 SUBAREA AREA(ACRES) = 10.70 SUBAREA RUNOFF(CFS) = 11.46
 EFFECTIVE AREA(ACRES) = 4468.33 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
 TOTAL AREA(ACRES) = 5726.3 PEAK FLOW RATE(CFS) = 5230.29
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

=====
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====

MAINLINE Tc(MIN.) = 48.50
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.432 **HZ-31115**
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCSSOIL AREA Fp Ap SCSS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"OPEN BRUSH" B 0.50 0.30 1.000 66
RESIDENTIAL
".4 DWELLING/ACRE" B 8.20 0.30 0.900 56
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.906
SUBAREA AREA(ACRES) = 8.70 SUBAREA RUNOFF(CFS) = 9.09
EFFECTIVE AREA(ACRES) = 4477.03 AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
TOTAL AREA(ACRES) = 5735.0 PEAK FLOW RATE(CFS) = 5230.29
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<<
=====

PEAK FLOWRATE TABLE FILE NAME: 3A00EVRL.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS: **A**
STREAM Q Tc Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (ACRES) NODE
1 1221.20 13.34 0.30(0.13) 0.43 436.8 120.00
2 1221.18 13.34 0.30(0.13) 0.43 436.8 110.00
3 1039.13 20.29 0.30(0.13) 0.43 504.5 100.00
4 976.70 22.82 0.30(0.13) 0.43 510.2 150.00
TOTAL AREA(ACRES) = 510.2

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<<
=====

** MAIN STREAM CONFLUENCE DATA **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 4517.52 32.64 1.805 0.30(0.26) 0.85 2828.4 31100.00
2 5210.44 46.80 1.469 0.30(0.25) 0.84 4335.3 13210.00
3 5229.03 47.31 1.458 0.30(0.25) 0.84 4387.2 13200.00
4 5230.29 48.50 1.432 0.30(0.25) 0.84 4477.0 13100.00
5 4989.12 72.41 1.206 0.30(0.25) 0.83 5715.2 13000.00
6 4934.17 74.68 1.191 0.30(0.25) 0.83 5735.0 13010.00
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 1221.20 13.34 3.218 0.30(0.13) 0.43 436.8 120.00
2 1221.18 13.34 3.218 0.30(0.13) 0.43 436.8 110.00
3 1039.13 20.29 2.401 0.30(0.13) 0.43 504.5 100.00

4 976.70 22.82 2.237 0.30(0.13) 0.43 510.2 150.00
LONGEST FLOWPATH FROM NODE 150.00 TO NODE 13305.00 = 9867.00 FEET.

** PEAK FLOW RATE TABLE **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 4750.46 13.34 3.218 0.30(0.22) 0.74 1592.2 120.00
2 4750.53 13.34 3.218 0.30(0.22) 0.74 1592.4 110.00
3 4926.41 20.29 2.401 0.30(0.23) 0.76 2262.1 100.00
4 5015.72 22.82 2.237 0.30(0.23) 0.77 2487.1 150.00
5 5293.74 32.64 1.805 0.30(0.24) 0.79 3338.6 31100.00
6 5831.28 46.80 1.469 0.30(0.24) 0.80 4845.5 13210.00
7 5844.73 47.31 1.458 0.30(0.24) 0.80 4897.4 13200.00
8 5834.03 48.50 1.432 0.30(0.24) 0.80 4987.2 13100.00
9 5488.06 72.41 1.206 0.30(0.24) 0.80 6225.4 13000.00
10 5426.05 74.68 1.191 0.30(0.24) 0.80 6245.2 13010.00
TOTAL AREA(ACRES) = 6245.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
PEAK FLOW RATE(CFS) = 5844.73 Tc(MIN.) = 47.315
EFFECTIVE AREA(ACRES) = 4897.35 AREA-AVERAGED Fm(INCH/HR) = 0.24
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.76
TOTAL AREA(ACRES) = 6245.2
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<<
=====

FLOW PROCESS FROM NODE 13305.00 TO NODE 13306.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<<
=====

ELEVATION DATA: UPSTREAM(FEET) = 315.00 DOWNSTREAM(FEET) = 245.50
CHANNEL LENGTH THRU SUBAREA(FEET) = 4408.41 CHANNEL SLOPE = 0.0158
GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 6.34 **S33-06**
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.369

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCSSOIL AREA Fp Ap SCSS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL POOR COVER
"BARREN" B 0.40 0.30 1.000 86
NATURAL FAIR COVER
"GRASS" B 9.20 0.30 1.000 69
NATURAL FAIR COVER
"OPEN BRUSH" B 1.00 0.30 1.000 66
NATURAL FAIR COVER
"WOODLAND,GRASS" B 1.30 0.30 1.000 65
NATURAL POOR COVER
"BARREN" B 2.40 0.30 1.000 86
NATURAL FAIR COVER
"CHAPARRAL,BROADLEAF" B 4.10 0.30 1.000 63

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5853.58
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 13.38
 AVERAGE FLOW DEPTH(FEET) = 6.34 TRAVEL TIME(MIN.) = 5.49
 Tc(MIN.) = 52.80
 SUBAREA AREA(ACRES) = 18.40 SUBAREA RUNOFF(CFS) = 17.71
 EFFECTIVE AREA(ACRES) = 4915.75 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6263.6 PEAK FLOW RATE(CFS) = 5844.73
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 6.34

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 6.34 FLOW VELOCITY(FEET/SEC.) = 13.37
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13306.00 = 46294.95 FEET.

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

 MAINLINE Tc(MIN.) = 52.80
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.369
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 NATURAL FAIR COVER
 "GRASS" B 19.20 0.30 1.000 69
 NATURAL FAIR COVER
 "OPEN BRUSH" B 20.90 0.30 1.000 66
 NATURAL FAIR COVER
 "WOODLAND, GRASS" B 4.10 0.30 1.000 65
 NATURAL FAIR COVER
 "CHAPARRAL, BROADLEAF" B 0.50 0.30 1.000 63
 NATURAL FAIR COVER
 "GRASS" B 4.30 0.30 1.000 69
 NATURAL FAIR COVER
 "OPEN BRUSH" B 0.60 0.30 1.000 66
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 49.60 SUBAREA RUNOFF(CFS) = 47.73
 EFFECTIVE AREA(ACRES) = 4965.35 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6313.2 PEAK FLOW RATE(CFS) = 5844.73
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

S33-06

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

 MAINLINE Tc(MIN.) = 52.80
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.369
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS

LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 NATURAL FAIR COVER
 "WOODLAND, GRASS" B 0.80 0.30 1.000 65
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 0.80 SUBAREA RUNOFF(CFS) = 0.77
 EFFECTIVE AREA(ACRES) = 4966.15 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6314.0 PEAK FLOW RATE(CFS) = 5844.73
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

S33-06

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

 MAINLINE Tc(MIN.) = 52.80
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.369
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 PUBLIC PARK B 0.10 0.30 0.850 56
 NATURAL FAIR COVER
 "OPEN BRUSH" B 0.10 0.30 1.000 66
 NATURAL FAIR COVER
 "WOODLAND, GRASS" B 0.10 0.30 1.000 65
 NATURAL POOR COVER
 "BARREN" B 0.20 0.30 1.000 86
 PUBLIC PARK B 0.40 0.30 0.850 56
 NATURAL FAIR COVER
 "GRASS" B 0.40 0.30 1.000 69
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.942
 SUBAREA AREA(ACRES) = 1.30 SUBAREA RUNOFF(CFS) = 1.27
 EFFECTIVE AREA(ACRES) = 4967.45 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6315.3 PEAK FLOW RATE(CFS) = 5844.73
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

S33-06

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

 MAINLINE Tc(MIN.) = 52.80
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.369
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 RESIDENTIAL
 ".4 DWELLING/ACRE" B 0.80 0.30 0.900 56
 NATURAL FAIR COVER
 "GRASS" B 0.80 0.30 1.000 69
 NATURAL FAIR COVER
 "OPEN BRUSH" B 1.00 0.30 1.000 66
 NATURAL FAIR COVER
 "WOODLAND, GRASS" B 1.10 0.30 1.000 65
 COMMERCIAL B 1.10 0.30 0.100 56

HZ-31116

RESIDENTIAL
 ".4 DWELLING/ACRE" B 2.80 0.30 0.900 56
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.822
 SUBAREA AREA(ACRES) = 7.60 SUBAREA RUNOFF(CFS) = 7.68
 EFFECTIVE AREA(ACRES) = 4975.05 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6322.9 PEAK FLOW RATE(CFS) = 5844.73
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 52.80
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.369 **HZ-31116**
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	3.50	0.30	0.100	56
NATURAL FAIR COVER "GRASS"	B	5.00	0.30	1.000	69
RESIDENTIAL ".4 DWELLING/ACRE"	B	6.70	0.30	0.900	56
NATURAL FAIR COVER "WOODLAND,GRASS"	B	7.80	0.30	1.000	65
NATURAL FAIR COVER "OPEN BRUSH"	B	10.80	0.30	1.000	66
COMMERCIAL	B	13.80	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.659
 SUBAREA AREA(ACRES) = 47.60 SUBAREA RUNOFF(CFS) = 50.19
 EFFECTIVE AREA(ACRES) = 5022.65 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6370.5 PEAK FLOW RATE(CFS) = 5844.73
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 52.80
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.369 **HZ-31116**
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER "BARREN"	B	21.54	0.30	1.000	86
NATURAL POOR COVER "BARREN"	B	36.64	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 58.18 SUBAREA RUNOFF(CFS) = 55.98
 EFFECTIVE AREA(ACRES) = 5080.83 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6428.7 PEAK FLOW RATE(CFS) = 5844.73

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13307.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 245.50 DOWNSTREAM(FEET) = 220.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1543.21 CHANNEL SLOPE = 0.0165
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 6.25
 CHANNEL FLOW THRU SUBAREA(CFS) = 5844.73
 FLOW VELOCITY(FEET/SEC.) = 13.59 FLOW DEPTH(FEET) = 6.25
 TRAVEL TIME(MIN.) = 1.89 Tc(MIN.) = 54.70
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13307.00 = 47838.16 FEET.

 FLOW PROCESS FROM NODE 13307.00 TO NODE 13307.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 54.70
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.348 **HZ-31010**
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	0.20	0.30	0.100	56
NATURAL FAIR COVER "GRASS"	B	0.10	0.30	1.000	69
AGRICULTURAL FAIR COVER "ORCHARDS"	B	0.20	0.30	1.000	65
NATURAL POOR COVER "BARREN"	B	3.70	0.30	1.000	86
COMMERCIAL	B	0.30	0.30	0.100	56
NATURAL FAIR COVER "GRASS"	B	3.20	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.942
 SUBAREA AREA(ACRES) = 7.70 SUBAREA RUNOFF(CFS) = 7.39
 EFFECTIVE AREA(ACRES) = 5088.53 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6436.4 PEAK FLOW RATE(CFS) = 5844.73
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13307.00 TO NODE 13307.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 54.70
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.348 **HZ-31010**
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "WOODLAND,GRASS"	B	3.60	0.30	1.000	65

NATURAL FAIR COVER
 "GRASS" B 1.90 0.30 1.000 69
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 0.60 0.30 1.000 65
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 6.10 SUBAREA RUNOFF(CFS) = 5.76
 EFFECTIVE AREA(ACRES) = 5094.63 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6442.5 PEAK FLOW RATE(CFS) = 5844.73
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13307.00 TO NODE 13308.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 220.00 DOWNSTREAM(FEET) = 212.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 925.62 CHANNEL SLOPE = 0.0086
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 7.46
 CHANNEL FLOW THRU SUBAREA(CFS) = 5844.73
 FLOW VELOCITY(FEET/SEC.) = 10.83 FLOW DEPTH(FEET) = 7.46
 TRAVEL TIME(MIN.) = 1.42 Tc(MIN.) = 56.12
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13308.00 = 48763.78 FEET.

 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 56.12 **HZ-208**
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.333
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	0.10	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.20	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	5.00	0.30	1.000	65
COMMERCIAL	B	3.20	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	0.10	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.90	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.697
 SUBAREA AREA(ACRES) = 9.50 SUBAREA RUNOFF(CFS) = 9.61
 EFFECTIVE AREA(ACRES) = 5104.13 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6452.0 PEAK FLOW RATE(CFS) = 5844.73
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 56.12 **HZ-208**
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.333
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
APARTMENTS	B	0.30	0.30	0.200	56
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	1.00	0.30	1.000	63
COMMERCIAL	B	41.90	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	7.20	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	25.00	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.498
 SUBAREA AREA(ACRES) = 75.60 SUBAREA RUNOFF(CFS) = 80.51
 EFFECTIVE AREA(ACRES) = 5179.73 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6527.6 PEAK FLOW RATE(CFS) = 5844.73
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 56.12 **HZ-208**
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.333
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	0.10	0.30	0.850	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	0.90	0.30	1.000	79
SCHOOL	B	0.30	0.30	0.600	56
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	13.20	0.30	1.000	65
APARTMENTS	B	0.50	0.30	0.200	56
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.60	0.30	1.000	63

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.966
 SUBAREA AREA(ACRES) = 15.60 SUBAREA RUNOFF(CFS) = 14.64
 EFFECTIVE AREA(ACRES) = 5195.33 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6543.2 PEAK FLOW RATE(CFS) = 5844.73
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

```

=====
MAINLINE Tc(MIN.) = 56.12
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.333 HZ-208
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
COMMERCIAL B 33.90 0.30 0.100 56
NATURAL FAIR COVER
"GRASS" B 17.60 0.30 1.000 69
NATURAL FAIR COVER
"OPEN BRUSH" B 16.80 0.30 1.000 66
RESIDENTIAL
"11+ DWELLINGS/ACRE" B 0.60 0.30 0.200 56
RESIDENTIAL
"8-10 DWELLINGS/ACRE" B 1.50 0.30 0.400 56
AGRICULTURAL POOR COVER
"ROW CROPS,CONTOURED" B 10.00 0.30 1.000 79
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.603
SUBAREA AREA(ACRES) = 80.40 SUBAREA RUNOFF(CFS) = 83.33
EFFECTIVE AREA(ACRES) = 5275.73 AREA-AVERAGED Fm(INCH/HR) = 0.24
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79
TOTAL AREA(ACRES) = 6623.6 PEAK FLOW RATE(CFS) = 5844.73
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====

```

```

=====
MAINLINE Tc(MIN.) = 56.12
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.333 HZ-208
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
SCHOOL B 0.30 0.30 0.600 56
NATURAL FAIR COVER
"WOODLAND,GRASS" B 0.70 0.30 1.000 65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.880
SUBAREA AREA(ACRES) = 1.00 SUBAREA RUNOFF(CFS) = 0.96
EFFECTIVE AREA(ACRES) = 5276.73 AREA-AVERAGED Fm(INCH/HR) = 0.24
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79
TOTAL AREA(ACRES) = 6624.6 PEAK FLOW RATE(CFS) = 5844.73
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====

```

```

=====
MAINLINE Tc(MIN.) = 56.12
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.333 HZ-31010.2
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"GRASS" B 0.30 0.30 1.000 69

```

```

NATURAL FAIR COVER
"WOODLAND,GRASS" B 0.80 0.30 1.000 65
NATURAL FAIR COVER
"GRASS" B 0.50 0.30 1.000 69
NATURAL FAIR COVER
"WOODLAND,GRASS" B 0.20 0.30 1.000 65
NATURAL FAIR COVER
"GRASS" B 0.30 0.30 1.000 69
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 2.10 SUBAREA RUNOFF(CFS) = 1.95
EFFECTIVE AREA(ACRES) = 5278.83 AREA-AVERAGED Fm(INCH/HR) = 0.24
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79
TOTAL AREA(ACRES) = 6626.7 PEAK FLOW RATE(CFS) = 5844.73
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====

```

```

=====
MAINLINE Tc(MIN.) = 56.12
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.333 HZ-31113.2
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"GRASS" B 1.20 0.30 1.000 69
NATURAL FAIR COVER
"OPEN BRUSH" B 0.50 0.30 1.000 66
PUBLIC PARK B 1.70 0.30 0.850 56
NATURAL FAIR COVER
"WOODLAND,GRASS" B 7.20 0.30 1.000 65
NATURAL FAIR COVER
"GRASS" B 1.00 0.30 1.000 69
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.978
SUBAREA AREA(ACRES) = 11.60 SUBAREA RUNOFF(CFS) = 10.85
EFFECTIVE AREA(ACRES) = 5290.44 AREA-AVERAGED Fm(INCH/HR) = 0.24
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79
TOTAL AREA(ACRES) = 6638.3 PEAK FLOW RATE(CFS) = 5844.73
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 10
-----
>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<
=====

```

```

*****
FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 15.1
-----
>>>>DEFINE MEMORY BANK # 2 <<<<
=====

```

```

PEAK FLOWRATE TABLE FILE NAME: RU00EV29.DNA S29
MEMORY BANK # 2 DEFINED AS FOLLOWS:
STREAM Q Tc Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (ACRES) NODE

```

1	24295.70	16.32	0.30 (0.24)	0.80	3744.5	203.00
2	25733.67	20.42	0.30 (0.24)	0.80	4727.0	50110.00
3	27547.57	25.20	0.30 (0.24)	0.81	6168.3	420.00
4	29872.69	32.32	0.30 (0.25)	0.83	8813.5	50260.00
5	31476.36	37.78	0.30 (0.26)	0.87	11007.8	390.00
6	34610.64	53.32	0.30 (0.27)	0.91	16927.6	40100.00
7	36610.73	60.55	0.30 (0.28)	0.92	19731.7	11801.00
8	39349.16	70.01	0.30 (0.28)	0.93	24028.5	11530.00
9	41576.93	78.54	0.30 (0.28)	0.95	29034.2	11910.00
10	43607.94	85.61	0.30 (0.29)	0.95	33615.8	11330.00
11	44596.62	91.95	0.30 (0.29)	0.96	38046.8	11130.00
12	44405.07	99.54	0.30 (0.29)	0.96	42040.8	12330.00
13	44104.83	106.18	0.30 (0.29)	0.96	45384.0	12400.00
14	43498.70	114.85	0.30 (0.29)	0.96	48752.7	12201.00
15	43004.18	118.81	0.30 (0.29)	0.96	49837.4	12111.00
16	42315.21	124.18	0.30 (0.29)	0.96	51206.9	12101.10
17	41758.73	128.20	0.30 (0.29)	0.97	52055.9	10400.00
18	40165.51	136.22	0.30 (0.29)	0.97	53371.1	12010.00
19	38835.15	142.09	0.30 (0.29)	0.97	53684.8	10210.00
20	35274.16	168.14	0.30 (0.29)	0.97	54417.5	10100.00

TOTAL AREA (ACRES) = 54417.5

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24295.70	16.32	0.30 (0.24)	0.80	3744.5	203.00
2	25733.67	20.42	0.30 (0.24)	0.80	4727.0	50110.00
3	27547.57	25.20	0.30 (0.24)	0.81	6168.3	420.00
4	29872.69	32.32	0.30 (0.25)	0.83	8813.5	50260.00
5	31476.36	37.78	0.30 (0.26)	0.87	11007.8	390.00
6	34610.64	53.32	0.30 (0.27)	0.91	16927.6	40100.00
7	36610.73	60.55	0.30 (0.28)	0.92	19731.7	11801.00
8	39349.16	70.01	0.30 (0.28)	0.93	24028.5	11530.00
9	41576.93	78.54	0.30 (0.28)	0.95	29034.2	11910.00
10	43607.94	85.61	0.30 (0.29)	0.95	33615.8	11330.00
11	44596.62	91.95	0.30 (0.29)	0.96	38046.8	11130.00
12	44405.07	99.54	0.30 (0.29)	0.96	42040.8	12330.00
13	44104.83	106.18	0.30 (0.29)	0.96	45384.0	12400.00
14	43498.70	114.85	0.30 (0.29)	0.96	48752.7	12201.00
15	43004.18	118.81	0.30 (0.29)	0.96	49837.4	12111.00
16	42315.21	124.18	0.30 (0.29)	0.96	51206.9	12101.10
17	41758.73	128.20	0.30 (0.29)	0.97	52055.9	10400.00
18	40165.51	136.22	0.30 (0.29)	0.97	53371.1	12010.00
19	38835.15	142.09	0.30 (0.29)	0.97	53684.8	10210.00
20	35274.16	168.14	0.30 (0.29)	0.97	54417.5	10100.00

TOTAL AREA (ACRES) = 54417.5

FLOW PROCESS FROM NODE 12904.00 TO NODE 13308.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 213.00 DOWNSTREAM(FEET) = 212.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1389.52 CHANNEL SLOPE = 0.0007
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 19.19
CHANNEL FLOW THRU SUBAREA(CFS) = 44596.62
FLOW VELOCITY(FEET/SEC.) = 7.85 FLOW DEPTH(FEET) = 19.19
TRAVEL TIME(MIN.) = 2.95 Tc(MIN.) = 94.90
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118087.91 FEET.

FLOW PROCESS FROM NODE 13307.00 TO NODE 13308.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24295.70	19.86	2.433	0.30 (0.24)	0.80	3744.5	203.00
2	25733.67	23.90	2.167	0.30 (0.24)	0.80	4727.0	50110.00
3	27547.57	28.61	1.934	0.30 (0.24)	0.81	6168.3	420.00
4	29872.69	35.65	1.728	0.30 (0.25)	0.83	8813.5	50260.00
5	31476.36	41.06	1.594	0.30 (0.26)	0.87	11007.8	390.00
6	34610.64	56.50	1.328	0.30 (0.27)	0.91	16927.6	40100.00
7	36610.73	63.68	1.265	0.30 (0.28)	0.92	19731.7	11801.00
8	39349.16	73.08	1.202	0.30 (0.28)	0.93	24028.5	11530.00
9	41576.93	81.56	1.145	0.30 (0.28)	0.95	29034.2	11910.00
10	43607.94	88.59	1.098	0.30 (0.29)	0.95	33615.8	11330.00
11	44596.62	94.90	1.066	0.30 (0.29)	0.96	38046.8	11130.00
12	44405.07	102.49	1.031	0.30 (0.29)	0.96	42040.8	12330.00
13	44104.83	109.14	1.001	0.30 (0.29)	0.96	45384.0	12400.00
14	43498.70	117.82	0.961	0.30 (0.29)	0.96	48752.7	12201.00
15	43004.18	121.79	0.946	0.30 (0.29)	0.96	49837.4	12111.00
16	42315.21	127.17	0.932	0.30 (0.29)	0.96	51206.9	12101.10
17	41758.73	131.21	0.922	0.30 (0.29)	0.97	52055.9	10400.00
18	40165.51	139.27	0.901	0.30 (0.29)	0.97	53371.1	12010.00
19	38835.15	145.16	0.886	0.30 (0.29)	0.97	53684.8	10210.00
20	35274.16	171.30	0.818	0.30 (0.29)	0.97	54417.5	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118087.91 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4750.46	22.71	2.244	0.30 (0.22)	0.74	1985.3	120.00
2	4750.53	22.71	2.244	0.30 (0.22)	0.74	1985.4	110.00
3	4926.41	29.57	1.891	0.30 (0.23)	0.76	2655.2	100.00
4	5015.72	32.04	1.820	0.30 (0.23)	0.77	2880.2	150.00
5	5293.74	41.72	1.580	0.30 (0.24)	0.79	3731.7	31100.00
6	5831.28	55.62	1.338	0.30 (0.24)	0.79	5238.5	13210.00
7	5844.73	56.12	1.333	0.30 (0.24)	0.79	5290.4	13200.00
8	5834.03	57.32	1.320	0.30 (0.24)	0.79	5380.3	13100.00
9	5488.06	81.39	1.146	0.30 (0.24)	0.80	6618.5	13000.00
10	5426.05	83.68	1.131	0.30 (0.24)	0.80	6638.3	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13308.00 = 48763.78 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28839.28	19.86	2.433	0.30 (0.23)	0.78	5480.6	203.00
2	30060.63	22.71	2.244	0.30 (0.23)	0.78	6423.0	120.00
3	30061.11	22.71	2.244	0.30 (0.23)	0.78	6423.4	110.00
4	30514.72	23.90	2.167	0.30 (0.23)	0.78	6828.7	50110.00
5	32449.33	28.61	1.934	0.30 (0.24)	0.79	8729.6	420.00
6	32790.97	29.57	1.891	0.30 (0.24)	0.80	9184.1	100.00
7	33698.41	32.04	1.820	0.30 (0.24)	0.80	10339.8	150.00
8	34991.91	35.65	1.728	0.30 (0.25)	0.82	12010.6	50260.00
9	36751.00	41.06	1.594	0.30 (0.25)	0.85	14680.9	390.00
10	36905.06	41.72	1.580	0.30 (0.25)	0.85	14994.4	31100.00
11	40261.90	55.62	1.338	0.30 (0.26)	0.88	21826.2	13210.00
12	40377.91	56.12	1.333	0.30 (0.26)	0.88	22071.8	13200.00
13	40451.95	56.50	1.328	0.30 (0.26)	0.88	22246.7	40100.00
14	40671.96	57.32	1.320	0.30 (0.26)	0.88	22626.6	13100.00
15	42353.31	63.68	1.265	0.30 (0.27)	0.89	25439.3	11801.00
16	44956.73	73.08	1.202	0.30 (0.27)	0.91	30219.3	11530.00
17	47021.65	81.39	1.146	0.30 (0.28)	0.92	35555.2	13000.00
18	47060.53	81.56	1.145	0.30 (0.28)	0.92	35654.1	11910.00
19	47617.55	83.68	1.131	0.30 (0.28)	0.92	37058.8	13010.00
20	48833.19	88.59	1.098	0.30 (0.28)	0.93	40254.1	11330.00
21	49627.84	94.90	1.066	0.30 (0.28)	0.93	44685.1	11130.00
22	49225.25	102.49	1.031	0.30 (0.28)	0.94	48679.1	12330.00
23	48740.35	109.14	1.001	0.30 (0.28)	0.94	52022.3	12400.00
24	47892.98	117.82	0.961	0.30 (0.28)	0.94	55391.0	12201.00
25	47309.60	121.79	0.946	0.30 (0.28)	0.94	56475.7	12111.00
26	46535.54	127.17	0.932	0.30 (0.28)	0.95	57845.2	12101.10
27	45915.21	131.21	0.922	0.30 (0.28)	0.95	58694.3	10400.00
28	44194.54	139.27	0.901	0.30 (0.28)	0.95	60009.4	12010.00
29	42770.93	145.16	0.886	0.30 (0.28)	0.95	60323.1	10210.00
30	38796.43	171.30	0.818	0.30 (0.28)	0.95	61055.8	10100.00

TOTAL AREA (ACRES) = 61055.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 49627.84 Tc (MIN.) = 94.897
EFFECTIVE AREA (ACRES) = 44685.12 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.88
TOTAL AREA (ACRES) = 61055.8
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118087.91 FEET.

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 61055.8 TC (MIN.) = 94.90
EFFECTIVE AREA (ACRES) = 44685.12 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.933
PEAK FLOW RATE (CFS) = 49627.84

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28839.28	19.86	2.433	0.30 (0.23)	0.78	5480.6	203.00
2	30060.63	22.71	2.244	0.30 (0.23)	0.78	6423.0	120.00
3	30061.11	22.71	2.244	0.30 (0.23)	0.78	6423.4	110.00
4	30514.72	23.90	2.167	0.30 (0.23)	0.78	6828.7	50110.00
5	32449.33	28.61	1.934	0.30 (0.24)	0.79	8729.6	420.00
6	32790.97	29.57	1.891	0.30 (0.24)	0.80	9184.1	100.00
7	33698.41	32.04	1.820	0.30 (0.24)	0.80	10339.8	150.00
8	34991.91	35.65	1.728	0.30 (0.25)	0.82	12010.6	50260.00

9	36751.00	41.06	1.594	0.30 (0.25)	0.85	14680.9	390.00
10	36905.06	41.72	1.580	0.30 (0.25)	0.85	14994.4	31100.00
11	40261.90	55.62	1.338	0.30 (0.26)	0.88	21826.2	13210.00
12	40377.91	56.12	1.333	0.30 (0.26)	0.88	22071.8	13200.00
13	40451.95	56.50	1.328	0.30 (0.26)	0.88	22246.7	40100.00
14	40671.96	57.32	1.320	0.30 (0.26)	0.88	22626.6	13100.00
15	42353.31	63.68	1.265	0.30 (0.27)	0.89	25439.3	11801.00
16	44956.73	73.08	1.202	0.30 (0.27)	0.91	30219.3	11530.00
17	47021.65	81.39	1.146	0.30 (0.28)	0.92	35555.2	13000.00
18	47060.53	81.56	1.145	0.30 (0.28)	0.92	35654.1	11910.00
19	47617.55	83.68	1.131	0.30 (0.28)	0.92	37058.8	13010.00
20	48833.19	88.59	1.098	0.30 (0.28)	0.93	40254.1	11330.00
21	49627.84	94.90	1.066	0.30 (0.28)	0.93	44685.1	11130.00
22	49225.25	102.49	1.031	0.30 (0.28)	0.94	48679.1	12330.00
23	48740.35	109.14	1.001	0.30 (0.28)	0.94	52022.3	12400.00
24	47892.98	117.82	0.961	0.30 (0.28)	0.94	55391.0	12201.00
25	47309.60	121.79	0.946	0.30 (0.28)	0.94	56475.7	12111.00
26	46535.54	127.17	0.932	0.30 (0.28)	0.95	57845.2	12101.10
27	45915.21	131.21	0.922	0.30 (0.28)	0.95	58694.3	10400.00
28	44194.54	139.27	0.901	0.30 (0.28)	0.95	60009.4	12010.00
29	42770.93	145.16	0.886	0.30 (0.28)	0.95	60323.1	10210.00
30	38796.43	171.30	0.818	0.30 (0.28)	0.95	61055.8	10100.00

END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2010 Advanced Engineering Software (aes)
Ver. 17.0 Release Date: 07/01/2010 License ID 1527

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 134 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 100-YR EV AUG 2023 ROKAMOTO *

FILE NAME: RU00EV34.DAT
TIME/DATE OF STUDY: 21:35 08/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 100.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.846
- 2) 10.00; 3.774
- 3) 15.00; 2.924
- 4) 20.00; 2.413
- 5) 25.00; 2.091
- 6) 30.00; 1.869
- 7) 40.00; 1.613
- 8) 50.00; 1.397
- 9) 60.00; 1.286
- 10) 90.00; 1.084
- 11) 120.00; 0.947
- 12) 180.00; 0.791
- 13) 360.00; 0.584
- 14) 1200.00; 0.255

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	(FT)	(FT)	SIDE / SIDE/ WAY	(FT)	(FT)	(FT)	(FT)	(n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: RU00EV33.DNA

S33

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28839.28	19.86	0.30 (0.23)	0.78	5480.6	203.00
2	30514.72	23.90	0.30 (0.23)	0.78	6828.7	50110.00
3	33698.41	32.04	0.30 (0.24)	0.80	10339.8	150.00
4	34991.91	35.65	0.30 (0.25)	0.82	12010.6	50260.00
5	36905.06	41.72	0.30 (0.25)	0.85	14994.4	31100.00
6	40671.96	57.32	0.30 (0.26)	0.88	22626.6	13100.00
7	42353.31	63.68	0.30 (0.27)	0.89	25439.3	11801.00
8	44956.73	73.08	0.30 (0.27)	0.91	30219.3	11530.00
9	47617.55	83.68	0.30 (0.28)	0.92	37058.8	13010.00
10	48833.19	88.59	0.30 (0.28)	0.93	40254.1	11330.00
11	49627.84	94.90	0.30 (0.28)	0.93	44685.1	11130.00
12	49225.25	102.49	0.30 (0.28)	0.94	48679.1	12330.00
13	48740.35	109.14	0.30 (0.28)	0.94	52022.3	12400.00
14	47892.98	117.82	0.30 (0.28)	0.94	55391.0	12201.00
15	47309.60	121.79	0.30 (0.28)	0.94	56475.7	12111.00
16	46535.54	127.17	0.30 (0.28)	0.95	57845.2	12101.10
17	45915.21	131.21	0.30 (0.28)	0.95	58694.3	10400.00
18	44194.54	139.27	0.30 (0.28)	0.95	60009.4	12010.00
19	42770.93	145.16	0.30 (0.28)	0.95	60323.1	10210.00
20	38796.43	171.30	0.30 (0.28)	0.95	61055.8	10100.00
TOTAL AREA (ACRES) =						61055.8

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28839.28	19.86	0.30 (0.23)	0.78	5480.6	203.00
2	30514.72	23.90	0.30 (0.23)	0.78	6828.7	50110.00
3	33698.41	32.04	0.30 (0.24)	0.80	10339.8	150.00
4	34991.91	35.65	0.30 (0.25)	0.82	12010.6	50260.00
5	36905.06	41.72	0.30 (0.25)	0.85	14994.4	31100.00
6	40671.96	57.32	0.30 (0.26)	0.88	22626.6	13100.00
7	42353.31	63.68	0.30 (0.27)	0.89	25439.3	11801.00
8	44956.73	73.08	0.30 (0.27)	0.91	30219.3	11530.00
9	47617.55	83.68	0.30 (0.28)	0.92	37058.8	13010.00
10	48833.19	88.59	0.30 (0.28)	0.93	40254.1	11330.00
11	49627.84	94.90	0.30 (0.28)	0.93	44685.1	11130.00
12	49225.25	102.49	0.30 (0.28)	0.94	48679.1	12330.00
13	48740.35	109.14	0.30 (0.28)	0.94	52022.3	12400.00

14 47892.98 117.82 0.30(0.28) 0.94 55391.0 12201.00
 15 47309.60 121.79 0.30(0.28) 0.94 56475.7 12111.00
 16 46535.54 127.17 0.30(0.28) 0.95 57845.2 12101.10
 17 45915.21 131.21 0.30(0.28) 0.95 58694.3 10400.00
 18 44194.54 139.27 0.30(0.28) 0.95 60009.4 12010.00
 19 42770.93 145.16 0.30(0.28) 0.95 60323.1 10210.00
 20 38796.43 171.30 0.30(0.28) 0.95 61055.8 10100.00
 TOTAL AREA(ACRES) = 61055.8

FLOW PROCESS FROM NODE 13308.00 TO NODE 13402.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 212.00 DOWNSTREAM(FEET) = 209.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 623.02 CHANNEL SLOPE = 0.0048
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 12.13
 CHANNEL FLOW THRU SUBAREA(CFS) = 49627.84
 FLOW VELOCITY(FEET/SEC.) = 15.70 FLOW DEPTH(FEET) = 12.13
 TRAVEL TIME(MIN.) = 0.66 Tc(MIN.) = 95.56
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118710.93 FEET.

FLOW PROCESS FROM NODE 13402.00 TO NODE 13402.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P505XXCE.DNA
 MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	282.54	17.03	0.30(0.29)	0.96	146.4	50500.00
TOTAL AREA(ACRES) =						146.4

FLOW PROCESS FROM NODE 13402.00 TO NODE 13402.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28839.28	20.65	2.371	0.30(0.23)	0.78	5480.6	203.00
2	30514.72	24.68	2.112	0.30(0.23)	0.78	6828.7	50110.00
3	33698.41	32.79	1.798	0.30(0.24)	0.80	10339.8	150.00
4	34991.91	36.38	1.706	0.30(0.25)	0.82	12010.6	50260.00
5	36905.06	42.45	1.560	0.30(0.25)	0.85	14994.4	31100.00
6	40671.96	58.02	1.308	0.30(0.26)	0.88	22626.6	13100.00
7	42353.31	64.38	1.257	0.30(0.27)	0.89	25439.3	11801.00
8	44956.73	73.76	1.193	0.30(0.27)	0.91	30219.3	11530.00
9	47617.55	84.35	1.122	0.30(0.28)	0.92	37058.8	13010.00
10	48833.19	89.25	1.089	0.30(0.28)	0.93	40254.1	11330.00
11	49627.84	95.56	1.059	0.30(0.28)	0.93	44685.1	11130.00
12	49225.25	103.16	1.024	0.30(0.28)	0.94	48679.1	12330.00

13 48740.35 109.81 0.994 0.30(0.28) 0.94 52022.3 12400.00
 14 47892.98 118.49 0.954 0.30(0.28) 0.94 55391.0 12201.00
 15 47309.60 122.47 0.941 0.30(0.28) 0.94 56475.7 12111.00
 16 46535.54 127.85 0.927 0.30(0.28) 0.95 57845.2 12101.10
 17 45915.21 131.89 0.916 0.30(0.28) 0.95 58694.3 10400.00
 18 44194.54 139.95 0.895 0.30(0.28) 0.95 60009.4 12010.00
 19 42770.93 145.86 0.880 0.30(0.28) 0.95 60323.1 10210.00
 20 38796.43 172.02 0.812 0.30(0.28) 0.95 61055.8 10100.00
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118710.93 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	282.54	17.03	2.717	0.30(0.29)	0.96	146.4	50500.00
LONGEST FLOWPATH FROM NODE 50500.00 TO NODE 13402.00 =							5416.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27908.73	17.03	2.717	0.30(0.24)	0.79	4665.4	50500.00
2	29081.62	20.65	2.371	0.30(0.24)	0.79	5627.0	203.00
3	30726.90	24.68	2.112	0.30(0.24)	0.79	6975.1	50110.00
4	33874.03	32.79	1.798	0.30(0.24)	0.81	10486.2	150.00
5	35156.83	36.38	1.706	0.30(0.25)	0.82	12157.0	50260.00
6	37053.07	42.45	1.560	0.30(0.25)	0.85	15140.8	31100.00
7	40790.64	58.02	1.308	0.30(0.27)	0.88	22773.0	13100.00
8	42466.01	64.38	1.257	0.30(0.27)	0.89	25585.7	11801.00
9	45062.09	73.76	1.193	0.30(0.27)	0.91	30365.7	11530.00
10	47714.60	84.35	1.122	0.30(0.28)	0.92	37205.2	13010.00
11	48926.41	89.25	1.089	0.30(0.28)	0.93	40400.5	11330.00
12	49717.53	95.56	1.059	0.30(0.28)	0.93	44831.5	11130.00
13	49310.90	103.16	1.024	0.30(0.28)	0.94	48825.5	12330.00
14	48822.46	109.81	0.994	0.30(0.28)	0.94	52168.7	12400.00
15	47970.48	118.49	0.954	0.30(0.28)	0.94	55537.4	12201.00
16	47385.56	122.47	0.941	0.30(0.28)	0.94	56622.1	12111.00
17	46609.87	127.85	0.927	0.30(0.28)	0.95	57991.6	12101.10
18	45988.32	131.89	0.916	0.30(0.28)	0.95	58840.7	10400.00
19	44265.21	139.95	0.895	0.30(0.28)	0.95	60155.8	12010.00
20	42839.81	145.86	0.880	0.30(0.28)	0.95	60469.5	10210.00
21	38857.39	172.02	0.812	0.30(0.28)	0.95	61202.2	10100.00
TOTAL AREA(ACRES) =						61202.2	

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 49717.53 Tc(MIN.) = 95.559
 EFFECTIVE AREA(ACRES) = 44831.52 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 61202.2
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118710.93 FEET.

FLOW PROCESS FROM NODE 13402.00 TO NODE 13404.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 209.00 DOWNSTREAM(FEET) = 207.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 395.35 CHANNEL SLOPE = 0.0051
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 11.97
 CHANNEL FLOW THRU SUBAREA(CFS) = 49717.53
 FLOW VELOCITY(FEET/SEC.) = 15.98 FLOW DEPTH(FEET) = 11.97
 TRAVEL TIME(MIN.) = 0.41 Tc(MIN.) = 95.97
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119106.28 FEET.

 FLOW PROCESS FROM NODE 13404.00 TO NODE 13404.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P506XXCE.DNA **HZ-506**
 MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	92.51	17.87	0.30	(0.29)	0.97	49.5	50600.00

 TOTAL AREA (ACRES) = 49.5

 FLOW PROCESS FROM NODE 13404.00 TO NODE 13404.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27908.73	17.52	2.666	0.30 (0.24)	0.79	4665.4	50500.00
2	29081.62	21.14	2.340	0.30 (0.24)	0.79	5627.0	203.00
3	30726.90	25.16	2.084	0.30 (0.24)	0.79	6975.1	50110.00
4	33874.03	33.26	1.786	0.30 (0.24)	0.81	10486.2	150.00
5	35156.83	36.85	1.694	0.30 (0.25)	0.82	12157.0	50260.00
6	37053.07	42.90	1.550	0.30 (0.25)	0.85	15140.8	31100.00
7	40790.64	58.46	1.303	0.30 (0.27)	0.88	22773.0	13100.00
8	42466.01	64.81	1.254	0.30 (0.27)	0.89	25585.7	11801.00
9	45062.09	74.18	1.191	0.30 (0.27)	0.91	30365.7	11530.00
10	47714.60	84.77	1.119	0.30 (0.28)	0.92	37205.2	13010.00
11	48926.41	89.66	1.086	0.30 (0.28)	0.93	40400.5	11330.00
12	49717.53	95.97	1.057	0.30 (0.28)	0.93	44831.5	11130.00
13	49310.90	103.57	1.022	0.30 (0.28)	0.94	48825.5	12330.00
14	48822.46	110.22	0.992	0.30 (0.28)	0.94	52168.7	12400.00
15	47970.48	118.91	0.952	0.30 (0.28)	0.94	55537.4	12201.00
16	47385.56	122.88	0.940	0.30 (0.28)	0.94	56622.1	12111.00
17	46609.87	128.27	0.926	0.30 (0.28)	0.95	57991.6	12101.10
18	45988.32	132.31	0.915	0.30 (0.28)	0.95	58840.7	10400.00
19	44265.21	140.38	0.894	0.30 (0.28)	0.95	60155.8	12010.00
20	42839.81	146.29	0.879	0.30 (0.28)	0.95	60469.5	10210.00
21	38857.39	172.47	0.811	0.30 (0.28)	0.95	61202.2	10100.00

 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119106.28 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	92.51	17.87	2.631	0.30 (0.29)	0.97	49.5	50600.00

 LONGEST FLOWPATH FROM NODE 50600.00 TO NODE 13404.00 = 4378.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28000.81	17.52	2.666	0.30 (0.24)	0.79	4713.9	50500.00
2	28114.05	17.87	2.631	0.30 (0.24)	0.79	4807.4	50600.00
3	29162.62	21.14	2.340	0.30 (0.24)	0.79	5676.5	203.00
4	30797.81	25.16	2.084	0.30 (0.24)	0.79	7024.6	50110.00
5	33933.15	33.26	1.786	0.30 (0.24)	0.81	10535.7	150.00
6	35212.32	36.85	1.694	0.30 (0.25)	0.82	12206.5	50260.00
7	37102.89	42.90	1.550	0.30 (0.25)	0.85	15190.3	31100.00
8	40830.70	58.46	1.303	0.30 (0.27)	0.88	22822.5	13100.00
9	42504.10	64.81	1.254	0.30 (0.27)	0.89	25635.2	11801.00
10	45097.69	74.18	1.191	0.30 (0.27)	0.91	30415.2	11530.00
11	47747.39	84.77	1.119	0.30 (0.28)	0.92	37254.7	13010.00
12	48957.89	89.66	1.086	0.30 (0.28)	0.93	40450.0	11330.00
13	49747.84	95.97	1.057	0.30 (0.28)	0.93	44881.0	11130.00
14	49339.85	103.57	1.022	0.30 (0.28)	0.94	48875.0	12330.00
15	48850.21	110.22	0.992	0.30 (0.28)	0.94	52218.2	12400.00
16	47996.65	118.91	0.952	0.30 (0.28)	0.94	55586.9	12201.00
17	47411.24	122.88	0.940	0.30 (0.28)	0.94	56671.6	12111.00
18	46635.00	128.27	0.926	0.30 (0.28)	0.95	58041.1	12101.10
19	46013.03	132.31	0.915	0.30 (0.28)	0.95	58890.2	10400.00
20	44289.10	140.38	0.894	0.30 (0.28)	0.95	60205.3	12010.00
21	42863.09	146.29	0.879	0.30 (0.28)	0.95	60519.0	10210.00
22	38877.98	172.47	0.811	0.30 (0.28)	0.95	61251.7	10100.00

 TOTAL AREA (ACRES) = 61251.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 49747.84 Tc(MIN.) = 95.971
 EFFECTIVE AREA(ACRES) = 44881.02 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 61251.7
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119106.28 FEET.

 FLOW PROCESS FROM NODE 13404.00 TO NODE 13406.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 207.00 DOWNSTREAM(FEET) = 195.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1601.97 CHANNEL SLOPE = 0.0075
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 10.73
 CHANNEL FLOW THRU SUBAREA(CFS) = 49747.84
 FLOW VELOCITY(FEET/SEC.) = 18.27 FLOW DEPTH(FEET) = 10.73
 TRAVEL TIME(MIN.) = 1.46 Tc(MIN.) = 97.43
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13406.00 = 120708.25 FEET.

 FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 97.43 **HZ-209**
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.050
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/	SCS SOIL	AREA	Fp	Ap	SCS
-------------------	----------	------	----	----	-----

LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

NATURAL FAIR COVER
"GRASS" B 0.20 0.30 1.000 69

NATURAL FAIR COVER
"GRASS" B 4.00 0.30 1.000 69

NATURAL FAIR COVER
"GRASS" B 2.00 0.30 1.000 69

NATURAL FAIR COVER
"OPEN BRUSH" B 9.70 0.30 1.000 66

NATURAL FAIR COVER
"OPEN BRUSH" B 2.60 0.30 1.000 66

AGRICULTURAL POOR COVER
"ROW CROPS, STRAIGHT ROW" B 1.60 0.30 1.000 81

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 20.10 SUBAREA RUNOFF (CFS) = 13.57
EFFECTIVE AREA (ACRES) = 44901.12 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA (ACRES) = 61271.8 PEAK FLOW RATE (CFS) = 49747.84
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 97.43 **HZ-209**

* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.050

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "ROW CROPS, STRAIGHT ROW"	B	2.00	0.30	1.000	81
NATURAL FAIR COVER "WOODLAND, GRASS"	B	7.10	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND, GRASS"	B	5.80	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.10	0.30	1.000	65

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 15.00 SUBAREA RUNOFF (CFS) = 10.13
EFFECTIVE AREA (ACRES) = 44916.12 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA (ACRES) = 61286.8 PEAK FLOW RATE (CFS) = 49747.84
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13406.00 TO NODE 13408.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 195.00 DOWNSTREAM (FEET) = 182.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 2458.36 CHANNEL SLOPE = 0.0053
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 11.83

* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.039 **S36-56.5**

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	7.00	0.30	1.000	66
NATURAL FAIR COVER "WOODLAND, GRASS"	B	3.30	0.30	1.000	65
COMMERCIAL	B	0.40	0.30	0.100	56
NATURAL FAIR COVER "OPEN BRUSH"	B	1.40	0.30	1.000	66
COMMERCIAL	B	0.30	0.30	0.100	56

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.949
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 49752.05
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 16.23
AVERAGE FLOW DEPTH (FEET) = 11.83 TRAVEL TIME (MIN.) = 2.52
Tc (MIN.) = 99.96
SUBAREA AREA (ACRES) = 12.40 SUBAREA RUNOFF (CFS) = 8.41
EFFECTIVE AREA (ACRES) = 44928.52 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA (ACRES) = 61299.2 PEAK FLOW RATE (CFS) = 49747.84
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 11.83

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 11.83 FLOW VELOCITY (FEET/SEC.) = 16.23
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123166.61 FEET.

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 2P00EVBB.DNA **S34.2**
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	842.59	9.80	0.30 (0.11)	0.38	246.8	429.00
2	890.71	11.26	0.30 (0.11)	0.38	283.5	425.00
3	905.71	11.71	0.30 (0.11)	0.38	294.8	400.00
4	943.25	13.11	0.30 (0.11)	0.38	330.1	300.00
5	1001.68	18.01	0.30 (0.11)	0.38	440.3	210.00
6	980.97	20.12	0.30 (0.11)	0.38	468.0	410.00
7	972.01	21.00	0.30 (0.11)	0.38	479.3	200.00
8	969.62	21.61	0.30 (0.11)	0.38	486.7	230.00
9	947.95	22.69	0.30 (0.11)	0.37	491.2	220.50
TOTAL AREA (ACRES) =			491.2			

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Rows 1-22 and summary row.

** MEMORY BANK # 1 CONFLUENCE DATA **

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Rows 1-9 and summary row.

** PEAK FLOW RATE TABLE **

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Rows 1-9.

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Rows 10-31 and summary row.

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 50160.56 Tc(MIN.) = 99.957
EFFECTIVE AREA(ACRES) = 45419.72 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.76
TOTAL AREA(ACRES) = 61790.4
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123166.61 FEET.

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P507XXCE.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Rows 1 and summary row.

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE.

1 22800.07 9.80 3.857 0.30 (0.22) 0.75 2336.4 429.00
2 24052.88 11.26 3.559 0.30 (0.22) 0.75 2685.6 425.00
3 24436.31 11.71 3.483 0.30 (0.22) 0.75 2792.2 400.00
4 25353.95 13.11 3.245 0.30 (0.22) 0.75 3125.6 300.00
5 27525.22 18.01 2.616 0.30 (0.22) 0.75 4280.6 210.00
6 27981.04 20.12 2.406 0.30 (0.22) 0.75 4757.5 410.00
7 28418.07 21.00 2.349 0.30 (0.22) 0.75 4957.1 200.00
8 28689.44 21.61 2.309 0.30 (0.23) 0.75 5095.5 230.00
9 28956.07 22.33 2.263 0.30 (0.23) 0.75 5251.1 50500.00
10 29062.46 22.67 2.241 0.30 (0.23) 0.75 5346.0 50600.00
11 29069.55 22.69 2.240 0.30 (0.23) 0.75 5352.4 220.50
12 30026.94 25.88 2.052 0.30 (0.23) 0.76 6215.2 203.00
13 31584.32 29.81 1.877 0.30 (0.23) 0.76 7563.3 50110.00
14 34627.35 37.77 1.670 0.30 (0.24) 0.79 11074.4 150.00
15 35868.52 41.30 1.585 0.30 (0.24) 0.80 12745.2 50260.00
16 37701.55 47.28 1.456 0.30 (0.25) 0.83 15729.0 31100.00
17 41345.57 62.71 1.268 0.30 (0.26) 0.87 23361.2 13100.00
18 43000.09 69.00 1.225 0.30 (0.27) 0.88 26173.9 11801.00
19 45565.79 78.30 1.163 0.30 (0.27) 0.90 30953.9 11530.00
20 48183.94 88.81 1.092 0.30 (0.27) 0.91 37793.4 13010.00
21 49383.40 93.67 1.067 0.30 (0.28) 0.92 40988.7 11330.00
22 50160.56 99.96 1.039 0.30 (0.28) 0.93 45419.7 11130.00
23 49737.08 107.57 1.004 0.30 (0.28) 0.93 49413.7 12330.00
24 49233.88 114.23 0.973 0.30 (0.28) 0.94 52756.9 12400.00
25 48365.17 122.94 0.939 0.30 (0.28) 0.94 56125.6 12201.00
26 47775.14 126.93 0.929 0.30 (0.28) 0.94 57210.3 12111.00
27 46992.62 132.34 0.915 0.30 (0.28) 0.94 58579.8 12101.10
28 46365.96 136.40 0.904 0.30 (0.28) 0.94 59428.9 10400.00
29 44632.61 144.52 0.883 0.30 (0.28) 0.94 60744.0 12010.00
30 43199.71 150.47 0.868 0.30 (0.28) 0.94 61057.7 10210.00
31 39184.12 176.78 0.799 0.30 (0.28) 0.94 61790.4 10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123166.61 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	374.22	22.05	2.281	0.30 (0.30)	0.99	231.4	50700.00

LONGEST FLOWPATH FROM NODE 50700.00 TO NODE 13408.00 = 7683.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23098.46	9.80	3.857	0.30 (0.23)	0.76	2439.2	429.00
2	24367.17	11.26	3.559	0.30 (0.23)	0.76	2803.8	425.00
3	24755.47	11.71	3.483	0.30 (0.23)	0.76	2915.1	400.00
4	25684.55	13.11	3.245	0.30 (0.23)	0.76	3263.1	300.00
5	27882.53	18.01	2.616	0.30 (0.23)	0.76	4469.6	210.00
6	28343.86	20.12	2.406	0.30 (0.23)	0.76	4968.6	410.00
7	28786.60	21.00	2.349	0.30 (0.23)	0.76	5177.5	200.00
8	29061.44	21.61	2.309	0.30 (0.23)	0.76	5322.3	230.00
9	29226.82	22.05	2.281	0.30 (0.23)	0.76	5422.1	50700.00
10	29326.92	22.33	2.263	0.30 (0.23)	0.76	5482.5	50500.00
11	29429.17	22.67	2.241	0.30 (0.23)	0.76	5577.4	50600.00
12	29435.98	22.69	2.240	0.30 (0.23)	0.76	5583.8	220.50
13	30357.98	25.88	2.052	0.30 (0.23)	0.76	6446.6	203.00
14	31882.43	29.81	1.877	0.30 (0.23)	0.77	7794.7	50110.00
15	34886.41	37.77	1.670	0.30 (0.24)	0.79	11305.8	150.00
16	36111.50	41.30	1.585	0.30 (0.24)	0.81	12976.6	50260.00

17 37920.17 47.28 1.456 0.30 (0.25) 0.84 15960.4 31100.00
18 41528.74 62.71 1.268 0.30 (0.26) 0.87 23592.6 13100.00
19 43175.27 69.00 1.225 0.30 (0.27) 0.89 26405.3 11801.00
20 45729.16 78.30 1.163 0.30 (0.27) 0.90 31185.3 11530.00
21 48333.96 88.81 1.092 0.30 (0.27) 0.91 38024.8 13010.00
22 49528.76 93.67 1.067 0.30 (0.28) 0.92 41220.1 11330.00
23 50300.50 99.96 1.039 0.30 (0.28) 0.93 45651.1 11130.00
24 49870.47 107.57 1.004 0.30 (0.28) 0.93 49645.1 12330.00
25 49361.53 114.23 0.973 0.30 (0.28) 0.94 52988.3 12400.00
26 48486.41 122.94 0.939 0.30 (0.28) 0.94 56357.0 12201.00
27 47894.42 126.93 0.929 0.30 (0.28) 0.94 57441.7 12111.00
28 47109.26 132.34 0.915 0.30 (0.28) 0.94 58811.2 12101.10
29 46480.60 136.40 0.904 0.30 (0.28) 0.94 59660.3 10400.00
30 44743.27 144.52 0.883 0.30 (0.28) 0.94 60975.4 12010.00
31 43307.45 150.47 0.868 0.30 (0.28) 0.94 61289.1 10210.00
32 39278.96 176.78 0.799 0.30 (0.28) 0.94 62021.8 10100.00

TOTAL AREA (ACRES) = 62021.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 50300.50 Tc (MIN.) = 99.957
EFFECTIVE AREA (ACRES) = 45651.12 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA (ACRES) = 62021.8
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123166.61 FEET.

FLOW PROCESS FROM NODE 13408.00 TO NODE 13410.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 182.00 DOWNSTREAM (FEET) = 178.72

CHANNEL LENGTH THRU SUBAREA (FEET) = 952.73 CHANNEL SLOPE = 0.0034

GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT (FEET) = 13.41

S36-86.6

* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.033

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.40	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	2.90	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 50301.59

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 14.05

AVERAGE FLOW DEPTH (FEET) = 13.41 TRAVEL TIME (MIN.) = 1.13

Tc (MIN.) = 101.09

SUBAREA AREA (ACRES) = 3.30 SUBAREA RUNOFF (CFS) = 2.18

EFFECTIVE AREA (ACRES) = 45654.42 AREA-AVERAGED Fm (INCH/HR) = 0.28

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA (ACRES) = 62025.1 PEAK FLOW RATE (CFS) = 50300.50

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT (FEET) = 13.40

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 13.40 FLOW VELOCITY(FEET/SEC.) = 14.06
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124119.34 FEET.

 FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<<

 FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<<

PEAK FLOWRATE TABLE FILE NAME: RU00EV36.DNA
 MEMORY BANK # 3 DEFINED AS FOLLOWS:

S36

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2775.64	27.02	0.30 (0.27)	0.90	1487.3	110.00
2	2878.61	29.40	0.30 (0.27)	0.90	1661.9	100.00
3	2888.47	30.54	0.30 (0.27)	0.90	1737.8	100.00
4	2912.70	33.54	0.30 (0.27)	0.91	1918.1	130.00
5	3088.56	46.09	0.30 (0.28)	0.93	2647.7	20100.00
6	3029.46	51.26	0.30 (0.28)	0.93	2828.9	13600.00
7	2905.42	85.17	0.30 (0.28)	0.93	3796.8	13510.00
8	2757.26	93.58	0.30 (0.28)	0.93	3859.7	13500.00
TOTAL AREA (ACRES) =						3859.7

 FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23098.46	11.25	3.562	0.30 (0.23)	0.76	2442.5	429.00
2	24367.17	12.69	3.317	0.30 (0.23)	0.76	2807.1	425.00
3	24755.47	13.13	3.242	0.30 (0.23)	0.76	2918.4	400.00
4	25684.55	14.51	3.007	0.30 (0.23)	0.76	3266.4	300.00
5	27882.53	19.37	2.477	0.30 (0.23)	0.76	4472.9	210.00
6	28343.86	21.47	2.318	0.30 (0.23)	0.76	4971.9	410.00
7	28786.60	22.35	2.262	0.30 (0.23)	0.76	5180.8	200.00
8	29061.44	22.96	2.223	0.30 (0.23)	0.76	5325.6	230.00
9	29226.82	23.39	2.194	0.30 (0.23)	0.76	5425.4	50700.00
10	29326.92	23.67	2.177	0.30 (0.23)	0.76	5485.8	50500.00
11	29429.17	24.01	2.155	0.30 (0.23)	0.76	5580.7	50600.00
12	29435.98	24.03	2.153	0.30 (0.23)	0.76	5587.1	220.50
13	30357.98	27.21	1.993	0.30 (0.23)	0.76	6449.9	203.00
14	31882.43	31.12	1.840	0.30 (0.23)	0.77	7798.0	50110.00
15	34886.41	39.03	1.638	0.30 (0.24)	0.79	11309.1	150.00
16	36111.50	42.56	1.558	0.30 (0.24)	0.81	12979.9	50260.00
17	37920.17	48.51	1.429	0.30 (0.25)	0.84	15963.7	31100.00
18	41528.74	63.91	1.260	0.30 (0.26)	0.87	23595.9	13100.00
19	43175.27	70.19	1.217	0.30 (0.27)	0.89	26408.6	11801.00

20	45729.16	79.46	1.155	0.30 (0.27)	0.90	31188.6	11530.00
21	48333.96	89.95	1.084	0.30 (0.27)	0.91	38028.1	13010.00
22	49528.76	94.81	1.062	0.30 (0.28)	0.92	41223.4	11330.00
23	50300.50	101.09	1.033	0.30 (0.28)	0.93	45654.4	11130.00
24	49870.47	108.70	0.999	0.30 (0.28)	0.93	49648.4	12330.00
25	49361.53	115.36	0.968	0.30 (0.28)	0.94	52991.6	12400.00
26	48486.41	124.08	0.936	0.30 (0.28)	0.94	56360.3	12201.00
27	47894.42	128.08	0.926	0.30 (0.28)	0.94	57445.0	12111.00
28	47109.26	133.49	0.912	0.30 (0.28)	0.94	58814.5	12101.10
29	46480.60	137.56	0.901	0.30 (0.28)	0.94	59663.6	10400.00
30	44743.27	145.69	0.880	0.30 (0.28)	0.94	60978.7	12010.00
31	43307.45	151.65	0.865	0.30 (0.28)	0.94	61292.4	10210.00
32	39278.96	178.00	0.796	0.30 (0.28)	0.94	62025.1	10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 =						124119.34 FEET.	

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2775.64	27.02	2.001	0.30 (0.27)	0.90	1487.3	110.00
2	2878.61	29.40	1.896	0.30 (0.27)	0.90	1661.9	100.00
3	2888.47	30.54	1.855	0.30 (0.27)	0.90	1737.8	100.00
4	2912.70	33.54	1.778	0.30 (0.27)	0.91	1918.1	130.00
5	3088.56	46.09	1.481	0.30 (0.28)	0.93	2647.7	20100.00
6	3029.46	51.26	1.383	0.30 (0.28)	0.93	2828.9	13600.00
7	2905.42	85.17	1.117	0.30 (0.28)	0.93	3796.8	13510.00
8	2757.26	93.58	1.068	0.30 (0.28)	0.93	3859.7	13500.00
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13410.00 =						41710.10 FEET.	

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25295.94	11.25	3.562	0.30 (0.24)	0.79	3061.7	429.00
2	26661.53	12.69	3.317	0.30 (0.24)	0.79	3505.5	425.00
3	27071.07	13.13	3.242	0.30 (0.24)	0.79	3641.0	400.00
4	28041.52	14.51	3.007	0.30 (0.24)	0.79	4065.0	300.00
5	30419.68	19.37	2.477	0.30 (0.24)	0.79	5539.1	210.00
6	30953.39	21.47	2.318	0.30 (0.24)	0.79	6153.6	410.00
7	31427.79	22.35	2.262	0.30 (0.24)	0.79	6410.7	200.00
8	31721.16	22.96	2.223	0.30 (0.24)	0.79	6589.1	230.00
9	31898.07	23.39	2.194	0.30 (0.24)	0.79	6713.0	50700.00
10	32004.72	23.67	2.177	0.30 (0.24)	0.79	6788.6	50500.00
11	32114.22	24.01	2.155	0.30 (0.24)	0.79	6902.2	50600.00
12	32121.49	24.03	2.153	0.30 (0.24)	0.79	6909.8	220.50
13	33079.97	27.02	2.001	0.30 (0.24)	0.79	7887.0	110.00
14	33141.62	27.21	1.993	0.30 (0.24)	0.79	7950.8	203.00
15	34090.12	29.40	1.896	0.30 (0.24)	0.79	8866.6	100.00
16	34546.48	30.54	1.855	0.30 (0.24)	0.79	9337.3	100.00
17	34775.55	31.12	1.840	0.30 (0.24)	0.79	9570.4	50110.00
18	35714.63	33.54	1.778	0.30 (0.24)	0.80	10790.8	130.00
19	37876.10	39.03	1.638	0.30 (0.24)	0.81	13546.7	150.00
20	39150.53	42.56	1.558	0.30 (0.25)	0.82	15422.2	50260.00
21	40272.32	46.09	1.481	0.30 (0.25)	0.84	17396.6	20100.00
22	40981.00	48.51	1.429	0.30 (0.25)	0.85	18696.4	31100.00
23	41592.98	51.26	1.383	0.30 (0.26)	0.86	20153.3	13600.00
24	44511.94	63.91	1.260	0.30 (0.26)	0.88	26785.8	13100.00
25	46135.50	70.19	1.217	0.30 (0.27)	0.89	29777.8	11801.00
26	48655.47	79.46	1.155	0.30 (0.27)	0.90	34822.4	11530.00
27	50052.01	85.17	1.117	0.30 (0.27)	0.91	38707.2	13510.00

28 51155.16 89.95 1.084 0.30(0.27) 0.92 41860.7 13010.00
29 51985.27 93.58 1.068 0.30(0.28) 0.92 44278.8 13500.00
30 52266.48 94.81 1.062 0.30(0.28) 0.92 45083.1 11330.00
31 52937.81 101.09 1.033 0.30(0.28) 0.93 49514.1 11130.00
32 52386.08 108.70 0.999 0.30(0.28) 0.93 53508.1 12330.00
33 51770.58 115.36 0.968 0.30(0.28) 0.94 56851.2 12400.00
34 50784.20 124.08 0.936 0.30(0.28) 0.94 60220.0 12201.00
35 50155.83 128.08 0.926 0.30(0.28) 0.94 61304.7 12111.00
36 49321.41 133.49 0.912 0.30(0.28) 0.94 62674.2 12101.10
37 48655.75 137.56 0.901 0.30(0.28) 0.94 63523.2 10400.00
38 46844.39 145.69 0.880 0.30(0.28) 0.94 64838.4 12010.00
39 45354.29 151.65 0.865 0.30(0.28) 0.94 65152.1 10210.00
40 41085.98 178.00 0.796 0.30(0.28) 0.94 65884.8 10100.00
TOTAL AREA (ACRES) = 65884.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 52937.81 Tc(MIN.) = 101.087
EFFECTIVE AREA(ACRES) = 49514.10 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.86
TOTAL AREA(ACRES) = 65884.8
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124119.34 FEET.

FLOW PROCESS FROM NODE 13410.00 TO NODE 13412.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 178.72 DOWNSTREAM(FEET) = 176.93
CHANNEL LENGTH THRU SUBAREA(FEET) = 169.78 CHANNEL SLOPE = 0.0105
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 10.10
CHANNEL FLOW THRU SUBAREA(CFS) = 52937.81
FLOW VELOCITY(FEET/SEC.) = 20.93 FLOW DEPTH(FEET) = 10.10
TRAVEL TIME(MIN.) = 0.14 Tc(MIN.) = 101.22
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124289.12 FEET.

FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506101b.DNA

HZ-101

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	683.96	36.50	0.30(0.30)	0.98	591.0	10100.00
TOTAL AREA(ACRES) =						591.0

FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 25295.94 11.42 3.532 0.30(0.24) 0.79 3061.7 429.00
2 26661.53 12.86 3.288 0.30(0.24) 0.79 3505.5 425.00
3 27071.07 13.30 3.213 0.30(0.24) 0.79 3641.0 400.00
4 28041.52 14.68 2.979 0.30(0.24) 0.79 4065.0 300.00
5 30419.68 19.53 2.461 0.30(0.24) 0.79 5539.1 210.00
6 30953.39 21.63 2.308 0.30(0.24) 0.79 6153.6 410.00
7 31427.79 22.51 2.251 0.30(0.24) 0.79 6410.7 200.00
8 31721.16 23.12 2.212 0.30(0.24) 0.79 6589.1 230.00
9 31898.07 23.55 2.184 0.30(0.24) 0.79 6713.0 50700.00
10 32004.72 23.83 2.166 0.30(0.24) 0.79 6788.6 50500.00
11 32114.22 24.17 2.144 0.30(0.24) 0.79 6902.2 50600.00
12 32121.49 24.19 2.143 0.30(0.24) 0.79 6909.8 220.50
13 33079.97 27.18 1.994 0.30(0.24) 0.79 7887.0 110.00
14 33141.62 27.36 1.986 0.30(0.24) 0.79 7950.8 203.00
15 34090.12 29.55 1.889 0.30(0.24) 0.79 8866.6 100.00
16 34546.48 30.70 1.851 0.30(0.24) 0.79 9337.3 100.00
17 34775.55 31.27 1.836 0.30(0.24) 0.79 9570.4 50110.00
18 35714.63 33.70 1.774 0.30(0.24) 0.80 10790.8 130.00
19 37876.10 39.19 1.634 0.30(0.24) 0.81 13546.7 150.00
20 39150.53 42.70 1.555 0.30(0.25) 0.82 15422.2 50260.00
21 40272.32 46.24 1.478 0.30(0.25) 0.84 17396.6 20100.00
22 40981.00 48.66 1.426 0.30(0.25) 0.85 18696.4 31100.00
23 41592.98 51.41 1.381 0.30(0.26) 0.86 20153.3 13600.00
24 44511.94 64.05 1.259 0.30(0.26) 0.88 26785.8 13100.00
25 46135.50 70.33 1.216 0.30(0.27) 0.89 29777.8 11801.00
26 48655.47 79.60 1.154 0.30(0.27) 0.90 34822.4 11530.00
27 50052.01 85.31 1.116 0.30(0.27) 0.91 38707.2 13510.00
28 51155.16 90.09 1.084 0.30(0.27) 0.92 41860.7 13010.00
29 51985.27 93.72 1.067 0.30(0.28) 0.92 44278.8 13500.00
30 52266.48 94.94 1.061 0.30(0.28) 0.92 45083.1 11330.00
31 52937.81 101.22 1.033 0.30(0.28) 0.93 49514.1 11130.00
32 52386.08 108.84 0.998 0.30(0.28) 0.93 53508.1 12330.00
33 51770.58 115.50 0.968 0.30(0.28) 0.94 56851.2 12400.00
34 50784.20 124.22 0.936 0.30(0.28) 0.94 60220.0 12201.00
35 50155.83 128.22 0.926 0.30(0.28) 0.94 61304.7 12111.00
36 49321.41 133.63 0.912 0.30(0.28) 0.94 62674.2 12101.10
37 48655.75 137.69 0.901 0.30(0.28) 0.94 63523.2 10400.00
38 46844.39 145.83 0.880 0.30(0.28) 0.94 64838.4 12010.00
39 45354.29 151.79 0.864 0.30(0.28) 0.94 65152.1 10210.00
40 41085.98 178.15 0.796 0.30(0.28) 0.94 65884.8 10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124289.12 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	683.96	36.50	1.703	0.30(0.30)	0.98	591.0	10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 =							14677.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
---------------	---------	-----------	---------------------	------------------	----	------------	----------------

```

1 25788.17 11.42 3.532 0.30( 0.24) 0.80 3246.6 429.00
2 27173.87 12.86 3.288 0.30( 0.24) 0.80 3713.7 425.00
3 27587.69 13.30 3.213 0.30( 0.24) 0.80 3856.3 400.00
4 28565.90 14.68 2.979 0.30( 0.24) 0.80 4302.6 300.00
5 30982.83 19.53 2.461 0.30( 0.24) 0.80 5855.4 210.00
6 31533.05 21.63 2.308 0.30( 0.24) 0.80 6503.8 410.00
7 32014.01 22.51 2.251 0.30( 0.24) 0.80 6775.2 200.00
8 32311.18 23.12 2.212 0.30( 0.24) 0.80 6963.4 230.00
9 32490.41 23.55 2.184 0.30( 0.24) 0.80 7094.3 50700.00
10 32598.36 23.83 2.166 0.30( 0.24) 0.80 7174.4 50500.00
11 32709.29 24.17 2.144 0.30( 0.24) 0.80 7293.5 50600.00
12 32716.64 24.19 2.143 0.30( 0.24) 0.80 7301.4 220.50
13 33694.79 27.18 1.994 0.30( 0.24) 0.80 8327.1 110.00
14 33757.62 27.36 1.986 0.30( 0.24) 0.80 8393.8 203.00
15 34717.16 29.55 1.889 0.30( 0.24) 0.80 9345.1 100.00
16 35182.41 30.70 1.851 0.30( 0.24) 0.80 9834.3 100.00
17 35417.26 31.27 1.836 0.30( 0.24) 0.80 10076.7 50110.00
18 36378.22 33.70 1.774 0.30( 0.24) 0.81 11336.4 130.00
19 37504.14 36.50 1.703 0.30( 0.24) 0.82 12791.4 10100.00
20 38526.70 39.19 1.634 0.30( 0.25) 0.82 14137.7 150.00
21 39762.61 42.70 1.555 0.30( 0.25) 0.83 16013.2 50260.00
22 40847.33 46.24 1.478 0.30( 0.25) 0.84 17987.6 20100.00
23 41530.54 48.66 1.426 0.30( 0.26) 0.85 19287.4 31100.00
24 42120.90 51.41 1.381 0.30( 0.26) 0.86 20744.3 13600.00
25 44980.25 64.05 1.259 0.30( 0.27) 0.88 27376.8 13100.00
26 46583.26 70.33 1.216 0.30( 0.27) 0.89 30368.8 11801.00
27 49072.90 79.60 1.154 0.30( 0.27) 0.90 35413.4 11530.00
28 50450.76 85.31 1.116 0.30( 0.27) 0.91 39298.2 13510.00
29 51538.36 90.09 1.084 0.30( 0.27) 0.92 42451.7 13010.00
30 52360.41 93.72 1.067 0.30( 0.28) 0.92 44869.8 13500.00
31 52638.92 94.94 1.061 0.30( 0.28) 0.92 45674.1 11330.00
32 53296.31 101.22 1.033 0.30( 0.28) 0.93 50105.1 11130.00
33 52727.68 108.84 0.998 0.30( 0.28) 0.93 54099.1 12330.00
34 52097.39 115.50 0.968 0.30( 0.28) 0.94 57442.2 12400.00
35 51095.69 124.22 0.936 0.30( 0.28) 0.94 60811.0 12201.00
36 50462.27 128.22 0.926 0.30( 0.28) 0.94 61895.7 12111.00
37 49621.01 133.63 0.912 0.30( 0.28) 0.94 63265.2 12101.10
38 48950.22 137.69 0.901 0.30( 0.28) 0.94 64114.2 10400.00
39 47128.59 145.83 0.880 0.30( 0.28) 0.94 65429.4 12010.00
40 45630.95 151.79 0.864 0.30( 0.28) 0.94 65743.1 10210.00
41 41329.34 178.15 0.796 0.30( 0.28) 0.94 66475.8 10100.00
TOTAL AREA (ACRES) = 66475.8

```

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 53296.31 Tc(MIN.) = 101.222
EFFECTIVE AREA(ACRES) = 50105.10 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 66475.8
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124289.12 FEET.

FLOW PROCESS FROM NODE 13412.00 TO NODE 13700.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 176.93 DOWNSTREAM(FEET) = 170.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 260.10 CHANNEL SLOPE = 0.0266

GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 7.79
CHANNEL FLOW THRU SUBAREA(CFS) = 53296.31
FLOW VELOCITY(FEET/SEC.) = 28.62 FLOW DEPTH(FEET) = 7.79
TRAVEL TIME(MIN.) = 0.15 Tc(MIN.) = 101.37
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124549.22 FEET.

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: P508XXCE.DNA HZ-508
MEMORY BANK # 2 DEFINED AS FOLLOWS:
STREAM Q Tc Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (ACRES) NODE
1 213.71 21.83 0.30(0.30) 0.99 131.3 50800.00
TOTAL AREA(ACRES) = 131.3

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25788.17	11.62	3.499	0.30(0.24)	0.80	3246.6	429.00
2	27173.87	13.05	3.256	0.30(0.24)	0.80	3713.7	425.00
3	27587.69	13.49	3.181	0.30(0.24)	0.80	3856.3	400.00
4	28565.90	14.86	2.947	0.30(0.24)	0.80	4302.6	300.00
5	30982.83	19.72	2.442	0.30(0.24)	0.80	5855.4	210.00
6	31533.05	21.81	2.296	0.30(0.24)	0.80	6503.8	410.00
7	32014.01	22.69	2.240	0.30(0.24)	0.80	6775.2	200.00
8	32311.18	23.30	2.201	0.30(0.24)	0.80	6963.4	230.00
9	32490.41	23.73	2.173	0.30(0.24)	0.80	7094.3	50700.00
10	32598.36	24.01	2.155	0.30(0.24)	0.80	7174.4	50500.00
11	32709.29	24.35	2.133	0.30(0.24)	0.80	7293.5	50600.00
12	32716.64	24.37	2.132	0.30(0.24)	0.80	7301.4	220.50
13	33694.79	27.36	1.986	0.30(0.24)	0.80	8327.1	110.00
14	33757.62	27.54	1.978	0.30(0.24)	0.80	8393.8	203.00
15	34717.16	29.73	1.881	0.30(0.24)	0.80	9345.1	100.00
16	35182.41	30.87	1.847	0.30(0.24)	0.80	9834.3	100.00
17	35417.26	31.45	1.832	0.30(0.24)	0.80	10076.7	50110.00
18	36378.22	33.87	1.770	0.30(0.24)	0.81	11336.4	130.00
19	37504.14	36.67	1.698	0.30(0.24)	0.82	12791.4	10100.00
20	38526.70	39.35	1.630	0.30(0.25)	0.82	14137.7	150.00
21	39762.61	42.87	1.551	0.30(0.25)	0.83	16013.2	50260.00
22	40847.33	46.40	1.475	0.30(0.25)	0.84	17987.6	20100.00
23	41530.54	48.83	1.422	0.30(0.26)	0.85	19287.4	31100.00

24	42120.90	51.57	1.380	0.30 (0.26)	0.86	20744.3	13600.00
25	44980.25	64.21	1.258	0.30 (0.27)	0.88	27376.8	13100.00
26	46583.26	70.49	1.215	0.30 (0.27)	0.89	30368.8	11801.00
27	49072.90	79.76	1.153	0.30 (0.27)	0.90	35413.4	11530.00
28	50450.76	85.46	1.115	0.30 (0.27)	0.91	39298.2	13510.00
29	51538.36	90.24	1.083	0.30 (0.27)	0.92	42451.7	13010.00
30	52360.41	93.87	1.066	0.30 (0.28)	0.92	44869.8	13500.00
31	52638.92	95.09	1.061	0.30 (0.28)	0.92	45674.1	11330.00
32	53296.31	101.37	1.032	0.30 (0.28)	0.93	50105.1	11130.00
33	52727.68	108.99	0.997	0.30 (0.28)	0.93	54099.1	12330.00
34	52097.39	115.65	0.967	0.30 (0.28)	0.94	57442.2	12400.00
35	51095.69	124.37	0.936	0.30 (0.28)	0.94	60811.0	12201.00
36	50462.27	128.37	0.925	0.30 (0.28)	0.94	61895.7	12111.00
37	49621.01	133.78	0.911	0.30 (0.28)	0.94	63265.2	12101.10
38	48950.22	137.85	0.901	0.30 (0.28)	0.94	64114.2	10400.00
39	47128.59	145.99	0.879	0.30 (0.28)	0.94	65429.4	12010.00
40	45630.95	151.95	0.864	0.30 (0.28)	0.94	65743.1	10210.00
41	41329.34	178.31	0.795	0.30 (0.28)	0.94	66475.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124549.22 FEET.

**** MEMORY BANK # 2 CONFLUENCE DATA ****

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	213.71	21.83	2.295	0.30 (0.30)	0.99	131.3	50800.00

LONGEST FLOWPATH FROM NODE 50800.00 TO NODE 13700.00 = 5946.00 FEET.

**** PEAK FLOW RATE TABLE ****

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25970.41	11.62	3.499	0.30 (0.24)	0.80	3316.5	429.00
2	27363.02	13.05	3.256	0.30 (0.24)	0.80	3792.2	425.00
3	27778.26	13.49	3.181	0.30 (0.24)	0.80	3937.4	400.00
4	28758.89	14.86	2.947	0.30 (0.24)	0.80	4392.1	300.00
5	31190.04	19.72	2.442	0.30 (0.24)	0.80	5974.0	210.00
6	31746.72	21.81	2.296	0.30 (0.24)	0.80	6635.1	410.00
7	31754.26	21.83	2.295	0.30 (0.24)	0.80	6639.4	50800.00
8	32221.79	22.69	2.240	0.30 (0.24)	0.80	6906.5	200.00
9	32514.77	23.30	2.201	0.30 (0.24)	0.80	7094.7	230.00
10	32691.00	23.73	2.173	0.30 (0.24)	0.80	7225.6	50700.00
11	32797.05	24.01	2.155	0.30 (0.24)	0.80	7305.7	50500.00
12	32905.65	24.35	2.133	0.30 (0.24)	0.80	7424.8	50600.00
13	32912.84	24.37	2.132	0.30 (0.24)	0.80	7432.7	220.50
14	33875.46	27.36	1.986	0.30 (0.24)	0.80	8458.4	110.00
15	33937.43	27.54	1.978	0.30 (0.24)	0.80	8525.1	203.00
16	34886.58	29.73	1.881	0.30 (0.24)	0.80	9476.4	100.00
17	35348.15	30.87	1.847	0.30 (0.24)	0.81	9965.6	100.00
18	35581.43	31.45	1.832	0.30 (0.24)	0.81	10208.0	50110.00
19	36535.77	33.87	1.770	0.30 (0.24)	0.81	11467.7	130.00
20	37654.01	36.67	1.698	0.30 (0.24)	0.82	12922.7	10100.00
21	38669.23	39.35	1.630	0.30 (0.25)	0.82	14269.0	150.00
22	39896.74	42.87	1.551	0.30 (0.25)	0.83	16144.5	50260.00
23	40973.31	46.40	1.475	0.30 (0.25)	0.85	18118.9	20100.00
24	41650.92	48.83	1.422	0.30 (0.26)	0.85	19418.7	31100.00
25	42236.71	51.57	1.380	0.30 (0.26)	0.86	20875.6	13600.00
26	45083.02	64.21	1.258	0.30 (0.27)	0.88	27508.2	13100.00
27	46681.51	70.49	1.215	0.30 (0.27)	0.89	30500.1	11801.00
28	49164.48	79.76	1.153	0.30 (0.27)	0.90	35544.7	11530.00
29	50538.23	85.46	1.115	0.30 (0.27)	0.91	39429.5	13510.00

30	51622.45	90.24	1.083	0.30 (0.27)	0.92	42583.0	13010.00
31	52442.73	93.87	1.066	0.30 (0.28)	0.92	45001.1	13500.00
32	52720.64	95.09	1.061	0.30 (0.28)	0.92	45805.4	11330.00
33	53374.96	101.37	1.032	0.30 (0.28)	0.93	50236.4	11130.00
34	52802.61	108.99	0.997	0.30 (0.28)	0.93	54230.4	12330.00
35	52169.07	115.65	0.967	0.30 (0.28)	0.94	57573.6	12400.00
36	51164.03	124.37	0.936	0.30 (0.28)	0.94	60942.3	12201.00
37	50529.50	128.37	0.925	0.30 (0.28)	0.94	62027.0	12111.00
38	49686.74	133.78	0.911	0.30 (0.28)	0.94	63396.5	12101.10
39	49014.81	137.85	0.901	0.30 (0.28)	0.94	64245.5	10400.00
40	47190.92	145.99	0.879	0.30 (0.28)	0.94	65560.7	12010.00
41	45691.62	151.95	0.864	0.30 (0.28)	0.94	65874.4	10210.00
42	41382.69	178.31	0.795	0.30 (0.28)	0.94	66607.1	10100.00

TOTAL AREA (ACRES) = 66607.1

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 53374.96 Tc(MIN.) = 101.374
EFFECTIVE AREA(ACRES) = 50236.40 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 66607.1
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124549.22 FEET.

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 66607.1 TC(MIN.) = 101.37
EFFECTIVE AREA(ACRES) = 50236.40 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.929
PEAK FLOW RATE(CFS) = 53374.96

**** PEAK FLOW RATE TABLE ****

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25970.41	11.62	3.499	0.30 (0.24)	0.80	3316.5	429.00
2	27363.02	13.05	3.256	0.30 (0.24)	0.80	3792.2	425.00
3	27778.26	13.49	3.181	0.30 (0.24)	0.80	3937.4	400.00
4	28758.89	14.86	2.947	0.30 (0.24)	0.80	4392.1	300.00
5	31190.04	19.72	2.442	0.30 (0.24)	0.80	5974.0	210.00
6	31746.72	21.81	2.296	0.30 (0.24)	0.80	6635.1	410.00
7	31754.26	21.83	2.295	0.30 (0.24)	0.80	6639.4	50800.00
8	32221.79	22.69	2.240	0.30 (0.24)	0.80	6906.5	200.00
9	32514.77	23.30	2.201	0.30 (0.24)	0.80	7094.7	230.00
10	32691.00	23.73	2.173	0.30 (0.24)	0.80	7225.6	50700.00
11	32797.05	24.01	2.155	0.30 (0.24)	0.80	7305.7	50500.00
12	32905.65	24.35	2.133	0.30 (0.24)	0.80	7424.8	50600.00
13	32912.84	24.37	2.132	0.30 (0.24)	0.80	7432.7	220.50
14	33875.46	27.36	1.986	0.30 (0.24)	0.80	8458.4	110.00
15	33937.43	27.54	1.978	0.30 (0.24)	0.80	8525.1	203.00
16	34886.58	29.73	1.881	0.30 (0.24)	0.80	9476.4	100.00
17	35348.15	30.87	1.847	0.30 (0.24)	0.81	9965.6	100.00
18	35581.43	31.45	1.832	0.30 (0.24)	0.81	10208.0	50110.00
19	36535.77	33.87	1.770	0.30 (0.24)	0.81	11467.7	130.00
20	37654.01	36.67	1.698	0.30 (0.24)	0.82	12922.7	10100.00
21	38669.23	39.35	1.630	0.30 (0.25)	0.82	14269.0	150.00
22	39896.74	42.87	1.551	0.30 (0.25)	0.83	16144.5	50260.00
23	40973.31	46.40	1.475	0.30 (0.25)	0.85	18118.9	20100.00
24	41650.92	48.83	1.422	0.30 (0.26)	0.85	19418.7	31100.00
25	42236.71	51.57	1.380	0.30 (0.26)	0.86	20875.6	13600.00
26	45083.02	64.21	1.258	0.30 (0.27)	0.88	27508.2	13100.00
27	46681.51	70.49	1.215	0.30 (0.27)	0.89	30500.1	11801.00

28	49164.48	79.76	1.153	0.30	(0.27)	0.90	35544.7	11530.00
29	50538.23	85.46	1.115	0.30	(0.27)	0.91	39429.5	13510.00
30	51622.45	90.24	1.083	0.30	(0.27)	0.92	42583.0	13010.00
31	52442.73	93.87	1.066	0.30	(0.28)	0.92	45001.1	13500.00
32	52720.64	95.09	1.061	0.30	(0.28)	0.92	45805.4	11330.00
33	53374.96	101.37	1.032	0.30	(0.28)	0.93	50236.4	11130.00
34	52802.61	108.99	0.997	0.30	(0.28)	0.93	54230.4	12330.00
35	52169.07	115.65	0.967	0.30	(0.28)	0.94	57573.6	12400.00
36	51164.03	124.37	0.936	0.30	(0.28)	0.94	60942.3	12201.00
37	50529.50	128.37	0.925	0.30	(0.28)	0.94	62027.0	12111.00
38	49686.74	133.78	0.911	0.30	(0.28)	0.94	63396.5	12101.10
39	49014.81	137.85	0.901	0.30	(0.28)	0.94	64245.5	10400.00
40	47190.92	145.99	0.879	0.30	(0.28)	0.94	65560.7	12010.00
41	45691.62	151.95	0.864	0.30	(0.28)	0.94	65874.4	10210.00
42	41382.69	178.31	0.795	0.30	(0.28)	0.94	66607.1	10100.00

=====
=====
END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 136 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 100-YR EV OCT 2022 ROKAMOTO *

FILE NAME: RU00EV36.DAT
TIME/DATE OF STUDY: 09:57 10/06/2022

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 100.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.785
- 2) 10.00; 3.744
- 3) 15.00; 2.904
- 4) 20.00; 2.401
- 5) 25.00; 2.083
- 6) 30.00; 1.861
- 7) 40.00; 1.606
- 8) 50.00; 1.392
- 9) 60.00; 1.279
- 10) 90.00; 1.075
- 11) 120.00; 0.938
- 12) 180.00; 0.782
- 13) 360.00; 0.577
- 14) 1200.00; 0.251

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13600.00 TO NODE 13600.50 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 488.61
ELEVATION DATA: UPSTREAM(FEET) = 872.12 DOWNSTREAM(FEET) = 744.80

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 10.995
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.577
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "OPEN BRUSH"	-	3.39	0.30	1.000	65	11.00

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 10.00
TOTAL AREA(ACRES) = 3.39 PEAK FLOW RATE(CFS) = 10.00

FLOW PROCESS FROM NODE 13600.50 TO NODE 13601.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 744.80 DOWNSTREAM(FEET) = 707.32
CHANNEL LENGTH THRU SUBAREA(FEET) = 418.30 CHANNEL SLOPE = 0.0896
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.46
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.288
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.45	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 20.04
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.06
AVERAGE FLOW DEPTH(FEET) = 0.45 TRAVEL TIME(MIN.) = 1.72
Tc(MIN.) = 12.71
SUBAREA AREA(ACRES) = 7.45 SUBAREA RUNOFF(CFS) = 20.04
EFFECTIVE AREA(ACRES) = 10.84 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 10.8 PEAK FLOW RATE(CFS) = 29.15
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.56

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.56 FLOW VELOCITY(FEET/SEC.) = 4.67
LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13601.00 = 906.91 FEET.

FLOW PROCESS FROM NODE 13601.00 TO NODE 13602.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 707.32 DOWNSTREAM(FEET) = 657.12
CHANNEL LENGTH THRU SUBAREA(FEET) = 777.60 CHANNEL SLOPE = 0.0646
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.03
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.898

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.32	0.30	1.000	-
USER-DEFINED	-	4.70	0.30	1.000	-
USER-DEFINED	-	25.05	0.30	1.000	-
USER-DEFINED	-	0.45	0.30	1.000	-
USER-DEFINED	-	0.44	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 65.43

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.52

AVERAGE FLOW DEPTH(FEET) = 0.99 TRAVEL TIME(MIN.) = 2.35

Tc(MIN.) = 15.06

SUBAREA AREA(ACRES) = 30.96 SUBAREA RUNOFF(CFS) = 72.39
EFFECTIVE AREA(ACRES) = 41.80 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 41.8 PEAK FLOW RATE(CFS) = 97.74
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.25

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.25 FLOW VELOCITY(FEET/SEC.) = 6.28

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13602.00 = 1684.51 FEET.

FLOW PROCESS FROM NODE 13602.00 TO NODE 13603.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 657.12 DOWNSTREAM(FEET) = 584.58
CHANNEL LENGTH THRU SUBAREA(FEET) = 1186.54 CHANNEL SLOPE = 0.0611
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.45
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.597

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.03	0.30	1.000	-
USER-DEFINED	-	2.51	0.30	1.000	-

USER-DEFINED - 1.52 0.30 1.000 -
USER-DEFINED - 12.30 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 121.91

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.62

AVERAGE FLOW DEPTH(FEET) = 1.43 TRAVEL TIME(MIN.) = 2.99

Tc(MIN.) = 18.05

SUBAREA AREA(ACRES) = 23.36 SUBAREA RUNOFF(CFS) = 48.30
EFFECTIVE AREA(ACRES) = 65.16 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 65.2 PEAK FLOW RATE(CFS) = 134.74
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.52

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.52 FLOW VELOCITY(FEET/SEC.) = 6.82

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13603.00 = 2871.05 FEET.

FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 584.58 DOWNSTREAM(FEET) = 544.91
CHANNEL LENGTH THRU SUBAREA(FEET) = 860.98 CHANNEL SLOPE = 0.0461
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.78
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.384

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	10.22	0.30	1.000	-
USER-DEFINED	-	4.19	0.30	1.000	-
USER-DEFINED	-	0.07	0.30	1.000	-
USER-DEFINED	-	1.11	0.30	1.000	-
USER-DEFINED	-	5.56	0.30	1.000	-
USER-DEFINED	-	0.09	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 154.66

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.47

AVERAGE FLOW DEPTH(FEET) = 1.77 TRAVEL TIME(MIN.) = 2.22

Tc(MIN.) = 20.27

SUBAREA AREA(ACRES) = 21.24 SUBAREA RUNOFF(CFS) = 39.84
EFFECTIVE AREA(ACRES) = 86.40 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 86.4 PEAK FLOW RATE(CFS) = 162.06
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.82

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.82 FLOW VELOCITY(FEET/SEC.) = 6.53

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13620.00 = 3732.03 FEET.

```

*****
FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 10
-----
>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<
=====
*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13522.00 IS CODE = 15.1
-----
>>>>DEFINE MEMORY BANK # 2 <<<<<
=====
PEAK FLOWRATE TABLE FILE NAME: S35X00.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:
STREAM      Q      Tc      Fp(Fm)    Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR) (ACRES)  NODE
  1      1365.67  51.63  0.30( 0.28) 0.95  1517.0  13510.00
  2      1241.97  59.58  0.30( 0.28) 0.94  1579.8  13500.00
TOTAL AREA(ACRES) =      1579.8

*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13522.00 IS CODE = 14.0
-----
>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<
=====
MAIN-STREAM MEMORY DEFINED AS FOLLOWS:
STREAM      Q      Tc      Fp(Fm)    Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR) (ACRES)  NODE
  1      1365.67  51.63  0.30( 0.28) 0.95  1517.0  13510.00
  2      1241.97  59.58  0.30( 0.28) 0.94  1579.8  13500.00
TOTAL AREA(ACRES) =      1579.8

*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13620.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 632.19 DOWNSTREAM(FEET) = 544.91
CHANNEL LENGTH THRU SUBAREA(FEET) = 2062.96 CHANNEL SLOPE = 0.0423
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.76
*100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.344
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp      Ap      SCS
LAND USE              GROUP  (ACRES)  (INCH/HR) (DECIMAL) CN
USER-DEFINED          -      17.68    0.30    1.000  -
USER-DEFINED          -      2.36    0.30    1.000  -
USER-DEFINED          -      0.60    0.30    1.000  -
USER-DEFINED          -      0.22    0.30    1.000  -
USER-DEFINED          -      2.22    0.30    1.000  -
USER-DEFINED          -      3.42    0.30    1.000  -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1378.12
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 13.05

```

```

AVERAGE FLOW DEPTH(FEET) = 2.76 TRAVEL TIME(MIN.) = 2.63
Tc(MIN.) = 54.26
SUBAREA AREA(ACRES) = 26.50 SUBAREA RUNOFF(CFS) = 24.90
EFFECTIVE AREA(ACRES) = 1543.46 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
TOTAL AREA(ACRES) = 1606.3 PEAK FLOW RATE(CFS) = 1471.93
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.87

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 2.87 FLOW VELOCITY(FEET/SEC.) = 13.31
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

*****
FLOW PROCESS FROM NODE 13620.00 TO NODE 13620.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====
MAINLINE Tc(MIN.) = 54.26
*100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.344
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp      Ap      SCS
LAND USE              GROUP  (ACRES)  (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"WOODLAND,GRASS"      B      1.44    0.30    1.000  65
NATURAL FAIR COVER
"WOODLAND,GRASS"      B      0.01    0.30    1.000  65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 1.45 SUBAREA RUNOFF(CFS) = 1.36
EFFECTIVE AREA(ACRES) = 1544.91 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
TOTAL AREA(ACRES) = 1607.8 PEAK FLOW RATE(CFS) = 1473.29

*****
FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 11
-----
>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<
=====
** MAIN STREAM CONFLUENCE DATA **
STREAM      Q      Tc      Intensity  Fp(Fm)    Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR) (INCH/HR) (ACRES)  NODE
  1      1473.29  54.26  1.344  0.30( 0.28) 0.95  1544.9  13510.00
  2      1417.77  62.30  1.263  0.30( 0.28) 0.95  1607.8  13500.00
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **
STREAM      Q      Tc      Intensity  Fp(Fm)    Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR) (INCH/HR) (ACRES)  NODE
  1      162.06  20.27  2.384  0.30( 0.30) 1.00    86.4  13600.00
LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13620.00 = 3732.03 FEET.

** PEAK FLOW RATE TABLE **
STREAM      Q      Tc      Intensity  Fp(Fm)    Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR) (INCH/HR) (ACRES)  NODE
  1      1252.52  20.27  2.384  0.30( 0.29) 0.95    663.4  13600.00

```


2 1554.47 54.26 1.344 0.30(0.29) 0.95 1631.3 13510.00
 3 1492.69 62.30 1.263 0.30(0.28) 0.95 1694.2 13500.00
 TOTAL AREA (ACRES) = 1694.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 1554.47 Tc (MIN.) = 54.262
 EFFECTIVE AREA (ACRES) = 1631.31 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
 TOTAL AREA (ACRES) = 1694.2
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

 FLOW PROCESS FROM NODE 13620.00 TO NODE 13640.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 544.91 DOWNSTREAM (FEET) = 489.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1384.37 CHANNEL SLOPE = 0.0404
 GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT (FEET) = 3.02
 * 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.324

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.39	0.30	1.000	-
USER-DEFINED	-	16.30	0.30	1.000	-
USER-DEFINED	-	4.08	0.30	1.000	-
USER-DEFINED	-	12.36	0.30	1.000	-
USER-DEFINED	-	11.23	0.30	1.000	-
USER-DEFINED	-	5.16	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 1579.60
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 13.40
 AVERAGE FLOW DEPTH (FEET) = 3.02 TRAVEL TIME (MIN.) = 1.72
 Tc (MIN.) = 55.98
 SUBAREA AREA (ACRES) = 54.52 SUBAREA RUNOFF (CFS) = 50.27
 EFFECTIVE AREA (ACRES) = 1685.83 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
 TOTAL AREA (ACRES) = 1748.7 PEAK FLOW RATE (CFS) = 1576.17
 GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT (FEET) = 3.02

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 3.02 FLOW VELOCITY (FEET/SEC.) = 13.38
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

 FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 55.98
 * 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.324
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	53.93	0.30	1.000	-
USER-DEFINED	-	0.45	0.30	1.000	-
USER-DEFINED	-	3.98	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 58.36 SUBAREA RUNOFF (CFS) = 53.81
 EFFECTIVE AREA (ACRES) = 1744.19 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
 TOTAL AREA (ACRES) = 1807.1 PEAK FLOW RATE (CFS) = 1629.97

 FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P201XXCE.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	262.78	16.94	0.30 (0.26)	0.85	133.8	20100.00
TOTAL AREA (ACRES) =		133.8				

 FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1382.76	22.10	2.267	0.30 (0.29)	0.96	776.3	13600.00
2	1629.97	55.98	1.324	0.30 (0.29)	0.95	1744.2	13510.00
3	1571.28	64.04	1.252	0.30 (0.29)	0.95	1807.1	13500.00
LONGEST FLOWPATH FROM NODE		13500.00 TO NODE 13640.00 = 22062.09 FEET.					

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	262.78	16.94	2.709	0.30 (0.26)	0.85	133.8	20100.00
LONGEST FLOWPATH FROM NODE		20100.00 TO NODE 13640.00 = 5247.00 FEET.					

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1559.13	16.94	2.709	0.30 (0.28)	0.94	728.9	20100.00
2	1598.27	22.10	2.267	0.30 (0.28)	0.95	910.1	13600.00
3	1744.43	55.98	1.324	0.30 (0.28)	0.95	1878.0	13510.00
4	1677.93	64.04	1.252	0.30 (0.28)	0.94	1940.9	13500.00
TOTAL AREA (ACRES) =		1940.9					

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 1744.43 Tc (MIN.) = 55.984
 EFFECTIVE AREA (ACRES) = 1877.99 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
 TOTAL AREA (ACRES) = 1940.9

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

FLOW PROCESS FROM NODE 13640.00 TO NODE 13641.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 489.00 DOWNSTREAM(FEET) = 436.89
CHANNEL LENGTH THRU SUBAREA(FEET) = 2994.52 CHANNEL SLOPE = 0.0174
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 4.06

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.274

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.96	0.30	1.000	-
USER-DEFINED	-	0.01	0.30	1.000	-
USER-DEFINED	-	1.56	0.30	1.000	-
USER-DEFINED	-	10.45	0.30	1.000	-
USER-DEFINED	-	44.94	0.30	1.000	-
USER-DEFINED	-	9.66	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1774.04

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.37

AVERAGE FLOW DEPTH(FEET) = 4.06 TRAVEL TIME(MIN.) = 4.81

Tc(MIN.) = 60.80

SUBAREA AREA(ACRES) = 67.58 SUBAREA RUNOFF(CFS) = 59.22

EFFECTIVE AREA(ACRES) = 1945.57 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95

TOTAL AREA(ACRES) = 2008.4 PEAK FLOW RATE(CFS) = 1744.43

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 4.02

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 4.02 FLOW VELOCITY(FEET/SEC.) = 10.31

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13641.00 = 25056.61 FEET.

FLOW PROCESS FROM NODE 13641.00 TO NODE 13641.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 60.80

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.274

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	16.49	0.30	1.000	-
USER-DEFINED	-	20.39	0.30	1.000	-
USER-DEFINED	-	7.02	0.30	1.000	-
USER-DEFINED	-	12.58	0.30	1.000	-
USER-DEFINED	-	42.49	0.30	1.000	-
USER-DEFINED	-	5.73	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 104.70 SUBAREA RUNOFF(CFS) = 91.75

EFFECTIVE AREA(ACRES) = 2050.27 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95

TOTAL AREA(ACRES) = 2113.1 PEAK FLOW RATE(CFS) = 1823.72

FLOW PROCESS FROM NODE 13641.00 TO NODE 13641.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 60.80

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.274

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.78	0.30	1.000	-
USER-DEFINED	-	6.25	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 8.03 SUBAREA RUNOFF(CFS) = 7.04

EFFECTIVE AREA(ACRES) = 2058.30 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95

TOTAL AREA(ACRES) = 2121.2 PEAK FLOW RATE(CFS) = 1830.76

FLOW PROCESS FROM NODE 13641.00 TO NODE 13642.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 436.89 DOWNSTREAM(FEET) = 394.80
CHANNEL LENGTH THRU SUBAREA(FEET) = 2814.16 CHANNEL SLOPE = 0.0150
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 4.42
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.242

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.67	0.30	1.000	-
USER-DEFINED	-	24.24	0.30	1.000	-
USER-DEFINED	-	1.34	0.30	1.000	-
USER-DEFINED	-	74.98	0.30	1.000	-
USER-DEFINED	-	101.12	0.30	1.000	-
USER-DEFINED	-	16.90	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1923.70

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.06

AVERAGE FLOW DEPTH(FEET) = 4.42 TRAVEL TIME(MIN.) = 4.66

Tc(MIN.) = 65.46

SUBAREA AREA(ACRES) = 219.25 SUBAREA RUNOFF(CFS) = 185.87

EFFECTIVE AREA(ACRES) = 2277.55 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96

TOTAL AREA(ACRES) = 2340.4 PEAK FLOW RATE(CFS) = 1957.90

GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 4.46

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 4.46 FLOW VELOCITY(FEET/SEC.) = 10.12
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13642.00 = 27870.77 FEET.

FLOW PROCESS FROM NODE 13642.00 TO NODE 13642.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 65.46
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.242
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 9.95 0.30 1.000 -
USER-DEFINED - 10.02 0.30 1.000 -
USER-DEFINED - 4.45 0.30 1.000 -
USER-DEFINED - 179.37 0.30 1.000 -
USER-DEFINED - 11.47 0.30 1.000 -
USER-DEFINED - 0.17 0.30 0.850 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 215.43 SUBAREA RUNOFF(CFS) = 182.64
EFFECTIVE AREA(ACRES) = 2492.98 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA(ACRES) = 2555.9 PEAK FLOW RATE(CFS) = 2140.54

FLOW PROCESS FROM NODE 13642.00 TO NODE 13642.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 65.46
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.242
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.03 0.30 0.850 -
USER-DEFINED - 5.14 0.30 1.000 -
USER-DEFINED - 11.22 0.30 1.000 -
USER-DEFINED - 0.33 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 16.72 SUBAREA RUNOFF(CFS) = 14.18
EFFECTIVE AREA(ACRES) = 2509.70 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA(ACRES) = 2572.6 PEAK FLOW RATE(CFS) = 2154.71

FLOW PROCESS FROM NODE 13642.00 TO NODE 13643.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 394.80 DOWNSTREAM(FEET) = 342.39

CHANNEL LENGTH THRU SUBAREA(FEET) = 2913.57 CHANNEL SLOPE = 0.0180
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 4.54
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.212

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.22 0.30 1.000 -
USER-DEFINED - 2.17 0.30 1.000 -
USER-DEFINED - 9.19 0.30 1.000 -
USER-DEFINED - 67.57 0.30 1.000 -
USER-DEFINED - 35.19 0.30 1.000 -
USER-DEFINED - 30.67 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2214.26
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.20
AVERAGE FLOW DEPTH(FEET) = 4.53 TRAVEL TIME(MIN.) = 4.34
Tc(MIN.) = 69.79
SUBAREA AREA(ACRES) = 145.01 SUBAREA RUNOFF(CFS) = 119.09
EFFECTIVE AREA(ACRES) = 2654.71 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA(ACRES) = 2717.6 PEAK FLOW RATE(CFS) = 2207.20
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 4.53

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 4.53 FLOW VELOCITY(FEET/SEC.) = 11.19
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13643.00 = 30784.34 FEET.

FLOW PROCESS FROM NODE 13643.00 TO NODE 13643.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 69.79
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.212
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.89 0.30 1.000 -
USER-DEFINED - 20.65 0.30 1.000 -
USER-DEFINED - 2.69 0.30 1.000 -
USER-DEFINED - 8.45 0.30 1.000 -
USER-DEFINED - 96.93 0.30 1.000 -
USER-DEFINED - 13.19 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 142.80 SUBAREA RUNOFF(CFS) = 117.27
EFFECTIVE AREA(ACRES) = 2797.51 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA(ACRES) = 2860.4 PEAK FLOW RATE(CFS) = 2324.47

** PEAK FLOW RATE TABLE **

STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE

1 2290.20 30.99 1.836 0.30(0.29) 0.97 1648.4 20100.00
 2 2328.15 36.09 1.706 0.30(0.29) 0.97 1829.6 13600.00
 3 2324.47 69.79 1.212 0.30(0.29) 0.96 2797.5 13510.00
 4 2234.36 78.00 1.157 0.30(0.29) 0.96 2860.4 13500.00
 NEW PEAK FLOW DATA ARE:
 PEAK FLOW RATE(CFS) = 2328.15 Tc(MIN.) = 36.09
 AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.97 EFFECTIVE AREA(ACRES) = 1829.61

 FLOW PROCESS FROM NODE 13643.00 TO NODE 13643.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 36.09
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.706
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	42.54	0.30	1.000	-
USER-DEFINED	-	16.96	0.30	1.000	-
USER-DEFINED	-	80.60	0.30	1.000	-
USER-DEFINED	-	1.56	0.30	1.000	-
USER-DEFINED	-	2.00	0.30	1.000	-
USER-DEFINED	-	3.11	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 146.77 SUBAREA RUNOFF(CFS) = 185.69
 EFFECTIVE AREA(ACRES) = 1976.38 AREA-AVERAGED Fm(INCH/HR) = 0.29
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA(ACRES) = 3007.2 PEAK FLOW RATE(CFS) = 2513.83

 FLOW PROCESS FROM NODE 13643.00 TO NODE 13660.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 342.39 DOWNSTREAM(FEET) = 300.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1591.23 CHANNEL SLOPE = 0.0266
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 4.40
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.655
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.89	0.30	1.000	-
USER-DEFINED	-	23.73	0.30	1.000	-
USER-DEFINED	-	0.27	0.30	1.000	-
USER-DEFINED	-	19.87	0.30	1.000	-
USER-DEFINED	-	6.40	0.30	1.000	-
USER-DEFINED	-	3.14	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2546.95
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 13.40
 AVERAGE FLOW DEPTH(FEET) = 4.40 TRAVEL TIME(MIN.) = 1.98

Tc(MIN.) = 38.07
 SUBAREA AREA(ACRES) = 54.30 SUBAREA RUNOFF(CFS) = 66.23
 EFFECTIVE AREA(ACRES) = 2030.68 AREA-AVERAGED Fm(INCH/HR) = 0.29
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
 TOTAL AREA(ACRES) = 3061.5 PEAK FLOW RATE(CFS) = 2513.83
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 4.37

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 4.37 FLOW VELOCITY(FEET/SEC.) = 13.35
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 32375.57 FEET.

 FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 38.07
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.655
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.67	0.30	1.000	-
USER-DEFINED	-	9.52	0.30	1.000	-
USER-DEFINED	-	0.71	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	39.42	0.30	1.000	-
USER-DEFINED	-	0.62	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 51.16 SUBAREA RUNOFF(CFS) = 62.40
 EFFECTIVE AREA(ACRES) = 2081.84 AREA-AVERAGED Fm(INCH/HR) = 0.29
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
 TOTAL AREA(ACRES) = 3112.6 PEAK FLOW RATE(CFS) = 2552.71

 FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 38.07
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.655
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.11	0.30	1.000	-
USER-DEFINED	-	0.77	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	2.69	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 3.79 SUBAREA RUNOFF(CFS) = 4.62
 EFFECTIVE AREA(ACRES) = 2085.63 AREA-AVERAGED Fm(INCH/HR) = 0.29
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
 TOTAL AREA(ACRES) = 3116.4 PEAK FLOW RATE(CFS) = 2557.33

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2557.45	32.97	1.785	0.30 (0.29)	0.98	1904.5	20100.00
2	2557.33	38.07	1.655	0.30 (0.29)	0.98	2085.6	13600.00
3	2497.40	71.79	1.199	0.30 (0.29)	0.97	3053.5	13510.00
4	2393.19	80.02	1.143	0.30 (0.29)	0.97	3116.4	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2557.45 Tc(MIN.) = 32.97
 AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.98 EFFECTIVE AREA(ACRES) = 1904.47

 FLOW PROCESS FROM NODE 13643.00 TO NODE 13660.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

 FLOW PROCESS FROM NODE 13659.00 TO NODE 13659.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 2P00EVAA.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	589.23	13.84	0.30 (0.11)	0.36	173.5	110.00
2	590.10	16.35	0.30 (0.11)	0.38	204.6	100.00
3	582.95	17.51	0.30 (0.11)	0.38	213.9	100.00
4	519.41	20.54	0.30 (0.12)	0.40	221.1	130.00
TOTAL AREA(ACRES) =						221.1

 FLOW PROCESS FROM NODE 13659.00 TO NODE 13660.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 338.00 DOWNSTREAM(FEET) = 300.00
 FLOW LENGTH(FEET) = 881.07 MANNING'S N = 0.013
 DEPTH OF FLOW IN 114.0 INCH PIPE IS 84.6 INCHES
 PIPE-FLOW VELOCITY(FEET/SEC.) = 45.37
 ESTIMATED PIPE DIAMETER(INCH) = 114.00 NUMBER OF PIPES = 1
 PIPE-FLOW(CFS) = 2557.45
 PIPE TRAVEL TIME(MIN.) = 0.32 Tc(MIN.) = 33.29
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

 FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2557.45	33.29	1.777	0.30 (0.29)	0.98	1904.5	20100.00

2	2557.33	38.39	1.647	0.30 (0.29)	0.98	2085.6	13600.00
3	2497.40	72.12	1.197	0.30 (0.29)	0.97	3053.5	13510.00
4	2393.19	80.35	1.141	0.30 (0.29)	0.97	3116.4	13500.00
LONGEST FLOWPATH FROM NODE						13500.00 TO NODE	13660.00 = 33256.64 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	589.23	13.84	3.099	0.30 (0.11)	0.36	173.5	110.00
2	590.10	16.35	2.768	0.30 (0.11)	0.38	204.6	100.00
3	582.95	17.51	2.651	0.30 (0.11)	0.38	213.9	100.00
4	519.41	20.54	2.367	0.30 (0.12)	0.40	221.1	130.00
LONGEST FLOWPATH FROM NODE						130.00 TO NODE	13660.00 = 6327.50 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2599.41	13.84	3.099	0.30 (0.26)	0.87	965.1	110.00
2	2684.89	16.35	2.768	0.30 (0.26)	0.87	1139.7	100.00
3	2720.74	17.51	2.651	0.30 (0.26)	0.87	1215.6	100.00
4	2724.10	20.54	2.367	0.30 (0.27)	0.89	1395.9	130.00
5	2940.50	33.29	1.777	0.30 (0.28)	0.92	2125.6	20100.00
6	2910.30	38.39	1.647	0.30 (0.28)	0.92	2306.7	13600.00
7	2746.24	72.12	1.197	0.30 (0.28)	0.93	3274.6	13510.00
8	2629.09	80.35	1.141	0.30 (0.28)	0.93	3337.5	13500.00
TOTAL AREA(ACRES) =						3337.5	

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 2940.50 Tc(MIN.) = 33.293
 EFFECTIVE AREA(ACRES) = 2125.57 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.87
 TOTAL AREA(ACRES) = 3337.5
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

 FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 33.29
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.777
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "FALLOW"	B	1.11	0.30	1.000	86
AGRICULTURAL POOR COVER "FALLOW"	B	0.44	0.30	1.000	86
NATURAL FAIR COVER "GRASS"	B	1.49	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	1.70	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	1.09	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	18.57	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 24.40 SUBAREA RUNOFF(CFS) = 32.44
EFFECTIVE AREA(ACRES) = 2149.97 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 3361.9 PEAK FLOW RATE(CFS) = 2940.50
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====

MAINLINE Tc(MIN.) = 33.29
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.777
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
AGRICULTURAL FAIR COVER
"ORCHARDS" B 12.39 0.30 1.000 65
AGRICULTURAL FAIR COVER
"ORCHARDS" B 2.30 0.30 1.000 65
AGRICULTURAL POOR COVER
"ROW CROPS,CONTOURED" B 5.19 0.30 1.000 79
AGRICULTURAL POOR COVER
"ROW CROPS,STRAIGHT ROW" B 28.71 0.30 1.000 81
NATURAL FAIR COVER
"WOODLAND,GRASS" B 0.17 0.30 1.000 65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 48.76 SUBAREA RUNOFF(CFS) = 64.82
EFFECTIVE AREA(ACRES) = 2198.73 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 3410.7 PEAK FLOW RATE(CFS) = 2970.22

FLOW PROCESS FROM NODE 13660.00 TO NODE 13680.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<
=====

ELEVATION DATA: UPSTREAM(FEET) = 300.00 DOWNSTREAM(FEET) = 288.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 933.89 CHANNEL SLOPE = 0.0128
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 5.81
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.740
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.22 0.30 1.000 -
USER-DEFINED - 9.23 0.30 1.000 -
USER-DEFINED - 0.54 0.30 1.000 -
USER-DEFINED - 5.66 0.30 1.000 -
USER-DEFINED - 3.66 0.30 1.000 -
USER-DEFINED - 0.67 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2983.17
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.83

AVERAGE FLOW DEPTH(FEET) = 5.81 TRAVEL TIME(MIN.) = 1.44
Tc(MIN.) = 34.73
SUBAREA AREA(ACRES) = 19.98 SUBAREA RUNOFF(CFS) = 25.90
EFFECTIVE AREA(ACRES) = 2218.71 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 3430.6 PEAK FLOW RATE(CFS) = 2970.22
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 5.79

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 5.79 FLOW VELOCITY(FEET/SEC.) = 10.82
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13680.00 = 34190.53 FEET.

FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====

MAINLINE Tc(MIN.) = 34.73
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.740
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 1.56 0.30 1.000 -
USER-DEFINED - 9.40 0.30 1.000 -
USER-DEFINED - 2.76 0.30 1.000 -
USER-DEFINED - 17.38 0.30 1.000 -
USER-DEFINED - 2.46 0.30 1.000 -
USER-DEFINED - 5.56 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 39.12 SUBAREA RUNOFF(CFS) = 50.72
EFFECTIVE AREA(ACRES) = 2257.83 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 3469.8 PEAK FLOW RATE(CFS) = 2974.30

FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====

MAINLINE Tc(MIN.) = 34.73
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.740
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.65 0.30 1.000 -
USER-DEFINED - 1.70 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 2.35 SUBAREA RUNOFF(CFS) = 3.05
EFFECTIVE AREA(ACRES) = 2260.18 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 3472.1 PEAK FLOW RATE(CFS) = 2977.35

FLOW PROCESS FROM NODE 13660.00 TO NODE 13680.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 34.73

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.740

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.29	0.30	1.000	-
USER-DEFINED	-	31.25	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	6.26	0.30	1.000	-
USER-DEFINED	-	0.07	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 43.31 SUBAREA RUNOFF(CFS) = 56.15

EFFECTIVE AREA(ACRES) = 2303.49 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92

TOTAL AREA(ACRES) = 3515.4 PEAK FLOW RATE(CFS) = 3033.50

FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 34.73

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.740

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	2.47	0.30	0.850	-
USER-DEFINED	-	3.06	0.30	0.850	-
USER-DEFINED	-	17.76	0.30	0.500	-
USER-DEFINED	-	7.31	0.30	0.500	-
USER-DEFINED	-	0.34	0.30	1.000	-
USER-DEFINED	-	8.22	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.659

SUBAREA AREA(ACRES) = 39.16 SUBAREA RUNOFF(CFS) = 54.37

EFFECTIVE AREA(ACRES) = 2342.65 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92

TOTAL AREA(ACRES) = 3554.6 PEAK FLOW RATE(CFS) = 3087.87

FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 34.73

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.740

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.53	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 0.53 SUBAREA RUNOFF(CFS) = 0.69
EFFECTIVE AREA(ACRES) = 2343.18 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 3555.1 PEAK FLOW RATE(CFS) = 3088.56

FLOW PROCESS FROM NODE 13680.00 TO NODE 13682.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 288.00 DOWNSTREAM(FEET) = 242.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 2860.77 CHANNEL SLOPE = 0.0161
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 5.58

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.638

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	5.28	0.30	1.000	-
USER-DEFINED	-	0.52	0.30	1.000	-
USER-DEFINED	-	3.61	0.30	1.000	-
USER-DEFINED	-	0.67	0.30	1.000	-
USER-DEFINED	-	1.37	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3095.59

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.86

AVERAGE FLOW DEPTH(FEET) = 5.58 TRAVEL TIME(MIN.) = 4.02

Tc(MIN.) = 38.75

SUBAREA AREA(ACRES) = 11.67 SUBAREA RUNOFF(CFS) = 14.05

EFFECTIVE AREA(ACRES) = 2354.85 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92

TOTAL AREA(ACRES) = 3566.8 PEAK FLOW RATE(CFS) = 3088.56

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 5.57

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 5.57 FLOW VELOCITY(FEET/SEC.) = 11.86

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13682.00 = 37051.30 FEET.

FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 38.75

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.638

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	6.90	0.30	1.000	-
USER-DEFINED	-	23.04	0.30	1.000	-
USER-DEFINED	-	1.18	0.30	1.000	-
USER-DEFINED	-	1.56	0.30	1.000	-
USER-DEFINED	-	53.20	0.30	1.000	-
USER-DEFINED	-	2.08	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 87.96 SUBAREA RUNOFF(CFS) = 105.92
EFFECTIVE AREA(ACRES) = 2442.81 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 3654.7 PEAK FLOW RATE(CFS) = 3088.56
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 38.75
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.638
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.01	0.30	1.000	-
USER-DEFINED	-	0.18	0.30	1.000	-
USER-DEFINED	-	0.38	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	7.73	0.30	1.000	-
USER-DEFINED	-	4.37	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 12.89 SUBAREA RUNOFF(CFS) = 15.52
EFFECTIVE AREA(ACRES) = 2455.70 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 3667.6 PEAK FLOW RATE(CFS) = 3088.56
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 38.75
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.638
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"FALLOW"	B	2.57	0.30	1.000	86
AGRICULTURAL POOR COVER					
"FALLOW"	B	1.97	0.30	1.000	86
NATURAL FAIR COVER					
"GRASS"	B	1.00	0.30	1.000	69
NATURAL FAIR COVER					

"GRASS"	B	2.98	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.39	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.67	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 12.58 SUBAREA RUNOFF(CFS) = 15.15
EFFECTIVE AREA(ACRES) = 2468.28 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 3680.2 PEAK FLOW RATE(CFS) = 3088.56
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 38.75
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.638
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.44	0.30	1.000	66
PUBLIC PARK	B	2.65	0.30	0.850	56
PUBLIC PARK	B	1.16	0.30	0.850	56
RESIDENTIAL					
"5-7 DWELLINGS/ACRE"	B	0.47	0.30	0.500	56
RESIDENTIAL					
"5-7 DWELLINGS/ACRE"	B	0.25	0.30	0.500	56
AGRICULTURAL POOR COVER					
"ROW CROPS, STRAIGHT ROW"	B	20.24	0.30	1.000	81

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.963
SUBAREA AREA(ACRES) = 25.21 SUBAREA RUNOFF(CFS) = 30.61
EFFECTIVE AREA(ACRES) = 2493.49 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 3705.4 PEAK FLOW RATE(CFS) = 3088.56
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 38.75
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.638
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.08	0.30	1.000	-
USER-DEFINED	-	6.75	0.30	1.000	-
USER-DEFINED	-	0.02	0.30	1.000	-
USER-DEFINED	-	0.93	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 14.78 SUBAREA RUNOFF(CFS) = 17.80

EFFECTIVE AREA(ACRES) = 2508.27 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 3720.2 PEAK FLOW RATE(CFS) = 3088.56
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13682.00 TO NODE 13683.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<
=====

ELEVATION DATA: UPSTREAM(FEET) = 242.00 DOWNSTREAM(FEET) = 208.53
CHANNEL LENGTH THRU SUBAREA(FEET) = 2526.22 CHANNEL SLOPE = 0.0132
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 5.89

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.551

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.49	0.30	1.000	-
USER-DEFINED	-	13.31	0.30	1.000	-
USER-DEFINED	-	0.87	0.30	1.000	-
USER-DEFINED	-	20.26	0.30	1.000	-
USER-DEFINED	-	1.21	0.30	1.000	-
USER-DEFINED	-	0.05	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3113.45

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.08

AVERAGE FLOW DEPTH(FEET) = 5.89 TRAVEL TIME(MIN.) = 3.80

Tc(MIN.) = 42.55

SUBAREA AREA(ACRES) = 44.19 SUBAREA RUNOFF(CFS) = 49.77

EFFECTIVE AREA(ACRES) = 2552.46 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA(ACRES) = 3764.4 PEAK FLOW RATE(CFS) = 3088.56

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 5.86

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 5.86 FLOW VELOCITY(FEET/SEC.) = 11.07

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13683.00 = 39577.52 FEET.

FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====

MAINLINE Tc(MIN.) = 42.55

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.551

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	12.56	0.30	1.000	-
USER-DEFINED	-	0.81	0.30	1.000	-
USER-DEFINED	-	0.01	0.30	1.000	-

USER-DEFINED - 1.11 0.30 1.000 -
USER-DEFINED - 0.59 0.30 1.000 -
USER-DEFINED - 3.04 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 18.12 SUBAREA RUNOFF(CFS) = 20.41

EFFECTIVE AREA(ACRES) = 2570.58 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA(ACRES) = 3782.5 PEAK FLOW RATE(CFS) = 3088.56

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====

MAINLINE Tc(MIN.) = 42.55

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.551

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL					
"8-10 DWELLINGS/ACRE"	B	0.10	0.30	0.400	56
PUBLIC PARK	B	1.30	0.30	0.850	56
RESIDENTIAL					
"8-10 DWELLINGS/ACRE"	B	0.10	0.30	0.400	56
PUBLIC PARK	B	1.70	0.30	0.850	56
PUBLIC PARK	B	0.10	0.30	0.850	56
PUBLIC PARK	B	2.90	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.835

SUBAREA AREA(ACRES) = 6.20 SUBAREA RUNOFF(CFS) = 7.26

EFFECTIVE AREA(ACRES) = 2576.78 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA(ACRES) = 3788.7 PEAK FLOW RATE(CFS) = 3088.56

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====

MAINLINE Tc(MIN.) = 42.55

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.551

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL					
"5-7 DWELLINGS/ACRE"	B	0.10	0.30	0.500	56
CONDOMINIUMS	B	0.10	0.30	0.350	56
PUBLIC PARK	B	6.90	0.30	0.850	56
PUBLIC PARK	B	0.40	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.839

SUBAREA AREA(ACRES) = 7.50 SUBAREA RUNOFF(CFS) = 8.77

EFFECTIVE AREA(ACRES) = 2584.28 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA(ACRES) = 3796.2 PEAK FLOW RATE(CFS) = 3088.56

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13682.00 TO NODE 13683.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

MEMORY BANK # 3 IS EMPTY - PROCESS IGNORED.

FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 42.55

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.551

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"FALLOW"	B	2.55	0.30	1.000	86
AGRICULTURAL POOR COVER					
"FALLOW"	B	0.01	0.30	1.000	86
AGRICULTURAL POOR COVER					
"FALLOW"	B	1.35	0.30	1.000	86
NATURAL FAIR COVER					
"GRASS"	B	0.44	0.30	1.000	69
NATURAL FAIR COVER					
"GRASS"	B	0.67	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.06	0.30	1.000	66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000					
SUBAREA AREA(ACRES) = 6.08		SUBAREA RUNOFF(CFS) = 6.85			
EFFECTIVE AREA(ACRES) = 2590.36		AREA-AVERAGED Fm(INCH/HR) = 0.28			
AREA-AVERAGED Fp(INCH/HR) = 0.30		AREA-AVERAGED Ap = 0.93			
TOTAL AREA(ACRES) = 3802.3		PEAK FLOW RATE(CFS) = 3088.56			
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE					

FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 42.55

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.551

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.16	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.45	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	6.15	0.30	1.000	66
AGRICULTURAL POOR COVER					
"ROW CROPS,STRAIGHT ROW"	B	1.34	0.30	1.000	81
AGRICULTURAL POOR COVER					

"ROW CROPS,STRAIGHT ROW" B 18.46 0.30 1.000 81
 AGRICULTURAL POOR COVER
 "ROW CROPS,STRAIGHT ROW" B 4.13 0.30 1.000 81
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 34.69 SUBAREA RUNOFF(CFS) = 39.07
 EFFECTIVE AREA(ACRES) = 2625.05 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 3837.0 PEAK FLOW RATE(CFS) = 3088.56
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 42.55

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.551

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS,STRAIGHT ROW"	B	8.69	0.30	1.000	81
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.73	0.30	1.000	65
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.41	0.30	1.000	65
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	1.37	0.30	1.000	65
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	3.11	0.30	1.000	65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000					
SUBAREA AREA(ACRES) = 14.31		SUBAREA RUNOFF(CFS) = 16.12			
EFFECTIVE AREA(ACRES) = 2639.36		AREA-AVERAGED Fm(INCH/HR) = 0.28			
AREA-AVERAGED Fp(INCH/HR) = 0.30		AREA-AVERAGED Ap = 0.93			
TOTAL AREA(ACRES) = 3851.3		PEAK FLOW RATE(CFS) = 3088.56			
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE					

FLOW PROCESS FROM NODE 13683.00 TO NODE 13685.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 208.53 DOWNSTREAM(FEET) = 194.24
 CHANNEL LENGTH THRU SUBAREA(FEET) = 289.01 CHANNEL SLOPE = 0.0494
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 4.13
 CHANNEL FLOW THRU SUBAREA(CFS) = 3088.56
 FLOW VELOCITY(FEET/SEC.) = 17.64 FLOW DEPTH(FEET) = 4.13
 TRAVEL TIME(MIN.) = 0.27 Tc(MIN.) = 42.82
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13685.00 = 39866.53 FEET.

FLOW PROCESS FROM NODE 13685.00 TO NODE 13410.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 194.24 DOWNSTREAM(FEET) = 178.72
CHANNEL LENGTH THRU SUBAREA(FEET) = 1843.57 CHANNEL SLOPE = 0.0084
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 6.60
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.476

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.23	0.30	1.000	-
USER-DEFINED	-	1.52	0.30	1.000	-
USER-DEFINED	-	0.06	0.30	1.000	-
USER-DEFINED	-	0.13	0.30	1.000	-
USER-DEFINED	-	6.45	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3093.00

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.41

AVERAGE FLOW DEPTH(FEET) = 6.60 TRAVEL TIME(MIN.) = 3.27

Tc(MIN.) = 46.09

SUBAREA AREA(ACRES) = 8.39 SUBAREA RUNOFF(CFS) = 8.88

EFFECTIVE AREA(ACRES) = 2647.75 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA(ACRES) = 3859.7 PEAK FLOW RATE(CFS) = 3088.56

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 6.60

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 6.60 FLOW VELOCITY(FEET/SEC.) = 9.40

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13410.00 = 41710.10 FEET.

=====

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 3859.7 TC(MIN.) = 46.09

EFFECTIVE AREA(ACRES) = 2647.75 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.928

PEAK FLOW RATE(CFS) = 3088.56

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2775.64	27.02	1.993	0.30(0.27)	0.90	1487.3	110.00
2	2878.61	29.40	1.888	0.30(0.27)	0.90	1661.9	100.00
3	2888.47	30.54	1.847	0.30(0.27)	0.90	1737.8	100.00
4	2912.70	33.54	1.771	0.30(0.27)	0.91	1918.1	130.00
5	3088.56	46.09	1.476	0.30(0.28)	0.93	2647.7	20100.00
6	3029.46	51.26	1.378	0.30(0.28)	0.93	2828.9	13600.00
7	2905.42	85.17	1.108	0.30(0.28)	0.93	3796.8	13510.00
8	2757.26	93.58	1.059	0.30(0.28)	0.93	3859.7	13500.00

=====

END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2010 Advanced Engineering Software (aes)
Ver. 17.0 Release Date: 07/01/2010 License ID 1527

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 137 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 100-YR EV AUG 2023 ROKAMOTO *

FILE NAME: RU00EV37.DAT
TIME/DATE OF STUDY: 21:36 08/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 100.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.768
- 2) 10.00; 3.736
- 3) 15.00; 2.899
- 4) 20.00; 2.397
- 5) 25.00; 2.080
- 6) 30.00; 1.859
- 7) 40.00; 1.604
- 8) 50.00; 1.391
- 9) 60.00; 1.276
- 10) 90.00; 1.073
- 11) 120.00; 0.936
- 12) 180.00; 0.780
- 13) 360.00; 0.574
- 14) 1200.00; 0.249

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU00EV34.DNA
MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28758.89	14.86	0.30 (0.24)	0.80	4392.1	300.00
2	31190.04	19.72	0.30 (0.24)	0.80	5974.0	210.00
3	33937.43	27.54	0.30 (0.24)	0.80	8525.1	203.00
4	39896.74	42.87	0.30 (0.25)	0.83	16144.5	50260.00
5	42236.71	51.57	0.30 (0.26)	0.86	20875.6	13600.00
6	45083.02	64.21	0.30 (0.27)	0.88	27508.2	13100.00
7	46681.51	70.49	0.30 (0.27)	0.89	30500.1	11801.00
8	49164.48	79.76	0.30 (0.27)	0.90	35544.7	11530.00
9	50538.23	85.46	0.30 (0.27)	0.91	39429.5	13510.00
10	51622.45	90.24	0.30 (0.27)	0.92	42583.0	13010.00
11	52720.64	95.09	0.30 (0.28)	0.92	45805.4	11330.00
12	53374.96	101.37	0.30 (0.28)	0.93	50236.4	11130.00
13	52802.61	108.99	0.30 (0.28)	0.93	54230.4	12330.00
14	52169.07	115.65	0.30 (0.28)	0.94	57573.6	12400.00
15	51164.03	124.37	0.30 (0.28)	0.94	60942.3	12201.00
16	49686.74	133.78	0.30 (0.28)	0.94	63396.5	12101.10
17	49014.81	137.85	0.30 (0.28)	0.94	64245.5	10400.00
18	47190.92	145.99	0.30 (0.28)	0.94	65560.7	12010.00
19	45691.62	151.95	0.30 (0.28)	0.94	65874.4	10210.00
20	41382.69	178.31	0.30 (0.28)	0.94	66607.1	10100.00
TOTAL AREA(ACRES) = 66607.1						

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 14.0

>>>>MEMORY BANK # 3 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28758.89	14.86	0.30 (0.24)	0.80	4392.1	300.00
2	31190.04	19.72	0.30 (0.24)	0.80	5974.0	210.00
3	33937.43	27.54	0.30 (0.24)	0.80	8525.1	203.00
4	39896.74	42.87	0.30 (0.25)	0.83	16144.5	50260.00
5	42236.71	51.57	0.30 (0.26)	0.86	20875.6	13600.00
6	45083.02	64.21	0.30 (0.27)	0.88	27508.2	13100.00
7	46681.51	70.49	0.30 (0.27)	0.89	30500.1	11801.00
8	49164.48	79.76	0.30 (0.27)	0.90	35544.7	11530.00
9	50538.23	85.46	0.30 (0.27)	0.91	39429.5	13510.00
10	51622.45	90.24	0.30 (0.27)	0.92	42583.0	13010.00
11	52720.64	95.09	0.30 (0.28)	0.92	45805.4	11330.00
12	53374.96	101.37	0.30 (0.28)	0.93	50236.4	11130.00
13	52802.61	108.99	0.30 (0.28)	0.93	54230.4	12330.00

14 52169.07 115.65 0.30(0.28) 0.94 57573.6 12400.00
 15 51164.03 124.37 0.30(0.28) 0.94 60942.3 12201.00
 16 49686.74 133.78 0.30(0.28) 0.94 63396.5 12101.10
 17 49014.81 137.85 0.30(0.28) 0.94 64245.5 10400.00
 18 47190.92 145.99 0.30(0.28) 0.94 65560.7 12010.00
 19 45691.62 151.95 0.30(0.28) 0.94 65874.4 10210.00
 20 41382.69 178.31 0.30(0.28) 0.94 66607.1 10100.00
 TOTAL AREA(ACRES) = 66607.1

FLOW PROCESS FROM NODE 13700.00 TO NODE 13720.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 170.00 DOWNSTREAM(FEET) = 165.51
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1891.83 CHANNEL SLOPE = 0.0024
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 15.33
 CHANNEL FLOW THRU SUBAREA(CFS) = 53374.96
 FLOW VELOCITY(FEET/SEC.) = 12.58 FLOW DEPTH(FEET) = 15.33
 TRAVEL TIME(MIN.) = 2.51 Tc(MIN.) = 103.88
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126441.05 FEET.

FLOW PROCESS FROM NODE 13700.00 TO NODE 13720.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

FLOW PROCESS FROM NODE 13720.00 TO NODE 13720.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506102b.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	406.54	14.41	2.998	0.30(0.29)	0.96	189.8	10230.00
2	372.26	23.72	2.161	0.30(0.29)	0.95	240.3	10200.00
3	368.40	24.34	2.122	0.30(0.29)	0.95	241.8	10250.00
4	339.08	28.10	1.943	0.30(0.29)	0.95	246.3	10220.00
TOTAL AREA(ACRES) =							246.3

FLOW PROCESS FROM NODE 13720.00 TO NODE 13720.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28758.89	17.90	2.608	0.30(0.24)	0.80	4392.1	300.00
2	31190.04	22.68	2.227	0.30(0.24)	0.80	5974.0	210.00
3	33937.43	30.43	1.848	0.30(0.24)	0.80	8525.1	203.00

4 39896.74 45.61 1.484 0.30(0.25) 0.83 16144.5 50260.00
 5 42236.71 54.26 1.342 0.30(0.26) 0.86 20875.6 13600.00
 6 45083.02 66.85 1.230 0.30(0.27) 0.88 27508.2 13100.00
 7 46681.51 73.10 1.187 0.30(0.27) 0.89 30500.1 11801.00
 8 49164.48 82.32 1.125 0.30(0.27) 0.90 35544.7 11530.00
 9 50538.23 88.01 1.086 0.30(0.27) 0.91 39429.5 13510.00
 10 51622.45 92.77 1.060 0.30(0.27) 0.92 42583.0 13010.00
 11 52720.64 97.61 1.038 0.30(0.28) 0.92 45805.4 11330.00
 12 53374.96 103.88 1.010 0.30(0.28) 0.93 50236.4 11130.00
 13 52802.61 111.50 0.975 0.30(0.28) 0.93 54230.4 12330.00
 14 52169.07 118.18 0.944 0.30(0.28) 0.94 57573.6 12400.00
 15 51164.03 126.91 0.918 0.30(0.28) 0.94 60942.3 12201.00
 16 49686.74 136.35 0.894 0.30(0.28) 0.94 63396.5 12101.10
 17 49014.81 140.42 0.883 0.30(0.28) 0.94 64245.5 10400.00
 18 47190.92 148.59 0.862 0.30(0.28) 0.94 65560.7 12010.00
 19 45691.62 154.58 0.846 0.30(0.28) 0.94 65874.4 10210.00
 20 41382.69 181.02 0.779 0.30(0.28) 0.94 66607.1 10100.00
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126441.05 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	406.54	14.41	2.998	0.30(0.29)	0.96	189.8	10230.00
2	372.26	23.72	2.161	0.30(0.29)	0.95	240.3	10200.00
3	368.40	24.34	2.122	0.30(0.29)	0.95	241.8	10250.00
4	339.08	28.10	1.943	0.30(0.29)	0.95	246.3	10220.00
LONGEST FLOWPATH FROM NODE 10200.00 TO NODE 13720.00 =							9099.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27370.04	14.41	2.998	0.30(0.24)	0.81	3725.0	10230.00
2	29152.57	17.90	2.608	0.30(0.24)	0.81	4600.8	300.00
3	31566.12	22.68	2.227	0.30(0.24)	0.81	6208.7	210.00
4	31930.74	23.72	2.161	0.30(0.24)	0.81	6556.4	10200.00
5	32147.95	24.34	2.122	0.30(0.24)	0.81	6763.2	10250.00
6	33451.81	28.10	1.943	0.30(0.24)	0.81	8005.6	10220.00
7	34257.10	30.43	1.848	0.30(0.24)	0.81	8771.4	203.00
8	40141.98	45.61	1.484	0.30(0.25)	0.83	16390.8	50260.00
9	42452.80	54.26	1.342	0.30(0.26)	0.86	21121.8	13600.00
10	45276.12	66.85	1.230	0.30(0.27)	0.88	27754.4	13100.00
11	46865.96	73.10	1.187	0.30(0.27)	0.89	30746.3	11801.00
12	49336.15	82.32	1.125	0.30(0.27)	0.90	35790.9	11530.00
13	50702.03	88.01	1.086	0.30(0.27)	0.91	39675.7	13510.00
14	51780.90	92.77	1.060	0.30(0.28)	0.92	42829.2	13010.00
15	52874.57	97.61	1.038	0.30(0.28)	0.92	46051.6	11330.00
16	53523.03	103.88	1.010	0.30(0.28)	0.93	50482.7	11130.00
17	52943.56	111.50	0.975	0.30(0.28)	0.93	54476.6	12330.00
18	52303.78	118.18	0.944	0.30(0.28)	0.94	57819.8	12400.00
19	51293.36	126.91	0.918	0.30(0.28)	0.94	61188.6	12201.00
20	49811.05	136.35	0.894	0.30(0.28)	0.94	63642.7	12101.10
21	49136.95	140.42	0.883	0.30(0.28)	0.94	64491.8	10400.00
22	47308.71	148.59	0.862	0.30(0.28)	0.94	65806.9	12010.00
23	45806.23	154.58	0.846	0.30(0.28)	0.94	66120.6	10210.00
24	41483.54	181.02	0.779	0.30(0.28)	0.94	66853.4	10100.00
TOTAL AREA(ACRES) =							66853.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 53523.03 Tc(MIN.) = 103.879
 EFFECTIVE AREA(ACRES) = 50482.66 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.90
 TOTAL AREA(ACRES) = 66853.4
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126441.05 FEET.

 FLOW PROCESS FROM NODE 13720.00 TO NODE 13740.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 165.51 DOWNSTREAM(FEET) = 161.03
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2067.54 CHANNEL SLOPE = 0.0022
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 15.74
 CHANNEL FLOW THRU SUBAREA(CFS) = 53523.03
 FLOW VELOCITY(FEET/SEC.) = 12.20 FLOW DEPTH(FEET) = 15.74
 TRAVEL TIME(MIN.) = 2.82 Tc(MIN.) = 106.70
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128508.59 FEET.

 FLOW PROCESS FROM NODE 13720.00 TO NODE 13740.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

 FLOW PROCESS FROM NODE 13740.00 TO NODE 13740.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 0506103b.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	810.21	17.74	0.30(0.23)	0.76	399.5	10300.00
2	813.53	18.53	0.30(0.23)	0.76	413.0	10380.00
3	800.95	20.83	0.30(0.23)	0.76	438.9	10320.00
4	771.92	23.06	0.30(0.23)	0.76	451.6	10360.00
5	728.08	25.86	0.30(0.23)	0.76	460.8	10340.00
TOTAL AREA(ACRES) =						460.8

 FLOW PROCESS FROM NODE 13740.00 TO NODE 13740.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27370.04	17.89	2.609	0.30(0.24)	0.81	3725.0	10230.00
2	29152.57	21.32	2.314	0.30(0.24)	0.81	4600.8	300.00
3	31566.12	26.01	2.035	0.30(0.24)	0.81	6208.7	210.00
4	31930.74	27.03	1.990	0.30(0.24)	0.81	6556.4	10200.00
5	32147.95	27.65	1.963	0.30(0.24)	0.81	6763.2	10250.00

6	33451.81	31.37	1.824	0.30(0.24)	0.81	8005.6	10220.00
7	34257.10	33.67	1.765	0.30(0.24)	0.81	8771.4	203.00
8	40141.98	48.70	1.419	0.30(0.25)	0.83	16390.8	50260.00
9	42452.80	57.30	1.307	0.30(0.26)	0.86	21121.8	13600.00
10	45276.12	69.82	1.210	0.30(0.27)	0.88	27754.4	13100.00
11	46865.96	76.04	1.167	0.30(0.27)	0.89	30746.3	11801.00
12	49336.15	85.22	1.105	0.30(0.27)	0.90	35790.9	11530.00
13	50702.03	90.88	1.069	0.30(0.27)	0.91	39675.7	13510.00
14	51780.90	95.63	1.047	0.30(0.28)	0.92	42829.2	13010.00
15	52874.57	100.44	1.025	0.30(0.28)	0.92	46051.6	11330.00
16	53523.03	106.70	0.997	0.30(0.28)	0.93	50482.7	11130.00
17	52943.56	114.34	0.962	0.30(0.28)	0.93	54476.6	12330.00
18	52303.78	121.02	0.933	0.30(0.28)	0.94	57819.8	12400.00
19	51293.36	129.77	0.911	0.30(0.28)	0.94	61188.6	12201.00
20	49811.05	139.23	0.886	0.30(0.28)	0.94	63642.7	12101.10
21	49136.95	143.32	0.875	0.30(0.28)	0.94	64491.8	10400.00
22	47308.71	151.52	0.854	0.30(0.28)	0.94	65806.9	12010.00
23	45806.23	157.54	0.838	0.30(0.28)	0.94	66120.6	10210.00
24	41483.54	184.08	0.775	0.30(0.28)	0.94	66853.4	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128508.59 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	810.21	17.74	2.623	0.30(0.23)	0.76	399.5	10300.00
2	813.53	18.53	2.544	0.30(0.23)	0.76	413.0	10380.00
3	800.95	20.83	2.345	0.30(0.23)	0.76	438.9	10320.00
4	771.92	23.06	2.203	0.30(0.23)	0.76	451.6	10360.00
5	728.08	25.86	2.042	0.30(0.23)	0.76	460.8	10340.00

LONGEST FLOWPATH FROM NODE 10320.00 TO NODE 13740.00 = 8457.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28125.02	17.74	2.623	0.30(0.24)	0.80	4094.1	10300.00
2	28180.86	17.89	2.609	0.30(0.24)	0.80	4127.1	10230.00
3	28518.91	18.53	2.544	0.30(0.24)	0.80	4302.8	10380.00
4	29699.74	20.83	2.345	0.30(0.24)	0.80	4915.0	10320.00
5	29947.17	21.32	2.314	0.30(0.24)	0.80	5042.5	300.00
6	30819.56	23.06	2.203	0.30(0.24)	0.80	5648.7	10360.00
7	32220.68	25.86	2.042	0.30(0.24)	0.80	6620.5	10340.00
8	32291.67	26.01	2.035	0.30(0.24)	0.80	6669.5	210.00
9	32638.05	27.03	1.990	0.30(0.24)	0.80	7017.2	10200.00
10	32844.35	27.65	1.963	0.30(0.24)	0.80	7224.0	10250.00
11	34092.47	31.37	1.824	0.30(0.24)	0.80	8466.4	10220.00
12	34874.20	33.67	1.765	0.30(0.24)	0.81	9232.2	203.00
13	40619.81	48.70	1.419	0.30(0.25)	0.83	16851.6	50260.00
14	42885.79	57.30	1.307	0.30(0.26)	0.86	21582.6	13600.00
15	45669.92	69.82	1.210	0.30(0.26)	0.88	28215.2	13100.00
16	47242.87	76.04	1.167	0.30(0.27)	0.89	31207.1	11801.00
17	49688.11	85.22	1.105	0.30(0.27)	0.90	36251.8	11530.00
18	51039.38	90.88	1.069	0.30(0.27)	0.91	40136.5	13510.00
19	52109.54	95.63	1.047	0.30(0.27)	0.92	43290.0	13010.00
20	53194.38	100.44	1.025	0.30(0.28)	0.92	46512.4	11330.00
21	53831.36	106.70	0.997	0.30(0.28)	0.93	50943.5	11130.00
22	53237.89	114.34	0.962	0.30(0.28)	0.93	54937.4	12330.00
23	52586.66	121.02	0.933	0.30(0.28)	0.94	58280.6	12400.00
24	51567.10	129.77	0.911	0.30(0.28)	0.94	61649.4	12201.00

25 50074.91 139.23 0.886 0.30(0.28) 0.94 64103.5 12101.10
 26 49396.54 143.32 0.875 0.30(0.28) 0.94 64952.6 10400.00
 27 47559.73 151.52 0.854 0.30(0.28) 0.94 66267.7 12010.00
 28 46050.97 157.54 0.838 0.30(0.28) 0.94 66581.4 10210.00
 29 41702.95 184.08 0.775 0.30(0.28) 0.94 67314.2 10100.00
 TOTAL AREA (ACRES) = 67314.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 53831.36 Tc(MIN.) = 106.704
 EFFECTIVE AREA(ACRES) = 50943.46 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.89
 TOTAL AREA(ACRES) = 67314.2
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128508.59 FEET.

FLOW PROCESS FROM NODE 13740.00 TO NODE 13741.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 161.03 DOWNSTREAM(FEET) = 141.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 364.08 CHANNEL SLOPE = 0.0550
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 9.16
 CHANNEL FLOW THRU SUBAREA(CFS) = 53831.36
 FLOW VELOCITY(FEET/SEC.) = 43.02 FLOW DEPTH(FEET) = 9.16
 TRAVEL TIME(MIN.) = 0.14 Tc(MIN.) = 106.85
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128872.66 FEET.

FLOW PROCESS FROM NODE 13740.00 TO NODE 13741.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

FLOW PROCESS FROM NODE 13741.00 TO NODE 13741.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506104b.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	82.60	19.10	0.30(0.24)	0.80	44.3	10400.00
TOTAL AREA(ACRES) =						44.3

FLOW PROCESS FROM NODE 13741.00 TO NODE 13741.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28125.02	17.92	2.606	0.30(0.24)	0.80	4094.1	10300.00

2	28180.86	18.06	2.591	0.30(0.24)	0.80	4127.1	10230.00
3	28518.91	18.71	2.527	0.30(0.24)	0.80	4302.8	10380.00
4	29699.74	21.00	2.334	0.30(0.24)	0.80	4915.0	10320.00
5	29947.17	21.48	2.303	0.30(0.24)	0.80	5042.5	300.00
6	30819.56	23.22	2.193	0.30(0.24)	0.80	5648.7	10360.00
7	32220.68	26.03	2.034	0.30(0.24)	0.80	6620.5	10340.00
8	32291.67	26.17	2.028	0.30(0.24)	0.80	6669.5	210.00
9	32638.05	27.20	1.983	0.30(0.24)	0.80	7017.2	10200.00
10	32844.35	27.81	1.956	0.30(0.24)	0.80	7224.0	10250.00
11	34092.47	31.53	1.820	0.30(0.24)	0.80	8466.4	10220.00
12	34874.20	33.83	1.761	0.30(0.24)	0.81	9232.2	203.00
13	40619.81	48.85	1.415	0.30(0.25)	0.83	16851.6	50260.00
14	42885.79	57.45	1.305	0.30(0.26)	0.86	21582.6	13600.00
15	45669.92	69.97	1.209	0.30(0.26)	0.88	28215.2	13100.00
16	47242.87	76.19	1.166	0.30(0.27)	0.89	31207.1	11801.00
17	49688.11	85.36	1.104	0.30(0.27)	0.90	36251.8	11530.00
18	51039.38	91.03	1.068	0.30(0.27)	0.91	40136.5	13510.00
19	52109.54	95.77	1.047	0.30(0.27)	0.92	43290.0	13010.00
20	53194.38	100.59	1.025	0.30(0.28)	0.92	46512.4	11330.00
21	53831.36	106.85	0.996	0.30(0.28)	0.93	50943.5	11130.00
22	53237.89	114.48	0.961	0.30(0.28)	0.93	54937.4	12330.00
23	52586.66	121.16	0.933	0.30(0.28)	0.94	58280.6	12400.00
24	51567.10	129.92	0.910	0.30(0.28)	0.94	61649.4	12201.00
25	50074.91	139.38	0.886	0.30(0.28)	0.94	64103.5	12101.10
26	49396.54	143.47	0.875	0.30(0.28)	0.94	64952.6	10400.00
27	47559.73	151.67	0.854	0.30(0.28)	0.94	66267.7	12010.00
28	46050.97	157.69	0.838	0.30(0.28)	0.94	66581.4	10210.00
29	41702.95	184.23	0.775	0.30(0.28)	0.94	67314.2	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128872.66 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	82.60	19.10	2.487	0.30(0.24)	0.80	44.3	10400.00
LONGEST FLOWPATH FROM NODE 10400.00 TO NODE 13741.00 =							6237.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28206.60	17.92	2.606	0.30(0.24)	0.80	4135.7	10300.00
2	28262.60	18.06	2.591	0.30(0.24)	0.80	4169.0	10230.00
3	28601.23	18.71	2.527	0.30(0.24)	0.80	4346.2	10380.00
4	28804.54	19.10	2.487	0.30(0.24)	0.80	4452.4	10400.00
5	29776.70	21.00	2.334	0.30(0.24)	0.80	4959.3	10320.00
6	30022.99	21.48	2.303	0.30(0.24)	0.80	5086.8	300.00
7	30891.33	23.22	2.193	0.30(0.24)	0.80	5693.0	10360.00
8	32286.64	26.03	2.034	0.30(0.24)	0.80	6664.8	10340.00
9	32357.40	26.17	2.028	0.30(0.24)	0.80	6713.8	210.00
10	32702.12	27.20	1.983	0.30(0.24)	0.80	7061.5	10200.00
11	32907.41	27.81	1.956	0.30(0.24)	0.80	7268.3	10250.00
12	34150.55	31.53	1.820	0.30(0.24)	0.80	8510.7	10220.00
13	34930.12	33.83	1.761	0.30(0.24)	0.81	9276.5	203.00
14	40663.03	48.85	1.415	0.30(0.25)	0.83	16895.9	50260.00
15	42924.96	57.45	1.305	0.30(0.26)	0.86	21626.9	13600.00
16	45705.53	69.97	1.209	0.30(0.26)	0.88	28259.5	13100.00
17	47276.94	76.19	1.166	0.30(0.27)	0.89	31251.4	11801.00
18	49719.89	85.36	1.104	0.30(0.27)	0.90	36296.1	11530.00
19	51069.84	91.03	1.068	0.30(0.27)	0.91	40180.8	13510.00

20	52139.20	95.77	1.047	0.30	(0.27)	0.92	43334.3	13010.00
21	53223.23	100.59	1.025	0.30	(0.28)	0.92	46556.7	11330.00
22	53859.17	106.85	0.996	0.30	(0.28)	0.93	50987.8	11130.00
23	53264.42	114.48	0.961	0.30	(0.28)	0.93	54981.7	12330.00
24	52612.14	121.16	0.933	0.30	(0.28)	0.94	58324.9	12400.00
25	51591.75	129.92	0.910	0.30	(0.28)	0.94	61693.7	12201.00
26	50098.65	139.38	0.886	0.30	(0.28)	0.94	64147.8	12101.10
27	49419.89	143.47	0.875	0.30	(0.28)	0.94	64996.9	10400.00
28	47582.30	151.67	0.854	0.30	(0.28)	0.94	66312.0	12010.00
29	46072.96	157.69	0.838	0.30	(0.28)	0.94	66625.7	10210.00
30	41722.63	184.23	0.775	0.30	(0.28)	0.94	67358.5	10100.00

TOTAL AREA (ACRES) = 67358.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 53859.17 Tc (MIN.) = 106.845
EFFECTIVE AREA (ACRES) = 50987.76 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA (ACRES) = 67358.5
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128872.66 FEET.

FLOW PROCESS FROM NODE 13741.00 TO NODE 13802.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 141.00 DOWNSTREAM (FEET) = 135.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 1533.41 CHANNEL SLOPE = 0.0039
GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 18.40
CHANNEL FLOW THRU SUBAREA (CFS) = 53859.17
FLOW VELOCITY (FEET/SEC.) = 16.86 FLOW DEPTH (FEET) = 18.40
TRAVEL TIME (MIN.) = 1.52 Tc (MIN.) = 108.36
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130406.07 FEET.

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<

PEAK FLOWRATE TABLE FILE NAME: 0506105i.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	447.60	14.36	0.30 (0.27)	0.90	208.7	10520.00
2	533.75	30.45	0.30 (0.28)	0.93	403.6	10500.00
TOTAL AREA (ACRES) =						403.6

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28206.60	19.74	2.423	0.30 (0.24)	0.80	4135.7	10300.00
2	28262.60	19.88	2.409	0.30 (0.24)	0.80	4169.0	10230.00
3	28601.23	20.52	2.364	0.30 (0.24)	0.80	4346.2	10380.00
4	28804.54	20.91	2.339	0.30 (0.24)	0.80	4452.4	10400.00
5	29776.70	22.79	2.220	0.30 (0.24)	0.80	4959.3	10320.00
6	30022.99	23.27	2.189	0.30 (0.24)	0.80	5086.8	300.00
7	30891.33	25.00	2.080	0.30 (0.24)	0.80	5693.0	10360.00
8	32286.64	27.78	1.957	0.30 (0.24)	0.80	6664.8	10340.00
9	32357.40	27.92	1.951	0.30 (0.24)	0.80	6713.8	210.00
10	32702.12	28.94	1.906	0.30 (0.24)	0.80	7061.5	10200.00
11	32907.41	29.56	1.879	0.30 (0.24)	0.80	7268.3	10250.00
12	34150.55	33.25	1.776	0.30 (0.24)	0.80	8510.7	10220.00
13	34930.12	35.54	1.718	0.30 (0.24)	0.81	9276.5	203.00
14	40663.03	50.49	1.385	0.30 (0.25)	0.83	16895.9	50260.00
15	42924.96	59.06	1.287	0.30 (0.26)	0.86	21626.9	13600.00
16	45705.53	71.56	1.198	0.30 (0.26)	0.88	28259.5	13100.00
17	47276.94	77.76	1.156	0.30 (0.27)	0.89	31251.4	11801.00
18	49719.89	86.91	1.094	0.30 (0.27)	0.90	36296.1	11530.00
19	51069.84	92.56	1.061	0.30 (0.27)	0.91	40180.8	13510.00
20	52139.20	97.30	1.040	0.30 (0.27)	0.92	43334.3	13010.00
21	53223.23	102.11	1.018	0.30 (0.28)	0.92	46556.7	11330.00
22	53859.17	108.36	0.989	0.30 (0.28)	0.93	50987.8	11130.00
23	53264.42	116.00	0.954	0.30 (0.28)	0.93	54981.7	12330.00
24	52612.14	122.69	0.929	0.30 (0.28)	0.94	58324.9	12400.00
25	51591.75	131.45	0.906	0.30 (0.28)	0.94	61693.7	12201.00
26	50098.65	140.92	0.882	0.30 (0.28)	0.94	64147.8	12101.10
27	49419.89	145.02	0.871	0.30 (0.28)	0.94	64996.9	10400.00
28	47582.30	153.24	0.850	0.30 (0.28)	0.94	66312.0	12010.00
29	46072.96	159.28	0.834	0.30 (0.28)	0.94	66625.7	10210.00
30	41722.63	185.86	0.773	0.30 (0.28)	0.94	67358.5	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130406.07 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (Min.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	447.60	14.36	3.006	0.30 (0.27)	0.90	208.7	10520.00
2	533.75	30.45	1.848	0.30 (0.28)	0.93	403.6	10500.00

LONGEST FLOWPATH FROM NODE 10500.00 TO NODE 13802.00 = 12187.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	26450.22	14.36	3.006	0.30 (0.24)	0.81	3218.1	10520.00
2	28682.99	19.74	2.423	0.30 (0.24)	0.81	4409.6	10300.00
3	28739.76	19.88	2.409	0.30 (0.24)	0.81	4444.6	10230.00
4	29081.80	20.52	2.364	0.30 (0.24)	0.81	4629.5	10380.00
5	29287.20	20.91	2.339	0.30 (0.24)	0.81	4740.4	10400.00
6	30269.43	22.79	2.220	0.30 (0.24)	0.81	5270.1	10320.00
7	30518.31	23.27	2.189	0.30 (0.24)	0.81	5403.5	300.00
8	31395.88	25.00	2.080	0.30 (0.24)	0.81	6030.6	10360.00
9	32806.10	27.78	1.957	0.30 (0.24)	0.81	7036.1	10340.00
10	32877.61	27.92	1.951	0.30 (0.24)	0.81	7086.8	210.00

11	33227.80	28.94	1.906	0.30	(0.24)	0.81	7446.9	10200.00
12	33436.37	29.56	1.879	0.30	(0.24)	0.81	7661.1	10250.00
13	33742.02	30.45	1.848	0.30	(0.24)	0.81	7972.6	10500.00
14	34660.00	33.25	1.776	0.30	(0.24)	0.81	8914.3	10220.00
15	35419.72	35.54	1.718	0.30	(0.24)	0.81	9680.1	203.00
16	41039.60	50.49	1.385	0.30	(0.25)	0.83	17299.5	50260.00
17	43268.02	59.06	1.287	0.30	(0.26)	0.86	22030.5	13600.00
18	46018.32	71.56	1.198	0.30	(0.26)	0.88	28663.1	13100.00
19	47575.46	77.76	1.156	0.30	(0.27)	0.89	31655.0	11801.00
20	49997.35	86.91	1.094	0.30	(0.27)	0.90	36699.7	11530.00
21	51336.21	92.56	1.061	0.30	(0.27)	0.91	40584.4	13510.00
22	52398.22	97.30	1.040	0.30	(0.27)	0.92	43737.9	13010.00
23	53474.79	102.11	1.018	0.30	(0.28)	0.92	46960.3	11330.00
24	54101.01	108.36	0.989	0.30	(0.28)	0.93	51391.4	11130.00
25	53494.40	116.00	0.954	0.30	(0.28)	0.93	55385.3	12330.00
26	52833.54	122.69	0.929	0.30	(0.28)	0.94	58728.5	12400.00
27	51805.39	131.45	0.906	0.30	(0.28)	0.94	62097.3	12201.00
28	50303.92	140.92	0.882	0.30	(0.28)	0.94	64551.4	12101.10
29	49621.54	145.02	0.871	0.30	(0.28)	0.94	65400.5	10400.00
30	47776.68	153.24	0.850	0.30	(0.28)	0.94	66715.6	12010.00
31	46262.00	159.28	0.834	0.30	(0.28)	0.94	67029.3	10210.00
32	41891.07	185.86	0.773	0.30	(0.28)	0.94	67762.1	10100.00

TOTAL AREA (ACRES) = 67762.1

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 54101.01 Tc (MIN.) = 108.361
EFFECTIVE AREA (ACRES) = 51391.36 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA (ACRES) = 67762.1
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130406.07 FEET.

FLOW PROCESS FROM NODE 13802.00 TO NODE 13803.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 135.00 DOWNSTREAM (FEET) = 134.99
CHANNEL LENGTH THRU SUBAREA (FEET) = 207.23 CHANNEL SLOPE = 0.0000
GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 52.24
CHANNEL FLOW THRU SUBAREA (CFS) = 54101.01
FLOW VELOCITY (FEET/SEC.) = 3.35 FLOW DEPTH (FEET) = 52.24
TRAVEL TIME (MIN.) = 1.03 Tc (MIN.) = 109.39
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130613.30 FEET.

FLOW PROCESS FROM NODE 13802.00 TO NODE 13803.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506106b.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	73.36	17.31	0.30 (0.20)	0.67	36.9	10600.00
TOTAL AREA (ACRES) =			36.9			

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	26450.22	15.60	2.839	0.30 (0.24)	0.81	3218.1	10520.00
2	28682.99	20.95	2.337	0.30 (0.24)	0.81	4409.6	10300.00
3	28739.76	21.10	2.327	0.30 (0.24)	0.81	4444.6	10230.00
4	29081.80	21.73	2.287	0.30 (0.24)	0.81	4629.5	10380.00
5	29287.20	22.12	2.263	0.30 (0.24)	0.81	4740.4	10400.00
6	30269.43	23.99	2.144	0.30 (0.24)	0.81	5270.1	10320.00
7	30518.31	24.47	2.114	0.30 (0.24)	0.81	5403.5	300.00
8	31395.88	26.18	2.028	0.30 (0.24)	0.81	6030.6	10360.00
9	32806.10	28.95	1.905	0.30 (0.24)	0.81	7036.1	10340.00
10	32877.61	29.09	1.899	0.30 (0.24)	0.81	7086.8	210.00
11	33227.80	30.11	1.856	0.30 (0.24)	0.81	7446.9	10200.00
12	33436.37	30.72	1.841	0.30 (0.24)	0.81	7661.1	10250.00
13	33742.02	31.61	1.818	0.30 (0.24)	0.81	7972.6	10500.00
14	34660.00	34.41	1.747	0.30 (0.24)	0.81	8914.3	10220.00
15	35419.72	36.69	1.688	0.30 (0.24)	0.81	9680.1	203.00
16	41039.60	51.60	1.373	0.30 (0.25)	0.83	17299.5	50260.00
17	43268.02	60.15	1.275	0.30 (0.26)	0.86	22030.5	13600.00
18	46018.32	72.63	1.191	0.30 (0.26)	0.88	28663.1	13100.00
19	47575.46	78.82	1.149	0.30 (0.27)	0.89	31655.0	11801.00
20	49997.35	87.97	1.087	0.30 (0.27)	0.90	36699.7	11530.00
21	51336.21	93.61	1.057	0.30 (0.27)	0.91	40584.4	13510.00
22	52398.22	98.34	1.035	0.30 (0.27)	0.92	43737.9	13010.00
23	53474.79	103.14	1.013	0.30 (0.28)	0.92	46960.3	11330.00
24	54101.01	109.39	0.984	0.30 (0.28)	0.93	51391.4	11130.00
25	53494.40	117.03	0.950	0.30 (0.28)	0.93	55385.3	12330.00
26	52833.54	123.73	0.926	0.30 (0.28)	0.94	58728.5	12400.00
27	51805.39	132.49	0.904	0.30 (0.28)	0.94	62097.3	12201.00
28	50303.92	141.97	0.879	0.30 (0.28)	0.94	64551.4	12101.10
29	49621.54	146.07	0.868	0.30 (0.28)	0.94	65400.5	10400.00
30	47776.68	154.30	0.847	0.30 (0.28)	0.94	66715.6	12010.00
31	46262.00	160.35	0.831	0.30 (0.28)	0.94	67029.3	10210.00
32	41891.07	186.96	0.772	0.30 (0.28)	0.94	67762.1	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130613.30 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	73.36	17.31	2.667	0.30 (0.20)	0.67	36.9	10600.00

LONGEST FLOWPATH FROM NODE 10600.00 TO NODE 13803.00 = 1713.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM	Q	Tc	Intensity	Fp (Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	---------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	26520.94	15.60	2.839	0.30 (0.24) 0.81	3251.4	10520.00
2	27235.77	17.31	2.667	0.30 (0.24) 0.81	3635.1	10600.00
3	28746.51	20.95	2.337	0.30 (0.24) 0.81	4446.5	10300.00
4	28803.02	21.10	2.327	0.30 (0.24) 0.81	4481.5	10230.00
5	29143.86	21.73	2.287	0.30 (0.24) 0.81	4666.4	10380.00
6	29348.53	22.12	2.263	0.30 (0.24) 0.81	4777.3	10400.00
7	30327.23	23.99	2.144	0.30 (0.24) 0.81	5307.0	10320.00
8	30575.21	24.47	2.114	0.30 (0.24) 0.81	5440.4	300.00
9	31450.22	26.18	2.028	0.30 (0.24) 0.81	6067.5	10360.00
10	32856.79	28.95	1.905	0.30 (0.24) 0.81	7073.0	10340.00
11	32928.12	29.09	1.899	0.30 (0.24) 0.81	7123.7	210.00
12	33277.04	30.11	1.856	0.30 (0.24) 0.81	7483.8	10200.00
13	33485.14	30.72	1.841	0.30 (0.24) 0.81	7698.0	10250.00
14	33790.12	31.61	1.818	0.30 (0.24) 0.81	8009.5	10500.00
15	34705.97	34.41	1.747	0.30 (0.24) 0.81	8951.2	10220.00
16	35463.96	36.69	1.688	0.30 (0.24) 0.81	9717.0	203.00
17	41074.45	51.60	1.373	0.30 (0.25) 0.83	17336.4	50260.00
18	43299.97	60.15	1.275	0.30 (0.26) 0.86	22067.4	13600.00
19	46047.76	72.63	1.191	0.30 (0.26) 0.88	28700.0	13100.00
20	47603.65	78.82	1.149	0.30 (0.27) 0.89	31691.9	11801.00
21	50023.70	87.97	1.087	0.30 (0.27) 0.90	36736.6	11530.00
22	51361.66	93.61	1.057	0.30 (0.27) 0.91	40621.3	13510.00
23	52423.03	98.34	1.035	0.30 (0.27) 0.92	43774.8	13010.00
24	53498.94	103.14	1.013	0.30 (0.28) 0.92	46997.2	11330.00
25	54124.32	109.39	0.984	0.30 (0.28) 0.93	51428.3	11130.00
26	53516.66	117.03	0.950	0.30 (0.28) 0.93	55422.2	12330.00
27	52855.11	123.73	0.926	0.30 (0.28) 0.94	58765.4	12400.00
28	51826.29	132.49	0.904	0.30 (0.28) 0.94	62134.2	12201.00
29	50324.08	141.97	0.879	0.30 (0.28) 0.94	64588.3	12101.10
30	49641.39	146.07	0.868	0.30 (0.28) 0.94	65437.4	10400.00
31	47795.89	154.30	0.847	0.30 (0.28) 0.94	66752.5	12010.00
32	46280.75	160.35	0.831	0.30 (0.28) 0.94	67066.2	10210.00
33	41908.06	186.96	0.772	0.30 (0.28) 0.94	67799.0	10100.00
TOTAL AREA (ACRES) = 67799.0						

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 54124.32 Tc (MIN.) = 109.391
EFFECTIVE AREA (ACRES) = 51428.26 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA (ACRES) = 67799.0
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130613.30 FEET.

=====

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 67799.0 TC (MIN.) = 109.39
EFFECTIVE AREA (ACRES) = 51428.26 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.927
PEAK FLOW RATE (CFS) = 54124.32

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	26520.94	15.60	2.839	0.30 (0.24) 0.81	3251.4	10520.00	
2	27235.77	17.31	2.667	0.30 (0.24) 0.81	3635.1	10600.00	
3	28746.51	20.95	2.337	0.30 (0.24) 0.81	4446.5	10300.00	
4	28803.02	21.10	2.327	0.30 (0.24) 0.81	4481.5	10230.00	
5	29143.86	21.73	2.287	0.30 (0.24) 0.81	4666.4	10380.00	
6	29348.53	22.12	2.263	0.30 (0.24) 0.81	4777.3	10400.00	

7	30327.23	23.99	2.144	0.30 (0.24) 0.81	5307.0	10320.00
8	30575.21	24.47	2.114	0.30 (0.24) 0.81	5440.4	300.00
9	31450.22	26.18	2.028	0.30 (0.24) 0.81	6067.5	10360.00
10	32856.79	28.95	1.905	0.30 (0.24) 0.81	7073.0	10340.00
11	32928.12	29.09	1.899	0.30 (0.24) 0.81	7123.7	210.00
12	33277.04	30.11	1.856	0.30 (0.24) 0.81	7483.8	10200.00
13	33485.14	30.72	1.841	0.30 (0.24) 0.81	7698.0	10250.00
14	33790.12	31.61	1.818	0.30 (0.24) 0.81	8009.5	10500.00
15	34705.97	34.41	1.747	0.30 (0.24) 0.81	8951.2	10220.00
16	35463.96	36.69	1.688	0.30 (0.24) 0.81	9717.0	203.00
17	41074.45	51.60	1.373	0.30 (0.25) 0.83	17336.4	50260.00
18	43299.97	60.15	1.275	0.30 (0.26) 0.86	22067.4	13600.00
19	46047.76	72.63	1.191	0.30 (0.26) 0.88	28700.0	13100.00
20	47603.65	78.82	1.149	0.30 (0.27) 0.89	31691.9	11801.00
21	50023.70	87.97	1.087	0.30 (0.27) 0.90	36736.6	11530.00
22	51361.66	93.61	1.057	0.30 (0.27) 0.91	40621.3	13510.00
23	52423.03	98.34	1.035	0.30 (0.27) 0.92	43774.8	13010.00
24	53498.94	103.14	1.013	0.30 (0.28) 0.92	46997.2	11330.00
25	54124.32	109.39	0.984	0.30 (0.28) 0.93	51428.3	11130.00
26	53516.66	117.03	0.950	0.30 (0.28) 0.93	55422.2	12330.00
27	52855.11	123.73	0.926	0.30 (0.28) 0.94	58765.4	12400.00
28	51826.29	132.49	0.904	0.30 (0.28) 0.94	62134.2	12201.00
29	50324.08	141.97	0.879	0.30 (0.28) 0.94	64588.3	12101.10
30	49641.39	146.07	0.868	0.30 (0.28) 0.94	65437.4	10400.00
31	47795.89	154.30	0.847	0.30 (0.28) 0.94	66752.5	12010.00
32	46280.75	160.35	0.831	0.30 (0.28) 0.94	67066.2	10210.00
33	41908.06	186.96	0.772	0.30 (0.28) 0.94	67799.0	10100.00

=====

END OF RATIONAL METHOD ANALYSIS

=====

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2010 Advanced Engineering Software (aes)
Ver. 17.0 Release Date: 07/01/2010 License ID 1527

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 138 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 100-YR EV AUG 2023 ROKAMOTO *

FILE NAME: RU00EV38.DAT
TIME/DATE OF STUDY: 21:38 08/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 100.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.750
- 2) 10.00; 3.727
- 3) 15.00; 2.893
- 4) 20.00; 2.393
- 5) 25.00; 2.078
- 6) 30.00; 1.857
- 7) 40.00; 1.601
- 8) 50.00; 1.389
- 9) 60.00; 1.274
- 10) 90.00; 1.070
- 11) 120.00; 0.933
- 12) 180.00; 0.777
- 13) 360.00; 0.572
- 14) 1200.00; 0.248

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU00EV37.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27235.77	17.31	0.30 (0.24)	0.81	3635.1	10600.00
2	29348.53	22.12	0.30 (0.24)	0.81	4777.3	10400.00
3	33790.12	31.61	0.30 (0.24)	0.81	8009.5	10500.00
4	35463.96	36.69	0.30 (0.24)	0.81	9717.0	203.00
5	41074.45	51.60	0.30 (0.25)	0.83	17336.4	50260.00
6	43299.97	60.15	0.30 (0.26)	0.86	22067.4	13600.00
7	46047.76	72.63	0.30 (0.26)	0.88	28700.0	13100.00
8	47603.65	78.82	0.30 (0.27)	0.89	31691.9	11801.00
9	50023.70	87.97	0.30 (0.27)	0.90	36736.6	11530.00
10	51361.66	93.61	0.30 (0.27)	0.91	40621.3	13510.00
11	52423.03	98.34	0.30 (0.27)	0.92	43774.8	13010.00
12	53498.94	103.14	0.30 (0.28)	0.92	46997.2	11330.00
13	54124.32	109.39	0.30 (0.28)	0.93	51428.3	11130.00
14	53516.66	117.03	0.30 (0.28)	0.93	55422.2	12330.00
15	52855.11	123.73	0.30 (0.28)	0.94	58765.4	12400.00
16	51826.29	132.49	0.30 (0.28)	0.94	62134.2	12201.00
17	50324.08	141.97	0.30 (0.28)	0.94	64588.3	12101.10
18	47795.89	154.30	0.30 (0.28)	0.94	66752.5	12010.00
19	46280.75	160.35	0.30 (0.28)	0.94	67066.2	10210.00
20	41908.06	186.96	0.30 (0.28)	0.94	67799.0	10100.00
TOTAL AREA (ACRES) =						67799.0

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27235.77	17.31	0.30 (0.24)	0.81	3635.1	10600.00
2	29348.53	22.12	0.30 (0.24)	0.81	4777.3	10400.00
3	33790.12	31.61	0.30 (0.24)	0.81	8009.5	10500.00
4	35463.96	36.69	0.30 (0.24)	0.81	9717.0	203.00
5	41074.45	51.60	0.30 (0.25)	0.83	17336.4	50260.00
6	43299.97	60.15	0.30 (0.26)	0.86	22067.4	13600.00
7	46047.76	72.63	0.30 (0.26)	0.88	28700.0	13100.00
8	47603.65	78.82	0.30 (0.27)	0.89	31691.9	11801.00
9	50023.70	87.97	0.30 (0.27)	0.90	36736.6	11530.00
10	51361.66	93.61	0.30 (0.27)	0.91	40621.3	13510.00
11	52423.03	98.34	0.30 (0.27)	0.92	43774.8	13010.00
12	53498.94	103.14	0.30 (0.28)	0.92	46997.2	11330.00
13	54124.32	109.39	0.30 (0.28)	0.93	51428.3	11130.00

14 53516.66 117.03 0.30 (0.28) 0.93 55422.2 12330.00
 15 52855.11 123.73 0.30 (0.28) 0.94 58765.4 12400.00
 16 51826.29 132.49 0.30 (0.28) 0.94 62134.2 12201.00
 17 50324.08 141.97 0.30 (0.28) 0.94 64588.3 12101.10
 18 47795.89 154.30 0.30 (0.28) 0.94 66752.5 12010.00
 19 46280.75 160.35 0.30 (0.28) 0.94 67066.2 10210.00
 20 41908.06 186.96 0.30 (0.28) 0.94 67799.0 10100.00
 TOTAL AREA (ACRES) = 67799.0

 FLOW PROCESS FROM NODE 13803.00 TO NODE 13820.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 134.99 DOWNSTREAM(FEET) = 134.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 926.91 CHANNEL SLOPE = 0.0011
 GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT (FEET) = 25.47
 * 100 YEAR RAINFALL INTENSITY (INCH/HR) = 0.975

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	31.44	0.30	0.983	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.983
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 54133.94
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 10.53
 AVERAGE FLOW DEPTH (FEET) = 25.47 TRAVEL TIME (MIN.) = 1.47
 Tc (MIN.) = 110.86

SUBAREA AREA (ACRES) = 31.44 SUBAREA RUNOFF (CFS) = 19.24
 EFFECTIVE AREA (ACRES) = 51459.70 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA (ACRES) = 67830.4 PEAK FLOW RATE (CFS) = 54124.32
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT (FEET) = 25.46

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 25.46 FLOW VELOCITY (FEET/SEC.) = 10.53
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13820.00 = 131540.20 FEET.

 FLOW PROCESS FROM NODE 13803.00 TO NODE 13820.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

=====

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
 TIME OF CONCENTRATION (MIN.) = 110.86
 RAINFALL INTENSITY (INCH/HR) = 0.97
 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.93
 EFFECTIVE STREAM AREA (ACRES) = 51459.70
 TOTAL STREAM AREA (ACRES) = 67830.41

PEAK FLOW RATE (CFS) AT CONFLUENCE = 54124.32

 FLOW PROCESS FROM NODE 13810.00 TO NODE 13811.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH (FEET) = 648.54
 ELEVATION DATA: UPSTREAM (FEET) = 756.46 DOWNSTREAM (FEET) = 586.02

Tc = K * [(LENGTH** 3.00) / (ELEVATION CHANGE)] ** 0.20
 SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 12.293
 * 100 YEAR RAINFALL INTENSITY (INCH/HR) = 3.345

SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL, BROADLEAF"	-	5.58	0.30	1.000	65	12.29

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA RUNOFF (CFS) = 15.29
 TOTAL AREA (ACRES) = 5.58 PEAK FLOW RATE (CFS) = 15.29

 FLOW PROCESS FROM NODE 13811.00 TO NODE 13811.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 586.02 DOWNSTREAM (FEET) = 437.69
 CHANNEL LENGTH THRU SUBAREA (FEET) = 696.28 CHANNEL SLOPE = 0.2130
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 0.49
 * 100 YEAR RAINFALL INTENSITY (INCH/HR) = 3.044

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	14.79	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 33.60
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.45
 AVERAGE FLOW DEPTH (FEET) = 0.48 TRAVEL TIME (MIN.) = 1.80
 Tc (MIN.) = 14.09

SUBAREA AREA (ACRES) = 14.79 SUBAREA RUNOFF (CFS) = 36.53
 EFFECTIVE AREA (ACRES) = 20.37 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 20.4 PEAK FLOW RATE (CFS) = 50.31
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 0.60

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 0.60 FLOW VELOCITY (FEET/SEC.) = 7.49
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13811.50 = 1344.82 FEET.

```

*****
FLOW PROCESS FROM NODE 13811.50 TO NODE 13812.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 437.69 DOWNSTREAM(FEET) = 402.36
CHANNEL LENGTH THRU SUBAREA(FEET) = 681.04 CHANNEL SLOPE = 0.0519
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.12
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.768
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp      Ap      SCS
LAND USE            GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN
USER-DEFINED        -       18.41    0.30    1.000    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 70.77
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.27
AVERAGE FLOW DEPTH(FEET) = 1.10 TRAVEL TIME(MIN.) = 2.16
Tc(MIN.) = 16.25
SUBAREA AREA(ACRES) = 18.41 SUBAREA RUNOFF(CFS) = 40.90
EFFECTIVE AREA(ACRES) = 38.78 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 38.8 PEAK FLOW RATE(CFS) = 86.15
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.23

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.23 FLOW VELOCITY(FEET/SEC.) = 5.60
LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13812.00 = 2025.86 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13812.00 TO NODE 13813.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 402.36 DOWNSTREAM(FEET) = 259.72
CHANNEL LENGTH THRU SUBAREA(FEET) = 1282.56 CHANNEL SLOPE = 0.1112
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.18
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.500
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp      Ap      SCS
LAND USE            GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN
USER-DEFINED        -       27.87    0.30    0.858    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.858
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 114.30
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.96
AVERAGE FLOW DEPTH(FEET) = 1.16 TRAVEL TIME(MIN.) = 2.68
Tc(MIN.) = 18.93
SUBAREA AREA(ACRES) = 27.87 SUBAREA RUNOFF(CFS) = 56.24
EFFECTIVE AREA(ACRES) = 66.65 AREA-AVERAGED Fm(INCH/HR) = 0.28

```

```

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94
TOTAL AREA(ACRES) = 66.7 PEAK FLOW RATE(CFS) = 133.02
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.27

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.27 FLOW VELOCITY(FEET/SEC.) = 8.34
LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13813.00 = 3308.42 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 31
-----

```

```

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<
=====

```

```

ELEVATION DATA: UPSTREAM(FEET) = 259.72 DOWNSTREAM(FEET) = 137.00
FLOW LENGTH(FEET) = 2412.88 MANNING'S N = 0.013
DEPTH OF FLOW IN 36.0 INCH PIPE IS 27.5 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 22.94
ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 133.02
PIPE TRAVEL TIME(MIN.) = 1.75 Tc(MIN.) = 20.69
LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13820.00 = 5721.30 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 20.69
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.350
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp      Ap      SCS
LAND USE            GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN
USER-DEFINED        -       83.64    0.30    0.570    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.570
SUBAREA AREA(ACRES) = 83.64 SUBAREA RUNOFF(CFS) = 164.01
EFFECTIVE AREA(ACRES) = 150.29 AREA-AVERAGED Fm(INCH/HR) = 0.22
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.73
TOTAL AREA(ACRES) = 150.3 PEAK FLOW RATE(CFS) = 288.03

```

```

*****
FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 1
-----

```

```

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<
=====

```

```

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 20.69
RAINFALL INTENSITY(INCH/HR) = 2.35
AREA-AVERAGED Fm(INCH/HR) = 0.22
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.73
EFFECTIVE STREAM AREA(ACRES) = 150.29
TOTAL STREAM AREA(ACRES) = 150.29

```

PEAK FLOW RATE(CFS) AT CONFLUENCE = 288.03

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27235.77	19.08	2.485	0.30(0.24)	0.81	3666.5	10600.00
1	29348.53	23.85	2.150	0.30(0.24)	0.81	4808.8	10400.00
1	33790.12	33.28	1.773	0.30(0.24)	0.81	8040.9	10500.00
1	35463.96	38.34	1.644	0.30(0.24)	0.81	9748.4	203.00
1	41074.45	53.18	1.352	0.30(0.25)	0.83	17367.8	50260.00
1	43299.97	61.71	1.262	0.30(0.26)	0.86	22098.9	13600.00
1	46047.76	74.16	1.178	0.30(0.26)	0.88	28731.4	13100.00
1	47603.65	80.34	1.136	0.30(0.27)	0.89	31723.4	11801.00
1	50023.70	89.46	1.074	0.30(0.27)	0.90	36768.0	11530.00
1	51361.66	95.10	1.047	0.30(0.27)	0.91	40652.8	13510.00
1	52423.03	99.82	1.025	0.30(0.27)	0.92	43806.3	13010.00
1	53498.94	104.61	1.003	0.30(0.28)	0.92	47028.7	11330.00
1	54124.32	110.86	0.975	0.30(0.28)	0.93	51459.7	11130.00
1	53516.66	118.50	0.940	0.30(0.28)	0.93	55453.7	12330.00
1	52855.11	125.20	0.919	0.30(0.28)	0.94	58796.9	12400.00
1	51826.29	133.98	0.897	0.30(0.28)	0.94	62165.6	12201.00
1	50324.08	143.47	0.872	0.30(0.28)	0.94	64619.8	12101.10
1	47795.89	155.82	0.840	0.30(0.28)	0.94	66784.0	12010.00
1	46280.75	161.88	0.824	0.30(0.28)	0.94	67097.7	10210.00
1	41908.06	188.53	0.767	0.30(0.28)	0.94	67830.4	10100.00
2	288.03	20.69	2.350	0.30(0.22)	0.73	150.3	13810.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27518.30	19.08	2.485	0.30(0.24)	0.81	3805.1	10600.00
2	28236.09	20.69	2.350	0.30(0.24)	0.81	4201.9	13810.00
3	29609.60	23.85	2.150	0.30(0.24)	0.81	4959.0	10400.00
4	34000.14	33.28	1.773	0.30(0.24)	0.81	8191.2	10500.00
5	35656.49	38.34	1.644	0.30(0.24)	0.81	9898.7	203.00
6	41227.59	53.18	1.352	0.30(0.25)	0.83	17518.1	50260.00
7	43440.93	61.71	1.262	0.30(0.26)	0.86	22249.2	13600.00
8	46177.26	74.16	1.178	0.30(0.26)	0.88	28881.7	13100.00
9	47727.47	80.34	1.136	0.30(0.27)	0.89	31873.7	11801.00
10	50139.13	89.46	1.074	0.30(0.27)	0.90	36918.3	11530.00
11	51473.45	95.10	1.047	0.30(0.27)	0.91	40803.1	13510.00
12	52531.90	99.82	1.025	0.30(0.27)	0.91	43956.6	13010.00
13	53604.85	104.61	1.003	0.30(0.28)	0.92	47179.0	11330.00
14	54226.37	110.86	0.975	0.30(0.28)	0.93	51610.0	11130.00
15	53614.00	118.50	0.940	0.30(0.28)	0.93	55604.0	12330.00
16	52949.69	125.20	0.919	0.30(0.28)	0.93	58947.1	12400.00
17	51917.78	133.98	0.897	0.30(0.28)	0.94	62315.9	12201.00
18	50412.23	143.47	0.872	0.30(0.28)	0.94	64770.1	12101.10
19	47879.70	155.82	0.840	0.30(0.28)	0.94	66934.3	12010.00
20	46362.43	161.88	0.824	0.30(0.28)	0.94	67248.0	10210.00
21	41982.05	188.53	0.767	0.30(0.28)	0.94	67980.7	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 54226.37 Tc(MIN.) = 110.86
EFFECTIVE AREA(ACRES) = 51609.99 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA(ACRES) = 67980.7

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13820.00 = 131540.20 FEET.

FLOW PROCESS FROM NODE 13820.00 TO NODE 13840.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 137.00 DOWNSTREAM(FEET) = 133.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 1261.34 CHANNEL SLOPE = 0.0032

GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT(FEET) = 19.47

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 0.969

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS

LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

USER-DEFINED - 31.60 0.30 0.683 -

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.683

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 54237.23

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 15.65

AVERAGE FLOW DEPTH(FEET) = 19.47 TRAVEL TIME(MIN.) = 1.34

Tc(MIN.) = 112.20

SUBAREA AREA(ACRES) = 31.60 SUBAREA RUNOFF(CFS) = 21.72

EFFECTIVE AREA(ACRES) = 51641.59 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA(ACRES) = 68012.3 PEAK FLOW RATE(CFS) = 54226.37

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT(FEET) = 19.47

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 19.47 FLOW VELOCITY(FEET/SEC.) = 15.65

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13840.00 = 132801.55 FEET.

FLOW PROCESS FROM NODE 13820.00 TO NODE 13840.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

TOTAL NUMBER OF STREAMS = 2

CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:

TIME OF CONCENTRATION(MIN.) = 112.20

RAINFALL INTENSITY(INCH/HR) = 0.97

AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.93

EFFECTIVE STREAM AREA(ACRES) = 51641.59

TOTAL STREAM AREA(ACRES) = 68012.30

PEAK FLOW RATE(CFS) AT CONFLUENCE = 54226.37

FLOW PROCESS FROM NODE 13830.00 TO NODE 13831.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH (FEET) = 744.71
ELEVATION DATA: UPSTREAM (FEET) = 1100.95 DOWNSTREAM (FEET) = 959.21

Tc = K * [(LENGTH** 3.00) / (ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 13.858
* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 3.083
SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER						
"CHAPARRAL, BROADLEAF"	-	5.06	0.30	1.000	65	13.86

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF (CFS) = 12.68
TOTAL AREA (ACRES) = 5.06 PEAK FLOW RATE (CFS) = 12.68

FLOW PROCESS FROM NODE 13831.00 TO NODE 13832.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 959.21 DOWNSTREAM (FEET) = 832.83
CHANNEL LENGTH THRU SUBAREA (FEET) = 1076.71 CHANNEL SLOPE = 0.1174
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT (FEET) = 0.74
* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.711
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	32.57	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 48.16
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.06
AVERAGE FLOW DEPTH (FEET) = 0.70 TRAVEL TIME (MIN.) = 2.96
Tc (MIN.) = 16.82
SUBAREA AREA (ACRES) = 32.57 SUBAREA RUNOFF (CFS) = 70.68
EFFECTIVE AREA (ACRES) = 37.63 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 37.6 PEAK FLOW RATE (CFS) = 81.66
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.95

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.95 FLOW VELOCITY (FEET/SEC.) = 7.23
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13832.00 = 1821.42 FEET.

FLOW PROCESS FROM NODE 13832.00 TO NODE 13833.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 832.83 DOWNSTREAM (FEET) = 572.49
CHANNEL LENGTH THRU SUBAREA (FEET) = 1883.58 CHANNEL SLOPE = 0.1382
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 1.11
* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.361
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	32.23	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 111.59
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.49
AVERAGE FLOW DEPTH (FEET) = 1.08 TRAVEL TIME (MIN.) = 3.70
Tc (MIN.) = 20.51
SUBAREA AREA (ACRES) = 32.23 SUBAREA RUNOFF (CFS) = 59.77
EFFECTIVE AREA (ACRES) = 69.86 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 69.9 PEAK FLOW RATE (CFS) = 129.56
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 1.18

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 1.18 FLOW VELOCITY (FEET/SEC.) = 8.90
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13833.00 = 3705.00 FEET.

FLOW PROCESS FROM NODE 13833.00 TO NODE 13834.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 572.49 DOWNSTREAM (FEET) = 471.65
CHANNEL LENGTH THRU SUBAREA (FEET) = 943.78 CHANNEL SLOPE = 0.1068
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT (FEET) = 1.40
* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.246
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	27.51	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 153.65
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.62
AVERAGE FLOW DEPTH (FEET) = 1.39 TRAVEL TIME (MIN.) = 1.82
Tc (MIN.) = 22.34
SUBAREA AREA (ACRES) = 27.51 SUBAREA RUNOFF (CFS) = 48.18
EFFECTIVE AREA (ACRES) = 97.37 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 97.4 PEAK FLOW RATE (CFS) = 170.51
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 1.48

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.48 FLOW VELOCITY(FEET/SEC.) = 8.91
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13834.00 = 4648.78 FEET.

FLOW PROCESS FROM NODE 13834.00 TO NODE 13835.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 471.65 DOWNSTREAM(FEET) = 347.06
CHANNEL LENGTH THRU SUBAREA(FEET) = 1647.45 CHANNEL SLOPE = 0.0756
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 2.02

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.058

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	94.21	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 245.10

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.82

AVERAGE FLOW DEPTH(FEET) = 1.99 TRAVEL TIME(MIN.) = 3.11

Tc(MIN.) = 25.45

SUBAREA AREA(ACRES) = 94.21 SUBAREA RUNOFF(CFS) = 149.07

EFFECTIVE AREA(ACRES) = 191.58 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 191.6 PEAK FLOW RATE(CFS) = 303.14

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 2.23

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.23 FLOW VELOCITY(FEET/SEC.) = 9.39

LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13835.00 = 6296.23 FEET.

FLOW PROCESS FROM NODE 13835.00 TO NODE 13836.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 347.06 DOWNSTREAM(FEET) = 269.29
CHANNEL LENGTH THRU SUBAREA(FEET) = 1696.71 CHANNEL SLOPE = 0.0458
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 3.28

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.918

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	233.25	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 473.04

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.90
AVERAGE FLOW DEPTH(FEET) = 3.23 TRAVEL TIME(MIN.) = 3.18
Tc(MIN.) = 28.63
SUBAREA AREA(ACRES) = 233.25 SUBAREA RUNOFF(CFS) = 339.58
EFFECTIVE AREA(ACRES) = 424.83 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 424.8 PEAK FLOW RATE(CFS) = 618.49
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 3.71

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 3.71 FLOW VELOCITY(FEET/SEC.) = 9.59

LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13836.00 = 7992.94 FEET.

FLOW PROCESS FROM NODE 13836.00 TO NODE 13837.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 269.29 DOWNSTREAM(FEET) = 191.87
CHANNEL LENGTH THRU SUBAREA(FEET) = 2529.21 CHANNEL SLOPE = 0.0306
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 4.42

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.766

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	134.70	0.30	0.880	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.880

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 709.58

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.58

AVERAGE FLOW DEPTH(FEET) = 4.40 TRAVEL TIME(MIN.) = 4.91

Tc(MIN.) = 33.54

SUBAREA AREA(ACRES) = 134.70 SUBAREA RUNOFF(CFS) = 182.13

EFFECTIVE AREA(ACRES) = 559.53 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97

TOTAL AREA(ACRES) = 559.5 PEAK FLOW RATE(CFS) = 742.79

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 4.50

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 4.50 FLOW VELOCITY(FEET/SEC.) = 8.69

LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13837.00 = 10522.15 FEET.

FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<

>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 191.87 DOWNSTREAM(FEET) = 133.00
FLOW LENGTH(FEET) = 1151.02 MANNING'S N = 0.013
DEPTH OF FLOW IN 69.0 INCH PIPE IS 51.9 INCHES

PIPE-FLOW VELOCITY (FEET/SEC.) = 35.42
 ESTIMATED PIPE DIAMETER (INCH) = 69.00 NUMBER OF PIPES = 1
 PIPE-FLOW (CFS) = 742.79
 PIPE TRAVEL TIME (MIN.) = 0.54 Tc (MIN.) = 34.08
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13840.00 = 11673.17 FEET.

 FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 34.08
 * 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.752
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 5.97 0.30 0.622 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.622
 SUBAREA AREA (ACRES) = 5.97 SUBAREA RUNOFF (CFS) = 8.41
 EFFECTIVE AREA (ACRES) = 565.50 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA (ACRES) = 565.5 PEAK FLOW RATE (CFS) = 744.23

 FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
 TIME OF CONCENTRATION (MIN.) = 34.08
 RAINFALL INTENSITY (INCH/HR) = 1.75
 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.97
 EFFECTIVE STREAM AREA (ACRES) = 565.50
 TOTAL STREAM AREA (ACRES) = 565.50
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 744.23

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27518.30	20.70	2.349	0.30 (0.24)	0.81	3836.7	10600.00
1	28236.09	22.30	2.248	0.30 (0.24)	0.81	4233.5	13810.00
1	29609.60	25.44	2.058	0.30 (0.24)	0.81	4990.6	10400.00
1	34000.14	34.81	1.734	0.30 (0.24)	0.81	8222.8	10500.00
1	35656.49	39.85	1.605	0.30 (0.24)	0.81	9930.3	203.00
1	41227.59	54.63	1.336	0.30 (0.25)	0.83	17549.7	50260.00
1	43440.93	63.14	1.253	0.30 (0.26)	0.86	22280.8	13600.00
1	46177.26	75.57	1.168	0.30 (0.26)	0.88	28913.3	13100.00
1	47727.47	81.73	1.126	0.30 (0.27)	0.89	31905.3	11801.00
1	50139.13	90.84	1.066	0.30 (0.27)	0.90	36949.9	11530.00
1	51473.45	96.46	1.041	0.30 (0.27)	0.91	40834.7	13510.00
1	52531.90	101.17	1.019	0.30 (0.27)	0.91	43988.2	13010.00
1	53604.85	105.96	0.997	0.30 (0.28)	0.92	47210.6	11330.00
1	54226.37	112.20	0.969	0.30 (0.28)	0.93	51641.6	11130.00

1	53614.00	119.85	0.934	0.30 (0.28)	0.93	55635.6	12330.00
1	52949.69	126.55	0.916	0.30 (0.28)	0.93	58978.7	12400.00
1	51917.78	135.34	0.893	0.30 (0.28)	0.94	62347.5	12201.00
1	50412.23	144.84	0.868	0.30 (0.28)	0.94	64801.7	12101.10
1	47879.70	157.21	0.836	0.30 (0.28)	0.94	66965.9	12010.00
1	46362.43	163.28	0.820	0.30 (0.28)	0.94	67279.6	10210.00
1	41982.05	189.97	0.766	0.30 (0.28)	0.94	68012.3	10100.00
2	744.23	34.08	1.752	0.30 (0.29)	0.97	565.5	13830.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28154.68	20.70	2.349	0.30 (0.25)	0.82	4180.2	10600.00
2	28888.05	22.30	2.248	0.30 (0.25)	0.82	4603.5	13810.00
3	30281.38	25.44	2.058	0.30 (0.25)	0.82	5412.8	10400.00
4	34404.02	34.08	1.752	0.30 (0.25)	0.82	8537.8	13830.00
5	34734.91	34.81	1.734	0.30 (0.25)	0.82	8788.3	10500.00
6	36325.66	39.85	1.605	0.30 (0.25)	0.82	10495.8	203.00
7	41759.77	54.63	1.336	0.30 (0.25)	0.84	18115.2	50260.00
8	43930.79	63.14	1.253	0.30 (0.26)	0.86	22846.3	13600.00
9	46624.10	75.57	1.168	0.30 (0.27)	0.88	29478.8	13100.00
10	48152.98	81.73	1.126	0.30 (0.27)	0.89	32470.8	11801.00
11	50534.08	90.84	1.066	0.30 (0.27)	0.90	37515.4	11530.00
12	51855.34	96.46	1.041	0.30 (0.27)	0.91	41400.2	13510.00
13	52902.83	101.17	1.019	0.30 (0.27)	0.92	44553.7	13010.00
14	53964.65	105.96	0.997	0.30 (0.28)	0.92	47776.1	11330.00
15	54571.66	112.20	0.969	0.30 (0.28)	0.93	52207.1	11130.00
16	53941.52	119.85	0.934	0.30 (0.28)	0.93	56201.1	12330.00
17	53268.19	126.55	0.916	0.30 (0.28)	0.93	59544.2	12400.00
18	52224.66	135.34	0.893	0.30 (0.28)	0.94	62913.0	12201.00
19	50706.54	144.84	0.868	0.30 (0.28)	0.94	65367.2	12101.10
20	48157.64	157.21	0.836	0.30 (0.28)	0.94	67531.4	12010.00
21	46632.32	163.28	0.820	0.30 (0.28)	0.94	67845.1	10210.00
22	42224.05	189.97	0.766	0.30 (0.28)	0.94	68577.8	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 54571.66 Tc (MIN.) = 112.20
 EFFECTIVE AREA (ACRES) = 52207.09 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA (ACRES) = 68577.8
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13840.00 = 132801.55 FEET.

 FLOW PROCESS FROM NODE 13840.00 TO NODE 13860.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 133.00 DOWNSTREAM (FEET) = 130.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 654.44 CHANNEL SLOPE = 0.0046
 GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT (FEET) = 17.79
 * 100 YEAR RAINFALL INTENSITY (INCH/HR) = 0.966
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 6.61 0.30 0.975 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.975
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 54573.67
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 17.92
 AVERAGE FLOW DEPTH(FEET) = 17.79 TRAVEL TIME(MIN.) = 0.61
 Tc(MIN.) = 112.81
 SUBAREA AREA(ACRES) = 6.61 SUBAREA RUNOFF(CFS) = 4.01
 EFFECTIVE AREA(ACRES) = 52213.70 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 68584.4 PEAK FLOW RATE(CFS) = 54571.66
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 17.79

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 17.79 FLOW VELOCITY(FEET/SEC.) = 17.92
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13860.00 = 133455.98 FEET.

 FLOW PROCESS FROM NODE 13840.00 TO NODE 13860.00 IS CODE = 1

 >>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
 TIME OF CONCENTRATION(MIN.) = 112.81
 RAINFALL INTENSITY(INCH/HR) = 0.97
 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.93
 EFFECTIVE STREAM AREA(ACRES) = 52213.70
 TOTAL STREAM AREA(ACRES) = 68584.41
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 54571.66

 FLOW PROCESS FROM NODE 13850.00 TO NODE 13851.00 IS CODE = 21

 >>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH(FEET) = 617.57
 ELEVATION DATA: UPSTREAM(FEET) = 646.95 DOWNSTREAM(FEET) = 490.10

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
 SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 12.137
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.371
 SUBAREA Tc AND LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)
 NATURAL FAIR COVER
 "CHAPARRAL,BROADLEAF" - 4.95 0.30 1.000 65 12.14
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA RUNOFF(CFS) = 13.68

TOTAL AREA(ACRES) = 4.95 PEAK FLOW RATE(CFS) = 13.68

 FLOW PROCESS FROM NODE 13851.00 TO NODE 13851.50 IS CODE = 56

 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 490.10 DOWNSTREAM(FEET) = 440.98
 CHANNEL LENGTH THRU SUBAREA(FEET) = 351.14 CHANNEL SLOPE = 0.1399
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 0.38
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.160
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 4.02 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 18.85
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.63
 AVERAGE FLOW DEPTH(FEET) = 0.38 TRAVEL TIME(MIN.) = 1.26
 Tc(MIN.) = 13.40

SUBAREA AREA(ACRES) = 4.02 SUBAREA RUNOFF(CFS) = 10.35
 EFFECTIVE AREA(ACRES) = 8.97 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 9.0 PEAK FLOW RATE(CFS) = 23.09
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 0.43

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 0.43 FLOW VELOCITY(FEET/SEC.) = 4.94
 LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13851.50 = 968.71 FEET.

 FLOW PROCESS FROM NODE 13851.50 TO NODE 13852.00 IS CODE = 56

 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 440.98 DOWNSTREAM(FEET) = 395.76
 CHANNEL LENGTH THRU SUBAREA(FEET) = 512.91 CHANNEL SLOPE = 0.0882
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 0.60
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.873
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 7.17 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 31.40
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.76
 AVERAGE FLOW DEPTH(FEET) = 0.59 TRAVEL TIME(MIN.) = 1.80
 Tc(MIN.) = 15.20

SUBAREA AREA (ACRES) = 7.17 SUBAREA RUNOFF (CFS) = 16.60
EFFECTIVE AREA (ACRES) = 16.14 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 16.1 PEAK FLOW RATE (CFS) = 37.38
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.65

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.65 FLOW VELOCITY (FEET/SEC.) = 5.06
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13852.00 = 1481.62 FEET.

FLOW PROCESS FROM NODE 13852.00 TO NODE 13853.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 395.76 DOWNSTREAM (FEET) = 354.94
CHANNEL LENGTH THRU SUBAREA (FEET) = 443.69 CHANNEL SLOPE = 0.0920
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.72
* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.738

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	6.76	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 44.80
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.49
AVERAGE FLOW DEPTH (FEET) = 0.71 TRAVEL TIME (MIN.) = 1.35
Tc (MIN.) = 16.55

SUBAREA AREA (ACRES) = 6.76 SUBAREA RUNOFF (CFS) = 14.84
EFFECTIVE AREA (ACRES) = 22.90 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 22.9 PEAK FLOW RATE (CFS) = 50.26
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.77

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.77 FLOW VELOCITY (FEET/SEC.) = 5.69
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13853.00 = 1925.31 FEET.

FLOW PROCESS FROM NODE 13853.00 TO NODE 13854.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 354.94 DOWNSTREAM (FEET) = 263.57
CHANNEL LENGTH THRU SUBAREA (FEET) = 962.09 CHANNEL SLOPE = 0.0950
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.92
* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.487

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	18.16	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 68.15
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.38
AVERAGE FLOW DEPTH (FEET) = 0.91 TRAVEL TIME (MIN.) = 2.51
Tc (MIN.) = 19.06

SUBAREA AREA (ACRES) = 18.16 SUBAREA RUNOFF (CFS) = 35.74
EFFECTIVE AREA (ACRES) = 41.06 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 41.1 PEAK FLOW RATE (CFS) = 80.82
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 1.00

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 1.00 FLOW VELOCITY (FEET/SEC.) = 6.72
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13854.00 = 2887.40 FEET.

FLOW PROCESS FROM NODE 13854.00 TO NODE 13855.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 263.57 DOWNSTREAM (FEET) = 188.74
CHANNEL LENGTH THRU SUBAREA (FEET) = 1228.77 CHANNEL SLOPE = 0.0609
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 1.41
* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.254

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	38.75	0.30	0.879	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.879
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 115.55
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.50
AVERAGE FLOW DEPTH (FEET) = 1.39 TRAVEL TIME (MIN.) = 3.15
Tc (MIN.) = 22.21

SUBAREA AREA (ACRES) = 38.75 SUBAREA RUNOFF (CFS) = 69.40
EFFECTIVE AREA (ACRES) = 79.81 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94
TOTAL AREA (ACRES) = 79.8 PEAK FLOW RATE (CFS) = 141.59
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 1.56

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 1.56 FLOW VELOCITY (FEET/SEC.) = 6.92
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13855.00 = 4116.17 FEET.

FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 31

```

-----
>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 188.74 DOWNSTREAM(FEET) = 130.00
FLOW LENGTH(FEET) = 2092.67 MANNING'S N = 0.013
DEPTH OF FLOW IN 42.0 INCH PIPE IS 30.7 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 18.77
ESTIMATED PIPE DIAMETER(INCH) = 42.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 141.59
PIPE TRAVEL TIME(MIN.) = 1.86 Tc(MIN.) = 24.07
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13860.00 = 6208.84 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 24.07
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.136
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 43.41 0.30 0.707 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.707
SUBAREA AREA(ACRES) = 43.41 SUBAREA RUNOFF(CFS) = 75.19
EFFECTIVE AREA(ACRES) = 123.22 AREA-AVERAGED Fm(INCH/HR) = 0.26
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.86
TOTAL AREA(ACRES) = 123.2 PEAK FLOW RATE(CFS) = 208.37

```

```

*****
FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 1
-----

```

```

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<
=====
TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 24.07
RAINFALL INTENSITY(INCH/HR) = 2.14
AREA-AVERAGED Fm(INCH/HR) = 0.26
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.86
EFFECTIVE STREAM AREA(ACRES) = 123.22
TOTAL STREAM AREA(ACRES) = 123.22
PEAK FLOW RATE(CFS) AT CONFLUENCE = 208.37

```

```

** CONFLUENCE DATA **

```

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28154.68	21.44	2.302	0.30(0.25)	0.82	4186.8	10600.00
1	28888.05	23.03	2.202	0.30(0.25)	0.82	4610.1	13810.00
1	30281.38	26.16	2.027	0.30(0.25)	0.82	5419.4	10400.00
1	34404.02	34.78	1.735	0.30(0.25)	0.82	8544.4	13830.00
1	34734.91	35.50	1.716	0.30(0.25)	0.82	8794.9	10500.00
1	36325.66	40.53	1.590	0.30(0.25)	0.82	10502.4	203.00
1	41759.77	55.28	1.328	0.30(0.25)	0.84	18121.8	50260.00

1	43930.79	63.79	1.248	0.30(0.26)	0.86	22852.9	13600.00
1	46624.10	76.21	1.164	0.30(0.27)	0.88	29485.4	13100.00
1	48152.98	82.36	1.122	0.30(0.27)	0.89	32477.4	11801.00
1	50534.08	91.46	1.063	0.30(0.27)	0.90	37522.0	11530.00
1	51855.34	97.08	1.038	0.30(0.27)	0.91	41406.8	13510.00
1	52902.83	101.79	1.016	0.30(0.27)	0.92	44560.3	13010.00
1	53964.65	106.57	0.994	0.30(0.28)	0.92	47782.7	11330.00
1	54571.66	112.81	0.966	0.30(0.28)	0.93	52213.7	11130.00
1	53941.52	120.46	0.932	0.30(0.28)	0.93	56207.7	12330.00
1	53268.19	127.17	0.914	0.30(0.28)	0.93	59550.9	12400.00
1	52224.66	135.95	0.892	0.30(0.28)	0.94	62919.6	12201.00
1	50706.54	145.46	0.867	0.30(0.28)	0.94	65373.8	12101.10
1	48157.64	157.84	0.835	0.30(0.28)	0.94	67538.0	12010.00
1	46632.32	163.92	0.819	0.30(0.28)	0.94	67851.7	10210.00
1	42224.05	190.63	0.765	0.30(0.28)	0.94	68584.4	10100.00
2	208.37	24.07	2.136	0.30(0.26)	0.86	123.2	13850.00

```

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

```

```

** PEAK FLOW RATE TABLE **

```

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28356.64	21.44	2.302	0.30(0.25)	0.82	4296.5	10600.00
2	29094.37	23.03	2.202	0.30(0.25)	0.82	4728.0	13810.00
3	29559.88	24.07	2.136	0.30(0.25)	0.82	5002.5	13850.00
4	30477.57	26.16	2.027	0.30(0.25)	0.82	5542.6	10400.00
5	34567.82	34.78	1.735	0.30(0.25)	0.82	8667.6	13830.00
6	34896.66	35.50	1.716	0.30(0.25)	0.82	8918.1	10500.00
7	36473.40	40.53	1.590	0.30(0.25)	0.82	10625.6	203.00
8	41878.50	55.28	1.328	0.30(0.25)	0.84	18245.0	50260.00
9	44040.66	63.79	1.248	0.30(0.26)	0.86	22976.1	13600.00
10	46724.60	76.21	1.164	0.30(0.27)	0.88	29608.7	13100.00
11	48248.84	82.36	1.122	0.30(0.27)	0.89	32600.6	11801.00
12	50623.44	91.46	1.063	0.30(0.27)	0.90	37645.2	11530.00
13	51941.86	97.08	1.038	0.30(0.27)	0.91	41530.0	13510.00
14	52986.96	101.79	1.016	0.30(0.27)	0.92	44683.5	13010.00
15	54046.36	106.57	0.994	0.30(0.28)	0.92	47905.9	11330.00
16	54650.21	112.81	0.966	0.30(0.28)	0.93	52336.9	11130.00
17	54016.29	120.46	0.932	0.30(0.28)	0.93	56330.9	12330.00
18	53341.03	127.17	0.914	0.30(0.28)	0.93	59674.1	12400.00
19	52294.96	135.95	0.892	0.30(0.28)	0.94	63042.8	12201.00
20	50774.10	145.46	0.867	0.30(0.28)	0.94	65497.0	12101.10
21	48221.63	157.84	0.835	0.30(0.28)	0.94	67661.2	12010.00
22	46694.57	163.92	0.819	0.30(0.28)	0.94	67974.9	10210.00
23	42280.31	190.63	0.765	0.30(0.28)	0.94	68707.6	10100.00

```

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
PEAK FLOW RATE(CFS) = 54650.21 Tc(MIN.) = 112.81
EFFECTIVE AREA(ACRES) = 52336.92 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 68707.6
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13860.00 = 133455.98 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13860.00 TO NODE 13880.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

```

>>>>TRAVELTIME THRU SUBAREA<<<<

```

=====
ELEVATION DATA: UPSTREAM(FEET) = 130.00 DOWNSTREAM(FEET) = 120.57
CHANNEL LENGTH THRU SUBAREA(FEET) = 610.77 CHANNEL SLOPE = 0.0154
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 13.00
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 0.964
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp        Ap      SCS
LAND USE            GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN
USER-DEFINED        -       4.89     0.30     1.000    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 54651.67
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 27.67
AVERAGE FLOW DEPTH(FEET) = 13.00 TRAVEL TIME(MIN.) = 0.37
Tc(MIN.) = 113.18
SUBAREA AREA(ACRES) = 4.89 SUBAREA RUNOFF(CFS) = 2.92
EFFECTIVE AREA(ACRES) = 52341.81 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 68712.5 PEAK FLOW RATE(CFS) = 54650.21
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 13.00

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 13.00 FLOW VELOCITY(FEET/SEC.) = 27.67
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13880.00 = 134066.75 FEET.

FLOW PROCESS FROM NODE 13860.00 TO NODE 13880.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

```

=====
TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION(MIN.) = 113.18
RAINFALL INTENSITY(INCH/HR) = 0.96
AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.93
EFFECTIVE STREAM AREA(ACRES) = 52341.81
TOTAL STREAM AREA(ACRES) = 68712.52
PEAK FLOW RATE(CFS) AT CONFLUENCE = 54650.21

```

FLOW PROCESS FROM NODE 13870.00 TO NODE 13871.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

```

=====
INITIAL SUBAREA FLOW-LENGTH(FEET) = 872.65
ELEVATION DATA: UPSTREAM(FEET) = 558.52 DOWNSTREAM(FEET) = 436.47

```

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 15.704

```

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.823
SUBAREA Tc AND LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp        Ap      SCS   Tc
LAND USE            GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN (MIN.)
NATURAL FAIR COVER
"GRASS"              -       7.32     0.30     1.000    65   15.70
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 16.62
TOTAL AREA(ACRES) = 7.32 PEAK FLOW RATE(CFS) = 16.62

```

FLOW PROCESS FROM NODE 13871.00 TO NODE 13872.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

```

=====
ELEVATION DATA: UPSTREAM(FEET) = 436.47 DOWNSTREAM(FEET) = 337.62
CHANNEL LENGTH THRU SUBAREA(FEET) = 827.95 CHANNEL SLOPE = 0.1194
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.54
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.555
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp        Ap      SCS
LAND USE            GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN
USER-DEFINED        -       13.01    0.30     1.000    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 29.85
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.16
AVERAGE FLOW DEPTH(FEET) = 0.52 TRAVEL TIME(MIN.) = 2.67
Tc(MIN.) = 18.38
SUBAREA AREA(ACRES) = 13.01 SUBAREA RUNOFF(CFS) = 26.41
EFFECTIVE AREA(ACRES) = 20.33 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 20.3 PEAK FLOW RATE(CFS) = 41.27
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.63

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.63 FLOW VELOCITY(FEET/SEC.) = 5.81
LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13872.00 = 1700.60 FEET.

FLOW PROCESS FROM NODE 13872.00 TO NODE 13873.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

```

=====
ELEVATION DATA: UPSTREAM(FEET) = 337.62 DOWNSTREAM(FEET) = 253.88
CHANNEL LENGTH THRU SUBAREA(FEET) = 1049.16 CHANNEL SLOPE = 0.0798
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.00
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.315
SUBAREA LOSS RATE DATA(AMC II):

```

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 32.99 0.30 0.923 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.923
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 71.56
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.11
 AVERAGE FLOW DEPTH (FEET) = 0.98 TRAVEL TIME (MIN.) = 2.86
 Tc (MIN.) = 21.24
 SUBAREA AREA (ACRES) = 32.99 SUBAREA RUNOFF (CFS) = 60.51
 EFFECTIVE AREA (ACRES) = 53.32 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
 TOTAL AREA (ACRES) = 53.3 PEAK FLOW RATE (CFS) = 97.38
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 1.17

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 1.17 FLOW VELOCITY (FEET/SEC.) = 6.74
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13873.00 = 2749.76 FEET.

 FLOW PROCESS FROM NODE 13873.00 TO NODE 13874.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 253.88 DOWNSTREAM (FEET) = 160.73
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1518.60 CHANNEL SLOPE = 0.0613
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT (FEET) = 1.16
 * 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.133
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	30.94	0.30	0.900	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.900
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 123.34
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.74
 AVERAGE FLOW DEPTH (FEET) = 1.15 TRAVEL TIME (MIN.) = 2.89
 Tc (MIN.) = 24.13
 SUBAREA AREA (ACRES) = 30.94 SUBAREA RUNOFF (CFS) = 51.87
 EFFECTIVE AREA (ACRES) = 84.26 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA (ACRES) = 84.3 PEAK FLOW RATE (CFS) = 140.50
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT (FEET) = 1.23

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 1.23 FLOW VELOCITY (FEET/SEC.) = 9.14
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13874.00 = 4268.36 FEET.

 FLOW PROCESS FROM NODE 13874.00 TO NODE 13875.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 160.73 DOWNSTREAM (FEET) = 158.14
 CHANNEL LENGTH THRU SUBAREA (FEET) = 582.74 CHANNEL SLOPE = 0.0044
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT (FEET) = 3.08
 * 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.010
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	73.67	0.30	0.930	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.930
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 197.90
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.03
 AVERAGE FLOW DEPTH (FEET) = 3.05 TRAVEL TIME (MIN.) = 2.41
 Tc (MIN.) = 26.54
 SUBAREA AREA (ACRES) = 73.67 SUBAREA RUNOFF (CFS) = 114.76
 EFFECTIVE AREA (ACRES) = 157.93 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA (ACRES) = 157.9 PEAK FLOW RATE (CFS) = 245.95
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT (FEET) = 3.41

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 3.41 FLOW VELOCITY (FEET/SEC.) = 4.28
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13875.00 = 4851.10 FEET.

 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 158.14 DOWNSTREAM (FEET) = 120.57
 FLOW LENGTH (FEET) = 1855.67 MANNING'S N = 0.013
 DEPTH OF FLOW IN 54.0 INCH PIPE IS 41.1 INCHES
 PIPE-FLOW VELOCITY (FEET/SEC.) = 18.95
 ESTIMATED PIPE DIAMETER (INCH) = 54.00 NUMBER OF PIPES = 1
 PIPE-FLOW (CFS) = 245.95
 PIPE TRAVEL TIME (MIN.) = 1.63 Tc (MIN.) = 28.17
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13880.00 = 6706.77 FEET.

 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 28.17
 * 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.938
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	34.90	0.30	0.743	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.743
 SUBAREA AREA(ACRES) = 34.90 SUBAREA RUNOFF(CFS) = 53.86
 EFFECTIVE AREA(ACRES) = 192.83 AREA-AVERAGED Fm(INCH/HR) = 0.27
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.90
 TOTAL AREA(ACRES) = 192.8 PEAK FLOW RATE(CFS) = 289.56

 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<
 =====

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
 TIME OF CONCENTRATION(MIN.) = 28.17
 RAINFALL INTENSITY(INCH/HR) = 1.94
 AREA-AVERAGED Fm(INCH/HR) = 0.27
 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.90
 EFFECTIVE STREAM AREA(ACRES) = 192.83
 TOTAL STREAM AREA(ACRES) = 192.83
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 289.56

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28356.64	21.89	2.274	0.30(0.25)	0.82	4301.4	10600.00
1	29094.37	23.47	2.174	0.30(0.25)	0.82	4732.9	13810.00
1	29559.88	24.51	2.109	0.30(0.25)	0.82	5007.4	13850.00
1	30477.57	26.60	2.007	0.30(0.25)	0.82	5547.5	10400.00
1	34567.82	35.20	1.724	0.30(0.25)	0.82	8672.5	13830.00
1	34896.66	35.92	1.705	0.30(0.25)	0.82	8923.0	10500.00
1	36473.40	40.94	1.581	0.30(0.25)	0.82	10630.5	203.00
1	41878.50	55.68	1.324	0.30(0.25)	0.84	18249.9	50260.00
1	44040.66	64.18	1.246	0.30(0.26)	0.86	22981.0	13600.00
1	46724.60	76.59	1.161	0.30(0.27)	0.88	29613.6	13100.00
1	48248.84	82.75	1.119	0.30(0.27)	0.89	32605.5	11801.00
1	50623.44	91.83	1.062	0.30(0.27)	0.90	37650.1	11530.00
1	51941.86	97.45	1.036	0.30(0.27)	0.91	41534.9	13510.00
1	52986.96	102.16	1.014	0.30(0.27)	0.92	44688.4	13010.00
1	54046.36	106.94	0.993	0.30(0.28)	0.92	47910.8	11330.00
1	54650.21	113.18	0.964	0.30(0.28)	0.93	52341.8	11130.00
1	54016.29	120.83	0.931	0.30(0.28)	0.93	56335.8	12330.00
1	53341.03	127.54	0.913	0.30(0.28)	0.93	59679.0	12400.00
1	52294.96	136.32	0.891	0.30(0.28)	0.94	63047.7	12201.00
1	50774.10	145.84	0.866	0.30(0.28)	0.94	65501.9	12101.10
1	48221.63	158.22	0.834	0.30(0.28)	0.94	67666.1	12010.00
1	46694.57	164.30	0.818	0.30(0.28)	0.94	67979.8	10210.00
1	42280.31	191.02	0.764	0.30(0.28)	0.94	68712.5	10100.00
2	289.56	28.17	1.938	0.30(0.27)	0.90	192.8	13870.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28626.93	21.89	2.274	0.30(0.25)	0.82	4451.2	10600.00

2	29369.81	23.47	2.174	0.30(0.25)	0.82	4893.5	13810.00
3	29837.63	24.51	2.109	0.30(0.25)	0.82	5175.2	13850.00
4	30762.35	26.60	2.007	0.30(0.25)	0.82	5729.5	10400.00
5	31516.20	28.17	1.938	0.30(0.25)	0.82	6312.6	13870.00
6	34820.29	35.20	1.724	0.30(0.25)	0.82	8865.3	13830.00
7	35145.91	35.92	1.705	0.30(0.25)	0.82	9115.9	10500.00
8	36701.06	40.94	1.581	0.30(0.25)	0.82	10823.4	203.00
9	42061.50	55.68	1.324	0.30(0.25)	0.84	18442.8	50260.00
10	44210.11	64.18	1.246	0.30(0.26)	0.86	23173.8	13600.00
11	46879.40	76.59	1.161	0.30(0.27)	0.88	29806.4	13100.00
12	48396.38	82.75	1.119	0.30(0.27)	0.89	32798.3	11801.00
13	50760.96	91.83	1.062	0.30(0.27)	0.90	37842.9	11530.00
14	52074.93	97.45	1.036	0.30(0.27)	0.91	41727.7	13510.00
15	53116.30	102.16	1.014	0.30(0.27)	0.91	44881.2	13010.00
16	54171.91	106.94	0.993	0.30(0.28)	0.92	48103.6	11330.00
17	54770.82	113.18	0.964	0.30(0.28)	0.93	52534.6	11130.00
18	54131.12	120.83	0.931	0.30(0.28)	0.93	56528.6	12330.00
19	53452.83	127.54	0.913	0.30(0.28)	0.93	59871.8	12400.00
20	52402.80	136.32	0.891	0.30(0.28)	0.94	63240.6	12201.00
21	50877.64	145.84	0.866	0.30(0.28)	0.94	65694.7	12101.10
22	48319.59	158.22	0.834	0.30(0.28)	0.94	67858.9	12010.00
23	46789.78	164.30	0.818	0.30(0.28)	0.94	68172.6	10210.00
24	42366.26	191.02	0.764	0.30(0.28)	0.94	68905.3	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 54770.82 Tc(MIN.) = 113.18
 EFFECTIVE AREA(ACRES) = 52534.64 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 68905.3
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13880.00 = 134066.75 FEET.

 FLOW PROCESS FROM NODE 13880.00 TO NODE 13910.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<
 =====

ELEVATION DATA: UPSTREAM(FEET) = 120.57 DOWNSTREAM(FEET) = 119.70
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1190.21 CHANNEL SLOPE = 0.0007
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 28.09
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 0.954
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	117.69	0.30	0.724	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.724
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 54809.86
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.19
 AVERAGE FLOW DEPTH(FEET) = 28.08 TRAVEL TIME(MIN.) = 2.16
 Tc(MIN.) = 115.34
 SUBAREA AREA(ACRES) = 117.69 SUBAREA RUNOFF(CFS) = 78.08
 EFFECTIVE AREA(ACRES) = 52652.33 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 69023.0 PEAK FLOW RATE(CFS) = 54770.82
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 28.07

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 28.07 FLOW VELOCITY (FEET/SEC.) = 9.19
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13910.00 = 135256.95 FEET.

FLOW PROCESS FROM NODE 13880.00 TO NODE 13910.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

=====

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION (MIN.) = 115.34
RAINFALL INTENSITY (INCH/HR) = 0.95
AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.93
EFFECTIVE STREAM AREA (ACRES) = 52652.33
TOTAL STREAM AREA (ACRES) = 69023.03
PEAK FLOW RATE (CFS) AT CONFLUENCE = 54770.82

FLOW PROCESS FROM NODE 13889.00 TO NODE 13890.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH (FEET) = 447.89
ELEVATION DATA: UPSTREAM (FEET) = 564.89 DOWNSTREAM (FEET) = 421.92

Tc = K * [(LENGTH** 3.00) / (ELEVATION CHANGE)] ** 0.20
SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 6.976
* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 4.951
SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
PUBLIC PARK	-	3.03	0.30	0.960	65	6.98

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.960
SUBAREA RUNOFF (CFS) = 12.71
TOTAL AREA (ACRES) = 3.03 PEAK FLOW RATE (CFS) = 12.71

FLOW PROCESS FROM NODE 13890.00 TO NODE 13891.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 421.92 DOWNSTREAM (FEET) = 392.64
CHANNEL LENGTH THRU SUBAREA (FEET) = 435.33 CHANNEL SLOPE = 0.0673
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.49
* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 4.410
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 8.12 0.30 0.986 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.986
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 27.80
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.43
AVERAGE FLOW DEPTH (FEET) = 0.47 TRAVEL TIME (MIN.) = 1.34
Tc (MIN.) = 8.31

SUBAREA AREA (ACRES) = 8.12 SUBAREA RUNOFF (CFS) = 30.07
EFFECTIVE AREA (ACRES) = 11.15 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
TOTAL AREA (ACRES) = 11.1 PEAK FLOW RATE (CFS) = 41.31
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.59

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.59 FLOW VELOCITY (FEET/SEC.) = 6.26
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13891.00 = 883.22 FEET.

FLOW PROCESS FROM NODE 13891.00 TO NODE 13892.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 392.64 DOWNSTREAM (FEET) = 324.46
CHANNEL LENGTH THRU SUBAREA (FEET) = 662.40 CHANNEL SLOPE = 0.1029
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.68
* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 3.868

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	12.50	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 61.43
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.24
AVERAGE FLOW DEPTH (FEET) = 0.66 TRAVEL TIME (MIN.) = 1.34
Tc (MIN.) = 9.65
SUBAREA AREA (ACRES) = 12.50 SUBAREA RUNOFF (CFS) = 40.14
EFFECTIVE AREA (ACRES) = 23.65 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 23.6 PEAK FLOW RATE (CFS) = 76.00
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.74

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.74 FLOW VELOCITY (FEET/SEC.) = 8.88
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13892.00 = 1545.62 FEET.

FLOW PROCESS FROM NODE 13892.00 TO NODE 13893.00 IS CODE = 56

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 324.46 DOWNSTREAM(FEET) = 240.82
CHANNEL LENGTH THRU SUBAREA(FEET) = 980.03 CHANNEL SLOPE = 0.0853
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.93
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.485
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 15.87 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 98.76
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.09
AVERAGE FLOW DEPTH(FEET) = 0.92 TRAVEL TIME(MIN.) = 1.80
Tc(MIN.) = 11.45
SUBAREA AREA(ACRES) = 15.87 SUBAREA RUNOFF(CFS) = 45.49
EFFECTIVE AREA(ACRES) = 39.52 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 39.5 PEAK FLOW RATE(CFS) = 113.35
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.99

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.99 FLOW VELOCITY(FEET/SEC.) = 9.50
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13893.00 = 2525.65 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13893.00 TO NODE 13894.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 240.82 DOWNSTREAM(FEET) = 163.04
CHANNEL LENGTH THRU SUBAREA(FEET) = 1144.35 CHANNEL SLOPE = 0.0680
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.26
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.157
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 28.41 0.30 0.985 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.985
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 149.96
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.68
AVERAGE FLOW DEPTH(FEET) = 1.24 TRAVEL TIME(MIN.) = 1.97
Tc(MIN.) = 13.42
SUBAREA AREA(ACRES) = 28.41 SUBAREA RUNOFF(CFS) = 73.16
EFFECTIVE AREA(ACRES) = 67.93 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 67.9 PEAK FLOW RATE(CFS) = 174.82
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

```

```

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.36

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.36 FLOW VELOCITY(FEET/SEC.) = 10.15
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13894.00 = 3670.00 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 31
-----

```

```

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 163.04 DOWNSTREAM(FEET) = 119.70
FLOW LENGTH(FEET) = 1899.01 MANNING'S N = 0.013
DEPTH OF FLOW IN 48.0 INCH PIPE IS 34.0 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 18.39
ESTIMATED PIPE DIAMETER(INCH) = 48.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 174.82
PIPE TRAVEL TIME(MIN.) = 1.72 Tc(MIN.) = 15.14
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13910.00 = 5569.01 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 15.14
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.879
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 11.69 0.30 0.634 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.634
SUBAREA AREA(ACRES) = 11.69 SUBAREA RUNOFF(CFS) = 28.29
EFFECTIVE AREA(ACRES) = 79.62 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94
TOTAL AREA(ACRES) = 79.6 PEAK FLOW RATE(CFS) = 186.13

```

```

*****
FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 1
-----

```

```

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<
=====
TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 15.14
RAINFALL INTENSITY(INCH/HR) = 2.88
AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.94
EFFECTIVE STREAM AREA(ACRES) = 79.62
TOTAL STREAM AREA(ACRES) = 79.62
PEAK FLOW RATE(CFS) AT CONFLUENCE = 186.13

```

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28626.93	24.45	2.112	0.30 (0.25)	0.82	4568.9	10600.00
1	29369.81	26.02	2.033	0.30 (0.25)	0.82	5011.2	13810.00
1	29837.63	27.05	1.987	0.30 (0.25)	0.82	5292.8	13850.00
1	30762.35	29.12	1.896	0.30 (0.25)	0.82	5847.2	10400.00
1	31516.20	30.68	1.840	0.30 (0.25)	0.82	6430.3	13870.00
1	34820.29	37.63	1.662	0.30 (0.25)	0.82	8983.0	13830.00
1	35145.91	38.35	1.643	0.30 (0.25)	0.82	9233.6	10500.00
1	36701.06	43.34	1.530	0.30 (0.25)	0.82	10941.1	203.00
1	42061.50	58.00	1.297	0.30 (0.25)	0.84	18560.4	50260.00
1	44210.11	66.46	1.230	0.30 (0.26)	0.86	23291.5	13600.00
1	46879.40	78.84	1.146	0.30 (0.26)	0.88	29924.1	13100.00
1	48396.38	84.98	1.104	0.30 (0.27)	0.89	32916.0	11801.00
1	50760.96	94.04	1.052	0.30 (0.27)	0.90	37960.6	11530.00
1	52074.93	99.64	1.026	0.30 (0.27)	0.91	41845.4	13510.00
1	53116.30	104.33	1.005	0.30 (0.27)	0.91	44998.9	13010.00
1	54171.91	109.10	0.983	0.30 (0.28)	0.92	48221.3	11330.00
1	54770.82	115.34	0.954	0.30 (0.28)	0.93	52652.3	11130.00
1	54131.12	122.99	0.925	0.30 (0.28)	0.93	56646.3	12330.00
1	53452.83	129.71	0.908	0.30 (0.28)	0.93	59989.5	12400.00
1	52402.80	138.51	0.885	0.30 (0.28)	0.94	63358.3	12201.00
1	50877.64	148.04	0.860	0.30 (0.28)	0.94	65812.4	12101.10
1	48319.59	160.45	0.828	0.30 (0.28)	0.94	67976.6	12010.00
1	46789.78	166.55	0.812	0.30 (0.28)	0.94	68290.3	10210.00
1	42366.26	193.33	0.762	0.30 (0.28)	0.94	69023.0	10100.00
2	186.13	15.14	2.879	0.30 (0.28)	0.94	79.6	13889.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25191.57	15.14	2.879	0.30 (0.25)	0.82	2908.5	13889.00
2	28758.14	24.45	2.112	0.30 (0.25)	0.82	4648.5	10600.00
3	29495.31	26.02	2.033	0.30 (0.25)	0.82	5090.8	13810.00
4	29959.87	27.05	1.987	0.30 (0.25)	0.82	5372.5	13850.00
5	30878.05	29.12	1.896	0.30 (0.25)	0.82	5926.8	10400.00
6	31627.86	30.68	1.840	0.30 (0.25)	0.82	6509.9	13870.00
7	34919.19	37.63	1.662	0.30 (0.25)	0.82	9062.6	13830.00
8	35243.49	38.35	1.643	0.30 (0.25)	0.82	9313.2	10500.00
9	36790.55	43.34	1.530	0.30 (0.25)	0.82	11020.7	203.00
10	42134.29	58.00	1.297	0.30 (0.25)	0.84	18640.1	50260.00
11	44278.09	66.46	1.230	0.30 (0.26)	0.86	23371.1	13600.00
12	46941.36	78.84	1.146	0.30 (0.26)	0.88	30003.7	13100.00
13	48455.34	84.98	1.104	0.30 (0.27)	0.89	32995.6	11801.00
14	50816.16	94.04	1.052	0.30 (0.27)	0.90	38040.2	11530.00
15	52128.29	99.64	1.026	0.30 (0.27)	0.91	41925.0	13510.00
16	53168.12	104.33	1.005	0.30 (0.27)	0.91	45078.5	13010.00
17	54222.18	109.10	0.983	0.30 (0.28)	0.92	48300.9	11330.00
18	54819.04	115.34	0.954	0.30 (0.28)	0.93	52732.0	11130.00
19	54177.26	122.99	0.925	0.30 (0.28)	0.93	56725.9	12330.00
20	53497.72	129.71	0.908	0.30 (0.28)	0.93	60069.1	12400.00
21	52446.05	138.51	0.885	0.30 (0.28)	0.94	63437.9	12201.00
22	50919.11	148.04	0.860	0.30 (0.28)	0.94	65892.0	12101.10
23	48358.75	160.45	0.828	0.30 (0.28)	0.94	68056.2	12010.00
24	46827.80	166.55	0.812	0.30 (0.28)	0.94	68369.9	10210.00

25 42400.69 193.33 0.762 0.30 (0.28) 0.94 69102.6 10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 54819.04 Tc(MIN.) = 115.34
EFFECTIVE AREA(ACRES) = 52731.95 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 69102.6
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13910.00 = 135256.95 FEET.

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 69102.6 TC(MIN.) = 115.34
EFFECTIVE AREA(ACRES) = 52731.95 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.926
PEAK FLOW RATE(CFS) = 54819.04

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25191.57	15.14	2.879	0.30 (0.25)	0.82	2908.5	13889.00
2	28758.14	24.45	2.112	0.30 (0.25)	0.82	4648.5	10600.00
3	29495.31	26.02	2.033	0.30 (0.25)	0.82	5090.8	13810.00
4	29959.87	27.05	1.987	0.30 (0.25)	0.82	5372.5	13850.00
5	30878.05	29.12	1.896	0.30 (0.25)	0.82	5926.8	10400.00
6	31627.86	30.68	1.840	0.30 (0.25)	0.82	6509.9	13870.00
7	34919.19	37.63	1.662	0.30 (0.25)	0.82	9062.6	13830.00
8	35243.49	38.35	1.643	0.30 (0.25)	0.82	9313.2	10500.00
9	36790.55	43.34	1.530	0.30 (0.25)	0.82	11020.7	203.00
10	42134.29	58.00	1.297	0.30 (0.25)	0.84	18640.1	50260.00
11	44278.09	66.46	1.230	0.30 (0.26)	0.86	23371.1	13600.00
12	46941.36	78.84	1.146	0.30 (0.26)	0.88	30003.7	13100.00
13	48455.34	84.98	1.104	0.30 (0.27)	0.89	32995.6	11801.00
14	50816.16	94.04	1.052	0.30 (0.27)	0.90	38040.2	11530.00
15	52128.29	99.64	1.026	0.30 (0.27)	0.91	41925.0	13510.00
16	53168.12	104.33	1.005	0.30 (0.27)	0.91	45078.5	13010.00
17	54222.18	109.10	0.983	0.30 (0.28)	0.92	48300.9	11330.00
18	54819.04	115.34	0.954	0.30 (0.28)	0.93	52732.0	11130.00
19	54177.26	122.99	0.925	0.30 (0.28)	0.93	56725.9	12330.00
20	53497.72	129.71	0.908	0.30 (0.28)	0.93	60069.1	12400.00
21	52446.05	138.51	0.885	0.30 (0.28)	0.94	63437.9	12201.00
22	50919.11	148.04	0.860	0.30 (0.28)	0.94	65892.0	12101.10
23	48358.75	160.45	0.828	0.30 (0.28)	0.94	68056.2	12010.00
24	46827.80	166.55	0.812	0.30 (0.28)	0.94	68369.9	10210.00
25	42400.69	193.33	0.762	0.30 (0.28)	0.94	69102.6	10100.00

END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2010 Advanced Engineering Software (aes)
Ver. 17.0 Release Date: 07/01/2010 License ID 1527

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 139 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 100-YR EV AUG 2023 ROKAMOTO *

FILE NAME: RU00EV39.DAT
TIME/DATE OF STUDY: 21:37 08/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 100.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.744
- 2) 10.00; 3.724
- 3) 15.00; 2.891
- 4) 20.00; 2.392
- 5) 25.00; 2.077
- 6) 30.00; 1.856
- 7) 40.00; 1.601
- 8) 50.00; 1.389
- 9) 60.00; 1.273
- 10) 90.00; 1.070
- 11) 120.00; 0.932
- 12) 180.00; 0.777
- 13) 360.00; 0.571
- 14) 1200.00; 0.248

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL: IN- / OUT-/PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13900.00 TO NODE 13901.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<
=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 600.65
ELEVATION DATA: UPSTREAM(FEET) = 442.40 DOWNSTREAM(FEET) = 385.16

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 10.859
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.581
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
AGRICULTURAL POOR COVER "FALLOW"	-	4.00	0.30	1.000	65	10.86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 11.81
TOTAL AREA(ACRES) = 4.00 PEAK FLOW RATE(CFS) = 11.81

FLOW PROCESS FROM NODE 13901.00 TO NODE 13902.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<
=====

ELEVATION DATA: UPSTREAM(FEET) = 385.16 DOWNSTREAM(FEET) = 288.21
CHANNEL LENGTH THRU SUBAREA(FEET) = 647.42 CHANNEL SLOPE = 0.1497
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.34
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.307
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.47	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 23.29
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.56
AVERAGE FLOW DEPTH(FEET) = 0.33 TRAVEL TIME(MIN.) = 1.64
Tc(MIN.) = 12.50
SUBAREA AREA(ACRES) = 8.47 SUBAREA RUNOFF(CFS) = 22.92
EFFECTIVE AREA(ACRES) = 12.47 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 12.5 PEAK FLOW RATE(CFS) = 33.75
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.41

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.41 FLOW VELOCITY(FEET/SEC.) = 7.51
LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13902.00 = 1248.07 FEET.

FLOW PROCESS FROM NODE 13902.00 TO NODE 13903.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 288.21 DOWNSTREAM(FEET) = 184.89
CHANNEL LENGTH THRU SUBAREA(FEET) = 669.27 CHANNEL SLOPE = 0.1544
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 0.61

* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 3.113

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	23.85	0.30	0.982	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.982

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 64.02

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 9.56

AVERAGE FLOW DEPTH (FEET) = 0.60 TRAVEL TIME (MIN.) = 1.17

Tc (MIN.) = 13.67

SUBAREA AREA (ACRES) = 23.85 SUBAREA RUNOFF (CFS) = 60.49

EFFECTIVE AREA (ACRES) = 36.32 AREA-AVERAGED Fm (INCH/HR) = 0.30

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA (ACRES) = 36.3 PEAK FLOW RATE (CFS) = 92.06

GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT (FEET) = 0.74

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 0.74 FLOW VELOCITY (FEET/SEC.) = 10.79

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13903.00 = 1917.34 FEET.

FLOW PROCESS FROM NODE 13903.00 TO NODE 13904.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 184.89 DOWNSTREAM(FEET) = 155.08

FLOW LENGTH (FEET) = 876.66 MANNING'S N = 0.013

ESTIMATED PIPE DIAMETER (INCH) INCREASED TO 36.000

DEPTH OF FLOW IN 36.0 INCH PIPE IS 24.1 INCHES

PIPE-FLOW VELOCITY (FEET/SEC.) = 18.29

ESTIMATED PIPE DIAMETER (INCH) = 36.00 NUMBER OF PIPES = 1

PIPE-FLOW (CFS) = 92.06

PIPE TRAVEL TIME (MIN.) = 0.80 Tc (MIN.) = 14.47

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13904.00 = 2794.00 FEET.

FLOW PROCESS FROM NODE 13903.00 TO NODE 13904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 14.47

* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.980

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	21.29	0.30	0.996	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.996

SUBAREA AREA (ACRES) = 21.29 SUBAREA RUNOFF (CFS) = 51.37

EFFECTIVE AREA (ACRES) = 57.61 AREA-AVERAGED Fm (INCH/HR) = 0.30

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA (ACRES) = 57.6 PEAK FLOW RATE (CFS) = 139.07

FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 155.08 DOWNSTREAM(FEET) = 118.00

FLOW LENGTH (FEET) = 1961.38 MANNING'S N = 0.013

DEPTH OF FLOW IN 45.0 INCH PIPE IS 32.8 INCHES

PIPE-FLOW VELOCITY (FEET/SEC.) = 16.12

ESTIMATED PIPE DIAMETER (INCH) = 45.00 NUMBER OF PIPES = 1

PIPE-FLOW (CFS) = 139.07

PIPE TRAVEL TIME (MIN.) = 2.03 Tc (MIN.) = 16.50

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13920.00 = 4755.38 FEET.

FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 16.50

* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.742

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	43.53	0.30	0.649	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.649

SUBAREA AREA (ACRES) = 43.53 SUBAREA RUNOFF (CFS) = 99.78

EFFECTIVE AREA (ACRES) = 101.14 AREA-AVERAGED Fm (INCH/HR) = 0.25

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84

TOTAL AREA (ACRES) = 101.1 PEAK FLOW RATE (CFS) = 226.52

FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<

FLOW PROCESS FROM NODE 13910.00 TO NODE 13910.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<

PEAK FLOWRATE TABLE FILE NAME: RU00EV38.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25191.57	15.14	0.30 (0.25)	0.82	2908.5	13889.00
2	31627.86	30.68	0.30 (0.25)	0.82	6509.9	13870.00
3	35243.49	38.35	0.30 (0.25)	0.82	9313.2	10500.00
4	36790.55	43.34	0.30 (0.25)	0.82	11020.7	203.00
5	42134.29	58.00	0.30 (0.25)	0.84	18640.1	50260.00
6	44278.09	66.46	0.30 (0.26)	0.86	23371.1	13600.00
7	46941.36	78.84	0.30 (0.26)	0.88	30003.7	13100.00
8	48455.34	84.98	0.30 (0.27)	0.89	32995.6	11801.00
9	50816.16	94.04	0.30 (0.27)	0.90	38040.2	11530.00
10	52128.29	99.64	0.30 (0.27)	0.91	41925.0	13510.00
11	53168.12	104.33	0.30 (0.27)	0.91	45078.5	13010.00
12	54222.18	109.10	0.30 (0.28)	0.92	48300.9	11330.00
13	54819.04	115.34	0.30 (0.28)	0.93	52732.0	11130.00
14	54177.26	122.99	0.30 (0.28)	0.93	56725.9	12330.00
15	53497.72	129.71	0.30 (0.28)	0.93	60069.1	12400.00
16	52446.05	138.51	0.30 (0.28)	0.94	63437.9	12201.00
17	50919.11	148.04	0.30 (0.28)	0.94	65892.0	12101.10
18	48358.75	160.45	0.30 (0.28)	0.94	68056.2	12010.00
19	46827.80	166.55	0.30 (0.28)	0.94	68369.9	10210.00
20	42400.69	193.33	0.30 (0.28)	0.94	69102.6	10100.00
TOTAL AREA (ACRES) =						69102.6

 FLOW PROCESS FROM NODE 13910.00 TO NODE 13910.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25191.57	15.14	0.30 (0.25)	0.82	2908.5	13889.00
2	31627.86	30.68	0.30 (0.25)	0.82	6509.9	13870.00
3	35243.49	38.35	0.30 (0.25)	0.82	9313.2	10500.00
4	36790.55	43.34	0.30 (0.25)	0.82	11020.7	203.00
5	42134.29	58.00	0.30 (0.25)	0.84	18640.1	50260.00
6	44278.09	66.46	0.30 (0.26)	0.86	23371.1	13600.00
7	46941.36	78.84	0.30 (0.26)	0.88	30003.7	13100.00
8	48455.34	84.98	0.30 (0.27)	0.89	32995.6	11801.00
9	50816.16	94.04	0.30 (0.27)	0.90	38040.2	11530.00
10	52128.29	99.64	0.30 (0.27)	0.91	41925.0	13510.00
11	53168.12	104.33	0.30 (0.27)	0.91	45078.5	13010.00
12	54222.18	109.10	0.30 (0.28)	0.92	48300.9	11330.00
13	54819.04	115.34	0.30 (0.28)	0.93	52732.0	11130.00
14	54177.26	122.99	0.30 (0.28)	0.93	56725.9	12330.00
15	53497.72	129.71	0.30 (0.28)	0.93	60069.1	12400.00
16	52446.05	138.51	0.30 (0.28)	0.94	63437.9	12201.00
17	50919.11	148.04	0.30 (0.28)	0.94	65892.0	12101.10
18	48358.75	160.45	0.30 (0.28)	0.94	68056.2	12010.00
19	46827.80	166.55	0.30 (0.28)	0.94	68369.9	10210.00
20	42400.69	193.33	0.30 (0.28)	0.94	69102.6	10100.00
TOTAL AREA (ACRES) =						69102.6

 FLOW PROCESS FROM NODE 13910.00 TO NODE 13920.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

```

=====
ELEVATION DATA: UPSTREAM(FEET) = 119.70 DOWNSTREAM(FEET) = 118.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1376.26 CHANNEL SLOPE = 0.0012
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 24.74
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 0.944
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 96.09 0.30 0.535 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.535
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 54852.92
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.14
AVERAGE FLOW DEPTH(FEET) = 24.74 TRAVEL TIME(MIN.) = 2.06
Tc(MIN.) = 117.39
SUBAREA AREA(ACRES) = 96.09 SUBAREA RUNOFF(CFS) = 67.76
EFFECTIVE AREA(ACRES) = 52828.04 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 69198.7 PEAK FLOW RATE(CFS) = 54819.04
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 24.73
=====
    
```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 24.73 FLOW VELOCITY(FEET/SEC.) = 11.14
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136633.22 FEET.

 FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25191.57	17.69	2.623	0.30 (0.24)	0.82	3004.6	13889.00
2	31627.86	33.07	1.778	0.30 (0.25)	0.82	6606.0	13870.00
3	35243.49	40.67	1.587	0.30 (0.25)	0.82	9409.3	10500.00
4	36790.55	45.64	1.481	0.30 (0.25)	0.82	11116.8	203.00
5	42134.29	60.21	1.272	0.30 (0.25)	0.84	18736.2	50260.00
6	44278.09	68.64	1.215	0.30 (0.26)	0.86	23467.2	13600.00
7	46941.36	80.99	1.131	0.30 (0.26)	0.88	30099.8	13100.00
8	48455.34	87.10	1.090	0.30 (0.27)	0.89	33091.7	11801.00
9	50816.16	96.14	1.042	0.30 (0.27)	0.90	38136.3	11530.00
10	52128.29	101.72	1.016	0.30 (0.27)	0.91	42021.1	13510.00
11	53168.12	106.41	0.995	0.30 (0.27)	0.91	45174.6	13010.00
12	54222.18	111.17	0.973	0.30 (0.28)	0.92	48397.0	11330.00
13	54819.04	117.39	0.944	0.30 (0.28)	0.93	52828.0	11130.00
14	54177.26	125.06	0.919	0.30 (0.28)	0.93	56822.0	12330.00
15	53497.72	131.78	0.902	0.30 (0.28)	0.93	60165.2	12400.00
16	52446.05	140.59	0.879	0.30 (0.28)	0.94	63534.0	12201.00

17 50919.11 150.14 0.854 0.30(0.28) 0.94 65988.1 12101.10
 18 48358.75 162.58 0.822 0.30(0.28) 0.94 68152.3 12010.00
 19 46827.80 168.70 0.806 0.30(0.28) 0.94 68466.0 10210.00
 20 42400.69 195.54 0.759 0.30(0.28) 0.94 69198.7 10100.00
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136633.22 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	226.52	16.50	2.742	0.30(0.25)	0.84	101.1	13900.00

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13920.00 = 4755.38 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24896.29	16.50	2.742	0.30(0.24)	0.82	2903.5	13900.00
2	25407.28	17.69	2.623	0.30(0.24)	0.82	3105.8	13889.00
3	31766.65	33.07	1.778	0.30(0.25)	0.82	6707.1	13870.00
4	35364.89	40.67	1.587	0.30(0.25)	0.82	9510.4	10500.00
5	36902.36	45.64	1.481	0.30(0.25)	0.82	11217.9	203.00
6	42227.00	60.21	1.272	0.30(0.25)	0.84	18837.3	50260.00
7	44365.61	68.64	1.215	0.30(0.26)	0.86	23568.4	13600.00
8	47021.27	80.99	1.131	0.30(0.26)	0.88	30200.9	13100.00
9	48531.48	87.10	1.090	0.30(0.27)	0.89	33192.9	11801.00
10	50887.95	96.14	1.042	0.30(0.27)	0.90	38237.5	11530.00
11	52197.74	101.72	1.016	0.30(0.27)	0.91	42122.3	13510.00
12	53235.61	106.41	0.995	0.30(0.27)	0.91	45275.8	13010.00
13	54287.67	111.17	0.973	0.30(0.28)	0.92	48498.2	11330.00
14	54881.93	117.39	0.944	0.30(0.28)	0.93	52929.2	11130.00
15	54237.87	125.06	0.919	0.30(0.28)	0.93	56923.1	12330.00
16	53556.75	131.78	0.902	0.30(0.28)	0.93	60266.3	12400.00
17	52503.01	140.59	0.879	0.30(0.28)	0.94	63635.1	12201.00
18	50973.82	150.14	0.854	0.30(0.28)	0.94	66089.2	12101.10
19	48410.53	162.58	0.822	0.30(0.28)	0.94	68253.5	12010.00
20	46878.15	168.70	0.806	0.30(0.28)	0.94	68567.2	10210.00
21	42446.76	195.54	0.759	0.30(0.28)	0.94	69299.9	10100.00

TOTAL AREA (ACRES) = 69299.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 54881.93 Tc(MIN.) = 117.394
 EFFECTIVE AREA(ACRES) = 52929.18 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA(ACRES) = 69299.9
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136633.22 FEET.

 FLOW PROCESS FROM NODE 13920.00 TO NODE 13921.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 118.00 DOWNSTREAM(FEET) = 115.28
 CHANNEL LENGTH THRU SUBAREA(FEET) = 335.44 CHANNEL SLOPE = 0.0081
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 15.42
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 0.943
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	134.30	0.30	0.658	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.658
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 54926.98
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 22.03
 AVERAGE FLOW DEPTH(FEET) = 15.42 TRAVEL TIME(MIN.) = 0.25
 Tc(MIN.) = 117.65
 SUBAREA AREA(ACRES) = 134.30 SUBAREA RUNOFF(CFS) = 90.10
 EFFECTIVE AREA(ACRES) = 53063.48 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA(ACRES) = 69434.2 PEAK FLOW RATE(CFS) = 54881.93
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 15.41

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 15.41 FLOW VELOCITY(FEET/SEC.) = 22.02
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13921.00 = 136968.66 FEET.

 FLOW PROCESS FROM NODE 13921.00 TO NODE 14010.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 115.28 DOWNSTREAM(FEET) = 100.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1396.08 CHANNEL SLOPE = 0.0109
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 14.26
 * 100 YEAR RAINFALL INTENSITY(INCH/HR) = 0.938
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	96.27	0.30	0.723	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.723
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 54913.20
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 24.52
 AVERAGE FLOW DEPTH(FEET) = 14.26 TRAVEL TIME(MIN.) = 0.95
 Tc(MIN.) = 118.60
 SUBAREA AREA(ACRES) = 96.27 SUBAREA RUNOFF(CFS) = 62.52
 EFFECTIVE AREA(ACRES) = 53159.75 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA(ACRES) = 69530.5 PEAK FLOW RATE(CFS) = 54881.93
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 14.26

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 14.26 FLOW VELOCITY(FEET/SEC.) = 24.52
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 14010.00 = 138364.73 FEET.

=====

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 69530.5 TC (MIN.) = 118.60
 EFFECTIVE AREA (ACRES) = 53159.75 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.924
 PEAK FLOW RATE (CFS) = 54881.93

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24896.29	18.01	2.590	0.30 (0.24)	0.81	3134.1	13900.00
2	25407.28	19.19	2.472	0.30 (0.24)	0.81	3336.3	13889.00
3	31766.65	34.48	1.742	0.30 (0.24)	0.81	6937.7	13870.00
4	35364.89	42.04	1.558	0.30 (0.24)	0.82	9741.0	10500.00
5	36902.36	46.99	1.453	0.30 (0.24)	0.81	11448.5	203.00
6	42227.00	61.50	1.263	0.30 (0.25)	0.83	19067.9	50260.00
7	44365.61	69.92	1.206	0.30 (0.26)	0.86	23798.9	13600.00
8	47021.27	82.24	1.122	0.30 (0.26)	0.88	30431.5	13100.00
9	48531.48	88.35	1.081	0.30 (0.27)	0.89	33423.4	11801.00
10	50887.95	97.37	1.036	0.30 (0.27)	0.90	38468.0	11530.00
11	52197.74	102.94	1.010	0.30 (0.27)	0.91	42352.8	13510.00
12	53235.61	107.62	0.989	0.30 (0.27)	0.91	45506.3	13010.00
13	54287.67	112.37	0.967	0.30 (0.28)	0.92	48728.7	11330.00
14	54881.93	118.60	0.938	0.30 (0.28)	0.92	53159.8	11130.00
15	54237.87	126.27	0.916	0.30 (0.28)	0.93	57153.7	12330.00
16	53556.75	132.99	0.898	0.30 (0.28)	0.93	60496.9	12400.00
17	52503.01	141.81	0.876	0.30 (0.28)	0.94	63865.7	12201.00
18	50973.82	151.37	0.851	0.30 (0.28)	0.94	66319.8	12101.10
19	48410.53	163.83	0.819	0.30 (0.28)	0.94	68484.0	12010.00
20	46878.15	169.96	0.803	0.30 (0.28)	0.94	68797.7	10210.00
21	42446.76	196.84	0.758	0.30 (0.28)	0.94	69530.5	10100.00

=====
 END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International
5 Hutton Centre Drive, Suite 500
Santa Ana, CA 92707

***** DESCRIPTION OF STUDY *****
* RANCHO MISSION VIEJO - PA3 & PA4 ROMP - NODE 119 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 2-YR RM EV APRIL 2019 FKAZI *

FILE NAME: RU02EV19.DAT
TIME/DATE OF STUDY: 12:02 04/03/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 2.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 1.878
- 2) 10.00; 1.253
- 3) 15.00; 0.953
- 4) 20.00; 0.778
- 5) 25.00; 0.670
- 6) 30.00; 0.594
- 7) 40.00; 0.512
- 8) 50.00; 0.455
- 9) 60.00; 0.400
- 10) 90.00; 0.346
- 11) 120.00; 0.290
- 12) 180.00; 0.236
- 13) 360.00; 0.180
- 14) 1200.00; 0.084

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:

- 1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 11900.00 TO NODE 11901.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 295.79
ELEVATION DATA: UPSTREAM(FEET) = 2369.48 DOWNSTREAM(FEET) = 2332.92

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 7.203
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 1.603
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
RESIDENTIAL ".4 DWELLING/ACRE"	-	1.62	0.60	0.999	0	7.20

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999
SUBAREA RUNOFF(CFS) = 1.46
TOTAL AREA(ACRES) = 1.62 PEAK FLOW RATE(CFS) = 1.46

FLOW PROCESS FROM NODE 11901.00 TO NODE 11902.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2332.92 DOWNSTREAM(FEET) = 2297.70
CHANNEL LENGTH THRU SUBAREA(FEET) = 664.26 CHANNEL SLOPE = 0.0530
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 1.177
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.35	0.60	0.906	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.906
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3.90
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 2.72
AVERAGE FLOW DEPTH(FEET) = 0.69 TRAVEL TIME(MIN.) = 4.07
Tc(MIN.) = 11.27
SUBAREA AREA(ACRES) = 8.35 SUBAREA RUNOFF(CFS) = 4.76
EFFECTIVE AREA(ACRES) = 9.97 AREA-AVERAGED Fm(INCH/HR) = 0.55
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 10.0 PEAK FLOW RATE(CFS) = 5.60

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.79 FLOW VELOCITY(FEET/SEC.) = 2.99
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11902.00 = 960.05 FEET.

FLOW PROCESS FROM NODE 11902.00 TO NODE 11902.50 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2297.70 DOWNSTREAM(FEET) = 2263.40
CHANNEL LENGTH THRU SUBAREA(FEET) = 928.77 CHANNEL SLOPE = 0.0369
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.909
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 34.48 0.60 0.904 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.904
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 11.47
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.11
AVERAGE FLOW DEPTH(FEET) = 1.11 TRAVEL TIME(MIN.) = 4.98
Tc(MIN.) = 16.25
SUBAREA AREA(ACRES) = 34.48 SUBAREA RUNOFF(CFS) = 11.39
EFFECTIVE AREA(ACRES) = 44.45 AREA-AVERAGED Fm(INCH/HR) = 0.54
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.91
TOTAL AREA(ACRES) = 44.5 PEAK FLOW RATE(CFS) = 14.59

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.22 FLOW VELOCITY(FEET/SEC.) = 3.29
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11902.50 = 1888.82 FEET.

FLOW PROCESS FROM NODE 11902.50 TO NODE 11903.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2263.40 DOWNSTREAM(FEET) = 2252.14
CHANNEL LENGTH THRU SUBAREA(FEET) = 895.50 CHANNEL SLOPE = 0.0126
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.716
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 23.65 0.60 0.958 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.958
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 16.14
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 2.26
AVERAGE FLOW DEPTH(FEET) = 1.54 TRAVEL TIME(MIN.) = 6.61
Tc(MIN.) = 22.86
SUBAREA AREA(ACRES) = 23.65 SUBAREA RUNOFF(CFS) = 3.01
EFFECTIVE AREA(ACRES) = 68.10 AREA-AVERAGED Fm(INCH/HR) = 0.56
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 68.1 PEAK FLOW RATE(CFS) = 14.59
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.48 FLOW VELOCITY(FEET/SEC.) = 2.21

LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11903.00 = 2784.32 FEET.

FLOW PROCESS FROM NODE 11903.00 TO NODE 11904.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<
ELEVATION DATA: UPSTREAM(FEET) = 2252.14 DOWNSTREAM(FEET) = 2186.04
CHANNEL LENGTH THRU SUBAREA(FEET) = 1924.35 CHANNEL SLOPE = 0.0343
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.571
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 68.53 0.60 0.961 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.961
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 15.28
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.24
AVERAGE FLOW DEPTH(FEET) = 1.25 TRAVEL TIME(MIN.) = 9.90
Tc(MIN.) = 32.77
SUBAREA AREA(ACRES) = 68.53 SUBAREA RUNOFF(CFS) = 1.37
EFFECTIVE AREA(ACRES) = 136.63 AREA-AVERAGED Fm(INCH/HR) = 0.57
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.94
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 136.6 PEAK FLOW RATE(CFS) = 14.59
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.23 FLOW VELOCITY(FEET/SEC.) = 3.21
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11904.00 = 4708.67 FEET.

FLOW PROCESS FROM NODE 11904.00 TO NODE 11905.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2186.04 DOWNSTREAM(FEET) = 1957.34
CHANNEL LENGTH THRU SUBAREA(FEET) = 1926.87 CHANNEL SLOPE = 0.1187
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.520
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 63.15 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 14.59
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.13

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.13

AVERAGE FLOW DEPTH (FEET) = 0.97 TRAVEL TIME (MIN.) = 6.26
Tc (MIN.) = 39.03
SUBAREA AREA (ACRES) = 63.15 SUBAREA RUNOFF (CFS) = 0.00
EFFECTIVE AREA (ACRES) = 199.78 AREA-AVERAGED Fm (INCH/HR) = 0.58
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.96
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA (ACRES) = 199.8 PEAK FLOW RATE (CFS) = 14.59
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.97 FLOW VELOCITY (FEET/SEC.) = 5.13
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11905.00 = 6635.54 FEET.

FLOW PROCESS FROM NODE 11905.00 TO NODE 11906.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 1957.34 DOWNSTREAM (FEET) = 1244.16
CHANNEL LENGTH THRU SUBAREA (FEET) = 2498.96 CHANNEL SLOPE = 0.2854
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.484

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	84.87	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 14.59
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.08
AVERAGE FLOW DEPTH (FEET) = 0.83 TRAVEL TIME (MIN.) = 5.88
Tc (MIN.) = 44.91

SUBAREA AREA (ACRES) = 84.87 SUBAREA RUNOFF (CFS) = 0.00
EFFECTIVE AREA (ACRES) = 284.65 AREA-AVERAGED Fm (INCH/HR) = 0.58
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.97
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA (ACRES) = 284.6 PEAK FLOW RATE (CFS) = 14.59
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.83 FLOW VELOCITY (FEET/SEC.) = 7.08
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11906.00 = 9134.50 FEET.

FLOW PROCESS FROM NODE 11906.00 TO NODE 11920.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 1244.16 DOWNSTREAM (FEET) = 873.95
CHANNEL LENGTH THRU SUBAREA (FEET) = 3370.75 CHANNEL SLOPE = 0.1098
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.421
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	199.43	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 14.59
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.97
AVERAGE FLOW DEPTH (FEET) = 0.99 TRAVEL TIME (MIN.) = 11.30
Tc (MIN.) = 56.21

SUBAREA AREA (ACRES) = 199.43 SUBAREA RUNOFF (CFS) = 0.00
EFFECTIVE AREA (ACRES) = 484.08 AREA-AVERAGED Fm (INCH/HR) = 0.59
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.98
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA (ACRES) = 484.1 PEAK FLOW RATE (CFS) = 14.59
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.99 FLOW VELOCITY (FEET/SEC.) = 4.97
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11920.00 = 12505.25 FEET.

FLOW PROCESS FROM NODE 11906.00 TO NODE 11920.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

=====

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION (MIN.) = 56.21
RAINFALL INTENSITY (INCH/HR) = 0.42
AREA-AVERAGED Fm (INCH/HR) = 0.59
AREA-AVERAGED Fp (INCH/HR) = 0.60
AREA-AVERAGED Ap = 0.98
EFFECTIVE STREAM AREA (ACRES) = 484.08
TOTAL STREAM AREA (ACRES) = 484.08
PEAK FLOW RATE (CFS) AT CONFLUENCE = 14.59

FLOW PROCESS FROM NODE 11910.00 TO NODE 11911.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH (FEET) = 517.62
ELEVATION DATA: UPSTREAM (FEET) = 2531.88 DOWNSTREAM (FEET) = 2441.33

Tc = K * [(LENGTH ** 3.00) / (ELEVATION CHANGE)] ** 0.20
SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 12.185
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 1.122
SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER						

"CHAPARRAL,BROADLEAF" - 3.46 0.60 1.000 0 12.19
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 1.63
TOTAL AREA(ACRES) = 3.46 PEAK FLOW RATE(CFS) = 1.63

FLOW PROCESS FROM NODE 11911.00 TO NODE 11912.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2441.33 DOWNSTREAM(FEET) = 2382.20
CHANNEL LENGTH THRU SUBAREA(FEET) = 397.30 CHANNEL SLOPE = 0.1488
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 1.012
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 5.79 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2.71
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.63
AVERAGE FLOW DEPTH(FEET) = 0.50 TRAVEL TIME(MIN.) = 1.82
Tc(MIN.) = 14.01
SUBAREA AREA(ACRES) = 5.79 SUBAREA RUNOFF(CFS) = 2.15
EFFECTIVE AREA(ACRES) = 9.25 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 9.2 PEAK FLOW RATE(CFS) = 3.43

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.54 FLOW VELOCITY(FEET/SEC.) = 3.86
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11912.00 = 914.92 FEET.

FLOW PROCESS FROM NODE 11912.00 TO NODE 11913.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2382.20 DOWNSTREAM(FEET) = 2263.77
CHANNEL LENGTH THRU SUBAREA(FEET) = 1891.47 CHANNEL SLOPE = 0.0626
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.702
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 54.30 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 6.71
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.32
AVERAGE FLOW DEPTH(FEET) = 0.82 TRAVEL TIME(MIN.) = 9.50
Tc(MIN.) = 23.51
SUBAREA AREA(ACRES) = 54.30 SUBAREA RUNOFF(CFS) = 5.00

EFFECTIVE AREA(ACRES) = 63.55 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 63.5 PEAK FLOW RATE(CFS) = 5.85

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.78 FLOW VELOCITY(FEET/SEC.) = 3.20
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11913.00 = 2806.39 FEET.

FLOW PROCESS FROM NODE 11913.00 TO NODE 11914.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2263.77 DOWNSTREAM(FEET) = 1845.23
CHANNEL LENGTH THRU SUBAREA(FEET) = 1957.31 CHANNEL SLOPE = 0.2138
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.595
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 65.14 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 6.01
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.07
AVERAGE FLOW DEPTH(FEET) = 0.63 TRAVEL TIME(MIN.) = 6.43
Tc(MIN.) = 29.94
SUBAREA AREA(ACRES) = 65.14 SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 128.69 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 128.7 PEAK FLOW RATE(CFS) = 5.85
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.62 FLOW VELOCITY(FEET/SEC.) = 5.06
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11914.00 = 4763.70 FEET.

FLOW PROCESS FROM NODE 11914.00 TO NODE 11915.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1845.23 DOWNSTREAM(FEET) = 1557.21
CHANNEL LENGTH THRU SUBAREA(FEET) = 1686.78 CHANNEL SLOPE = 0.1708
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.545
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 78.52 0.60 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5.85
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.68
AVERAGE FLOW DEPTH(FEET) = 0.65 TRAVEL TIME(MIN.) = 6.01
Tc(MIN.) = 35.95
SUBAREA AREA(ACRES) = 78.52 SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 207.21 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 207.2 PEAK FLOW RATE(CFS) = 5.85
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.65 FLOW VELOCITY(FEET/SEC.) = 4.68
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11915.00 = 6450.48 FEET.

FLOW PROCESS FROM NODE 11915.00 TO NODE 11916.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<
=====

ELEVATION DATA: UPSTREAM(FEET) = 1557.21 DOWNSTREAM(FEET) = 1403.38
CHANNEL LENGTH THRU SUBAREA(FEET) = 1909.39 CHANNEL SLOPE = 0.0806
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.484
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 70.48 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5.85
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.52
AVERAGE FLOW DEPTH(FEET) = 0.74 TRAVEL TIME(MIN.) = 9.05
Tc(MIN.) = 44.99
SUBAREA AREA(ACRES) = 70.48 SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 277.69 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 277.7 PEAK FLOW RATE(CFS) = 5.85
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.74 FLOW VELOCITY(FEET/SEC.) = 3.52
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11916.00 = 8359.87 FEET.

FLOW PROCESS FROM NODE 11916.00 TO NODE 11917.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<
=====

ELEVATION DATA: UPSTREAM(FEET) = 1403.38 DOWNSTREAM(FEET) = 1079.99
CHANNEL LENGTH THRU SUBAREA(FEET) = 1945.82 CHANNEL SLOPE = 0.1662
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.444
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 232.20 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5.85
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.60
AVERAGE FLOW DEPTH(FEET) = 0.65 TRAVEL TIME(MIN.) = 7.05
Tc(MIN.) = 52.04
SUBAREA AREA(ACRES) = 232.20 SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 509.89 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 509.9 PEAK FLOW RATE(CFS) = 5.85
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.65 FLOW VELOCITY(FEET/SEC.) = 4.60
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11917.00 = 10305.69 FEET.

FLOW PROCESS FROM NODE 11917.00 TO NODE 11920.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<
=====

ELEVATION DATA: UPSTREAM(FEET) = 1079.99 DOWNSTREAM(FEET) = 873.95
CHANNEL LENGTH THRU SUBAREA(FEET) = 2563.91 CHANNEL SLOPE = 0.0804
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.392
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 110.82 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5.85
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.52
AVERAGE FLOW DEPTH(FEET) = 0.74 TRAVEL TIME(MIN.) = 12.15
Tc(MIN.) = 64.19
SUBAREA AREA(ACRES) = 110.82 SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 620.71 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA (ACRES) = 620.7 PEAK FLOW RATE (CFS) = 5.85
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 0.74 FLOW VELOCITY (FEET/SEC.) = 3.52
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11920.00 = 12869.60 FEET.

FLOW PROCESS FROM NODE 11917.00 TO NODE 11920.00 IS CODE = 1

 >>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

 TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
 TIME OF CONCENTRATION (MIN.) = 64.19
 RAINFALL INTENSITY (INCH/HR) = 0.39
 AREA-AVERAGED Fm (INCH/HR) = 0.60
 AREA-AVERAGED Fp (INCH/HR) = 0.60
 AREA-AVERAGED Ap = 1.00
 EFFECTIVE STREAM AREA (ACRES) = 620.71
 TOTAL STREAM AREA (ACRES) = 620.71
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 5.85

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14.59	56.21	0.421	0.60 (0.59)	0.98	484.1	11900.00
2	5.85	64.19	0.392	0.60 (0.60)	1.00	620.7	11910.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20.08	56.21	0.421	0.60 (0.60)	0.99	1027.6	11900.00
2	19.46	64.19	0.392	0.60 (0.60)	0.99	1104.8	11910.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
 PEAK FLOW RATE (CFS) = 20.08 Tc (MIN.) = 56.21
 EFFECTIVE AREA (ACRES) = 1027.65 AREA-AVERAGED Fm (INCH/HR) = 0.60
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 1104.8
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11920.00 = 12869.60 FEET.

FLOW PROCESS FROM NODE 11920.00 TO NODE 11921.00 IS CODE = 51

 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

 ELEVATION DATA: UPSTREAM (FEET) = 873.95 DOWNSTREAM (FEET) = 827.94
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1417.25 CHANNEL SLOPE = 0.0325
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00

* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.394
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 107.47 0.60 1.000 -
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 20.08
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 3.41
 AVERAGE FLOW DEPTH (FEET) = 1.40 TRAVEL TIME (MIN.) = 6.93
 Tc (MIN.) = 63.14
 SUBAREA AREA (ACRES) = 107.47 SUBAREA RUNOFF (CFS) = 0.00
 EFFECTIVE AREA (ACRES) = 1135.12 AREA-AVERAGED Fm (INCH/HR) = 0.60
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA (ACRES) = 1212.3 PEAK FLOW RATE (CFS) = 20.08
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 1.40 FLOW VELOCITY (FEET/SEC.) = 3.41
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11921.00 = 14286.85 FEET.

FLOW PROCESS FROM NODE 11921.00 TO NODE 11922.00 IS CODE = 51

 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

 ELEVATION DATA: UPSTREAM (FEET) = 827.94 DOWNSTREAM (FEET) = 753.55
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1886.43 CHANNEL SLOPE = 0.0394
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.379

SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 344.27 0.60 1.000 -
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 20.08
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 3.66
 AVERAGE FLOW DEPTH (FEET) = 1.35 TRAVEL TIME (MIN.) = 8.60
 Tc (MIN.) = 71.74
 SUBAREA AREA (ACRES) = 344.27 SUBAREA RUNOFF (CFS) = 0.00
 EFFECTIVE AREA (ACRES) = 1479.39 AREA-AVERAGED Fm (INCH/HR) = 0.60
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA (ACRES) = 1556.5 PEAK FLOW RATE (CFS) = 20.08
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 1.35 FLOW VELOCITY (FEET/SEC.) = 3.66

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11922.00 = 16173.28 FEET.

FLOW PROCESS FROM NODE 11922.00 TO NODE 11923.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 753.55 DOWNSTREAM(FEET) = 641.58
CHANNEL LENGTH THRU SUBAREA(FEET) = 2860.88 CHANNEL SLOPE = 0.0391
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.355

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	165.18	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 20.08

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.65

AVERAGE FLOW DEPTH(FEET) = 1.36 TRAVEL TIME(MIN.) = 13.08

Tc(MIN.) = 84.82

SUBAREA AREA(ACRES) = 165.18 SUBAREA RUNOFF(CFS) = 0.00

EFFECTIVE AREA(ACRES) = 1644.57 AREA-AVERAGED Fm(INCH/HR) = 0.60

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.000

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 1721.7 PEAK FLOW RATE(CFS) = 20.08

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.36 FLOW VELOCITY(FEET/SEC.) = 3.65

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11923.00 = 19034.16 FEET.

FLOW PROCESS FROM NODE 11923.00 TO NODE 11924.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 641.58 DOWNSTREAM(FEET) = 579.89
CHANNEL LENGTH THRU SUBAREA(FEET) = 1844.02 CHANNEL SLOPE = 0.0335
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.339

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	433.73	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 20.08

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.45

AVERAGE FLOW DEPTH(FEET) = 1.39 TRAVEL TIME(MIN.) = 8.91

Tc(MIN.) = 93.73

SUBAREA AREA(ACRES) = 433.73 SUBAREA RUNOFF(CFS) = 0.00

EFFECTIVE AREA(ACRES) = 2078.30 AREA-AVERAGED Fm(INCH/HR) = 0.60

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.000

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 2155.4 PEAK FLOW RATE(CFS) = 20.08

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.39 FLOW VELOCITY(FEET/SEC.) = 3.45

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11924.00 = 20878.18 FEET.

FLOW PROCESS FROM NODE 11924.00 TO NODE 11925.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 579.89 DOWNSTREAM(FEET) = 494.12
CHANNEL LENGTH THRU SUBAREA(FEET) = 2756.15 CHANNEL SLOPE = 0.0311
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.313

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	265.42	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 20.08

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.35

AVERAGE FLOW DEPTH(FEET) = 1.41 TRAVEL TIME(MIN.) = 13.73

Tc(MIN.) = 107.46

SUBAREA AREA(ACRES) = 265.42 SUBAREA RUNOFF(CFS) = 0.00

EFFECTIVE AREA(ACRES) = 2343.72 AREA-AVERAGED Fm(INCH/HR) = 0.60

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.000

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 2420.9 PEAK FLOW RATE(CFS) = 20.08

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.41 FLOW VELOCITY(FEET/SEC.) = 3.35

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11925.00 = 23634.33 FEET.

FLOW PROCESS FROM NODE 11925.00 TO NODE 11926.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 494.12 DOWNSTREAM(FEET) = 458.40
CHANNEL LENGTH THRU SUBAREA(FEET) = 1922.70 CHANNEL SLOPE = 0.0186
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.292
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 97.46 0.60 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 20.08
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 2.75
 AVERAGE FLOW DEPTH (FEET) = 1.56 TRAVEL TIME (MIN.) = 11.64
 Tc (MIN.) = 119.10
 SUBAREA AREA (ACRES) = 97.46 SUBAREA RUNOFF (CFS) = 0.00
 EFFECTIVE AREA (ACRES) = 2441.18 AREA-AVERAGED Fm (INCH/HR) = 0.60
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA (ACRES) = 2518.3 PEAK FLOW RATE (CFS) = 20.08
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 1.56 FLOW VELOCITY (FEET/SEC.) = 2.75
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11926.00 = 25557.03 FEET.

 FLOW PROCESS FROM NODE 11926.00 TO NODE 11927.00 IS CODE = 51

>>>> COMPUTE TRAPEZOIDAL CHANNEL FLOW <<<<<
 >>>> TRAVELTIME THRU SUBAREA (EXISTING ELEMENT) <<<<<

ELEVATION DATA: UPSTREAM (FEET) = 458.40 DOWNSTREAM (FEET) = 399.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 2710.13 CHANNEL SLOPE = 0.0219
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.277
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 53.83 0.60 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 20.08
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 2.94
 AVERAGE FLOW DEPTH (FEET) = 1.51 TRAVEL TIME (MIN.) = 15.34
 Tc (MIN.) = 134.44
 SUBAREA AREA (ACRES) = 53.83 SUBAREA RUNOFF (CFS) = 0.00
 EFFECTIVE AREA (ACRES) = 2495.01 AREA-AVERAGED Fm (INCH/HR) = 0.60
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA (ACRES) = 2572.1 PEAK FLOW RATE (CFS) = 20.08
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 1.51 FLOW VELOCITY (FEET/SEC.) = 2.94
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 28267.16 FEET.

 FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 10

>>>> MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<
 =====

 FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 15.1

>>>> DEFINE MEMORY BANK # 1 <<<<<
 =====

PEAK FLOWRATE TABLE FILE NAME: P401XX02.DNA
 MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	26.02	43.27	0.60 (0.60)	1.00	607.9	40130.00
2	25.27	47.99	0.60 (0.60)	1.00	654.2	40100.00
TOTAL AREA (ACRES) =			654.2			

 FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 11

>>>> CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY <<<<<
 =====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20.08	134.44	0.277	0.60 (0.60)	1.00	2495.0	11900.00
2	19.46	143.09	0.269	0.60 (0.60)	1.00	2572.1	11910.00
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 =			28267.16 FEET.				

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	26.02	43.27	0.493	0.60 (0.60)	1.00	607.9	40130.00
2	25.27	47.99	0.466	0.60 (0.60)	1.00	654.2	40100.00
LONGEST FLOWPATH FROM NODE 40100.00 TO NODE 11927.00 =			10245.00 FEET.				

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	37.54	43.27	0.493	0.60 (0.60)	1.00	1411.0	40130.00
2	37.34	47.99	0.466	0.60 (0.60)	1.00	1544.9	40100.00
3	35.09	134.44	0.277	0.60 (0.60)	1.00	3149.2	11900.00
4	34.04	143.09	0.269	0.60 (0.60)	1.00	3226.4	11910.00
TOTAL AREA (ACRES) =			3226.4				

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 37.54 Tc (MIN.) = 43.272
 EFFECTIVE AREA (ACRES) = 1410.97 AREA-AVERAGED Fm (INCH/HR) = 0.60
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 3226.4
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 28267.16 FEET.

```

*****
FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 12
-----
>>>>CLEAR MEMORY BANK # 1 <<<<<
=====
*****
FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.50 IS CODE = 51
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 399.00 DOWNSTREAM(FEET) = 384.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 986.26 CHANNEL SLOPE = 0.0152
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
CHANNEL FLOW THRU SUBAREA(CFS) = 37.54
FLOW VELOCITY(FEET/SEC.) = 2.98 FLOW DEPTH(FEET) = 2.05
TRAVEL TIME(MIN.) = 5.51 Tc(MIN.) = 48.78
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.50 = 29253.42 FEET.
*****
FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 48.78
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.462
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 2.40 0.60 1.000 -
USER-DEFINED - 1.70 0.60 1.000 -
USER-DEFINED - 1.50 0.60 1.000 -
USER-DEFINED - 1.30 0.60 1.000 -
USER-DEFINED - 0.90 0.60 1.000 -
USER-DEFINED - 0.60 0.60 1.000 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 8.40 SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 1419.37 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 3234.8 PEAK FLOW RATE(CFS) = 37.54
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
*****
FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 48.78
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.462
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 78.01 0.60 0.984 -

```

```

LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.30 0.60 1.000 -
USER-DEFINED - 0.10 0.60 1.000 -
USER-DEFINED - 0.10 0.60 1.000 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 0.50 SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 1419.87 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 3235.2 PEAK FLOW RATE(CFS) = 37.54
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
*****
FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 48.78
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.462
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.80 0.60 1.000 -
USER-DEFINED - 0.70 0.60 1.000 -
USER-DEFINED - 0.20 0.60 1.000 -
USER-DEFINED - 0.20 0.60 0.000 -
USER-DEFINED - 0.10 0.60 1.000 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.900
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 2.00 SUBAREA RUNOFF(CFS) = 0.08
EFFECTIVE AREA(ACRES) = 1421.87 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 3237.2 PEAK FLOW RATE(CFS) = 37.54
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
*****
FLOW PROCESS FROM NODE 11927.50 TO NODE 11928.00 IS CODE = 51
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 384.00 DOWNSTREAM(FEET) = 359.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 647.19 CHANNEL SLOPE = 0.0386
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.448
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 78.01 0.60 0.984 -

```

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.984
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 37.79
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.25
 AVERAGE FLOW DEPTH(FEET) = 1.72 TRAVEL TIME(MIN.) = 2.54
 Tc(MIN.) = 51.32
 SUBAREA AREA(ACRES) = 78.01 SUBAREA RUNOFF(CFS) = 0.50
 EFFECTIVE AREA(ACRES) = 1499.88 AREA-AVERAGED Fm(INCH/HR) = 0.60
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA(ACRES) = 3315.3 PEAK FLOW RATE(CFS) = 37.54
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 1.72 FLOW VELOCITY(FEET/SEC.) = 4.23
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11928.00 = 29900.61 FEET.

 FLOW PROCESS FROM NODE 11928.00 TO NODE 11928.00 IS CODE = 81

 >>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 51.32
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.448
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.10	0.60	1.000	-
USER-DEFINED	-	0.60	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 SUBAREA AREA(ACRES) = 1.70 SUBAREA RUNOFF(CFS) = 0.00
 EFFECTIVE AREA(ACRES) = 1501.58 AREA-AVERAGED Fm(INCH/HR) = 0.60
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA(ACRES) = 3317.0 PEAK FLOW RATE(CFS) = 37.54
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 51

 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 359.00 DOWNSTREAM(FEET) = 341.63
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1322.66 CHANNEL SLOPE = 0.0131
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.405
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

USER-DEFINED - 8.18 0.60 0.890 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.890
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 37.70
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 2.84
 AVERAGE FLOW DEPTH(FEET) = 2.10 TRAVEL TIME(MIN.) = 7.76
 Tc(MIN.) = 59.07
 SUBAREA AREA(ACRES) = 8.18 SUBAREA RUNOFF(CFS) = 0.33
 EFFECTIVE AREA(ACRES) = 1509.76 AREA-AVERAGED Fm(INCH/HR) = 0.60
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA(ACRES) = 3325.1 PEAK FLOW RATE(CFS) = 37.54
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 2.10 FLOW VELOCITY(FEET/SEC.) = 2.83
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11929.00 = 31223.27 FEET.

 FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 81

 >>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 59.07
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.405
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.90	0.60	1.000	-
USER-DEFINED	-	0.60	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 SUBAREA AREA(ACRES) = 2.50 SUBAREA RUNOFF(CFS) = 0.00
 EFFECTIVE AREA(ACRES) = 1512.26 AREA-AVERAGED Fm(INCH/HR) = 0.60
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA(ACRES) = 3327.6 PEAK FLOW RATE(CFS) = 37.54
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 10

 >>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 3 <<<<

 FLOW PROCESS FROM NODE 11841.00 TO NODE 12527.00 IS CODE = 15.1

 >>>>DEFINE MEMORY BANK # 1 <<<<

=====

PEAK FLOWRATE TABLE FILE NAME: S18X02.DNA
 MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	368.65	67.72	0.60 (0.60)	0.99	5288.9	11831.00
2	465.61	93.02	0.60 (0.60)	0.99	7637.9	11530.00
3	535.78	108.89	0.60 (0.60)	0.99	9918.6	11701.00
4	556.64	113.96	0.60 (0.60)	0.99	10678.6	11000.00
5	648.54	131.44	0.60 (0.60)	1.00	14702.7	11350.00
6	669.95	137.84	0.60 (0.60)	1.00	16212.5	10850.00
7	634.45	145.72	0.60 (0.60)	1.00	17563.5	10800.00
8	586.10	152.52	0.60 (0.60)	1.00	18539.6	11220.00
9	519.45	163.12	0.60 (0.60)	1.00	19646.2	10910.00
10	469.53	171.24	0.60 (0.60)	1.00	20293.7	10630.00
11	347.01	209.19	0.60 (0.60)	1.00	24538.0	10600.00
12	331.29	220.41	0.60 (0.60)	1.00	26174.2	11600.00
13	322.91	238.24	0.60 (0.60)	1.00	28033.8	10710.00
14	317.31	246.05	0.60 (0.60)	1.00	28544.1	10410.00
15	303.17	267.47	0.60 (0.60)	1.00	29747.0	10700.00
16	301.61	284.97	0.60 (0.60)	1.00	30768.1	10200.00
17	295.49	303.27	0.60 (0.60)	1.00	31516.6	10320.00
18	293.33	307.96	0.60 (0.60)	1.00	31656.1	10300.00
19	283.27	326.33	0.60 (0.60)	1.00	31924.4	10210.00
20	238.59	442.68	0.60 (0.60)	1.00	32916.6	10100.00

TOTAL AREA (ACRES) = 32916.6

FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<<

PEAK FLOWRATE TABLE FILE NAME: S25X02.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	125.40	141.27	0.60 (0.59)	0.99	4854.0	12500.00
2	161.45	169.35	0.60 (0.59)	0.99	6554.4	12300.00
3	161.10	174.44	0.60 (0.59)	0.99	6936.3	12330.00
4	157.88	201.19	0.60 (0.59)	0.98	8762.3	12410.00
5	155.88	214.55	0.60 (0.59)	0.98	9659.4	12400.00
6	155.08	218.12	0.60 (0.59)	0.98	9844.2	12211.00
7	166.76	226.18	0.60 (0.59)	0.98	10504.5	12201.00
8	174.86	233.49	0.60 (0.58)	0.97	10953.4	12261.00
9	174.65	235.08	0.60 (0.58)	0.98	11005.7	12111.00
10	174.14	239.69	0.60 (0.59)	0.98	11204.7	12231.00
11	171.80	258.00	0.60 (0.59)	0.98	11864.4	12101.10
12	151.73	298.09	0.60 (0.59)	0.98	13091.3	12010.00
13	99.71	374.11	0.60 (0.59)	0.98	13237.1	12000.00

TOTAL AREA (ACRES) = 13237.1

FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	125.40	141.27	0.60 (0.59)	0.99	4854.0	12500.00

2	161.45	169.35	0.60 (0.59)	0.99	6554.4	12300.00
3	161.10	174.44	0.60 (0.59)	0.99	6936.3	12330.00
4	157.88	201.19	0.60 (0.59)	0.98	8762.3	12410.00
5	155.88	214.55	0.60 (0.59)	0.98	9659.4	12400.00
6	155.08	218.12	0.60 (0.59)	0.98	9844.2	12211.00
7	166.76	226.18	0.60 (0.59)	0.98	10504.5	12201.00
8	174.86	233.49	0.60 (0.58)	0.97	10953.4	12261.00
9	174.65	235.08	0.60 (0.58)	0.98	11005.7	12111.00
10	174.14	239.69	0.60 (0.59)	0.98	11204.7	12231.00
11	171.80	258.00	0.60 (0.59)	0.98	11864.4	12101.10
12	151.73	298.09	0.60 (0.59)	0.98	13091.3	12010.00
13	99.71	374.11	0.60 (0.59)	0.98	13237.1	12000.00

TOTAL AREA (ACRES) = 13237.1

FLOW PROCESS FROM NODE 11841.00 TO NODE 12527.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	125.40	141.27	0.271	0.60 (0.59)	0.99	4854.0	12500.00
2	161.45	169.35	0.246	0.60 (0.59)	0.99	6554.4	12300.00
3	161.10	174.44	0.241	0.60 (0.59)	0.99	6936.3	12330.00
4	157.88	201.19	0.229	0.60 (0.59)	0.98	8762.3	12410.00
5	155.88	214.55	0.225	0.60 (0.59)	0.98	9659.4	12400.00
6	155.08	218.12	0.224	0.60 (0.59)	0.98	9844.2	12211.00
7	166.76	226.18	0.222	0.60 (0.59)	0.98	10504.5	12201.00
8	174.86	233.49	0.219	0.60 (0.58)	0.97	10953.4	12261.00
9	174.65	235.08	0.219	0.60 (0.58)	0.98	11005.7	12111.00
10	174.14	239.69	0.217	0.60 (0.59)	0.98	11204.7	12231.00
11	171.80	258.00	0.212	0.60 (0.59)	0.98	11864.4	12101.10
12	151.73	298.09	0.199	0.60 (0.59)	0.98	13091.3	12010.00
13	99.71	374.11	0.178	0.60 (0.59)	0.98	13237.1	12000.00

LONGEST FLOWPATH FROM NODE 12000.00 TO NODE 12527.00 = 77156.98 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	368.65	67.72	0.386	0.60 (0.60)	0.99	5288.9	11831.00
2	465.61	93.02	0.340	0.60 (0.60)	0.99	7637.9	11530.00
3	535.78	108.89	0.311	0.60 (0.60)	0.99	9918.6	11701.00
4	556.64	113.96	0.301	0.60 (0.60)	0.99	10678.6	11000.00
5	648.54	131.44	0.280	0.60 (0.60)	1.00	14702.7	11350.00
6	669.95	137.84	0.274	0.60 (0.60)	1.00	16212.5	10850.00
7	634.45	145.72	0.267	0.60 (0.60)	1.00	17563.5	10800.00
8	586.10	152.52	0.261	0.60 (0.60)	1.00	18539.6	11220.00
9	519.45	163.12	0.251	0.60 (0.60)	1.00	19646.2	10910.00
10	469.53	171.24	0.244	0.60 (0.60)	1.00	20293.7	10630.00
11	347.01	209.19	0.227	0.60 (0.60)	1.00	24538.0	10600.00
12	331.29	220.41	0.223	0.60 (0.60)	1.00	26174.2	11600.00
13	322.91	238.24	0.218	0.60 (0.60)	1.00	28033.8	10710.00
14	317.31	246.05	0.215	0.60 (0.60)	1.00	28544.1	10410.00
15	303.17	267.47	0.209	0.60 (0.60)	1.00	29747.0	10700.00
16	301.61	284.97	0.203	0.60 (0.60)	1.00	30768.1	10200.00
17	295.49	303.27	0.198	0.60 (0.60)	1.00	31516.6	10320.00

18 293.33 307.96 0.196 0.60(0.60) 1.00 31656.1 10300.00
 19 283.27 326.33 0.190 0.60(0.60) 1.00 31924.4 10210.00
 20 238.59 442.68 0.171 0.60(0.60) 1.00 32916.6 10100.00
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12527.00 = 97868.13 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	454.34	67.72	0.386	0.60(0.60)	0.99	7615.8	11831.00
2	569.38	93.02	0.340	0.60(0.60)	0.99	10834.1	11530.00
3	646.68	108.89	0.311	0.60(0.60)	0.99	13660.2	11701.00
4	669.16	113.96	0.301	0.60(0.60)	0.99	14594.1	11000.00
5	769.03	131.44	0.280	0.60(0.60)	0.99	19219.0	11350.00
6	793.71	137.84	0.274	0.60(0.60)	0.99	20948.8	10850.00
7	779.92	141.27	0.271	0.60(0.60)	0.99	21653.9	12500.00
8	765.57	145.72	0.267	0.60(0.60)	0.99	22687.0	10800.00
9	725.95	152.52	0.261	0.60(0.60)	0.99	24074.8	11220.00
10	672.92	163.12	0.251	0.60(0.60)	0.99	25823.7	10910.00
11	642.64	169.35	0.246	0.60(0.60)	0.99	26696.9	12300.00
12	630.86	171.24	0.244	0.60(0.60)	0.99	26990.1	10630.00
13	620.31	174.44	0.241	0.60(0.60)	0.99	27587.8	12330.00
14	530.72	201.19	0.229	0.60(0.60)	0.99	32405.3	12410.00
15	503.69	209.19	0.227	0.60(0.60)	0.99	33837.6	10600.00
16	495.39	214.55	0.225	0.60(0.60)	0.99	34978.5	12400.00
17	489.58	218.12	0.224	0.60(0.59)	0.99	35684.0	12211.00
18	489.69	220.41	0.223	0.60(0.59)	0.99	36206.2	11600.00
19	495.34	226.18	0.222	0.60(0.59)	0.99	37280.7	12201.00
20	500.01	233.49	0.219	0.60(0.59)	0.99	38491.2	12261.00
21	499.05	235.08	0.219	0.60(0.59)	0.99	38709.5	12111.00
22	497.21	238.24	0.218	0.60(0.59)	0.99	39176.2	10710.00
23	496.02	239.69	0.217	0.60(0.59)	0.99	39332.8	12231.00
24	490.64	246.05	0.215	0.60(0.59)	0.99	39977.8	10410.00
25	481.22	258.00	0.212	0.60(0.59)	0.99	41079.8	12101.10
26	470.23	267.47	0.209	0.60(0.59)	0.99	41901.2	10700.00
27	459.92	284.97	0.203	0.60(0.59)	0.99	43457.9	10200.00
28	448.96	298.09	0.199	0.60(0.59)	0.99	44396.1	12010.00
29	443.68	303.27	0.198	0.60(0.59)	0.99	44617.8	10320.00
30	438.31	307.96	0.196	0.60(0.59)	0.99	44766.3	10300.00
31	415.69	326.33	0.190	0.60(0.60)	0.99	45069.8	10210.00
32	364.64	374.11	0.178	0.60(0.60)	0.99	45568.9	12000.00
33	333.92	442.68	0.171	0.60(0.60)	0.99	46153.7	10100.00

TOTAL AREA(ACRES) = 46153.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
 PEAK FLOW RATE(CFS) = 793.71 Tc(MIN.) = 137.844
 EFFECTIVE AREA(ACRES) = 20948.83 AREA-AVERAGED Fm(INCH/HR) = 0.60
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 46153.7
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12527.00 = 97868.13 FEET.

 FLOW PROCESS FROM NODE 12527.00 TO NODE 11929.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

 ELEVATION DATA: UPSTREAM(FEET) = 347.47 DOWNSTREAM(FEET) = 341.63
 CHANNEL LENGTH THRU SUBAREA(FEET) = 532.38 CHANNEL SLOPE = 0.0110

CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.273
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCSSOIL AREA Fp Ap SCSS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 14.37 0.60 0.987 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.987
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 793.73
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.69
 AVERAGE FLOW DEPTH(FEET) = 5.86 TRAVEL TIME(MIN.) = 1.15
 Tc(MIN.) = 139.00
 SUBAREA AREA(ACRES) = 14.37 SUBAREA RUNOFF(CFS) = 0.05
 EFFECTIVE AREA(ACRES) = 20963.20 AREA-AVERAGED Fm(INCH/HR) = 0.60
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA(ACRES) = 46168.0 PEAK FLOW RATE(CFS) = 793.71
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 5.86 FLOW VELOCITY(FEET/SEC.) = 7.69
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

 FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<
 =====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	454.34	69.05	0.384	0.60(0.60)	0.99	7630.2	11831.00
2	569.38	94.27	0.338	0.60(0.60)	0.99	10848.4	11530.00
3	646.68	110.11	0.308	0.60(0.60)	0.99	13674.5	11701.00
4	669.16	115.16	0.299	0.60(0.60)	0.99	14608.5	11000.00
5	769.03	132.60	0.279	0.60(0.60)	0.99	19233.4	11350.00
6	793.71	139.00	0.273	0.60(0.60)	0.99	20963.2	10850.00
7	779.92	142.43	0.270	0.60(0.60)	0.99	21668.2	12500.00
8	765.57	146.88	0.266	0.60(0.60)	0.99	22701.4	10800.00
9	725.95	153.70	0.260	0.60(0.60)	0.99	24089.2	11220.00
10	672.92	164.33	0.250	0.60(0.60)	0.99	25838.1	10910.00
11	642.64	170.56	0.244	0.60(0.60)	0.99	26711.3	12300.00
12	630.86	172.47	0.243	0.60(0.60)	0.99	27004.5	10630.00
13	620.31	175.67	0.240	0.60(0.60)	0.99	27602.2	12330.00
14	530.72	202.46	0.229	0.60(0.60)	0.99	32419.7	12410.00
15	503.69	210.48	0.227	0.60(0.60)	0.99	33852.0	10600.00
16	495.39	215.85	0.225	0.60(0.60)	0.99	34992.9	12400.00
17	489.58	219.42	0.224	0.60(0.59)	0.99	35698.4	12211.00
18	489.69	221.71	0.223	0.60(0.59)	0.99	36220.6	11600.00
19	495.34	227.48	0.221	0.60(0.59)	0.99	37295.0	12201.00
20	500.01	234.78	0.219	0.60(0.59)	0.99	38505.6	12261.00
21	499.05	236.37	0.218	0.60(0.59)	0.99	38723.9	12111.00
22	497.21	239.54	0.217	0.60(0.59)	0.99	39190.6	10710.00

23	496.02	240.98	0.217	0.60 (0.59)	0.99	39347.2	12231.00
24	490.64	247.35	0.215	0.60 (0.59)	0.99	39992.2	10410.00
25	481.22	259.31	0.211	0.60 (0.59)	0.99	41094.2	12101.10
26	470.23	268.79	0.208	0.60 (0.59)	0.99	41915.6	10700.00
27	459.92	286.29	0.203	0.60 (0.59)	0.99	43472.2	10200.00
28	448.96	299.42	0.199	0.60 (0.59)	0.99	44410.5	12010.00
29	443.68	304.60	0.197	0.60 (0.59)	0.99	44632.2	10320.00
30	438.31	309.30	0.196	0.60 (0.59)	0.99	44780.7	10300.00
31	415.69	327.68	0.190	0.60 (0.60)	0.99	45084.2	10210.00
32	364.64	375.51	0.178	0.60 (0.60)	0.99	45583.3	12000.00
33	333.92	444.11	0.170	0.60 (0.60)	0.99	46168.0	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	37.54	59.07	0.405	0.60 (0.60)	1.00	1512.3	40130.00
2	37.34	63.82	0.393	0.60 (0.60)	1.00	1646.2	40100.00
3	35.09	150.49	0.263	0.60 (0.60)	1.00	3250.5	11900.00
4	34.04	159.28	0.255	0.60 (0.60)	1.00	3327.6	11910.00

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11929.00 = 31223.27 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	447.92	59.07	0.405	0.60 (0.60)	0.99	8040.4	40130.00
2	467.58	63.82	0.393	0.60 (0.60)	0.99	8698.7	40100.00
3	491.55	69.05	0.384	0.60 (0.60)	0.99	9373.2	11831.00
4	605.93	94.27	0.338	0.60 (0.60)	0.99	13058.3	11530.00
5	682.82	110.11	0.308	0.60 (0.60)	0.99	16177.5	11701.00
6	705.17	115.16	0.299	0.60 (0.60)	0.99	17205.0	11000.00
7	804.59	132.60	0.279	0.60 (0.60)	0.99	22152.7	11350.00
8	829.10	139.00	0.273	0.60 (0.60)	0.99	24000.9	10850.00
9	815.22	142.43	0.270	0.60 (0.60)	0.99	24769.4	12500.00
10	800.75	146.88	0.266	0.60 (0.60)	0.99	25885.1	10800.00
11	779.66	150.49	0.263	0.60 (0.60)	0.99	26687.4	11900.00
12	760.65	153.70	0.260	0.60 (0.60)	0.99	27367.8	11220.00
13	732.14	159.28	0.255	0.60 (0.60)	0.99	28335.4	11910.00
14	706.35	164.33	0.250	0.60 (0.60)	0.99	29165.7	10910.00
15	675.33	170.56	0.244	0.60 (0.60)	0.99	30038.9	12300.00
16	663.31	172.47	0.243	0.60 (0.60)	0.99	30332.2	10630.00
17	652.38	175.67	0.240	0.60 (0.60)	0.99	30929.8	12330.00
18	561.34	202.46	0.229	0.60 (0.60)	0.99	35747.4	12410.00
19	533.97	210.48	0.227	0.60 (0.60)	0.99	37179.6	10600.00
20	525.44	215.85	0.225	0.60 (0.60)	0.99	38320.6	12400.00
21	519.49	219.42	0.224	0.60 (0.60)	0.99	39026.0	12211.00
22	519.50	221.71	0.223	0.60 (0.60)	0.99	39548.2	11600.00
23	524.91	227.48	0.221	0.60 (0.59)	0.99	40622.7	12201.00
24	529.28	234.78	0.219	0.60 (0.59)	0.99	41833.3	12261.00
25	528.26	236.37	0.218	0.60 (0.59)	0.99	42051.5	12111.00
26	526.28	239.54	0.217	0.60 (0.59)	0.99	42518.2	10710.00
27	525.03	240.98	0.217	0.60 (0.59)	0.99	42674.8	12231.00
28	519.39	247.35	0.215	0.60 (0.59)	0.99	43319.9	10410.00
29	509.47	259.31	0.211	0.60 (0.59)	0.99	44421.8	12101.10
30	498.09	268.79	0.208	0.60 (0.59)	0.99	45243.2	10700.00
31	487.05	286.29	0.203	0.60 (0.60)	0.99	46799.9	10200.00
32	475.54	299.42	0.199	0.60 (0.60)	0.99	47738.1	12010.00
33	470.05	304.60	0.197	0.60 (0.60)	0.99	47959.9	10320.00

34	464.49	309.30	0.196	0.60 (0.60)	0.99	48108.4	10300.00
35	441.09	327.68	0.190	0.60 (0.60)	0.99	48411.9	10210.00
36	388.46	375.51	0.178	0.60 (0.60)	0.99	48910.9	12000.00
37	356.70	444.11	0.170	0.60 (0.60)	0.99	49495.7	10100.00

TOTAL AREA (ACRES) = 49495.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 829.10 Tc (MIN.) = 138.997
 EFFECTIVE AREA (ACRES) = 24000.90 AREA-AVERAGED Fm (INCH/HR) = 0.60
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 49495.7
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

=====

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 49495.7 TC (MIN.) = 139.00
 EFFECTIVE AREA (ACRES) = 24000.90 AREA-AVERAGED Fm (INCH/HR) = 0.60
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.995
 PEAK FLOW RATE (CFS) = 829.10

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	447.92	59.07	0.405	0.60 (0.60)	0.99	8040.4	40130.00
2	467.58	63.82	0.393	0.60 (0.60)	0.99	8698.7	40100.00
3	491.55	69.05	0.384	0.60 (0.60)	0.99	9373.2	11831.00
4	605.93	94.27	0.338	0.60 (0.60)	0.99	13058.3	11530.00
5	682.82	110.11	0.308	0.60 (0.60)	0.99	16177.5	11701.00
6	705.17	115.16	0.299	0.60 (0.60)	0.99	17205.0	11000.00
7	804.59	132.60	0.279	0.60 (0.60)	0.99	22152.7	11350.00
8	829.10	139.00	0.273	0.60 (0.60)	0.99	24000.9	10850.00
9	815.22	142.43	0.270	0.60 (0.60)	0.99	24769.4	12500.00
10	800.75	146.88	0.266	0.60 (0.60)	0.99	25885.1	10800.00
11	779.66	150.49	0.263	0.60 (0.60)	0.99	26687.4	11900.00
12	760.65	153.70	0.260	0.60 (0.60)	0.99	27367.8	11220.00
13	732.14	159.28	0.255	0.60 (0.60)	0.99	28335.4	11910.00
14	706.35	164.33	0.250	0.60 (0.60)	0.99	29165.7	10910.00
15	675.33	170.56	0.244	0.60 (0.60)	0.99	30038.9	12300.00
16	663.31	172.47	0.243	0.60 (0.60)	0.99	30332.2	10630.00
17	652.38	175.67	0.240	0.60 (0.60)	0.99	30929.8	12330.00
18	561.34	202.46	0.229	0.60 (0.60)	0.99	35747.4	12410.00
19	533.97	210.48	0.227	0.60 (0.60)	0.99	37179.6	10600.00
20	525.44	215.85	0.225	0.60 (0.60)	0.99	38320.6	12400.00
21	519.49	219.42	0.224	0.60 (0.60)	0.99	39026.0	12211.00
22	519.50	221.71	0.223	0.60 (0.60)	0.99	39548.2	11600.00
23	524.91	227.48	0.221	0.60 (0.59)	0.99	40622.7	12201.00
24	529.28	234.78	0.219	0.60 (0.59)	0.99	41833.3	12261.00
25	528.26	236.37	0.218	0.60 (0.59)	0.99	42051.5	12111.00
26	526.28	239.54	0.217	0.60 (0.59)	0.99	42518.2	10710.00
27	525.03	240.98	0.217	0.60 (0.59)	0.99	42674.8	12231.00
28	519.39	247.35	0.215	0.60 (0.59)	0.99	43319.9	10410.00
29	509.47	259.31	0.211	0.60 (0.59)	0.99	44421.8	12101.10
30	498.09	268.79	0.208	0.60 (0.59)	0.99	45243.2	10700.00
31	487.05	286.29	0.203	0.60 (0.60)	0.99	46799.9	10200.00
32	475.54	299.42	0.199	0.60 (0.60)	0.99	47738.1	12010.00
33	470.05	304.60	0.197	0.60 (0.60)	0.99	47959.9	10320.00
34	464.49	309.30	0.196	0.60 (0.60)	0.99	48108.4	10300.00
35	441.09	327.68	0.190	0.60 (0.60)	0.99	48411.9	10210.00
36	388.46	375.51	0.178	0.60 (0.60)	0.99	48910.9	12000.00

37 356.70 444.11 0.170 0.60 (0.60) 0.99 49495.7 10100.00

=====
=====
END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 126 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 2-YR EV FEB 2023 ROKAMOTO *

FILE NAME: RU02EV26.DAT
TIME/DATE OF STUDY: 13:34 02/09/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 2.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 1.873
- 2) 10.00; 1.249
- 3) 15.00; 0.951
- 4) 20.00; 0.777
- 5) 25.00; 0.669
- 6) 30.00; 0.593
- 7) 40.00; 0.511
- 8) 50.00; 0.454
- 9) 60.00; 0.400
- 10) 90.00; 0.346
- 11) 120.00; 0.290
- 12) 180.00; 0.236
- 13) 360.00; 0.180
- 14) 1200.00; 0.084

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU02EV19.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	491.55	69.05	0.60 (0.60)	0.99	9373.2	11831.00
2	605.93	94.27	0.60 (0.60)	0.99	13058.3	11530.00
3	705.17	115.16	0.60 (0.60)	0.99	17205.0	11000.00
4	804.59	132.60	0.60 (0.60)	0.99	22152.7	11350.00
5	829.10	139.00	0.60 (0.60)	0.99	24000.9	10850.00
6	800.75	146.88	0.60 (0.60)	0.99	25885.1	10800.00
7	732.14	159.28	0.60 (0.60)	0.99	28335.4	11910.00
8	675.33	170.56	0.60 (0.60)	0.99	30038.9	12300.00
9	561.34	202.46	0.60 (0.60)	0.99	35747.4	12410.00
10	533.97	210.48	0.60 (0.60)	0.99	37179.6	10600.00
11	524.91	227.48	0.60 (0.59)	0.99	40622.7	12201.00
12	529.28	234.78	0.60 (0.59)	0.99	41833.3	12261.00
13	519.39	247.35	0.60 (0.59)	0.99	43319.9	10410.00
14	509.47	259.31	0.60 (0.59)	0.99	44421.8	12101.10
15	498.09	268.79	0.60 (0.59)	0.99	45243.2	10700.00
16	487.05	286.29	0.60 (0.60)	0.99	46799.9	10200.00
17	475.54	299.42	0.60 (0.60)	0.99	47738.1	12010.00
18	441.09	327.68	0.60 (0.60)	0.99	48411.9	10210.00
19	388.46	375.51	0.60 (0.60)	0.99	48910.9	12000.00
20	356.70	444.11	0.60 (0.60)	0.99	49495.7	10100.00
TOTAL AREA (ACRES) =						49495.7

FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	491.55	69.05	0.60 (0.60)	0.99	9373.2	11831.00
2	605.93	94.27	0.60 (0.60)	0.99	13058.3	11530.00
3	705.17	115.16	0.60 (0.60)	0.99	17205.0	11000.00
4	804.59	132.60	0.60 (0.60)	0.99	22152.7	11350.00
5	829.10	139.00	0.60 (0.60)	0.99	24000.9	10850.00
6	800.75	146.88	0.60 (0.60)	0.99	25885.1	10800.00
7	732.14	159.28	0.60 (0.60)	0.99	28335.4	11910.00
8	675.33	170.56	0.60 (0.60)	0.99	30038.9	12300.00
9	561.34	202.46	0.60 (0.60)	0.99	35747.4	12410.00
10	533.97	210.48	0.60 (0.60)	0.99	37179.6	10600.00
11	524.91	227.48	0.60 (0.59)	0.99	40622.7	12201.00
12	529.28	234.78	0.60 (0.59)	0.99	41833.3	12261.00
13	519.39	247.35	0.60 (0.59)	0.99	43319.9	10410.00

14 509.47 259.31 0.60(0.59) 0.99 44421.8 12101.10
 15 498.09 268.79 0.60(0.59) 0.99 45243.2 10700.00
 16 487.05 286.29 0.60(0.60) 0.99 46799.9 10200.00
 17 475.54 299.42 0.60(0.60) 0.99 47738.1 12010.00
 18 441.09 327.68 0.60(0.60) 0.99 48411.9 10210.00
 19 388.46 375.51 0.60(0.60) 0.99 48910.9 12000.00
 20 356.70 444.11 0.60(0.60) 0.99 49495.7 10100.00
 TOTAL AREA(ACRES) = 49495.7

FLOW PROCESS FROM NODE 11929.00 TO NODE 12601.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 341.63 DOWNSTREAM(FEET) = 325.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1467.93 CHANNEL SLOPE = 0.0113
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.271

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.40	0.60	1.000	-
USER-DEFINED	-	0.50	0.60	1.000	-
USER-DEFINED	-	0.90	0.60	1.000	-
USER-DEFINED	-	0.50	0.60	1.000	-
USER-DEFINED	-	11.50	0.60	1.000	-
USER-DEFINED	-	0.30	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 829.10
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.76
 AVERAGE FLOW DEPTH(FEET) = 5.32 TRAVEL TIME(MIN.) = 2.51
 Tc(MIN.) = 141.50
 SUBAREA AREA(ACRES) = 14.10 SUBAREA RUNOFF(CFS) = 0.00
 EFFECTIVE AREA(ACRES) = 24015.00 AREA-AVERAGED Fm(INCH/HR) = 0.60
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA(ACRES) = 49509.8 PEAK FLOW RATE(CFS) = 829.10
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 5.32 FLOW VELOCITY(FEET/SEC.) = 9.76
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<<

PEAK FLOWRATE TABLE FILE NAME: 3002EVRL.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
------------------	------------	--------------	---------------------	----	---------------	-------------------

1 8.27 20.70 0.60(0.59) 0.98 51.1 600.00
 TOTAL AREA(ACRES) = 51.1

FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	491.55	71.90	0.379	0.60(0.60)	0.99	9387.3	11831.00
2	605.93	96.98	0.333	0.60(0.60)	0.99	13072.4	11530.00
3	705.17	117.77	0.294	0.60(0.60)	0.99	17219.1	11000.00
4	804.59	135.13	0.276	0.60(0.60)	0.99	22166.8	11350.00
5	829.10	141.50	0.271	0.60(0.60)	0.99	24015.0	10850.00
6	800.75	149.41	0.264	0.60(0.60)	0.99	25899.2	10800.00
7	732.14	161.86	0.252	0.60(0.60)	0.99	28349.5	11910.00
8	675.33	173.20	0.242	0.60(0.60)	0.99	30053.0	12300.00
9	561.34	205.22	0.228	0.60(0.60)	0.99	35761.5	12410.00
10	533.97	213.28	0.226	0.60(0.60)	0.99	37193.7	10600.00
11	524.91	230.29	0.220	0.60(0.59)	0.99	40636.8	12201.00
12	529.28	237.59	0.218	0.60(0.59)	0.99	41847.4	12261.00
13	519.39	250.16	0.214	0.60(0.59)	0.99	43334.0	10410.00
14	509.47	262.14	0.210	0.60(0.59)	0.99	44435.9	12101.10
15	498.09	271.63	0.207	0.60(0.59)	0.99	45257.3	10700.00
16	487.05	289.16	0.202	0.60(0.60)	0.99	46814.0	10200.00
17	475.54	302.30	0.198	0.60(0.60)	0.99	47752.2	12010.00
18	441.09	330.62	0.189	0.60(0.60)	0.99	48426.0	10210.00
19	388.46	378.54	0.178	0.60(0.60)	0.99	48925.0	12000.00
20	356.70	447.21	0.170	0.60(0.60)	0.99	49509.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	8.27	20.70	0.762	0.60(0.59)	0.98	51.1	600.00

LONGEST FLOWPATH FROM NODE 600.00 TO NODE 12601.00 = 4850.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	293.10	20.70	0.762	0.60(0.60)	0.99	2754.3	600.00
2	491.85	71.90	0.379	0.60(0.60)	0.99	9438.4	11831.00
3	606.19	96.98	0.333	0.60(0.60)	0.99	13123.5	11530.00
4	705.40	117.77	0.294	0.60(0.60)	0.99	17270.2	11000.00
5	804.80	135.13	0.276	0.60(0.60)	0.99	22217.9	11350.00
6	829.31	141.50	0.271	0.60(0.60)	0.99	24066.1	10850.00
7	800.96	149.41	0.264	0.60(0.60)	0.99	25950.3	10800.00
8	732.33	161.86	0.252	0.60(0.60)	0.99	28400.6	11910.00
9	675.52	173.20	0.242	0.60(0.60)	0.99	30104.1	12300.00
10	561.52	205.22	0.228	0.60(0.60)	0.99	35812.6	12410.00
11	534.15	213.28	0.226	0.60(0.60)	0.99	37244.8	10600.00
12	525.09	230.29	0.220	0.60(0.59)	0.99	40687.9	12201.00
13	529.45	237.59	0.218	0.60(0.59)	0.99	41898.5	12261.00
14	519.56	250.16	0.214	0.60(0.59)	0.99	43385.1	10410.00
15	509.64	262.14	0.210	0.60(0.59)	0.99	44487.0	12101.10

16 498.25 271.63 0.207 0.60(0.59) 0.99 45308.4 10700.00
17 487.20 289.16 0.202 0.60(0.60) 0.99 46865.1 10200.00
18 475.69 302.30 0.198 0.60(0.60) 0.99 47803.3 12010.00
19 441.24 330.62 0.189 0.60(0.60) 0.99 48477.1 10210.00
20 388.60 378.54 0.178 0.60(0.60) 0.99 48976.1 12000.00
21 356.83 447.21 0.170 0.60(0.60) 0.99 49560.9 10100.00
TOTAL AREA(ACRES) = 49560.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 829.31 Tc(MIN.) = 141.503
EFFECTIVE AREA(ACRES) = 24066.10 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 49560.9
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

FLOW PROCESS FROM NODE 12601.00 TO NODE 12603.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 325.00 DOWNSTREAM(FEET) = 310.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1690.00 CHANNEL SLOPE = 0.0089
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
CHANNEL FLOW THRU SUBAREA(CFS) = 829.31
FLOW VELOCITY(FEET/SEC.) = 8.92 FLOW DEPTH(FEET) = 5.57
TRAVEL TIME(MIN.) = 3.16 Tc(MIN.) = 144.66
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.45 FEET.

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 4E02EVRL.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM	Q	Tc	Fp(Fm)	Ap	Ae	HEADWATER
NUMBER	(CFS)	(MIN.)	(INCH/HR)	(ACRES)		NODE
1	120.67	10.61	0.60(0.31)	0.52	147.4	800.00
2	98.94	14.81	0.60(0.34)	0.57	167.3	818.00
3	87.28	16.53	0.60(0.35)	0.58	171.0	810.00

TOTAL AREA(ACRES) = 171.0

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	--------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	293.10	24.80	0.673	0.60(0.60)	0.99	2754.3 600.00
2	491.85	75.49	0.372	0.60(0.60)	0.99	9438.4 11831.00
3	606.19	100.39	0.327	0.60(0.60)	0.99	13123.5 11530.00
4	705.40	121.06	0.289	0.60(0.60)	0.99	17270.2 11000.00
5	804.80	138.31	0.274	0.60(0.60)	0.99	22217.9 11350.00
6	829.31	144.66	0.268	0.60(0.60)	0.99	24066.1 10850.00
7	800.96	152.60	0.261	0.60(0.60)	0.99	25950.3 10800.00
8	732.33	165.12	0.249	0.60(0.60)	0.99	28400.6 11910.00
9	675.52	176.52	0.239	0.60(0.60)	0.99	30104.1 12300.00
10	561.52	208.71	0.227	0.60(0.60)	0.99	35812.6 12410.00
11	534.15	216.81	0.225	0.60(0.60)	0.99	37244.8 10600.00
12	525.09	233.83	0.219	0.60(0.59)	0.99	40687.9 12201.00
13	529.45	241.12	0.217	0.60(0.59)	0.99	41898.5 12261.00
14	519.56	253.71	0.213	0.60(0.59)	0.99	43385.1 10410.00
15	509.64	265.71	0.209	0.60(0.59)	0.99	44487.0 12101.10
16	498.25	275.22	0.206	0.60(0.59)	0.99	45308.4 10700.00
17	487.20	292.76	0.201	0.60(0.60)	0.99	46865.1 10200.00
18	475.69	305.92	0.197	0.60(0.60)	0.99	47803.3 12010.00
19	441.24	334.32	0.188	0.60(0.60)	0.99	48477.1 10210.00
20	388.60	382.36	0.177	0.60(0.60)	0.99	48976.1 12000.00
21	356.83	451.11	0.170	0.60(0.60)	0.99	49560.9 10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.45 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)		(ACRES)	NODE
1	120.67	10.61	1.213	0.60(0.31)	0.52	147.4	800.00
2	98.94	14.81	0.962	0.60(0.34)	0.57	167.3	818.00
3	87.28	16.53	0.898	0.60(0.35)	0.58	171.0	810.00

LONGEST FLOWPATH FROM NODE 810.00 TO NODE 12603.00 = 3814.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)		(ACRES)	NODE
1	413.78	10.61	1.213	0.60(0.56)	0.94	1325.0	800.00
2	392.04	14.81	0.962	0.60(0.57)	0.95	1812.2	818.00
3	380.39	16.53	0.898	0.60(0.57)	0.96	2007.0	810.00
4	344.76	24.80	0.673	0.60(0.58)	0.97	2925.3	600.00
5	516.67	75.49	0.372	0.60(0.59)	0.99	9609.4	11831.00
6	627.97	100.39	0.327	0.60(0.59)	0.99	13294.5	11530.00
7	724.68	121.06	0.289	0.60(0.59)	0.99	17441.2	11000.00
8	823.04	138.31	0.274	0.60(0.59)	0.99	22388.9	11350.00
9	847.17	144.66	0.268	0.60(0.59)	0.99	24237.1	10850.00
10	818.34	152.60	0.261	0.60(0.60)	0.99	26121.3	10800.00
11	748.97	165.12	0.249	0.60(0.60)	0.99	28571.6	11910.00
12	691.47	176.52	0.239	0.60(0.60)	0.99	30275.1	12300.00
13	576.66	208.71	0.227	0.60(0.59)	0.99	35983.6	12410.00
14	549.13	216.81	0.225	0.60(0.59)	0.99	37415.8	10600.00
15	539.71	233.83	0.219	0.60(0.59)	0.99	40858.9	12201.00
16	543.92	241.12	0.217	0.60(0.59)	0.99	42069.5	12261.00
17	533.77	253.71	0.213	0.60(0.59)	0.99	43556.1	10410.00
18	523.60	265.71	0.209	0.60(0.59)	0.99	44658.0	12101.10
19	512.01	275.22	0.206	0.60(0.59)	0.99	45479.4	10700.00
20	500.61	292.76	0.201	0.60(0.59)	0.99	47036.1	10200.00
21	488.82	305.92	0.197	0.60(0.59)	0.99	47974.3	12010.00
22	453.78	334.32	0.188	0.60(0.59)	0.99	48648.1	10210.00
23	400.44	382.36	0.177	0.60(0.59)	0.99	49147.1	12000.00

24 368.15 451.11 0.170 0.60(0.59) 0.99 49731.9 10100.00
TOTAL AREA(ACRES) = 49731.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 847.17 Tc(MIN.) = 144.660
EFFECTIVE AREA(ACRES) = 24237.10 AREA-AVERAGED Fm(INCH/HR) = 0.59
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 49731.9
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.45 FEET.

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 144.66

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.268

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	1.30	0.60	1.000	-
USER-DEFINED	-	1.30	0.60	0.850	-
USER-DEFINED	-	1.40	0.60	0.100	-
USER-DEFINED	-	1.70	0.60	0.900	-
USER-DEFINED	-	12.40	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.911

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 18.30 SUBAREA RUNOFF(CFS) = 0.39

EFFECTIVE AREA(ACRES) = 24255.40 AREA-AVERAGED Fm(INCH/HR) = 0.59

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 49750.2 PEAK FLOW RATE(CFS) = 847.17

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 144.66

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.268

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	26.90	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 26.90 SUBAREA RUNOFF(CFS) = 0.00

EFFECTIVE AREA(ACRES) = 24282.30 AREA-AVERAGED Fm(INCH/HR) = 0.59

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 49777.1 PEAK FLOW RATE(CFS) = 847.17
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 144.66

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.268

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.50	0.60	1.000	-
USER-DEFINED	-	0.40	0.60	1.000	-
USER-DEFINED	-	0.40	0.60	1.000	-
USER-DEFINED	-	0.60	0.60	1.000	-
USER-DEFINED	-	0.70	0.60	0.850	-
USER-DEFINED	-	0.70	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.968

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 3.30 SUBAREA RUNOFF(CFS) = 0.03

EFFECTIVE AREA(ACRES) = 24285.60 AREA-AVERAGED Fm(INCH/HR) = 0.59

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 49780.4 PEAK FLOW RATE(CFS) = 847.17

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 144.66

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.268

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.00	0.60	1.000	-
USER-DEFINED	-	1.20	0.60	1.000	-
USER-DEFINED	-	1.70	0.60	0.900	-
USER-DEFINED	-	1.90	0.60	1.000	-
USER-DEFINED	-	2.10	0.60	0.900	-
USER-DEFINED	-	2.90	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.965

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 10.80 SUBAREA RUNOFF(CFS) = 0.09

EFFECTIVE AREA(ACRES) = 24296.40 AREA-AVERAGED Fm(INCH/HR) = 0.59

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 49791.2 PEAK FLOW RATE(CFS) = 847.17

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 144.66

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.268

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.60	0.60	1.000	-
USER-DEFINED	-	9.00	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 14.60 SUBAREA RUNOFF(CFS) = 0.00

EFFECTIVE AREA(ACRES) = 24311.00 AREA-AVERAGED Fm(INCH/HR) = 0.59

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 49805.8 PEAK FLOW RATE(CFS) = 847.17

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12603.00 TO NODE 12605.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 310.00 DOWNSTREAM(FEET) = 305.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 885.00 CHANNEL SLOPE = 0.0056

CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00

CHANNEL FLOW THRU SUBAREA(CFS) = 847.17

FLOW VELOCITY(FEET/SEC.) = 7.57 FLOW DEPTH(FEET) = 6.11

TRAVEL TIME(MIN.) = 1.95 Tc(MIN.) = 146.61

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.00 = 102443.45 FEET.

FLOW PROCESS FROM NODE 12605.00 TO NODE 12605.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 146.61

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.266

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.50	0.60	1.000	-
USER-DEFINED	-	0.70	0.60	1.000	-
USER-DEFINED	-	1.30	0.60	0.850	-
USER-DEFINED	-	1.30	0.60	0.900	-
USER-DEFINED	-	1.90	0.60	1.000	-
USER-DEFINED	-	2.10	0.60	0.850	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.918

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 7.80 SUBAREA RUNOFF(CFS) = 0.15

EFFECTIVE AREA(ACRES) = 24318.80 AREA-AVERAGED Fm(INCH/HR) = 0.59

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 49813.6 PEAK FLOW RATE(CFS) = 847.17

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12605.00 TO NODE 12605.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 146.61

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.266

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	3.20	0.60	1.000	-
USER-DEFINED	-	3.50	0.60	1.000	-
USER-DEFINED	-	6.10	0.60	0.850	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.929

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 12.80 SUBAREA RUNOFF(CFS) = 0.22

EFFECTIVE AREA(ACRES) = 24331.60 AREA-AVERAGED Fm(INCH/HR) = 0.59

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 49826.4 PEAK FLOW RATE(CFS) = 847.17

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12605.00 TO NODE 12606.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 305.00 DOWNSTREAM(FEET) = 286.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 2159.00 CHANNEL SLOPE = 0.0088

CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00

CHANNEL FLOW THRU SUBAREA(CFS) = 847.17

FLOW VELOCITY(FEET/SEC.) = 8.94 FLOW DEPTH(FEET) = 5.62

TRAVEL TIME(MIN.) = 4.02 Tc(MIN.) = 150.63

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104602.45 FEET.

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<

PEAK FLOWRATE TABLE FILE NAME: 4F02EVRL.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM	Q	Tc	Fp(Fm)	Ap	Ae	HEADWATER
--------	---	----	--------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(ACRES)	NODE
1	222.53	11.09	0.60 (0.46) 0.76	340.6	940.00
2	221.70	11.29	0.60 (0.46) 0.77	345.5	930.00
3	176.56	15.44	0.60 (0.48) 0.81	435.0	910.00
4	122.82	20.68	0.60 (0.51) 0.84	531.5	900.00
5	113.09	21.88	0.60 (0.51) 0.85	553.3	920.00
6	112.26	21.97	0.60 (0.51) 0.85	553.8	950.00
TOTAL AREA (ACRES) =		553.8			

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	815.71	16.64	0.894	0.60 (0.56) 0.94	1419.5	800.00	
2	660.88	21.17	0.752	0.60 (0.57) 0.95	1906.7	818.00	
3	604.15	23.04	0.711	0.60 (0.57) 0.96	2101.5	810.00	
4	344.76	32.28	0.574	0.60 (0.58) 0.97	3019.8	600.00	
5	516.67	82.26	0.360	0.60 (0.59) 0.99	9703.9	11831.00	
6	627.97	106.83	0.315	0.60 (0.59) 0.99	13389.0	11530.00	
7	724.68	127.27	0.283	0.60 (0.59) 0.99	17535.7	11000.00	
8	823.04	144.33	0.268	0.60 (0.59) 0.99	22483.4	11350.00	
9	847.17	150.63	0.262	0.60 (0.59) 0.99	24331.6	10850.00	
10	818.34	158.63	0.255	0.60 (0.60) 0.99	26215.8	10800.00	
11	748.97	171.29	0.244	0.60 (0.60) 0.99	28666.1	11910.00	
12	691.47	182.81	0.235	0.60 (0.60) 0.99	30369.6	12300.00	
13	576.66	215.28	0.225	0.60 (0.59) 0.99	36078.1	12410.00	
14	549.13	223.47	0.222	0.60 (0.59) 0.99	37510.3	10600.00	
15	539.71	240.52	0.217	0.60 (0.59) 0.99	40953.4	12201.00	
16	543.92	247.80	0.215	0.60 (0.59) 0.99	42164.0	12261.00	
17	533.77	260.42	0.211	0.60 (0.59) 0.99	43650.6	10410.00	
18	523.60	272.45	0.207	0.60 (0.59) 0.99	44752.5	12101.10	
19	512.01	282.00	0.204	0.60 (0.59) 0.99	45573.9	10700.00	
20	500.61	299.57	0.199	0.60 (0.59) 0.99	47130.6	10200.00	
21	488.82	312.78	0.195	0.60 (0.59) 0.99	48068.8	12010.00	
22	453.78	341.31	0.186	0.60 (0.59) 0.99	48742.6	10210.00	
23	400.44	389.57	0.177	0.60 (0.59) 0.99	49241.6	12000.00	
24	368.15	458.47	0.169	0.60 (0.59) 0.99	49826.4	10100.00	

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104602.45 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	222.53	11.09	1.184	0.60 (0.46) 0.76	340.6	940.00	
2	221.70	11.29	1.172	0.60 (0.46) 0.77	345.5	930.00	
3	176.56	15.44	0.936	0.60 (0.48) 0.81	435.0	910.00	
4	122.82	20.68	0.762	0.60 (0.51) 0.84	531.5	900.00	
5	113.09	21.88	0.736	0.60 (0.51) 0.85	553.3	920.00	
6	112.26	21.97	0.735	0.60 (0.51) 0.85	553.8	950.00	

LONGEST FLOWPATH FROM NODE 920.00 TO NODE 12606.00 = 6933.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
---------------	---------	-----------	---------------------	------------------	----	------------	----------------

1	1038.23	11.09	1.184	0.60 (0.54) 0.89	1286.5	940.00	
2	1037.41	11.29	1.172	0.60 (0.54) 0.90	1308.6	930.00	
3	992.27	15.44	0.936	0.60 (0.54) 0.91	1752.6	910.00	
4	980.02	16.64	0.894	0.60 (0.55) 0.91	1876.5	800.00	
5	800.44	20.68	0.762	0.60 (0.56) 0.93	2385.5	900.00	
6	779.73	21.17	0.752	0.60 (0.56) 0.93	2447.1	818.00	
7	752.38	21.88	0.736	0.60 (0.56) 0.93	2534.2	920.00	
8	749.05	21.97	0.735	0.60 (0.56) 0.93	2543.2	950.00	
9	704.83	23.04	0.711	0.60 (0.56) 0.94	2655.3	810.00	
10	387.98	32.28	0.574	0.60 (0.57) 0.95	3573.6	600.00	
11	543.75	82.26	0.360	0.60 (0.59) 0.98	10257.7	11831.00	
12	651.64	106.83	0.315	0.60 (0.59) 0.98	13942.8	11530.00	
13	746.01	127.27	0.283	0.60 (0.59) 0.99	18089.5	11000.00	
14	843.22	144.33	0.268	0.60 (0.59) 0.99	23037.2	11350.00	
15	866.92	150.63	0.262	0.60 (0.59) 0.99	24885.4	10850.00	
16	837.55	158.63	0.255	0.60 (0.59) 0.99	26769.6	10800.00	
17	767.32	171.29	0.244	0.60 (0.59) 0.99	29219.9	11910.00	
18	709.16	182.81	0.235	0.60 (0.59) 0.99	30923.4	12300.00	
19	593.59	215.28	0.225	0.60 (0.59) 0.99	36631.9	12410.00	
20	565.87	223.47	0.222	0.60 (0.59) 0.99	38064.1	10600.00	
21	556.05	240.52	0.217	0.60 (0.59) 0.99	41507.2	12201.00	
22	560.09	247.80	0.215	0.60 (0.59) 0.99	42717.8	12261.00	
23	549.65	260.42	0.211	0.60 (0.59) 0.99	44204.4	10410.00	
24	539.19	272.45	0.207	0.60 (0.59) 0.99	45306.3	12101.10	
25	527.38	282.00	0.204	0.60 (0.59) 0.99	46127.7	10700.00	
26	515.57	299.57	0.199	0.60 (0.59) 0.99	47684.4	10200.00	
27	503.47	312.78	0.195	0.60 (0.59) 0.99	48622.6	12010.00	
28	467.76	341.31	0.186	0.60 (0.59) 0.99	49296.4	10210.00	
29	413.73	389.57	0.177	0.60 (0.59) 0.99	49795.4	12000.00	
30	380.84	458.47	0.169	0.60 (0.59) 0.99	50380.2	10100.00	
TOTAL AREA (ACRES) =		50380.2					

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 1038.23 Tc (MIN.) = 11.086
EFFECTIVE AREA (ACRES) = 1286.54 AREA-AVERAGED Fm (INCH/HR) = 0.54
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 50380.2
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104602.45 FEET.

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 11.09

* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 1.184

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.30	0.60	1.000	-
USER-DEFINED	-	0.30	0.60	1.000	-
USER-DEFINED	-	0.40	0.60	0.850	-
USER-DEFINED	-	0.60	0.60	1.000	-
USER-DEFINED	-	1.10	0.60	0.100	-
USER-DEFINED	-	0.80	0.60	0.850	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.666

SUBAREA AREA (ACRES) = 3.50 SUBAREA RUNOFF (CFS) = 2.47

EFFECTIVE AREA (ACRES) = 1290.04 AREA-AVERAGED Fm (INCH/HR) = 0.54
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.89
 TOTAL AREA (ACRES) = 50383.7 PEAK FLOW RATE (CFS) = 1038.23
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 11.09

* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 1.184

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.80	0.60	1.000	-
USER-DEFINED	-	0.90	0.60	1.000	-
USER-DEFINED	-	1.50	0.60	1.000	-
USER-DEFINED	-	1.60	0.60	1.000	-
USER-DEFINED	-	1.80	0.60	1.000	-
USER-DEFINED	-	1.90	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 8.50 SUBAREA RUNOFF (CFS) = 4.47

EFFECTIVE AREA (ACRES) = 1298.54 AREA-AVERAGED Fm (INCH/HR) = 0.54

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.89

TOTAL AREA (ACRES) = 50392.2 PEAK FLOW RATE (CFS) = 1038.23

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 11.09

* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 1.184

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	3.30	0.60	1.000	-
USER-DEFINED	-	3.70	0.60	1.000	-
USER-DEFINED	-	3.90	0.60	1.000	-
USER-DEFINED	-	5.90	0.60	1.000	-
USER-DEFINED	-	9.10	0.60	1.000	-
USER-DEFINED	-	20.60	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 46.50 SUBAREA RUNOFF (CFS) = 24.46

EFFECTIVE AREA (ACRES) = 1345.04 AREA-AVERAGED Fm (INCH/HR) = 0.54

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.90

TOTAL AREA (ACRES) = 50438.7 PEAK FLOW RATE (CFS) = 1038.23

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 50438.7 TC (MIN.) = 11.09

EFFECTIVE AREA (ACRES) = 1345.04 AREA-AVERAGED Fm (INCH/HR) = 0.54

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.898

PEAK FLOW RATE (CFS) = 1038.23

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1038.23	11.09	1.184	0.60 (0.54)	0.90	1345.0	940.00
2	1037.41	11.29	1.172	0.60 (0.54)	0.90	1367.1	930.00
3	992.27	15.44	0.936	0.60 (0.55)	0.91	1811.1	910.00
4	980.02	16.64	0.894	0.60 (0.55)	0.91	1935.0	800.00
5	800.44	20.68	0.762	0.60 (0.56)	0.93	2444.0	900.00
6	779.73	21.17	0.752	0.60 (0.56)	0.93	2505.6	818.00
7	752.38	21.88	0.736	0.60 (0.56)	0.93	2592.7	920.00
8	749.05	21.97	0.735	0.60 (0.56)	0.93	2601.7	950.00
9	704.83	23.04	0.711	0.60 (0.56)	0.94	2713.8	810.00
10	387.98	32.28	0.574	0.60 (0.57)	0.95	3632.1	600.00
11	543.75	82.26	0.360	0.60 (0.59)	0.98	10316.2	11831.00
12	651.64	106.83	0.315	0.60 (0.59)	0.98	14001.3	11530.00
13	746.01	127.27	0.283	0.60 (0.59)	0.99	18148.0	11000.00
14	843.22	144.33	0.268	0.60 (0.59)	0.99	23095.8	11350.00
15	866.92	150.63	0.262	0.60 (0.59)	0.99	24943.9	10850.00
16	837.55	158.63	0.255	0.60 (0.59)	0.99	26828.1	10800.00
17	767.32	171.29	0.244	0.60 (0.59)	0.99	29278.4	11910.00
18	709.16	182.81	0.235	0.60 (0.59)	0.99	30981.9	12300.00
19	593.59	215.28	0.225	0.60 (0.59)	0.99	36690.4	12410.00
20	565.87	223.47	0.222	0.60 (0.59)	0.99	38122.6	10600.00
21	556.05	240.52	0.217	0.60 (0.59)	0.99	41565.7	12201.00
22	560.09	247.80	0.215	0.60 (0.59)	0.99	42776.3	12261.00
23	549.65	260.42	0.211	0.60 (0.59)	0.99	44262.9	10410.00
24	539.19	272.45	0.207	0.60 (0.59)	0.99	45364.8	12101.10
25	527.38	282.00	0.204	0.60 (0.59)	0.99	46186.2	10700.00
26	515.57	299.57	0.199	0.60 (0.59)	0.99	47742.9	10200.00
27	503.47	312.78	0.195	0.60 (0.59)	0.99	48681.1	12010.00
28	467.76	341.31	0.186	0.60 (0.59)	0.99	49354.9	10210.00
29	413.73	389.57	0.177	0.60 (0.59)	0.99	49853.9	12000.00
30	380.84	458.47	0.169	0.60 (0.59)	0.99	50438.7	10100.00

END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 127 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 2-YR EV FEB 2023 ROKAMOTO *

FILE NAME: RU02EV27.DAT
TIME/DATE OF STUDY: 13:35 02/09/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 2.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 1.861
- 2) 10.00; 1.241
- 3) 15.00; 0.946
- 4) 20.00; 0.775
- 5) 25.00; 0.667
- 6) 30.00; 0.592
- 7) 40.00; 0.510
- 8) 50.00; 0.453
- 9) 60.00; 0.399
- 10) 90.00; 0.345
- 11) 120.00; 0.290
- 12) 180.00; 0.236
- 13) 360.00; 0.180
- 14) 1200.00; 0.083

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	(FT)	(FT)	SIDE / SIDE/ WAY	(FT)	(FT)	(FT)	(FT)	(n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU02EV26.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1038.23	11.09	0.60 (0.54)	0.90	1345.0	940.00
2	800.44	20.68	0.60 (0.56)	0.93	2444.0	900.00
3	387.98	32.28	0.60 (0.57)	0.95	3632.1	600.00
4	543.75	82.26	0.60 (0.59)	0.98	10316.2	11831.00
5	651.64	106.83	0.60 (0.59)	0.98	14001.3	11530.00
6	746.01	127.27	0.60 (0.59)	0.99	18148.0	11000.00
7	866.92	150.63	0.60 (0.59)	0.99	24943.9	10850.00
8	767.32	171.29	0.60 (0.59)	0.99	29278.4	11910.00
9	709.16	182.81	0.60 (0.59)	0.99	30981.9	12300.00
10	593.59	215.28	0.60 (0.59)	0.99	36690.4	12410.00
11	565.87	223.47	0.60 (0.59)	0.99	38122.6	10600.00
12	560.09	247.80	0.60 (0.59)	0.99	42776.3	12261.00
13	549.65	260.42	0.60 (0.59)	0.99	44262.9	10210.00
14	539.19	272.45	0.60 (0.59)	0.99	45364.8	12101.10
15	527.38	282.00	0.60 (0.59)	0.99	46186.2	10700.00
16	515.57	299.57	0.60 (0.59)	0.99	47742.9	10200.00
17	503.47	312.78	0.60 (0.59)	0.99	48681.1	12010.00
18	467.76	341.31	0.60 (0.59)	0.99	49354.9	10210.00
19	413.73	389.57	0.60 (0.59)	0.99	49853.9	12000.00
20	380.84	458.47	0.60 (0.59)	0.99	50438.7	10100.00
TOTAL AREA (ACRES) =						50438.7

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1038.23	11.09	0.60 (0.54)	0.90	1345.0	940.00
2	800.44	20.68	0.60 (0.56)	0.93	2444.0	900.00
3	387.98	32.28	0.60 (0.57)	0.95	3632.1	600.00
4	543.75	82.26	0.60 (0.59)	0.98	10316.2	11831.00
5	651.64	106.83	0.60 (0.59)	0.98	14001.3	11530.00
6	746.01	127.27	0.60 (0.59)	0.99	18148.0	11000.00
7	866.92	150.63	0.60 (0.59)	0.99	24943.9	10850.00
8	767.32	171.29	0.60 (0.59)	0.99	29278.4	11910.00
9	709.16	182.81	0.60 (0.59)	0.99	30981.9	12300.00
10	593.59	215.28	0.60 (0.59)	0.99	36690.4	12410.00
11	565.87	223.47	0.60 (0.59)	0.99	38122.6	10600.00
12	560.09	247.80	0.60 (0.59)	0.99	42776.3	12261.00
13	549.65	260.42	0.60 (0.59)	0.99	44262.9	10410.00

14 539.19 272.45 0.60(0.59) 0.99 45364.8 12101.10
 15 527.38 282.00 0.60(0.59) 0.99 46186.2 10700.00
 16 515.57 299.57 0.60(0.59) 0.99 47742.9 10200.00
 17 503.47 312.78 0.60(0.59) 0.99 48681.1 12010.00
 18 467.76 341.31 0.60(0.59) 0.99 49354.9 10210.00
 19 413.73 389.57 0.60(0.59) 0.99 49853.9 12000.00
 20 380.84 458.47 0.60(0.59) 0.99 50438.7 10100.00
 TOTAL AREA (ACRES) = 50438.7

 FLOW PROCESS FROM NODE 12606.00 TO NODE 12701.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 286.00 DOWNSTREAM(FEET) = 276.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1260.19 CHANNEL SLOPE = 0.0079
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 1.040

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.70	0.60	0.500	-
USER-DEFINED	-	0.90	0.60	0.850	-
USER-DEFINED	-	3.40	0.60	0.100	-
USER-DEFINED	-	3.60	0.60	1.000	-
USER-DEFINED	-	10.10	0.60	0.850	-
USER-DEFINED	-	17.40	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.860
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 1046.76
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 9.06
 AVERAGE FLOW DEPTH (FEET) = 6.21 TRAVEL TIME (MIN.) = 2.32
 Tc (MIN.) = 13.40
 SUBAREA AREA (ACRES) = 36.10 SUBAREA RUNOFF (CFS) = 17.04
 EFFECTIVE AREA (ACRES) = 1381.14 AREA-AVERAGED Fm (INCH/HR) = 0.54
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.90
 TOTAL AREA (ACRES) = 50474.8 PEAK FLOW RATE (CFS) = 1038.23
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 6.18 FLOW VELOCITY (FEET/SEC.) = 9.05
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12701.00 = 105862.63 FEET.

 FLOW PROCESS FROM NODE 12701.00 TO NODE 12720.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 276.00 DOWNSTREAM(FEET) = 275.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 147.65 CHANNEL SLOPE = 0.0068
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00
 CHANNEL FLOW THRU SUBAREA (CFS) = 1038.23
 FLOW VELOCITY (FEET/SEC.) = 8.52 FLOW DEPTH (FEET) = 6.37
 TRAVEL TIME (MIN.) = 0.29 Tc (MIN.) = 13.69

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.00 = 106010.28 FEET.

 FLOW PROCESS FROM NODE 12701.00 TO NODE 12720.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

=====

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
 TIME OF CONCENTRATION (MIN.) = 13.69
 RAINFALL INTENSITY (INCH/HR) = 1.02
 AREA-AVERAGED Fm (INCH/HR) = 0.54
 AREA-AVERAGED Fp (INCH/HR) = 0.60
 AREA-AVERAGED Ap = 0.90
 EFFECTIVE STREAM AREA (ACRES) = 1381.14
 TOTAL STREAM AREA (ACRES) = 50474.79
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 1038.23

 FLOW PROCESS FROM NODE 12710.00 TO NODE 12711.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH (FEET) = 943.56
 ELEVATION DATA: UPSTREAM (FEET) = 940.78 DOWNSTREAM (FEET) = 657.79

Tc = K * [(LENGTH ** 3.00) / (ELEVATION CHANGE)] ** 0.20
 SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 13.910
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 1.010

SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER						
"GRASS"	-	6.56	0.60	1.000	65	13.91

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA RUNOFF (CFS) = 2.42
 TOTAL AREA (ACRES) = 6.56 PEAK FLOW RATE (CFS) = 2.42

 FLOW PROCESS FROM NODE 12711.00 TO NODE 12712.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 657.79 DOWNSTREAM (FEET) = 585.63
 CHANNEL LENGTH THRU SUBAREA (FEET) = 766.00 CHANNEL SLOPE = 0.0942
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.914

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	26.94	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 6.28

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.33
AVERAGE FLOW DEPTH (FEET) = 0.58 TRAVEL TIME (MIN.) = 2.02
Tc (MIN.) = 15.93
SUBAREA AREA (ACRES) = 26.94 SUBAREA RUNOFF (CFS) = 7.62
EFFECTIVE AREA (ACRES) = 33.50 AREA-AVERAGED Fm (INCH/HR) = 0.60
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 33.5 PEAK FLOW RATE (CFS) = 9.48

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.67 FLOW VELOCITY (FEET/SEC.) = 7.07
LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12712.00 = 1709.56 FEET.

FLOW PROCESS FROM NODE 12712.00 TO NODE 12713.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 585.63 DOWNSTREAM (FEET) = 463.75
CHANNEL LENGTH THRU SUBAREA (FEET) = 1025.79 CHANNEL SLOPE = 0.1188
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.842
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 14.73 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 11.09
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.08
AVERAGE FLOW DEPTH (FEET) = 0.68 TRAVEL TIME (MIN.) = 2.11
Tc (MIN.) = 18.04
SUBAREA AREA (ACRES) = 14.73 SUBAREA RUNOFF (CFS) = 3.21
EFFECTIVE AREA (ACRES) = 48.23 AREA-AVERAGED Fm (INCH/HR) = 0.60
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 48.2 PEAK FLOW RATE (CFS) = 10.51

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.67 FLOW VELOCITY (FEET/SEC.) = 7.88
LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12713.00 = 2735.35 FEET.

FLOW PROCESS FROM NODE 12713.00 TO NODE 12714.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 463.75 DOWNSTREAM (FEET) = 360.30
CHANNEL LENGTH THRU SUBAREA (FEET) = 1148.54 CHANNEL SLOPE = 0.0901
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.767
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 105.64 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 18.55
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.23
AVERAGE FLOW DEPTH (FEET) = 0.87 TRAVEL TIME (MIN.) = 2.33
Tc (MIN.) = 20.37
SUBAREA AREA (ACRES) = 105.64 SUBAREA RUNOFF (CFS) = 15.90
EFFECTIVE AREA (ACRES) = 153.87 AREA-AVERAGED Fm (INCH/HR) = 0.60
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 153.9 PEAK FLOW RATE (CFS) = 23.15

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.94 FLOW VELOCITY (FEET/SEC.) = 8.68
LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12714.00 = 3883.89 FEET.

FLOW PROCESS FROM NODE 12714.00 TO NODE 12720.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 360.30 DOWNSTREAM (FEET) = 275.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 1314.99 CHANNEL SLOPE = 0.0649
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 10.00
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.709
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 127.13 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 29.48
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.18
AVERAGE FLOW DEPTH (FEET) = 1.10 TRAVEL TIME (MIN.) = 2.68
Tc (MIN.) = 23.05
SUBAREA AREA (ACRES) = 127.13 SUBAREA RUNOFF (CFS) = 12.51
EFFECTIVE AREA (ACRES) = 281.00 AREA-AVERAGED Fm (INCH/HR) = 0.60
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 281.0 PEAK FLOW RATE (CFS) = 27.65

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 1.07 FLOW VELOCITY (FEET/SEC.) = 8.04
LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12720.00 = 5198.88 FEET.

FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION (MIN.) = 23.05
RAINFALL INTENSITY (INCH/HR) = 0.71
AREA-AVERAGED Fm (INCH/HR) = 0.60
AREA-AVERAGED Fp (INCH/HR) = 0.60
AREA-AVERAGED Ap = 1.00
EFFECTIVE STREAM AREA (ACRES) = 281.00

TOTAL STREAM AREA(ACRES) = 281.00
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 27.65

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1038.23	13.69	1.023	0.60 (0.54)	0.90	1381.1	940.00
1	800.44	23.47	0.700	0.60 (0.56)	0.93	2480.1	900.00
1	387.98	35.62	0.546	0.60 (0.57)	0.95	3668.2	600.00
1	543.75	85.33	0.353	0.60 (0.59)	0.98	10352.3	11831.00
1	651.64	109.77	0.309	0.60 (0.59)	0.98	14037.4	11530.00
1	746.01	130.10	0.281	0.60 (0.59)	0.99	18184.1	11000.00
1	866.92	153.36	0.260	0.60 (0.59)	0.99	24980.0	10850.00
1	767.32	174.10	0.241	0.60 (0.59)	0.99	29314.5	11910.00
1	709.16	185.68	0.234	0.60 (0.59)	0.99	31018.0	12300.00
1	593.59	218.29	0.224	0.60 (0.59)	0.99	36726.5	12410.00
1	565.87	226.50	0.222	0.60 (0.59)	0.99	38158.7	10600.00
1	560.09	250.85	0.214	0.60 (0.59)	0.99	42812.4	12261.00
1	549.65	263.47	0.210	0.60 (0.59)	0.99	44299.0	10410.00
1	539.19	275.53	0.206	0.60 (0.59)	0.99	45400.9	12101.10
1	527.38	285.09	0.203	0.60 (0.59)	0.99	46222.3	10700.00
1	515.57	302.68	0.198	0.60 (0.59)	0.99	47779.0	10200.00
1	503.47	315.91	0.194	0.60 (0.59)	0.99	48717.2	12010.00
1	467.76	344.50	0.185	0.60 (0.59)	0.99	49391.0	10210.00
1	413.73	392.85	0.176	0.60 (0.59)	0.99	49890.0	12000.00
1	380.84	461.82	0.168	0.60 (0.59)	0.99	50474.8	10100.00
2	27.65	23.05	0.709	0.60 (0.60)	1.00	281.0	12710.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1065.89	13.69	1.023	0.60 (0.54)	0.91	1548.1	940.00
2	838.34	23.05	0.709	0.60 (0.56)	0.93	2713.7	12710.00
3	825.79	23.47	0.700	0.60 (0.56)	0.94	2761.1	900.00
4	387.97	35.62	0.546	0.60 (0.57)	0.95	3949.2	600.00
5	543.75	85.33	0.353	0.60 (0.59)	0.98	10633.3	11831.00
6	651.64	109.77	0.309	0.60 (0.59)	0.98	14318.4	11530.00
7	746.01	130.10	0.281	0.60 (0.59)	0.99	18465.1	11000.00
8	866.92	153.36	0.260	0.60 (0.59)	0.99	25261.0	10850.00
9	767.32	174.10	0.241	0.60 (0.59)	0.99	29595.5	11910.00
10	709.16	185.68	0.234	0.60 (0.59)	0.99	31299.0	12300.00
11	593.59	218.29	0.224	0.60 (0.59)	0.99	37007.5	12410.00
12	565.87	226.50	0.222	0.60 (0.59)	0.99	38439.7	10600.00
13	560.09	250.85	0.214	0.60 (0.59)	0.99	43093.4	12261.00
14	549.65	263.47	0.210	0.60 (0.59)	0.99	44580.0	10410.00
15	539.19	275.53	0.206	0.60 (0.59)	0.99	45681.9	12101.10
16	527.38	285.09	0.203	0.60 (0.59)	0.99	46503.3	10700.00
17	515.57	302.68	0.198	0.60 (0.59)	0.99	48060.0	10200.00
18	503.47	315.91	0.194	0.60 (0.59)	0.99	48998.2	12010.00
19	467.76	344.50	0.185	0.60 (0.59)	0.99	49672.0	10210.00
20	413.73	392.85	0.176	0.60 (0.59)	0.99	50171.0	12000.00
21	380.84	461.82	0.168	0.60 (0.59)	0.99	50755.8	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 1065.89 Tc(MIN.) = 13.69

EFFECTIVE AREA(ACRES) = 1548.10 AREA-AVERAGED Fm(INCH/HR) = 0.54
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.91
 TOTAL AREA(ACRES) = 50755.8
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.00 = 106010.28 FEET.

 FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.50 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<
 =====

ELEVATION DATA: UPSTREAM(FEET) = 275.00 DOWNSTREAM(FEET) = 258.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2669.21 CHANNEL SLOPE = 0.0064
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.809

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	0.30	0.60	1.000	-
USER-DEFINED	-	0.30	0.60	0.100	-
USER-DEFINED	-	0.50	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.841
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1066.12
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.38
 AVERAGE FLOW DEPTH(FEET) = 6.51 TRAVEL TIME(MIN.) = 5.31
 Tc(MIN.) = 19.00

SUBAREA AREA(ACRES) = 1.70 SUBAREA RUNOFF(CFS) = 0.47
 EFFECTIVE AREA(ACRES) = 1549.80 AREA-AVERAGED Fm(INCH/HR) = 0.54
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.91
 TOTAL AREA(ACRES) = 50757.5 PEAK FLOW RATE(CFS) = 1065.89
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 6.51 FLOW VELOCITY(FEET/SEC.) = 8.38
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108679.49 FEET.

 FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
 =====

MAINLINE Tc(MIN.) = 19.00
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.809
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.50	0.60	0.850	-
USER-DEFINED	-	0.70	0.60	1.000	-
USER-DEFINED	-	1.50	0.60	1.000	-
USER-DEFINED	-	1.40	0.60	0.100	-
USER-DEFINED	-	2.30	0.60	0.100	-
USER-DEFINED	-	9.30	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.783
SUBAREA AREA(ACRES) = 15.70 SUBAREA RUNOFF(CFS) = 4.80
EFFECTIVE AREA(ACRES) = 1565.50 AREA-AVERAGED Fm(INCH/HR) = 0.54
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.91
TOTAL AREA(ACRES) = 50773.2 PEAK FLOW RATE(CFS) = 1065.89
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 19.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.809
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 11.20 0.60 1.000 -
USER-DEFINED - 11.40 0.60 1.000 -
USER-DEFINED - 11.80 0.60 1.000 -
USER-DEFINED - 27.70 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 62.10 SUBAREA RUNOFF(CFS) = 11.70
EFFECTIVE AREA(ACRES) = 1627.60 AREA-AVERAGED Fm(INCH/HR) = 0.55
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.91
TOTAL AREA(ACRES) = 50835.3 PEAK FLOW RATE(CFS) = 1065.89
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 3C02EVRL.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:
STREAM Q Tc Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (ACRES) NODE
1 517.52 15.30 0.60(0.25) 0.41 835.1 410.00
2 517.31 17.25 0.60(0.25) 0.41 924.4 420.00
3 495.30 21.61 0.60(0.25) 0.41 1109.7 310.00
4 476.56 23.62 0.60(0.25) 0.41 1175.8 400.00
5 444.40 26.38 0.60(0.25) 0.41 1236.8 300.00
6 438.89 26.86 0.60(0.25) 0.41 1246.0 430.00
7 437.70 26.98 0.60(0.25) 0.41 1248.1 320.00
8 325.32 43.22 0.60(0.26) 0.43 1292.3 390.00
TOTAL AREA(ACRES) = 1292.3

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 1065.89 19.00 0.809 0.60(0.55) 0.91 1627.6 940.00

2 838.34 28.68 0.612 0.60(0.56) 0.94 2793.2 12710.00
3 825.79 29.12 0.605 0.60(0.56) 0.94 2840.6 900.00
4 387.97 42.46 0.496 0.60(0.57) 0.95 4028.7 600.00
5 543.75 91.60 0.342 0.60(0.59) 0.98 10712.8 11831.00
6 651.64 115.77 0.298 0.60(0.59) 0.98 14397.9 11530.00
7 746.01 135.90 0.276 0.60(0.59) 0.99 18544.6 11000.00
8 866.92 158.95 0.255 0.60(0.59) 0.99 25340.5 10850.00
9 767.32 179.87 0.236 0.60(0.59) 0.99 29675.0 11910.00
10 709.16 191.56 0.232 0.60(0.59) 0.99 31378.5 12300.00
11 593.59 224.43 0.222 0.60(0.59) 0.99 37087.0 12410.00
12 565.87 232.71 0.220 0.60(0.59) 0.99 38519.2 10600.00
13 560.09 257.08 0.212 0.60(0.59) 0.99 43172.9 12261.00
14 549.65 269.73 0.208 0.60(0.59) 0.99 44659.5 10410.00
15 539.19 281.82 0.204 0.60(0.59) 0.99 45761.4 12101.10
16 527.38 291.42 0.201 0.60(0.59) 0.99 46582.8 10700.00
17 515.57 309.04 0.196 0.60(0.59) 0.99 48139.5 10200.00
18 503.47 322.32 0.192 0.60(0.59) 0.99 49077.7 12010.00
19 467.76 351.02 0.183 0.60(0.59) 0.99 49751.5 10210.00
20 413.73 399.57 0.175 0.60(0.59) 0.99 50250.5 12000.00
21 380.84 468.69 0.167 0.60(0.59) 0.99 50835.3 10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108679.49 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 517.52 15.30 0.936 0.60(0.25) 0.41 835.1 410.00
2 517.31 17.25 0.869 0.60(0.25) 0.41 924.4 420.00
3 495.30 21.61 0.740 0.60(0.25) 0.41 1109.7 310.00
4 476.56 23.62 0.697 0.60(0.25) 0.41 1175.8 400.00
5 444.40 26.38 0.646 0.60(0.25) 0.41 1236.8 300.00
6 438.89 26.86 0.639 0.60(0.25) 0.41 1246.0 430.00
7 437.70 26.98 0.637 0.60(0.25) 0.41 1248.1 320.00
8 325.32 43.22 0.492 0.60(0.26) 0.43 1292.3 390.00
LONGEST FLOWPATH FROM NODE 390.00 TO NODE 12720.50 = 13248.00 FEET.

** PEAK FLOW RATE TABLE **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 1583.41 15.30 0.936 0.60(0.43) 0.72 2145.9 410.00
2 1583.20 17.25 0.869 0.60(0.43) 0.72 2402.5 420.00
3 1574.38 19.00 0.809 0.60(0.43) 0.72 2626.3 940.00
4 1499.78 21.61 0.740 0.60(0.44) 0.73 3051.9 310.00
5 1433.85 23.62 0.697 0.60(0.45) 0.74 3359.7 400.00
6 1336.67 26.38 0.646 0.60(0.46) 0.76 3753.9 300.00
7 1319.93 26.86 0.639 0.60(0.46) 0.76 3820.5 430.00
8 1316.06 26.98 0.637 0.60(0.46) 0.76 3836.3 320.00
9 1264.27 28.68 0.612 0.60(0.46) 0.77 4046.0 12710.00
10 1248.64 29.12 0.605 0.60(0.47) 0.78 4094.5 900.00
11 718.55 42.46 0.496 0.60(0.50) 0.83 5318.9 600.00
12 715.70 43.22 0.492 0.60(0.50) 0.83 5424.2 390.00
13 770.08 91.60 0.342 0.60(0.55) 0.92 12005.1 11831.00
14 848.66 115.77 0.298 0.60(0.56) 0.94 15690.2 11530.00
15 928.42 135.90 0.276 0.60(0.57) 0.95 19836.9 11000.00
16 1035.61 158.95 0.255 0.60(0.58) 0.96 26632.8 10850.00
17 923.55 179.87 0.236 0.60(0.58) 0.97 30967.3 11910.00
18 862.93 191.56 0.232 0.60(0.58) 0.97 32670.8 12300.00
19 740.60 224.43 0.222 0.60(0.58) 0.97 38379.3 12410.00
20 711.17 232.71 0.220 0.60(0.58) 0.97 39811.5 10600.00

21 700.38 257.08 0.212 0.60(0.58) 0.97 44465.2 12261.00
 22 687.33 269.73 0.208 0.60(0.58) 0.97 45951.8 10410.00
 23 674.39 281.82 0.204 0.60(0.58) 0.97 47053.7 12101.10
 24 660.60 291.42 0.201 0.60(0.58) 0.97 47875.1 10700.00
 25 645.15 309.04 0.196 0.60(0.58) 0.97 49431.8 10200.00
 26 630.33 322.32 0.192 0.60(0.58) 0.97 50370.0 12010.00
 27 588.71 351.02 0.183 0.60(0.58) 0.97 51043.8 10210.00
 28 529.80 399.57 0.175 0.60(0.58) 0.98 51542.8 12000.00
 29 491.64 468.69 0.167 0.60(0.59) 0.98 52127.6 10100.00
 TOTAL AREA (ACRES) = 52127.6

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 1583.41 Tc(MIN.) = 15.302
 EFFECTIVE AREA (ACRES) = 2145.94 AREA-AVERAGED Fm (INCH/HR) = 0.43
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.97
 TOTAL AREA (ACRES) = 52127.6
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108679.49 FEET.

 FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<<

 FLOW PROCESS FROM NODE 12720.50 TO NODE 12722.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 258.00 DOWNSTREAM (FEET) = 255.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1269.00 CHANNEL SLOPE = 0.0024
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00

* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.822

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.10	0.60	0.850	-
USER-DEFINED	-	0.10	0.60	1.000	-
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	0.30	0.60	1.000	-
USER-DEFINED	-	0.30	0.60	1.000	-
USER-DEFINED	-	0.40	0.60	0.100	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.732

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 1583.65

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.38

AVERAGE FLOW DEPTH (FEET) = 9.10 TRAVEL TIME (MIN.) = 3.32

Tc (MIN.) = 18.62

SUBAREA AREA (ACRES) = 1.40 SUBAREA RUNOFF (CFS) = 0.48

EFFECTIVE AREA (ACRES) = 2147.34 AREA-AVERAGED Fm (INCH/HR) = 0.43

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.72

TOTAL AREA (ACRES) = 52129.0 PEAK FLOW RATE (CFS) = 1583.41

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 9.09 FLOW VELOCITY (FEET/SEC.) = 6.39

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12722.00 = 109948.49 FEET.

 FLOW PROCESS FROM NODE 12722.00 TO NODE 12722.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<

MAINLINE Tc (MIN.) = 18.62

* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.822

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.50	0.60	0.100	-
USER-DEFINED	-	0.60	0.60	1.000	-
USER-DEFINED	-	0.60	0.60	1.000	-
USER-DEFINED	-	0.60	0.60	0.100	-
USER-DEFINED	-	0.90	0.60	1.000	-
USER-DEFINED	-	1.00	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.764

SUBAREA AREA (ACRES) = 4.20 SUBAREA RUNOFF (CFS) = 1.38

EFFECTIVE AREA (ACRES) = 2151.54 AREA-AVERAGED Fm (INCH/HR) = 0.43

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.72

TOTAL AREA (ACRES) = 52133.2 PEAK FLOW RATE (CFS) = 1583.41

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12722.00 TO NODE 12722.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<

MAINLINE Tc (MIN.) = 18.62

* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.822

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.30	0.60	1.000	-
USER-DEFINED	-	3.20	0.60	1.000	-
USER-DEFINED	-	3.70	0.60	1.000	-
USER-DEFINED	-	12.00	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 20.20 SUBAREA RUNOFF (CFS) = 4.04

EFFECTIVE AREA (ACRES) = 2171.74 AREA-AVERAGED Fm (INCH/HR) = 0.43

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.72

TOTAL AREA (ACRES) = 52153.4 PEAK FLOW RATE (CFS) = 1583.41

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12722.00 TO NODE 12740.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 255.00 DOWNSTREAM (FEET) = 252.10
 CHANNEL LENGTH THRU SUBAREA (FEET) = 624.00 CHANNEL SLOPE = 0.0046
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00

* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.779
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.10	0.60	1.000	-
USER-DEFINED	-	0.50	0.60	0.850	-
USER-DEFINED	-	0.50	0.60	1.000	-
USER-DEFINED	-	0.80	0.60	1.000	-
USER-DEFINED	-	1.20	0.60	1.000	-
USER-DEFINED	-	1.50	0.60	0.100	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.690
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 1584.16
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.22
AVERAGE FLOW DEPTH (FEET) = 8.01 TRAVEL TIME (MIN.) = 1.26
Tc (MIN.) = 19.88
SUBAREA AREA (ACRES) = 4.60 SUBAREA RUNOFF (CFS) = 1.51
EFFECTIVE AREA (ACRES) = 2176.34 AREA-AVERAGED Fm (INCH/HR) = 0.43
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.72
TOTAL AREA (ACRES) = 52158.0 PEAK FLOW RATE (CFS) = 1583.41
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 8.01 FLOW VELOCITY (FEET/SEC.) = 8.22
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12740.00 = 110572.49 FEET.

FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 19.88
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.779
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	2.50	0.60	0.100	-
USER-DEFINED	-	2.60	0.60	1.000	-
USER-DEFINED	-	2.80	0.60	1.000	-
USER-DEFINED	-	5.40	0.60	1.000	-
USER-DEFINED	-	6.20	0.60	1.000	-
USER-DEFINED	-	6.50	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.913
SUBAREA AREA (ACRES) = 26.00 SUBAREA RUNOFF (CFS) = 5.41
EFFECTIVE AREA (ACRES) = 2202.34 AREA-AVERAGED Fm (INCH/HR) = 0.43
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.72
TOTAL AREA (ACRES) = 52184.0 PEAK FLOW RATE (CFS) = 1583.41
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 19.88
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.779
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	6.70	0.60	1.000	-
USER-DEFINED	-	12.00	0.60	1.000	-
USER-DEFINED	-	20.30	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 39.00 SUBAREA RUNOFF (CFS) = 6.29
EFFECTIVE AREA (ACRES) = 2241.34 AREA-AVERAGED Fm (INCH/HR) = 0.44
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.73
TOTAL AREA (ACRES) = 52223.0 PEAK FLOW RATE (CFS) = 1583.41
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
=====

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION (MIN.) = 19.88
RAINFALL INTENSITY (INCH/HR) = 0.78
AREA-AVERAGED Fm (INCH/HR) = 0.44
AREA-AVERAGED Fp (INCH/HR) = 0.60
AREA-AVERAGED Ap = 0.73
EFFECTIVE STREAM AREA (ACRES) = 2241.34
TOTAL STREAM AREA (ACRES) = 52222.99
PEAK FLOW RATE (CFS) AT CONFLUENCE = 1583.41

FLOW PROCESS FROM NODE 12730.00 TO NODE 12731.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<
=====

INITIAL SUBAREA FLOW-LENGTH (FEET) = 561.54
ELEVATION DATA: UPSTREAM (FEET) = 613.29 DOWNSTREAM (FEET) = 551.75

Tc = K * [(LENGTH** 3.00) / (ELEVATION CHANGE)] ** 0.20
SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 13.823
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 1.015
SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL, BROADLEAF"	-	6.33	0.60	1.000	65	13.82

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF (CFS) = 2.37
TOTAL AREA (ACRES) = 6.33 PEAK FLOW RATE (CFS) = 2.37

FLOW PROCESS FROM NODE 12731.00 TO NODE 12732.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====

ELEVATION DATA: UPSTREAM (FEET) = 551.75 DOWNSTREAM (FEET) = 494.40

CHANNEL LENGTH THRU SUBAREA(FEET) = 971.91 CHANNEL SLOPE = 0.0590
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.886
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 34.62 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 6.90
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.52
AVERAGE FLOW DEPTH(FEET) = 0.65 TRAVEL TIME(MIN.) = 2.94
Tc(MIN.) = 16.76
SUBAREA AREA(ACRES) = 34.62 SUBAREA RUNOFF(CFS) = 8.91
EFFECTIVE AREA(ACRES) = 40.95 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 40.9 PEAK FLOW RATE(CFS) = 10.54

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.76 FLOW VELOCITY(FEET/SEC.) = 6.08
LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12732.00 = 1533.45 FEET.

FLOW PROCESS FROM NODE 12732.00 TO NODE 12733.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 494.40 DOWNSTREAM(FEET) = 431.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1156.41 CHANNEL SLOPE = 0.0548
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.786
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 59.52 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 15.61
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.57
AVERAGE FLOW DEPTH(FEET) = 0.89 TRAVEL TIME(MIN.) = 2.93
Tc(MIN.) = 19.69
SUBAREA AREA(ACRES) = 59.52 SUBAREA RUNOFF(CFS) = 9.95
EFFECTIVE AREA(ACRES) = 100.47 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 100.5 PEAK FLOW RATE(CFS) = 16.79

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.92 FLOW VELOCITY(FEET/SEC.) = 6.64
LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12733.00 = 2689.86 FEET.

FLOW PROCESS FROM NODE 12733.00 TO NODE 12734.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 431.00 DOWNSTREAM(FEET) = 367.10
CHANNEL LENGTH THRU SUBAREA(FEET) = 1654.48 CHANNEL SLOPE = 0.0386
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.683
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 64.05 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 19.29
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.03
AVERAGE FLOW DEPTH(FEET) = 1.03 TRAVEL TIME(MIN.) = 4.57
Tc(MIN.) = 24.27
SUBAREA AREA(ACRES) = 64.05 SUBAREA RUNOFF(CFS) = 4.79
EFFECTIVE AREA(ACRES) = 164.52 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 164.5 PEAK FLOW RATE(CFS) = 16.79
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.98 FLOW VELOCITY(FEET/SEC.) = 5.84
LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12734.00 = 4344.34 FEET.

FLOW PROCESS FROM NODE 12734.00 TO NODE 12740.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 367.11 DOWNSTREAM(FEET) = 252.10
CHANNEL LENGTH THRU SUBAREA(FEET) = 1880.98 CHANNEL SLOPE = 0.0611
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.610
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 26.02 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 16.93
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.92
AVERAGE FLOW DEPTH(FEET) = 0.90 TRAVEL TIME(MIN.) = 4.53
Tc(MIN.) = 28.80
SUBAREA AREA(ACRES) = 26.02 SUBAREA RUNOFF(CFS) = 0.24
EFFECTIVE AREA(ACRES) = 190.54 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 190.5 PEAK FLOW RATE(CFS) = 16.79
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.90 FLOW VELOCITY(FEET/SEC.) = 6.95
LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12740.00 = 6225.32 FEET.

FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 28.80
RAINFALL INTENSITY(INCH/HR) = 0.61
AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60
AREA-AVERAGED Ap = 1.00
EFFECTIVE STREAM AREA(ACRES) = 190.54
TOTAL STREAM AREA(ACRES) = 190.54
PEAK FLOW RATE(CFS) AT CONFLUENCE = 16.79

** CONFLUENCE DATA **

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 30 rows of data.

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 2 rows of data.

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 30 rows of data.

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 1600.20 Tc(MIN.) = 19.88
EFFECTIVE AREA(ACRES) = 2372.90 AREA-AVERAGED Fm(INCH/HR) = 0.44
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.74
TOTAL AREA(ACRES) = 52413.5
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12740.00 = 110572.49 FEET.

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 252.10 DOWNSTREAM(FEET) = 240.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1200.00 CHANNEL SLOPE = 0.0101
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.738

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Contains 6 rows of data.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.784

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1600.97
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.03
 AVERAGE FLOW DEPTH(FEET) = 6.96 TRAVEL TIME(MIN.) = 1.81
 Tc(MIN.) = 21.70
 SUBAREA AREA(ACRES) = 6.40 SUBAREA RUNOFF(CFS) = 1.54
 EFFECTIVE AREA(ACRES) = 2379.30 AREA-AVERAGED Fm(INCH/HR) = 0.44
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.74
 TOTAL AREA(ACRES) = 52419.9 PEAK FLOW RATE(CFS) = 1600.20
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 6.96 FLOW VELOCITY(FEET/SEC.) = 11.03
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111772.49 FEET.

 FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 81

=====
 >>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
 =====

MAINLINE Tc(MIN.) = 21.70
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.738
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 3.90 0.60 1.000 -
 USER-DEFINED - 8.70 0.60 1.000 -
 USER-DEFINED - 10.30 0.60 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 22.90 SUBAREA RUNOFF(CFS) = 2.85
 EFFECTIVE AREA(ACRES) = 2402.20 AREA-AVERAGED Fm(INCH/HR) = 0.45
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.74
 TOTAL AREA(ACRES) = 52442.8 PEAK FLOW RATE(CFS) = 1600.20
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

=====
 END OF STUDY SUMMARY:
 TOTAL AREA(ACRES) = 52442.8 TC(MIN.) = 21.70
 EFFECTIVE AREA(ACRES) = 2402.20 AREA-AVERAGED Fm(INCH/HR) = 0.45
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.744
 PEAK FLOW RATE(CFS) = 1600.20

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1600.20	21.70	0.738	0.60(0.45)	0.74	2402.2	410.00
2	1600.00	23.64	0.696	0.60(0.45)	0.74	2671.6	420.00
3	1591.18	25.40	0.661	0.60(0.45)	0.75	2907.0	940.00
4	1516.58	28.09	0.621	0.60(0.45)	0.75	3350.3	310.00
5	1450.64	30.17	0.591	0.60(0.46)	0.76	3671.7	400.00
6	1434.08	30.66	0.587	0.60(0.46)	0.77	3742.1	12730.00
7	1336.66	33.06	0.567	0.60(0.47)	0.78	4069.1	300.00
8	1319.92	33.56	0.563	0.60(0.47)	0.78	4135.7	430.00
9	1316.06	33.68	0.562	0.60(0.47)	0.78	4151.6	320.00
10	1264.26	35.45	0.547	0.60(0.47)	0.79	4361.2	12710.00
11	1248.64	35.91	0.544	0.60(0.47)	0.79	4409.8	900.00
12	718.54	50.25	0.452	0.60(0.50)	0.84	5634.2	600.00
13	715.70	51.02	0.447	0.60(0.50)	0.84	5739.5	390.00
14	770.08	99.26	0.328	0.60(0.55)	0.92	12320.3	11831.00

15	848.66	123.25	0.287	0.60(0.56)	0.94	16005.4	11530.00
16	928.42	143.21	0.269	0.60(0.57)	0.95	20152.1	11000.00
17	1035.61	166.06	0.249	0.60(0.58)	0.96	26948.0	10850.00
18	923.55	187.18	0.234	0.60(0.58)	0.97	31282.6	11910.00
19	862.93	199.00	0.230	0.60(0.58)	0.97	32986.1	12300.00
20	740.60	232.17	0.220	0.60(0.58)	0.97	38694.5	12410.00
21	711.17	240.52	0.217	0.60(0.58)	0.97	40126.7	10600.00
22	700.38	264.92	0.210	0.60(0.58)	0.97	44780.4	12261.00
23	687.33	277.62	0.206	0.60(0.58)	0.97	46267.0	10410.00
24	674.39	289.73	0.202	0.60(0.58)	0.97	47369.0	12101.10
25	660.60	299.38	0.199	0.60(0.58)	0.97	48190.3	10700.00
26	645.15	317.05	0.193	0.60(0.58)	0.97	49747.0	10200.00
27	630.33	330.37	0.189	0.60(0.58)	0.97	50685.3	12010.00
28	588.71	359.21	0.180	0.60(0.58)	0.97	51359.0	10210.00
29	529.80	407.99	0.174	0.60(0.59)	0.98	51858.1	12000.00
30	491.64	477.26	0.166	0.60(0.59)	0.98	52442.8	10100.00

=====
 END OF RATIONAL METHOD ANALYSIS
 =====

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 128 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 2-YR EV FEB 2023 ROKAMOTO *

FILE NAME: RU02EV28.DAT
TIME/DATE OF STUDY: 13:36 02/09/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 2.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 1.861
- 2) 10.00; 1.241
- 3) 15.00; 0.946
- 4) 20.00; 0.775
- 5) 25.00; 0.667
- 6) 30.00; 0.592
- 7) 40.00; 0.510
- 8) 50.00; 0.453
- 9) 60.00; 0.399
- 10) 90.00; 0.345
- 11) 120.00; 0.290
- 12) 180.00; 0.236
- 13) 360.00; 0.180
- 14) 1200.00; 0.083

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL: IN- / OUT-/PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU02EV27.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1600.20	21.70	0.60 (0.45)	0.74	2402.2	410.00
2	1336.66	33.06	0.60 (0.47)	0.78	4069.1	300.00
3	718.54	50.25	0.60 (0.50)	0.84	5634.2	600.00
4	770.08	99.26	0.60 (0.55)	0.92	12320.3	11831.00
5	848.66	123.25	0.60 (0.56)	0.94	16005.4	11530.00
6	928.42	143.21	0.60 (0.57)	0.95	20152.1	11000.00
7	1035.61	166.06	0.60 (0.58)	0.96	26948.0	10850.00
8	923.55	187.18	0.60 (0.58)	0.97	31282.6	11910.00
9	862.93	199.00	0.60 (0.58)	0.97	32986.1	12300.00
10	740.60	232.17	0.60 (0.58)	0.97	38694.5	12410.00
11	711.17	240.52	0.60 (0.58)	0.97	40126.7	10600.00
12	700.38	264.92	0.60 (0.58)	0.97	44780.4	12261.00
13	687.33	277.62	0.60 (0.58)	0.97	46267.0	10410.00
14	674.39	289.73	0.60 (0.58)	0.97	47369.0	12101.10
15	660.60	299.38	0.60 (0.58)	0.97	48190.3	10700.00
16	645.15	317.05	0.60 (0.58)	0.97	49747.0	10200.00
17	630.33	330.37	0.60 (0.58)	0.97	50685.3	12010.00
18	588.71	359.21	0.60 (0.58)	0.97	51359.0	10210.00
19	529.80	407.99	0.60 (0.59)	0.98	51858.1	12000.00
20	491.64	477.26	0.60 (0.59)	0.98	52442.8	10100.00
TOTAL AREA (ACRES) =						52442.8

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: P501XX02.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	55.42	15.69	0.60 (0.50)	0.83	166.9	50110.00
2	49.27	21.93	0.60 (0.51)	0.85	223.2	50100.00
TOTAL AREA (ACRES) =						223.2

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
------------------	------------	--------------	----------------------	----	---------------	-------------------

1	55.42	15.69	0.60	(0.50)	0.83	166.9	50110.00
2	49.27	21.93	0.60	(0.51)	0.85	223.2	50100.00
TOTAL AREA (ACRES) =		223.2					

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	55.42	15.69	0.923	0.60 (0.50)	0.83	166.9	50110.00
2	49.27	21.93	0.733	0.60 (0.51)	0.85	223.2	50100.00

LONGEST FLOWPATH FROM NODE 50100.00 TO NODE 12800.00 = 4170.00 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1600.20	21.70	0.738	0.60 (0.45)	0.74	2402.2	410.00
2	1336.66	33.06	0.567	0.60 (0.47)	0.78	4069.1	300.00
3	718.54	50.25	0.452	0.60 (0.50)	0.84	5634.2	600.00
4	770.08	99.26	0.328	0.60 (0.55)	0.92	12320.3	11831.00
5	848.66	123.25	0.287	0.60 (0.56)	0.94	16005.4	11530.00
6	928.42	143.21	0.269	0.60 (0.57)	0.95	20152.1	11000.00
7	1035.61	166.06	0.249	0.60 (0.58)	0.96	26948.0	10850.00
8	923.55	187.18	0.234	0.60 (0.58)	0.97	31282.6	11910.00
9	862.93	199.00	0.230	0.60 (0.58)	0.97	32986.1	12300.00
10	740.60	232.17	0.220	0.60 (0.58)	0.97	38694.5	12410.00
11	711.17	240.52	0.217	0.60 (0.58)	0.97	40126.7	10600.00
12	700.38	264.92	0.210	0.60 (0.58)	0.97	44780.4	12261.00
13	687.33	277.62	0.206	0.60 (0.58)	0.97	46267.0	10410.00
14	674.39	289.73	0.202	0.60 (0.58)	0.97	47369.0	12101.10
15	660.60	299.38	0.199	0.60 (0.58)	0.97	48190.3	10700.00
16	645.15	317.05	0.193	0.60 (0.58)	0.97	49747.0	10200.00
17	630.33	330.37	0.189	0.60 (0.58)	0.97	50685.3	12010.00
18	588.71	359.21	0.180	0.60 (0.58)	0.97	51359.0	10210.00
19	529.80	407.99	0.174	0.60 (0.59)	0.98	51858.1	12000.00
20	491.64	477.26	0.166	0.60 (0.59)	0.98	52442.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111772.49 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1655.62	15.69	0.923	0.60 (0.45)	0.75	1903.6	50110.00
2	1649.70	21.70	0.738	0.60 (0.45)	0.75	2623.3	410.00
3	1644.03	21.93	0.733	0.60 (0.45)	0.75	2659.8	50100.00
4	1355.38	33.06	0.567	0.60 (0.47)	0.78	4292.3	300.00
5	733.45	50.25	0.452	0.60 (0.50)	0.84	5857.4	600.00
6	780.91	99.26	0.328	0.60 (0.55)	0.92	12543.5	11831.00
7	858.13	123.25	0.287	0.60 (0.56)	0.94	16228.6	11530.00
8	937.30	143.21	0.269	0.60 (0.57)	0.95	20375.3	11000.00
9	1043.81	166.06	0.249	0.60 (0.58)	0.96	27171.2	10850.00
10	931.26	187.18	0.234	0.60 (0.58)	0.97	31505.8	11910.00
11	870.52	199.00	0.230	0.60 (0.58)	0.97	33209.2	12300.00
12	747.85	232.17	0.220	0.60 (0.58)	0.97	38917.7	12410.00
13	718.33	240.52	0.217	0.60 (0.58)	0.97	40349.9	10600.00

14	707.30	264.92	0.210	0.60 (0.58)	0.97	45003.6	12261.00
15	694.11	277.62	0.206	0.60 (0.58)	0.97	46490.2	10410.00
16	681.05	289.73	0.202	0.60 (0.58)	0.97	47592.2	12101.10
17	667.16	299.38	0.199	0.60 (0.58)	0.97	48413.5	10700.00
18	651.54	317.05	0.193	0.60 (0.58)	0.97	49970.2	10200.00
19	636.57	330.37	0.189	0.60 (0.58)	0.97	50908.5	12010.00
20	594.66	359.21	0.180	0.60 (0.58)	0.97	51582.2	10210.00
21	535.56	407.99	0.174	0.60 (0.58)	0.97	52081.3	12000.00
22	497.13	477.26	0.166	0.60 (0.58)	0.97	52666.0	10100.00
TOTAL AREA (ACRES) =		52666.0					

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 1655.62 Tc (MIN.) = 15.686
EFFECTIVE AREA (ACRES) = 1903.63 AREA-AVERAGED Fm (INCH/HR) = 0.45
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.75
TOTAL AREA (ACRES) = 52666.0
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111772.49 FEET.

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 52666.0 TC (MIN.) = 15.69
EFFECTIVE AREA (ACRES) = 1903.63 AREA-AVERAGED Fm (INCH/HR) = 0.45
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.752
PEAK FLOW RATE (CFS) = 1655.62

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1655.62	15.69	0.923	0.60 (0.45)	0.75	1903.6	50110.00
2	1649.70	21.70	0.738	0.60 (0.45)	0.75	2623.3	410.00
3	1644.03	21.93	0.733	0.60 (0.45)	0.75	2659.8	50100.00
4	1355.38	33.06	0.567	0.60 (0.47)	0.78	4292.3	300.00
5	733.45	50.25	0.452	0.60 (0.50)	0.84	5857.4	600.00
6	780.91	99.26	0.328	0.60 (0.55)	0.92	12543.5	11831.00
7	858.13	123.25	0.287	0.60 (0.56)	0.94	16228.6	11530.00
8	937.30	143.21	0.269	0.60 (0.57)	0.95	20375.3	11000.00
9	1043.81	166.06	0.249	0.60 (0.58)	0.96	27171.2	10850.00
10	931.26	187.18	0.234	0.60 (0.58)	0.97	31505.8	11910.00
11	870.52	199.00	0.230	0.60 (0.58)	0.97	33209.2	12300.00
12	747.85	232.17	0.220	0.60 (0.58)	0.97	38917.7	12410.00
13	718.33	240.52	0.217	0.60 (0.58)	0.97	40349.9	10600.00
14	707.30	264.92	0.210	0.60 (0.58)	0.97	45003.6	12261.00
15	694.11	277.62	0.206	0.60 (0.58)	0.97	46490.2	10410.00
16	681.05	289.73	0.202	0.60 (0.58)	0.97	47592.2	12101.10
17	667.16	299.38	0.199	0.60 (0.58)	0.97	48413.5	10700.00
18	651.54	317.05	0.193	0.60 (0.58)	0.97	49970.2	10200.00
19	636.57	330.37	0.189	0.60 (0.58)	0.97	50908.5	12010.00
20	594.66	359.21	0.180	0.60 (0.58)	0.97	51582.2	10210.00
21	535.56	407.99	0.174	0.60 (0.58)	0.97	52081.3	12000.00
22	497.13	477.26	0.166	0.60 (0.58)	0.97	52666.0	10100.00

END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 129 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 2-YR EV FEB 2023 ROKAMOTO *

FILE NAME: RU02EV29.DAT
TIME/DATE OF STUDY: 13:37 02/09/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 2.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 1.853
- 2) 10.00; 1.236
- 3) 15.00; 0.943
- 4) 20.00; 0.773
- 5) 25.00; 0.666
- 6) 30.00; 0.591
- 7) 40.00; 0.509
- 8) 50.00; 0.452
- 9) 60.00; 0.398
- 10) 90.00; 0.342
- 11) 120.00; 0.286
- 12) 180.00; 0.230
- 13) 360.00; 0.176
- 14) 1200.00; 0.082

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL
HALF- CROWN TO STREET-CROSSFALL: CURB GUTTER-GEOMETRIES: MANNING
WIDTH CROSSFALL IN- / OUT-/PARK- HEIGHT WIDTH LIP HIKE FACTOR
NO. (FT) (FT) SIDE / SIDE/ WAY (FT) (FT) (FT) (FT) (n)
=====
1 30.0 20.0 0.018/0.018/0.020 0.67 2.00 0.0313 0.167 0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU02EV28.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1655.62	15.69	0.60 (0.45)	0.75	1903.6	50110.00
2	1355.38	33.06	0.60 (0.47)	0.78	4292.3	300.00
3	733.45	50.25	0.60 (0.50)	0.84	5857.4	600.00
4	780.91	99.26	0.60 (0.55)	0.92	12543.5	11831.00
5	858.13	123.25	0.60 (0.56)	0.94	16228.6	11530.00
6	937.30	143.21	0.60 (0.57)	0.95	20375.3	11000.00
7	1043.81	166.06	0.60 (0.58)	0.96	27171.2	10850.00
8	931.26	187.18	0.60 (0.58)	0.97	31505.8	11910.00
9	870.52	199.00	0.60 (0.58)	0.97	33209.2	12300.00
10	747.85	232.17	0.60 (0.58)	0.97	38917.7	12410.00
11	718.33	240.52	0.60 (0.58)	0.97	40349.9	10600.00
12	707.30	264.92	0.60 (0.58)	0.97	45003.6	12261.00
13	694.11	277.62	0.60 (0.58)	0.97	46490.2	10140.00
14	681.05	289.73	0.60 (0.58)	0.97	47592.2	12101.10
15	667.16	299.38	0.60 (0.58)	0.97	48413.5	10700.00
16	651.54	317.05	0.60 (0.58)	0.97	49970.2	10200.00
17	636.57	330.37	0.60 (0.58)	0.97	50908.5	12010.00
18	594.66	359.21	0.60 (0.58)	0.97	51582.2	10210.00
19	535.56	407.99	0.60 (0.58)	0.97	52081.3	12000.00
20	497.13	477.26	0.60 (0.58)	0.97	52666.0	10100.00
TOTAL AREA(ACRES) =						52666.0

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1655.62	15.69	0.60 (0.45)	0.75	1903.6	50110.00
2	1355.38	33.06	0.60 (0.47)	0.78	4292.3	300.00
3	733.45	50.25	0.60 (0.50)	0.84	5857.4	600.00
4	780.91	99.26	0.60 (0.55)	0.92	12543.5	11831.00
5	858.13	123.25	0.60 (0.56)	0.94	16228.6	11530.00
6	937.30	143.21	0.60 (0.57)	0.95	20375.3	11000.00
7	1043.81	166.06	0.60 (0.58)	0.96	27171.2	10850.00
8	931.26	187.18	0.60 (0.58)	0.97	31505.8	11910.00
9	870.52	199.00	0.60 (0.58)	0.97	33209.2	12300.00
10	747.85	232.17	0.60 (0.58)	0.97	38917.7	12410.00
11	718.33	240.52	0.60 (0.58)	0.97	40349.9	10600.00
12	707.30	264.92	0.60 (0.58)	0.97	45003.6	12261.00
13	694.11	277.62	0.60 (0.58)	0.97	46490.2	10140.00

14	681.05	289.73	0.60	(0.58)	0.97	47592.2	12101.10
15	667.16	299.38	0.60	(0.58)	0.97	48413.5	10700.00
16	651.54	317.05	0.60	(0.58)	0.97	49970.2	10200.00
17	636.57	330.37	0.60	(0.58)	0.97	50908.5	12010.00
18	594.66	359.21	0.60	(0.58)	0.97	51582.2	10210.00
19	535.56	407.99	0.60	(0.58)	0.97	52081.3	12000.00
20	497.13	477.26	0.60	(0.58)	0.97	52666.0	10100.00
TOTAL AREA (ACRES) =			52666.0				

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<<
=====

FLOW PROCESS FROM NODE 12800.00 TO NODE 12901.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<<
=====

ELEVATION DATA: UPSTREAM(FEET) = 240.00 DOWNSTREAM(FEET) = 216.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 3120.28 CHANNEL SLOPE = 0.0077
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
CHANNEL FLOW THRU SUBAREA(CFS) = 1655.62
FLOW VELOCITY(FEET/SEC.) = 10.04 FLOW DEPTH(FEET) = 7.41
TRAVEL TIME(MIN.) = 5.18 Tc(MIN.) = 20.86
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12901.00 = 114892.77 FEET.

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<
=====

MAINLINE Tc(MIN.) = 20.86
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.755

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	14.30	0.60	0.100	-
USER-DEFINED	-	9.40	0.60	0.850	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.397
SUBAREA AREA(ACRES) = 23.70 SUBAREA RUNOFF(CFS) = 11.01
EFFECTIVE AREA(ACRES) = 1927.33 AREA-AVERAGED Fm(INCH/HR) = 0.45
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.75
TOTAL AREA(ACRES) = 52689.7 PEAK FLOW RATE(CFS) = 1655.62
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<
=====

MAINLINE Tc(MIN.) = 20.86
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.755

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.20	0.60	0.100	-
USER-DEFINED	-	0.40	0.60	0.500	-
USER-DEFINED	-	0.50	0.60	0.900	-
USER-DEFINED	-	0.60	0.60	1.000	-
USER-DEFINED	-	0.70	0.60	0.100	-
USER-DEFINED	-	0.70	0.60	0.900	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.635
SUBAREA AREA(ACRES) = 3.10 SUBAREA RUNOFF(CFS) = 1.04
EFFECTIVE AREA(ACRES) = 1930.43 AREA-AVERAGED Fm(INCH/HR) = 0.45
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.75
TOTAL AREA(ACRES) = 52692.8 PEAK FLOW RATE(CFS) = 1655.62
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<
=====

MAINLINE Tc(MIN.) = 20.86
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.755

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.70	0.60	0.850	-
USER-DEFINED	-	1.00	0.60	1.000	-
USER-DEFINED	-	1.40	0.60	1.000	-
USER-DEFINED	-	1.50	0.60	1.000	-
USER-DEFINED	-	1.70	0.60	0.100	-
USER-DEFINED	-	2.90	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.822
SUBAREA AREA(ACRES) = 9.20 SUBAREA RUNOFF(CFS) = 2.16
EFFECTIVE AREA(ACRES) = 1939.63 AREA-AVERAGED Fm(INCH/HR) = 0.45
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.75
TOTAL AREA(ACRES) = 52702.0 PEAK FLOW RATE(CFS) = 1655.62
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<
=====

MAINLINE Tc(MIN.) = 20.86
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.755

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	3.60	0.60	1.000	-
USER-DEFINED	-	3.70	0.60	0.500	-
USER-DEFINED	-	4.10	0.60	0.900	-
USER-DEFINED	-	5.40	0.60	0.900	-
USER-DEFINED	-	6.70	0.60	1.000	-
USER-DEFINED	-	12.00	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.921

SUBAREA AREA (ACRES) = 35.50 SUBAREA RUNOFF (CFS) = 6.45
 EFFECTIVE AREA (ACRES) = 1975.13 AREA-AVERAGED Fm (INCH/HR) = 0.45
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.75
 TOTAL AREA (ACRES) = 52737.5 PEAK FLOW RATE (CFS) = 1655.62
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 20.86
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.755
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 12.90 0.60 1.000 -
 USER-DEFINED - 38.60 0.60 0.850 -
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.888
 SUBAREA AREA (ACRES) = 51.50 SUBAREA RUNOFF (CFS) = 10.29
 EFFECTIVE AREA (ACRES) = 2026.63 AREA-AVERAGED Fm (INCH/HR) = 0.45
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.75
 TOTAL AREA (ACRES) = 52789.0 PEAK FLOW RATE (CFS) = 1655.62
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12901.00 TO NODE 12902.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM (FEET) = 216.00 DOWNSTREAM (FEET) = 215.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 122.04 CHANNEL SLOPE = 0.0082
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00
 CHANNEL FLOW THRU SUBAREA (CFS) = 1655.62
 FLOW VELOCITY (FEET/SEC.) = 10.28 FLOW DEPTH (FEET) = 7.33
 TRAVEL TIME (MIN.) = 0.20 Tc (MIN.) = 21.06
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115014.81 FEET.

 FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<

PEAK FLOWRATE TABLE FILE NAME: P503XX02.DNA
 MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	249.94	24.13	0.60 (0.44)	0.74	974.1	50320.00
2	238.06	27.18	0.60 (0.44)	0.74	1066.0	50240.00
3	235.52	27.54	0.60 (0.44)	0.74	1075.7	50330.00
4	204.90	31.73	0.60 (0.44)	0.74	1176.9	50300.00
5	202.01	32.10	0.60 (0.44)	0.74	1183.1	50280.00
6	159.62	37.43	0.60 (0.44)	0.74	1246.6	50220.00
7	136.90	45.01	0.60 (0.44)	0.74	1294.0	50260.00
8	132.00	47.96	0.60 (0.44)	0.74	1298.6	50200.00

TOTAL AREA (ACRES) = 1298.6

 FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1655.62	21.06	0.750	0.60 (0.45)	0.75	2026.6	50110.00
2	1355.38	38.71	0.520	0.60 (0.47)	0.78	4415.3	300.00
3	733.45	56.83	0.415	0.60 (0.50)	0.83	5980.4	600.00
4	780.91	105.74	0.313	0.60 (0.55)	0.92	12666.5	11831.00
5	858.13	129.58	0.277	0.60 (0.56)	0.94	16351.6	11530.00
6	937.30	149.41	0.259	0.60 (0.57)	0.95	20498.3	11000.00
7	1043.81	172.10	0.237	0.60 (0.58)	0.96	27294.2	10850.00
8	931.26	193.38	0.226	0.60 (0.58)	0.96	31628.8	11910.00
9	870.52	205.31	0.222	0.60 (0.58)	0.97	33332.2	12300.00
10	747.85	238.73	0.212	0.60 (0.58)	0.97	39040.7	12410.00
11	718.33	247.15	0.210	0.60 (0.58)	0.97	40472.9	10600.00
12	707.30	271.57	0.203	0.60 (0.58)	0.97	45126.6	12261.00
13	694.11	284.30	0.199	0.60 (0.58)	0.97	46613.2	10410.00
14	681.05	296.45	0.195	0.60 (0.58)	0.97	47715.2	12101.10
15	667.16	306.12	0.192	0.60 (0.58)	0.97	48536.5	10700.00
16	651.54	323.83	0.187	0.60 (0.58)	0.97	50093.2	10200.00
17	636.57	337.19	0.183	0.60 (0.58)	0.97	51031.5	12010.00
18	594.66	366.15	0.175	0.60 (0.58)	0.97	51705.2	10210.00
19	535.56	415.12	0.170	0.60 (0.58)	0.97	52204.3	12000.00
20	497.13	484.52	0.162	0.60 (0.58)	0.97	52789.0	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115014.81 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	249.94	24.13	0.685	0.60 (0.44)	0.74	974.1	50320.00
2	238.06	27.18	0.633	0.60 (0.44)	0.74	1066.0	50240.00
3	235.52	27.54	0.628	0.60 (0.44)	0.74	1075.7	50330.00
4	204.90	31.73	0.577	0.60 (0.44)	0.74	1176.9	50300.00
5	202.01	32.10	0.574	0.60 (0.44)	0.74	1183.1	50280.00
6	159.62	37.43	0.530	0.60 (0.44)	0.74	1246.6	50220.00
7	136.90	45.01	0.480	0.60 (0.44)	0.74	1294.0	50260.00
8	132.00	47.96	0.464	0.60 (0.44)	0.74	1298.6	50200.00

LONGEST FLOWPATH FROM NODE 50220.00 TO NODE 12902.00 = 17597.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1905.56	21.06	0.750	0.60 (0.45)	0.75	2876.9	50110.00
2	1853.39	24.13	0.685	0.60 (0.45)	0.75	3415.8	50320.00
3	1789.57	27.18	0.633	0.60 (0.45)	0.76	3920.9	50240.00
4	1780.99	27.54	0.628	0.60 (0.45)	0.76	3978.6	50330.00
5	1679.05	31.73	0.577	0.60 (0.46)	0.76	4647.3	50300.00
6	1669.85	32.10	0.574	0.60 (0.46)	0.76	4703.7	50280.00
7	1536.76	37.43	0.530	0.60 (0.46)	0.77	5488.8	50220.00
8	1511.17	38.71	0.520	0.60 (0.46)	0.77	5669.9	300.00
9	1275.97	45.01	0.480	0.60 (0.47)	0.79	6253.7	50260.00

10	1170.09	47.96	0.464	0.60	(0.48)	0.79	6512.4	50200.00
11	851.63	56.83	0.415	0.60	(0.49)	0.82	7279.0	600.00
12	869.91	105.74	0.313	0.60	(0.54)	0.90	13965.1	11831.00
13	937.01	129.58	0.277	0.60	(0.55)	0.92	17650.2	11530.00
14	1010.91	149.41	0.259	0.60	(0.56)	0.94	21796.9	11000.00
15	1111.39	172.10	0.237	0.60	(0.57)	0.95	28592.8	10850.00
16	995.60	193.38	0.226	0.60	(0.57)	0.96	32927.4	11910.00
17	933.84	205.31	0.222	0.60	(0.57)	0.96	34630.9	12300.00
18	808.32	238.73	0.212	0.60	(0.58)	0.96	40339.3	12410.00
19	778.08	247.15	0.210	0.60	(0.58)	0.96	41771.5	10600.00
20	764.96	271.57	0.203	0.60	(0.58)	0.96	46425.2	12261.00
21	750.69	284.30	0.199	0.60	(0.58)	0.97	47911.8	10410.00
22	736.58	296.45	0.195	0.60	(0.58)	0.97	49013.8	12101.10
23	721.87	306.12	0.192	0.60	(0.58)	0.97	49835.1	10700.00
24	704.73	323.83	0.187	0.60	(0.58)	0.97	51391.8	10200.00
25	688.63	337.19	0.183	0.60	(0.58)	0.97	52330.1	12010.00
26	644.57	366.15	0.175	0.60	(0.58)	0.97	53003.8	10210.00
27	583.91	415.12	0.170	0.60	(0.58)	0.97	53502.9	12000.00
28	543.27	484.52	0.162	0.60	(0.58)	0.97	54087.6	10100.00
TOTAL AREA (ACRES) =								54087.6

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 1905.56 Tc (MIN.) = 21.062
EFFECTIVE AREA (ACRES) = 2876.91 AREA-AVERAGED Fm (INCH/HR) = 0.45
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.75
TOTAL AREA (ACRES) = 54087.6
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115014.81 FEET.

FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<<
=====

FLOW PROCESS FROM NODE 12902.00 TO NODE 12903.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<
=====

ELEVATION DATA: UPSTREAM (FEET) = 215.00 DOWNSTREAM (FEET) = 214.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 895.53 CHANNEL SLOPE = 0.0011
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00
CHANNEL FLOW THRU SUBAREA (CFS) = 1905.56
FLOW VELOCITY (FEET/SEC.) = 5.05 FLOW DEPTH (FEET) = 11.22
TRAVEL TIME (MIN.) = 2.96 Tc (MIN.) = 24.02
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115910.34 FEET.

FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<
=====

PEAK FLOWRATE TABLE FILE NAME: P504XX02.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
---------------	---------	-----------	-------------------	----	------------	----------------

1	14.83	16.85	0.60	(0.56)	0.94	70.7	50400.00
TOTAL AREA (ACRES) =						70.7	

FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<
=====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1905.56	24.02	0.687	0.60 (0.45)	0.75	2876.9	50110.00
2	1853.39	27.11	0.634	0.60 (0.45)	0.75	3415.8	50320.00
3	1789.57	30.19	0.589	0.60 (0.45)	0.76	3920.9	50240.00
4	1780.99	30.54	0.587	0.60 (0.45)	0.76	3978.6	50330.00
5	1679.05	34.78	0.552	0.60 (0.46)	0.76	4647.3	50300.00
6	1669.85	35.16	0.549	0.60 (0.46)	0.76	4703.7	50280.00
7	1536.76	40.55	0.506	0.60 (0.46)	0.77	5488.8	50220.00
8	1511.17	41.85	0.498	0.60 (0.46)	0.77	5669.9	300.00
9	1275.97	48.28	0.462	0.60 (0.47)	0.79	6253.7	50260.00
10	1170.09	51.30	0.445	0.60 (0.48)	0.79	6512.4	50200.00
11	851.63	60.45	0.397	0.60 (0.49)	0.82	7279.0	600.00
12	869.91	109.34	0.306	0.60 (0.54)	0.90	13965.1	11831.00
13	937.01	133.11	0.274	0.60 (0.55)	0.92	17650.2	11530.00
14	1010.91	152.87	0.255	0.60 (0.56)	0.94	21796.9	11000.00
15	1111.39	175.48	0.234	0.60 (0.57)	0.95	28592.8	10850.00
16	995.60	196.86	0.225	0.60 (0.57)	0.96	32927.4	11910.00
17	933.84	208.85	0.221	0.60 (0.57)	0.96	34630.9	12300.00
18	808.32	242.40	0.211	0.60 (0.58)	0.96	40339.3	12410.00
19	778.08	250.85	0.209	0.60 (0.58)	0.96	41771.5	10600.00
20	764.96	275.29	0.201	0.60 (0.58)	0.96	46425.2	12261.00
21	750.69	288.03	0.198	0.60 (0.58)	0.97	47911.8	10410.00
22	736.58	300.20	0.194	0.60 (0.58)	0.97	49013.8	12101.10
23	721.87	309.88	0.191	0.60 (0.58)	0.97	49835.1	10700.00
24	704.73	327.62	0.186	0.60 (0.58)	0.97	51391.8	10200.00
25	688.63	341.00	0.182	0.60 (0.58)	0.97	52330.1	12010.00
26	644.57	370.03	0.175	0.60 (0.58)	0.97	53003.8	10210.00
27	583.91	419.09	0.169	0.60 (0.58)	0.97	53502.9	12000.00
28	543.27	488.57	0.162	0.60 (0.58)	0.97	54087.6	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115910.34 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14.83	16.85	0.880	0.60 (0.56)	0.94	70.7	50400.00

LONGEST FLOWPATH FROM NODE 50400.00 TO NODE 12903.00 = 3607.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1920.39	16.85	0.880	0.60 (0.45)	0.76	2089.3	50400.00
2	1911.37	24.02	0.687	0.60 (0.45)	0.75	2947.6	50110.00
3	1856.74	27.11	0.634	0.60 (0.45)	0.76	3486.5	50320.00
4	1791.28	30.19	0.589	0.60 (0.46)	0.76	3991.6	50240.00
5	1782.70	30.54	0.587	0.60 (0.46)	0.76	4049.3	50330.00
6	1680.65	34.78	0.552	0.60 (0.46)	0.77	4718.0	50300.00
7	1671.45	35.16	0.549	0.60 (0.46)	0.77	4774.4	50280.00

Stream Number	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
8	1538.23	40.55	0.506	0.60 (0.46)	0.77	5559.5	50220.00
9	1512.62	41.85	0.498	0.60 (0.46)	0.77	5740.6	300.00
10	1277.32	48.28	0.462	0.60 (0.47)	0.79	6324.4	50260.00
11	1171.38	51.30	0.445	0.60 (0.48)	0.80	6583.1	50200.00
12	852.79	60.45	0.397	0.60 (0.49)	0.82	7349.7	600.00
13	870.80	109.34	0.306	0.60 (0.54)	0.90	14035.8	11831.00
14	937.81	133.11	0.274	0.60 (0.55)	0.92	17720.9	11530.00
15	1011.65	152.87	0.255	0.60 (0.56)	0.94	21867.6	11000.00
16	1112.07	175.48	0.234	0.60 (0.57)	0.95	28663.5	10850.00
17	996.25	196.86	0.225	0.60 (0.57)	0.96	32998.1	11910.00
18	934.49	208.85	0.221	0.60 (0.57)	0.96	34701.6	12300.00
19	808.93	242.40	0.211	0.60 (0.58)	0.96	40410.0	12410.00
20	778.69	250.85	0.209	0.60 (0.58)	0.96	41842.2	10600.00
21	765.54	275.29	0.201	0.60 (0.58)	0.96	46495.9	12261.00
22	751.26	288.03	0.198	0.60 (0.58)	0.97	47982.5	10410.00
23	737.15	300.20	0.194	0.60 (0.58)	0.97	49084.5	12101.10
24	722.43	309.88	0.191	0.60 (0.58)	0.97	49905.8	10700.00
25	705.27	327.62	0.186	0.60 (0.58)	0.97	51462.5	10200.00
26	689.16	341.00	0.182	0.60 (0.58)	0.97	52400.8	12010.00
27	645.08	370.03	0.175	0.60 (0.58)	0.97	53074.5	10210.00
28	584.41	419.09	0.169	0.60 (0.58)	0.97	53573.6	12000.00
29	543.74	488.57	0.162	0.60 (0.58)	0.97	54158.3	10100.00

TOTAL AREA (ACRES) = 54158.3

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 1920.39 Tc (MIN.) = 16.853
EFFECTIVE AREA (ACRES) = 2089.26 AREA-AVERAGED Fm (INCH/HR) = 0.45
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.97
TOTAL AREA (ACRES) = 54158.3
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115910.34 FEET.

FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

FLOW PROCESS FROM NODE 12903.00 TO NODE 12904.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 214.00 DOWNSTREAM (FEET) = 213.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 767.57 CHANNEL SLOPE = 0.0013
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00
CHANNEL FLOW THRU SUBAREA (CFS) = 1920.39
FLOW VELOCITY (FEET/SEC.) = 5.36 FLOW DEPTH (FEET) = 10.93
TRAVEL TIME (MIN.) = 2.39 Tc (MIN.) = 19.24
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116677.91 FEET.

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 3B02EVRL.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

Stream Number	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	89.21	20.90	0.60	(0.26)	0.43	200.4	203.00
2	86.32	23.19	0.60	(0.26)	0.43	213.7	210.00

TOTAL AREA (ACRES) = 213.7

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

Stream Number	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1920.39	19.24	0.799	0.60 (0.45)	0.76	2089.3	50400.00
2	1911.37	26.41	0.645	0.60 (0.45)	0.75	2947.6	50110.00
3	1856.74	29.51	0.598	0.60 (0.45)	0.76	3486.5	50320.00
4	1791.28	32.62	0.570	0.60 (0.46)	0.76	3991.6	50240.00
5	1782.70	32.98	0.567	0.60 (0.46)	0.76	4049.3	50330.00
6	1680.65	37.25	0.532	0.60 (0.46)	0.77	4718.0	50300.00
7	1671.45	37.63	0.528	0.60 (0.46)	0.77	4774.4	50280.00
8	1538.23	43.08	0.491	0.60 (0.46)	0.77	5559.5	50220.00
9	1512.62	44.38	0.484	0.60 (0.46)	0.77	5740.6	300.00
10	1277.32	50.93	0.447	0.60 (0.47)	0.79	6324.4	50260.00
11	1171.38	54.00	0.430	0.60 (0.48)	0.80	6583.1	50200.00
12	852.79	63.38	0.392	0.60 (0.49)	0.82	7349.7	600.00
13	870.80	112.25	0.300	0.60 (0.54)	0.90	14035.8	11831.00
14	937.81	135.97	0.271	0.60 (0.55)	0.92	17720.9	11530.00
15	1011.65	155.68	0.253	0.60 (0.56)	0.94	21867.6	11000.00
16	1112.07	178.22	0.232	0.60 (0.57)	0.95	28663.5	10850.00
17	996.25	199.68	0.224	0.60 (0.57)	0.96	32998.1	11910.00
18	934.49	211.71	0.220	0.60 (0.57)	0.96	34701.6	12300.00
19	808.93	245.36	0.210	0.60 (0.58)	0.96	40410.0	12410.00
20	778.69	253.84	0.208	0.60 (0.58)	0.96	41842.2	10600.00
21	765.54	278.29	0.201	0.60 (0.58)	0.96	46495.9	12261.00
22	751.26	291.05	0.197	0.60 (0.58)	0.97	47982.5	10410.00
23	737.15	303.23	0.193	0.60 (0.58)	0.97	49084.5	12101.10
24	722.43	312.94	0.190	0.60 (0.58)	0.97	49905.8	10700.00
25	705.27	330.69	0.185	0.60 (0.58)	0.97	51462.5	10200.00
26	689.16	344.08	0.181	0.60 (0.58)	0.97	52400.8	12010.00
27	645.08	373.17	0.175	0.60 (0.58)	0.97	53074.5	10210.00
28	584.41	422.31	0.169	0.60 (0.58)	0.97	53573.6	12000.00
29	543.74	491.84	0.161	0.60 (0.58)	0.97	54158.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116677.91 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

Stream Number	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	89.21	20.90	0.754	0.60 (0.26)	0.43	200.4	203.00
2	86.32	23.19	0.705	0.60 (0.26)	0.43	213.7	210.00

LONGEST FLOWPATH FROM NODE 210.00 TO NODE 12904.00 = 7986.00 FEET.

** PEAK FLOW RATE TABLE **

Stream Number	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2009.60	19.24	0.799	0.60 (0.44)	0.73	2273.8	50400.00

2	2007.52	20.90	0.754	0.60	(0.44)	0.73	2488.2	203.00
3	2001.74	23.19	0.705	0.60	(0.44)	0.73	2776.1	210.00
4	1986.19	26.41	0.645	0.60	(0.44)	0.73	3161.3	50110.00
5	1922.73	29.51	0.598	0.60	(0.44)	0.74	3700.2	50320.00
6	1854.10	32.62	0.570	0.60	(0.45)	0.74	4205.3	50240.00
7	1845.19	32.98	0.567	0.60	(0.45)	0.74	4263.0	50330.00
8	1739.28	37.25	0.532	0.60	(0.45)	0.75	4931.7	50300.00
9	1729.73	37.63	0.528	0.60	(0.45)	0.75	4988.1	50280.00
10	1592.43	43.08	0.491	0.60	(0.46)	0.76	5773.2	50220.00
11	1566.00	44.38	0.484	0.60	(0.46)	0.76	5954.3	300.00
12	1326.62	50.93	0.447	0.60	(0.47)	0.78	6538.1	50260.00
13	1218.86	54.00	0.430	0.60	(0.47)	0.78	6796.8	50200.00
14	895.99	63.38	0.392	0.60	(0.48)	0.81	7563.4	600.00
15	903.94	112.25	0.300	0.60	(0.54)	0.90	14249.5	11831.00
16	967.71	135.97	0.271	0.60	(0.55)	0.92	17934.6	11530.00
17	1039.53	155.68	0.253	0.60	(0.56)	0.93	22081.3	11000.00
18	1137.62	178.22	0.232	0.60	(0.57)	0.95	28877.2	10850.00
19	1020.97	199.68	0.224	0.60	(0.57)	0.95	33211.8	11910.00
20	958.81	211.71	0.220	0.60	(0.57)	0.95	34915.2	12300.00
21	832.14	245.36	0.210	0.60	(0.58)	0.96	40623.7	12410.00
22	801.61	253.84	0.208	0.60	(0.58)	0.96	42055.9	10600.00
23	787.66	278.29	0.201	0.60	(0.58)	0.96	46709.6	12261.00
24	772.95	291.05	0.197	0.60	(0.58)	0.96	48196.2	10410.00
25	758.44	303.23	0.193	0.60	(0.58)	0.96	49298.2	12101.10
26	743.40	312.94	0.190	0.60	(0.58)	0.96	50119.5	10700.00
27	725.65	330.69	0.185	0.60	(0.58)	0.97	51676.2	10200.00
28	709.10	344.08	0.181	0.60	(0.58)	0.97	52614.5	12010.00
29	664.33	373.17	0.175	0.60	(0.58)	0.97	53288.2	10210.00
30	603.05	422.31	0.169	0.60	(0.58)	0.97	53787.3	12000.00
31	561.53	491.84	0.161	0.60	(0.58)	0.97	54372.0	10100.00
TOTAL AREA (ACRES) =		54372.0						

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 2009.60 Tc(MIN.) = 19.241
EFFECTIVE AREA(ACRES) = 2273.76 AREA-AVERAGED Fm(INCH/HR) = 0.44
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.73
TOTAL AREA(ACRES) = 54372.0
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116677.91 FEET.

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 19.24

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.799

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.10	0.60	0.900	-
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	0.80	0.60	1.000	-
USER-DEFINED	-	1.20	0.60	0.100	-
USER-DEFINED	-	1.50	0.60	1.000	-
USER-DEFINED	-	3.00	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.840

SUBAREA AREA(ACRES) = 6.80 SUBAREA RUNOFF(CFS) = 1.81

EFFECTIVE AREA(ACRES) = 2280.56 AREA-AVERAGED Fm(INCH/HR) = 0.44
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.73
TOTAL AREA(ACRES) = 54378.8 PEAK FLOW RATE(CFS) = 2009.60
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 19.24

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.799

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	3.60	0.60	1.000	-
USER-DEFINED	-	15.10	0.60	0.850	-
USER-DEFINED	-	20.00	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.941

SUBAREA AREA(ACRES) = 38.70 SUBAREA RUNOFF(CFS) = 8.15

EFFECTIVE AREA(ACRES) = 2319.26 AREA-AVERAGED Fm(INCH/HR) = 0.44

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.73

TOTAL AREA(ACRES) = 54417.5 PEAK FLOW RATE(CFS) = 2009.60

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 54417.5 TC(MIN.) = 19.24

EFFECTIVE AREA(ACRES) = 2319.26 AREA-AVERAGED Fm(INCH/HR) = 0.44

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.734

PEAK FLOW RATE(CFS) = 2009.60

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2009.60	19.24	0.799	0.60(0.44)	0.73	2319.3	50400.00
2	2007.52	20.90	0.754	0.60(0.44)	0.73	2533.7	203.00
3	2001.74	23.19	0.705	0.60(0.44)	0.73	2821.6	210.00
4	1986.19	26.41	0.645	0.60(0.44)	0.74	3206.8	50110.00
5	1922.73	29.51	0.598	0.60(0.44)	0.74	3745.7	50320.00
6	1854.10	32.62	0.570	0.60(0.45)	0.75	4250.8	50240.00
7	1845.19	32.98	0.567	0.60(0.45)	0.75	4308.5	50330.00
8	1739.28	37.25	0.532	0.60(0.45)	0.75	4977.2	50300.00
9	1729.73	37.63	0.528	0.60(0.45)	0.75	5033.6	50280.00
10	1592.43	43.08	0.491	0.60(0.46)	0.76	5818.7	50220.00
11	1566.00	44.38	0.484	0.60(0.46)	0.76	5999.8	300.00
12	1326.62	50.93	0.447	0.60(0.47)	0.78	6583.6	50260.00
13	1218.86	54.00	0.430	0.60(0.47)	0.79	6842.3	50200.00
14	895.99	63.38	0.392	0.60(0.49)	0.81	7608.9	600.00
15	903.94	112.25	0.300	0.60(0.54)	0.90	14295.0	11831.00
16	967.71	135.97	0.271	0.60(0.55)	0.92	17980.1	11530.00
17	1039.53	155.68	0.253	0.60(0.56)	0.93	22126.8	11000.00
18	1137.62	178.22	0.232	0.60(0.57)	0.95	28922.7	10850.00
19	1020.97	199.68	0.224	0.60(0.57)	0.95	33257.3	11910.00
20	958.81	211.71	0.220	0.60(0.57)	0.95	34960.8	12300.00
21	832.14	245.36	0.210	0.60(0.58)	0.96	40669.2	12410.00
22	801.61	253.84	0.208	0.60(0.58)	0.96	42101.4	10600.00
23	787.66	278.29	0.201	0.60(0.58)	0.96	46755.1	12261.00

24	772.95	291.05	0.197	0.60	(0.58)	0.96	48241.7	10410.00
25	758.44	303.23	0.193	0.60	(0.58)	0.96	49343.7	12101.10
26	743.40	312.94	0.190	0.60	(0.58)	0.96	50165.0	10700.00
27	725.65	330.69	0.185	0.60	(0.58)	0.97	51721.7	10200.00
28	709.10	344.08	0.181	0.60	(0.58)	0.97	52660.0	12010.00
29	664.33	373.17	0.175	0.60	(0.58)	0.97	53333.7	10210.00
30	603.05	422.31	0.169	0.60	(0.58)	0.97	53832.8	12000.00
31	561.53	491.84	0.161	0.60	(0.58)	0.97	54417.5	10100.00

=====
=====
END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 133 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 2-YR EV FEB 2023 ROKAMOTO *

FILE NAME: RU02EV33.DAT
TIME/DATE OF STUDY: 13:37 02/09/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 2.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 1.825
- 2) 10.00; 1.217
- 3) 15.00; 0.932
- 4) 20.00; 0.766
- 5) 25.00; 0.662
- 6) 30.00; 0.587
- 7) 40.00; 0.506
- 8) 50.00; 0.449
- 9) 60.00; 0.395
- 10) 90.00; 0.340
- 11) 120.00; 0.286
- 12) 180.00; 0.232
- 13) 360.00; 0.178
- 14) 1200.00; 0.080

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL: IN- / OUT-/PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13112.00 TO NODE 13222.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: S31X02.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	170.57	51.53	0.60 (0.49)	0.81	2407.7	13100.00
2	195.69	91.33	0.60 (0.48)	0.81	3776.8	13000.00
3	193.58	94.68	0.60 (0.48)	0.81	3796.8	13010.00
TOTAL AREA (ACRES) =						3796.8

FLOW PROCESS FROM NODE 13221.00 TO NODE 13222.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: S32X02.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	71.12	52.96	0.60 (0.49)	0.82	1090.8	13200.00
2	65.38	59.51	0.60 (0.50)	0.83	1127.6	13210.00
TOTAL AREA (ACRES) =						1127.6

FLOW PROCESS FROM NODE 13221.00 TO NODE 13222.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	71.12	52.96	0.60 (0.49)	0.82	1090.8	13200.00
2	65.38	59.51	0.60 (0.50)	0.83	1127.6	13210.00
TOTAL AREA (ACRES) =						1127.6

FLOW PROCESS FROM NODE 13112.00 TO NODE 13222.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

=====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	71.12	52.96	0.433	0.60 (0.49)	0.82	1090.8	13200.00
2	65.38	59.51	0.398	0.60 (0.50)	0.83	1127.6	13210.00
LONGEST FLOWPATH FROM NODE 13200.00 TO NODE 13222.00 =							16821.05 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	170.57	51.53	0.441	0.60 (0.49)	0.81	2407.7	13100.00
2	195.69	91.33	0.338	0.60 (0.48)	0.81	3776.8	13000.00
3	193.58	94.68	0.332	0.60 (0.48)	0.81	3796.8	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13222.00 = 32126.49 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	241.00	51.53	0.441	0.60 (0.49)	0.81	3469.1	13100.00
2	242.59	52.96	0.433	0.60 (0.49)	0.81	3547.6	13200.00
3	240.98	59.51	0.398	0.60 (0.49)	0.81	3809.6	13210.00
4	251.19	91.33	0.338	0.60 (0.49)	0.81	4904.4	13000.00
5	248.09	94.68	0.332	0.60 (0.49)	0.81	4924.4	13010.00

TOTAL AREA (ACRES) = 4924.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 251.19 Tc(MIN.) = 91.333
EFFECTIVE AREA(ACRES) = 4904.45 AREA-AVERAGED Fm(INCH/HR) = 0.49
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.81
TOTAL AREA (ACRES) = 4924.4
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13222.00 = 32126.49 FEET.

FLOW PROCESS FROM NODE 13222.00 TO NODE 13222.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 13222.00 TO NODE 13222.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

FLOW PROCESS FROM NODE 13222.00 TO NODE 13301.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 427.51 DOWNSTREAM(FEET) = 382.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 2533.33 CHANNEL SLOPE = 0.0180
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.327

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.40	0.60	0.100	-
USER-DEFINED	-	15.60	0.60	1.000	-
USER-DEFINED	-	0.10	0.60	0.600	-
USER-DEFINED	-	5.30	0.60	1.000	-
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	22.60	0.60	0.100	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.521

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 254.38
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.96
AVERAGE FLOW DEPTH(FEET) = 3.49 TRAVEL TIME(MIN.) = 6.06
Tc(MIN.) = 97.40

SUBAREA AREA(ACRES) = 45.20 SUBAREA RUNOFF(CFS) = 6.36
EFFECTIVE AREA(ACRES) = 4949.65 AREA-AVERAGED Fm(INCH/HR) = 0.49
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.81
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 4969.6 PEAK FLOW RATE(CFS) = 276.97

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 3.60 FLOW VELOCITY(FEET/SEC.) = 7.11
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 97.40

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.327

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.00	0.60	1.000	-
USER-DEFINED	-	0.50	0.60	1.000	-
USER-DEFINED	-	7.40	0.60	0.100	-
USER-DEFINED	-	4.70	0.60	1.000	-
USER-DEFINED	-	2.90	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.596

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 16.50 SUBAREA RUNOFF(CFS) = 1.96

EFFECTIVE AREA(ACRES) = 4966.15 AREA-AVERAGED Fm(INCH/HR) = 0.49

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.81

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 4986.1 PEAK FLOW RATE(CFS) = 278.93

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 97.40

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.327

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.30	0.60	1.000	-
USER-DEFINED	-	0.20	0.60	0.100	-
USER-DEFINED	-	5.30	0.60	1.000	-
USER-DEFINED	-	0.30	0.60	1.000	-

USER-DEFINED - 0.20 0.60 1.000 -
 USER-DEFINED - 0.60 0.60 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.977
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 SUBAREA AREA (ACRES) = 7.90 SUBAREA RUNOFF (CFS) = 0.05
 EFFECTIVE AREA (ACRES) = 4974.05 AREA-AVERAGED Fm (INCH/HR) = 0.49
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.81
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA (ACRES) = 4994.0 PEAK FLOW RATE (CFS) = 278.98

 FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 97.40
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.327
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	4.30	0.60	1.000	-
USER-DEFINED	-	0.80	0.60	1.000	-
USER-DEFINED	-	1.10	0.60	1.000	-
USER-DEFINED	-	6.90	0.60	1.000	-
USER-DEFINED	-	7.90	0.60	1.000	-
USER-DEFINED	-	1.00	0.60	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 SUBAREA AREA (ACRES) = 22.00 SUBAREA RUNOFF (CFS) = 0.00
 EFFECTIVE AREA (ACRES) = 4996.05 AREA-AVERAGED Fm (INCH/HR) = 0.49
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.81
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA (ACRES) = 5016.0 PEAK FLOW RATE (CFS) = 278.98

 FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 97.40
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.327
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.40	0.60	1.000	-
USER-DEFINED	-	14.60	0.60	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 SUBAREA AREA (ACRES) = 15.00 SUBAREA RUNOFF (CFS) = 0.00
 EFFECTIVE AREA (ACRES) = 5011.05 AREA-AVERAGED Fm (INCH/HR) = 0.49

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.81
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA (ACRES) = 5031.0 PEAK FLOW RATE (CFS) = 278.98

 FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1<<<<<

 FLOW PROCESS FROM NODE 31100.00 TO NODE 31101.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<

>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH (FEET) = 317.00
 ELEVATION DATA: UPSTREAM (FEET) = 801.00 DOWNSTREAM (FEET) = 685.00

Tc = K * [(LENGTH ** 3.00) / (ELEVATION CHANGE)] ** 0.20
 SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 8.641
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 1.382
 SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL, BROADLEAF"	-	0.50	0.60	1.000	65	8.64
NATURAL FAIR COVER "OPEN BRUSH"	-	0.30	0.60	1.000	65	8.64
NATURAL FAIR COVER "OPEN BRUSH"	-	0.30	0.60	1.000	65	8.64

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA RUNOFF (CFS) = 0.77
 TOTAL AREA (ACRES) = 1.10 PEAK FLOW RATE (CFS) = 0.77

 FLOW PROCESS FROM NODE 31101.00 TO NODE 31102.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 685.00 DOWNSTREAM (FEET) = 655.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 135.00 CHANNEL SLOPE = 0.2222
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 1.324
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.50	0.60	1.000	-
USER-DEFINED	-	0.10	0.60	1.000	-
USER-DEFINED	-	0.70	0.60	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 1.20
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.66

AVERAGE FLOW DEPTH(FEET) = 0.29 TRAVEL TIME(MIN.) = 0.48
Tc(MIN.) = 9.12
SUBAREA AREA(ACRES) = 1.30 SUBAREA RUNOFF(CFS) = 0.85
EFFECTIVE AREA(ACRES) = 2.40 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 2.4 PEAK FLOW RATE(CFS) = 1.56

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.32 FLOW VELOCITY(FEET/SEC.) = 4.99
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31102.00 = 452.00 FEET.

FLOW PROCESS FROM NODE 31102.00 TO NODE 31103.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 655.00 DOWNSTREAM(FEET) = 630.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 203.00 CHANNEL SLOPE = 0.1232
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 1.230

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.30	0.60	1.000	-
USER-DEFINED	-	0.10	0.60	1.000	-
USER-DEFINED	-	1.90	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2.22
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.41
AVERAGE FLOW DEPTH(FEET) = 0.41 TRAVEL TIME(MIN.) = 0.77
Tc(MIN.) = 9.89
SUBAREA AREA(ACRES) = 2.30 SUBAREA RUNOFF(CFS) = 1.31
EFFECTIVE AREA(ACRES) = 4.70 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 4.7 PEAK FLOW RATE(CFS) = 2.67

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.44 FLOW VELOCITY(FEET/SEC.) = 4.60
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31103.00 = 655.00 FEET.

FLOW PROCESS FROM NODE 31103.00 TO NODE 31104.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 630.00 DOWNSTREAM(FEET) = 605.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 321.00 CHANNEL SLOPE = 0.0779
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 1.149

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.10	0.60	1.000	-

USER-DEFINED - 2.50 0.60 1.000 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3.56
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.11
AVERAGE FLOW DEPTH(FEET) = 0.54 TRAVEL TIME(MIN.) = 1.30
Tc(MIN.) = 11.19
SUBAREA AREA(ACRES) = 3.60 SUBAREA RUNOFF(CFS) = 1.78
EFFECTIVE AREA(ACRES) = 8.30 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 8.3 PEAK FLOW RATE(CFS) = 4.10

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.56 FLOW VELOCITY(FEET/SEC.) = 4.33
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31104.00 = 976.00 FEET.

FLOW PROCESS FROM NODE 31104.00 TO NODE 31105.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 605.00 DOWNSTREAM(FEET) = 585.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 288.00 CHANNEL SLOPE = 0.0694
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 1.087

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.70	0.60	1.000	-
USER-DEFINED	-	0.60	0.60	1.000	-
USER-DEFINED	-	3.00	0.60	1.000	-
USER-DEFINED	-	2.10	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5.51
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.43
AVERAGE FLOW DEPTH(FEET) = 0.64 TRAVEL TIME(MIN.) = 1.08
Tc(MIN.) = 12.27
SUBAREA AREA(ACRES) = 6.40 SUBAREA RUNOFF(CFS) = 2.81
EFFECTIVE AREA(ACRES) = 14.70 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 14.7 PEAK FLOW RATE(CFS) = 6.45

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.68 FLOW VELOCITY(FEET/SEC.) = 4.62
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31105.00 = 1264.00 FEET.

FLOW PROCESS FROM NODE 31105.00 TO NODE 31106.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 585.00 DOWNSTREAM(FEET) = 560.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 344.00 CHANNEL SLOPE = 0.0727
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 1.022
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.60	0.60	1.000	-
USER-DEFINED	-	2.80	0.60	1.000	-
USER-DEFINED	-	0.60	0.60	1.000	-
USER-DEFINED	-	0.10	0.60	1.000	-
USER-DEFINED	-	2.60	0.60	1.000	-
USER-DEFINED	-	4.10	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 8.51
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.03
 AVERAGE FLOW DEPTH (FEET) = 0.75 TRAVEL TIME (MIN.) = 1.14
 Tc (MIN.) = 13.41
 SUBAREA AREA (ACRES) = 10.80 SUBAREA RUNOFF (CFS) = 4.11
 EFFECTIVE AREA (ACRES) = 25.50 AREA-AVERAGED Fm (INCH/HR) = 0.60
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 25.5 PEAK FLOW RATE (CFS) = 9.70

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 0.79 FLOW VELOCITY (FEET/SEC.) = 5.20
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31106.00 = 1608.00 FEET.

 FLOW PROCESS FROM NODE 31106.00 TO NODE 31107.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 560.00 DOWNSTREAM (FEET) = 530.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 619.00 CHANNEL SLOPE = 0.0485
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.911
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.80	0.60	1.000	-
USER-DEFINED	-	1.90	0.60	1.000	-
USER-DEFINED	-	1.50	0.60	1.000	-
USER-DEFINED	-	8.20	0.60	1.000	-
USER-DEFINED	-	2.70	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 11.83
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.67
 AVERAGE FLOW DEPTH (FEET) = 0.92 TRAVEL TIME (MIN.) = 2.21
 Tc (MIN.) = 15.62
 SUBAREA AREA (ACRES) = 15.10 SUBAREA RUNOFF (CFS) = 4.23
 EFFECTIVE AREA (ACRES) = 40.60 AREA-AVERAGED Fm (INCH/HR) = 0.60
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 40.6 PEAK FLOW RATE (CFS) = 11.38

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 0.90 FLOW VELOCITY (FEET/SEC.) = 4.65

LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31107.00 = 2227.00 FEET.

 FLOW PROCESS FROM NODE 31107.00 TO NODE 31108.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 530.00 DOWNSTREAM (FEET) = 515.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 377.00 CHANNEL SLOPE = 0.0398
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.865
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.50	0.60	1.000	-
USER-DEFINED	-	6.50	0.60	1.000	-
USER-DEFINED	-	1.30	0.60	1.000	-
USER-DEFINED	-	1.10	0.60	1.000	-
USER-DEFINED	-	5.50	0.60	1.000	-
USER-DEFINED	-	3.40	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 13.57
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.50
 AVERAGE FLOW DEPTH (FEET) = 1.00 TRAVEL TIME (MIN.) = 1.40
 Tc (MIN.) = 17.02
 SUBAREA AREA (ACRES) = 18.30 SUBAREA RUNOFF (CFS) = 4.37
 EFFECTIVE AREA (ACRES) = 58.90 AREA-AVERAGED Fm (INCH/HR) = 0.60
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 58.9 PEAK FLOW RATE (CFS) = 14.06

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 1.02 FLOW VELOCITY (FEET/SEC.) = 4.53
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31108.00 = 2604.00 FEET.

 FLOW PROCESS FROM NODE 31108.00 TO NODE 31109.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 515.00 DOWNSTREAM (FEET) = 490.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 520.00 CHANNEL SLOPE = 0.0481
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.808
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.70	0.60	1.000	-
USER-DEFINED	-	2.20	0.60	1.000	-
USER-DEFINED	-	3.10	0.60	1.000	-
USER-DEFINED	-	0.90	0.60	1.000	-
USER-DEFINED	-	7.40	0.60	1.000	-
USER-DEFINED	-	0.30	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 15.43
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.02
 AVERAGE FLOW DEPTH(FEET) = 1.01 TRAVEL TIME(MIN.) = 1.73
 Tc(MIN.) = 18.74
 SUBAREA AREA(ACRES) = 14.60 SUBAREA RUNOFF(CFS) = 2.73
 EFFECTIVE AREA(ACRES) = 73.50 AREA-AVERAGED Fm(INCH/HR) = 0.60
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 73.5 PEAK FLOW RATE(CFS) = 14.06
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 0.98 FLOW VELOCITY(FEET/SEC.) = 4.89
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31109.00 = 3124.00 FEET.

 FLOW PROCESS FROM NODE 31109.00 TO NODE 31109.00 IS CODE = 81

 >>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
 =====

MAINLINE Tc(MIN.) = 18.74
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.808
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	11.40	0.60	1.000	-
USER-DEFINED	-	8.90	0.60	1.000	-
USER-DEFINED	-	1.90	0.60	1.000	-
USER-DEFINED	-	9.20	0.60	1.000	-
USER-DEFINED	-	1.40	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 32.80 SUBAREA RUNOFF(CFS) = 6.14
 EFFECTIVE AREA(ACRES) = 106.30 AREA-AVERAGED Fm(INCH/HR) = 0.60
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 106.3 PEAK FLOW RATE(CFS) = 19.89

 FLOW PROCESS FROM NODE 31109.00 TO NODE 31110.00 IS CODE = 51

 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
 =====

ELEVATION DATA: UPSTREAM(FEET) = 490.00 DOWNSTREAM(FEET) = 432.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1420.00 CHANNEL SLOPE = 0.0408
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.695
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.80	0.60	1.000	-
USER-DEFINED	-	0.60	0.60	1.000	-
USER-DEFINED	-	0.10	0.60	0.900	-
USER-DEFINED	-	1.30	0.60	1.000	-
USER-DEFINED	-	4.00	0.60	1.000	-
USER-DEFINED	-	1.50	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 20.25
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.04
 AVERAGE FLOW DEPTH(FEET) = 1.16 TRAVEL TIME(MIN.) = 4.69
 Tc(MIN.) = 23.43
 SUBAREA AREA(ACRES) = 8.30 SUBAREA RUNOFF(CFS) = 0.71
 EFFECTIVE AREA(ACRES) = 114.60 AREA-AVERAGED Fm(INCH/HR) = 0.60
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 114.6 PEAK FLOW RATE(CFS) = 19.89
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 1.15 FLOW VELOCITY(FEET/SEC.) = 5.02
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31110.00 = 4544.00 FEET.

 FLOW PROCESS FROM NODE 31110.00 TO NODE 31110.00 IS CODE = 81

 >>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
 =====

MAINLINE Tc(MIN.) = 23.43
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.695
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.30	0.60	1.000	-
USER-DEFINED	-	9.60	0.60	1.000	-
USER-DEFINED	-	0.40	0.60	0.900	-
USER-DEFINED	-	6.20	0.60	1.000	-
USER-DEFINED	-	3.90	0.60	1.000	-
USER-DEFINED	-	1.40	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.998
 SUBAREA AREA(ACRES) = 21.80 SUBAREA RUNOFF(CFS) = 1.88
 EFFECTIVE AREA(ACRES) = 136.40 AREA-AVERAGED Fm(INCH/HR) = 0.60
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 136.4 PEAK FLOW RATE(CFS) = 19.89
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 31110.00 TO NODE 13301.00 IS CODE = 51

 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
 =====

ELEVATION DATA: UPSTREAM(FEET) = 432.00 DOWNSTREAM(FEET) = 382.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1847.00 CHANNEL SLOPE = 0.0271
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.582
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	4.90	0.60	1.000	-
USER-DEFINED	-	1.50	0.60	1.000	-
USER-DEFINED	-	0.60	0.60	0.900	-
USER-DEFINED	-	2.50	0.60	1.000	-
USER-DEFINED	-	5.30	0.60	1.000	-

USER-DEFINED - 3.30 0.60 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.997
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 19.91
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.31
 AVERAGE FLOW DEPTH(FEET) = 1.24 TRAVEL TIME(MIN.) = 7.14
 Tc(MIN.) = 30.57
 SUBAREA AREA(ACRES) = 18.10 SUBAREA RUNOFF(CFS) = 0.03
 EFFECTIVE AREA(ACRES) = 154.50 AREA-AVERAGED Fm(INCH/HR) = 0.60
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA(ACRES) = 154.5 PEAK FLOW RATE(CFS) = 19.89
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 1.24 FLOW VELOCITY(FEET/SEC.) = 4.31
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 13301.00 = 6391.00 FEET.

 FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 11

 >>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<
 =====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19.89	30.57	0.582	0.60(0.60)	1.00	154.5	31100.00

 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 13301.00 = 6391.00 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	247.43	57.64	0.408	0.60(0.49)	0.81	3575.7	13100.00
2	248.10	59.06	0.400	0.60(0.49)	0.81	3654.2	13200.00
3	253.89	65.62	0.385	0.60(0.49)	0.81	3916.2	13210.00
4	278.98	97.40	0.327	0.60(0.49)	0.81	5011.0	13000.00
5	275.15	100.77	0.321	0.60(0.49)	0.81	5031.0	13010.00

 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	207.33	30.57	0.582	0.60(0.50)	0.83	2050.9	31100.00
2	261.36	57.64	0.408	0.60(0.49)	0.82	3730.2	13100.00
3	261.77	59.06	0.400	0.60(0.49)	0.82	3808.7	13200.00
4	267.03	65.62	0.385	0.60(0.49)	0.82	4070.7	13210.00
5	290.14	97.40	0.327	0.60(0.49)	0.82	5165.5	13000.00
6	286.10	100.77	0.321	0.60(0.49)	0.82	5185.5	13010.00

 TOTAL AREA(ACRES) = 5185.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
 PEAK FLOW RATE(CFS) = 290.14 Tc(MIN.) = 97.396
 EFFECTIVE AREA(ACRES) = 5165.55 AREA-AVERAGED Fm(INCH/HR) = 0.49
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.82

TOTAL AREA(ACRES) = 5185.5
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

 FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1<<<<<
 =====

 FLOW PROCESS FROM NODE 13301.00 TO NODE 13302.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<
 =====

ELEVATION DATA: UPSTREAM(FEET) = 382.00 DOWNSTREAM(FEET) = 375.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1141.09 CHANNEL SLOPE = 0.0061
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.320

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.20	0.60	1.000	-
USER-DEFINED	-	0.60	0.60	1.000	-
USER-DEFINED	-	0.90	0.60	1.000	-
USER-DEFINED	-	4.80	0.60	1.000	-
USER-DEFINED	-	1.90	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 290.14
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.81
 AVERAGE FLOW DEPTH(FEET) = 4.48 TRAVEL TIME(MIN.) = 3.95
 Tc(MIN.) = 101.35

SUBAREA AREA(ACRES) = 9.40 SUBAREA RUNOFF(CFS) = 0.00
 EFFECTIVE AREA(ACRES) = 5174.95 AREA-AVERAGED Fm(INCH/HR) = 0.49
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.82

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 5194.9 PEAK FLOW RATE(CFS) = 290.14
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 4.48 FLOW VELOCITY(FEET/SEC.) = 4.81
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13302.00 = 35800.91 FEET.

 FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
 =====

MAINLINE Tc(MIN.) = 101.35
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.320

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

USER-DEFINED - 13.80 0.60 1.000 -
 USER-DEFINED - 2.60 0.60 1.000 -
 USER-DEFINED - 1.10 0.60 0.100 -
 USER-DEFINED - 3.50 0.60 0.900 -
 USER-DEFINED - 6.90 0.60 1.000 -
 USER-DEFINED - 0.20 0.60 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.952
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 SUBAREA AREA (ACRES) = 28.10 SUBAREA RUNOFF (CFS) = 0.39
 EFFECTIVE AREA (ACRES) = 5203.05 AREA-AVERAGED Fm (INCH/HR) = 0.49
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.82
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA (ACRES) = 5223.0 PEAK FLOW RATE (CFS) = 290.14
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 101.35
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.320
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.10	0.60	1.000	-
USER-DEFINED	-	0.10	0.60	0.100	-
USER-DEFINED	-	2.40	0.60	0.900	-
USER-DEFINED	-	0.50	0.60	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.894
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 SUBAREA AREA (ACRES) = 3.10 SUBAREA RUNOFF (CFS) = 0.09
 EFFECTIVE AREA (ACRES) = 5206.15 AREA-AVERAGED Fm (INCH/HR) = 0.49
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.82
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA (ACRES) = 5226.1 PEAK FLOW RATE (CFS) = 290.14
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 101.35
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.320
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.10	0.60	1.000	-
USER-DEFINED	-	2.60	0.60	1.000	-
USER-DEFINED	-	3.10	0.60	1.000	-
USER-DEFINED	-	0.40	0.60	1.000	-

USER-DEFINED - 0.20 0.60 1.000 -
 USER-DEFINED - 13.80 0.60 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 SUBAREA AREA (ACRES) = 20.20 SUBAREA RUNOFF (CFS) = 0.00
 EFFECTIVE AREA (ACRES) = 5226.35 AREA-AVERAGED Fm (INCH/HR) = 0.49
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.82
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA (ACRES) = 5246.3 PEAK FLOW RATE (CFS) = 290.14
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 101.35
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.320
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	34.60	0.60	1.000	-
USER-DEFINED	-	2.40	0.60	1.000	-
USER-DEFINED	-	22.60	0.60	1.000	-
USER-DEFINED	-	11.60	0.60	1.000	-
USER-DEFINED	-	0.40	0.60	0.200	-
USER-DEFINED	-	4.80	0.60	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.996
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 SUBAREA AREA (ACRES) = 76.40 SUBAREA RUNOFF (CFS) = 0.09
 EFFECTIVE AREA (ACRES) = 5302.75 AREA-AVERAGED Fm (INCH/HR) = 0.49
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.82
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA (ACRES) = 5322.7 PEAK FLOW RATE (CFS) = 290.14
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 101.35
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.320
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.60	0.60	1.000	-
USER-DEFINED	-	46.40	0.60	1.000	-
USER-DEFINED	-	0.10	0.60	0.200	-
USER-DEFINED	-	60.70	0.60	1.000	-
USER-DEFINED	-	5.80	0.60	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 SUBAREA AREA (ACRES) = 114.60 SUBAREA RUNOFF (CFS) = 0.02
 EFFECTIVE AREA (ACRES) = 5417.35 AREA-AVERAGED Fm (INCH/HR) = 0.49
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.82
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA (ACRES) = 5437.3 PEAK FLOW RATE (CFS) = 290.14
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13302.00 TO NODE 13303.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 375.00 DOWNSTREAM (FEET) = 355.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 2193.96 CHANNEL SLOPE = 0.0091
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00
 CHANNEL FLOW THRU SUBAREA (CFS) = 290.14
 FLOW VELOCITY (FEET/SEC.) = 5.58 FLOW DEPTH (FEET) = 4.16
 TRAVEL TIME (MIN.) = 6.55 Tc (MIN.) = 107.90
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13303.00 = 37994.87 FEET.

 FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 107.90
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.308
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	0.40	0.60	1.000	-
USER-DEFINED	-	0.80	0.60	1.000	-
USER-DEFINED	-	1.40	0.60	0.100	-
USER-DEFINED	-	2.60	0.60	1.000	-
USER-DEFINED	-	2.20	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.834
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 SUBAREA AREA (ACRES) = 7.60 SUBAREA RUNOFF (CFS) = 0.35
 EFFECTIVE AREA (ACRES) = 5424.95 AREA-AVERAGED Fm (INCH/HR) = 0.49
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.82
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA (ACRES) = 5444.9 PEAK FLOW RATE (CFS) = 290.14
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 107.90
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.308
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	3.10	0.60	1.000	-
USER-DEFINED	-	3.40	0.60	1.000	-
USER-DEFINED	-	0.50	0.60	1.000	-
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	3.60	0.60	0.100	-
USER-DEFINED	-	4.00	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.781
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA (ACRES) = 14.80 SUBAREA RUNOFF (CFS) = 0.90
 EFFECTIVE AREA (ACRES) = 5439.75 AREA-AVERAGED Fm (INCH/HR) = 0.49
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.82
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA (ACRES) = 5459.7 PEAK FLOW RATE (CFS) = 290.14
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 107.90
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.308
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	14.60	0.60	1.000	-
USER-DEFINED	-	6.30	0.60	1.000	-
USER-DEFINED	-	3.70	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 SUBAREA AREA (ACRES) = 24.60 SUBAREA RUNOFF (CFS) = 0.00
 EFFECTIVE AREA (ACRES) = 5464.35 AREA-AVERAGED Fm (INCH/HR) = 0.49
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA (ACRES) = 5484.3 PEAK FLOW RATE (CFS) = 290.14
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 107.90
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.308
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
USER-DEFINED	-	0.50	0.60	1.000	-
USER-DEFINED	-	0.30	0.60	0.100	-
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	0.80	0.60	0.900	-
USER-DEFINED	-	1.60	0.60	1.000	-
USER-DEFINED	-	31.90	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.990
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 35.30 SUBAREA RUNOFF(CFS) = 0.10
EFFECTIVE AREA(ACRES) = 5499.65 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 5519.6 PEAK FLOW RATE(CFS) = 290.14
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 107.90
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.308
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.70	0.60	0.100	-
USER-DEFINED	-	0.30	0.60	1.000	-
USER-DEFINED	-	2.60	0.60	0.900	-
USER-DEFINED	-	5.50	0.60	1.000	-
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	0.20	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.830
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 10.50 SUBAREA RUNOFF(CFS) = 0.50
EFFECTIVE AREA(ACRES) = 5510.15 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 5530.1 PEAK FLOW RATE(CFS) = 290.14
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 107.90
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.308
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.30	0.60	0.900	-

USER-DEFINED	-	0.30	0.60	1.000	-
USER-DEFINED	-	0.20	0.60	0.100	-
USER-DEFINED	-	0.30	0.60	1.000	-
USER-DEFINED	-	6.50	0.60	0.900	-
USER-DEFINED	-	3.00	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.917
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 11.60 SUBAREA RUNOFF(CFS) = 0.27
EFFECTIVE AREA(ACRES) = 5521.75 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 5541.7 PEAK FLOW RATE(CFS) = 290.14
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13303.00 TO NODE 13304.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 355.00 DOWNSTREAM(FEET) = 350.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 925.40 CHANNEL SLOPE = 0.0054
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.302
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	0.50	0.60	1.000	-
USER-DEFINED	-	1.10	0.60	1.000	-
USER-DEFINED	-	0.30	0.60	1.000	-
USER-DEFINED	-	1.10	0.60	1.000	-
USER-DEFINED	-	3.50	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 290.14
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.59
AVERAGE FLOW DEPTH(FEET) = 4.59 TRAVEL TIME(MIN.) = 3.36
Tc(MIN.) = 111.26
SUBAREA AREA(ACRES) = 6.70 SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 5528.45 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 5548.4 PEAK FLOW RATE(CFS) = 290.14
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 4.59 FLOW VELOCITY(FEET/SEC.) = 4.59
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13304.00 = 38920.27 FEET.

FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 111.26

* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.302

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.40	0.60	1.000	-
USER-DEFINED	-	4.80	0.60	1.000	-
USER-DEFINED	-	0.90	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA (ACRES) = 7.10 SUBAREA RUNOFF (CFS) = 0.00

EFFECTIVE AREA (ACRES) = 5535.55 AREA-AVERAGED Fm (INCH/HR) = 0.50

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA (ACRES) = 5555.5 PEAK FLOW RATE (CFS) = 290.14

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 111.26

* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.302

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.80	0.60	1.000	-
USER-DEFINED	-	1.70	0.60	1.000	-
USER-DEFINED	-	9.40	0.60	1.000	-
USER-DEFINED	-	1.20	0.60	1.000	-
USER-DEFINED	-	0.10	0.60	0.900	-
USER-DEFINED	-	2.60	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA (ACRES) = 22.80 SUBAREA RUNOFF (CFS) = 0.00

EFFECTIVE AREA (ACRES) = 5558.35 AREA-AVERAGED Fm (INCH/HR) = 0.50

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA (ACRES) = 5578.3 PEAK FLOW RATE (CFS) = 290.14

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 111.26

* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.302

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	0.30	0.60	1.000	-
USER-DEFINED	-	0.20	0.60	0.900	-
USER-DEFINED	-	2.70	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.994

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA (ACRES) = 3.40 SUBAREA RUNOFF (CFS) = 0.01

EFFECTIVE AREA (ACRES) = 5561.75 AREA-AVERAGED Fm (INCH/HR) = 0.50

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA (ACRES) = 5581.7 PEAK FLOW RATE (CFS) = 290.14

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13304.00 TO NODE 13305.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM (FEET) = 350.00 DOWNSTREAM (FEET) = 315.00

CHANNEL LENGTH THRU SUBAREA (FEET) = 2966.27 CHANNEL SLOPE = 0.0118

CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00

* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.287

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.70	0.60	1.000	-
USER-DEFINED	-	0.60	0.60	1.000	-
USER-DEFINED	-	0.10	0.60	1.000	-
USER-DEFINED	-	0.40	0.60	1.000	-
USER-DEFINED	-	2.20	0.60	1.000	-
USER-DEFINED	-	4.20	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 290.14

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.15

AVERAGE FLOW DEPTH (FEET) = 3.96 TRAVEL TIME (MIN.) = 8.03

Tc (MIN.) = 119.29

SUBAREA AREA (ACRES) = 9.20 SUBAREA RUNOFF (CFS) = 0.00

EFFECTIVE AREA (ACRES) = 5570.95 AREA-AVERAGED Fm (INCH/HR) = 0.50

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA (ACRES) = 5590.9 PEAK FLOW RATE (CFS) = 290.14

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 3.96 FLOW VELOCITY (FEET/SEC.) = 6.15

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 119.29

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.287

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.10	0.60	1.000	-
USER-DEFINED	-	2.30	0.60	1.000	-
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	6.90	0.60	1.000	-
USER-DEFINED	-	0.70	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 18.20 SUBAREA RUNOFF(CFS) = 0.00

EFFECTIVE AREA(ACRES) = 5589.15 AREA-AVERAGED Fm(INCH/HR) = 0.50

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 5609.1 PEAK FLOW RATE(CFS) = 290.14

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 119.29

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.287

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	18.40	0.60	1.000	-
USER-DEFINED	-	1.20	0.60	1.000	-
USER-DEFINED	-	0.10	0.60	1.000	-
USER-DEFINED	-	26.60	0.60	1.000	-
USER-DEFINED	-	3.90	0.60	0.100	-
USER-DEFINED	-	3.00	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.934

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 53.20 SUBAREA RUNOFF(CFS) = 0.91

EFFECTIVE AREA(ACRES) = 5642.35 AREA-AVERAGED Fm(INCH/HR) = 0.50

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 5662.3 PEAK FLOW RATE(CFS) = 290.14

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 119.29

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.287

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.10	0.60	1.000	-
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	14.00	0.60	1.000	-
USER-DEFINED	-	4.30	0.60	0.100	-
USER-DEFINED	-	5.30	0.60	1.000	-
USER-DEFINED	-	2.70	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.860

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 27.60 SUBAREA RUNOFF(CFS) = 1.00

EFFECTIVE AREA(ACRES) = 5669.95 AREA-AVERAGED Fm(INCH/HR) = 0.50

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 5689.9 PEAK FLOW RATE(CFS) = 290.14

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 119.29

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.287

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	3.20	0.60	1.000	-
USER-DEFINED	-	6.10	0.60	1.000	-
USER-DEFINED	-	7.50	0.60	0.900	-
USER-DEFINED	-	5.40	0.60	1.000	-
USER-DEFINED	-	1.60	0.60	1.000	-
USER-DEFINED	-	1.90	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.971

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 25.70 SUBAREA RUNOFF(CFS) = 0.19

EFFECTIVE AREA(ACRES) = 5695.65 AREA-AVERAGED Fm(INCH/HR) = 0.50

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 5715.6 PEAK FLOW RATE(CFS) = 290.14

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 119.29

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.287

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	2.00	0.60	0.100	-
USER-DEFINED	-	3.70	0.60	1.000	-
USER-DEFINED	-	2.10	0.60	1.000	-
USER-DEFINED	-	2.60	0.60	0.900	-
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	0.10	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.807

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 10.70 SUBAREA RUNOFF(CFS) = 0.53

EFFECTIVE AREA(ACRES) = 5706.35 AREA-AVERAGED Fm(INCH/HR) = 0.50

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 5726.3 PEAK FLOW RATE(CFS) = 290.14

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 119.29

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.287

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.50	0.60	1.000	-
USER-DEFINED	-	8.20	0.60	0.900	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.906

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 8.70 SUBAREA RUNOFF(CFS) = 0.21

EFFECTIVE AREA(ACRES) = 5715.05 AREA-AVERAGED Fm(INCH/HR) = 0.50

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 5735.0 PEAK FLOW RATE(CFS) = 290.14

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 3A02EVRL.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap (DECIMAL)	Ae (ACRES)	HEADWATER NODE
------------------	------------	--------------	---------------------	-----------------	---------------	-------------------

1	253.57	16.02	0.60(0.26)	0.43	423.9	120.00
2	249.96	16.56	0.60(0.26)	0.43	431.7	110.00
3	195.31	25.12	0.60(0.25)	0.42	498.0	100.00
4	160.80	32.93	0.60(0.26)	0.43	510.2	150.00
TOTAL AREA(ACRES) =						510.2

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

=====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	207.33	54.40	0.425	0.60(0.51)	0.85	2600.4	31100.00
2	261.36	80.13	0.358	0.60(0.50)	0.84	4279.7	13100.00
3	261.77	81.53	0.356	0.60(0.50)	0.84	4358.2	13200.00
4	267.03	87.97	0.344	0.60(0.50)	0.84	4620.2	13210.00
5	290.14	119.29	0.287	0.60(0.50)	0.83	5715.1	13000.00
6	286.10	122.76	0.284	0.60(0.50)	0.83	5735.0	13010.00
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.							

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	253.57	16.02	0.898	0.60(0.26)	0.43	423.9	120.00
2	249.96	16.56	0.880	0.60(0.26)	0.43	431.7	110.00
3	195.31	25.12	0.660	0.60(0.25)	0.42	498.0	100.00
4	160.80	32.93	0.563	0.60(0.26)	0.43	510.2	150.00
LONGEST FLOWPATH FROM NODE 150.00 TO NODE 13305.00 = 9867.00 FEET.							

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	460.90	16.02	0.898	0.60(0.42)	0.70	1189.6	120.00
2	457.29	16.56	0.880	0.60(0.42)	0.70	1223.5	110.00
3	402.64	25.12	0.660	0.60(0.44)	0.73	1698.7	100.00
4	327.04	32.93	0.563	0.60(0.45)	0.75	2084.4	150.00
5	328.73	54.40	0.425	0.60(0.47)	0.79	3110.6	31100.00
6	363.59	80.13	0.358	0.60(0.48)	0.79	4789.9	13100.00
7	363.26	81.53	0.356	0.60(0.48)	0.79	4868.4	13200.00
8	365.16	87.97	0.344	0.60(0.48)	0.80	5130.4	13210.00
9	372.15	119.29	0.287	0.60(0.48)	0.80	6225.3	13000.00
10	367.04	122.76	0.284	0.60(0.48)	0.80	6245.2	13010.00
TOTAL AREA(ACRES) = 6245.2							

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 460.90 Tc(MIN.) = 16.018

EFFECTIVE AREA(ACRES) = 1189.63 AREA-AVERAGED Fm(INCH/HR) = 0.42

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.79

TOTAL AREA(ACRES) = 6245.2

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<

```

=====
*****
FLOW PROCESS FROM NODE 13305.00 TO NODE 13306.00 IS CODE = 51
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
-----
ELEVATION DATA: UPSTREAM(FEET) = 315.00 DOWNSTREAM(FEET) = 245.50
CHANNEL LENGTH THRU SUBAREA(FEET) = 4408.41 CHANNEL SLOPE = 0.0158
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.654
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.40 0.60 1.000 -
USER-DEFINED - 9.20 0.60 1.000 -
USER-DEFINED - 1.00 0.60 1.000 -
USER-DEFINED - 1.30 0.60 1.000 -
USER-DEFINED - 2.40 0.60 1.000 -
USER-DEFINED - 4.10 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 461.35
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.70
AVERAGE FLOW DEPTH(FEET) = 4.47 TRAVEL TIME(MIN.) = 9.54
Tc(MIN.) = 25.56
SUBAREA AREA(ACRES) = 18.40 SUBAREA RUNOFF(CFS) = 0.89
EFFECTIVE AREA(ACRES) = 1208.03 AREA-AVERAGED Fm(INCH/HR) = 0.42
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.71
TOTAL AREA(ACRES) = 6263.6 PEAK FLOW RATE(CFS) = 460.90
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 4.47 FLOW VELOCITY(FEET/SEC.) = 7.70
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13306.00 = 46294.95 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
-----
MAINLINE Tc(MIN.) = 25.56
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.654
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 19.20 0.60 1.000 -
USER-DEFINED - 20.90 0.60 1.000 -
USER-DEFINED - 4.10 0.60 1.000 -
USER-DEFINED - 0.50 0.60 1.000 -
USER-DEFINED - 4.30 0.50 1.000 -
USER-DEFINED - 0.60 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.59
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 49.60 SUBAREA RUNOFF(CFS) = 2.79
EFFECTIVE AREA(ACRES) = 1257.63 AREA-AVERAGED Fm(INCH/HR) = 0.43

```

```

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.72
TOTAL AREA(ACRES) = 6313.2 PEAK FLOW RATE(CFS) = 460.90
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
*****
FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
-----
MAINLINE Tc(MIN.) = 25.56
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.654
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.80 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 0.80 SUBAREA RUNOFF(CFS) = 0.04
EFFECTIVE AREA(ACRES) = 1258.43 AREA-AVERAGED Fm(INCH/HR) = 0.43
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.72
TOTAL AREA(ACRES) = 6314.0 PEAK FLOW RATE(CFS) = 460.90
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
-----
MAINLINE Tc(MIN.) = 25.56
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.654
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.10 0.60 0.850 -
USER-DEFINED - 0.10 0.60 1.000 -
USER-DEFINED - 0.10 0.60 1.000 -
USER-DEFINED - 0.20 0.60 1.000 -
USER-DEFINED - 0.40 0.60 0.850 -
USER-DEFINED - 0.40 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.942
SUBAREA AREA(ACRES) = 1.30 SUBAREA RUNOFF(CFS) = 0.10
EFFECTIVE AREA(ACRES) = 1259.73 AREA-AVERAGED Fm(INCH/HR) = 0.43
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.72
TOTAL AREA(ACRES) = 6315.3 PEAK FLOW RATE(CFS) = 460.90
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
-----
MAINLINE Tc(MIN.) = 25.56
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.654
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.80 0.60 0.900 -

```

```

USER-DEFINED      -      0.80      0.60      1.000      -
USER-DEFINED      -      1.00      0.60      1.000      -
USER-DEFINED      -      1.10      0.60      1.000      -
USER-DEFINED      -      1.10      0.60      0.100      -
USER-DEFINED      -      2.80      0.60      0.900      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.822
SUBAREA AREA (ACRES) = 7.60      SUBAREA RUNOFF (CFS) = 1.10
EFFECTIVE AREA (ACRES) = 1267.33      AREA-AVERAGED Fm (INCH/HR) = 0.43
AREA-AVERAGED Fp (INCH/HR) = 0.60      AREA-AVERAGED Ap = 0.72
TOTAL AREA (ACRES) = 6322.9      PEAK FLOW RATE (CFS) = 460.90
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

```

```

=====
MAINLINE Tc (MIN.) = 25.56
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.654
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/      SCS SOIL      AREA      Fp      Ap      SCS
LAND USE      GROUP      (ACRES)      (INCH/HR)      (DECIMAL)      CN
USER-DEFINED      -      3.50      0.60      0.100      -
USER-DEFINED      -      5.00      0.60      1.000      -
USER-DEFINED      -      6.70      0.60      0.900      -
USER-DEFINED      -      7.80      0.60      1.000      -
USER-DEFINED      -      10.80      0.60      1.000      -
USER-DEFINED      -      13.80      0.60      0.100      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.659
SUBAREA AREA (ACRES) = 47.60      SUBAREA RUNOFF (CFS) = 11.07
EFFECTIVE AREA (ACRES) = 1314.93      AREA-AVERAGED Fm (INCH/HR) = 0.43
AREA-AVERAGED Fp (INCH/HR) = 0.60      AREA-AVERAGED Ap = 0.72
TOTAL AREA (ACRES) = 6370.5      PEAK FLOW RATE (CFS) = 460.90
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

```

```

=====
MAINLINE Tc (MIN.) = 25.56
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.654
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/      SCS SOIL      AREA      Fp      Ap      SCS
LAND USE      GROUP      (ACRES)      (INCH/HR)      (DECIMAL)      CN
USER-DEFINED      -      21.54      0.60      1.000      -
USER-DEFINED      -      36.64      0.60      1.000      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 58.18      SUBAREA RUNOFF (CFS) = 2.82
EFFECTIVE AREA (ACRES) = 1373.11      AREA-AVERAGED Fm (INCH/HR) = 0.44
AREA-AVERAGED Fp (INCH/HR) = 0.60      AREA-AVERAGED Ap = 0.73
TOTAL AREA (ACRES) = 6428.7      PEAK FLOW RATE (CFS) = 460.90
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****

```

```

FLOW PROCESS FROM NODE 13306.00 TO NODE 13307.00 IS CODE = 51

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

```

```

=====
ELEVATION DATA: UPSTREAM (FEET) = 245.50      DOWNSTREAM (FEET) = 220.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 1543.21      CHANNEL SLOPE = 0.0165
CHANNEL BASE (FEET) = 0.00      "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040      MAXIMUM DEPTH (FEET) = 20.00
CHANNEL FLOW THRU SUBAREA (CFS) = 460.90
FLOW VELOCITY (FEET/SEC.) = 7.84      FLOW DEPTH (FEET) = 4.43
TRAVEL TIME (MIN.) = 3.28      Tc (MIN.) = 28.84
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13307.00 = 47838.16 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13307.00 TO NODE 13307.00 IS CODE = 81

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

```

```

=====
MAINLINE Tc (MIN.) = 28.84
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.604
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/      SCS SOIL      AREA      Fp      Ap      SCS
LAND USE      GROUP      (ACRES)      (INCH/HR)      (DECIMAL)      CN
USER-DEFINED      -      0.20      0.60      0.100      -
USER-DEFINED      -      0.10      0.60      1.000      -
USER-DEFINED      -      0.20      0.60      1.000      -
USER-DEFINED      -      3.70      0.60      1.000      -
USER-DEFINED      -      0.30      0.60      0.100      -
USER-DEFINED      -      3.20      0.60      1.000      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.942
SUBAREA AREA (ACRES) = 7.70      SUBAREA RUNOFF (CFS) = 0.27
EFFECTIVE AREA (ACRES) = 1380.81      AREA-AVERAGED Fm (INCH/HR) = 0.44
AREA-AVERAGED Fp (INCH/HR) = 0.60      AREA-AVERAGED Ap = 0.73
TOTAL AREA (ACRES) = 6436.4      PEAK FLOW RATE (CFS) = 460.90
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13307.00 TO NODE 13307.00 IS CODE = 81

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

```

```

=====
MAINLINE Tc (MIN.) = 28.84
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.604
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/      SCS SOIL      AREA      Fp      Ap      SCS
LAND USE      GROUP      (ACRES)      (INCH/HR)      (DECIMAL)      CN
USER-DEFINED      -      3.60      0.60      1.000      -
USER-DEFINED      -      1.90      0.60      1.000      -
USER-DEFINED      -      0.60      0.60      1.000      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 6.10      SUBAREA RUNOFF (CFS) = 0.03
EFFECTIVE AREA (ACRES) = 1386.91      AREA-AVERAGED Fm (INCH/HR) = 0.44
AREA-AVERAGED Fp (INCH/HR) = 0.60      AREA-AVERAGED Ap = 0.73
TOTAL AREA (ACRES) = 6442.5      PEAK FLOW RATE (CFS) = 460.90
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

FLOW PROCESS FROM NODE 13307.00 TO NODE 13308.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 220.00 DOWNSTREAM(FEET) = 212.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 925.62 CHANNEL SLOPE = 0.0086
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
CHANNEL FLOW THRU SUBAREA(CFS) = 460.90
FLOW VELOCITY(FEET/SEC.) = 6.15 FLOW DEPTH(FEET) = 5.00
TRAVEL TIME(MIN.) = 2.51 Tc(MIN.) = 31.35
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13308.00 = 48763.78 FEET.

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 31.35

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.576

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include USER-DEFINED entries with various values.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.697

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 9.50 SUBAREA RUNOFF(CFS) = 1.49

EFFECTIVE AREA(ACRES) = 1396.41 AREA-AVERAGED Fm(INCH/HR) = 0.44

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.73

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 6452.0 PEAK FLOW RATE(CFS) = 460.90

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 31.35

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.576

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include USER-DEFINED entries with various values.

USER-DEFINED - 7.20 0.60 1.000 -
USER-DEFINED - 25.00 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.498
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 75.60 SUBAREA RUNOFF(CFS) = 19.68
EFFECTIVE AREA(ACRES) = 1472.01 AREA-AVERAGED Fm(INCH/HR) = 0.43
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.72
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 6527.6 PEAK FLOW RATE(CFS) = 460.90
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 31.35

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.576

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include USER-DEFINED entries with various values.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.966

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 15.60 SUBAREA RUNOFF(CFS) = 0.28

EFFECTIVE AREA(ACRES) = 1487.61 AREA-AVERAGED Fm(INCH/HR) = 0.43

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.72

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 6543.2 PEAK FLOW RATE(CFS) = 460.90

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 31.35

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.576

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include USER-DEFINED entries with various values.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.603
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 SUBAREA AREA(ACRES) = 80.40 SUBAREA RUNOFF(CFS) = 16.53
 EFFECTIVE AREA(ACRES) = 1568.01 AREA-AVERAGED Fm(INCH/HR) = 0.43
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.72
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA(ACRES) = 6623.6 PEAK FLOW RATE(CFS) = 460.90
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 31.35
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.576
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.30	0.60	0.600	-
USER-DEFINED	-	0.70	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.880
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 SUBAREA AREA(ACRES) = 1.00 SUBAREA RUNOFF(CFS) = 0.06
 EFFECTIVE AREA(ACRES) = 1569.01 AREA-AVERAGED Fm(INCH/HR) = 0.43
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.72
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA(ACRES) = 6624.6 PEAK FLOW RATE(CFS) = 460.90
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 31.35
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.576
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.30	0.60	1.000	-
USER-DEFINED	-	0.80	0.60	1.000	-
USER-DEFINED	-	0.50	0.60	1.000	-
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	0.30	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 SUBAREA AREA(ACRES) = 2.10 SUBAREA RUNOFF(CFS) = 0.00
 EFFECTIVE AREA(ACRES) = 1571.11 AREA-AVERAGED Fm(INCH/HR) = 0.43
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.72

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA(ACRES) = 6626.7 PEAK FLOW RATE(CFS) = 460.90
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 31.35
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.576
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.20	0.60	1.000	-
USER-DEFINED	-	0.50	0.60	1.000	-
USER-DEFINED	-	1.70	0.60	0.850	-
USER-DEFINED	-	7.20	0.60	1.000	-
USER-DEFINED	-	1.00	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.978
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 SUBAREA AREA(ACRES) = 11.60 SUBAREA RUNOFF(CFS) = 0.13
 EFFECTIVE AREA(ACRES) = 1582.71 AREA-AVERAGED Fm(INCH/HR) = 0.43
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.72
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA(ACRES) = 6638.3 PEAK FLOW RATE(CFS) = 460.90
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<

 FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU02EV29.DNA
 MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2009.60	19.24	0.60(0.44)	0.73	2319.3	50400.00
2	1922.73	29.51	0.60(0.44)	0.74	3745.7	50320.00
3	1326.62	50.93	0.60(0.47)	0.78	6583.6	50260.00
4	895.99	63.38	0.60(0.49)	0.81	7608.9	600.00
5	903.94	112.25	0.60(0.54)	0.90	14295.0	11831.00
6	967.71	135.97	0.60(0.55)	0.92	17980.1	11530.00
7	1039.53	155.68	0.60(0.56)	0.93	22126.8	11000.00
8	1137.62	178.22	0.60(0.57)	0.95	28922.7	10850.00
9	1020.97	199.68	0.60(0.57)	0.95	33257.3	11910.00
10	958.81	211.71	0.60(0.57)	0.95	34960.8	12300.00
11	832.14	245.36	0.60(0.58)	0.96	40669.2	12410.00

12	787.66	278.29	0.60	(0.58)	0.96	46755.1	12261.00
13	772.95	291.05	0.60	(0.58)	0.96	48241.7	10410.00
14	758.44	303.23	0.60	(0.58)	0.96	49343.7	12101.10
15	743.40	312.94	0.60	(0.58)	0.96	50165.0	10700.00
16	725.65	330.69	0.60	(0.58)	0.97	51721.7	10200.00
17	709.10	344.08	0.60	(0.58)	0.97	52660.0	12010.00
18	664.33	373.17	0.60	(0.58)	0.97	53333.7	10210.00
19	603.05	422.31	0.60	(0.58)	0.97	53832.8	12000.00
20	561.53	491.84	0.60	(0.58)	0.97	54417.5	10100.00

TOTAL AREA (ACRES) = 54417.5

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<<
=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2009.60	19.24	0.60 (0.44)	0.73	2319.3	50400.00
2	1922.73	29.51	0.60 (0.44)	0.74	3745.7	50320.00
3	1326.62	50.93	0.60 (0.47)	0.78	6583.6	50260.00
4	895.99	63.38	0.60 (0.49)	0.81	7608.9	600.00
5	903.94	112.25	0.60 (0.54)	0.90	14295.0	11831.00
6	967.71	135.97	0.60 (0.55)	0.92	17980.1	11530.00
7	1039.53	155.68	0.60 (0.56)	0.93	22126.8	11000.00
8	1137.62	178.22	0.60 (0.57)	0.95	28922.7	10850.00
9	1020.97	199.68	0.60 (0.57)	0.95	33257.3	11910.00
10	958.81	211.71	0.60 (0.57)	0.95	34960.8	12300.00
11	832.14	245.36	0.60 (0.58)	0.96	40669.2	12410.00
12	787.66	278.29	0.60 (0.58)	0.96	46755.1	12261.00
13	772.95	291.05	0.60 (0.58)	0.96	48241.7	10410.00
14	758.44	303.23	0.60 (0.58)	0.96	49343.7	12101.10
15	743.40	312.94	0.60 (0.58)	0.96	50165.0	10700.00
16	725.65	330.69	0.60 (0.58)	0.97	51721.7	10200.00
17	709.10	344.08	0.60 (0.58)	0.97	52660.0	12010.00
18	664.33	373.17	0.60 (0.58)	0.97	53333.7	10210.00
19	603.05	422.31	0.60 (0.58)	0.97	53832.8	12000.00
20	561.53	491.84	0.60 (0.58)	0.97	54417.5	10100.00

TOTAL AREA (ACRES) = 54417.5

FLOW PROCESS FROM NODE 12904.00 TO NODE 13308.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<<
=====

ELEVATION DATA: UPSTREAM (FEET) = 213.00 DOWNSTREAM (FEET) = 212.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 1389.52 CHANNEL SLOPE = 0.0007
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00
CHANNEL FLOW THRU SUBAREA (CFS) = 2009.60
FLOW VELOCITY (FEET/SEC.) = 4.33 FLOW DEPTH (FEET) = 12.43
TRAVEL TIME (MIN.) = 5.34 Tc (MIN.) = 24.58
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118067.44 FEET.

FLOW PROCESS FROM NODE 13307.00 TO NODE 13308.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<<
=====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2009.60	24.58	0.671	0.60 (0.44)	0.73	2319.3	50400.00
2	1922.73	34.92	0.547	0.60 (0.44)	0.74	3745.7	50320.00
3	1326.62	56.86	0.412	0.60 (0.47)	0.78	6583.6	50260.00
4	895.99	69.91	0.377	0.60 (0.49)	0.81	7608.9	600.00
5	903.94	118.77	0.288	0.60 (0.54)	0.90	14295.0	11831.00
6	967.71	142.38	0.266	0.60 (0.55)	0.92	17980.1	11530.00
7	1039.53	161.97	0.248	0.60 (0.56)	0.93	22126.8	11000.00
8	1137.62	184.38	0.231	0.60 (0.57)	0.95	28922.7	10850.00
9	1020.97	206.00	0.224	0.60 (0.57)	0.95	33257.3	11910.00
10	958.81	218.13	0.221	0.60 (0.57)	0.95	34960.8	12300.00
11	832.14	252.02	0.210	0.60 (0.58)	0.96	40669.2	12410.00
12	787.66	285.04	0.200	0.60 (0.58)	0.96	46755.1	12261.00
13	772.95	297.83	0.197	0.60 (0.58)	0.96	48241.7	10410.00
14	758.44	310.05	0.193	0.60 (0.58)	0.96	49343.7	12101.10
15	743.40	319.78	0.190	0.60 (0.58)	0.96	50165.0	10700.00
16	725.65	337.58	0.185	0.60 (0.58)	0.97	51721.7	10200.00
17	709.10	351.02	0.181	0.60 (0.58)	0.97	52660.0	12010.00
18	664.33	380.21	0.176	0.60 (0.58)	0.97	53333.7	10210.00
19	603.05	429.52	0.170	0.60 (0.58)	0.97	53832.8	12000.00
20	561.53	499.18	0.162	0.60 (0.58)	0.97	54417.5	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118067.44 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	460.90	31.35	0.576	0.60 (0.43)	0.72	1582.7	120.00
2	457.29	31.94	0.571	0.60 (0.43)	0.72	1616.6	110.00
3	402.64	40.98	0.500	0.60 (0.44)	0.73	2091.8	100.00
4	327.04	49.63	0.451	0.60 (0.45)	0.75	2477.5	150.00
5	328.73	71.08	0.375	0.60 (0.47)	0.78	3503.7	31100.00
6	363.59	96.40	0.328	0.60 (0.48)	0.79	5183.0	13100.00
7	363.26	97.81	0.326	0.60 (0.48)	0.79	5261.5	13200.00
8	365.16	104.23	0.314	0.60 (0.48)	0.79	5523.5	13210.00
9	372.15	135.47	0.272	0.60 (0.48)	0.80	6618.3	13000.00
10	367.04	138.99	0.269	0.60 (0.48)	0.80	6638.3	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13308.00 = 48763.78 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2470.50	24.58	0.671	0.60 (0.44)	0.73	3560.4	50400.00
2	2413.62	31.35	0.576	0.60 (0.44)	0.73	4836.1	120.00
3	2405.02	31.94	0.571	0.60 (0.44)	0.73	4951.7	110.00
4	2362.05	34.92	0.547	0.60 (0.44)	0.74	5518.6	50320.00
5	2160.49	40.98	0.500	0.60 (0.45)	0.75	6622.5	100.00
6	1849.87	49.63	0.451	0.60 (0.46)	0.76	8127.0	150.00
7	1654.23	56.86	0.412	0.60 (0.46)	0.77	9406.6	50260.00
8	1224.63	69.91	0.377	0.60 (0.48)	0.80	11056.8	600.00
9	1224.91	71.08	0.375	0.60 (0.48)	0.80	11272.1	31100.00
10	1263.89	96.40	0.328	0.60 (0.50)	0.84	16416.7	13100.00

11	1263.79	97.81	0.326	0.60	(0.50)	0.84	16688.1	13200.00
12	1266.73	104.23	0.314	0.60	(0.51)	0.85	17828.3	13210.00
13	1272.35	118.77	0.288	0.60	(0.52)	0.87	20328.2	11831.00
14	1321.19	135.47	0.272	0.60	(0.53)	0.88	23519.6	13000.00
15	1325.59	138.99	0.269	0.60	(0.53)	0.88	24089.3	13010.00
16	1330.58	142.38	0.266	0.60	(0.53)	0.88	24618.4	11530.00
17	1378.33	161.97	0.248	0.60	(0.54)	0.90	28765.1	11000.00
18	1452.49	184.38	0.231	0.60	(0.55)	0.92	35561.0	10850.00
19	1326.99	206.00	0.224	0.60	(0.56)	0.93	39895.6	11910.00
20	1259.85	218.13	0.221	0.60	(0.56)	0.93	41599.1	12300.00
21	1119.31	252.02	0.210	0.60	(0.56)	0.94	47307.5	12410.00
22	1061.31	285.04	0.200	0.60	(0.56)	0.94	53393.4	12261.00
23	1041.37	297.83	0.197	0.60	(0.57)	0.94	54880.0	10410.00
24	1021.85	310.05	0.193	0.60	(0.57)	0.94	55982.0	12101.10
25	1002.82	319.78	0.190	0.60	(0.57)	0.94	56803.4	10700.00
26	977.79	337.58	0.185	0.60	(0.57)	0.95	58360.0	10200.00
27	955.73	351.02	0.181	0.60	(0.57)	0.95	59298.3	12010.00
28	904.06	380.21	0.176	0.60	(0.57)	0.95	59972.0	10210.00
29	834.93	429.52	0.170	0.60	(0.57)	0.95	60471.1	12000.00
30	782.32	499.18	0.162	0.60	(0.57)	0.95	61055.8	10100.00

TOTAL AREA (ACRES) = 61055.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 2470.50 Tc (MIN.) = 24.583
EFFECTIVE AREA (ACRES) = 3560.40 AREA-AVERAGED Fm (INCH/HR) = 0.44
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.73
TOTAL AREA (ACRES) = 61055.8
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118067.44 FEET.

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 61055.8 TC (MIN.) = 24.58
EFFECTIVE AREA (ACRES) = 3560.40 AREA-AVERAGED Fm (INCH/HR) = 0.44
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.728
PEAK FLOW RATE (CFS) = 2470.50

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2470.50	24.58	0.671	0.60 (0.44)	0.73	3560.4	50400.00
2	2413.62	31.35	0.576	0.60 (0.44)	0.73	4836.1	120.00
3	2405.02	31.94	0.571	0.60 (0.44)	0.73	4951.7	110.00
4	2362.05	34.92	0.547	0.60 (0.44)	0.74	5518.6	50320.00
5	2160.49	40.98	0.500	0.60 (0.45)	0.75	6622.5	100.00
6	1849.87	49.63	0.451	0.60 (0.46)	0.76	8127.0	150.00
7	1654.23	56.86	0.412	0.60 (0.46)	0.77	9406.6	50260.00
8	1224.63	69.91	0.377	0.60 (0.48)	0.80	11056.8	600.00
9	1224.91	71.08	0.375	0.60 (0.48)	0.80	11272.1	31100.00
10	1263.89	96.40	0.328	0.60 (0.50)	0.84	16416.7	13100.00
11	1263.79	97.81	0.326	0.60 (0.50)	0.84	16688.1	13200.00
12	1266.73	104.23	0.314	0.60 (0.51)	0.85	17828.3	13210.00
13	1272.35	118.77	0.288	0.60 (0.52)	0.87	20328.2	11831.00
14	1321.19	135.47	0.272	0.60 (0.53)	0.88	23519.6	13000.00
15	1325.59	138.99	0.269	0.60 (0.53)	0.88	24089.3	13010.00
16	1330.58	142.38	0.266	0.60 (0.53)	0.88	24618.4	11530.00
17	1378.33	161.97	0.248	0.60 (0.54)	0.90	28765.1	11000.00
18	1452.49	184.38	0.231	0.60 (0.55)	0.92	35561.0	10850.00
19	1326.99	206.00	0.224	0.60 (0.56)	0.93	39895.6	11910.00
20	1259.85	218.13	0.221	0.60 (0.56)	0.93	41599.1	12300.00

21	1119.31	252.02	0.210	0.60	(0.56)	0.94	47307.5	12410.00
22	1061.31	285.04	0.200	0.60	(0.56)	0.94	53393.4	12261.00
23	1041.37	297.83	0.197	0.60	(0.57)	0.94	54880.0	10410.00
24	1021.85	310.05	0.193	0.60	(0.57)	0.94	55982.0	12101.10
25	1002.82	319.78	0.190	0.60	(0.57)	0.94	56803.4	10700.00
26	977.79	337.58	0.185	0.60	(0.57)	0.95	58360.0	10200.00
27	955.73	351.02	0.181	0.60	(0.57)	0.95	59298.3	12010.00
28	904.06	380.21	0.176	0.60	(0.57)	0.95	59972.0	10210.00
29	834.93	429.52	0.170	0.60	(0.57)	0.95	60471.1	12000.00
30	782.32	499.18	0.162	0.60	(0.57)	0.95	61055.8	10100.00

=====

END OF RATIONAL METHOD ANALYSIS

=====

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2010 Advanced Engineering Software (aes)
Ver. 17.0 Release Date: 07/01/2010 License ID 1527

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 134 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 2-YR EV AUG 2023 ROKAMOTO *

FILE NAME: RU02EV34.DAT
TIME/DATE OF STUDY: 23:51 08/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 2.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 1.819
- 2) 10.00; 1.213
- 3) 15.00; 0.930
- 4) 20.00; 0.765
- 5) 25.00; 0.661
- 6) 30.00; 0.587
- 7) 40.00; 0.505
- 8) 50.00; 0.448
- 9) 60.00; 0.390
- 10) 90.00; 0.336
- 11) 120.00; 0.280
- 12) 180.00; 0.226
- 13) 360.00; 0.170
- 14) 1200.00; 0.080

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU02EV33.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2470.50	24.58	0.60 (0.44)	0.73	3560.4	50400.00
2	2160.49	40.98	0.60 (0.45)	0.75	6622.5	100.00
3	1224.91	71.08	0.60 (0.48)	0.80	11272.1	31100.00
4	1266.73	104.23	0.60 (0.51)	0.85	17828.3	13210.00
5	1272.35	118.77	0.60 (0.52)	0.87	20328.2	11831.00
6	1330.58	142.38	0.60 (0.53)	0.88	24618.4	11530.00
7	1378.33	161.97	0.60 (0.54)	0.90	28765.1	11000.00
8	1452.49	184.38	0.60 (0.55)	0.92	35561.0	10850.00
9	1326.99	206.00	0.60 (0.56)	0.93	39895.6	11910.00
10	1259.85	218.13	0.60 (0.56)	0.93	41599.1	12300.00
11	1119.31	252.02	0.60 (0.56)	0.94	47307.5	12410.00
12	1061.31	285.04	0.60 (0.56)	0.94	53393.4	12261.00
13	1041.37	297.83	0.60 (0.57)	0.94	54880.0	10410.00
14	1021.85	310.05	0.60 (0.57)	0.94	55982.0	12101.10
15	1002.82	319.78	0.60 (0.57)	0.94	56803.4	10700.00
16	977.79	337.58	0.60 (0.57)	0.95	58360.0	10200.00
17	955.73	351.02	0.60 (0.57)	0.95	59298.3	12010.00
18	904.06	380.21	0.60 (0.57)	0.95	59972.0	10210.00
19	834.93	429.52	0.60 (0.57)	0.95	60471.1	12000.00
20	782.32	499.18	0.60 (0.57)	0.95	61055.8	10100.00
TOTAL AREA (ACRES) =						61055.8

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2470.50	24.58	0.60 (0.44)	0.73	3560.4	50400.00
2	2160.49	40.98	0.60 (0.45)	0.75	6622.5	100.00
3	1224.91	71.08	0.60 (0.48)	0.80	11272.1	31100.00
4	1266.73	104.23	0.60 (0.51)	0.85	17828.3	13210.00
5	1272.35	118.77	0.60 (0.52)	0.87	20328.2	11831.00
6	1330.58	142.38	0.60 (0.53)	0.88	24618.4	11530.00
7	1378.33	161.97	0.60 (0.54)	0.90	28765.1	11000.00
8	1452.49	184.38	0.60 (0.55)	0.92	35561.0	10850.00
9	1326.99	206.00	0.60 (0.56)	0.93	39895.6	11910.00
10	1259.85	218.13	0.60 (0.56)	0.93	41599.1	12300.00
11	1119.31	252.02	0.60 (0.56)	0.94	47307.5	12410.00
12	1061.31	285.04	0.60 (0.56)	0.94	53393.4	12261.00
13	1041.37	297.83	0.60 (0.57)	0.94	54880.0	10410.00

14	1021.85	310.05	0.60	(0.57)	0.94	55982.0	12101.10
15	1002.82	319.78	0.60	(0.57)	0.94	56803.4	10700.00
16	977.79	337.58	0.60	(0.57)	0.95	58360.0	10200.00
17	955.73	351.02	0.60	(0.57)	0.95	59298.3	12010.00
18	904.06	380.21	0.60	(0.57)	0.95	59972.0	10210.00
19	834.93	429.52	0.60	(0.57)	0.95	60471.1	12000.00
20	782.32	499.18	0.60	(0.57)	0.95	61055.8	10100.00

TOTAL AREA (ACRES) = 61055.8

FLOW PROCESS FROM NODE 13308.00 TO NODE 13402.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 212.00 DOWNSTREAM(FEET) = 209.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 623.02 CHANNEL SLOPE = 0.0048
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
 CHANNEL FLOW THRU SUBAREA(CFS) = 2470.50
 FLOW VELOCITY(FEET/SEC.) = 9.32 FLOW DEPTH(FEET) = 9.40
 TRAVEL TIME(MIN.) = 1.11 Tc(MIN.) = 25.70
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118690.46 FEET.

FLOW PROCESS FROM NODE 13402.00 TO NODE 13402.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<

PEAK FLOWRATE TABLE FILE NAME: P505XX02.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	8.61	24.42	0.60	(0.58)	0.96	146.4	50500.00

TOTAL AREA (ACRES) = 146.4

FLOW PROCESS FROM NODE 13402.00 TO NODE 13402.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2470.50	25.70	0.651	0.60 (0.44)	0.73	3560.4	50400.00
2	2160.49	42.14	0.493	0.60 (0.45)	0.75	6622.5	100.00
3	1224.91	72.41	0.368	0.60 (0.48)	0.80	11272.1	31100.00
4	1266.73	105.55	0.307	0.60 (0.51)	0.85	17828.3	13210.00
5	1272.35	120.09	0.280	0.60 (0.52)	0.87	20328.2	11831.00
6	1330.58	143.68	0.259	0.60 (0.53)	0.88	24618.4	11530.00
7	1378.33	163.26	0.241	0.60 (0.54)	0.90	28765.1	11000.00
8	1452.49	185.65	0.224	0.60 (0.55)	0.92	35561.0	10850.00
9	1326.99	207.30	0.218	0.60 (0.56)	0.93	39895.6	11910.00
10	1259.85	219.45	0.214	0.60 (0.56)	0.93	41599.1	12300.00
11	1119.31	253.38	0.203	0.60 (0.56)	0.94	47307.5	12410.00
12	1061.31	286.42	0.193	0.60 (0.56)	0.94	53393.4	12261.00
13	1041.37	299.22	0.189	0.60 (0.57)	0.94	54880.0	10410.00

14	1021.85	311.44	0.185	0.60 (0.57)	0.94	55982.0	12101.10
15	1002.82	321.18	0.182	0.60 (0.57)	0.94	56803.4	10700.00
16	977.79	338.99	0.177	0.60 (0.57)	0.95	58360.0	10200.00
17	955.73	352.43	0.172	0.60 (0.57)	0.95	59298.3	12010.00
18	904.06	381.64	0.168	0.60 (0.57)	0.95	59972.0	10210.00
19	834.93	430.99	0.162	0.60 (0.57)	0.95	60471.1	12000.00
20	782.32	500.67	0.155	0.60 (0.57)	0.95	61055.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118690.46 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	8.61	24.42	0.673	0.60 (0.58)	0.96	146.4	50500.00

LONGEST FLOWPATH FROM NODE 50500.00 TO NODE 13402.00 = 5416.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2479.11	24.42	0.673	0.60 (0.44)	0.74	3530.3	50500.00
2	2477.15	25.70	0.651	0.60 (0.44)	0.74	3706.8	50400.00
3	2162.28	42.14	0.493	0.60 (0.45)	0.75	6768.9	100.00
4	1226.25	72.41	0.368	0.60 (0.48)	0.80	11418.5	31100.00
5	1267.85	105.55	0.307	0.60 (0.51)	0.85	17974.7	13210.00
6	1273.37	120.09	0.280	0.60 (0.52)	0.87	20474.6	11831.00
7	1331.52	143.68	0.259	0.60 (0.53)	0.88	24764.8	11530.00
8	1379.21	163.26	0.241	0.60 (0.54)	0.90	28911.5	11000.00
9	1453.30	185.65	0.224	0.60 (0.55)	0.92	35707.4	10850.00
10	1327.78	207.30	0.218	0.60 (0.56)	0.93	40042.0	11910.00
11	1260.63	219.45	0.214	0.60 (0.56)	0.93	41745.5	12300.00
12	1120.04	253.38	0.203	0.60 (0.56)	0.94	47453.9	12410.00
13	1062.01	286.42	0.193	0.60 (0.56)	0.94	53539.8	12261.00
14	1042.05	299.22	0.189	0.60 (0.57)	0.94	55026.4	10410.00
15	1022.52	311.44	0.185	0.60 (0.57)	0.94	56128.4	12101.10
16	1003.49	321.18	0.182	0.60 (0.57)	0.94	56949.8	10700.00
17	978.43	338.99	0.177	0.60 (0.57)	0.95	58506.4	10200.00
18	956.36	352.43	0.172	0.60 (0.57)	0.95	59444.7	12010.00
19	904.67	381.64	0.168	0.60 (0.57)	0.95	60118.4	10210.00
20	835.52	430.99	0.162	0.60 (0.57)	0.95	60617.5	12000.00
21	782.88	500.67	0.155	0.60 (0.57)	0.95	61202.2	10100.00

TOTAL AREA (ACRES) = 61202.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 2479.11 Tc(MIN.) = 24.424
 EFFECTIVE AREA(ACRES) = 3530.33 AREA-AVERAGED Fm(INCH/HR) = 0.44
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.95
 TOTAL AREA(ACRES) = 61202.2
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118690.46 FEET.

FLOW PROCESS FROM NODE 13402.00 TO NODE 13404.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 209.00 DOWNSTREAM(FEET) = 207.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 395.35 CHANNEL SLOPE = 0.0051
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00

CHANNEL FLOW THRU SUBAREA(CFS) = 2479.11
 FLOW VELOCITY(FEET/SEC.) = 9.50 FLOW DEPTH(FEET) = 9.33
 TRAVEL TIME(MIN.) = 0.69 Tc(MIN.) = 25.12
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119085.81 FEET.

 FLOW PROCESS FROM NODE 13404.00 TO NODE 13404.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P506XX02.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4.90	24.14	0.60 (0.58)	0.97	49.5	50600.00
TOTAL AREA (ACRES) =						49.5

 FLOW PROCESS FROM NODE 13404.00 TO NODE 13404.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2479.11	25.12	0.659	0.60 (0.44)	0.74	3530.3	50500.00
2	2477.15	26.39	0.640	0.60 (0.44)	0.74	3706.8	50400.00
3	2162.28	42.86	0.489	0.60 (0.45)	0.75	6768.9	100.00
4	1226.25	73.24	0.366	0.60 (0.48)	0.80	11418.5	31100.00
5	1267.85	106.37	0.305	0.60 (0.51)	0.85	17974.7	13210.00
6	1273.37	120.91	0.279	0.60 (0.52)	0.87	20474.6	11831.00
7	1331.52	144.49	0.258	0.60 (0.53)	0.88	24764.8	11530.00
8	1379.21	164.07	0.240	0.60 (0.54)	0.90	28911.5	11000.00
9	1453.30	186.45	0.224	0.60 (0.55)	0.92	35707.4	10850.00
10	1327.78	208.11	0.217	0.60 (0.56)	0.93	40042.0	11910.00
11	1260.63	220.27	0.213	0.60 (0.56)	0.93	41745.5	12300.00
12	1120.04	254.23	0.203	0.60 (0.56)	0.94	47453.9	12410.00
13	1062.01	287.28	0.193	0.60 (0.56)	0.94	53539.8	12261.00
14	1042.05	300.08	0.189	0.60 (0.57)	0.94	55026.4	10410.00
15	1022.52	312.30	0.185	0.60 (0.57)	0.94	56128.4	12101.10
16	1003.49	322.05	0.182	0.60 (0.57)	0.94	56949.8	10700.00
17	978.43	339.86	0.176	0.60 (0.57)	0.95	58506.4	10200.00
18	956.36	353.31	0.172	0.60 (0.57)	0.95	59444.7	12010.00
19	904.67	382.53	0.168	0.60 (0.57)	0.95	60118.4	10210.00
20	835.52	431.90	0.162	0.60 (0.57)	0.95	60617.5	12000.00
21	782.88	501.59	0.155	0.60 (0.57)	0.95	61202.2	10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 =							119085.81 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4.90	24.14	0.679	0.60 (0.58)	0.97	49.5	50600.00
LONGEST FLOWPATH FROM NODE 50600.00 TO NODE 13404.00 =							4378.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4.90	24.14	0.679	0.60 (0.58)	0.97	49.5	50600.00

1	2484.01	24.14	0.679	0.60 (0.44)	0.74	3442.8	50600.00
2	2483.04	25.12	0.659	0.60 (0.44)	0.74	3579.8	50500.00
3	2480.16	26.39	0.640	0.60 (0.44)	0.74	3756.3	50400.00
4	2163.11	42.86	0.489	0.60 (0.45)	0.75	6818.4	100.00
5	1226.87	73.24	0.366	0.60 (0.48)	0.81	11468.0	31100.00
6	1268.36	106.37	0.305	0.60 (0.51)	0.85	18024.2	13210.00
7	1273.84	120.91	0.279	0.60 (0.52)	0.87	20524.1	11831.00
8	1331.96	144.49	0.258	0.60 (0.53)	0.88	24814.3	11530.00
9	1379.61	164.07	0.240	0.60 (0.54)	0.90	28961.0	11000.00
10	1453.68	186.45	0.224	0.60 (0.55)	0.92	35756.9	10850.00
11	1328.15	208.11	0.217	0.60 (0.56)	0.93	40091.5	11910.00
12	1260.99	220.27	0.213	0.60 (0.56)	0.93	41795.0	12300.00
13	1120.39	254.23	0.203	0.60 (0.56)	0.94	47503.4	12410.00
14	1062.33	287.28	0.193	0.60 (0.56)	0.94	53589.3	12261.00
15	1042.37	300.08	0.189	0.60 (0.57)	0.94	55075.9	10410.00
16	1022.84	312.30	0.185	0.60 (0.57)	0.94	56177.9	12101.10
17	1003.79	322.05	0.182	0.60 (0.57)	0.94	56999.3	10700.00
18	978.73	339.86	0.176	0.60 (0.57)	0.95	58555.9	10200.00
19	956.65	353.31	0.172	0.60 (0.57)	0.95	59494.2	12010.00
20	904.96	382.53	0.168	0.60 (0.57)	0.95	60167.9	10210.00
21	835.80	431.90	0.162	0.60 (0.57)	0.95	60667.0	12000.00
22	783.14	501.59	0.155	0.60 (0.57)	0.95	61251.7	10100.00
TOTAL AREA (ACRES) =							61251.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 2484.01 Tc(MIN.) = 24.143
 EFFECTIVE AREA(ACRES) = 3442.76 AREA-AVERAGED Fm(INCH/HR) = 0.44
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.95
 TOTAL AREA (ACRES) = 61251.7
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119085.81 FEET.

 FLOW PROCESS FROM NODE 13404.00 TO NODE 13406.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 207.00 DOWNSTREAM(FEET) = 195.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1601.97 CHANNEL SLOPE = 0.0075
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
 CHANNEL FLOW THRU SUBAREA(CFS) = 2484.01
 FLOW VELOCITY(FEET/SEC.) = 11.01 FLOW DEPTH(FEET) = 8.67
 TRAVEL TIME(MIN.) = 2.42 Tc(MIN.) = 26.57
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13406.00 = 120687.78 FEET.

 FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 26.57

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.638

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	4.00	0.60	1.000	-

USER-DEFINED - 2.00 0.60 1.000 -
 USER-DEFINED - 9.70 0.60 1.000 -
 USER-DEFINED - 2.60 0.60 1.000 -
 USER-DEFINED - 1.60 0.60 1.000 -
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 20.10 SUBAREA RUNOFF(CFS) = 0.69
 EFFECTIVE AREA(ACRES) = 3462.86 AREA-AVERAGED Fm(INCH/HR) = 0.45
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.74
 TOTAL AREA(ACRES) = 61271.8 PEAK FLOW RATE(CFS) = 2484.01
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 26.57
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.638
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	2.00	0.60	1.000	-
USER-DEFINED	-	7.10	0.60	1.000	-
USER-DEFINED	-	5.80	0.60	1.000	-
USER-DEFINED	-	0.10	0.60	1.000	-

 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 15.00 SUBAREA RUNOFF(CFS) = 0.51
 EFFECTIVE AREA(ACRES) = 3477.86 AREA-AVERAGED Fm(INCH/HR) = 0.45
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.74
 TOTAL AREA(ACRES) = 61286.8 PEAK FLOW RATE(CFS) = 2484.01
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13406.00 TO NODE 13408.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 195.00 DOWNSTREAM(FEET) = 182.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2458.36 CHANNEL SLOPE = 0.0053
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.580
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.00	0.60	1.000	-
USER-DEFINED	-	3.30	0.60	1.000	-
USER-DEFINED	-	0.40	0.60	0.100	-
USER-DEFINED	-	1.40	0.60	1.000	-
USER-DEFINED	-	0.30	0.60	0.100	-

 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.949
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2484.17

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.66
 AVERAGE FLOW DEPTH(FEET) = 9.26 TRAVEL TIME(MIN.) = 4.24
 Tc(MIN.) = 30.81
 SUBAREA AREA(ACRES) = 12.40 SUBAREA RUNOFF(CFS) = 0.33
 EFFECTIVE AREA(ACRES) = 3490.26 AREA-AVERAGED Fm(INCH/HR) = 0.45
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.74
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA(ACRES) = 61299.2 PEAK FLOW RATE(CFS) = 2484.01
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 9.26 FLOW VELOCITY(FEET/SEC.) = 9.66
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123146.14 FEET.

 FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1<<<<

 FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1<<<<

PEAK FLOWRATE TABLE FILE NAME: 2P02EVBB.DNA
 MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	194.02	10.81	0.60(0.22)	0.37	221.7	429.00
2	201.81	12.63	0.60(0.22)	0.37	258.9	425.00
3	202.30	12.83	0.60(0.22)	0.37	263.0	400.00
4	203.94	14.48	0.60(0.22)	0.37	297.3	300.00
5	198.94	22.38	0.60(0.22)	0.37	440.6	210.00
6	195.86	23.21	0.60(0.22)	0.37	449.5	410.00
7	187.76	25.35	0.60(0.22)	0.37	471.9	200.00
8	183.91	26.92	0.60(0.22)	0.37	487.0	230.00
9	177.74	28.12	0.60(0.22)	0.37	491.2	220.50
TOTAL AREA(ACRES) =						491.2

 FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2484.01	30.81	0.580	0.60(0.45)	0.74	3490.3	50600.00
2	2483.04	31.79	0.572	0.60(0.45)	0.74	3627.3	50500.00
3	2480.16	33.06	0.562	0.60(0.45)	0.74	3803.8	50400.00
4	2163.11	49.76	0.449	0.60(0.45)	0.75	6865.9	100.00
5	1226.87	81.19	0.352	0.60(0.48)	0.81	11515.5	31100.00
6	1268.36	114.26	0.291	0.60(0.51)	0.85	18071.7	13210.00
7	1273.84	128.78	0.272	0.60(0.52)	0.87	20571.6	11831.00
8	1331.96	152.28	0.251	0.60(0.53)	0.88	24861.8	11530.00

9	1379.61	171.79	0.233	0.60	(0.54)	0.90	29008.5	11000.00
10	1453.68	194.07	0.222	0.60	(0.55)	0.92	35804.4	10850.00
11	1328.15	215.91	0.215	0.60	(0.56)	0.93	40139.0	11910.00
12	1260.99	228.18	0.211	0.60	(0.56)	0.93	41842.5	12300.00
13	1120.39	262.36	0.200	0.60	(0.56)	0.94	47550.9	12410.00
14	1062.33	295.52	0.190	0.60	(0.56)	0.94	53636.8	12261.00
15	1042.37	308.36	0.186	0.60	(0.57)	0.94	55123.4	10410.00
16	1022.84	320.63	0.182	0.60	(0.57)	0.94	56225.4	12101.10
17	1003.79	330.40	0.179	0.60	(0.57)	0.94	57046.8	10700.00
18	978.73	348.27	0.174	0.60	(0.57)	0.95	58603.4	10200.00
19	956.65	361.77	0.170	0.60	(0.57)	0.95	59541.7	12010.00
20	904.96	391.11	0.167	0.60	(0.57)	0.95	60215.4	10210.00
21	835.80	440.65	0.161	0.60	(0.57)	0.95	60714.5	12000.00
22	783.14	510.49	0.154	0.60	(0.57)	0.95	61299.2	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123146.14 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	194.02	10.81	1.167	0.60 (0.22)	0.37	221.7	429.00
2	201.81	12.63	1.064	0.60 (0.22)	0.37	258.9	425.00
3	202.30	12.83	1.053	0.60 (0.22)	0.37	263.0	400.00
4	203.94	14.48	0.959	0.60 (0.22)	0.37	297.3	300.00
5	198.94	22.38	0.715	0.60 (0.22)	0.37	440.6	210.00
6	195.86	23.21	0.698	0.60 (0.22)	0.37	449.5	410.00
7	187.76	25.35	0.656	0.60 (0.22)	0.37	471.9	200.00
8	183.91	26.92	0.633	0.60 (0.22)	0.37	487.0	230.00
9	177.74	28.12	0.615	0.60 (0.22)	0.37	491.2	220.50

LONGEST FLOWPATH FROM NODE 230.00 TO NODE 13408.00 = 11903.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2678.02	10.81	1.167	0.60 (0.41)	0.69	1446.0	429.00
2	2685.82	12.63	1.064	0.60 (0.41)	0.69	1689.5	425.00
3	2686.31	12.83	1.053	0.60 (0.41)	0.69	1716.2	400.00
4	2687.95	14.48	0.959	0.60 (0.41)	0.69	1938.0	300.00
5	2682.94	22.38	0.715	0.60 (0.41)	0.69	2976.1	210.00
6	2679.86	23.21	0.698	0.60 (0.41)	0.69	3079.3	410.00
7	2671.77	25.35	0.656	0.60 (0.41)	0.69	3343.1	200.00
8	2667.92	26.92	0.633	0.60 (0.42)	0.69	3536.5	230.00
9	2661.74	28.12	0.615	0.60 (0.42)	0.69	3677.2	220.50
10	2649.47	30.81	0.580	0.60 (0.42)	0.70	3981.5	50600.00
11	2646.23	31.79	0.572	0.60 (0.42)	0.70	4118.5	50500.00
12	2640.36	33.06	0.562	0.60 (0.42)	0.70	4295.0	50400.00
13	2291.23	49.76	0.449	0.60 (0.44)	0.73	7357.1	100.00
14	1327.19	81.19	0.352	0.60 (0.47)	0.79	12006.7	31100.00
15	1351.25	114.26	0.291	0.60 (0.50)	0.84	18562.9	13210.00
16	1351.42	128.78	0.272	0.60 (0.51)	0.86	21062.8	11831.00
17	1403.50	152.28	0.251	0.60 (0.52)	0.87	25353.0	11530.00
18	1446.16	171.79	0.233	0.60 (0.53)	0.89	29499.7	11000.00
19	1516.87	194.07	0.222	0.60 (0.55)	0.91	36295.6	10850.00
20	1389.39	215.91	0.215	0.60 (0.55)	0.92	40630.2	11910.00
21	1321.15	228.18	0.211	0.60 (0.55)	0.92	42333.7	12300.00
22	1177.52	262.36	0.200	0.60 (0.56)	0.93	48042.1	12410.00
23	1116.52	295.52	0.190	0.60 (0.56)	0.94	54128.0	12261.00
24	1095.42	308.36	0.186	0.60 (0.56)	0.94	55614.6	10410.00
25	1074.80	320.63	0.182	0.60 (0.56)	0.94	56716.6	12101.10

26	1054.89	330.40	0.179	0.60	(0.56)	0.94	57538.0	10700.00
27	1028.24	348.27	0.174	0.60	(0.56)	0.94	59094.6	10200.00
28	1005.06	361.77	0.170	0.60	(0.57)	0.94	60032.9	12010.00
29	952.48	391.11	0.167	0.60	(0.57)	0.94	60706.6	10210.00
30	881.80	440.65	0.161	0.60	(0.57)	0.94	61205.7	12000.00
31	827.02	510.49	0.154	0.60	(0.57)	0.94	61790.4	10100.00

TOTAL AREA (ACRES) = 61790.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 2687.95 Tc (MIN.) = 14.483
EFFECTIVE AREA (ACRES) = 1938.01 AREA-AVERAGED Fm (INCH/HR) = 0.41
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.94
TOTAL AREA (ACRES) = 61790.4
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123146.14 FEET.

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P507XX02.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4.18	36.03	0.60 (0.59)	0.99	231.4	50700.00

TOTAL AREA (ACRES) = 231.4

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2678.02	10.81	1.167	0.60 (0.41)	0.69	1446.0	429.00
2	2685.82	12.63	1.064	0.60 (0.41)	0.69	1689.5	425.00
3	2686.31	12.83	1.053	0.60 (0.41)	0.69	1716.2	400.00
4	2687.95	14.48	0.959	0.60 (0.41)	0.69	1938.0	300.00
5	2682.94	22.38	0.715	0.60 (0.41)	0.69	2976.1	210.00
6	2679.86	23.21	0.698	0.60 (0.41)	0.69	3079.3	410.00
7	2671.77	25.35	0.656	0.60 (0.41)	0.69	3343.1	200.00
8	2667.92	26.92	0.633	0.60 (0.42)	0.69	3536.5	230.00
9	2661.74	28.12	0.615	0.60 (0.42)	0.69	3677.2	220.50
10	2649.47	30.81	0.580	0.60 (0.42)	0.70	3981.5	50600.00
11	2646.23	31.79	0.572	0.60 (0.42)	0.70	4118.5	50500.00
12	2640.36	33.06	0.562	0.60 (0.42)	0.70	4295.0	50400.00
13	2291.23	49.76	0.449	0.60 (0.44)	0.73	7357.1	100.00
14	1327.19	81.19	0.352	0.60 (0.47)	0.79	12006.7	31100.00
15	1351.25	114.26	0.291	0.60 (0.50)	0.84	18562.9	13210.00
16	1351.42	128.78	0.272	0.60 (0.51)	0.86	21062.8	11831.00

17	1403.50	152.28	0.251	0.60 (0.52)	0.87	25353.0	11530.00
18	1446.16	171.79	0.233	0.60 (0.53)	0.89	29499.7	11000.00
19	1516.87	194.07	0.222	0.60 (0.55)	0.91	36295.6	10850.00
20	1389.39	215.91	0.215	0.60 (0.55)	0.92	40630.2	11910.00
21	1321.15	228.18	0.211	0.60 (0.55)	0.92	42333.7	12300.00
22	1177.52	262.36	0.200	0.60 (0.56)	0.93	48042.1	12410.00
23	1116.52	295.52	0.190	0.60 (0.56)	0.94	54128.0	12261.00
24	1095.42	308.36	0.186	0.60 (0.56)	0.94	55614.6	10410.00
25	1074.80	320.63	0.182	0.60 (0.56)	0.94	56716.6	12101.10
26	1054.89	330.40	0.179	0.60 (0.56)	0.94	57538.0	10700.00
27	1028.24	348.27	0.174	0.60 (0.56)	0.94	59094.6	10200.00
28	1005.06	361.77	0.170	0.60 (0.57)	0.94	60032.9	12010.00
29	952.48	391.11	0.167	0.60 (0.57)	0.94	60706.6	10210.00
30	881.80	440.65	0.161	0.60 (0.57)	0.94	61205.7	12000.00
31	827.02	510.49	0.154	0.60 (0.57)	0.94	61790.4	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123146.14 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4.18	36.03	0.538	0.60 (0.59)	0.99	231.4	50700.00

LONGEST FLOWPATH FROM NODE 50700.00 TO NODE 13408.00 = 7683.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2680.75	10.81	1.167	0.60 (0.42)	0.70	1515.4	429.00
2	2688.72	12.63	1.064	0.60 (0.42)	0.70	1770.6	425.00
3	2689.23	12.83	1.053	0.60 (0.42)	0.70	1798.6	400.00
4	2690.95	14.48	0.959	0.60 (0.42)	0.70	2031.0	300.00
5	2686.40	22.38	0.715	0.60 (0.42)	0.70	3119.9	210.00
6	2683.36	23.21	0.698	0.60 (0.42)	0.70	3228.4	410.00
7	2675.36	25.35	0.656	0.60 (0.42)	0.71	3505.9	200.00
8	2671.60	26.92	0.633	0.60 (0.42)	0.71	3709.4	230.00
9	2665.47	28.12	0.615	0.60 (0.42)	0.71	3857.8	220.50
10	2653.33	30.81	0.580	0.60 (0.43)	0.71	4179.3	50600.00
11	2650.15	31.79	0.572	0.60 (0.43)	0.71	4322.7	50500.00
12	2644.37	33.06	0.562	0.60 (0.43)	0.71	4507.3	50400.00
13	2582.49	36.03	0.538	0.60 (0.43)	0.72	5070.6	50700.00
14	2294.73	49.76	0.449	0.60 (0.44)	0.74	7588.5	100.00
15	1329.92	81.19	0.352	0.60 (0.47)	0.79	12238.1	31100.00
16	1353.51	114.26	0.291	0.60 (0.50)	0.84	18794.3	13210.00
17	1353.54	128.78	0.272	0.60 (0.51)	0.86	21294.2	11831.00
18	1405.46	152.28	0.251	0.60 (0.52)	0.87	25584.4	11530.00
19	1447.97	171.79	0.233	0.60 (0.53)	0.89	29731.1	11000.00
20	1518.60	194.07	0.222	0.60 (0.55)	0.91	36527.0	10850.00
21	1391.07	215.91	0.215	0.60 (0.55)	0.92	40861.6	11910.00
22	1322.79	228.18	0.211	0.60 (0.55)	0.92	42565.1	12300.00
23	1179.08	262.36	0.200	0.60 (0.56)	0.93	48273.5	12410.00
24	1118.00	295.52	0.190	0.60 (0.56)	0.94	54359.4	12261.00
25	1096.87	308.36	0.186	0.60 (0.56)	0.94	55846.0	10410.00
26	1076.21	320.63	0.182	0.60 (0.56)	0.94	56948.0	12101.10
27	1056.28	330.40	0.179	0.60 (0.56)	0.94	57769.4	10700.00
28	1029.59	348.27	0.174	0.60 (0.56)	0.94	59326.0	10200.00
29	1006.38	361.77	0.170	0.60 (0.57)	0.94	60264.3	12010.00
30	953.77	391.11	0.167	0.60 (0.57)	0.94	60938.0	10210.00
31	883.06	440.65	0.161	0.60 (0.57)	0.94	61437.1	12000.00
32	828.21	510.49	0.154	0.60 (0.57)	0.94	62021.8	10100.00

TOTAL AREA(ACRES) = 62021.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
 PEAK FLOW RATE(CFS) = 2690.95 Tc(MIN.) = 14.483
 EFFECTIVE AREA(ACRES) = 2031.03 AREA-AVERAGED Fm(INCH/HR) = 0.42
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.70
 TOTAL AREA(ACRES) = 62021.8
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123146.14 FEET.

 FLOW PROCESS FROM NODE 13408.00 TO NODE 13410.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 182.00 DOWNSTREAM(FEET) = 178.72
 CHANNEL LENGTH THRU SUBAREA(FEET) = 952.73 CHANNEL SLOPE = 0.0034
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.885

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.40	0.60	1.000	-
USER-DEFINED	-	2.90	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2691.37
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.39
 AVERAGE FLOW DEPTH(FEET) = 10.34 TRAVEL TIME(MIN.) = 1.89
 Tc(MIN.) = 16.38
 SUBAREA AREA(ACRES) = 3.30 SUBAREA RUNOFF(CFS) = 0.85
 EFFECTIVE AREA(ACRES) = 2034.33 AREA-AVERAGED Fm(INCH/HR) = 0.42
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.70
 TOTAL AREA(ACRES) = 62025.1 PEAK FLOW RATE(CFS) = 2690.95
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 10.34 FLOW VELOCITY(FEET/SEC.) = 8.39
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124098.87 FEET.

 FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

=====

 FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU02EV36.DNA
 MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	212.85	41.95	0.60 (0.53)	0.89	1194.3	110.00
2	182.13	45.87	0.60 (0.53)	0.88	1308.8	100.00

3	166.70	48.25	0.60	(0.53)	0.88	1371.9	100.00
4	138.00	55.27	0.60	(0.54)	0.89	1542.5	130.00
5	114.28	88.34	0.60	(0.56)	0.93	2427.8	20100.00
6	99.46	100.42	0.60	(0.56)	0.93	2568.9	13600.00
7	61.98	214.44	0.60	(0.56)	0.93	3822.6	13510.00
8	61.68	223.75	0.60	(0.56)	0.93	3859.7	13500.00

TOTAL AREA (ACRES) = 3859.7

 FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 11

 >>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<
 =====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2680.75	12.70	1.060	0.60 (0.42)	0.70	1518.7	429.00
2	2688.72	14.52	0.957	0.60 (0.42)	0.70	1773.9	425.00
3	2689.23	14.72	0.946	0.60 (0.42)	0.70	1801.9	400.00
4	2690.95	16.38	0.885	0.60 (0.42)	0.70	2034.3	300.00
5	2686.40	24.28	0.676	0.60 (0.42)	0.70	3123.2	210.00
6	2683.36	25.11	0.659	0.60 (0.42)	0.70	3231.7	410.00
7	2675.36	27.24	0.628	0.60 (0.42)	0.71	3509.2	200.00
8	2671.60	28.82	0.605	0.60 (0.42)	0.71	3712.7	230.00
9	2665.47	30.02	0.587	0.60 (0.42)	0.71	3861.1	220.50
10	2653.33	32.71	0.565	0.60 (0.43)	0.71	4182.6	50600.00
11	2650.15	33.69	0.557	0.60 (0.43)	0.71	4326.0	50500.00
12	2644.37	34.96	0.546	0.60 (0.43)	0.71	4510.6	50400.00
13	2582.49	37.94	0.522	0.60 (0.43)	0.72	5073.9	50700.00
14	2294.73	51.73	0.438	0.60 (0.44)	0.74	7591.8	100.00
15	1329.92	83.44	0.348	0.60 (0.47)	0.79	12241.4	31100.00
16	1353.51	116.50	0.287	0.60 (0.50)	0.84	18797.6	13210.00
17	1353.54	131.03	0.270	0.60 (0.51)	0.86	21297.5	11831.00
18	1405.46	154.51	0.249	0.60 (0.52)	0.87	25587.7	11530.00
19	1447.97	174.00	0.231	0.60 (0.53)	0.89	29734.4	11000.00
20	1518.60	196.25	0.221	0.60 (0.55)	0.91	36530.3	10850.00
21	1391.07	218.14	0.214	0.60 (0.55)	0.92	40864.9	11910.00
22	1322.79	230.44	0.210	0.60 (0.55)	0.92	42568.4	12300.00
23	1179.08	264.69	0.200	0.60 (0.56)	0.93	48276.8	12410.00
24	1118.00	297.87	0.189	0.60 (0.56)	0.94	54362.7	12261.00
25	1096.87	310.73	0.185	0.60 (0.56)	0.94	55849.3	10410.00
26	1076.21	323.01	0.182	0.60 (0.56)	0.94	56951.3	12101.10
27	1056.28	332.80	0.178	0.60 (0.56)	0.94	57772.7	10700.00
28	1029.59	350.68	0.173	0.60 (0.56)	0.94	59329.3	10200.00
29	1006.38	364.19	0.170	0.60 (0.57)	0.94	60267.6	12010.00
30	953.77	393.56	0.166	0.60 (0.57)	0.94	60941.3	10210.00
31	883.06	443.15	0.161	0.60 (0.57)	0.94	61440.4	12000.00
32	828.21	513.04	0.154	0.60 (0.57)	0.94	62025.1	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124098.87 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	212.85	41.95	0.494	0.60 (0.53)	0.89	1194.3	110.00
2	182.13	45.87	0.472	0.60 (0.53)	0.88	1308.8	100.00
3	166.70	48.25	0.458	0.60 (0.53)	0.88	1371.9	100.00
4	138.00	55.27	0.417	0.60 (0.54)	0.89	1542.5	130.00

5	114.28	88.34	0.339	0.60	(0.56)	0.93	2427.8	20100.00
6	99.46	100.42	0.317	0.60	(0.56)	0.93	2568.9	13600.00
7	61.98	214.44	0.215	0.60	(0.56)	0.93	3822.6	13510.00
8	61.68	223.75	0.212	0.60	(0.56)	0.93	3859.7	13500.00

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13410.00 = 41710.10 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2893.60	12.70	1.060	0.60 (0.44)	0.74	1880.3	429.00
2	2901.57	14.52	0.957	0.60 (0.44)	0.74	2187.3	425.00
3	2902.08	14.72	0.946	0.60 (0.44)	0.74	2221.1	400.00
4	2903.80	16.38	0.885	0.60 (0.44)	0.74	2500.6	300.00
5	2899.25	24.28	0.676	0.60 (0.44)	0.74	3814.3	210.00
6	2896.21	25.11	0.659	0.60 (0.44)	0.74	3946.5	410.00
7	2888.21	27.24	0.628	0.60 (0.44)	0.74	4284.8	200.00
8	2861.50	28.82	0.605	0.60 (0.44)	0.74	4533.1	230.00
9	2846.47	30.02	0.587	0.60 (0.44)	0.74	4715.8	220.50
10	2843.13	32.71	0.565	0.60 (0.45)	0.74	5113.9	50600.00
11	2842.84	33.69	0.557	0.60 (0.45)	0.74	5285.0	50500.00
12	2840.60	34.96	0.546	0.60 (0.45)	0.75	5506.0	50400.00
13	2785.92	37.94	0.522	0.60 (0.45)	0.75	6154.1	50700.00
14	2711.69	41.95	0.494	0.60 (0.45)	0.75	7000.2	110.00
15	2599.14	45.87	0.472	0.60 (0.45)	0.75	7830.7	100.00
16	2533.93	48.25	0.458	0.60 (0.45)	0.76	8329.3	100.00
17	2447.21	51.73	0.438	0.60 (0.46)	0.76	9048.2	100.00
18	2325.09	55.27	0.417	0.60 (0.46)	0.77	9653.0	130.00
19	1447.71	83.44	0.348	0.60 (0.49)	0.81	14538.2	31100.00
20	1447.69	88.34	0.339	0.60 (0.49)	0.82	15640.0	20100.00
21	1441.50	100.42	0.317	0.60 (0.50)	0.83	18177.1	13600.00
22	1447.69	116.50	0.287	0.60 (0.51)	0.85	21543.3	13210.00
23	1442.94	131.03	0.270	0.60 (0.52)	0.87	24202.9	11831.00
24	1487.14	154.51	0.249	0.60 (0.53)	0.88	28751.3	11530.00
25	1523.25	174.00	0.231	0.60 (0.54)	0.90	33112.3	11000.00
26	1586.56	196.25	0.221	0.60 (0.55)	0.91	40152.9	10850.00
27	1474.60	214.44	0.215	0.60 (0.55)	0.92	43954.7	13510.00
28	1452.93	218.14	0.214	0.60 (0.55)	0.92	44702.2	11910.00
29	1421.60	223.75	0.212	0.60 (0.55)	0.92	45501.5	13500.00
30	1383.87	230.44	0.210	0.60 (0.55)	0.92	46428.0	12300.00
31	1237.06	264.69	0.200	0.60 (0.56)	0.93	52136.5	12410.00
32	1172.98	297.87	0.189	0.60 (0.56)	0.94	58222.4	12261.00
33	1150.69	310.73	0.185	0.60 (0.56)	0.94	59709.0	10410.00
34	1128.92	323.01	0.182	0.60 (0.56)	0.94	60810.9	12101.10
35	1108.11	332.80	0.178	0.60 (0.56)	0.94	61632.3	10700.00
36	1079.80	350.68	0.173	0.60 (0.56)	0.94	63189.0	10200.00
37	1055.62	364.19	0.170	0.60 (0.56)	0.94	64127.3	12010.00
38	1002.10	393.56	0.166	0.60 (0.57)	0.94	64801.0	10210.00
39	929.84	443.15	0.161	0.60 (0.57)	0.94	65300.1	12000.00
40	872.82	513.04	0.154	0.60 (0.57)	0.94	65884.8	10100.00

TOTAL AREA (ACRES) = 65884.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 2903.80 Tc (MIN.) = 16.376
 EFFECTIVE AREA (ACRES) = 2500.56 AREA-AVERAGED Fm (INCH/HR) = 0.44
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.74
 TOTAL AREA (ACRES) = 65884.8
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124098.87 FEET.

```

*****
FLOW PROCESS FROM NODE 13410.00 TO NODE 13412.00 IS CODE = 51
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 178.72 DOWNSTREAM(FEET) = 176.93
CHANNEL LENGTH THRU SUBAREA(FEET) = 169.78 CHANNEL SLOPE = 0.0105
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
CHANNEL FLOW THRU SUBAREA(CFS) = 2903.80
FLOW VELOCITY(FEET/SEC.) = 13.01 FLOW DEPTH(FEET) = 8.63
TRAVEL TIME(MIN.) = 0.22 Tc(MIN.) = 16.59
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124268.65 FEET.

*****
FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 12
-----
>>>>CLEAR MEMORY BANK # 1 <<<<
=====
*****
FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 15.1
-----
>>>>DEFINE MEMORY BANK # 1 <<<<
=====
PEAK FLOWRATE TABLE FILE NAME: 0506101G.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:
STREAM Q Tc Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (ACRES) NODE
1 4.52 82.13 0.60(0.59) 0.98 591.0 10100.00
TOTAL AREA(ACRES) = 591.0

*****
FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 11
-----
>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<
=====
** MAIN STREAM CONFLUENCE DATA **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 2893.60 12.92 1.048 0.60(0.44) 0.74 1880.3 429.00
2 2901.57 14.74 0.945 0.60(0.44) 0.74 2187.3 425.00
3 2902.08 14.94 0.933 0.60(0.44) 0.74 2221.1 400.00
4 2903.80 16.59 0.877 0.60(0.44) 0.74 2500.6 300.00
5 2899.25 24.49 0.672 0.60(0.44) 0.74 3814.3 210.00
6 2896.21 25.32 0.656 0.60(0.44) 0.74 3946.5 410.00
7 2888.21 27.46 0.625 0.60(0.44) 0.74 4284.8 200.00
8 2861.50 29.03 0.601 0.60(0.44) 0.74 4533.1 230.00
9 2846.47 30.24 0.585 0.60(0.44) 0.74 4715.8 220.50
10 2843.13 32.93 0.563 0.60(0.45) 0.74 5113.9 50600.00
11 2842.84 33.90 0.555 0.60(0.45) 0.74 5285.0 50500.00
12 2840.60 35.18 0.545 0.60(0.45) 0.75 5506.0 50400.00
13 2785.92 38.16 0.520 0.60(0.45) 0.75 6154.1 50700.00
14 2711.69 42.17 0.493 0.60(0.45) 0.75 7000.2 110.00
15 2599.14 46.09 0.470 0.60(0.45) 0.75 7830.7 100.00
16 2533.93 48.48 0.457 0.60(0.45) 0.76 8329.3 100.00

```

```

17 2447.21 51.96 0.437 0.60(0.46) 0.76 9048.2 100.00
18 2325.09 55.50 0.416 0.60(0.46) 0.77 9653.0 130.00
19 1447.71 83.70 0.347 0.60(0.49) 0.81 14538.2 31100.00
20 1447.69 88.60 0.339 0.60(0.49) 0.82 15640.0 20100.00
21 1441.50 100.68 0.316 0.60(0.50) 0.83 18177.1 13600.00
22 1447.69 116.76 0.286 0.60(0.51) 0.85 21543.3 13210.00
23 1442.94 131.29 0.270 0.60(0.52) 0.87 24202.9 11831.00
24 1487.14 154.77 0.249 0.60(0.53) 0.88 28751.3 11530.00
25 1523.25 174.26 0.231 0.60(0.54) 0.90 33112.3 11000.00
26 1586.56 196.50 0.221 0.60(0.55) 0.91 40152.9 10850.00
27 1474.60 214.70 0.215 0.60(0.55) 0.92 43954.7 13510.00
28 1452.93 218.40 0.214 0.60(0.55) 0.92 44702.2 11910.00
29 1421.60 224.01 0.212 0.60(0.55) 0.92 45501.5 13500.00
30 1383.87 230.70 0.210 0.60(0.55) 0.92 46428.0 12300.00
31 1237.06 264.96 0.200 0.60(0.56) 0.93 52136.5 12410.00
32 1172.98 298.15 0.189 0.60(0.56) 0.94 58222.4 12261.00
33 1150.69 311.00 0.185 0.60(0.56) 0.94 59709.0 10410.00
34 1128.92 323.29 0.181 0.60(0.56) 0.94 60810.9 12101.10
35 1108.11 333.07 0.178 0.60(0.56) 0.94 61632.3 10700.00
36 1079.80 350.96 0.173 0.60(0.56) 0.94 63189.0 10200.00
37 1055.62 364.47 0.170 0.60(0.56) 0.94 64127.3 12010.00
38 1002.10 393.85 0.166 0.60(0.57) 0.94 64801.0 10210.00
39 929.84 443.44 0.161 0.60(0.57) 0.94 65300.1 12000.00
40 872.82 513.33 0.154 0.60(0.57) 0.94 65884.8 10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124268.65 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 4.52 82.13 0.350 0.60(0.59) 0.98 591.0 10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 14677.00 FEET.

** PEAK FLOW RATE TABLE **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 2895.72 12.92 1.048 0.60(0.45) 0.75 1973.3 429.00
2 2903.76 14.74 0.945 0.60(0.45) 0.75 2293.4 425.00
3 2904.27 14.94 0.933 0.60(0.45) 0.75 2328.6 400.00
4 2906.09 16.59 0.877 0.60(0.45) 0.75 2620.0 300.00
5 2901.83 24.49 0.672 0.60(0.45) 0.75 3990.6 210.00
6 2898.82 25.32 0.656 0.60(0.45) 0.75 4128.7 410.00
7 2890.90 27.46 0.625 0.60(0.45) 0.75 4482.4 200.00
8 2864.24 29.03 0.601 0.60(0.45) 0.75 4742.0 230.00
9 2849.24 30.24 0.585 0.60(0.45) 0.75 4933.4 220.50
10 2846.04 32.93 0.563 0.60(0.45) 0.75 5350.9 50600.00
11 2845.80 33.90 0.555 0.60(0.45) 0.76 5529.0 50500.00
12 2843.61 35.18 0.545 0.60(0.45) 0.76 5759.2 50400.00
13 2789.04 38.16 0.520 0.60(0.45) 0.76 6428.7 50700.00
14 2714.95 42.17 0.493 0.60(0.46) 0.76 7303.7 110.00
15 2602.54 46.09 0.470 0.60(0.46) 0.76 8162.4 100.00
16 2537.41 48.48 0.457 0.60(0.46) 0.77 8678.2 100.00
17 2450.77 51.96 0.437 0.60(0.46) 0.77 9422.1 100.00
18 2328.71 55.50 0.416 0.60(0.46) 0.77 10052.3 130.00
19 1501.11 82.13 0.350 0.60(0.49) 0.82 14857.0 10100.00
20 1452.19 83.70 0.347 0.60(0.49) 0.82 15129.2 31100.00
21 1452.06 88.60 0.339 0.60(0.49) 0.82 16231.0 20100.00
22 1445.58 100.68 0.316 0.60(0.50) 0.84 18768.1 13600.00
23 1451.38 116.76 0.286 0.60(0.51) 0.85 22134.3 13210.00

```


24	1446.42	131.29	0.270	0.60	(0.52)	0.87	24793.9	11831.00
25	1490.35	154.77	0.249	0.60	(0.53)	0.88	29342.3	11530.00
26	1526.23	174.26	0.231	0.60	(0.54)	0.90	33703.3	11000.00
27	1589.40	196.50	0.221	0.60	(0.55)	0.91	40743.9	10850.00
28	1477.38	214.70	0.215	0.60	(0.55)	0.92	44545.7	13510.00
29	1455.69	218.40	0.214	0.60	(0.55)	0.92	45293.2	11910.00
30	1424.34	224.01	0.212	0.60	(0.55)	0.92	46092.5	13500.00
31	1386.58	230.70	0.210	0.60	(0.55)	0.92	47019.0	12300.00
32	1239.63	264.96	0.200	0.60	(0.56)	0.93	52727.5	12410.00
33	1175.42	298.15	0.189	0.60	(0.56)	0.94	58813.4	12261.00
34	1153.08	311.00	0.185	0.60	(0.56)	0.94	60300.0	10410.00
35	1131.26	323.29	0.181	0.60	(0.56)	0.94	61401.9	12101.10
36	1110.41	333.07	0.178	0.60	(0.56)	0.94	62223.3	10700.00
37	1082.03	350.96	0.173	0.60	(0.56)	0.94	63780.0	10200.00
38	1057.81	364.47	0.170	0.60	(0.57)	0.94	64718.3	12010.00
39	1004.24	393.85	0.166	0.60	(0.57)	0.94	65392.0	10210.00
40	931.92	443.44	0.161	0.60	(0.57)	0.94	65891.0	12000.00
41	874.80	513.33	0.154	0.60	(0.57)	0.94	66475.8	10100.00
TOTAL AREA (ACRES) =								66475.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 2906.09 Tc (MIN.) = 16.593
EFFECTIVE AREA (ACRES) = 2619.96 AREA-AVERAGED Fm (INCH/HR) = 0.45
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.75
TOTAL AREA (ACRES) = 66475.8
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124268.65 FEET.

FLOW PROCESS FROM NODE 13412.00 TO NODE 13700.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 176.93 DOWNSTREAM (FEET) = 170.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 260.10 CHANNEL SLOPE = 0.0266
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00
CHANNEL FLOW THRU SUBAREA (CFS) = 2906.09
FLOW VELOCITY (FEET/SEC.) = 18.43 FLOW DEPTH (FEET) = 7.25
TRAVEL TIME (MIN.) = 0.24 Tc (MIN.) = 16.83
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124528.75 FEET.

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P508XX02.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2.36	34.92	0.60 (0.59)	0.99	131.3	50800.00

TOTAL AREA (ACRES) = 131.3

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2895.72	13.15	1.034	0.60 (0.45)	0.75	1973.3	429.00
2	2903.76	14.97	0.931	0.60 (0.45)	0.75	2293.4	425.00
3	2904.27	15.18	0.924	0.60 (0.45)	0.75	2328.6	400.00
4	2906.09	16.83	0.870	0.60 (0.45)	0.75	2620.0	300.00
5	2901.83	24.73	0.667	0.60 (0.45)	0.75	3990.6	210.00
6	2898.82	25.56	0.653	0.60 (0.45)	0.75	4128.7	410.00
7	2890.90	27.69	0.621	0.60 (0.45)	0.75	4482.4	200.00
8	2864.24	29.27	0.598	0.60 (0.45)	0.75	4742.0	230.00
9	2849.24	30.48	0.583	0.60 (0.45)	0.75	4933.4	220.50
10	2846.04	33.17	0.561	0.60 (0.45)	0.75	5350.9	50600.00
11	2845.80	34.14	0.553	0.60 (0.45)	0.76	5529.0	50500.00
12	2843.61	35.42	0.543	0.60 (0.45)	0.76	5759.2	50400.00
13	2789.04	38.40	0.518	0.60 (0.45)	0.76	6428.7	50700.00
14	2714.95	42.41	0.491	0.60 (0.46)	0.76	7303.7	110.00
15	2602.54	46.33	0.469	0.60 (0.46)	0.76	8162.4	100.00
16	2537.41	48.72	0.455	0.60 (0.46)	0.77	8678.2	100.00
17	2450.77	52.20	0.435	0.60 (0.46)	0.77	9422.1	100.00
18	2328.71	55.75	0.415	0.60 (0.46)	0.77	10052.3	130.00
19	1501.11	82.41	0.350	0.60 (0.49)	0.82	14857.0	10100.00
20	1452.19	83.98	0.347	0.60 (0.49)	0.82	15129.2	31100.00
21	1452.06	88.88	0.338	0.60 (0.49)	0.82	16231.0	20100.00
22	1445.58	100.96	0.316	0.60 (0.50)	0.84	18768.1	13600.00
23	1451.38	117.04	0.286	0.60 (0.51)	0.85	22134.3	13210.00
24	1446.42	131.57	0.270	0.60 (0.52)	0.87	24793.9	11831.00
25	1490.35	155.04	0.248	0.60 (0.53)	0.88	29342.3	11530.00
26	1526.23	174.53	0.231	0.60 (0.54)	0.90	33703.3	11000.00
27	1589.40	196.78	0.221	0.60 (0.55)	0.91	40743.9	10850.00
28	1477.38	214.98	0.215	0.60 (0.55)	0.92	44545.7	13510.00
29	1455.69	218.68	0.214	0.60 (0.55)	0.92	45293.2	11910.00
30	1424.34	224.29	0.212	0.60 (0.55)	0.92	46092.5	13500.00
31	1386.58	230.98	0.210	0.60 (0.55)	0.92	47019.0	12300.00
32	1239.63	265.25	0.199	0.60 (0.56)	0.93	52727.5	12410.00
33	1175.42	298.44	0.189	0.60 (0.56)	0.94	58813.4	12261.00
34	1153.08	311.30	0.185	0.60 (0.56)	0.94	60300.0	10410.00
35	1131.26	323.59	0.181	0.60 (0.56)	0.94	61401.9	12101.10
36	1110.41	333.37	0.178	0.60 (0.56)	0.94	62223.3	10700.00
37	1082.03	351.26	0.173	0.60 (0.56)	0.94	63780.0	10200.00
38	1057.81	364.77	0.169	0.60 (0.57)	0.94	64718.3	12010.00
39	1004.24	394.15	0.166	0.60 (0.57)	0.94	65392.0	10210.00
40	931.92	443.75	0.161	0.60 (0.57)	0.94	65891.0	12000.00
41	874.80	513.65	0.154	0.60 (0.57)	0.94	66475.8	10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124528.75 FEET.							

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2.36	34.92	0.547	0.60 (0.59)	0.99	131.3	50800.00

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 136 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 2-YR EV OCT 2022 ROKAMOTO *

FILE NAME: RU02EV36.DAT
TIME/DATE OF STUDY: 13:54 10/24/2022

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 2.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 1.806
- 2) 10.00; 1.204
- 3) 15.00; 0.925
- 4) 20.00; 0.762
- 5) 25.00; 0.659
- 6) 30.00; 0.585
- 7) 40.00; 0.504
- 8) 50.00; 0.447
- 9) 60.00; 0.390
- 10) 90.00; 0.336
- 11) 120.00; 0.280
- 12) 180.00; 0.226
- 13) 360.00; 0.170
- 14) 1200.00; 0.080

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH LIP (FT)	MANNING HIKE FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312 0.167 0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:

- 1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13600.00 TO NODE 13600.50 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 488.61
ELEVATION DATA: UPSTREAM(FEET) = 872.12 DOWNSTREAM(FEET) = 744.80

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 10.995
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 1.148
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "OPEN BRUSH"	-	3.39	0.60	1.000	65	11.00

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 1.67
TOTAL AREA(ACRES) = 3.39 PEAK FLOW RATE(CFS) = 1.67

FLOW PROCESS FROM NODE 13600.50 TO NODE 13601.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 744.80 DOWNSTREAM(FEET) = 707.32
CHANNEL LENGTH THRU SUBAREA(FEET) = 418.30 CHANNEL SLOPE = 0.0896
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 1.024
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.45	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3.10
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.13
AVERAGE FLOW DEPTH(FEET) = 0.58 TRAVEL TIME(MIN.) = 2.23
Tc(MIN.) = 13.22
SUBAREA AREA(ACRES) = 7.45 SUBAREA RUNOFF(CFS) = 2.84
EFFECTIVE AREA(ACRES) = 10.84 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 10.8 PEAK FLOW RATE(CFS) = 4.14

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.64 FLOW VELOCITY(FEET/SEC.) = 3.33
LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13601.00 = 906.91 FEET.

FLOW PROCESS FROM NODE 13601.00 TO NODE 13602.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 707.32 DOWNSTREAM(FEET) = 657.12
CHANNEL LENGTH THRU SUBAREA(FEET) = 777.60 CHANNEL SLOPE = 0.0646
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.862

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include USER-DEFINED entries with various area and loss rate values.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 7.89
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.50
AVERAGE FLOW DEPTH(FEET) = 0.87 TRAVEL TIME(MIN.) = 3.70
Tc(MIN.) = 16.93
SUBAREA AREA(ACRES) = 30.96 SUBAREA RUNOFF(CFS) = 7.31
EFFECTIVE AREA(ACRES) = 41.80 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 41.8 PEAK FLOW RATE(CFS) = 9.87

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.94 FLOW VELOCITY(FEET/SEC.) = 3.70
LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13602.00 = 1684.51 FEET.

FLOW PROCESS FROM NODE 13602.00 TO NODE 13603.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 657.12 DOWNSTREAM(FEET) = 584.58
CHANNEL LENGTH THRU SUBAREA(FEET) = 1186.54 CHANNEL SLOPE = 0.0611
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.716

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include USER-DEFINED entries with various area and loss rate values.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 11.12
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.73
AVERAGE FLOW DEPTH(FEET) = 1.00 TRAVEL TIME(MIN.) = 5.30
Tc(MIN.) = 22.23
SUBAREA AREA(ACRES) = 23.36 SUBAREA RUNOFF(CFS) = 2.44

EFFECTIVE AREA(ACRES) = 65.16 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 65.2 PEAK FLOW RATE(CFS) = 9.87
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.96 FLOW VELOCITY(FEET/SEC.) = 3.60
LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13603.00 = 2871.05 FEET.

FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 584.58 DOWNSTREAM(FEET) = 544.91
CHANNEL LENGTH THRU SUBAREA(FEET) = 860.98 CHANNEL SLOPE = 0.0461
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.635

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include USER-DEFINED entries with various area and loss rate values.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 10.22
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.28
AVERAGE FLOW DEPTH(FEET) = 1.02 TRAVEL TIME(MIN.) = 4.38
Tc(MIN.) = 26.60

SUBAREA AREA(ACRES) = 21.24 SUBAREA RUNOFF(CFS) = 0.68
EFFECTIVE AREA(ACRES) = 86.40 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 86.4 PEAK FLOW RATE(CFS) = 9.87
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.00 FLOW VELOCITY(FEET/SEC.) = 3.26
LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13620.00 = 3732.03 FEET.

FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 13522.00 TO NODE 13522.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: S35X02.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:

```

STREAM      Q      Tc      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS) (MIN.) (INCH/HR)      (ACRES)      NODE
1          18.94 124.94 0.60( 0.57) 0.95    1542.7 13510.00
2          19.25 134.44 0.60( 0.57) 0.94    1579.8 13500.00
TOTAL AREA(ACRES) =      1579.8

*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13522.00 IS CODE = 14.0
-----
>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<
=====
MAIN-STREAM MEMORY DEFINED AS FOLLOWS:
STREAM      Q      Tc      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS) (MIN.) (INCH/HR)      (ACRES)      NODE
1          18.94 124.94 0.60( 0.57) 0.95    1542.7 13510.00
2          19.25 134.44 0.60( 0.57) 0.94    1579.8 13500.00
TOTAL AREA(ACRES) =      1579.8

*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13620.00 IS CODE = 51
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 632.19 DOWNSTREAM(FEET) = 544.91
CHANNEL LENGTH THRU SUBAREA(FEET) = 2062.96 CHANNEL SLOPE = 0.0423
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.261
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL      AREA      Fp      Ap      SCS
LAND USE      GROUP      (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED      -      17.68      0.60      1.000      -
USER-DEFINED      -      2.36      0.60      1.000      -
USER-DEFINED      -      0.60      0.60      1.000      -
USER-DEFINED      -      0.22      0.60      1.000      -
USER-DEFINED      -      2.22      0.60      1.000      -
USER-DEFINED      -      3.42      0.60      1.000      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 19.25
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.06
AVERAGE FLOW DEPTH(FEET) = 1.13 TRAVEL TIME(MIN.) = 6.80
Tc(MIN.) = 141.24
SUBAREA AREA(ACRES) = 26.50 SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 1606.33 AREA-AVERAGED Fm(INCH/HR) = 0.57
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.95
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 1606.3 PEAK FLOW RATE(CFS) = 20.58

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.16 FLOW VELOCITY(FEET/SEC.) = 5.13
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13620.00 TO NODE 13620.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====
MAINLINE Tc(MIN.) = 141.24
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.261
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL      AREA      Fp      Ap      SCS
LAND USE      GROUP      (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED      -      1.44      0.60      1.000      -
USER-DEFINED      -      0.01      0.60      1.000      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 1.45 SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 1607.78 AREA-AVERAGED Fm(INCH/HR) = 0.57
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.95
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 1607.8 PEAK FLOW RATE(CFS) = 20.58
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

*****
FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 11
-----
>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<
=====
** MAIN STREAM CONFLUENCE DATA **
STREAM      Q      Tc      Intensity      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS) (MIN.) (INCH/HR) (INCH/HR)      (ACRES)      NODE
1          20.27 131.83 0.269 0.60( 0.57) 0.95    1570.7 13510.00
2          20.58 141.24 0.261 0.60( 0.57) 0.95    1607.8 13500.00
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **
STREAM      Q      Tc      Intensity      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS) (MIN.) (INCH/HR) (INCH/HR)      (ACRES)      NODE
1          9.87 26.60 0.635 0.60( 0.60) 1.00    86.4 13600.00
LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13620.00 = 3732.03 FEET.

** PEAK FLOW RATE TABLE **
STREAM      Q      Tc      Intensity      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS) (MIN.) (INCH/HR) (INCH/HR)      (ACRES)      NODE
1          29.08 26.60 0.635 0.60( 0.57) 0.96    403.4 13600.00
2          20.27 131.83 0.269 0.60( 0.57) 0.95    1657.1 13510.00
3          20.58 141.24 0.261 0.60( 0.57) 0.95    1694.2 13500.00
TOTAL AREA(ACRES) = 1694.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
PEAK FLOW RATE(CFS) = 29.08 Tc(MIN.) = 26.603
EFFECTIVE AREA(ACRES) = 403.36 AREA-AVERAGED Fm(INCH/HR) = 0.57
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.95
TOTAL AREA(ACRES) = 1694.2
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13620.00 TO NODE 13640.00 IS CODE = 51
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 544.91 DOWNSTREAM(FEET) = 489.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1384.37 CHANNEL SLOPE = 0.0404
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.578
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 5.39 0.60 1.000 -
USER-DEFINED - 16.30 0.60 1.000 -
USER-DEFINED - 4.08 0.60 1.000 -
USER-DEFINED - 12.36 0.60 1.000 -
USER-DEFINED - 11.23 0.60 1.000 -
USER-DEFINED - 5.16 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 29.08
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.48
AVERAGE FLOW DEPTH(FEET) = 1.33 TRAVEL TIME(MIN.) = 4.21
Tc(MIN.) = 30.82
SUBAREA AREA(ACRES) = 54.52 SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 457.88 AREA-AVERAGED Fm(INCH/HR) = 0.58
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.96
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 1748.7 PEAK FLOW RATE(CFS) = 29.08
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.33 FLOW VELOCITY(FEET/SEC.) = 5.48
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 30.82
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.578
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 53.93 0.60 1.000 -
USER-DEFINED - 0.45 0.60 1.000 -
USER-DEFINED - 3.98 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 58.36 SUBAREA RUNOFF(CFS) = 0.00

```

```

EFFECTIVE AREA(ACRES) = 516.24 AREA-AVERAGED Fm(INCH/HR) = 0.58
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.97
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 1807.1 PEAK FLOW RATE(CFS) = 29.08
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 15.1
-----
>>>>DEFINE MEMORY BANK # 3 <<<<
=====
PEAK FLOWRATE TABLE FILE NAME: P201XX02.DNA
MEMORY BANK # 3 DEFINED AS FOLLOWS:
STREAM Q Tc Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 19.79 22.40 0.60(0.51) 0.85 133.8 20100.00
TOTAL AREA(ACRES) = 133.8

```

```

*****
FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 11
-----
>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<
=====

```

```

** MAIN STREAM CONFLUENCE DATA **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 29.08 30.82 0.578 0.60(0.58) 0.97 516.2 13600.00
2 20.27 136.44 0.265 0.60(0.57) 0.95 1770.0 13510.00
3 20.58 145.80 0.257 0.60(0.57) 0.95 1807.1 13500.00
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

```

```

** MEMORY BANK # 3 CONFLUENCE DATA **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 19.79 22.40 0.713 0.60(0.51) 0.85 133.8 20100.00
LONGEST FLOWPATH FROM NODE 20100.00 TO NODE 13640.00 = 5247.00 FEET.

```

```

** PEAK FLOW RATE TABLE **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 48.87 22.40 0.713 0.60(0.56) 0.94 509.0 20100.00
2 37.41 30.82 0.578 0.60(0.57) 0.94 650.0 13600.00
3 24.09 136.44 0.265 0.60(0.57) 0.95 1903.8 13510.00
4 24.27 145.80 0.257 0.60(0.57) 0.94 1940.9 13500.00
TOTAL AREA(ACRES) = 1940.9

```

```

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
PEAK FLOW RATE(CFS) = 48.87 Tc(MIN.) = 22.397
EFFECTIVE AREA(ACRES) = 509.02 AREA-AVERAGED Fm(INCH/HR) = 0.56
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.94
TOTAL AREA(ACRES) = 1940.9
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13640.00 TO NODE 13641.00 IS CODE = 51
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 489.00 DOWNSTREAM(FEET) = 436.89
CHANNEL LENGTH THRU SUBAREA(FEET) = 2994.52 CHANNEL SLOPE = 0.0174
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.558
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.96 0.60 1.000 -
USER-DEFINED - 0.01 0.60 1.000 -
USER-DEFINED - 1.56 0.60 1.000 -
USER-DEFINED - 10.45 0.60 1.000 -
USER-DEFINED - 44.94 0.60 1.000 -
USER-DEFINED - 9.66 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 48.87
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.56
AVERAGE FLOW DEPTH(FEET) = 1.89 TRAVEL TIME(MIN.) = 10.93
Tc(MIN.) = 33.33
SUBAREA AREA(ACRES) = 67.58 SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 576.60 AREA-AVERAGED Fm(INCH/HR) = 0.57
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.94
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 2008.4 PEAK FLOW RATE(CFS) = 48.87
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.89 FLOW VELOCITY(FEET/SEC.) = 4.56
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13641.00 = 25056.61 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13641.00 TO NODE 13641.00 IS CODE = 81

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====

```

```

MAINLINE Tc(MIN.) = 33.33
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.558
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 16.49 0.60 1.000 -
USER-DEFINED - 20.39 0.60 1.000 -
USER-DEFINED - 7.02 0.60 1.000 -
USER-DEFINED - 12.58 0.60 1.000 -
USER-DEFINED - 42.49 0.60 1.000 -
USER-DEFINED - 5.73 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 104.70 SUBAREA RUNOFF(CFS) = 0.00

```

```

EFFECTIVE AREA(ACRES) = 681.30 AREA-AVERAGED Fm(INCH/HR) = 0.57
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.95
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 2113.1 PEAK FLOW RATE(CFS) = 48.87
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13641.00 TO NODE 13641.00 IS CODE = 81

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====

```

```

MAINLINE Tc(MIN.) = 33.33
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.558
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 1.78 0.60 1.000 -
USER-DEFINED - 6.25 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 8.03 SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 689.33 AREA-AVERAGED Fm(INCH/HR) = 0.57
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.95
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 2121.2 PEAK FLOW RATE(CFS) = 48.87
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13641.00 TO NODE 13642.00 IS CODE = 51

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====

```

```

ELEVATION DATA: UPSTREAM(FEET) = 436.89 DOWNSTREAM(FEET) = 394.80
CHANNEL LENGTH THRU SUBAREA(FEET) = 2814.16 CHANNEL SLOPE = 0.0150
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.480
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.67 0.60 1.000 -
USER-DEFINED - 24.24 0.60 1.000 -
USER-DEFINED - 1.34 0.60 1.000 -
USER-DEFINED - 74.98 0.60 1.000 -
USER-DEFINED - 101.12 0.60 1.000 -
USER-DEFINED - 16.90 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 48.87
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.32
AVERAGE FLOW DEPTH(FEET) = 1.94 TRAVEL TIME(MIN.) = 10.87

```


Tc(MIN.) = 44.20
SUBAREA AREA(ACRES) = 219.25 SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 908.58 AREA-AVERAGED Fm(INCH/HR) = 0.58
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.97
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 2340.4 PEAK FLOW RATE(CFS) = 48.87
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.94 FLOW VELOCITY(FEET/SEC.) = 4.32
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13642.00 = 27870.77 FEET.

FLOW PROCESS FROM NODE 13642.00 TO NODE 13642.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 44.20
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.480
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 9.95 0.60 1.000 -
USER-DEFINED - 10.02 0.60 1.000 -
USER-DEFINED - 4.45 0.60 1.000 -
USER-DEFINED - 179.37 0.60 1.000 -
USER-DEFINED - 11.47 0.60 1.000 -
USER-DEFINED - 0.17 0.60 0.850 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 215.43 SUBAREA RUNOFF(CFS) = 0.01
EFFECTIVE AREA(ACRES) = 1124.01 AREA-AVERAGED Fm(INCH/HR) = 0.58
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.97
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 2555.8 PEAK FLOW RATE(CFS) = 48.87
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13642.00 TO NODE 13642.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 44.20
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.480
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.03 0.60 0.850 -
USER-DEFINED - 5.14 0.60 1.000 -
USER-DEFINED - 11.22 0.60 1.000 -
USER-DEFINED - 0.33 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 16.72 SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 1140.73 AREA-AVERAGED Fm(INCH/HR) = 0.58
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.97
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 2572.6 PEAK FLOW RATE(CFS) = 48.87
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13642.00 TO NODE 13643.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 394.80 DOWNSTREAM(FEET) = 342.39
CHANNEL LENGTH THRU SUBAREA(FEET) = 2913.57 CHANNEL SLOPE = 0.0180
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.420
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.22 0.60 1.000 -
USER-DEFINED - 2.17 0.60 1.000 -
USER-DEFINED - 9.19 0.60 1.000 -
USER-DEFINED - 67.57 0.60 1.000 -
USER-DEFINED - 35.19 0.60 1.000 -
USER-DEFINED - 30.67 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 48.87
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.61
AVERAGE FLOW DEPTH(FEET) = 1.88 TRAVEL TIME(MIN.) = 10.53
Tc(MIN.) = 54.73
SUBAREA AREA(ACRES) = 145.01 SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 1285.74 AREA-AVERAGED Fm(INCH/HR) = 0.59
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.98
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 2717.6 PEAK FLOW RATE(CFS) = 48.87
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.88 FLOW VELOCITY(FEET/SEC.) = 4.61
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13643.00 = 30784.34 FEET.

FLOW PROCESS FROM NODE 13643.00 TO NODE 13643.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 54.73
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.420
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS

LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
USER-DEFINED	-	0.89	0.60	1.000	-
USER-DEFINED	-	20.65	0.60	1.000	-
USER-DEFINED	-	2.69	0.60	1.000	-
USER-DEFINED	-	8.45	0.60	1.000	-
USER-DEFINED	-	96.93	0.60	1.000	-
USER-DEFINED	-	13.19	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 142.80 SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 1428.54 AREA-AVERAGED Fm(INCH/HR) = 0.59
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.98
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 2860.4 PEAK FLOW RATE(CFS) = 48.87
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13643.00 TO NODE 13643.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 54.73
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.420
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	42.54	0.60	1.000	-
USER-DEFINED	-	16.96	0.60	1.000	-
USER-DEFINED	-	80.60	0.60	1.000	-
USER-DEFINED	-	1.56	0.60	1.000	-
USER-DEFINED	-	2.00	0.60	1.000	-
USER-DEFINED	-	3.11	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 146.77 SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 1575.31 AREA-AVERAGED Fm(INCH/HR) = 0.59
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.98
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 3007.1 PEAK FLOW RATE(CFS) = 48.87
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13643.00 TO NODE 13660.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 342.39 DOWNSTREAM(FEET) = 300.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1591.23 CHANNEL SLOPE = 0.0266
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.392

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.89	0.60	1.000	-
USER-DEFINED	-	23.73	0.60	1.000	-
USER-DEFINED	-	0.27	0.60	1.000	-
USER-DEFINED	-	19.87	0.60	1.000	-
USER-DEFINED	-	6.40	0.60	1.000	-
USER-DEFINED	-	3.14	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 48.87
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.35
AVERAGE FLOW DEPTH(FEET) = 1.74 TRAVEL TIME(MIN.) = 4.95
Tc(MIN.) = 59.68
SUBAREA AREA(ACRES) = 54.30 SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 1629.61 AREA-AVERAGED Fm(INCH/HR) = 0.59
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.98
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 3061.4 PEAK FLOW RATE(CFS) = 48.87
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.74 FLOW VELOCITY(FEET/SEC.) = 5.35
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 32375.57 FEET.

FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 59.68
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.392
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.67	0.60	1.000	-
USER-DEFINED	-	9.52	0.60	1.000	-
USER-DEFINED	-	0.71	0.60	1.000	-
USER-DEFINED	-	0.22	0.60	1.000	-
USER-DEFINED	-	39.42	0.60	1.000	-
USER-DEFINED	-	0.62	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 51.16 SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 1680.77 AREA-AVERAGED Fm(INCH/HR) = 0.59
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.98
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 3112.6 PEAK FLOW RATE(CFS) = 48.87
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 59.68

* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.392

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.11	0.60	1.000	-
USER-DEFINED	-	0.77	0.60	1.000	-
USER-DEFINED	-	0.22	0.60	1.000	-
USER-DEFINED	-	2.69	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 3.79 SUBAREA RUNOFF(CFS) = 0.00

EFFECTIVE AREA(ACRES) = 1684.56 AREA-AVERAGED Fm(INCH/HR) = 0.59

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.98

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 3116.4 PEAK FLOW RATE(CFS) = 48.87

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13643.00 TO NODE 13660.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<

FLOW PROCESS FROM NODE 13659.00 TO NODE 13659.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<

PEAK FLOWRATE TABLE FILE NAME: 2P02EVAA.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	140.95	18.14	0.60(0.21)	0.35	167.3	110.00
2	140.05	21.10	0.60(0.22)	0.37	199.3	100.00
3	133.31	22.95	0.60(0.22)	0.37	211.1	100.00
4	102.00	28.72	0.60(0.24)	0.40	221.1	130.00
TOTAL AREA(ACRES) =						221.1

FLOW PROCESS FROM NODE 13659.00 TO NODE 13660.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<

>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 338.00 DOWNSTREAM(FEET) = 300.00

FLOW LENGTH(FEET) = 881.07 MANNING'S N = 0.013

ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000

DEPTH OF FLOW IN 36.0 INCH PIPE IS 15.2 INCHES

PIPE-FLOW VELOCITY(FEET/SEC.) = 17.22

ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1

PIPE-FLOW(CFS) = 48.87

PIPE TRAVEL TIME(MIN.) = 0.85 Tc(MIN.) = 60.53

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	48.87	60.53	0.389	0.60(0.59)	0.98	1684.6	20100.00
2	37.41	71.62	0.369	0.60(0.59)	0.98	1825.6	13600.00
3	24.09	182.03	0.225	0.60(0.58)	0.97	3079.3	13510.00
4	24.27	191.30	0.222	0.60(0.58)	0.97	3116.4	13500.00
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.							

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	140.95	18.14	0.823	0.60(0.21)	0.35	167.3	110.00
2	140.05	21.10	0.739	0.60(0.22)	0.37	199.3	100.00
3	133.31	22.95	0.701	0.60(0.22)	0.37	211.1	100.00
4	102.00	28.72	0.604	0.60(0.24)	0.40	221.1	130.00
LONGEST FLOWPATH FROM NODE 130.00 TO NODE 13660.00 = 6327.50 FEET.							

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	171.92	18.14	0.823	0.60(0.49)	0.83	672.1	110.00
2	172.42	21.10	0.739	0.60(0.49)	0.83	786.6	100.00
3	166.70	22.95	0.701	0.60(0.50)	0.83	849.7	100.00
4	138.00	28.72	0.604	0.60(0.51)	0.86	1020.3	130.00
5	114.28	60.53	0.389	0.60(0.55)	0.91	1905.7	20100.00
6	99.46	71.62	0.369	0.60(0.55)	0.92	2046.7	13600.00
7	61.98	182.03	0.225	0.60(0.56)	0.93	3300.4	13510.00
8	61.68	191.30	0.222	0.60(0.56)	0.93	3337.5	13500.00
TOTAL AREA(ACRES) =						3337.5	

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 172.42 Tc(MIN.) = 21.104

EFFECTIVE AREA(ACRES) = 786.59 AREA-AVERAGED Fm(INCH/HR) = 0.49

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.92

TOTAL AREA(ACRES) = 3337.5

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 21.10

* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.739

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

USER-DEFINED - 1.11 0.60 1.000 -
 USER-DEFINED - 0.44 0.60 1.000 -
 USER-DEFINED - 1.49 0.60 1.000 -
 USER-DEFINED - 1.70 0.60 1.000 -
 USER-DEFINED - 1.09 0.60 1.000 -
 USER-DEFINED - 18.57 0.60 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 24.40 SUBAREA RUNOFF (CFS) = 3.06
 EFFECTIVE AREA (ACRES) = 810.99 AREA-AVERAGED Fm (INCH/HR) = 0.50
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83
 TOTAL AREA (ACRES) = 3361.9 PEAK FLOW RATE (CFS) = 176.02

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	203.08	18.14	0.823	0.60 (0.50)	0.83	696.5	110.00
2	176.02	21.10	0.739	0.60 (0.50)	0.83	811.0	100.00
3	166.70	22.95	0.701	0.60 (0.50)	0.83	874.1	100.00
4	138.00	28.72	0.604	0.60 (0.52)	0.86	1044.7	130.00
5	114.28	60.53	0.389	0.60 (0.55)	0.91	1930.1	20100.00
6	99.46	71.62	0.369	0.60 (0.55)	0.92	2071.1	13600.00
7	61.98	182.03	0.225	0.60 (0.56)	0.93	3324.8	13510.00
8	61.68	191.30	0.222	0.60 (0.56)	0.93	3361.9	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 203.08 Tc (MIN.) = 18.14
 AREA-AVERAGED Fm (INCH/HR) = 0.50 AREA-AVERAGED Fp (INCH/HR) = 0.60
 AREA-AVERAGED Ap = 0.83 EFFECTIVE AREA (ACRES) = 696.55

 FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 18.14

* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.823

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	12.39	0.60	1.000	-
USER-DEFINED	-	2.30	0.60	1.000	-
USER-DEFINED	-	5.19	0.60	1.000	-
USER-DEFINED	-	28.71	0.60	1.000	-
USER-DEFINED	-	0.17	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 48.76 SUBAREA RUNOFF (CFS) = 9.78

EFFECTIVE AREA (ACRES) = 745.31 AREA-AVERAGED Fm (INCH/HR) = 0.51

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.84

TOTAL AREA (ACRES) = 3410.7 PEAK FLOW RATE (CFS) = 212.85

 FLOW PROCESS FROM NODE 13660.00 TO NODE 13680.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 300.00 DOWNSTREAM (FEET) = 288.00

CHANNEL LENGTH THRU SUBAREA (FEET) = 933.89 CHANNEL SLOPE = 0.0128
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.746

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.22	0.60	1.000	-
USER-DEFINED	-	9.23	0.60	1.000	-
USER-DEFINED	-	0.54	0.60	1.000	-
USER-DEFINED	-	5.66	0.60	1.000	-
USER-DEFINED	-	3.66	0.60	1.000	-
USER-DEFINED	-	0.67	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 214.17

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.88

AVERAGE FLOW DEPTH (FEET) = 3.48 TRAVEL TIME (MIN.) = 2.65

Tc (MIN.) = 20.79

SUBAREA AREA (ACRES) = 19.98 SUBAREA RUNOFF (CFS) = 2.62

EFFECTIVE AREA (ACRES) = 765.29 AREA-AVERAGED Fm (INCH/HR) = 0.51

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.85

TOTAL AREA (ACRES) = 3430.6 PEAK FLOW RATE (CFS) = 212.85

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 3.47 FLOW VELOCITY (FEET/SEC.) = 5.88

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13680.00 = 34190.53 FEET.

 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 20.79

* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.746

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.56	0.60	1.000	-
USER-DEFINED	-	9.40	0.60	1.000	-
USER-DEFINED	-	2.76	0.60	1.000	-
USER-DEFINED	-	17.38	0.60	1.000	-
USER-DEFINED	-	2.46	0.60	1.000	-
USER-DEFINED	-	5.56	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 39.12 SUBAREA RUNOFF (CFS) = 5.14

EFFECTIVE AREA (ACRES) = 804.41 AREA-AVERAGED Fm (INCH/HR) = 0.51

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.85

TOTAL AREA (ACRES) = 3469.8 PEAK FLOW RATE (CFS) = 212.85

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 20.79
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.746
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 0.65 0.60 1.000 -
 USER-DEFINED - 1.70 0.60 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 2.35 SUBAREA RUNOFF(CFS) = 0.31
 EFFECTIVE AREA(ACRES) = 806.76 AREA-AVERAGED Fm(INCH/HR) = 0.51
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.85
 TOTAL AREA(ACRES) = 3472.1 PEAK FLOW RATE(CFS) = 212.85
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13660.00 TO NODE 13680.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<<
 =====

 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<
 =====

MAINLINE Tc(MIN.) = 20.79
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.746
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 5.29 0.60 1.000 -
 USER-DEFINED - 31.25 0.60 1.000 -
 USER-DEFINED - 0.22 0.60 1.000 -
 USER-DEFINED - 6.26 0.60 1.000 -
 USER-DEFINED - 0.07 0.60 1.000 -
 USER-DEFINED - 0.22 0.60 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 43.31 SUBAREA RUNOFF(CFS) = 5.69
 EFFECTIVE AREA(ACRES) = 850.07 AREA-AVERAGED Fm(INCH/HR) = 0.52
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.86
 TOTAL AREA(ACRES) = 3515.4 PEAK FLOW RATE(CFS) = 212.85
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<
 =====

MAINLINE Tc(MIN.) = 20.79
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.746
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 2.47 0.60 0.850 -
 USER-DEFINED - 3.06 0.60 0.850 -
 USER-DEFINED - 17.76 0.60 0.500 -

USER-DEFINED - 7.31 0.60 0.500 -
 USER-DEFINED - 0.34 0.60 1.000 -
 USER-DEFINED - 8.22 0.60 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.659
 SUBAREA AREA(ACRES) = 39.16 SUBAREA RUNOFF(CFS) = 12.36
 EFFECTIVE AREA(ACRES) = 889.23 AREA-AVERAGED Fm(INCH/HR) = 0.51
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.85
 TOTAL AREA(ACRES) = 3554.6 PEAK FLOW RATE(CFS) = 212.85
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<
 =====

MAINLINE Tc(MIN.) = 20.79
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.746
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 0.53 0.60 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 0.53 SUBAREA RUNOFF(CFS) = 0.07
 EFFECTIVE AREA(ACRES) = 889.76 AREA-AVERAGED Fm(INCH/HR) = 0.51
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.85
 TOTAL AREA(ACRES) = 3555.1 PEAK FLOW RATE(CFS) = 212.85
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13680.00 TO NODE 13682.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<<
 =====

ELEVATION DATA: UPSTREAM(FEET) = 288.00 DOWNSTREAM(FEET) = 242.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2860.77 CHANNEL SLOPE = 0.0161
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.611

SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 0.22 0.60 1.000 -
 USER-DEFINED - 5.28 0.60 1.000 -
 USER-DEFINED - 0.52 0.60 1.000 -
 USER-DEFINED - 3.61 0.60 1.000 -
 USER-DEFINED - 0.67 0.60 1.000 -
 USER-DEFINED - 1.37 0.60 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 212.91
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.40
 AVERAGE FLOW DEPTH(FEET) = 3.33 TRAVEL TIME(MIN.) = 7.46
 Tc(MIN.) = 28.24
 SUBAREA AREA(ACRES) = 11.67 SUBAREA RUNOFF(CFS) = 0.12
 EFFECTIVE AREA(ACRES) = 901.43 AREA-AVERAGED Fm(INCH/HR) = 0.51

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.85
TOTAL AREA (ACRES) = 3566.8 PEAK FLOW RATE (CFS) = 212.85
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 3.33 FLOW VELOCITY (FEET/SEC.) = 6.39
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13682.00 = 37051.30 FEET.

FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 28.24
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.611
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	6.90	0.60	1.000	-
USER-DEFINED	-	23.04	0.60	1.000	-
USER-DEFINED	-	1.18	0.60	1.000	-
USER-DEFINED	-	1.56	0.60	1.000	-
USER-DEFINED	-	53.20	0.60	1.000	-
USER-DEFINED	-	2.08	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 87.96 SUBAREA RUNOFF (CFS) = 0.88
EFFECTIVE AREA (ACRES) = 989.39 AREA-AVERAGED Fm (INCH/HR) = 0.52
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.87
TOTAL AREA (ACRES) = 3654.7 PEAK FLOW RATE (CFS) = 212.85
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 28.24
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.611
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.01	0.60	1.000	-
USER-DEFINED	-	0.18	0.60	1.000	-
USER-DEFINED	-	0.38	0.60	1.000	-
USER-DEFINED	-	0.22	0.60	1.000	-
USER-DEFINED	-	7.73	0.60	1.000	-
USER-DEFINED	-	4.37	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 12.89 SUBAREA RUNOFF (CFS) = 0.13
EFFECTIVE AREA (ACRES) = 1002.28 AREA-AVERAGED Fm (INCH/HR) = 0.52
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.87
TOTAL AREA (ACRES) = 3667.6 PEAK FLOW RATE (CFS) = 212.85
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 28.24
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.611
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	2.57	0.60	1.000	-
USER-DEFINED	-	1.97	0.60	1.000	-
USER-DEFINED	-	1.00	0.60	1.000	-
USER-DEFINED	-	2.98	0.60	1.000	-
USER-DEFINED	-	2.39	0.60	1.000	-
USER-DEFINED	-	1.67	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 12.58 SUBAREA RUNOFF (CFS) = 0.13
EFFECTIVE AREA (ACRES) = 1014.86 AREA-AVERAGED Fm (INCH/HR) = 0.52
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.87
TOTAL AREA (ACRES) = 3680.2 PEAK FLOW RATE (CFS) = 212.85
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 28.24
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.611
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.44	0.60	1.000	-
USER-DEFINED	-	2.65	0.60	0.850	-
USER-DEFINED	-	1.16	0.60	0.850	-
USER-DEFINED	-	0.47	0.60	0.500	-
USER-DEFINED	-	0.25	0.60	0.500	-
USER-DEFINED	-	20.24	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.963
SUBAREA AREA (ACRES) = 25.21 SUBAREA RUNOFF (CFS) = 0.76
EFFECTIVE AREA (ACRES) = 1040.07 AREA-AVERAGED Fm (INCH/HR) = 0.52
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.87
TOTAL AREA (ACRES) = 3705.4 PEAK FLOW RATE (CFS) = 212.85
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 28.24
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.611
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.08	0.60	1.000	-
USER-DEFINED	-	6.75	0.60	1.000	-

USER-DEFINED - 0.02 0.60 1.000 -
 USER-DEFINED - 0.93 0.60 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 14.78 SUBAREA RUNOFF (CFS) = 0.15
 EFFECTIVE AREA (ACRES) = 1054.85 AREA-AVERAGED Fm (INCH/HR) = 0.52
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.88
 TOTAL AREA (ACRES) = 3720.2 PEAK FLOW RATE (CFS) = 212.85
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13682.00 TO NODE 13683.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 242.00 DOWNSTREAM(FEET) = 208.53
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2526.22 CHANNEL SLOPE = 0.0132
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00

* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.542

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.49	0.60	1.000	-
USER-DEFINED	-	13.31	0.60	1.000	-
USER-DEFINED	-	0.87	0.60	1.000	-
USER-DEFINED	-	20.26	0.60	1.000	-
USER-DEFINED	-	1.21	0.60	1.000	-
USER-DEFINED	-	0.05	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 212.85

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.95

AVERAGE FLOW DEPTH (FEET) = 3.45 TRAVEL TIME (MIN.) = 7.08

Tc (MIN.) = 35.32

SUBAREA AREA (ACRES) = 44.19 SUBAREA RUNOFF (CFS) = 0.00

EFFECTIVE AREA (ACRES) = 1099.04 AREA-AVERAGED Fm (INCH/HR) = 0.53

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.88

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA (ACRES) = 3764.4 PEAK FLOW RATE (CFS) = 212.85

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 3.45 FLOW VELOCITY (FEET/SEC.) = 5.95

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13683.00 = 39577.52 FEET.

 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 35.32

* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.542

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	12.56	0.60	1.000	-
USER-DEFINED	-	0.81	0.60	1.000	-
USER-DEFINED	-	0.01	0.60	1.000	-
USER-DEFINED	-	1.11	0.60	1.000	-
USER-DEFINED	-	0.59	0.60	1.000	-
USER-DEFINED	-	3.04	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA (ACRES) = 18.12 SUBAREA RUNOFF (CFS) = 0.00

EFFECTIVE AREA (ACRES) = 1117.16 AREA-AVERAGED Fm (INCH/HR) = 0.53

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.88

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA (ACRES) = 3782.5 PEAK FLOW RATE (CFS) = 212.85

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 35.32

* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.542

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.10	0.60	0.400	-
USER-DEFINED	-	1.30	0.60	0.850	-
USER-DEFINED	-	0.10	0.60	0.400	-
USER-DEFINED	-	1.70	0.60	0.850	-
USER-DEFINED	-	0.10	0.60	0.850	-
USER-DEFINED	-	2.90	0.60	0.850	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.835

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA (ACRES) = 6.20 SUBAREA RUNOFF (CFS) = 0.50

EFFECTIVE AREA (ACRES) = 1123.36 AREA-AVERAGED Fm (INCH/HR) = 0.53

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.88

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA (ACRES) = 3788.7 PEAK FLOW RATE (CFS) = 212.85

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 35.32

* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.542

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

```

USER-DEFINED      -      0.10      0.60      0.500      -
USER-DEFINED      -      0.10      0.60      0.350      -
USER-DEFINED      -      6.90      0.60      0.850      -
USER-DEFINED      -      0.40      0.60      0.850      -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.839
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 7.50      SUBAREA RUNOFF(CFS) = 0.59
EFFECTIVE AREA(ACRES) = 1130.86      AREA-AVERAGED Fm(INCH/HR) = 0.53
AREA-AVERAGED Fp(INCH/HR) = 0.60      AREA-AVERAGED Ap = 0.88
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 3796.2      PEAK FLOW RATE(CFS) = 212.85
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13682.00 TO NODE 13683.00 IS CODE = 12
-----

```

```

>>>>CLEAR MEMORY BANK # 3 <<<<<
=====

```

```

***MEMORY BANK # 3 IS EMPTY - PROCESS IGNORED.***

```

```

*****
FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====

```

```

MAINLINE Tc(MIN.) = 35.32
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.542
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL      AREA      Fp      Ap      SCS
LAND USE      GROUP      (ACRES)      (INCH/HR)      (DECIMAL)      CN
USER-DEFINED      -      2.55      0.60      1.000      -
USER-DEFINED      -      0.01      0.60      1.000      -
USER-DEFINED      -      1.35      0.60      1.000      -
USER-DEFINED      -      0.44      0.60      1.000      -
USER-DEFINED      -      0.67      0.60      1.000      -
USER-DEFINED      -      1.06      0.60      1.000      -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 6.08      SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 1136.94      AREA-AVERAGED Fm(INCH/HR) = 0.53
AREA-AVERAGED Fp(INCH/HR) = 0.60      AREA-AVERAGED Ap = 0.88
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 3802.3      PEAK FLOW RATE(CFS) = 212.85
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====

```

```

MAINLINE Tc(MIN.) = 35.32
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.542

```

```

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL      AREA      Fp      Ap      SCS
LAND USE      GROUP      (ACRES)      (INCH/HR)      (DECIMAL)      CN
USER-DEFINED      -      2.16      0.60      1.000      -
USER-DEFINED      -      2.45      0.60      1.000      -
USER-DEFINED      -      6.15      0.60      1.000      -
USER-DEFINED      -      1.34      0.60      1.000      -
USER-DEFINED      -      18.46      0.60      1.000      -
USER-DEFINED      -      4.13      0.60      1.000      -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 34.69      SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 1171.63      AREA-AVERAGED Fm(INCH/HR) = 0.53
AREA-AVERAGED Fp(INCH/HR) = 0.60      AREA-AVERAGED Ap = 0.89
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 3837.0      PEAK FLOW RATE(CFS) = 212.85
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====

```

```

MAINLINE Tc(MIN.) = 35.32
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.542
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL      AREA      Fp      Ap      SCS
LAND USE      GROUP      (ACRES)      (INCH/HR)      (DECIMAL)      CN
USER-DEFINED      -      8.69      0.60      1.000      -
USER-DEFINED      -      0.73      0.60      1.000      -
USER-DEFINED      -      0.41      0.60      1.000      -
USER-DEFINED      -      1.37      0.60      1.000      -
USER-DEFINED      -      3.11      0.60      1.000      -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 14.31      SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 1185.94      AREA-AVERAGED Fm(INCH/HR) = 0.53
AREA-AVERAGED Fp(INCH/HR) = 0.60      AREA-AVERAGED Ap = 0.89
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 3851.3      PEAK FLOW RATE(CFS) = 212.85
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13683.00 TO NODE 13685.00 IS CODE = 51
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<
=====

```

```

ELEVATION DATA: UPSTREAM(FEET) = 208.53      DOWNSTREAM(FEET) = 194.24
CHANNEL LENGTH THRU SUBAREA( FEET) = 289.01      CHANNEL SLOPE = 0.0494
CHANNEL BASE( FEET) = 0.00      "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040      MAXIMUM DEPTH( FEET) = 20.00

```


CHANNEL FLOW THRU SUBAREA(CFS) = 212.85
 FLOW VELOCITY(FEET/SEC.) = 9.75 FLOW DEPTH(FEET) = 2.70
 TRAVEL TIME(MIN.) = 0.49 Tc(MIN.) = 35.81
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13685.00 = 39866.53 FEET.

 FLOW PROCESS FROM NODE 13685.00 TO NODE 13410.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 194.24 DOWNSTREAM(FEET) = 178.72
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1843.57 CHANNEL SLOPE = 0.0084
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.493

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.23	0.60	1.000	-
USER-DEFINED	-	1.52	0.60	1.000	-
USER-DEFINED	-	0.06	0.60	1.000	-
USER-DEFINED	-	0.13	0.60	1.000	-
USER-DEFINED	-	6.45	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 212.85
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.01
 AVERAGE FLOW DEPTH(FEET) = 3.76 TRAVEL TIME(MIN.) = 6.14
 Tc(MIN.) = 41.95
 SUBAREA AREA(ACRES) = 8.39 SUBAREA RUNOFF(CFS) = 0.00
 EFFECTIVE AREA(ACRES) = 1194.33 AREA-AVERAGED Fm(INCH/HR) = 0.53
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.89
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA(ACRES) = 3859.7 PEAK FLOW RATE(CFS) = 212.85
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 3.76 FLOW VELOCITY(FEET/SEC.) = 5.01
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13410.00 = 41710.10 FEET.

=====

END OF STUDY SUMMARY:
 TOTAL AREA(ACRES) = 3859.7 TC(MIN.) = 41.95
 EFFECTIVE AREA(ACRES) = 1194.33 AREA-AVERAGED Fm(INCH/HR) = 0.53
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.888
 PEAK FLOW RATE(CFS) = 212.85

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	212.85	41.95	0.493	0.60(0.53)	0.89	1194.3	110.00
2	182.13	45.87	0.471	0.60(0.53)	0.88	1308.8	100.00
3	166.70	48.25	0.457	0.60(0.53)	0.88	1371.9	100.00
4	138.00	55.27	0.417	0.60(0.54)	0.89	1542.5	130.00
5	114.28	88.34	0.339	0.60(0.56)	0.93	2427.8	20100.00

6	99.46	100.42	0.317	0.60(0.56)	0.93	2568.9	13600.00
7	61.98	214.44	0.215	0.60(0.56)	0.93	3822.6	13510.00
8	61.68	223.75	0.212	0.60(0.56)	0.93	3859.7	13500.00

=====

END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2010 Advanced Engineering Software (aes)
Ver. 17.0 Release Date: 07/01/2010 License ID 1527

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 137 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 2-YR EV AUG 2023 ROKAMOTO *

FILE NAME: RU02EV37.DAT
TIME/DATE OF STUDY: 23:52 08/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 2.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 1.802
- 2) 10.00; 1.202
- 3) 15.00; 0.923
- 4) 20.00; 0.761
- 5) 25.00; 0.659
- 6) 30.00; 0.585
- 7) 40.00; 0.503
- 8) 50.00; 0.446
- 9) 60.00; 0.390
- 10) 90.00; 0.336
- 11) 120.00; 0.280
- 12) 180.00; 0.226
- 13) 360.00; 0.170
- 14) 1200.00; 0.080

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU02EV34.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2907.89	16.83	0.60 (0.45)	0.75	2683.2	300.00
2	2848.33	33.17	0.60 (0.46)	0.76	5475.6	50600.00
3	2452.65	52.20	0.60 (0.46)	0.77	9553.4	100.00
4	1502.62	82.41	0.60 (0.49)	0.82	14988.3	10100.00
5	1446.94	100.96	0.60 (0.50)	0.84	18899.4	13600.00
6	1452.61	117.04	0.60 (0.51)	0.85	22265.6	13210.00
7	1447.58	131.57	0.60 (0.52)	0.87	24925.2	11831.00
8	1491.42	155.04	0.60 (0.53)	0.88	29473.6	11530.00
9	1527.22	174.53	0.60 (0.54)	0.90	33834.6	11000.00
10	1590.36	196.78	0.60 (0.55)	0.91	40875.2	10850.00
11	1478.31	214.98	0.60 (0.55)	0.92	44677.0	13510.00
12	1240.49	265.25	0.60 (0.56)	0.93	52858.8	12410.00
13	1176.24	298.44	0.60 (0.56)	0.94	58944.7	12261.00
14	1153.88	311.30	0.60 (0.56)	0.94	60431.3	10410.00
15	1132.05	323.59	0.60 (0.56)	0.94	61533.2	12101.10
16	1082.77	351.26	0.60 (0.56)	0.94	63911.3	10200.00
17	1058.54	364.77	0.60 (0.57)	0.94	64849.6	12010.00
18	1004.96	394.15	0.60 (0.57)	0.94	65523.3	10210.00
19	932.61	443.75	0.60 (0.57)	0.94	66022.3	12000.00
20	875.46	513.65	0.60 (0.57)	0.94	66607.1	10100.00
TOTAL AREA (ACRES) =						66607.1

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 14.0

>>>>MEMORY BANK # 3 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2907.89	16.83	0.60 (0.45)	0.75	2683.2	300.00
2	2848.33	33.17	0.60 (0.46)	0.76	5475.6	50600.00
3	2452.65	52.20	0.60 (0.46)	0.77	9553.4	100.00
4	1502.62	82.41	0.60 (0.49)	0.82	14988.3	10100.00
5	1446.94	100.96	0.60 (0.50)	0.84	18899.4	13600.00
6	1452.61	117.04	0.60 (0.51)	0.85	22265.6	13210.00
7	1447.58	131.57	0.60 (0.52)	0.87	24925.2	11831.00
8	1491.42	155.04	0.60 (0.53)	0.88	29473.6	11530.00
9	1527.22	174.53	0.60 (0.54)	0.90	33834.6	11000.00
10	1590.36	196.78	0.60 (0.55)	0.91	40875.2	10850.00
11	1478.31	214.98	0.60 (0.55)	0.92	44677.0	13510.00
12	1240.49	265.25	0.60 (0.56)	0.93	52858.8	12410.00
13	1176.24	298.44	0.60 (0.56)	0.94	58944.7	12261.00

```

14 1153.88 311.30 0.60( 0.56) 0.94 60431.3 10410.00
15 1132.05 323.59 0.60( 0.56) 0.94 61533.2 12101.10
16 1082.77 351.26 0.60( 0.56) 0.94 63911.3 10200.00
17 1058.54 364.77 0.60( 0.57) 0.94 64849.6 12010.00
18 1004.96 394.15 0.60( 0.57) 0.94 65523.3 10210.00
19 932.61 443.75 0.60( 0.57) 0.94 66022.3 12000.00
20 875.46 513.65 0.60( 0.57) 0.94 66607.1 10100.00
TOTAL AREA(ACRES) = 66607.1

```

FLOW PROCESS FROM NODE 13700.00 TO NODE 13720.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 170.00 DOWNSTREAM(FEET) = 165.51
CHANNEL LENGTH THRU SUBAREA(FEET) = 1891.83 CHANNEL SLOPE = 0.0024
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
CHANNEL FLOW THRU SUBAREA(CFS) = 2907.89
FLOW VELOCITY(FEET/SEC.) = 7.44 FLOW DEPTH(FEET) = 11.42
TRAVEL TIME(MIN.) = 4.24 Tc(MIN.) = 21.07
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126420.58 FEET.

FLOW PROCESS FROM NODE 13700.00 TO NODE 13720.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

FLOW PROCESS FROM NODE 13720.00 TO NODE 13720.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 0506102g.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	23.78	20.85	0.60(0.58)	0.96	198.9	10230.00
2	18.42	27.77	0.60(0.57)	0.96	227.7	10250.00
3	15.17	31.87	0.60(0.57)	0.95	240.4	10200.00
4	8.86	39.09	0.60(0.57)	0.95	246.3	10220.00
TOTAL AREA(ACRES) =						246.3

FLOW PROCESS FROM NODE 13720.00 TO NODE 13720.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

=====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	2907.89	21.07	0.739	0.60(0.45)	0.75	2683.2	300.00
2	2848.33	37.42	0.524	0.60(0.46)	0.76	5475.6	50600.00
3	2452.65	56.62	0.409	0.60(0.46)	0.77	9553.4	100.00
4	1502.62	87.40	0.341	0.60(0.49)	0.82	14988.3	10100.00

```

5 1446.94 106.01 0.306 0.60( 0.50) 0.84 18899.4 13600.00
6 1452.61 122.08 0.278 0.60( 0.51) 0.85 22265.6 13210.00
7 1447.58 136.61 0.265 0.60( 0.52) 0.87 24925.2 11831.00
8 1491.42 160.05 0.244 0.60( 0.53) 0.88 29473.6 11530.00
9 1527.22 179.51 0.226 0.60( 0.54) 0.90 33834.6 11000.00
10 1590.36 201.71 0.219 0.60( 0.55) 0.91 40875.2 10850.00
11 1478.31 219.99 0.214 0.60( 0.55) 0.92 44677.0 13510.00
12 1240.49 270.49 0.198 0.60( 0.56) 0.93 52858.8 12410.00
13 1176.24 303.76 0.187 0.60( 0.56) 0.94 58944.7 12261.00
14 1153.88 316.64 0.183 0.60( 0.56) 0.94 60431.3 10410.00
15 1132.05 328.95 0.180 0.60( 0.56) 0.94 61533.2 12101.10
16 1082.77 356.68 0.171 0.60( 0.56) 0.94 63911.3 10200.00
17 1058.54 370.23 0.169 0.60( 0.57) 0.94 64849.6 12010.00
18 1004.96 399.68 0.166 0.60( 0.57) 0.94 65523.3 10210.00
19 932.61 449.38 0.160 0.60( 0.57) 0.94 66022.3 12000.00
20 875.46 519.37 0.153 0.60( 0.57) 0.94 66607.1 10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126420.58 FEET.

```

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	23.78	20.85	0.744	0.60(0.58)	0.96	198.9	10230.00
2	18.42	27.77	0.618	0.60(0.57)	0.96	227.7	10250.00
3	15.17	31.87	0.570	0.60(0.57)	0.95	240.4	10200.00
4	8.86	39.09	0.510	0.60(0.57)	0.95	246.3	10220.00
LONGEST FLOWPATH FROM NODE							10200.00 TO NODE 13720.00 = 9099.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	2931.68	20.85	0.744	0.60(0.46)	0.77	2853.8	10230.00
2	2931.51	21.07	0.739	0.60(0.46)	0.77	2883.1	300.00
3	2901.92	27.77	0.618	0.60(0.46)	0.77	4055.0	10250.00
4	2883.73	31.87	0.570	0.60(0.46)	0.77	4767.9	10200.00
5	2858.65	37.42	0.524	0.60(0.46)	0.77	5720.5	50600.00
6	2822.84	39.09	0.510	0.60(0.46)	0.77	6075.9	10220.00
7	2459.74	56.62	0.409	0.60(0.47)	0.78	9799.6	100.00
8	1508.53	87.40	0.341	0.60(0.49)	0.82	15234.5	10100.00
9	1452.25	106.01	0.306	0.60(0.50)	0.84	19145.6	13600.00
10	1457.44	122.08	0.278	0.60(0.51)	0.85	22511.8	13210.00
11	1452.18	136.61	0.265	0.60(0.52)	0.87	25171.5	11831.00
12	1495.65	160.05	0.244	0.60(0.53)	0.88	29719.9	11530.00
13	1531.15	179.51	0.226	0.60(0.54)	0.90	34080.9	11000.00
14	1594.16	201.71	0.219	0.60(0.55)	0.91	41123.5	10850.00
15	1482.01	219.99	0.214	0.60(0.55)	0.92	44923.2	13510.00
16	1243.92	270.49	0.198	0.60(0.56)	0.93	53105.0	12410.00
17	1179.49	303.76	0.187	0.60(0.56)	0.94	59190.9	12261.00
18	1157.06	316.64	0.183	0.60(0.56)	0.94	60677.6	10410.00
19	1135.16	328.95	0.180	0.60(0.56)	0.94	61779.5	12101.10
20	1085.74	356.68	0.171	0.60(0.56)	0.94	64157.6	10200.00
21	1061.47	370.23	0.169	0.60(0.57)	0.94	65095.8	12010.00
22	1007.84	399.68	0.166	0.60(0.57)	0.94	65769.5	10210.00
23	935.39	449.38	0.160	0.60(0.57)	0.94	66268.6	12000.00
24	878.12	519.37	0.153	0.60(0.57)	0.94	66853.4	10100.00
TOTAL AREA(ACRES) =							66853.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 2931.68 Tc(MIN.) = 20.846

EFFECTIVE AREA (ACRES) = 2853.83 AREA-AVERAGED Fm (INCH/HR) = 0.46
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.94
 TOTAL AREA (ACRES) = 66853.4
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126420.58 FEET.

FLOW PROCESS FROM NODE 13720.00 TO NODE 13740.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM (FEET) = 165.51 DOWNSTREAM (FEET) = 161.03
 CHANNEL LENGTH THRU SUBAREA (FEET) = 2067.54 CHANNEL SLOPE = 0.0022
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00
 CHANNEL FLOW THRU SUBAREA (CFS) = 2931.68
 FLOW VELOCITY (FEET/SEC.) = 7.20 FLOW DEPTH (FEET) = 11.65
 TRAVEL TIME (MIN.) = 4.78 Tc (MIN.) = 25.63
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128488.12 FEET.

FLOW PROCESS FROM NODE 13720.00 TO NODE 13740.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3<<<<

FLOW PROCESS FROM NODE 13740.00 TO NODE 13740.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506103g.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	100.02	24.05	0.60 (0.45)	0.75	396.7	10380.00
2	99.68	24.58	0.60 (0.45)	0.75	403.1	10300.00
3	86.78	29.19	0.60 (0.45)	0.76	440.4	10320.00
4	81.58	32.88	0.60 (0.46)	0.76	455.7	10340.00
5	76.28	36.17	0.60 (0.46)	0.76	460.8	10360.00
TOTAL AREA (ACRES) =						460.8

FLOW PROCESS FROM NODE 13740.00 TO NODE 13740.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2931.68	25.63	0.650	0.60 (0.46)	0.77	2853.8	10230.00
2	2931.51	25.85	0.646	0.60 (0.46)	0.77	2883.1	300.00
3	2901.92	32.56	0.564	0.60 (0.46)	0.77	4055.0	10250.00
4	2883.73	36.68	0.530	0.60 (0.46)	0.77	4767.9	10200.00
5	2858.65	42.24	0.490	0.60 (0.46)	0.77	5720.5	50600.00
6	2822.84	43.92	0.481	0.60 (0.46)	0.77	6075.9	10220.00
7	2459.74	61.62	0.387	0.60 (0.47)	0.78	9799.6	100.00

8	1508.53	93.05	0.330	0.60 (0.49)	0.82	15234.5	10100.00
9	1452.25	111.71	0.295	0.60 (0.50)	0.84	19145.6	13600.00
10	1457.44	127.78	0.273	0.60 (0.51)	0.85	22511.8	13210.00
11	1452.18	142.31	0.260	0.60 (0.52)	0.87	25171.5	11831.00
12	1495.65	165.71	0.239	0.60 (0.53)	0.88	29719.9	11530.00
13	1531.15	185.14	0.224	0.60 (0.54)	0.90	34080.9	11000.00
14	1594.16	207.28	0.218	0.60 (0.55)	0.91	41121.5	10850.00
15	1482.01	225.66	0.212	0.60 (0.55)	0.92	44923.2	13510.00
16	1243.92	276.41	0.196	0.60 (0.56)	0.93	53105.0	12410.00
17	1179.49	309.76	0.186	0.60 (0.56)	0.94	59190.9	12261.00
18	1157.06	322.67	0.182	0.60 (0.56)	0.94	60677.6	10410.00
19	1135.16	335.02	0.178	0.60 (0.56)	0.94	61779.5	12101.10
20	1085.74	362.81	0.170	0.60 (0.56)	0.94	64157.6	10200.00
21	1061.47	376.39	0.168	0.60 (0.57)	0.94	65095.8	12010.00
22	1007.84	405.92	0.165	0.60 (0.57)	0.94	65769.5	10210.00
23	935.39	455.75	0.160	0.60 (0.57)	0.94	66268.6	12000.00
24	878.12	525.83	0.152	0.60 (0.57)	0.94	66853.4	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128488.12 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	100.02	24.05	0.678	0.60 (0.45)	0.75	396.7	10380.00
2	99.68	24.58	0.668	0.60 (0.45)	0.75	403.1	10300.00
3	86.78	29.19	0.597	0.60 (0.45)	0.76	440.4	10320.00
4	81.58	32.88	0.561	0.60 (0.46)	0.76	455.7	10340.00
5	76.28	36.17	0.534	0.60 (0.46)	0.76	460.8	10360.00

LONGEST FLOWPATH FROM NODE 10320.00 TO NODE 13740.00 = 8457.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3031.70	24.05	0.678	0.60 (0.46)	0.77	3074.4	10380.00
2	3031.36	24.58	0.668	0.60 (0.46)	0.77	3139.9	10300.00
3	3028.42	25.63	0.650	0.60 (0.46)	0.77	3265.4	10230.00
4	3027.63	25.85	0.646	0.60 (0.46)	0.77	3296.5	300.00
5	3003.55	29.19	0.597	0.60 (0.46)	0.77	3907.2	10320.00
6	2983.94	32.56	0.564	0.60 (0.46)	0.77	4509.3	10250.00
7	2982.08	32.88	0.561	0.60 (0.46)	0.77	4565.9	10340.00
8	2962.22	36.17	0.534	0.60 (0.46)	0.77	5141.9	10360.00
9	2959.42	36.68	0.530	0.60 (0.46)	0.77	5228.7	10200.00
10	2928.63	42.24	0.490	0.60 (0.46)	0.77	6181.3	50600.00
11	2891.45	43.92	0.481	0.60 (0.46)	0.77	6536.7	10220.00
12	2515.00	61.62	0.387	0.60 (0.47)	0.78	10260.4	100.00
13	1555.68	93.05	0.330	0.60 (0.49)	0.82	15695.3	10100.00
14	1494.43	111.71	0.295	0.60 (0.50)	0.84	19606.4	13600.00
15	1496.40	127.78	0.273	0.60 (0.51)	0.85	22972.6	13210.00
16	1489.28	142.31	0.260	0.60 (0.52)	0.87	25632.3	11831.00
17	1529.75	165.71	0.239	0.60 (0.53)	0.88	30180.7	11530.00
18	1563.18	185.14	0.224	0.60 (0.54)	0.90	34541.7	11000.00
19	1625.21	207.28	0.218	0.60 (0.55)	0.91	41582.3	10850.00
20	1512.25	225.66	0.212	0.60 (0.55)	0.92	45384.0	13510.00
21	1271.90	276.41	0.196	0.60 (0.56)	0.93	53565.8	12410.00
22	1205.99	309.76	0.186	0.60 (0.56)	0.94	59651.8	12261.00
23	1182.98	322.67	0.182	0.60 (0.56)	0.94	61138.4	10410.00
24	1160.54	335.02	0.178	0.60 (0.56)	0.94	62240.3	12101.10
25	1109.97	362.81	0.170	0.60 (0.56)	0.94	64618.4	10200.00
26	1085.49	376.39	0.168	0.60 (0.56)	0.94	65556.6	12010.00

27 1031.40 405.92 0.165 0.60(0.56) 0.94 66230.3 10210.00
 28 958.20 455.75 0.160 0.60(0.57) 0.94 66729.4 12000.00
 29 899.85 525.83 0.152 0.60(0.57) 0.94 67314.2 10100.00
 TOTAL AREA(ACRES) = 67314.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 3031.70 Tc(MIN.) = 24.048
 EFFECTIVE AREA(ACRES) = 3074.45 AREA-AVERAGED Fm(INCH/HR) = 0.46
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.94
 TOTAL AREA(ACRES) = 67314.2
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128488.12 FEET.

 FLOW PROCESS FROM NODE 13740.00 TO NODE 13741.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 161.03 DOWNSTREAM(FEET) = 141.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 364.08 CHANNEL SLOPE = 0.0550
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
 CHANNEL FLOW THRU SUBAREA(CFS) = 3031.70
 FLOW VELOCITY(FEET/SEC.) = 24.45 FLOW DEPTH(FEET) = 6.43
 TRAVEL TIME(MIN.) = 0.25 Tc(MIN.) = 24.30
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128852.20 FEET.

 FLOW PROCESS FROM NODE 13740.00 TO NODE 13741.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<

 FLOW PROCESS FROM NODE 13741.00 TO NODE 13741.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<

PEAK FLOWRATE TABLE FILE NAME: 0506104g.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	7.30	27.55	0.621	0.60(0.48)	0.80	44.3	10400.00
TOTAL AREA(ACRES) =							44.3

 FLOW PROCESS FROM NODE 13741.00 TO NODE 13741.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3031.70	24.30	0.673	0.60(0.46)	0.77	3074.4	10380.00
2	3031.36	24.83	0.663	0.60(0.46)	0.77	3139.9	10300.00
3	3028.42	25.88	0.646	0.60(0.46)	0.77	3265.4	10230.00
4	3027.63	26.10	0.643	0.60(0.46)	0.77	3296.5	300.00

5	3003.55	29.44	0.593	0.60(0.46)	0.77	3907.2	10320.00
6	2983.94	32.81	0.562	0.60(0.46)	0.77	4509.3	10250.00
7	2982.08	33.13	0.559	0.60(0.46)	0.77	4565.9	10340.00
8	2962.22	36.42	0.532	0.60(0.46)	0.77	5141.9	10360.00
9	2959.42	36.93	0.528	0.60(0.46)	0.77	5228.7	10200.00
10	2928.63	42.49	0.489	0.60(0.46)	0.77	6181.3	50600.00
11	2891.45	44.17	0.479	0.60(0.46)	0.77	6536.7	10220.00
12	2515.00	61.88	0.387	0.60(0.47)	0.78	10260.4	100.00
13	1555.68	93.34	0.330	0.60(0.49)	0.82	15695.3	10100.00
14	1494.43	112.01	0.295	0.60(0.50)	0.84	19606.4	13600.00
15	1496.40	128.08	0.273	0.60(0.51)	0.85	22972.6	13210.00
16	1489.28	142.61	0.260	0.60(0.52)	0.87	25632.3	11831.00
17	1529.75	166.01	0.239	0.60(0.53)	0.88	30180.7	11530.00
18	1563.18	185.43	0.224	0.60(0.54)	0.90	34541.7	11000.00
19	1625.21	207.57	0.217	0.60(0.55)	0.91	41582.3	10850.00
20	1512.25	225.96	0.212	0.60(0.55)	0.92	45384.0	13510.00
21	1271.90	276.72	0.196	0.60(0.56)	0.93	53565.8	12410.00
22	1205.99	310.07	0.186	0.60(0.56)	0.94	59651.8	12261.00
23	1182.98	322.99	0.182	0.60(0.56)	0.94	61138.4	10410.00
24	1160.54	335.33	0.178	0.60(0.56)	0.94	62240.3	12101.10
25	1109.97	363.13	0.170	0.60(0.56)	0.94	64618.4	10200.00
26	1085.49	376.72	0.168	0.60(0.56)	0.94	65556.6	12010.00
27	1031.40	406.25	0.165	0.60(0.56)	0.94	66230.3	10210.00
28	958.20	456.08	0.160	0.60(0.57)	0.94	66729.4	12000.00
29	899.85	526.17	0.152	0.60(0.57)	0.94	67314.2	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128852.20 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	7.30	27.55	0.621	0.60(0.48)	0.80	44.3	10400.00

LONGEST FLOWPATH FROM NODE 10400.00 TO NODE 13741.00 = 6237.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3039.00	24.30	0.673	0.60(0.46)	0.77	3113.5	10380.00
2	3038.66	24.83	0.663	0.60(0.46)	0.77	3179.8	10300.00
3	3035.72	25.88	0.646	0.60(0.46)	0.77	3307.1	10230.00
4	3034.93	26.10	0.643	0.60(0.46)	0.77	3338.5	300.00
5	3024.49	27.55	0.621	0.60(0.46)	0.77	3605.7	10400.00
6	3009.69	29.44	0.593	0.60(0.46)	0.77	3951.5	10320.00
7	2989.75	32.81	0.562	0.60(0.46)	0.77	4553.6	10250.00
8	2987.87	33.13	0.559	0.60(0.46)	0.77	4610.2	10340.00
9	2967.72	36.42	0.532	0.60(0.46)	0.77	5186.2	10360.00
10	2964.88	36.93	0.528	0.60(0.46)	0.77	5273.0	10200.00
11	2933.68	42.49	0.489	0.60(0.46)	0.77	6225.6	50600.00
12	2896.40	44.17	0.479	0.60(0.46)	0.77	6581.0	10220.00
13	2518.99	61.88	0.387	0.60(0.47)	0.78	10304.7	100.00
14	1559.09	93.34	0.330	0.60(0.49)	0.82	15739.6	10100.00
15	1497.48	112.01	0.295	0.60(0.50)	0.84	19650.7	13600.00
16	1499.22	128.08	0.273	0.60(0.51)	0.85	23016.9	13210.00
17	1491.97	142.61	0.260	0.60(0.52)	0.87	25676.6	11831.00
18	1532.21	166.01	0.239	0.60(0.53)	0.88	30225.0	11530.00
19	1565.50	185.43	0.224	0.60(0.54)	0.90	34586.0	11000.00
20	1627.46	207.57	0.217	0.60(0.55)	0.91	41626.6	10850.00
21	1514.43	225.96	0.212	0.60(0.55)	0.92	45428.3	13510.00
22	1273.93	276.72	0.196	0.60(0.56)	0.93	53610.1	12410.00

23	1207.91	310.07	0.186	0.60 (0.56)	0.94	59696.1	12261.00
24	1184.86	322.99	0.182	0.60 (0.56)	0.94	61182.7	10410.00
25	1162.38	335.33	0.178	0.60 (0.56)	0.94	62284.6	12101.10
26	1111.72	363.13	0.170	0.60 (0.56)	0.94	64662.7	10200.00
27	1087.22	376.72	0.168	0.60 (0.56)	0.94	65600.9	12010.00
28	1033.11	406.25	0.165	0.60 (0.56)	0.94	66274.6	10210.00
29	959.85	456.08	0.160	0.60 (0.56)	0.94	66773.7	12000.00
30	901.42	526.17	0.152	0.60 (0.57)	0.94	67358.5	10100.00

TOTAL AREA (ACRES) = 67358.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 3039.00 Tc (MIN.) = 24.296
EFFECTIVE AREA (ACRES) = 3113.52 AREA-AVERAGED Fm (INCH/HR) = 0.46
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.77
TOTAL AREA (ACRES) = 67358.5
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128852.20 FEET.

FLOW PROCESS FROM NODE 13741.00 TO NODE 13802.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 141.00 DOWNSTREAM (FEET) = 135.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 1533.41 CHANNEL SLOPE = 0.0039
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00
CHANNEL FLOW THRU SUBAREA (CFS) = 3039.00
FLOW VELOCITY (FEET/SEC.) = 9.08 FLOW DEPTH (FEET) = 10.56
TRAVEL TIME (MIN.) = 2.82 Tc (MIN.) = 27.11
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130385.60 FEET.

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<

PEAK FLOWRATE TABLE FILE NAME: 0506105n.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	32.00	17.46	0.60 (0.53)	0.88	140.9	10520.00
2	10.21	60.70	0.60 (0.56)	0.93	403.6	10500.00
TOTAL AREA (ACRES) =						403.6

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3039.00	27.11	0.628	0.60 (0.46)	0.77	3113.5	10380.00
2	3038.66	27.64	0.620	0.60 (0.46)	0.77	3179.8	10300.00
3	3035.72	28.69	0.604	0.60 (0.46)	0.77	3307.1	10230.00
4	3034.93	28.92	0.601	0.60 (0.46)	0.77	3338.5	300.00
5	3024.49	30.37	0.582	0.60 (0.46)	0.77	3605.7	10400.00
6	3009.69	32.27	0.566	0.60 (0.46)	0.77	3951.5	10320.00
7	2989.75	35.64	0.539	0.60 (0.46)	0.77	4553.6	10250.00
8	2987.87	35.96	0.536	0.60 (0.46)	0.77	4610.2	10340.00
9	2967.72	39.26	0.509	0.60 (0.46)	0.77	5186.2	10360.00
10	2964.88	39.76	0.505	0.60 (0.46)	0.77	5273.0	10200.00
11	2933.68	45.33	0.473	0.60 (0.46)	0.77	6225.6	50600.00
12	2896.40	47.02	0.463	0.60 (0.46)	0.77	6581.0	10220.00
13	2518.99	64.83	0.381	0.60 (0.47)	0.78	10304.7	100.00
14	1559.09	96.67	0.324	0.60 (0.49)	0.82	15739.6	10100.00
15	1497.48	115.37	0.289	0.60 (0.50)	0.84	19650.7	13600.00
16	1499.22	131.44	0.270	0.60 (0.51)	0.85	23016.9	13210.00
17	1491.97	145.97	0.257	0.60 (0.52)	0.87	25676.6	11831.00
18	1532.21	169.35	0.236	0.60 (0.53)	0.88	30225.0	11530.00
19	1565.50	188.76	0.223	0.60 (0.54)	0.90	34586.0	11000.00
20	1627.46	210.86	0.216	0.60 (0.55)	0.91	41626.6	10850.00
21	1514.43	229.31	0.211	0.60 (0.55)	0.92	45428.3	13510.00
22	1273.93	280.22	0.195	0.60 (0.56)	0.93	53610.1	12410.00
23	1207.91	313.62	0.184	0.60 (0.56)	0.94	59696.1	12261.00
24	1184.86	326.55	0.180	0.60 (0.56)	0.94	61182.7	10410.00
25	1162.38	338.91	0.177	0.60 (0.56)	0.94	62284.6	12101.10
26	1111.72	366.75	0.169	0.60 (0.56)	0.94	64662.7	10200.00
27	1087.22	380.35	0.168	0.60 (0.56)	0.94	65600.9	12010.00
28	1033.11	409.94	0.165	0.60 (0.56)	0.94	66274.6	10210.00
29	959.85	459.83	0.159	0.60 (0.56)	0.94	66773.7	12000.00
30	901.42	529.98	0.152	0.60 (0.57)	0.94	67358.5	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130385.60 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	32.00	17.46	0.843	0.60 (0.53)	0.88	140.9	10520.00
2	10.21	60.70	0.389	0.60 (0.56)	0.93	403.6	10500.00

LONGEST FLOWPATH FROM NODE 10500.00 TO NODE 13802.00 = 12187.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3071.00	17.46	0.843	0.60 (0.46)	0.77	2146.6	10520.00
2	3066.14	27.11	0.628	0.60 (0.46)	0.77	3313.0	10380.00
3	3065.53	27.64	0.620	0.60 (0.46)	0.77	3382.5	10300.00
4	3062.07	28.69	0.604	0.60 (0.46)	0.77	3516.2	10230.00
5	3061.16	28.92	0.601	0.60 (0.46)	0.77	3548.9	300.00
6	3049.99	30.37	0.582	0.60 (0.46)	0.77	3825.0	10400.00
7	3034.23	32.27	0.566	0.60 (0.46)	0.77	4182.3	10320.00
8	3012.60	35.64	0.539	0.60 (0.46)	0.77	4804.9	10250.00
9	3010.55	35.96	0.536	0.60 (0.46)	0.77	4863.5	10340.00
10	2988.74	39.26	0.509	0.60 (0.46)	0.77	5459.5	10360.00
11	2985.65	39.76	0.505	0.60 (0.46)	0.77	5549.3	10200.00
12	2951.64	45.33	0.473	0.60 (0.46)	0.77	6535.8	50600.00
13	2913.51	47.02	0.463	0.60 (0.47)	0.78	6901.5	10220.00
14	2616.73	60.70	0.389	0.60 (0.47)	0.78	9844.8	10500.00

15	2529.01	64.83	0.381	0.60	(0.47)	0.78	10708.3	100.00
16	1567.59	96.67	0.324	0.60	(0.49)	0.82	16143.2	10100.00
17	1505.06	115.37	0.289	0.60	(0.50)	0.84	20054.3	13600.00
18	1506.31	131.44	0.270	0.60	(0.51)	0.85	23420.5	13210.00
19	1498.71	145.97	0.257	0.60	(0.52)	0.87	26080.2	11831.00
20	1538.40	169.35	0.236	0.60	(0.53)	0.88	30628.6	11530.00
21	1571.37	188.76	0.223	0.60	(0.54)	0.90	34989.6	11000.00
22	1633.14	210.86	0.216	0.60	(0.55)	0.91	42030.2	10850.00
23	1519.97	229.31	0.211	0.60	(0.55)	0.92	45831.9	13510.00
24	1279.05	280.22	0.195	0.60	(0.56)	0.93	54013.8	12410.00
25	1212.75	313.62	0.184	0.60	(0.56)	0.94	60099.7	12261.00
26	1189.60	326.55	0.180	0.60	(0.56)	0.94	61586.3	10410.00
27	1167.01	338.91	0.177	0.60	(0.56)	0.94	62688.2	12101.10
28	1116.17	366.75	0.169	0.60	(0.56)	0.94	65066.3	10200.00
29	1091.63	380.35	0.168	0.60	(0.56)	0.94	66004.5	12010.00
30	1037.43	409.94	0.165	0.60	(0.56)	0.94	66678.2	10210.00
31	964.03	459.83	0.159	0.60	(0.56)	0.94	67177.3	12000.00
32	905.41	529.98	0.152	0.60	(0.57)	0.94	67762.1	10100.00

TOTAL AREA(ACRES) = 67762.1

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 3071.00 Tc(MIN.) = 17.465
EFFECTIVE AREA(ACRES) = 2146.56 AREA-AVERAGED Fm(INCH/HR) = 0.46
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.94
TOTAL AREA(ACRES) = 67762.1
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130385.60 FEET.

FLOW PROCESS FROM NODE 13802.00 TO NODE 13803.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 135.00 DOWNSTREAM(FEET) = 134.99
CHANNEL LENGTH THRU SUBAREA(FEET) = 207.23 CHANNEL SLOPE = 0.0000
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00

==>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL
CAPACITY(NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM
ALLOWABLE DEPTH).
AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM
ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

CHANNEL FLOW THRU SUBAREA(CFS) = 3071.00
FLOW VELOCITY(FEET/SEC.) = 2.56 FLOW DEPTH(FEET) = 20.00
TRAVEL TIME(MIN.) = 1.35 Tc(MIN.) = 18.81
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130592.83 FEET.

FLOW PROCESS FROM NODE 13802.00 TO NODE 13803.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506106g.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	10.57	19.99	0.60(0.40)	0.67	36.9	10600.00
TOTAL AREA(ACRES) = 36.9						

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3071.00	18.81	0.799	0.60(0.46)	0.77	2146.6	10520.00
2	3066.14	28.46	0.608	0.60(0.46)	0.77	3313.0	10380.00
3	3065.53	28.99	0.600	0.60(0.46)	0.77	3382.5	10300.00
4	3062.07	30.05	0.585	0.60(0.46)	0.77	3516.2	10230.00
5	3061.16	30.27	0.583	0.60(0.46)	0.77	3548.9	300.00
6	3049.99	31.73	0.571	0.60(0.46)	0.77	3825.0	10400.00
7	3034.23	33.63	0.555	0.60(0.46)	0.77	4182.3	10320.00
8	3012.60	37.02	0.527	0.60(0.46)	0.77	4804.9	10250.00
9	3010.55	37.34	0.525	0.60(0.46)	0.77	4863.5	10340.00
10	2988.74	40.64	0.499	0.60(0.46)	0.77	5459.5	10360.00
11	2985.65	41.15	0.496	0.60(0.46)	0.77	5549.3	10200.00
12	2951.64	46.73	0.465	0.60(0.46)	0.77	6535.8	50600.00
13	2913.51	48.45	0.455	0.60(0.47)	0.78	6901.5	10220.00
14	2616.73	62.29	0.386	0.60(0.47)	0.78	9844.8	10500.00
15	2529.01	66.47	0.378	0.60(0.47)	0.78	10708.3	100.00
16	1567.59	99.01	0.319	0.60(0.49)	0.82	16143.2	10100.00
17	1505.06	117.73	0.284	0.60(0.50)	0.84	20054.3	13600.00
18	1506.31	133.80	0.268	0.60(0.51)	0.85	23420.5	13210.00
19	1498.71	148.33	0.254	0.60(0.52)	0.87	26080.2	11831.00
20	1538.40	171.70	0.233	0.60(0.53)	0.88	30628.6	11530.00
21	1571.37	191.09	0.223	0.60(0.54)	0.90	34989.6	11000.00
22	1633.14	213.17	0.216	0.60(0.55)	0.91	42030.2	10850.00
23	1519.97	231.66	0.210	0.60(0.55)	0.92	45831.9	13510.00
24	1279.05	282.68	0.194	0.60(0.56)	0.93	54013.8	12410.00
25	1212.75	316.11	0.184	0.60(0.56)	0.94	60099.7	12261.00
26	1189.60	329.05	0.180	0.60(0.56)	0.94	61586.3	10410.00
27	1167.01	341.42	0.176	0.60(0.56)	0.94	62688.2	12101.10
28	1116.17	369.29	0.169	0.60(0.56)	0.94	65066.3	10200.00
29	1091.63	382.91	0.168	0.60(0.56)	0.94	66004.5	12010.00
30	1037.43	412.53	0.164	0.60(0.56)	0.94	66678.2	10210.00
31	964.03	462.47	0.159	0.60(0.56)	0.94	67177.3	12000.00
32	905.41	532.66	0.152	0.60(0.57)	0.94	67762.1	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130592.83 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	10.57	19.99	0.761	0.60(0.40)	0.67	36.9	10600.00
LONGEST FLOWPATH FROM NODE 10600.00 TO NODE 13803.00 = 1713.00 FEET.							

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3081.57	18.81	0.799	0.60 (0.46)	0.77	2181.3	10520.00
2	3080.98	19.99	0.761	0.60 (0.46)	0.77	2326.0	10600.00
3	3072.20	28.46	0.608	0.60 (0.46)	0.77	3349.9	10380.00
4	3071.36	28.99	0.600	0.60 (0.46)	0.77	3419.4	10300.00
5	3067.74	30.05	0.585	0.60 (0.46)	0.77	3553.1	10230.00
6	3066.82	30.27	0.583	0.60 (0.46)	0.77	3585.8	300.00
7	3055.53	31.73	0.571	0.60 (0.46)	0.77	3861.9	10400.00
8	3039.62	33.63	0.555	0.60 (0.46)	0.77	4219.2	10320.00
9	3017.72	37.02	0.527	0.60 (0.46)	0.77	4841.8	10250.00
10	3015.64	37.34	0.525	0.60 (0.46)	0.77	4900.4	10340.00
11	2993.59	40.64	0.499	0.60 (0.46)	0.77	5496.4	10360.00
12	2990.47	41.15	0.496	0.60 (0.46)	0.77	5586.2	10200.00
13	2956.15	46.73	0.465	0.60 (0.46)	0.77	6572.7	50600.00
14	2917.92	48.45	0.455	0.60 (0.46)	0.77	6938.4	10220.00
15	2620.47	62.29	0.386	0.60 (0.47)	0.78	9881.7	10500.00
16	2532.68	66.47	0.378	0.60 (0.47)	0.78	10745.2	100.00
17	1570.69	99.01	0.319	0.60 (0.49)	0.82	16180.1	10100.00
18	1507.82	117.73	0.284	0.60 (0.50)	0.84	20091.2	13600.00
19	1508.91	133.80	0.268	0.60 (0.51)	0.85	23457.4	13210.00
20	1501.18	148.33	0.254	0.60 (0.52)	0.87	26117.1	11831.00
21	1540.67	171.70	0.233	0.60 (0.53)	0.88	30665.5	11530.00
22	1573.53	191.09	0.223	0.60 (0.54)	0.90	35026.5	11000.00
23	1635.24	213.17	0.216	0.60 (0.55)	0.91	42067.1	10850.00
24	1522.01	231.66	0.210	0.60 (0.55)	0.92	45868.8	13510.00
25	1280.93	282.68	0.194	0.60 (0.56)	0.93	54050.6	12410.00
26	1214.54	316.11	0.184	0.60 (0.56)	0.93	60136.6	12261.00
27	1191.34	329.05	0.180	0.60 (0.56)	0.94	61623.2	10410.00
28	1168.72	341.42	0.176	0.60 (0.56)	0.94	62725.1	12101.10
29	1117.81	369.29	0.169	0.60 (0.56)	0.94	65103.2	10200.00
30	1093.26	382.91	0.168	0.60 (0.56)	0.94	66041.4	12010.00
31	1039.03	412.53	0.164	0.60 (0.56)	0.94	66715.1	10210.00
32	965.58	462.47	0.159	0.60 (0.56)	0.94	67214.2	12000.00
33	906.88	532.66	0.152	0.60 (0.57)	0.94	67799.0	10100.00

TOTAL AREA (ACRES) = 67799.0

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 3081.57 Tc (MIN.) = 18.814
 EFFECTIVE AREA (ACRES) = 2181.29 AREA-AVERAGED Fm (INCH/HR) = 0.46
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.77
 TOTAL AREA (ACRES) = 67799.0
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130592.83 FEET.

=====
 END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 67799.0 TC (MIN.) = 18.81
 EFFECTIVE AREA (ACRES) = 2181.29 AREA-AVERAGED Fm (INCH/HR) = 0.46
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.772
 PEAK FLOW RATE (CFS) = 3081.57

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3081.57	18.81	0.799	0.60 (0.46)	0.77	2181.3	10520.00
2	3080.98	19.99	0.761	0.60 (0.46)	0.77	2326.0	10600.00
3	3072.20	28.46	0.608	0.60 (0.46)	0.77	3349.9	10380.00
4	3071.36	28.99	0.600	0.60 (0.46)	0.77	3419.4	10300.00

5	3067.74	30.05	0.585	0.60 (0.46)	0.77	3553.1	10230.00
6	3066.82	30.27	0.583	0.60 (0.46)	0.77	3585.8	300.00
7	3055.53	31.73	0.571	0.60 (0.46)	0.77	3861.9	10400.00
8	3039.62	33.63	0.555	0.60 (0.46)	0.77	4219.2	10320.00
9	3017.72	37.02	0.527	0.60 (0.46)	0.77	4841.8	10250.00
10	3015.64	37.34	0.525	0.60 (0.46)	0.77	4900.4	10340.00
11	2993.59	40.64	0.499	0.60 (0.46)	0.77	5496.4	10360.00
12	2990.47	41.15	0.496	0.60 (0.46)	0.77	5586.2	10200.00
13	2956.15	46.73	0.465	0.60 (0.46)	0.77	6572.7	50600.00
14	2917.92	48.45	0.455	0.60 (0.46)	0.77	6938.4	10220.00
15	2620.47	62.29	0.386	0.60 (0.47)	0.78	9881.7	10500.00
16	2532.68	66.47	0.378	0.60 (0.47)	0.78	10745.2	100.00
17	1570.69	99.01	0.319	0.60 (0.49)	0.82	16180.1	10100.00
18	1507.82	117.73	0.284	0.60 (0.50)	0.84	20091.2	13600.00
19	1508.91	133.80	0.268	0.60 (0.51)	0.85	23457.4	13210.00
20	1501.18	148.33	0.254	0.60 (0.52)	0.87	26117.1	11831.00
21	1540.67	171.70	0.233	0.60 (0.53)	0.88	30665.5	11530.00
22	1573.53	191.09	0.223	0.60 (0.54)	0.90	35026.5	11000.00
23	1635.24	213.17	0.216	0.60 (0.55)	0.91	42067.1	10850.00
24	1522.01	231.66	0.210	0.60 (0.55)	0.92	45868.8	13510.00
25	1280.93	282.68	0.194	0.60 (0.56)	0.93	54050.6	12410.00
26	1214.54	316.11	0.184	0.60 (0.56)	0.93	60136.6	12261.00
27	1191.34	329.05	0.180	0.60 (0.56)	0.94	61623.2	10410.00
28	1168.72	341.42	0.176	0.60 (0.56)	0.94	62725.1	12101.10
29	1117.81	369.29	0.169	0.60 (0.56)	0.94	65103.2	10200.00
30	1093.26	382.91	0.168	0.60 (0.56)	0.94	66041.4	12010.00
31	1039.03	412.53	0.164	0.60 (0.56)	0.94	66715.1	10210.00
32	965.58	462.47	0.159	0.60 (0.56)	0.94	67214.2	12000.00
33	906.88	532.66	0.152	0.60 (0.57)	0.94	67799.0	10100.00

=====
 END OF RATIONAL METHOD ANALYSIS
 =====

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2010 Advanced Engineering Software (aes)
Ver. 17.0 Release Date: 07/01/2010 License ID 1527

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 138 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 2-YR EV AUG 2023 ROKAMOTO *

FILE NAME: RU02EV38.DAT
TIME/DATE OF STUDY: 23:52 08/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 2.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 1.798
- 2) 10.00; 1.199
- 3) 15.00; 0.922
- 4) 20.00; 0.760
- 5) 25.00; 0.658
- 6) 30.00; 0.584
- 7) 40.00; 0.503
- 8) 50.00; 0.446
- 9) 60.00; 0.390
- 10) 90.00; 0.336
- 11) 120.00; 0.280
- 12) 180.00; 0.226
- 13) 360.00; 0.170
- 14) 1200.00; 0.080

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU02EV37.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3081.57	18.81	0.60 (0.46)	0.77	2181.3	10520.00
2	2956.15	46.73	0.60 (0.46)	0.77	6572.7	50600.00
3	2620.47	62.29	0.60 (0.47)	0.78	9881.7	10500.00
4	1570.69	99.01	0.60 (0.49)	0.82	16180.1	10100.00
5	1507.82	117.73	0.60 (0.50)	0.84	20091.2	13600.00
6	1508.91	133.80	0.60 (0.51)	0.85	23457.4	13210.00
7	1501.18	148.33	0.60 (0.52)	0.87	26117.1	11831.00
8	1540.67	171.70	0.60 (0.53)	0.88	30665.5	11530.00
9	1573.53	191.09	0.60 (0.54)	0.90	35026.5	11000.00
10	1635.24	213.17	0.60 (0.55)	0.91	42067.1	10850.00
11	1522.01	231.66	0.60 (0.55)	0.92	45868.8	13510.00
12	1280.93	282.68	0.60 (0.56)	0.93	54050.6	12410.00
13	1214.54	316.11	0.60 (0.56)	0.93	60136.6	12261.00
14	1191.34	329.05	0.60 (0.56)	0.94	61623.2	10410.00
15	1168.72	341.42	0.60 (0.56)	0.94	62725.1	12101.10
16	1117.81	369.29	0.60 (0.56)	0.94	65103.2	10200.00
17	1093.26	382.91	0.60 (0.56)	0.94	66041.4	12010.00
18	1039.03	412.53	0.60 (0.56)	0.94	66715.1	10210.00
19	965.58	462.47	0.60 (0.56)	0.94	67214.2	12000.00
20	906.88	532.66	0.60 (0.57)	0.94	67799.0	10100.00
TOTAL AREA (ACRES) =						67799.0

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3081.57	18.81	0.60 (0.46)	0.77	2181.3	10520.00
2	2956.15	46.73	0.60 (0.46)	0.77	6572.7	50600.00
3	2620.47	62.29	0.60 (0.47)	0.78	9881.7	10500.00
4	1570.69	99.01	0.60 (0.49)	0.82	16180.1	10100.00
5	1507.82	117.73	0.60 (0.50)	0.84	20091.2	13600.00
6	1508.91	133.80	0.60 (0.51)	0.85	23457.4	13210.00
7	1501.18	148.33	0.60 (0.52)	0.87	26117.1	11831.00
8	1540.67	171.70	0.60 (0.53)	0.88	30665.5	11530.00
9	1573.53	191.09	0.60 (0.54)	0.90	35026.5	11000.00
10	1635.24	213.17	0.60 (0.55)	0.91	42067.1	10850.00
11	1522.01	231.66	0.60 (0.55)	0.92	45868.8	13510.00
12	1280.93	282.68	0.60 (0.56)	0.93	54050.6	12410.00
13	1214.54	316.11	0.60 (0.56)	0.93	60136.6	12261.00

14	1191.34	329.05	0.60	(0.56)	0.94	61623.2	10410.00
15	1168.72	341.42	0.60	(0.56)	0.94	62725.1	12101.10
16	1117.81	369.29	0.60	(0.56)	0.94	65103.2	10200.00
17	1093.26	382.91	0.60	(0.56)	0.94	66041.4	12010.00
18	1039.03	412.53	0.60	(0.56)	0.94	66715.1	10210.00
19	965.58	462.47	0.60	(0.56)	0.94	67214.2	12000.00
20	906.88	532.66	0.60	(0.57)	0.94	67799.0	10100.00

TOTAL AREA (ACRES) = 67799.0

FLOW PROCESS FROM NODE 13803.00 TO NODE 13820.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 134.99 DOWNSTREAM(FEET) = 134.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 926.91 CHANNEL SLOPE = 0.0011
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.728

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	31.44	0.60	0.983	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.983
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3083.53
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.60
AVERAGE FLOW DEPTH(FEET) = 13.55 TRAVEL TIME (MIN.) = 2.76
Tc (MIN.) = 21.57
SUBAREA AREA (ACRES) = 31.44 SUBAREA RUNOFF (CFS) = 3.91
EFFECTIVE AREA (ACRES) = 2212.73 AREA-AVERAGED Fm (INCH/HR) = 0.46
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.78
TOTAL AREA (ACRES) = 67830.4 PEAK FLOW RATE (CFS) = 3081.57
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 13.55 FLOW VELOCITY (FEET/SEC.) = 5.60
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13820.00 = 131519.73 FEET.

FLOW PROCESS FROM NODE 13803.00 TO NODE 13820.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION (MIN.) = 21.57
RAINFALL INTENSITY (INCH/HR) = 0.73
AREA-AVERAGED Fm (INCH/HR) = 0.46
AREA-AVERAGED Fp (INCH/HR) = 0.60
AREA-AVERAGED Ap = 0.78
EFFECTIVE STREAM AREA (ACRES) = 2212.73
TOTAL STREAM AREA (ACRES) = 67830.41
PEAK FLOW RATE (CFS) AT CONFLUENCE = 3081.57

FLOW PROCESS FROM NODE 13810.00 TO NODE 13811.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<
=====

INITIAL SUBAREA FLOW-LENGTH (FEET) = 648.54
ELEVATION DATA: UPSTREAM (FEET) = 756.46 DOWNSTREAM (FEET) = 586.02

Tc = K * [(LENGTH** 3.00) / (ELEVATION CHANGE)] ** 0.20
SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 12.293
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 1.072
SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL, BROADLEAF"	-	5.58	0.60	1.000	65	12.29

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF (CFS) = 2.37
TOTAL AREA (ACRES) = 5.58 PEAK FLOW RATE (CFS) = 2.37

FLOW PROCESS FROM NODE 13811.00 TO NODE 13811.50 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 586.02 DOWNSTREAM(FEET) = 437.69
CHANNEL LENGTH THRU SUBAREA(FEET) = 696.28 CHANNEL SLOPE = 0.2130
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.938

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	14.79	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 4.65
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.79
AVERAGE FLOW DEPTH(FEET) = 0.57 TRAVEL TIME (MIN.) = 2.42
Tc (MIN.) = 14.72
SUBAREA AREA (ACRES) = 14.79 SUBAREA RUNOFF (CFS) = 4.50
EFFECTIVE AREA (ACRES) = 20.37 AREA-AVERAGED Fm (INCH/HR) = 0.60
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 20.4 PEAK FLOW RATE (CFS) = 6.19

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.64 FLOW VELOCITY (FEET/SEC.) = 5.10
LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13811.50 = 1344.82 FEET.

FLOW PROCESS FROM NODE 13811.50 TO NODE 13812.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 437.69 DOWNSTREAM(FEET) = 402.36
CHANNEL LENGTH THRU SUBAREA(FEET) = 681.04 CHANNEL SLOPE = 0.0519

CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.817
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 18.41 0.60 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 8.02
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 3.22
 AVERAGE FLOW DEPTH (FEET) = 0.91 TRAVEL TIME (MIN.) = 3.52
 Tc (MIN.) = 18.24
 SUBAREA AREA (ACRES) = 18.41 SUBAREA RUNOFF (CFS) = 3.60
 EFFECTIVE AREA (ACRES) = 38.78 AREA-AVERAGED Fm (INCH/HR) = 0.60
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 38.8 PEAK FLOW RATE (CFS) = 7.58

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 0.89 FLOW VELOCITY (FEET/SEC.) = 3.19
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13812.00 = 2025.86 FEET.

 FLOW PROCESS FROM NODE 13812.00 TO NODE 13813.00 IS CODE = 51

 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 402.36 DOWNSTREAM (FEET) = 259.72
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1282.56 CHANNEL SLOPE = 0.1112
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.699
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 27.87 0.60 0.858 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.858
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 9.91
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.49
 AVERAGE FLOW DEPTH (FEET) = 0.86 TRAVEL TIME (MIN.) = 4.76
 Tc (MIN.) = 23.00
 SUBAREA AREA (ACRES) = 27.87 SUBAREA RUNOFF (CFS) = 4.62
 EFFECTIVE AREA (ACRES) = 66.65 AREA-AVERAGED Fm (INCH/HR) = 0.56
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.94
 TOTAL AREA (ACRES) = 66.7 PEAK FLOW RATE (CFS) = 8.07

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 0.79 FLOW VELOCITY (FEET/SEC.) = 4.31
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13813.00 = 3308.42 FEET.

 FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 31

 >>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 259.72 DOWNSTREAM (FEET) = 137.00
 FLOW LENGTH (FEET) = 2412.88 MANNING'S N = 0.013
 ESTIMATED PIPE DIAMETER (INCH) INCREASED TO 36.000
 DEPTH OF FLOW IN 36.0 INCH PIPE IS 5.8 INCHES
 PIPE-FLOW VELOCITY (FEET/SEC.) = 10.92
 ESTIMATED PIPE DIAMETER (INCH) = 36.00 NUMBER OF PIPES = 1
 PIPE-FLOW (CFS) = 8.07
 PIPE TRAVEL TIME (MIN.) = 3.68 Tc (MIN.) = 26.68
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13820.00 = 5721.30 FEET.

 FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 81

 >>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 26.68
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.633
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 83.64 0.60 0.570 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.570
 SUBAREA AREA (ACRES) = 83.64 SUBAREA RUNOFF (CFS) = 21.92
 EFFECTIVE AREA (ACRES) = 150.29 AREA-AVERAGED Fm (INCH/HR) = 0.44
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.73
 TOTAL AREA (ACRES) = 150.3 PEAK FLOW RATE (CFS) = 26.05

 FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 1

 >>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
 TIME OF CONCENTRATION (MIN.) = 26.68
 RAINFALL INTENSITY (INCH/HR) = 0.63
 AREA-AVERAGED Fm (INCH/HR) = 0.44
 AREA-AVERAGED Fp (INCH/HR) = 0.60
 AREA-AVERAGED Ap = 0.73
 EFFECTIVE STREAM AREA (ACRES) = 150.29
 TOTAL STREAM AREA (ACRES) = 150.29
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 26.05

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3081.57	21.57	0.728	0.60 (0.46)	0.78	2212.7	10520.00
1	2956.15	49.52	0.449	0.60 (0.46)	0.78	6604.1	50600.00
1	2620.47	65.16	0.381	0.60 (0.47)	0.78	9913.1	10500.00
1	1570.69	102.27	0.313	0.60 (0.49)	0.82	16211.6	10100.00
1	1507.82	121.03	0.279	0.60 (0.50)	0.84	20122.7	13600.00
1	1508.91	137.10	0.265	0.60 (0.51)	0.85	23488.9	13210.00
1	1501.18	151.64	0.252	0.60 (0.52)	0.87	26148.5	11831.00
1	1540.67	174.98	0.231	0.60 (0.53)	0.88	30696.9	11530.00
1	1573.53	194.36	0.222	0.60 (0.54)	0.90	35057.9	11000.00
1	1635.24	216.40	0.215	0.60 (0.55)	0.91	42098.5	10850.00

1	1522.01	234.96	0.209	0.60	(0.55)	0.92	45900.3	13510.00
1	1280.93	286.12	0.193	0.60	(0.56)	0.93	54082.1	12410.00
1	1214.54	319.59	0.183	0.60	(0.56)	0.93	60168.0	12261.00
1	1191.34	332.55	0.179	0.60	(0.56)	0.94	61654.6	10410.00
1	1168.72	344.94	0.175	0.60	(0.56)	0.94	62756.5	12101.10
1	1117.81	372.85	0.169	0.60	(0.56)	0.94	65134.6	10200.00
1	1093.26	386.49	0.167	0.60	(0.56)	0.94	66072.9	12010.00
1	1039.03	416.15	0.164	0.60	(0.56)	0.94	66746.6	10210.00
1	965.58	466.16	0.159	0.60	(0.56)	0.94	67245.6	12000.00
1	906.88	536.41	0.151	0.60	(0.57)	0.94	67830.4	10100.00
2	26.05	26.68	0.633	0.60	(0.44)	0.73	150.3	13810.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3107.62	21.57	0.728	0.60 (0.46)	0.77	2334.2	10520.00
2	3084.70	26.68	0.633	0.60 (0.46)	0.77	3165.4	13810.00
3	2972.27	49.52	0.449	0.60 (0.46)	0.77	6754.4	50600.00
4	2634.15	65.16	0.381	0.60 (0.47)	0.78	10063.4	10500.00
5	1581.94	102.27	0.313	0.60 (0.49)	0.82	16361.9	10100.00
6	1517.85	121.03	0.279	0.60 (0.50)	0.84	20273.0	13600.00
7	1518.42	137.10	0.265	0.60 (0.51)	0.85	23639.1	13210.00
8	1510.22	151.64	0.252	0.60 (0.52)	0.87	26298.8	11831.00
9	1548.95	174.98	0.231	0.60 (0.53)	0.88	30847.2	11530.00
10	1581.49	194.36	0.222	0.60 (0.54)	0.90	35208.2	11000.00
11	1642.95	216.40	0.215	0.60 (0.55)	0.91	42248.8	10850.00
12	1529.51	234.96	0.209	0.60 (0.55)	0.92	46050.6	13510.00
13	1287.86	286.12	0.193	0.60 (0.56)	0.93	54232.4	12410.00
14	1221.10	319.59	0.183	0.60 (0.56)	0.93	60318.3	12261.00
15	1197.76	332.55	0.179	0.60 (0.56)	0.94	61804.9	10410.00
16	1175.00	344.94	0.175	0.60 (0.56)	0.94	62906.8	12101.10
17	1123.87	372.85	0.169	0.60 (0.56)	0.94	65284.9	10200.00
18	1099.27	386.49	0.167	0.60 (0.56)	0.94	66223.1	12010.00
19	1044.92	416.15	0.164	0.60 (0.56)	0.94	66896.9	10210.00
20	971.28	466.16	0.159	0.60 (0.56)	0.94	67395.9	12000.00
21	912.31	536.41	0.151	0.60 (0.56)	0.94	67980.7	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 3107.62 Tc (MIN.) = 21.57
EFFECTIVE AREA(ACRES) = 2334.25 AREA-AVERAGED Fm(INCH/HR) = 0.46
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.77
TOTAL AREA(ACRES) = 67980.7
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13820.00 = 131519.73 FEET.

FLOW PROCESS FROM NODE 13820.00 TO NODE 13840.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 137.00 DOWNSTREAM(FEET) = 133.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1261.34 CHANNEL SLOPE = 0.0032
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.677

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	31.60	0.60	0.683	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.683
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3111.42
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.44
AVERAGE FLOW DEPTH(FEET) = 11.09 TRAVEL TIME(MIN.) = 2.49
Tc(MIN.) = 24.07
SUBAREA AREA(ACRES) = 31.60 SUBAREA RUNOFF(CFS) = 7.60
EFFECTIVE AREA(ACRES) = 2365.85 AREA-AVERAGED Fm(INCH/HR) = 0.46
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.77
TOTAL AREA(ACRES) = 68012.3 PEAK FLOW RATE(CFS) = 3107.62
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 11.08 FLOW VELOCITY(FEET/SEC.) = 8.43
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13840.00 = 132781.08 FEET.

FLOW PROCESS FROM NODE 13820.00 TO NODE 13840.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

=====

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION(MIN.) = 24.07
RAINFALL INTENSITY(INCH/HR) = 0.68
AREA-AVERAGED Fm(INCH/HR) = 0.46
AREA-AVERAGED Fp(INCH/HR) = 0.60
AREA-AVERAGED Ap = 0.77
EFFECTIVE STREAM AREA(ACRES) = 2365.85
TOTAL STREAM AREA(ACRES) = 68012.30
PEAK FLOW RATE(CFS) AT CONFLUENCE = 3107.62

FLOW PROCESS FROM NODE 13830.00 TO NODE 13831.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 744.71
ELEVATION DATA: UPSTREAM(FEET) = 1100.95 DOWNSTREAM(FEET) = 959.21

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 13.858
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.985

SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL, BROADLEAF"	-	5.06	0.60	1.000	65	13.86

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 1.76
TOTAL AREA(ACRES) = 5.06 PEAK FLOW RATE(CFS) = 1.76

FLOW PROCESS FROM NODE 13831.00 TO NODE 13832.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 959.21 DOWNSTREAM(FEET) = 832.83
CHANNEL LENGTH THRU SUBAREA(FEET) = 1076.71 CHANNEL SLOPE = 0.1174
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.809
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 32.57 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5.03
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.86
AVERAGE FLOW DEPTH(FEET) = 0.66 TRAVEL TIME(MIN.) = 4.64
Tc(MIN.) = 18.50
SUBAREA AREA(ACRES) = 32.57 SUBAREA RUNOFF(CFS) = 6.12
EFFECTIVE AREA(ACRES) = 37.63 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 37.6 PEAK FLOW RATE(CFS) = 7.07

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.74 FLOW VELOCITY(FEET/SEC.) = 4.25
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13832.00 = 1821.42 FEET.

FLOW PROCESS FROM NODE 13832.00 TO NODE 13833.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 832.83 DOWNSTREAM(FEET) = 572.49
CHANNEL LENGTH THRU SUBAREA(FEET) = 1883.58 CHANNEL SLOPE = 0.1382
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.655
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 32.23 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 7.95
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.68
AVERAGE FLOW DEPTH(FEET) = 0.75 TRAVEL TIME(MIN.) = 6.71
Tc(MIN.) = 25.21
SUBAREA AREA(ACRES) = 32.23 SUBAREA RUNOFF(CFS) = 1.59
EFFECTIVE AREA(ACRES) = 69.86 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 69.9 PEAK FLOW RATE(CFS) = 7.07

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.72 FLOW VELOCITY(FEET/SEC.) = 4.52
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13833.00 = 3705.00 FEET.

FLOW PROCESS FROM NODE 13833.00 TO NODE 13834.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 572.49 DOWNSTREAM(FEET) = 471.65
CHANNEL LENGTH THRU SUBAREA(FEET) = 943.78 CHANNEL SLOPE = 0.1068
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.598
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 27.51 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 7.07
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.10
AVERAGE FLOW DEPTH(FEET) = 0.76 TRAVEL TIME(MIN.) = 3.83
Tc(MIN.) = 29.05
SUBAREA AREA(ACRES) = 27.51 SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 97.37 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 97.4 PEAK FLOW RATE(CFS) = 7.07

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.76 FLOW VELOCITY(FEET/SEC.) = 4.10
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13834.00 = 4648.78 FEET.

FLOW PROCESS FROM NODE 13834.00 TO NODE 13835.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 471.65 DOWNSTREAM(FEET) = 347.06
CHANNEL LENGTH THRU SUBAREA(FEET) = 1647.45 CHANNEL SLOPE = 0.0756
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.530
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 94.21 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 7.07

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 3.58
AVERAGE FLOW DEPTH (FEET) = 0.81 TRAVEL TIME (MIN.) = 7.68
Tc (MIN.) = 36.72
SUBAREA AREA (ACRES) = 94.21 SUBAREA RUNOFF (CFS) = 0.00
EFFECTIVE AREA (ACRES) = 191.58 AREA-AVERAGED Fm (INCH/HR) = 0.60
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA (ACRES) = 191.6 PEAK FLOW RATE (CFS) = 7.07
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.81 FLOW VELOCITY (FEET/SEC.) = 3.58
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13835.00 = 6296.23 FEET.

FLOW PROCESS FROM NODE 13835.00 TO NODE 13836.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 347.06 DOWNSTREAM (FEET) = 269.29
CHANNEL LENGTH THRU SUBAREA (FEET) = 1696.71 CHANNEL SLOPE = 0.0458
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.467
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	233.25	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 7.07
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 2.98
AVERAGE FLOW DEPTH (FEET) = 0.89 TRAVEL TIME (MIN.) = 9.50
Tc (MIN.) = 46.23
SUBAREA AREA (ACRES) = 233.25 SUBAREA RUNOFF (CFS) = 0.00
EFFECTIVE AREA (ACRES) = 424.83 AREA-AVERAGED Fm (INCH/HR) = 0.60
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA (ACRES) = 424.8 PEAK FLOW RATE (CFS) = 7.07
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.89 FLOW VELOCITY (FEET/SEC.) = 2.98
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13836.00 = 7992.94 FEET.

FLOW PROCESS FROM NODE 13836.00 TO NODE 13837.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 269.29 DOWNSTREAM (FEET) = 191.87
CHANNEL LENGTH THRU SUBAREA (FEET) = 2529.21 CHANNEL SLOPE = 0.0306

CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.388
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	134.70	0.60	0.880	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.880
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 9.88
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 2.79
AVERAGE FLOW DEPTH (FEET) = 1.09 TRAVEL TIME (MIN.) = 15.11
Tc (MIN.) = 61.34

SUBAREA AREA (ACRES) = 134.70 SUBAREA RUNOFF (CFS) = 5.64
EFFECTIVE AREA (ACRES) = 559.53 AREA-AVERAGED Fm (INCH/HR) = 0.58
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.97
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA (ACRES) = 559.5 PEAK FLOW RATE (CFS) = 7.07
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.96 FLOW VELOCITY (FEET/SEC.) = 2.56
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13837.00 = 10522.15 FEET.

FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 191.87 DOWNSTREAM (FEET) = 133.00
FLOW LENGTH (FEET) = 1151.02 MANNING'S N = 0.013
ESTIMATED PIPE DIAMETER (INCH) INCREASED TO 36.000
DEPTH OF FLOW IN 36.0 INCH PIPE IS 5.4 INCHES
PIPE-FLOW VELOCITY (FEET/SEC.) = 10.51
ESTIMATED PIPE DIAMETER (INCH) = 36.00 NUMBER OF PIPES = 1
PIPE-FLOW (CFS) = 7.07
PIPE TRAVEL TIME (MIN.) = 1.82 Tc (MIN.) = 63.16
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13840.00 = 11673.17 FEET.

FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) = 63.16
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.384
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.97	0.60	0.622	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.622
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA (ACRES) = 5.97 SUBAREA RUNOFF (CFS) = 0.78
 EFFECTIVE AREA (ACRES) = 565.50 AREA-AVERAGED Fm (INCH/HR) = 0.58
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.97
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA (ACRES) = 565.5 PEAK FLOW RATE (CFS) = 7.07
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<<

=====

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
 TIME OF CONCENTRATION (MIN.) = 63.16
 RAINFALL INTENSITY (INCH/HR) = 0.38
 AREA-AVERAGED Fm (INCH/HR) = 0.58
 AREA-AVERAGED Fp (INCH/HR) = 0.60
 AREA-AVERAGED Ap = 0.97
 EFFECTIVE STREAM AREA (ACRES) = 565.50
 TOTAL STREAM AREA (ACRES) = 565.50
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 7.07

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3107.62	24.07	0.677	0.60 (0.46)	0.77	2365.9	10520.00
1	3084.70	29.18	0.596	0.60 (0.46)	0.77	3197.0	13810.00
1	2972.27	52.04	0.435	0.60 (0.46)	0.77	6786.0	50600.00
1	2634.15	67.76	0.376	0.60 (0.47)	0.78	10095.0	10500.00
1	1581.94	105.23	0.308	0.60 (0.49)	0.82	16393.5	10100.00
1	1517.85	124.01	0.276	0.60 (0.50)	0.84	20304.6	13600.00
1	1518.42	140.08	0.262	0.60 (0.51)	0.85	23670.7	13210.00
1	1510.22	154.63	0.249	0.60 (0.52)	0.87	26330.4	11831.00
1	1548.95	177.95	0.228	0.60 (0.53)	0.88	30878.8	11530.00
1	1581.49	197.30	0.221	0.60 (0.54)	0.90	35239.8	11000.00
1	1642.95	219.33	0.214	0.60 (0.55)	0.91	42280.4	10850.00
1	1529.51	237.93	0.208	0.60 (0.55)	0.92	46082.2	13510.00
1	1287.86	289.22	0.192	0.60 (0.56)	0.93	54264.0	12410.00
1	1221.10	322.74	0.182	0.60 (0.56)	0.93	60349.9	12261.00
1	1197.76	335.72	0.178	0.60 (0.56)	0.94	61836.5	10410.00
1	1175.00	348.12	0.174	0.60 (0.56)	0.94	62938.4	12101.10
1	1123.87	376.07	0.168	0.60 (0.56)	0.94	65316.5	10200.00
1	1099.27	389.72	0.167	0.60 (0.56)	0.94	66254.8	12010.00
1	1044.92	419.43	0.164	0.60 (0.56)	0.94	66928.5	10210.00
1	971.28	469.49	0.158	0.60 (0.56)	0.94	67427.5	12000.00
1	912.31	539.79	0.151	0.60 (0.56)	0.94	68012.3	10100.00
2	7.07	63.16	0.384	0.60 (0.58)	0.97	565.5	13830.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3114.69	24.07	0.677	0.60 (0.47)	0.79	2581.3	10520.00

2	3089.77	29.18	0.596	0.60 (0.47)	0.79	3458.3	13810.00
3	2978.86	52.04	0.435	0.60 (0.47)	0.79	7252.0	50600.00
4	2740.15	63.16	0.384	0.60 (0.47)	0.79	9692.4	13830.00
5	2641.06	67.76	0.376	0.60 (0.47)	0.79	10660.5	10500.00
6	1587.59	105.23	0.308	0.60 (0.49)	0.83	16959.0	10100.00
7	1522.93	124.01	0.276	0.60 (0.50)	0.84	20870.1	13600.00
8	1523.23	140.08	0.262	0.60 (0.51)	0.86	24236.2	13210.00
9	1514.79	154.63	0.249	0.60 (0.52)	0.87	26895.9	11831.00
10	1553.14	177.95	0.228	0.60 (0.53)	0.88	31444.3	11530.00
11	1585.55	197.30	0.221	0.60 (0.54)	0.90	35805.3	11000.00
12	1646.88	219.33	0.214	0.60 (0.55)	0.91	42845.9	10850.00
13	1533.34	237.93	0.208	0.60 (0.55)	0.92	46647.7	13510.00
14	1291.39	289.22	0.192	0.60 (0.56)	0.93	54829.5	12410.00
15	1224.44	322.74	0.182	0.60 (0.56)	0.93	60915.4	12261.00
16	1201.02	335.72	0.178	0.60 (0.56)	0.94	62402.0	10410.00
17	1178.19	348.12	0.174	0.60 (0.56)	0.94	63503.9	12101.10
18	1126.96	376.07	0.168	0.60 (0.56)	0.94	65882.0	10200.00
19	1102.33	389.72	0.167	0.60 (0.56)	0.94	66820.2	12010.00
20	1047.93	419.43	0.164	0.60 (0.56)	0.94	67494.0	10210.00
21	974.19	469.49	0.158	0.60 (0.56)	0.94	67993.0	12000.00
22	915.08	539.79	0.151	0.60 (0.56)	0.94	68577.8	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 3114.69 Tc (MIN.) = 24.07
 EFFECTIVE AREA (ACRES) = 2581.33 AREA-AVERAGED Fm (INCH/HR) = 0.47
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.79
 TOTAL AREA (ACRES) = 68577.8
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13840.00 = 132781.08 FEET.

 FLOW PROCESS FROM NODE 13840.00 TO NODE 13860.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 133.00 DOWNSTREAM (FEET) = 130.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 654.44 CHANNEL SLOPE = 0.0046
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.655

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	6.61	0.60	0.975	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.975
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 3114.90
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 9.69
 AVERAGE FLOW DEPTH (FEET) = 10.35 TRAVEL TIME (MIN.) = 1.13
 Tc (MIN.) = 25.19
 SUBAREA AREA (ACRES) = 6.61 SUBAREA RUNOFF (CFS) = 0.42
 EFFECTIVE AREA (ACRES) = 2587.94 AREA-AVERAGED Fm (INCH/HR) = 0.47
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.79
 TOTAL AREA (ACRES) = 68584.4 PEAK FLOW RATE (CFS) = 3114.69
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 10.35 FLOW VELOCITY (FEET/SEC.) = 9.69

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13860.00 = 133435.52 FEET.

FLOW PROCESS FROM NODE 13840.00 TO NODE 13860.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

TOTAL NUMBER OF STREAMS = 2

CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:

TIME OF CONCENTRATION(MIN.) = 25.19

RAINFALL INTENSITY(INCH/HR) = 0.66

AREA-AVERAGED Fm(INCH/HR) = 0.47

AREA-AVERAGED Fp(INCH/HR) = 0.60

AREA-AVERAGED Ap = 0.79

EFFECTIVE STREAM AREA(ACRES) = 2587.94

TOTAL STREAM AREA(ACRES) = 68584.41

PEAK FLOW RATE(CFS) AT CONFLUENCE = 3114.69

FLOW PROCESS FROM NODE 13850.00 TO NODE 13851.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<

>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH(FEET) = 617.57

ELEVATION DATA: UPSTREAM(FEET) = 646.95 DOWNSTREAM(FEET) = 490.10

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20

SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 12.137

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 1.081

SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER						
"CHAPARRAL,BROADLEAF"	-	4.95	0.60	1.000	65	12.14
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60						
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000						
SUBAREA RUNOFF(CFS) = 2.14						
TOTAL AREA(ACRES) = 4.95 PEAK FLOW RATE(CFS) = 2.14						

FLOW PROCESS FROM NODE 13851.00 TO NODE 13851.50 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 490.10 DOWNSTREAM(FEET) = 440.98

CHANNEL LENGTH THRU SUBAREA(FEET) = 351.14 CHANNEL SLOPE = 0.1399

CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.990

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	4.02	0.60	1.000	-
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000					
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2.85					

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.60

AVERAGE FLOW DEPTH(FEET) = 0.51 TRAVEL TIME(MIN.) = 1.63

Tc(MIN.) = 13.76

SUBAREA AREA(ACRES) = 4.02 SUBAREA RUNOFF(CFS) = 1.41

EFFECTIVE AREA(ACRES) = 8.97 AREA-AVERAGED Fm(INCH/HR) = 0.60

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 9.0 PEAK FLOW RATE(CFS) = 3.15

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.53 FLOW VELOCITY(FEET/SEC.) = 3.73

LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13851.50 = 968.71 FEET.

FLOW PROCESS FROM NODE 13851.50 TO NODE 13852.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 440.98 DOWNSTREAM(FEET) = 395.76

CHANNEL LENGTH THRU SUBAREA(FEET) = 512.91 CHANNEL SLOPE = 0.0882

CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.879

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.17	0.60	1.000	-
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000					
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 4.06					
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.32					
AVERAGE FLOW DEPTH(FEET) = 0.64 TRAVEL TIME(MIN.) = 2.57					
Tc(MIN.) = 16.34					
SUBAREA AREA(ACRES) = 7.17 SUBAREA RUNOFF(CFS) = 1.80					
EFFECTIVE AREA(ACRES) = 16.14 AREA-AVERAGED Fm(INCH/HR) = 0.60					
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00					
TOTAL AREA(ACRES) = 16.1 PEAK FLOW RATE(CFS) = 4.05					

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.64 FLOW VELOCITY(FEET/SEC.) = 3.32

LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13852.00 = 1481.62 FEET.

FLOW PROCESS FROM NODE 13852.00 TO NODE 13853.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 395.76 DOWNSTREAM(FEET) = 354.94

CHANNEL LENGTH THRU SUBAREA(FEET) = 443.69 CHANNEL SLOPE = 0.0920

CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.810

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	6.76	0.60	1.000	-
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60					

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 4.69
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.50
 AVERAGE FLOW DEPTH(FEET) = 0.67 TRAVEL TIME(MIN.) = 2.11
 Tc(MIN.) = 18.45
 SUBAREA AREA(ACRES) = 6.76 SUBAREA RUNOFF(CFS) = 1.28
 EFFECTIVE AREA(ACRES) = 22.90 AREA-AVERAGED Fm(INCH/HR) = 0.60
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 22.9 PEAK FLOW RATE(CFS) = 4.34

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 0.65 FLOW VELOCITY(FEET/SEC.) = 3.41
 LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13853.00 = 1925.31 FEET.

 FLOW PROCESS FROM NODE 13853.00 TO NODE 13854.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 354.94 DOWNSTREAM(FEET) = 263.57
 CHANNEL LENGTH THRU SUBAREA(FEET) = 962.09 CHANNEL SLOPE = 0.0950
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.701

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	18.16	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5.20
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.62
 AVERAGE FLOW DEPTH(FEET) = 0.69 TRAVEL TIME(MIN.) = 4.42
 Tc(MIN.) = 22.88
 SUBAREA AREA(ACRES) = 18.16 SUBAREA RUNOFF(CFS) = 1.66
 EFFECTIVE AREA(ACRES) = 41.06 AREA-AVERAGED Fm(INCH/HR) = 0.60
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 41.1 PEAK FLOW RATE(CFS) = 4.34
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 0.65 FLOW VELOCITY(FEET/SEC.) = 3.47
 LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13854.00 = 2887.40 FEET.

 FLOW PROCESS FROM NODE 13854.00 TO NODE 13855.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 263.57 DOWNSTREAM(FEET) = 188.74
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1228.77 CHANNEL SLOPE = 0.0609
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.592
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	43.41	0.60	0.707	-

LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 38.75 0.60 0.879 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.879
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5.59
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.12
 AVERAGE FLOW DEPTH(FEET) = 0.77 TRAVEL TIME(MIN.) = 6.57
 Tc(MIN.) = 29.45
 SUBAREA AREA(ACRES) = 38.75 SUBAREA RUNOFF(CFS) = 2.50
 EFFECTIVE AREA(ACRES) = 79.81 AREA-AVERAGED Fm(INCH/HR) = 0.56
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.94
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 79.8 PEAK FLOW RATE(CFS) = 4.34
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 0.70 FLOW VELOCITY(FEET/SEC.) = 2.96
 LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13855.00 = 4116.17 FEET.

 FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 188.74 DOWNSTREAM(FEET) = 130.00
 FLOW LENGTH(FEET) = 2092.67 MANNING'S N = 0.013
 ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000
 DEPTH OF FLOW IN 36.0 INCH PIPE IS 5.0 INCHES
 PIPE-FLOW VELOCITY(FEET/SEC.) = 7.36
 ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1
 PIPE-FLOW(CFS) = 4.34
 PIPE TRAVEL TIME(MIN.) = 4.74 Tc(MIN.) = 34.19
 LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13860.00 = 6208.84 FEET.

 FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 34.19
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.550
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	43.41	0.60	0.707	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.707
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 SUBAREA AREA(ACRES) = 43.41 SUBAREA RUNOFF(CFS) = 6.30
 EFFECTIVE AREA(ACRES) = 123.22 AREA-AVERAGED Fm(INCH/HR) = 0.52
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.86
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA (ACRES) = 123.2 PEAK FLOW RATE (CFS) = 8.62

FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION (MIN.) = 34.19
RAINFALL INTENSITY (INCH/HR) = 0.55
AREA-AVERAGED Fm (INCH/HR) = 0.52
AREA-AVERAGED Fp (INCH/HR) = 0.60
AREA-AVERAGED Ap = 0.86
EFFECTIVE STREAM AREA (ACRES) = 123.22
TOTAL STREAM AREA (ACRES) = 123.22
PEAK FLOW RATE (CFS) AT CONFLUENCE = 8.62

** CONFLUENCE DATA **

Table with columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp (Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 20 rows of data.

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

Table with columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp (Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 6 rows of data.

Table with columns: Node number, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp (Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 19 rows of data.

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 3123.31 Tc (MIN.) = 25.19
EFFECTIVE AREA (ACRES) = 2678.74 AREA-AVERAGED Fm (INCH/HR) = 0.47
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.79
TOTAL AREA (ACRES) = 68707.6
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13860.00 = 133435.52 FEET.

FLOW PROCESS FROM NODE 13860.00 TO NODE 13880.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 130.00 DOWNSTREAM (FEET) = 120.57
CHANNEL LENGTH THRU SUBAREA (FEET) = 610.77 CHANNEL SLOPE = 0.0154
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.645

SUBAREA LOSS RATE DATA (AMC II):

Table with columns: DEVELOPMENT TYPE/LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Contains 1 row of data.

USER-DEFINED - 4.89 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 3123.41
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 15.29
AVERAGE FLOW DEPTH (FEET) = 8.25 TRAVEL TIME (MIN.) = 0.67
Tc (MIN.) = 25.86
SUBAREA AREA (ACRES) = 4.89 SUBAREA RUNOFF (CFS) = 0.20
EFFECTIVE AREA (ACRES) = 2683.63 AREA-AVERAGED Fm (INCH/HR) = 0.47
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.79
TOTAL AREA (ACRES) = 68712.5 PEAK FLOW RATE (CFS) = 3123.31
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 8.25 FLOW VELOCITY (FEET/SEC.) = 15.29
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13880.00 = 134046.28 FEET.

FLOW PROCESS FROM NODE 13860.00 TO NODE 13880.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION(MIN.) = 25.86
RAINFALL INTENSITY(INCH/HR) = 0.65
AREA-AVERAGED Fm(INCH/HR) = 0.47
AREA-AVERAGED Fp(INCH/HR) = 0.60
AREA-AVERAGED Ap = 0.79
EFFECTIVE STREAM AREA(ACRES) = 2683.63
TOTAL STREAM AREA(ACRES) = 68712.52
PEAK FLOW RATE(CFS) AT CONFLUENCE = 3123.31

FLOW PROCESS FROM NODE 13870.00 TO NODE 13871.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH(FEET) = 872.65
ELEVATION DATA: UPSTREAM(FEET) = 558.52 DOWNSTREAM(FEET) = 436.47

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 15.704
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.899
SUBAREA Tc AND LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)
NATURAL FAIR COVER
"GRASS" - 7.32 0.60 1.000 65 15.70
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 1.97
TOTAL AREA(ACRES) = 7.32 PEAK FLOW RATE(CFS) = 1.97

FLOW PROCESS FROM NODE 13871.00 TO NODE 13872.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 436.47 DOWNSTREAM(FEET) = 337.62
CHANNEL LENGTH THRU SUBAREA(FEET) = 827.95 CHANNEL SLOPE = 0.1194
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.770
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 13.01 0.60 1.000 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3.00
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.45
AVERAGE FLOW DEPTH(FEET) = 0.54 TRAVEL TIME(MIN.) = 4.00
Tc(MIN.) = 19.70
SUBAREA AREA(ACRES) = 13.01 SUBAREA RUNOFF(CFS) = 1.99

EFFECTIVE AREA(ACRES) = 20.33 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 20.3 PEAK FLOW RATE(CFS) = 3.11

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.55 FLOW VELOCITY(FEET/SEC.) = 3.47
LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13872.00 = 1700.60 FEET.

FLOW PROCESS FROM NODE 13872.00 TO NODE 13873.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 337.62 DOWNSTREAM(FEET) = 253.88
CHANNEL LENGTH THRU SUBAREA(FEET) = 1049.16 CHANNEL SLOPE = 0.0798
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.658
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 32.99 0.60 0.923 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.923
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 4.73
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.32
AVERAGE FLOW DEPTH(FEET) = 0.69 TRAVEL TIME(MIN.) = 5.27
Tc(MIN.) = 24.98
SUBAREA AREA(ACRES) = 32.99 SUBAREA RUNOFF(CFS) = 3.11
EFFECTIVE AREA(ACRES) = 53.32 AREA-AVERAGED Fm(INCH/HR) = 0.57
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.95
TOTAL AREA(ACRES) = 53.3 PEAK FLOW RATE(CFS) = 4.18

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.66 FLOW VELOCITY(FEET/SEC.) = 3.21
LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13873.00 = 2749.76 FEET.

FLOW PROCESS FROM NODE 13873.00 TO NODE 13874.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 253.88 DOWNSTREAM(FEET) = 160.73
CHANNEL LENGTH THRU SUBAREA(FEET) = 1518.60 CHANNEL SLOPE = 0.0613
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.575
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 30.94 0.60 0.900 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.900
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 4.99

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.11
 AVERAGE FLOW DEPTH (FEET) = 0.64 TRAVEL TIME (MIN.) = 6.16
 Tc (MIN.) = 31.14
 SUBAREA AREA (ACRES) = 30.94 SUBAREA RUNOFF (CFS) = 1.60
 EFFECTIVE AREA (ACRES) = 84.26 AREA-AVERAGED Fm (INCH/HR) = 0.56
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.93
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA (ACRES) = 84.3 PEAK FLOW RATE (CFS) = 4.18
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 0.59 FLOW VELOCITY (FEET/SEC.) = 3.98
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13874.00 = 4268.36 FEET.

 FLOW PROCESS FROM NODE 13874.00 TO NODE 13875.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 160.73 DOWNSTREAM (FEET) = 158.14
 CHANNEL LENGTH THRU SUBAREA (FEET) = 582.74 CHANNEL SLOPE = 0.0044
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00

* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.525
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 73.67 0.60 0.930 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.930
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 5.41
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 1.57
 AVERAGE FLOW DEPTH (FEET) = 1.07 TRAVEL TIME (MIN.) = 6.18
 Tc (MIN.) = 37.32
 SUBAREA AREA (ACRES) = 73.67 SUBAREA RUNOFF (CFS) = 2.44
 EFFECTIVE AREA (ACRES) = 157.93 AREA-AVERAGED Fm (INCH/HR) = 0.56
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.93
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA (ACRES) = 157.9 PEAK FLOW RATE (CFS) = 5.10

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 1.05 FLOW VELOCITY (FEET/SEC.) = 1.55
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13875.00 = 4851.10 FEET.

 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 158.14 DOWNSTREAM (FEET) = 120.57
 FLOW LENGTH (FEET) = 1855.67 MANNING'S N = 0.013
 ESTIMATED PIPE DIAMETER (INCH) INCREASED TO 36.000

DEPTH OF FLOW IN 36.0 INCH PIPE IS 5.8 INCHES
 PIPE-FLOW VELOCITY (FEET/SEC.) = 6.89
 ESTIMATED PIPE DIAMETER (INCH) = 36.00 NUMBER OF PIPES = 1
 PIPE-FLOW (CFS) = 5.10
 PIPE TRAVEL TIME (MIN.) = 4.49 Tc (MIN.) = 41.81
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13880.00 = 6706.77 FEET.

 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 41.81
 * 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.493
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 34.90 0.60 0.743 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.743
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 SUBAREA AREA (ACRES) = 34.90 SUBAREA RUNOFF (CFS) = 3.98
 EFFECTIVE AREA (ACRES) = 192.83 AREA-AVERAGED Fm (INCH/HR) = 0.54
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.90
 * RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
 * IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
 TOTAL AREA (ACRES) = 192.8 PEAK FLOW RATE (CFS) = 8.76

 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
 TIME OF CONCENTRATION (MIN.) = 41.81
 RAINFALL INTENSITY (INCH/HR) = 0.49
 AREA-AVERAGED Fm (INCH/HR) = 0.54
 AREA-AVERAGED Fp (INCH/HR) = 0.60
 AREA-AVERAGED Ap = 0.90
 EFFECTIVE STREAM AREA (ACRES) = 192.83
 TOTAL STREAM AREA (ACRES) = 192.83
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 8.76

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3123.31	25.86	0.645	0.60 (0.47)	0.79	2683.6	10520.00
1	3097.85	30.97	0.576	0.60 (0.47)	0.79	3579.0	13810.00
1	3079.58	34.86	0.545	0.60 (0.47)	0.79	4236.5	13850.00
1	2985.57	53.86	0.424	0.60 (0.47)	0.79	7386.7	50600.00
1	2746.13	65.01	0.381	0.60 (0.47)	0.79	9827.1	13830.00
1	2646.92	69.63	0.373	0.60 (0.47)	0.79	10795.3	10500.00
1	1592.37	107.35	0.304	0.60 (0.50)	0.83	17093.7	10100.00
1	1527.24	126.15	0.274	0.60 (0.50)	0.84	21004.8	13600.00
1	1527.32	142.22	0.260	0.60 (0.51)	0.86	24371.0	13210.00

1	1518.67	156.77	0.247	0.60	(0.52)	0.87	27030.6	11831.00
1	1556.69	180.08	0.226	0.60	(0.53)	0.88	31579.0	11530.00
1	1589.00	199.43	0.220	0.60	(0.54)	0.90	35940.0	11000.00
1	1650.22	221.43	0.213	0.60	(0.55)	0.91	42980.6	10850.00
1	1536.59	240.07	0.207	0.60	(0.55)	0.92	46782.4	13510.00
1	1294.40	291.46	0.191	0.60	(0.56)	0.93	54964.2	12410.00
1	1227.27	325.00	0.181	0.60	(0.56)	0.93	61050.1	12261.00
1	1203.80	337.99	0.177	0.60	(0.56)	0.94	62536.7	10410.00
1	1180.91	350.40	0.173	0.60	(0.56)	0.94	63638.7	12101.10
1	1129.59	378.38	0.168	0.60	(0.56)	0.94	66016.7	10200.00
1	1104.94	392.05	0.167	0.60	(0.56)	0.94	66955.0	12010.00
1	1050.49	421.78	0.163	0.60	(0.56)	0.94	67628.7	10210.00
1	976.66	471.89	0.158	0.60	(0.56)	0.94	68127.7	12000.00
1	917.44	542.23	0.150	0.60	(0.56)	0.94	68712.5	10100.00
2	8.76	41.81	0.493	0.60	(0.54)	0.90	192.8	13870.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3132.07	25.86	0.645	0.60 (0.48)	0.80	2802.9	10520.00
2	3105.44	30.97	0.576	0.60 (0.48)	0.79	3721.9	13810.00
3	3087.65	34.86	0.545	0.60 (0.48)	0.79	4397.2	13850.00
4	3053.92	41.81	0.493	0.60 (0.48)	0.79	5582.7	13870.00
5	2993.11	53.86	0.424	0.60 (0.47)	0.79	7579.5	50600.00
6	2752.91	65.01	0.381	0.60 (0.48)	0.79	10019.9	13830.00
7	2653.55	69.63	0.373	0.60 (0.48)	0.79	10988.1	10500.00
8	1597.77	107.35	0.304	0.60 (0.50)	0.83	17286.5	10100.00
9	1532.12	126.15	0.274	0.60 (0.50)	0.84	21197.6	13600.00
10	1531.94	142.22	0.260	0.60 (0.51)	0.86	24563.8	13210.00
11	1523.06	156.77	0.247	0.60 (0.52)	0.87	27223.5	11831.00
12	1560.71	180.08	0.226	0.60 (0.53)	0.88	31771.9	11530.00
13	1592.91	199.43	0.220	0.60 (0.54)	0.90	36132.9	11000.00
14	1654.01	221.43	0.213	0.60 (0.55)	0.91	43173.4	10850.00
15	1540.28	240.07	0.207	0.60 (0.55)	0.92	46975.2	13510.00
16	1297.80	291.46	0.191	0.60 (0.56)	0.93	55157.0	12410.00
17	1230.49	325.00	0.181	0.60 (0.56)	0.93	61242.9	12261.00
18	1206.94	337.99	0.177	0.60 (0.56)	0.94	62729.5	10410.00
19	1183.98	350.40	0.173	0.60 (0.56)	0.94	63831.5	12101.10
20	1132.58	378.38	0.168	0.60 (0.56)	0.94	66209.6	10200.00
21	1107.91	392.05	0.167	0.60 (0.56)	0.94	67147.8	12010.00
22	1053.40	421.78	0.163	0.60 (0.56)	0.94	67821.5	10210.00
23	979.47	471.89	0.158	0.60 (0.56)	0.94	68320.6	12000.00
24	920.11	542.23	0.150	0.60 (0.56)	0.94	68905.3	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 3132.07 Tc (MIN.) = 25.86
EFFECTIVE AREA(ACRES) = 2802.89 AREA-AVERAGED Fm(INCH/HR) = 0.48
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.80
TOTAL AREA(ACRES) = 68905.3
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13880.00 = 134046.28 FEET.

FLOW PROCESS FROM NODE 13880.00 TO NODE 13910.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 120.57 DOWNSTREAM(FEET) = 119.70
CHANNEL LENGTH THRU SUBAREA(FEET) = 1190.21 CHANNEL SLOPE = 0.0007
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.585

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	117.69	0.60	0.724	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.724

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3140.63

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.88

AVERAGE FLOW DEPTH(FEET) = 14.65 TRAVEL TIME(MIN.) = 4.07

Tc(MIN.) = 29.93

SUBAREA AREA(ACRES) = 117.69 SUBAREA RUNOFF(CFS) = 17.10

EFFECTIVE AREA(ACRES) = 2920.58 AREA-AVERAGED Fm(INCH/HR) = 0.48

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.79

* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 69023.0 PEAK FLOW RATE(CFS) = 3132.07

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 14.64 FLOW VELOCITY(FEET/SEC.) = 4.87

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13910.00 = 135236.48 FEET.

FLOW PROCESS FROM NODE 13880.00 TO NODE 13910.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

TOTAL NUMBER OF STREAMS = 2

CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:

TIME OF CONCENTRATION(MIN.) = 29.93

RAINFALL INTENSITY(INCH/HR) = 0.59

AREA-AVERAGED Fm(INCH/HR) = 0.48

AREA-AVERAGED Fp(INCH/HR) = 0.60

AREA-AVERAGED Ap = 0.79

EFFECTIVE STREAM AREA(ACRES) = 2920.58

TOTAL STREAM AREA(ACRES) = 69023.03

PEAK FLOW RATE(CFS) AT CONFLUENCE = 3132.07

FLOW PROCESS FROM NODE 13889.00 TO NODE 13890.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<

>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH(FEET) = 447.89

ELEVATION DATA: UPSTREAM(FEET) = 564.89 DOWNSTREAM(FEET) = 421.92

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20

SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 6.976

* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 1.561
SUBAREA Tc AND LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)
PUBLIC PARK - 3.03 0.60 0.960 65 6.98
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.960
SUBAREA RUNOFF (CFS) = 2.69
TOTAL AREA (ACRES) = 3.03 PEAK FLOW RATE (CFS) = 2.69

FLOW PROCESS FROM NODE 13890.00 TO NODE 13891.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 421.92 DOWNSTREAM (FEET) = 392.64
CHANNEL LENGTH THRU SUBAREA (FEET) = 435.33 CHANNEL SLOPE = 0.0673
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00

* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 1.365
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 8.12 0.60 0.986 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.986
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 5.53
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.42
AVERAGE FLOW DEPTH (FEET) = 0.65 TRAVEL TIME (MIN.) = 1.64
Tc (MIN.) = 8.62
SUBAREA AREA (ACRES) = 8.12 SUBAREA RUNOFF (CFS) = 5.65
EFFECTIVE AREA (ACRES) = 11.15 AREA-AVERAGED Fm (INCH/HR) = 0.59
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.98
TOTAL AREA (ACRES) = 11.1 PEAK FLOW RATE (CFS) = 7.80

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.74 FLOW VELOCITY (FEET/SEC.) = 4.78
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13891.00 = 883.22 FEET.

FLOW PROCESS FROM NODE 13891.00 TO NODE 13892.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 392.64 DOWNSTREAM (FEET) = 324.46
CHANNEL LENGTH THRU SUBAREA (FEET) = 662.40 CHANNEL SLOPE = 0.1029
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00

* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 1.176
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 12.50 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 11.05

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.13
AVERAGE FLOW DEPTH (FEET) = 0.78 TRAVEL TIME (MIN.) = 1.80
Tc (MIN.) = 10.42
SUBAREA AREA (ACRES) = 12.50 SUBAREA RUNOFF (CFS) = 6.48
EFFECTIVE AREA (ACRES) = 23.65 AREA-AVERAGED Fm (INCH/HR) = 0.59
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 23.6 PEAK FLOW RATE (CFS) = 12.39

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.81 FLOW VELOCITY (FEET/SEC.) = 6.27
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13892.00 = 1545.62 FEET.

FLOW PROCESS FROM NODE 13892.00 TO NODE 13893.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 324.46 DOWNSTREAM (FEET) = 240.82
CHANNEL LENGTH THRU SUBAREA (FEET) = 980.03 CHANNEL SLOPE = 0.0853
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00

* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 1.030
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 15.87 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 15.47
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.22
AVERAGE FLOW DEPTH (FEET) = 0.91 TRAVEL TIME (MIN.) = 2.63
Tc (MIN.) = 13.05
SUBAREA AREA (ACRES) = 15.87 SUBAREA RUNOFF (CFS) = 6.15
EFFECTIVE AREA (ACRES) = 39.52 AREA-AVERAGED Fm (INCH/HR) = 0.60
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 39.5 PEAK FLOW RATE (CFS) = 15.44

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.91 FLOW VELOCITY (FEET/SEC.) = 6.20
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13893.00 = 2525.65 FEET.

FLOW PROCESS FROM NODE 13893.00 TO NODE 13894.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 240.82 DOWNSTREAM (FEET) = 163.04
CHANNEL LENGTH THRU SUBAREA (FEET) = 1144.35 CHANNEL SLOPE = 0.0680
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00

* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.882
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 28.41 0.60 0.985 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.985
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 19.20
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.00
 AVERAGE FLOW DEPTH(FEET) = 1.03 TRAVEL TIME(MIN.) = 3.18
 Tc(MIN.) = 16.23
 SUBAREA AREA(ACRES) = 28.41 SUBAREA RUNOFF(CFS) = 7.45
 EFFECTIVE AREA(ACRES) = 67.93 AREA-AVERAGED Fm(INCH/HR) = 0.59
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 67.9 PEAK FLOW RATE(CFS) = 17.62

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 1.00 FLOW VELOCITY(FEET/SEC.) = 5.92
 LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13894.00 = 3670.00 FEET.

 FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 163.04 DOWNSTREAM(FEET) = 119.70
 FLOW LENGTH(FEET) = 1899.01 MANNING'S N = 0.013
 ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000
 DEPTH OF FLOW IN 36.0 INCH PIPE IS 10.5 INCHES
 PIPE-FLOW VELOCITY(FEET/SEC.) = 10.32
 ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1
 PIPE-FLOW(CFS) = 17.62
 PIPE TRAVEL TIME(MIN.) = 3.07 Tc(MIN.) = 19.29
 LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13910.00 = 5569.01 FEET.

 FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 19.29
 * 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.783
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	11.69	0.60	0.634	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.634
 SUBAREA AREA(ACRES) = 11.69 SUBAREA RUNOFF(CFS) = 4.24
 EFFECTIVE AREA(ACRES) = 79.62 AREA-AVERAGED Fm(INCH/HR) = 0.56
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.94
 TOTAL AREA(ACRES) = 79.6 PEAK FLOW RATE(CFS) = 17.62
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
 TIME OF CONCENTRATION(MIN.) = 19.29

RAINFALL INTENSITY(INCH/HR) = 0.78
 AREA-AVERAGED Fm(INCH/HR) = 0.56
 AREA-AVERAGED Fp(INCH/HR) = 0.60
 AREA-AVERAGED Ap = 0.94
 EFFECTIVE STREAM AREA(ACRES) = 79.62
 TOTAL STREAM AREA(ACRES) = 79.62
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 17.62

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3132.07	29.93	0.585	0.60(0.48)	0.79	2920.6	10520.00
1	3105.44	35.05	0.543	0.60(0.47)	0.79	3839.6	13810.00
1	3087.65	38.94	0.512	0.60(0.47)	0.79	4514.9	13850.00
1	3053.92	45.90	0.469	0.60(0.47)	0.79	5700.4	13870.00
1	2993.11	57.97	0.401	0.60(0.47)	0.79	7697.2	50600.00
1	2752.91	69.21	0.373	0.60(0.47)	0.79	10137.6	13830.00
1	2653.55	73.87	0.365	0.60(0.48)	0.79	11105.8	10500.00
1	1597.77	112.16	0.295	0.60(0.50)	0.83	17404.2	10100.00
1	1532.12	131.02	0.270	0.60(0.50)	0.84	21315.3	13600.00
1	1531.94	147.08	0.256	0.60(0.51)	0.86	24681.5	13210.00
1	1523.06	161.64	0.243	0.60(0.52)	0.87	27341.2	11831.00
1	1560.71	184.93	0.224	0.60(0.53)	0.88	31889.5	11530.00
1	1592.91	204.24	0.218	0.60(0.54)	0.90	36250.6	11000.00
1	1654.01	226.20	0.212	0.60(0.55)	0.91	43291.1	10850.00
1	1540.28	244.93	0.206	0.60(0.55)	0.92	47092.9	13510.00
1	1297.80	296.53	0.190	0.60(0.56)	0.93	55274.7	12410.00
1	1230.49	330.14	0.179	0.60(0.56)	0.93	61360.6	12261.00
1	1206.94	343.15	0.175	0.60(0.56)	0.94	62847.2	10410.00
1	1183.98	355.60	0.171	0.60(0.56)	0.94	63949.2	12101.10
1	1132.58	383.62	0.167	0.60(0.56)	0.94	66327.2	10200.00
1	1107.91	397.32	0.166	0.60(0.56)	0.94	67265.5	12010.00
1	1053.40	427.12	0.163	0.60(0.56)	0.94	67939.2	10210.00
1	979.47	477.33	0.157	0.60(0.56)	0.94	68438.3	12000.00
1	920.11	547.75	0.150	0.60(0.56)	0.94	69023.0	10100.00
2	17.62	19.29	0.783	0.60(0.56)	0.94	79.6	13889.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3149.69	19.29	0.783	0.60(0.48)	0.80	1962.4	13889.00
2	3134.97	29.93	0.585	0.60(0.48)	0.80	3000.2	10520.00
3	3108.13	35.05	0.543	0.60(0.48)	0.79	3919.2	13810.00
4	3090.19	38.94	0.512	0.60(0.48)	0.79	4594.5	13850.00
5	3056.25	45.90	0.469	0.60(0.48)	0.79	5780.0	13870.00
6	2995.11	57.97	0.401	0.60(0.47)	0.79	7776.8	50600.00
7	2754.76	69.21	0.373	0.60(0.48)	0.79	10217.2	13830.00
8	2655.36	73.87	0.365	0.60(0.48)	0.79	11185.4	10500.00
9	1599.24	112.16	0.295	0.60(0.50)	0.83	17483.8	10100.00
10	1533.46	131.02	0.270	0.60(0.50)	0.84	21394.9	13600.00
11	1533.21	147.08	0.256	0.60(0.51)	0.86	24761.1	13210.00
12	1524.27	161.64	0.243	0.60(0.52)	0.87	27420.8	11831.00
13	1561.82	184.93	0.224	0.60(0.53)	0.88	31969.2	11530.00
14	1593.99	204.24	0.218	0.60(0.54)	0.90	36330.2	11000.00
15	1655.06	226.20	0.212	0.60(0.55)	0.91	43370.7	10850.00

16	1541.30	244.93	0.206	0.60	(0.55)	0.92	47172.5	13510.00
17	1298.74	296.53	0.190	0.60	(0.56)	0.93	55354.3	12410.00
18	1231.38	330.14	0.179	0.60	(0.56)	0.93	61440.2	12261.00
19	1207.81	343.15	0.175	0.60	(0.56)	0.94	62926.8	10410.00
20	1184.83	355.60	0.171	0.60	(0.56)	0.94	64028.8	12101.10
21	1133.41	383.62	0.167	0.60	(0.56)	0.94	66406.9	10200.00
22	1108.73	397.32	0.166	0.60	(0.56)	0.94	67345.1	12010.00
23	1054.20	427.12	0.163	0.60	(0.56)	0.94	68018.8	10210.00
24	980.26	477.33	0.157	0.60	(0.56)	0.94	68517.9	12000.00
25	920.86	547.75	0.150	0.60	(0.56)	0.94	69102.6	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 3149.69 Tc (MIN.) = 19.29
EFFECTIVE AREA (ACRES) = 1962.44 AREA-AVERAGED Fm (INCH/HR) = 0.48
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.80
TOTAL AREA (ACRES) = 69102.6
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13910.00 = 135236.48 FEET.

=====
END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 69102.6 TC (MIN.) = 19.29
EFFECTIVE AREA (ACRES) = 1962.44 AREA-AVERAGED Fm (INCH/HR) = 0.48
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.799
PEAK FLOW RATE (CFS) = 3149.69

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3149.69	19.29	0.783	0.60 (0.48)	0.80	1962.4	13889.00
2	3134.97	29.93	0.585	0.60 (0.48)	0.80	3000.2	10520.00
3	3108.13	35.05	0.543	0.60 (0.48)	0.79	3919.2	13810.00
4	3090.19	38.94	0.512	0.60 (0.48)	0.79	4594.5	13850.00
5	3056.25	45.90	0.469	0.60 (0.48)	0.79	5780.0	13870.00
6	2995.11	57.97	0.401	0.60 (0.47)	0.79	7776.8	50600.00
7	2754.76	69.21	0.373	0.60 (0.48)	0.79	10217.2	13830.00
8	2655.36	73.87	0.365	0.60 (0.48)	0.79	11185.4	10500.00
9	1599.24	112.16	0.295	0.60 (0.50)	0.83	17483.8	10100.00
10	1533.46	131.02	0.270	0.60 (0.50)	0.84	21394.9	13600.00
11	1533.21	147.08	0.256	0.60 (0.51)	0.86	24761.1	13210.00
12	1524.27	161.64	0.243	0.60 (0.52)	0.87	27420.8	11831.00
13	1561.82	184.93	0.224	0.60 (0.53)	0.88	31969.2	11530.00
14	1593.99	204.24	0.218	0.60 (0.54)	0.90	36330.2	11000.00
15	1655.06	226.20	0.212	0.60 (0.55)	0.91	43370.7	10850.00
16	1541.30	244.93	0.206	0.60 (0.55)	0.92	47172.5	13510.00
17	1298.74	296.53	0.190	0.60 (0.56)	0.93	55354.3	12410.00
18	1231.38	330.14	0.179	0.60 (0.56)	0.93	61440.2	12261.00
19	1207.81	343.15	0.175	0.60 (0.56)	0.94	62926.8	10410.00
20	1184.83	355.60	0.171	0.60 (0.56)	0.94	64028.8	12101.10
21	1133.41	383.62	0.167	0.60 (0.56)	0.94	66406.9	10200.00
22	1108.73	397.32	0.166	0.60 (0.56)	0.94	67345.1	12010.00
23	1054.20	427.12	0.163	0.60 (0.56)	0.94	68018.8	10210.00
24	980.26	477.33	0.157	0.60 (0.56)	0.94	68517.9	12000.00
25	920.86	547.75	0.150	0.60 (0.56)	0.94	69102.6	10100.00

=====
END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2010 Advanced Engineering Software (aes)
Ver. 17.0 Release Date: 07/01/2010 License ID 1527

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 139 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 2-YR EV AUG 2023 ROKAMOTO *

FILE NAME: RU02EV39.DAT
TIME/DATE OF STUDY: 23:52 08/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 2.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 1.797
- 2) 10.00; 1.198
- 3) 15.00; 0.921
- 4) 20.00; 0.760
- 5) 25.00; 0.658
- 6) 30.00; 0.584
- 7) 40.00; 0.503
- 8) 50.00; 0.446
- 9) 60.00; 0.390
- 10) 90.00; 0.336
- 11) 120.00; 0.280
- 12) 180.00; 0.226
- 13) 360.00; 0.166
- 14) 1200.00; 0.080

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT-/PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH LIP (FT)	HIKE FACTOR (FT)	MANNING (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167 0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:

- 1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13900.00 TO NODE 13901.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 600.65
ELEVATION DATA: UPSTREAM(FEET) = 442.40 DOWNSTREAM(FEET) = 385.16

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 10.859
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 1.150
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
AGRICULTURAL POOR COVER "FALLOW"	-	4.00	0.60	1.000	65	10.86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 1.98
TOTAL AREA(ACRES) = 4.00 PEAK FLOW RATE(CFS) = 1.98

FLOW PROCESS FROM NODE 13901.00 TO NODE 13902.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 385.16 DOWNSTREAM(FEET) = 288.21
CHANNEL LENGTH THRU SUBAREA(FEET) = 647.42 CHANNEL SLOPE = 0.1497
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 1.039
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.47	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3.66
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.35
AVERAGE FLOW DEPTH(FEET) = 0.48 TRAVEL TIME(MIN.) = 2.02
Tc(MIN.) = 12.88
SUBAREA AREA(ACRES) = 8.47 SUBAREA RUNOFF(CFS) = 3.35
EFFECTIVE AREA(ACRES) = 12.47 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 12.5 PEAK FLOW RATE(CFS) = 4.92

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.54 FLOW VELOCITY(FEET/SEC.) = 5.69
LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13902.00 = 1248.07 FEET.

FLOW PROCESS FROM NODE 13902.00 TO NODE 13903.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 288.21 DOWNSTREAM(FEET) = 184.89
CHANNEL LENGTH THRU SUBAREA(FEET) = 669.27 CHANNEL SLOPE = 0.1544
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.947
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 23.85 0.60 0.982 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.982
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 8.78
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.74
AVERAGE FLOW DEPTH(FEET) = 0.66 TRAVEL TIME(MIN.) = 1.65
Tc(MIN.) = 14.53
SUBAREA AREA(ACRES) = 23.85 SUBAREA RUNOFF(CFS) = 7.68
EFFECTIVE AREA(ACRES) = 36.32 AREA-AVERAGED Fm(INCH/HR) = 0.59
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 36.3 PEAK FLOW RATE(CFS) = 11.58

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.73 FLOW VELOCITY(FEET/SEC.) = 7.25
LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13903.00 = 1917.34 FEET.

FLOW PROCESS FROM NODE 13903.00 TO NODE 13904.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 184.89 DOWNSTREAM(FEET) = 155.08
FLOW LENGTH(FEET) = 876.66 MANNING'S N = 0.013
ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000
DEPTH OF FLOW IN 36.0 INCH PIPE IS 7.7 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 10.53
ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 11.58
PIPE TRAVEL TIME(MIN.) = 1.39 Tc(MIN.) = 15.92
LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13904.00 = 2794.00 FEET.

FLOW PROCESS FROM NODE 13903.00 TO NODE 13904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 15.92
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.891
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 21.29 0.60 0.996 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.996

SUBAREA AREA(ACRES) = 21.29 SUBAREA RUNOFF(CFS) = 5.63
EFFECTIVE AREA(ACRES) = 57.61 AREA-AVERAGED Fm(INCH/HR) = 0.59
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 57.6 PEAK FLOW RATE(CFS) = 15.40

FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 155.08 DOWNSTREAM(FEET) = 118.00
FLOW LENGTH(FEET) = 1961.38 MANNING'S N = 0.013
ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000
DEPTH OF FLOW IN 36.0 INCH PIPE IS 10.3 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 9.28
ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 15.40
PIPE TRAVEL TIME(MIN.) = 3.52 Tc(MIN.) = 19.44
LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13920.00 = 4755.38 FEET.

FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 19.44
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.778
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 43.53 0.60 0.649 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.649
SUBAREA AREA(ACRES) = 43.53 SUBAREA RUNOFF(CFS) = 15.23
EFFECTIVE AREA(ACRES) = 101.14 AREA-AVERAGED Fm(INCH/HR) = 0.51
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.84
TOTAL AREA(ACRES) = 101.1 PEAK FLOW RATE(CFS) = 24.74

FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 13910.00 TO NODE 13910.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: RU02EV38.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:
STREAM Q Tc Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (ACRES) NODE
1 3149.69 19.29 0.60(0.48) 0.80 1962.4 13889.00
2 3056.25 45.90 0.60(0.48) 0.79 5780.0 13870.00
3 2995.11 57.97 0.60(0.47) 0.79 7776.8 50600.00
4 1599.24 112.16 0.60(0.50) 0.83 17483.8 10100.00

5	1533.46	131.02	0.60	(0.50)	0.84	21394.9	13600.00
6	1533.21	147.08	0.60	(0.51)	0.86	24761.1	13210.00
7	1524.27	161.64	0.60	(0.52)	0.87	27420.8	11831.00
8	1561.82	184.93	0.60	(0.53)	0.88	31969.2	11530.00
9	1593.99	204.24	0.60	(0.54)	0.90	36330.2	11000.00
10	1655.06	226.20	0.60	(0.55)	0.91	43370.7	10850.00
11	1541.30	244.93	0.60	(0.55)	0.92	47172.5	13510.00
12	1298.74	296.53	0.60	(0.56)	0.93	55354.3	12410.00
13	1231.38	330.14	0.60	(0.56)	0.93	61440.2	12261.00
14	1207.81	343.15	0.60	(0.56)	0.94	62926.8	10410.00
15	1184.83	355.60	0.60	(0.56)	0.94	64028.8	12101.10
16	1133.41	383.62	0.60	(0.56)	0.94	66406.9	10200.00
17	1108.73	397.32	0.60	(0.56)	0.94	67345.1	12010.00
18	1054.20	427.12	0.60	(0.56)	0.94	68018.8	10210.00
19	980.26	477.33	0.60	(0.56)	0.94	68517.9	12000.00
20	920.86	547.75	0.60	(0.56)	0.94	69102.6	10100.00

TOTAL AREA (ACRES) = 69102.6

FLOW PROCESS FROM NODE 13910.00 TO NODE 13910.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3149.69	19.29	0.60 (0.48)	0.80	1962.4	13889.00
2	3056.25	45.90	0.60 (0.48)	0.79	5780.0	13870.00
3	2995.11	57.97	0.60 (0.47)	0.79	7776.8	50600.00
4	1599.24	112.16	0.60 (0.50)	0.83	17483.8	10100.00
5	1533.46	131.02	0.60 (0.50)	0.84	21394.9	13600.00
6	1533.21	147.08	0.60 (0.51)	0.86	24761.1	13210.00
7	1524.27	161.64	0.60 (0.52)	0.87	27420.8	11831.00
8	1561.82	184.93	0.60 (0.53)	0.88	31969.2	11530.00
9	1593.99	204.24	0.60 (0.54)	0.90	36330.2	11000.00
10	1655.06	226.20	0.60 (0.55)	0.91	43370.7	10850.00
11	1541.30	244.93	0.60 (0.55)	0.92	47172.5	13510.00
12	1298.74	296.53	0.60 (0.56)	0.93	55354.3	12410.00
13	1231.38	330.14	0.60 (0.56)	0.93	61440.2	12261.00
14	1207.81	343.15	0.60 (0.56)	0.94	62926.8	10410.00
15	1184.83	355.60	0.60 (0.56)	0.94	64028.8	12101.10
16	1133.41	383.62	0.60 (0.56)	0.94	66406.9	10200.00
17	1108.73	397.32	0.60 (0.56)	0.94	67345.1	12010.00
18	1054.20	427.12	0.60 (0.56)	0.94	68018.8	10210.00
19	980.26	477.33	0.60 (0.56)	0.94	68517.9	12000.00
20	920.86	547.75	0.60 (0.56)	0.94	69102.6	10100.00

TOTAL AREA (ACRES) = 69102.6

FLOW PROCESS FROM NODE 13910.00 TO NODE 13920.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 119.70 DOWNSTREAM(FEET) = 118.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1376.26 CHANNEL SLOPE = 0.0012
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.696
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCSSOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 96.09 0.60 0.535 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.535
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3165.92
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.95
AVERAGE FLOW DEPTH(FEET) = 13.32 TRAVEL TIME(MIN.) = 3.86
Tc(MIN.) = 23.15
SUBAREA AREA(ACRES) = 96.09 SUBAREA RUNOFF(CFS) = 32.42
EFFECTIVE AREA(ACRES) = 2058.53 AREA-AVERAGED Fm(INCH/HR) = 0.47
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.79
TOTAL AREA(ACRES) = 69198.7 PEAK FLOW RATE(CFS) = 3149.69
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 13.29 FLOW VELOCITY(FEET/SEC.) = 5.94
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136612.75 FEET.

FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3149.69	23.15	0.696	0.60 (0.47)	0.79	2058.5	13889.00
2	3056.25	49.79	0.447	0.60 (0.47)	0.79	5876.1	13870.00
3	2995.11	61.88	0.387	0.60 (0.47)	0.79	7872.9	50600.00
4	1599.24	116.73	0.286	0.60 (0.49)	0.82	17579.9	10100.00
5	1533.46	135.63	0.266	0.60 (0.50)	0.84	21491.0	13600.00
6	1533.21	151.70	0.251	0.60 (0.51)	0.85	24857.2	13210.00
7	1524.27	166.27	0.238	0.60 (0.52)	0.87	27516.9	11831.00
8	1561.82	189.52	0.223	0.60 (0.53)	0.88	32065.3	11530.00
9	1593.99	208.81	0.216	0.60 (0.54)	0.90	36426.3	11000.00
10	1655.06	230.73	0.209	0.60 (0.55)	0.91	43466.8	10850.00
11	1541.30	249.55	0.203	0.60 (0.55)	0.92	47268.6	13510.00
12	1298.74	301.34	0.186	0.60 (0.56)	0.93	55450.4	12410.00
13	1231.38	335.02	0.174	0.60 (0.56)	0.93	61536.3	12261.00
14	1207.81	348.06	0.170	0.60 (0.56)	0.93	63022.9	10410.00
15	1184.83	360.52	0.166	0.60 (0.56)	0.94	64124.9	12101.10
16	1133.41	388.60	0.163	0.60 (0.56)	0.94	66503.0	10200.00
17	1108.73	402.33	0.162	0.60 (0.56)	0.94	67441.2	12010.00
18	1054.20	432.19	0.159	0.60 (0.56)	0.94	68114.9	10210.00
19	980.26	482.49	0.153	0.60 (0.56)	0.94	68614.0	12000.00
20	920.86	552.99	0.146	0.60 (0.56)	0.94	69198.7	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136612.75 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24.74	19.44	0.778	0.60 (0.51)	0.84	101.1	13900.00

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13920.00 = 4755.38 FEET.

** PEAK FLOW RATE TABLE **

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp (Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 21 rows of data and a total area calculation.

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 3174.44 Tc(MIN.) = 19.440
EFFECTIVE AREA(ACRES) = 1829.94 AREA-AVERAGED Fm(INCH/HR) = 0.47
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.94
TOTAL AREA(ACRES) = 69299.9
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136612.75 FEET.

FLOW PROCESS FROM NODE 13920.00 TO NODE 13921.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 118.00 DOWNSTREAM(FEET) = 115.28
CHANNEL LENGTH THRU SUBAREA(FEET) = 335.44 CHANNEL SLOPE = 0.0081
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.763
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 134.30 0.60 0.658 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.658
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3196.71
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.07
AVERAGE FLOW DEPTH(FEET) = 9.39 TRAVEL TIME(MIN.) = 0.46
Tc(MIN.) = 19.90
SUBAREA AREA(ACRES) = 134.30 SUBAREA RUNOFF(CFS) = 44.53
EFFECTIVE AREA(ACRES) = 1964.24 AREA-AVERAGED Fm(INCH/HR) = 0.47
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.78

TOTAL AREA(ACRES) = 69434.2 PEAK FLOW RATE(CFS) = 3174.44

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 9.37 FLOW VELOCITY(FEET/SEC.) = 12.06
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13921.00 = 136948.19 FEET.

FLOW PROCESS FROM NODE 13921.00 TO NODE 14010.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 115.28 DOWNSTREAM(FEET) = 100.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1396.08 CHANNEL SLOPE = 0.0109
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.727
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 96.27 0.60 0.723 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.723
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3187.15
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 13.50
AVERAGE FLOW DEPTH(FEET) = 8.87 TRAVEL TIME(MIN.) = 1.72
Tc(MIN.) = 21.63
SUBAREA AREA(ACRES) = 96.27 SUBAREA RUNOFF(CFS) = 25.40
EFFECTIVE AREA(ACRES) = 2060.51 AREA-AVERAGED Fm(INCH/HR) = 0.47
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.78
TOTAL AREA(ACRES) = 69530.5 PEAK FLOW RATE(CFS) = 3174.44
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 8.85 FLOW VELOCITY(FEET/SEC.) = 13.50
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 14010.00 = 138344.27 FEET.

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 69530.5 TC(MIN.) = 21.63
EFFECTIVE AREA(ACRES) = 2060.51 AREA-AVERAGED Fm(INCH/HR) = 0.47
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.778
PEAK FLOW RATE(CFS) = 3174.44

** PEAK FLOW RATE TABLE **

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp (Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 11 rows of data.

12	1544.18	252.17	0.202	0.60	(0.55)	0.92	47600.3	13510.00
13	1301.38	304.08	0.185	0.60	(0.56)	0.93	55782.1	12410.00
14	1233.86	337.79	0.173	0.60	(0.56)	0.93	61868.0	12261.00
15	1210.23	350.84	0.169	0.60	(0.56)	0.93	63354.6	10410.00
16	1187.19	363.32	0.166	0.60	(0.56)	0.93	64456.6	12101.10
17	1135.73	391.43	0.163	0.60	(0.56)	0.94	66834.7	10200.00
18	1111.03	405.18	0.161	0.60	(0.56)	0.94	67772.9	12010.00
19	1056.46	435.07	0.158	0.60	(0.56)	0.94	68446.6	10210.00
20	982.44	485.42	0.153	0.60	(0.56)	0.94	68945.7	12000.00
21	922.94	555.97	0.146	0.60	(0.56)	0.94	69530.5	10100.00

=====
=====
END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International
5 Hutton Centre Drive, Suite 500
Santa Ana, CA 92707

***** DESCRIPTION OF STUDY *****
* RANCHO MISSION VIEJO - PA3 & PA4 ROMP - NODE 119 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 5-YR RM EV APRIL 2019 FKAZI *

FILE NAME: RU05EV19.DAT
TIME/DATE OF STUDY: 11:09 04/03/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 5.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 2.749
- 2) 10.00; 1.821
- 3) 15.00; 1.328
- 4) 20.00; 1.137
- 5) 25.00; 0.990
- 6) 30.00; 0.887
- 7) 40.00; 0.760
- 8) 50.00; 0.677
- 9) 60.00; 0.617
- 10) 90.00; 0.514
- 11) 120.00; 0.457
- 12) 180.00; 0.384
- 13) 360.00; 0.286
- 14) 1200.00; 0.126

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:

- 1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 11900.00 TO NODE 11901.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 295.79
ELEVATION DATA: UPSTREAM(FEET) = 2369.48 DOWNSTREAM(FEET) = 2332.92

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 7.203
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 2.340
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
RESIDENTIAL ".4 DWELLING/ACRE"	-	1.62	0.50	0.999	0	7.20

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999
SUBAREA RUNOFF(CFS) = 2.68
TOTAL AREA(ACRES) = 1.62 PEAK FLOW RATE(CFS) = 2.68

FLOW PROCESS FROM NODE 11901.00 TO NODE 11902.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2332.92 DOWNSTREAM(FEET) = 2297.70
CHANNEL LENGTH THRU SUBAREA(FEET) = 664.26 CHANNEL SLOPE = 0.0530
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.758
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.35	0.50	0.906	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.906
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 7.65
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.22
AVERAGE FLOW DEPTH(FEET) = 0.89 TRAVEL TIME(MIN.) = 3.44
Tc(MIN.) = 10.64
SUBAREA AREA(ACRES) = 8.35 SUBAREA RUNOFF(CFS) = 9.80
EFFECTIVE AREA(ACRES) = 9.97 AREA-AVERAGED Fm(INCH/HR) = 0.46
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 10.0 PEAK FLOW RATE(CFS) = 11.64

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.04 FLOW VELOCITY(FEET/SEC.) = 3.57
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11902.00 = 960.05 FEET.

FLOW PROCESS FROM NODE 11902.00 TO NODE 11902.50 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2297.70 DOWNSTREAM(FEET) = 2263.40
CHANNEL LENGTH THRU SUBAREA(FEET) = 928.77 CHANNEL SLOPE = 0.0369
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.357
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 34.48 0.50 0.904 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.904
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 25.97
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.81
AVERAGE FLOW DEPTH(FEET) = 1.51 TRAVEL TIME(MIN.) = 4.07
Tc(MIN.) = 14.71
SUBAREA AREA(ACRES) = 34.48 SUBAREA RUNOFF(CFS) = 28.08
EFFECTIVE AREA(ACRES) = 44.45 AREA-AVERAGED Fm(INCH/HR) = 0.45
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.91
TOTAL AREA(ACRES) = 44.5 PEAK FLOW RATE(CFS) = 36.12

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.71 FLOW VELOCITY(FEET/SEC.) = 4.14
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11902.50 = 1888.82 FEET.

FLOW PROCESS FROM NODE 11902.50 TO NODE 11903.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2263.40 DOWNSTREAM(FEET) = 2252.14
CHANNEL LENGTH THRU SUBAREA(FEET) = 895.50 CHANNEL SLOPE = 0.0126
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.142
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 23.65 0.50 0.958 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.958
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 43.19
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 2.89
AVERAGE FLOW DEPTH(FEET) = 2.23 TRAVEL TIME(MIN.) = 5.17
Tc(MIN.) = 19.87
SUBAREA AREA(ACRES) = 23.65 SUBAREA RUNOFF(CFS) = 14.10
EFFECTIVE AREA(ACRES) = 68.10 AREA-AVERAGED Fm(INCH/HR) = 0.46
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 68.1 PEAK FLOW RATE(CFS) = 41.62

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 2.20 FLOW VELOCITY(FEET/SEC.) = 2.86
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11903.00 = 2784.32 FEET.

FLOW PROCESS FROM NODE 11903.00 TO NODE 11904.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2252.14 DOWNSTREAM(FEET) = 2186.04
CHANNEL LENGTH THRU SUBAREA(FEET) = 1924.35 CHANNEL SLOPE = 0.0343
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.948
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 68.53 0.50 0.961 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.961
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 56.17
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.49
AVERAGE FLOW DEPTH(FEET) = 2.04 TRAVEL TIME(MIN.) = 7.14
Tc(MIN.) = 27.01
SUBAREA AREA(ACRES) = 68.53 SUBAREA RUNOFF(CFS) = 28.85
EFFECTIVE AREA(ACRES) = 136.63 AREA-AVERAGED Fm(INCH/HR) = 0.47
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.94
TOTAL AREA(ACRES) = 136.6 PEAK FLOW RATE(CFS) = 58.62

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 2.07 FLOW VELOCITY(FEET/SEC.) = 4.55
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11904.00 = 4708.67 FEET.

FLOW PROCESS FROM NODE 11904.00 TO NODE 11905.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2186.04 DOWNSTREAM(FEET) = 1957.34
CHANNEL LENGTH THRU SUBAREA(FEET) = 1926.87 CHANNEL SLOPE = 0.1187
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.871
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 63.15 0.50 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 69.17
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.53
AVERAGE FLOW DEPTH(FEET) = 1.75 TRAVEL TIME(MIN.) = 4.27
Tc(MIN.) = 31.28
SUBAREA AREA(ACRES) = 63.15 SUBAREA RUNOFF(CFS) = 21.06
EFFECTIVE AREA(ACRES) = 199.78 AREA-AVERAGED Fm(INCH/HR) = 0.48
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.96
TOTAL AREA(ACRES) = 199.8 PEAK FLOW RATE(CFS) = 70.12

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.76 FLOW VELOCITY(FEET/SEC.) = 7.57
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11905.00 = 6635.54 FEET.

FLOW PROCESS FROM NODE 11905.00 TO NODE 11906.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) =	1957.34	DOWNSTREAM(FEET) =	1244.16
CHANNEL LENGTH THRU SUBAREA(FEET) =	2498.96	CHANNEL SLOPE =	0.2854
CHANNEL BASE(FEET) =	0.00	"Z" FACTOR =	3.000
MANNING'S FACTOR =	0.060	MAXIMUM DEPTH(FEET) =	20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) =	0.822		

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	84.87	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 82.43

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.95

AVERAGE FLOW DEPTH(FEET) = 1.58 TRAVEL TIME(MIN.) = 3.80

Tc(MIN.) = 35.08

SUBAREA AREA(ACRES) = 84.87 SUBAREA RUNOFF(CFS) = 24.61

EFFECTIVE AREA(ACRES) = 284.65 AREA-AVERAGED Fm(INCH/HR) = 0.49

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.97

TOTAL AREA(ACRES) = 284.6 PEAK FLOW RATE(CFS) = 86.05

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.61 FLOW VELOCITY(FEET/SEC.) = 11.03

LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11906.00 = 9134.50 FEET.

FLOW PROCESS FROM NODE 11906.00 TO NODE 11920.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) =	1244.16	DOWNSTREAM(FEET) =	873.95
CHANNEL LENGTH THRU SUBAREA(FEET) =	3370.75	CHANNEL SLOPE =	0.1098
CHANNEL BASE(FEET) =	0.00	"Z" FACTOR =	3.000
MANNING'S FACTOR =	0.060	MAXIMUM DEPTH(FEET) =	20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) =	0.744		

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	199.43	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 108.00

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.20

AVERAGE FLOW DEPTH(FEET) = 2.10 TRAVEL TIME(MIN.) = 6.85

Tc(MIN.) = 41.93

SUBAREA AREA(ACRES) = 199.43 SUBAREA RUNOFF(CFS) = 43.75

EFFECTIVE AREA(ACRES) = 484.08 AREA-AVERAGED Fm(INCH/HR) = 0.49

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.98

TOTAL AREA(ACRES) = 484.1 PEAK FLOW RATE(CFS) = 109.69

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.11 FLOW VELOCITY(FEET/SEC.) = 8.21

LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11920.00 = 12505.25 FEET.

FLOW PROCESS FROM NODE 11906.00 TO NODE 11920.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

=====

TOTAL NUMBER OF STREAMS = 2

CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:

TIME OF CONCENTRATION(MIN.) = 41.93

RAINFALL INTENSITY(INCH/HR) = 0.74

AREA-AVERAGED Fm(INCH/HR) = 0.49

AREA-AVERAGED Fp(INCH/HR) = 0.50

AREA-AVERAGED Ap = 0.98

EFFECTIVE STREAM AREA(ACRES) = 484.08

TOTAL STREAM AREA(ACRES) = 484.08

PEAK FLOW RATE(CFS) AT CONFLUENCE = 109.69

FLOW PROCESS FROM NODE 11910.00 TO NODE 11911.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<

>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 517.62

ELEVATION DATA: UPSTREAM(FEET) = 2531.88 DOWNSTREAM(FEET) = 2441.33

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20

SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 12.185

* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.606

SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	-	3.46	0.50	1.000	0	12.19

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA RUNOFF(CFS) = 3.44

TOTAL AREA(ACRES) = 3.46 PEAK FLOW RATE(CFS) = 3.44

FLOW PROCESS FROM NODE 11911.00 TO NODE 11912.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) =	2441.33	DOWNSTREAM(FEET) =	2382.20
CHANNEL LENGTH THRU SUBAREA(FEET) =	397.30	CHANNEL SLOPE =	0.1488
CHANNEL BASE(FEET) =	0.00	"Z" FACTOR =	3.000
MANNING'S FACTOR =	0.060	MAXIMUM DEPTH(FEET) =	20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) =	1.458		

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.79	0.50	1.000	-

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.98

TOTAL AREA(ACRES) = 5.79 PEAK FLOW RATE(CFS) = 109.69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5.94
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.43
AVERAGE FLOW DEPTH(FEET) = 0.67 TRAVEL TIME(MIN.) = 1.49
Tc(MIN.) = 13.68
SUBAREA AREA(ACRES) = 5.79 SUBAREA RUNOFF(CFS) = 4.99
EFFECTIVE AREA(ACRES) = 9.25 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 9.2 PEAK FLOW RATE(CFS) = 7.98

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.74 FLOW VELOCITY(FEET/SEC.) = 4.79
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11912.00 = 914.92 FEET.

FLOW PROCESS FROM NODE 11912.00 TO NODE 11913.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2382.20 DOWNSTREAM(FEET) = 2263.77
CHANNEL LENGTH THRU SUBAREA(FEET) = 1891.47 CHANNEL SLOPE = 0.0626
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.117

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 54.30 0.50 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 23.41
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.51
AVERAGE FLOW DEPTH(FEET) = 1.32 TRAVEL TIME(MIN.) = 6.99
Tc(MIN.) = 20.66
SUBAREA AREA(ACRES) = 54.30 SUBAREA RUNOFF(CFS) = 30.17
EFFECTIVE AREA(ACRES) = 63.55 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 63.5 PEAK FLOW RATE(CFS) = 35.30

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.53 FLOW VELOCITY(FEET/SEC.) = 5.02
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11913.00 = 2806.39 FEET.

FLOW PROCESS FROM NODE 11913.00 TO NODE 11914.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2263.77 DOWNSTREAM(FEET) = 1845.23
CHANNEL LENGTH THRU SUBAREA(FEET) = 1957.31 CHANNEL SLOPE = 0.2138
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.007

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS

LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 65.14 0.50 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 50.20
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.64
AVERAGE FLOW DEPTH(FEET) = 1.39 TRAVEL TIME(MIN.) = 3.77
Tc(MIN.) = 24.44
SUBAREA AREA(ACRES) = 65.14 SUBAREA RUNOFF(CFS) = 29.68
EFFECTIVE AREA(ACRES) = 128.69 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 128.7 PEAK FLOW RATE(CFS) = 58.64

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.47 FLOW VELOCITY(FEET/SEC.) = 9.05
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11914.00 = 4763.70 FEET.

FLOW PROCESS FROM NODE 11914.00 TO NODE 11915.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1845.23 DOWNSTREAM(FEET) = 1557.21
CHANNEL LENGTH THRU SUBAREA(FEET) = 1686.78 CHANNEL SLOPE = 0.1708
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.936

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 78.52 0.50 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 74.05
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.79
AVERAGE FLOW DEPTH(FEET) = 1.68 TRAVEL TIME(MIN.) = 3.20
Tc(MIN.) = 27.64
SUBAREA AREA(ACRES) = 78.52 SUBAREA RUNOFF(CFS) = 30.77
EFFECTIVE AREA(ACRES) = 207.21 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 207.2 PEAK FLOW RATE(CFS) = 81.21

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.73 FLOW VELOCITY(FEET/SEC.) = 9.00
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11915.00 = 6450.48 FEET.

FLOW PROCESS FROM NODE 11915.00 TO NODE 11916.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1557.21 DOWNSTREAM(FEET) = 1403.38
CHANNEL LENGTH THRU SUBAREA(FEET) = 1909.39 CHANNEL SLOPE = 0.0806
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.859

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	70.48	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 92.62
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.99
AVERAGE FLOW DEPTH(FEET) = 2.10 TRAVEL TIME(MIN.) = 4.55
Tc(MIN.) = 32.19
SUBAREA AREA(ACRES) = 70.48 SUBAREA RUNOFF(CFS) = 22.77
EFFECTIVE AREA(ACRES) = 277.69 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 277.7 PEAK FLOW RATE(CFS) = 89.73

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 2.07 FLOW VELOCITY(FEET/SEC.) = 6.96
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11916.00 = 8359.87 FEET.

FLOW PROCESS FROM NODE 11916.00 TO NODE 11917.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 1403.38 DOWNSTREAM(FEET) = 1079.99
CHANNEL LENGTH THRU SUBAREA(FEET) = 1945.82 CHANNEL SLOPE = 0.1662
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.817

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	232.20	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 122.92
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.85
AVERAGE FLOW DEPTH(FEET) = 2.04 TRAVEL TIME(MIN.) = 3.29
Tc(MIN.) = 35.48
SUBAREA AREA(ACRES) = 232.20 SUBAREA RUNOFF(CFS) = 66.29
EFFECTIVE AREA(ACRES) = 509.89 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 509.9 PEAK FLOW RATE(CFS) = 145.56

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 2.17 FLOW VELOCITY(FEET/SEC.) = 10.29
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11917.00 = 10305.69 FEET.

FLOW PROCESS FROM NODE 11917.00 TO NODE 11920.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 1079.99 DOWNSTREAM(FEET) = 873.95
CHANNEL LENGTH THRU SUBAREA(FEET) = 2563.91 CHANNEL SLOPE = 0.0804
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.753

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	110.82	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 158.20
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.01
AVERAGE FLOW DEPTH(FEET) = 2.57 TRAVEL TIME(MIN.) = 5.34
Tc(MIN.) = 40.82
SUBAREA AREA(ACRES) = 110.82 SUBAREA RUNOFF(CFS) = 25.24
EFFECTIVE AREA(ACRES) = 620.71 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 620.7 PEAK FLOW RATE(CFS) = 145.56
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 2.49 FLOW VELOCITY(FEET/SEC.) = 7.83
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11920.00 = 12869.60 FEET.

FLOW PROCESS FROM NODE 11917.00 TO NODE 11920.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 40.82
RAINFALL INTENSITY(INCH/HR) = 0.75
AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50
AREA-AVERAGED Ap = 1.00
EFFECTIVE STREAM AREA(ACRES) = 620.71
TOTAL STREAM AREA(ACRES) = 620.71
PEAK FLOW RATE(CFS) AT CONFLUENCE = 145.56

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	109.69	41.93	0.744	0.50(0.49)	0.98	484.1	11900.00
2	145.56	40.82	0.753	0.50(0.50)	1.00	620.7	11910.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	255.25	40.82	0.753	0.50(0.50)	0.99	1091.9	11910.00
2	249.92	41.93	0.744	0.50(0.50)	0.99	1104.8	11900.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
PEAK FLOW RATE(CFS) = 255.25 Tc(MIN.) = 40.82
EFFECTIVE AREA(ACRES) = 1091.90 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99

TOTAL AREA (ACRES) = 1104.8
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11920.00 = 12869.60 FEET.

FLOW PROCESS FROM NODE 11920.00 TO NODE 11921.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 873.95 DOWNSTREAM (FEET) = 827.94
CHANNEL LENGTH THRU SUBAREA (FEET) = 1417.25 CHANNEL SLOPE = 0.0325
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.723
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	107.47	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 266.03
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.49
AVERAGE FLOW DEPTH (FEET) = 3.70 TRAVEL TIME (MIN.) = 3.64
Tc (MIN.) = 44.46
SUBAREA AREA (ACRES) = 107.47 SUBAREA RUNOFF (CFS) = 21.55
EFFECTIVE AREA (ACRES) = 1199.37 AREA-AVERAGED Fm (INCH/HR) = 0.50
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 1212.3 PEAK FLOW RATE (CFS) = 255.25
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 3.64 FLOW VELOCITY (FEET/SEC.) = 6.41
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11921.00 = 14286.85 FEET.

FLOW PROCESS FROM NODE 11921.00 TO NODE 11922.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 827.94 DOWNSTREAM (FEET) = 753.55
CHANNEL LENGTH THRU SUBAREA (FEET) = 1886.43 CHANNEL SLOPE = 0.0394
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.686
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	344.27	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 284.11
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.10
AVERAGE FLOW DEPTH (FEET) = 3.65 TRAVEL TIME (MIN.) = 4.43
Tc (MIN.) = 48.89
SUBAREA AREA (ACRES) = 344.27 SUBAREA RUNOFF (CFS) = 57.64
EFFECTIVE AREA (ACRES) = 1543.64 AREA-AVERAGED Fm (INCH/HR) = 0.50
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00

TOTAL AREA (ACRES) = 1556.5 PEAK FLOW RATE (CFS) = 261.87

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 3.54 FLOW VELOCITY (FEET/SEC.) = 6.95
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11922.00 = 16173.28 FEET.

FLOW PROCESS FROM NODE 11922.00 TO NODE 11923.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 753.55 DOWNSTREAM (FEET) = 641.58
CHANNEL LENGTH THRU SUBAREA (FEET) = 2860.88 CHANNEL SLOPE = 0.0391
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.643
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	165.18	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 272.48
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.99
AVERAGE FLOW DEPTH (FEET) = 3.60 TRAVEL TIME (MIN.) = 6.82
Tc (MIN.) = 55.70
SUBAREA AREA (ACRES) = 165.18 SUBAREA RUNOFF (CFS) = 21.19
EFFECTIVE AREA (ACRES) = 1708.82 AREA-AVERAGED Fm (INCH/HR) = 0.50
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 1721.7 PEAK FLOW RATE (CFS) = 261.87
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 3.55 FLOW VELOCITY (FEET/SEC.) = 6.92
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11923.00 = 19034.16 FEET.

FLOW PROCESS FROM NODE 11923.00 TO NODE 11924.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 641.58 DOWNSTREAM (FEET) = 579.89
CHANNEL LENGTH THRU SUBAREA (FEET) = 1844.02 CHANNEL SLOPE = 0.0335
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.616
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	433.73	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 284.49
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.67
AVERAGE FLOW DEPTH (FEET) = 3.77 TRAVEL TIME (MIN.) = 4.61
Tc (MIN.) = 60.31

SUBAREA AREA (ACRES) = 433.73 SUBAREA RUNOFF (CFS) = 45.17
EFFECTIVE AREA (ACRES) = 2142.55 AREA-AVERAGED Fm (INCH/HR) = 0.50
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 2155.4 PEAK FLOW RATE (CFS) = 261.87
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 3.65 FLOW VELOCITY (FEET/SEC.) = 6.55
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11924.00 = 20878.18 FEET.

FLOW PROCESS FROM NODE 11924.00 TO NODE 11925.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 579.89 DOWNSTREAM (FEET) = 494.12
CHANNEL LENGTH THRU SUBAREA (FEET) = 2756.15 CHANNEL SLOPE = 0.0311
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00

* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.591

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	265.42	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 272.77

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.44

AVERAGE FLOW DEPTH (FEET) = 3.76 TRAVEL TIME (MIN.) = 7.14

Tc (MIN.) = 67.45

SUBAREA AREA (ACRES) = 265.42 SUBAREA RUNOFF (CFS) = 21.79

EFFECTIVE AREA (ACRES) = 2407.97 AREA-AVERAGED Fm (INCH/HR) = 0.50

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00

TOTAL AREA (ACRES) = 2420.9 PEAK FLOW RATE (CFS) = 261.87

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 3.71 FLOW VELOCITY (FEET/SEC.) = 6.36

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11925.00 = 23634.33 FEET.

FLOW PROCESS FROM NODE 11925.00 TO NODE 11926.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 494.12 DOWNSTREAM (FEET) = 458.40
CHANNEL LENGTH THRU SUBAREA (FEET) = 1922.70 CHANNEL SLOPE = 0.0186
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00

* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.570

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	97.46	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 264.95
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.25
AVERAGE FLOW DEPTH (FEET) = 4.10 TRAVEL TIME (MIN.) = 6.10
Tc (MIN.) = 73.55

SUBAREA AREA (ACRES) = 97.46 SUBAREA RUNOFF (CFS) = 6.16
EFFECTIVE AREA (ACRES) = 2505.43 AREA-AVERAGED Fm (INCH/HR) = 0.50
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 2518.3 PEAK FLOW RATE (CFS) = 261.87
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 4.08 FLOW VELOCITY (FEET/SEC.) = 5.25

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11926.00 = 25557.03 FEET.

FLOW PROCESS FROM NODE 11926.00 TO NODE 11927.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 458.40 DOWNSTREAM (FEET) = 399.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 2710.13 CHANNEL SLOPE = 0.0219
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00

* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.543

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	53.83	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 262.90

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.58

AVERAGE FLOW DEPTH (FEET) = 3.96 TRAVEL TIME (MIN.) = 8.09

Tc (MIN.) = 81.64

SUBAREA AREA (ACRES) = 53.83 SUBAREA RUNOFF (CFS) = 2.06

EFFECTIVE AREA (ACRES) = 2559.26 AREA-AVERAGED Fm (INCH/HR) = 0.50

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00

TOTAL AREA (ACRES) = 2572.1 PEAK FLOW RATE (CFS) = 261.87

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 3.95 FLOW VELOCITY (FEET/SEC.) = 5.58

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 28267.16 FEET.

FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P401XX05.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	197.11	35.87	0.50 (0.50)	1.00	624.4	40130.00
2	188.26	38.23	0.50 (0.50)	1.00	654.2	40100.00
TOTAL AREA (ACRES) =		654.2				

FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<
=====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	261.87	81.64	0.543	0.50 (0.50)	1.00	2559.3	11910.00
2	250.73	83.14	0.538	0.50 (0.50)	1.00	2572.1	11900.00
LONGEST FLOWPATH FROM NODE		11910.00 TO NODE 11927.00 = 28267.16 FEET.					

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	197.11	35.87	0.812	0.50 (0.50)	1.00	624.4	40130.00
2	188.26	38.23	0.783	0.50 (0.50)	1.00	654.2	40100.00
LONGEST FLOWPATH FROM NODE		40100.00 TO NODE 11927.00 = 11231.26 FEET.					

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	458.97	35.87	0.812	0.50 (0.50)	1.00	1748.9	40130.00
2	450.13	38.23	0.783	0.50 (0.50)	1.00	1852.5	40100.00
3	290.20	81.64	0.543	0.50 (0.50)	1.00	3213.5	11910.00
4	275.63	83.14	0.538	0.50 (0.50)	1.00	3226.4	11900.00
TOTAL AREA (ACRES) =		3226.4					

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 458.97 Tc (MIN.) = 35.875
EFFECTIVE AREA (ACRES) = 1748.93 AREA-AVERAGED Fm (INCH/HR) = 0.50
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 3226.4
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 28267.16 FEET.

FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<
=====

FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.50 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<
=====

ELEVATION DATA: UPSTREAM (FEET) = 399.00 DOWNSTREAM (FEET) = 384.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 986.26 CHANNEL SLOPE = 0.0152
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00

CHANNEL FLOW THRU SUBAREA (CFS) = 458.97
FLOW VELOCITY (FEET/SEC.) = 5.60 FLOW DEPTH (FEET) = 5.23
TRAVEL TIME (MIN.) = 2.94 Tc (MIN.) = 38.81
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.50 = 29253.42 FEET.

FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====

MAINLINE Tc (MIN.) = 38.81
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.775
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 2.40 0.50 1.000 -
USER-DEFINED - 1.70 0.50 1.000 -
USER-DEFINED - 1.50 0.50 1.000 -
USER-DEFINED - 1.30 0.50 1.000 -
USER-DEFINED - 0.90 0.50 1.000 -
USER-DEFINED - 0.60 0.50 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 8.40 SUBAREA RUNOFF (CFS) = 2.08
EFFECTIVE AREA (ACRES) = 1757.33 AREA-AVERAGED Fm (INCH/HR) = 0.50
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 3234.8 PEAK FLOW RATE (CFS) = 458.97
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====

MAINLINE Tc (MIN.) = 38.81
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.775
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.30 0.50 1.000 -
USER-DEFINED - 0.10 0.50 1.000 -
USER-DEFINED - 0.10 0.50 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 0.50 SUBAREA RUNOFF (CFS) = 0.12
EFFECTIVE AREA (ACRES) = 1757.83 AREA-AVERAGED Fm (INCH/HR) = 0.50
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 3235.2 PEAK FLOW RATE (CFS) = 458.97
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====

MAINLINE Tc (MIN.) = 38.81
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.775
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.80	0.50	1.000	-
USER-DEFINED	-	0.70	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	0.10	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 2.00 SUBAREA RUNOFF(CFS) = 0.49
EFFECTIVE AREA(ACRES) = 1759.83 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 3237.2 PEAK FLOW RATE(CFS) = 458.97
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 11927.50 TO NODE 11928.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 384.00 DOWNSTREAM(FEET) = 359.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 647.19 CHANNEL SLOPE = 0.0386
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.759
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	78.01	0.50	0.984	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.984
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 468.33
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.98
AVERAGE FLOW DEPTH(FEET) = 4.42 TRAVEL TIME(MIN.) = 1.35
Tc(MIN.) = 40.16
SUBAREA AREA(ACRES) = 78.01 SUBAREA RUNOFF(CFS) = 18.71
EFFECTIVE AREA(ACRES) = 1837.84 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 3315.3 PEAK FLOW RATE(CFS) = 458.97
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 4.39 FLOW VELOCITY(FEET/SEC.) = 7.94
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11928.00 = 29900.61 FEET.

FLOW PROCESS FROM NODE 11928.00 TO NODE 11928.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 40.16
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.759
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.10	0.50	1.000	-
USER-DEFINED	-	0.60	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 1.70 SUBAREA RUNOFF(CFS) = 0.40
EFFECTIVE AREA(ACRES) = 1839.54 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 3317.0 PEAK FLOW RATE(CFS) = 458.97
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 359.00 DOWNSTREAM(FEET) = 341.63
CHANNEL LENGTH THRU SUBAREA(FEET) = 1322.66 CHANNEL SLOPE = 0.0131
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.724
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.18	0.50	0.890	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.890
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 460.00
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.29
AVERAGE FLOW DEPTH(FEET) = 5.38 TRAVEL TIME(MIN.) = 4.16
Tc(MIN.) = 44.33
SUBAREA AREA(ACRES) = 8.18 SUBAREA RUNOFF(CFS) = 2.05
EFFECTIVE AREA(ACRES) = 1847.72 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 3325.1 PEAK FLOW RATE(CFS) = 458.97
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 5.37 FLOW VELOCITY(FEET/SEC.) = 5.30
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11929.00 = 31223.27 FEET.

FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 44.33
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.724
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.90	0.50	1.000	-
USER-DEFINED	-	0.60	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 2.50 SUBAREA RUNOFF(CFS) = 0.50
EFFECTIVE AREA(ACRES) = 1850.22 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 3327.6 PEAK FLOW RATE(CFS) = 458.97
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 3 <<<<<

FLOW PROCESS FROM NODE 11841.00 TO NODE 12527.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: S18X05.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	6871.23	43.27	0.50 (0.50)	0.99	7177.4	11801.00
2	6868.03	46.61	0.50 (0.50)	0.99	7821.6	11831.00
3	6831.35	54.45	0.50 (0.50)	0.99	9253.7	11500.00
4	6778.10	60.05	0.50 (0.50)	0.99	10627.1	11701.00
5	6681.76	66.19	0.50 (0.50)	1.00	12121.5	11000.00
6	6475.61	83.04	0.50 (0.50)	1.00	17603.2	11330.00
7	6342.06	88.36	0.50 (0.50)	1.00	19494.9	10900.00
8	6230.68	91.62	0.50 (0.50)	1.00	20592.4	10830.00
9	5983.87	96.58	0.50 (0.50)	1.00	21984.5	11130.00
10	5363.28	107.52	0.50 (0.50)	1.00	24463.0	11620.00
11	5080.72	112.52	0.50 (0.50)	1.00	25521.2	10600.00
12	4959.28	115.06	0.50 (0.50)	1.00	26061.4	11600.00
13	4208.11	125.27	0.50 (0.50)	1.00	27870.7	10500.00
14	3686.50	134.23	0.50 (0.50)	1.00	29001.0	10710.00
15	3079.50	146.58	0.50 (0.50)	1.00	30024.8	10700.00
16	2649.64	155.94	0.50 (0.50)	1.00	30698.5	10400.00
17	2296.99	164.19	0.50 (0.50)	1.00	31188.4	10200.00
18	1901.26	178.29	0.50 (0.50)	1.00	31917.9	10300.00
19	1742.48	184.66	0.50 (0.50)	1.00	32047.5	10210.00
20	608.82	267.18	0.50 (0.50)	1.00	32916.6	10100.00

TOTAL AREA (ACRES) = 32916.6

FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: S25X05.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1893.24	82.32	0.50 (0.49)	0.99	5730.4	12500.00
2	1840.67	101.00	0.50 (0.49)	0.99	7460.2	12300.00
3	1831.66	103.75	0.50 (0.49)	0.99	7807.7	12330.00
4	1786.92	113.52	0.50 (0.49)	0.98	8941.0	12410.00
5	1724.88	122.39	0.50 (0.49)	0.98	9874.6	12400.00
6	1697.93	124.27	0.50 (0.49)	0.98	10031.7	12211.00
7	1549.17	132.90	0.50 (0.49)	0.98	10707.0	12201.00
8	1383.71	141.46	0.50 (0.49)	0.98	11230.3	12111.00
9	1282.12	147.13	0.50 (0.49)	0.98	11586.3	12231.00
10	1154.55	155.77	0.50 (0.49)	0.98	12067.3	12261.00
11	1138.83	156.90	0.50 (0.49)	0.98	12113.1	12101.10

12	821.51	184.54	0.50 (0.49)	0.98	13109.5	12010.00
13	621.28	203.48	0.50 (0.49)	0.98	13237.1	12000.00
TOTAL AREA (ACRES) = 13237.1						

FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1893.24	82.32	0.50 (0.49)	0.99	5730.4	12500.00
2	1840.67	101.00	0.50 (0.49)	0.99	7460.2	12300.00
3	1831.66	103.75	0.50 (0.49)	0.99	7807.7	12330.00
4	1786.92	113.52	0.50 (0.49)	0.98	8941.0	12410.00
5	1724.88	122.39	0.50 (0.49)	0.98	9874.6	12400.00
6	1697.93	124.27	0.50 (0.49)	0.98	10031.7	12211.00
7	1549.17	132.90	0.50 (0.49)	0.98	10707.0	12201.00
8	1383.71	141.46	0.50 (0.49)	0.98	11230.3	12111.00
9	1282.12	147.13	0.50 (0.49)	0.98	11586.3	12231.00
10	1154.55	155.77	0.50 (0.49)	0.98	12067.3	12261.00
11	1138.83	156.90	0.50 (0.49)	0.98	12113.1	12101.10
12	821.51	184.54	0.50 (0.49)	0.98	13109.5	12010.00
13	621.28	203.48	0.50 (0.49)	0.98	13237.1	12000.00
TOTAL AREA (ACRES) = 13237.1						

FLOW PROCESS FROM NODE 11841.00 TO NODE 12527.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1893.24	82.32	0.540	0.50 (0.49)	0.99	5730.4	12500.00
2	1840.67	101.00	0.493	0.50 (0.49)	0.99	7460.2	12300.00
3	1831.66	103.75	0.488	0.50 (0.49)	0.99	7807.7	12330.00
4	1786.92	113.52	0.469	0.50 (0.49)	0.98	8941.0	12410.00
5	1724.88	122.39	0.454	0.50 (0.49)	0.98	9874.6	12400.00
6	1697.93	124.27	0.452	0.50 (0.49)	0.98	10031.7	12211.00
7	1549.17	132.90	0.441	0.50 (0.49)	0.98	10707.0	12201.00
8	1383.71	141.46	0.431	0.50 (0.49)	0.98	11230.3	12111.00
9	1282.12	147.13	0.424	0.50 (0.49)	0.98	11586.3	12231.00
10	1154.55	155.77	0.413	0.50 (0.49)	0.98	12067.3	12261.00
11	1138.83	156.90	0.412	0.50 (0.49)	0.98	12113.1	12101.10
12	821.51	184.54	0.382	0.50 (0.49)	0.98	13109.5	12010.00
13	621.28	203.48	0.371	0.50 (0.49)	0.98	13237.1	12000.00
LONGEST FLOWPATH FROM NODE 12000.00 TO NODE 12527.00 = 77156.98 FEET.							

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	6871.23	43.27	0.733	0.50 (0.50)	0.99	7177.4	11801.00
2	6868.03	46.61	0.705	0.50 (0.50)	0.99	7821.6	11831.00
3	6831.35	54.45	0.650	0.50 (0.50)	0.99	9253.7	11500.00

4	6778.10	60.05	0.617	0.50	(0.50)	0.99	10627.1	11701.00
5	6681.76	66.19	0.596	0.50	(0.50)	1.00	12121.5	11000.00
6	6475.61	83.04	0.538	0.50	(0.50)	1.00	17603.2	11330.00
7	6342.06	88.36	0.520	0.50	(0.50)	1.00	19494.9	10900.00
8	6230.68	91.62	0.511	0.50	(0.50)	1.00	20592.4	10830.00
9	5983.87	96.58	0.502	0.50	(0.50)	1.00	21984.5	11130.00
10	5363.28	107.52	0.481	0.50	(0.50)	1.00	24463.0	11620.00
11	5080.72	112.52	0.471	0.50	(0.50)	1.00	25521.2	10600.00
12	4959.28	115.06	0.466	0.50	(0.50)	1.00	26061.4	11600.00
13	4208.11	125.27	0.451	0.50	(0.50)	1.00	27870.7	10500.00
14	3686.50	134.23	0.440	0.50	(0.50)	1.00	29001.0	10710.00
15	3079.50	146.58	0.425	0.50	(0.50)	1.00	30024.8	10700.00
16	2649.64	155.94	0.413	0.50	(0.50)	1.00	30698.5	10400.00
17	2296.99	164.19	0.403	0.50	(0.50)	1.00	31188.4	10200.00
18	1901.26	178.29	0.386	0.50	(0.50)	1.00	31917.9	10300.00
19	1742.48	184.66	0.381	0.50	(0.50)	1.00	32047.5	10210.00
20	608.82	267.18	0.337	0.50	(0.50)	1.00	32916.6	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12527.00 = 97868.13 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	8764.47	43.27	0.733	0.50 (0.50)	0.99	10189.2	11801.00
2	8761.27	46.61	0.705	0.50 (0.50)	0.99	11066.1	11831.00
3	8724.59	54.45	0.650	0.50 (0.50)	0.99	13043.9	11500.00
4	8671.34	60.05	0.617	0.50 (0.50)	0.99	14807.3	11701.00
5	8575.00	66.19	0.596	0.50 (0.50)	0.99	16728.7	11000.00
6	8377.64	82.32	0.540	0.50 (0.50)	0.99	23099.8	12500.00
7	8366.83	83.04	0.538	0.50 (0.50)	0.99	23400.2	11330.00
8	8218.32	88.36	0.520	0.50 (0.50)	0.99	25784.2	10900.00
9	8097.74	91.62	0.511	0.50 (0.50)	0.99	27184.1	10830.00
10	7836.98	96.58	0.502	0.50 (0.50)	0.99	29035.2	11130.00
11	7573.80	101.00	0.493	0.50 (0.50)	0.99	30446.1	12300.00
12	7408.63	103.75	0.488	0.50 (0.50)	0.99	31417.3	12330.00
13	7177.69	107.52	0.481	0.50 (0.50)	0.99	32707.8	11620.00
14	6872.25	112.52	0.471	0.50 (0.50)	0.99	34345.6	10600.00
15	6819.67	113.52	0.469	0.50 (0.50)	0.99	34675.6	12410.00
16	6735.43	115.06	0.466	0.50 (0.50)	0.99	35164.5	11600.00
17	6145.43	122.39	0.454	0.50 (0.50)	0.99	37233.5	12400.00
18	5980.02	124.27	0.452	0.50 (0.50)	0.99	37724.2	12211.00
19	5888.70	125.27	0.451	0.50 (0.50)	0.99	37981.1	10500.00
20	5313.35	132.90	0.441	0.50 (0.50)	0.99	39539.7	12201.00
21	5209.88	134.23	0.440	0.50 (0.50)	0.99	39789.6	10710.00
22	4715.07	141.46	0.431	0.50 (0.50)	0.99	40830.3	12111.00
23	4371.41	146.58	0.425	0.50 (0.50)	0.99	41576.8	10700.00
24	4336.52	147.13	0.424	0.50 (0.50)	0.99	41650.4	12231.00
25	3812.19	155.77	0.413	0.50 (0.50)	0.99	42753.2	12261.00
26	3801.75	155.94	0.413	0.50 (0.50)	0.99	42772.9	10400.00
27	3747.77	156.90	0.412	0.50 (0.50)	0.99	42868.1	12101.10
28	3352.08	164.19	0.403	0.50 (0.50)	0.99	43564.4	10200.00
29	2794.46	178.29	0.386	0.50 (0.50)	0.99	44802.3	10300.00
30	2567.05	184.54	0.382	0.50 (0.50)	0.99	45154.5	12010.00
31	2562.70	184.66	0.381	0.50 (0.50)	0.99	45157.8	10210.00
32	2105.15	203.48	0.371	0.50 (0.50)	0.99	45482.9	12000.00
33	1172.06	267.18	0.337	0.50 (0.50)	0.99	46153.7	10100.00

TOTAL AREA (ACRES) = 46153.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 8764.47 Tc (MIN.) = 43.268
EFFECTIVE AREA (ACRES) = 10189.25 AREA-AVERAGED Fm (INCH/HR) = 0.50
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 46153.7
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12527.00 = 97868.13 FEET.

FLOW PROCESS FROM NODE 12527.00 TO NODE 11929.00 IS CODE = 51

>>>> COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>> TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 347.47 DOWNSTREAM (FEET) = 341.63
CHANNEL LENGTH THRU SUBAREA (FEET) = 532.38 CHANNEL SLOPE = 0.0110
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.728

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	14.37	0.50	0.987	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.987
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 8765.98
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 14.03
AVERAGE FLOW DEPTH (FEET) = 14.43 TRAVEL TIME (MIN.) = 0.63
Tc (MIN.) = 43.90
SUBAREA AREA (ACRES) = 14.37 SUBAREA RUNOFF (CFS) = 3.03
EFFECTIVE AREA (ACRES) = 10203.62 AREA-AVERAGED Fm (INCH/HR) = 0.50
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 46168.0 PEAK FLOW RATE (CFS) = 8764.47
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 14.43 FLOW VELOCITY (FEET/SEC.) = 14.03
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 11

>>>> CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	8764.47	43.90	0.728	0.50 (0.50)	0.99	10203.6	11801.00
2	8761.27	47.24	0.700	0.50 (0.50)	0.99	11080.5	11831.00
3	8724.59	55.08	0.646	0.50 (0.50)	0.99	13058.3	11500.00
4	8671.34	60.69	0.615	0.50 (0.50)	0.99	14821.7	11701.00
5	8575.00	66.82	0.594	0.50 (0.50)	0.99	16743.1	11000.00
6	8377.64	82.96	0.538	0.50 (0.50)	0.99	23114.1	12500.00
7	8366.83	83.68	0.536	0.50 (0.50)	0.99	23414.6	11330.00
8	8218.32	89.00	0.517	0.50 (0.50)	0.99	25798.5	10900.00
9	8097.74	92.27	0.510	0.50 (0.50)	0.99	27198.5	10830.00
10	7836.98	97.23	0.500	0.50 (0.50)	0.99	29049.6	11130.00
11	7573.80	101.65	0.492	0.50 (0.50)	0.99	30460.5	12300.00
12	7408.63	104.41	0.487	0.50 (0.50)	0.99	31431.6	12330.00

13	7177.69	108.18	0.479	0.50 (0.50)	0.99	32722.1	11620.00
14	6872.25	113.19	0.470	0.50 (0.50)	0.99	34359.9	10600.00
15	6819.67	114.19	0.468	0.50 (0.50)	0.99	34690.0	12410.00
16	6735.43	115.74	0.465	0.50 (0.50)	0.99	35178.9	11600.00
17	6145.43	123.08	0.453	0.50 (0.50)	0.99	37247.9	12400.00
18	5980.02	124.96	0.451	0.50 (0.50)	0.99	37738.5	12211.00
19	5888.70	125.97	0.450	0.50 (0.50)	0.99	37995.4	10500.00
20	5313.35	133.62	0.440	0.50 (0.50)	0.99	39554.1	12201.00
21	5209.88	134.95	0.439	0.50 (0.50)	0.99	39804.0	10710.00
22	4715.07	142.20	0.430	0.50 (0.50)	0.99	40844.7	12111.00
23	4371.41	147.34	0.424	0.50 (0.50)	0.99	41591.2	10700.00
24	4336.52	147.88	0.423	0.50 (0.50)	0.99	41664.8	12231.00
25	3812.19	156.55	0.413	0.50 (0.50)	0.99	42767.6	12261.00
26	3801.75	156.72	0.412	0.50 (0.50)	0.99	42787.3	10400.00
27	3747.77	157.68	0.411	0.50 (0.50)	0.99	42882.5	12101.10
28	3352.08	164.99	0.402	0.50 (0.50)	0.99	43578.7	10200.00
29	2794.46	179.13	0.385	0.50 (0.50)	0.99	44816.7	10300.00
30	2567.05	185.40	0.381	0.50 (0.50)	0.99	45168.9	12010.00
31	2562.70	185.52	0.381	0.50 (0.50)	0.99	45172.2	10210.00
32	2105.15	204.39	0.371	0.50 (0.50)	0.99	45497.3	12000.00
33	1172.06	268.23	0.336	0.50 (0.50)	0.99	46168.0	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	458.97	44.33	0.724	0.50 (0.50)	1.00	1850.2	40130.00
2	450.13	46.71	0.704	0.50 (0.50)	1.00	1953.8	40100.00
3	290.20	91.13	0.512	0.50 (0.50)	1.00	3314.7	11910.00
4	275.63	92.76	0.509	0.50 (0.50)	1.00	3327.6	11900.00

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11929.00 = 31223.27 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9223.45	43.90	0.728	0.50 (0.50)	0.99	12036.0	11801.00
2	9223.04	44.33	0.724	0.50 (0.50)	0.99	12165.8	40130.00
3	9211.91	46.71	0.704	0.50 (0.50)	0.99	12895.3	40100.00
4	9209.49	47.24	0.700	0.50 (0.50)	0.99	13050.5	11831.00
5	9144.58	55.08	0.646	0.50 (0.50)	0.99	15268.5	11500.00
6	9071.16	60.69	0.615	0.50 (0.50)	0.99	17203.6	11701.00
7	8952.72	66.82	0.594	0.50 (0.50)	0.99	19313.0	11000.00
8	8697.25	82.96	0.538	0.50 (0.50)	0.99	26178.6	12500.00
9	8683.84	83.68	0.536	0.50 (0.50)	0.99	26501.1	11330.00
10	8516.19	89.00	0.517	0.50 (0.50)	0.99	29048.0	10900.00
11	8429.94	91.13	0.512	0.50 (0.50)	0.99	30025.6	11910.00
12	8377.76	92.27	0.510	0.50 (0.50)	0.99	30522.2	10830.00
13	8347.65	92.76	0.509	0.50 (0.50)	0.99	30708.7	11900.00
14	7879.54	97.23	0.500	0.50 (0.50)	0.99	32377.3	11130.00
15	7613.95	101.65	0.492	0.50 (0.50)	0.99	33788.1	12300.00
16	7448.35	104.41	0.487	0.50 (0.50)	0.99	34759.3	12330.00
17	7216.82	108.18	0.479	0.50 (0.50)	0.99	36049.8	11620.00
18	6910.61	113.19	0.470	0.50 (0.50)	0.99	37687.6	10600.00
19	6857.87	114.19	0.468	0.50 (0.50)	0.99	38017.6	12410.00
20	6773.39	115.74	0.465	0.50 (0.50)	0.99	38506.5	11600.00
21	6182.43	123.08	0.453	0.50 (0.50)	0.99	40575.5	12400.00
22	6016.83	124.96	0.451	0.50 (0.50)	0.99	41066.2	12211.00
23	5925.41	125.97	0.450	0.50 (0.50)	0.99	41323.1	10500.00

24	5349.30	133.62	0.440	0.50 (0.50)	0.99	42881.7	12201.00
25	5245.70	134.95	0.439	0.50 (0.50)	0.99	43131.6	10710.00
26	4750.17	142.20	0.430	0.50 (0.50)	0.99	44172.4	12111.00
27	4406.00	147.34	0.424	0.50 (0.50)	0.99	44918.8	10700.00
28	4371.05	147.88	0.423	0.50 (0.50)	0.99	44992.4	12231.00
29	3845.87	156.55	0.413	0.50 (0.50)	0.99	46095.3	12261.00
30	3835.41	156.72	0.412	0.50 (0.50)	0.99	46114.9	10400.00
31	3781.33	157.68	0.411	0.50 (0.50)	0.99	46210.1	12101.10
32	3384.92	164.99	0.402	0.50 (0.50)	0.99	46906.4	10200.00
33	2825.89	179.13	0.385	0.50 (0.50)	0.99	48144.3	10300.00
34	2598.15	185.40	0.381	0.50 (0.50)	0.99	48496.5	12010.00
35	2593.79	185.52	0.381	0.50 (0.50)	0.99	48499.8	10210.00
36	2135.41	204.39	0.371	0.50 (0.50)	0.99	48824.9	12000.00
37	1199.48	268.23	0.336	0.50 (0.50)	0.99	49495.7	10100.00

TOTAL AREA (ACRES) = 49495.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 9223.45 Tc (MIN.) = 43.901
EFFECTIVE AREA (ACRES) = 12036.02 AREA-AVERAGED Fm (INCH/HR) = 0.50
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 49495.7
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 49495.7 TC (MIN.) = 43.90
EFFECTIVE AREA (ACRES) = 12036.02 AREA-AVERAGED Fm (INCH/HR) = 0.50
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.993
PEAK FLOW RATE (CFS) = 9223.45

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9223.45	43.90	0.728	0.50 (0.50)	0.99	12036.0	11801.00
2	9223.04	44.33	0.724	0.50 (0.50)	0.99	12165.8	40130.00
3	9211.91	46.71	0.704	0.50 (0.50)	0.99	12895.3	40100.00
4	9209.49	47.24	0.700	0.50 (0.50)	0.99	13050.5	11831.00
5	9144.58	55.08	0.646	0.50 (0.50)	0.99	15268.5	11500.00
6	9071.16	60.69	0.615	0.50 (0.50)	0.99	17203.6	11701.00
7	8952.72	66.82	0.594	0.50 (0.50)	0.99	19313.0	11000.00
8	8697.25	82.96	0.538	0.50 (0.50)	0.99	26178.6	12500.00
9	8683.84	83.68	0.536	0.50 (0.50)	0.99	26501.1	11330.00
10	8516.19	89.00	0.517	0.50 (0.50)	0.99	29048.0	10900.00
11	8429.94	91.13	0.512	0.50 (0.50)	0.99	30025.6	11910.00
12	8377.76	92.27	0.510	0.50 (0.50)	0.99	30522.2	10830.00
13	8347.65	92.76	0.509	0.50 (0.50)	0.99	30708.7	11900.00
14	7879.54	97.23	0.500	0.50 (0.50)	0.99	32377.3	11130.00
15	7613.95	101.65	0.492	0.50 (0.50)	0.99	33788.1	12300.00
16	7448.35	104.41	0.487	0.50 (0.50)	0.99	34759.3	12330.00
17	7216.82	108.18	0.479	0.50 (0.50)	0.99	36049.8	11620.00
18	6910.61	113.19	0.470	0.50 (0.50)	0.99	37687.6	10600.00
19	6857.87	114.19	0.468	0.50 (0.50)	0.99	38017.6	12410.00
20	6773.39	115.74	0.465	0.50 (0.50)	0.99	38506.5	11600.00
21	6182.43	123.08	0.453	0.50 (0.50)	0.99	40575.5	12400.00
22	6016.83	124.96	0.451	0.50 (0.50)	0.99	41066.2	12211.00
23	5925.41	125.97	0.450	0.50 (0.50)	0.99	41323.1	10500.00
24	5349.30	133.62	0.440	0.50 (0.50)	0.99	42881.7	12201.00
25	5245.70	134.95	0.439	0.50 (0.50)	0.99	43131.6	10710.00
26	4750.17	142.20	0.430	0.50 (0.50)	0.99	44172.4	12111.00

27	4406.00	147.34	0.424	0.50	(0.50)	0.99	44918.8	10700.00
28	4371.05	147.88	0.423	0.50	(0.50)	0.99	44992.4	12231.00
29	3845.87	156.55	0.413	0.50	(0.50)	0.99	46095.3	12261.00
30	3835.41	156.72	0.412	0.50	(0.50)	0.99	46114.9	10400.00
31	3781.33	157.68	0.411	0.50	(0.50)	0.99	46210.1	12101.10
32	3384.92	164.99	0.402	0.50	(0.50)	0.99	46906.4	10200.00
33	2825.89	179.13	0.385	0.50	(0.50)	0.99	48144.3	10300.00
34	2598.15	185.40	0.381	0.50	(0.50)	0.99	48496.5	12010.00
35	2593.79	185.52	0.381	0.50	(0.50)	0.99	48499.8	10210.00
36	2135.41	204.39	0.371	0.50	(0.50)	0.99	48824.9	12000.00
37	1199.48	268.23	0.336	0.50	(0.50)	0.99	49495.7	10100.00

=====
=====
END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 126 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 5-YR EV FEB 2023 ROKAMOTO *

FILE NAME: RU05EV26.DAT
TIME/DATE OF STUDY: 08:56 02/08/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 5.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 2.739
- 2) 10.00; 1.815
- 3) 15.00; 1.325
- 4) 20.00; 1.135
- 5) 25.00; 0.989
- 6) 30.00; 0.885
- 7) 40.00; 0.759
- 8) 50.00; 0.676
- 9) 60.00; 0.615
- 10) 90.00; 0.513
- 11) 120.00; 0.455
- 12) 180.00; 0.383
- 13) 360.00; 0.284
- 14) 1200.00; 0.125

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU05EV19.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9223.45	43.90	0.50 (0.50)	0.99	12036.0	11801.00
2	9144.58	55.08	0.50 (0.50)	0.99	15268.5	11500.00
3	9071.16	60.69	0.50 (0.50)	0.99	17203.6	11701.00
4	8952.72	66.82	0.50 (0.50)	0.99	19313.0	11000.00
5	8697.25	82.96	0.50 (0.50)	0.99	26178.6	12500.00
6	8516.19	89.00	0.50 (0.50)	0.99	29048.0	10900.00
7	7879.54	97.23	0.50 (0.50)	0.99	32377.3	11130.00
8	7613.95	101.65	0.50 (0.50)	0.99	33788.1	12300.00
9	7216.82	108.18	0.50 (0.50)	0.99	36049.8	11620.00
10	6910.61	113.19	0.50 (0.50)	0.99	37687.6	10600.00
11	6182.43	123.08	0.50 (0.50)	0.99	40575.5	12400.00
12	5349.30	133.62	0.50 (0.50)	0.99	42881.7	12201.00
13	4750.17	142.20	0.50 (0.50)	0.99	44172.4	12111.00
14	4406.00	147.34	0.50 (0.50)	0.99	44918.8	10700.00
15	3845.87	156.55	0.50 (0.50)	0.99	46095.3	12261.00
16	3384.92	164.99	0.50 (0.50)	0.99	46906.4	10200.00
17	2825.89	179.13	0.50 (0.50)	0.99	48144.3	10300.00
18	2598.15	185.40	0.50 (0.50)	0.99	48496.5	12010.00
19	2135.41	204.39	0.50 (0.50)	0.99	48824.9	12000.00
20	1199.48	268.23	0.50 (0.50)	0.99	49495.7	10100.00
TOTAL AREA (ACRES) =						49495.7

FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9223.45	43.90	0.50 (0.50)	0.99	12036.0	11801.00
2	9144.58	55.08	0.50 (0.50)	0.99	15268.5	11500.00
3	9071.16	60.69	0.50 (0.50)	0.99	17203.6	11701.00
4	8952.72	66.82	0.50 (0.50)	0.99	19313.0	11000.00
5	8697.25	82.96	0.50 (0.50)	0.99	26178.6	12500.00
6	8516.19	89.00	0.50 (0.50)	0.99	29048.0	10900.00
7	7879.54	97.23	0.50 (0.50)	0.99	32377.3	11130.00
8	7613.95	101.65	0.50 (0.50)	0.99	33788.1	12300.00
9	7216.82	108.18	0.50 (0.50)	0.99	36049.8	11620.00
10	6910.61	113.19	0.50 (0.50)	0.99	37687.6	10600.00
11	6182.43	123.08	0.50 (0.50)	0.99	40575.5	12400.00
12	5349.30	133.62	0.50 (0.50)	0.99	42881.7	12201.00
13	4750.17	142.20	0.50 (0.50)	0.99	44172.4	12111.00

14	4406.00	147.34	0.50	(0.50)	0.99	44918.8	10700.00
15	3845.87	156.55	0.50	(0.50)	0.99	46095.3	12261.00
16	3384.92	164.99	0.50	(0.50)	0.99	46906.4	10200.00
17	2825.89	179.13	0.50	(0.50)	0.99	48144.3	10300.00
18	2598.15	185.40	0.50	(0.50)	0.99	48496.5	12010.00
19	2135.41	204.39	0.50	(0.50)	0.99	48824.9	12000.00
20	1199.48	268.23	0.50	(0.50)	0.99	49495.7	10100.00
TOTAL AREA (ACRES) =							49495.7

FLOW PROCESS FROM NODE 11929.00 TO NODE 12601.00 IS CODE = 51

 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

 ELEVATION DATA: UPSTREAM (FEET) = 341.63 DOWNSTREAM (FEET) = 325.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1467.93 CHANNEL SLOPE = 0.0113
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.715

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.40	0.50	1.000	-
USER-DEFINED	-	0.50	0.50	1.000	-
USER-DEFINED	-	0.90	0.50	1.000	-
USER-DEFINED	-	0.50	0.50	1.000	-
USER-DEFINED	-	11.50	0.50	1.000	-
USER-DEFINED	-	0.30	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 9224.81
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 17.84
 AVERAGE FLOW DEPTH (FEET) = 13.13 TRAVEL TIME (MIN.) = 1.37
 Tc (MIN.) = 45.27
 SUBAREA AREA (ACRES) = 14.10 SUBAREA RUNOFF (CFS) = 2.73
 EFFECTIVE AREA (ACRES) = 12050.12 AREA-AVERAGED Fm (INCH/HR) = 0.50
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 49509.8 PEAK FLOW RATE (CFS) = 9223.45
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 13.13 FLOW VELOCITY (FEET/SEC.) = 17.85
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9223.45	45.27	0.715	0.50 (0.50)	0.99	12050.1	11801.00
2	9144.58	56.46	0.637	0.50 (0.50)	0.99	15282.6	11500.00
3	9071.16	62.06	0.608	0.50 (0.50)	0.99	17217.7	11701.00
4	8952.72	68.21	0.587	0.50 (0.50)	0.99	19327.1	11000.00
5	8697.25	84.35	0.532	0.50 (0.50)	0.99	26192.7	12500.00
6	8516.19	90.40	0.512	0.50 (0.50)	0.99	29062.1	10900.00
7	7879.54	98.65	0.496	0.50 (0.50)	0.99	32391.4	11130.00
8	7613.95	103.09	0.488	0.50 (0.50)	0.99	33802.2	12300.00
9	7216.82	109.64	0.475	0.50 (0.50)	0.99	36063.9	11620.00
10	6910.61	114.66	0.465	0.50 (0.50)	0.99	37701.7	10600.00

11	6182.43	124.59	0.449	0.50 (0.50)	0.99	40589.6	12400.00
12	5349.30	135.19	0.437	0.50 (0.50)	0.99	42895.8	12201.00
13	4750.17	143.82	0.426	0.50 (0.50)	0.99	44186.5	12111.00
14	4406.00	148.99	0.420	0.50 (0.50)	0.99	44932.9	10700.00
15	3845.87	158.25	0.409	0.50 (0.50)	0.99	46109.4	12261.00
16	3384.92	166.76	0.399	0.50 (0.50)	0.99	46920.5	10200.00
17	2825.89	180.98	0.382	0.50 (0.50)	0.99	48158.4	10300.00
18	2598.15	187.28	0.379	0.50 (0.50)	0.99	48510.6	12010.00
19	2135.41	206.36	0.369	0.50 (0.50)	0.99	48839.0	12000.00
20	1199.48	270.51	0.333	0.50 (0.50)	0.99	49509.8	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 9223.45 Tc (MIN.) = 45.27
 AREA-AVERAGED Fm (INCH/HR) = 0.50 AREA-AVERAGED Fp (INCH/HR) = 0.50
 AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA (ACRES) = 12050.12

FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 15.1

 >>>>DEFINE MEMORY BANK # 2 <<<<<

 PEAK FLOWRATE TABLE FILE NAME: 3005EVRL.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	32.19	18.50	0.50 (0.49)	0.98	51.1	600.00
TOTAL AREA (ACRES) = 51.1						

FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 11

 >>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

 ** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9223.45	45.27	0.715	0.50 (0.50)	0.99	12050.1	11801.00
2	9144.58	56.46	0.637	0.50 (0.50)	0.99	15282.6	11500.00
3	9071.16	62.06	0.608	0.50 (0.50)	0.99	17217.7	11701.00
4	8952.72	68.21	0.587	0.50 (0.50)	0.99	19327.1	11000.00
5	8697.25	84.35	0.532	0.50 (0.50)	0.99	26192.7	12500.00
6	8516.19	90.40	0.512	0.50 (0.50)	0.99	29062.1	10900.00
7	7879.54	98.65	0.496	0.50 (0.50)	0.99	32391.4	11130.00
8	7613.95	103.09	0.488	0.50 (0.50)	0.99	33802.2	12300.00
9	7216.82	109.64	0.475	0.50 (0.50)	0.99	36063.9	11620.00
10	6910.61	114.66	0.465	0.50 (0.50)	0.99	37701.7	10600.00
11	6182.43	124.59	0.449	0.50 (0.50)	0.99	40589.6	12400.00
12	5349.30	135.19	0.437	0.50 (0.50)	0.99	42895.8	12201.00
13	4750.17	143.82	0.426	0.50 (0.50)	0.99	44186.5	12111.00
14	4406.00	148.99	0.420	0.50 (0.50)	0.99	44932.9	10700.00
15	3845.87	158.25	0.409	0.50 (0.50)	0.99	46109.4	12261.00
16	3384.92	166.76	0.399	0.50 (0.50)	0.99	46920.5	10200.00
17	2825.89	180.98	0.382	0.50 (0.50)	0.99	48158.4	10300.00
18	2598.15	187.28	0.379	0.50 (0.50)	0.99	48510.6	12010.00
19	2135.41	206.36	0.369	0.50 (0.50)	0.99	48839.0	12000.00
20	1199.48	270.51	0.333	0.50 (0.50)	0.99	49509.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	32.19	18.50	1.192	0.50(0.49)	0.98	51.1	600.00

LONGEST FLOWPATH FROM NODE 600.00 TO NODE 12601.00 = 4850.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9255.63	18.50	1.192	0.50(0.50)	0.99	4975.6	600.00
2	9233.71	45.27	0.715	0.50(0.50)	0.99	12101.2	11801.00
3	9151.22	56.46	0.637	0.50(0.50)	0.99	15333.7	11500.00
4	9076.49	62.06	0.608	0.50(0.50)	0.99	17268.8	11701.00
5	8957.09	68.21	0.587	0.50(0.50)	0.99	19378.2	11000.00
6	8699.10	84.35	0.532	0.50(0.50)	0.99	26243.8	12500.00
7	8517.11	90.40	0.512	0.50(0.50)	0.99	29113.2	10900.00
8	7879.91	98.65	0.496	0.50(0.50)	0.99	32442.5	11130.00
9	7614.31	103.09	0.488	0.50(0.50)	0.99	33853.3	12300.00
10	7217.18	109.64	0.475	0.50(0.50)	0.99	36115.0	11620.00
11	6910.96	114.66	0.465	0.50(0.50)	0.99	37752.8	10600.00
12	6182.76	124.59	0.449	0.50(0.50)	0.99	40640.7	12400.00
13	5349.63	135.19	0.437	0.50(0.50)	0.99	42946.9	12201.00
14	4750.48	143.82	0.426	0.50(0.50)	0.99	44237.6	12111.00
15	4406.31	148.99	0.420	0.50(0.50)	0.99	44984.0	10700.00
16	3846.17	158.25	0.409	0.50(0.50)	0.99	46160.5	12261.00
17	3385.21	166.76	0.399	0.50(0.50)	0.99	46971.6	10200.00
18	2826.17	180.98	0.382	0.50(0.50)	0.99	48209.5	10300.00
19	2598.44	187.28	0.379	0.50(0.50)	0.99	48561.7	12010.00
20	2135.68	206.36	0.369	0.50(0.50)	0.99	48890.1	12000.00
21	1199.73	270.51	0.333	0.50(0.50)	0.99	49560.9	10100.00

TOTAL AREA (ACRES) = 49560.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
 PEAK FLOW RATE(CFS) = 9255.63 Tc(MIN.) = 18.501
 EFFECTIVE AREA(ACRES) = 4975.60 AREA-AVERAGED Fm(INCH/HR) = 0.50
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 49560.9
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

 FLOW PROCESS FROM NODE 12601.00 TO NODE 12603.00 IS CODE = 51

 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

 ELEVATION DATA: UPSTREAM(FEET) = 325.00 DOWNSTREAM(FEET) = 310.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1690.00 CHANNEL SLOPE = 0.0089
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
 CHANNEL FLOW THRU SUBAREA(CFS) = 9255.63
 FLOW VELOCITY(FEET/SEC.) = 16.30 FLOW DEPTH(FEET) = 13.76
 TRAVEL TIME(MIN.) = 1.73 Tc(MIN.) = 20.23
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.45 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9255.63	20.23	1.128	0.50(0.50)	0.99	4975.6	600.00

2	9233.71	47.00	0.701	0.50(0.50)	0.99	12101.2	11801.00
3	9151.22	58.19	0.626	0.50(0.50)	0.99	15333.7	11500.00
4	9076.49	63.80	0.602	0.50(0.50)	0.99	17268.8	11701.00
5	8957.09	69.95	0.581	0.50(0.50)	0.99	19378.2	11000.00
6	8699.10	86.11	0.526	0.50(0.50)	0.99	26243.8	12500.00
7	8517.11	92.16	0.509	0.50(0.50)	0.99	29113.2	10900.00
8	7879.91	100.45	0.493	0.50(0.50)	0.99	32442.5	11130.00
9	7614.31	104.91	0.484	0.50(0.50)	0.99	33853.3	12300.00
10	7217.18	111.48	0.471	0.50(0.50)	0.99	36115.0	11620.00
11	6910.96	116.52	0.462	0.50(0.50)	0.99	37752.8	10600.00
12	6182.76	126.50	0.447	0.50(0.50)	0.99	40640.7	12400.00
13	5349.63	137.17	0.434	0.50(0.50)	0.99	42946.9	12201.00
14	4750.48	145.86	0.424	0.50(0.50)	0.99	44237.6	12111.00
15	4406.31	151.07	0.418	0.50(0.50)	0.99	44984.0	10700.00
16	3846.17	160.41	0.407	0.50(0.50)	0.99	46160.5	12261.00
17	3385.21	168.98	0.396	0.50(0.50)	0.99	46971.6	10200.00
18	2826.17	183.30	0.381	0.50(0.50)	0.99	48209.5	10300.00
19	2598.44	189.65	0.378	0.50(0.50)	0.99	48561.7	12010.00
20	2135.68	208.86	0.367	0.50(0.50)	0.99	48890.1	12000.00
21	1199.73	273.39	0.332	0.50(0.50)	0.99	49560.9	10100.00

NEW PEAK FLOW DATA ARE:
 PEAK FLOW RATE(CFS) = 9255.63 Tc(MIN.) = 20.23
 AREA-AVERAGED Fm(INCH/HR) = 0.50 AREA-AVERAGED Fp(INCH/HR) = 0.50
 AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 4975.60

 FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

 FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

 PEAK FLOWRATE TABLE FILE NAME: 4E05EVRL.DNA
 MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	211.44	10.04	0.50(0.26)	0.52	148.5	800.00
2	178.48	13.84	0.50(0.29)	0.57	167.9	818.00
3	161.90	15.20	0.50(0.29)	0.58	171.0	810.00

TOTAL AREA (ACRES) = 171.0

 FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9255.63	20.23	1.128	0.50(0.50)	0.99	4975.6	600.00
2	9233.71	47.00	0.701	0.50(0.50)	0.99	12101.2	11801.00
3	9151.22	58.19	0.626	0.50(0.50)	0.99	15333.7	11500.00
4	9076.49	63.80	0.602	0.50(0.50)	0.99	17268.8	11701.00

5	8957.09	69.95	0.581	0.50(0.50)	0.99	19378.2	11000.00
6	8699.10	86.11	0.526	0.50(0.50)	0.99	26243.8	12500.00
7	8517.11	92.16	0.509	0.50(0.50)	0.99	29113.2	10900.00
8	7879.91	100.45	0.493	0.50(0.50)	0.99	32442.5	11130.00
9	7614.31	104.91	0.484	0.50(0.50)	0.99	33853.3	12300.00
10	7217.18	111.48	0.471	0.50(0.50)	0.99	36115.0	11620.00
11	6910.96	116.52	0.462	0.50(0.50)	0.99	37752.8	10600.00
12	6182.76	126.50	0.447	0.50(0.50)	0.99	40640.7	12400.00
13	5349.63	137.17	0.434	0.50(0.50)	0.99	42946.9	12201.00
14	4750.48	145.86	0.424	0.50(0.50)	0.99	44237.6	12111.00
15	4406.31	151.07	0.418	0.50(0.50)	0.99	44984.0	10700.00
16	3846.17	160.41	0.407	0.50(0.50)	0.99	46160.5	12261.00
17	3385.21	168.98	0.396	0.50(0.50)	0.99	46971.6	10200.00
18	2826.17	183.30	0.381	0.50(0.50)	0.99	48209.5	10300.00
19	2598.44	189.65	0.378	0.50(0.50)	0.99	48561.7	12010.00
20	2135.68	208.86	0.367	0.50(0.50)	0.99	48890.1	12000.00
21	1199.73	273.39	0.332	0.50(0.50)	0.99	49560.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.45 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	211.44	10.04	1.811	0.50(0.26)	0.52	148.5	800.00
2	178.48	13.84	1.439	0.50(0.29)	0.57	167.9	818.00
3	161.90	15.20	1.317	0.50(0.29)	0.58	171.0	810.00

LONGEST FLOWPATH FROM NODE 810.00 TO NODE 12603.00 = 3814.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9467.07	10.04	1.811	0.50(0.48)	0.97	2617.8	800.00
2	9434.11	13.84	1.439	0.50(0.49)	0.97	3571.1	818.00
3	9198.66	15.20	1.317	0.50(0.49)	0.98	3908.9	810.00
4	9387.72	20.23	1.128	0.50(0.49)	0.98	5146.6	600.00
5	9298.44	47.00	0.701	0.50(0.49)	0.99	12272.2	11801.00
6	9204.16	58.19	0.626	0.50(0.49)	0.99	15504.7	11500.00
7	9125.65	63.80	0.602	0.50(0.49)	0.99	17439.8	11701.00
8	9002.96	69.95	0.581	0.50(0.50)	0.99	19549.2	11000.00
9	8736.31	86.11	0.526	0.50(0.50)	0.99	26414.8	12500.00
10	8551.58	92.16	0.509	0.50(0.50)	0.99	29284.2	10900.00
11	7912.53	100.45	0.493	0.50(0.50)	0.99	32613.5	11130.00
12	7646.36	104.91	0.484	0.50(0.50)	0.99	34024.3	12300.00
13	7248.38	111.48	0.471	0.50(0.50)	0.99	36286.0	11620.00
14	6941.52	116.52	0.462	0.50(0.50)	0.99	37923.8	10600.00
15	6212.36	126.50	0.447	0.50(0.50)	0.99	40811.7	12400.00
16	5378.38	137.17	0.434	0.50(0.50)	0.99	43117.9	12201.00
17	4778.55	145.86	0.424	0.50(0.50)	0.99	44408.6	12111.00
18	4433.96	151.07	0.418	0.50(0.50)	0.99	45155.0	10700.00
19	3873.08	160.41	0.407	0.50(0.50)	0.99	46331.5	12261.00
20	3411.44	168.98	0.396	0.50(0.50)	0.99	47142.6	10200.00
21	2851.40	183.30	0.381	0.50(0.50)	0.99	48380.5	10300.00
22	2623.44	189.65	0.378	0.50(0.50)	0.99	48732.7	12010.00
23	2159.98	208.86	0.367	0.50(0.50)	0.99	49061.1	12000.00
24	1221.69	273.39	0.332	0.50(0.50)	0.99	49731.9	10100.00

TOTAL AREA (ACRES) = 49731.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
 PEAK FLOW RATE (CFS) = 9467.07 Tc (MIN.) = 10.040

EFFECTIVE AREA (ACRES) = 2617.84 AREA-AVERAGED Fm (INCH/HR) = 0.48
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 49731.9
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.45 FEET.

 FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 10.04
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.811
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	1.30	0.50	1.000	-
USER-DEFINED	-	1.30	0.50	0.850	-
USER-DEFINED	-	1.40	0.50	0.100	-
USER-DEFINED	-	1.70	0.50	0.900	-
USER-DEFINED	-	12.40	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.911
 SUBAREA AREA (ACRES) = 18.30 SUBAREA RUNOFF (CFS) = 22.32
 EFFECTIVE AREA (ACRES) = 2636.14 AREA-AVERAGED Fm (INCH/HR) = 0.48
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.97
 TOTAL AREA (ACRES) = 49750.2 PEAK FLOW RATE (CFS) = 9467.07
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 10.04
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.811
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	26.90	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 26.90 SUBAREA RUNOFF (CFS) = 31.74
 EFFECTIVE AREA (ACRES) = 2663.04 AREA-AVERAGED Fm (INCH/HR) = 0.48
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.97
 TOTAL AREA (ACRES) = 49777.1 PEAK FLOW RATE (CFS) = 9467.07
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 10.04
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.811
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	26.90	0.50	1.000	-


```

USER-DEFINED      -      0.50      0.50      1.000      -
USER-DEFINED      -      0.40      0.50      1.000      -
USER-DEFINED      -      0.40      0.50      1.000      -
USER-DEFINED      -      0.60      0.50      1.000      -
USER-DEFINED      -      0.70      0.50      0.850      -
USER-DEFINED      -      0.70      0.50      1.000      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.968
SUBAREA AREA (ACRES) = 3.30      SUBAREA RUNOFF (CFS) = 3.94
EFFECTIVE AREA (ACRES) = 2666.34      AREA-AVERAGED Fm (INCH/HR) = 0.48
AREA-AVERAGED Fp (INCH/HR) = 0.50      AREA-AVERAGED Ap = 0.97
TOTAL AREA (ACRES) = 49780.4      PEAK FLOW RATE (CFS) = 9467.07
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

```

```

=====
MAINLINE Tc (MIN.) = 10.04
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.811
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/      SCS SOIL      AREA      Fp      Ap      SCS
LAND USE      GROUP      (ACRES)      (INCH/HR)      (DECIMAL)      CN
USER-DEFINED      -      1.00      0.50      1.000      -
USER-DEFINED      -      1.20      0.50      1.000      -
USER-DEFINED      -      1.70      0.50      0.900      -
USER-DEFINED      -      1.90      0.50      1.000      -
USER-DEFINED      -      2.10      0.50      0.900      -
USER-DEFINED      -      2.90      0.50      1.000      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.965
SUBAREA AREA (ACRES) = 10.80      SUBAREA RUNOFF (CFS) = 12.91
EFFECTIVE AREA (ACRES) = 2677.14      AREA-AVERAGED Fm (INCH/HR) = 0.48
AREA-AVERAGED Fp (INCH/HR) = 0.50      AREA-AVERAGED Ap = 0.97
TOTAL AREA (ACRES) = 49791.2      PEAK FLOW RATE (CFS) = 9467.07
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

```

```

=====
MAINLINE Tc (MIN.) = 10.04
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.811
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/      SCS SOIL      AREA      Fp      Ap      SCS
LAND USE      GROUP      (ACRES)      (INCH/HR)      (DECIMAL)      CN
USER-DEFINED      -      5.60      0.50      1.000      -
USER-DEFINED      -      9.00      0.50      1.000      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 14.60      SUBAREA RUNOFF (CFS) = 17.23
EFFECTIVE AREA (ACRES) = 2691.74      AREA-AVERAGED Fm (INCH/HR) = 0.48
AREA-AVERAGED Fp (INCH/HR) = 0.50      AREA-AVERAGED Ap = 0.97
TOTAL AREA (ACRES) = 49805.8      PEAK FLOW RATE (CFS) = 9467.07
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 12603.00 TO NODE 12605.00 IS CODE = 51
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM (FEET) = 310.00      DOWNSTREAM (FEET) = 305.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 885.00      CHANNEL SLOPE = 0.0056
CHANNEL BASE (FEET) = 0.00      "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030      MAXIMUM DEPTH (FEET) = 20.00
CHANNEL FLOW THRU SUBAREA (CFS) = 9467.07
FLOW VELOCITY (FEET/SEC.) = 13.84      FLOW DEPTH (FEET) = 15.10
TRAVEL TIME (MIN.) = 1.07      Tc (MIN.) = 11.11
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.00 = 102443.45 FEET.

```

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9467.07	11.11	1.707	0.50 (0.48)	0.97	2691.7	800.00
2	9434.11	14.90	1.334	0.50 (0.49)	0.97	3645.0	818.00
3	9198.66	16.27	1.277	0.50 (0.49)	0.98	3982.8	810.00
4	9387.72	21.30	1.097	0.50 (0.49)	0.98	5220.5	600.00
5	9298.44	48.07	0.692	0.50 (0.49)	0.99	12346.1	11801.00
6	9204.16	59.26	0.619	0.50 (0.49)	0.99	15578.6	11500.00
7	9125.65	64.88	0.598	0.50 (0.49)	0.99	17513.7	11701.00
8	9002.96	71.03	0.578	0.50 (0.50)	0.99	19623.1	11000.00
9	8736.31	87.20	0.523	0.50 (0.50)	0.99	26488.7	12500.00
10	8551.58	93.26	0.507	0.50 (0.50)	0.99	29358.1	10900.00
11	7912.53	101.57	0.491	0.50 (0.50)	0.99	32687.4	11130.00
12	7646.36	106.03	0.482	0.50 (0.50)	0.99	34098.2	12300.00
13	7248.38	112.62	0.469	0.50 (0.50)	0.99	36359.9	11620.00
14	6941.52	117.67	0.459	0.50 (0.50)	0.99	37997.7	10600.00
15	6212.36	127.69	0.446	0.50 (0.50)	0.99	40885.6	12400.00
16	5378.38	138.40	0.433	0.50 (0.50)	0.99	43191.8	12201.00
17	4778.55	147.12	0.422	0.50 (0.50)	0.99	44482.5	12111.00
18	4433.96	152.36	0.416	0.50 (0.50)	0.99	45228.9	10700.00
19	3873.08	161.74	0.405	0.50 (0.50)	0.99	46405.4	12261.00
20	3411.44	170.35	0.395	0.50 (0.50)	0.99	47216.5	10200.00
21	2851.40	184.74	0.380	0.50 (0.50)	0.99	48454.4	10300.00
22	2623.44	191.12	0.377	0.50 (0.50)	0.99	48806.6	12010.00
23	2159.98	210.40	0.366	0.50 (0.50)	0.99	49135.0	12000.00
24	1221.69	275.17	0.331	0.50 (0.50)	0.99	49805.8	10100.00

```

NEW PEAK FLOW DATA ARE:
PEAK FLOW RATE (CFS) = 9467.07      Tc (MIN.) = 11.11
AREA-AVERAGED Fm (INCH/HR) = 0.48      AREA-AVERAGED Fp (INCH/HR) = 0.50
AREA-AVERAGED Ap = 0.97      EFFECTIVE AREA (ACRES) = 2691.74

```

```

*****
FLOW PROCESS FROM NODE 12605.00 TO NODE 12605.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

```

```

=====
MAINLINE Tc (MIN.) = 11.11
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.707
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/      SCS SOIL      AREA      Fp      Ap      SCS
LAND USE      GROUP      (ACRES)      (INCH/HR)      (DECIMAL)      CN
USER-DEFINED      -      0.50      0.50      1.000      -

```

USER-DEFINED - 0.70 0.50 1.000 -
 USER-DEFINED - 1.30 0.50 0.850 -
 USER-DEFINED - 1.30 0.50 0.900 -
 USER-DEFINED - 1.90 0.50 1.000 -
 USER-DEFINED - 2.10 0.50 0.850 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.918
 SUBAREA AREA(ACRES) = 7.80 SUBAREA RUNOFF(CFS) = 8.76
 EFFECTIVE AREA(ACRES) = 2699.54 AREA-AVERAGED Fm(INCH/HR) = 0.48
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.97
 TOTAL AREA(ACRES) = 49813.6 PEAK FLOW RATE(CFS) = 9467.07
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12605.00 TO NODE 12605.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 11.11
 * 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.707

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	3.20	0.50	1.000	-
USER-DEFINED	-	3.50	0.50	1.000	-
USER-DEFINED	-	6.10	0.50	0.850	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.929
 SUBAREA AREA(ACRES) = 12.80 SUBAREA RUNOFF(CFS) = 14.31
 EFFECTIVE AREA(ACRES) = 2712.34 AREA-AVERAGED Fm(INCH/HR) = 0.48
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.97
 TOTAL AREA(ACRES) = 49826.4 PEAK FLOW RATE(CFS) = 9467.07
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12605.00 TO NODE 12606.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 305.00 DOWNSTREAM(FEET) = 286.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2159.00 CHANNEL SLOPE = 0.0088
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
 CHANNEL FLOW THRU SUBAREA(CFS) = 9467.07
 FLOW VELOCITY(FEET/SEC.) = 16.34 FLOW DEPTH(FEET) = 13.90
 TRAVEL TIME(MIN.) = 2.20 Tc(MIN.) = 13.31
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104602.45 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9467.07	13.31	1.491	0.50(0.48)	0.97	2712.3	800.00
2	9434.11	17.11	1.245	0.50(0.49)	0.97	3665.6	818.00
3	9198.66	18.49	1.192	0.50(0.49)	0.97	4003.4	810.00
4	9387.72	23.50	1.033	0.50(0.49)	0.98	5241.1	600.00
5	9298.44	50.28	0.674	0.50(0.49)	0.99	12366.7	11801.00
6	9204.16	61.48	0.610	0.50(0.49)	0.99	15599.2	11500.00

7	9125.65	67.10	0.591	0.50(0.49)	0.99	17534.3	11701.00
8	9002.96	73.26	0.570	0.50(0.50)	0.99	19643.8	11000.00
9	8736.31	89.44	0.515	0.50(0.50)	0.99	26509.3	12500.00
10	8551.58	95.51	0.502	0.50(0.50)	0.99	29378.7	10900.00
11	7912.53	103.87	0.486	0.50(0.50)	0.99	32708.0	11130.00
12	7646.36	108.36	0.478	0.50(0.50)	0.99	34118.8	12300.00
13	7248.38	114.98	0.465	0.50(0.50)	0.99	36380.5	11620.00
14	6941.52	120.05	0.455	0.50(0.50)	0.99	38018.3	10600.00
15	6212.36	130.14	0.443	0.50(0.50)	0.99	40906.2	12400.00
16	5378.38	140.94	0.430	0.50(0.50)	0.99	43212.4	12201.00
17	4778.55	149.74	0.419	0.50(0.50)	0.99	44503.1	12111.00
18	4433.96	155.02	0.413	0.50(0.50)	0.99	45249.5	10700.00
19	3873.08	164.49	0.402	0.50(0.50)	0.99	46426.0	12261.00
20	3411.44	173.20	0.391	0.50(0.50)	0.99	47237.1	10200.00
21	2851.40	187.72	0.379	0.50(0.50)	0.99	48475.0	10300.00
22	2623.44	194.15	0.375	0.50(0.50)	0.99	48827.2	12010.00
23	2159.98	213.59	0.365	0.50(0.50)	0.99	49155.6	12000.00
24	1221.69	278.84	0.329	0.50(0.50)	0.99	49826.4	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 9467.07 Tc(MIN.) = 13.31
 AREA-AVERAGED Fm(INCH/HR) = 0.48 AREA-AVERAGED Fp(INCH/HR) = 0.50
 AREA-AVERAGED Ap = 0.97 EFFECTIVE AREA(ACRES) = 2712.34

 FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<

PEAK FLOWRATE TABLE FILE NAME: 4F05EVRL.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	444.41	10.57	0.50(0.39)	0.78	360.1	940.00
2	444.42	10.77	0.50(0.39)	0.78	365.5	930.00
3	402.73	14.22	0.50(0.41)	0.81	450.0	910.00
4	371.68	18.99	0.50(0.42)	0.85	551.4	920.00
5	368.10	19.23	0.50(0.42)	0.85	552.9	900.00
6	365.93	19.37	0.50(0.42)	0.85	553.8	950.00
TOTAL AREA(ACRES) =						553.8

 FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9467.07	13.31	1.491	0.50(0.48)	0.97	2712.3	800.00
2	9434.11	17.11	1.245	0.50(0.49)	0.97	3665.6	818.00
3	9198.66	18.49	1.192	0.50(0.49)	0.97	4003.4	810.00
4	9387.72	23.50	1.033	0.50(0.49)	0.98	5241.1	600.00
5	9298.44	50.28	0.674	0.50(0.49)	0.99	12366.7	11801.00
6	9204.16	61.48	0.610	0.50(0.49)	0.99	15599.2	11500.00
7	9125.65	67.10	0.591	0.50(0.49)	0.99	17534.3	11701.00
8	9002.96	73.26	0.570	0.50(0.50)	0.99	19643.8	11000.00
9	8736.31	89.44	0.515	0.50(0.50)	0.99	26509.3	12500.00

10	8551.58	95.51	0.502	0.50	(0.50)	0.99	29378.7	10900.00
11	7912.53	103.87	0.486	0.50	(0.50)	0.99	32708.0	11130.00
12	7646.36	108.36	0.478	0.50	(0.50)	0.99	34118.8	12300.00
13	7248.38	114.98	0.465	0.50	(0.50)	0.99	36380.5	11620.00
14	6941.52	120.05	0.455	0.50	(0.50)	0.99	38018.3	10600.00
15	6212.36	130.14	0.443	0.50	(0.50)	0.99	40906.2	12400.00
16	5378.38	140.94	0.430	0.50	(0.50)	0.99	43212.4	12201.00
17	4778.55	149.74	0.419	0.50	(0.50)	0.99	44503.1	12111.00
18	4433.96	155.02	0.413	0.50	(0.50)	0.99	45249.5	10700.00
19	3873.08	164.49	0.402	0.50	(0.50)	0.99	46426.0	12261.00
20	3411.44	173.20	0.391	0.50	(0.50)	0.99	47237.1	10200.00
21	2851.40	187.72	0.379	0.50	(0.50)	0.99	48475.0	10300.00
22	2623.44	194.15	0.375	0.50	(0.50)	0.99	48827.2	12010.00
23	2159.98	213.59	0.365	0.50	(0.50)	0.99	49155.6	12000.00
24	1221.69	278.84	0.329	0.50	(0.50)	0.99	49826.4	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104602.45 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	444.41	10.57	1.759	0.50 (0.39)	0.78	360.1	940.00
2	444.42	10.77	1.740	0.50 (0.39)	0.78	365.5	930.00
3	402.73	14.22	1.402	0.50 (0.41)	0.81	450.0	910.00
4	371.68	18.99	1.173	0.50 (0.42)	0.85	551.4	920.00
5	368.10	19.23	1.164	0.50 (0.42)	0.85	552.9	900.00
6	365.93	19.37	1.159	0.50 (0.42)	0.85	553.8	950.00

LONGEST FLOWPATH FROM NODE 920.00 TO NODE 12606.00 = 6933.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9911.48	10.57	1.759	0.50 (0.47)	0.94	2513.9	940.00
2	9911.49	10.77	1.740	0.50 (0.47)	0.94	2559.6	930.00
3	9880.79	13.31	1.491	0.50 (0.47)	0.94	3140.1	800.00
4	9861.92	14.22	1.402	0.50 (0.47)	0.95	3390.4	910.00
5	9818.04	17.11	1.245	0.50 (0.48)	0.96	4177.0	818.00
6	9573.60	18.49	1.192	0.50 (0.48)	0.96	4544.2	810.00
7	9589.26	18.99	1.173	0.50 (0.48)	0.96	4678.8	920.00
8	9594.62	19.23	1.164	0.50 (0.48)	0.96	4738.7	900.00
9	9597.83	19.37	1.159	0.50 (0.48)	0.96	4774.9	950.00
10	9690.75	23.50	1.033	0.50 (0.48)	0.97	5794.9	600.00
11	9422.84	50.28	0.674	0.50 (0.49)	0.98	12920.5	11801.00
12	9296.51	61.48	0.610	0.50 (0.49)	0.98	16153.0	11500.00
13	9208.48	67.10	0.591	0.50 (0.49)	0.99	18088.1	11701.00
14	9075.35	73.26	0.570	0.50 (0.49)	0.99	20197.6	11000.00
15	8781.27	89.44	0.515	0.50 (0.49)	0.99	27063.1	12500.00
16	8590.29	95.51	0.502	0.50 (0.49)	0.99	29932.5	10900.00
17	7949.11	103.87	0.486	0.50 (0.50)	0.99	33261.8	11130.00
18	7682.29	108.36	0.478	0.50 (0.50)	0.99	34672.6	12300.00
19	7283.35	114.98	0.465	0.50 (0.50)	0.99	36934.3	11620.00
20	6975.76	120.05	0.455	0.50 (0.50)	0.99	38572.1	10600.00
21	6245.69	130.14	0.443	0.50 (0.50)	0.99	41460.0	12400.00
22	5410.73	140.94	0.430	0.50 (0.49)	0.99	43766.2	12201.00
23	4810.10	149.74	0.419	0.50 (0.49)	0.99	45056.9	12111.00
24	4465.04	155.02	0.413	0.50 (0.49)	0.99	45803.3	10700.00
25	3903.30	164.49	0.402	0.50 (0.49)	0.99	46979.8	12261.00
26	3440.88	173.20	0.391	0.50 (0.49)	0.99	47790.9	10200.00
27	2879.90	187.72	0.379	0.50 (0.49)	0.99	49028.8	10300.00

28	2651.67	194.15	0.375	0.50	(0.49)	0.99	49381.0	12010.00
29	2187.41	213.59	0.365	0.50	(0.49)	0.99	49709.4	12000.00
30	1246.41	278.84	0.329	0.50	(0.49)	0.99	50380.2	10100.00

TOTAL AREA (ACRES) = 50380.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 9911.49 Tc (MIN.) = 10.765
EFFECTIVE AREA (ACRES) = 2559.55 AREA-AVERAGED Fm (INCH/HR) = 0.47
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 50380.2
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104602.45 FEET.

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 10.77

* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.740

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.30	0.50	1.000	-
USER-DEFINED	-	0.30	0.50	1.000	-
USER-DEFINED	-	0.40	0.50	0.850	-
USER-DEFINED	-	0.60	0.50	1.000	-
USER-DEFINED	-	1.10	0.50	0.100	-
USER-DEFINED	-	0.80	0.50	0.850	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.666

SUBAREA AREA (ACRES) = 3.50 SUBAREA RUNOFF (CFS) = 4.43

EFFECTIVE AREA (ACRES) = 2563.05 AREA-AVERAGED Fm (INCH/HR) = 0.47

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.94

TOTAL AREA (ACRES) = 50383.7 PEAK FLOW RATE (CFS) = 9911.49

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 10.77

* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.740

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.80	0.50	1.000	-
USER-DEFINED	-	0.90	0.50	1.000	-
USER-DEFINED	-	1.50	0.50	1.000	-
USER-DEFINED	-	1.60	0.50	1.000	-
USER-DEFINED	-	1.80	0.50	1.000	-
USER-DEFINED	-	1.90	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 8.50 SUBAREA RUNOFF (CFS) = 9.48

EFFECTIVE AREA (ACRES) = 2571.55 AREA-AVERAGED Fm (INCH/HR) = 0.47

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.94

TOTAL AREA (ACRES) = 50392.2 PEAK FLOW RATE (CFS) = 9911.49

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 10.77

* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.740

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	3.30	0.50	1.000	-
USER-DEFINED	-	3.70	0.50	1.000	-
USER-DEFINED	-	3.90	0.50	1.000	-
USER-DEFINED	-	5.90	0.50	1.000	-
USER-DEFINED	-	9.10	0.50	1.000	-
USER-DEFINED	-	20.60	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 46.50 SUBAREA RUNOFF(CFS) = 51.89

EFFECTIVE AREA(ACRES) = 2618.05 AREA-AVERAGED Fm(INCH/HR) = 0.47

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.94

TOTAL AREA(ACRES) = 50438.7 PEAK FLOW RATE(CFS) = 9911.49

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 50438.7 TC(MIN.) = 10.77

EFFECTIVE AREA(ACRES) = 2618.05 AREA-AVERAGED Fm(INCH/HR) = 0.47

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.940

PEAK FLOW RATE(CFS) = 9911.49

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9911.48	10.57	1.759	0.50(0.47)	0.94	2572.4	940.00
2	9911.49	10.77	1.740	0.50(0.47)	0.94	2618.1	930.00
3	9880.79	13.31	1.491	0.50(0.47)	0.94	3198.6	800.00
4	9861.92	14.22	1.402	0.50(0.47)	0.95	3448.9	910.00
5	9818.04	17.11	1.245	0.50(0.48)	0.96	4235.5	818.00
6	9573.60	18.49	1.192	0.50(0.48)	0.96	4602.7	810.00
7	9589.26	18.99	1.173	0.50(0.48)	0.96	4737.3	920.00
8	9594.62	19.23	1.164	0.50(0.48)	0.96	4797.2	900.00
9	9597.83	19.37	1.159	0.50(0.48)	0.96	4833.4	950.00
10	9690.75	23.50	1.033	0.50(0.48)	0.97	5853.4	600.00
11	9422.84	50.28	0.674	0.50(0.49)	0.98	12979.0	11801.00
12	9296.51	61.48	0.610	0.50(0.49)	0.98	16211.5	11500.00
13	9208.48	67.10	0.591	0.50(0.49)	0.99	18146.6	11701.00
14	9075.35	73.26	0.570	0.50(0.49)	0.99	20256.1	11000.00
15	8781.27	89.44	0.515	0.50(0.49)	0.99	27121.6	12500.00
16	8590.29	95.51	0.502	0.50(0.49)	0.99	29991.0	10900.00
17	7949.11	103.87	0.486	0.50(0.50)	0.99	33320.3	11130.00
18	7682.29	108.36	0.478	0.50(0.50)	0.99	34731.1	12300.00
19	7283.35	114.98	0.465	0.50(0.50)	0.99	36992.8	11620.00
20	6975.76	120.05	0.455	0.50(0.50)	0.99	38630.6	10600.00
21	6245.69	130.14	0.443	0.50(0.50)	0.99	41518.5	12400.00
22	5410.73	140.94	0.430	0.50(0.49)	0.99	43824.7	12201.00
23	4810.10	149.74	0.419	0.50(0.49)	0.99	45115.4	12111.00

24	4465.04	155.02	0.413	0.50(0.49)	0.99	45861.8	10700.00
25	3903.30	164.49	0.402	0.50(0.49)	0.99	47038.3	12261.00
26	3440.88	173.20	0.391	0.50(0.49)	0.99	47849.4	10200.00
27	2879.90	187.72	0.379	0.50(0.49)	0.99	49087.3	10300.00
28	2651.67	194.15	0.375	0.50(0.49)	0.99	49439.5	12010.00
29	2187.41	213.59	0.365	0.50(0.49)	0.99	49767.9	12000.00
30	1246.41	278.84	0.329	0.50(0.49)	0.99	50438.7	10100.00

END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 127 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 5-YR EV FEB 2023 ROKAMOTO *

FILE NAME: RU05EV27.DAT
TIME/DATE OF STUDY: 08:56 02/08/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 5.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 2.715
- 2) 10.00; 1.802
- 3) 15.00; 1.320
- 4) 20.00; 1.130
- 5) 25.00; 0.985
- 6) 30.00; 0.883
- 7) 40.00; 0.756
- 8) 50.00; 0.673
- 9) 60.00; 0.612
- 10) 90.00; 0.510
- 11) 120.00; 0.452
- 12) 180.00; 0.379
- 13) 360.00; 0.281
- 14) 1200.00; 0.124

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL
HALF- CROWN TO STREET-CROSSFALL: CURB GUTTER-GEOMETRIES: MANNING
WIDTH CROSSFALL IN- / OUT-/PARK- HEIGHT WIDTH LIP HIKE FACTOR
NO. (FT) (FT) SIDE / SIDE/ WAY (FT) (FT) (FT) (FT) (n)
====

1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150
---	------	------	-------------------	------	------	--------	-------	--------

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU05EV26.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9911.49	10.77	0.50 (0.47)	0.94	2618.1	930.00
2	9818.04	17.11	0.50 (0.48)	0.96	4235.5	818.00
3	9690.75	23.50	0.50 (0.48)	0.97	5853.4	600.00
4	9422.84	50.28	0.50 (0.49)	0.98	12979.0	11801.00
5	9296.51	61.48	0.50 (0.49)	0.98	16211.5	11500.00
6	9208.48	67.10	0.50 (0.49)	0.99	18146.6	11701.00
7	9075.35	73.26	0.50 (0.49)	0.99	20256.1	11000.00
8	8781.27	89.44	0.50 (0.49)	0.99	27121.6	12500.00
9	8590.29	95.51	0.50 (0.49)	0.99	29991.0	10900.00
10	7949.11	103.87	0.50 (0.50)	0.99	33320.3	11130.00
11	7283.35	114.98	0.50 (0.50)	0.99	36992.8	11620.00
12	6245.69	130.14	0.50 (0.50)	0.99	41518.5	12400.00
13	5410.73	140.94	0.50 (0.49)	0.99	43824.7	12201.00
14	4810.10	149.74	0.50 (0.49)	0.99	45115.4	12111.00
15	3903.30	164.49	0.50 (0.49)	0.99	47038.3	12261.00
16	3440.88	173.20	0.50 (0.49)	0.99	47849.4	10200.00
17	2879.90	187.72	0.50 (0.49)	0.99	49087.3	10300.00
18	2651.67	194.15	0.50 (0.49)	0.99	49439.5	12010.00
19	2187.41	213.59	0.50 (0.49)	0.99	49767.9	12000.00
20	1246.41	278.84	0.50 (0.49)	0.99	50438.7	10100.00
TOTAL AREA (ACRES) =						50438.7

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9911.49	10.77	0.50 (0.47)	0.94	2618.1	930.00
2	9818.04	17.11	0.50 (0.48)	0.96	4235.5	818.00
3	9690.75	23.50	0.50 (0.48)	0.97	5853.4	600.00
4	9422.84	50.28	0.50 (0.49)	0.98	12979.0	11801.00
5	9296.51	61.48	0.50 (0.49)	0.98	16211.5	11500.00
6	9208.48	67.10	0.50 (0.49)	0.99	18146.6	11701.00
7	9075.35	73.26	0.50 (0.49)	0.99	20256.1	11000.00
8	8781.27	89.44	0.50 (0.49)	0.99	27121.6	12500.00
9	8590.29	95.51	0.50 (0.49)	0.99	29991.0	10900.00
10	7949.11	103.87	0.50 (0.50)	0.99	33320.3	11130.00
11	7283.35	114.98	0.50 (0.50)	0.99	36992.8	11620.00
12	6245.69	130.14	0.50 (0.50)	0.99	41518.5	12400.00
13	5410.73	140.94	0.50 (0.49)	0.99	43824.7	12201.00

14	4810.10	149.74	0.50	(0.49)	0.99	45115.4	12111.00
15	3903.30	164.49	0.50	(0.49)	0.99	47038.3	12261.00
16	3440.88	173.20	0.50	(0.49)	0.99	47849.4	10200.00
17	2879.90	187.72	0.50	(0.49)	0.99	49087.3	10300.00
18	2651.67	194.15	0.50	(0.49)	0.99	49439.5	12010.00
19	2187.41	213.59	0.50	(0.49)	0.99	49767.9	12000.00
20	1246.41	278.84	0.50	(0.49)	0.99	50438.7	10100.00
TOTAL AREA (ACRES) =			50438.7				

FLOW PROCESS FROM NODE 12606.00 TO NODE 12701.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 286.00 DOWNSTREAM (FEET) = 276.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1260.19 CHANNEL SLOPE = 0.0079
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.601

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.70	0.50	0.500	-
USER-DEFINED	-	0.90	0.50	0.850	-
USER-DEFINED	-	3.40	0.50	0.100	-
USER-DEFINED	-	3.60	0.50	1.000	-
USER-DEFINED	-	10.10	0.50	0.850	-
USER-DEFINED	-	17.40	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.860

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 9930.51

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 15.91

AVERAGE FLOW DEPTH (FEET) = 14.42 TRAVEL TIME (MIN.) = 1.32

Tc (MIN.) = 12.09

SUBAREA AREA (ACRES) = 36.10 SUBAREA RUNOFF (CFS) = 38.04

EFFECTIVE AREA (ACRES) = 2654.15 AREA-AVERAGED Fm (INCH/HR) = 0.47

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.94

TOTAL AREA (ACRES) = 50474.8 PEAK FLOW RATE (CFS) = 9911.49

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 14.42 FLOW VELOCITY (FEET/SEC.) = 15.90

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12701.00 = 105862.63 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9911.49	12.09	1.601	0.50 (0.47)	0.94	2654.2	930.00
2	9818.04	18.43	1.190	0.50 (0.48)	0.96	4271.6	818.00
3	9690.75	24.83	0.990	0.50 (0.48)	0.97	5889.5	600.00
4	9422.84	51.62	0.663	0.50 (0.49)	0.98	13015.1	11801.00
5	9296.51	62.82	0.602	0.50 (0.49)	0.98	16247.6	11500.00
6	9208.48	68.45	0.583	0.50 (0.49)	0.98	18182.7	11701.00
7	9075.35	74.61	0.562	0.50 (0.49)	0.99	20292.2	11000.00
8	8781.27	90.80	0.508	0.50 (0.49)	0.99	27157.7	12500.00
9	8590.29	96.88	0.497	0.50 (0.49)	0.99	30027.1	10900.00
10	7949.11	105.27	0.480	0.50 (0.50)	0.99	33356.4	11130.00

11	7283.35	116.40	0.459	0.50 (0.50)	0.99	37028.9	11620.00
12	6245.69	131.62	0.438	0.50 (0.50)	0.99	41554.6	12400.00
13	5410.73	142.47	0.425	0.50 (0.49)	0.99	43860.8	12201.00
14	4810.10	151.32	0.414	0.50 (0.49)	0.99	45151.5	12111.00
15	3903.30	166.16	0.396	0.50 (0.49)	0.99	47074.4	12261.00
16	3440.88	174.92	0.385	0.50 (0.49)	0.99	47885.5	10200.00
17	2879.90	189.51	0.374	0.50 (0.49)	0.99	49123.4	10300.00
18	2651.67	195.99	0.370	0.50 (0.49)	0.99	49475.6	12010.00
19	2187.41	215.51	0.360	0.50 (0.49)	0.99	49804.0	12000.00
20	1246.41	281.06	0.324	0.50 (0.49)	0.99	50474.8	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 9911.49 Tc (MIN.) = 12.09

AREA-AVERAGED Fm (INCH/HR) = 0.47 AREA-AVERAGED Fp (INCH/HR) = 0.50

AREA-AVERAGED Ap = 0.94 EFFECTIVE AREA (ACRES) = 2654.15

FLOW PROCESS FROM NODE 12701.00 TO NODE 12720.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 276.00 DOWNSTREAM (FEET) = 275.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 147.65 CHANNEL SLOPE = 0.0068
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00
 CHANNEL FLOW THRU SUBAREA (CFS) = 9911.49
 FLOW VELOCITY (FEET/SEC.) = 14.98 FLOW DEPTH (FEET) = 14.85
 TRAVEL TIME (MIN.) = 0.16 Tc (MIN.) = 12.25
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.00 = 106010.28 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9911.49	12.25	1.585	0.50 (0.47)	0.94	2654.2	930.00
2	9818.04	18.60	1.183	0.50 (0.48)	0.96	4271.6	818.00
3	9690.75	25.00	0.985	0.50 (0.48)	0.97	5889.5	600.00
4	9422.84	51.79	0.662	0.50 (0.49)	0.98	13015.1	11801.00
5	9296.51	62.99	0.602	0.50 (0.49)	0.98	16247.6	11500.00
6	9208.48	68.61	0.583	0.50 (0.49)	0.98	18182.7	11701.00
7	9075.35	74.78	0.562	0.50 (0.49)	0.99	20292.2	11000.00
8	8781.27	90.97	0.508	0.50 (0.49)	0.99	27157.7	12500.00
9	8590.29	97.05	0.496	0.50 (0.49)	0.99	30027.1	10900.00
10	7949.11	105.44	0.480	0.50 (0.50)	0.99	33356.4	11130.00
11	7283.35	116.58	0.459	0.50 (0.50)	0.99	37028.9	11620.00
12	6245.69	131.80	0.438	0.50 (0.50)	0.99	41554.6	12400.00
13	5410.73	142.66	0.424	0.50 (0.49)	0.99	43860.8	12201.00
14	4810.10	151.51	0.414	0.50 (0.49)	0.99	45151.5	12111.00
15	3903.30	166.37	0.396	0.50 (0.49)	0.99	47074.4	12261.00
16	3440.88	175.13	0.385	0.50 (0.49)	0.99	47885.5	10200.00
17	2879.90	189.74	0.374	0.50 (0.49)	0.99	49123.4	10300.00
18	2651.67	196.22	0.370	0.50 (0.49)	0.99	49475.6	12010.00
19	2187.41	215.75	0.360	0.50 (0.49)	0.99	49804.0	12000.00
20	1246.41	281.34	0.324	0.50 (0.49)	0.99	50474.8	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 9911.49 Tc (MIN.) = 12.25

AREA-AVERAGED Fm (INCH/HR) = 0.47 AREA-AVERAGED Fp (INCH/HR) = 0.50

AREA-AVERAGED Ap = 0.94 EFFECTIVE AREA (ACRES) = 2654.15

```

*****
FLOW PROCESS FROM NODE 12701.00 TO NODE 12720.00 IS CODE = 1
-----
>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
-----
TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION(MIN.) = 12.25
RAINFALL INTENSITY(INCH/HR) = 1.59
AREA-AVERAGED Fm(INCH/HR) = 0.47
AREA-AVERAGED Fp(INCH/HR) = 0.50
AREA-AVERAGED Ap = 0.94
EFFECTIVE STREAM AREA(ACRES) = 2654.15
TOTAL STREAM AREA(ACRES) = 50474.79
PEAK FLOW RATE(CFS) AT CONFLUENCE = 9911.49

```

```

*****
FLOW PROCESS FROM NODE 12710.00 TO NODE 12711.00 IS CODE = 21
-----
>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<
-----
INITIAL SUBAREA FLOW-LENGTH(FEET) = 943.56
ELEVATION DATA: UPSTREAM(FEET) = 940.78 DOWNSTREAM(FEET) = 657.79

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 13.910
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.425
SUBAREA Tc AND LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)
NATURAL FAIR COVER
"GRASS" - 6.56 0.50 1.000 65 13.91
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 5.46
TOTAL AREA(ACRES) = 6.56 PEAK FLOW RATE(CFS) = 5.46

```

```

*****
FLOW PROCESS FROM NODE 12711.00 TO NODE 12712.00 IS CODE = 51
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
-----
ELEVATION DATA: UPSTREAM(FEET) = 657.79 DOWNSTREAM(FEET) = 585.63
CHANNEL LENGTH THRU SUBAREA(FEET) = 766.00 CHANNEL SLOPE = 0.0942
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.300
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 26.94 0.50 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 15.18
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.94
AVERAGE FLOW DEPTH(FEET) = 0.80 TRAVEL TIME(MIN.) = 1.61

```

```

Tc(MIN.) = 15.52
SUBAREA AREA(ACRES) = 26.94 SUBAREA RUNOFF(CFS) = 19.40
EFFECTIVE AREA(ACRES) = 33.50 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 33.5 PEAK FLOW RATE(CFS) = 24.12

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.95 FLOW VELOCITY(FEET/SEC.) = 8.93
LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12712.00 = 1709.56 FEET.

```

```

*****
FLOW PROCESS FROM NODE 12712.00 TO NODE 12713.00 IS CODE = 51
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
-----

```

```

ELEVATION DATA: UPSTREAM(FEET) = 585.63 DOWNSTREAM(FEET) = 463.75
CHANNEL LENGTH THRU SUBAREA(FEET) = 1025.79 CHANNEL SLOPE = 0.1188
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.237
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 14.73 0.50 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 29.01
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.20
AVERAGE FLOW DEPTH(FEET) = 0.97 TRAVEL TIME(MIN.) = 1.68
Tc(MIN.) = 17.19
SUBAREA AREA(ACRES) = 14.73 SUBAREA RUNOFF(CFS) = 9.76
EFFECTIVE AREA(ACRES) = 48.23 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 48.2 PEAK FLOW RATE(CFS) = 31.97

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.01 FLOW VELOCITY(FEET/SEC.) = 10.45
LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12713.00 = 2735.35 FEET.

```

```

*****
FLOW PROCESS FROM NODE 12713.00 TO NODE 12714.00 IS CODE = 51
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
-----

```

```

ELEVATION DATA: UPSTREAM(FEET) = 463.75 DOWNSTREAM(FEET) = 360.30
CHANNEL LENGTH THRU SUBAREA(FEET) = 1148.54 CHANNEL SLOPE = 0.0901
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.172
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 105.64 0.50 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 63.93

```


TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 11.22
 AVERAGE FLOW DEPTH (FEET) = 1.38 TRAVEL TIME (MIN.) = 1.71
 Tc (MIN.) = 18.90
 SUBAREA AREA (ACRES) = 105.64 SUBAREA RUNOFF (CFS) = 63.85
 EFFECTIVE AREA (ACRES) = 153.87 AREA-AVERAGED Fm (INCH/HR) = 0.50
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 153.9 PEAK FLOW RATE (CFS) = 93.01

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 1.59 FLOW VELOCITY (FEET/SEC.) = 12.27
 LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12714.00 = 3883.89 FEET.

 FLOW PROCESS FROM NODE 12714.00 TO NODE 12720.00 IS CODE = 51

>>>> COMPUTE TRAPEZOIDAL CHANNEL FLOW <<<<<
 >>>> TRAVELTIME THRU SUBAREA (EXISTING ELEMENT) <<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 360.30 DOWNSTREAM (FEET) = 275.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1314.99 CHANNEL SLOPE = 0.0649
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 10.00
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.108
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	127.13	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 127.80
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 11.77
 AVERAGE FLOW DEPTH (FEET) = 1.90 TRAVEL TIME (MIN.) = 1.86
 Tc (MIN.) = 20.76

SUBAREA AREA (ACRES) = 127.13 SUBAREA RUNOFF (CFS) = 69.53
 EFFECTIVE AREA (ACRES) = 281.00 AREA-AVERAGED Fm (INCH/HR) = 0.50
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 281.0 PEAK FLOW RATE (CFS) = 153.69

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 2.04 FLOW VELOCITY (FEET/SEC.) = 12.31
 LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12720.00 = 5198.88 FEET.

 FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.00 IS CODE = 1

>>>> DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE <<<<<
 >>>> AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES <<<<<

=====

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
 TIME OF CONCENTRATION (MIN.) = 20.76
 RAINFALL INTENSITY (INCH/HR) = 1.11
 AREA-AVERAGED Fm (INCH/HR) = 0.50
 AREA-AVERAGED Fp (INCH/HR) = 0.50
 AREA-AVERAGED Ap = 1.00
 EFFECTIVE STREAM AREA (ACRES) = 281.00
 TOTAL STREAM AREA (ACRES) = 281.00
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 153.69

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9911.49	12.25	1.585	0.50 (0.47)	0.94	2654.2	930.00
1	9818.04	18.60	1.183	0.50 (0.48)	0.96	4271.6	818.00
1	9690.75	25.00	0.985	0.50 (0.48)	0.97	5889.5	600.00
1	9422.84	51.79	0.662	0.50 (0.49)	0.98	13015.1	11801.00
1	9296.51	62.99	0.602	0.50 (0.49)	0.98	16247.6	11500.00
1	9208.48	68.61	0.583	0.50 (0.49)	0.98	18182.7	11701.00
1	9075.35	74.78	0.562	0.50 (0.49)	0.99	20292.2	11000.00
1	8781.27	90.97	0.508	0.50 (0.49)	0.99	27157.7	12500.00
1	8590.29	97.05	0.496	0.50 (0.49)	0.99	30027.1	10900.00
1	7949.11	105.44	0.480	0.50 (0.50)	0.99	33356.4	11130.00
1	7283.35	116.58	0.459	0.50 (0.50)	0.99	37028.9	11620.00
1	6245.69	131.80	0.438	0.50 (0.50)	0.99	41554.6	12400.00
1	5410.73	142.66	0.424	0.50 (0.49)	0.99	43860.8	12201.00
1	4810.10	151.51	0.414	0.50 (0.49)	0.99	45151.5	12111.00
1	3903.30	166.37	0.396	0.50 (0.49)	0.99	47074.4	12261.00
1	3440.88	175.13	0.385	0.50 (0.49)	0.99	47885.5	10200.00
1	2879.90	189.74	0.374	0.50 (0.49)	0.99	49123.4	10300.00
1	2651.67	196.22	0.370	0.50 (0.49)	0.99	49475.6	12010.00
1	2187.41	215.75	0.360	0.50 (0.49)	0.99	49804.0	12000.00
1	1246.41	281.34	0.324	0.50 (0.49)	0.99	50474.8	10100.00
2	153.69	20.76	1.108	0.50 (0.50)	1.00	281.0	12710.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	10065.18	12.25	1.585	0.50 (0.47)	0.94	2819.9	930.00
2	9971.73	18.60	1.183	0.50 (0.48)	0.96	4523.3	818.00
3	9928.68	20.76	1.108	0.50 (0.48)	0.96	5099.8	12710.00
4	9813.37	25.00	0.985	0.50 (0.48)	0.97	6170.5	600.00
5	9463.78	51.79	0.662	0.50 (0.49)	0.98	13296.1	11801.00
6	9322.21	62.99	0.602	0.50 (0.49)	0.98	16528.6	11500.00
7	9229.34	68.61	0.583	0.50 (0.49)	0.98	18463.7	11701.00
8	9090.92	74.78	0.562	0.50 (0.49)	0.99	20573.2	11000.00
9	8783.27	90.97	0.508	0.50 (0.49)	0.99	27438.7	12500.00
10	8590.29	97.05	0.496	0.50 (0.49)	0.99	30308.1	10900.00
11	7949.11	105.44	0.480	0.50 (0.50)	0.99	33637.4	11130.00
12	7283.35	116.58	0.459	0.50 (0.50)	0.99	37309.9	11620.00
13	6245.69	131.80	0.438	0.50 (0.50)	0.99	41835.6	12400.00
14	5410.73	142.66	0.424	0.50 (0.49)	0.99	44141.8	12201.00
15	4810.10	151.51	0.414	0.50 (0.49)	0.99	45432.5	12111.00
16	3903.30	166.37	0.396	0.50 (0.49)	0.99	47355.4	12261.00
17	3440.87	175.13	0.385	0.50 (0.49)	0.99	48166.5	10200.00
18	2879.90	189.74	0.374	0.50 (0.49)	0.99	49404.4	10300.00
19	2651.67	196.22	0.370	0.50 (0.49)	0.99	49756.6	12010.00
20	2187.41	215.75	0.360	0.50 (0.49)	0.99	50085.0	12000.00
21	1246.41	281.34	0.324	0.50 (0.49)	0.99	50755.8	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
 PEAK FLOW RATE (CFS) = 10065.18 Tc (MIN.) = 12.25
 EFFECTIVE AREA (ACRES) = 2819.94 AREA-AVERAGED Fm (INCH/HR) = 0.47
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.94

TOTAL AREA (ACRES) = 50755.8
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.00 = 106010.28 FEET.

FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.50 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 275.00 DOWNSTREAM (FEET) = 258.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 2669.21 CHANNEL SLOPE = 0.0064
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.309

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	0.30	0.50	1.000	-
USER-DEFINED	-	0.30	0.50	0.100	-
USER-DEFINED	-	0.50	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.841

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 10065.86

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 14.69

AVERAGE FLOW DEPTH (FEET) = 15.11 TRAVEL TIME (MIN.) = 3.03

Tc (MIN.) = 15.28

SUBAREA AREA (ACRES) = 1.70 SUBAREA RUNOFF (CFS) = 1.36

EFFECTIVE AREA (ACRES) = 2821.64 AREA-AVERAGED Fm (INCH/HR) = 0.47

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.94

TOTAL AREA (ACRES) = 50757.5 PEAK FLOW RATE (CFS) = 10065.18

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 15.11 FLOW VELOCITY (FEET/SEC.) = 14.70

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108679.49 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	10065.18	15.28	1.309	0.50 (0.47)	0.94	2821.6	930.00
2	9971.73	21.63	1.083	0.50 (0.48)	0.96	4525.0	818.00
3	9928.68	23.80	1.020	0.50 (0.48)	0.96	5101.5	12710.00
4	9813.37	28.04	0.923	0.50 (0.48)	0.97	6172.2	600.00
5	9463.78	54.86	0.643	0.50 (0.49)	0.98	13297.8	11801.00
6	9322.21	66.08	0.591	0.50 (0.49)	0.98	16530.3	11500.00
7	9229.34	71.71	0.572	0.50 (0.49)	0.98	18465.4	11701.00
8	9090.92	77.88	0.551	0.50 (0.49)	0.99	20574.8	11000.00
9	8783.27	94.11	0.502	0.50 (0.49)	0.99	27440.4	12500.00
10	8590.29	100.20	0.490	0.50 (0.49)	0.99	30309.8	10900.00
11	7949.11	108.65	0.474	0.50 (0.50)	0.99	33639.1	11130.00
12	7283.35	119.86	0.452	0.50 (0.50)	0.99	37311.6	11620.00
13	6245.69	135.21	0.433	0.50 (0.50)	0.99	41837.3	12400.00
14	5410.73	146.20	0.420	0.50 (0.49)	0.99	44143.5	12201.00
15	4810.10	155.15	0.409	0.50 (0.49)	0.99	45434.2	12111.00
16	3903.30	170.20	0.391	0.50 (0.49)	0.99	47357.1	12261.00

17	3440.87	179.09	0.380	0.50 (0.49)	0.99	48168.2	10200.00
18	2879.90	193.88	0.371	0.50 (0.49)	0.99	49406.1	10300.00
19	2651.67	200.44	0.368	0.50 (0.49)	0.99	49758.3	12010.00
20	2187.41	220.19	0.357	0.50 (0.49)	0.99	50086.7	12000.00
21	1246.41	286.44	0.321	0.50 (0.49)	0.99	50757.5	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 10065.18 Tc (MIN.) = 15.28

AREA-AVERAGED Fm (INCH/HR) = 0.47 AREA-AVERAGED Fp (INCH/HR) = 0.50

AREA-AVERAGED Ap = 0.94 EFFECTIVE AREA (ACRES) = 2821.64

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 15.28

* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.309

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.50	0.50	0.850	-
USER-DEFINED	-	0.70	0.50	1.000	-
USER-DEFINED	-	1.50	0.50	1.000	-
USER-DEFINED	-	1.40	0.50	0.100	-
USER-DEFINED	-	2.30	0.50	0.100	-
USER-DEFINED	-	9.30	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.783

SUBAREA AREA (ACRES) = 15.70 SUBAREA RUNOFF (CFS) = 12.97

EFFECTIVE AREA (ACRES) = 2837.34 AREA-AVERAGED Fm (INCH/HR) = 0.47

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.94

TOTAL AREA (ACRES) = 50773.2 PEAK FLOW RATE (CFS) = 10065.18

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 15.28

* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.309

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	11.20	0.50	1.000	-
USER-DEFINED	-	11.40	0.50	1.000	-
USER-DEFINED	-	11.80	0.50	1.000	-
USER-DEFINED	-	27.70	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 62.10 SUBAREA RUNOFF (CFS) = 45.23

EFFECTIVE AREA (ACRES) = 2899.44 AREA-AVERAGED Fm (INCH/HR) = 0.47

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.94

TOTAL AREA (ACRES) = 50835.3 PEAK FLOW RATE (CFS) = 10065.18

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 15.1

=====
>>>>DEFINE MEMORY BANK # 2 <<<<<
=====

PEAK FLOWRATE TABLE FILE NAME: 3C05EVRL.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	912.51	14.10	0.50 (0.21)	0.42	846.2	410.00
2	907.08	15.83	0.50 (0.21)	0.42	933.3	420.00
3	938.94	20.08	0.50 (0.21)	0.42	1133.0	310.00
4	934.39	21.28	0.50 (0.21)	0.42	1176.7	400.00
5	898.94	24.05	0.50 (0.21)	0.42	1244.9	430.00
6	893.55	24.46	0.50 (0.21)	0.42	1254.6	300.00
7	887.32	24.80	0.50 (0.21)	0.42	1261.6	320.00
8	724.03	33.53	0.50 (0.22)	0.43	1292.3	390.00
TOTAL AREA (ACRES) =						1292.3

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<
=====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	10065.18	15.28	1.309	0.50 (0.47)	0.94	2899.4	930.00
2	9971.73	21.63	1.083	0.50 (0.48)	0.96	4602.8	818.00
3	9928.68	23.80	1.020	0.50 (0.48)	0.96	5179.3	12710.00
4	9813.37	28.04	0.923	0.50 (0.48)	0.97	6250.0	600.00
5	9463.78	54.86	0.643	0.50 (0.49)	0.98	13375.6	11801.00
6	9322.21	66.08	0.591	0.50 (0.49)	0.98	16608.1	11500.00
7	9229.34	71.71	0.572	0.50 (0.49)	0.98	18543.2	11701.00
8	9090.92	77.88	0.551	0.50 (0.49)	0.99	20652.6	11000.00
9	8783.27	94.11	0.502	0.50 (0.49)	0.99	27518.2	12500.00
10	8590.29	100.20	0.490	0.50 (0.49)	0.99	30387.6	10900.00
11	7949.11	108.65	0.474	0.50 (0.50)	0.99	33716.9	11130.00
12	7283.35	119.86	0.452	0.50 (0.50)	0.99	37389.4	11620.00
13	6245.69	135.21	0.433	0.50 (0.50)	0.99	41915.1	12400.00
14	5410.73	146.20	0.420	0.50 (0.49)	0.99	44221.3	12201.00
15	4810.10	155.15	0.409	0.50 (0.49)	0.99	45512.0	12111.00
16	3903.30	170.20	0.391	0.50 (0.49)	0.99	47434.9	12261.00
17	3440.87	179.09	0.380	0.50 (0.49)	0.99	48246.0	10200.00
18	2879.90	193.88	0.371	0.50 (0.49)	0.99	49483.9	10300.00
19	2651.67	200.44	0.368	0.50 (0.49)	0.99	49836.1	12010.00
20	2187.41	220.19	0.357	0.50 (0.49)	0.99	50164.5	12000.00
21	1246.41	286.44	0.321	0.50 (0.49)	0.99	50835.3	10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 =							108679.49 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	912.51	14.10	1.407	0.50 (0.21)	0.42	846.2	410.00
2	907.08	15.83	1.289	0.50 (0.21)	0.42	933.3	420.00
3	938.94	20.08	1.128	0.50 (0.21)	0.42	1133.0	310.00
4	934.39	21.28	1.093	0.50 (0.21)	0.42	1176.7	400.00
5	898.94	24.05	1.013	0.50 (0.21)	0.42	1244.9	430.00
6	893.55	24.46	1.001	0.50 (0.21)	0.42	1254.6	300.00

7 887.32 24.80 0.991 0.50 (0.21) 0.42 1261.6 320.00
8 724.03 33.53 0.838 0.50 (0.22) 0.43 1292.3 390.00
LONGEST FLOWPATH FROM NODE 390.00 TO NODE 12720.50 = 13248.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	10977.69	14.10	1.407	0.50 (0.41)	0.82	3522.2	410.00
2	10973.99	15.28	1.309	0.50 (0.41)	0.82	3805.0	930.00
3	10964.14	15.83	1.289	0.50 (0.41)	0.82	3980.6	420.00
4	10933.44	20.08	1.128	0.50 (0.42)	0.84	5320.6	310.00
5	10911.32	21.28	1.093	0.50 (0.42)	0.85	5684.8	400.00
6	10901.61	21.63	1.083	0.50 (0.42)	0.85	5788.2	818.00
7	10830.84	23.80	1.020	0.50 (0.43)	0.86	6418.0	12710.00
8	10820.77	24.05	1.013	0.50 (0.43)	0.86	6487.8	430.00
9	10804.27	24.46	1.001	0.50 (0.43)	0.86	6600.8	300.00
10	10788.86	24.80	0.991	0.50 (0.43)	0.86	6693.0	320.00
11	10640.00	28.04	0.923	0.50 (0.44)	0.88	7523.0	600.00
12	10465.88	33.53	0.838	0.50 (0.45)	0.89	9000.2	390.00
13	9961.22	54.86	0.643	0.50 (0.47)	0.93	14667.9	11801.00
14	9759.17	66.08	0.591	0.50 (0.47)	0.94	17900.4	11500.00
15	9644.04	71.71	0.572	0.50 (0.47)	0.95	19835.5	11701.00
16	9481.19	77.88	0.551	0.50 (0.48)	0.95	21944.9	11000.00
17	9116.40	94.11	0.502	0.50 (0.48)	0.96	28810.5	12500.00
18	8914.68	100.20	0.490	0.50 (0.48)	0.97	31679.9	10900.00
19	8262.70	108.65	0.474	0.50 (0.48)	0.97	35009.2	11130.00
20	7582.60	119.86	0.452	0.50 (0.49)	0.97	38681.7	11620.00
21	6532.51	135.21	0.433	0.50 (0.49)	0.97	43207.4	12400.00
22	5688.71	146.20	0.420	0.50 (0.49)	0.97	45513.6	12201.00
23	5080.87	155.15	0.409	0.50 (0.49)	0.97	46804.3	12111.00
24	4161.96	170.20	0.391	0.50 (0.49)	0.97	48727.2	12261.00
25	3692.38	179.09	0.380	0.50 (0.49)	0.97	49538.3	10200.00
26	3125.67	193.88	0.371	0.50 (0.49)	0.97	50776.2	10300.00
27	2895.07	200.44	0.368	0.50 (0.49)	0.98	51128.4	12010.00
28	2423.70	220.19	0.357	0.50 (0.49)	0.98	51456.8	12000.00
29	1458.84	286.44	0.321	0.50 (0.49)	0.98	52127.6	10100.00
TOTAL AREA (ACRES) =							52127.6

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 10977.69 Tc (MIN.) = 14.100
EFFECTIVE AREA (ACRES) = 3522.22 AREA-AVERAGED Fm (INCH/HR) = 0.41
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.97
TOTAL AREA (ACRES) = 52127.6
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108679.49 FEET.

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<
=====

FLOW PROCESS FROM NODE 12720.50 TO NODE 12722.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 258.00 DOWNSTREAM (FEET) = 255.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 1269.00 CHANNEL SLOPE = 0.0024
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
 * 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.277
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.10	0.50	0.850	-
USER-DEFINED	-	0.10	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	0.30	0.50	1.000	-
USER-DEFINED	-	0.30	0.50	1.000	-
USER-DEFINED	-	0.40	0.50	0.100	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.732
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 10978.26
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.36
 AVERAGE FLOW DEPTH(FEET) = 18.80 TRAVEL TIME(MIN.) = 2.04
 Tc(MIN.) = 16.14
 SUBAREA AREA(ACRES) = 1.40 SUBAREA RUNOFF(CFS) = 1.15
 EFFECTIVE AREA(ACRES) = 3523.62 AREA-AVERAGED Fm(INCH/HR) = 0.41
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.82
 TOTAL AREA(ACRES) = 52129.0 PEAK FLOW RATE(CFS) = 10977.69
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 18.80 FLOW VELOCITY(FEET/SEC.) = 10.36
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12722.00 = 109948.49 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	10977.69	16.14	1.277	0.50(0.41)	0.82	3523.6	410.00
2	10973.99	17.32	1.232	0.50(0.41)	0.82	3806.4	930.00
3	10964.14	17.87	1.211	0.50(0.41)	0.82	3982.0	420.00
4	10933.44	22.13	1.068	0.50(0.42)	0.84	5322.0	310.00
5	10911.32	23.32	1.034	0.50(0.42)	0.85	5686.2	400.00
6	10901.61	23.68	1.023	0.50(0.42)	0.85	5789.6	818.00
7	10830.84	25.85	0.968	0.50(0.43)	0.86	6419.4	12710.00
8	10820.77	26.10	0.963	0.50(0.43)	0.86	6489.2	430.00
9	10804.27	26.51	0.954	0.50(0.43)	0.86	6602.2	300.00
10	10788.86	26.85	0.947	0.50(0.43)	0.86	6694.4	320.00
11	10640.00	30.10	0.882	0.50(0.44)	0.88	7524.4	600.00
12	10465.88	35.60	0.812	0.50(0.45)	0.89	9001.6	390.00
13	9961.22	56.96	0.631	0.50(0.47)	0.93	14669.3	11801.00
14	9759.17	68.18	0.584	0.50(0.47)	0.94	17901.8	11500.00
15	9644.04	73.82	0.565	0.50(0.47)	0.95	19836.9	11701.00
16	9481.19	80.00	0.544	0.50(0.48)	0.95	21946.3	11000.00
17	9116.40	96.24	0.498	0.50(0.48)	0.96	28811.9	12500.00
18	8914.68	102.35	0.486	0.50(0.48)	0.97	31681.3	10900.00
19	8262.70	110.85	0.470	0.50(0.48)	0.97	35010.6	11130.00
20	7582.60	122.10	0.449	0.50(0.49)	0.97	38683.1	11620.00
21	6532.51	137.54	0.431	0.50(0.49)	0.97	43208.8	12400.00
22	5688.71	148.61	0.417	0.50(0.49)	0.97	45515.0	12201.00
23	5080.87	157.63	0.406	0.50(0.49)	0.97	46805.7	12111.00
24	4161.96	172.81	0.388	0.50(0.49)	0.97	48728.6	12261.00
25	3692.38	181.77	0.378	0.50(0.49)	0.97	49539.7	10200.00
26	3125.67	196.67	0.370	0.50(0.49)	0.97	50777.6	10300.00

27 2895.07 203.29 0.366 0.50(0.49) 0.97 51129.8 12010.00
 28 2423.70 223.17 0.355 0.50(0.49) 0.98 51458.2 12000.00
 29 1458.84 289.82 0.319 0.50(0.49) 0.98 52129.0 10100.00
 NEW PEAK FLOW DATA ARE:
 PEAK FLOW RATE(CFS) = 10977.69 Tc(MIN.) = 16.14
 AREA-AVERAGED Fm(INCH/HR) = 0.41 AREA-AVERAGED Fp(INCH/HR) = 0.50
 AREA-AVERAGED Ap = 0.82 EFFECTIVE AREA(ACRES) = 3523.62

 FLOW PROCESS FROM NODE 12722.00 TO NODE 12722.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 16.14
 * 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.277
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.50	0.50	0.100	-
USER-DEFINED	-	0.60	0.50	1.000	-
USER-DEFINED	-	0.60	0.50	1.000	-
USER-DEFINED	-	0.60	0.50	0.100	-
USER-DEFINED	-	0.90	0.50	1.000	-
USER-DEFINED	-	1.00	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.764
 SUBAREA AREA(ACRES) = 4.20 SUBAREA RUNOFF(CFS) = 3.38
 EFFECTIVE AREA(ACRES) = 3527.82 AREA-AVERAGED Fm(INCH/HR) = 0.41
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.82
 TOTAL AREA(ACRES) = 52133.2 PEAK FLOW RATE(CFS) = 10977.69
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12722.00 TO NODE 12722.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 16.14
 * 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.277
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.30	0.50	1.000	-
USER-DEFINED	-	3.20	0.50	1.000	-
USER-DEFINED	-	3.70	0.50	1.000	-
USER-DEFINED	-	12.00	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 20.20 SUBAREA RUNOFF(CFS) = 14.12
 EFFECTIVE AREA(ACRES) = 3548.02 AREA-AVERAGED Fm(INCH/HR) = 0.41
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.82
 TOTAL AREA(ACRES) = 52153.4 PEAK FLOW RATE(CFS) = 10977.69
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12722.00 TO NODE 12740.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 255.00 DOWNSTREAM(FEET) = 252.10
CHANNEL LENGTH THRU SUBAREA(FEET) = 624.00 CHANNEL SLOPE = 0.0046
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00

* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.247

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include USER-DEFINED entries with various soil groups and areas.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.690

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 10979.55

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 13.34

AVERAGE FLOW DEPTH(FEET) = 16.56 TRAVEL TIME(MIN.) = 0.78

Tc(MIN.) = 16.92

SUBAREA AREA(ACRES) = 4.60 SUBAREA RUNOFF(CFS) = 3.73

EFFECTIVE AREA(ACRES) = 3552.62 AREA-AVERAGED Fm(INCH/HR) = 0.41

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.82

TOTAL AREA(ACRES) = 52158.0 PEAK FLOW RATE(CFS) = 10977.69

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 16.56 FLOW VELOCITY(FEET/SEC.) = 13.35

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12740.00 = 110572.49 FEET.

** PEAK FLOW RATE TABLE **

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 23 rows of data for different stream numbers.

Table with 8 columns: Node number, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 5 rows of data for nodes 24 through 29.

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 10977.69 Tc(MIN.) = 16.92

AREA-AVERAGED Fm(INCH/HR) = 0.41 AREA-AVERAGED Fp(INCH/HR) = 0.50

AREA-AVERAGED Ap = 0.82 EFFECTIVE AREA(ACRES) = 3552.62

***** FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 81 *****

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 16.92

* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.247

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include USER-DEFINED entries.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.913

SUBAREA AREA(ACRES) = 26.00 SUBAREA RUNOFF(CFS) = 18.49

EFFECTIVE AREA(ACRES) = 3578.62 AREA-AVERAGED Fm(INCH/HR) = 0.41

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.82

TOTAL AREA(ACRES) = 52184.0 PEAK FLOW RATE(CFS) = 10977.69

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

***** FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 81 *****

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 16.92

* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.247

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include USER-DEFINED entries.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 39.00 SUBAREA RUNOFF(CFS) = 26.21

EFFECTIVE AREA(ACRES) = 3617.62 AREA-AVERAGED Fm(INCH/HR) = 0.41

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.82

TOTAL AREA(ACRES) = 52223.0 PEAK FLOW RATE(CFS) = 10977.69

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

***** FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 1 *****

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION(MIN.) = 16.92
RAINFALL INTENSITY(INCH/HR) = 1.25
AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50
AREA-AVERAGED Ap = 0.82
EFFECTIVE STREAM AREA(ACRES) = 3617.62
TOTAL STREAM AREA(ACRES) = 52222.99
PEAK FLOW RATE(CFS) AT CONFLUENCE = 10977.69

FLOW PROCESS FROM NODE 12730.00 TO NODE 12731.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH(FEET) = 561.54
ELEVATION DATA: UPSTREAM(FEET) = 613.29 DOWNSTREAM(FEET) = 551.75

$T_c = K * [(LENGTH ** 3.00) / (ELEVATION CHANGE)] ** 0.20$
SUBAREA ANALYSIS USED MINIMUM T_c (MIN.) = 13.823
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.433
SUBAREA T_c AND LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS T_c
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)
NATURAL FAIR COVER
"CHAPARRAL,BROADLEAF" - 6.33 0.50 1.000 65 13.82
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 5.32
TOTAL AREA(ACRES) = 6.33 PEAK FLOW RATE(CFS) = 5.32

FLOW PROCESS FROM NODE 12731.00 TO NODE 12732.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 551.75 DOWNSTREAM(FEET) = 494.40
CHANNEL LENGTH THRU SUBAREA(FEET) = 971.91 CHANNEL SLOPE = 0.0590
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.275
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 34.62 0.50 1.000 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 17.44
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.89
AVERAGE FLOW DEPTH(FEET) = 0.92 TRAVEL TIME(MIN.) = 2.35
 T_c (MIN.) = 16.17
SUBAREA AREA(ACRES) = 34.62 SUBAREA RUNOFF(CFS) = 24.15

EFFECTIVE AREA(ACRES) = 40.95 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 40.9 PEAK FLOW RATE(CFS) = 28.57

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.10 FLOW VELOCITY(FEET/SEC.) = 7.82
LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12732.00 = 1533.45 FEET.

FLOW PROCESS FROM NODE 12732.00 TO NODE 12733.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 494.40 DOWNSTREAM(FEET) = 431.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1156.41 CHANNEL SLOPE = 0.0548
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.191
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 59.52 0.50 1.000 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 47.07
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.64
AVERAGE FLOW DEPTH(FEET) = 1.35 TRAVEL TIME(MIN.) = 2.23
 T_c (MIN.) = 18.40
SUBAREA AREA(ACRES) = 59.52 SUBAREA RUNOFF(CFS) = 36.99
EFFECTIVE AREA(ACRES) = 100.47 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 100.5 PEAK FLOW RATE(CFS) = 62.43

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.50 FLOW VELOCITY(FEET/SEC.) = 9.25
LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12733.00 = 2689.86 FEET.

FLOW PROCESS FROM NODE 12733.00 TO NODE 12734.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 431.00 DOWNSTREAM(FEET) = 367.10
CHANNEL LENGTH THRU SUBAREA(FEET) = 1654.48 CHANNEL SLOPE = 0.0386
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.083
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 64.05 0.50 1.000 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 79.27
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.61
AVERAGE FLOW DEPTH(FEET) = 1.75 TRAVEL TIME(MIN.) = 3.20

Tc(MIN.) = 21.61
 SUBAREA AREA(ACRES) = 64.05 SUBAREA RUNOFF(CFS) = 33.62
 EFFECTIVE AREA(ACRES) = 164.52 AREA-AVERAGED Fm(INCH/HR) = 0.50
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 164.5 PEAK FLOW RATE(CFS) = 86.35

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 1.81 FLOW VELOCITY(FEET/SEC.) = 8.78
 LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12734.00 = 4344.34 FEET.

 FLOW PROCESS FROM NODE 12734.00 TO NODE 12740.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 367.11 DOWNSTREAM(FEET) = 252.10
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1880.98 CHANNEL SLOPE = 0.0611
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00

* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.998
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 26.02 0.50 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 92.19
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.65
 AVERAGE FLOW DEPTH(FEET) = 1.70 TRAVEL TIME(MIN.) = 2.94
 Tc(MIN.) = 24.55
 SUBAREA AREA(ACRES) = 26.02 SUBAREA RUNOFF(CFS) = 11.66
 EFFECTIVE AREA(ACRES) = 190.54 AREA-AVERAGED Fm(INCH/HR) = 0.50
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 190.5 PEAK FLOW RATE(CFS) = 86.35
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 1.66 FLOW VELOCITY(FEET/SEC.) = 10.44
 LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12740.00 = 6225.32 FEET.

 FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
 TIME OF CONCENTRATION(MIN.) = 24.55
 RAINFALL INTENSITY(INCH/HR) = 1.00
 AREA-AVERAGED Fm(INCH/HR) = 0.50
 AREA-AVERAGED Fp(INCH/HR) = 0.50
 AREA-AVERAGED Ap = 1.00
 EFFECTIVE STREAM AREA(ACRES) = 190.54
 TOTAL STREAM AREA(ACRES) = 190.54
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 86.35

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	10977.69	16.92	1.247	0.50(0.41)	0.82	3617.6	410.00
1	10973.99	18.10	1.202	0.50(0.41)	0.82	3900.4	930.00
1	10964.14	18.65	1.181	0.50(0.41)	0.82	4076.0	420.00
1	10933.44	22.91	1.046	0.50(0.42)	0.84	5416.0	310.00
1	10911.32	24.10	1.011	0.50(0.42)	0.85	5780.2	400.00
1	10901.61	24.46	1.001	0.50(0.42)	0.85	5883.6	818.00
1	10830.84	26.63	0.952	0.50(0.43)	0.86	6513.4	12710.00
1	10820.77	26.88	0.947	0.50(0.43)	0.86	6583.2	430.00
1	10804.27	27.29	0.938	0.50(0.43)	0.86	6696.2	300.00
1	10788.86	27.63	0.931	0.50(0.43)	0.86	6788.4	320.00
1	10640.00	30.89	0.872	0.50(0.44)	0.88	7618.4	600.00
1	10465.88	36.39	0.802	0.50(0.45)	0.89	9095.6	390.00
1	9961.22	57.75	0.626	0.50(0.47)	0.93	14763.3	11801.00
1	9759.17	68.98	0.581	0.50(0.47)	0.94	17995.8	11500.00
1	9644.04	74.62	0.562	0.50(0.47)	0.95	19930.9	11701.00
1	9481.19	80.81	0.541	0.50(0.48)	0.95	22040.3	11000.00
1	9116.40	97.06	0.496	0.50(0.48)	0.96	28905.9	12500.00
1	8914.68	103.18	0.485	0.50(0.48)	0.97	31775.3	10900.00
1	8262.70	111.68	0.468	0.50(0.48)	0.97	35104.6	11130.00
1	7582.60	122.96	0.448	0.50(0.49)	0.97	38777.1	11620.00
1	6532.51	138.42	0.430	0.50(0.49)	0.97	43302.8	12400.00
1	5688.71	149.52	0.416	0.50(0.49)	0.97	45609.0	12201.00
1	5080.87	158.58	0.405	0.50(0.49)	0.97	46899.7	12111.00
1	4161.96	173.80	0.387	0.50(0.49)	0.97	48822.6	12261.00
1	3692.38	182.80	0.377	0.50(0.49)	0.97	49633.7	10200.00
1	3125.67	197.74	0.369	0.50(0.49)	0.97	50871.6	10300.00
1	2895.07	204.38	0.366	0.50(0.49)	0.97	51223.8	12010.00
1	2423.70	224.30	0.355	0.50(0.49)	0.98	51552.2	12000.00
1	1458.84	291.11	0.319	0.50(0.49)	0.98	52223.0	10100.00
2	86.35	24.55	0.998	0.50(0.50)	1.00	190.5	12730.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11064.04	16.92	1.247	0.50(0.41)	0.83	3749.0	410.00
2	11060.34	18.10	1.202	0.50(0.41)	0.83	4040.8	930.00
3	11050.50	18.65	1.181	0.50(0.42)	0.83	4220.7	420.00
4	11019.80	22.91	1.046	0.50(0.42)	0.85	5593.8	310.00
5	10997.67	24.10	1.011	0.50(0.43)	0.85	5967.3	400.00
6	10987.96	24.46	1.001	0.50(0.43)	0.85	6073.4	818.00
7	10984.94	24.55	0.998	0.50(0.43)	0.85	6101.0	12730.00
8	10909.16	26.63	0.952	0.50(0.43)	0.86	6704.0	12710.00
9	10898.19	26.88	0.947	0.50(0.43)	0.86	6773.8	430.00
10	10880.24	27.29	0.938	0.50(0.43)	0.86	6886.7	300.00
11	10863.63	27.63	0.931	0.50(0.43)	0.87	6978.9	320.00
12	10704.44	30.89	0.872	0.50(0.44)	0.88	7809.0	600.00
13	10518.20	36.39	0.802	0.50(0.45)	0.90	9286.1	390.00
14	9982.99	57.75	0.626	0.50(0.47)	0.93	14953.9	11801.00
15	9773.26	68.98	0.581	0.50(0.47)	0.94	18186.4	11500.00
16	9654.81	74.62	0.562	0.50(0.47)	0.95	20121.5	11701.00
17	9488.31	80.81	0.541	0.50(0.48)	0.95	22230.9	11000.00
18	9116.40	97.06	0.496	0.50(0.48)	0.96	29096.5	12500.00

19	8914.68	103.18	0.485	0.50	(0.48)	0.97	31965.9	10900.00
20	8262.70	111.68	0.468	0.50	(0.48)	0.97	35295.1	11130.00
21	7582.60	122.96	0.448	0.50	(0.49)	0.97	38967.6	11620.00
22	6532.51	138.42	0.430	0.50	(0.49)	0.97	43493.4	12400.00
23	5688.71	149.52	0.416	0.50	(0.49)	0.97	45799.6	12201.00
24	5080.87	158.58	0.405	0.50	(0.49)	0.97	47090.2	12111.00
25	4161.96	173.80	0.387	0.50	(0.49)	0.97	49013.1	12261.00
26	3692.38	182.80	0.377	0.50	(0.49)	0.97	49824.2	10200.00
27	3125.67	197.74	0.369	0.50	(0.49)	0.97	51062.2	10300.00
28	2895.07	204.38	0.366	0.50	(0.49)	0.98	51414.4	12010.00
29	2423.70	224.30	0.355	0.50	(0.49)	0.98	51742.7	12000.00
30	1458.84	291.11	0.319	0.50	(0.49)	0.98	52413.5	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 11064.04 Tc(MIN.) = 16.92
EFFECTIVE AREA(ACRES) = 3748.95 AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.83
TOTAL AREA(ACRES) = 52413.5
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12740.00 = 110572.49 FEET.

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 252.10 DOWNSTREAM(FEET) = 240.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1200.00 CHANNEL SLOPE = 0.0101
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.205

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.30	0.50	1.000	-
USER-DEFINED	-	0.40	0.50	1.000	-
USER-DEFINED	-	0.40	0.50	0.100	-
USER-DEFINED	-	0.60	0.50	0.100	-
USER-DEFINED	-	1.50	0.50	1.000	-
USER-DEFINED	-	3.20	0.50	0.850	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.784
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 11066.38
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 17.88
AVERAGE FLOW DEPTH(FEET) = 14.36 TRAVEL TIME(MIN.) = 1.12
Tc(MIN.) = 18.04
SUBAREA AREA(ACRES) = 6.40 SUBAREA RUNOFF(CFS) = 4.68
EFFECTIVE AREA(ACRES) = 3755.35 AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.83
TOTAL AREA(ACRES) = 52419.9 PEAK FLOW RATE(CFS) = 11064.04
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 14.36 FLOW VELOCITY(FEET/SEC.) = 17.88
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111772.49 FEET.

** PEAK FLOW RATE TABLE **

STREAM	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	--------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	11064.04	18.04	1.205	0.50(0.41)	0.83	3755.4 410.00
2	11060.34	19.22	1.160	0.50(0.41)	0.83	4047.2 930.00
3	11050.50	19.77	1.139	0.50(0.42)	0.83	4227.1 420.00
4	11019.80	24.03	1.013	0.50(0.42)	0.85	5600.2 310.00
5	10997.67	25.22	0.980	0.50(0.43)	0.85	5973.7 400.00
6	10987.96	25.58	0.973	0.50(0.43)	0.85	6079.8 818.00
7	10984.94	25.67	0.971	0.50(0.43)	0.85	6107.4 12730.00
8	10909.16	27.75	0.929	0.50(0.43)	0.86	6710.4 12710.00
9	10898.19	28.01	0.924	0.50(0.43)	0.86	6780.2 430.00
10	10880.24	28.42	0.915	0.50(0.43)	0.86	6893.1 300.00
11	10863.63	28.76	0.908	0.50(0.43)	0.87	6985.3 320.00
12	10704.44	32.02	0.857	0.50(0.44)	0.88	7815.4 600.00
13	10518.20	37.52	0.787	0.50(0.45)	0.90	9292.5 390.00
14	9982.99	58.90	0.619	0.50(0.47)	0.93	14960.3 11801.00
15	9773.26	70.14	0.578	0.50(0.47)	0.94	18192.8 11500.00
16	9654.81	75.78	0.558	0.50(0.47)	0.95	20127.9 11701.00
17	9488.31	81.97	0.537	0.50(0.48)	0.95	22237.3 11000.00
18	9116.40	98.23	0.494	0.50(0.48)	0.96	29102.9 12500.00
19	8914.68	104.36	0.482	0.50(0.48)	0.97	31972.3 10900.00
20	8262.70	112.89	0.466	0.50(0.48)	0.97	35301.5 11130.00
21	7582.60	124.19	0.447	0.50(0.49)	0.97	38974.0 11620.00
22	6532.51	139.70	0.428	0.50(0.49)	0.97	43499.8 12400.00
23	5688.71	150.85	0.414	0.50(0.49)	0.97	45806.0 12201.00
24	5080.87	159.93	0.403	0.50(0.49)	0.97	47096.6 12111.00
25	4161.96	175.23	0.385	0.50(0.49)	0.97	49019.5 12261.00
26	3692.38	184.27	0.377	0.50(0.49)	0.97	49830.6 10200.00
27	3125.67	199.27	0.369	0.50(0.49)	0.97	51068.6 10300.00
28	2895.07	205.94	0.365	0.50(0.49)	0.98	51420.8 12010.00
29	2423.70	225.94	0.354	0.50(0.49)	0.98	51749.1 12000.00
30	1458.84	292.97	0.317	0.50(0.49)	0.98	52419.9 10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 11064.04 Tc(MIN.) = 18.04
AREA-AVERAGED Fm(INCH/HR) = 0.41 AREA-AVERAGED Fp(INCH/HR) = 0.50
AREA-AVERAGED Ap = 0.83 EFFECTIVE AREA(ACRES) = 3755.35

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 18.04
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.205
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	3.90	0.50	1.000	-
USER-DEFINED	-	8.70	0.50	1.000	-
USER-DEFINED	-	10.30	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 22.90 SUBAREA RUNOFF(CFS) = 14.52
EFFECTIVE AREA(ACRES) = 3778.25 AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.83
TOTAL AREA(ACRES) = 52442.8 PEAK FLOW RATE(CFS) = 11064.04
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 52442.8 TC (MIN.) = 18.04
 EFFECTIVE AREA (ACRES) = 3778.25 AREA-AVERAGED Fm (INCH/HR) = 0.41
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.827
 PEAK FLOW RATE (CFS) = 11064.04

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11064.04	18.04	1.205	0.50 (0.41)	0.83	3778.3	410.00
2	11060.34	19.22	1.160	0.50 (0.41)	0.83	4070.1	930.00
3	11050.50	19.77	1.139	0.50 (0.42)	0.83	4250.0	420.00
4	11019.80	24.03	1.013	0.50 (0.42)	0.85	5623.1	310.00
5	10997.67	25.22	0.980	0.50 (0.43)	0.85	5996.6	400.00
6	10987.96	25.58	0.973	0.50 (0.43)	0.85	6102.7	818.00
7	10984.94	25.67	0.971	0.50 (0.43)	0.85	6130.3	12730.00
8	10909.16	27.75	0.929	0.50 (0.43)	0.86	6733.3	12710.00
9	10898.19	28.01	0.924	0.50 (0.43)	0.86	6803.1	430.00
10	10880.24	28.42	0.915	0.50 (0.43)	0.86	6916.0	300.00
11	10863.63	28.76	0.908	0.50 (0.43)	0.87	7008.2	320.00
12	10704.44	32.02	0.857	0.50 (0.44)	0.88	7838.3	600.00
13	10518.20	37.52	0.787	0.50 (0.45)	0.90	9315.4	390.00
14	9982.99	58.90	0.619	0.50 (0.47)	0.93	14983.2	11801.00
15	9773.26	70.14	0.578	0.50 (0.47)	0.94	18215.7	11500.00
16	9654.81	75.78	0.558	0.50 (0.47)	0.95	20150.8	11701.00
17	9488.31	81.97	0.537	0.50 (0.48)	0.95	22260.2	11000.00
18	9116.40	98.23	0.494	0.50 (0.48)	0.96	29125.8	12500.00
19	8914.68	104.36	0.482	0.50 (0.48)	0.97	31995.2	10900.00
20	8262.70	112.89	0.466	0.50 (0.48)	0.97	35324.4	11130.00
21	7582.60	124.19	0.447	0.50 (0.49)	0.97	38996.9	11620.00
22	6532.51	139.70	0.428	0.50 (0.49)	0.97	43522.7	12400.00
23	5688.71	150.85	0.414	0.50 (0.49)	0.97	45828.9	12201.00
24	5080.87	159.93	0.403	0.50 (0.49)	0.97	47119.5	12111.00
25	4161.96	175.23	0.385	0.50 (0.49)	0.97	49042.4	12261.00
26	3692.38	184.27	0.377	0.50 (0.49)	0.97	49853.5	10200.00
27	3125.67	199.27	0.369	0.50 (0.49)	0.97	51091.5	10300.00
28	2895.07	205.94	0.365	0.50 (0.49)	0.98	51443.7	12010.00
29	2423.70	225.94	0.354	0.50 (0.49)	0.98	51772.0	12000.00
30	1458.84	292.97	0.317	0.50 (0.49)	0.98	52442.8	10100.00

=====
 END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 128 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 5-YR EV FEB 2023 ROKAMOTO *

FILE NAME: RU05EV28.DAT
TIME/DATE OF STUDY: 08:56 02/08/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 5.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 2.715
- 2) 10.00; 1.802
- 3) 15.00; 1.320
- 4) 20.00; 1.130
- 5) 25.00; 0.985
- 6) 30.00; 0.883
- 7) 40.00; 0.756
- 8) 50.00; 0.673
- 9) 60.00; 0.612
- 10) 90.00; 0.510
- 11) 120.00; 0.452
- 12) 180.00; 0.379
- 13) 360.00; 0.281
- 14) 1200.00; 0.124

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:

- 1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: RU05EV27.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11064.04	18.04	0.50 (0.41)	0.83	3778.3	410.00
2	10704.44	32.02	0.50 (0.44)	0.88	7838.3	600.00
3	10518.20	37.52	0.50 (0.45)	0.90	9315.4	390.00
4	9982.99	58.90	0.50 (0.47)	0.93	14983.2	11801.00
5	9773.26	70.14	0.50 (0.47)	0.94	18215.7	11500.00
6	9654.81	75.78	0.50 (0.47)	0.95	20150.8	11701.00
7	9488.31	81.97	0.50 (0.48)	0.95	22260.2	11000.00
8	9116.40	98.23	0.50 (0.48)	0.96	29125.8	12500.00
9	8914.68	104.36	0.50 (0.48)	0.97	31995.2	10900.00
10	8262.70	112.89	0.50 (0.48)	0.97	35324.4	11130.00
11	7582.60	124.19	0.50 (0.49)	0.97	38996.9	11620.00
12	6532.51	139.70	0.50 (0.49)	0.97	43522.7	12400.00
13	5688.71	150.85	0.50 (0.49)	0.97	45828.9	12201.00
14	5080.87	159.93	0.50 (0.49)	0.97	47119.5	12111.00
15	4161.96	175.23	0.50 (0.49)	0.97	49042.4	12261.00
16	3692.38	184.27	0.50 (0.49)	0.97	49853.5	10200.00
17	3125.67	199.27	0.50 (0.49)	0.97	51091.5	10300.00
18	2895.07	205.94	0.50 (0.49)	0.98	51443.7	12010.00
19	2423.70	225.94	0.50 (0.49)	0.98	51772.0	12000.00
20	1458.84	292.97	0.50 (0.49)	0.98	52442.8	10100.00
TOTAL AREA (ACRES) =						52442.8

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P501XX05.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	132.46	14.68	0.50 (0.42)	0.84	171.0	50110.00
2	129.35	20.00	0.50 (0.43)	0.85	223.2	50100.00
TOTAL AREA (ACRES) =						223.2

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
------------------	------------	--------------	----------------------	----	---------------	-------------------

1 132.46 14.68 0.50(0.42) 0.84 171.0 50110.00
 2 129.35 20.00 0.50(0.43) 0.85 223.2 50100.00
 TOTAL AREA (ACRES) = 223.2

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	132.46	14.68	1.350	0.50(0.42)	0.84	171.0	50110.00
2	129.35	20.00	1.130	0.50(0.43)	0.85	223.2	50100.00

LONGEST FLOWPATH FROM NODE 50100.00 TO NODE 12800.00 = 4170.00 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11064.04	18.04	1.205	0.50(0.41)	0.83	3778.3	410.00
2	10704.44	32.02	0.857	0.50(0.44)	0.88	7838.3	600.00
3	10518.20	37.52	0.787	0.50(0.45)	0.90	9315.4	390.00
4	9982.99	58.90	0.619	0.50(0.47)	0.93	14983.2	11801.00
5	9773.26	70.14	0.578	0.50(0.47)	0.94	18215.7	11500.00
6	9654.81	75.78	0.558	0.50(0.47)	0.95	20150.8	11701.00
7	9488.31	81.97	0.537	0.50(0.48)	0.95	22260.2	11000.00
8	9116.40	98.23	0.494	0.50(0.48)	0.96	29125.8	12500.00
9	8914.68	104.36	0.482	0.50(0.48)	0.97	31995.2	10900.00
10	8262.70	112.89	0.466	0.50(0.48)	0.97	35324.4	11130.00
11	7582.60	124.19	0.447	0.50(0.49)	0.97	38996.9	11620.00
12	6532.51	139.70	0.428	0.50(0.49)	0.97	43522.7	12400.00
13	5688.71	150.85	0.414	0.50(0.49)	0.97	45828.9	12201.00
14	5080.87	159.93	0.403	0.50(0.49)	0.97	47119.5	12111.00
15	4161.96	175.23	0.385	0.50(0.49)	0.97	49042.4	12261.00
16	3692.38	184.27	0.377	0.50(0.49)	0.97	49853.5	10200.00
17	3125.67	199.27	0.369	0.50(0.49)	0.97	51091.5	10300.00
18	2895.07	205.94	0.365	0.50(0.49)	0.98	51443.7	12010.00
19	2423.70	225.94	0.354	0.50(0.49)	0.98	51772.0	12000.00
20	1458.84	292.97	0.317	0.50(0.49)	0.98	52442.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111772.49 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	10801.06	14.68	1.350	0.50(0.41)	0.83	3246.6	50110.00
2	11194.54	18.04	1.205	0.50(0.41)	0.83	3982.2	410.00
3	11142.90	20.00	1.130	0.50(0.42)	0.84	4571.5	50100.00
4	10783.75	32.02	0.857	0.50(0.44)	0.88	8061.5	600.00
5	10584.68	37.52	0.787	0.50(0.45)	0.89	9538.6	390.00
6	10018.47	58.90	0.619	0.50(0.47)	0.93	15206.4	11801.00
7	9801.19	70.14	0.578	0.50(0.47)	0.94	18438.9	11500.00
8	9679.21	75.78	0.558	0.50(0.47)	0.95	20374.0	11701.00
9	9508.85	81.97	0.537	0.50(0.48)	0.95	22483.4	11000.00
10	9129.96	98.23	0.494	0.50(0.48)	0.96	29349.0	12500.00
11	8927.91	104.36	0.482	0.50(0.48)	0.97	32218.4	10900.00
12	8275.48	112.89	0.466	0.50(0.48)	0.97	35547.6	11130.00
13	7594.86	124.19	0.447	0.50(0.49)	0.97	39220.1	11620.00

14	6544.26	139.70	0.428	0.50(0.49)	0.97	43745.9	12400.00
15	5700.08	150.85	0.414	0.50(0.49)	0.97	46052.1	12201.00
16	5091.94	159.93	0.403	0.50(0.49)	0.97	47342.7	12111.00
17	4172.52	175.23	0.385	0.50(0.49)	0.97	49265.6	12261.00
18	3702.71	184.27	0.377	0.50(0.49)	0.97	50076.7	10200.00
19	3135.79	199.27	0.369	0.50(0.49)	0.97	51314.7	10300.00
20	2905.09	205.94	0.365	0.50(0.49)	0.97	51666.9	12010.00
21	2433.42	225.94	0.354	0.50(0.49)	0.97	51995.2	12000.00
22	1467.55	292.97	0.317	0.50(0.49)	0.97	52666.0	10100.00

TOTAL AREA (ACRES) = 52666.0

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 11194.54 Tc (MIN.) = 18.039
 EFFECTIVE AREA (ACRES) = 3982.19 AREA-AVERAGED Fm (INCH/HR) = 0.41
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.84
 TOTAL AREA (ACRES) = 52666.0
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111772.49 FEET.

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 52666.0 TC (MIN.) = 18.04
 EFFECTIVE AREA (ACRES) = 3982.19 AREA-AVERAGED Fm (INCH/HR) = 0.41
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.828
 PEAK FLOW RATE (CFS) = 11194.54

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	10801.06	14.68	1.350	0.50(0.41)	0.83	3246.6	50110.00
2	11194.54	18.04	1.205	0.50(0.41)	0.83	3982.2	410.00
3	11142.90	20.00	1.130	0.50(0.42)	0.84	4571.5	50100.00
4	10783.75	32.02	0.857	0.50(0.44)	0.88	8061.5	600.00
5	10584.68	37.52	0.787	0.50(0.45)	0.89	9538.6	390.00
6	10018.47	58.90	0.619	0.50(0.47)	0.93	15206.4	11801.00
7	9801.19	70.14	0.578	0.50(0.47)	0.94	18438.9	11500.00
8	9679.21	75.78	0.558	0.50(0.47)	0.95	20374.0	11701.00
9	9508.85	81.97	0.537	0.50(0.48)	0.95	22483.4	11000.00
10	9129.96	98.23	0.494	0.50(0.48)	0.96	29349.0	12500.00
11	8927.91	104.36	0.482	0.50(0.48)	0.97	32218.4	10900.00
12	8275.48	112.89	0.466	0.50(0.48)	0.97	35547.6	11130.00
13	7594.86	124.19	0.447	0.50(0.49)	0.97	39220.1	11620.00
14	6544.26	139.70	0.428	0.50(0.49)	0.97	43745.9	12400.00
15	5700.08	150.85	0.414	0.50(0.49)	0.97	46052.1	12201.00
16	5091.94	159.93	0.403	0.50(0.49)	0.97	47342.7	12111.00
17	4172.52	175.23	0.385	0.50(0.49)	0.97	49265.6	12261.00
18	3702.71	184.27	0.377	0.50(0.49)	0.97	50076.7	10200.00
19	3135.79	199.27	0.369	0.50(0.49)	0.97	51314.7	10300.00
20	2905.09	205.94	0.365	0.50(0.49)	0.97	51666.9	12010.00
21	2433.42	225.94	0.354	0.50(0.49)	0.97	51995.2	12000.00
22	1467.55	292.97	0.317	0.50(0.49)	0.97	52666.0	10100.00

END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 129 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 5-YR EV FEB 2023 ROKAMOTO *

FILE NAME: RU05EV29.DAT
TIME/DATE OF STUDY: 08:57 02/08/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 5.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 2.698
- 2) 10.00; 1.792
- 3) 15.00; 1.316
- 4) 20.00; 1.127
- 5) 25.00; 0.982
- 6) 30.00; 0.881
- 7) 40.00; 0.754
- 8) 50.00; 0.671
- 9) 60.00; 0.610
- 10) 90.00; 0.507
- 11) 120.00; 0.449
- 12) 180.00; 0.377
- 13) 360.00; 0.279
- 14) 1200.00; 0.123

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN CROSSFALL (FT)	TO STREET- / SIDE/ WAY	CROSSFALL (FT)	STREET-CROSSFALL: IN- / OUT- / PARK- SIDE (FT)	CURB HEIGHT (FT)	GUTTER WIDTH (FT)	GEOMETRIES: LIP (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150	

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU05EV28.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11194.54	18.04	0.50 (0.41)	0.83	3982.2	410.00
2	10783.75	32.02	0.50 (0.44)	0.88	8061.5	600.00
3	10584.68	37.52	0.50 (0.45)	0.89	9538.6	390.00
4	10018.47	58.90	0.50 (0.47)	0.93	15206.4	11801.00
5	9801.19	70.14	0.50 (0.47)	0.94	18438.9	11500.00
6	9679.21	75.78	0.50 (0.47)	0.95	20374.0	11701.00
7	9508.85	81.97	0.50 (0.48)	0.95	22483.4	11000.00
8	9129.96	98.23	0.50 (0.48)	0.96	29349.0	12500.00
9	8927.91	104.36	0.50 (0.48)	0.97	32218.4	10900.00
10	8275.48	112.89	0.50 (0.48)	0.97	35547.6	11130.00
11	7594.86	124.19	0.50 (0.49)	0.97	39220.1	11620.00
12	6544.26	139.70	0.50 (0.49)	0.97	43745.9	12400.00
13	5700.08	150.85	0.50 (0.49)	0.97	46052.1	12010.00
14	5091.94	159.93	0.50 (0.49)	0.97	47342.7	12111.00
15	4172.52	175.23	0.50 (0.49)	0.97	49265.6	12261.00
16	3702.71	184.27	0.50 (0.49)	0.97	50076.7	10200.00
17	3135.79	199.27	0.50 (0.49)	0.97	51314.7	10300.00
18	2905.09	205.94	0.50 (0.49)	0.97	51666.9	12010.00
19	2433.42	225.94	0.50 (0.49)	0.97	51995.2	12000.00
20	1467.55	292.97	0.50 (0.49)	0.97	52666.0	10100.00
TOTAL AREA (ACRES) =						52666.0

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11194.54	18.04	0.50 (0.41)	0.83	3982.2	410.00
2	10783.75	32.02	0.50 (0.44)	0.88	8061.5	600.00
3	10584.68	37.52	0.50 (0.45)	0.89	9538.6	390.00
4	10018.47	58.90	0.50 (0.47)	0.93	15206.4	11801.00
5	9801.19	70.14	0.50 (0.47)	0.94	18438.9	11500.00
6	9679.21	75.78	0.50 (0.47)	0.95	20374.0	11701.00
7	9508.85	81.97	0.50 (0.48)	0.95	22483.4	11000.00
8	9129.96	98.23	0.50 (0.48)	0.96	29349.0	12500.00
9	8927.91	104.36	0.50 (0.48)	0.97	32218.4	10900.00
10	8275.48	112.89	0.50 (0.48)	0.97	35547.6	11130.00
11	7594.86	124.19	0.50 (0.49)	0.97	39220.1	11620.00
12	6544.26	139.70	0.50 (0.49)	0.97	43745.9	12400.00
13	5700.08	150.85	0.50 (0.49)	0.97	46052.1	12201.00

```

14 5091.94 159.93 0.50( 0.49) 0.97 47342.7 12111.00
15 4172.52 175.23 0.50( 0.49) 0.97 49265.6 12261.00
16 3702.71 184.27 0.50( 0.49) 0.97 50076.7 10200.00
17 3135.79 199.27 0.50( 0.49) 0.97 51314.7 10300.00
18 2905.09 205.94 0.50( 0.49) 0.97 51666.9 12010.00
19 2433.42 225.94 0.50( 0.49) 0.97 51995.2 12000.00
20 1467.55 292.97 0.50( 0.49) 0.97 52666.0 10100.00
TOTAL AREA(ACRES) = 52666.0

```

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 12800.00 TO NODE 12901.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

```

ELEVATION DATA: UPSTREAM(FEET) = 240.00 DOWNSTREAM(FEET) = 216.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 3120.28 CHANNEL SLOPE = 0.0077
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
CHANNEL FLOW THRU SUBAREA(CFS) = 11194.54
FLOW VELOCITY(FEET/SEC.) = 16.20 FLOW DEPTH(FEET) = 15.18
TRAVEL TIME(MIN.) = 3.21 Tc(MIN.) = 21.25
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12901.00 = 114892.77 FEET.

```

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11194.54	21.25	1.091	0.50(0.41)	0.83	3982.2	410.00
2	10783.75	35.26	0.814	0.50(0.44)	0.88	8061.5	600.00
3	10584.68	40.78	0.748	0.50(0.45)	0.89	9538.6	390.00
4	10018.47	62.20	0.602	0.50(0.47)	0.93	15206.4	11801.00
5	9801.19	73.46	0.564	0.50(0.47)	0.94	18438.9	11500.00
6	9679.21	79.11	0.544	0.50(0.47)	0.95	20374.0	11701.00
7	9508.85	85.32	0.523	0.50(0.48)	0.95	22483.4	11000.00
8	9129.96	101.61	0.485	0.50(0.48)	0.96	29349.0	12500.00
9	8927.91	107.75	0.473	0.50(0.48)	0.97	32218.4	10900.00
10	8275.48	116.35	0.456	0.50(0.48)	0.97	35547.6	11130.00
11	7594.86	127.73	0.440	0.50(0.49)	0.97	39220.1	11620.00
12	6544.26	143.37	0.421	0.50(0.49)	0.97	43745.9	12400.00
13	5700.08	154.65	0.407	0.50(0.49)	0.97	46052.1	12201.00
14	5091.94	163.84	0.396	0.50(0.49)	0.97	47342.7	12111.00
15	4172.52	179.34	0.378	0.50(0.49)	0.97	49265.6	12261.00
16	3702.71	188.50	0.372	0.50(0.49)	0.97	50076.7	10200.00
17	3135.79	203.69	0.364	0.50(0.49)	0.97	51314.7	10300.00
18	2905.09	210.44	0.360	0.50(0.49)	0.97	51666.9	12010.00
19	2433.42	230.64	0.349	0.50(0.49)	0.97	51995.2	12000.00
20	1467.55	298.30	0.313	0.50(0.49)	0.97	52666.0	10100.00

NEW PEAK FLOW DATA ARE:

```

PEAK FLOW RATE(CFS) = 11194.54 Tc(MIN.) = 21.25
AREA-AVERAGED Fm(INCH/HR) = 0.41 AREA-AVERAGED Fp(INCH/HR) = 0.50
AREA-AVERAGED Ap = 0.83 EFFECTIVE AREA(ACRES) = 3982.19

```

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 21.25

* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.091

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	14.30	0.50	0.100	-
USER-DEFINED	-	9.40	0.50	0.850	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.397

SUBAREA AREA(ACRES) = 23.70 SUBAREA RUNOFF(CFS) = 19.03

EFFECTIVE AREA(ACRES) = 4005.89 AREA-AVERAGED Fm(INCH/HR) = 0.41

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.83

TOTAL AREA(ACRES) = 52689.7 PEAK FLOW RATE(CFS) = 11194.54

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 21.25

* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.091

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.20	0.50	0.100	-
USER-DEFINED	-	0.40	0.50	0.500	-
USER-DEFINED	-	0.50	0.50	0.900	-
USER-DEFINED	-	0.60	0.50	1.000	-
USER-DEFINED	-	0.70	0.50	0.100	-
USER-DEFINED	-	0.70	0.50	0.900	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.635

SUBAREA AREA(ACRES) = 3.10 SUBAREA RUNOFF(CFS) = 2.16

EFFECTIVE AREA(ACRES) = 4008.99 AREA-AVERAGED Fm(INCH/HR) = 0.41

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.83

TOTAL AREA(ACRES) = 52692.8 PEAK FLOW RATE(CFS) = 11194.54

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 21.25

* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.091

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.70	0.50	0.850	-
USER-DEFINED	-	1.00	0.50	1.000	-
USER-DEFINED	-	1.40	0.50	1.000	-
USER-DEFINED	-	1.50	0.50	1.000	-

```

USER-DEFINED          -      1.70      0.50      0.100      -
USER-DEFINED          -      2.90      0.50      1.000      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.822
SUBAREA AREA(ACRES) = 9.20      SUBAREA RUNOFF(CFS) = 5.63
EFFECTIVE AREA(ACRES) = 4018.19      AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50      AREA-AVERAGED Ap = 0.83
TOTAL AREA(ACRES) = 52702.0      PEAK FLOW RATE(CFS) = 11194.54
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
-----

```

```

MAINLINE Tc(MIN.) = 21.25
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.091
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp      Ap      SCS
LAND USE              GROUP  (ACRES)  (INCH/HR)  (DECIMAL)  CN
USER-DEFINED          -      3.60      0.50      1.000      -
USER-DEFINED          -      3.70      0.50      0.500      -
USER-DEFINED          -      4.10      0.50      0.900      -
USER-DEFINED          -      5.40      0.50      0.900      -
USER-DEFINED          -      6.70      0.50      1.000      -
USER-DEFINED          -      12.00     0.50      1.000      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.921
SUBAREA AREA(ACRES) = 35.50      SUBAREA RUNOFF(CFS) = 20.13
EFFECTIVE AREA(ACRES) = 4053.69      AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50      AREA-AVERAGED Ap = 0.83
TOTAL AREA(ACRES) = 52737.5      PEAK FLOW RATE(CFS) = 11194.54
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
-----

```

```

MAINLINE Tc(MIN.) = 21.25
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.091
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp      Ap      SCS
LAND USE              GROUP  (ACRES)  (INCH/HR)  (DECIMAL)  CN
USER-DEFINED          -      12.90     0.50      1.000      -
USER-DEFINED          -      38.60     0.50      0.850      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.888
SUBAREA AREA(ACRES) = 51.50      SUBAREA RUNOFF(CFS) = 29.98
EFFECTIVE AREA(ACRES) = 4105.19      AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50      AREA-AVERAGED Ap = 0.83
TOTAL AREA(ACRES) = 52789.0      PEAK FLOW RATE(CFS) = 11194.54
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 12901.00 TO NODE 12902.00 IS CODE = 51
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

```

```

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 216.00      DOWNSTREAM(FEET) = 215.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 122.04      CHANNEL SLOPE = 0.0082
CHANNEL BASE(FEET) = 0.00      "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030      MAXIMUM DEPTH(FEET) = 20.00
CHANNEL FLOW THRU SUBAREA(CFS) = 11194.54
FLOW VELOCITY(FEET/SEC.) = 16.59      FLOW DEPTH(FEET) = 15.00
TRAVEL TIME(MIN.) = 0.12      Tc(MIN.) = 21.37
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115014.81 FEET.

```

```

** PEAK FLOW RATE TABLE **

```

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11194.54	21.37	1.087	0.50(0.41)	0.83	4105.2	410.00
2	10783.75	35.38	0.813	0.50(0.44)	0.88	8184.5	600.00
3	10584.68	40.90	0.747	0.50(0.45)	0.89	9661.6	390.00
4	10018.47	62.33	0.602	0.50(0.47)	0.93	15329.4	11801.00
5	9801.19	73.58	0.563	0.50(0.47)	0.94	18561.9	11500.00
6	9679.21	79.23	0.544	0.50(0.47)	0.95	20497.0	11701.00
7	9508.85	85.44	0.523	0.50(0.48)	0.95	22606.4	11000.00
8	9129.96	101.74	0.484	0.50(0.48)	0.96	29472.0	12500.00
9	8927.91	107.88	0.472	0.50(0.48)	0.97	32341.4	10900.00
10	8275.48	116.48	0.456	0.50(0.48)	0.97	35670.6	11130.00
11	7594.86	127.86	0.440	0.50(0.49)	0.97	39343.1	11620.00
12	6544.26	143.51	0.421	0.50(0.49)	0.97	43868.9	12400.00
13	5700.08	154.79	0.407	0.50(0.49)	0.97	46175.1	12201.00
14	5091.94	163.99	0.396	0.50(0.49)	0.97	47465.7	12111.00
15	4172.52	179.50	0.378	0.50(0.49)	0.97	49388.6	12261.00
16	3702.71	188.66	0.372	0.50(0.49)	0.97	50199.7	10200.00
17	3135.79	203.85	0.364	0.50(0.49)	0.97	51437.7	10300.00
18	2905.09	210.61	0.360	0.50(0.49)	0.97	51789.9	12010.00
19	2433.42	230.82	0.349	0.50(0.49)	0.97	52118.2	12000.00
20	1467.55	298.51	0.312	0.50(0.49)	0.97	52789.0	10100.00

```

NEW PEAK FLOW DATA ARE:
PEAK FLOW RATE(CFS) = 11194.54      Tc(MIN.) = 21.37
AREA-AVERAGED Fm(INCH/HR) = 0.41      AREA-AVERAGED Fp(INCH/HR) = 0.50
AREA-AVERAGED Ap = 0.83      EFFECTIVE AREA(ACRES) = 4105.19

```

```

*****
FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 15.1
-----

```

```

>>>>DEFINE MEMORY BANK # 1 <<<<
-----

```

```

PEAK FLOWRATE TABLE FILE NAME: P503XX05.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

```

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE	
1	584.35	21.36	0.50(0.37)	0.74	995.0	50320.00	
2	579.24	23.33	0.50(0.37)	0.74	1063.4	50240.00	
3	575.13	24.07	0.50(0.37)	0.74	1088.2	50330.00	
4	554.36	27.47	0.50(0.37)	0.74	1186.0	50280.00	
5	543.27	28.48	0.50(0.37)	0.74	1207.3	50300.00	
6	509.57	31.04	0.50(0.37)	0.74	1246.1	50220.00	
7	422.48	37.74	0.50(0.37)	0.74	1295.8	50260.00	
8	402.34	39.31	0.50(0.37)	0.74	1298.6	50200.00	
TOTAL AREA(ACRES) =		1298.6					

FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11194.54	21.37	1.087	0.50 (0.41)	0.83	4105.2	410.00
2	10783.75	35.38	0.813	0.50 (0.44)	0.88	8184.5	600.00
3	10584.68	40.90	0.747	0.50 (0.45)	0.89	9661.6	390.00
4	10018.47	62.33	0.602	0.50 (0.47)	0.93	15329.4	11801.00
5	9801.19	73.58	0.563	0.50 (0.47)	0.94	18561.9	11500.00
6	9679.21	79.23	0.544	0.50 (0.47)	0.95	20497.0	11701.00
7	9508.85	85.44	0.523	0.50 (0.48)	0.95	22606.4	11000.00
8	9129.96	101.74	0.484	0.50 (0.48)	0.96	29472.0	12500.00
9	8927.91	107.88	0.472	0.50 (0.48)	0.97	32341.4	10900.00
10	8275.48	116.48	0.456	0.50 (0.48)	0.97	35670.6	11130.00
11	7594.86	127.86	0.440	0.50 (0.49)	0.97	39343.1	11620.00
12	6544.26	143.51	0.421	0.50 (0.49)	0.97	43868.9	12400.00
13	5700.08	154.79	0.407	0.50 (0.49)	0.97	46175.1	12201.00
14	5091.94	163.99	0.396	0.50 (0.49)	0.97	47465.7	12111.00
15	4172.52	179.50	0.378	0.50 (0.49)	0.97	49388.6	12261.00
16	3702.71	188.66	0.372	0.50 (0.49)	0.97	50199.7	10200.00
17	3135.79	203.85	0.364	0.50 (0.49)	0.97	51437.7	10300.00
18	2905.09	210.61	0.360	0.50 (0.49)	0.97	51789.9	12010.00
19	2433.42	230.82	0.349	0.50 (0.49)	0.97	52118.2	12000.00
20	1467.55	298.51	0.312	0.50 (0.49)	0.97	52789.0	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115014.81 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	584.35	21.36	1.087	0.50 (0.37)	0.74	995.0	50320.00
2	579.24	23.33	1.030	0.50 (0.37)	0.74	1063.4	50240.00
3	575.13	24.07	1.009	0.50 (0.37)	0.74	1088.2	50330.00
4	554.36	27.47	0.932	0.50 (0.37)	0.74	1186.0	50280.00
5	543.27	28.48	0.912	0.50 (0.37)	0.74	1207.3	50300.00
6	509.57	31.04	0.868	0.50 (0.37)	0.74	1246.1	50220.00
7	422.48	37.74	0.783	0.50 (0.37)	0.74	1295.8	50260.00
8	402.34	39.31	0.763	0.50 (0.37)	0.74	1298.6	50200.00

LONGEST FLOWPATH FROM NODE 50220.00 TO NODE 12902.00 = 17597.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11778.50	21.36	1.087	0.50 (0.41)	0.81	5098.4	50320.00
2	11778.87	21.37	1.087	0.50 (0.41)	0.81	5100.5	410.00
3	11716.34	23.33	1.030	0.50 (0.41)	0.82	5738.9	50240.00
4	11690.57	24.07	1.009	0.50 (0.41)	0.82	5979.0	50330.00
5	11570.22	27.47	0.932	0.50 (0.42)	0.83	7065.6	50280.00
6	11529.24	28.48	0.912	0.50 (0.42)	0.83	7383.6	50300.00
7	11420.50	31.04	0.868	0.50 (0.42)	0.84	8167.7	50220.00
8	11236.94	35.38	0.813	0.50 (0.43)	0.86	9462.7	600.00
9	11121.07	37.74	0.783	0.50 (0.43)	0.87	10112.1	50260.00
10	11044.26	39.31	0.763	0.50 (0.44)	0.87	10535.5	50200.00
11	10970.38	40.90	0.747	0.50 (0.44)	0.88	10960.2	390.00

12	10255.72	62.33	0.602	0.50 (0.46)	0.92	16628.0	11801.00
13	9998.75	73.58	0.563	0.50 (0.46)	0.93	19860.5	11500.00
14	9856.84	79.23	0.544	0.50 (0.47)	0.94	21795.6	11701.00
15	9664.58	85.44	0.523	0.50 (0.47)	0.94	23905.0	11000.00
16	9258.42	101.74	0.484	0.50 (0.48)	0.95	30770.6	12500.00
17	9053.22	107.88	0.472	0.50 (0.48)	0.96	33640.0	10900.00
18	8396.38	116.48	0.456	0.50 (0.48)	0.96	36969.2	11130.00
19	7711.45	127.86	0.440	0.50 (0.48)	0.96	40641.7	11620.00
20	6655.87	143.51	0.421	0.50 (0.48)	0.97	45167.5	12400.00
21	5808.10	154.79	0.407	0.50 (0.48)	0.97	47473.7	12201.00
22	5197.03	163.99	0.396	0.50 (0.48)	0.97	48764.3	12111.00
23	4272.67	179.50	0.378	0.50 (0.48)	0.97	50687.2	12261.00
24	3801.46	188.66	0.372	0.50 (0.48)	0.97	51498.3	10200.00
25	3232.34	203.85	0.364	0.50 (0.48)	0.97	52736.3	10300.00
26	3000.66	210.61	0.360	0.50 (0.48)	0.97	53088.5	12010.00
27	2526.08	230.82	0.349	0.50 (0.48)	0.97	53416.8	12000.00
28	1550.44	298.51	0.312	0.50 (0.48)	0.97	54087.6	10100.00

TOTAL AREA (ACRES) = 54087.6

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 11778.87 Tc(MIN.) = 21.372

EFFECTIVE AREA(ACRES) = 5100.54 AREA-AVERAGED Fm(INCH/HR) = 0.41

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.81

TOTAL AREA(ACRES) = 54087.6

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115014.81 FEET.

FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 12902.00 TO NODE 12903.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 215.00 DOWNSTREAM(FEET) = 214.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 895.53 CHANNEL SLOPE = 0.0011

CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00

==>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL

CAPACITY(NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM

ALLOWABLE DEPTH).

AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM

ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

CHANNEL FLOW THRU SUBAREA(CFS) = 11778.87

FLOW VELOCITY(FEET/SEC.) = 9.82 FLOW DEPTH(FEET) = 20.00

TRAVEL TIME(MIN.) = 1.52 Tc(MIN.) = 22.89

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115910.34 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11778.50	22.88	1.043	0.50 (0.41)	0.81	5098.4	50320.00

2	11778.87	22.89	1.043	0.50 (0.41)	0.81	5100.5	410.00
3	11716.34	24.86	0.986	0.50 (0.41)	0.82	5738.9	50240.00
4	11690.57	25.60	0.970	0.50 (0.41)	0.82	5979.0	50330.00
5	11570.22	29.01	0.901	0.50 (0.42)	0.83	7065.6	50280.00
6	11529.24	30.04	0.881	0.50 (0.42)	0.83	7383.6	50300.00
7	11420.50	32.61	0.848	0.50 (0.42)	0.84	8167.7	50220.00
8	11236.94	36.97	0.792	0.50 (0.43)	0.86	9462.7	600.00
9	11121.07	39.35	0.762	0.50 (0.43)	0.87	10112.1	50260.00
10	11044.26	40.94	0.746	0.50 (0.44)	0.87	10535.5	50200.00
11	10970.38	42.53	0.733	0.50 (0.44)	0.88	10960.2	390.00
12	10255.72	64.08	0.596	0.50 (0.46)	0.92	16628.0	11801.00
13	9998.75	75.37	0.557	0.50 (0.46)	0.93	19860.5	11500.00
14	9856.84	81.05	0.538	0.50 (0.47)	0.94	21795.6	11701.00
15	9664.58	87.30	0.516	0.50 (0.47)	0.94	23905.0	11000.00
16	9258.42	103.68	0.481	0.50 (0.48)	0.95	30770.6	12500.00
17	9053.22	109.86	0.469	0.50 (0.48)	0.96	33640.0	10900.00
18	8396.38	118.52	0.452	0.50 (0.48)	0.96	36969.2	11130.00
19	7711.45	129.95	0.437	0.50 (0.48)	0.96	40641.7	11620.00
20	6655.87	145.68	0.418	0.50 (0.48)	0.97	45167.5	12400.00
21	5808.10	157.03	0.405	0.50 (0.48)	0.97	47473.7	12201.00
22	5197.03	166.30	0.393	0.50 (0.48)	0.97	48764.3	12111.00
23	4272.67	181.91	0.376	0.50 (0.48)	0.97	50687.2	12261.00
24	3801.46	191.15	0.371	0.50 (0.48)	0.97	51498.3	10200.00
25	3232.34	206.45	0.363	0.50 (0.48)	0.97	52736.3	10300.00
26	3000.66	213.26	0.359	0.50 (0.48)	0.97	53088.5	12010.00
27	2526.08	233.58	0.348	0.50 (0.48)	0.97	53416.8	12000.00
28	1550.44	301.62	0.311	0.50 (0.48)	0.97	54087.6	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 11778.87 Tc(MIN.) = 22.89

AREA-AVERAGED Fm(INCH/HR) = 0.41 AREA-AVERAGED Fp(INCH/HR) = 0.50

AREA-AVERAGED Ap = 0.81 EFFECTIVE AREA(ACRES) = 5100.54

FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P504XX05.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	46.39	15.05	1.314	0.50 (0.47)	0.94	70.7	50400.00
TOTAL AREA(ACRES) =							70.7

FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11778.50	22.88	1.043	0.50 (0.41)	0.81	5098.4	50320.00
2	11778.87	22.89	1.043	0.50 (0.41)	0.81	5100.5	410.00
3	11716.34	24.86	0.986	0.50 (0.41)	0.82	5738.9	50240.00
4	11690.57	25.60	0.970	0.50 (0.41)	0.82	5979.0	50330.00
5	11570.22	29.01	0.901	0.50 (0.42)	0.83	7065.6	50280.00

6	11529.24	30.04	0.881	0.50 (0.42)	0.83	7383.6	50300.00
7	11420.50	32.61	0.848	0.50 (0.42)	0.84	8167.7	50220.00
8	11236.94	36.97	0.792	0.50 (0.43)	0.86	9462.7	600.00
9	11121.07	39.35	0.762	0.50 (0.43)	0.87	10112.1	50260.00
10	11044.26	40.94	0.746	0.50 (0.44)	0.87	10535.5	50200.00
11	10970.38	42.53	0.733	0.50 (0.44)	0.88	10960.2	390.00
12	10255.72	64.08	0.596	0.50 (0.46)	0.92	16628.0	11801.00
13	9998.75	75.37	0.557	0.50 (0.46)	0.93	19860.5	11500.00
14	9856.84	81.05	0.538	0.50 (0.47)	0.94	21795.6	11701.00
15	9664.58	87.30	0.516	0.50 (0.47)	0.94	23905.0	11000.00
16	9258.42	103.68	0.481	0.50 (0.48)	0.95	30770.6	12500.00
17	9053.22	109.86	0.469	0.50 (0.48)	0.96	33640.0	10900.00
18	8396.38	118.52	0.452	0.50 (0.48)	0.96	36969.2	11130.00
19	7711.45	129.95	0.437	0.50 (0.48)	0.96	40641.7	11620.00
20	6655.87	145.68	0.418	0.50 (0.48)	0.97	45167.5	12400.00
21	5808.10	157.03	0.405	0.50 (0.48)	0.97	47473.7	12201.00
22	5197.03	166.30	0.393	0.50 (0.48)	0.97	48764.3	12111.00
23	4272.67	181.91	0.376	0.50 (0.48)	0.97	50687.2	12261.00
24	3801.46	191.15	0.371	0.50 (0.48)	0.97	51498.3	10200.00
25	3232.34	206.45	0.363	0.50 (0.48)	0.97	52736.3	10300.00
26	3000.66	213.26	0.359	0.50 (0.48)	0.97	53088.5	12010.00
27	2526.08	233.58	0.348	0.50 (0.48)	0.97	53416.8	12000.00
28	1550.44	301.62	0.311	0.50 (0.48)	0.97	54087.6	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115910.34 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	46.39	15.05	1.314	0.50 (0.47)	0.94	70.7	50400.00

LONGEST FLOWPATH FROM NODE 50400.00 TO NODE 12903.00 = 3607.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11079.87	15.05	1.314	0.50 (0.41)	0.81	3424.0	50400.00
2	11810.03	22.88	1.043	0.50 (0.41)	0.81	5169.1	50320.00
3	11810.39	22.89	1.043	0.50 (0.41)	0.81	5171.2	410.00
4	11744.73	24.86	0.986	0.50 (0.41)	0.82	5809.6	50240.00
5	11718.06	25.60	0.970	0.50 (0.41)	0.82	6049.7	50330.00
6	11593.93	29.01	0.901	0.50 (0.42)	0.83	7136.3	50280.00
7	11551.83	30.04	0.881	0.50 (0.42)	0.84	7454.3	50300.00
8	11441.29	32.61	0.848	0.50 (0.42)	0.84	8238.4	50220.00
9	11254.69	36.97	0.792	0.50 (0.43)	0.86	9533.4	600.00
10	11137.17	39.35	0.762	0.50 (0.43)	0.87	10182.8	50260.00
11	11059.48	40.94	0.746	0.50 (0.44)	0.87	10606.2	50200.00
12	10984.87	42.53	0.733	0.50 (0.44)	0.88	11030.9	390.00
13	10262.69	64.08	0.596	0.50 (0.46)	0.92	16698.7	11801.00
14	10003.59	75.37	0.557	0.50 (0.46)	0.93	19931.2	11500.00
15	9860.61	81.05	0.538	0.50 (0.47)	0.94	21866.3	11701.00
16	9667.17	87.30	0.516	0.50 (0.47)	0.94	23975.7	11000.00
17	9260.06	103.68	0.481	0.50 (0.48)	0.95	30841.3	12500.00
18	9054.82	109.86	0.469	0.50 (0.48)	0.96	33710.7	10900.00
19	8397.92	118.52	0.452	0.50 (0.48)	0.96	37039.9	11130.00
20	7712.95	129.95	0.437	0.50 (0.48)	0.96	40712.4	11620.00
21	6657.30	145.68	0.418	0.50 (0.48)	0.97	45238.2	12400.00
22	5809.48	157.03	0.405	0.50 (0.48)	0.97	47544.4	12201.00
23	5198.38	166.30	0.393	0.50 (0.48)	0.97	48835.0	12111.00
24	4273.96	181.91	0.376	0.50 (0.48)	0.97	50757.9	12261.00

25 3802.73 191.15 0.371 0.50(0.48) 0.97 51569.0 10200.00
 26 3233.58 206.45 0.363 0.50(0.48) 0.97 52807.0 10300.00
 27 3001.89 213.26 0.359 0.50(0.48) 0.97 53159.2 12010.00
 28 2527.27 233.58 0.348 0.50(0.48) 0.97 53487.5 12000.00
 29 1551.50 301.62 0.311 0.50(0.48) 0.97 54158.3 10100.00
 TOTAL AREA (ACRES) = 54158.3

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 11810.39 Tc(MIN.) = 22.893
 EFFECTIVE AREA(ACRES) = 5171.25 AREA-AVERAGED Fm(INCH/HR) = 0.41
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.81
 TOTAL AREA(ACRES) = 54158.3
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115910.34 FEET.

 FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

 FLOW PROCESS FROM NODE 12903.00 TO NODE 12904.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 214.00 DOWNSTREAM(FEET) = 213.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 767.57 CHANNEL SLOPE = 0.0013
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00

==>>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL
 CAPACITY(NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM
 ALLOWABLE DEPTH).
 AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM
 ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

CHANNEL FLOW THRU SUBAREA(CFS) = 11810.39
 FLOW VELOCITY(FEET/SEC.) = 9.84 FLOW DEPTH(FEET) = 20.00
 TRAVEL TIME(MIN.) = 1.30 Tc(MIN.) = 24.19
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116677.91 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11079.87	16.44	1.262	0.50(0.41)	0.81	3424.0	50400.00
2	11810.03	24.18	1.006	0.50(0.41)	0.81	5169.1	50320.00
3	11810.39	24.19	1.005	0.50(0.41)	0.81	5171.2	410.00
4	11744.73	26.17	0.958	0.50(0.41)	0.82	5809.6	50240.00
5	11718.06	26.91	0.943	0.50(0.41)	0.82	6049.7	50330.00
6	11593.93	30.34	0.877	0.50(0.42)	0.83	7136.3	50280.00
7	11551.83	31.37	0.864	0.50(0.42)	0.84	7454.3	50300.00
8	11441.29	33.95	0.831	0.50(0.42)	0.84	8238.4	50220.00
9	11254.69	38.34	0.775	0.50(0.43)	0.86	9533.4	600.00
10	11137.17	40.73	0.748	0.50(0.43)	0.87	10182.8	50260.00
11	11059.48	42.32	0.735	0.50(0.44)	0.87	10606.2	50200.00
12	10984.87	43.93	0.721	0.50(0.44)	0.88	11030.9	390.00
13	10262.69	65.57	0.591	0.50(0.46)	0.92	16698.7	11801.00

14 10003.59 76.91 0.552 0.50(0.46) 0.93 19931.2 11500.00
 15 9860.61 82.61 0.532 0.50(0.47) 0.94 21866.3 11701.00
 16 9667.17 88.89 0.511 0.50(0.47) 0.94 23975.7 11000.00
 17 9260.06 105.29 0.477 0.50(0.48) 0.95 30841.3 12500.00
 18 9054.82 111.48 0.465 0.50(0.48) 0.96 33710.7 10900.00
 19 8397.92 120.17 0.449 0.50(0.48) 0.96 37039.9 11130.00
 20 7712.95 131.63 0.435 0.50(0.48) 0.96 40712.4 11620.00
 21 6657.30 147.43 0.416 0.50(0.48) 0.97 45238.2 12400.00
 22 5809.48 158.84 0.402 0.50(0.48) 0.97 47544.4 12201.00
 23 5198.38 168.16 0.391 0.50(0.48) 0.97 48835.0 12111.00
 24 4273.96 183.87 0.375 0.50(0.48) 0.97 50757.9 12261.00
 25 3802.73 193.16 0.370 0.50(0.48) 0.97 51569.0 10200.00
 26 3233.58 208.54 0.361 0.50(0.48) 0.97 52807.0 10300.00
 27 3001.89 215.39 0.358 0.50(0.48) 0.97 53159.2 12010.00
 28 2527.27 235.81 0.347 0.50(0.48) 0.97 53487.5 12000.00
 29 1551.50 304.14 0.309 0.50(0.48) 0.97 54158.3 10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 11810.39 Tc(MIN.) = 24.19
 AREA-AVERAGED Fm(INCH/HR) = 0.41 AREA-AVERAGED Fp(INCH/HR) = 0.50
 AREA-AVERAGED Ap = 0.81 EFFECTIVE AREA(ACRES) = 5171.25

 FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 3B05EVRL.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	169.21	19.05	0.50(0.22)	0.43	198.6	203.00
2	167.61	21.45	0.50(0.21)	0.43	213.7	210.00
TOTAL AREA(ACRES) =			213.7			

 FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11079.87	16.44	1.262	0.50(0.41)	0.81	3424.0	50400.00
2	11810.03	24.18	1.006	0.50(0.41)	0.81	5169.1	50320.00
3	11810.39	24.19	1.005	0.50(0.41)	0.81	5171.2	410.00
4	11744.73	26.17	0.958	0.50(0.41)	0.82	5809.6	50240.00
5	11718.06	26.91	0.943	0.50(0.41)	0.82	6049.7	50330.00
6	11593.93	30.34	0.877	0.50(0.42)	0.83	7136.3	50280.00
7	11551.83	31.37	0.864	0.50(0.42)	0.84	7454.3	50300.00
8	11441.29	33.95	0.831	0.50(0.42)	0.84	8238.4	50220.00
9	11254.69	38.34	0.775	0.50(0.43)	0.86	9533.4	600.00
10	11137.17	40.73	0.748	0.50(0.43)	0.87	10182.8	50260.00
11	11059.48	42.32	0.735	0.50(0.44)	0.87	10606.2	50200.00
12	10984.87	43.93	0.721	0.50(0.44)	0.88	11030.9	390.00
13	10262.69	65.57	0.591	0.50(0.46)	0.92	16698.7	11801.00
14	10003.59	76.91	0.552	0.50(0.46)	0.93	19931.2	11500.00
15	9860.61	82.61	0.532	0.50(0.47)	0.94	21866.3	11701.00

16	9667.17	88.89	0.511	0.50	(0.47)	0.94	23975.7	11000.00
17	9260.06	105.29	0.477	0.50	(0.48)	0.95	30841.3	12500.00
18	9054.82	111.48	0.465	0.50	(0.48)	0.96	33710.7	10900.00
19	8397.92	120.17	0.449	0.50	(0.48)	0.96	37039.9	11130.00
20	7712.95	131.63	0.435	0.50	(0.48)	0.96	40712.4	11620.00
21	6657.30	147.43	0.416	0.50	(0.48)	0.97	45238.2	12400.00
22	5809.48	158.84	0.402	0.50	(0.48)	0.97	47544.4	12201.00
23	5198.38	168.16	0.391	0.50	(0.48)	0.97	48835.0	12111.00
24	4273.96	183.87	0.375	0.50	(0.48)	0.97	50757.9	12261.00
25	3802.73	193.16	0.370	0.50	(0.48)	0.97	51569.0	10200.00
26	3233.58	208.54	0.361	0.50	(0.48)	0.97	52807.0	10300.00
27	3001.89	215.39	0.358	0.50	(0.48)	0.97	53159.2	12010.00
28	2527.27	235.81	0.347	0.50	(0.48)	0.97	53487.5	12000.00
29	1551.50	304.14	0.309	0.50	(0.48)	0.97	54158.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116677.91 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	169.21	19.05	1.163	0.50(0.22)	0.43	198.6	203.00
2	167.61	21.45	1.085	0.50(0.21)	0.43	213.7	210.00

LONGEST FLOWPATH FROM NODE 210.00 TO NODE 12904.00 = 7986.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11241.12	16.44	1.262	0.50(0.40)	0.79	3595.4	50400.00
2	11495.00	19.05	1.163	0.50(0.40)	0.79	4210.4	203.00
3	11720.41	21.45	1.085	0.50(0.40)	0.80	4768.0	210.00
4	11962.42	24.18	1.006	0.50(0.40)	0.80	5382.8	50320.00
5	11962.72	24.19	1.005	0.50(0.40)	0.80	5384.9	410.00
6	11888.03	26.17	0.958	0.50(0.40)	0.80	6023.3	50240.00
7	11858.47	26.91	0.943	0.50(0.40)	0.81	6263.4	50330.00
8	11721.52	30.34	0.877	0.50(0.41)	0.82	7350.0	50280.00
9	11676.91	31.37	0.864	0.50(0.41)	0.82	7668.0	50300.00
10	11560.04	33.95	0.831	0.50(0.42)	0.83	8452.1	50220.00
11	11362.73	38.34	0.775	0.50(0.43)	0.85	9747.1	600.00
12	11239.98	40.73	0.748	0.50(0.43)	0.86	10396.5	50260.00
13	11159.75	42.32	0.735	0.50(0.43)	0.86	10819.9	50200.00
14	11082.57	43.93	0.721	0.50(0.43)	0.87	11244.6	390.00
15	10335.30	65.57	0.591	0.50(0.46)	0.91	16912.4	11801.00
16	10068.71	76.91	0.552	0.50(0.46)	0.92	20144.9	11500.00
17	9921.97	82.61	0.532	0.50(0.47)	0.93	22080.0	11701.00
18	9724.38	88.89	0.511	0.50(0.47)	0.94	24189.4	11000.00
19	9312.72	105.29	0.477	0.50(0.47)	0.95	31055.0	12500.00
20	9106.17	111.48	0.465	0.50(0.48)	0.95	33924.4	10900.00
21	8447.42	120.17	0.449	0.50(0.48)	0.96	37253.6	11130.00
22	7760.93	131.63	0.435	0.50(0.48)	0.96	40926.1	11620.00
23	6703.19	147.43	0.416	0.50(0.48)	0.96	45451.9	12400.00
24	5853.87	158.84	0.402	0.50(0.48)	0.96	47758.1	12201.00
25	5241.53	168.16	0.391	0.50(0.48)	0.96	49048.7	12111.00
26	4315.31	183.87	0.375	0.50(0.48)	0.96	50971.6	12261.00
27	3843.52	193.16	0.370	0.50(0.48)	0.97	51782.7	10200.00
28	3273.45	208.54	0.361	0.50(0.48)	0.97	53020.7	10300.00
29	3041.35	215.39	0.358	0.50(0.48)	0.97	53372.9	12010.00
30	2565.50	235.81	0.347	0.50(0.48)	0.97	53701.2	12000.00
31	1585.63	304.14	0.309	0.50(0.48)	0.97	54372.0	10100.00

TOTAL AREA (ACRES) = 54372.0

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 11962.72 Tc(MIN.) = 24.193
EFFECTIVE AREA(ACRES) = 5384.95 AREA-AVERAGED Fm(INCH/HR) = 0.40
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.80
TOTAL AREA(ACRES) = 54372.0
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116677.91 FEET.

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 24.19
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.005
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.10	0.50	0.900	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	0.80	0.50	1.000	-
USER-DEFINED	-	1.20	0.50	0.100	-
USER-DEFINED	-	1.50	0.50	1.000	-
USER-DEFINED	-	3.00	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.840
SUBAREA AREA(ACRES) = 6.80 SUBAREA RUNOFF(CFS) = 3.58
EFFECTIVE AREA(ACRES) = 5391.75 AREA-AVERAGED Fm(INCH/HR) = 0.40
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.80
TOTAL AREA(ACRES) = 54378.8 PEAK FLOW RATE(CFS) = 11962.72
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 24.19
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.005
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	3.60	0.50	1.000	-
USER-DEFINED	-	15.10	0.50	0.850	-
USER-DEFINED	-	20.00	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.941
SUBAREA AREA(ACRES) = 38.70 SUBAREA RUNOFF(CFS) = 18.62
EFFECTIVE AREA(ACRES) = 5430.45 AREA-AVERAGED Fm(INCH/HR) = 0.40
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.80
TOTAL AREA(ACRES) = 54417.5 PEAK FLOW RATE(CFS) = 11962.72
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF STUDY SUMMARY:
TOTAL AREA(ACRES) = 54417.5 TC(MIN.) = 24.19
EFFECTIVE AREA(ACRES) = 5430.45 AREA-AVERAGED Fm(INCH/HR) = 0.40
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.798
PEAK FLOW RATE(CFS) = 11962.72

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11241.12	16.44	1.262	0.50 (0.40)	0.80	3640.9	50400.00
2	11495.00	19.05	1.163	0.50 (0.40)	0.80	4255.9	203.00
3	11720.41	21.45	1.085	0.50 (0.40)	0.80	4813.5	210.00
4	11962.42	24.18	1.006	0.50 (0.40)	0.80	5428.3	50320.00
5	11962.72	24.19	1.005	0.50 (0.40)	0.80	5430.4	410.00
6	11888.03	26.17	0.958	0.50 (0.40)	0.81	6068.8	50240.00
7	11858.47	26.91	0.943	0.50 (0.40)	0.81	6308.9	50330.00
8	11721.52	30.34	0.877	0.50 (0.41)	0.82	7395.5	50280.00
9	11676.91	31.37	0.864	0.50 (0.41)	0.82	7713.5	50300.00
10	11560.04	33.95	0.831	0.50 (0.42)	0.83	8497.6	50220.00
11	11362.73	38.34	0.775	0.50 (0.43)	0.85	9792.6	600.00
12	11239.98	40.73	0.748	0.50 (0.43)	0.86	10442.0	50260.00
13	11159.75	42.32	0.735	0.50 (0.43)	0.86	10865.4	50200.00
14	11082.57	43.93	0.721	0.50 (0.43)	0.87	11290.1	390.00
15	10335.30	65.57	0.591	0.50 (0.46)	0.91	16957.9	11801.00
16	10068.71	76.91	0.552	0.50 (0.46)	0.92	20190.4	11500.00
17	9921.97	82.61	0.532	0.50 (0.47)	0.93	22125.5	11701.00
18	9724.38	88.89	0.511	0.50 (0.47)	0.94	24234.9	11000.00
19	9312.72	105.29	0.477	0.50 (0.47)	0.95	31100.5	12500.00
20	9106.17	111.48	0.465	0.50 (0.48)	0.95	33969.9	10900.00
21	8447.42	120.17	0.449	0.50 (0.48)	0.96	37299.1	11130.00
22	7760.93	131.63	0.435	0.50 (0.48)	0.96	40971.6	11620.00
23	6703.19	147.43	0.416	0.50 (0.48)	0.96	45497.4	12400.00
24	5853.87	158.84	0.402	0.50 (0.48)	0.96	47803.6	12201.00
25	5241.53	168.16	0.391	0.50 (0.48)	0.96	49094.2	12111.00
26	4315.31	183.87	0.375	0.50 (0.48)	0.96	51017.1	12261.00
27	3843.52	193.16	0.370	0.50 (0.48)	0.97	51828.2	10200.00
28	3273.45	208.54	0.361	0.50 (0.48)	0.97	53066.2	10300.00
29	3041.35	215.39	0.358	0.50 (0.48)	0.97	53418.4	12010.00
30	2565.50	235.81	0.347	0.50 (0.48)	0.97	53746.7	12000.00
31	1585.63	304.14	0.309	0.50 (0.48)	0.97	54417.5	10100.00

=====
 END OF RATIONAL METHOD ANALYSIS
 =====

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 133 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 5-YR EV FEB 2023 ROKAMOTO *

FILE NAME: RU05EV33.DAT
TIME/DATE OF STUDY: 09:08 02/08/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 5.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 2.642
- 2) 10.00; 1.762
- 3) 15.00; 1.304
- 4) 20.00; 1.115
- 5) 25.00; 0.974
- 6) 30.00; 0.875
- 7) 40.00; 0.748
- 8) 50.00; 0.665
- 9) 60.00; 0.603
- 10) 90.00; 0.500
- 11) 120.00; 0.441
- 12) 180.00; 0.369
- 13) 360.00; 0.272
- 14) 1200.00; 0.119

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL: IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:

1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13112.00 TO NODE 13222.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: S31X05.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	769.71	39.09	0.50 (0.41)	0.81	2485.9	13100.00
2	520.73	70.06	0.50 (0.40)	0.81	3771.2	13000.00
3	475.69	73.98	0.50 (0.40)	0.81	3796.8	13010.00
TOTAL AREA (ACRES) =						3796.8

FLOW PROCESS FROM NODE 13221.00 TO NODE 13222.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: S32X05.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	284.60	41.45	0.50 (0.41)	0.83	1124.1	13200.00
2	281.25	41.90	0.50 (0.41)	0.83	1127.6	13210.00
TOTAL AREA (ACRES) =						1127.6

FLOW PROCESS FROM NODE 13221.00 TO NODE 13222.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	284.60	41.45	0.50 (0.41)	0.83	1124.1	13200.00
2	281.25	41.90	0.50 (0.41)	0.83	1127.6	13210.00
TOTAL AREA (ACRES) =						1127.6

FLOW PROCESS FROM NODE 13112.00 TO NODE 13222.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

=====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	284.60	41.45	0.736	0.50 (0.41)	0.83	1124.1	13200.00
2	281.25	41.90	0.732	0.50 (0.41)	0.83	1127.6	13210.00

LONGEST FLOWPATH FROM NODE 13200.00 TO NODE 13222.00 = 16821.05 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	769.71	39.09	0.760	0.50(0.41)	0.81	2485.9	13100.00
2	520.73	70.06	0.568	0.50(0.40)	0.81	3771.2	13000.00
3	475.69	73.98	0.555	0.50(0.40)	0.81	3796.8	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13222.00 = 32126.49 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1054.32	39.09	0.760	0.50(0.41)	0.82	3546.1	13100.00
2	1035.40	41.45	0.736	0.50(0.41)	0.82	3707.6	13200.00
3	1028.41	41.90	0.732	0.50(0.41)	0.82	3729.9	13210.00
4	657.26	70.06	0.568	0.50(0.41)	0.81	4898.8	13000.00
5	600.32	73.98	0.555	0.50(0.41)	0.81	4924.4	13010.00

TOTAL AREA (ACRES) = 4924.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 1054.32 Tc(MIN.) = 39.093
EFFECTIVE AREA(ACRES) = 3546.13 AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.82
TOTAL AREA (ACRES) = 4924.4
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13222.00 = 32126.49 FEET.

FLOW PROCESS FROM NODE 13222.00 TO NODE 13222.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 13222.00 TO NODE 13222.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

FLOW PROCESS FROM NODE 13222.00 TO NODE 13301.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 427.51 DOWNSTREAM(FEET) = 382.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 2533.33 CHANNEL SLOPE = 0.0180
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.720

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.40	0.50	0.100	-
USER-DEFINED	-	15.60	0.50	1.000	-
USER-DEFINED	-	0.10	0.50	0.600	-
USER-DEFINED	-	5.30	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	22.60	0.50	0.100	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.521
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1063.66
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.97
AVERAGE FLOW DEPTH(FEET) = 5.96 TRAVEL TIME(MIN.) = 4.23
Tc(MIN.) = 43.33
SUBAREA AREA(ACRES) = 45.20 SUBAREA RUNOFF(CFS) = 18.70
EFFECTIVE AREA(ACRES) = 3591.33 AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.81
TOTAL AREA(ACRES) = 4969.6 PEAK FLOW RATE(CFS) = 1054.32
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 5.95 FLOW VELOCITY(FEET/SEC.) = 9.94
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1054.32	43.33	0.720	0.50(0.41)	0.81	3591.3	13100.00
2	1035.40	45.70	0.701	0.50(0.41)	0.81	3752.8	13200.00
3	1028.41	46.16	0.697	0.50(0.41)	0.81	3775.1	13210.00
4	657.26	74.82	0.552	0.50(0.41)	0.81	4944.0	13000.00
5	600.32	78.87	0.538	0.50(0.40)	0.81	4969.6	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 1054.32 Tc(MIN.) = 43.33
AREA-AVERAGED Fm(INCH/HR) = 0.41 AREA-AVERAGED Fp(INCH/HR) = 0.50
AREA-AVERAGED Ap = 0.81 EFFECTIVE AREA(ACRES) = 3591.33

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 43.33
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.720
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.00	0.50	1.000	-
USER-DEFINED	-	0.50	0.50	1.000	-
USER-DEFINED	-	7.40	0.50	0.100	-
USER-DEFINED	-	4.70	0.50	1.000	-
USER-DEFINED	-	2.90	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.596
SUBAREA AREA(ACRES) = 16.50 SUBAREA RUNOFF(CFS) = 6.27
EFFECTIVE AREA(ACRES) = 3607.83 AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.81
TOTAL AREA(ACRES) = 4986.1 PEAK FLOW RATE(CFS) = 1054.32
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 43.33
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.720

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.30	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	0.100	-
USER-DEFINED	-	5.30	0.50	1.000	-
USER-DEFINED	-	0.30	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	0.60	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.977
SUBAREA AREA(ACRES) = 7.90 SUBAREA RUNOFF(CFS) = 1.65
EFFECTIVE AREA(ACRES) = 3615.73 AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.81
TOTAL AREA(ACRES) = 4994.0 PEAK FLOW RATE(CFS) = 1054.32
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 43.33
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.720
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	4.30	0.50	1.000	-
USER-DEFINED	-	0.80	0.50	1.000	-
USER-DEFINED	-	1.10	0.50	1.000	-
USER-DEFINED	-	6.90	0.50	1.000	-
USER-DEFINED	-	7.90	0.50	1.000	-
USER-DEFINED	-	1.00	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 22.00 SUBAREA RUNOFF(CFS) = 4.36
EFFECTIVE AREA(ACRES) = 3637.73 AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.81
TOTAL AREA(ACRES) = 5016.0 PEAK FLOW RATE(CFS) = 1054.32
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 43.33
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.720
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.40	0.50	1.000	-
USER-DEFINED	-	14.60	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 15.00 SUBAREA RUNOFF(CFS) = 2.97
EFFECTIVE AREA(ACRES) = 3652.73 AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.81

TOTAL AREA(ACRES) = 5031.0 PEAK FLOW RATE(CFS) = 1054.32
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1<<<<

FLOW PROCESS FROM NODE 31100.00 TO NODE 31101.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH(FEET) = 317.00
ELEVATION DATA: UPSTREAM(FEET) = 801.00 DOWNSTREAM(FEET) = 685.00

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 8.641
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 2.001
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER						
"CHAPARRAL,BROADLEAF"	-	0.50	0.50	1.000	65	8.64
NATURAL FAIR COVER						
"OPEN BRUSH"	-	0.30	0.50	1.000	65	8.64
NATURAL FAIR COVER						
"OPEN BRUSH"	-	0.30	0.50	1.000	65	8.64

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 1.49
TOTAL AREA(ACRES) = 1.10 PEAK FLOW RATE(CFS) = 1.49

FLOW PROCESS FROM NODE 31101.00 TO NODE 31102.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 685.00 DOWNSTREAM(FEET) = 655.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 135.00 CHANNEL SLOPE = 0.2222
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.929
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.50	0.50	1.000	-
USER-DEFINED	-	0.10	0.50	1.000	-
USER-DEFINED	-	0.70	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2.32
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.46
AVERAGE FLOW DEPTH(FEET) = 0.38 TRAVEL TIME(MIN.) = 0.41
Tc(MIN.) = 9.05

SUBAREA AREA (ACRES) = 1.30 SUBAREA RUNOFF (CFS) = 1.67
EFFECTIVE AREA (ACRES) = 2.40 AREA-AVERAGED Fm (INCH/HR) = 0.50
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 2.4 PEAK FLOW RATE (CFS) = 3.09

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 0.42 FLOW VELOCITY (FEET/SEC.) = 5.92
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31102.00 = 452.00 FEET.

FLOW PROCESS FROM NODE 31102.00 TO NODE 31103.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 655.00 DOWNSTREAM (FEET) = 630.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 203.00 CHANNEL SLOPE = 0.1232
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.815

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.30	0.50	1.000	-
USER-DEFINED	-	0.10	0.50	1.000	-
USER-DEFINED	-	1.90	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 4.45

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.25

AVERAGE FLOW DEPTH (FEET) = 0.53 TRAVEL TIME (MIN.) = 0.64

Tc (MIN.) = 9.70

SUBAREA AREA (ACRES) = 2.30 SUBAREA RUNOFF (CFS) = 2.72

EFFECTIVE AREA (ACRES) = 4.70 AREA-AVERAGED Fm (INCH/HR) = 0.50

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00

TOTAL AREA (ACRES) = 4.7 PEAK FLOW RATE (CFS) = 5.56

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 0.58 FLOW VELOCITY (FEET/SEC.) = 5.46
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31103.00 = 655.00 FEET.

FLOW PROCESS FROM NODE 31103.00 TO NODE 31104.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 630.00 DOWNSTREAM (FEET) = 605.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 321.00 CHANNEL SLOPE = 0.0779
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.692

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.10	0.50	1.000	-
USER-DEFINED	-	2.50	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 7.49
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.00
AVERAGE FLOW DEPTH (FEET) = 0.71 TRAVEL TIME (MIN.) = 1.07
Tc (MIN.) = 10.77

SUBAREA AREA (ACRES) = 3.60 SUBAREA RUNOFF (CFS) = 3.86
EFFECTIVE AREA (ACRES) = 8.30 AREA-AVERAGED Fm (INCH/HR) = 0.50
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 8.3 PEAK FLOW RATE (CFS) = 8.90

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 0.75 FLOW VELOCITY (FEET/SEC.) = 5.24
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31104.00 = 976.00 FEET.

FLOW PROCESS FROM NODE 31104.00 TO NODE 31105.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 605.00 DOWNSTREAM (FEET) = 585.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 288.00 CHANNEL SLOPE = 0.0694
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.610

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.70	0.50	1.000	-
USER-DEFINED	-	0.60	0.50	1.000	-
USER-DEFINED	-	3.00	0.50	1.000	-
USER-DEFINED	-	2.10	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 12.10

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.39

AVERAGE FLOW DEPTH (FEET) = 0.86 TRAVEL TIME (MIN.) = 0.89

Tc (MIN.) = 11.66

SUBAREA AREA (ACRES) = 6.40 SUBAREA RUNOFF (CFS) = 6.39

EFFECTIVE AREA (ACRES) = 14.70 AREA-AVERAGED Fm (INCH/HR) = 0.50

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00

TOTAL AREA (ACRES) = 14.7 PEAK FLOW RATE (CFS) = 14.69

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 0.93 FLOW VELOCITY (FEET/SEC.) = 5.68
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31105.00 = 1264.00 FEET.

FLOW PROCESS FROM NODE 31105.00 TO NODE 31106.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 585.00 DOWNSTREAM (FEET) = 560.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 344.00 CHANNEL SLOPE = 0.0727
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.526

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.60	0.50	1.000	-
USER-DEFINED	-	2.80	0.50	1.000	-
USER-DEFINED	-	0.60	0.50	1.000	-
USER-DEFINED	-	0.10	0.50	1.000	-
USER-DEFINED	-	2.60	0.50	1.000	-
USER-DEFINED	-	4.10	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 19.67
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.22
AVERAGE FLOW DEPTH (FEET) = 1.03 TRAVEL TIME (MIN.) = 0.92
Tc (MIN.) = 12.58
SUBAREA AREA (ACRES) = 10.80 SUBAREA RUNOFF (CFS) = 9.97
EFFECTIVE AREA (ACRES) = 25.50 AREA-AVERAGED Fm (INCH/HR) = 0.50
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 25.5 PEAK FLOW RATE (CFS) = 23.53

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 1.10 FLOW VELOCITY (FEET/SEC.) = 6.47
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31106.00 = 1608.00 FEET.

FLOW PROCESS FROM NODE 31106.00 TO NODE 31107.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<
=====

ELEVATION DATA: UPSTREAM (FEET) = 560.00 DOWNSTREAM (FEET) = 530.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 619.00 CHANNEL SLOPE = 0.0485
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.365

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.80	0.50	1.000	-
USER-DEFINED	-	1.90	0.50	1.000	-
USER-DEFINED	-	1.50	0.50	1.000	-
USER-DEFINED	-	8.20	0.50	1.000	-
USER-DEFINED	-	2.70	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 29.42
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.87
AVERAGE FLOW DEPTH (FEET) = 1.29 TRAVEL TIME (MIN.) = 1.76
Tc (MIN.) = 14.34
SUBAREA AREA (ACRES) = 15.10 SUBAREA RUNOFF (CFS) = 11.75
EFFECTIVE AREA (ACRES) = 40.60 AREA-AVERAGED Fm (INCH/HR) = 0.50
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 40.6 PEAK FLOW RATE (CFS) = 31.59

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 1.32 FLOW VELOCITY (FEET/SEC.) = 6.00
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31107.00 = 2227.00 FEET.

FLOW PROCESS FROM NODE 31107.00 TO NODE 31108.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<
=====

ELEVATION DATA: UPSTREAM (FEET) = 530.00 DOWNSTREAM (FEET) = 515.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 377.00 CHANNEL SLOPE = 0.0398
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.288

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.50	0.50	1.000	-
USER-DEFINED	-	6.50	0.50	1.000	-
USER-DEFINED	-	1.30	0.50	1.000	-
USER-DEFINED	-	1.10	0.50	1.000	-
USER-DEFINED	-	5.50	0.50	1.000	-
USER-DEFINED	-	3.40	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 38.08
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.83
AVERAGE FLOW DEPTH (FEET) = 1.48 TRAVEL TIME (MIN.) = 1.08
Tc (MIN.) = 15.41

SUBAREA AREA (ACRES) = 18.30 SUBAREA RUNOFF (CFS) = 12.98
EFFECTIVE AREA (ACRES) = 58.90 AREA-AVERAGED Fm (INCH/HR) = 0.50
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 58.9 PEAK FLOW RATE (CFS) = 41.78

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 1.53 FLOW VELOCITY (FEET/SEC.) = 5.96
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31108.00 = 2604.00 FEET.

FLOW PROCESS FROM NODE 31108.00 TO NODE 31109.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<
=====

ELEVATION DATA: UPSTREAM (FEET) = 515.00 DOWNSTREAM (FEET) = 490.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 520.00 CHANNEL SLOPE = 0.0481
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.239

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.70	0.50	1.000	-
USER-DEFINED	-	2.20	0.50	1.000	-
USER-DEFINED	-	3.10	0.50	1.000	-
USER-DEFINED	-	0.90	0.50	1.000	-
USER-DEFINED	-	7.40	0.50	1.000	-
USER-DEFINED	-	0.30	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 46.63

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.59
AVERAGE FLOW DEPTH (FEET) = 1.54 TRAVEL TIME (MIN.) = 1.32
Tc (MIN.) = 16.73
SUBAREA AREA (ACRES) = 14.60 SUBAREA RUNOFF (CFS) = 9.70
EFFECTIVE AREA (ACRES) = 73.50 AREA-AVERAGED Fm (INCH/HR) = 0.50
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 73.5 PEAK FLOW RATE (CFS) = 48.85

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 1.56 FLOW VELOCITY (FEET/SEC.) = 6.68
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31109.00 = 3124.00 FEET.

FLOW PROCESS FROM NODE 31109.00 TO NODE 31109.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) = 16.73
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.239
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	11.40	0.50	1.000	-
USER-DEFINED	-	8.90	0.50	1.000	-
USER-DEFINED	-	1.90	0.50	1.000	-
USER-DEFINED	-	9.20	0.50	1.000	-
USER-DEFINED	-	1.40	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 32.80 SUBAREA RUNOFF (CFS) = 21.80
EFFECTIVE AREA (ACRES) = 106.30 AREA-AVERAGED Fm (INCH/HR) = 0.50
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 106.3 PEAK FLOW RATE (CFS) = 70.64

FLOW PROCESS FROM NODE 31109.00 TO NODE 31110.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 490.00 DOWNSTREAM (FEET) = 432.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 1420.00 CHANNEL SLOPE = 0.0408
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.111
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.80	0.50	1.000	-
USER-DEFINED	-	0.60	0.50	1.000	-
USER-DEFINED	-	0.10	0.50	0.900	-
USER-DEFINED	-	1.30	0.50	1.000	-
USER-DEFINED	-	4.00	0.50	1.000	-
USER-DEFINED	-	1.50	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 72.93
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.94

AVERAGE FLOW DEPTH (FEET) = 1.87 TRAVEL TIME (MIN.) = 3.41
Tc (MIN.) = 20.14
SUBAREA AREA (ACRES) = 8.30 SUBAREA RUNOFF (CFS) = 4.57
EFFECTIVE AREA (ACRES) = 114.60 AREA-AVERAGED Fm (INCH/HR) = 0.50
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 114.6 PEAK FLOW RATE (CFS) = 70.64
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 1.85 FLOW VELOCITY (FEET/SEC.) = 6.89
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31110.00 = 4544.00 FEET.

FLOW PROCESS FROM NODE 31110.00 TO NODE 31110.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) = 20.14
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.111
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.30	0.50	1.000	-
USER-DEFINED	-	9.60	0.50	1.000	-
USER-DEFINED	-	0.40	0.50	0.900	-
USER-DEFINED	-	6.20	0.50	1.000	-
USER-DEFINED	-	3.90	0.50	1.000	-
USER-DEFINED	-	1.40	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.998
SUBAREA AREA (ACRES) = 21.80 SUBAREA RUNOFF (CFS) = 12.00
EFFECTIVE AREA (ACRES) = 136.40 AREA-AVERAGED Fm (INCH/HR) = 0.50
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 136.4 PEAK FLOW RATE (CFS) = 75.01

FLOW PROCESS FROM NODE 31110.00 TO NODE 13301.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 432.00 DOWNSTREAM (FEET) = 382.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 1847.00 CHANNEL SLOPE = 0.0271
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.970
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	4.90	0.50	1.000	-
USER-DEFINED	-	1.50	0.50	1.000	-
USER-DEFINED	-	0.60	0.50	0.900	-
USER-DEFINED	-	2.50	0.50	1.000	-
USER-DEFINED	-	5.30	0.50	1.000	-
USER-DEFINED	-	3.30	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.997
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 78.85

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.07
 AVERAGE FLOW DEPTH (FEET) = 2.08 TRAVEL TIME (MIN.) = 5.07
 Tc (MIN.) = 25.21
 SUBAREA AREA (ACRES) = 18.10 SUBAREA RUNOFF (CFS) = 7.68
 EFFECTIVE AREA (ACRES) = 154.50 AREA-AVERAGED Fm (INCH/HR) = 0.50
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 154.5 PEAK FLOW RATE (CFS) = 75.01
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 2.04 FLOW VELOCITY (FEET/SEC.) = 6.00
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 13301.00 = 6391.00 FEET.

 FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	75.01	25.21	0.970	0.50 (0.50)	1.00	154.5	31100.00

LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 13301.00 = 6391.00 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1054.32	43.33	0.720	0.50 (0.41)	0.81	3652.7	13100.00
2	1035.40	45.70	0.701	0.50 (0.41)	0.81	3814.2	13200.00
3	1028.41	46.16	0.697	0.50 (0.41)	0.81	3836.5	13210.00
4	660.41	74.82	0.552	0.50 (0.41)	0.81	5005.4	13000.00
5	601.45	78.87	0.538	0.50 (0.41)	0.81	5031.0	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1129.32	25.21	0.970	0.50 (0.41)	0.83	2279.7	31100.00
2	1089.51	43.33	0.720	0.50 (0.41)	0.82	3807.2	13100.00
3	1067.44	45.70	0.701	0.50 (0.41)	0.82	3968.7	13200.00
4	1059.85	46.16	0.697	0.50 (0.41)	0.82	3991.0	13210.00
5	668.75	74.82	0.552	0.50 (0.41)	0.82	5159.9	13000.00
6	607.57	78.87	0.538	0.50 (0.41)	0.82	5185.5	13010.00

TOTAL AREA (ACRES) = 5185.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
 PEAK FLOW RATE (CFS) = 1129.32 Tc (MIN.) = 25.209
 EFFECTIVE AREA (ACRES) = 2279.72 AREA-AVERAGED Fm (INCH/HR) = 0.41
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.83
 TOTAL AREA (ACRES) = 5185.5
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

 FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<

 FLOW PROCESS FROM NODE 13301.00 TO NODE 13302.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM (FEET) = 382.00 DOWNSTREAM (FEET) = 375.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1141.09 CHANNEL SLOPE = 0.0061
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.914

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.20	0.50	1.000	-
USER-DEFINED	-	0.60	0.50	1.000	-
USER-DEFINED	-	0.90	0.50	1.000	-
USER-DEFINED	-	4.80	0.50	1.000	-
USER-DEFINED	-	1.90	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 1131.07
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.76
 AVERAGE FLOW DEPTH (FEET) = 7.47 TRAVEL TIME (MIN.) = 2.81
 Tc (MIN.) = 28.02

SUBAREA AREA (ACRES) = 9.40 SUBAREA RUNOFF (CFS) = 3.50
 EFFECTIVE AREA (ACRES) = 2289.12 AREA-AVERAGED Fm (INCH/HR) = 0.41
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.83
 TOTAL AREA (ACRES) = 5194.9 PEAK FLOW RATE (CFS) = 1129.32
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 7.46 FLOW VELOCITY (FEET/SEC.) = 6.76
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13302.00 = 35800.91 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1129.32	28.02	0.914	0.50 (0.41)	0.83	2289.1	31100.00
2	1089.51	46.17	0.697	0.50 (0.41)	0.82	3816.6	13100.00
3	1067.44	48.55	0.677	0.50 (0.41)	0.82	3978.1	13200.00
4	1059.85	49.02	0.673	0.50 (0.41)	0.82	4000.4	13210.00
5	668.75	78.03	0.541	0.50 (0.41)	0.82	5169.3	13000.00
6	607.57	82.15	0.527	0.50 (0.41)	0.82	5194.9	13010.00

NEW PEAK FLOW DATA ARE:
 PEAK FLOW RATE (CFS) = 1129.32 Tc (MIN.) = 28.02
 AREA-AVERAGED Fm (INCH/HR) = 0.41 AREA-AVERAGED Fp (INCH/HR) = 0.50
 AREA-AVERAGED Ap = 0.83 EFFECTIVE AREA (ACRES) = 2289.12

 FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 28.02
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.914
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 13.80 0.50 1.000 -
 USER-DEFINED - 2.60 0.50 1.000 -
 USER-DEFINED - 1.10 0.50 0.100 -
 USER-DEFINED - 3.50 0.50 0.900 -
 USER-DEFINED - 6.90 0.50 1.000 -
 USER-DEFINED - 0.20 0.50 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.952
 SUBAREA AREA (ACRES) = 28.10 SUBAREA RUNOFF (CFS) = 11.07
 EFFECTIVE AREA (ACRES) = 2317.22 AREA-AVERAGED Fm (INCH/HR) = 0.41
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.83
 TOTAL AREA (ACRES) = 5223.0 PEAK FLOW RATE (CFS) = 1129.32
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 28.02
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.914
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 0.10 0.50 1.000 -
 USER-DEFINED - 0.10 0.50 0.100 -
 USER-DEFINED - 2.40 0.50 0.900 -
 USER-DEFINED - 0.50 0.50 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.894
 SUBAREA AREA (ACRES) = 3.10 SUBAREA RUNOFF (CFS) = 1.30
 EFFECTIVE AREA (ACRES) = 2320.32 AREA-AVERAGED Fm (INCH/HR) = 0.41
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.83
 TOTAL AREA (ACRES) = 5226.1 PEAK FLOW RATE (CFS) = 1129.32
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 28.02
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.914
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 0.10 0.50 1.000 -
 USER-DEFINED - 2.60 0.50 1.000 -
 USER-DEFINED - 3.10 0.50 1.000 -
 USER-DEFINED - 0.40 0.50 1.000 -
 USER-DEFINED - 0.20 0.50 1.000 -
 USER-DEFINED - 13.80 0.50 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 20.20 SUBAREA RUNOFF (CFS) = 7.53
 EFFECTIVE AREA (ACRES) = 2340.52 AREA-AVERAGED Fm (INCH/HR) = 0.41

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.83
 TOTAL AREA (ACRES) = 5246.3 PEAK FLOW RATE (CFS) = 1129.32
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 28.02
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.914
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 34.60 0.50 1.000 -
 USER-DEFINED - 2.40 0.50 1.000 -
 USER-DEFINED - 22.60 0.50 1.000 -
 USER-DEFINED - 11.60 0.50 1.000 -
 USER-DEFINED - 0.40 0.50 0.200 -
 USER-DEFINED - 4.80 0.50 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.996
 SUBAREA AREA (ACRES) = 76.40 SUBAREA RUNOFF (CFS) = 28.61
 EFFECTIVE AREA (ACRES) = 2416.92 AREA-AVERAGED Fm (INCH/HR) = 0.42
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.83
 TOTAL AREA (ACRES) = 5322.7 PEAK FLOW RATE (CFS) = 1129.32
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 28.02
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.914
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 1.60 0.50 1.000 -
 USER-DEFINED - 46.40 0.50 1.000 -
 USER-DEFINED - 0.10 0.50 0.200 -
 USER-DEFINED - 60.70 0.50 1.000 -
 USER-DEFINED - 5.80 0.50 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999
 SUBAREA AREA (ACRES) = 114.60 SUBAREA RUNOFF (CFS) = 42.73
 EFFECTIVE AREA (ACRES) = 2531.52 AREA-AVERAGED Fm (INCH/HR) = 0.42
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.84
 TOTAL AREA (ACRES) = 5437.3 PEAK FLOW RATE (CFS) = 1129.32
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13302.00 TO NODE 13303.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 375.00 DOWNSTREAM (FEET) = 355.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 2193.96 CHANNEL SLOPE = 0.0091
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
 CHANNEL FLOW THRU SUBAREA(CFS) = 1129.32
 FLOW VELOCITY(FEET/SEC.) = 7.84 FLOW DEPTH(FEET) = 6.93
 TRAVEL TIME(MIN.) = 4.67 Tc(MIN.) = 32.69
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13303.00 = 37994.87 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1129.32	32.69	0.841	0.50(0.42)	0.84	2531.5	31100.00
2	1089.51	50.88	0.660	0.50(0.42)	0.83	4059.0	13100.00
3	1067.44	53.29	0.645	0.50(0.42)	0.83	4220.5	13200.00
4	1059.85	53.76	0.642	0.50(0.42)	0.83	4242.8	13210.00
5	668.75	83.35	0.523	0.50(0.41)	0.82	5411.7	13000.00
6	607.57	87.59	0.508	0.50(0.41)	0.82	5437.3	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 1129.32 Tc(MIN.) = 32.69
 AREA-AVERAGED Fm(INCH/HR) = 0.42 AREA-AVERAGED Fp(INCH/HR) = 0.50
 AREA-AVERAGED Ap = 0.84 EFFECTIVE AREA(ACRES) = 2531.52

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 32.69

* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.841

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	0.40	0.50	1.000	-
USER-DEFINED	-	0.80	0.50	1.000	-
USER-DEFINED	-	1.40	0.50	0.100	-
USER-DEFINED	-	2.60	0.50	1.000	-
USER-DEFINED	-	2.20	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.834

SUBAREA AREA(ACRES) = 7.60 SUBAREA RUNOFF(CFS) = 2.90

EFFECTIVE AREA(ACRES) = 2539.12 AREA-AVERAGED Fm(INCH/HR) = 0.42

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.84

TOTAL AREA(ACRES) = 5444.9 PEAK FLOW RATE(CFS) = 1129.32

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 32.69

* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.841

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	3.10	0.50	1.000	-
USER-DEFINED	-	3.40	0.50	1.000	-

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.50	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	3.60	0.50	0.100	-
USER-DEFINED	-	4.00	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.781
 SUBAREA AREA(ACRES) = 14.80 SUBAREA RUNOFF(CFS) = 6.00
 EFFECTIVE AREA(ACRES) = 2553.92 AREA-AVERAGED Fm(INCH/HR) = 0.42
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.84
 TOTAL AREA(ACRES) = 5459.7 PEAK FLOW RATE(CFS) = 1129.32
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 32.69

* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.841

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	14.60	0.50	1.000	-
USER-DEFINED	-	6.30	0.50	1.000	-
USER-DEFINED	-	3.70	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 24.60 SUBAREA RUNOFF(CFS) = 7.54

EFFECTIVE AREA(ACRES) = 2578.52 AREA-AVERAGED Fm(INCH/HR) = 0.42

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.84

TOTAL AREA(ACRES) = 5484.3 PEAK FLOW RATE(CFS) = 1129.32

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 32.69

* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.841

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.50	0.50	1.000	-
USER-DEFINED	-	0.30	0.50	0.100	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	0.80	0.50	0.900	-
USER-DEFINED	-	1.60	0.50	1.000	-
USER-DEFINED	-	31.90	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.990

SUBAREA AREA(ACRES) = 35.30 SUBAREA RUNOFF(CFS) = 10.98

EFFECTIVE AREA(ACRES) = 2613.82 AREA-AVERAGED Fm(INCH/HR) = 0.42

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85

TOTAL AREA(ACRES) = 5519.6 PEAK FLOW RATE(CFS) = 1129.32

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 32.69
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.841
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.70	0.50	0.100	-
USER-DEFINED	-	0.30	0.50	1.000	-
USER-DEFINED	-	2.60	0.50	0.900	-
USER-DEFINED	-	5.50	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.830
 SUBAREA AREA (ACRES) = 10.50 SUBAREA RUNOFF (CFS) = 4.03
 EFFECTIVE AREA (ACRES) = 2624.32 AREA-AVERAGED Fm (INCH/HR) = 0.42
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.84
 TOTAL AREA (ACRES) = 5530.1 PEAK FLOW RATE (CFS) = 1129.32
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 32.69
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.841
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.30	0.50	0.900	-
USER-DEFINED	-	0.30	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	0.100	-
USER-DEFINED	-	0.30	0.50	1.000	-
USER-DEFINED	-	6.50	0.50	0.900	-
USER-DEFINED	-	3.00	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.917
 SUBAREA AREA (ACRES) = 11.60 SUBAREA RUNOFF (CFS) = 3.99
 EFFECTIVE AREA (ACRES) = 2635.92 AREA-AVERAGED Fm (INCH/HR) = 0.42
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85
 TOTAL AREA (ACRES) = 5541.7 PEAK FLOW RATE (CFS) = 1129.32
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 32.69
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.841
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.40	0.50	1.000	-

USER-DEFINED - 4.80 0.50 1.000 -
 USER-DEFINED - 0.90 0.50 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 7.10 SUBAREA RUNOFF (CFS) = 2.18
 EFFECTIVE AREA (ACRES) = 2643.02 AREA-AVERAGED Fm (INCH/HR) = 0.42
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85
 TOTAL AREA (ACRES) = 5548.8 PEAK FLOW RATE (CFS) = 1129.32
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13303.00 TO NODE 13304.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 355.00 DOWNSTREAM(FEET) = 350.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 925.40 CHANNEL SLOPE = 0.0054
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.810
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	0.50	0.50	1.000	-
USER-DEFINED	-	1.10	0.50	1.000	-
USER-DEFINED	-	0.30	0.50	1.000	-
USER-DEFINED	-	1.10	0.50	1.000	-
USER-DEFINED	-	3.50	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 1130.26
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.44
 AVERAGE FLOW DEPTH (FEET) = 7.65 TRAVEL TIME (MIN.) = 2.39
 Tc (MIN.) = 35.08
 SUBAREA AREA (ACRES) = 6.70 SUBAREA RUNOFF (CFS) = 1.87
 EFFECTIVE AREA (ACRES) = 2649.72 AREA-AVERAGED Fm (INCH/HR) = 0.42
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85
 TOTAL AREA (ACRES) = 5555.5 PEAK FLOW RATE (CFS) = 1129.32
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 7.64 FLOW VELOCITY (FEET/SEC.) = 6.45
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13304.00 = 38920.27 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap (DECIMAL)	Ae (ACRES)	HEADWATER NODE
1	1129.32	35.08	0.810	0.50 (0.42)	0.85	2649.7	31100.00
2	1089.51	53.29	0.645	0.50 (0.42)	0.83	4177.2	13100.00
3	1067.44	55.71	0.630	0.50 (0.42)	0.83	4338.7	13200.00
4	1059.85	56.19	0.627	0.50 (0.42)	0.83	4361.0	13210.00
5	668.75	86.08	0.513	0.50 (0.41)	0.83	5529.9	13000.00
6	607.57	90.39	0.499	0.50 (0.41)	0.83	5555.5	13010.00

NEW PEAK FLOW DATA ARE:
 PEAK FLOW RATE (CFS) = 1129.32 Tc (MIN.) = 35.08
 AREA-AVERAGED Fm (INCH/HR) = 0.42 AREA-AVERAGED Fp (INCH/HR) = 0.50

AREA-AVERAGED Ap = 0.85 EFFECTIVE AREA(ACRES) = 2649.72

FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 35.08

* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.810

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.80	0.50	1.000	-
USER-DEFINED	-	1.70	0.50	1.000	-
USER-DEFINED	-	9.40	0.50	1.000	-
USER-DEFINED	-	1.20	0.50	1.000	-
USER-DEFINED	-	0.10	0.50	0.900	-
USER-DEFINED	-	2.60	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 22.80 SUBAREA RUNOFF(CFS) = 6.37

EFFECTIVE AREA(ACRES) = 2672.52 AREA-AVERAGED Fm(INCH/HR) = 0.42

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85

TOTAL AREA(ACRES) = 5578.3 PEAK FLOW RATE(CFS) = 1129.32

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 35.08

* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.810

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	0.30	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	0.900	-
USER-DEFINED	-	2.70	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.994

SUBAREA AREA(ACRES) = 3.40 SUBAREA RUNOFF(CFS) = 0.96

EFFECTIVE AREA(ACRES) = 2675.92 AREA-AVERAGED Fm(INCH/HR) = 0.42

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85

TOTAL AREA(ACRES) = 5581.7 PEAK FLOW RATE(CFS) = 1129.32

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13304.00 TO NODE 13305.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 350.00 DOWNSTREAM(FEET) = 315.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 2966.27 CHANNEL SLOPE = 0.0118

CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00

* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.741

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.70	0.50	1.000	-
USER-DEFINED	-	0.60	0.50	1.000	-
USER-DEFINED	-	0.10	0.50	1.000	-
USER-DEFINED	-	0.40	0.50	1.000	-
USER-DEFINED	-	2.20	0.50	1.000	-
USER-DEFINED	-	4.20	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1130.32

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.64

AVERAGE FLOW DEPTH(FEET) = 6.60 TRAVEL TIME(MIN.) = 5.72

Tc(MIN.) = 40.80

SUBAREA AREA(ACRES) = 9.20 SUBAREA RUNOFF(CFS) = 2.00

EFFECTIVE AREA(ACRES) = 2685.12 AREA-AVERAGED Fm(INCH/HR) = 0.42

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85

TOTAL AREA(ACRES) = 5590.9 PEAK FLOW RATE(CFS) = 1129.32

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 6.60 FLOW VELOCITY(FEET/SEC.) = 8.64

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1129.32	40.80	0.741	0.50(0.42)	0.85	2685.1	31100.00
2	1089.51	59.06	0.609	0.50(0.42)	0.84	4212.6	13100.00
3	1067.44	61.52	0.598	0.50(0.42)	0.83	4374.1	13200.00
4	1059.85	62.01	0.596	0.50(0.42)	0.83	4396.4	13210.00
5	668.75	92.60	0.495	0.50(0.41)	0.83	5565.3	13000.00
6	607.57	97.06	0.486	0.50(0.41)	0.83	5590.9	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 1129.32 Tc(MIN.) = 40.80

AREA-AVERAGED Fm(INCH/HR) = 0.42 AREA-AVERAGED Fp(INCH/HR) = 0.50

AREA-AVERAGED Ap = 0.85 EFFECTIVE AREA(ACRES) = 2685.12

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 40.80

* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.741

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.10	0.50	1.000	-
USER-DEFINED	-	2.30	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	6.90	0.50	1.000	-
USER-DEFINED	-	0.70	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 18.20 SUBAREA RUNOFF(CFS) = 3.95

EFFECTIVE AREA(ACRES) = 2703.32 AREA-AVERAGED Fm(INCH/HR) = 0.42
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85
TOTAL AREA(ACRES) = 5609.1 PEAK FLOW RATE(CFS) = 1129.32
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 40.80
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.741
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	18.40	0.50	1.000	-
USER-DEFINED	-	1.20	0.50	1.000	-
USER-DEFINED	-	0.10	0.50	1.000	-
USER-DEFINED	-	26.60	0.50	1.000	-
USER-DEFINED	-	3.90	0.50	0.100	-
USER-DEFINED	-	3.00	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.934
SUBAREA AREA(ACRES) = 53.20 SUBAREA RUNOFF(CFS) = 13.13
EFFECTIVE AREA(ACRES) = 2756.52 AREA-AVERAGED Fm(INCH/HR) = 0.43
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85
TOTAL AREA(ACRES) = 5662.3 PEAK FLOW RATE(CFS) = 1129.32
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 40.80
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.741
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.10	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	14.00	0.50	1.000	-
USER-DEFINED	-	4.30	0.50	0.100	-
USER-DEFINED	-	5.30	0.50	1.000	-
USER-DEFINED	-	2.70	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.860
SUBAREA AREA(ACRES) = 27.60 SUBAREA RUNOFF(CFS) = 7.73
EFFECTIVE AREA(ACRES) = 2784.12 AREA-AVERAGED Fm(INCH/HR) = 0.43
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85
TOTAL AREA(ACRES) = 5689.9 PEAK FLOW RATE(CFS) = 1129.32
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 40.80
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.741
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	3.20	0.50	1.000	-
USER-DEFINED	-	6.10	0.50	1.000	-
USER-DEFINED	-	7.50	0.50	0.900	-
USER-DEFINED	-	5.40	0.50	1.000	-
USER-DEFINED	-	1.60	0.50	1.000	-
USER-DEFINED	-	1.90	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.971
SUBAREA AREA(ACRES) = 25.70 SUBAREA RUNOFF(CFS) = 5.91
EFFECTIVE AREA(ACRES) = 2809.82 AREA-AVERAGED Fm(INCH/HR) = 0.43
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85
TOTAL AREA(ACRES) = 5715.6 PEAK FLOW RATE(CFS) = 1129.32
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 40.80
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.741
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	2.00	0.50	0.100	-
USER-DEFINED	-	3.70	0.50	1.000	-
USER-DEFINED	-	2.10	0.50	1.000	-
USER-DEFINED	-	2.60	0.50	0.900	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	0.10	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.807
SUBAREA AREA(ACRES) = 10.70 SUBAREA RUNOFF(CFS) = 3.25
EFFECTIVE AREA(ACRES) = 2820.52 AREA-AVERAGED Fm(INCH/HR) = 0.43
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85
TOTAL AREA(ACRES) = 5726.3 PEAK FLOW RATE(CFS) = 1129.32
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 40.80
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.741
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.50	0.50	1.000	-
USER-DEFINED	-	8.20	0.50	0.900	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.906
SUBAREA AREA(ACRES) = 8.70 SUBAREA RUNOFF(CFS) = 2.26

EFFECTIVE AREA(ACRES) = 2829.22 AREA-AVERAGED Fm(INCH/HR) = 0.43
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85
 TOTAL AREA(ACRES) = 5735.0 PEAK FLOW RATE(CFS) = 1129.32
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 3A05EVRL.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	448.39	14.96	0.50 (0.22)	0.43	429.7	120.00
2	443.05	15.30	0.50 (0.21)	0.43	435.1	110.00
3	375.74	23.09	0.50 (0.21)	0.42	501.8	100.00
4	332.86	27.58	0.50 (0.22)	0.43	510.2	150.00
TOTAL AREA(ACRES) =		510.2				

 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1129.32	40.80	0.741	0.50 (0.43)	0.85	2829.2	31100.00
2	1089.51	59.06	0.609	0.50 (0.42)	0.84	4356.7	13100.00
3	1067.44	61.52	0.598	0.50 (0.42)	0.84	4518.2	13200.00
4	1059.85	62.01	0.596	0.50 (0.42)	0.84	4540.5	13210.00
5	668.75	92.60	0.495	0.50 (0.42)	0.83	5709.4	13000.00
6	607.57	97.06	0.486	0.50 (0.42)	0.83	5735.0	13010.00
LONGEST FLOWPATH FROM NODE		13010.00 TO NODE 13305.00 = 41886.54 FEET.					

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	448.39	14.96	1.308	0.50 (0.22)	0.43	429.7	120.00
2	443.05	15.30	1.293	0.50 (0.21)	0.43	435.1	110.00
3	375.74	23.09	1.028	0.50 (0.21)	0.42	501.8	100.00
4	332.86	27.58	0.923	0.50 (0.22)	0.43	510.2	150.00
LONGEST FLOWPATH FROM NODE		150.00 TO NODE 13305.00 = 9867.00 FEET.					

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1577.71	14.96	1.308	0.50 (0.36)	0.73	1466.7	120.00
2	1572.37	15.30	1.293	0.50 (0.36)	0.73	1496.0	110.00
3	1505.06	23.09	1.028	0.50 (0.38)	0.75	2102.9	100.00
4	1462.18	27.58	0.923	0.50 (0.38)	0.76	2422.8	150.00
5	1376.60	40.80	0.741	0.50 (0.39)	0.79	3339.4	31100.00
6	1274.30	59.06	0.609	0.50 (0.40)	0.80	4866.9	13100.00
7	1247.04	61.52	0.598	0.50 (0.40)	0.80	5028.4	13200.00
8	1238.65	62.01	0.596	0.50 (0.40)	0.80	5050.7	13210.00
9	800.92	92.60	0.495	0.50 (0.40)	0.80	6219.6	13000.00

10 737.39 97.06 0.486 0.50 (0.40) 0.80 6245.2 13010.00
 TOTAL AREA(ACRES) = 6245.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 1577.71 Tc(MIN.) = 14.955
 EFFECTIVE AREA(ACRES) = 1466.72 AREA-AVERAGED Fm(INCH/HR) = 0.36
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6245.2
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

 FLOW PROCESS FROM NODE 13305.00 TO NODE 13306.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 315.00 DOWNSTREAM(FEET) = 245.50
 CHANNEL LENGTH THRU SUBAREA(FEET) = 4408.41 CHANNEL SLOPE = 0.0158
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
 * 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.059

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.40	0.50	1.000	-
USER-DEFINED	-	9.20	0.50	1.000	-
USER-DEFINED	-	1.00	0.50	1.000	-
USER-DEFINED	-	1.30	0.50	1.000	-
USER-DEFINED	-	2.40	0.50	1.000	-
USER-DEFINED	-	4.10	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1582.35

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.47

AVERAGE FLOW DEPTH(FEET) = 7.10 TRAVEL TIME(MIN.) = 7.02

Tc(MIN.) = 21.97

SUBAREA AREA(ACRES) = 18.40 SUBAREA RUNOFF(CFS) = 9.26

EFFECTIVE AREA(ACRES) = 1485.12 AREA-AVERAGED Fm(INCH/HR) = 0.37

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.73

TOTAL AREA(ACRES) = 6263.6 PEAK FLOW RATE(CFS) = 1577.71

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 7.09 FLOW VELOCITY(FEET/SEC.) = 10.46

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13306.00 = 46294.95 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1577.71	21.97	1.059	0.50 (0.37)	0.73	1485.1	120.00
2	1572.37	22.32	1.050	0.50 (0.37)	0.73	1514.4	110.00
3	1505.06	30.19	0.873	0.50 (0.38)	0.75	2121.3	100.00

4	1462.18	34.73	0.815	0.50	(0.38)	0.77	2441.2	150.00
5	1376.60	48.07	0.681	0.50	(0.39)	0.79	3357.8	31100.00
6	1274.30	66.46	0.581	0.50	(0.40)	0.80	4885.3	13100.00
7	1247.04	68.96	0.572	0.50	(0.40)	0.80	5046.8	13200.00
8	1238.65	69.46	0.571	0.50	(0.40)	0.80	5069.1	13210.00
9	800.92	100.91	0.479	0.50	(0.40)	0.80	6238.0	13000.00
10	737.39	105.55	0.469	0.50	(0.40)	0.80	6263.6	13010.00

NEW PEAK FLOW DATA ARE:
PEAK FLOW RATE(CFS) = 1577.71 Tc(MIN.) = 21.97
AREA-AVERAGED Fm(INCH/HR) = 0.37 AREA-AVERAGED Fp(INCH/HR) = 0.50
AREA-AVERAGED Ap = 0.73 EFFECTIVE AREA(ACRES) = 1485.12

FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 21.97
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.059
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	19.20	0.50	1.000	-
USER-DEFINED	-	20.90	0.50	1.000	-
USER-DEFINED	-	4.10	0.50	1.000	-
USER-DEFINED	-	0.50	0.50	1.000	-
USER-DEFINED	-	4.30	0.50	1.000	-
USER-DEFINED	-	0.60	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 49.60 SUBAREA RUNOFF(CFS) = 24.96
EFFECTIVE AREA(ACRES) = 1534.72 AREA-AVERAGED Fm(INCH/HR) = 0.37
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.74
TOTAL AREA(ACRES) = 6313.2 PEAK FLOW RATE(CFS) = 1577.71
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 21.97
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.059
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.80	0.30	1.000	65

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 0.80 SUBAREA RUNOFF(CFS) = 0.55
EFFECTIVE AREA(ACRES) = 1535.52 AREA-AVERAGED Fm(INCH/HR) = 0.37
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.74
TOTAL AREA(ACRES) = 6314.0 PEAK FLOW RATE(CFS) = 1577.71
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====

MAINLINE Tc(MIN.) = 21.97
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.059

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.10	0.50	0.850	-
USER-DEFINED	-	0.10	0.50	1.000	-
USER-DEFINED	-	0.10	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	0.40	0.50	0.850	-
USER-DEFINED	-	0.40	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.942
SUBAREA AREA(ACRES) = 1.30 SUBAREA RUNOFF(CFS) = 0.69
EFFECTIVE AREA(ACRES) = 1536.82 AREA-AVERAGED Fm(INCH/HR) = 0.37
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.74
TOTAL AREA(ACRES) = 6315.3 PEAK FLOW RATE(CFS) = 1577.71
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 21.97
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.059

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.80	0.50	0.900	-
USER-DEFINED	-	0.80	0.50	1.000	-
USER-DEFINED	-	1.00	0.50	1.000	-
USER-DEFINED	-	1.10	0.50	1.000	-
USER-DEFINED	-	1.10	0.50	0.100	-
USER-DEFINED	-	2.80	0.50	0.900	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.822
SUBAREA AREA(ACRES) = 7.60 SUBAREA RUNOFF(CFS) = 4.43
EFFECTIVE AREA(ACRES) = 1544.42 AREA-AVERAGED Fm(INCH/HR) = 0.37
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.74
TOTAL AREA(ACRES) = 6322.9 PEAK FLOW RATE(CFS) = 1577.71
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 21.97
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.059

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	3.50	0.50	0.100	-
USER-DEFINED	-	5.00	0.50	1.000	-

USER-DEFINED - 6.70 0.50 0.900 -
 USER-DEFINED - 7.80 0.50 1.000 -
 USER-DEFINED - 10.80 0.50 1.000 -
 USER-DEFINED - 13.80 0.50 0.100 -
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.659
 SUBAREA AREA(ACRES) = 47.60 SUBAREA RUNOFF(CFS) = 31.26
 EFFECTIVE AREA(ACRES) = 1592.02 AREA-AVERAGED Fm(INCH/HR) = 0.37
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.74
 TOTAL AREA(ACRES) = 6370.5 PEAK FLOW RATE(CFS) = 1577.71
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 21.97
 * 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.059
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	21.54	0.50	1.000	-
USER-DEFINED	-	36.64	0.50	1.000	-

 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 58.18 SUBAREA RUNOFF(CFS) = 29.28
 EFFECTIVE AREA(ACRES) = 1650.20 AREA-AVERAGED Fm(INCH/HR) = 0.37
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.75
 TOTAL AREA(ACRES) = 6428.7 PEAK FLOW RATE(CFS) = 1577.71
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13307.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 245.50 DOWNSTREAM(FEET) = 220.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1543.21 CHANNEL SLOPE = 0.0165
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
 CHANNEL FLOW THRU SUBAREA(CFS) = 1577.71
 FLOW VELOCITY(FEET/SEC.) = 10.66 FLOW DEPTH(FEET) = 7.02
 TRAVEL TIME(MIN.) = 2.41 Tc(MIN.) = 24.39
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13307.00 = 47838.16 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1577.71	24.39	0.991	0.50(0.37)	0.75	1650.2	120.00
2	1572.37	24.73	0.982	0.50(0.37)	0.75	1679.5	110.00
3	1505.06	32.63	0.842	0.50(0.38)	0.76	2286.4	100.00
4	1462.18	37.19	0.784	0.50(0.39)	0.77	2606.2	150.00
5	1376.60	50.56	0.662	0.50(0.40)	0.79	3522.9	31100.00
6	1274.30	69.01	0.572	0.50(0.40)	0.80	5050.4	13100.00
7	1247.04	71.52	0.563	0.50(0.40)	0.80	5211.9	13200.00
8	1238.65	72.03	0.562	0.50(0.40)	0.80	5234.2	13210.00

9 800.92 103.77 0.473 0.50(0.40) 0.80 6403.1 13000.00
 10 737.39 108.47 0.464 0.50(0.40) 0.80 6428.7 13010.00
 NEW PEAK FLOW DATA ARE:
 PEAK FLOW RATE(CFS) = 1577.71 Tc(MIN.) = 24.39
 AREA-AVERAGED Fm(INCH/HR) = 0.37 AREA-AVERAGED Fp(INCH/HR) = 0.50
 AREA-AVERAGED Ap = 0.75 EFFECTIVE AREA(ACRES) = 1650.20

 FLOW PROCESS FROM NODE 13307.00 TO NODE 13307.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 24.39
 * 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.991
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.20	0.50	0.100	-
USER-DEFINED	-	0.10	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	3.70	0.50	1.000	-
USER-DEFINED	-	0.30	0.50	0.100	-
USER-DEFINED	-	3.20	0.50	1.000	-

 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.942
 SUBAREA AREA(ACRES) = 7.70 SUBAREA RUNOFF(CFS) = 3.61
 EFFECTIVE AREA(ACRES) = 1657.90 AREA-AVERAGED Fm(INCH/HR) = 0.37
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.75
 TOTAL AREA(ACRES) = 6436.4 PEAK FLOW RATE(CFS) = 1577.71
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13307.00 TO NODE 13307.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 24.39
 * 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.991
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	3.60	0.50	1.000	-
USER-DEFINED	-	1.90	0.50	1.000	-
USER-DEFINED	-	0.60	0.50	1.000	-

 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 6.10 SUBAREA RUNOFF(CFS) = 2.70
 EFFECTIVE AREA(ACRES) = 1664.00 AREA-AVERAGED Fm(INCH/HR) = 0.37
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.75
 TOTAL AREA(ACRES) = 6442.5 PEAK FLOW RATE(CFS) = 1577.71
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13307.00 TO NODE 13308.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 220.00 DOWNSTREAM(FEET) = 212.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 925.62 CHANNEL SLOPE = 0.0086
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
 CHANNEL FLOW THRU SUBAREA(CFS) = 1577.71
 FLOW VELOCITY(FEET/SEC.) = 8.36 FLOW DEPTH(FEET) = 7.93
 TRAVEL TIME(MIN.) = 1.85 Tc(MIN.) = 26.23
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13308.00 = 48763.78 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap (DECIMAL)	Ae (ACRES)	HEADWATER NODE
1	1577.71	26.23	0.950	0.50(0.37)	0.75	1664.0	120.00
2	1572.37	26.58	0.943	0.50(0.38)	0.75	1693.3	110.00
3	1505.06	34.50	0.818	0.50(0.38)	0.76	2300.2	100.00
4	1462.18	39.07	0.760	0.50(0.39)	0.77	2620.0	150.00
5	1376.60	52.47	0.650	0.50(0.40)	0.79	3536.7	31100.00
6	1274.30	70.95	0.565	0.50(0.40)	0.80	5064.2	13100.00
7	1247.04	73.48	0.557	0.50(0.40)	0.80	5225.7	13200.00
8	1238.65	73.99	0.555	0.50(0.40)	0.80	5248.0	13210.00
9	800.92	105.96	0.469	0.50(0.40)	0.80	6416.9	13000.00
10	737.39	110.70	0.459	0.50(0.40)	0.80	6442.5	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 1577.71 Tc(MIN.) = 26.23
 AREA-AVERAGED Fm(INCH/HR) = 0.37 AREA-AVERAGED Fp(INCH/HR) = 0.50
 AREA-AVERAGED Ap = 0.75 EFFECTIVE AREA(ACRES) = 1664.00

 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 26.23

* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.950

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.10	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	5.00	0.50	1.000	-
USER-DEFINED	-	3.20	0.50	0.100	-
USER-DEFINED	-	0.10	0.50	1.000	-
USER-DEFINED	-	0.90	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.697

SUBAREA AREA(ACRES) = 9.50 SUBAREA RUNOFF(CFS) = 5.14

EFFECTIVE AREA(ACRES) = 1673.50 AREA-AVERAGED Fm(INCH/HR) = 0.37

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.75

TOTAL AREA(ACRES) = 6452.0 PEAK FLOW RATE(CFS) = 1577.71

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 26.23

* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.950

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.30	0.50	0.200	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	1.00	0.50	1.000	-
USER-DEFINED	-	41.90	0.50	0.100	-
USER-DEFINED	-	7.20	0.50	1.000	-
USER-DEFINED	-	25.00	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.498

SUBAREA AREA(ACRES) = 75.60 SUBAREA RUNOFF(CFS) = 47.66

EFFECTIVE AREA(ACRES) = 1749.10 AREA-AVERAGED Fm(INCH/HR) = 0.37

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.74

TOTAL AREA(ACRES) = 6527.6 PEAK FLOW RATE(CFS) = 1577.71

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 26.23

* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.950

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.10	0.50	0.850	-
USER-DEFINED	-	0.90	0.50	1.000	-
USER-DEFINED	-	0.30	0.50	0.600	-
USER-DEFINED	-	13.20	0.50	1.000	-
USER-DEFINED	-	0.50	0.50	0.200	-
USER-DEFINED	-	0.60	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.966

SUBAREA AREA(ACRES) = 15.60 SUBAREA RUNOFF(CFS) = 6.55

EFFECTIVE AREA(ACRES) = 1764.70 AREA-AVERAGED Fm(INCH/HR) = 0.37

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.74

TOTAL AREA(ACRES) = 6543.2 PEAK FLOW RATE(CFS) = 1577.71

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 26.23

* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.950

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	33.90	0.50	0.100	-
USER-DEFINED	-	17.60	0.50	1.000	-
USER-DEFINED	-	16.80	0.50	1.000	-
USER-DEFINED	-	0.60	0.50	0.200	-
USER-DEFINED	-	1.50	0.50	0.400	-
USER-DEFINED	-	10.00	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.603
 SUBAREA AREA (ACRES) = 80.40 SUBAREA RUNOFF (CFS) = 46.88
 EFFECTIVE AREA (ACRES) = 1845.10 AREA-AVERAGED Fm (INCH/HR) = 0.37
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.73
 TOTAL AREA (ACRES) = 6623.6 PEAK FLOW RATE (CFS) = 1577.71
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) = 26.23
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.950
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.30	0.50	0.600	-
USER-DEFINED	-	0.70	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.880
 SUBAREA AREA (ACRES) = 1.00 SUBAREA RUNOFF (CFS) = 0.46
 EFFECTIVE AREA (ACRES) = 1846.10 AREA-AVERAGED Fm (INCH/HR) = 0.37
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.73
 TOTAL AREA (ACRES) = 6624.6 PEAK FLOW RATE (CFS) = 1577.71
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) = 26.23
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.950
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.30	0.50	1.000	-
USER-DEFINED	-	0.80	0.50	1.000	-
USER-DEFINED	-	0.50	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	0.30	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 2.10 SUBAREA RUNOFF (CFS) = 0.85
 EFFECTIVE AREA (ACRES) = 1848.20 AREA-AVERAGED Fm (INCH/HR) = 0.37
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.73
 TOTAL AREA (ACRES) = 6626.7 PEAK FLOW RATE (CFS) = 1577.71
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) = 26.23
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.950
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.20	0.50	1.000	-
USER-DEFINED	-	0.50	0.50	1.000	-
USER-DEFINED	-	1.70	0.50	0.850	-
USER-DEFINED	-	7.20	0.50	1.000	-
USER-DEFINED	-	1.00	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.978
 SUBAREA AREA (ACRES) = 11.60 SUBAREA RUNOFF (CFS) = 4.81
 EFFECTIVE AREA (ACRES) = 1859.80 AREA-AVERAGED Fm (INCH/HR) = 0.37
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.74
 TOTAL AREA (ACRES) = 6638.3 PEAK FLOW RATE (CFS) = 1577.71
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<

 FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU05EV29.DNA
 MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11241.12	16.44	0.50 (0.40)	0.80	3640.9	50400.00
2	11962.72	24.19	0.50 (0.40)	0.80	5430.4	410.00
3	11721.52	30.34	0.50 (0.41)	0.82	7395.5	50280.00
4	11362.73	38.34	0.50 (0.43)	0.85	9792.6	600.00
5	10335.30	65.57	0.50 (0.46)	0.91	16957.9	11801.00
6	10068.71	76.91	0.50 (0.46)	0.92	20190.4	11500.00
7	9724.38	88.89	0.50 (0.47)	0.94	24234.9	11000.00
8	9312.72	105.29	0.50 (0.47)	0.95	31100.5	12500.00
9	9106.17	111.48	0.50 (0.48)	0.95	33969.9	10900.00
10	8447.42	120.17	0.50 (0.48)	0.96	37299.1	11130.00
11	7760.93	131.63	0.50 (0.48)	0.96	40971.6	11620.00
12	6703.19	147.43	0.50 (0.48)	0.96	45497.4	12400.00
13	5853.87	158.84	0.50 (0.48)	0.96	47803.6	12201.00
14	5241.53	168.16	0.50 (0.48)	0.96	49094.2	12111.00
15	4315.31	183.87	0.50 (0.48)	0.96	51017.1	12261.00
16	3843.52	193.16	0.50 (0.48)	0.97	51828.2	10200.00
17	3273.45	208.54	0.50 (0.48)	0.97	53066.2	10300.00
18	3041.35	215.39	0.50 (0.48)	0.97	53418.4	12010.00
19	2565.50	235.81	0.50 (0.48)	0.97	53746.7	12000.00
20	1585.63	304.14	0.50 (0.48)	0.97	54417.5	10100.00
TOTAL AREA (ACRES) =						54417.5

 FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11241.12	16.44	0.50 (0.40)	0.80		3640.9	50400.00
2	11962.72	24.19	0.50 (0.40)	0.80		5430.4	410.00
3	11721.52	30.34	0.50 (0.41)	0.82		7395.5	50280.00
4	11362.73	38.34	0.50 (0.43)	0.85		9792.6	600.00
5	10335.30	65.57	0.50 (0.46)	0.91		16957.9	11801.00
6	10068.71	76.91	0.50 (0.46)	0.92		20190.4	11500.00
7	9724.38	88.89	0.50 (0.47)	0.94		24234.9	11000.00
8	9312.72	105.29	0.50 (0.47)	0.95		31100.5	12500.00
9	9106.17	111.48	0.50 (0.48)	0.95		33969.9	10900.00
10	8447.42	120.17	0.50 (0.48)	0.96		37299.1	11130.00
11	7760.93	131.63	0.50 (0.48)	0.96		40971.6	11620.00
12	6703.19	147.43	0.50 (0.48)	0.96		45497.4	12400.00
13	5853.87	158.84	0.50 (0.48)	0.96		47803.6	12201.00
14	5241.53	168.16	0.50 (0.48)	0.96		49094.2	12111.00
15	4315.31	183.87	0.50 (0.48)	0.96		51017.1	12261.00
16	3843.52	193.16	0.50 (0.48)	0.97		51828.2	10200.00
17	3273.45	208.54	0.50 (0.48)	0.97		53066.2	10300.00
18	3041.35	215.39	0.50 (0.48)	0.97		53418.4	12010.00
19	2565.50	235.81	0.50 (0.48)	0.97		53746.7	12000.00
20	1585.63	304.14	0.50 (0.48)	0.97		54417.5	10100.00
TOTAL AREA (ACRES) =							54417.5

 FLOW PROCESS FROM NODE 12904.00 TO NODE 13308.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 213.00 DOWNSTREAM(FEET) = 212.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1389.52 CHANNEL SLOPE = 0.0007
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00

==>>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL
 CAPACITY(NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM
 ALLOWABLE DEPTH).
 AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM
 ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

CHANNEL FLOW THRU SUBAREA(CFS) = 11962.72
 FLOW VELOCITY(FEET/SEC.) = 9.97 FLOW DEPTH(FEET) = 20.00
 TRAVEL TIME(MIN.) = 2.32 Tc(MIN.) = 26.52
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118067.44 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11241.12	18.91	1.156	0.50 (0.40)	0.80	3640.9	50400.00
2	11962.72	26.52	0.944	0.50 (0.40)	0.80	5430.4	410.00
3	11721.52	32.71	0.841	0.50 (0.41)	0.82	7395.5	50280.00
4	11362.73	40.78	0.741	0.50 (0.43)	0.85	9792.6	600.00
5	10335.30	68.26	0.575	0.50 (0.46)	0.91	16957.9	11801.00
6	10068.71	79.67	0.535	0.50 (0.46)	0.92	20190.4	11500.00
7	9724.38	91.74	0.497	0.50 (0.47)	0.94	24234.9	11000.00
8	9312.72	108.27	0.464	0.50 (0.47)	0.95	31100.5	12500.00

9	9106.17	114.54	0.452	0.50 (0.48)	0.95	33969.9	10900.00
10	8447.42	123.46	0.437	0.50 (0.48)	0.96	37299.1	11130.00
11	7760.93	135.22	0.423	0.50 (0.48)	0.96	40971.6	11620.00
12	6703.19	151.38	0.403	0.50 (0.48)	0.96	45497.4	12400.00
13	5853.87	162.93	0.389	0.50 (0.48)	0.96	47803.6	12201.00
14	5241.53	172.36	0.378	0.50 (0.48)	0.96	49094.2	12111.00
15	4315.31	188.28	0.365	0.50 (0.48)	0.96	51017.1	12261.00
16	3843.52	197.71	0.359	0.50 (0.48)	0.97	51828.2	10200.00
17	3273.45	213.27	0.351	0.50 (0.48)	0.97	53066.2	10300.00
18	3041.35	220.21	0.347	0.50 (0.48)	0.97	53418.4	12010.00
19	2565.50	240.83	0.336	0.50 (0.48)	0.97	53746.7	12000.00
20	1585.63	309.81	0.299	0.50 (0.48)	0.97	54417.5	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 11962.72 Tc(MIN.) = 26.52
 AREA-AVERAGED Fm(INCH/HR) = 0.40 AREA-AVERAGED Fp(INCH/HR) = 0.50
 AREA-AVERAGED Ap = 0.80 EFFECTIVE AREA(ACRES) = 5430.45

FLOW PROCESS FROM NODE 13307.00 TO NODE 13308.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11241.12	18.91	1.156	0.50 (0.40)	0.80	3640.9	50400.00
2	11962.72	26.52	0.944	0.50 (0.40)	0.80	5430.4	410.00
3	11721.52	32.71	0.841	0.50 (0.41)	0.82	7395.5	50280.00
4	11362.73	40.78	0.741	0.50 (0.43)	0.85	9792.6	600.00
5	10335.30	68.26	0.575	0.50 (0.46)	0.91	16957.9	11801.00
6	10068.71	79.67	0.535	0.50 (0.46)	0.92	20190.4	11500.00
7	9724.38	91.74	0.497	0.50 (0.47)	0.94	24234.9	11000.00
8	9312.72	108.27	0.464	0.50 (0.47)	0.95	31100.5	12500.00
9	9106.17	114.54	0.452	0.50 (0.48)	0.95	33969.9	10900.00
10	8447.42	123.46	0.437	0.50 (0.48)	0.96	37299.1	11130.00
11	7760.93	135.22	0.423	0.50 (0.48)	0.96	40971.6	11620.00
12	6703.19	151.38	0.403	0.50 (0.48)	0.96	45497.4	12400.00
13	5853.87	162.93	0.389	0.50 (0.48)	0.96	47803.6	12201.00
14	5241.53	172.36	0.378	0.50 (0.48)	0.96	49094.2	12111.00
15	4315.31	188.28	0.365	0.50 (0.48)	0.96	51017.1	12261.00
16	3843.52	197.71	0.359	0.50 (0.48)	0.97	51828.2	10200.00
17	3273.45	213.27	0.351	0.50 (0.48)	0.97	53066.2	10300.00
18	3041.35	220.21	0.347	0.50 (0.48)	0.97	53418.4	12010.00
19	2565.50	240.83	0.336	0.50 (0.48)	0.97	53746.7	12000.00
20	1585.63	309.81	0.299	0.50 (0.48)	0.97	54417.5	10100.00
LONGEST FLOWPATH FROM NODE							10100.00 TO NODE 13308.00 = 118067.44 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1577.71	26.23	0.950	0.50 (0.37)	0.74	1859.8	120.00
2	1572.37	26.58	0.943	0.50 (0.37)	0.74	1889.1	110.00
3	1505.06	34.50	0.818	0.50 (0.38)	0.75	2496.0	100.00
4	1462.18	39.07	0.760	0.50 (0.38)	0.76	2815.8	150.00
5	1376.60	52.47	0.650	0.50 (0.39)	0.79	3732.5	31100.00
6	1274.30	70.95	0.565	0.50 (0.40)	0.79	5260.0	13100.00
7	1247.04	73.48	0.557	0.50 (0.40)	0.79	5421.5	13200.00

8 1238.65 73.99 0.555 0.50(0.40) 0.79 5443.8 13210.00
 9 800.92 105.96 0.469 0.50(0.40) 0.80 6612.7 13000.00
 10 737.39 110.70 0.459 0.50(0.40) 0.80 6638.3 13010.00
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13308.00 = 48763.78 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12782.65	18.91	1.156	0.50(0.39)	0.78	4981.5	50400.00
2	13513.51	26.23	0.950	0.50(0.39)	0.78	7223.5	120.00
3	13536.08	26.52	0.944	0.50(0.39)	0.78	7314.1	410.00
4	13532.61	26.58	0.943	0.50(0.39)	0.78	7339.8	110.00
5	13241.80	32.71	0.841	0.50(0.40)	0.80	9754.3	50280.00
6	13147.09	34.50	0.818	0.50(0.40)	0.81	10422.6	100.00
7	12901.01	39.07	0.760	0.50(0.41)	0.83	12100.1	150.00
8	12813.98	40.78	0.741	0.50(0.42)	0.83	12725.6	600.00
9	12302.23	52.47	0.650	0.50(0.43)	0.86	16573.4	31100.00
10	11624.52	68.26	0.575	0.50(0.44)	0.88	21995.2	11801.00
11	11546.64	70.95	0.565	0.50(0.44)	0.89	22981.4	13100.00
12	11460.39	73.48	0.557	0.50(0.44)	0.89	23858.1	13200.00
13	11440.12	73.99	0.555	0.50(0.44)	0.89	24024.4	13210.00
14	11229.58	79.67	0.535	0.50(0.45)	0.90	25841.9	11500.00
15	10719.92	91.74	0.497	0.50(0.45)	0.91	30327.9	11000.00
16	10171.25	105.96	0.469	0.50(0.46)	0.92	36752.3	13000.00
17	10082.67	108.27	0.464	0.50(0.46)	0.92	37725.6	12500.00
18	9969.93	110.70	0.459	0.50(0.46)	0.92	38852.6	13010.00
19	9831.45	114.54	0.452	0.50(0.46)	0.93	40608.2	10900.00
20	9148.79	123.46	0.437	0.50(0.47)	0.93	43937.4	11130.00
21	8439.65	135.22	0.423	0.50(0.47)	0.94	47609.9	11620.00
22	7350.77	151.38	0.403	0.50(0.47)	0.94	52135.7	12400.00
23	6479.19	162.93	0.389	0.50(0.47)	0.94	54441.9	12201.00
24	5848.69	172.36	0.378	0.50(0.47)	0.94	55732.5	12111.00
25	4900.58	188.28	0.365	0.50(0.47)	0.95	57655.4	12261.00
26	4420.64	197.71	0.359	0.50(0.47)	0.95	58466.5	10200.00
27	3837.10	213.27	0.351	0.50(0.47)	0.95	59704.5	10300.00
28	3599.00	220.21	0.347	0.50(0.47)	0.95	60056.7	12010.00
29	3105.31	240.83	0.336	0.50(0.47)	0.95	60385.1	12000.00
30	2065.75	309.81	0.299	0.50(0.47)	0.95	61055.8	10100.00

TOTAL AREA (ACRES) = 61055.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 13536.08 Tc(MIN.) = 26.516
 EFFECTIVE AREA(ACRES) = 7314.13 AREA-AVERAGED Fm(INCH/HR) = 0.39
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.78
 TOTAL AREA(ACRES) = 61055.8
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118067.44 FEET.

=====
 END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 61055.8 TC(MIN.) = 26.52
 EFFECTIVE AREA(ACRES) = 7314.13 AREA-AVERAGED Fm(INCH/HR) = 0.39
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.782
 PEAK FLOW RATE(CFS) = 13536.08

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12782.65	18.91	1.156	0.50(0.39)	0.78	4981.5	50400.00
2	13513.51	26.23	0.950	0.50(0.39)	0.78	7223.5	120.00

3	13536.08	26.52	0.944	0.50(0.39)	0.78	7314.1	410.00
4	13532.61	26.58	0.943	0.50(0.39)	0.78	7339.8	110.00
5	13241.80	32.71	0.841	0.50(0.40)	0.80	9754.3	50280.00
6	13147.09	34.50	0.818	0.50(0.40)	0.81	10422.6	100.00
7	12901.01	39.07	0.760	0.50(0.41)	0.83	12100.1	150.00
8	12813.98	40.78	0.741	0.50(0.42)	0.83	12725.6	600.00
9	12302.23	52.47	0.650	0.50(0.43)	0.86	16573.4	31100.00
10	11624.52	68.26	0.575	0.50(0.44)	0.88	21995.2	11801.00
11	11546.64	70.95	0.565	0.50(0.44)	0.89	22981.4	13100.00
12	11460.39	73.48	0.557	0.50(0.44)	0.89	23858.1	13200.00
13	11440.12	73.99	0.555	0.50(0.44)	0.89	24024.4	13210.00
14	11229.58	79.67	0.535	0.50(0.45)	0.90	25841.9	11500.00
15	10719.92	91.74	0.497	0.50(0.45)	0.91	30327.9	11000.00
16	10171.25	105.96	0.469	0.50(0.46)	0.92	36752.3	13000.00
17	10082.67	108.27	0.464	0.50(0.46)	0.92	37725.6	12500.00
18	9969.93	110.70	0.459	0.50(0.46)	0.92	38852.6	13010.00
19	9831.45	114.54	0.452	0.50(0.46)	0.93	40608.2	10900.00
20	9148.79	123.46	0.437	0.50(0.47)	0.93	43937.4	11130.00
21	8439.65	135.22	0.423	0.50(0.47)	0.94	47609.9	11620.00
22	7350.77	151.38	0.403	0.50(0.47)	0.94	52135.7	12400.00
23	6479.19	162.93	0.389	0.50(0.47)	0.94	54441.9	12201.00
24	5848.69	172.36	0.378	0.50(0.47)	0.94	55732.5	12111.00
25	4900.58	188.28	0.365	0.50(0.47)	0.95	57655.4	12261.00
26	4420.64	197.71	0.359	0.50(0.47)	0.95	58466.5	10200.00
27	3837.10	213.27	0.351	0.50(0.47)	0.95	59704.5	10300.00
28	3599.00	220.21	0.347	0.50(0.47)	0.95	60056.7	12010.00
29	3105.31	240.83	0.336	0.50(0.47)	0.95	60385.1	12000.00
30	2065.75	309.81	0.299	0.50(0.47)	0.95	61055.8	10100.00

=====
 END OF RATIONAL METHOD ANALYSIS
 =====

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2010 Advanced Engineering Software (aes)
Ver. 17.0 Release Date: 07/01/2010 License ID 1527

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 134 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 5-YR EV AUG 2023 ROKAMOTO *

FILE NAME: RU05EV34.DAT
TIME/DATE OF STUDY: 23:46 08/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 5.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 2.630
- 2) 10.00; 1.755
- 3) 15.00; 1.301
- 4) 20.00; 1.113
- 5) 25.00; 0.972
- 6) 30.00; 0.874
- 7) 40.00; 0.746
- 8) 50.00; 0.663
- 9) 60.00; 0.602
- 10) 90.00; 0.498
- 11) 120.00; 0.439
- 12) 180.00; 0.368
- 13) 360.00; 0.270
- 14) 1200.00; 0.118

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU05EV33.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12782.65	18.91	0.50 (0.39)	0.78	4981.5	50400.00
2	13536.08	26.52	0.50 (0.39)	0.78	7314.1	410.00
3	13241.80	32.71	0.50 (0.40)	0.80	9754.3	50280.00
4	12901.01	39.07	0.50 (0.41)	0.83	12100.1	150.00
5	12302.23	52.47	0.50 (0.43)	0.86	16573.4	31100.00
6	11624.52	68.26	0.50 (0.44)	0.88	21995.2	11801.00
7	11229.58	79.67	0.50 (0.45)	0.90	25841.9	11500.00
8	10719.92	91.74	0.50 (0.45)	0.91	30327.9	11000.00
9	10171.25	105.96	0.50 (0.46)	0.92	36752.3	13000.00
10	9148.79	123.46	0.50 (0.47)	0.93	43937.4	11130.00
11	8439.65	135.22	0.50 (0.47)	0.94	47609.9	11620.00
12	7350.77	151.38	0.50 (0.47)	0.94	52135.7	12400.00
13	6479.19	162.93	0.50 (0.47)	0.94	54441.9	12201.00
14	5848.69	172.36	0.50 (0.47)	0.94	55732.5	12111.00
15	4900.58	188.28	0.50 (0.47)	0.95	57655.4	12261.00
16	4420.64	197.71	0.50 (0.47)	0.95	58466.5	10200.00
17	3837.10	213.27	0.50 (0.47)	0.95	59704.5	10300.00
18	3599.00	220.21	0.50 (0.47)	0.95	60056.7	12010.00
19	3105.31	240.83	0.50 (0.47)	0.95	60385.1	12000.00
20	2065.75	309.81	0.50 (0.47)	0.95	61055.8	10100.00
TOTAL AREA(ACRES) =						61055.8

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12782.65	18.91	0.50 (0.39)	0.78	4981.5	50400.00
2	13536.08	26.52	0.50 (0.39)	0.78	7314.1	410.00
3	13241.80	32.71	0.50 (0.40)	0.80	9754.3	50280.00
4	12901.01	39.07	0.50 (0.41)	0.83	12100.1	150.00
5	12302.23	52.47	0.50 (0.43)	0.86	16573.4	31100.00
6	11624.52	68.26	0.50 (0.44)	0.88	21995.2	11801.00
7	11229.58	79.67	0.50 (0.45)	0.90	25841.9	11500.00
8	10719.92	91.74	0.50 (0.45)	0.91	30327.9	11000.00
9	10171.25	105.96	0.50 (0.46)	0.92	36752.3	13000.00
10	9148.79	123.46	0.50 (0.47)	0.93	43937.4	11130.00
11	8439.65	135.22	0.50 (0.47)	0.94	47609.9	11620.00
12	7350.77	151.38	0.50 (0.47)	0.94	52135.7	12400.00
13	6479.19	162.93	0.50 (0.47)	0.94	54441.9	12201.00

14	5848.69	172.36	0.50	(0.47)	0.94	55732.5	12111.00
15	4900.58	188.28	0.50	(0.47)	0.95	57655.4	12261.00
16	4420.64	197.71	0.50	(0.47)	0.95	58466.5	10200.00
17	3837.10	213.27	0.50	(0.47)	0.95	59704.5	10300.00
18	3599.00	220.21	0.50	(0.47)	0.95	60056.7	12010.00
19	3105.31	240.83	0.50	(0.47)	0.95	60385.1	12000.00
20	2065.75	309.81	0.50	(0.47)	0.95	61055.8	10100.00

TOTAL AREA (ACRES) = 61055.8

FLOW PROCESS FROM NODE 13308.00 TO NODE 13402.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 212.00 DOWNSTREAM(FEET) = 209.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 623.02 CHANNEL SLOPE = 0.0048
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
 CHANNEL FLOW THRU SUBAREA(CFS) = 13536.08
 FLOW VELOCITY(FEET/SEC.) = 14.25 FLOW DEPTH(FEET) = 17.79
 TRAVEL TIME(MIN.) = 0.73 Tc(MIN.) = 27.24
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118690.46 FEET.

FLOW PROCESS FROM NODE 13402.00 TO NODE 13402.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<

PEAK FLOWRATE TABLE FILE NAME: P505XX05.DNA
 MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	69.44	20.56	0.50 (0.48)	0.96	146.4	50500.00
TOTAL AREA (ACRES) =						146.4

FLOW PROCESS FROM NODE 13402.00 TO NODE 13402.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12782.65	19.65	1.126	0.50 (0.39)	0.78	4981.5	50400.00
2	13536.08	27.24	0.928	0.50 (0.39)	0.78	7314.1	410.00
3	13241.80	33.44	0.830	0.50 (0.40)	0.80	9754.3	50280.00
4	12901.01	39.81	0.748	0.50 (0.41)	0.83	12100.1	150.00
5	12302.23	53.22	0.643	0.50 (0.43)	0.86	16573.4	31100.00
6	11624.52	69.02	0.571	0.50 (0.44)	0.88	21995.2	11801.00
7	11229.58	80.43	0.531	0.50 (0.45)	0.90	25841.9	11500.00
8	10719.92	92.52	0.493	0.50 (0.45)	0.91	30327.9	11000.00
9	10171.25	106.74	0.465	0.50 (0.46)	0.92	36752.3	13000.00
10	9148.79	124.27	0.434	0.50 (0.47)	0.93	43937.4	11130.00
11	8439.65	136.04	0.420	0.50 (0.47)	0.94	47609.9	11620.00
12	7350.77	152.23	0.401	0.50 (0.47)	0.94	52135.7	12400.00
13	6479.19	163.81	0.387	0.50 (0.47)	0.94	54441.9	12201.00

14	5848.69	173.26	0.376	0.50 (0.47)	0.94	55732.5	12111.00
15	4900.58	189.22	0.363	0.50 (0.47)	0.95	57655.4	12261.00
16	4420.64	198.67	0.358	0.50 (0.47)	0.95	58466.5	10200.00
17	3837.10	214.27	0.349	0.50 (0.47)	0.95	59704.5	10300.00
18	3599.00	221.22	0.346	0.50 (0.47)	0.95	60056.7	12010.00
19	3105.31	241.88	0.334	0.50 (0.47)	0.95	60385.1	12000.00
20	2065.75	310.97	0.297	0.50 (0.47)	0.95	61055.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118690.46 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	69.44	20.56	1.097	0.50 (0.48)	0.96	146.4	50500.00
LONGEST FLOWPATH FROM NODE							50500.00 TO NODE 13402.00 = 5416.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12852.09	19.65	1.126	0.50 (0.39)	0.79	5121.4	50400.00
2	12942.69	20.56	1.097	0.50 (0.39)	0.79	5408.4	50500.00
3	13586.50	27.24	0.928	0.50 (0.39)	0.79	7460.5	410.00
4	13281.20	33.44	0.830	0.50 (0.40)	0.81	9900.7	50280.00
5	12931.24	39.81	0.748	0.50 (0.41)	0.83	12246.5	150.00
6	12320.66	53.22	0.643	0.50 (0.43)	0.86	16719.8	31100.00
7	11634.78	69.02	0.571	0.50 (0.44)	0.88	22141.6	11801.00
8	11235.39	80.43	0.531	0.50 (0.45)	0.90	25988.3	11500.00
9	10722.22	92.52	0.493	0.50 (0.45)	0.91	30474.3	11000.00
10	10173.41	106.74	0.465	0.50 (0.46)	0.92	36898.7	13000.00
11	9150.80	124.27	0.434	0.50 (0.47)	0.93	44083.8	11130.00
12	8441.61	136.04	0.420	0.50 (0.47)	0.94	47756.3	11620.00
13	7352.64	152.23	0.401	0.50 (0.47)	0.94	52282.1	12400.00
14	6480.99	163.81	0.387	0.50 (0.47)	0.94	54588.3	12201.00
15	5850.43	173.26	0.376	0.50 (0.47)	0.94	55878.9	12111.00
16	4902.27	189.22	0.363	0.50 (0.47)	0.95	57801.8	12261.00
17	4422.30	198.67	0.358	0.50 (0.47)	0.95	58612.9	10200.00
18	3838.72	214.27	0.349	0.50 (0.47)	0.95	59850.9	10300.00
19	3600.61	221.22	0.346	0.50 (0.47)	0.95	60203.1	12010.00
20	3106.86	241.88	0.334	0.50 (0.47)	0.95	60531.4	12000.00
21	2067.13	310.97	0.297	0.50 (0.47)	0.95	61202.2	10100.00
TOTAL AREA (ACRES) =						61202.2	

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 13586.50 Tc(MIN.) = 27.245
 EFFECTIVE AREA(ACRES) = 7460.53 AREA-AVERAGED Fm(INCH/HR) = 0.39
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.79
 TOTAL AREA(ACRES) = 61202.2
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118690.46 FEET.

FLOW PROCESS FROM NODE 13402.00 TO NODE 13404.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 209.00 DOWNSTREAM(FEET) = 207.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 395.35 CHANNEL SLOPE = 0.0051
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00

CHANNEL FLOW THRU SUBAREA(CFS) = 13586.50
 FLOW VELOCITY(FEET/SEC.) = 14.53 FLOW DEPTH(FEET) = 17.66
 TRAVEL TIME(MIN.) = 0.45 Tc(MIN.) = 27.70
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119085.81 FEET.

 FLOW PROCESS FROM NODE 13404.00 TO NODE 13404.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P506XX05.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23.28	20.61	0.50 (0.48)	0.97	49.5	50600.00
TOTAL AREA (ACRES) =						49.5

 FLOW PROCESS FROM NODE 13404.00 TO NODE 13404.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12852.09	20.11	1.110	0.50 (0.39)	0.79	5121.4	50400.00
2	12942.69	21.02	1.084	0.50 (0.39)	0.79	5408.4	50500.00
3	13586.50	27.70	0.919	0.50 (0.39)	0.79	7460.5	410.00
4	13281.20	33.90	0.824	0.50 (0.40)	0.81	9900.7	50280.00
5	12931.24	40.27	0.744	0.50 (0.41)	0.83	12246.5	150.00
6	12320.66	53.68	0.641	0.50 (0.43)	0.86	16719.8	31100.00
7	11634.78	69.49	0.569	0.50 (0.44)	0.88	22141.6	11801.00
8	11235.39	80.91	0.530	0.50 (0.45)	0.90	25988.3	11500.00
9	10722.22	93.00	0.492	0.50 (0.45)	0.91	30474.3	11000.00
10	10173.41	107.23	0.464	0.50 (0.46)	0.92	36898.7	13000.00
11	9150.80	124.77	0.433	0.50 (0.47)	0.93	44083.8	11130.00
12	8441.61	136.55	0.419	0.50 (0.47)	0.94	47756.3	11620.00
13	7352.64	152.76	0.400	0.50 (0.47)	0.94	52282.1	12400.00
14	6480.99	164.35	0.387	0.50 (0.47)	0.94	54588.3	12201.00
15	5850.43	173.82	0.375	0.50 (0.47)	0.94	55878.9	12111.00
16	4902.27	189.80	0.363	0.50 (0.47)	0.95	57801.8	12261.00
17	4422.30	199.27	0.358	0.50 (0.47)	0.95	58612.9	10200.00
18	3838.72	214.89	0.349	0.50 (0.47)	0.95	59850.9	10300.00
19	3600.61	221.85	0.345	0.50 (0.47)	0.95	60203.1	12010.00
20	3106.86	242.54	0.334	0.50 (0.47)	0.95	60531.4	12000.00
21	2067.13	311.70	0.296	0.50 (0.47)	0.95	61202.2	10100.00
LONGEST FLOWPATH FROM NODE						10100.00 TO NODE	13404.00 = 119085.81 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23.28	20.61	1.096	0.50 (0.48)	0.97	49.5	50600.00
LONGEST FLOWPATH FROM NODE						50600.00 TO NODE	13404.00 = 4378.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23.28	20.61	1.096	0.50 (0.48)	0.97	49.5	50600.00

1	12875.32	20.11	1.110	0.50 (0.39)	0.79	5169.7	50400.00
2	12925.01	20.61	1.096	0.50 (0.39)	0.79	5328.2	50600.00
3	12965.52	21.02	1.084	0.50 (0.39)	0.79	5457.9	50500.00
4	13603.06	27.70	0.919	0.50 (0.39)	0.79	7510.0	410.00
5	13294.15	33.90	0.824	0.50 (0.40)	0.81	9950.2	50280.00
6	12941.15	40.27	0.744	0.50 (0.41)	0.83	12296.0	150.00
7	12326.64	53.68	0.641	0.50 (0.43)	0.86	16769.3	31100.00
8	11638.05	69.49	0.569	0.50 (0.44)	0.88	22191.1	11801.00
9	11237.16	80.91	0.530	0.50 (0.45)	0.90	26037.8	11500.00
10	10722.86	93.00	0.492	0.50 (0.45)	0.91	30523.8	11000.00
11	10174.02	107.23	0.464	0.50 (0.46)	0.92	36948.2	13000.00
12	9151.37	124.77	0.433	0.50 (0.47)	0.93	44133.3	11130.00
13	8442.16	136.55	0.419	0.50 (0.47)	0.94	47805.8	11620.00
14	7353.16	152.76	0.400	0.50 (0.47)	0.94	52331.6	12400.00
15	6481.50	164.35	0.387	0.50 (0.47)	0.94	54637.8	12201.00
16	5850.93	173.82	0.375	0.50 (0.47)	0.94	55928.4	12111.00
17	4902.75	189.80	0.363	0.50 (0.47)	0.95	57851.3	12261.00
18	4422.77	199.27	0.358	0.50 (0.47)	0.95	58662.4	10200.00
19	3839.18	214.89	0.349	0.50 (0.47)	0.95	59900.4	10300.00
20	3601.06	221.85	0.345	0.50 (0.47)	0.95	60252.6	12010.00
21	3107.30	242.54	0.334	0.50 (0.47)	0.95	60580.9	12000.00
22	2067.52	311.70	0.296	0.50 (0.47)	0.95	61251.7	10100.00
TOTAL AREA (ACRES) =						61251.7	

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 13603.06 Tc(MIN.) = 27.698
 EFFECTIVE AREA(ACRES) = 7510.03 AREA-AVERAGED Fm(INCH/HR) = 0.39
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.79
 TOTAL AREA (ACRES) = 61251.7
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119085.81 FEET.

 FLOW PROCESS FROM NODE 13404.00 TO NODE 13406.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 207.00 DOWNSTREAM(FEET) = 195.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1601.97 CHANNEL SLOPE = 0.0075
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
 CHANNEL FLOW THRU SUBAREA(CFS) = 13603.06
 FLOW VELOCITY(FEET/SEC.) = 16.84 FLOW DEPTH(FEET) = 16.41
 TRAVEL TIME(MIN.) = 1.59 Tc(MIN.) = 29.28
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13406.00 = 120687.78 FEET.

 FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 29.28
 * 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.888
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	4.00	0.50	1.000	-

USER-DEFINED - 2.00 0.50 1.000 -
 USER-DEFINED - 9.70 0.50 1.000 -
 USER-DEFINED - 2.60 0.50 1.000 -
 USER-DEFINED - 1.60 0.50 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 20.10 SUBAREA RUNOFF(CFS) = 7.02
 EFFECTIVE AREA(ACRES) = 7530.13 AREA-AVERAGED Fm(INCH/HR) = 0.39
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.79
 TOTAL AREA(ACRES) = 61271.8 PEAK FLOW RATE(CFS) = 13603.06
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 29.28
 * 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.888
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	2.00	0.50	1.000	-
USER-DEFINED	-	7.10	0.50	1.000	-
USER-DEFINED	-	5.80	0.50	1.000	-
USER-DEFINED	-	0.10	0.50	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 15.00 SUBAREA RUNOFF(CFS) = 5.24
 EFFECTIVE AREA(ACRES) = 7545.13 AREA-AVERAGED Fm(INCH/HR) = 0.39
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.79
 TOTAL AREA(ACRES) = 61286.8 PEAK FLOW RATE(CFS) = 13603.06
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13406.00 TO NODE 13408.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 195.00 DOWNSTREAM(FEET) = 182.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2458.36 CHANNEL SLOPE = 0.0053
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
 * 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.848
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.00	0.50	1.000	-
USER-DEFINED	-	3.30	0.50	1.000	-
USER-DEFINED	-	0.40	0.50	0.100	-
USER-DEFINED	-	1.40	0.50	1.000	-
USER-DEFINED	-	0.30	0.50	0.100	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.949
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 13605.15
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 14.77
 AVERAGE FLOW DEPTH(FEET) = 17.52 TRAVEL TIME(MIN.) = 2.77

Tc(MIN.) = 32.06
 SUBAREA AREA(ACRES) = 12.40 SUBAREA RUNOFF(CFS) = 4.16
 EFFECTIVE AREA(ACRES) = 7557.53 AREA-AVERAGED Fm(INCH/HR) = 0.39
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.79
 TOTAL AREA(ACRES) = 61299.2 PEAK FLOW RATE(CFS) = 13603.06
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 17.51 FLOW VELOCITY(FEET/SEC.) = 14.78
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123146.14 FEET.

 FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

 FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 2P05EVBB.DNA
 MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	324.09	10.46	0.50(0.18)	0.37	230.2	429.00
2	338.93	12.25	0.50(0.18)	0.37	269.4	425.00
3	340.01	12.46	0.50(0.18)	0.37	274.1	400.00
4	343.88	14.30	0.50(0.19)	0.37	315.0	300.00
5	364.37	20.67	0.50(0.19)	0.37	439.8	210.00
6	360.20	22.34	0.50(0.19)	0.37	459.0	410.00
7	355.69	24.05	0.50(0.18)	0.37	478.3	200.00
8	351.99	24.89	0.50(0.18)	0.37	487.0	230.00
9	344.00	26.01	0.50(0.18)	0.37	491.2	220.50
TOTAL AREA(ACRES) =		491.2				

 FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12875.32	24.53	0.985	0.50(0.39)	0.79	5217.2	50400.00
2	12925.01	25.02	0.972	0.50(0.39)	0.79	5375.7	50600.00
3	12965.52	25.43	0.964	0.50(0.39)	0.79	5505.4	50500.00
4	13603.06	32.06	0.848	0.50(0.39)	0.79	7557.5	410.00
5	13294.15	38.28	0.768	0.50(0.40)	0.81	9997.7	50280.00
6	12941.15	44.68	0.707	0.50(0.41)	0.83	12343.5	150.00
7	12326.64	58.15	0.613	0.50(0.43)	0.86	16816.8	31100.00
8	11638.05	74.02	0.553	0.50(0.44)	0.88	22238.6	11801.00
9	11237.16	85.48	0.514	0.50(0.45)	0.90	26085.3	11500.00
10	10722.86	97.62	0.483	0.50(0.45)	0.91	30571.3	11000.00
11	10174.02	111.92	0.455	0.50(0.46)	0.92	36995.7	13000.00
12	9151.37	129.58	0.428	0.50(0.47)	0.93	44180.8	11130.00

13	8442.16	141.46	0.414	0.50 (0.47)	0.94	47853.3	11620.00
14	7353.16	157.84	0.394	0.50 (0.47)	0.94	52379.1	12400.00
15	6481.50	169.60	0.380	0.50 (0.47)	0.94	54685.3	12201.00
16	5850.93	179.20	0.369	0.50 (0.47)	0.94	55975.9	12111.00
17	4902.75	195.43	0.360	0.50 (0.47)	0.95	57898.8	12261.00
18	4422.77	205.04	0.354	0.50 (0.47)	0.95	58709.9	10200.00
19	3839.18	220.87	0.346	0.50 (0.47)	0.95	59947.9	10300.00
20	3601.06	227.93	0.342	0.50 (0.47)	0.95	60300.1	12010.00
21	3107.30	248.84	0.331	0.50 (0.47)	0.95	60628.4	12000.00
22	2067.52	318.68	0.292	0.50 (0.47)	0.95	61299.2	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123146.14 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	324.09	10.46	1.713	0.50 (0.18)	0.37	230.2	429.00
2	338.93	12.25	1.551	0.50 (0.18)	0.37	269.4	425.00
3	340.01	12.46	1.532	0.50 (0.18)	0.37	274.1	400.00
4	343.88	14.30	1.364	0.50 (0.19)	0.37	315.0	300.00
5	364.37	20.67	1.094	0.50 (0.19)	0.37	439.8	210.00
6	360.20	22.34	1.047	0.50 (0.19)	0.37	459.0	410.00
7	355.69	24.05	0.999	0.50 (0.18)	0.37	478.3	200.00
8	351.99	24.89	0.975	0.50 (0.18)	0.37	487.0	230.00
9	344.00	26.01	0.952	0.50 (0.18)	0.37	491.2	220.50

LONGEST FLOWPATH FROM NODE 230.00 TO NODE 13408.00 = 11903.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12578.31	10.46	1.713	0.50 (0.37)	0.75	2454.8	429.00
2	12922.22	12.25	1.551	0.50 (0.37)	0.75	2874.9	425.00
3	12928.01	12.46	1.532	0.50 (0.37)	0.75	2924.1	400.00
4	12667.17	14.30	1.364	0.50 (0.37)	0.75	3357.8	300.00
5	13212.37	20.67	1.094	0.50 (0.38)	0.75	4837.1	210.00
6	13235.52	22.34	1.047	0.50 (0.38)	0.75	5211.6	410.00
7	13231.01	24.05	0.999	0.50 (0.38)	0.75	5595.3	200.00
8	13228.91	24.53	0.985	0.50 (0.38)	0.75	5700.4	50400.00
9	13263.40	24.89	0.975	0.50 (0.38)	0.75	5819.3	230.00
10	13276.04	25.02	0.972	0.50 (0.38)	0.75	5863.2	50600.00
11	13313.65	25.43	0.964	0.50 (0.38)	0.75	5994.5	50500.00
12	13365.53	26.01	0.952	0.50 (0.38)	0.76	6176.9	220.50
13	13900.32	32.06	0.848	0.50 (0.38)	0.76	8048.7	410.00
14	13555.76	38.28	0.768	0.50 (0.39)	0.79	10488.9	50280.00
15	13175.52	44.68	0.707	0.50 (0.41)	0.81	12834.7	150.00
16	12519.01	58.15	0.613	0.50 (0.42)	0.84	17308.0	31100.00
17	11803.63	74.02	0.553	0.50 (0.44)	0.87	22729.8	11801.00
18	11384.96	85.48	0.514	0.50 (0.44)	0.89	26576.5	11500.00
19	10859.76	97.62	0.483	0.50 (0.45)	0.90	31062.5	11000.00
20	10302.96	111.92	0.455	0.50 (0.46)	0.91	37486.9	13000.00
21	9272.59	129.58	0.428	0.50 (0.46)	0.93	44672.0	11130.00
22	8559.39	141.46	0.414	0.50 (0.47)	0.93	48344.5	11620.00
23	7464.90	157.84	0.394	0.50 (0.47)	0.94	52870.3	12400.00
24	6589.29	169.60	0.380	0.50 (0.47)	0.94	55176.5	12201.00
25	5955.50	179.20	0.369	0.50 (0.47)	0.94	56467.1	12111.00
26	5004.67	195.43	0.360	0.50 (0.47)	0.94	58390.0	12261.00
27	4523.21	205.04	0.354	0.50 (0.47)	0.94	59201.1	10200.00
28	3937.18	220.87	0.346	0.50 (0.47)	0.94	60439.1	10300.00
29	3697.97	227.93	0.342	0.50 (0.47)	0.94	60791.3	12010.00

30	3200.98	248.84	0.331	0.50 (0.47)	0.94	61119.6	12000.00
31	2150.43	318.68	0.292	0.50 (0.47)	0.94	61790.4	10100.00

TOTAL AREA (ACRES) = 61790.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 13900.32 Tc (MIN.) = 32.057
EFFECTIVE AREA (ACRES) = 8048.73 AREA-AVERAGED Fm (INCH/HR) = 0.38
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.75
TOTAL AREA (ACRES) = 61790.4
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123146.14 FEET.

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<<
=====

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<<
=====

PEAK FLOWRATE TABLE FILE NAME: P507XX05.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	76.41	27.15	0.50 (0.49)	0.99	231.4	50700.00

TOTAL AREA (ACRES) = 231.4

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<<
=====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12578.31	10.46	1.713	0.50 (0.37)	0.75	2454.8	429.00
2	12922.22	12.25	1.551	0.50 (0.37)	0.75	2874.9	425.00
3	12928.01	12.46	1.532	0.50 (0.37)	0.75	2924.1	400.00
4	12667.17	14.30	1.364	0.50 (0.37)	0.75	3357.8	300.00
5	13212.37	20.67	1.094	0.50 (0.38)	0.75	4837.1	210.00
6	13235.52	22.34	1.047	0.50 (0.38)	0.75	5211.6	410.00
7	13231.01	24.05	0.999	0.50 (0.38)	0.75	5595.3	200.00
8	13228.91	24.53	0.985	0.50 (0.38)	0.75	5700.4	50400.00
9	13263.40	24.89	0.975	0.50 (0.38)	0.75	5819.3	230.00
10	13276.04	25.02	0.972	0.50 (0.38)	0.75	5863.2	50600.00
11	13313.65	25.43	0.964	0.50 (0.38)	0.75	5994.5	50500.00
12	13365.53	26.01	0.952	0.50 (0.38)	0.76	6176.9	220.50
13	13900.32	32.06	0.848	0.50 (0.38)	0.76	8048.7	410.00
14	13555.76	38.28	0.768	0.50 (0.39)	0.79	10488.9	50280.00
15	13175.52	44.68	0.707	0.50 (0.41)	0.81	12834.7	150.00
16	12519.01	58.15	0.613	0.50 (0.42)	0.84	17308.0	31100.00
17	11803.63	74.02	0.553	0.50 (0.44)	0.87	22729.8	11801.00
18	11384.96	85.48	0.514	0.50 (0.44)	0.89	26576.5	11500.00
19	10859.76	97.62	0.483	0.50 (0.45)	0.90	31062.5	11000.00
20	10302.96	111.92	0.455	0.50 (0.46)	0.91	37486.9	13000.00

21	9272.59	129.58	0.428	0.50 (0.46)	0.93	44672.0	11130.00
22	8559.39	141.46	0.414	0.50 (0.47)	0.93	48344.5	11620.00
23	7464.90	157.84	0.394	0.50 (0.47)	0.94	52870.3	12400.00
24	6589.29	169.60	0.380	0.50 (0.47)	0.94	55176.5	12201.00
25	5955.50	179.20	0.369	0.50 (0.47)	0.94	56467.1	12111.00
26	5004.67	195.43	0.360	0.50 (0.47)	0.94	58390.0	12261.00
27	4523.21	205.04	0.354	0.50 (0.47)	0.94	59201.1	10200.00
28	3937.18	220.87	0.346	0.50 (0.47)	0.94	60439.1	10300.00
29	3697.97	227.93	0.342	0.50 (0.47)	0.94	60791.3	12010.00
30	3200.98	248.84	0.331	0.50 (0.47)	0.94	61119.6	12000.00
31	2150.43	318.68	0.292	0.50 (0.47)	0.94	61790.4	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123146.14 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	76.41	27.15	0.930	0.50 (0.49)	0.99	231.4	50700.00

LONGEST FLOWPATH FROM NODE 50700.00 TO NODE 13408.00 = 7683.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12654.73	10.46	1.713	0.50 (0.38)	0.76	2543.9	429.00
2	12998.63	12.25	1.551	0.50 (0.38)	0.76	2979.2	425.00
3	13004.43	12.46	1.532	0.50 (0.38)	0.76	3030.3	400.00
4	12743.58	14.30	1.364	0.50 (0.38)	0.76	3479.7	300.00
5	13288.79	20.67	1.094	0.50 (0.38)	0.76	5013.2	210.00
6	13311.94	22.34	1.047	0.50 (0.38)	0.76	5402.0	410.00
7	13307.42	24.05	0.999	0.50 (0.38)	0.76	5800.3	200.00
8	13305.32	24.53	0.985	0.50 (0.38)	0.76	5909.5	50400.00
9	13339.81	24.89	0.975	0.50 (0.38)	0.76	6031.4	230.00
10	13352.45	25.02	0.972	0.50 (0.38)	0.76	6076.4	50600.00
11	13390.06	25.43	0.964	0.50 (0.38)	0.76	6211.2	50500.00
12	13441.94	26.01	0.952	0.50 (0.38)	0.76	6398.6	220.50
13	13542.67	27.15	0.930	0.50 (0.38)	0.76	6760.9	50700.00
14	13962.32	32.06	0.848	0.50 (0.38)	0.77	8280.1	410.00
15	13603.78	38.28	0.768	0.50 (0.40)	0.79	10720.3	50280.00
16	13212.86	44.68	0.707	0.50 (0.41)	0.81	13066.1	150.00
17	12539.88	58.15	0.613	0.50 (0.42)	0.85	17539.4	31100.00
18	11813.99	74.02	0.553	0.50 (0.44)	0.87	22961.2	11801.00
19	11388.35	85.48	0.514	0.50 (0.44)	0.89	26807.9	11500.00
20	10860.75	97.62	0.483	0.50 (0.45)	0.90	31293.9	11000.00
21	10303.89	111.92	0.455	0.50 (0.46)	0.91	37718.3	13000.00
22	9273.46	129.58	0.428	0.50 (0.46)	0.93	44903.4	11130.00
23	8560.23	141.46	0.414	0.50 (0.47)	0.93	48575.9	11620.00
24	7465.71	157.84	0.394	0.50 (0.47)	0.94	53101.7	12400.00
25	6590.07	169.60	0.380	0.50 (0.47)	0.94	55407.9	12201.00
26	5956.25	179.20	0.369	0.50 (0.47)	0.94	56698.5	12111.00
27	5005.41	195.43	0.360	0.50 (0.47)	0.94	58621.4	12261.00
28	4523.94	205.04	0.354	0.50 (0.47)	0.94	59432.5	10200.00
29	3937.89	220.87	0.346	0.50 (0.47)	0.94	60670.5	10300.00
30	3698.67	227.93	0.342	0.50 (0.47)	0.94	61022.7	12010.00
31	3201.66	248.84	0.331	0.50 (0.47)	0.94	61351.0	12000.00
32	2151.02	318.68	0.292	0.50 (0.47)	0.94	62021.8	10100.00

TOTAL AREA (ACRES) = 62021.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 13962.32 Tc (MIN.) = 32.057

EFFECTIVE AREA (ACRES) = 8280.13 AREA-AVERAGED Fm (INCH/HR) = 0.38
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.76
 TOTAL AREA (ACRES) = 62021.8
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123146.14 FEET.

FLOW PROCESS FROM NODE 13408.00 TO NODE 13410.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM (FEET) = 182.00 DOWNSTREAM (FEET) = 178.72
 CHANNEL LENGTH THRU SUBAREA (FEET) = 952.73 CHANNEL SLOPE = 0.0034
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.832

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.40	0.50	1.000	-
USER-DEFINED	-	2.90	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 13962.81

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 12.67

AVERAGE FLOW DEPTH (FEET) = 19.17 TRAVEL TIME (MIN.) = 1.25

Tc (MIN.) = 33.31

SUBAREA AREA (ACRES) = 3.30 SUBAREA RUNOFF (CFS) = 0.98

EFFECTIVE AREA (ACRES) = 8283.43 AREA-AVERAGED Fm (INCH/HR) = 0.38

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.77

TOTAL AREA (ACRES) = 62025.1 PEAK FLOW RATE (CFS) = 13962.32

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 19.17 FLOW VELOCITY (FEET/SEC.) = 12.66

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124098.87 FEET.

FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<

FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<

PEAK FLOWRATE TABLE FILE NAME: RU05EV36.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	716.94	33.96	0.50 (0.45)	0.90	1392.8	110.00
2	712.41	36.72	0.50 (0.45)	0.90	1540.3	100.00
3	702.91	38.48	0.50 (0.45)	0.90	1624.0	100.00
4	658.46	42.79	0.50 (0.45)	0.91	1804.5	130.00
5	539.46	61.06	0.50 (0.46)	0.93	2545.6	20100.00
6	464.24	68.52	0.50 (0.46)	0.93	2700.4	13600.00

7 180.53 136.50 0.50(0.47) 0.93 3777.9 13510.00
 8 122.83 163.10 0.50(0.47) 0.93 3859.7 13500.00
 TOTAL AREA (ACRES) = 3859.7

 FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12654.73	11.74	1.597	0.50(0.38)	0.76	2547.2	429.00
2	12998.63	13.52	1.435	0.50(0.38)	0.76	2982.5	425.00
3	13004.43	13.73	1.416	0.50(0.38)	0.76	3033.6	400.00
4	12743.58	15.59	1.279	0.50(0.38)	0.76	3483.0	300.00
5	13288.79	21.94	1.058	0.50(0.38)	0.76	5016.5	210.00
6	13311.94	23.61	1.011	0.50(0.38)	0.76	5405.3	410.00
7	13307.42	25.32	0.966	0.50(0.38)	0.76	5803.6	200.00
8	13305.32	25.79	0.956	0.50(0.38)	0.76	5912.8	50400.00
9	13339.81	26.15	0.949	0.50(0.38)	0.76	6034.7	230.00
10	13352.45	26.29	0.947	0.50(0.38)	0.76	6079.7	50600.00
11	13390.06	26.70	0.939	0.50(0.38)	0.76	6214.5	50500.00
12	13441.94	27.28	0.927	0.50(0.38)	0.76	6401.9	220.50
13	13542.67	28.42	0.905	0.50(0.38)	0.76	6764.2	50700.00
14	13962.32	33.31	0.832	0.50(0.38)	0.77	8283.4	410.00
15	13603.78	39.54	0.752	0.50(0.40)	0.79	10723.6	50280.00
16	13212.86	45.95	0.697	0.50(0.41)	0.81	13069.4	150.00
17	12539.88	59.44	0.605	0.50(0.42)	0.85	17542.7	31100.00
18	11813.99	75.33	0.549	0.50(0.44)	0.87	22964.5	11801.00
19	11388.35	86.80	0.509	0.50(0.44)	0.89	26811.2	11500.00
20	10860.75	98.96	0.480	0.50(0.45)	0.90	31297.2	11000.00
21	10303.89	113.27	0.452	0.50(0.46)	0.91	37721.6	13000.00
22	9273.46	130.97	0.426	0.50(0.46)	0.93	44906.7	11130.00
23	8560.23	142.87	0.412	0.50(0.47)	0.93	48579.2	11620.00
24	7465.71	159.30	0.392	0.50(0.47)	0.94	53105.0	12400.00
25	6590.07	171.11	0.379	0.50(0.47)	0.94	55411.2	12201.00
26	5956.25	180.75	0.368	0.50(0.47)	0.94	56701.8	12111.00
27	5005.41	197.05	0.359	0.50(0.47)	0.94	58624.7	12261.00
28	4523.94	206.70	0.353	0.50(0.47)	0.94	59435.8	10200.00
29	3937.89	222.59	0.345	0.50(0.47)	0.94	60673.8	10300.00
30	3698.67	229.67	0.341	0.50(0.47)	0.94	61026.0	12010.00
31	3201.66	250.65	0.330	0.50(0.47)	0.94	61354.3	12000.00
32	2151.02	320.68	0.291	0.50(0.47)	0.94	62025.1	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124098.87 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	716.94	33.96	0.823	0.50(0.45)	0.90	1392.8	110.00
2	712.41	36.72	0.788	0.50(0.45)	0.90	1540.3	100.00
3	702.91	38.48	0.765	0.50(0.45)	0.90	1624.0	100.00
4	658.46	42.79	0.723	0.50(0.45)	0.91	1804.5	130.00
5	539.46	61.06	0.598	0.50(0.46)	0.93	2545.6	20100.00
6	464.24	68.52	0.572	0.50(0.46)	0.93	2700.4	13600.00
7	180.53	136.50	0.419	0.50(0.47)	0.93	3777.9	13510.00
8	122.83	163.10	0.388	0.50(0.47)	0.93	3859.7	13500.00

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13410.00 = 41710.10 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13371.67	11.74	1.597	0.50(0.39)	0.78	3028.7	429.00
2	13715.58	13.52	1.435	0.50(0.39)	0.78	3537.1	425.00
3	13721.37	13.73	1.416	0.50(0.39)	0.78	3596.8	400.00
4	13460.52	15.59	1.279	0.50(0.39)	0.78	4122.1	300.00
5	14005.73	21.94	1.058	0.50(0.39)	0.78	5916.2	210.00
6	14028.88	23.61	1.011	0.50(0.39)	0.78	6373.5	410.00
7	14024.36	25.32	0.966	0.50(0.39)	0.78	6842.0	200.00
8	14022.27	25.79	0.956	0.50(0.39)	0.78	6970.5	50400.00
9	14056.76	26.15	0.949	0.50(0.39)	0.78	7107.2	230.00
10	14069.39	26.29	0.947	0.50(0.39)	0.78	7157.8	50600.00
11	14107.00	26.70	0.939	0.50(0.39)	0.78	7309.3	50500.00
12	14158.89	27.28	0.927	0.50(0.39)	0.78	7520.6	220.50
13	14259.61	28.42	0.905	0.50(0.39)	0.78	7929.4	50700.00
14	14679.26	33.31	0.832	0.50(0.39)	0.79	9649.4	410.00
15	14641.64	33.96	0.823	0.50(0.39)	0.79	9932.2	110.00
16	14478.41	36.72	0.788	0.50(0.40)	0.80	11159.8	100.00
17	14367.78	38.48	0.765	0.50(0.40)	0.80	11931.8	100.00
18	14295.74	39.54	0.752	0.50(0.40)	0.81	12392.0	50280.00
19	14063.93	42.79	0.723	0.50(0.41)	0.82	13718.1	130.00
20	13850.75	45.95	0.697	0.50(0.41)	0.83	15002.0	150.00
21	13089.90	59.44	0.605	0.50(0.43)	0.86	20022.6	31100.00
22	13005.32	61.06	0.598	0.50(0.43)	0.86	20641.3	20100.00
23	12589.40	68.52	0.572	0.50(0.44)	0.87	23340.6	13600.00
24	12249.80	75.33	0.549	0.50(0.44)	0.88	25772.8	11801.00
25	11776.29	86.80	0.509	0.50(0.45)	0.89	29801.3	11500.00
26	11197.96	98.96	0.480	0.50(0.45)	0.90	34480.0	11000.00
27	10581.37	113.27	0.452	0.50(0.46)	0.92	41131.3	13000.00
28	9477.08	130.97	0.426	0.50(0.46)	0.93	48596.9	11130.00
29	9122.47	136.50	0.419	0.50(0.46)	0.93	50391.7	13510.00
30	8726.94	142.87	0.412	0.50(0.47)	0.93	52376.7	11620.00
31	7596.76	159.30	0.392	0.50(0.47)	0.94	56953.0	12400.00
32	7307.30	163.10	0.388	0.50(0.47)	0.94	57705.4	13500.00
33	6709.90	171.11	0.379	0.50(0.47)	0.94	59270.9	12201.00
34	6072.62	180.75	0.368	0.50(0.47)	0.94	60561.5	12111.00
35	5118.97	197.05	0.359	0.50(0.47)	0.94	62484.4	12261.00
36	4635.83	206.70	0.353	0.50(0.47)	0.94	63295.5	10200.00
37	4047.04	222.59	0.345	0.50(0.47)	0.94	64533.4	10300.00
38	3806.61	229.67	0.341	0.50(0.47)	0.94	64885.7	12010.00
39	3305.98	250.65	0.330	0.50(0.47)	0.94	65214.0	12000.00
40	2243.28	320.68	0.291	0.50(0.47)	0.94	65884.8	10100.00

TOTAL AREA (ACRES) = 65884.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 14679.26 Tc(MIN.) = 33.310
 EFFECTIVE AREA(ACRES) = 9649.37 AREA-AVERAGED Fm(INCH/HR) = 0.39
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.79
 TOTAL AREA(ACRES) = 65884.8
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124098.87 FEET.

FLOW PROCESS FROM NODE 13410.00 TO NODE 13412.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 178.72 DOWNSTREAM(FEET) = 176.93
CHANNEL LENGTH THRU SUBAREA(FEET) = 169.78 CHANNEL SLOPE = 0.0105
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
CHANNEL FLOW THRU SUBAREA(CFS) = 14679.26
FLOW VELOCITY(FEET/SEC.) = 19.51 FLOW DEPTH(FEET) = 15.84
TRAVEL TIME(MIN.) = 0.15 Tc(MIN.) = 33.46
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124268.65 FEET.

FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<

FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<

PEAK FLOWRATE TABLE FILE NAME: 0506101F.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM Q Tc Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 85.74 49.56 0.50(0.49) 0.98 591.0 10100.00
TOTAL AREA(ACRES) = 591.0

FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 13371.67 11.89 1.583 0.50(0.39) 0.78 3028.7 429.00
2 13715.58 13.67 1.422 0.50(0.39) 0.78 3537.1 425.00
3 13721.37 13.88 1.403 0.50(0.39) 0.78 3596.8 400.00
4 13460.52 15.73 1.273 0.50(0.39) 0.78 4122.1 300.00
5 14005.73 22.09 1.054 0.50(0.39) 0.78 5916.2 210.00
6 14028.88 23.76 1.007 0.50(0.39) 0.78 6373.5 410.00
7 14024.36 25.47 0.963 0.50(0.39) 0.78 6842.0 200.00
8 14022.27 25.94 0.954 0.50(0.39) 0.78 6970.5 50400.00
9 14056.76 26.30 0.946 0.50(0.39) 0.78 7107.2 230.00
10 14069.39 26.44 0.944 0.50(0.39) 0.78 7157.8 50600.00
11 14107.00 26.85 0.936 0.50(0.39) 0.78 7309.3 50500.00
12 14158.89 27.43 0.924 0.50(0.39) 0.78 7520.6 220.50
13 14259.61 28.56 0.902 0.50(0.39) 0.78 7929.4 50700.00
14 14679.26 33.46 0.830 0.50(0.39) 0.79 9649.4 410.00
15 14641.64 34.11 0.821 0.50(0.39) 0.79 9932.2 110.00
16 14478.41 36.87 0.786 0.50(0.40) 0.80 11159.8 100.00
17 14367.78 38.63 0.764 0.50(0.40) 0.80 11931.8 100.00
18 14295.74 39.69 0.750 0.50(0.40) 0.81 12392.0 50280.00
19 14063.93 42.94 0.722 0.50(0.41) 0.82 13718.1 130.00
20 13850.75 46.10 0.695 0.50(0.41) 0.83 15002.0 150.00

21 13089.90 59.59 0.605 0.50(0.43) 0.86 20022.6 31100.00
22 13005.32 61.21 0.598 0.50(0.43) 0.86 20641.3 20100.00
23 12589.40 68.67 0.572 0.50(0.44) 0.87 23340.6 13600.00
24 12249.80 75.48 0.548 0.50(0.44) 0.88 25772.8 11801.00
25 11776.29 86.95 0.509 0.50(0.45) 0.89 29801.3 11500.00
26 11197.96 99.11 0.480 0.50(0.45) 0.90 34480.0 11000.00
27 10581.37 113.43 0.452 0.50(0.46) 0.92 41131.3 13000.00
28 9477.08 131.13 0.426 0.50(0.46) 0.93 48596.9 11130.00
29 9122.47 136.66 0.419 0.50(0.46) 0.93 50391.7 13510.00
30 8726.94 143.04 0.412 0.50(0.47) 0.93 52376.7 11620.00
31 7596.76 159.48 0.392 0.50(0.47) 0.94 56953.0 12400.00
32 7307.30 163.27 0.388 0.50(0.47) 0.94 57705.4 13500.00
33 6709.90 171.29 0.378 0.50(0.47) 0.94 59270.9 12201.00
34 6072.62 180.93 0.367 0.50(0.47) 0.94 60561.5 12111.00
35 5118.97 197.24 0.359 0.50(0.47) 0.94 62484.4 12261.00
36 4635.83 206.90 0.353 0.50(0.47) 0.94 63295.5 10200.00
37 4047.04 222.79 0.345 0.50(0.47) 0.94 64533.4 10300.00
38 3806.61 229.88 0.341 0.50(0.47) 0.94 64885.7 12010.00
39 3305.98 250.86 0.329 0.50(0.47) 0.94 65214.0 12000.00
40 2243.28 320.91 0.291 0.50(0.47) 0.94 65884.8 10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124268.65 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 85.74 49.56 0.667 0.50(0.49) 0.98 591.0 10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 14677.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 13457.41 11.89 1.583 0.50(0.39) 0.79 3170.5 429.00
2 13801.31 13.67 1.422 0.50(0.39) 0.79 3700.1 425.00
3 13807.11 13.88 1.403 0.50(0.39) 0.79 3762.3 400.00
4 13546.26 15.73 1.273 0.50(0.39) 0.79 4309.8 300.00
5 14091.46 22.09 1.054 0.50(0.39) 0.79 6179.6 210.00
6 14114.62 23.76 1.007 0.50(0.40) 0.79 6656.8 410.00
7 14110.10 25.47 0.963 0.50(0.40) 0.79 7145.7 200.00
8 14108.00 25.94 0.954 0.50(0.40) 0.79 7279.8 50400.00
9 14142.49 26.30 0.946 0.50(0.40) 0.79 7420.8 230.00
10 14155.13 26.44 0.944 0.50(0.40) 0.79 7473.0 50600.00
11 14192.74 26.85 0.936 0.50(0.40) 0.79 7629.4 50500.00
12 14244.62 27.43 0.924 0.50(0.40) 0.79 7847.6 220.50
13 14345.34 28.56 0.902 0.50(0.40) 0.79 8269.9 50700.00
14 14765.00 33.46 0.830 0.50(0.40) 0.80 10048.3 410.00
15 14727.38 34.11 0.821 0.50(0.40) 0.80 10338.9 110.00
16 14564.15 36.87 0.786 0.50(0.40) 0.80 11599.4 100.00
17 14453.52 38.63 0.764 0.50(0.40) 0.81 12392.4 100.00
18 14381.48 39.69 0.750 0.50(0.41) 0.81 12865.3 50280.00
19 14149.67 42.94 0.722 0.50(0.41) 0.82 14230.1 130.00
20 13936.49 46.10 0.695 0.50(0.42) 0.83 15551.7 150.00
21 13741.13 49.56 0.667 0.50(0.42) 0.84 16882.1 10100.00
22 13145.14 59.59 0.605 0.50(0.43) 0.86 20613.6 31100.00
23 13057.26 61.21 0.598 0.50(0.43) 0.86 21232.3 20100.00
24 12628.65 68.67 0.572 0.50(0.44) 0.87 23931.6 13600.00
25 12277.46 75.48 0.548 0.50(0.44) 0.88 26363.8 11801.00
26 11784.42 86.95 0.509 0.50(0.45) 0.89 30392.3 11500.00
27 11201.82 99.11 0.480 0.50(0.45) 0.90 35071.0 11000.00

28	10585.00	113.43	0.452	0.50	(0.46)	0.92	41722.3	13000.00
29	9480.51	131.13	0.426	0.50	(0.46)	0.93	49187.9	11130.00
30	9125.84	136.66	0.419	0.50	(0.47)	0.93	50982.7	13510.00
31	8730.25	143.04	0.412	0.50	(0.47)	0.93	52967.7	11620.00
32	7599.92	159.48	0.392	0.50	(0.47)	0.94	57544.0	12400.00
33	7310.42	163.27	0.388	0.50	(0.47)	0.94	58296.4	13500.00
34	6712.94	171.29	0.378	0.50	(0.47)	0.94	59861.9	12201.00
35	6075.58	180.93	0.367	0.50	(0.47)	0.94	61152.5	12111.00
36	5121.85	197.24	0.359	0.50	(0.47)	0.94	63075.4	12261.00
37	4638.67	206.90	0.353	0.50	(0.47)	0.94	63886.5	10200.00
38	4049.81	222.79	0.345	0.50	(0.47)	0.94	65124.4	10300.00
39	3809.34	229.88	0.341	0.50	(0.47)	0.94	65476.7	12010.00
40	3308.62	250.86	0.329	0.50	(0.47)	0.94	65805.0	12000.00
41	2245.62	320.91	0.291	0.50	(0.47)	0.94	66475.8	10100.00

TOTAL AREA (ACRES) = 66475.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 14765.00 Tc (MIN.) = 33.455
EFFECTIVE AREA (ACRES) = 10048.31 AREA-AVERAGED Fm (INCH/HR) = 0.40
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.80
TOTAL AREA (ACRES) = 66475.8
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124268.65 FEET.

FLOW PROCESS FROM NODE 13412.00 TO NODE 13700.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 176.93 DOWNSTREAM (FEET) = 170.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 260.10 CHANNEL SLOPE = 0.0266
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00
CHANNEL FLOW THRU SUBAREA (CFS) = 14765.00
FLOW VELOCITY (FEET/SEC.) = 27.66 FLOW DEPTH (FEET) = 13.34
TRAVEL TIME (MIN.) = 0.16 Tc (MIN.) = 33.61
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124528.75 FEET.

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P508XX05.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	45.66	26.25	0.50 (0.49)	0.99	131.3	50800.00

TOTAL AREA (ACRES) = 131.3

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 11

----->>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<-----

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13457.41	12.05	1.569	0.50 (0.39)	0.79	3170.5	429.00
2	13801.31	13.83	1.407	0.50 (0.39)	0.79	3700.1	425.00
3	13807.11	14.04	1.388	0.50 (0.39)	0.79	3762.3	400.00
4	13546.26	15.90	1.267	0.50 (0.39)	0.79	4309.8	300.00
5	14091.46	22.25	1.050	0.50 (0.39)	0.79	6179.6	210.00
6	14114.62	23.92	1.003	0.50 (0.40)	0.79	6656.8	410.00
7	14110.10	25.63	0.960	0.50 (0.40)	0.79	7145.7	200.00
8	14108.00	26.10	0.950	0.50 (0.40)	0.79	7279.8	50400.00
9	14142.49	26.46	0.943	0.50 (0.40)	0.79	7420.8	230.00
10	14155.13	26.59	0.941	0.50 (0.40)	0.79	7473.0	50600.00
11	14192.74	27.00	0.933	0.50 (0.40)	0.79	7629.4	50500.00
12	14244.62	27.58	0.921	0.50 (0.40)	0.79	7847.6	220.50
13	14345.34	28.72	0.899	0.50 (0.40)	0.79	8269.9	50700.00
14	14765.00	33.61	0.828	0.50 (0.40)	0.80	10048.3	410.00
15	14727.38	34.27	0.819	0.50 (0.40)	0.80	10338.9	110.00
16	14564.15	37.03	0.784	0.50 (0.40)	0.80	11599.4	100.00
17	14453.52	38.78	0.762	0.50 (0.40)	0.81	12392.4	100.00
18	14381.48	39.85	0.748	0.50 (0.41)	0.81	12865.3	50280.00
19	14149.67	43.10	0.720	0.50 (0.41)	0.82	14230.1	130.00
20	13936.49	46.26	0.694	0.50 (0.42)	0.83	15551.7	150.00
21	13741.13	49.72	0.665	0.50 (0.42)	0.84	16882.1	10100.00
22	13145.14	59.75	0.604	0.50 (0.43)	0.86	20613.6	31100.00
23	13057.26	61.37	0.597	0.50 (0.43)	0.86	21232.3	20100.00
24	12628.65	68.83	0.571	0.50 (0.44)	0.87	23931.6	13600.00
25	12277.46	75.64	0.548	0.50 (0.44)	0.88	26363.8	11801.00
26	11784.42	87.12	0.508	0.50 (0.45)	0.89	30392.3	11500.00
27	11201.82	99.28	0.480	0.50 (0.45)	0.90	35071.0	11000.00
28	10585.00	113.60	0.452	0.50 (0.46)	0.92	41722.3	13000.00
29	9480.51	131.31	0.426	0.50 (0.46)	0.93	49187.9	11130.00
30	9125.84	136.84	0.419	0.50 (0.47)	0.93	50982.7	13510.00
31	8730.25	143.22	0.412	0.50 (0.47)	0.93	52967.7	11620.00
32	7599.92	159.66	0.392	0.50 (0.47)	0.94	57544.0	12400.00
33	7310.42	163.46	0.388	0.50 (0.47)	0.94	58296.4	13500.00
34	6712.94	171.48	0.378	0.50 (0.47)	0.94	59861.9	12201.00
35	6075.58	181.13	0.367	0.50 (0.47)	0.94	61152.5	12111.00
36	5121.85	197.44	0.359	0.50 (0.47)	0.94	63075.4	12261.00
37	4638.67	207.11	0.353	0.50 (0.47)	0.94	63886.5	10200.00
38	4049.81	223.01	0.345	0.50 (0.47)	0.94	65124.4	10300.00
39	3809.34	230.10	0.341	0.50 (0.47)	0.94	65476.7	12010.00
40	3308.62	251.09	0.329	0.50 (0.47)	0.94	65805.0	12000.00
41	2245.62	321.17	0.291	0.50 (0.47)	0.94	66475.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124528.75 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	45.66	26.25	0.947	0.50 (0.49)	0.99	131.3	50800.00

LONGEST FLOWPATH FROM NODE 50800.00 TO NODE 13700.00 = 5946.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM	Q	Tc	Intensity	Fp (Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	---------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	13503.06	12.05	1.569	0.50 (0.40)	0.79	3230.8 429.00
2	13846.97	13.83	1.407	0.50 (0.40)	0.79	3769.3 425.00
3	13852.76	14.04	1.388	0.50 (0.40)	0.79	3832.5 400.00
4	13591.92	15.90	1.267	0.50 (0.40)	0.79	4389.3 300.00
5	14137.12	22.25	1.050	0.50 (0.40)	0.79	6290.9 210.00
6	14160.27	23.92	1.003	0.50 (0.40)	0.79	6776.4 410.00
7	14155.76	25.63	0.960	0.50 (0.40)	0.79	7273.9 200.00
8	14153.66	26.10	0.950	0.50 (0.40)	0.79	7410.4 50400.00
9	14168.45	26.25	0.947	0.50 (0.40)	0.79	7471.6 50800.00
10	14187.75	26.46	0.943	0.50 (0.40)	0.79	7552.1 230.00
11	14200.11	26.59	0.941	0.50 (0.40)	0.79	7604.3 50600.00
12	14236.92	27.00	0.933	0.50 (0.40)	0.79	7760.7 50500.00
13	14287.66	27.58	0.921	0.50 (0.40)	0.80	7978.9 220.50
14	14386.13	28.72	0.899	0.50 (0.40)	0.80	8401.2 50700.00
15	14798.59	33.61	0.828	0.50 (0.40)	0.80	10179.6 410.00
16	14760.13	34.27	0.819	0.50 (0.40)	0.80	10470.2 110.00
17	14593.34	37.03	0.784	0.50 (0.40)	0.81	11730.7 100.00
18	14480.45	38.78	0.762	0.50 (0.41)	0.81	12523.7 100.00
19	14407.04	39.85	0.748	0.50 (0.41)	0.81	12996.6 50280.00
20	14172.44	43.10	0.720	0.50 (0.41)	0.82	14361.4 130.00
21	13956.61	46.26	0.694	0.50 (0.42)	0.83	15683.0 150.00
22	13758.36	49.72	0.665	0.50 (0.42)	0.84	17013.4 10100.00
23	13156.14	59.75	0.604	0.50 (0.43)	0.86	20744.9 31100.00
24	13067.63	61.37	0.597	0.50 (0.43)	0.86	21363.6 20100.00
25	12636.41	68.83	0.571	0.50 (0.44)	0.87	24062.9 13600.00
26	12282.84	75.64	0.548	0.50 (0.44)	0.88	26495.1 11801.00
27	11785.79	87.12	0.508	0.50 (0.45)	0.89	30523.6 11500.00
28	11202.38	99.28	0.480	0.50 (0.45)	0.90	35202.3 11000.00
29	10585.54	113.60	0.452	0.50 (0.46)	0.92	41853.6 13000.00
30	9481.01	131.31	0.426	0.50 (0.46)	0.93	49319.2 11130.00
31	9126.33	136.84	0.419	0.50 (0.47)	0.93	51114.0 13510.00
32	8730.73	143.22	0.412	0.50 (0.47)	0.93	53099.0 11620.00
33	7600.38	159.66	0.392	0.50 (0.47)	0.94	57675.3 12400.00
34	7310.87	163.46	0.388	0.50 (0.47)	0.94	58427.7 13500.00
35	6713.39	171.48	0.378	0.50 (0.47)	0.94	59993.2 12201.00
36	6076.01	181.13	0.367	0.50 (0.47)	0.94	61283.8 12111.00
37	5122.27	197.44	0.359	0.50 (0.47)	0.94	63206.7 12261.00
38	4639.09	207.11	0.353	0.50 (0.47)	0.94	64017.8 10200.00
39	4050.22	223.01	0.345	0.50 (0.47)	0.94	65255.8 10300.00
40	3809.74	230.10	0.341	0.50 (0.47)	0.94	65608.0 12010.00
41	3309.01	251.09	0.329	0.50 (0.47)	0.94	65936.3 12000.00
42	2245.96	321.17	0.291	0.50 (0.47)	0.94	66607.1 10100.00
TOTAL AREA (ACRES) = 66607.1						

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 14798.59 Tc(MIN.) = 33.612
EFFECTIVE AREA(ACRES) = 10179.61 AREA-AVERAGED Fm(INCH/HR) = 0.40
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.80
TOTAL AREA(ACRES) = 66607.1
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124528.75 FEET.

=====
END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 66607.1 TC(MIN.) = 33.61
EFFECTIVE AREA(ACRES) = 10179.61 AREA-AVERAGED Fm(INCH/HR) = 0.40
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.797
PEAK FLOW RATE(CFS) = 14798.59

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13503.06	12.05	1.569	0.50 (0.40)	0.79	3230.8	429.00
2	13846.97	13.83	1.407	0.50 (0.40)	0.79	3769.3	425.00
3	13852.76	14.04	1.388	0.50 (0.40)	0.79	3832.5	400.00
4	13591.92	15.90	1.267	0.50 (0.40)	0.79	4389.3	300.00
5	14137.12	22.25	1.050	0.50 (0.40)	0.79	6290.9	210.00
6	14160.27	23.92	1.003	0.50 (0.40)	0.79	6776.4	410.00
7	14155.76	25.63	0.960	0.50 (0.40)	0.79	7273.9	200.00
8	14153.66	26.10	0.950	0.50 (0.40)	0.79	7410.4	50400.00
9	14168.45	26.25	0.947	0.50 (0.40)	0.79	7471.6	50800.00
10	14187.75	26.46	0.943	0.50 (0.40)	0.79	7552.1	230.00
11	14200.11	26.59	0.941	0.50 (0.40)	0.79	7604.3	50600.00
12	14236.92	27.00	0.933	0.50 (0.40)	0.79	7760.7	50500.00
13	14287.66	27.58	0.921	0.50 (0.40)	0.80	7978.9	220.50
14	14386.13	28.72	0.899	0.50 (0.40)	0.80	8401.2	50700.00
15	14798.59	33.61	0.828	0.50 (0.40)	0.80	10179.6	410.00
16	14760.13	34.27	0.819	0.50 (0.40)	0.80	10470.2	110.00
17	14593.34	37.03	0.784	0.50 (0.40)	0.81	11730.7	100.00
18	14480.45	38.78	0.762	0.50 (0.41)	0.81	12523.7	100.00
19	14407.04	39.85	0.748	0.50 (0.41)	0.81	12996.6	50280.00
20	14172.44	43.10	0.720	0.50 (0.41)	0.82	14361.4	130.00
21	13956.61	46.26	0.694	0.50 (0.42)	0.83	15683.0	150.00
22	13758.36	49.72	0.665	0.50 (0.42)	0.84	17013.4	10100.00
23	13156.14	59.75	0.604	0.50 (0.43)	0.86	20744.9	31100.00
24	13067.63	61.37	0.597	0.50 (0.43)	0.86	21363.6	20100.00
25	12636.41	68.83	0.571	0.50 (0.44)	0.87	24062.9	13600.00
26	12282.84	75.64	0.548	0.50 (0.44)	0.88	26495.1	11801.00
27	11785.79	87.12	0.508	0.50 (0.45)	0.89	30523.6	11500.00
28	11202.38	99.28	0.480	0.50 (0.45)	0.90	35202.3	11000.00
29	10585.54	113.60	0.452	0.50 (0.46)	0.92	41853.6	13000.00
30	9481.01	131.31	0.426	0.50 (0.46)	0.93	49319.2	11130.00
31	9126.33	136.84	0.419	0.50 (0.47)	0.93	51114.0	13510.00
32	8730.73	143.22	0.412	0.50 (0.47)	0.93	53099.0	11620.00
33	7600.38	159.66	0.392	0.50 (0.47)	0.94	57675.3	12400.00
34	7310.87	163.46	0.388	0.50 (0.47)	0.94	58427.7	13500.00
35	6713.39	171.48	0.378	0.50 (0.47)	0.94	59993.2	12201.00
36	6076.01	181.13	0.367	0.50 (0.47)	0.94	61283.8	12111.00
37	5122.27	197.44	0.359	0.50 (0.47)	0.94	63206.7	12261.00
38	4639.09	207.11	0.353	0.50 (0.47)	0.94	64017.8	10200.00
39	4050.22	223.01	0.345	0.50 (0.47)	0.94	65255.8	10300.00
40	3809.74	230.10	0.341	0.50 (0.47)	0.94	65608.0	12010.00
41	3309.01	251.09	0.329	0.50 (0.47)	0.94	65936.3	12000.00
42	2245.96	321.17	0.291	0.50 (0.47)	0.94	66607.1	10100.00

=====
END OF RATIONAL METHOD ANALYSIS
=====

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 136 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 5-YR EV OCT 2022 ROKAMOTO *

FILE NAME: RU05EV36.DAT
TIME/DATE OF STUDY: 13:43 10/24/2022

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 5.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 2.604
- 2) 10.00; 1.741
- 3) 15.00; 1.296
- 4) 20.00; 1.108
- 5) 25.00; 0.968
- 6) 30.00; 0.871
- 7) 40.00; 0.743
- 8) 50.00; 0.660
- 9) 60.00; 0.598
- 10) 90.00; 0.495
- 11) 120.00; 0.435
- 12) 180.00; 0.364
- 13) 360.00; 0.267
- 14) 1200.00; 0.116

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	MANNING LIP (FT)	HIKE FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167 0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:

- 1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13600.00 TO NODE 13600.50 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 488.61
ELEVATION DATA: UPSTREAM(FEET) = 872.12 DOWNSTREAM(FEET) = 744.80

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 10.995
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.652
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "OPEN BRUSH"	-	3.39	0.50	1.000	0	11.00

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 3.52
TOTAL AREA(ACRES) = 3.39 PEAK FLOW RATE(CFS) = 3.52

FLOW PROCESS FROM NODE 13600.50 TO NODE 13601.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 744.80 DOWNSTREAM(FEET) = 707.32
CHANNEL LENGTH THRU SUBAREA(FEET) = 418.30 CHANNEL SLOPE = 0.0896
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.489
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.45	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 6.84
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.79
AVERAGE FLOW DEPTH(FEET) = 0.78 TRAVEL TIME(MIN.) = 1.84
Tc(MIN.) = 12.83
SUBAREA AREA(ACRES) = 7.45 SUBAREA RUNOFF(CFS) = 6.63
EFFECTIVE AREA(ACRES) = 10.84 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 10.8 PEAK FLOW RATE(CFS) = 9.65

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.88 FLOW VELOCITY(FEET/SEC.) = 4.15
LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13601.00 = 906.91 FEET.

FLOW PROCESS FROM NODE 13601.00 TO NODE 13602.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 707.32 DOWNSTREAM(FEET) = 657.12
CHANNEL LENGTH THRU SUBAREA(FEET) = 777.60 CHANNEL SLOPE = 0.0646
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00

* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.267

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include USER-DEFINED entries with various soil types and areas.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 20.38

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.41

AVERAGE FLOW DEPTH(FEET) = 1.24 TRAVEL TIME(MIN.) = 2.94

Tc(MIN.) = 15.77

SUBAREA AREA(ACRES) = 30.96 SUBAREA RUNOFF(CFS) = 21.37

EFFECTIVE AREA(ACRES) = 41.80 AREA-AVERAGED Fm(INCH/HR) = 0.50

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 41.8 PEAK FLOW RATE(CFS) = 28.85

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.41 FLOW VELOCITY(FEET/SEC.) = 4.81

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13602.00 = 1684.51 FEET.

FLOW PROCESS FROM NODE 13602.00 TO NODE 13603.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 657.12 DOWNSTREAM(FEET) = 584.58
CHANNEL LENGTH THRU SUBAREA(FEET) = 1186.54 CHANNEL SLOPE = 0.0611
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00

* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.118

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include USER-DEFINED entries with various soil types and areas.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 35.35

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.98

AVERAGE FLOW DEPTH(FEET) = 1.54 TRAVEL TIME(MIN.) = 3.97

Tc(MIN.) = 19.74

SUBAREA AREA(ACRES) = 23.36 SUBAREA RUNOFF(CFS) = 12.98

EFFECTIVE AREA(ACRES) = 65.16 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 65.2 PEAK FLOW RATE(CFS) = 36.22

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.55 FLOW VELOCITY(FEET/SEC.) = 5.00

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13603.00 = 2871.05 FEET.

FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 584.58 DOWNSTREAM(FEET) = 544.91
CHANNEL LENGTH THRU SUBAREA(FEET) = 860.98 CHANNEL SLOPE = 0.0461
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00

* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.029

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include USER-DEFINED entries with various soil types and areas.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 41.27

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.64

AVERAGE FLOW DEPTH(FEET) = 1.72 TRAVEL TIME(MIN.) = 3.09

Tc(MIN.) = 22.83

SUBAREA AREA(ACRES) = 21.24 SUBAREA RUNOFF(CFS) = 10.10

EFFECTIVE AREA(ACRES) = 86.40 AREA-AVERAGED Fm(INCH/HR) = 0.50

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 86.4 PEAK FLOW RATE(CFS) = 41.10

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.72 FLOW VELOCITY(FEET/SEC.) = 4.63

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13620.00 = 3732.03 FEET.

FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 13522.00 TO NODE 13522.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: S35X05.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

Table with 7 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Fp(Fm) (INCH/HR), Ap (ACRES), Ae (ACRES), HEADWATER NODE.

1 100.55 73.18 0.50(0.47) 0.95 1498.1 13510.00
 2 54.12 90.88 0.50(0.47) 0.94 1579.8 13500.00
 TOTAL AREA (ACRES) = 1579.8

FLOW PROCESS FROM NODE 13522.00 TO NODE 13522.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	100.55	73.18	0.50 (0.47)	0.95	1498.1	13510.00
2	54.12	90.88	0.50 (0.47)	0.94	1579.8	13500.00
TOTAL AREA (ACRES) =						1579.8

FLOW PROCESS FROM NODE 13522.00 TO NODE 13620.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 632.19 DOWNSTREAM (FEET) = 544.91

CHANNEL LENGTH THRU SUBAREA (FEET) = 2062.96 CHANNEL SLOPE = 0.0423

CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00

* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.537

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	17.68	0.50	1.000	-
USER-DEFINED	-	2.36	0.50	1.000	-
USER-DEFINED	-	0.60	0.50	1.000	-
USER-DEFINED	-	0.22	0.50	1.000	-
USER-DEFINED	-	2.22	0.50	1.000	-
USER-DEFINED	-	3.42	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 101.00

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.63

AVERAGE FLOW DEPTH (FEET) = 2.10 TRAVEL TIME (MIN.) = 4.51

Tc (MIN.) = 77.69

SUBAREA AREA (ACRES) = 26.50 SUBAREA RUNOFF (CFS) = 0.88

EFFECTIVE AREA (ACRES) = 1524.58 AREA-AVERAGED Fm (INCH/HR) = 0.47

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.95

TOTAL AREA (ACRES) = 1606.3 PEAK FLOW RATE (CFS) = 100.55

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 2.10 FLOW VELOCITY (FEET/SEC.) = 7.64

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

FLOW PROCESS FROM NODE 13620.00 TO NODE 13620.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 77.69

* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.537

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.44	0.50	1.000	-
USER-DEFINED	-	0.01	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 1.45 SUBAREA RUNOFF (CFS) = 0.05

EFFECTIVE AREA (ACRES) = 1526.03 AREA-AVERAGED Fm (INCH/HR) = 0.47

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.95

TOTAL AREA (ACRES) = 1607.8 PEAK FLOW RATE (CFS) = 100.55

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	100.55	77.69	0.537	0.50 (0.47)	0.95	1526.0	13510.00
2	54.12	96.14	0.483	0.50 (0.47)	0.95	1607.8	13500.00
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.							

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	41.10	22.83	1.029	0.50 (0.50)	1.00	86.4	13600.00
LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13620.00 = 3732.03 FEET.							

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	141.65	22.83	1.029	0.50 (0.48)	0.96	534.9	13600.00
2	103.43	77.69	0.537	0.50 (0.48)	0.95	1612.4	13510.00
3	54.12	96.14	0.483	0.50 (0.47)	0.95	1694.2	13500.00
TOTAL AREA (ACRES) = 1694.2							

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 141.65 Tc (MIN.) = 22.831

EFFECTIVE AREA (ACRES) = 534.85 AREA-AVERAGED Fm (INCH/HR) = 0.48

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.95

TOTAL AREA (ACRES) = 1694.2

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

FLOW PROCESS FROM NODE 13620.00 TO NODE 13640.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 544.91 DOWNSTREAM (FEET) = 489.00

CHANNEL LENGTH THRU SUBAREA (FEET) = 1384.37 CHANNEL SLOPE = 0.0404

CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.956
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.39	0.50	1.000	-
USER-DEFINED	-	16.30	0.50	1.000	-
USER-DEFINED	-	4.08	0.50	1.000	-
USER-DEFINED	-	12.36	0.50	1.000	-
USER-DEFINED	-	11.23	0.50	1.000	-
USER-DEFINED	-	5.16	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 152.83
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.31
 AVERAGE FLOW DEPTH (FEET) = 2.48 TRAVEL TIME (MIN.) = 2.78
 Tc (MIN.) = 25.61
 SUBAREA AREA (ACRES) = 54.52 SUBAREA RUNOFF (CFS) = 22.37
 EFFECTIVE AREA (ACRES) = 589.37 AREA-AVERAGED Fm (INCH/HR) = 0.48
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.96
 TOTAL AREA (ACRES) = 1748.7 PEAK FLOW RATE (CFS) = 252.29

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 2.99 FLOW VELOCITY (FEET/SEC.) = 9.42
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

 FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 25.61
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.956
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	53.93	0.50	1.000	-
USER-DEFINED	-	0.45	0.50	1.000	-
USER-DEFINED	-	3.98	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 58.36 SUBAREA RUNOFF (CFS) = 23.95
 EFFECTIVE AREA (ACRES) = 647.73 AREA-AVERAGED Fm (INCH/HR) = 0.48
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.96
 TOTAL AREA (ACRES) = 1807.1 PEAK FLOW RATE (CFS) = 276.24

 FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P201XX05.DNA
 MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap (DECIMAL)	Ae (ACRES)	HEADWATER NODE
1	73.57	19.49	0.50 (0.43)	0.85	133.8	20100.00

TOTAL AREA (ACRES) = 133.8

 FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap (DECIMAL)	Ae (ACRES)	HEADWATER NODE
1	276.24	25.61	0.956	0.50 (0.48)	0.96	647.7	13600.00
2	103.43	80.74	0.527	0.50 (0.48)	0.95	1725.3	13510.00
3	54.12	99.73	0.476	0.50 (0.48)	0.95	1807.1	13500.00

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap (DECIMAL)	Ae (ACRES)	HEADWATER NODE
1	73.57	19.49	1.127	0.50 (0.43)	0.85	133.8	20100.00

LONGEST FLOWPATH FROM NODE 20100.00 TO NODE 13640.00 = 5247.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap (DECIMAL)	Ae (ACRES)	HEADWATER NODE
1	349.80	19.49	1.127	0.50 (0.47)	0.94	626.8	20100.00
2	331.83	25.61	0.956	0.50 (0.47)	0.95	781.5	13600.00
3	113.89	80.74	0.527	0.50 (0.47)	0.95	1859.1	13510.00
4	61.40	99.73	0.476	0.50 (0.47)	0.94	1940.9	13500.00

TOTAL AREA (ACRES) = 1940.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 349.80 Tc (MIN.) = 19.493
 EFFECTIVE AREA (ACRES) = 626.82 AREA-AVERAGED Fm (INCH/HR) = 0.47
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.94
 TOTAL AREA (ACRES) = 1940.9
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

 FLOW PROCESS FROM NODE 13640.00 TO NODE 13641.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 489.00 DOWNSTREAM (FEET) = 436.89
 CHANNEL LENGTH THRU SUBAREA (FEET) = 2994.52 CHANNEL SLOPE = 0.0174
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.946

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.96	0.50	1.000	-
USER-DEFINED	-	0.01	0.50	1.000	-
USER-DEFINED	-	1.56	0.50	1.000	-
USER-DEFINED	-	10.45	0.50	1.000	-
USER-DEFINED	-	44.94	0.50	1.000	-
USER-DEFINED	-	9.66	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 363.38
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.53
 AVERAGE FLOW DEPTH(FEET) = 4.01 TRAVEL TIME(MIN.) = 6.63
 Tc(MIN.) = 26.12
 SUBAREA AREA(ACRES) = 67.58 SUBAREA RUNOFF(CFS) = 27.13
 EFFECTIVE AREA(ACRES) = 694.40 AREA-AVERAGED Fm(INCH/HR) = 0.47
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.95
 TOTAL AREA(ACRES) = 2008.4 PEAK FLOW RATE(CFS) = 349.80
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 3.95 FLOW VELOCITY(FEET/SEC.) = 7.45
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13641.00 = 25056.61 FEET.

 FLOW PROCESS FROM NODE 13641.00 TO NODE 13641.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 26.12
 * 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.946
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 16.49 0.50 1.000 -
 USER-DEFINED - 20.39 0.50 1.000 -
 USER-DEFINED - 7.02 0.50 1.000 -
 USER-DEFINED - 12.58 0.50 1.000 -
 USER-DEFINED - 42.49 0.50 1.000 -
 USER-DEFINED - 5.73 0.50 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 104.70 SUBAREA RUNOFF(CFS) = 42.04
 EFFECTIVE AREA(ACRES) = 799.10 AREA-AVERAGED Fm(INCH/HR) = 0.48
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.95
 TOTAL AREA(ACRES) = 2113.1 PEAK FLOW RATE(CFS) = 349.80
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13641.00 TO NODE 13641.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 26.12
 * 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.946
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 1.78 0.50 1.000 -
 USER-DEFINED - 6.25 0.50 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 8.03 SUBAREA RUNOFF(CFS) = 3.22
 EFFECTIVE AREA(ACRES) = 807.13 AREA-AVERAGED Fm(INCH/HR) = 0.48
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.95
 TOTAL AREA(ACRES) = 2121.2 PEAK FLOW RATE(CFS) = 349.80
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13641.00 TO NODE 13642.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 436.89 DOWNSTREAM(FEET) = 394.80
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2814.16 CHANNEL SLOPE = 0.0150
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
 * 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.837

SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 0.67 0.50 1.000 -
 USER-DEFINED - 24.24 0.50 1.000 -
 USER-DEFINED - 1.34 0.50 1.000 -
 USER-DEFINED - 74.98 0.50 1.000 -
 USER-DEFINED - 101.12 0.50 1.000 -
 USER-DEFINED - 16.90 0.50 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 383.14
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.21
 AVERAGE FLOW DEPTH(FEET) = 4.21 TRAVEL TIME(MIN.) = 6.50
 Tc(MIN.) = 32.62
 SUBAREA AREA(ACRES) = 219.25 SUBAREA RUNOFF(CFS) = 66.54
 EFFECTIVE AREA(ACRES) = 1026.38 AREA-AVERAGED Fm(INCH/HR) = 0.48
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.96
 TOTAL AREA(ACRES) = 2340.4 PEAK FLOW RATE(CFS) = 349.80
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 4.07 FLOW VELOCITY(FEET/SEC.) = 7.04
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13642.00 = 27870.77 FEET.

 FLOW PROCESS FROM NODE 13642.00 TO NODE 13642.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 32.62
 * 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.837
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 9.95 0.50 1.000 -
 USER-DEFINED - 10.02 0.50 1.000 -
 USER-DEFINED - 4.45 0.50 1.000 -
 USER-DEFINED - 179.37 0.50 1.000 -
 USER-DEFINED - 11.47 0.50 1.000 -
 USER-DEFINED - 0.17 0.50 0.850 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 215.43 SUBAREA RUNOFF(CFS) = 65.39
 EFFECTIVE AREA(ACRES) = 1241.81 AREA-AVERAGED Fm(INCH/HR) = 0.49
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.97
 TOTAL AREA(ACRES) = 2555.8 PEAK FLOW RATE(CFS) = 393.60


```

*****
FLOW PROCESS FROM NODE 13642.00 TO NODE 13642.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 32.62
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.837
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp        Ap        SCS
LAND USE                GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED            -         0.03     0.50     0.850    -
USER-DEFINED            -         5.14     0.50     1.000    -
USER-DEFINED            -        11.22     0.50     1.000    -
USER-DEFINED            -         0.33     0.50     1.000    -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 16.72      SUBAREA RUNOFF(CFS) = 5.08
EFFECTIVE AREA(ACRES) = 1258.53  AREA-AVERAGED Fm(INCH/HR) = 0.49
AREA-AVERAGED Fp(INCH/HR) = 0.50  AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 2572.6      PEAK FLOW RATE(CFS) = 398.68
*****
FLOW PROCESS FROM NODE 13642.00 TO NODE 13643.00 IS CODE = 51
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 394.80  DOWNSTREAM(FEET) = 342.39
CHANNEL LENGTH THRU SUBAREA(FEET) = 2913.57  CHANNEL SLOPE = 0.0180
CHANNEL BASE(FEET) = 0.00  "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040  MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.759
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp        Ap        SCS
LAND USE                GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED            -         0.22     0.50     1.000    -
USER-DEFINED            -         2.17     0.50     1.000    -
USER-DEFINED            -         9.19     0.50     1.000    -
USER-DEFINED            -        67.57     0.50     1.000    -
USER-DEFINED            -        35.19     0.50     1.000    -
USER-DEFINED            -        30.67     0.50     1.000    -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 415.55
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.88
AVERAGE FLOW DEPTH(FEET) = 4.19  TRAVEL TIME(MIN.) = 6.16
Tc(MIN.) = 38.79
SUBAREA AREA(ACRES) = 145.01      SUBAREA RUNOFF(CFS) = 33.71
EFFECTIVE AREA(ACRES) = 1403.54  AREA-AVERAGED Fm(INCH/HR) = 0.49
AREA-AVERAGED Fp(INCH/HR) = 0.50  AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 2717.6      PEAK FLOW RATE(CFS) = 398.68
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 4.13  FLOW VELOCITY(FEET/SEC.) = 7.79
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13643.00 = 30784.34 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13643.00 TO NODE 13643.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 38.79
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.759
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp        Ap        SCS
LAND USE                GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED            -         0.89     0.50     1.000    -
USER-DEFINED            -        20.65     0.50     1.000    -
USER-DEFINED            -         2.69     0.50     1.000    -
USER-DEFINED            -         8.45     0.50     1.000    -
USER-DEFINED            -        96.93     0.50     1.000    -
USER-DEFINED            -        13.19     0.50     1.000    -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 142.80      SUBAREA RUNOFF(CFS) = 33.20
EFFECTIVE AREA(ACRES) = 1546.34  AREA-AVERAGED Fm(INCH/HR) = 0.49
AREA-AVERAGED Fp(INCH/HR) = 0.50  AREA-AVERAGED Ap = 0.98
TOTAL AREA(ACRES) = 2860.4      PEAK FLOW RATE(CFS) = 398.68
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
*****
FLOW PROCESS FROM NODE 13643.00 TO NODE 13643.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 38.79
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.759
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp        Ap        SCS
LAND USE                GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED            -        42.54     0.50     1.000    -
USER-DEFINED            -        16.96     0.50     1.000    -
USER-DEFINED            -        80.60     0.50     1.000    -
USER-DEFINED            -         1.56     0.50     1.000    -
USER-DEFINED            -         2.00     0.50     1.000    -
USER-DEFINED            -         3.11     0.50     1.000    -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 146.77      SUBAREA RUNOFF(CFS) = 34.12
EFFECTIVE AREA(ACRES) = 1693.11  AREA-AVERAGED Fm(INCH/HR) = 0.49
AREA-AVERAGED Fp(INCH/HR) = 0.50  AREA-AVERAGED Ap = 0.98
TOTAL AREA(ACRES) = 3007.1      PEAK FLOW RATE(CFS) = 410.34
*****
FLOW PROCESS FROM NODE 13643.00 TO NODE 13660.00 IS CODE = 51
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 342.39  DOWNSTREAM(FEET) = 300.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1591.23  CHANNEL SLOPE = 0.0266
CHANNEL BASE(FEET) = 0.00  "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040  MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.729

```

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.89	0.50	1.000	-
USER-DEFINED	-	23.73	0.50	1.000	-
USER-DEFINED	-	0.27	0.50	1.000	-
USER-DEFINED	-	19.87	0.50	1.000	-
USER-DEFINED	-	6.40	0.50	1.000	-
USER-DEFINED	-	3.14	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 415.93
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.14
AVERAGE FLOW DEPTH(FEET) = 3.90 TRAVEL TIME(MIN.) = 2.90
Tc(MIN.) = 41.69
SUBAREA AREA(ACRES) = 54.30 SUBAREA RUNOFF(CFS) = 11.18
EFFECTIVE AREA(ACRES) = 1747.41 AREA-AVERAGED Fm(INCH/HR) = 0.49
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.98
TOTAL AREA(ACRES) = 3061.4 PEAK FLOW RATE(CFS) = 410.34
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 3.88 FLOW VELOCITY(FEET/SEC.) = 9.09
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 32375.57 FEET.

FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====

MAINLINE Tc(MIN.) = 41.69
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.729
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.67	0.50	1.000	-
USER-DEFINED	-	9.52	0.50	1.000	-
USER-DEFINED	-	0.71	0.50	1.000	-
USER-DEFINED	-	0.22	0.50	1.000	-
USER-DEFINED	-	39.42	0.50	1.000	-
USER-DEFINED	-	0.62	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 51.16 SUBAREA RUNOFF(CFS) = 10.53
EFFECTIVE AREA(ACRES) = 1798.57 AREA-AVERAGED Fm(INCH/HR) = 0.49
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.98
TOTAL AREA(ACRES) = 3112.6 PEAK FLOW RATE(CFS) = 410.34
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====

MAINLINE Tc(MIN.) = 41.69
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.729
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
USER-DEFINED	-	0.11	0.50	1.000	-
USER-DEFINED	-	0.77	0.50	1.000	-
USER-DEFINED	-	0.22	0.50	1.000	-
USER-DEFINED	-	2.69	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 3.79 SUBAREA RUNOFF(CFS) = 0.78
EFFECTIVE AREA(ACRES) = 1802.36 AREA-AVERAGED Fm(INCH/HR) = 0.49
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.98
TOTAL AREA(ACRES) = 3116.4 PEAK FLOW RATE(CFS) = 410.34
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13643.00 TO NODE 13660.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<
=====

FLOW PROCESS FROM NODE 13659.00 TO NODE 13659.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<
=====

PEAK FLOWRATE TABLE FILE NAME: 2P05EVAA.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	233.64	16.39	0.50(0.18)	0.36	170.4	110.00
2	231.85	19.13	0.50(0.19)	0.37	201.2	100.00
3	223.62	20.82	0.50(0.19)	0.38	212.8	100.00
4	190.12	24.85	0.50(0.20)	0.40	221.1	130.00
TOTAL AREA(ACRES) =		221.1				

FLOW PROCESS FROM NODE 13659.00 TO NODE 13660.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<
=====

ELEVATION DATA: UPSTREAM(FEET) = 338.00 DOWNSTREAM(FEET) = 300.00
FLOW LENGTH(FEET) = 881.07 MANNING'S N = 0.013
DEPTH OF FLOW IN 57.0 INCH PIPE IS 43.0 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 28.64
ESTIMATED PIPE DIAMETER(INCH) = 57.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 410.34
PIPE TRAVEL TIME(MIN.) = 0.51 Tc(MIN.) = 42.20
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<
=====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
------------------	------------	--------------	------------------------	---------------------	----	---------------	-------------------

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	410.34	42.20	0.725	0.50 (0.49)	0.98	1802.4	20100.00
2	348.87	48.93	0.669	0.50 (0.49)	0.98	1957.1	13600.00
3	113.89	111.68	0.452	0.50 (0.48)	0.97	3034.7	13510.00
4	61.40	135.77	0.416	0.50 (0.48)	0.97	3116.4	13500.00

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	233.64	16.39	1.244	0.50 (0.18)	0.36	170.4	110.00
2	231.85	19.13	1.141	0.50 (0.19)	0.37	201.2	100.00
3	223.62	20.82	1.085	0.50 (0.19)	0.38	212.8	100.00
4	190.12	24.85	0.972	0.50 (0.20)	0.40	221.1	130.00

LONGEST FLOWPATH FROM NODE 130.00 TO NODE 13660.00 = 6327.50 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	643.98	16.39	1.244	0.50 (0.43)	0.86	870.6	110.00
2	642.18	19.13	1.141	0.50 (0.43)	0.86	1018.1	100.00
3	633.96	20.82	1.085	0.50 (0.43)	0.86	1101.9	100.00
4	600.45	24.85	0.972	0.50 (0.44)	0.88	1282.3	130.00
5	539.46	42.20	0.725	0.50 (0.46)	0.92	2023.5	20100.00
6	464.24	48.93	0.669	0.50 (0.46)	0.92	2178.2	13600.00
7	180.53	111.68	0.452	0.50 (0.46)	0.93	3255.8	13510.00
8	122.83	135.77	0.416	0.50 (0.46)	0.93	3337.5	13500.00

TOTAL AREA (ACRES) = 3337.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 643.98 Tc (MIN.) = 16.395
 EFFECTIVE AREA (ACRES) = 870.58 AREA-AVERAGED Fm (INCH/HR) = 0.43
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.92
 TOTAL AREA (ACRES) = 3337.5
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

 FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 16.39

* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.244

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.11	0.50	1.000	-
USER-DEFINED	-	0.44	0.50	1.000	-
USER-DEFINED	-	1.49	0.50	1.000	-
USER-DEFINED	-	1.70	0.50	1.000	-
USER-DEFINED	-	1.09	0.50	1.000	-
USER-DEFINED	-	18.57	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 24.40 SUBAREA RUNOFF (CFS) = 16.32
 EFFECTIVE AREA (ACRES) = 894.98 AREA-AVERAGED Fm (INCH/HR) = 0.43
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.86
 TOTAL AREA (ACRES) = 3361.9 PEAK FLOW RATE (CFS) = 654.34

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	654.34	16.39	1.244	0.50 (0.43)	0.86	895.0	110.00
2	665.60	19.13	1.141	0.50 (0.43)	0.86	1042.5	100.00
3	660.79	20.82	1.085	0.50 (0.43)	0.87	1126.3	100.00
4	624.56	24.85	0.972	0.50 (0.44)	0.88	1306.7	130.00
5	539.46	42.20	0.725	0.50 (0.46)	0.92	2047.9	20100.00
6	464.24	48.93	0.669	0.50 (0.46)	0.92	2202.6	13600.00
7	180.53	111.68	0.452	0.50 (0.47)	0.93	3280.2	13510.00
8	122.83	135.77	0.416	0.50 (0.46)	0.93	3361.9	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 665.60 Tc (MIN.) = 19.13
 AREA-AVERAGED Fm (INCH/HR) = 0.43 AREA-AVERAGED Fp (INCH/HR) = 0.50
 AREA-AVERAGED Ap = 0.86 EFFECTIVE AREA (ACRES) = 1042.49

 FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 19.13

* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.141

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	12.39	0.50	1.000	-
USER-DEFINED	-	2.30	0.50	1.000	-
USER-DEFINED	-	5.19	0.50	1.000	-
USER-DEFINED	-	28.71	0.50	1.000	-
USER-DEFINED	-	0.17	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 48.76 SUBAREA RUNOFF (CFS) = 28.11
 EFFECTIVE AREA (ACRES) = 1091.25 AREA-AVERAGED Fm (INCH/HR) = 0.43
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.87
 TOTAL AREA (ACRES) = 3410.7 PEAK FLOW RATE (CFS) = 693.71

 FLOW PROCESS FROM NODE 13660.00 TO NODE 13680.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 300.00 DOWNSTREAM (FEET) = 288.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 933.89 CHANNEL SLOPE = 0.0128
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.077

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.22	0.50	1.000	-
USER-DEFINED	-	9.23	0.50	1.000	-
USER-DEFINED	-	0.54	0.50	1.000	-
USER-DEFINED	-	5.66	0.50	1.000	-
USER-DEFINED	-	3.66	0.50	1.000	-
USER-DEFINED	-	0.67	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 698.90
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.91
 AVERAGE FLOW DEPTH(FEET) = 5.43 TRAVEL TIME(MIN.) = 1.97
 Tc(MIN.) = 21.10
 SUBAREA AREA(ACRES) = 19.98 SUBAREA RUNOFF(CFS) = 10.38
 EFFECTIVE AREA(ACRES) = 1111.23 AREA-AVERAGED Fm(INCH/HR) = 0.44
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.87
 TOTAL AREA(ACRES) = 3430.6 PEAK FLOW RATE(CFS) = 693.71
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 5.41 FLOW VELOCITY(FEET/SEC.) = 7.89
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13680.00 = 34190.53 FEET.

 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 21.10
 * 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.077
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.56	0.50	1.000	-
USER-DEFINED	-	9.40	0.50	1.000	-
USER-DEFINED	-	2.76	0.50	1.000	-
USER-DEFINED	-	17.38	0.50	1.000	-
USER-DEFINED	-	2.46	0.50	1.000	-
USER-DEFINED	-	5.56	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 39.12 SUBAREA RUNOFF(CFS) = 20.32
 EFFECTIVE AREA(ACRES) = 1150.35 AREA-AVERAGED Fm(INCH/HR) = 0.44
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.88
 TOTAL AREA(ACRES) = 3469.8 PEAK FLOW RATE(CFS) = 693.71
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 21.10
 * 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.077
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.65	0.50	1.000	-
USER-DEFINED	-	1.70	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 2.35 SUBAREA RUNOFF(CFS) = 1.22
 EFFECTIVE AREA(ACRES) = 1152.70 AREA-AVERAGED Fm(INCH/HR) = 0.44
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.88
 TOTAL AREA(ACRES) = 3472.1 PEAK FLOW RATE(CFS) = 693.71

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13660.00 TO NODE 13680.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 21.10
 * 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.077
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.29	0.50	1.000	-
USER-DEFINED	-	31.25	0.50	1.000	-
USER-DEFINED	-	0.22	0.50	1.000	-
USER-DEFINED	-	6.26	0.50	1.000	-
USER-DEFINED	-	0.07	0.50	1.000	-
USER-DEFINED	-	0.22	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 43.31 SUBAREA RUNOFF(CFS) = 22.49
 EFFECTIVE AREA(ACRES) = 1196.01 AREA-AVERAGED Fm(INCH/HR) = 0.44
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.88
 TOTAL AREA(ACRES) = 3515.4 PEAK FLOW RATE(CFS) = 693.71
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 21.10
 * 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.077
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	2.47	0.50	0.850	-
USER-DEFINED	-	3.06	0.50	0.850	-
USER-DEFINED	-	17.76	0.50	0.500	-
USER-DEFINED	-	7.31	0.50	0.500	-
USER-DEFINED	-	0.34	0.50	1.000	-
USER-DEFINED	-	8.22	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.659
 SUBAREA AREA(ACRES) = 39.16 SUBAREA RUNOFF(CFS) = 26.36
 EFFECTIVE AREA(ACRES) = 1235.17 AREA-AVERAGED Fm(INCH/HR) = 0.44
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.87
 TOTAL AREA(ACRES) = 3554.6 PEAK FLOW RATE(CFS) = 712.14

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap (ACRES)	Ae (ACRES)	HEADWATER NODE
------------------	------------	--------------	------------------------	---------------------	---------------	---------------	-------------------

1	716.62	18.37	1.169	0.50	(0.44)	0.87	1087.7	110.00
2	712.14	21.10	1.077	0.50	(0.44)	0.87	1235.2	100.00
3	702.65	22.79	1.030	0.50	(0.44)	0.88	1318.9	100.00
4	658.25	26.85	0.932	0.50	(0.44)	0.89	1499.4	130.00
5	539.46	44.30	0.707	0.50	(0.46)	0.92	2240.5	20100.00
6	464.24	51.11	0.653	0.50	(0.46)	0.92	2395.3	13600.00
7	180.53	114.44	0.446	0.50	(0.47)	0.93	3472.8	13510.00
8	122.83	138.81	0.413	0.50	(0.46)	0.93	3554.6	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 716.62 Tc(MIN.) = 18.37
 AREA-AVERAGED Fm(INCH/HR) = 0.44 AREA-AVERAGED Fp(INCH/HR) = 0.50
 AREA-AVERAGED Ap = 0.87 EFFECTIVE AREA(ACRES) = 1087.66

 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 18.37
 * 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.169
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/	SCS SOIL	AREA	Fp	Ap	SCS
LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
USER-DEFINED	-	0.53	0.50	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 0.53 SUBAREA RUNOFF(CFS) = 0.32
 EFFECTIVE AREA(ACRES) = 1088.19 AREA-AVERAGED Fm(INCH/HR) = 0.44
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.87
 TOTAL AREA(ACRES) = 3555.1 PEAK FLOW RATE(CFS) = 716.94

 FLOW PROCESS FROM NODE 13680.00 TO NODE 13682.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 288.00 DOWNSTREAM(FEET) = 242.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2860.77 CHANNEL SLOPE = 0.0161
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
 * 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.000
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/	SCS SOIL	AREA	Fp	Ap	SCS
LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
USER-DEFINED	-	0.22	0.50	1.000	-
USER-DEFINED	-	5.28	0.50	1.000	-
USER-DEFINED	-	0.52	0.50	1.000	-
USER-DEFINED	-	3.61	0.50	1.000	-
USER-DEFINED	-	0.67	0.50	1.000	-
USER-DEFINED	-	1.37	0.50	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 719.57
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.66
 AVERAGE FLOW DEPTH(FEET) = 5.26 TRAVEL TIME(MIN.) = 5.50
 Tc(MIN.) = 23.87
 SUBAREA AREA(ACRES) = 11.67 SUBAREA RUNOFF(CFS) = 5.25

EFFECTIVE AREA(ACRES) = 1099.86 AREA-AVERAGED Fm(INCH/HR) = 0.44
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.88
 TOTAL AREA(ACRES) = 3566.8 PEAK FLOW RATE(CFS) = 716.94
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 5.25 FLOW VELOCITY(FEET/SEC.) = 8.66
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13682.00 = 37051.30 FEET.

 FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 23.87
 * 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.000
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/	SCS SOIL	AREA	Fp	Ap	SCS
LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
USER-DEFINED	-	6.90	0.50	1.000	-
USER-DEFINED	-	23.04	0.50	1.000	-
USER-DEFINED	-	1.18	0.50	1.000	-
USER-DEFINED	-	1.56	0.50	1.000	-
USER-DEFINED	-	53.20	0.50	1.000	-
USER-DEFINED	-	2.08	0.50	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 87.96 SUBAREA RUNOFF(CFS) = 39.53
 EFFECTIVE AREA(ACRES) = 1187.82 AREA-AVERAGED Fm(INCH/HR) = 0.44
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.88
 TOTAL AREA(ACRES) = 3654.7 PEAK FLOW RATE(CFS) = 716.94
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 23.87
 * 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.000
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/	SCS SOIL	AREA	Fp	Ap	SCS
LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
USER-DEFINED	-	0.01	0.50	1.000	-
USER-DEFINED	-	0.18	0.50	1.000	-
USER-DEFINED	-	0.38	0.50	1.000	-
USER-DEFINED	-	0.22	0.50	1.000	-
USER-DEFINED	-	7.73	0.50	1.000	-
USER-DEFINED	-	4.37	0.50	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 12.89 SUBAREA RUNOFF(CFS) = 5.79
 EFFECTIVE AREA(ACRES) = 1200.71 AREA-AVERAGED Fm(INCH/HR) = 0.44
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.89
 TOTAL AREA(ACRES) = 3667.6 PEAK FLOW RATE(CFS) = 716.94
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 23.87

* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.000

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	2.57	0.50	1.000	-
USER-DEFINED	-	1.97	0.50	1.000	-
USER-DEFINED	-	1.00	0.50	1.000	-
USER-DEFINED	-	2.98	0.50	1.000	-
USER-DEFINED	-	2.39	0.50	1.000	-
USER-DEFINED	-	1.67	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 12.58 SUBAREA RUNOFF (CFS) = 5.65

EFFECTIVE AREA (ACRES) = 1213.29 AREA-AVERAGED Fm (INCH/HR) = 0.44

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.89

TOTAL AREA (ACRES) = 3680.2 PEAK FLOW RATE (CFS) = 716.94

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 23.87

* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.000

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.44	0.50	1.000	-
USER-DEFINED	-	2.65	0.50	0.850	-
USER-DEFINED	-	1.16	0.50	0.850	-
USER-DEFINED	-	0.47	0.50	0.500	-
USER-DEFINED	-	0.25	0.50	0.500	-
USER-DEFINED	-	20.24	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.963

SUBAREA AREA (ACRES) = 25.21 SUBAREA RUNOFF (CFS) = 11.75

EFFECTIVE AREA (ACRES) = 1238.50 AREA-AVERAGED Fm (INCH/HR) = 0.44

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.89

TOTAL AREA (ACRES) = 3705.4 PEAK FLOW RATE (CFS) = 716.94

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 23.87

* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.000

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.08	0.50	1.000	-

USER-DEFINED - 6.75 0.50 1.000 -
USER-DEFINED - 0.02 0.50 1.000 -
USER-DEFINED - 0.93 0.50 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 14.78 SUBAREA RUNOFF (CFS) = 6.64

EFFECTIVE AREA (ACRES) = 1253.28 AREA-AVERAGED Fm (INCH/HR) = 0.45

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.89

TOTAL AREA (ACRES) = 3720.2 PEAK FLOW RATE (CFS) = 716.94

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13682.00 TO NODE 13683.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 242.00 DOWNSTREAM (FEET) = 208.53

CHANNEL LENGTH THRU SUBAREA (FEET) = 2526.22 CHANNEL SLOPE = 0.0132

CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00

* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.889

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.49	0.50	1.000	-
USER-DEFINED	-	13.31	0.50	1.000	-
USER-DEFINED	-	0.87	0.50	1.000	-
USER-DEFINED	-	20.26	0.50	1.000	-
USER-DEFINED	-	1.21	0.50	1.000	-
USER-DEFINED	-	0.05	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 724.67

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.08

AVERAGE FLOW DEPTH (FEET) = 5.47 TRAVEL TIME (MIN.) = 5.21

Tc (MIN.) = 29.08

SUBAREA AREA (ACRES) = 44.19 SUBAREA RUNOFF (CFS) = 15.46

EFFECTIVE AREA (ACRES) = 1297.47 AREA-AVERAGED Fm (INCH/HR) = 0.45

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.89

TOTAL AREA (ACRES) = 3764.4 PEAK FLOW RATE (CFS) = 716.94

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 5.45 FLOW VELOCITY (FEET/SEC.) = 8.05

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13683.00 = 39577.52 FEET.

FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 29.08

* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.889

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	12.56	0.50	1.000	-

```

USER-DEFINED      -      0.81      0.50      1.000      -
USER-DEFINED      -      0.01      0.50      1.000      -
USER-DEFINED      -      1.11      0.50      1.000      -
USER-DEFINED      -      0.59      0.50      1.000      -
USER-DEFINED      -      3.04      0.50      1.000      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 18.12      SUBAREA RUNOFF (CFS) = 6.34
EFFECTIVE AREA (ACRES) = 1315.59      AREA-AVERAGED Fm (INCH/HR) = 0.45
AREA-AVERAGED Fp (INCH/HR) = 0.50      AREA-AVERAGED Ap = 0.90
TOTAL AREA (ACRES) = 3782.5      PEAK FLOW RATE (CFS) = 716.94
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81
-----

```

```
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
```

```

=====
MAINLINE Tc (MIN.) = 29.08
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.889
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/      SCS SOIL      AREA      Fp      Ap      SCS
LAND USE      GROUP      (ACRES)      (INCH/HR)      (DECIMAL)      CN
USER-DEFINED      -      0.10      0.50      0.400      -
USER-DEFINED      -      1.30      0.50      0.850      -
USER-DEFINED      -      0.10      0.50      0.400      -
USER-DEFINED      -      1.70      0.50      0.850      -
USER-DEFINED      -      0.10      0.50      0.850      -
USER-DEFINED      -      2.90      0.50      0.850      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.835
SUBAREA AREA (ACRES) = 6.20      SUBAREA RUNOFF (CFS) = 2.63
EFFECTIVE AREA (ACRES) = 1321.79      AREA-AVERAGED Fm (INCH/HR) = 0.45
AREA-AVERAGED Fp (INCH/HR) = 0.50      AREA-AVERAGED Ap = 0.89
TOTAL AREA (ACRES) = 3788.7      PEAK FLOW RATE (CFS) = 716.94
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81
-----

```

```
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
```

```

=====
MAINLINE Tc (MIN.) = 29.08
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.889
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/      SCS SOIL      AREA      Fp      Ap      SCS
LAND USE      GROUP      (ACRES)      (INCH/HR)      (DECIMAL)      CN
USER-DEFINED      -      0.10      0.50      0.500      -
USER-DEFINED      -      0.10      0.50      0.350      -
USER-DEFINED      -      6.90      0.50      0.850      -
USER-DEFINED      -      0.40      0.50      0.850      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.839
SUBAREA AREA (ACRES) = 7.50      SUBAREA RUNOFF (CFS) = 3.17
EFFECTIVE AREA (ACRES) = 1329.29      AREA-AVERAGED Fm (INCH/HR) = 0.45
AREA-AVERAGED Fp (INCH/HR) = 0.50      AREA-AVERAGED Ap = 0.89
TOTAL AREA (ACRES) = 3796.2      PEAK FLOW RATE (CFS) = 716.94
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13682.00 TO NODE 13683.00 IS CODE = 12
-----

```

```
>>>>CLEAR MEMORY BANK # 3 <<<<
```

```
*****MEMORY BANK # 3 IS EMPTY - PROCESS IGNORED.***
```

```

*****
FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81
-----

```

```
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
```

```

=====
MAINLINE Tc (MIN.) = 29.08
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.889
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/      SCS SOIL      AREA      Fp      Ap      SCS
LAND USE      GROUP      (ACRES)      (INCH/HR)      (DECIMAL)      CN
USER-DEFINED      -      2.55      0.50      1.000      -
USER-DEFINED      -      0.01      0.50      1.000      -
USER-DEFINED      -      1.35      0.50      1.000      -
USER-DEFINED      -      0.44      0.50      1.000      -
USER-DEFINED      -      0.67      0.50      1.000      -
USER-DEFINED      -      1.06      0.50      1.000      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 6.08      SUBAREA RUNOFF (CFS) = 2.13
EFFECTIVE AREA (ACRES) = 1335.37      AREA-AVERAGED Fm (INCH/HR) = 0.45
AREA-AVERAGED Fp (INCH/HR) = 0.50      AREA-AVERAGED Ap = 0.90
TOTAL AREA (ACRES) = 3802.3      PEAK FLOW RATE (CFS) = 716.94
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81
-----

```

```
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
```

```

=====
MAINLINE Tc (MIN.) = 29.08
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.889
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/      SCS SOIL      AREA      Fp      Ap      SCS
LAND USE      GROUP      (ACRES)      (INCH/HR)      (DECIMAL)      CN
USER-DEFINED      -      2.16      0.50      1.000      -
USER-DEFINED      -      2.45      0.50      1.000      -
USER-DEFINED      -      6.15      0.50      1.000      -
USER-DEFINED      -      1.34      0.50      1.000      -
USER-DEFINED      -      18.46      0.50      1.000      -
USER-DEFINED      -      4.13      0.50      1.000      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 34.69      SUBAREA RUNOFF (CFS) = 12.13
EFFECTIVE AREA (ACRES) = 1370.06      AREA-AVERAGED Fm (INCH/HR) = 0.45
AREA-AVERAGED Fp (INCH/HR) = 0.50      AREA-AVERAGED Ap = 0.90
TOTAL AREA (ACRES) = 3837.0      PEAK FLOW RATE (CFS) = 716.94
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81
-----

```

=====
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====

MAINLINE Tc(MIN.) = 29.08
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.889
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 8.69 0.50 1.000 -
USER-DEFINED - 0.73 0.50 1.000 -
USER-DEFINED - 0.41 0.50 1.000 -
USER-DEFINED - 1.37 0.50 1.000 -
USER-DEFINED - 3.11 0.50 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 14.31 SUBAREA RUNOFF(CFS) = 5.01
EFFECTIVE AREA(ACRES) = 1384.37 AREA-AVERAGED Fm(INCH/HR) = 0.45
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.90
TOTAL AREA(ACRES) = 3851.3 PEAK FLOW RATE(CFS) = 716.94
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13683.00 TO NODE 13685.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====

ELEVATION DATA: UPSTREAM(FEET) = 208.53 DOWNSTREAM(FEET) = 194.24
CHANNEL LENGTH THRU SUBAREA(FEET) = 289.01 CHANNEL SLOPE = 0.0494
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
CHANNEL FLOW THRU SUBAREA(CFS) = 716.94
FLOW VELOCITY(FEET/SEC.) = 13.20 FLOW DEPTH(FEET) = 4.25
TRAVEL TIME(MIN.) = 0.36 Tc(MIN.) = 29.45
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13685.00 = 39866.53 FEET.

FLOW PROCESS FROM NODE 13685.00 TO NODE 13410.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====

ELEVATION DATA: UPSTREAM(FEET) = 194.24 DOWNSTREAM(FEET) = 178.72
CHANNEL LENGTH THRU SUBAREA(FEET) = 1843.57 CHANNEL SLOPE = 0.0084
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.820
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.23 0.50 1.000 -
USER-DEFINED - 1.52 0.50 1.000 -
USER-DEFINED - 0.06 0.50 1.000 -
USER-DEFINED - 0.13 0.50 1.000 -
USER-DEFINED - 6.45 0.50 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 718.15

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.80
AVERAGE FLOW DEPTH(FEET) = 5.93 TRAVEL TIME(MIN.) = 4.52
Tc(MIN.) = 33.96
SUBAREA AREA(ACRES) = 8.39 SUBAREA RUNOFF(CFS) = 2.42
EFFECTIVE AREA(ACRES) = 1392.76 AREA-AVERAGED Fm(INCH/HR) = 0.45
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.90
TOTAL AREA(ACRES) = 3859.7 PEAK FLOW RATE(CFS) = 716.94
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 5.93 FLOW VELOCITY(FEET/SEC.) = 6.79
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13410.00 = 41710.10 FEET.
=====

END OF STUDY SUMMARY:
TOTAL AREA(ACRES) = 3859.7 TC(MIN.) = 33.96
EFFECTIVE AREA(ACRES) = 1392.76 AREA-AVERAGED Fm(INCH/HR) = 0.45
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.899
PEAK FLOW RATE(CFS) = 716.94

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	716.94	33.96	0.820	0.50(0.45)	0.90	1392.8	110.00
2	712.41	36.72	0.785	0.50(0.45)	0.90	1540.3	100.00
3	702.91	38.48	0.762	0.50(0.45)	0.90	1624.0	100.00
4	658.46	42.79	0.720	0.50(0.45)	0.91	1804.5	130.00
5	539.46	61.06	0.594	0.50(0.46)	0.93	2545.6	20100.00
6	464.24	68.52	0.569	0.50(0.46)	0.93	2700.4	13600.00
7	180.53	136.50	0.415	0.50(0.47)	0.93	3777.9	13510.00
8	122.83	163.10	0.384	0.50(0.47)	0.93	3859.7	13500.00

=====
END OF RATIONAL METHOD ANALYSIS
=====

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2010 Advanced Engineering Software (aes)
Ver. 17.0 Release Date: 07/01/2010 License ID 1527

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 137 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 5-YR EV AUG 2023 ROKAMOTO *

FILE NAME: RU05EV37.DAT
TIME/DATE OF STUDY: 23:46 08/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 5.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 2.596
- 2) 10.00; 1.737
- 3) 15.00; 1.294
- 4) 20.00; 1.106
- 5) 25.00; 0.966
- 6) 30.00; 0.870
- 7) 40.00; 0.742
- 8) 50.00; 0.660
- 9) 60.00; 0.598
- 10) 90.00; 0.494
- 11) 120.00; 0.434
- 12) 180.00; 0.363
- 13) 360.00; 0.266
- 14) 1200.00; 0.116

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU05EV34.DNA
MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13852.76	14.04	0.50 (0.40)	0.79	3832.5	400.00
2	14798.59	33.61	0.50 (0.40)	0.80	10179.6	410.00
3	14172.44	43.10	0.50 (0.41)	0.82	14361.4	130.00
4	13156.14	59.75	0.50 (0.43)	0.86	20744.9	31100.00
5	12636.41	68.83	0.50 (0.44)	0.87	24062.9	13600.00
6	12282.84	75.64	0.50 (0.44)	0.88	26495.1	11801.00
7	11785.79	87.12	0.50 (0.45)	0.89	30523.6	11500.00
8	11202.38	99.28	0.50 (0.45)	0.90	35202.3	11000.00
9	10585.54	113.60	0.50 (0.46)	0.92	41853.6	13000.00
10	9481.01	131.31	0.50 (0.46)	0.93	49319.2	11130.00
11	8730.73	143.22	0.50 (0.47)	0.93	53099.0	11620.00
12	7600.38	159.66	0.50 (0.47)	0.94	57675.3	12400.00
13	6713.39	171.48	0.50 (0.47)	0.94	59993.2	12201.00
14	6076.01	181.13	0.50 (0.47)	0.94	61283.8	12111.00
15	5122.27	197.44	0.50 (0.47)	0.94	63206.7	12261.00
16	4639.09	207.11	0.50 (0.47)	0.94	64017.8	10200.00
17	4050.22	223.01	0.50 (0.47)	0.94	65255.8	10300.00
18	3809.74	230.10	0.50 (0.47)	0.94	65608.0	12010.00
19	3309.01	251.09	0.50 (0.47)	0.94	65936.3	12000.00
20	2245.96	321.17	0.50 (0.47)	0.94	66607.1	10100.00
TOTAL AREA (ACRES) =						66607.1

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 14.0

>>>>MEMORY BANK # 3 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13852.76	14.04	0.50 (0.40)	0.79	3832.5	400.00
2	14798.59	33.61	0.50 (0.40)	0.80	10179.6	410.00
3	14172.44	43.10	0.50 (0.41)	0.82	14361.4	130.00
4	13156.14	59.75	0.50 (0.43)	0.86	20744.9	31100.00
5	12636.41	68.83	0.50 (0.44)	0.87	24062.9	13600.00
6	12282.84	75.64	0.50 (0.44)	0.88	26495.1	11801.00
7	11785.79	87.12	0.50 (0.45)	0.89	30523.6	11500.00
8	11202.38	99.28	0.50 (0.45)	0.90	35202.3	11000.00
9	10585.54	113.60	0.50 (0.46)	0.92	41853.6	13000.00
10	9481.01	131.31	0.50 (0.46)	0.93	49319.2	11130.00
11	8730.73	143.22	0.50 (0.47)	0.93	53099.0	11620.00
12	7600.38	159.66	0.50 (0.47)	0.94	57675.3	12400.00
13	6713.39	171.48	0.50 (0.47)	0.94	59993.2	12201.00

14	6076.01	181.13	0.50	(0.47)	0.94	61283.8	12111.00
15	5122.27	197.44	0.50	(0.47)	0.94	63206.7	12261.00
16	4639.09	207.11	0.50	(0.47)	0.94	64017.8	10200.00
17	4050.22	223.01	0.50	(0.47)	0.94	65255.8	10300.00
18	3809.74	230.10	0.50	(0.47)	0.94	65608.0	12010.00
19	3309.01	251.09	0.50	(0.47)	0.94	65936.3	12000.00
20	2245.96	321.17	0.50	(0.47)	0.94	66607.1	10100.00

TOTAL AREA(ACRES) = 66607.1

FLOW PROCESS FROM NODE 13700.00 TO NODE 13720.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 170.00 DOWNSTREAM(FEET) = 165.51
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1891.83 CHANNEL SLOPE = 0.0024
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00

==>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL
 CAPACITY(NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM
 ALLOWABLE DEPTH).
 AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM
 ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

CHANNEL FLOW THRU SUBAREA(CFS) = 14798.59
 FLOW VELOCITY(FEET/SEC.) = 12.33 FLOW DEPTH(FEET) = 20.00
 TRAVEL TIME(MIN.) = 2.56 Tc(MIN.) = 36.17
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126420.58 FEET.

FLOW PROCESS FROM NODE 13700.00 TO NODE 13720.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

FLOW PROCESS FROM NODE 13720.00 TO NODE 13720.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506102f.DNA
 MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	108.74	17.82	0.50 (0.48)	0.96	196.1	10230.00
2	89.60	26.01	0.50 (0.48)	0.95	235.1	10250.00
3	84.70	27.80	0.50 (0.48)	0.95	241.6	10200.00
4	70.42	32.34	0.50 (0.48)	0.95	246.3	10220.00

TOTAL AREA(ACRES) = 246.3

FLOW PROCESS FROM NODE 13720.00 TO NODE 13720.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13852.76	16.77	1.227	0.50 (0.40)	0.79	3832.5	400.00
2	14798.59	36.17	0.791	0.50 (0.40)	0.80	10179.6	410.00
3	14172.44	45.77	0.695	0.50 (0.41)	0.82	14361.4	130.00
4	13156.14	62.63	0.589	0.50 (0.43)	0.86	20744.9	31100.00
5	12636.41	71.77	0.557	0.50 (0.44)	0.87	24062.9	13600.00
6	12282.84	78.60	0.534	0.50 (0.44)	0.88	26495.1	11801.00
7	11785.79	90.10	0.494	0.50 (0.45)	0.89	30523.6	11500.00
8	11202.38	102.31	0.469	0.50 (0.45)	0.90	35202.3	11000.00
9	10585.54	116.66	0.441	0.50 (0.46)	0.92	41853.6	13000.00
10	9481.01	134.46	0.417	0.50 (0.46)	0.93	49319.2	11130.00
11	8730.73	146.44	0.403	0.50 (0.47)	0.93	53099.0	11620.00
12	7600.38	162.99	0.383	0.50 (0.47)	0.94	57675.3	12400.00
13	6713.39	174.91	0.369	0.50 (0.47)	0.94	59993.2	12201.00
14	6076.01	184.65	0.360	0.50 (0.47)	0.94	61283.8	12111.00
15	5122.27	201.12	0.352	0.50 (0.47)	0.94	63206.7	12261.00
16	4639.09	210.88	0.346	0.50 (0.47)	0.94	64017.8	10200.00
17	4050.22	226.91	0.338	0.50 (0.47)	0.94	65255.8	10300.00
18	3809.74	234.06	0.334	0.50 (0.47)	0.94	65608.0	12010.00
19	3309.01	255.20	0.322	0.50 (0.47)	0.94	65936.3	12000.00
20	2245.96	325.68	0.284	0.50 (0.47)	0.94	66607.1	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126420.58 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	108.74	17.82	1.188	0.50 (0.48)	0.96	196.1	10230.00
2	89.60	26.01	0.947	0.50 (0.48)	0.95	235.1	10250.00
3	84.70	27.80	0.912	0.50 (0.48)	0.95	241.6	10200.00
4	70.42	32.34	0.840	0.50 (0.48)	0.95	246.3	10220.00

LONGEST FLOWPATH FROM NODE 10200.00 TO NODE 13720.00 = 9099.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13960.82	16.77	1.227	0.50 (0.40)	0.80	4017.0	400.00
2	14012.74	17.82	1.188	0.50 (0.40)	0.80	4372.4	10230.00
3	14393.05	26.01	0.947	0.50 (0.40)	0.80	7092.0	10250.00
4	14475.30	27.80	0.912	0.50 (0.40)	0.80	7683.3	10200.00
5	14682.49	32.34	0.840	0.50 (0.40)	0.80	9174.2	10220.00
6	14859.52	36.17	0.791	0.50 (0.40)	0.80	10425.9	410.00
7	14214.66	45.77	0.695	0.50 (0.41)	0.83	14607.7	130.00
8	13177.84	62.63	0.589	0.50 (0.43)	0.86	20991.2	31100.00
9	12651.96	71.77	0.557	0.50 (0.44)	0.87	24309.2	13600.00
10	12293.79	78.60	0.534	0.50 (0.44)	0.88	26741.3	11801.00
11	11790.22	90.10	0.494	0.50 (0.45)	0.89	30769.9	11500.00
12	11206.59	102.31	0.469	0.50 (0.45)	0.91	35448.6	11000.00
13	10589.49	116.66	0.441	0.50 (0.46)	0.92	42099.9	13000.00
14	9484.75	134.46	0.417	0.50 (0.46)	0.93	49565.5	11130.00
15	8734.35	146.44	0.403	0.50 (0.47)	0.93	53345.3	11620.00
16	7603.81	162.99	0.383	0.50 (0.47)	0.94	57921.6	12400.00
17	6716.70	174.91	0.369	0.50 (0.47)	0.94	60239.4	12201.00
18	6079.24	184.65	0.360	0.50 (0.47)	0.94	61530.0	12111.00
19	5125.42	201.12	0.352	0.50 (0.47)	0.94	63452.9	12261.00
20	4642.19	210.88	0.346	0.50 (0.47)	0.94	64264.1	10200.00
21	4053.25	226.91	0.338	0.50 (0.47)	0.94	65502.0	10300.00

22 3812.74 234.06 0.334 0.50(0.47) 0.94 65854.2 12010.00
 23 3311.90 255.20 0.322 0.50(0.47) 0.94 66182.6 12000.00
 24 2248.51 325.68 0.284 0.50(0.47) 0.94 66853.4 10100.00
 TOTAL AREA(ACRES) = 66853.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 14859.52 Tc(MIN.) = 36.169
 EFFECTIVE AREA(ACRES) = 10425.86 AREA-AVERAGED Fm(INCH/HR) = 0.40
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 66853.4
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126420.58 FEET.

 FLOW PROCESS FROM NODE 13720.00 TO NODE 13740.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 165.51 DOWNSTREAM(FEET) = 161.03
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2067.54 CHANNEL SLOPE = 0.0022
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00

==>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL
 CAPACITY(NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM
 ALLOWABLE DEPTH).
 AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM
 ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

CHANNEL FLOW THRU SUBAREA(CFS) = 14859.52
 FLOW VELOCITY(FEET/SEC.) = 12.38 FLOW DEPTH(FEET) = 20.00
 TRAVEL TIME(MIN.) = 2.78 Tc(MIN.) = 38.95
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128488.12 FEET.

 FLOW PROCESS FROM NODE 13720.00 TO NODE 13740.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<

 FLOW PROCESS FROM NODE 13740.00 TO NODE 13740.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 0506103f.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	252.52	21.48	0.50(0.38)	0.76	404.4	10300.00
2	251.96	21.77	0.50(0.38)	0.76	408.5	10380.00
3	235.57	25.33	0.50(0.38)	0.76	442.2	10320.00
4	219.91	27.75	0.50(0.38)	0.76	453.9	10360.00
5	202.40	30.24	0.50(0.38)	0.76	460.8	10340.00
TOTAL AREA(ACRES) =						460.8

 FLOW PROCESS FROM NODE 13740.00 TO NODE 13740.00 IS CODE = 11

 >>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<
 =====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13960.82	19.73	1.116	0.50(0.40)	0.80	4017.0	400.00
2	14012.74	20.77	1.084	0.50(0.40)	0.80	4372.4	10230.00
3	14393.05	28.89	0.891	0.50(0.40)	0.80	7092.0	10250.00
4	14475.30	30.66	0.862	0.50(0.40)	0.80	7683.3	10200.00
5	14682.49	35.16	0.804	0.50(0.40)	0.80	9174.2	10220.00
6	14859.52	38.95	0.755	0.50(0.40)	0.80	10425.9	410.00
7	14214.66	48.68	0.671	0.50(0.41)	0.83	14607.7	130.00
8	13177.84	65.76	0.578	0.50(0.43)	0.86	20991.2	31100.00
9	12651.96	75.03	0.546	0.50(0.44)	0.87	24309.2	13600.00
10	12293.79	81.94	0.522	0.50(0.44)	0.88	26741.3	11801.00
11	11790.22	93.48	0.487	0.50(0.45)	0.89	30769.9	11500.00
12	11206.59	105.73	0.463	0.50(0.45)	0.91	35448.6	11000.00
13	10589.49	120.13	0.434	0.50(0.46)	0.92	42099.9	13000.00
14	9484.75	138.02	0.413	0.50(0.46)	0.93	49565.5	11130.00
15	8734.35	150.08	0.398	0.50(0.47)	0.93	53345.3	11620.00
16	7603.81	166.76	0.379	0.50(0.47)	0.94	57921.6	12400.00
17	6716.70	178.80	0.364	0.50(0.47)	0.94	60239.4	12201.00
18	6079.24	188.64	0.358	0.50(0.47)	0.94	61530.0	12111.00
19	5125.42	205.28	0.349	0.50(0.47)	0.94	63452.9	12261.00
20	4642.19	215.14	0.344	0.50(0.47)	0.94	64264.1	10200.00
21	4053.25	231.32	0.335	0.50(0.47)	0.94	65502.0	10300.00
22	3812.74	238.54	0.331	0.50(0.47)	0.94	65854.2	12010.00
23	3311.90	259.83	0.320	0.50(0.47)	0.94	66182.6	12000.00
24	2248.51	330.79	0.282	0.50(0.47)	0.94	66853.4	10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 =							128488.12 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	252.52	21.48	1.065	0.50(0.38)	0.76	404.4	10300.00
2	251.96	21.77	1.057	0.50(0.38)	0.76	408.5	10380.00
3	235.57	25.33	0.960	0.50(0.38)	0.76	442.2	10320.00
4	219.91	27.75	0.913	0.50(0.38)	0.76	453.9	10360.00
5	202.40	30.24	0.867	0.50(0.38)	0.76	460.8	10340.00
LONGEST FLOWPATH FROM NODE 10320.00 TO NODE 13740.00 =							8457.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14210.21	19.73	1.116	0.50(0.40)	0.80	4388.6	400.00
2	14264.00	20.77	1.084	0.50(0.40)	0.80	4763.5	10230.00
3	14298.32	21.48	1.065	0.50(0.40)	0.80	5013.2	10300.00
4	14311.18	21.77	1.057	0.50(0.40)	0.80	5113.2	10380.00
5	14462.03	25.33	0.960	0.50(0.40)	0.80	6342.9	10320.00
6	14559.66	27.75	0.913	0.50(0.40)	0.80	7164.7	10360.00
7	14604.95	28.89	0.891	0.50(0.40)	0.80	7549.0	10250.00
8	14658.15	30.24	0.867	0.50(0.40)	0.80	8003.6	10340.00
9	14675.45	30.66	0.862	0.50(0.40)	0.80	8144.1	10200.00
10	14858.59	35.16	0.804	0.50(0.40)	0.80	9635.0	10220.00
11	15015.36	38.95	0.755	0.50(0.40)	0.80	10886.7	410.00
12	14335.22	48.68	0.671	0.50(0.41)	0.82	15068.5	130.00

13	13259.65	65.76	0.578	0.50	(0.43)	0.86	21452.0	31100.00
14	12720.36	75.03	0.546	0.50	(0.44)	0.87	24770.0	13600.00
15	12352.20	81.94	0.522	0.50	(0.44)	0.88	27202.1	11801.00
16	11838.26	93.48	0.487	0.50	(0.45)	0.89	31230.7	11500.00
17	11252.21	105.73	0.463	0.50	(0.45)	0.90	35909.4	11000.00
18	10632.28	120.13	0.434	0.50	(0.46)	0.91	42560.7	13000.00
19	9525.45	138.02	0.413	0.50	(0.46)	0.93	50026.3	11130.00
20	8773.64	150.08	0.398	0.50	(0.47)	0.93	53806.1	11620.00
21	7641.16	166.76	0.379	0.50	(0.47)	0.94	58382.4	12400.00
22	6752.64	178.80	0.364	0.50	(0.47)	0.94	60700.2	12201.00
23	6114.59	188.64	0.358	0.50	(0.47)	0.94	61990.8	12111.00
24	5159.88	205.28	0.349	0.50	(0.47)	0.94	63913.7	12261.00
25	4676.13	215.14	0.344	0.50	(0.47)	0.94	64724.9	10200.00
26	4086.32	231.32	0.335	0.50	(0.47)	0.94	65962.8	10300.00
27	3845.43	238.54	0.331	0.50	(0.47)	0.94	66315.0	12010.00
28	3343.46	259.83	0.320	0.50	(0.47)	0.94	66643.4	12000.00
29	2276.30	330.79	0.282	0.50	(0.47)	0.94	67314.2	10100.00
TOTAL AREA (ACRES) =		67314.2						

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 15015.36 Tc (MIN.) = 38.952
EFFECTIVE AREA (ACRES) = 10886.66 AREA-AVERAGED Fm (INCH/HR) = 0.40
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.80
TOTAL AREA (ACRES) = 67314.2
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128488.12 FEET.

FLOW PROCESS FROM NODE 13740.00 TO NODE 13741.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<
=====

ELEVATION DATA: UPSTREAM (FEET) = 161.03 DOWNSTREAM (FEET) = 141.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 364.08 CHANNEL SLOPE = 0.0550
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00
CHANNEL FLOW THRU SUBAREA (CFS) = 15015.36
FLOW VELOCITY (FEET/SEC.) = 36.46 FLOW DEPTH (FEET) = 11.72
TRAVEL TIME (MIN.) = 0.17 Tc (MIN.) = 39.12
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128852.20 FEET.

FLOW PROCESS FROM NODE 13740.00 TO NODE 13741.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<
=====

FLOW PROCESS FROM NODE 13741.00 TO NODE 13741.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<
=====

PEAK FLOWRATE TABLE FILE NAME: 0506104f.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22.86	23.27	0.50 (0.40)	0.80	44.3	10400.00
TOTAL AREA (ACRES) =		44.3				

FLOW PROCESS FROM NODE 13741.00 TO NODE 13741.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<
=====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14210.21	19.90	1.110	0.50 (0.40)	0.80	4388.6	400.00
2	14264.00	20.94	1.080	0.50 (0.40)	0.80	4763.5	10230.00
3	14298.32	21.65	1.060	0.50 (0.40)	0.80	5013.2	10300.00
4	14311.18	21.93	1.052	0.50 (0.40)	0.80	5113.2	10380.00
5	14462.03	25.50	0.956	0.50 (0.40)	0.80	6342.9	10320.00
6	14559.66	27.92	0.910	0.50 (0.40)	0.80	7164.7	10360.00
7	14604.95	29.06	0.888	0.50 (0.40)	0.80	7549.0	10250.00
8	14658.15	30.41	0.865	0.50 (0.40)	0.80	8003.6	10340.00
9	14675.45	30.83	0.859	0.50 (0.40)	0.80	8144.1	10200.00
10	14858.59	35.33	0.802	0.50 (0.40)	0.80	9635.0	10220.00
11	15015.36	39.12	0.753	0.50 (0.40)	0.80	10886.7	410.00
12	14335.22	48.85	0.669	0.50 (0.41)	0.82	15068.5	130.00
13	13259.65	65.93	0.577	0.50 (0.43)	0.86	21452.0	31100.00
14	12720.36	75.21	0.545	0.50 (0.44)	0.87	24770.0	13600.00
15	12352.20	82.12	0.521	0.50 (0.44)	0.88	27202.1	11801.00
16	11838.26	93.66	0.487	0.50 (0.45)	0.89	31230.7	11500.00
17	11252.21	105.90	0.462	0.50 (0.45)	0.90	35909.4	11000.00
18	10632.28	120.31	0.434	0.50 (0.46)	0.91	42560.7	13000.00
19	9525.45	138.21	0.412	0.50 (0.46)	0.93	50026.3	11130.00
20	8773.64	150.27	0.398	0.50 (0.47)	0.93	53806.1	11620.00
21	7641.16	166.96	0.378	0.50 (0.47)	0.94	58382.4	12400.00
22	6752.64	179.01	0.364	0.50 (0.47)	0.94	60700.2	12201.00
23	6114.59	188.85	0.358	0.50 (0.47)	0.94	61990.8	12111.00
24	5159.88	205.49	0.349	0.50 (0.47)	0.94	63913.7	12261.00
25	4676.13	215.36	0.344	0.50 (0.47)	0.94	64724.9	10200.00
26	4086.32	231.55	0.335	0.50 (0.47)	0.94	65962.8	10300.00
27	3845.43	238.77	0.331	0.50 (0.47)	0.94	66315.0	12010.00
28	3343.46	260.07	0.320	0.50 (0.47)	0.94	66643.4	12000.00
29	2276.30	331.06	0.282	0.50 (0.47)	0.94	67314.2	10100.00
LONGEST FLOWPATH FROM NODE		10100.00	TO NODE		13741.00	= 128852.20 FEET.	

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22.86	23.27	1.014	0.50 (0.40)	0.80	44.3	10400.00
LONGEST FLOWPATH FROM NODE		10400.00	TO NODE		13741.00	= 6237.00 FEET.	

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14232.79	19.90	1.110	0.50 (0.40)	0.80	4426.4	400.00
2	14286.75	20.94	1.080	0.50 (0.40)	0.80	4803.3	10230.00
3	14321.16	21.65	1.060	0.50 (0.40)	0.80	5054.4	10300.00
4	14334.04	21.93	1.052	0.50 (0.40)	0.80	5155.0	10380.00
5	14390.73	23.27	1.014	0.50 (0.40)	0.80	5619.6	10400.00
6	14482.74	25.50	0.956	0.50 (0.40)	0.80	6387.2	10320.00
7	14578.64	27.92	0.910	0.50 (0.40)	0.80	7209.0	10360.00
8	14623.13	29.06	0.888	0.50 (0.40)	0.80	7593.3	10250.00

Stream Number	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
9	14675.46	30.41	0.865	0.50 (0.40)	0.80	8047.9	10340.00
10	14692.55	30.83	0.859	0.50 (0.40)	0.80	8188.4	10200.00
11	14873.56	35.33	0.802	0.50 (0.40)	0.80	9679.3	10220.00
12	15028.52	39.12	0.753	0.50 (0.40)	0.80	10931.0	410.00
13	14345.26	48.85	0.669	0.50 (0.41)	0.82	15112.8	130.00
14	13266.27	65.93	0.577	0.50 (0.43)	0.86	21496.3	31100.00
15	12725.79	75.21	0.545	0.50 (0.44)	0.87	24814.3	13600.00
16	12356.73	82.12	0.521	0.50 (0.44)	0.88	27246.4	11801.00
17	11841.91	93.66	0.487	0.50 (0.45)	0.89	31275.0	11500.00
18	11255.68	105.90	0.462	0.50 (0.45)	0.90	35953.7	11000.00
19	10635.53	120.31	0.434	0.50 (0.46)	0.91	42605.0	13000.00
20	9528.54	138.21	0.412	0.50 (0.46)	0.93	50070.6	11130.00
21	8776.63	150.27	0.398	0.50 (0.47)	0.93	53850.4	11620.00
22	7644.00	166.96	0.378	0.50 (0.47)	0.94	58426.7	12400.00
23	6755.37	179.01	0.364	0.50 (0.47)	0.94	60744.5	12201.00
24	6117.27	188.85	0.358	0.50 (0.47)	0.94	62035.1	12111.00
25	5162.50	205.49	0.349	0.50 (0.47)	0.94	63958.0	12261.00
26	4678.71	215.36	0.344	0.50 (0.47)	0.94	64769.2	10200.00
27	4088.84	231.55	0.335	0.50 (0.47)	0.94	66007.1	10300.00
28	3847.92	238.77	0.331	0.50 (0.47)	0.94	66359.3	12010.00
29	3345.86	260.07	0.320	0.50 (0.47)	0.94	66687.7	12000.00
30	2278.41	331.06	0.282	0.50 (0.47)	0.94	67358.5	10100.00

TOTAL AREA (ACRES) = 67358.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 15028.52 Tc (MIN.) = 39.118
EFFECTIVE AREA (ACRES) = 10930.96 AREA-AVERAGED Fm (INCH/HR) = 0.40
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.80
TOTAL AREA (ACRES) = 67358.5
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128852.20 FEET.

FLOW PROCESS FROM NODE 13741.00 TO NODE 13802.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM (FEET) = 141.00 DOWNSTREAM (FEET) = 135.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 1533.41 CHANNEL SLOPE = 0.0039
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00
CHANNEL FLOW THRU SUBAREA (CFS) = 15028.52
FLOW VELOCITY (FEET/SEC.) = 13.53 FLOW DEPTH (FEET) = 19.24
TRAVEL TIME (MIN.) = 1.89 Tc (MIN.) = 41.01
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130385.60 FEET.

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<

PEAK FLOWRATE TABLE FILE NAME: 0506105m.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

Stream Number	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	119.37	16.20	0.50 (0.45)	0.90	187.4	10520.00	
2	91.55	39.09	0.50 (0.46)	0.93	403.6	10500.00	

TOTAL AREA (ACRES) = 403.6

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<

** MAIN STREAM CONFLUENCE DATA **

Stream Number	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14232.79	21.82	1.055	0.50 (0.40)	0.80	4426.4	400.00
2	14286.75	22.85	1.026	0.50 (0.40)	0.80	4803.3	10230.00
3	14321.16	23.56	1.006	0.50 (0.40)	0.80	5054.4	10300.00
4	14334.04	23.84	0.998	0.50 (0.40)	0.80	5155.0	10380.00
5	14390.73	25.18	0.962	0.50 (0.40)	0.80	5619.6	10400.00
6	14482.74	27.41	0.920	0.50 (0.40)	0.80	6387.2	10320.00
7	14578.64	29.82	0.873	0.50 (0.40)	0.80	7209.0	10360.00
8	14623.13	30.96	0.858	0.50 (0.40)	0.80	7593.3	10250.00
9	14675.46	32.30	0.840	0.50 (0.40)	0.80	8047.9	10340.00
10	14692.55	32.73	0.835	0.50 (0.40)	0.80	8188.4	10200.00
11	14873.56	37.22	0.778	0.50 (0.40)	0.80	9679.3	10220.00
12	15028.52	41.01	0.734	0.50 (0.40)	0.80	10931.0	410.00
13	14345.26	50.76	0.655	0.50 (0.41)	0.82	15112.8	130.00
14	13266.27	67.88	0.571	0.50 (0.43)	0.86	21496.3	31100.00
15	12725.79	77.18	0.538	0.50 (0.44)	0.87	24814.3	13600.00
16	12356.73	84.10	0.514	0.50 (0.44)	0.88	27246.4	11801.00
17	11841.91	95.66	0.483	0.50 (0.45)	0.89	31275.0	11500.00
18	11255.68	107.93	0.458	0.50 (0.45)	0.90	35953.7	11000.00
19	10635.53	122.37	0.431	0.50 (0.46)	0.91	42605.0	13000.00
20	9528.54	140.33	0.410	0.50 (0.46)	0.93	50070.6	11130.00
21	8776.63	152.43	0.396	0.50 (0.47)	0.93	53850.4	11620.00
22	7644.00	169.19	0.376	0.50 (0.47)	0.94	58426.7	12400.00
23	6755.37	181.31	0.362	0.50 (0.47)	0.94	60744.5	12201.00
24	6117.27	191.21	0.357	0.50 (0.47)	0.94	62035.1	12111.00
25	5162.50	207.96	0.348	0.50 (0.47)	0.94	63958.0	12261.00
26	4678.71	217.89	0.343	0.50 (0.47)	0.94	64769.2	10200.00
27	4088.84	234.16	0.334	0.50 (0.47)	0.94	66007.1	10300.00
28	3847.92	241.42	0.330	0.50 (0.47)	0.94	66359.3	12010.00
29	3345.86	262.82	0.318	0.50 (0.47)	0.94	66687.7	12000.00
30	2278.41	334.09	0.280	0.50 (0.47)	0.94	67358.5	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130385.60 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

Stream Number	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	119.37	16.20	1.249	0.50 (0.45)	0.90	187.4	10520.00
2	91.55	39.09	0.754	0.50 (0.46)	0.93	403.6	10500.00

LONGEST FLOWPATH FROM NODE 10500.00 TO NODE 13802.00 = 12187.00 FEET.

** PEAK FLOW RATE TABLE **

Stream Number	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
---------------	---------	-----------	---------------------	-------------------	----	------------	----------------

Node	Q (CFS)	Tc (MIN.)	Fp (INCH/HR)	Ap (ACRES)	Ae (ACRES)	HEADWATER (FEET)
1	13805.83	16.20	1.249	0.50 (0.40)	0.80	3473.5
2	14345.33	21.82	1.055	0.50 (0.40)	0.80	4667.0
3	14398.03	22.85	1.026	0.50 (0.40)	0.80	5053.7
4	14431.58	23.56	1.006	0.50 (0.40)	0.80	5311.4
5	14444.11	23.84	0.998	0.50 (0.40)	0.80	5414.7
6	14499.17	25.18	0.962	0.50 (0.40)	0.80	5891.9
7	14588.49	27.41	0.920	0.50 (0.40)	0.80	6680.5
8	14681.45	29.82	0.873	0.50 (0.40)	0.80	7525.1
9	14724.56	30.96	0.858	0.50 (0.40)	0.80	7920.2
10	14775.25	32.30	0.840	0.50 (0.40)	0.80	8387.4
11	14791.83	32.73	0.835	0.50 (0.40)	0.80	8531.9
12	14967.38	37.22	0.778	0.50 (0.40)	0.80	10065.3
13	15041.43	39.09	0.754	0.50 (0.40)	0.80	10699.3
14	15113.78	41.01	0.734	0.50 (0.40)	0.80	11334.6
15	14405.76	50.76	0.655	0.50 (0.41)	0.83	15516.4
16	13300.06	67.88	0.571	0.50 (0.43)	0.86	21899.9
17	12749.41	77.18	0.538	0.50 (0.44)	0.87	25217.9
18	12372.78	84.10	0.514	0.50 (0.44)	0.88	27650.0
19	11853.05	95.66	0.483	0.50 (0.45)	0.89	31678.6
20	11266.25	107.93	0.458	0.50 (0.45)	0.90	36357.3
21	10645.48	122.37	0.431	0.50 (0.46)	0.91	43008.6
22	9538.00	140.33	0.410	0.50 (0.46)	0.93	50474.2
23	8785.76	152.43	0.396	0.50 (0.47)	0.93	54254.0
24	7652.67	169.19	0.376	0.50 (0.47)	0.94	58830.3
25	6763.73	181.31	0.362	0.50 (0.47)	0.94	61148.1
26	6125.51	191.21	0.357	0.50 (0.47)	0.94	62438.8
27	5170.53	207.96	0.348	0.50 (0.47)	0.94	64361.6
28	4686.62	217.89	0.343	0.50 (0.47)	0.94	65172.8
29	4096.54	234.16	0.334	0.50 (0.47)	0.94	66410.7
30	3855.53	241.42	0.330	0.50 (0.47)	0.94	66762.9
31	3353.21	262.82	0.318	0.50 (0.47)	0.94	67091.3
32	2284.87	334.09	0.280	0.50 (0.47)	0.94	67762.1

TOTAL AREA (ACRES) = 67762.1

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 15113.78 Tc (MIN.) = 41.006
EFFECTIVE AREA (ACRES) = 11334.56 AREA-AVERAGED Fm (INCH/HR) = 0.40
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.80
TOTAL AREA (ACRES) = 67762.1
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130385.60 FEET.

FLOW PROCESS FROM NODE 13802.00 TO NODE 13803.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 135.00 DOWNSTREAM (FEET) = 134.99
CHANNEL LENGTH THRU SUBAREA (FEET) = 207.23 CHANNEL SLOPE = 0.0000
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00

==>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL
CAPACITY (NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM
ALLOWABLE DEPTH).
AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM
ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

CHANNEL FLOW THRU SUBAREA (CFS) = 15113.78
FLOW VELOCITY (FEET/SEC.) = 12.59 FLOW DEPTH (FEET) = 20.00
TRAVEL TIME (MIN.) = 0.27 Tc (MIN.) = 41.28
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130592.83 FEET.

FLOW PROCESS FROM NODE 13802.00 TO NODE 13803.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 0506106f.DNA
MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (INCH/HR)	Ap (ACRES)	Ae (ACRES)	HEADWATER NODE
1	23.96	18.98	0.50 (0.34)	0.67	36.9	10600.00
TOTAL AREA (ACRES) =		36.9				

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (INCH/HR)	Ap (ACRES)	Ae (ACRES)	HEADWATER NODE
1	13805.83	16.50	1.238	0.50 (0.40)	0.80	3473.5	10520.00
2	14345.33	22.11	1.047	0.50 (0.40)	0.80	4667.0	400.00
3	14398.03	23.14	1.018	0.50 (0.40)	0.80	5053.7	10230.00
4	14431.58	23.85	0.998	0.50 (0.40)	0.80	5311.4	10300.00
5	14444.11	24.13	0.990	0.50 (0.40)	0.80	5414.7	10380.00
6	14499.17	25.47	0.957	0.50 (0.40)	0.80	5891.9	10400.00
7	14588.49	27.69	0.914	0.50 (0.40)	0.80	6680.5	10320.00
8	14681.45	30.10	0.869	0.50 (0.40)	0.80	7525.1	10360.00
9	14724.56	31.24	0.854	0.50 (0.40)	0.80	7920.2	10250.00
10	14775.25	32.59	0.837	0.50 (0.40)	0.80	8387.4	10340.00
11	14791.83	33.01	0.832	0.50 (0.40)	0.80	8531.9	10200.00
12	14967.38	37.50	0.774	0.50 (0.40)	0.80	10065.3	10220.00
13	15041.43	39.36	0.750	0.50 (0.40)	0.80	10699.3	10500.00
14	15113.78	41.28	0.731	0.50 (0.40)	0.80	11334.6	410.00
15	14405.76	51.04	0.654	0.50 (0.41)	0.83	15516.4	130.00
16	13300.06	68.19	0.570	0.50 (0.43)	0.86	21899.9	31100.00
17	12749.41	77.50	0.537	0.50 (0.44)	0.87	25217.9	13600.00
18	12372.78	84.43	0.513	0.50 (0.44)	0.88	27650.0	11801.00
19	11853.05	96.01	0.482	0.50 (0.45)	0.89	31678.6	11500.00
20	11266.25	108.30	0.457	0.50 (0.45)	0.90	36357.3	11000.00
21	10645.48	122.76	0.431	0.50 (0.46)	0.91	43008.6	13000.00
22	9538.00	140.76	0.409	0.50 (0.46)	0.93	50474.2	11130.00
23	8785.76	152.90	0.395	0.50 (0.47)	0.93	54254.0	11620.00
24	7652.67	169.74	0.375	0.50 (0.47)	0.94	58830.3	12400.00
25	6763.73	181.93	0.362	0.50 (0.47)	0.94	61148.1	12201.00
26	6125.51	191.89	0.357	0.50 (0.47)	0.94	62438.8	12111.00

27 5170.53 208.76 0.347 0.50(0.47) 0.94 64361.6 12261.00
 28 4686.62 218.78 0.342 0.50(0.47) 0.94 65172.8 10200.00
 29 4096.54 235.17 0.333 0.50(0.47) 0.94 66410.7 10300.00
 30 3855.53 242.50 0.329 0.50(0.47) 0.94 66762.9 12010.00
 31 3353.21 264.06 0.318 0.50(0.47) 0.94 67091.3 12000.00
 32 2284.87 335.90 0.279 0.50(0.47) 0.94 67762.1 10100.00
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130592.83 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23.96	18.98	1.144	0.50(0.34)	0.67	36.9	10600.00

LONGEST FLOWPATH FROM NODE 10600.00 TO NODE 13803.00 = 1713.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13829.06	16.50	1.238	0.50(0.40)	0.80	3505.5	10520.00
2	14069.04	18.98	1.144	0.50(0.40)	0.80	4039.7	10600.00
3	14366.41	22.11	1.047	0.50(0.40)	0.80	4703.9	400.00
4	14418.25	23.14	1.018	0.50(0.40)	0.80	5090.6	10230.00
5	14451.22	23.85	0.998	0.50(0.40)	0.80	5348.3	10300.00
6	14463.51	24.13	0.990	0.50(0.40)	0.80	5451.6	10380.00
7	14517.59	25.47	0.957	0.50(0.40)	0.80	5928.8	10400.00
8	14605.64	27.69	0.914	0.50(0.40)	0.80	6717.4	10320.00
9	14697.25	30.10	0.869	0.50(0.40)	0.80	7562.0	10360.00
10	14739.93	31.24	0.854	0.50(0.40)	0.80	7957.1	10250.00
11	14790.11	32.59	0.837	0.50(0.40)	0.80	8424.3	10340.00
12	14806.53	33.01	0.832	0.50(0.40)	0.80	8568.8	10200.00
13	14980.37	37.50	0.774	0.50(0.40)	0.80	10102.2	10220.00
14	15053.72	39.36	0.750	0.50(0.40)	0.80	10736.2	10500.00
15	15125.51	41.28	0.731	0.50(0.40)	0.80	11371.5	410.00
16	14415.18	51.04	0.654	0.50(0.41)	0.83	15553.3	130.00
17	13307.00	68.19	0.570	0.50(0.43)	0.86	21936.8	31100.00
18	12755.39	77.50	0.537	0.50(0.44)	0.87	25254.8	13600.00
19	12378.05	84.43	0.513	0.50(0.44)	0.88	27686.9	11801.00
20	11857.75	96.01	0.482	0.50(0.45)	0.89	31715.5	11500.00
21	11270.72	108.30	0.457	0.50(0.45)	0.90	36394.2	11000.00
22	10649.69	122.76	0.431	0.50(0.46)	0.91	43045.5	13000.00
23	9542.00	140.76	0.409	0.50(0.46)	0.93	50511.1	11130.00
24	8789.62	152.90	0.395	0.50(0.47)	0.93	54290.9	11620.00
25	7656.34	169.74	0.375	0.50(0.47)	0.94	58867.2	12400.00
26	6767.27	181.93	0.362	0.50(0.47)	0.94	61185.0	12201.00
27	6128.99	191.89	0.357	0.50(0.47)	0.94	62475.6	12111.00
28	5173.93	208.76	0.347	0.50(0.47)	0.94	64398.5	12261.00
29	4689.96	218.78	0.342	0.50(0.47)	0.94	65209.7	10200.00
30	4099.80	235.17	0.333	0.50(0.47)	0.94	66447.6	10300.00
31	3858.75	242.50	0.329	0.50(0.47)	0.94	66799.8	12010.00
32	3356.31	264.06	0.318	0.50(0.47)	0.94	67128.2	12000.00
33	2287.60	335.90	0.279	0.50(0.47)	0.94	67799.0	10100.00

TOTAL AREA (ACRES) = 67799.0

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 15125.51 Tc(MIN.) = 41.281
 EFFECTIVE AREA(ACRES) = 11371.46 AREA-AVERAGED Fm(INCH/HR) = 0.40
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 67799.0
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130592.83 FEET.

=====
 END OF STUDY SUMMARY:
 TOTAL AREA(ACRES) = 67799.0 TC(MIN.) = 41.28
 EFFECTIVE AREA(ACRES) = 11371.46 AREA-AVERAGED Fm(INCH/HR)= 0.40
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.804
 PEAK FLOW RATE(CFS) = 15125.51

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13829.06	16.50	1.238	0.50(0.40)	0.80	3505.5	10520.00
2	14069.04	18.98	1.144	0.50(0.40)	0.80	4039.7	10600.00
3	14366.41	22.11	1.047	0.50(0.40)	0.80	4703.9	400.00
4	14418.25	23.14	1.018	0.50(0.40)	0.80	5090.6	10230.00
5	14451.22	23.85	0.998	0.50(0.40)	0.80	5348.3	10300.00
6	14463.51	24.13	0.990	0.50(0.40)	0.80	5451.6	10380.00
7	14517.59	25.47	0.957	0.50(0.40)	0.80	5928.8	10400.00
8	14605.64	27.69	0.914	0.50(0.40)	0.80	6717.4	10320.00
9	14697.25	30.10	0.869	0.50(0.40)	0.80	7562.0	10360.00
10	14739.93	31.24	0.854	0.50(0.40)	0.80	7957.1	10250.00
11	14790.11	32.59	0.837	0.50(0.40)	0.80	8424.3	10340.00
12	14806.53	33.01	0.832	0.50(0.40)	0.80	8568.8	10200.00
13	14980.37	37.50	0.774	0.50(0.40)	0.80	10102.2	10220.00
14	15053.72	39.36	0.750	0.50(0.40)	0.80	10736.2	10500.00
15	15125.51	41.28	0.731	0.50(0.40)	0.80	11371.5	410.00
16	14415.18	51.04	0.654	0.50(0.41)	0.83	15553.3	130.00
17	13307.00	68.19	0.570	0.50(0.43)	0.86	21936.8	31100.00
18	12755.39	77.50	0.537	0.50(0.44)	0.87	25254.8	13600.00
19	12378.05	84.43	0.513	0.50(0.44)	0.88	27686.9	11801.00
20	11857.75	96.01	0.482	0.50(0.45)	0.89	31715.5	11500.00
21	11270.72	108.30	0.457	0.50(0.45)	0.90	36394.2	11000.00
22	10649.69	122.76	0.431	0.50(0.46)	0.91	43045.5	13000.00
23	9542.00	140.76	0.409	0.50(0.46)	0.93	50511.1	11130.00
24	8789.62	152.90	0.395	0.50(0.47)	0.93	54290.9	11620.00
25	7656.34	169.74	0.375	0.50(0.47)	0.94	58867.2	12400.00
26	6767.27	181.93	0.362	0.50(0.47)	0.94	61185.0	12201.00
27	6128.99	191.89	0.357	0.50(0.47)	0.94	62475.6	12111.00
28	5173.93	208.76	0.347	0.50(0.47)	0.94	64398.5	12261.00
29	4689.96	218.78	0.342	0.50(0.47)	0.94	65209.7	10200.00
30	4099.80	235.17	0.333	0.50(0.47)	0.94	66447.6	10300.00
31	3858.75	242.50	0.329	0.50(0.47)	0.94	66799.8	12010.00
32	3356.31	264.06	0.318	0.50(0.47)	0.94	67128.2	12000.00
33	2287.60	335.90	0.279	0.50(0.47)	0.94	67799.0	10100.00

=====
 END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2010 Advanced Engineering Software (aes)
Ver. 17.0 Release Date: 07/01/2010 License ID 1527

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 138 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 5-YR EV AUG 2023 ROKAMOTO *

FILE NAME: RU05EV38.DAT
TIME/DATE OF STUDY: 23:47 08/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 5.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 2.589
- 2) 10.00; 1.733
- 3) 15.00; 1.292
- 4) 20.00; 1.105
- 5) 25.00; 0.965
- 6) 30.00; 0.869
- 7) 40.00; 0.741
- 8) 50.00; 0.659
- 9) 60.00; 0.597
- 10) 90.00; 0.493
- 11) 120.00; 0.433
- 12) 180.00; 0.362
- 13) 360.00; 0.265
- 14) 1200.00; 0.115

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU05EV37.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14366.41	22.11	0.50 (0.40)	0.80	4703.9	400.00
2	14806.53	33.01	0.50 (0.40)	0.80	8568.8	10200.00
3	15125.51	41.28	0.50 (0.40)	0.80	11371.5	410.00
4	14415.18	51.04	0.50 (0.41)	0.83	15553.3	130.00
5	13307.00	68.19	0.50 (0.43)	0.86	21936.8	31100.00
6	12755.39	77.50	0.50 (0.44)	0.87	25254.8	13600.00
7	11857.75	96.01	0.50 (0.45)	0.89	31715.5	11500.00
8	11270.72	108.30	0.50 (0.45)	0.90	36394.2	11000.00
9	10649.69	122.76	0.50 (0.46)	0.91	43045.5	13000.00
10	9542.00	140.76	0.50 (0.46)	0.93	50511.1	11130.00
11	8789.62	152.90	0.50 (0.47)	0.93	54290.9	11620.00
12	7656.34	169.74	0.50 (0.47)	0.94	58867.2	12400.00
13	6767.27	181.93	0.50 (0.47)	0.94	61185.0	12201.00
14	6128.99	191.89	0.50 (0.47)	0.94	62475.6	12111.00
15	5173.93	208.76	0.50 (0.47)	0.94	64398.5	12261.00
16	4689.96	218.78	0.50 (0.47)	0.94	65209.7	10200.00
17	4099.80	235.17	0.50 (0.47)	0.94	66447.6	10300.00
18	3858.75	242.50	0.50 (0.47)	0.94	66799.8	12010.00
19	3356.31	264.06	0.50 (0.47)	0.94	67128.2	12000.00
20	2287.60	335.90	0.50 (0.47)	0.94	67799.0	10100.00
TOTAL AREA (ACRES) =						67799.0

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14366.41	22.11	0.50 (0.40)	0.80	4703.9	400.00
2	14806.53	33.01	0.50 (0.40)	0.80	8568.8	10200.00
3	15125.51	41.28	0.50 (0.40)	0.80	11371.5	410.00
4	14415.18	51.04	0.50 (0.41)	0.83	15553.3	130.00
5	13307.00	68.19	0.50 (0.43)	0.86	21936.8	31100.00
6	12755.39	77.50	0.50 (0.44)	0.87	25254.8	13600.00
7	11857.75	96.01	0.50 (0.45)	0.89	31715.5	11500.00
8	11270.72	108.30	0.50 (0.45)	0.90	36394.2	11000.00
9	10649.69	122.76	0.50 (0.46)	0.91	43045.5	13000.00
10	9542.00	140.76	0.50 (0.46)	0.93	50511.1	11130.00
11	8789.62	152.90	0.50 (0.47)	0.93	54290.9	11620.00
12	7656.34	169.74	0.50 (0.47)	0.94	58867.2	12400.00
13	6767.27	181.93	0.50 (0.47)	0.94	61185.0	12201.00

14 6128.99 191.89 0.50 (0.47) 0.94 62475.6 12111.00
 15 5173.93 208.76 0.50 (0.47) 0.94 64398.5 12261.00
 16 4689.96 218.78 0.50 (0.47) 0.94 65209.7 10200.00
 17 4099.80 235.17 0.50 (0.47) 0.94 66447.6 10300.00
 18 3858.75 242.50 0.50 (0.47) 0.94 66799.8 12010.00
 19 3356.31 264.06 0.50 (0.47) 0.94 67128.2 12000.00
 20 2287.60 335.90 0.50 (0.47) 0.94 67799.0 10100.00
 TOTAL AREA (ACRES) = 67799.0

FLOW PROCESS FROM NODE 13803.00 TO NODE 13820.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 134.99 DOWNSTREAM(FEET) = 134.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 926.91 CHANNEL SLOPE = 0.0011
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00

==>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL
 CAPACITY(NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM
 ALLOWABLE DEPTH).
 AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM
 ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.720

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	31.44	0.50	0.983	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.983
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 15128.75
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.61
 AVERAGE FLOW DEPTH(FEET) = 20.00 TRAVEL TIME(MIN.) = 1.23
 Tc(MIN.) = 42.51
 SUBAREA AREA(ACRES) = 31.44 SUBAREA RUNOFF(CFS) = 6.47
 EFFECTIVE AREA(ACRES) = 11402.90 AREA-AVERAGED Fm(INCH/HR) = 0.40
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 67830.4 PEAK FLOW RATE(CFS) = 15125.51
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

==>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL
 CAPACITY(NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM
 ALLOWABLE DEPTH).
 AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM
 ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 20.00 FLOW VELOCITY(FEET/SEC.) = 12.60

==>FLOWDEPTH EXCEEDS MAXIMUM ALLOWABLE DEPTH

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13820.00 = 131519.73 FEET.

FLOW PROCESS FROM NODE 13803.00 TO NODE 13820.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
 TIME OF CONCENTRATION(MIN.) = 42.51
 RAINFALL INTENSITY(INCH/HR) = 0.72
 AREA-AVERAGED Fm(INCH/HR) = 0.40
 AREA-AVERAGED Fp(INCH/HR) = 0.50
 AREA-AVERAGED Ap = 0.80
 EFFECTIVE STREAM AREA(ACRES) = 11402.90
 TOTAL STREAM AREA(ACRES) = 67830.41
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 15125.51

FLOW PROCESS FROM NODE 13810.00 TO NODE 13811.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH(FEET) = 648.54
 ELEVATION DATA: UPSTREAM(FEET) = 756.46 DOWNSTREAM(FEET) = 586.02

Tc = K * [(LENGTH** 3.00) / (ELEVATION CHANGE)] ** 0.20
 SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 12.293
 * 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.531
 SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL, BROADLEAF"	-	5.58	0.50	1.000	65	12.29

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA RUNOFF(CFS) = 5.18
 TOTAL AREA(ACRES) = 5.58 PEAK FLOW RATE(CFS) = 5.18

FLOW PROCESS FROM NODE 13811.00 TO NODE 13811.50 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 586.02 DOWNSTREAM(FEET) = 437.69
 CHANNEL LENGTH THRU SUBAREA(FEET) = 696.28 CHANNEL SLOPE = 0.2130
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
 * 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.358
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	14.79	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 10.91
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.93
 AVERAGE FLOW DEPTH(FEET) = 0.78 TRAVEL TIME(MIN.) = 1.96
 Tc(MIN.) = 14.25

SUBAREA AREA (ACRES) = 14.79 SUBAREA RUNOFF (CFS) = 11.42
EFFECTIVE AREA (ACRES) = 20.37 AREA-AVERAGED Fm (INCH/HR) = 0.50
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 20.4 PEAK FLOW RATE (CFS) = 15.73

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 0.90 FLOW VELOCITY (FEET/SEC.) = 6.51
LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13811.50 = 1344.82 FEET.

FLOW PROCESS FROM NODE 13811.50 TO NODE 13812.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 437.69 DOWNSTREAM (FEET) = 402.36
CHANNEL LENGTH THRU SUBAREA (FEET) = 681.04 CHANNEL SLOPE = 0.0519
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.217

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	18.41	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 21.68

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.13

AVERAGE FLOW DEPTH (FEET) = 1.32 TRAVEL TIME (MIN.) = 2.75

Tc (MIN.) = 17.00

SUBAREA AREA (ACRES) = 18.41 SUBAREA RUNOFF (CFS) = 11.88

EFFECTIVE AREA (ACRES) = 38.78 AREA-AVERAGED Fm (INCH/HR) = 0.50

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00

TOTAL AREA (ACRES) = 38.8 PEAK FLOW RATE (CFS) = 25.03

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 1.39 FLOW VELOCITY (FEET/SEC.) = 4.30
LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13812.00 = 2025.86 FEET.

FLOW PROCESS FROM NODE 13812.00 TO NODE 13813.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 402.36 DOWNSTREAM (FEET) = 259.72
CHANNEL LENGTH THRU SUBAREA (FEET) = 1282.56 CHANNEL SLOPE = 0.1112
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.091

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	27.87	0.50	0.858	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.858

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 33.34

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.12

AVERAGE FLOW DEPTH (FEET) = 1.35 TRAVEL TIME (MIN.) = 3.49

Tc (MIN.) = 20.49

SUBAREA AREA (ACRES) = 27.87 SUBAREA RUNOFF (CFS) = 16.61

EFFECTIVE AREA (ACRES) = 66.65 AREA-AVERAGED Fm (INCH/HR) = 0.47

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.94

TOTAL AREA (ACRES) = 66.7 PEAK FLOW RATE (CFS) = 37.24

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 1.41 FLOW VELOCITY (FEET/SEC.) = 6.27
LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13813.00 = 3308.42 FEET.

FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<

>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 259.72 DOWNSTREAM (FEET) = 137.00

FLOW LENGTH (FEET) = 2412.88 MANNING'S N = 0.013

ESTIMATED PIPE DIAMETER (INCH) INCREASED TO 36.000

DEPTH OF FLOW IN 36.0 INCH PIPE IS 12.6 INCHES

PIPE-FLOW VELOCITY (FEET/SEC.) = 16.98

ESTIMATED PIPE DIAMETER (INCH) = 36.00 NUMBER OF PIPES = 1

PIPE-FLOW (CFS) = 37.24

PIPE TRAVEL TIME (MIN.) = 2.37 Tc (MIN.) = 22.86

LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13820.00 = 5721.30 FEET.

FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 22.86

* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.025

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	83.64	0.50	0.570	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.570

SUBAREA AREA (ACRES) = 83.64 SUBAREA RUNOFF (CFS) = 55.70

EFFECTIVE AREA (ACRES) = 150.29 AREA-AVERAGED Fm (INCH/HR) = 0.37

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.73

TOTAL AREA (ACRES) = 150.3 PEAK FLOW RATE (CFS) = 88.96

FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

TOTAL NUMBER OF STREAMS = 2

CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:

TIME OF CONCENTRATION (MIN.) = 22.86

RAINFALL INTENSITY (INCH/HR) = 1.03

AREA-AVERAGED Fm (INCH/HR) = 0.37

AREA-AVERAGED Fp (INCH/HR) = 0.50

AREA-AVERAGED Ap = 0.73

EFFECTIVE STREAM AREA(ACRES) = 150.29
 TOTAL STREAM AREA(ACRES) = 150.29
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 88.96

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14366.41	23.40	1.010	0.50(0.40)	0.80	4735.3	400.00
1	14806.53	34.26	0.815	0.50(0.40)	0.80	8600.3	10200.00
1	15125.51	42.51	0.720	0.50(0.40)	0.80	11402.9	410.00
1	14415.18	52.33	0.645	0.50(0.41)	0.83	15584.7	130.00
1	13307.00	69.59	0.564	0.50(0.43)	0.86	21968.2	31100.00
1	12755.39	78.95	0.531	0.50(0.44)	0.87	25286.2	13600.00
1	11857.75	97.58	0.478	0.50(0.45)	0.89	31746.9	11500.00
1	11270.72	109.95	0.453	0.50(0.45)	0.90	36425.6	11000.00
1	10649.69	124.50	0.428	0.50(0.46)	0.91	43076.9	13000.00
1	9542.00	142.70	0.406	0.50(0.46)	0.93	50542.5	11130.00
1	8789.62	155.01	0.392	0.50(0.47)	0.93	54322.3	11620.00
1	7656.34	171.94	0.372	0.50(0.47)	0.94	58898.6	12400.00
1	6767.27	184.19	0.360	0.50(0.47)	0.94	61216.5	12201.00
1	6128.99	194.21	0.354	0.50(0.47)	0.94	62507.1	12111.00
1	5173.93	211.19	0.345	0.50(0.47)	0.94	64430.0	12261.00
1	4689.96	221.26	0.340	0.50(0.47)	0.94	65241.1	10200.00
1	4099.80	237.74	0.331	0.50(0.47)	0.94	66479.0	10300.00
1	3858.75	245.11	0.327	0.50(0.47)	0.94	66831.2	12010.00
1	3356.31	266.76	0.315	0.50(0.47)	0.94	67159.6	12000.00
1	2287.60	338.88	0.276	0.50(0.47)	0.94	67830.4	10100.00
2	88.96	22.86	1.025	0.50(0.37)	0.73	150.3	13810.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14455.37	22.86	1.025	0.50(0.40)	0.80	4776.6	13810.00
2	14453.33	23.40	1.010	0.50(0.40)	0.80	4885.6	400.00
3	14867.02	34.26	0.815	0.50(0.40)	0.80	8750.6	10200.00
4	15173.28	42.51	0.720	0.50(0.40)	0.80	11553.2	410.00
5	14452.68	52.33	0.645	0.50(0.41)	0.83	15735.0	130.00
6	13333.57	69.59	0.564	0.50(0.43)	0.86	22118.5	31100.00
7	12777.57	78.95	0.531	0.50(0.44)	0.87	25436.5	13600.00
8	11874.92	97.58	0.478	0.50(0.45)	0.89	31897.2	11500.00
9	11287.00	109.95	0.453	0.50(0.45)	0.90	36575.9	11000.00
10	10665.06	124.50	0.428	0.50(0.46)	0.91	43227.2	13000.00
11	9556.60	142.70	0.406	0.50(0.46)	0.93	50692.8	11130.00
12	8803.69	155.01	0.392	0.50(0.47)	0.93	54472.6	11620.00
13	7669.69	171.94	0.372	0.50(0.47)	0.93	59048.9	12400.00
14	6780.19	184.19	0.360	0.50(0.47)	0.94	61366.7	12201.00
15	6141.73	194.21	0.354	0.50(0.47)	0.94	62657.4	12111.00
16	5186.33	211.19	0.345	0.50(0.47)	0.94	64580.3	12261.00
17	4702.17	221.26	0.340	0.50(0.47)	0.94	65391.4	10200.00
18	4111.69	237.74	0.331	0.50(0.47)	0.94	66629.3	10300.00
19	3870.49	245.11	0.327	0.50(0.47)	0.94	66981.5	12010.00
20	3367.64	266.76	0.315	0.50(0.47)	0.94	67309.9	12000.00
21	2297.53	338.88	0.276	0.50(0.47)	0.94	67980.7	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 15173.28 Tc(MIN.) = 42.51
 EFFECTIVE AREA(ACRES) = 11553.19 AREA-AVERAGED Fm(INCH/HR) = 0.40
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 67980.7
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13820.00 = 131519.73 FEET.

FLOW PROCESS FROM NODE 13820.00 TO NODE 13840.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 137.00 DOWNSTREAM(FEET) = 133.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1261.34 CHANNEL SLOPE = 0.0032
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00

==>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL
 CAPACITY(NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM
 ALLOWABLE DEPTH).
 AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM
 ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.707

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	31.60	0.50	0.683	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.683

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 15178.47

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.65

AVERAGE FLOW DEPTH(FEET) = 20.00 TRAVEL TIME(MIN.) = 1.66

Tc(MIN.) = 44.17

SUBAREA AREA(ACRES) = 31.60 SUBAREA RUNOFF(CFS) = 10.39

EFFECTIVE AREA(ACRES) = 11584.79 AREA-AVERAGED Fm(INCH/HR) = 0.40

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.80

TOTAL AREA(ACRES) = 68012.3 PEAK FLOW RATE(CFS) = 15173.28

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

==>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL
 CAPACITY(NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM
 ALLOWABLE DEPTH).
 AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM
 ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 20.00 FLOW VELOCITY(FEET/SEC.) = 12.64

==>FLOWDEPTH EXCEEDS MAXIMUM ALLOWABLE DEPTH

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13840.00 = 132781.08 FEET.

FLOW PROCESS FROM NODE 13820.00 TO NODE 13840.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION(MIN.) = 44.17
RAINFALL INTENSITY(INCH/HR) = 0.71
AREA-AVERAGED Fm(INCH/HR) = 0.40
AREA-AVERAGED Fp(INCH/HR) = 0.50
AREA-AVERAGED Ap = 0.80
EFFECTIVE STREAM AREA(ACRES) = 11584.79
TOTAL STREAM AREA(ACRES) = 68012.30
PEAK FLOW RATE(CFS) AT CONFLUENCE = 15173.28

FLOW PROCESS FROM NODE 13830.00 TO NODE 13831.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 744.71
ELEVATION DATA: UPSTREAM(FEET) = 1100.95 DOWNSTREAM(FEET) = 959.21

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 13.858
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.393
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	-	5.06	0.50	1.000	65	13.86

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 4.06
TOTAL AREA(ACRES) = 5.06 PEAK FLOW RATE(CFS) = 4.06

FLOW PROCESS FROM NODE 13831.00 TO NODE 13832.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 959.21 DOWNSTREAM(FEET) = 832.83
CHANNEL LENGTH THRU SUBAREA(FEET) = 1076.71 CHANNEL SLOPE = 0.1174
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.202
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	32.57	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 14.43
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.07
AVERAGE FLOW DEPTH(FEET) = 0.97 TRAVEL TIME(MIN.) = 3.54
Tc(MIN.) = 17.39
SUBAREA AREA(ACRES) = 32.57 SUBAREA RUNOFF(CFS) = 20.58
EFFECTIVE AREA(ACRES) = 37.63 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 37.6 PEAK FLOW RATE(CFS) = 23.78

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.17 FLOW VELOCITY(FEET/SEC.) = 5.77
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13832.00 = 1821.42 FEET.

FLOW PROCESS FROM NODE 13832.00 TO NODE 13833.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 832.83 DOWNSTREAM(FEET) = 572.49
CHANNEL LENGTH THRU SUBAREA(FEET) = 1883.58 CHANNEL SLOPE = 0.1382
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.044
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	32.23	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 31.70
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.56
AVERAGE FLOW DEPTH(FEET) = 1.27 TRAVEL TIME(MIN.) = 4.79
Tc(MIN.) = 22.18
SUBAREA AREA(ACRES) = 32.23 SUBAREA RUNOFF(CFS) = 15.77
EFFECTIVE AREA(ACRES) = 69.86 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 69.9 PEAK FLOW RATE(CFS) = 34.19

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.31 FLOW VELOCITY(FEET/SEC.) = 6.67
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13833.00 = 3705.00 FEET.

FLOW PROCESS FROM NODE 13833.00 TO NODE 13834.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 572.49 DOWNSTREAM(FEET) = 471.65
CHANNEL LENGTH THRU SUBAREA(FEET) = 943.78 CHANNEL SLOPE = 0.1068
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.974
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	27.51	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 40.06
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.31
AVERAGE FLOW DEPTH(FEET) = 1.45 TRAVEL TIME(MIN.) = 2.49
Tc(MIN.) = 24.67
SUBAREA AREA(ACRES) = 27.51 SUBAREA RUNOFF(CFS) = 11.73

EFFECTIVE AREA(ACRES) = 97.37 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 97.4 PEAK FLOW RATE(CFS) = 41.54

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.48 FLOW VELOCITY(FEET/SEC.) = 6.36
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13834.00 = 4648.78 FEET.

FLOW PROCESS FROM NODE 13834.00 TO NODE 13835.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 471.65 DOWNSTREAM(FEET) = 347.06
CHANNEL LENGTH THRU SUBAREA(FEET) = 1647.45 CHANNEL SLOPE = 0.0756
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.885

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	94.21	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 57.90

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.09

AVERAGE FLOW DEPTH(FEET) = 1.78 TRAVEL TIME(MIN.) = 4.51

Tc(MIN.) = 29.18

SUBAREA AREA(ACRES) = 94.21 SUBAREA RUNOFF(CFS) = 32.60

EFFECTIVE AREA(ACRES) = 191.58 AREA-AVERAGED Fm(INCH/HR) = 0.50

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 191.6 PEAK FLOW RATE(CFS) = 66.29

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.87 FLOW VELOCITY(FEET/SEC.) = 6.29
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13835.00 = 6296.23 FEET.

FLOW PROCESS FROM NODE 13835.00 TO NODE 13836.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 347.06 DOWNSTREAM(FEET) = 269.29
CHANNEL LENGTH THRU SUBAREA(FEET) = 1696.71 CHANNEL SLOPE = 0.0458
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.817

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	233.25	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 99.64

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.77

AVERAGE FLOW DEPTH(FEET) = 2.40 TRAVEL TIME(MIN.) = 4.90

Tc(MIN.) = 34.08
SUBAREA AREA(ACRES) = 233.25 SUBAREA RUNOFF(CFS) = 66.45
EFFECTIVE AREA(ACRES) = 424.83 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 424.8 PEAK FLOW RATE(CFS) = 121.04

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.58 FLOW VELOCITY(FEET/SEC.) = 6.05
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13836.00 = 7992.94 FEET.

FLOW PROCESS FROM NODE 13836.00 TO NODE 13837.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 269.29 DOWNSTREAM(FEET) = 191.87
CHANNEL LENGTH THRU SUBAREA(FEET) = 2529.21 CHANNEL SLOPE = 0.0306
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.725

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	134.70	0.50	0.880	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.880

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 138.34

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.39

AVERAGE FLOW DEPTH(FEET) = 2.92 TRAVEL TIME(MIN.) = 7.82

Tc(MIN.) = 41.90

SUBAREA AREA(ACRES) = 134.70 SUBAREA RUNOFF(CFS) = 34.58

EFFECTIVE AREA(ACRES) = 559.53 AREA-AVERAGED Fm(INCH/HR) = 0.49

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.97

TOTAL AREA(ACRES) = 559.5 PEAK FLOW RATE(CFS) = 121.04

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.78 FLOW VELOCITY(FEET/SEC.) = 5.21
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13837.00 = 10522.15 FEET.

FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<

>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 191.87 DOWNSTREAM(FEET) = 133.00
FLOW LENGTH(FEET) = 1151.02 MANNING'S N = 0.013
DEPTH OF FLOW IN 36.0 INCH PIPE IS 25.4 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 22.71
ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 121.04
PIPE TRAVEL TIME(MIN.) = 0.84 Tc(MIN.) = 42.75
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13840.00 = 11673.17 FEET.

FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 81

=====
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====

MAINLINE Tc(MIN.) = 42.75
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.718
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 5.97 0.50 0.622 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.622
SUBAREA AREA(ACRES) = 5.97 SUBAREA RUNOFF(CFS) = 2.19
EFFECTIVE AREA(ACRES) = 565.50 AREA-AVERAGED Fm(INCH/HR) = 0.48
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 565.5 PEAK FLOW RATE(CFS) = 121.04
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 1
=====

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<
=====

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 42.75
RAINFALL INTENSITY(INCH/HR) = 0.72
AREA-AVERAGED Fm(INCH/HR) = 0.48
AREA-AVERAGED Fp(INCH/HR) = 0.50
AREA-AVERAGED Ap = 0.97
EFFECTIVE STREAM AREA(ACRES) = 565.50
TOTAL STREAM AREA(ACRES) = 565.50
PEAK FLOW RATE(CFS) AT CONFLUENCE = 121.04

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14455.37	24.55	0.977	0.50(0.40)	0.80	4808.2	13810.00
1	14453.33	25.09	0.963	0.50(0.40)	0.80	4917.2	400.00
1	14867.02	35.94	0.793	0.50(0.40)	0.80	8782.2	10200.00
1	15173.28	44.17	0.707	0.50(0.40)	0.80	11584.8	410.00
1	14452.68	54.03	0.634	0.50(0.41)	0.83	15766.6	130.00
1	13333.57	71.32	0.558	0.50(0.43)	0.86	22150.1	31100.00
1	12777.57	80.70	0.525	0.50(0.44)	0.87	25468.1	13600.00
1	11874.92	99.36	0.474	0.50(0.45)	0.89	31928.8	11500.00
1	11287.00	111.75	0.449	0.50(0.45)	0.90	36607.5	11000.00
1	10665.06	126.33	0.426	0.50(0.46)	0.91	43258.8	13000.00
1	9556.60	144.59	0.404	0.50(0.46)	0.93	50724.4	11130.00
1	8803.69	156.93	0.389	0.50(0.47)	0.93	54504.2	11620.00
1	7669.69	173.92	0.369	0.50(0.47)	0.93	59080.5	12400.00
1	6780.19	186.24	0.359	0.50(0.47)	0.94	61398.3	12201.00
1	6141.73	196.32	0.353	0.50(0.47)	0.94	62689.0	12111.00
1	5186.33	213.38	0.344	0.50(0.47)	0.94	64611.9	12261.00
1	4702.17	223.51	0.339	0.50(0.47)	0.94	65423.0	10200.00
1	4111.69	240.07	0.330	0.50(0.47)	0.94	66660.9	10300.00
1	3870.49	247.47	0.326	0.50(0.47)	0.94	67013.1	12010.00
1	3367.64	269.21	0.314	0.50(0.47)	0.94	67341.5	12000.00
1	2297.53	341.56	0.275	0.50(0.47)	0.94	68012.3	10100.00

2 121.04 42.75 0.718 0.50(0.48) 0.97 565.5 13830.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14576.41	24.55	0.977	0.50(0.41)	0.81	5133.1	13810.00
2	14574.37	25.09	0.963	0.50(0.41)	0.81	5249.1	400.00
3	14988.06	35.94	0.793	0.50(0.41)	0.81	9257.7	10200.00
4	15241.37	42.75	0.718	0.50(0.41)	0.81	11665.8	13830.00
5	15288.30	44.17	0.707	0.50(0.41)	0.81	12150.3	410.00
6	14530.14	54.03	0.634	0.50(0.42)	0.83	16332.1	130.00
7	13371.67	71.32	0.558	0.50(0.43)	0.86	22715.6	31100.00
8	12798.89	80.70	0.525	0.50(0.44)	0.87	26033.6	13600.00
9	11882.89	99.36	0.474	0.50(0.45)	0.89	32494.3	11500.00
10	11294.55	111.75	0.449	0.50(0.45)	0.90	37173.0	11000.00
11	10672.21	126.33	0.426	0.50(0.46)	0.91	43824.3	13000.00
12	9563.38	144.59	0.404	0.50(0.46)	0.93	51289.9	11130.00
13	8810.23	156.93	0.389	0.50(0.47)	0.93	55069.7	11620.00
14	7675.89	173.92	0.369	0.50(0.47)	0.93	59646.0	12400.00
15	6786.22	186.24	0.359	0.50(0.47)	0.94	61963.8	12201.00
16	6147.66	196.32	0.353	0.50(0.47)	0.94	63254.5	12111.00
17	5192.11	213.38	0.344	0.50(0.47)	0.94	65177.4	12261.00
18	4707.86	223.51	0.339	0.50(0.47)	0.94	65988.5	10200.00
19	4117.23	240.07	0.330	0.50(0.47)	0.94	67226.4	10300.00
20	3875.97	247.47	0.326	0.50(0.47)	0.94	67578.6	12010.00
21	3372.92	269.21	0.314	0.50(0.47)	0.94	67907.0	12000.00
22	2302.15	341.56	0.275	0.50(0.47)	0.94	68577.8	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 15288.30 Tc(MIN.) = 44.17
EFFECTIVE AREA(ACRES) = 12150.29 AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.81
TOTAL AREA(ACRES) = 68577.8
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13840.00 = 132781.08 FEET.

FLOW PROCESS FROM NODE 13840.00 TO NODE 13860.00 IS CODE = 51
=====

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====

ELEVATION DATA: UPSTREAM(FEET) = 133.00 DOWNSTREAM(FEET) = 130.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 654.44 CHANNEL SLOPE = 0.0046
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.701
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 6.61 0.50 0.975 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.975
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 15288.93
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 14.43
AVERAGE FLOW DEPTH(FEET) = 18.80 TRAVEL TIME(MIN.) = 0.76

Tc(MIN.) = 44.92
SUBAREA AREA(ACRES) = 6.61 SUBAREA RUNOFF(CFS) = 1.27
EFFECTIVE AREA(ACRES) = 12156.90 AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.81
TOTAL AREA(ACRES) = 68584.4 PEAK FLOW RATE(CFS) = 15288.30
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 18.80 FLOW VELOCITY(FEET/SEC.) = 14.42
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13860.00 = 133435.52 FEET.

FLOW PROCESS FROM NODE 13840.00 TO NODE 13860.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

=====

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION(MIN.) = 44.92
RAINFALL INTENSITY(INCH/HR) = 0.70
AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50
AREA-AVERAGED Ap = 0.81
EFFECTIVE STREAM AREA(ACRES) = 12156.90
TOTAL STREAM AREA(ACRES) = 68584.41
PEAK FLOW RATE(CFS) AT CONFLUENCE = 15288.30

FLOW PROCESS FROM NODE 13850.00 TO NODE 13851.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 617.57
ELEVATION DATA: UPSTREAM(FEET) = 646.95 DOWNSTREAM(FEET) = 490.10

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 12.137
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.544

SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER						
"CHAPARRAL,BROADLEAF"	-	4.95	0.50	1.000	65	12.14

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 4.65
TOTAL AREA(ACRES) = 4.95 PEAK FLOW RATE(CFS) = 4.65

FLOW PROCESS FROM NODE 13851.00 TO NODE 13851.50 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 490.10 DOWNSTREAM(FEET) = 440.98
CHANNEL LENGTH THRU SUBAREA(FEET) = 351.14 CHANNEL SLOPE = 0.1399
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.428

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	4.02	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 6.33
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.42
AVERAGE FLOW DEPTH(FEET) = 0.69 TRAVEL TIME(MIN.) = 1.33
Tc(MIN.) = 13.46
SUBAREA AREA(ACRES) = 4.02 SUBAREA RUNOFF(CFS) = 3.36
EFFECTIVE AREA(ACRES) = 8.97 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 9.0 PEAK FLOW RATE(CFS) = 7.49

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.74 FLOW VELOCITY(FEET/SEC.) = 4.59
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13851.50 = 968.71 FEET.

FLOW PROCESS FROM NODE 13851.50 TO NODE 13852.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 440.98 DOWNSTREAM(FEET) = 395.76
CHANNEL LENGTH THRU SUBAREA(FEET) = 512.91 CHANNEL SLOPE = 0.0882
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.272

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.17	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 9.98
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.15
AVERAGE FLOW DEPTH(FEET) = 0.90 TRAVEL TIME(MIN.) = 2.06
Tc(MIN.) = 15.52
SUBAREA AREA(ACRES) = 7.17 SUBAREA RUNOFF(CFS) = 4.98
EFFECTIVE AREA(ACRES) = 16.14 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 16.1 PEAK FLOW RATE(CFS) = 11.22

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.94 FLOW VELOCITY(FEET/SEC.) = 4.27
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13852.00 = 1481.62 FEET.

FLOW PROCESS FROM NODE 13852.00 TO NODE 13853.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 395.76 DOWNSTREAM(FEET) = 354.94

CHANNEL LENGTH THRU SUBAREA (FEET) = 443.69 CHANNEL SLOPE = 0.0920
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.212
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	6.76	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 13.38
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.56
 AVERAGE FLOW DEPTH (FEET) = 0.99 TRAVEL TIME (MIN.) = 1.62
 Tc (MIN.) = 17.14
 SUBAREA AREA (ACRES) = 6.76 SUBAREA RUNOFF (CFS) = 4.33
 EFFECTIVE AREA (ACRES) = 22.90 AREA-AVERAGED Fm (INCH/HR) = 0.50
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 22.9 PEAK FLOW RATE (CFS) = 14.67

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 1.03 FLOW VELOCITY (FEET/SEC.) = 4.65
 LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13853.00 = 1925.31 FEET.

FLOW PROCESS FROM NODE 13853.00 TO NODE 13854.00 IS CODE = 51

 >>>> COMPUTE TRAPEZOIDAL CHANNEL FLOW <<<<<
 >>>> TRAVELTIME THRU SUBAREA (EXISTING ELEMENT) <<<<<

 ELEVATION DATA: UPSTREAM (FEET) = 354.94 DOWNSTREAM (FEET) = 263.57
 CHANNEL LENGTH THRU SUBAREA (FEET) = 962.09 CHANNEL SLOPE = 0.0950
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.096
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	18.16	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 19.54
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.07
 AVERAGE FLOW DEPTH (FEET) = 1.13 TRAVEL TIME (MIN.) = 3.16
 Tc (MIN.) = 20.31
 SUBAREA AREA (ACRES) = 18.16 SUBAREA RUNOFF (CFS) = 9.74
 EFFECTIVE AREA (ACRES) = 41.06 AREA-AVERAGED Fm (INCH/HR) = 0.50
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 41.1 PEAK FLOW RATE (CFS) = 22.03

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 1.19 FLOW VELOCITY (FEET/SEC.) = 5.21
 LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13854.00 = 2887.40 FEET.

FLOW PROCESS FROM NODE 13854.00 TO NODE 13855.00 IS CODE = 51

 >>>> COMPUTE TRAPEZOIDAL CHANNEL FLOW <<<<<
 >>>> TRAVELTIME THRU SUBAREA (EXISTING ELEMENT) <<<<<

 ELEVATION DATA: UPSTREAM (FEET) = 263.57 DOWNSTREAM (FEET) = 188.74
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1228.77 CHANNEL SLOPE = 0.0609
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.977
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	38.75	0.50	0.879	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.879
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 31.42
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.81
 AVERAGE FLOW DEPTH (FEET) = 1.48 TRAVEL TIME (MIN.) = 4.26
 Tc (MIN.) = 24.57
 SUBAREA AREA (ACRES) = 38.75 SUBAREA RUNOFF (CFS) = 18.75
 EFFECTIVE AREA (ACRES) = 79.81 AREA-AVERAGED Fm (INCH/HR) = 0.47
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.94
 TOTAL AREA (ACRES) = 79.8 PEAK FLOW RATE (CFS) = 36.37

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 1.56 FLOW VELOCITY (FEET/SEC.) = 4.99
 LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13855.00 = 4116.17 FEET.

FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 31

 >>>> COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA <<<<<
 >>>> USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW) <<<<<

 ELEVATION DATA: UPSTREAM (FEET) = 188.74 DOWNSTREAM (FEET) = 130.00
 FLOW LENGTH (FEET) = 2092.67 MANNING'S N = 0.013
 ESTIMATED PIPE DIAMETER (INCH) INCREASED TO 36.000
 DEPTH OF FLOW IN 36.0 INCH PIPE IS 14.5 INCHES
 PIPE-FLOW VELOCITY (FEET/SEC.) = 13.60
 ESTIMATED PIPE DIAMETER (INCH) = 36.00 NUMBER OF PIPES = 1
 PIPE-FLOW (CFS) = 36.37
 PIPE TRAVEL TIME (MIN.) = 2.57 Tc (MIN.) = 27.13
 LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13860.00 = 6208.84 FEET.

FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 81

 >>>> ADDITION OF SUBAREA TO MAINLINE PEAK FLOW <<<<<

 MAINLINE Tc (MIN.) = 27.13
 * 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.924
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	43.41	0.50	0.707	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.707
 SUBAREA AREA (ACRES) = 43.41 SUBAREA RUNOFF (CFS) = 22.29
 EFFECTIVE AREA (ACRES) = 123.22 AREA-AVERAGED Fm (INCH/HR) = 0.43
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.86
 TOTAL AREA (ACRES) = 123.2 PEAK FLOW RATE (CFS) = 54.85

FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 27.13
RAINFALL INTENSITY(INCH/HR) = 0.92
AREA-AVERAGED Fm(INCH/HR) = 0.43
AREA-AVERAGED Fp(INCH/HR) = 0.50
AREA-AVERAGED Ap = 0.86
EFFECTIVE STREAM AREA(ACRES) = 123.22
TOTAL STREAM AREA(ACRES) = 123.22
PEAK FLOW RATE(CFS) AT CONFLUENCE = 54.85

** CONFLUENCE DATA **

Table with columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 20 rows of data.

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

Table with columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 7 rows of data.

Table with columns: Node number, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 18 rows of data.

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 15318.36 Tc(MIN.) = 44.92
EFFECTIVE AREA(ACRES) = 12280.12 AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.81
TOTAL AREA(ACRES) = 68707.6
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13860.00 = 133435.52 FEET.

FLOW PROCESS FROM NODE 13860.00 TO NODE 13880.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 130.00 DOWNSTREAM(FEET) = 120.57
CHANNEL LENGTH THRU SUBAREA(FEET) = 610.77 CHANNEL SLOPE = 0.0154
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.697
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 4.89 0.50 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 15318.79
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 22.75
AVERAGE FLOW DEPTH(FEET) = 14.98 TRAVEL TIME(MIN.) = 0.45
Tc(MIN.) = 45.37
SUBAREA AREA(ACRES) = 4.89 SUBAREA RUNOFF(CFS) = 0.87
EFFECTIVE AREA(ACRES) = 12285.01 AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.81
TOTAL AREA(ACRES) = 68712.5 PEAK FLOW RATE(CFS) = 15318.36
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 14.98 FLOW VELOCITY(FEET/SEC.) = 22.75
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13880.00 = 134046.28 FEET.

FLOW PROCESS FROM NODE 13860.00 TO NODE 13880.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION(MIN.) = 45.37
RAINFALL INTENSITY(INCH/HR) = 0.70
AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50
AREA-AVERAGED Ap = 0.81
EFFECTIVE STREAM AREA(ACRES) = 12285.01
TOTAL STREAM AREA(ACRES) = 68712.52
PEAK FLOW RATE(CFS) AT CONFLUENCE = 15318.36

FLOW PROCESS FROM NODE 13870.00 TO NODE 13871.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH(FEET) = 872.65
ELEVATION DATA: UPSTREAM(FEET) = 558.52 DOWNSTREAM(FEET) = 436.47

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 15.704
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.266
SUBAREA Tc AND LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)
NATURAL FAIR COVER
"GRASS" - 7.32 0.50 1.000 65 15.70
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 5.04
TOTAL AREA(ACRES) = 7.32 PEAK FLOW RATE(CFS) = 5.04

FLOW PROCESS FROM NODE 13871.00 TO NODE 13872.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 436.47 DOWNSTREAM(FEET) = 337.62
CHANNEL LENGTH THRU SUBAREA(FEET) = 827.95 CHANNEL SLOPE = 0.1194
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.151
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 13.01 0.50 1.000 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 8.87
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.49
AVERAGE FLOW DEPTH(FEET) = 0.81 TRAVEL TIME(MIN.) = 3.07
Tc(MIN.) = 18.78
SUBAREA AREA(ACRES) = 13.01 SUBAREA RUNOFF(CFS) = 7.62
EFFECTIVE AREA(ACRES) = 20.33 AREA-AVERAGED Fm(INCH/HR) = 0.50

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 20.3 PEAK FLOW RATE(CFS) = 11.90

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.90 FLOW VELOCITY(FEET/SEC.) = 4.86
LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13872.00 = 1700.60 FEET.

FLOW PROCESS FROM NODE 13872.00 TO NODE 13873.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 337.62 DOWNSTREAM(FEET) = 253.88
CHANNEL LENGTH THRU SUBAREA(FEET) = 1049.16 CHANNEL SLOPE = 0.0798
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.037
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 32.99 0.50 0.923 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.923
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 20.46
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.79
AVERAGE FLOW DEPTH(FEET) = 1.19 TRAVEL TIME(MIN.) = 3.65
Tc(MIN.) = 22.43
SUBAREA AREA(ACRES) = 32.99 SUBAREA RUNOFF(CFS) = 17.08
EFFECTIVE AREA(ACRES) = 53.32 AREA-AVERAGED Fm(INCH/HR) = 0.48
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.95
TOTAL AREA(ACRES) = 53.3 PEAK FLOW RATE(CFS) = 26.91

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.32 FLOW VELOCITY(FEET/SEC.) = 5.13
LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13873.00 = 2749.76 FEET.

FLOW PROCESS FROM NODE 13873.00 TO NODE 13874.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 253.88 DOWNSTREAM(FEET) = 160.73
CHANNEL LENGTH THRU SUBAREA(FEET) = 1518.60 CHANNEL SLOPE = 0.0613
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.941
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 30.94 0.50 0.900 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.900
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 33.75
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.66
AVERAGE FLOW DEPTH(FEET) = 1.30 TRAVEL TIME(MIN.) = 3.80
Tc(MIN.) = 26.23

SUBAREA AREA (ACRES) = 30.94 SUBAREA RUNOFF (CFS) = 13.68
EFFECTIVE AREA (ACRES) = 84.26 AREA-AVERAGED Fm (INCH/HR) = 0.47
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.93
TOTAL AREA (ACRES) = 84.3 PEAK FLOW RATE (CFS) = 36.00

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 1.33 FLOW VELOCITY (FEET/SEC.) = 6.78
LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13874.00 = 4268.36 FEET.

FLOW PROCESS FROM NODE 13874.00 TO NODE 13875.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 160.73 DOWNSTREAM (FEET) = 158.14
CHANNEL LENGTH THRU SUBAREA (FEET) = 582.74 CHANNEL SLOPE = 0.0044
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.873

SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 73.67 0.50 0.930 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.930
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 49.56
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 2.74
AVERAGE FLOW DEPTH (FEET) = 2.45 TRAVEL TIME (MIN.) = 3.54
Tc (MIN.) = 29.77
SUBAREA AREA (ACRES) = 73.67 SUBAREA RUNOFF (CFS) = 27.07
EFFECTIVE AREA (ACRES) = 157.93 AREA-AVERAGED Fm (INCH/HR) = 0.47
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.93
TOTAL AREA (ACRES) = 157.9 PEAK FLOW RATE (CFS) = 57.91

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 2.60 FLOW VELOCITY (FEET/SEC.) = 2.85
LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13875.00 = 4851.10 FEET.

FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 158.14 DOWNSTREAM (FEET) = 120.57
FLOW LENGTH (FEET) = 1855.67 MANNING'S N = 0.013
ESTIMATED PIPE DIAMETER (INCH) INCREASED TO 36.000
DEPTH OF FLOW IN 36.0 INCH PIPE IS 21.0 INCHES
PIPE-FLOW VELOCITY (FEET/SEC.) = 13.53
ESTIMATED PIPE DIAMETER (INCH) = 36.00 NUMBER OF PIPES = 1
PIPE-FLOW (CFS) = 57.91
PIPE TRAVEL TIME (MIN.) = 2.29 Tc (MIN.) = 32.05
LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13880.00 = 6706.77 FEET.

FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 32.05
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.843
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 34.90 0.50 0.743 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.743
SUBAREA AREA (ACRES) = 34.90 SUBAREA RUNOFF (CFS) = 14.80
EFFECTIVE AREA (ACRES) = 192.83 AREA-AVERAGED Fm (INCH/HR) = 0.45
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.90
TOTAL AREA (ACRES) = 192.8 PEAK FLOW RATE (CFS) = 68.34

FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION (MIN.) = 32.05
RAINFALL INTENSITY (INCH/HR) = 0.84
AREA-AVERAGED Fm (INCH/HR) = 0.45
AREA-AVERAGED Fp (INCH/HR) = 0.50
AREA-AVERAGED Ap = 0.90
EFFECTIVE STREAM AREA (ACRES) = 192.83
TOTAL STREAM AREA (ACRES) = 192.83
PEAK FLOW RATE (CFS) AT CONFLUENCE = 68.34

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14631.19	25.77	0.950	0.50 (0.41)	0.81	5259.6	13810.00
1	14629.21	26.31	0.940	0.50 (0.41)	0.81	5378.1	400.00
1	14677.76	27.58	0.915	0.50 (0.41)	0.81	5854.2	13850.00
1	15027.28	37.15	0.777	0.50 (0.41)	0.81	9392.4	10200.00
1	15272.73	43.95	0.709	0.50 (0.41)	0.81	11800.5	13830.00
1	15318.36	45.37	0.697	0.50 (0.41)	0.81	12285.0	410.00
1	14552.29	55.25	0.626	0.50 (0.42)	0.83	16466.8	130.00
1	13385.59	72.56	0.553	0.50 (0.43)	0.86	22850.3	31100.00
1	12809.20	81.96	0.521	0.50 (0.44)	0.87	26168.4	13600.00
1	11890.30	100.64	0.472	0.50 (0.45)	0.89	32629.0	11500.00
1	11301.57	113.05	0.447	0.50 (0.45)	0.90	37307.7	11000.00
1	10678.86	127.65	0.424	0.50 (0.46)	0.91	43959.0	13000.00
1	9569.70	145.94	0.402	0.50 (0.46)	0.93	51424.6	11130.00
1	8816.31	158.31	0.388	0.50 (0.47)	0.93	55204.4	11620.00
1	7681.66	175.35	0.367	0.50 (0.47)	0.93	59780.7	12400.00
1	6791.83	187.72	0.358	0.50 (0.47)	0.94	62098.6	12201.00
1	6153.19	197.83	0.352	0.50 (0.47)	0.94	63389.2	12111.00
1	5197.49	214.96	0.343	0.50 (0.47)	0.94	65312.1	12261.00
1	4713.15	225.12	0.338	0.50 (0.47)	0.94	66123.2	10200.00
1	4122.38	241.74	0.329	0.50 (0.47)	0.94	67361.1	10300.00
1	3881.06	249.16	0.325	0.50 (0.47)	0.94	67713.4	12010.00
1	3377.83	270.96	0.313	0.50 (0.47)	0.94	68041.7	12000.00
1	2306.45	343.50	0.274	0.50 (0.47)	0.94	68712.5	10100.00

2 68.34 32.05 0.843 0.50(0.45) 0.90 192.8 13870.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14699.53	25.77	0.950	0.50(0.41)	0.81	5414.6	13810.00
2	14697.55	26.31	0.940	0.50(0.41)	0.81	5536.4	400.00
3	14746.09	27.58	0.915	0.50(0.41)	0.81	6020.2	13850.00
4	14909.41	32.05	0.843	0.50(0.41)	0.81	7700.3	13870.00
5	15084.29	37.15	0.777	0.50(0.41)	0.81	9585.2	10200.00
6	15317.79	43.95	0.709	0.50(0.41)	0.81	11993.4	13830.00
7	15361.40	45.37	0.697	0.50(0.41)	0.81	12477.8	410.00
8	14583.10	55.25	0.626	0.50(0.42)	0.83	16659.6	130.00
9	13403.73	72.56	0.553	0.50(0.43)	0.86	23043.1	31100.00
10	12821.68	81.96	0.521	0.50(0.44)	0.87	26361.2	13600.00
11	11898.69	100.64	0.472	0.50(0.45)	0.89	32821.8	11500.00
12	11309.52	113.05	0.447	0.50(0.45)	0.90	37500.6	11000.00
13	10686.40	127.65	0.424	0.50(0.46)	0.91	44151.8	13000.00
14	9576.85	145.94	0.402	0.50(0.46)	0.93	51617.5	11130.00
15	8823.21	158.31	0.388	0.50(0.47)	0.93	55397.3	11620.00
16	7688.20	175.35	0.367	0.50(0.47)	0.93	59973.5	12400.00
17	6798.20	187.72	0.358	0.50(0.47)	0.94	62291.4	12201.00
18	6159.46	197.83	0.352	0.50(0.47)	0.94	63582.0	12111.00
19	5203.60	214.96	0.343	0.50(0.47)	0.94	65504.9	12261.00
20	4719.16	225.12	0.338	0.50(0.47)	0.94	66316.1	10200.00
21	4128.23	241.74	0.329	0.50(0.47)	0.94	67554.0	10300.00
22	3886.83	249.16	0.325	0.50(0.47)	0.94	67906.2	12010.00
23	3383.39	270.96	0.313	0.50(0.47)	0.94	68234.5	12000.00
24	2311.32	343.50	0.274	0.50(0.47)	0.94	68905.3	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 15361.40 Tc(MIN.) = 45.37
EFFECTIVE AREA(ACRES) = 12477.84 AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.81
TOTAL AREA(ACRES) = 68905.3
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13880.00 = 134046.28 FEET.

FLOW PROCESS FROM NODE 13880.00 TO NODE 13910.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 120.57 DOWNSTREAM(FEET) = 119.70
CHANNEL LENGTH THRU SUBAREA(FEET) = 1190.21 CHANNEL SLOPE = 0.0007
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00

==>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL
CAPACITY(NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM
ALLOWABLE DEPTH) .
AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM
ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.684

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 117.69 0.50 0.724 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.724
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 15378.46
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.82
AVERAGE FLOW DEPTH(FEET) = 20.00 TRAVEL TIME(MIN.) = 1.55
Tc(MIN.) = 46.92
SUBAREA AREA(ACRES) = 117.69 SUBAREA RUNOFF(CFS) = 34.12
EFFECTIVE AREA(ACRES) = 12595.53 AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.81
TOTAL AREA(ACRES) = 69023.0 PEAK FLOW RATE(CFS) = 15361.40
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

==>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL
CAPACITY(NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM
ALLOWABLE DEPTH) .
AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM
ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 20.00 FLOW VELOCITY(FEET/SEC.) = 12.80

==>FLOWDEPTH EXCEEDS MAXIMUM ALLOWABLE DEPTH

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13910.00 = 135236.48 FEET.

FLOW PROCESS FROM NODE 13880.00 TO NODE 13910.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION(MIN.) = 46.92
RAINFALL INTENSITY(INCH/HR) = 0.68
AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50
AREA-AVERAGED Ap = 0.81
EFFECTIVE STREAM AREA(ACRES) = 12595.53
TOTAL STREAM AREA(ACRES) = 69023.03
PEAK FLOW RATE(CFS) AT CONFLUENCE = 15361.40

FLOW PROCESS FROM NODE 13889.00 TO NODE 13890.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH(FEET) = 447.89
ELEVATION DATA: UPSTREAM(FEET) = 564.89 DOWNSTREAM(FEET) = 421.92

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 6.976
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 2.251

SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
PUBLIC PARK	-	3.03	0.50	0.960	65	6.98

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.960
SUBAREA RUNOFF (CFS) = 4.83
TOTAL AREA (ACRES) = 3.03 PEAK FLOW RATE (CFS) = 4.83

FLOW PROCESS FROM NODE 13890.00 TO NODE 13891.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 421.92 DOWNSTREAM (FEET) = 392.64
CHANNEL LENGTH THRU SUBAREA (FEET) = 435.33 CHANNEL SLOPE = 0.0673
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 2.009

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.12	0.50	0.986	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.986
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 10.38
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.13
AVERAGE FLOW DEPTH (FEET) = 0.82 TRAVEL TIME (MIN.) = 1.41
Tc (MIN.) = 8.39
SUBAREA AREA (ACRES) = 8.12 SUBAREA RUNOFF (CFS) = 11.08
EFFECTIVE AREA (ACRES) = 11.15 AREA-AVERAGED Fm (INCH/HR) = 0.49
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.98
TOTAL AREA (ACRES) = 11.1 PEAK FLOW RATE (CFS) = 15.24

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.95 FLOW VELOCITY (FEET/SEC.) = 5.64
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13891.00 = 883.22 FEET.

FLOW PROCESS FROM NODE 13891.00 TO NODE 13892.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 392.64 DOWNSTREAM (FEET) = 324.46
CHANNEL LENGTH THRU SUBAREA (FEET) = 662.40 CHANNEL SLOPE = 0.1029
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.749

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	12.50	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 22.29
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.29

AVERAGE FLOW DEPTH (FEET) = 1.01 TRAVEL TIME (MIN.) = 1.52
Tc (MIN.) = 9.91
SUBAREA AREA (ACRES) = 12.50 SUBAREA RUNOFF (CFS) = 14.05
EFFECTIVE AREA (ACRES) = 23.65 AREA-AVERAGED Fm (INCH/HR) = 0.50
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 23.6 PEAK FLOW RATE (CFS) = 26.69

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 1.08 FLOW VELOCITY (FEET/SEC.) = 7.62
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13892.00 = 1545.62 FEET.

FLOW PROCESS FROM NODE 13892.00 TO NODE 13893.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 324.46 DOWNSTREAM (FEET) = 240.82
CHANNEL LENGTH THRU SUBAREA (FEET) = 980.03 CHANNEL SLOPE = 0.0853
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.552

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	15.87	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 34.21
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.59
AVERAGE FLOW DEPTH (FEET) = 1.23 TRAVEL TIME (MIN.) = 2.15
Tc (MIN.) = 12.06
SUBAREA AREA (ACRES) = 15.87 SUBAREA RUNOFF (CFS) = 15.02
EFFECTIVE AREA (ACRES) = 39.52 AREA-AVERAGED Fm (INCH/HR) = 0.50
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 39.5 PEAK FLOW RATE (CFS) = 37.50

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 1.27 FLOW VELOCITY (FEET/SEC.) = 7.74
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13893.00 = 2525.65 FEET.

FLOW PROCESS FROM NODE 13893.00 TO NODE 13894.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 240.82 DOWNSTREAM (FEET) = 163.04
CHANNEL LENGTH THRU SUBAREA (FEET) = 1144.35 CHANNEL SLOPE = 0.0680
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.330

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	28.41	0.50	0.985	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.985

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 48.23
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.60
 AVERAGE FLOW DEPTH(FEET) = 1.45 TRAVEL TIME(MIN.) = 2.51
 Tc(MIN.) = 14.57
 SUBAREA AREA(ACRES) = 28.41 SUBAREA RUNOFF(CFS) = 21.42
 EFFECTIVE AREA(ACRES) = 67.93 AREA-AVERAGED Fm(INCH/HR) = 0.50
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 67.9 PEAK FLOW RATE(CFS) = 51.05

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 1.49 FLOW VELOCITY(FEET/SEC.) = 7.66
 LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13894.00 = 3670.00 FEET.

 FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 163.04 DOWNSTREAM(FEET) = 119.70
 FLOW LENGTH(FEET) = 1899.01 MANNING'S N = 0.013
 ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000
 DEPTH OF FLOW IN 36.0 INCH PIPE IS 18.7 INCHES
 PIPE-FLOW VELOCITY(FEET/SEC.) = 13.75
 ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1
 PIPE-FLOW(CFS) = 51.05
 PIPE TRAVEL TIME(MIN.) = 2.30 Tc(MIN.) = 16.87
 LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13910.00 = 5569.01 FEET.

 FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 16.87
 * 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.222
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 11.69 0.50 0.634 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.634
 SUBAREA AREA(ACRES) = 11.69 SUBAREA RUNOFF(CFS) = 9.52
 EFFECTIVE AREA(ACRES) = 79.62 AREA-AVERAGED Fm(INCH/HR) = 0.47
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.94
 TOTAL AREA(ACRES) = 79.6 PEAK FLOW RATE(CFS) = 53.96

 FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
 TIME OF CONCENTRATION(MIN.) = 16.87
 RAINFALL INTENSITY(INCH/HR) = 1.22
 AREA-AVERAGED Fm(INCH/HR) = 0.47

AREA-AVERAGED Fp(INCH/HR) = 0.50
 AREA-AVERAGED Ap = 0.94
 EFFECTIVE STREAM AREA(ACRES) = 79.62
 TOTAL STREAM AREA(ACRES) = 79.62
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 53.96

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14699.53	27.39	0.919	0.50(0.41)	0.81	5532.3	13810.00
1	14697.55	27.93	0.909	0.50(0.41)	0.81	5654.1	400.00
1	14746.09	29.19	0.884	0.50(0.41)	0.81	6137.9	13850.00
1	14909.41	33.65	0.822	0.50(0.41)	0.81	7818.0	13870.00
1	15084.29	38.73	0.757	0.50(0.41)	0.81	9702.9	10200.00
1	15317.79	45.50	0.696	0.50(0.41)	0.81	12111.1	13830.00
1	15361.40	46.92	0.684	0.50(0.41)	0.81	12595.5	410.00
1	14583.10	56.88	0.616	0.50(0.42)	0.83	16777.3	130.00
1	13403.73	74.34	0.547	0.50(0.43)	0.86	23160.8	31100.00
1	12821.68	83.82	0.514	0.50(0.44)	0.87	26478.9	13600.00
1	11898.69	102.64	0.468	0.50(0.45)	0.89	32939.5	11500.00
1	11309.52	115.15	0.443	0.50(0.45)	0.90	37618.3	11000.00
1	10686.40	129.88	0.421	0.50(0.46)	0.91	44269.5	13000.00
1	9576.85	148.42	0.399	0.50(0.46)	0.93	51735.2	11130.00
1	8823.21	161.01	0.384	0.50(0.47)	0.93	55515.0	11620.00
1	7688.20	178.45	0.364	0.50(0.47)	0.93	60091.2	12400.00
1	6798.20	191.07	0.356	0.50(0.47)	0.94	62409.1	12201.00
1	6159.46	201.26	0.351	0.50(0.47)	0.94	63699.7	12111.00
1	5203.60	218.54	0.341	0.50(0.47)	0.94	65622.6	12261.00
1	4719.16	228.80	0.336	0.50(0.47)	0.94	66433.8	10200.00
1	4128.23	245.54	0.327	0.50(0.47)	0.94	67671.7	10300.00
1	3886.83	253.02	0.323	0.50(0.47)	0.94	68023.9	12010.00
1	3383.39	274.95	0.311	0.50(0.47)	0.94	68352.2	12000.00
1	2311.32	347.88	0.272	0.50(0.47)	0.94	69023.0	10100.00
2	53.96	16.87	1.222	0.50(0.47)	0.94	79.6	13889.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14456.03	16.87	1.222	0.50(0.41)	0.82	3486.9	13889.00
2	14731.77	27.39	0.919	0.50(0.41)	0.81	5611.9	13810.00
3	14729.05	27.93	0.909	0.50(0.41)	0.81	5733.7	400.00
4	14775.85	29.19	0.884	0.50(0.41)	0.81	6217.5	13850.00
5	14934.71	33.65	0.822	0.50(0.41)	0.81	7897.6	13870.00
6	15104.93	38.73	0.757	0.50(0.41)	0.81	9782.5	10200.00
7	15334.04	45.50	0.696	0.50(0.41)	0.81	12190.7	13830.00
8	15376.81	46.92	0.684	0.50(0.41)	0.81	12675.2	410.00
9	14593.65	56.88	0.616	0.50(0.42)	0.83	16856.9	130.00
10	13409.33	74.34	0.547	0.50(0.43)	0.86	23240.4	31100.00
11	12824.92	83.82	0.514	0.50(0.44)	0.87	26558.5	13600.00
12	11900.77	102.64	0.468	0.50(0.45)	0.89	33019.2	11500.00
13	11311.49	115.15	0.443	0.50(0.45)	0.90	37697.9	11000.00
14	10688.27	129.88	0.421	0.50(0.46)	0.91	44349.2	13000.00
15	9578.63	148.42	0.399	0.50(0.46)	0.93	51814.8	11130.00
16	8824.92	161.01	0.384	0.50(0.47)	0.93	55594.6	11620.00
17	7689.81	178.45	0.364	0.50(0.47)	0.93	60170.9	12400.00

18	6799.78	191.07	0.356	0.50	(0.47)	0.94	62488.7	12201.00
19	6161.01	201.26	0.351	0.50	(0.47)	0.94	63779.3	12111.00
20	5205.11	218.54	0.341	0.50	(0.47)	0.94	65702.2	12261.00
21	4720.65	228.80	0.336	0.50	(0.47)	0.94	66513.4	10200.00
22	4129.68	245.54	0.327	0.50	(0.47)	0.94	67751.3	10300.00
23	3888.27	253.02	0.323	0.50	(0.47)	0.94	68103.5	12010.00
24	3384.77	274.95	0.311	0.50	(0.47)	0.94	68431.9	12000.00
25	2312.52	347.88	0.272	0.50	(0.47)	0.94	69102.6	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 15376.81 Tc (MIN.) = 46.92
EFFECTIVE AREA (ACRES) = 12675.15 AREA-AVERAGED Fm (INCH/HR) = 0.41
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.81
TOTAL AREA (ACRES) = 69102.6
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13910.00 = 135236.48 FEET.

=====
END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 69102.6 TC (MIN.) = 46.92
EFFECTIVE AREA (ACRES) = 12675.15 AREA-AVERAGED Fm (INCH/HR) = 0.41
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.813
PEAK FLOW RATE (CFS) = 15376.81

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14456.03	16.87	1.222	0.50 (0.41)	0.82	3486.9	13889.00
2	14731.77	27.39	0.919	0.50 (0.41)	0.81	5611.9	13810.00
3	14729.05	27.93	0.909	0.50 (0.41)	0.81	5733.7	400.00
4	14775.85	29.19	0.884	0.50 (0.41)	0.81	6217.5	13850.00
5	14934.71	33.65	0.822	0.50 (0.41)	0.81	7897.6	13870.00
6	15104.93	38.73	0.757	0.50 (0.41)	0.81	9782.5	10200.00
7	15334.04	45.50	0.696	0.50 (0.41)	0.81	12190.7	13830.00
8	15376.81	46.92	0.684	0.50 (0.41)	0.81	12675.2	410.00
9	14593.65	56.88	0.616	0.50 (0.42)	0.83	16856.9	130.00
10	13409.33	74.34	0.547	0.50 (0.43)	0.86	23240.4	31100.00
11	12824.92	83.82	0.514	0.50 (0.44)	0.87	26558.5	13600.00
12	11900.77	102.64	0.468	0.50 (0.45)	0.89	33019.2	11500.00
13	11311.49	115.15	0.443	0.50 (0.45)	0.90	37697.9	11000.00
14	10688.27	129.88	0.421	0.50 (0.46)	0.91	44349.2	13000.00
15	9578.63	148.42	0.399	0.50 (0.46)	0.93	51814.8	11130.00
16	8824.92	161.01	0.384	0.50 (0.47)	0.93	55594.6	11620.00
17	7689.81	178.45	0.364	0.50 (0.47)	0.93	60170.9	12400.00
18	6799.78	191.07	0.356	0.50 (0.47)	0.94	62488.7	12201.00
19	6161.01	201.26	0.351	0.50 (0.47)	0.94	63779.3	12111.00
20	5205.11	218.54	0.341	0.50 (0.47)	0.94	65702.2	12261.00
21	4720.65	228.80	0.336	0.50 (0.47)	0.94	66513.4	10200.00
22	4129.68	245.54	0.327	0.50 (0.47)	0.94	67751.3	10300.00
23	3888.27	253.02	0.323	0.50 (0.47)	0.94	68103.5	12010.00
24	3384.77	274.95	0.311	0.50 (0.47)	0.94	68431.9	12000.00
25	2312.52	347.88	0.272	0.50 (0.47)	0.94	69102.6	10100.00

=====
END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2010 Advanced Engineering Software (aes)
Ver. 17.0 Release Date: 07/01/2010 License ID 1527

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 139 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 5-YR EV AUG 2023 ROKAMOTO *

FILE NAME: RU05EV39.DAT
TIME/DATE OF STUDY: 23:47 08/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 5.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 2.586
- 2) 10.00; 1.731
- 3) 15.00; 1.292
- 4) 20.00; 1.104
- 5) 25.00; 0.965
- 6) 30.00; 0.869
- 7) 40.00; 0.741
- 8) 50.00; 0.658
- 9) 60.00; 0.596
- 10) 90.00; 0.493
- 11) 120.00; 0.433
- 12) 180.00; 0.362
- 13) 360.00; 0.264
- 14) 1200.00; 0.115

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:

- 1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13900.00 TO NODE 13901.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 600.65
ELEVATION DATA: UPSTREAM(FEET) = 442.40 DOWNSTREAM(FEET) = 385.16

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 10.859
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.656
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
AGRICULTURAL POOR COVER "FALLOW"	-	4.00	0.50	1.000	65	10.86

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 4.16
TOTAL AREA(ACRES) = 4.00 PEAK FLOW RATE(CFS) = 4.16

FLOW PROCESS FROM NODE 13901.00 TO NODE 13902.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 385.16 DOWNSTREAM(FEET) = 288.21
CHANNEL LENGTH THRU SUBAREA(FEET) = 647.42 CHANNEL SLOPE = 0.1497
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.509
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.47	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 8.01
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.45
AVERAGE FLOW DEPTH(FEET) = 0.64 TRAVEL TIME(MIN.) = 1.67
Tc(MIN.) = 12.53
SUBAREA AREA(ACRES) = 8.47 SUBAREA RUNOFF(CFS) = 7.69
EFFECTIVE AREA(ACRES) = 12.47 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 12.5 PEAK FLOW RATE(CFS) = 11.32

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.73 FLOW VELOCITY(FEET/SEC.) = 7.09
LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13902.00 = 1248.07 FEET.

FLOW PROCESS FROM NODE 13902.00 TO NODE 13903.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 288.21 DOWNSTREAM(FEET) = 184.89
CHANNEL LENGTH THRU SUBAREA(FEET) = 669.27 CHANNEL SLOPE = 0.1544
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.392
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 23.85 0.50 0.982 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.982
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 21.00
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.40
AVERAGE FLOW DEPTH(FEET) = 0.91 TRAVEL TIME(MIN.) = 1.33
Tc(MIN.) = 13.86
SUBAREA AREA(ACRES) = 23.85 SUBAREA RUNOFF(CFS) = 19.34
EFFECTIVE AREA(ACRES) = 36.32 AREA-AVERAGED Fm(INCH/HR) = 0.49
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 36.3 PEAK FLOW RATE(CFS) = 29.35

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.03 FLOW VELOCITY(FEET/SEC.) = 9.14
LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13903.00 = 1917.34 FEET.

FLOW PROCESS FROM NODE 13903.00 TO NODE 13904.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 184.89 DOWNSTREAM(FEET) = 155.08
FLOW LENGTH(FEET) = 876.66 MANNING'S N = 0.013
ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000
DEPTH OF FLOW IN 36.0 INCH PIPE IS 12.3 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 13.74
ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 29.35
PIPE TRAVEL TIME(MIN.) = 1.06 Tc(MIN.) = 14.92
LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13904.00 = 2794.00 FEET.

FLOW PROCESS FROM NODE 13903.00 TO NODE 13904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 14.92
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.299
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 21.29 0.50 0.996 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.996

SUBAREA AREA(ACRES) = 21.29 SUBAREA RUNOFF(CFS) = 15.34
EFFECTIVE AREA(ACRES) = 57.61 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 57.6 PEAK FLOW RATE(CFS) = 41.63

FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 155.08 DOWNSTREAM(FEET) = 118.00
FLOW LENGTH(FEET) = 1961.38 MANNING'S N = 0.013
ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000
DEPTH OF FLOW IN 36.0 INCH PIPE IS 17.5 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 12.17
ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 41.63
PIPE TRAVEL TIME(MIN.) = 2.69 Tc(MIN.) = 17.61
LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13920.00 = 4755.38 FEET.

FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 17.61
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.194
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 43.53 0.50 0.649 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.649
SUBAREA AREA(ACRES) = 43.53 SUBAREA RUNOFF(CFS) = 34.06
EFFECTIVE AREA(ACRES) = 101.14 AREA-AVERAGED Fm(INCH/HR) = 0.42
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.84
TOTAL AREA(ACRES) = 101.1 PEAK FLOW RATE(CFS) = 70.25

FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 13910.00 TO NODE 13910.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: RU05EV38.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:
STREAM Q Tc Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (ACRES) NODE
1 14456.03 16.87 0.50(0.41) 0.82 3486.9 13889.00
2 15104.93 38.73 0.50(0.41) 0.81 9782.5 10200.00
3 15376.81 46.92 0.50(0.41) 0.81 12675.2 410.00
4 14593.65 56.88 0.50(0.42) 0.83 16856.9 130.00

5	13409.33	74.34	0.50	(0.43)	0.86	23240.4	31100.00
6	12824.92	83.82	0.50	(0.44)	0.87	26558.5	13600.00
7	11900.77	102.64	0.50	(0.45)	0.89	33019.2	11500.00
8	11311.49	115.15	0.50	(0.45)	0.90	37697.9	11000.00
9	10688.27	129.88	0.50	(0.46)	0.91	44349.2	13000.00
10	9578.63	148.42	0.50	(0.46)	0.93	51814.8	11130.00
11	8824.92	161.01	0.50	(0.47)	0.93	55594.6	11620.00
12	7689.81	178.45	0.50	(0.47)	0.93	60170.9	12400.00
13	6799.78	191.07	0.50	(0.47)	0.94	62488.7	12201.00
14	6161.01	201.26	0.50	(0.47)	0.94	63779.3	12111.00
15	5205.11	218.54	0.50	(0.47)	0.94	65702.2	12261.00
16	4720.65	228.80	0.50	(0.47)	0.94	66513.4	10200.00
17	4129.68	245.54	0.50	(0.47)	0.94	67751.3	10300.00
18	3888.27	253.02	0.50	(0.47)	0.94	68103.5	12010.00
19	3384.77	274.95	0.50	(0.47)	0.94	68431.9	12000.00
20	2312.52	347.88	0.50	(0.47)	0.94	69102.6	10100.00

TOTAL AREA (ACRES) = 69102.6

FLOW PROCESS FROM NODE 13910.00 TO NODE 13910.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<
=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14456.03	16.87	0.50 (0.41)	0.82	3486.9	13889.00
2	15104.93	38.73	0.50 (0.41)	0.81	9782.5	10200.00
3	15376.81	46.92	0.50 (0.41)	0.81	12675.2	410.00
4	14593.65	56.88	0.50 (0.42)	0.83	16856.9	130.00
5	13409.33	74.34	0.50 (0.43)	0.86	23240.4	31100.00
6	12824.92	83.82	0.50 (0.44)	0.87	26558.5	13600.00
7	11900.77	102.64	0.50 (0.45)	0.89	33019.2	11500.00
8	11311.49	115.15	0.50 (0.45)	0.90	37697.9	11000.00
9	10688.27	129.88	0.50 (0.46)	0.91	44349.2	13000.00
10	9578.63	148.42	0.50 (0.46)	0.93	51814.8	11130.00
11	8824.92	161.01	0.50 (0.47)	0.93	55594.6	11620.00
12	7689.81	178.45	0.50 (0.47)	0.93	60170.9	12400.00
13	6799.78	191.07	0.50 (0.47)	0.94	62488.7	12201.00
14	6161.01	201.26	0.50 (0.47)	0.94	63779.3	12111.00
15	5205.11	218.54	0.50 (0.47)	0.94	65702.2	12261.00
16	4720.65	228.80	0.50 (0.47)	0.94	66513.4	10200.00
17	4129.68	245.54	0.50 (0.47)	0.94	67751.3	10300.00
18	3888.27	253.02	0.50 (0.47)	0.94	68103.5	12010.00
19	3384.77	274.95	0.50 (0.47)	0.94	68431.9	12000.00
20	2312.52	347.88	0.50 (0.47)	0.94	69102.6	10100.00

TOTAL AREA (ACRES) = 69102.6

FLOW PROCESS FROM NODE 13910.00 TO NODE 13920.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<
=====

ELEVATION DATA: UPSTREAM (FEET) = 119.70 DOWNSTREAM (FEET) = 118.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 1376.26 CHANNEL SLOPE = 0.0012
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00

==>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL
CAPACITY (NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM
ALLOWABLE DEPTH).
AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM
ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.669
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCSSOIL AREA Fp Ap SCSS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 96.09 0.50 0.535 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.535
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 15394.16
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 12.83
AVERAGE FLOW DEPTH (FEET) = 20.00 TRAVEL TIME (MIN.) = 1.79
Tc (MIN.) = 48.71
SUBAREA AREA (ACRES) = 96.09 SUBAREA RUNOFF (CFS) = 34.69
EFFECTIVE AREA (ACRES) = 12771.24 AREA-AVERAGED Fm (INCH/HR) = 0.41
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.81
TOTAL AREA (ACRES) = 69198.7 PEAK FLOW RATE (CFS) = 15376.81
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

==>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL
CAPACITY (NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM
ALLOWABLE DEPTH).
AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM
ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 20.00 FLOW VELOCITY (FEET/SEC.) = 12.81

==>FLOWDEPTH EXCEEDS MAXIMUM ALLOWABLE DEPTH

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136612.75 FEET.

FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<
=====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14456.03	18.77	1.150	0.50 (0.40)	0.81	3583.0	13889.00
2	15104.93	40.55	0.736	0.50 (0.41)	0.81	9878.6	10200.00
3	15376.81	48.71	0.669	0.50 (0.41)	0.81	12771.2	410.00
4	14593.65	58.76	0.604	0.50 (0.41)	0.83	16953.0	130.00
5	13409.33	76.39	0.540	0.50 (0.43)	0.86	23336.5	31100.00
6	12824.92	85.96	0.507	0.50 (0.44)	0.87	26654.6	13600.00
7	11900.77	104.95	0.463	0.50 (0.45)	0.89	33115.2	11500.00
8	11311.49	117.59	0.438	0.50 (0.45)	0.90	37794.0	11000.00
9	10688.27	132.45	0.418	0.50 (0.46)	0.91	44445.2	13000.00
10	9578.63	151.30	0.396	0.50 (0.46)	0.92	51910.9	11130.00

11	8824.92	163.99	0.381	0.50 (0.46)	0.93	55690.7	11620.00
12	7689.81	181.54	0.361	0.50 (0.47)	0.93	60266.9	12400.00
13	6799.78	194.26	0.354	0.50 (0.47)	0.94	62584.8	12201.00
14	6161.01	204.53	0.349	0.50 (0.47)	0.94	63875.4	12111.00
15	5205.11	221.95	0.339	0.50 (0.47)	0.94	65798.3	12261.00
16	4720.65	232.28	0.334	0.50 (0.47)	0.94	66609.5	10200.00
17	4129.68	249.14	0.324	0.50 (0.47)	0.94	67847.4	10300.00
18	3888.27	256.68	0.320	0.50 (0.47)	0.94	68199.6	12010.00
19	3384.77	278.74	0.308	0.50 (0.47)	0.94	68527.9	12000.00
20	2312.52	352.05	0.268	0.50 (0.47)	0.94	69198.7	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136612.75 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	70.25	17.61	1.194	0.50 (0.42)	0.84	101.1	13900.00

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13920.00 = 4755.38 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14425.58	17.61	1.194	0.50 (0.40)	0.81	3463.0	13900.00
2	14522.32	18.77	1.150	0.50 (0.40)	0.81	3684.1	13889.00
3	15133.55	40.55	0.736	0.50 (0.41)	0.81	9979.7	10200.00
4	15399.26	48.71	0.669	0.50 (0.41)	0.81	12872.4	410.00
5	14610.18	58.76	0.604	0.50 (0.41)	0.83	17054.2	130.00
6	13420.03	76.39	0.540	0.50 (0.43)	0.86	23437.7	31100.00
7	12832.64	85.96	0.507	0.50 (0.44)	0.87	26755.7	13600.00
8	11907.35	104.95	0.463	0.50 (0.45)	0.89	33216.4	11500.00
9	11317.71	117.59	0.438	0.50 (0.45)	0.90	37895.1	11000.00
10	10694.22	132.45	0.418	0.50 (0.46)	0.91	44546.4	13000.00
11	9584.25	151.30	0.396	0.50 (0.46)	0.92	52012.0	11130.00
12	8830.33	163.99	0.381	0.50 (0.46)	0.93	55791.8	11620.00
13	7694.95	181.54	0.361	0.50 (0.47)	0.93	60368.1	12400.00
14	6804.81	194.26	0.354	0.50 (0.47)	0.94	62685.9	12201.00
15	6165.97	204.53	0.349	0.50 (0.47)	0.94	63976.6	12111.00
16	5209.93	221.95	0.339	0.50 (0.47)	0.94	65899.5	12261.00
17	4725.39	232.28	0.334	0.50 (0.47)	0.94	66710.6	10200.00
18	4134.29	249.14	0.324	0.50 (0.47)	0.94	67948.5	10300.00
19	3892.82	256.68	0.320	0.50 (0.47)	0.94	68300.7	12010.00
20	3389.15	278.74	0.308	0.50 (0.47)	0.94	68629.1	12000.00
21	2316.34	352.05	0.268	0.50 (0.47)	0.94	69299.9	10100.00

TOTAL AREA (ACRES) = 69299.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 15399.26 Tc (MIN.) = 48.707
EFFECTIVE AREA (ACRES) = 12872.38 AREA-AVERAGED Fm (INCH/HR) = 0.41
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.81
TOTAL AREA (ACRES) = 69299.9
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136612.75 FEET.

FLOW PROCESS FROM NODE 13920.00 TO NODE 13921.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 118.00 DOWNSTREAM (FEET) = 115.28

CHANNEL LENGTH THRU SUBAREA (FEET) = 335.44 CHANNEL SLOPE = 0.0081
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.666
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	134.30	0.50	0.658	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.658
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 15419.63
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 17.89
AVERAGE FLOW DEPTH (FEET) = 16.95 TRAVEL TIME (MIN.) = 0.31
Tc (MIN.) = 49.02
SUBAREA AREA (ACRES) = 134.30 SUBAREA RUNOFF (CFS) = 40.73
EFFECTIVE AREA (ACRES) = 13006.68 AREA-AVERAGED Fm (INCH/HR) = 0.40
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.81
TOTAL AREA (ACRES) = 69434.2 PEAK FLOW RATE (CFS) = 15399.26
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 16.93 FLOW VELOCITY (FEET/SEC.) = 17.90
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13921.00 = 136948.19 FEET.

FLOW PROCESS FROM NODE 13921.00 TO NODE 14010.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 115.28 DOWNSTREAM (FEET) = 100.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 1396.08 CHANNEL SLOPE = 0.0109
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.657
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	96.27	0.50	0.723	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.723
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 15412.05
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 20.03
AVERAGE FLOW DEPTH (FEET) = 16.02 TRAVEL TIME (MIN.) = 1.16
Tc (MIN.) = 50.18
SUBAREA AREA (ACRES) = 96.27 SUBAREA RUNOFF (CFS) = 25.58
EFFECTIVE AREA (ACRES) = 13102.95 AREA-AVERAGED Fm (INCH/HR) = 0.40
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.81
TOTAL AREA (ACRES) = 69530.5 PEAK FLOW RATE (CFS) = 15399.26
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 16.01 FLOW VELOCITY (FEET/SEC.) = 20.02
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 14010.00 = 138344.27 FEET.

=====

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 69530.5 TC (MIN.) = 50.18
EFFECTIVE AREA (ACRES) = 13102.95 AREA-AVERAGED Fm (INCH/HR) = 0.40

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.809

PEAK FLOW RATE (CFS) = 15399.26

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14425.58	19.11	1.138	0.50 (0.40)	0.80	3693.6	13900.00
2	14522.32	20.26	1.097	0.50 (0.40)	0.80	3914.7	13889.00
3	15133.55	42.03	0.724	0.50 (0.40)	0.81	10210.3	10200.00
4	15399.26	50.18	0.657	0.50 (0.40)	0.81	13103.0	410.00
5	14610.18	60.26	0.595	0.50 (0.41)	0.83	17284.7	130.00
6	13420.03	77.92	0.534	0.50 (0.43)	0.86	23668.2	31100.00
7	12832.64	87.51	0.502	0.50 (0.44)	0.87	26986.3	13600.00
8	11907.35	106.52	0.460	0.50 (0.45)	0.89	33447.0	11500.00
9	11317.71	119.18	0.435	0.50 (0.45)	0.90	38125.7	11000.00
10	10694.22	134.07	0.416	0.50 (0.46)	0.91	44777.0	13000.00
11	9584.25	152.96	0.394	0.50 (0.46)	0.92	52242.6	11130.00
12	8830.33	165.68	0.379	0.50 (0.46)	0.93	56022.4	11620.00
13	7694.95	183.29	0.360	0.50 (0.47)	0.93	60598.7	12400.00
14	6804.81	196.07	0.353	0.50 (0.47)	0.93	62916.5	12201.00
15	6165.97	206.38	0.348	0.50 (0.47)	0.94	64207.1	12111.00
16	5209.93	223.88	0.338	0.50 (0.47)	0.94	66130.0	12261.00
17	4725.39	234.26	0.332	0.50 (0.47)	0.94	66941.2	10200.00
18	4134.29	251.19	0.323	0.50 (0.47)	0.94	68179.1	10300.00
19	3892.82	258.76	0.319	0.50 (0.47)	0.94	68531.3	12010.00
20	3389.15	280.90	0.307	0.50 (0.47)	0.94	68859.7	12000.00
21	2316.34	354.42	0.267	0.50 (0.47)	0.94	69530.5	10100.00

=====
=====
END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International
5 Hutton Centre Drive, Suite 500
Santa Ana, CA 92707

***** DESCRIPTION OF STUDY *****
* RANCHO MISSION VIEJO - PA3 & PA4 ROMP - NODE 119 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 10-YR RM EV APRIL 2019 FKAZI *

FILE NAME: RU10EV19.DAT
TIME/DATE OF STUDY: 09:34 04/03/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 10.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 3.927
- 2) 10.00; 2.601
- 3) 15.00; 1.897
- 4) 20.00; 1.624
- 5) 25.00; 1.415
- 6) 30.00; 1.266
- 7) 40.00; 1.086
- 8) 50.00; 0.968
- 9) 60.00; 0.881
- 10) 90.00; 0.734
- 11) 120.00; 0.652
- 12) 180.00; 0.549
- 13) 360.00; 0.408
- 14) 1200.00; 0.180

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 11900.00 TO NODE 11901.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 295.79
ELEVATION DATA: UPSTREAM(FEET) = 2369.48 DOWNSTREAM(FEET) = 2332.92

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 7.203
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 3.343
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
RESIDENTIAL ".4 DWELLING/ACRE"	-	1.62	0.30	0.999	0	7.20

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999
SUBAREA RUNOFF(CFS) = 4.44
TOTAL AREA(ACRES) = 1.62 PEAK FLOW RATE(CFS) = 4.44

FLOW PROCESS FROM NODE 11901.00 TO NODE 11902.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2332.92 DOWNSTREAM(FEET) = 2297.70
CHANNEL LENGTH THRU SUBAREA(FEET) = 664.26 CHANNEL SLOPE = 0.0530
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.46
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.467
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.35	0.30	0.906	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.906
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 12.81
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 2.95
AVERAGE FLOW DEPTH(FEET) = 0.40 TRAVEL TIME(MIN.) = 3.75
Tc(MIN.) = 10.95
SUBAREA AREA(ACRES) = 8.35 SUBAREA RUNOFF(CFS) = 16.50
EFFECTIVE AREA(ACRES) = 9.97 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 10.0 PEAK FLOW RATE(CFS) = 19.66
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.52

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.52 FLOW VELOCITY(FEET/SEC.) = 3.41
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11902.00 = 960.05 FEET.

FLOW PROCESS FROM NODE 11902.00 TO NODE 11902.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2297.70 DOWNSTREAM(FEET) = 2263.40
CHANNEL LENGTH THRU SUBAREA(FEET) = 928.77 CHANNEL SLOPE = 0.0369
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 1.03
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.931

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	34.48	0.30	0.904	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.904
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 45.86
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.06
AVERAGE FLOW DEPTH(FEET) = 0.95 TRAVEL TIME(MIN.) = 3.81
Tc(MIN.) = 14.76

SUBAREA AREA(ACRES) = 34.48 SUBAREA RUNOFF(CFS) = 51.49
EFFECTIVE AREA(ACRES) = 44.45 AREA-AVERAGED Fm(INCH/HR) = 0.27
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.91
TOTAL AREA(ACRES) = 44.5 PEAK FLOW RATE(CFS) = 66.34
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.17

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.17 FLOW VELOCITY(FEET/SEC.) = 4.59
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11902.50 = 1888.82 FEET.

FLOW PROCESS FROM NODE 11902.50 TO NODE 11903.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2263.40 DOWNSTREAM(FEET) = 2252.14
CHANNEL LENGTH THRU SUBAREA(FEET) = 895.50 CHANNEL SLOPE = 0.0126
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 1.81
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.669

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	23.65	0.30	0.958	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.958
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 81.06
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.38
AVERAGE FLOW DEPTH(FEET) = 1.77 TRAVEL TIME(MIN.) = 4.42

Tc(MIN.) = 19.18
SUBAREA AREA(ACRES) = 23.65 SUBAREA RUNOFF(CFS) = 29.40
EFFECTIVE AREA(ACRES) = 68.10 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 68.1 PEAK FLOW RATE(CFS) = 85.26
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.82

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.82 FLOW VELOCITY(FEET/SEC.) = 3.43
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11903.00 = 2784.32 FEET.

FLOW PROCESS FROM NODE 11903.00 TO NODE 11904.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2252.14 DOWNSTREAM(FEET) = 2186.04
CHANNEL LENGTH THRU SUBAREA(FEET) = 1924.35 CHANNEL SLOPE = 0.0343
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 1.73
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.411

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	68.53	0.30	0.961	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.961
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 120.00
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.39
AVERAGE FLOW DEPTH(FEET) = 1.67 TRAVEL TIME(MIN.) = 5.95
Tc(MIN.) = 25.13

SUBAREA AREA(ACRES) = 68.53 SUBAREA RUNOFF(CFS) = 69.26
EFFECTIVE AREA(ACRES) = 136.63 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94
TOTAL AREA(ACRES) = 136.6 PEAK FLOW RATE(CFS) = 138.74
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.81

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.81 FLOW VELOCITY(FEET/SEC.) = 5.65
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11904.00 = 4708.67 FEET.

FLOW PROCESS FROM NODE 11904.00 TO NODE 11905.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2186.04 DOWNSTREAM(FEET) = 1957.34
CHANNEL LENGTH THRU SUBAREA(FEET) = 1926.87 CHANNEL SLOPE = 0.1187
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 1.44

* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.307
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	63.15	0.30	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 167.37
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 9.16
 AVERAGE FLOW DEPTH (FEET) = 1.42 TRAVEL TIME (MIN.) = 3.50
 Tc (MIN.) = 28.63
 SUBAREA AREA (ACRES) = 63.15 SUBAREA RUNOFF (CFS) = 57.22
 EFFECTIVE AREA (ACRES) = 199.78 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
 TOTAL AREA (ACRES) = 199.8 PEAK FLOW RATE (CFS) = 183.12
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 1.49
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 1.49 FLOW VELOCITY (FEET/SEC.) = 9.45
 LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11905.00 = 6635.54 FEET.

 FLOW PROCESS FROM NODE 11905.00 TO NODE 11906.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

 ELEVATION DATA: UPSTREAM (FEET) = 1957.34 DOWNSTREAM (FEET) = 1244.16
 CHANNEL LENGTH THRU SUBAREA (FEET) = 2498.96 CHANNEL SLOPE = 0.2854
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 1.30
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.235
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	84.87	0.30	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 218.85
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 13.46
 AVERAGE FLOW DEPTH (FEET) = 1.29 TRAVEL TIME (MIN.) = 3.09
 Tc (MIN.) = 31.73
 SUBAREA AREA (ACRES) = 84.87 SUBAREA RUNOFF (CFS) = 71.42
 EFFECTIVE AREA (ACRES) = 284.65 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA (ACRES) = 284.6 PEAK FLOW RATE (CFS) = 241.62
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 1.36
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 1.36 FLOW VELOCITY (FEET/SEC.) = 13.93
 LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11906.00 = 9134.50 FEET.

FLOW PROCESS FROM NODE 11906.00 TO NODE 11920.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

 ELEVATION DATA: UPSTREAM (FEET) = 1244.16 DOWNSTREAM (FEET) = 873.95
 CHANNEL LENGTH THRU SUBAREA (FEET) = 3370.75 CHANNEL SLOPE = 0.1098
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 2.10
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.142
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	199.43	0.30	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 317.23
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 10.84
 AVERAGE FLOW DEPTH (FEET) = 2.07 TRAVEL TIME (MIN.) = 5.18
 Tc (MIN.) = 36.91
 SUBAREA AREA (ACRES) = 199.43 SUBAREA RUNOFF (CFS) = 151.06
 EFFECTIVE AREA (ACRES) = 484.08 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
 TOTAL AREA (ACRES) = 484.1 PEAK FLOW RATE (CFS) = 368.78
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 2.25
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 2.25 FLOW VELOCITY (FEET/SEC.) = 11.33
 LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11920.00 = 12505.25 FEET.

 FLOW PROCESS FROM NODE 11906.00 TO NODE 11920.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

 TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
 TIME OF CONCENTRATION (MIN.) = 36.91
 RAINFALL INTENSITY (INCH/HR) = 1.14
 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.98
 EFFECTIVE STREAM AREA (ACRES) = 484.08
 TOTAL STREAM AREA (ACRES) = 484.08
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 368.78

 FLOW PROCESS FROM NODE 11910.00 TO NODE 11911.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

 INITIAL SUBAREA FLOW-LENGTH (FEET) = 517.62
 ELEVATION DATA: UPSTREAM (FEET) = 2531.88 DOWNSTREAM (FEET) = 2441.33

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
 SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 12.185
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.293
 SUBAREA Tc AND LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)
 NATURAL FAIR COVER
 "CHAPARRAL,BROADLEAF" - 3.46 0.30 1.000 0 12.19
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA RUNOFF(CFS) = 6.21
 TOTAL AREA(ACRES) = 3.46 PEAK FLOW RATE(CFS) = 6.21

 FLOW PROCESS FROM NODE 11911.00 TO NODE 11912.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2441.33 DOWNSTREAM(FEET) = 2382.20
 CHANNEL LENGTH THRU SUBAREA(FEET) = 397.30 CHANNEL SLOPE = 0.1488
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 0.28
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.047

SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 5.79 0.30 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 10.78
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.79
 AVERAGE FLOW DEPTH(FEET) = 0.27 TRAVEL TIME(MIN.) = 1.75
 Tc(MIN.) = 13.93
 SUBAREA AREA(ACRES) = 5.79 SUBAREA RUNOFF(CFS) = 9.11
 EFFECTIVE AREA(ACRES) = 9.25 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 9.2 PEAK FLOW RATE(CFS) = 14.55
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 0.32

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 0.32 FLOW VELOCITY(FEET/SEC.) = 4.23
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11912.00 = 914.92 FEET.

 FLOW PROCESS FROM NODE 11912.00 TO NODE 11913.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2382.20 DOWNSTREAM(FEET) = 2263.77
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1891.47 CHANNEL SLOPE = 0.0626
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 0.93

* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.609
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 54.30 0.30 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 46.93
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.91
 AVERAGE FLOW DEPTH(FEET) = 0.82 TRAVEL TIME(MIN.) = 6.42
 Tc(MIN.) = 20.35
 SUBAREA AREA(ACRES) = 54.30 SUBAREA RUNOFF(CFS) = 63.98
 EFFECTIVE AREA(ACRES) = 63.55 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 63.5 PEAK FLOW RATE(CFS) = 74.88
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 1.08

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 1.08 FLOW VELOCITY(FEET/SEC.) = 5.71
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11913.00 = 2806.39 FEET.

 FLOW PROCESS FROM NODE 11913.00 TO NODE 11914.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2263.77 DOWNSTREAM(FEET) = 1845.23
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1957.31 CHANNEL SLOPE = 0.2138
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 0.96
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.470

SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 65.14 0.30 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 109.23
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.77
 AVERAGE FLOW DEPTH(FEET) = 0.94 TRAVEL TIME(MIN.) = 3.34
 Tc(MIN.) = 23.69
 SUBAREA AREA(ACRES) = 65.14 SUBAREA RUNOFF(CFS) = 68.57
 EFFECTIVE AREA(ACRES) = 128.69 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 128.7 PEAK FLOW RATE(CFS) = 135.47
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 1.07

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 1.07 FLOW VELOCITY(FEET/SEC.) = 10.48
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11914.00 = 4763.70 FEET.

FLOW PROCESS FROM NODE 11914.00 TO NODE 11915.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1845.23 DOWNSTREAM(FEET) = 1557.21
CHANNEL LENGTH THRU SUBAREA(FEET) = 1686.78 CHANNEL SLOPE = 0.1708
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 1.32
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.374

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE, SCS SOIL, AREA, Fp, Ap, SCS. Row 1: LAND USE, GROUP, (ACRES), (INCH/HR), (DECIMAL), CN. Row 2: USER-DEFINED, -, 78.52, 0.30, 1.000, -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 173.44
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.52
AVERAGE FLOW DEPTH(FEET) = 1.31 TRAVEL TIME(MIN.) = 2.67
Tc(MIN.) = 26.37

SUBAREA AREA(ACRES) = 78.52 SUBAREA RUNOFF(CFS) = 75.92
EFFECTIVE AREA(ACRES) = 207.21 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 207.2 PEAK FLOW RATE(CFS) = 200.34
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.42

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.42 FLOW VELOCITY(FEET/SEC.) = 11.02
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11915.00 = 6450.48 FEET.

FLOW PROCESS FROM NODE 11915.00 TO NODE 11916.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1557.21 DOWNSTREAM(FEET) = 1403.38
CHANNEL LENGTH THRU SUBAREA(FEET) = 1909.39 CHANNEL SLOPE = 0.0806
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 1.91
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.267

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE, SCS SOIL, AREA, Fp, Ap, SCS. Row 1: LAND USE, GROUP, (ACRES), (INCH/HR), (DECIMAL), CN. Row 2: USER-DEFINED, -, 70.48, 0.30, 1.000, -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 231.03
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.84
AVERAGE FLOW DEPTH(FEET) = 1.89 TRAVEL TIME(MIN.) = 3.60
Tc(MIN.) = 29.97

SUBAREA AREA(ACRES) = 70.48 SUBAREA RUNOFF(CFS) = 61.34
EFFECTIVE AREA(ACRES) = 277.69 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 277.7 PEAK FLOW RATE(CFS) = 241.68
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.94

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.94 FLOW VELOCITY(FEET/SEC.) = 8.97
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11916.00 = 8359.87 FEET.

FLOW PROCESS FROM NODE 11916.00 TO NODE 11917.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1403.38 DOWNSTREAM(FEET) = 1079.99
CHANNEL LENGTH THRU SUBAREA(FEET) = 1945.82 CHANNEL SLOPE = 0.1662
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 1.93
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.221

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE, SCS SOIL, AREA, Fp, Ap, SCS. Row 1: LAND USE, GROUP, (ACRES), (INCH/HR), (DECIMAL), CN. Row 2: USER-DEFINED, -, 232.20, 0.30, 1.000, -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 337.93
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.78
AVERAGE FLOW DEPTH(FEET) = 1.91 TRAVEL TIME(MIN.) = 2.54
Tc(MIN.) = 32.50

SUBAREA AREA(ACRES) = 232.20 SUBAREA RUNOFF(CFS) = 192.47
EFFECTIVE AREA(ACRES) = 509.89 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 509.9 PEAK FLOW RATE(CFS) = 422.64
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.16

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.16 FLOW VELOCITY(FEET/SEC.) = 13.65
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11917.00 = 10305.69 FEET.

FLOW PROCESS FROM NODE 11917.00 TO NODE 11920.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1079.99 DOWNSTREAM(FEET) = 873.95
CHANNEL LENGTH THRU SUBAREA(FEET) = 2563.91 CHANNEL SLOPE = 0.0804
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 2.77
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.150

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE, SCS SOIL, AREA, Fp, Ap, SCS. Row 1: LAND USE, GROUP, (ACRES), (INCH/HR), (DECIMAL), CN

USER-DEFINED - 110.82 0.30 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 465.04
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 10.83
 AVERAGE FLOW DEPTH (FEET) = 2.76 TRAVEL TIME (MIN.) = 3.95
 Tc (MIN.) = 36.45
 SUBAREA AREA (ACRES) = 110.82 SUBAREA RUNOFF (CFS) = 84.77
 EFFECTIVE AREA (ACRES) = 620.71 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 620.7 PEAK FLOW RATE (CFS) = 474.83
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 2.80

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 2.80 FLOW VELOCITY (FEET/SEC.) = 10.90
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11920.00 = 12869.60 FEET.

 FLOW PROCESS FROM NODE 11917.00 TO NODE 11920.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<
 =====

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
 TIME OF CONCENTRATION (MIN.) = 36.45
 RAINFALL INTENSITY (INCH/HR) = 1.15
 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30
 AREA-AVERAGED Ap = 1.00
 EFFECTIVE STREAM AREA (ACRES) = 620.71
 TOTAL STREAM AREA (ACRES) = 620.71
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 474.83

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	368.78	36.91	1.142	0.30 (0.30)	0.98	484.1	11900.00
2	474.83	36.45	1.150	0.30 (0.30)	1.00	620.7	11910.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	842.56	36.45	1.150	0.30 (0.30)	0.99	1098.7	11910.00
2	838.95	36.91	1.142	0.30 (0.30)	0.99	1104.8	11900.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
 PEAK FLOW RATE (CFS) = 842.56 Tc (MIN.) = 36.45
 EFFECTIVE AREA (ACRES) = 1098.72 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 1104.8
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11920.00 = 12869.60 FEET.

 FLOW PROCESS FROM NODE 11920.00 TO NODE 11921.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<
 =====

ELEVATION DATA: UPSTREAM (FEET) = 873.95 DOWNSTREAM (FEET) = 827.94
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1417.25 CHANNEL SLOPE = 0.0325
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 4.83
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.104
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	107.47	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 881.46
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 9.29
 AVERAGE FLOW DEPTH (FEET) = 4.83 TRAVEL TIME (MIN.) = 2.54
 Tc (MIN.) = 38.99
 SUBAREA AREA (ACRES) = 107.47 SUBAREA RUNOFF (CFS) = 77.79
 EFFECTIVE AREA (ACRES) = 1206.19 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 1212.3 PEAK FLOW RATE (CFS) = 875.11
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 4.81

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 4.81 FLOW VELOCITY (FEET/SEC.) = 9.27
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11921.00 = 14286.85 FEET.

 FLOW PROCESS FROM NODE 11921.00 TO NODE 11922.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<
 =====

ELEVATION DATA: UPSTREAM (FEET) = 827.94 DOWNSTREAM (FEET) = 753.55
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1886.43 CHANNEL SLOPE = 0.0394
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 4.90
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.062
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	344.27	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 993.16
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 10.30
 AVERAGE FLOW DEPTH (FEET) = 4.88 TRAVEL TIME (MIN.) = 3.05
 Tc (MIN.) = 42.04
 SUBAREA AREA (ACRES) = 344.27 SUBAREA RUNOFF (CFS) = 236.08
 EFFECTIVE AREA (ACRES) = 1550.46 AREA-AVERAGED Fm (INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 1556.5 PEAK FLOW RATE(CFS) = 1065.30
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 5.05

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 5.05 FLOW VELOCITY(FEET/SEC.) = 10.48
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11922.00 = 16173.28 FEET.

FLOW PROCESS FROM NODE 11922.00 TO NODE 11923.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 753.55 DOWNSTREAM(FEET) = 641.58
CHANNEL LENGTH THRU SUBAREA(FEET) = 2860.88 CHANNEL SLOPE = 0.0391
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 5.19
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.009

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	165.18	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1117.99

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.59

AVERAGE FLOW DEPTH(FEET) = 5.18 TRAVEL TIME(MIN.) = 4.50

Tc(MIN.) = 46.55

SUBAREA AREA(ACRES) = 165.18 SUBAREA RUNOFF(CFS) = 105.37

EFFECTIVE AREA(ACRES) = 1715.64 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 1721.7 PEAK FLOW RATE(CFS) = 1096.54

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 5.13

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 5.13 FLOW VELOCITY(FEET/SEC.) = 10.55
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11923.00 = 19034.16 FEET.

FLOW PROCESS FROM NODE 11923.00 TO NODE 11924.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 641.58 DOWNSTREAM(FEET) = 579.89
CHANNEL LENGTH THRU SUBAREA(FEET) = 1844.02 CHANNEL SLOPE = 0.0335
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 5.65

* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.973

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	165.18	0.30	1.000	-

LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 433.73 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1227.99
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.25
AVERAGE FLOW DEPTH(FEET) = 5.63 TRAVEL TIME(MIN.) = 3.00
Tc(MIN.) = 49.54
SUBAREA AREA(ACRES) = 433.73 SUBAREA RUNOFF(CFS) = 262.88
EFFECTIVE AREA(ACRES) = 2149.37 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 2155.4 PEAK FLOW RATE(CFS) = 1304.79
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 5.80

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 5.80 FLOW VELOCITY(FEET/SEC.) = 10.41
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11924.00 = 20878.18 FEET.

FLOW PROCESS FROM NODE 11924.00 TO NODE 11925.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 579.89 DOWNSTREAM(FEET) = 494.12
CHANNEL LENGTH THRU SUBAREA(FEET) = 2756.15 CHANNEL SLOPE = 0.0311
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 6.08

* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.933

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	265.42	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1380.42

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.29

AVERAGE FLOW DEPTH(FEET) = 6.06 TRAVEL TIME(MIN.) = 4.46

Tc(MIN.) = 54.01

SUBAREA AREA(ACRES) = 265.42 SUBAREA RUNOFF(CFS) = 151.26

EFFECTIVE AREA(ACRES) = 2414.79 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 2420.9 PEAK FLOW RATE(CFS) = 1378.20

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 6.06

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 6.06 FLOW VELOCITY(FEET/SEC.) = 10.28
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11925.00 = 23634.33 FEET.

FLOW PROCESS FROM NODE 11925.00 TO NODE 11926.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 494.12 DOWNSTREAM(FEET) = 458.40
CHANNEL LENGTH THRU SUBAREA(FEET) = 1922.70 CHANNEL SLOPE = 0.0186
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 6.91

* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.900

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

USER-DEFINED - 97.46 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1404.54

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.54

AVERAGE FLOW DEPTH(FEET) = 6.91 TRAVEL TIME(MIN.) = 3.75

Tc(MIN.) = 57.76

SUBAREA AREA(ACRES) = 97.46 SUBAREA RUNOFF(CFS) = 52.68

EFFECTIVE AREA(ACRES) = 2512.25 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 2518.3 PEAK FLOW RATE(CFS) = 1378.20

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 6.85

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 6.85 FLOW VELOCITY(FEET/SEC.) = 8.50

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11926.00 = 25557.03 FEET.

FLOW PROCESS FROM NODE 11926.00 TO NODE 11927.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 458.40 DOWNSTREAM(FEET) = 399.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 2170.13 CHANNEL SLOPE = 0.0274

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 6.28

* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.874

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

USER-DEFINED - 53.83 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1392.11

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.84

AVERAGE FLOW DEPTH(FEET) = 6.28 TRAVEL TIME(MIN.) = 3.68

Tc(MIN.) = 61.44

SUBAREA AREA(ACRES) = 53.83 SUBAREA RUNOFF(CFS) = 27.81

EFFECTIVE AREA(ACRES) = 2566.08 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 2572.1 PEAK FLOW RATE(CFS) = 1378.20

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 6.25

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 6.25 FLOW VELOCITY(FEET/SEC.) = 9.81

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 27727.16 FEET.

FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P401XX10.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

Table with columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Fp (Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 2 rows of data and a total area row.

FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

Table with columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp (Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 2 rows of data and a longest flowpath row.

** MEMORY BANK # 1 CONFLUENCE DATA **

Table with columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp (Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 2 rows of data and a longest flowpath row.

** PEAK FLOW RATE TABLE **

Table with columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp (Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 4 rows of data and a total area row.

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 1692.35 Tc(MIN.) = 61.439

EFFECTIVE AREA(ACRES) = 3220.28 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 3226.4
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 27727.16 FEET.

FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<<

FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 399.00 DOWNSTREAM(FEET) = 384.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 986.26 CHANNEL SLOPE = 0.0152
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 7.89
CHANNEL FLOW THRU SUBAREA(CFS) = 1692.35
FLOW VELOCITY(FEET/SEC.) = 8.32 FLOW DEPTH(FEET) = 7.89
TRAVEL TIME(MIN.) = 1.98 Tc(MIN.) = 63.42
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.50 = 28713.42 FEET.

FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<

MAINLINE Tc(MIN.) = 63.42
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.864
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"WOODLAND,GRASS" B 2.40 0.30 1.000 65
NATURAL FAIR COVER
"WOODLAND,GRASS" B 1.70 0.30 1.000 65
NATURAL FAIR COVER
"WOODLAND,GRASS" B 1.50 0.30 1.000 65
NATURAL FAIR COVER
"OPEN BRUSH" B 1.30 0.30 1.000 66
NATURAL FAIR COVER
"OPEN BRUSH" B 0.90 0.30 1.000 66
NATURAL FAIR COVER
"GRASS" B 0.60 0.30 1.000 69
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 8.40 SUBAREA RUNOFF(CFS) = 4.27
EFFECTIVE AREA(ACRES) = 3228.68 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 3234.8 PEAK FLOW RATE(CFS) = 1692.35
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<

MAINLINE Tc(MIN.) = 63.42
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.864
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"OPEN BRUSH" B 0.30 0.30 1.000 66
NATURAL FAIR COVER
"OPEN BRUSH" B 0.10 0.30 1.000 66
NATURAL FAIR COVER
"WOODLAND,GRASS" B 0.10 0.30 1.000 65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 0.50 SUBAREA RUNOFF(CFS) = 0.25
EFFECTIVE AREA(ACRES) = 3229.18 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 3235.2 PEAK FLOW RATE(CFS) = 1692.35
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<

MAINLINE Tc(MIN.) = 63.42
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.864
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"WOODLAND,GRASS" B 0.80 0.30 1.000 65
NATURAL FAIR COVER
"WOODLAND,GRASS" B 0.70 0.30 1.000 65
NATURAL FAIR COVER
"OPEN BRUSH" B 0.20 0.30 1.000 66
NATURAL FAIR COVER
"WOODLAND,GRASS" B 0.20 0.30 1.000 65
NATURAL FAIR COVER
"OPEN BRUSH" B 0.10 0.30 1.000 66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 2.00 SUBAREA RUNOFF(CFS) = 1.02
EFFECTIVE AREA(ACRES) = 3231.18 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 3237.2 PEAK FLOW RATE(CFS) = 1692.35
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 11927.50 TO NODE 11928.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 384.00 DOWNSTREAM(FEET) = 359.00

CHANNEL LENGTH THRU SUBAREA (FEET) = 647.19 CHANNEL SLOPE = 0.0386
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 6.38
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.860
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	78.01	0.30	0.984	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.984
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 1712.17
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 11.79
 AVERAGE FLOW DEPTH (FEET) = 6.38 TRAVEL TIME (MIN.) = 0.92
 Tc (MIN.) = 64.33
 SUBAREA AREA (ACRES) = 78.01 SUBAREA RUNOFF (CFS) = 39.64
 EFFECTIVE AREA (ACRES) = 3309.19 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 3315.3 PEAK FLOW RATE (CFS) = 1692.35
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 6.34

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 6.34 FLOW VELOCITY (FEET/SEC.) = 11.76
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11928.00 = 29360.61 FEET.

FLOW PROCESS FROM NODE 11928.00 TO NODE 11928.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 64.33
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.860
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "WOODLAND, GRASS"	B	1.10	0.30	1.000	65
NATURAL FAIR COVER "OPEN BRUSH"	B	0.60	0.30	1.000	66

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 1.70 SUBAREA RUNOFF (CFS) = 0.86
 EFFECTIVE AREA (ACRES) = 3310.89 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 3317.0 PEAK FLOW RATE (CFS) = 1692.35
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 359.00 DOWNSTREAM (FEET) = 341.63
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1322.66 CHANNEL SLOPE = 0.0131

GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 8.17
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.846
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.18	0.30	0.890	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.890
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 1694.48
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.88
 AVERAGE FLOW DEPTH (FEET) = 8.17 TRAVEL TIME (MIN.) = 2.80
 Tc (MIN.) = 67.13
 SUBAREA AREA (ACRES) = 8.18 SUBAREA RUNOFF (CFS) = 4.26
 EFFECTIVE AREA (ACRES) = 3319.07 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 3325.1 PEAK FLOW RATE (CFS) = 1692.35
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 8.16

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 8.16 FLOW VELOCITY (FEET/SEC.) = 7.88
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11929.00 = 30683.27 FEET.

FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 67.13
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.846
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	1.90	0.30	1.000	66
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.60	0.30	1.000	65

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 2.50 SUBAREA RUNOFF (CFS) = 1.23
 EFFECTIVE AREA (ACRES) = 3321.57 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 3327.6 PEAK FLOW RATE (CFS) = 1692.35
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 3 <<<<<

FLOW PROCESS FROM NODE 11841.00 TO NODE 12527.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: S18X10.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11616.90	44.00	0.30 (0.30)	1.00	7599.6	11801.00
2	12892.03	58.27	0.30 (0.30)	1.00	10804.1	11530.00
3	13438.67	64.50	0.30 (0.30)	1.00	12758.4	11701.00
4	13628.71	66.49	0.30 (0.30)	1.00	13434.8	11000.00
5	15265.02	77.21	0.30 (0.30)	1.00	18437.6	11330.00
6	15528.32	79.96	0.30 (0.30)	1.00	19719.4	10800.00
7	15902.78	82.44	0.30 (0.30)	1.00	21039.3	11300.00
8	16140.10	85.75	0.30 (0.30)	1.00	22434.4	10630.00
9	15918.65	96.09	0.30 (0.30)	1.00	25763.3	11620.00
10	15868.02	97.88	0.30 (0.30)	1.00	26303.3	11600.00
11	15636.46	103.56	0.30 (0.30)	1.00	27777.9	11111.00
12	15531.21	106.40	0.30 (0.30)	1.00	28370.9	10500.00
13	15352.00	110.70	0.30 (0.30)	1.00	29161.8	10710.00
14	15201.33	113.32	0.30 (0.30)	1.00	29547.2	10410.00
15	14857.39	118.86	0.30 (0.30)	1.00	30260.6	10700.00
16	14446.26	125.40	0.30 (0.30)	1.00	31040.6	10400.00
17	14178.55	129.18	0.30 (0.30)	1.00	31414.4	10200.00
18	13775.63	136.31	0.30 (0.30)	1.00	32035.9	10320.00
19	13411.70	140.89	0.30 (0.30)	1.00	32196.8	10210.00
20	11422.66	173.20	0.30 (0.30)	1.00	32916.6	10100.00

TOTAL AREA (ACRES) = 32916.6

FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: S25X10.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4457.80	74.17	0.30 (0.30)	0.99	6215.9	12500.00
2	4830.00	89.61	0.30 (0.30)	0.99	8185.8	12300.00
3	4886.59	91.31	0.30 (0.30)	0.99	8494.7	12330.00
4	4976.75	94.56	0.30 (0.30)	0.98	9045.8	12410.00
5	5066.75	99.26	0.30 (0.29)	0.98	9767.7	12400.00
6	5124.87	104.67	0.30 (0.29)	0.98	10457.3	12211.00
7	5154.35	109.58	0.30 (0.29)	0.98	11071.5	12201.00
8	5066.62	114.70	0.30 (0.29)	0.98	11560.6	12111.00
9	5049.30	118.21	0.30 (0.29)	0.98	11939.4	12231.00
10	5009.12	121.09	0.30 (0.29)	0.98	12207.1	12101.10
11	4983.48	122.44	0.30 (0.29)	0.98	12317.7	12261.00
12	4583.59	136.43	0.30 (0.29)	0.98	13120.1	12010.00
13	4254.50	145.50	0.30 (0.29)	0.98	13237.1	12000.00

TOTAL AREA (ACRES) = 13237.1

FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4457.80	74.17	0.30 (0.30)	0.99	6215.9	12500.00
2	4830.00	89.61	0.30 (0.30)	0.99	8185.8	12300.00
3	4886.59	91.31	0.30 (0.30)	0.99	8494.7	12330.00
4	4976.75	94.56	0.30 (0.30)	0.98	9045.8	12410.00
5	5066.75	99.26	0.30 (0.29)	0.98	9767.7	12400.00
6	5124.87	104.67	0.30 (0.29)	0.98	10457.3	12211.00
7	5154.35	109.58	0.30 (0.29)	0.98	11071.5	12201.00
8	5066.62	114.70	0.30 (0.29)	0.98	11560.6	12111.00
9	5049.30	118.21	0.30 (0.29)	0.98	11939.4	12231.00
10	5009.12	121.09	0.30 (0.29)	0.98	12207.1	12101.10
11	4983.48	122.44	0.30 (0.29)	0.98	12317.7	12261.00
12	4583.59	136.43	0.30 (0.29)	0.98	13120.1	12010.00
13	4254.50	145.50	0.30 (0.29)	0.98	13237.1	12000.00

TOTAL AREA (ACRES) = 13237.1

FLOW PROCESS FROM NODE 11841.00 TO NODE 12527.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4457.80	74.17	0.812	0.30 (0.30)	0.99	6215.9	12500.00
2	4830.00	89.61	0.736	0.30 (0.30)	0.99	8185.8	12300.00
3	4886.59	91.31	0.730	0.30 (0.30)	0.99	8494.7	12330.00
4	4976.75	94.56	0.722	0.30 (0.30)	0.98	9045.8	12410.00
5	5066.75	99.26	0.709	0.30 (0.29)	0.98	9767.7	12400.00
6	5124.87	104.67	0.694	0.30 (0.29)	0.98	10457.3	12211.00
7	5154.35	109.58	0.680	0.30 (0.29)	0.98	11071.5	12201.00
8	5066.62	114.70	0.666	0.30 (0.29)	0.98	11560.6	12111.00
9	5049.30	118.21	0.657	0.30 (0.29)	0.98	11939.4	12231.00
10	5009.12	121.09	0.650	0.30 (0.29)	0.98	12207.1	12101.10
11	4983.48	122.44	0.648	0.30 (0.29)	0.98	12317.7	12261.00
12	4583.59	136.43	0.624	0.30 (0.29)	0.98	13120.1	12010.00
13	4254.50	145.50	0.608	0.30 (0.29)	0.98	13237.1	12000.00

LONGEST FLOWPATH FROM NODE 12000.00 TO NODE 12527.00 = 77156.98 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11616.90	44.00	1.039	0.30 (0.30)	1.00	7599.6	11801.00
2	12892.03	58.27	0.896	0.30 (0.30)	1.00	10804.1	11530.00
3	13438.67	64.50	0.859	0.30 (0.30)	1.00	12758.4	11701.00
4	13628.71	66.49	0.849	0.30 (0.30)	1.00	13434.8	11000.00
5	15265.02	77.21	0.797	0.30 (0.30)	1.00	18437.6	11330.00
6	15528.32	79.96	0.783	0.30 (0.30)	1.00	19719.4	10800.00
7	15902.78	82.44	0.771	0.30 (0.30)	1.00	21039.3	11300.00
8	16140.10	85.75	0.755	0.30 (0.30)	1.00	22434.4	10630.00
9	15918.65	96.09	0.717	0.30 (0.30)	1.00	25763.3	11620.00
10	15868.02	97.88	0.712	0.30 (0.30)	1.00	26303.3	11600.00
11	15636.46	103.56	0.697	0.30 (0.30)	1.00	27777.9	11111.00
12	15531.21	106.40	0.689	0.30 (0.30)	1.00	28370.9	10500.00
13	15352.00	110.70	0.677	0.30 (0.30)	1.00	29161.8	10710.00

14 15201.33 113.32 0.670 0.30(0.30) 1.00 29547.2 10410.00
 15 14857.39 118.86 0.655 0.30(0.30) 1.00 30260.6 10700.00
 16 14446.26 125.40 0.643 0.30(0.30) 1.00 31040.6 10400.00
 17 14178.55 129.18 0.636 0.30(0.30) 1.00 31414.4 10200.00
 18 13775.63 136.31 0.624 0.30(0.30) 1.00 32035.9 10320.00
 19 13411.70 140.89 0.616 0.30(0.30) 1.00 32196.8 10210.00
 20 11422.66 173.20 0.561 0.30(0.30) 1.00 32916.6 10100.00
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12527.00 = 97868.13 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15427.07	44.00	1.039	0.30(0.30)	0.99	11287.3	11801.00
2	16968.09	58.27	0.896	0.30(0.30)	0.99	15687.3	11530.00
3	17671.53	64.50	0.859	0.30(0.30)	0.99	18163.7	11701.00
4	17916.64	66.49	0.849	0.30(0.30)	0.99	19007.1	11000.00
5	19259.36	74.17	0.812	0.30(0.30)	0.99	23236.5	12500.00
6	19795.97	77.21	0.797	0.30(0.30)	0.99	25040.6	11330.00
7	20125.68	79.96	0.783	0.30(0.30)	0.99	26674.0	10800.00
8	20559.80	82.44	0.771	0.30(0.30)	0.99	28309.7	11300.00
9	20877.05	85.75	0.755	0.30(0.30)	0.99	30127.8	10630.00
10	20887.39	89.61	0.736	0.30(0.30)	0.99	31863.6	12300.00
11	20907.71	91.31	0.730	0.30(0.30)	0.99	32717.7	12330.00
12	20928.11	94.56	0.722	0.30(0.30)	0.99	34317.4	12410.00
13	20924.67	96.09	0.717	0.30(0.30)	0.99	35043.8	11620.00
14	20908.49	97.88	0.712	0.30(0.30)	0.99	35860.1	11600.00
15	20878.88	99.26	0.709	0.30(0.30)	0.99	36427.0	12400.00
16	20749.46	103.56	0.697	0.30(0.30)	0.99	38094.4	11111.00
17	20720.29	104.67	0.694	0.30(0.30)	0.99	38466.4	12211.00
18	20666.45	106.40	0.689	0.30(0.30)	0.99	39044.4	10500.00
19	20552.81	109.58	0.680	0.30(0.30)	0.99	40028.3	12201.00
20	20487.24	110.70	0.677	0.30(0.30)	0.99	40339.9	10710.00
21	20291.57	113.32	0.670	0.30(0.30)	0.99	40976.1	10410.00
22	20182.47	114.70	0.666	0.30(0.30)	0.99	41285.1	12111.00
23	19946.92	118.21	0.657	0.30(0.30)	0.99	42116.5	12231.00
24	19897.64	118.86	0.655	0.30(0.30)	0.99	42260.3	10700.00
25	19726.52	121.09	0.650	0.30(0.30)	0.99	42733.2	12101.10
26	19615.75	122.44	0.648	0.30(0.30)	0.99	43005.4	12261.00
27	19345.12	125.40	0.643	0.30(0.30)	0.99	43528.1	10400.00
28	18969.58	129.18	0.636	0.30(0.30)	0.99	44118.3	10200.00
29	18362.79	136.31	0.624	0.30(0.30)	0.99	45148.8	10320.00
30	18349.32	136.43	0.624	0.30(0.30)	0.99	45160.4	12010.00
31	17833.67	140.89	0.616	0.30(0.30)	0.99	45374.3	10210.00
32	17382.11	145.50	0.608	0.30(0.30)	0.99	45536.7	12000.00
33	15034.06	173.20	0.561	0.30(0.30)	0.99	46153.7	10100.00
TOTAL AREA (ACRES) =		46153.7					

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 20928.11 Tc(MIN.) = 94.562
 EFFECTIVE AREA(ACRES) = 34317.40 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 46153.7
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12527.00 = 97868.13 FEET.

 FLOW PROCESS FROM NODE 12527.00 TO NODE 11929.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 347.47 DOWNSTREAM(FEET) = 341.63
 CHANNEL LENGTH THRU SUBAREA(FEET) = 532.38 CHANNEL SLOPE = 0.0110
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 6.93
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.720

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	14.37	0.30	0.987	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.987
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 20930.85
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.87
 AVERAGE FLOW DEPTH(FEET) = 6.93 TRAVEL TIME(MIN.) = 0.69
 Tc(MIN.) = 95.25
 SUBAREA AREA(ACRES) = 14.37 SUBAREA RUNOFF(CFS) = 5.48
 EFFECTIVE AREA(ACRES) = 34331.77 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 46168.0 PEAK FLOW RATE(CFS) = 20928.11

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 6.93

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 6.93 FLOW VELOCITY(FEET/SEC.) = 12.87
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

=====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15427.07	44.77	1.030	0.30(0.30)	0.99	11301.7	11801.00
2	16968.09	59.01	0.890	0.30(0.30)	0.99	15701.7	11530.00
3	17671.53	65.23	0.855	0.30(0.30)	0.99	18178.1	11701.00
4	17916.64	67.22	0.846	0.30(0.30)	0.99	19021.5	11000.00
5	19259.36	74.88	0.808	0.30(0.30)	0.99	23250.9	12500.00
6	19795.97	77.91	0.793	0.30(0.30)	0.99	25055.0	11330.00
7	20125.68	80.66	0.780	0.30(0.30)	0.99	26688.3	10800.00
8	20559.80	83.13	0.768	0.30(0.30)	0.99	28324.0	11300.00
9	20877.05	86.44	0.751	0.30(0.30)	0.99	30142.2	10630.00
10	20887.39	90.30	0.733	0.30(0.30)	0.99	31878.0	12300.00
11	20907.71	92.00	0.729	0.30(0.30)	0.99	32732.0	12330.00
12	20928.11	95.25	0.720	0.30(0.30)	0.99	34331.8	12410.00
13	20924.67	96.78	0.715	0.30(0.30)	0.99	35058.2	11620.00
14	20908.49	98.57	0.711	0.30(0.30)	0.99	35874.5	11600.00
15	20878.88	99.95	0.707	0.30(0.30)	0.99	36441.4	12400.00
16	20749.46	104.26	0.695	0.30(0.30)	0.99	38108.8	11111.00
17	20720.29	105.36	0.692	0.30(0.30)	0.99	38480.8	12211.00
18	20666.45	107.09	0.687	0.30(0.30)	0.99	39058.8	10500.00

33	19364.66	137.03	0.623	0.30	(0.30)	0.99	48490.9	10320.00
34	19350.52	137.15	0.623	0.30	(0.30)	0.99	48502.4	12010.00
35	18811.18	141.62	0.615	0.30	(0.30)	0.99	48716.3	10210.00
36	18335.06	146.24	0.607	0.30	(0.30)	0.99	48878.7	12000.00
37	15839.68	173.97	0.559	0.30	(0.30)	0.99	49495.7	10100.00

=====
=====
END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 126 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 10-YR EV FEB 2023 ROKAMOTO *

FILE NAME: RU10EV26.DAT
TIME/DATE OF STUDY: 08:26 02/08/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 10.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 3.912
- 2) 10.00; 2.592
- 3) 15.00; 1.893
- 4) 20.00; 1.621
- 5) 25.00; 1.412
- 6) 30.00; 1.265
- 7) 40.00; 1.084
- 8) 50.00; 0.966
- 9) 60.00; 0.879
- 10) 90.00; 0.732
- 11) 120.00; 0.650
- 12) 180.00; 0.547
- 13) 360.00; 0.406
- 14) 1200.00; 0.179

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	(FT)	(FT)	SIDE / SIDE/ WAY	(FT)	(FT)	(FT)	(FT)	(n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU10EV19.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	16173.79	35.33	0.30 (0.30)	0.99	10911.0	40100.00
2	17100.60	44.77	0.30 (0.30)	0.99	13688.7	11801.00
3	18653.61	59.01	0.30 (0.30)	0.99	18684.0	11530.00
4	19672.87	67.62	0.30 (0.30)	0.99	22572.1	11900.00
5	21325.43	77.91	0.30 (0.30)	0.99	28382.6	11330.00
6	22010.08	83.13	0.30 (0.30)	0.99	31651.7	11300.00
7	22277.11	86.44	0.30 (0.30)	0.99	33469.8	10630.00
8	22236.95	92.00	0.30 (0.30)	0.99	36059.7	12330.00
9	22229.80	95.25	0.30 (0.30)	0.99	37659.4	12410.00
10	22182.07	98.57	0.30 (0.30)	0.99	39202.1	11600.00
11	21974.99	104.26	0.30 (0.30)	0.99	41436.4	11111.00
12	21727.41	110.28	0.30 (0.30)	0.99	43370.3	12201.00
13	21434.54	114.02	0.30 (0.30)	0.99	44318.1	10410.00
14	21048.44	118.91	0.30 (0.30)	0.99	45458.5	12231.00
15	20404.98	126.11	0.30 (0.30)	0.99	46870.1	10400.00
16	20009.38	129.89	0.30 (0.30)	0.99	47460.3	10200.00
17	19364.66	137.03	0.30 (0.30)	0.99	48490.9	10320.00
18	18811.18	141.62	0.30 (0.30)	0.99	48716.3	10210.00
19	18335.06	146.24	0.30 (0.30)	0.99	48878.7	12000.00
20	15839.68	173.97	0.30 (0.30)	0.99	49495.7	10100.00
TOTAL AREA(ACRES) =						49495.7

FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	16173.79	35.33	0.30 (0.30)	0.99	10911.0	40100.00
2	17100.60	44.77	0.30 (0.30)	0.99	13688.7	11801.00
3	18653.61	59.01	0.30 (0.30)	0.99	18684.0	11530.00
4	19672.87	67.62	0.30 (0.30)	0.99	22572.1	11900.00
5	21325.43	77.91	0.30 (0.30)	0.99	28382.6	11330.00
6	22010.08	83.13	0.30 (0.30)	0.99	31651.7	11300.00
7	22277.11	86.44	0.30 (0.30)	0.99	33469.8	10630.00
8	22236.95	92.00	0.30 (0.30)	0.99	36059.7	12330.00
9	22229.80	95.25	0.30 (0.30)	0.99	37659.4	12410.00
10	22182.07	98.57	0.30 (0.30)	0.99	39202.1	11600.00
11	21974.99	104.26	0.30 (0.30)	0.99	41436.4	11111.00
12	21727.41	110.28	0.30 (0.30)	0.99	43370.3	12201.00
13	21434.54	114.02	0.30 (0.30)	0.99	44318.1	10410.00

14	21048.44	118.91	0.30	(0.30)	0.99	45458.5	12231.00
15	20404.98	126.11	0.30	(0.30)	0.99	46870.1	10400.00
16	20009.38	129.89	0.30	(0.30)	0.99	47460.3	10200.00
17	19364.66	137.03	0.30	(0.30)	0.99	48490.9	10320.00
18	18811.18	141.62	0.30	(0.30)	0.99	48716.3	10210.00
19	18335.06	146.24	0.30	(0.30)	0.99	48878.7	12000.00
20	15839.68	173.97	0.30	(0.30)	0.99	49495.7	10100.00

TOTAL AREA (ACRES) = 49495.7

FLOW PROCESS FROM NODE 11929.00 TO NODE 12601.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 341.63 DOWNSTREAM (FEET) = 325.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 1467.93 CHANNEL SLOPE = 0.0113
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 6.03

* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.742

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	0.40	0.30	1.000	66
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.50	0.30	1.000	65
NATURAL FAIR COVER "CHAPARRAL, BROADLEAF"	B	0.90	0.30	1.000	63
NATURAL FAIR COVER "GRASS"	B	0.50	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	11.50	0.30	1.000	66
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.30	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 22279.91

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 16.05

AVERAGE FLOW DEPTH (FEET) = 6.03 TRAVEL TIME (MIN.) = 1.52

Tc (MIN.) = 87.97

SUBAREA AREA (ACRES) = 14.10 SUBAREA RUNOFF (CFS) = 5.61

EFFECTIVE AREA (ACRES) = 33483.91 AREA-AVERAGED Fm (INCH/HR) = 0.30

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA (ACRES) = 49509.8 PEAK FLOW RATE (CFS) = 22277.11

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT (FEET) = 6.03

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 6.03 FLOW VELOCITY (FEET/SEC.) = 16.05

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 3010EVRL.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	67.76	17.31	0.30 (0.29)	0.98	51.1	600.00

TOTAL AREA (ACRES) = 51.1

FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	16173.79	37.03	1.138	0.30 (0.30)	0.99	10925.1	40100.00
2	17100.60	46.44	1.008	0.30 (0.30)	0.99	13702.8	11801.00
3	18653.61	60.63	0.876	0.30 (0.30)	0.99	18698.1	11530.00
4	19672.87	69.21	0.834	0.30 (0.30)	0.99	22586.2	11900.00
5	21325.43	79.46	0.784	0.30 (0.30)	0.99	28396.7	11330.00
6	22010.08	84.66	0.758	0.30 (0.30)	0.99	31665.8	11300.00
7	22277.11	87.97	0.742	0.30 (0.30)	0.99	33483.9	10630.00
8	22236.95	93.52	0.722	0.30 (0.30)	0.99	36073.8	12330.00
9	22229.80	96.78	0.713	0.30 (0.30)	0.99	37673.5	12410.00
10	22182.07	100.10	0.704	0.30 (0.30)	0.99	39216.2	11600.00
11	21974.99	105.79	0.689	0.30 (0.30)	0.99	41450.6	11111.00
12	21727.41	111.81	0.672	0.30 (0.30)	0.99	43384.4	12201.00
13	21434.54	115.56	0.662	0.30 (0.30)	0.99	44332.2	10410.00
14	21048.44	120.47	0.649	0.30 (0.30)	0.99	45472.6	12231.00
15	20404.98	127.69	0.637	0.30 (0.30)	0.99	46884.2	10400.00
16	20009.38	131.47	0.630	0.30 (0.30)	0.99	47474.4	10200.00
17	19364.66	138.63	0.618	0.30 (0.30)	0.99	48505.0	10320.00
18	18811.18	143.23	0.610	0.30 (0.30)	0.99	48730.4	10210.00
19	18335.06	147.87	0.602	0.30 (0.30)	0.99	48892.8	12000.00
20	15839.68	175.69	0.554	0.30 (0.30)	0.99	49509.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	67.76	17.31	1.767	0.30 (0.29)	0.98	51.1	600.00

LONGEST FLOWPATH FROM NODE 600.00 TO NODE 12601.00 = 4850.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13297.29	17.31	1.767	0.30 (0.30)	0.99	5159.0	600.00
2	16212.60	37.03	1.138	0.30 (0.30)	0.99	10976.2	40100.00
3	17133.45	46.44	1.008	0.30 (0.30)	0.99	13753.9	11801.00
4	18680.38	60.63	0.876	0.30 (0.30)	0.99	18749.2	11530.00
5	19697.71	69.21	0.834	0.30 (0.30)	0.99	22637.3	11900.00
6	21347.96	79.46	0.784	0.30 (0.30)	0.99	28447.8	11330.00
7	22031.44	84.66	0.758	0.30 (0.30)	0.99	31716.9	11300.00
8	22297.72	87.97	0.742	0.30 (0.30)	0.99	33535.0	10630.00
9	22256.66	93.52	0.722	0.30 (0.30)	0.99	36124.9	12330.00

ST	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)		(ACRES)	NODE
10	22249.10	96.78	0.713	0.30 (0.30)	0.99	37724.6	12410.00
11	22200.96	100.10	0.704	0.30 (0.30)	0.99	39267.3	11600.00
12	21993.16	105.79	0.689	0.30 (0.30)	0.99	41501.7	11111.00
13	21744.82	111.81	0.672	0.30 (0.30)	0.99	43435.5	12201.00
14	21451.48	115.56	0.662	0.30 (0.30)	0.99	44383.3	10410.00
15	21064.79	120.47	0.649	0.30 (0.30)	0.99	45523.8	12231.00
16	20420.76	127.69	0.637	0.30 (0.30)	0.99	46935.3	10400.00
17	20024.86	131.47	0.630	0.30 (0.30)	0.99	47525.5	10200.00
18	19379.57	138.63	0.618	0.30 (0.30)	0.99	48556.1	10320.00
19	18825.73	143.23	0.610	0.30 (0.30)	0.99	48781.5	10210.00
20	18349.25	147.87	0.602	0.30 (0.30)	0.99	48943.9	12000.00
21	15851.67	175.69	0.554	0.30 (0.30)	0.99	49560.9	10100.00

TOTAL AREA (ACRES) = 49560.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 22297.72 Tc (MIN.) = 87.968
EFFECTIVE AREA (ACRES) = 33535.01 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 49560.9
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

FLOW PROCESS FROM NODE 12601.00 TO NODE 12603.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 325.00 DOWNSTREAM (FEET) = 310.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 1690.00 CHANNEL SLOPE = 0.0089
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 6.47
CHANNEL FLOW THRU SUBAREA (CFS) = 22297.72
FLOW VELOCITY (FEET/SEC.) = 14.82 FLOW DEPTH (FEET) = 6.47
TRAVEL TIME (MIN.) = 1.90 Tc (MIN.) = 89.87
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.45 FEET.

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 4E10EVRL.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM	Q	Tc	Fp (Fm)	Ap	Ae	HEADWATER
NUMBER	(CFS)	(MIN.)	(INCH/HR)		(ACRES)	NODE
1	346.22	9.57	0.30 (0.16)	0.52	148.8	800.00
2	304.47	13.17	0.30 (0.17)	0.57	168.1	818.00
3	283.23	14.36	0.30 (0.17)	0.58	171.0	810.00

TOTAL AREA (ACRES) = 171.0

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)		(ACRES)	NODE
1	13297.29	19.59	1.643	0.30 (0.30)	0.99	5159.0	600.00
2	16212.60	39.16	1.099	0.30 (0.30)	0.99	10976.2	40100.00
3	17133.45	48.52	0.983	0.30 (0.30)	0.99	13753.9	11801.00
4	18680.38	62.65	0.866	0.30 (0.30)	0.99	18749.2	11530.00
5	19697.71	71.20	0.824	0.30 (0.30)	0.99	22637.3	11900.00
6	21347.96	81.39	0.774	0.30 (0.30)	0.99	28447.8	11330.00
7	22031.44	86.57	0.749	0.30 (0.30)	0.99	31716.9	11300.00
8	22297.72	89.87	0.733	0.30 (0.30)	0.99	33535.0	10630.00
9	22256.66	95.42	0.717	0.30 (0.30)	0.99	36124.9	12330.00
10	22249.10	98.68	0.708	0.30 (0.30)	0.99	37724.6	12410.00
11	22200.96	102.01	0.699	0.30 (0.30)	0.99	39267.3	11600.00
12	21993.16	107.70	0.684	0.30 (0.30)	0.99	41501.7	11111.00
13	21744.82	113.73	0.667	0.30 (0.30)	0.99	43435.5	12201.00
14	21451.48	117.49	0.657	0.30 (0.30)	0.99	44383.3	10410.00
15	21064.79	122.41	0.646	0.30 (0.30)	0.99	45523.8	12231.00
16	20420.76	129.64	0.633	0.30 (0.30)	0.99	46935.3	10400.00
17	20024.86	133.45	0.627	0.30 (0.30)	0.99	47525.5	10200.00
18	19379.57	140.63	0.615	0.30 (0.30)	0.99	48556.1	10320.00
19	18825.73	145.25	0.607	0.30 (0.30)	0.99	48781.5	10210.00
20	18349.25	149.90	0.599	0.30 (0.30)	0.99	48943.9	12000.00
21	15851.67	177.83	0.551	0.30 (0.30)	0.99	49560.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.45 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)		(ACRES)	NODE
1	346.22	9.57	2.705	0.30 (0.16)	0.52	148.8	800.00
2	304.47	13.17	2.148	0.30 (0.17)	0.57	168.1	818.00
3	283.23	14.36	1.983	0.30 (0.17)	0.58	171.0	810.00

LONGEST FLOWPATH FROM NODE 810.00 TO NODE 12603.00 = 3814.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)		(ACRES)	NODE
1	11970.58	9.57	2.705	0.30 (0.29)	0.97	2669.7	800.00
2	12602.99	13.17	2.148	0.30 (0.29)	0.97	3637.3	818.00
3	12488.28	14.36	1.983	0.30 (0.29)	0.98	3951.7	810.00
4	13527.34	19.59	1.643	0.30 (0.29)	0.98	5330.0	600.00
5	16357.47	39.16	1.099	0.30 (0.30)	0.99	11147.2	40100.00
6	17260.18	48.52	0.983	0.30 (0.30)	0.99	13924.9	11801.00
7	18788.73	62.65	0.866	0.30 (0.30)	0.99	18920.2	11530.00
8	19799.50	71.20	0.824	0.30 (0.30)	0.99	22808.3	11900.00
9	21441.94	81.39	0.774	0.30 (0.30)	0.99	28618.8	11330.00
10	22121.44	86.57	0.749	0.30 (0.30)	0.99	31887.9	11300.00
11	22385.19	89.87	0.733	0.30 (0.30)	0.99	33706.0	10630.00
12	22341.71	95.42	0.717	0.30 (0.30)	0.99	36295.9	12330.00
13	22332.75	98.68	0.708	0.30 (0.30)	0.99	37895.6	12410.00
14	22283.19	102.01	0.699	0.30 (0.30)	0.99	39438.3	11600.00
15	22072.96	107.70	0.684	0.30 (0.30)	0.99	41672.7	11111.00
16	21822.04	113.73	0.667	0.30 (0.30)	0.99	43606.5	12201.00

17	21527.09	117.49	0.657	0.30	(0.30)	0.99	44554.3	10410.00
18	21138.67	122.41	0.646	0.30	(0.30)	0.99	45694.8	12231.00
19	20492.69	129.64	0.633	0.30	(0.30)	0.99	47106.3	10400.00
20	20095.77	133.45	0.627	0.30	(0.30)	0.99	47696.5	10200.00
21	19448.56	140.63	0.615	0.30	(0.30)	0.99	48727.1	10320.00
22	18893.47	145.25	0.607	0.30	(0.30)	0.99	48952.5	10210.00
23	18415.74	149.90	0.599	0.30	(0.30)	0.99	49114.9	12000.00
24	15910.65	177.83	0.551	0.30	(0.30)	0.99	49731.9	10100.00

TOTAL AREA (ACRES) = 49731.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 22385.19 Tc (MIN.) = 89.869
EFFECTIVE AREA (ACRES) = 33706.01 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 49731.9
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.45 FEET.

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 89.87
* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.733
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.20	0.30	1.000	65
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.30	0.30	1.000	66
PUBLIC PARK	B	1.30	0.30	0.850	56
COMMERCIAL	B	1.40	0.30	0.100	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	1.70	0.30	0.900	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	12.40	0.30	1.000	66

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.911
SUBAREA AREA (ACRES) = 18.30 SUBAREA RUNOFF (CFS) = 7.56
EFFECTIVE AREA (ACRES) = 33724.31 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 49750.2 PEAK FLOW RATE (CFS) = 22385.19
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 89.87
* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.733
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	26.90	0.30	1.000	65

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 26.90 SUBAREA RUNOFF (CFS) = 10.47
EFFECTIVE AREA (ACRES) = 33751.21 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 49777.1 PEAK FLOW RATE (CFS) = 22385.19
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 89.87
* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.733
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	0.50	0.30	1.000	63
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.40	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL, NARROWLEAF"	B	0.40	0.30	1.000	72
NATURAL FAIR COVER					
"GRASS"	B	0.60	0.30	1.000	69
PUBLIC PARK	B	0.70	0.30	0.850	56
NATURAL FAIR COVER					
"CHAPARRAL, NARROWLEAF"	B	0.70	0.30	1.000	72

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.968
SUBAREA AREA (ACRES) = 3.30 SUBAREA RUNOFF (CFS) = 1.31
EFFECTIVE AREA (ACRES) = 33754.51 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 49780.4 PEAK FLOW RATE (CFS) = 22385.19
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 89.87
* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.733
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.00	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.20	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	1.70	0.30	0.900	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.90	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	2.10	0.30	0.900	56
NATURAL FAIR COVER					
"CHAPARRAL, NARROWLEAF"	B	2.90	0.30	1.000	72

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.965
 SUBAREA AREA(ACRES) = 10.80 SUBAREA RUNOFF(CFS) = 4.31
 EFFECTIVE AREA(ACRES) = 33765.31 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 49791.2 PEAK FLOW RATE(CFS) = 22385.19
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

 MAINLINE Tc(MIN.) = 89.87
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.733
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "WOODLAND,GRASS"	B	5.60	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND,GRASS"	B	9.00	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 14.60 SUBAREA RUNOFF(CFS) = 5.68
 EFFECTIVE AREA(ACRES) = 33779.91 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 49805.8 PEAK FLOW RATE(CFS) = 22385.19
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12603.00 TO NODE 12605.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

 ELEVATION DATA: UPSTREAM(FEET) = 310.00 DOWNSTREAM(FEET) = 305.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 885.00 CHANNEL SLOPE = 0.0056
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 7.39
 CHANNEL FLOW THRU SUBAREA(CFS) = 22385.19
 FLOW VELOCITY(FEET/SEC.) = 12.78 FLOW DEPTH(FEET) = 7.39
 TRAVEL TIME(MIN.) = 1.15 Tc(MIN.) = 91.02
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.00 = 102443.45 FEET.

 FLOW PROCESS FROM NODE 12605.00 TO NODE 12605.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

 MAINLINE Tc(MIN.) = 91.02
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.729
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "ROW CROPS,STRAIGHT ROW"	B	0.50	0.30	1.000	81

NATURAL FAIR COVER

"WOODLAND,GRASS"	B	0.70	0.30	1.000	65
PUBLIC PARK	B	1.30	0.30	0.850	56
RESIDENTIAL ".4 DWELLING/ACRE"	B	1.30	0.30	0.900	56
AGRICULTURAL POOR COVER "ROW CROPS,STRAIGHT ROW"	B	1.90	0.30	1.000	81
PUBLIC PARK	B	2.10	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.918
 SUBAREA AREA(ACRES) = 7.80 SUBAREA RUNOFF(CFS) = 3.19
 EFFECTIVE AREA(ACRES) = 33787.71 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 49813.6 PEAK FLOW RATE(CFS) = 22385.19
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12605.00 TO NODE 12605.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

 MAINLINE Tc(MIN.) = 91.02
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.729
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	3.20	0.30	1.000	66
NATURAL FAIR COVER "WOODLAND,GRASS"	B	3.50	0.30	1.000	65
PUBLIC PARK	B	6.10	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.929
 SUBAREA AREA(ACRES) = 12.80 SUBAREA RUNOFF(CFS) = 5.19
 EFFECTIVE AREA(ACRES) = 33800.51 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 49826.4 PEAK FLOW RATE(CFS) = 22385.19
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12605.00 TO NODE 12606.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

 ELEVATION DATA: UPSTREAM(FEET) = 305.00 DOWNSTREAM(FEET) = 286.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2159.47 CHANNEL SLOPE = 0.0088
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 6.51
 CHANNEL FLOW THRU SUBAREA(CFS) = 22385.19
 FLOW VELOCITY(FEET/SEC.) = 14.80 FLOW DEPTH(FEET) = 6.51
 TRAVEL TIME(MIN.) = 2.43 Tc(MIN.) = 93.45
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104602.91 FEET.

 FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 4F10EVRL.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	782.26	10.18	0.30 (0.24)	0.78	372.7	940.00
2	785.21	10.40	0.30 (0.24)	0.79	379.2	930.00
3	773.11	13.38	0.30 (0.25)	0.82	458.5	910.00
4	748.34	17.31	0.30 (0.25)	0.85	549.5	920.00
5	737.08	17.93	0.30 (0.25)	0.85	553.8	950.00
6	726.64	18.32	0.30 (0.25)	0.85	553.8	900.00
TOTAL AREA (ACRES) =						553.8

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11970.58	14.03	2.029	0.30 (0.29)	0.97	2764.2	800.00
2	12602.99	17.55	1.754	0.30 (0.29)	0.97	3731.8	818.00
3	12488.28	18.75	1.689	0.30 (0.29)	0.98	4046.2	810.00
4	13527.34	23.86	1.460	0.30 (0.29)	0.98	5424.5	600.00
5	16357.47	43.15	1.047	0.30 (0.30)	0.99	11241.7	40100.00
6	17260.18	52.45	0.945	0.30 (0.30)	0.99	14019.4	11801.00
7	18788.73	66.46	0.847	0.30 (0.30)	0.99	19014.7	11530.00
8	19799.50	74.94	0.806	0.30 (0.30)	0.99	22902.8	11900.00
9	21441.94	85.03	0.756	0.30 (0.30)	0.99	28713.3	11330.00
10	22121.44	90.17	0.732	0.30 (0.30)	0.99	31982.4	11300.00
11	22385.19	93.45	0.723	0.30 (0.30)	0.99	33800.5	10630.00
12	22341.71	99.01	0.707	0.30 (0.30)	0.99	36390.4	12330.00
13	22332.75	102.27	0.698	0.30 (0.30)	0.99	37990.1	12410.00
14	22283.19	105.60	0.689	0.30 (0.30)	0.99	39532.8	11600.00
15	22072.96	111.30	0.674	0.30 (0.30)	0.99	41767.2	11111.00
16	21822.04	117.35	0.657	0.30 (0.30)	0.99	43701.0	12201.00
17	21527.09	121.12	0.648	0.30 (0.30)	0.99	44648.8	10410.00
18	21138.67	126.07	0.640	0.30 (0.30)	0.99	45789.3	12231.00
19	20492.69	133.34	0.627	0.30 (0.30)	0.99	47200.8	10400.00
20	20095.77	137.17	0.621	0.30 (0.30)	0.99	47791.0	10200.00
21	19448.56	144.39	0.608	0.30 (0.30)	0.99	48821.6	10320.00
22	18893.47	149.05	0.600	0.30 (0.30)	0.99	49047.0	10210.00
23	18415.74	153.74	0.592	0.30 (0.30)	0.99	49209.4	12000.00
24	15910.65	181.86	0.546	0.30 (0.30)	0.99	49826.4	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104602.91 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	782.26	10.18	2.567	0.30 (0.24)	0.78	372.7	940.00
2	785.21	10.40	2.536	0.30 (0.24)	0.79	379.2	930.00
3	773.11	13.38	2.119	0.30 (0.25)	0.82	458.5	910.00
4	748.34	17.31	1.767	0.30 (0.25)	0.85	549.5	920.00
5	737.08	17.93	1.734	0.30 (0.25)	0.85	553.8	950.00
6	726.64	18.32	1.713	0.30 (0.25)	0.85	553.8	900.00

LONGEST FLOWPATH FROM NODE 920.00 TO NODE 12606.00 = 6933.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12155.86	10.18	2.567	0.30 (0.28)	0.94	2377.8	940.00
2	12248.55	10.40	2.536	0.30 (0.28)	0.94	2428.1	930.00
3	12743.69	13.38	2.119	0.30 (0.28)	0.94	3095.4	910.00
4	12739.61	14.03	2.029	0.30 (0.28)	0.95	3237.7	800.00
5	13307.18	17.31	1.767	0.30 (0.29)	0.96	4213.8	920.00
6	13346.87	17.55	1.754	0.30 (0.29)	0.96	4283.0	818.00
7	13304.04	17.93	1.734	0.30 (0.29)	0.96	4384.3	950.00
8	13256.50	18.32	1.713	0.30 (0.29)	0.96	4486.1	900.00
9	13203.18	18.75	1.689	0.30 (0.29)	0.96	4600.0	810.00
10	14127.90	23.86	1.460	0.30 (0.29)	0.97	5978.3	600.00
11	16752.27	43.15	1.047	0.30 (0.29)	0.98	11795.5	40100.00
12	17604.10	52.45	0.945	0.30 (0.29)	0.98	14573.2	11801.00
13	19084.11	66.46	0.847	0.30 (0.30)	0.99	19568.5	11530.00
14	20074.17	74.94	0.806	0.30 (0.30)	0.99	23456.6	11900.00
15	21691.98	85.03	0.756	0.30 (0.30)	0.99	29267.1	11330.00
16	22359.10	90.17	0.732	0.30 (0.30)	0.99	32536.2	11300.00
17	22618.37	93.45	0.723	0.30 (0.30)	0.99	34354.3	10630.00
18	22567.32	99.01	0.707	0.30 (0.30)	0.99	36944.2	12330.00
19	22553.93	102.27	0.698	0.30 (0.30)	0.99	38543.9	12410.00
20	22499.83	105.60	0.689	0.30 (0.30)	0.99	40086.6	11600.00
21	22281.83	111.30	0.674	0.30 (0.30)	0.99	42321.0	11111.00
22	22022.67	117.35	0.657	0.30 (0.30)	0.99	44254.8	12201.00
23	21723.15	121.12	0.648	0.30 (0.30)	0.99	45202.6	10410.00
24	21330.50	126.07	0.640	0.30 (0.30)	0.99	46343.1	12231.00
25	20678.30	133.34	0.627	0.30 (0.30)	0.99	47754.6	10400.00
26	20278.10	137.17	0.621	0.30 (0.30)	0.99	48344.8	10200.00
27	19624.71	144.39	0.608	0.30 (0.30)	0.99	49375.4	10320.00
28	19065.64	149.05	0.600	0.30 (0.30)	0.99	49600.8	10210.00
29	18583.90	153.74	0.592	0.30 (0.30)	0.99	49763.2	12000.00
30	16055.61	181.86	0.546	0.30 (0.30)	0.99	50380.2	10100.00
TOTAL AREA (ACRES) =						50380.2	

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 22618.37 Tc(MIN.) = 93.454

EFFECTIVE AREA(ACRES) = 34354.31 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98

TOTAL AREA (ACRES) = 50380.2

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104602.91 FEET.

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 93.45

* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.723

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	0.30	0.30	1.000	63
NATURAL FAIR COVER					
"GRASS"	B	0.30	0.30	1.000	69

PUBLIC PARK B 0.40 0.30 0.850 56
 NATURAL FAIR COVER
 "CHAPARRAL,NARROWLEAF" B 0.60 0.30 1.000 72
 COMMERCIAL B 1.10 0.30 0.100 56
 PUBLIC PARK B 0.80 0.30 0.850 56
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.666
 SUBAREA AREA(ACRES) = 3.50 SUBAREA RUNOFF(CFS) = 1.65
 EFFECTIVE AREA(ACRES) = 34357.81 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 50383.7 PEAK FLOW RATE(CFS) = 22618.37
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

 MAINLINE Tc(MIN.) = 93.45
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.723
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 NATURAL FAIR COVER
 "GRASS" B 0.80 0.30 1.000 69
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 0.90 0.30 1.000 65
 AGRICULTURAL POOR COVER
 "ROW CROPS,STRAIGHT ROW" B 1.50 0.30 1.000 81
 NATURAL FAIR COVER
 "OPEN BRUSH" B 1.60 0.30 1.000 66
 NATURAL FAIR COVER
 "OPEN BRUSH" B 1.80 0.30 1.000 66
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 1.90 0.30 1.000 65
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 8.50 SUBAREA RUNOFF(CFS) = 3.23
 EFFECTIVE AREA(ACRES) = 34366.31 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 50392.2 PEAK FLOW RATE(CFS) = 22618.37
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

 MAINLINE Tc(MIN.) = 93.45
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.723
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 NATURAL FAIR COVER
 "OPEN BRUSH" B 3.30 0.30 1.000 66
 PUBLIC PARK B 3.70 0.30 0.850 56
 NATURAL FAIR COVER
 "CHAPARRAL,NARROWLEAF" B 3.90 0.30 1.000 72

PUBLIC PARK B 5.90 0.30 0.850 56
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 9.10 0.30 1.000 65
 NATURAL FAIR COVER
 "OPEN BRUSH" B 20.60 0.30 1.000 66
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.969
 SUBAREA AREA(ACRES) = 46.50 SUBAREA RUNOFF(CFS) = 18.07
 EFFECTIVE AREA(ACRES) = 34412.81 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 50438.7 PEAK FLOW RATE(CFS) = 22618.37
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 END OF STUDY SUMMARY:
 TOTAL AREA(ACRES) = 50438.7 TC(MIN.) = 93.45
 EFFECTIVE AREA(ACRES) = 34412.81 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.990
 PEAK FLOW RATE(CFS) = 22618.37

***** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12155.86	10.18	2.567	0.30(0.28)	0.94	2436.3	940.00
2	12248.55	10.40	2.536	0.30(0.28)	0.94	2486.6	930.00
3	12743.69	13.38	2.119	0.30(0.28)	0.94	3153.9	910.00
4	12739.61	14.03	2.029	0.30(0.28)	0.95	3296.2	800.00
5	13307.18	17.31	1.767	0.30(0.29)	0.96	4272.3	920.00
6	13346.87	17.55	1.754	0.30(0.29)	0.96	4341.5	818.00
7	13304.04	17.93	1.734	0.30(0.29)	0.96	4442.8	950.00
8	13256.50	18.32	1.713	0.30(0.29)	0.96	4544.6	900.00
9	13203.18	18.75	1.689	0.30(0.29)	0.96	4658.5	810.00
10	14127.90	23.86	1.460	0.30(0.29)	0.97	6036.8	600.00
11	16752.27	43.15	1.047	0.30(0.29)	0.98	11854.0	40100.00
12	17604.10	52.45	0.945	0.30(0.29)	0.98	14631.7	11801.00
13	19084.11	66.46	0.847	0.30(0.30)	0.99	19627.0	11530.00
14	20074.17	74.94	0.806	0.30(0.30)	0.99	23515.1	11900.00
15	21691.98	85.03	0.756	0.30(0.30)	0.99	29325.6	11330.00
16	22359.10	90.17	0.732	0.30(0.30)	0.99	32594.7	11300.00
17	22618.37	93.45	0.723	0.30(0.30)	0.99	34412.8	10630.00
18	22567.32	99.01	0.707	0.30(0.30)	0.99	37002.7	12330.00
19	22553.93	102.27	0.698	0.30(0.30)	0.99	38602.4	12410.00
20	22499.83	105.60	0.689	0.30(0.30)	0.99	40145.1	11600.00
21	22281.83	111.30	0.674	0.30(0.30)	0.99	42379.5	11111.00
22	22022.67	117.35	0.657	0.30(0.30)	0.99	44313.3	12201.00
23	21723.15	121.12	0.648	0.30(0.30)	0.99	45261.1	10410.00
24	21330.50	126.07	0.640	0.30(0.30)	0.99	46401.6	12231.00
25	20678.30	133.34	0.627	0.30(0.30)	0.99	47813.1	10400.00
26	20278.10	137.17	0.621	0.30(0.30)	0.99	48403.3	10200.00
27	19624.71	144.39	0.608	0.30(0.30)	0.99	49433.9	10320.00
28	19065.64	149.05	0.600	0.30(0.30)	0.99	49659.3	10210.00
29	18583.90	153.74	0.592	0.30(0.30)	0.99	49821.7	12000.00
30	16055.61	181.86	0.546	0.30(0.30)	0.99	50438.7	10100.00

 END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 127 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 10-YR EV FEB 2023 ROKAMOTO *

FILE NAME: RU10EV27.DAT
TIME/DATE OF STUDY: 08:28 02/08/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 10.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 3.879
- 2) 10.00; 2.574
- 3) 15.00; 1.886
- 4) 20.00; 1.614
- 5) 25.00; 1.407
- 6) 30.00; 1.261
- 7) 40.00; 1.080
- 8) 50.00; 0.962
- 9) 60.00; 0.875
- 10) 90.00; 0.728
- 11) 120.00; 0.645
- 12) 180.00; 0.542
- 13) 360.00; 0.402
- 14) 1200.00; 0.177

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU10EV26.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12743.69	13.38	0.30 (0.28)	0.94	3153.9	910.00
2	13346.87	17.55	0.30 (0.29)	0.96	4341.5	818.00
3	14127.90	23.86	0.30 (0.29)	0.97	6036.8	600.00
4	16752.27	43.15	0.30 (0.29)	0.98	11854.0	40100.00
5	17604.10	52.45	0.30 (0.29)	0.98	14631.7	11801.00
6	19084.11	66.46	0.30 (0.30)	0.99	19627.0	11530.00
7	20074.17	74.94	0.30 (0.30)	0.99	23515.1	11900.00
8	21691.98	85.03	0.30 (0.30)	0.99	29325.6	11330.00
9	22618.37	93.45	0.30 (0.30)	0.99	34412.8	10630.00
10	22567.32	99.01	0.30 (0.30)	0.99	37002.7	12330.00
11	22499.83	105.60	0.30 (0.30)	0.99	40145.1	11600.00
12	22281.83	111.30	0.30 (0.30)	0.99	42379.5	11111.00
13	22022.67	117.35	0.30 (0.30)	0.99	44313.3	10210.00
14	21330.50	126.07	0.30 (0.30)	0.99	46401.6	12231.00
15	20678.30	133.34	0.30 (0.30)	0.99	47813.1	10400.00
16	20278.10	137.17	0.30 (0.30)	0.99	48403.3	10200.00
17	19624.71	144.39	0.30 (0.30)	0.99	49433.9	10320.00
18	19065.64	149.05	0.30 (0.30)	0.99	49659.3	10210.00
19	18583.90	153.74	0.30 (0.30)	0.99	49821.7	12000.00
20	16055.61	181.86	0.30 (0.30)	0.99	50438.7	10100.00
TOTAL AREA (ACRES) =						50438.7

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12743.69	13.38	0.30 (0.28)	0.94	3153.9	910.00
2	13346.87	17.55	0.30 (0.29)	0.96	4341.5	818.00
3	14127.90	23.86	0.30 (0.29)	0.97	6036.8	600.00
4	16752.27	43.15	0.30 (0.29)	0.98	11854.0	40100.00
5	17604.10	52.45	0.30 (0.29)	0.98	14631.7	11801.00
6	19084.11	66.46	0.30 (0.30)	0.99	19627.0	11530.00
7	20074.17	74.94	0.30 (0.30)	0.99	23515.1	11900.00
8	21691.98	85.03	0.30 (0.30)	0.99	29325.6	11330.00
9	22618.37	93.45	0.30 (0.30)	0.99	34412.8	10630.00
10	22567.32	99.01	0.30 (0.30)	0.99	37002.7	12330.00
11	22499.83	105.60	0.30 (0.30)	0.99	40145.1	11600.00
12	22281.83	111.30	0.30 (0.30)	0.99	42379.5	11111.00
13	22022.67	117.35	0.30 (0.30)	0.99	44313.3	12201.00

14 21330.50 126.07 0.30(0.30) 0.99 46401.6 12231.00
 15 20678.30 133.34 0.30(0.30) 0.99 47813.1 10400.00
 16 20278.10 137.17 0.30(0.30) 0.99 48403.3 10200.00
 17 19624.71 144.39 0.30(0.30) 0.99 49433.9 10320.00
 18 19065.64 149.05 0.30(0.30) 0.99 49659.3 10210.00
 19 18583.90 153.74 0.30(0.30) 0.99 49821.7 12000.00
 20 16055.61 181.86 0.30(0.30) 0.99 50438.7 10100.00
 TOTAL AREA(ACRES) = 50438.7

FLOW PROCESS FROM NODE 12606.00 TO NODE 12701.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 286.00 DOWNSTREAM(FEET) = 276.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1260.19 CHANNEL SLOPE = 0.0079
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 6.75
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.714

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

RESIDENTIAL					
"5-7 DWELLINGS/ACRE"	B	0.70	0.30	0.500	56
PUBLIC PARK	B	0.90	0.30	0.850	56
COMMERCIAL	B	3.40	0.30	0.100	56
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	3.60	0.30	1.000	65
PUBLIC PARK	B	10.10	0.30	0.850	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	17.40	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.860

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 22625.79

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 14.35

AVERAGE FLOW DEPTH(FEET) = 6.75 TRAVEL TIME(MIN.) = 1.46

Tc(MIN.) = 94.92

SUBAREA AREA(ACRES) = 36.10 SUBAREA RUNOFF(CFS) = 14.83

EFFECTIVE AREA(ACRES) = 34448.91 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 50474.8 PEAK FLOW RATE(CFS) = 22618.37

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT(FEET) = 6.74

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 6.74 FLOW VELOCITY(FEET/SEC.) = 14.36

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12701.00 = 105863.10 FEET.

FLOW PROCESS FROM NODE 12701.00 TO NODE 12720.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 276.00 DOWNSTREAM(FEET) = 275.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 147.65 CHANNEL SLOPE = 0.0068
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 7.06
 CHANNEL FLOW THRU SUBAREA(CFS) = 22618.37
 FLOW VELOCITY(FEET/SEC.) = 13.62 FLOW DEPTH(FEET) = 7.06
 TRAVEL TIME(MIN.) = 0.18 Tc(MIN.) = 95.10
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.00 = 106010.75 FEET.

FLOW PROCESS FROM NODE 12701.00 TO NODE 12720.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
 TIME OF CONCENTRATION(MIN.) = 95.10
 RAINFALL INTENSITY(INCH/HR) = 0.71
 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.99
 EFFECTIVE STREAM AREA(ACRES) = 34448.91
 TOTAL STREAM AREA(ACRES) = 50474.79
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 22618.37

FLOW PROCESS FROM NODE 12710.00 TO NODE 12711.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH(FEET) = 943.56
 ELEVATION DATA: UPSTREAM(FEET) = 940.78 DOWNSTREAM(FEET) = 657.79

Tc = K*(LENGTH** 3.00)/(ELEVATION CHANGE)**0.20

SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 13.910

* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.036

SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------	--------------

NATURAL FAIR COVER						
"GRASS"	B	6.56	0.30	1.000	69	13.91
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30						
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000						
SUBAREA RUNOFF(CFS) = 10.25						
TOTAL AREA(ACRES) = 6.56 PEAK FLOW RATE(CFS) = 10.25						

FLOW PROCESS FROM NODE 12711.00 TO NODE 12712.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 657.79 DOWNSTREAM(FEET) = 585.63
 CHANNEL LENGTH THRU SUBAREA(FEET) = 766.00 CHANNEL SLOPE = 0.0942
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT (FEET) = 0.58
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.797
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	26.94	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 28.46
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.70
 AVERAGE FLOW DEPTH (FEET) = 0.55 TRAVEL TIME (MIN.) = 2.72
 Tc (MIN.) = 16.63
 SUBAREA AREA (ACRES) = 26.94 SUBAREA RUNOFF (CFS) = 36.31
 EFFECTIVE AREA (ACRES) = 33.50 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 33.5 PEAK FLOW RATE (CFS) = 45.15
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 0.71

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 0.71 FLOW VELOCITY (FEET/SEC.) = 5.53
 LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12712.00 = 1709.56 FEET.

 FLOW PROCESS FROM NODE 12712.00 TO NODE 12713.00 IS CODE = 56

>>>> COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>> TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 585.63 DOWNSTREAM (FEET) = 463.75
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1025.79 CHANNEL SLOPE = 0.1188
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 0.75
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.651
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	14.73	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 54.11
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.34
 AVERAGE FLOW DEPTH (FEET) = 0.74 TRAVEL TIME (MIN.) = 2.70
 Tc (MIN.) = 19.32
 SUBAREA AREA (ACRES) = 14.73 SUBAREA RUNOFF (CFS) = 17.91
 EFFECTIVE AREA (ACRES) = 48.23 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 48.2 PEAK FLOW RATE (CFS) = 58.63
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 0.78

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 0.78 FLOW VELOCITY (FEET/SEC.) = 6.49

LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12713.00 = 2735.35 FEET.

 FLOW PROCESS FROM NODE 12713.00 TO NODE 12714.00 IS CODE = 56

>>>> COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>> TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 463.75 DOWNSTREAM (FEET) = 360.30
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1148.54 CHANNEL SLOPE = 0.0901
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 1.29
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.536
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	105.64	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 117.47
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.47
 AVERAGE FLOW DEPTH (FEET) = 1.26 TRAVEL TIME (MIN.) = 2.56
 Tc (MIN.) = 21.89
 SUBAREA AREA (ACRES) = 105.64 SUBAREA RUNOFF (CFS) = 117.51
 EFFECTIVE AREA (ACRES) = 153.87 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 153.9 PEAK FLOW RATE (CFS) = 171.16
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 1.55

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 1.55 FLOW VELOCITY (FEET/SEC.) = 8.41
 LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12714.00 = 3883.89 FEET.

 FLOW PROCESS FROM NODE 12714.00 TO NODE 12720.00 IS CODE = 56

>>>> COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>> TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 360.30 DOWNSTREAM (FEET) = 275.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1314.99 CHANNEL SLOPE = 0.0649
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 2.06
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.426
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	127.13	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 235.63
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.24

AVERAGE FLOW DEPTH (FEET) = 2.03 TRAVEL TIME (MIN.) = 2.66
 Tc (MIN.) = 24.54
 SUBAREA AREA (ACRES) = 127.13 SUBAREA RUNOFF (CFS) = 128.82
 EFFECTIVE AREA (ACRES) = 281.00 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 281.0 PEAK FLOW RATE (CFS) = 284.73
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 2.25

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 2.25 FLOW VELOCITY (FEET/SEC.) = 8.74
 LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12720.00 = 5198.88 FEET.

 FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====
 TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
 TIME OF CONCENTRATION (MIN.) = 24.54
 RAINFALL INTENSITY (INCH/HR) = 1.43
 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30
 AREA-AVERAGED Ap = 1.00
 EFFECTIVE STREAM AREA (ACRES) = 281.00
 TOTAL STREAM AREA (ACRES) = 281.00
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 284.73

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12743.69	15.39	1.865	0.30 (0.28)	0.94	3190.0	910.00
1	13346.87	19.53	1.640	0.30 (0.29)	0.96	4377.6	818.00
1	14127.90	25.79	1.384	0.30 (0.29)	0.97	6072.9	600.00
1	16752.27	44.98	1.021	0.30 (0.29)	0.98	11890.1	40100.00
1	17604.10	54.24	0.925	0.30 (0.29)	0.98	14667.8	11801.00
1	19084.11	68.21	0.835	0.30 (0.30)	0.99	19663.1	11530.00
1	20074.17	76.65	0.793	0.30 (0.30)	0.99	23551.2	11900.00
1	21691.98	86.69	0.744	0.30 (0.30)	0.99	29361.7	11330.00
1	22618.37	95.10	0.714	0.30 (0.30)	0.99	34448.9	10630.00
1	22567.32	100.66	0.699	0.30 (0.30)	0.99	37038.8	12330.00
1	22499.83	107.24	0.680	0.30 (0.30)	0.99	40181.2	11600.00
1	22281.83	112.96	0.664	0.30 (0.30)	0.99	42415.6	11111.00
1	22022.67	119.01	0.648	0.30 (0.30)	0.99	44349.4	12201.00
1	21330.50	127.74	0.632	0.30 (0.30)	0.99	46437.7	12231.00
1	20678.30	135.04	0.619	0.30 (0.30)	0.99	47849.2	10400.00
1	20278.10	138.87	0.613	0.30 (0.30)	0.99	48439.4	10200.00
1	19624.71	146.12	0.600	0.30 (0.30)	0.99	49470.0	10320.00
1	19065.64	150.79	0.592	0.30 (0.30)	0.99	49695.4	10210.00
1	18583.90	155.49	0.584	0.30 (0.30)	0.99	49857.8	12000.00
1	16055.61	183.71	0.539	0.30 (0.30)	0.99	50474.8	10100.00
2	284.73	24.54	1.426	0.30 (0.30)	1.00	281.0	12710.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12991.83	15.39	1.865	0.30 (0.28)	0.95	3366.2	910.00
2	13616.43	19.53	1.640	0.30 (0.29)	0.96	4601.2	818.00
3	14256.75	24.54	1.426	0.30 (0.29)	0.97	6015.5	12710.00
4	14401.99	25.79	1.384	0.30 (0.29)	0.97	6353.9	600.00
5	16934.68	44.98	1.021	0.30 (0.29)	0.98	12171.1	40100.00
6	17762.20	54.24	0.925	0.30 (0.29)	0.98	14948.8	11801.00
7	19219.36	68.21	0.835	0.30 (0.30)	0.99	19944.1	11530.00
8	20198.95	76.65	0.793	0.30 (0.30)	0.99	23832.2	11900.00
9	21804.32	86.69	0.744	0.30 (0.30)	0.99	29642.7	11330.00
10	22723.05	95.10	0.714	0.30 (0.30)	0.99	34729.9	10630.00
11	22668.11	100.66	0.699	0.30 (0.30)	0.99	37319.8	12330.00
12	22596.01	107.24	0.680	0.30 (0.30)	0.99	40462.2	11600.00
13	22374.01	112.96	0.664	0.30 (0.30)	0.99	42696.6	11111.00
14	22110.62	119.01	0.648	0.30 (0.30)	0.99	44630.4	12201.00
15	21414.39	127.74	0.632	0.30 (0.30)	0.99	46718.7	12231.00
16	20759.02	135.04	0.619	0.30 (0.30)	0.99	48130.2	10400.00
17	20357.16	138.87	0.613	0.30 (0.30)	0.99	48720.4	10200.00
18	19700.62	146.12	0.600	0.30 (0.30)	0.99	49751.0	10320.00
19	19139.52	150.79	0.592	0.30 (0.30)	0.99	49976.4	10210.00
20	18655.74	155.49	0.584	0.30 (0.30)	0.99	50138.8	12000.00
21	16116.08	183.71	0.539	0.30 (0.30)	0.99	50755.8	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 22723.05 Tc (MIN.) = 95.10
 EFFECTIVE AREA (ACRES) = 34729.91 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 50755.8
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.00 = 10610.75 FEET.

 FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====
 ELEVATION DATA: UPSTREAM (FEET) = 275.00 DOWNSTREAM (FEET) = 258.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 2669.21 CHANNEL SLOPE = 0.0064
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT (FEET) = 7.21

* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.705

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.20	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.30	0.30	1.000	65
COMMERCIAL	B	0.30	0.30	0.100	56
NATURAL FAIR COVER					

"MEADOWS" B 0.50 0.30 1.000 70
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.841
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 22723.39
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 13.36
 AVERAGE FLOW DEPTH (FEET) = 7.21 TRAVEL TIME (MIN.) = 3.33
 Tc (MIN.) = 98.43
 SUBAREA AREA (ACRES) = 1.70 SUBAREA RUNOFF (CFS) = 0.69
 EFFECTIVE AREA (ACRES) = 34731.61 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 50757.5 PEAK FLOW RATE (CFS) = 22723.05
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT (FEET) = 7.21

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 7.21 FLOW VELOCITY (FEET/SEC.) = 13.36
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108679.96 FEET.

 FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<
 =====

MAINLINE Tc (MIN.) = 98.43
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.705
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 PUBLIC PARK B 0.50 0.30 0.850 56
 NATURAL FAIR COVER
 "WOODLAND, GRASS" B 0.70 0.30 1.000 65
 NATURAL FAIR COVER
 "OPEN BRUSH" B 1.50 0.30 1.000 66
 COMMERCIAL B 1.40 0.30 0.100 56
 COMMERCIAL B 2.30 0.30 0.100 56
 NATURAL FAIR COVER
 "GRASS" B 9.30 0.30 1.000 69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.783
 SUBAREA AREA (ACRES) = 15.70 SUBAREA RUNOFF (CFS) = 6.64
 EFFECTIVE AREA (ACRES) = 34747.31 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 50773.2 PEAK FLOW RATE (CFS) = 22723.05
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<
 =====

MAINLINE Tc (MIN.) = 98.43
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.705
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 NATURAL FAIR COVER

"WOODLAND, GRASS" B 11.20 0.30 1.000 65
 NATURAL FAIR COVER
 "WOODLAND, GRASS" B 11.40 0.30 1.000 65
 NATURAL FAIR COVER
 "CHAPARRAL, NARROWLEAF" B 11.80 0.30 1.000 72
 NATURAL FAIR COVER
 "OPEN BRUSH" B 27.70 0.30 1.000 66
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 62.10 SUBAREA RUNOFF (CFS) = 22.62
 EFFECTIVE AREA (ACRES) = 34809.41 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 50835.3 PEAK FLOW RATE (CFS) = 22723.05
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<<
 =====

PEAK FLOWRATE TABLE FILE NAME: 3C10EVRL.DNA
 MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1549.37	13.18	0.30 (0.13)	0.42	856.0	410.00
2	1523.53	14.67	0.30 (0.13)	0.42	937.5	420.00
3	1604.99	18.83	0.30 (0.13)	0.42	1149.0	310.00
4	1605.77	19.48	0.30 (0.13)	0.42	1175.3	400.00
5	1570.85	22.03	0.30 (0.13)	0.42	1243.6	430.00
6	1561.76	22.70	0.30 (0.13)	0.42	1261.1	300.00
7	1557.57	22.92	0.30 (0.13)	0.42	1265.9	320.00
8	1332.20	29.53	0.30 (0.13)	0.43	1292.3	390.00
TOTAL AREA (ACRES) =		1292.3				

 FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<<
 =====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12991.83	19.43	1.645	0.30 (0.28)	0.95	3445.7	910.00
2	13616.43	23.50	1.469	0.30 (0.29)	0.96	4680.7	818.00
3	14256.75	28.45	1.306	0.30 (0.29)	0.97	6095.0	12710.00
4	14401.99	29.69	1.270	0.30 (0.29)	0.97	6433.4	600.00
5	16934.68	48.65	0.978	0.30 (0.29)	0.98	12250.6	40100.00
6	17762.20	57.86	0.894	0.30 (0.29)	0.98	15028.3	11801.00
7	19219.36	71.73	0.818	0.30 (0.30)	0.99	20023.6	11530.00
8	20198.95	80.12	0.776	0.30 (0.30)	0.99	23911.7	11900.00
9	21804.32	90.07	0.728	0.30 (0.30)	0.99	29722.2	11330.00
10	22723.05	98.43	0.705	0.30 (0.30)	0.99	34809.4	10630.00
11	22668.11	103.99	0.689	0.30 (0.30)	0.99	37399.3	12330.00
12	22596.01	110.58	0.671	0.30 (0.30)	0.99	40541.7	11600.00
13	22374.01	116.30	0.655	0.30 (0.30)	0.99	42776.1	11111.00
14	22110.62	122.37	0.641	0.30 (0.30)	0.99	44709.9	12201.00
15	21414.39	131.14	0.626	0.30 (0.30)	0.99	46798.2	12231.00

16 20759.02 138.47 0.613 0.30(0.30) 0.99 48209.7 10400.00
 17 20357.16 142.33 0.607 0.30(0.30) 0.99 48799.9 10200.00
 18 19700.62 149.61 0.594 0.30(0.30) 0.99 49830.5 10320.00
 19 19139.52 154.32 0.586 0.30(0.30) 0.99 50055.9 10210.00
 20 18655.74 159.05 0.578 0.30(0.30) 0.99 50218.3 12000.00
 21 16116.08 187.45 0.536 0.30(0.30) 0.99 50835.3 10100.00
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108679.96 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1549.37	13.18	2.137	0.30(0.13)	0.42	856.0	410.00
2	1523.53	14.67	1.931	0.30(0.13)	0.42	937.5	420.00
3	1604.99	18.83	1.678	0.30(0.13)	0.42	1149.0	310.00
4	1605.77	19.48	1.642	0.30(0.13)	0.42	1175.3	400.00
5	1570.85	22.03	1.530	0.30(0.13)	0.42	1243.6	430.00
6	1561.76	22.70	1.502	0.30(0.13)	0.42	1261.1	300.00
7	1557.57	22.92	1.493	0.30(0.13)	0.42	1265.9	320.00
8	1332.20	29.53	1.275	0.30(0.13)	0.43	1292.3	390.00

LONGEST FLOWPATH FROM NODE 390.00 TO NODE 12720.50 = 13248.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13544.85	13.18	2.137	0.30(0.24)	0.81	3193.5	410.00
2	13397.34	14.67	1.931	0.30(0.24)	0.81	3539.7	420.00
3	14497.45	18.83	1.678	0.30(0.24)	0.81	4488.3	310.00
4	14597.53	19.43	1.645	0.30(0.24)	0.81	4618.7	910.00
5	14606.43	19.48	1.642	0.30(0.24)	0.81	4638.5	400.00
6	14962.16	22.03	1.530	0.30(0.25)	0.83	5479.1	430.00
7	15056.12	22.70	1.502	0.30(0.25)	0.84	5700.4	300.00
8	15085.05	22.92	1.493	0.30(0.25)	0.84	5770.8	320.00
9	15154.24	23.50	1.469	0.30(0.25)	0.84	5948.9	818.00
10	15625.70	28.45	1.306	0.30(0.26)	0.87	7383.0	12710.00
11	15715.52	29.53	1.275	0.30(0.26)	0.88	7682.2	390.00
12	15728.79	29.69	1.270	0.30(0.26)	0.88	7725.7	600.00
13	17921.61	48.65	0.978	0.30(0.28)	0.93	13542.9	40100.00
14	18651.13	57.86	0.894	0.30(0.28)	0.94	16320.6	11801.00
15	20019.78	71.73	0.818	0.30(0.29)	0.95	21315.9	11530.00
16	20951.57	80.12	0.776	0.30(0.29)	0.96	25204.0	11900.00
17	22500.39	90.07	0.728	0.30(0.29)	0.97	31014.5	11330.00
18	23392.22	98.43	0.705	0.30(0.29)	0.97	36101.7	10630.00
19	23319.40	103.99	0.689	0.30(0.29)	0.97	38691.6	12330.00
20	23226.08	110.58	0.671	0.30(0.29)	0.97	41834.0	11600.00
21	22985.67	116.30	0.655	0.30(0.29)	0.97	44068.4	11111.00
22	22705.65	122.37	0.641	0.30(0.29)	0.97	46002.2	12201.00
23	21991.90	131.14	0.626	0.30(0.29)	0.97	48090.5	12231.00
24	21321.91	138.47	0.613	0.30(0.29)	0.97	49502.0	10400.00
25	20912.33	142.33	0.607	0.30(0.29)	0.97	50092.2	10200.00
26	20241.26	149.61	0.594	0.30(0.29)	0.97	51122.8	10320.00
27	19670.75	154.32	0.586	0.30(0.29)	0.98	51348.2	10210.00
28	19177.52	159.05	0.578	0.30(0.29)	0.98	51510.6	12000.00
29	16589.30	187.45	0.536	0.30(0.29)	0.98	52127.6	10100.00

TOTAL AREA (ACRES) = 52127.6

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 23392.22 Tc (MIN.) = 98.428
 EFFECTIVE AREA (ACRES) = 36101.71 AREA-AVERAGED Fm (INCH/HR) = 0.29

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.87
 TOTAL AREA (ACRES) = 52127.6
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108679.96 FEET.

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

FLOW PROCESS FROM NODE 12720.50 TO NODE 12722.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 258.00 DOWNSTREAM (FEET) = 255.00

CHANNEL LENGTH THRU SUBAREA (FEET) = 1269.00 CHANNEL SLOPE = 0.0024

GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT (FEET) = 9.71

* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.699

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	0.10	0.30	0.850	56
NATURAL FAIR COVER					
"GRASS"	B	0.10	0.30	1.000	69
NATURAL FAIR COVER					
"GRASS"	B	0.20	0.30	1.000	69
NATURAL FAIR COVER					
"GRASS"	B	0.30	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.30	0.30	1.000	66
COMMERCIAL	B	0.40	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.732

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 23392.52

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 9.69

AVERAGE FLOW DEPTH (FEET) = 9.71 TRAVEL TIME (MIN.) = 2.18

Tc (MIN.) = 100.61

SUBAREA AREA (ACRES) = 1.40 SUBAREA RUNOFF (CFS) = 0.60

EFFECTIVE AREA (ACRES) = 36103.11 AREA-AVERAGED Fm (INCH/HR) = 0.29

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97

TOTAL AREA (ACRES) = 52129.0 PEAK FLOW RATE (CFS) = 23392.22

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT (FEET) = 9.71

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 9.71 FLOW VELOCITY (FEET/SEC.) = 9.69

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12722.00 = 109948.96 FEET.

FLOW PROCESS FROM NODE 12722.00 TO NODE 12722.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

```

=====
MAINLINE Tc(MIN.) = 100.61
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.699
SUBAREA LOSS RATE DATA(AMC II):
  DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp        Ap      SCS
    LAND USE            GROUP  (ACRES)  (INCH/HR)  (DECIMAL)  CN
COMMERCIAL                B         0.50    0.30    0.100    56
NATURAL FAIR COVER
"WOODLAND,GRASS"        B         0.60    0.30    1.000    65
NATURAL POOR COVER
"BARREN"                 B         0.60    0.30    1.000    86
COMMERCIAL                B         0.60    0.30    0.100    56
NATURAL FAIR COVER
"OPEN BRUSH"            B         0.90    0.30    1.000    66
NATURAL FAIR COVER
"CHAPARRAL,BROADLEAF"   B         1.00    0.30    1.000    63
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.764
SUBAREA AREA(ACRES) = 4.20      SUBAREA RUNOFF(CFS) = 1.77
EFFECTIVE AREA(ACRES) = 36107.31  AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30  AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 52133.2      PEAK FLOW RATE(CFS) = 23392.22
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 12722.00 TO NODE 12722.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
-----

```

```

=====
MAINLINE Tc(MIN.) = 100.61
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.699
SUBAREA LOSS RATE DATA(AMC II):
  DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp        Ap      SCS
    LAND USE            GROUP  (ACRES)  (INCH/HR)  (DECIMAL)  CN
NATURAL FAIR COVER
"WOODLAND,GRASS"        B         1.30    0.30    1.000    65
NATURAL FAIR COVER
"MEADOWS"               B         3.20    0.30    1.000    70
NATURAL FAIR COVER
"WOODLAND,GRASS"        B         3.70    0.30    1.000    65
NATURAL FAIR COVER
"OPEN BRUSH"            B        12.00    0.30    1.000    66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 20.20      SUBAREA RUNOFF(CFS) = 7.25
EFFECTIVE AREA(ACRES) = 36127.51  AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30  AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 52153.4      PEAK FLOW RATE(CFS) = 23392.22
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 12722.00 TO NODE 12740.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
-----

```

```

ELEVATION DATA: UPSTREAM(FEET) = 255.00  DOWNSTREAM(FEET) = 252.10
CHANNEL LENGTH THRU SUBAREA( FEET) = 624.00  CHANNEL SLOPE = 0.0046

```

```

GIVEN CHANNEL BASE(FEET) = 200.00  CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000  MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 8.02
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.696
SUBAREA LOSS RATE DATA(AMC II):
  DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp        Ap      SCS
    LAND USE            GROUP  (ACRES)  (INCH/HR)  (DECIMAL)  CN
AGRICULTURAL POOR COVER
"ROW CROPS,STRAIGHT ROW"  B         0.10    0.30    1.000    81
PUBLIC PARK                B         0.50    0.30    0.850    56
NATURAL FAIR COVER
"GRASS"                   B         0.50    0.30    1.000    69
NATURAL FAIR COVER
"CHAPARRAL,BROADLEAF"    B         0.80    0.30    1.000    63
NATURAL FAIR COVER
"WOODLAND,GRASS"         B         1.20    0.30    1.000    65
COMMERCIAL                B         1.50    0.30    0.100    56
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.690
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 23393.23
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.16
AVERAGE FLOW DEPTH(FEET) = 8.02  TRAVEL TIME(MIN.) = 0.86
Tc(MIN.) = 101.47
SUBAREA AREA(ACRES) = 4.60      SUBAREA RUNOFF(CFS) = 2.03
EFFECTIVE AREA(ACRES) = 36132.11  AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30  AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 52158.0      PEAK FLOW RATE(CFS) = 23392.22
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 200.00  CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000  MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 8.02

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 8.02  FLOW VELOCITY(FEET/SEC.) = 12.16
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12740.00 = 110572.96 FEET.

```

```

*****
FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
-----

```

```

=====
MAINLINE Tc(MIN.) = 101.47
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.696
SUBAREA LOSS RATE DATA(AMC II):
  DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp        Ap      SCS
    LAND USE            GROUP  (ACRES)  (INCH/HR)  (DECIMAL)  CN
COMMERCIAL                B         2.50    0.30    0.100    56
NATURAL FAIR COVER
"GRASS"                   B         2.60    0.30    1.000    69
NATURAL FAIR COVER
"GRASS"                   B         2.80    0.30    1.000    69
NATURAL FAIR COVER
"OPEN BRUSH"              B         5.40    0.30    1.000    66
NATURAL FAIR COVER
"WOODLAND,GRASS"         B         6.20    0.30    1.000    65
NATURAL FAIR COVER
"WOODLAND,GRASS"         B         6.50    0.30    1.000    65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

```

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.913
SUBAREA AREA (ACRES) = 26.00 SUBAREA RUNOFF (CFS) = 9.88
EFFECTIVE AREA (ACRES) = 36158.11 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA (ACRES) = 52184.0 PEAK FLOW RATE (CFS) = 23392.22
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 101.47
* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.696
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"OPEN BRUSH" B 6.70 0.30 1.000 66
NATURAL FAIR COVER
"OPEN BRUSH" B 12.00 0.30 1.000 66
NATURAL FAIR COVER
"CHAPARRAL, BROADLEAF" B 20.30 0.30 1.000 63
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 39.00 SUBAREA RUNOFF (CFS) = 13.91
EFFECTIVE AREA (ACRES) = 36197.11 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA (ACRES) = 52223.0 PEAK FLOW RATE (CFS) = 23392.22
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION (MIN.) = 101.47
RAINFALL INTENSITY (INCH/HR) = 0.70
AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.97
EFFECTIVE STREAM AREA (ACRES) = 36197.11
TOTAL STREAM AREA (ACRES) = 52222.99
PEAK FLOW RATE (CFS) AT CONFLUENCE = 23392.22

FLOW PROCESS FROM NODE 12730.00 TO NODE 12731.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH (FEET) = 561.54
ELEVATION DATA: UPSTREAM (FEET) = 613.29 DOWNSTREAM (FEET) = 551.75

Tc = K * [(LENGTH** 3.00) / (ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 13.823

* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 2.048
SUBAREA Tc AND LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)
NATURAL FAIR COVER
"CHAPARRAL, BROADLEAF" B 6.33 0.30 1.000 63 13.82
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF (CFS) = 9.96
TOTAL AREA (ACRES) = 6.33 PEAK FLOW RATE (CFS) = 9.96

FLOW PROCESS FROM NODE 12731.00 TO NODE 12732.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 551.75 DOWNSTREAM (FEET) = 494.40
CHANNEL LENGTH THRU SUBAREA (FEET) = 971.91 CHANNEL SLOPE = 0.0590
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.73
* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.742
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"OPEN BRUSH" B 34.62 0.30 1.000 66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 32.58
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.24
AVERAGE FLOW DEPTH (FEET) = 0.68 TRAVEL TIME (MIN.) = 3.82
Tc (MIN.) = 17.64
SUBAREA AREA (ACRES) = 34.62 SUBAREA RUNOFF (CFS) = 44.94
EFFECTIVE AREA (ACRES) = 40.95 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 40.9 PEAK FLOW RATE (CFS) = 53.16
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.90

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.90 FLOW VELOCITY (FEET/SEC.) = 4.99
LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12732.00 = 1533.45 FEET.

FLOW PROCESS FROM NODE 12732.00 TO NODE 12733.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 494.40 DOWNSTREAM (FEET) = 431.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 1156.41 CHANNEL SLOPE = 0.0548
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 1.26
* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.573

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	59.52	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 87.31
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.73
AVERAGE FLOW DEPTH(FEET) = 1.22 TRAVEL TIME(MIN.) = 3.36
Tc(MIN.) = 21.00
SUBAREA AREA(ACRES) = 59.52 SUBAREA RUNOFF(CFS) = 68.17
EFFECTIVE AREA(ACRES) = 100.47 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 100.5 PEAK FLOW RATE(CFS) = 115.07
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.43

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.43 FLOW VELOCITY(FEET/SEC.) = 6.26
LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12733.00 = 2689.86 FEET.

FLOW PROCESS FROM NODE 12733.00 TO NODE 12734.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 431.00 DOWNSTREAM(FEET) = 367.10
CHANNEL LENGTH THRU SUBAREA(FEET) = 1654.48 CHANNEL SLOPE = 0.0386
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.84
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.389

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	64.05	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 146.48
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.97
AVERAGE FLOW DEPTH(FEET) = 1.80 TRAVEL TIME(MIN.) = 4.62
Tc(MIN.) = 25.62
SUBAREA AREA(ACRES) = 64.05 SUBAREA RUNOFF(CFS) = 62.77
EFFECTIVE AREA(ACRES) = 164.52 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 164.5 PEAK FLOW RATE(CFS) = 161.23
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.90

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.90 FLOW VELOCITY(FEET/SEC.) = 6.14
LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12734.00 = 4344.34 FEET.

FLOW PROCESS FROM NODE 12734.00 TO NODE 12740.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 367.11 DOWNSTREAM(FEET) = 252.10
CHANNEL LENGTH THRU SUBAREA(FEET) = 1880.98 CHANNEL SLOPE = 0.0611
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.74
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.265

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	26.02	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 172.53
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.37
AVERAGE FLOW DEPTH(FEET) = 1.74 TRAVEL TIME(MIN.) = 4.25
Tc(MIN.) = 29.87
SUBAREA AREA(ACRES) = 26.02 SUBAREA RUNOFF(CFS) = 22.59
EFFECTIVE AREA(ACRES) = 190.54 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 190.5 PEAK FLOW RATE(CFS) = 165.44
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.70

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.70 FLOW VELOCITY(FEET/SEC.) = 7.27
LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12740.00 = 6225.32 FEET.

FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 29.87
RAINFALL INTENSITY(INCH/HR) = 1.26
AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 1.00
EFFECTIVE STREAM AREA(ACRES) = 190.54
TOTAL STREAM AREA(ACRES) = 190.54
PEAK FLOW RATE(CFS) AT CONFLUENCE = 165.44

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13544.85	16.82	1.787	0.30(0.24)	0.81	3288.9	410.00
1	13397.34	18.33	1.705	0.30(0.24)	0.81	3635.1	420.00
1	14497.45	22.39	1.515	0.30(0.24)	0.81	4583.7	310.00

1	14597.53	22.98	1.491	0.30 (0.24)	0.82	4714.1	910.00
1	14606.43	23.04	1.488	0.30 (0.24)	0.82	4733.9	400.00
1	14962.16	25.56	1.391	0.30 (0.25)	0.84	5574.5	430.00
1	15056.12	26.22	1.371	0.30 (0.25)	0.84	5795.8	300.00
1	15085.05	26.43	1.365	0.30 (0.25)	0.84	5866.2	320.00
1	15154.24	27.01	1.348	0.30 (0.25)	0.85	6044.3	818.00
1	15625.70	31.92	1.226	0.30 (0.26)	0.87	7478.4	12710.00
1	15715.52	33.00	1.207	0.30 (0.26)	0.88	7777.6	390.00
1	15728.79	33.15	1.204	0.30 (0.26)	0.88	7821.1	600.00
1	17921.61	51.97	0.945	0.30 (0.28)	0.93	13638.3	40100.00
1	18651.13	61.13	0.869	0.30 (0.28)	0.94	16416.0	11801.00
1	20019.78	74.93	0.802	0.30 (0.29)	0.95	21411.3	11530.00
1	20951.57	83.27	0.761	0.30 (0.29)	0.96	25299.4	11900.00
1	22500.39	93.15	0.719	0.30 (0.29)	0.97	31109.9	11330.00
1	23392.22	101.47	0.696	0.30 (0.29)	0.97	36197.1	10630.00
1	23319.40	107.03	0.681	0.30 (0.29)	0.97	38787.0	12330.00
1	23226.08	113.63	0.663	0.30 (0.29)	0.97	41929.4	11600.00
1	22985.67	119.36	0.647	0.30 (0.29)	0.97	44163.8	11111.00
1	22705.65	125.43	0.636	0.30 (0.29)	0.97	46097.6	12201.00
1	21991.90	134.24	0.621	0.30 (0.29)	0.97	48185.9	12231.00
1	21321.91	141.60	0.608	0.30 (0.29)	0.97	49597.4	10400.00
1	20912.33	145.48	0.601	0.30 (0.29)	0.97	50187.6	10200.00
1	20241.26	152.80	0.589	0.30 (0.29)	0.97	51218.2	10320.00
1	19670.75	157.54	0.581	0.30 (0.29)	0.98	51443.6	10210.00
1	19177.52	162.30	0.572	0.30 (0.29)	0.98	51606.0	12000.00
1	16589.30	190.86	0.534	0.30 (0.29)	0.98	52223.0	10100.00
2	165.44	29.87	1.265	0.30 (0.30)	1.00	190.5	12730.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13688.45	16.82	1.787	0.30 (0.24)	0.82	3396.2	410.00
2	13545.17	18.33	1.705	0.30 (0.24)	0.82	3752.0	420.00
3	14653.63	22.39	1.515	0.30 (0.25)	0.82	4726.5	310.00
4	14754.60	22.98	1.491	0.30 (0.25)	0.82	4860.7	910.00
5	14763.57	23.04	1.488	0.30 (0.25)	0.82	4880.8	400.00
6	15122.18	25.56	1.391	0.30 (0.25)	0.84	5737.5	430.00
7	15217.38	26.22	1.371	0.30 (0.25)	0.84	5963.0	300.00
8	15246.68	26.43	1.365	0.30 (0.25)	0.85	6034.8	320.00
9	15316.78	27.01	1.348	0.30 (0.25)	0.85	6216.6	818.00
10	15594.36	29.87	1.265	0.30 (0.26)	0.87	7070.4	12730.00
11	15784.52	31.92	1.226	0.30 (0.26)	0.88	7669.0	12710.00
12	15871.02	33.00	1.207	0.30 (0.26)	0.88	7968.2	390.00
13	15883.80	33.15	1.204	0.30 (0.26)	0.88	8011.7	600.00
14	18032.19	51.97	0.945	0.30 (0.28)	0.93	13828.8	40100.00
15	18748.78	61.13	0.869	0.30 (0.28)	0.94	16606.5	11801.00
16	20105.84	74.93	0.802	0.30 (0.29)	0.95	21601.8	11530.00
17	21030.62	83.27	0.761	0.30 (0.29)	0.96	25489.9	11900.00
18	22572.29	93.15	0.719	0.30 (0.29)	0.97	31300.5	11330.00
19	23460.18	101.47	0.696	0.30 (0.29)	0.97	36387.7	10630.00
20	23384.71	107.03	0.681	0.30 (0.29)	0.97	38977.5	12330.00
21	23288.26	113.63	0.663	0.30 (0.29)	0.97	42120.0	11600.00
22	23045.14	119.36	0.647	0.30 (0.29)	0.97	44354.3	11111.00
23	22763.21	125.43	0.636	0.30 (0.29)	0.97	46288.1	12201.00
24	22046.88	134.24	0.621	0.30 (0.29)	0.97	48376.4	12231.00

25	21374.71	141.60	0.608	0.30 (0.29)	0.97	49787.9	10400.00
26	20964.00	145.48	0.601	0.30 (0.29)	0.97	50378.2	10200.00
27	20290.77	152.80	0.589	0.30 (0.29)	0.98	51408.7	10320.00
28	19718.87	157.54	0.581	0.30 (0.29)	0.98	51634.2	10210.00
29	19224.23	162.30	0.572	0.30 (0.29)	0.98	51796.5	12000.00
30	16629.35	190.86	0.534	0.30 (0.29)	0.98	52413.5	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 23460.18 Tc (MIN.) = 101.47
EFFECTIVE AREA(ACRES) = 36387.65 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 52413.5
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12740.00 = 110572.96 FEET.

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 252.10 DOWNSTREAM(FEET) = 240.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1220.00 CHANNEL SLOPE = 0.0099
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 6.46
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.693
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS, STRAIGHT ROW"	B	0.30	0.30	1.000	81
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.40	0.30	1.000	65
COMMERCIAL	B	0.40	0.30	0.100	56
COMMERCIAL	B	0.60	0.30	0.100	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.50	0.30	1.000	66
PUBLIC PARK	B	3.20	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.784
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 23461.49
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 15.64
AVERAGE FLOW DEPTH(FEET) = 6.46 TRAVEL TIME(MIN.) = 1.30
Tc(MIN.) = 102.77
SUBAREA AREA(ACRES) = 6.40 SUBAREA RUNOFF(CFS) = 2.63
EFFECTIVE AREA(ACRES) = 36394.05 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 52419.9 PEAK FLOW RATE(CFS) = 23460.18
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 6.46

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 6.46 FLOW VELOCITY(FEET/SEC.) = 15.64
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111792.96 FEET.

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 102.77

* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.693

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "GRASS"	B	3.90	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	8.70	0.30	1.000	69
NATURAL FAIR COVER "WOODLAND,GRASS"	B	10.30	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 22.90 SUBAREA RUNOFF(CFS) = 8.09

EFFECTIVE AREA(ACRES) = 36416.95 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97

TOTAL AREA(ACRES) = 52442.8 PEAK FLOW RATE(CFS) = 23460.18

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 52442.8 TC(MIN.) = 102.77

EFFECTIVE AREA(ACRES) = 36416.95 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.970

PEAK FLOW RATE(CFS) = 23460.18

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13688.45	18.39	1.701	0.30(0.24)	0.82	3425.5	410.00
2	13545.17	19.91	1.619	0.30(0.25)	0.82	3781.3	420.00
3	14653.63	23.92	1.452	0.30(0.25)	0.82	4755.8	310.00
4	14754.60	24.51	1.427	0.30(0.25)	0.82	4890.0	910.00
5	14763.57	24.57	1.425	0.30(0.25)	0.82	4910.1	400.00
6	15122.18	27.07	1.347	0.30(0.25)	0.84	5766.8	430.00
7	15217.38	27.73	1.327	0.30(0.25)	0.84	5992.3	300.00
8	15246.68	27.94	1.321	0.30(0.25)	0.85	6064.1	320.00
9	15316.78	28.52	1.304	0.30(0.26)	0.85	6245.9	818.00
10	15594.36	31.37	1.236	0.30(0.26)	0.87	7099.7	12730.00
11	15784.52	33.42	1.199	0.30(0.26)	0.88	7698.3	12710.00
12	15871.02	34.49	1.180	0.30(0.26)	0.88	7997.5	390.00
13	15883.80	34.64	1.177	0.30(0.26)	0.88	8041.0	600.00
14	18032.19	53.40	0.932	0.30(0.28)	0.93	13858.1	40100.00
15	18748.78	62.54	0.863	0.30(0.28)	0.94	16635.8	11801.00
16	20105.84	76.30	0.795	0.30(0.29)	0.95	21631.1	11530.00
17	21030.62	84.62	0.754	0.30(0.29)	0.96	25519.2	11900.00
18	22572.29	94.46	0.716	0.30(0.29)	0.97	31329.8	11330.00
19	23460.18	102.77	0.693	0.30(0.29)	0.97	36416.9	10630.00
20	23384.71	108.33	0.677	0.30(0.29)	0.97	39006.8	12330.00
21	23288.26	114.93	0.659	0.30(0.29)	0.97	42149.3	11600.00
22	23045.14	120.66	0.644	0.30(0.29)	0.97	44383.6	11111.00
23	22763.21	126.75	0.633	0.30(0.29)	0.97	46317.4	12201.00
24	22046.88	135.57	0.618	0.30(0.29)	0.97	48405.7	12231.00
25	21374.71	142.94	0.606	0.30(0.29)	0.97	49817.2	10400.00
26	20964.00	146.83	0.599	0.30(0.29)	0.97	50407.5	10200.00

27	20290.77	154.16	0.586	0.30(0.29)	0.97	51438.0	10320.00
28	19718.87	158.92	0.578	0.30(0.29)	0.98	51663.5	10210.00
29	19224.23	163.69	0.570	0.30(0.29)	0.98	51825.8	12000.00
30	16629.35	192.32	0.532	0.30(0.29)	0.98	52442.8	10100.00

END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 128 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 10-YR EV FEB 2023 ROKAMOTO *

FILE NAME: RU10EV28.DAT
TIME/DATE OF STUDY: 08:28 02/08/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 10.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 3.879
- 2) 10.00; 2.574
- 3) 15.00; 1.886
- 4) 20.00; 1.614
- 5) 25.00; 1.407
- 6) 30.00; 1.261
- 7) 40.00; 1.080
- 8) 50.00; 0.962
- 9) 60.00; 0.875
- 10) 90.00; 0.728
- 11) 120.00; 0.645
- 12) 180.00; 0.542
- 13) 360.00; 0.402
- 14) 1200.00; 0.177

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU10EV27.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13688.45	18.39	0.30 (0.24)	0.82	3425.5	410.00
2	14763.57	24.57	0.30 (0.25)	0.82	4910.1	400.00
3	15883.80	34.64	0.30 (0.26)	0.88	8041.0	600.00
4	18032.19	53.40	0.30 (0.28)	0.93	13858.1	40100.00
5	18748.78	62.54	0.30 (0.28)	0.94	16635.8	11801.00
6	20105.84	76.30	0.30 (0.29)	0.95	21631.1	11530.00
7	21030.62	84.62	0.30 (0.29)	0.96	25519.2	11900.00
8	22572.29	94.46	0.30 (0.29)	0.97	31329.8	11330.00
9	23460.18	102.77	0.30 (0.29)	0.97	36416.9	10630.00
10	23384.71	108.33	0.30 (0.29)	0.97	39006.8	12330.00
11	23288.26	114.93	0.30 (0.29)	0.97	42149.3	11600.00
12	23045.14	120.66	0.30 (0.29)	0.97	44383.6	11111.00
13	22763.21	126.75	0.30 (0.29)	0.97	46317.4	12201.00
14	22046.88	135.57	0.30 (0.29)	0.97	48405.7	12231.00
15	21374.71	142.94	0.30 (0.29)	0.97	49817.2	10400.00
16	20964.00	146.83	0.30 (0.29)	0.97	50407.5	10200.00
17	20290.77	154.16	0.30 (0.29)	0.97	51438.0	10320.00
18	19718.87	158.92	0.30 (0.29)	0.98	51663.5	10210.00
19	19224.23	163.69	0.30 (0.29)	0.98	51825.8	12000.00
20	16629.35	192.32	0.30 (0.29)	0.98	52442.8	10100.00
TOTAL AREA (ACRES) =						52442.8

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: P501XX10.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	250.32	13.83	0.30 (0.25)	0.84	172.7	50110.00
2	263.89	18.66	0.30 (0.26)	0.85	223.2	50100.00
TOTAL AREA (ACRES) =						223.2

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
------------------	------------	--------------	----------------------	----	---------------	-------------------

1 250.32 13.83 0.30(0.25) 0.84 172.7 50110.00
 2 263.89 18.66 0.30(0.26) 0.85 223.2 50100.00
 TOTAL AREA (ACRES) = 223.2

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	250.32	13.83	2.046	0.30(0.25)	0.84	172.7	50110.00
2	263.89	18.66	1.687	0.30(0.26)	0.85	223.2	50100.00

LONGEST FLOWPATH FROM NODE 50100.00 TO NODE 12800.00 = 4170.00 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13688.45	18.39	1.701	0.30(0.24)	0.82	3425.5	410.00
2	14763.57	24.57	1.425	0.30(0.25)	0.82	4910.1	400.00
3	15883.80	34.64	1.177	0.30(0.26)	0.88	8041.0	600.00
4	18032.19	53.40	0.932	0.30(0.28)	0.93	13858.1	40100.00
5	18748.78	62.54	0.863	0.30(0.28)	0.94	16635.8	11801.00
6	20105.84	76.30	0.795	0.30(0.29)	0.95	21631.1	11530.00
7	21030.62	84.62	0.754	0.30(0.29)	0.96	25519.2	11900.00
8	22572.29	94.46	0.716	0.30(0.29)	0.97	31329.8	11330.00
9	23460.18	102.77	0.693	0.30(0.29)	0.97	36416.9	10630.00
10	23384.71	108.33	0.677	0.30(0.29)	0.97	39006.8	12330.00
11	23288.26	114.93	0.659	0.30(0.29)	0.97	42149.3	11600.00
12	23045.14	120.66	0.644	0.30(0.29)	0.97	44383.6	11111.00
13	22763.21	126.75	0.633	0.30(0.29)	0.97	46317.4	12201.00
14	22046.88	135.57	0.618	0.30(0.29)	0.97	48405.7	12231.00
15	21374.71	142.94	0.606	0.30(0.29)	0.97	49817.2	10400.00
16	20964.00	146.83	0.599	0.30(0.29)	0.97	50407.5	10200.00
17	20290.77	154.16	0.586	0.30(0.29)	0.97	51438.0	10320.00
18	19718.87	158.92	0.578	0.30(0.29)	0.98	51663.5	10210.00
19	19224.23	163.69	0.570	0.30(0.29)	0.98	51825.8	12000.00
20	16629.35	192.32	0.532	0.30(0.29)	0.98	52442.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111792.96 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12984.65	13.83	2.046	0.30(0.25)	0.82	2749.2	50110.00
2	13951.59	18.39	1.701	0.30(0.25)	0.82	3645.9	410.00
3	13999.03	18.66	1.687	0.30(0.25)	0.82	3713.2	50100.00
4	14979.21	24.57	1.425	0.30(0.25)	0.82	5133.3	400.00
5	16053.72	34.64	1.177	0.30(0.26)	0.88	8264.2	600.00
6	18157.04	53.40	0.932	0.30(0.28)	0.93	14081.3	40100.00
7	18860.75	62.54	0.863	0.30(0.28)	0.94	16859.0	11801.00
8	20205.38	76.30	0.795	0.30(0.29)	0.95	21854.3	11530.00
9	21122.65	84.62	0.754	0.30(0.29)	0.96	25742.4	11900.00
10	22657.18	94.46	0.716	0.30(0.29)	0.96	31553.0	11330.00
11	23540.83	102.77	0.693	0.30(0.29)	0.97	36640.1	10630.00
12	23462.53	108.33	0.677	0.30(0.29)	0.97	39230.0	12330.00
13	23362.72	114.93	0.659	0.30(0.29)	0.97	42372.5	11600.00

14	23116.79	120.66	0.644	0.30(0.29)	0.97	44606.8	11111.00
15	22832.94	126.75	0.633	0.30(0.29)	0.97	46540.6	12201.00
16	22113.81	135.57	0.618	0.30(0.29)	0.97	48628.9	12231.00
17	21439.32	142.94	0.606	0.30(0.29)	0.97	50040.4	10400.00
18	21027.37	146.83	0.599	0.30(0.29)	0.97	50630.7	10200.00
19	20351.82	154.16	0.586	0.30(0.29)	0.97	51661.2	10320.00
20	19778.42	158.92	0.578	0.30(0.29)	0.97	51886.7	10210.00
21	19282.28	163.69	0.570	0.30(0.29)	0.97	52049.0	12000.00
22	16680.47	192.32	0.532	0.30(0.29)	0.97	52666.0	10100.00

TOTAL AREA (ACRES) = 52666.0

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 23540.83 Tc (MIN.) = 102.766
 EFFECTIVE AREA (ACRES) = 36640.15 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA (ACRES) = 52666.0
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111792.96 FEET.

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 52666.0 TC (MIN.) = 102.77
 EFFECTIVE AREA (ACRES) = 36640.15 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.969
 PEAK FLOW RATE (CFS) = 23540.83

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12984.65	13.83	2.046	0.30(0.25)	0.82	2749.2	50110.00
2	13951.59	18.39	1.701	0.30(0.25)	0.82	3645.9	410.00
3	13999.03	18.66	1.687	0.30(0.25)	0.82	3713.2	50100.00
4	14979.21	24.57	1.425	0.30(0.25)	0.82	5133.3	400.00
5	16053.72	34.64	1.177	0.30(0.26)	0.88	8264.2	600.00
6	18157.04	53.40	0.932	0.30(0.28)	0.93	14081.3	40100.00
7	18860.75	62.54	0.863	0.30(0.28)	0.94	16859.0	11801.00
8	20205.38	76.30	0.795	0.30(0.29)	0.95	21854.3	11530.00
9	21122.65	84.62	0.754	0.30(0.29)	0.96	25742.4	11900.00
10	22657.18	94.46	0.716	0.30(0.29)	0.96	31553.0	11330.00
11	23540.83	102.77	0.693	0.30(0.29)	0.97	36640.1	10630.00
12	23462.53	108.33	0.677	0.30(0.29)	0.97	39230.0	12330.00
13	23362.72	114.93	0.659	0.30(0.29)	0.97	42372.5	11600.00
14	23116.79	120.66	0.644	0.30(0.29)	0.97	44606.8	11111.00
15	22832.94	126.75	0.633	0.30(0.29)	0.97	46540.6	12201.00
16	22113.81	135.57	0.618	0.30(0.29)	0.97	48628.9	12231.00
17	21439.32	142.94	0.606	0.30(0.29)	0.97	50040.4	10400.00
18	21027.37	146.83	0.599	0.30(0.29)	0.97	50630.7	10200.00
19	20351.82	154.16	0.586	0.30(0.29)	0.97	51661.2	10320.00
20	19778.42	158.92	0.578	0.30(0.29)	0.97	51886.7	10210.00
21	19282.28	163.69	0.570	0.30(0.29)	0.97	52049.0	12000.00
22	16680.47	192.32	0.532	0.30(0.29)	0.97	52666.0	10100.00

END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 129 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 10-YR EV FEB 2023 ROKAMOTO *

FILE NAME: RU10EV29.DAT
TIME/DATE OF STUDY: 08:28 02/08/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 10.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 3.854
- 2) 10.00; 2.561
- 3) 15.00; 1.881
- 4) 20.00; 1.609
- 5) 25.00; 1.403
- 6) 30.00; 1.259
- 7) 40.00; 1.077
- 8) 50.00; 0.959
- 9) 60.00; 0.872
- 10) 90.00; 0.725
- 11) 120.00; 0.641
- 12) 180.00; 0.539
- 13) 360.00; 0.399
- 14) 1200.00; 0.175

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	(FT)	(FT)	SIDE / SIDE/ WAY	(FT)	(FT)	(FT)	(FT)	(n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU10EV28.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12984.65	13.83	0.30 (0.25)	0.82	2749.2	50110.00
2	13999.03	18.66	0.30 (0.25)	0.82	3713.2	50100.00
3	14979.21	24.57	0.30 (0.25)	0.82	5133.3	400.00
4	16053.72	34.64	0.30 (0.26)	0.88	8264.2	600.00
5	18157.04	53.40	0.30 (0.28)	0.93	14081.3	40100.00
6	18860.75	62.54	0.30 (0.28)	0.94	16859.0	11801.00
7	20205.38	76.30	0.30 (0.29)	0.95	21854.3	11530.00
8	21122.65	84.62	0.30 (0.29)	0.96	25742.4	11900.00
9	22657.18	94.46	0.30 (0.29)	0.96	31553.0	11330.00
10	23540.83	102.77	0.30 (0.29)	0.97	36640.1	10630.00
11	23462.53	108.33	0.30 (0.29)	0.97	39230.0	12330.00
12	23362.72	114.93	0.30 (0.29)	0.97	42372.5	11600.00
13	23116.79	120.66	0.30 (0.29)	0.97	44606.8	11111.00
14	22832.94	126.75	0.30 (0.29)	0.97	46540.6	12201.00
15	22113.81	135.57	0.30 (0.29)	0.97	48628.9	12231.00
16	21439.32	142.94	0.30 (0.29)	0.97	50040.4	10400.00
17	20351.82	154.16	0.30 (0.29)	0.97	51661.2	10320.00
18	19778.42	158.92	0.30 (0.29)	0.97	51886.7	10210.00
19	19282.28	163.69	0.30 (0.29)	0.97	52049.0	12000.00
20	16680.47	192.32	0.30 (0.29)	0.97	52666.0	10100.00
TOTAL AREA (ACRES) =						52666.0

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12984.65	13.83	0.30 (0.25)	0.82	2749.2	50110.00
2	13999.03	18.66	0.30 (0.25)	0.82	3713.2	50100.00
3	14979.21	24.57	0.30 (0.25)	0.82	5133.3	400.00
4	16053.72	34.64	0.30 (0.26)	0.88	8264.2	600.00
5	18157.04	53.40	0.30 (0.28)	0.93	14081.3	40100.00
6	18860.75	62.54	0.30 (0.28)	0.94	16859.0	11801.00
7	20205.38	76.30	0.30 (0.29)	0.95	21854.3	11530.00
8	21122.65	84.62	0.30 (0.29)	0.96	25742.4	11900.00
9	22657.18	94.46	0.30 (0.29)	0.96	31553.0	11330.00
10	23540.83	102.77	0.30 (0.29)	0.97	36640.1	10630.00
11	23462.53	108.33	0.30 (0.29)	0.97	39230.0	12330.00
12	23362.72	114.93	0.30 (0.29)	0.97	42372.5	11600.00
13	23116.79	120.66	0.30 (0.29)	0.97	44606.8	11111.00

14	22832.94	126.75	0.30	(0.29)	0.97	46540.6	12201.00
15	22113.81	135.57	0.30	(0.29)	0.97	48628.9	12231.00
16	21439.32	142.94	0.30	(0.29)	0.97	50040.4	10400.00
17	20351.82	154.16	0.30	(0.29)	0.97	51661.2	10320.00
18	19778.42	158.92	0.30	(0.29)	0.97	51886.7	10210.00
19	19282.28	163.69	0.30	(0.29)	0.97	52049.0	12000.00
20	16680.47	192.32	0.30	(0.29)	0.97	52666.0	10100.00

TOTAL AREA (ACRES) = 52666.0

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 12800.00 TO NODE 12901.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 240.00 DOWNSTREAM (FEET) = 216.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 3120.28 CHANNEL SLOPE = 0.0077
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT (FEET) = 6.96
 CHANNEL FLOW THRU SUBAREA (CFS) = 23540.83
 FLOW VELOCITY (FEET/SEC.) = 14.40 FLOW DEPTH (FEET) = 6.96
 TRAVEL TIME (MIN.) = 3.61 Tc (MIN.) = 106.38
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12901.00 = 114913.24 FEET.

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 106.38
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.679
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	14.30	0.30	0.100	56
PUBLIC PARK	B	9.40	0.30	0.850	56

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.397
 SUBAREA AREA (ACRES) = 23.70 SUBAREA RUNOFF (CFS) = 11.94
 EFFECTIVE AREA (ACRES) = 36663.85 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA (ACRES) = 52689.7 PEAK FLOW RATE (CFS) = 23540.83
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 106.38
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.679

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	0.20	0.30	0.100	56
RESIDENTIAL					
"5-7 DWELLINGS/ACRE"	B	0.40	0.30	0.500	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.50	0.30	0.900	56
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.60	0.30	1.000	65
COMMERCIAL	B	0.70	0.30	0.100	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.70	0.30	0.900	56

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.635
 SUBAREA AREA (ACRES) = 3.10 SUBAREA RUNOFF (CFS) = 1.36
 EFFECTIVE AREA (ACRES) = 36666.95 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA (ACRES) = 52692.8 PEAK FLOW RATE (CFS) = 23540.83
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 106.38
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.679
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	0.70	0.30	0.850	56
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	1.00	0.30	1.000	65
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.40	0.30	1.000	66
NATURAL FAIR COVER					
"GRASS"	B	1.50	0.30	1.000	69
COMMERCIAL	B	1.70	0.30	0.100	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.90	0.30	1.000	66

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.822
 SUBAREA AREA (ACRES) = 9.20 SUBAREA RUNOFF (CFS) = 3.58
 EFFECTIVE AREA (ACRES) = 36676.15 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA (ACRES) = 52702.0 PEAK FLOW RATE (CFS) = 23540.83
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 106.38
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.679
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
NATURAL FAIR COVER "WOODLAND, GRASS"	B	3.60	0.30	1.000	65
RESIDENTIAL "5-7 DWELLINGS/ACRE"	B	3.70	0.30	0.500	56
RESIDENTIAL "5-7 DWELLINGS/ACRE"	B	4.10	0.30	0.500	56
RESIDENTIAL ".4 DWELLING/ACRE"	B	5.40	0.30	0.900	56
NATURAL FAIR COVER "OPEN BRUSH"	B	6.70	0.30	1.000	66
NATURAL POOR COVER "BARREN"	B	12.00	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.875
SUBAREA AREA (ACRES) = 35.50 SUBAREA RUNOFF (CFS) = 13.31
EFFECTIVE AREA (ACRES) = 36711.65 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA (ACRES) = 52737.5 PEAK FLOW RATE (CFS) = 23540.83
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<

MAINLINE Tc (MIN.) = 106.38
* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.679
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "GRASS"	B	12.90	0.30	1.000	69
PUBLIC PARK	B	38.60	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.888
SUBAREA AREA (ACRES) = 51.50 SUBAREA RUNOFF (CFS) = 19.14
EFFECTIVE AREA (ACRES) = 36763.15 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA (ACRES) = 52789.0 PEAK FLOW RATE (CFS) = 23540.83
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12901.00 TO NODE 12902.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 216.00 DOWNSTREAM (FEET) = 215.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 122.04 CHANNEL SLOPE = 0.0082
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 6.84
CHANNEL FLOW THRU SUBAREA (CFS) = 23540.83
FLOW VELOCITY (FEET/SEC.) = 14.70 FLOW DEPTH (FEET) = 6.84
TRAVEL TIME (MIN.) = 0.14 Tc (MIN.) = 106.52
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115035.28 FEET.

FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<<

PEAK FLOWRATE TABLE FILE NAME: P503XX10.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1147.25	19.67	0.30 (0.22)	0.74	1015.8	50320.00
2	1155.57	20.90	0.30 (0.22)	0.74	1063.4	50240.00
3	1161.70	21.75	0.30 (0.22)	0.74	1095.6	50330.00
4	1155.23	24.73	0.30 (0.22)	0.74	1192.0	50280.00
5	1146.67	25.95	0.30 (0.22)	0.74	1221.5	50300.00
6	1124.24	27.59	0.30 (0.22)	0.74	1248.7	50220.00
7	1033.51	32.98	0.30 (0.22)	0.74	1294.8	50260.00
8	999.73	34.83	0.30 (0.22)	0.74	1298.6	50200.00
TOTAL AREA (ACRES) =		1298.6				

FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12984.65	18.44	1.694	0.30 (0.24)	0.82	2872.2	50110.00
2	13999.03	23.15	1.479	0.30 (0.25)	0.82	3836.2	50100.00
3	14979.21	28.95	1.289	0.30 (0.25)	0.82	5256.3	400.00
4	16053.72	38.92	1.097	0.30 (0.26)	0.88	8387.2	600.00
5	18157.04	57.50	0.894	0.30 (0.28)	0.93	14204.3	40100.00
6	18860.75	66.58	0.840	0.30 (0.28)	0.94	16982.0	11801.00
7	20205.38	80.25	0.773	0.30 (0.28)	0.95	21977.3	11530.00
8	21122.65	88.51	0.732	0.30 (0.29)	0.96	25865.4	11900.00
9	22657.18	98.26	0.702	0.30 (0.29)	0.96	31676.0	11330.00
10	23540.83	106.52	0.679	0.30 (0.29)	0.97	36763.1	10630.00
11	23462.53	112.08	0.663	0.30 (0.29)	0.97	39353.0	12330.00
12	23362.72	118.69	0.645	0.30 (0.29)	0.97	42495.5	11600.00
13	23116.79	124.44	0.633	0.30 (0.29)	0.97	44729.8	11111.00
14	22832.94	130.54	0.623	0.30 (0.29)	0.97	46663.6	12201.00
15	22113.81	139.40	0.608	0.30 (0.29)	0.97	48751.9	12231.00
16	21439.32	146.81	0.595	0.30 (0.29)	0.97	50163.4	10400.00
17	20351.82	158.10	0.576	0.30 (0.29)	0.97	51784.2	10320.00
18	19778.42	162.90	0.568	0.30 (0.29)	0.97	52009.7	10210.00
19	19282.28	167.70	0.560	0.30 (0.29)	0.97	52172.0	12000.00
20	16680.47	196.55	0.526	0.30 (0.29)	0.97	52789.0	10100.00
LONGEST FLOWPATH FROM NODE		10100.00 TO NODE 12902.00 = 115035.28 FEET.					

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1147.25	19.67	1.627	0.30 (0.22)	0.74	1015.8	50320.00
2	1155.57	20.90	1.572	0.30 (0.22)	0.74	1063.4	50240.00
3	1161.70	21.75	1.537	0.30 (0.22)	0.74	1095.6	50330.00
4	1155.23	24.73	1.414	0.30 (0.22)	0.74	1192.0	50280.00
5	1146.67	25.95	1.376	0.30 (0.22)	0.74	1221.5	50300.00

6 1124.24 27.59 1.328 0.30(0.22) 0.74 1248.7 50220.00
 7 1033.51 32.98 1.205 0.30(0.22) 0.74 1294.8 50260.00
 8 999.73 34.83 1.171 0.30(0.22) 0.74 1298.6 50200.00
 LONGEST FLOWPATH FROM NODE 50220.00 TO NODE 12902.00 = 17597.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14111.42	18.44	1.694	0.30(0.24)	0.80	3824.5	50110.00
2	14396.86	19.67	1.627	0.30(0.24)	0.80	4139.8	50320.00
3	14668.66	20.90	1.572	0.30(0.24)	0.80	4437.8	50240.00
4	14859.55	21.75	1.537	0.30(0.24)	0.80	4645.5	50330.00
5	15157.70	23.15	1.479	0.30(0.24)	0.80	4976.9	50100.00
6	15421.79	24.73	1.414	0.30(0.24)	0.80	5415.7	50280.00
7	15619.72	25.95	1.376	0.30(0.24)	0.80	5744.4	50300.00
8	15874.11	27.59	1.328	0.30(0.24)	0.81	6172.8	50220.00
9	16080.61	28.95	1.289	0.30(0.24)	0.81	6516.6	400.00
10	16447.23	32.98	1.205	0.30(0.25)	0.83	7817.1	50260.00
11	16612.68	34.83	1.171	0.30(0.25)	0.84	8401.5	50200.00
12	16974.97	38.92	1.097	0.30(0.26)	0.86	9685.8	600.00
13	18864.53	57.50	0.894	0.30(0.27)	0.91	15502.9	40100.00
14	19511.28	66.58	0.840	0.30(0.28)	0.92	18280.6	11801.00
15	20785.35	80.25	0.773	0.30(0.28)	0.94	23275.9	11530.00
16	21659.96	88.51	0.732	0.30(0.28)	0.95	27164.0	11900.00
17	23162.40	98.26	0.702	0.30(0.29)	0.96	32974.6	11330.00
18	24021.70	106.52	0.679	0.30(0.29)	0.96	38061.8	10630.00
19	23926.97	112.08	0.663	0.30(0.29)	0.96	40651.6	12330.00
20	23807.66	118.69	0.645	0.30(0.29)	0.96	43794.1	11600.00
21	23549.92	124.44	0.633	0.30(0.29)	0.97	46028.4	11111.00
22	23255.14	130.54	0.623	0.30(0.29)	0.97	47962.2	12201.00
23	22520.13	139.40	0.608	0.30(0.29)	0.97	50050.5	12231.00
24	21832.35	146.81	0.595	0.30(0.29)	0.97	51462.0	10400.00
25	20724.63	158.10	0.576	0.30(0.29)	0.97	53082.8	10320.00
26	20142.64	162.90	0.568	0.30(0.29)	0.97	53308.3	10210.00
27	19637.88	167.70	0.560	0.30(0.29)	0.97	53470.6	12000.00
28	17000.48	196.55	0.526	0.30(0.29)	0.97	54087.6	10100.00

TOTAL AREA (ACRES) = 54087.6

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 24021.70 Tc (MIN.) = 106.516
 EFFECTIVE AREA (ACRES) = 38061.75 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
 TOTAL AREA (ACRES) = 54087.6
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115035.28 FEET.

 FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<<

 FLOW PROCESS FROM NODE 12902.00 TO NODE 12903.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 215.00 DOWNSTREAM (FEET) = 214.00

CHANNEL LENGTH THRU SUBAREA (FEET) = 895.53 CHANNEL SLOPE = 0.0011
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT (FEET) = 12.16
 CHANNEL FLOW THRU SUBAREA (CFS) = 24021.70
 FLOW VELOCITY (FEET/SEC.) = 7.58 FLOW DEPTH (FEET) = 12.16
 TRAVEL TIME (MIN.) = 1.97 Tc (MIN.) = 108.49
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115930.81 FEET.

 FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: P504XX10.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	96.33	13.93	0.30(0.28)	0.94		70.7	50400.00
TOTAL AREA (ACRES) =							70.7

 FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14111.42	20.78	1.577	0.30(0.24)	0.80	3824.5	50110.00
2	14396.86	22.00	1.527	0.30(0.24)	0.80	4139.8	50320.00
3	14668.66	23.21	1.477	0.30(0.24)	0.80	4437.8	50240.00
4	14859.55	24.05	1.442	0.30(0.24)	0.80	4645.5	50330.00
5	15157.70	25.44	1.390	0.30(0.24)	0.80	4976.9	50100.00
6	15421.79	27.00	1.345	0.30(0.24)	0.80	5415.7	50280.00
7	15619.72	28.22	1.310	0.30(0.24)	0.80	5744.4	50300.00
8	15874.11	29.84	1.264	0.30(0.24)	0.81	6172.8	50220.00
9	16080.61	31.19	1.237	0.30(0.24)	0.81	6516.6	400.00
10	16447.23	35.21	1.164	0.30(0.25)	0.83	7817.1	50260.00
11	16612.68	37.05	1.131	0.30(0.25)	0.84	8401.5	50200.00
12	16974.97	41.12	1.064	0.30(0.26)	0.86	9685.8	600.00
13	18864.53	59.62	0.875	0.30(0.27)	0.91	15502.9	40100.00
14	19511.28	68.69	0.829	0.30(0.28)	0.92	18280.6	11801.00
15	20785.35	82.31	0.763	0.30(0.28)	0.94	23275.9	11530.00
16	21659.96	90.54	0.723	0.30(0.28)	0.95	27164.0	11900.00
17	23162.40	100.26	0.696	0.30(0.29)	0.96	32974.6	11330.00
18	24021.70	108.49	0.673	0.30(0.29)	0.96	38061.8	10630.00
19	23926.97	114.06	0.658	0.30(0.29)	0.96	40651.6	12330.00
20	23807.66	120.66	0.640	0.30(0.29)	0.96	43794.1	11600.00
21	23549.92	126.42	0.630	0.30(0.29)	0.97	46028.4	11111.00
22	23255.14	132.53	0.620	0.30(0.29)	0.97	47962.2	12201.00
23	22520.13	141.41	0.605	0.30(0.29)	0.97	50050.5	12231.00
24	21832.35	148.85	0.592	0.30(0.29)	0.97	51462.0	10400.00
25	20724.63	160.17	0.573	0.30(0.29)	0.97	53082.8	10320.00
26	20142.64	164.98	0.565	0.30(0.29)	0.97	53308.3	10210.00
27	19637.88	169.80	0.556	0.30(0.29)	0.97	53470.6	12000.00
28	17000.48	198.75	0.524	0.30(0.29)	0.97	54087.6	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115930.81 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	96.33	13.93	2.027	0.30(0.28)	0.94	70.7	50400.00

LONGEST FLOWPATH FROM NODE 50400.00 TO NODE 12903.00 = 3607.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12735.41	13.93	2.027	0.30(0.24)	0.80	2633.6	50400.00
2	14182.90	20.78	1.577	0.30(0.24)	0.80	3895.2	50110.00
3	14465.59	22.00	1.527	0.30(0.24)	0.80	4210.5	50320.00
4	14734.64	23.21	1.477	0.30(0.24)	0.80	4508.5	50240.00
5	14923.60	24.05	1.442	0.30(0.24)	0.80	4716.2	50330.00
6	15218.90	25.44	1.390	0.30(0.24)	0.80	5047.6	50100.00
7	15480.50	27.00	1.345	0.30(0.24)	0.80	5486.4	50280.00
8	15676.50	28.22	1.310	0.30(0.24)	0.80	5815.1	50300.00
9	15928.31	29.84	1.264	0.30(0.24)	0.81	6243.5	50220.00
10	16133.37	31.19	1.237	0.30(0.24)	0.81	6587.3	400.00
11	16495.95	35.21	1.164	0.30(0.25)	0.83	7887.8	50260.00
12	16659.55	37.05	1.131	0.30(0.25)	0.84	8472.2	50200.00
13	17018.15	41.12	1.064	0.30(0.26)	0.86	9756.5	600.00
14	18897.30	59.62	0.875	0.30(0.27)	0.91	15573.6	40100.00
15	19541.52	68.69	0.829	0.30(0.28)	0.92	18351.3	11801.00
16	20811.91	82.31	0.763	0.30(0.28)	0.94	23346.6	11530.00
17	21684.36	90.54	0.723	0.30(0.28)	0.95	27234.7	11900.00
18	23185.30	100.26	0.696	0.30(0.29)	0.96	33045.3	11330.00
19	24043.32	108.49	0.673	0.30(0.29)	0.96	38132.4	10630.00
20	23947.74	114.06	0.658	0.30(0.29)	0.96	40722.3	12330.00
21	23827.45	120.66	0.640	0.30(0.29)	0.96	43864.8	11600.00
22	23569.16	126.42	0.630	0.30(0.29)	0.97	46099.1	11111.00
23	23273.82	132.53	0.620	0.30(0.29)	0.97	48032.9	12201.00
24	22537.97	141.41	0.605	0.30(0.29)	0.97	50121.2	12231.00
25	21849.50	148.85	0.592	0.30(0.29)	0.97	51532.7	10400.00
26	20740.71	160.17	0.573	0.30(0.29)	0.97	53153.5	10320.00
27	20158.27	164.98	0.565	0.30(0.29)	0.97	53379.0	10210.00
28	19653.06	169.80	0.556	0.30(0.29)	0.97	53541.3	12000.00
29	17013.90	198.75	0.524	0.30(0.29)	0.97	54158.3	10100.00

TOTAL AREA (ACRES) = 54158.3

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 24043.32 Tc (MIN.) = 108.486
EFFECTIVE AREA (ACRES) = 38132.45 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA (ACRES) = 54158.3
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115930.81 FEET.

FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

FLOW PROCESS FROM NODE 12903.00 TO NODE 12904.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 214.00 DOWNSTREAM (FEET) = 213.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 767.57 CHANNEL SLOPE = 0.0013
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 11.65
CHANNEL FLOW THRU SUBAREA (CFS) = 24043.32
FLOW VELOCITY (FEET/SEC.) = 7.99 FLOW DEPTH (FEET) = 11.65
TRAVEL TIME (MIN.) = 1.60 Tc (MIN.) = 110.09
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116698.38 FEET.

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 3B10EVRL.DNA
MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	285.43	17.62	0.30(0.13)	0.43	0.43	197.2	203.00
2	284.16	20.09	0.30(0.13)	0.43	0.43	213.7	210.00

TOTAL AREA (ACRES) = 213.7

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12735.41	15.90	1.832	0.30(0.24)	0.80	2633.6	50400.00
2	14182.90	22.68	1.498	0.30(0.24)	0.80	3895.2	50110.00
3	14465.59	23.88	1.449	0.30(0.24)	0.80	4210.5	50320.00
4	14734.64	25.08	1.401	0.30(0.24)	0.80	4508.5	50240.00
5	14923.60	25.92	1.376	0.30(0.24)	0.80	4716.2	50330.00
6	15218.90	27.29	1.337	0.30(0.24)	0.80	5047.6	50100.00
7	15480.50	28.85	1.292	0.30(0.24)	0.80	5486.4	50280.00
8	15676.50	30.06	1.258	0.30(0.24)	0.80	5815.1	50300.00
9	15928.31	31.67	1.229	0.30(0.24)	0.81	6243.5	50220.00
10	16133.37	33.01	1.204	0.30(0.24)	0.81	6587.3	400.00
11	16495.95	37.01	1.131	0.30(0.25)	0.83	7887.8	50260.00
12	16659.55	38.85	1.098	0.30(0.25)	0.84	8472.2	50200.00
13	17018.15	42.91	1.043	0.30(0.26)	0.86	9756.5	600.00
14	18897.30	61.35	0.865	0.30(0.27)	0.91	15573.6	40100.00
15	19541.52	70.40	0.821	0.30(0.28)	0.92	18351.3	11801.00
16	20811.91	83.99	0.754	0.30(0.28)	0.94	23346.6	11530.00
17	21684.36	92.20	0.719	0.30(0.28)	0.95	27234.7	11900.00
18	23185.30	101.88	0.692	0.30(0.29)	0.96	33045.3	11330.00
19	24043.32	110.09	0.669	0.30(0.29)	0.96	38132.4	10630.00
20	23947.74	115.66	0.653	0.30(0.29)	0.96	40722.3	12330.00
21	23827.45	122.27	0.637	0.30(0.29)	0.96	43864.8	11600.00
22	23569.16	128.03	0.627	0.30(0.29)	0.97	46099.1	11111.00
23	23273.82	134.15	0.617	0.30(0.29)	0.97	48032.9	12201.00

24	22537.97	143.05	0.602	0.30(0.29)	0.97	50121.2	12231.00
25	21849.50	150.50	0.589	0.30(0.29)	0.97	51532.7	10400.00
26	20740.71	161.85	0.570	0.30(0.29)	0.97	53153.5	10320.00
27	20158.27	166.68	0.562	0.30(0.29)	0.97	53379.0	10210.00
28	19653.06	171.51	0.553	0.30(0.29)	0.97	53541.3	12000.00
29	17013.90	200.54	0.523	0.30(0.29)	0.97	54158.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116698.38 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	285.43	17.62	1.739	0.30(0.13)	0.43	197.2	203.00
2	284.16	20.09	1.605	0.30(0.13)	0.43	213.7	210.00

LONGEST FLOWPATH FROM NODE 210.00 TO NODE 12904.00 = 7986.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13007.95	15.90	1.832	0.30(0.23)	0.78	2811.5	50400.00
2	13387.98	17.62	1.739	0.30(0.23)	0.78	3150.8	203.00
3	13913.41	20.09	1.605	0.30(0.23)	0.78	3626.4	210.00
4	14446.50	22.68	1.498	0.30(0.23)	0.78	4108.9	50110.00
5	14719.66	23.88	1.449	0.30(0.23)	0.78	4424.2	50320.00
6	14979.42	25.08	1.401	0.30(0.24)	0.78	4722.2	50240.00
7	15163.73	25.92	1.376	0.30(0.24)	0.79	4929.9	50330.00
8	15451.44	27.29	1.337	0.30(0.24)	0.79	5261.3	50100.00
9	15704.40	28.85	1.292	0.30(0.24)	0.79	5700.1	50280.00
10	15893.84	30.06	1.258	0.30(0.24)	0.79	6028.8	50300.00
11	16140.00	31.67	1.229	0.30(0.24)	0.79	6457.2	50220.00
12	16340.37	33.01	1.204	0.30(0.24)	0.80	6801.0	400.00
13	16688.93	37.01	1.131	0.30(0.25)	0.82	8101.5	50260.00
14	16846.10	38.85	1.098	0.30(0.25)	0.83	8685.9	50200.00
15	17194.06	42.91	1.043	0.30(0.26)	0.85	9970.2	600.00
16	19039.13	61.35	0.865	0.30(0.27)	0.90	15787.3	40100.00
17	19674.82	70.40	0.821	0.30(0.28)	0.92	18565.0	11801.00
18	20932.41	83.99	0.754	0.30(0.28)	0.93	23560.3	11530.00
19	21798.01	92.20	0.719	0.30(0.28)	0.94	27448.4	11900.00
20	23293.73	101.88	0.692	0.30(0.29)	0.95	33259.0	11330.00
21	24147.34	110.09	0.669	0.30(0.29)	0.96	38346.1	10630.00
22	24048.75	115.66	0.653	0.30(0.29)	0.96	40936.0	12330.00
23	23925.38	122.27	0.637	0.30(0.29)	0.96	44078.5	11600.00
24	23665.21	128.03	0.627	0.30(0.29)	0.96	46312.8	11111.00
25	23367.87	134.15	0.617	0.30(0.29)	0.96	48246.6	12201.00
26	22629.11	143.05	0.602	0.30(0.29)	0.96	50334.9	12231.00
27	21938.20	150.50	0.589	0.30(0.29)	0.97	51746.4	10400.00
28	20825.71	161.85	0.570	0.30(0.29)	0.97	53367.2	10320.00
29	20241.68	166.68	0.562	0.30(0.29)	0.97	53592.7	10210.00
30	19734.89	171.51	0.553	0.30(0.29)	0.97	53755.0	12000.00
31	17089.88	200.54	0.523	0.30(0.29)	0.97	54372.0	10100.00

TOTAL AREA (ACRES) = 54372.0

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 24147.34 Tc(MIN.) = 110.088
EFFECTIVE AREA(ACRES) = 38346.15 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94
TOTAL AREA(ACRES) = 54372.0
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116698.38 FEET.

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 110.09
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.669
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
RESIDENTIAL
".4 DWELLING/ACRE" B 0.10 0.30 0.900 56
NATURAL FAIR COVER
"WOODLAND,GRASS" B 0.20 0.30 1.000 65
NATURAL FAIR COVER
"WOODLAND,GRASS" B 0.80 0.30 1.000 65
COMMERCIAL B 1.20 0.30 0.100 56
COMMERCIAL B 1.50 0.30 0.100 56
NATURAL FAIR COVER
"GRASS" B 3.00 0.30 1.000 69
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.641
SUBAREA AREA(ACRES) = 6.80 SUBAREA RUNOFF(CFS) = 2.92
EFFECTIVE AREA(ACRES) = 38352.95 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA(ACRES) = 54378.8 PEAK FLOW RATE(CFS) = 24147.34
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 110.09
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.669
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"GRASS" B 3.60 0.30 1.000 69
PUBLIC PARK B 15.10 0.30 0.850 56
NATURAL FAIR COVER
"GRASS" B 20.00 0.30 1.000 69
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.941
SUBAREA AREA(ACRES) = 38.70 SUBAREA RUNOFF(CFS) = 13.46
EFFECTIVE AREA(ACRES) = 38391.65 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA(ACRES) = 54417.5 PEAK FLOW RATE(CFS) = 24147.34
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 54417.5 TC(MIN.) = 110.09
EFFECTIVE AREA(ACRES) = 38391.65 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.958
PEAK FLOW RATE(CFS) = 24147.34

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13007.95	15.90	1.832	0.30(0.23)	0.78	2857.0	50400.00
2	13387.98	17.62	1.739	0.30(0.23)	0.78	3196.3	203.00
3	13913.41	20.09	1.605	0.30(0.23)	0.78	3671.9	210.00
4	14446.50	22.68	1.498	0.30(0.23)	0.78	4154.4	50110.00
5	14719.66	23.88	1.449	0.30(0.23)	0.78	4469.7	50320.00
6	14979.42	25.08	1.401	0.30(0.24)	0.79	4767.7	50240.00
7	15163.73	25.92	1.376	0.30(0.24)	0.79	4975.4	50330.00
8	15451.44	27.29	1.337	0.30(0.24)	0.79	5306.8	50100.00
9	15704.40	28.85	1.292	0.30(0.24)	0.79	5745.6	50280.00
10	15893.84	30.06	1.258	0.30(0.24)	0.79	6074.3	50300.00
11	16140.00	31.67	1.229	0.30(0.24)	0.79	6502.7	50220.00
12	16340.37	33.01	1.204	0.30(0.24)	0.80	6846.5	400.00
13	16688.93	37.01	1.131	0.30(0.25)	0.82	8147.0	50260.00
14	16846.10	38.85	1.098	0.30(0.25)	0.83	8731.4	50200.00
15	17194.06	42.91	1.043	0.30(0.26)	0.85	10015.7	600.00
16	19039.13	61.35	0.865	0.30(0.27)	0.90	15832.8	40100.00
17	19674.82	70.40	0.821	0.30(0.28)	0.92	18610.5	11801.00
18	20932.41	83.99	0.754	0.30(0.28)	0.93	23605.8	11530.00
19	21798.01	92.20	0.719	0.30(0.28)	0.94	27493.9	11900.00
20	23293.73	101.88	0.692	0.30(0.29)	0.95	33304.5	11330.00
21	24147.34	110.09	0.669	0.30(0.29)	0.96	38391.6	10630.00
22	24048.75	115.66	0.653	0.30(0.29)	0.96	40981.5	12330.00
23	23925.38	122.27	0.637	0.30(0.29)	0.96	44124.0	11600.00
24	23665.21	128.03	0.627	0.30(0.29)	0.96	46358.3	11111.00
25	23367.87	134.15	0.617	0.30(0.29)	0.96	48292.1	12201.00
26	22629.11	143.05	0.602	0.30(0.29)	0.96	50380.4	12231.00
27	21938.20	150.50	0.589	0.30(0.29)	0.97	51791.9	10400.00
28	20825.71	161.85	0.570	0.30(0.29)	0.97	53412.7	10320.00
29	20241.68	166.68	0.562	0.30(0.29)	0.97	53638.2	10210.00
30	19734.89	171.51	0.553	0.30(0.29)	0.97	53800.5	12000.00
31	17089.88	200.54	0.523	0.30(0.29)	0.97	54417.5	10100.00

=====
 END OF RATIONAL METHOD ANALYSIS
 =====

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 133 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 10-YR EV FEB 2023 ROKAMOTO *

FILE NAME: RU10EV33.DAT
TIME/DATE OF STUDY: 08:49 02/08/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 10.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 3.774
- 2) 10.00; 2.517
- 3) 15.00; 1.863
- 4) 20.00; 1.593
- 5) 25.00; 1.391
- 6) 30.00; 1.250
- 7) 40.00; 1.068
- 8) 50.00; 0.950
- 9) 60.00; 0.862
- 10) 90.00; 0.714
- 11) 120.00; 0.630
- 12) 180.00; 0.528
- 13) 360.00; 0.388
- 14) 1200.00; 0.170

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL: IN- / OUT-/PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:

- 1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13112.00 TO NODE 13222.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: S31X10.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1716.14	38.98	0.30 (0.24)	0.81	2485.1	13100.00
2	1689.35	68.05	0.30 (0.24)	0.81	3778.1	13000.00
3	1657.69	70.37	0.30 (0.24)	0.81	3796.8	13010.00
TOTAL AREA (ACRES) =						3796.8

FLOW PROCESS FROM NODE 13221.00 TO NODE 13222.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: S32X10.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	821.94	36.32	0.30 (0.25)	0.83	1125.1	13210.00
2	821.47	36.44	0.30 (0.25)	0.83	1127.6	13200.00
TOTAL AREA (ACRES) =						1127.6

FLOW PROCESS FROM NODE 13221.00 TO NODE 13222.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	821.94	36.32	0.30 (0.25)	0.83	1125.1	13210.00
2	821.47	36.44	0.30 (0.25)	0.83	1127.6	13200.00
TOTAL AREA (ACRES) =						1127.6

FLOW PROCESS FROM NODE 13112.00 TO NODE 13222.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

=====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	821.94	36.32	1.135	0.30 (0.25)	0.83	1125.1	13210.00
2	821.47	36.44	1.133	0.30 (0.25)	0.83	1127.6	13200.00
LONGEST FLOWPATH FROM NODE 13200.00 TO NODE 13222.00 =							16821.05 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1716.14	38.98	1.087	0.30(0.24)	0.81	2485.1	13100.00
2	1689.35	68.05	0.822	0.30(0.24)	0.81	3778.1	13000.00
3	1657.69	70.37	0.811	0.30(0.24)	0.81	3796.8	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13222.00 = 32126.49 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2512.74	36.32	1.135	0.30(0.24)	0.82	3440.8	13210.00
2	2513.70	36.44	1.133	0.30(0.24)	0.82	3450.9	13200.00
3	2494.71	38.98	1.087	0.30(0.24)	0.82	3612.7	13100.00
4	2222.44	68.05	0.822	0.30(0.24)	0.81	4905.7	13000.00
5	2180.16	70.37	0.811	0.30(0.24)	0.81	4924.4	13010.00

TOTAL AREA (ACRES) = 4924.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 2513.70 Tc(MIN.) = 36.438

EFFECTIVE AREA(ACRES) = 3450.86 AREA-AVERAGED Fm(INCH/HR) = 0.24

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82

TOTAL AREA (ACRES) = 4924.4

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13222.00 = 32126.49 FEET.

FLOW PROCESS FROM NODE 13222.00 TO NODE 13222.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

=====

FLOW PROCESS FROM NODE 13222.00 TO NODE 13222.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

=====

FLOW PROCESS FROM NODE 13222.00 TO NODE 13301.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 427.51 DOWNSTREAM(FEET) = 382.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 2533.33 CHANNEL SLOPE = 0.0180

GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 3.83

* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.064

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	1.40	0.30	0.100	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	15.60	0.30	1.000	66
RESIDENTIAL					
"3-4 DWELLINGS/ACRE"	B	0.10	0.30	0.600	56
AGRICULTURAL POOR COVER					

"ROW CROPS,CONTOURED"	B	5.30	0.30	1.000	79
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86
COMMERCIAL	B	22.60	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.521

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2532.15

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.74

AVERAGE FLOW DEPTH(FEET) = 3.83 TRAVEL TIME(MIN.) = 3.93

Tc(MIN.) = 40.37

SUBAREA AREA(ACRES) = 45.20 SUBAREA RUNOFF(CFS) = 36.91

EFFECTIVE AREA(ACRES) = 3496.06 AREA-AVERAGED Fm(INCH/HR) = 0.24

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81

TOTAL AREA(ACRES) = 4969.6 PEAK FLOW RATE(CFS) = 2580.54

GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 3.87

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 3.87 FLOW VELOCITY(FEET/SEC.) = 10.82

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2577.71	40.24	1.065	0.30(0.24)	0.81	3486.0	13210.00
2	2580.54	40.37	1.064	0.30(0.24)	0.81	3496.1	13200.00
3	2601.28	42.91	1.034	0.30(0.24)	0.81	3657.9	13100.00
4	2491.96	72.14	0.802	0.30(0.24)	0.81	4950.9	13000.00
5	2449.85	74.49	0.791	0.30(0.24)	0.81	4969.6	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2601.28 Tc(MIN.) = 42.91

AREA-AVERAGED Fm(INCH/HR) = 0.24 AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.81 EFFECTIVE AREA(ACRES) = 3657.90

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 42.91

* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.034

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	1.00	0.30	1.000	79
NATURAL POOR COVER					
"BARREN"	B	0.50	0.30	1.000	86
COMMERCIAL	B	7.40	0.30	0.100	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	4.70	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	2.90	0.30	1.000	65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.596					
SUBAREA AREA(ACRES) = 16.50 SUBAREA RUNOFF(CFS) = 12.69					
EFFECTIVE AREA(ACRES) = 3674.40 AREA-AVERAGED Fm(INCH/HR) = 0.24					

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81
TOTAL AREA (ACRES) = 4986.1 PEAK FLOW RATE (CFS) = 2613.98

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
MAINLINE Tc (MIN.) = 42.91					
* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.034					
SUBAREA LOSS RATE DATA (AMC II):					
NATURAL POOR COVER					
"BARREN"	B	1.30	0.30	1.000	86
COMMERCIAL	B	0.20	0.30	0.100	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	5.30	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.30	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	0.20	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.60	0.30	1.000	66
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30					
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.977					
SUBAREA AREA (ACRES) = 7.90 SUBAREA RUNOFF (CFS) = 5.26					
EFFECTIVE AREA (ACRES) = 3682.30 AREA-AVERAGED Fm (INCH/HR) = 0.24					
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81					
TOTAL AREA (ACRES) = 4994.0 PEAK FLOW RATE (CFS) = 2619.24					

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
MAINLINE Tc (MIN.) = 42.91					
* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.034					
SUBAREA LOSS RATE DATA (AMC II):					
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	4.30	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.80	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	1.10	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	6.90	0.30	1.000	66
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	7.90	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	1.00	0.30	1.000	65
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30					
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000					
SUBAREA AREA (ACRES) = 22.00 SUBAREA RUNOFF (CFS) = 14.53					
EFFECTIVE AREA (ACRES) = 3704.30 AREA-AVERAGED Fm (INCH/HR) = 0.24					
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81					

TOTAL AREA (ACRES) = 5016.0 PEAK FLOW RATE (CFS) = 2633.77

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
MAINLINE Tc (MIN.) = 42.91					
* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.034					
SUBAREA LOSS RATE DATA (AMC II):					
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.40	0.30	1.000	66
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	14.60	0.30	1.000	79
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30					
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000					
SUBAREA AREA (ACRES) = 15.00 SUBAREA RUNOFF (CFS) = 9.90					
EFFECTIVE AREA (ACRES) = 3719.30 AREA-AVERAGED Fm (INCH/HR) = 0.24					
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81					
TOTAL AREA (ACRES) = 5031.0 PEAK FLOW RATE (CFS) = 2643.67					

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<

FLOW PROCESS FROM NODE 31100.00 TO NODE 31101.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH (FEET) = 317.00
ELEVATION DATA: UPSTREAM (FEET) = 801.00 DOWNSTREAM (FEET) = 685.00

Tc = K * [(LENGTH ** 3.00) / (ELEVATION CHANGE)] ** 0.20
SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 8.641
* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 2.859
SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER						
"CHAPARRAL, BROADLEAF"	B	0.50	0.30	1.000	63	8.64
NATURAL FAIR COVER						
"OPEN BRUSH"	B	0.30	0.30	1.000	66	8.64
NATURAL FAIR COVER						
"OPEN BRUSH"	B	0.30	0.30	1.000	66	8.64
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30						
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000						
SUBAREA RUNOFF (CFS) = 2.53						
TOTAL AREA (ACRES) = 1.10 PEAK FLOW RATE (CFS) = 2.53						

FLOW PROCESS FROM NODE 31101.00 TO NODE 31102.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 685.00 DOWNSTREAM(FEET) = 655.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 135.00 CHANNEL SLOPE = 0.2222
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.768

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	B	0.50	0.30	1.000	63
---	---	------	------	-------	----

NATURAL FAIR COVER "OPEN BRUSH"	B	0.10	0.30	1.000	66
------------------------------------	---	------	------	-------	----

NATURAL FAIR COVER "OPEN BRUSH"	B	0.70	0.30	1.000	66
------------------------------------	---	------	------	-------	----

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3.98

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.25

AVERAGE FLOW DEPTH(FEET) = 0.46 TRAVEL TIME(MIN.) = 0.36

Tc(MIN.) = 9.00

SUBAREA AREA(ACRES) = 1.30 SUBAREA RUNOFF(CFS) = 2.89

EFFECTIVE AREA(ACRES) = 2.40 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 2.4 PEAK FLOW RATE(CFS) = 5.33

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.51 FLOW VELOCITY(FEET/SEC.) = 6.88

LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31102.00 = 452.00 FEET.

FLOW PROCESS FROM NODE 31102.00 TO NODE 31103.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 655.00 DOWNSTREAM(FEET) = 630.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 203.00 CHANNEL SLOPE = 0.1232
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 10.00
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.654

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	B	0.30	0.30	1.000	63
---	---	------	------	-------	----

NATURAL FAIR COVER "OPEN BRUSH"	B	0.10	0.30	1.000	66
------------------------------------	---	------	------	-------	----

NATURAL FAIR COVER "OPEN BRUSH"	B	1.90	0.30	1.000	66
------------------------------------	---	------	------	-------	----

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 7.77

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.43

AVERAGE FLOW DEPTH(FEET) = 0.59 TRAVEL TIME(MIN.) = 0.46

Tc(MIN.) = 9.46

SUBAREA AREA(ACRES) = 2.30 SUBAREA RUNOFF(CFS) = 4.87
EFFECTIVE AREA(ACRES) = 4.70 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 4.7 PEAK FLOW RATE(CFS) = 9.96

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.65 FLOW VELOCITY(FEET/SEC.) = 7.96

LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31103.00 = 655.00 FEET.

FLOW PROCESS FROM NODE 31103.00 TO NODE 31104.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 630.00 DOWNSTREAM(FEET) = 605.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 321.00 CHANNEL SLOPE = 0.0779
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.467

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL FAIR COVER "OPEN BRUSH"	B	1.10	0.30	1.000	66
------------------------------------	---	------	------	-------	----

NATURAL FAIR COVER "OPEN BRUSH"	B	2.50	0.30	1.000	66
------------------------------------	---	------	------	-------	----

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 13.47

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.79

AVERAGE FLOW DEPTH(FEET) = 0.88 TRAVEL TIME(MIN.) = 0.92

Tc(MIN.) = 10.38

SUBAREA AREA(ACRES) = 3.60 SUBAREA RUNOFF(CFS) = 7.02

EFFECTIVE AREA(ACRES) = 8.30 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 8.3 PEAK FLOW RATE(CFS) = 16.19

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.94 FLOW VELOCITY(FEET/SEC.) = 6.07

LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31104.00 = 976.00 FEET.

FLOW PROCESS FROM NODE 31104.00 TO NODE 31105.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 605.00 DOWNSTREAM(FEET) = 585.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 288.00 CHANNEL SLOPE = 0.0694
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.367

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	B	0.70	0.30	1.000	63
---	---	------	------	-------	----

NATURAL FAIR COVER
 "CHAPARRAL,BROADLEAF" B 0.60 0.30 1.000 63
 NATURAL FAIR COVER
 "OPEN BRUSH" B 3.00 0.30 1.000 66
 NATURAL FAIR COVER
 "OPEN BRUSH" B 2.10 0.30 1.000 66
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 22.15
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.26
 AVERAGE FLOW DEPTH(FEET) = 1.09 TRAVEL TIME(MIN.) = 0.77
 Tc(MIN.) = 11.15
 SUBAREA AREA(ACRES) = 6.40 SUBAREA RUNOFF(CFS) = 11.91
 EFFECTIVE AREA(ACRES) = 14.70 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 14.7 PEAK FLOW RATE(CFS) = 27.35

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 1.17 FLOW VELOCITY(FEET/SEC.) = 6.64
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31105.00 = 1264.00 FEET.

 FLOW PROCESS FROM NODE 31105.00 TO NODE 31106.00 IS CODE = 51

 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

 ELEVATION DATA: UPSTREAM(FEET) = 585.00 DOWNSTREAM(FEET) = 560.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 344.00 CHANNEL SLOPE = 0.0727
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.264

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.60	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	2.80	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.60	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.10	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.60	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	4.10	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 36.89
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.26
 AVERAGE FLOW DEPTH(FEET) = 1.30 TRAVEL TIME(MIN.) = 0.79
 Tc(MIN.) = 11.94
 SUBAREA AREA(ACRES) = 10.80 SUBAREA RUNOFF(CFS) = 19.09
 EFFECTIVE AREA(ACRES) = 25.50 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 25.5 PEAK FLOW RATE(CFS) = 45.07

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 1.40 FLOW VELOCITY(FEET/SEC.) = 7.65
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31106.00 = 1608.00 FEET.

 FLOW PROCESS FROM NODE 31106.00 TO NODE 31107.00 IS CODE = 51

 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

 ELEVATION DATA: UPSTREAM(FEET) = 560.00 DOWNSTREAM(FEET) = 530.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 619.00 CHANNEL SLOPE = 0.0485
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.070

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.80	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	1.90	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.50	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	8.20	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.70	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 57.10
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.97
 AVERAGE FLOW DEPTH(FEET) = 1.65 TRAVEL TIME(MIN.) = 1.48
 Tc(MIN.) = 13.42
 SUBAREA AREA(ACRES) = 15.10 SUBAREA RUNOFF(CFS) = 24.05
 EFFECTIVE AREA(ACRES) = 40.60 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 40.6 PEAK FLOW RATE(CFS) = 64.68

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 1.73 FLOW VELOCITY(FEET/SEC.) = 7.16
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31107.00 = 2227.00 FEET.

 FLOW PROCESS FROM NODE 31107.00 TO NODE 31108.00 IS CODE = 51

 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

 ELEVATION DATA: UPSTREAM(FEET) = 530.00 DOWNSTREAM(FEET) = 515.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 377.00 CHANNEL SLOPE = 0.0398
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.952

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					

"CHAPARRAL,BROADLEAF" B 0.50 0.30 1.000 63
 NATURAL FAIR COVER
 "CHAPARRAL,BROADLEAF" B 6.50 0.30 1.000 63
 NATURAL FAIR COVER
 "CHAPARRAL,BROADLEAF" B 1.30 0.30 1.000 63
 NATURAL FAIR COVER
 "OPEN BRUSH" B 1.10 0.30 1.000 66
 NATURAL FAIR COVER
 "OPEN BRUSH" B 5.50 0.30 1.000 66
 NATURAL FAIR COVER
 "OPEN BRUSH" B 3.40 0.30 1.000 66
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 78.29
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.98
 AVERAGE FLOW DEPTH(FEET) = 1.93 TRAVEL TIME(MIN.) = 0.90
 Tc(MIN.) = 14.32
 SUBAREA AREA(ACRES) = 18.30 SUBAREA RUNOFF(CFS) = 27.21
 EFFECTIVE AREA(ACRES) = 58.90 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 58.9 PEAK FLOW RATE(CFS) = 87.59

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 2.02 FLOW VELOCITY(FEET/SEC.) = 7.18
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31108.00 = 2604.00 FEET.

 FLOW PROCESS FROM NODE 31108.00 TO NODE 31109.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 515.00 DOWNSTREAM(FEET) = 490.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 520.00 CHANNEL SLOPE = 0.0481
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.841
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.70	0.30	1.000	63
NATURAL FAIR COVER					
"GRASS"	B	2.20	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	3.10	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.90	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	7.40	0.30	1.000	63
NATURAL FAIR COVER					
"GRASS"	B	0.30	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 97.71
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.93
 AVERAGE FLOW DEPTH(FEET) = 2.03 TRAVEL TIME(MIN.) = 1.09
 Tc(MIN.) = 15.41

SUBAREA AREA(ACRES) = 14.60 SUBAREA RUNOFF(CFS) = 20.25
 EFFECTIVE AREA(ACRES) = 73.50 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 73.5 PEAK FLOW RATE(CFS) = 101.93

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 2.06 FLOW VELOCITY(FEET/SEC.) = 8.03
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31109.00 = 3124.00 FEET.

 FLOW PROCESS FROM NODE 31109.00 TO NODE 31109.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
 =====

MAINLINE Tc(MIN.) = 15.41
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.841
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	11.40	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	8.90	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	1.90	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	9.20	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	1.40	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 32.80 SUBAREA RUNOFF(CFS) = 45.49
 EFFECTIVE AREA(ACRES) = 106.30 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 106.3 PEAK FLOW RATE(CFS) = 147.42

 FLOW PROCESS FROM NODE 31109.00 TO NODE 31110.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 490.00 DOWNSTREAM(FEET) = 432.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1420.00 CHANNEL SLOPE = 0.0408
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.688
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	0.80	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.60	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.10	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	1.30	0.30	1.000	79

NATURAL FAIR COVER
 "WOODLAND,GRASS" B 4.00 0.30 1.000 65
 NATURAL FAIR COVER
 "CHAPARRAL,BROADLEAF" B 1.50 0.30 1.000 63
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 152.60
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.34
 AVERAGE FLOW DEPTH(FEET) = 2.47 TRAVEL TIME(MIN.) = 2.84
 Tc(MIN.) = 18.25
 SUBAREA AREA(ACRES) = 8.30 SUBAREA RUNOFF(CFS) = 10.37
 EFFECTIVE AREA(ACRES) = 114.60 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 114.6 PEAK FLOW RATE(CFS) = 147.42
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 2.44 FLOW VELOCITY(FEET/SEC.) = 8.28
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31110.00 = 4544.00 FEET.

 FLOW PROCESS FROM NODE 31110.00 TO NODE 31110.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

 MAINLINE Tc(MIN.) = 18.25
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.688
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 NATURAL FAIR COVER
 "GRASS" B 0.30 0.30 1.000 69
 NATURAL FAIR COVER
 "OPEN BRUSH" B 9.60 0.30 1.000 66
 RESIDENTIAL
 ".4 DWELLING/ACRE" B 0.40 0.30 0.900 56
 AGRICULTURAL POOR COVER
 "ROW CROPS,CONTOURED" B 6.20 0.30 1.000 79
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 3.90 0.30 1.000 65
 AGRICULTURAL POOR COVER
 "ROW CROPS,CONTOURED" B 1.40 0.30 1.000 79
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.998
 SUBAREA AREA(ACRES) = 21.80 SUBAREA RUNOFF(CFS) = 27.24
 EFFECTIVE AREA(ACRES) = 136.40 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 136.4 PEAK FLOW RATE(CFS) = 170.37

 FLOW PROCESS FROM NODE 31110.00 TO NODE 13301.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

 ELEVATION DATA: UPSTREAM(FEET) = 432.00 DOWNSTREAM(FEET) = 382.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1847.00 CHANNEL SLOPE = 0.0271
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.497
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 NATURAL POOR COVER
 "BARREN" B 4.90 0.30 1.000 86
 AGRICULTURAL POOR COVER
 "ROW CROPS,CONTOURED" B 1.50 0.30 1.000 79
 RESIDENTIAL
 ".4 DWELLING/ACRE" B 0.60 0.30 0.900 56
 AGRICULTURAL POOR COVER
 "ROW CROPS,CONTOURED" B 2.50 0.30 1.000 79
 AGRICULTURAL POOR COVER
 "ROW CROPS,CONTOURED" B 5.30 0.30 1.000 79
 AGRICULTURAL POOR COVER
 "ROW CROPS,CONTOURED" B 3.30 0.30 1.000 79
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.997
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 180.13
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.44
 AVERAGE FLOW DEPTH(FEET) = 2.84 TRAVEL TIME(MIN.) = 4.14
 Tc(MIN.) = 22.38
 SUBAREA AREA(ACRES) = 18.10 SUBAREA RUNOFF(CFS) = 19.51
 EFFECTIVE AREA(ACRES) = 154.50 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 154.5 PEAK FLOW RATE(CFS) = 170.37
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 2.78 FLOW VELOCITY(FEET/SEC.) = 7.35
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 13301.00 = 6391.00 FEET.

 FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

 ** MAIN STREAM CONFLUENCE DATA **
 STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
 NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
 1 170.37 22.38 1.497 0.30(0.30) 1.00 154.5 31100.00
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 13301.00 = 6391.00 FEET.

 ** MEMORY BANK # 1 CONFLUENCE DATA **
 STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
 NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
 1 2621.84 40.24 1.065 0.30(0.24) 0.81 3547.4 13210.00
 2 2624.58 40.37 1.064 0.30(0.24) 0.81 3557.5 13200.00
 3 2643.67 42.91 1.034 0.30(0.24) 0.81 3719.3 13100.00
 4 2521.55 72.14 0.802 0.30(0.24) 0.81 5012.3 13000.00
 5 2478.80 74.49 0.791 0.30(0.24) 0.81 5031.0 13010.00
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

 ** PEAK FLOW RATE TABLE **
 STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
 NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE

1	2395.04	22.38	1.497	0.30	(0.25)	0.83	2127.6	31100.00
2	2730.78	40.24	1.065	0.30	(0.25)	0.82	3701.9	13210.00
3	2733.32	40.37	1.064	0.30	(0.25)	0.82	3712.0	13200.00
4	2748.13	42.91	1.034	0.30	(0.25)	0.82	3873.8	13100.00
5	2593.06	72.14	0.802	0.30	(0.24)	0.82	5166.8	13000.00
6	2548.66	74.49	0.791	0.30	(0.24)	0.82	5185.5	13010.00

TOTAL AREA (ACRES) = 5185.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 2748.13 Tc(MIN.) = 42.911
EFFECTIVE AREA(ACRES) = 3873.80 AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82
TOTAL AREA(ACRES) = 5185.5
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<<

FLOW PROCESS FROM NODE 13301.00 TO NODE 13302.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 382.00 DOWNSTREAM(FEET) = 375.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1141.09 CHANNEL SLOPE = 0.0061
GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 5.43
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.004
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	1.20	0.30	1.000	86
AGRICULTURAL POOR COVER					
"ROW CROPS, STRAIGHT ROW"	B	0.60	0.30	1.000	81
NATURAL POOR COVER					
"BARREN"	B	0.90	0.30	1.000	86
NATURAL FAIR COVER					
"OPEN BRUSH"	B	4.80	0.30	1.000	66
AGRICULTURAL POOR COVER					
"ROW CROPS, STRAIGHT ROW"	B	1.90	0.30	1.000	81

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2751.11
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.65
AVERAGE FLOW DEPTH(FEET) = 5.43 TRAVEL TIME(MIN.) = 2.49
Tc(MIN.) = 45.40
SUBAREA AREA(ACRES) = 9.40 SUBAREA RUNOFF(CFS) = 5.96
EFFECTIVE AREA(ACRES) = 3883.20 AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82
TOTAL AREA(ACRES) = 5194.9 PEAK FLOW RATE(CFS) = 2748.13
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 5.42

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 5.42 FLOW VELOCITY(FEET/SEC.) = 7.65
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13302.00 = 35800.91 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2395.04	24.98	1.392	0.30(0.25)	0.83	2137.0	31100.00
2	2730.78	42.73	1.036	0.30(0.25)	0.82	3711.3	13210.00
3	2733.32	42.86	1.034	0.30(0.25)	0.82	3721.4	13200.00
4	2748.13	45.40	1.004	0.30(0.25)	0.82	3883.2	13100.00
5	2593.06	74.67	0.790	0.30(0.24)	0.82	5176.2	13000.00
6	2548.66	77.03	0.778	0.30(0.24)	0.82	5194.9	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2748.13 Tc(MIN.) = 45.40
AREA-AVERAGED Fm(INCH/HR) = 0.25 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.82 EFFECTIVE AREA(ACRES) = 3883.20

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 45.40
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.004
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	13.80	0.30	1.000	86
NATURAL POOR COVER					
"BARREN"	B	2.60	0.30	1.000	86
COMMERCIAL	B	1.10	0.30	0.100	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	3.50	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	6.90	0.30	1.000	79
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.952
SUBAREA AREA(ACRES) = 28.10 SUBAREA RUNOFF(CFS) = 18.17
EFFECTIVE AREA(ACRES) = 3911.30 AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82
TOTAL AREA(ACRES) = 5223.0 PEAK FLOW RATE(CFS) = 2748.13
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 45.40
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.004
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	0.10	0.30	1.000	79
COMMERCIAL	B	0.10	0.30	0.100	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	2.40	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	0.50	0.30	1.000	79

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.894
SUBAREA AREA(ACRES) = 3.10 SUBAREA RUNOFF(CFS) = 2.05
EFFECTIVE AREA(ACRES) = 3914.40 AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82
TOTAL AREA(ACRES) = 5226.1 PEAK FLOW RATE(CFS) = 2748.13
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 45.40
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.004
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	0.10	0.30	1.000	86
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.60	0.30	1.000	66
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	3.10	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.40	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.20	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	13.80	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 20.20 SUBAREA RUNOFF(CFS) = 12.80
EFFECTIVE AREA(ACRES) = 3934.60 AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82
TOTAL AREA(ACRES) = 5246.3 PEAK FLOW RATE(CFS) = 2748.13
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 45.40
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.004
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					

"ROW CROPS,CONTOURED"	B	34.60	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	2.40	0.30	1.000	65
NATURAL FAIR COVER					
"OPEN BRUSH"	B	22.60	0.30	1.000	66
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	11.60	0.30	1.000	79
APARTMENTS	B	0.40	0.30	0.200	56
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	4.80	0.30	1.000	63

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.996
SUBAREA AREA(ACRES) = 76.40 SUBAREA RUNOFF(CFS) = 48.51
EFFECTIVE AREA(ACRES) = 4011.00 AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
TOTAL AREA(ACRES) = 5322.7 PEAK FLOW RATE(CFS) = 2748.13
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 45.40
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.004
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	1.60	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	46.40	0.30	1.000	66
RESIDENTIAL					
"11+ DWELLINGS/ACRE"	B	0.10	0.30	0.200	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	60.70	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	5.80	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999
SUBAREA AREA(ACRES) = 114.60 SUBAREA RUNOFF(CFS) = 72.66
EFFECTIVE AREA(ACRES) = 4125.60 AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
TOTAL AREA(ACRES) = 5437.3 PEAK FLOW RATE(CFS) = 2803.58

FLOW PROCESS FROM NODE 13302.00 TO NODE 13303.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 375.00 DOWNSTREAM(FEET) = 355.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 2193.96 CHANNEL SLOPE = 0.0091
GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 4.91
CHANNEL FLOW THRU SUBAREA(CFS) = 2803.58
FLOW VELOCITY(FEET/SEC.) = 8.82 FLOW DEPTH(FEET) = 4.91

TRAVEL TIME(MIN.) = 4.15 Tc(MIN.) = 49.54
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13303.00 = 37994.87 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2438.32	29.31	1.269	0.30(0.25)	0.84	2379.4	31100.00
2	2797.64	46.88	0.987	0.30(0.25)	0.83	3953.7	13210.00
3	2799.68	47.01	0.985	0.30(0.25)	0.83	3963.8	13200.00
4	2803.58	49.54	0.955	0.30(0.25)	0.83	4125.6	13100.00
5	2644.86	78.89	0.769	0.30(0.25)	0.82	5418.6	13000.00
6	2597.35	81.28	0.757	0.30(0.25)	0.82	5437.3	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2803.58 Tc(MIN.) = 49.54
AREA-AVERAGED Fm(INCH/HR) = 0.25 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.83 EFFECTIVE AREA(ACRES) = 4125.60

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 49.54

* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.955

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER "BARREN"	B	0.20	0.30	1.000	86
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.40	0.30	1.000	65
NATURAL POOR COVER "BARREN"	B	0.80	0.30	1.000	86
COMMERCIAL	B	1.40	0.30	0.100	56
NATURAL FAIR COVER "GRASS"	B	2.60	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	2.20	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.834

SUBAREA AREA(ACRES) = 7.60 SUBAREA RUNOFF(CFS) = 4.82

EFFECTIVE AREA(ACRES) = 4133.20 AREA-AVERAGED Fm(INCH/HR) = 0.25

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83

TOTAL AREA(ACRES) = 5444.9 PEAK FLOW RATE(CFS) = 2803.58

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 49.54

* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.955

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	3.10	0.30	1.000	79

NATURAL FAIR COVER "WOODLAND,GRASS"	B	3.40	0.30	1.000	65
NATURAL POOR COVER "BARREN"	B	0.50	0.30	1.000	86
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	B	0.20	0.30	1.000	63
COMMERCIAL	B	3.60	0.30	0.100	56
NATURAL FAIR COVER "GRASS"	B	4.00	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.781
SUBAREA AREA(ACRES) = 14.80 SUBAREA RUNOFF(CFS) = 9.60
EFFECTIVE AREA(ACRES) = 4148.00 AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
TOTAL AREA(ACRES) = 5459.7 PEAK FLOW RATE(CFS) = 2803.58
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 49.54

* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.955

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	14.60	0.30	1.000	66
AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	6.30	0.30	1.000	79
NATURAL FAIR COVER "WOODLAND,GRASS"	B	3.70	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 24.60 SUBAREA RUNOFF(CFS) = 14.51
EFFECTIVE AREA(ACRES) = 4172.60 AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
TOTAL AREA(ACRES) = 5484.3 PEAK FLOW RATE(CFS) = 2803.58
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 49.54

* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.955

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER "BARREN"	B	0.50	0.30	1.000	86
COMMERCIAL	B	0.30	0.30	0.100	56
NATURAL FAIR COVER "OPEN BRUSH"	B	0.20	0.30	1.000	66
RESIDENTIAL ".4 DWELLING/ACRE"	B	0.80	0.30	0.900	56

AGRICULTURAL POOR COVER
 "ROW CROPS,CONTOURED" B 1.60 0.30 1.000 79
 NATURAL POOR COVER
 "BARREN" B 31.90 0.30 1.000 86
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.990
 SUBAREA AREA(ACRES) = 35.30 SUBAREA RUNOFF(CFS) = 20.92
 EFFECTIVE AREA(ACRES) = 4207.90 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
 TOTAL AREA(ACRES) = 5519.6 PEAK FLOW RATE(CFS) = 2803.58
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 49.54
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.955
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	1.70	0.30	0.100	56
NATURAL FAIR COVER "OPEN BRUSH"	B	0.30	0.30	1.000	66
RESIDENTIAL ".4 DWELLING/ACRE"	B	2.60	0.30	0.900	56
AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	5.50	0.30	1.000	79
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.20	0.30	1.000	65
NATURAL FAIR COVER "OPEN BRUSH"	B	0.20	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.830
 SUBAREA AREA(ACRES) = 10.50 SUBAREA RUNOFF(CFS) = 6.68
 EFFECTIVE AREA(ACRES) = 4218.40 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
 TOTAL AREA(ACRES) = 5530.1 PEAK FLOW RATE(CFS) = 2803.58
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 49.54
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.955
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL ".4 DWELLING/ACRE"	B	1.30	0.30	0.900	56
NATURAL POOR COVER "BARREN"	B	0.30	0.30	1.000	86
COMMERCIAL	B	0.20	0.30	0.100	56
NATURAL FAIR COVER "OPEN BRUSH"	B	0.30	0.30	1.000	66

RESIDENTIAL
 ".4 DWELLING/ACRE" B 6.50 0.30 0.900 56
 AGRICULTURAL POOR COVER
 "ROW CROPS,CONTOURED" B 3.00 0.30 1.000 79
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.917
 SUBAREA AREA(ACRES) = 11.60 SUBAREA RUNOFF(CFS) = 7.10
 EFFECTIVE AREA(ACRES) = 4230.00 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
 TOTAL AREA(ACRES) = 5541.7 PEAK FLOW RATE(CFS) = 2803.58
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13303.00 TO NODE 13304.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 355.00 DOWNSTREAM(FEET) = 350.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 925.40 CHANNEL SLOPE = 0.0054
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 5.68
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.936
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER "BARREN"	B	0.20	0.30	1.000	86
AGRICULTURAL POOR COVER "ROW CROPS,STRAIGHT ROW"	B	0.50	0.30	1.000	81
NATURAL FAIR COVER "WOODLAND,GRASS"	B	1.10	0.30	1.000	65
NATURAL POOR COVER "BARREN"	B	0.30	0.30	1.000	86
NATURAL FAIR COVER "GRASS"	B	1.10	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	3.50	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2805.49
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.37
 AVERAGE FLOW DEPTH(FEET) = 5.68 TRAVEL TIME(MIN.) = 2.09
 Tc(MIN.) = 51.64
 SUBAREA AREA(ACRES) = 6.70 SUBAREA RUNOFF(CFS) = 3.83
 EFFECTIVE AREA(ACRES) = 4236.70 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
 TOTAL AREA(ACRES) = 5548.4 PEAK FLOW RATE(CFS) = 2803.58
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 5.68

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 5.68 FLOW VELOCITY(FEET/SEC.) = 7.36
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13304.00 = 38920.27 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2438.32	31.50	1.223	0.30 (0.25)	0.85	2490.5	31100.00
2	2797.64	48.98	0.962	0.30 (0.25)	0.83	4064.8	13210.00
3	2799.68	49.10	0.961	0.30 (0.25)	0.83	4074.9	13200.00
4	2803.58	51.64	0.936	0.30 (0.25)	0.83	4236.7	13100.00
5	2644.86	81.02	0.758	0.30 (0.25)	0.83	5529.7	13000.00
6	2597.35	83.42	0.746	0.30 (0.25)	0.83	5548.4	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2803.58 Tc(MIN.) = 51.64
 AREA-AVERAGED Fm(INCH/HR) = 0.25 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.83 EFFECTIVE AREA(ACRES) = 4236.70

 FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 51.64
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.936
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS,STRAIGHT ROW"	B	1.40	0.30	1.000	81
NATURAL FAIR COVER					
"OPEN BRUSH"	B	4.80	0.30	1.000	66
AGRICULTURAL POOR COVER					
"ROW CROPS,STRAIGHT ROW"	B	0.90	0.30	1.000	81
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000					
SUBAREA AREA(ACRES) = 7.10					
SUBAREA RUNOFF(CFS) = 4.06					
EFFECTIVE AREA(ACRES) = 4243.80					
AREA-AVERAGED Fm(INCH/HR) = 0.25					
AREA-AVERAGED Fp(INCH/HR) = 0.30					
AREA-AVERAGED Ap = 0.83					
TOTAL AREA(ACRES) = 5555.5					
PEAK FLOW RATE(CFS) = 2803.58					

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 51.64
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.936
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	7.80	0.30	1.000	86
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	1.70	0.30	1.000	79
NATURAL POOR COVER					
"BARREN"	B	9.40	0.30	1.000	86
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.20	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.10	0.30	0.900	56

AGRICULTURAL POOR COVER

"ROW CROPS,CONTOURED" B 2.60 0.30 1.000 79
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 22.80 SUBAREA RUNOFF(CFS) = 13.05
 EFFECTIVE AREA(ACRES) = 4266.60 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
 TOTAL AREA(ACRES) = 5578.3 PEAK FLOW RATE(CFS) = 2803.58
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 51.64
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.936
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.20	0.30	1.000	65
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.30	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.20	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	2.70	0.30	1.000	79
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.994					
SUBAREA AREA(ACRES) = 3.40					
SUBAREA RUNOFF(CFS) = 1.95					
EFFECTIVE AREA(ACRES) = 4270.00					
AREA-AVERAGED Fm(INCH/HR) = 0.25					
AREA-AVERAGED Fp(INCH/HR) = 0.30					
AREA-AVERAGED Ap = 0.83					
TOTAL AREA(ACRES) = 5581.7					
PEAK FLOW RATE(CFS) = 2803.58					

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13304.00 TO NODE 13305.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 350.00 DOWNSTREAM(FEET) = 315.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2966.27 CHANNEL SLOPE = 0.0118
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 4.57
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.890
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	1.70	0.30	1.000	86
NATURAL FAIR COVER					
"GRASS"	B	0.60	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.10	0.30	1.000	66
NATURAL FAIR COVER					

"WOODLAND,GRASS" A 0.40 0.40 1.000 44
 NATURAL POOR COVER
 "BARREN" B 2.20 0.30 1.000 86
 NATURAL FAIR COVER
 "GRASS" B 4.20 0.30 1.000 69
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2806.00
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.63
 AVERAGE FLOW DEPTH(FEET) = 4.57 TRAVEL TIME(MIN.) = 5.13
 Tc(MIN.) = 56.77
 SUBAREA AREA(ACRES) = 9.20 SUBAREA RUNOFF(CFS) = 4.85
 EFFECTIVE AREA(ACRES) = 4279.20 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
 TOTAL AREA(ACRES) = 5590.9 PEAK FLOW RATE(CFS) = 2803.58
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 4.57

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 4.57 FLOW VELOCITY(FEET/SEC.) = 9.64
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2438.32	36.86	1.125	0.30(0.26)	0.85	2533.0	31100.00
2	2797.64	54.11	0.914	0.30(0.25)	0.84	4107.3	13210.00
3	2799.68	54.23	0.913	0.30(0.25)	0.84	4117.4	13200.00
4	2803.58	56.77	0.890	0.30(0.25)	0.84	4279.2	13100.00
5	2644.86	86.25	0.733	0.30(0.25)	0.83	5572.2	13000.00
6	2597.35	88.68	0.721	0.30(0.25)	0.83	5590.9	13010.00

NEW PEAK FLOW DATA ARE:
 PEAK FLOW RATE(CFS) = 2803.58 Tc(MIN.) = 56.77
 AREA-AVERAGED Fm(INCH/HR) = 0.25 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.84 EFFECTIVE AREA(ACRES) = 4279.20

 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 56.77
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.890
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 NATURAL FAIR COVER
 "OPEN BRUSH" B 8.10 0.30 1.000 66
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 2.30 0.30 1.000 65
 NATURAL FAIR COVER
 "GRASS" B 0.20 0.30 1.000 69
 NATURAL FAIR COVER
 "OPEN BRUSH" B 6.90 0.30 1.000 66
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 0.70 0.30 1.000 65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 18.20 SUBAREA RUNOFF(CFS) = 9.67
 EFFECTIVE AREA(ACRES) = 4297.40 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
 TOTAL AREA(ACRES) = 5609.1 PEAK FLOW RATE(CFS) = 2803.58
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 56.77
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.890
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 NATURAL POOR COVER
 "BARREN" B 18.40 0.30 1.000 86
 NATURAL FAIR COVER
 "MEADOWS" B 1.20 0.30 1.000 70
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 0.10 0.30 1.000 65
 NATURAL POOR COVER
 "BARREN" B 26.60 0.30 1.000 86
 COMMERCIAL B 3.90 0.30 0.100 56
 AGRICULTURAL POOR COVER
 "FALLOW" B 3.00 0.30 1.000 86
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.934
 SUBAREA AREA(ACRES) = 53.20 SUBAREA RUNOFF(CFS) = 29.22
 EFFECTIVE AREA(ACRES) = 4350.60 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
 TOTAL AREA(ACRES) = 5662.3 PEAK FLOW RATE(CFS) = 2803.58
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 56.77
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.890
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 AGRICULTURAL POOR COVER
 "ROW CROPS,CONTOURED" B 1.10 0.30 1.000 79
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 0.20 0.30 1.000 65
 NATURAL POOR COVER
 "BARREN" B 14.00 0.30 1.000 86
 COMMERCIAL B 4.30 0.30 0.100 56
 AGRICULTURAL POOR COVER
 "FALLOW" B 5.30 0.30 1.000 86
 NATURAL FAIR COVER
 "GRASS" B 2.70 0.30 1.000 69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.860
 SUBAREA AREA(ACRES) = 27.60 SUBAREA RUNOFF(CFS) = 15.71
 EFFECTIVE AREA(ACRES) = 4378.20 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
 TOTAL AREA(ACRES) = 5689.9 PEAK FLOW RATE(CFS) = 2803.58
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 56.77
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.890
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "MEADOWS"	B	3.20	0.30	1.000	70
NATURAL FAIR COVER "OPEN BRUSH"	B	6.10	0.30	1.000	66
RESIDENTIAL ".4 DWELLING/ACRE"	B	7.50	0.30	0.900	56
AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	5.40	0.30	1.000	79
NATURAL FAIR COVER "WOODLAND,GRASS"	B	1.60	0.30	1.000	65
NATURAL POOR COVER "BARREN"	B	1.90	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.971
 SUBAREA AREA(ACRES) = 25.70 SUBAREA RUNOFF(CFS) = 13.86
 EFFECTIVE AREA(ACRES) = 4403.90 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
 TOTAL AREA(ACRES) = 5715.6 PEAK FLOW RATE(CFS) = 2803.58
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 56.77
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.890
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	2.00	0.30	0.100	56
AGRICULTURAL POOR COVER "FALLOW"	B	3.70	0.30	1.000	86
NATURAL FAIR COVER "OPEN BRUSH"	B	2.10	0.30	1.000	66
RESIDENTIAL ".4 DWELLING/ACRE"	B	2.60	0.30	0.900	56
AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	0.20	0.30	1.000	79
NATURAL FAIR COVER					

"WOODLAND,GRASS" B 0.10 0.30 1.000 65
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.807
 SUBAREA AREA(ACRES) = 10.70 SUBAREA RUNOFF(CFS) = 6.24
 EFFECTIVE AREA(ACRES) = 4414.60 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
 TOTAL AREA(ACRES) = 5726.3 PEAK FLOW RATE(CFS) = 2803.58
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 56.77
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.890
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	0.50	0.30	1.000	66
RESIDENTIAL ".4 DWELLING/ACRE"	B	8.20	0.30	0.900	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.906
 SUBAREA AREA(ACRES) = 8.70 SUBAREA RUNOFF(CFS) = 4.84
 EFFECTIVE AREA(ACRES) = 4423.30 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
 TOTAL AREA(ACRES) = 5735.0 PEAK FLOW RATE(CFS) = 2803.58
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<

PEAK FLOWRATE TABLE FILE NAME: 3A10EVRL.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	742.58	14.11	0.30(0.13)	0.43	433.8	120.00
2	739.67	14.27	0.30(0.13)	0.43	436.5	110.00
3	635.72	21.58	0.30(0.13)	0.43	503.8	100.00
4	587.61	24.64	0.30(0.13)	0.43	510.2	150.00
TOTAL AREA(ACRES) =		510.2				

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2438.32	36.86	1.125	0.30(0.26)	0.85	2677.1	31100.00
2	2797.64	54.11	0.914	0.30(0.25)	0.84	4251.4	13210.00
3	2799.68	54.23	0.913	0.30(0.25)	0.84	4261.5	13200.00

4 2803.58 56.77 0.890 0.30(0.25) 0.84 4423.3 13100.00
 5 2644.86 86.25 0.733 0.30(0.25) 0.83 5716.3 13000.00
 6 2597.35 88.68 0.721 0.30(0.25) 0.83 5735.0 13010.00
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	742.58	14.11	1.980	0.30(0.13)	0.43	433.8	120.00
2	739.67	14.27	1.959	0.30(0.13)	0.43	436.5	110.00
3	635.72	21.58	1.529	0.30(0.13)	0.43	503.8	100.00
4	587.61	24.64	1.406	0.30(0.13)	0.43	510.2	150.00

LONGEST FLOWPATH FROM NODE 150.00 TO NODE 13305.00 = 9867.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2593.77	14.11	1.980	0.30(0.22)	0.73	1458.5	120.00
2	2589.12	14.27	1.959	0.30(0.22)	0.73	1472.8	110.00
3	2727.10	21.58	1.529	0.30(0.23)	0.75	2071.2	100.00
4	2743.60	24.64	1.406	0.30(0.23)	0.76	2299.7	150.00
5	2896.72	36.86	1.125	0.30(0.24)	0.79	3187.3	31100.00
6	3158.69	54.11	0.914	0.30(0.24)	0.80	4761.6	13210.00
7	3160.24	54.23	0.913	0.30(0.24)	0.80	4771.7	13200.00
8	3153.84	56.77	0.890	0.30(0.24)	0.80	4933.5	13100.00
9	2922.38	86.25	0.733	0.30(0.24)	0.80	6226.5	13000.00
10	2869.36	88.68	0.721	0.30(0.24)	0.80	6245.2	13010.00

TOTAL AREA (ACRES) = 6245.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 3160.24 Tc (MIN.) = 54.232
 EFFECTIVE AREA (ACRES) = 4771.66 AREA-AVERAGED Fm (INCH/HR) = 0.24
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.75
 TOTAL AREA (ACRES) = 6245.2
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

 FLOW PROCESS FROM NODE 13305.00 TO NODE 13306.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 315.00 DOWNSTREAM (FEET) = 245.50
 CHANNEL LENGTH THRU SUBAREA (FEET) = 4408.41 CHANNEL SLOPE = 0.0158
 GIVEN CHANNEL BASE (FEET) = 50.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT (FEET) = 4.51

* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.858

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					

"BARREN"	B	0.40	0.30	1.000	86
NATURAL FAIR COVER					
"GRASS"	B	9.20	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.00	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	1.30	0.30	1.000	65
NATURAL POOR COVER					
"BARREN"	B	2.40	0.30	1.000	86
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	4.10	0.30	1.000	63

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 3164.86
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 11.06
 AVERAGE FLOW DEPTH (FEET) = 4.51 TRAVEL TIME (MIN.) = 6.64
 Tc (MIN.) = 60.88
 SUBAREA AREA (ACRES) = 18.40 SUBAREA RUNOFF (CFS) = 9.24
 EFFECTIVE AREA (ACRES) = 4790.06 AREA-AVERAGED Fm (INCH/HR) = 0.24
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA (ACRES) = 6263.6 PEAK FLOW RATE (CFS) = 3160.24
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE (FEET) = 50.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT (FEET) = 4.50

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 4.50 FLOW VELOCITY (FEET/SEC.) = 11.05
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13306.00 = 46294.95 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2593.77	21.19	1.545	0.30(0.22)	0.73	1476.9	120.00
2	2589.12	21.35	1.539	0.30(0.22)	0.73	1491.2	110.00
3	2727.10	28.55	1.291	0.30(0.23)	0.75	2089.6	100.00
4	2743.60	31.58	1.221	0.30(0.23)	0.76	2318.1	150.00
5	2896.72	43.69	1.024	0.30(0.24)	0.79	3205.7	31100.00
6	3158.69	60.76	0.858	0.30(0.24)	0.80	4780.0	13210.00
7	3160.24	60.88	0.858	0.30(0.24)	0.80	4790.1	13200.00
8	3153.84	63.43	0.845	0.30(0.24)	0.80	4951.9	13100.00
9	2922.38	93.07	0.705	0.30(0.24)	0.80	6244.9	13000.00
10	2869.36	95.53	0.699	0.30(0.24)	0.80	6263.6	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 3160.24 Tc (MIN.) = 60.88
 AREA-AVERAGED Fm (INCH/HR) = 0.24 AREA-AVERAGED Fp (INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.80 EFFECTIVE AREA (ACRES) = 4790.06

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 60.88

* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.858

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN

NATURAL FAIR COVER
 "GRASS" B 19.20 0.30 1.000 69
 NATURAL FAIR COVER
 "OPEN BRUSH" B 20.90 0.30 1.000 66
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 4.10 0.30 1.000 65
 NATURAL FAIR COVER
 "CHAPARRAL,BROADLEAF" B 0.50 0.30 1.000 63
 NATURAL FAIR COVER
 "GRASS" B 4.30 0.30 1.000 69
 NATURAL FAIR COVER
 "OPEN BRUSH" B 0.60 0.30 1.000 66
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 49.60 SUBAREA RUNOFF(CFS) = 24.89
 EFFECTIVE AREA(ACRES) = 4839.66 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6313.2 PEAK FLOW RATE(CFS) = 3160.24
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 60.88
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.858
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 0.80 0.30 1.000 65
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 0.80 SUBAREA RUNOFF(CFS) = 0.40
 EFFECTIVE AREA(ACRES) = 4840.46 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6314.0 PEAK FLOW RATE(CFS) = 3160.24
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 60.88
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.858
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 PUBLIC PARK B 0.10 0.30 0.850 56
 NATURAL FAIR COVER
 "OPEN BRUSH" B 0.10 0.30 1.000 66
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 0.10 0.30 1.000 65
 NATURAL POOR COVER
 "BARREN" B 0.20 0.30 1.000 86
 PUBLIC PARK B 0.40 0.30 0.850 56

NATURAL FAIR COVER
 "GRASS" B 0.40 0.30 1.000 69
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.942
 SUBAREA AREA(ACRES) = 1.30 SUBAREA RUNOFF(CFS) = 0.67
 EFFECTIVE AREA(ACRES) = 4841.76 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6315.3 PEAK FLOW RATE(CFS) = 3160.24
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 60.88
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.858
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 RESIDENTIAL
 ".4 DWELLING/ACRE" B 0.80 0.30 0.900 56
 NATURAL FAIR COVER
 "GRASS" B 0.80 0.30 1.000 69
 NATURAL FAIR COVER
 "OPEN BRUSH" B 1.00 0.30 1.000 66
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 1.10 0.30 1.000 65
 COMMERCIAL B 1.10 0.30 0.100 56
 RESIDENTIAL
 ".4 DWELLING/ACRE" B 2.80 0.30 0.900 56
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.822
 SUBAREA AREA(ACRES) = 7.60 SUBAREA RUNOFF(CFS) = 4.18
 EFFECTIVE AREA(ACRES) = 4849.36 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6322.9 PEAK FLOW RATE(CFS) = 3160.24
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 60.88
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.858
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 COMMERCIAL B 3.50 0.30 0.100 56
 NATURAL FAIR COVER
 "GRASS" B 5.00 0.30 1.000 69
 RESIDENTIAL
 ".4 DWELLING/ACRE" B 6.70 0.30 0.900 56
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 7.80 0.30 1.000 65
 NATURAL FAIR COVER
 "OPEN BRUSH" B 10.80 0.30 1.000 66

COMMERCIAL B 13.80 0.30 0.100 56
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.659
 SUBAREA AREA(ACRES) = 47.60 SUBAREA RUNOFF(CFS) = 28.28
 EFFECTIVE AREA(ACRES) = 4896.96 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6370.5 PEAK FLOW RATE(CFS) = 3160.24
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 60.88
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.858
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER "BARREN"	B	21.54	0.30	1.000	86
NATURAL POOR COVER "BARREN"	B	36.64	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 58.18 SUBAREA RUNOFF(CFS) = 29.20
 EFFECTIVE AREA(ACRES) = 4955.14 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6428.7 PEAK FLOW RATE(CFS) = 3160.24
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13307.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 245.50 DOWNSTREAM(FEET) = 220.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1543.21 CHANNEL SLOPE = 0.0165
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 4.45
 CHANNEL FLOW THRU SUBAREA(CFS) = 3160.24
 FLOW VELOCITY(FEET/SEC.) = 11.23 FLOW DEPTH(FEET) = 4.45
 TRAVEL TIME(MIN.) = 2.29 Tc(MIN.) = 63.17
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13307.00 = 47838.16 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2593.77	23.63	1.446	0.30(0.22)	0.75	1642.0	120.00
2	2589.12	23.79	1.440	0.30(0.22)	0.75	1656.2	110.00
3	2727.10	30.95	1.233	0.30(0.23)	0.76	2254.7	100.00
4	2743.60	33.98	1.178	0.30(0.23)	0.77	2483.1	150.00
5	2896.72	46.05	0.997	0.30(0.24)	0.79	3370.8	31100.00
6	3158.69	63.05	0.847	0.30(0.24)	0.80	4945.1	13210.00
7	3160.24	63.17	0.846	0.30(0.24)	0.80	4955.1	13200.00
8	3153.84	65.72	0.834	0.30(0.24)	0.80	5117.0	13100.00

9 2922.38 95.42 0.699 0.30(0.24) 0.80 6410.0 13000.00
 10 2869.36 97.89 0.692 0.30(0.24) 0.80 6428.7 13010.00
 NEW PEAK FLOW DATA ARE:
 PEAK FLOW RATE(CFS) = 3160.24 Tc(MIN.) = 63.17
 AREA-AVERAGED Fm(INCH/HR) = 0.24 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.80 EFFECTIVE AREA(ACRES) = 4955.14

 FLOW PROCESS FROM NODE 13307.00 TO NODE 13307.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 63.17
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.846
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	0.20	0.30	0.100	56
NATURAL FAIR COVER "GRASS"	B	0.10	0.30	1.000	69
AGRICULTURAL FAIR COVER "ORCHARDS"	B	0.20	0.30	1.000	65
NATURAL POOR COVER "BARREN"	B	3.70	0.30	1.000	86
COMMERCIAL	B	0.30	0.30	0.100	56
NATURAL FAIR COVER "GRASS"	B	3.20	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.942
 SUBAREA AREA(ACRES) = 7.70 SUBAREA RUNOFF(CFS) = 3.91
 EFFECTIVE AREA(ACRES) = 4962.84 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6436.4 PEAK FLOW RATE(CFS) = 3160.24
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13307.00 TO NODE 13307.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 63.17
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.846
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "WOODLAND,GRASS"	B	3.60	0.30	1.000	65
NATURAL FAIR COVER "GRASS"	B	1.90	0.30	1.000	69
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.60	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 6.10 SUBAREA RUNOFF(CFS) = 3.00
 EFFECTIVE AREA(ACRES) = 4968.94 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6442.5 PEAK FLOW RATE(CFS) = 3160.24
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13307.00 TO NODE 13308.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 220.00 DOWNSTREAM(FEET) = 212.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 925.62 CHANNEL SLOPE = 0.0086
GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 5.33
CHANNEL FLOW THRU SUBAREA(CFS) = 3160.24
FLOW VELOCITY(FEET/SEC.) = 8.99 FLOW DEPTH(FEET) = 5.33
TRAVEL TIME(MIN.) = 1.72 Tc(MIN.) = 64.88
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13308.00 = 48763.78 FEET.

** PEAK FLOW RATE TABLE **

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 10 rows of data.

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 3160.24 Tc(MIN.) = 64.88
AREA-AVERAGED Fm(INCH/HR) = 0.24 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.80 EFFECTIVE AREA(ACRES) = 4968.94

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 64.88
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.838
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"GRASS" B 0.10 0.30 1.000 69
NATURAL FAIR COVER
"OPEN BRUSH" B 0.20 0.30 1.000 66
NATURAL FAIR COVER
"WOODLAND,GRASS" B 5.00 0.30 1.000 65
COMMERCIAL B 3.20 0.30 0.100 56
NATURAL FAIR COVER
"GRASS" B 0.10 0.30 1.000 69
NATURAL FAIR COVER
"OPEN BRUSH" B 0.90 0.30 1.000 66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.697

SUBAREA AREA(ACRES) = 9.50 SUBAREA RUNOFF(CFS) = 5.38
EFFECTIVE AREA(ACRES) = 4978.44 AREA-AVERAGED Fm(INCH/HR) = 0.24
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
TOTAL AREA(ACRES) = 6452.0 PEAK FLOW RATE(CFS) = 3160.24
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 64.88
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.838
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
APARTMENTS B 0.30 0.30 0.200 56
NATURAL POOR COVER
"BARREN" B 0.20 0.30 1.000 86
NATURAL FAIR COVER
"CHAPARRAL,BROADLEAF" B 1.00 0.30 1.000 63
COMMERCIAL B 41.90 0.30 0.100 56
NATURAL FAIR COVER
"GRASS" B 7.20 0.30 1.000 69
NATURAL FAIR COVER
"OPEN BRUSH" B 25.00 0.30 1.000 66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.498
SUBAREA AREA(ACRES) = 75.60 SUBAREA RUNOFF(CFS) = 46.85
EFFECTIVE AREA(ACRES) = 5054.04 AREA-AVERAGED Fm(INCH/HR) = 0.24
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
TOTAL AREA(ACRES) = 6527.6 PEAK FLOW RATE(CFS) = 3160.24
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 64.88
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.838
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
PUBLIC PARK B 0.10 0.30 0.850 56
AGRICULTURAL POOR COVER
"ROW CROPS,CONTOURED" B 0.90 0.30 1.000 79
SCHOOL B 0.30 0.30 0.600 56
NATURAL FAIR COVER
"WOODLAND,GRASS" B 13.20 0.30 1.000 65
APARTMENTS B 0.50 0.30 0.200 56
NATURAL FAIR COVER
"CHAPARRAL,BROADLEAF" B 0.60 0.30 1.000 63
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.966
SUBAREA AREA(ACRES) = 15.60 SUBAREA RUNOFF(CFS) = 7.70
EFFECTIVE AREA(ACRES) = 5069.64 AREA-AVERAGED Fm(INCH/HR) = 0.24
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80

TOTAL AREA (ACRES) = 6543.2 PEAK FLOW RATE (CFS) = 3160.24
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) =	64.88				
* 10 YEAR RAINFALL INTENSITY (INCH/HR) =	0.838				
SUBAREA LOSS RATE DATA (AMC II):					
DEVELOPMENT TYPE/	SCS SOIL	AREA	Fp	Ap	SCS
LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
COMMERCIAL	B	33.90	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	17.60	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	16.80	0.30	1.000	66
RESIDENTIAL					
"11+ DWELLINGS/ACRE"	B	0.60	0.30	0.200	56
RESIDENTIAL					
"8-10 DWELLINGS/ACRE"	B	1.50	0.30	0.400	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	10.00	0.30	1.000	79

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.603
SUBAREA AREA (ACRES) = 80.40 SUBAREA RUNOFF (CFS) = 47.53
EFFECTIVE AREA (ACRES) = 5150.04 AREA-AVERAGED Fm (INCH/HR) = 0.24
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79
TOTAL AREA (ACRES) = 6623.6 PEAK FLOW RATE (CFS) = 3160.24
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) =	64.88				
* 10 YEAR RAINFALL INTENSITY (INCH/HR) =	0.838				
SUBAREA LOSS RATE DATA (AMC II):					
DEVELOPMENT TYPE/	SCS SOIL	AREA	Fp	Ap	SCS
LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
SCHOOL	B	0.30	0.30	0.600	56
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.70	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.880
SUBAREA AREA (ACRES) = 1.00 SUBAREA RUNOFF (CFS) = 0.52
EFFECTIVE AREA (ACRES) = 5151.04 AREA-AVERAGED Fm (INCH/HR) = 0.24
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79
TOTAL AREA (ACRES) = 6624.6 PEAK FLOW RATE (CFS) = 3160.24
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 64.88
* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.838
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/	SCS SOIL	AREA	Fp	Ap	SCS
LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
NATURAL FAIR COVER					
"GRASS"	B	0.30	0.30	1.000	69
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.80	0.30	1.000	65
NATURAL FAIR COVER					
"GRASS"	B	0.50	0.30	1.000	69
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.20	0.30	1.000	65
NATURAL FAIR COVER					
"GRASS"	B	0.30	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 2.10 SUBAREA RUNOFF (CFS) = 1.02
EFFECTIVE AREA (ACRES) = 5153.14 AREA-AVERAGED Fm (INCH/HR) = 0.24
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79
TOTAL AREA (ACRES) = 6626.7 PEAK FLOW RATE (CFS) = 3160.24
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) =	64.88				
* 10 YEAR RAINFALL INTENSITY (INCH/HR) =	0.838				
SUBAREA LOSS RATE DATA (AMC II):					
DEVELOPMENT TYPE/	SCS SOIL	AREA	Fp	Ap	SCS
LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
NATURAL FAIR COVER					
"GRASS"	B	1.20	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.50	0.30	1.000	66
PUBLIC PARK	B	1.70	0.30	0.850	56
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	7.20	0.30	1.000	65
NATURAL FAIR COVER					
"GRASS"	B	1.00	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.978
SUBAREA AREA (ACRES) = 11.60 SUBAREA RUNOFF (CFS) = 5.68
EFFECTIVE AREA (ACRES) = 5164.74 AREA-AVERAGED Fm (INCH/HR) = 0.24
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79
TOTAL AREA (ACRES) = 6638.3 PEAK FLOW RATE (CFS) = 3160.24
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 15.1

=====
>>>>DEFINE MEMORY BANK # 2 <<<<
=====

PEAK FLOWRATE TABLE FILE NAME: RU10EV29.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14719.66	23.88	0.30 (0.23)	0.78	4469.7	50320.00
2	16340.37	33.01	0.30 (0.24)	0.80	6846.5	400.00
3	16846.10	38.85	0.30 (0.25)	0.83	8731.4	50200.00
4	17194.06	42.91	0.30 (0.26)	0.85	10015.7	600.00
5	19039.13	61.35	0.30 (0.27)	0.90	15832.8	40100.00
6	19674.82	70.40	0.30 (0.28)	0.92	18610.5	11801.00
7	20932.41	83.99	0.30 (0.28)	0.93	23605.8	11530.00
8	21798.01	92.20	0.30 (0.28)	0.94	27493.9	11900.00
9	23293.73	101.88	0.30 (0.29)	0.95	33304.5	11330.00
10	24147.34	110.09	0.30 (0.29)	0.96	38391.6	10630.00
11	24048.75	115.66	0.30 (0.29)	0.96	40981.5	12330.00
12	23925.38	122.27	0.30 (0.29)	0.96	44124.0	11600.00
13	23665.21	128.03	0.30 (0.29)	0.96	46358.3	11111.00
14	23367.87	134.15	0.30 (0.29)	0.96	48292.1	12201.00
15	22629.11	143.05	0.30 (0.29)	0.96	50380.4	12231.00
16	21938.20	150.50	0.30 (0.29)	0.97	51791.9	10400.00
17	20825.71	161.85	0.30 (0.29)	0.97	53412.7	10320.00
18	20241.68	166.68	0.30 (0.29)	0.97	53638.2	10210.00
19	19734.89	171.51	0.30 (0.29)	0.97	53800.5	12000.00
20	17089.88	200.54	0.30 (0.29)	0.97	54417.5	10100.00

TOTAL AREA (ACRES) = 54417.5

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 14.0

=====
>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<
=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14719.66	23.88	0.30 (0.23)	0.78	4469.7	50320.00
2	16340.37	33.01	0.30 (0.24)	0.80	6846.5	400.00
3	16846.10	38.85	0.30 (0.25)	0.83	8731.4	50200.00
4	17194.06	42.91	0.30 (0.26)	0.85	10015.7	600.00
5	19039.13	61.35	0.30 (0.27)	0.90	15832.8	40100.00
6	19674.82	70.40	0.30 (0.28)	0.92	18610.5	11801.00
7	20932.41	83.99	0.30 (0.28)	0.93	23605.8	11530.00
8	21798.01	92.20	0.30 (0.28)	0.94	27493.9	11900.00
9	23293.73	101.88	0.30 (0.29)	0.95	33304.5	11330.00
10	24147.34	110.09	0.30 (0.29)	0.96	38391.6	10630.00
11	24048.75	115.66	0.30 (0.29)	0.96	40981.5	12330.00
12	23925.38	122.27	0.30 (0.29)	0.96	44124.0	11600.00
13	23665.21	128.03	0.30 (0.29)	0.96	46358.3	11111.00
14	23367.87	134.15	0.30 (0.29)	0.96	48292.1	12201.00
15	22629.11	143.05	0.30 (0.29)	0.96	50380.4	12231.00
16	21938.20	150.50	0.30 (0.29)	0.97	51791.9	10400.00
17	20825.71	161.85	0.30 (0.29)	0.97	53412.7	10320.00
18	20241.68	166.68	0.30 (0.29)	0.97	53638.2	10210.00
19	19734.89	171.51	0.30 (0.29)	0.97	53800.5	12000.00
20	17089.88	200.54	0.30 (0.29)	0.97	54417.5	10100.00

TOTAL AREA (ACRES) = 54417.5

FLOW PROCESS FROM NODE 12904.00 TO NODE 13308.00 IS CODE = 56

=====
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<
=====

ELEVATION DATA: UPSTREAM (FEET) = 213.00 DOWNSTREAM (FEET) = 212.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1389.52 CHANNEL SLOPE = 0.0007
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT (FEET) = 13.77
 CHANNEL FLOW THRU SUBAREA (CFS) = 24147.34
 FLOW VELOCITY (FEET/SEC.) = 6.52 FLOW DEPTH (FEET) = 13.77
 TRAVEL TIME (MIN.) = 3.55 Tc (MIN.) = 113.64
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118087.91 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14719.66	28.03	1.305	0.30 (0.23)	0.78	4469.7	50320.00
2	16340.37	37.02	1.122	0.30 (0.24)	0.80	6846.5	400.00
3	16846.10	42.83	1.035	0.30 (0.25)	0.83	8731.4	50200.00
4	17194.06	46.86	0.987	0.30 (0.26)	0.85	10015.7	600.00
5	19039.13	65.18	0.836	0.30 (0.27)	0.90	15832.8	40100.00
6	19674.82	74.19	0.792	0.30 (0.28)	0.92	18610.5	11801.00
7	20932.41	87.70	0.725	0.30 (0.28)	0.93	23605.8	11530.00
8	21798.01	95.86	0.698	0.30 (0.28)	0.94	27493.9	11900.00
9	23293.73	105.47	0.671	0.30 (0.29)	0.95	33304.5	11330.00
10	24147.34	113.64	0.648	0.30 (0.29)	0.96	38391.6	10630.00
11	24048.75	119.21	0.632	0.30 (0.29)	0.96	40981.5	12330.00
12	23925.38	125.83	0.620	0.30 (0.29)	0.96	44124.0	11600.00
13	23665.21	131.61	0.610	0.30 (0.29)	0.96	46358.3	11111.00
14	23367.87	137.73	0.600	0.30 (0.29)	0.96	48292.1	12201.00
15	22629.11	146.67	0.585	0.30 (0.29)	0.96	50380.4	12231.00
16	21938.20	154.15	0.572	0.30 (0.29)	0.97	51791.9	10400.00
17	20825.71	165.57	0.553	0.30 (0.29)	0.97	53412.7	10320.00
18	20241.68	170.43	0.544	0.30 (0.29)	0.97	53638.2	10210.00
19	19734.89	175.29	0.536	0.30 (0.29)	0.97	53800.5	12000.00
20	17089.88	204.50	0.509	0.30 (0.29)	0.97	54417.5	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 24147.34 Tc (MIN.) = 113.64
 AREA-AVERAGED Fm (INCH/HR) = 0.29 AREA-AVERAGED Fp (INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.96 EFFECTIVE AREA (ACRES) = 38391.65

FLOW PROCESS FROM NODE 13307.00 TO NODE 13308.00 IS CODE = 11

=====
>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<
=====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14719.66	28.03	1.305	0.30 (0.23)	0.78	4469.7	50320.00
2	16340.37	37.02	1.122	0.30 (0.24)	0.80	6846.5	400.00
3	16846.10	42.83	1.035	0.30 (0.25)	0.83	8731.4	50200.00

=====
END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2010 Advanced Engineering Software (aes)
Ver. 17.0 Release Date: 07/01/2010 License ID 1527

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 134 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 10-YR EV AUG 2023 ROKAMOTO *

FILE NAME: RU10EV34.DAT
TIME/DATE OF STUDY: 23:35 08/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 10.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 3.757
- 2) 10.00; 2.507
- 3) 15.00; 1.859
- 4) 20.00; 1.590
- 5) 25.00; 1.388
- 6) 30.00; 1.248
- 7) 40.00; 1.066
- 8) 50.00; 0.948
- 9) 60.00; 0.860
- 10) 90.00; 0.712
- 11) 120.00; 0.627
- 12) 180.00; 0.525
- 13) 360.00; 0.386
- 14) 1200.00; 0.169

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU10EV33.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	17355.57	28.03	0.30 (0.23)	0.77	6538.5	50320.00
2	19099.88	37.02	0.30 (0.24)	0.79	9631.5	400.00
3	19679.43	42.83	0.30 (0.24)	0.82	11944.2	50200.00
4	20186.15	47.81	0.30 (0.25)	0.84	13896.7	31100.00
5	22352.19	67.43	0.30 (0.26)	0.88	21855.1	13100.00
6	22776.12	74.19	0.30 (0.27)	0.89	24230.7	11801.00
7	23928.51	87.70	0.30 (0.27)	0.90	29813.6	11530.00
8	25258.78	99.66	0.30 (0.28)	0.92	36429.7	13010.00
9	26059.02	105.47	0.30 (0.28)	0.93	39942.8	11330.00
10	26766.16	113.64	0.30 (0.28)	0.93	45030.0	10630.00
11	26567.64	119.21	0.30 (0.28)	0.94	47619.8	12330.00
12	26366.72	125.83	0.30 (0.28)	0.94	50762.3	11600.00
13	26043.70	131.61	0.30 (0.28)	0.94	52996.6	11111.00
14	25679.68	137.73	0.30 (0.28)	0.94	54930.5	12201.00
15	24843.67	146.67	0.30 (0.28)	0.94	57018.7	12231.00
16	24071.31	154.15	0.30 (0.28)	0.95	58430.3	10400.00
17	22834.62	165.57	0.30 (0.28)	0.95	60051.0	10320.00
18	22197.69	170.43	0.30 (0.28)	0.95	60276.5	10210.00
19	21637.94	175.29	0.30 (0.28)	0.95	60438.8	12000.00
20	18819.74	204.50	0.30 (0.28)	0.95	61055.8	10100.00
TOTAL AREA (ACRES) =						61055.8

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	17355.57	28.03	0.30 (0.23)	0.77	6538.5	50320.00
2	19099.88	37.02	0.30 (0.24)	0.79	9631.5	400.00
3	19679.43	42.83	0.30 (0.24)	0.82	11944.2	50200.00
4	20186.15	47.81	0.30 (0.25)	0.84	13896.7	31100.00
5	22352.19	67.43	0.30 (0.26)	0.88	21855.1	13100.00
6	22776.12	74.19	0.30 (0.27)	0.89	24230.7	11801.00
7	23928.51	87.70	0.30 (0.27)	0.90	29813.6	11530.00
8	25258.78	99.66	0.30 (0.28)	0.92	36429.7	13010.00
9	26059.02	105.47	0.30 (0.28)	0.93	39942.8	11330.00
10	26766.16	113.64	0.30 (0.28)	0.93	45030.0	10630.00
11	26567.64	119.21	0.30 (0.28)	0.94	47619.8	12330.00
12	26366.72	125.83	0.30 (0.28)	0.94	50762.3	11600.00
13	26043.70	131.61	0.30 (0.28)	0.94	52996.6	11111.00

14	25679.68	137.73	0.30(0.28)	0.94	54930.5	12201.00
15	24843.67	146.67	0.30(0.28)	0.94	57018.7	12231.00
16	24071.31	154.15	0.30(0.28)	0.95	58430.3	10400.00
17	22834.62	165.57	0.30(0.28)	0.95	60051.0	10320.00
18	22197.69	170.43	0.30(0.28)	0.95	60276.5	10210.00
19	21637.94	175.29	0.30(0.28)	0.95	60438.8	12000.00
20	18819.74	204.50	0.30(0.28)	0.95	61055.8	10100.00

TOTAL AREA (ACRES) = 61055.8

FLOW PROCESS FROM NODE 13308.00 TO NODE 13402.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 212.00 DOWNSTREAM (FEET) = 209.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 623.02 CHANNEL SLOPE = 0.0048
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 8.57
CHANNEL FLOW THRU SUBAREA (CFS) = 26766.16
FLOW VELOCITY (FEET/SEC.) = 12.86 FLOW DEPTH (FEET) = 8.57
TRAVEL TIME (MIN.) = 0.81 Tc (MIN.) = 114.45
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118710.93 FEET.

FLOW PROCESS FROM NODE 13402.00 TO NODE 13402.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P505XX10.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	165.51	18.39	0.30(0.29)	0.96	146.4	50500.00

TOTAL AREA (ACRES) = 146.4

FLOW PROCESS FROM NODE 13402.00 TO NODE 13402.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	17355.57	28.97	1.277	0.30(0.23)	0.77	6538.5	50320.00
2	19099.88	37.93	1.104	0.30(0.24)	0.79	9631.5	400.00
3	19679.43	43.72	1.022	0.30(0.24)	0.82	11944.2	50200.00
4	20186.15	48.70	0.963	0.30(0.25)	0.84	13896.7	31100.00
5	22352.19	68.29	0.819	0.30(0.26)	0.88	21855.1	13100.00
6	22776.12	75.04	0.786	0.30(0.27)	0.89	24230.7	11801.00
7	23928.51	88.54	0.719	0.30(0.27)	0.90	29813.6	11530.00
8	25258.78	100.48	0.682	0.30(0.28)	0.92	36429.7	13010.00
9	26059.02	106.28	0.666	0.30(0.28)	0.93	39942.8	11330.00
10	26766.16	114.45	0.643	0.30(0.28)	0.93	45030.0	10630.00
11	26567.64	120.02	0.627	0.30(0.28)	0.94	47619.8	12330.00
12	26366.72	126.64	0.616	0.30(0.28)	0.94	50762.3	11600.00

13	26043.70	132.42	0.606	0.30(0.28)	0.94	52996.6	11111.00
14	25679.68	138.55	0.595	0.30(0.28)	0.94	54930.5	12201.00
15	24843.67	147.50	0.580	0.30(0.28)	0.94	57018.7	12231.00
16	24071.31	154.99	0.568	0.30(0.28)	0.95	58430.3	10400.00
17	22834.62	166.42	0.548	0.30(0.28)	0.95	60051.0	10320.00
18	22197.69	171.29	0.540	0.30(0.28)	0.95	60276.5	10210.00
19	21637.94	176.16	0.532	0.30(0.28)	0.95	60438.8	12000.00
20	18819.74	205.41	0.505	0.30(0.28)	0.95	61055.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118710.93 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	165.51	18.39	1.677	0.30(0.29)	0.96	146.4	50500.00

LONGEST FLOWPATH FROM NODE 50500.00 TO NODE 13402.00 = 5416.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	15395.12	18.39	1.677	0.30(0.23)	0.78	4297.6	50500.00
2	17473.46	28.97	1.277	0.30(0.23)	0.77	6684.9	50320.00
3	19197.13	37.93	1.104	0.30(0.24)	0.79	9777.9	400.00
4	19766.95	43.72	1.022	0.30(0.24)	0.82	12090.6	50200.00
5	20266.68	48.70	0.963	0.30(0.25)	0.84	14043.1	31100.00
6	22415.53	68.29	0.819	0.30(0.26)	0.88	22001.5	13100.00
7	22835.49	75.04	0.786	0.30(0.27)	0.89	24377.1	11801.00
8	23979.95	88.54	0.719	0.30(0.27)	0.91	29960.0	11530.00
9	25305.82	100.48	0.682	0.30(0.28)	0.92	36576.1	13010.00
10	26104.11	106.28	0.666	0.30(0.28)	0.93	40089.2	11330.00
11	26808.49	114.45	0.643	0.30(0.28)	0.93	45176.4	10630.00
12	26608.08	120.02	0.627	0.30(0.28)	0.94	47766.2	12330.00
13	26405.83	126.64	0.616	0.30(0.28)	0.94	50908.7	11600.00
14	26081.64	132.42	0.606	0.30(0.28)	0.94	53143.0	11111.00
15	25716.37	138.55	0.595	0.30(0.28)	0.94	55076.9	12201.00
16	24878.55	147.50	0.580	0.30(0.28)	0.94	57165.1	12231.00
17	24104.67	154.99	0.568	0.30(0.28)	0.95	58576.7	10400.00
18	22865.66	166.42	0.548	0.30(0.28)	0.95	60197.4	10320.00
19	22227.75	171.29	0.540	0.30(0.28)	0.95	60422.9	10210.00
20	21667.01	176.16	0.532	0.30(0.28)	0.95	60585.2	12000.00
21	18845.70	205.41	0.505	0.30(0.28)	0.95	61202.2	10100.00

TOTAL AREA (ACRES) = 61202.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 26808.49 Tc (MIN.) = 114.445
EFFECTIVE AREA (ACRES) = 45176.36 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA (ACRES) = 61202.2
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118710.93 FEET.

FLOW PROCESS FROM NODE 13402.00 TO NODE 13404.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 209.00 DOWNSTREAM (FEET) = 207.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 395.35 CHANNEL SLOPE = 0.0051
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 8.46
CHANNEL FLOW THRU SUBAREA (CFS) = 26808.49
FLOW VELOCITY (FEET/SEC.) = 13.09 FLOW DEPTH (FEET) = 8.46
TRAVEL TIME (MIN.) = 0.50 Tc (MIN.) = 114.95
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119106.28 FEET.

FLOW PROCESS FROM NODE 13404.00 TO NODE 13404.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P506XX10.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	54.80	18.85	0.30 (0.29)	0.97	49.5	50600.00	
TOTAL AREA (ACRES) =							49.5

FLOW PROCESS FROM NODE 13404.00 TO NODE 13404.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15395.12	19.00	1.644	0.30 (0.23)	0.78	4297.6	50500.00
2	17473.46	29.55	1.261	0.30 (0.23)	0.77	6684.9	50320.00
3	19197.13	38.49	1.093	0.30 (0.24)	0.79	9777.9	400.00
4	19766.95	44.28	1.016	0.30 (0.24)	0.82	12090.6	50200.00
5	20266.68	49.25	0.957	0.30 (0.25)	0.84	14043.1	31100.00
6	22415.53	68.83	0.816	0.30 (0.26)	0.88	22001.5	13100.00
7	22835.49	75.57	0.783	0.30 (0.27)	0.89	24377.1	11801.00
8	23979.95	89.06	0.717	0.30 (0.27)	0.91	29960.0	11530.00
9	25305.82	101.00	0.681	0.30 (0.28)	0.92	36576.1	13010.00
10	26104.11	106.79	0.664	0.30 (0.28)	0.93	40089.2	11330.00
11	26808.49	114.95	0.641	0.30 (0.28)	0.93	45176.4	10630.00
12	26608.08	120.53	0.626	0.30 (0.28)	0.94	47766.2	12330.00
13	26405.83	127.15	0.615	0.30 (0.28)	0.94	50908.7	11600.00
14	26081.64	132.93	0.605	0.30 (0.28)	0.94	53143.0	11111.00
15	25716.37	139.06	0.595	0.30 (0.28)	0.94	55076.9	12201.00
16	24878.55	148.01	0.579	0.30 (0.28)	0.94	57165.1	12231.00
17	24104.67	155.51	0.567	0.30 (0.28)	0.95	58576.7	10400.00
18	22865.66	166.95	0.547	0.30 (0.28)	0.95	60197.4	10320.00
19	22227.75	171.82	0.539	0.30 (0.28)	0.95	60422.9	10210.00
20	21667.01	176.70	0.531	0.30 (0.28)	0.95	60585.2	12000.00
21	18845.70	205.97	0.505	0.30 (0.28)	0.95	61202.2	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119106.28 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	54.80	18.85	1.652	0.30 (0.29)	0.97	49.5	50600.00

LONGEST FLOWPATH FROM NODE 50600.00 TO NODE 13404.00 = 4378.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15416.28	18.85	1.652	0.30 (0.23)	0.78	4313.6	50600.00
2	15449.60	19.00	1.644	0.30 (0.23)	0.78	4347.1	50500.00
3	17512.53	29.55	1.261	0.30 (0.23)	0.78	6734.4	50320.00
4	19229.47	38.49	1.093	0.30 (0.24)	0.79	9827.4	400.00
5	19796.16	44.28	1.016	0.30 (0.25)	0.82	12140.1	50200.00
6	20293.52	49.25	0.957	0.30 (0.25)	0.84	14092.6	31100.00
7	22436.73	68.83	0.816	0.30 (0.26)	0.88	22051.0	13100.00
8	22855.35	75.57	0.783	0.30 (0.27)	0.89	24426.6	11801.00
9	23997.13	89.06	0.717	0.30 (0.27)	0.91	30009.5	11530.00
10	25321.56	101.00	0.681	0.30 (0.28)	0.92	36625.6	13010.00
11	26119.19	106.79	0.664	0.30 (0.28)	0.93	40138.7	11330.00
12	26822.64	114.95	0.641	0.30 (0.28)	0.93	45225.9	10630.00
13	26621.62	120.53	0.626	0.30 (0.28)	0.94	47815.7	12330.00
14	26418.91	127.15	0.615	0.30 (0.28)	0.94	50958.2	11600.00
15	26094.33	132.93	0.605	0.30 (0.28)	0.94	53192.5	11111.00
16	25728.64	139.06	0.595	0.30 (0.28)	0.94	55126.4	12201.00
17	24890.21	148.01	0.579	0.30 (0.28)	0.94	57214.6	12231.00
18	24115.81	155.51	0.567	0.30 (0.28)	0.95	58626.2	10400.00
19	22876.03	166.95	0.547	0.30 (0.28)	0.95	60246.9	10320.00
20	22237.78	171.82	0.539	0.30 (0.28)	0.95	60472.4	10210.00
21	21676.71	176.70	0.531	0.30 (0.28)	0.95	60634.7	12000.00
22	18854.36	205.97	0.505	0.30 (0.28)	0.95	61251.7	10100.00

TOTAL AREA (ACRES) = 61251.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
PEAK FLOW RATE (CFS) = 26822.64 Tc (MIN.) = 114.949
EFFECTIVE AREA (ACRES) = 45225.86 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA (ACRES) = 61251.7
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119106.28 FEET.

FLOW PROCESS FROM NODE 13404.00 TO NODE 13406.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 207.00 DOWNSTREAM (FEET) = 195.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 1601.97 CHANNEL SLOPE = 0.0075
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 7.56
CHANNEL FLOW THRU SUBAREA (CFS) = 26822.64
FLOW VELOCITY (FEET/SEC.) = 14.91 FLOW DEPTH (FEET) = 7.56
TRAVEL TIME (MIN.) = 1.79 Tc (MIN.) = 116.74
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13406.00 = 120708.25 FEET.

FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 116.74
* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.636
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/	SCS SOIL	AREA	Fp	Ap	SCS
-------------------	----------	------	----	----	-----

LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

NATURAL FAIR COVER
"GRASS" B 0.20 0.30 1.000 69

NATURAL FAIR COVER
"GRASS" B 4.00 0.30 1.000 69

NATURAL FAIR COVER
"GRASS" B 2.00 0.30 1.000 69

NATURAL FAIR COVER
"OPEN BRUSH" B 9.70 0.30 1.000 66

NATURAL FAIR COVER
"OPEN BRUSH" B 2.60 0.30 1.000 66

AGRICULTURAL POOR COVER
"ROW CROPS, STRAIGHT ROW" B 1.60 0.30 1.000 81

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 20.10 SUBAREA RUNOFF (CFS) = 6.08
EFFECTIVE AREA (ACRES) = 45245.96 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA (ACRES) = 61271.8 PEAK FLOW RATE (CFS) = 26822.64
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 116.74

* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.636

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "ROW CROPS, STRAIGHT ROW"	B	2.00	0.30	1.000	81
NATURAL FAIR COVER "WOODLAND, GRASS"	B	7.10	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND, GRASS"	B	5.80	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.10	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 15.00 SUBAREA RUNOFF (CFS) = 4.54

EFFECTIVE AREA (ACRES) = 45260.96 AREA-AVERAGED Fm (INCH/HR) = 0.28

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA (ACRES) = 61286.8 PEAK FLOW RATE (CFS) = 26822.64

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13406.00 TO NODE 13408.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 195.00 DOWNSTREAM (FEET) = 182.00

CHANNEL LENGTH THRU SUBAREA (FEET) = 2458.36 CHANNEL SLOPE = 0.0053

GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT (FEET) = 8.35

* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.628

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	7.00	0.30	1.000	66
NATURAL FAIR COVER "WOODLAND, GRASS"	B	3.30	0.30	1.000	65
COMMERCIAL	B	0.40	0.30	0.100	56
NATURAL FAIR COVER "OPEN BRUSH"	B	1.40	0.30	1.000	66
COMMERCIAL	B	0.30	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.949

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 26824.55

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 13.29

AVERAGE FLOW DEPTH (FEET) = 8.35 TRAVEL TIME (MIN.) = 3.08

Tc (MIN.) = 119.82

SUBAREA AREA (ACRES) = 12.40 SUBAREA RUNOFF (CFS) = 3.83

EFFECTIVE AREA (ACRES) = 45273.36 AREA-AVERAGED Fm (INCH/HR) = 0.28

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA (ACRES) = 61299.2 PEAK FLOW RATE (CFS) = 26822.64

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT (FEET) = 8.35

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 8.35 FLOW VELOCITY (FEET/SEC.) = 13.29

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123166.61 FEET.

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<

PEAK FLOWRATE TABLE FILE NAME: 2P10EVBB.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	518.09	10.14	0.30 (0.11)	0.38	237.9	429.00
2	548.24	11.82	0.30 (0.11)	0.38	277.3	425.00
3	551.99	12.10	0.30 (0.11)	0.38	284.1	400.00
4	566.31	13.74	0.30 (0.11)	0.38	322.9	300.00
5	605.65	19.30	0.30 (0.11)	0.38	439.2	210.00
6	601.31	21.30	0.30 (0.11)	0.38	463.8	410.00
7	598.36	22.55	0.30 (0.11)	0.38	478.8	200.00
8	595.72	23.25	0.30 (0.11)	0.38	486.6	230.00
9	580.44	24.41	0.30 (0.11)	0.37	491.2	220.50
TOTAL AREA (ACRES) =			491.2			

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Rows 1-22 showing flow data for various stream numbers.

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Rows 10-31 showing flow data for various stream numbers.

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
PEAK FLOW RATE(CFS) = 27052.75 Tc(MIN.) = 119.823
EFFECTIVE AREA(ACRES) = 45764.56 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.75
TOTAL AREA(ACRES) = 61790.4
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123166.61 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Rows 1-9 showing flow data for various stream numbers.

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P507XX10.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Rows 1 and TOTAL AREA(ACRES) = 231.4

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE

1	12752.87	10.14	2.489	0.30(0.22)	0.73	2025.0	429.00
2	13435.31	11.82	2.271	0.30(0.22)	0.73	2361.5	425.00
3	13509.70	12.10	2.234	0.30(0.22)	0.73	2418.0	400.00
4	13716.15	13.74	2.022	0.30(0.22)	0.73	2746.1	300.00
5	14999.42	19.30	1.628	0.30(0.22)	0.74	3841.6	210.00
6	15458.72	21.30	1.537	0.30(0.22)	0.74	4219.0	410.00
7	15717.35	22.55	1.487	0.30(0.22)	0.74	4453.6	200.00
8	15832.39	23.25	1.459	0.30(0.22)	0.74	4585.0	230.00
9	15966.06	24.41	1.412	0.30(0.22)	0.74	4795.6	220.50
10	15990.91	24.74	1.399	0.30(0.22)	0.74	4852.3	50600.00
11	16021.69	24.88	1.393	0.30(0.22)	0.74	4885.8	50500.00
12	17977.72	35.18	1.154	0.30(0.23)	0.75	7273.1	50320.00
13	19634.71	43.94	1.019	0.30(0.23)	0.77	10366.1	400.00
14	20171.15	49.68	0.952	0.30(0.24)	0.80	12678.8	50200.00
15	20648.72	54.60	0.907	0.30(0.25)	0.82	14631.3	31100.00
16	22739.85	74.00	0.791	0.30(0.26)	0.87	22589.7	13100.00
17	23143.68	80.71	0.758	0.30(0.26)	0.88	24965.3	11801.00
18	24259.78	94.12	0.700	0.30(0.27)	0.90	30548.2	11530.00
19	25569.21	105.97	0.667	0.30(0.27)	0.91	37164.3	13010.00
20	26359.57	111.71	0.650	0.30(0.28)	0.92	40677.4	11330.00
21	27052.75	119.82	0.628	0.30(0.28)	0.93	45764.6	10630.00
22	26847.40	125.41	0.618	0.30(0.28)	0.93	48354.4	12330.00
23	26639.65	132.05	0.607	0.30(0.28)	0.93	51496.9	11600.00
24	26310.66	137.85	0.597	0.30(0.28)	0.94	53731.2	11111.00
25	25940.30	144.00	0.586	0.30(0.28)	0.94	55665.1	12201.00
26	25095.03	153.01	0.571	0.30(0.28)	0.94	57753.3	12231.00
27	24314.90	160.56	0.558	0.30(0.28)	0.94	59164.9	10400.00
28	23066.35	172.09	0.538	0.30(0.28)	0.94	60785.6	10320.00
29	22424.37	177.01	0.530	0.30(0.28)	0.94	61011.1	10210.00
30	21860.36	181.94	0.524	0.30(0.28)	0.94	61173.4	12000.00
31	19027.83	211.46	0.501	0.30(0.28)	0.94	61790.4	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123166.61 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	215.04	23.85	1.434	0.30(0.30)	0.99	231.4	50700.00

LONGEST FLOWPATH FROM NODE 50700.00 TO NODE 13408.00 = 7683.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12928.97	10.14	2.489	0.30(0.22)	0.75	2123.3	429.00
2	13620.24	11.82	2.271	0.30(0.22)	0.75	2476.2	425.00
3	13695.53	12.10	2.234	0.30(0.22)	0.75	2535.4	400.00
4	13904.02	13.74	2.022	0.30(0.22)	0.75	2879.4	300.00
5	15202.97	19.30	1.628	0.30(0.22)	0.75	4028.8	210.00
6	15668.15	21.30	1.537	0.30(0.22)	0.75	4425.6	410.00
7	15930.04	22.55	1.487	0.30(0.22)	0.75	4672.3	200.00
8	16046.47	23.25	1.459	0.30(0.22)	0.75	4810.5	230.00
9	16116.88	23.85	1.434	0.30(0.23)	0.75	4925.8	50700.00
10	16176.81	24.41	1.412	0.30(0.23)	0.75	5027.0	220.50
11	16199.21	24.74	1.399	0.30(0.23)	0.75	5083.7	50600.00
12	16228.91	24.88	1.393	0.30(0.23)	0.75	5117.2	50500.00
13	18139.72	35.18	1.154	0.30(0.23)	0.76	7504.5	50320.00
14	19771.35	43.94	1.019	0.30(0.23)	0.78	10597.5	400.00
15	20295.00	49.68	0.952	0.30(0.24)	0.80	12910.2	50200.00
16	20764.20	54.60	0.907	0.30(0.25)	0.83	14862.7	31100.00

17	22833.30	74.00	0.791	0.30(0.26)	0.87	22821.1	13100.00
18	23230.88	80.71	0.758	0.30(0.26)	0.88	25196.7	11801.00
19	24336.10	94.12	0.700	0.30(0.27)	0.90	30779.6	11530.00
20	25639.20	105.97	0.667	0.30(0.27)	0.91	37395.7	13010.00
21	26426.48	111.71	0.650	0.30(0.28)	0.92	40908.8	11330.00
22	27115.32	119.82	0.628	0.30(0.28)	0.93	45996.0	10630.00
23	26908.13	125.41	0.618	0.30(0.28)	0.93	48585.8	12330.00
24	26698.25	132.05	0.607	0.30(0.28)	0.94	51728.3	11600.00
25	26367.40	137.85	0.597	0.30(0.28)	0.94	53962.6	11111.00
26	25995.06	144.00	0.586	0.30(0.28)	0.94	55896.4	12201.00
27	25146.90	153.01	0.571	0.30(0.28)	0.94	57984.7	12231.00
28	24364.34	160.56	0.558	0.30(0.28)	0.94	59396.2	10400.00
29	23112.09	172.09	0.538	0.30(0.28)	0.94	61017.0	10320.00
30	22468.52	177.01	0.530	0.30(0.28)	0.94	61242.5	10210.00
31	21903.27	181.94	0.524	0.30(0.28)	0.94	61404.8	12000.00
32	19066.43	211.46	0.501	0.30(0.28)	0.94	62021.8	10100.00

TOTAL AREA (ACRES) = 62021.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 27115.32 Tc (MIN.) = 119.823
 EFFECTIVE AREA (ACRES) = 45995.96 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA (ACRES) = 62021.8
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123166.61 FEET.

FLOW PROCESS FROM NODE 13408.00 TO NODE 13410.00 IS CODE = 56

>>>> COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>> TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 182.00 DOWNSTREAM (FEET) = 178.72
 CHANNEL LENGTH THRU SUBAREA (FEET) = 952.73 CHANNEL SLOPE = 0.0034
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 * ESTIMATED CHANNEL HEIGHT (FEET) = 9.49
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.625
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.40	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	2.90	0.30	1.000	65

SUBAREA AVERAGE Pervious LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE Pervious AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 27115.80
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 11.54
 AVERAGE FLOW DEPTH (FEET) = 9.49 TRAVEL TIME (MIN.) = 1.38
 Tc (MIN.) = 121.20
 SUBAREA AREA (ACRES) = 3.30 SUBAREA RUNOFF (CFS) = 0.97
 EFFECTIVE AREA (ACRES) = 45999.26 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA (ACRES) = 62025.1 PEAK FLOW RATE (CFS) = 27115.32
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 * ESTIMATED CHANNEL HEIGHT (FEET) = 9.49

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 9.49 FLOW VELOCITY(FEET/SEC.) = 11.54

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124119.34 FEET.

FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: RU10EV36.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1521.80	30.81	0.30(0.27)	0.90	1440.9	110.00
2	1573.72	33.19	0.30(0.27)	0.90	1597.0	100.00
3	1590.73	34.56	0.30(0.27)	0.90	1678.1	100.00
4	1600.63	37.85	0.30(0.27)	0.91	1850.3	130.00
5	1651.13	52.91	0.30(0.28)	0.93	2602.0	20100.00
6	1611.81	59.35	0.30(0.28)	0.93	2797.2	13600.00
7	1408.16	100.08	0.30(0.28)	0.93	3789.3	13510.00
8	1318.82	111.28	0.30(0.28)	0.93	3859.7	13500.00
TOTAL AREA(ACRES) =						3859.7

FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12928.97	11.90	2.261	0.30(0.22)	0.75	2126.6	429.00
2	13620.24	13.55	2.046	0.30(0.22)	0.75	2479.5	425.00
3	13695.53	13.83	2.010	0.30(0.22)	0.75	2538.7	400.00
4	13904.02	15.46	1.834	0.30(0.22)	0.75	2882.7	300.00
5	15202.97	20.97	1.551	0.30(0.22)	0.75	4032.1	210.00
6	15668.15	22.95	1.471	0.30(0.22)	0.75	4428.9	410.00
7	15930.04	24.19	1.421	0.30(0.22)	0.75	4675.6	200.00
8	16046.47	24.88	1.393	0.30(0.22)	0.75	4813.8	230.00
9	16116.88	25.49	1.374	0.30(0.23)	0.75	4929.1	50700.00
10	16176.81	26.05	1.359	0.30(0.23)	0.75	5030.3	220.50
11	16199.21	26.37	1.350	0.30(0.23)	0.75	5087.0	50600.00
12	16228.91	26.51	1.346	0.30(0.23)	0.75	5120.5	50500.00
13	18139.72	36.75	1.125	0.30(0.23)	0.76	7507.8	50320.00
14	19771.35	45.47	1.001	0.30(0.23)	0.78	10600.8	400.00
15	20295.00	51.19	0.938	0.30(0.24)	0.80	12913.5	50200.00
16	20764.20	56.11	0.894	0.30(0.25)	0.83	14866.0	31100.00
17	22833.30	75.46	0.784	0.30(0.26)	0.87	22824.4	13100.00
18	23230.88	82.16	0.751	0.30(0.26)	0.88	25200.0	11801.00
19	24336.10	95.55	0.696	0.30(0.27)	0.90	30782.9	11530.00

20	25639.20	107.37	0.663	0.30(0.27)	0.91	37399.0	13010.00
21	26426.48	113.10	0.647	0.30(0.28)	0.92	40912.1	11330.00
22	27115.32	121.20	0.625	0.30(0.28)	0.93	45999.3	10630.00
23	26908.13	126.79	0.615	0.30(0.28)	0.93	48589.1	12330.00
24	26698.25	133.43	0.604	0.30(0.28)	0.94	51731.6	11600.00
25	26367.40	139.24	0.594	0.30(0.28)	0.94	53965.9	11111.00
26	25995.06	145.40	0.584	0.30(0.28)	0.94	55899.8	12201.00
27	25146.90	154.42	0.568	0.30(0.28)	0.94	57988.0	12231.00
28	24364.34	161.99	0.556	0.30(0.28)	0.94	59399.6	10400.00
29	23112.09	173.54	0.536	0.30(0.28)	0.94	61020.3	10320.00
30	22468.52	178.48	0.528	0.30(0.28)	0.94	61245.8	10210.00
31	21903.27	183.41	0.522	0.30(0.28)	0.94	61408.1	12000.00
32	19066.43	213.01	0.500	0.30(0.28)	0.94	62025.1	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124119.34 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1521.80	30.81	1.233	0.30(0.27)	0.90	1440.9	110.00
2	1573.72	33.19	1.190	0.30(0.27)	0.90	1597.0	100.00
3	1590.73	34.56	1.165	0.30(0.27)	0.90	1678.1	100.00
4	1600.63	37.85	1.105	0.30(0.27)	0.91	1850.3	130.00
5	1651.13	52.91	0.922	0.30(0.28)	0.93	2602.0	20100.00
6	1611.81	59.35	0.866	0.30(0.28)	0.93	2797.2	13600.00
7	1408.16	100.08	0.683	0.30(0.28)	0.93	3789.3	13510.00
8	1318.82	111.28	0.652	0.30(0.28)	0.93	3859.7	13500.00

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13410.00 = 41710.10 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14143.95	11.90	2.261	0.30(0.23)	0.78	2683.2	429.00
2	14855.07	13.55	2.046	0.30(0.23)	0.78	3113.4	425.00
3	14930.13	13.83	2.010	0.30(0.23)	0.78	3185.7	400.00
4	15144.44	15.46	1.834	0.30(0.23)	0.78	3606.0	300.00
5	16580.30	20.97	1.551	0.30(0.23)	0.78	5012.8	210.00
6	17081.47	22.95	1.471	0.30(0.23)	0.78	5502.4	410.00
7	17357.52	24.19	1.421	0.30(0.23)	0.78	5806.9	200.00
8	17479.14	24.88	1.393	0.30(0.23)	0.78	5977.7	230.00
9	17560.34	25.49	1.374	0.30(0.23)	0.78	6121.3	50700.00
10	17631.02	26.05	1.359	0.30(0.23)	0.78	6248.6	220.50
11	17659.20	26.37	1.350	0.30(0.23)	0.78	6320.4	50600.00
12	17691.32	26.51	1.346	0.30(0.23)	0.78	6360.4	50500.00
13	18552.00	30.81	1.233	0.30(0.23)	0.78	7562.4	110.00
14	19048.07	33.19	1.190	0.30(0.23)	0.78	8273.5	100.00
15	19321.12	34.56	1.165	0.30(0.24)	0.78	8674.4	100.00
16	19737.05	36.75	1.125	0.30(0.24)	0.79	9300.7	50320.00
17	19945.64	37.85	1.105	0.30(0.24)	0.79	9747.3	130.00
18	21397.53	45.47	1.001	0.30(0.24)	0.80	12831.5	400.00
19	21940.38	51.19	0.938	0.30(0.25)	0.82	15430.1	50200.00
20	22109.58	52.91	0.922	0.30(0.25)	0.83	16195.8	20100.00
21	22395.80	56.11	0.894	0.30(0.25)	0.84	17565.0	31100.00
22	22723.11	59.35	0.866	0.30(0.25)	0.85	18998.3	13600.00
23	24364.59	75.46	0.784	0.30(0.26)	0.88	26013.9	13100.00
24	24728.63	82.16	0.751	0.30(0.27)	0.89	28552.9	11801.00
25	25766.92	95.55	0.696	0.30(0.27)	0.90	34461.9	11530.00
26	26243.59	100.08	0.683	0.30(0.27)	0.91	37107.4	13510.00
27	26989.22	107.37	0.663	0.30(0.27)	0.91	41234.1	13010.00

28	27495.70	111.28	0.652	0.30(0.28)	0.92	43658.0	13500.00
29	27727.04	113.10	0.647	0.30(0.28)	0.92	44771.8	11330.00
30	28339.22	121.20	0.625	0.30(0.28)	0.93	49858.9	10630.00
31	28098.29	126.79	0.615	0.30(0.28)	0.93	52448.8	12330.00
32	27848.38	133.43	0.604	0.30(0.28)	0.93	55591.3	11600.00
33	27482.51	139.24	0.594	0.30(0.28)	0.94	57825.6	11111.00
34	27072.99	145.40	0.584	0.30(0.28)	0.94	59759.4	12201.00
35	26170.40	154.42	0.568	0.30(0.28)	0.94	61847.7	12231.00
36	25342.20	161.99	0.556	0.30(0.28)	0.94	63259.2	10400.00
37	24020.28	173.54	0.536	0.30(0.28)	0.94	64880.0	10320.00
38	23346.93	178.48	0.528	0.30(0.28)	0.94	65105.5	10210.00
39	22763.13	183.41	0.522	0.30(0.28)	0.94	65267.8	12000.00
40	19845.19	213.01	0.500	0.30(0.28)	0.94	65884.8	10100.00
TOTAL AREA (ACRES) = 65884.8							

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 28339.22 Tc(MIN.) = 121.199
EFFECTIVE AREA(ACRES) = 49858.94 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.85
TOTAL AREA(ACRES) = 65884.8
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124119.34 FEET.

FLOW PROCESS FROM NODE 13410.00 TO NODE 13412.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 178.72 DOWNSTREAM(FEET) = 176.93
CHANNEL LENGTH THRU SUBAREA(FEET) = 169.78 CHANNEL SLOPE = 0.0105
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 7.08
CHANNEL FLOW THRU SUBAREA(CFS) = 28339.22
FLOW VELOCITY(FEET/SEC.) = 17.02 FLOW DEPTH(FEET) = 7.08
TRAVEL TIME(MIN.) = 0.17 Tc(MIN.) = 121.37
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124289.12 FEET.

FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506101E.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	366.95	40.42	0.30(0.30)	0.98	591.0	10100.00
TOTAL AREA (ACRES) = 591.0						

FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14143.95	12.11	2.233	0.30(0.23)	0.78	2683.2	429.00
2	14855.07	13.76	2.020	0.30(0.23)	0.78	3113.4	425.00
3	14930.13	14.04	1.983	0.30(0.23)	0.78	3185.7	400.00
4	15144.44	15.67	1.823	0.30(0.23)	0.78	3606.0	300.00
5	16580.30	21.17	1.543	0.30(0.23)	0.78	5012.8	210.00
6	17081.47	23.15	1.463	0.30(0.23)	0.78	5502.4	410.00
7	17357.52	24.38	1.413	0.30(0.23)	0.78	5806.9	200.00
8	17479.14	25.08	1.386	0.30(0.23)	0.78	5977.7	230.00
9	17560.34	25.68	1.369	0.30(0.23)	0.78	6121.3	50700.00
10	17631.02	26.24	1.353	0.30(0.23)	0.78	6248.6	220.50
11	17659.20	26.57	1.344	0.30(0.23)	0.78	6320.4	50600.00
12	17691.32	26.71	1.340	0.30(0.23)	0.78	6360.4	50500.00
13	18552.00	31.00	1.230	0.30(0.23)	0.78	7562.4	110.00
14	19048.07	33.38	1.187	0.30(0.23)	0.78	8273.5	100.00
15	19321.12	34.75	1.162	0.30(0.24)	0.78	8674.4	100.00
16	19737.05	36.94	1.122	0.30(0.24)	0.79	9300.7	50320.00
17	19945.64	38.04	1.102	0.30(0.24)	0.79	9747.3	130.00
18	21397.53	45.65	0.999	0.30(0.24)	0.80	12831.5	400.00
19	21940.38	51.37	0.936	0.30(0.25)	0.82	15430.1	50200.00
20	22109.58	53.09	0.921	0.30(0.25)	0.83	16195.8	20100.00
21	22395.80	56.29	0.893	0.30(0.25)	0.84	17565.0	31100.00
22	22723.11	59.53	0.864	0.30(0.25)	0.85	18998.3	13600.00
23	24364.59	75.63	0.783	0.30(0.26)	0.88	26013.9	13100.00
24	24728.63	82.33	0.750	0.30(0.27)	0.89	28552.9	11801.00
25	25766.92	95.72	0.696	0.30(0.27)	0.90	34461.9	11530.00
26	26243.59	100.25	0.683	0.30(0.27)	0.91	37107.4	13510.00
27	26989.22	107.54	0.662	0.30(0.27)	0.91	41234.1	13010.00
28	27495.70	111.45	0.651	0.30(0.28)	0.92	43658.0	13500.00
29	27727.04	113.26	0.646	0.30(0.28)	0.92	44771.8	11330.00
30	28339.22	121.37	0.625	0.30(0.28)	0.93	49858.9	10630.00
31	28098.29	126.96	0.615	0.30(0.28)	0.93	52448.8	12330.00
32	27848.38	133.60	0.604	0.30(0.28)	0.93	55591.3	11600.00
33	27482.51	139.40	0.594	0.30(0.28)	0.94	57825.6	11111.00
34	27072.99	145.57	0.584	0.30(0.28)	0.94	59759.4	12201.00
35	26170.40	154.59	0.568	0.30(0.28)	0.94	61847.7	12231.00
36	25342.20	162.16	0.555	0.30(0.28)	0.94	63259.2	10400.00
37	24020.28	173.71	0.536	0.30(0.28)	0.94	64880.0	10320.00
38	23346.93	178.65	0.527	0.30(0.28)	0.94	65105.5	10210.00
39	22763.13	183.59	0.522	0.30(0.28)	0.94	65267.8	12000.00
40	19845.19	213.20	0.499	0.30(0.28)	0.94	65884.8	10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124289.12 FEET.							

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	366.95	40.42	1.061	0.30(0.30)	0.98	591.0	10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 14677.00 FEET.							

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
---------------	---------	-----------	---------------------	------------------	----	------------	----------------

1	14422.16	12.11	2.233	0.30(0.24)	0.79	2860.2	429.00
2	15136.31	13.76	2.020	0.30(0.24)	0.79	3314.6	425.00
3	15211.06	14.04	1.983	0.30(0.24)	0.79	3391.0	400.00
4	15428.20	15.67	1.823	0.30(0.24)	0.79	3835.2	300.00
5	16893.32	21.17	1.543	0.30(0.24)	0.79	5322.3	210.00
6	17401.84	23.15	1.463	0.30(0.24)	0.79	5840.9	410.00
7	17680.55	24.38	1.413	0.30(0.24)	0.79	6163.4	200.00
8	17803.34	25.08	1.386	0.30(0.24)	0.79	6344.4	230.00
9	17887.19	25.68	1.369	0.30(0.24)	0.79	6496.8	50700.00
10	17960.12	26.24	1.353	0.30(0.24)	0.79	6632.3	220.50
11	17989.49	26.57	1.344	0.30(0.24)	0.79	6708.8	50600.00
12	18022.12	26.71	1.340	0.30(0.24)	0.79	6750.8	50500.00
13	18895.41	31.00	1.230	0.30(0.24)	0.79	8015.6	110.00
14	19400.71	33.38	1.187	0.30(0.24)	0.79	8761.5	100.00
15	19677.97	34.75	1.162	0.30(0.24)	0.80	9182.4	100.00
16	20098.95	36.94	1.122	0.30(0.24)	0.80	9840.8	50320.00
17	20309.28	38.04	1.102	0.30(0.24)	0.80	10303.4	130.00
18	20767.64	40.42	1.061	0.30(0.24)	0.80	11304.9	10100.00
19	21734.93	45.65	0.999	0.30(0.24)	0.81	13422.5	400.00
20	22247.40	51.37	0.936	0.30(0.25)	0.83	16021.1	50200.00
21	22409.39	53.09	0.921	0.30(0.25)	0.84	16786.8	20100.00
22	22682.11	56.29	0.893	0.30(0.25)	0.85	18156.0	31100.00
23	22995.75	59.53	0.864	0.30(0.26)	0.85	19589.3	13600.00
24	24598.31	75.63	0.783	0.30(0.26)	0.88	26604.9	13100.00
25	24946.51	82.33	0.750	0.30(0.27)	0.89	29143.9	11801.00
26	25958.92	95.72	0.696	0.30(0.27)	0.90	35052.9	11530.00
27	26429.44	100.25	0.683	0.30(0.27)	0.91	37698.4	13510.00
28	27165.18	107.54	0.662	0.30(0.27)	0.92	41825.1	13010.00
29	27666.35	111.45	0.651	0.30(0.28)	0.92	44249.0	13500.00
30	27895.22	113.26	0.646	0.30(0.28)	0.92	45362.8	11330.00
31	28497.15	121.37	0.625	0.30(0.28)	0.93	50449.9	10630.00
32	28251.66	126.96	0.615	0.30(0.28)	0.93	53039.8	12330.00
33	27996.35	133.60	0.604	0.30(0.28)	0.94	56182.3	11600.00
34	27625.75	139.40	0.594	0.30(0.28)	0.94	58416.6	11111.00
35	27211.21	145.57	0.584	0.30(0.28)	0.94	60350.4	12201.00
36	26301.27	154.59	0.568	0.30(0.28)	0.94	62438.7	12231.00
37	25466.90	162.16	0.555	0.30(0.28)	0.94	63850.2	10400.00
38	24135.57	173.71	0.536	0.30(0.28)	0.94	65471.0	10320.00
39	23458.20	178.65	0.527	0.30(0.28)	0.94	65696.5	10210.00
40	22871.98	183.59	0.522	0.30(0.28)	0.94	65858.8	12000.00
41	19943.09	213.20	0.499	0.30(0.28)	0.94	66475.8	10100.00

TOTAL AREA (ACRES) = 66475.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 28497.15 Tc (MIN.) = 121.366
EFFECTIVE AREA (ACRES) = 50449.94 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA (ACRES) = 66475.8
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124289.12 FEET.

FLOW PROCESS FROM NODE 13412.00 TO NODE 13700.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 176.93 DOWNSTREAM (FEET) = 170.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 260.10 CHANNEL SLOPE = 0.0266

GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 5.43
CHANNEL FLOW THRU SUBAREA (CFS) = 28497.15
FLOW VELOCITY (FEET/SEC.) = 23.11 FLOW DEPTH (FEET) = 5.43
TRAVEL TIME (MIN.) = 0.19 Tc (MIN.) = 121.55
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124549.22 FEET.

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<

PEAK FLOWRATE TABLE FILE NAME: P508XX10.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	124.05	23.35	0.30(0.30)	0.99	131.3	50800.00
TOTAL AREA (ACRES) =				131.3		

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14422.16	12.35	2.202	0.30(0.24)	0.79	2860.2	429.00
2	15136.31	14.00	1.989	0.30(0.24)	0.79	3314.6	425.00
3	15211.06	14.28	1.953	0.30(0.24)	0.79	3391.0	400.00
4	15428.20	15.90	1.810	0.30(0.24)	0.79	3835.2	300.00
5	16893.32	21.39	1.534	0.30(0.24)	0.79	5322.3	210.00
6	17401.84	23.37	1.454	0.30(0.24)	0.79	5840.9	410.00
7	17680.55	24.61	1.404	0.30(0.24)	0.79	6163.4	200.00
8	17803.34	25.30	1.380	0.30(0.24)	0.79	6344.4	230.00
9	17887.19	25.91	1.363	0.30(0.24)	0.79	6496.8	50700.00
10	17960.12	26.46	1.347	0.30(0.24)	0.79	6632.3	220.50
11	17989.49	26.79	1.338	0.30(0.24)	0.79	6708.8	50600.00
12	18022.12	26.93	1.334	0.30(0.24)	0.79	6750.8	50500.00
13	18895.41	31.21	1.226	0.30(0.24)	0.79	8015.6	110.00
14	19400.71	33.59	1.183	0.30(0.24)	0.79	8761.5	100.00
15	19677.97	34.96	1.158	0.30(0.24)	0.80	9182.4	100.00
16	20098.95	37.15	1.118	0.30(0.24)	0.80	9840.8	50320.00
17	20309.28	38.25	1.098	0.30(0.24)	0.80	10303.4	130.00
18	20767.64	40.63	1.059	0.30(0.24)	0.80	11304.9	10100.00
19	21734.93	45.86	0.997	0.30(0.24)	0.81	13422.5	400.00
20	22247.40	51.58	0.934	0.30(0.25)	0.83	16021.1	50200.00
21	22409.39	53.29	0.919	0.30(0.25)	0.84	16786.8	20100.00
22	22682.11	56.49	0.891	0.30(0.25)	0.85	18156.0	31100.00
23	22995.75	59.73	0.862	0.30(0.26)	0.85	19589.3	13600.00

24	24598.31	75.83	0.782	0.30 (0.26)	0.88	26604.9	13100.00
25	24946.51	82.53	0.749	0.30 (0.27)	0.89	29143.9	11801.00
26	25958.92	95.91	0.695	0.30 (0.27)	0.90	35052.9	11530.00
27	26429.44	100.44	0.682	0.30 (0.27)	0.91	37698.4	13510.00
28	27165.18	107.73	0.662	0.30 (0.27)	0.92	41825.1	13010.00
29	27666.35	111.64	0.651	0.30 (0.28)	0.92	44249.0	13500.00
30	27895.22	113.45	0.646	0.30 (0.28)	0.92	45362.8	11330.00
31	28497.15	121.55	0.624	0.30 (0.28)	0.93	50449.9	10630.00
32	28251.66	127.15	0.615	0.30 (0.28)	0.93	53039.8	12330.00
33	27996.35	133.79	0.604	0.30 (0.28)	0.94	56182.3	11600.00
34	27625.75	139.59	0.594	0.30 (0.28)	0.94	58416.6	11111.00
35	27211.21	145.76	0.583	0.30 (0.28)	0.94	60350.4	12201.00
36	26301.27	154.79	0.568	0.30 (0.28)	0.94	62438.7	12231.00
37	25466.90	162.36	0.555	0.30 (0.28)	0.94	63850.2	10400.00
38	24135.57	173.91	0.535	0.30 (0.28)	0.94	65471.0	10320.00
39	23458.20	178.85	0.527	0.30 (0.28)	0.94	65696.5	10210.00
40	22871.98	183.79	0.522	0.30 (0.28)	0.94	65858.8	12000.00
41	19943.09	213.41	0.499	0.30 (0.28)	0.94	66475.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124549.22 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	124.05	23.35	1.455	0.30 (0.30)	0.99	131.3	50800.00

LONGEST FLOWPATH FROM NODE 50800.00 TO NODE 13700.00 = 5946.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14530.14	12.35	2.202	0.30 (0.24)	0.80	2929.7	429.00
2	15244.99	14.00	1.989	0.30 (0.24)	0.79	3393.4	425.00
3	15319.53	14.28	1.953	0.30 (0.24)	0.79	3471.3	400.00
4	15538.65	15.90	1.810	0.30 (0.24)	0.79	3924.6	300.00
5	17014.74	21.39	1.534	0.30 (0.24)	0.79	5442.6	210.00
6	17519.00	23.35	1.455	0.30 (0.24)	0.79	5965.2	50800.00
7	17525.77	23.37	1.454	0.30 (0.24)	0.79	5972.2	410.00
8	17799.15	24.61	1.404	0.30 (0.24)	0.80	6294.7	200.00
9	17919.33	25.30	1.380	0.30 (0.24)	0.80	6475.7	230.00
10	18001.37	25.91	1.363	0.30 (0.24)	0.80	6628.1	50700.00
11	18072.63	26.46	1.347	0.30 (0.24)	0.80	6763.6	220.50
12	18101.04	26.79	1.338	0.30 (0.24)	0.80	6840.1	50600.00
13	18133.24	26.93	1.334	0.30 (0.24)	0.80	6882.1	50500.00
14	18994.95	31.21	1.226	0.30 (0.24)	0.80	8146.9	110.00
15	19495.62	33.59	1.183	0.30 (0.24)	0.80	8892.8	100.00
16	19770.21	34.96	1.158	0.30 (0.24)	0.80	9313.7	100.00
17	20186.91	37.15	1.118	0.30 (0.24)	0.80	9972.1	50320.00
18	20395.11	38.25	1.098	0.30 (0.24)	0.80	10434.7	130.00
19	20849.25	40.63	1.059	0.30 (0.24)	0.80	11436.2	10100.00
20	21809.94	45.86	0.997	0.30 (0.24)	0.81	13553.8	400.00
21	22315.69	51.58	0.934	0.30 (0.25)	0.83	16152.4	50200.00
22	22476.07	53.29	0.919	0.30 (0.25)	0.84	16918.1	20100.00
23	22745.78	56.49	0.891	0.30 (0.25)	0.85	18287.3	31100.00
24	23056.35	59.73	0.862	0.30 (0.26)	0.85	19720.6	13600.00
25	24650.30	75.83	0.782	0.30 (0.26)	0.88	26736.2	13100.00
26	24994.96	82.53	0.749	0.30 (0.27)	0.89	29275.2	11801.00
27	26001.63	95.91	0.695	0.30 (0.27)	0.90	35184.2	11530.00
28	26470.78	100.44	0.682	0.30 (0.27)	0.91	37829.7	13510.00
29	27204.30	107.73	0.662	0.30 (0.27)	0.92	41956.4	13010.00

30	27704.29	111.64	0.651	0.30 (0.28)	0.92	44380.3	13500.00
31	27932.61	113.45	0.646	0.30 (0.28)	0.92	45494.1	11330.00
32	28532.27	121.55	0.624	0.30 (0.28)	0.93	50581.2	10630.00
33	28285.76	127.15	0.615	0.30 (0.28)	0.93	53171.1	12330.00
34	28029.24	133.79	0.604	0.30 (0.28)	0.94	56313.6	11600.00
35	27657.58	139.59	0.594	0.30 (0.28)	0.94	58547.9	11111.00
36	27241.92	145.76	0.583	0.30 (0.28)	0.94	60481.7	12201.00
37	26330.33	154.79	0.568	0.30 (0.28)	0.94	62570.0	12231.00
38	25494.59	162.36	0.555	0.30 (0.28)	0.94	63981.5	10400.00
39	24161.15	173.91	0.535	0.30 (0.28)	0.94	65602.3	10320.00
40	23482.88	178.85	0.527	0.30 (0.28)	0.94	65827.8	10210.00
41	22896.14	183.79	0.522	0.30 (0.28)	0.94	65990.1	12000.00
42	19964.80	213.41	0.499	0.30 (0.28)	0.94	66607.1	10100.00

TOTAL AREA (ACRES) = 66607.1

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 28532.27 Tc (MIN.) = 121.553
EFFECTIVE AREA (ACRES) = 50581.24 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA (ACRES) = 66607.1
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124549.22 FEET.

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 66607.1 TC (MIN.) = 121.55
EFFECTIVE AREA (ACRES) = 50581.24 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.929
PEAK FLOW RATE (CFS) = 28532.27

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14530.14	12.35	2.202	0.30 (0.24)	0.80	2929.7	429.00
2	15244.99	14.00	1.989	0.30 (0.24)	0.79	3393.4	425.00
3	15319.53	14.28	1.953	0.30 (0.24)	0.79	3471.3	400.00
4	15538.65	15.90	1.810	0.30 (0.24)	0.79	3924.6	300.00
5	17014.74	21.39	1.534	0.30 (0.24)	0.79	5442.6	210.00
6	17519.00	23.35	1.455	0.30 (0.24)	0.79	5965.2	50800.00
7	17525.77	23.37	1.454	0.30 (0.24)	0.79	5972.2	410.00
8	17799.15	24.61	1.404	0.30 (0.24)	0.80	6294.7	200.00
9	17919.33	25.30	1.380	0.30 (0.24)	0.80	6475.7	230.00
10	18001.37	25.91	1.363	0.30 (0.24)	0.80	6628.1	50700.00
11	18072.63	26.46	1.347	0.30 (0.24)	0.80	6763.6	220.50
12	18101.04	26.79	1.338	0.30 (0.24)	0.80	6840.1	50600.00
13	18133.24	26.93	1.334	0.30 (0.24)	0.80	6882.1	50500.00
14	18994.95	31.21	1.226	0.30 (0.24)	0.80	8146.9	110.00
15	19495.62	33.59	1.183	0.30 (0.24)	0.80	8892.8	100.00
16	19770.21	34.96	1.158	0.30 (0.24)	0.80	9313.7	100.00
17	20186.91	37.15	1.118	0.30 (0.24)	0.80	9972.1	50320.00
18	20395.11	38.25	1.098	0.30 (0.24)	0.80	10434.7	130.00
19	20849.25	40.63	1.059	0.30 (0.24)	0.80	11436.2	10100.00
20	21809.94	45.86	0.997	0.30 (0.24)	0.81	13553.8	400.00
21	22315.69	51.58	0.934	0.30 (0.25)	0.83	16152.4	50200.00
22	22476.07	53.29	0.919	0.30 (0.25)	0.84	16918.1	20100.00
23	22745.78	56.49	0.891	0.30 (0.25)	0.85	18287.3	31100.00
24	23056.35	59.73	0.862	0.30 (0.26)	0.85	19720.6	13600.00
25	24650.30	75.83	0.782	0.30 (0.26)	0.88	26736.2	13100.00
26	24994.96	82.53	0.749	0.30 (0.27)	0.89	29275.2	11801.00
27	26001.63	95.91	0.695	0.30 (0.27)	0.90	35184.2	11530.00

28	26470.78	100.44	0.682	0.30 (0.27)	0.91	37829.7	13510.00
29	27204.30	107.73	0.662	0.30 (0.27)	0.92	41956.4	13010.00
30	27704.29	111.64	0.651	0.30 (0.28)	0.92	44380.3	13500.00
31	27932.61	113.45	0.646	0.30 (0.28)	0.92	45494.1	11330.00
32	28532.27	121.55	0.624	0.30 (0.28)	0.93	50581.2	10630.00
33	28285.76	127.15	0.615	0.30 (0.28)	0.93	53171.1	12330.00
34	28029.24	133.79	0.604	0.30 (0.28)	0.94	56313.6	11600.00
35	27657.58	139.59	0.594	0.30 (0.28)	0.94	58547.9	11111.00
36	27241.92	145.76	0.583	0.30 (0.28)	0.94	60481.7	12201.00
37	26330.33	154.79	0.568	0.30 (0.28)	0.94	62570.0	12231.00
38	25494.59	162.36	0.555	0.30 (0.28)	0.94	63981.5	10400.00
39	24161.15	173.91	0.535	0.30 (0.28)	0.94	65602.3	10320.00
40	23482.88	178.85	0.527	0.30 (0.28)	0.94	65827.8	10210.00
41	22896.14	183.79	0.522	0.30 (0.28)	0.94	65990.1	12000.00
42	19964.80	213.41	0.499	0.30 (0.28)	0.94	66607.1	10100.00

=====
=====
END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 136 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 10-YR EV OCT 2022 ROKAMOTO *

FILE NAME: RU10EV36.DAT
TIME/DATE OF STUDY: 13:50 10/24/2022

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 10.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 3.720
- 2) 10.00; 2.487
- 3) 15.00; 1.851
- 4) 20.00; 1.582
- 5) 25.00; 1.382
- 6) 30.00; 1.244
- 7) 40.00; 1.061
- 8) 50.00; 0.944
- 9) 60.00; 0.855
- 10) 90.00; 0.707
- 11) 120.00; 0.622
- 12) 180.00; 0.520
- 13) 360.00; 0.381
- 14) 1200.00; 0.166

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	STREET-CROSSFALL: HEIGHT (FT)	CURB WIDTH (FT)	GUTTER-GEOMETRIES: LIP (FT)	HIKE FACTOR (FT)	MANNING (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13600.00 TO NODE 13600.50 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 488.61
ELEVATION DATA: UPSTREAM(FEET) = 872.12 DOWNSTREAM(FEET) = 744.80

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 10.995
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.360
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "OPEN BRUSH"	-	3.39	0.30	1.000	65	11.00

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 6.29
TOTAL AREA(ACRES) = 3.39 PEAK FLOW RATE(CFS) = 6.29

FLOW PROCESS FROM NODE 13600.50 TO NODE 13601.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 744.80 DOWNSTREAM(FEET) = 707.32
CHANNEL LENGTH THRU SUBAREA(FEET) = 418.30 CHANNEL SLOPE = 0.0896
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.35
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.101
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.45	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 12.34
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.41
AVERAGE FLOW DEPTH(FEET) = 0.34 TRAVEL TIME(MIN.) = 2.04
Tc(MIN.) = 13.04
SUBAREA AREA(ACRES) = 7.45 SUBAREA RUNOFF(CFS) = 12.07
EFFECTIVE AREA(ACRES) = 10.84 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 10.8 PEAK FLOW RATE(CFS) = 17.57
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.42

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.42 FLOW VELOCITY(FEET/SEC.) = 3.89
LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13601.00 = 906.91 FEET.

FLOW PROCESS FROM NODE 13601.00 TO NODE 13602.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 707.32 DOWNSTREAM(FEET) = 657.12
CHANNEL LENGTH THRU SUBAREA(FEET) = 777.60 CHANNEL SLOPE = 0.0646
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.77
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.806

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.32	0.30	1.000	-
USER-DEFINED	-	4.70	0.30	1.000	-
USER-DEFINED	-	25.05	0.30	1.000	-
USER-DEFINED	-	0.45	0.30	1.000	-
USER-DEFINED	-	0.44	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 38.61

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.62

AVERAGE FLOW DEPTH(FEET) = 0.73 TRAVEL TIME(MIN.) = 2.81

Tc(MIN.) = 15.84

SUBAREA AREA(ACRES) = 30.96 SUBAREA RUNOFF(CFS) = 41.96
EFFECTIVE AREA(ACRES) = 41.80 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 41.8 PEAK FLOW RATE(CFS) = 56.64
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.91

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.91 FLOW VELOCITY(FEET/SEC.) = 5.26

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13602.00 = 1684.51 FEET.

FLOW PROCESS FROM NODE 13602.00 TO NODE 13603.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 657.12 DOWNSTREAM(FEET) = 584.58
CHANNEL LENGTH THRU SUBAREA(FEET) = 1186.54 CHANNEL SLOPE = 0.0611
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.07
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.614

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.03	0.30	1.000	-
USER-DEFINED	-	2.51	0.30	1.000	-

USER-DEFINED - 1.52 0.30 1.000 -
USER-DEFINED - 12.30 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 70.48

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.56

AVERAGE FLOW DEPTH(FEET) = 1.05 TRAVEL TIME(MIN.) = 3.56

Tc(MIN.) = 19.40

SUBAREA AREA(ACRES) = 23.36 SUBAREA RUNOFF(CFS) = 27.63
EFFECTIVE AREA(ACRES) = 65.16 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 65.2 PEAK FLOW RATE(CFS) = 77.08
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.10

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.10 FLOW VELOCITY(FEET/SEC.) = 5.72

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13603.00 = 2871.05 FEET.

FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 584.58 DOWNSTREAM(FEET) = 544.91
CHANNEL LENGTH THRU SUBAREA(FEET) = 860.98 CHANNEL SLOPE = 0.0461
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.30
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.500

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	10.22	0.30	1.000	-
USER-DEFINED	-	4.19	0.30	1.000	-
USER-DEFINED	-	0.07	0.30	1.000	-
USER-DEFINED	-	1.11	0.30	1.000	-
USER-DEFINED	-	5.56	0.30	1.000	-
USER-DEFINED	-	0.09	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 88.56

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.44

AVERAGE FLOW DEPTH(FEET) = 1.29 TRAVEL TIME(MIN.) = 2.64

Tc(MIN.) = 22.04

SUBAREA AREA(ACRES) = 21.24 SUBAREA RUNOFF(CFS) = 22.95
EFFECTIVE AREA(ACRES) = 86.40 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 86.4 PEAK FLOW RATE(CFS) = 93.35
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.33

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.33 FLOW VELOCITY(FEET/SEC.) = 5.53

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13620.00 = 3732.03 FEET.

```

*****
FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 10
-----
>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<
=====
*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13522.00 IS CODE = 15.1
-----
>>>>DEFINE MEMORY BANK # 2 <<<<<
=====
PEAK FLOWRATE TABLE FILE NAME: S35X10.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:
STREAM      Q      Tc      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR)    (ACRES)  NODE
  1         688.52  58.84  0.30( 0.28) 0.95    1509.5  13510.00
  2         640.29  69.13  0.30( 0.28) 0.94    1579.8  13500.00
TOTAL AREA (ACRES) = 1579.8

*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13522.00 IS CODE = 14.0
-----
>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<
=====
MAIN-STREAM MEMORY DEFINED AS FOLLOWS:
STREAM      Q      Tc      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR)    (ACRES)  NODE
  1         688.52  58.84  0.30( 0.28) 0.95    1509.5  13510.00
  2         640.29  69.13  0.30( 0.28) 0.94    1579.8  13500.00
TOTAL AREA (ACRES) = 1579.8

*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13620.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 632.19 DOWNSTREAM(FEET) = 544.91
CHANNEL LENGTH THRU SUBAREA(FEET) = 2062.96 CHANNEL SLOPE = 0.0423
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.87
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.844
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp      Ap      SCS
LAND USE              GROUP  (ACRES)  (INCH/HR)  (DECIMAL)  CN
USER-DEFINED          -      17.68    0.30    1.000    -
USER-DEFINED          -      2.36    0.30    1.000    -
USER-DEFINED          -      0.60    0.30    1.000    -
USER-DEFINED          -      0.22    0.30    1.000    -
USER-DEFINED          -      2.22    0.30    1.000    -
USER-DEFINED          -      3.42    0.30    1.000    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 695.01
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.42

```

```

AVERAGE FLOW DEPTH(FEET) = 1.87 TRAVEL TIME(MIN.) = 3.30
Tc(MIN.) = 62.14
SUBAREA AREA(ACRES) = 26.50 SUBAREA RUNOFF(CFS) = 12.99
EFFECTIVE AREA(ACRES) = 1535.98 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
TOTAL AREA(ACRES) = 1606.3 PEAK FLOW RATE(CFS) = 774.35
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.99

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.99 FLOW VELOCITY(FEET/SEC.) = 10.79
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

*****
FLOW PROCESS FROM NODE 13620.00 TO NODE 13620.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====
MAINLINE Tc(MIN.) = 62.14
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.844
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp      Ap      SCS
LAND USE              GROUP  (ACRES)  (INCH/HR)  (DECIMAL)  CN
NATURAL FAIR COVER
"WOODLAND,GRASS"      B      1.44    0.30    1.000    65
NATURAL FAIR COVER
"WOODLAND,GRASS"      B      0.01    0.30    1.000    65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 1.45 SUBAREA RUNOFF(CFS) = 0.71
EFFECTIVE AREA(ACRES) = 1537.43 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
TOTAL AREA(ACRES) = 1607.8 PEAK FLOW RATE(CFS) = 775.06

*****
FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 11
-----
>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<
=====
** MAIN STREAM CONFLUENCE DATA **
STREAM      Q      Tc      Intensity  Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR)  (INCH/HR)  (ACRES)  NODE
  1         775.06  62.14  0.844  0.30( 0.28) 0.95    1537.4  13510.00
  2         737.52  72.51  0.793  0.30( 0.28) 0.95    1607.8  13500.00
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **
STREAM      Q      Tc      Intensity  Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR)  (INCH/HR)  (ACRES)  NODE
  1         93.35  22.04  1.500  0.30( 0.30) 1.00    86.4    13600.00
LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13620.00 = 3732.03 FEET.

** PEAK FLOW RATE TABLE **
STREAM      Q      Tc      Intensity  Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR)  (INCH/HR)  (ACRES)  NODE
  1         690.20  22.04  1.500  0.30( 0.29) 0.96    631.7   13600.00

```

2 817.40 62.14 0.844 0.30(0.29) 0.95 1623.8 13510.00
3 775.88 72.51 0.793 0.30(0.28) 0.95 1694.2 13500.00
TOTAL AREA(ACRES) = 1694.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 817.40 Tc(MIN.) = 62.136
EFFECTIVE AREA(ACRES) = 1623.83 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA(ACRES) = 1694.2
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

FLOW PROCESS FROM NODE 13620.00 TO NODE 13640.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 544.91 DOWNSTREAM(FEET) = 489.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1384.37 CHANNEL SLOPE = 0.0404
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.10
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.834

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.39	0.30	1.000	-
USER-DEFINED	-	16.30	0.30	1.000	-
USER-DEFINED	-	4.08	0.30	1.000	-
USER-DEFINED	-	12.36	0.30	1.000	-
USER-DEFINED	-	11.23	0.30	1.000	-
USER-DEFINED	-	5.16	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 830.51
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.89
AVERAGE FLOW DEPTH(FEET) = 2.10 TRAVEL TIME(MIN.) = 2.12
Tc(MIN.) = 64.26

SUBAREA AREA(ACRES) = 54.52 SUBAREA RUNOFF(CFS) = 26.21
EFFECTIVE AREA(ACRES) = 1678.35 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
TOTAL AREA(ACRES) = 1748.7 PEAK FLOW RATE(CFS) = 828.33
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.10

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.10 FLOW VELOCITY(FEET/SEC.) = 10.90
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 64.26
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.834
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	53.93	0.30	1.000	-
USER-DEFINED	-	0.45	0.30	1.000	-
USER-DEFINED	-	3.98	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 58.36 SUBAREA RUNOFF(CFS) = 28.05
EFFECTIVE AREA(ACRES) = 1736.71 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
TOTAL AREA(ACRES) = 1807.1 PEAK FLOW RATE(CFS) = 856.39

FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P201XX10.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	158.08	17.90	0.30(0.26)	0.85	133.8	20100.00

TOTAL AREA(ACRES) = 133.8

FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	752.50	24.27	1.411	0.30(0.29)	0.96	744.6	13600.00
2	856.39	64.26	0.834	0.30(0.29)	0.95	1736.7	13510.00
3	808.68	74.67	0.783	0.30(0.29)	0.95	1807.1	13500.00

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	158.08	17.90	1.695	0.30(0.26)	0.85	133.8	20100.00

LONGEST FLOWPATH FROM NODE 20100.00 TO NODE 13640.00 = 5247.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	853.43	17.90	1.695	0.30(0.28)	0.94	683.2	20100.00
2	879.44	24.27	1.411	0.30(0.28)	0.95	878.4	13600.00
3	919.88	64.26	0.834	0.30(0.28)	0.95	1870.5	13510.00
4	866.53	74.67	0.783	0.30(0.28)	0.94	1940.9	13500.00

TOTAL AREA(ACRES) = 1940.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 919.88 Tc(MIN.) = 64.255
EFFECTIVE AREA(ACRES) = 1870.51 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
TOTAL AREA(ACRES) = 1940.9

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

FLOW PROCESS FROM NODE 13640.00 TO NODE 13641.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 489.00 DOWNSTREAM(FEET) = 436.89
CHANNEL LENGTH THRU SUBAREA(FEET) = 2994.52 CHANNEL SLOPE = 0.0174
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 2.85

* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.805

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.96	0.30	1.000	-
USER-DEFINED	-	0.01	0.30	1.000	-
USER-DEFINED	-	1.56	0.30	1.000	-
USER-DEFINED	-	10.45	0.30	1.000	-
USER-DEFINED	-	44.94	0.30	1.000	-
USER-DEFINED	-	9.66	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 935.24

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.51

AVERAGE FLOW DEPTH(FEET) = 2.85 TRAVEL TIME(MIN.) = 5.86

Tc(MIN.) = 70.12

SUBAREA AREA(ACRES) = 67.58 SUBAREA RUNOFF(CFS) = 30.72

EFFECTIVE AREA(ACRES) = 1938.09 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95

TOTAL AREA(ACRES) = 2008.4 PEAK FLOW RATE(CFS) = 919.88

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 2.83

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.83 FLOW VELOCITY(FEET/SEC.) = 8.46

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13641.00 = 25056.61 FEET.

FLOW PROCESS FROM NODE 13641.00 TO NODE 13641.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 70.12

* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.805

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	16.49	0.30	1.000	-
USER-DEFINED	-	20.39	0.30	1.000	-
USER-DEFINED	-	7.02	0.30	1.000	-
USER-DEFINED	-	12.58	0.30	1.000	-
USER-DEFINED	-	42.49	0.30	1.000	-
USER-DEFINED	-	5.73	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 104.70 SUBAREA RUNOFF(CFS) = 47.60

EFFECTIVE AREA(ACRES) = 2042.79 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95

TOTAL AREA(ACRES) = 2113.1 PEAK FLOW RATE(CFS) = 955.58

FLOW PROCESS FROM NODE 13641.00 TO NODE 13641.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 70.12

* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.805

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.78	0.30	1.000	-
USER-DEFINED	-	6.25	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 8.03 SUBAREA RUNOFF(CFS) = 3.65

EFFECTIVE AREA(ACRES) = 2050.82 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95

TOTAL AREA(ACRES) = 2121.2 PEAK FLOW RATE(CFS) = 959.23

FLOW PROCESS FROM NODE 13641.00 TO NODE 13642.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 436.89 DOWNSTREAM(FEET) = 394.80
CHANNEL LENGTH THRU SUBAREA(FEET) = 2814.16 CHANNEL SLOPE = 0.0150
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 3.10
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.777

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.67	0.30	1.000	-
USER-DEFINED	-	24.24	0.30	1.000	-
USER-DEFINED	-	1.34	0.30	1.000	-
USER-DEFINED	-	74.98	0.30	1.000	-
USER-DEFINED	-	101.12	0.30	1.000	-
USER-DEFINED	-	16.90	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1006.31

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.26

AVERAGE FLOW DEPTH(FEET) = 3.10 TRAVEL TIME(MIN.) = 5.68

Tc(MIN.) = 75.80

SUBAREA AREA(ACRES) = 219.25 SUBAREA RUNOFF(CFS) = 94.15

EFFECTIVE AREA(ACRES) = 2270.07 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96

TOTAL AREA(ACRES) = 2340.4 PEAK FLOW RATE(CFS) = 1001.67

GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 3.09

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 3.09 FLOW VELOCITY(FEET/SEC.) = 8.26
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13642.00 = 27870.77 FEET.

FLOW PROCESS FROM NODE 13642.00 TO NODE 13642.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 75.80
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.777
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	9.95	0.30	1.000	-
USER-DEFINED	-	10.02	0.30	1.000	-
USER-DEFINED	-	4.45	0.30	1.000	-
USER-DEFINED	-	179.37	0.30	1.000	-
USER-DEFINED	-	11.47	0.30	1.000	-
USER-DEFINED	-	0.17	0.30	0.850	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 215.43 SUBAREA RUNOFF(CFS) = 92.52
EFFECTIVE AREA(ACRES) = 2485.50 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA(ACRES) = 2555.9 PEAK FLOW RATE(CFS) = 1094.18

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1127.58	29.58	1.256	0.30(0.29)	0.97	1298.2	20100.00
2	1137.09	35.88	1.136	0.30(0.29)	0.97	1493.4	13600.00
3	1094.18	75.80	0.777	0.30(0.29)	0.96	2485.5	13510.00
4	1005.57	86.45	0.725	0.30(0.29)	0.96	2555.9	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 1137.09 Tc(MIN.) = 35.88
AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.97 EFFECTIVE AREA(ACRES) = 1493.41

FLOW PROCESS FROM NODE 13642.00 TO NODE 13642.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 35.88
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.136
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.03	0.30	0.850	-
USER-DEFINED	-	5.14	0.30	1.000	-
USER-DEFINED	-	11.22	0.30	1.000	-
USER-DEFINED	-	0.33	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 16.72 SUBAREA RUNOFF(CFS) = 12.59
EFFECTIVE AREA(ACRES) = 1510.13 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 2572.6 PEAK FLOW RATE(CFS) = 1149.68

FLOW PROCESS FROM NODE 13642.00 TO NODE 13643.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 394.80 DOWNSTREAM(FEET) = 342.39
CHANNEL LENGTH THRU SUBAREA(FEET) = 2913.57 CHANNEL SLOPE = 0.0180
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 3.25
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.048
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	2.17	0.30	1.000	-
USER-DEFINED	-	9.19	0.30	1.000	-
USER-DEFINED	-	67.57	0.30	1.000	-
USER-DEFINED	-	35.19	0.30	1.000	-
USER-DEFINED	-	30.67	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1198.50
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.29
AVERAGE FLOW DEPTH(FEET) = 3.25 TRAVEL TIME(MIN.) = 5.22
Tc(MIN.) = 41.11
SUBAREA AREA(ACRES) = 145.01 SUBAREA RUNOFF(CFS) = 97.63
EFFECTIVE AREA(ACRES) = 1655.14 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 2717.6 PEAK FLOW RATE(CFS) = 1149.68
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 3.17

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 3.17 FLOW VELOCITY(FEET/SEC.) = 9.18
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13643.00 = 30784.34 FEET.

FLOW PROCESS FROM NODE 13643.00 TO NODE 13643.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 41.11
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.048
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.89	0.30	1.000	-
USER-DEFINED	-	20.65	0.30	1.000	-
USER-DEFINED	-	2.69	0.30	1.000	-

USER-DEFINED - 8.45 0.30 1.000 -
 USER-DEFINED - 96.93 0.30 1.000 -
 USER-DEFINED - 13.19 0.30 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 142.80 SUBAREA RUNOFF(CFS) = 96.14
 EFFECTIVE AREA(ACRES) = 1797.94 AREA-AVERAGED Fm(INCH/HR) = 0.29
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA(ACRES) = 2860.4 PEAK FLOW RATE(CFS) = 1223.45

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1246.17	34.79	1.156	0.30(0.29)	0.97	1602.7	20100.00
2	1223.45	41.11	1.048	0.30(0.29)	0.97	1797.9	13600.00
3	1159.10	81.12	0.751	0.30(0.29)	0.96	2790.0	13510.00
4	1062.94	91.91	0.702	0.30(0.29)	0.96	2860.4	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 1246.17 Tc(MIN.) = 34.79
 AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.97 EFFECTIVE AREA(ACRES) = 1602.73

FLOW PROCESS FROM NODE 13643.00 TO NODE 13643.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 34.79

* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.156

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	42.54	0.30	1.000	-
USER-DEFINED	-	16.96	0.30	1.000	-
USER-DEFINED	-	80.60	0.30	1.000	-
USER-DEFINED	-	1.56	0.30	1.000	-
USER-DEFINED	-	2.00	0.30	1.000	-
USER-DEFINED	-	3.11	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 146.77 SUBAREA RUNOFF(CFS) = 113.12

EFFECTIVE AREA(ACRES) = 1749.50 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98

TOTAL AREA(ACRES) = 3007.2 PEAK FLOW RATE(CFS) = 1359.28

FLOW PROCESS FROM NODE 13643.00 TO NODE 13660.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 342.39 DOWNSTREAM(FEET) = 300.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 1591.23 CHANNEL SLOPE = 0.0266

GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 3.15

* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.113

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.89	0.30	1.000	-
USER-DEFINED	-	23.73	0.30	1.000	-
USER-DEFINED	-	0.27	0.30	1.000	-
USER-DEFINED	-	19.87	0.30	1.000	-
USER-DEFINED	-	6.40	0.30	1.000	-
USER-DEFINED	-	3.14	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1379.14

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.11

AVERAGE FLOW DEPTH(FEET) = 3.15 TRAVEL TIME(MIN.) = 2.39

Tc(MIN.) = 37.18

SUBAREA AREA(ACRES) = 54.30 SUBAREA RUNOFF(CFS) = 39.72

EFFECTIVE AREA(ACRES) = 1803.80 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98

TOTAL AREA(ACRES) = 3061.5 PEAK FLOW RATE(CFS) = 1359.28

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 3.12

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 3.12 FLOW VELOCITY(FEET/SEC.) = 11.08

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 32375.57 FEET.

FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 37.18

* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.113

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.67	0.30	1.000	-
USER-DEFINED	-	9.52	0.30	1.000	-
USER-DEFINED	-	0.71	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	39.42	0.30	1.000	-
USER-DEFINED	-	0.62	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 51.16 SUBAREA RUNOFF(CFS) = 37.42

EFFECTIVE AREA(ACRES) = 1854.96 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98

TOTAL AREA(ACRES) = 3112.6 PEAK FLOW RATE(CFS) = 1367.67

FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 37.18

* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.113

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 0.11 0.30 1.000 -
 USER-DEFINED - 0.77 0.30 1.000 -
 USER-DEFINED - 0.22 0.30 1.000 -
 USER-DEFINED - 2.69 0.30 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 3.79 SUBAREA RUNOFF (CFS) = 2.77
 EFFECTIVE AREA (ACRES) = 1858.75 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
 TOTAL AREA (ACRES) = 3116.4 PEAK FLOW RATE (CFS) = 1370.44

 FLOW PROCESS FROM NODE 13643.00 TO NODE 13660.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

 FLOW PROCESS FROM NODE 13659.00 TO NODE 13659.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 2P10EVAA.DNA
 MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap (DECIMAL)	Ae (ACRES)	HEADWATER NODE
1	369.81	15.08	0.30 (0.11)	0.36	172.7	110.00
2	370.44	17.62	0.30 (0.11)	0.37	203.0	100.00
3	361.39	19.04	0.30 (0.11)	0.38	213.7	100.00
4	316.02	22.37	0.30 (0.12)	0.40	221.1	130.00
TOTAL AREA (ACRES) =						221.1

 FLOW PROCESS FROM NODE 13659.00 TO NODE 13660.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 338.00 DOWNSTREAM (FEET) = 300.00
 FLOW LENGTH (FEET) = 881.07 MANNING'S N = 0.013
 DEPTH OF FLOW IN 87.0 INCH PIPE IS 70.7 INCHES
 PIPE-FLOW VELOCITY (FEET/SEC.) = 38.17
 ESTIMATED PIPE DIAMETER (INCH) = 87.00 NUMBER OF PIPES = 1
 PIPE-FLOW (CFS) = 1370.44
 PIPE TRAVEL TIME (MIN.) = 0.38 Tc (MIN.) = 37.56
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

 FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap (DECIMAL)	Ae (ACRES)	HEADWATER NODE
---------------	---------	-----------	---------------------	-------------------	--------------	------------	----------------

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap (DECIMAL)	Ae (ACRES)	HEADWATER NODE
1	1370.44	37.56	1.106	0.30 (0.29)	0.98	1858.7	20100.00
2	1343.78	43.90	1.015	0.30 (0.29)	0.98	2054.0	13600.00
3	1229.56	83.98	0.737	0.30 (0.29)	0.97	3046.0	13510.00
4	1135.31	94.85	0.693	0.30 (0.29)	0.97	3116.4	13500.00

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap (DECIMAL)	Ae (ACRES)	HEADWATER NODE
1	369.81	15.08	1.847	0.30 (0.11)	0.36	172.7	110.00
2	370.44	17.62	1.710	0.30 (0.11)	0.37	203.0	100.00
3	361.39	19.04	1.634	0.30 (0.11)	0.38	213.7	100.00
4	316.02	22.37	1.487	0.30 (0.12)	0.40	221.1	130.00

LONGEST FLOWPATH FROM NODE 130.00 TO NODE 13660.00 = 6327.50 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap (DECIMAL)	Ae (ACRES)	HEADWATER NODE
1	1421.87	15.08	1.847	0.30 (0.26)	0.86	918.7	110.00
2	1491.67	17.62	1.710	0.30 (0.26)	0.86	1074.8	100.00
3	1507.68	19.04	1.634	0.30 (0.26)	0.87	1155.9	100.00
4	1515.65	22.37	1.487	0.30 (0.26)	0.88	1328.1	130.00
5	1598.25	37.56	1.106	0.30 (0.28)	0.92	2079.8	20100.00
6	1550.73	43.90	1.015	0.30 (0.28)	0.92	2275.1	13600.00
7	1372.07	83.98	0.737	0.30 (0.28)	0.93	3267.1	13510.00
8	1267.78	94.85	0.693	0.30 (0.28)	0.93	3337.5	13500.00
TOTAL AREA (ACRES) =						3337.5	

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
 PEAK FLOW RATE (CFS) = 1598.25 Tc (MIN.) = 37.564
 EFFECTIVE AREA (ACRES) = 2079.85 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.86
 TOTAL AREA (ACRES) = 3337.5
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

 FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 37.56
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.106
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "FALLOW"	B	1.11	0.30	1.000	86
AGRICULTURAL POOR COVER "FALLOW"	B	0.44	0.30	1.000	86
NATURAL FAIR COVER "GRASS"	B	1.49	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	1.70	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	1.09	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	18.57	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 24.40 SUBAREA RUNOFF (CFS) = 17.69
 EFFECTIVE AREA (ACRES) = 2104.25 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA (ACRES) = 3361.9 PEAK FLOW RATE (CFS) = 1598.25
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) = 37.56

* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.106

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL FAIR COVER "ORCHARDS"	B	12.39	0.30	1.000	65
AGRICULTURAL FAIR COVER "ORCHARDS"	B	2.30	0.30	1.000	65
AGRICULTURAL POOR COVER "ROW CROPS, CONTOURED"	B	5.19	0.30	1.000	79
AGRICULTURAL POOR COVER "ROW CROPS, STRAIGHT ROW"	B	28.71	0.30	1.000	81
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.17	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 48.76 SUBAREA RUNOFF (CFS) = 35.35

EFFECTIVE AREA (ACRES) = 2153.01 AREA-AVERAGED Fm (INCH/HR) = 0.28

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92

TOTAL AREA (ACRES) = 3410.7 PEAK FLOW RATE (CFS) = 1607.75

 FLOW PROCESS FROM NODE 13660.00 TO NODE 13680.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 300.00 DOWNSTREAM (FEET) = 288.00

CHANNEL LENGTH THRU SUBAREA (FEET) = 933.89 CHANNEL SLOPE = 0.0128

GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

* ESTIMATED CHANNEL HEIGHT (FEET) = 4.19

* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.074

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	9.23	0.30	1.000	-
USER-DEFINED	-	0.54	0.30	1.000	-
USER-DEFINED	-	5.66	0.30	1.000	-
USER-DEFINED	-	3.66	0.30	1.000	-
USER-DEFINED	-	0.67	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 1614.71

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 9.06
 AVERAGE FLOW DEPTH (FEET) = 4.19 TRAVEL TIME (MIN.) = 1.72
 Tc (MIN.) = 39.28
 SUBAREA AREA (ACRES) = 19.98 SUBAREA RUNOFF (CFS) = 13.92
 EFFECTIVE AREA (ACRES) = 2172.99 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA (ACRES) = 3430.6 PEAK FLOW RATE (CFS) = 1607.75
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 * ESTIMATED CHANNEL HEIGHT (FEET) = 4.18

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 4.18 FLOW VELOCITY (FEET/SEC.) = 9.05

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13680.00 = 34190.53 FEET.

 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) = 39.28

* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.074

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.56	0.30	1.000	-
USER-DEFINED	-	9.40	0.30	1.000	-
USER-DEFINED	-	2.76	0.30	1.000	-
USER-DEFINED	-	17.38	0.30	1.000	-
USER-DEFINED	-	2.46	0.30	1.000	-
USER-DEFINED	-	5.56	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 39.12 SUBAREA RUNOFF (CFS) = 27.26

EFFECTIVE AREA (ACRES) = 2212.11 AREA-AVERAGED Fm (INCH/HR) = 0.28

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92

TOTAL AREA (ACRES) = 3469.8 PEAK FLOW RATE (CFS) = 1607.75

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) = 39.28

* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.074

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.65	0.30	1.000	-
USER-DEFINED	-	1.70	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 2.35 SUBAREA RUNOFF (CFS) = 1.64

EFFECTIVE AREA (ACRES) = 2214.46 AREA-AVERAGED Fm (INCH/HR) = 0.28

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92

TOTAL AREA (ACRES) = 3472.1 PEAK FLOW RATE (CFS) = 1607.75

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

*****
FLOW PROCESS FROM NODE 13660.00 TO NODE 13680.00 IS CODE = 12
-----
>>>>CLEAR MEMORY BANK # 3 <<<<<
=====
*****
FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 39.28
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.074
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp      Ap      SCS
LAND USE            GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN
USER-DEFINED        -         5.29    0.30    1.000    -
USER-DEFINED        -        31.25    0.30    1.000    -
USER-DEFINED        -         0.22    0.30    1.000    -
USER-DEFINED        -         6.26    0.30    1.000    -
USER-DEFINED        -         0.07    0.30    1.000    -
USER-DEFINED        -         0.22    0.30    1.000    -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 43.31      SUBAREA RUNOFF(CFS) = 30.18
EFFECTIVE AREA(ACRES) = 2257.77  AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30  AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 3515.4      PEAK FLOW RATE(CFS) = 1619.86

*****
FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 39.28
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.074
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp      Ap      SCS
LAND USE            GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN
USER-DEFINED        -         2.47    0.30    0.850    -
USER-DEFINED        -         3.06    0.30    0.850    -
USER-DEFINED        -        17.76    0.30    0.500    -
USER-DEFINED        -         7.31    0.30    0.500    -
USER-DEFINED        -         0.34    0.30    1.000    -
USER-DEFINED        -         8.22    0.30    1.000    -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.659
SUBAREA AREA(ACRES) = 39.16      SUBAREA RUNOFF(CFS) = 30.89
EFFECTIVE AREA(ACRES) = 2296.93  AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30  AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 3554.6      PEAK FLOW RATE(CFS) = 1650.76

*****
FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

```

```

=====
MAINLINE Tc(MIN.) = 39.28
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.074
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp      Ap      SCS
LAND USE            GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN
USER-DEFINED        -         0.53    0.30    1.000    -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 0.53      SUBAREA RUNOFF(CFS) = 0.37
EFFECTIVE AREA(ACRES) = 2297.46  AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30  AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 3555.1      PEAK FLOW RATE(CFS) = 1651.13

*****
FLOW PROCESS FROM NODE 13680.00 TO NODE 13682.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 288.00  DOWNSTREAM(FEET) = 242.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 2860.77  CHANNEL SLOPE = 0.0161
GIVEN CHANNEL BASE(FEET) = 30.00  CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000  MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 3.99
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.013
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp      Ap      SCS
LAND USE            GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN
USER-DEFINED        -         0.22    0.30    1.000    -
USER-DEFINED        -         5.28    0.30    1.000    -
USER-DEFINED        -         0.52    0.30    1.000    -
USER-DEFINED        -         3.61    0.30    1.000    -
USER-DEFINED        -         0.67    0.30    1.000    -
USER-DEFINED        -         1.37    0.30    1.000    -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1654.87
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.87
AVERAGE FLOW DEPTH(FEET) = 3.99  TRAVEL TIME(MIN.) = 4.83
Tc(MIN.) = 44.11
SUBAREA AREA(ACRES) = 11.67      SUBAREA RUNOFF(CFS) = 7.49
EFFECTIVE AREA(ACRES) = 2309.13  AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30  AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 3566.8      PEAK FLOW RATE(CFS) = 1651.13
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 30.00  CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000  MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 3.99

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 3.99  FLOW VELOCITY(FEET/SEC.) = 9.87
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13682.00 = 37051.30 FEET.

*****
FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

```

```

=====
MAINLINE Tc(MIN.) = 44.11
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.013
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS
LAND USE            GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED        -         6.90   0.30   1.000   -
USER-DEFINED        -        23.04   0.30   1.000   -
USER-DEFINED        -         1.18   0.30   1.000   -
USER-DEFINED        -         1.56   0.30   1.000   -
USER-DEFINED        -        53.20   0.30   1.000   -
USER-DEFINED        -         2.08   0.30   1.000   -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 87.96   SUBAREA RUNOFF(CFS) = 56.44
EFFECTIVE AREA(ACRES) = 2397.09   AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30   AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 3654.7   PEAK FLOW RATE(CFS) = 1651.13
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
-----

```

```

=====
MAINLINE Tc(MIN.) = 44.11
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.013
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS
LAND USE            GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED        -         0.01   0.30   1.000   -
USER-DEFINED        -         0.18   0.30   1.000   -
USER-DEFINED        -         0.38   0.30   1.000   -
USER-DEFINED        -         0.22   0.30   1.000   -
USER-DEFINED        -         7.73   0.30   1.000   -
USER-DEFINED        -         4.37   0.30   1.000   -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 12.89   SUBAREA RUNOFF(CFS) = 8.27
EFFECTIVE AREA(ACRES) = 2409.98   AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30   AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 3667.6   PEAK FLOW RATE(CFS) = 1651.13
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
-----

```

```

=====
MAINLINE Tc(MIN.) = 44.11
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.013
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS
LAND USE            GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
AGRICULTURAL POOR COVER
"FALLOW"           B         2.57   0.30   1.000   86
AGRICULTURAL POOR COVER
"FALLOW"           B         1.97   0.30   1.000   86

```

```

NATURAL FAIR COVER
"GRASS"           B         1.00   0.30   1.000   69
NATURAL FAIR COVER
"GRASS"           B         2.98   0.30   1.000   69
NATURAL FAIR COVER
"OPEN BRUSH"      B         2.39   0.30   1.000   66
NATURAL FAIR COVER
"OPEN BRUSH"      B         1.67   0.30   1.000   66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 12.58   SUBAREA RUNOFF(CFS) = 8.07
EFFECTIVE AREA(ACRES) = 2422.56   AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30   AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 3680.2   PEAK FLOW RATE(CFS) = 1651.13
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
-----

```

```

=====
MAINLINE Tc(MIN.) = 44.11
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.013
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS
LAND USE            GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"OPEN BRUSH"      B         0.44   0.30   1.000   66
PUBLIC PARK        B         2.65   0.30   0.850   56
PUBLIC PARK        B         1.16   0.30   0.850   56
RESIDENTIAL
"5-7 DWELLINGS/ACRE" B         0.47   0.30   0.500   56
RESIDENTIAL
"5-7 DWELLINGS/ACRE" B         0.25   0.30   0.500   56
AGRICULTURAL POOR COVER
"ROW CROPS,STRAIGHT ROW" B        20.24   0.30   1.000   81
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.963
SUBAREA AREA(ACRES) = 25.21   SUBAREA RUNOFF(CFS) = 16.43
EFFECTIVE AREA(ACRES) = 2447.77   AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30   AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 3705.4   PEAK FLOW RATE(CFS) = 1651.13
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
-----

```

```

=====
MAINLINE Tc(MIN.) = 44.11
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.013
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS
LAND USE            GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED        -         7.08   0.30   1.000   -
USER-DEFINED        -         6.75   0.30   1.000   -
USER-DEFINED        -         0.02   0.30   1.000   -
USER-DEFINED        -         0.93   0.30   1.000   -

```

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 14.78 SUBAREA RUNOFF(CFS) = 9.48
 EFFECTIVE AREA(ACRES) = 2462.55 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA(ACRES) = 3720.2 PEAK FLOW RATE(CFS) = 1651.13
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13682.00 TO NODE 13683.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 242.00 DOWNSTREAM(FEET) = 208.53
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2526.22 CHANNEL SLOPE = 0.0132
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 4.22
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.960

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.49	0.30	1.000	-
USER-DEFINED	-	13.31	0.30	1.000	-
USER-DEFINED	-	0.87	0.30	1.000	-
USER-DEFINED	-	20.26	0.30	1.000	-
USER-DEFINED	-	1.21	0.30	1.000	-
USER-DEFINED	-	0.05	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1664.24
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.24
 AVERAGE FLOW DEPTH(FEET) = 4.22 TRAVEL TIME(MIN.) = 4.56
 Tc(MIN.) = 48.67
 SUBAREA AREA(ACRES) = 44.19 SUBAREA RUNOFF(CFS) = 26.24
 EFFECTIVE AREA(ACRES) = 2506.74 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 3764.4 PEAK FLOW RATE(CFS) = 1651.13
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 4.20

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 4.20 FLOW VELOCITY(FEET/SEC.) = 9.23
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13683.00 = 39577.52 FEET.

 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 48.67
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.960
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL					
"5-7 DWELLINGS/ACRE"	B	0.10	0.30	0.500	56
CONDOMINIUMS	B	0.10	0.30	0.350	56
PUBLIC PARK	B	6.90	0.30	0.850	56
PUBLIC PARK	B	0.40	0.30	0.850	56

USER-DEFINED - 12.56 0.30 1.000 -
 USER-DEFINED - 0.81 0.30 1.000 -
 USER-DEFINED - 0.01 0.30 1.000 -
 USER-DEFINED - 1.11 0.30 1.000 -
 USER-DEFINED - 0.59 0.30 1.000 -
 USER-DEFINED - 3.04 0.30 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 18.12 SUBAREA RUNOFF(CFS) = 10.76
 EFFECTIVE AREA(ACRES) = 2524.86 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 3782.5 PEAK FLOW RATE(CFS) = 1651.13
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 48.67
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.960
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL					
"8-10 DWELLINGS/ACRE"	B	0.10	0.30	0.400	56
PUBLIC PARK	B	1.30	0.30	0.850	56
RESIDENTIAL					
"8-10 DWELLINGS/ACRE"	B	0.10	0.30	0.400	56
PUBLIC PARK	B	1.70	0.30	0.850	56
PUBLIC PARK	B	0.10	0.30	0.850	56
PUBLIC PARK	B	2.90	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.835
 SUBAREA AREA(ACRES) = 6.20 SUBAREA RUNOFF(CFS) = 3.96
 EFFECTIVE AREA(ACRES) = 2531.06 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 3788.7 PEAK FLOW RATE(CFS) = 1651.13
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 48.67
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.960
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL					
"5-7 DWELLINGS/ACRE"	B	0.10	0.30	0.500	56
CONDOMINIUMS	B	0.10	0.30	0.350	56
PUBLIC PARK	B	6.90	0.30	0.850	56
PUBLIC PARK	B	0.40	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.839
 SUBAREA AREA(ACRES) = 7.50 SUBAREA RUNOFF(CFS) = 4.78

EFFECTIVE AREA (ACRES) = 2538.56 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA (ACRES) = 3796.2 PEAK FLOW RATE (CFS) = 1651.13
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13682.00 TO NODE 13683.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

=====
MEMORY BANK # 3 IS EMPTY - PROCESS IGNORED.
=====

FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====
MAINLINE Tc (MIN.) = 48.67

* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.960

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "FALLOW"	B	2.55	0.30	1.000	86
AGRICULTURAL POOR COVER "FALLOW"	B	0.01	0.30	1.000	86
AGRICULTURAL POOR COVER "FALLOW"	B	1.35	0.30	1.000	86
NATURAL FAIR COVER "GRASS"	B	0.44	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	0.67	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	1.06	0.30	1.000	66

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 6.08 SUBAREA RUNOFF (CFS) = 3.61

EFFECTIVE AREA (ACRES) = 2544.64 AREA-AVERAGED Fm (INCH/HR) = 0.28

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA (ACRES) = 3802.3 PEAK FLOW RATE (CFS) = 1651.13

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====
MAINLINE Tc (MIN.) = 48.67

* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.960

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	2.16	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	2.45	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	6.15	0.30	1.000	66

AGRICULTURAL POOR COVER
"ROW CROPS, STRAIGHT ROW" B 1.34 0.30 1.000 81
AGRICULTURAL POOR COVER
"ROW CROPS, STRAIGHT ROW" B 18.46 0.30 1.000 81
AGRICULTURAL POOR COVER
"ROW CROPS, STRAIGHT ROW" B 4.13 0.30 1.000 81
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 34.69 SUBAREA RUNOFF (CFS) = 20.59
EFFECTIVE AREA (ACRES) = 2579.33 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA (ACRES) = 3837.0 PEAK FLOW RATE (CFS) = 1651.13
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====
MAINLINE Tc (MIN.) = 48.67

* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.960

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "ROW CROPS, STRAIGHT ROW"	B	8.69	0.30	1.000	81
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.73	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.41	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND, GRASS"	B	1.37	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND, GRASS"	B	3.11	0.30	1.000	65

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 14.31 SUBAREA RUNOFF (CFS) = 8.49

EFFECTIVE AREA (ACRES) = 2593.64 AREA-AVERAGED Fm (INCH/HR) = 0.28

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA (ACRES) = 3851.3 PEAK FLOW RATE (CFS) = 1651.13

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13683.00 TO NODE 13685.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====
ELEVATION DATA: UPSTREAM (FEET) = 208.53 DOWNSTREAM (FEET) = 194.24
CHANNEL LENGTH THRU SUBAREA (FEET) = 289.01 CHANNEL SLOPE = 0.0494
GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT (FEET) = 2.92
CHANNEL FLOW THRU SUBAREA (CFS) = 1651.13
FLOW VELOCITY (FEET/SEC.) = 14.56 FLOW DEPTH (FEET) = 2.92
TRAVEL TIME (MIN.) = 0.33 Tc (MIN.) = 49.00
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13685.00 = 39866.53 FEET.

FLOW PROCESS FROM NODE 13685.00 TO NODE 13410.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 194.24 DOWNSTREAM(FEET) = 178.72
CHANNEL LENGTH THRU SUBAREA(FEET) = 1843.57 CHANNEL SLOPE = 0.0084
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 4.75
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.918
SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include USER-DEFINED entries with various soil groups and area values.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1653.46
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.87
AVERAGE FLOW DEPTH(FEET) = 4.75 TRAVEL TIME(MIN.) = 3.91
Tc(MIN.) = 52.91
SUBAREA AREA(ACRES) = 8.39 SUBAREA RUNOFF(CFS) = 4.67
EFFECTIVE AREA(ACRES) = 2602.03 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 3859.7 PEAK FLOW RATE(CFS) = 1651.13
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 4.75

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 4.75 FLOW VELOCITY(FEET/SEC.) = 7.86
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13410.00 = 41710.10 FEET.

END OF STUDY SUMMARY:
TOTAL AREA(ACRES) = 3859.7 TC(MIN.) = 52.91
EFFECTIVE AREA(ACRES) = 2602.03 AREA-AVERAGED Fm(INCH/HR)= 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.927
PEAK FLOW RATE(CFS) = 1651.13

** PEAK FLOW RATE TABLE **

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 8 rows of data for different stream segments.

END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2010 Advanced Engineering Software (aes)
Ver. 17.0 Release Date: 07/01/2010 License ID 1527

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 137 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 10-YR EV AUG 2023 ROKAMOTO *

FILE NAME: RU10EV37.DAT
TIME/DATE OF STUDY: 23:36 08/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 10.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 3.709
- 2) 10.00; 2.481
- 3) 15.00; 1.848
- 4) 20.00; 1.580
- 5) 25.00; 1.381
- 6) 30.00; 1.243
- 7) 40.00; 1.060
- 8) 50.00; 0.942
- 9) 60.00; 0.854
- 10) 90.00; 0.706
- 11) 120.00; 0.620
- 12) 180.00; 0.519
- 13) 360.00; 0.379
- 14) 1200.00; 0.165

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU10EV34.DNA
MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15538.65	15.90	0.30 (0.24)	0.79	3924.6	300.00
2	18133.24	26.93	0.30 (0.24)	0.80	6882.1	50500.00
3	19770.21	34.96	0.30 (0.24)	0.80	9313.7	100.00
4	21809.94	45.86	0.30 (0.24)	0.81	13553.8	400.00
5	23056.35	59.73	0.30 (0.26)	0.85	19720.6	13600.00
6	24650.30	75.83	0.30 (0.26)	0.88	26736.2	13100.00
7	24994.96	82.53	0.30 (0.27)	0.89	29275.2	11801.00
8	26470.78	100.44	0.30 (0.27)	0.91	37829.7	13510.00
9	27204.30	107.73	0.30 (0.27)	0.92	41956.4	13010.00
10	27932.61	113.45	0.30 (0.28)	0.92	45494.1	11330.00
11	28532.27	121.55	0.30 (0.28)	0.93	50581.2	10630.00
12	28285.76	127.15	0.30 (0.28)	0.93	53171.1	12330.00
13	28029.24	133.79	0.30 (0.28)	0.94	56313.6	11600.00
14	27657.58	139.59	0.30 (0.28)	0.94	58547.9	11111.00
15	27241.92	145.76	0.30 (0.28)	0.94	60481.7	12201.00
16	26330.33	154.79	0.30 (0.28)	0.94	62570.0	12231.00
17	25494.59	162.36	0.30 (0.28)	0.94	63981.5	10400.00
18	24161.15	173.91	0.30 (0.28)	0.94	65602.3	10320.00
19	22896.14	183.79	0.30 (0.28)	0.94	65990.1	12000.00
20	19964.80	213.41	0.30 (0.28)	0.94	66607.1	10100.00
TOTAL AREA (ACRES) =						66607.1

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 14.0

>>>>MEMORY BANK # 3 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15538.65	15.90	0.30 (0.24)	0.79	3924.6	300.00
2	18133.24	26.93	0.30 (0.24)	0.80	6882.1	50500.00
3	19770.21	34.96	0.30 (0.24)	0.80	9313.7	100.00
4	21809.94	45.86	0.30 (0.24)	0.81	13553.8	400.00
5	23056.35	59.73	0.30 (0.26)	0.85	19720.6	13600.00
6	24650.30	75.83	0.30 (0.26)	0.88	26736.2	13100.00
7	24994.96	82.53	0.30 (0.27)	0.89	29275.2	11801.00
8	26470.78	100.44	0.30 (0.27)	0.91	37829.7	13510.00
9	27204.30	107.73	0.30 (0.27)	0.92	41956.4	13010.00
10	27932.61	113.45	0.30 (0.28)	0.92	45494.1	11330.00
11	28532.27	121.55	0.30 (0.28)	0.93	50581.2	10630.00
12	28285.76	127.15	0.30 (0.28)	0.93	53171.1	12330.00
13	28029.24	133.79	0.30 (0.28)	0.94	56313.6	11600.00

14 27657.58 139.59 0.30(0.28) 0.94 58547.9 11111.00
15 27241.92 145.76 0.30(0.28) 0.94 60481.7 12201.00
16 26330.33 154.79 0.30(0.28) 0.94 62570.0 12231.00
17 25494.59 162.36 0.30(0.28) 0.94 63981.5 10400.00
18 24161.15 173.91 0.30(0.28) 0.94 65602.3 10320.00
19 22896.14 183.79 0.30(0.28) 0.94 65990.1 12000.00
20 19964.80 213.41 0.30(0.28) 0.94 66607.1 10100.00
TOTAL AREA (ACRES) = 66607.1

FLOW PROCESS FROM NODE 13700.00 TO NODE 13720.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 170.00 DOWNSTREAM(FEET) = 165.51
CHANNEL LENGTH THRU SUBAREA(FEET) = 1891.83 CHANNEL SLOPE = 0.0024
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 10.85
CHANNEL FLOW THRU SUBAREA(CFS) = 28532.27
FLOW VELOCITY(FEET/SEC.) = 10.35 FLOW DEPTH(FEET) = 10.85
TRAVEL TIME(MIN.) = 3.05 Tc(MIN.) = 124.60
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126441.05 FEET.

FLOW PROCESS FROM NODE 13700.00 TO NODE 13720.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

FLOW PROCESS FROM NODE 13720.00 TO NODE 13720.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506102E.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm)	Ap	Ae (ACRES)	HEADWATER NODE
1	239.83	16.06	1.791	0.30(0.29)	0.96	193.8	10230.00
2	217.18	25.14	1.377	0.30(0.29)	0.95	240.5	10250.00
3	216.13	25.45	1.369	0.30(0.29)	0.95	241.8	10200.00
4	200.96	29.41	1.259	0.30(0.29)	0.95	246.3	10220.00

TOTAL AREA (ACRES) = 246.3

FLOW PROCESS FROM NODE 13720.00 TO NODE 13720.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm)	Ap	Ae (ACRES)	HEADWATER NODE
1	15538.65	19.62	1.600	0.30(0.24)	0.79	3924.6	300.00
2	18133.24	30.46	1.235	0.30(0.24)	0.80	6882.1	50500.00
3	19770.21	38.39	1.089	0.30(0.24)	0.80	9313.7	100.00

4 21809.94 49.18 0.952 0.30(0.24) 0.81 13553.8 400.00
5 23056.35 63.00 0.839 0.30(0.26) 0.85 19720.6 13600.00
6 24650.30 79.02 0.760 0.30(0.26) 0.88 26736.2 13100.00
7 24994.96 85.71 0.727 0.30(0.27) 0.89 29275.2 11801.00
8 26470.78 103.56 0.667 0.30(0.27) 0.91 37829.7 13510.00
9 27204.30 110.82 0.646 0.30(0.27) 0.92 41956.4 13010.00
10 27932.61 116.52 0.630 0.30(0.28) 0.92 45494.1 11330.00
11 28532.27 124.60 0.612 0.30(0.28) 0.93 50581.2 10630.00
12 28285.76 130.20 0.603 0.30(0.28) 0.93 53171.1 12330.00
13 28029.24 136.85 0.592 0.30(0.28) 0.94 56313.6 11600.00
14 27657.58 142.67 0.582 0.30(0.28) 0.94 58547.9 11111.00
15 27241.92 148.85 0.571 0.30(0.28) 0.94 60481.7 12201.00
16 26330.33 157.91 0.556 0.30(0.28) 0.94 62570.0 12231.00
17 25494.59 165.52 0.543 0.30(0.28) 0.94 63981.5 10400.00
18 24161.15 177.13 0.524 0.30(0.28) 0.94 65602.3 10320.00
19 22896.14 187.07 0.514 0.30(0.28) 0.94 65990.1 12000.00
20 19964.80 216.83 0.490 0.30(0.28) 0.94 66607.1 10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126441.05 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm)	Ap	Ae (ACRES)	HEADWATER NODE
1	239.83	16.06	1.791	0.30(0.29)	0.96	193.8	10230.00
2	217.18	25.14	1.377	0.30(0.29)	0.95	240.5	10250.00
3	216.13	25.45	1.369	0.30(0.29)	0.95	241.8	10200.00
4	200.96	29.41	1.259	0.30(0.29)	0.95	246.3	10220.00

LONGEST FLOWPATH FROM NODE 10200.00 TO NODE 13720.00 = 9099.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm)	Ap	Ae (ACRES)	HEADWATER NODE
1	14741.83	16.06	1.791	0.30(0.24)	0.80	3406.6	10230.00
2	15769.60	19.62	1.600	0.30(0.24)	0.80	4136.8	300.00
3	17077.51	25.14	1.377	0.30(0.24)	0.80	5671.7	10250.00
4	17150.55	25.45	1.369	0.30(0.24)	0.80	5757.4	10200.00
5	18083.66	29.41	1.259	0.30(0.24)	0.80	6842.8	10220.00
6	18329.12	30.46	1.235	0.30(0.24)	0.80	7128.4	50500.00
7	19936.10	38.39	1.089	0.30(0.24)	0.80	9560.0	100.00
8	21947.38	49.18	0.952	0.30(0.24)	0.81	13800.1	400.00
9	23170.58	63.00	0.839	0.30(0.26)	0.85	19966.9	13600.00
10	24748.20	79.02	0.760	0.30(0.26)	0.88	26982.5	13100.00
11	25086.05	85.71	0.727	0.30(0.27)	0.89	29521.4	11801.00
12	26549.47	103.56	0.667	0.30(0.27)	0.91	38076.0	13510.00
13	27278.70	110.82	0.646	0.30(0.27)	0.92	42202.7	13010.00
14	28003.63	116.52	0.630	0.30(0.28)	0.92	45740.3	11330.00
15	28599.63	124.60	0.612	0.30(0.28)	0.93	50827.5	10630.00
16	28351.17	130.20	0.603	0.30(0.28)	0.93	53417.4	12330.00
17	28092.34	136.85	0.592	0.30(0.28)	0.94	56559.8	11600.00
18	27718.66	142.67	0.582	0.30(0.28)	0.94	58794.1	11111.00
19	27300.85	148.85	0.571	0.30(0.28)	0.94	60728.0	12201.00
20	26386.11	157.91	0.556	0.30(0.28)	0.94	62816.2	12231.00
21	25547.72	165.52	0.543	0.30(0.28)	0.94	64227.8	10400.00
22	24210.25	177.13	0.524	0.30(0.28)	0.94	65848.5	10320.00
23	22943.11	187.07	0.514	0.30(0.28)	0.94	66236.4	12000.00
24	20006.99	216.83	0.490	0.30(0.28)	0.94	66853.4	10100.00

TOTAL AREA (ACRES) = 66853.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 28599.63 Tc(MIN.) = 124.600
EFFECTIVE AREA(ACRES) = 50827.50 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.89
TOTAL AREA(ACRES) = 66853.4
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126441.05 FEET.

FLOW PROCESS FROM NODE 13720.00 TO NODE 13740.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 165.51 DOWNSTREAM(FEET) = 161.03
CHANNEL LENGTH THRU SUBAREA(FEET) = 2067.54 CHANNEL SLOPE = 0.0022
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 11.14
CHANNEL FLOW THRU SUBAREA(CFS) = 28599.63
FLOW VELOCITY(FEET/SEC.) = 10.04 FLOW DEPTH(FEET) = 11.14
TRAVEL TIME(MIN.) = 3.43 Tc(MIN.) = 128.03
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128508.59 FEET.

FLOW PROCESS FROM NODE 13720.00 TO NODE 13740.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<

FLOW PROCESS FROM NODE 13740.00 TO NODE 13740.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<

PEAK FLOWRATE TABLE FILE NAME: 0506103E.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	489.59	19.32	0.30 (0.23)	0.76	401.6	10300.00
2	490.14	20.03	0.30 (0.23)	0.76	412.9	10380.00
3	480.40	22.78	0.30 (0.23)	0.76	441.7	10320.00
4	464.91	24.67	0.30 (0.23)	0.76	451.8	10360.00
5	436.74	27.62	0.30 (0.23)	0.76	460.8	10340.00
TOTAL AREA(ACRES) =					460.8	

FLOW PROCESS FROM NODE 13740.00 TO NODE 13740.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14741.83	20.33	1.567	0.30 (0.24)	0.80	3406.6	10230.00
2	15769.60	23.80	1.429	0.30 (0.24)	0.80	4136.8	300.00
3	17077.51	29.20	1.265	0.30 (0.24)	0.80	5671.7	10250.00
4	17150.55	29.51	1.257	0.30 (0.24)	0.80	5757.4	10200.00
5	18083.66	33.40	1.181	0.30 (0.24)	0.80	6842.8	10220.00

6	18329.12	34.42	1.162	0.30 (0.24)	0.80	7128.4	50500.00
7	19936.10	42.25	1.033	0.30 (0.24)	0.80	9560.0	100.00
8	21947.38	52.92	0.916	0.30 (0.24)	0.81	13800.1	400.00
9	23170.58	66.67	0.821	0.30 (0.26)	0.85	19966.9	13600.00
10	24748.20	82.62	0.742	0.30 (0.26)	0.88	26982.5	13100.00
11	25086.05	89.29	0.710	0.30 (0.27)	0.89	29521.4	11801.00
12	26549.47	107.08	0.657	0.30 (0.27)	0.91	38076.0	13510.00
13	27278.70	114.31	0.636	0.30 (0.27)	0.92	42202.7	13010.00
14	28003.63	119.98	0.620	0.30 (0.28)	0.92	45740.3	11330.00
15	28599.63	128.03	0.606	0.30 (0.28)	0.93	50827.5	10630.00
16	28351.17	133.65	0.597	0.30 (0.28)	0.93	53417.4	12330.00
17	28092.34	140.30	0.586	0.30 (0.28)	0.94	56559.8	11600.00
18	27718.66	146.14	0.576	0.30 (0.28)	0.94	58794.1	11111.00
19	27300.85	152.33	0.566	0.30 (0.28)	0.94	60728.0	12201.00
20	26386.11	161.44	0.550	0.30 (0.28)	0.94	62816.2	12231.00
21	25547.72	169.07	0.537	0.30 (0.28)	0.94	64227.8	10400.00
22	24210.25	180.75	0.518	0.30 (0.28)	0.94	65848.5	10320.00
23	22943.11	190.75	0.511	0.30 (0.28)	0.94	66236.4	12000.00
24	20006.99	220.69	0.487	0.30 (0.28)	0.94	66853.4	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128508.59 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	489.59	19.32	1.617	0.30 (0.23)	0.76	401.6	10300.00
2	490.14	20.03	1.579	0.30 (0.23)	0.76	412.9	10380.00
3	480.40	22.78	1.469	0.30 (0.23)	0.76	441.7	10320.00
4	464.91	24.67	1.394	0.30 (0.23)	0.76	451.8	10360.00
5	436.74	27.62	1.309	0.30 (0.23)	0.76	460.8	10340.00

LONGEST FLOWPATH FROM NODE 10320.00 TO NODE 13740.00 = 8457.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15022.58	19.32	1.617	0.30 (0.24)	0.80	3638.5	10300.00
2	15146.16	20.03	1.579	0.30 (0.24)	0.80	3769.7	10380.00
3	15230.92	20.33	1.567	0.30 (0.24)	0.80	3822.6	10230.00
4	15948.58	22.78	1.469	0.30 (0.24)	0.80	4364.3	10320.00
5	16241.67	23.80	1.429	0.30 (0.24)	0.80	4583.9	300.00
6	16445.85	24.67	1.394	0.30 (0.24)	0.80	4836.6	10360.00
7	17131.28	27.62	1.309	0.30 (0.24)	0.80	5683.0	10340.00
8	17496.57	29.20	1.265	0.30 (0.24)	0.80	6132.5	10250.00
9	17566.21	29.51	1.257	0.30 (0.24)	0.80	6218.2	10200.00
10	18468.69	33.40	1.181	0.30 (0.24)	0.80	7303.6	10220.00
11	18706.54	34.42	1.162	0.30 (0.24)	0.80	7589.2	50500.00
12	20261.49	42.25	1.033	0.30 (0.24)	0.80	10020.8	100.00
13	22225.39	52.92	0.916	0.30 (0.24)	0.81	14260.9	400.00
14	23410.07	66.67	0.821	0.30 (0.26)	0.85	20427.7	13600.00
15	24955.87	82.62	0.742	0.30 (0.26)	0.88	27443.3	13100.00
16	25280.41	89.29	0.710	0.30 (0.27)	0.89	29982.2	11801.00
17	26722.61	107.08	0.657	0.30 (0.27)	0.91	38536.8	13510.00
18	27443.45	114.31	0.636	0.30 (0.27)	0.91	42663.5	13010.00
19	28161.81	119.98	0.620	0.30 (0.28)	0.92	46201.1	11330.00
20	28752.31	128.03	0.606	0.30 (0.28)	0.93	51288.3	10630.00
21	28500.03	133.65	0.597	0.30 (0.28)	0.93	53878.2	12330.00
22	28236.67	140.30	0.586	0.30 (0.28)	0.93	57020.6	11600.00
23	27859.01	146.14	0.576	0.30 (0.28)	0.94	59254.9	11111.00
24	27436.98	152.33	0.566	0.30 (0.28)	0.94	61188.8	12201.00

25 26516.05 161.44 0.550 0.30(0.28) 0.94 63277.0 12231.00
26 25672.46 169.07 0.537 0.30(0.28) 0.94 64688.6 10400.00
27 24327.31 180.75 0.518 0.30(0.28) 0.94 66309.3 10320.00
28 23057.02 190.75 0.511 0.30(0.28) 0.94 66697.2 12000.00
29 20111.48 220.69 0.487 0.30(0.28) 0.94 67314.2 10100.00
TOTAL AREA (ACRES) = 67314.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 28752.31 Tc(MIN.) = 128.033
EFFECTIVE AREA(ACRES) = 51288.30 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.88
TOTAL AREA (ACRES) = 67314.2
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128508.59 FEET.

FLOW PROCESS FROM NODE 13740.00 TO NODE 13741.00 IS CODE = 56

=====
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<
=====

ELEVATION DATA: UPSTREAM(FEET) = 161.03 DOWNSTREAM(FEET) = 141.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 364.08 CHANNEL SLOPE = 0.0550
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 6.46
CHANNEL FLOW THRU SUBAREA(CFS) = 28752.31
FLOW VELOCITY(FEET/SEC.) = 35.34 FLOW DEPTH(FEET) = 6.46
TRAVEL TIME(MIN.) = 0.17 Tc(MIN.) = 128.20
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128872.66 FEET.

FLOW PROCESS FROM NODE 13740.00 TO NODE 13741.00 IS CODE = 12

=====
>>>>CLEAR MEMORY BANK # 3 <<<<<
=====

FLOW PROCESS FROM NODE 13741.00 TO NODE 13741.00 IS CODE = 15.1

=====
>>>>DEFINE MEMORY BANK # 3 <<<<<
=====

PEAK FLOWRATE TABLE FILE NAME: 0506104E.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	49.20	20.74	0.30(0.24)	0.80	44.3	10400.00
TOTAL AREA(ACRES) = 44.3						

FLOW PROCESS FROM NODE 13741.00 TO NODE 13741.00 IS CODE = 11

=====
>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<
=====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15022.58	19.53	1.605	0.30(0.24)	0.80	3638.5	10300.00

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
2	15146.16	20.24	1.570	0.30(0.24)	0.80	3769.7	10380.00
3	15230.92	20.54	1.558	0.30(0.24)	0.80	3822.6	10230.00
4	15948.58	22.99	1.461	0.30(0.24)	0.80	4364.3	10320.00
5	16241.67	24.00	1.421	0.30(0.24)	0.80	4583.9	300.00
6	16445.85	24.88	1.386	0.30(0.24)	0.80	4836.6	10360.00
7	17131.28	27.82	1.303	0.30(0.24)	0.80	5683.0	10340.00
8	17496.57	29.41	1.259	0.30(0.24)	0.80	6132.5	10250.00
9	17566.21	29.71	1.251	0.30(0.24)	0.80	6218.2	10200.00
10	18468.69	33.59	1.177	0.30(0.24)	0.80	7303.6	10220.00
11	18706.54	34.62	1.158	0.30(0.24)	0.80	7589.2	50500.00
12	20261.49	42.44	1.031	0.30(0.24)	0.80	10020.8	100.00
13	22225.39	53.11	0.915	0.30(0.24)	0.81	14260.9	400.00
14	23410.07	66.86	0.820	0.30(0.26)	0.85	20427.7	13600.00
15	24955.87	82.80	0.742	0.30(0.26)	0.88	27443.3	13100.00
16	25280.41	89.47	0.709	0.30(0.27)	0.89	29982.2	11801.00
17	26722.61	107.25	0.657	0.30(0.27)	0.91	38536.8	13510.00
18	27443.45	114.48	0.636	0.30(0.27)	0.91	42663.5	13010.00
19	28161.81	120.15	0.620	0.30(0.28)	0.92	46201.1	11330.00
20	28752.31	128.20	0.606	0.30(0.28)	0.93	51288.3	10630.00
21	28500.03	133.82	0.597	0.30(0.28)	0.93	53878.2	12330.00
22	28236.67	140.48	0.586	0.30(0.28)	0.93	57020.6	11600.00
23	27859.01	146.31	0.576	0.30(0.28)	0.94	59254.9	11111.00
24	27436.98	152.51	0.565	0.30(0.28)	0.94	61188.8	12201.00
25	26516.05	161.61	0.550	0.30(0.28)	0.94	63277.0	12231.00
26	25672.46	169.25	0.537	0.30(0.28)	0.94	64688.6	10400.00
27	24327.31	180.93	0.518	0.30(0.28)	0.94	66309.3	10320.00
28	23057.02	190.94	0.510	0.30(0.28)	0.94	66697.2	12000.00
29	20111.48	220.88	0.487	0.30(0.28)	0.94	67314.2	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128872.66 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	49.20	20.74	1.551	0.30(0.24)	0.80	44.3	10400.00

LONGEST FLOWPATH FROM NODE 10400.00 TO NODE 13741.00 = 6237.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15070.85	19.53	1.605	0.30(0.24)	0.80	3680.3	10300.00
2	15194.91	20.24	1.570	0.30(0.24)	0.80	3813.0	10380.00
3	15279.95	20.54	1.558	0.30(0.24)	0.80	3866.5	10230.00
4	15336.96	20.74	1.551	0.30(0.24)	0.80	3909.8	10400.00
5	15994.41	22.99	1.461	0.30(0.24)	0.80	4408.6	10320.00
6	16285.99	24.00	1.421	0.30(0.24)	0.80	4628.2	300.00
7	16488.87	24.88	1.386	0.30(0.24)	0.80	4880.9	10360.00
8	17171.19	27.82	1.303	0.30(0.24)	0.80	5727.3	10340.00
9	17534.84	29.41	1.259	0.30(0.24)	0.80	6176.8	10250.00
10	17604.16	29.71	1.251	0.30(0.24)	0.80	6262.5	10200.00
11	18503.88	33.59	1.177	0.30(0.24)	0.80	7347.9	10220.00
12	18741.02	34.62	1.158	0.30(0.24)	0.80	7633.5	50500.00
13	20291.19	42.44	1.031	0.30(0.24)	0.80	10065.1	100.00
14	22250.72	53.11	0.915	0.30(0.24)	0.81	14305.2	400.00
15	23431.86	66.86	0.820	0.30(0.26)	0.85	20472.0	13600.00
16	24974.71	82.80	0.742	0.30(0.26)	0.88	27487.6	13100.00
17	25298.01	89.47	0.709	0.30(0.27)	0.89	30026.5	11801.00
18	26738.26	107.25	0.657	0.30(0.27)	0.91	38581.1	13510.00
19	27458.32	114.48	0.636	0.30(0.27)	0.91	42707.8	13010.00

20 28176.08 120.15 0.620 0.30(0.28) 0.92 46245.4 11330.00
21 28766.07 128.20 0.606 0.30(0.28) 0.93 51332.6 10630.00
22 28513.44 133.82 0.597 0.30(0.28) 0.93 53922.5 12330.00
23 28249.65 140.48 0.586 0.30(0.28) 0.93 57064.9 11600.00
24 27871.63 146.31 0.576 0.30(0.28) 0.94 59299.2 11111.00
25 27449.20 152.51 0.565 0.30(0.28) 0.94 61233.1 12201.00
26 26527.70 161.61 0.550 0.30(0.28) 0.94 63321.3 12231.00
27 25683.63 169.25 0.537 0.30(0.28) 0.94 64732.9 10400.00
28 24337.77 180.93 0.518 0.30(0.28) 0.94 66353.6 10320.00
29 23067.19 190.94 0.510 0.30(0.28) 0.94 66741.5 12000.00
30 20120.77 220.88 0.487 0.30(0.28) 0.94 67358.5 10100.00
TOTAL AREA (ACRES) = 67358.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
PEAK FLOW RATE (CFS) = 28766.07 Tc (MIN.) = 128.205
EFFECTIVE AREA (ACRES) = 51332.60 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA (ACRES) = 67358.5
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128872.66 FEET.

FLOW PROCESS FROM NODE 13741.00 TO NODE 13802.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 141.00 DOWNSTREAM (FEET) = 135.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 1533.41 CHANNEL SLOPE = 0.0039
GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 13.30
CHANNEL FLOW THRU SUBAREA (CFS) = 28766.07
FLOW VELOCITY (FEET/SEC.) = 14.11 FLOW DEPTH (FEET) = 13.30
TRAVEL TIME (MIN.) = 1.81 Tc (MIN.) = 130.02
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130406.07 FEET.

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<

PEAK FLOWRATE TABLE FILE NAME: 0506105L.DNA
MEMORY BANK # 3 DEFINED AS FOLLOWS:
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 263.73 15.21 1.837 0.30(0.27) 0.90 203.7 10520.00
2 303.03 33.18 1.185 0.30(0.28) 0.93 403.6 10500.00
TOTAL AREA (ACRES) = 403.6

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 11

>>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<<

** MAIN STREAM CONFLUENCE DATA **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 15070.85 21.72 1.511 0.30(0.24) 0.80 3680.3 10300.00
2 15194.91 22.43 1.483 0.30(0.24) 0.80 3813.0 10380.00
3 15279.95 22.73 1.472 0.30(0.24) 0.80 3866.5 10230.00
4 15336.96 22.92 1.464 0.30(0.24) 0.80 3909.8 10400.00
5 15994.41 25.14 1.377 0.30(0.24) 0.80 4408.6 10320.00
6 16285.99 26.15 1.349 0.30(0.24) 0.80 4628.2 300.00
7 16488.87 27.01 1.325 0.30(0.24) 0.80 4880.9 10360.00
8 17171.19 29.93 1.245 0.30(0.24) 0.80 5727.3 10340.00
9 17534.84 31.50 1.216 0.30(0.24) 0.80 6176.8 10250.00
10 17604.16 31.80 1.210 0.30(0.24) 0.80 6262.5 10200.00
11 18503.88 35.66 1.139 0.30(0.24) 0.80 7347.9 10220.00
12 18741.02 36.68 1.121 0.30(0.24) 0.80 7633.5 50500.00
13 20291.19 44.45 1.007 0.30(0.24) 0.80 10065.1 100.00
14 22250.72 55.06 0.897 0.30(0.24) 0.81 14305.2 400.00
15 23431.86 68.78 0.811 0.30(0.26) 0.85 20472.0 13600.00
16 24974.71 84.69 0.732 0.30(0.26) 0.88 27487.6 13100.00
17 25298.01 91.35 0.702 0.30(0.27) 0.89 30026.5 11801.00
18 26738.26 109.10 0.651 0.30(0.27) 0.91 38581.1 13510.00
19 27458.32 116.32 0.631 0.30(0.27) 0.91 42707.8 13010.00
20 28176.08 121.97 0.617 0.30(0.28) 0.92 46245.4 11330.00
21 28766.07 130.02 0.603 0.30(0.28) 0.93 51332.6 10630.00
22 28513.44 135.63 0.594 0.30(0.28) 0.93 53922.5 12330.00
23 28249.65 142.30 0.582 0.30(0.28) 0.93 57064.9 11600.00
24 27871.63 148.14 0.573 0.30(0.28) 0.94 59299.2 11111.00
25 27449.20 154.35 0.562 0.30(0.28) 0.94 61233.1 12201.00
26 26527.70 163.47 0.547 0.30(0.28) 0.94 63321.3 12231.00
27 25683.63 171.12 0.534 0.30(0.28) 0.94 64732.9 10400.00
28 24337.77 182.83 0.517 0.30(0.28) 0.94 66353.6 10320.00
29 23067.19 192.87 0.509 0.30(0.28) 0.94 66741.5 12000.00
30 20120.77 222.89 0.486 0.30(0.28) 0.94 67358.5 10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130406.07 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 263.73 15.21 1.837 0.30(0.27) 0.90 203.7 10520.00
2 303.03 33.18 1.185 0.30(0.28) 0.93 403.6 10500.00
LONGEST FLOWPATH FROM NODE 10500.00 TO NODE 13802.00 = 12187.00 FEET.

** PEAK FLOW RATE TABLE **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 13515.46 15.21 1.837 0.30(0.24) 0.81 2780.7 10520.00
2 15348.82 21.72 1.511 0.30(0.24) 0.81 3956.4 10300.00
3 15474.44 22.43 1.483 0.30(0.24) 0.81 4097.0 10380.00
4 15560.11 22.73 1.472 0.30(0.24) 0.81 4153.8 10230.00
5 15617.54 22.92 1.464 0.30(0.24) 0.81 4199.2 10400.00
6 16279.86 25.14 1.377 0.30(0.24) 0.81 4722.8 10320.00
7 16573.63 26.15 1.349 0.30(0.24) 0.81 4953.5 300.00
8 16778.41 27.01 1.325 0.30(0.24) 0.81 5215.8 10360.00
9 17467.11 29.93 1.245 0.30(0.24) 0.81 6094.8 10340.00
10 17834.19 31.50 1.216 0.30(0.24) 0.81 6561.7 10250.00

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
11	17904.18	31.80	1.210	0.30 (0.24)	0.81	6650.7	10200.00
12	18229.36	33.18	1.185	0.30 (0.24)	0.81	7054.7	10500.00
13	18791.78	35.66	1.139	0.30 (0.24)	0.81	7751.5	10220.00
14	19022.68	36.68	1.121	0.30 (0.24)	0.81	8037.1	50500.00
15	20534.98	44.45	1.007	0.30 (0.24)	0.80	10468.7	100.00
16	22457.74	55.06	0.897	0.30 (0.24)	0.81	14708.8	400.00
17	23609.88	68.78	0.811	0.30 (0.26)	0.85	20875.6	13600.00
18	25126.50	84.69	0.732	0.30 (0.26)	0.88	27891.2	13100.00
19	25439.75	91.35	0.702	0.30 (0.27)	0.89	30430.1	11801.00
20	26862.99	109.10	0.651	0.30 (0.27)	0.91	38984.7	13510.00
21	27576.15	116.32	0.631	0.30 (0.27)	0.91	43111.4	13010.00
22	28289.26	121.97	0.617	0.30 (0.28)	0.92	46649.0	11330.00
23	28874.73	130.02	0.603	0.30 (0.28)	0.93	51736.2	10630.00
24	28618.94	135.63	0.594	0.30 (0.28)	0.93	54326.1	12330.00
25	28351.40	142.30	0.582	0.30 (0.28)	0.93	57468.5	11600.00
26	27970.09	148.14	0.573	0.30 (0.28)	0.94	59702.8	11111.00
27	27544.18	154.35	0.562	0.30 (0.28)	0.94	61636.7	12201.00
28	26617.54	163.47	0.547	0.30 (0.28)	0.94	63724.9	12231.00
29	25769.16	171.12	0.534	0.30 (0.28)	0.94	65136.5	10400.00
30	24417.58	182.83	0.517	0.30 (0.28)	0.94	66757.2	10320.00
31	23144.38	192.87	0.509	0.30 (0.28)	0.94	67145.1	12000.00
32	20190.17	222.89	0.486	0.30 (0.28)	0.94	67762.1	10100.00

TOTAL AREA (ACRES) = 67762.1

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
PEAK FLOW RATE (CFS) = 28874.73 Tc (MIN.) = 130.016
EFFECTIVE AREA (ACRES) = 51736.20 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.91
TOTAL AREA (ACRES) = 67762.1
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130406.07 FEET.

FLOW PROCESS FROM NODE 13802.00 TO NODE 13803.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 135.00 DOWNSTREAM (FEET) = 134.99
CHANNEL LENGTH THRU SUBAREA (FEET) = 207.23 CHANNEL SLOPE = 0.0000
GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 39.35
CHANNEL FLOW THRU SUBAREA (CFS) = 28874.73
FLOW VELOCITY (FEET/SEC.) = 2.85 FLOW DEPTH (FEET) = 39.35
TRAVEL TIME (MIN.) = 1.21 Tc (MIN.) = 131.23
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130613.30 FEET.

FLOW PROCESS FROM NODE 13802.00 TO NODE 13803.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506106E.DNA
MEMORY BANK # 3 DEFINED AS FOLLOWS:
STREAM Q Tc Fp (Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 45.15 18.06 0.30 (0.20) 0.67 36.9 10600.00
TOTAL AREA (ACRES) = 36.9

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13515.46	16.69	1.757	0.30 (0.24)	0.81	2780.7	10520.00
2	15348.82	23.15	1.454	0.30 (0.24)	0.81	3956.4	10300.00
3	15474.44	23.86	1.426	0.30 (0.24)	0.81	4097.0	10380.00
4	15560.11	24.15	1.415	0.30 (0.24)	0.81	4153.8	10230.00
5	15617.54	24.34	1.407	0.30 (0.24)	0.81	4199.2	10400.00
6	16279.86	26.55	1.338	0.30 (0.24)	0.81	4722.8	10320.00
7	16573.63	27.55	1.311	0.30 (0.24)	0.81	4953.5	300.00
8	16778.41	28.41	1.287	0.30 (0.24)	0.81	5215.8	10360.00
9	17467.11	31.31	1.219	0.30 (0.24)	0.81	6094.8	10340.00
10	17834.19	32.88	1.190	0.30 (0.24)	0.81	6561.7	10250.00
11	17904.18	33.18	1.185	0.30 (0.24)	0.81	6650.7	10200.00
12	18229.36	34.55	1.160	0.30 (0.24)	0.81	7054.7	10500.00
13	18791.78	37.01	1.115	0.30 (0.24)	0.81	7751.5	10220.00
14	19022.68	38.03	1.096	0.30 (0.24)	0.81	8037.1	50500.00
15	20534.98	45.77	0.992	0.30 (0.24)	0.80	10468.7	100.00
16	22457.74	56.35	0.886	0.30 (0.24)	0.81	14708.8	400.00
17	23609.88	70.06	0.804	0.30 (0.26)	0.85	20875.6	13600.00
18	25126.50	85.94	0.726	0.30 (0.26)	0.88	27891.2	13100.00
19	25439.75	92.60	0.699	0.30 (0.27)	0.89	30430.1	11801.00
20	26862.99	110.34	0.648	0.30 (0.27)	0.91	38984.7	13510.00
21	27576.15	117.54	0.627	0.30 (0.27)	0.91	43111.4	13010.00
22	28289.26	123.19	0.615	0.30 (0.28)	0.92	46649.0	11330.00
23	28874.73	131.23	0.601	0.30 (0.28)	0.93	51736.2	10630.00
24	28618.94	136.85	0.592	0.30 (0.28)	0.93	54326.1	12330.00
25	28351.40	143.51	0.580	0.30 (0.28)	0.93	57468.5	11600.00
26	27970.09	149.36	0.571	0.30 (0.28)	0.94	59702.8	11111.00
27	27544.18	155.57	0.560	0.30 (0.28)	0.94	61636.7	12201.00
28	26617.54	164.70	0.545	0.30 (0.28)	0.94	63724.9	12231.00
29	25769.16	172.37	0.532	0.30 (0.28)	0.94	65136.5	10400.00
30	24417.58	184.10	0.516	0.30 (0.28)	0.94	66757.2	10320.00
31	23144.38	194.15	0.508	0.30 (0.28)	0.94	67145.1	12000.00
32	20190.17	224.22	0.485	0.30 (0.28)	0.94	67762.1	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130613.30 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **
STREAM Q Tc Intensity Fp (Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 45.15 18.06 1.684 0.30 (0.20) 0.67 36.9 10600.00
LONGEST FLOWPATH FROM NODE 10600.00 TO NODE 13803.00 = 1713.00 FEET.

** PEAK FLOW RATE TABLE **
STREAM Q Tc Intensity Fp (Fm) Ap Ae HEADWATER

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	13559.25	16.69	1.757	0.30 (0.24)	0.80	2814.8 10520.00
2	13950.44	18.06	1.684	0.30 (0.24)	0.80	3067.6 10600.00
3	15386.99	23.15	1.454	0.30 (0.24)	0.81	3993.3 10300.00
4	15511.75	23.86	1.426	0.30 (0.24)	0.81	4133.9 10380.00
5	15597.08	24.15	1.415	0.30 (0.24)	0.81	4190.7 10230.00
6	15654.27	24.34	1.407	0.30 (0.24)	0.81	4236.1 10400.00
7	16314.49	26.55	1.338	0.30 (0.24)	0.81	4759.7 10320.00
8	16607.42	27.55	1.311	0.30 (0.24)	0.81	4990.4 300.00
9	16811.48	28.41	1.287	0.30 (0.24)	0.81	5252.7 10360.00
10	17498.11	31.31	1.219	0.30 (0.24)	0.81	6131.7 10340.00
11	17864.32	32.88	1.190	0.30 (0.24)	0.81	6598.6 10250.00
12	17934.14	33.18	1.185	0.30 (0.24)	0.81	6687.6 10200.00
13	18258.55	34.55	1.160	0.30 (0.24)	0.81	7091.6 10500.00
14	18819.61	37.01	1.115	0.30 (0.24)	0.81	7788.4 10220.00
15	19049.94	38.03	1.096	0.30 (0.24)	0.81	8074.0 50500.00
16	20559.07	45.77	0.992	0.30 (0.24)	0.80	10505.6 100.00
17	22478.60	56.35	0.886	0.30 (0.24)	0.81	14745.7 400.00
18	23628.26	70.06	0.804	0.30 (0.26)	0.85	20912.5 13600.00
19	25142.49	85.94	0.726	0.30 (0.26)	0.88	27928.1 13100.00
20	25454.91	92.60	0.699	0.30 (0.27)	0.89	30467.0 11801.00
21	26876.59	110.34	0.648	0.30 (0.27)	0.91	39021.6 13510.00
22	27589.12	117.54	0.627	0.30 (0.27)	0.91	43148.3 13010.00
23	28301.86	123.19	0.615	0.30 (0.28)	0.92	46685.9 11330.00
24	28886.91	131.23	0.601	0.30 (0.28)	0.93	51773.1 10630.00
25	28630.83	136.85	0.592	0.30 (0.28)	0.93	54363.0 12330.00
26	28362.96	143.51	0.580	0.30 (0.28)	0.93	57505.4 11600.00
27	27981.35	149.36	0.571	0.30 (0.28)	0.94	59739.7 11111.00
28	27555.11	155.57	0.560	0.30 (0.28)	0.94	61673.6 12201.00
29	26628.01	164.70	0.545	0.30 (0.28)	0.94	63761.8 12231.00
30	25779.24	172.37	0.532	0.30 (0.28)	0.94	65173.4 10400.00
31	24427.17	184.10	0.516	0.30 (0.28)	0.94	66794.1 10320.00
32	23153.73	194.15	0.508	0.30 (0.28)	0.94	67182.0 12000.00
33	20198.80	224.22	0.485	0.30 (0.28)	0.94	67799.0 10100.00
TOTAL AREA (ACRES) = 67799.0						

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 28886.91 Tc (MIN.) = 131.227
EFFECTIVE AREA (ACRES) = 51773.10 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA (ACRES) = 67799.0
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130613.30 FEET.

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 67799.0 TC (MIN.) = 131.23
EFFECTIVE AREA (ACRES) = 51773.10 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.928
PEAK FLOW RATE (CFS) = 28886.91

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13559.25	16.69	1.757	0.30 (0.24)	0.80	2814.8	10520.00
2	13950.44	18.06	1.684	0.30 (0.24)	0.80	3067.6	10600.00
3	15386.99	23.15	1.454	0.30 (0.24)	0.81	3993.3	10300.00
4	15511.75	23.86	1.426	0.30 (0.24)	0.81	4133.9	10380.00
5	15597.08	24.15	1.415	0.30 (0.24)	0.81	4190.7	10230.00
6	15654.27	24.34	1.407	0.30 (0.24)	0.81	4236.1	10400.00

7	16314.49	26.55	1.338	0.30 (0.24)	0.81	4759.7	10320.00
8	16607.42	27.55	1.311	0.30 (0.24)	0.81	4990.4	300.00
9	16811.48	28.41	1.287	0.30 (0.24)	0.81	5252.7	10360.00
10	17498.11	31.31	1.219	0.30 (0.24)	0.81	6131.7	10340.00
11	17864.32	32.88	1.190	0.30 (0.24)	0.81	6598.6	10250.00
12	17934.14	33.18	1.185	0.30 (0.24)	0.81	6687.6	10200.00
13	18258.55	34.55	1.160	0.30 (0.24)	0.81	7091.6	10500.00
14	18819.61	37.01	1.115	0.30 (0.24)	0.81	7788.4	10220.00
15	19049.94	38.03	1.096	0.30 (0.24)	0.81	8074.0	50500.00
16	20559.07	45.77	0.992	0.30 (0.24)	0.80	10505.6	100.00
17	22478.60	56.35	0.886	0.30 (0.24)	0.81	14745.7	400.00
18	23628.26	70.06	0.804	0.30 (0.26)	0.85	20912.5	13600.00
19	25142.49	85.94	0.726	0.30 (0.26)	0.88	27928.1	13100.00
20	25454.91	92.60	0.699	0.30 (0.27)	0.89	30467.0	11801.00
21	26876.59	110.34	0.648	0.30 (0.27)	0.91	39021.6	13510.00
22	27589.12	117.54	0.627	0.30 (0.27)	0.91	43148.3	13010.00
23	28301.86	123.19	0.615	0.30 (0.28)	0.92	46685.9	11330.00
24	28886.91	131.23	0.601	0.30 (0.28)	0.93	51773.1	10630.00
25	28630.83	136.85	0.592	0.30 (0.28)	0.93	54363.0	12330.00
26	28362.96	143.51	0.580	0.30 (0.28)	0.93	57505.4	11600.00
27	27981.35	149.36	0.571	0.30 (0.28)	0.94	59739.7	11111.00
28	27555.11	155.57	0.560	0.30 (0.28)	0.94	61673.6	12201.00
29	26628.01	164.70	0.545	0.30 (0.28)	0.94	63761.8	12231.00
30	25779.24	172.37	0.532	0.30 (0.28)	0.94	65173.4	10400.00
31	24427.17	184.10	0.516	0.30 (0.28)	0.94	66794.1	10320.00
32	23153.73	194.15	0.508	0.30 (0.28)	0.94	67182.0	12000.00
33	20198.80	224.22	0.485	0.30 (0.28)	0.94	67799.0	10100.00

=====
END OF RATIONAL METHOD ANALYSIS
=====

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2010 Advanced Engineering Software (aes)
Ver. 17.0 Release Date: 07/01/2010 License ID 1527

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 138 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 10-YR EV AUG 2023 ROKAMOTO *

FILE NAME: RU10EV38.DAT
TIME/DATE OF STUDY: 23:37 08/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 10.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 3.698
- 2) 10.00; 2.475
- 3) 15.00; 1.846
- 4) 20.00; 1.578
- 5) 25.00; 1.379
- 6) 30.00; 1.242
- 7) 40.00; 1.059
- 8) 50.00; 0.941
- 9) 60.00; 0.852
- 10) 90.00; 0.704
- 11) 120.00; 0.619
- 12) 180.00; 0.517
- 13) 360.00; 0.378
- 14) 1200.00; 0.165

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU10EV37.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13950.44	18.06	0.30 (0.24)	0.80	3067.6	10600.00
2	15654.27	24.34	0.30 (0.24)	0.81	4236.1	10400.00
3	19049.94	38.03	0.30 (0.24)	0.81	8074.0	50500.00
4	20559.07	45.77	0.30 (0.24)	0.80	10505.6	100.00
5	22478.60	56.35	0.30 (0.24)	0.81	14745.7	400.00
6	23628.26	70.06	0.30 (0.26)	0.85	20912.5	13600.00
7	25142.49	85.94	0.30 (0.26)	0.88	27928.1	13100.00
8	25454.91	92.60	0.30 (0.27)	0.89	30467.0	11801.00
9	26876.59	110.34	0.30 (0.27)	0.91	39021.6	13510.00
10	28301.86	123.19	0.30 (0.28)	0.92	46685.9	11330.00
11	28886.91	131.23	0.30 (0.28)	0.93	51773.1	10630.00
12	28630.83	136.85	0.30 (0.28)	0.93	54363.0	12330.00
13	28362.96	143.51	0.30 (0.28)	0.93	57505.4	11600.00
14	27981.35	149.36	0.30 (0.28)	0.94	59739.7	11111.00
15	27555.11	155.57	0.30 (0.28)	0.94	61673.6	12201.00
16	26628.01	164.70	0.30 (0.28)	0.94	63761.8	12231.00
17	25779.24	172.37	0.30 (0.28)	0.94	65173.4	10400.00
18	24427.17	184.10	0.30 (0.28)	0.94	66794.1	10320.00
19	23153.73	194.15	0.30 (0.28)	0.94	67182.0	12000.00
20	20198.80	224.22	0.30 (0.28)	0.94	67799.0	10100.00
TOTAL AREA (ACRES) =						67799.0

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13950.44	18.06	0.30 (0.24)	0.80	3067.6	10600.00
2	15654.27	24.34	0.30 (0.24)	0.81	4236.1	10400.00
3	19049.94	38.03	0.30 (0.24)	0.81	8074.0	50500.00
4	20559.07	45.77	0.30 (0.24)	0.80	10505.6	100.00
5	22478.60	56.35	0.30 (0.24)	0.81	14745.7	400.00
6	23628.26	70.06	0.30 (0.26)	0.85	20912.5	13600.00
7	25142.49	85.94	0.30 (0.26)	0.88	27928.1	13100.00
8	25454.91	92.60	0.30 (0.27)	0.89	30467.0	11801.00
9	26876.59	110.34	0.30 (0.27)	0.91	39021.6	13510.00
10	28301.86	123.19	0.30 (0.28)	0.92	46685.9	11330.00
11	28886.91	131.23	0.30 (0.28)	0.93	51773.1	10630.00
12	28630.83	136.85	0.30 (0.28)	0.93	54363.0	12330.00
13	28362.96	143.51	0.30 (0.28)	0.93	57505.4	11600.00

14 27981.35 149.36 0.30(0.28) 0.94 59739.7 11111.00
 15 27555.11 155.57 0.30(0.28) 0.94 61673.6 12201.00
 16 26628.01 164.70 0.30(0.28) 0.94 63761.8 12231.00
 17 25779.24 172.37 0.30(0.28) 0.94 65173.4 10400.00
 18 24427.17 184.10 0.30(0.28) 0.94 66794.1 10320.00
 19 23153.73 194.15 0.30(0.28) 0.94 67182.0 12000.00
 20 20198.80 224.22 0.30(0.28) 0.94 67799.0 10100.00
 TOTAL AREA (ACRES) = 67799.0

FLOW PROCESS FROM NODE 13803.00 TO NODE 13820.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 134.99 DOWNSTREAM(FEET) = 134.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 926.91 CHANNEL SLOPE = 0.0011
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT(FEET) = 18.65

* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.597

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	31.44	0.30	0.983	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.983

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 28891.19

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.87

AVERAGE FLOW DEPTH(FEET) = 18.65 TRAVEL TIME(MIN.) = 1.74

Tc(MIN.) = 132.97

SUBAREA AREA(ACRES) = 31.44 SUBAREA RUNOFF(CFS) = 8.55

EFFECTIVE AREA(ACRES) = 51804.54 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA(ACRES) = 67830.4 PEAK FLOW RATE(CFS) = 28886.91

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT(FEET) = 18.65

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 18.65 FLOW VELOCITY(FEET/SEC.) = 8.87

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13820.00 = 131540.20 FEET.

FLOW PROCESS FROM NODE 13803.00 TO NODE 13820.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

TOTAL NUMBER OF STREAMS = 2

CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:

TIME OF CONCENTRATION(MIN.) = 132.97

RAINFALL INTENSITY(INCH/HR) = 0.60

AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.93

EFFECTIVE STREAM AREA(ACRES) = 51804.54

TOTAL STREAM AREA(ACRES) = 67830.41

PEAK FLOW RATE(CFS) AT CONFLUENCE = 28886.91

FLOW PROCESS FROM NODE 13810.00 TO NODE 13811.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<

>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH(FEET) = 648.54

ELEVATION DATA: UPSTREAM(FEET) = 756.46 DOWNSTREAM(FEET) = 586.02

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20

SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 12.293

* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.187

SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	-	5.58	0.30	1.000	65	12.29

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

SUBAREA RUNOFF(CFS) = 9.47

TOTAL AREA(ACRES) = 5.58 PEAK FLOW RATE(CFS) = 9.47

FLOW PROCESS FROM NODE 13811.00 TO NODE 13811.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 586.02 DOWNSTREAM(FEET) = 437.69
 CHANNEL LENGTH THRU SUBAREA(FEET) = 696.28 CHANNEL SLOPE = 0.2130
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 0.37

* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.914

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	14.79	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 20.28

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.35

AVERAGE FLOW DEPTH(FEET) = 0.35 TRAVEL TIME(MIN.) = 2.17

Tc(MIN.) = 14.46

SUBAREA AREA(ACRES) = 14.79 SUBAREA RUNOFF(CFS) = 21.48

EFFECTIVE AREA(ACRES) = 20.37 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 20.4 PEAK FLOW RATE(CFS) = 29.59

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 0.44

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.44 FLOW VELOCITY(FEET/SEC.) = 6.19

LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13811.50 = 1344.82 FEET.

```

*****
FLOW PROCESS FROM NODE 13811.50 TO NODE 13812.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 437.69 DOWNSTREAM(FEET) = 402.36
CHANNEL LENGTH THRU SUBAREA(FEET) = 681.04 CHANNEL SLOPE = 0.0519
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.83
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.737
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp        Ap   SCS
LAND USE           GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED       -         18.41     0.30     1.000   -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 41.51
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.40
AVERAGE FLOW DEPTH(FEET) = 0.81 TRAVEL TIME(MIN.) = 2.58
Tc(MIN.) = 17.04
SUBAREA AREA(ACRES) = 18.41 SUBAREA RUNOFF(CFS) = 23.81
EFFECTIVE AREA(ACRES) = 38.78 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 38.8 PEAK FLOW RATE(CFS) = 50.14
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.90

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.90 FLOW VELOCITY(FEET/SEC.) = 4.70
LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13812.00 = 2025.86 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13812.00 TO NODE 13813.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 402.36 DOWNSTREAM(FEET) = 259.72
CHANNEL LENGTH THRU SUBAREA(FEET) = 1282.56 CHANNEL SLOPE = 0.1112
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.86
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.568
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp        Ap   SCS
LAND USE           GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED       -         27.87     0.30     0.858   -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.858
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 66.60
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.68
AVERAGE FLOW DEPTH(FEET) = 0.85 TRAVEL TIME(MIN.) = 3.20
Tc(MIN.) = 20.24
SUBAREA AREA(ACRES) = 27.87 SUBAREA RUNOFF(CFS) = 32.89
EFFECTIVE AREA(ACRES) = 66.65 AREA-AVERAGED Fm(INCH/HR) = 0.28

```

```

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94
TOTAL AREA(ACRES) = 66.7 PEAK FLOW RATE(CFS) = 77.16
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.93

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.93 FLOW VELOCITY(FEET/SEC.) = 7.01
LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13813.00 = 3308.42 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 31
-----

```

```

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 259.72 DOWNSTREAM(FEET) = 137.00
FLOW LENGTH(FEET) = 2412.88 MANNING'S N = 0.013
ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000
DEPTH OF FLOW IN 36.0 INCH PIPE IS 18.9 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 20.58
ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 77.16
PIPE TRAVEL TIME(MIN.) = 1.95 Tc(MIN.) = 22.19
LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13820.00 = 5721.30 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 22.19
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.491
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp        Ap   SCS
LAND USE           GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED       -         83.64     0.30     0.570   -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.570
SUBAREA AREA(ACRES) = 83.64 SUBAREA RUNOFF(CFS) = 99.35
EFFECTIVE AREA(ACRES) = 150.29 AREA-AVERAGED Fm(INCH/HR) = 0.22
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.73
TOTAL AREA(ACRES) = 150.3 PEAK FLOW RATE(CFS) = 171.84

```

```

*****
FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 1
-----

```

```

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<
=====
TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 22.19
RAINFALL INTENSITY(INCH/HR) = 1.49
AREA-AVERAGED Fm(INCH/HR) = 0.22
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.73
EFFECTIVE STREAM AREA(ACRES) = 150.29

```

TOTAL STREAM AREA(ACRES) = 150.29
PEAK FLOW RATE(CFS) AT CONFLUENCE = 171.84

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13950.44	20.21	1.570	0.30 (0.24)	0.81	3099.1	10600.00
1	15654.27	26.41	1.340	0.30 (0.24)	0.81	4267.6	10400.00
1	19049.94	39.98	1.059	0.30 (0.24)	0.81	8105.4	50500.00
1	20559.07	47.69	0.968	0.30 (0.24)	0.80	10537.0	100.00
1	22478.60	58.22	0.868	0.30 (0.24)	0.81	14777.1	400.00
1	23628.26	71.90	0.793	0.30 (0.26)	0.85	20943.9	13600.00
1	25142.49	87.75	0.715	0.30 (0.26)	0.88	27959.5	13100.00
1	25454.91	94.40	0.692	0.30 (0.27)	0.89	30498.5	11801.00
1	26876.59	112.11	0.641	0.30 (0.27)	0.91	39053.0	13510.00
1	28301.86	124.94	0.611	0.30 (0.28)	0.92	46717.4	11330.00
1	28886.91	132.97	0.597	0.30 (0.28)	0.93	51804.5	10630.00
1	28630.83	138.59	0.587	0.30 (0.28)	0.93	54394.4	12330.00
1	28362.96	145.26	0.576	0.30 (0.28)	0.93	57536.9	11600.00
1	27981.35	151.12	0.566	0.30 (0.28)	0.94	59771.2	11111.00
1	27555.11	157.34	0.556	0.30 (0.28)	0.94	61705.0	12201.00
1	26628.01	166.49	0.540	0.30 (0.28)	0.94	63793.3	12231.00
1	25779.24	174.17	0.527	0.30 (0.28)	0.94	65204.8	10400.00
1	24427.17	185.92	0.512	0.30 (0.28)	0.94	66825.6	10320.00
1	23153.73	196.00	0.505	0.30 (0.28)	0.94	67213.4	12000.00
1	20198.80	226.15	0.481	0.30 (0.28)	0.94	67830.4	10100.00
2	171.84	22.19	1.491	0.30 (0.22)	0.73	150.3	13810.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14116.63	20.21	1.570	0.30 (0.24)	0.80	3235.9	10600.00
2	14668.10	22.19	1.491	0.30 (0.24)	0.80	3623.7	13810.00
3	15805.78	26.41	1.340	0.30 (0.24)	0.80	4417.8	10400.00
4	19163.43	39.98	1.059	0.30 (0.24)	0.80	8255.7	50500.00
5	20660.25	47.69	0.968	0.30 (0.24)	0.80	10687.3	100.00
6	22566.20	58.22	0.868	0.30 (0.24)	0.81	14927.4	400.00
7	23705.77	71.90	0.793	0.30 (0.26)	0.85	21094.2	13600.00
8	25209.42	87.75	0.715	0.30 (0.26)	0.88	28109.8	13100.00
9	25518.65	94.40	0.692	0.30 (0.27)	0.89	30648.7	11801.00
10	26933.55	112.11	0.641	0.30 (0.27)	0.91	39203.3	13510.00
11	28354.66	124.94	0.611	0.30 (0.28)	0.92	46867.7	11330.00
12	28937.87	132.97	0.597	0.30 (0.28)	0.93	51954.8	10630.00
13	28680.49	138.59	0.587	0.30 (0.28)	0.93	54544.7	12330.00
14	28411.08	145.26	0.576	0.30 (0.28)	0.93	57687.1	11600.00
15	28028.12	151.12	0.566	0.30 (0.28)	0.94	59921.5	11111.00
16	27600.46	157.34	0.556	0.30 (0.28)	0.94	61855.3	12201.00
17	26671.25	166.49	0.540	0.30 (0.28)	0.94	63943.6	12231.00
18	25820.71	174.17	0.527	0.30 (0.28)	0.94	65355.1	10400.00
19	24466.69	185.92	0.512	0.30 (0.28)	0.94	66975.9	10320.00
20	23192.20	196.00	0.505	0.30 (0.28)	0.94	67363.7	12000.00
21	20234.12	226.15	0.481	0.30 (0.28)	0.94	67980.7	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 28937.87 Tc(MIN.) = 132.97

EFFECTIVE AREA(ACRES) = 51954.83 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 67980.7
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13820.00 = 131540.20 FEET.

FLOW PROCESS FROM NODE 13820.00 TO NODE 13840.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 137.00 DOWNSTREAM(FEET) = 133.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 1261.34 CHANNEL SLOPE = 0.0032

GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT(FEET) = 14.10

* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.594

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

USER-DEFINED - 31.60 0.30 0.683 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.683

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 28943.40

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 13.12

AVERAGE FLOW DEPTH(FEET) = 14.10 TRAVEL TIME(MIN.) = 1.60

Tc(MIN.) = 134.57

SUBAREA AREA(ACRES) = 31.60 SUBAREA RUNOFF(CFS) = 11.07

EFFECTIVE AREA(ACRES) = 51986.43 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA(ACRES) = 68012.3 PEAK FLOW RATE(CFS) = 28937.87

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT(FEET) = 14.10

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 14.10 FLOW VELOCITY(FEET/SEC.) = 13.12

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13840.00 = 132801.55 FEET.

FLOW PROCESS FROM NODE 13820.00 TO NODE 13840.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

TOTAL NUMBER OF STREAMS = 2

CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:

TIME OF CONCENTRATION(MIN.) = 134.57

RAINFALL INTENSITY(INCH/HR) = 0.59

AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.93

EFFECTIVE STREAM AREA(ACRES) = 51986.43

TOTAL STREAM AREA(ACRES) = 68012.30

PEAK FLOW RATE(CFS) AT CONFLUENCE = 28937.87

FLOW PROCESS FROM NODE 13830.00 TO NODE 13831.00 IS CODE = 21

```

-----
>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<
=====
INITIAL SUBAREA FLOW-LENGTH (FEET) = 744.71
ELEVATION DATA: UPSTREAM (FEET) = 1100.95 DOWNSTREAM (FEET) = 959.21

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 13.858
* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.990
SUBAREA Tc AND LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)
NATURAL FAIR COVER
"CHAPARRAL, BROADLEAF" - 5.06 0.30 1.000 65 13.86
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF (CFS) = 7.70
TOTAL AREA (ACRES) = 5.06 PEAK FLOW RATE (CFS) = 7.70

```

```

*****
FLOW PROCESS FROM NODE 13831.00 TO NODE 13832.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<
=====

```

```

ELEVATION DATA: UPSTREAM (FEET) = 959.21 DOWNSTREAM (FEET) = 832.83
CHANNEL LENGTH THRU SUBAREA (FEET) = 1076.71 CHANNEL SLOPE = 0.1174
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.55
* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.716
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 32.57 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 28.59
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.04
AVERAGE FLOW DEPTH (FEET) = 0.51 TRAVEL TIME (MIN.) = 3.56
Tc (MIN.) = 17.42
SUBAREA AREA (ACRES) = 32.57 SUBAREA RUNOFF (CFS) = 41.52
EFFECTIVE AREA (ACRES) = 37.63 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 37.6 PEAK FLOW RATE (CFS) = 47.97
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.70

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.70 FLOW VELOCITY (FEET/SEC.) = 6.04
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13832.00 = 1821.42 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13832.00 TO NODE 13833.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

```

```

>>>>TRAVELTIME THRU SUBAREA<<<<<
=====

```

```

ELEVATION DATA: UPSTREAM (FEET) = 832.83 DOWNSTREAM (FEET) = 572.49
CHANNEL LENGTH THRU SUBAREA (FEET) = 1883.58 CHANNEL SLOPE = 0.1382
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.81
* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.505
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 32.23 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 65.50
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.10
AVERAGE FLOW DEPTH (FEET) = 0.80 TRAVEL TIME (MIN.) = 4.42
Tc (MIN.) = 21.84
SUBAREA AREA (ACRES) = 32.23 SUBAREA RUNOFF (CFS) = 34.95
EFFECTIVE AREA (ACRES) = 69.86 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 69.9 PEAK FLOW RATE (CFS) = 75.75
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.86

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.86 FLOW VELOCITY (FEET/SEC.) = 7.47
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13833.00 = 3705.00 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13833.00 TO NODE 13834.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<
=====

```

```

ELEVATION DATA: UPSTREAM (FEET) = 572.49 DOWNSTREAM (FEET) = 471.65
CHANNEL LENGTH THRU SUBAREA (FEET) = 943.78 CHANNEL SLOPE = 0.1068
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 1.03
* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.418
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 27.51 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 89.60
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.25
AVERAGE FLOW DEPTH (FEET) = 1.03 TRAVEL TIME (MIN.) = 2.17
Tc (MIN.) = 24.01
SUBAREA AREA (ACRES) = 27.51 SUBAREA RUNOFF (CFS) = 27.69
EFFECTIVE AREA (ACRES) = 97.37 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 97.4 PEAK FLOW RATE (CFS) = 98.02
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

```

*ESTIMATED CHANNEL HEIGHT (FEET) = 1.08
END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 1.08 FLOW VELOCITY (FEET/SEC.) = 7.46
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13834.00 = 4648.78 FEET.

FLOW PROCESS FROM NODE 13834.00 TO NODE 13835.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 471.65 DOWNSTREAM (FEET) = 347.06
CHANNEL LENGTH THRU SUBAREA (FEET) = 1647.45 CHANNEL SLOPE = 0.0756
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT (FEET) = 1.49
* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.305

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	94.21	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 140.67

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.45

AVERAGE FLOW DEPTH (FEET) = 1.46 TRAVEL TIME (MIN.) = 3.69

Tc (MIN.) = 27.70

SUBAREA AREA (ACRES) = 94.21 SUBAREA RUNOFF (CFS) = 85.23

EFFECTIVE AREA (ACRES) = 191.58 AREA-AVERAGED Fm (INCH/HR) = 0.30

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.000

TOTAL AREA (ACRES) = 191.6 PEAK FLOW RATE (CFS) = 173.31

GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT (FEET) = 1.64

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 1.64 FLOW VELOCITY (FEET/SEC.) = 7.94

LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13835.00 = 6296.23 FEET.

FLOW PROCESS FROM NODE 13835.00 TO NODE 13836.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 347.06 DOWNSTREAM (FEET) = 269.29
CHANNEL LENGTH THRU SUBAREA (FEET) = 1696.71 CHANNEL SLOPE = 0.0458
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT (FEET) = 2.44

* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.216

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	233.25	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 269.53
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.59
AVERAGE FLOW DEPTH (FEET) = 2.40 TRAVEL TIME (MIN.) = 3.72
Tc (MIN.) = 31.42
SUBAREA AREA (ACRES) = 233.25 SUBAREA RUNOFF (CFS) = 192.31
EFFECTIVE AREA (ACRES) = 424.83 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.000
TOTAL AREA (ACRES) = 424.8 PEAK FLOW RATE (CFS) = 350.25
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 2.76

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 2.76 FLOW VELOCITY (FEET/SEC.) = 8.18

LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13836.00 = 7992.94 FEET.

FLOW PROCESS FROM NODE 13836.00 TO NODE 13837.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 269.29 DOWNSTREAM (FEET) = 191.87
CHANNEL LENGTH THRU SUBAREA (FEET) = 2529.21 CHANNEL SLOPE = 0.0306
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT (FEET) = 3.31

* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.111

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	134.70	0.30	0.880	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.880

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 401.61

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.35

AVERAGE FLOW DEPTH (FEET) = 3.29 TRAVEL TIME (MIN.) = 5.73

Tc (MIN.) = 37.15

SUBAREA AREA (ACRES) = 134.70 SUBAREA RUNOFF (CFS) = 102.70

EFFECTIVE AREA (ACRES) = 559.53 AREA-AVERAGED Fm (INCH/HR) = 0.29

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97

TOTAL AREA (ACRES) = 559.5 PEAK FLOW RATE (CFS) = 412.84

GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT (FEET) = 3.34

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 3.34 FLOW VELOCITY (FEET/SEC.) = 7.41

LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13837.00 = 10522.15 FEET.

FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 191.87 DOWNSTREAM (FEET) = 133.00
FLOW LENGTH (FEET) = 1151.02 MANNING'S N = 0.013

DEPTH OF FLOW IN 54.0 INCH PIPE IS 43.2 INCHES
 PIPE-FLOW VELOCITY (FEET/SEC.) = 30.24
 ESTIMATED PIPE DIAMETER (INCH) = 54.00 NUMBER OF PIPES = 1
 PIPE-FLOW (CFS) = 412.84
 PIPE TRAVEL TIME (MIN.) = 0.63 Tc (MIN.) = 37.79
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13840.00 = 11673.17 FEET.

 FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 37.79
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.099
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.97	0.30	0.622	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.622
 SUBAREA AREA (ACRES) = 5.97 SUBAREA RUNOFF (CFS) = 4.91
 EFFECTIVE AREA (ACRES) = 565.50 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA (ACRES) = 565.5 PEAK FLOW RATE (CFS) = 412.84
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
 TIME OF CONCENTRATION (MIN.) = 37.79
 RAINFALL INTENSITY (INCH/HR) = 1.10
 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.97
 EFFECTIVE STREAM AREA (ACRES) = 565.50
 TOTAL STREAM AREA (ACRES) = 565.50
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 412.84

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14116.63	22.19	1.491	0.30 (0.24)	0.80	3267.5	10600.00
1	14668.10	24.15	1.413	0.30 (0.24)	0.80	3655.3	13810.00
1	15805.78	28.32	1.288	0.30 (0.24)	0.80	4449.4	10400.00
1	19163.43	41.79	1.038	0.30 (0.24)	0.80	8287.3	50500.00
1	20660.25	49.46	0.947	0.30 (0.24)	0.80	10718.9	100.00
1	22566.20	59.94	0.853	0.30 (0.24)	0.81	14959.0	400.00
1	23705.77	73.59	0.785	0.30 (0.26)	0.85	21125.8	13600.00
1	25209.42	89.42	0.707	0.30 (0.26)	0.88	28141.4	13100.00
1	25518.65	96.07	0.687	0.30 (0.27)	0.89	30680.3	11801.00
1	26933.55	113.75	0.637	0.30 (0.27)	0.91	39234.9	13510.00
1	28354.66	126.55	0.608	0.30 (0.28)	0.92	46899.3	11330.00
1	28937.87	134.57	0.594	0.30 (0.28)	0.93	51986.4	10630.00

1	28680.49	140.20	0.585	0.30 (0.28)	0.93	54576.3	12330.00
1	28411.08	146.87	0.573	0.30 (0.28)	0.93	57718.8	11600.00
1	28028.12	152.74	0.563	0.30 (0.28)	0.94	59953.1	11111.00
1	27600.46	158.96	0.553	0.30 (0.28)	0.94	61886.9	12201.00
1	26671.25	168.13	0.537	0.30 (0.28)	0.94	63975.2	12231.00
1	25820.71	175.83	0.524	0.30 (0.28)	0.94	65386.7	10400.00
1	24466.69	187.60	0.511	0.30 (0.28)	0.94	67007.5	10320.00
1	23192.20	197.71	0.503	0.30 (0.28)	0.94	67395.3	12000.00
1	20234.12	227.92	0.480	0.30 (0.28)	0.94	68012.3	10100.00
2	412.84	37.79	1.099	0.30 (0.29)	0.97	565.5	13830.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14476.28	22.19	1.491	0.30 (0.25)	0.82	3599.5	10600.00
2	15034.09	24.15	1.413	0.30 (0.25)	0.82	4016.7	13810.00
3	16187.28	28.32	1.288	0.30 (0.25)	0.82	4873.3	10400.00
4	18578.17	37.79	1.099	0.30 (0.24)	0.82	7712.0	13830.00
5	19544.84	41.79	1.038	0.30 (0.24)	0.81	8852.8	50500.00
6	20995.52	49.46	0.947	0.30 (0.24)	0.81	11284.4	100.00
7	22853.05	59.94	0.853	0.30 (0.25)	0.82	15524.5	400.00
8	23958.16	73.59	0.785	0.30 (0.26)	0.86	21691.3	13600.00
9	25421.99	89.42	0.707	0.30 (0.26)	0.88	28706.9	13100.00
10	25720.99	96.07	0.687	0.30 (0.27)	0.89	31245.8	11801.00
11	27110.33	113.75	0.637	0.30 (0.27)	0.91	39800.4	13510.00
12	28516.72	126.55	0.608	0.30 (0.28)	0.92	47464.8	11330.00
13	29092.97	134.57	0.594	0.30 (0.28)	0.93	52551.9	10630.00
14	28830.72	140.20	0.585	0.30 (0.28)	0.93	55141.8	12330.00
15	28555.53	146.87	0.573	0.30 (0.28)	0.93	58284.2	11600.00
16	28167.48	152.74	0.563	0.30 (0.28)	0.94	60518.6	11111.00
17	27734.42	158.96	0.553	0.30 (0.28)	0.94	62452.4	12201.00
18	26797.26	168.13	0.537	0.30 (0.28)	0.94	64540.7	12231.00
19	25940.05	175.83	0.524	0.30 (0.28)	0.94	65952.2	10400.00
20	24579.40	187.60	0.511	0.30 (0.28)	0.94	67573.0	10320.00
21	23300.94	197.71	0.503	0.30 (0.28)	0.94	67960.8	12000.00
22	20330.96	227.92	0.480	0.30 (0.28)	0.94	68577.8	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 29092.97 Tc (MIN.) = 134.57
 EFFECTIVE AREA (ACRES) = 52551.93 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA (ACRES) = 68577.8
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13840.00 = 132801.55 FEET.

 FLOW PROCESS FROM NODE 13840.00 TO NODE 13860.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 133.00 DOWNSTREAM (FEET) = 130.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 654.44 CHANNEL SLOPE = 0.0046
 GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT (FEET) = 12.84

* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.593
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 6.61 0.30 0.975 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.975
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 29093.87
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 14.98
 AVERAGE FLOW DEPTH (FEET) = 12.84 TRAVEL TIME (MIN.) = 0.73
 Tc (MIN.) = 135.30
 SUBAREA AREA (ACRES) = 6.61 SUBAREA RUNOFF (CFS) = 1.79
 EFFECTIVE AREA (ACRES) = 52558.54 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA (ACRES) = 68584.4 PEAK FLOW RATE (CFS) = 29092.97
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT (FEET) = 12.84

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 12.84 FLOW VELOCITY (FEET/SEC.) = 14.98
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13860.00 = 133455.98 FEET.

 FLOW PROCESS FROM NODE 13840.00 TO NODE 13860.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

=====

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
 TIME OF CONCENTRATION (MIN.) = 135.30
 RAINFALL INTENSITY (INCH/HR) = 0.59
 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.93
 EFFECTIVE STREAM AREA (ACRES) = 52558.54
 TOTAL STREAM AREA (ACRES) = 68584.41
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 29092.97

 FLOW PROCESS FROM NODE 13850.00 TO NODE 13851.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH (FEET) = 617.57
 ELEVATION DATA: UPSTREAM (FEET) = 646.95 DOWNSTREAM (FEET) = 490.10

Tc = K * [(LENGTH ** 3.00) / (ELEVATION CHANGE)] ** 0.20
 SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 12.137
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 2.206
 SUBAREA Tc AND LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)
 NATURAL FAIR COVER
 "CHAPARRAL, BROADLEAF" - 4.95 0.30 1.000 65 12.14
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA RUNOFF (CFS) = 8.49
 TOTAL AREA (ACRES) = 4.95 PEAK FLOW RATE (CFS) = 8.49

 FLOW PROCESS FROM NODE 13851.00 TO NODE 13851.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 490.10 DOWNSTREAM (FEET) = 440.98
 CHANNEL LENGTH THRU SUBAREA (FEET) = 351.14 CHANNEL SLOPE = 0.1399
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 0.29
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 2.015

SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 4.02 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 11.59
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 3.85
 AVERAGE FLOW DEPTH (FEET) = 0.29 TRAVEL TIME (MIN.) = 1.52
 Tc (MIN.) = 13.66

SUBAREA AREA (ACRES) = 4.02 SUBAREA RUNOFF (CFS) = 6.20
 EFFECTIVE AREA (ACRES) = 8.97 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 9.0 PEAK FLOW RATE (CFS) = 13.84
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 0.32

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 0.32 FLOW VELOCITY (FEET/SEC.) = 4.10
 LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13851.50 = 968.71 FEET.

 FLOW PROCESS FROM NODE 13851.50 TO NODE 13852.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 440.98 DOWNSTREAM (FEET) = 395.76
 CHANNEL LENGTH THRU SUBAREA (FEET) = 512.91 CHANNEL SLOPE = 0.0882
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 0.45
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.803

SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 7.17 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 18.69
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 3.98

AVERAGE FLOW DEPTH (FEET) = 0.43 TRAVEL TIME (MIN.) = 2.15
Tc (MIN.) = 15.80
SUBAREA AREA (ACRES) = 7.17 SUBAREA RUNOFF (CFS) = 9.70
EFFECTIVE AREA (ACRES) = 16.14 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 16.1 PEAK FLOW RATE (CFS) = 21.83
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.48

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.48 FLOW VELOCITY (FEET/SEC.) = 4.19
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13852.00 = 1481.62 FEET.

FLOW PROCESS FROM NODE 13852.00 TO NODE 13853.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<
=====

ELEVATION DATA: UPSTREAM (FEET) = 395.76 DOWNSTREAM (FEET) = 354.94
CHANNEL LENGTH THRU SUBAREA (FEET) = 443.69 CHANNEL SLOPE = 0.0920
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT (FEET) = 0.52
* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.715
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	6.76	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 26.14
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.52
AVERAGE FLOW DEPTH (FEET) = 0.52 TRAVEL TIME (MIN.) = 1.64
Tc (MIN.) = 17.44

SUBAREA AREA (ACRES) = 6.76 SUBAREA RUNOFF (CFS) = 8.61
EFFECTIVE AREA (ACRES) = 22.90 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 22.9 PEAK FLOW RATE (CFS) = 29.17
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.56

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.56 FLOW VELOCITY (FEET/SEC.) = 4.69
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13853.00 = 1925.31 FEET.

FLOW PROCESS FROM NODE 13853.00 TO NODE 13854.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<
=====

ELEVATION DATA: UPSTREAM (FEET) = 354.94 DOWNSTREAM (FEET) = 263.57
CHANNEL LENGTH THRU SUBAREA (FEET) = 962.09 CHANNEL SLOPE = 0.0950
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT (FEET) = 0.67
* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.559
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	18.16	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 39.46
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.29
AVERAGE FLOW DEPTH (FEET) = 0.66 TRAVEL TIME (MIN.) = 3.03
Tc (MIN.) = 20.47

SUBAREA AREA (ACRES) = 18.16 SUBAREA RUNOFF (CFS) = 20.58
EFFECTIVE AREA (ACRES) = 41.06 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 41.1 PEAK FLOW RATE (CFS) = 46.54
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.73

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.73 FLOW VELOCITY (FEET/SEC.) = 5.58
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13854.00 = 2887.40 FEET.

FLOW PROCESS FROM NODE 13854.00 TO NODE 13855.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<
=====

ELEVATION DATA: UPSTREAM (FEET) = 263.57 DOWNSTREAM (FEET) = 188.74
CHANNEL LENGTH THRU SUBAREA (FEET) = 1228.77 CHANNEL SLOPE = 0.0609
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 1.03
* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.409
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	38.75	0.30	0.879	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.879
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 66.54
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.43
AVERAGE FLOW DEPTH (FEET) = 1.02 TRAVEL TIME (MIN.) = 3.77
Tc (MIN.) = 24.24

SUBAREA AREA (ACRES) = 38.75 SUBAREA RUNOFF (CFS) = 39.95
EFFECTIVE AREA (ACRES) = 79.81 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94
TOTAL AREA (ACRES) = 79.8 PEAK FLOW RATE (CFS) = 80.95
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 1.13

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 1.13 FLOW VELOCITY (FEET/SEC.) = 5.82
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13855.00 = 4116.17 FEET.

```

*****
FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 31
-----
>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 188.74 DOWNSTREAM(FEET) = 130.00
FLOW LENGTH(FEET) = 2092.67 MANNING'S N = 0.013
ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000
DEPTH OF FLOW IN 36.0 INCH PIPE IS 23.6 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 16.52
ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 80.95
PIPE TRAVEL TIME(MIN.) = 2.11 Tc(MIN.) = 26.35
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13860.00 = 6208.84 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====

```

```

MAINLINE Tc(MIN.) = 26.35
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.342
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS
LAND USE            GROUP  (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED        -      43.41  0.30  0.707 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.707
SUBAREA AREA(ACRES) = 43.41 SUBAREA RUNOFF(CFS) = 44.14
EFFECTIVE AREA(ACRES) = 123.22 AREA-AVERAGED Fm(INCH/HR) = 0.26
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.86
TOTAL AREA(ACRES) = 123.2 PEAK FLOW RATE(CFS) = 120.26

```

```

*****
FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 1
-----
>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<
=====

```

```

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 26.35
RAINFALL INTENSITY(INCH/HR) = 1.34
AREA-AVERAGED Fm(INCH/HR) = 0.26
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.86
EFFECTIVE STREAM AREA(ACRES) = 123.22
TOTAL STREAM AREA(ACRES) = 123.22
PEAK FLOW RATE(CFS) AT CONFLUENCE = 120.26

```

```

** CONFLUENCE DATA **

```

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14476.28	23.08	1.455	0.30(0.25)	0.82	3606.1	10600.00
1	15034.09	25.04	1.378	0.30(0.25)	0.82	4023.3	13810.00
1	16187.28	29.19	1.264	0.30(0.25)	0.82	4879.9	10400.00
1	18578.17	38.62	1.084	0.30(0.24)	0.82	7718.6	13830.00

1	19544.84	42.61	1.028	0.30(0.24)	0.81	8859.4	50500.00
1	20995.52	50.26	0.939	0.30(0.24)	0.81	11291.0	100.00
1	22853.05	60.73	0.848	0.30(0.25)	0.82	15531.1	400.00
1	23958.16	74.37	0.781	0.30(0.26)	0.86	21697.9	13600.00
1	25421.99	90.18	0.703	0.30(0.26)	0.88	28713.5	13100.00
1	25720.99	96.82	0.685	0.30(0.27)	0.89	31252.5	11801.00
1	27110.33	114.49	0.635	0.30(0.27)	0.91	39807.0	13510.00
1	28516.72	127.28	0.607	0.30(0.28)	0.92	47471.4	11330.00
1	29092.97	135.30	0.593	0.30(0.28)	0.93	52558.5	10630.00
1	28830.72	140.93	0.583	0.30(0.28)	0.93	55148.4	12330.00
1	28555.53	147.61	0.572	0.30(0.28)	0.93	58290.9	11600.00
1	28167.48	153.47	0.562	0.30(0.28)	0.94	60525.2	11111.00
1	27734.42	159.70	0.552	0.30(0.28)	0.94	62459.0	12201.00
1	26797.26	168.87	0.536	0.30(0.28)	0.94	64547.3	12231.00
1	25940.05	176.58	0.523	0.30(0.28)	0.94	65958.8	10400.00
1	24579.40	188.37	0.511	0.30(0.28)	0.94	67579.6	10320.00
1	23300.94	198.49	0.503	0.30(0.28)	0.94	67967.4	12000.00
1	20330.96	228.73	0.479	0.30(0.28)	0.94	68584.4	10100.00
2	120.26	26.35	1.342	0.30(0.26)	0.86	123.2	13850.00

```

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

```

```

** PEAK FLOW RATE TABLE **

```

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14592.62	23.08	1.455	0.30(0.25)	0.82	3714.0	10600.00
2	15152.15	25.04	1.378	0.30(0.25)	0.82	4140.4	13810.00
3	15519.51	26.35	1.342	0.30(0.25)	0.82	4417.8	13850.00
4	16298.91	29.19	1.264	0.30(0.25)	0.82	5003.1	10400.00
5	18669.85	38.62	1.084	0.30(0.24)	0.82	7841.8	13830.00
6	19630.30	42.61	1.028	0.30(0.24)	0.82	8982.6	50500.00
7	21071.06	50.26	0.939	0.30(0.24)	0.81	11414.3	100.00
8	22918.58	60.73	0.848	0.30(0.25)	0.82	15654.3	400.00
9	24016.22	74.37	0.781	0.30(0.26)	0.86	21821.1	13600.00
10	25471.44	90.18	0.703	0.30(0.26)	0.88	28836.8	13100.00
11	25768.36	96.82	0.685	0.30(0.27)	0.89	31375.7	11801.00
12	27152.15	114.49	0.635	0.30(0.27)	0.91	39930.2	13510.00
13	28555.44	127.28	0.607	0.30(0.28)	0.92	47594.6	11330.00
14	29130.17	135.30	0.593	0.30(0.28)	0.93	52681.8	10630.00
15	28866.86	140.93	0.583	0.30(0.28)	0.93	55271.6	12330.00
16	28590.40	147.61	0.572	0.30(0.28)	0.93	58414.1	11600.00
17	28201.26	153.47	0.562	0.30(0.28)	0.94	60648.4	11111.00
18	27767.02	159.70	0.552	0.30(0.28)	0.94	62582.3	12201.00
19	26828.13	168.87	0.536	0.30(0.28)	0.94	64670.5	12231.00
20	25969.46	176.58	0.523	0.30(0.28)	0.94	66082.1	10400.00
21	24607.46	188.37	0.511	0.30(0.28)	0.94	67702.8	10320.00
22	23328.12	198.49	0.503	0.30(0.28)	0.94	68090.6	12000.00
23	20355.55	228.73	0.479	0.30(0.28)	0.94	68707.6	10100.00

```

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
PEAK FLOW RATE(CFS) = 29130.17 Tc(MIN.) = 135.30
EFFECTIVE AREA(ACRES) = 52681.76 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 68707.6
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13860.00 = 133455.98 FEET.

```

FLOW PROCESS FROM NODE 13860.00 TO NODE 13880.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 130.00 DOWNSTREAM(FEET) = 120.57
CHANNEL LENGTH THRU SUBAREA(FEET) = 610.77 CHANNEL SLOPE = 0.0154
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT(FEET) = 9.26

* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.592

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 4.89 0.30 1.000 -

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 29130.82

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 22.94

AVERAGE FLOW DEPTH(FEET) = 9.26 TRAVEL TIME(MIN.) = 0.44

Tc(MIN.) = 135.74

SUBAREA AREA(ACRES) = 4.89 SUBAREA RUNOFF(CFS) = 1.29

EFFECTIVE AREA(ACRES) = 52686.65 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA(ACRES) = 68712.5 PEAK FLOW RATE(CFS) = 29130.17

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT(FEET) = 9.26

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 9.26 FLOW VELOCITY(FEET/SEC.) = 22.94

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13880.00 = 134066.75 FEET.

FLOW PROCESS FROM NODE 13860.00 TO NODE 13880.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

TOTAL NUMBER OF STREAMS = 2

CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:

TIME OF CONCENTRATION(MIN.) = 135.74

RAINFALL INTENSITY(INCH/HR) = 0.59

AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.93

EFFECTIVE STREAM AREA(ACRES) = 52686.65

TOTAL STREAM AREA(ACRES) = 68712.52

PEAK FLOW RATE(CFS) AT CONFLUENCE = 29130.17

FLOW PROCESS FROM NODE 13870.00 TO NODE 13871.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<

>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH(FEET) = 872.65

ELEVATION DATA: UPSTREAM(FEET) = 558.52 DOWNSTREAM(FEET) = 436.47

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20

SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 15.704

* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.808

SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)
NATURAL FAIR COVER

"GRASS" - 7.32 0.30 1.000 65 15.70

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

SUBAREA RUNOFF(CFS) = 9.94

TOTAL AREA(ACRES) = 7.32 PEAK FLOW RATE(CFS) = 9.94

FLOW PROCESS FROM NODE 13871.00 TO NODE 13872.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 436.47 DOWNSTREAM(FEET) = 337.62

CHANNEL LENGTH THRU SUBAREA(FEET) = 827.95 CHANNEL SLOPE = 0.1194

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 0.40

* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.635

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 13.01 0.30 1.000 -

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 17.77

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.27

AVERAGE FLOW DEPTH(FEET) = 0.39 TRAVEL TIME(MIN.) = 3.23

Tc(MIN.) = 18.93

SUBAREA AREA(ACRES) = 13.01 SUBAREA RUNOFF(CFS) = 15.63

EFFECTIVE AREA(ACRES) = 20.33 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 20.3 PEAK FLOW RATE(CFS) = 24.43

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 0.46

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.46 FLOW VELOCITY(FEET/SEC.) = 4.83

LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13872.00 = 1700.60 FEET.

FLOW PROCESS FROM NODE 13872.00 TO NODE 13873.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 337.62 DOWNSTREAM(FEET) = 253.88

CHANNEL LENGTH THRU SUBAREA(FEET) = 1049.16 CHANNEL SLOPE = 0.0798

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT (FEET) = 0.74
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.485
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 32.99 0.30 0.923 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.923
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 42.38
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.13
 AVERAGE FLOW DEPTH (FEET) = 0.72 TRAVEL TIME (MIN.) = 3.41
 Tc (MIN.) = 22.34
 SUBAREA AREA (ACRES) = 32.99 SUBAREA RUNOFF (CFS) = 35.86
 EFFECTIVE AREA (ACRES) = 53.32 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
 TOTAL AREA (ACRES) = 53.3 PEAK FLOW RATE (CFS) = 57.54
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 0.86

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 0.86 FLOW VELOCITY (FEET/SEC.) = 5.67
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13873.00 = 2749.76 FEET.

 FLOW PROCESS FROM NODE 13873.00 TO NODE 13874.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<
 =====

ELEVATION DATA: UPSTREAM (FEET) = 253.88 DOWNSTREAM (FEET) = 160.73
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1518.60 CHANNEL SLOPE = 0.0613
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT (FEET) = 0.86
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.358

SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 30.94 0.30 0.900 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.900
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 72.69
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.37
 AVERAGE FLOW DEPTH (FEET) = 0.84 TRAVEL TIME (MIN.) = 3.43
 Tc (MIN.) = 25.78
 SUBAREA AREA (ACRES) = 30.94 SUBAREA RUNOFF (CFS) = 30.29
 EFFECTIVE AREA (ACRES) = 84.26 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA (ACRES) = 84.3 PEAK FLOW RATE (CFS) = 81.74
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT (FEET) = 0.90

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 0.90 FLOW VELOCITY (FEET/SEC.) = 7.67
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13874.00 = 4268.36 FEET.

 FLOW PROCESS FROM NODE 13874.00 TO NODE 13875.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<
 =====

ELEVATION DATA: UPSTREAM (FEET) = 160.73 DOWNSTREAM (FEET) = 158.14
 CHANNEL LENGTH THRU SUBAREA (FEET) = 582.74 CHANNEL SLOPE = 0.0044
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT (FEET) = 2.31
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.281

SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 73.67 0.30 0.930 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.930
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 114.96
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 3.46
 AVERAGE FLOW DEPTH (FEET) = 2.28 TRAVEL TIME (MIN.) = 2.81
 Tc (MIN.) = 28.59
 SUBAREA AREA (ACRES) = 73.67 SUBAREA RUNOFF (CFS) = 66.42
 EFFECTIVE AREA (ACRES) = 157.93 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA (ACRES) = 157.9 PEAK FLOW RATE (CFS) = 142.31
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT (FEET) = 2.56

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 2.56 FLOW VELOCITY (FEET/SEC.) = 3.68
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13875.00 = 4851.10 FEET.

 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<
 =====

ELEVATION DATA: UPSTREAM (FEET) = 158.14 DOWNSTREAM (FEET) = 120.57
 FLOW LENGTH (FEET) = 1855.67 MANNING'S N = 0.013
 DEPTH OF FLOW IN 45.0 INCH PIPE IS 32.5 INCHES
 PIPE-FLOW VELOCITY (FEET/SEC.) = 16.65
 ESTIMATED PIPE DIAMETER (INCH) = 45.00 NUMBER OF PIPES = 1
 PIPE-FLOW (CFS) = 142.31
 PIPE TRAVEL TIME (MIN.) = 1.86 Tc (MIN.) = 30.45
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13880.00 = 6706.77 FEET.

 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
 =====

MAINLINE Tc (MIN.) = 30.45
 * 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.234
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS

LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 34.90 0.30 0.743 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.743
SUBAREA AREA(ACRES) = 34.90 SUBAREA RUNOFF(CFS) = 31.76
EFFECTIVE AREA(ACRES) = 192.83 AREA-AVERAGED Fm(INCH/HR) = 0.27
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.90
TOTAL AREA(ACRES) = 192.8 PEAK FLOW RATE(CFS) = 167.41

FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 30.45
RAINFALL INTENSITY(INCH/HR) = 1.23
AREA-AVERAGED Fm(INCH/HR) = 0.27
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.90
EFFECTIVE STREAM AREA(ACRES) = 192.83
TOTAL STREAM AREA(ACRES) = 192.83
PEAK FLOW RATE(CFS) AT CONFLUENCE = 167.41

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14592.62	23.63	1.433	0.30(0.25)	0.82	3718.9	10600.00
1	15152.15	25.58	1.363	0.30(0.25)	0.82	4145.2	13810.00
1	15519.51	26.89	1.327	0.30(0.25)	0.82	4422.7	13850.00
1	16298.91	29.72	1.250	0.30(0.25)	0.82	5008.0	10400.00
1	18669.85	39.13	1.075	0.30(0.24)	0.82	7846.7	13830.00
1	19630.30	43.11	1.022	0.30(0.24)	0.82	8987.5	50500.00
1	21071.06	50.75	0.934	0.30(0.24)	0.81	11419.2	100.00
1	22918.58	61.20	0.846	0.30(0.25)	0.82	15659.2	400.00
1	24016.22	74.84	0.779	0.30(0.26)	0.86	21826.0	13600.00
1	25471.44	90.64	0.702	0.30(0.26)	0.88	28841.7	13100.00
1	25768.36	97.28	0.683	0.30(0.27)	0.89	31380.6	11801.00
1	27152.15	114.94	0.633	0.30(0.27)	0.91	39935.1	13510.00
1	28555.44	127.73	0.606	0.30(0.28)	0.92	47599.5	11330.00
1	29130.17	135.74	0.592	0.30(0.28)	0.93	52686.7	10630.00
1	28866.86	141.38	0.583	0.30(0.28)	0.93	55276.5	12330.00
1	28590.40	148.05	0.571	0.30(0.28)	0.93	58419.0	11600.00
1	28201.26	153.92	0.561	0.30(0.28)	0.94	60653.3	11111.00
1	27767.02	160.15	0.551	0.30(0.28)	0.94	62587.1	12201.00
1	26828.13	169.33	0.535	0.30(0.28)	0.94	64675.4	12231.00
1	25969.46	177.04	0.522	0.30(0.28)	0.94	66086.9	10400.00
1	24607.46	188.84	0.510	0.30(0.28)	0.94	67707.7	10320.00
1	23328.12	198.96	0.502	0.30(0.28)	0.94	68095.5	12000.00
1	20355.55	229.23	0.479	0.30(0.28)	0.94	68712.5	10100.00
2	167.41	30.45	1.234	0.30(0.27)	0.90	192.8	13870.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14749.46	23.63	1.433	0.30(0.25)	0.82	3868.6	10600.00
2	15311.66	25.58	1.363	0.30(0.25)	0.82	4307.3	13810.00
3	15681.69	26.89	1.327	0.30(0.25)	0.82	4593.0	13850.00
4	16465.01	29.72	1.250	0.30(0.25)	0.82	5196.3	10400.00
5	16648.42	30.45	1.234	0.30(0.25)	0.82	5418.9	13870.00
6	18809.68	39.13	1.075	0.30(0.25)	0.82	8039.5	13830.00
7	19761.00	43.11	1.022	0.30(0.25)	0.82	9180.4	50500.00
8	21186.49	50.75	0.934	0.30(0.24)	0.81	11612.0	100.00
9	23018.69	61.20	0.846	0.30(0.25)	0.82	15852.1	400.00
10	24104.66	74.84	0.779	0.30(0.26)	0.86	22018.8	13600.00
11	25546.59	90.64	0.702	0.30(0.26)	0.88	29034.5	13100.00
12	25840.23	97.28	0.683	0.30(0.27)	0.89	31573.4	11801.00
13	27215.34	114.94	0.633	0.30(0.27)	0.91	40127.9	13510.00
14	28613.86	127.73	0.606	0.30(0.28)	0.92	47792.3	11330.00
15	29186.24	135.74	0.592	0.30(0.28)	0.93	52879.5	10630.00
16	28921.26	141.38	0.583	0.30(0.28)	0.93	55469.3	12330.00
17	28642.84	148.05	0.571	0.30(0.28)	0.93	58611.8	11600.00
18	28251.96	153.92	0.561	0.30(0.28)	0.94	60846.1	11111.00
19	27815.88	160.15	0.551	0.30(0.28)	0.94	62780.0	12201.00
20	26874.29	169.33	0.535	0.30(0.28)	0.94	64868.2	12231.00
21	26013.34	177.04	0.522	0.30(0.28)	0.94	66279.8	10400.00
22	24649.28	188.84	0.510	0.30(0.28)	0.94	67900.5	10320.00
23	23368.59	198.96	0.502	0.30(0.28)	0.94	68288.4	12000.00
24	20391.96	229.23	0.479	0.30(0.28)	0.94	68905.3	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 29186.24 Tc(MIN.) = 135.74
EFFECTIVE AREA(ACRES) = 52879.48 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 68905.3
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13880.00 = 134066.75 FEET.

FLOW PROCESS FROM NODE 13880.00 TO NODE 13910.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 120.57 DOWNSTREAM(FEET) = 119.70
CHANNEL LENGTH THRU SUBAREA(FEET) = 1190.21 CHANNEL SLOPE = 0.0007
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 20.63
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.588
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 117.69 0.30 0.724 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.724
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 29205.87
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.76
AVERAGE FLOW DEPTH(FEET) = 20.63 TRAVEL TIME(MIN.) = 2.56
Tc(MIN.) = 138.30
SUBAREA AREA(ACRES) = 117.69 SUBAREA RUNOFF(CFS) = 39.27
EFFECTIVE AREA(ACRES) = 52997.17 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA (ACRES) = 69023.0 PEAK FLOW RATE (CFS) = 29186.24
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 20.62

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 20.62 FLOW VELOCITY (FEET/SEC.) = 7.76
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13910.00 = 135256.95 FEET.

FLOW PROCESS FROM NODE 13880.00 TO NODE 13910.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

=====

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION (MIN.) = 138.30
RAINFALL INTENSITY (INCH/HR) = 0.59
AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.93
EFFECTIVE STREAM AREA (ACRES) = 52997.17
TOTAL STREAM AREA (ACRES) = 69023.03
PEAK FLOW RATE (CFS) AT CONFLUENCE = 29186.24

FLOW PROCESS FROM NODE 13889.00 TO NODE 13890.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH (FEET) = 447.89
ELEVATION DATA: UPSTREAM (FEET) = 564.89 DOWNSTREAM (FEET) = 421.92

Tc = K * [(LENGTH** 3.00) / (ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 6.976
* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 3.215
SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
PUBLIC PARK	-	3.03	0.30	0.960	65	6.98

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.960
SUBAREA RUNOFF (CFS) = 7.98
TOTAL AREA (ACRES) = 3.03 PEAK FLOW RATE (CFS) = 7.98

FLOW PROCESS FROM NODE 13890.00 TO NODE 13891.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 421.92 DOWNSTREAM (FEET) = 392.64
CHANNEL LENGTH THRU SUBAREA (FEET) = 435.33 CHANNEL SLOPE = 0.0673
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT (FEET) = 0.37
* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 2.825
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.12	0.30	0.986	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.986
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 17.27
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.56
AVERAGE FLOW DEPTH (FEET) = 0.35 TRAVEL TIME (MIN.) = 1.59
Tc (MIN.) = 8.57
SUBAREA AREA (ACRES) = 8.12 SUBAREA RUNOFF (CFS) = 18.49
EFFECTIVE AREA (ACRES) = 11.15 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
TOTAL AREA (ACRES) = 11.1 PEAK FLOW RATE (CFS) = 25.41
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.45

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.45 FLOW VELOCITY (FEET/SEC.) = 5.24
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13891.00 = 883.22 FEET.

FLOW PROCESS FROM NODE 13891.00 TO NODE 13892.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 392.64 DOWNSTREAM (FEET) = 324.46
CHANNEL LENGTH THRU SUBAREA (FEET) = 662.40 CHANNEL SLOPE = 0.1029
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.51
* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 2.455
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	12.50	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 37.55
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.93
AVERAGE FLOW DEPTH (FEET) = 0.49 TRAVEL TIME (MIN.) = 1.59
Tc (MIN.) = 10.16
SUBAREA AREA (ACRES) = 12.50 SUBAREA RUNOFF (CFS) = 24.24
EFFECTIVE AREA (ACRES) = 23.65 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 23.6 PEAK FLOW RATE (CFS) = 45.93
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.55

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.55 FLOW VELOCITY (FEET/SEC.) = 7.46
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13892.00 = 1545.62 FEET.


```

*****
FLOW PROCESS FROM NODE 13892.00 TO NODE 13893.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 324.46 DOWNSTREAM(FEET) = 240.82
CHANNEL LENGTH THRU SUBAREA(FEET) = 980.03 CHANNEL SLOPE = 0.0853
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.70
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.187
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp      Ap      SCS
LAND USE            GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN
USER-DEFINED        -       15.87    0.30    1.000    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 59.42
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.67
AVERAGE FLOW DEPTH(FEET) = 0.68 TRAVEL TIME(MIN.) = 2.13
Tc(MIN.) = 12.29
SUBAREA AREA(ACRES) = 15.87 SUBAREA RUNOFF(CFS) = 26.95
EFFECTIVE AREA(ACRES) = 39.52 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 39.5 PEAK FLOW RATE(CFS) = 67.18
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.74

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.74 FLOW VELOCITY(FEET/SEC.) = 7.97
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13893.00 = 2525.65 FEET.
*****
FLOW PROCESS FROM NODE 13893.00 TO NODE 13894.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 240.82 DOWNSTREAM(FEET) = 163.04
CHANNEL LENGTH THRU SUBAREA(FEET) = 1144.35 CHANNEL SLOPE = 0.0680
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.94
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.891
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp      Ap      SCS
LAND USE            GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN
USER-DEFINED        -       28.41    0.30    0.985    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.985
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 87.63
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.12
AVERAGE FLOW DEPTH(FEET) = 0.91 TRAVEL TIME(MIN.) = 2.35
Tc(MIN.) = 14.64
SUBAREA AREA(ACRES) = 28.41 SUBAREA RUNOFF(CFS) = 40.81
EFFECTIVE AREA(ACRES) = 67.93 AREA-AVERAGED Fm(INCH/HR) = 0.30

```

```

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 67.9 PEAK FLOW RATE(CFS) = 97.48
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.97

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.97 FLOW VELOCITY(FEET/SEC.) = 8.40
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13894.00 = 3670.00 FEET.
*****
FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 31
-----
>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 163.04 DOWNSTREAM(FEET) = 119.70
FLOW LENGTH(FEET) = 1899.01 MANNING'S N = 0.013
DEPTH OF FLOW IN 39.0 INCH PIPE IS 27.0 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 15.93
ESTIMATED PIPE DIAMETER(INCH) = 39.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 97.48
PIPE TRAVEL TIME(MIN.) = 1.99 Tc(MIN.) = 16.63
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13910.00 = 5569.01 FEET.
*****
FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 16.63
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.759
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp      Ap      SCS
LAND USE            GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN
USER-DEFINED        -       11.69    0.30    0.634    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.634
SUBAREA AREA(ACRES) = 11.69 SUBAREA RUNOFF(CFS) = 16.50
EFFECTIVE AREA(ACRES) = 79.62 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94
TOTAL AREA(ACRES) = 79.6 PEAK FLOW RATE(CFS) = 105.88
*****
FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 1
-----
>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<
=====
TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 16.63
RAINFALL INTENSITY(INCH/HR) = 1.76
AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.94
EFFECTIVE STREAM AREA(ACRES) = 79.62
TOTAL STREAM AREA(ACRES) = 79.62

```

PEAK FLOW RATE(CFS) AT CONFLUENCE = 105.88

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14749.46	26.73	1.332	0.30 (0.25)	0.82	3986.3	10600.00
1	15311.66	28.64	1.279	0.30 (0.25)	0.82	4425.0	13810.00
1	15681.69	29.93	1.244	0.30 (0.25)	0.82	4710.7	13850.00
1	16465.01	32.72	1.192	0.30 (0.25)	0.82	5314.0	10400.00
1	16648.42	33.43	1.179	0.30 (0.25)	0.82	5536.6	13870.00
1	18809.68	42.02	1.035	0.30 (0.25)	0.82	8157.2	13830.00
1	19761.00	45.96	0.989	0.30 (0.24)	0.82	9298.1	50500.00
1	21186.49	53.54	0.909	0.30 (0.24)	0.81	11729.7	100.00
1	23018.69	63.93	0.833	0.30 (0.25)	0.82	15969.7	400.00
1	24104.66	77.53	0.766	0.30 (0.26)	0.86	22136.5	13600.00
1	25546.59	93.29	0.695	0.30 (0.26)	0.88	29152.2	13100.00
1	25840.23	99.92	0.676	0.30 (0.27)	0.89	31691.1	11801.00
1	27215.34	117.55	0.626	0.30 (0.27)	0.91	40245.6	13510.00
1	28613.86	130.30	0.601	0.30 (0.28)	0.92	47910.0	11330.00
1	29186.24	138.30	0.588	0.30 (0.28)	0.93	52997.2	10630.00
1	28921.26	143.94	0.578	0.30 (0.28)	0.93	55587.0	12330.00
1	28642.84	150.62	0.567	0.30 (0.28)	0.93	58729.5	11600.00
1	28251.96	156.50	0.557	0.30 (0.28)	0.93	60963.8	11111.00
1	27815.88	162.74	0.546	0.30 (0.28)	0.94	62897.7	12201.00
1	26874.29	171.94	0.531	0.30 (0.28)	0.94	64985.9	12231.00
1	26013.34	179.68	0.518	0.30 (0.28)	0.94	66397.5	10400.00
1	24649.28	191.52	0.508	0.30 (0.28)	0.94	68018.2	10320.00
1	23368.59	201.68	0.500	0.30 (0.28)	0.94	68406.0	12000.00
1	20391.96	232.05	0.477	0.30 (0.28)	0.94	69023.0	10100.00
2	105.88	16.63	1.759	0.30 (0.28)	0.94	79.6	13889.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12890.02	16.63	1.759	0.30 (0.25)	0.82	2559.3	13889.00
2	14824.73	26.73	1.332	0.30 (0.25)	0.82	4065.9	10600.00
3	15383.16	28.64	1.279	0.30 (0.25)	0.82	4504.6	13810.00
4	15750.67	29.93	1.244	0.30 (0.25)	0.82	4790.3	13850.00
5	16530.29	32.72	1.192	0.30 (0.25)	0.82	5393.6	10400.00
6	16712.76	33.43	1.179	0.30 (0.25)	0.82	5616.2	13870.00
7	18863.70	42.02	1.035	0.30 (0.25)	0.82	8236.8	13830.00
8	19811.68	45.96	0.989	0.30 (0.25)	0.82	9377.7	50500.00
9	21231.50	53.54	0.909	0.30 (0.24)	0.81	11809.3	100.00
10	23058.20	63.93	0.833	0.30 (0.25)	0.82	16049.4	400.00
11	24139.36	77.53	0.766	0.30 (0.26)	0.86	22216.2	13600.00
12	25576.21	93.29	0.695	0.30 (0.26)	0.88	29231.8	13100.00
13	25868.51	99.92	0.676	0.30 (0.27)	0.89	31770.7	11801.00
14	27240.04	117.55	0.626	0.30 (0.27)	0.91	40325.2	13510.00
15	28636.81	130.30	0.601	0.30 (0.28)	0.92	47989.6	11330.00
16	29208.21	138.30	0.588	0.30 (0.28)	0.93	53076.8	10630.00
17	28942.54	143.94	0.578	0.30 (0.28)	0.93	55666.7	12330.00
18	28663.30	150.62	0.567	0.30 (0.28)	0.93	58809.1	11600.00
19	28271.71	156.50	0.557	0.30 (0.28)	0.93	61043.4	11111.00
20	27834.88	162.74	0.546	0.30 (0.28)	0.94	62977.3	12201.00
21	26892.16	171.94	0.531	0.30 (0.28)	0.94	65065.5	12231.00

22	26030.27	179.68	0.518	0.30 (0.28)	0.94	66477.1	10400.00
23	24665.53	191.52	0.508	0.30 (0.28)	0.94	68097.8	10320.00
24	23384.28	201.68	0.500	0.30 (0.28)	0.94	68485.7	12000.00
25	20405.97	232.05	0.477	0.30 (0.28)	0.94	69102.6	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 29208.21 Tc(MIN.) = 138.30
 EFFECTIVE AREA(ACRES) = 53076.79 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 69102.6
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13910.00 = 135256.95 FEET.

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 69102.6 TC(MIN.) = 138.30
 EFFECTIVE AREA(ACRES) = 53076.79 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.927
 PEAK FLOW RATE(CFS) = 29208.21

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12890.02	16.63	1.759	0.30 (0.25)	0.82	2559.3	13889.00
2	14824.73	26.73	1.332	0.30 (0.25)	0.82	4065.9	10600.00
3	15383.16	28.64	1.279	0.30 (0.25)	0.82	4504.6	13810.00
4	15750.67	29.93	1.244	0.30 (0.25)	0.82	4790.3	13850.00
5	16530.29	32.72	1.192	0.30 (0.25)	0.82	5393.6	10400.00
6	16712.76	33.43	1.179	0.30 (0.25)	0.82	5616.2	13870.00
7	18863.70	42.02	1.035	0.30 (0.25)	0.82	8236.8	13830.00
8	19811.68	45.96	0.989	0.30 (0.25)	0.82	9377.7	50500.00
9	21231.50	53.54	0.909	0.30 (0.24)	0.81	11809.3	100.00
10	23058.20	63.93	0.833	0.30 (0.25)	0.82	16049.4	400.00
11	24139.36	77.53	0.766	0.30 (0.26)	0.86	22216.2	13600.00
12	25576.21	93.29	0.695	0.30 (0.26)	0.88	29231.8	13100.00
13	25868.51	99.92	0.676	0.30 (0.27)	0.89	31770.7	11801.00
14	27240.04	117.55	0.626	0.30 (0.27)	0.91	40325.2	13510.00
15	28636.81	130.30	0.601	0.30 (0.28)	0.92	47989.6	11330.00
16	29208.21	138.30	0.588	0.30 (0.28)	0.93	53076.8	10630.00
17	28942.54	143.94	0.578	0.30 (0.28)	0.93	55666.7	12330.00
18	28663.30	150.62	0.567	0.30 (0.28)	0.93	58809.1	11600.00
19	28271.71	156.50	0.557	0.30 (0.28)	0.93	61043.4	11111.00
20	27834.88	162.74	0.546	0.30 (0.28)	0.94	62977.3	12201.00
21	26892.16	171.94	0.531	0.30 (0.28)	0.94	65065.5	12231.00
22	26030.27	179.68	0.518	0.30 (0.28)	0.94	66477.1	10400.00
23	24665.53	191.52	0.508	0.30 (0.28)	0.94	68097.8	10320.00
24	23384.28	201.68	0.500	0.30 (0.28)	0.94	68485.7	12000.00
25	20405.97	232.05	0.477	0.30 (0.28)	0.94	69102.6	10100.00

END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2010 Advanced Engineering Software (aes)
Ver. 17.0 Release Date: 07/01/2010 License ID 1527

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 139 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 10-YR EV AUG 2023 ROKAMOTO *

FILE NAME: RU10EV39.DAT
TIME/DATE OF STUDY: 23:37 08/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 10.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 3.695
- 2) 10.00; 2.473
- 3) 15.00; 1.845
- 4) 20.00; 1.577
- 5) 25.00; 1.378
- 6) 30.00; 1.242
- 7) 40.00; 1.058
- 8) 50.00; 0.941
- 9) 60.00; 0.852
- 10) 90.00; 0.704
- 11) 120.00; 0.618
- 12) 180.00; 0.516
- 13) 360.00; 0.377
- 14) 1200.00; 0.164

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL: IN- / OUT-/PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13900.00 TO NODE 13901.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 600.65
ELEVATION DATA: UPSTREAM(FEET) = 442.40 DOWNSTREAM(FEET) = 385.16

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 10.859
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.365
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
AGRICULTURAL POOR COVER "FALLOW"	-	4.00	0.30	1.000	65	10.86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 7.43
TOTAL AREA(ACRES) = 4.00 PEAK FLOW RATE(CFS) = 7.43

FLOW PROCESS FROM NODE 13901.00 TO NODE 13902.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 385.16 DOWNSTREAM(FEET) = 288.21
CHANNEL LENGTH THRU SUBAREA(FEET) = 647.42 CHANNEL SLOPE = 0.1497
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.26
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.119
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.47	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 14.40
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.51
AVERAGE FLOW DEPTH(FEET) = 0.25 TRAVEL TIME(MIN.) = 1.96
Tc(MIN.) = 12.82
SUBAREA AREA(ACRES) = 8.47 SUBAREA RUNOFF(CFS) = 13.87
EFFECTIVE AREA(ACRES) = 12.47 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 12.5 PEAK FLOW RATE(CFS) = 20.42
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.31

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.31 FLOW VELOCITY(FEET/SEC.) = 6.24
LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13902.00 = 1248.07 FEET.

FLOW PROCESS FROM NODE 13902.00 TO NODE 13903.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 288.21 DOWNSTREAM(FEET) = 184.89
CHANNEL LENGTH THRU SUBAREA(FEET) = 669.27 CHANNEL SLOPE = 0.1544
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.45
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.943

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	23.85	0.30	0.982	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.982

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 38.14

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.97

AVERAGE FLOW DEPTH(FEET) = 0.44 TRAVEL TIME(MIN.) = 1.40

Tc(MIN.) = 14.22

SUBAREA AREA(ACRES) = 23.85 SUBAREA RUNOFF(CFS) = 35.39

EFFECTIVE AREA(ACRES) = 36.32 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 36.3 PEAK FLOW RATE(CFS) = 53.84

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 0.54

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.54 FLOW VELOCITY(FEET/SEC.) = 9.02

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13903.00 = 1917.34 FEET.

FLOW PROCESS FROM NODE 13903.00 TO NODE 13904.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 184.89 DOWNSTREAM(FEET) = 155.08

FLOW LENGTH(FEET) = 876.66 MANNING'S N = 0.013

ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000

DEPTH OF FLOW IN 36.0 INCH PIPE IS 17.2 INCHES

PIPE-FLOW VELOCITY(FEET/SEC.) = 16.18

ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1

PIPE-FLOW(CFS) = 53.84

PIPE TRAVEL TIME(MIN.) = 0.90 Tc(MIN.) = 15.12

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13904.00 = 2794.00 FEET.

FLOW PROCESS FROM NODE 13903.00 TO NODE 13904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 15.12

* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.839

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	21.29	0.30	0.996	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.996

SUBAREA AREA(ACRES) = 21.29 SUBAREA RUNOFF(CFS) = 29.51

EFFECTIVE AREA(ACRES) = 57.61 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 57.6 PEAK FLOW RATE(CFS) = 79.92

FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 155.08 DOWNSTREAM(FEET) = 118.00

FLOW LENGTH(FEET) = 1961.38 MANNING'S N = 0.013

DEPTH OF FLOW IN 36.0 INCH PIPE IS 27.2 INCHES

PIPE-FLOW VELOCITY(FEET/SEC.) = 13.96

ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1

PIPE-FLOW(CFS) = 79.92

PIPE TRAVEL TIME(MIN.) = 2.34 Tc(MIN.) = 17.46

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13920.00 = 4755.38 FEET.

FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 17.46

* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.713

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	43.53	0.30	0.649	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.649

SUBAREA AREA(ACRES) = 43.53 SUBAREA RUNOFF(CFS) = 59.49

EFFECTIVE AREA(ACRES) = 101.14 AREA-AVERAGED Fm(INCH/HR) = 0.25

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84

TOTAL AREA(ACRES) = 101.1 PEAK FLOW RATE(CFS) = 132.90

FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 13910.00 TO NODE 13910.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU10EV38.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12890.02	16.63	0.30 (0.25)	0.82	2559.3	13889.00
2	16712.76	33.43	0.30 (0.25)	0.82	5616.2	13870.00
3	19811.68	45.96	0.30 (0.25)	0.82	9377.7	50500.00
4	21231.50	53.54	0.30 (0.24)	0.81	11809.3	100.00
5	23058.20	63.93	0.30 (0.25)	0.82	16049.4	400.00
6	24139.36	77.53	0.30 (0.26)	0.86	22216.2	13600.00
7	25576.21	93.29	0.30 (0.26)	0.88	29231.8	13100.00
8	25868.51	99.92	0.30 (0.27)	0.89	31770.7	11801.00
9	27240.04	117.55	0.30 (0.27)	0.91	40325.2	13510.00
10	28636.81	130.30	0.30 (0.28)	0.92	47989.6	11330.00
11	29208.21	138.30	0.30 (0.28)	0.93	53076.8	10630.00
12	28942.54	143.94	0.30 (0.28)	0.93	55666.7	12330.00
13	28663.30	150.62	0.30 (0.28)	0.93	58809.1	11600.00
14	28271.71	156.50	0.30 (0.28)	0.93	61043.4	11111.00
15	27834.88	162.74	0.30 (0.28)	0.94	62977.3	12201.00
16	26892.16	171.94	0.30 (0.28)	0.94	65065.5	12231.00
17	26030.27	179.68	0.30 (0.28)	0.94	66477.1	10400.00
18	24665.53	191.52	0.30 (0.28)	0.94	68097.8	10320.00
19	23384.28	201.68	0.30 (0.28)	0.94	68485.7	12000.00
20	20405.97	232.05	0.30 (0.28)	0.94	69102.6	10100.00
TOTAL AREA (ACRES) =						69102.6

FLOW PROCESS FROM NODE 13910.00 TO NODE 13910.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12890.02	16.63	0.30 (0.25)	0.82	2559.3	13889.00
2	16712.76	33.43	0.30 (0.25)	0.82	5616.2	13870.00
3	19811.68	45.96	0.30 (0.25)	0.82	9377.7	50500.00
4	21231.50	53.54	0.30 (0.24)	0.81	11809.3	100.00
5	23058.20	63.93	0.30 (0.25)	0.82	16049.4	400.00
6	24139.36	77.53	0.30 (0.26)	0.86	22216.2	13600.00
7	25576.21	93.29	0.30 (0.26)	0.88	29231.8	13100.00
8	25868.51	99.92	0.30 (0.27)	0.89	31770.7	11801.00
9	27240.04	117.55	0.30 (0.27)	0.91	40325.2	13510.00
10	28636.81	130.30	0.30 (0.28)	0.92	47989.6	11330.00
11	29208.21	138.30	0.30 (0.28)	0.93	53076.8	10630.00
12	28942.54	143.94	0.30 (0.28)	0.93	55666.7	12330.00
13	28663.30	150.62	0.30 (0.28)	0.93	58809.1	11600.00
14	28271.71	156.50	0.30 (0.28)	0.93	61043.4	11111.00
15	27834.88	162.74	0.30 (0.28)	0.94	62977.3	12201.00
16	26892.16	171.94	0.30 (0.28)	0.94	65065.5	12231.00
17	26030.27	179.68	0.30 (0.28)	0.94	66477.1	10400.00
18	24665.53	191.52	0.30 (0.28)	0.94	68097.8	10320.00
19	23384.28	201.68	0.30 (0.28)	0.94	68485.7	12000.00
20	20405.97	232.05	0.30 (0.28)	0.94	69102.6	10100.00
TOTAL AREA (ACRES) =						69102.6

FLOW PROCESS FROM NODE 13910.00 TO NODE 13920.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 119.70 DOWNSTREAM(FEET) = 118.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1376.26 CHANNEL SLOPE = 0.0012
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 18.08
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.583
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 96.09 0.30 0.535 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.535
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 29226.46
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.38
 AVERAGE FLOW DEPTH(FEET) = 18.08 TRAVEL TIME(MIN.) = 2.44
 Tc(MIN.) = 140.74
 SUBAREA AREA(ACRES) = 96.09 SUBAREA RUNOFF(CFS) = 36.52
 EFFECTIVE AREA(ACRES) = 53172.88 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 69198.7 PEAK FLOW RATE(CFS) = 29208.21
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 18.07

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 18.07 FLOW VELOCITY(FEET/SEC.) = 9.38

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136633.22 FEET.

FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12890.02	19.71	1.592	0.30 (0.24)	0.81	2655.4	13889.00
2	16712.76	36.30	1.126	0.30 (0.24)	0.82	5712.3	13870.00
3	19811.68	48.69	0.956	0.30 (0.24)	0.81	9473.8	50500.00
4	21231.50	56.22	0.886	0.30 (0.24)	0.81	11905.4	100.00
5	23058.20	66.55	0.820	0.30 (0.25)	0.82	16145.5	400.00
6	24139.36	80.11	0.753	0.30 (0.26)	0.85	22312.2	13600.00
7	25576.21	95.83	0.687	0.30 (0.26)	0.88	29327.9	13100.00
8	25868.51	102.45	0.668	0.30 (0.27)	0.89	31866.8	11801.00
9	27240.04	120.04	0.618	0.30 (0.27)	0.90	40421.3	13510.00
10	28636.81	132.76	0.596	0.30 (0.28)	0.92	48085.7	11330.00
11	29208.21	140.74	0.583	0.30 (0.28)	0.93	53172.9	10630.00
12	28942.54	146.39	0.573	0.30 (0.28)	0.93	55762.8	12330.00
13	28663.30	153.08	0.562	0.30 (0.28)	0.93	58905.2	11600.00
14	28271.71	158.97	0.552	0.30 (0.28)	0.93	61139.5	11111.00
15	27834.88	165.22	0.541	0.30 (0.28)	0.94	63073.4	12201.00
16	26892.16	174.45	0.525	0.30 (0.28)	0.94	65161.6	12231.00

17 26030.27 182.20 0.514 0.30(0.28) 0.94 66573.2 10400.00
 18 24665.53 194.08 0.505 0.30(0.28) 0.94 68193.9 10320.00
 19 23384.28 204.28 0.497 0.30(0.28) 0.94 68581.8 12000.00
 20 20405.97 234.76 0.474 0.30(0.28) 0.94 69198.7 10100.00
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136633.22 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	132.90	17.46	1.713	0.30(0.25)	0.84	101.1	13900.00

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13920.00 = 4755.38 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12572.44	17.46	1.713	0.30(0.24)	0.81	2453.4	13900.00
2	13011.94	19.71	1.592	0.30(0.24)	0.81	2756.5	13889.00
3	16792.23	36.30	1.126	0.30(0.24)	0.82	5813.4	13870.00
4	19875.70	48.69	0.956	0.30(0.24)	0.81	9574.9	50500.00
5	21289.09	56.22	0.886	0.30(0.24)	0.81	12006.5	100.00
6	23109.77	66.55	0.820	0.30(0.25)	0.82	16246.6	400.00
7	24184.84	80.11	0.753	0.30(0.26)	0.85	22413.4	13600.00
8	25615.73	95.83	0.687	0.30(0.26)	0.88	29429.0	13100.00
9	25906.30	102.45	0.668	0.30(0.27)	0.89	31967.9	11801.00
10	27273.24	120.04	0.618	0.30(0.27)	0.90	40522.5	13510.00
11	28668.05	132.76	0.596	0.30(0.28)	0.92	48186.9	11330.00
12	29238.21	140.74	0.583	0.30(0.28)	0.93	53274.0	10630.00
13	28971.67	146.39	0.573	0.30(0.28)	0.93	55863.9	12330.00
14	28691.40	153.08	0.562	0.30(0.28)	0.93	59006.3	11600.00
15	28298.89	158.97	0.552	0.30(0.28)	0.93	61240.7	11111.00
16	27861.09	165.22	0.541	0.30(0.28)	0.94	63174.5	12201.00
17	26916.95	174.45	0.525	0.30(0.28)	0.94	65262.8	12231.00
18	26054.05	182.20	0.514	0.30(0.28)	0.94	66674.3	10400.00
19	24688.47	194.08	0.505	0.30(0.28)	0.94	68295.1	10320.00
20	23406.50	204.28	0.497	0.30(0.28)	0.94	68682.9	12000.00
21	20426.05	234.76	0.474	0.30(0.28)	0.94	69299.9	10100.00

TOTAL AREA (ACRES) = 69299.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 29238.21 Tc(MIN.) = 140.744
 EFFECTIVE AREA(ACRES) = 53274.02 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA(ACRES) = 69299.9
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136633.22 FEET.

 FLOW PROCESS FROM NODE 13920.00 TO NODE 13921.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 118.00 DOWNSTREAM(FEET) = 115.28
 CHANNEL LENGTH THRU SUBAREA(FEET) = 335.44 CHANNEL SLOPE = 0.0081
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 11.06
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.582
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	134.30	0.30	0.658	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.658
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 29261.47
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 18.35
 AVERAGE FLOW DEPTH(FEET) = 11.06 TRAVEL TIME(MIN.) = 0.30
 Tc(MIN.) = 141.05
 SUBAREA AREA(ACRES) = 134.30 SUBAREA RUNOFF(CFS) = 46.52
 EFFECTIVE AREA(ACRES) = 53408.32 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 69434.2 PEAK FLOW RATE(CFS) = 29238.21
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 11.05

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 11.05 FLOW VELOCITY(FEET/SEC.) = 18.34
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13921.00 = 136968.66 FEET.

 FLOW PROCESS FROM NODE 13921.00 TO NODE 14010.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 115.28 DOWNSTREAM(FEET) = 100.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1396.08 CHANNEL SLOPE = 0.0109
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 10.20
 * 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.580
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	96.27	0.30	0.723	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.723
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 29253.96
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 20.38
 AVERAGE FLOW DEPTH(FEET) = 10.20 TRAVEL TIME(MIN.) = 1.14
 Tc(MIN.) = 142.19
 SUBAREA AREA(ACRES) = 96.27 SUBAREA RUNOFF(CFS) = 31.49
 EFFECTIVE AREA(ACRES) = 53504.59 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA(ACRES) = 69530.5 PEAK FLOW RATE(CFS) = 29238.21
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 10.20

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 10.20 FLOW VELOCITY(FEET/SEC.) = 20.37
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 14010.00 = 138364.73 FEET.

=====

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 69530.5 TC (MIN.) = 142.19
 EFFECTIVE AREA (ACRES) = 53504.59 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.925
 PEAK FLOW RATE (CFS) = 29238.21

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12572.44	19.34	1.612	0.30 (0.24)	0.80	2683.9	13900.00
2	13011.94	21.57	1.515	0.30 (0.24)	0.80	2987.1	13889.00
3	16792.23	38.01	1.095	0.30 (0.24)	0.81	6044.0	13870.00
4	19875.70	50.31	0.938	0.30 (0.24)	0.81	9805.5	50500.00
5	21289.09	57.81	0.871	0.30 (0.24)	0.81	12237.1	100.00
6	23109.77	68.10	0.812	0.30 (0.25)	0.82	16477.2	400.00
7	24184.84	81.64	0.745	0.30 (0.26)	0.85	22644.0	13600.00
8	25615.73	97.33	0.683	0.30 (0.26)	0.88	29659.6	13100.00
9	25906.30	103.95	0.664	0.30 (0.27)	0.89	32198.5	11801.00
10	27273.24	121.52	0.615	0.30 (0.27)	0.90	40753.1	13510.00
11	28668.05	134.22	0.594	0.30 (0.28)	0.92	48417.4	11330.00
12	29238.21	142.19	0.580	0.30 (0.28)	0.92	53504.6	10630.00
13	28971.67	147.84	0.571	0.30 (0.28)	0.93	56094.5	12330.00
14	28691.40	154.53	0.559	0.30 (0.28)	0.93	59236.9	11600.00
15	28298.89	160.43	0.549	0.30 (0.28)	0.93	61471.2	11111.00
16	27861.09	166.69	0.539	0.30 (0.28)	0.93	63405.1	12201.00
17	26916.95	175.93	0.523	0.30 (0.28)	0.94	65493.3	12231.00
18	26054.05	183.70	0.513	0.30 (0.28)	0.94	66904.9	10400.00
19	24688.47	195.60	0.504	0.30 (0.28)	0.94	68525.6	10320.00
20	23406.50	205.83	0.496	0.30 (0.28)	0.94	68913.5	12000.00
21	20426.05	236.37	0.472	0.30 (0.28)	0.94	69530.5	10100.00

=====
 END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International
5 Hutton Centre Drive, Suite 500
Santa Ana, CA 92707

***** DESCRIPTION OF STUDY *****
* RANCHO MISSION VIEJO - PA3 & PA4 ROMP - NODE 119 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 25-YR RM EV APRIL 2019 FKAZI *

FILE NAME: RU25EV19.DAT
TIME/DATE OF STUDY: 10:56 04/01/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 25.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.002
- 2) 10.00; 3.253
- 3) 15.00; 2.474
- 4) 20.00; 2.039
- 5) 25.00; 1.776
- 6) 30.00; 1.555
- 7) 40.00; 1.357
- 8) 50.00; 1.203
- 9) 60.00; 1.080
- 10) 90.00; 0.912
- 11) 120.00; 0.803
- 12) 180.00; 0.673
- 13) 360.00; 0.500
- 14) 1200.00; 0.221

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 11900.00 TO NODE 11901.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 295.79
ELEVATION DATA: UPSTREAM(FEET) = 2369.48 DOWNSTREAM(FEET) = 2332.92

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 7.203
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 4.231
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
RESIDENTIAL ".4 DWELLING/ACRE"	-	1.62	0.30	0.999	0	7.20

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999
SUBAREA RUNOFF(CFS) = 5.73
TOTAL AREA(ACRES) = 1.62 PEAK FLOW RATE(CFS) = 5.73

FLOW PROCESS FROM NODE 11901.00 TO NODE 11902.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2332.92 DOWNSTREAM(FEET) = 2297.70
CHANNEL LENGTH THRU SUBAREA(FEET) = 664.26 CHANNEL SLOPE = 0.0530
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.53
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 3.158
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.35	0.30	0.906	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.906
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 16.71
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.25
AVERAGE FLOW DEPTH(FEET) = 0.47 TRAVEL TIME(MIN.) = 3.41
Tc(MIN.) = 10.61
SUBAREA AREA(ACRES) = 8.35 SUBAREA RUNOFF(CFS) = 21.69
EFFECTIVE AREA(ACRES) = 9.97 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 10.0 PEAK FLOW RATE(CFS) = 25.86
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.61

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.61 FLOW VELOCITY(FEET/SEC.) = 3.76
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11902.00 = 960.05 FEET.

FLOW PROCESS FROM NODE 11902.00 TO NODE 11902.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2297.70 DOWNSTREAM(FEET) = 2263.40
CHANNEL LENGTH THRU SUBAREA(FEET) = 928.77 CHANNEL SLOPE = 0.0369
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 1.21
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.623

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	34.48	0.30	0.904	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.904
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 62.68
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.51
AVERAGE FLOW DEPTH(FEET) = 1.13 TRAVEL TIME(MIN.) = 3.44
Tc(MIN.) = 14.05

SUBAREA AREA(ACRES) = 34.48 SUBAREA RUNOFF(CFS) = 72.97
EFFECTIVE AREA(ACRES) = 44.45 AREA-AVERAGED Fm(INCH/HR) = 0.27
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.91
TOTAL AREA(ACRES) = 44.5 PEAK FLOW RATE(CFS) = 94.03
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.42

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.42 FLOW VELOCITY(FEET/SEC.) = 5.14
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11902.50 = 1888.82 FEET.

FLOW PROCESS FROM NODE 11902.50 TO NODE 11903.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2263.40 DOWNSTREAM(FEET) = 2252.14
CHANNEL LENGTH THRU SUBAREA(FEET) = 895.50 CHANNEL SLOPE = 0.0126
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 2.19
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.210

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	23.65	0.30	0.958	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.958
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 114.54
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.75
AVERAGE FLOW DEPTH(FEET) = 2.14 TRAVEL TIME(MIN.) = 3.98

Tc(MIN.) = 18.03
SUBAREA AREA(ACRES) = 23.65 SUBAREA RUNOFF(CFS) = 40.93
EFFECTIVE AREA(ACRES) = 68.10 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 68.1 PEAK FLOW RATE(CFS) = 118.47
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.18

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.18 FLOW VELOCITY(FEET/SEC.) = 3.77
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11903.00 = 2784.32 FEET.

FLOW PROCESS FROM NODE 11903.00 TO NODE 11904.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2252.14 DOWNSTREAM(FEET) = 2186.04
CHANNEL LENGTH THRU SUBAREA(FEET) = 1924.35 CHANNEL SLOPE = 0.0343
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 2.07
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.860

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	68.53	0.30	0.961	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.961
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 167.09
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.96
AVERAGE FLOW DEPTH(FEET) = 2.00 TRAVEL TIME(MIN.) = 5.38
Tc(MIN.) = 23.41

SUBAREA AREA(ACRES) = 68.53 SUBAREA RUNOFF(CFS) = 96.92
EFFECTIVE AREA(ACRES) = 136.63 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94
TOTAL AREA(ACRES) = 136.6 PEAK FLOW RATE(CFS) = 193.88
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.17

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.17 FLOW VELOCITY(FEET/SEC.) = 6.22
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11904.00 = 4708.67 FEET.

FLOW PROCESS FROM NODE 11904.00 TO NODE 11905.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2186.04 DOWNSTREAM(FEET) = 1957.34
CHANNEL LENGTH THRU SUBAREA(FEET) = 1926.87 CHANNEL SLOPE = 0.1187
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 1.73

* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.707
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 63.15 0.30 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 233.88
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 10.18
 AVERAGE FLOW DEPTH (FEET) = 1.71 TRAVEL TIME (MIN.) = 3.16
 Tc (MIN.) = 26.57
 SUBAREA AREA (ACRES) = 63.15 SUBAREA RUNOFF (CFS) = 79.96
 EFFECTIVE AREA (ACRES) = 199.78 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
 TOTAL AREA (ACRES) = 199.8 PEAK FLOW RATE (CFS) = 255.05
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 1.80
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 1.80 FLOW VELOCITY (FEET/SEC.) = 10.45
 LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11905.00 = 6635.54 FEET.

FLOW PROCESS FROM NODE 11905.00 TO NODE 11906.00 IS CODE = 56

 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 1957.34 DOWNSTREAM (FEET) = 1244.16
 CHANNEL LENGTH THRU SUBAREA (FEET) = 2498.96 CHANNEL SLOPE = 0.2854
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 1.57
 * 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.584
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 84.87 0.30 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 304.10
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 14.96
 AVERAGE FLOW DEPTH (FEET) = 1.55 TRAVEL TIME (MIN.) = 2.78
 Tc (MIN.) = 29.35
 SUBAREA AREA (ACRES) = 84.87 SUBAREA RUNOFF (CFS) = 98.06
 EFFECTIVE AREA (ACRES) = 284.65 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA (ACRES) = 284.6 PEAK FLOW RATE (CFS) = 330.98
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 1.63

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 1.63 FLOW VELOCITY (FEET/SEC.) = 15.34
 LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11906.00 = 9134.50 FEET.

FLOW PROCESS FROM NODE 11906.00 TO NODE 11920.00 IS CODE = 56

 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 1244.16 DOWNSTREAM (FEET) = 873.95
 CHANNEL LENGTH THRU SUBAREA (FEET) = 3370.75 CHANNEL SLOPE = 0.1098
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 2.49
 * 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.474
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 199.43 0.30 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 436.43
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 11.89
 AVERAGE FLOW DEPTH (FEET) = 2.46 TRAVEL TIME (MIN.) = 4.72
 Tc (MIN.) = 34.07
 SUBAREA AREA (ACRES) = 199.43 SUBAREA RUNOFF (CFS) = 210.79
 EFFECTIVE AREA (ACRES) = 484.08 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
 TOTAL AREA (ACRES) = 484.1 PEAK FLOW RATE (CFS) = 513.75
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 2.68

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 2.68 FLOW VELOCITY (FEET/SEC.) = 12.48
 LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11920.00 = 12505.25 FEET.

FLOW PROCESS FROM NODE 11906.00 TO NODE 11920.00 IS CODE = 1

 >>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
 TIME OF CONCENTRATION (MIN.) = 34.07
 RAINFALL INTENSITY (INCH/HR) = 1.47
 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.98
 EFFECTIVE STREAM AREA (ACRES) = 484.08
 TOTAL STREAM AREA (ACRES) = 484.08
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 513.75

FLOW PROCESS FROM NODE 11910.00 TO NODE 11911.00 IS CODE = 21

 >>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH (FEET) = 517.62
 ELEVATION DATA: UPSTREAM (FEET) = 2531.88 DOWNSTREAM (FEET) = 2441.33

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
 SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 12.185
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.913
 SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	-	3.46	0.30	1.000	0	12.19

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA RUNOFF(CFS) = 8.14
 TOTAL AREA(ACRES) = 3.46 PEAK FLOW RATE(CFS) = 8.14

 FLOW PROCESS FROM NODE 11911.00 TO NODE 11912.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2441.33 DOWNSTREAM(FEET) = 2382.20
 CHANNEL LENGTH THRU SUBAREA(FEET) = 397.30 CHANNEL SLOPE = 0.1488
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 0.33

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.669

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.79	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 14.32
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.24
 AVERAGE FLOW DEPTH(FEET) = 0.32 TRAVEL TIME(MIN.) = 1.56
 Tc(MIN.) = 13.75

SUBAREA AREA(ACRES) = 5.79 SUBAREA RUNOFF(CFS) = 12.35
 EFFECTIVE AREA(ACRES) = 9.25 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 9.2 PEAK FLOW RATE(CFS) = 19.72
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 0.38

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 0.38 FLOW VELOCITY(FEET/SEC.) = 4.77
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11912.00 = 914.92 FEET.

 FLOW PROCESS FROM NODE 11912.00 TO NODE 11913.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2382.20 DOWNSTREAM(FEET) = 2263.77
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1891.47 CHANNEL SLOPE = 0.0626
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 1.10

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.076
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	54.30	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 63.91
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.41
 AVERAGE FLOW DEPTH(FEET) = 0.99 TRAVEL TIME(MIN.) = 5.83
 Tc(MIN.) = 19.58
 SUBAREA AREA(ACRES) = 54.30 SUBAREA RUNOFF(CFS) = 86.79
 EFFECTIVE AREA(ACRES) = 63.55 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 63.5 PEAK FLOW RATE(CFS) = 101.57
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 1.28

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 1.28 FLOW VELOCITY(FEET/SEC.) = 6.29
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11913.00 = 2806.39 FEET.

 FLOW PROCESS FROM NODE 11913.00 TO NODE 11914.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2263.77 DOWNSTREAM(FEET) = 1845.23
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1957.31 CHANNEL SLOPE = 0.2138
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 1.15

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.902

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	65.14	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 148.58
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.79
 AVERAGE FLOW DEPTH(FEET) = 1.12 TRAVEL TIME(MIN.) = 3.02
 Tc(MIN.) = 22.60

SUBAREA AREA(ACRES) = 65.14 SUBAREA RUNOFF(CFS) = 93.93
 EFFECTIVE AREA(ACRES) = 128.69 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 128.7 PEAK FLOW RATE(CFS) = 185.57
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 1.28

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 1.28 FLOW VELOCITY(FEET/SEC.) = 11.58
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11914.00 = 4763.70 FEET.

FLOW PROCESS FROM NODE 11914.00 TO NODE 11915.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1845.23 DOWNSTREAM(FEET) = 1557.21
CHANNEL LENGTH THRU SUBAREA(FEET) = 1686.78 CHANNEL SLOPE = 0.1708
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 1.58
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.775

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 78.52 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 237.72

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.60

AVERAGE FLOW DEPTH(FEET) = 1.56 TRAVEL TIME(MIN.) = 2.42

Tc(MIN.) = 25.02

SUBAREA AREA(ACRES) = 78.52 SUBAREA RUNOFF(CFS) = 104.24

EFFECTIVE AREA(ACRES) = 207.21 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 207.2 PEAK FLOW RATE(CFS) = 275.07

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 1.70

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.70 FLOW VELOCITY(FEET/SEC.) = 12.11

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11915.00 = 6450.48 FEET.

FLOW PROCESS FROM NODE 11915.00 TO NODE 11916.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1557.21 DOWNSTREAM(FEET) = 1403.38
CHANNEL LENGTH THRU SUBAREA(FEET) = 1909.39 CHANNEL SLOPE = 0.0806
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 2.27
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.630

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 70.48 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 317.28

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.74

AVERAGE FLOW DEPTH(FEET) = 2.25 TRAVEL TIME(MIN.) = 3.27

Tc(MIN.) = 28.29

SUBAREA AREA(ACRES) = 70.48 SUBAREA RUNOFF(CFS) = 84.40

EFFECTIVE AREA(ACRES) = 277.69 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 277.7 PEAK FLOW RATE(CFS) = 332.54
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.31

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.31 FLOW VELOCITY(FEET/SEC.) = 9.85

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11916.00 = 8359.87 FEET.

FLOW PROCESS FROM NODE 11916.00 TO NODE 11917.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1403.38 DOWNSTREAM(FEET) = 1079.99
CHANNEL LENGTH THRU SUBAREA(FEET) = 1945.82 CHANNEL SLOPE = 0.1662
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 2.29
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.543

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 232.20 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 462.46

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 14.02

AVERAGE FLOW DEPTH(FEET) = 2.27 TRAVEL TIME(MIN.) = 2.31

Tc(MIN.) = 30.60

SUBAREA AREA(ACRES) = 232.20 SUBAREA RUNOFF(CFS) = 259.78

EFFECTIVE AREA(ACRES) = 509.89 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 509.9 PEAK FLOW RATE(CFS) = 570.46

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 2.54

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.54 FLOW VELOCITY(FEET/SEC.) = 14.91

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11917.00 = 10305.69 FEET.

FLOW PROCESS FROM NODE 11917.00 TO NODE 11920.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1079.99 DOWNSTREAM(FEET) = 873.95
CHANNEL LENGTH THRU SUBAREA(FEET) = 2563.91 CHANNEL SLOPE = 0.0804
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 3.25

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.471

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

USER-DEFINED - 110.82 0.30 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 628.88
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 11.79
 AVERAGE FLOW DEPTH (FEET) = 3.24 TRAVEL TIME (MIN.) = 3.62
 Tc (MIN.) = 34.23
 SUBAREA AREA (ACRES) = 110.82 SUBAREA RUNOFF (CFS) = 116.83
 EFFECTIVE AREA (ACRES) = 620.71 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 620.7 PEAK FLOW RATE (CFS) = 654.35
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 3.30

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 3.30 FLOW VELOCITY (FEET/SEC.) = 11.94
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11920.00 = 12869.60 FEET.

 FLOW PROCESS FROM NODE 11917.00 TO NODE 11920.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

 TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
 TIME OF CONCENTRATION (MIN.) = 34.23
 RAINFALL INTENSITY (INCH/HR) = 1.47
 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30
 AREA-AVERAGED Ap = 1.00
 EFFECTIVE STREAM AREA (ACRES) = 620.71
 TOTAL STREAM AREA (ACRES) = 620.71
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 654.35

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	513.75	34.07	1.474	0.30 (0.30)	0.98	484.1	11900.00
2	654.35	34.23	1.471	0.30 (0.30)	1.00	620.7	11910.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1166.84	34.07	1.474	0.30 (0.30)	0.99	1102.0	11900.00
2	1166.76	34.23	1.471	0.30 (0.30)	0.99	1104.8	11910.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
 PEAK FLOW RATE (CFS) = 1166.84 Tc (MIN.) = 34.07
 EFFECTIVE AREA (ACRES) = 1101.97 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 1104.8
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11920.00 = 12869.60 FEET.

 FLOW PROCESS FROM NODE 11920.00 TO NODE 11921.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 873.95 DOWNSTREAM (FEET) = 827.94
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1417.25 CHANNEL SLOPE = 0.0325
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 5.66
 * 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.428

SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 107.47 0.30 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 1221.40
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 10.13
 AVERAGE FLOW DEPTH (FEET) = 5.66 TRAVEL TIME (MIN.) = 2.33
 Tc (MIN.) = 36.41
 SUBAREA AREA (ACRES) = 107.47 SUBAREA RUNOFF (CFS) = 109.12
 EFFECTIVE AREA (ACRES) = 1209.44 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 1212.3 PEAK FLOW RATE (CFS) = 1230.16
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 5.68

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 5.68 FLOW VELOCITY (FEET/SEC.) = 10.14
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11921.00 = 14286.85 FEET.

 FLOW PROCESS FROM NODE 11921.00 TO NODE 11922.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 827.94 DOWNSTREAM (FEET) = 753.55
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1886.43 CHANNEL SLOPE = 0.0394
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 5.78
 * 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.373

SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 344.27 0.30 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 1396.39
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 11.27
 AVERAGE FLOW DEPTH (FEET) = 5.76 TRAVEL TIME (MIN.) = 2.79
 Tc (MIN.) = 39.20
 SUBAREA AREA (ACRES) = 344.27 SUBAREA RUNOFF (CFS) = 332.46
 EFFECTIVE AREA (ACRES) = 1553.71 AREA-AVERAGED Fm (INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 1556.5 PEAK FLOW RATE(CFS) = 1502.51
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 5.96

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 5.96 FLOW VELOCITY(FEET/SEC.) = 11.49
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11922.00 = 16173.28 FEET.

FLOW PROCESS FROM NODE 11922.00 TO NODE 11923.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 753.55 DOWNSTREAM(FEET) = 641.58
CHANNEL LENGTH THRU SUBAREA(FEET) = 2860.88 CHANNEL SLOPE = 0.0391
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 6.13
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.306
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	165.18	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1577.30
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.60
AVERAGE FLOW DEPTH(FEET) = 6.12 TRAVEL TIME(MIN.) = 4.11
Tc(MIN.) = 43.31
SUBAREA AREA(ACRES) = 165.18 SUBAREA RUNOFF(CFS) = 149.58
EFFECTIVE AREA(ACRES) = 1718.89 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 1721.7 PEAK FLOW RATE(CFS) = 1558.63
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 6.08

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 6.08 FLOW VELOCITY(FEET/SEC.) = 11.56
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11923.00 = 19034.16 FEET.

FLOW PROCESS FROM NODE 11923.00 TO NODE 11924.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 641.58 DOWNSTREAM(FEET) = 579.89
CHANNEL LENGTH THRU SUBAREA(FEET) = 1844.02 CHANNEL SLOPE = 0.0335
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 6.68
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.264
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	165.18	0.30	1.000	-

LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 433.73 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1746.79
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.23
AVERAGE FLOW DEPTH(FEET) = 6.67 TRAVEL TIME(MIN.) = 2.74
Tc(MIN.) = 46.04
SUBAREA AREA(ACRES) = 433.73 SUBAREA RUNOFF(CFS) = 376.31
EFFECTIVE AREA(ACRES) = 2152.62 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 2155.4 PEAK FLOW RATE(CFS) = 1869.76
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 6.88

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 6.88 FLOW VELOCITY(FEET/SEC.) = 11.44
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11924.00 = 20878.18 FEET.

FLOW PROCESS FROM NODE 11924.00 TO NODE 11925.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 579.89 DOWNSTREAM(FEET) = 494.12
CHANNEL LENGTH THRU SUBAREA(FEET) = 2756.15 CHANNEL SLOPE = 0.0311
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 7.20
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.202

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	265.42	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1977.47
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.30
AVERAGE FLOW DEPTH(FEET) = 7.18 TRAVEL TIME(MIN.) = 4.07
Tc(MIN.) = 50.11
SUBAREA AREA(ACRES) = 265.42 SUBAREA RUNOFF(CFS) = 215.41
EFFECTIVE AREA(ACRES) = 2418.04 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 2420.9 PEAK FLOW RATE(CFS) = 1964.49
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 7.16

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 7.16 FLOW VELOCITY(FEET/SEC.) = 11.28
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11925.00 = 23634.33 FEET.

FLOW PROCESS FROM NODE 11925.00 TO NODE 11926.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 494.12 DOWNSTREAM(FEET) = 458.40
CHANNEL LENGTH THRU SUBAREA(FEET) = 1922.70 CHANNEL SLOPE = 0.0186
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 8.15
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.160
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	97.46	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2002.19
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.35
AVERAGE FLOW DEPTH(FEET) = 8.14 TRAVEL TIME(MIN.) = 3.43
Tc(MIN.) = 53.53
SUBAREA AREA(ACRES) = 97.46 SUBAREA RUNOFF(CFS) = 75.40
EFFECTIVE AREA(ACRES) = 2515.50 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 2518.3 PEAK FLOW RATE(CFS) = 1964.49
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 8.07

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 8.07 FLOW VELOCITY(FEET/SEC.) = 9.30
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11926.00 = 25557.03 FEET.

FLOW PROCESS FROM NODE 11926.00 TO NODE 11927.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 458.40 DOWNSTREAM(FEET) = 399.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 2170.13 CHANNEL SLOPE = 0.0274
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 7.42
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.118
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	53.83	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1984.31
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.78
AVERAGE FLOW DEPTH(FEET) = 7.41 TRAVEL TIME(MIN.) = 3.35
Tc(MIN.) = 56.89
SUBAREA AREA(ACRES) = 53.83 SUBAREA RUNOFF(CFS) = 39.65
EFFECTIVE AREA(ACRES) = 2569.33 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 2572.1 PEAK FLOW RATE(CFS) = 1964.49
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 7.38

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 7.38 FLOW VELOCITY(FEET/SEC.) = 10.75
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 27727.16 FEET.

FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<

FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<

=====

PEAK FLOWRATE TABLE FILE NAME: P401XX25.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	738.86	26.31	0.30(0.30)	1.00	624.3	40130.00
2	730.65	28.19	0.30(0.30)	1.00	654.2	40100.00
TOTAL AREA(ACRES) =						654.2

FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1964.49	56.89	1.118	0.30(0.30)	1.00	2569.3	11900.00
2	1962.33	57.06	1.116	0.30(0.30)	1.00	2572.1	11910.00
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 27727.16 FEET.							

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	738.86	26.31	1.718	0.30(0.30)	1.00	624.3	40130.00
2	730.65	28.19	1.635	0.30(0.30)	1.00	654.2	40100.00
LONGEST FLOWPATH FROM NODE 40100.00 TO NODE 11927.00 = 10245.00 FEET.							

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2312.56	26.31	1.718	0.30(0.30)	1.00	1812.4	40130.00
2	2318.12	28.19	1.635	0.30(0.30)	1.00	1927.4	40100.00
3	2412.36	56.89	1.118	0.30(0.30)	1.00	3223.5	11900.00
4	2409.06	57.06	1.116	0.30(0.30)	1.00	3226.4	11910.00
TOTAL AREA(ACRES) =						3226.4	

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
PEAK FLOW RATE(CFS) = 2412.36 Tc(MIN.) = 56.889

EFFECTIVE AREA(ACRES) = 3223.53 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 3226.4
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 27727.16 FEET.

FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<<

FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 399.00 DOWNSTREAM(FEET) = 384.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 986.26 CHANNEL SLOPE = 0.0152
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 9.28
CHANNEL FLOW THRU SUBAREA(CFS) = 2412.36
FLOW VELOCITY(FEET/SEC.) = 9.10 FLOW DEPTH(FEET) = 9.28
TRAVEL TIME(MIN.) = 1.81 Tc(MIN.) = 58.69
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.50 = 28713.42 FEET.

FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<

MAINLINE Tc(MIN.) = 58.69
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.096
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"WOODLAND,GRASS" B 2.40 0.30 1.000 65
NATURAL FAIR COVER
"WOODLAND,GRASS" B 1.70 0.30 1.000 65
NATURAL FAIR COVER
"WOODLAND,GRASS" B 1.50 0.30 1.000 65
NATURAL FAIR COVER
"OPEN BRUSH" B 1.30 0.30 1.000 66
NATURAL FAIR COVER
"OPEN BRUSH" B 0.90 0.30 1.000 66
NATURAL FAIR COVER
"GRASS" B 0.60 0.30 1.000 69
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 8.40 SUBAREA RUNOFF(CFS) = 6.02
EFFECTIVE AREA(ACRES) = 3231.93 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 3234.8 PEAK FLOW RATE(CFS) = 2412.36
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<

MAINLINE Tc(MIN.) = 58.69
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.096
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"OPEN BRUSH" B 0.30 0.30 1.000 66
NATURAL FAIR COVER
"OPEN BRUSH" B 0.10 0.30 1.000 66
NATURAL FAIR COVER
"WOODLAND,GRASS" B 0.10 0.30 1.000 65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 0.50 SUBAREA RUNOFF(CFS) = 0.36
EFFECTIVE AREA(ACRES) = 3232.43 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 3235.2 PEAK FLOW RATE(CFS) = 2412.36
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<

MAINLINE Tc(MIN.) = 58.69
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.096
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"WOODLAND,GRASS" B 0.80 0.30 1.000 65
NATURAL FAIR COVER
"WOODLAND,GRASS" B 0.70 0.30 1.000 65
NATURAL FAIR COVER
"OPEN BRUSH" B 0.20 0.30 1.000 66
NATURAL FAIR COVER
"WOODLAND,GRASS" B 0.20 0.30 1.000 65
NATURAL FAIR COVER
"OPEN BRUSH" B 0.10 0.30 1.000 66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 2.00 SUBAREA RUNOFF(CFS) = 1.43
EFFECTIVE AREA(ACRES) = 3234.43 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 3237.2 PEAK FLOW RATE(CFS) = 2412.36
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 11927.50 TO NODE 11928.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 384.00 DOWNSTREAM(FEET) = 359.00

CHANNEL LENGTH THRU SUBAREA (FEET) = 647.19 CHANNEL SLOPE = 0.0386
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 7.53
 * 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.086
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	78.01	0.30	0.984	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.984
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 2440.11
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 12.92
 AVERAGE FLOW DEPTH (FEET) = 7.53 TRAVEL TIME (MIN.) = 0.84
 Tc (MIN.) = 59.53
 SUBAREA AREA (ACRES) = 78.01 SUBAREA RUNOFF (CFS) = 55.51
 EFFECTIVE AREA (ACRES) = 3312.44 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 3315.3 PEAK FLOW RATE (CFS) = 2412.36
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 7.49

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 7.49 FLOW VELOCITY (FEET/SEC.) = 12.88
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11928.00 = 29360.61 FEET.

 FLOW PROCESS FROM NODE 11928.00 TO NODE 11928.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) = 59.53
 * 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.086
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "WOODLAND, GRASS"	B	1.10	0.30	1.000	65
NATURAL FAIR COVER "OPEN BRUSH"	B	0.60	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 1.70 SUBAREA RUNOFF (CFS) = 1.20
 EFFECTIVE AREA (ACRES) = 3314.14 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 3317.0 PEAK FLOW RATE (CFS) = 2412.36
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 359.00 DOWNSTREAM (FEET) = 341.63
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1322.66 CHANNEL SLOPE = 0.0131

GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 9.59
 * 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.068
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.18	0.30	0.890	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.890
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 2415.31
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.62
 AVERAGE FLOW DEPTH (FEET) = 9.59 TRAVEL TIME (MIN.) = 2.56
 Tc (MIN.) = 62.09
 SUBAREA AREA (ACRES) = 8.18 SUBAREA RUNOFF (CFS) = 5.90
 EFFECTIVE AREA (ACRES) = 3322.32 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 3325.1 PEAK FLOW RATE (CFS) = 2412.36
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 9.59

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 9.59 FLOW VELOCITY (FEET/SEC.) = 8.62
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11929.00 = 30683.27 FEET.

 FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) = 62.09
 * 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.068
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	1.90	0.30	1.000	66
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.60	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 2.50 SUBAREA RUNOFF (CFS) = 1.73
 EFFECTIVE AREA (ACRES) = 3324.82 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 3327.6 PEAK FLOW RATE (CFS) = 2412.36
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 3 <<<<

 FLOW PROCESS FROM NODE 11841.00 TO NODE 12527.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: S18X25.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	16891.05	38.90	0.30 (0.30)	1.00	7699.7	11831.00
2	17269.04	41.07	0.30 (0.30)	1.00	8149.8	11801.00
3	19484.28	52.56	0.30 (0.30)	1.00	11111.4	11530.00
4	20384.42	59.71	0.30 (0.30)	1.00	13605.9	11000.00
5	22298.73	70.25	0.30 (0.30)	1.00	18738.3	11330.00
6	22627.08	72.15	0.30 (0.30)	1.00	19721.6	11350.00
7	22975.81	75.44	0.30 (0.30)	1.00	21433.1	11300.00
8	23115.65	77.03	0.30 (0.30)	1.00	22200.3	11130.00
9	22643.41	86.92	0.30 (0.30)	1.00	25590.3	11620.00
10	22485.53	89.04	0.30 (0.30)	1.00	26262.8	11600.00
11	22019.00	94.91	0.30 (0.30)	1.00	27853.1	11111.00
12	21832.20	97.18	0.30 (0.30)	1.00	28360.1	10500.00
13	21473.90	101.65	0.30 (0.30)	1.00	29218.6	10710.00
14	21235.80	103.95	0.30 (0.30)	1.00	29569.4	10410.00
15	20918.29	108.69	0.30 (0.30)	1.00	30244.3	10700.00
16	20477.99	115.41	0.30 (0.30)	1.00	31136.9	10400.00
17	20244.15	118.03	0.30 (0.30)	1.00	31425.5	10200.00
18	19628.83	124.41	0.30 (0.30)	1.00	32019.9	10300.00
19	19047.00	129.43	0.30 (0.30)	1.00	32209.8	10210.00
20	16600.03	158.26	0.30 (0.30)	1.00	32916.6	10100.00

TOTAL AREA (ACRES) = 32916.6

FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: S25X25.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	5840.09	69.19	0.30 (0.30)	0.99	6331.6	12500.00
2	6596.78	83.06	0.30 (0.30)	0.99	8310.4	12300.00
3	6685.50	84.54	0.30 (0.30)	0.98	8607.7	12330.00
4	6818.17	87.39	0.30 (0.30)	0.98	9133.8	12410.00
5	6967.16	91.70	0.30 (0.29)	0.98	9855.5	12400.00
6	7051.85	96.73	0.30 (0.29)	0.98	10551.8	12211.00
7	7157.86	100.97	0.30 (0.29)	0.98	11151.2	12201.00
8	7157.25	105.22	0.30 (0.29)	0.98	11623.9	12111.00
9	7110.02	108.20	0.30 (0.29)	0.98	11957.2	12231.00
10	7048.35	111.16	0.30 (0.29)	0.98	12251.1	12101.10
11	7025.02	112.24	0.30 (0.29)	0.98	12348.3	12261.00
12	6564.46	124.38	0.30 (0.29)	0.98	13114.4	12010.00
13	6112.24	133.26	0.30 (0.29)	0.98	13237.1	12000.00

TOTAL AREA (ACRES) = 13237.1

FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	5840.09	69.19	0.30 (0.30)	0.99	6331.6	12500.00
2	6596.78	83.06	0.30 (0.30)	0.99	8310.4	12300.00
3	6685.50	84.54	0.30 (0.30)	0.98	8607.7	12330.00
4	6818.17	87.39	0.30 (0.30)	0.98	9133.8	12410.00
5	6967.16	91.70	0.30 (0.29)	0.98	9855.5	12400.00
6	7051.85	96.73	0.30 (0.29)	0.98	10551.8	12211.00
7	7157.86	100.97	0.30 (0.29)	0.98	11151.2	12201.00
8	7157.25	105.22	0.30 (0.29)	0.98	11623.9	12111.00
9	7110.02	108.20	0.30 (0.29)	0.98	11957.2	12231.00
10	7048.35	111.16	0.30 (0.29)	0.98	12251.1	12101.10
11	7025.02	112.24	0.30 (0.29)	0.98	12348.3	12261.00
12	6564.46	124.38	0.30 (0.29)	0.98	13114.4	12010.00
13	6112.24	133.26	0.30 (0.29)	0.98	13237.1	12000.00

TOTAL AREA (ACRES) = 13237.1

FLOW PROCESS FROM NODE 11841.00 TO NODE 12527.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	5840.09	69.19	1.029	0.30 (0.30)	0.99	6331.6	12500.00
2	6596.78	83.06	0.951	0.30 (0.30)	0.99	8310.4	12300.00
3	6685.50	84.54	0.943	0.30 (0.30)	0.98	8607.7	12330.00
4	6818.17	87.39	0.927	0.30 (0.30)	0.98	9133.8	12410.00
5	6967.16	91.70	0.906	0.30 (0.29)	0.98	9855.5	12400.00
6	7051.85	96.73	0.888	0.30 (0.29)	0.98	10551.8	12211.00
7	7157.86	100.97	0.872	0.30 (0.29)	0.98	11151.2	12201.00
8	7157.25	105.22	0.857	0.30 (0.29)	0.98	11623.9	12111.00
9	7110.02	108.20	0.846	0.30 (0.29)	0.98	11957.2	12231.00
10	7048.35	111.16	0.835	0.30 (0.29)	0.98	12251.1	12101.10
11	7025.02	112.24	0.831	0.30 (0.29)	0.98	12348.3	12261.00
12	6564.46	124.38	0.794	0.30 (0.29)	0.98	13114.4	12010.00
13	6112.24	133.26	0.774	0.30 (0.29)	0.98	13237.1	12000.00

LONGEST FLOWPATH FROM NODE 12000.00 TO NODE 12527.00 = 77156.98 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	16891.05	38.90	1.379	0.30 (0.30)	1.00	7699.7	11831.00
2	17269.04	41.07	1.340	0.30 (0.30)	1.00	8149.8	11801.00
3	19484.28	52.56	1.172	0.30 (0.30)	1.00	11111.4	11530.00
4	20384.42	59.71	1.084	0.30 (0.30)	1.00	13605.9	11000.00
5	22298.73	70.25	1.023	0.30 (0.30)	1.00	18738.3	11330.00
6	22627.08	72.15	1.012	0.30 (0.30)	1.00	19721.6	11350.00
7	22975.81	75.44	0.994	0.30 (0.30)	1.00	21433.1	11300.00
8	23115.65	77.03	0.985	0.30 (0.30)	1.00	22200.3	11130.00
9	22643.41	86.92	0.929	0.30 (0.30)	1.00	25590.3	11620.00
10	22485.53	89.04	0.917	0.30 (0.30)	1.00	26262.8	11600.00
11	22019.00	94.91	0.894	0.30 (0.30)	1.00	27853.1	11111.00
12	21832.20	97.18	0.886	0.30 (0.30)	1.00	28360.1	10500.00
13	21473.90	101.65	0.870	0.30 (0.30)	1.00	29218.6	10710.00

14 21235.80 103.95 0.861 0.30(0.30) 1.00 29569.4 10410.00
 15 20918.29 108.69 0.844 0.30(0.30) 1.00 30244.3 10700.00
 16 20477.99 115.41 0.820 0.30(0.30) 1.00 31136.9 10400.00
 17 20244.15 118.03 0.810 0.30(0.30) 1.00 31425.5 10200.00
 18 19628.83 124.41 0.793 0.30(0.30) 1.00 32019.9 10300.00
 19 19047.00 129.43 0.783 0.30(0.30) 1.00 32209.8 10210.00
 20 16600.03 158.26 0.720 0.30(0.30) 1.00 32916.6 10100.00
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12527.00 = 97868.13 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21744.22	38.90	1.379	0.30(0.30)	0.99	11259.4	11831.00
2	22212.18	41.07	1.340	0.30(0.30)	0.99	11908.7	11801.00
3	24786.46	52.56	1.172	0.30(0.30)	0.99	15920.9	11530.00
4	25802.98	59.71	1.084	0.30(0.30)	0.99	19070.2	11000.00
5	27946.32	69.19	1.029	0.30(0.30)	0.99	24553.8	12500.00
6	28196.63	70.25	1.023	0.30(0.30)	0.99	25221.1	11330.00
7	28628.91	72.15	1.012	0.30(0.30)	0.99	26476.2	11350.00
8	29156.91	75.44	0.994	0.30(0.30)	0.99	28656.5	11300.00
9	29383.42	77.03	0.985	0.30(0.30)	0.99	29650.4	11130.00
10	29424.60	83.06	0.951	0.30(0.30)	0.99	32577.0	12300.00
11	29442.55	84.54	0.943	0.30(0.30)	0.99	33382.3	12330.00
12	29439.82	86.92	0.929	0.30(0.30)	0.99	34637.9	11620.00
13	29426.78	87.39	0.927	0.30(0.30)	0.99	34872.4	12410.00
14	29360.88	89.04	0.917	0.30(0.30)	0.99	35673.5	11600.00
15	29241.66	91.70	0.906	0.30(0.30)	0.99	36837.6	12400.00
16	29040.22	94.91	0.894	0.30(0.30)	0.99	38153.0	11111.00
17	28921.00	96.73	0.888	0.30(0.30)	0.99	38811.6	12211.00
18	28895.27	97.18	0.886	0.30(0.30)	0.99	38975.3	10500.00
19	28686.30	100.97	0.872	0.30(0.30)	0.99	40239.2	12201.00
20	28631.67	101.65	0.870	0.30(0.30)	0.99	40445.6	10710.00
21	28393.24	103.95	0.861	0.30(0.30)	0.99	41052.8	10410.00
22	28308.43	105.22	0.857	0.30(0.30)	0.99	41373.2	12111.00
23	28060.91	108.20	0.846	0.30(0.30)	0.99	42132.2	12231.00
24	28018.20	108.69	0.844	0.30(0.30)	0.99	42249.7	10700.00
25	27804.43	111.16	0.835	0.30(0.30)	0.99	42824.2	12101.10
26	27710.28	112.24	0.831	0.30(0.30)	0.99	43065.0	12261.00
27	27382.95	115.41	0.820	0.30(0.30)	0.99	43684.9	10400.00
28	27049.59	118.03	0.810	0.30(0.30)	0.99	44139.1	10200.00
29	26196.32	124.38	0.794	0.30(0.30)	0.99	45131.3	12010.00
30	26191.70	124.41	0.793	0.30(0.30)	0.99	45134.7	10300.00
31	25354.30	129.43	0.783	0.30(0.30)	0.99	45393.9	10210.00
32	24834.19	133.26	0.774	0.30(0.30)	0.99	45540.7	12000.00
33	22023.28	158.26	0.720	0.30(0.30)	0.99	46153.7	10100.00

TOTAL AREA (ACRES) = 46153.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 29442.55 Tc (MIN.) = 84.542
 EFFECTIVE AREA (ACRES) = 33382.26 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 46153.7
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12527.00 = 97868.13 FEET.

 FLOW PROCESS FROM NODE 12527.00 TO NODE 11929.00 IS CODE = 56

 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 347.47 DOWNSTREAM (FEET) = 341.63
 CHANNEL LENGTH THRU SUBAREA (FEET) = 532.38 CHANNEL SLOPE = 0.0110
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT (FEET) = 8.43
 * 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.939
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	14.37	0.30	0.987	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.987
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 29446.71
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 14.43
 AVERAGE FLOW DEPTH (FEET) = 8.43 TRAVEL TIME (MIN.) = 0.61
 Tc (MIN.) = 85.16
 SUBAREA AREA (ACRES) = 14.37 SUBAREA RUNOFF (CFS) = 8.32
 EFFECTIVE AREA (ACRES) = 33396.63 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 46168.0 PEAK FLOW RATE (CFS) = 29442.55
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT (FEET) = 8.43

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 8.43 FLOW VELOCITY (FEET/SEC.) = 14.43
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

 FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21744.22	39.58	1.365	0.30(0.30)	0.99	11273.8	11831.00
2	22212.18	41.75	1.330	0.30(0.30)	0.99	11923.1	11801.00
3	24786.46	53.21	1.164	0.30(0.30)	0.99	15935.3	11530.00
4	25802.98	60.35	1.078	0.30(0.30)	0.99	19084.6	11000.00
5	27946.32	69.81	1.025	0.30(0.30)	0.99	24568.2	12500.00
6	28196.63	70.87	1.019	0.30(0.30)	0.99	25235.5	11330.00
7	28628.91	72.77	1.008	0.30(0.30)	0.99	26490.6	11350.00
8	29156.91	76.06	0.990	0.30(0.30)	0.99	28670.9	11300.00
9	29383.42	77.64	0.981	0.30(0.30)	0.99	29664.8	11130.00
10	29424.60	83.67	0.947	0.30(0.30)	0.99	32591.4	12300.00
11	29442.55	85.16	0.939	0.30(0.30)	0.99	33396.6	12330.00
12	29439.82	87.54	0.926	0.30(0.30)	0.99	34652.2	11620.00
13	29426.78	88.01	0.923	0.30(0.30)	0.99	34886.8	12410.00
14	29360.88	89.66	0.914	0.30(0.30)	0.99	35687.9	11600.00
15	29241.66	92.31	0.904	0.30(0.30)	0.99	36852.0	12400.00
16	29040.22	95.53	0.892	0.30(0.30)	0.99	38167.4	11111.00
17	28921.00	97.35	0.885	0.30(0.30)	0.99	38826.0	12211.00
18	28895.27	97.80	0.884	0.30(0.30)	0.99	38989.7	10500.00

19	28686.30	101.59	0.870	0.30(0.30)	0.99	40253.5	12201.00
20	28631.67	102.27	0.867	0.30(0.30)	0.99	40460.0	10710.00
21	28393.24	104.58	0.859	0.30(0.30)	0.99	41067.2	10410.00
22	28308.43	105.84	0.854	0.30(0.30)	0.99	41387.6	12111.00
23	28060.91	108.83	0.844	0.30(0.30)	0.99	42146.6	12231.00
24	28018.20	109.31	0.842	0.30(0.30)	0.99	42264.1	10700.00
25	27804.43	111.79	0.833	0.30(0.30)	0.99	42838.6	12101.10
26	27710.28	112.87	0.829	0.30(0.30)	0.99	43079.4	12261.00
27	27382.95	116.04	0.817	0.30(0.30)	0.99	43699.3	10400.00
28	27049.59	118.66	0.808	0.30(0.30)	0.99	44153.4	10200.00
29	26196.32	125.02	0.792	0.30(0.30)	0.99	45145.7	12010.00
30	26191.70	125.05	0.792	0.30(0.30)	0.99	45149.1	10300.00
31	25354.30	130.08	0.781	0.30(0.30)	0.99	45408.3	10210.00
32	24834.19	133.91	0.773	0.30(0.30)	0.99	45555.1	12000.00
33	22023.28	158.94	0.719	0.30(0.30)	0.99	46168.0	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

**** MEMORY BANK # 3 CONFLUENCE DATA ****

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2312.56	31.56	1.524	0.30(0.30)	1.00	1913.7	40130.00
2	2318.12	33.44	1.487	0.30(0.30)	1.00	2028.7	40100.00
3	2412.36	62.09	1.068	0.30(0.30)	1.00	3324.8	11900.00
4	2409.06	62.26	1.067	0.30(0.30)	1.00	3327.6	11910.00

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11929.00 = 30683.27 FEET.

**** PEAK FLOW RATE TABLE ****

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22229.05	31.56	1.524	0.30(0.30)	0.99	10902.5	40130.00
2	22780.82	33.44	1.487	0.30(0.30)	0.99	11553.3	40100.00
3	24082.55	39.58	1.365	0.30(0.30)	0.99	13580.4	11831.00
4	24557.65	41.75	1.330	0.30(0.30)	0.99	14327.9	11801.00
5	27169.61	53.21	1.164	0.30(0.30)	0.99	18858.4	11530.00
6	28209.64	60.35	1.078	0.30(0.30)	0.99	22331.0	11000.00
7	28607.78	62.09	1.068	0.30(0.30)	0.99	23413.4	11900.00
8	28643.17	62.26	1.067	0.30(0.30)	0.99	23515.2	11910.00
9	30222.67	69.81	1.025	0.30(0.30)	0.99	27895.8	12500.00
10	30454.41	70.87	1.019	0.30(0.30)	0.99	28563.1	11330.00
11	30853.30	72.77	1.008	0.30(0.30)	0.99	29818.2	11350.00
12	31323.67	76.06	0.990	0.30(0.30)	0.99	31998.5	11300.00
13	31522.31	77.64	0.981	0.30(0.30)	0.99	32992.4	11130.00
14	31457.60	83.67	0.947	0.30(0.30)	0.99	35919.0	12300.00
15	31449.52	85.16	0.939	0.30(0.30)	0.99	36724.3	12330.00
16	31404.98	87.54	0.926	0.30(0.30)	0.99	37979.9	11620.00
17	31383.73	88.01	0.923	0.30(0.30)	0.99	38214.4	12410.00
18	31288.81	89.66	0.914	0.30(0.30)	0.99	39015.5	11600.00
19	31137.25	92.31	0.904	0.30(0.30)	0.99	40179.6	12400.00
20	30899.19	95.53	0.892	0.30(0.30)	0.99	41495.0	11111.00
21	30759.23	97.35	0.885	0.30(0.30)	0.99	42153.6	12211.00
22	30728.38	97.80	0.884	0.30(0.30)	0.99	42317.4	10500.00
23	30476.18	101.59	0.870	0.30(0.30)	0.99	43581.2	12201.00
24	30413.79	102.27	0.867	0.30(0.30)	0.99	43787.7	10710.00
25	30149.10	104.58	0.859	0.30(0.30)	0.99	44394.9	10410.00
26	30049.92	105.84	0.854	0.30(0.30)	0.99	44715.2	12111.00
27	29768.36	108.83	0.844	0.30(0.30)	0.99	45474.2	12231.00
28	29720.11	109.31	0.842	0.30(0.30)	0.99	45591.7	10700.00
29	29478.12	111.79	0.833	0.30(0.30)	0.99	46166.3	12101.10

30	29371.65	112.87	0.829	0.30(0.30)	0.99	46407.0	12261.00
31	29008.24	116.04	0.817	0.30(0.30)	0.99	47026.9	10400.00
32	28644.99	118.66	0.808	0.30(0.30)	0.99	47481.1	10200.00
33	27742.38	125.02	0.792	0.30(0.30)	0.99	48473.4	12010.00
34	27737.54	125.05	0.792	0.30(0.30)	0.99	48476.7	10300.00
35	26866.01	130.08	0.781	0.30(0.30)	0.99	48735.9	10210.00
36	26319.85	133.91	0.773	0.30(0.30)	0.99	48882.8	12000.00
37	23338.91	158.94	0.719	0.30(0.30)	0.99	49495.7	10100.00
TOTAL AREA(ACRES) =							49495.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 31522.31 Tc(MIN.) = 77.644
 EFFECTIVE AREA(ACRES) = 32992.41 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 49495.7
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 49495.7 TC(MIN.) = 77.64
 EFFECTIVE AREA(ACRES) = 32992.41 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.994
 PEAK FLOW RATE(CFS) = 31522.31

**** PEAK FLOW RATE TABLE ****

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22229.05	31.56	1.524	0.30(0.30)	0.99	10902.5	40130.00
2	22780.82	33.44	1.487	0.30(0.30)	0.99	11553.3	40100.00
3	24082.55	39.58	1.365	0.30(0.30)	0.99	13580.4	11831.00
4	24557.65	41.75	1.330	0.30(0.30)	0.99	14327.9	11801.00
5	27169.61	53.21	1.164	0.30(0.30)	0.99	18858.4	11530.00
6	28209.64	60.35	1.078	0.30(0.30)	0.99	22331.0	11000.00
7	28607.78	62.09	1.068	0.30(0.30)	0.99	23413.4	11900.00
8	28643.17	62.26	1.067	0.30(0.30)	0.99	23515.2	11910.00
9	30222.67	69.81	1.025	0.30(0.30)	0.99	27895.8	12500.00
10	30454.41	70.87	1.019	0.30(0.30)	0.99	28563.1	11330.00
11	30853.30	72.77	1.008	0.30(0.30)	0.99	29818.2	11350.00
12	31323.67	76.06	0.990	0.30(0.30)	0.99	31998.5	11300.00
13	31522.31	77.64	0.981	0.30(0.30)	0.99	32992.4	11130.00
14	31457.60	83.67	0.947	0.30(0.30)	0.99	35919.0	12300.00
15	31449.52	85.16	0.939	0.30(0.30)	0.99	36724.3	12330.00
16	31404.98	87.54	0.926	0.30(0.30)	0.99	37979.9	11620.00
17	31383.73	88.01	0.923	0.30(0.30)	0.99	38214.4	12410.00
18	31288.81	89.66	0.914	0.30(0.30)	0.99	39015.5	11600.00
19	31137.25	92.31	0.904	0.30(0.30)	0.99	40179.6	12400.00
20	30899.19	95.53	0.892	0.30(0.30)	0.99	41495.0	11111.00
21	30759.23	97.35	0.885	0.30(0.30)	0.99	42153.6	12211.00
22	30728.38	97.80	0.884	0.30(0.30)	0.99	42317.4	10500.00
23	30476.18	101.59	0.870	0.30(0.30)	0.99	43581.2	12201.00
24	30413.79	102.27	0.867	0.30(0.30)	0.99	43787.7	10710.00
25	30149.10	104.58	0.859	0.30(0.30)	0.99	44394.9	10410.00
26	30049.92	105.84	0.854	0.30(0.30)	0.99	44715.2	12111.00
27	29768.36	108.83	0.844	0.30(0.30)	0.99	45474.2	12231.00
28	29720.11	109.31	0.842	0.30(0.30)	0.99	45591.7	10700.00
29	29478.12	111.79	0.833	0.30(0.30)	0.99	46166.3	12101.10
30	29371.65	112.87	0.829	0.30(0.30)	0.99	46407.0	12261.00
31	29008.24	116.04	0.817	0.30(0.30)	0.99	47026.9	10400.00
32	28644.99	118.66	0.808	0.30(0.30)	0.99	47481.1	10200.00

33	27742.38	125.02	0.792	0.30	(0.30)	0.99	48473.4	12010.00
34	27737.54	125.05	0.792	0.30	(0.30)	0.99	48476.7	10300.00
35	26866.01	130.08	0.781	0.30	(0.30)	0.99	48735.9	10210.00
36	26319.85	133.91	0.773	0.30	(0.30)	0.99	48882.8	12000.00
37	23338.91	158.94	0.719	0.30	(0.30)	0.99	49495.7	10100.00

=====
=====
END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 126 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 25-YR EV FEB 2023 ROKAMOTO *

FILE NAME: RU25EV26.DAT
TIME/DATE OF STUDY: 15:21 02/07/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 25.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 4.985
- 2) 10.00; 3.243
- 3) 15.00; 2.468
- 4) 20.00; 2.035
- 5) 25.00; 1.773
- 6) 30.00; 1.553
- 7) 40.00; 1.354
- 8) 50.00; 1.201
- 9) 60.00; 1.077
- 10) 90.00; 0.909
- 11) 120.00; 0.800
- 12) 180.00; 0.670
- 13) 360.00; 0.498
- 14) 1200.00; 0.220

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER WIDTH (FT)	GEOMETRIES: LIP (FT)	MANNING HIKE (FT)	FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU25EV19.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22780.82	33.44	0.30 (0.30)	0.99	11553.3	40100.00
2	24557.65	41.75	0.30 (0.30)	0.99	14327.9	11801.00
3	27169.61	53.21	0.30 (0.30)	0.99	18858.4	11530.00
4	28643.17	62.26	0.30 (0.30)	0.99	23515.2	11910.00
5	30853.30	72.77	0.30 (0.30)	0.99	29818.2	11350.00
6	31522.31	77.64	0.30 (0.30)	0.99	32992.4	11130.00
7	31457.60	83.67	0.30 (0.30)	0.99	35919.0	12300.00
8	31404.98	87.54	0.30 (0.30)	0.99	37979.9	11620.00
9	31137.25	92.31	0.30 (0.30)	0.99	40179.6	12400.00
10	30899.19	95.53	0.30 (0.30)	0.99	41495.0	11111.00
11	30476.18	101.59	0.30 (0.30)	0.99	43581.2	12201.00
12	30149.10	104.58	0.30 (0.30)	0.99	44394.9	10410.00
13	29768.36	108.83	0.30 (0.30)	0.99	45474.2	12231.00
14	29478.12	111.79	0.30 (0.30)	0.99	46166.3	12101.10
15	29008.24	116.04	0.30 (0.30)	0.99	47026.9	10400.00
16	28644.99	118.66	0.30 (0.30)	0.99	47481.1	10200.00
17	27742.38	125.02	0.30 (0.30)	0.99	48473.4	12010.00
18	26866.01	130.08	0.30 (0.30)	0.99	48735.9	10210.00
19	26319.85	133.91	0.30 (0.30)	0.99	48882.8	12000.00
20	23338.91	158.94	0.30 (0.30)	0.99	49495.7	10100.00
TOTAL AREA (ACRES) =						49495.7

FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22780.82	33.44	0.30 (0.30)	0.99	11553.3	40100.00
2	24557.65	41.75	0.30 (0.30)	0.99	14327.9	11801.00
3	27169.61	53.21	0.30 (0.30)	0.99	18858.4	11530.00
4	28643.17	62.26	0.30 (0.30)	0.99	23515.2	11910.00
5	30853.30	72.77	0.30 (0.30)	0.99	29818.2	11350.00
6	31522.31	77.64	0.30 (0.30)	0.99	32992.4	11130.00
7	31457.60	83.67	0.30 (0.30)	0.99	35919.0	12300.00
8	31404.98	87.54	0.30 (0.30)	0.99	37979.9	11620.00
9	31137.25	92.31	0.30 (0.30)	0.99	40179.6	12400.00
10	30899.19	95.53	0.30 (0.30)	0.99	41495.0	11111.00
11	30476.18	101.59	0.30 (0.30)	0.99	43581.2	12201.00
12	30149.10	104.58	0.30 (0.30)	0.99	44394.9	10410.00
13	29768.36	108.83	0.30 (0.30)	0.99	45474.2	12231.00

14 29478.12 111.79 0.30(0.30) 0.99 46166.3 12101.10
 15 29008.24 116.04 0.30(0.30) 0.99 47026.9 10400.00
 16 28644.99 118.66 0.30(0.30) 0.99 47481.1 10200.00
 17 27742.38 125.02 0.30(0.30) 0.99 48473.4 12010.00
 18 26866.01 130.08 0.30(0.30) 0.99 48735.9 10210.00
 19 26319.85 133.91 0.30(0.30) 0.99 48882.8 12000.00
 20 23338.91 158.94 0.30(0.30) 0.99 49495.7 10100.00
 TOTAL AREA(ACRES) = 49495.7

FLOW PROCESS FROM NODE 11929.00 TO NODE 12601.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 341.63 DOWNSTREAM(FEET) = 325.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1467.93 CHANNEL SLOPE = 0.0113
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 7.37

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.971

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	0.40	0.30	1.000	66
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.50	0.30	1.000	65
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	B	0.90	0.30	1.000	63
NATURAL FAIR COVER "GRASS"	B	0.50	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	11.50	0.30	1.000	66
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.30	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 31526.56

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 18.07

AVERAGE FLOW DEPTH(FEET) = 7.37 TRAVEL TIME(MIN.) = 1.35

Tc(MIN.) = 79.00

SUBAREA AREA(ACRES) = 14.10 SUBAREA RUNOFF(CFS) = 8.51

EFFECTIVE AREA(ACRES) = 33006.52 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 49509.8 PEAK FLOW RATE(CFS) = 31522.31

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT(FEET) = 7.37

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 7.37 FLOW VELOCITY(FEET/SEC.) = 18.07

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap (ACRES)	Ae (ACRES)	HEADWATER NODE
------------------	------------	--------------	------------------------	---------------------	---------------	---------------	-------------------

1	22780.82	34.95	1.454	0.30(0.30)	0.99	11567.4	40100.00
2	24557.65	43.23	1.305	0.30(0.30)	0.99	14342.0	11801.00
3	27169.61	54.63	1.144	0.30(0.30)	0.99	18872.5	11530.00
4	28643.17	63.66	1.057	0.30(0.30)	0.99	23529.3	11910.00
5	30853.30	74.14	0.998	0.30(0.30)	0.99	29832.3	11350.00
6	31522.31	79.00	0.971	0.30(0.30)	0.99	33006.5	11130.00
7	31457.60	85.03	0.937	0.30(0.30)	0.99	35933.1	12300.00
8	31404.98	88.89	0.915	0.30(0.30)	0.99	37994.0	11620.00
9	31137.25	93.67	0.896	0.30(0.30)	0.99	40193.7	12400.00
10	30899.19	96.89	0.884	0.30(0.30)	0.99	41509.1	11111.00
11	30476.18	102.96	0.862	0.30(0.30)	0.99	43595.3	12201.00
12	30149.10	105.95	0.851	0.30(0.30)	0.99	44409.0	10410.00
13	29768.36	110.21	0.836	0.30(0.30)	0.99	45488.3	12231.00
14	29478.12	113.18	0.825	0.30(0.30)	0.99	46180.4	12101.10
15	29008.24	117.43	0.809	0.30(0.30)	0.99	47041.0	10400.00
16	28644.99	120.06	0.800	0.30(0.30)	0.99	47495.2	10200.00
17	27742.38	126.43	0.786	0.30(0.30)	0.99	48487.5	12010.00
18	26866.01	131.50	0.775	0.30(0.30)	0.99	48750.0	10210.00
19	26319.85	135.35	0.767	0.30(0.30)	0.99	48896.9	12000.00
20	23338.91	160.44	0.712	0.30(0.30)	0.99	49509.8	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 31522.31 Tc(MIN.) = 79.00

AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 33006.52

FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 3025EVRL.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap (ACRES)	Ae (ACRES)	HEADWATER NODE
1	92.92	16.77	0.30(0.29)	0.98	51.1	600.00
TOTAL AREA(ACRES) = 51.1						

FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap (ACRES)	Ae (ACRES)	HEADWATER NODE
1	22780.82	34.95	1.454	0.30(0.30)	0.99	11567.4	40100.00
2	24557.65	43.23	1.305	0.30(0.30)	0.99	14342.0	11801.00
3	27169.61	54.63	1.144	0.30(0.30)	0.99	18872.5	11530.00
4	28643.17	63.66	1.057	0.30(0.30)	0.99	23529.3	11910.00
5	30853.30	74.14	0.998	0.30(0.30)	0.99	29832.3	11350.00
6	31522.31	79.00	0.971	0.30(0.30)	0.99	33006.5	11130.00
7	31457.60	85.03	0.937	0.30(0.30)	0.99	35933.1	12300.00
8	31404.98	88.89	0.915	0.30(0.30)	0.99	37994.0	11620.00
9	31137.25	93.67	0.896	0.30(0.30)	0.99	40193.7	12400.00
10	30899.19	96.89	0.884	0.30(0.30)	0.99	41509.1	11111.00
11	30476.18	102.96	0.862	0.30(0.30)	0.99	43595.3	12201.00
12	30149.10	105.95	0.851	0.30(0.30)	0.99	44409.0	10410.00

13	29768.36	110.21	0.836	0.30	(0.30)	0.99	45488.3	12231.00
14	29478.12	113.18	0.825	0.30	(0.30)	0.99	46180.4	12101.10
15	29008.24	117.43	0.809	0.30	(0.30)	0.99	47041.0	10400.00
16	28644.99	120.06	0.800	0.30	(0.30)	0.99	47495.2	10200.00
17	27742.38	126.43	0.786	0.30	(0.30)	0.99	48487.5	12010.00
18	26866.01	131.50	0.775	0.30	(0.30)	0.99	48750.0	10210.00
19	26319.85	135.35	0.767	0.30	(0.30)	0.99	48896.9	12000.00
20	23338.91	160.44	0.712	0.30	(0.30)	0.99	49509.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	92.92	16.77	2.315	0.30 (0.29)	0.98	51.1	600.00

LONGEST FLOWPATH FROM NODE 600.00 TO NODE 12601.00 = 4850.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19154.32	16.77	2.315	0.30 (0.30)	0.99	5601.9	600.00
2	22834.20	34.95	1.454	0.30 (0.30)	0.99	11618.5	40100.00
3	24604.13	43.23	1.305	0.30 (0.30)	0.99	14393.1	11801.00
4	27208.68	54.63	1.144	0.30 (0.30)	0.99	18923.6	11530.00
5	28678.24	63.66	1.057	0.30 (0.30)	0.99	23580.4	11910.00
6	30885.67	74.14	0.998	0.30 (0.30)	0.99	29883.4	11350.00
7	31553.43	79.00	0.971	0.30 (0.30)	0.99	33057.6	11130.00
8	31487.16	85.03	0.937	0.30 (0.30)	0.99	35984.2	12300.00
9	31433.55	88.89	0.915	0.30 (0.30)	0.99	38045.1	11620.00
10	31164.92	93.67	0.896	0.30 (0.30)	0.99	40244.8	12400.00
11	30926.32	96.89	0.884	0.30 (0.30)	0.99	41560.2	11111.00
12	30502.30	102.96	0.862	0.30 (0.30)	0.99	43646.4	12201.00
13	30174.72	105.95	0.851	0.30 (0.30)	0.99	44460.1	10410.00
14	29793.27	110.21	0.836	0.30 (0.30)	0.99	45539.4	12231.00
15	29502.53	113.18	0.825	0.30 (0.30)	0.99	46231.5	12101.10
16	29031.95	117.43	0.809	0.30 (0.30)	0.99	47092.1	10400.00
17	28668.26	120.06	0.800	0.30 (0.30)	0.99	47546.3	10200.00
18	27765.01	126.43	0.786	0.30 (0.30)	0.99	48538.6	12010.00
19	26888.14	131.50	0.775	0.30 (0.30)	0.99	48801.1	10210.00
20	26341.59	135.35	0.767	0.30 (0.30)	0.99	48948.0	12000.00
21	23358.15	160.44	0.712	0.30 (0.30)	0.99	49560.9	10100.00

TOTAL AREA (ACRES) = 49560.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 31553.43 Tc (MIN.) = 78.998
 EFFECTIVE AREA (ACRES) = 33057.62 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 49560.9
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

FLOW PROCESS FROM NODE 12601.00 TO NODE 12603.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 325.00 DOWNSTREAM (FEET) = 310.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1690.00 CHANNEL SLOPE = 0.0089
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT (FEET) = 7.91
 CHANNEL FLOW THRU SUBAREA (CFS) = 31553.43
 FLOW VELOCITY (FEET/SEC.) = 16.66 FLOW DEPTH (FEET) = 7.91
 TRAVEL TIME (MIN.) = 1.69 Tc (MIN.) = 80.69
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.45 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19154.32	18.78	2.141	0.30 (0.30)	0.99	5601.9	600.00
2	22834.20	36.84	1.417	0.30 (0.30)	0.99	11618.5	40100.00
3	24604.13	45.06	1.277	0.30 (0.30)	0.99	14393.1	11801.00
4	27208.68	56.41	1.122	0.30 (0.30)	0.99	18923.6	11530.00
5	28678.24	65.40	1.047	0.30 (0.30)	0.99	23580.4	11910.00
6	30885.67	75.84	0.988	0.30 (0.30)	0.99	29883.4	11350.00
7	31553.43	80.69	0.961	0.30 (0.30)	0.99	33057.6	11130.00
8	31487.16	86.72	0.927	0.30 (0.30)	0.99	35984.2	12300.00
9	31433.55	90.59	0.907	0.30 (0.30)	0.99	38045.1	11620.00
10	31164.92	95.37	0.889	0.30 (0.30)	0.99	40244.8	12400.00
11	30926.32	98.59	0.878	0.30 (0.30)	0.99	41560.2	11111.00
12	30502.30	104.67	0.856	0.30 (0.30)	0.99	43646.4	12201.00
13	30174.72	107.67	0.845	0.30 (0.30)	0.99	44460.1	10410.00
14	29793.27	111.93	0.829	0.30 (0.30)	0.99	45539.4	12231.00
15	29502.53	114.90	0.819	0.30 (0.30)	0.99	46231.5	12101.10
16	29031.95	119.17	0.803	0.30 (0.30)	0.99	47092.1	10400.00
17	28668.26	121.81	0.796	0.30 (0.30)	0.99	47546.3	10200.00
18	27765.01	128.20	0.782	0.30 (0.30)	0.99	48538.6	12010.00
19	26888.14	133.29	0.771	0.30 (0.30)	0.99	48801.1	10210.00
20	26341.59	137.15	0.763	0.30 (0.30)	0.99	48948.0	12000.00
21	23358.15	162.31	0.708	0.30 (0.30)	0.99	49560.9	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 31553.43 Tc (MIN.) = 80.69
 AREA-AVERAGED Fm (INCH/HR) = 0.30 AREA-AVERAGED Fp (INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA (ACRES) = 33057.62

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 4E25EVRL.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	449.88	9.31	0.30 (0.16)	0.52	148.6	800.00
2	404.95	12.87	0.30 (0.17)	0.57	168.1	818.00
3	381.66	14.01	0.30 (0.17)	0.58	171.0	810.00

TOTAL AREA (ACRES) = 171.0

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 11

=====
>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<
=====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19154.32	18.78	2.141	0.30(0.30)	0.99	5601.9	600.00
2	22834.20	36.84	1.417	0.30(0.30)	0.99	11618.5	40100.00
3	24604.13	45.06	1.277	0.30(0.30)	0.99	14393.1	11801.00
4	27208.68	56.41	1.122	0.30(0.30)	0.99	18923.6	11530.00
5	28678.24	65.40	1.047	0.30(0.30)	0.99	23580.4	11910.00
6	30885.67	75.84	0.988	0.30(0.30)	0.99	29883.4	11350.00
7	31553.43	80.69	0.961	0.30(0.30)	0.99	33057.6	11130.00
8	31487.16	86.72	0.927	0.30(0.30)	0.99	35984.2	12300.00
9	31433.55	90.59	0.907	0.30(0.30)	0.99	38045.1	11620.00
10	31164.92	95.37	0.889	0.30(0.30)	0.99	40244.8	12400.00
11	30926.32	98.59	0.878	0.30(0.30)	0.99	41560.2	11111.00
12	30502.30	104.67	0.856	0.30(0.30)	0.99	43646.4	12201.00
13	30174.72	107.67	0.845	0.30(0.30)	0.99	44460.1	10410.00
14	29793.27	111.93	0.829	0.30(0.30)	0.99	45539.4	12231.00
15	29502.53	114.90	0.819	0.30(0.30)	0.99	46231.5	12101.10
16	29031.95	119.17	0.803	0.30(0.30)	0.99	47092.1	10400.00
17	28668.26	121.81	0.796	0.30(0.30)	0.99	47546.3	10200.00
18	27765.01	128.20	0.782	0.30(0.30)	0.99	48538.6	12010.00
19	26888.14	133.29	0.771	0.30(0.30)	0.99	48801.1	10210.00
20	26341.59	137.15	0.763	0.30(0.30)	0.99	48948.0	12000.00
21	23358.15	162.31	0.708	0.30(0.30)	0.99	49560.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.45 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	449.88	9.31	3.483	0.30(0.16)	0.52	148.6	800.00
2	404.95	12.87	2.798	0.30(0.17)	0.57	168.1	818.00
3	381.66	14.01	2.621	0.30(0.17)	0.58	171.0	810.00

LONGEST FLOWPATH FROM NODE 810.00 TO NODE 12603.00 = 3814.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	16864.99	9.31	3.483	0.30(0.29)	0.97	2926.7	800.00
2	18216.67	12.87	2.798	0.30(0.29)	0.98	4009.3	818.00
3	18400.09	14.01	2.621	0.30(0.29)	0.98	4352.5	810.00
4	19461.16	18.78	2.141	0.30(0.29)	0.98	5772.9	600.00
5	23028.08	36.84	1.417	0.30(0.30)	0.99	11789.5	40100.00
6	24776.11	45.06	1.277	0.30(0.30)	0.99	14564.1	11801.00
7	27356.49	56.41	1.122	0.30(0.30)	0.99	19094.6	11530.00
8	28814.38	65.40	1.047	0.30(0.30)	0.99	23751.4	11910.00
9	31012.69	75.84	0.988	0.30(0.30)	0.99	30054.4	11350.00
10	31676.21	80.69	0.961	0.30(0.30)	0.99	33228.6	11130.00
11	31604.68	86.72	0.927	0.30(0.30)	0.99	36155.2	12300.00
12	31547.87	90.59	0.907	0.30(0.30)	0.99	38216.1	11620.00
13	31276.53	95.37	0.889	0.30(0.30)	0.99	40415.8	12400.00
14	31036.11	98.59	0.878	0.30(0.30)	0.99	41731.2	11111.00
15	30608.64	104.67	0.856	0.30(0.30)	0.99	43817.4	12201.00
16	30279.36	107.67	0.845	0.30(0.30)	0.99	44631.1	10410.00
17	29895.50	111.93	0.829	0.30(0.30)	0.99	45710.4	12231.00

18	29603.07	114.90	0.819	0.30(0.30)	0.99	46402.5	12101.10
19	29130.07	119.17	0.803	0.30(0.30)	0.99	47263.1	10400.00
20	28765.30	121.81	0.796	0.30(0.30)	0.99	47717.3	10200.00
21	27859.89	128.20	0.782	0.30(0.30)	0.99	48709.6	12010.00
22	26981.30	133.29	0.771	0.30(0.30)	0.99	48972.1	10210.00
23	26433.44	137.15	0.763	0.30(0.30)	0.99	49119.0	12000.00
24	23441.50	162.31	0.708	0.30(0.30)	0.99	49731.9	10100.00

TOTAL AREA (ACRES) = 49731.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 31676.21 Tc (MIN.) = 80.688
EFFECTIVE AREA (ACRES) = 33228.62 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 49731.9
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.45 FEET.

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 80.69
* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.961
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.20	0.30	1.000	65
NATURAL FAIR COVER "OPEN BRUSH"	B	1.30	0.30	1.000	66
PUBLIC PARK	B	1.30	0.30	0.850	56
COMMERCIAL RESIDENTIAL ".4 DWELLING/ACRE"	B	1.40	0.30	0.100	56
NATURAL FAIR COVER "OPEN BRUSH"	B	12.40	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.911
SUBAREA AREA (ACRES) = 18.30 SUBAREA RUNOFF (CFS) = 11.33
EFFECTIVE AREA (ACRES) = 33246.92 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 49750.2 PEAK FLOW RATE (CFS) = 31676.21
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 80.69
* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.961
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "WOODLAND, GRASS"	B	26.90	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 26.90 SUBAREA RUNOFF (CFS) = 16.01
 EFFECTIVE AREA (ACRES) = 33273.82 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 49777.1 PEAK FLOW RATE (CFS) = 31676.21
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 80.69
 * 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.961
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	0.50	0.30	1.000	63
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.40	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL, NARROWLEAF"	B	0.40	0.30	1.000	72
NATURAL FAIR COVER					
"GRASS"	B	0.60	0.30	1.000	69
PUBLIC PARK	B	0.70	0.30	0.850	56
NATURAL FAIR COVER					
"CHAPARRAL, NARROWLEAF"	B	0.70	0.30	1.000	72

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.968
 SUBAREA AREA (ACRES) = 3.30 SUBAREA RUNOFF (CFS) = 1.99
 EFFECTIVE AREA (ACRES) = 33277.12 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 49780.4 PEAK FLOW RATE (CFS) = 31676.21
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 80.69
 * 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.961
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.00	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.20	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	1.70	0.30	0.900	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.90	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	2.10	0.30	0.900	56
NATURAL FAIR COVER					
"CHAPARRAL, NARROWLEAF"	B	2.90	0.30	1.000	72

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.965
 SUBAREA AREA (ACRES) = 10.80 SUBAREA RUNOFF (CFS) = 6.53
 EFFECTIVE AREA (ACRES) = 33287.92 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 49791.2 PEAK FLOW RATE (CFS) = 31676.21
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 80.69
 * 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.961
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	5.60	0.30	1.000	65
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	9.00	0.30	1.000	65

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 14.60 SUBAREA RUNOFF (CFS) = 8.69
 EFFECTIVE AREA (ACRES) = 33302.52 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 49805.8 PEAK FLOW RATE (CFS) = 31676.21
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12603.00 TO NODE 12605.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 310.00 DOWNSTREAM (FEET) = 305.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 885.00 CHANNEL SLOPE = 0.0056
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT (FEET) = 9.01
 CHANNEL FLOW THRU SUBAREA (CFS) = 31676.21
 FLOW VELOCITY (FEET/SEC.) = 14.35 FLOW DEPTH (FEET) = 9.01
 TRAVEL TIME (MIN.) = 1.03 Tc (MIN.) = 81.72
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.00 = 102443.45 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	16864.99	10.58	3.153	0.30 (0.29)	0.97	3000.6	800.00
2	18216.67	14.11	2.606	0.30 (0.29)	0.98	4083.2	818.00
3	18400.09	15.25	2.446	0.30 (0.29)	0.98	4426.4	810.00
4	19461.16	19.98	2.036	0.30 (0.29)	0.98	5846.8	600.00
5	23028.08	37.98	1.394	0.30 (0.30)	0.99	11863.4	40100.00
6	24776.11	46.18	1.259	0.30 (0.30)	0.99	14638.0	11801.00
7	27356.49	57.49	1.108	0.30 (0.30)	0.99	19168.5	11530.00
8	28814.38	66.46	1.041	0.30 (0.30)	0.99	23825.3	11910.00
9	31012.69	76.88	0.982	0.30 (0.30)	0.99	30128.3	11350.00
10	31676.21	81.72	0.955	0.30 (0.30)	0.99	33302.5	11130.00

11	31604.68	87.75	0.922	0.30	(0.30)	0.99	36229.1	12300.00
12	31547.87	91.62	0.903	0.30	(0.30)	0.99	38290.0	11620.00
13	31276.53	96.40	0.886	0.30	(0.30)	0.99	40489.7	12400.00
14	31036.11	99.63	0.874	0.30	(0.30)	0.99	41805.1	11111.00
15	30608.64	105.71	0.852	0.30	(0.30)	0.99	43891.3	12201.00
16	30279.36	108.71	0.841	0.30	(0.30)	0.99	44705.0	10410.00
17	29895.50	112.98	0.826	0.30	(0.30)	0.99	45784.3	12231.00
18	29603.07	115.96	0.815	0.30	(0.30)	0.99	46476.4	12101.10
19	29130.07	120.23	0.800	0.30	(0.30)	0.99	47337.0	10400.00
20	28765.30	122.87	0.794	0.30	(0.30)	0.99	47791.2	10200.00
21	27859.89	129.27	0.780	0.30	(0.30)	0.99	48783.5	12010.00
22	26981.30	134.37	0.769	0.30	(0.30)	0.99	49046.0	10210.00
23	26433.44	138.24	0.760	0.30	(0.30)	0.99	49192.9	12000.00
24	23441.50	163.45	0.706	0.30	(0.30)	0.99	49805.8	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 31676.21 Tc(MIN.) = 81.72
 AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 33302.52

 FLOW PROCESS FROM NODE 12605.00 TO NODE 12605.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 81.72
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.955
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS,STRAIGHT ROW"	B	0.50	0.30	1.000	81
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.70	0.30	1.000	65
PUBLIC PARK	B	1.30	0.30	0.850	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	1.30	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS,STRAIGHT ROW"	B	1.90	0.30	1.000	81
PUBLIC PARK	B	2.10	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.918
 SUBAREA AREA(ACRES) = 7.80 SUBAREA RUNOFF(CFS) = 4.77
 EFFECTIVE AREA(ACRES) = 33310.32 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 49813.6 PEAK FLOW RATE(CFS) = 31676.21
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12605.00 TO NODE 12605.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 81.72
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.955
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					

"OPEN BRUSH"	B	3.20	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	3.50	0.30	1.000	65
PUBLIC PARK	B	6.10	0.30	0.850	56
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.929					
SUBAREA AREA(ACRES) = 12.80 SUBAREA RUNOFF(CFS) = 7.80					
EFFECTIVE AREA(ACRES) = 33323.12 AREA-AVERAGED Fm(INCH/HR) = 0.30					
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99					
TOTAL AREA(ACRES) = 49826.4 PEAK FLOW RATE(CFS) = 31676.21					
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE					

 FLOW PROCESS FROM NODE 12605.00 TO NODE 12606.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 305.00 DOWNSTREAM(FEET) = 286.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2159.47 CHANNEL SLOPE = 0.0088
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 7.95
 CHANNEL FLOW THRU SUBAREA(CFS) = 31676.21
 FLOW VELOCITY(FEET/SEC.) = 16.63 FLOW DEPTH(FEET) = 7.95
 TRAVEL TIME(MIN.) = 2.16 Tc(MIN.) = 83.88
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104602.91 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	16864.99	13.27	2.737	0.30(0.29)	0.97	3021.2	800.00
2	18216.67	16.72	2.319	0.30(0.29)	0.98	4103.8	818.00
3	18400.09	17.85	2.221	0.30(0.29)	0.98	4447.0	810.00
4	19461.16	22.54	1.902	0.30(0.29)	0.98	5867.4	600.00
5	23028.08	40.39	1.348	0.30(0.30)	0.99	11884.0	40100.00
6	24776.11	48.53	1.224	0.30(0.30)	0.99	14658.6	11801.00
7	27356.49	59.76	1.080	0.30(0.30)	0.99	19189.1	11530.00
8	28814.38	68.70	1.028	0.30(0.30)	0.99	23845.9	11910.00
9	31012.69	79.05	0.970	0.30(0.30)	0.99	30148.9	11350.00
10	31676.21	83.88	0.943	0.30(0.30)	0.99	33323.1	11130.00
11	31604.68	89.91	0.909	0.30(0.30)	0.99	36249.7	12300.00
12	31547.87	93.78	0.895	0.30(0.30)	0.99	38310.6	11620.00
13	31276.53	98.57	0.878	0.30(0.30)	0.99	40510.3	12400.00
14	31036.11	101.80	0.866	0.30(0.30)	0.99	41825.7	11111.00
15	30608.64	107.90	0.844	0.30(0.30)	0.99	43911.9	12201.00
16	30279.36	110.91	0.833	0.30(0.30)	0.99	44725.6	10410.00
17	29895.50	115.18	0.817	0.30(0.30)	0.99	45804.9	12231.00
18	29603.07	118.17	0.807	0.30(0.30)	0.99	46497.0	12101.10
19	29130.07	122.45	0.795	0.30(0.30)	0.99	47357.6	10400.00
20	28765.30	125.10	0.789	0.30(0.30)	0.99	47811.8	10200.00
21	27859.89	131.53	0.775	0.30(0.30)	0.99	48804.1	12010.00
22	26981.30	136.65	0.764	0.30(0.30)	0.99	49066.6	10210.00
23	26433.44	140.54	0.756	0.30(0.30)	0.99	49213.5	12000.00
24	23441.50	165.84	0.701	0.30(0.30)	0.99	49826.4	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 31676.21 Tc(MIN.) = 83.88
 AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA (ACRES) = 33323.12

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 4F25EVRL.DNA
MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1022.10	10.03	0.30 (0.24)	0.79	378.2	940.00
2	1028.54	10.26	0.30 (0.24)	0.79	385.2	930.00
3	1049.87	13.05	0.30 (0.25)	0.82	462.2	910.00
4	1022.23	16.66	0.30 (0.25)	0.85	548.8	920.00
5	1000.92	17.37	0.30 (0.25)	0.85	553.8	950.00
6	974.91	17.97	0.30 (0.25)	0.85	553.8	900.00

TOTAL AREA (ACRES) = 553.8

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	16864.99	13.27	2.737	0.30 (0.29)	0.97	3021.2	800.00
2	18216.67	16.72	2.319	0.30 (0.29)	0.98	4103.8	818.00
3	18400.09	17.85	2.221	0.30 (0.29)	0.98	4447.0	810.00
4	19461.16	22.54	1.902	0.30 (0.29)	0.98	5867.4	600.00
5	23028.08	40.39	1.348	0.30 (0.30)	0.99	11884.0	40100.00
6	24776.11	48.53	1.224	0.30 (0.30)	0.99	14658.6	11801.00
7	27356.49	59.76	1.080	0.30 (0.30)	0.99	19189.1	11530.00
8	28814.38	68.70	1.028	0.30 (0.30)	0.99	23845.9	11910.00
9	31012.69	79.05	0.970	0.30 (0.30)	0.99	30148.9	11350.00
10	31676.21	83.88	0.943	0.30 (0.30)	0.99	33323.1	11130.00
11	31604.68	89.91	0.909	0.30 (0.30)	0.99	36249.7	12300.00
12	31547.87	93.78	0.895	0.30 (0.30)	0.99	38310.6	11620.00
13	31276.53	98.57	0.878	0.30 (0.30)	0.99	40510.3	12400.00
14	31036.11	101.80	0.866	0.30 (0.30)	0.99	41825.7	11111.00
15	30608.64	107.90	0.844	0.30 (0.30)	0.99	43911.9	12201.00
16	30279.36	110.91	0.833	0.30 (0.30)	0.99	44725.6	10410.00
17	29895.50	115.18	0.817	0.30 (0.30)	0.99	45804.9	12231.00
18	29603.07	118.17	0.807	0.30 (0.30)	0.99	46497.0	12101.10
19	29130.07	122.45	0.795	0.30 (0.30)	0.99	47357.6	10400.00
20	28765.30	125.10	0.789	0.30 (0.30)	0.99	47811.8	10200.00
21	27859.89	131.53	0.775	0.30 (0.30)	0.99	48804.1	12010.00
22	26981.30	136.65	0.764	0.30 (0.30)	0.99	49066.6	10210.00
23	26433.44	140.54	0.756	0.30 (0.30)	0.99	49213.5	12000.00
24	23441.50	165.84	0.701	0.30 (0.30)	0.99	49826.4	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104602.91 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1022.10	10.03	3.239	0.30 (0.24)	0.79	378.2	940.00

2	1028.54	10.26	3.203	0.30 (0.24)	0.79	385.2	930.00
3	1049.87	13.05	2.770	0.30 (0.25)	0.82	462.2	910.00
4	1022.23	16.66	2.324	0.30 (0.25)	0.85	548.8	920.00
5	1000.92	17.37	2.263	0.30 (0.25)	0.85	553.8	950.00
6	974.91	17.97	2.211	0.30 (0.25)	0.85	553.8	900.00

LONGEST FLOWPATH FROM NODE 920.00 TO NODE 12606.00 = 6933.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	16384.56	10.03	3.239	0.30 (0.28)	0.94	2661.2	940.00
2	16555.00	10.26	3.203	0.30 (0.28)	0.94	2721.2	930.00
3	17868.20	13.05	2.770	0.30 (0.28)	0.95	3435.0	910.00
4	17913.23	13.27	2.737	0.30 (0.28)	0.95	3488.5	800.00
5	19215.48	16.66	2.324	0.30 (0.29)	0.96	4633.9	920.00
6	19237.09	16.72	2.319	0.30 (0.29)	0.96	4653.0	818.00
7	19322.05	17.37	2.263	0.30 (0.29)	0.96	4853.0	950.00
8	19380.14	17.85	2.221	0.30 (0.29)	0.96	5000.8	810.00
9	19402.01	17.97	2.211	0.30 (0.29)	0.96	5036.9	900.00
10	20282.22	22.54	1.902	0.30 (0.29)	0.97	6421.2	600.00
11	23573.02	40.39	1.348	0.30 (0.29)	0.98	12437.8	40100.00
12	25258.98	48.53	1.224	0.30 (0.29)	0.98	15212.4	11801.00
13	27767.82	59.76	1.080	0.30 (0.30)	0.99	19742.9	11530.00
14	29199.96	68.70	1.028	0.30 (0.30)	0.99	24399.7	11910.00
15	31369.36	79.05	0.970	0.30 (0.30)	0.99	30702.7	11350.00
16	32019.41	83.88	0.943	0.30 (0.30)	0.99	33876.9	11130.00
17	31931.04	89.91	0.909	0.30 (0.30)	0.99	36803.5	12300.00
18	31867.14	93.78	0.895	0.30 (0.30)	0.99	38864.4	11620.00
19	31587.12	98.57	0.878	0.30 (0.30)	0.99	41064.1	12400.00
20	31340.85	101.80	0.866	0.30 (0.30)	0.99	42379.5	11111.00
21	30902.34	107.90	0.844	0.30 (0.30)	0.99	44465.7	12201.00
22	30567.61	110.91	0.833	0.30 (0.30)	0.99	45279.4	10410.00
23	30176.00	115.18	0.817	0.30 (0.30)	0.99	46358.7	12231.00
24	29878.17	118.17	0.807	0.30 (0.30)	0.99	47050.8	12101.10
25	29399.21	122.45	0.795	0.30 (0.30)	0.99	47911.4	10400.00
26	29031.57	125.10	0.789	0.30 (0.30)	0.99	48365.6	10200.00
27	28119.22	131.53	0.775	0.30 (0.30)	0.99	49357.9	12010.00
28	27235.10	136.65	0.764	0.30 (0.30)	0.99	49620.4	10210.00
29	26683.05	140.54	0.756	0.30 (0.30)	0.99	49767.3	12000.00
30	23663.78	165.84	0.701	0.30 (0.30)	0.99	50380.2	10100.00

TOTAL AREA (ACRES) = 50380.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 32019.41 Tc (MIN.) = 83.880
EFFECTIVE AREA (ACRES) = 33876.92 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA (ACRES) = 50380.2
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104602.91 FEET.

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 83.88

* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.943

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/	SCS SOIL	AREA	Fp	Ap	SCS
-------------------	----------	------	----	----	-----

LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.30	0.30	1.000	63
NATURAL FAIR COVER					
"GRASS"	B	0.30	0.30	1.000	69
PUBLIC PARK	B	0.40	0.30	0.850	56
NATURAL FAIR COVER					
"CHAPARRAL,NARROWLEAF"	B	0.60	0.30	1.000	72
COMMERCIAL	B	1.10	0.30	0.100	56
PUBLIC PARK	B	0.80	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.666
SUBAREA AREA(ACRES) = 3.50 SUBAREA RUNOFF(CFS) = 2.34
EFFECTIVE AREA(ACRES) = 33880.42 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 50383.7 PEAK FLOW RATE(CFS) = 32019.41
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 83.88
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.943
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	0.80	0.30	1.000	69
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.90	0.30	1.000	65
AGRICULTURAL POOR COVER					
"ROW CROPS,STRAIGHT ROW"	B	1.50	0.30	1.000	81
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.60	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.80	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	1.90	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 8.50 SUBAREA RUNOFF(CFS) = 4.92
EFFECTIVE AREA(ACRES) = 33888.92 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 50392.2 PEAK FLOW RATE(CFS) = 32019.41
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 83.88
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.943
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	0.80	0.30	1.000	69
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.90	0.30	1.000	65
AGRICULTURAL POOR COVER					
"ROW CROPS,STRAIGHT ROW"	B	1.50	0.30	1.000	81
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.60	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.80	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	1.90	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 8.50 SUBAREA RUNOFF(CFS) = 4.92
EFFECTIVE AREA(ACRES) = 33888.92 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 50392.2 PEAK FLOW RATE(CFS) = 32019.41
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

NATURAL FAIR COVER					
"OPEN BRUSH"	B	3.30	0.30	1.000	66
PUBLIC PARK	B	3.70	0.30	0.850	56
NATURAL FAIR COVER					
"CHAPARRAL,NARROWLEAF"	B	3.90	0.30	1.000	72
PUBLIC PARK	B	5.90	0.30	0.850	56
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	9.10	0.30	1.000	65
NATURAL FAIR COVER					
"OPEN BRUSH"	B	20.60	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.969
SUBAREA AREA(ACRES) = 46.50 SUBAREA RUNOFF(CFS) = 27.31
EFFECTIVE AREA(ACRES) = 33935.42 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 50438.7 PEAK FLOW RATE(CFS) = 32019.41
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF STUDY SUMMARY:
TOTAL AREA(ACRES) = 50438.7 TC(MIN.) = 83.88
EFFECTIVE AREA(ACRES) = 33935.42 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.990
PEAK FLOW RATE(CFS) = 32019.41

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	16384.56	10.03	3.239	0.30(0.28)	0.94	2719.7	940.00
2	16555.00	10.26	3.203	0.30(0.28)	0.94	2779.7	930.00
3	17868.20	13.05	2.770	0.30(0.28)	0.95	3493.5	910.00
4	17913.23	13.27	2.737	0.30(0.28)	0.95	3547.0	800.00
5	19215.48	16.66	2.324	0.30(0.29)	0.96	4692.4	920.00
6	19237.09	16.72	2.319	0.30(0.29)	0.96	4711.5	818.00
7	19322.05	17.37	2.263	0.30(0.29)	0.96	4911.5	950.00
8	19380.14	17.85	2.221	0.30(0.29)	0.96	5059.3	810.00
9	19402.01	17.97	2.211	0.30(0.29)	0.96	5095.4	900.00
10	20282.22	22.54	1.902	0.30(0.29)	0.97	6479.7	600.00
11	23573.02	40.39	1.348	0.30(0.29)	0.98	12496.3	40100.00
12	25258.98	48.53	1.224	0.30(0.29)	0.98	15270.9	11801.00
13	27767.82	59.76	1.080	0.30(0.30)	0.99	19801.4	11530.00
14	29199.96	68.70	1.028	0.30(0.30)	0.99	24458.2	11910.00
15	31369.36	79.05	0.970	0.30(0.30)	0.99	30761.2	11350.00
16	32019.41	83.88	0.943	0.30(0.30)	0.99	33935.4	11130.00
17	31931.04	89.91	0.909	0.30(0.30)	0.99	36862.0	12300.00
18	31867.14	93.78	0.895	0.30(0.30)	0.99	38922.9	11620.00
19	31587.12	98.57	0.878	0.30(0.30)	0.99	41122.6	12400.00
20	31340.85	101.80	0.866	0.30(0.30)	0.99	42438.0	11111.00
21	30902.34	107.90	0.844	0.30(0.30)	0.99	44524.2	12201.00
22	30567.61	110.91	0.833	0.30(0.30)	0.99	45337.9	10410.00
23	30176.00	115.18	0.817	0.30(0.30)	0.99	46417.2	12231.00
24	29878.17	118.17	0.807	0.30(0.30)	0.99	47109.3	12101.10
25	29399.21	122.45	0.795	0.30(0.30)	0.99	47969.9	10400.00
26	29031.57	125.10	0.789	0.30(0.30)	0.99	48424.1	10200.00
27	28119.22	131.53	0.775	0.30(0.30)	0.99	49416.4	12010.00
28	27235.10	136.65	0.764	0.30(0.30)	0.99	49678.9	10210.00
29	26683.05	140.54	0.756	0.30(0.30)	0.99	49825.8	12000.00
30	23663.78	165.84	0.701	0.30(0.30)	0.99	50438.7	10100.00

=====
END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 127 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 25-YR EV FEB 2023 ROKAMOTO *

FILE NAME: RU25EV27.DAT
TIME/DATE OF STUDY: 15:22 02/07/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 25.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 4.947
- 2) 10.00; 3.222
- 3) 15.00; 2.455
- 4) 20.00; 2.027
- 5) 25.00; 1.766
- 6) 30.00; 1.548
- 7) 40.00; 1.349
- 8) 50.00; 1.196
- 9) 60.00; 1.072
- 10) 90.00; 0.904
- 11) 120.00; 0.794
- 12) 180.00; 0.664
- 13) 360.00; 0.492
- 14) 1200.00; 0.217

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU25EV26.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	17913.23	13.27	0.30 (0.28)	0.95	3547.0	800.00
2	19402.01	17.97	0.30 (0.29)	0.96	5095.4	900.00
3	20282.22	22.54	0.30 (0.29)	0.97	6479.7	600.00
4	23573.02	40.39	0.30 (0.29)	0.98	12496.3	40100.00
5	25258.98	48.53	0.30 (0.29)	0.98	15270.9	11801.00
6	27767.82	59.76	0.30 (0.30)	0.99	19801.4	11530.00
7	29199.96	68.70	0.30 (0.30)	0.99	24458.2	11910.00
8	31369.36	79.05	0.30 (0.30)	0.99	30761.2	11350.00
9	32019.41	83.88	0.30 (0.30)	0.99	33935.4	11130.00
10	31931.04	89.91	0.30 (0.30)	0.99	36862.0	12300.00
11	31867.14	93.78	0.30 (0.30)	0.99	38922.9	11620.00
12	31587.12	98.57	0.30 (0.30)	0.99	41122.6	12400.00
13	30902.34	107.90	0.30 (0.30)	0.99	44524.2	12201.00
14	30567.61	110.91	0.30 (0.30)	0.99	45337.9	10410.00
15	30176.00	115.18	0.30 (0.30)	0.99	46417.2	12231.00
16	29399.21	122.45	0.30 (0.30)	0.99	47969.9	10400.00
17	28119.22	131.53	0.30 (0.30)	0.99	49416.4	12010.00
18	27235.10	136.65	0.30 (0.30)	0.99	49678.9	10210.00
19	26683.05	140.54	0.30 (0.30)	0.99	49825.8	12000.00
20	23663.78	165.84	0.30 (0.30)	0.99	50438.7	10100.00
TOTAL AREA (ACRES) =						50438.7

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	17913.23	13.27	0.30 (0.28)	0.95	3547.0	800.00
2	19402.01	17.97	0.30 (0.29)	0.96	5095.4	900.00
3	20282.22	22.54	0.30 (0.29)	0.97	6479.7	600.00
4	23573.02	40.39	0.30 (0.29)	0.98	12496.3	40100.00
5	25258.98	48.53	0.30 (0.29)	0.98	15270.9	11801.00
6	27767.82	59.76	0.30 (0.30)	0.99	19801.4	11530.00
7	29199.96	68.70	0.30 (0.30)	0.99	24458.2	11910.00
8	31369.36	79.05	0.30 (0.30)	0.99	30761.2	11350.00
9	32019.41	83.88	0.30 (0.30)	0.99	33935.4	11130.00
10	31931.04	89.91	0.30 (0.30)	0.99	36862.0	12300.00
11	31867.14	93.78	0.30 (0.30)	0.99	38922.9	11620.00
12	31587.12	98.57	0.30 (0.30)	0.99	41122.6	12400.00
13	30902.34	107.90	0.30 (0.30)	0.99	44524.2	12201.00

14	30567.61	110.91	0.30	(0.30)	0.99	45337.9	10410.00
15	30176.00	115.18	0.30	(0.30)	0.99	46417.2	12231.00
16	29399.21	122.45	0.30	(0.30)	0.99	47969.9	10400.00
17	28119.22	131.53	0.30	(0.30)	0.99	49416.4	12010.00
18	27235.10	136.65	0.30	(0.30)	0.99	49678.9	10210.00
19	26683.05	140.54	0.30	(0.30)	0.99	49825.8	12000.00
20	23663.78	165.84	0.30	(0.30)	0.99	50438.7	10100.00
TOTAL AREA (ACRES) =							50438.7

FLOW PROCESS FROM NODE 12606.00 TO NODE 12701.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 286.00 DOWNSTREAM(FEET) = 276.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1260.19 CHANNEL SLOPE = 0.0079
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 8.23
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.931
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL					
"5-7 DWELLINGS/ACRE"	B	0.70	0.30	0.500	56
PUBLIC PARK	B	0.90	0.30	0.850	56
COMMERCIAL	B	3.40	0.30	0.100	56
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	3.60	0.30	1.000	65
PUBLIC PARK	B	10.10	0.30	0.850	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	17.40	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.860
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 32030.34
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 16.14
AVERAGE FLOW DEPTH(FEET) = 8.23 TRAVEL TIME(MIN.) = 1.30
Tc(MIN.) = 85.18

SUBAREA AREA(ACRES) = 36.10 SUBAREA RUNOFF(CFS) = 21.87
EFFECTIVE AREA(ACRES) = 33971.52 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 50474.8 PEAK FLOW RATE(CFS) = 32019.41
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 8.23

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 8.23 FLOW VELOCITY(FEET/SEC.) = 16.14
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12701.00 = 105863.10 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	17913.23	14.85	2.478	0.30(0.28)	0.95	3583.1	800.00
2	19402.01	19.51	2.069	0.30(0.29)	0.96	5131.5	900.00
3	20282.22	24.06	1.815	0.30(0.29)	0.97	6515.8	600.00

4	23573.02	41.83	1.321	0.30(0.29)	0.98	12532.4	40100.00
5	25258.98	49.94	1.197	0.30(0.29)	0.98	15307.0	11801.00
6	27767.82	61.12	1.066	0.30(0.30)	0.99	19837.5	11530.00
7	29199.96	70.04	1.016	0.30(0.30)	0.99	24494.3	11910.00
8	31369.36	80.37	0.958	0.30(0.30)	0.99	30797.3	11350.00
9	32019.41	85.18	0.931	0.30(0.30)	0.99	33971.5	11130.00
10	31931.04	91.22	0.900	0.30(0.30)	0.99	36898.1	12300.00
11	31867.14	95.09	0.885	0.30(0.30)	0.99	38959.0	11620.00
12	31587.12	99.88	0.868	0.30(0.30)	0.99	41158.7	12400.00
13	30902.34	109.22	0.834	0.30(0.30)	0.99	44560.3	12201.00
14	30567.61	112.23	0.822	0.30(0.30)	0.99	45374.0	10410.00
15	30176.00	116.51	0.807	0.30(0.30)	0.99	46453.3	12231.00
16	29399.21	123.79	0.786	0.30(0.30)	0.99	48006.0	10400.00
17	28119.22	132.89	0.766	0.30(0.30)	0.99	49452.5	12010.00
18	27235.10	138.03	0.755	0.30(0.30)	0.99	49715.0	10210.00
19	26683.05	141.92	0.747	0.30(0.30)	0.99	49861.9	12000.00
20	23663.78	167.28	0.692	0.30(0.30)	0.99	50474.8	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 32019.41 Tc(MIN.) = 85.18
AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 33971.52

FLOW PROCESS FROM NODE 12701.00 TO NODE 12720.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 276.00 DOWNSTREAM(FEET) = 275.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 147.65 CHANNEL SLOPE = 0.0068
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 8.61
CHANNEL FLOW THRU SUBAREA(CFS) = 32019.41

FLOW VELOCITY(FEET/SEC.) = 15.30 FLOW DEPTH(FEET) = 8.61
TRAVEL TIME(MIN.) = 0.16 Tc(MIN.) = 85.34
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.00 = 106010.75 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	17913.23	15.05	2.451	0.30(0.28)	0.95	3583.1	800.00
2	19402.01	19.70	2.052	0.30(0.29)	0.96	5131.5	900.00
3	20282.22	24.24	1.805	0.30(0.29)	0.97	6515.8	600.00
4	23573.02	42.01	1.318	0.30(0.29)	0.98	12532.4	40100.00
5	25258.98	50.11	1.195	0.30(0.29)	0.98	15307.0	11801.00
6	27767.82	61.29	1.065	0.30(0.30)	0.99	19837.5	11530.00
7	29199.96	70.20	1.015	0.30(0.30)	0.99	24494.3	11910.00
8	31369.36	80.53	0.957	0.30(0.30)	0.99	30797.3	11350.00
9	32019.41	85.34	0.930	0.30(0.30)	0.99	33971.5	11130.00
10	31931.04	91.38	0.899	0.30(0.30)	0.99	36898.1	12300.00
11	31867.14	95.25	0.885	0.30(0.30)	0.99	38959.0	11620.00
12	31587.12	100.04	0.867	0.30(0.30)	0.99	41158.7	12400.00
13	30902.34	109.38	0.833	0.30(0.30)	0.99	44560.3	12201.00
14	30567.61	112.39	0.822	0.30(0.30)	0.99	45374.0	10410.00
15	30176.00	116.68	0.806	0.30(0.30)	0.99	46453.3	12231.00
16	29399.21	123.95	0.785	0.30(0.30)	0.99	48006.0	10400.00
17	28119.22	133.06	0.766	0.30(0.30)	0.99	49452.5	12010.00

18 27235.10 138.20 0.755 0.30(0.30) 0.99 49715.0 10210.00
19 26683.05 142.09 0.746 0.30(0.30) 0.99 49861.9 12000.00
20 23663.78 167.46 0.691 0.30(0.30) 0.99 50474.8 10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 32019.41 Tc(MIN.) = 85.34
AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 33971.52

FLOW PROCESS FROM NODE 12701.00 TO NODE 12720.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION(MIN.) = 85.34
RAINFALL INTENSITY(INCH/HR) = 0.93
AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.99
EFFECTIVE STREAM AREA(ACRES) = 33971.52
TOTAL STREAM AREA(ACRES) = 50474.79
PEAK FLOW RATE(CFS) AT CONFLUENCE = 32019.41

FLOW PROCESS FROM NODE 12710.00 TO NODE 12711.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH(FEET) = 943.56
ELEVATION DATA: UPSTREAM(FEET) = 940.78 DOWNSTREAM(FEET) = 657.79

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 13.910
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.622
SUBAREA Tc AND LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)
NATURAL FAIR COVER
"GRASS" B 6.56 0.30 1.000 69 13.91
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 13.71
TOTAL AREA(ACRES) = 6.56 PEAK FLOW RATE(CFS) = 13.71

FLOW PROCESS FROM NODE 12711.00 TO NODE 12712.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 657.79 DOWNSTREAM(FEET) = 585.63
CHANNEL LENGTH THRU SUBAREA(FEET) = 766.00 CHANNEL SLOPE = 0.0942
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.68
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.339

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

NATURAL FAIR COVER
"OPEN BRUSH" B 26.94 0.30 1.000 66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 38.51
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.23
AVERAGE FLOW DEPTH(FEET) = 0.65 TRAVEL TIME(MIN.) = 2.44
Tc(MIN.) = 16.35
SUBAREA AREA(ACRES) = 26.94 SUBAREA RUNOFF(CFS) = 49.45
EFFECTIVE AREA(ACRES) = 33.50 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 33.5 PEAK FLOW RATE(CFS) = 61.49
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.86

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.86 FLOW VELOCITY(FEET/SEC.) = 6.12
LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12712.00 = 1709.56 FEET.

FLOW PROCESS FROM NODE 12712.00 TO NODE 12713.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 585.63 DOWNSTREAM(FEET) = 463.75
CHANNEL LENGTH THRU SUBAREA(FEET) = 1025.79 CHANNEL SLOPE = 0.1188
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.90
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.132

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

NATURAL FAIR COVER
"OPEN BRUSH" B 14.73 0.30 1.000 66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 73.64
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.04
AVERAGE FLOW DEPTH(FEET) = 0.89 TRAVEL TIME(MIN.) = 2.43
Tc(MIN.) = 18.78
SUBAREA AREA(ACRES) = 14.73 SUBAREA RUNOFF(CFS) = 24.28
EFFECTIVE AREA(ACRES) = 48.23 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 48.2 PEAK FLOW RATE(CFS) = 79.51
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.93

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.93 FLOW VELOCITY(FEET/SEC.) = 7.23
LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12713.00 = 2735.35 FEET.

```

*****
FLOW PROCESS FROM NODE 12713.00 TO NODE 12714.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 463.75 DOWNSTREAM(FEET) = 360.30
CHANNEL LENGTH THRU SUBAREA(FEET) = 1148.54 CHANNEL SLOPE = 0.0901
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.53
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.969
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp        Ap      SCS
LAND USE           GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"OPEN BRUSH"         B      105.64    0.30     1.000    66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 158.94
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.21
AVERAGE FLOW DEPTH(FEET) = 1.49 TRAVEL TIME(MIN.) = 2.33
Tc(MIN.) = 21.11
SUBAREA AREA(ACRES) = 105.64 SUBAREA RUNOFF(CFS) = 158.70
EFFECTIVE AREA(ACRES) = 153.87 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 153.9 PEAK FLOW RATE(CFS) = 231.15
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.84

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.84 FLOW VELOCITY(FEET/SEC.) = 9.21
LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12714.00 = 3883.89 FEET.

```

```

*****
FLOW PROCESS FROM NODE 12714.00 TO NODE 12720.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 360.30 DOWNSTREAM(FEET) = 275.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1314.99 CHANNEL SLOPE = 0.0649
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.42
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.842
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp        Ap      SCS
LAND USE           GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"OPEN BRUSH"         B      127.13    0.30     1.000    66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 319.43
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.03
AVERAGE FLOW DEPTH(FEET) = 2.39 TRAVEL TIME(MIN.) = 2.43
Tc(MIN.) = 23.54

```

```

SUBAREA AREA(ACRES) = 127.13 SUBAREA RUNOFF(CFS) = 176.48
EFFECTIVE AREA(ACRES) = 281.00 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 281.0 PEAK FLOW RATE(CFS) = 390.08
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.67

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 2.67 FLOW VELOCITY(FEET/SEC.) = 9.55
LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12720.00 = 5198.88 FEET.

```

```

*****
FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.00 IS CODE = 1
-----
>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<
=====
TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 23.54
RAINFALL INTENSITY(INCH/HR) = 1.84
AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 1.00
EFFECTIVE STREAM AREA(ACRES) = 281.00
TOTAL STREAM AREA(ACRES) = 281.00
PEAK FLOW RATE(CFS) AT CONFLUENCE = 390.08

```

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	17913.23	15.05	2.451	0.30(0.28)	0.95	3583.1	800.00
1	19402.01	19.70	2.052	0.30(0.29)	0.96	5131.5	900.00
1	20282.22	24.24	1.805	0.30(0.29)	0.97	6515.8	600.00
1	23573.02	42.01	1.318	0.30(0.29)	0.98	12532.4	40100.00
1	25258.98	50.11	1.195	0.30(0.29)	0.98	15307.0	11801.00
1	27767.82	61.29	1.065	0.30(0.30)	0.99	19837.5	11530.00
1	29199.96	70.20	1.015	0.30(0.30)	0.99	24494.3	11910.00
1	31369.36	80.53	0.957	0.30(0.30)	0.99	30797.3	11350.00
1	32019.41	85.34	0.930	0.30(0.30)	0.99	33971.5	11130.00
1	31931.04	91.38	0.899	0.30(0.30)	0.99	36898.1	12300.00
1	31867.14	95.25	0.885	0.30(0.30)	0.99	38959.0	11620.00
1	31587.12	100.04	0.867	0.30(0.30)	0.99	41158.7	12400.00
1	30902.34	109.38	0.833	0.30(0.30)	0.99	44560.3	12201.00
1	30567.61	112.39	0.822	0.30(0.30)	0.99	45374.0	10410.00
1	30176.00	116.68	0.806	0.30(0.30)	0.99	46453.3	12231.00
1	29399.21	123.95	0.785	0.30(0.30)	0.99	48006.0	10400.00
1	28119.22	133.06	0.766	0.30(0.30)	0.99	49452.5	12010.00
1	27235.10	138.20	0.755	0.30(0.30)	0.99	49715.0	10210.00
1	26683.05	142.09	0.746	0.30(0.30)	0.99	49861.9	12000.00
1	23663.78	167.46	0.691	0.30(0.30)	0.99	50474.8	10100.00
2	390.08	23.54	1.842	0.30(0.30)	1.00	281.0	12710.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18261.02	15.05	2.451	0.30(0.29)	0.95	3762.7	800.00
2	19773.02	19.70	2.052	0.30(0.29)	0.96	5366.8	900.00
3	20535.03	23.54	1.842	0.30(0.29)	0.97	6580.9	12710.00
4	20662.95	24.24	1.805	0.30(0.29)	0.97	6796.8	600.00
5	23830.53	42.01	1.318	0.30(0.29)	0.98	12813.4	40100.00
6	25485.22	50.11	1.195	0.30(0.29)	0.98	15588.0	11801.00
7	27961.23	61.29	1.065	0.30(0.30)	0.99	20118.5	11530.00
8	29380.74	70.20	1.015	0.30(0.30)	0.99	24775.3	11910.00
9	31535.52	80.53	0.957	0.30(0.30)	0.99	31078.3	11350.00
10	32178.75	85.34	0.930	0.30(0.30)	0.99	34252.5	11130.00
11	32082.51	91.38	0.899	0.30(0.30)	0.99	37179.1	12300.00
12	32015.02	95.25	0.885	0.30(0.30)	0.99	39240.0	11620.00
13	31730.56	100.04	0.867	0.30(0.30)	0.99	41439.7	12400.00
14	31037.12	109.38	0.833	0.30(0.30)	0.99	44841.3	12201.00
15	30699.60	112.39	0.822	0.30(0.30)	0.99	45655.0	10410.00
16	30304.02	116.68	0.806	0.30(0.30)	0.99	46734.3	12231.00
17	29521.97	123.95	0.785	0.30(0.30)	0.99	48287.0	10400.00
18	28237.00	133.06	0.766	0.30(0.30)	0.99	49733.5	12010.00
19	27350.06	138.20	0.755	0.30(0.30)	0.99	49996.0	10210.00
20	26795.88	142.09	0.746	0.30(0.30)	0.99	50142.9	12000.00
21	23762.71	167.46	0.691	0.30(0.30)	0.99	50755.8	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 32178.75 Tc(MIN.) = 85.34
 EFFECTIVE AREA(ACRES) = 34252.52 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 50755.8
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.00 = 106010.75 FEET.

 FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 275.00 DOWNSTREAM(FEET) = 258.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2669.21 CHANNEL SLOPE = 0.0064
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 8.79
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.913

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER "BARREN"	B	0.20	0.30	1.000	86
NATURAL POOR COVER "BARREN"	B	0.20	0.30	1.000	86
NATURAL FAIR COVER "OPEN BRUSH"	B	0.20	0.30	1.000	66
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.30	0.30	1.000	65
COMMERCIAL	B	0.30	0.30	0.100	56
NATURAL FAIR COVER "MEADOWS"	B	0.50	0.30	1.000	70

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.841
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 32179.26
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 15.01
 AVERAGE FLOW DEPTH(FEET) = 8.79 TRAVEL TIME(MIN.) = 2.96
 Tc(MIN.) = 88.31
 SUBAREA AREA(ACRES) = 1.70 SUBAREA RUNOFF(CFS) = 1.01
 EFFECTIVE AREA(ACRES) = 34254.22 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 50757.5 PEAK FLOW RATE(CFS) = 32178.75
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 8.79

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 8.79 FLOW VELOCITY(FEET/SEC.) = 15.01
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108679.96 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18261.02	18.63	2.144	0.30(0.29)	0.95	3764.4	800.00
2	19773.02	23.19	1.860	0.30(0.29)	0.96	5368.5	900.00
3	20535.03	26.98	1.680	0.30(0.29)	0.97	6582.6	12710.00
4	20662.95	27.68	1.649	0.30(0.29)	0.97	6798.5	600.00
5	23830.53	45.29	1.268	0.30(0.29)	0.98	12815.1	40100.00
6	25485.22	53.32	1.155	0.30(0.29)	0.98	15589.7	11801.00
7	27961.23	64.40	1.047	0.30(0.30)	0.99	20120.2	11530.00
8	29380.74	73.26	0.998	0.30(0.30)	0.99	24777.0	11910.00
9	31535.52	83.51	0.940	0.30(0.30)	0.99	31080.0	11350.00
10	32178.75	88.31	0.913	0.30(0.30)	0.99	34254.2	11130.00
11	32082.51	94.34	0.888	0.30(0.30)	0.99	37180.8	12300.00
12	32015.02	98.21	0.874	0.30(0.30)	0.99	39241.7	11620.00
13	31730.56	103.02	0.856	0.30(0.30)	0.99	41441.4	12400.00
14	31037.12	112.38	0.822	0.30(0.30)	0.99	44843.0	12201.00
15	30699.60	115.40	0.811	0.30(0.30)	0.99	45656.7	10410.00
16	30304.02	119.70	0.795	0.30(0.30)	0.99	46736.0	12231.00
17	29521.97	127.00	0.779	0.30(0.30)	0.99	48288.7	10400.00
18	28237.00	136.15	0.759	0.30(0.30)	0.99	49735.2	12010.00
19	27350.06	141.33	0.748	0.30(0.30)	0.99	49997.7	10210.00
20	26795.88	145.24	0.739	0.30(0.30)	0.99	50144.6	12000.00
21	23762.71	170.74	0.684	0.30(0.30)	0.99	50757.5	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 32178.75 Tc(MIN.) = 88.31
 AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 34254.22

 FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 88.31
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.913

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	0.50	0.30	0.850	56

NATURAL FAIR COVER
 "WOODLAND,GRASS" B 0.70 0.30 1.000 65
 NATURAL FAIR COVER
 "OPEN BRUSH" B 1.50 0.30 1.000 66
 COMMERCIAL B 1.40 0.30 0.100 56
 COMMERCIAL B 2.30 0.30 0.100 56
 NATURAL FAIR COVER
 "GRASS" B 9.30 0.30 1.000 69
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.783
 SUBAREA AREA (ACRES) = 15.70 SUBAREA RUNOFF (CFS) = 9.59
 EFFECTIVE AREA (ACRES) = 34269.92 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 50773.2 PEAK FLOW RATE (CFS) = 32178.75
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 81

 >>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 88.31
 * 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.913
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	11.20	0.30	1.000	65
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	11.40	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL,NARROWLEAF"	B	11.80	0.30	1.000	72
NATURAL FAIR COVER					
"OPEN BRUSH"	B	27.70	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 62.10 SUBAREA RUNOFF (CFS) = 34.29
 EFFECTIVE AREA (ACRES) = 34332.02 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 50835.3 PEAK FLOW RATE (CFS) = 32178.75
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<
 =====

PEAK FLOWRATE TABLE FILE NAME: 3C25EVRL.DNA
 MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2076.96	12.77	0.30 (0.13)	0.42	864.0	410.00
2	2086.53	14.12	0.30 (0.13)	0.42	940.9	420.00
3	2141.29	18.17	0.30 (0.13)	0.42	1155.9	310.00
4	2137.49	18.62	0.30 (0.13)	0.42	1174.6	400.00
5	2067.81	21.15	0.30 (0.13)	0.42	1245.4	430.00
6	2052.56	21.87	0.30 (0.13)	0.42	1264.9	300.00
7	2050.57	21.97	0.30 (0.13)	0.42	1267.1	320.00

8 1754.01 27.95 0.30 (0.13) 0.43 1292.3 390.00
 TOTAL AREA (ACRES) = 1292.3

 FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<
 =====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18261.02	18.63	2.144	0.30 (0.29)	0.95	3842.2	800.00
2	19773.02	23.19	1.860	0.30 (0.29)	0.96	5446.3	900.00
3	20535.03	26.98	1.680	0.30 (0.29)	0.97	6660.5	12710.00
4	20662.95	27.68	1.649	0.30 (0.29)	0.97	6876.3	600.00
5	23830.53	45.29	1.268	0.30 (0.29)	0.98	12892.9	40100.00
6	25485.22	53.32	1.155	0.30 (0.29)	0.98	15667.5	11801.00
7	27961.23	64.40	1.047	0.30 (0.30)	0.99	20198.0	11530.00
8	29380.74	73.26	0.998	0.30 (0.30)	0.99	24854.8	11910.00
9	31535.52	83.51	0.940	0.30 (0.30)	0.99	31157.8	11350.00
10	32178.75	88.31	0.913	0.30 (0.30)	0.99	34332.0	11130.00
11	32082.51	94.34	0.888	0.30 (0.30)	0.99	37258.6	12300.00
12	32015.02	98.21	0.874	0.30 (0.30)	0.99	39319.5	11620.00
13	31730.56	103.02	0.856	0.30 (0.30)	0.99	41519.2	12400.00
14	31037.12	112.38	0.822	0.30 (0.30)	0.99	44920.8	12201.00
15	30699.60	115.40	0.811	0.30 (0.30)	0.99	45734.5	10410.00
16	30304.02	119.70	0.795	0.30 (0.30)	0.99	46813.8	12231.00
17	29521.97	127.00	0.779	0.30 (0.30)	0.99	48366.5	10400.00
18	28237.00	136.15	0.759	0.30 (0.30)	0.99	49813.0	12010.00
19	27350.06	141.33	0.748	0.30 (0.30)	0.99	50075.5	10210.00
20	26795.88	145.24	0.739	0.30 (0.30)	0.99	50222.4	12000.00
21	23762.71	170.74	0.684	0.30 (0.30)	0.99	50835.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108679.96 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2076.96	12.77	2.797	0.30 (0.13)	0.42	864.0	410.00
2	2086.53	14.12	2.590	0.30 (0.13)	0.42	940.9	420.00
3	2141.29	18.17	2.184	0.30 (0.13)	0.42	1155.9	310.00
4	2137.49	18.62	2.145	0.30 (0.13)	0.42	1174.6	400.00
5	2067.81	21.15	1.967	0.30 (0.13)	0.42	1245.4	430.00
6	2052.56	21.87	1.929	0.30 (0.13)	0.42	1264.9	300.00
7	2050.57	21.97	1.924	0.30 (0.13)	0.42	1267.1	320.00
8	1754.01	27.95	1.637	0.30 (0.13)	0.43	1292.3	390.00

LONGEST FLOWPATH FROM NODE 390.00 TO NODE 12720.50 = 13248.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18989.30	12.77	2.797	0.30 (0.25)	0.82	3497.4	410.00
2	19244.82	14.12	2.590	0.30 (0.25)	0.82	3852.8	420.00
3	20327.90	18.17	2.184	0.30 (0.25)	0.83	4902.2	310.00
4	20396.37	18.62	2.145	0.30 (0.25)	0.83	5013.6	400.00
5	20398.09	18.63	2.144	0.30 (0.25)	0.83	5017.2	800.00
6	21164.69	21.15	1.967	0.30 (0.25)	0.85	5974.4	430.00
7	21387.87	21.87	1.929	0.30 (0.26)	0.85	6246.8	300.00

8	21416.68	21.97	1.924	0.30	(0.26)	0.85	6281.7	320.00
9	21762.79	23.19	1.860	0.30	(0.26)	0.86	6718.6	900.00
10	22337.09	26.98	1.680	0.30	(0.26)	0.88	7948.7	12710.00
11	22430.31	27.68	1.649	0.30	(0.27)	0.88	8167.5	600.00
12	22465.42	27.95	1.637	0.30	(0.27)	0.89	8260.7	390.00
13	25155.03	45.29	1.268	0.30	(0.28)	0.93	14185.2	40100.00
14	26678.02	53.32	1.155	0.30	(0.28)	0.94	16959.8	11801.00
15	29028.97	64.40	1.047	0.30	(0.29)	0.95	21490.3	11530.00
16	30390.78	73.26	0.998	0.30	(0.29)	0.96	26147.1	11910.00
17	32478.79	83.51	0.940	0.30	(0.29)	0.97	32450.1	11350.00
18	33090.79	88.31	0.913	0.30	(0.29)	0.97	35624.3	11130.00
19	32964.98	94.34	0.888	0.30	(0.29)	0.97	38550.9	12300.00
20	32880.98	98.21	0.874	0.30	(0.29)	0.97	40611.8	11620.00
21	32576.03	103.02	0.856	0.30	(0.29)	0.97	42811.5	12400.00
22	31842.68	112.38	0.822	0.30	(0.29)	0.97	46213.1	12201.00
23	31492.26	115.40	0.811	0.30	(0.29)	0.97	47026.8	10410.00
24	31078.35	119.70	0.795	0.30	(0.29)	0.97	48106.1	12231.00
25	30277.38	127.00	0.779	0.30	(0.29)	0.97	49658.8	10400.00
26	28969.36	136.15	0.759	0.30	(0.29)	0.97	51105.3	12010.00
27	28069.37	141.33	0.748	0.30	(0.29)	0.98	51367.8	10210.00
28	27505.33	145.24	0.739	0.30	(0.29)	0.98	51514.7	12000.00
29	24407.91	170.74	0.684	0.30	(0.29)	0.98	52127.6	10100.00

TOTAL AREA (ACRES) = 52127.6

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 33090.79 Tc (MIN.) = 88.305
EFFECTIVE AREA (ACRES) = 35624.32 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.88
TOTAL AREA (ACRES) = 52127.6
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108679.96 FEET.

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

FLOW PROCESS FROM NODE 12720.50 TO NODE 12722.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 258.00 DOWNSTREAM (FEET) = 255.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 1269.00 CHANNEL SLOPE = 0.0024
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 11.80
* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.903

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	0.10	0.30	0.850	56
NATURAL FAIR COVER "GRASS"	B	0.10	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	0.20	0.30	1.000	69

"GRASS"	B	0.30	0.30	1.000	69
---------	---	------	------	-------	----

NATURAL FAIR COVER
"OPEN BRUSH" B | 0.30 | 0.30 | 1.000 | 66 |
COMMERCIAL B | 0.40 | 0.30 | 0.100 | 56 |
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.732
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 33091.21
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 10.83
AVERAGE FLOW DEPTH (FEET) = 11.80 TRAVEL TIME (MIN.) = 1.95
Tc (MIN.) = 90.26
SUBAREA AREA (ACRES) = 1.40 SUBAREA RUNOFF (CFS) = 0.86
EFFECTIVE AREA (ACRES) = 35625.72 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA (ACRES) = 52129.0 PEAK FLOW RATE (CFS) = 33090.79
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 11.80

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 11.80 FLOW VELOCITY (FEET/SEC.) = 10.83
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12722.00 = 109948.96 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18989.30	15.11	2.446	0.30 (0.25)	0.82	3498.8	410.00
2	19244.82	16.45	2.331	0.30 (0.25)	0.82	3854.2	420.00
3	20327.90	20.45	2.003	0.30 (0.25)	0.83	4903.6	310.00
4	20396.37	20.90	1.980	0.30 (0.25)	0.83	5015.0	400.00
5	20398.09	20.92	1.979	0.30 (0.25)	0.83	5018.6	800.00
6	21164.69	23.41	1.849	0.30 (0.25)	0.85	5975.8	430.00
7	21387.87	24.12	1.812	0.30 (0.26)	0.85	6248.2	300.00
8	21416.68	24.21	1.807	0.30 (0.26)	0.85	6283.1	320.00
9	21762.79	25.43	1.747	0.30 (0.26)	0.86	6720.0	900.00
10	22337.09	29.20	1.583	0.30 (0.26)	0.88	7950.1	12710.00
11	22430.31	29.89	1.553	0.30 (0.27)	0.88	8168.9	600.00
12	22465.42	30.16	1.545	0.30 (0.27)	0.89	8262.1	390.00
13	25155.03	47.42	1.236	0.30 (0.28)	0.93	14186.6	40100.00
14	26678.02	55.41	1.129	0.30 (0.28)	0.94	16961.2	11801.00
15	29028.97	66.43	1.036	0.30 (0.29)	0.95	21491.7	11530.00
16	30390.78	75.26	0.987	0.30 (0.29)	0.96	26148.5	11910.00
17	32478.79	85.47	0.929	0.30 (0.29)	0.97	32451.5	11350.00
18	33090.79	90.26	0.903	0.30 (0.29)	0.97	35625.7	11130.00
19	32964.98	96.30	0.881	0.30 (0.29)	0.97	38552.3	12300.00
20	32880.98	100.17	0.867	0.30 (0.29)	0.97	40613.2	11620.00
21	32576.03	104.98	0.849	0.30 (0.29)	0.97	42812.9	12400.00
22	31842.68	114.35	0.815	0.30 (0.29)	0.97	46214.5	12201.00
23	31492.26	117.39	0.804	0.30 (0.29)	0.97	47028.2	10410.00
24	31078.35	121.69	0.790	0.30 (0.29)	0.97	48107.5	12231.00
25	30277.38	129.01	0.774	0.30 (0.29)	0.97	49660.2	10400.00
26	28969.36	138.19	0.755	0.30 (0.29)	0.97	51106.7	12010.00
27	28069.37	143.38	0.743	0.30 (0.29)	0.98	51369.2	10210.00
28	27505.33	147.31	0.735	0.30 (0.29)	0.98	51516.1	12000.00
29	24407.91	172.89	0.679	0.30 (0.29)	0.98	52129.0	10100.00

NEW PEAK FLOW DATA ARE:
PEAK FLOW RATE (CFS) = 33090.79 Tc (MIN.) = 90.26
AREA-AVERAGED Fm (INCH/HR) = 0.29 AREA-AVERAGED Fp (INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.97 EFFECTIVE AREA(ACRES) = 35625.72

FLOW PROCESS FROM NODE 12722.00 TO NODE 12722.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 90.26
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.903
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCSSOIL AREA Fp Ap SCSS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
COMMERCIAL B 0.50 0.30 0.100 56
NATURAL FAIR COVER
"WOODLAND,GRASS" B 0.60 0.30 1.000 65
NATURAL POOR COVER
"BARREN" B 0.60 0.30 1.000 86
COMMERCIAL B 0.60 0.30 0.100 56
NATURAL FAIR COVER
"OPEN BRUSH" B 0.90 0.30 1.000 66
NATURAL FAIR COVER
"CHAPARRAL,BROADLEAF" B 1.00 0.30 1.000 63
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.764
SUBAREA AREA(ACRES) = 4.20 SUBAREA RUNOFF(CFS) = 2.55
EFFECTIVE AREA(ACRES) = 35629.92 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 52133.2 PEAK FLOW RATE(CFS) = 33090.79
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12722.00 TO NODE 12722.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 90.26
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.903
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCSSOIL AREA Fp Ap SCSS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"WOODLAND,GRASS" B 1.30 0.30 1.000 65
NATURAL FAIR COVER
"MEADOWS" B 3.20 0.30 1.000 70
NATURAL FAIR COVER
"WOODLAND,GRASS" B 3.70 0.30 1.000 65
NATURAL FAIR COVER
"OPEN BRUSH" B 12.00 0.30 1.000 66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 20.20 SUBAREA RUNOFF(CFS) = 10.96
EFFECTIVE AREA(ACRES) = 35650.12 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 52153.4 PEAK FLOW RATE(CFS) = 33090.79
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12722.00 TO NODE 12740.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 255.00 DOWNSTREAM(FEET) = 252.10
CHANNEL LENGTH THRU SUBAREA(FEET) = 624.00 CHANNEL SLOPE = 0.0046
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 9.76
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.900
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCSSOIL AREA Fp Ap SCSS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
AGRICULTURAL POOR COVER
"ROW CROPS,STRAIGHT ROW" B 0.10 0.30 1.000 81
PUBLIC PARK B 0.50 0.30 0.850 56
NATURAL FAIR COVER
"GRASS" B 0.50 0.30 1.000 69
NATURAL FAIR COVER
"CHAPARRAL,BROADLEAF" B 0.80 0.30 1.000 63
NATURAL FAIR COVER
"WOODLAND,GRASS" B 1.20 0.30 1.000 65
COMMERCIAL B 1.50 0.30 0.100 56
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.690
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 33092.22
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 13.63
AVERAGE FLOW DEPTH(FEET) = 9.76 TRAVEL TIME(MIN.) = 0.76
Tc(MIN.) = 91.02
SUBAREA AREA(ACRES) = 4.60 SUBAREA RUNOFF(CFS) = 2.87
EFFECTIVE AREA(ACRES) = 35654.72 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 52158.0 PEAK FLOW RATE(CFS) = 33090.79
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 9.76
END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 9.76 FLOW VELOCITY(FEET/SEC.) = 13.63
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12740.00 = 110572.96 FEET.

** PEAK FLOW RATE TABLE **

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 13 rows of data.

	DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
14	26678.02	56.23	1.119	0.30(0.28)	0.94	16990.2 11801.00
15	29028.97	67.23	1.032	0.30(0.29)	0.95	21520.7 11530.00
16	30390.78	76.05	0.982	0.30(0.29)	0.96	26177.5 11910.00
17	32478.79	86.24	0.925	0.30(0.29)	0.97	32480.5 11350.00
18	33090.79	91.02	0.900	0.30(0.29)	0.97	35654.7 11130.00
19	32964.98	97.06	0.878	0.30(0.29)	0.97	38581.3 12300.00
20	32880.98	100.94	0.864	0.30(0.29)	0.97	40642.2 11620.00
21	32576.03	105.75	0.846	0.30(0.29)	0.97	42841.9 12400.00
22	31842.68	115.13	0.812	0.30(0.29)	0.97	46243.5 12201.00
23	31492.26	118.16	0.801	0.30(0.29)	0.97	47057.2 10410.00
24	31078.35	122.47	0.789	0.30(0.29)	0.97	48136.5 12231.00
25	30277.38	129.80	0.773	0.30(0.29)	0.97	49689.2 10400.00
26	28969.36	138.98	0.753	0.30(0.29)	0.97	51135.7 12010.00
27	28069.37	144.19	0.742	0.30(0.29)	0.98	51398.2 10210.00
28	27505.33	148.12	0.733	0.30(0.29)	0.98	51545.1 12000.00
29	24407.91	173.73	0.678	0.30(0.29)	0.98	52158.0 10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 33090.79 Tc(MIN.) = 91.02
 AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.97 EFFECTIVE AREA(ACRES) = 35654.72

 FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

 MAINLINE Tc(MIN.) = 91.02
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.900
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	2.50	0.30	0.100	56
NATURAL FAIR COVER "GRASS"	B	2.60	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	2.80	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	5.40	0.30	1.000	66
NATURAL FAIR COVER "WOODLAND,GRASS"	B	6.20	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND,GRASS"	B	6.50	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.913
 SUBAREA AREA(ACRES) = 26.00 SUBAREA RUNOFF(CFS) = 14.65
 EFFECTIVE AREA(ACRES) = 35680.72 AREA-AVERAGED Fm(INCH/HR) = 0.29
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA(ACRES) = 52184.0 PEAK FLOW RATE(CFS) = 33090.79
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

 MAINLINE Tc(MIN.) = 91.02
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.900
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	6.70	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	12.00	0.30	1.000	66
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	B	20.30	0.30	1.000	63

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 39.00 SUBAREA RUNOFF(CFS) = 21.07
 EFFECTIVE AREA(ACRES) = 35719.72 AREA-AVERAGED Fm(INCH/HR) = 0.29
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA(ACRES) = 52223.0 PEAK FLOW RATE(CFS) = 33090.79
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

 TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
 TIME OF CONCENTRATION(MIN.) = 91.02
 RAINFALL INTENSITY(INCH/HR) = 0.90
 AREA-AVERAGED Fm(INCH/HR) = 0.29
 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.97
 EFFECTIVE STREAM AREA(ACRES) = 35719.72
 TOTAL STREAM AREA(ACRES) = 52222.99
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 33090.79

 FLOW PROCESS FROM NODE 12730.00 TO NODE 12731.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

 INITIAL SUBAREA FLOW-LENGTH(FEET) = 561.54
 ELEVATION DATA: UPSTREAM(FEET) = 613.29 DOWNSTREAM(FEET) = 551.75

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
 SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 13.823
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.636
 SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	B	6.33	0.30	1.000	63	13.82

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA RUNOFF(CFS) = 13.31
 TOTAL AREA(ACRES) = 6.33 PEAK FLOW RATE(CFS) = 13.31

 FLOW PROCESS FROM NODE 12731.00 TO NODE 12732.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

```

=====
ELEVATION DATA: UPSTREAM(FEET) = 551.75 DOWNSTREAM(FEET) = 494.40
CHANNEL LENGTH THRU SUBAREA(FEET) = 971.91 CHANNEL SLOPE = 0.0590
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.87
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.261
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp        Ap      SCS
LAND USE           GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"OPEN BRUSH"         B         34.62    0.30     1.000    66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 44.03
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.70
AVERAGE FLOW DEPTH(FEET) = 0.81 TRAVEL TIME(MIN.) = 3.44
Tc(MIN.) = 17.27
SUBAREA AREA(ACRES) = 34.62 SUBAREA RUNOFF(CFS) = 61.10
EFFECTIVE AREA(ACRES) = 40.95 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 40.9 PEAK FLOW RATE(CFS) = 72.27
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.07

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.07 FLOW VELOCITY(FEET/SEC.) = 5.55
LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12732.00 = 1533.45 FEET.

```

```

*****
FLOW PROCESS FROM NODE 12732.00 TO NODE 12733.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<

```

```

=====
ELEVATION DATA: UPSTREAM(FEET) = 494.40 DOWNSTREAM(FEET) = 431.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1156.41 CHANNEL SLOPE = 0.0548
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.50
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.010
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp        Ap      SCS
LAND USE           GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"OPEN BRUSH"         B         59.52    0.30     1.000    66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 118.15
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.30
AVERAGE FLOW DEPTH(FEET) = 1.45 TRAVEL TIME(MIN.) = 3.06
Tc(MIN.) = 20.32
SUBAREA AREA(ACRES) = 59.52 SUBAREA RUNOFF(CFS) = 91.61
EFFECTIVE AREA(ACRES) = 100.47 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 100.5 PEAK FLOW RATE(CFS) = 154.63

```

```

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.69

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.69 FLOW VELOCITY(FEET/SEC.) = 6.84
LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12733.00 = 2689.86 FEET.

```

```

*****
FLOW PROCESS FROM NODE 12733.00 TO NODE 12734.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<

```

```

=====
ELEVATION DATA: UPSTREAM(FEET) = 431.00 DOWNSTREAM(FEET) = 367.10
CHANNEL LENGTH THRU SUBAREA(FEET) = 1654.48 CHANNEL SLOPE = 0.0386
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.16
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.789
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp        Ap      SCS
LAND USE           GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"OPEN BRUSH"         B         64.05    0.30     1.000    66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 197.62
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.52
AVERAGE FLOW DEPTH(FEET) = 2.13 TRAVEL TIME(MIN.) = 4.23
Tc(MIN.) = 24.55
SUBAREA AREA(ACRES) = 64.05 SUBAREA RUNOFF(CFS) = 85.86
EFFECTIVE AREA(ACRES) = 164.52 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 164.5 PEAK FLOW RATE(CFS) = 220.54
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.26

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 2.26 FLOW VELOCITY(FEET/SEC.) = 6.74
LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12734.00 = 4344.34 FEET.

```

```

*****
FLOW PROCESS FROM NODE 12734.00 TO NODE 12740.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<

```

```

=====
ELEVATION DATA: UPSTREAM(FEET) = 367.11 DOWNSTREAM(FEET) = 252.10
CHANNEL LENGTH THRU SUBAREA(FEET) = 1880.98 CHANNEL SLOPE = 0.0611
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.07
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.617
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp        Ap      SCS
LAND USE           GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN

```

NATURAL FAIR COVER
 "OPEN BRUSH" B 26.02 0.30 1.000 66
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 235.97
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.09
 AVERAGE FLOW DEPTH(FEET) = 2.06 TRAVEL TIME(MIN.) = 3.88
 Tc(MIN.) = 28.43
 SUBAREA AREA(ACRES) = 26.02 SUBAREA RUNOFF(CFS) = 30.83
 EFFECTIVE AREA(ACRES) = 190.54 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 190.54 PEAK FLOW RATE(CFS) = 225.78
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 2.02

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 2.02 FLOW VELOCITY(FEET/SEC.) = 7.98
 LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12740.00 = 6225.32 FEET.

 FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
 TIME OF CONCENTRATION(MIN.) = 28.43
 RAINFALL INTENSITY(INCH/HR) = 1.62
 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 1.00
 EFFECTIVE STREAM AREA(ACRES) = 190.54
 TOTAL STREAM AREA(ACRES) = 190.54
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 225.78

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18989.30	16.03	2.367	0.30(0.25)	0.82	3592.8	410.00
1	19244.82	17.36	2.253	0.30(0.25)	0.82	3948.2	420.00
1	20327.90	21.35	1.957	0.30(0.25)	0.83	4997.6	310.00
1	20396.37	21.80	1.933	0.30(0.25)	0.83	5109.0	400.00
1	20398.09	21.81	1.932	0.30(0.25)	0.83	5112.6	800.00
1	21164.69	24.29	1.803	0.30(0.25)	0.85	6069.8	430.00
1	21387.87	25.00	1.766	0.30(0.26)	0.85	6342.2	300.00
1	21416.68	25.09	1.762	0.30(0.26)	0.85	6377.1	320.00
1	21762.79	26.30	1.709	0.30(0.26)	0.86	6814.0	900.00
1	22337.09	30.06	1.547	0.30(0.26)	0.88	8044.1	12710.00
1	22430.31	30.76	1.533	0.30(0.27)	0.89	8262.9	600.00
1	22465.42	31.03	1.528	0.30(0.27)	0.89	8356.1	390.00
1	25155.03	48.25	1.223	0.30(0.28)	0.93	14280.6	40100.00
1	26678.02	56.23	1.119	0.30(0.28)	0.94	17055.2	11801.00
1	29028.97	67.23	1.032	0.30(0.29)	0.95	21585.7	11530.00
1	30390.78	76.05	0.982	0.30(0.29)	0.96	26242.5	11910.00
1	32478.79	86.24	0.925	0.30(0.29)	0.97	32545.5	11350.00
1	33090.79	91.02	0.900	0.30(0.29)	0.97	35719.7	11130.00

1	32964.98	97.06	0.878	0.30(0.29)	0.97	38646.3	12300.00
1	32880.98	100.94	0.864	0.30(0.29)	0.97	40707.2	11620.00
1	32576.03	105.75	0.846	0.30(0.29)	0.97	42906.9	12400.00
1	31842.68	115.13	0.812	0.30(0.29)	0.97	46308.5	12201.00
1	31492.26	118.16	0.801	0.30(0.29)	0.97	47122.2	10410.00
1	31078.35	122.47	0.789	0.30(0.29)	0.97	48201.5	12231.00
1	30277.38	129.80	0.773	0.30(0.29)	0.97	49754.2	10400.00
1	28969.36	138.98	0.753	0.30(0.29)	0.97	51200.7	12010.00
1	28069.37	144.19	0.742	0.30(0.29)	0.98	51463.2	10210.00
1	27505.33	148.12	0.733	0.30(0.29)	0.98	51610.1	12000.00
1	24407.91	173.73	0.678	0.30(0.29)	0.98	52223.0	10100.00
2	225.78	28.43	1.617	0.30(0.30)	1.00	190.5	12730.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19189.15	16.03	2.367	0.30(0.25)	0.83	3700.2	410.00
2	19449.36	17.36	2.253	0.30(0.25)	0.83	4064.5	420.00
3	20541.26	21.35	1.957	0.30(0.25)	0.83	5140.7	310.00
4	20611.12	21.80	1.933	0.30(0.25)	0.83	5255.1	400.00
5	20612.88	21.81	1.932	0.30(0.25)	0.83	5258.8	800.00
6	21384.94	24.29	1.803	0.30(0.26)	0.85	6232.6	430.00
7	21608.96	25.00	1.766	0.30(0.26)	0.86	6509.8	300.00
8	21637.98	25.09	1.762	0.30(0.26)	0.86	6545.3	320.00
9	21986.39	26.30	1.709	0.30(0.26)	0.87	6990.3	900.00
10	22312.80	28.43	1.617	0.30(0.26)	0.88	7699.0	12730.00
11	22550.88	30.06	1.547	0.30(0.27)	0.88	8234.6	12710.00
12	22641.73	30.76	1.533	0.30(0.27)	0.89	8453.4	600.00
13	22675.93	31.03	1.528	0.30(0.27)	0.89	8546.6	390.00
14	25313.26	48.25	1.223	0.30(0.28)	0.93	14471.2	40100.00
15	26818.43	56.23	1.119	0.30(0.28)	0.94	17245.7	11801.00
16	29154.42	67.23	1.032	0.30(0.29)	0.95	21776.3	11530.00
17	30507.75	76.05	0.982	0.30(0.29)	0.96	26433.1	11910.00
18	32585.97	86.24	0.925	0.30(0.29)	0.97	32736.0	11350.00
19	33193.72	91.02	0.900	0.30(0.29)	0.97	35910.3	11130.00
20	33064.12	97.06	0.878	0.30(0.29)	0.97	38836.8	12300.00
21	32977.69	100.94	0.864	0.30(0.29)	0.97	40897.7	11620.00
22	32669.70	105.75	0.846	0.30(0.29)	0.97	43097.4	12400.00
23	31930.46	115.13	0.812	0.30(0.29)	0.97	46499.0	12201.00
24	31578.13	118.16	0.801	0.30(0.29)	0.97	47312.7	10410.00
25	31162.15	122.47	0.789	0.30(0.29)	0.97	48392.0	12231.00
26	30358.45	129.80	0.773	0.30(0.29)	0.97	49944.8	10400.00
27	29047.02	138.98	0.753	0.30(0.29)	0.98	51391.2	12010.00
28	28145.10	144.19	0.742	0.30(0.29)	0.98	51653.8	10210.00
29	27579.59	148.12	0.733	0.30(0.29)	0.98	51800.6	12000.00
30	24472.66	173.73	0.678	0.30(0.29)	0.98	52413.5	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 33193.72 Tc(MIN.) = 91.02
 EFFECTIVE AREA(ACRES) = 35910.26 AREA-AVERAGED Fm(INCH/HR) = 0.29
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA(ACRES) = 52413.5
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12740.00 = 110572.96 FEET.

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 252.10 DOWNSTREAM(FEET) = 240.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 1220.00 CHANNEL SLOPE = 0.0099

GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT(FEET) = 7.88

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.896

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "ROW CROPS,STRAIGHT ROW"	B	0.30	0.30	1.000	81
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.40	0.30	1.000	65
COMMERCIAL	B	0.40	0.30	0.100	56
COMMERCIAL	B	0.60	0.30	0.100	56
NATURAL FAIR COVER "OPEN BRUSH"	B	1.50	0.30	1.000	66
PUBLIC PARK	B	3.20	0.30	0.850	56

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.784

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 33195.62

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 17.59

AVERAGE FLOW DEPTH(FEET) = 7.88 TRAVEL TIME(MIN.) = 1.16

Tc(MIN.) = 92.18

SUBAREA AREA(ACRES) = 6.40 SUBAREA RUNOFF(CFS) = 3.81

EFFECTIVE AREA(ACRES) = 35916.66 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97

TOTAL AREA(ACRES) = 52419.9 PEAK FLOW RATE(CFS) = 33193.72

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT(FEET) = 7.88

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 7.88 FLOW VELOCITY(FEET/SEC.) = 17.59

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111792.96 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19189.15	17.42	2.248	0.30(0.25)	0.83	3706.6	410.00
2	19449.36	18.75	2.134	0.30(0.25)	0.83	4070.9	420.00
3	20541.26	22.71	1.885	0.30(0.25)	0.83	5147.1	310.00
4	20611.12	23.16	1.862	0.30(0.25)	0.83	5261.5	400.00
5	20612.88	23.17	1.862	0.30(0.25)	0.83	5265.2	800.00
6	21384.94	25.64	1.738	0.30(0.26)	0.85	6239.0	430.00
7	21608.96	26.34	1.708	0.30(0.26)	0.86	6516.2	300.00
8	21637.98	26.43	1.704	0.30(0.26)	0.86	6551.7	320.00
9	21986.39	27.63	1.651	0.30(0.26)	0.87	6996.7	900.00
10	22312.80	29.75	1.559	0.30(0.26)	0.88	7705.4	12730.00
11	22550.88	31.38	1.520	0.30(0.27)	0.88	8241.0	12710.00
12	22641.73	32.08	1.507	0.30(0.27)	0.89	8459.8	600.00
13	22675.93	32.34	1.501	0.30(0.27)	0.89	8553.0	390.00

14	25313.26	49.52	1.203	0.30(0.28)	0.93	14477.6	40100.00
15	26818.43	57.47	1.103	0.30(0.28)	0.94	17252.1	11801.00
16	29154.42	68.44	1.025	0.30(0.29)	0.95	21782.7	11530.00
17	30507.75	77.24	0.975	0.30(0.29)	0.96	26439.5	11910.00
18	32585.97	87.41	0.919	0.30(0.29)	0.97	32742.4	11350.00
19	33193.72	92.18	0.896	0.30(0.29)	0.97	35916.7	11130.00
20	33064.12	98.22	0.874	0.30(0.29)	0.97	38843.2	12300.00
21	32977.69	102.09	0.860	0.30(0.29)	0.97	40904.1	11620.00
22	32669.70	106.91	0.842	0.30(0.29)	0.97	43103.8	12400.00
23	31930.46	116.30	0.808	0.30(0.29)	0.97	46505.4	12201.00
24	31578.13	119.34	0.796	0.30(0.29)	0.97	47319.1	10410.00
25	31162.15	123.65	0.786	0.30(0.29)	0.97	48398.4	12231.00
26	30358.45	130.99	0.770	0.30(0.29)	0.97	49951.2	10400.00
27	29047.02	140.19	0.750	0.30(0.29)	0.97	51397.6	12010.00
28	28145.10	145.41	0.739	0.30(0.29)	0.98	51660.2	10210.00
29	27579.59	149.35	0.730	0.30(0.29)	0.98	51807.0	12000.00
30	24472.66	175.01	0.675	0.30(0.29)	0.98	52419.9	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 33193.72 Tc(MIN.) = 92.18

AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.97 EFFECTIVE AREA(ACRES) = 35916.66

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 92.18

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.896

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "GRASS"	B	3.90	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	8.70	0.30	1.000	69
NATURAL FAIR COVER "WOODLAND,GRASS"	B	10.30	0.30	1.000	65

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 22.90 SUBAREA RUNOFF(CFS) = 12.28

EFFECTIVE AREA(ACRES) = 35939.56 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97

TOTAL AREA(ACRES) = 52442.8 PEAK FLOW RATE(CFS) = 33193.72

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 52442.8 TC(MIN.) = 92.18

EFFECTIVE AREA(ACRES) = 35939.56 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.969

PEAK FLOW RATE(CFS) = 33193.72

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19189.15	17.42	2.248	0.30(0.25)	0.83	3729.5	410.00
2	19449.36	18.75	2.134	0.30(0.25)	0.83	4093.8	420.00
3	20541.26	22.71	1.885	0.30(0.25)	0.83	5170.0	310.00

4	20611.12	23.16	1.862	0.30	(0.25)	0.83	5284.4	400.00
5	20612.88	23.17	1.862	0.30	(0.25)	0.83	5288.1	800.00
6	21384.94	25.64	1.738	0.30	(0.26)	0.85	6261.9	430.00
7	21608.96	26.34	1.708	0.30	(0.26)	0.86	6539.1	300.00
8	21637.98	26.43	1.704	0.30	(0.26)	0.86	6574.6	320.00
9	21986.39	27.63	1.651	0.30	(0.26)	0.87	7019.6	900.00
10	22312.80	29.75	1.559	0.30	(0.26)	0.88	7728.3	12730.00
11	22550.88	31.38	1.520	0.30	(0.27)	0.89	8263.9	12710.00
12	22641.73	32.08	1.507	0.30	(0.27)	0.89	8482.7	600.00
13	22675.93	32.34	1.501	0.30	(0.27)	0.89	8575.9	390.00
14	25313.26	49.52	1.203	0.30	(0.28)	0.93	14500.5	40100.00
15	26818.43	57.47	1.103	0.30	(0.28)	0.94	17275.0	11801.00
16	29154.42	68.44	1.025	0.30	(0.29)	0.95	21805.6	11530.00
17	30507.75	77.24	0.975	0.30	(0.29)	0.96	26462.4	11910.00
18	32585.97	87.41	0.919	0.30	(0.29)	0.97	32765.3	11350.00
19	33193.72	92.18	0.896	0.30	(0.29)	0.97	35939.6	11130.00
20	33064.12	98.22	0.874	0.30	(0.29)	0.97	38866.1	12300.00
21	32977.69	102.09	0.860	0.30	(0.29)	0.97	40927.0	11620.00
22	32669.70	106.91	0.842	0.30	(0.29)	0.97	43126.7	12400.00
23	31930.46	116.30	0.808	0.30	(0.29)	0.97	46528.3	12201.00
24	31578.13	119.34	0.796	0.30	(0.29)	0.97	47342.0	10410.00
25	31162.15	123.65	0.786	0.30	(0.29)	0.97	48421.3	12231.00
26	30358.45	130.99	0.770	0.30	(0.29)	0.97	49974.1	10400.00
27	29047.02	140.19	0.750	0.30	(0.29)	0.97	51420.5	12010.00
28	28145.10	145.41	0.739	0.30	(0.29)	0.98	51683.1	10210.00
29	27579.59	149.35	0.730	0.30	(0.29)	0.98	51829.9	12000.00
30	24472.66	175.01	0.675	0.30	(0.29)	0.98	52442.8	10100.00

=====
 END OF RATIONAL METHOD ANALYSIS
 =====

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 128 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 25-YR EV FEB 2023 ROKAMOTO *

FILE NAME: RU25EV28.DAT
TIME/DATE OF STUDY: 15:22 02/07/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 25.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 4.947
- 2) 10.00; 3.222
- 3) 15.00; 2.455
- 4) 20.00; 2.027
- 5) 25.00; 1.766
- 6) 30.00; 1.548
- 7) 40.00; 1.349
- 8) 50.00; 1.196
- 9) 60.00; 1.072
- 10) 90.00; 0.904
- 11) 120.00; 0.794
- 12) 180.00; 0.664
- 13) 360.00; 0.492
- 14) 1200.00; 0.217

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU25EV27.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19449.36	18.75	0.30 (0.25)	0.83	4093.8	420.00
2	20612.88	23.17	0.30 (0.25)	0.83	5288.1	800.00
3	22675.93	32.34	0.30 (0.27)	0.89	8575.9	390.00
4	25313.26	49.52	0.30 (0.28)	0.93	14500.5	40100.00
5	26818.43	57.47	0.30 (0.28)	0.94	17275.0	11801.00
6	29154.42	68.44	0.30 (0.29)	0.95	21805.6	11530.00
7	30507.75	77.24	0.30 (0.29)	0.96	26462.4	11910.00
8	32585.97	87.41	0.30 (0.29)	0.97	32765.3	11350.00
9	33193.72	92.18	0.30 (0.29)	0.97	35939.6	11130.00
10	33064.12	98.22	0.30 (0.29)	0.97	38866.1	12300.00
11	32977.69	102.09	0.30 (0.29)	0.97	40927.0	11620.00
12	32669.70	106.91	0.30 (0.29)	0.97	43126.7	12400.00
13	31930.46	116.30	0.30 (0.29)	0.97	46528.3	12201.00
14	31578.13	119.34	0.30 (0.29)	0.97	47342.0	10410.00
15	31162.15	123.65	0.30 (0.29)	0.97	48421.3	12231.00
16	30358.45	130.99	0.30 (0.29)	0.97	49974.1	10400.00
17	29047.02	140.19	0.30 (0.29)	0.97	51420.5	12010.00
18	28145.10	145.41	0.30 (0.29)	0.98	51683.1	10210.00
19	27579.59	149.35	0.30 (0.29)	0.98	51829.9	12000.00
20	24472.66	175.01	0.30 (0.29)	0.98	52442.8	10100.00
TOTAL AREA (ACRES) =						52442.8

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: P501XX25.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	332.36	13.44	0.30 (0.25)	0.84	173.8	50110.00
2	350.43	18.02	0.30 (0.26)	0.85	223.2	50100.00
TOTAL AREA (ACRES) =						223.2

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
------------------	------------	--------------	----------------------	----	---------------	-------------------

1 332.36 13.44 0.30 (0.25) 0.84 173.8 50110.00
2 350.43 18.02 0.30 (0.26) 0.85 223.2 50100.00
TOTAL AREA (ACRES) = 223.2

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	332.36	13.44	2.694	0.30 (0.25)	0.84	173.8	50110.00
2	350.43	18.02	2.196	0.30 (0.26)	0.85	223.2	50100.00

LONGEST FLOWPATH FROM NODE 50100.00 TO NODE 12800.00 = 4170.00 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19449.36	18.75	2.134	0.30 (0.25)	0.83	4093.8	420.00
2	20612.88	23.17	1.862	0.30 (0.25)	0.83	5288.1	800.00
3	22675.93	32.34	1.501	0.30 (0.27)	0.89	8575.9	390.00
4	25313.26	49.52	1.203	0.30 (0.28)	0.93	14500.5	40100.00
5	26818.43	57.47	1.103	0.30 (0.28)	0.94	17275.0	11801.00
6	29154.42	68.44	1.025	0.30 (0.29)	0.95	21805.6	11530.00
7	30507.75	77.24	0.975	0.30 (0.29)	0.96	26462.4	11910.00
8	32585.97	87.41	0.919	0.30 (0.29)	0.97	32765.3	11350.00
9	33193.72	92.18	0.896	0.30 (0.29)	0.97	35939.6	11130.00
10	33064.12	98.22	0.874	0.30 (0.29)	0.97	38866.1	12300.00
11	32977.69	102.09	0.860	0.30 (0.29)	0.97	40927.0	11620.00
12	32669.70	106.91	0.842	0.30 (0.29)	0.97	43126.7	12400.00
13	31930.46	116.30	0.808	0.30 (0.29)	0.97	46528.3	12201.00
14	31578.13	119.34	0.796	0.30 (0.29)	0.97	47342.0	10410.00
15	31162.15	123.65	0.786	0.30 (0.29)	0.97	48421.3	12231.00
16	30358.45	130.99	0.770	0.30 (0.29)	0.97	49974.1	10400.00
17	29047.02	140.19	0.750	0.30 (0.29)	0.97	51420.5	12010.00
18	28145.10	145.41	0.739	0.30 (0.29)	0.98	51683.1	10210.00
19	27579.59	149.35	0.730	0.30 (0.29)	0.98	51829.9	12000.00
20	24472.66	175.01	0.675	0.30 (0.29)	0.98	52442.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111792.96 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18417.76	13.44	2.694	0.30 (0.25)	0.83	3108.4	50110.00
2	19662.81	18.02	2.196	0.30 (0.25)	0.83	4158.4	50100.00
3	19788.55	18.75	2.134	0.30 (0.25)	0.83	4317.0	420.00
4	20902.87	23.17	1.862	0.30 (0.25)	0.83	5511.3	800.00
5	22900.90	32.34	1.501	0.30 (0.27)	0.89	8799.1	390.00
6	25484.43	49.52	1.203	0.30 (0.28)	0.93	14723.7	40100.00
7	26971.56	57.47	1.103	0.30 (0.28)	0.94	17498.2	11801.00
8	29293.35	68.44	1.025	0.30 (0.29)	0.95	22028.8	11530.00
9	30637.79	77.24	0.975	0.30 (0.29)	0.96	26685.6	11910.00
10	32705.73	87.41	0.919	0.30 (0.29)	0.97	32988.5	11350.00
11	33309.41	92.18	0.896	0.30 (0.29)	0.97	36162.8	11130.00
12	33175.81	98.22	0.874	0.30 (0.29)	0.97	39089.3	12300.00
13	33086.82	102.09	0.860	0.30 (0.29)	0.97	41150.2	11620.00

14	32775.65	106.91	0.842	0.30 (0.29)	0.97	43349.9	12400.00
15	32030.19	116.30	0.808	0.30 (0.29)	0.97	46751.5	12201.00
16	31675.85	119.34	0.796	0.30 (0.29)	0.97	47565.2	10410.00
17	31258.00	123.65	0.786	0.30 (0.29)	0.97	48644.5	12231.00
18	30451.44	130.99	0.770	0.30 (0.29)	0.97	50197.3	10400.00
19	29136.40	140.19	0.750	0.30 (0.29)	0.97	51643.7	12010.00
20	28232.44	145.41	0.739	0.30 (0.29)	0.97	51906.3	10210.00
21	27665.39	149.35	0.730	0.30 (0.29)	0.97	52053.1	12000.00
22	24548.42	175.01	0.675	0.30 (0.29)	0.97	52666.0	10100.00

TOTAL AREA (ACRES) = 52666.0

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 33309.41 Tc (MIN.) = 92.178
EFFECTIVE AREA (ACRES) = 36162.76 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA (ACRES) = 52666.0
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111792.96 FEET.

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 52666.0 TC (MIN.) = 92.18
EFFECTIVE AREA (ACRES) = 36162.76 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.969
PEAK FLOW RATE (CFS) = 33309.41

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18417.76	13.44	2.694	0.30 (0.25)	0.83	3108.4	50110.00
2	19662.81	18.02	2.196	0.30 (0.25)	0.83	4158.4	50100.00
3	19788.55	18.75	2.134	0.30 (0.25)	0.83	4317.0	420.00
4	20902.87	23.17	1.862	0.30 (0.25)	0.83	5511.3	800.00
5	22900.90	32.34	1.501	0.30 (0.27)	0.89	8799.1	390.00
6	25484.43	49.52	1.203	0.30 (0.28)	0.93	14723.7	40100.00
7	26971.56	57.47	1.103	0.30 (0.28)	0.94	17498.2	11801.00
8	29293.35	68.44	1.025	0.30 (0.29)	0.95	22028.8	11530.00
9	30637.79	77.24	0.975	0.30 (0.29)	0.96	26685.6	11910.00
10	32705.73	87.41	0.919	0.30 (0.29)	0.97	32988.5	11350.00
11	33309.41	92.18	0.896	0.30 (0.29)	0.97	36162.8	11130.00
12	33175.81	98.22	0.874	0.30 (0.29)	0.97	39089.3	12300.00
13	33086.82	102.09	0.860	0.30 (0.29)	0.97	41150.2	11620.00
14	32775.65	106.91	0.842	0.30 (0.29)	0.97	43349.9	12400.00
15	32030.19	116.30	0.808	0.30 (0.29)	0.97	46751.5	12201.00
16	31675.85	119.34	0.796	0.30 (0.29)	0.97	47565.2	10410.00
17	31258.00	123.65	0.786	0.30 (0.29)	0.97	48644.5	12231.00
18	30451.44	130.99	0.770	0.30 (0.29)	0.97	50197.3	10400.00
19	29136.40	140.19	0.750	0.30 (0.29)	0.97	51643.7	12010.00
20	28232.44	145.41	0.739	0.30 (0.29)	0.97	51906.3	10210.00
21	27665.39	149.35	0.730	0.30 (0.29)	0.97	52053.1	12000.00
22	24548.42	175.01	0.675	0.30 (0.29)	0.97	52666.0	10100.00

END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 129 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 25-YR EV FEB 2023 ROKAMOTO *

FILE NAME: RU25EV29.DAT
TIME/DATE OF STUDY: 15:22 02/07/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 25.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 4.919
- 2) 10.00; 3.206
- 3) 15.00; 2.446
- 4) 20.00; 2.020
- 5) 25.00; 1.761
- 6) 30.00; 1.545
- 7) 40.00; 1.345
- 8) 50.00; 1.192
- 9) 60.00; 1.068
- 10) 90.00; 0.899
- 11) 120.00; 0.789
- 12) 180.00; 0.660
- 13) 360.00; 0.488
- 14) 1200.00; 0.215

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU25EV28.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18417.76	13.44	0.30 (0.25)	0.83	3108.4	50110.00
2	19788.55	18.75	0.30 (0.25)	0.83	4317.0	420.00
3	20902.87	23.17	0.30 (0.25)	0.83	5511.3	800.00
4	22900.90	32.34	0.30 (0.27)	0.89	8799.1	390.00
5	25484.43	49.52	0.30 (0.28)	0.93	14723.7	40100.00
6	26971.56	57.47	0.30 (0.28)	0.94	17498.2	11801.00
7	29293.35	68.44	0.30 (0.29)	0.95	22028.8	11530.00
8	30637.79	77.24	0.30 (0.29)	0.96	26685.6	11910.00
9	32705.73	87.41	0.30 (0.29)	0.97	32988.5	11350.00
10	33309.41	92.18	0.30 (0.29)	0.97	36162.8	11130.00
11	33175.81	98.22	0.30 (0.29)	0.97	39089.3	12300.00
12	33086.82	102.09	0.30 (0.29)	0.97	41150.2	11620.00
13	32775.65	106.91	0.30 (0.29)	0.97	43349.9	12400.00
14	32030.19	116.30	0.30 (0.29)	0.97	46751.5	12201.00
15	31258.00	123.65	0.30 (0.29)	0.97	48644.5	12231.00
16	30451.44	130.99	0.30 (0.29)	0.97	50197.3	10400.00
17	29136.40	140.19	0.30 (0.29)	0.97	51643.7	12010.00
18	28232.44	145.41	0.30 (0.29)	0.97	51906.3	10210.00
19	27665.39	149.35	0.30 (0.29)	0.97	52053.1	12000.00
20	24548.42	175.01	0.30 (0.29)	0.97	52666.0	10100.00
TOTAL AREA (ACRES) =						52666.0

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18417.76	13.44	0.30 (0.25)	0.83	3108.4	50110.00
2	19788.55	18.75	0.30 (0.25)	0.83	4317.0	420.00
3	20902.87	23.17	0.30 (0.25)	0.83	5511.3	800.00
4	22900.90	32.34	0.30 (0.27)	0.89	8799.1	390.00
5	25484.43	49.52	0.30 (0.28)	0.93	14723.7	40100.00
6	26971.56	57.47	0.30 (0.28)	0.94	17498.2	11801.00
7	29293.35	68.44	0.30 (0.29)	0.95	22028.8	11530.00
8	30637.79	77.24	0.30 (0.29)	0.96	26685.6	11910.00
9	32705.73	87.41	0.30 (0.29)	0.97	32988.5	11350.00
10	33309.41	92.18	0.30 (0.29)	0.97	36162.8	11130.00
11	33175.81	98.22	0.30 (0.29)	0.97	39089.3	12300.00
12	33086.82	102.09	0.30 (0.29)	0.97	41150.2	11620.00
13	32775.65	106.91	0.30 (0.29)	0.97	43349.9	12400.00

14 32030.19 116.30 0.30(0.29) 0.97 46751.5 12201.00
 15 31258.00 123.65 0.30(0.29) 0.97 48644.5 12231.00
 16 30451.44 130.99 0.30(0.29) 0.97 50197.3 10400.00
 17 29136.40 140.19 0.30(0.29) 0.97 51643.7 12010.00
 18 28232.44 145.41 0.30(0.29) 0.97 51906.3 10210.00
 19 27665.39 149.35 0.30(0.29) 0.97 52053.1 12000.00
 20 24548.42 175.01 0.30(0.29) 0.97 52666.0 10100.00
 TOTAL AREA(ACRES) = 52666.0

 FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

 FLOW PROCESS FROM NODE 12800.00 TO NODE 12901.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 240.00 DOWNSTREAM(FEET) = 216.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 3120.28 CHANNEL SLOPE = 0.0077
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 8.49
 CHANNEL FLOW THRU SUBAREA(CFS) = 33309.41
 FLOW VELOCITY(FEET/SEC.) = 16.17 FLOW DEPTH(FEET) = 8.49
 TRAVEL TIME(MIN.) = 3.22 Tc(MIN.) = 95.39
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12901.00 = 114913.24 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18417.76	17.37	2.244	0.30(0.25)	0.83	3108.4	50110.00
2	19788.55	22.58	1.886	0.30(0.25)	0.83	4317.0	420.00
3	20902.87	26.93	1.678	0.30(0.25)	0.83	5511.3	800.00
4	22900.90	35.99	1.425	0.30(0.27)	0.89	8799.1	390.00
5	25484.43	53.04	1.154	0.30(0.28)	0.93	14723.7	40100.00
6	26971.56	60.92	1.063	0.30(0.28)	0.94	17498.2	11801.00
7	29293.35	71.79	1.002	0.30(0.29)	0.95	22028.8	11530.00
8	30637.79	80.54	0.952	0.30(0.29)	0.96	26685.6	11910.00
9	32705.73	90.64	0.897	0.30(0.29)	0.97	32988.5	11350.00
10	33309.41	95.39	0.879	0.30(0.29)	0.97	36162.8	11130.00
11	33175.81	101.44	0.857	0.30(0.29)	0.97	39089.3	12300.00
12	33086.82	105.32	0.843	0.30(0.29)	0.97	41150.2	11620.00
13	32775.65	110.14	0.825	0.30(0.29)	0.97	43349.9	12400.00
14	32030.19	119.55	0.791	0.30(0.29)	0.97	46751.5	12201.00
15	31258.00	126.93	0.774	0.30(0.29)	0.97	48644.5	12231.00
16	30451.44	134.30	0.758	0.30(0.29)	0.97	50197.3	10400.00
17	29136.40	143.56	0.738	0.30(0.29)	0.97	51643.7	12010.00
18	28232.44	148.81	0.727	0.30(0.29)	0.97	51906.3	10210.00
19	27665.39	152.77	0.719	0.30(0.29)	0.97	52053.1	12000.00
20	24548.42	178.57	0.663	0.30(0.29)	0.97	52666.0	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 33309.41 Tc(MIN.) = 95.39
 AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.97 EFFECTIVE AREA(ACRES) = 36162.76

 FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 95.39
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.879
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 COMMERCIAL B 14.30 0.30 0.100 56
 PUBLIC PARK B 9.40 0.30 0.850 56
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.397
 SUBAREA AREA(ACRES) = 23.70 SUBAREA RUNOFF(CFS) = 16.21
 EFFECTIVE AREA(ACRES) = 36186.46 AREA-AVERAGED Fm(INCH/HR) = 0.29
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA(ACRES) = 52689.7 PEAK FLOW RATE(CFS) = 33309.41
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 95.39
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.879
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 COMMERCIAL B 0.20 0.30 0.100 56
 RESIDENTIAL
 "5-7 DWELLINGS/ACRE" B 0.40 0.30 0.500 56
 RESIDENTIAL
 ".4 DWELLING/ACRE" B 0.50 0.30 0.900 56
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 0.60 0.30 1.000 65
 COMMERCIAL B 0.70 0.30 0.100 56
 RESIDENTIAL
 ".4 DWELLING/ACRE" B 0.70 0.30 0.900 56
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.635
 SUBAREA AREA(ACRES) = 3.10 SUBAREA RUNOFF(CFS) = 1.92
 EFFECTIVE AREA(ACRES) = 36189.56 AREA-AVERAGED Fm(INCH/HR) = 0.29
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA(ACRES) = 52692.8 PEAK FLOW RATE(CFS) = 33309.41
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 95.39
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.879
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS

LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
PUBLIC PARK B 0.70 0.30 0.850 56
NATURAL FAIR COVER
"WOODLAND,GRASS" B 1.00 0.30 1.000 65
NATURAL FAIR COVER
"OPEN BRUSH" B 1.40 0.30 1.000 66
NATURAL FAIR COVER
"GRASS" B 1.50 0.30 1.000 69
COMMERCIAL B 1.70 0.30 0.100 56
NATURAL FAIR COVER
"OPEN BRUSH" B 2.90 0.30 1.000 66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.822
SUBAREA AREA(ACRES) = 9.20 SUBAREA RUNOFF(CFS) = 5.24
EFFECTIVE AREA(ACRES) = 36198.76 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 52702.0 PEAK FLOW RATE(CFS) = 33309.41
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 95.39
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.879
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "WOODLAND,GRASS"	B	3.60	0.30	1.000	65
RESIDENTIAL "5-7 DWELLINGS/ACRE"	B	3.70	0.30	0.500	56
RESIDENTIAL "5-7 DWELLINGS/ACRE"	B	4.10	0.30	0.500	56
RESIDENTIAL ".4 DWELLING/ACRE"	B	5.40	0.30	0.900	56
NATURAL FAIR COVER "OPEN BRUSH"	B	6.70	0.30	1.000	66
NATURAL POOR COVER "BARREN"	B	12.00	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.875
SUBAREA AREA(ACRES) = 35.50 SUBAREA RUNOFF(CFS) = 19.71
EFFECTIVE AREA(ACRES) = 36234.26 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 52737.5 PEAK FLOW RATE(CFS) = 33309.41
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 95.39
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.879
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"GRASS" B 12.90 0.30 1.000 69
PUBLIC PARK B 38.60 0.30 0.850 56
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.888
SUBAREA AREA(ACRES) = 51.50 SUBAREA RUNOFF(CFS) = 28.41
EFFECTIVE AREA(ACRES) = 36285.76 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 52789.0 PEAK FLOW RATE(CFS) = 33309.41
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12901.00 TO NODE 12902.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 216.00 DOWNSTREAM(FEET) = 215.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 122.04 CHANNEL SLOPE = 0.0082
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 8.34
CHANNEL FLOW THRU SUBAREA(CFS) = 33309.41
FLOW VELOCITY(FEET/SEC.) = 16.52 FLOW DEPTH(FEET) = 8.34
TRAVEL TIME(MIN.) = 0.12 Tc(MIN.) = 95.52
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115035.28 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18417.76	17.52	2.231	0.30(0.25)	0.83	3231.4	50110.00
2	19788.55	22.73	1.879	0.30(0.25)	0.83	4440.0	420.00
3	20902.87	27.08	1.671	0.30(0.25)	0.83	5634.3	800.00
4	22900.90	36.13	1.422	0.30(0.27)	0.89	8922.1	390.00
5	25484.43	53.17	1.153	0.30(0.28)	0.93	14846.7	40100.00
6	26971.56	61.05	1.062	0.30(0.28)	0.94	17621.2	11801.00
7	29293.35	71.92	1.001	0.30(0.29)	0.95	22151.8	11530.00
8	30637.79	80.67	0.952	0.30(0.29)	0.96	26808.6	11910.00
9	32705.73	90.76	0.896	0.30(0.29)	0.97	33111.5	11350.00
10	33309.41	95.52	0.879	0.30(0.29)	0.97	36285.8	11130.00
11	33175.81	101.56	0.857	0.30(0.29)	0.97	39212.3	12300.00
12	33086.82	105.44	0.842	0.30(0.29)	0.97	41273.2	11620.00
13	32775.65	110.27	0.825	0.30(0.29)	0.97	43472.9	12400.00
14	32030.19	119.68	0.790	0.30(0.29)	0.97	46874.5	12201.00
15	31258.00	127.06	0.774	0.30(0.29)	0.97	48767.5	1231.00
16	30451.44	134.43	0.758	0.30(0.29)	0.97	50320.3	10400.00
17	29136.40	143.68	0.738	0.30(0.29)	0.97	51766.7	12010.00
18	28232.44	148.94	0.727	0.30(0.29)	0.97	52029.3	10210.00
19	27665.39	152.91	0.718	0.30(0.29)	0.97	52176.1	12000.00
20	24548.42	178.71	0.663	0.30(0.29)	0.97	52789.0	10100.00

NEW PEAK FLOW DATA ARE:
PEAK FLOW RATE(CFS) = 33309.41 Tc(MIN.) = 95.52
AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.97 EFFECTIVE AREA(ACRES) = 36285.76

FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 15.1

=====
>>>>DEFINE MEMORY BANK # 1 <<<<
=====

PEAK FLOWRATE TABLE FILE NAME: P503XX25.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1550.55	18.97	0.30	(0.22)	0.74	1028.1	50320.00
2	1548.96	19.87	0.30	(0.22)	0.74	1064.5	50240.00
3	1557.87	20.83	0.30	(0.22)	0.74	1101.6	50330.00
4	1557.26	23.76	0.30	(0.22)	0.74	1199.8	50280.00
5	1537.88	24.97	0.30	(0.22)	0.74	1230.2	50300.00
6	1519.40	26.29	0.30	(0.22)	0.74	1253.8	50220.00
7	1413.89	30.55	0.30	(0.22)	0.74	1292.3	50260.00
8	1346.29	33.44	0.30	(0.22)	0.74	1298.6	50200.00
TOTAL AREA (ACRES) =							1298.6

FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<
=====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18417.76	17.52	2.231	0.30	(0.25)	0.83	3231.4 50110.00
2	19788.55	22.73	1.879	0.30	(0.25)	0.83	4440.0 420.00
3	20902.87	27.08	1.671	0.30	(0.25)	0.83	5634.3 800.00
4	22900.90	36.13	1.422	0.30	(0.27)	0.89	8922.1 390.00
5	25484.43	53.17	1.153	0.30	(0.28)	0.93	14846.7 40100.00
6	26971.56	61.05	1.062	0.30	(0.28)	0.94	17621.2 11801.00
7	29293.35	71.92	1.001	0.30	(0.29)	0.95	22151.8 11530.00
8	30637.79	80.67	0.952	0.30	(0.29)	0.96	26808.6 11910.00
9	32705.73	90.76	0.896	0.30	(0.29)	0.97	33111.5 11350.00
10	33309.41	95.52	0.879	0.30	(0.29)	0.97	36285.8 11130.00
11	33175.81	101.56	0.857	0.30	(0.29)	0.97	39212.3 12300.00
12	33086.82	105.44	0.842	0.30	(0.29)	0.97	41273.2 11620.00
13	32775.65	110.27	0.825	0.30	(0.29)	0.97	43472.9 12400.00
14	32030.19	119.68	0.790	0.30	(0.29)	0.97	46874.5 12201.00
15	31258.00	127.06	0.774	0.30	(0.29)	0.97	48767.5 12231.00
16	30451.44	134.43	0.758	0.30	(0.29)	0.97	50320.3 10400.00
17	29136.40	143.68	0.738	0.30	(0.29)	0.97	51766.7 12010.00
18	28232.44	148.94	0.727	0.30	(0.29)	0.97	52029.3 10210.00
19	27665.39	152.91	0.718	0.30	(0.29)	0.97	52176.1 12000.00
20	24548.42	178.71	0.663	0.30	(0.29)	0.97	52789.0 10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 =							115035.28 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1550.55	18.97	2.108	0.30	(0.22)	0.74	1028.1 50320.00
2	1548.96	19.87	2.031	0.30	(0.22)	0.74	1064.5 50240.00
3	1557.87	20.83	1.977	0.30	(0.22)	0.74	1101.6 50330.00
4	1557.26	23.76	1.825	0.30	(0.22)	0.74	1199.8 50280.00
5	1537.88	24.97	1.762	0.30	(0.22)	0.74	1230.2 50300.00
6	1519.40	26.29	1.705	0.30	(0.22)	0.74	1253.8 50220.00
7	1413.89	30.55	1.534	0.30	(0.22)	0.74	1292.3 50260.00

8 1346.29 33.44 1.476 0.30(0.22) 0.74 1298.6 50200.00
LONGEST FLOWPATH FROM NODE 50220.00 TO NODE 12902.00 = 17597.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19943.59	17.52	2.231	0.30	(0.24)	0.81	4180.8 50110.00
2	20350.57	18.97	2.108	0.30	(0.24)	0.81	4596.6 50320.00
3	20584.34	19.87	2.031	0.30	(0.24)	0.81	4840.5 50240.00
4	20847.06	20.83	1.977	0.30	(0.24)	0.81	5101.4 50330.00
5	21346.03	22.73	1.879	0.30	(0.24)	0.81	5605.1 420.00
6	21611.70	23.76	1.825	0.30	(0.24)	0.81	5924.8 50280.00
7	21902.13	24.97	1.762	0.30	(0.24)	0.81	6287.2 50300.00
8	22220.39	26.29	1.705	0.30	(0.24)	0.82	6671.7 50220.00
9	22402.74	27.08	1.671	0.30	(0.24)	0.82	6895.2 800.00
10	23082.66	30.55	1.534	0.30	(0.25)	0.84	8186.9 50260.00
11	23652.76	33.44	1.476	0.30	(0.26)	0.85	9242.6 50200.00
12	24189.34	36.13	1.422	0.30	(0.26)	0.87	10220.7 390.00
13	26483.24	53.17	1.153	0.30	(0.27)	0.91	16145.3 40100.00
14	27873.11	61.05	1.062	0.30	(0.28)	0.93	18919.8 11801.00
15	30129.13	71.92	1.001	0.30	(0.28)	0.94	23450.4 11530.00
16	31420.65	80.67	0.952	0.30	(0.28)	0.95	28107.2 11910.00
17	33429.15	90.76	0.896	0.30	(0.29)	0.96	34410.1 11350.00
18	34014.12	95.52	0.879	0.30	(0.29)	0.96	37584.4 11130.00
19	33856.72	101.56	0.857	0.30	(0.29)	0.96	40510.9 12300.00
20	33752.46	105.44	0.842	0.30	(0.29)	0.96	42571.8 11620.00
21	33422.29	110.27	0.825	0.30	(0.29)	0.97	44771.5 12400.00
22	32639.76	119.68	0.790	0.30	(0.29)	0.97	48173.1 12201.00
23	31850.01	127.06	0.774	0.30	(0.29)	0.97	50066.1 12231.00
24	31026.44	134.43	0.758	0.30	(0.29)	0.97	51618.9 10400.00
25	29690.03	143.68	0.738	0.30	(0.29)	0.97	53065.3 12010.00
26	28773.95	148.94	0.727	0.30	(0.29)	0.97	53327.9 10210.00
27	28197.74	152.91	0.718	0.30	(0.29)	0.97	53474.7 12000.00
28	25021.19	178.71	0.663	0.30	(0.29)	0.97	54087.6 10100.00
TOTAL AREA (ACRES) =							54087.6

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 34014.12 Tc(MIN.) = 95.516
EFFECTIVE AREA(ACRES) = 37584.36 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
TOTAL AREA(ACRES) = 54087.6
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115035.28 FEET.

FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<
=====

FLOW PROCESS FROM NODE 12902.00 TO NODE 12903.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<
=====

ELEVATION DATA: UPSTREAM(FEET) = 215.00 DOWNSTREAM(FEET) = 214.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 895.53 CHANNEL SLOPE = 0.0011
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 14.73
 CHANNEL FLOW THRU SUBAREA(CFS) = 34014.12
 FLOW VELOCITY(FEET/SEC.) = 8.44 FLOW DEPTH(FEET) = 14.73
 TRAVEL TIME(MIN.) = 1.77 Tc(MIN.) = 97.29
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115930.81 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19943.59	19.61	2.053	0.30(0.24)	0.81	4180.8	50110.00
2	20350.57	21.05	1.966	0.30(0.24)	0.81	4596.6	50320.00
3	20584.34	21.94	1.920	0.30(0.24)	0.81	4840.5	50240.00
4	20847.06	22.89	1.870	0.30(0.24)	0.81	5101.4	50330.00
5	21346.03	24.77	1.773	0.30(0.24)	0.81	5605.1	420.00
6	21611.70	25.80	1.726	0.30(0.24)	0.81	5924.8	50280.00
7	21902.13	27.00	1.674	0.30(0.24)	0.81	6287.2	50300.00
8	22220.39	28.31	1.618	0.30(0.24)	0.82	6671.7	50220.00
9	22402.74	29.09	1.584	0.30(0.24)	0.82	6895.2	800.00
10	23082.66	32.54	1.494	0.30(0.25)	0.84	8186.9	50260.00
11	23652.76	35.42	1.437	0.30(0.26)	0.85	9242.6	50200.00
12	24189.34	38.10	1.383	0.30(0.26)	0.87	10220.7	390.00
13	26483.24	55.08	1.129	0.30(0.27)	0.91	16145.3	40100.00
14	27873.11	62.93	1.051	0.30(0.28)	0.93	18919.8	11801.00
15	30129.13	73.76	0.990	0.30(0.28)	0.94	23450.4	11530.00
16	31420.65	82.48	0.941	0.30(0.28)	0.95	28107.2	11910.00
17	33429.15	92.54	0.890	0.30(0.29)	0.96	34410.1	11350.00
18	34014.12	97.29	0.872	0.30(0.29)	0.96	37584.4	11130.00
19	33856.72	103.33	0.850	0.30(0.29)	0.96	40510.9	12300.00
20	33752.46	107.21	0.836	0.30(0.29)	0.96	42571.8	11620.00
21	33422.29	112.04	0.818	0.30(0.29)	0.97	44771.5	12400.00
22	32639.76	121.47	0.786	0.30(0.29)	0.97	48173.1	12201.00
23	31850.01	128.86	0.770	0.30(0.29)	0.97	50066.1	12231.00
24	31026.44	136.25	0.754	0.30(0.29)	0.97	51618.9	10400.00
25	29690.03	145.53	0.734	0.30(0.29)	0.97	53065.3	12010.00
26	28773.95	150.80	0.723	0.30(0.29)	0.97	53327.9	10210.00
27	28197.74	154.78	0.714	0.30(0.29)	0.97	53474.7	12000.00
28	25021.19	180.66	0.659	0.30(0.29)	0.97	54087.6	10100.00

NEW PEAK FLOW DATA ARE:
 PEAK FLOW RATE(CFS) = 34014.12 Tc(MIN.) = 97.29
 AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.96 EFFECTIVE AREA(ACRES) = 37584.36

 FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P504XX25.DNA
 MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	128.78	13.45	0.30(0.28)	0.94	70.7	50400.00
TOTAL AREA(ACRES) =		70.7				

 FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<
 =====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19943.59	19.61	2.053	0.30(0.24)	0.81	4180.8	50110.00
2	20350.57	21.05	1.966	0.30(0.24)	0.81	4596.6	50320.00
3	20584.34	21.94	1.920	0.30(0.24)	0.81	4840.5	50240.00
4	20847.06	22.89	1.870	0.30(0.24)	0.81	5101.4	50330.00
5	21346.03	24.77	1.773	0.30(0.24)	0.81	5605.1	420.00
6	21611.70	25.80	1.726	0.30(0.24)	0.81	5924.8	50280.00
7	21902.13	27.00	1.674	0.30(0.24)	0.81	6287.2	50300.00
8	22220.39	28.31	1.618	0.30(0.24)	0.82	6671.7	50220.00
9	22402.74	29.09	1.584	0.30(0.24)	0.82	6895.2	800.00
10	23082.66	32.54	1.494	0.30(0.25)	0.84	8186.9	50260.00
11	23652.76	35.42	1.437	0.30(0.26)	0.85	9242.6	50200.00
12	24189.34	38.10	1.383	0.30(0.26)	0.87	10220.7	390.00
13	26483.24	55.08	1.129	0.30(0.27)	0.91	16145.3	40100.00
14	27873.11	62.93	1.051	0.30(0.28)	0.93	18919.8	11801.00
15	30129.13	73.76	0.990	0.30(0.28)	0.94	23450.4	11530.00
16	31420.65	82.48	0.941	0.30(0.28)	0.95	28107.2	11910.00
17	33429.15	92.54	0.890	0.30(0.29)	0.96	34410.1	11350.00
18	34014.12	97.29	0.872	0.30(0.29)	0.96	37584.4	11130.00
19	33856.72	103.33	0.850	0.30(0.29)	0.96	40510.9	12300.00
20	33752.46	107.21	0.836	0.30(0.29)	0.96	42571.8	11620.00
21	33422.29	112.04	0.818	0.30(0.29)	0.97	44771.5	12400.00
22	32639.76	121.47	0.786	0.30(0.29)	0.97	48173.1	12201.00
23	31850.01	128.86	0.770	0.30(0.29)	0.97	50066.1	12231.00
24	31026.44	136.25	0.754	0.30(0.29)	0.97	51618.9	10400.00
25	29690.03	145.53	0.734	0.30(0.29)	0.97	53065.3	12010.00
26	28773.95	150.80	0.723	0.30(0.29)	0.97	53327.9	10210.00
27	28197.74	154.78	0.714	0.30(0.29)	0.97	53474.7	12000.00
28	25021.19	180.66	0.659	0.30(0.29)	0.97	54087.6	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115930.81 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	128.78	13.45	2.682	0.30(0.28)	0.94	70.7	50400.00

LONGEST FLOWPATH FROM NODE 50400.00 TO NODE 12903.00 = 3607.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18554.10	13.45	2.682	0.30(0.24)	0.81	2937.8	50400.00
2	20038.65	19.61	2.053	0.30(0.24)	0.81	4251.5	50110.00
3	20440.93	21.05	1.966	0.30(0.24)	0.81	4667.3	50320.00
4	20672.23	21.94	1.920	0.30(0.24)	0.81	4911.2	50240.00
5	20932.30	22.89	1.870	0.30(0.24)	0.81	5172.1	50330.00
6	21426.04	24.77	1.773	0.30(0.24)	0.81	5675.8	420.00
7	21689.22	25.80	1.726	0.30(0.24)	0.81	5995.5	50280.00
8	21976.87	27.00	1.674	0.30(0.24)	0.82	6357.9	50300.00
9	22292.11	28.31	1.618	0.30(0.24)	0.82	6742.4	50220.00
10	22472.64	29.09	1.584	0.30(0.25)	0.82	6965.9	800.00
11	23147.72	32.54	1.494	0.30(0.25)	0.84	8257.6	50260.00
12	23714.74	35.42	1.437	0.30(0.26)	0.85	9313.3	50200.00
13	24248.45	38.10	1.383	0.30(0.26)	0.87	10291.4	390.00

14	26528.71	55.08	1.129	0.30	(0.27)	0.91	16216.0	40100.00
15	27914.43	62.93	1.051	0.30	(0.28)	0.93	18990.5	11801.00
16	30167.17	73.76	0.990	0.30	(0.28)	0.94	23521.1	11530.00
17	31456.06	82.48	0.941	0.30	(0.28)	0.95	28177.9	11910.00
18	33461.79	92.54	0.890	0.30	(0.29)	0.96	34480.8	11350.00
19	34045.83	97.29	0.872	0.30	(0.29)	0.96	37655.1	11130.00
20	33887.23	103.33	0.850	0.30	(0.29)	0.96	40581.6	12300.00
21	33782.21	107.21	0.836	0.30	(0.29)	0.96	42642.5	11620.00
22	33451.09	112.04	0.818	0.30	(0.29)	0.96	44842.2	12400.00
23	32666.83	121.47	0.786	0.30	(0.29)	0.97	48243.8	12201.00
24	31876.23	128.86	0.770	0.30	(0.29)	0.97	50136.8	12231.00
25	31051.80	136.25	0.754	0.30	(0.29)	0.97	51689.6	10400.00
26	29714.33	145.53	0.734	0.30	(0.29)	0.97	53136.0	12010.00
27	28797.63	150.80	0.723	0.30	(0.29)	0.97	53398.6	10210.00
28	28220.96	154.78	0.714	0.30	(0.29)	0.97	53545.4	12000.00
29	25041.47	180.66	0.659	0.30	(0.29)	0.97	54158.3	10100.00

TOTAL AREA (ACRES) = 54158.3

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 34045.83 Tc(MIN.) = 97.285
EFFECTIVE AREA (ACRES) = 37655.06 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA (ACRES) = 54158.3
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115930.81 FEET.

FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

FLOW PROCESS FROM NODE 12903.00 TO NODE 12904.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 214.00 DOWNSTREAM(FEET) = 213.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 767.57 CHANNEL SLOPE = 0.0013
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 14.13
CHANNEL FLOW THRU SUBAREA(CFS) = 34045.83
FLOW VELOCITY(FEET/SEC.) = 8.91 FLOW DEPTH(FEET) = 14.13
TRAVEL TIME(MIN.) = 1.44 Tc(MIN.) = 98.72
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116698.38 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18554.10	15.19	2.430	0.30 (0.24)	0.81	2937.8	50400.00
2	20038.65	21.31	1.952	0.30 (0.24)	0.81	4251.5	50110.00
3	20440.93	22.74	1.878	0.30 (0.24)	0.81	4667.3	50320.00
4	20672.23	23.62	1.833	0.30 (0.24)	0.81	4911.2	50240.00
5	20932.30	24.56	1.784	0.30 (0.24)	0.81	5172.1	50330.00
6	21426.04	26.43	1.699	0.30 (0.24)	0.81	5675.8	420.00
7	21689.22	27.46	1.655	0.30 (0.24)	0.81	5995.5	50280.00
8	21976.87	28.65	1.603	0.30 (0.24)	0.82	6357.9	50300.00

9	22292.11	29.95	1.547	0.30	(0.24)	0.82	6742.4	50220.00
10	22472.64	30.73	1.530	0.30	(0.25)	0.82	6965.9	800.00
11	23147.72	34.16	1.462	0.30	(0.25)	0.84	8257.6	50260.00
12	23714.74	37.03	1.404	0.30	(0.26)	0.85	9313.3	50200.00
13	24248.45	39.69	1.351	0.30	(0.26)	0.87	10291.4	390.00
14	26528.71	56.64	1.110	0.30	(0.27)	0.91	16216.0	40100.00
15	27914.43	64.46	1.043	0.30	(0.28)	0.93	18990.5	11801.00
16	30167.17	75.25	0.982	0.30	(0.28)	0.94	23521.1	11530.00
17	31456.06	83.96	0.933	0.30	(0.28)	0.95	28177.9	11910.00
18	33461.79	93.99	0.884	0.30	(0.29)	0.96	34480.8	11350.00
19	34045.83	98.72	0.867	0.30	(0.29)	0.96	37655.1	11130.00
20	33887.23	104.77	0.845	0.30	(0.29)	0.96	40581.6	12300.00
21	33782.21	108.65	0.831	0.30	(0.29)	0.96	42642.5	11620.00
22	33451.09	113.49	0.813	0.30	(0.29)	0.96	44842.2	12400.00
23	32666.83	122.93	0.783	0.30	(0.29)	0.97	48243.8	12201.00
24	31876.23	130.33	0.767	0.30	(0.29)	0.97	50136.8	12231.00
25	31051.80	137.73	0.751	0.30	(0.29)	0.97	51689.6	10400.00
26	29714.33	147.03	0.731	0.30	(0.29)	0.97	53136.0	12010.00
27	28797.63	152.31	0.720	0.30	(0.29)	0.97	53398.6	10210.00
28	28220.96	156.30	0.711	0.30	(0.29)	0.97	53545.4	12000.00
29	25041.47	182.24	0.658	0.30	(0.29)	0.97	54158.3	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 34045.83 Tc(MIN.) = 98.72
AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.96 EFFECTIVE AREA (ACRES) = 37655.06

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 3B25EVRL.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	381.83	16.87	0.30 (0.13)	0.43	196.7	203.00
2	375.17	19.31	0.30 (0.13)	0.43	213.7	210.00
TOTAL AREA (ACRES) =			213.7			

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18554.10	15.19	2.430	0.30 (0.24)	0.81	2937.8	50400.00
2	20038.65	21.31	1.952	0.30 (0.24)	0.81	4251.5	50110.00
3	20440.93	22.74	1.878	0.30 (0.24)	0.81	4667.3	50320.00
4	20672.23	23.62	1.833	0.30 (0.24)	0.81	4911.2	50240.00
5	20932.30	24.56	1.784	0.30 (0.24)	0.81	5172.1	50330.00
6	21426.04	26.43	1.699	0.30 (0.24)	0.81	5675.8	420.00
7	21689.22	27.46	1.655	0.30 (0.24)	0.81	5995.5	50280.00
8	21976.87	28.65	1.603	0.30 (0.24)	0.82	6357.9	50300.00
9	22292.11	29.95	1.547	0.30 (0.24)	0.82	6742.4	50220.00
10	22472.64	30.73	1.530	0.30 (0.25)	0.82	6965.9	800.00

11	23147.72	34.16	1.462	0.30 (0.25)	0.84	8257.6	50260.00
12	23714.74	37.03	1.404	0.30 (0.26)	0.85	9313.3	50200.00
13	24248.45	39.69	1.351	0.30 (0.26)	0.87	10291.4	390.00
14	26528.71	56.64	1.110	0.30 (0.27)	0.91	16216.0	40100.00
15	27914.43	64.46	1.043	0.30 (0.28)	0.93	18990.5	11801.00
16	30167.17	75.25	0.982	0.30 (0.28)	0.94	23521.1	11530.00
17	31456.06	83.96	0.933	0.30 (0.28)	0.95	28177.9	11910.00
18	33461.79	93.99	0.884	0.30 (0.29)	0.96	34480.8	11350.00
19	34045.83	98.72	0.867	0.30 (0.29)	0.96	37655.1	11130.00
20	33887.23	104.77	0.845	0.30 (0.29)	0.96	40581.6	12300.00
21	33782.21	108.65	0.831	0.30 (0.29)	0.96	42642.5	11620.00
22	33451.09	113.49	0.813	0.30 (0.29)	0.96	44842.2	12400.00
23	32666.83	122.93	0.783	0.30 (0.29)	0.97	48243.8	12201.00
24	31876.23	130.33	0.767	0.30 (0.29)	0.97	50136.8	12231.00
25	31051.80	137.73	0.751	0.30 (0.29)	0.97	51689.6	10400.00
26	29714.33	147.03	0.731	0.30 (0.29)	0.97	53136.0	12010.00
27	28797.63	152.31	0.720	0.30 (0.29)	0.97	53398.6	10210.00
28	28220.96	156.30	0.711	0.30 (0.29)	0.97	53545.4	12000.00
29	25041.47	182.24	0.658	0.30 (0.29)	0.97	54158.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116698.38 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	381.83	16.87	2.287	0.30 (0.13)	0.43	196.7	203.00
2	375.17	19.31	2.079	0.30 (0.13)	0.43	213.7	210.00

LONGEST FLOWPATH FROM NODE 210.00 TO NODE 12904.00 = 7986.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18920.70	15.19	2.430	0.30 (0.24)	0.79	3114.9	50400.00
2	19344.07	16.87	2.287	0.30 (0.24)	0.79	3495.7	203.00
3	19929.69	19.31	2.079	0.30 (0.24)	0.79	4036.8	210.00
4	20389.52	21.31	1.952	0.30 (0.24)	0.79	4465.2	50110.00
5	20777.56	22.74	1.878	0.30 (0.24)	0.79	4881.0	50320.00
6	21000.11	23.62	1.833	0.30 (0.24)	0.80	5124.9	50240.00
7	21250.72	24.56	1.784	0.30 (0.24)	0.80	5385.8	50330.00
8	21728.21	26.43	1.699	0.30 (0.24)	0.80	5889.5	420.00
9	21982.89	27.46	1.655	0.30 (0.24)	0.80	6209.2	50280.00
10	22260.63	28.65	1.603	0.30 (0.24)	0.80	6571.6	50300.00
11	22565.07	29.95	1.547	0.30 (0.24)	0.80	6956.1	50220.00
12	22742.39	30.73	1.530	0.30 (0.24)	0.81	7179.6	800.00
13	23404.25	34.16	1.462	0.30 (0.25)	0.83	8471.3	50260.00
14	23960.26	37.03	1.404	0.30 (0.25)	0.84	9527.0	50200.00
15	24483.70	39.69	1.351	0.30 (0.26)	0.86	10505.1	390.00
16	26717.54	56.64	1.110	0.30 (0.27)	0.91	16429.7	40100.00
17	28090.40	64.46	1.043	0.30 (0.28)	0.92	19204.2	11801.00
18	30331.45	75.25	0.982	0.30 (0.28)	0.93	23734.8	11530.00
19	31610.90	83.96	0.933	0.30 (0.28)	0.94	28391.6	11910.00
20	33607.27	93.99	0.884	0.30 (0.29)	0.95	34694.5	11350.00
21	34187.97	98.72	0.867	0.30 (0.29)	0.96	37868.8	11130.00
22	34025.11	104.77	0.845	0.30 (0.29)	0.96	40795.3	12300.00
23	33917.36	108.65	0.831	0.30 (0.29)	0.96	42856.2	11620.00
24	33582.82	113.49	0.813	0.30 (0.29)	0.96	45055.9	12400.00
25	32792.76	122.93	0.783	0.30 (0.29)	0.96	48457.5	12201.00
26	31999.10	130.33	0.767	0.30 (0.29)	0.96	50350.5	12231.00
27	31171.61	137.73	0.751	0.30 (0.29)	0.97	51903.3	10400.00

28	29830.29	147.03	0.731	0.30 (0.29)	0.97	53349.7	12010.00
29	28911.41	152.31	0.720	0.30 (0.29)	0.97	53612.3	10210.00
30	28333.09	156.30	0.711	0.30 (0.29)	0.97	53759.1	12000.00
31	25143.39	182.24	0.658	0.30 (0.29)	0.97	54372.0	10100.00

TOTAL AREA (ACRES) = 54372.0

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 34187.97 Tc (MIN.) = 98.722
EFFECTIVE AREA (ACRES) = 37868.76 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94
TOTAL AREA (ACRES) = 54372.0
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116698.38 FEET.

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 98.72
* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.867
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCSSOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
RESIDENTIAL
".4 DWELLING/ACRE" B 0.10 0.30 0.900 56
NATURAL FAIR COVER
"WOODLAND, GRASS" B 0.20 0.30 1.000 65
NATURAL FAIR COVER
"WOODLAND, GRASS" B 0.80 0.30 1.000 65
COMMERCIAL B 1.20 0.30 0.100 56
COMMERCIAL B 1.50 0.30 0.100 56
NATURAL FAIR COVER
"GRASS" B 3.00 0.30 1.000 69
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.641
SUBAREA AREA (ACRES) = 6.80 SUBAREA RUNOFF (CFS) = 4.13
EFFECTIVE AREA (ACRES) = 37875.56 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA (ACRES) = 54378.8 PEAK FLOW RATE (CFS) = 34187.97
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 98.72
* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.867
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCSSOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"GRASS" B 3.60 0.30 1.000 69
PUBLIC PARK B 15.10 0.30 0.850 56
NATURAL FAIR COVER
"GRASS" B 20.00 0.30 1.000 69
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.941

SUBAREA AREA(ACRES) = 38.70 SUBAREA RUNOFF(CFS) = 20.36
 EFFECTIVE AREA(ACRES) = 37914.26 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
 TOTAL AREA(ACRES) = 54417.5 PEAK FLOW RATE(CFS) = 34187.97
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

=====

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 54417.5 TC(MIN.) = 98.72
 EFFECTIVE AREA(ACRES) = 37914.26 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.957
 PEAK FLOW RATE(CFS) = 34187.97

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18920.70	15.19	2.430	0.30(0.24)	0.79	3160.4	50400.00
2	19344.07	16.87	2.287	0.30(0.24)	0.79	3541.2	203.00
3	19929.69	19.31	2.079	0.30(0.24)	0.79	4082.3	210.00
4	20389.52	21.31	1.952	0.30(0.24)	0.79	4510.7	50110.00
5	20777.56	22.74	1.878	0.30(0.24)	0.80	4926.5	50320.00
6	21000.11	23.62	1.833	0.30(0.24)	0.80	5170.4	50240.00
7	21250.72	24.56	1.784	0.30(0.24)	0.80	5431.3	50330.00
8	21728.21	26.43	1.699	0.30(0.24)	0.80	5935.0	420.00
9	21982.89	27.46	1.655	0.30(0.24)	0.80	6254.7	50280.00
10	22260.63	28.65	1.603	0.30(0.24)	0.80	6617.1	50300.00
11	22565.07	29.95	1.547	0.30(0.24)	0.81	7001.6	50220.00
12	22742.39	30.73	1.530	0.30(0.24)	0.81	7225.1	800.00
13	23404.25	34.16	1.462	0.30(0.25)	0.83	8516.8	50260.00
14	23960.26	37.03	1.404	0.30(0.25)	0.84	9572.5	50200.00
15	24483.70	39.69	1.351	0.30(0.26)	0.86	10550.6	390.00
16	26717.54	56.64	1.110	0.30(0.27)	0.91	16475.2	40100.00
17	28090.40	64.46	1.043	0.30(0.28)	0.92	19249.7	11801.00
18	30331.45	75.25	0.982	0.30(0.28)	0.93	23780.3	11530.00
19	31610.90	83.96	0.933	0.30(0.28)	0.94	28437.1	11910.00
20	33607.27	93.99	0.884	0.30(0.29)	0.95	34740.0	11350.00
21	34187.97	98.72	0.867	0.30(0.29)	0.96	37914.3	11130.00
22	34025.11	104.77	0.845	0.30(0.29)	0.96	40840.8	12300.00
23	33917.36	108.65	0.831	0.30(0.29)	0.96	42901.7	11620.00
24	33582.82	113.49	0.813	0.30(0.29)	0.96	45101.4	12400.00
25	32792.76	122.93	0.783	0.30(0.29)	0.96	48503.0	12201.00
26	31999.10	130.33	0.767	0.30(0.29)	0.96	50396.0	12231.00
27	31171.61	137.73	0.751	0.30(0.29)	0.97	51948.8	10400.00
28	29830.29	147.03	0.731	0.30(0.29)	0.97	53395.2	12010.00
29	28911.41	152.31	0.720	0.30(0.29)	0.97	53657.8	10210.00
30	28333.09	156.30	0.711	0.30(0.29)	0.97	53804.6	12000.00
31	25143.39	182.24	0.658	0.30(0.29)	0.97	54417.5	10100.00

=====

END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 133 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 25-YR EV FEB 2023 ROKAMOTO *

FILE NAME: RU25EV33.DAT
TIME/DATE OF STUDY: 08:20 02/08/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 25.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 4.828
- 2) 10.00; 3.154
- 3) 15.00; 2.415
- 4) 20.00; 2.000
- 5) 25.00; 1.745
- 6) 30.00; 1.533
- 7) 40.00; 1.333
- 8) 50.00; 1.180
- 9) 60.00; 1.055
- 10) 90.00; 0.886
- 11) 120.00; 0.775
- 12) 180.00; 0.646
- 13) 360.00; 0.475
- 14) 1200.00; 0.208

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL
HALF- CROWN TO STREET-CROSSFALL: CURB GUTTER-GEOMETRIES: MANNING
WIDTH CROSSFALL IN- / OUT-/PARK- HEIGHT WIDTH LIP HIKE FACTOR
NO. (FT) (FT) SIDE / SIDE/ WAY (FT) (FT) (FT) (FT) (n)
=== =====

NO.	(FT)	(FT)	SIDE / SIDE/ WAY	(FT)	(FT)	(FT)	(FT)	(n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:

- 1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13112.00 TO NODE 13222.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: S31X25.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2430.28	35.90	0.30 (0.24)	0.81	2511.7	13100.00
2	2369.04	61.85	0.30 (0.24)	0.81	3776.9	13000.00
3	2335.36	64.17	0.30 (0.24)	0.81	3796.8	13010.00
TOTAL AREA (ACRES) =						3796.8

FLOW PROCESS FROM NODE 13221.00 TO NODE 13222.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: S32X25.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1123.08	33.84	0.30 (0.25)	0.83	1121.8	13210.00
2	1123.47	34.10	0.30 (0.25)	0.83	1127.6	13200.00
TOTAL AREA (ACRES) =						1127.6

FLOW PROCESS FROM NODE 13221.00 TO NODE 13222.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1123.08	33.84	0.30 (0.25)	0.83	1121.8	13210.00
2	1123.47	34.10	0.30 (0.25)	0.83	1127.6	13200.00
TOTAL AREA (ACRES) =						1127.6

FLOW PROCESS FROM NODE 13112.00 TO NODE 13222.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

=====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1123.08	33.84	1.456	0.30 (0.25)	0.83	1121.8	13210.00
2	1123.47	34.10	1.451	0.30 (0.25)	0.83	1127.6	13200.00
LONGEST FLOWPATH FROM NODE 13200.00 TO NODE 13222.00 =							16821.05 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2430.28	35.90	1.415	0.30(0.24)	0.81	2511.7	13100.00
2	2369.04	61.85	1.045	0.30(0.24)	0.81	3776.9	13000.00
3	2335.36	64.17	1.032	0.30(0.24)	0.81	3796.8	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13222.00 = 32126.49 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3494.44	33.84	1.456	0.30(0.24)	0.82	3489.4	13210.00
2	3502.81	34.10	1.451	0.30(0.24)	0.82	3513.4	13200.00
3	3520.15	35.90	1.415	0.30(0.24)	0.82	3639.3	13100.00
4	3112.88	61.85	1.045	0.30(0.24)	0.81	4904.5	13000.00
5	3066.96	64.17	1.032	0.30(0.24)	0.81	4924.4	13010.00

TOTAL AREA (ACRES) = 4924.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 3520.15 Tc(MIN.) = 35.896

EFFECTIVE AREA(ACRES) = 3639.28 AREA-AVERAGED Fm(INCH/HR) = 0.24

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82

TOTAL AREA (ACRES) = 4924.4

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13222.00 = 32126.49 FEET.

FLOW PROCESS FROM NODE 13222.00 TO NODE 13222.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

=====

FLOW PROCESS FROM NODE 13222.00 TO NODE 13222.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

=====

FLOW PROCESS FROM NODE 13222.00 TO NODE 13301.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 427.51 DOWNSTREAM(FEET) = 382.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 2533.33 CHANNEL SLOPE = 0.0180

GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 4.63

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.345

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	1.40	0.30	0.100	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	15.60	0.30	1.000	66
RESIDENTIAL					
"3-4 DWELLINGS/ACRE"	B	0.10	0.30	0.600	56
AGRICULTURAL POOR COVER					

"ROW CROPS, CONTOURED"	B	5.30	0.30	1.000	79
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86
COMMERCIAL	B	22.60	0.30	0.100	56

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.521

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3544.32

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.99

AVERAGE FLOW DEPTH(FEET) = 4.63 TRAVEL TIME(MIN.) = 3.52

Tc(MIN.) = 39.42

SUBAREA AREA(ACRES) = 45.20 SUBAREA RUNOFF(CFS) = 48.34

EFFECTIVE AREA(ACRES) = 3684.48 AREA-AVERAGED Fm(INCH/HR) = 0.24

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81

TOTAL AREA(ACRES) = 4969.6 PEAK FLOW RATE(CFS) = 3651.50

GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 4.71

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 4.71 FLOW VELOCITY(FEET/SEC.) = 12.09

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 39.42

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.345

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	1.00	0.30	1.000	79
NATURAL POOR COVER					
"BARREN"	B	0.50	0.30	1.000	86
COMMERCIAL	B	7.40	0.30	0.100	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	4.70	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	2.90	0.30	1.000	65

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.596

SUBAREA AREA(ACRES) = 16.50 SUBAREA RUNOFF(CFS) = 17.31

EFFECTIVE AREA(ACRES) = 3700.98 AREA-AVERAGED Fm(INCH/HR) = 0.24

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81

TOTAL AREA(ACRES) = 4986.1 PEAK FLOW RATE(CFS) = 3668.81

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 39.42

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.345

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					

NATURAL POOR COVER
 "BARREN" B 1.30 0.30 1.000 86
 COMMERCIAL B 0.20 0.30 0.100 56
 AGRICULTURAL POOR COVER
 "ROW CROPS,CONTOURED" B 5.30 0.30 1.000 79
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 0.30 0.30 1.000 65
 NATURAL FAIR COVER
 "CHAPARRAL,BROADLEAF" B 0.20 0.30 1.000 63
 NATURAL FAIR COVER
 "OPEN BRUSH" B 0.60 0.30 1.000 66
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.977
 SUBAREA AREA (ACRES) = 7.90 SUBAREA RUNOFF(CFS) = 7.48
 EFFECTIVE AREA(ACRES) = 3708.88 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81
 TOTAL AREA (ACRES) = 4994.0 PEAK FLOW RATE(CFS) = 3676.29

 FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 39.42
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.345
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	4.30	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.80	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	1.10	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	6.90	0.30	1.000	66
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	7.90	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	1.00	0.30	1.000	65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000					
SUBAREA AREA (ACRES) = 22.00 SUBAREA RUNOFF(CFS) = 20.68					
EFFECTIVE AREA(ACRES) = 3730.88 AREA-AVERAGED Fm(INCH/HR) = 0.24					
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81					
TOTAL AREA (ACRES) = 5016.0 PEAK FLOW RATE(CFS) = 3696.97					

 FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 39.42
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.345
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.50	0.30	1.000	63

"OPEN BRUSH" B 0.40 0.30 1.000 66
 AGRICULTURAL POOR COVER
 "ROW CROPS,CONTOURED" B 14.60 0.30 1.000 79
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 15.00 SUBAREA RUNOFF(CFS) = 14.10
 EFFECTIVE AREA(ACRES) = 3745.88 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81
 TOTAL AREA (ACRES) = 5031.0 PEAK FLOW RATE(CFS) = 3711.07

 FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1<<<<<

 FLOW PROCESS FROM NODE 31100.00 TO NODE 31101.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 317.00
 ELEVATION DATA: UPSTREAM(FEET) = 801.00 DOWNSTREAM(FEET) = 685.00

Tc = K*[LENGTH** 3.00]/(ELEVATION CHANGE)]**0.20
 SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 8.641
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 3.609
 SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER						
"CHAPARRAL,BROADLEAF"	B	0.50	0.30	1.000	63	8.64
NATURAL FAIR COVER						
"OPEN BRUSH"	B	0.30	0.30	1.000	66	8.64
NATURAL FAIR COVER						
"OPEN BRUSH"	B	0.30	0.30	1.000	66	8.64
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30						
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000						
SUBAREA RUNOFF(CFS) = 3.28						
TOTAL AREA (ACRES) = 1.10 PEAK FLOW RATE(CFS) = 3.28						

 FLOW PROCESS FROM NODE 31101.00 TO NODE 31102.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 685.00 DOWNSTREAM(FEET) = 655.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 135.00 CHANNEL SLOPE = 0.2222
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 3.496
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.50	0.30	1.000	63

NATURAL FAIR COVER
 "OPEN BRUSH" B 0.10 0.30 1.000 66
 NATURAL FAIR COVER
 "OPEN BRUSH" B 0.70 0.30 1.000 66
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5.15
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.69
 AVERAGE FLOW DEPTH(FEET) = 0.51 TRAVEL TIME(MIN.) = 0.34
 Tc(MIN.) = 8.98
 SUBAREA AREA(ACRES) = 1.30 SUBAREA RUNOFF(CFS) = 3.74
 EFFECTIVE AREA(ACRES) = 2.40 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 2.4 PEAK FLOW RATE(CFS) = 6.90

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 0.56 FLOW VELOCITY(FEET/SEC.) = 7.29
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31102.00 = 452.00 FEET.

 FLOW PROCESS FROM NODE 31102.00 TO NODE 31103.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 655.00 DOWNSTREAM(FEET) = 630.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 203.00 CHANNEL SLOPE = 0.1232
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 10.00
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 3.353
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.30	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.10	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.90	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 10.07
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.91
 AVERAGE FLOW DEPTH(FEET) = 0.65 TRAVEL TIME(MIN.) = 0.43
 Tc(MIN.) = 9.40
 SUBAREA AREA(ACRES) = 2.30 SUBAREA RUNOFF(CFS) = 6.32
 EFFECTIVE AREA(ACRES) = 4.70 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 4.7 PEAK FLOW RATE(CFS) = 12.92

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 0.71 FLOW VELOCITY(FEET/SEC.) = 8.44
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31103.00 = 655.00 FEET.

 FLOW PROCESS FROM NODE 31103.00 TO NODE 31104.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<
 =====

ELEVATION DATA: UPSTREAM(FEET) = 630.00 DOWNSTREAM(FEET) = 605.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 321.00 CHANNEL SLOPE = 0.0779
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 3.114
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.10	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.50	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 17.47
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.17
 AVERAGE FLOW DEPTH(FEET) = 0.97 TRAVEL TIME(MIN.) = 0.87
 Tc(MIN.) = 10.27
 SUBAREA AREA(ACRES) = 3.60 SUBAREA RUNOFF(CFS) = 9.12
 EFFECTIVE AREA(ACRES) = 8.30 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 8.3 PEAK FLOW RATE(CFS) = 21.02

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 1.04 FLOW VELOCITY(FEET/SEC.) = 6.47
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31104.00 = 976.00 FEET.

 FLOW PROCESS FROM NODE 31104.00 TO NODE 31105.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 605.00 DOWNSTREAM(FEET) = 585.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 288.00 CHANNEL SLOPE = 0.0694
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 3.008
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.70	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.60	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	3.00	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.10	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 28.82
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.73
 AVERAGE FLOW DEPTH(FEET) = 1.19 TRAVEL TIME(MIN.) = 0.71
 Tc(MIN.) = 10.99
 SUBAREA AREA(ACRES) = 6.40 SUBAREA RUNOFF(CFS) = 15.60

EFFECTIVE AREA(ACRES) = 14.70 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 14.7 PEAK FLOW RATE(CFS) = 35.83

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.30 FLOW VELOCITY(FEET/SEC.) = 7.07
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31105.00 = 1264.00 FEET.

FLOW PROCESS FROM NODE 31105.00 TO NODE 31106.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 585.00 DOWNSTREAM(FEET) = 560.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 344.00 CHANNEL SLOPE = 0.0727
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.900

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.60	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	2.80	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.60	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.10	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.60	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	4.10	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 48.47

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.80

AVERAGE FLOW DEPTH(FEET) = 1.44 TRAVEL TIME(MIN.) = 0.73

Tc(MIN.) = 11.72

SUBAREA AREA(ACRES) = 10.80 SUBAREA RUNOFF(CFS) = 25.27

EFFECTIVE AREA(ACRES) = 25.50 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 25.5 PEAK FLOW RATE(CFS) = 59.66

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.56 FLOW VELOCITY(FEET/SEC.) = 8.18
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31106.00 = 1608.00 FEET.

FLOW PROCESS FROM NODE 31106.00 TO NODE 31107.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 560.00 DOWNSTREAM(FEET) = 530.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 619.00 CHANNEL SLOPE = 0.0485
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.695

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.80	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	1.90	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.50	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	8.20	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.70	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 75.95

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.47

AVERAGE FLOW DEPTH(FEET) = 1.84 TRAVEL TIME(MIN.) = 1.38

Tc(MIN.) = 13.10

SUBAREA AREA(ACRES) = 15.10 SUBAREA RUNOFF(CFS) = 32.55

EFFECTIVE AREA(ACRES) = 40.60 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 40.6 PEAK FLOW RATE(CFS) = 87.53

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.94 FLOW VELOCITY(FEET/SEC.) = 7.75
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31107.00 = 2227.00 FEET.

FLOW PROCESS FROM NODE 31107.00 TO NODE 31108.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 530.00 DOWNSTREAM(FEET) = 515.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 377.00 CHANNEL SLOPE = 0.0398

CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.573

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.50	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	6.50	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	1.30	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.10	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	5.50	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	3.40	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 106.25
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.56
AVERAGE FLOW DEPTH(FEET) = 2.16 TRAVEL TIME(MIN.) = 0.83
Tc(MIN.) = 13.93
SUBAREA AREA(ACRES) = 18.30 SUBAREA RUNOFF(CFS) = 37.43
EFFECTIVE AREA(ACRES) = 58.90 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 58.9 PEAK FLOW RATE(CFS) = 120.47

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 2.27 FLOW VELOCITY(FEET/SEC.) = 7.79
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31108.00 = 2604.00 FEET.

FLOW PROCESS FROM NODE 31108.00 TO NODE 31109.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 515.00 DOWNSTREAM(FEET) = 490.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 520.00 CHANNEL SLOPE = 0.0481
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.424

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.70	0.30	1.000	63
NATURAL FAIR COVER					
"GRASS"	B	2.20	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	3.10	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.90	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	7.40	0.30	1.000	63
NATURAL FAIR COVER					
"GRASS"	B	0.30	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 134.43
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.59
AVERAGE FLOW DEPTH(FEET) = 2.28 TRAVEL TIME(MIN.) = 1.01
Tc(MIN.) = 14.94
SUBAREA AREA(ACRES) = 14.60 SUBAREA RUNOFF(CFS) = 27.90
EFFECTIVE AREA(ACRES) = 73.50 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 73.5 PEAK FLOW RATE(CFS) = 140.47

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 2.32 FLOW VELOCITY(FEET/SEC.) = 8.68
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31109.00 = 3124.00 FEET.

FLOW PROCESS FROM NODE 31109.00 TO NODE 31109.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 14.94
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.424

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	11.40	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	8.90	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	1.90	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	9.20	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	1.40	0.30	1.000	65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000					
SUBAREA AREA(ACRES) = 32.80 SUBAREA RUNOFF(CFS) = 62.69					
EFFECTIVE AREA(ACRES) = 106.30 AREA-AVERAGED Fm(INCH/HR) = 0.30					
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00					
TOTAL AREA(ACRES) = 106.3 PEAK FLOW RATE(CFS) = 203.16					

FLOW PROCESS FROM NODE 31109.00 TO NODE 31110.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 490.00 DOWNSTREAM(FEET) = 432.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1420.00 CHANNEL SLOPE = 0.0408
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.203

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	0.80	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.60	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.10	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	1.30	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	4.00	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	1.50	0.30	1.000	63

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 210.26
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.06
AVERAGE FLOW DEPTH(FEET) = 2.78 TRAVEL TIME(MIN.) = 2.61
Tc(MIN.) = 17.56
SUBAREA AREA(ACRES) = 8.30 SUBAREA RUNOFF(CFS) = 14.22
EFFECTIVE AREA(ACRES) = 114.60 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA (ACRES) = 114.6 PEAK FLOW RATE (CFS) = 203.16
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 2.75 FLOW VELOCITY (FEET/SEC.) = 8.96
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31110.00 = 4544.00 FEET.

FLOW PROCESS FROM NODE 31110.00 TO NODE 31110.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 17.56
* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 2.203
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	0.30	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	9.60	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.40	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	6.20	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	3.90	0.30	1.000	65
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	1.40	0.30	1.000	79

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.998
SUBAREA AREA (ACRES) = 21.80 SUBAREA RUNOFF (CFS) = 37.35
EFFECTIVE AREA (ACRES) = 136.40 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 136.4 PEAK FLOW RATE (CFS) = 233.61

FLOW PROCESS FROM NODE 31110.00 TO NODE 13301.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM (FEET) = 432.00 DOWNSTREAM (FEET) = 382.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 1847.00 CHANNEL SLOPE = 0.0271
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 10.00
* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.930
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	4.90	0.30	1.000	86
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	1.50	0.30	1.000	79
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.60	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	2.50	0.30	1.000	79

AGRICULTURAL POOR COVER
"ROW CROPS, CONTOURED" B 5.30 0.30 1.000 79
AGRICULTURAL POOR COVER
"ROW CROPS, CONTOURED" B 3.30 0.30 1.000 79
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.997
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 246.90
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.07
AVERAGE FLOW DEPTH (FEET) = 3.19 TRAVEL TIME (MIN.) = 3.82
Tc (MIN.) = 21.37
SUBAREA AREA (ACRES) = 18.10 SUBAREA RUNOFF (CFS) = 26.57
EFFECTIVE AREA (ACRES) = 154.50 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 154.5 PEAK FLOW RATE (CFS) = 233.61
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 3.13 FLOW VELOCITY (FEET/SEC.) = 7.94
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 13301.00 = 6391.00 FEET.

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	233.61	21.37	1.930	0.30 (0.30)	1.00	154.5	31100.00

LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 13301.00 = 6391.00 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3695.03	37.37	1.386	0.30 (0.24)	0.81	3596.0	13210.00
2	3702.98	37.63	1.380	0.30 (0.24)	0.81	3620.0	13200.00
3	3711.07	39.42	1.345	0.30 (0.24)	0.81	3745.9	13100.00
4	3521.37	65.52	1.024	0.30 (0.24)	0.81	5011.1	13000.00
5	3475.90	67.86	1.011	0.30 (0.24)	0.81	5031.0	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3354.46	21.37	1.930	0.30 (0.25)	0.83	2211.0	31100.00
2	3850.62	37.37	1.386	0.30 (0.25)	0.82	3750.5	13210.00
3	3857.83	37.63	1.380	0.30 (0.25)	0.82	3774.5	13200.00
4	3860.79	39.42	1.345	0.30 (0.25)	0.82	3900.4	13100.00
5	3625.14	65.52	1.024	0.30 (0.24)	0.82	5165.6	13000.00
6	3577.78	67.86	1.011	0.30 (0.24)	0.82	5185.5	13010.00

TOTAL AREA (ACRES) = 5185.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
PEAK FLOW RATE (CFS) = 3860.79 Tc (MIN.) = 39.418
EFFECTIVE AREA (ACRES) = 3900.38 AREA-AVERAGED Fm (INCH/HR) = 0.25
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82
TOTAL AREA (ACRES) = 5185.5

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 13301.00 TO NODE 13302.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 382.00 DOWNSTREAM(FEET) = 375.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 1141.09 CHANNEL SLOPE = 0.0061

GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 6.54

* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.308

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL POOR COVER

"BARREN" B 1.20 0.30 1.000 86

AGRICULTURAL POOR COVER

"ROW CROPS, STRAIGHT ROW" B 0.60 0.30 1.000 81

NATURAL POOR COVER

"BARREN" B 0.90 0.30 1.000 86

NATURAL FAIR COVER

"OPEN BRUSH" B 4.80 0.30 1.000 66

AGRICULTURAL POOR COVER

"ROW CROPS, STRAIGHT ROW" B 1.90 0.30 1.000 81

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 3865.06

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.49

AVERAGE FLOW DEPTH (FEET) = 6.54 TRAVEL TIME (MIN.) = 2.24

Tc (MIN.) = 41.66

SUBAREA AREA (ACRES) = 9.40 SUBAREA RUNOFF (CFS) = 8.52

EFFECTIVE AREA (ACRES) = 3909.78 AREA-AVERAGED Fm (INCH/HR) = 0.25

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82

TOTAL AREA (ACRES) = 5194.9 PEAK FLOW RATE (CFS) = 3860.79

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE (FEET) = 50.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT (FEET) = 6.54

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 6.54 FLOW VELOCITY (FEET/SEC.) = 8.49

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13302.00 = 35800.91 FEET.

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 41.66

* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.308

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL POOR COVER

"BARREN" B 13.80 0.30 1.000 86

NATURAL POOR COVER

"BARREN" B 2.60 0.30 1.000 86

COMMERCIAL

B 1.10 0.30 0.100 56

RESIDENTIAL

".4 DWELLING/ACRE" B 3.50 0.30 0.900 56

AGRICULTURAL POOR COVER

"ROW CROPS, CONTOURED" B 6.90 0.30 1.000 79

NATURAL POOR COVER

"BARREN" B 0.20 0.30 1.000 86

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.952

SUBAREA AREA (ACRES) = 28.10 SUBAREA RUNOFF (CFS) = 25.84

EFFECTIVE AREA (ACRES) = 3937.88 AREA-AVERAGED Fm (INCH/HR) = 0.25

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82

TOTAL AREA (ACRES) = 5223.0 PEAK FLOW RATE (CFS) = 3860.79

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 41.66

* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.308

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

AGRICULTURAL POOR COVER

"ROW CROPS, CONTOURED" B 0.10 0.30 1.000 79

COMMERCIAL B 0.10 0.30 0.100 56

RESIDENTIAL

".4 DWELLING/ACRE" B 2.40 0.30 0.900 56

AGRICULTURAL POOR COVER

"ROW CROPS, CONTOURED" B 0.50 0.30 1.000 79

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.894

SUBAREA AREA (ACRES) = 3.10 SUBAREA RUNOFF (CFS) = 2.90

EFFECTIVE AREA (ACRES) = 3940.98 AREA-AVERAGED Fm (INCH/HR) = 0.25

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82

TOTAL AREA (ACRES) = 5226.1 PEAK FLOW RATE (CFS) = 3860.79

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 41.66

* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.308

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

LAND USE	GROUP	ACRES	(INCH/HR)	(DECIMAL)	CN
NATURAL POOR COVER					
"BARREN"	B	0.10	0.30	1.000	86
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.60	0.30	1.000	66
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	3.10	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.40	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	0.20	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	13.80	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 20.20 SUBAREA RUNOFF (CFS) = 18.32
EFFECTIVE AREA (ACRES) = 3961.18 AREA-AVERAGED Fm (INCH/HR) = 0.25
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82
TOTAL AREA (ACRES) = 5246.3 PEAK FLOW RATE (CFS) = 3860.79
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 41.66
* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.308
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	34.60	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	2.40	0.30	1.000	65
NATURAL FAIR COVER					
"OPEN BRUSH"	B	22.60	0.30	1.000	66
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	11.60	0.30	1.000	79
APARTMENTS	B	0.40	0.30	0.200	56
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	4.80	0.30	1.000	63

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.996
SUBAREA AREA (ACRES) = 76.40 SUBAREA RUNOFF (CFS) = 69.37
EFFECTIVE AREA (ACRES) = 4037.58 AREA-AVERAGED Fm (INCH/HR) = 0.25
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
TOTAL AREA (ACRES) = 5322.7 PEAK FLOW RATE (CFS) = 3860.79
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 41.66
* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.308
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.40	0.30	1.000	65
NATURAL POOR COVER					
"BARREN"	B	0.80	0.30	1.000	86
COMMERCIAL	B	1.40	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	2.60	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.20	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.834
SUBAREA AREA (ACRES) = 7.60 SUBAREA RUNOFF (CFS) = 6.84

LAND USE	GROUP	ACRES	(INCH/HR)	(DECIMAL)	CN
NATURAL FAIR COVER					
"GRASS"	B	1.60	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	46.40	0.30	1.000	66
RESIDENTIAL					
"11+ DWELLINGS/ACRE"	B	0.10	0.30	0.200	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	60.70	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	5.80	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999
SUBAREA AREA (ACRES) = 114.60 SUBAREA RUNOFF (CFS) = 103.95
EFFECTIVE AREA (ACRES) = 4152.18 AREA-AVERAGED Fm (INCH/HR) = 0.25
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
TOTAL AREA (ACRES) = 5437.3 PEAK FLOW RATE (CFS) = 3955.31

FLOW PROCESS FROM NODE 13302.00 TO NODE 13303.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 375.00 DOWNSTREAM (FEET) = 355.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 2193.96 CHANNEL SLOPE = 0.0091
GIVEN CHANNEL BASE (FEET) = 50.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT (FEET) = 5.94
CHANNEL FLOW THRU SUBAREA (CFS) = 3955.31
FLOW VELOCITY (FEET/SEC.) = 9.82 FLOW DEPTH (FEET) = 5.94
TRAVEL TIME (MIN.) = 3.72 Tc (MIN.) = 45.38
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13303.00 = 37994.87 FEET.

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 45.38
* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.251
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.40	0.30	1.000	65
NATURAL POOR COVER					
"BARREN"	B	0.80	0.30	1.000	86
COMMERCIAL	B	1.40	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	2.60	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.20	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.834
SUBAREA AREA (ACRES) = 7.60 SUBAREA RUNOFF (CFS) = 6.84

EFFECTIVE AREA(ACRES) = 4159.78 AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
TOTAL AREA(ACRES) = 5444.9 PEAK FLOW RATE(CFS) = 3955.31
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 45.38					
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.251					
SUBAREA LOSS RATE DATA(AMC II):					
DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	3.10	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	3.40	0.30	1.000	65
NATURAL POOR COVER					
"BARREN"	B	0.50	0.30	1.000	86
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.20	0.30	1.000	63
COMMERCIAL	B	3.60	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	4.00	0.30	1.000	69
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.781					
SUBAREA AREA(ACRES) = 14.80 SUBAREA RUNOFF(CFS) = 13.54					
EFFECTIVE AREA(ACRES) = 4174.58 AREA-AVERAGED Fm(INCH/HR) = 0.25					
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83					
TOTAL AREA(ACRES) = 5459.7 PEAK FLOW RATE(CFS) = 3955.31					
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE					

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 45.38					
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.251					
SUBAREA LOSS RATE DATA(AMC II):					
DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	14.60	0.30	1.000	66
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	6.30	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	3.70	0.30	1.000	65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000					
SUBAREA AREA(ACRES) = 24.60 SUBAREA RUNOFF(CFS) = 21.05					
EFFECTIVE AREA(ACRES) = 4199.18 AREA-AVERAGED Fm(INCH/HR) = 0.25					
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83					
TOTAL AREA(ACRES) = 5484.3 PEAK FLOW RATE(CFS) = 3955.31					
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE					

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 45.38					
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.251					
SUBAREA LOSS RATE DATA(AMC II):					
DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	0.50	0.30	1.000	86
COMMERCIAL	B	0.30	0.30	0.100	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.20	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.80	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	1.60	0.30	1.000	79
NATURAL POOR COVER					
"BARREN"	B	31.90	0.30	1.000	86
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.990					
SUBAREA AREA(ACRES) = 35.30 SUBAREA RUNOFF(CFS) = 30.30					
EFFECTIVE AREA(ACRES) = 4234.48 AREA-AVERAGED Fm(INCH/HR) = 0.25					
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83					
TOTAL AREA(ACRES) = 5519.6 PEAK FLOW RATE(CFS) = 3955.31					
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE					

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 45.38					
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.251					
SUBAREA LOSS RATE DATA(AMC II):					
DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	1.70	0.30	0.100	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.30	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	2.60	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	5.50	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.20	0.30	1.000	65
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.20	0.30	1.000	66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.830					
SUBAREA AREA(ACRES) = 10.50 SUBAREA RUNOFF(CFS) = 9.47					
EFFECTIVE AREA(ACRES) = 4244.98 AREA-AVERAGED Fm(INCH/HR) = 0.25					
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83					
TOTAL AREA(ACRES) = 5530.1 PEAK FLOW RATE(CFS) = 3955.31					
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE					

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 45.38

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.251

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

RESIDENTIAL ".4 DWELLING/ACRE"	B	1.30	0.30	0.900	56
-----------------------------------	---	------	------	-------	----

NATURAL POOR COVER

"BARREN"	B	0.30	0.30	1.000	86
----------	---	------	------	-------	----

COMMERCIAL	B	0.20	0.30	0.100	56
------------	---	------	------	-------	----

NATURAL FAIR COVER "OPEN BRUSH"	B	0.30	0.30	1.000	66
------------------------------------	---	------	------	-------	----

RESIDENTIAL ".4 DWELLING/ACRE"	B	6.50	0.30	0.900	56
-----------------------------------	---	------	------	-------	----

AGRICULTURAL POOR COVER

"ROW CROPS,CONTOURED"	B	3.00	0.30	1.000	79
-----------------------	---	------	------	-------	----

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.917

SUBAREA AREA(ACRES) = 11.60 SUBAREA RUNOFF(CFS) = 10.18

EFFECTIVE AREA(ACRES) = 4256.58 AREA-AVERAGED Fm(INCH/HR) = 0.25

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83

TOTAL AREA(ACRES) = 5541.7 PEAK FLOW RATE(CFS) = 3955.31

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13303.00 TO NODE 13304.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 355.00 DOWNSTREAM(FEET) = 350.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 925.40 CHANNEL SLOPE = 0.0054

GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 6.86

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.222

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL POOR COVER "BARREN"	B	0.20	0.30	1.000	86
--------------------------------	---	------	------	-------	----

AGRICULTURAL POOR COVER "ROW CROPS,STRAIGHT ROW"	B	0.50	0.30	1.000	81
---	---	------	------	-------	----

NATURAL FAIR COVER "WOODLAND,GRASS"	B	1.10	0.30	1.000	65
--	---	------	------	-------	----

NATURAL POOR COVER "BARREN"	B	0.30	0.30	1.000	86
--------------------------------	---	------	------	-------	----

NATURAL FAIR COVER "GRASS"	B	1.10	0.30	1.000	69
-------------------------------	---	------	------	-------	----

NATURAL FAIR COVER "OPEN BRUSH"	B	3.50	0.30	1.000	66
------------------------------------	---	------	------	-------	----

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3958.09

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.18

AVERAGE FLOW DEPTH(FEET) = 6.86 TRAVEL TIME(MIN.) = 1.89

Tc(MIN.) = 47.27

SUBAREA AREA(ACRES) = 6.70 SUBAREA RUNOFF(CFS) = 5.56

EFFECTIVE AREA(ACRES) = 4263.28 AREA-AVERAGED Fm(INCH/HR) = 0.25

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83

TOTAL AREA(ACRES) = 5548.4 PEAK FLOW RATE(CFS) = 3955.31

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 6.85

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 6.85 FLOW VELOCITY(FEET/SEC.) = 8.18

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13304.00 = 38920.27 FEET.

FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 47.27

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.222

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

AGRICULTURAL POOR COVER "ROW CROPS,STRAIGHT ROW"	B	1.40	0.30	1.000	81
---	---	------	------	-------	----

NATURAL FAIR COVER "OPEN BRUSH"	B	4.80	0.30	1.000	66
------------------------------------	---	------	------	-------	----

AGRICULTURAL POOR COVER "ROW CROPS,STRAIGHT ROW"	B	0.90	0.30	1.000	81
---	---	------	------	-------	----

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
--	--	--	--	--	--

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000					
--	--	--	--	--	--

SUBAREA AREA(ACRES) = 7.10 SUBAREA RUNOFF(CFS) = 5.89

EFFECTIVE AREA(ACRES) = 4270.38 AREA-AVERAGED Fm(INCH/HR) = 0.25

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83

TOTAL AREA(ACRES) = 5555.5 PEAK FLOW RATE(CFS) = 3955.31

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 47.27

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.222

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL POOR COVER "BARREN"	B	7.80	0.30	1.000	86
--------------------------------	---	------	------	-------	----

AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	1.70	0.30	1.000	79
--	---	------	------	-------	----

NATURAL POOR COVER "BARREN"	B	9.40	0.30	1.000	86
--------------------------------	---	------	------	-------	----

NATURAL FAIR COVER					
--------------------	--	--	--	--	--

"OPEN BRUSH" B 1.20 0.30 1.000 66
 RESIDENTIAL
 ".4 DWELLING/ACRE" B 0.10 0.30 0.900 56
 AGRICULTURAL POOR COVER
 "ROW CROPS,CONTOURED" B 2.60 0.30 1.000 79
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 22.80 SUBAREA RUNOFF(CFS) = 18.92
 EFFECTIVE AREA(ACRES) = 4293.18 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
 TOTAL AREA(ACRES) = 5578.3 PEAK FLOW RATE(CFS) = 3955.31
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 47.27
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.222
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.20	0.30	1.000	65
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.30	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.20	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	2.70	0.30	1.000	79

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.994
 SUBAREA AREA(ACRES) = 3.40 SUBAREA RUNOFF(CFS) = 2.83
 EFFECTIVE AREA(ACRES) = 4296.58 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
 TOTAL AREA(ACRES) = 5581.7 PEAK FLOW RATE(CFS) = 3955.31
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13304.00 TO NODE 13305.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

 ELEVATION DATA: UPSTREAM(FEET) = 350.00 DOWNSTREAM(FEET) = 315.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2966.27 CHANNEL SLOPE = 0.0118
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 5.54
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.157
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	1.70	0.30	1.000	86
NATURAL FAIR COVER					
"GRASS"	B	0.60	0.30	1.000	69

NATURAL FAIR COVER
 "OPEN BRUSH" B 0.10 0.30 1.000 66
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 0.40 0.30 1.000 65
 NATURAL POOR COVER
 "BARREN" B 2.20 0.30 1.000 86
 NATURAL FAIR COVER
 "GRASS" B 4.20 0.30 1.000 69
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3958.85
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.74
 AVERAGE FLOW DEPTH(FEET) = 5.54 TRAVEL TIME(MIN.) = 4.60
 Tc(MIN.) = 51.87
 SUBAREA AREA(ACRES) = 9.20 SUBAREA RUNOFF(CFS) = 7.09
 EFFECTIVE AREA(ACRES) = 4305.78 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
 TOTAL AREA(ACRES) = 5590.9 PEAK FLOW RATE(CFS) = 3955.31
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 5.53

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 5.53 FLOW VELOCITY(FEET/SEC.) = 10.73
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 51.87
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.157
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	8.10	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	2.30	0.30	1.000	65
NATURAL FAIR COVER					
"GRASS"	B	0.20	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	6.90	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.70	0.30	1.000	65

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 18.20 SUBAREA RUNOFF(CFS) = 14.03
 EFFECTIVE AREA(ACRES) = 4323.98 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
 TOTAL AREA(ACRES) = 5609.1 PEAK FLOW RATE(CFS) = 3955.31
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 51.87
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.157
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	18.40	0.30	1.000	86
NATURAL FAIR COVER					
"MEADOWS"	B	1.20	0.30	1.000	70
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.10	0.30	1.000	65
NATURAL POOR COVER					
"BARREN"	B	26.60	0.30	1.000	86
COMMERCIAL	B	3.90	0.30	0.100	56
AGRICULTURAL POOR COVER					
"FALLOW"	B	3.00	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.934
 SUBAREA AREA(ACRES) = 53.20 SUBAREA RUNOFF(CFS) = 41.96
 EFFECTIVE AREA(ACRES) = 4377.18 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
 TOTAL AREA(ACRES) = 5662.3 PEAK FLOW RATE(CFS) = 3955.31
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 51.87
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.157
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	1.10	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.20	0.30	1.000	65
NATURAL POOR COVER					
"BARREN"	B	14.00	0.30	1.000	86
COMMERCIAL	B	4.30	0.30	0.100	56
AGRICULTURAL POOR COVER					
"FALLOW"	B	5.30	0.30	1.000	86
NATURAL FAIR COVER					
"GRASS"	B	2.70	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.860
 SUBAREA AREA(ACRES) = 27.60 SUBAREA RUNOFF(CFS) = 22.32
 EFFECTIVE AREA(ACRES) = 4404.78 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
 TOTAL AREA(ACRES) = 5689.9 PEAK FLOW RATE(CFS) = 3955.31
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 51.87
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.157
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"MEADOWS"	B	3.20	0.30	1.000	70
NATURAL FAIR COVER					
"OPEN BRUSH"	B	6.10	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	7.50	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	5.40	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	1.60	0.30	1.000	65
NATURAL POOR COVER					
"BARREN"	B	1.90	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.971
 SUBAREA AREA(ACRES) = 25.70 SUBAREA RUNOFF(CFS) = 20.02
 EFFECTIVE AREA(ACRES) = 4430.48 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
 TOTAL AREA(ACRES) = 5715.6 PEAK FLOW RATE(CFS) = 3955.31
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 51.87
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.157
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	2.00	0.30	0.100	56
AGRICULTURAL POOR COVER					
"FALLOW"	B	3.70	0.30	1.000	86
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.10	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	2.60	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	0.20	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.10	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.807
 SUBAREA AREA(ACRES) = 10.70 SUBAREA RUNOFF(CFS) = 8.81
 EFFECTIVE AREA(ACRES) = 4441.18 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
 TOTAL AREA(ACRES) = 5726.3 PEAK FLOW RATE(CFS) = 3955.31
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

=====
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====

MAINLINE Tc(MIN.) = 51.87

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.157

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL FAIR COVER

"OPEN BRUSH"	B	0.50	0.30	1.000	66
--------------	---	------	------	-------	----

RESIDENTIAL

".4 DWELLING/ACRE"	B	8.20	0.30	0.900	56
--------------------	---	------	------	-------	----

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.906

SUBAREA AREA(ACRES) = 8.70 SUBAREA RUNOFF(CFS) = 6.93

EFFECTIVE AREA(ACRES) = 4449.88 AREA-AVERAGED Fm(INCH/HR) = 0.25

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84

TOTAL AREA(ACRES) = 5735.0 PEAK FLOW RATE(CFS) = 3955.31

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 15.1

=====
>>>>DEFINE MEMORY BANK # 1 <<<<
=====

PEAK FLOWRATE TABLE FILE NAME: 3A25EVRL.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	985.44	13.67	0.30(0.13)	0.43	435.7	120.00
2	984.77	13.72	0.30(0.13)	0.43	436.5	110.00
3	831.39	20.84	0.30(0.13)	0.43	504.3	100.00
4	778.32	23.57	0.30(0.13)	0.43	510.2	150.00
TOTAL AREA(ACRES) =						510.2

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 11

=====
>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<
=====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	3453.18	34.36	1.446	0.30(0.26)	0.85	2760.5	31100.00
2	3931.16	49.85	1.182	0.30(0.25)	0.84	4300.0	13210.00
3	3936.31	50.10	1.179	0.30(0.25)	0.84	4324.0	13200.00
4	3955.31	51.87	1.157	0.30(0.25)	0.84	4449.9	13100.00
5	3723.93	78.21	0.952	0.30(0.25)	0.83	5715.1	13000.00
6	3673.16	80.60	0.939	0.30(0.25)	0.83	5735.0	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	985.44	13.67	2.612	0.30(0.13)	0.43	435.7	120.00
2	984.77	13.72	2.604	0.30(0.13)	0.43	436.5	110.00
3	831.39	20.84	1.957	0.30(0.13)	0.43	504.3	100.00

4 778.32 23.57 1.818 0.30(0.13) 0.43 510.2 150.00
LONGEST FLOWPATH FROM NODE 150.00 TO NODE 13305.00 = 9867.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	3705.24	13.67	2.612	0.30(0.22)	0.73	1533.9	120.00
2	3705.97	13.72	2.604	0.30(0.22)	0.73	1538.8	110.00
3	3825.86	20.84	1.957	0.30(0.23)	0.75	2178.5	100.00
4	3887.78	23.57	1.818	0.30(0.23)	0.76	2403.5	150.00
5	4059.82	34.36	1.446	0.30(0.24)	0.79	3270.7	31100.00
6	4416.33	49.85	1.182	0.30(0.24)	0.80	4810.2	13210.00
7	4419.86	50.10	1.179	0.30(0.24)	0.80	4834.2	13200.00
8	4428.61	51.87	1.157	0.30(0.24)	0.80	4960.1	13100.00
9	4103.11	78.21	0.952	0.30(0.24)	0.80	6225.3	13000.00
10	4046.12	80.60	0.939	0.30(0.24)	0.80	6245.2	13010.00
TOTAL AREA(ACRES) =						6245.2	

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 4428.61 Tc(MIN.) = 51.874

EFFECTIVE AREA(ACRES) = 4960.08 AREA-AVERAGED Fm(INCH/HR) = 0.24

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.76

TOTAL AREA(ACRES) = 6245.2

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 12

=====
>>>>CLEAR MEMORY BANK # 1 <<<<
=====

FLOW PROCESS FROM NODE 13305.00 TO NODE 13306.00 IS CODE = 56

=====
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<
=====

ELEVATION DATA: UPSTREAM(FEET) = 315.00 DOWNSTREAM(FEET) = 245.50

CHANNEL LENGTH THRU SUBAREA(FEET) = 4408.41 CHANNEL SLOPE = 0.0158

GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 5.44

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.082

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL POOR COVER

"BARREN"	B	0.40	0.30	1.000	86
----------	---	------	------	-------	----

NATURAL FAIR COVER

"GRASS"	B	9.20	0.30	1.000	69
---------	---	------	------	-------	----

NATURAL FAIR COVER

"OPEN BRUSH"	B	1.00	0.30	1.000	66
--------------	---	------	------	-------	----

NATURAL FAIR COVER

"WOODLAND,GRASS"	B	1.30	0.30	1.000	65
------------------	---	------	------	-------	----

NATURAL POOR COVER

"BARREN"	B	2.40	0.30	1.000	86
----------	---	------	------	-------	----

NATURAL FAIR COVER

"CHAPARRAL,BROADLEAF"	B	4.10	0.30	1.000	63
-----------------------	---	------	------	-------	----

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 4435.08
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.29
 AVERAGE FLOW DEPTH(FEET) = 5.44 TRAVEL TIME(MIN.) = 5.98
 Tc(MIN.) = 57.85
 SUBAREA AREA(ACRES) = 18.40 SUBAREA RUNOFF(CFS) = 12.95
 EFFECTIVE AREA(ACRES) = 4978.48 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6263.6 PEAK FLOW RATE(CFS) = 4428.61
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 5.44

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 5.44 FLOW VELOCITY(FEET/SEC.) = 12.28
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13306.00 = 46294.95 FEET.

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 57.85

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.082

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	19.20	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	20.90	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	4.10	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	0.50	0.30	1.000	63
NATURAL FAIR COVER					
"GRASS"	B	4.30	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.60	0.30	1.000	66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000					
SUBAREA AREA(ACRES) = 49.60 SUBAREA RUNOFF(CFS) = 34.90					
EFFECTIVE AREA(ACRES) = 5028.08 AREA-AVERAGED Fm(INCH/HR) = 0.24					
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80					
TOTAL AREA(ACRES) = 6313.2 PEAK FLOW RATE(CFS) = 4428.61					
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE					

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 57.85

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.082

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 NATURAL FAIR COVER
 "WOODLAND, GRASS" B 0.80 0.30 1.000 65
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 0.80 SUBAREA RUNOFF(CFS) = 0.56
 EFFECTIVE AREA(ACRES) = 5028.88 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6314.0 PEAK FLOW RATE(CFS) = 4428.61
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 57.85

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.082

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.10	0.30	0.850	56
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.10	0.30	1.000	65
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86
PUBLIC PARK	B	0.40	0.30	0.850	56
NATURAL FAIR COVER					
"GRASS"	B	0.40	0.30	1.000	69
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.942					
SUBAREA AREA(ACRES) = 1.30 SUBAREA RUNOFF(CFS) = 0.93					
EFFECTIVE AREA(ACRES) = 5030.18 AREA-AVERAGED Fm(INCH/HR) = 0.24					
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80					
TOTAL AREA(ACRES) = 6315.3 PEAK FLOW RATE(CFS) = 4428.61					
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE					

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 57.85

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.082

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.80	0.30	0.900	56
NATURAL FAIR COVER					
"GRASS"	B	0.80	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.00	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	1.10	0.30	1.000	65
COMMERCIAL	B	1.10	0.30	0.100	56

RESIDENTIAL
 ".4 DWELLING/ACRE" B 2.80 0.30 0.900 56
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.822
 SUBAREA AREA(ACRES) = 7.60 SUBAREA RUNOFF(CFS) = 5.71
 EFFECTIVE AREA(ACRES) = 5037.78 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6322.9 PEAK FLOW RATE(CFS) = 4428.61
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 57.85
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.082
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 COMMERCIAL B 3.50 0.30 0.100 56
 NATURAL FAIR COVER
 "GRASS" B 5.00 0.30 1.000 69
 RESIDENTIAL
 ".4 DWELLING/ACRE" B 6.70 0.30 0.900 56
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 7.80 0.30 1.000 65
 NATURAL FAIR COVER
 "OPEN BRUSH" B 10.80 0.30 1.000 66
 COMMERCIAL B 13.80 0.30 0.100 56
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.659
 SUBAREA AREA(ACRES) = 47.60 SUBAREA RUNOFF(CFS) = 37.88
 EFFECTIVE AREA(ACRES) = 5085.38 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6370.5 PEAK FLOW RATE(CFS) = 4428.61
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 57.85
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.082
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 NATURAL POOR COVER
 "BARREN" B 21.54 0.30 1.000 86
 NATURAL POOR COVER
 "BARREN" B 36.64 0.30 1.000 86
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 58.18 SUBAREA RUNOFF(CFS) = 40.94
 EFFECTIVE AREA(ACRES) = 5143.56 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6428.7 PEAK FLOW RATE(CFS) = 4428.61

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13307.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 245.50 DOWNSTREAM(FEET) = 220.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1543.21 CHANNEL SLOPE = 0.0165
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 5.37
 CHANNEL FLOW THRU SUBAREA(CFS) = 4428.61
 FLOW VELOCITY(FEET/SEC.) = 12.49 FLOW DEPTH(FEET) = 5.37
 TRAVEL TIME(MIN.) = 2.06 Tc(MIN.) = 59.91
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13307.00 = 47838.16 FEET.

 FLOW PROCESS FROM NODE 13307.00 TO NODE 13307.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 59.91
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.056
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 COMMERCIAL B 0.20 0.30 0.100 56
 NATURAL FAIR COVER
 "GRASS" B 0.10 0.30 1.000 69
 AGRICULTURAL FAIR COVER
 "ORCHARDS" B 0.20 0.30 1.000 65
 NATURAL POOR COVER
 "BARREN" B 3.70 0.30 1.000 86
 COMMERCIAL B 0.30 0.30 0.100 56
 NATURAL FAIR COVER
 "GRASS" B 3.20 0.30 1.000 69
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.942
 SUBAREA AREA(ACRES) = 7.70 SUBAREA RUNOFF(CFS) = 5.36
 EFFECTIVE AREA(ACRES) = 5151.26 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6436.4 PEAK FLOW RATE(CFS) = 4428.61
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13307.00 TO NODE 13307.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 59.91
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.056
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 3.60 0.30 1.000 65

NATURAL FAIR COVER
 "GRASS" B 1.90 0.30 1.000 69
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 0.60 0.30 1.000 65
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 6.10 SUBAREA RUNOFF(CFS) = 4.15
 EFFECTIVE AREA(ACRES) = 5157.36 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6442.5 PEAK FLOW RATE(CFS) = 4428.61
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13307.00 TO NODE 13308.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 220.00 DOWNSTREAM(FEET) = 212.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 925.62 CHANNEL SLOPE = 0.0086
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 6.41
 CHANNEL FLOW THRU SUBAREA(CFS) = 4428.61
 FLOW VELOCITY(FEET/SEC.) = 9.97 FLOW DEPTH(FEET) = 6.41
 TRAVEL TIME(MIN.) = 1.55 Tc(MIN.) = 61.46
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13308.00 = 48763.78 FEET.

 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 61.46
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.047
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	0.10	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.20	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	5.00	0.30	1.000	65
COMMERCIAL	B	3.20	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	0.10	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.90	0.30	1.000	66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.697					
SUBAREA AREA(ACRES) = 9.50 SUBAREA RUNOFF(CFS) = 7.16					
EFFECTIVE AREA(ACRES) = 5166.86 AREA-AVERAGED Fm(INCH/HR) = 0.24					
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80					
TOTAL AREA(ACRES) = 6452.0 PEAK FLOW RATE(CFS) = 4428.61					
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE					

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 61.46
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.047
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
APARTMENTS	B	0.30	0.30	0.200	56
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	1.00	0.30	1.000	63
COMMERCIAL	B	41.90	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	7.20	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	25.00	0.30	1.000	66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.498					
SUBAREA AREA(ACRES) = 75.60 SUBAREA RUNOFF(CFS) = 61.06					
EFFECTIVE AREA(ACRES) = 5242.46 AREA-AVERAGED Fm(INCH/HR) = 0.24					
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80					
TOTAL AREA(ACRES) = 6527.6 PEAK FLOW RATE(CFS) = 4428.61					
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE					

 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 61.46
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.047
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	0.10	0.30	0.850	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	0.90	0.30	1.000	79
SCHOOL	B	0.30	0.30	0.600	56
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	13.20	0.30	1.000	65
APARTMENTS	B	0.50	0.30	0.200	56
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.60	0.30	1.000	63
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.966					
SUBAREA AREA(ACRES) = 15.60 SUBAREA RUNOFF(CFS) = 10.63					
EFFECTIVE AREA(ACRES) = 5258.06 AREA-AVERAGED Fm(INCH/HR) = 0.24					
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80					
TOTAL AREA(ACRES) = 6543.2 PEAK FLOW RATE(CFS) = 4428.61					
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE					

 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<


```

=====
MAINLINE Tc(MIN.) = 61.46
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.047
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp        Ap      SCS
LAND USE                GROUP  (ACRES)  (INCH/HR)  (DECIMAL)  CN
COMMERCIAL              B      33.90    0.30      0.100     56
NATURAL FAIR COVER
"GRASS"                 B      17.60    0.30      1.000     69
NATURAL FAIR COVER
"OPEN BRUSH"           B      16.80    0.30      1.000     66
RESIDENTIAL
"11+ DWELLINGS/ACRE"  B      0.60     0.30      0.200     56
RESIDENTIAL
"8-10 DWELLINGS/ACRE" B      1.50     0.30      0.400     56
AGRICULTURAL POOR COVER
"ROW CROPS,CONTOURED" B      10.00    0.30      1.000     79
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.603
SUBAREA AREA(ACRES) = 80.40      SUBAREA RUNOFF(CFS) = 62.65
EFFECTIVE AREA(ACRES) = 5338.46  AREA-AVERAGED Fm(INCH/HR) = 0.24
AREA-AVERAGED Fp(INCH/HR) = 0.30  AREA-AVERAGED Ap = 0.79
TOTAL AREA(ACRES) = 6623.6      PEAK FLOW RATE(CFS) = 4428.61
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====

```

```

MAINLINE Tc(MIN.) = 61.46
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.047
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp        Ap      SCS
LAND USE                GROUP  (ACRES)  (INCH/HR)  (DECIMAL)  CN
SCHOOL                  B      0.30     0.30      0.600     56
NATURAL FAIR COVER
"WOODLAND,GRASS"       B      0.70     0.30      1.000     65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.880
SUBAREA AREA(ACRES) = 1.00      SUBAREA RUNOFF(CFS) = 0.70
EFFECTIVE AREA(ACRES) = 5339.46  AREA-AVERAGED Fm(INCH/HR) = 0.24
AREA-AVERAGED Fp(INCH/HR) = 0.30  AREA-AVERAGED Ap = 0.79
TOTAL AREA(ACRES) = 6624.6      PEAK FLOW RATE(CFS) = 4428.61
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====

```

```

MAINLINE Tc(MIN.) = 61.46
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.047
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp        Ap      SCS
LAND USE                GROUP  (ACRES)  (INCH/HR)  (DECIMAL)  CN
NATURAL FAIR COVER
"GRASS"                 B      0.30     0.30      1.000     69

```

```

NATURAL FAIR COVER
"WOODLAND,GRASS"       B      0.80     0.30      1.000     65
NATURAL FAIR COVER
"GRASS"                 B      0.50     0.30      1.000     69
NATURAL FAIR COVER
"WOODLAND,GRASS"       B      0.20     0.30      1.000     65
NATURAL FAIR COVER
"GRASS"                 B      0.30     0.30      1.000     69
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 2.10      SUBAREA RUNOFF(CFS) = 1.41
EFFECTIVE AREA(ACRES) = 5341.56  AREA-AVERAGED Fm(INCH/HR) = 0.24
AREA-AVERAGED Fp(INCH/HR) = 0.30  AREA-AVERAGED Ap = 0.79
TOTAL AREA(ACRES) = 6626.7      PEAK FLOW RATE(CFS) = 4428.61
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====

```

```

MAINLINE Tc(MIN.) = 61.46
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.047
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp        Ap      SCS
LAND USE                GROUP  (ACRES)  (INCH/HR)  (DECIMAL)  CN
NATURAL FAIR COVER
"GRASS"                 B      1.20     0.30      1.000     69
NATURAL FAIR COVER
"OPEN BRUSH"           B      0.50     0.30      1.000     66
PUBLIC PARK             B      1.70     0.30      0.850     56
NATURAL FAIR COVER
"WOODLAND,GRASS"       B      7.20     0.30      1.000     65
NATURAL FAIR COVER
"GRASS"                 B      1.00     0.30      1.000     69
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.978
SUBAREA AREA(ACRES) = 11.60     SUBAREA RUNOFF(CFS) = 7.87
EFFECTIVE AREA(ACRES) = 5353.17  AREA-AVERAGED Fm(INCH/HR) = 0.24
AREA-AVERAGED Fp(INCH/HR) = 0.30  AREA-AVERAGED Ap = 0.79
TOTAL AREA(ACRES) = 6638.3      PEAK FLOW RATE(CFS) = 4428.61
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 10
-----
>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<
=====

```

```

*****
FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 15.1
-----
>>>>DEFINE MEMORY BANK # 2 <<<<
=====

```

```

PEAK FLOWRATE TABLE FILE NAME: RU25EV29.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:
STREAM      Q      Tc      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)  (MIN.)  (INCH/HR)   (ACRES)  NODE

```

1	19344.07	16.87	0.30	(0.24)	0.79	3541.2	203.00
2	21250.72	24.56	0.30	(0.24)	0.80	5431.3	50330.00
3	22742.39	30.73	0.30	(0.24)	0.81	7225.1	800.00
4	24483.70	39.69	0.30	(0.26)	0.86	10550.6	390.00
5	26717.54	56.64	0.30	(0.27)	0.91	16475.2	40100.00
6	28090.40	64.46	0.30	(0.28)	0.92	19249.7	11801.00
7	30331.45	75.25	0.30	(0.28)	0.93	23780.3	11530.00
8	31610.90	83.96	0.30	(0.28)	0.94	28437.1	11910.00
9	33607.27	93.99	0.30	(0.29)	0.95	34740.0	11350.00
10	34187.97	98.72	0.30	(0.29)	0.96	37914.3	11130.00
11	34025.11	104.77	0.30	(0.29)	0.96	40840.8	12300.00
12	33917.36	108.65	0.30	(0.29)	0.96	42901.7	11620.00
13	33582.82	113.49	0.30	(0.29)	0.96	45101.4	12400.00
14	32792.76	122.93	0.30	(0.29)	0.96	48503.0	12201.00
15	31999.10	130.33	0.30	(0.29)	0.96	50396.0	12231.00
16	31171.61	137.73	0.30	(0.29)	0.97	51948.8	10400.00
17	29830.29	147.03	0.30	(0.29)	0.97	53395.2	12010.00
18	28911.41	152.31	0.30	(0.29)	0.97	53657.8	10210.00
19	28333.09	156.30	0.30	(0.29)	0.97	53804.6	12000.00
20	25143.39	182.24	0.30	(0.29)	0.97	54417.5	10100.00

TOTAL AREA (ACRES) = 54417.5

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19344.07	16.87	0.30 (0.24)	0.79	3541.2	203.00
2	21250.72	24.56	0.30 (0.24)	0.80	5431.3	50330.00
3	22742.39	30.73	0.30 (0.24)	0.81	7225.1	800.00
4	24483.70	39.69	0.30 (0.26)	0.86	10550.6	390.00
5	26717.54	56.64	0.30 (0.27)	0.91	16475.2	40100.00
6	28090.40	64.46	0.30 (0.28)	0.92	19249.7	11801.00
7	30331.45	75.25	0.30 (0.28)	0.93	23780.3	11530.00
8	31610.90	83.96	0.30 (0.28)	0.94	28437.1	11910.00
9	33607.27	93.99	0.30 (0.29)	0.95	34740.0	11350.00
10	34187.97	98.72	0.30 (0.29)	0.96	37914.3	11130.00
11	34025.11	104.77	0.30 (0.29)	0.96	40840.8	12300.00
12	33917.36	108.65	0.30 (0.29)	0.96	42901.7	11620.00
13	33582.82	113.49	0.30 (0.29)	0.96	45101.4	12400.00
14	32792.76	122.93	0.30 (0.29)	0.96	48503.0	12201.00
15	31999.10	130.33	0.30 (0.29)	0.96	50396.0	12231.00
16	31171.61	137.73	0.30 (0.29)	0.97	51948.8	10400.00
17	29830.29	147.03	0.30 (0.29)	0.97	53395.2	12010.00
18	28911.41	152.31	0.30 (0.29)	0.97	53657.8	10210.00
19	28333.09	156.30	0.30 (0.29)	0.97	53804.6	12000.00
20	25143.39	182.24	0.30 (0.29)	0.97	54417.5	10100.00

TOTAL AREA (ACRES) = 54417.5

FLOW PROCESS FROM NODE 12904.00 TO NODE 13308.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 213.00 DOWNSTREAM(FEET) = 212.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1389.52 CHANNEL SLOPE = 0.0007
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 16.64
CHANNEL FLOW THRU SUBAREA(CFS) = 34187.97
FLOW VELOCITY(FEET/SEC.) = 7.25 FLOW DEPTH(FEET) = 16.64
TRAVEL TIME(MIN.) = 3.19 Tc(MIN.) = 101.91
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118087.91 FEET.

FLOW PROCESS FROM NODE 13307.00 TO NODE 13308.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19344.07	20.68	1.966	0.30 (0.24)	0.79	3541.2	203.00
2	21250.72	28.26	1.607	0.30 (0.24)	0.80	5431.3	50330.00
3	22742.39	34.34	1.446	0.30 (0.24)	0.81	7225.1	800.00
4	24483.70	43.23	1.284	0.30 (0.26)	0.86	10550.6	390.00
5	26717.54	60.08	1.055	0.30 (0.27)	0.91	16475.2	40100.00
6	28090.40	67.85	1.011	0.30 (0.28)	0.92	19249.7	11801.00
7	30331.45	78.56	0.950	0.30 (0.28)	0.93	23780.3	11530.00
8	31610.90	87.22	0.902	0.30 (0.28)	0.94	28437.1	11910.00
9	33607.27	97.20	0.859	0.30 (0.29)	0.95	34740.0	11350.00
10	34187.97	101.91	0.842	0.30 (0.29)	0.96	37914.3	11130.00
11	34025.11	107.97	0.820	0.30 (0.29)	0.96	40840.8	12300.00
12	33917.36	111.85	0.805	0.30 (0.29)	0.96	42901.7	11620.00
13	33582.82	116.70	0.787	0.30 (0.29)	0.96	45101.4	12400.00
14	32792.76	126.16	0.762	0.30 (0.29)	0.96	48503.0	12201.00
15	31999.10	133.59	0.746	0.30 (0.29)	0.96	50396.0	12231.00
16	31171.61	141.01	0.730	0.30 (0.29)	0.97	51948.8	10400.00
17	29830.29	150.36	0.710	0.30 (0.29)	0.97	53395.2	12010.00
18	28911.41	155.67	0.698	0.30 (0.29)	0.97	53657.8	10210.00
19	28333.09	159.68	0.690	0.30 (0.29)	0.97	53804.6	12000.00
20	25143.39	185.74	0.641	0.30 (0.29)	0.97	54417.5	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118087.91 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3705.24	23.80	1.806	0.30 (0.22)	0.74	1926.9	120.00
2	3705.97	23.85	1.804	0.30 (0.22)	0.74	1931.9	110.00
3	3825.86	30.87	1.516	0.30 (0.23)	0.76	2571.6	100.00
4	3887.78	33.54	1.462	0.30 (0.23)	0.76	2796.5	150.00
5	4059.82	44.21	1.269	0.30 (0.24)	0.79	3663.8	31100.00
6	4416.33	59.45	1.062	0.30 (0.24)	0.79	5203.3	13210.00
7	4419.86	59.69	1.059	0.30 (0.24)	0.79	5227.3	13200.00
8	4428.61	61.46	1.047	0.30 (0.24)	0.79	5353.2	13100.00
9	4103.11	88.02	0.897	0.30 (0.24)	0.80	6618.4	13000.00
10	4046.12	90.46	0.884	0.30 (0.24)	0.80	6638.3	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13308.00 = 48763.78 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22886.85	20.68	1.966	0.30 (0.23)	0.78	5215.6	203.00
2	23833.76	23.80	1.806	0.30 (0.23)	0.78	6245.8	120.00
3	23847.63	23.85	1.804	0.30 (0.23)	0.78	6263.7	110.00
4	25031.95	28.26	1.607	0.30 (0.23)	0.78	7764.7	50330.00
5	25717.51	30.87	1.516	0.30 (0.24)	0.79	8773.6	100.00
6	26433.65	33.54	1.462	0.30 (0.24)	0.79	9785.3	150.00
7	26643.11	34.34	1.446	0.30 (0.24)	0.80	10086.9	800.00
8	28527.76	43.23	1.284	0.30 (0.25)	0.84	14134.9	390.00
9	28673.10	44.21	1.269	0.30 (0.25)	0.84	14558.0	31100.00
10	31050.10	59.45	1.062	0.30 (0.26)	0.88	21456.2	13210.00
11	31085.70	59.69	1.059	0.30 (0.26)	0.88	21565.3	13200.00
12	31139.32	60.08	1.055	0.30 (0.26)	0.88	21730.1	40100.00
13	31390.73	61.46	1.047	0.30 (0.26)	0.88	22322.6	13100.00
14	32440.76	67.85	1.011	0.30 (0.27)	0.89	24907.0	11801.00
15	34550.53	78.56	0.950	0.30 (0.27)	0.91	29947.9	11530.00
16	35723.81	87.22	0.902	0.30 (0.27)	0.92	35017.4	11910.00
17	35874.07	88.02	0.897	0.30 (0.28)	0.92	35560.8	13000.00
18	36305.36	90.46	0.884	0.30 (0.28)	0.92	37122.3	13010.00
19	37497.25	97.20	0.859	0.30 (0.28)	0.93	41378.4	11350.00
20	37968.52	101.91	0.842	0.30 (0.28)	0.93	44552.6	11130.00
21	37665.26	107.97	0.820	0.30 (0.28)	0.94	47479.2	12300.00
22	37467.43	111.85	0.805	0.30 (0.28)	0.94	49540.0	11620.00
23	37020.54	116.70	0.787	0.30 (0.28)	0.94	51739.8	12400.00
24	36070.92	126.16	0.762	0.30 (0.28)	0.94	55141.3	12201.00
25	35177.15	133.59	0.746	0.30 (0.28)	0.94	57034.4	12231.00
26	34249.66	141.01	0.730	0.30 (0.28)	0.95	58587.1	10400.00
27	32782.40	150.36	0.710	0.30 (0.28)	0.95	60033.5	12010.00
28	31791.88	155.67	0.698	0.30 (0.28)	0.95	60296.1	10210.00
29	31159.54	159.68	0.690	0.30 (0.28)	0.95	60442.9	12000.00
30	27661.84	185.74	0.641	0.30 (0.28)	0.95	61055.8	10100.00

TOTAL AREA (ACRES) = 61055.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 37968.52 Tc (MIN.) = 101.915
EFFECTIVE AREA (ACRES) = 44552.57 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.88
TOTAL AREA (ACRES) = 61055.8
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118087.91 FEET.

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 61055.8 TC (MIN.) = 101.91
EFFECTIVE AREA (ACRES) = 44552.57 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.933
PEAK FLOW RATE (CFS) = 37968.52

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22886.85	20.68	1.966	0.30 (0.23)	0.78	5215.6	203.00
2	23833.76	23.80	1.806	0.30 (0.23)	0.78	6245.8	120.00
3	23847.63	23.85	1.804	0.30 (0.23)	0.78	6263.7	110.00
4	25031.95	28.26	1.607	0.30 (0.23)	0.78	7764.7	50330.00
5	25717.51	30.87	1.516	0.30 (0.24)	0.79	8773.6	100.00
6	26433.65	33.54	1.462	0.30 (0.24)	0.79	9785.3	150.00
7	26643.11	34.34	1.446	0.30 (0.24)	0.80	10086.9	800.00
8	28527.76	43.23	1.284	0.30 (0.25)	0.84	14134.9	390.00

9	28673.10	44.21	1.269	0.30 (0.25)	0.84	14558.0	31100.00
10	31050.10	59.45	1.062	0.30 (0.26)	0.88	21456.2	13210.00
11	31085.70	59.69	1.059	0.30 (0.26)	0.88	21565.3	13200.00
12	31139.32	60.08	1.055	0.30 (0.26)	0.88	21730.1	40100.00
13	31390.73	61.46	1.047	0.30 (0.26)	0.88	22322.6	13100.00
14	32440.76	67.85	1.011	0.30 (0.27)	0.89	24907.0	11801.00
15	34550.53	78.56	0.950	0.30 (0.27)	0.91	29947.9	11530.00
16	35723.81	87.22	0.902	0.30 (0.27)	0.92	35017.4	11910.00
17	35874.07	88.02	0.897	0.30 (0.28)	0.92	35560.8	13000.00
18	36305.36	90.46	0.884	0.30 (0.28)	0.92	37122.3	13010.00
19	37497.25	97.20	0.859	0.30 (0.28)	0.93	41378.4	11350.00
20	37968.52	101.91	0.842	0.30 (0.28)	0.93	44552.6	11130.00
21	37665.26	107.97	0.820	0.30 (0.28)	0.94	47479.2	12300.00
22	37467.43	111.85	0.805	0.30 (0.28)	0.94	49540.0	11620.00
23	37020.54	116.70	0.787	0.30 (0.28)	0.94	51739.8	12400.00
24	36070.92	126.16	0.762	0.30 (0.28)	0.94	55141.3	12201.00
25	35177.15	133.59	0.746	0.30 (0.28)	0.94	57034.4	12231.00
26	34249.66	141.01	0.730	0.30 (0.28)	0.95	58587.1	10400.00
27	32782.40	150.36	0.710	0.30 (0.28)	0.95	60033.5	12010.00
28	31791.88	155.67	0.698	0.30 (0.28)	0.95	60296.1	10210.00
29	31159.54	159.68	0.690	0.30 (0.28)	0.95	60442.9	12000.00
30	27661.84	185.74	0.641	0.30 (0.28)	0.95	61055.8	10100.00

=====
END OF RATIONAL METHOD ANALYSIS
=====

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2010 Advanced Engineering Software (aes)
Ver. 17.0 Release Date: 07/01/2010 License ID 1527

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 134 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 25-YR EV AUG 2023 ROKAMOTO *

FILE NAME: RU25EV34.DAT
TIME/DATE OF STUDY: 22:25 08/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 25.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 4.808
- 2) 10.00; 3.142
- 3) 15.00; 2.408
- 4) 20.00; 1.996
- 5) 25.00; 1.741
- 6) 30.00; 1.531
- 7) 40.00; 1.330
- 8) 50.00; 1.178
- 9) 60.00; 1.052
- 10) 90.00; 0.883
- 11) 120.00; 0.772
- 12) 180.00; 0.642
- 13) 360.00; 0.472
- 14) 1200.00; 0.207

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU25EV33.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23847.63	23.85	0.30 (0.23)	0.78	6263.7	110.00
2	25717.51	30.87	0.30 (0.24)	0.79	8773.6	100.00
3	26643.11	34.34	0.30 (0.24)	0.80	10086.9	800.00
4	28673.10	44.21	0.30 (0.25)	0.84	14558.0	31100.00
5	31390.73	61.46	0.30 (0.26)	0.88	22322.6	13100.00
6	32440.76	67.85	0.30 (0.27)	0.89	24907.0	11801.00
7	34550.53	78.56	0.30 (0.27)	0.91	29947.9	11530.00
8	36305.36	90.46	0.30 (0.28)	0.92	37122.3	13010.00
9	37497.25	97.20	0.30 (0.28)	0.93	41378.4	11350.00
10	37968.52	101.91	0.30 (0.28)	0.93	44552.6	11130.00
11	37665.26	107.97	0.30 (0.28)	0.94	47479.2	12300.00
12	37467.43	111.85	0.30 (0.28)	0.94	49540.0	11620.00
13	37020.54	116.70	0.30 (0.28)	0.94	51739.8	12400.00
14	36070.92	126.16	0.30 (0.28)	0.94	55141.3	12201.00
15	35177.15	133.59	0.30 (0.28)	0.94	57034.4	12231.00
16	34249.66	141.01	0.30 (0.28)	0.95	58587.1	10400.00
17	32782.40	150.36	0.30 (0.28)	0.95	60033.5	12010.00
18	31791.88	155.67	0.30 (0.28)	0.95	60296.1	10210.00
19	31159.54	159.68	0.30 (0.28)	0.95	60442.9	12000.00
20	27661.84	185.74	0.30 (0.28)	0.95	61055.8	10100.00
TOTAL AREA (ACRES) =						61055.8

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23847.63	23.85	0.30 (0.23)	0.78	6263.7	110.00
2	25717.51	30.87	0.30 (0.24)	0.79	8773.6	100.00
3	26643.11	34.34	0.30 (0.24)	0.80	10086.9	800.00
4	28673.10	44.21	0.30 (0.25)	0.84	14558.0	31100.00
5	31390.73	61.46	0.30 (0.26)	0.88	22322.6	13100.00
6	32440.76	67.85	0.30 (0.27)	0.89	24907.0	11801.00
7	34550.53	78.56	0.30 (0.27)	0.91	29947.9	11530.00
8	36305.36	90.46	0.30 (0.28)	0.92	37122.3	13010.00
9	37497.25	97.20	0.30 (0.28)	0.93	41378.4	11350.00
10	37968.52	101.91	0.30 (0.28)	0.93	44552.6	11130.00
11	37665.26	107.97	0.30 (0.28)	0.94	47479.2	12300.00
12	37467.43	111.85	0.30 (0.28)	0.94	49540.0	11620.00
13	37020.54	116.70	0.30 (0.28)	0.94	51739.8	12400.00

```

14 36070.92 126.16 0.30( 0.28) 0.94 55141.3 12201.00
15 35177.15 133.59 0.30( 0.28) 0.94 57034.4 12231.00
16 34249.66 141.01 0.30( 0.28) 0.95 58587.1 10400.00
17 32782.40 150.36 0.30( 0.28) 0.95 60033.5 12010.00
18 31791.88 155.67 0.30( 0.28) 0.95 60296.1 10210.00
19 31159.54 159.68 0.30( 0.28) 0.95 60442.9 12000.00
20 27661.84 185.74 0.30( 0.28) 0.95 61055.8 10100.00
TOTAL AREA(ACRES) = 61055.8

```

FLOW PROCESS FROM NODE 13308.00 TO NODE 13402.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 212.00 DOWNSTREAM(FEET) = 209.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 623.02 CHANNEL SLOPE = 0.0048
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 10.44
CHANNEL FLOW THRU SUBAREA(CFS) = 37968.52
FLOW VELOCITY(FEET/SEC.) = 14.42 FLOW DEPTH(FEET) = 10.44
TRAVEL TIME(MIN.) = 0.72 Tc(MIN.) = 102.64
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118710.93 FEET.

FLOW PROCESS FROM NODE 13402.00 TO NODE 13402.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: P505XX25.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	224.31	17.58	0.30(0.29)	0.96	146.4	50500.00
TOTAL AREA(ACRES) =						146.4

FLOW PROCESS FROM NODE 13402.00 TO NODE 13402.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23847.63	24.69	1.757	0.30(0.23)	0.78	6263.7	110.00
2	25717.51	31.69	1.497	0.30(0.24)	0.79	8773.6	100.00
3	26643.11	35.15	1.427	0.30(0.24)	0.80	10086.9	800.00
4	28673.10	45.00	1.254	0.30(0.25)	0.84	14558.0	31100.00
5	31390.73	62.23	1.039	0.30(0.26)	0.88	22322.6	13100.00
6	32440.76	68.60	1.004	0.30(0.27)	0.89	24907.0	11801.00
7	34550.53	79.30	0.943	0.30(0.27)	0.91	29947.9	11530.00
8	36305.36	91.19	0.879	0.30(0.28)	0.92	37122.3	13010.00
9	37497.25	97.92	0.854	0.30(0.28)	0.93	41378.4	11350.00
10	37968.52	102.64	0.836	0.30(0.28)	0.93	44552.6	11130.00
11	37665.26	108.69	0.814	0.30(0.28)	0.94	47479.2	12300.00
12	37467.43	112.58	0.799	0.30(0.28)	0.94	49540.0	11620.00

```

13 37020.54 117.42 0.782 0.30( 0.28) 0.94 51739.8 12400.00
14 36070.92 126.89 0.757 0.30( 0.28) 0.94 55141.3 12201.00
15 35177.15 134.33 0.741 0.30( 0.28) 0.94 57034.4 12231.00
16 34249.66 141.75 0.725 0.30( 0.28) 0.95 58587.1 10400.00
17 32782.40 151.11 0.705 0.30( 0.28) 0.95 60033.5 12010.00
18 31791.88 156.43 0.693 0.30( 0.28) 0.95 60296.1 10210.00
19 31159.54 160.45 0.684 0.30( 0.28) 0.95 60442.9 12000.00
20 27661.84 186.54 0.636 0.30( 0.28) 0.95 61055.8 10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118710.93 FEET.

```

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	224.31	17.58	2.196	0.30(0.29)	0.96	146.4	50500.00
LONGEST FLOWPATH FROM NODE 50500.00 TO NODE 13402.00 =							5416.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22092.20	17.58	2.196	0.30(0.23)	0.78	4606.3	50500.00
2	24020.38	24.69	1.757	0.30(0.23)	0.78	6410.1	110.00
3	25859.69	31.69	1.497	0.30(0.24)	0.79	8920.0	100.00
4	26777.11	35.15	1.427	0.30(0.24)	0.80	10233.3	800.00
5	28786.72	45.00	1.254	0.30(0.25)	0.84	14704.4	31100.00
6	31479.13	62.23	1.039	0.30(0.26)	0.88	22469.0	13100.00
7	32524.93	68.60	1.004	0.30(0.27)	0.89	25053.4	11801.00
8	34627.61	79.30	0.943	0.30(0.27)	0.91	30094.3	11530.00
9	36374.84	91.19	0.879	0.30(0.28)	0.92	37268.7	13010.00
10	37563.80	97.92	0.854	0.30(0.28)	0.93	41524.8	11350.00
11	38033.02	102.64	0.836	0.30(0.28)	0.93	44699.0	11130.00
12	37727.13	108.69	0.814	0.30(0.28)	0.94	47625.6	12300.00
13	37527.61	112.58	0.799	0.30(0.28)	0.94	49686.4	11620.00
14	37078.61	117.42	0.782	0.30(0.28)	0.94	51886.1	12400.00
15	36126.12	126.89	0.757	0.30(0.28)	0.94	55287.7	12201.00
16	35230.45	134.33	0.741	0.30(0.28)	0.94	57180.8	12231.00
17	34301.07	141.75	0.725	0.30(0.28)	0.95	58733.5	10400.00
18	32831.43	151.11	0.705	0.30(0.28)	0.95	60179.9	12010.00
19	31839.55	156.43	0.693	0.30(0.28)	0.95	60442.5	10210.00
20	31206.19	160.45	0.684	0.30(0.28)	0.95	60589.3	12000.00
21	27702.78	186.54	0.636	0.30(0.28)	0.95	61202.2	10100.00
TOTAL AREA(ACRES) =						61202.2	

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 38033.02 Tc(MIN.) = 102.635
EFFECTIVE AREA(ACRES) = 44698.97 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 61202.2
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118710.93 FEET.

FLOW PROCESS FROM NODE 13402.00 TO NODE 13404.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 209.00 DOWNSTREAM(FEET) = 207.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 395.35 CHANNEL SLOPE = 0.0051
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 10.30
 CHANNEL FLOW THRU SUBAREA(CFS) = 38033.02
 FLOW VELOCITY(FEET/SEC.) = 14.67 FLOW DEPTH(FEET) = 10.30
 TRAVEL TIME(MIN.) = 0.45 Tc(MIN.) = 103.08
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119106.28 FEET.

 FLOW PROCESS FROM NODE 13404.00 TO NODE 13404.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P506XX25.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	73.67	18.28	0.30	(0.29)	0.97	49.5	50600.00
TOTAL AREA (ACRES) =							49.5

 FLOW PROCESS FROM NODE 13404.00 TO NODE 13404.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22092.20	18.11	2.151	0.30 (0.23)	0.78	4606.3	50500.00
2	24020.38	25.21	1.732	0.30 (0.23)	0.78	6410.1	110.00
3	25859.69	32.20	1.487	0.30 (0.24)	0.79	8920.0	100.00
4	26777.11	35.66	1.417	0.30 (0.24)	0.80	10233.3	800.00
5	28786.72	45.49	1.247	0.30 (0.25)	0.84	14704.4	31100.00
6	31479.13	62.70	1.037	0.30 (0.26)	0.88	22469.0	13100.00
7	32524.93	69.08	1.001	0.30 (0.27)	0.89	25053.4	11801.00
8	34627.61	79.77	0.941	0.30 (0.27)	0.91	30094.3	11530.00
9	36374.84	91.65	0.877	0.30 (0.28)	0.92	37268.7	13010.00
10	37563.80	98.37	0.852	0.30 (0.28)	0.93	41524.8	11350.00
11	38033.02	103.08	0.835	0.30 (0.28)	0.93	44699.0	11130.00
12	37727.13	109.14	0.812	0.30 (0.28)	0.94	47625.6	12300.00
13	37527.61	113.03	0.798	0.30 (0.28)	0.94	49686.4	11620.00
14	37078.61	117.88	0.780	0.30 (0.28)	0.94	51886.1	12400.00
15	36126.12	127.35	0.756	0.30 (0.28)	0.94	55287.7	12201.00
16	35230.45	134.79	0.740	0.30 (0.28)	0.94	57180.8	12231.00
17	34301.07	142.22	0.724	0.30 (0.28)	0.95	58733.5	10400.00
18	32831.43	151.58	0.704	0.30 (0.28)	0.95	60179.9	12010.00
19	31839.55	156.91	0.692	0.30 (0.28)	0.95	60442.5	10210.00
20	31206.19	160.93	0.683	0.30 (0.28)	0.95	60589.3	12000.00
21	27702.78	187.04	0.635	0.30 (0.28)	0.95	61202.2	10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 =							119106.28 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	73.67	18.28	2.137	0.30 (0.29)	0.97	49.5	50600.00
LONGEST FLOWPATH FROM NODE 50600.00 TO NODE 13404.00 =							4378.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22165.73	18.11	2.151	0.30 (0.24)	0.79	4655.4	50500.00
2	22212.17	18.28	2.137	0.30 (0.24)	0.79	4699.1	50600.00
3	24077.89	25.21	1.732	0.30 (0.23)	0.78	6459.6	110.00
4	25907.42	32.20	1.487	0.30 (0.24)	0.79	8969.5	100.00
5	26822.07	35.66	1.417	0.30 (0.24)	0.80	10282.8	800.00
6	28824.88	45.49	1.247	0.30 (0.25)	0.84	14753.9	31100.00
7	31508.92	62.70	1.037	0.30 (0.26)	0.88	22518.5	13100.00
8	32553.29	69.08	1.001	0.30 (0.27)	0.89	25102.9	11801.00
9	34653.57	79.77	0.941	0.30 (0.27)	0.91	30143.8	11530.00
10	36398.26	91.65	0.877	0.30 (0.28)	0.92	37318.2	13010.00
11	37586.23	98.37	0.852	0.30 (0.28)	0.93	41574.2	11350.00
12	38054.75	103.08	0.835	0.30 (0.28)	0.93	44748.5	11130.00
13	37747.96	109.14	0.812	0.30 (0.28)	0.94	47675.1	12300.00
14	37547.88	113.03	0.798	0.30 (0.28)	0.94	49735.9	11620.00
15	37098.16	117.88	0.780	0.30 (0.28)	0.94	51935.6	12400.00
16	36144.71	127.35	0.756	0.30 (0.28)	0.94	55337.2	12201.00
17	35248.41	134.79	0.740	0.30 (0.28)	0.94	57230.3	12231.00
18	34318.39	142.22	0.724	0.30 (0.28)	0.95	58783.0	10400.00
19	32847.94	151.58	0.704	0.30 (0.28)	0.95	60229.4	12010.00
20	31855.59	156.91	0.692	0.30 (0.28)	0.95	60492.0	10210.00
21	31221.88	160.93	0.683	0.30 (0.28)	0.95	60638.8	12000.00
22	27716.57	187.04	0.635	0.30 (0.28)	0.95	61251.7	10100.00
TOTAL AREA (ACRES) =							61251.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 38054.75 Tc(MIN.) = 103.084
 EFFECTIVE AREA(ACRES) = 44748.47 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 61251.7
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119106.28 FEET.

 FLOW PROCESS FROM NODE 13404.00 TO NODE 13406.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 207.00 DOWNSTREAM(FEET) = 195.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1601.97 CHANNEL SLOPE = 0.0075
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 9.23
 CHANNEL FLOW THRU SUBAREA(CFS) = 38054.75
 FLOW VELOCITY(FEET/SEC.) = 16.75 FLOW DEPTH(FEET) = 9.23
 TRAVEL TIME(MIN.) = 1.59 Tc(MIN.) = 104.68
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13406.00 = 120708.25 FEET.

 FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 104.68
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.829
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS

LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

NATURAL FAIR COVER
"GRASS" B 0.20 0.30 1.000 69

NATURAL FAIR COVER
"GRASS" B 4.00 0.30 1.000 69

NATURAL FAIR COVER
"GRASS" B 2.00 0.30 1.000 69

NATURAL FAIR COVER
"OPEN BRUSH" B 9.70 0.30 1.000 66

NATURAL FAIR COVER
"OPEN BRUSH" B 2.60 0.30 1.000 66

AGRICULTURAL POOR COVER
"ROW CROPS, STRAIGHT ROW" B 1.60 0.30 1.000 81

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 20.10 SUBAREA RUNOFF (CFS) = 9.56
EFFECTIVE AREA (ACRES) = 44768.57 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA (ACRES) = 61271.8 PEAK FLOW RATE (CFS) = 38054.75
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 104.68
* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.829
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "ROW CROPS, STRAIGHT ROW"	B	2.00	0.30	1.000	81
NATURAL FAIR COVER "WOODLAND, GRASS"	B	7.10	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND, GRASS"	B	5.80	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.10	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 15.00 SUBAREA RUNOFF (CFS) = 7.14
EFFECTIVE AREA (ACRES) = 44783.57 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA (ACRES) = 61286.8 PEAK FLOW RATE (CFS) = 38054.75
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13406.00 TO NODE 13408.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 195.00 DOWNSTREAM (FEET) = 182.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 2458.36 CHANNEL SLOPE = 0.0053
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 10.18

* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.819
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	7.00	0.30	1.000	66
NATURAL FAIR COVER "WOODLAND, GRASS"	B	3.30	0.30	1.000	65
COMMERCIAL	B	0.40	0.30	0.100	56
NATURAL FAIR COVER "OPEN BRUSH"	B	1.40	0.30	1.000	66
COMMERCIAL	B	0.30	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.949
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 38057.73
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 14.90
AVERAGE FLOW DEPTH (FEET) = 10.18 TRAVEL TIME (MIN.) = 2.75
Tc (MIN.) = 107.43
SUBAREA AREA (ACRES) = 12.40 SUBAREA RUNOFF (CFS) = 5.96
EFFECTIVE AREA (ACRES) = 44795.97 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA (ACRES) = 61299.2 PEAK FLOW RATE (CFS) = 38054.75
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 10.18

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 10.18 FLOW VELOCITY (FEET/SEC.) = 14.89
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123166.61 FEET.

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 2P25EVBB.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	676.18	9.97	0.30 (0.11)	0.38	243.5	429.00
2	719.57	11.48	0.30 (0.11)	0.38	280.3	425.00
3	729.64	11.90	0.30 (0.11)	0.38	290.5	400.00
4	756.99	13.36	0.30 (0.11)	0.38	326.6	300.00
5	801.01	18.55	0.30 (0.11)	0.38	439.8	210.00
6	788.68	20.66	0.30 (0.11)	0.38	466.8	410.00
7	782.25	21.72	0.30 (0.11)	0.38	480.1	200.00
8	780.36	22.29	0.30 (0.11)	0.38	486.6	230.00
9	762.79	23.40	0.30 (0.11)	0.37	491.2	220.50
TOTAL AREA (ACRES) =			491.2			

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22165.73	23.31	1.827	0.30 (0.24)	0.79	4702.9	50500.00
2	22212.17	23.48	1.819	0.30 (0.24)	0.79	4746.6	50600.00
3	24077.89	30.26	1.526	0.30 (0.24)	0.78	6507.1	110.00
4	25907.42	37.13	1.388	0.30 (0.24)	0.79	9017.0	100.00
5	26822.07	40.53	1.322	0.30 (0.24)	0.80	10330.3	800.00
6	28824.88	50.25	1.175	0.30 (0.25)	0.85	14801.4	31100.00
7	31508.92	67.33	1.011	0.30 (0.26)	0.88	22566.0	13100.00
8	32553.29	73.65	0.975	0.30 (0.27)	0.89	25150.4	11801.00
9	34653.57	84.25	0.915	0.30 (0.27)	0.91	30191.3	11530.00
10	36398.26	96.06	0.861	0.30 (0.28)	0.92	37365.7	13010.00
11	37586.23	102.73	0.836	0.30 (0.28)	0.93	41621.8	11350.00
12	38054.75	107.43	0.819	0.30 (0.28)	0.93	44796.0	11130.00
13	37747.96	113.50	0.796	0.30 (0.28)	0.94	47722.6	12300.00
14	37547.88	117.39	0.782	0.30 (0.28)	0.94	49783.4	11620.00
15	37098.16	122.26	0.767	0.30 (0.28)	0.94	51983.1	12400.00
16	36144.71	131.76	0.747	0.30 (0.28)	0.94	55384.7	12201.00
17	35248.41	139.24	0.730	0.30 (0.28)	0.94	57277.8	12231.00
18	34318.39	146.71	0.714	0.30 (0.28)	0.95	58830.5	10400.00
19	32847.94	156.14	0.694	0.30 (0.28)	0.95	60276.9	12010.00
20	31855.59	161.52	0.682	0.30 (0.28)	0.95	60539.5	10210.00
21	31221.88	165.56	0.673	0.30 (0.28)	0.95	60686.3	12000.00
22	27716.57	191.86	0.631	0.30 (0.28)	0.95	61299.2	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123166.61 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	676.18	9.97	3.154	0.30 (0.11)	0.38	243.5	429.00
2	719.57	11.48	2.925	0.30 (0.11)	0.38	280.3	425.00
3	729.64	11.90	2.863	0.30 (0.11)	0.38	290.5	400.00
4	756.99	13.36	2.648	0.30 (0.11)	0.38	326.6	300.00
5	801.01	18.55	2.115	0.30 (0.11)	0.38	439.8	210.00
6	788.68	20.66	1.962	0.30 (0.11)	0.38	466.8	410.00
7	782.25	21.72	1.908	0.30 (0.11)	0.38	480.1	200.00
8	780.36	22.29	1.879	0.30 (0.11)	0.38	486.6	230.00
9	762.79	23.40	1.823	0.30 (0.11)	0.37	491.2	220.50

LONGEST FLOWPATH FROM NODE 230.00 TO NODE 13408.00 = 11903.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18051.91	9.97	3.154	0.30 (0.22)	0.74	2254.1	429.00
2	19165.08	11.48	2.925	0.30 (0.22)	0.74	2596.0	425.00
3	19411.60	11.90	2.863	0.30 (0.22)	0.74	2691.0	400.00
4	20022.35	13.36	2.648	0.30 (0.22)	0.74	3023.1	300.00
5	21636.83	18.55	2.115	0.30 (0.22)	0.74	4182.7	210.00
6	22104.78	20.66	1.962	0.30 (0.22)	0.75	4635.8	410.00
7	22489.26	21.72	1.908	0.30 (0.22)	0.75	4862.5	200.00
8	22668.47	22.29	1.879	0.30 (0.22)	0.75	4983.2	230.00
9	22929.95	23.31	1.827	0.30 (0.22)	0.75	5193.7	50500.00

10	22953.44	23.40	1.823	0.30 (0.22)	0.75	5217.6	220.50
11	22973.18	23.48	1.819	0.30 (0.22)	0.75	5237.8	50600.00
12	24708.27	30.26	1.526	0.30 (0.23)	0.76	6998.3	110.00
13	26476.22	37.13	1.388	0.30 (0.23)	0.77	9508.2	100.00
14	27361.54	40.53	1.322	0.30 (0.23)	0.78	10821.5	800.00
15	29298.78	50.25	1.175	0.30 (0.25)	0.83	15292.6	31100.00
16	31909.59	67.33	1.011	0.30 (0.26)	0.87	23057.2	13100.00
17	32938.07	73.65	0.975	0.30 (0.26)	0.88	25641.6	11801.00
18	35011.73	84.25	0.915	0.30 (0.27)	0.90	30682.5	11530.00
19	36731.96	96.06	0.861	0.30 (0.27)	0.91	37856.9	13010.00
20	37908.92	102.73	0.836	0.30 (0.28)	0.92	42112.9	11350.00
21	38369.69	107.43	0.819	0.30 (0.28)	0.93	45287.2	11130.00
22	38052.89	113.50	0.796	0.30 (0.28)	0.93	48213.8	12300.00
23	37846.37	117.39	0.782	0.30 (0.28)	0.93	50274.6	11620.00
24	37390.16	122.26	0.767	0.30 (0.28)	0.94	52474.3	12400.00
25	36427.54	131.76	0.747	0.30 (0.28)	0.94	55875.9	12201.00
26	35524.01	139.24	0.730	0.30 (0.28)	0.94	57769.0	12231.00
27	34586.77	146.71	0.714	0.30 (0.28)	0.94	59321.7	10400.00
28	33107.20	156.14	0.694	0.30 (0.28)	0.94	60768.1	12010.00
29	32109.66	161.52	0.682	0.30 (0.28)	0.94	61030.7	10210.00
30	31472.04	165.56	0.673	0.30 (0.28)	0.94	61177.5	12000.00
31	27947.78	191.86	0.631	0.30 (0.28)	0.94	61790.4	10100.00

TOTAL AREA (ACRES) = 61790.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 38369.69 Tc (MIN.) = 107.428
EFFECTIVE AREA (ACRES) = 45287.17 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.76
TOTAL AREA (ACRES) = 61790.4
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123166.61 FEET.

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P507XX25.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	293.66	22.81	0.30 (0.30)	0.99	231.4	50700.00	

TOTAL AREA (ACRES) = 231.4

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
---------------	---------	-----------	---------------------	------------------	----	------------	----------------

1	18051.91	9.97	3.154	0.30	(0.22)	0.74	2254.1	429.00
2	19165.08	11.48	2.925	0.30	(0.22)	0.74	2596.0	425.00
3	19411.60	11.90	2.863	0.30	(0.22)	0.74	2691.0	400.00
4	20022.35	13.36	2.648	0.30	(0.22)	0.74	3023.1	300.00
5	21636.83	18.55	2.115	0.30	(0.22)	0.74	4182.7	210.00
6	22104.78	20.66	1.962	0.30	(0.22)	0.75	4635.8	410.00
7	22489.26	21.72	1.908	0.30	(0.22)	0.75	4862.5	200.00
8	22668.47	22.29	1.879	0.30	(0.22)	0.75	4983.2	230.00
9	22929.95	23.31	1.827	0.30	(0.22)	0.75	5193.7	50500.00
10	22953.44	23.40	1.823	0.30	(0.22)	0.75	5217.6	220.50
11	22973.18	23.48	1.819	0.30	(0.22)	0.75	5237.8	50600.00
12	24708.27	30.26	1.526	0.30	(0.23)	0.76	6998.3	110.00
13	26476.22	37.13	1.388	0.30	(0.23)	0.77	9508.2	100.00
14	27361.54	40.53	1.322	0.30	(0.23)	0.78	10821.5	800.00
15	29298.78	50.25	1.175	0.30	(0.25)	0.83	15292.6	31100.00
16	31909.59	67.33	1.011	0.30	(0.26)	0.87	23057.2	13100.00
17	32938.07	73.65	0.975	0.30	(0.26)	0.88	25641.6	11801.00
18	35011.73	84.25	0.915	0.30	(0.27)	0.90	30682.5	11530.00
19	36731.96	96.06	0.861	0.30	(0.27)	0.91	37856.9	13010.00
20	37908.92	102.73	0.836	0.30	(0.28)	0.92	42112.9	11350.00
21	38369.69	107.43	0.819	0.30	(0.28)	0.93	45287.2	11130.00
22	38052.89	113.50	0.796	0.30	(0.28)	0.93	48213.8	12300.00
23	37846.37	117.39	0.782	0.30	(0.28)	0.93	50274.6	11620.00
24	37390.16	122.26	0.767	0.30	(0.28)	0.94	52474.3	12400.00
25	36427.54	131.76	0.747	0.30	(0.28)	0.94	55875.9	12201.00
26	35524.01	139.24	0.730	0.30	(0.28)	0.94	57769.0	12231.00
27	34586.77	146.71	0.714	0.30	(0.28)	0.94	59321.7	10400.00
28	33107.20	156.14	0.694	0.30	(0.28)	0.94	60768.1	12010.00
29	32109.66	161.52	0.682	0.30	(0.28)	0.94	61030.7	10210.00
30	31472.04	165.56	0.673	0.30	(0.28)	0.94	61177.5	12000.00
31	27947.78	191.86	0.631	0.30	(0.28)	0.94	61790.4	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123166.61 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	293.66	22.81	1.853	0.30	(0.30)	0.99	231.4 50700.00

LONGEST FLOWPATH FROM NODE 50700.00 TO NODE 13408.00 = 7683.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18287.46	9.97	3.154	0.30	(0.23)	0.75	2355.2 429.00
2	19414.68	11.48	2.925	0.30	(0.23)	0.75	2712.5 425.00
3	19664.27	11.90	2.863	0.30	(0.23)	0.75	2811.7 400.00
4	20282.36	13.36	2.648	0.30	(0.23)	0.75	3158.7 300.00
5	21915.99	18.55	2.115	0.30	(0.23)	0.75	4370.9 210.00
6	22389.54	20.66	1.962	0.30	(0.23)	0.76	4845.4 410.00
7	22778.90	21.72	1.908	0.30	(0.23)	0.76	5082.9 200.00
8	22960.33	22.29	1.879	0.30	(0.23)	0.76	5209.4 230.00
9	23094.91	22.81	1.853	0.30	(0.23)	0.76	5321.5 50700.00
10	23218.78	23.31	1.827	0.30	(0.23)	0.76	5425.1 50500.00
11	23241.39	23.40	1.823	0.30	(0.23)	0.76	5449.0 220.50
12	23260.38	23.48	1.819	0.30	(0.23)	0.76	5469.2 50600.00
13	24940.21	30.26	1.526	0.30	(0.23)	0.76	7229.7 110.00
14	26682.11	37.13	1.388	0.30	(0.23)	0.78	9739.6 100.00
15	27555.03	40.53	1.322	0.30	(0.24)	0.78	11052.9 800.00
16	29464.52	50.25	1.175	0.30	(0.25)	0.83	15524.0 31100.00

17	32044.36	67.33	1.011	0.30	(0.26)	0.87	23288.6	13100.00
18	33066.12	73.65	0.975	0.30	(0.26)	0.88	25873.0	11801.00
19	35128.52	84.25	0.915	0.30	(0.27)	0.90	30913.9	11530.00
20	36838.41	96.06	0.861	0.30	(0.27)	0.91	38088.3	13010.00
21	38010.70	102.73	0.836	0.30	(0.28)	0.92	42344.3	11350.00
22	38468.19	107.43	0.819	0.30	(0.28)	0.93	45518.6	11130.00
23	38147.16	113.50	0.796	0.30	(0.28)	0.93	48445.1	12300.00
24	37937.92	117.39	0.782	0.30	(0.28)	0.93	50506.0	11620.00
25	37478.97	122.26	0.767	0.30	(0.28)	0.94	52705.7	12400.00
26	36512.45	131.76	0.747	0.30	(0.28)	0.94	56107.3	12201.00
27	35605.87	139.24	0.730	0.30	(0.28)	0.94	58000.4	12231.00
28	34665.57	146.71	0.714	0.30	(0.28)	0.94	59553.1	10400.00
29	33182.16	156.14	0.694	0.30	(0.28)	0.94	60999.5	12010.00
30	32182.42	161.52	0.682	0.30	(0.28)	0.94	61262.1	10210.00
31	31543.15	165.56	0.673	0.30	(0.28)	0.94	61408.9	12000.00
32	28010.86	191.86	0.631	0.30	(0.28)	0.94	62021.8	10100.00

TOTAL AREA (ACRES) = 62021.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 38468.19 Tc (MIN.) = 107.428
 EFFECTIVE AREA (ACRES) = 45518.57 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA (ACRES) = 62021.8
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123166.61 FEET.

FLOW PROCESS FROM NODE 13408.00 TO NODE 13410.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 182.00 DOWNSTREAM (FEET) = 178.72
 CHANNEL LENGTH THRU SUBAREA (FEET) = 952.73 CHANNEL SLOPE = 0.0034
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT (FEET) = 11.55
 * 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.814
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.40	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	2.90	0.30	1.000	65

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 38468.95
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 12.92
 AVERAGE FLOW DEPTH (FEET) = 11.55 TRAVEL TIME (MIN.) = 1.23
 Tc (MIN.) = 108.66
 SUBAREA AREA (ACRES) = 3.30 SUBAREA RUNOFF (CFS) = 1.53
 EFFECTIVE AREA (ACRES) = 45521.87 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA (ACRES) = 62025.1 PEAK FLOW RATE (CFS) = 38468.19
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT (FEET) = 11.55

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 11.55 FLOW VELOCITY(FEET/SEC.) = 12.92
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124119.34 FEET.

 FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<<

 FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<<

PEAK FLOWRATE TABLE FILE NAME: RU25EV36.DNA
 MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2146.94	28.56	0.30(0.27)	0.90	1467.2	110.00
2	2209.70	30.95	0.30(0.27)	0.90	1632.7	100.00
3	2208.11	32.23	0.30(0.27)	0.90	1711.6	100.00
4	2242.46	35.30	0.30(0.27)	0.91	1886.6	130.00
5	2335.95	48.91	0.30(0.28)	0.93	2627.1	20100.00
6	2291.36	54.60	0.30(0.28)	0.93	2814.2	13600.00
7	2090.26	91.42	0.30(0.28)	0.93	3793.8	13510.00
8	1979.94	100.93	0.30(0.28)	0.93	3859.7	13500.00
TOTAL AREA (ACRES) =						3859.7

 FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18287.46	11.53	2.917	0.30(0.23)	0.75	2358.5	429.00
2	19414.68	13.01	2.699	0.30(0.23)	0.75	2715.8	425.00
3	19664.27	13.43	2.639	0.30(0.23)	0.75	2815.0	400.00
4	20282.36	14.88	2.426	0.30(0.23)	0.75	3162.0	300.00
5	21915.99	20.03	1.995	0.30(0.23)	0.76	4374.2	210.00
6	22389.54	22.13	1.887	0.30(0.23)	0.76	4848.7	410.00
7	22778.90	23.18	1.834	0.30(0.23)	0.76	5086.2	200.00
8	22960.33	23.74	1.805	0.30(0.23)	0.76	5212.7	230.00
9	23094.91	24.26	1.779	0.30(0.23)	0.76	5324.8	50700.00
10	23218.78	24.76	1.753	0.30(0.23)	0.76	5428.4	50500.00
11	23241.39	24.85	1.749	0.30(0.23)	0.76	5452.3	220.50
12	23260.38	24.92	1.745	0.30(0.23)	0.76	5472.5	50600.00
13	24940.21	31.68	1.497	0.30(0.23)	0.76	7233.0	110.00
14	26682.11	38.51	1.360	0.30(0.23)	0.78	9742.9	100.00
15	27555.03	41.90	1.301	0.30(0.24)	0.78	11056.2	800.00
16	29464.52	51.58	1.158	0.30(0.25)	0.83	15527.3	31100.00
17	32044.36	68.63	1.003	0.30(0.26)	0.87	23291.9	13100.00
18	33066.12	74.94	0.968	0.30(0.26)	0.88	25876.3	11801.00
19	35128.52	85.51	0.908	0.30(0.27)	0.90	30917.2	11530.00

20	36838.41	97.30	0.856	0.30(0.27)	0.91	38091.6	13010.00
21	38010.70	103.97	0.831	0.30(0.28)	0.92	42347.6	11350.00
22	38468.19	108.66	0.814	0.30(0.28)	0.93	45521.9	11130.00
23	38147.16	114.73	0.791	0.30(0.28)	0.93	48448.4	12300.00
24	37937.92	118.63	0.777	0.30(0.28)	0.93	50509.3	11620.00
25	37478.97	123.50	0.764	0.30(0.28)	0.94	52709.0	12400.00
26	36512.45	133.01	0.744	0.30(0.28)	0.94	56110.6	12201.00
27	35605.87	140.50	0.728	0.30(0.28)	0.94	58003.7	12231.00
28	34665.57	147.98	0.711	0.30(0.28)	0.94	59556.4	10400.00
29	33182.16	157.43	0.691	0.30(0.28)	0.94	61002.8	12010.00
30	32182.42	162.82	0.679	0.30(0.28)	0.94	61265.4	10210.00
31	31543.15	166.87	0.670	0.30(0.28)	0.94	61412.2	12000.00
32	28010.86	193.22	0.630	0.30(0.28)	0.94	62025.1	10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 =						124119.34 FEET.	

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2146.94	28.56	1.591	0.30(0.27)	0.90	1467.2	110.00
2	2209.70	30.95	1.512	0.30(0.27)	0.90	1632.7	100.00
3	2208.11	32.23	1.486	0.30(0.27)	0.90	1711.6	100.00
4	2242.46	35.30	1.425	0.30(0.27)	0.91	1886.6	130.00
5	2335.95	48.91	1.195	0.30(0.28)	0.93	2627.1	20100.00
6	2291.36	54.60	1.120	0.30(0.28)	0.93	2814.2	13600.00
7	2090.26	91.42	0.878	0.30(0.28)	0.93	3793.8	13510.00
8	1979.94	100.93	0.843	0.30(0.28)	0.93	3859.7	13500.00
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13410.00 =						41710.10 FEET.	

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20024.35	11.53	2.917	0.30(0.24)	0.78	2950.8	429.00
2	21213.65	13.01	2.699	0.30(0.23)	0.78	3384.3	425.00
3	21473.98	13.43	2.639	0.30(0.23)	0.78	3504.7	400.00
4	22107.29	14.88	2.426	0.30(0.23)	0.78	3926.2	300.00
5	23880.91	20.03	1.995	0.30(0.23)	0.78	5402.8	210.00
6	24425.71	22.13	1.887	0.30(0.24)	0.78	5985.4	410.00
7	24841.05	23.18	1.834	0.30(0.24)	0.78	6276.8	200.00
8	25033.76	23.74	1.805	0.30(0.24)	0.78	6432.1	230.00
9	25177.08	24.26	1.779	0.30(0.24)	0.79	6570.8	50700.00
10	25307.94	24.76	1.753	0.30(0.24)	0.79	6700.1	50500.00
11	25331.67	24.85	1.749	0.30(0.24)	0.79	6728.6	220.50
12	25351.57	24.92	1.745	0.30(0.24)	0.79	6752.8	50600.00
13	26312.56	28.56	1.591	0.30(0.24)	0.79	7888.4	110.00
14	26970.17	30.95	1.512	0.30(0.24)	0.79	8677.4	100.00
15	27149.01	31.68	1.497	0.30(0.24)	0.79	8910.4	110.00
16	27289.54	32.23	1.486	0.30(0.24)	0.79	9148.1	100.00
17	28104.69	35.30	1.425	0.30(0.24)	0.80	10448.2	130.00
18	28946.67	38.51	1.360	0.30(0.24)	0.80	11804.6	100.00
19	29842.84	41.90	1.301	0.30(0.24)	0.81	13302.0	800.00
20	31273.53	48.91	1.195	0.30(0.25)	0.84	16920.6	20100.00
21	31779.52	51.58	1.158	0.30(0.25)	0.85	18242.4	31100.00
22	32212.18	54.60	1.120	0.30(0.26)	0.85	19714.8	13600.00
23	34259.10	68.63	1.003	0.30(0.26)	0.88	26479.4	13100.00
24	35246.39	74.94	0.968	0.30(0.27)	0.89	29231.6	11801.00
25	37251.05	85.51	0.908	0.30(0.27)	0.90	34553.8	11530.00
26	38075.61	91.42	0.878	0.30(0.27)	0.91	38306.1	13510.00
27	38860.39	97.30	0.856	0.30(0.27)	0.92	41926.2	13010.00

28	39455.72	100.93	0.843	0.30	(0.28)	0.92	44265.3	13500.00
29	39951.05	103.97	0.831	0.30	(0.28)	0.92	46207.3	11350.00
30	40347.44	108.66	0.814	0.30	(0.28)	0.93	49381.6	11130.00
31	39947.32	114.73	0.791	0.30	(0.28)	0.93	52308.1	12300.00
32	39687.37	118.63	0.777	0.30	(0.28)	0.93	54369.0	11620.00
33	39183.84	123.50	0.764	0.30	(0.28)	0.94	56568.7	12400.00
34	38144.75	133.01	0.744	0.30	(0.28)	0.94	59970.3	12201.00
35	37181.08	140.50	0.728	0.30	(0.28)	0.94	61863.3	12231.00
36	36183.73	147.98	0.711	0.30	(0.28)	0.94	63416.1	10400.00
37	34628.27	157.43	0.691	0.30	(0.28)	0.94	64862.5	12010.00
38	33587.44	162.82	0.679	0.30	(0.28)	0.94	65125.1	10210.00
39	32917.25	166.87	0.670	0.30	(0.28)	0.94	65271.9	12000.00
40	29240.90	193.22	0.630	0.30	(0.28)	0.94	65884.8	10100.00

TOTAL AREA (ACRES) = 65884.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 40347.44 Tc (MIN.) = 108.658
EFFECTIVE AREA (ACRES) = 49381.55 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.85
TOTAL AREA (ACRES) = 65884.8
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124119.34 FEET.

FLOW PROCESS FROM NODE 13410.00 TO NODE 13412.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 178.72 DOWNSTREAM (FEET) = 176.93
CHANNEL LENGTH THRU SUBAREA (FEET) = 169.78 CHANNEL SLOPE = 0.0105
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 8.66
CHANNEL FLOW THRU SUBAREA (CFS) = 40347.44
FLOW VELOCITY (FEET/SEC.) = 19.16 FLOW DEPTH (FEET) = 8.66
TRAVEL TIME (MIN.) = 0.15 Tc (MIN.) = 108.81
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124289.12 FEET.

FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<

FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<

PEAK FLOWRATE TABLE FILE NAME: 0506101D.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	518.50	38.19	0.30 (0.30)	0.98	591.0	10100.00

TOTAL AREA (ACRES) = 591.0

FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20024.35	11.72	2.890	0.30 (0.24)	0.78	2950.8	429.00
2	21213.65	13.20	2.673	0.30 (0.23)	0.78	3384.3	425.00
3	21473.98	13.61	2.612	0.30 (0.23)	0.78	3504.7	400.00
4	22107.29	15.06	2.403	0.30 (0.23)	0.78	3926.2	300.00
5	23880.91	20.20	1.986	0.30 (0.23)	0.78	5402.8	210.00
6	24425.71	22.30	1.879	0.30 (0.24)	0.78	5985.4	410.00
7	24841.05	23.35	1.825	0.30 (0.24)	0.78	6276.8	200.00
8	25033.76	23.91	1.796	0.30 (0.24)	0.78	6432.1	230.00
9	25177.08	24.43	1.770	0.30 (0.24)	0.79	6570.8	50700.00
10	25307.94	24.93	1.745	0.30 (0.24)	0.79	6700.1	50500.00
11	25331.67	25.02	1.740	0.30 (0.24)	0.79	6728.6	220.50
12	25351.57	25.10	1.737	0.30 (0.24)	0.79	6752.8	50600.00
13	26312.56	28.73	1.584	0.30 (0.24)	0.79	7888.4	110.00
14	26970.17	31.12	1.508	0.30 (0.24)	0.79	8677.4	100.00
15	27149.01	31.85	1.494	0.30 (0.24)	0.79	8910.4	110.00
16	27289.54	32.40	1.483	0.30 (0.24)	0.79	9148.1	100.00
17	28104.69	35.46	1.421	0.30 (0.24)	0.80	10448.2	130.00
18	28946.67	38.68	1.357	0.30 (0.24)	0.80	11804.6	100.00
19	29842.84	42.06	1.299	0.30 (0.24)	0.81	13302.0	800.00
20	31273.53	49.07	1.192	0.30 (0.25)	0.84	16920.6	20100.00
21	31779.52	51.74	1.156	0.30 (0.25)	0.85	18242.4	31100.00
22	32212.18	54.76	1.118	0.30 (0.26)	0.85	19714.8	13600.00
23	34259.10	68.79	1.003	0.30 (0.26)	0.88	26479.4	13100.00
24	35246.39	75.09	0.967	0.30 (0.27)	0.89	29231.6	11801.00
25	37251.05	85.66	0.907	0.30 (0.27)	0.90	34553.8	11530.00
26	38075.61	91.57	0.877	0.30 (0.27)	0.91	38306.1	13510.00
27	38860.39	97.45	0.855	0.30 (0.27)	0.92	41926.2	13010.00
28	39455.72	101.07	0.842	0.30 (0.28)	0.92	44265.3	13500.00
29	39951.05	104.11	0.831	0.30 (0.28)	0.92	46207.3	11350.00
30	40347.44	108.81	0.813	0.30 (0.28)	0.93	49381.6	11130.00
31	39947.32	114.88	0.791	0.30 (0.28)	0.93	52308.1	12300.00
32	39687.37	118.77	0.777	0.30 (0.28)	0.93	54369.0	11620.00
33	39183.84	123.65	0.764	0.30 (0.28)	0.94	56568.7	12400.00
34	38144.75	133.17	0.743	0.30 (0.28)	0.94	59970.3	12201.00
35	37181.08	140.65	0.727	0.30 (0.28)	0.94	61863.3	12231.00
36	36183.73	148.14	0.711	0.30 (0.28)	0.94	63416.1	10400.00
37	34628.27	157.58	0.691	0.30 (0.28)	0.94	64862.5	12010.00
38	33587.44	162.97	0.679	0.30 (0.28)	0.94	65125.1	10210.00
39	32917.25	167.03	0.670	0.30 (0.28)	0.94	65271.9	12000.00
40	29240.90	193.39	0.629	0.30 (0.28)	0.94	65884.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124289.12 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	518.50	38.19	1.366	0.30 (0.30)	0.98	591.0	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 14677.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	518.50	38.19	1.366	0.30 (0.30)	0.98	591.0	10100.00

1	20409.68	11.72	2.890	0.30	(0.24)	0.80	3132.2	429.00
2	21611.29	13.20	2.673	0.30	(0.24)	0.79	3588.5	425.00
3	21873.61	13.61	2.612	0.30	(0.24)	0.79	3715.3	400.00
4	22509.60	15.06	2.403	0.30	(0.24)	0.79	4159.3	300.00
5	24313.75	20.20	1.986	0.30	(0.24)	0.79	5715.5	210.00
6	24873.28	22.30	1.879	0.30	(0.24)	0.80	6330.6	410.00
7	25293.83	23.35	1.825	0.30	(0.24)	0.80	6638.2	200.00
8	25488.75	23.91	1.796	0.30	(0.24)	0.80	6802.2	230.00
9	25633.75	24.43	1.770	0.30	(0.24)	0.80	6948.8	50700.00
10	25765.89	24.93	1.745	0.30	(0.24)	0.80	7085.9	50500.00
11	25789.88	25.02	1.740	0.30	(0.24)	0.80	7115.8	220.50
12	25810.16	25.10	1.737	0.30	(0.24)	0.80	7141.2	50600.00
13	26781.98	28.73	1.584	0.30	(0.24)	0.80	8333.1	110.00
14	27448.75	31.12	1.508	0.30	(0.24)	0.80	9159.0	100.00
15	27632.83	31.85	1.494	0.30	(0.24)	0.80	9403.2	110.00
16	27777.21	32.40	1.483	0.30	(0.24)	0.80	9649.5	100.00
17	28610.80	35.46	1.421	0.30	(0.24)	0.80	10997.0	130.00
18	29337.06	38.19	1.366	0.30	(0.24)	0.81	12189.2	10100.00
19	29460.41	38.68	1.357	0.30	(0.24)	0.81	12395.6	100.00
20	30328.55	42.06	1.299	0.30	(0.24)	0.81	13893.0	800.00
21	31707.68	49.07	1.192	0.30	(0.25)	0.84	17511.6	20100.00
22	32196.21	51.74	1.156	0.30	(0.26)	0.85	18833.4	31100.00
23	32610.49	54.76	1.118	0.30	(0.26)	0.86	20305.8	13600.00
24	34601.50	68.79	1.003	0.30	(0.26)	0.88	27070.4	13100.00
25	35571.59	75.09	0.967	0.30	(0.27)	0.89	29822.6	11801.00
26	37547.43	85.66	0.907	0.30	(0.27)	0.90	35144.8	11530.00
27	38357.36	91.57	0.877	0.30	(0.27)	0.91	38897.1	13510.00
28	39131.61	97.45	0.855	0.30	(0.27)	0.92	42517.2	13010.00
29	39720.45	101.07	0.842	0.30	(0.28)	0.92	44856.3	13500.00
30	40210.34	104.11	0.831	0.30	(0.28)	0.92	46798.3	11350.00
31	40598.32	108.81	0.813	0.30	(0.28)	0.93	49972.6	11130.00
32	40187.33	114.88	0.791	0.30	(0.28)	0.93	52899.1	12300.00
33	39920.40	118.77	0.777	0.30	(0.28)	0.93	54960.0	11620.00
34	39410.86	123.65	0.764	0.30	(0.28)	0.94	57159.7	12400.00
35	38361.79	133.17	0.743	0.30	(0.28)	0.94	60561.3	12201.00
36	37390.26	140.65	0.727	0.30	(0.28)	0.94	62454.3	12231.00
37	36385.06	148.14	0.711	0.30	(0.28)	0.94	64007.1	10400.00
38	34819.70	157.58	0.691	0.30	(0.28)	0.94	65453.5	12010.00
39	33773.22	162.97	0.679	0.30	(0.28)	0.94	65716.1	10210.00
40	33098.77	167.03	0.670	0.30	(0.28)	0.94	65862.9	12000.00
41	29402.70	193.39	0.629	0.30	(0.28)	0.94	66475.8	10100.00

TOTAL AREA (ACRES) = 66475.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 40598.32 Tc (MIN.) = 108.805
EFFECTIVE AREA (ACRES) = 49972.55 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA (ACRES) = 66475.8
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124289.12 FEET.

FLOW PROCESS FROM NODE 13412.00 TO NODE 13700.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 176.93 DOWNSTREAM (FEET) = 170.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 260.10 CHANNEL SLOPE = 0.0266

GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 6.66
CHANNEL FLOW THRU SUBAREA (CFS) = 40598.32
FLOW VELOCITY (FEET/SEC.) = 26.11 FLOW DEPTH (FEET) = 6.66
TRAVEL TIME (MIN.) = 0.17 Tc (MIN.) = 108.97
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124549.22 FEET.

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P508XX25.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	168.28	22.49	0.30 (0.30)	0.99	131.3	50800.00
TOTAL AREA (ACRES) =				131.3		

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20409.68	11.93	2.859	0.30 (0.24)	0.80	3132.2	429.00
2	21611.29	13.40	2.642	0.30 (0.24)	0.79	3588.5	425.00
3	21873.61	13.82	2.582	0.30 (0.24)	0.79	3715.3	400.00
4	22509.60	15.26	2.386	0.30 (0.24)	0.79	4159.3	300.00
5	24313.75	20.40	1.976	0.30 (0.24)	0.79	5715.5	210.00
6	24873.28	22.50	1.868	0.30 (0.24)	0.80	6330.6	410.00
7	25293.83	23.55	1.815	0.30 (0.24)	0.80	6638.2	200.00
8	25488.75	24.11	1.786	0.30 (0.24)	0.80	6802.2	230.00
9	25633.75	24.62	1.760	0.30 (0.24)	0.80	6948.8	50700.00
10	25765.89	25.12	1.736	0.30 (0.24)	0.80	7085.9	50500.00
11	25789.88	25.21	1.732	0.30 (0.24)	0.80	7115.8	220.50
12	25810.16	25.29	1.729	0.30 (0.24)	0.80	7141.2	50600.00
13	26781.98	28.93	1.576	0.30 (0.24)	0.80	8333.1	110.00
14	27448.75	31.31	1.505	0.30 (0.24)	0.80	9159.0	100.00
15	27632.83	32.03	1.490	0.30 (0.24)	0.80	9403.2	110.00
16	27777.21	32.59	1.479	0.30 (0.24)	0.80	9649.5	100.00
17	28610.80	35.65	1.417	0.30 (0.24)	0.80	10997.0	130.00
18	29337.06	38.38	1.363	0.30 (0.24)	0.81	12189.2	10100.00
19	29460.41	38.86	1.353	0.30 (0.24)	0.81	12395.6	100.00
20	30328.55	42.25	1.296	0.30 (0.24)	0.81	13893.0	800.00
21	31707.68	49.25	1.189	0.30 (0.25)	0.84	17511.6	20100.00
22	32196.21	51.92	1.154	0.30 (0.26)	0.85	18833.4	31100.00
23	32610.49	54.94	1.116	0.30 (0.26)	0.86	20305.8	13600.00

24	34601.50	68.96	1.002	0.30	(0.26)	0.88	27070.4	13100.00
25	35571.59	75.27	0.966	0.30	(0.27)	0.89	29822.6	11801.00
26	37547.43	85.83	0.906	0.30	(0.27)	0.90	35144.8	11530.00
27	38357.36	91.74	0.877	0.30	(0.27)	0.91	38897.1	13510.00
28	39131.61	97.62	0.855	0.30	(0.27)	0.92	42517.2	13010.00
29	39720.45	101.24	0.841	0.30	(0.28)	0.92	44856.3	13500.00
30	40210.34	104.28	0.830	0.30	(0.28)	0.92	46798.3	11350.00
31	40598.32	108.97	0.813	0.30	(0.28)	0.93	49972.6	11130.00
32	40187.33	115.05	0.790	0.30	(0.28)	0.93	52899.1	12300.00
33	39920.40	118.94	0.776	0.30	(0.28)	0.93	54960.0	11620.00
34	39410.86	123.81	0.764	0.30	(0.28)	0.94	57159.7	12400.00
35	38361.79	133.33	0.743	0.30	(0.28)	0.94	60561.3	12201.00
36	37390.26	140.82	0.727	0.30	(0.28)	0.94	62454.3	12231.00
37	36385.06	148.31	0.711	0.30	(0.28)	0.94	64007.1	10400.00
38	34819.70	157.76	0.690	0.30	(0.28)	0.94	65453.5	12010.00
39	33773.22	163.15	0.679	0.30	(0.28)	0.94	65716.1	10210.00
40	33098.77	167.21	0.670	0.30	(0.28)	0.94	65862.9	12000.00
41	29402.70	193.57	0.629	0.30	(0.28)	0.94	66475.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124549.22 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	168.28	22.49	1.869	0.30(0.30)	0.99	131.3	50800.00

LONGEST FLOWPATH FROM NODE 50800.00 TO NODE 13700.00 = 5946.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20555.13	11.93	2.859	0.30(0.24)	0.80	3201.9	429.00
2	21760.91	13.40	2.642	0.30(0.24)	0.80	3666.8	425.00
3	22023.85	13.82	2.582	0.30(0.24)	0.80	3796.0	400.00
4	22661.39	15.26	2.386	0.30(0.24)	0.80	4248.4	300.00
5	24476.75	20.40	1.976	0.30(0.24)	0.80	5834.6	210.00
6	25038.26	22.49	1.869	0.30(0.24)	0.80	6458.2	50800.00
7	25041.50	22.50	1.868	0.30(0.24)	0.80	6461.9	410.00
8	25456.33	23.55	1.815	0.30(0.24)	0.80	6769.5	200.00
9	25648.19	24.11	1.786	0.30(0.24)	0.80	6933.5	230.00
10	25790.37	24.62	1.760	0.30(0.24)	0.80	7080.1	50700.00
11	25919.91	25.12	1.736	0.30(0.24)	0.80	7217.2	50500.00
12	25943.49	25.21	1.732	0.30(0.24)	0.80	7247.1	220.50
13	25963.42	25.29	1.729	0.30(0.24)	0.80	7272.5	50600.00
14	26918.92	28.93	1.576	0.30(0.24)	0.80	8464.4	110.00
15	27578.03	31.31	1.505	0.30(0.24)	0.80	9290.3	100.00
16	27760.56	32.03	1.490	0.30(0.24)	0.80	9534.5	110.00
17	27903.75	32.59	1.479	0.30(0.24)	0.80	9780.8	100.00
18	28730.75	35.65	1.417	0.30(0.24)	0.81	11128.3	130.00
19	29451.15	38.38	1.363	0.30(0.24)	0.81	12320.5	10100.00
20	29573.45	38.86	1.353	0.30(0.24)	0.81	12526.9	100.00
21	30435.49	42.25	1.296	0.30(0.24)	0.82	14024.3	800.00
22	31803.23	49.25	1.189	0.30(0.25)	0.84	17642.9	20100.00
23	32287.95	51.92	1.154	0.30(0.26)	0.85	18964.7	31100.00
24	32698.17	54.94	1.116	0.30(0.26)	0.86	20437.1	13600.00
25	34676.95	68.96	1.002	0.30(0.26)	0.88	27201.7	13100.00
26	35643.23	75.27	0.966	0.30(0.27)	0.89	29953.9	11801.00
27	37612.71	85.83	0.906	0.30(0.27)	0.90	35276.1	11530.00
28	38419.44	91.74	0.877	0.30(0.27)	0.91	39028.4	13510.00
29	39191.36	97.62	0.855	0.30(0.28)	0.92	42648.5	13010.00

30	39778.76	101.24	0.841	0.30	(0.28)	0.92	44987.6	13500.00
31	40267.45	104.28	0.830	0.30	(0.28)	0.92	46929.6	11350.00
32	40653.58	108.97	0.813	0.30	(0.28)	0.93	50103.9	11130.00
33	40240.18	115.05	0.790	0.30	(0.28)	0.93	53030.4	12300.00
34	39971.71	118.94	0.776	0.30	(0.28)	0.93	55091.3	11620.00
35	39460.86	123.81	0.764	0.30	(0.28)	0.94	57291.0	12400.00
36	38409.58	133.33	0.743	0.30	(0.28)	0.94	60692.6	12201.00
37	37436.32	140.82	0.727	0.30	(0.28)	0.94	62585.6	12231.00
38	36429.39	148.31	0.711	0.30	(0.28)	0.94	64138.4	10400.00
39	34861.84	157.76	0.690	0.30	(0.28)	0.94	65584.8	12010.00
40	33814.10	163.15	0.679	0.30	(0.28)	0.94	65847.4	10210.00
41	33138.71	167.21	0.670	0.30	(0.28)	0.94	65994.2	12000.00
42	29438.31	193.57	0.629	0.30	(0.28)	0.94	66607.1	10100.00
TOTAL AREA (ACRES) =								66607.1

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 40653.58 Tc(MIN.) = 108.971
 EFFECTIVE AREA(ACRES) = 50103.85 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA(ACRES) = 66607.1
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124549.22 FEET.

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 66607.1 TC(MIN.) = 108.97
 EFFECTIVE AREA(ACRES) = 50103.85 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.929
 PEAK FLOW RATE(CFS) = 40653.58

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20555.13	11.93	2.859	0.30(0.24)	0.80	3201.9	429.00
2	21760.91	13.40	2.642	0.30(0.24)	0.80	3666.8	425.00
3	22023.85	13.82	2.582	0.30(0.24)	0.80	3796.0	400.00
4	22661.39	15.26	2.386	0.30(0.24)	0.80	4248.4	300.00
5	24476.75	20.40	1.976	0.30(0.24)	0.80	5834.6	210.00
6	25038.26	22.49	1.869	0.30(0.24)	0.80	6458.2	50800.00
7	25041.50	22.50	1.868	0.30(0.24)	0.80	6461.9	410.00
8	25456.33	23.55	1.815	0.30(0.24)	0.80	6769.5	200.00
9	25648.19	24.11	1.786	0.30(0.24)	0.80	6933.5	230.00
10	25790.37	24.62	1.760	0.30(0.24)	0.80	7080.1	50700.00
11	25919.91	25.12	1.736	0.30(0.24)	0.80	7217.2	50500.00
12	25943.49	25.21	1.732	0.30(0.24)	0.80	7247.1	220.50
13	25963.42	25.29	1.729	0.30(0.24)	0.80	7272.5	50600.00
14	26918.92	28.93	1.576	0.30(0.24)	0.80	8464.4	110.00
15	27578.03	31.31	1.505	0.30(0.24)	0.80	9290.3	100.00
16	27760.56	32.03	1.490	0.30(0.24)	0.80	9534.5	110.00
17	27903.75	32.59	1.479	0.30(0.24)	0.80	9780.8	100.00
18	28730.75	35.65	1.417	0.30(0.24)	0.81	11128.3	130.00
19	29451.15	38.38	1.363	0.30(0.24)	0.81	12320.5	10100.00
20	29573.45	38.86	1.353	0.30(0.24)	0.81	12526.9	100.00
21	30435.49	42.25	1.296	0.30(0.24)	0.82	14024.3	800.00
22	31803.23	49.25	1.189	0.30(0.25)	0.84	17642.9	20100.00
23	32287.95	51.92	1.154	0.30(0.26)	0.85	18964.7	31100.00
24	32698.17	54.94	1.116	0.30(0.26)	0.86	20437.1	13600.00
25	34676.95	68.96	1.002	0.30(0.26)	0.88	27201.7	13100.00
26	35643.23	75.27	0.966	0.30(0.27)	0.89	29953.9	11801.00
27	37612.71	85.83	0.906	0.30(0.27)	0.90	35276.1	11530.00

28	38419.44	91.74	0.877	0.30 (0.27)	0.91	39028.4	13510.00
29	39191.36	97.62	0.855	0.30 (0.28)	0.92	42648.5	13010.00
30	39778.76	101.24	0.841	0.30 (0.28)	0.92	44987.6	13500.00
31	40267.45	104.28	0.830	0.30 (0.28)	0.92	46929.6	11350.00
32	40653.58	108.97	0.813	0.30 (0.28)	0.93	50103.9	11130.00
33	40240.18	115.05	0.790	0.30 (0.28)	0.93	53030.4	12300.00
34	39971.71	118.94	0.776	0.30 (0.28)	0.93	55091.3	11620.00
35	39460.86	123.81	0.764	0.30 (0.28)	0.94	57291.0	12400.00
36	38409.58	133.33	0.743	0.30 (0.28)	0.94	60692.6	12201.00
37	37436.32	140.82	0.727	0.30 (0.28)	0.94	62585.6	12231.00
38	36429.39	148.31	0.711	0.30 (0.28)	0.94	64138.4	10400.00
39	34861.84	157.76	0.690	0.30 (0.28)	0.94	65584.8	12010.00
40	33814.10	163.15	0.679	0.30 (0.28)	0.94	65847.4	10210.00
41	33138.71	167.21	0.670	0.30 (0.28)	0.94	65994.2	12000.00
42	29438.31	193.57	0.629	0.30 (0.28)	0.94	66607.1	10100.00

=====
=====

END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 136 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 25-YR EV OCT 2022 ROKAMOTO *

FILE NAME: RU25EV36.DAT
TIME/DATE OF STUDY: 10:34 10/06/2022

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 25.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 4.765
- 2) 10.00; 3.118
- 3) 15.00; 2.394
- 4) 20.00; 1.986
- 5) 25.00; 1.734
- 6) 30.00; 1.526
- 7) 40.00; 1.325
- 8) 50.00; 1.173
- 9) 60.00; 1.046
- 10) 90.00; 0.877
- 11) 120.00; 0.765
- 12) 180.00; 0.636
- 13) 360.00; 0.466
- 14) 1200.00; 0.203

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13600.00 TO NODE 13600.50 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 488.61
ELEVATION DATA: UPSTREAM(FEET) = 872.12 DOWNSTREAM(FEET) = 744.80

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 10.995
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.974
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "OPEN BRUSH"	-	3.39	0.30	1.000	65	11.00

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 8.16
TOTAL AREA(ACRES) = 3.39 PEAK FLOW RATE(CFS) = 8.16

FLOW PROCESS FROM NODE 13600.50 TO NODE 13601.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 744.80 DOWNSTREAM(FEET) = 707.32
CHANNEL LENGTH THRU SUBAREA(FEET) = 418.30 CHANNEL SLOPE = 0.0896
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.41
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.706
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.45	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 16.25
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.77
AVERAGE FLOW DEPTH(FEET) = 0.40 TRAVEL TIME(MIN.) = 1.85
Tc(MIN.) = 12.85
SUBAREA AREA(ACRES) = 7.45 SUBAREA RUNOFF(CFS) = 16.13
EFFECTIVE AREA(ACRES) = 10.84 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 10.8 PEAK FLOW RATE(CFS) = 23.47
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.49

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.49 FLOW VELOCITY(FEET/SEC.) = 4.33
LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13601.00 = 906.91 FEET.

FLOW PROCESS FROM NODE 13601.00 TO NODE 13602.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 707.32 DOWNSTREAM(FEET) = 657.12
CHANNEL LENGTH THRU SUBAREA(FEET) = 777.60 CHANNEL SLOPE = 0.0646
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.91
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.364

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.32	0.30	1.000	-
USER-DEFINED	-	4.70	0.30	1.000	-
USER-DEFINED	-	25.05	0.30	1.000	-
USER-DEFINED	-	0.45	0.30	1.000	-
USER-DEFINED	-	0.44	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 52.30

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.14

AVERAGE FLOW DEPTH(FEET) = 0.87 TRAVEL TIME(MIN.) = 2.52

Tc(MIN.) = 15.37

SUBAREA AREA(ACRES) = 30.96 SUBAREA RUNOFF(CFS) = 57.51
EFFECTIVE AREA(ACRES) = 41.80 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 41.8 PEAK FLOW RATE(CFS) = 77.65
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.09

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.09 FLOW VELOCITY(FEET/SEC.) = 5.82

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13602.00 = 1684.51 FEET.

FLOW PROCESS FROM NODE 13602.00 TO NODE 13603.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 657.12 DOWNSTREAM(FEET) = 584.58
CHANNEL LENGTH THRU SUBAREA(FEET) = 1186.54 CHANNEL SLOPE = 0.0611
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.28
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.102

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.03	0.30	1.000	-
USER-DEFINED	-	2.51	0.30	1.000	-

USER-DEFINED - 1.52 0.30 1.000 -
USER-DEFINED - 12.30 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 96.61

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.15

AVERAGE FLOW DEPTH(FEET) = 1.26 TRAVEL TIME(MIN.) = 3.22

Tc(MIN.) = 18.58

SUBAREA AREA(ACRES) = 23.36 SUBAREA RUNOFF(CFS) = 37.88

EFFECTIVE AREA(ACRES) = 65.16 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 65.2 PEAK FLOW RATE(CFS) = 105.65

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 1.32

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.32 FLOW VELOCITY(FEET/SEC.) = 6.32

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13603.00 = 2871.05 FEET.

FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 584.58 DOWNSTREAM(FEET) = 544.91
CHANNEL LENGTH THRU SUBAREA(FEET) = 860.98 CHANNEL SLOPE = 0.0461
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.56
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.937

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	10.22	0.30	1.000	-
USER-DEFINED	-	4.19	0.30	1.000	-
USER-DEFINED	-	0.07	0.30	1.000	-
USER-DEFINED	-	1.11	0.30	1.000	-
USER-DEFINED	-	5.56	0.30	1.000	-
USER-DEFINED	-	0.09	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 121.30

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.99

AVERAGE FLOW DEPTH(FEET) = 1.55 TRAVEL TIME(MIN.) = 2.39

Tc(MIN.) = 20.98

SUBAREA AREA(ACRES) = 21.24 SUBAREA RUNOFF(CFS) = 31.29

EFFECTIVE AREA(ACRES) = 86.40 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 86.4 PEAK FLOW RATE(CFS) = 127.28

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 1.59

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.59 FLOW VELOCITY(FEET/SEC.) = 6.07

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13620.00 = 3732.03 FEET.

```

*****
FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 10
-----
>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<
=====
*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13522.00 IS CODE = 15.1
-----
>>>>DEFINE MEMORY BANK # 2 <<<<<
=====
PEAK FLOWRATE TABLE FILE NAME: S35X25.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:
STREAM      Q      Tc      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR)    (ACRES)  NODE
  1      1006.57  54.62  0.30( 0.28) 0.95    1513.9  13510.00
  2       918.88  63.50  0.30( 0.28) 0.94    1579.8  13500.00
TOTAL AREA(ACRES) =      1579.8

*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13522.00 IS CODE = 14.0
-----
>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<
=====
MAIN-STREAM MEMORY DEFINED AS FOLLOWS:
STREAM      Q      Tc      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR)    (ACRES)  NODE
  1      1006.57  54.62  0.30( 0.28) 0.95    1513.9  13510.00
  2       918.88  63.50  0.30( 0.28) 0.94    1579.8  13500.00
TOTAL AREA(ACRES) =      1579.8

*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13620.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 632.19 DOWNSTREAM(FEET) = 544.91
CHANNEL LENGTH THRU SUBAREA(FEET) = 2062.96 CHANNEL SLOPE = 0.0423
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.32
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.077
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp      Ap      SCS
LAND USE              GROUP  (ACRES)  (INCH/HR)  (DECIMAL)  CN
USER-DEFINED          -      17.68    0.30    1.000    -
USER-DEFINED          -      2.36    0.30    1.000    -
USER-DEFINED          -      0.60    0.30    1.000    -
USER-DEFINED          -      0.22    0.30    1.000    -
USER-DEFINED          -      2.22    0.30    1.000    -
USER-DEFINED          -      3.42    0.30    1.000    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1015.85
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.82

```

```

AVERAGE FLOW DEPTH(FEET) = 2.32 TRAVEL TIME(MIN.) = 2.91
Tc(MIN.) = 57.52
SUBAREA AREA(ACRES) = 26.50 SUBAREA RUNOFF(CFS) = 18.55
EFFECTIVE AREA(ACRES) = 1540.42 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
TOTAL AREA(ACRES) = 1606.3 PEAK FLOW RATE(CFS) = 1099.65
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.43

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 2.43 FLOW VELOCITY(FEET/SEC.) = 12.13
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

*****
FLOW PROCESS FROM NODE 13620.00 TO NODE 13620.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====
MAINLINE Tc(MIN.) = 57.52
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.077
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp      Ap      SCS
LAND USE              GROUP  (ACRES)  (INCH/HR)  (DECIMAL)  CN
NATURAL FAIR COVER
"WOODLAND,GRASS"      B      1.44    0.30    1.000    65
NATURAL FAIR COVER
"WOODLAND,GRASS"      B      0.01    0.30    1.000    65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 1.45 SUBAREA RUNOFF(CFS) = 1.01
EFFECTIVE AREA(ACRES) = 1541.87 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
TOTAL AREA(ACRES) = 1607.8 PEAK FLOW RATE(CFS) = 1100.66

*****
FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 11
-----
>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<
=====
** MAIN STREAM CONFLUENCE DATA **
STREAM      Q      Tc      Intensity  Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR)  (INCH/HR)  (ACRES)  NODE
  1      1100.66  57.52    1.077  0.30( 0.28) 0.95    1541.9  13510.00
  2      1050.24  66.50    1.009  0.30( 0.28) 0.95    1607.8  13500.00
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **
STREAM      Q      Tc      Intensity  Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR)  (INCH/HR)  (ACRES)  NODE
  1      127.28  20.98    1.937  0.30( 0.30) 1.00     86.4   13600.00
LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13620.00 = 3732.03 FEET.

** PEAK FLOW RATE TABLE **
STREAM      Q      Tc      Intensity  Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR)  (INCH/HR)  (ACRES)  NODE
  1      963.51  20.98    1.937  0.30( 0.29) 0.95    648.7  13600.00

```

2 1161.12 57.52 1.077 0.30(0.29) 0.95 1628.3 13510.00
 3 1105.40 66.50 1.009 0.30(0.28) 0.95 1694.2 13500.00
 TOTAL AREA (ACRES) = 1694.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 1161.12 Tc (MIN.) = 57.525
 EFFECTIVE AREA (ACRES) = 1628.27 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
 TOTAL AREA (ACRES) = 1694.2
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

 FLOW PROCESS FROM NODE 13620.00 TO NODE 13640.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 544.91 DOWNSTREAM (FEET) = 489.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1384.37 CHANNEL SLOPE = 0.0404
 GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT (FEET) = 2.57
 * 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.053

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.39	0.30	1.000	-
USER-DEFINED	-	16.30	0.30	1.000	-
USER-DEFINED	-	4.08	0.30	1.000	-
USER-DEFINED	-	12.36	0.30	1.000	-
USER-DEFINED	-	11.23	0.30	1.000	-
USER-DEFINED	-	5.16	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 1179.61
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 12.19
 AVERAGE FLOW DEPTH (FEET) = 2.57 TRAVEL TIME (MIN.) = 1.89
 Tc (MIN.) = 59.42

SUBAREA AREA (ACRES) = 54.52 SUBAREA RUNOFF (CFS) = 36.97
 EFFECTIVE AREA (ACRES) = 1682.79 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
 TOTAL AREA (ACRES) = 1748.7 PEAK FLOW RATE (CFS) = 1162.87
 GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT (FEET) = 2.54

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 2.54 FLOW VELOCITY (FEET/SEC.) = 12.15
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

 FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 59.42
 * 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.053
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	53.93	0.30	1.000	-
USER-DEFINED	-	0.45	0.30	1.000	-
USER-DEFINED	-	3.98	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 58.36 SUBAREA RUNOFF (CFS) = 39.58
 EFFECTIVE AREA (ACRES) = 1741.15 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
 TOTAL AREA (ACRES) = 1807.1 PEAK FLOW RATE (CFS) = 1202.45

 FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P201XX25.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap (DECIMAL)	Ae (ACRES)	HEADWATER NODE
1	210.74	17.33	0.30 (0.26)	0.85	133.8	20100.00
TOTAL AREA (ACRES) =		133.8				

 FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap (DECIMAL)	Ae (ACRES)	HEADWATER NODE
1	1060.92	22.97	1.836	0.30 (0.29)	0.96	761.6	13600.00
2	1202.45	59.42	1.053	0.30 (0.29)	0.95	1741.1	13510.00
3	1159.89	68.42	0.999	0.30 (0.29)	0.95	1807.1	13500.00
LONGEST FLOWPATH FROM NODE		13500.00 TO NODE 13640.00 = 22062.09 FEET.					

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap (DECIMAL)	Ae (ACRES)	HEADWATER NODE
1	210.74	17.33	2.204	0.30 (0.26)	0.85	133.8	20100.00
LONGEST FLOWPATH FROM NODE		20100.00 TO NODE 13640.00 = 5247.00 FEET.					

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap (DECIMAL)	Ae (ACRES)	HEADWATER NODE
1	1201.19	17.33	2.204	0.30 (0.28)	0.94	708.3	20100.00
2	1231.87	22.97	1.836	0.30 (0.28)	0.95	895.4	13600.00
3	1288.70	59.42	1.053	0.30 (0.28)	0.95	1874.9	13510.00
4	1240.21	68.42	0.999	0.30 (0.28)	0.94	1940.9	13500.00
TOTAL AREA (ACRES) =		1940.9					

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 1288.70 Tc (MIN.) = 59.417
 EFFECTIVE AREA (ACRES) = 1874.95 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
 TOTAL AREA (ACRES) = 1940.9

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

FLOW PROCESS FROM NODE 13640.00 TO NODE 13641.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 489.00 DOWNSTREAM(FEET) = 436.89
CHANNEL LENGTH THRU SUBAREA(FEET) = 2994.52 CHANNEL SLOPE = 0.0174
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 3.44

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.020

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include USER-DEFINED entries with various area and loss rate values.

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1310.59

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.46

AVERAGE FLOW DEPTH(FEET) = 3.44 TRAVEL TIME(MIN.) = 5.28

Tc(MIN.) = 64.70

SUBAREA AREA(ACRES) = 67.58 SUBAREA RUNOFF(CFS) = 43.77

EFFECTIVE AREA(ACRES) = 1942.53 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95

TOTAL AREA(ACRES) = 2008.4 PEAK FLOW RATE(CFS) = 1288.70

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 3.41

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 3.41 FLOW VELOCITY(FEET/SEC.) = 9.40

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13641.00 = 25056.61 FEET.

FLOW PROCESS FROM NODE 13641.00 TO NODE 13641.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 64.70

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.020

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include USER-DEFINED entries with various area and loss rate values.

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 104.70 SUBAREA RUNOFF(CFS) = 67.81

EFFECTIVE AREA(ACRES) = 2047.23 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95

TOTAL AREA(ACRES) = 2113.1 PEAK FLOW RATE(CFS) = 1352.90

FLOW PROCESS FROM NODE 13641.00 TO NODE 13641.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 64.70

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.020

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include USER-DEFINED entries with various area and loss rate values.

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 8.03 SUBAREA RUNOFF(CFS) = 5.20

EFFECTIVE AREA(ACRES) = 2055.26 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95

TOTAL AREA(ACRES) = 2121.2 PEAK FLOW RATE(CFS) = 1358.10

FLOW PROCESS FROM NODE 13641.00 TO NODE 13642.00 IS CODE = 56

ELEVATION DATA: UPSTREAM(FEET) = 436.89 DOWNSTREAM(FEET) = 394.80

CHANNEL LENGTH THRU SUBAREA(FEET) = 2814.16 CHANNEL SLOPE = 0.0150

GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 3.76

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.991

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include USER-DEFINED entries with various area and loss rate values.

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1426.27

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.20

AVERAGE FLOW DEPTH(FEET) = 3.76 TRAVEL TIME(MIN.) = 5.10

Tc(MIN.) = 69.79

SUBAREA AREA(ACRES) = 219.25 SUBAREA RUNOFF(CFS) = 136.33

EFFECTIVE AREA(ACRES) = 2274.51 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96

TOTAL AREA(ACRES) = 2340.4 PEAK FLOW RATE(CFS) = 1441.31

GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 3.78

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 3.78 FLOW VELOCITY(FEET/SEC.) = 9.23
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13642.00 = 27870.77 FEET.

FLOW PROCESS FROM NODE 13642.00 TO NODE 13642.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 69.79
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.991
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 9.95 0.30 1.000 -
USER-DEFINED - 10.02 0.30 1.000 -
USER-DEFINED - 4.45 0.30 1.000 -
USER-DEFINED - 179.37 0.30 1.000 -
USER-DEFINED - 11.47 0.30 1.000 -
USER-DEFINED - 0.17 0.30 0.850 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 215.43 SUBAREA RUNOFF(CFS) = 133.96
EFFECTIVE AREA(ACRES) = 2489.94 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA(ACRES) = 2555.9 PEAK FLOW RATE(CFS) = 1575.27

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1578.90	27.83	1.616	0.30(0.29)	0.97	1323.3	20100.00
2	1585.73	33.44	1.457	0.30(0.29)	0.97	1510.4	13600.00
3	1575.27	69.79	0.991	0.30(0.29)	0.96	2489.9	13510.00
4	1499.78	78.93	0.939	0.30(0.29)	0.96	2555.9	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 1585.73 Tc(MIN.) = 33.44
AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.97 EFFECTIVE AREA(ACRES) = 1510.36

FLOW PROCESS FROM NODE 13642.00 TO NODE 13642.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 33.44
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.457
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.03 0.30 0.850 -
USER-DEFINED - 5.14 0.30 1.000 -
USER-DEFINED - 11.22 0.30 1.000 -
USER-DEFINED - 0.33 0.30 1.000 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 16.72 SUBAREA RUNOFF(CFS) = 17.41
EFFECTIVE AREA(ACRES) = 1527.08 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 2572.6 PEAK FLOW RATE(CFS) = 1603.13

FLOW PROCESS FROM NODE 13642.00 TO NODE 13643.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 394.80 DOWNSTREAM(FEET) = 342.39
CHANNEL LENGTH THRU SUBAREA(FEET) = 2913.57 CHANNEL SLOPE = 0.0180
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 3.90
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.362
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.22 0.30 1.000 -
USER-DEFINED - 2.17 0.30 1.000 -
USER-DEFINED - 9.19 0.30 1.000 -
USER-DEFINED - 67.57 0.30 1.000 -
USER-DEFINED - 35.19 0.30 1.000 -
USER-DEFINED - 30.67 0.30 1.000 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1672.45
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.30
AVERAGE FLOW DEPTH(FEET) = 3.90 TRAVEL TIME(MIN.) = 4.72
Tc(MIN.) = 38.16
SUBAREA AREA(ACRES) = 145.01 SUBAREA RUNOFF(CFS) = 138.61
EFFECTIVE AREA(ACRES) = 1672.09 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 2717.6 PEAK FLOW RATE(CFS) = 1611.48
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 3.82

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 3.82 FLOW VELOCITY(FEET/SEC.) = 10.18
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13643.00 = 30784.34 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1598.71	32.55	1.475	0.30(0.29)	0.97	1485.0	20100.00
2	1611.48	38.16	1.362	0.30(0.29)	0.97	1672.1	13600.00
3	1611.93	74.55	0.964	0.30(0.29)	0.96	2651.7	13510.00
4	1526.38	83.75	0.912	0.30(0.29)	0.96	2717.6	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 1611.93 Tc(MIN.) = 74.55
AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.96 EFFECTIVE AREA(ACRES) = 2651.67

FLOW PROCESS FROM NODE 13643.00 TO NODE 13643.00 IS CODE = 81

=====
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====

MAINLINE Tc(MIN.) = 74.55
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.964
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.89 0.30 1.000 -
USER-DEFINED - 20.65 0.30 1.000 -
USER-DEFINED - 2.69 0.30 1.000 -
USER-DEFINED - 8.45 0.30 1.000 -
USER-DEFINED - 96.93 0.30 1.000 -
USER-DEFINED - 13.19 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 142.80 SUBAREA RUNOFF(CFS) = 85.35
EFFECTIVE AREA(ACRES) = 2794.47 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA(ACRES) = 2860.4 PEAK FLOW RATE(CFS) = 1697.29

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1732.48	32.55	1.475	0.30(0.29)	0.97	1627.8	20100.00
2	1747.98	38.16	1.362	0.30(0.29)	0.97	1814.9	13600.00
3	1697.29	74.55	0.964	0.30(0.29)	0.96	2794.5	13510.00
4	1605.07	83.75	0.912	0.30(0.29)	0.96	2860.4	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 1747.98 Tc(MIN.) = 38.16
AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.97 EFFECTIVE AREA(ACRES) = 1814.89

FLOW PROCESS FROM NODE 13643.00 TO NODE 13643.00 IS CODE = 81

=====
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====

MAINLINE Tc(MIN.) = 38.16
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.362
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 42.54 0.30 1.000 -
USER-DEFINED - 16.96 0.30 1.000 -
USER-DEFINED - 80.60 0.30 1.000 -
USER-DEFINED - 1.56 0.30 1.000 -
USER-DEFINED - 2.00 0.30 1.000 -
USER-DEFINED - 3.11 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 146.77 SUBAREA RUNOFF(CFS) = 140.29
EFFECTIVE AREA(ACRES) = 1961.66 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
TOTAL AREA(ACRES) = 3007.2 PEAK FLOW RATE(CFS) = 1888.27

FLOW PROCESS FROM NODE 13643.00 TO NODE 13660.00 IS CODE = 56

=====
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
=====

>>>>TRAVELTIME THRU SUBAREA<<<<
=====

ELEVATION DATA: UPSTREAM(FEET) = 342.39 DOWNSTREAM(FEET) = 300.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1591.23 CHANNEL SLOPE = 0.0266
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 3.77
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.320
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.89 0.30 1.000 -
USER-DEFINED - 23.73 0.30 1.000 -
USER-DEFINED - 0.27 0.30 1.000 -
USER-DEFINED - 19.87 0.30 1.000 -
USER-DEFINED - 6.40 0.30 1.000 -
USER-DEFINED - 3.14 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1913.20
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.30
AVERAGE FLOW DEPTH(FEET) = 3.77 TRAVEL TIME(MIN.) = 2.16
Tc(MIN.) = 40.32
SUBAREA AREA(ACRES) = 54.30 SUBAREA RUNOFF(CFS) = 49.86
EFFECTIVE AREA(ACRES) = 2015.96 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
TOTAL AREA(ACRES) = 3061.5 PEAK FLOW RATE(CFS) = 1888.27
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 3.74

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 3.74 FLOW VELOCITY(FEET/SEC.) = 12.24
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 32375.57 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1887.68	34.70	1.432	0.30(0.29)	0.98	1828.9	20100.00
2	1888.27	40.32	1.320	0.30(0.29)	0.98	2016.0	13600.00
3	1785.01	76.74	0.952	0.30(0.29)	0.97	2995.5	13510.00
4	1685.95	85.99	0.900	0.30(0.29)	0.96	3061.5	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 1888.27 Tc(MIN.) = 40.32
AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.98 EFFECTIVE AREA(ACRES) = 2015.96

FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

=====
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====

MAINLINE Tc(MIN.) = 40.32
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.320
SUBAREA LOSS RATE DATA(AMC II):

```

DEVELOPMENT TYPE/   SCS SOIL  AREA      Fp      Ap      SCS
LAND USE            GROUP  (ACRES)  (INCH/HR)  (DECIMAL)  CN
USER-DEFINED        -         0.67     0.30     1.000     -
USER-DEFINED        -         9.52     0.30     1.000     -
USER-DEFINED        -         0.71     0.30     1.000     -
USER-DEFINED        -         0.22     0.30     1.000     -
USER-DEFINED        -        39.42     0.30     1.000     -
USER-DEFINED        -         0.62     0.30     1.000     -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 51.16      SUBAREA RUNOFF(CFS) = 46.98
EFFECTIVE AREA(ACRES) = 2067.12  AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30  AREA-AVERAGED Ap = 0.98
TOTAL AREA(ACRES) = 3112.6      PEAK FLOW RATE(CFS) = 1911.33

```

```

** PEAK FLOW RATE TABLE **
STREAM      Q      Tc      Intensity  Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)  (MIN.)  (INCH/HR)  (INCH/HR)  (DECIMAL)  (ACRES)  NODE
1           1925.95  34.70   1.432     0.30( 0.29) 0.98     1880.1   20100.00
2           1911.33  40.32   1.320     0.30( 0.29) 0.98     2067.1   13600.00
3           1814.12  76.74   0.952     0.30( 0.29) 0.97     3046.7   13510.00
4           1708.80  85.99   0.900     0.30( 0.29) 0.97     3112.6   13500.00
NEW PEAK FLOW DATA ARE:
PEAK FLOW RATE(CFS) = 1925.95  Tc(MIN.) = 34.70
AREA-AVERAGED Fm(INCH/HR) = 0.29  AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.98  EFFECTIVE AREA(ACRES) = 1880.05

```

```

*****
FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 34.70
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.432
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL  AREA      Fp      Ap      SCS
LAND USE            GROUP  (ACRES)  (INCH/HR)  (DECIMAL)  CN
USER-DEFINED        -         0.11     0.30     1.000     -
USER-DEFINED        -         0.77     0.30     1.000     -
USER-DEFINED        -         0.22     0.30     1.000     -
USER-DEFINED        -         2.69     0.30     1.000     -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 3.79      SUBAREA RUNOFF(CFS) = 3.86
EFFECTIVE AREA(ACRES) = 1883.84  AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30  AREA-AVERAGED Ap = 0.98
TOTAL AREA(ACRES) = 3116.4      PEAK FLOW RATE(CFS) = 1929.81

```

```

*****
FLOW PROCESS FROM NODE 13643.00 TO NODE 13660.00 IS CODE = 12
-----

```

```

>>>>CLEAR MEMORY BANK # 1 <<<<
=====

```

```

*****
FLOW PROCESS FROM NODE 13659.00 TO NODE 13659.00 IS CODE = 15.1
-----

```

```

>>>>DEFINE MEMORY BANK # 1 <<<<

```

```

=====
PEAK FLOWRATE TABLE FILE NAME: 2P25EVAA.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:
STREAM      Q      Tc      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)  (MIN.)  (INCH/HR)  (DECIMAL)  (ACRES)  NODE
1           479.23   14.36   0.30( 0.11) 0.36     173.1   110.00
2           481.39   16.87   0.30( 0.11) 0.37     203.9   100.00
3           473.65   18.15   0.30( 0.11) 0.38     213.8   100.00
4           419.54   21.27   0.30( 0.12) 0.40     221.1   130.00
TOTAL AREA(ACRES) = 221.1

```

```

*****
FLOW PROCESS FROM NODE 13659.00 TO NODE 13660.00 IS CODE = 31
-----

```

```

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<
=====

```

```

ELEVATION DATA: UPSTREAM(FEET) = 338.00  DOWNSTREAM(FEET) = 300.00
FLOW LENGTH(FEET) = 881.07  MANNING'S N = 0.013
DEPTH OF FLOW IN 102.0 INCH PIPE IS 76.6 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 42.20
ESTIMATED PIPE DIAMETER(INCH) = 102.00  NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 1929.81
PIPE TRAVEL TIME(MIN.) = 0.35  Tc(MIN.) = 35.05
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 11
-----

```

```

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<
=====

```

```

** MAIN STREAM CONFLUENCE DATA **
STREAM      Q      Tc      Intensity  Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)  (MIN.)  (INCH/HR)  (INCH/HR)  (DECIMAL)  (ACRES)  NODE
1           1929.81  35.05   1.425     0.30( 0.29) 0.98     1883.8   20100.00
2           1914.81  40.66   1.315     0.30( 0.29) 0.98     2070.9   13600.00
3           1816.34  77.09   0.950     0.30( 0.29) 0.97     3050.5   13510.00
4           1710.85  86.35   0.898     0.30( 0.29) 0.97     3116.4   13500.00
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

```

```

** MEMORY BANK # 1 CONFLUENCE DATA **
STREAM      Q      Tc      Intensity  Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)  (MIN.)  (INCH/HR)  (INCH/HR)  (DECIMAL)  (ACRES)  NODE
1           479.23   14.36   2.487     0.30( 0.11) 0.36     173.1   110.00
2           481.39   16.87   2.242     0.30( 0.11) 0.37     203.9   100.00
3           473.65   18.15   2.137     0.30( 0.11) 0.38     213.8   100.00
4           419.54   21.27   1.922     0.30( 0.12) 0.40     221.1   130.00
LONGEST FLOWPATH FROM NODE 130.00 TO NODE 13660.00 = 6327.50 FEET.

```

```

** PEAK FLOW RATE TABLE **
STREAM      Q      Tc      Intensity  Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)  (MIN.)  (INCH/HR)  (INCH/HR)  (DECIMAL)  (ACRES)  NODE
1           2012.29  14.36   2.487     0.30( 0.26) 0.87     945.0   110.00
2           2080.98  16.87   2.242     0.30( 0.26) 0.87     1110.5   100.00
3           2102.39  18.15   2.137     0.30( 0.26) 0.87     1189.4   100.00
4           2105.75  21.27   1.922     0.30( 0.27) 0.88     1364.4   130.00
5           2233.52  35.05   1.425     0.30( 0.28) 0.92     2104.9   20100.00

```

6 2193.00 40.66 1.315 0.30(0.28) 0.92 2292.0 13600.00
 7 2009.48 77.09 0.950 0.30(0.28) 0.93 3271.6 13510.00
 8 1891.84 86.35 0.898 0.30(0.28) 0.93 3337.5 13500.00
 TOTAL AREA(ACRES) = 3337.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 2233.52 Tc(MIN.) = 35.049
 EFFECTIVE AREA(ACRES) = 2104.94 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.87
 TOTAL AREA(ACRES) = 3337.5
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

 FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 35.05
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.425
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "FALLOW"	B	1.11	0.30	1.000	86
AGRICULTURAL POOR COVER "FALLOW"	B	0.44	0.30	1.000	86
NATURAL FAIR COVER "GRASS"	B	1.49	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	1.70	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	1.09	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	18.57	0.30	1.000	66

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 24.40 SUBAREA RUNOFF(CFS) = 24.69
 EFFECTIVE AREA(ACRES) = 2129.34 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA(ACRES) = 3361.9 PEAK FLOW RATE(CFS) = 2233.52
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 35.05
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.425
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL FAIR COVER "ORCHARDS"	B	12.39	0.30	1.000	65
AGRICULTURAL FAIR COVER "ORCHARDS"	B	2.30	0.30	1.000	65
AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	5.19	0.30	1.000	79

AGRICULTURAL POOR COVER
 "ROW CROPS,STRAIGHT ROW" B 28.71 0.30 1.000 81
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 0.17 0.30 1.000 65
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 48.76 SUBAREA RUNOFF(CFS) = 49.35
 EFFECTIVE AREA(ACRES) = 2178.10 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA(ACRES) = 3410.7 PEAK FLOW RATE(CFS) = 2251.51

 FLOW PROCESS FROM NODE 13660.00 TO NODE 13680.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 300.00 DOWNSTREAM(FEET) = 288.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 933.89 CHANNEL SLOPE = 0.0128
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 5.02
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.393
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	9.23	0.30	1.000	-
USER-DEFINED	-	0.54	0.30	1.000	-
USER-DEFINED	-	5.66	0.30	1.000	-
USER-DEFINED	-	3.66	0.30	1.000	-
USER-DEFINED	-	0.67	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2261.34
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.00
 AVERAGE FLOW DEPTH(FEET) = 5.02 TRAVEL TIME(MIN.) = 1.56
 Tc(MIN.) = 36.60
 SUBAREA AREA(ACRES) = 19.98 SUBAREA RUNOFF(CFS) = 19.66
 EFFECTIVE AREA(ACRES) = 2198.08 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA(ACRES) = 3430.6 PEAK FLOW RATE(CFS) = 2251.51
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 5.01

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 5.01 FLOW VELOCITY(FEET/SEC.) = 9.99
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13680.00 = 34190.53 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2038.00	15.96	2.316	0.30(0.26)	0.88	1038.1	110.00
2	2108.28	18.45	2.112	0.30(0.26)	0.88	1203.7	100.00
3	2128.98	19.73	2.008	0.30(0.26)	0.88	1282.5	100.00
4	2141.13	22.85	1.842	0.30(0.27)	0.89	1457.6	130.00

5 2251.51 36.60 1.393 0.30(0.28) 0.92 2198.1 20100.00
6 2209.48 42.23 1.291 0.30(0.28) 0.92 2385.1 13600.00
7 2018.73 78.70 0.941 0.30(0.28) 0.93 3364.7 13510.00
8 1899.14 87.98 0.888 0.30(0.28) 0.93 3430.6 13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2251.51 Tc(MIN.) = 36.60
AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.92 EFFECTIVE AREA(ACRES) = 2198.08

FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 36.60

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.393

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.56	0.30	1.000	-
USER-DEFINED	-	9.40	0.30	1.000	-
USER-DEFINED	-	2.76	0.30	1.000	-
USER-DEFINED	-	17.38	0.30	1.000	-
USER-DEFINED	-	2.46	0.30	1.000	-
USER-DEFINED	-	5.56	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 39.12 SUBAREA RUNOFF(CFS) = 38.49

EFFECTIVE AREA(ACRES) = 2237.20 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92

TOTAL AREA(ACRES) = 3469.8 PEAK FLOW RATE(CFS) = 2251.51

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 36.60

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.393

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.65	0.30	1.000	-
USER-DEFINED	-	1.70	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 2.35 SUBAREA RUNOFF(CFS) = 2.31

EFFECTIVE AREA(ACRES) = 2239.55 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92

TOTAL AREA(ACRES) = 3472.1 PEAK FLOW RATE(CFS) = 2251.51

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13660.00 TO NODE 13680.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 36.60

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.393

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.29	0.30	1.000	-
USER-DEFINED	-	31.25	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	6.26	0.30	1.000	-
USER-DEFINED	-	0.07	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 43.31 SUBAREA RUNOFF(CFS) = 42.62

EFFECTIVE AREA(ACRES) = 2282.86 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92

TOTAL AREA(ACRES) = 3515.4 PEAK FLOW RATE(CFS) = 2293.29

FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 36.60

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.393

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	2.47	0.30	0.850	-
USER-DEFINED	-	3.06	0.30	0.850	-
USER-DEFINED	-	17.76	0.30	0.500	-
USER-DEFINED	-	7.31	0.30	0.500	-
USER-DEFINED	-	0.34	0.30	1.000	-
USER-DEFINED	-	8.22	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.659

SUBAREA AREA(ACRES) = 39.16 SUBAREA RUNOFF(CFS) = 42.14

EFFECTIVE AREA(ACRES) = 2322.02 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92

TOTAL AREA(ACRES) = 3554.6 PEAK FLOW RATE(CFS) = 2335.43

FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 36.60

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.393

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.53	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 0.53 SUBAREA RUNOFF(CFS) = 0.52
 EFFECTIVE AREA(ACRES) = 2322.55 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA(ACRES) = 3555.1 PEAK FLOW RATE(CFS) = 2335.95

 FLOW PROCESS FROM NODE 13680.00 TO NODE 13682.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 288.00 DOWNSTREAM(FEET) = 242.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2860.77 CHANNEL SLOPE = 0.0161
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 4.82
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.310

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	5.28	0.30	1.000	-
USER-DEFINED	-	0.52	0.30	1.000	-
USER-DEFINED	-	3.61	0.30	1.000	-
USER-DEFINED	-	0.67	0.30	1.000	-
USER-DEFINED	-	1.37	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2341.25
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.93
 AVERAGE FLOW DEPTH(FEET) = 4.82 TRAVEL TIME(MIN.) = 4.36
 Tc(MIN.) = 40.97
 SUBAREA AREA(ACRES) = 11.67 SUBAREA RUNOFF(CFS) = 10.61
 EFFECTIVE AREA(ACRES) = 2334.22 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA(ACRES) = 3566.8 PEAK FLOW RATE(CFS) = 2335.95

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 4.81
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 4.81 FLOW VELOCITY(FEET/SEC.) = 10.93
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13682.00 = 37051.30 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2146.94	20.42	1.965	0.30(0.26)	0.88	1174.3	110.00
2	2209.70	22.88	1.841	0.30(0.26)	0.88	1339.8	100.00
3	2208.11	24.16	1.776	0.30(0.26)	0.88	1418.7	100.00
4	2242.46	27.26	1.640	0.30(0.27)	0.89	1593.7	130.00
5	2335.95	40.97	1.310	0.30(0.28)	0.92	2334.2	20100.00
6	2291.36	46.61	1.225	0.30(0.28)	0.92	2521.3	13600.00
7	2078.40	83.21	0.915	0.30(0.28)	0.93	3500.9	13510.00
8	1950.98	92.58	0.867	0.30(0.28)	0.93	3566.8	13500.00

NEW PEAK FLOW DATA ARE:
 PEAK FLOW RATE(CFS) = 2335.95 Tc(MIN.) = 40.97
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.92 EFFECTIVE AREA(ACRES) = 2334.22

 FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 40.97
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.310
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	6.90	0.30	1.000	-
USER-DEFINED	-	23.04	0.30	1.000	-
USER-DEFINED	-	1.18	0.30	1.000	-
USER-DEFINED	-	1.56	0.30	1.000	-
USER-DEFINED	-	53.20	0.30	1.000	-
USER-DEFINED	-	2.08	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 87.96 SUBAREA RUNOFF(CFS) = 79.99
 EFFECTIVE AREA(ACRES) = 2422.18 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA(ACRES) = 3654.7 PEAK FLOW RATE(CFS) = 2335.95
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 40.97
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.310
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.01	0.30	1.000	-
USER-DEFINED	-	0.18	0.30	1.000	-
USER-DEFINED	-	0.38	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	7.73	0.30	1.000	-
USER-DEFINED	-	4.37	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 12.89 SUBAREA RUNOFF(CFS) = 11.72
 EFFECTIVE AREA(ACRES) = 2435.07 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA(ACRES) = 3667.6 PEAK FLOW RATE(CFS) = 2335.95
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 40.97
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.310
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "FALLOW"	B	2.57	0.30	1.000	86
AGRICULTURAL POOR COVER "FALLOW"	B	1.97	0.30	1.000	86
NATURAL FAIR COVER "GRASS"	B	1.00	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	2.98	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	2.39	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	1.67	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 12.58 SUBAREA RUNOFF(CFS) = 11.44
 EFFECTIVE AREA(ACRES) = 2447.65 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA(ACRES) = 3680.2 PEAK FLOW RATE(CFS) = 2335.95
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 40.97
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.310
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	0.44	0.30	1.000	66
PUBLIC PARK	B	2.65	0.30	0.850	56
PUBLIC PARK	B	1.16	0.30	0.850	56
RESIDENTIAL "5-7 DWELLINGS/ACRE"	B	0.47	0.30	0.500	56
RESIDENTIAL "5-7 DWELLINGS/ACRE"	B	0.25	0.30	0.500	56
AGRICULTURAL POOR COVER "ROW CROPS,STRAIGHT ROW"	B	20.24	0.30	1.000	81

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.963
 SUBAREA AREA(ACRES) = 25.21 SUBAREA RUNOFF(CFS) = 23.17
 EFFECTIVE AREA(ACRES) = 2472.86 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA(ACRES) = 3705.4 PEAK FLOW RATE(CFS) = 2335.95
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 40.97
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.310
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.08	0.30	1.000	-
USER-DEFINED	-	6.75	0.30	1.000	-
USER-DEFINED	-	0.02	0.30	1.000	-
USER-DEFINED	-	0.93	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 14.78 SUBAREA RUNOFF(CFS) = 13.44
 EFFECTIVE AREA(ACRES) = 2487.64 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA(ACRES) = 3720.2 PEAK FLOW RATE(CFS) = 2335.95
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13682.00 TO NODE 13683.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 242.00 DOWNSTREAM(FEET) = 208.53
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2526.22 CHANNEL SLOPE = 0.0132
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 5.09
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.248
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.49	0.30	1.000	-
USER-DEFINED	-	13.31	0.30	1.000	-
USER-DEFINED	-	0.87	0.30	1.000	-
USER-DEFINED	-	20.26	0.30	1.000	-
USER-DEFINED	-	1.21	0.30	1.000	-
USER-DEFINED	-	0.05	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2354.80
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.24
 AVERAGE FLOW DEPTH(FEET) = 5.08 TRAVEL TIME(MIN.) = 4.11
 Tc(MIN.) = 45.08
 SUBAREA AREA(ACRES) = 44.19 SUBAREA RUNOFF(CFS) = 37.70
 EFFECTIVE AREA(ACRES) = 2531.83 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 3764.4 PEAK FLOW RATE(CFS) = 2335.95
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 5.06

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 5.06 FLOW VELOCITY(FEET/SEC.) = 10.21
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13683.00 = 39577.52 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2146.94	24.64	1.752	0.30(0.27)	0.90	1371.9	110.00
2	2209.70	27.06	1.648	0.30(0.27)	0.89	1537.4	100.00
3	2208.11	28.34	1.595	0.30(0.27)	0.90	1616.3	100.00
4	2242.46	31.42	1.497	0.30(0.27)	0.90	1791.3	130.00
5	2335.95	45.08	1.248	0.30(0.28)	0.93	2531.8	20100.00
6	2291.36	50.75	1.164	0.30(0.28)	0.93	2718.9	13600.00
7	2090.26	87.46	0.891	0.30(0.28)	0.93	3698.5	13510.00
8	1968.40	96.91	0.851	0.30(0.28)	0.93	3764.4	13500.00

NEW PEAK FLOW DATA ARE:
 PEAK FLOW RATE(CFS) = 2335.95 Tc(MIN.) = 45.08
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 2531.83

 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
 =====

MAINLINE Tc(MIN.) = 45.08
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.248
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 12.56 0.30 1.000 -
 USER-DEFINED - 0.81 0.30 1.000 -
 USER-DEFINED - 0.01 0.30 1.000 -
 USER-DEFINED - 1.11 0.30 1.000 -
 USER-DEFINED - 0.59 0.30 1.000 -
 USER-DEFINED - 3.04 0.30 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 18.12 SUBAREA RUNOFF(CFS) = 15.46
 EFFECTIVE AREA(ACRES) = 2549.95 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 3782.5 PEAK FLOW RATE(CFS) = 2335.95
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
 =====

MAINLINE Tc(MIN.) = 45.08
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.248
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 RESIDENTIAL
 "8-10 DWELLINGS/ACRE" B 0.10 0.30 0.400 56
 PUBLIC PARK B 1.30 0.30 0.850 56
 RESIDENTIAL
 "8-10 DWELLINGS/ACRE" B 0.10 0.30 0.400 56
 PUBLIC PARK B 1.70 0.30 0.850 56
 PUBLIC PARK B 0.10 0.30 0.850 56
 PUBLIC PARK B 2.90 0.30 0.850 56
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.835
 SUBAREA AREA(ACRES) = 6.20 SUBAREA RUNOFF(CFS) = 5.56
 EFFECTIVE AREA(ACRES) = 2556.15 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 3788.7 PEAK FLOW RATE(CFS) = 2335.95
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
 =====

MAINLINE Tc(MIN.) = 45.08
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.248
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 RESIDENTIAL
 "5-7 DWELLINGS/ACRE" B 0.10 0.30 0.500 56
 CONDOMINIUMS B 0.10 0.30 0.350 56
 PUBLIC PARK B 6.90 0.30 0.850 56
 PUBLIC PARK B 0.40 0.30 0.850 56
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.839
 SUBAREA AREA(ACRES) = 7.50 SUBAREA RUNOFF(CFS) = 6.72
 EFFECTIVE AREA(ACRES) = 2563.65 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 3796.2 PEAK FLOW RATE(CFS) = 2335.95
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13682.00 TO NODE 13683.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<
 =====

MEMORY BANK # 3 IS EMPTY - PROCESS IGNORED.
 =====

 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
 =====

MAINLINE Tc(MIN.) = 45.08
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.248
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 AGRICULTURAL POOR COVER
 "FALLOW" B 2.55 0.30 1.000 86
 AGRICULTURAL POOR COVER
 "FALLOW" B 0.01 0.30 1.000 86
 AGRICULTURAL POOR COVER
 "FALLOW" B 1.35 0.30 1.000 86
 NATURAL FAIR COVER
 "GRASS" B 0.44 0.30 1.000 69
 NATURAL FAIR COVER
 "GRASS" B 0.67 0.30 1.000 69
 NATURAL FAIR COVER

"OPEN BRUSH" B 1.06 0.30 1.000 66
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 6.08 SUBAREA RUNOFF (CFS) = 5.19
 EFFECTIVE AREA (ACRES) = 2569.73 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA (ACRES) = 3802.3 PEAK FLOW RATE (CFS) = 2335.95
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 45.08
 * 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.248
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 NATURAL FAIR COVER
 "OPEN BRUSH" B 2.16 0.30 1.000 66
 NATURAL FAIR COVER
 "OPEN BRUSH" B 2.45 0.30 1.000 66
 NATURAL FAIR COVER
 "OPEN BRUSH" B 6.15 0.30 1.000 66
 AGRICULTURAL POOR COVER
 "ROW CROPS, STRAIGHT ROW" B 1.34 0.30 1.000 81
 AGRICULTURAL POOR COVER
 "ROW CROPS, STRAIGHT ROW" B 18.46 0.30 1.000 81
 AGRICULTURAL POOR COVER
 "ROW CROPS, STRAIGHT ROW" B 4.13 0.30 1.000 81
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 34.69 SUBAREA RUNOFF (CFS) = 29.59
 EFFECTIVE AREA (ACRES) = 2604.42 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA (ACRES) = 3837.0 PEAK FLOW RATE (CFS) = 2335.95
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 45.08
 * 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.248
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 AGRICULTURAL POOR COVER
 "ROW CROPS, STRAIGHT ROW" B 8.69 0.30 1.000 81
 NATURAL FAIR COVER
 "WOODLAND, GRASS" B 0.73 0.30 1.000 65
 NATURAL FAIR COVER
 "WOODLAND, GRASS" B 0.41 0.30 1.000 65
 NATURAL FAIR COVER
 "WOODLAND, GRASS" B 1.37 0.30 1.000 65
 NATURAL FAIR COVER

"WOODLAND, GRASS" B 3.11 0.30 1.000 65
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 14.31 SUBAREA RUNOFF (CFS) = 12.21
 EFFECTIVE AREA (ACRES) = 2618.73 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA (ACRES) = 3851.3 PEAK FLOW RATE (CFS) = 2335.95
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13683.00 TO NODE 13685.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 208.53 DOWNSTREAM (FEET) = 194.24
 CHANNEL LENGTH THRU SUBAREA (FEET) = 289.01 CHANNEL SLOPE = 0.0494
 GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT (FEET) = 3.54
 CHANNEL FLOW THRU SUBAREA (CFS) = 2335.95
 FLOW VELOCITY (FEET/SEC.) = 16.22 FLOW DEPTH (FEET) = 3.54
 TRAVEL TIME (MIN.) = 0.30 Tc (MIN.) = 45.38
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13685.00 = 39866.53 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2146.94	24.94	1.737	0.30 (0.27)	0.90	1458.8	110.00
2	2209.70	27.36	1.636	0.30 (0.27)	0.90	1624.3	100.00
3	2208.11	28.64	1.583	0.30 (0.27)	0.90	1703.2	100.00
4	2242.46	31.72	1.491	0.30 (0.27)	0.91	1878.2	130.00
5	2335.95	45.38	1.243	0.30 (0.28)	0.93	2618.7	20100.00
6	2291.36	51.05	1.160	0.30 (0.28)	0.93	2805.8	13600.00
7	2090.26	87.77	0.890	0.30 (0.28)	0.93	3785.4	13510.00
8	1979.94	97.22	0.850	0.30 (0.28)	0.93	3851.3	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 2335.95 Tc (MIN.) = 45.38
 AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA (ACRES) = 2618.73

FLOW PROCESS FROM NODE 13685.00 TO NODE 13410.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 194.24 DOWNSTREAM (FEET) = 178.72
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1843.57 CHANNEL SLOPE = 0.0084
 GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT (FEET) = 5.71
 * 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.190
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 0.23 0.30 1.000 -
 USER-DEFINED - 1.52 0.30 1.000 -

USER-DEFINED - 0.06 0.30 1.000 -
 USER-DEFINED - 0.13 0.30 1.000 -
 USER-DEFINED - 6.45 0.30 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2339.31
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.69
 AVERAGE FLOW DEPTH(FEET) = 5.71 TRAVEL TIME(MIN.) = 3.54
 Tc(MIN.) = 48.91
 SUBAREA AREA(ACRES) = 8.39 SUBAREA RUNOFF(CFS) = 6.72
 EFFECTIVE AREA(ACRES) = 2627.12 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 3859.7 PEAK FLOW RATE(CFS) = 2335.95
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 5.70

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 5.70 FLOW VELOCITY(FEET/SEC.) = 8.69
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13410.00 = 41710.10 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2146.94	28.56	1.586	0.30(0.27)	0.90	1467.2	110.00
2	2209.70	30.95	1.507	0.30(0.27)	0.90	1632.7	100.00
3	2208.11	32.23	1.481	0.30(0.27)	0.90	1711.6	100.00
4	2242.46	35.30	1.420	0.30(0.27)	0.91	1886.6	130.00
5	2335.95	48.91	1.190	0.30(0.28)	0.93	2627.1	20100.00
6	2291.36	54.60	1.115	0.30(0.28)	0.93	2814.2	13600.00
7	2090.26	91.42	0.872	0.30(0.28)	0.93	3793.8	13510.00
8	1979.94	100.93	0.836	0.30(0.28)	0.93	3859.7	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2335.95 Tc(MIN.) = 48.91
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 2627.12

=====
 END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 3859.7 TC(MIN.) = 48.91
 EFFECTIVE AREA(ACRES) = 2627.12 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.927
 PEAK FLOW RATE(CFS) = 2335.95

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2146.94	28.56	1.586	0.30(0.27)	0.90	1467.2	110.00
2	2209.70	30.95	1.507	0.30(0.27)	0.90	1632.7	100.00
3	2208.11	32.23	1.481	0.30(0.27)	0.90	1711.6	100.00
4	2242.46	35.30	1.420	0.30(0.27)	0.91	1886.6	130.00
5	2335.95	48.91	1.190	0.30(0.28)	0.93	2627.1	20100.00
6	2291.36	54.60	1.115	0.30(0.28)	0.93	2814.2	13600.00
7	2090.26	91.42	0.872	0.30(0.28)	0.93	3793.8	13510.00
8	1979.94	100.93	0.836	0.30(0.28)	0.93	3859.7	13500.00

=====
 END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2010 Advanced Engineering Software (aes)
Ver. 17.0 Release Date: 07/01/2010 License ID 1527

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 137 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 25-YR EV AUG 2023 ROKAMOTO *

FILE NAME: RU25EV37.DAT
TIME/DATE OF STUDY: 22:26 08/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 25.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED

NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 4.753
- 2) 10.00; 3.112
- 3) 15.00; 2.390
- 4) 20.00; 1.984
- 5) 25.00; 1.732
- 6) 30.00; 1.524
- 7) 40.00; 1.323
- 8) 50.00; 1.171
- 9) 60.00; 1.045
- 10) 90.00; 0.875
- 11) 120.00; 0.763
- 12) 180.00; 0.634
- 13) 360.00; 0.464
- 14) 1200.00; 0.203

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:

- 1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU25EV34.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22661.39	15.26	0.30 (0.24)	0.80	4248.4	300.00
2	26918.92	28.93	0.30 (0.24)	0.80	8464.4	110.00
3	30435.49	42.25	0.30 (0.24)	0.82	14024.3	800.00
4	32698.17	54.94	0.30 (0.26)	0.86	20437.1	13600.00
5	34676.95	68.96	0.30 (0.26)	0.88	27201.7	13100.00
6	35643.23	75.27	0.30 (0.27)	0.89	29953.9	11801.00
7	37612.71	85.83	0.30 (0.27)	0.90	35276.1	11530.00
8	38419.44	91.74	0.30 (0.27)	0.91	39028.4	13510.00
9	39191.36	97.62	0.30 (0.28)	0.92	42648.5	13010.00
10	40267.45	104.28	0.30 (0.28)	0.92	46929.6	11350.00
11	40653.58	108.97	0.30 (0.28)	0.93	50103.9	11130.00
12	40240.18	115.05	0.30 (0.28)	0.93	53030.4	12300.00
13	39460.86	123.81	0.30 (0.28)	0.94	57291.0	12400.00
14	38409.58	133.33	0.30 (0.28)	0.94	60692.6	12201.00
15	37436.32	140.82	0.30 (0.28)	0.94	62585.6	12231.00
16	36429.39	148.31	0.30 (0.28)	0.94	64138.4	10400.00
17	34861.84	157.76	0.30 (0.28)	0.94	6584.8	12010.00
18	33814.10	163.15	0.30 (0.28)	0.94	65847.4	10210.00
19	33138.71	167.21	0.30 (0.28)	0.94	65994.2	12000.00
20	29438.31	193.57	0.30 (0.28)	0.94	66607.1	10100.00
TOTAL AREA (ACRES) =						66607.1

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 14.0

>>>>MEMORY BANK # 3 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22661.39	15.26	0.30 (0.24)	0.80	4248.4	300.00
2	26918.92	28.93	0.30 (0.24)	0.80	8464.4	110.00
3	30435.49	42.25	0.30 (0.24)	0.82	14024.3	800.00
4	32698.17	54.94	0.30 (0.26)	0.86	20437.1	13600.00
5	34676.95	68.96	0.30 (0.26)	0.88	27201.7	13100.00
6	35643.23	75.27	0.30 (0.27)	0.89	29953.9	11801.00
7	37612.71	85.83	0.30 (0.27)	0.90	35276.1	11530.00
8	38419.44	91.74	0.30 (0.27)	0.91	39028.4	13510.00
9	39191.36	97.62	0.30 (0.28)	0.92	42648.5	13010.00
10	40267.45	104.28	0.30 (0.28)	0.92	46929.6	11350.00
11	40653.58	108.97	0.30 (0.28)	0.93	50103.9	11130.00
12	40240.18	115.05	0.30 (0.28)	0.93	53030.4	12300.00
13	39460.86	123.81	0.30 (0.28)	0.94	57291.0	12400.00

14 38409.58 133.33 0.30(0.28) 0.94 60692.6 12201.00
 15 37436.32 140.82 0.30(0.28) 0.94 62585.6 12231.00
 16 36429.39 148.31 0.30(0.28) 0.94 64138.4 10400.00
 17 34861.84 157.76 0.30(0.28) 0.94 65584.8 12010.00
 18 33814.10 163.15 0.30(0.28) 0.94 65847.4 10210.00
 19 33138.71 167.21 0.30(0.28) 0.94 65994.2 12000.00
 20 29438.31 193.57 0.30(0.28) 0.94 66607.1 10100.00
 TOTAL AREA(ACRES) = 66607.1

FLOW PROCESS FROM NODE 13700.00 TO NODE 13720.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 170.00 DOWNSTREAM(FEET) = 165.51
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1891.83 CHANNEL SLOPE = 0.0024
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 13.21
 CHANNEL FLOW THRU SUBAREA(CFS) = 40653.58
 FLOW VELOCITY(FEET/SEC.) = 11.57 FLOW DEPTH(FEET) = 13.21
 TRAVEL TIME(MIN.) = 2.73 Tc(MIN.) = 111.70
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126441.05 FEET.

FLOW PROCESS FROM NODE 13700.00 TO NODE 13720.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

FLOW PROCESS FROM NODE 13720.00 TO NODE 13720.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506102D.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	321.17	15.37	2.360	0.30(0.29)	0.96	192.9	10230.00
2	293.25	24.48	1.758	0.30(0.29)	0.95	241.2	10200.00
3	292.00	24.71	1.747	0.30(0.29)	0.95	241.7	10250.00
4	266.33	28.63	1.581	0.30(0.29)	0.95	246.3	10220.00
TOTAL AREA(ACRES) =							246.3

FLOW PROCESS FROM NODE 13720.00 TO NODE 13720.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22661.39	18.55	2.102	0.30(0.24)	0.80	4248.4	300.00
2	26918.92	32.03	1.483	0.30(0.24)	0.80	8464.4	110.00
3	30435.49	45.23	1.243	0.30(0.24)	0.82	14024.3	800.00

4	32698.17	57.86	1.072	0.30(0.26)	0.86	20437.1	13600.00
5	34676.95	71.83	0.978	0.30(0.26)	0.88	27201.7	13100.00
6	35643.23	78.11	0.942	0.30(0.27)	0.89	29953.9	11801.00
7	37612.71	88.63	0.883	0.30(0.27)	0.90	35276.1	11530.00
8	38419.44	94.51	0.858	0.30(0.27)	0.91	39028.4	13510.00
9	39191.36	100.38	0.836	0.30(0.28)	0.92	42648.5	13010.00
10	40267.45	107.01	0.811	0.30(0.28)	0.92	46929.6	11350.00
11	40653.58	111.70	0.794	0.30(0.28)	0.93	50103.9	11130.00
12	40240.18	117.78	0.771	0.30(0.28)	0.93	53030.4	12300.00
13	39460.86	126.56	0.749	0.30(0.28)	0.94	57291.0	12400.00
14	38409.58	136.11	0.728	0.30(0.28)	0.94	60692.6	12201.00
15	37436.32	143.62	0.712	0.30(0.28)	0.94	62585.6	12231.00
16	36429.39	151.13	0.696	0.30(0.28)	0.94	64138.4	10400.00
17	34861.84	160.62	0.676	0.30(0.28)	0.94	65584.8	12010.00
18	33814.10	166.04	0.664	0.30(0.28)	0.94	65847.4	10210.00
19	33138.71	170.11	0.655	0.30(0.28)	0.94	65994.2	12000.00
20	29438.31	196.59	0.618	0.30(0.28)	0.94	66607.1	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126441.05 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	321.17	15.37	2.360	0.30(0.29)	0.96	192.9	10230.00
2	293.25	24.48	1.758	0.30(0.29)	0.95	241.2	10200.00
3	292.00	24.71	1.747	0.30(0.29)	0.95	241.7	10250.00
4	266.33	28.63	1.581	0.30(0.29)	0.95	246.3	10220.00

LONGEST FLOWPATH FROM NODE 10200.00 TO NODE 13720.00 = 9099.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21701.66	15.37	2.360	0.30(0.24)	0.81	3713.6	10230.00
2	22972.82	18.55	2.102	0.30(0.24)	0.81	4458.1	300.00
3	24827.79	24.48	1.758	0.30(0.24)	0.81	6344.4	10200.00
4	24900.04	24.71	1.747	0.30(0.24)	0.81	6417.8	10250.00
5	26110.73	28.63	1.581	0.30(0.24)	0.81	7646.6	10220.00
6	27165.11	32.03	1.483	0.30(0.24)	0.81	8710.6	110.00
7	30632.39	45.23	1.243	0.30(0.25)	0.82	14270.5	800.00
8	32859.80	57.86	1.072	0.30(0.26)	0.86	20683.4	13600.00
9	34819.25	71.83	0.978	0.30(0.27)	0.88	27447.9	13100.00
10	35778.21	78.11	0.942	0.30(0.27)	0.89	30200.2	11801.00
11	37735.43	88.63	0.883	0.30(0.27)	0.90	35522.3	11530.00
12	38537.09	94.51	0.858	0.30(0.27)	0.91	39274.6	13510.00
13	39304.51	100.38	0.836	0.30(0.28)	0.92	42894.7	13010.00
14	40375.51	107.01	0.811	0.30(0.28)	0.92	47175.9	11350.00
15	40758.04	111.70	0.794	0.30(0.28)	0.93	50350.1	11130.00
16	40339.97	117.78	0.771	0.30(0.28)	0.93	53276.7	12300.00
17	39556.05	126.56	0.749	0.30(0.28)	0.94	57537.3	12400.00
18	38500.54	136.11	0.728	0.30(0.28)	0.94	60938.9	12201.00
19	37523.96	143.62	0.712	0.30(0.28)	0.94	62831.9	12231.00
20	36513.71	151.13	0.696	0.30(0.28)	0.94	64384.6	10400.00
21	34941.96	160.62	0.676	0.30(0.28)	0.94	65831.0	12010.00
22	33891.83	166.04	0.664	0.30(0.28)	0.94	66093.6	10210.00
23	33214.64	170.11	0.655	0.30(0.28)	0.94	66240.4	12000.00
24	29506.64	196.59	0.618	0.30(0.28)	0.94	66853.4	10100.00
TOTAL AREA(ACRES) =							66853.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 40758.04 Tc(MIN.) = 111.697
 EFFECTIVE AREA(ACRES) = 50350.11 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.90
 TOTAL AREA(ACRES) = 66853.4
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126441.05 FEET.

 FLOW PROCESS FROM NODE 13720.00 TO NODE 13740.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 165.51 DOWNSTREAM(FEET) = 161.03
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2067.54 CHANNEL SLOPE = 0.0022
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 13.56
 CHANNEL FLOW THRU SUBAREA(CFS) = 40758.04
 FLOW VELOCITY(FEET/SEC.) = 11.22 FLOW DEPTH(FEET) = 13.56
 TRAVEL TIME(MIN.) = 3.07 Tc(MIN.) = 114.77
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128508.59 FEET.

 FLOW PROCESS FROM NODE 13720.00 TO NODE 13740.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

 FLOW PROCESS FROM NODE 13740.00 TO NODE 13740.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 0506103D.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	651.40	18.38	0.30(0.23)	0.76	399.7	10300.00
2	652.99	19.22	0.30(0.23)	0.76	413.6	10380.00
3	641.00	21.63	0.30(0.23)	0.76	440.0	10320.00
4	618.06	23.73	0.30(0.23)	0.76	451.6	10360.00
5	581.15	26.62	0.30(0.23)	0.76	460.8	10340.00
TOTAL AREA(ACRES) =						460.8

 FLOW PROCESS FROM NODE 13740.00 TO NODE 13740.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

=====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21701.66	19.12	2.055	0.30(0.24)	0.81	3713.6	10230.00
2	22972.82	22.23	1.872	0.30(0.24)	0.81	4458.1	300.00
3	24827.79	28.07	1.604	0.30(0.24)	0.81	6344.4	10200.00
4	24900.04	28.30	1.595	0.30(0.24)	0.81	6417.8	10250.00
5	26110.73	32.16	1.481	0.30(0.24)	0.81	7646.6	10220.00

6	27165.11	35.52	1.413	0.30(0.24)	0.81	8710.6	110.00
7	30632.39	48.59	1.192	0.30(0.25)	0.82	14270.5	800.00
8	32859.80	61.14	1.039	0.30(0.26)	0.86	20683.4	13600.00
9	34819.25	75.05	0.960	0.30(0.27)	0.88	27447.9	13100.00
10	35778.21	81.31	0.924	0.30(0.27)	0.89	30200.2	11801.00
11	37735.43	91.77	0.868	0.30(0.27)	0.90	35522.3	11530.00
12	38537.09	97.64	0.846	0.30(0.27)	0.91	39274.6	13510.00
13	39304.51	103.48	0.825	0.30(0.28)	0.92	42894.7	13010.00
14	40375.51	110.09	0.800	0.30(0.28)	0.92	47175.9	11350.00
15	40758.04	114.77	0.783	0.30(0.28)	0.93	50350.1	11130.00
16	40339.97	120.86	0.761	0.30(0.28)	0.93	53276.7	12300.00
17	39556.05	129.66	0.742	0.30(0.28)	0.94	57537.3	12400.00
18	38500.54	139.23	0.722	0.30(0.28)	0.94	60938.9	12201.00
19	37523.96	146.77	0.705	0.30(0.28)	0.94	62831.9	12231.00
20	36513.71	154.31	0.689	0.30(0.28)	0.94	64384.6	10400.00
21	34941.96	163.84	0.669	0.30(0.28)	0.94	65831.0	12010.00
22	33891.83	169.29	0.657	0.30(0.28)	0.94	66093.6	10210.00
23	33214.64	173.39	0.648	0.30(0.28)	0.94	66240.4	12000.00
24	29506.64	199.99	0.615	0.30(0.28)	0.94	66853.4	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128508.59 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	651.40	18.38	2.116	0.30(0.23)	0.76	399.7	10300.00
2	652.99	19.22	2.047	0.30(0.23)	0.76	413.6	10380.00
3	641.00	21.63	1.902	0.30(0.23)	0.76	440.0	10320.00
4	618.06	23.73	1.796	0.30(0.23)	0.76	451.6	10360.00
5	581.15	26.62	1.665	0.30(0.23)	0.76	460.8	10340.00

LONGEST FLOWPATH FROM NODE 10320.00 TO NODE 13740.00 = 8457.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22203.91	18.38	2.116	0.30(0.24)	0.80	3969.1	10300.00
2	22354.47	19.12	2.055	0.30(0.24)	0.80	4125.6	10230.00
3	22393.94	19.22	2.047	0.30(0.24)	0.80	4150.2	10380.00
4	23370.43	21.63	1.902	0.30(0.24)	0.80	4755.6	10320.00
5	23607.32	22.23	1.872	0.30(0.24)	0.80	4901.4	300.00
6	24067.98	23.73	1.796	0.30(0.24)	0.80	5394.9	10360.00
7	24947.84	26.62	1.665	0.30(0.24)	0.80	6336.3	10340.00
8	25384.48	28.07	1.604	0.30(0.24)	0.80	6805.2	10200.00
9	25452.88	28.30	1.595	0.30(0.24)	0.80	6878.6	10250.00
10	26617.37	32.16	1.481	0.30(0.24)	0.80	8107.4	10220.00
11	27644.42	35.52	1.413	0.30(0.24)	0.80	9171.4	110.00
12	31022.39	48.59	1.192	0.30(0.24)	0.82	14731.3	800.00
13	33187.50	61.14	1.039	0.30(0.26)	0.86	21144.2	13600.00
14	35115.04	75.05	0.960	0.30(0.26)	0.88	27908.7	13100.00
15	36059.65	81.31	0.924	0.30(0.27)	0.89	30661.0	11801.00
16	37994.25	91.77	0.868	0.30(0.27)	0.90	35983.1	11530.00
17	38787.04	97.64	0.846	0.30(0.27)	0.91	39735.4	13510.00
18	39545.63	103.48	0.825	0.30(0.27)	0.92	43355.5	13010.00
19	40606.64	110.09	0.800	0.30(0.28)	0.92	47636.7	11350.00
20	40982.11	114.77	0.783	0.30(0.28)	0.93	50810.9	11130.00
21	40555.38	120.86	0.761	0.30(0.28)	0.93	53737.5	12300.00
22	39763.79	129.66	0.742	0.30(0.28)	0.94	57998.1	12400.00
23	38699.96	139.23	0.722	0.30(0.28)	0.94	61399.7	12201.00
24	37716.82	146.77	0.705	0.30(0.28)	0.94	63292.7	12231.00

25 36700.00 154.31 0.689 0.30(0.28) 0.94 64845.4 10400.00
 26 35119.96 163.84 0.669 0.30(0.28) 0.94 66291.8 12010.00
 27 34065.09 169.29 0.657 0.30(0.28) 0.94 66554.4 10210.00
 28 33384.33 173.39 0.648 0.30(0.28) 0.94 66701.2 12000.00
 29 29662.94 199.99 0.615 0.30(0.28) 0.94 67314.2 10100.00
 TOTAL AREA (ACRES) = 67314.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 40982.11 Tc(MIN.) = 114.768
 EFFECTIVE AREA(ACRES) = 50810.91 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.89
 TOTAL AREA(ACRES) = 67314.2
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128508.59 FEET.

FLOW PROCESS FROM NODE 13740.00 TO NODE 13741.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 161.03 DOWNSTREAM(FEET) = 141.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 364.08 CHANNEL SLOPE = 0.0550
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 7.88
 CHANNEL FLOW THRU SUBAREA(CFS) = 40982.11
 FLOW VELOCITY(FEET/SEC.) = 39.55 FLOW DEPTH(FEET) = 7.88
 TRAVEL TIME(MIN.) = 0.15 Tc(MIN.) = 114.92
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128872.66 FEET.

FLOW PROCESS FROM NODE 13740.00 TO NODE 13741.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

FLOW PROCESS FROM NODE 13741.00 TO NODE 13741.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506104D.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	65.97	19.78	0.30(0.24)	0.80	44.3	10400.00
TOTAL AREA(ACRES) =						44.3

FLOW PROCESS FROM NODE 13741.00 TO NODE 13741.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22203.91	18.57	2.100	0.30(0.24)	0.80	3969.1	10300.00

2	22354.47	19.31	2.040	0.30(0.24)	0.80	4125.6	10230.00
3	22393.94	19.40	2.032	0.30(0.24)	0.80	4150.2	10380.00
4	23370.43	21.82	1.892	0.30(0.24)	0.80	4755.6	10320.00
5	23607.32	22.41	1.862	0.30(0.24)	0.80	4901.4	300.00
6	24067.98	23.91	1.787	0.30(0.24)	0.80	5394.9	10360.00
7	24947.84	26.80	1.657	0.30(0.24)	0.80	6336.3	10340.00
8	25384.48	28.25	1.597	0.30(0.24)	0.80	6805.2	10200.00
9	25452.88	28.48	1.587	0.30(0.24)	0.80	6878.6	10250.00
10	26617.37	32.34	1.477	0.30(0.24)	0.80	8107.4	10220.00
11	27644.42	35.69	1.410	0.30(0.24)	0.80	9171.4	110.00
12	31022.39	48.76	1.190	0.30(0.24)	0.82	14731.3	800.00
13	33187.50	61.31	1.038	0.30(0.26)	0.86	21144.2	13600.00
14	35115.04	75.21	0.959	0.30(0.26)	0.88	27908.7	13100.00
15	36059.65	81.47	0.923	0.30(0.27)	0.89	30661.0	11801.00
16	37994.25	91.93	0.868	0.30(0.27)	0.90	35983.1	11530.00
17	38787.04	97.79	0.846	0.30(0.27)	0.91	39735.4	13510.00
18	39545.63	103.64	0.824	0.30(0.27)	0.92	43355.5	13010.00
19	40606.64	110.25	0.799	0.30(0.28)	0.92	47636.7	11350.00
20	40982.11	114.92	0.782	0.30(0.28)	0.93	50810.9	11130.00
21	40555.38	121.01	0.761	0.30(0.28)	0.93	53737.5	12300.00
22	39763.79	129.82	0.742	0.30(0.28)	0.94	57998.1	12400.00
23	38699.96	139.39	0.721	0.30(0.28)	0.94	61399.7	12201.00
24	37716.82	146.93	0.705	0.30(0.28)	0.94	63292.7	12231.00
25	36700.00	154.47	0.689	0.30(0.28)	0.94	64845.4	10400.00
26	35119.96	164.00	0.668	0.30(0.28)	0.94	66291.8	12010.00
27	34065.09	169.45	0.657	0.30(0.28)	0.94	66554.4	10210.00
28	33384.33	173.55	0.648	0.30(0.28)	0.94	66701.2	12000.00
29	29662.94	200.16	0.615	0.30(0.28)	0.94	67314.2	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128872.66 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	65.97	19.78	2.002	0.30(0.24)	0.80	44.3	10400.00

LONGEST FLOWPATH FROM NODE 10400.00 TO NODE 13741.00 = 6237.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22269.30	18.57	2.100	0.30(0.24)	0.80	4010.7	10300.00
2	22420.27	19.31	2.040	0.30(0.24)	0.80	4168.8	10230.00
3	22459.78	19.40	2.032	0.30(0.24)	0.80	4193.7	10380.00
4	22611.42	19.78	2.002	0.30(0.24)	0.80	4288.4	10400.00
5	23432.30	21.82	1.892	0.30(0.24)	0.80	4799.9	10320.00
6	23668.07	22.41	1.862	0.30(0.24)	0.80	4945.7	300.00
7	24125.90	23.91	1.787	0.30(0.24)	0.80	5439.2	10360.00
8	25000.90	26.80	1.657	0.30(0.24)	0.80	6380.6	10340.00
9	25435.29	28.25	1.597	0.30(0.24)	0.80	6849.5	10200.00
10	25503.33	28.48	1.587	0.30(0.24)	0.80	6922.9	10250.00
11	26663.69	32.34	1.477	0.30(0.24)	0.80	8151.7	10220.00
12	27688.22	35.69	1.410	0.30(0.24)	0.80	9215.7	110.00
13	31057.97	48.76	1.190	0.30(0.24)	0.82	14775.6	800.00
14	33217.38	61.31	1.038	0.30(0.26)	0.86	21188.5	13600.00
15	35141.96	75.21	0.959	0.30(0.26)	0.88	27953.0	13100.00
16	36085.25	81.47	0.923	0.30(0.27)	0.89	30705.3	11801.00
17	38017.77	91.93	0.868	0.30(0.27)	0.90	36027.4	11530.00
18	38809.74	97.79	0.846	0.30(0.27)	0.91	39779.7	13510.00
19	39567.52	103.64	0.824	0.30(0.27)	0.92	43399.8	13010.00

20	40627.60	110.25	0.799	0.30	(0.28)	0.92	47681.0	11350.00
21	41002.41	114.92	0.782	0.30	(0.28)	0.93	50855.2	11130.00
22	40574.89	121.01	0.761	0.30	(0.28)	0.93	53781.8	12300.00
23	39782.60	129.82	0.742	0.30	(0.28)	0.94	58042.4	12400.00
24	38718.00	139.39	0.721	0.30	(0.28)	0.94	61444.0	12201.00
25	37734.25	146.93	0.705	0.30	(0.28)	0.94	63337.0	12231.00
26	36716.83	154.47	0.689	0.30	(0.28)	0.94	64889.7	10400.00
27	35136.02	164.00	0.668	0.30	(0.28)	0.94	66336.1	12010.00
28	34080.70	169.45	0.657	0.30	(0.28)	0.94	66598.7	10210.00
29	33399.62	173.55	0.648	0.30	(0.28)	0.94	66745.5	12000.00
30	29676.99	200.16	0.615	0.30	(0.28)	0.94	67358.5	10100.00

TOTAL AREA (ACRES) = 67358.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 41002.41 Tc (MIN.) = 114.921
EFFECTIVE AREA (ACRES) = 50855.21 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA (ACRES) = 67358.5
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128872.66 FEET.

FLOW PROCESS FROM NODE 13741.00 TO NODE 13802.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 141.00 DOWNSTREAM (FEET) = 135.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 1533.41 CHANNEL SLOPE = 0.0039
GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 16.00
CHANNEL FLOW THRU SUBAREA (CFS) = 41002.41
FLOW VELOCITY (FEET/SEC.) = 15.62 FLOW DEPTH (FEET) = 16.00
TRAVEL TIME (MIN.) = 1.64 Tc (MIN.) = 116.56
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130406.07 FEET.

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<

PEAK FLOWRATE TABLE FILE NAME: 0506105K.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	355.73	14.74	0.30 (0.27)	0.90	206.7	10520.00
2	414.68	31.61	0.30 (0.28)	0.93	403.6	10500.00
TOTAL AREA (ACRES) =						403.6

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22269.30	20.52	1.958	0.30 (0.24)	0.80	4010.7	10300.00
2	22420.27	21.26	1.921	0.30 (0.24)	0.80	4168.8	10230.00
3	22459.78	21.35	1.916	0.30 (0.24)	0.80	4193.7	10380.00
4	22611.42	21.72	1.897	0.30 (0.24)	0.80	4288.4	10400.00
5	23432.30	23.74	1.795	0.30 (0.24)	0.80	4799.9	10320.00
6	23668.07	24.33	1.766	0.30 (0.24)	0.80	4945.7	300.00
7	24125.90	25.82	1.698	0.30 (0.24)	0.80	5439.2	10360.00
8	25000.90	28.69	1.579	0.30 (0.24)	0.80	6380.6	10340.00
9	25435.29	30.13	1.521	0.30 (0.24)	0.80	6849.5	10200.00
10	25503.33	30.36	1.517	0.30 (0.24)	0.80	6922.9	10250.00
11	26663.69	34.19	1.440	0.30 (0.24)	0.80	8151.7	10220.00
12	27688.22	37.52	1.373	0.30 (0.24)	0.80	9215.7	110.00
13	31057.97	50.53	1.164	0.30 (0.24)	0.82	14775.6	800.00
14	33217.38	63.04	1.028	0.30 (0.26)	0.86	21188.5	13600.00
15	35141.96	76.92	0.949	0.30 (0.26)	0.88	27953.0	13100.00
16	36085.25	83.16	0.914	0.30 (0.27)	0.89	30705.3	11801.00
17	38017.77	93.60	0.862	0.30 (0.27)	0.90	36027.4	11530.00
18	38809.74	99.46	0.840	0.30 (0.27)	0.91	39779.7	13510.00
19	39567.52	105.29	0.818	0.30 (0.27)	0.92	43399.8	13010.00
20	40627.60	111.89	0.793	0.30 (0.28)	0.92	47681.0	11350.00
21	41002.41	116.56	0.776	0.30 (0.28)	0.93	50855.2	11130.00
22	40574.89	122.66	0.757	0.30 (0.28)	0.93	53781.8	12300.00
23	39782.60	131.47	0.738	0.30 (0.28)	0.94	58042.4	12400.00
24	38718.00	141.05	0.718	0.30 (0.28)	0.94	61444.0	12201.00
25	37734.25	148.60	0.702	0.30 (0.28)	0.94	63337.0	12231.00
26	36716.83	156.15	0.685	0.30 (0.28)	0.94	64889.7	10400.00
27	35136.02	165.71	0.665	0.30 (0.28)	0.94	66336.1	12010.00
28	34080.70	171.18	0.653	0.30 (0.28)	0.94	66598.7	10210.00
29	33399.62	175.29	0.644	0.30 (0.28)	0.94	66745.5	12000.00
30	29676.99	201.95	0.613	0.30 (0.28)	0.94	67358.5	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130406.07 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	355.73	14.74	2.428	0.30 (0.27)	0.90	206.7	10520.00
2	414.68	31.61	1.492	0.30 (0.28)	0.93	403.6	10500.00

LONGEST FLOWPATH FROM NODE 10500.00 TO NODE 13802.00 = 12187.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20728.27	14.74	2.428	0.30 (0.24)	0.81	3087.3	10520.00
2	22645.23	20.52	1.958	0.30 (0.24)	0.81	4284.8	10300.00
3	22798.77	21.26	1.921	0.30 (0.24)	0.81	4451.6	10230.00
4	22838.61	21.35	1.916	0.30 (0.24)	0.81	4477.5	10380.00
5	22991.55	21.72	1.897	0.30 (0.24)	0.81	4576.6	10400.00
6	23819.48	23.74	1.795	0.30 (0.24)	0.81	5111.6	10320.00
7	24057.30	24.33	1.766	0.30 (0.24)	0.81	5264.3	300.00
8	24520.35	25.82	1.698	0.30 (0.24)	0.81	5775.2	10360.00
9	25405.35	28.69	1.579	0.30 (0.24)	0.81	6750.1	10340.00
10	25844.78	30.13	1.521	0.30 (0.24)	0.81	7235.8	10200.00

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
11	25913.61	30.36	1.517	0.30 (0.24)	0.81	7311.8	10250.00
12	26299.04	31.61	1.492	0.30 (0.24)	0.81	7730.0	10500.00
13	27060.69	34.19	1.440	0.30 (0.24)	0.81	8555.3	10220.00
14	28062.31	37.52	1.373	0.30 (0.24)	0.81	9619.3	110.00
15	31360.84	50.53	1.164	0.30 (0.25)	0.82	15179.2	800.00
16	33473.58	63.04	1.028	0.30 (0.26)	0.86	21592.1	13600.00
17	35371.29	76.92	0.949	0.30 (0.26)	0.88	28356.6	13100.00
18	36302.49	83.16	0.914	0.30 (0.27)	0.89	31108.9	11801.00
19	38217.18	93.60	0.862	0.30 (0.27)	0.90	36431.0	11530.00
20	39001.68	99.46	0.840	0.30 (0.27)	0.91	40183.3	13510.00
21	39752.01	105.29	0.818	0.30 (0.27)	0.92	43803.4	13010.00
22	40803.68	111.89	0.793	0.30 (0.28)	0.92	48084.6	11350.00
23	41172.54	116.56	0.776	0.30 (0.28)	0.93	51258.8	11130.00
24	40738.67	122.66	0.757	0.30 (0.28)	0.93	54185.4	12300.00
25	39939.91	131.47	0.738	0.30 (0.28)	0.94	58446.0	12400.00
26	38868.26	141.05	0.718	0.30 (0.28)	0.94	61847.6	12201.00
27	37878.96	148.60	0.702	0.30 (0.28)	0.94	63740.6	12231.00
28	36856.00	156.15	0.685	0.30 (0.28)	0.94	65293.3	10400.00
29	35268.16	165.71	0.665	0.30 (0.28)	0.94	66739.7	12010.00
30	34208.83	171.18	0.653	0.30 (0.28)	0.94	67002.3	10210.00
31	33524.73	175.29	0.644	0.30 (0.28)	0.94	67149.1	12000.00
32	29791.55	201.95	0.613	0.30 (0.28)	0.94	67762.1	10100.00

TOTAL AREA (ACRES) = 67762.1

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 41172.54 Tc (MIN.) = 116.557
EFFECTIVE AREA (ACRES) = 51258.81 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA (ACRES) = 67762.1
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130406.07 FEET.

FLOW PROCESS FROM NODE 13802.00 TO NODE 13803.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 135.00 DOWNSTREAM (FEET) = 134.99
CHANNEL LENGTH THRU SUBAREA (FEET) = 207.23 CHANNEL SLOPE = 0.0000
GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 46.24
CHANNEL FLOW THRU SUBAREA (CFS) = 41172.54
FLOW VELOCITY (FEET/SEC.) = 3.13 FLOW DEPTH (FEET) = 46.24
TRAVEL TIME (MIN.) = 1.11 Tc (MIN.) = 117.66
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130613.30 FEET.

FLOW PROCESS FROM NODE 13802.00 TO NODE 13803.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506106D.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	59.23	17.66	0.30 (0.20)	0.67		36.9	10600.00
TOTAL AREA (ACRES) =			36.9				

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20728.27	16.06	2.304	0.30 (0.24)	0.81	3087.3	10520.00
2	22645.23	21.81	1.893	0.30 (0.24)	0.81	4284.8	10300.00
3	22798.77	22.54	1.856	0.30 (0.24)	0.81	4451.6	10230.00
4	22838.61	22.64	1.851	0.30 (0.24)	0.81	4477.5	10380.00
5	22991.55	23.01	1.832	0.30 (0.24)	0.81	4576.6	10400.00
6	23819.48	25.02	1.731	0.30 (0.24)	0.81	5111.6	10320.00
7	24057.30	25.60	1.707	0.30 (0.24)	0.81	5264.3	300.00
8	24520.35	27.08	1.645	0.30 (0.24)	0.81	5775.2	10360.00
9	25405.35	29.94	1.527	0.30 (0.24)	0.81	6750.1	10340.00
10	25844.78	31.37	1.496	0.30 (0.24)	0.81	7235.8	10200.00
11	25913.61	31.60	1.492	0.30 (0.24)	0.81	7311.8	10250.00
12	26299.04	32.86	1.467	0.30 (0.24)	0.81	7730.0	10500.00
13	27060.69	35.42	1.415	0.30 (0.24)	0.81	8555.3	10220.00
14	28062.31	38.74	1.348	0.30 (0.24)	0.81	9619.3	110.00
15	31360.84	51.71	1.149	0.30 (0.25)	0.82	15179.2	800.00
16	33473.58	64.21	1.021	0.30 (0.26)	0.86	21592.1	13600.00
17	35371.29	78.07	0.943	0.30 (0.26)	0.88	28356.6	13100.00
18	36302.49	84.30	0.907	0.30 (0.27)	0.89	31108.9	11801.00
19	38217.18	94.73	0.857	0.30 (0.27)	0.90	36431.0	11530.00
20	39001.68	100.58	0.836	0.30 (0.27)	0.91	40183.3	13510.00
21	39752.01	106.41	0.814	0.30 (0.27)	0.92	43803.4	13010.00
22	40803.68	113.00	0.789	0.30 (0.28)	0.92	48084.6	11350.00
23	41172.54	117.66	0.772	0.30 (0.28)	0.93	51258.8	11130.00
24	40738.67	123.76	0.755	0.30 (0.28)	0.93	54185.4	12300.00
25	39939.91	132.58	0.736	0.30 (0.28)	0.94	58446.0	12400.00
26	38868.26	142.17	0.715	0.30 (0.28)	0.94	61847.6	12201.00
27	37878.96	149.73	0.699	0.30 (0.28)	0.94	63740.6	12231.00
28	36856.00	157.29	0.683	0.30 (0.28)	0.94	65293.3	10400.00
29	35268.16	166.86	0.662	0.30 (0.28)	0.94	66739.7	12010.00
30	34208.83	172.34	0.650	0.30 (0.28)	0.94	67002.3	10210.00
31	33524.73	176.45	0.642	0.30 (0.28)	0.94	67149.1	12000.00
32	29791.55	203.15	0.612	0.30 (0.28)	0.94	67762.1	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130613.30 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	59.23	17.66	2.174	0.30 (0.20)	0.67	36.9	10600.00

LONGEST FLOWPATH FROM NODE 10600.00 TO NODE 13803.00 = 1713.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM	Q	Tc	Intensity	Fp (Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	---------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	20785.68	16.06	2.304	0.30 (0.24) 0.81	3120.9	10520.00
2	21320.77	17.66	2.174	0.30 (0.24) 0.81	3457.4	10600.00
3	22696.01	21.81	1.893	0.30 (0.24) 0.81	4321.7	10300.00
4	22848.44	22.54	1.856	0.30 (0.24) 0.81	4488.5	10230.00
5	22888.14	22.64	1.851	0.30 (0.24) 0.81	4514.4	10380.00
6	23040.52	23.01	1.832	0.30 (0.24) 0.81	4613.5	10400.00
7	23865.43	25.02	1.731	0.30 (0.24) 0.81	5148.5	10320.00
8	24102.51	25.60	1.707	0.30 (0.24) 0.81	5301.2	300.00
9	24563.70	27.08	1.645	0.30 (0.24) 0.81	5812.1	10360.00
10	25445.15	29.94	1.527	0.30 (0.24) 0.81	6787.0	10340.00
11	25883.66	31.37	1.496	0.30 (0.24) 0.81	7272.7	10200.00
12	25952.36	31.60	1.492	0.30 (0.24) 0.81	7348.7	10250.00
13	26337.03	32.86	1.467	0.30 (0.24) 0.81	7766.9	10500.00
14	27097.13	35.42	1.415	0.30 (0.24) 0.81	8592.2	10220.00
15	28096.75	38.74	1.348	0.30 (0.24) 0.81	9656.2	110.00
16	31389.31	51.71	1.149	0.30 (0.25) 0.82	15216.1	800.00
17	33498.20	64.21	1.021	0.30 (0.26) 0.86	21629.0	13600.00
18	35393.55	78.07	0.943	0.30 (0.26) 0.88	28393.5	13100.00
19	36323.70	84.30	0.907	0.30 (0.27) 0.89	31145.8	11801.00
20	38236.88	94.73	0.857	0.30 (0.27) 0.90	36467.9	11530.00
21	39020.73	100.58	0.836	0.30 (0.27) 0.91	40220.2	13510.00
22	39770.40	106.41	0.814	0.30 (0.27) 0.92	43840.3	13010.00
23	40821.33	113.00	0.789	0.30 (0.28) 0.92	48121.5	11350.00
24	41189.67	117.66	0.772	0.30 (0.28) 0.93	51295.7	11130.00
25	40755.30	123.76	0.755	0.30 (0.28) 0.93	54222.3	12300.00
26	39955.96	132.58	0.736	0.30 (0.28) 0.93	58482.9	12400.00
27	38883.70	142.17	0.715	0.30 (0.28) 0.94	61884.5	12201.00
28	37893.92	149.73	0.699	0.30 (0.28) 0.94	63777.5	12231.00
29	36870.46	157.29	0.683	0.30 (0.28) 0.94	65330.2	10400.00
30	35282.01	166.86	0.662	0.30 (0.28) 0.94	66776.6	12010.00
31	34222.32	172.34	0.650	0.30 (0.28) 0.94	67039.2	10210.00
32	33537.96	176.45	0.642	0.30 (0.28) 0.94	67186.0	12000.00
33	29803.90	203.15	0.612	0.30 (0.28) 0.94	67799.0	10100.00

TOTAL AREA (ACRES) = 67799.0

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 41189.67 Tc (MIN.) = 117.662
EFFECTIVE AREA (ACRES) = 51295.71 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA (ACRES) = 67799.0
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130613.30 FEET.

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 67799.0 TC (MIN.) = 117.66
EFFECTIVE AREA (ACRES) = 51295.71 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.927
PEAK FLOW RATE (CFS) = 41189.67

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20785.68	16.06	2.304	0.30 (0.24) 0.81	3120.9	10520.00	
2	21320.77	17.66	2.174	0.30 (0.24) 0.81	3457.4	10600.00	
3	22696.01	21.81	1.893	0.30 (0.24) 0.81	4321.7	10300.00	
4	22848.44	22.54	1.856	0.30 (0.24) 0.81	4488.5	10230.00	
5	22888.14	22.64	1.851	0.30 (0.24) 0.81	4514.4	10380.00	
6	23040.52	23.01	1.832	0.30 (0.24) 0.81	4613.5	10400.00	

7	23865.43	25.02	1.731	0.30 (0.24) 0.81	5148.5	10320.00
8	24102.51	25.60	1.707	0.30 (0.24) 0.81	5301.2	300.00
9	24563.70	27.08	1.645	0.30 (0.24) 0.81	5812.1	10360.00
10	25445.15	29.94	1.527	0.30 (0.24) 0.81	6787.0	10340.00
11	25883.66	31.37	1.496	0.30 (0.24) 0.81	7272.7	10200.00
12	25952.36	31.60	1.492	0.30 (0.24) 0.81	7348.7	10250.00
13	26337.03	32.86	1.467	0.30 (0.24) 0.81	7766.9	10500.00
14	27097.13	35.42	1.415	0.30 (0.24) 0.81	8592.2	10220.00
15	28096.75	38.74	1.348	0.30 (0.24) 0.81	9656.2	110.00
16	31389.31	51.71	1.149	0.30 (0.25) 0.82	15216.1	800.00
17	33498.20	64.21	1.021	0.30 (0.26) 0.86	21629.0	13600.00
18	35393.55	78.07	0.943	0.30 (0.26) 0.88	28393.5	13100.00
19	36323.70	84.30	0.907	0.30 (0.27) 0.89	31145.8	11801.00
20	38236.88	94.73	0.857	0.30 (0.27) 0.90	36467.9	11530.00
21	39020.73	100.58	0.836	0.30 (0.27) 0.91	40220.2	13510.00
22	39770.40	106.41	0.814	0.30 (0.27) 0.92	43840.3	13010.00
23	40821.33	113.00	0.789	0.30 (0.28) 0.92	48121.5	11350.00
24	41189.67	117.66	0.772	0.30 (0.28) 0.93	51295.7	11130.00
25	40755.30	123.76	0.755	0.30 (0.28) 0.93	54222.3	12300.00
26	39955.96	132.58	0.736	0.30 (0.28) 0.93	58482.9	12400.00
27	38883.70	142.17	0.715	0.30 (0.28) 0.94	61884.5	12201.00
28	37893.92	149.73	0.699	0.30 (0.28) 0.94	63777.5	12231.00
29	36870.46	157.29	0.683	0.30 (0.28) 0.94	65330.2	10400.00
30	35282.01	166.86	0.662	0.30 (0.28) 0.94	66776.6	12010.00
31	34222.32	172.34	0.650	0.30 (0.28) 0.94	67039.2	10210.00
32	33537.96	176.45	0.642	0.30 (0.28) 0.94	67186.0	12000.00
33	29803.90	203.15	0.612	0.30 (0.28) 0.94	67799.0	10100.00

=====
END OF RATIONAL METHOD ANALYSIS
=====

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2010 Advanced Engineering Software (aes)
Ver. 17.0 Release Date: 07/01/2010 License ID 1527

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 138 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 25-YR EV AUG 2023 ROKAMOTO *

FILE NAME: RU25EV38.DAT
TIME/DATE OF STUDY: 22:26 08/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 25.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 4.741
- 2) 10.00; 3.104
- 3) 15.00; 2.386
- 4) 20.00; 1.981
- 5) 25.00; 1.730
- 6) 30.00; 1.523
- 7) 40.00; 1.322
- 8) 50.00; 1.169
- 9) 60.00; 1.043
- 10) 90.00; 0.873
- 11) 120.00; 0.761
- 12) 180.00; 0.632
- 13) 360.00; 0.462
- 14) 1200.00; 0.202

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	(FT)	(FT)	SIDE / SIDE/ WAY	(FT)	(FT)	(FT)	(FT)	(n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU25EV37.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21320.77	17.66	0.30 (0.24)	0.81	3457.4	10600.00
2	23040.52	23.01	0.30 (0.24)	0.81	4613.5	10400.00
3	28096.75	38.74	0.30 (0.24)	0.81	9656.2	110.00
4	31389.31	51.71	0.30 (0.25)	0.82	15216.1	800.00
5	33498.20	64.21	0.30 (0.26)	0.86	21629.0	13600.00
6	35393.55	78.07	0.30 (0.26)	0.88	28393.5	13100.00
7	36323.70	84.30	0.30 (0.27)	0.89	31145.8	11801.00
8	38236.88	94.73	0.30 (0.27)	0.90	36467.9	11530.00
9	39020.73	100.58	0.30 (0.27)	0.91	40220.2	13510.00
10	39770.40	106.41	0.30 (0.27)	0.92	43840.3	13010.00
11	40821.33	113.00	0.30 (0.28)	0.92	48121.5	11350.00
12	41189.67	117.66	0.30 (0.28)	0.93	51295.7	11130.00
13	40755.30	123.76	0.30 (0.28)	0.93	54222.3	12010.00
14	39955.96	132.58	0.30 (0.28)	0.93	58482.9	12400.00
15	38883.70	142.17	0.30 (0.28)	0.94	61884.5	12201.00
16	37893.92	149.73	0.30 (0.28)	0.94	63777.5	12231.00
17	36870.46	157.29	0.30 (0.28)	0.94	65330.2	10400.00
18	35282.01	166.86	0.30 (0.28)	0.94	66776.6	12010.00
19	34222.32	172.34	0.30 (0.28)	0.94	67039.2	10210.00
20	29803.90	203.15	0.30 (0.28)	0.94	67799.0	10100.00
TOTAL AREA(ACRES) =						67799.0

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21320.77	17.66	0.30 (0.24)	0.81	3457.4	10600.00
2	23040.52	23.01	0.30 (0.24)	0.81	4613.5	10400.00
3	28096.75	38.74	0.30 (0.24)	0.81	9656.2	110.00
4	31389.31	51.71	0.30 (0.25)	0.82	15216.1	800.00
5	33498.20	64.21	0.30 (0.26)	0.86	21629.0	13600.00
6	35393.55	78.07	0.30 (0.26)	0.88	28393.5	13100.00
7	36323.70	84.30	0.30 (0.27)	0.89	31145.8	11801.00
8	38236.88	94.73	0.30 (0.27)	0.90	36467.9	11530.00
9	39020.73	100.58	0.30 (0.27)	0.91	40220.2	13510.00
10	39770.40	106.41	0.30 (0.27)	0.92	43840.3	13010.00
11	40821.33	113.00	0.30 (0.28)	0.92	48121.5	11350.00
12	41189.67	117.66	0.30 (0.28)	0.93	51295.7	11130.00
13	40755.30	123.76	0.30 (0.28)	0.93	54222.3	12300.00

14 39955.96 132.58 0.30(0.28) 0.93 58482.9 12400.00
 15 38883.70 142.17 0.30(0.28) 0.94 61884.5 12201.00
 16 37893.92 149.73 0.30(0.28) 0.94 63777.5 12231.00
 17 36870.46 157.29 0.30(0.28) 0.94 65330.2 10400.00
 18 35282.01 166.86 0.30(0.28) 0.94 66776.6 12010.00
 19 34222.32 172.34 0.30(0.28) 0.94 67039.2 10210.00
 20 29803.90 203.15 0.30(0.28) 0.94 67799.0 10100.00
 TOTAL AREA(ACRES) = 67799.0

FLOW PROCESS FROM NODE 13803.00 TO NODE 13820.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 134.99 DOWNSTREAM(FEET) = 134.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 926.91 CHANNEL SLOPE = 0.0011
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT(FEET) = 22.27

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.764

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	31.44	0.30	0.983	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.983

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 41196.30

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.78

AVERAGE FLOW DEPTH(FEET) = 22.27 TRAVEL TIME(MIN.) = 1.58

Tc(MIN.) = 119.24

SUBAREA AREA(ACRES) = 31.44 SUBAREA RUNOFF(CFS) = 13.27

EFFECTIVE AREA(ACRES) = 51327.15 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA(ACRES) = 67830.4 PEAK FLOW RATE(CFS) = 41189.67

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT(FEET) = 22.27

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 22.27 FLOW VELOCITY(FEET/SEC.) = 9.78

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13820.00 = 131540.20 FEET.

FLOW PROCESS FROM NODE 13803.00 TO NODE 13820.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

TOTAL NUMBER OF STREAMS = 2

CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:

TIME OF CONCENTRATION(MIN.) = 119.24

RAINFALL INTENSITY(INCH/HR) = 0.76

AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.93

EFFECTIVE STREAM AREA(ACRES) = 51327.15

TOTAL STREAM AREA(ACRES) = 67830.41

PEAK FLOW RATE(CFS) AT CONFLUENCE = 41189.67

FLOW PROCESS FROM NODE 13810.00 TO NODE 13811.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<

>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH(FEET) = 648.54

ELEVATION DATA: UPSTREAM(FEET) = 756.46 DOWNSTREAM(FEET) = 586.02

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20

SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 12.293

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.775

SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	-	5.58	0.30	1.000	65	12.29

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

SUBAREA RUNOFF(CFS) = 12.43

TOTAL AREA(ACRES) = 5.58 PEAK FLOW RATE(CFS) = 12.43

FLOW PROCESS FROM NODE 13811.00 TO NODE 13811.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 586.02 DOWNSTREAM(FEET) = 437.69
 CHANNEL LENGTH THRU SUBAREA(FEET) = 696.28 CHANNEL SLOPE = 0.2130
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 0.43

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.497

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	14.79	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 27.10

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.00

AVERAGE FLOW DEPTH(FEET) = 0.42 TRAVEL TIME(MIN.) = 1.93

Tc(MIN.) = 14.23

SUBAREA AREA(ACRES) = 14.79 SUBAREA RUNOFF(CFS) = 29.25

EFFECTIVE AREA(ACRES) = 20.37 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 20.4 PEAK FLOW RATE(CFS) = 40.28

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 0.53

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.53 FLOW VELOCITY(FEET/SEC.) = 6.88

LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13811.50 = 1344.82 FEET.

```

*****
FLOW PROCESS FROM NODE 13811.50 TO NODE 13812.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 437.69 DOWNSTREAM(FEET) = 402.36
CHANNEL LENGTH THRU SUBAREA(FEET) = 681.04 CHANNEL SLOPE = 0.0519
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.99
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.261
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS
LAND USE           GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED       -         18.41   0.30  1.000  -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 56.54
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.91
AVERAGE FLOW DEPTH(FEET) = 0.97 TRAVEL TIME(MIN.) = 2.31
Tc(MIN.) = 16.54
SUBAREA AREA(ACRES) = 18.41 SUBAREA RUNOFF(CFS) = 32.50
EFFECTIVE AREA(ACRES) = 38.78 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 38.8 PEAK FLOW RATE(CFS) = 68.45
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.08

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.08 FLOW VELOCITY(FEET/SEC.) = 5.21
LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13812.00 = 2025.86 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13812.00 TO NODE 13813.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 402.36 DOWNSTREAM(FEET) = 259.72
CHANNEL LENGTH THRU SUBAREA(FEET) = 1282.56 CHANNEL SLOPE = 0.1112
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.03
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.027
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS
LAND USE           GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED       -         27.87   0.30  0.858  -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.858
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 90.67
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.39
AVERAGE FLOW DEPTH(FEET) = 1.02 TRAVEL TIME(MIN.) = 2.89
Tc(MIN.) = 19.43
SUBAREA AREA(ACRES) = 27.87 SUBAREA RUNOFF(CFS) = 44.38
EFFECTIVE AREA(ACRES) = 66.65 AREA-AVERAGED Fm(INCH/HR) = 0.28

```

```

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94
TOTAL AREA(ACRES) = 66.7 PEAK FLOW RATE(CFS) = 104.66
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.11

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.11 FLOW VELOCITY(FEET/SEC.) = 7.72
LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13813.00 = 3308.42 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 31
-----

```

```

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<
=====

```

```

ELEVATION DATA: UPSTREAM(FEET) = 259.72 DOWNSTREAM(FEET) = 137.00
FLOW LENGTH(FEET) = 2412.88 MANNING'S N = 0.013
ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000
DEPTH OF FLOW IN 36.0 INCH PIPE IS 22.9 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 22.06
ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 104.66
PIPE TRAVEL TIME(MIN.) = 1.82 Tc(MIN.) = 21.26
LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13820.00 = 5721.30 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====

```

```

MAINLINE Tc(MIN.) = 21.26
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.918
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS
LAND USE           GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED       -         83.64   0.30  0.570  -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.570
SUBAREA AREA(ACRES) = 83.64 SUBAREA RUNOFF(CFS) = 131.50
EFFECTIVE AREA(ACRES) = 150.29 AREA-AVERAGED Fm(INCH/HR) = 0.22
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.73
TOTAL AREA(ACRES) = 150.3 PEAK FLOW RATE(CFS) = 229.62

```

```

*****
FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 1
-----

```

```

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<
=====

```

```

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 21.26
RAINFALL INTENSITY(INCH/HR) = 1.92
AREA-AVERAGED Fm(INCH/HR) = 0.22
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.73
EFFECTIVE STREAM AREA(ACRES) = 150.29

```

TOTAL STREAM AREA(ACRES) = 150.29
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 229.62

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21320.77	19.55	2.017	0.30 (0.24)	0.81	3488.8	10600.00
1	23040.52	24.86	1.737	0.30 (0.24)	0.81	4644.9	10400.00
1	28096.75	40.50	1.314	0.30 (0.24)	0.81	9687.7	110.00
1	31389.31	53.42	1.126	0.30 (0.25)	0.82	15247.6	800.00
1	33498.20	65.88	1.010	0.30 (0.26)	0.86	21660.4	13600.00
1	35393.55	79.72	0.931	0.30 (0.26)	0.88	28425.0	13100.00
1	36323.70	85.94	0.896	0.30 (0.27)	0.89	31177.2	11801.00
1	38236.88	96.34	0.849	0.30 (0.27)	0.90	36499.4	11530.00
1	39020.73	102.18	0.828	0.30 (0.27)	0.91	40251.7	13510.00
1	39770.40	108.00	0.806	0.30 (0.27)	0.92	43871.8	13010.00
1	40821.33	114.58	0.781	0.30 (0.28)	0.92	48152.9	11350.00
1	41189.67	119.24	0.764	0.30 (0.28)	0.93	51327.2	11130.00
1	40755.30	125.35	0.750	0.30 (0.28)	0.93	54253.7	12300.00
1	39955.96	134.18	0.731	0.30 (0.28)	0.93	58514.3	12400.00
1	38883.70	143.78	0.710	0.30 (0.28)	0.94	61915.9	12201.00
1	37893.92	151.35	0.694	0.30 (0.28)	0.94	63808.9	12231.00
1	36870.46	158.92	0.677	0.30 (0.28)	0.94	65361.7	10400.00
1	35282.01	168.51	0.657	0.30 (0.28)	0.94	66808.1	12010.00
1	34222.32	174.00	0.645	0.30 (0.28)	0.94	67070.6	10210.00
1	29803.90	204.88	0.609	0.30 (0.28)	0.94	67830.4	10100.00
2	229.62	21.26	1.918	0.30 (0.22)	0.73	150.3	13810.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21544.34	19.55	2.017	0.30 (0.24)	0.81	3627.0	10600.00
2	22102.57	21.26	1.918	0.30 (0.24)	0.81	4010.3	13810.00
3	23245.67	24.86	1.737	0.30 (0.24)	0.81	4795.2	10400.00
4	28244.74	40.50	1.314	0.30 (0.24)	0.81	9838.0	110.00
5	31511.82	53.42	1.126	0.30 (0.25)	0.82	15397.8	800.00
6	33604.98	65.88	1.010	0.30 (0.26)	0.86	21810.7	13600.00
7	35489.72	79.72	0.931	0.30 (0.26)	0.88	28575.3	13100.00
8	36415.10	85.94	0.896	0.30 (0.27)	0.89	31327.5	11801.00
9	38321.97	96.34	0.849	0.30 (0.27)	0.90	36649.7	11530.00
10	39102.87	102.18	0.828	0.30 (0.27)	0.91	40402.0	13510.00
11	39849.60	108.00	0.806	0.30 (0.27)	0.91	44022.1	13010.00
12	40897.21	114.58	0.781	0.30 (0.28)	0.92	48303.2	11350.00
13	41263.19	119.24	0.764	0.30 (0.28)	0.93	51477.4	11130.00
14	40826.89	125.35	0.750	0.30 (0.28)	0.93	54404.0	12300.00
15	40024.98	134.18	0.731	0.30 (0.28)	0.93	58664.6	12400.00
16	38949.93	143.78	0.710	0.30 (0.28)	0.94	62066.2	12201.00
17	37957.94	151.35	0.694	0.30 (0.28)	0.94	63959.2	12231.00
18	36932.29	158.92	0.677	0.30 (0.28)	0.94	65512.0	10400.00
19	35341.05	168.51	0.657	0.30 (0.28)	0.94	66958.4	12010.00
20	34279.76	174.00	0.645	0.30 (0.28)	0.94	67220.9	10210.00
21	29856.41	204.88	0.609	0.30 (0.28)	0.94	67980.7	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 41263.19 Tc(MIN.) = 119.24

EFFECTIVE AREA(ACRES) = 51477.44 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 67980.7
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13820.00 = 131540.20 FEET.

FLOW PROCESS FROM NODE 13820.00 TO NODE 13840.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 137.00 DOWNSTREAM(FEET) = 133.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 1261.34 CHANNEL SLOPE = 0.0032

GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT(FEET) = 16.95

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.760

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	31.60	0.30	0.683	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.683

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 41271.08

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 14.51

AVERAGE FLOW DEPTH(FEET) = 16.95 TRAVEL TIME(MIN.) = 1.45

Tc(MIN.) = 120.69

SUBAREA AREA(ACRES) = 31.60 SUBAREA RUNOFF(CFS) = 15.77

EFFECTIVE AREA(ACRES) = 51509.04 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA(ACRES) = 68012.3 PEAK FLOW RATE(CFS) = 41263.19

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT(FEET) = 16.95

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 16.95 FLOW VELOCITY(FEET/SEC.) = 14.51

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13840.00 = 132801.55 FEET.

FLOW PROCESS FROM NODE 13820.00 TO NODE 13840.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

TOTAL NUMBER OF STREAMS = 2

CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:

TIME OF CONCENTRATION(MIN.) = 120.69

RAINFALL INTENSITY(INCH/HR) = 0.76

AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.93

EFFECTIVE STREAM AREA(ACRES) = 51509.04

TOTAL STREAM AREA(ACRES) = 68012.30

PEAK FLOW RATE(CFS) AT CONFLUENCE = 41263.19

FLOW PROCESS FROM NODE 13830.00 TO NODE 13831.00 IS CODE = 21

```

-----
>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<
=====
INITIAL SUBAREA FLOW-LENGTH (FEET) = 744.71
ELEVATION DATA: UPSTREAM (FEET) = 1100.95 DOWNSTREAM (FEET) = 959.21

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 13.858
* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 2.550
SUBAREA Tc AND LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)
NATURAL FAIR COVER
"CHAPARRAL, BROADLEAF" - 5.06 0.30 1.000 65 13.86
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF (CFS) = 10.25
TOTAL AREA (ACRES) = 5.06 PEAK FLOW RATE (CFS) = 10.25

```

```

*****
FLOW PROCESS FROM NODE 13831.00 TO NODE 13832.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<
=====

```

```

ELEVATION DATA: UPSTREAM (FEET) = 959.21 DOWNSTREAM (FEET) = 832.83
CHANNEL LENGTH THRU SUBAREA (FEET) = 1076.71 CHANNEL SLOPE = 0.1174
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.65
* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 2.219
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 32.57 0.30 1.000 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 38.54
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.60
AVERAGE FLOW DEPTH (FEET) = 0.61 TRAVEL TIME (MIN.) = 3.21
Tc (MIN.) = 17.06
SUBAREA AREA (ACRES) = 32.57 SUBAREA RUNOFF (CFS) = 56.25
EFFECTIVE AREA (ACRES) = 37.63 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 37.6 PEAK FLOW RATE (CFS) = 64.99
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.83

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.83 FLOW VELOCITY (FEET/SEC.) = 6.73
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13832.00 = 1821.42 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13832.00 TO NODE 13833.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

```

```

>>>>TRAVELTIME THRU SUBAREA<<<<<
=====

```

```

ELEVATION DATA: UPSTREAM (FEET) = 832.83 DOWNSTREAM (FEET) = 572.49
CHANNEL LENGTH THRU SUBAREA (FEET) = 1883.58 CHANNEL SLOPE = 0.1382
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.97
* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.928
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 32.23 0.30 1.000 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 88.65
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.85
AVERAGE FLOW DEPTH (FEET) = 0.95 TRAVEL TIME (MIN.) = 4.00
Tc (MIN.) = 21.06
SUBAREA AREA (ACRES) = 32.23 SUBAREA RUNOFF (CFS) = 47.22
EFFECTIVE AREA (ACRES) = 69.86 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 69.9 PEAK FLOW RATE (CFS) = 102.34
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 1.03

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 1.03 FLOW VELOCITY (FEET/SEC.) = 8.27
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13833.00 = 3705.00 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13833.00 TO NODE 13834.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<
=====

```

```

ELEVATION DATA: UPSTREAM (FEET) = 572.49 DOWNSTREAM (FEET) = 471.65
CHANNEL LENGTH THRU SUBAREA (FEET) = 943.78 CHANNEL SLOPE = 0.1068
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 1.23
* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.829
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 27.51 0.30 1.000 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 121.28
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.01
AVERAGE FLOW DEPTH (FEET) = 1.22 TRAVEL TIME (MIN.) = 1.96
Tc (MIN.) = 23.03
SUBAREA AREA (ACRES) = 27.51 SUBAREA RUNOFF (CFS) = 37.86
EFFECTIVE AREA (ACRES) = 97.37 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 97.4 PEAK FLOW RATE (CFS) = 134.01
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

```

*ESTIMATED CHANNEL HEIGHT (FEET) = 1.29
END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 1.29 FLOW VELOCITY (FEET/SEC.) = 8.24
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13834.00 = 4648.78 FEET.

FLOW PROCESS FROM NODE 13834.00 TO NODE 13835.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 471.65 DOWNSTREAM (FEET) = 347.06
CHANNEL LENGTH THRU SUBAREA (FEET) = 1647.45 CHANNEL SLOPE = 0.0756
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT (FEET) = 1.77
* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.673

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	94.21	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 192.28

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.18

AVERAGE FLOW DEPTH (FEET) = 1.74 TRAVEL TIME (MIN.) = 3.36

Tc (MIN.) = 26.38

SUBAREA AREA (ACRES) = 94.21 SUBAREA RUNOFF (CFS) = 116.41

EFFECTIVE AREA (ACRES) = 191.58 AREA-AVERAGED Fm (INCH/HR) = 0.30

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA (ACRES) = 191.6 PEAK FLOW RATE (CFS) = 236.72

GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT (FEET) = 1.95

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 1.95 FLOW VELOCITY (FEET/SEC.) = 8.73

LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13835.00 = 6296.23 FEET.

FLOW PROCESS FROM NODE 13835.00 TO NODE 13836.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 347.06 DOWNSTREAM (FEET) = 269.29
CHANNEL LENGTH THRU SUBAREA (FEET) = 1696.71 CHANNEL SLOPE = 0.0458
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT (FEET) = 2.88

* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.531

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	233.25	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 366.16
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.28
AVERAGE FLOW DEPTH (FEET) = 2.83 TRAVEL TIME (MIN.) = 3.42
Tc (MIN.) = 29.80
SUBAREA AREA (ACRES) = 233.25 SUBAREA RUNOFF (CFS) = 258.52
EFFECTIVE AREA (ACRES) = 424.83 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 424.8 PEAK FLOW RATE (CFS) = 470.85
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 3.22

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 3.22 FLOW VELOCITY (FEET/SEC.) = 8.89

LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13836.00 = 7992.94 FEET.

FLOW PROCESS FROM NODE 13836.00 TO NODE 13837.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 269.29 DOWNSTREAM (FEET) = 191.87
CHANNEL LENGTH THRU SUBAREA (FEET) = 2529.21 CHANNEL SLOPE = 0.0306
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT (FEET) = 3.86

* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.421

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	134.70	0.30	0.880	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.880

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 540.99

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.98

AVERAGE FLOW DEPTH (FEET) = 3.83 TRAVEL TIME (MIN.) = 5.28

Tc (MIN.) = 35.08

SUBAREA AREA (ACRES) = 134.70 SUBAREA RUNOFF (CFS) = 140.27

EFFECTIVE AREA (ACRES) = 559.53 AREA-AVERAGED Fm (INCH/HR) = 0.29

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97

TOTAL AREA (ACRES) = 559.5 PEAK FLOW RATE (CFS) = 568.89

GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT (FEET) = 3.93

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 3.93 FLOW VELOCITY (FEET/SEC.) = 8.09

LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13837.00 = 10522.15 FEET.

FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 191.87 DOWNSTREAM (FEET) = 133.00
FLOW LENGTH (FEET) = 1151.02 MANNING'S N = 0.013

DEPTH OF FLOW IN 63.0 INCH PIPE IS 46.5 INCHES
 PIPE-FLOW VELOCITY (FEET/SEC.) = 33.24
 ESTIMATED PIPE DIAMETER (INCH) = 63.00 NUMBER OF PIPES = 1
 PIPE-FLOW (CFS) = 568.89
 PIPE TRAVEL TIME (MIN.) = 0.58 Tc (MIN.) = 35.65
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13840.00 = 11673.17 FEET.

 FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) = 35.65
 * 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.409
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.97	0.30	0.622	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.622
 SUBAREA AREA (ACRES) = 5.97 SUBAREA RUNOFF (CFS) = 6.57
 EFFECTIVE AREA (ACRES) = 565.50 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA (ACRES) = 565.5 PEAK FLOW RATE (CFS) = 569.62

 FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<

=====

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
 TIME OF CONCENTRATION (MIN.) = 35.65
 RAINFALL INTENSITY (INCH/HR) = 1.41
 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.97
 EFFECTIVE STREAM AREA (ACRES) = 565.50
 TOTAL STREAM AREA (ACRES) = 565.50
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 569.62

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21544.34	21.30	1.916	0.30 (0.24)	0.80	3658.6	10600.00
1	22102.57	22.99	1.831	0.30 (0.24)	0.80	4041.9	13810.00
1	23245.67	26.57	1.665	0.30 (0.24)	0.81	4826.8	10400.00
1	28244.74	42.11	1.290	0.30 (0.24)	0.81	9869.6	110.00
1	31511.82	54.98	1.106	0.30 (0.25)	0.82	15429.4	800.00
1	33604.98	67.42	1.001	0.30 (0.26)	0.86	21842.3	13600.00
1	35489.72	81.23	0.923	0.30 (0.26)	0.88	28606.9	13100.00
1	36415.10	87.44	0.888	0.30 (0.27)	0.89	31359.1	11801.00
1	38321.97	97.82	0.844	0.30 (0.27)	0.90	36681.3	11530.00
1	39102.87	103.65	0.822	0.30 (0.27)	0.91	40433.6	13510.00
1	39849.60	109.46	0.800	0.30 (0.27)	0.91	44053.7	13010.00
1	40897.21	116.03	0.776	0.30 (0.28)	0.92	48334.8	11350.00
1	41263.19	120.69	0.760	0.30 (0.28)	0.93	51509.0	11130.00

1	40826.89	126.80	0.746	0.30 (0.28)	0.93	54435.6	12300.00
1	40024.98	135.64	0.727	0.30 (0.28)	0.93	58696.2	12400.00
1	38949.93	145.25	0.707	0.30 (0.28)	0.94	62097.8	12201.00
1	37957.94	152.83	0.690	0.30 (0.28)	0.94	63990.8	12231.00
1	36932.29	160.41	0.674	0.30 (0.28)	0.94	65543.6	10400.00
1	35341.05	170.02	0.653	0.30 (0.28)	0.94	66990.0	12010.00
1	34279.76	175.53	0.642	0.30 (0.28)	0.94	67252.5	10210.00
1	29856.41	206.47	0.607	0.30 (0.28)	0.94	68012.3	10100.00
2	569.62	35.65	1.409	0.30 (0.29)	0.97	565.5	13830.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22038.59	21.30	1.916	0.30 (0.25)	0.82	3996.4	10600.00
2	22608.21	22.99	1.831	0.30 (0.25)	0.82	4406.5	13810.00
3	23767.12	26.57	1.665	0.30 (0.25)	0.82	5248.2	10400.00
4	26737.09	35.65	1.409	0.30 (0.25)	0.82	8339.6	13830.00
5	28753.44	42.11	1.290	0.30 (0.24)	0.82	10435.1	110.00
6	31927.17	54.98	1.106	0.30 (0.25)	0.82	15994.9	800.00
7	33966.75	67.42	1.001	0.30 (0.26)	0.86	22407.8	13600.00
8	35811.66	81.23	0.923	0.30 (0.26)	0.88	29172.4	13100.00
9	36719.12	87.44	0.888	0.30 (0.27)	0.89	31924.6	11801.00
10	38603.75	97.82	0.844	0.30 (0.27)	0.90	37246.8	11530.00
11	39373.56	103.65	0.822	0.30 (0.27)	0.91	40999.1	13510.00
12	40109.25	109.46	0.800	0.30 (0.27)	0.92	44619.2	13010.00
13	41144.39	116.03	0.776	0.30 (0.28)	0.92	48900.3	11350.00
14	41502.07	120.69	0.760	0.30 (0.28)	0.93	52074.5	11130.00
15	41059.08	126.80	0.746	0.30 (0.28)	0.93	55001.1	12300.00
16	40247.51	135.64	0.727	0.30 (0.28)	0.93	59261.7	12400.00
17	39161.93	145.25	0.707	0.30 (0.28)	0.94	62663.3	12201.00
18	38161.65	152.83	0.690	0.30 (0.28)	0.94	64556.3	12231.00
19	37127.70	160.41	0.674	0.30 (0.28)	0.94	66109.1	10400.00
20	35525.95	170.02	0.653	0.30 (0.28)	0.94	67555.5	12010.00
21	34458.64	175.53	0.642	0.30 (0.28)	0.94	67818.0	10210.00
22	30017.67	206.47	0.607	0.30 (0.28)	0.94	68577.8	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 41502.07 Tc (MIN.) = 120.69
 EFFECTIVE AREA (ACRES) = 52074.54 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA (ACRES) = 68577.8
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13840.00 = 132801.55 FEET.

 FLOW PROCESS FROM NODE 13840.00 TO NODE 13860.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 133.00 DOWNSTREAM (FEET) = 130.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 654.44 CHANNEL SLOPE = 0.0046
 GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT (FEET) = 15.46
 * 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.758

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	6.61	0.30	0.975	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.975
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 41503.46
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 16.59
AVERAGE FLOW DEPTH(FEET) = 15.46 TRAVEL TIME(MIN.) = 0.66
Tc(MIN.) = 121.35
SUBAREA AREA(ACRES) = 6.61 SUBAREA RUNOFF(CFS) = 2.77
EFFECTIVE AREA(ACRES) = 52081.15 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 68584.4 PEAK FLOW RATE(CFS) = 41502.07
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 15.46

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 15.46 FLOW VELOCITY(FEET/SEC.) = 16.59
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13860.00 = 133455.98 FEET.

FLOW PROCESS FROM NODE 13840.00 TO NODE 13860.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION(MIN.) = 121.35
RAINFALL INTENSITY(INCH/HR) = 0.76
AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.93
EFFECTIVE STREAM AREA(ACRES) = 52081.15
TOTAL STREAM AREA(ACRES) = 68584.41
PEAK FLOW RATE(CFS) AT CONFLUENCE = 41502.07

FLOW PROCESS FROM NODE 13850.00 TO NODE 13851.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH(FEET) = 617.57
ELEVATION DATA: UPSTREAM(FEET) = 646.95 DOWNSTREAM(FEET) = 490.10

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 12.137
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.797
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	-	4.95	0.30	1.000	65	12.14

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

SUBAREA RUNOFF(CFS) = 11.12
TOTAL AREA(ACRES) = 4.95 PEAK FLOW RATE(CFS) = 11.12

FLOW PROCESS FROM NODE 13851.00 TO NODE 13851.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 490.10 DOWNSTREAM(FEET) = 440.98
CHANNEL LENGTH THRU SUBAREA(FEET) = 351.14 CHANNEL SLOPE = 0.1399
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.34
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.598

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	4.02	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 15.29
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.23
AVERAGE FLOW DEPTH(FEET) = 0.34 TRAVEL TIME(MIN.) = 1.38
Tc(MIN.) = 13.52
SUBAREA AREA(ACRES) = 4.02 SUBAREA RUNOFF(CFS) = 8.32
EFFECTIVE AREA(ACRES) = 8.97 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 9.0 PEAK FLOW RATE(CFS) = 18.56
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.38

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.38 FLOW VELOCITY(FEET/SEC.) = 4.58
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13851.50 = 968.71 FEET.

FLOW PROCESS FROM NODE 13851.50 TO NODE 13852.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 440.98 DOWNSTREAM(FEET) = 395.76
CHANNEL LENGTH THRU SUBAREA(FEET) = 512.91 CHANNEL SLOPE = 0.0882
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.53
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.349

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.17	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 25.17
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.42
AVERAGE FLOW DEPTH(FEET) = 0.52 TRAVEL TIME(MIN.) = 1.93

Tc(MIN.) = 15.45
SUBAREA AREA(ACRES) = 7.17 SUBAREA RUNOFF(CFS) = 13.22
EFFECTIVE AREA(ACRES) = 16.14 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 16.1 PEAK FLOW RATE(CFS) = 29.77
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.57

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.57 FLOW VELOCITY(FEET/SEC.) = 4.69
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13852.00 = 1481.62 FEET.

FLOW PROCESS FROM NODE 13852.00 TO NODE 13853.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 395.76 DOWNSTREAM(FEET) = 354.94
CHANNEL LENGTH THRU SUBAREA(FEET) = 443.69 CHANNEL SLOPE = 0.0920
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.63

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.230

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 6.76 0.30 1.000 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 35.64
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.04
AVERAGE FLOW DEPTH(FEET) = 0.63 TRAVEL TIME(MIN.) = 1.47
Tc(MIN.) = 16.92

SUBAREA AREA(ACRES) = 6.76 SUBAREA RUNOFF(CFS) = 11.74
EFFECTIVE AREA(ACRES) = 22.90 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 22.9 PEAK FLOW RATE(CFS) = 39.79
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.67

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.67 FLOW VELOCITY(FEET/SEC.) = 5.25
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13853.00 = 1925.31 FEET.

FLOW PROCESS FROM NODE 13853.00 TO NODE 13854.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 354.94 DOWNSTREAM(FEET) = 263.57
CHANNEL LENGTH THRU SUBAREA(FEET) = 962.09 CHANNEL SLOPE = 0.0950
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.81

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.009
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 18.16 0.30 1.000 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 53.77
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.87
AVERAGE FLOW DEPTH(FEET) = 0.79 TRAVEL TIME(MIN.) = 2.73
Tc(MIN.) = 19.65
SUBAREA AREA(ACRES) = 18.16 SUBAREA RUNOFF(CFS) = 27.94
EFFECTIVE AREA(ACRES) = 41.06 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 41.1 PEAK FLOW RATE(CFS) = 63.16
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.87

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.87 FLOW VELOCITY(FEET/SEC.) = 6.21
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13854.00 = 2887.40 FEET.

FLOW PROCESS FROM NODE 13854.00 TO NODE 13855.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 263.57 DOWNSTREAM(FEET) = 188.74
CHANNEL LENGTH THRU SUBAREA(FEET) = 1228.77 CHANNEL SLOPE = 0.0609
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.23

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.828

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 38.75 0.30 0.879 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.879
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 90.46
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.02
AVERAGE FLOW DEPTH(FEET) = 1.21 TRAVEL TIME(MIN.) = 3.40
Tc(MIN.) = 23.06

SUBAREA AREA(ACRES) = 38.75 SUBAREA RUNOFF(CFS) = 54.54
EFFECTIVE AREA(ACRES) = 79.81 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94
TOTAL AREA(ACRES) = 79.8 PEAK FLOW RATE(CFS) = 111.00
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.36

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.36 FLOW VELOCITY(FEET/SEC.) = 6.41
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13855.00 = 4116.17 FEET.

FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 31

 >>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

 ELEVATION DATA: UPSTREAM(FEET) = 188.74 DOWNSTREAM(FEET) = 130.00
 FLOW LENGTH(FEET) = 2092.67 MANNING'S N = 0.013
 DEPTH OF FLOW IN 39.0 INCH PIPE IS 27.5 INCHES
 PIPE-FLOW VELOCITY(FEET/SEC.) = 17.74
 ESTIMATED PIPE DIAMETER(INCH) = 39.00 NUMBER OF PIPES = 1
 PIPE-FLOW(CFS) = 111.00
 PIPE TRAVEL TIME(MIN.) = 1.97 Tc(MIN.) = 25.02
 LONGEST FLOWPATH FROM NODE 13855.00 TO NODE 13860.00 = 6208.84 FEET.

 FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

 MAINLINE Tc(MIN.) = 25.02
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.729
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 43.41 0.30 0.707 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.707
 SUBAREA AREA(ACRES) = 43.41 SUBAREA RUNOFF(CFS) = 59.27
 EFFECTIVE AREA(ACRES) = 123.22 AREA-AVERAGED Fm(INCH/HR) = 0.26
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.86
 TOTAL AREA(ACRES) = 123.2 PEAK FLOW RATE(CFS) = 163.19

 FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

 TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
 TIME OF CONCENTRATION(MIN.) = 25.02
 RAINFALL INTENSITY(INCH/HR) = 1.73
 AREA-AVERAGED Fm(INCH/HR) = 0.26
 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.86
 EFFECTIVE STREAM AREA(ACRES) = 123.22
 TOTAL STREAM AREA(ACRES) = 123.22
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 163.19

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22038.59	22.09	1.876	0.30(0.25)	0.82	4003.1	10600.00
1	22608.21	23.77	1.792	0.30(0.25)	0.82	4413.1	13810.00
1	23767.12	27.34	1.633	0.30(0.25)	0.82	5254.8	10400.00
1	26737.09	36.40	1.394	0.30(0.25)	0.82	8346.3	13830.00
1	28753.44	42.84	1.279	0.30(0.24)	0.82	10441.7	110.00
1	31927.17	55.69	1.097	0.30(0.25)	0.82	16001.6	800.00

1	33966.75	68.11	0.997	0.30(0.26)	0.86	22414.4	13600.00
1	35811.66	81.91	0.919	0.30(0.26)	0.88	29179.0	13100.00
1	36719.12	88.12	0.884	0.30(0.27)	0.89	31931.2	11801.00
1	38603.75	98.49	0.841	0.30(0.27)	0.90	37253.4	11530.00
1	39373.56	104.32	0.820	0.30(0.27)	0.91	41005.7	13510.00
1	40109.25	110.13	0.798	0.30(0.27)	0.92	44625.8	13010.00
1	41144.39	116.69	0.773	0.30(0.28)	0.92	48906.9	11350.00
1	41502.07	121.35	0.758	0.30(0.28)	0.93	52081.2	11130.00
1	41059.08	127.46	0.745	0.30(0.28)	0.93	55007.7	12300.00
1	40247.51	136.30	0.726	0.30(0.28)	0.93	59268.3	12400.00
1	39161.93	145.92	0.705	0.30(0.28)	0.94	62669.9	12201.00
1	38161.65	153.50	0.689	0.30(0.28)	0.94	64562.9	12231.00
1	37127.70	161.09	0.673	0.30(0.28)	0.94	66115.7	10400.00
1	35525.95	170.71	0.652	0.30(0.28)	0.94	67562.1	12010.00
1	34458.64	176.22	0.640	0.30(0.28)	0.94	67824.6	10210.00
1	30017.67	207.19	0.606	0.30(0.28)	0.94	68584.4	10100.00
2	163.19	25.02	1.729	0.30(0.26)	0.86	123.2	13850.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22197.05	22.09	1.876	0.30(0.25)	0.82	4111.8	10600.00
2	22769.85	23.77	1.792	0.30(0.25)	0.82	4530.2	13810.00
3	23176.57	25.02	1.729	0.30(0.25)	0.82	4830.6	13850.00
4	23919.66	27.34	1.633	0.30(0.25)	0.82	5378.1	10400.00
5	26863.16	36.40	1.394	0.30(0.25)	0.82	8469.5	13830.00
6	28866.66	42.84	1.279	0.30(0.24)	0.82	10564.9	110.00
7	32020.29	55.69	1.097	0.30(0.25)	0.82	16124.8	800.00
8	34048.75	68.11	0.997	0.30(0.26)	0.86	22537.7	13600.00
9	35884.99	81.91	0.919	0.30(0.26)	0.88	29302.2	13100.00
10	36788.55	88.12	0.884	0.30(0.27)	0.89	32054.5	11801.00
11	38668.49	98.49	0.841	0.30(0.27)	0.90	37376.6	11530.00
12	39435.89	104.32	0.820	0.30(0.27)	0.91	41128.9	13510.00
13	40169.17	110.13	0.798	0.30(0.27)	0.92	44749.0	13010.00
14	41201.59	116.69	0.773	0.30(0.28)	0.92	49030.2	11350.00
15	41557.58	121.35	0.758	0.30(0.28)	0.93	52204.4	11130.00
16	41113.13	127.46	0.745	0.30(0.28)	0.93	55131.0	12300.00
17	40299.45	136.30	0.726	0.30(0.28)	0.93	59391.6	12400.00
18	39211.58	145.92	0.705	0.30(0.28)	0.94	62793.1	12201.00
19	38209.49	153.50	0.689	0.30(0.28)	0.94	64686.2	12231.00
20	37173.73	161.09	0.673	0.30(0.28)	0.94	66238.9	10400.00
21	35569.68	170.71	0.652	0.30(0.28)	0.94	67685.3	12010.00
22	34501.06	176.22	0.640	0.30(0.28)	0.94	67947.9	10210.00
23	30056.34	207.19	0.606	0.30(0.28)	0.94	68707.6	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
 PEAK FLOW RATE(CFS) = 41557.58 Tc(MIN.) = 121.35
 EFFECTIVE AREA(ACRES) = 52204.37 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 68707.6
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13860.00 = 133455.98 FEET.

 FLOW PROCESS FROM NODE 13860.00 TO NODE 13880.00 IS CODE = 56

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 130.00 DOWNSTREAM(FEET) = 120.57
CHANNEL LENGTH THRU SUBAREA(FEET) = 610.77 CHANNEL SLOPE = 0.0154
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 11.23
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.757
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 4.89 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 41558.59
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 25.54
AVERAGE FLOW DEPTH(FEET) = 11.23 TRAVEL TIME(MIN.) = 0.40
Tc(MIN.) = 121.75
SUBAREA AREA(ACRES) = 4.89 SUBAREA RUNOFF(CFS) = 2.01
EFFECTIVE AREA(ACRES) = 52209.26 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 68712.5 PEAK FLOW RATE(CFS) = 41557.58
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 11.23

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 11.23 FLOW VELOCITY(FEET/SEC.) = 25.54
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13880.00 = 134066.75 FEET.

*****
FLOW PROCESS FROM NODE 13860.00 TO NODE 13880.00 IS CODE = 1
-----
>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
=====
TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION(MIN.) = 121.75
RAINFALL INTENSITY(INCH/HR) = 0.76
AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.93
EFFECTIVE STREAM AREA(ACRES) = 52209.26
TOTAL STREAM AREA(ACRES) = 68712.52
PEAK FLOW RATE(CFS) AT CONFLUENCE = 41557.58

*****
FLOW PROCESS FROM NODE 13870.00 TO NODE 13871.00 IS CODE = 21
-----
>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<
=====
INITIAL SUBAREA FLOW-LENGTH(FEET) = 872.65
ELEVATION DATA: UPSTREAM(FEET) = 558.52 DOWNSTREAM(FEET) = 436.47

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20

```

```

SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 15.704
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.329
SUBAREA Tc AND LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)
NATURAL FAIR COVER
"GRASS" - 7.32 0.30 1.000 65 15.70
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 13.37
TOTAL AREA(ACRES) = 7.32 PEAK FLOW RATE(CFS) = 13.37

*****
FLOW PROCESS FROM NODE 13871.00 TO NODE 13872.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 436.47 DOWNSTREAM(FEET) = 337.62
CHANNEL LENGTH THRU SUBAREA(FEET) = 827.95 CHANNEL SLOPE = 0.1194
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.48
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.094
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 13.01 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 23.90
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.75
AVERAGE FLOW DEPTH(FEET) = 0.46 TRAVEL TIME(MIN.) = 2.91
Tc(MIN.) = 18.61
SUBAREA AREA(ACRES) = 13.01 SUBAREA RUNOFF(CFS) = 21.00
EFFECTIVE AREA(ACRES) = 20.33 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 20.3 PEAK FLOW RATE(CFS) = 32.82
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.55

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.55 FLOW VELOCITY(FEET/SEC.) = 5.33
LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13872.00 = 1700.60 FEET.

*****
FLOW PROCESS FROM NODE 13872.00 TO NODE 13873.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 337.62 DOWNSTREAM(FEET) = 253.88
CHANNEL LENGTH THRU SUBAREA(FEET) = 1049.16 CHANNEL SLOPE = 0.0798
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.88
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.895

```

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	32.99	0.30	0.923	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.923
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 56.89
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.65
AVERAGE FLOW DEPTH(FEET) = 0.86 TRAVEL TIME(MIN.) = 3.10
Tc(MIN.) = 21.70
SUBAREA AREA(ACRES) = 32.99 SUBAREA RUNOFF(CFS) = 48.06
EFFECTIVE AREA(ACRES) = 53.32 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
TOTAL AREA(ACRES) = 53.3 PEAK FLOW RATE(CFS) = 77.25
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.03

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.03 FLOW VELOCITY(FEET/SEC.) = 6.25
LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13873.00 = 2749.76 FEET.

FLOW PROCESS FROM NODE 13873.00 TO NODE 13874.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 253.88 DOWNSTREAM(FEET) = 160.73
CHANNEL LENGTH THRU SUBAREA(FEET) = 1518.60 CHANNEL SLOPE = 0.0613
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.01
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.739
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	30.94	0.30	0.900	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.900
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 97.73
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.12
AVERAGE FLOW DEPTH(FEET) = 1.00 TRAVEL TIME(MIN.) = 3.12
Tc(MIN.) = 24.82
SUBAREA AREA(ACRES) = 30.94 SUBAREA RUNOFF(CFS) = 40.91
EFFECTIVE AREA(ACRES) = 84.26 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 84.3 PEAK FLOW RATE(CFS) = 110.65
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.07

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.07 FLOW VELOCITY(FEET/SEC.) = 8.49
LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13874.00 = 4268.36 FEET.

FLOW PROCESS FROM NODE 13874.00 TO NODE 13875.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 160.73 DOWNSTREAM(FEET) = 158.14
CHANNEL LENGTH THRU SUBAREA(FEET) = 582.74 CHANNEL SLOPE = 0.0044
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.72
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.631
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	73.67	0.30	0.930	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.930
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 155.49
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.76
AVERAGE FLOW DEPTH(FEET) = 2.69 TRAVEL TIME(MIN.) = 2.58
Tc(MIN.) = 27.40
SUBAREA AREA(ACRES) = 73.67 SUBAREA RUNOFF(CFS) = 89.62
EFFECTIVE AREA(ACRES) = 157.93 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 157.9 PEAK FLOW RATE(CFS) = 192.04
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 3.00

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 3.00 FLOW VELOCITY(FEET/SEC.) = 4.00
LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13875.00 = 4851.10 FEET.

FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 158.14 DOWNSTREAM(FEET) = 120.57
FLOW LENGTH(FEET) = 1855.67 MANNING'S N = 0.013
DEPTH OF FLOW IN 48.0 INCH PIPE IS 38.9 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 17.59
ESTIMATED PIPE DIAMETER(INCH) = 48.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 192.04
PIPE TRAVEL TIME(MIN.) = 1.76 Tc(MIN.) = 29.16
LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13880.00 = 6706.77 FEET.

FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 29.16
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.558
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	34.90	0.30	0.743	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.743
 SUBAREA AREA(ACRES) = 34.90 SUBAREA RUNOFF(CFS) = 41.93
 EFFECTIVE AREA(ACRES) = 192.83 AREA-AVERAGED Fm(INCH/HR) = 0.27
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.90
 TOTAL AREA(ACRES) = 192.8 PEAK FLOW RATE(CFS) = 223.63

 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
 TIME OF CONCENTRATION(MIN.) = 29.16
 RAINFALL INTENSITY(INCH/HR) = 1.56
 AREA-AVERAGED Fm(INCH/HR) = 0.27
 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.90
 EFFECTIVE STREAM AREA(ACRES) = 192.83
 TOTAL STREAM AREA(ACRES) = 192.83
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 223.63

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22197.05	22.57	1.852	0.30(0.25)	0.82	4116.7	10600.00
1	22769.85	24.25	1.768	0.30(0.25)	0.82	4535.1	13810.00
1	23176.57	25.50	1.709	0.30(0.25)	0.82	4835.5	13850.00
1	23919.66	27.81	1.614	0.30(0.25)	0.82	5382.9	10400.00
1	26863.16	36.85	1.385	0.30(0.25)	0.82	8474.4	13830.00
1	28866.66	43.29	1.272	0.30(0.24)	0.82	10569.8	110.00
1	32020.29	56.12	1.092	0.30(0.25)	0.82	16129.7	800.00
1	34048.75	68.53	0.995	0.30(0.26)	0.86	22542.5	13600.00
1	35884.99	82.33	0.916	0.30(0.26)	0.88	29307.1	13100.00
1	36788.55	88.53	0.881	0.30(0.27)	0.89	32059.4	11801.00
1	38668.49	98.90	0.840	0.30(0.27)	0.90	37381.5	11530.00
1	39435.89	104.72	0.818	0.30(0.27)	0.91	41133.8	13510.00
1	40169.17	110.53	0.796	0.30(0.27)	0.92	44753.9	13010.00
1	41201.59	117.09	0.772	0.30(0.28)	0.92	49035.0	11350.00
1	41557.58	121.75	0.757	0.30(0.28)	0.93	52209.3	11130.00
1	41113.13	127.86	0.744	0.30(0.28)	0.93	55135.8	12300.00
1	40299.45	136.70	0.725	0.30(0.28)	0.93	59396.4	12400.00
1	39211.58	146.33	0.704	0.30(0.28)	0.94	62798.0	12201.00
1	38209.49	153.91	0.688	0.30(0.28)	0.94	64691.0	12231.00
1	37173.73	161.51	0.672	0.30(0.28)	0.94	66243.8	10400.00
1	35569.68	171.13	0.651	0.30(0.28)	0.94	67690.2	12010.00
1	34501.06	176.64	0.639	0.30(0.28)	0.94	67952.8	10210.00
1	30056.34	207.63	0.606	0.30(0.28)	0.94	68712.5	10100.00
2	223.63	29.16	1.558	0.30(0.27)	0.90	192.8	13870.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22197.05	22.57	1.852	0.30(0.25)	0.82	4116.7	10600.00
1	22769.85	24.25	1.768	0.30(0.25)	0.82	4535.1	13810.00
1	23176.57	25.50	1.709	0.30(0.25)	0.82	4835.5	13850.00
1	23919.66	27.81	1.614	0.30(0.25)	0.82	5382.9	10400.00
1	26863.16	36.85	1.385	0.30(0.25)	0.82	8474.4	13830.00
1	28866.66	43.29	1.272	0.30(0.24)	0.82	10569.8	110.00
1	32020.29	56.12	1.092	0.30(0.25)	0.82	16129.7	800.00
1	34048.75	68.53	0.995	0.30(0.26)	0.86	22542.5	13600.00
1	35884.99	82.33	0.916	0.30(0.26)	0.88	29307.1	13100.00
1	36788.55	88.53	0.881	0.30(0.27)	0.89	32059.4	11801.00
1	38668.49	98.90	0.840	0.30(0.27)	0.90	37381.5	11530.00
1	39435.89	104.72	0.818	0.30(0.27)	0.91	41133.8	13510.00
1	40169.17	110.53	0.796	0.30(0.27)	0.92	44753.9	13010.00
1	41201.59	117.09	0.772	0.30(0.28)	0.92	49035.0	11350.00
1	41557.58	121.75	0.757	0.30(0.28)	0.93	52209.3	11130.00
1	41113.13	127.86	0.744	0.30(0.28)	0.93	55135.8	12300.00
1	40299.45	136.70	0.725	0.30(0.28)	0.93	59396.4	12400.00
1	39211.58	146.33	0.704	0.30(0.28)	0.94	62798.0	12201.00
1	38209.49	153.91	0.688	0.30(0.28)	0.94	64691.0	12231.00
1	37173.73	161.51	0.672	0.30(0.28)	0.94	66243.8	10400.00
1	35569.68	171.13	0.651	0.30(0.28)	0.94	67690.2	12010.00
1	34501.06	176.64	0.639	0.30(0.28)	0.94	67952.8	10210.00
1	30056.34	207.63	0.606	0.30(0.28)	0.94	68712.5	10100.00
2	223.63	29.16	1.558	0.30(0.27)	0.90	192.8	13870.00

1	22409.66	22.57	1.852	0.30(0.25)	0.82	4266.0	10600.00
2	22986.11	24.25	1.768	0.30(0.25)	0.82	4695.5	13810.00
3	23395.11	25.50	1.709	0.30(0.25)	0.82	5004.1	13850.00
4	24142.19	27.81	1.614	0.30(0.25)	0.82	5566.9	10400.00
5	24582.11	29.16	1.558	0.30(0.25)	0.82	6036.6	13870.00
6	27056.84	36.85	1.385	0.30(0.25)	0.82	8667.2	13830.00
7	29040.64	43.29	1.272	0.30(0.25)	0.82	10762.6	110.00
8	32163.07	56.12	1.092	0.30(0.25)	0.82	16322.5	800.00
9	34174.65	68.53	0.995	0.30(0.26)	0.86	22735.4	13600.00
10	35997.32	82.33	0.916	0.30(0.26)	0.88	29499.9	13100.00
11	36894.78	88.53	0.881	0.30(0.27)	0.89	32252.2	11801.00
12	38767.51	98.90	0.840	0.30(0.27)	0.90	37574.3	11530.00
13	39531.14	104.72	0.818	0.30(0.27)	0.91	41326.6	13510.00
14	40260.66	110.53	0.796	0.30(0.27)	0.91	44946.7	13010.00
15	41288.82	117.09	0.772	0.30(0.28)	0.92	49227.9	11350.00
16	41642.28	121.75	0.757	0.30(0.28)	0.93	52402.1	11130.00
17	41195.55	127.86	0.744	0.30(0.28)	0.93	55328.7	12300.00
18	40378.57	136.70	0.725	0.30(0.28)	0.93	59589.3	12400.00
19	39287.11	146.33	0.704	0.30(0.28)	0.94	62990.9	12201.00
20	38282.19	153.91	0.688	0.30(0.28)	0.94	64883.9	12231.00
21	37243.59	161.51	0.672	0.30(0.28)	0.94	66436.6	10400.00
22	35635.96	171.13	0.651	0.30(0.28)	0.94	67883.0	12010.00
23	34565.28	176.64	0.639	0.30(0.28)	0.94	68145.6	10210.00
24	30114.78	207.63	0.606	0.30(0.28)	0.94	68905.3	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 41642.28 Tc(MIN.) = 121.75
 EFFECTIVE AREA(ACRES) = 52402.09 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 68905.3
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13880.00 = 134066.75 FEET.

 FLOW PROCESS FROM NODE 13880.00 TO NODE 13910.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 120.57 DOWNSTREAM(FEET) = 119.70
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1190.21 CHANNEL SLOPE = 0.0007
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 24.59
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.752

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/	SCS SOIL	AREA	Fp	Ap	SCS
LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
USER-DEFINED	-	117.69	0.30	0.724	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.724
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 41670.62
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.54
 AVERAGE FLOW DEPTH(FEET) = 24.59 TRAVEL TIME(MIN.) = 2.32
 Tc(MIN.) = 124.07

SUBAREA AREA(ACRES) = 117.69 SUBAREA RUNOFF(CFS) = 56.68
 EFFECTIVE AREA(ACRES) = 52519.78 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 69023.0 PEAK FLOW RATE(CFS) = 41642.28

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 24.58

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 24.58 FLOW VELOCITY (FEET/SEC.) = 8.54
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13910.00 = 135256.95 FEET.

FLOW PROCESS FROM NODE 13880.00 TO NODE 13910.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

=====

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION (MIN.) = 124.07
RAINFALL INTENSITY (INCH/HR) = 0.75
AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.93
EFFECTIVE STREAM AREA (ACRES) = 52519.78
TOTAL STREAM AREA (ACRES) = 69023.03
PEAK FLOW RATE (CFS) AT CONFLUENCE = 41642.28

FLOW PROCESS FROM NODE 13889.00 TO NODE 13890.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH (FEET) = 447.89
ELEVATION DATA: UPSTREAM (FEET) = 564.89 DOWNSTREAM (FEET) = 421.92

Tc = K * [(LENGTH ** 3.00) / (ELEVATION CHANGE)] ** 0.20
SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 6.976
* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 4.094
SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
PUBLIC PARK	-	3.03	0.30	0.960	65	6.98

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.960
SUBAREA RUNOFF (CFS) = 10.38
TOTAL AREA (ACRES) = 3.03 PEAK FLOW RATE (CFS) = 10.38

FLOW PROCESS FROM NODE 13890.00 TO NODE 13891.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 421.92 DOWNSTREAM (FEET) = 392.64
CHANNEL LENGTH THRU SUBAREA (FEET) = 435.33 CHANNEL SLOPE = 0.0673
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.43
* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 3.621

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.12	0.30	0.986	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.986
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 22.58
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.03
AVERAGE FLOW DEPTH (FEET) = 0.41 TRAVEL TIME (MIN.) = 1.44
Tc (MIN.) = 8.42
SUBAREA AREA (ACRES) = 8.12 SUBAREA RUNOFF (CFS) = 24.30
EFFECTIVE AREA (ACRES) = 11.15 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
TOTAL AREA (ACRES) = 11.1 PEAK FLOW RATE (CFS) = 33.40
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.52

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.52 FLOW VELOCITY (FEET/SEC.) = 5.80
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13891.00 = 883.22 FEET.

FLOW PROCESS FROM NODE 13891.00 TO NODE 13892.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 392.64 DOWNSTREAM (FEET) = 324.46
CHANNEL LENGTH THRU SUBAREA (FEET) = 662.40 CHANNEL SLOPE = 0.1029
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.60
* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 3.151
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	12.50	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 49.47
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.69
AVERAGE FLOW DEPTH (FEET) = 0.58 TRAVEL TIME (MIN.) = 1.44
Tc (MIN.) = 9.86
SUBAREA AREA (ACRES) = 12.50 SUBAREA RUNOFF (CFS) = 32.08
EFFECTIVE AREA (ACRES) = 23.65 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 23.6 PEAK FLOW RATE (CFS) = 60.75
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.65

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.65 FLOW VELOCITY (FEET/SEC.) = 8.23
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13892.00 = 1545.62 FEET.

FLOW PROCESS FROM NODE 13892.00 TO NODE 13893.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 324.46 DOWNSTREAM(FEET) = 240.82
CHANNEL LENGTH THRU SUBAREA(FEET) = 980.03 CHANNEL SLOPE = 0.0853
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.82
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.847
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 15.87 0.30 1.000 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 78.96
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.46
AVERAGE FLOW DEPTH(FEET) = 0.80 TRAVEL TIME(MIN.) = 1.93
Tc(MIN.) = 11.79
SUBAREA AREA(ACRES) = 15.87 SUBAREA RUNOFF(CFS) = 36.39
EFFECTIVE AREA(ACRES) = 39.52 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 39.5 PEAK FLOW RATE(CFS) = 90.68
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.87

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.87 FLOW VELOCITY(FEET/SEC.) = 8.85
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13893.00 = 2525.65 FEET.

FLOW PROCESS FROM NODE 13893.00 TO NODE 13894.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 240.82 DOWNSTREAM(FEET) = 163.04
CHANNEL LENGTH THRU SUBAREA(FEET) = 1144.35 CHANNEL SLOPE = 0.0680
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.11
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.542
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 28.41 0.30 0.985 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.985
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 119.45
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.96
AVERAGE FLOW DEPTH(FEET) = 1.09 TRAVEL TIME(MIN.) = 2.13
Tc(MIN.) = 13.91
SUBAREA AREA(ACRES) = 28.41 SUBAREA RUNOFF(CFS) = 57.44
EFFECTIVE AREA(ACRES) = 67.93 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 67.9 PEAK FLOW RATE(CFS) = 137.24

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.18

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.18 FLOW VELOCITY(FEET/SEC.) = 9.41
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13894.00 = 3670.00 FEET.

FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 163.04 DOWNSTREAM(FEET) = 119.70
FLOW LENGTH(FEET) = 1899.01 MANNING'S N = 0.013
DEPTH OF FLOW IN 42.0 INCH PIPE IS 32.7 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 17.06
ESTIMATED PIPE DIAMETER(INCH) = 42.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 137.24
PIPE TRAVEL TIME(MIN.) = 1.86 Tc(MIN.) = 15.77
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13910.00 = 5569.01 FEET.

FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 15.77
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.324
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 11.69 0.30 0.634 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.634
SUBAREA AREA(ACRES) = 11.69 SUBAREA RUNOFF(CFS) = 22.45
EFFECTIVE AREA(ACRES) = 79.62 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94
TOTAL AREA(ACRES) = 79.6 PEAK FLOW RATE(CFS) = 146.34

FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 15.77
RAINFALL INTENSITY(INCH/HR) = 2.32
AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.94
EFFECTIVE STREAM AREA(ACRES) = 79.62
TOTAL STREAM AREA(ACRES) = 79.62
PEAK FLOW RATE(CFS) AT CONFLUENCE = 146.34

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22409.66	25.32	1.717	0.30 (0.25)	0.82	4383.7	10600.00
1	22986.11	26.98	1.648	0.30 (0.25)	0.82	4813.2	13810.00
1	23395.11	28.21	1.597	0.30 (0.25)	0.82	5121.8	13850.00
1	24142.19	30.51	1.513	0.30 (0.25)	0.82	5684.5	10400.00
1	24582.11	31.84	1.486	0.30 (0.25)	0.82	6154.3	13870.00
1	27056.84	39.46	1.333	0.30 (0.25)	0.82	8784.9	13830.00
1	29040.64	45.85	1.233	0.30 (0.24)	0.82	10880.3	110.00
1	32163.07	58.61	1.061	0.30 (0.25)	0.82	16440.2	800.00
1	34174.65	70.98	0.981	0.30 (0.26)	0.86	22853.1	13600.00
1	35997.32	84.75	0.903	0.30 (0.26)	0.88	29617.6	13100.00
1	36894.78	90.93	0.870	0.30 (0.27)	0.89	32369.9	11801.00
1	38767.51	101.26	0.831	0.30 (0.27)	0.90	37692.0	11530.00
1	39531.14	107.08	0.809	0.30 (0.27)	0.91	41444.3	13510.00
1	40260.66	112.87	0.788	0.30 (0.27)	0.91	45064.4	13010.00
1	41288.82	119.42	0.763	0.30 (0.28)	0.92	49345.6	11350.00
1	41642.28	124.07	0.752	0.30 (0.28)	0.93	52519.8	11130.00
1	41195.55	130.19	0.739	0.30 (0.28)	0.93	55446.4	12300.00
1	40378.57	139.04	0.720	0.30 (0.28)	0.93	59707.0	12400.00
1	39287.11	148.68	0.699	0.30 (0.28)	0.94	63108.5	12201.00
1	38282.19	156.29	0.683	0.30 (0.28)	0.94	65001.6	12231.00
1	37243.59	163.90	0.667	0.30 (0.28)	0.94	66554.3	10400.00
1	35635.96	173.55	0.646	0.30 (0.28)	0.94	68000.7	12010.00
1	34565.28	179.08	0.634	0.30 (0.28)	0.94	68263.3	10210.00
1	30114.78	210.17	0.604	0.30 (0.28)	0.94	69023.0	10100.00
2	146.34	15.77	2.324	0.30 (0.28)	0.94	79.6	13889.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19863.09	15.77	2.324	0.30 (0.25)	0.82	2810.0	13889.00
2	22512.52	25.32	1.717	0.30 (0.25)	0.82	4463.3	10600.00
3	23084.04	26.98	1.648	0.30 (0.25)	0.82	4892.8	13810.00
4	23489.39	28.21	1.597	0.30 (0.25)	0.82	5201.4	13850.00
5	24230.44	30.51	1.513	0.30 (0.25)	0.82	5764.2	10400.00
6	24668.43	31.84	1.486	0.30 (0.25)	0.82	6234.0	13870.00
7	27132.18	39.46	1.333	0.30 (0.25)	0.82	8864.5	13830.00
8	29108.80	45.85	1.233	0.30 (0.25)	0.82	10959.9	110.00
9	32218.91	58.61	1.061	0.30 (0.25)	0.82	16519.8	800.00
10	34224.77	70.98	0.981	0.30 (0.26)	0.86	22932.7	13600.00
11	36041.85	84.75	0.903	0.30 (0.26)	0.88	29697.2	13100.00
12	36936.93	90.93	0.870	0.30 (0.27)	0.89	32449.5	11801.00
13	38806.90	101.26	0.831	0.30 (0.27)	0.90	37771.6	11530.00
14	39568.96	107.08	0.809	0.30 (0.27)	0.91	41523.9	13510.00
15	40296.93	112.87	0.788	0.30 (0.27)	0.91	45144.0	13010.00
16	41323.35	119.42	0.763	0.30 (0.28)	0.92	49425.2	11350.00
17	41676.02	124.07	0.752	0.30 (0.28)	0.93	52599.4	11130.00
18	41228.35	130.19	0.739	0.30 (0.28)	0.93	55526.0	12300.00
19	40410.01	139.04	0.720	0.30 (0.28)	0.93	59786.6	12400.00
20	39317.06	148.68	0.699	0.30 (0.28)	0.94	63188.2	12201.00
21	38310.97	156.29	0.683	0.30 (0.28)	0.94	65081.2	12231.00
22	37271.20	163.90	0.667	0.30 (0.28)	0.94	66633.9	10400.00
23	35662.08	173.55	0.646	0.30 (0.28)	0.94	68080.3	12010.00

24	34590.55	179.08	0.634	0.30 (0.28)	0.94	68342.9	10210.00
25	30137.87	210.17	0.604	0.30 (0.28)	0.94	69102.6	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 41676.02 Tc(MIN.) = 124.07
 EFFECTIVE AREA(ACRES) = 52599.40 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 69102.6
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13910.00 = 135256.95 FEET.

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 69102.6 TC(MIN.) = 124.07
 EFFECTIVE AREA(ACRES) = 52599.40 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.926
 PEAK FLOW RATE(CFS) = 41676.02

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19863.09	15.77	2.324	0.30 (0.25)	0.82	2810.0	13889.00
2	22512.52	25.32	1.717	0.30 (0.25)	0.82	4463.3	10600.00
3	23084.04	26.98	1.648	0.30 (0.25)	0.82	4892.8	13810.00
4	23489.39	28.21	1.597	0.30 (0.25)	0.82	5201.4	13850.00
5	24230.44	30.51	1.513	0.30 (0.25)	0.82	5764.2	10400.00
6	24668.43	31.84	1.486	0.30 (0.25)	0.82	6234.0	13870.00
7	27132.18	39.46	1.333	0.30 (0.25)	0.82	8864.5	13830.00
8	29108.80	45.85	1.233	0.30 (0.25)	0.82	10959.9	110.00
9	32218.91	58.61	1.061	0.30 (0.25)	0.82	16519.8	800.00
10	34224.77	70.98	0.981	0.30 (0.26)	0.86	22932.7	13600.00
11	36041.85	84.75	0.903	0.30 (0.26)	0.88	29697.2	13100.00
12	36936.93	90.93	0.870	0.30 (0.27)	0.89	32449.5	11801.00
13	38806.90	101.26	0.831	0.30 (0.27)	0.90	37771.6	11530.00
14	39568.96	107.08	0.809	0.30 (0.27)	0.91	41523.9	13510.00
15	40296.93	112.87	0.788	0.30 (0.27)	0.91	45144.0	13010.00
16	41323.35	119.42	0.763	0.30 (0.28)	0.92	49425.2	11350.00
17	41676.02	124.07	0.752	0.30 (0.28)	0.93	52599.4	11130.00
18	41228.35	130.19	0.739	0.30 (0.28)	0.93	55526.0	12300.00
19	40410.01	139.04	0.720	0.30 (0.28)	0.93	59786.6	12400.00
20	39317.06	148.68	0.699	0.30 (0.28)	0.94	63188.2	12201.00
21	38310.97	156.29	0.683	0.30 (0.28)	0.94	65081.2	12231.00
22	37271.20	163.90	0.667	0.30 (0.28)	0.94	66633.9	10400.00
23	35662.08	173.55	0.646	0.30 (0.28)	0.94	68080.3	12010.00
24	34590.55	179.08	0.634	0.30 (0.28)	0.94	68342.9	10210.00
25	30137.87	210.17	0.604	0.30 (0.28)	0.94	69102.6	10100.00

END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2010 Advanced Engineering Software (aes)
Ver. 17.0 Release Date: 07/01/2010 License ID 1527

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 139 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 25-YR EV AUG 2023 ROKAMOTO *

FILE NAME: RU25EV39.DAT
TIME/DATE OF STUDY: 22:26 08/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 25.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 4.737
- 2) 10.00; 3.102
- 3) 15.00; 2.384
- 4) 20.00; 1.980
- 5) 25.00; 1.729
- 6) 30.00; 1.522
- 7) 40.00; 1.321
- 8) 50.00; 1.169
- 9) 60.00; 1.042
- 10) 90.00; 0.872
- 11) 120.00; 0.761
- 12) 180.00; 0.631
- 13) 360.00; 0.462
- 14) 1200.00; 0.201

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13900.00 TO NODE 13901.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 600.65
ELEVATION DATA: UPSTREAM(FEET) = 442.40 DOWNSTREAM(FEET) = 385.16

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 10.859
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.979
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
AGRICULTURAL POOR COVER "FALLOW"	-	4.00	0.30	1.000	65	10.86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 9.64
TOTAL AREA(ACRES) = 4.00 PEAK FLOW RATE(CFS) = 9.64

FLOW PROCESS FROM NODE 13901.00 TO NODE 13902.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 385.16 DOWNSTREAM(FEET) = 288.21
CHANNEL LENGTH THRU SUBAREA(FEET) = 647.42 CHANNEL SLOPE = 0.1497
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.30
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.725
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.47	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 18.90
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.10
AVERAGE FLOW DEPTH(FEET) = 0.29 TRAVEL TIME(MIN.) = 1.77
Tc(MIN.) = 12.63
SUBAREA AREA(ACRES) = 8.47 SUBAREA RUNOFF(CFS) = 18.48
EFFECTIVE AREA(ACRES) = 12.47 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 12.5 PEAK FLOW RATE(CFS) = 27.21
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.36

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.36 FLOW VELOCITY(FEET/SEC.) = 6.98
LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13902.00 = 1248.07 FEET.

FLOW PROCESS FROM NODE 13902.00 TO NODE 13903.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) =	288.21	DOWNSTREAM(FEET) =	184.89
CHANNEL LENGTH THRU SUBAREA(FEET) =	669.27	CHANNEL SLOPE =	0.1544
GIVEN CHANNEL BASE(FEET) =	10.00	CHANNEL FREEBOARD(FEET) =	0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 0.54

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.544

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	23.85	0.30	0.982	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.982

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 51.37

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.88

AVERAGE FLOW DEPTH(FEET) = 0.52 TRAVEL TIME(MIN.) = 1.26

Tc(MIN.) = 13.88

SUBAREA AREA(ACRES) = 23.85 SUBAREA RUNOFF(CFS) = 48.29

EFFECTIVE AREA(ACRES) = 36.32 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 36.3 PEAK FLOW RATE(CFS) = 73.48

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 0.65

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.65 FLOW VELOCITY(FEET/SEC.) = 9.98

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13903.00 = 1917.34 FEET.

FLOW PROCESS FROM NODE 13903.00 TO NODE 13904.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) =	184.89	DOWNSTREAM(FEET) =	155.08
FLOW LENGTH(FEET) =	876.66	MANNING'S N =	0.013
ESTIMATED PIPE DIAMETER(INCH) INCREASED TO	36.000		

DEPTH OF FLOW IN 36.0 INCH PIPE IS 20.7 INCHES

PIPE-FLOW VELOCITY(FEET/SEC.) = 17.45

ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1

PIPE-FLOW(CFS) = 73.48

PIPE TRAVEL TIME(MIN.) = 0.84 Tc(MIN.) = 14.72

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13904.00 = 2794.00 FEET.

FLOW PROCESS FROM NODE 13903.00 TO NODE 13904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 14.72

* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.424

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	21.29	0.30	0.996	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.996

SUBAREA AREA(ACRES) = 21.29 SUBAREA RUNOFF(CFS) = 40.72

EFFECTIVE AREA(ACRES) = 57.61 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 57.6 PEAK FLOW RATE(CFS) = 110.27

FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) =	155.08	DOWNSTREAM(FEET) =	118.00
FLOW LENGTH(FEET) =	1961.38	MANNING'S N =	0.013
DEPTH OF FLOW IN 42.0 INCH PIPE IS	29.5 INCHES		

PIPE-FLOW VELOCITY(FEET/SEC.) = 15.28

ESTIMATED PIPE DIAMETER(INCH) = 42.00 NUMBER OF PIPES = 1

PIPE-FLOW(CFS) = 110.27

PIPE TRAVEL TIME(MIN.) = 2.14 Tc(MIN.) = 16.86

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13920.00 = 4755.38 FEET.

FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) =	16.86		
* 25 YEAR RAINFALL INTENSITY(INCH/HR) =	2.234		
SUBAREA LOSS RATE DATA(AMC II):			

DEVELOPMENT TYPE/
LAND USE

SCS SOIL
GROUP

AREA
(ACRES)

Fp
(INCH/HR)

Ap
(DECIMAL)

SCS
CN

USER-DEFINED

-

43.53

0.30

0.649

-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.649

SUBAREA AREA(ACRES) = 43.53 SUBAREA RUNOFF(CFS) = 79.88

EFFECTIVE AREA(ACRES) = 101.14 AREA-AVERAGED Fm(INCH/HR) = 0.25

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84

TOTAL AREA(ACRES) = 101.1 PEAK FLOW RATE(CFS) = 180.28

FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 13910.00 TO NODE 13910.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU25EV38.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19863.09	15.77	0.30 (0.25)	0.82	2810.0	13889.00
2	24668.43	31.84	0.30 (0.25)	0.82	6234.0	13870.00
3	27132.18	39.46	0.30 (0.25)	0.82	8864.5	13830.00
4	29108.80	45.85	0.30 (0.25)	0.82	10959.9	110.00
5	32218.91	58.61	0.30 (0.25)	0.82	16519.8	800.00
6	34224.77	70.98	0.30 (0.26)	0.86	22932.7	13600.00
7	36041.85	84.75	0.30 (0.26)	0.88	29697.2	13100.00
8	36936.93	90.93	0.30 (0.27)	0.89	32449.5	11801.00
9	38806.90	101.26	0.30 (0.27)	0.90	37771.6	11530.00
10	39568.96	107.08	0.30 (0.27)	0.91	41523.9	13510.00
11	40296.93	112.87	0.30 (0.27)	0.91	45144.0	13010.00
12	41676.02	124.07	0.30 (0.28)	0.93	52599.4	11130.00
13	41228.35	130.19	0.30 (0.28)	0.93	55526.0	12300.00
14	40410.01	139.04	0.30 (0.28)	0.93	59786.6	12400.00
15	39317.06	148.68	0.30 (0.28)	0.94	63188.2	12201.00
16	38310.97	156.29	0.30 (0.28)	0.94	65081.2	12231.00
17	37271.20	163.90	0.30 (0.28)	0.94	66633.9	10400.00
18	35662.08	173.55	0.30 (0.28)	0.94	68080.3	12010.00
19	34590.55	179.08	0.30 (0.28)	0.94	68342.9	10210.00
20	30137.87	210.17	0.30 (0.28)	0.94	69102.6	10100.00
TOTAL AREA (ACRES) =						69102.6

FLOW PROCESS FROM NODE 13910.00 TO NODE 13910.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19863.09	15.77	0.30 (0.25)	0.82	2810.0	13889.00
2	24668.43	31.84	0.30 (0.25)	0.82	6234.0	13870.00
3	27132.18	39.46	0.30 (0.25)	0.82	8864.5	13830.00
4	29108.80	45.85	0.30 (0.25)	0.82	10959.9	110.00
5	32218.91	58.61	0.30 (0.25)	0.82	16519.8	800.00
6	34224.77	70.98	0.30 (0.26)	0.86	22932.7	13600.00
7	36041.85	84.75	0.30 (0.26)	0.88	29697.2	13100.00
8	36936.93	90.93	0.30 (0.27)	0.89	32449.5	11801.00
9	38806.90	101.26	0.30 (0.27)	0.90	37771.6	11530.00
10	39568.96	107.08	0.30 (0.27)	0.91	41523.9	13510.00
11	40296.93	112.87	0.30 (0.27)	0.91	45144.0	13010.00
12	41676.02	124.07	0.30 (0.28)	0.93	52599.4	11130.00
13	41228.35	130.19	0.30 (0.28)	0.93	55526.0	12300.00
14	40410.01	139.04	0.30 (0.28)	0.93	59786.6	12400.00
15	39317.06	148.68	0.30 (0.28)	0.94	63188.2	12201.00
16	38310.97	156.29	0.30 (0.28)	0.94	65081.2	12231.00
17	37271.20	163.90	0.30 (0.28)	0.94	66633.9	10400.00
18	35662.08	173.55	0.30 (0.28)	0.94	68080.3	12010.00
19	34590.55	179.08	0.30 (0.28)	0.94	68342.9	10210.00
20	30137.87	210.17	0.30 (0.28)	0.94	69102.6	10100.00
TOTAL AREA (ACRES) =						69102.6

FLOW PROCESS FROM NODE 13910.00 TO NODE 13920.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 119.70 DOWNSTREAM(FEET) = 118.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1376.26 CHANNEL SLOPE = 0.0012
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 21.62
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.747
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 96.09 0.30 0.535 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.535
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 41701.40
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.35
AVERAGE FLOW DEPTH(FEET) = 21.62 TRAVEL TIME(MIN.) = 2.22
Tc(MIN.) = 126.29
SUBAREA AREA(ACRES) = 96.09 SUBAREA RUNOFF(CFS) = 50.76
EFFECTIVE AREA(ACRES) = 52695.49 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 69198.7 PEAK FLOW RATE(CFS) = 41676.02
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 21.61

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 21.61 FLOW VELOCITY(FEET/SEC.) = 10.34
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136633.22 FEET.

FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19863.09	18.49	2.102	0.30 (0.24)	0.81	2906.1	13889.00
2	24668.43	34.40	1.434	0.30 (0.25)	0.82	6330.0	13870.00
3	27132.18	41.96	1.291	0.30 (0.24)	0.82	8960.6	13830.00
4	29108.80	48.29	1.195	0.30 (0.24)	0.81	11056.0	110.00
5	32218.91	60.99	1.036	0.30 (0.25)	0.82	16615.9	800.00
6	34224.77	73.32	0.966	0.30 (0.26)	0.86	23028.8	13600.00
7	36041.85	87.05	0.889	0.30 (0.26)	0.88	29793.3	13100.00
8	36936.93	93.22	0.860	0.30 (0.27)	0.89	32545.6	11801.00
9	38806.90	103.52	0.822	0.30 (0.27)	0.90	37867.7	11530.00
10	39568.96	109.33	0.800	0.30 (0.27)	0.91	41620.0	13510.00
11	40296.93	115.11	0.779	0.30 (0.27)	0.91	45240.1	13010.00
12	41676.02	126.29	0.747	0.30 (0.28)	0.93	52695.5	11130.00
13	41228.35	132.41	0.734	0.30 (0.28)	0.93	55622.1	12300.00
14	40410.01	141.28	0.715	0.30 (0.28)	0.93	59882.7	12400.00
15	39317.06	150.94	0.694	0.30 (0.28)	0.94	63284.3	12201.00
16	38310.97	158.56	0.677	0.30 (0.28)	0.94	65177.3	12231.00

17 37271.20 166.18 0.661 0.30(0.28) 0.94 66730.0 10400.00
 18 35662.08 175.86 0.640 0.30(0.28) 0.94 68176.4 12010.00
 19 34590.55 181.42 0.630 0.30(0.28) 0.94 68439.0 10210.00
 20 30137.87 212.59 0.600 0.30(0.28) 0.94 69198.7 10100.00
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136633.22 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	180.28	16.86	2.234	0.30(0.25)	0.84	101.1	13900.00

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13920.00 = 4755.38 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19575.92	16.86	2.234	0.30(0.24)	0.81	2750.8	13900.00
2	20031.37	18.49	2.102	0.30(0.24)	0.81	3007.2	13889.00
3	24775.88	34.40	1.434	0.30(0.25)	0.82	6431.2	13870.00
4	27226.68	41.96	1.291	0.30(0.24)	0.82	9061.7	13830.00
5	29194.54	48.29	1.195	0.30(0.24)	0.82	11157.2	110.00
6	32290.21	60.99	1.036	0.30(0.25)	0.82	16717.0	800.00
7	34289.71	73.32	0.966	0.30(0.26)	0.86	23129.9	13600.00
8	36099.71	87.05	0.889	0.30(0.26)	0.88	29894.5	13100.00
9	36992.18	93.22	0.860	0.30(0.27)	0.89	32646.7	11801.00
10	38858.68	103.52	0.822	0.30(0.27)	0.90	37968.9	11530.00
11	39618.79	109.33	0.800	0.30(0.27)	0.91	41721.2	13510.00
12	40344.81	115.11	0.779	0.30(0.27)	0.91	45341.3	13010.00
13	41721.02	126.29	0.747	0.30(0.28)	0.93	52796.6	11130.00
14	41272.14	132.41	0.734	0.30(0.28)	0.93	55723.2	12300.00
15	40452.05	141.28	0.715	0.30(0.28)	0.93	59983.8	12400.00
16	39357.19	150.94	0.694	0.30(0.28)	0.94	63385.4	12201.00
17	38349.60	158.56	0.677	0.30(0.28)	0.94	65278.4	12231.00
18	37308.32	166.18	0.661	0.30(0.28)	0.94	66831.1	10400.00
19	35697.29	175.86	0.640	0.30(0.28)	0.94	68277.6	12010.00
20	34624.82	181.42	0.630	0.30(0.28)	0.94	68540.1	10210.00
21	30169.48	212.59	0.600	0.30(0.28)	0.94	69299.9	10100.00

TOTAL AREA (ACRES) = 69299.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 41721.02 Tc(MIN.) = 126.286
 EFFECTIVE AREA(ACRES) = 52796.63 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.91
 TOTAL AREA(ACRES) = 69299.9
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136633.22 FEET.

 FLOW PROCESS FROM NODE 13920.00 TO NODE 13921.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 118.00 DOWNSTREAM(FEET) = 115.28
 CHANNEL LENGTH THRU SUBAREA(FEET) = 335.44 CHANNEL SLOPE = 0.0081
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 13.36
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.747
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	134.30	0.30	0.658	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.658
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 41754.22
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 20.36
 AVERAGE FLOW DEPTH(FEET) = 13.36 TRAVEL TIME(MIN.) = 0.27
 Tc(MIN.) = 126.56
 SUBAREA AREA(ACRES) = 134.30 SUBAREA RUNOFF(CFS) = 66.41
 EFFECTIVE AREA(ACRES) = 52930.93 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA(ACRES) = 69434.2 PEAK FLOW RATE(CFS) = 41721.02
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 13.36

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 13.36 FLOW VELOCITY(FEET/SEC.) = 20.36
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13921.00 = 136968.66 FEET.

 FLOW PROCESS FROM NODE 13921.00 TO NODE 14010.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 115.28 DOWNSTREAM(FEET) = 100.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1396.08 CHANNEL SLOPE = 0.0109
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 12.34
 * 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.745
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	96.27	0.30	0.723	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.723
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 41743.88
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 22.65
 AVERAGE FLOW DEPTH(FEET) = 12.34 TRAVEL TIME(MIN.) = 1.03
 Tc(MIN.) = 127.59
 SUBAREA AREA(ACRES) = 96.27 SUBAREA RUNOFF(CFS) = 45.72
 EFFECTIVE AREA(ACRES) = 53027.20 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA(ACRES) = 69530.5 PEAK FLOW RATE(CFS) = 41721.02
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 12.34

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 12.34 FLOW VELOCITY(FEET/SEC.) = 22.64
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 14010.00 = 138364.73 FEET.

=====

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 69530.5 TC (MIN.) = 127.59
 EFFECTIVE AREA (ACRES) = 53027.20 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.924
 PEAK FLOW RATE (CFS) = 41721.02

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19575.92	18.49	2.102	0.30 (0.24)	0.80	2981.3	13900.00
2	20031.37	20.11	1.974	0.30 (0.24)	0.81	3237.8	13889.00
3	24775.88	35.92	1.403	0.30 (0.24)	0.81	6661.8	13870.00
4	27226.68	43.44	1.269	0.30 (0.24)	0.81	9292.3	13830.00
5	29194.54	49.74	1.173	0.30 (0.24)	0.81	11387.7	110.00
6	32290.21	62.39	1.028	0.30 (0.25)	0.82	16947.6	800.00
7	34289.71	74.70	0.959	0.30 (0.26)	0.86	23360.5	13600.00
8	36099.71	88.41	0.881	0.30 (0.26)	0.88	30125.0	13100.00
9	36992.18	94.57	0.855	0.30 (0.27)	0.89	32877.3	11801.00
10	38858.68	104.85	0.817	0.30 (0.27)	0.90	38199.4	11530.00
11	39618.79	110.65	0.796	0.30 (0.27)	0.91	41951.7	13510.00
12	40344.81	116.43	0.774	0.30 (0.27)	0.91	45571.8	13010.00
13	41721.02	127.59	0.745	0.30 (0.28)	0.92	53027.2	11130.00
14	41272.14	133.72	0.731	0.30 (0.28)	0.93	55953.8	12300.00
15	40452.05	142.59	0.712	0.30 (0.28)	0.93	60214.4	12400.00
16	39357.19	152.26	0.691	0.30 (0.28)	0.93	63616.0	12201.00
17	38349.60	159.89	0.675	0.30 (0.28)	0.94	65509.0	12231.00
18	37308.32	167.53	0.658	0.30 (0.28)	0.94	67061.7	10400.00
19	35697.29	177.23	0.637	0.30 (0.28)	0.94	68508.1	12010.00
20	34624.82	182.79	0.628	0.30 (0.28)	0.94	68770.7	10210.00
21	30169.48	214.02	0.599	0.30 (0.28)	0.94	69530.5	10100.00

=====
 END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International
5 Hutton Centre Drive, Suite 500
Santa Ana, CA 92707

***** DESCRIPTION OF STUDY *****
* RANCHO MISSION VIEJO - PA3 & PA4 ROMP - NODE 119 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 50-YR RM EV APRIL 2019 FKAZI *

FILE NAME: RU50EV19.DAT
TIME/DATE OF STUDY: 11:51 04/01/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 50.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.535
- 2) 10.00; 3.529
- 3) 15.00; 2.693
- 4) 20.00; 2.246
- 5) 25.00; 1.938
- 6) 30.00; 1.744
- 7) 40.00; 1.475
- 8) 50.00; 1.313
- 9) 60.00; 1.214
- 10) 90.00; 1.010
- 11) 120.00; 0.880
- 12) 180.00; 0.760
- 13) 360.00; 0.566
- 14) 1200.00; 0.250

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 11900.00 TO NODE 11901.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<
=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 295.79
ELEVATION DATA: UPSTREAM(FEET) = 2369.48 DOWNSTREAM(FEET) = 2332.92

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 7.203
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 4.651
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
RESIDENTIAL ".4 DWELLING/ACRE"	-	1.62	0.30	0.999	56	7.20

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999
SUBAREA RUNOFF(CFS) = 6.34
TOTAL AREA(ACRES) = 1.62 PEAK FLOW RATE(CFS) = 6.34

FLOW PROCESS FROM NODE 11901.00 TO NODE 11902.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<
=====

ELEVATION DATA: UPSTREAM(FEET) = 2332.92 DOWNSTREAM(FEET) = 2297.70
CHANNEL LENGTH THRU SUBAREA(FEET) = 664.26 CHANNEL SLOPE = 0.0530
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.57
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 3.443
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.35	0.30	0.906	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.906
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 18.40
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.34
AVERAGE FLOW DEPTH(FEET) = 0.50 TRAVEL TIME(MIN.) = 3.31
Tc(MIN.) = 10.52
SUBAREA AREA(ACRES) = 8.35 SUBAREA RUNOFF(CFS) = 23.83
EFFECTIVE AREA(ACRES) = 9.97 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 10.0 PEAK FLOW RATE(CFS) = 28.41
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.65

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.65 FLOW VELOCITY(FEET/SEC.) = 3.90
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11902.00 = 960.05 FEET.

FLOW PROCESS FROM NODE 11902.00 TO NODE 11902.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2297.70 DOWNSTREAM(FEET) = 2263.40
CHANNEL LENGTH THRU SUBAREA(FEET) = 928.77 CHANNEL SLOPE = 0.0369
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 1.28

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.887

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	34.48	0.30	0.904	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.904

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 69.30

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.65

AVERAGE FLOW DEPTH(FEET) = 1.20 TRAVEL TIME(MIN.) = 3.33

Tc(MIN.) = 13.84

SUBAREA AREA(ACRES) = 34.48 SUBAREA RUNOFF(CFS) = 81.16

EFFECTIVE AREA(ACRES) = 44.45 AREA-AVERAGED Fm(INCH/HR) = 0.27

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.91

TOTAL AREA(ACRES) = 44.5 PEAK FLOW RATE(CFS) = 104.58

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 1.51

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.51 FLOW VELOCITY(FEET/SEC.) = 5.30

LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11902.50 = 1888.82 FEET.

FLOW PROCESS FROM NODE 11902.50 TO NODE 11903.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2263.40 DOWNSTREAM(FEET) = 2252.14
CHANNEL LENGTH THRU SUBAREA(FEET) = 895.50 CHANNEL SLOPE = 0.0126
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 2.32

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.451

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	23.65	0.30	0.958	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.958

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 127.65

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.87

AVERAGE FLOW DEPTH(FEET) = 2.27 TRAVEL TIME(MIN.) = 3.86

Tc(MIN.) = 17.70
SUBAREA AREA(ACRES) = 23.65 SUBAREA RUNOFF(CFS) = 46.06
EFFECTIVE AREA(ACRES) = 68.10 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 68.1 PEAK FLOW RATE(CFS) = 133.24
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.32

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.32 FLOW VELOCITY(FEET/SEC.) = 3.91

LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11903.00 = 2784.32 FEET.

FLOW PROCESS FROM NODE 11903.00 TO NODE 11904.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2252.14 DOWNSTREAM(FEET) = 2186.04
CHANNEL LENGTH THRU SUBAREA(FEET) = 1924.35 CHANNEL SLOPE = 0.0343
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 2.21

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.067

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	68.53	0.30	0.961	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.961

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 188.28

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.16

AVERAGE FLOW DEPTH(FEET) = 2.14 TRAVEL TIME(MIN.) = 5.20

Tc(MIN.) = 22.91

SUBAREA AREA(ACRES) = 68.53 SUBAREA RUNOFF(CFS) = 109.71

EFFECTIVE AREA(ACRES) = 136.63 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94

TOTAL AREA(ACRES) = 136.6 PEAK FLOW RATE(CFS) = 219.39

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 2.32

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.32 FLOW VELOCITY(FEET/SEC.) = 6.45

LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11904.00 = 4708.67 FEET.

FLOW PROCESS FROM NODE 11904.00 TO NODE 11905.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2186.04 DOWNSTREAM(FEET) = 1957.34
CHANNEL LENGTH THRU SUBAREA(FEET) = 1926.87 CHANNEL SLOPE = 0.1187
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 1.86

* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.901
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 63.15 0.30 1.000 -
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 264.91
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 10.57
 AVERAGE FLOW DEPTH (FEET) = 1.83 TRAVEL TIME (MIN.) = 3.04
 Tc (MIN.) = 25.94
 SUBAREA AREA (ACRES) = 63.15 SUBAREA RUNOFF (CFS) = 91.02
 EFFECTIVE AREA (ACRES) = 199.78 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
 TOTAL AREA (ACRES) = 199.8 PEAK FLOW RATE (CFS) = 290.04
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 1.93

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 1.93 FLOW VELOCITY (FEET/SEC.) = 10.86
 LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11905.00 = 6635.54 FEET.

FLOW PROCESS FROM NODE 11905.00 TO NODE 11906.00 IS CODE = 56

 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 1957.34 DOWNSTREAM (FEET) = 1244.16
 CHANNEL LENGTH THRU SUBAREA (FEET) = 2498.96 CHANNEL SLOPE = 0.2854
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 1.68
 * 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.797
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 84.87 0.30 1.000 -
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 347.25
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 15.54
 AVERAGE FLOW DEPTH (FEET) = 1.67 TRAVEL TIME (MIN.) = 2.68
 Tc (MIN.) = 28.62
 SUBAREA AREA (ACRES) = 84.87 SUBAREA RUNOFF (CFS) = 114.38
 EFFECTIVE AREA (ACRES) = 284.65 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA (ACRES) = 284.6 PEAK FLOW RATE (CFS) = 385.73
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 1.77

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 1.77 FLOW VELOCITY (FEET/SEC.) = 16.06
 LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11906.00 = 9134.50 FEET.

FLOW PROCESS FROM NODE 11906.00 TO NODE 11920.00 IS CODE = 56

 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 1244.16 DOWNSTREAM (FEET) = 873.95
 CHANNEL LENGTH THRU SUBAREA (FEET) = 3370.75 CHANNEL SLOPE = 0.1098
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 2.70
 * 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.659
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 199.43 0.30 1.000 -
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 507.80
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 12.43
 AVERAGE FLOW DEPTH (FEET) = 2.67 TRAVEL TIME (MIN.) = 4.52
 Tc (MIN.) = 33.14
 SUBAREA AREA (ACRES) = 199.43 SUBAREA RUNOFF (CFS) = 244.01
 EFFECTIVE AREA (ACRES) = 484.08 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
 TOTAL AREA (ACRES) = 484.1 PEAK FLOW RATE (CFS) = 594.38
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 2.90

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 2.90 FLOW VELOCITY (FEET/SEC.) = 12.99
 LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11920.00 = 12505.25 FEET.

FLOW PROCESS FROM NODE 11906.00 TO NODE 11920.00 IS CODE = 1

 >>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
 TIME OF CONCENTRATION (MIN.) = 33.14
 RAINFALL INTENSITY (INCH/HR) = 1.66
 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.98
 EFFECTIVE STREAM AREA (ACRES) = 484.08
 TOTAL STREAM AREA (ACRES) = 484.08
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 594.38

FLOW PROCESS FROM NODE 11910.00 TO NODE 11911.00 IS CODE = 21

 >>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH (FEET) = 517.62
 ELEVATION DATA: UPSTREAM (FEET) = 2531.88 DOWNSTREAM (FEET) = 2441.33

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
 SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 12.185
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 3.164
 SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	-	3.46	0.30	1.000	56	12.19

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA RUNOFF(CFS) = 8.92
 TOTAL AREA(ACRES) = 3.46 PEAK FLOW RATE(CFS) = 8.92

 FLOW PROCESS FROM NODE 11911.00 TO NODE 11912.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2441.33 DOWNSTREAM(FEET) = 2382.20
 CHANNEL LENGTH THRU SUBAREA(FEET) = 397.30 CHANNEL SLOPE = 0.1488
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 0.35
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.909
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.79	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 15.73
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.35
 AVERAGE FLOW DEPTH(FEET) = 0.34 TRAVEL TIME(MIN.) = 1.52
 Tc(MIN.) = 13.71
 SUBAREA AREA(ACRES) = 5.79 SUBAREA RUNOFF(CFS) = 13.60
 EFFECTIVE AREA(ACRES) = 9.25 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 9.2 PEAK FLOW RATE(CFS) = 21.72
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 0.41

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 0.41 FLOW VELOCITY(FEET/SEC.) = 4.93
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11912.00 = 914.92 FEET.

 FLOW PROCESS FROM NODE 11912.00 TO NODE 11913.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2382.20 DOWNSTREAM(FEET) = 2263.77
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1891.47 CHANNEL SLOPE = 0.0626
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 1.16

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.308
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	54.30	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 71.48
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.63
 AVERAGE FLOW DEPTH(FEET) = 1.05 TRAVEL TIME(MIN.) = 5.60
 Tc(MIN.) = 19.31
 SUBAREA AREA(ACRES) = 54.30 SUBAREA RUNOFF(CFS) = 98.12
 EFFECTIVE AREA(ACRES) = 63.55 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 63.5 PEAK FLOW RATE(CFS) = 114.83
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 1.38

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 1.38 FLOW VELOCITY(FEET/SEC.) = 6.54
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11913.00 = 2806.39 FEET.

 FLOW PROCESS FROM NODE 11913.00 TO NODE 11914.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2263.77 DOWNSTREAM(FEET) = 1845.23
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1957.31 CHANNEL SLOPE = 0.2138
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 1.23
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.110
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	65.14	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 167.95
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.26
 AVERAGE FLOW DEPTH(FEET) = 1.20 TRAVEL TIME(MIN.) = 2.90
 Tc(MIN.) = 22.21
 SUBAREA AREA(ACRES) = 65.14 SUBAREA RUNOFF(CFS) = 106.12
 EFFECTIVE AREA(ACRES) = 128.69 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 128.7 PEAK FLOW RATE(CFS) = 209.64
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 1.37

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 1.37 FLOW VELOCITY(FEET/SEC.) = 12.03
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11914.00 = 4763.70 FEET.

FLOW PROCESS FROM NODE 11914.00 TO NODE 11915.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1845.23 DOWNSTREAM(FEET) = 1557.21
CHANNEL LENGTH THRU SUBAREA(FEET) = 1686.78 CHANNEL SLOPE = 0.1708
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 1.69
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.966

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/, SCS SOIL, AREA, Fp, Ap, SCS. Row 1: LAND USE, GROUP, (ACRES), (INCH/HR), (DECIMAL), CN. Row 2: USER-DEFINED, -, 78.52, 0.30, 1.000, -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 268.54
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.02
AVERAGE FLOW DEPTH(FEET) = 1.67 TRAVEL TIME(MIN.) = 2.34
Tc(MIN.) = 24.55

SUBAREA AREA(ACRES) = 78.52 SUBAREA RUNOFF(CFS) = 117.73
EFFECTIVE AREA(ACRES) = 207.21 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 207.2 PEAK FLOW RATE(CFS) = 310.69
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.81

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.81 FLOW VELOCITY(FEET/SEC.) = 12.58
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11915.00 = 6450.48 FEET.

FLOW PROCESS FROM NODE 11915.00 TO NODE 11916.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1557.21 DOWNSTREAM(FEET) = 1403.38
CHANNEL LENGTH THRU SUBAREA(FEET) = 1909.39 CHANNEL SLOPE = 0.0806
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 2.42
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.833

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/, SCS SOIL, AREA, Fp, Ap, SCS. Row 1: LAND USE, GROUP, (ACRES), (INCH/HR), (DECIMAL), CN. Row 2: USER-DEFINED, -, 70.48, 0.30, 1.000, -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 359.32
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.08
AVERAGE FLOW DEPTH(FEET) = 2.41 TRAVEL TIME(MIN.) = 3.16
Tc(MIN.) = 27.70

SUBAREA AREA(ACRES) = 70.48 SUBAREA RUNOFF(CFS) = 97.25
EFFECTIVE AREA(ACRES) = 277.69 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 277.7 PEAK FLOW RATE(CFS) = 383.17
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.49

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.49 FLOW VELOCITY(FEET/SEC.) = 10.27
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11916.00 = 8359.87 FEET.

FLOW PROCESS FROM NODE 11916.00 TO NODE 11917.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1403.38 DOWNSTREAM(FEET) = 1079.99
CHANNEL LENGTH THRU SUBAREA(FEET) = 1945.82 CHANNEL SLOPE = 0.1662
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 2.47
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.747

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/, SCS SOIL, AREA, Fp, Ap, SCS. Row 1: LAND USE, GROUP, (ACRES), (INCH/HR), (DECIMAL), CN. Row 2: USER-DEFINED, -, 232.20, 0.30, 1.000, -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 534.42
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 14.62
AVERAGE FLOW DEPTH(FEET) = 2.45 TRAVEL TIME(MIN.) = 2.22
Tc(MIN.) = 29.92

SUBAREA AREA(ACRES) = 232.20 SUBAREA RUNOFF(CFS) = 302.42
EFFECTIVE AREA(ACRES) = 509.89 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 509.9 PEAK FLOW RATE(CFS) = 664.09
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.75

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.75 FLOW VELOCITY(FEET/SEC.) = 15.57
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11917.00 = 10305.69 FEET.

FLOW PROCESS FROM NODE 11917.00 TO NODE 11920.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1079.99 DOWNSTREAM(FEET) = 873.95
CHANNEL LENGTH THRU SUBAREA(FEET) = 2563.91 CHANNEL SLOPE = 0.0804
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 3.51
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.653

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/, SCS SOIL, AREA, Fp, Ap, SCS. Row 1: LAND USE, GROUP, (ACRES), (INCH/HR), (DECIMAL), CN

USER-DEFINED - 110.82 0.30 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 731.56
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.30
 AVERAGE FLOW DEPTH(FEET) = 3.50 TRAVEL TIME(MIN.) = 3.47
 Tc(MIN.) = 33.40
 SUBAREA AREA(ACRES) = 110.82 SUBAREA RUNOFF(CFS) = 134.92
 EFFECTIVE AREA(ACRES) = 620.71 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 620.7 PEAK FLOW RATE(CFS) = 755.69
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 3.56

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 3.56 FLOW VELOCITY(FEET/SEC.) = 12.41
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11920.00 = 12869.60 FEET.

 FLOW PROCESS FROM NODE 11917.00 TO NODE 11920.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
 TIME OF CONCENTRATION(MIN.) = 33.40
 RAINFALL INTENSITY(INCH/HR) = 1.65
 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 1.00
 EFFECTIVE STREAM AREA(ACRES) = 620.71
 TOTAL STREAM AREA(ACRES) = 620.71
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 755.69

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	594.38	33.14	1.659	0.30(0.30)	0.98	484.1	11900.00
2	755.69	33.40	1.653	0.30(0.30)	1.00	620.7	11910.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1348.14	33.14	1.659	0.30(0.30)	0.99	1100.1	11900.00
2	1347.14	33.40	1.653	0.30(0.30)	0.99	1104.8	11910.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
 PEAK FLOW RATE(CFS) = 1348.14 Tc(MIN.) = 33.14
 EFFECTIVE AREA(ACRES) = 1100.13 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 1104.8
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11920.00 = 12869.60 FEET.

 FLOW PROCESS FROM NODE 11920.00 TO NODE 11921.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 873.95 DOWNSTREAM(FEET) = 827.94
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1417.25 CHANNEL SLOPE = 0.0325
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 6.07
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.599

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	107.47	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1410.97
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.52
 AVERAGE FLOW DEPTH(FEET) = 6.06 TRAVEL TIME(MIN.) = 2.25
 Tc(MIN.) = 35.39
 SUBAREA AREA(ACRES) = 107.47 SUBAREA RUNOFF(CFS) = 125.65
 EFFECTIVE AREA(ACRES) = 1207.60 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 1212.3 PEAK FLOW RATE(CFS) = 1413.99
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 6.07

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 6.07 FLOW VELOCITY(FEET/SEC.) = 10.52
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11921.00 = 14286.85 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1413.99	35.39	1.599	0.30(0.30)	0.99	1207.6	11900.00
2	1412.02	35.64	1.592	0.30(0.30)	0.99	1212.3	11910.00

NEW PEAK FLOW DATA ARE:
 PEAK FLOW RATE(CFS) = 1413.99 Tc(MIN.) = 35.39
 AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 1207.60

 FLOW PROCESS FROM NODE 11921.00 TO NODE 11922.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 827.94 DOWNSTREAM(FEET) = 753.55
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1886.43 CHANNEL SLOPE = 0.0394
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 6.18
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.527

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	107.47	0.30	1.000	-

LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 344.27 0.30 1.000 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1604.04
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.68
 AVERAGE FLOW DEPTH(FEET) = 6.15 TRAVEL TIME(MIN.) = 2.69
 Tc(MIN.) = 38.08
 SUBAREA AREA(ACRES) = 344.27 SUBAREA RUNOFF(CFS) = 380.08
 EFFECTIVE AREA(ACRES) = 1551.87 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 1556.5 PEAK FLOW RATE(CFS) = 1715.40
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 6.35

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 6.35 FLOW VELOCITY(FEET/SEC.) = 11.89
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11922.00 = 16173.28 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1715.40	38.08	1.527	0.30(0.30)	1.00	1551.9	11900.00
2	1710.87	38.34	1.520	0.30(0.30)	1.00	1556.5	11910.00

NEW PEAK FLOW DATA ARE:
 PEAK FLOW RATE(CFS) = 1715.40 Tc(MIN.) = 38.08
 AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 1.00 EFFECTIVE AREA(ACRES) = 1551.87

 FLOW PROCESS FROM NODE 11922.00 TO NODE 11923.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 753.55 DOWNSTREAM(FEET) = 641.58
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2860.88 CHANNEL SLOPE = 0.0391
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 6.53
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.442
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	165.18	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1800.27
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.01
 AVERAGE FLOW DEPTH(FEET) = 6.51 TRAVEL TIME(MIN.) = 3.97
 Tc(MIN.) = 42.05
 SUBAREA AREA(ACRES) = 165.18 SUBAREA RUNOFF(CFS) = 169.74
 EFFECTIVE AREA(ACRES) = 1717.05 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 1721.7 PEAK FLOW RATE(CFS) = 1766.60
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 6.46

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 6.46 FLOW VELOCITY(FEET/SEC.) = 11.94
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11923.00 = 19034.16 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1766.60	42.05	1.442	0.30(0.30)	1.00	1717.1	11900.00
2	1764.86	42.31	1.438	0.30(0.30)	1.00	1721.7	11910.00

NEW PEAK FLOW DATA ARE:
 PEAK FLOW RATE(CFS) = 1766.60 Tc(MIN.) = 42.05
 AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 1.00 EFFECTIVE AREA(ACRES) = 1717.05

 FLOW PROCESS FROM NODE 11923.00 TO NODE 11924.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 641.58 DOWNSTREAM(FEET) = 579.89
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1844.02 CHANNEL SLOPE = 0.0335
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 7.08
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.399
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	433.73	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1981.09
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.61
 AVERAGE FLOW DEPTH(FEET) = 7.07 TRAVEL TIME(MIN.) = 2.65
 Tc(MIN.) = 44.70
 SUBAREA AREA(ACRES) = 433.73 SUBAREA RUNOFF(CFS) = 428.97
 EFFECTIVE AREA(ACRES) = 2150.78 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 2155.4 PEAK FLOW RATE(CFS) = 2129.29
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 7.31

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 7.31 FLOW VELOCITY(FEET/SEC.) = 11.83
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11924.00 = 20878.18 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2129.29	44.70	1.399	0.30(0.30)	1.00	2150.8	11900.00
2	2125.66	44.96	1.395	0.30(0.30)	1.00	2155.4	11910.00

NEW PEAK FLOW DATA ARE:
 PEAK FLOW RATE(CFS) = 2129.29 Tc(MIN.) = 44.70
 AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 1.00 EFFECTIVE AREA(ACRES) = 2150.78

FLOW PROCESS FROM NODE 11924.00 TO NODE 11925.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 579.89 DOWNSTREAM(FEET) = 494.12
CHANNEL LENGTH THRU SUBAREA(FEET) = 2756.15 CHANNEL SLOPE = 0.0311
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 7.65
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.335

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 265.42 0.30 1.000 -

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2252.94
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.68
AVERAGE FLOW DEPTH(FEET) = 7.63 TRAVEL TIME(MIN.) = 3.93
Tc(MIN.) = 48.63

SUBAREA AREA(ACRES) = 265.42 SUBAREA RUNOFF(CFS) = 247.29
EFFECTIVE AREA(ACRES) = 2416.20 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 2420.9 PEAK FLOW RATE(CFS) = 2253.25
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 7.63

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 7.63 FLOW VELOCITY(FEET/SEC.) = 11.68
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11925.00 = 23634.33 FEET.

** PEAK FLOW RATE TABLE **

STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 2253.25 48.63 1.335 0.30(0.30) 1.00 2416.2 11900.00
2 2248.30 48.90 1.331 0.30(0.30) 1.00 2420.9 11910.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2253.25 Tc(MIN.) = 48.63
AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 1.00 EFFECTIVE AREA(ACRES) = 2416.20

FLOW PROCESS FROM NODE 11925.00 TO NODE 11926.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 494.12 DOWNSTREAM(FEET) = 458.40
CHANNEL LENGTH THRU SUBAREA(FEET) = 1922.70 CHANNEL SLOPE = 0.0186
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 8.68
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.294

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 97.46 0.30 1.000 -

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2296.83
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.69
AVERAGE FLOW DEPTH(FEET) = 8.67 TRAVEL TIME(MIN.) = 3.31
Tc(MIN.) = 51.94

SUBAREA AREA(ACRES) = 97.46 SUBAREA RUNOFF(CFS) = 87.17
EFFECTIVE AREA(ACRES) = 2513.66 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 2518.3 PEAK FLOW RATE(CFS) = 2253.25
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 8.60

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 8.60 FLOW VELOCITY(FEET/SEC.) = 9.64
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11926.00 = 25557.03 FEET.

** PEAK FLOW RATE TABLE **

STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 2253.25 51.94 1.294 0.30(0.30) 1.00 2513.7 11900.00
2 2248.71 52.21 1.291 0.30(0.30) 1.00 2518.3 11910.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2253.25 Tc(MIN.) = 51.94
AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 1.00 EFFECTIVE AREA(ACRES) = 2513.66

FLOW PROCESS FROM NODE 11926.00 TO NODE 11927.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 458.40 DOWNSTREAM(FEET) = 399.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 2170.13 CHANNEL SLOPE = 0.0274
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 7.90
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.262

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 53.83 0.30 1.000 -

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2276.54
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.17
AVERAGE FLOW DEPTH(FEET) = 7.90 TRAVEL TIME(MIN.) = 3.24
Tc(MIN.) = 55.18

SUBAREA AREA(ACRES) = 53.83 SUBAREA RUNOFF(CFS) = 46.60
EFFECTIVE AREA(ACRES) = 2567.49 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA (ACRES) = 2572.1 PEAK FLOW RATE (CFS) = 2253.25
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 7.86

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 7.86 FLOW VELOCITY (FEET/SEC.) = 11.14
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 27727.16 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2253.25	55.18	1.262	0.30 (0.30)	1.00	2567.5	11900.00
2	2248.71	55.45	1.259	0.30 (0.30)	1.00	2572.1	11910.00

NEW PEAK FLOW DATA ARE:
 PEAK FLOW RATE (CFS) = 2253.25 Tc (MIN.) = 55.18
 AREA-AVERAGED Fm (INCH/HR) = 0.30 AREA-AVERAGED Fp (INCH/HR) = 0.30
 AREA-AVERAGED Ap = 1.00 EFFECTIVE AREA (ACRES) = 2567.49

 FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<<
 =====

 FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<<
 =====

PEAK FLOWRATE TABLE FILE NAME: P401XX50.DNA
 MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	850.75	25.74	0.30 (0.30)	1.00	624.8	40130.00
2	844.35	27.56	0.30 (0.30)	1.00	654.2	40100.00
TOTAL AREA (ACRES) = 654.2						

 FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<<
 =====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2253.25	55.18	1.262	0.30 (0.30)	1.00	2567.5	11900.00
2	2248.71	55.45	1.259	0.30 (0.30)	1.00	2572.1	11910.00
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 27727.16 FEET.							

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	850.75	25.74	1.909	0.30 (0.30)	1.00	624.8	40130.00
2	844.35	27.56	1.839	0.30 (0.30)	1.00	654.2	40100.00
LONGEST FLOWPATH FROM NODE 40100.00 TO NODE 11927.00 = 10245.00 FEET.							

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2608.92	25.74	1.909	0.30 (0.30)	1.00	1822.6	40130.00
2	2644.22	27.56	1.839	0.30 (0.30)	1.00	1936.6	40100.00
3	2781.01	55.18	1.262	0.30 (0.30)	1.00	3221.7	11900.00
4	2775.02	55.45	1.259	0.30 (0.30)	1.00	3226.4	11910.00
TOTAL AREA (ACRES) = 3226.4							

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
 PEAK FLOW RATE (CFS) = 2781.01 Tc (MIN.) = 55.180
 EFFECTIVE AREA (ACRES) = 3221.69 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA (ACRES) = 3226.4
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 27727.16 FEET.

 FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<<
 =====

 FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<<
 =====

ELEVATION DATA: UPSTREAM (FEET) = 399.00 DOWNSTREAM (FEET) = 384.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 986.26 CHANNEL SLOPE = 0.0152
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 9.89
 CHANNEL FLOW THRU SUBAREA (CFS) = 2781.01
 FLOW VELOCITY (FEET/SEC.) = 9.44 FLOW DEPTH (FEET) = 9.89
 TRAVEL TIME (MIN.) = 1.74 Tc (MIN.) = 56.92
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.50 = 28713.42 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2608.92	27.51	1.841	0.30 (0.30)	1.00	1822.6	40130.00
2	2644.22	29.32	1.770	0.30 (0.30)	1.00	1936.6	40100.00
3	2781.01	56.92	1.244	0.30 (0.30)	1.00	3221.7	11900.00
4	2775.02	57.19	1.242	0.30 (0.30)	1.00	3226.4	11910.00

NEW PEAK FLOW DATA ARE:
 PEAK FLOW RATE (CFS) = 2781.01 Tc (MIN.) = 56.92
 AREA-AVERAGED Fm (INCH/HR) = 0.30 AREA-AVERAGED Fp (INCH/HR) = 0.30
 AREA-AVERAGED Ap = 1.00 EFFECTIVE AREA (ACRES) = 3221.69

 FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<
 =====

MAINLINE Tc (MIN.) = 56.92
 * 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.244

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	2.40	0.30	1.000	65
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	1.70	0.30	1.000	65
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	1.50	0.30	1.000	65
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.30	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.90	0.30	1.000	66
NATURAL FAIR COVER					
"GRASS"	B	0.60	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 8.40 SUBAREA RUNOFF (CFS) = 7.14
EFFECTIVE AREA (ACRES) = 3230.09 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 3234.8 PEAK FLOW RATE (CFS) = 2781.01
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 56.92
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.244

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.30	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.10	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.10	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 0.50 SUBAREA RUNOFF (CFS) = 0.43
EFFECTIVE AREA (ACRES) = 3230.59 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 3235.2 PEAK FLOW RATE (CFS) = 2781.01
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 56.92
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.244

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
"WOODLAND,GRASS"	B	0.80	0.30	1.000	65
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.70	0.30	1.000	65
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.20	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.20	0.30	1.000	65
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.10	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 2.00 SUBAREA RUNOFF (CFS) = 1.70
EFFECTIVE AREA (ACRES) = 3232.59 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 3237.2 PEAK FLOW RATE (CFS) = 2781.01
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 11927.50 TO NODE 11928.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 384.00 DOWNSTREAM (FEET) = 359.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 647.19 CHANNEL SLOPE = 0.0386
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 8.05
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.237

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	78.01	0.30	0.984	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.984
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 2814.06
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 13.40
AVERAGE FLOW DEPTH (FEET) = 8.05 TRAVEL TIME (MIN.) = 0.80
Tc (MIN.) = 57.73
SUBAREA AREA (ACRES) = 78.01 SUBAREA RUNOFF (CFS) = 66.09
EFFECTIVE AREA (ACRES) = 3310.60 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 3315.3 PEAK FLOW RATE (CFS) = 2792.98
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 8.02

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 8.02 FLOW VELOCITY (FEET/SEC.) = 13.37
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11928.00 = 29360.61 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap (DECIMAL)	Ae (ACRES)	HEADWATER NODE
1	2608.92	28.33	1.809	0.30 (0.30)	1.00	1911.5	40130.00
2	2644.22	30.14	1.740	0.30 (0.30)	1.00	2025.5	40100.00
3	2792.98	57.73	1.237	0.30 (0.30)	1.00	3310.6	11900.00
4	2789.01	57.99	1.234	0.30 (0.30)	1.00	3315.3	11910.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2792.98 Tc(MIN.) = 57.73
AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 1.00 EFFECTIVE AREA(ACRES) = 3310.60

FLOW PROCESS FROM NODE 11928.00 TO NODE 11928.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 57.73

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.237

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE SCS SOIL GROUP AREA (ACRES) Fp (INCH/HR) Ap (DECIMAL) SCS CN

NATURAL FAIR COVER "WOODLAND,GRASS" B 1.10 0.30 1.000 65
NATURAL FAIR COVER "OPEN BRUSH" B 0.60 0.30 1.000 66

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 1.70 SUBAREA RUNOFF(CFS) = 1.43

EFFECTIVE AREA(ACRES) = 3312.30 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 3317.0 PEAK FLOW RATE(CFS) = 2794.41

FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 359.00 DOWNSTREAM(FEET) = 341.63

CHANNEL LENGTH THRU SUBAREA(FEET) = 1322.66 CHANNEL SLOPE = 0.0131

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 10.25

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.213

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE SCS SOIL GROUP AREA (ACRES) Fp (INCH/HR) Ap (DECIMAL) SCS CN

USER-DEFINED - 8.18 0.30 0.890 -

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.890

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2797.90

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.95

AVERAGE FLOW DEPTH(FEET) = 10.25 TRAVEL TIME(MIN.) = 2.46

Tc(MIN.) = 60.19

SUBAREA AREA(ACRES) = 8.18 SUBAREA RUNOFF(CFS) = 6.96

EFFECTIVE AREA(ACRES) = 3320.48 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 3325.1 PEAK FLOW RATE(CFS) = 2794.41

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT(FEET) = 10.24

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 10.24 FLOW VELOCITY(FEET/SEC.) = 8.95

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11929.00 = 30683.27 FEET.

** PEAK FLOW RATE TABLE **

Table with 7 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp (Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Rows 1-4.

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2794.41 Tc(MIN.) = 60.19

AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 1.00 EFFECTIVE AREA(ACRES) = 3320.48

FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 60.19

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.213

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE SCS SOIL GROUP AREA (ACRES) Fp (INCH/HR) Ap (DECIMAL) SCS CN

NATURAL FAIR COVER "OPEN BRUSH" B 1.90 0.30 1.000 66
NATURAL FAIR COVER "WOODLAND,GRASS" B 0.60 0.30 1.000 65

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 2.50 SUBAREA RUNOFF(CFS) = 2.05

EFFECTIVE AREA(ACRES) = 3322.98 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 3327.6 PEAK FLOW RATE(CFS) = 2794.41

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 3 <<<<

FLOW PROCESS FROM NODE 11841.00 TO NODE 12527.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<

PEAK FLOWRATE TABLE FILE NAME: S18X50.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

Table with 7 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Fp (Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Rows 1-6.

7	24998.78	70.58	0.30	(0.30)	1.00	19900.2	10800.00
8	25620.24	74.96	0.30	(0.30)	1.00	22211.8	11130.00
9	25459.58	83.55	0.30	(0.30)	1.00	25307.4	11620.00
10	25389.29	85.79	0.30	(0.30)	1.00	26059.8	11600.00
11	25269.09	87.43	0.30	(0.30)	1.00	26526.1	10600.00
12	25052.94	92.79	0.30	(0.30)	1.00	28070.1	11201.00
13	24726.86	98.42	0.30	(0.30)	1.00	29254.4	10710.00
14	24565.08	100.41	0.30	(0.30)	1.00	29586.3	10410.00
15	24070.54	105.10	0.30	(0.30)	1.00	30247.3	10700.00
16	23353.04	112.10	0.30	(0.30)	1.00	31166.7	10400.00
17	23163.67	114.42	0.30	(0.30)	1.00	31437.3	10200.00
18	22543.84	120.36	0.30	(0.30)	1.00	32015.5	10300.00
19	21907.93	125.43	0.30	(0.30)	1.00	32220.3	10210.00
20	19363.37	152.55	0.30	(0.30)	1.00	32916.6	10100.00

TOTAL AREA (ACRES) = 32916.6

FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: S25X50.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	6814.52	66.91	0.30 (0.30)	0.99	6393.3	12500.00
2	7515.45	80.53	0.30 (0.30)	0.99	8363.5	12300.00
3	7623.90	81.91	0.30 (0.30)	0.98	8652.7	12330.00
4	7789.58	84.57	0.30 (0.30)	0.98	9163.3	12410.00
5	7994.43	88.75	0.30 (0.29)	0.98	9893.3	12400.00
6	8150.23	93.51	0.30 (0.29)	0.98	10584.1	12211.00
7	8242.61	97.70	0.30 (0.29)	0.98	11179.8	12201.00
8	8205.03	101.92	0.30 (0.29)	0.98	11654.1	12111.00
9	8180.32	104.56	0.30 (0.29)	0.98	11967.4	12231.00
10	8145.23	107.37	0.30 (0.29)	0.98	12265.9	12101.10
11	8125.55	108.34	0.30 (0.29)	0.98	12357.2	12261.00
12	7675.64	119.74	0.30 (0.29)	0.98	13113.0	12010.00
13	7214.09	128.35	0.30 (0.29)	0.98	13237.1	12000.00

TOTAL AREA (ACRES) = 13237.1

FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	6814.52	66.91	0.30 (0.30)	0.99	6393.3	12500.00
2	7515.45	80.53	0.30 (0.30)	0.99	8363.5	12300.00
3	7623.90	81.91	0.30 (0.30)	0.98	8652.7	12330.00
4	7789.58	84.57	0.30 (0.30)	0.98	9163.3	12410.00
5	7994.43	88.75	0.30 (0.29)	0.98	9893.3	12400.00
6	8150.23	93.51	0.30 (0.29)	0.98	10584.1	12211.00
7	8242.61	97.70	0.30 (0.29)	0.98	11179.8	12201.00
8	8205.03	101.92	0.30 (0.29)	0.98	11654.1	12111.00
9	8180.32	104.56	0.30 (0.29)	0.98	11967.4	12231.00

10	8145.23	107.37	0.30	(0.29)	0.98	12265.9	12101.10
11	8125.55	108.34	0.30	(0.29)	0.98	12357.2	12261.00
12	7675.64	119.74	0.30	(0.29)	0.98	13113.0	12010.00
13	7214.09	128.35	0.30	(0.29)	0.98	13237.1	12000.00

TOTAL AREA (ACRES) = 13237.1

FLOW PROCESS FROM NODE 11841.00 TO NODE 12527.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	6814.52	66.91	1.167	0.30 (0.30)	0.99	6393.3	12500.00
2	7515.45	80.53	1.074	0.30 (0.30)	0.99	8363.5	12300.00
3	7623.90	81.91	1.065	0.30 (0.30)	0.98	8652.7	12330.00
4	7789.58	84.57	1.047	0.30 (0.30)	0.98	9163.3	12410.00
5	7994.43	88.75	1.018	0.30 (0.29)	0.98	9893.3	12400.00
6	8150.23	93.51	0.995	0.30 (0.29)	0.98	10584.1	12211.00
7	8242.61	97.70	0.977	0.30 (0.29)	0.98	11179.8	12201.00
8	8205.03	101.92	0.958	0.30 (0.29)	0.98	11654.1	12111.00
9	8180.32	104.56	0.947	0.30 (0.29)	0.98	11967.4	12231.00
10	8145.23	107.37	0.935	0.30 (0.29)	0.98	12265.9	12101.10
11	8125.55	108.34	0.931	0.30 (0.29)	0.98	12357.2	12261.00
12	7675.64	119.74	0.881	0.30 (0.29)	0.98	13113.0	12010.00
13	7214.09	128.35	0.863	0.30 (0.29)	0.98	13237.1	12000.00

LONGEST FLOWPATH FROM NODE 12000.00 TO NODE 12527.00 = 77156.98 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18863.84	37.77	1.535	0.30 (0.30)	1.00	7696.5	11831.00
2	19171.93	40.18	1.472	0.30 (0.30)	1.00	8206.0	11801.00
3	20870.42	51.52	1.298	0.30 (0.30)	1.00	11178.6	11530.00
4	21741.74	56.15	1.252	0.30 (0.30)	1.00	12836.1	11701.00
5	22206.97	58.56	1.228	0.30 (0.30)	1.00	13761.0	11000.00
6	24578.79	68.37	1.157	0.30 (0.30)	1.00	18741.7	11330.00
7	24998.78	70.58	1.142	0.30 (0.30)	1.00	19900.2	10800.00
8	25620.24	74.96	1.112	0.30 (0.30)	1.00	22211.8	11130.00
9	25459.58	83.55	1.054	0.30 (0.30)	1.00	25307.4	11620.00
10	25389.29	85.79	1.039	0.30 (0.30)	1.00	26059.8	11600.00
11	25269.09	87.43	1.027	0.30 (0.30)	1.00	26526.1	10600.00
12	25052.94	92.79	0.998	0.30 (0.30)	1.00	28070.1	11201.00
13	24726.86	98.42	0.974	0.30 (0.30)	1.00	29254.4	10710.00
14	24565.08	100.41	0.965	0.30 (0.30)	1.00	29586.3	10410.00
15	24070.54	105.10	0.945	0.30 (0.30)	1.00	30247.3	10700.00
16	23353.04	112.10	0.914	0.30 (0.30)	1.00	31166.7	10400.00
17	23163.67	114.42	0.904	0.30 (0.30)	1.00	31437.3	10200.00
18	22543.84	120.36	0.879	0.30 (0.30)	1.00	32015.5	10300.00
19	21907.93	125.43	0.869	0.30 (0.30)	1.00	32220.3	10210.00
20	19363.37	152.55	0.815	0.30 (0.30)	1.00	32916.6	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12527.00 = 97868.13 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
---------------	---------	-----------	---------------------	-------------------	----	------------	----------------

1	24335.68	37.77	1.535	0.30	(0.30)	0.99	11305.9	11831.00
2	24697.44	40.18	1.472	0.30	(0.30)	0.99	12045.5	11801.00
3	26906.53	51.52	1.298	0.30	(0.30)	0.99	16101.8	11530.00
4	28019.04	56.15	1.252	0.30	(0.30)	0.99	18201.1	11701.00
5	28590.34	58.56	1.228	0.30	(0.30)	0.99	19356.3	11000.00
6	31039.95	66.91	1.167	0.30	(0.30)	0.99	24392.9	12500.00
7	31468.57	68.37	1.157	0.30	(0.30)	0.99	25346.5	11330.00
8	32002.18	70.58	1.142	0.30	(0.30)	0.99	26824.3	10800.00
9	32849.10	74.96	1.112	0.30	(0.30)	0.99	29769.7	11130.00
10	33031.62	80.53	1.074	0.30	(0.30)	0.99	32580.5	12300.00
11	33114.20	81.91	1.065	0.30	(0.30)	0.99	33368.0	12330.00
12	33186.01	83.55	1.054	0.30	(0.30)	0.99	34276.0	11620.00
13	33217.38	84.57	1.047	0.30	(0.30)	0.99	34810.9	12410.00
14	33238.92	85.79	1.039	0.30	(0.30)	0.99	35437.1	11600.00
15	33199.04	87.43	1.027	0.30	(0.30)	0.99	36189.6	10600.00
16	33210.37	88.75	1.018	0.30	(0.30)	0.99	36799.1	12400.00
17	33179.69	92.79	0.998	0.30	(0.30)	0.99	38550.0	11201.00
18	33161.66	93.51	0.995	0.30	(0.30)	0.99	38804.9	12211.00
19	33011.46	97.70	0.977	0.30	(0.30)	0.99	40281.7	12201.00
20	32963.01	98.42	0.974	0.30	(0.30)	0.99	40515.8	10710.00
21	32783.54	100.41	0.965	0.30	(0.30)	0.99	41070.9	10410.00
22	32611.09	101.92	0.958	0.30	(0.30)	0.99	41453.0	12111.00
23	32307.60	104.56	0.947	0.30	(0.30)	0.99	42138.9	12231.00
24	32244.16	105.10	0.945	0.30	(0.30)	0.99	42271.8	10700.00
25	31982.44	107.37	0.935	0.30	(0.30)	0.99	42812.2	12101.10
26	31863.89	108.34	0.931	0.30	(0.30)	0.99	43030.2	12261.00
27	31330.23	112.10	0.914	0.30	(0.30)	0.99	43773.2	10400.00
28	31049.28	114.42	0.904	0.30	(0.30)	0.99	44197.6	10200.00
29	30284.07	119.74	0.881	0.30	(0.30)	0.99	45068.3	12010.00
30	30186.30	120.36	0.879	0.30	(0.30)	0.99	45137.4	10300.00
31	29278.79	125.43	0.869	0.30	(0.30)	0.99	45415.2	10210.00
32	28847.68	128.35	0.863	0.30	(0.30)	0.99	45532.4	12000.00
33	25964.49	152.55	0.815	0.30	(0.30)	0.99	46153.7	10100.00

TOTAL AREA (ACRES) = 46153.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 33238.92 Tc (MIN.) = 85.792
EFFECTIVE AREA (ACRES) = 35437.09 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 46153.7
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12527.00 = 97868.13 FEET.

FLOW PROCESS FROM NODE 12527.00 TO NODE 11929.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 347.47 DOWNSTREAM (FEET) = 341.63
CHANNEL LENGTH THRU SUBAREA (FEET) = 532.38 CHANNEL SLOPE = 0.0110
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT (FEET) = 9.03
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.035
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	14.37	0.30	0.987	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.987
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 33243.70
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 15.02
AVERAGE FLOW DEPTH (FEET) = 9.03 TRAVEL TIME (MIN.) = 0.59
Tc (MIN.) = 86.38
SUBAREA AREA (ACRES) = 14.37 SUBAREA RUNOFF (CFS) = 9.55
EFFECTIVE AREA (ACRES) = 35451.46 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 46168.0 PEAK FLOW RATE (CFS) = 33238.92
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT (FEET) = 9.03

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 9.03 FLOW VELOCITY (FEET/SEC.) = 15.01
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24335.68	38.43	1.517	0.30 (0.30)	0.99	11320.3	11831.00
2	24697.44	40.83	1.461	0.30 (0.30)	0.99	12059.9	11801.00
3	26906.53	52.16	1.292	0.30 (0.30)	0.99	16116.2	11530.00
4	28019.04	56.77	1.246	0.30 (0.30)	0.99	18215.4	11701.00
5	28590.34	59.18	1.222	0.30 (0.30)	0.99	19370.6	11000.00
6	31039.95	67.51	1.163	0.30 (0.30)	0.99	24407.3	12500.00
7	31468.57	68.97	1.153	0.30 (0.30)	0.99	25360.9	11330.00
8	32002.18	71.18	1.138	0.30 (0.30)	0.99	26838.7	10800.00
9	32849.10	75.55	1.108	0.30 (0.30)	0.99	29784.1	11130.00
10	33031.62	81.12	1.070	0.30 (0.30)	0.99	32594.9	12300.00
11	33114.20	82.50	1.061	0.30 (0.30)	0.99	33382.4	12330.00
12	33186.01	84.14	1.050	0.30 (0.30)	0.99	34290.4	11620.00
13	33217.38	85.16	1.043	0.30 (0.30)	0.99	34825.3	12410.00
14	33238.92	86.38	1.035	0.30 (0.30)	0.99	35451.5	11600.00
15	33199.04	88.02	1.023	0.30 (0.30)	0.99	36204.0	10600.00
16	33210.37	89.34	1.014	0.30 (0.30)	0.99	36813.4	12400.00
17	33179.69	93.38	0.995	0.30 (0.30)	0.99	38564.4	11201.00
18	33161.66	94.10	0.992	0.30 (0.30)	0.99	38819.3	12211.00
19	33011.46	98.29	0.974	0.30 (0.30)	0.99	40296.1	12201.00
20	32963.01	99.01	0.971	0.30 (0.30)	0.99	40530.1	10710.00
21	32783.54	101.00	0.962	0.30 (0.30)	0.99	41085.2	10410.00
22	32611.09	102.51	0.956	0.30 (0.30)	0.99	41467.3	12111.00
23	32307.60	105.16	0.944	0.30 (0.30)	0.99	42153.2	12231.00
24	32244.16	105.69	0.942	0.30 (0.30)	0.99	42286.1	10700.00
25	31982.44	107.97	0.932	0.30 (0.30)	0.99	42826.5	12101.10
26	31863.89	108.94	0.928	0.30 (0.30)	0.99	43044.6	12261.00
27	31330.23	112.70	0.912	0.30 (0.30)	0.99	43787.5	10400.00
28	31049.28	115.02	0.902	0.30 (0.30)	0.99	44211.9	10200.00
29	30284.07	120.35	0.879	0.30 (0.30)	0.99	45082.6	12010.00
30	30186.30	120.97	0.878	0.30 (0.30)	0.99	45151.8	10300.00
31	29278.79	126.04	0.868	0.30 (0.30)	0.99	45429.6	10210.00
32	28847.68	128.97	0.862	0.30 (0.30)	0.99	45546.8	12000.00
33	25964.49	153.19	0.814	0.30 (0.30)	0.99	46168.0	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 33238.92 Tc (MIN.) = 86.38
AREA-AVERAGED Fm (INCH/HR) = 0.30 AREA-AVERAGED Fp (INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 35451.46

FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24335.68	38.43	1.517	0.30(0.30)	0.99	11320.3	11831.00
2	24697.44	40.83	1.461	0.30(0.30)	0.99	12059.9	11801.00
3	26906.53	52.16	1.292	0.30(0.30)	0.99	16116.2	11530.00
4	28019.04	56.77	1.246	0.30(0.30)	0.99	18215.4	11701.00
5	28590.34	59.18	1.222	0.30(0.30)	0.99	19370.6	11000.00
6	31039.95	67.51	1.163	0.30(0.30)	0.99	24407.3	12500.00
7	31468.57	68.97	1.153	0.30(0.30)	0.99	25360.9	11330.00
8	32002.18	71.18	1.138	0.30(0.30)	0.99	26838.7	10800.00
9	32849.10	75.55	1.108	0.30(0.30)	0.99	29784.1	11130.00
10	33031.62	81.12	1.070	0.30(0.30)	0.99	32594.9	12300.00
11	33114.20	82.50	1.061	0.30(0.30)	0.99	33382.4	12330.00
12	33186.01	84.14	1.050	0.30(0.30)	0.99	34290.4	11620.00
13	33217.38	85.16	1.043	0.30(0.30)	0.99	34825.3	12410.00
14	33238.92	86.38	1.035	0.30(0.30)	0.99	35451.5	11600.00
15	33199.04	88.02	1.023	0.30(0.30)	0.99	36204.0	10600.00
16	33210.37	89.34	1.014	0.30(0.30)	0.99	36813.4	12400.00
17	33179.69	93.38	0.995	0.30(0.30)	0.99	38564.4	11201.00
18	33161.66	94.10	0.992	0.30(0.30)	0.99	38819.3	12211.00
19	33011.46	98.29	0.974	0.30(0.30)	0.99	40296.1	12201.00
20	32963.01	99.01	0.971	0.30(0.30)	0.99	40530.1	10710.00
21	32783.54	101.00	0.962	0.30(0.30)	0.99	41085.2	10410.00
22	32611.09	102.51	0.956	0.30(0.30)	0.99	41467.3	12111.00
23	32307.60	105.16	0.944	0.30(0.30)	0.99	42153.2	12231.00
24	32244.16	105.69	0.942	0.30(0.30)	0.99	42286.1	10700.00
25	31982.44	107.97	0.932	0.30(0.30)	0.99	42826.5	12101.10
26	31863.89	108.94	0.928	0.30(0.30)	0.99	43044.6	12261.00
27	31330.23	112.70	0.912	0.30(0.30)	0.99	43787.5	10400.00
28	31049.28	115.02	0.902	0.30(0.30)	0.99	44211.9	10200.00
29	30284.07	120.35	0.879	0.30(0.30)	0.99	45082.6	12010.00
30	30186.30	120.97	0.878	0.30(0.30)	0.99	45151.8	10300.00
31	29278.79	126.04	0.868	0.30(0.30)	0.99	45429.6	10210.00
32	28847.68	128.97	0.862	0.30(0.30)	0.99	45546.8	12000.00
33	25964.49	153.19	0.814	0.30(0.30)	0.99	46168.0	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2608.92	30.83	1.722	0.30(0.30)	1.00	1923.9	40130.00
2	2644.22	32.64	1.673	0.30(0.30)	1.00	2037.9	40100.00
3	2794.41	60.19	1.213	0.30(0.30)	1.00	3323.0	11900.00
4	2790.44	60.46	1.211	0.30(0.30)	1.00	3327.6	11910.00

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11929.00 = 30683.27 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2608.92	30.83	1.722	0.30(0.30)	1.00	1923.9	40130.00
2	2644.22	32.64	1.673	0.30(0.30)	1.00	2037.9	40100.00
3	2794.41	60.19	1.213	0.30(0.30)	1.00	3323.0	11900.00
4	2790.44	60.46	1.211	0.30(0.30)	1.00	3327.6	11910.00

1	25406.30	30.83	1.722	0.30(0.30)	0.99	11007.2	40130.00
2	25952.56	32.64	1.673	0.30(0.30)	0.99	11652.1	40100.00
3	27011.47	38.43	1.517	0.30(0.30)	0.99	13628.3	11831.00
4	27386.34	40.83	1.461	0.30(0.30)	0.99	14480.1	11801.00
5	29657.15	52.16	1.292	0.30(0.30)	0.99	19064.5	11530.00
6	30794.82	56.77	1.246	0.30(0.30)	0.99	21379.0	11701.00
7	31379.23	59.18	1.222	0.30(0.30)	0.99	22646.4	11000.00
8	31682.43	60.19	1.213	0.30(0.30)	0.99	23305.7	11900.00
9	31757.19	60.46	1.211	0.30(0.30)	0.99	23472.2	11910.00
10	33683.59	67.51	1.163	0.30(0.30)	0.99	27734.9	12500.00
11	34081.84	68.97	1.153	0.30(0.30)	0.99	28688.5	11330.00
12	34569.59	71.18	1.138	0.30(0.30)	0.99	30166.4	10800.00
13	35325.47	75.55	1.108	0.30(0.30)	0.99	33111.7	11130.00
14	35392.14	81.12	1.070	0.30(0.30)	0.99	35922.5	12300.00
15	35445.93	82.50	1.061	0.30(0.30)	0.99	36710.1	12330.00
16	35483.55	84.14	1.050	0.30(0.30)	0.99	37618.1	11620.00
17	35493.85	85.16	1.043	0.30(0.30)	0.99	38152.9	12410.00
18	35489.87	86.38	1.035	0.30(0.30)	0.99	38779.1	11600.00
19	35415.85	88.02	1.023	0.30(0.30)	0.99	39531.6	10600.00
20	35399.76	89.34	1.014	0.30(0.30)	0.99	40141.1	12400.00
21	35310.54	93.38	0.995	0.30(0.30)	0.99	41892.0	11201.00
22	35283.00	94.10	0.992	0.30(0.30)	0.99	42146.9	12211.00
23	35077.23	98.29	0.974	0.30(0.30)	0.99	43623.7	12201.00
24	35019.16	99.01	0.971	0.30(0.30)	0.99	43857.8	10710.00
25	34813.35	101.00	0.962	0.30(0.30)	0.99	44412.9	10410.00
26	34620.89	102.51	0.956	0.30(0.30)	0.99	44795.0	12111.00
27	34282.30	105.16	0.944	0.30(0.30)	0.99	45480.9	12231.00
28	34211.72	105.69	0.942	0.30(0.30)	0.99	45613.8	10700.00
29	33919.79	107.97	0.932	0.30(0.30)	0.99	46154.2	12101.10
30	33788.43	108.94	0.928	0.30(0.30)	0.99	46372.2	12261.00
31	33204.87	112.70	0.912	0.30(0.30)	0.99	47115.2	10400.00
32	32893.12	115.02	0.902	0.30(0.30)	0.99	47539.6	10200.00
33	32059.78	120.35	0.879	0.30(0.30)	0.99	48410.3	12010.00
34	31958.21	120.97	0.878	0.30(0.30)	0.99	48479.4	10300.00
35	31019.66	126.04	0.868	0.30(0.30)	0.99	48757.2	10210.00
36	30570.63	128.97	0.862	0.30(0.30)	0.99	48874.4	12000.00
37	27539.19	153.19	0.814	0.30(0.30)	0.99	49495.7	10100.00
TOTAL AREA(ACRES) =							49495.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 35493.85 Tc(MIN.) = 85.157
EFFECTIVE AREA(ACRES) = 38152.91 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 49495.7
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 49495.7 TC(MIN.) = 85.16
EFFECTIVE AREA(ACRES) = 38152.91 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.994
PEAK FLOW RATE(CFS) = 35493.85

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25406.30	30.83	1.722	0.30(0.30)	0.99	11007.2	40130.00
2	25952.56	32.64	1.673	0.30(0.30)	0.99	11652.1	40100.00
3	27011.47	38.43	1.517	0.30(0.30)	0.99	13628.3	11831.00

4	27386.34	40.83	1.461	0.30	(0.30)	0.99	14480.1	11801.00
5	29657.15	52.16	1.292	0.30	(0.30)	0.99	19064.5	11530.00
6	30794.82	56.77	1.246	0.30	(0.30)	0.99	21379.0	11701.00
7	31379.23	59.18	1.222	0.30	(0.30)	0.99	22646.4	11000.00
8	31682.43	60.19	1.213	0.30	(0.30)	0.99	23305.7	11900.00
9	31757.19	60.46	1.211	0.30	(0.30)	0.99	23472.2	11910.00
10	33683.59	67.51	1.163	0.30	(0.30)	0.99	27734.9	12500.00
11	34081.84	68.97	1.153	0.30	(0.30)	0.99	28688.5	11330.00
12	34569.59	71.18	1.138	0.30	(0.30)	0.99	30166.4	10800.00
13	35325.47	75.55	1.108	0.30	(0.30)	0.99	33111.7	11130.00
14	35392.14	81.12	1.070	0.30	(0.30)	0.99	35922.5	12300.00
15	35445.93	82.50	1.061	0.30	(0.30)	0.99	36710.1	12330.00
16	35483.55	84.14	1.050	0.30	(0.30)	0.99	37618.1	11620.00
17	35493.85	85.16	1.043	0.30	(0.30)	0.99	38152.9	12410.00
18	35489.87	86.38	1.035	0.30	(0.30)	0.99	38779.1	11600.00
19	35415.85	88.02	1.023	0.30	(0.30)	0.99	39531.6	10600.00
20	35399.76	89.34	1.014	0.30	(0.30)	0.99	40141.1	12400.00
21	35310.54	93.38	0.995	0.30	(0.30)	0.99	41892.0	11201.00
22	35283.00	94.10	0.992	0.30	(0.30)	0.99	42146.9	12211.00
23	35077.23	98.29	0.974	0.30	(0.30)	0.99	43623.7	12201.00
24	35019.16	99.01	0.971	0.30	(0.30)	0.99	43857.8	10710.00
25	34813.35	101.00	0.962	0.30	(0.30)	0.99	44412.9	10410.00
26	34620.89	102.51	0.956	0.30	(0.30)	0.99	44795.0	12111.00
27	34282.30	105.16	0.944	0.30	(0.30)	0.99	45480.9	12231.00
28	34211.72	105.69	0.942	0.30	(0.30)	0.99	45613.8	10700.00
29	33919.79	107.97	0.932	0.30	(0.30)	0.99	46154.2	12101.10
30	33788.43	108.94	0.928	0.30	(0.30)	0.99	46372.2	12261.00
31	33204.87	112.70	0.912	0.30	(0.30)	0.99	47115.2	10400.00
32	32893.12	115.02	0.902	0.30	(0.30)	0.99	47539.6	10200.00
33	32059.78	120.35	0.879	0.30	(0.30)	0.99	48410.3	12010.00
34	31958.21	120.97	0.878	0.30	(0.30)	0.99	48479.4	10300.00
35	31019.66	126.04	0.868	0.30	(0.30)	0.99	48757.2	10210.00
36	30570.63	128.97	0.862	0.30	(0.30)	0.99	48874.4	12000.00
37	27539.19	153.19	0.814	0.30	(0.30)	0.99	49495.7	10100.00

=====
 END OF RATIONAL METHOD ANALYSIS
 =====

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 126 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 50-YR EV MAY 2023 ROKAMOTO *

FILE NAME: RU50EV26.DAT
TIME/DATE OF STUDY: 11:30 05/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 50.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.515
- 2) 10.00; 3.520
- 3) 15.00; 2.687
- 4) 20.00; 2.242
- 5) 25.00; 1.935
- 6) 30.00; 1.741
- 7) 40.00; 1.473
- 8) 50.00; 1.311
- 9) 60.00; 1.211
- 10) 90.00; 1.007
- 11) 120.00; 0.877
- 12) 180.00; 0.757
- 13) 360.00; 0.563
- 14) 1200.00; 0.248

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	(FT)	(FT)	SIDE / SIDE/ WAY	(FT)	(FT)	(FT)	(FT)	(n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU50EV19.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25952.56	32.64	0.30 (0.30)	0.99	11652.1	40100.00
2	27386.34	40.83	0.30 (0.30)	0.99	14480.1	11801.00
3	29657.15	52.16	0.30 (0.30)	0.99	19064.5	11530.00
4	30794.82	56.77	0.30 (0.30)	0.99	21379.0	11701.00
5	31757.19	60.46	0.30 (0.30)	0.99	23472.2	11910.00
6	34569.59	71.18	0.30 (0.30)	0.99	30166.4	10800.00
7	35325.47	75.55	0.30 (0.30)	0.99	33111.7	11130.00
8	35445.93	82.50	0.30 (0.30)	0.99	36710.1	12330.00
9	35493.85	85.16	0.30 (0.30)	0.99	38152.9	12410.00
10	35415.85	88.02	0.30 (0.30)	0.99	39531.6	10600.00
11	35310.54	93.38	0.30 (0.30)	0.99	41892.0	11201.00
12	35077.23	98.29	0.30 (0.30)	0.99	43623.7	12201.00
13	34813.35	101.00	0.30 (0.30)	0.99	44412.9	10410.00
14	34282.30	105.16	0.30 (0.30)	0.99	45480.9	12231.00
15	33919.79	107.97	0.30 (0.30)	0.99	46154.2	12101.10
16	33204.87	112.70	0.30 (0.30)	0.99	47115.2	10400.00
17	32059.78	120.35	0.30 (0.30)	0.99	48410.3	12010.00
18	31019.66	126.04	0.30 (0.30)	0.99	48757.2	10210.00
19	30570.63	128.97	0.30 (0.30)	0.99	48874.4	12000.00
20	27539.19	153.19	0.30 (0.30)	0.99	49495.7	10100.00
TOTAL AREA(ACRES) =						49495.7

FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25952.56	32.64	0.30 (0.30)	0.99	11652.1	40100.00
2	27386.34	40.83	0.30 (0.30)	0.99	14480.1	11801.00
3	29657.15	52.16	0.30 (0.30)	0.99	19064.5	11530.00
4	30794.82	56.77	0.30 (0.30)	0.99	21379.0	11701.00
5	31757.19	60.46	0.30 (0.30)	0.99	23472.2	11910.00
6	34569.59	71.18	0.30 (0.30)	0.99	30166.4	10800.00
7	35325.47	75.55	0.30 (0.30)	0.99	33111.7	11130.00
8	35445.93	82.50	0.30 (0.30)	0.99	36710.1	12330.00
9	35493.85	85.16	0.30 (0.30)	0.99	38152.9	12410.00
10	35415.85	88.02	0.30 (0.30)	0.99	39531.6	10600.00
11	35310.54	93.38	0.30 (0.30)	0.99	41892.0	11201.00
12	35077.23	98.29	0.30 (0.30)	0.99	43623.7	12201.00
13	34813.35	101.00	0.30 (0.30)	0.99	44412.9	10410.00

14 34282.30 105.16 0.30(0.30) 0.99 45480.9 12231.00
 15 33919.79 107.97 0.30(0.30) 0.99 46154.2 12101.10
 16 33204.87 112.70 0.30(0.30) 0.99 47115.2 10400.00
 17 32059.78 120.35 0.30(0.30) 0.99 48410.3 12010.00
 18 31019.66 126.04 0.30(0.30) 0.99 48757.2 10210.00
 19 30570.63 128.97 0.30(0.30) 0.99 48874.4 12000.00
 20 27539.19 153.19 0.30(0.30) 0.99 49495.7 10100.00
 TOTAL AREA(ACRES) = 49495.7

FLOW PROCESS FROM NODE 11929.00 TO NODE 12601.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 341.63 DOWNSTREAM(FEET) = 325.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1467.93 CHANNEL SLOPE = 0.0113
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 7.89
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.031

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	0.40	0.30	1.000	66
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.50	0.30	1.000	65
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	B	0.90	0.30	1.000	63
NATURAL FAIR COVER "GRASS"	B	0.50	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	11.50	0.30	1.000	66
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.30	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 35498.49
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 18.80
 AVERAGE FLOW DEPTH(FEET) = 7.89 TRAVEL TIME(MIN.) = 1.30
 Tc(MIN.) = 86.46
 SUBAREA AREA(ACRES) = 14.10 SUBAREA RUNOFF(CFS) = 9.28
 EFFECTIVE AREA(ACRES) = 38167.02 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 49509.8 PEAK FLOW RATE(CFS) = 35493.85
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 7.89

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 7.89 FLOW VELOCITY(FEET/SEC.) = 18.80
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap (ACRES)	Ae (ACRES)	HEADWATER NODE
------------------	------------	--------------	------------------------	---------------------	---------------	---------------	-------------------

1	25952.56	34.08	1.632	0.30(0.30)	0.99	11666.2	40100.00
2	27386.34	42.25	1.436	0.30(0.30)	0.99	14494.2	11801.00
3	29657.15	53.54	1.276	0.30(0.30)	0.99	19078.6	11530.00
4	30794.82	58.14	1.230	0.30(0.30)	0.99	21393.1	11701.00
5	31757.19	61.81	1.199	0.30(0.30)	0.99	23486.3	11910.00
6	34569.59	72.49	1.126	0.30(0.30)	0.99	30180.5	10800.00
7	35325.47	76.85	1.096	0.30(0.30)	0.99	33125.8	11130.00
8	35445.93	83.80	1.049	0.30(0.30)	0.99	36724.2	12330.00
9	35493.85	86.46	1.031	0.30(0.30)	0.99	38167.0	12410.00
10	35415.85	89.33	1.012	0.30(0.30)	0.99	39545.7	10600.00
11	35310.54	94.68	0.987	0.30(0.30)	0.99	41906.1	11201.00
12	35077.23	99.59	0.965	0.30(0.30)	0.99	43637.8	12201.00
13	34813.35	102.31	0.954	0.30(0.30)	0.99	44427.0	10410.00
14	34282.30	106.47	0.936	0.30(0.30)	0.99	45495.0	12231.00
15	33919.79	109.29	0.923	0.30(0.30)	0.99	46168.3	12101.10
16	33204.87	114.03	0.903	0.30(0.30)	0.99	47129.3	10400.00
17	32059.78	121.70	0.874	0.30(0.30)	0.99	48424.4	12010.00
18	31019.66	127.40	0.862	0.30(0.30)	0.99	48771.3	10210.00
19	30570.63	130.34	0.856	0.30(0.30)	0.99	48888.6	12000.00
20	27539.19	154.61	0.808	0.30(0.30)	0.99	49509.8	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 35493.85 Tc(MIN.) = 86.46
 AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 38167.02

FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 3050EVRL.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap (ACRES)	Ae (ACRES)	HEADWATER NODE
1	103.71	16.55	0.30(0.29)	0.98	51.1	600.00
TOTAL AREA(ACRES) =		51.1				

FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap (ACRES)	Ae (ACRES)	HEADWATER NODE
1	25952.56	34.08	1.632	0.30(0.30)	0.99	11666.2	40100.00
2	27386.34	42.25	1.436	0.30(0.30)	0.99	14494.2	11801.00
3	29657.15	53.54	1.276	0.30(0.30)	0.99	19078.6	11530.00
4	30794.82	58.14	1.230	0.30(0.30)	0.99	21393.1	11701.00
5	31757.19	61.81	1.199	0.30(0.30)	0.99	23486.3	11910.00
6	34569.59	72.49	1.126	0.30(0.30)	0.99	30180.5	10800.00
7	35325.47	76.85	1.096	0.30(0.30)	0.99	33125.8	11130.00
8	35445.93	83.80	1.049	0.30(0.30)	0.99	36724.2	12330.00
9	35493.85	86.46	1.031	0.30(0.30)	0.99	38167.0	12410.00
10	35415.85	89.33	1.012	0.30(0.30)	0.99	39545.7	10600.00
11	35310.54	94.68	0.987	0.30(0.30)	0.99	41906.1	11201.00
12	35077.23	99.59	0.965	0.30(0.30)	0.99	43637.8	12201.00

13 34813.35 102.31 0.954 0.30(0.30) 0.99 44427.0 10410.00
 14 34282.30 106.47 0.936 0.30(0.30) 0.99 45495.0 12231.00
 15 33919.79 109.29 0.923 0.30(0.30) 0.99 46168.3 12101.10
 16 33204.87 114.03 0.903 0.30(0.30) 0.99 47129.3 10400.00
 17 32059.78 121.70 0.874 0.30(0.30) 0.99 48424.4 12010.00
 18 31019.66 127.40 0.862 0.30(0.30) 0.99 48771.3 10210.00
 19 30570.63 130.34 0.856 0.30(0.30) 0.99 48888.6 12000.00
 20 27539.19 154.61 0.808 0.30(0.30) 0.99 49509.8 10100.00
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	103.71	16.55	2.549	0.30(0.29)	0.98	51.1	600.00

LONGEST FLOWPATH FROM NODE 600.00 TO NODE 12601.00 = 4850.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21375.29	16.55	2.549	0.30(0.30)	0.99	5716.0	600.00
2	26014.07	34.08	1.632	0.30(0.30)	0.99	11717.3	40100.00
3	27438.89	42.25	1.436	0.30(0.30)	0.99	14545.3	11801.00
4	29702.30	53.54	1.276	0.30(0.30)	0.99	19129.7	11530.00
5	30837.85	58.14	1.230	0.30(0.30)	0.99	21444.2	11701.00
6	31798.79	61.81	1.199	0.30(0.30)	0.99	23537.4	11910.00
7	34607.86	72.49	1.126	0.30(0.30)	0.99	30231.6	10800.00
8	35362.37	76.85	1.096	0.30(0.30)	0.99	33176.9	11130.00
9	35480.66	83.80	1.049	0.30(0.30)	0.99	36775.3	12330.00
10	35527.75	86.46	1.031	0.30(0.30)	0.99	38218.1	12410.00
11	35448.85	89.33	1.012	0.30(0.30)	0.99	39596.8	10600.00
12	35342.40	94.68	0.987	0.30(0.30)	0.99	41957.2	11201.00
13	35108.11	99.59	0.965	0.30(0.30)	0.99	43688.9	12201.00
14	34843.69	102.31	0.954	0.30(0.30)	0.99	44478.1	10410.00
15	34311.80	106.47	0.936	0.30(0.30)	0.99	45546.1	12231.00
16	33948.73	109.29	0.923	0.30(0.30)	0.99	46219.4	12101.10
17	33232.87	114.03	0.903	0.30(0.30)	0.99	47180.4	10400.00
18	32086.44	121.70	0.874	0.30(0.30)	0.99	48475.5	12010.00
19	31045.79	127.40	0.862	0.30(0.30)	0.99	48822.4	10210.00
20	30596.49	130.34	0.856	0.30(0.30)	0.99	48939.7	12000.00
21	27562.82	154.61	0.808	0.30(0.30)	0.99	49560.9	10100.00

TOTAL AREA (ACRES) = 49560.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 35527.75 Tc(MIN.) = 86.458
 EFFECTIVE AREA (ACRES) = 38218.12 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 49560.9
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

FLOW PROCESS FROM NODE 12601.00 TO NODE 12603.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 325.00 DOWNSTREAM(FEET) = 310.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1690.00 CHANNEL SLOPE = 0.0089
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 8.46
 CHANNEL FLOW THRU SUBAREA(CFS) = 35527.75
 FLOW VELOCITY(FEET/SEC.) = 17.34 FLOW DEPTH(FEET) = 8.46
 TRAVEL TIME(MIN.) = 1.62 Tc(MIN.) = 88.08
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.45 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21375.29	18.48	2.377	0.30(0.30)	0.99	5716.0	600.00
2	26014.07	35.89	1.583	0.30(0.30)	0.99	11717.3	40100.00
3	27438.89	44.03	1.408	0.30(0.30)	0.99	14545.3	11801.00
4	29702.30	55.26	1.258	0.30(0.30)	0.99	19129.7	11530.00
5	30837.85	59.84	1.213	0.30(0.30)	0.99	21444.2	11701.00
6	31798.79	63.49	1.187	0.30(0.30)	0.99	23537.4	11910.00
7	34607.86	74.13	1.115	0.30(0.30)	0.99	30231.6	10800.00
8	35362.37	78.48	1.085	0.30(0.30)	0.99	33176.9	11130.00
9	35480.66	85.43	1.038	0.30(0.30)	0.99	36775.3	12330.00
10	35527.75	88.08	1.020	0.30(0.30)	0.99	38218.1	12410.00
11	35448.85	90.95	1.003	0.30(0.30)	0.99	39596.8	10600.00
12	35342.40	96.31	0.980	0.30(0.30)	0.99	41957.2	11201.00
13	35108.11	101.23	0.958	0.30(0.30)	0.99	43688.9	12201.00
14	34843.69	103.95	0.947	0.30(0.30)	0.99	44478.1	10410.00
15	34311.80	108.12	0.928	0.30(0.30)	0.99	45546.1	12231.00
16	33948.73	110.94	0.916	0.30(0.30)	0.99	46219.4	12101.10
17	33232.87	115.69	0.896	0.30(0.30)	0.99	47180.4	10400.00
18	32086.44	123.38	0.870	0.30(0.30)	0.99	48475.5	12010.00
19	31045.79	129.10	0.859	0.30(0.30)	0.99	48822.4	10210.00
20	30596.49	132.05	0.853	0.30(0.30)	0.99	48939.7	12000.00
21	27562.82	156.38	0.804	0.30(0.30)	0.99	49560.9	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 35527.75 Tc(MIN.) = 88.08
 AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA (ACRES) = 38218.12

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 4E50EVRL.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	496.91	9.20	0.30(0.16)	0.52	148.3	800.00
2	445.43	12.80	0.30(0.17)	0.57	168.2	818.00
3	420.20	13.91	0.30(0.17)	0.58	171.0	810.00

TOTAL AREA (ACRES) = 171.0

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 11

=====
>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<
=====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21375.29	18.48	2.377	0.30(0.30)	0.99	5716.0	600.00
2	26014.07	35.89	1.583	0.30(0.30)	0.99	11717.3	40100.00
3	27438.89	44.03	1.408	0.30(0.30)	0.99	14545.3	11801.00
4	29702.30	55.26	1.258	0.30(0.30)	0.99	19129.7	11530.00
5	30837.85	59.84	1.213	0.30(0.30)	0.99	21444.2	11701.00
6	31798.79	63.49	1.187	0.30(0.30)	0.99	23537.4	11910.00
7	34607.86	74.13	1.115	0.30(0.30)	0.99	30231.6	10800.00
8	35362.37	78.48	1.085	0.30(0.30)	0.99	33176.9	11130.00
9	35480.66	85.43	1.038	0.30(0.30)	0.99	36775.3	12330.00
10	35527.75	88.08	1.020	0.30(0.30)	0.99	38218.1	12410.00
11	35448.85	90.95	1.003	0.30(0.30)	0.99	39596.8	10600.00
12	35342.40	96.31	0.980	0.30(0.30)	0.99	41957.2	11201.00
13	35108.11	101.23	0.958	0.30(0.30)	0.99	43688.9	12201.00
14	34843.69	103.95	0.947	0.30(0.30)	0.99	44478.1	10410.00
15	34311.80	108.12	0.928	0.30(0.30)	0.99	45546.1	12231.00
16	33948.73	110.94	0.916	0.30(0.30)	0.99	46219.4	12101.10
17	33232.87	115.69	0.896	0.30(0.30)	0.99	47180.4	10400.00
18	32086.44	123.38	0.870	0.30(0.30)	0.99	48475.5	12010.00
19	31045.79	129.10	0.859	0.30(0.30)	0.99	48822.4	10210.00
20	30596.49	132.05	0.853	0.30(0.30)	0.99	48939.7	12000.00
21	27562.82	156.38	0.804	0.30(0.30)	0.99	49560.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.45 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	496.91	9.20	3.838	0.30(0.16)	0.52	148.3	800.00
2	445.43	12.80	3.054	0.30(0.17)	0.57	168.2	818.00
3	420.20	13.91	2.869	0.30(0.17)	0.58	171.0	810.00

LONGEST FLOWPATH FROM NODE 810.00 TO NODE 12603.00 = 3814.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18619.66	9.20	3.838	0.30(0.29)	0.97	2995.0	800.00
2	20064.17	12.80	3.054	0.30(0.29)	0.98	4126.0	818.00
3	20310.97	13.91	2.869	0.30(0.29)	0.98	4473.2	810.00
4	21718.85	18.48	2.377	0.30(0.29)	0.98	5887.0	600.00
5	26233.80	35.89	1.583	0.30(0.30)	0.99	11888.3	40100.00
6	27631.27	44.03	1.408	0.30(0.30)	0.99	14716.3	11801.00
7	29871.38	55.26	1.258	0.30(0.30)	0.99	19300.7	11530.00
8	30999.79	59.84	1.213	0.30(0.30)	0.99	21615.2	11701.00
9	31956.79	63.49	1.187	0.30(0.30)	0.99	23708.4	11910.00
10	34754.57	74.13	1.115	0.30(0.30)	0.99	30402.6	10800.00
11	35504.47	78.48	1.085	0.30(0.30)	0.99	33347.9	11130.00
12	35615.40	85.43	1.038	0.30(0.30)	0.99	36946.3	12330.00
13	35659.67	88.08	1.020	0.30(0.30)	0.99	38389.1	12410.00
14	35578.09	90.95	1.003	0.30(0.30)	0.99	39767.8	10600.00
15	35468.02	96.31	0.980	0.30(0.30)	0.99	42128.2	11201.00
16	35230.41	101.23	0.958	0.30(0.30)	0.99	43859.9	12201.00
17	34964.15	103.95	0.947	0.30(0.30)	0.99	44649.1	10410.00

18	34429.45	108.12	0.928	0.30(0.30)	0.99	45717.1	12231.00
19	34064.46	110.94	0.916	0.30(0.30)	0.99	46390.4	12101.10
20	33345.40	115.69	0.896	0.30(0.30)	0.99	47351.4	10400.00
21	32195.00	123.38	0.870	0.30(0.30)	0.99	48646.5	12010.00
22	31152.57	129.10	0.859	0.30(0.30)	0.99	48993.4	10210.00
23	30702.35	132.05	0.853	0.30(0.30)	0.99	49110.7	12000.00
24	27661.10	156.38	0.804	0.30(0.30)	0.99	49731.9	10100.00

TOTAL AREA (ACRES) = 49731.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 35659.67 Tc (MIN.) = 88.083
EFFECTIVE AREA (ACRES) = 38389.12 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 49731.9
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.45 FEET.

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

=====
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====

MAINLINE Tc (MIN.) = 88.08
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.020
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.20	0.30	1.000	65
NATURAL FAIR COVER "OPEN BRUSH"	B	1.30	0.30	1.000	66
PUBLIC PARK	B	1.30	0.30	0.850	56
COMMERCIAL	B	1.40	0.30	0.100	56
RESIDENTIAL ".4 DWELLING/ACRE"	B	1.70	0.30	0.900	56
NATURAL FAIR COVER "OPEN BRUSH"	B	12.40	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.911
SUBAREA AREA (ACRES) = 18.30 SUBAREA RUNOFF (CFS) = 12.30
EFFECTIVE AREA (ACRES) = 38407.42 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 49750.2 PEAK FLOW RATE (CFS) = 35659.67
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

=====
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====

MAINLINE Tc (MIN.) = 88.08
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.020
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "WOODLAND, GRASS"	B	26.90	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 26.90 SUBAREA RUNOFF (CFS) = 17.43
 EFFECTIVE AREA (ACRES) = 38434.32 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 49777.1 PEAK FLOW RATE (CFS) = 35659.67
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 88.08
 * 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.020
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	0.50	0.30	1.000	63
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.40	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL, NARROWLEAF"	B	0.40	0.30	1.000	72
NATURAL FAIR COVER					
"GRASS"	B	0.60	0.30	1.000	69
PUBLIC PARK	B	0.70	0.30	0.850	56
NATURAL FAIR COVER					
"CHAPARRAL, NARROWLEAF"	B	0.70	0.30	1.000	72

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.968
 SUBAREA AREA (ACRES) = 3.30 SUBAREA RUNOFF (CFS) = 2.17
 EFFECTIVE AREA (ACRES) = 38437.62 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 49780.4 PEAK FLOW RATE (CFS) = 35659.67
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 88.08
 * 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.020
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.00	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.20	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	1.70	0.30	0.900	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.90	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	2.10	0.30	0.900	56
NATURAL FAIR COVER					
"CHAPARRAL, NARROWLEAF"	B	2.90	0.30	1.000	72

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.965
 SUBAREA AREA (ACRES) = 10.80 SUBAREA RUNOFF (CFS) = 7.10
 EFFECTIVE AREA (ACRES) = 38448.42 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 49791.2 PEAK FLOW RATE (CFS) = 35659.67
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 88.08
 * 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.020
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	5.60	0.30	1.000	65
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	9.00	0.30	1.000	65

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 14.60 SUBAREA RUNOFF (CFS) = 9.46
 EFFECTIVE AREA (ACRES) = 38463.02 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 49805.8 PEAK FLOW RATE (CFS) = 35659.67
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12603.00 TO NODE 12605.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 310.00 DOWNSTREAM (FEET) = 305.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 885.00 CHANNEL SLOPE = 0.0056
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT (FEET) = 9.63
 CHANNEL FLOW THRU SUBAREA (CFS) = 35659.67
 FLOW VELOCITY (FEET/SEC.) = 14.92 FLOW DEPTH (FEET) = 9.63
 TRAVEL TIME (MIN.) = 0.99 Tc (MIN.) = 89.07
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.00 = 102443.45 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18619.66	10.43	3.448	0.30 (0.29)	0.97	3068.9	800.00
2	20064.17	13.99	2.855	0.30 (0.29)	0.98	4199.9	818.00
3	20310.97	15.10	2.678	0.30 (0.29)	0.98	4547.1	810.00
4	21718.85	19.65	2.274	0.30 (0.29)	0.98	5960.9	600.00
5	26233.80	36.98	1.554	0.30 (0.30)	0.99	11962.2	40100.00
6	27631.27	45.10	1.390	0.30 (0.30)	0.99	14790.2	11801.00
7	29871.38	56.31	1.248	0.30 (0.30)	0.99	19374.6	11530.00
8	30999.79	60.88	1.205	0.30 (0.30)	0.99	21689.1	11701.00
9	31956.79	64.52	1.180	0.30 (0.30)	0.99	23782.3	11910.00
10	34754.57	75.13	1.108	0.30 (0.30)	0.99	30476.5	10800.00

11	35504.47	79.47	1.079	0.30	(0.30)	0.99	33421.8	11130.00
12	35615.40	86.42	1.031	0.30	(0.30)	0.99	37020.2	12330.00
13	35659.67	89.07	1.013	0.30	(0.30)	0.99	38463.0	12410.00
14	35578.09	91.94	0.999	0.30	(0.30)	0.99	39841.7	10600.00
15	35468.02	97.30	0.975	0.30	(0.30)	0.99	42202.1	11201.00
16	35230.41	102.22	0.954	0.30	(0.30)	0.99	43933.8	12201.00
17	34964.15	104.94	0.942	0.30	(0.30)	0.99	44723.0	10410.00
18	34429.45	109.12	0.924	0.30	(0.30)	0.99	45791.0	12231.00
19	34064.46	111.95	0.912	0.30	(0.30)	0.99	46464.3	12101.10
20	33345.40	116.70	0.891	0.30	(0.30)	0.99	47425.3	10400.00
21	32195.00	124.40	0.868	0.30	(0.30)	0.99	48720.4	12010.00
22	31152.57	130.14	0.857	0.30	(0.30)	0.99	49067.3	10210.00
23	30702.35	133.09	0.851	0.30	(0.30)	0.99	49184.6	12000.00
24	27661.10	157.45	0.802	0.30	(0.30)	0.99	49805.8	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 35659.67 Tc(MIN.) = 89.07
 AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 38463.02

 FLOW PROCESS FROM NODE 12605.00 TO NODE 12605.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 89.07

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.013

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS,STRAIGHT ROW"	B	0.50	0.30	1.000	81
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.70	0.30	1.000	65
PUBLIC PARK	B	1.30	0.30	0.850	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	1.30	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS,STRAIGHT ROW"	B	1.90	0.30	1.000	81
PUBLIC PARK	B	2.10	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.918
 SUBAREA AREA(ACRES) = 7.80 SUBAREA RUNOFF(CFS) = 5.18
 EFFECTIVE AREA(ACRES) = 38470.82 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 49813.6 PEAK FLOW RATE(CFS) = 35659.67
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12605.00 TO NODE 12605.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 89.07

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.013

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					

"OPEN BRUSH"	B	3.20	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	3.50	0.30	1.000	65
PUBLIC PARK	B	6.10	0.30	0.850	56
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.929					
SUBAREA AREA(ACRES) = 12.80 SUBAREA RUNOFF(CFS) = 8.46					
EFFECTIVE AREA(ACRES) = 38483.62 AREA-AVERAGED Fm(INCH/HR) = 0.30					
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99					
TOTAL AREA(ACRES) = 49826.4 PEAK FLOW RATE(CFS) = 35659.67					
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE					

 FLOW PROCESS FROM NODE 12605.00 TO NODE 12606.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 305.00 DOWNSTREAM(FEET) = 286.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2159.47 CHANNEL SLOPE = 0.0088
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 8.50
 CHANNEL FLOW THRU SUBAREA(CFS) = 35659.67
 FLOW VELOCITY(FEET/SEC.) = 17.31 FLOW DEPTH(FEET) = 8.50
 TRAVEL TIME(MIN.) = 2.08 Tc(MIN.) = 91.15
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104602.91 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18619.66	13.02	3.016	0.30(0.29)	0.97	3089.5	800.00
2	20064.17	16.52	2.552	0.30(0.29)	0.98	4220.5	818.00
3	20310.97	17.62	2.454	0.30(0.29)	0.98	4567.7	810.00
4	21718.85	22.10	2.113	0.30(0.29)	0.98	5981.5	600.00
5	26233.80	39.29	1.492	0.30(0.30)	0.99	11982.8	40100.00
6	27631.27	47.37	1.354	0.30(0.30)	0.99	14810.8	11801.00
7	29871.38	58.52	1.226	0.30(0.30)	0.99	19395.2	11530.00
8	30999.79	63.05	1.190	0.30(0.30)	0.99	21709.7	11701.00
9	31956.79	66.68	1.166	0.30(0.30)	0.99	23802.9	11910.00
10	34754.57	77.22	1.094	0.30(0.30)	0.99	30497.1	10800.00
11	35504.47	81.55	1.064	0.30(0.30)	0.99	33442.4	11130.00
12	35615.40	88.50	1.017	0.30(0.30)	0.99	37040.8	12330.00
13	35659.67	91.15	1.002	0.30(0.30)	0.99	38483.6	12410.00
14	35578.09	94.02	0.990	0.30(0.30)	0.99	39862.3	10600.00
15	35468.02	99.39	0.966	0.30(0.30)	0.99	42222.7	11201.00
16	35230.41	104.31	0.945	0.30(0.30)	0.99	43954.4	12201.00
17	34964.15	107.03	0.933	0.30(0.30)	0.99	44743.6	10410.00
18	34429.45	111.22	0.915	0.30(0.30)	0.99	45811.6	12231.00
19	34064.46	114.06	0.903	0.30(0.30)	0.99	46484.9	12101.10
20	33345.40	118.83	0.882	0.30(0.30)	0.99	47445.9	10400.00
21	32195.00	126.55	0.864	0.30(0.30)	0.99	48741.0	12010.00
22	31152.57	132.31	0.852	0.30(0.30)	0.99	49087.9	10210.00
23	30702.35	135.27	0.846	0.30(0.30)	0.99	49205.2	12000.00
24	27661.10	159.72	0.798	0.30(0.30)	0.99	49826.4	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 35659.67 Tc(MIN.) = 91.15
 AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 38483.62

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 4F50EVRL.DNA
MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1127.73	9.96	0.30	(0.24)	0.79	379.9	940.00
2	1132.56	10.20	0.30	(0.24)	0.79	387.3	930.00
3	1160.93	12.96	0.30	(0.25)	0.82	463.7	910.00
4	1137.62	16.43	0.30	(0.25)	0.85	548.3	920.00
5	1114.54	17.20	0.30	(0.25)	0.85	553.8	950.00
6	1085.95	17.85	0.30	(0.25)	0.85	553.8	900.00
TOTAL AREA(ACRES) =							553.8

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18619.66	13.02	3.016	0.30	(0.29)	0.97	3089.5 800.00
2	20064.17	16.52	2.552	0.30	(0.29)	0.98	4220.5 818.00
3	20310.97	17.62	2.454	0.30	(0.29)	0.98	4567.7 810.00
4	21718.85	22.10	2.113	0.30	(0.29)	0.98	5981.5 600.00
5	26233.80	39.29	1.492	0.30	(0.30)	0.99	11982.8 40100.00
6	27631.27	47.37	1.354	0.30	(0.30)	0.99	14810.8 11801.00
7	29871.38	58.52	1.226	0.30	(0.30)	0.99	19395.2 11530.00
8	30999.79	63.05	1.190	0.30	(0.30)	0.99	21709.7 11701.00
9	31956.79	66.68	1.166	0.30	(0.30)	0.99	23802.9 11910.00
10	34754.57	77.22	1.094	0.30	(0.30)	0.99	30497.1 10800.00
11	35504.47	81.55	1.064	0.30	(0.30)	0.99	33442.4 11130.00
12	35615.40	88.50	1.017	0.30	(0.30)	0.99	37040.8 12330.00
13	35659.67	91.15	1.002	0.30	(0.30)	0.99	38483.6 12410.00
14	35578.09	94.02	0.990	0.30	(0.30)	0.99	39862.3 10600.00
15	35468.02	99.39	0.966	0.30	(0.30)	0.99	42222.7 11201.00
16	35230.41	104.31	0.945	0.30	(0.30)	0.99	43954.4 12201.00
17	34964.15	107.03	0.933	0.30	(0.30)	0.99	44743.6 10410.00
18	34429.45	111.22	0.915	0.30	(0.30)	0.99	45811.6 12231.00
19	34064.46	114.06	0.903	0.30	(0.30)	0.99	46484.9 12101.10
20	33345.40	118.83	0.882	0.30	(0.30)	0.99	47445.9 10400.00
21	32195.00	126.55	0.864	0.30	(0.30)	0.99	48741.0 12010.00
22	31152.57	132.31	0.852	0.30	(0.30)	0.99	49087.9 10210.00
23	30702.35	135.27	0.846	0.30	(0.30)	0.99	49205.2 12000.00
24	27661.10	159.72	0.798	0.30	(0.30)	0.99	49826.4 10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104602.91 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1127.73	9.96	3.535	0.30	(0.24)	0.79	379.9 940.00

2	1132.56	10.20	3.486	0.30	(0.24)	0.79	387.3 930.00
3	1160.93	12.96	3.028	0.30	(0.25)	0.82	463.7 910.00
4	1137.62	16.43	2.560	0.30	(0.25)	0.85	548.3 920.00
5	1114.54	17.20	2.491	0.30	(0.25)	0.85	553.8 950.00
6	1085.95	17.85	2.433	0.30	(0.25)	0.85	553.8 900.00

LONGEST FLOWPATH FROM NODE 920.00 TO NODE 12606.00 = 6933.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18081.63	9.96	3.535	0.30	(0.28)	0.94	2743.4 940.00
2	18235.44	10.20	3.486	0.30	(0.28)	0.94	2807.9 930.00
3	19760.62	12.96	3.028	0.30	(0.28)	0.95	3537.3 910.00
4	19780.14	13.02	3.016	0.30	(0.28)	0.95	3554.8 800.00
5	21165.54	16.43	2.560	0.30	(0.29)	0.96	4740.4 920.00
6	21199.17	16.52	2.552	0.30	(0.29)	0.96	4769.4 818.00
7	21332.24	17.20	2.491	0.30	(0.29)	0.96	4990.2 950.00
8	21407.15	17.62	2.454	0.30	(0.29)	0.96	5121.4 810.00
9	21469.53	17.85	2.433	0.30	(0.29)	0.96	5194.4 900.00
10	22644.95	22.10	2.113	0.30	(0.29)	0.97	6535.3 600.00
11	26850.56	39.29	1.492	0.30	(0.29)	0.98	12536.6 40100.00
12	28179.02	47.37	1.354	0.30	(0.29)	0.98	15364.6 11801.00
13	30355.40	58.52	1.226	0.30	(0.30)	0.99	19949.0 11530.00
14	31466.08	63.05	1.190	0.30	(0.30)	0.99	22263.5 11701.00
15	32410.79	66.68	1.166	0.30	(0.30)	0.99	24356.7 11910.00
16	35172.83	77.22	1.094	0.30	(0.30)	0.99	31050.9 10800.00
17	35908.05	81.55	1.064	0.30	(0.30)	0.99	33996.2 11130.00
18	35995.45	88.50	1.017	0.30	(0.30)	0.99	37594.6 12330.00
19	36032.14	91.15	1.002	0.30	(0.30)	0.99	39037.4 12410.00
20	35944.36	94.02	0.990	0.30	(0.30)	0.99	40416.1 10600.00
21	35822.70	99.39	0.966	0.30	(0.30)	0.99	42776.5 11201.00
22	35574.46	104.31	0.945	0.30	(0.30)	0.99	44508.2 12201.00
23	35302.32	107.03	0.933	0.30	(0.30)	0.99	45297.4 10410.00
24	34758.58	111.22	0.915	0.30	(0.30)	0.99	46365.4 12231.00
25	34387.46	114.06	0.903	0.30	(0.30)	0.99	47038.7 12101.10
26	33658.09	118.83	0.882	0.30	(0.30)	0.99	47999.7 10400.00
27	32498.63	126.55	0.864	0.30	(0.30)	0.99	49294.8 12010.00
28	31450.46	132.31	0.852	0.30	(0.30)	0.99	49641.8 10210.00
29	30997.29	135.27	0.846	0.30	(0.30)	0.99	49759.0 12000.00
30	27931.67	159.72	0.798	0.30	(0.30)	0.99	50380.2 10100.00
TOTAL AREA(ACRES) =							50380.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 36032.14 Tc(MIN.) = 91.151
EFFECTIVE AREA(ACRES) = 39037.42 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 50380.2
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104602.91 FEET.

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 91.15
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.002
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS

LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

NATURAL FAIR COVER
 "CHAPARRAL,BROADLEAF" B 0.30 0.30 1.000 63
 NATURAL FAIR COVER
 "GRASS" B 0.30 0.30 1.000 69
 PUBLIC PARK B 0.40 0.30 0.850 56
 NATURAL FAIR COVER
 "CHAPARRAL,NARROWLEAF" B 0.60 0.30 1.000 72
 COMMERCIAL B 1.10 0.30 0.100 56
 PUBLIC PARK B 0.80 0.30 0.850 56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.666
 SUBAREA AREA(ACRES) = 3.50 SUBAREA RUNOFF(CFS) = 2.53
 EFFECTIVE AREA(ACRES) = 39040.92 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 50383.7 PEAK FLOW RATE(CFS) = 36032.14
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

 MAINLINE Tc(MIN.) = 91.15
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.002
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

NATURAL FAIR COVER
 "GRASS" B 0.80 0.30 1.000 69
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 0.90 0.30 1.000 65
 AGRICULTURAL POOR COVER
 "ROW CROPS,STRAIGHT ROW" B 1.50 0.30 1.000 81
 NATURAL FAIR COVER
 "OPEN BRUSH" B 1.60 0.30 1.000 66
 NATURAL FAIR COVER
 "OPEN BRUSH" B 1.80 0.30 1.000 66
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 1.90 0.30 1.000 65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 8.50 SUBAREA RUNOFF(CFS) = 5.37
 EFFECTIVE AREA(ACRES) = 39049.42 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 50392.2 PEAK FLOW RATE(CFS) = 36032.14
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

 MAINLINE Tc(MIN.) = 91.15
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.002
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

NATURAL FAIR COVER
 "OPEN BRUSH" B 3.30 0.30 1.000 66
 PUBLIC PARK B 3.70 0.30 0.850 56
 NATURAL FAIR COVER
 "CHAPARRAL,NARROWLEAF" B 3.90 0.30 1.000 72
 PUBLIC PARK B 5.90 0.30 0.850 56
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 9.10 0.30 1.000 65
 NATURAL FAIR COVER
 "OPEN BRUSH" B 20.60 0.30 1.000 66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.969
 SUBAREA AREA(ACRES) = 46.50 SUBAREA RUNOFF(CFS) = 29.77
 EFFECTIVE AREA(ACRES) = 39095.92 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA(ACRES) = 50438.7 PEAK FLOW RATE(CFS) = 36032.14
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

=====

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 50438.7 TC(MIN.) = 91.15
 EFFECTIVE AREA(ACRES) = 39095.92 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.990
 PEAK FLOW RATE(CFS) = 36032.14

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18081.63	9.96	3.535	0.30(0.28)	0.94	2801.9	940.00
2	18235.44	10.20	3.486	0.30(0.28)	0.94	2866.4	930.00
3	19760.62	12.96	3.028	0.30(0.28)	0.95	3595.8	910.00
4	19780.14	13.02	3.016	0.30(0.28)	0.95	3613.3	800.00
5	21165.54	16.43	2.560	0.30(0.29)	0.96	4798.9	920.00
6	21199.17	16.52	2.552	0.30(0.29)	0.96	4827.9	818.00
7	21332.24	17.20	2.491	0.30(0.29)	0.96	5048.7	950.00
8	21407.15	17.62	2.454	0.30(0.29)	0.96	5179.9	810.00
9	21469.53	17.85	2.433	0.30(0.29)	0.96	5252.9	900.00
10	22644.95	22.10	2.113	0.30(0.29)	0.97	6593.8	600.00
11	26850.56	39.29	1.492	0.30(0.29)	0.98	12595.1	40100.00
12	28179.02	47.37	1.354	0.30(0.29)	0.98	15423.1	11801.00
13	30355.40	58.52	1.226	0.30(0.30)	0.99	20007.5	11530.00
14	31466.08	63.05	1.190	0.30(0.30)	0.99	22322.0	11701.00
15	32410.79	66.68	1.166	0.30(0.30)	0.99	24415.2	11910.00
16	35172.83	77.22	1.094	0.30(0.30)	0.99	31109.4	10800.00
17	35908.05	81.55	1.064	0.30(0.30)	0.99	34054.7	11130.00
18	35995.45	88.50	1.017	0.30(0.30)	0.99	37653.1	12330.00
19	36032.14	91.15	1.002	0.30(0.30)	0.99	39095.9	12410.00
20	35944.36	94.02	0.990	0.30(0.30)	0.99	40474.6	10600.00
21	35822.70	99.39	0.966	0.30(0.30)	0.99	42835.0	11201.00
22	35574.46	104.31	0.945	0.30(0.30)	0.99	44566.7	12201.00
23	35302.32	107.03	0.933	0.30(0.30)	0.99	45355.9	10410.00
24	34758.58	111.22	0.915	0.30(0.30)	0.99	46423.9	12231.00
25	34387.46	114.06	0.903	0.30(0.30)	0.99	47097.2	12101.10
26	33658.09	118.83	0.882	0.30(0.30)	0.99	48058.2	10400.00
27	32498.63	126.55	0.864	0.30(0.30)	0.99	49353.3	12010.00
28	31450.46	132.31	0.852	0.30(0.30)	0.99	49700.2	10210.00
29	30997.29	135.27	0.846	0.30(0.30)	0.99	49817.5	12000.00
30	27931.67	159.72	0.798	0.30(0.30)	0.99	50438.7	10100.00

=====

=====
END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 127 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 50-YR EV MAY 2023 ROKAMOTO *

FILE NAME: RU50EV27.DAT
TIME/DATE OF STUDY: 11:30 05/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 50.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.469
- 2) 10.00; 3.498
- 3) 15.00; 2.675
- 4) 20.00; 2.233
- 5) 25.00; 1.929
- 6) 30.00; 1.735
- 7) 40.00; 1.468
- 8) 50.00; 1.307
- 9) 60.00; 1.204
- 10) 90.00; 1.001
- 11) 120.00; 0.871
- 12) 180.00; 0.750
- 13) 360.00; 0.557
- 14) 1200.00; 0.245

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	(FT)	(FT)	SIDE / SIDE/ WAY	(FT)	(FT)	(FT)	(FT)	(n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU50EV26.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19780.14	13.02	0.30 (0.28)	0.95	3613.3	800.00
2	21469.53	17.85	0.30 (0.29)	0.96	5252.9	900.00
3	22644.95	22.10	0.30 (0.29)	0.97	6593.8	600.00
4	26850.56	39.29	0.30 (0.29)	0.98	12595.1	40100.00
5	28179.02	47.37	0.30 (0.29)	0.98	15423.1	11801.00
6	30355.40	58.52	0.30 (0.30)	0.99	20007.5	11530.00
7	31466.08	63.05	0.30 (0.30)	0.99	22322.0	11701.00
8	32410.79	66.68	0.30 (0.30)	0.99	24415.2	11910.00
9	35172.83	77.22	0.30 (0.30)	0.99	31109.4	10800.00
10	35908.05	81.55	0.30 (0.30)	0.99	34054.7	11130.00
11	36032.14	91.15	0.30 (0.30)	0.99	39095.9	12410.00
12	35822.70	99.39	0.30 (0.30)	0.99	42835.0	11201.00
13	35574.46	104.31	0.30 (0.30)	0.99	44566.7	12201.00
14	34758.58	111.22	0.30 (0.30)	0.99	46423.9	12231.00
15	34387.46	114.06	0.30 (0.30)	0.99	47097.2	12101.10
16	33658.09	118.83	0.30 (0.30)	0.99	48058.2	10400.00
17	32498.63	126.55	0.30 (0.30)	0.99	49353.3	12010.00
18	31450.46	132.31	0.30 (0.30)	0.99	49700.2	10210.00
19	30997.29	135.27	0.30 (0.30)	0.99	49817.5	12000.00
20	27931.67	159.72	0.30 (0.30)	0.99	50438.7	10100.00
TOTAL AREA(ACRES) =						50438.7

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19780.14	13.02	0.30 (0.28)	0.95	3613.3	800.00
2	21469.53	17.85	0.30 (0.29)	0.96	5252.9	900.00
3	22644.95	22.10	0.30 (0.29)	0.97	6593.8	600.00
4	26850.56	39.29	0.30 (0.29)	0.98	12595.1	40100.00
5	28179.02	47.37	0.30 (0.29)	0.98	15423.1	11801.00
6	30355.40	58.52	0.30 (0.30)	0.99	20007.5	11530.00
7	31466.08	63.05	0.30 (0.30)	0.99	22322.0	11701.00
8	32410.79	66.68	0.30 (0.30)	0.99	24415.2	11910.00
9	35172.83	77.22	0.30 (0.30)	0.99	31109.4	10800.00
10	35908.05	81.55	0.30 (0.30)	0.99	34054.7	11130.00
11	36032.14	91.15	0.30 (0.30)	0.99	39095.9	12410.00
12	35822.70	99.39	0.30 (0.30)	0.99	42835.0	11201.00
13	35574.46	104.31	0.30 (0.30)	0.99	44566.7	12201.00

14 34758.58 111.22 0.30(0.30) 0.99 46423.9 12231.00
15 34387.46 114.06 0.30(0.30) 0.99 47097.2 12101.10
16 33658.09 118.83 0.30(0.30) 0.99 48058.2 10400.00
17 32498.63 126.55 0.30(0.30) 0.99 49353.3 12010.00
18 31450.46 132.31 0.30(0.30) 0.99 49700.2 10210.00
19 30997.29 135.27 0.30(0.30) 0.99 49817.5 12000.00
20 27931.67 159.72 0.30(0.30) 0.99 50438.7 10100.00
TOTAL AREA(ACRES) = 50438.7

FLOW PROCESS FROM NODE 12606.00 TO NODE 12701.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 286.00 DOWNSTREAM(FEET) = 276.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1260.19 CHANNEL SLOPE = 0.0079
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT(FEET) = 8.81

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.991

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

RESIDENTIAL					
"5-7 DWELLINGS/ACRE"	B	0.70	0.30	0.500	56
PUBLIC PARK	B	0.90	0.30	0.850	56
COMMERCIAL	B	3.40	0.30	0.100	56
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	3.60	0.30	1.000	65
PUBLIC PARK	B	10.10	0.30	0.850	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	17.40	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.860

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 36044.05

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 16.78

AVERAGE FLOW DEPTH(FEET) = 8.80 TRAVEL TIME(MIN.) = 1.25

Tc(MIN.) = 92.40

SUBAREA AREA(ACRES) = 36.10 SUBAREA RUNOFF(CFS) = 23.80

EFFECTIVE AREA(ACRES) = 39132.02 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 50474.8 PEAK FLOW RATE(CFS) = 36032.14

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT(FEET) = 8.80

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 8.80 FLOW VELOCITY(FEET/SEC.) = 16.78

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12701.00 = 105863.10 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19780.14	14.55	2.748	0.30(0.28)	0.95	3649.4	800.00
2	21469.53	19.34	2.292	0.30(0.29)	0.96	5289.0	900.00
3	22644.95	23.57	2.016	0.30(0.29)	0.97	6629.9	600.00

4 26850.56 40.67 1.457 0.30(0.29) 0.98 12631.2 40100.00
5 28179.02 48.72 1.328 0.30(0.29) 0.98 15459.2 11801.00
6 30355.40 59.84 1.206 0.30(0.30) 0.99 20043.6 11530.00
7 31466.08 64.36 1.174 0.30(0.30) 0.99 22358.1 11701.00
8 32410.79 67.97 1.150 0.30(0.30) 0.99 24451.3 11910.00
9 35172.83 78.48 1.079 0.30(0.30) 0.99 31145.5 10800.00
10 35908.05 82.81 1.050 0.30(0.30) 0.99 34090.8 11130.00
11 36032.14 92.40 0.991 0.30(0.30) 0.99 39132.0 12410.00
12 35822.70 100.64 0.955 0.30(0.30) 0.99 42871.1 11201.00
13 35574.46 105.57 0.934 0.30(0.30) 0.99 44602.8 12201.00
14 34758.58 112.49 0.904 0.30(0.30) 0.99 46460.0 12231.00
15 34387.46 115.33 0.891 0.30(0.30) 0.99 47133.3 12101.10
16 33658.09 120.11 0.871 0.30(0.30) 0.99 48094.3 10400.00
17 32498.63 127.85 0.855 0.30(0.30) 0.99 49389.4 12010.00
18 31450.46 133.62 0.844 0.30(0.30) 0.99 49736.4 10210.00
19 30997.29 136.59 0.838 0.30(0.30) 0.99 49853.6 12000.00
20 27931.67 161.08 0.788 0.30(0.30) 0.99 50474.8 10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 36032.14 Tc(MIN.) = 92.40

AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 39132.02

FLOW PROCESS FROM NODE 12701.00 TO NODE 12720.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 276.00 DOWNSTREAM(FEET) = 275.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 147.65 CHANNEL SLOPE = 0.0068
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT(FEET) = 9.21

CHANNEL FLOW THRU SUBAREA(CFS) = 36032.14

FLOW VELOCITY(FEET/SEC.) = 15.91 FLOW DEPTH(FEET) = 9.21

TRAVEL TIME(MIN.) = 0.15 Tc(MIN.) = 92.56

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.00 = 106010.75 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19780.14	14.74	2.717	0.30(0.28)	0.95	3649.4	800.00
2	21469.53	19.52	2.275	0.30(0.29)	0.96	5289.0	900.00
3	22644.95	23.75	2.005	0.30(0.29)	0.97	6629.9	600.00
4	26850.56	40.84	1.455	0.30(0.29)	0.98	12631.2	40100.00
5	28179.02	48.89	1.325	0.30(0.29)	0.98	15459.2	11801.00
6	30355.40	60.01	1.204	0.30(0.30)	0.99	20043.6	11530.00
7	31466.08	64.53	1.173	0.30(0.30)	0.99	22358.1	11701.00
8	32410.79	68.13	1.149	0.30(0.30)	0.99	24451.3	11910.00
9	35172.83	78.64	1.078	0.30(0.30)	0.99	31145.5	10800.00
10	35908.05	82.96	1.049	0.30(0.30)	0.99	34090.8	11130.00
11	36032.14	92.56	0.990	0.30(0.30)	0.99	39132.0	12410.00
12	35822.70	100.80	0.954	0.30(0.30)	0.99	42871.1	11201.00
13	35574.46	105.72	0.933	0.30(0.30)	0.99	44602.8	12201.00
14	34758.58	112.64	0.903	0.30(0.30)	0.99	46460.0	12231.00
15	34387.46	115.49	0.891	0.30(0.30)	0.99	47133.3	12101.10
16	33658.09	120.27	0.870	0.30(0.30)	0.99	48094.3	10400.00
17	32498.63	128.01	0.855	0.30(0.30)	0.99	49389.4	12010.00

18 31450.46 133.78 0.843 0.30(0.30) 0.99 49736.4 10210.00
19 30997.29 136.75 0.837 0.30(0.30) 0.99 49853.6 12000.00
20 27931.67 161.25 0.788 0.30(0.30) 0.99 50474.8 10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 36032.14 Tc(MIN.) = 92.56
AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 39132.02

FLOW PROCESS FROM NODE 12701.00 TO NODE 12720.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

=====

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION(MIN.) = 92.56
RAINFALL INTENSITY(INCH/HR) = 0.99
AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.99
EFFECTIVE STREAM AREA(ACRES) = 39132.02
TOTAL STREAM AREA(ACRES) = 50474.79
PEAK FLOW RATE(CFS) AT CONFLUENCE = 36032.14

FLOW PROCESS FROM NODE 12710.00 TO NODE 12711.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 943.56
ELEVATION DATA: UPSTREAM(FEET) = 940.78 DOWNSTREAM(FEET) = 657.79

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 13.910
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.854
SUBAREA Tc AND LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)
NATURAL FAIR COVER
"GRASS" B 6.56 0.30 1.000 69 13.91
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 15.08
TOTAL AREA(ACRES) = 6.56 PEAK FLOW RATE(CFS) = 15.08

FLOW PROCESS FROM NODE 12711.00 TO NODE 12712.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 657.79 DOWNSTREAM(FEET) = 585.63
CHANNEL LENGTH THRU SUBAREA(FEET) = 766.00 CHANNEL SLOPE = 0.0942
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.72
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.563

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

NATURAL FAIR COVER
"OPEN BRUSH" B 26.94 0.30 1.000 66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 42.59
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.41
AVERAGE FLOW DEPTH(FEET) = 0.69 TRAVEL TIME(MIN.) = 2.36
Tc(MIN.) = 16.27
SUBAREA AREA(ACRES) = 26.94 SUBAREA RUNOFF(CFS) = 54.86
EFFECTIVE AREA(ACRES) = 33.50 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 33.5 PEAK FLOW RATE(CFS) = 68.22
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.91

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.91 FLOW VELOCITY(FEET/SEC.) = 6.34
LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12712.00 = 1709.56 FEET.

FLOW PROCESS FROM NODE 12712.00 TO NODE 12713.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 585.63 DOWNSTREAM(FEET) = 463.75
CHANNEL LENGTH THRU SUBAREA(FEET) = 1025.79 CHANNEL SLOPE = 0.1188
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.95
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.356

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

NATURAL FAIR COVER
"OPEN BRUSH" B 14.73 0.30 1.000 66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 81.86
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.30
AVERAGE FLOW DEPTH(FEET) = 0.94 TRAVEL TIME(MIN.) = 2.34
Tc(MIN.) = 18.61
SUBAREA AREA(ACRES) = 14.73 SUBAREA RUNOFF(CFS) = 27.25
EFFECTIVE AREA(ACRES) = 48.23 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 48.2 PEAK FLOW RATE(CFS) = 89.24
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.99

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.99 FLOW VELOCITY(FEET/SEC.) = 7.48
LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12713.00 = 2735.35 FEET.


```

*****
FLOW PROCESS FROM NODE 12713.00 TO NODE 12714.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 463.75 DOWNSTREAM(FEET) = 360.30
CHANNEL LENGTH THRU SUBAREA(FEET) = 1148.54 CHANNEL SLOPE = 0.0901
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.63
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.181
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp        Ap      SCS
LAND USE           GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"OPEN BRUSH"         B      105.64    0.30     1.000    66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 178.75
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.52
AVERAGE FLOW DEPTH(FEET) = 1.59 TRAVEL TIME(MIN.) = 2.25
Tc(MIN.) = 20.86
SUBAREA AREA(ACRES) = 105.64 SUBAREA RUNOFF(CFS) = 178.83
EFFECTIVE AREA(ACRES) = 153.87 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 153.9 PEAK FLOW RATE(CFS) = 260.47
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.96

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.96 FLOW VELOCITY(FEET/SEC.) = 9.52
LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12714.00 = 3883.89 FEET.

```

```

*****
FLOW PROCESS FROM NODE 12714.00 TO NODE 12720.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 360.30 DOWNSTREAM(FEET) = 275.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1314.99 CHANNEL SLOPE = 0.0649
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.58
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.038
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp        Ap      SCS
LAND USE           GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"OPEN BRUSH"         B      127.13    0.30     1.000    66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 359.96
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.33
AVERAGE FLOW DEPTH(FEET) = 2.55 TRAVEL TIME(MIN.) = 2.35
Tc(MIN.) = 23.21

```

```

SUBAREA AREA(ACRES) = 127.13 SUBAREA RUNOFF(CFS) = 198.87
EFFECTIVE AREA(ACRES) = 281.00 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 281.0 PEAK FLOW RATE(CFS) = 439.57
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.84

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 2.84 FLOW VELOCITY(FEET/SEC.) = 9.89
LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12720.00 = 5198.88 FEET.

```

```

*****
FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.00 IS CODE = 1
-----
>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<
=====
TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 23.21
RAINFALL INTENSITY(INCH/HR) = 2.04
AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 1.00
EFFECTIVE STREAM AREA(ACRES) = 281.00
TOTAL STREAM AREA(ACRES) = 281.00
PEAK FLOW RATE(CFS) AT CONFLUENCE = 439.57

```

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19780.14	14.74	2.717	0.30(0.28)	0.95	3649.4	800.00
1	21469.53	19.52	2.275	0.30(0.29)	0.96	5289.0	900.00
1	22644.95	23.75	2.005	0.30(0.29)	0.97	6629.9	600.00
1	26850.56	40.84	1.455	0.30(0.29)	0.98	12631.2	40100.00
1	28179.02	48.89	1.325	0.30(0.29)	0.98	15459.2	11801.00
1	30355.40	60.01	1.204	0.30(0.30)	0.99	20043.6	11530.00
1	31466.08	64.53	1.173	0.30(0.30)	0.99	22358.1	11701.00
1	32410.79	68.13	1.149	0.30(0.30)	0.99	24451.3	11910.00
1	35172.83	78.64	1.078	0.30(0.30)	0.99	31145.5	10800.00
1	35908.05	82.96	1.049	0.30(0.30)	0.99	34090.8	11130.00
1	36032.14	92.56	0.990	0.30(0.30)	0.99	39132.0	12410.00
1	35822.70	100.80	0.954	0.30(0.30)	0.99	42871.1	11201.00
1	35574.46	105.72	0.933	0.30(0.30)	0.99	44602.8	12201.00
1	34758.58	112.64	0.903	0.30(0.30)	0.99	46460.0	12231.00
1	34387.46	115.49	0.891	0.30(0.30)	0.99	47133.3	12101.10
1	33658.09	120.27	0.870	0.30(0.30)	0.99	48094.3	10400.00
1	32498.63	128.01	0.855	0.30(0.30)	0.99	49389.4	12010.00
1	31450.46	133.78	0.843	0.30(0.30)	0.99	49736.4	10210.00
1	30997.29	136.75	0.837	0.30(0.30)	0.99	49853.6	12000.00
1	27931.67	161.25	0.788	0.30(0.30)	0.99	50474.8	10100.00
2	439.57	23.21	2.038	0.30(0.30)	1.00	281.0	12710.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20168.54	14.74	2.717	0.30(0.29)	0.95	3828.0	800.00
2	21889.78	19.52	2.275	0.30(0.29)	0.96	5525.4	900.00
3	22933.66	23.21	2.038	0.30(0.29)	0.97	6738.8	12710.00
4	23076.18	23.75	2.005	0.30(0.29)	0.97	6910.9	600.00
5	27142.54	40.84	1.455	0.30(0.29)	0.98	12912.2	40100.00
6	28438.20	48.89	1.325	0.30(0.29)	0.98	15740.2	11801.00
7	30584.01	60.01	1.204	0.30(0.30)	0.99	20324.6	11530.00
8	31686.95	64.53	1.173	0.30(0.30)	0.99	22639.1	11701.00
9	32625.50	68.13	1.149	0.30(0.30)	0.99	24732.3	11910.00
10	35369.55	78.64	1.078	0.30(0.30)	0.99	31426.5	10800.00
11	36097.38	82.96	1.049	0.30(0.30)	0.99	34371.8	11130.00
12	36206.62	92.56	0.990	0.30(0.30)	0.99	39413.0	12410.00
13	35988.16	100.80	0.954	0.30(0.30)	0.99	43152.1	11201.00
14	35734.52	105.72	0.933	0.30(0.30)	0.99	44883.8	12201.00
15	34911.05	112.64	0.903	0.30(0.30)	0.99	46741.0	12231.00
16	34536.81	115.49	0.891	0.30(0.30)	0.99	47414.3	12101.10
17	33802.36	120.27	0.870	0.30(0.30)	0.99	48375.3	10400.00
18	32638.96	128.01	0.855	0.30(0.30)	0.99	49670.4	12010.00
19	31587.84	133.78	0.843	0.30(0.30)	0.99	50017.4	10210.00
20	31133.16	136.75	0.837	0.30(0.30)	0.99	50134.6	12000.00
21	28055.04	161.25	0.788	0.30(0.30)	0.99	50755.8	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 36206.62 Tc(MIN.) = 92.56
EFFECTIVE AREA(ACRES) = 39413.02 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 50755.8
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.00 = 106010.75 FEET.

FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 275.00 DOWNSTREAM(FEET) = 258.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 2669.21 CHANNEL SLOPE = 0.0064
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 9.39
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.978

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER "BARREN"	B	0.20	0.30	1.000	86
NATURAL POOR COVER "BARREN"	B	0.20	0.30	1.000	86
NATURAL FAIR COVER "OPEN BRUSH"	B	0.20	0.30	1.000	66
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.30	0.30	1.000	65
COMMERCIAL	B	0.30	0.30	0.100	56
NATURAL FAIR COVER "MEADOWS"	B	0.50	0.30	1.000	70

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.841
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 36207.18
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 15.61
AVERAGE FLOW DEPTH(FEET) = 9.39 TRAVEL TIME(MIN.) = 2.85
Tc(MIN.) = 95.41
SUBAREA AREA(ACRES) = 1.70 SUBAREA RUNOFF(CFS) = 1.11
EFFECTIVE AREA(ACRES) = 39414.72 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 50757.5 PEAK FLOW RATE(CFS) = 36206.62
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 9.39

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 9.39 FLOW VELOCITY(FEET/SEC.) = 15.60
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108679.96 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20168.54	18.21	2.391	0.30(0.29)	0.95	3829.7	800.00
2	21889.78	22.89	2.057	0.30(0.29)	0.96	5527.1	900.00
3	22933.66	26.52	1.870	0.30(0.29)	0.97	6740.5	12710.00
4	23076.18	27.06	1.849	0.30(0.29)	0.97	6912.6	600.00
5	27142.54	43.97	1.404	0.30(0.29)	0.98	12913.9	40100.00
6	28438.20	51.98	1.287	0.30(0.29)	0.98	15741.9	11801.00
7	30584.01	63.02	1.184	0.30(0.30)	0.99	20326.3	11530.00
8	31686.95	67.50	1.153	0.30(0.30)	0.99	22640.8	11701.00
9	32625.50	71.08	1.129	0.30(0.30)	0.99	24734.0	11910.00
10	35369.55	81.51	1.058	0.30(0.30)	0.99	31428.2	10800.00
11	36097.38	85.82	1.029	0.30(0.30)	0.99	34373.5	11130.00
12	36206.62	95.41	0.978	0.30(0.30)	0.99	39414.7	12410.00
13	35988.16	103.65	0.942	0.30(0.30)	0.99	43153.8	11201.00
14	35734.52	108.58	0.920	0.30(0.30)	0.99	44885.5	12201.00
15	34911.05	115.53	0.890	0.30(0.30)	0.99	46742.7	12231.00
16	34536.81	118.38	0.878	0.30(0.30)	0.99	47416.0	12101.10
17	33802.36	123.18	0.865	0.30(0.30)	0.99	48377.0	10400.00
18	32638.96	130.96	0.849	0.30(0.30)	0.99	49672.1	12010.00
19	31587.84	136.77	0.837	0.30(0.30)	0.99	50019.1	10210.00
20	31133.16	139.75	0.831	0.30(0.30)	0.99	50136.3	12000.00
21	28055.04	164.35	0.782	0.30(0.30)	0.99	50757.5	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 36206.62 Tc(MIN.) = 95.41
AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 39414.72

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 95.41

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.978

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	0.50	0.30	0.850	56

NATURAL FAIR COVER
 "WOODLAND,GRASS" B 0.70 0.30 1.000 65
 NATURAL FAIR COVER
 "OPEN BRUSH" B 1.50 0.30 1.000 66
 COMMERCIAL B 1.40 0.30 0.100 56
 COMMERCIAL B 2.30 0.30 0.100 56
 NATURAL FAIR COVER
 "GRASS" B 9.30 0.30 1.000 69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.783
 SUBAREA AREA (ACRES) = 15.70 SUBAREA RUNOFF (CFS) = 10.49
 EFFECTIVE AREA (ACRES) = 39430.42 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 50773.2 PEAK FLOW RATE (CFS) = 36206.62
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 95.41
 * 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.978
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	11.20	0.30	1.000	65
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	11.40	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL,NARROWLEAF"	B	11.80	0.30	1.000	72
NATURAL FAIR COVER					
"OPEN BRUSH"	B	27.70	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 62.10 SUBAREA RUNOFF (CFS) = 37.87
 EFFECTIVE AREA (ACRES) = 39492.52 AREA-AVERAGED Fm (INCH/HR) = 0.30
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
 TOTAL AREA (ACRES) = 50835.3 PEAK FLOW RATE (CFS) = 36206.62
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 3C50EVRL.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2289.94	12.60	0.30 (0.13)	0.42	864.0	410.00
2	2307.96	13.97	0.30 (0.13)	0.42	943.2	420.00
3	2384.33	17.91	0.30 (0.13)	0.42	1155.3	310.00
4	2381.53	18.32	0.30 (0.13)	0.42	1172.8	400.00
5	2302.22	21.00	0.30 (0.13)	0.42	1248.7	430.00
6	2287.87	21.61	0.30 (0.13)	0.42	1265.3	300.00
7	2285.28	21.70	0.30 (0.13)	0.42	1267.7	320.00

8 1982.70 27.45 0.30 (0.13) 0.43 1292.3 390.00
 TOTAL AREA (ACRES) = 1292.3

 FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20168.54	18.21	2.391	0.30 (0.29)	0.95	3907.5	800.00
2	21889.78	22.89	2.057	0.30 (0.29)	0.96	5604.9	900.00
3	22933.66	26.52	1.870	0.30 (0.29)	0.97	6818.3	12710.00
4	23076.18	27.06	1.849	0.30 (0.29)	0.97	6990.4	600.00
5	27142.54	43.97	1.404	0.30 (0.29)	0.98	12991.7	40100.00
6	28438.20	51.98	1.287	0.30 (0.29)	0.98	15819.7	11801.00
7	30584.01	63.02	1.184	0.30 (0.30)	0.99	20404.1	11530.00
8	31686.95	67.50	1.153	0.30 (0.30)	0.99	22718.6	11701.00
9	32625.50	71.08	1.129	0.30 (0.30)	0.99	24811.8	11910.00
10	35369.55	81.51	1.058	0.30 (0.30)	0.99	31506.0	10800.00
11	36097.38	85.82	1.029	0.30 (0.30)	0.99	34451.3	11130.00
12	36206.62	95.41	0.978	0.30 (0.30)	0.99	39492.5	12410.00
13	35988.16	103.65	0.942	0.30 (0.30)	0.99	43231.6	11201.00
14	35734.52	108.58	0.920	0.30 (0.30)	0.99	44963.3	12201.00
15	34911.05	115.53	0.890	0.30 (0.30)	0.99	46820.5	12231.00
16	34536.81	118.38	0.878	0.30 (0.30)	0.99	47493.8	12101.10
17	33802.36	123.18	0.865	0.30 (0.30)	0.99	48454.8	10400.00
18	32638.96	130.96	0.849	0.30 (0.30)	0.99	49749.9	12010.00
19	31587.84	136.77	0.837	0.30 (0.30)	0.99	50096.9	10210.00
20	31133.16	139.75	0.831	0.30 (0.30)	0.99	50214.1	12000.00
21	28055.04	164.35	0.782	0.30 (0.30)	0.99	50835.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108679.96 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2289.94	12.60	3.071	0.30 (0.13)	0.42	864.0	410.00
2	2307.96	13.97	2.845	0.30 (0.13)	0.42	943.2	420.00
3	2384.33	17.91	2.418	0.30 (0.13)	0.42	1155.3	310.00
4	2381.53	18.32	2.381	0.30 (0.13)	0.42	1172.8	400.00
5	2302.22	21.00	2.172	0.30 (0.13)	0.42	1248.7	430.00
6	2287.87	21.61	2.135	0.30 (0.13)	0.42	1265.3	300.00
7	2285.28	21.70	2.129	0.30 (0.13)	0.42	1267.7	320.00
8	1982.70	27.45	1.834	0.30 (0.13)	0.43	1292.3	390.00

LONGEST FLOWPATH FROM NODE 390.00 TO NODE 12720.50 = 13248.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20741.77	12.60	3.071	0.30 (0.25)	0.82	3566.7	410.00
2	21110.98	13.97	2.845	0.30 (0.25)	0.82	3940.6	420.00
3	22469.79	17.91	2.418	0.30 (0.25)	0.83	4997.9	310.00
4	22550.83	18.21	2.391	0.30 (0.25)	0.83	5075.5	800.00
5	22591.50	18.32	2.381	0.30 (0.25)	0.83	5121.1	400.00
6	23497.29	21.00	2.172	0.30 (0.25)	0.85	6168.5	430.00
7	23704.46	21.61	2.135	0.30 (0.26)	0.85	6403.5	300.00

8	23738.13	21.70	2.129	0.30	(0.26)	0.85	6441.7	320.00
9	24112.42	22.89	2.057	0.30	(0.26)	0.86	6877.6	900.00
10	24965.02	26.52	1.870	0.30	(0.27)	0.88	8106.7	12710.00
11	25079.35	27.06	1.849	0.30	(0.27)	0.89	8281.1	600.00
12	25152.31	27.45	1.834	0.30	(0.27)	0.89	8420.6	390.00
13	28625.13	43.97	1.404	0.30	(0.28)	0.93	14284.0	40100.00
14	29784.23	51.98	1.287	0.30	(0.28)	0.94	17112.0	11801.00
15	31810.19	63.02	1.184	0.30	(0.29)	0.95	21696.4	11530.00
16	32877.83	67.50	1.153	0.30	(0.29)	0.96	24010.9	11701.00
17	33788.21	71.08	1.129	0.30	(0.29)	0.96	26104.1	11910.00
18	36450.17	81.51	1.058	0.30	(0.29)	0.97	32798.3	10800.00
19	37144.13	85.82	1.029	0.30	(0.29)	0.97	35743.6	11130.00
20	37193.20	95.41	0.978	0.30	(0.29)	0.97	40784.8	12410.00
21	36933.18	103.65	0.942	0.30	(0.29)	0.97	44523.9	11201.00
22	36654.68	108.58	0.920	0.30	(0.29)	0.97	46255.6	12201.00
23	35796.22	115.53	0.890	0.30	(0.29)	0.97	48112.8	12231.00
24	35407.59	118.38	0.878	0.30	(0.29)	0.97	48786.1	12101.10
25	34657.52	123.18	0.865	0.30	(0.29)	0.97	49747.1	10400.00
26	33475.88	130.96	0.849	0.30	(0.29)	0.97	51042.2	12010.00
27	32411.14	136.77	0.837	0.30	(0.29)	0.98	51389.2	10210.00
28	31949.47	139.75	0.831	0.30	(0.29)	0.98	51506.4	12000.00
29	28813.65	164.35	0.782	0.30	(0.29)	0.98	52127.6	10100.00

TOTAL AREA (ACRES) = 52127.6

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 37193.20 Tc (MIN.) = 95.408
EFFECTIVE AREA (ACRES) = 40784.82 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.89
TOTAL AREA (ACRES) = 52127.6
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108679.96 FEET.

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

FLOW PROCESS FROM NODE 12720.50 TO NODE 12722.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 258.00 DOWNSTREAM (FEET) = 255.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 1269.00 CHANNEL SLOPE = 0.0024
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 12.59
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.969

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	0.10	0.30	0.850	56
NATURAL FAIR COVER "GRASS"	B	0.10	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	0.20	0.30	1.000	69
NATURAL FAIR COVER					

"GRASS"	B	0.30	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.30	0.30	1.000	66
COMMERCIAL	B	0.40	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.732
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 37193.67
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 11.24
AVERAGE FLOW DEPTH (FEET) = 12.59 TRAVEL TIME (MIN.) = 1.88
Tc (MIN.) = 97.29
SUBAREA AREA (ACRES) = 1.40 SUBAREA RUNOFF (CFS) = 0.94
EFFECTIVE AREA (ACRES) = 40786.22 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA (ACRES) = 52129.0 PEAK FLOW RATE (CFS) = 37193.20
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 12.59

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 12.59 FLOW VELOCITY (FEET/SEC.) = 11.24
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12722.00 = 109948.96 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20741.77	14.87	2.697	0.30 (0.25)	0.82	3568.1	410.00
2	21110.98	16.23	2.567	0.30 (0.25)	0.82	3942.0	420.00
3	22469.79	20.12	2.226	0.30 (0.25)	0.83	4999.3	310.00
4	22550.83	20.42	2.208	0.30 (0.25)	0.83	5076.9	800.00
5	22591.50	20.53	2.201	0.30 (0.25)	0.83	5122.5	400.00
6	23497.29	23.18	2.039	0.30 (0.25)	0.85	6169.9	430.00
7	23704.46	23.78	2.003	0.30 (0.26)	0.85	6404.9	300.00
8	23738.13	23.88	1.997	0.30 (0.26)	0.85	6443.1	320.00
9	24112.42	25.05	1.927	0.30 (0.26)	0.86	6879.0	900.00
10	24965.02	28.66	1.787	0.30 (0.27)	0.88	8108.1	12710.00
11	25079.35	29.19	1.766	0.30 (0.27)	0.89	8282.5	600.00
12	25152.31	29.58	1.751	0.30 (0.27)	0.89	8422.0	390.00
13	28625.13	46.02	1.371	0.30 (0.28)	0.93	14285.4	40100.00
14	29784.23	54.00	1.266	0.30 (0.28)	0.94	17113.4	11801.00
15	31810.19	65.00	1.170	0.30 (0.29)	0.95	21697.8	11530.00
16	32877.83	69.46	1.140	0.30 (0.29)	0.96	24012.3	11701.00
17	33788.21	73.02	1.116	0.30 (0.29)	0.96	26105.5	11910.00
18	36450.17	83.41	1.046	0.30 (0.29)	0.97	32799.7	10800.00
19	37144.13	87.70	1.017	0.30 (0.29)	0.97	35745.0	11130.00
20	37193.20	97.29	0.969	0.30 (0.29)	0.97	40786.2	12410.00
21	36933.18	105.54	0.934	0.30 (0.29)	0.97	44525.3	11201.00
22	36654.68	110.47	0.912	0.30 (0.29)	0.97	46257.0	12201.00
23	35796.22	117.43	0.882	0.30 (0.29)	0.97	48114.2	12231.00
24	35407.59	120.29	0.870	0.30 (0.29)	0.97	48787.5	12101.10
25	34657.52	125.11	0.861	0.30 (0.29)	0.97	49748.5	10400.00
26	33475.88	132.90	0.845	0.30 (0.29)	0.97	51043.6	12010.00
27	32411.14	138.73	0.833	0.30 (0.29)	0.98	51390.6	10210.00
28	31949.47	141.72	0.827	0.30 (0.29)	0.98	51507.8	12000.00
29	28813.65	166.39	0.777	0.30 (0.29)	0.98	52129.0	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 37193.20 Tc (MIN.) = 97.29
AREA-AVERAGED Fm (INCH/HR) = 0.29 AREA-AVERAGED Fp (INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.97 EFFECTIVE AREA(ACRES) = 40786.22

FLOW PROCESS FROM NODE 12722.00 TO NODE 12722.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 97.29

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.969

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	0.50	0.30	0.100	56
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.60	0.30	1.000	65
NATURAL POOR COVER "BARREN"	B	0.60	0.30	1.000	86
COMMERCIAL	B	0.60	0.30	0.100	56
NATURAL FAIR COVER "OPEN BRUSH"	B	0.90	0.30	1.000	66
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	B	1.00	0.30	1.000	63

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.764

SUBAREA AREA(ACRES) = 4.20 SUBAREA RUNOFF(CFS) = 2.80

EFFECTIVE AREA(ACRES) = 40790.42 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97

TOTAL AREA(ACRES) = 52133.2 PEAK FLOW RATE(CFS) = 37193.20

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12722.00 TO NODE 12722.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 97.29

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.969

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "WOODLAND,GRASS"	B	1.30	0.30	1.000	65
NATURAL FAIR COVER "MEADOWS"	B	3.20	0.30	1.000	70
NATURAL FAIR COVER "WOODLAND,GRASS"	B	3.70	0.30	1.000	65
NATURAL FAIR COVER "OPEN BRUSH"	B	12.00	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 20.20 SUBAREA RUNOFF(CFS) = 12.17

EFFECTIVE AREA(ACRES) = 40810.62 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97

TOTAL AREA(ACRES) = 52153.4 PEAK FLOW RATE(CFS) = 37193.20

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12722.00 TO NODE 12740.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 255.00 DOWNSTREAM(FEET) = 252.10

CHANNEL LENGTH THRU SUBAREA(FEET) = 624.00 CHANNEL SLOPE = 0.0046

GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT(FEET) = 10.42

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.966

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "ROW CROPS,STRAIGHT ROW"	B	0.10	0.30	1.000	81
PUBLIC PARK	B	0.50	0.30	0.850	56
NATURAL FAIR COVER "GRASS"	B	0.50	0.30	1.000	69
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	B	0.80	0.30	1.000	63
NATURAL FAIR COVER "WOODLAND,GRASS"	B	1.20	0.30	1.000	65
COMMERCIAL	B	1.50	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.690

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 37194.77

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 14.15

AVERAGE FLOW DEPTH(FEET) = 10.42 TRAVEL TIME(MIN.) = 0.73

Tc(MIN.) = 98.02

SUBAREA AREA(ACRES) = 4.60 SUBAREA RUNOFF(CFS) = 3.14

EFFECTIVE AREA(ACRES) = 40815.22 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97

TOTAL AREA(ACRES) = 52158.0 PEAK FLOW RATE(CFS) = 37193.20

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT(FEET) = 10.42

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 10.42 FLOW VELOCITY(FEET/SEC.) = 14.15

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12740.00 = 110572.96 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20741.77	15.76	2.608	0.30(0.25)	0.82	3597.1	410.00
2	21110.98	17.11	2.488	0.30(0.25)	0.82	3971.0	420.00
3	22469.79	20.99	2.173	0.30(0.25)	0.83	5028.3	310.00
4	22550.83	21.28	2.155	0.30(0.25)	0.83	5105.9	800.00
5	22591.50	21.40	2.148	0.30(0.25)	0.83	5151.5	400.00
6	23497.29	24.04	1.988	0.30(0.26)	0.85	6198.9	430.00
7	23704.46	24.63	1.951	0.30(0.26)	0.85	6433.9	300.00
8	23738.13	24.73	1.946	0.30(0.26)	0.86	6472.1	320.00
9	24112.42	25.90	1.894	0.30(0.26)	0.86	6908.0	900.00
10	24965.02	29.50	1.754	0.30(0.27)	0.88	8137.1	12710.00
11	25079.35	30.03	1.734	0.30(0.27)	0.89	8311.5	600.00
12	25152.31	30.41	1.724	0.30(0.27)	0.89	8451.0	390.00
13	28625.13	46.82	1.358	0.30(0.28)	0.93	14314.4	40100.00

14	29784.23	54.79	1.258	0.30	(0.28)	0.94	17142.4	11801.00
15	31810.19	65.77	1.165	0.30	(0.29)	0.95	21726.8	11530.00
16	32877.83	70.22	1.135	0.30	(0.29)	0.96	24041.3	11701.00
17	33788.21	73.78	1.111	0.30	(0.29)	0.96	26134.5	11910.00
18	36450.17	84.15	1.041	0.30	(0.29)	0.97	32828.7	10800.00
19	37144.13	88.43	1.012	0.30	(0.29)	0.97	35774.0	11130.00
20	37193.20	98.02	0.966	0.30	(0.29)	0.97	40815.2	12410.00
21	36933.18	106.28	0.930	0.30	(0.29)	0.97	44554.3	11201.00
22	36654.68	111.21	0.909	0.30	(0.29)	0.97	46286.0	12201.00
23	35796.22	118.18	0.879	0.30	(0.29)	0.97	48143.2	12231.00
24	35407.59	121.04	0.869	0.30	(0.29)	0.97	48816.5	12101.10
25	34657.52	125.86	0.859	0.30	(0.29)	0.97	49777.5	10400.00
26	33475.88	133.67	0.843	0.30	(0.29)	0.97	51072.6	12010.00
27	32411.14	139.50	0.832	0.30	(0.29)	0.98	51419.6	10210.00
28	31949.47	142.49	0.826	0.30	(0.29)	0.98	51536.8	12000.00
29	28813.65	167.19	0.776	0.30	(0.29)	0.98	52158.0	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 37193.20 Tc(MIN.) = 98.02
 AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.97 EFFECTIVE AREA(ACRES) = 40815.22

 FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

 MAINLINE Tc(MIN.) = 98.02
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.966
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	2.50	0.30	0.100	56
NATURAL FAIR COVER "GRASS"	B	2.60	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	2.80	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	5.40	0.30	1.000	66
NATURAL FAIR COVER "WOODLAND,GRASS"	B	6.20	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND,GRASS"	B	6.50	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.913
 SUBAREA AREA(ACRES) = 26.00 SUBAREA RUNOFF(CFS) = 16.20
 EFFECTIVE AREA(ACRES) = 40841.22 AREA-AVERAGED Fm(INCH/HR) = 0.29
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA(ACRES) = 52184.0 PEAK FLOW RATE(CFS) = 37193.20
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

 MAINLINE Tc(MIN.) = 98.02
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.966
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	6.70	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	12.00	0.30	1.000	66
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	B	20.30	0.30	1.000	63

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 39.00 SUBAREA RUNOFF(CFS) = 23.38
 EFFECTIVE AREA(ACRES) = 40880.22 AREA-AVERAGED Fm(INCH/HR) = 0.29
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA(ACRES) = 52223.0 PEAK FLOW RATE(CFS) = 37193.20
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

 TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
 TIME OF CONCENTRATION(MIN.) = 98.02
 RAINFALL INTENSITY(INCH/HR) = 0.97
 AREA-AVERAGED Fm(INCH/HR) = 0.29
 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.97
 EFFECTIVE STREAM AREA(ACRES) = 40880.22
 TOTAL STREAM AREA(ACRES) = 52222.99
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 37193.20

 FLOW PROCESS FROM NODE 12730.00 TO NODE 12731.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

 INITIAL SUBAREA FLOW-LENGTH(FEET) = 561.54
 ELEVATION DATA: UPSTREAM(FEET) = 613.29 DOWNSTREAM(FEET) = 551.75

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
 SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 13.823
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.869
 SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	B	6.33	0.30	1.000	63	13.82

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA RUNOFF(CFS) = 14.63
 TOTAL AREA(ACRES) = 6.33 PEAK FLOW RATE(CFS) = 14.63

 FLOW PROCESS FROM NODE 12731.00 TO NODE 12732.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 551.75 DOWNSTREAM(FEET) = 494.40
 CHANNEL LENGTH THRU SUBAREA(FEET) = 971.91 CHANNEL SLOPE = 0.0590
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 0.91
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.485

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	34.62	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 48.85
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.86
 AVERAGE FLOW DEPTH(FEET) = 0.86 TRAVEL TIME(MIN.) = 3.33
 Tc(MIN.) = 17.15
 SUBAREA AREA(ACRES) = 34.62 SUBAREA RUNOFF(CFS) = 68.07
 EFFECTIVE AREA(ACRES) = 40.95 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 40.9 PEAK FLOW RATE(CFS) = 80.51
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 1.14

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 1.14 FLOW VELOCITY(FEET/SEC.) = 5.74
 LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12732.00 = 1533.45 FEET.

 FLOW PROCESS FROM NODE 12732.00 TO NODE 12733.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 494.40 DOWNSTREAM(FEET) = 431.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1156.41 CHANNEL SLOPE = 0.0548
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 1.59
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.227

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	59.52	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 132.19
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.53
 AVERAGE FLOW DEPTH(FEET) = 1.55 TRAVEL TIME(MIN.) = 2.95
 Tc(MIN.) = 20.10
 SUBAREA AREA(ACRES) = 59.52 SUBAREA RUNOFF(CFS) = 103.21
 EFFECTIVE AREA(ACRES) = 100.47 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 100.5 PEAK FLOW RATE(CFS) = 174.21

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 1.80

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 1.80 FLOW VELOCITY(FEET/SEC.) = 7.10
 LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12733.00 = 2689.86 FEET.

 FLOW PROCESS FROM NODE 12733.00 TO NODE 12734.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 431.00 DOWNSTREAM(FEET) = 367.10
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1654.48 CHANNEL SLOPE = 0.0386
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 2.31
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.978

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	64.05	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 222.66
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.75
 AVERAGE FLOW DEPTH(FEET) = 2.27 TRAVEL TIME(MIN.) = 4.08
 Tc(MIN.) = 24.19
 SUBAREA AREA(ACRES) = 64.05 SUBAREA RUNOFF(CFS) = 96.75
 EFFECTIVE AREA(ACRES) = 164.52 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 164.5 PEAK FLOW RATE(CFS) = 248.50
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 2.41

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 2.41 FLOW VELOCITY(FEET/SEC.) = 6.97
 LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12734.00 = 4344.34 FEET.

 FLOW PROCESS FROM NODE 12734.00 TO NODE 12740.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 367.11 DOWNSTREAM(FEET) = 252.10
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1880.98 CHANNEL SLOPE = 0.0611
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 2.22
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.815

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL FAIR COVER
 "OPEN BRUSH" B 26.02 0.30 1.000 66
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 266.25
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.37
 AVERAGE FLOW DEPTH(FEET) = 2.21 TRAVEL TIME(MIN.) = 3.75
 Tc(MIN.) = 27.94
 SUBAREA AREA(ACRES) = 26.02 SUBAREA RUNOFF(CFS) = 35.48
 EFFECTIVE AREA(ACRES) = 190.54 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 190.54 PEAK FLOW RATE(CFS) = 259.81
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 2.18

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 2.18 FLOW VELOCITY(FEET/SEC.) = 8.31
 LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12740.00 = 6225.32 FEET.

 FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

 TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
 TIME OF CONCENTRATION(MIN.) = 27.94
 RAINFALL INTENSITY(INCH/HR) = 1.82
 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 1.00
 EFFECTIVE STREAM AREA(ACRES) = 190.54
 TOTAL STREAM AREA(ACRES) = 190.54
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 259.81

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20741.77	15.76	2.608	0.30(0.25)	0.83	3662.1	410.00
1	21110.98	17.11	2.488	0.30(0.25)	0.83	4036.0	420.00
1	22469.79	20.99	2.173	0.30(0.25)	0.83	5093.3	310.00
1	22550.83	21.28	2.155	0.30(0.25)	0.83	5170.9	800.00
1	22591.50	21.40	2.148	0.30(0.25)	0.83	5216.5	400.00
1	23497.29	24.04	1.988	0.30(0.26)	0.85	6263.9	430.00
1	23704.46	24.63	1.951	0.30(0.26)	0.86	6498.9	300.00
1	23738.13	24.73	1.946	0.30(0.26)	0.86	6537.1	320.00
1	24112.42	25.90	1.894	0.30(0.26)	0.87	6973.0	900.00
1	24965.02	29.50	1.754	0.30(0.27)	0.88	8202.1	12710.00
1	25079.35	30.03	1.734	0.30(0.27)	0.89	8376.5	600.00
1	25152.31	30.41	1.724	0.30(0.27)	0.89	8516.0	390.00
1	28625.13	46.82	1.358	0.30(0.28)	0.93	14379.4	40100.00
1	29784.23	54.79	1.258	0.30(0.28)	0.94	17207.4	11801.00
1	31810.19	65.77	1.165	0.30(0.29)	0.95	21791.8	11530.00
1	32877.83	70.22	1.135	0.30(0.29)	0.96	24106.3	11701.00
1	33788.21	73.78	1.111	0.30(0.29)	0.96	26199.5	11910.00
1	36450.17	84.15	1.041	0.30(0.29)	0.97	32893.7	10800.00

1	37144.13	88.43	1.012	0.30(0.29)	0.97	35839.0	11130.00
1	37193.20	98.02	0.966	0.30(0.29)	0.97	40880.2	12410.00
1	36933.18	106.28	0.930	0.30(0.29)	0.97	44619.3	11201.00
1	36654.68	111.21	0.909	0.30(0.29)	0.97	46351.0	12201.00
1	35796.22	118.18	0.879	0.30(0.29)	0.97	48208.2	12231.00
1	35407.59	121.04	0.869	0.30(0.29)	0.97	48881.5	12101.10
1	34657.52	125.86	0.859	0.30(0.29)	0.97	49842.5	10400.00
1	33475.88	133.67	0.843	0.30(0.29)	0.97	51137.6	12010.00
1	32411.14	139.50	0.832	0.30(0.29)	0.98	51484.6	10210.00
1	31949.47	142.49	0.826	0.30(0.29)	0.98	51601.8	12000.00
1	28813.65	167.19	0.776	0.30(0.29)	0.98	52223.0	10100.00
2	259.81	27.94	1.815	0.30(0.30)	1.00	190.5	12730.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20965.01	15.76	2.608	0.30(0.25)	0.83	3769.5	410.00
2	21340.84	17.11	2.488	0.30(0.25)	0.83	4152.7	420.00
3	22711.08	20.99	2.173	0.30(0.25)	0.84	5236.5	310.00
4	22793.18	21.28	2.155	0.30(0.25)	0.84	5316.1	800.00
5	22834.23	21.40	2.148	0.30(0.25)	0.84	5362.5	400.00
6	23746.29	24.04	1.988	0.30(0.26)	0.86	6427.8	430.00
7	23954.15	24.63	1.951	0.30(0.26)	0.86	6666.9	300.00
8	23987.91	24.73	1.946	0.30(0.26)	0.86	6705.7	320.00
9	24365.86	25.90	1.894	0.30(0.26)	0.87	7149.7	900.00
10	24854.73	27.94	1.815	0.30(0.26)	0.88	7859.1	12730.00
11	25214.44	29.50	1.754	0.30(0.27)	0.89	8392.6	12710.00
12	25325.31	30.03	1.734	0.30(0.27)	0.89	8567.0	600.00
13	25396.50	30.41	1.724	0.30(0.27)	0.89	8706.6	390.00
14	28806.61	46.82	1.358	0.30(0.28)	0.93	14570.0	40100.00
15	29948.46	54.79	1.258	0.30(0.28)	0.94	17397.9	11801.00
16	31958.51	65.77	1.165	0.30(0.29)	0.95	21982.3	11530.00
17	33020.99	70.22	1.135	0.30(0.29)	0.96	24296.8	11701.00
18	33927.24	73.78	1.111	0.30(0.29)	0.96	26390.0	11910.00
19	36577.17	84.15	1.041	0.30(0.29)	0.97	33084.2	10800.00
20	37266.16	88.43	1.012	0.30(0.29)	0.97	36029.6	11130.00
21	37307.45	98.02	0.966	0.30(0.29)	0.97	41070.8	12410.00
22	37041.29	106.28	0.930	0.30(0.29)	0.97	44809.9	11201.00
23	36759.13	111.21	0.909	0.30(0.29)	0.97	46541.6	12201.00
24	35895.49	118.18	0.879	0.30(0.29)	0.97	48398.7	12231.00
25	35505.15	121.04	0.869	0.30(0.29)	0.97	49072.0	12101.10
26	34753.41	125.86	0.859	0.30(0.29)	0.97	50033.0	10400.00
27	33569.07	133.67	0.843	0.30(0.29)	0.97	51328.1	12010.00
28	32502.32	139.50	0.832	0.30(0.29)	0.98	51675.1	10210.00
29	32039.61	142.49	0.826	0.30(0.29)	0.98	51792.3	12000.00
30	28895.25	167.19	0.776	0.30(0.29)	0.98	52413.5	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
 PEAK FLOW RATE(CFS) = 37307.45 Tc(MIN.) = 98.02
 EFFECTIVE AREA(ACRES) = 41070.76 AREA-AVERAGED Fm(INCH/HR) = 0.29
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA(ACRES) = 52413.5
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12740.00 = 110572.96 FEET.

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 252.10 DOWNSTREAM(FEET) = 240.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1220.00 CHANNEL SLOPE = 0.0099
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 8.43
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.961

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include Agricultural Poor Cover, Open Brush, Public Park, Commercial, Woodland/Grass, etc.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.784

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 37309.54

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 18.28

AVERAGE FLOW DEPTH(FEET) = 8.43 TRAVEL TIME(MIN.) = 1.11

Tc(MIN.) = 99.14

SUBAREA AREA(ACRES) = 6.40 SUBAREA RUNOFF(CFS) = 4.18

EFFECTIVE AREA(ACRES) = 41077.16 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97

TOTAL AREA(ACRES) = 52419.9 PEAK FLOW RATE(CFS) = 37307.45

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT(FEET) = 8.43

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 8.43 FLOW VELOCITY(FEET/SEC.) = 18.29

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111792.96 FEET.

** PEAK FLOW RATE TABLE **

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Rows 1-13.

Table with 8 columns: Node number, Elevation, Depth, Velocity, Intensity, Fp, Ap, SCS CN. Rows 14-30.

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 37307.45 Tc(MIN.) = 99.14

AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.97 EFFECTIVE AREA(ACRES) = 41077.16

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 99.14

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.961

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include Natural Fair Cover, Grass, Woodland/Grass, etc.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 22.90 SUBAREA RUNOFF(CFS) = 13.63

EFFECTIVE AREA(ACRES) = 41100.06 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97

TOTAL AREA(ACRES) = 52442.8 PEAK FLOW RATE(CFS) = 37307.45

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 52442.8 TC(MIN.) = 99.14

EFFECTIVE AREA(ACRES) = 41100.06 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.972

PEAK FLOW RATE(CFS) = 37307.45

** PEAK FLOW RATE TABLE **

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Rows 1-3.

4	22793.18	22.60	2.075	0.30	(0.25)	0.84	5345.4	800.00
5	22834.23	22.71	2.068	0.30	(0.25)	0.84	5391.8	400.00
6	23746.29	25.33	1.916	0.30	(0.26)	0.86	6457.1	430.00
7	23954.15	25.92	1.893	0.30	(0.26)	0.86	6696.2	300.00
8	23987.91	26.02	1.890	0.30	(0.26)	0.86	6735.0	320.00
9	24365.86	27.18	1.844	0.30	(0.26)	0.87	7179.0	900.00
10	24854.73	29.21	1.766	0.30	(0.26)	0.88	7888.4	12730.00
11	25214.44	30.77	1.715	0.30	(0.27)	0.89	8421.9	12710.00
12	25325.31	31.29	1.700	0.30	(0.27)	0.89	8596.3	600.00
13	25396.50	31.68	1.690	0.30	(0.27)	0.89	8735.9	390.00
14	28806.61	48.03	1.339	0.30	(0.28)	0.93	14599.3	40100.00
15	29948.46	55.98	1.245	0.30	(0.28)	0.94	17427.2	11801.00
16	31958.51	66.94	1.157	0.30	(0.29)	0.95	22011.6	11530.00
17	33020.99	71.38	1.127	0.30	(0.29)	0.96	24326.1	11701.00
18	33927.24	74.93	1.103	0.30	(0.29)	0.96	26419.3	11910.00
19	36577.17	85.27	1.033	0.30	(0.29)	0.97	33113.5	10800.00
20	37266.16	89.55	1.004	0.30	(0.29)	0.97	36058.9	11130.00
21	37307.45	99.14	0.961	0.30	(0.29)	0.97	41100.1	12410.00
22	37041.29	107.39	0.926	0.30	(0.29)	0.97	44839.2	11201.00
23	36759.13	112.33	0.904	0.30	(0.29)	0.97	46570.9	12201.00
24	35895.49	119.30	0.874	0.30	(0.29)	0.97	48428.0	12231.00
25	35505.15	122.17	0.867	0.30	(0.29)	0.97	49101.3	12101.10
26	34753.41	127.00	0.857	0.30	(0.29)	0.97	50062.3	10400.00
27	33569.07	134.82	0.841	0.30	(0.29)	0.97	51357.4	12010.00
28	32502.32	140.66	0.829	0.30	(0.29)	0.98	51704.4	10210.00
29	32039.61	143.66	0.823	0.30	(0.29)	0.98	51821.6	12000.00
30	28895.25	168.40	0.773	0.30	(0.29)	0.98	52442.8	10100.00

=====
 END OF RATIONAL METHOD ANALYSIS
 =====

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 128 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 50-YR EV MAY 2023 ROKAMOTO *

FILE NAME: RU50EV28.DAT
TIME/DATE OF STUDY: 11:30 05/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 50.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.469
- 2) 10.00; 3.498
- 3) 15.00; 2.675
- 4) 20.00; 2.233
- 5) 25.00; 1.929
- 6) 30.00; 1.735
- 7) 40.00; 1.468
- 8) 50.00; 1.307
- 9) 60.00; 1.204
- 10) 90.00; 1.001
- 11) 120.00; 0.871
- 12) 180.00; 0.750
- 13) 360.00; 0.557
- 14) 1200.00; 0.245

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:

- 1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: RU50EV27.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21340.84	18.45	0.30 (0.25)	0.83	4182.0	420.00
2	22834.23	22.71	0.30 (0.25)	0.84	5391.8	400.00
3	25396.50	31.68	0.30 (0.27)	0.89	8735.9	390.00
4	28806.61	48.03	0.30 (0.28)	0.93	14599.3	40100.00
5	29948.46	55.98	0.30 (0.28)	0.94	17427.2	11801.00
6	31958.51	66.94	0.30 (0.29)	0.95	22011.6	11530.00
7	33020.99	71.38	0.30 (0.29)	0.96	24326.1	11701.00
8	33927.24	74.93	0.30 (0.29)	0.96	26419.3	11910.00
9	36577.17	85.27	0.30 (0.29)	0.97	33113.5	10800.00
10	37266.16	89.55	0.30 (0.29)	0.97	36058.9	11130.00
11	37307.45	99.14	0.30 (0.29)	0.97	41100.1	12410.00
12	37041.29	107.39	0.30 (0.29)	0.97	44839.2	11201.00
13	36759.13	112.33	0.30 (0.29)	0.97	46570.9	12201.00
14	35895.49	119.30	0.30 (0.29)	0.97	48428.0	12231.00
15	35505.15	122.17	0.30 (0.29)	0.97	49101.3	12101.10
16	34753.41	127.00	0.30 (0.29)	0.97	50062.3	10400.00
17	33569.07	134.82	0.30 (0.29)	0.97	51357.4	12010.00
18	32502.32	140.66	0.30 (0.29)	0.98	51704.4	10210.00
19	32039.61	143.66	0.30 (0.29)	0.98	51821.6	12000.00
20	28895.25	168.40	0.30 (0.29)	0.98	52442.8	10100.00
TOTAL AREA (ACRES) =						52442.8

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P501XX50.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	374.01	13.28	0.30 (0.25)	0.84	174.4	50110.00
2	396.68	17.73	0.30 (0.26)	0.85	223.2	50100.00
TOTAL AREA (ACRES) =						223.2

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
------------------	------------	--------------	----------------------	----	---------------	-------------------

1 374.01 13.28 0.30 (0.25) 0.84 174.4 50110.00
 2 396.68 17.73 0.30 (0.26) 0.85 223.2 50100.00
 TOTAL AREA (ACRES) = 223.2

FLOW PROCESS FROM NODE 12740.00 TO NODE 12800.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	374.01	13.28	2.958	0.30 (0.25)	0.84	174.4	50110.00
2	396.68	17.73	2.434	0.30 (0.26)	0.85	223.2	50100.00

LONGEST FLOWPATH FROM NODE 50100.00 TO NODE 12800.00 = 4170.00 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21340.84	18.45	2.370	0.30 (0.25)	0.83	4182.0	420.00
2	22834.23	22.71	2.068	0.30 (0.25)	0.84	5391.8	400.00
3	25396.50	31.68	1.690	0.30 (0.27)	0.89	8735.9	390.00
4	28806.61	48.03	1.339	0.30 (0.28)	0.93	14599.3	40100.00
5	29948.46	55.98	1.245	0.30 (0.28)	0.94	17427.2	11801.00
6	31958.51	66.94	1.157	0.30 (0.29)	0.95	22011.6	11530.00
7	33020.99	71.38	1.127	0.30 (0.29)	0.96	24326.1	11701.00
8	33927.24	74.93	1.103	0.30 (0.29)	0.96	26419.3	11910.00
9	36577.17	85.27	1.033	0.30 (0.29)	0.97	33113.5	10800.00
10	37266.16	89.55	1.004	0.30 (0.29)	0.97	36058.9	11130.00
11	37307.45	99.14	0.961	0.30 (0.29)	0.97	41100.1	12410.00
12	37041.29	107.39	0.926	0.30 (0.29)	0.97	44839.2	11201.00
13	36759.13	112.33	0.904	0.30 (0.29)	0.97	46570.9	12201.00
14	35895.49	119.30	0.874	0.30 (0.29)	0.97	48428.0	12231.00
15	35505.15	122.17	0.867	0.30 (0.29)	0.97	49101.3	12101.10
16	34753.41	127.00	0.857	0.30 (0.29)	0.97	50062.3	10400.00
17	33569.07	134.82	0.841	0.30 (0.29)	0.97	51357.4	12010.00
18	32502.32	140.66	0.829	0.30 (0.29)	0.98	51704.4	10210.00
19	32039.61	143.66	0.823	0.30 (0.29)	0.98	51821.6	12000.00
20	28895.25	168.40	0.773	0.30 (0.29)	0.98	52442.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111792.96 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19994.38	13.28	2.958	0.30 (0.25)	0.83	3183.8	50110.00
2	21518.64	17.73	2.434	0.30 (0.25)	0.83	4240.7	50100.00
3	21725.83	18.45	2.370	0.30 (0.25)	0.83	4405.2	420.00
4	23164.37	22.71	2.068	0.30 (0.25)	0.84	5615.0	400.00
5	25657.78	31.68	1.690	0.30 (0.27)	0.89	8959.1	390.00
6	29003.91	48.03	1.339	0.30 (0.28)	0.93	14822.5	40100.00
7	30128.76	55.98	1.245	0.30 (0.28)	0.94	17650.4	11801.00
8	32122.73	66.94	1.157	0.30 (0.29)	0.95	22234.8	11530.00
9	33179.73	71.38	1.127	0.30 (0.29)	0.96	24549.3	11701.00
10	34081.62	74.93	1.103	0.30 (0.29)	0.96	26642.5	11910.00
11	36718.81	85.27	1.033	0.30 (0.29)	0.97	33336.7	10800.00
12	37402.52	89.55	1.004	0.30 (0.29)	0.97	36282.1	11130.00
13	37436.05	99.14	0.961	0.30 (0.29)	0.97	41323.3	12410.00

14	37163.38	107.39	0.926	0.30 (0.29)	0.97	45062.4	11201.00
15	36877.32	112.33	0.904	0.30 (0.29)	0.97	46794.1	12201.00
16	36008.18	119.30	0.874	0.30 (0.29)	0.97	48651.2	12231.00
17	35616.49	122.17	0.867	0.30 (0.29)	0.97	49324.5	12101.10
18	34862.98	127.00	0.857	0.30 (0.29)	0.97	50285.5	10400.00
19	33675.77	134.82	0.841	0.30 (0.29)	0.97	51580.6	12010.00
20	32606.87	140.66	0.829	0.30 (0.29)	0.97	51927.6	10210.00
21	32143.06	143.66	0.823	0.30 (0.29)	0.97	52044.8	12000.00
22	28989.62	168.40	0.773	0.30 (0.29)	0.97	52666.0	10100.00

TOTAL AREA (ACRES) = 52666.0

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 37436.05 Tc (MIN.) = 99.137
 EFFECTIVE AREA (ACRES) = 41323.26 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA (ACRES) = 52666.0
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111792.96 FEET.

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 52666.0 TC (MIN.) = 99.14
 EFFECTIVE AREA (ACRES) = 41323.26 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.971
 PEAK FLOW RATE (CFS) = 37436.05

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19994.38	13.28	2.958	0.30 (0.25)	0.83	3183.8	50110.00
2	21518.64	17.73	2.434	0.30 (0.25)	0.83	4240.7	50100.00
3	21725.83	18.45	2.370	0.30 (0.25)	0.83	4405.2	420.00
4	23164.37	22.71	2.068	0.30 (0.25)	0.84	5615.0	400.00
5	25657.78	31.68	1.690	0.30 (0.27)	0.89	8959.1	390.00
6	29003.91	48.03	1.339	0.30 (0.28)	0.93	14822.5	40100.00
7	30128.76	55.98	1.245	0.30 (0.28)	0.94	17650.4	11801.00
8	32122.73	66.94	1.157	0.30 (0.29)	0.95	22234.8	11530.00
9	33179.73	71.38	1.127	0.30 (0.29)	0.96	24549.3	11701.00
10	34081.62	74.93	1.103	0.30 (0.29)	0.96	26642.5	11910.00
11	36718.81	85.27	1.033	0.30 (0.29)	0.97	33336.7	10800.00
12	37402.52	89.55	1.004	0.30 (0.29)	0.97	36282.1	11130.00
13	37436.05	99.14	0.961	0.30 (0.29)	0.97	41323.3	12410.00
14	37163.38	107.39	0.926	0.30 (0.29)	0.97	45062.4	11201.00
15	36877.32	112.33	0.904	0.30 (0.29)	0.97	46794.1	12201.00
16	36008.18	119.30	0.874	0.30 (0.29)	0.97	48651.2	12231.00
17	35616.49	122.17	0.867	0.30 (0.29)	0.97	49324.5	12101.10
18	34862.98	127.00	0.857	0.30 (0.29)	0.97	50285.5	10400.00
19	33675.77	134.82	0.841	0.30 (0.29)	0.97	51580.6	12010.00
20	32606.87	140.66	0.829	0.30 (0.29)	0.97	51927.6	10210.00
21	32143.06	143.66	0.823	0.30 (0.29)	0.97	52044.8	12000.00
22	28989.62	168.40	0.773	0.30 (0.29)	0.97	52666.0	10100.00

END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 129 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 50-YR EV MAY 2023 ROKAMOTO *

FILE NAME: RU50EV29.DAT
TIME/DATE OF STUDY: 11:30 05/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 50.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.436
- 2) 10.00; 3.482
- 3) 15.00; 2.666
- 4) 20.00; 2.226
- 5) 25.00; 1.924
- 6) 30.00; 1.731
- 7) 40.00; 1.465
- 8) 50.00; 1.303
- 9) 60.00; 1.200
- 10) 90.00; 0.997
- 11) 120.00; 0.867
- 12) 180.00; 0.745
- 13) 360.00; 0.552
- 14) 1200.00; 0.242

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	(FT)	(FT)	SIDE / SIDE/ WAY	(FT)	(FT)	(FT)	(FT)	(n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU50EV28.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19994.38	13.28	0.30 (0.25)	0.83	3183.8	50110.00
2	21725.83	18.45	0.30 (0.25)	0.83	4405.2	420.00
3	23164.37	22.71	0.30 (0.25)	0.84	5615.0	400.00
4	25657.78	31.68	0.30 (0.27)	0.89	8959.1	390.00
5	29003.91	48.03	0.30 (0.28)	0.93	14822.5	40100.00
6	30128.76	55.98	0.30 (0.28)	0.94	17650.4	11801.00
7	32122.73	66.94	0.30 (0.29)	0.95	22234.8	11530.00
8	33179.73	71.38	0.30 (0.29)	0.96	24549.3	11701.00
9	34081.62	74.93	0.30 (0.29)	0.96	26642.5	11910.00
10	36718.81	85.27	0.30 (0.29)	0.97	33336.7	10800.00
11	37402.52	89.55	0.30 (0.29)	0.97	36282.1	11130.00
12	37436.05	99.14	0.30 (0.29)	0.97	41323.3	12410.00
13	37163.38	107.39	0.30 (0.29)	0.97	45062.4	11201.00
14	36877.32	112.33	0.30 (0.29)	0.97	46794.1	12201.00
15	36008.18	119.30	0.30 (0.29)	0.97	48651.2	12231.00
16	34862.98	127.00	0.30 (0.29)	0.97	50285.5	10400.00
17	33675.77	134.82	0.30 (0.29)	0.97	51580.6	12010.00
18	32606.87	140.66	0.30 (0.29)	0.97	51927.6	10210.00
19	32143.06	143.66	0.30 (0.29)	0.97	52044.8	12000.00
20	28989.62	168.40	0.30 (0.29)	0.97	52666.0	10100.00
TOTAL AREA(ACRES) =						52666.0

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19994.38	13.28	0.30 (0.25)	0.83	3183.8	50110.00
2	21725.83	18.45	0.30 (0.25)	0.83	4405.2	420.00
3	23164.37	22.71	0.30 (0.25)	0.84	5615.0	400.00
4	25657.78	31.68	0.30 (0.27)	0.89	8959.1	390.00
5	29003.91	48.03	0.30 (0.28)	0.93	14822.5	40100.00
6	30128.76	55.98	0.30 (0.28)	0.94	17650.4	11801.00
7	32122.73	66.94	0.30 (0.29)	0.95	22234.8	11530.00
8	33179.73	71.38	0.30 (0.29)	0.96	24549.3	11701.00
9	34081.62	74.93	0.30 (0.29)	0.96	26642.5	11910.00
10	36718.81	85.27	0.30 (0.29)	0.97	33336.7	10800.00
11	37402.52	89.55	0.30 (0.29)	0.97	36282.1	11130.00
12	37436.05	99.14	0.30 (0.29)	0.97	41323.3	12410.00
13	37163.38	107.39	0.30 (0.29)	0.97	45062.4	11201.00

```

14 36877.32 112.33 0.30( 0.29) 0.97 46794.1 12201.00
15 36008.18 119.30 0.30( 0.29) 0.97 48651.2 12231.00
16 34862.98 127.00 0.30( 0.29) 0.97 50285.5 10400.00
17 33675.77 134.82 0.30( 0.29) 0.97 51580.6 12010.00
18 32606.87 140.66 0.30( 0.29) 0.97 51927.6 10210.00
19 32143.06 143.66 0.30( 0.29) 0.97 52044.8 12000.00
20 28989.62 168.40 0.30( 0.29) 0.97 52666.0 10100.00
TOTAL AREA(ACRES) = 52666.0

```

```

*****
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 12
-----

```

```
>>>>CLEAR MEMORY BANK # 1 <<<<<
```

```

*****
FLOW PROCESS FROM NODE 12800.00 TO NODE 12901.00 IS CODE = 56
-----

```

```
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<
```

```

=====
ELEVATION DATA: UPSTREAM(FEET) = 240.00 DOWNSTREAM(FEET) = 216.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 3120.28 CHANNEL SLOPE = 0.0077
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 9.08
CHANNEL FLOW THRU SUBAREA(CFS) = 37436.05
FLOW VELOCITY(FEET/SEC.) = 16.81 FLOW DEPTH(FEET) = 9.08
TRAVEL TIME(MIN.) = 3.09 Tc(MIN.) = 102.23
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12901.00 = 114913.24 FEET.

```

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19994.38	17.10	2.481	0.30(0.25)	0.83	3183.8	50110.00
2	21725.83	22.17	2.095	0.30(0.25)	0.83	4405.2	420.00
3	23164.37	26.34	1.872	0.30(0.25)	0.84	5615.0	400.00
4	25657.78	35.19	1.593	0.30(0.27)	0.89	8959.1	390.00
5	29003.91	51.40	1.289	0.30(0.28)	0.93	14822.5	40100.00
6	30128.76	59.31	1.207	0.30(0.28)	0.94	17650.4	11801.00
7	32122.73	70.19	1.131	0.30(0.29)	0.95	22234.8	11530.00
8	33179.73	74.60	1.101	0.30(0.29)	0.96	24549.3	11701.00
9	34081.62	78.12	1.077	0.30(0.29)	0.96	26642.5	11910.00
10	36718.81	88.38	1.008	0.30(0.29)	0.97	33336.7	10800.00
11	37402.52	92.64	0.986	0.30(0.29)	0.97	36282.1	11130.00
12	37436.05	102.23	0.944	0.30(0.29)	0.97	41323.3	12410.00
13	37163.38	110.49	0.908	0.30(0.29)	0.97	45062.4	11201.00
14	36877.32	115.44	0.887	0.30(0.29)	0.97	46794.1	12201.00
15	36008.18	122.44	0.862	0.30(0.29)	0.97	48651.2	12231.00
16	34862.98	130.17	0.846	0.30(0.29)	0.97	50285.5	10400.00
17	33675.77	138.02	0.830	0.30(0.29)	0.97	51580.6	12010.00
18	32606.87	143.90	0.818	0.30(0.29)	0.97	51927.6	10210.00
19	32143.06	146.92	0.812	0.30(0.29)	0.97	52044.8	12000.00
20	28989.62	171.77	0.762	0.30(0.29)	0.97	52666.0	10100.00

NEW PEAK FLOW DATA ARE:

```

PEAK FLOW RATE(CFS) = 37436.05 Tc(MIN.) = 102.23
AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.97 EFFECTIVE AREA(ACRES) = 41323.26

```

```

*****
FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81
-----

```

```
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
```

```

=====
MAINLINE Tc(MIN.) = 102.23
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.944
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS
LAND USE            GROUP (ACRES) (INCH/HR) (DECIMAL) CN
COMMERCIAL          B         14.30  0.30  0.100  56
PUBLIC PARK         B         9.40   0.30  0.850  56
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.397
SUBAREA AREA(ACRES) = 23.70 SUBAREA RUNOFF(CFS) = 17.59
EFFECTIVE AREA(ACRES) = 41346.96 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 52689.7 PEAK FLOW RATE(CFS) = 37436.05
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81
-----

```

```
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
```

```

=====
MAINLINE Tc(MIN.) = 102.23
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.944
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS
LAND USE            GROUP (ACRES) (INCH/HR) (DECIMAL) CN
COMMERCIAL          B         0.20   0.30  0.100  56
RESIDENTIAL
"5-7 DWELLINGS/ACRE" B         0.40   0.30  0.500  56
RESIDENTIAL
".4 DWELLING/ACRE"  B         0.50   0.30  0.900  56
NATURAL FAIR COVER
"WOODLAND,GRASS"   B         0.60   0.30  1.000  65
COMMERCIAL          B         0.70   0.30  0.100  56
RESIDENTIAL
".4 DWELLING/ACRE"  B         0.70   0.30  0.900  56
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.635
SUBAREA AREA(ACRES) = 3.10 SUBAREA RUNOFF(CFS) = 2.10
EFFECTIVE AREA(ACRES) = 41350.06 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 52692.8 PEAK FLOW RATE(CFS) = 37436.05
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81
-----

```

```
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
```

```

=====
MAINLINE Tc(MIN.) = 102.23
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.944
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS

```

LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
PUBLIC PARK	B	0.70	0.30	0.850	56
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	1.00	0.30	1.000	65
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.40	0.30	1.000	66
NATURAL FAIR COVER					
"GRASS"	B	1.50	0.30	1.000	69
COMMERCIAL	B	1.70	0.30	0.100	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.90	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.822
SUBAREA AREA(ACRES) = 9.20 SUBAREA RUNOFF(CFS) = 5.77
EFFECTIVE AREA(ACRES) = 41359.26 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 52702.0 PEAK FLOW RATE(CFS) = 37436.05
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 102.23
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.944
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	3.60	0.30	1.000	65
RESIDENTIAL					
"5-7 DWELLINGS/ACRE"	B	3.70	0.30	0.500	56
RESIDENTIAL					
"5-7 DWELLINGS/ACRE"	B	4.10	0.30	0.500	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	5.40	0.30	0.900	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	6.70	0.30	1.000	66
NATURAL POOR COVER					
"BARREN"	B	12.00	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.875
SUBAREA AREA(ACRES) = 35.50 SUBAREA RUNOFF(CFS) = 21.77
EFFECTIVE AREA(ACRES) = 41394.76 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 52737.5 PEAK FLOW RATE(CFS) = 37436.05
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 102.23
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.944
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	3.60	0.30	1.000	65
RESIDENTIAL					
"5-7 DWELLINGS/ACRE"	B	3.70	0.30	0.500	56
RESIDENTIAL					
"5-7 DWELLINGS/ACRE"	B	4.10	0.30	0.500	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	5.40	0.30	0.900	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	6.70	0.30	1.000	66
NATURAL POOR COVER					
"BARREN"	B	12.00	0.30	1.000	86

LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
NATURAL FAIR COVER					
"GRASS"	B	12.90	0.30	1.000	69
PUBLIC PARK	B	38.60	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.888
SUBAREA AREA(ACRES) = 51.50 SUBAREA RUNOFF(CFS) = 31.41
EFFECTIVE AREA(ACRES) = 41446.26 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 52789.0 PEAK FLOW RATE(CFS) = 37436.05
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12901.00 TO NODE 12902.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 216.00 DOWNSTREAM(FEET) = 215.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 122.04 CHANNEL SLOPE = 0.0082
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 8.91
CHANNEL FLOW THRU SUBAREA(CFS) = 37436.05
FLOW VELOCITY(FEET/SEC.) = 17.17 FLOW DEPTH(FEET) = 8.91
TRAVEL TIME(MIN.) = 0.12 Tc(MIN.) = 102.35
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115035.28 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19994.38	17.25	2.468	0.30(0.25)	0.83	3306.8	50110.00
2	21725.83	22.31	2.087	0.30(0.25)	0.83	4528.2	420.00
3	23164.37	26.48	1.867	0.30(0.25)	0.84	5738.0	400.00
4	25657.78	35.32	1.589	0.30(0.27)	0.89	9082.1	390.00
5	29003.91	51.52	1.287	0.30(0.28)	0.93	14945.5	40100.00
6	30128.76	59.44	1.206	0.30(0.28)	0.94	17773.4	11801.00
7	32122.73	70.32	1.130	0.30(0.29)	0.95	22357.8	11530.00
8	33179.73	74.73	1.100	0.30(0.29)	0.95	24672.3	11701.00
9	34081.62	78.24	1.077	0.30(0.29)	0.96	26765.5	11910.00
10	36718.81	88.50	1.007	0.30(0.29)	0.97	33459.7	10800.00
11	37402.52	92.76	0.985	0.30(0.29)	0.97	36405.1	11130.00
12	37436.05	102.35	0.943	0.30(0.29)	0.97	41446.3	12410.00
13	37163.38	110.61	0.908	0.30(0.29)	0.97	45185.4	11201.00
14	36877.32	115.56	0.886	0.30(0.29)	0.97	46917.1	12201.00
15	36008.18	122.56	0.862	0.30(0.29)	0.97	48774.2	12231.00
16	34862.98	130.29	0.846	0.30(0.29)	0.97	50408.5	10400.00
17	33675.77	138.14	0.830	0.30(0.29)	0.97	51703.6	12010.00
18	32606.87	144.02	0.818	0.30(0.29)	0.97	52050.6	10210.00
19	32143.06	147.04	0.812	0.30(0.29)	0.97	52167.8	12000.00
20	28989.62	171.90	0.761	0.30(0.29)	0.97	52789.0	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 37436.05 Tc(MIN.) = 102.35
AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.97 EFFECTIVE AREA(ACRES) = 41446.26

FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 15.1

=====
>>>>DEFINE MEMORY BANK # 1 <<<<
=====

PEAK FLOWRATE TABLE FILE NAME: P503XX50.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1768.30	18.70	0.30 (0.22)	0.74	1033.3	50320.00
2	1770.28	19.45	0.30 (0.22)	0.74	1064.8	50240.00
3	1774.79	20.47	0.30 (0.22)	0.74	1104.7	50330.00
4	1782.58	23.35	0.30 (0.22)	0.74	1202.5	50280.00
5	1764.12	24.56	0.30 (0.22)	0.74	1233.6	50300.00
6	1740.24	25.78	0.30 (0.22)	0.74	1255.7	50220.00
7	1627.11	29.66	0.30 (0.22)	0.74	1291.5	50260.00
8	1541.67	32.85	0.30 (0.22)	0.74	1298.6	50200.00
TOTAL AREA (ACRES) =						1298.6

FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<
=====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19994.38	17.25	2.468	0.30 (0.25)	0.83	3306.8	50110.00
2	21725.83	22.31	2.087	0.30 (0.25)	0.83	4528.2	420.00
3	23164.37	26.48	1.867	0.30 (0.25)	0.84	5738.0	400.00
4	25657.78	35.32	1.589	0.30 (0.27)	0.89	9082.1	390.00
5	29003.91	51.52	1.287	0.30 (0.28)	0.93	14945.5	40100.00
6	30128.76	59.44	1.206	0.30 (0.28)	0.94	17773.4	11801.00
7	32122.73	70.32	1.130	0.30 (0.29)	0.95	22357.8	11530.00
8	33179.73	74.73	1.100	0.30 (0.29)	0.95	24672.3	11701.00
9	34081.62	78.24	1.077	0.30 (0.29)	0.96	26765.5	11910.00
10	36718.81	88.50	1.007	0.30 (0.29)	0.97	33459.7	10800.00
11	37402.52	92.76	0.985	0.30 (0.29)	0.97	36405.1	11130.00
12	37436.05	102.35	0.943	0.30 (0.29)	0.97	41446.3	12410.00
13	37163.38	110.61	0.908	0.30 (0.29)	0.97	45185.4	11201.00
14	36877.32	115.56	0.886	0.30 (0.29)	0.97	46917.1	12201.00
15	36008.18	122.56	0.862	0.30 (0.29)	0.97	48774.2	12231.00
16	34862.98	130.29	0.846	0.30 (0.29)	0.97	50408.5	10400.00
17	33675.77	138.14	0.830	0.30 (0.29)	0.97	51703.6	12010.00
18	32606.87	144.02	0.818	0.30 (0.29)	0.97	52050.6	10210.00
19	32143.06	147.04	0.812	0.30 (0.29)	0.97	52167.8	12000.00
20	28989.62	171.90	0.761	0.30 (0.29)	0.97	52789.0	10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 =							115035.28 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1768.30	18.70	2.340	0.30 (0.22)	0.74	1033.3	50320.00
2	1770.28	19.45	2.274	0.30 (0.22)	0.74	1064.8	50240.00
3	1774.79	20.47	2.197	0.30 (0.22)	0.74	1104.7	50330.00
4	1782.58	23.35	2.024	0.30 (0.22)	0.74	1202.5	50280.00
5	1764.12	24.56	1.950	0.30 (0.22)	0.74	1233.6	50300.00
6	1740.24	25.78	1.894	0.30 (0.22)	0.74	1255.7	50220.00
7	1627.11	29.66	1.744	0.30 (0.22)	0.74	1291.5	50260.00

8 1541.67 32.85 1.655 0.30 (0.22) 0.74 1298.6 50200.00
LONGEST FLOWPATH FROM NODE 50220.00 TO NODE 12902.00 = 17597.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21723.63	17.25	2.468	0.30 (0.24)	0.81	4259.7	50110.00
2	22260.64	18.70	2.340	0.30 (0.24)	0.81	4691.4	50320.00
3	22520.10	19.45	2.274	0.30 (0.24)	0.81	4904.6	50240.00
4	22873.22	20.47	2.197	0.30 (0.24)	0.81	5190.4	50330.00
5	23505.59	22.31	2.087	0.30 (0.24)	0.81	5695.4	420.00
6	23866.53	23.35	2.024	0.30 (0.24)	0.81	6031.9	50280.00
7	24267.13	24.56	1.950	0.30 (0.24)	0.82	6415.4	50300.00
8	24661.74	25.78	1.894	0.30 (0.25)	0.82	6789.4	50220.00
9	24884.11	26.48	1.867	0.30 (0.25)	0.82	7000.2	400.00
10	25688.99	29.66	1.744	0.30 (0.25)	0.84	8233.2	50260.00
11	26502.96	32.85	1.655	0.30 (0.26)	0.86	9446.6	50200.00
12	27128.76	35.32	1.589	0.30 (0.26)	0.87	10380.7	390.00
13	30149.73	51.52	1.287	0.30 (0.27)	0.91	16244.1	40100.00
14	31186.90	59.44	1.206	0.30 (0.28)	0.93	19072.0	11801.00
15	33099.48	70.32	1.130	0.30 (0.28)	0.94	23656.4	11530.00
16	34124.39	74.73	1.100	0.30 (0.28)	0.94	25970.9	11701.00
17	35000.68	78.24	1.077	0.30 (0.28)	0.95	28064.1	11910.00
18	37563.17	88.50	1.007	0.30 (0.29)	0.96	34758.3	10800.00
19	38223.10	92.76	0.985	0.30 (0.29)	0.96	37703.7	11130.00
20	38211.90	102.35	0.943	0.30 (0.29)	0.96	42744.9	12410.00
21	37900.71	110.61	0.908	0.30 (0.29)	0.97	46484.0	11201.00
22	37591.58	115.56	0.886	0.30 (0.29)	0.97	48215.7	12201.00
23	36696.13	122.56	0.862	0.30 (0.29)	0.97	50072.8	12231.00
24	35534.02	130.29	0.846	0.30 (0.29)	0.97	51707.1	10400.00
25	34329.62	138.14	0.830	0.30 (0.29)	0.97	53002.2	12010.00
26	33247.85	144.02	0.818	0.30 (0.29)	0.97	53349.2	10210.00
27	32777.44	147.04	0.812	0.30 (0.29)	0.97	53466.4	12000.00
28	29569.62	171.90	0.761	0.30 (0.29)	0.97	54087.6	10100.00
TOTAL AREA (ACRES) =							54087.6

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 38223.10 Tc (MIN.) = 92.759
EFFECTIVE AREA (ACRES) = 37703.66 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.86
TOTAL AREA (ACRES) = 54087.6
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115035.28 FEET.

FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<
=====

FLOW PROCESS FROM NODE 12902.00 TO NODE 12903.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<
=====

ELEVATION DATA: UPSTREAM (FEET) = 215.00 DOWNSTREAM (FEET) = 214.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 895.53 CHANNEL SLOPE = 0.0011
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT (FEET) = 15.70
 CHANNEL FLOW THRU SUBAREA (CFS) = 38223.10
 FLOW VELOCITY (FEET/SEC.) = 8.74 FLOW DEPTH (FEET) = 15.70
 TRAVEL TIME (MIN.) = 1.71 Tc (MIN.) = 94.47
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115930.81 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21723.63	19.28	2.289	0.30 (0.24)	0.81	4259.7	50110.00
2	22260.64	20.72	2.183	0.30 (0.24)	0.81	4691.4	50320.00
3	22520.10	21.47	2.137	0.30 (0.24)	0.81	4904.6	50240.00
4	22873.22	22.48	2.076	0.30 (0.24)	0.81	5190.4	50330.00
5	23505.59	24.29	1.967	0.30 (0.24)	0.81	5695.4	420.00
6	23866.53	25.32	1.912	0.30 (0.24)	0.81	6031.9	50280.00
7	24267.13	26.53	1.865	0.30 (0.24)	0.82	6415.4	50300.00
8	24661.74	27.73	1.819	0.30 (0.25)	0.82	6789.4	50220.00
9	24884.11	28.43	1.792	0.30 (0.25)	0.82	7000.2	400.00
10	25688.99	31.59	1.689	0.30 (0.25)	0.84	8233.2	50260.00
11	26502.96	34.76	1.604	0.30 (0.26)	0.86	9446.6	50200.00
12	27128.76	37.22	1.539	0.30 (0.26)	0.87	10380.7	390.00
13	30149.73	53.36	1.268	0.30 (0.27)	0.91	16244.1	40100.00
14	31186.90	61.25	1.192	0.30 (0.28)	0.93	19072.0	11801.00
15	33099.48	72.10	1.118	0.30 (0.28)	0.94	23656.4	11530.00
16	34124.39	76.49	1.088	0.30 (0.28)	0.94	25970.9	11701.00
17	35000.68	79.99	1.065	0.30 (0.28)	0.95	28064.1	11910.00
18	37563.17	90.22	0.996	0.30 (0.29)	0.96	34758.3	10800.00
19	38223.10	94.47	0.978	0.30 (0.29)	0.96	37703.7	11130.00
20	38211.90	104.06	0.936	0.30 (0.29)	0.96	42744.9	12410.00
21	37900.71	112.32	0.900	0.30 (0.29)	0.97	46484.0	11201.00
22	37591.58	117.27	0.879	0.30 (0.29)	0.97	48215.7	12201.00
23	36696.13	124.29	0.858	0.30 (0.29)	0.97	50072.8	12231.00
24	35534.02	132.03	0.843	0.30 (0.29)	0.97	51707.1	10400.00
25	34329.62	139.91	0.827	0.30 (0.29)	0.97	53002.2	12010.00
26	33247.85	145.81	0.815	0.30 (0.29)	0.97	53349.2	10210.00
27	32777.44	148.83	0.808	0.30 (0.29)	0.97	53466.4	12000.00
28	29569.62	173.74	0.758	0.30 (0.29)	0.97	54087.6	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 38223.10 Tc (MIN.) = 94.47
 AREA-AVERAGED Fm (INCH/HR) = 0.29 AREA-AVERAGED Fp (INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.96 EFFECTIVE AREA (ACRES) = 37703.66

 FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P504XX50.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	145.17	13.27	0.30 (0.28)	0.94	70.7	50400.00
TOTAL AREA (ACRES) = 70.7						

 FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21723.63	19.28	2.289	0.30 (0.24)	0.81	4259.7	50110.00
2	22260.64	20.72	2.183	0.30 (0.24)	0.81	4691.4	50320.00
3	22520.10	21.47	2.137	0.30 (0.24)	0.81	4904.6	50240.00
4	22873.22	22.48	2.076	0.30 (0.24)	0.81	5190.4	50330.00
5	23505.59	24.29	1.967	0.30 (0.24)	0.81	5695.4	420.00
6	23866.53	25.32	1.912	0.30 (0.24)	0.81	6031.9	50280.00
7	24267.13	26.53	1.865	0.30 (0.24)	0.82	6415.4	50300.00
8	24661.74	27.73	1.819	0.30 (0.25)	0.82	6789.4	50220.00
9	24884.11	28.43	1.792	0.30 (0.25)	0.82	7000.2	400.00
10	25688.99	31.59	1.689	0.30 (0.25)	0.84	8233.2	50260.00
11	26502.96	34.76	1.604	0.30 (0.26)	0.86	9446.6	50200.00
12	27128.76	37.22	1.539	0.30 (0.26)	0.87	10380.7	390.00
13	30149.73	53.36	1.268	0.30 (0.27)	0.91	16244.1	40100.00
14	31186.90	61.25	1.192	0.30 (0.28)	0.93	19072.0	11801.00
15	33099.48	72.10	1.118	0.30 (0.28)	0.94	23656.4	11530.00
16	34124.39	76.49	1.088	0.30 (0.28)	0.94	25970.9	11701.00
17	35000.68	79.99	1.065	0.30 (0.28)	0.95	28064.1	11910.00
18	37563.17	90.22	0.996	0.30 (0.29)	0.96	34758.3	10800.00
19	38223.10	94.47	0.978	0.30 (0.29)	0.96	37703.7	11130.00
20	38211.90	104.06	0.936	0.30 (0.29)	0.96	42744.9	12410.00
21	37900.71	112.32	0.900	0.30 (0.29)	0.97	46484.0	11201.00
22	37591.58	117.27	0.879	0.30 (0.29)	0.97	48215.7	12201.00
23	36696.13	124.29	0.858	0.30 (0.29)	0.97	50072.8	12231.00
24	35534.02	132.03	0.843	0.30 (0.29)	0.97	51707.1	10400.00
25	34329.62	139.91	0.827	0.30 (0.29)	0.97	53002.2	12010.00
26	33247.85	145.81	0.815	0.30 (0.29)	0.97	53349.2	10210.00
27	32777.44	148.83	0.808	0.30 (0.29)	0.97	53466.4	12000.00
28	29569.62	173.74	0.758	0.30 (0.29)	0.97	54087.6	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115930.81 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	145.17	13.27	2.948	0.30 (0.28)	0.94	70.7	50400.00

LONGEST FLOWPATH FROM NODE 50400.00 TO NODE 12903.00 = 3607.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19913.19	13.27	2.948	0.30 (0.24)	0.81	3003.2	50400.00
2	21832.95	19.28	2.289	0.30 (0.24)	0.81	4330.4	50110.00
3	22364.14	20.72	2.183	0.30 (0.24)	0.81	4762.1	50320.00
4	22621.15	21.47	2.137	0.30 (0.24)	0.81	4975.3	50240.00
5	22970.95	22.48	2.076	0.30 (0.24)	0.81	5261.1	50330.00
6	23597.35	24.29	1.967	0.30 (0.24)	0.82	5766.1	420.00
7	23955.28	25.32	1.912	0.30 (0.24)	0.82	6102.6	50280.00
8	24353.36	26.53	1.865	0.30 (0.25)	0.82	6486.1	50300.00
9	24745.44	27.73	1.819	0.30 (0.25)	0.82	6860.1	50220.00
10	24966.33	28.43	1.792	0.30 (0.25)	0.82	7070.9	400.00
11	25765.61	31.59	1.689	0.30 (0.25)	0.84	8303.9	50260.00
12	26574.98	34.76	1.604	0.30 (0.26)	0.86	9517.3	50200.00
13	27197.23	37.22	1.539	0.30 (0.26)	0.87	10451.4	390.00

14	30203.46	53.36	1.268	0.30	(0.27)	0.91	16314.8	40100.00
15	31236.45	61.25	1.192	0.30	(0.28)	0.93	19142.7	11801.00
16	33145.04	72.10	1.118	0.30	(0.28)	0.94	23727.1	11530.00
17	34168.34	76.49	1.088	0.30	(0.28)	0.94	26041.6	11701.00
18	35043.33	79.99	1.065	0.30	(0.28)	0.95	28134.8	11910.00
19	37602.09	90.22	0.996	0.30	(0.29)	0.96	34829.0	10800.00
20	38261.01	94.47	0.978	0.30	(0.29)	0.96	37774.4	11130.00
21	38247.55	104.06	0.936	0.30	(0.29)	0.96	42815.6	12410.00
22	37934.41	112.32	0.900	0.30	(0.29)	0.97	46554.7	11201.00
23	37624.11	117.27	0.879	0.30	(0.29)	0.97	48286.4	12201.00
24	36727.55	124.29	0.858	0.30	(0.29)	0.97	50143.5	12231.00
25	35564.57	132.03	0.843	0.30	(0.29)	0.97	51777.8	10400.00
26	34359.30	139.91	0.827	0.30	(0.29)	0.97	53072.9	12010.00
27	33276.88	145.81	0.815	0.30	(0.29)	0.97	53419.9	10210.00
28	32806.14	148.83	0.808	0.30	(0.29)	0.97	53537.1	12000.00
29	29595.55	173.74	0.758	0.30	(0.29)	0.97	54158.3	10100.00

TOTAL AREA (ACRES) = 54158.3

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 38261.01 Tc (MIN.) = 94.466
EFFECTIVE AREA (ACRES) = 37774.36 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA (ACRES) = 54158.3
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115930.81 FEET.

FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

FLOW PROCESS FROM NODE 12903.00 TO NODE 12904.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 214.00 DOWNSTREAM (FEET) = 213.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 767.57 CHANNEL SLOPE = 0.0013
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 15.06
CHANNEL FLOW THRU SUBAREA (CFS) = 38261.01
FLOW VELOCITY (FEET/SEC.) = 9.23 FLOW DEPTH (FEET) = 15.06
TRAVEL TIME (MIN.) = 1.39 Tc (MIN.) = 95.85
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116698.38 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19913.19	14.97	2.670	0.30 (0.24)	0.81	3003.2	50400.00
2	21832.95	20.93	2.170	0.30 (0.24)	0.81	4330.4	50110.00
3	22364.14	22.36	2.084	0.30 (0.24)	0.81	4762.1	50320.00
4	22621.15	23.10	2.039	0.30 (0.24)	0.81	4975.3	50240.00
5	22970.95	24.10	1.978	0.30 (0.24)	0.81	5261.1	50330.00
6	23597.35	25.90	1.889	0.30 (0.24)	0.82	5766.1	420.00
7	23955.28	26.93	1.850	0.30 (0.24)	0.82	6102.6	50280.00
8	24353.36	28.12	1.804	0.30 (0.25)	0.82	6486.1	50300.00

9	24745.44	29.32	1.757	0.30	(0.25)	0.82	6860.1	50220.00
10	24966.33	30.01	1.731	0.30	(0.25)	0.82	7070.9	400.00
11	25765.61	33.16	1.647	0.30	(0.25)	0.84	8303.9	50260.00
12	26574.98	36.31	1.563	0.30	(0.26)	0.86	9517.3	50200.00
13	27197.23	38.76	1.498	0.30	(0.26)	0.87	10451.4	390.00
14	30203.46	54.85	1.253	0.30	(0.27)	0.91	16314.8	40100.00
15	31236.45	62.73	1.182	0.30	(0.28)	0.93	19142.7	11801.00
16	33145.04	73.55	1.108	0.30	(0.28)	0.94	23727.1	11530.00
17	34168.34	77.93	1.079	0.30	(0.28)	0.94	26041.6	11701.00
18	35043.33	81.42	1.055	0.30	(0.28)	0.95	28134.8	11910.00
19	37602.09	91.61	0.990	0.30	(0.29)	0.96	34829.0	10800.00
20	38261.01	95.85	0.972	0.30	(0.29)	0.96	37774.4	11130.00
21	38247.55	105.44	0.930	0.30	(0.29)	0.96	42815.6	12410.00
22	37934.41	113.71	0.894	0.30	(0.29)	0.97	46554.7	11201.00
23	37624.11	118.67	0.873	0.30	(0.29)	0.97	48286.4	12201.00
24	36727.55	125.69	0.855	0.30	(0.29)	0.97	50143.5	12231.00
25	35564.57	133.45	0.840	0.30	(0.29)	0.97	51777.8	10400.00
26	34359.30	141.34	0.824	0.30	(0.29)	0.97	53072.9	12010.00
27	33276.88	147.25	0.812	0.30	(0.29)	0.97	53419.9	10210.00
28	32806.14	150.28	0.805	0.30	(0.29)	0.97	53537.1	12000.00
29	29595.55	175.24	0.755	0.30	(0.29)	0.97	54158.3	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 38261.01 Tc (MIN.) = 95.85
AREA-AVERAGED Fm (INCH/HR) = 0.29 AREA-AVERAGED Fp (INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.96 EFFECTIVE AREA (ACRES) = 37774.36

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 3B50EVRL.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	421.97	16.63	0.30 (0.13)	0.43	195.9	203.00
2	417.74	19.16	0.30 (0.13)	0.43	213.7	210.00
TOTAL AREA (ACRES) =			213.7			

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19913.19	14.97	2.670	0.30 (0.24)	0.81	3003.2	50400.00
2	21832.95	20.93	2.170	0.30 (0.24)	0.81	4330.4	50110.00
3	22364.14	22.36	2.084	0.30 (0.24)	0.81	4762.1	50320.00
4	22621.15	23.10	2.039	0.30 (0.24)	0.81	4975.3	50240.00
5	22970.95	24.10	1.978	0.30 (0.24)	0.81	5261.1	50330.00
6	23597.35	25.90	1.889	0.30 (0.24)	0.82	5766.1	420.00
7	23955.28	26.93	1.850	0.30 (0.24)	0.82	6102.6	50280.00
8	24353.36	28.12	1.804	0.30 (0.25)	0.82	6486.1	50300.00
9	24745.44	29.32	1.757	0.30 (0.25)	0.82	6860.1	50220.00
10	24966.33	30.01	1.731	0.30 (0.25)	0.82	7070.9	400.00

11	25765.61	33.16	1.647	0.30 (0.25)	0.84	8303.9	50260.00
12	26574.98	36.31	1.563	0.30 (0.26)	0.86	9517.3	50200.00
13	27197.23	38.76	1.498	0.30 (0.26)	0.87	10451.4	390.00
14	30203.46	54.85	1.253	0.30 (0.27)	0.91	16314.8	40100.00
15	31236.45	62.73	1.182	0.30 (0.28)	0.93	19142.7	11801.00
16	33145.04	73.55	1.108	0.30 (0.28)	0.94	23727.1	11530.00
17	34168.34	77.93	1.079	0.30 (0.28)	0.94	26041.6	11701.00
18	35043.33	81.42	1.055	0.30 (0.28)	0.95	28134.8	11910.00
19	37602.09	91.61	0.990	0.30 (0.29)	0.96	34829.0	10800.00
20	38261.01	95.85	0.972	0.30 (0.29)	0.96	37774.4	11130.00
21	38247.55	105.44	0.930	0.30 (0.29)	0.96	42815.6	12410.00
22	37934.41	113.71	0.894	0.30 (0.29)	0.97	46554.7	11201.00
23	37624.11	118.67	0.873	0.30 (0.29)	0.97	48286.4	12201.00
24	36727.55	125.69	0.855	0.30 (0.29)	0.97	50143.5	12231.00
25	35564.57	133.45	0.840	0.30 (0.29)	0.97	51777.8	10400.00
26	34359.30	141.34	0.824	0.30 (0.29)	0.97	53072.9	12010.00
27	33276.88	147.25	0.812	0.30 (0.29)	0.97	53419.9	10210.00
28	32806.14	150.28	0.805	0.30 (0.29)	0.97	53537.1	12000.00
29	29595.55	175.24	0.755	0.30 (0.29)	0.97	54158.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116698.38 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	421.97	16.63	2.523	0.30 (0.13)	0.43	195.9	203.00
2	417.74	19.16	2.300	0.30 (0.13)	0.43	213.7	210.00

LONGEST FLOWPATH FROM NODE 210.00 TO NODE 12904.00 = 7986.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20316.63	14.97	2.670	0.30 (0.24)	0.79	3179.6	50400.00
2	20867.65	16.63	2.523	0.30 (0.24)	0.79	3567.3	203.00
3	21679.88	19.16	2.300	0.30 (0.24)	0.79	4149.5	210.00
4	22225.65	20.93	2.170	0.30 (0.24)	0.79	4544.1	50110.00
5	22740.26	22.36	2.084	0.30 (0.24)	0.80	4975.8	50320.00
6	22988.67	23.10	2.039	0.30 (0.24)	0.80	5189.0	50240.00
7	23326.83	24.10	1.978	0.30 (0.24)	0.80	5474.8	50330.00
8	23936.08	25.90	1.889	0.30 (0.24)	0.80	5979.8	420.00
9	24286.42	26.93	1.850	0.30 (0.24)	0.80	6316.3	50280.00
10	24675.62	28.12	1.804	0.30 (0.24)	0.81	6699.8	50300.00
11	25058.82	29.32	1.757	0.30 (0.24)	0.81	7073.8	50220.00
12	25274.59	30.01	1.731	0.30 (0.24)	0.81	7284.6	400.00
13	26057.77	33.16	1.647	0.30 (0.25)	0.83	8517.6	50260.00
14	26850.99	36.31	1.563	0.30 (0.25)	0.85	9731.0	50200.00
15	27460.74	38.76	1.498	0.30 (0.26)	0.86	10665.1	390.00
16	30419.85	54.85	1.253	0.30 (0.27)	0.91	16528.5	40100.00
17	31439.09	62.73	1.182	0.30 (0.28)	0.92	19356.4	11801.00
18	33333.59	73.55	1.108	0.30 (0.28)	0.93	23940.8	11530.00
19	34351.19	77.93	1.079	0.30 (0.28)	0.94	26255.3	11701.00
20	35221.64	81.42	1.055	0.30 (0.28)	0.94	28348.5	11910.00
21	37767.89	91.61	0.990	0.30 (0.29)	0.95	35042.7	10800.00
22	38423.27	95.85	0.972	0.30 (0.29)	0.96	37988.1	11130.00
23	38401.82	105.44	0.930	0.30 (0.29)	0.96	43029.3	12410.00
24	38081.80	113.71	0.894	0.30 (0.29)	0.96	46768.4	11201.00
25	37767.36	118.67	0.873	0.30 (0.29)	0.96	48500.1	12201.00
26	36867.46	125.69	0.855	0.30 (0.29)	0.96	50357.2	12231.00
27	35701.45	133.45	0.840	0.30 (0.29)	0.97	51991.5	10400.00

28	34493.10	141.34	0.824	0.30 (0.29)	0.97	53286.6	12010.00
29	33408.37	147.25	0.812	0.30 (0.29)	0.97	53633.6	10210.00
30	32936.43	150.28	0.805	0.30 (0.29)	0.97	53750.8	12000.00
31	29716.09	175.24	0.755	0.30 (0.29)	0.97	54372.0	10100.00

TOTAL AREA (ACRES) = 54372.0

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 38423.27 Tc (MIN.) = 95.85
EFFECTIVE AREA (ACRES) = 37988.05 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94
TOTAL AREA (ACRES) = 54372.0
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116698.38 FEET.

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 95.85
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.972
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCSSOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
RESIDENTIAL
".4 DWELLING/ACRE" B 0.10 0.30 0.900 56
NATURAL FAIR COVER
"WOODLAND, GRASS" B 0.20 0.30 1.000 65
NATURAL FAIR COVER
"WOODLAND, GRASS" B 0.80 0.30 1.000 65
COMMERCIAL B 1.20 0.30 0.100 56
COMMERCIAL B 1.50 0.30 0.100 56
NATURAL FAIR COVER
"GRASS" B 3.00 0.30 1.000 69
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.641
SUBAREA AREA (ACRES) = 6.80 SUBAREA RUNOFF (CFS) = 4.77
EFFECTIVE AREA (ACRES) = 37994.86 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA (ACRES) = 54378.8 PEAK FLOW RATE (CFS) = 38423.27
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 95.85
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.972
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCSSOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"GRASS" B 3.60 0.30 1.000 69
PUBLIC PARK B 15.10 0.30 0.850 56
NATURAL FAIR COVER
"GRASS" B 20.00 0.30 1.000 69
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.941

SUBAREA AREA (ACRES) = 38.70 SUBAREA RUNOFF (CFS) = 24.00
EFFECTIVE AREA (ACRES) = 38033.55 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA (ACRES) = 54417.5 PEAK FLOW RATE (CFS) = 38423.27
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

=====
END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 54417.5 TC (MIN.) = 95.85
EFFECTIVE AREA (ACRES) = 38033.55 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.957
PEAK FLOW RATE (CFS) = 38423.27

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20316.63	14.97	2.670	0.30 (0.24)	0.79	3225.1	50400.00
2	20867.65	16.63	2.523	0.30 (0.24)	0.79	3612.8	203.00
3	21679.88	19.16	2.300	0.30 (0.24)	0.79	4195.0	210.00
4	22225.65	20.93	2.170	0.30 (0.24)	0.80	4589.6	50110.00
5	22740.26	22.36	2.084	0.30 (0.24)	0.80	5021.3	50320.00
6	22988.67	23.10	2.039	0.30 (0.24)	0.80	5234.5	50240.00
7	23326.83	24.10	1.978	0.30 (0.24)	0.80	5520.3	50330.00
8	23936.08	25.90	1.889	0.30 (0.24)	0.80	6025.3	420.00
9	24286.42	26.93	1.850	0.30 (0.24)	0.80	6361.8	50280.00
10	24675.62	28.12	1.804	0.30 (0.24)	0.81	6745.3	50300.00
11	25058.82	29.32	1.757	0.30 (0.24)	0.81	7119.3	50220.00
12	25274.59	30.01	1.731	0.30 (0.24)	0.81	7330.1	400.00
13	26057.77	33.16	1.647	0.30 (0.25)	0.83	8563.1	50260.00
14	26850.99	36.31	1.563	0.30 (0.25)	0.85	9776.5	50200.00
15	27460.74	38.76	1.498	0.30 (0.26)	0.86	10710.6	390.00
16	30419.85	54.85	1.253	0.30 (0.27)	0.91	16574.0	40100.00
17	31439.09	62.73	1.182	0.30 (0.28)	0.92	19401.9	11801.00
18	33333.59	73.55	1.108	0.30 (0.28)	0.93	23986.3	11530.00
19	34351.19	77.93	1.079	0.30 (0.28)	0.94	26300.8	11701.00
20	35221.64	81.42	1.055	0.30 (0.28)	0.94	28394.0	11910.00
21	37767.89	91.61	0.990	0.30 (0.29)	0.95	35088.2	10800.00
22	38423.27	95.85	0.972	0.30 (0.29)	0.96	38033.6	11130.00
23	38401.82	105.44	0.930	0.30 (0.29)	0.96	43074.8	12410.00
24	38081.80	113.71	0.894	0.30 (0.29)	0.96	46813.9	11201.00
25	37767.36	118.67	0.873	0.30 (0.29)	0.96	48545.6	12201.00
26	36867.46	125.69	0.855	0.30 (0.29)	0.96	50402.7	12231.00
27	35701.45	133.45	0.840	0.30 (0.29)	0.97	52037.0	10400.00
28	34493.10	141.34	0.824	0.30 (0.29)	0.97	53332.1	12010.00
29	33408.37	147.25	0.812	0.30 (0.29)	0.97	53679.1	10210.00
30	32936.43	150.28	0.805	0.30 (0.29)	0.97	53796.3	12000.00
31	29716.09	175.24	0.755	0.30 (0.29)	0.97	54417.5	10100.00

=====
END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2013 Advanced Engineering Software (aes)
Ver. 20.0 Release Date: 06/01/2013 License ID 1237

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 133C FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 50-YR EV MAY 2023 ROKAMOTO *

FILE NAME: RU50EV33.DAT
TIME/DATE OF STUDY: 11:30 05/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 50.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.328
- 2) 10.00; 3.431
- 3) 15.00; 2.636
- 4) 20.00; 2.205
- 5) 25.00; 1.909
- 6) 30.00; 1.717
- 7) 40.00; 1.454
- 8) 50.00; 1.293
- 9) 60.00; 1.185
- 10) 90.00; 0.982
- 11) 120.00; 0.852
- 12) 180.00; 0.728
- 13) 360.00; 0.537
- 14) 1200.00; 0.235

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL: IN- / OUT-/PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:

- 1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13112.00 TO NODE 13222.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: S31X50.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2838.09	34.69	0.30 (0.24)	0.81	2526.1	13100.00
2	2813.56	59.31	0.30 (0.24)	0.81	3777.1	13000.00
3	2759.78	61.54	0.30 (0.24)	0.81	3796.8	13010.00
TOTAL AREA (ACRES) =						3796.8

FLOW PROCESS FROM NODE 13221.00 TO NODE 13222.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: S32X50.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1294.02	32.85	0.30 (0.25)	0.83	1118.5	13210.00
2	1295.27	33.25	0.30 (0.25)	0.83	1127.6	13200.00
TOTAL AREA (ACRES) =						1127.6

FLOW PROCESS FROM NODE 13221.00 TO NODE 13222.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1294.02	32.85	0.30 (0.25)	0.83	1118.5	13210.00
2	1295.27	33.25	0.30 (0.25)	0.83	1127.6	13200.00
TOTAL AREA (ACRES) =						1127.6

FLOW PROCESS FROM NODE 13112.00 TO NODE 13222.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

=====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1294.02	32.85	1.642	0.30 (0.25)	0.83	1118.5	13210.00
2	1295.27	33.25	1.631	0.30 (0.25)	0.83	1127.6	13200.00
LONGEST FLOWPATH FROM NODE 13200.00 TO NODE 13222.00 =							16821.05 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2838.09	34.69	1.594	0.30 (0.24)	0.81	2526.1	13100.00
2	2813.56	59.31	1.192	0.30 (0.24)	0.81	3777.1	13000.00
3	2759.78	61.54	1.175	0.30 (0.24)	0.81	3796.8	13010.00

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4078.05	32.85	1.642	0.30 (0.24)	0.82	3511.0	13210.00
2	4091.97	33.25	1.631	0.30 (0.24)	0.82	3549.2	13200.00
3	4098.01	34.69	1.594	0.30 (0.24)	0.82	3653.7	13100.00
4	3697.73	59.31	1.192	0.30 (0.24)	0.81	4904.7	13000.00
5	3627.24	61.54	1.175	0.30 (0.24)	0.81	4924.4	13010.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 4098.01 Tc(MIN.) = 34.689
 EFFECTIVE AREA(ACRES) = 3653.73 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82
 TOTAL AREA(ACRES) = 4924.4
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13222.00 = 32126.49 FEET.

FLOW PROCESS FROM NODE 13222.00 TO NODE 13222.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 13222.00 TO NODE 13222.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

FLOW PROCESS FROM NODE 13222.00 TO NODE 13301.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 427.51 DOWNSTREAM(FEET) = 382.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2533.33 CHANNEL SLOPE = 0.0180
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 5.04
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.505
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	1.40	0.30	0.100	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	15.60	0.30	1.000	66
RESIDENTIAL					
"3-4 DWELLINGS/ACRE"	B	0.10	0.30	0.600	56
AGRICULTURAL POOR COVER					

"ROW CROPS,CONTOURED" B 5.30 0.30 1.000 79

NATURAL POOR COVER
"BARREN" B 0.20 0.30 1.000 86
COMMERCIAL B 22.60 0.30 0.100 56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.521
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 4125.45
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.57
 AVERAGE FLOW DEPTH(FEET) = 5.04 TRAVEL TIME(MIN.) = 3.36
 Tc(MIN.) = 38.05
 SUBAREA AREA(ACRES) = 45.20 SUBAREA RUNOFF(CFS) = 54.88
 EFFECTIVE AREA(ACRES) = 3698.93 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81
 TOTAL AREA(ACRES) = 4969.6 PEAK FLOW RATE(CFS) = 4200.85
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 5.09

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 5.09 FLOW VELOCITY(FEET/SEC.) = 12.64
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4192.43	36.22	1.553	0.30 (0.24)	0.81	3556.2	13210.00
2	4203.97	36.62	1.543	0.30 (0.24)	0.81	3594.4	13200.00
3	4200.85	38.05	1.505	0.30 (0.24)	0.81	3698.9	13100.00
4	4113.28	62.78	1.166	0.30 (0.24)	0.81	4949.9	13000.00
5	4061.85	65.03	1.151	0.30 (0.24)	0.81	4969.6	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 4203.97 Tc(MIN.) = 36.62
 AREA-AVERAGED Fm(INCH/HR) = 0.24 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.81 EFFECTIVE AREA(ACRES) = 3594.44

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 36.62
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.543
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	1.00	0.30	1.000	79
NATURAL POOR COVER					
"BARREN"	B	0.50	0.30	1.000	86
COMMERCIAL	B	7.40	0.30	0.100	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	4.70	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	2.90	0.30	1.000	65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.596					
SUBAREA AREA(ACRES) = 16.50 SUBAREA RUNOFF(CFS) = 20.26					
EFFECTIVE AREA(ACRES) = 3610.94 AREA-AVERAGED Fm(INCH/HR) = 0.24					

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81
TOTAL AREA (ACRES) = 4986.1 PEAK FLOW RATE (CFS) = 4224.23

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 36.62
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.543
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL POOR COVER
"BARREN" B 1.30 0.30 1.000 86
COMMERCIAL B 0.20 0.30 0.100 56
AGRICULTURAL POOR COVER
"ROW CROPS, CONTOURED" B 5.30 0.30 1.000 79
NATURAL FAIR COVER
"WOODLAND, GRASS" B 0.30 0.30 1.000 65
NATURAL FAIR COVER
"CHAPARRAL, BROADLEAF" B 0.20 0.30 1.000 63
NATURAL FAIR COVER
"OPEN BRUSH" B 0.60 0.30 1.000 66
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.977
SUBAREA AREA (ACRES) = 7.90 SUBAREA RUNOFF (CFS) = 8.89
EFFECTIVE AREA (ACRES) = 3618.84 AREA-AVERAGED Fm (INCH/HR) = 0.24
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81
TOTAL AREA (ACRES) = 4994.0 PEAK FLOW RATE (CFS) = 4233.12

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 36.62
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.543
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
AGRICULTURAL POOR COVER
"ROW CROPS, CONTOURED" B 4.30 0.30 1.000 79
NATURAL FAIR COVER
"WOODLAND, GRASS" B 0.80 0.30 1.000 65
NATURAL FAIR COVER
"CHAPARRAL, BROADLEAF" B 1.10 0.30 1.000 63
NATURAL FAIR COVER
"OPEN BRUSH" B 6.90 0.30 1.000 66
AGRICULTURAL POOR COVER
"ROW CROPS, CONTOURED" B 7.90 0.30 1.000 79
NATURAL FAIR COVER
"WOODLAND, GRASS" B 1.00 0.30 1.000 65
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 22.00 SUBAREA RUNOFF (CFS) = 24.61
EFFECTIVE AREA (ACRES) = 3640.84 AREA-AVERAGED Fm (INCH/HR) = 0.24
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81

TOTAL AREA (ACRES) = 5016.0 PEAK FLOW RATE (CFS) = 4257.73

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 36.62
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.543
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"OPEN BRUSH" B 0.40 0.30 1.000 66
AGRICULTURAL POOR COVER
"ROW CROPS, CONTOURED" B 14.60 0.30 1.000 79
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 15.00 SUBAREA RUNOFF (CFS) = 16.78
EFFECTIVE AREA (ACRES) = 3655.84 AREA-AVERAGED Fm (INCH/HR) = 0.24
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81
TOTAL AREA (ACRES) = 5031.0 PEAK FLOW RATE (CFS) = 4274.51

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<

FLOW PROCESS FROM NODE 31100.00 TO NODE 31101.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH (FEET) = 317.00
ELEVATION DATA: UPSTREAM (FEET) = 801.00 DOWNSTREAM (FEET) = 685.00

Tc = K * [(LENGTH ** 3.00) / (ELEVATION CHANGE)] ** 0.20
SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 8.641
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 3.947
SUBAREA Tc AND LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)
NATURAL FAIR COVER
"CHAPARRAL, BROADLEAF" B 0.50 0.30 1.000 63 8.64
NATURAL FAIR COVER
"OPEN BRUSH" B 0.30 0.30 1.000 66 8.64
NATURAL FAIR COVER
"OPEN BRUSH" B 0.30 0.30 1.000 66 8.64
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF (CFS) = 3.61
TOTAL AREA (ACRES) = 1.10 PEAK FLOW RATE (CFS) = 3.61

FLOW PROCESS FROM NODE 31101.00 TO NODE 31102.00 IS CODE = 51

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 685.00 DOWNSTREAM(FEET) = 655.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 135.00 CHANNEL SLOPE = 0.2222
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 3.823
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS
LAND USE           GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"CHAPARRAL,BROADLEAF"   B       0.50   0.30   1.000   63
NATURAL FAIR COVER
"OPEN BRUSH"           B       0.10   0.30   1.000   66
NATURAL FAIR COVER
"OPEN BRUSH"           B       0.70   0.30   1.000   66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5.67
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.90
AVERAGE FLOW DEPTH(FEET) = 0.52 TRAVEL TIME(MIN.) = 0.33
Tc(MIN.) = 8.97
SUBAREA AREA(ACRES) = 1.30 SUBAREA RUNOFF(CFS) = 4.12
EFFECTIVE AREA(ACRES) = 2.40 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 2.4 PEAK FLOW RATE(CFS) = 7.61

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.58 FLOW VELOCITY(FEET/SEC.) = 7.42
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31102.00 = 452.00 FEET.

```

```

*****
FLOW PROCESS FROM NODE 31102.00 TO NODE 31103.00 IS CODE = 51
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 655.00 DOWNSTREAM(FEET) = 630.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 203.00 CHANNEL SLOPE = 0.1232
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 10.00
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 3.665
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS
LAND USE           GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"CHAPARRAL,BROADLEAF"   B       0.30   0.30   1.000   63
NATURAL FAIR COVER
"OPEN BRUSH"           B       0.10   0.30   1.000   66
NATURAL FAIR COVER
"OPEN BRUSH"           B       1.90   0.30   1.000   66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 11.09
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.13
AVERAGE FLOW DEPTH(FEET) = 0.67 TRAVEL TIME(MIN.) = 0.42
Tc(MIN.) = 9.38

```

```

SUBAREA AREA(ACRES) = 2.30 SUBAREA RUNOFF(CFS) = 6.97
EFFECTIVE AREA(ACRES) = 4.70 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 4.7 PEAK FLOW RATE(CFS) = 14.23

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.74 FLOW VELOCITY(FEET/SEC.) = 8.60
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31103.00 = 655.00 FEET.

```

```

*****
FLOW PROCESS FROM NODE 31103.00 TO NODE 31104.00 IS CODE = 51
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 630.00 DOWNSTREAM(FEET) = 605.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 321.00 CHANNEL SLOPE = 0.0779
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 3.395
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS
LAND USE           GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"OPEN BRUSH"           B       1.10   0.30   1.000   66
NATURAL FAIR COVER
"OPEN BRUSH"           B       2.50   0.30   1.000   66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 19.25
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.36
AVERAGE FLOW DEPTH(FEET) = 1.00 TRAVEL TIME(MIN.) = 0.84
Tc(MIN.) = 10.22
SUBAREA AREA(ACRES) = 3.60 SUBAREA RUNOFF(CFS) = 10.03
EFFECTIVE AREA(ACRES) = 8.30 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 8.3 PEAK FLOW RATE(CFS) = 23.12

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.08 FLOW VELOCITY(FEET/SEC.) = 6.63
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31104.00 = 976.00 FEET.

```

```

*****
FLOW PROCESS FROM NODE 31104.00 TO NODE 31105.00 IS CODE = 51
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 605.00 DOWNSTREAM(FEET) = 585.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 288.00 CHANNEL SLOPE = 0.0694
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 3.284
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS
LAND USE           GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"CHAPARRAL,BROADLEAF"   B       0.70   0.30   1.000   63

```

NATURAL FAIR COVER
"CHAPARRAL,BROADLEAF" B 0.60 0.30 1.000 63
NATURAL FAIR COVER
"OPEN BRUSH" B 3.00 0.30 1.000 66
NATURAL FAIR COVER
"OPEN BRUSH" B 2.10 0.30 1.000 66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 31.72
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.87
AVERAGE FLOW DEPTH(FEET) = 1.24 TRAVEL TIME(MIN.) = 0.70
Tc(MIN.) = 10.92
SUBAREA AREA(ACRES) = 6.40 SUBAREA RUNOFF(CFS) = 17.19
EFFECTIVE AREA(ACRES) = 14.70 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 14.7 PEAK FLOW RATE(CFS) = 39.48

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.35 FLOW VELOCITY(FEET/SEC.) = 7.27
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31105.00 = 1264.00 FEET.

FLOW PROCESS FROM NODE 31105.00 TO NODE 31106.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 585.00 DOWNSTREAM(FEET) = 560.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 344.00 CHANNEL SLOPE = 0.0727
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 3.170

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.60	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	2.80	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.60	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.10	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.60	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	4.10	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 53.43
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.00
AVERAGE FLOW DEPTH(FEET) = 1.49 TRAVEL TIME(MIN.) = 0.72
Tc(MIN.) = 11.64
SUBAREA AREA(ACRES) = 10.80 SUBAREA RUNOFF(CFS) = 27.90
EFFECTIVE AREA(ACRES) = 25.50 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 25.5 PEAK FLOW RATE(CFS) = 65.87

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.62 FLOW VELOCITY(FEET/SEC.) = 8.36
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31106.00 = 1608.00 FEET.

FLOW PROCESS FROM NODE 31106.00 TO NODE 31107.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 560.00 DOWNSTREAM(FEET) = 530.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 619.00 CHANNEL SLOPE = 0.0485
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.956

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.80	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	1.90	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.50	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	8.20	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.70	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 83.92
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.67
AVERAGE FLOW DEPTH(FEET) = 1.91 TRAVEL TIME(MIN.) = 1.35
Tc(MIN.) = 12.99
SUBAREA AREA(ACRES) = 15.10 SUBAREA RUNOFF(CFS) = 36.10
EFFECTIVE AREA(ACRES) = 40.60 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 40.6 PEAK FLOW RATE(CFS) = 97.06

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 2.02 FLOW VELOCITY(FEET/SEC.) = 7.94
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31107.00 = 2227.00 FEET.

FLOW PROCESS FROM NODE 31107.00 TO NODE 31108.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 530.00 DOWNSTREAM(FEET) = 515.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 377.00 CHANNEL SLOPE = 0.0398
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.827

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					

"CHAPARRAL,BROADLEAF" B 0.50 0.30 1.000 63
 NATURAL FAIR COVER
 "CHAPARRAL,BROADLEAF" B 6.50 0.30 1.000 63
 NATURAL FAIR COVER
 "CHAPARRAL,BROADLEAF" B 1.30 0.30 1.000 63
 NATURAL FAIR COVER
 "OPEN BRUSH" B 1.10 0.30 1.000 66
 NATURAL FAIR COVER
 "OPEN BRUSH" B 5.50 0.30 1.000 66
 NATURAL FAIR COVER
 "OPEN BRUSH" B 3.40 0.30 1.000 66
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 117.88
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.74
 AVERAGE FLOW DEPTH(FEET) = 2.25 TRAVEL TIME(MIN.) = 0.81
 Tc(MIN.) = 13.80
 SUBAREA AREA(ACRES) = 18.30 SUBAREA RUNOFF(CFS) = 41.62
 EFFECTIVE AREA(ACRES) = 58.90 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 58.9 PEAK FLOW RATE(CFS) = 133.97
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 2.36 FLOW VELOCITY(FEET/SEC.) = 8.00
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31108.00 = 2604.00 FEET.

 FLOW PROCESS FROM NODE 31108.00 TO NODE 31109.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 515.00 DOWNSTREAM(FEET) = 490.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 520.00 CHANNEL SLOPE = 0.0481
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.671
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.70	0.30	1.000	63
NATURAL FAIR COVER					
"GRASS"	B	2.20	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	3.10	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.90	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	7.40	0.30	1.000	63
NATURAL FAIR COVER					
"GRASS"	B	0.30	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 149.55
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.82
 AVERAGE FLOW DEPTH(FEET) = 2.38 TRAVEL TIME(MIN.) = 0.98
 Tc(MIN.) = 14.78

SUBAREA AREA(ACRES) = 14.60 SUBAREA RUNOFF(CFS) = 31.15
 EFFECTIVE AREA(ACRES) = 73.50 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 73.5 PEAK FLOW RATE(CFS) = 156.84
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 2.42 FLOW VELOCITY(FEET/SEC.) = 8.92
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31109.00 = 3124.00 FEET.

 FLOW PROCESS FROM NODE 31109.00 TO NODE 31109.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 14.78
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.671
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	11.40	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	8.90	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	1.90	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	9.20	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	1.40	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 32.80 SUBAREA RUNOFF(CFS) = 69.99
 EFFECTIVE AREA(ACRES) = 106.30 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 106.3 PEAK FLOW RATE(CFS) = 226.83

 FLOW PROCESS FROM NODE 31109.00 TO NODE 31110.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 490.00 DOWNSTREAM(FEET) = 432.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1420.00 CHANNEL SLOPE = 0.0408
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.435
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	0.80	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.60	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.10	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	1.30	0.30	1.000	79

NATURAL FAIR COVER
 "WOODLAND,GRASS" B 4.00 0.30 1.000 65
 NATURAL FAIR COVER
 "CHAPARRAL,BROADLEAF" B 1.50 0.30 1.000 63
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 234.81
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.29
 AVERAGE FLOW DEPTH(FEET) = 2.90 TRAVEL TIME(MIN.) = 2.55
 Tc(MIN.) = 17.33
 SUBAREA AREA(ACRES) = 8.30 SUBAREA RUNOFF(CFS) = 15.95
 EFFECTIVE AREA(ACRES) = 114.60 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 114.6 PEAK FLOW RATE(CFS) = 226.83
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 2.87 FLOW VELOCITY(FEET/SEC.) = 9.21
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31110.00 = 4544.00 FEET.

 FLOW PROCESS FROM NODE 31110.00 TO NODE 31110.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 17.33
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.435
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 NATURAL FAIR COVER
 "GRASS" B 0.30 0.30 1.000 69
 NATURAL FAIR COVER
 "OPEN BRUSH" B 9.60 0.30 1.000 66
 RESIDENTIAL
 ".4 DWELLING/ACRE" B 0.40 0.30 0.900 56
 AGRICULTURAL POOR COVER
 "ROW CROPS,CONTOURED" B 6.20 0.30 1.000 79
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 3.90 0.30 1.000 65
 AGRICULTURAL POOR COVER
 "ROW CROPS,CONTOURED" B 1.40 0.30 1.000 79
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.998
 SUBAREA AREA(ACRES) = 21.80 SUBAREA RUNOFF(CFS) = 41.91
 EFFECTIVE AREA(ACRES) = 136.40 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 136.4 PEAK FLOW RATE(CFS) = 262.16

 FLOW PROCESS FROM NODE 31110.00 TO NODE 13301.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 432.00 DOWNSTREAM(FEET) = 382.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1847.00 CHANNEL SLOPE = 0.0271
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.144
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 NATURAL POOR COVER
 "BARREN" B 4.90 0.30 1.000 86
 AGRICULTURAL POOR COVER
 "ROW CROPS,CONTOURED" B 1.50 0.30 1.000 79
 RESIDENTIAL
 ".4 DWELLING/ACRE" B 0.60 0.30 0.900 56
 AGRICULTURAL POOR COVER
 "ROW CROPS,CONTOURED" B 2.50 0.30 1.000 79
 AGRICULTURAL POOR COVER
 "ROW CROPS,CONTOURED" B 5.30 0.30 1.000 79
 AGRICULTURAL POOR COVER
 "ROW CROPS,CONTOURED" B 3.30 0.30 1.000 79
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.997
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 277.19
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.30
 AVERAGE FLOW DEPTH(FEET) = 3.34 TRAVEL TIME(MIN.) = 3.71
 Tc(MIN.) = 21.04
 SUBAREA AREA(ACRES) = 18.10 SUBAREA RUNOFF(CFS) = 30.05
 EFFECTIVE AREA(ACRES) = 154.50 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 154.5 PEAK FLOW RATE(CFS) = 262.16
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 3.27 FLOW VELOCITY(FEET/SEC.) = 8.18
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 13301.00 = 6391.00 FEET.

 FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	262.16	21.04	2.144	0.30(0.30)	1.00	154.5	31100.00

LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 13301.00 = 6391.00 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4263.54	36.22	1.553	0.30(0.24)	0.81	3617.6	13210.00
2	4274.51	36.62	1.543	0.30(0.24)	0.81	3655.8	13200.00
3	4269.30	38.05	1.505	0.30(0.24)	0.81	3760.3	13100.00
4	4162.99	62.78	1.166	0.30(0.24)	0.81	5011.3	13000.00
5	4110.72	65.03	1.151	0.30(0.24)	0.81	5031.0	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
---------------	---------	-----------	---------------------	------------------	----	------------	----------------

1	3854.45	21.04	2.144	0.30	(0.25)	0.83	2255.5	31100.00
2	4441.77	36.22	1.553	0.30	(0.25)	0.82	3772.1	13210.00
3	4451.27	36.62	1.543	0.30	(0.25)	0.82	3810.3	13200.00
4	4440.71	38.05	1.505	0.30	(0.25)	0.82	3914.8	13100.00
5	4286.17	62.78	1.166	0.30	(0.24)	0.82	5165.8	13000.00
6	4231.74	65.03	1.151	0.30	(0.24)	0.82	5185.5	13010.00

TOTAL AREA (ACRES) = 5185.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 4451.27 Tc(MIN.) = 36.616
EFFECTIVE AREA(ACRES) = 3810.34 AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82
TOTAL AREA(ACRES) = 5185.5
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<<

FLOW PROCESS FROM NODE 13301.00 TO NODE 13302.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 382.00 DOWNSTREAM(FEET) = 375.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1141.09 CHANNEL SLOPE = 0.0061
GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 7.07
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.487
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	1.20	0.30	1.000	86
AGRICULTURAL POOR COVER					
"ROW CROPS, STRAIGHT ROW"	B	0.60	0.30	1.000	81
NATURAL POOR COVER					
"BARREN"	B	0.90	0.30	1.000	86
NATURAL FAIR COVER					
"OPEN BRUSH"	B	4.80	0.30	1.000	66
AGRICULTURAL POOR COVER					
"ROW CROPS, STRAIGHT ROW"	B	1.90	0.30	1.000	81

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 4456.29
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.86
AVERAGE FLOW DEPTH(FEET) = 7.07 TRAVEL TIME(MIN.) = 2.15
Tc(MIN.) = 38.76
SUBAREA AREA(ACRES) = 9.40 SUBAREA RUNOFF(CFS) = 10.04
EFFECTIVE AREA(ACRES) = 3819.74 AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82
TOTAL AREA(ACRES) = 5194.9 PEAK FLOW RATE(CFS) = 4451.27
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 7.06

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 7.06 FLOW VELOCITY(FEET/SEC.) = 8.86

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13302.00 = 35800.91 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3854.45	23.28	2.011	0.30(0.25)	0.83	2264.9	31100.00
2	4441.77	38.37	1.497	0.30(0.25)	0.82	3781.5	13210.00
3	4451.27	38.76	1.487	0.30(0.25)	0.82	3819.7	13200.00
4	4440.71	40.20	1.451	0.30(0.25)	0.82	3924.2	13100.00
5	4286.17	64.96	1.151	0.30(0.24)	0.82	5175.2	13000.00
6	4231.74	67.21	1.136	0.30(0.24)	0.82	5194.9	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 4451.27 Tc(MIN.) = 38.76
AREA-AVERAGED Fm(INCH/HR) = 0.25 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.82 EFFECTIVE AREA(ACRES) = 3819.74

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 38.76
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.487
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	13.80	0.30	1.000	86
NATURAL POOR COVER					
"BARREN"	B	2.60	0.30	1.000	86
COMMERCIAL	B	1.10	0.30	0.100	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	3.50	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	6.90	0.30	1.000	79
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.952
SUBAREA AREA(ACRES) = 28.10 SUBAREA RUNOFF(CFS) = 30.37
EFFECTIVE AREA(ACRES) = 3847.84 AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82
TOTAL AREA(ACRES) = 5223.0 PEAK FLOW RATE(CFS) = 4451.27
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 38.76
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.487
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	0.10	0.30	1.000	79
COMMERCIAL	B	0.10	0.30	0.100	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	2.40	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	0.50	0.30	1.000	79

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.894
SUBAREA AREA(ACRES) = 3.10 SUBAREA RUNOFF(CFS) = 3.40
EFFECTIVE AREA(ACRES) = 3850.94 AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82
TOTAL AREA(ACRES) = 5226.1 PEAK FLOW RATE(CFS) = 4451.27
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 38.76
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.487
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	0.10	0.30	1.000	86
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.60	0.30	1.000	66
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	3.10	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.40	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	0.20	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	13.80	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 20.20 SUBAREA RUNOFF(CFS) = 21.57
EFFECTIVE AREA(ACRES) = 3871.14 AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82
TOTAL AREA(ACRES) = 5246.3 PEAK FLOW RATE(CFS) = 4451.27
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 38.76
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.487
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
"ROW CROPS, CONTOURED"	B	34.60	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	2.40	0.30	1.000	65
NATURAL FAIR COVER					
"OPEN BRUSH"	B	22.60	0.30	1.000	66
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	11.60	0.30	1.000	79
APARTMENTS	B	0.40	0.30	0.200	56
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	4.80	0.30	1.000	63

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.996
SUBAREA AREA(ACRES) = 76.40 SUBAREA RUNOFF(CFS) = 81.67
EFFECTIVE AREA(ACRES) = 3947.54 AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
TOTAL AREA(ACRES) = 5322.7 PEAK FLOW RATE(CFS) = 4451.27
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 38.76
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.487
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	1.60	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	46.40	0.30	1.000	66
RESIDENTIAL					
"11+ DWELLINGS/ACRE"	B	0.10	0.30	0.200	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	60.70	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	5.80	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999
SUBAREA AREA(ACRES) = 114.60 SUBAREA RUNOFF(CFS) = 122.40
EFFECTIVE AREA(ACRES) = 4062.14 AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
TOTAL AREA(ACRES) = 5437.3 PEAK FLOW RATE(CFS) = 4523.12

FLOW PROCESS FROM NODE 13302.00 TO NODE 13303.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 375.00 DOWNSTREAM(FEET) = 355.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 2193.96 CHANNEL SLOPE = 0.0091
GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 6.40
CHANNEL FLOW THRU SUBAREA(CFS) = 4523.12
FLOW VELOCITY(FEET/SEC.) = 10.22 FLOW DEPTH(FEET) = 6.40

TRAVEL TIME(MIN.) = 3.58 Tc(MIN.) = 42.34
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13303.00 = 37994.87 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3967.75	27.00	1.832	0.30(0.25)	0.84	2507.3	31100.00
2	4517.95	41.95	1.423	0.30(0.25)	0.83	4023.9	13210.00
3	4523.12	42.34	1.416	0.30(0.25)	0.83	4062.1	13200.00
4	4506.32	43.78	1.393	0.30(0.25)	0.83	4166.6	13100.00
5	4408.65	68.56	1.127	0.30(0.25)	0.82	5417.6	13000.00
6	4350.33	70.83	1.112	0.30(0.25)	0.82	5437.3	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 4523.12 Tc(MIN.) = 42.34
AREA-AVERAGED Fm(INCH/HR) = 0.25 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.83 EFFECTIVE AREA(ACRES) = 4062.14

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 42.34

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.416

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER "BARREN"	B	0.20	0.30	1.000	86
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.40	0.30	1.000	65
NATURAL POOR COVER "BARREN"	B	0.80	0.30	1.000	86
COMMERCIAL	B	1.40	0.30	0.100	56
NATURAL FAIR COVER "GRASS"	B	2.60	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	2.20	0.30	1.000	66

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.834

SUBAREA AREA(ACRES) = 7.60 SUBAREA RUNOFF(CFS) = 7.98

EFFECTIVE AREA(ACRES) = 4069.74 AREA-AVERAGED Fm(INCH/HR) = 0.25

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83

TOTAL AREA(ACRES) = 5444.9 PEAK FLOW RATE(CFS) = 4523.12

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 42.34

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.416

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	3.10	0.30	1.000	79

NATURAL FAIR COVER "WOODLAND,GRASS"	B	3.40	0.30	1.000	65
NATURAL POOR COVER "BARREN"	B	0.50	0.30	1.000	86
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	B	0.20	0.30	1.000	63
COMMERCIAL	B	3.60	0.30	0.100	56
NATURAL FAIR COVER "GRASS"	B	4.00	0.30	1.000	69

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.781
SUBAREA AREA(ACRES) = 14.80 SUBAREA RUNOFF(CFS) = 15.74
EFFECTIVE AREA(ACRES) = 4084.54 AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
TOTAL AREA(ACRES) = 5459.7 PEAK FLOW RATE(CFS) = 4523.12
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 42.34

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.416

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	14.60	0.30	1.000	66
AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	6.30	0.30	1.000	79
NATURAL FAIR COVER "WOODLAND,GRASS"	B	3.70	0.30	1.000	65

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 24.60 SUBAREA RUNOFF(CFS) = 24.72
EFFECTIVE AREA(ACRES) = 4109.14 AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
TOTAL AREA(ACRES) = 5484.3 PEAK FLOW RATE(CFS) = 4523.12
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 42.34

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.416

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER "BARREN"	B	0.50	0.30	1.000	86
COMMERCIAL	B	0.30	0.30	0.100	56
NATURAL FAIR COVER "OPEN BRUSH"	B	0.20	0.30	1.000	66
RESIDENTIAL ".4 DWELLING/ACRE"	B	0.80	0.30	0.900	56

AGRICULTURAL POOR COVER
 "ROW CROPS,CONTOURED" B 1.60 0.30 1.000 79
 NATURAL POOR COVER
 "BARREN" B 31.90 0.30 1.000 86
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.990
 SUBAREA AREA(ACRES) = 35.30 SUBAREA RUNOFF(CFS) = 35.56
 EFFECTIVE AREA(ACRES) = 4144.44 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
 TOTAL AREA(ACRES) = 5519.6 PEAK FLOW RATE(CFS) = 4523.12
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 42.34
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.416
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	1.70	0.30	0.100	56
NATURAL FAIR COVER "OPEN BRUSH"	B	0.30	0.30	1.000	66
RESIDENTIAL ".4 DWELLING/ACRE"	B	2.60	0.30	0.900	56
AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	5.50	0.30	1.000	79
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.20	0.30	1.000	65
NATURAL FAIR COVER "OPEN BRUSH"	B	0.20	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.830
 SUBAREA AREA(ACRES) = 10.50 SUBAREA RUNOFF(CFS) = 11.03
 EFFECTIVE AREA(ACRES) = 4154.94 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
 TOTAL AREA(ACRES) = 5530.1 PEAK FLOW RATE(CFS) = 4523.12
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 42.34
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.416
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL ".4 DWELLING/ACRE"	B	1.30	0.30	0.900	56
NATURAL POOR COVER "BARREN"	B	0.30	0.30	1.000	86
COMMERCIAL	B	0.20	0.30	0.100	56
NATURAL FAIR COVER "OPEN BRUSH"	B	0.30	0.30	1.000	66

RESIDENTIAL
 ".4 DWELLING/ACRE" B 6.50 0.30 0.900 56
 AGRICULTURAL POOR COVER
 "ROW CROPS,CONTOURED" B 3.00 0.30 1.000 79
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.917
 SUBAREA AREA(ACRES) = 11.60 SUBAREA RUNOFF(CFS) = 11.91
 EFFECTIVE AREA(ACRES) = 4166.54 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
 TOTAL AREA(ACRES) = 5541.7 PEAK FLOW RATE(CFS) = 4523.12
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13303.00 TO NODE 13304.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 355.00 DOWNSTREAM(FEET) = 350.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 925.40 CHANNEL SLOPE = 0.0054
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 7.37
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.387
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER "BARREN"	B	0.20	0.30	1.000	86
AGRICULTURAL POOR COVER "ROW CROPS,STRAIGHT ROW"	B	0.50	0.30	1.000	81
NATURAL FAIR COVER "WOODLAND,GRASS"	B	1.10	0.30	1.000	65
NATURAL POOR COVER "BARREN"	B	0.30	0.30	1.000	86
NATURAL FAIR COVER "GRASS"	B	1.10	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	3.50	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 4526.40
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.51
 AVERAGE FLOW DEPTH(FEET) = 7.37 TRAVEL TIME(MIN.) = 1.81
 Tc(MIN.) = 44.15
 SUBAREA AREA(ACRES) = 6.70 SUBAREA RUNOFF(CFS) = 6.56
 EFFECTIVE AREA(ACRES) = 4173.24 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
 TOTAL AREA(ACRES) = 5548.4 PEAK FLOW RATE(CFS) = 4523.12
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 7.37

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 7.37 FLOW VELOCITY(FEET/SEC.) = 8.51
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13304.00 = 38920.27 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3967.75	28.88	1.760	0.30 (0.25)	0.85	2618.4	31100.00
2	4517.95	43.76	1.393	0.30 (0.25)	0.83	4135.0	13210.00
3	4523.12	44.15	1.387	0.30 (0.25)	0.83	4173.2	13200.00
4	4506.32	45.59	1.364	0.30 (0.25)	0.83	4277.7	13100.00
5	4408.65	70.39	1.115	0.30 (0.25)	0.83	5528.7	13000.00
6	4350.33	72.66	1.099	0.30 (0.25)	0.83	5548.4	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 4523.12 Tc(MIN.) = 44.15
 AREA-AVERAGED Fm(INCH/HR) = 0.25 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.83 EFFECTIVE AREA(ACRES) = 4173.24

FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 44.15
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.387
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 AGRICULTURAL POOR COVER
 "ROW CROPS,STRAIGHT ROW" B 1.40 0.30 1.000 81
 NATURAL FAIR COVER
 "OPEN BRUSH" B 4.80 0.30 1.000 66
 AGRICULTURAL POOR COVER
 "ROW CROPS,STRAIGHT ROW" B 0.90 0.30 1.000 81
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 7.10 SUBAREA RUNOFF(CFS) = 6.95
 EFFECTIVE AREA(ACRES) = 4180.34 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83
 TOTAL AREA(ACRES) = 5555.5 PEAK FLOW RATE(CFS) = 4523.12
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 44.15
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.387
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 NATURAL POOR COVER
 "BARREN" B 7.80 0.30 1.000 86
 AGRICULTURAL POOR COVER
 "ROW CROPS,CONTOURED" B 1.70 0.30 1.000 79
 NATURAL POOR COVER
 "BARREN" B 9.40 0.30 1.000 86
 NATURAL FAIR COVER
 "OPEN BRUSH" B 1.20 0.30 1.000 66
 RESIDENTIAL
 ".4 DWELLING/ACRE" B 0.10 0.30 0.900 56

AGRICULTURAL POOR COVER

"ROW CROPS,CONTOURED" B 2.60 0.30 1.000 79
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 22.80 SUBAREA RUNOFF(CFS) = 22.31
 EFFECTIVE AREA(ACRES) = 4203.14 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
 TOTAL AREA(ACRES) = 5578.3 PEAK FLOW RATE(CFS) = 4523.12
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 44.15
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.387
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 0.20 0.30 1.000 65
 NATURAL FAIR COVER
 "OPEN BRUSH" B 0.30 0.30 1.000 66
 RESIDENTIAL
 ".4 DWELLING/ACRE" B 0.20 0.30 0.900 56
 AGRICULTURAL POOR COVER
 "ROW CROPS,CONTOURED" B 2.70 0.30 1.000 79
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.994
 SUBAREA AREA(ACRES) = 3.40 SUBAREA RUNOFF(CFS) = 3.33
 EFFECTIVE AREA(ACRES) = 4206.54 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
 TOTAL AREA(ACRES) = 5581.7 PEAK FLOW RATE(CFS) = 4523.12
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13304.00 TO NODE 13305.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 350.00 DOWNSTREAM(FEET) = 315.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2966.27 CHANNEL SLOPE = 0.0118
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 5.96
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.316
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 NATURAL POOR COVER
 "BARREN" B 1.70 0.30 1.000 86
 NATURAL FAIR COVER
 "GRASS" B 0.60 0.30 1.000 69
 NATURAL FAIR COVER
 "OPEN BRUSH" B 0.10 0.30 1.000 66
 NATURAL FAIR COVER

"WOODLAND,GRASS" B 0.40 0.30 1.000 65
 NATURAL POOR COVER
 "BARREN" B 2.20 0.30 1.000 86
 NATURAL FAIR COVER
 "GRASS" B 4.20 0.30 1.000 69
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 4527.33
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.19
 AVERAGE FLOW DEPTH(FEET) = 5.96 TRAVEL TIME(MIN.) = 4.42
 Tc(MIN.) = 48.57
 SUBAREA AREA(ACRES) = 9.20 SUBAREA RUNOFF(CFS) = 8.41
 EFFECTIVE AREA(ACRES) = 4215.74 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
 TOTAL AREA(ACRES) = 5590.9 PEAK FLOW RATE(CFS) = 4523.12
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 5.96

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 5.96 FLOW VELOCITY(FEET/SEC.) = 11.18
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3967.75	33.49	1.625	0.30(0.25)	0.85	2660.9	31100.00
2	4517.95	48.18	1.322	0.30(0.25)	0.84	4177.5	13210.00
3	4523.12	48.57	1.316	0.30(0.25)	0.84	4215.7	13200.00
4	4506.32	50.01	1.293	0.30(0.25)	0.83	4320.2	13100.00
5	4408.65	74.84	1.085	0.30(0.25)	0.83	5571.2	13000.00
6	4350.33	77.14	1.069	0.30(0.25)	0.83	5590.9	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 4523.12 Tc(MIN.) = 48.57
 AREA-AVERAGED Fm(INCH/HR) = 0.25 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.84 EFFECTIVE AREA(ACRES) = 4215.74

 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 48.57

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.316

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	8.10	0.30	1.000	66
NATURAL FAIR COVER "WOODLAND,GRASS"	B	2.30	0.30	1.000	65
NATURAL FAIR COVER "GRASS"	B	0.20	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	6.90	0.30	1.000	66
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.70	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 18.20 SUBAREA RUNOFF(CFS) = 16.64
 EFFECTIVE AREA(ACRES) = 4233.94 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
 TOTAL AREA(ACRES) = 5609.1 PEAK FLOW RATE(CFS) = 4523.12
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 48.57

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.316

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER "BARREN"	B	18.40	0.30	1.000	86
NATURAL FAIR COVER "MEADOWS"	B	1.20	0.30	1.000	70
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.10	0.30	1.000	65
NATURAL POOR COVER "BARREN"	B	26.60	0.30	1.000	86
COMMERCIAL "FALLOW"	B	3.90	0.30	0.100	56
AGRICULTURAL POOR COVER "FALLOW"	B	3.00	0.30	1.000	86
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.934 SUBAREA AREA(ACRES) = 53.20 SUBAREA RUNOFF(CFS) = 49.59 EFFECTIVE AREA(ACRES) = 4287.14 AREA-AVERAGED Fm(INCH/HR) = 0.25 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84 TOTAL AREA(ACRES) = 5662.3 PEAK FLOW RATE(CFS) = 4523.12 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE					

 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 48.57

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.316

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "ROW CROPS, CONTOURED"	B	1.10	0.30	1.000	79
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.20	0.30	1.000	65
NATURAL POOR COVER "BARREN"	B	14.00	0.30	1.000	86
COMMERCIAL "FALLOW"	B	4.30	0.30	0.100	56
AGRICULTURAL POOR COVER "FALLOW"	B	5.30	0.30	1.000	86
NATURAL FAIR COVER "GRASS"	B	2.70	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.860
 SUBAREA AREA(ACRES) = 27.60 SUBAREA RUNOFF(CFS) = 26.28
 EFFECTIVE AREA(ACRES) = 4314.74 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
 TOTAL AREA(ACRES) = 5689.9 PEAK FLOW RATE(CFS) = 4523.12
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 48.57
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.316
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "MEADOWS"	B	3.20	0.30	1.000	70
NATURAL FAIR COVER "OPEN BRUSH"	B	6.10	0.30	1.000	66
RESIDENTIAL ".4 DWELLING/ACRE"	B	7.50	0.30	0.900	56
AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	5.40	0.30	1.000	79
NATURAL FAIR COVER "WOODLAND,GRASS"	B	1.60	0.30	1.000	65
NATURAL POOR COVER "BARREN"	B	1.90	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.971
 SUBAREA AREA(ACRES) = 25.70 SUBAREA RUNOFF(CFS) = 23.70
 EFFECTIVE AREA(ACRES) = 4340.44 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
 TOTAL AREA(ACRES) = 5715.6 PEAK FLOW RATE(CFS) = 4523.12
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 48.57
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.316
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	2.00	0.30	0.100	56
AGRICULTURAL POOR COVER "FALLOW"	B	3.70	0.30	1.000	86
NATURAL FAIR COVER "OPEN BRUSH"	B	2.10	0.30	1.000	66
RESIDENTIAL ".4 DWELLING/ACRE"	B	2.60	0.30	0.900	56
AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	0.20	0.30	1.000	79
NATURAL FAIR COVER					

"WOODLAND,GRASS" B 0.10 0.30 1.000 65
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.807
 SUBAREA AREA(ACRES) = 10.70 SUBAREA RUNOFF(CFS) = 10.34
 EFFECTIVE AREA(ACRES) = 4351.14 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
 TOTAL AREA(ACRES) = 5726.3 PEAK FLOW RATE(CFS) = 4523.12
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 48.57
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.316
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	0.50	0.30	1.000	66
RESIDENTIAL ".4 DWELLING/ACRE"	B	8.20	0.30	0.900	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.906
 SUBAREA AREA(ACRES) = 8.70 SUBAREA RUNOFF(CFS) = 8.18
 EFFECTIVE AREA(ACRES) = 4359.84 AREA-AVERAGED Fm(INCH/HR) = 0.25
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84
 TOTAL AREA(ACRES) = 5735.0 PEAK FLOW RATE(CFS) = 4523.12
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<

PEAK FLOWRATE TABLE FILE NAME: 3A50EVRL.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1087.20	13.49	0.30(0.13)	0.43	436.1	120.00
2	1086.73	13.53	0.30(0.13)	0.43	436.7	110.00
3	930.63	20.54	0.30(0.13)	0.43	504.3	100.00
4	870.49	23.19	0.30(0.13)	0.43	510.2	150.00
TOTAL AREA(ACRES) =		510.2				

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3967.75	33.49	1.625	0.30(0.26)	0.85	2805.0	31100.00
2	4517.95	48.18	1.322	0.30(0.25)	0.84	4321.6	13210.00
3	4523.12	48.57	1.316	0.30(0.25)	0.84	4359.8	13200.00

4 4506.32 50.01 1.293 0.30(0.25) 0.84 4464.3 13100.00
 5 4408.65 74.84 1.085 0.30(0.25) 0.83 5715.3 13000.00
 6 4350.33 77.14 1.069 0.30(0.25) 0.83 5735.0 13010.00
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1087.20	13.49	2.876	0.30(0.13)	0.43	436.1	120.00
2	1086.73	13.53	2.870	0.30(0.13)	0.43	436.7	110.00
3	930.63	20.54	2.173	0.30(0.13)	0.43	504.3	100.00
4	870.49	23.19	2.016	0.30(0.13)	0.43	510.2	150.00

LONGEST FLOWPATH FROM NODE 150.00 TO NODE 13305.00 = 9867.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4145.50	13.49	2.876	0.30(0.22)	0.74	1566.3	120.00
2	4146.53	13.53	2.870	0.30(0.22)	0.74	1570.0	110.00
3	4337.87	20.54	2.173	0.30(0.23)	0.76	2225.1	100.00
4	4402.38	23.19	2.016	0.30(0.23)	0.77	2452.7	150.00
5	4657.85	33.49	1.625	0.30(0.24)	0.79	3315.2	31100.00
6	5068.23	48.18	1.322	0.30(0.24)	0.80	4831.8	13210.00
7	5070.47	48.57	1.316	0.30(0.24)	0.80	4870.0	13200.00
8	5042.98	50.01	1.293	0.30(0.24)	0.80	4974.5	13100.00
9	4849.18	74.84	1.085	0.30(0.24)	0.80	6225.5	13000.00
10	4783.69	77.14	1.069	0.30(0.24)	0.80	6245.2	13010.00

TOTAL AREA (ACRES) = 6245.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 5070.47 Tc (MIN.) = 48.572
 EFFECTIVE AREA (ACRES) = 4870.04 AREA-AVERAGED Fm (INCH/HR) = 0.24
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.76
 TOTAL AREA (ACRES) = 6245.2
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

 FLOW PROCESS FROM NODE 13305.00 TO NODE 13306.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 315.00 DOWNSTREAM (FEET) = 245.50
 CHANNEL LENGTH THRU SUBAREA (FEET) = 4408.41 CHANNEL SLOPE = 0.0158
 GIVEN CHANNEL BASE (FEET) = 50.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT (FEET) = 5.86
 * 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.246

SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 NATURAL POOR COVER

"BARREN"	B	0.40	0.30	1.000	86
NATURAL FAIR COVER					
"GRASS"	B	9.20	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.00	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	1.30	0.30	1.000	65
NATURAL POOR COVER					
"BARREN"	B	2.40	0.30	1.000	86
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	4.10	0.30	1.000	63

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 5078.30
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 12.81
 AVERAGE FLOW DEPTH (FEET) = 5.86 TRAVEL TIME (MIN.) = 5.73
 Tc (MIN.) = 54.31
 SUBAREA AREA (ACRES) = 18.40 SUBAREA RUNOFF (CFS) = 15.67
 EFFECTIVE AREA (ACRES) = 4888.44 AREA-AVERAGED Fm (INCH/HR) = 0.24
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA (ACRES) = 6263.6 PEAK FLOW RATE (CFS) = 5070.47
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE (FEET) = 50.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT (FEET) = 5.86

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 5.86 FLOW VELOCITY (FEET/SEC.) = 12.81
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13306.00 = 46294.95 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4145.50	19.59	2.240	0.30(0.22)	0.74	1584.7	120.00
2	4146.53	19.63	2.237	0.30(0.22)	0.74	1588.4	110.00
3	4337.87	26.56	1.849	0.30(0.23)	0.76	2243.5	100.00
4	4402.38	29.18	1.749	0.30(0.23)	0.77	2471.1	150.00
5	4657.85	39.37	1.471	0.30(0.24)	0.79	3333.6	31100.00
6	5068.23	53.91	1.251	0.30(0.24)	0.80	4850.2	13210.00
7	5070.47	54.31	1.246	0.30(0.24)	0.80	4888.4	13200.00
8	5042.98	55.76	1.231	0.30(0.24)	0.80	4992.9	13100.00
9	4849.18	80.65	1.045	0.30(0.24)	0.80	6243.9	13000.00
10	4783.69	82.98	1.030	0.30(0.24)	0.80	6263.6	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 5070.47 Tc (MIN.) = 54.31
 AREA-AVERAGED Fm (INCH/HR) = 0.24 AREA-AVERAGED Fp (INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.80 EFFECTIVE AREA (ACRES) = 4888.44

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 54.31
 * 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.246
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

NATURAL FAIR COVER
 "GRASS" B 19.20 0.30 1.000 69
 NATURAL FAIR COVER
 "OPEN BRUSH" B 20.90 0.30 1.000 66
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 4.10 0.30 1.000 65
 NATURAL FAIR COVER
 "CHAPARRAL,BROADLEAF" B 0.50 0.30 1.000 63
 NATURAL FAIR COVER
 "GRASS" B 4.30 0.30 1.000 69
 NATURAL FAIR COVER
 "OPEN BRUSH" B 0.60 0.30 1.000 66
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 49.60 SUBAREA RUNOFF(CFS) = 42.25
 EFFECTIVE AREA(ACRES) = 4938.04 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6313.2 PEAK FLOW RATE(CFS) = 5070.47
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 54.31
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.246
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 0.80 0.30 1.000 65
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 0.80 SUBAREA RUNOFF(CFS) = 0.68
 EFFECTIVE AREA(ACRES) = 4938.84 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6314.0 PEAK FLOW RATE(CFS) = 5070.47
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 54.31
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.246
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 PUBLIC PARK B 0.10 0.30 0.850 56
 NATURAL FAIR COVER
 "OPEN BRUSH" B 0.10 0.30 1.000 66
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 0.10 0.30 1.000 65
 NATURAL POOR COVER
 "BARREN" B 0.20 0.30 1.000 86
 PUBLIC PARK B 0.40 0.30 0.850 56

NATURAL FAIR COVER
 "GRASS" B 0.40 0.30 1.000 69
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.942
 SUBAREA AREA(ACRES) = 1.30 SUBAREA RUNOFF(CFS) = 1.13
 EFFECTIVE AREA(ACRES) = 4940.14 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6315.3 PEAK FLOW RATE(CFS) = 5070.47
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 54.31
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.246
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 RESIDENTIAL
 ".4 DWELLING/ACRE" B 0.80 0.30 0.900 56
 NATURAL FAIR COVER
 "GRASS" B 0.80 0.30 1.000 69
 NATURAL FAIR COVER
 "OPEN BRUSH" B 1.00 0.30 1.000 66
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 1.10 0.30 1.000 65
 COMMERCIAL B 1.10 0.30 0.100 56
 RESIDENTIAL
 ".4 DWELLING/ACRE" B 2.80 0.30 0.900 56
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.822
 SUBAREA AREA(ACRES) = 7.60 SUBAREA RUNOFF(CFS) = 6.84
 EFFECTIVE AREA(ACRES) = 4947.74 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6322.9 PEAK FLOW RATE(CFS) = 5070.47
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 54.31
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.246
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 COMMERCIAL B 3.50 0.30 0.100 56
 NATURAL FAIR COVER
 "GRASS" B 5.00 0.30 1.000 69
 RESIDENTIAL
 ".4 DWELLING/ACRE" B 6.70 0.30 0.900 56
 NATURAL FAIR COVER
 "WOODLAND,GRASS" B 7.80 0.30 1.000 65
 NATURAL FAIR COVER
 "OPEN BRUSH" B 10.80 0.30 1.000 66

COMMERCIAL B 13.80 0.30 0.100 56
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.659
 SUBAREA AREA(ACRES) = 47.60 SUBAREA RUNOFF(CFS) = 44.93
 EFFECTIVE AREA(ACRES) = 4995.34 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6370.5 PEAK FLOW RATE(CFS) = 5070.47
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 54.31
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.246
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER "BARREN"	B	21.54	0.30	1.000	86
NATURAL POOR COVER "BARREN"	B	36.64	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 58.18 SUBAREA RUNOFF(CFS) = 49.56
 EFFECTIVE AREA(ACRES) = 5053.52 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6428.7 PEAK FLOW RATE(CFS) = 5070.47
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13306.00 TO NODE 13307.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 245.50 DOWNSTREAM(FEET) = 220.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1543.21 CHANNEL SLOPE = 0.0165
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 5.79
 CHANNEL FLOW THRU SUBAREA(CFS) = 5070.47
 FLOW VELOCITY(FEET/SEC.) = 13.01 FLOW DEPTH(FEET) = 5.79
 TRAVEL TIME(MIN.) = 1.98 Tc(MIN.) = 56.28
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13307.00 = 47838.16 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4145.50	21.70	2.105	0.30(0.23)	0.75	1749.8	120.00
2	4146.53	21.73	2.102	0.30(0.23)	0.75	1753.5	110.00
3	4337.87	28.63	1.770	0.30(0.23)	0.77	2408.6	100.00
4	4402.38	31.24	1.684	0.30(0.23)	0.78	2636.2	150.00
5	4657.85	41.40	1.431	0.30(0.24)	0.79	3498.7	31100.00
6	5068.23	55.89	1.229	0.30(0.24)	0.80	5015.3	13210.00
7	5070.47	56.28	1.225	0.30(0.24)	0.80	5053.5	13200.00
8	5042.98	57.74	1.209	0.30(0.24)	0.80	5158.0	13100.00

9 4849.18 82.66 1.032 0.30(0.24) 0.80 6409.0 13000.00
 10 4783.69 84.99 1.016 0.30(0.24) 0.80 6428.7 13010.00
 NEW PEAK FLOW DATA ARE:
 PEAK FLOW RATE(CFS) = 5070.47 Tc(MIN.) = 56.28
 AREA-AVERAGED Fm(INCH/HR) = 0.24 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.80 EFFECTIVE AREA(ACRES) = 5053.52

 FLOW PROCESS FROM NODE 13307.00 TO NODE 13307.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 56.28
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.225
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	0.20	0.30	0.100	56
NATURAL FAIR COVER "GRASS"	B	0.10	0.30	1.000	69
AGRICULTURAL FAIR COVER "ORCHARDS"	B	0.20	0.30	1.000	65
NATURAL POOR COVER "BARREN"	B	3.70	0.30	1.000	86
COMMERCIAL	B	0.30	0.30	0.100	56
NATURAL FAIR COVER "GRASS"	B	3.20	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.942
 SUBAREA AREA(ACRES) = 7.70 SUBAREA RUNOFF(CFS) = 6.53
 EFFECTIVE AREA(ACRES) = 5061.22 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6436.4 PEAK FLOW RATE(CFS) = 5070.47
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13307.00 TO NODE 13307.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 56.28
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.225
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "WOODLAND,GRASS"	B	3.60	0.30	1.000	65
NATURAL FAIR COVER "GRASS"	B	1.90	0.30	1.000	69
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.60	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 6.10 SUBAREA RUNOFF(CFS) = 5.08
 EFFECTIVE AREA(ACRES) = 5067.32 AREA-AVERAGED Fm(INCH/HR) = 0.24
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
 TOTAL AREA(ACRES) = 6442.5 PEAK FLOW RATE(CFS) = 5070.47
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13307.00 TO NODE 13308.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 220.00 DOWNSTREAM(FEET) = 212.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 925.62 CHANNEL SLOPE = 0.0086
GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 6.91
CHANNEL FLOW THRU SUBAREA(CFS) = 5070.47
FLOW VELOCITY(FEET/SEC.) = 10.38 FLOW DEPTH(FEET) = 6.91
TRAVEL TIME(MIN.) = 1.49 Tc(MIN.) = 57.77
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13308.00 = 48763.78 FEET.

** PEAK FLOW RATE TABLE **

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 10 rows of data.

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 5070.47 Tc(MIN.) = 57.77
AREA-AVERAGED Fm(INCH/HR) = 0.24 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.80 EFFECTIVE AREA(ACRES) = 5067.32

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 57.77

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.209

SUBAREA LOSS RATE DATA(AMC II):

Table with 7 columns: DEVELOPMENT TYPE/LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Lists various land uses like GRASS, OPEN BRUSH, WOODLAND, etc.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.697

SUBAREA AREA(ACRES) = 9.50 SUBAREA RUNOFF(CFS) = 8.55
EFFECTIVE AREA(ACRES) = 5076.82 AREA-AVERAGED Fm(INCH/HR) = 0.24
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80
TOTAL AREA(ACRES) = 6452.0 PEAK FLOW RATE(CFS) = 5070.47
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 57.77

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.209

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Lists various land uses like BARREN, CHAPARRAL, COMMERCIAL, etc.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.498

SUBAREA AREA(ACRES) = 75.60 SUBAREA RUNOFF(CFS) = 72.10

EFFECTIVE AREA(ACRES) = 5152.42 AREA-AVERAGED Fm(INCH/HR) = 0.24

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80

TOTAL AREA(ACRES) = 6527.6 PEAK FLOW RATE(CFS) = 5070.47

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 57.77

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.209

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Lists various land uses like PUBLIC PARK, AGRICULTURAL POOR COVER, etc.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.966

SUBAREA AREA(ACRES) = 15.60 SUBAREA RUNOFF(CFS) = 12.91

EFFECTIVE AREA(ACRES) = 5168.02 AREA-AVERAGED Fm(INCH/HR) = 0.24

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80

TOTAL AREA (ACRES) = 6543.2 PEAK FLOW RATE (CFS) = 5070.47
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) = 57.77
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.209
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	33.90	0.30	0.100	56
NATURAL FAIR COVER "GRASS"	B	17.60	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	16.80	0.30	1.000	66
RESIDENTIAL "11+ DWELLINGS/ACRE"	B	0.60	0.30	0.200	56
RESIDENTIAL "8-10 DWELLINGS/ACRE"	B	1.50	0.30	0.400	56
AGRICULTURAL POOR COVER "ROW CROPS, CONTOURED"	B	10.00	0.30	1.000	79

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.603
SUBAREA AREA (ACRES) = 80.40 SUBAREA RUNOFF (CFS) = 74.39
EFFECTIVE AREA (ACRES) = 5248.42 AREA-AVERAGED Fm (INCH/HR) = 0.24
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79
TOTAL AREA (ACRES) = 6623.6 PEAK FLOW RATE (CFS) = 5070.47
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) = 57.77
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.209
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
SCHOOL	B	0.30	0.30	0.600	56
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.70	0.30	1.000	65

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.880
SUBAREA AREA (ACRES) = 1.00 SUBAREA RUNOFF (CFS) = 0.85
EFFECTIVE AREA (ACRES) = 5249.42 AREA-AVERAGED Fm (INCH/HR) = 0.24
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79
TOTAL AREA (ACRES) = 6624.6 PEAK FLOW RATE (CFS) = 5070.47
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 57.77
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.209
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "GRASS"	B	0.30	0.30	1.000	69
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.80	0.30	1.000	65
NATURAL FAIR COVER "GRASS"	B	0.50	0.30	1.000	69
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.20	0.30	1.000	65
NATURAL FAIR COVER "GRASS"	B	0.30	0.30	1.000	69

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 2.10 SUBAREA RUNOFF (CFS) = 1.72
EFFECTIVE AREA (ACRES) = 5251.52 AREA-AVERAGED Fm (INCH/HR) = 0.24
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79
TOTAL AREA (ACRES) = 6626.7 PEAK FLOW RATE (CFS) = 5070.47
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) = 57.77
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.209
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "GRASS"	B	1.20	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	0.50	0.30	1.000	66
PUBLIC PARK	B	1.70	0.30	0.850	56
NATURAL FAIR COVER "WOODLAND, GRASS"	B	7.20	0.30	1.000	65
NATURAL FAIR COVER "GRASS"	B	1.00	0.30	1.000	69

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.978
SUBAREA AREA (ACRES) = 11.60 SUBAREA RUNOFF (CFS) = 9.56
EFFECTIVE AREA (ACRES) = 5263.12 AREA-AVERAGED Fm (INCH/HR) = 0.24
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79
TOTAL AREA (ACRES) = 6638.3 PEAK FLOW RATE (CFS) = 5070.47
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 15.1

=====
>>>>DEFINE MEMORY BANK # 2 <<<<
=====

PEAK FLOWRATE TABLE FILE NAME: RU50EV29.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20867.65	16.63	0.30 (0.24)	0.79	3612.8	203.00
2	23326.83	24.10	0.30 (0.24)	0.80	5520.3	50330.00
3	26057.77	33.16	0.30 (0.25)	0.83	8563.1	50260.00
4	27460.74	38.76	0.30 (0.26)	0.86	10710.6	390.00
5	30419.85	54.85	0.30 (0.27)	0.91	16574.0	40100.00
6	31439.09	62.73	0.30 (0.28)	0.92	19401.9	11801.00
7	33333.59	73.55	0.30 (0.28)	0.93	23986.3	11530.00
8	34351.19	77.93	0.30 (0.28)	0.94	26300.8	11701.00
9	35221.64	81.42	0.30 (0.28)	0.94	28394.0	11910.00
10	37767.89	91.61	0.30 (0.29)	0.95	35088.2	10800.00
11	38423.27	95.85	0.30 (0.29)	0.96	38033.6	11130.00
12	38401.82	105.44	0.30 (0.29)	0.96	43074.8	12410.00
13	38081.80	113.71	0.30 (0.29)	0.96	46813.9	11201.00
14	37767.36	118.67	0.30 (0.29)	0.96	48545.6	12201.00
15	36867.46	125.69	0.30 (0.29)	0.96	50402.7	12231.00
16	35701.45	133.45	0.30 (0.29)	0.97	52037.0	10400.00
17	34493.10	141.34	0.30 (0.29)	0.97	53332.1	12010.00
18	33408.37	147.25	0.30 (0.29)	0.97	53679.1	10210.00
19	32936.43	150.28	0.30 (0.29)	0.97	53796.3	12000.00
20	29716.09	175.24	0.30 (0.29)	0.97	54417.5	10100.00

TOTAL AREA (ACRES) = 54417.5

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<
=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20867.65	16.63	0.30 (0.24)	0.79	3612.8	203.00
2	23326.83	24.10	0.30 (0.24)	0.80	5520.3	50330.00
3	26057.77	33.16	0.30 (0.25)	0.83	8563.1	50260.00
4	27460.74	38.76	0.30 (0.26)	0.86	10710.6	390.00
5	30419.85	54.85	0.30 (0.27)	0.91	16574.0	40100.00
6	31439.09	62.73	0.30 (0.28)	0.92	19401.9	11801.00
7	33333.59	73.55	0.30 (0.28)	0.93	23986.3	11530.00
8	34351.19	77.93	0.30 (0.28)	0.94	26300.8	11701.00
9	35221.64	81.42	0.30 (0.28)	0.94	28394.0	11910.00
10	37767.89	91.61	0.30 (0.29)	0.95	35088.2	10800.00
11	38423.27	95.85	0.30 (0.29)	0.96	38033.6	11130.00
12	38401.82	105.44	0.30 (0.29)	0.96	43074.8	12410.00
13	38081.80	113.71	0.30 (0.29)	0.96	46813.9	11201.00
14	37767.36	118.67	0.30 (0.29)	0.96	48545.6	12201.00
15	36867.46	125.69	0.30 (0.29)	0.96	50402.7	12231.00
16	35701.45	133.45	0.30 (0.29)	0.97	52037.0	10400.00
17	34493.10	141.34	0.30 (0.29)	0.97	53332.1	12010.00
18	33408.37	147.25	0.30 (0.29)	0.97	53679.1	10210.00
19	32936.43	150.28	0.30 (0.29)	0.97	53796.3	12000.00
20	29716.09	175.24	0.30 (0.29)	0.97	54417.5	10100.00

TOTAL AREA (ACRES) = 54417.5

FLOW PROCESS FROM NODE 12904.00 TO NODE 13308.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====

ELEVATION DATA: UPSTREAM (FEET) = 213.00 DOWNSTREAM (FEET) = 212.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 1389.52 CHANNEL SLOPE = 0.0007
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 17.73
CHANNEL FLOW THRU SUBAREA (CFS) = 38423.27
FLOW VELOCITY (FEET/SEC.) = 7.51 FLOW DEPTH (FEET) = 17.73
TRAVEL TIME (MIN.) = 3.08 Tc (MIN.) = 98.94
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118087.91 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20867.65	20.34	2.185	0.30 (0.24)	0.79	3612.8	203.00
2	23326.83	27.69	1.806	0.30 (0.24)	0.80	5520.3	50330.00
3	26057.77	36.63	1.543	0.30 (0.25)	0.83	8563.1	50260.00
4	27460.74	42.17	1.419	0.30 (0.26)	0.86	10710.6	390.00
5	30419.85	58.16	1.205	0.30 (0.27)	0.91	16574.0	40100.00
6	31439.09	66.00	1.144	0.30 (0.28)	0.92	19401.9	11801.00
7	33333.59	76.77	1.072	0.30 (0.28)	0.93	23986.3	11530.00
8	34351.19	81.12	1.042	0.30 (0.28)	0.94	26300.8	11701.00
9	35221.64	84.58	1.019	0.30 (0.28)	0.94	28394.0	11910.00
10	37767.89	94.71	0.962	0.30 (0.29)	0.95	35088.2	10800.00
11	38423.27	98.94	0.943	0.30 (0.29)	0.96	38033.6	11130.00
12	38401.82	108.53	0.902	0.30 (0.29)	0.96	43074.8	12410.00
13	38081.80	116.80	0.866	0.30 (0.29)	0.96	46813.9	11201.00
14	37767.36	121.77	0.848	0.30 (0.29)	0.96	48545.6	12201.00
15	36867.46	128.81	0.834	0.30 (0.29)	0.96	50402.7	12231.00
16	35701.45	136.60	0.818	0.30 (0.29)	0.97	52037.0	10400.00
17	34493.10	144.53	0.801	0.30 (0.29)	0.97	53332.1	12010.00
18	33408.37	150.47	0.789	0.30 (0.29)	0.97	53679.1	10210.00
19	32936.43	153.51	0.783	0.30 (0.29)	0.97	53796.3	12000.00
20	29716.09	178.57	0.731	0.30 (0.29)	0.97	54417.5	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 38423.27 Tc (MIN.) = 98.94
AREA-AVERAGED Fm (INCH/HR) = 0.29 AREA-AVERAGED Fp (INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.96 EFFECTIVE AREA (ACRES) = 38033.55

FLOW PROCESS FROM NODE 13307.00 TO NODE 13308.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<
=====

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20867.65	20.34	2.185	0.30 (0.24)	0.79	3612.8	203.00
2	23326.83	27.69	1.806	0.30 (0.24)	0.80	5520.3	50330.00
3	26057.77	36.63	1.543	0.30 (0.25)	0.83	8563.1	50260.00

4	27460.74	42.17	1.419	0.30 (0.26)	0.86	10710.6	390.00
5	30419.85	58.16	1.205	0.30 (0.27)	0.91	16574.0	40100.00
6	31439.09	66.00	1.144	0.30 (0.28)	0.92	19401.9	11801.00
7	33333.59	76.77	1.072	0.30 (0.28)	0.93	23986.3	11530.00
8	34351.19	81.12	1.042	0.30 (0.28)	0.94	26300.8	11701.00
9	35221.64	84.58	1.019	0.30 (0.28)	0.94	28394.0	11910.00
10	37767.89	94.71	0.962	0.30 (0.29)	0.95	35088.2	10800.00
11	38423.27	98.94	0.943	0.30 (0.29)	0.96	38033.6	11130.00
12	38401.82	108.53	0.902	0.30 (0.29)	0.96	43074.8	12410.00
13	38081.80	116.80	0.866	0.30 (0.29)	0.96	46813.9	11201.00
14	37767.36	121.77	0.848	0.30 (0.29)	0.96	48545.6	12201.00
15	36867.46	128.81	0.834	0.30 (0.29)	0.96	50402.7	12231.00
16	35701.45	136.60	0.818	0.30 (0.29)	0.97	52037.0	10400.00
17	34493.10	144.53	0.801	0.30 (0.29)	0.97	53332.1	12010.00
18	33408.37	150.47	0.789	0.30 (0.29)	0.97	53679.1	10210.00
19	32936.43	153.51	0.783	0.30 (0.29)	0.97	53796.3	12000.00
20	29716.09	178.57	0.731	0.30 (0.29)	0.97	54417.5	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118087.91 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4145.50	23.27	2.011	0.30 (0.22)	0.74	1959.4	120.00
2	4146.53	23.31	2.009	0.30 (0.22)	0.74	1963.1	110.00
3	4337.87	30.19	1.712	0.30 (0.23)	0.76	2618.2	100.00
4	4402.38	32.79	1.644	0.30 (0.23)	0.77	2845.8	150.00
5	4657.85	42.92	1.407	0.30 (0.24)	0.79	3708.3	31100.00
6	5068.23	57.37	1.213	0.30 (0.24)	0.79	5224.9	13210.00
7	5070.47	57.77	1.209	0.30 (0.24)	0.79	5263.1	13200.00
8	5042.98	59.23	1.193	0.30 (0.24)	0.79	5367.6	13100.00
9	4849.18	84.16	1.021	0.30 (0.24)	0.80	6618.6	13000.00
10	4783.69	86.50	1.006	0.30 (0.24)	0.80	6638.3	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13308.00 = 48763.78 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24842.48	20.34	2.185	0.30 (0.23)	0.78	5325.2	203.00
2	25994.84	23.27	2.011	0.30 (0.23)	0.78	6333.6	120.00
3	26008.03	23.31	2.009	0.30 (0.23)	0.78	6346.8	110.00
4	27595.18	27.69	1.806	0.30 (0.24)	0.79	7900.5	50330.00
5	28428.20	30.19	1.712	0.30 (0.24)	0.79	8989.2	100.00
6	29289.00	32.79	1.644	0.30 (0.24)	0.80	10104.0	150.00
7	30556.80	36.63	1.543	0.30 (0.24)	0.81	11735.2	50260.00
8	32099.61	42.17	1.419	0.30 (0.25)	0.84	14354.8	390.00
9	32257.91	42.92	1.407	0.30 (0.25)	0.84	14694.9	31100.00
10	35342.52	57.37	1.213	0.30 (0.26)	0.88	21510.5	13210.00
11	35418.27	57.77	1.209	0.30 (0.26)	0.88	21694.3	13200.00
12	35482.96	58.16	1.205	0.30 (0.26)	0.88	21865.0	40100.00
13	35601.34	59.23	1.193	0.30 (0.26)	0.88	22325.9	13100.00
14	36429.40	66.00	1.144	0.30 (0.27)	0.89	25109.5	11801.00
15	38240.24	76.77	1.072	0.30 (0.27)	0.91	30233.9	11530.00
16	39224.05	81.12	1.042	0.30 (0.27)	0.91	32766.6	11701.00
17	39965.51	84.16	1.021	0.30 (0.27)	0.92	34759.4	13000.00
18	40059.08	84.58	1.019	0.30 (0.27)	0.92	35016.2	11910.00
19	40487.61	86.50	1.006	0.30 (0.28)	0.92	36300.3	13010.00
20	42276.61	94.71	0.962	0.30 (0.28)	0.93	41726.5	10800.00
21	42817.75	98.94	0.943	0.30 (0.28)	0.93	44671.9	11130.00

22	42537.07	108.53	0.902	0.30 (0.28)	0.94	49713.1	12410.00
23	41993.36	116.80	0.866	0.30 (0.28)	0.94	53452.2	11201.00
24	41569.74	121.77	0.848	0.30 (0.28)	0.94	55183.9	12201.00
25	40579.04	128.81	0.834	0.30 (0.28)	0.94	57041.0	12231.00
26	39312.59	136.60	0.818	0.30 (0.28)	0.95	58675.3	10400.00
27	38002.11	144.53	0.801	0.30 (0.28)	0.95	59970.4	12010.00
28	36840.78	150.47	0.789	0.30 (0.28)	0.95	60317.4	10210.00
29	36329.62	153.51	0.783	0.30 (0.28)	0.95	60434.6	12000.00
30	32786.22	178.57	0.731	0.30 (0.28)	0.95	61055.8	10100.00

TOTAL AREA (ACRES) = 61055.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 42817.75 Tc (MIN.) = 98.935
EFFECTIVE AREA (ACRES) = 44671.87 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.88
TOTAL AREA (ACRES) = 61055.8
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118087.91 FEET.

=====
END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 61055.8 TC (MIN.) = 98.94
EFFECTIVE AREA (ACRES) = 44671.87 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.933
PEAK FLOW RATE (CFS) = 42817.75

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24842.48	20.34	2.185	0.30 (0.23)	0.78	5325.2	203.00
2	25994.84	23.27	2.011	0.30 (0.23)	0.78	6333.6	120.00
3	26008.03	23.31	2.009	0.30 (0.23)	0.78	6346.8	110.00
4	27595.18	27.69	1.806	0.30 (0.24)	0.79	7900.5	50330.00
5	28428.20	30.19	1.712	0.30 (0.24)	0.79	8989.2	100.00
6	29289.00	32.79	1.644	0.30 (0.24)	0.80	10104.0	150.00
7	30556.80	36.63	1.543	0.30 (0.24)	0.81	11735.2	50260.00
8	32099.61	42.17	1.419	0.30 (0.25)	0.84	14354.8	390.00
9	32257.91	42.92	1.407	0.30 (0.25)	0.84	14694.9	31100.00
10	35342.52	57.37	1.213	0.30 (0.26)	0.88	21510.5	13210.00
11	35418.27	57.77	1.209	0.30 (0.26)	0.88	21694.3	13200.00
12	35482.96	58.16	1.205	0.30 (0.26)	0.88	21865.0	40100.00
13	35601.34	59.23	1.193	0.30 (0.26)	0.88	22325.9	13100.00
14	36429.40	66.00	1.144	0.30 (0.27)	0.89	25109.5	11801.00
15	38240.24	76.77	1.072	0.30 (0.27)	0.91	30233.9	11530.00
16	39224.05	81.12	1.042	0.30 (0.27)	0.91	32766.6	11701.00
17	39965.51	84.16	1.021	0.30 (0.27)	0.92	34759.4	13000.00
18	40059.08	84.58	1.019	0.30 (0.27)	0.92	35016.2	11910.00
19	40487.61	86.50	1.006	0.30 (0.28)	0.92	36300.3	13010.00
20	42276.61	94.71	0.962	0.30 (0.28)	0.93	41726.5	10800.00
21	42817.75	98.94	0.943	0.30 (0.28)	0.93	44671.9	11130.00
22	42537.07	108.53	0.902	0.30 (0.28)	0.94	49713.1	12410.00
23	41993.36	116.80	0.866	0.30 (0.28)	0.94	53452.2	11201.00
24	41569.74	121.77	0.848	0.30 (0.28)	0.94	55183.9	12201.00
25	40579.04	128.81	0.834	0.30 (0.28)	0.94	57041.0	12231.00
26	39312.59	136.60	0.818	0.30 (0.28)	0.95	58675.3	10400.00
27	38002.11	144.53	0.801	0.30 (0.28)	0.95	59970.4	12010.00
28	36840.78	150.47	0.789	0.30 (0.28)	0.95	60317.4	10210.00
29	36329.62	153.51	0.783	0.30 (0.28)	0.95	60434.6	12000.00
30	32786.22	178.57	0.731	0.30 (0.28)	0.95	61055.8	10100.00

=====

=====
END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2010 Advanced Engineering Software (aes)
Ver. 17.0 Release Date: 07/01/2010 License ID 1527

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 134 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 50-YR EV AUG 2023 ROKAMOTO *

FILE NAME: RU50EV34.DAT
TIME/DATE OF STUDY: 22:19 08/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 50.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.304
- 2) 10.00; 3.420
- 3) 15.00; 2.629
- 4) 20.00; 2.200
- 5) 25.00; 1.906
- 6) 30.00; 1.714
- 7) 40.00; 1.452
- 8) 50.00; 1.290
- 9) 60.00; 1.181
- 10) 90.00; 0.979
- 11) 120.00; 0.849
- 12) 180.00; 0.725
- 13) 360.00; 0.534
- 14) 1200.00; 0.233

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL
HALF- CROWN TO STREET-CROSSFALL: CURB GUTTER-GEOMETRIES: MANNING
WIDTH CROSSFALL IN- / OUT-/PARK- HEIGHT WIDTH LIP HIKE FACTOR
NO. (FT) (FT) SIDE / SIDE/ WAY (FT) (FT) (FT) (FT) (n)
=====
1 30.0 20.0 0.018/0.018/0.020 0.67 2.00 0.0313 0.167 0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU50EV33.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	26008.03	23.31	0.30 (0.23)	0.78	6346.8	110.00
2	29289.00	32.79	0.30 (0.24)	0.80	10104.0	150.00
3	30556.80	36.63	0.30 (0.24)	0.81	11735.2	50260.00
4	32257.91	42.92	0.30 (0.25)	0.84	14694.9	31100.00
5	35601.34	59.23	0.30 (0.26)	0.88	22325.9	13100.00
6	36429.40	66.00	0.30 (0.27)	0.89	25109.5	11801.00
7	38240.24	76.77	0.30 (0.27)	0.91	30233.9	11530.00
8	39224.05	81.12	0.30 (0.27)	0.91	32766.6	11701.00
9	40487.61	86.50	0.30 (0.28)	0.92	36300.3	13010.00
10	42276.61	94.71	0.30 (0.28)	0.93	41726.5	10800.00
11	42817.75	98.94	0.30 (0.28)	0.93	44671.9	11130.00
12	42537.07	108.53	0.30 (0.28)	0.94	49713.1	12410.00
13	41993.36	116.80	0.30 (0.28)	0.94	53452.2	11201.00
14	41569.74	121.77	0.30 (0.28)	0.94	55183.9	12201.00
15	40579.04	128.81	0.30 (0.28)	0.94	57041.0	12231.00
16	39312.59	136.60	0.30 (0.28)	0.95	58675.3	10400.00
17	38002.11	144.53	0.30 (0.28)	0.95	59970.4	12010.00
18	36840.78	150.47	0.30 (0.28)	0.95	60317.4	10210.00
19	36329.62	153.51	0.30 (0.28)	0.95	60434.6	12000.00
20	32786.22	178.57	0.30 (0.28)	0.95	61055.8	10100.00
TOTAL AREA (ACRES) =						61055.8

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	26008.03	23.31	0.30 (0.23)	0.78	6346.8	110.00
2	29289.00	32.79	0.30 (0.24)	0.80	10104.0	150.00
3	30556.80	36.63	0.30 (0.24)	0.81	11735.2	50260.00
4	32257.91	42.92	0.30 (0.25)	0.84	14694.9	31100.00
5	35601.34	59.23	0.30 (0.26)	0.88	22325.9	13100.00
6	36429.40	66.00	0.30 (0.27)	0.89	25109.5	11801.00
7	38240.24	76.77	0.30 (0.27)	0.91	30233.9	11530.00
8	39224.05	81.12	0.30 (0.27)	0.91	32766.6	11701.00
9	40487.61	86.50	0.30 (0.28)	0.92	36300.3	13010.00
10	42276.61	94.71	0.30 (0.28)	0.93	41726.5	10800.00
11	42817.75	98.94	0.30 (0.28)	0.93	44671.9	11130.00
12	42537.07	108.53	0.30 (0.28)	0.94	49713.1	12410.00
13	41993.36	116.80	0.30 (0.28)	0.94	53452.2	11201.00

14	41569.74	121.77	0.30	(0.28)	0.94	55183.9	12201.00
15	40579.04	128.81	0.30	(0.28)	0.94	57041.0	12231.00
16	39312.59	136.60	0.30	(0.28)	0.95	58675.3	10400.00
17	38002.11	144.53	0.30	(0.28)	0.95	59970.4	12010.00
18	36840.78	150.47	0.30	(0.28)	0.95	60317.4	10210.00
19	36329.62	153.51	0.30	(0.28)	0.95	60434.6	12000.00
20	32786.22	178.57	0.30	(0.28)	0.95	61055.8	10100.00

TOTAL AREA (ACRES) = 61055.8

FLOW PROCESS FROM NODE 13308.00 TO NODE 13402.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 212.00 DOWNSTREAM(FEET) = 209.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 623.02 CHANNEL SLOPE = 0.0048
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 11.17
CHANNEL FLOW THRU SUBAREA(CFS) = 42817.75
FLOW VELOCITY(FEET/SEC.) = 14.99 FLOW DEPTH(FEET) = 11.17
TRAVEL TIME(MIN.) = 0.69 Tc(MIN.) = 99.63
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118710.93 FEET.

FLOW PROCESS FROM NODE 13402.00 TO NODE 13402.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: P505XX50.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	255.49	17.27	0.30 (0.29)	0.96	146.4	50500.00

TOTAL AREA (ACRES) = 146.4

FLOW PROCESS FROM NODE 13402.00 TO NODE 13402.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	26008.03	24.13	1.957	0.30 (0.23)	0.78	6346.8	110.00
2	29289.00	33.58	1.620	0.30 (0.24)	0.80	10104.0	150.00
3	30556.80	37.40	1.520	0.30 (0.24)	0.81	11735.2	50260.00
4	32257.91	43.68	1.392	0.30 (0.25)	0.84	14694.9	31100.00
5	35601.34	59.96	1.181	0.30 (0.26)	0.88	22325.9	13100.00
6	36429.40	66.73	1.136	0.30 (0.27)	0.89	25109.5	11801.00
7	38240.24	77.49	1.063	0.30 (0.27)	0.91	30233.9	11530.00
8	39224.05	81.83	1.034	0.30 (0.27)	0.91	32766.6	11701.00
9	40487.61	87.21	0.998	0.30 (0.28)	0.92	36300.3	13010.00
10	42276.61	95.40	0.956	0.30 (0.28)	0.93	41726.5	10800.00
11	42817.75	99.63	0.937	0.30 (0.28)	0.93	44671.9	11130.00
12	42537.07	109.22	0.896	0.30 (0.28)	0.94	49713.1	12410.00

13	41993.36	117.50	0.860	0.30 (0.28)	0.94	53452.2	11201.00
14	41569.74	122.47	0.844	0.30 (0.28)	0.94	55183.9	12201.00
15	40579.04	129.52	0.829	0.30 (0.28)	0.94	57041.0	12231.00
16	39312.59	137.31	0.813	0.30 (0.28)	0.95	58675.3	10400.00
17	38002.11	145.25	0.797	0.30 (0.28)	0.95	59970.4	12010.00
18	36840.78	151.20	0.785	0.30 (0.28)	0.95	60317.4	10210.00
19	36329.62	154.24	0.778	0.30 (0.28)	0.95	60434.6	12000.00
20	32786.22	179.33	0.726	0.30 (0.28)	0.95	61055.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118710.93 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	255.49	17.27	2.434	0.30 (0.29)	0.96	146.4	50500.00

LONGEST FLOWPATH FROM NODE 50500.00 TO NODE 13402.00 = 5416.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24023.14	17.27	2.434	0.30 (0.24)	0.79	4689.5	50500.00
2	26206.77	24.13	1.957	0.30 (0.24)	0.78	6493.2	110.00
3	29447.62	33.58	1.620	0.30 (0.24)	0.80	10250.4	150.00
4	30703.50	37.40	1.520	0.30 (0.24)	0.82	11881.6	50260.00
5	32389.40	43.68	1.392	0.30 (0.25)	0.85	14841.3	31100.00
6	35707.73	59.96	1.181	0.30 (0.26)	0.88	22472.3	13100.00
7	36530.34	66.73	1.136	0.30 (0.27)	0.89	25255.9	11801.00
8	38332.56	77.49	1.063	0.30 (0.27)	0.91	30380.3	11530.00
9	39312.89	81.83	1.034	0.30 (0.27)	0.91	32913.0	11701.00
10	40572.14	87.21	0.998	0.30 (0.28)	0.92	36446.7	13010.00
11	42356.11	95.40	0.956	0.30 (0.28)	0.93	41872.9	10800.00
12	42895.08	99.63	0.937	0.30 (0.28)	0.93	44818.3	11130.00
13	42609.45	109.22	0.896	0.30 (0.28)	0.94	49859.5	12410.00
14	42061.47	117.50	0.860	0.30 (0.28)	0.94	53598.6	11201.00
15	41635.96	122.47	0.844	0.30 (0.28)	0.94	55330.3	12201.00
16	40643.52	129.52	0.829	0.30 (0.28)	0.94	57187.4	12231.00
17	39375.16	137.31	0.813	0.30 (0.28)	0.95	58821.7	10400.00
18	38062.73	145.25	0.797	0.30 (0.28)	0.95	60116.8	12010.00
19	36899.93	151.20	0.785	0.30 (0.28)	0.95	60463.8	10210.00
20	36388.02	154.24	0.778	0.30 (0.28)	0.95	60581.0	12000.00
21	32838.45	179.33	0.726	0.30 (0.28)	0.95	61202.2	10100.00

TOTAL AREA (ACRES) = 61202.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 42895.08 Tc (MIN.) = 99.628
EFFECTIVE AREA (ACRES) = 44818.27 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA (ACRES) = 61202.2
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118710.93 FEET.

FLOW PROCESS FROM NODE 13402.00 TO NODE 13404.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 209.00 DOWNSTREAM(FEET) = 207.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 395.35 CHANNEL SLOPE = 0.0051
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 11.03
 CHANNEL FLOW THRU SUBAREA(CFS) = 42895.08
 FLOW VELOCITY(FEET/SEC.) = 15.25 FLOW DEPTH(FEET) = 11.03
 TRAVEL TIME(MIN.) = 0.43 Tc(MIN.) = 100.06
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119106.28 FEET.

 FLOW PROCESS FROM NODE 13404.00 TO NODE 13404.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: P506XX50.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	83.84	18.04	0.30	(0.29)	0.97	49.5	50600.00
TOTAL AREA (ACRES) =							49.5

 FLOW PROCESS FROM NODE 13404.00 TO NODE 13404.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

 ** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24023.14	17.79	2.389	0.30 (0.24)	0.79	4689.5	50500.00
2	26206.77	24.63	1.928	0.30 (0.24)	0.78	6493.2	110.00
3	29447.62	34.06	1.607	0.30 (0.24)	0.80	10250.4	150.00
4	30703.50	37.88	1.508	0.30 (0.24)	0.82	11881.6	50260.00
5	32389.40	44.16	1.385	0.30 (0.25)	0.85	14841.3	31100.00
6	35707.73	60.42	1.178	0.30 (0.26)	0.88	22472.3	13100.00
7	36530.34	67.19	1.133	0.30 (0.27)	0.89	25255.9	11801.00
8	38332.56	77.93	1.060	0.30 (0.27)	0.91	30380.3	11530.00
9	39312.89	82.27	1.031	0.30 (0.27)	0.91	32913.0	11701.00
10	40572.14	87.65	0.995	0.30 (0.28)	0.92	36446.7	13010.00
11	42356.11	95.84	0.954	0.30 (0.28)	0.93	41872.9	10800.00
12	42895.08	100.06	0.935	0.30 (0.28)	0.93	44818.3	11130.00
13	42609.45	109.65	0.894	0.30 (0.28)	0.94	49859.5	12410.00
14	42061.47	117.93	0.858	0.30 (0.28)	0.94	53598.6	11201.00
15	41635.96	122.90	0.843	0.30 (0.28)	0.94	55330.3	12201.00
16	40643.52	129.96	0.828	0.30 (0.28)	0.94	57187.4	12231.00
17	39375.16	137.76	0.812	0.30 (0.28)	0.95	58821.7	10400.00
18	38062.73	145.69	0.796	0.30 (0.28)	0.95	60116.8	12010.00
19	36899.93	151.65	0.784	0.30 (0.28)	0.95	60463.8	10210.00
20	36388.02	154.70	0.777	0.30 (0.28)	0.95	60581.0	12000.00
21	32838.45	179.80	0.725	0.30 (0.28)	0.95	61202.2	10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 =							119106.28 FEET.

 ** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	83.84	18.04	2.369	0.30 (0.29)	0.97	49.5	50600.00
LONGEST FLOWPATH FROM NODE 50600.00 TO NODE 13404.00 =							4378.00 FEET.

 ** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24106.67	17.79	2.389	0.30 (0.24)	0.79	4738.4	50500.00
2	24184.81	18.04	2.369	0.30 (0.24)	0.79	4803.3	50600.00
3	26272.82	24.63	1.928	0.30 (0.24)	0.78	6542.7	110.00
4	29500.76	34.06	1.607	0.30 (0.24)	0.80	10299.9	150.00
5	30752.62	37.88	1.508	0.30 (0.24)	0.82	11931.1	50260.00
6	32433.56	44.16	1.385	0.30 (0.25)	0.85	14890.8	31100.00
7	35743.57	60.42	1.178	0.30 (0.26)	0.88	22521.8	13100.00
8	36564.34	67.19	1.133	0.30 (0.27)	0.89	25305.4	11801.00
9	38363.64	77.93	1.060	0.30 (0.27)	0.91	30429.8	11530.00
10	39342.79	82.27	1.031	0.30 (0.27)	0.91	32962.5	11701.00
11	40600.58	87.65	0.995	0.30 (0.28)	0.92	36496.2	13010.00
12	42382.89	95.84	0.954	0.30 (0.28)	0.93	41922.4	10800.00
13	42921.12	100.06	0.935	0.30 (0.28)	0.93	44867.8	11130.00
14	42633.82	109.65	0.894	0.30 (0.28)	0.94	49909.0	12410.00
15	42084.39	117.93	0.858	0.30 (0.28)	0.94	53648.1	11201.00
16	41658.27	122.90	0.843	0.30 (0.28)	0.94	55379.8	12201.00
17	40665.25	129.96	0.828	0.30 (0.28)	0.94	57236.9	12231.00
18	39396.24	137.76	0.812	0.30 (0.28)	0.95	58871.2	10400.00
19	38083.14	145.69	0.796	0.30 (0.28)	0.95	60166.3	12010.00
20	36919.85	151.65	0.784	0.30 (0.28)	0.95	60513.3	10210.00
21	36407.69	154.70	0.777	0.30 (0.28)	0.95	60630.5	12000.00
22	32856.03	179.80	0.725	0.30 (0.28)	0.95	61251.7	10100.00
TOTAL AREA (ACRES) =						61251.7	

 COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 42921.12 Tc(MIN.) = 100.060
 EFFECTIVE AREA(ACRES) = 44867.77 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 61251.7
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119106.28 FEET.

 FLOW PROCESS FROM NODE 13404.00 TO NODE 13406.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 207.00 DOWNSTREAM(FEET) = 195.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1601.97 CHANNEL SLOPE = 0.0075
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 9.88
 CHANNEL FLOW THRU SUBAREA(CFS) = 42921.12
 FLOW VELOCITY(FEET/SEC.) = 17.42 FLOW DEPTH(FEET) = 9.88
 TRAVEL TIME(MIN.) = 1.53 Tc(MIN.) = 101.59
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13406.00 = 120708.25 FEET.

 FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 101.59
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.929
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/	SCS SOIL	AREA	Fp	Ap	SCS
-------------------	----------	------	----	----	-----

LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

NATURAL FAIR COVER
 "GRASS" B 0.20 0.30 1.000 69
 NATURAL FAIR COVER
 "GRASS" B 4.00 0.30 1.000 69
 NATURAL FAIR COVER
 "GRASS" B 2.00 0.30 1.000 69
 NATURAL FAIR COVER
 "OPEN BRUSH" B 9.70 0.30 1.000 66
 NATURAL FAIR COVER
 "OPEN BRUSH" B 2.60 0.30 1.000 66
 AGRICULTURAL POOR COVER
 "ROW CROPS, STRAIGHT ROW" B 1.60 0.30 1.000 81
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 20.10 SUBAREA RUNOFF (CFS) = 11.37
 EFFECTIVE AREA (ACRES) = 44887.87 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA (ACRES) = 61271.8 PEAK FLOW RATE (CFS) = 42921.12
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 101.59

* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.929

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "ROW CROPS, STRAIGHT ROW"	B	2.00	0.30	1.000	81
NATURAL FAIR COVER "WOODLAND, GRASS"	B	7.10	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND, GRASS"	B	5.80	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.10	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 15.00 SUBAREA RUNOFF (CFS) = 8.49

EFFECTIVE AREA (ACRES) = 44902.87 AREA-AVERAGED Fm (INCH/HR) = 0.28

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA (ACRES) = 61286.8 PEAK FLOW RATE (CFS) = 42921.12

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13406.00 TO NODE 13408.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 195.00 DOWNSTREAM (FEET) = 182.00

CHANNEL LENGTH THRU SUBAREA (FEET) = 2458.36 CHANNEL SLOPE = 0.0053

GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT (FEET) = 10.89

* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.917

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	7.00	0.30	1.000	66
NATURAL FAIR COVER "WOODLAND, GRASS"	B	3.30	0.30	1.000	65
COMMERCIAL	B	0.40	0.30	0.100	56
NATURAL FAIR COVER "OPEN BRUSH"	B	1.40	0.30	1.000	66
COMMERCIAL	B	0.30	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.949

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 42924.66

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 15.49

AVERAGE FLOW DEPTH (FEET) = 10.89 TRAVEL TIME (MIN.) = 2.65

Tc (MIN.) = 104.24

SUBAREA AREA (ACRES) = 12.40 SUBAREA RUNOFF (CFS) = 7.06

EFFECTIVE AREA (ACRES) = 44915.27 AREA-AVERAGED Fm (INCH/HR) = 0.28

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA (ACRES) = 61299.2 PEAK FLOW RATE (CFS) = 42921.12

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT (FEET) = 10.89

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 10.89 FLOW VELOCITY (FEET/SEC.) = 15.49

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123166.61 FEET.

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 2P50EVBB.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	748.33	9.86	0.30 (0.11)	0.38	244.2	429.00
2	793.01	11.37	0.30 (0.11)	0.38	281.3	425.00
3	804.73	11.79	0.30 (0.11)	0.38	291.7	400.00
4	836.36	13.23	0.30 (0.11)	0.38	327.6	300.00
5	892.30	18.33	0.30 (0.11)	0.38	440.3	210.00
6	879.40	20.37	0.30 (0.11)	0.38	466.7	410.00
7	872.79	21.37	0.30 (0.11)	0.38	479.4	200.00
8	870.12	21.98	0.30 (0.11)	0.38	486.6	230.00
9	849.67	23.09	0.30 (0.11)	0.37	491.2	220.50
TOTAL AREA (ACRES) =			491.2			

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24106.67	22.84	2.033	0.30 (0.24)	0.79	4785.9	50500.00
2	24184.81	23.08	2.019	0.30 (0.24)	0.79	4850.8	50600.00
3	26272.82	29.54	1.732	0.30 (0.24)	0.79	6590.2	110.00
4	29500.76	38.79	1.484	0.30 (0.24)	0.81	10347.4	150.00
5	30752.62	42.54	1.411	0.30 (0.24)	0.82	11978.6	50260.00
6	32433.56	48.73	1.311	0.30 (0.25)	0.85	14938.3	31100.00
7	35743.57	64.85	1.148	0.30 (0.26)	0.88	22569.3	13100.00
8	36564.34	71.59	1.103	0.30 (0.27)	0.89	25352.9	11801.00
9	38363.64	82.27	1.031	0.30 (0.27)	0.91	30477.3	11530.00
10	39342.79	86.57	1.002	0.30 (0.27)	0.91	33010.0	11701.00
11	40600.58	91.90	0.971	0.30 (0.28)	0.92	36543.7	13010.00
12	42382.89	100.03	0.936	0.30 (0.28)	0.93	41969.9	10800.00
13	42921.12	104.24	0.917	0.30 (0.28)	0.93	44915.3	11130.00
14	42633.82	113.84	0.876	0.30 (0.28)	0.94	49956.5	12410.00
15	42084.39	122.14	0.845	0.30 (0.28)	0.94	53695.6	11201.00
16	41658.27	127.12	0.834	0.30 (0.28)	0.94	55427.3	12201.00
17	40665.25	134.21	0.820	0.30 (0.28)	0.94	57284.4	12231.00
18	39396.24	142.05	0.803	0.30 (0.28)	0.95	58918.7	10400.00
19	38083.14	150.04	0.787	0.30 (0.28)	0.95	60213.8	12010.00
20	36919.85	156.04	0.775	0.30 (0.28)	0.95	60560.8	10210.00
21	36407.69	159.10	0.768	0.30 (0.28)	0.95	60678.0	12000.00
22	32856.03	184.36	0.720	0.30 (0.28)	0.95	61299.2	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123166.61 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	748.33	9.86	3.472	0.30 (0.11)	0.38	244.2	429.00
2	793.01	11.37	3.204	0.30 (0.11)	0.38	281.3	425.00
3	804.73	11.79	3.137	0.30 (0.11)	0.38	291.7	400.00
4	836.36	13.23	2.909	0.30 (0.11)	0.38	327.6	300.00
5	892.30	18.33	2.343	0.30 (0.11)	0.38	440.3	210.00
6	879.40	20.37	2.178	0.30 (0.11)	0.38	466.7	410.00
7	872.79	21.37	2.119	0.30 (0.11)	0.38	479.4	200.00
8	870.12	21.98	2.083	0.30 (0.11)	0.38	486.6	230.00
9	849.67	23.09	2.018	0.30 (0.11)	0.37	491.2	220.50

LONGEST FLOWPATH FROM NODE 230.00 TO NODE 13408.00 = 11903.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19494.65	9.86	3.472	0.30 (0.22)	0.75	2310.1	429.00
2	20609.17	11.37	3.204	0.30 (0.22)	0.75	2662.9	425.00
3	20892.76	11.79	3.137	0.30 (0.22)	0.75	2761.3	400.00
4	21609.22	13.23	2.909	0.30 (0.22)	0.75	3099.7	300.00
5	23579.97	18.33	2.343	0.30 (0.22)	0.75	4280.8	210.00
6	24117.01	20.37	2.178	0.30 (0.22)	0.75	4734.6	410.00
7	24512.17	21.37	2.119	0.30 (0.22)	0.75	4956.5	200.00
8	24722.32	21.98	2.083	0.30 (0.22)	0.75	5092.3	230.00
9	24960.86	22.84	2.033	0.30 (0.23)	0.75	5276.0	50500.00

10	25034.56	23.08	2.019	0.30 (0.23)	0.75	5342.0	50600.00
11	25035.89	23.09	2.018	0.30 (0.23)	0.75	5343.2	220.50
12	26994.62	29.54	1.732	0.30 (0.23)	0.76	7081.4	110.00
13	30112.09	38.79	1.484	0.30 (0.24)	0.79	10838.6	150.00
14	31331.44	42.54	1.411	0.30 (0.24)	0.80	12469.8	50260.00
15	32967.65	48.73	1.311	0.30 (0.25)	0.83	15429.5	31100.00
16	36205.36	64.85	1.148	0.30 (0.26)	0.87	23060.5	13100.00
17	37005.91	71.59	1.103	0.30 (0.26)	0.88	25844.1	11801.00
18	38773.16	82.27	1.031	0.30 (0.27)	0.90	30968.5	11530.00
19	39739.39	86.57	1.002	0.30 (0.27)	0.90	33501.2	11701.00
20	40983.21	91.90	0.971	0.30 (0.27)	0.91	37034.9	13010.00
21	42749.82	100.03	0.936	0.30 (0.28)	0.92	42461.1	10800.00
22	43279.93	104.24	0.917	0.30 (0.28)	0.93	45406.5	11130.00
23	42974.06	113.84	0.876	0.30 (0.28)	0.93	50447.7	12410.00
24	42410.77	122.14	0.845	0.30 (0.28)	0.94	54186.8	11201.00
25	41980.06	127.12	0.834	0.30 (0.28)	0.94	55918.5	12201.00
26	40980.51	134.21	0.820	0.30 (0.28)	0.94	57775.6	12231.00
27	39704.27	142.05	0.803	0.30 (0.28)	0.94	59409.9	10400.00
28	38383.82	150.04	0.787	0.30 (0.28)	0.94	60705.0	12010.00
29	37215.00	156.04	0.775	0.30 (0.28)	0.94	61052.0	10210.00
30	36700.02	159.10	0.768	0.30 (0.28)	0.94	61169.2	12000.00
31	33127.04	184.36	0.720	0.30 (0.28)	0.94	61790.4	10100.00

TOTAL AREA (ACRES) = 61790.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 43279.93 Tc (MIN.) = 104.238
EFFECTIVE AREA (ACRES) = 45406.46 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79
TOTAL AREA (ACRES) = 61790.4
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123166.61 FEET.

***** FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 12 *****

>>>>CLEAR MEMORY BANK # 2 <<<<<

***** FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 15.1 *****

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P507XX50.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	337.32	22.37	0.30 (0.30)	0.99	231.4	50700.00	

TOTAL AREA (ACRES) = 231.4

***** FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 11 *****

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
---------------	---------	-----------	---------------------	------------------	----	------------	----------------

1	19494.65	9.86	3.472	0.30	(0.22)	0.75	2310.1	429.00
2	20609.17	11.37	3.204	0.30	(0.22)	0.75	2662.9	425.00
3	20892.76	11.79	3.137	0.30	(0.22)	0.75	2761.3	400.00
4	21609.22	13.23	2.909	0.30	(0.22)	0.75	3099.7	300.00
5	23579.97	18.33	2.343	0.30	(0.22)	0.75	4280.8	210.00
6	24117.01	20.37	2.178	0.30	(0.22)	0.75	4734.6	410.00
7	24512.17	21.37	2.119	0.30	(0.22)	0.75	4956.5	200.00
8	24722.32	21.98	2.083	0.30	(0.22)	0.75	5092.3	230.00
9	24960.86	22.84	2.033	0.30	(0.23)	0.75	5276.0	50500.00
10	25034.56	23.08	2.019	0.30	(0.23)	0.75	5342.0	50600.00
11	25035.89	23.09	2.018	0.30	(0.23)	0.75	5343.2	220.50
12	26994.62	29.54	1.732	0.30	(0.23)	0.76	7081.4	110.00
13	30112.09	38.79	1.484	0.30	(0.24)	0.79	10838.6	150.00
14	31331.44	42.54	1.411	0.30	(0.24)	0.80	12469.8	50260.00
15	32967.65	48.73	1.311	0.30	(0.25)	0.83	15429.5	31100.00
16	36205.36	64.85	1.148	0.30	(0.26)	0.87	23060.5	13100.00
17	37005.91	71.59	1.103	0.30	(0.26)	0.88	25844.1	11801.00
18	38773.16	82.27	1.031	0.30	(0.27)	0.90	30968.5	11530.00
19	39739.39	86.57	1.002	0.30	(0.27)	0.90	33501.2	11701.00
20	40983.21	91.90	0.971	0.30	(0.27)	0.91	37034.9	13010.00
21	42749.82	100.03	0.936	0.30	(0.28)	0.92	42461.1	10800.00
22	43279.93	104.24	0.917	0.30	(0.28)	0.93	45406.5	11130.00
23	42974.06	113.84	0.876	0.30	(0.28)	0.93	50447.7	12410.00
24	42410.77	122.14	0.845	0.30	(0.28)	0.94	54186.8	11201.00
25	41980.06	127.12	0.834	0.30	(0.28)	0.94	55918.5	12201.00
26	40980.51	134.21	0.820	0.30	(0.28)	0.94	57775.6	12231.00
27	39704.27	142.05	0.803	0.30	(0.28)	0.94	59409.9	10400.00
28	38383.82	150.04	0.787	0.30	(0.28)	0.94	60705.0	12010.00
29	37215.00	156.04	0.775	0.30	(0.28)	0.94	61052.0	10210.00
30	36700.02	159.10	0.768	0.30	(0.28)	0.94	61169.2	12000.00
31	33127.04	184.36	0.720	0.30	(0.28)	0.94	61790.4	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123166.61 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	337.32	22.37	2.061	0.30 (0.30)	0.99	231.4	50700.00

LONGEST FLOWPATH FROM NODE 50700.00 TO NODE 13408.00 = 7683.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19762.32	9.86	3.472	0.30 (0.23)	0.76	2412.1	429.00
2	20891.63	11.37	3.204	0.30 (0.23)	0.76	2780.5	425.00
3	21178.96	11.79	3.137	0.30 (0.23)	0.76	2883.2	400.00
4	21904.65	13.23	2.909	0.30 (0.23)	0.76	3236.5	300.00
5	23900.65	18.33	2.343	0.30 (0.23)	0.76	4470.5	210.00
6	24444.65	20.37	2.178	0.30 (0.23)	0.76	4945.3	410.00
7	24845.14	21.37	2.119	0.30 (0.23)	0.76	5177.5	200.00
8	25058.07	21.98	2.083	0.30 (0.23)	0.76	5319.6	230.00
9	25167.38	22.37	2.061	0.30 (0.23)	0.76	5406.7	50700.00
10	25292.87	22.84	2.033	0.30 (0.23)	0.76	5507.4	50500.00
11	25363.89	23.08	2.019	0.30 (0.23)	0.76	5573.4	50600.00
12	25365.16	23.09	2.018	0.30 (0.23)	0.76	5574.6	220.50
13	27269.04	29.54	1.732	0.30 (0.23)	0.77	7312.8	110.00
14	30339.13	38.79	1.484	0.30 (0.24)	0.79	11070.0	150.00
15	31544.54	42.54	1.411	0.30 (0.24)	0.80	12701.2	50260.00
16	33161.56	48.73	1.311	0.30 (0.25)	0.83	15660.9	31100.00

17	36368.25	64.85	1.148	0.30	(0.26)	0.87	23291.9	13100.00
18	37160.13	71.59	1.103	0.30	(0.27)	0.88	26075.5	11801.00
19	38913.63	82.27	1.031	0.30	(0.27)	0.90	31199.9	11530.00
20	39874.32	86.57	1.002	0.30	(0.27)	0.90	33732.6	11701.00
21	41112.16	91.90	0.971	0.30	(0.27)	0.91	37266.3	13010.00
22	42872.02	100.03	0.936	0.30	(0.28)	0.92	42692.5	10800.00
23	43398.64	104.24	0.917	0.30	(0.28)	0.93	45637.9	11130.00
24	43084.82	113.84	0.876	0.30	(0.28)	0.93	50679.1	12410.00
25	42515.59	122.14	0.845	0.30	(0.28)	0.94	54418.2	11201.00
26	42082.91	127.12	0.834	0.30	(0.28)	0.94	56149.9	12201.00
27	41080.56	134.21	0.820	0.30	(0.28)	0.94	58007.0	12231.00
28	39801.22	142.05	0.803	0.30	(0.28)	0.94	59641.3	10400.00
29	38477.61	150.04	0.787	0.30	(0.28)	0.94	60936.4	12010.00
30	37306.42	156.04	0.775	0.30	(0.28)	0.94	61283.4	10210.00
31	36790.22	159.10	0.768	0.30	(0.28)	0.94	61400.6	12000.00
32	33208.11	184.36	0.720	0.30	(0.28)	0.94	62021.8	10100.00

TOTAL AREA (ACRES) = 62021.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 43398.64 Tc (MIN.) = 104.238
EFFECTIVE AREA (ACRES) = 45637.86 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA (ACRES) = 62021.8
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123166.61 FEET.

FLOW PROCESS FROM NODE 13408.00 TO NODE 13410.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 182.00 DOWNSTREAM (FEET) = 178.72
CHANNEL LENGTH THRU SUBAREA (FEET) = 952.73 CHANNEL SLOPE = 0.0034
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 12.35
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.912
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.40	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	2.90	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 43399.55
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 13.42
AVERAGE FLOW DEPTH (FEET) = 12.35 TRAVEL TIME (MIN.) = 1.18
Tc (MIN.) = 105.42
SUBAREA AREA (ACRES) = 3.30 SUBAREA RUNOFF (CFS) = 1.82
EFFECTIVE AREA (ACRES) = 45641.16 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA (ACRES) = 62025.1 PEAK FLOW RATE (CFS) = 43398.64
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 12.35

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 12.35 FLOW VELOCITY(FEET/SEC.) = 13.42

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124119.34 FEET.

FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: RU50EV36.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	2426.61	27.79	0.30 (0.27)	0.90	1478.1	110.00
2	2523.08	30.18	0.30 (0.27)	0.90	1650.5	100.00
3	2535.23	31.37	0.30 (0.27)	0.90	1727.1	100.00
4	2565.50	34.38	0.30 (0.27)	0.91	1904.1	130.00
5	2700.64	47.40	0.30 (0.28)	0.93	2638.7	20100.00
6	2620.76	52.90	0.30 (0.28)	0.93	2824.4	13600.00
7	2498.72	87.84	0.30 (0.28)	0.93	3795.6	13510.00
8	2354.93	96.73	0.30 (0.28)	0.93	3859.7	13500.00

TOTAL AREA (ACRES) = 3859.7

FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	19762.32	11.39	3.200	0.30 (0.23)	0.76	2415.4	429.00
2	20891.63	12.87	2.966	0.30 (0.23)	0.76	2783.8	425.00
3	21178.96	13.28	2.901	0.30 (0.23)	0.76	2886.5	400.00
4	21904.65	14.71	2.675	0.30 (0.23)	0.76	3239.8	300.00
5	23900.65	19.77	2.220	0.30 (0.23)	0.76	4473.8	210.00
6	24444.65	21.79	2.094	0.30 (0.23)	0.76	4948.6	410.00
7	24845.14	22.79	2.036	0.30 (0.23)	0.76	5180.8	200.00
8	25058.07	23.39	2.000	0.30 (0.23)	0.76	5322.9	230.00
9	25167.38	23.78	1.978	0.30 (0.23)	0.76	5410.0	50700.00
10	25292.87	24.25	1.950	0.30 (0.23)	0.76	5510.7	50500.00
11	25363.89	24.49	1.936	0.30 (0.23)	0.76	5576.7	50600.00
12	25365.16	24.49	1.936	0.30 (0.23)	0.76	5577.9	220.50
13	27269.04	30.92	1.690	0.30 (0.23)	0.77	7316.1	110.00
14	30339.13	40.11	1.450	0.30 (0.24)	0.79	11073.3	150.00
15	31544.54	43.85	1.390	0.30 (0.24)	0.80	12704.5	50260.00
16	33161.56	50.02	1.290	0.30 (0.25)	0.83	15664.2	31100.00
17	36368.25	66.10	1.140	0.30 (0.26)	0.87	23295.2	13100.00
18	37160.13	72.83	1.095	0.30 (0.27)	0.88	26078.8	11801.00
19	38913.63	83.49	1.023	0.30 (0.27)	0.90	31203.2	11530.00

20	39874.32	87.79	0.994	0.30 (0.27)	0.90	33735.9	11701.00
21	41112.16	93.10	0.966	0.30 (0.27)	0.91	37269.6	13010.00
22	42872.02	101.22	0.930	0.30 (0.28)	0.92	42695.8	10800.00
23	43398.64	105.42	0.912	0.30 (0.28)	0.93	45641.2	11130.00
24	43084.82	115.03	0.871	0.30 (0.28)	0.93	50682.4	12410.00
25	42515.59	123.33	0.842	0.30 (0.28)	0.94	54421.5	11201.00
26	42082.91	128.32	0.832	0.30 (0.28)	0.94	56153.2	12201.00
27	41080.56	135.41	0.817	0.30 (0.28)	0.94	58010.3	12231.00
28	39801.22	143.27	0.801	0.30 (0.28)	0.94	59644.6	10400.00
29	38477.61	151.27	0.784	0.30 (0.28)	0.94	60939.7	12010.00
30	37306.42	157.28	0.772	0.30 (0.28)	0.94	61286.7	10210.00
31	36790.22	160.35	0.766	0.30 (0.28)	0.94	61403.9	12000.00
32	33208.11	185.64	0.719	0.30 (0.28)	0.94	62025.1	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124119.34 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	2426.61	27.79	1.799	0.30 (0.27)	0.90	1478.1	110.00
2	2523.08	30.18	1.709	0.30 (0.27)	0.90	1650.5	100.00
3	2535.23	31.37	1.678	0.30 (0.27)	0.90	1727.1	100.00
4	2565.50	34.38	1.599	0.30 (0.27)	0.91	1904.1	130.00
5	2700.64	47.40	1.332	0.30 (0.28)	0.93	2638.7	20100.00
6	2620.76	52.90	1.258	0.30 (0.28)	0.93	2824.4	13600.00
7	2498.72	87.84	0.994	0.30 (0.28)	0.93	3795.6	13510.00
8	2354.93	96.73	0.950	0.30 (0.28)	0.93	3859.7	13500.00

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13410.00 = 41710.10 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	21668.76	11.39	3.200	0.30 (0.24)	0.79	3021.2	429.00
2	22873.62	12.87	2.966	0.30 (0.24)	0.78	3468.2	425.00
3	23174.96	13.28	2.901	0.30 (0.24)	0.78	3592.8	400.00
4	23925.43	14.71	2.675	0.30 (0.24)	0.78	4022.1	300.00
5	26102.32	19.77	2.220	0.30 (0.24)	0.78	5525.0	210.00
6	26715.88	21.79	2.094	0.30 (0.24)	0.79	6107.8	410.00
7	27143.78	22.79	2.036	0.30 (0.24)	0.79	6392.7	200.00
8	27370.28	23.39	2.000	0.30 (0.24)	0.79	6567.3	230.00
9	27486.90	23.78	1.978	0.30 (0.24)	0.79	6674.8	50700.00
10	27619.94	24.25	1.950	0.30 (0.24)	0.79	6800.6	50500.00
11	27694.21	24.49	1.936	0.30 (0.24)	0.79	6879.2	50600.00
12	27695.54	24.49	1.936	0.30 (0.24)	0.79	6880.7	220.50
13	28769.15	27.79	1.799	0.30 (0.24)	0.79	7948.3	110.00
14	29573.66	30.18	1.709	0.30 (0.24)	0.79	8767.2	100.00
15	29799.65	30.92	1.690	0.30 (0.24)	0.79	9014.1	110.00
16	29955.13	31.37	1.678	0.30 (0.24)	0.79	9227.8	100.00
17	30990.76	34.38	1.599	0.30 (0.24)	0.80	10635.2	130.00
18	32964.12	40.11	1.450	0.30 (0.24)	0.81	13300.9	150.00
19	34208.30	43.85	1.390	0.30 (0.25)	0.82	15142.8	50260.00
20	35176.08	47.40	1.332	0.30 (0.25)	0.84	17047.1	20100.00
21	35824.14	50.02	1.290	0.30 (0.25)	0.85	18391.4	31100.00
22	36356.25	52.90	1.258	0.30 (0.26)	0.85	19854.4	13600.00
23	38942.89	66.10	1.140	0.30 (0.26)	0.88	26486.6	13100.00
24	39711.27	72.83	1.095	0.30 (0.27)	0.89	29457.2	11801.00
25	41427.53	83.49	1.023	0.30 (0.27)	0.90	34878.0	11530.00
26	42373.22	87.79	0.994	0.30 (0.27)	0.91	37530.0	11701.00
27	42385.55	87.84	0.994	0.30 (0.27)	0.91	37567.3	13510.00

28	43525.76	93.10	0.966	0.30	(0.27)	0.91	41103.1	13010.00
29	44253.82	96.73	0.950	0.30	(0.28)	0.92	43555.0	13500.00
30	45158.56	101.22	0.930	0.30	(0.28)	0.92	46555.5	10800.00
31	45621.20	105.42	0.912	0.30	(0.28)	0.93	49500.8	11130.00
32	45161.02	115.03	0.871	0.30	(0.28)	0.93	54542.1	12410.00
33	44491.82	123.33	0.842	0.30	(0.28)	0.94	58281.2	11201.00
34	44022.92	128.32	0.832	0.30	(0.28)	0.94	60012.9	12201.00
35	42969.01	135.41	0.817	0.30	(0.28)	0.94	61870.0	12231.00
36	41632.57	143.27	0.801	0.30	(0.28)	0.94	63504.3	10400.00
37	40250.85	151.27	0.784	0.30	(0.28)	0.94	64799.4	12010.00
38	39035.98	157.28	0.772	0.30	(0.28)	0.94	65146.4	10210.00
39	38497.46	160.35	0.766	0.30	(0.28)	0.94	65263.6	12000.00
40	34751.51	185.64	0.719	0.30	(0.28)	0.94	65884.8	10100.00

TOTAL AREA (ACRES) = 65884.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 45621.20 Tc (MIN.) = 105.421
EFFECTIVE AREA (ACRES) = 49500.85 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.88
TOTAL AREA (ACRES) = 65884.8
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124119.34 FEET.

FLOW PROCESS FROM NODE 13410.00 TO NODE 13412.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 178.72 DOWNSTREAM (FEET) = 176.93
CHANNEL LENGTH THRU SUBAREA (FEET) = 169.78 CHANNEL SLOPE = 0.0105
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 9.28
CHANNEL FLOW THRU SUBAREA (CFS) = 45621.20
FLOW VELOCITY (FEET/SEC.) = 19.95 FLOW DEPTH (FEET) = 9.28
TRAVEL TIME (MIN.) = 0.14 Tc (MIN.) = 105.56
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124289.12 FEET.

FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<

FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<

PEAK FLOWRATE TABLE FILE NAME: 0506101C.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM	Q	Tc	Fp (Fm)	Ap	Ae	HEADWATER
NUMBER	(CFS)	(MIN.)	(INCH/HR)		(ACRES)	NODE
1	570.78	37.58	0.30 (0.30)	0.98	591.0	10100.00

TOTAL AREA (ACRES) = 591.0

FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM	Q	Tc	Intensity	Fp (Fm)	Ap	Ae	HEADWATER
NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)		(ACRES)	NODE
1	21668.76	11.57	3.171	0.30 (0.24)	0.79	3021.2	429.00
2	22873.62	13.05	2.938	0.30 (0.24)	0.78	3468.2	425.00
3	23174.96	13.46	2.873	0.30 (0.24)	0.78	3592.8	400.00
4	23925.43	14.88	2.647	0.30 (0.24)	0.78	4022.1	300.00
5	26102.32	19.94	2.205	0.30 (0.24)	0.78	5525.0	210.00
6	26715.88	21.96	2.084	0.30 (0.24)	0.79	6107.8	410.00
7	27143.78	22.95	2.026	0.30 (0.24)	0.79	6392.7	200.00
8	27370.28	23.56	1.990	0.30 (0.24)	0.79	6567.3	230.00
9	27486.90	23.95	1.968	0.30 (0.24)	0.79	6674.8	50700.00
10	27619.94	24.42	1.940	0.30 (0.24)	0.79	6800.6	50500.00
11	27694.21	24.66	1.926	0.30 (0.24)	0.79	6879.2	50600.00
12	27695.54	24.66	1.926	0.30 (0.24)	0.79	6880.7	220.50
13	28769.15	27.96	1.792	0.30 (0.24)	0.79	7948.3	110.00
14	29573.66	30.34	1.705	0.30 (0.24)	0.79	8767.2	100.00
15	29799.65	31.08	1.686	0.30 (0.24)	0.79	9014.1	110.00
16	29955.13	31.53	1.674	0.30 (0.24)	0.79	9227.8	100.00
17	30990.76	34.54	1.595	0.30 (0.24)	0.80	10635.2	130.00
18	32964.12	40.27	1.448	0.30 (0.24)	0.81	13300.9	150.00
19	34208.30	44.00	1.387	0.30 (0.25)	0.82	15142.8	50260.00
20	35176.08	47.56	1.330	0.30 (0.25)	0.84	17047.1	20100.00
21	35824.14	50.18	1.288	0.30 (0.25)	0.85	18391.4	31100.00
22	36356.25	53.05	1.257	0.30 (0.26)	0.85	19854.4	13600.00
23	38942.89	66.25	1.139	0.30 (0.26)	0.88	26486.6	13100.00
24	39711.27	72.98	1.094	0.30 (0.27)	0.89	29457.2	11801.00
25	41427.53	83.64	1.022	0.30 (0.27)	0.90	34878.0	11530.00
26	42373.22	87.93	0.993	0.30 (0.27)	0.91	37530.0	11701.00
27	42385.55	87.98	0.993	0.30 (0.27)	0.91	37567.3	13510.00
28	43525.76	93.25	0.965	0.30 (0.27)	0.91	41103.1	13010.00
29	44253.82	96.88	0.949	0.30 (0.28)	0.92	43555.0	13500.00
30	45158.56	101.36	0.930	0.30 (0.28)	0.92	46555.5	10800.00
31	45621.20	105.56	0.912	0.30 (0.28)	0.93	49500.8	11130.00
32	45161.02	115.17	0.870	0.30 (0.28)	0.93	54542.1	12410.00
33	44491.82	123.47	0.842	0.30 (0.28)	0.94	58281.2	11201.00
34	44022.92	128.46	0.832	0.30 (0.28)	0.94	60012.9	12201.00
35	42969.01	135.56	0.817	0.30 (0.28)	0.94	61870.0	12231.00
36	41632.57	143.42	0.801	0.30 (0.28)	0.94	63504.3	10400.00
37	40250.85	151.42	0.784	0.30 (0.28)	0.94	64799.4	12010.00
38	39035.98	157.43	0.772	0.30 (0.28)	0.94	65146.4	10210.00
39	38497.46	160.50	0.765	0.30 (0.28)	0.94	65263.6	12000.00
40	34751.51	185.80	0.719	0.30 (0.28)	0.94	65884.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124289.12 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM	Q	Tc	Intensity	Fp (Fm)	Ap	Ae	HEADWATER
NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)		(ACRES)	NODE
1	570.78	37.58	1.515	0.30 (0.30)	0.98	591.0	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 14677.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM	Q	Tc	Intensity	Fp (Fm)	Ap	Ae	HEADWATER
NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)		(ACRES)	NODE

1	22082.99	11.57	3.171	0.30	(0.24)	0.80	3203.1	429.00
2	23302.77	13.05	2.938	0.30	(0.24)	0.80	3673.4	425.00
3	23606.75	13.46	2.873	0.30	(0.24)	0.80	3804.5	400.00
4	24361.17	14.88	2.647	0.30	(0.24)	0.80	4256.2	300.00
5	26576.34	19.94	2.205	0.30	(0.24)	0.80	5838.6	210.00
6	27205.05	21.96	2.084	0.30	(0.24)	0.80	6453.3	410.00
7	27638.37	22.95	2.026	0.30	(0.24)	0.80	6753.7	200.00
8	27867.49	23.56	1.990	0.30	(0.24)	0.80	6937.8	230.00
9	27985.49	23.95	1.968	0.30	(0.24)	0.80	7051.5	50700.00
10	28119.92	24.42	1.940	0.30	(0.24)	0.80	7184.7	50500.00
11	28194.77	24.66	1.926	0.30	(0.24)	0.80	7267.0	50600.00
12	28196.11	24.66	1.926	0.30	(0.24)	0.80	7268.5	220.50
13	29290.17	27.96	1.792	0.30	(0.24)	0.80	8388.0	110.00
14	30106.12	30.34	1.705	0.30	(0.24)	0.80	9244.4	100.00
15	30337.58	31.08	1.686	0.30	(0.24)	0.80	9502.9	110.00
16	30496.23	31.53	1.674	0.30	(0.24)	0.80	9723.7	100.00
17	31549.61	34.54	1.595	0.30	(0.24)	0.81	11178.4	130.00
18	32607.61	37.58	1.515	0.30	(0.24)	0.81	12639.3	10100.00
19	33503.18	40.27	1.448	0.30	(0.25)	0.82	13891.9	150.00
20	34719.07	44.00	1.387	0.30	(0.25)	0.83	15733.8	50260.00
21	35659.93	47.56	1.330	0.30	(0.25)	0.84	17638.1	20100.00
22	36288.59	50.18	1.288	0.30	(0.26)	0.85	18982.4	31100.00
23	36806.03	53.05	1.257	0.30	(0.26)	0.86	20445.4	13600.00
24	39337.56	66.25	1.139	0.30	(0.26)	0.88	27077.6	13100.00
25	40084.77	72.98	1.094	0.30	(0.27)	0.89	30048.2	11801.00
26	41767.46	83.64	1.022	0.30	(0.27)	0.90	35469.0	11530.00
27	42699.63	87.93	0.993	0.30	(0.27)	0.91	38121.0	11701.00
28	42711.79	87.98	0.993	0.30	(0.27)	0.91	38158.3	13510.00
29	43839.07	93.25	0.965	0.30	(0.27)	0.92	41694.1	13010.00
30	44559.78	96.88	0.949	0.30	(0.28)	0.92	44146.0	13500.00
31	45455.42	101.36	0.930	0.30	(0.28)	0.92	47146.5	10800.00
32	45909.54	105.56	0.912	0.30	(0.28)	0.93	50091.8	11130.00
33	45429.90	115.17	0.870	0.30	(0.28)	0.93	55133.1	12410.00
34	44747.55	123.47	0.842	0.30	(0.28)	0.94	58872.2	11201.00
35	44273.83	128.46	0.832	0.30	(0.28)	0.94	60603.9	12201.00
36	43213.07	135.56	0.817	0.30	(0.28)	0.94	62461.0	12231.00
37	41869.03	143.42	0.801	0.30	(0.28)	0.94	64095.3	10400.00
38	40479.58	151.42	0.784	0.30	(0.28)	0.94	65390.4	12010.00
39	39258.89	157.43	0.772	0.30	(0.28)	0.94	65737.4	10210.00
40	38717.41	160.50	0.765	0.30	(0.28)	0.94	65854.6	12000.00
41	34949.73	185.80	0.719	0.30	(0.28)	0.94	66475.8	10100.00

TOTAL AREA (ACRES) = 66475.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 45909.54 Tc (MIN.) = 105.563
EFFECTIVE AREA (ACRES) = 50091.85 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA (ACRES) = 66475.8
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124289.12 FEET.

```
*****
FLOW PROCESS FROM NODE 13412.00 TO NODE 13700.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM (FEET) = 176.93 DOWNSTREAM (FEET) = 170.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 260.10 CHANNEL SLOPE = 0.0266
```

GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 7.15
CHANNEL FLOW THRU SUBAREA (CFS) = 45909.54
FLOW VELOCITY (FEET/SEC.) = 27.22 FLOW DEPTH (FEET) = 7.15
TRAVEL TIME (MIN.) = 0.16 Tc (MIN.) = 105.72
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124549.22 FEET.

```
*****
FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 12
-----
>>>>CLEAR MEMORY BANK # 2 <<<<
=====
```

```
*****
FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 15.1
-----
>>>>DEFINE MEMORY BANK # 2 <<<<
=====
```

PEAK FLOWRATE TABLE FILE NAME: P508XX50.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	192.92	22.10	0.30 (0.30)	0.99	131.3	50800.00
TOTAL AREA (ACRES) =		131.3				

```
*****
FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 11
-----
>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<
=====
```

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22082.99	11.78	3.139	0.30 (0.24)	0.80	3203.1	429.00
2	23302.77	13.25	2.906	0.30 (0.24)	0.80	3673.4	425.00
3	23606.75	13.66	2.841	0.30 (0.24)	0.80	3804.5	400.00
4	24361.17	15.08	2.622	0.30 (0.24)	0.80	4256.2	300.00
5	26576.34	20.13	2.192	0.30 (0.24)	0.80	5838.6	210.00
6	27205.05	22.16	2.073	0.30 (0.24)	0.80	6453.3	410.00
7	27638.37	23.14	2.015	0.30 (0.24)	0.80	6753.7	200.00
8	27867.49	23.75	1.979	0.30 (0.24)	0.80	6937.8	230.00
9	27985.49	24.14	1.957	0.30 (0.24)	0.80	7051.5	50700.00
10	28119.92	24.61	1.929	0.30 (0.24)	0.80	7184.7	50500.00
11	28194.77	24.85	1.915	0.30 (0.24)	0.80	7267.0	50600.00
12	28196.11	24.85	1.915	0.30 (0.24)	0.80	7268.5	220.50
13	29290.17	28.14	1.785	0.30 (0.24)	0.80	8388.0	110.00
14	30106.12	30.53	1.700	0.30 (0.24)	0.80	9244.4	100.00
15	30337.58	31.26	1.681	0.30 (0.24)	0.80	9502.9	110.00
16	30496.23	31.71	1.669	0.30 (0.24)	0.80	9723.7	100.00
17	31549.61	34.72	1.590	0.30 (0.24)	0.81	11178.4	130.00
18	32607.61	37.76	1.511	0.30 (0.24)	0.81	12639.3	10100.00
19	33503.18	40.45	1.445	0.30 (0.25)	0.82	13891.9	150.00
20	34719.07	44.18	1.384	0.30 (0.25)	0.83	15733.8	50260.00
21	35659.93	47.73	1.327	0.30 (0.25)	0.84	17638.1	20100.00
22	36288.59	50.35	1.286	0.30 (0.26)	0.85	18982.4	31100.00
23	36806.03	53.22	1.255	0.30 (0.26)	0.86	20445.4	13600.00

24	39337.56	66.42	1.138	0.30 (0.26)	0.88	27077.6	13100.00
25	40084.77	73.15	1.092	0.30 (0.27)	0.89	30048.2	11801.00
26	41767.46	83.80	1.021	0.30 (0.27)	0.90	35469.0	11530.00
27	42699.63	88.09	0.992	0.30 (0.27)	0.91	38121.0	11701.00
28	42711.79	88.15	0.991	0.30 (0.27)	0.91	38158.3	13510.00
29	43839.07	93.41	0.964	0.30 (0.27)	0.92	41694.1	13010.00
30	44559.78	97.04	0.949	0.30 (0.28)	0.92	44146.0	13500.00
31	45455.42	101.52	0.929	0.30 (0.28)	0.92	47146.5	10800.00
32	45909.54	105.72	0.911	0.30 (0.28)	0.93	50091.8	11130.00
33	45429.90	115.33	0.869	0.30 (0.28)	0.93	55133.1	12410.00
34	44747.55	123.63	0.841	0.30 (0.28)	0.94	58872.2	11201.00
35	44273.83	128.62	0.831	0.30 (0.28)	0.94	60603.9	12201.00
36	43213.07	135.72	0.817	0.30 (0.28)	0.94	62461.0	12231.00
37	41869.03	143.58	0.800	0.30 (0.28)	0.94	64095.3	10400.00
38	40479.58	151.58	0.784	0.30 (0.28)	0.94	65390.4	12010.00
39	39258.89	157.60	0.771	0.30 (0.28)	0.94	65737.4	10210.00
40	38717.41	160.67	0.765	0.30 (0.28)	0.94	65854.6	12000.00
41	34949.73	185.97	0.719	0.30 (0.28)	0.94	66475.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124549.22 FEET.

** MEMORY BANK # 2 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	192.92	22.10	2.076	0.30 (0.30)	0.99	131.3	50800.00

LONGEST FLOWPATH FROM NODE 50800.00 TO NODE 13700.00 = 5946.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22247.14	11.78	3.139	0.30 (0.24)	0.80	3273.1	429.00
2	23472.31	13.25	2.906	0.30 (0.24)	0.80	3752.1	425.00
3	23777.20	13.66	2.841	0.30 (0.24)	0.80	3885.6	400.00
4	24533.17	15.08	2.622	0.30 (0.24)	0.80	4345.8	300.00
5	26763.49	20.13	2.192	0.30 (0.24)	0.80	5958.1	210.00
6	27381.91	22.10	2.076	0.30 (0.24)	0.80	6568.9	50800.00
7	27397.65	22.16	2.073	0.30 (0.24)	0.80	6584.6	410.00
8	27824.66	23.14	2.015	0.30 (0.24)	0.80	6885.0	200.00
9	28049.90	23.75	1.979	0.30 (0.24)	0.80	7069.1	230.00
10	28165.45	24.14	1.957	0.30 (0.24)	0.80	7182.8	50700.00
11	28296.88	24.61	1.929	0.30 (0.24)	0.80	7316.0	50500.00
12	28370.21	24.85	1.915	0.30 (0.24)	0.80	7398.3	50600.00
13	28371.53	24.85	1.915	0.30 (0.24)	0.80	7399.8	220.50
14	29451.55	28.14	1.785	0.30 (0.24)	0.80	8519.3	110.00
15	30258.28	30.53	1.700	0.30 (0.24)	0.80	9375.7	100.00
16	30487.64	31.26	1.681	0.30 (0.24)	0.80	9634.2	110.00
17	30645.02	31.71	1.669	0.30 (0.24)	0.80	9855.0	100.00
18	31689.85	34.72	1.590	0.30 (0.24)	0.81	11309.7	130.00
19	32739.23	37.76	1.511	0.30 (0.24)	0.82	12770.6	10100.00
20	33627.64	40.45	1.445	0.30 (0.25)	0.82	14023.2	150.00
21	34836.98	44.18	1.384	0.30 (0.25)	0.83	15865.1	50260.00
22	35771.61	47.73	1.327	0.30 (0.25)	0.84	17769.4	20100.00
23	36395.87	50.35	1.286	0.30 (0.26)	0.85	19113.7	31100.00
24	36909.91	53.22	1.255	0.30 (0.26)	0.86	20576.7	13600.00
25	39428.75	66.42	1.138	0.30 (0.26)	0.88	27208.9	13100.00
26	40171.05	73.15	1.092	0.30 (0.27)	0.89	30179.5	11801.00
27	41845.96	83.80	1.021	0.30 (0.27)	0.90	35600.3	11530.00
28	42775.00	88.09	0.992	0.30 (0.27)	0.91	38252.3	11701.00
29	42787.12	88.15	0.991	0.30 (0.27)	0.91	38289.6	13510.00

30	43911.45	93.41	0.964	0.30 (0.27)	0.92	41825.4	13010.00
31	44630.46	97.04	0.949	0.30 (0.28)	0.92	44277.3	13500.00
32	45523.99	101.52	0.929	0.30 (0.28)	0.92	47277.8	10800.00
33	45976.14	105.72	0.911	0.30 (0.28)	0.93	50223.1	11130.00
34	45491.99	115.33	0.869	0.30 (0.28)	0.93	55264.4	12410.00
35	44806.63	123.63	0.841	0.30 (0.28)	0.94	59003.5	11201.00
36	44331.79	128.62	0.831	0.30 (0.28)	0.94	60735.2	12201.00
37	43269.44	135.72	0.817	0.30 (0.28)	0.94	62592.3	12231.00
38	41923.64	143.58	0.800	0.30 (0.28)	0.94	64226.6	10400.00
39	40532.40	151.58	0.784	0.30 (0.28)	0.94	65521.7	12010.00
40	39310.37	157.60	0.771	0.30 (0.28)	0.94	65868.7	10210.00
41	38768.19	160.67	0.765	0.30 (0.28)	0.94	65985.9	12000.00
42	34995.50	185.97	0.719	0.30 (0.28)	0.94	66607.1	10100.00

TOTAL AREA (ACRES) = 66607.1

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 45976.14 Tc(MIN.) = 105.723

EFFECTIVE AREA(ACRES) = 50223.15 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92

TOTAL AREA (ACRES) = 66607.1

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124549.22 FEET.

=====

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 66607.1 TC(MIN.) = 105.72

EFFECTIVE AREA(ACRES) = 50223.15 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.929

PEAK FLOW RATE(CFS) = 45976.14

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22247.14	11.78	3.139	0.30 (0.24)	0.80	3273.1	429.00
2	23472.31	13.25	2.906	0.30 (0.24)	0.80	3752.1	425.00
3	23777.20	13.66	2.841	0.30 (0.24)	0.80	3885.6	400.00
4	24533.17	15.08	2.622	0.30 (0.24)	0.80	4345.8	300.00
5	26763.49	20.13	2.192	0.30 (0.24)	0.80	5958.1	210.00
6	27381.91	22.10	2.076	0.30 (0.24)	0.80	6568.9	50800.00
7	27397.65	22.16	2.073	0.30 (0.24)	0.80	6584.6	410.00
8	27824.66	23.14	2.015	0.30 (0.24)	0.80	6885.0	200.00
9	28049.90	23.75	1.979	0.30 (0.24)	0.80	7069.1	230.00
10	28165.45	24.14	1.957	0.30 (0.24)	0.80	7182.8	50700.00
11	28296.88	24.61	1.929	0.30 (0.24)	0.80	7316.0	50500.00
12	28370.21	24.85	1.915	0.30 (0.24)	0.80	7398.3	50600.00
13	28371.53	24.85	1.915	0.30 (0.24)	0.80	7399.8	220.50
14	29451.55	28.14	1.785	0.30 (0.24)	0.80	8519.3	110.00
15	30258.28	30.53	1.700	0.30 (0.24)	0.80	9375.7	100.00
16	30487.64	31.26	1.681	0.30 (0.24)	0.80	9634.2	110.00
17	30645.02	31.71	1.669	0.30 (0.24)	0.80	9855.0	100.00
18	31689.85	34.72	1.590	0.30 (0.24)	0.81	11309.7	130.00
19	32739.23	37.76	1.511	0.30 (0.24)	0.82	12770.6	10100.00
20	33627.64	40.45	1.445	0.30 (0.25)	0.82	14023.2	150.00
21	34836.98	44.18	1.384	0.30 (0.25)	0.83	15865.1	50260.00
22	35771.61	47.73	1.327	0.30 (0.25)	0.84	17769.4	20100.00
23	36395.87	50.35	1.286	0.30 (0.26)	0.85	19113.7	31100.00
24	36909.91	53.22	1.255	0.30 (0.26)	0.86	20576.7	13600.00
25	39428.75	66.42	1.138	0.30 (0.26)	0.88	27208.9	13100.00
26	40171.05	73.15	1.092	0.30 (0.27)	0.89	30179.5	11801.00
27	41845.96	83.80	1.021	0.30 (0.27)	0.90	35600.3	11530.00

28	42775.00	88.09	0.992	0.30 (0.27)	0.91	38252.3	11701.00
29	42787.12	88.15	0.991	0.30 (0.27)	0.91	38289.6	13510.00
30	43911.45	93.41	0.964	0.30 (0.27)	0.92	41825.4	13010.00
31	44630.46	97.04	0.949	0.30 (0.28)	0.92	44277.3	13500.00
32	45523.99	101.52	0.929	0.30 (0.28)	0.92	47277.8	10800.00
33	45976.14	105.72	0.911	0.30 (0.28)	0.93	50223.1	11130.00
34	45491.99	115.33	0.869	0.30 (0.28)	0.93	55264.4	12410.00
35	44806.63	123.63	0.841	0.30 (0.28)	0.94	59003.5	11201.00
36	44331.79	128.62	0.831	0.30 (0.28)	0.94	60735.2	12201.00
37	43269.44	135.72	0.817	0.30 (0.28)	0.94	62592.3	12231.00
38	41923.64	143.58	0.800	0.30 (0.28)	0.94	64226.6	10400.00
39	40532.40	151.58	0.784	0.30 (0.28)	0.94	65521.7	12010.00
40	39310.37	157.60	0.771	0.30 (0.28)	0.94	65868.7	10210.00
41	38768.19	160.67	0.765	0.30 (0.28)	0.94	65985.9	12000.00
42	34995.50	185.97	0.719	0.30 (0.28)	0.94	66607.1	10100.00

=====
=====

END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2010 Advanced Engineering Software (aes)
Ver. 17.0 Release Date: 07/01/2010 License ID 1527

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 136 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 50-YR EV JULY 2023 ROKAMOTO *

FILE NAME: RU50EV36.DAT
TIME/DATE OF STUDY: 10:46 07/05/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 50.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.254
- 2) 10.00; 3.396
- 3) 15.00; 2.615
- 4) 20.00; 2.190
- 5) 25.00; 1.899
- 6) 30.00; 1.707
- 7) 40.00; 1.447
- 8) 50.00; 1.285
- 9) 60.00; 1.174
- 10) 90.00; 0.972
- 11) 120.00; 0.842
- 12) 180.00; 0.717
- 13) 360.00; 0.527
- 14) 1200.00; 0.230

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / SIDE / WAY	CURB HEIGHT (FT)	GUTTER WIDTH (FT)	GEOMETRIES LIP (FT)	MANNING HIKE FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167 0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13600.00 TO NODE 13600.50 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<
=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 488.61
ELEVATION DATA: UPSTREAM(FEET) = 872.12 DOWNSTREAM(FEET) = 744.80

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 10.995
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 3.241
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "OPEN BRUSH"	-	3.39	0.30	1.000	0	11.00

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 8.97
TOTAL AREA(ACRES) = 3.39 PEAK FLOW RATE(CFS) = 8.97

FLOW PROCESS FROM NODE 13600.50 TO NODE 13601.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<<
=====

ELEVATION DATA: UPSTREAM(FEET) = 744.80 DOWNSTREAM(FEET) = 707.32
CHANNEL LENGTH THRU SUBAREA(FEET) = 418.30 CHANNEL SLOPE = 0.0896
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.43
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.962
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.45	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 17.92
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.91
AVERAGE FLOW DEPTH(FEET) = 0.42 TRAVEL TIME(MIN.) = 1.78
Tc(MIN.) = 12.78
SUBAREA AREA(ACRES) = 7.45 SUBAREA RUNOFF(CFS) = 17.85
EFFECTIVE AREA(ACRES) = 10.84 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 10.8 PEAK FLOW RATE(CFS) = 25.97
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.52

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 0.52 FLOW VELOCITY (FEET/SEC.) = 4.49
LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13601.00 = 906.91 FEET.

FLOW PROCESS FROM NODE 13601.00 TO NODE 13602.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 707.32 DOWNSTREAM (FEET) = 657.12
CHANNEL LENGTH THRU SUBAREA (FEET) = 777.60 CHANNEL SLOPE = 0.0646
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.97
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 2.596

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.32	0.30	1.000	-
USER-DEFINED	-	4.70	0.30	1.000	-
USER-DEFINED	-	25.05	0.30	1.000	-
USER-DEFINED	-	0.45	0.30	1.000	-
USER-DEFINED	-	0.44	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 58.05

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.29

AVERAGE FLOW DEPTH (FEET) = 0.93 TRAVEL TIME (MIN.) = 2.45

Tc (MIN.) = 15.23

SUBAREA AREA (ACRES) = 30.96 SUBAREA RUNOFF (CFS) = 63.97
EFFECTIVE AREA (ACRES) = 41.80 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 41.8 PEAK FLOW RATE (CFS) = 86.36
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 1.16

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 1.16 FLOW VELOCITY (FEET/SEC.) = 6.03

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13602.00 = 1684.51 FEET.

FLOW PROCESS FROM NODE 13602.00 TO NODE 13603.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 657.12 DOWNSTREAM (FEET) = 584.58
CHANNEL LENGTH THRU SUBAREA (FEET) = 1186.54 CHANNEL SLOPE = 0.0611
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 1.36
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 2.331

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.03	0.30	1.000	-
USER-DEFINED	-	2.51	0.30	1.000	-

USER-DEFINED - 1.52 0.30 1.000 -
USER-DEFINED - 12.30 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 107.74

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.35

AVERAGE FLOW DEPTH (FEET) = 1.34 TRAVEL TIME (MIN.) = 3.11

Tc (MIN.) = 18.34

SUBAREA AREA (ACRES) = 23.36 SUBAREA RUNOFF (CFS) = 42.70
EFFECTIVE AREA (ACRES) = 65.16 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 65.2 PEAK FLOW RATE (CFS) = 119.11
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 1.41

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 1.41 FLOW VELOCITY (FEET/SEC.) = 6.56

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13603.00 = 2871.05 FEET.

FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 584.58 DOWNSTREAM (FEET) = 544.91
CHANNEL LENGTH THRU SUBAREA (FEET) = 860.98 CHANNEL SLOPE = 0.0461
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 1.67
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 2.152

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	10.22	0.30	1.000	-
USER-DEFINED	-	4.19	0.30	1.000	-
USER-DEFINED	-	0.07	0.30	1.000	-
USER-DEFINED	-	1.11	0.30	1.000	-
USER-DEFINED	-	5.56	0.30	1.000	-
USER-DEFINED	-	0.09	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 136.82

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.22

AVERAGE FLOW DEPTH (FEET) = 1.65 TRAVEL TIME (MIN.) = 2.31

Tc (MIN.) = 20.65

SUBAREA AREA (ACRES) = 21.24 SUBAREA RUNOFF (CFS) = 35.41
EFFECTIVE AREA (ACRES) = 86.40 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 86.4 PEAK FLOW RATE (CFS) = 144.04
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 1.70

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 1.70 FLOW VELOCITY (FEET/SEC.) = 6.30

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13620.00 = 3732.03 FEET.


```

*****
FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 10
-----
>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<
=====
*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13522.00 IS CODE = 15.1
-----
>>>>DEFINE MEMORY BANK # 2 <<<<
=====
PEAK FLOWRATE TABLE FILE NAME: S35X50.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:
STREAM      Q      Tc      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR)    (ACRES)  NODE
  1      1198.50  52.93  0.30( 0.28)  0.95    1515.8  13510.00
  2      1092.68  61.25  0.30( 0.28)  0.94    1579.8  13500.00
TOTAL AREA(ACRES) =      1579.8

*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13522.00 IS CODE = 14.0
-----
>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<
=====
MAIN-STREAM MEMORY DEFINED AS FOLLOWS:
STREAM      Q      Tc      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR)    (ACRES)  NODE
  1      1198.50  52.93  0.30( 0.28)  0.95    1515.8  13510.00
  2      1092.68  61.25  0.30( 0.28)  0.94    1579.8  13500.00
TOTAL AREA(ACRES) =      1579.8

*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13620.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 632.19 DOWNSTREAM(FEET) = 544.91
CHANNEL LENGTH THRU SUBAREA(FEET) = 2062.96 CHANNEL SLOPE = 0.0423
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.57
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.222
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp      Ap      SCS
LAND USE              GROUP  (ACRES)  (INCH/HR)  (DECIMAL)  CN
USER-DEFINED          -      17.68    0.30    1.000    -
USER-DEFINED          -      2.36    0.30    1.000    -
USER-DEFINED          -      0.60    0.30    1.000    -
USER-DEFINED          -      0.22    0.30    1.000    -
USER-DEFINED          -      2.22    0.30    1.000    -
USER-DEFINED          -      3.42    0.30    1.000    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1209.50
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.50

```

```

AVERAGE FLOW DEPTH(FEET) = 2.57 TRAVEL TIME(MIN.) = 2.75
Tc(MIN.) = 55.68
SUBAREA AREA(ACRES) = 26.50 SUBAREA RUNOFF(CFS) = 22.00
EFFECTIVE AREA(ACRES) = 1542.26 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
TOTAL AREA(ACRES) = 1606.3 PEAK FLOW RATE(CFS) = 1301.65
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.68

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 2.68 FLOW VELOCITY(FEET/SEC.) = 12.80
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13620.00 TO NODE 13620.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 55.68
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.222
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp      Ap      SCS
LAND USE              GROUP  (ACRES)  (INCH/HR)  (DECIMAL)  CN
NATURAL FAIR COVER
"WOODLAND,GRASS"      B      1.44    0.30    1.000    65
NATURAL FAIR COVER
"WOODLAND,GRASS"      B      0.01    0.30    1.000    65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 1.45 SUBAREA RUNOFF(CFS) = 1.20
EFFECTIVE AREA(ACRES) = 1543.71 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
TOTAL AREA(ACRES) = 1607.8 PEAK FLOW RATE(CFS) = 1302.85

```

```

*****
FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 11
-----
>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<
=====

```

** MAIN STREAM CONFLUENCE DATA **

```

STREAM      Q      Tc      Intensity  Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR)  (INCH/HR)    (ACRES)  NODE
  1      1302.85  55.68    1.222  0.30( 0.28)  0.95    1543.7  13510.00
  2      1248.68  64.08    1.147  0.30( 0.28)  0.95    1607.8  13500.00
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

```

** MEMORY BANK # 1 CONFLUENCE DATA **

```

STREAM      Q      Tc      Intensity  Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR)  (INCH/HR)    (ACRES)  NODE
  1      144.04  20.65    2.152  0.30( 0.30)  1.00    86.4    13600.00
LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13620.00 = 3732.03 FEET.

```

** PEAK FLOW RATE TABLE **

```

STREAM      Q      Tc      Intensity  Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR)  (INCH/HR)    (ACRES)  NODE
  1      1106.54  20.65    2.152  0.30( 0.29)  0.95    658.9   13600.00

```

2 1374.55 55.68 1.222 0.30(0.29) 0.95 1630.1 13510.00
 3 1314.51 64.08 1.147 0.30(0.28) 0.95 1694.2 13500.00
 TOTAL AREA (ACRES) = 1694.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 1374.55 Tc (MIN.) = 55.676
 EFFECTIVE AREA (ACRES) = 1630.11 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
 TOTAL AREA (ACRES) = 1694.2
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

 FLOW PROCESS FROM NODE 13620.00 TO NODE 13640.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 544.91 DOWNSTREAM (FEET) = 489.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1384.37 CHANNEL SLOPE = 0.0404
 GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT (FEET) = 2.82
 * 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.202

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.39	0.30	1.000	-
USER-DEFINED	-	16.30	0.30	1.000	-
USER-DEFINED	-	4.08	0.30	1.000	-
USER-DEFINED	-	12.36	0.30	1.000	-
USER-DEFINED	-	11.23	0.30	1.000	-
USER-DEFINED	-	5.16	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 1396.69
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 12.88
 AVERAGE FLOW DEPTH (FEET) = 2.82 TRAVEL TIME (MIN.) = 1.79
 Tc (MIN.) = 57.47
 SUBAREA AREA (ACRES) = 54.52 SUBAREA RUNOFF (CFS) = 44.27
 EFFECTIVE AREA (ACRES) = 1684.63 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
 TOTAL AREA (ACRES) = 1748.7 PEAK FLOW RATE (CFS) = 1389.65
 GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT (FEET) = 2.81

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 2.81 FLOW VELOCITY (FEET/SEC.) = 12.87
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

 FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 57.47
 * 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.202
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	53.93	0.30	1.000	-
USER-DEFINED	-	0.45	0.30	1.000	-
USER-DEFINED	-	3.98	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 58.36 SUBAREA RUNOFF (CFS) = 47.39
 EFFECTIVE AREA (ACRES) = 1742.99 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
 TOTAL AREA (ACRES) = 1807.1 PEAK FLOW RATE (CFS) = 1437.03

 FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P201XX50.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	238.49	17.13	0.30 (0.26)	0.85	133.8	20100.00
TOTAL AREA (ACRES) =		133.8				

 FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1217.61	22.55	2.041	0.30 (0.29)	0.96	771.8	13600.00
2	1437.03	57.47	1.202	0.30 (0.29)	0.95	1743.0	13510.00
3	1380.61	65.90	1.134	0.30 (0.29)	0.95	1807.1	13500.00
LONGEST FLOWPATH FROM NODE		13500.00 TO NODE 13640.00 = 22062.09 FEET.					

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	238.49	17.13	2.434	0.30 (0.26)	0.85	133.8	20100.00
LONGEST FLOWPATH FROM NODE		20100.00 TO NODE 13640.00 = 5247.00 FEET.					

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1370.34	17.13	2.434	0.30 (0.28)	0.94	719.9	20100.00
2	1413.09	22.55	2.041	0.30 (0.28)	0.95	905.6	13600.00
3	1540.61	57.47	1.202	0.30 (0.28)	0.95	1876.8	13510.00
4	1476.77	65.90	1.134	0.30 (0.28)	0.94	1940.9	13500.00
TOTAL AREA (ACRES) =		1940.9					

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 1540.61 Tc (MIN.) = 57.467
 EFFECTIVE AREA (ACRES) = 1876.79 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
 TOTAL AREA (ACRES) = 1940.9

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

FLOW PROCESS FROM NODE 13640.00 TO NODE 13641.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 489.00 DOWNSTREAM(FEET) = 436.89
CHANNEL LENGTH THRU SUBAREA(FEET) = 2994.52 CHANNEL SLOPE = 0.0174
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 3.79

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.157

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.96	0.30	1.000	-
USER-DEFINED	-	0.01	0.30	1.000	-
USER-DEFINED	-	1.56	0.30	1.000	-
USER-DEFINED	-	10.45	0.30	1.000	-
USER-DEFINED	-	44.94	0.30	1.000	-
USER-DEFINED	-	9.66	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1566.69

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.98

AVERAGE FLOW DEPTH(FEET) = 3.79 TRAVEL TIME(MIN.) = 5.00

Tc(MIN.) = 62.47

SUBAREA AREA(ACRES) = 67.58 SUBAREA RUNOFF(CFS) = 52.15

EFFECTIVE AREA(ACRES) = 1944.37 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95

TOTAL AREA(ACRES) = 2008.4 PEAK FLOW RATE(CFS) = 1540.61

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 3.76

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 3.76 FLOW VELOCITY(FEET/SEC.) = 9.93

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13641.00 = 25056.61 FEET.

FLOW PROCESS FROM NODE 13641.00 TO NODE 13641.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 62.47

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.157

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	16.49	0.30	1.000	-
USER-DEFINED	-	20.39	0.30	1.000	-
USER-DEFINED	-	7.02	0.30	1.000	-
USER-DEFINED	-	12.58	0.30	1.000	-
USER-DEFINED	-	42.49	0.30	1.000	-
USER-DEFINED	-	5.73	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 104.70 SUBAREA RUNOFF(CFS) = 80.80

EFFECTIVE AREA(ACRES) = 2049.07 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95

TOTAL AREA(ACRES) = 2113.1 PEAK FLOW RATE(CFS) = 1608.30

FLOW PROCESS FROM NODE 13641.00 TO NODE 13641.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 62.47

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.157

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.78	0.30	1.000	-
USER-DEFINED	-	6.25	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 8.03 SUBAREA RUNOFF(CFS) = 6.20

EFFECTIVE AREA(ACRES) = 2057.10 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95

TOTAL AREA(ACRES) = 2121.2 PEAK FLOW RATE(CFS) = 1614.50

FLOW PROCESS FROM NODE 13641.00 TO NODE 13642.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 436.89 DOWNSTREAM(FEET) = 394.80

CHANNEL LENGTH THRU SUBAREA(FEET) = 2814.16 CHANNEL SLOPE = 0.0150

GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 4.13

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.125

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.67	0.30	1.000	-
USER-DEFINED	-	24.24	0.30	1.000	-
USER-DEFINED	-	1.34	0.30	1.000	-
USER-DEFINED	-	74.98	0.30	1.000	-
USER-DEFINED	-	101.12	0.30	1.000	-
USER-DEFINED	-	16.90	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1695.89

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.70

AVERAGE FLOW DEPTH(FEET) = 4.12 TRAVEL TIME(MIN.) = 4.83

Tc(MIN.) = 67.30

SUBAREA AREA(ACRES) = 219.25 SUBAREA RUNOFF(CFS) = 162.77

EFFECTIVE AREA(ACRES) = 2276.35 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96

TOTAL AREA(ACRES) = 2340.4 PEAK FLOW RATE(CFS) = 1717.01

GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 4.16

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 4.16 FLOW VELOCITY(FEET/SEC.) = 9.73
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13642.00 = 27870.77 FEET.

FLOW PROCESS FROM NODE 13642.00 TO NODE 13642.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 67.30
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.125
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	9.95	0.30	1.000	-
USER-DEFINED	-	10.02	0.30	1.000	-
USER-DEFINED	-	4.45	0.30	1.000	-
USER-DEFINED	-	179.37	0.30	1.000	-
USER-DEFINED	-	11.47	0.30	1.000	-
USER-DEFINED	-	0.17	0.30	0.850	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 215.43 SUBAREA RUNOFF(CFS) = 159.94
EFFECTIVE AREA(ACRES) = 2491.78 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA(ACRES) = 2555.9 PEAK FLOW RATE(CFS) = 1876.96

FLOW PROCESS FROM NODE 13642.00 TO NODE 13642.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 67.30
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.125
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.03	0.30	0.850	-
USER-DEFINED	-	5.14	0.30	1.000	-
USER-DEFINED	-	11.22	0.30	1.000	-
USER-DEFINED	-	0.33	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 16.72 SUBAREA RUNOFF(CFS) = 12.41
EFFECTIVE AREA(ACRES) = 2508.50 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA(ACRES) = 2572.6 PEAK FLOW RATE(CFS) = 1889.37

FLOW PROCESS FROM NODE 13642.00 TO NODE 13643.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 394.80 DOWNSTREAM(FEET) = 342.39

CHANNEL LENGTH THRU SUBAREA(FEET) = 2913.57 CHANNEL SLOPE = 0.0180
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 4.23
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.094

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	2.17	0.30	1.000	-
USER-DEFINED	-	9.19	0.30	1.000	-
USER-DEFINED	-	67.57	0.30	1.000	-
USER-DEFINED	-	35.19	0.30	1.000	-
USER-DEFINED	-	30.67	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1941.22
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.77
AVERAGE FLOW DEPTH(FEET) = 4.22 TRAVEL TIME(MIN.) = 4.51
Tc(MIN.) = 71.81
SUBAREA AREA(ACRES) = 145.01 SUBAREA RUNOFF(CFS) = 103.69
EFFECTIVE AREA(ACRES) = 2653.51 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA(ACRES) = 2717.6 PEAK FLOW RATE(CFS) = 1924.53
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 4.21

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 4.21 FLOW VELOCITY(FEET/SEC.) = 10.73
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13643.00 = 30784.34 FEET.

FLOW PROCESS FROM NODE 13643.00 TO NODE 13643.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 71.81
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.094
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.89	0.30	1.000	-
USER-DEFINED	-	20.65	0.30	1.000	-
USER-DEFINED	-	2.69	0.30	1.000	-
USER-DEFINED	-	8.45	0.30	1.000	-
USER-DEFINED	-	96.93	0.30	1.000	-
USER-DEFINED	-	13.19	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 142.80 SUBAREA RUNOFF(CFS) = 102.11
EFFECTIVE AREA(ACRES) = 2796.31 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA(ACRES) = 2860.4 PEAK FLOW RATE(CFS) = 2026.64

FLOW PROCESS FROM NODE 13643.00 TO NODE 13643.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 71.81
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.094
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	42.54	0.30	1.000	-
USER-DEFINED	-	16.96	0.30	1.000	-
USER-DEFINED	-	80.60	0.30	1.000	-
USER-DEFINED	-	1.56	0.30	1.000	-
USER-DEFINED	-	2.00	0.30	1.000	-
USER-DEFINED	-	3.11	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 146.77 SUBAREA RUNOFF(CFS) = 104.95
 EFFECTIVE AREA(ACRES) = 2943.08 AREA-AVERAGED Fm(INCH/HR) = 0.29
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA(ACRES) = 3007.2 PEAK FLOW RATE(CFS) = 2131.59

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2201.63	31.72	1.662	0.30(0.29)	0.98	1786.2	20100.00
2	2183.27	37.09	1.523	0.30(0.29)	0.97	1971.9	13600.00
3	2131.59	71.81	1.094	0.30(0.29)	0.97	2943.1	13510.00
4	2022.39	80.42	1.036	0.30(0.29)	0.96	3007.2	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2201.63 Tc(MIN.) = 31.72
 AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.98 EFFECTIVE AREA(ACRES) = 1786.18

FLOW PROCESS FROM NODE 13643.00 TO NODE 13660.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 342.39 DOWNSTREAM(FEET) = 300.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1591.23 CHANNEL SLOPE = 0.0266
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 4.10

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.609

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.89	0.30	1.000	-
USER-DEFINED	-	23.73	0.30	1.000	-
USER-DEFINED	-	0.27	0.30	1.000	-
USER-DEFINED	-	19.87	0.30	1.000	-
USER-DEFINED	-	6.40	0.30	1.000	-
USER-DEFINED	-	3.14	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2233.62

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.88

AVERAGE FLOW DEPTH(FEET) = 4.10 TRAVEL TIME(MIN.) = 2.06

Tc(MIN.) = 33.78

SUBAREA AREA(ACRES) = 54.30 SUBAREA RUNOFF(CFS) = 63.97
 EFFECTIVE AREA(ACRES) = 1840.48 AREA-AVERAGED Fm(INCH/HR) = 0.29
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
 TOTAL AREA(ACRES) = 3061.5 PEAK FLOW RATE(CFS) = 2201.63
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 4.06

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 4.06 FLOW VELOCITY(FEET/SEC.) = 12.84

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 32375.57 FEET.

FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 33.78
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.609
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.67	0.30	1.000	-
USER-DEFINED	-	9.52	0.30	1.000	-
USER-DEFINED	-	0.71	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	39.42	0.30	1.000	-
USER-DEFINED	-	0.62	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 51.16 SUBAREA RUNOFF(CFS) = 60.27

EFFECTIVE AREA(ACRES) = 1891.64 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98

TOTAL AREA(ACRES) = 3112.6 PEAK FLOW RATE(CFS) = 2239.80

FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 33.78
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.609
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.11	0.30	1.000	-
USER-DEFINED	-	0.77	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	2.69	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 3.79 SUBAREA RUNOFF(CFS) = 4.46

EFFECTIVE AREA(ACRES) = 1895.43 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98

TOTAL AREA(ACRES) = 3116.4 PEAK FLOW RATE(CFS) = 2244.27

```

*****
FLOW PROCESS FROM NODE 13643.00 TO NODE 13660.00 IS CODE = 12
-----
>>>>CLEAR MEMORY BANK # 1 <<<<<
=====
*****
FLOW PROCESS FROM NODE 13659.00 TO NODE 13659.00 IS CODE = 15.1
-----
>>>>DEFINE MEMORY BANK # 1 <<<<<
=====
PEAK FLOWRATE TABLE FILE NAME: 2P50EVAA.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:
STREAM      Q      Tc      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES)  NODE
1           528.88  14.09  0.30( 0.11) 0.36    173.1   110.00
2           529.33  16.63  0.30( 0.11) 0.37    204.3   100.00
3           521.87  17.83  0.30( 0.11) 0.38    213.9   100.00
4           463.87  20.89  0.30( 0.12) 0.40    221.1   130.00
TOTAL AREA(ACRES) =      221.1
*****
FLOW PROCESS FROM NODE 13659.00 TO NODE 13660.00 IS CODE = 31
-----
>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 338.00 DOWNSTREAM(FEET) = 300.00
FLOW LENGTH(FEET) = 881.07 MANNING'S N = 0.013
DEPTH OF FLOW IN 108.0 INCH PIPE IS 81.0 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 43.83
ESTIMATED PIPE DIAMETER(INCH) = 108.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 2244.27
PIPE TRAVEL TIME(MIN.) = 0.34 Tc(MIN.) = 34.11
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.
*****
FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 11
-----
>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<
=====
** MAIN STREAM CONFLUENCE DATA **
STREAM      Q      Tc      Intensity  Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES)  NODE
1           2244.27  34.11  1.600  0.30( 0.29) 0.98    1895.4  20100.00
2           2202.96  39.49  1.460  0.30( 0.29) 0.98    2081.1  13600.00
3           2171.20  74.23  1.078  0.30( 0.29) 0.97    3052.3  13510.00
4           2054.87  82.88  1.020  0.30( 0.29) 0.97    3116.4  13500.00
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.
** MEMORY BANK # 1 CONFLUENCE DATA **
STREAM      Q      Tc      Intensity  Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES)  NODE
1           528.88  14.09  2.758  0.30( 0.11) 0.36    173.1   110.00
2           529.33  16.63  2.477  0.30( 0.11) 0.37    204.3   100.00
3           521.87  17.83  2.374  0.30( 0.11) 0.38    213.9   100.00
4           463.87  20.89  2.138  0.30( 0.12) 0.40    221.1   130.00

```

```

LONGEST FLOWPATH FROM NODE 130.00 TO NODE 13660.00 = 6327.50 FEET.
** PEAK FLOW RATE TABLE **
STREAM      Q      Tc      Intensity  Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES)  NODE
1           2276.62  14.09  2.758  0.30( 0.26) 0.87    955.9   110.00
2           2357.12  16.63  2.477  0.30( 0.26) 0.87    1128.4  100.00
3           2390.18  17.83  2.374  0.30( 0.26) 0.87    1204.9  100.00
4           2404.22  20.89  2.138  0.30( 0.27) 0.89    1381.9  130.00
5           2584.45  34.11  1.600  0.30( 0.28) 0.92    2116.5  20100.00
6           2510.99  39.49  1.460  0.30( 0.28) 0.92    2302.2  13600.00
7           2391.39  74.23  1.078  0.30( 0.28) 0.93    3273.4  13510.00
8           2261.67  82.88  1.020  0.30( 0.28) 0.93    3337.5  13500.00
TOTAL AREA(ACRES) =      3337.5
COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
PEAK FLOW RATE(CFS) = 2584.45 Tc(MIN.) = 34.110
EFFECTIVE AREA(ACRES) = 2116.53 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.87
TOTAL AREA(ACRES) = 3337.5
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.
*****
FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====
MAINLINE Tc(MIN.) = 34.11
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.600
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL      AREA      Fp      Ap      SCS
LAND USE                GROUP (ACRES) (INCH/HR) (DECIMAL) CN
AGRICULTURAL POOR COVER
"FALLOW"                B           1.11    0.30    1.000   86
AGRICULTURAL POOR COVER
"FALLOW"                B           0.44    0.30    1.000   86
NATURAL FAIR COVER
"GRASS"                  B           1.49    0.30    1.000   69
NATURAL FAIR COVER
"GRASS"                  B           1.70    0.30    1.000   69
NATURAL FAIR COVER
"OPEN BRUSH"            B           1.09    0.30    1.000   66
NATURAL FAIR COVER
"OPEN BRUSH"            B           18.57   0.30    1.000   66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 24.40 SUBAREA RUNOFF(CFS) = 28.55
EFFECTIVE AREA(ACRES) = 2140.93 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 3361.9 PEAK FLOW RATE(CFS) = 2584.45
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
*****
FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====
MAINLINE Tc(MIN.) = 34.11

```

* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.600
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL FAIR COVER "ORCHARDS"	B	12.39	0.30	1.000	65
AGRICULTURAL FAIR COVER "ORCHARDS"	B	2.30	0.30	1.000	65
AGRICULTURAL POOR COVER "ROW CROPS, CONTOURED"	B	5.19	0.30	1.000	79
AGRICULTURAL POOR COVER "ROW CROPS, STRAIGHT ROW"	B	28.71	0.30	1.000	81
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.17	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 48.76 SUBAREA RUNOFF (CFS) = 57.06
 EFFECTIVE AREA (ACRES) = 2189.69 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA (ACRES) = 3410.7 PEAK FLOW RATE (CFS) = 2609.48

 FLOW PROCESS FROM NODE 13660.00 TO NODE 13680.00 IS CODE = 56

>>>> COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>> TRAVELTIME THRU SUBAREA<<<<<
 =====

ELEVATION DATA: UPSTREAM (FEET) = 300.00 DOWNSTREAM (FEET) = 288.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 933.89 CHANNEL SLOPE = 0.0128
 GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 * ESTIMATED CHANNEL HEIGHT (FEET) = 5.43
 * 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.561
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	9.23	0.30	1.000	-
USER-DEFINED	-	0.54	0.30	1.000	-
USER-DEFINED	-	5.66	0.30	1.000	-
USER-DEFINED	-	3.66	0.30	1.000	-
USER-DEFINED	-	0.67	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 2620.82
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 10.43
 AVERAGE FLOW DEPTH (FEET) = 5.43 TRAVEL TIME (MIN.) = 1.49
 Tc (MIN.) = 35.60
 SUBAREA AREA (ACRES) = 19.98 SUBAREA RUNOFF (CFS) = 22.68
 EFFECTIVE AREA (ACRES) = 2209.67 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA (ACRES) = 3430.6 PEAK FLOW RATE (CFS) = 2609.48
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 * ESTIMATED CHANNEL HEIGHT (FEET) = 5.41

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 5.41 FLOW VELOCITY (FEET/SEC.) = 10.43
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13680.00 = 34190.53 FEET.

 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>> ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
 =====

MAINLINE Tc (MIN.) = 35.60
 * 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.561
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.56	0.30	1.000	-
USER-DEFINED	-	9.40	0.30	1.000	-
USER-DEFINED	-	2.76	0.30	1.000	-
USER-DEFINED	-	17.38	0.30	1.000	-
USER-DEFINED	-	2.46	0.30	1.000	-
USER-DEFINED	-	5.56	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 39.12 SUBAREA RUNOFF (CFS) = 44.41
 EFFECTIVE AREA (ACRES) = 2248.79 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA (ACRES) = 3469.8 PEAK FLOW RATE (CFS) = 2609.48
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>> ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
 =====

MAINLINE Tc (MIN.) = 35.60
 * 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.561
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.65	0.30	1.000	-
USER-DEFINED	-	1.70	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 2.35 SUBAREA RUNOFF (CFS) = 2.67
 EFFECTIVE AREA (ACRES) = 2251.14 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA (ACRES) = 3472.1 PEAK FLOW RATE (CFS) = 2609.48
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13660.00 TO NODE 13680.00 IS CODE = 12

>>>> CLEAR MEMORY BANK # 3 <<<<<
 =====

 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>> ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
 =====

MAINLINE Tc(MIN.) = 35.60
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.561
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.29	0.30	1.000	-
USER-DEFINED	-	31.25	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	6.26	0.30	1.000	-
USER-DEFINED	-	0.07	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 43.31 SUBAREA RUNOFF(CFS) = 49.17
 EFFECTIVE AREA(ACRES) = 2294.45 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA(ACRES) = 3515.4 PEAK FLOW RATE(CFS) = 2651.97

 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 35.60
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.561
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	2.47	0.30	0.850	-
USER-DEFINED	-	3.06	0.30	0.850	-
USER-DEFINED	-	17.76	0.30	0.500	-
USER-DEFINED	-	7.31	0.30	0.500	-
USER-DEFINED	-	0.34	0.30	1.000	-
USER-DEFINED	-	8.22	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.659
 SUBAREA AREA(ACRES) = 39.16 SUBAREA RUNOFF(CFS) = 48.07
 EFFECTIVE AREA(ACRES) = 2333.61 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA(ACRES) = 3554.6 PEAK FLOW RATE(CFS) = 2700.04

 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 35.60
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.561
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.53	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 0.53 SUBAREA RUNOFF(CFS) = 0.60
 EFFECTIVE AREA(ACRES) = 2334.14 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA(ACRES) = 3555.1 PEAK FLOW RATE(CFS) = 2700.64

 FLOW PROCESS FROM NODE 13680.00 TO NODE 13682.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 288.00 DOWNSTREAM(FEET) = 242.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2860.77 CHANNEL SLOPE = 0.0161
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 5.20
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.453
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	5.28	0.30	1.000	-
USER-DEFINED	-	0.52	0.30	1.000	-
USER-DEFINED	-	3.61	0.30	1.000	-
USER-DEFINED	-	0.67	0.30	1.000	-
USER-DEFINED	-	1.37	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2706.69
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.41
 AVERAGE FLOW DEPTH(FEET) = 5.20 TRAVEL TIME(MIN.) = 4.18
 Tc(MIN.) = 39.78
 SUBAREA AREA(ACRES) = 11.67 SUBAREA RUNOFF(CFS) = 12.11
 EFFECTIVE AREA(ACRES) = 2345.81 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA(ACRES) = 3566.8 PEAK FLOW RATE(CFS) = 2700.64
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 5.19

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 5.19 FLOW VELOCITY(FEET/SEC.) = 11.41
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13682.00 = 37051.30 FEET.

 FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 39.78
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.453
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	6.90	0.30	1.000	-
USER-DEFINED	-	23.04	0.30	1.000	-
USER-DEFINED	-	1.18	0.30	1.000	-
USER-DEFINED	-	1.56	0.30	1.000	-
USER-DEFINED	-	53.20	0.30	1.000	-
USER-DEFINED	-	2.08	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 87.96 SUBAREA RUNOFF (CFS) = 91.26
 EFFECTIVE AREA (ACRES) = 2433.77 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA (ACRES) = 3654.7 PEAK FLOW RATE (CFS) = 2700.64
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) = 39.78
 * 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.453
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.01	0.30	1.000	-
USER-DEFINED	-	0.18	0.30	1.000	-
USER-DEFINED	-	0.38	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	7.73	0.30	1.000	-
USER-DEFINED	-	4.37	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 12.89 SUBAREA RUNOFF (CFS) = 13.37
 EFFECTIVE AREA (ACRES) = 2446.66 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA (ACRES) = 3667.6 PEAK FLOW RATE (CFS) = 2700.64
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) = 39.78
 * 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.453
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "FALLOW"	B	2.57	0.30	1.000	86
AGRICULTURAL POOR COVER "FALLOW"	B	1.97	0.30	1.000	86
NATURAL FAIR COVER "GRASS"	B	1.00	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	2.98	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	2.39	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	1.67	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 12.58 SUBAREA RUNOFF (CFS) = 13.05
 EFFECTIVE AREA (ACRES) = 2459.24 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92

TOTAL AREA (ACRES) = 3680.2 PEAK FLOW RATE (CFS) = 2700.64
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) = 39.78
 * 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.453
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	0.44	0.30	1.000	66
PUBLIC PARK	B	2.65	0.30	0.850	56
PUBLIC PARK	B	1.16	0.30	0.850	56
RESIDENTIAL "5-7 DWELLINGS/ACRE"	B	0.47	0.30	0.500	56
RESIDENTIAL "5-7 DWELLINGS/ACRE"	B	0.25	0.30	0.500	56
AGRICULTURAL POOR COVER "ROW CROPS, STRAIGHT ROW"	B	20.24	0.30	1.000	81

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.963
 SUBAREA AREA (ACRES) = 25.21 SUBAREA RUNOFF (CFS) = 26.41
 EFFECTIVE AREA (ACRES) = 2484.45 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA (ACRES) = 3705.4 PEAK FLOW RATE (CFS) = 2700.64
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) = 39.78
 * 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.453
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.08	0.30	1.000	-
USER-DEFINED	-	6.75	0.30	1.000	-
USER-DEFINED	-	0.02	0.30	1.000	-
USER-DEFINED	-	0.93	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA (ACRES) = 14.78 SUBAREA RUNOFF (CFS) = 15.33
 EFFECTIVE AREA (ACRES) = 2499.23 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA (ACRES) = 3720.2 PEAK FLOW RATE (CFS) = 2700.64
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

 FLOW PROCESS FROM NODE 13682.00 TO NODE 13683.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<

```

=====
ELEVATION DATA: UPSTREAM(FEET) = 242.00 DOWNSTREAM(FEET) = 208.53
CHANNEL LENGTH THRU SUBAREA(FEET) = 2526.22 CHANNEL SLOPE = 0.0132
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 5.49
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.387
SUBAREA LOSS RATE DATA(AMC II):
  DEVELOPMENT TYPE/    SCS SOIL  AREA      Fp      Ap    SCS
    LAND USE          GROUP  (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED          -         8.49    0.30    1.000  -
USER-DEFINED          -        13.31    0.30    1.000  -
USER-DEFINED          -         0.87    0.30    1.000  -
USER-DEFINED          -        20.26    0.30    1.000  -
USER-DEFINED          -         1.21    0.30    1.000  -
USER-DEFINED          -         0.05    0.30    1.000  -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2722.25
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.67
AVERAGE FLOW DEPTH(FEET) = 5.49 TRAVEL TIME(MIN.) = 3.95
Tc(MIN.) = 43.73
SUBAREA AREA(ACRES) = 44.19 SUBAREA RUNOFF(CFS) = 43.22
EFFECTIVE AREA(ACRES) = 2543.42 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 3764.4 PEAK FLOW RATE(CFS) = 2700.64
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 5.47

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 5.47 FLOW VELOCITY(FEET/SEC.) = 10.64
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13683.00 = 39577.52 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

```

```

=====
MAINLINE Tc(MIN.) = 43.73
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.387
SUBAREA LOSS RATE DATA(AMC II):
  DEVELOPMENT TYPE/    SCS SOIL  AREA      Fp      Ap    SCS
    LAND USE          GROUP  (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED          -        12.56    0.30    1.000  -
USER-DEFINED          -         0.81    0.30    1.000  -
USER-DEFINED          -         0.01    0.30    1.000  -
USER-DEFINED          -         1.11    0.30    1.000  -
USER-DEFINED          -         0.59    0.30    1.000  -
USER-DEFINED          -         3.04    0.30    1.000  -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 18.12 SUBAREA RUNOFF(CFS) = 17.72
EFFECTIVE AREA(ACRES) = 2561.54 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 3782.5 PEAK FLOW RATE(CFS) = 2700.64
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

```

```

=====
MAINLINE Tc(MIN.) = 43.73
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.387
SUBAREA LOSS RATE DATA(AMC II):
  DEVELOPMENT TYPE/    SCS SOIL  AREA      Fp      Ap    SCS
    LAND USE          GROUP  (ACRES) (INCH/HR) (DECIMAL) CN
RESIDENTIAL
"8-10 DWELLINGS/ACRE" B         0.10    0.30    0.400  56
PUBLIC PARK          B         1.30    0.30    0.850  56
RESIDENTIAL
"8-10 DWELLINGS/ACRE" B         0.10    0.30    0.400  56
PUBLIC PARK          B         1.70    0.30    0.850  56
PUBLIC PARK          B         0.10    0.30    0.850  56
PUBLIC PARK          B         2.90    0.30    0.850  56
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.835
SUBAREA AREA(ACRES) = 6.20 SUBAREA RUNOFF(CFS) = 6.34
EFFECTIVE AREA(ACRES) = 2567.74 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 3788.7 PEAK FLOW RATE(CFS) = 2700.64
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

```

```

=====
MAINLINE Tc(MIN.) = 43.73
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.387
SUBAREA LOSS RATE DATA(AMC II):
  DEVELOPMENT TYPE/    SCS SOIL  AREA      Fp      Ap    SCS
    LAND USE          GROUP  (ACRES) (INCH/HR) (DECIMAL) CN
RESIDENTIAL
"5-7 DWELLINGS/ACRE" B         0.10    0.30    0.500  56
CONDOMINIUMS        B         0.10    0.30    0.350  56
PUBLIC PARK          B         6.90    0.30    0.850  56
PUBLIC PARK          B         0.40    0.30    0.850  56
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.839
SUBAREA AREA(ACRES) = 7.50 SUBAREA RUNOFF(CFS) = 7.66
EFFECTIVE AREA(ACRES) = 2575.24 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 3796.2 PEAK FLOW RATE(CFS) = 2700.64
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13682.00 TO NODE 13683.00 IS CODE = 12

```

```

>>>>CLEAR MEMORY BANK # 3 <<<<

```

```

***MEMORY BANK # 3 IS EMPTY - PROCESS IGNORED.***

```

```

*****

```

FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 43.73
 * 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.387
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "FALLOW"	B	2.55	0.30	1.000	86
AGRICULTURAL POOR COVER "FALLOW"	B	0.01	0.30	1.000	86
AGRICULTURAL POOR COVER "FALLOW"	B	1.35	0.30	1.000	86
NATURAL FAIR COVER "GRASS"	B	0.44	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	0.67	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	1.06	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 6.08 SUBAREA RUNOFF(CFS) = 5.95
 EFFECTIVE AREA(ACRES) = 2581.32 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 3802.3 PEAK FLOW RATE(CFS) = 2700.64
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 43.73
 * 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.387
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	2.16	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	2.45	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	6.15	0.30	1.000	66
AGRICULTURAL POOR COVER "ROW CROPS, STRAIGHT ROW"	B	1.34	0.30	1.000	81
AGRICULTURAL POOR COVER "ROW CROPS, STRAIGHT ROW"	B	18.46	0.30	1.000	81
AGRICULTURAL POOR COVER "ROW CROPS, STRAIGHT ROW"	B	4.13	0.30	1.000	81

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 34.69 SUBAREA RUNOFF(CFS) = 33.93
 EFFECTIVE AREA(ACRES) = 2616.01 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 3837.0 PEAK FLOW RATE(CFS) = 2700.64
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 43.73
 * 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.387
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "ROW CROPS, STRAIGHT ROW"	B	8.69	0.30	1.000	81
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.73	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.41	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND, GRASS"	B	1.37	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND, GRASS"	B	3.11	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA AREA(ACRES) = 14.31 SUBAREA RUNOFF(CFS) = 13.99
 EFFECTIVE AREA(ACRES) = 2630.32 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 3851.3 PEAK FLOW RATE(CFS) = 2700.64
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

FLOW PROCESS FROM NODE 13683.00 TO NODE 13685.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 208.53 DOWNSTREAM(FEET) = 194.24
 CHANNEL LENGTH THRU SUBAREA(FEET) = 289.01 CHANNEL SLOPE = 0.0494
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 3.84
 CHANNEL FLOW THRU SUBAREA(CFS) = 2700.64
 FLOW VELOCITY(FEET/SEC.) = 16.94 FLOW DEPTH(FEET) = 3.84
 TRAVEL TIME(MIN.) = 0.28 Tc(MIN.) = 44.01
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13685.00 = 39866.53 FEET.

FLOW PROCESS FROM NODE 13685.00 TO NODE 13410.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 194.24 DOWNSTREAM(FEET) = 178.72
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1843.57 CHANNEL SLOPE = 0.0084
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT(FEET) = 6.16
 * 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.327
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE SCS SOIL GROUP AREA (ACRES) Fp (INCH/HR) Ap (DECIMAL) SCS CN

USER-DEFINED - 0.23 0.30 1.000 -

USER-DEFINED - 1.52 0.30 1.000 -

USER-DEFINED - 0.06 0.30 1.000 -

USER-DEFINED - 0.13 0.30 1.000 -

USER-DEFINED - 6.45 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2704.52

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.06

AVERAGE FLOW DEPTH(FEET) = 6.16 TRAVEL TIME(MIN.) = 3.39

Tc(MIN.) = 47.40

SUBAREA AREA(ACRES) = 8.39 SUBAREA RUNOFF(CFS) = 7.76

EFFECTIVE AREA(ACRES) = 2638.71 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA(ACRES) = 3859.7 PEAK FLOW RATE(CFS) = 2700.64

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 6.15

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 6.15 FLOW VELOCITY(FEET/SEC.) = 9.06

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13410.00 = 41710.10 FEET.

=====

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 3859.7 TC(MIN.) = 47.40

EFFECTIVE AREA(ACRES) = 2638.71 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.928

PEAK FLOW RATE(CFS) = 2700.64

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2426.61	27.79	1.792	0.30(0.27)	0.90	1478.1	110.00
2	2523.08	30.18	1.702	0.30(0.27)	0.90	1650.5	100.00
3	2535.23	31.37	1.671	0.30(0.27)	0.90	1727.1	100.00
4	2565.50	34.38	1.593	0.30(0.27)	0.91	1904.1	130.00
5	2700.64	47.40	1.327	0.30(0.28)	0.93	2638.7	20100.00
6	2620.76	52.90	1.253	0.30(0.28)	0.93	2824.4	13600.00
7	2498.72	87.84	0.987	0.30(0.28)	0.93	3795.6	13510.00
8	2354.93	96.73	0.943	0.30(0.28)	0.93	3859.7	13500.00

=====

END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2010 Advanced Engineering Software (aes)
Ver. 17.0 Release Date: 07/01/2010 License ID 1527

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 137 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 50-YR EV AUG 2023 ROKAMOTO *

FILE NAME: RU50EV37.DAT
TIME/DATE OF STUDY: 22:19 08/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 50.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.240
- 2) 10.00; 3.389
- 3) 15.00; 2.611
- 4) 20.00; 2.187
- 5) 25.00; 1.897
- 6) 30.00; 1.705
- 7) 40.00; 1.446
- 8) 50.00; 1.284
- 9) 60.00; 1.172
- 10) 90.00; 0.970
- 11) 120.00; 0.840
- 12) 180.00; 0.715
- 13) 360.00; 0.524
- 14) 1200.00; 0.229

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU50EV34.DNA
MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24533.17	15.08	0.30 (0.24)	0.80	4345.8	300.00
2	26763.49	20.13	0.30 (0.24)	0.80	5958.1	210.00
3	29451.55	28.14	0.30 (0.24)	0.80	8519.3	110.00
4	31689.85	34.72	0.30 (0.24)	0.81	11309.7	130.00
5	34836.98	44.18	0.30 (0.25)	0.83	15865.1	50260.00
6	36909.91	53.22	0.30 (0.26)	0.86	20576.7	13600.00
7	39428.75	66.42	0.30 (0.26)	0.88	27208.9	13100.00
8	40171.05	73.15	0.30 (0.27)	0.89	30179.5	11801.00
9	42787.12	88.15	0.30 (0.27)	0.91	38289.6	13510.00
10	44630.46	97.04	0.30 (0.28)	0.92	44277.3	13500.00
11	45523.99	101.52	0.30 (0.28)	0.92	47277.8	10800.00
12	45976.14	105.72	0.30 (0.28)	0.93	50223.1	11130.00
13	45491.99	115.33	0.30 (0.28)	0.93	55264.4	12410.00
14	44806.63	123.63	0.30 (0.28)	0.94	59003.5	11201.00
15	44331.79	128.62	0.30 (0.28)	0.94	60735.2	12201.00
16	43269.44	135.72	0.30 (0.28)	0.94	62592.3	12231.00
17	41923.64	143.58	0.30 (0.28)	0.94	64226.6	10400.00
18	40532.40	151.58	0.30 (0.28)	0.94	65521.7	12010.00
19	39310.37	157.60	0.30 (0.28)	0.94	65868.7	10210.00
20	34995.50	185.97	0.30 (0.28)	0.94	66607.1	10100.00
TOTAL AREA(ACRES) =						66607.1

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 14.0

>>>>MEMORY BANK # 3 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24533.17	15.08	0.30 (0.24)	0.80	4345.8	300.00
2	26763.49	20.13	0.30 (0.24)	0.80	5958.1	210.00
3	29451.55	28.14	0.30 (0.24)	0.80	8519.3	110.00
4	31689.85	34.72	0.30 (0.24)	0.81	11309.7	130.00
5	34836.98	44.18	0.30 (0.25)	0.83	15865.1	50260.00
6	36909.91	53.22	0.30 (0.26)	0.86	20576.7	13600.00
7	39428.75	66.42	0.30 (0.26)	0.88	27208.9	13100.00
8	40171.05	73.15	0.30 (0.27)	0.89	30179.5	11801.00
9	42787.12	88.15	0.30 (0.27)	0.91	38289.6	13510.00
10	44630.46	97.04	0.30 (0.28)	0.92	44277.3	13500.00
11	45523.99	101.52	0.30 (0.28)	0.92	47277.8	10800.00
12	45976.14	105.72	0.30 (0.28)	0.93	50223.1	11130.00
13	45491.99	115.33	0.30 (0.28)	0.93	55264.4	12410.00

14 44806.63 123.63 0.30(0.28) 0.94 59003.5 11201.00
 15 44331.79 128.62 0.30(0.28) 0.94 60735.2 12201.00
 16 43269.44 135.72 0.30(0.28) 0.94 62592.3 12231.00
 17 41923.64 143.58 0.30(0.28) 0.94 64226.6 10400.00
 18 40532.40 151.58 0.30(0.28) 0.94 65521.7 12010.00
 19 39310.37 157.60 0.30(0.28) 0.94 65868.7 10210.00
 20 34995.50 185.97 0.30(0.28) 0.94 66607.1 10100.00
 TOTAL AREA(ACRES) = 66607.1

FLOW PROCESS FROM NODE 13700.00 TO NODE 13720.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 170.00 DOWNSTREAM(FEET) = 165.51
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1891.83 CHANNEL SLOPE = 0.0024
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 14.13
 CHANNEL FLOW THRU SUBAREA(CFS) = 45976.14
 FLOW VELOCITY(FEET/SEC.) = 12.02 FLOW DEPTH(FEET) = 14.13
 TRAVEL TIME(MIN.) = 2.62 Tc(MIN.) = 108.35
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126441.05 FEET.

FLOW PROCESS FROM NODE 13700.00 TO NODE 13720.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

FLOW PROCESS FROM NODE 13720.00 TO NODE 13720.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506102C.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm)	Ap	Ae (ACRES)	HEADWATER NODE
1	368.04	14.55	2.681	0.30(0.29)	0.96	189.6	10230.00
2	334.70	24.11	1.948	0.30(0.29)	0.95	240.8	10200.00
3	332.42	24.51	1.925	0.30(0.29)	0.95	241.8	10250.00
4	305.13	28.32	1.769	0.30(0.29)	0.95	246.3	10220.00
TOTAL AREA(ACRES) =							246.3

FLOW PROCESS FROM NODE 13720.00 TO NODE 13720.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm)	Ap	Ae (ACRES)	HEADWATER NODE
1	24533.17	18.28	2.333	0.30(0.24)	0.80	4345.8	300.00
2	26763.49	23.24	1.999	0.30(0.24)	0.80	5958.1	210.00
3	29451.55	31.16	1.675	0.30(0.24)	0.80	8519.3	110.00

4	31689.85	37.67	1.506	0.30(0.24)	0.81	11309.7	130.00
5	34836.98	47.04	1.332	0.30(0.25)	0.83	15865.1	50260.00
6	36909.91	56.03	1.216	0.30(0.26)	0.86	20576.7	13600.00
7	39428.75	69.17	1.110	0.30(0.26)	0.88	27208.9	13100.00
8	40171.05	75.88	1.065	0.30(0.27)	0.89	30179.5	11801.00
9	42787.12	90.83	0.966	0.30(0.27)	0.91	38289.6	13510.00
10	44630.46	99.68	0.928	0.30(0.28)	0.92	44277.3	13500.00
11	45523.99	104.15	0.909	0.30(0.28)	0.92	47277.8	10800.00
12	45976.14	108.35	0.891	0.30(0.28)	0.93	50223.1	11130.00
13	45491.99	117.96	0.849	0.30(0.28)	0.93	55264.4	12410.00
14	44806.63	126.28	0.827	0.30(0.28)	0.94	59003.5	11201.00
15	44331.79	131.27	0.817	0.30(0.28)	0.94	60735.2	12201.00
16	43269.44	138.39	0.802	0.30(0.28)	0.94	62592.3	12231.00
17	41923.64	146.28	0.785	0.30(0.28)	0.94	64226.6	10400.00
18	40532.40	154.31	0.769	0.30(0.28)	0.94	65521.7	12010.00
19	39310.37	160.35	0.756	0.30(0.28)	0.94	65868.7	10210.00
20	34995.50	188.83	0.706	0.30(0.28)	0.94	66607.1	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126441.05 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm)	Ap	Ae (ACRES)	HEADWATER NODE
1	368.04	14.55	2.681	0.30(0.29)	0.96	189.6	10230.00
2	334.70	24.11	1.948	0.30(0.29)	0.95	240.8	10200.00
3	332.42	24.51	1.925	0.30(0.29)	0.95	241.8	10250.00
4	305.13	28.32	1.769	0.30(0.29)	0.95	246.3	10220.00

LONGEST FLOWPATH FROM NODE 10200.00 TO NODE 13720.00 = 9099.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm)	Ap	Ae (ACRES)	HEADWATER NODE
1	23142.47	14.55	2.681	0.30(0.24)	0.81	3647.6	10230.00
2	24888.20	18.28	2.333	0.30(0.24)	0.81	4555.3	300.00
3	27101.24	23.24	1.999	0.30(0.24)	0.81	6194.3	210.00
4	27395.31	24.11	1.948	0.30(0.24)	0.81	6482.1	10200.00
5	27527.39	24.51	1.925	0.30(0.24)	0.81	6611.0	10250.00
6	28793.24	28.32	1.769	0.30(0.24)	0.81	7847.6	10220.00
7	29737.24	31.16	1.675	0.30(0.24)	0.81	8765.5	110.00
8	31940.86	37.67	1.506	0.30(0.24)	0.81	11556.0	130.00
9	35052.11	47.04	1.332	0.30(0.25)	0.83	16111.3	50260.00
10	37101.28	56.03	1.216	0.30(0.26)	0.86	20823.0	13600.00
11	39598.28	69.17	1.110	0.30(0.27)	0.88	27455.2	13100.00
12	40331.29	75.88	1.065	0.30(0.27)	0.89	30425.8	11801.00
13	42927.07	90.83	0.966	0.30(0.27)	0.91	38535.8	13510.00
14	44762.50	99.68	0.928	0.30(0.28)	0.92	44523.6	13500.00
15	45652.05	104.15	0.909	0.30(0.28)	0.92	47524.0	10800.00
16	46100.47	108.35	0.891	0.30(0.28)	0.93	50469.4	11130.00
17	45607.75	117.96	0.849	0.30(0.28)	0.93	55510.6	12410.00
18	44917.88	126.28	0.827	0.30(0.28)	0.94	59249.7	11201.00
19	44440.90	131.27	0.817	0.30(0.28)	0.94	60981.4	12201.00
20	43375.50	138.39	0.802	0.30(0.28)	0.94	62838.6	12231.00
21	42026.32	146.28	0.785	0.30(0.28)	0.94	64472.9	10400.00
22	40631.64	154.31	0.769	0.30(0.28)	0.94	65768.0	12010.00
23	39407.02	160.35	0.756	0.30(0.28)	0.94	66114.9	10210.00
24	35081.80	188.83	0.706	0.30(0.28)	0.94	66853.4	10100.00
TOTAL AREA(ACRES) =							66853.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 46100.47 Tc(MIN.) = 108.346
 EFFECTIVE AREA(ACRES) = 50469.41 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.89
 TOTAL AREA(ACRES) = 66853.4
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126441.05 FEET.

 FLOW PROCESS FROM NODE 13720.00 TO NODE 13740.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 165.51 DOWNSTREAM(FEET) = 161.03
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2067.54 CHANNEL SLOPE = 0.0022
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 14.51
 CHANNEL FLOW THRU SUBAREA(CFS) = 46100.47
 FLOW VELOCITY(FEET/SEC.) = 11.65 FLOW DEPTH(FEET) = 14.51
 TRAVEL TIME(MIN.) = 2.96 Tc(MIN.) = 111.30
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128508.59 FEET.

 FLOW PROCESS FROM NODE 13720.00 TO NODE 13740.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

 FLOW PROCESS FROM NODE 13740.00 TO NODE 13740.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506103C.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	702.74	18.17	0.30(0.23)	0.76	400.0	10300.00
2	704.90	18.97	0.30(0.23)	0.76	413.4	10380.00
3	693.05	21.35	0.30(0.23)	0.76	439.7	10320.00
4	668.71	23.48	0.30(0.23)	0.76	451.6	10360.00
5	629.78	26.35	0.30(0.23)	0.76	460.8	10340.00
TOTAL AREA(ACRES) =						460.8

 FLOW PROCESS FROM NODE 13740.00 TO NODE 13740.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23142.47	18.22	2.338	0.30(0.24)	0.81	3647.6	10230.00
2	24888.20	21.87	2.079	0.30(0.24)	0.81	4555.3	300.00
3	27101.24	26.73	1.830	0.30(0.24)	0.81	6194.3	210.00
4	27395.31	27.59	1.797	0.30(0.24)	0.81	6482.1	10200.00
5	27527.39	27.99	1.782	0.30(0.24)	0.81	6611.0	10250.00

6	28793.24	31.75	1.660	0.30(0.24)	0.81	7847.6	10220.00
7	29737.24	34.55	1.587	0.30(0.24)	0.81	8765.5	110.00
8	31940.86	40.98	1.430	0.30(0.24)	0.81	11556.0	130.00
9	35052.11	50.26	1.281	0.30(0.25)	0.83	16111.3	50260.00
10	37101.28	59.20	1.181	0.30(0.26)	0.86	20823.0	13600.00
11	39598.28	72.27	1.089	0.30(0.27)	0.88	27455.2	13100.00
12	40331.29	78.96	1.044	0.30(0.27)	0.89	30425.8	11801.00
13	42927.07	93.85	0.953	0.30(0.27)	0.91	38535.8	13510.00
14	44762.50	102.67	0.915	0.30(0.28)	0.92	44523.6	13500.00
15	45652.05	107.12	0.896	0.30(0.28)	0.92	47524.0	10800.00
16	46100.47	111.30	0.878	0.30(0.28)	0.93	50469.4	11130.00
17	45607.75	120.93	0.838	0.30(0.28)	0.93	55510.6	12410.00
18	44917.88	129.26	0.821	0.30(0.28)	0.94	59249.7	11201.00
19	44440.90	134.26	0.810	0.30(0.28)	0.94	60981.4	12201.00
20	43375.50	141.40	0.795	0.30(0.28)	0.94	62838.6	12231.00
21	42026.32	149.32	0.779	0.30(0.28)	0.94	64472.9	10400.00
22	40631.64	157.38	0.762	0.30(0.28)	0.94	65768.0	12010.00
23	39407.02	163.45	0.749	0.30(0.28)	0.94	66114.9	10210.00
24	35081.80	192.05	0.702	0.30(0.28)	0.94	66853.4	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128508.59 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	702.74	18.17	2.342	0.30(0.23)	0.76	400.0	10300.00
2	704.90	18.97	2.274	0.30(0.23)	0.76	413.4	10380.00
3	693.05	21.35	2.109	0.30(0.23)	0.76	439.7	10320.00
4	668.71	23.48	1.985	0.30(0.23)	0.76	451.6	10360.00
5	629.78	26.35	1.845	0.30(0.23)	0.76	460.8	10340.00

LONGEST FLOWPATH FROM NODE 10320.00 TO NODE 13740.00 = 8457.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23826.97	18.17	2.342	0.30(0.24)	0.80	4036.8	10300.00
2	23845.36	18.22	2.338	0.30(0.24)	0.80	4048.5	10230.00
3	24205.72	18.97	2.274	0.30(0.24)	0.80	4247.3	10380.00
4	25331.47	21.35	2.109	0.30(0.24)	0.80	4865.1	10320.00
5	25575.27	21.87	2.079	0.30(0.24)	0.80	4997.9	300.00
6	26288.01	23.48	1.985	0.30(0.24)	0.80	5548.4	10360.00
7	27558.85	26.35	1.845	0.30(0.24)	0.80	6527.6	10340.00
8	27725.35	26.73	1.830	0.30(0.24)	0.80	6655.1	210.00
9	28006.53	27.59	1.797	0.30(0.24)	0.80	6942.9	10200.00
10	28132.75	27.99	1.782	0.30(0.24)	0.80	7071.8	10250.00
11	29350.84	31.75	1.660	0.30(0.24)	0.80	8308.4	10220.00
12	30266.54	34.55	1.587	0.30(0.24)	0.80	9226.3	110.00
13	32408.93	40.98	1.430	0.30(0.24)	0.81	12016.8	130.00
14	35462.12	50.26	1.281	0.30(0.25)	0.83	16572.1	50260.00
15	37472.29	59.20	1.181	0.30(0.26)	0.86	21283.8	13600.00
16	39933.57	72.27	1.089	0.30(0.26)	0.88	27916.0	13100.00
17	40649.02	78.96	1.044	0.30(0.27)	0.89	30886.6	11801.00
18	43209.33	93.85	0.953	0.30(0.27)	0.91	38996.6	13510.00
19	45029.88	102.67	0.915	0.30(0.28)	0.92	44984.4	13500.00
20	45911.91	107.12	0.896	0.30(0.28)	0.92	47984.8	10800.00
21	46353.26	111.30	0.878	0.30(0.28)	0.93	50930.2	11130.00
22	45845.10	120.93	0.838	0.30(0.28)	0.93	55971.4	12410.00
23	45148.47	129.26	0.821	0.30(0.28)	0.94	59710.5	11201.00
24	44667.43	134.26	0.810	0.30(0.28)	0.94	61442.2	12201.00

25 43596.22 141.40 0.795 0.30(0.28) 0.94 63299.4 12231.00
26 42240.62 149.32 0.779 0.30(0.28) 0.94 64933.7 10400.00
27 40839.39 157.38 0.762 0.30(0.28) 0.94 66228.8 12010.00
28 39609.84 163.45 0.749 0.30(0.28) 0.94 66575.7 10210.00
29 35266.20 192.05 0.702 0.30(0.28) 0.94 67314.2 10100.00
TOTAL AREA (ACRES) = 67314.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 46353.26 Tc(MIN.) = 111.303
EFFECTIVE AREA(ACRES) = 50930.21 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.88
TOTAL AREA(ACRES) = 67314.2
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128508.59 FEET.

FLOW PROCESS FROM NODE 13740.00 TO NODE 13741.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 161.03 DOWNSTREAM(FEET) = 141.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 364.08 CHANNEL SLOPE = 0.0550
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 8.43
CHANNEL FLOW THRU SUBAREA(CFS) = 46353.26
FLOW VELOCITY(FEET/SEC.) = 41.10 FLOW DEPTH(FEET) = 8.43
TRAVEL TIME(MIN.) = 0.15 Tc(MIN.) = 111.45
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128872.66 FEET.

FLOW PROCESS FROM NODE 13740.00 TO NODE 13741.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

FLOW PROCESS FROM NODE 13741.00 TO NODE 13741.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506104C.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	71.30	19.53	0.30(0.24)	0.80	44.3	10400.00

TOTAL AREA(ACRES) = 44.3

FLOW PROCESS FROM NODE 13741.00 TO NODE 13741.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23826.97	18.35	2.327	0.30(0.24)	0.80	4036.8	10300.00

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
2	23845.36	18.40	2.322	0.30(0.24)	0.80	4048.5	10230.00
3	24205.72	19.15	2.259	0.30(0.24)	0.80	4247.3	10380.00
4	25331.47	21.53	2.098	0.30(0.24)	0.80	4865.1	10320.00
5	25575.27	22.05	2.068	0.30(0.24)	0.80	4997.9	300.00
6	26288.01	23.65	1.975	0.30(0.24)	0.80	5548.4	10360.00
7	27558.85	26.53	1.838	0.30(0.24)	0.80	6527.6	10340.00
8	27725.35	26.91	1.824	0.30(0.24)	0.80	6655.1	210.00
9	28006.53	27.77	1.791	0.30(0.24)	0.80	6942.9	10200.00
10	28132.75	28.16	1.776	0.30(0.24)	0.80	7071.8	10250.00
11	29350.84	31.92	1.655	0.30(0.24)	0.80	8308.4	10220.00
12	30266.54	34.72	1.583	0.30(0.24)	0.80	9226.3	110.00
13	32408.93	41.15	1.427	0.30(0.24)	0.81	12016.8	130.00
14	35462.12	50.42	1.279	0.30(0.25)	0.83	16572.1	50260.00
15	37472.29	59.35	1.179	0.30(0.26)	0.86	21283.8	13600.00
16	39933.57	72.43	1.088	0.30(0.26)	0.88	27916.0	13100.00
17	40649.02	79.12	1.043	0.30(0.27)	0.89	30886.6	11801.00
18	43209.33	94.00	0.953	0.30(0.27)	0.91	38996.6	13510.00
19	45029.88	102.82	0.914	0.30(0.28)	0.92	44984.4	13500.00
20	45911.91	107.27	0.895	0.30(0.28)	0.92	47984.8	10800.00
21	46353.26	111.45	0.877	0.30(0.28)	0.93	50930.2	11130.00
22	45845.10	121.08	0.838	0.30(0.28)	0.93	55971.4	12410.00
23	45148.47	129.41	0.820	0.30(0.28)	0.94	59710.5	11201.00
24	44667.43	134.41	0.810	0.30(0.28)	0.94	61442.2	12201.00
25	43596.22	141.55	0.795	0.30(0.28)	0.94	63299.4	12231.00
26	42240.62	149.47	0.779	0.30(0.28)	0.94	64933.7	10400.00
27	40839.39	157.54	0.762	0.30(0.28)	0.94	66228.8	12010.00
28	39609.84	163.61	0.749	0.30(0.28)	0.94	66575.7	10210.00
29	35266.20	192.21	0.702	0.30(0.28)	0.94	67314.2	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128872.66 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	71.30	19.53	2.227	0.30(0.24)	0.80	44.3	10400.00

LONGEST FLOWPATH FROM NODE 10400.00 TO NODE 13741.00 = 6237.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23897.34	18.35	2.327	0.30(0.24)	0.80	4078.4	10300.00
2	23915.78	18.40	2.322	0.30(0.24)	0.80	4090.3	10230.00
3	24276.78	19.15	2.259	0.30(0.24)	0.80	4290.8	10380.00
4	24457.69	19.53	2.227	0.30(0.24)	0.80	4390.8	10400.00
5	25398.17	21.53	2.098	0.30(0.24)	0.80	4909.4	10320.00
6	25640.89	22.05	2.068	0.30(0.24)	0.80	5042.2	300.00
7	26350.29	23.65	1.975	0.30(0.24)	0.80	5592.7	10360.00
8	27616.23	26.53	1.838	0.30(0.24)	0.80	6571.9	10340.00
9	27782.21	26.91	1.824	0.30(0.24)	0.80	6699.4	210.00
10	28062.19	27.77	1.791	0.30(0.24)	0.80	6987.2	10200.00
11	28187.88	28.16	1.776	0.30(0.24)	0.80	7116.1	10250.00
12	29401.65	31.92	1.655	0.30(0.24)	0.80	8352.7	10220.00
13	30314.75	34.72	1.583	0.30(0.24)	0.80	9270.6	110.00
14	32451.55	41.15	1.427	0.30(0.24)	0.81	12061.1	130.00
15	35499.43	50.42	1.279	0.30(0.25)	0.83	16616.4	50260.00
16	37506.01	59.35	1.179	0.30(0.26)	0.86	21328.1	13600.00
17	39964.04	72.43	1.088	0.30(0.26)	0.88	27960.3	13100.00
18	40677.87	79.12	1.043	0.30(0.27)	0.89	30930.9	11801.00
19	43234.93	94.00	0.953	0.30(0.27)	0.91	39040.9	13510.00

20	45054.11	102.82	0.914	0.30	(0.28)	0.92	45028.7	13500.00
21	45935.45	107.27	0.895	0.30	(0.28)	0.92	48029.1	10800.00
22	46376.14	111.45	0.877	0.30	(0.28)	0.93	50974.5	11130.00
23	45866.57	121.08	0.838	0.30	(0.28)	0.93	56015.7	12410.00
24	45169.32	129.41	0.820	0.30	(0.28)	0.94	59754.8	11201.00
25	44687.90	134.41	0.810	0.30	(0.28)	0.94	61486.5	12201.00
26	43616.16	141.55	0.795	0.30	(0.28)	0.94	63343.7	12231.00
27	42259.96	149.47	0.779	0.30	(0.28)	0.94	64978.0	10400.00
28	40858.13	157.54	0.762	0.30	(0.28)	0.94	66273.1	12010.00
29	39628.13	163.61	0.749	0.30	(0.28)	0.94	66620.0	10210.00
30	35282.80	192.21	0.702	0.30	(0.28)	0.94	67358.5	10100.00

TOTAL AREA (ACRES) = 67358.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 46376.14 Tc (MIN.) = 111.451
EFFECTIVE AREA (ACRES) = 50974.51 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA (ACRES) = 67358.5
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128872.66 FEET.

FLOW PROCESS FROM NODE 13741.00 TO NODE 13802.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 141.00 DOWNSTREAM (FEET) = 135.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 1533.41 CHANNEL SLOPE = 0.0039
GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 17.05
CHANNEL FLOW THRU SUBAREA (CFS) = 46376.14
FLOW VELOCITY (FEET/SEC.) = 16.17 FLOW DEPTH (FEET) = 17.05
TRAVEL TIME (MIN.) = 1.58 Tc (MIN.) = 113.03
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130406.07 FEET.

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<

PEAK FLOWRATE TABLE FILE NAME: 0506105J.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	385.37	14.62	0.30 (0.27)	0.90	207.5	10520.00
2	453.34	31.20	0.30 (0.28)	0.93	403.6	10500.00
TOTAL AREA (ACRES) =						403.6

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23897.34	20.26	2.172	0.30 (0.24)	0.80	4078.4	10300.00
2	23915.78	20.32	2.169	0.30 (0.24)	0.80	4090.3	10230.00
3	24276.78	21.06	2.126	0.30 (0.24)	0.80	4290.8	10380.00
4	24457.69	21.43	2.104	0.30 (0.24)	0.80	4390.8	10400.00
5	25398.17	23.41	1.989	0.30 (0.24)	0.80	4909.4	10320.00
6	25640.89	23.92	1.960	0.30 (0.24)	0.80	5042.2	300.00
7	26350.29	25.51	1.877	0.30 (0.24)	0.80	5592.7	10360.00
8	27616.23	28.36	1.768	0.30 (0.24)	0.80	6571.9	10340.00
9	27782.21	28.73	1.754	0.30 (0.24)	0.80	6699.4	210.00
10	28062.19	29.59	1.721	0.30 (0.24)	0.80	6987.2	10200.00
11	28187.88	29.98	1.706	0.30 (0.24)	0.80	7116.1	10250.00
12	29401.65	33.71	1.609	0.30 (0.24)	0.80	8352.7	10220.00
13	30314.75	36.50	1.537	0.30 (0.24)	0.80	9270.6	110.00
14	32451.55	42.90	1.399	0.30 (0.24)	0.81	12061.1	130.00
15	35499.43	52.12	1.260	0.30 (0.25)	0.83	16616.4	50260.00
16	37506.01	61.03	1.165	0.30 (0.26)	0.86	21328.1	13600.00
17	39964.04	74.07	1.077	0.30 (0.26)	0.88	27960.3	13100.00
18	40677.87	80.76	1.032	0.30 (0.27)	0.89	30930.9	11801.00
19	43234.93	95.62	0.946	0.30 (0.27)	0.91	39040.9	13510.00
20	45054.11	104.41	0.908	0.30 (0.28)	0.92	45028.7	13500.00
21	45935.45	108.85	0.888	0.30 (0.28)	0.92	48029.1	10800.00
22	46376.14	113.03	0.870	0.30 (0.28)	0.93	50974.5	11130.00
23	45866.57	122.66	0.834	0.30 (0.28)	0.93	56015.7	12410.00
24	45169.32	131.00	0.817	0.30 (0.28)	0.94	59754.8	11201.00
25	44687.90	136.01	0.807	0.30 (0.28)	0.94	61486.5	12201.00
26	43616.16	143.16	0.792	0.30 (0.28)	0.94	63343.7	12231.00
27	42259.96	151.09	0.775	0.30 (0.28)	0.94	64978.0	10400.00
28	40858.13	159.18	0.758	0.30 (0.28)	0.94	66273.1	12010.00
29	39628.13	165.26	0.746	0.30 (0.28)	0.94	66620.0	10210.00
30	35282.80	193.92	0.700	0.30 (0.28)	0.94	67358.5	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130406.07 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	385.37	14.62	2.670	0.30 (0.27)	0.90	207.5	10520.00
2	453.34	31.20	1.674	0.30 (0.28)	0.93	403.6	10500.00

LONGEST FLOWPATH FROM NODE 10500.00 TO NODE 13802.00 = 12187.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22078.43	14.62	2.670	0.30 (0.24)	0.81	3150.3	10520.00
2	24305.83	20.26	2.172	0.30 (0.24)	0.81	4352.6	10300.00
3	24324.50	20.32	2.169	0.30 (0.24)	0.81	4365.1	10230.00
4	24688.52	21.06	2.126	0.30 (0.24)	0.81	4574.4	10380.00
5	24870.99	21.43	2.104	0.30 (0.24)	0.81	4678.9	10400.00
6	25819.55	23.41	1.989	0.30 (0.24)	0.81	5220.8	10320.00
7	26064.39	23.92	1.960	0.30 (0.24)	0.81	5359.7	300.00
8	26780.30	25.51	1.877	0.30 (0.24)	0.81	5929.0	10360.00
9	28057.92	28.36	1.768	0.30 (0.24)	0.81	6941.9	10340.00
10	28225.43	28.73	1.754	0.30 (0.24)	0.81	7073.8	210.00

11	28508.93	29.59	1.721	0.30	(0.24)	0.81	7371.7	10200.00
12	28636.21	29.98	1.706	0.30	(0.24)	0.81	7505.3	10250.00
13	29038.88	31.20	1.674	0.30	(0.24)	0.81	7924.8	10500.00
14	29833.87	33.71	1.609	0.30	(0.24)	0.81	8756.3	10220.00
15	30723.52	36.50	1.537	0.30	(0.24)	0.81	9674.2	110.00
16	32815.66	42.90	1.399	0.30	(0.24)	0.81	12464.7	130.00
17	35818.44	52.12	1.260	0.30	(0.25)	0.83	17020.0	50260.00
18	37794.11	61.03	1.165	0.30	(0.26)	0.86	21731.7	13600.00
19	40223.62	74.07	1.077	0.30	(0.26)	0.88	28363.9	13100.00
20	40922.84	80.76	1.032	0.30	(0.27)	0.89	31334.5	11801.00
21	43451.77	95.62	0.946	0.30	(0.27)	0.91	39444.5	13510.00
22	45258.58	104.41	0.908	0.30	(0.28)	0.92	45432.3	13500.00
23	46133.66	108.85	0.888	0.30	(0.28)	0.92	48432.7	10800.00
24	46568.48	113.03	0.870	0.30	(0.28)	0.93	51378.1	11130.00
25	46047.30	122.66	0.834	0.30	(0.28)	0.93	56419.3	12410.00
26	45344.41	131.00	0.817	0.30	(0.28)	0.94	60158.4	11201.00
27	44859.60	136.01	0.807	0.30	(0.28)	0.94	61890.1	12201.00
28	43783.02	143.16	0.792	0.30	(0.28)	0.94	63747.3	12231.00
29	42421.46	151.09	0.775	0.30	(0.28)	0.94	65381.6	10400.00
30	41014.16	159.18	0.758	0.30	(0.28)	0.94	66676.7	12010.00
31	39780.04	165.26	0.746	0.30	(0.28)	0.94	67023.6	10210.00
32	35419.94	193.92	0.700	0.30	(0.28)	0.94	67762.1	10100.00

TOTAL AREA (ACRES) = 67762.1

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 46568.48 Tc (MIN.) = 113.031
EFFECTIVE AREA (ACRES) = 51378.11 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA (ACRES) = 67762.1
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130406.07 FEET.

FLOW PROCESS FROM NODE 13802.00 TO NODE 13803.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 135.00 DOWNSTREAM (FEET) = 133.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 207.23 CHANNEL SLOPE = 0.0097
GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 13.52
CHANNEL FLOW THRU SUBAREA (CFS) = 46568.48
FLOW VELOCITY (FEET/SEC.) = 22.36 FLOW DEPTH (FEET) = 13.52
TRAVEL TIME (MIN.) = 0.15 Tc (MIN.) = 113.19
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130613.30 FEET.

FLOW PROCESS FROM NODE 13802.00 TO NODE 13803.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506106C.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	63.85	17.52	0.30 (0.20)	0.67	36.9	10600.00
TOTAL AREA (ACRES) =			36.9			

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22078.43	14.81	2.640	0.30 (0.24)	0.81	3150.3	10520.00
2	24305.83	20.45	2.161	0.30 (0.24)	0.81	4352.6	10300.00
3	24324.50	20.50	2.158	0.30 (0.24)	0.81	4365.1	10230.00
4	24688.52	21.24	2.115	0.30 (0.24)	0.81	4574.4	10380.00
5	24870.99	21.62	2.093	0.30 (0.24)	0.81	4678.9	10400.00
6	25819.55	23.59	1.979	0.30 (0.24)	0.81	5220.8	10320.00
7	26064.39	24.10	1.949	0.30 (0.24)	0.81	5359.7	300.00
8	26780.30	25.69	1.870	0.30 (0.24)	0.81	5929.0	10360.00
9	28057.92	28.54	1.761	0.30 (0.24)	0.81	6941.9	10340.00
10	28225.43	28.91	1.747	0.30 (0.24)	0.81	7073.8	210.00
11	28508.93	29.77	1.714	0.30 (0.24)	0.81	7371.7	10200.00
12	28636.21	30.16	1.701	0.30 (0.24)	0.81	7505.3	10250.00
13	29038.88	31.38	1.669	0.30 (0.24)	0.81	7924.8	10500.00
14	29833.87	33.89	1.604	0.30 (0.24)	0.81	8756.3	10220.00
15	30723.52	36.68	1.532	0.30 (0.24)	0.81	9674.2	110.00
16	32815.66	43.07	1.396	0.30 (0.24)	0.81	12464.7	130.00
17	35818.44	52.29	1.258	0.30 (0.25)	0.83	17020.0	50260.00
18	37794.11	61.20	1.164	0.30 (0.26)	0.86	21731.7	13600.00
19	40223.62	74.24	1.076	0.30 (0.26)	0.88	28363.9	13100.00
20	40922.84	80.92	1.031	0.30 (0.27)	0.89	31334.5	11801.00
21	43451.77	95.77	0.945	0.30 (0.27)	0.91	39444.5	13510.00
22	45258.58	104.57	0.907	0.30 (0.28)	0.92	45432.3	13500.00
23	46133.66	109.01	0.888	0.30 (0.28)	0.92	48432.7	10800.00
24	46568.48	113.19	0.870	0.30 (0.28)	0.93	51378.1	11130.00
25	46047.30	122.82	0.834	0.30 (0.28)	0.93	56419.3	12410.00
26	45344.41	131.16	0.817	0.30 (0.28)	0.94	60158.4	11201.00
27	44859.60	136.17	0.806	0.30 (0.28)	0.94	61890.1	12201.00
28	43783.02	143.32	0.791	0.30 (0.28)	0.94	63747.3	12231.00
29	42421.46	151.25	0.775	0.30 (0.28)	0.94	65381.6	10400.00
30	41014.16	159.34	0.758	0.30 (0.28)	0.94	66676.7	12010.00
31	39780.04	165.42	0.745	0.30 (0.28)	0.94	67023.6	10210.00
32	35419.94	194.08	0.700	0.30 (0.28)	0.94	67762.1	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130613.30 FEET.

** MEMORY BANK # 3 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	63.85	17.52	2.397	0.30 (0.20)	0.67	36.9	10600.00

LONGEST FLOWPATH FROM NODE 10600.00 TO NODE 13803.00 = 1713.00 FEET.

** PEAK FLOW RATE TABLE **

STREAM	Q	Tc	Intensity	Fp (Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	---------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	22138.38	14.81	2.640	0.30 (0.24)	0.81	3181.5 10520.00
2	23212.24	17.52	2.397	0.30 (0.24)	0.81	3764.8 10600.00
3	24362.81	20.45	2.161	0.30 (0.24)	0.81	4389.5 10300.00
4	24381.39	20.50	2.158	0.30 (0.24)	0.81	4402.0 10230.00
5	24744.16	21.24	2.115	0.30 (0.24)	0.81	4611.3 10380.00
6	24925.99	21.62	2.093	0.30 (0.24)	0.81	4715.8 10400.00
7	25871.24	23.59	1.979	0.30 (0.24)	0.81	5257.7 10320.00
8	26115.21	24.10	1.949	0.30 (0.24)	0.81	5396.6 300.00
9	26828.84	25.69	1.870	0.30 (0.24)	0.81	5965.9 10360.00
10	28103.27	28.54	1.761	0.30 (0.24)	0.81	6978.8 10340.00
11	28270.37	28.91	1.747	0.30 (0.24)	0.81	7110.7 210.00
12	28552.91	29.77	1.714	0.30 (0.24)	0.81	7408.6 10200.00
13	28679.81	30.16	1.701	0.30 (0.24)	0.81	7542.2 10250.00
14	29081.57	31.38	1.669	0.30 (0.24)	0.81	7961.7 10500.00
15	29874.67	33.89	1.604	0.30 (0.24)	0.81	8793.2 10220.00
16	30762.22	36.68	1.532	0.30 (0.24)	0.81	9711.1 110.00
17	32850.41	43.07	1.396	0.30 (0.24)	0.81	12501.6 130.00
18	35849.18	52.29	1.258	0.30 (0.25)	0.83	17056.9 50260.00
19	37822.11	61.20	1.164	0.30 (0.26)	0.86	21768.6 13600.00
20	40249.06	74.24	1.076	0.30 (0.26)	0.88	28400.8 13100.00
21	40946.97	80.92	1.031	0.30 (0.27)	0.89	31371.4 11801.00
22	43473.40	95.77	0.945	0.30 (0.27)	0.91	39481.4 13510.00
23	45279.10	104.57	0.907	0.30 (0.28)	0.92	45469.2 13500.00
24	46153.62	109.01	0.888	0.30 (0.28)	0.92	48469.6 10800.00
25	46587.92	113.19	0.870	0.30 (0.28)	0.93	51415.0 11130.00
26	46065.71	122.82	0.834	0.30 (0.28)	0.93	56456.2 12410.00
27	45362.31	131.16	0.817	0.30 (0.28)	0.94	60195.3 11201.00
28	44877.20	136.17	0.806	0.30 (0.28)	0.94	61927.0 12201.00
29	43800.18	143.32	0.791	0.30 (0.28)	0.94	63784.2 12231.00
30	42438.14	151.25	0.775	0.30 (0.28)	0.94	65418.5 10400.00
31	41030.35	159.34	0.758	0.30 (0.28)	0.94	66713.6 12010.00
32	39795.86	165.42	0.745	0.30 (0.28)	0.94	67060.5 10210.00
33	35434.45	194.08	0.700	0.30 (0.28)	0.94	67799.0 10100.00
TOTAL AREA (ACRES) = 67799.0						

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 46587.92 Tc (MIN.) = 113.185
EFFECTIVE AREA (ACRES) = 51415.01 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
TOTAL AREA (ACRES) = 67799.0
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130613.30 FEET.

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 67799.0 TC (MIN.) = 113.19
EFFECTIVE AREA (ACRES) = 51415.01 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.927
PEAK FLOW RATE (CFS) = 46587.92

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22138.38	14.81	2.640	0.30 (0.24)	0.81	3181.5	10520.00
2	23212.24	17.52	2.397	0.30 (0.24)	0.81	3764.8	10600.00
3	24362.81	20.45	2.161	0.30 (0.24)	0.81	4389.5	10300.00
4	24381.39	20.50	2.158	0.30 (0.24)	0.81	4402.0	10230.00
5	24744.16	21.24	2.115	0.30 (0.24)	0.81	4611.3	10380.00
6	24925.99	21.62	2.093	0.30 (0.24)	0.81	4715.8	10400.00

7	25871.24	23.59	1.979	0.30 (0.24)	0.81	5257.7	10320.00
8	26115.21	24.10	1.949	0.30 (0.24)	0.81	5396.6	300.00
9	26828.84	25.69	1.870	0.30 (0.24)	0.81	5965.9	10360.00
10	28103.27	28.54	1.761	0.30 (0.24)	0.81	6978.8	10340.00
11	28270.37	28.91	1.747	0.30 (0.24)	0.81	7110.7	210.00
12	28552.91	29.77	1.714	0.30 (0.24)	0.81	7408.6	10200.00
13	28679.81	30.16	1.701	0.30 (0.24)	0.81	7542.2	10250.00
14	29081.57	31.38	1.669	0.30 (0.24)	0.81	7961.7	10500.00
15	29874.67	33.89	1.604	0.30 (0.24)	0.81	8793.2	10220.00
16	30762.22	36.68	1.532	0.30 (0.24)	0.81	9711.1	110.00
17	32850.41	43.07	1.396	0.30 (0.24)	0.81	12501.6	130.00
18	35849.18	52.29	1.258	0.30 (0.25)	0.83	17056.9	50260.00
19	37822.11	61.20	1.164	0.30 (0.26)	0.86	21768.6	13600.00
20	40249.06	74.24	1.076	0.30 (0.26)	0.88	28400.8	13100.00
21	40946.97	80.92	1.031	0.30 (0.27)	0.89	31371.4	11801.00
22	43473.40	95.77	0.945	0.30 (0.27)	0.91	39481.4	13510.00
23	45279.10	104.57	0.907	0.30 (0.28)	0.92	45469.2	13500.00
24	46153.62	109.01	0.888	0.30 (0.28)	0.92	48469.6	10800.00
25	46587.92	113.19	0.870	0.30 (0.28)	0.93	51415.0	11130.00
26	46065.71	122.82	0.834	0.30 (0.28)	0.93	56456.2	12410.00
27	45362.31	131.16	0.817	0.30 (0.28)	0.94	60195.3	11201.00
28	44877.20	136.17	0.806	0.30 (0.28)	0.94	61927.0	12201.00
29	43800.18	143.32	0.791	0.30 (0.28)	0.94	63784.2	12231.00
30	42438.14	151.25	0.775	0.30 (0.28)	0.94	65418.5	10400.00
31	41030.35	159.34	0.758	0.30 (0.28)	0.94	66713.6	12010.00
32	39795.86	165.42	0.745	0.30 (0.28)	0.94	67060.5	10210.00
33	35434.45	194.08	0.700	0.30 (0.28)	0.94	67799.0	10100.00

=====
END OF RATIONAL METHOD ANALYSIS
=====

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2010 Advanced Engineering Software (aes)
Ver. 17.0 Release Date: 07/01/2010 License ID 1527

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 138 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 50-YR EV AUG 2023 ROKAMOTO *

FILE NAME: RU50EV38.DAT
TIME/DATE OF STUDY: 22:19 08/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 50.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.225
- 2) 10.00; 3.382
- 3) 15.00; 2.607
- 4) 20.00; 2.184
- 5) 25.00; 1.895
- 6) 30.00; 1.703
- 7) 40.00; 1.444
- 8) 50.00; 1.282
- 9) 60.00; 1.170
- 10) 90.00; 0.968
- 11) 120.00; 0.838
- 12) 180.00; 0.713
- 13) 360.00; 0.522
- 14) 1200.00; 0.227

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RU50EV37.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24925.99	21.62	0.30 (0.24)	0.81	4715.8	10400.00
2	26828.84	25.69	0.30 (0.24)	0.81	5965.9	10360.00
3	30762.22	36.68	0.30 (0.24)	0.81	9711.1	110.00
4	32850.41	43.07	0.30 (0.24)	0.81	12501.6	130.00
5	35849.18	52.29	0.30 (0.25)	0.83	17056.9	50260.00
6	37822.11	61.20	0.30 (0.26)	0.86	21768.6	13600.00
7	40249.06	74.24	0.30 (0.26)	0.88	28400.8	13100.00
8	40946.97	80.92	0.30 (0.27)	0.89	31371.4	11801.00
9	43473.40	95.77	0.30 (0.27)	0.91	39481.4	13510.00
10	45279.10	104.57	0.30 (0.28)	0.92	45469.2	13500.00
11	46153.62	109.01	0.30 (0.28)	0.92	48469.6	10800.00
12	46587.92	113.19	0.30 (0.28)	0.93	51415.0	11130.00
13	46065.71	122.82	0.30 (0.28)	0.93	56456.2	12410.00
14	45362.31	131.16	0.30 (0.28)	0.94	60195.3	11201.00
15	44877.20	136.17	0.30 (0.28)	0.94	61927.0	12201.00
16	43800.18	143.32	0.30 (0.28)	0.94	63784.2	12231.00
17	42438.14	151.25	0.30 (0.28)	0.94	65418.5	10400.00
18	41030.35	159.34	0.30 (0.28)	0.94	66713.6	12010.00
19	39795.86	165.42	0.30 (0.28)	0.94	67060.5	10210.00
20	35434.45	194.08	0.30 (0.28)	0.94	67799.0	10100.00
TOTAL AREA (ACRES) =						67799.0

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 14.0

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24925.99	21.62	0.30 (0.24)	0.81	4715.8	10400.00
2	26828.84	25.69	0.30 (0.24)	0.81	5965.9	10360.00
3	30762.22	36.68	0.30 (0.24)	0.81	9711.1	110.00
4	32850.41	43.07	0.30 (0.24)	0.81	12501.6	130.00
5	35849.18	52.29	0.30 (0.25)	0.83	17056.9	50260.00
6	37822.11	61.20	0.30 (0.26)	0.86	21768.6	13600.00
7	40249.06	74.24	0.30 (0.26)	0.88	28400.8	13100.00
8	40946.97	80.92	0.30 (0.27)	0.89	31371.4	11801.00
9	43473.40	95.77	0.30 (0.27)	0.91	39481.4	13510.00
10	45279.10	104.57	0.30 (0.28)	0.92	45469.2	13500.00
11	46153.62	109.01	0.30 (0.28)	0.92	48469.6	10800.00
12	46587.92	113.19	0.30 (0.28)	0.93	51415.0	11130.00
13	46065.71	122.82	0.30 (0.28)	0.93	56456.2	12410.00

14 45362.31 131.16 0.30(0.28) 0.94 60195.3 11201.00
 15 44877.20 136.17 0.30(0.28) 0.94 61927.0 12201.00
 16 43800.18 143.32 0.30(0.28) 0.94 63784.2 12231.00
 17 42438.14 151.25 0.30(0.28) 0.94 65418.5 10400.00
 18 41030.35 159.34 0.30(0.28) 0.94 66713.6 12010.00
 19 39795.86 165.42 0.30(0.28) 0.94 67060.5 10210.00
 20 35434.45 194.08 0.30(0.28) 0.94 67799.0 10100.00
 TOTAL AREA (ACRES) = 67799.0

 FLOW PROCESS FROM NODE 13803.00 TO NODE 13820.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 134.99 DOWNSTREAM(FEET) = 134.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 926.91 CHANNEL SLOPE = 0.0011
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 23.67
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.861

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	31.44	0.30	0.983	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.983

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 46595.93
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.11
 AVERAGE FLOW DEPTH(FEET) = 23.67 TRAVEL TIME(MIN.) = 1.53
 Tc(MIN.) = 114.71

SUBAREA AREA(ACRES) = 31.44 SUBAREA RUNOFF(CFS) = 16.02
 EFFECTIVE AREA(ACRES) = 51446.45 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA(ACRES) = 67830.4 PEAK FLOW RATE(CFS) = 46587.92
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 23.67

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 23.67 FLOW VELOCITY(FEET/SEC.) = 10.11
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13820.00 = 131540.20 FEET.

 FLOW PROCESS FROM NODE 13803.00 TO NODE 13820.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

=====

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
 TIME OF CONCENTRATION(MIN.) = 114.71
 RAINFALL INTENSITY(INCH/HR) = 0.86
 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.93
 EFFECTIVE STREAM AREA(ACRES) = 51446.45
 TOTAL STREAM AREA(ACRES) = 67830.41

PEAK FLOW RATE(CFS) AT CONFLUENCE = 46587.92

 FLOW PROCESS FROM NODE 13810.00 TO NODE 13811.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 648.54
 ELEVATION DATA: UPSTREAM(FEET) = 756.46 DOWNSTREAM(FEET) = 586.02

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
 SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 12.293
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 3.027

SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	-	5.58	0.30	1.000	65	12.29

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA RUNOFF(CFS) = 13.69
 TOTAL AREA(ACRES) = 5.58 PEAK FLOW RATE(CFS) = 13.69

 FLOW PROCESS FROM NODE 13811.00 TO NODE 13811.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 586.02 DOWNSTREAM(FEET) = 437.69
 CHANNEL LENGTH THRU SUBAREA(FEET) = 696.28 CHANNEL SLOPE = 0.2130
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 0.46
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.739

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	14.79	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 29.95
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.26
 AVERAGE FLOW DEPTH(FEET) = 0.44 TRAVEL TIME(MIN.) = 1.85
 Tc(MIN.) = 14.15

SUBAREA AREA(ACRES) = 14.79 SUBAREA RUNOFF(CFS) = 32.47
 EFFECTIVE AREA(ACRES) = 20.37 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 20.4 PEAK FLOW RATE(CFS) = 44.72
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 0.56

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 0.56 FLOW VELOCITY(FEET/SEC.) = 7.18
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13811.50 = 1344.82 FEET.

```

*****
FLOW PROCESS FROM NODE 13811.50 TO NODE 13812.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 437.69 DOWNSTREAM(FEET) = 402.36
CHANNEL LENGTH THRU SUBAREA(FEET) = 681.04 CHANNEL SLOPE = 0.0519
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.05
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.490
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/    SCS SOIL  AREA      Fp        Ap    SCS
  LAND USE          GROUP  (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED         -      18.41    0.30     1.000   -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 62.88
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.08
AVERAGE FLOW DEPTH(FEET) = 1.03 TRAVEL TIME(MIN.) = 2.23
Tc(MIN.) = 16.38
SUBAREA AREA(ACRES) = 18.41 SUBAREA RUNOFF(CFS) = 36.29
EFFECTIVE AREA(ACRES) = 38.78 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 38.8 PEAK FLOW RATE(CFS) = 76.44
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.15

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.15 FLOW VELOCITY(FEET/SEC.) = 5.41
LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13812.00 = 2025.86 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13812.00 TO NODE 13813.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 402.36 DOWNSTREAM(FEET) = 259.72
CHANNEL LENGTH THRU SUBAREA(FEET) = 1282.56 CHANNEL SLOPE = 0.1112
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.10
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.254
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/    SCS SOIL  AREA      Fp        Ap    SCS
  LAND USE          GROUP  (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED         -      27.87    0.30     0.858   -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.858
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 101.51
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.66
AVERAGE FLOW DEPTH(FEET) = 1.09 TRAVEL TIME(MIN.) = 2.79
Tc(MIN.) = 19.17
SUBAREA AREA(ACRES) = 27.87 SUBAREA RUNOFF(CFS) = 50.08
EFFECTIVE AREA(ACRES) = 66.65 AREA-AVERAGED Fm(INCH/HR) = 0.28

```

```

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94
TOTAL AREA(ACRES) = 66.7 PEAK FLOW RATE(CFS) = 118.29
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.19

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.19 FLOW VELOCITY(FEET/SEC.) = 8.05
LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13813.00 = 3308.42 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 31
-----

```

```

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<
=====

```

```

ELEVATION DATA: UPSTREAM(FEET) = 259.72 DOWNSTREAM(FEET) = 137.00
FLOW LENGTH(FEET) = 2412.88 MANNING'S N = 0.013
DEPTH OF FLOW IN 36.0 INCH PIPE IS 25.0 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 22.57
ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 118.29
PIPE TRAVEL TIME(MIN.) = 1.78 Tc(MIN.) = 20.95
LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13820.00 = 5721.30 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 20.95
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.129
SUBAREA LOSS RATE DATA(AMC II):

```

```

DEVELOPMENT TYPE/    SCS SOIL  AREA      Fp        Ap    SCS
  LAND USE          GROUP  (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED         -      83.64    0.30     0.570   -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.570
SUBAREA AREA(ACRES) = 83.64 SUBAREA RUNOFF(CFS) = 147.39
EFFECTIVE AREA(ACRES) = 150.29 AREA-AVERAGED Fm(INCH/HR) = 0.22
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.73
TOTAL AREA(ACRES) = 150.3 PEAK FLOW RATE(CFS) = 258.17

```

```

*****
FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 1
-----

```

```

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<
=====

```

```

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 20.95
RAINFALL INTENSITY(INCH/HR) = 2.13
AREA-AVERAGED Fm(INCH/HR) = 0.22
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.73
EFFECTIVE STREAM AREA(ACRES) = 150.29
TOTAL STREAM AREA(ACRES) = 150.29

```

PEAK FLOW RATE(CFS) AT CONFLUENCE = 258.17

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24925.99	23.43	1.986	0.30 (0.24)	0.81	4747.2	10400.00
1	26828.84	27.47	1.800	0.30 (0.24)	0.81	5997.3	10360.00
1	30762.22	38.39	1.486	0.30 (0.24)	0.81	9742.6	110.00
1	32850.41	44.75	1.367	0.30 (0.24)	0.81	12533.0	130.00
1	35849.18	53.93	1.238	0.30 (0.25)	0.83	17088.4	50260.00
1	37822.11	62.81	1.151	0.30 (0.26)	0.86	21800.0	13600.00
1	40249.06	75.82	1.063	0.30 (0.26)	0.88	28432.2	13100.00
1	40946.97	82.50	1.019	0.30 (0.27)	0.89	31402.8	11801.00
1	43473.40	97.33	0.936	0.30 (0.27)	0.91	39512.9	13510.00
1	45279.10	106.11	0.898	0.30 (0.28)	0.92	45500.6	13500.00
1	46153.62	110.54	0.879	0.30 (0.28)	0.92	48501.1	10800.00
1	46587.92	114.71	0.861	0.30 (0.28)	0.93	51446.4	11130.00
1	46065.71	124.35	0.829	0.30 (0.28)	0.93	56487.7	12410.00
1	45362.31	132.69	0.812	0.30 (0.28)	0.94	60226.8	11201.00
1	44877.20	137.71	0.801	0.30 (0.28)	0.94	61958.5	12201.00
1	43800.18	144.87	0.786	0.30 (0.28)	0.94	63815.6	12231.00
1	42438.14	152.82	0.770	0.30 (0.28)	0.94	65449.9	10400.00
1	41030.35	160.92	0.753	0.30 (0.28)	0.94	66745.0	12010.00
1	39795.86	167.02	0.740	0.30 (0.28)	0.94	67092.0	10210.00
1	35434.45	195.73	0.696	0.30 (0.28)	0.94	67830.4	10100.00
2	258.17	20.95	2.129	0.30 (0.22)	0.73	150.3	13810.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24379.56	20.95	2.129	0.30 (0.24)	0.81	4395.2	13810.00
2	25164.78	23.43	1.986	0.30 (0.24)	0.81	4897.5	10400.00
3	27042.53	27.47	1.800	0.30 (0.24)	0.81	6147.6	10360.00
4	30933.39	38.39	1.486	0.30 (0.24)	0.81	9892.9	110.00
5	33005.52	44.75	1.367	0.30 (0.24)	0.81	12683.3	130.00
6	35986.84	53.93	1.238	0.30 (0.25)	0.83	17238.7	50260.00
7	37948.01	62.81	1.151	0.30 (0.26)	0.86	21950.3	13600.00
8	40363.11	75.82	1.063	0.30 (0.26)	0.88	28582.5	13100.00
9	41054.95	82.50	1.019	0.30 (0.27)	0.89	31553.1	11801.00
10	43570.25	97.33	0.936	0.30 (0.27)	0.91	39663.2	13510.00
11	45370.80	106.11	0.898	0.30 (0.28)	0.92	45650.9	13500.00
12	46242.73	110.54	0.879	0.30 (0.28)	0.92	48651.4	10800.00
13	46674.57	114.71	0.861	0.30 (0.28)	0.93	51596.7	11130.00
14	46148.04	124.35	0.829	0.30 (0.28)	0.93	56637.9	12410.00
15	45442.29	132.69	0.812	0.30 (0.28)	0.94	60377.1	11201.00
16	44955.76	137.71	0.801	0.30 (0.28)	0.94	62108.8	12201.00
17	43876.73	144.87	0.786	0.30 (0.28)	0.94	63965.9	12231.00
18	42512.45	152.82	0.770	0.30 (0.28)	0.94	65600.2	10400.00
19	41102.38	160.92	0.753	0.30 (0.28)	0.94	66895.3	12010.00
20	39866.17	167.02	0.740	0.30 (0.28)	0.94	67242.2	10210.00
21	35498.84	195.73	0.696	0.30 (0.28)	0.94	67980.7	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 46674.57 Tc(MIN.) = 114.71
EFFECTIVE AREA(ACRES) = 51596.74 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA(ACRES) = 67980.7

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13820.00 = 131540.20 FEET.

FLOW PROCESS FROM NODE 13820.00 TO NODE 13840.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 137.00 DOWNSTREAM(FEET) = 133.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 1261.34 CHANNEL SLOPE = 0.0032

GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT(FEET) = 18.05

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.855

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS

LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

USER-DEFINED - 31.60 0.30 0.683 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.683

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 46683.82

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 15.02

AVERAGE FLOW DEPTH(FEET) = 18.05 TRAVEL TIME(MIN.) = 1.40

Tc(MIN.) = 116.11

SUBAREA AREA(ACRES) = 31.60 SUBAREA RUNOFF(CFS) = 18.49

EFFECTIVE AREA(ACRES) = 51628.34 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA(ACRES) = 68012.3 PEAK FLOW RATE(CFS) = 46674.57

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030

*ESTIMATED CHANNEL HEIGHT(FEET) = 18.05

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 18.05 FLOW VELOCITY(FEET/SEC.) = 15.02

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13840.00 = 132801.55 FEET.

FLOW PROCESS FROM NODE 13820.00 TO NODE 13840.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

TOTAL NUMBER OF STREAMS = 2

CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:

TIME OF CONCENTRATION(MIN.) = 116.11

RAINFALL INTENSITY(INCH/HR) = 0.85

AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.93

EFFECTIVE STREAM AREA(ACRES) = 51628.34

TOTAL STREAM AREA(ACRES) = 68012.30

PEAK FLOW RATE(CFS) AT CONFLUENCE = 46674.57

FLOW PROCESS FROM NODE 13830.00 TO NODE 13831.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<

>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH (FEET) = 744.71
ELEVATION DATA: UPSTREAM (FEET) = 1100.95 DOWNSTREAM (FEET) = 959.21

Tc = K * [(LENGTH ** 3.00) / (ELEVATION CHANGE)] ** 0.20

SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 13.858

* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 2.784

SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)

NATURAL FAIR COVER

"CHAPARRAL, BROADLEAF" - 5.06 0.30 1.000 65 13.86

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

SUBAREA RUNOFF (CFS) = 11.31

TOTAL AREA (ACRES) = 5.06 PEAK FLOW RATE (CFS) = 11.31

FLOW PROCESS FROM NODE 13831.00 TO NODE 13832.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 959.21 DOWNSTREAM (FEET) = 832.83

CHANNEL LENGTH THRU SUBAREA (FEET) = 1076.71 CHANNEL SLOPE = 0.1174

GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

* ESTIMATED CHANNEL HEIGHT (FEET) = 0.69

* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 2.443

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

USER-DEFINED - 32.57 0.30 1.000 -

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 42.87

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.82

AVERAGE FLOW DEPTH (FEET) = 0.65 TRAVEL TIME (MIN.) = 3.08

Tc (MIN.) = 16.94

SUBAREA AREA (ACRES) = 32.57 SUBAREA RUNOFF (CFS) = 62.82

EFFECTIVE AREA (ACRES) = 37.63 AREA-AVERAGED Fm (INCH/HR) = 0.30

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA (ACRES) = 37.6 PEAK FLOW RATE (CFS) = 72.58

GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

* ESTIMATED CHANNEL HEIGHT (FEET) = 0.88

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 0.88 FLOW VELOCITY (FEET/SEC.) = 6.99

LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13832.00 = 1821.42 FEET.

FLOW PROCESS FROM NODE 13832.00 TO NODE 13833.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 832.83 DOWNSTREAM (FEET) = 572.49
CHANNEL LENGTH THRU SUBAREA (FEET) = 1883.58 CHANNEL SLOPE = 0.1382
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
* ESTIMATED CHANNEL HEIGHT (FEET) = 1.03
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 2.139
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 32.23 0.30 1.000 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 99.30
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.18
AVERAGE FLOW DEPTH (FEET) = 1.01 TRAVEL TIME (MIN.) = 3.84
Tc (MIN.) = 20.78
SUBAREA AREA (ACRES) = 32.23 SUBAREA RUNOFF (CFS) = 53.35
EFFECTIVE AREA (ACRES) = 69.86 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 69.9 PEAK FLOW RATE (CFS) = 115.63
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
* ESTIMATED CHANNEL HEIGHT (FEET) = 1.10

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 1.10 FLOW VELOCITY (FEET/SEC.) = 8.59

LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13833.00 = 3705.00 FEET.

FLOW PROCESS FROM NODE 13833.00 TO NODE 13834.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 572.49 DOWNSTREAM (FEET) = 471.65

CHANNEL LENGTH THRU SUBAREA (FEET) = 943.78 CHANNEL SLOPE = 0.1068

GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

* ESTIMATED CHANNEL HEIGHT (FEET) = 1.32

* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 2.030

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

USER-DEFINED - 27.51 0.30 1.000 -

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 137.05

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.31

AVERAGE FLOW DEPTH (FEET) = 1.31 TRAVEL TIME (MIN.) = 1.89

Tc (MIN.) = 22.67

SUBAREA AREA (ACRES) = 27.51 SUBAREA RUNOFF (CFS) = 42.83

EFFECTIVE AREA (ACRES) = 97.37 AREA-AVERAGED Fm (INCH/HR) = 0.30

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA (ACRES) = 97.4 PEAK FLOW RATE (CFS) = 151.58

GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

* ESTIMATED CHANNEL HEIGHT (FEET) = 1.38

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 1.38 FLOW VELOCITY (FEET/SEC.) = 8.58
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13834.00 = 4648.78 FEET.

FLOW PROCESS FROM NODE 13834.00 TO NODE 13835.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 471.65 DOWNSTREAM (FEET) = 347.06
CHANNEL LENGTH THRU SUBAREA (FEET) = 1647.45 CHANNEL SLOPE = 0.0756
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT (FEET) = 1.90
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.861

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	94.21	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 217.79

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.51

AVERAGE FLOW DEPTH (FEET) = 1.86 TRAVEL TIME (MIN.) = 3.23

Tc (MIN.) = 25.90

SUBAREA AREA (ACRES) = 94.21 SUBAREA RUNOFF (CFS) = 132.32

EFFECTIVE AREA (ACRES) = 191.58 AREA-AVERAGED Fm (INCH/HR) = 0.30

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA (ACRES) = 191.6 PEAK FLOW RATE (CFS) = 269.08

GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT (FEET) = 2.09

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 2.09 FLOW VELOCITY (FEET/SEC.) = 9.06

LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13835.00 = 6296.23 FEET.

FLOW PROCESS FROM NODE 13835.00 TO NODE 13836.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 347.06 DOWNSTREAM (FEET) = 269.29
CHANNEL LENGTH THRU SUBAREA (FEET) = 1696.71 CHANNEL SLOPE = 0.0458
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT (FEET) = 3.09

* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.734

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	233.25	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 419.75

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.61
AVERAGE FLOW DEPTH (FEET) = 3.03 TRAVEL TIME (MIN.) = 3.28
Tc (MIN.) = 29.18
SUBAREA AREA (ACRES) = 233.25 SUBAREA RUNOFF (CFS) = 301.14
EFFECTIVE AREA (ACRES) = 424.83 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 424.8 PEAK FLOW RATE (CFS) = 548.48
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 3.48

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 3.48 FLOW VELOCITY (FEET/SEC.) = 9.28

LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13836.00 = 7992.94 FEET.

FLOW PROCESS FROM NODE 13836.00 TO NODE 13837.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 269.29 DOWNSTREAM (FEET) = 191.87
CHANNEL LENGTH THRU SUBAREA (FEET) = 2529.21 CHANNEL SLOPE = 0.0306
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT (FEET) = 4.16

* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.593

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	134.70	0.30	0.880	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.880

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 629.05

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.31

AVERAGE FLOW DEPTH (FEET) = 4.14 TRAVEL TIME (MIN.) = 5.07

Tc (MIN.) = 34.25

SUBAREA AREA (ACRES) = 134.70 SUBAREA RUNOFF (CFS) = 161.11

EFFECTIVE AREA (ACRES) = 559.53 AREA-AVERAGED Fm (INCH/HR) = 0.29

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97

TOTAL AREA (ACRES) = 559.5 PEAK FLOW RATE (CFS) = 655.45

GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

*ESTIMATED CHANNEL HEIGHT (FEET) = 4.23

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 4.23 FLOW VELOCITY (FEET/SEC.) = 8.40

LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13837.00 = 10522.15 FEET.

FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 191.87 DOWNSTREAM (FEET) = 133.00
FLOW LENGTH (FEET) = 1151.02 MANNING'S N = 0.013
DEPTH OF FLOW IN 66.0 INCH PIPE IS 49.4 INCHES

PIPE-FLOW VELOCITY (FEET/SEC.) = 34.36
 ESTIMATED PIPE DIAMETER (INCH) = 66.00 NUMBER OF PIPES = 1
 PIPE-FLOW (CFS) = 655.45
 PIPE TRAVEL TIME (MIN.) = 0.56 Tc (MIN.) = 34.81
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13840.00 = 11673.17 FEET.

 FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 34.81
 * 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.578
 SUBAREA LOSS RATE DATA (AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 5.97 0.30 0.622 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.622
 SUBAREA AREA (ACRES) = 5.97 SUBAREA RUNOFF (CFS) = 7.48
 EFFECTIVE AREA (ACRES) = 565.50 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
 TOTAL AREA (ACRES) = 565.5 PEAK FLOW RATE (CFS) = 655.65

 FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
 TIME OF CONCENTRATION (MIN.) = 34.81
 RAINFALL INTENSITY (INCH/HR) = 1.58
 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.97
 EFFECTIVE STREAM AREA (ACRES) = 565.50
 TOTAL STREAM AREA (ACRES) = 565.50
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 655.65

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24379.56	22.64	2.032	0.30 (0.24)	0.81	4426.8	13810.00
1	25164.78	25.10	1.891	0.30 (0.24)	0.81	4929.1	10400.00
1	27042.53	29.10	1.737	0.30 (0.24)	0.81	6179.2	10360.00
1	30933.39	39.96	1.445	0.30 (0.24)	0.81	9924.5	110.00
1	33005.52	46.29	1.342	0.30 (0.24)	0.81	12714.9	130.00
1	35986.84	55.44	1.221	0.30 (0.25)	0.83	17270.3	50260.00
1	37948.01	64.30	1.141	0.30 (0.26)	0.86	21981.9	13600.00
1	40363.11	77.28	1.054	0.30 (0.26)	0.88	28614.1	13100.00
1	41054.95	83.95	1.009	0.30 (0.27)	0.89	31584.7	11801.00
1	43570.25	98.76	0.930	0.30 (0.27)	0.91	39694.8	13510.00
1	45370.80	107.52	0.892	0.30 (0.28)	0.92	45682.5	13500.00
1	46242.73	111.94	0.873	0.30 (0.28)	0.92	48683.0	10800.00
1	46674.57	116.11	0.855	0.30 (0.28)	0.93	51628.3	11130.00
1	46148.04	125.75	0.826	0.30 (0.28)	0.93	56669.5	12410.00

1	45442.29	134.10	0.809	0.30 (0.28)	0.94	60408.7	11201.00
1	44955.76	139.12	0.798	0.30 (0.28)	0.94	62140.4	12201.00
1	43876.73	146.30	0.783	0.30 (0.28)	0.94	63997.5	12231.00
1	42512.45	154.26	0.767	0.30 (0.28)	0.94	65631.8	10400.00
1	41102.38	162.37	0.750	0.30 (0.28)	0.94	66926.9	12010.00
1	39866.17	168.48	0.737	0.30 (0.28)	0.94	67273.9	10210.00
1	35498.84	197.24	0.695	0.30 (0.28)	0.94	68012.3	10100.00
2	655.65	34.81	1.578	0.30 (0.29)	0.97	565.5	13830.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24955.91	22.64	2.032	0.30 (0.25)	0.82	4794.5	13810.00
2	25752.31	25.10	1.891	0.30 (0.25)	0.82	5336.9	10400.00
3	27658.36	29.10	1.737	0.30 (0.25)	0.82	6652.0	10360.00
4	29743.69	34.81	1.578	0.30 (0.25)	0.82	8713.7	13830.00
5	31521.18	39.96	1.445	0.30 (0.24)	0.82	10490.0	110.00
6	33540.89	46.29	1.342	0.30 (0.25)	0.82	13280.4	130.00
7	36460.64	55.44	1.221	0.30 (0.25)	0.83	17835.8	50260.00
8	38381.09	64.30	1.141	0.30 (0.26)	0.86	22547.4	13600.00
9	40751.68	77.28	1.054	0.30 (0.26)	0.88	29179.6	13100.00
10	41420.67	83.95	1.009	0.30 (0.27)	0.89	32150.2	11801.00
11	43895.92	98.76	0.930	0.30 (0.27)	0.91	40260.3	13510.00
12	45677.16	107.52	0.892	0.30 (0.28)	0.92	46248.0	13500.00
13	46539.32	111.94	0.873	0.30 (0.28)	0.92	49248.5	10800.00
14	46961.97	116.11	0.855	0.30 (0.28)	0.93	52193.8	11130.00
15	46420.76	125.75	0.826	0.30 (0.28)	0.93	57235.0	12410.00
16	45706.16	134.10	0.809	0.30 (0.28)	0.94	60974.2	11201.00
17	45214.30	139.12	0.798	0.30 (0.28)	0.94	62705.9	12201.00
18	44127.67	146.30	0.783	0.30 (0.28)	0.94	64563.0	12231.00
19	42754.95	154.26	0.767	0.30 (0.28)	0.94	66197.3	10400.00
20	41336.28	162.37	0.750	0.30 (0.28)	0.94	67492.4	12010.00
21	40093.59	168.48	0.737	0.30 (0.28)	0.94	67839.4	10210.00
22	35704.73	197.24	0.695	0.30 (0.28)	0.94	68577.8	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 46961.97 Tc (MIN.) = 116.11
 EFFECTIVE AREA (ACRES) = 52193.84 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA (ACRES) = 68577.8
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13840.00 = 132801.55 FEET.

 FLOW PROCESS FROM NODE 13840.00 TO NODE 13860.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 133.00 DOWNSTREAM (FEET) = 130.00
 CHANNEL LENGTH THRU SUBAREA (FEET) = 654.44 CHANNEL SLOPE = 0.0046
 GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT (FEET) = 16.48
 * 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.852
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 6.61 0.30 0.975 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.975
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 46963.63
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 17.18
 AVERAGE FLOW DEPTH(FEET) = 16.48 TRAVEL TIME(MIN.) = 0.63
 Tc(MIN.) = 116.75
 SUBAREA AREA(ACRES) = 6.61 SUBAREA RUNOFF(CFS) = 3.33
 EFFECTIVE AREA(ACRES) = 52200.45 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 68584.4 PEAK FLOW RATE(CFS) = 46961.97
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 16.48

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 16.48 FLOW VELOCITY(FEET/SEC.) = 17.18
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13860.00 = 133455.98 FEET.

 FLOW PROCESS FROM NODE 13840.00 TO NODE 13860.00 IS CODE = 1

 >>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
 TIME OF CONCENTRATION(MIN.) = 116.75
 RAINFALL INTENSITY(INCH/HR) = 0.85
 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.93
 EFFECTIVE STREAM AREA(ACRES) = 52200.45
 TOTAL STREAM AREA(ACRES) = 68584.41
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 46961.97

 FLOW PROCESS FROM NODE 13850.00 TO NODE 13851.00 IS CODE = 21

 >>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH(FEET) = 617.57
 ELEVATION DATA: UPSTREAM(FEET) = 646.95 DOWNSTREAM(FEET) = 490.10

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
 SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 12.137
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 3.051
 SUBAREA Tc AND LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)
 NATURAL FAIR COVER
 "CHAPARRAL,BROADLEAF" - 4.95 0.30 1.000 65 12.14
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 SUBAREA RUNOFF(CFS) = 12.25

TOTAL AREA(ACRES) = 4.95 PEAK FLOW RATE(CFS) = 12.25

 FLOW PROCESS FROM NODE 13851.00 TO NODE 13851.50 IS CODE = 56

 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 490.10 DOWNSTREAM(FEET) = 440.98
 CHANNEL LENGTH THRU SUBAREA(FEET) = 351.14 CHANNEL SLOPE = 0.1399
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 0.36
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.846
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 4.02 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 16.86
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.43
 AVERAGE FLOW DEPTH(FEET) = 0.36 TRAVEL TIME(MIN.) = 1.32
 Tc(MIN.) = 13.46

SUBAREA AREA(ACRES) = 4.02 SUBAREA RUNOFF(CFS) = 9.21
 EFFECTIVE AREA(ACRES) = 8.97 AREA-AVERAGED Fm(INCH/HR) = 0.30
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
 TOTAL AREA(ACRES) = 9.0 PEAK FLOW RATE(CFS) = 20.55
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 0.40

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 0.40 FLOW VELOCITY(FEET/SEC.) = 4.74
 LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13851.50 = 968.71 FEET.

 FLOW PROCESS FROM NODE 13851.50 TO NODE 13852.00 IS CODE = 56

 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 440.98 DOWNSTREAM(FEET) = 395.76
 CHANNEL LENGTH THRU SUBAREA(FEET) = 512.91 CHANNEL SLOPE = 0.0882
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT(FEET) = 0.56
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.578
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 7.17 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 27.91
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.55
 AVERAGE FLOW DEPTH(FEET) = 0.55 TRAVEL TIME(MIN.) = 1.88
 Tc(MIN.) = 15.34

SUBAREA AREA (ACRES) = 7.17 SUBAREA RUNOFF (CFS) = 14.70
EFFECTIVE AREA (ACRES) = 16.14 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 16.1 PEAK FLOW RATE (CFS) = 33.10
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.61

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.61 FLOW VELOCITY (FEET/SEC.) = 4.86
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13852.00 = 1481.62 FEET.

FLOW PROCESS FROM NODE 13852.00 TO NODE 13853.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 395.76 DOWNSTREAM (FEET) = 354.94
CHANNEL LENGTH THRU SUBAREA (FEET) = 443.69 CHANNEL SLOPE = 0.0920
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.67
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 2.459

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	6.76	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 39.67
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.23
AVERAGE FLOW DEPTH (FEET) = 0.67 TRAVEL TIME (MIN.) = 1.41
Tc (MIN.) = 16.75

SUBAREA AREA (ACRES) = 6.76 SUBAREA RUNOFF (CFS) = 13.14
EFFECTIVE AREA (ACRES) = 22.90 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 22.9 PEAK FLOW RATE (CFS) = 44.50
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.71

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.71 FLOW VELOCITY (FEET/SEC.) = 5.45
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13853.00 = 1925.31 FEET.

FLOW PROCESS FROM NODE 13853.00 TO NODE 13854.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 354.94 DOWNSTREAM (FEET) = 263.57
CHANNEL LENGTH THRU SUBAREA (FEET) = 962.09 CHANNEL SLOPE = 0.0950
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.86
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 2.237

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	18.16	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 60.34
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.12
AVERAGE FLOW DEPTH (FEET) = 0.84 TRAVEL TIME (MIN.) = 2.62
Tc (MIN.) = 19.37

SUBAREA AREA (ACRES) = 18.16 SUBAREA RUNOFF (CFS) = 31.66
EFFECTIVE AREA (ACRES) = 41.06 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 41.1 PEAK FLOW RATE (CFS) = 71.59
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.93

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.93 FLOW VELOCITY (FEET/SEC.) = 6.46
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13854.00 = 2887.40 FEET.

FLOW PROCESS FROM NODE 13854.00 TO NODE 13855.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 263.57 DOWNSTREAM (FEET) = 188.74
CHANNEL LENGTH THRU SUBAREA (FEET) = 1228.77 CHANNEL SLOPE = 0.0609
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 1.32
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 2.031

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	38.75	0.30	0.879	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.879
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 102.43
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.25
AVERAGE FLOW DEPTH (FEET) = 1.30 TRAVEL TIME (MIN.) = 3.27
Tc (MIN.) = 22.65

SUBAREA AREA (ACRES) = 38.75 SUBAREA RUNOFF (CFS) = 61.64
EFFECTIVE AREA (ACRES) = 79.81 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94
TOTAL AREA (ACRES) = 79.8 PEAK FLOW RATE (CFS) = 125.61
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT (FEET) = 1.46

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 1.46 FLOW VELOCITY (FEET/SEC.) = 6.66
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13855.00 = 4116.17 FEET.

FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 31

```

-----
>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 188.74 DOWNSTREAM(FEET) = 130.00
FLOW LENGTH(FEET) = 2092.67 MANNING'S N = 0.013
DEPTH OF FLOW IN 39.0 INCH PIPE IS 30.6 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 18.01
ESTIMATED PIPE DIAMETER(INCH) = 39.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 125.61
PIPE TRAVEL TIME(MIN.) = 1.94 Tc(MIN.) = 24.58
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13860.00 = 6208.84 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 24.58
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.919
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 43.41 0.30 0.707 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.707
SUBAREA AREA(ACRES) = 43.41 SUBAREA RUNOFF(CFS) = 66.69
EFFECTIVE AREA(ACRES) = 123.22 AREA-AVERAGED Fm(INCH/HR) = 0.26
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.86
TOTAL AREA(ACRES) = 123.2 PEAK FLOW RATE(CFS) = 184.26

```

```

*****
FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 1
-----

```

```

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<
=====
TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 24.58
RAINFALL INTENSITY(INCH/HR) = 1.92
AREA-AVERAGED Fm(INCH/HR) = 0.26
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.86
EFFECTIVE STREAM AREA(ACRES) = 123.22
TOTAL STREAM AREA(ACRES) = 123.22
PEAK FLOW RATE(CFS) AT CONFLUENCE = 184.26

```

```

** CONFLUENCE DATA **

```

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24955.91	23.40	1.988	0.30 (0.25)	0.82	4801.1	13810.00
1	25752.31	25.85	1.862	0.30 (0.25)	0.82	5343.5	10400.00
1	27658.36	29.84	1.709	0.30 (0.25)	0.82	6658.6	10360.00
1	29743.69	35.53	1.560	0.30 (0.25)	0.82	8720.3	13830.00
1	31521.18	40.67	1.433	0.30 (0.24)	0.82	10496.6	110.00
1	33540.89	46.99	1.331	0.30 (0.25)	0.82	13287.0	130.00
1	36460.64	56.12	1.213	0.30 (0.25)	0.83	17842.4	50260.00

1	38381.09	64.97	1.137	0.30 (0.26)	0.86	22554.0	13600.00
1	40751.68	77.94	1.049	0.30 (0.26)	0.88	29186.2	13100.00
1	41420.67	84.61	1.004	0.30 (0.27)	0.89	32156.8	11801.00
1	43895.92	99.40	0.927	0.30 (0.27)	0.91	40266.9	13510.00
1	45677.16	108.16	0.889	0.30 (0.28)	0.92	46254.6	13500.00
1	46539.32	112.58	0.870	0.30 (0.28)	0.92	49255.1	10800.00
1	46961.97	116.75	0.852	0.30 (0.28)	0.93	52200.4	11130.00
1	46420.76	126.39	0.825	0.30 (0.28)	0.93	57241.7	12410.00
1	45706.16	134.74	0.807	0.30 (0.28)	0.94	60980.8	11201.00
1	45214.30	139.77	0.797	0.30 (0.28)	0.94	62712.5	12201.00
1	44127.67	146.94	0.782	0.30 (0.28)	0.94	64569.6	12231.00
1	42754.95	154.91	0.765	0.30 (0.28)	0.94	66203.9	10400.00
1	41336.28	163.03	0.748	0.30 (0.28)	0.94	67499.0	12010.00
1	40093.59	169.14	0.736	0.30 (0.28)	0.94	67846.0	10210.00
1	35704.73	197.93	0.694	0.30 (0.28)	0.94	68584.4	10100.00
2	184.26	24.58	1.919	0.30 (0.26)	0.86	123.2	13850.00

```

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

```

```

** PEAK FLOW RATE TABLE **

```

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25138.52	23.40	1.988	0.30 (0.25)	0.82	4918.4	13810.00
2	25524.23	24.58	1.919	0.30 (0.25)	0.82	5185.9	13850.00
3	25930.26	25.85	1.862	0.30 (0.25)	0.82	5466.7	10400.00
4	27819.32	29.84	1.709	0.30 (0.25)	0.82	6781.8	10360.00
5	29888.09	35.53	1.560	0.30 (0.25)	0.82	8843.5	13830.00
6	31651.55	40.67	1.433	0.30 (0.25)	0.82	10619.8	110.00
7	33659.90	46.99	1.331	0.30 (0.25)	0.82	13410.3	130.00
8	36566.65	56.12	1.213	0.30 (0.25)	0.83	17965.6	50260.00
9	38478.56	64.97	1.137	0.30 (0.26)	0.86	22677.2	13600.00
10	40839.46	77.94	1.049	0.30 (0.26)	0.88	29309.4	13100.00
11	41503.48	84.61	1.004	0.30 (0.27)	0.89	32280.0	11801.00
12	43970.18	99.40	0.927	0.30 (0.27)	0.91	40390.1	13510.00
13	45747.22	108.16	0.889	0.30 (0.28)	0.92	46377.8	13500.00
14	46607.26	112.58	0.870	0.30 (0.28)	0.92	49378.3	10800.00
15	47027.90	116.75	0.852	0.30 (0.28)	0.93	52323.7	11130.00
16	46483.66	126.39	0.825	0.30 (0.28)	0.93	57364.9	12410.00
17	45767.12	134.74	0.807	0.30 (0.28)	0.94	61104.0	11201.00
18	45274.11	139.77	0.797	0.30 (0.28)	0.94	62835.7	12201.00
19	44185.81	146.94	0.782	0.30 (0.28)	0.94	64692.8	12231.00
20	42811.25	154.91	0.765	0.30 (0.28)	0.94	66327.1	10400.00
21	41390.71	163.03	0.748	0.30 (0.28)	0.94	67622.2	12010.00
22	40146.61	169.14	0.736	0.30 (0.28)	0.94	67969.2	10210.00
23	35753.12	197.93	0.694	0.30 (0.28)	0.94	68707.6	10100.00

```

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
PEAK FLOW RATE(CFS) = 47027.90 Tc(MIN.) = 116.75
EFFECTIVE AREA(ACRES) = 52323.67 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 68707.6
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13860.00 = 133455.98 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13860.00 TO NODE 13880.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

```

>>>>TRAVELTIME THRU SUBAREA<<<<

```

=====
ELEVATION DATA: UPSTREAM(FEET) = 130.00 DOWNSTREAM(FEET) = 120.57
CHANNEL LENGTH THRU SUBAREA(FEET) = 610.77 CHANNEL SLOPE = 0.0154
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 12.00
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.850
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp        Ap      SCS
LAND USE           GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN
USER-DEFINED       -       4.89     0.30     1.000    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 47029.11
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 26.49
AVERAGE FLOW DEPTH(FEET) = 12.00 TRAVEL TIME(MIN.) = 0.38
Tc(MIN.) = 117.13
SUBAREA AREA(ACRES) = 4.89 SUBAREA RUNOFF(CFS) = 2.42
EFFECTIVE AREA(ACRES) = 52328.56 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 68712.5 PEAK FLOW RATE(CFS) = 47027.90
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 12.00

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 12.00 FLOW VELOCITY(FEET/SEC.) = 26.48
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13880.00 = 134066.75 FEET.

FLOW PROCESS FROM NODE 13860.00 TO NODE 13880.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

```

=====
TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION(MIN.) = 117.13
RAINFALL INTENSITY(INCH/HR) = 0.85
AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.93
EFFECTIVE STREAM AREA(ACRES) = 52328.56
TOTAL STREAM AREA(ACRES) = 68712.52
PEAK FLOW RATE(CFS) AT CONFLUENCE = 47027.90

```

FLOW PROCESS FROM NODE 13870.00 TO NODE 13871.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

```

=====
INITIAL SUBAREA FLOW-LENGTH(FEET) = 872.65
ELEVATION DATA: UPSTREAM(FEET) = 558.52 DOWNSTREAM(FEET) = 436.47

```

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 15.704

```

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.547
SUBAREA Tc AND LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp        Ap      SCS   Tc
LAND USE           GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN (MIN.)
NATURAL FAIR COVER
"GRASS"             -       7.32     0.30     1.000    65   15.70
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 14.81
TOTAL AREA(ACRES) = 7.32 PEAK FLOW RATE(CFS) = 14.81

```

FLOW PROCESS FROM NODE 13871.00 TO NODE 13872.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

```

=====
ELEVATION DATA: UPSTREAM(FEET) = 436.47 DOWNSTREAM(FEET) = 337.62
CHANNEL LENGTH THRU SUBAREA(FEET) = 827.95 CHANNEL SLOPE = 0.1194
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.51
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.311
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp        Ap      SCS
LAND USE           GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN
USER-DEFINED       -       13.01    0.30     1.000    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 26.60
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.93
AVERAGE FLOW DEPTH(FEET) = 0.49 TRAVEL TIME(MIN.) = 2.80
Tc(MIN.) = 18.50
SUBAREA AREA(ACRES) = 13.01 SUBAREA RUNOFF(CFS) = 23.54
EFFECTIVE AREA(ACRES) = 20.33 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 20.3 PEAK FLOW RATE(CFS) = 36.79
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.59

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.59 FLOW VELOCITY(FEET/SEC.) = 5.55
LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13872.00 = 1700.60 FEET.

FLOW PROCESS FROM NODE 13872.00 TO NODE 13873.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

```

=====
ELEVATION DATA: UPSTREAM(FEET) = 337.62 DOWNSTREAM(FEET) = 253.88
CHANNEL LENGTH THRU SUBAREA(FEET) = 1049.16 CHANNEL SLOPE = 0.0798
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.94
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.099
SUBAREA LOSS RATE DATA(AMC II):

```

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 32.99 0.30 0.923 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.923
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 63.87
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.88
 AVERAGE FLOW DEPTH (FEET) = 0.92 TRAVEL TIME (MIN.) = 2.98
 Tc (MIN.) = 21.48
 SUBAREA AREA (ACRES) = 32.99 SUBAREA RUNOFF (CFS) = 54.09
 EFFECTIVE AREA (ACRES) = 53.32 AREA-AVERAGED Fm (INCH/HR) = 0.29
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
 TOTAL AREA (ACRES) = 53.3 PEAK FLOW RATE (CFS) = 87.00
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
 *ESTIMATED CHANNEL HEIGHT (FEET) = 1.10

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 1.10 FLOW VELOCITY (FEET/SEC.) = 6.51
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13873.00 = 2749.76 FEET.

 FLOW PROCESS FROM NODE 13873.00 TO NODE 13874.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 253.88 DOWNSTREAM (FEET) = 160.73
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1518.60 CHANNEL SLOPE = 0.0613
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT (FEET) = 1.09
 * 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.925
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	30.94	0.30	0.900	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.900
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 110.06
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.45
 AVERAGE FLOW DEPTH (FEET) = 1.07 TRAVEL TIME (MIN.) = 3.00
 Tc (MIN.) = 24.47
 SUBAREA AREA (ACRES) = 30.94 SUBAREA RUNOFF (CFS) = 46.10
 EFFECTIVE AREA (ACRES) = 84.26 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA (ACRES) = 84.3 PEAK FLOW RATE (CFS) = 124.79
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT (FEET) = 1.15

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 1.15 FLOW VELOCITY (FEET/SEC.) = 8.78
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13874.00 = 4268.36 FEET.

 FLOW PROCESS FROM NODE 13874.00 TO NODE 13875.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 160.73 DOWNSTREAM (FEET) = 158.14
 CHANNEL LENGTH THRU SUBAREA (FEET) = 582.74 CHANNEL SLOPE = 0.0044
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT (FEET) = 2.90
 * 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.820
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	73.67	0.30	0.930	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.930
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 175.88
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 3.90
 AVERAGE FLOW DEPTH (FEET) = 2.87 TRAVEL TIME (MIN.) = 2.49
 Tc (MIN.) = 26.96
 SUBAREA AREA (ACRES) = 73.67 SUBAREA RUNOFF (CFS) = 102.15
 EFFECTIVE AREA (ACRES) = 157.93 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA (ACRES) = 157.9 PEAK FLOW RATE (CFS) = 218.91
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
 *ESTIMATED CHANNEL HEIGHT (FEET) = 3.21

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH (FEET) = 3.21 FLOW VELOCITY (FEET/SEC.) = 4.14
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13875.00 = 4851.10 FEET.

 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 158.14 DOWNSTREAM (FEET) = 120.57
 FLOW LENGTH (FEET) = 1855.67 MANNING'S N = 0.013
 DEPTH OF FLOW IN 51.0 INCH PIPE IS 40.1 INCHES
 PIPE-FLOW VELOCITY (FEET/SEC.) = 18.30
 ESTIMATED PIPE DIAMETER (INCH) = 51.00 NUMBER OF PIPES = 1
 PIPE-FLOW (CFS) = 218.91
 PIPE TRAVEL TIME (MIN.) = 1.69 Tc (MIN.) = 28.65
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13880.00 = 6706.77 FEET.

 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 28.65
 * 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.755
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	34.90	0.30	0.743	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.743
 SUBAREA AREA(ACRES) = 34.90 SUBAREA RUNOFF(CFS) = 48.11
 EFFECTIVE AREA(ACRES) = 192.83 AREA-AVERAGED Fm(INCH/HR) = 0.27
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.90
 TOTAL AREA(ACRES) = 192.8 PEAK FLOW RATE(CFS) = 257.80

 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====

TOTAL NUMBER OF STREAMS = 2
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
 TIME OF CONCENTRATION(MIN.) = 28.65
 RAINFALL INTENSITY(INCH/HR) = 1.75
 AREA-AVERAGED Fm(INCH/HR) = 0.27
 AREA-AVERAGED Fp(INCH/HR) = 0.30
 AREA-AVERAGED Ap = 0.90
 EFFECTIVE STREAM AREA(ACRES) = 192.83
 TOTAL STREAM AREA(ACRES) = 192.83
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 257.80

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25138.52	23.86	1.961	0.30(0.25)	0.82	4923.3	13810.00
1	25524.23	25.04	1.893	0.30(0.25)	0.82	5190.8	13850.00
1	25930.26	26.31	1.845	0.30(0.25)	0.82	5471.6	10400.00
1	27819.32	30.29	1.695	0.30(0.25)	0.82	6786.7	10360.00
1	29888.09	35.97	1.548	0.30(0.25)	0.82	8848.4	13830.00
1	31651.55	41.10	1.426	0.30(0.25)	0.82	10624.7	110.00
1	33659.90	47.42	1.324	0.30(0.25)	0.82	13415.1	130.00
1	36566.65	56.53	1.209	0.30(0.25)	0.83	17970.5	50260.00
1	38478.56	65.38	1.134	0.30(0.26)	0.86	22682.1	13600.00
1	40839.46	78.34	1.046	0.30(0.26)	0.88	29314.3	13100.00
1	41503.48	85.01	1.002	0.30(0.27)	0.89	32284.9	11801.00
1	43970.18	99.80	0.926	0.30(0.27)	0.91	40395.0	13510.00
1	45747.22	108.54	0.888	0.30(0.28)	0.92	46382.7	13500.00
1	46607.26	112.96	0.868	0.30(0.28)	0.92	49383.2	10800.00
1	47027.90	117.13	0.850	0.30(0.28)	0.93	52328.6	11130.00
1	46483.66	126.78	0.824	0.30(0.28)	0.93	57369.8	12410.00
1	45767.12	135.13	0.806	0.30(0.28)	0.94	61108.9	11201.00
1	45274.11	140.15	0.796	0.30(0.28)	0.94	62840.6	12201.00
1	44185.81	147.33	0.781	0.30(0.28)	0.94	64697.7	12231.00
1	42811.25	155.30	0.764	0.30(0.28)	0.94	66332.0	10400.00
1	41390.71	163.42	0.748	0.30(0.28)	0.94	67627.1	12010.00
1	40146.61	169.55	0.735	0.30(0.28)	0.94	67974.1	10210.00
1	35753.12	198.35	0.694	0.30(0.28)	0.94	68712.5	10100.00
2	257.80	28.65	1.755	0.30(0.27)	0.90	192.8	13870.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25382.99	23.86	1.961	0.30(0.25)	0.82	5083.9	13810.00

2	25770.58	25.04	1.893	0.30(0.25)	0.82	5359.3	13850.00
3	26181.33	26.31	1.845	0.30(0.25)	0.82	5648.7	10400.00
4	27299.16	28.65	1.755	0.30(0.25)	0.82	6437.9	13870.00
5	28066.84	30.29	1.695	0.30(0.25)	0.82	6979.5	10360.00
6	30110.07	35.97	1.548	0.30(0.25)	0.82	9041.2	13830.00
7	31852.33	41.10	1.426	0.30(0.25)	0.82	10817.5	110.00
8	33842.94	47.42	1.324	0.30(0.25)	0.82	13608.0	130.00
9	36729.72	56.53	1.209	0.30(0.25)	0.84	18163.3	50260.00
10	38628.61	65.38	1.134	0.30(0.26)	0.86	22874.9	13600.00
11	40974.36	78.34	1.046	0.30(0.26)	0.88	29507.1	13100.00
12	41630.59	85.01	1.002	0.30(0.27)	0.89	32477.8	11801.00
13	44084.09	99.80	0.926	0.30(0.27)	0.91	40587.8	13510.00
14	45854.55	108.54	0.888	0.30(0.28)	0.92	46575.5	13500.00
15	46711.26	112.96	0.868	0.30(0.28)	0.92	49576.0	10800.00
16	47128.77	117.13	0.850	0.30(0.28)	0.93	52521.4	11130.00
17	46579.92	126.78	0.824	0.30(0.28)	0.93	57562.6	12410.00
18	45860.36	135.13	0.806	0.30(0.28)	0.94	61301.7	11201.00
19	45365.54	140.15	0.796	0.30(0.28)	0.94	63033.4	12201.00
20	44274.64	147.33	0.781	0.30(0.28)	0.94	64890.6	12231.00
21	42897.20	155.30	0.764	0.30(0.28)	0.94	66524.9	10400.00
22	41473.72	163.42	0.748	0.30(0.28)	0.94	67819.9	12010.00
23	40227.41	169.55	0.735	0.30(0.28)	0.94	68166.9	10210.00
24	35826.77	198.35	0.694	0.30(0.28)	0.94	68905.3	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 47128.77 Tc(MIN.) = 117.13
 EFFECTIVE AREA(ACRES) = 52521.39 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 68905.3
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13880.00 = 134066.75 FEET.

 FLOW PROCESS FROM NODE 13880.00 TO NODE 13910.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 120.57 DOWNSTREAM(FEET) = 119.70
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1190.21 CHANNEL SLOPE = 0.0007
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 26.12
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.841
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	117.69	0.30	0.724	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.724
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 47161.80
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.83
 AVERAGE FLOW DEPTH(FEET) = 26.12 TRAVEL TIME(MIN.) = 2.25
 Tc(MIN.) = 119.38
 SUBAREA AREA(ACRES) = 117.69 SUBAREA RUNOFF(CFS) = 66.05
 EFFECTIVE AREA(ACRES) = 52639.08 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 69023.0 PEAK FLOW RATE(CFS) = 47128.77
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT (FEET) = 26.11

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 26.11 FLOW VELOCITY (FEET/SEC.) = 8.83
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13910.00 = 135256.95 FEET.

FLOW PROCESS FROM NODE 13880.00 TO NODE 13910.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

=====

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION (MIN.) = 119.38
RAINFALL INTENSITY (INCH/HR) = 0.84
AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.93
EFFECTIVE STREAM AREA (ACRES) = 52639.08
TOTAL STREAM AREA (ACRES) = 69023.03
PEAK FLOW RATE (CFS) AT CONFLUENCE = 47128.77

FLOW PROCESS FROM NODE 13889.00 TO NODE 13890.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH (FEET) = 447.89
ELEVATION DATA: UPSTREAM (FEET) = 564.89 DOWNSTREAM (FEET) = 421.92

Tc = K * [(LENGTH** 3.00) / (ELEVATION CHANGE)] ** 0.20
SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 6.976
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 4.497
SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
PUBLIC PARK	-	3.03	0.30	0.960	65	6.98

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.960
SUBAREA RUNOFF (CFS) = 11.48
TOTAL AREA (ACRES) = 3.03 PEAK FLOW RATE (CFS) = 11.48

FLOW PROCESS FROM NODE 13890.00 TO NODE 13891.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 421.92 DOWNSTREAM (FEET) = 392.64
CHANNEL LENGTH THRU SUBAREA (FEET) = 435.33 CHANNEL SLOPE = 0.0673
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.46
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 3.985
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 8.12 0.30 0.986 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.986
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 25.00
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.23
AVERAGE FLOW DEPTH (FEET) = 0.44 TRAVEL TIME (MIN.) = 1.39
Tc (MIN.) = 8.36

SUBAREA AREA (ACRES) = 8.12 SUBAREA RUNOFF (CFS) = 26.96
EFFECTIVE AREA (ACRES) = 11.15 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
TOTAL AREA (ACRES) = 11.1 PEAK FLOW RATE (CFS) = 37.04
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.55

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.55 FLOW VELOCITY (FEET/SEC.) = 6.02
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13891.00 = 883.22 FEET.

FLOW PROCESS FROM NODE 13891.00 TO NODE 13892.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 392.64 DOWNSTREAM (FEET) = 324.46
CHANNEL LENGTH THRU SUBAREA (FEET) = 662.40 CHANNEL SLOPE = 0.1029
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.64
* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 3.473

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	12.50	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 54.93
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.95
AVERAGE FLOW DEPTH (FEET) = 0.62 TRAVEL TIME (MIN.) = 1.39
Tc (MIN.) = 9.75
SUBAREA AREA (ACRES) = 12.50 SUBAREA RUNOFF (CFS) = 35.70
EFFECTIVE AREA (ACRES) = 23.65 AREA-AVERAGED Fm (INCH/HR) = 0.30
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA (ACRES) = 23.6 PEAK FLOW RATE (CFS) = 67.61
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.70

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 0.70 FLOW VELOCITY (FEET/SEC.) = 8.51
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13892.00 = 1545.62 FEET.

FLOW PROCESS FROM NODE 13892.00 TO NODE 13893.00 IS CODE = 56

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 324.46 DOWNSTREAM(FEET) = 240.82
CHANNEL LENGTH THRU SUBAREA(FEET) = 980.03 CHANNEL SLOPE = 0.0853
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.87
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 3.131
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 15.87 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 87.84
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.75
AVERAGE FLOW DEPTH(FEET) = 0.86 TRAVEL TIME(MIN.) = 1.87
Tc(MIN.) = 11.62
SUBAREA AREA(ACRES) = 15.87 SUBAREA RUNOFF(CFS) = 40.43
EFFECTIVE AREA(ACRES) = 39.52 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 39.5 PEAK FLOW RATE(CFS) = 100.75
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.93

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.93 FLOW VELOCITY(FEET/SEC.) = 9.18
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13893.00 = 2525.65 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13893.00 TO NODE 13894.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 240.82 DOWNSTREAM(FEET) = 163.04
CHANNEL LENGTH THRU SUBAREA(FEET) = 1144.35 CHANNEL SLOPE = 0.0680
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.18
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.812
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 28.41 0.30 0.985 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.985
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 132.98
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.28
AVERAGE FLOW DEPTH(FEET) = 1.16 TRAVEL TIME(MIN.) = 2.05
Tc(MIN.) = 13.68
SUBAREA AREA(ACRES) = 28.41 SUBAREA RUNOFF(CFS) = 64.36
EFFECTIVE AREA(ACRES) = 67.93 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 67.9 PEAK FLOW RATE(CFS) = 153.78
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

```

```

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.26

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.26 FLOW VELOCITY(FEET/SEC.) = 9.73
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13894.00 = 3670.00 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 31
-----

```

```

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 163.04 DOWNSTREAM(FEET) = 119.70
FLOW LENGTH(FEET) = 1899.01 MANNING'S N = 0.013
DEPTH OF FLOW IN 45.0 INCH PIPE IS 33.0 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 17.73
ESTIMATED PIPE DIAMETER(INCH) = 45.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 153.78
PIPE TRAVEL TIME(MIN.) = 1.79 Tc(MIN.) = 15.46
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13910.00 = 5569.01 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 15.46
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.568
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 11.69 0.30 0.634 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.634
SUBAREA AREA(ACRES) = 11.69 SUBAREA RUNOFF(CFS) = 25.02
EFFECTIVE AREA(ACRES) = 79.62 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94
TOTAL AREA(ACRES) = 79.6 PEAK FLOW RATE(CFS) = 163.86

```

```

*****
FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 1
-----

```

```

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<
=====
TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 15.46
RAINFALL INTENSITY(INCH/HR) = 2.57
AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.94
EFFECTIVE STREAM AREA(ACRES) = 79.62
TOTAL STREAM AREA(ACRES) = 79.62
PEAK FLOW RATE(CFS) AT CONFLUENCE = 163.86

```

** CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25382.99	26.52	1.837	0.30 (0.25)	0.82	5201.6	13810.00
1	25770.58	27.69	1.792	0.30 (0.25)	0.82	5477.0	13850.00
1	26181.33	28.95	1.743	0.30 (0.25)	0.82	5766.3	10400.00
1	27299.16	31.26	1.670	0.30 (0.25)	0.82	6555.6	13870.00
1	28066.84	32.88	1.629	0.30 (0.25)	0.82	7097.2	10360.00
1	30110.07	38.51	1.483	0.30 (0.25)	0.82	9158.9	13830.00
1	31852.33	43.60	1.386	0.30 (0.25)	0.82	10935.2	110.00
1	33842.94	49.87	1.284	0.30 (0.25)	0.82	13725.7	130.00
1	36729.72	58.93	1.182	0.30 (0.25)	0.83	18281.0	50260.00
1	38628.61	67.74	1.118	0.30 (0.26)	0.86	22992.6	13600.00
1	40974.36	80.68	1.031	0.30 (0.26)	0.88	29624.8	13100.00
1	41630.59	87.33	0.986	0.30 (0.27)	0.89	32595.5	11801.00
1	44084.09	102.08	0.916	0.30 (0.27)	0.91	40705.5	13510.00
1	45854.55	110.81	0.878	0.30 (0.28)	0.92	46693.2	13500.00
1	46711.26	115.22	0.859	0.30 (0.28)	0.92	49693.7	10800.00
1	47128.77	119.38	0.841	0.30 (0.28)	0.93	52639.1	11130.00
1	46579.92	129.03	0.819	0.30 (0.28)	0.93	57680.3	12410.00
1	45860.36	137.39	0.802	0.30 (0.28)	0.94	61419.4	11201.00
1	45365.54	142.42	0.791	0.30 (0.28)	0.94	63151.1	12201.00
1	44274.64	149.62	0.776	0.30 (0.28)	0.94	65008.2	12231.00
1	42897.20	157.61	0.760	0.30 (0.28)	0.94	66642.5	10400.00
1	41473.72	165.75	0.743	0.30 (0.28)	0.94	67937.6	12010.00
1	40227.41	171.89	0.730	0.30 (0.28)	0.94	68284.6	10210.00
1	35826.77	200.76	0.691	0.30 (0.28)	0.94	69023.0	10100.00
2	163.86	15.46	2.568	0.30 (0.28)	0.94	79.6	13889.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21766.55	15.46	2.568	0.30 (0.25)	0.82	3112.3	13889.00
2	25494.45	26.52	1.837	0.30 (0.25)	0.82	5281.2	13810.00
3	25878.82	27.69	1.792	0.30 (0.25)	0.82	5556.6	13850.00
4	26286.10	28.95	1.743	0.30 (0.25)	0.82	5846.0	10400.00
5	27398.70	31.26	1.670	0.30 (0.25)	0.82	6635.2	13870.00
6	28163.38	32.88	1.629	0.30 (0.25)	0.82	7176.8	10360.00
7	30196.15	38.51	1.483	0.30 (0.25)	0.82	9238.5	13830.00
8	31931.46	43.60	1.386	0.30 (0.25)	0.82	11014.8	110.00
9	33914.79	49.87	1.284	0.30 (0.25)	0.82	13805.3	130.00
10	36794.25	58.93	1.182	0.30 (0.25)	0.84	18360.6	50260.00
11	38688.56	67.74	1.118	0.30 (0.26)	0.86	23072.2	13600.00
12	41028.06	80.68	1.031	0.30 (0.26)	0.88	29704.5	13100.00
13	41681.09	87.33	0.986	0.30 (0.27)	0.89	32675.1	11801.00
14	44129.55	102.08	0.916	0.30 (0.27)	0.91	40785.1	13510.00
15	45897.29	110.81	0.878	0.30 (0.28)	0.92	46772.9	13500.00
16	46752.64	115.22	0.859	0.30 (0.28)	0.92	49773.3	10800.00
17	47168.86	119.38	0.841	0.30 (0.28)	0.93	52718.7	11130.00
18	46618.46	129.03	0.819	0.30 (0.28)	0.93	57759.9	12410.00
19	45897.66	137.39	0.802	0.30 (0.28)	0.94	61499.0	11201.00
20	45402.08	142.42	0.791	0.30 (0.28)	0.94	63230.7	12201.00
21	44310.11	149.62	0.776	0.30 (0.28)	0.94	65087.9	12231.00
22	42931.48	157.61	0.760	0.30 (0.28)	0.94	66722.2	10400.00
23	41506.79	165.75	0.743	0.30 (0.28)	0.94	68017.2	12010.00
24	40259.55	171.89	0.730	0.30 (0.28)	0.94	68364.2	10210.00

25 35856.12 200.76 0.691 0.30 (0.28) 0.94 69102.6 10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 47168.86 Tc(MIN.) = 119.38
EFFECTIVE AREA(ACRES) = 52718.70 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 69102.6
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13910.00 = 135256.95 FEET.

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 69102.6 TC(MIN.) = 119.38
EFFECTIVE AREA(ACRES) = 52718.70 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.926
PEAK FLOW RATE(CFS) = 47168.86

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21766.55	15.46	2.568	0.30 (0.25)	0.82	3112.3	13889.00
2	25494.45	26.52	1.837	0.30 (0.25)	0.82	5281.2	13810.00
3	25878.82	27.69	1.792	0.30 (0.25)	0.82	5556.6	13850.00
4	26286.10	28.95	1.743	0.30 (0.25)	0.82	5846.0	10400.00
5	27398.70	31.26	1.670	0.30 (0.25)	0.82	6635.2	13870.00
6	28163.38	32.88	1.629	0.30 (0.25)	0.82	7176.8	10360.00
7	30196.15	38.51	1.483	0.30 (0.25)	0.82	9238.5	13830.00
8	31931.46	43.60	1.386	0.30 (0.25)	0.82	11014.8	110.00
9	33914.79	49.87	1.284	0.30 (0.25)	0.82	13805.3	130.00
10	36794.25	58.93	1.182	0.30 (0.25)	0.84	18360.6	50260.00
11	38688.56	67.74	1.118	0.30 (0.26)	0.86	23072.2	13600.00
12	41028.06	80.68	1.031	0.30 (0.26)	0.88	29704.5	13100.00
13	41681.09	87.33	0.986	0.30 (0.27)	0.89	32675.1	11801.00
14	44129.55	102.08	0.916	0.30 (0.27)	0.91	40785.1	13510.00
15	45897.29	110.81	0.878	0.30 (0.28)	0.92	46772.9	13500.00
16	46752.64	115.22	0.859	0.30 (0.28)	0.92	49773.3	10800.00
17	47168.86	119.38	0.841	0.30 (0.28)	0.93	52718.7	11130.00
18	46618.46	129.03	0.819	0.30 (0.28)	0.93	57759.9	12410.00
19	45897.66	137.39	0.802	0.30 (0.28)	0.94	61499.0	11201.00
20	45402.08	142.42	0.791	0.30 (0.28)	0.94	63230.7	12201.00
21	44310.11	149.62	0.776	0.30 (0.28)	0.94	65087.9	12231.00
22	42931.48	157.61	0.760	0.30 (0.28)	0.94	66722.2	10400.00
23	41506.79	165.75	0.743	0.30 (0.28)	0.94	68017.2	12010.00
24	40259.55	171.89	0.730	0.30 (0.28)	0.94	68364.2	10210.00
25	35856.12	200.76	0.691	0.30 (0.28)	0.94	69102.6	10100.00

END OF RATIONAL METHOD ANALYSIS

RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)
(c) Copyright 1983-2010 Advanced Engineering Software (aes)
Ver. 17.0 Release Date: 07/01/2010 License ID 1527

Analysis prepared by:

***** DESCRIPTION OF STUDY *****
* RMV PA-3 BODR 2022 - NODE 139 FREE DRAINING *
* RATIONAL METHOD HYDROLOGY MODEL REGIONAL *
* 50-YR EV AUG 2023 ROKAMOTO *

FILE NAME: RU50EV39.DAT
TIME/DATE OF STUDY: 22:19 08/10/2023

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--*TIME-OF-CONCENTRATION MODEL*--

USER SPECIFIED STORM EVENT(YEAR) = 50.00
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
USER-DEFINED TABLED RAINFALL USED
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.220
- 2) 10.00; 3.380
- 3) 15.00; 2.606
- 4) 20.00; 2.184
- 5) 25.00; 1.894
- 6) 30.00; 1.703
- 7) 40.00; 1.444
- 8) 50.00; 1.282
- 9) 60.00; 1.169
- 10) 90.00; 0.968
- 11) 120.00; 0.837
- 12) 180.00; 0.712
- 13) 360.00; 0.522
- 14) 1200.00; 0.227

ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD

USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL: IN- / OUT-/PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
1. Relative Flow-Depth = 0.00 FEET
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)*(Velocity) Constraint = 6.0 (FT*FT/S)
*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

FLOW PROCESS FROM NODE 13900.00 TO NODE 13901.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 600.65
ELEVATION DATA: UPSTREAM(FEET) = 442.40 DOWNSTREAM(FEET) = 385.16

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 10.859
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 3.247
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
AGRICULTURAL POOR COVER "FALLOW"	-	4.00	0.30	1.000	65	10.86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 10.61
TOTAL AREA(ACRES) = 4.00 PEAK FLOW RATE(CFS) = 10.61

FLOW PROCESS FROM NODE 13901.00 TO NODE 13902.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 385.16 DOWNSTREAM(FEET) = 288.21
CHANNEL LENGTH THRU SUBAREA(FEET) = 647.42 CHANNEL SLOPE = 0.1497
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.32
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.983
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.47	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 20.86
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.34
AVERAGE FLOW DEPTH(FEET) = 0.31 TRAVEL TIME(MIN.) = 1.70
Tc(MIN.) = 12.56
SUBAREA AREA(ACRES) = 8.47 SUBAREA RUNOFF(CFS) = 20.46
EFFECTIVE AREA(ACRES) = 12.47 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 12.5 PEAK FLOW RATE(CFS) = 30.12
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.39

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.39 FLOW VELOCITY(FEET/SEC.) = 7.24
LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13902.00 = 1248.07 FEET.

FLOW PROCESS FROM NODE 13902.00 TO NODE 13903.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 288.21 DOWNSTREAM(FEET) = 184.89
CHANNEL LENGTH THRU SUBAREA(FEET) = 669.27 CHANNEL SLOPE = 0.1544
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 0.57

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.795

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	23.85	0.30	0.982	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.982

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 56.98

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.15

AVERAGE FLOW DEPTH(FEET) = 0.56 TRAVEL TIME(MIN.) = 1.22

Tc(MIN.) = 13.78

SUBAREA AREA(ACRES) = 23.85 SUBAREA RUNOFF(CFS) = 53.67

EFFECTIVE AREA(ACRES) = 36.32 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 36.3 PEAK FLOW RATE(CFS) = 81.67

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040

*ESTIMATED CHANNEL HEIGHT(FEET) = 0.69

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.69 FLOW VELOCITY(FEET/SEC.) = 10.38

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13903.00 = 1917.34 FEET.

FLOW PROCESS FROM NODE 13903.00 TO NODE 13904.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<

>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 184.89 DOWNSTREAM(FEET) = 155.08

FLOW LENGTH(FEET) = 876.66 MANNING'S N = 0.013

ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000

DEPTH OF FLOW IN 36.0 INCH PIPE IS 22.2 INCHES

PIPE-FLOW VELOCITY(FEET/SEC.) = 17.86

ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1

PIPE-FLOW(CFS) = 81.67

PIPE TRAVEL TIME(MIN.) = 0.82 Tc(MIN.) = 14.60

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13904.00 = 2794.00 FEET.

FLOW PROCESS FROM NODE 13903.00 TO NODE 13904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 14.60

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.668

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	21.29	0.30	0.996	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.996

SUBAREA AREA(ACRES) = 21.29 SUBAREA RUNOFF(CFS) = 45.40

EFFECTIVE AREA(ACRES) = 57.61 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 57.6 PEAK FLOW RATE(CFS) = 122.93

FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<

>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 155.08 DOWNSTREAM(FEET) = 118.00

FLOW LENGTH(FEET) = 1961.38 MANNING'S N = 0.013

DEPTH OF FLOW IN 42.0 INCH PIPE IS 32.3 INCHES

PIPE-FLOW VELOCITY(FEET/SEC.) = 15.50

ESTIMATED PIPE DIAMETER(INCH) = 42.00 NUMBER OF PIPES = 1

PIPE-FLOW(CFS) = 122.93

PIPE TRAVEL TIME(MIN.) = 2.11 Tc(MIN.) = 16.71

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13920.00 = 4755.38 FEET.

FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 16.71

* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.462

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	43.53	0.30	0.649	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.649

SUBAREA AREA(ACRES) = 43.53 SUBAREA RUNOFF(CFS) = 88.82

EFFECTIVE AREA(ACRES) = 101.14 AREA-AVERAGED Fm(INCH/HR) = 0.25

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84

TOTAL AREA(ACRES) = 101.1 PEAK FLOW RATE(CFS) = 201.06

FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<

FLOW PROCESS FROM NODE 13910.00 TO NODE 13910.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<

PEAK FLOWRATE TABLE FILE NAME: RU50EV38.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21766.55	15.46	0.30 (0.25)	0.82	3112.3	13889.00
2	28163.38	32.88	0.30 (0.25)	0.82	7176.8	10360.00
3	30196.15	38.51	0.30 (0.25)	0.82	9238.5	13830.00
4	31931.46	43.60	0.30 (0.25)	0.82	11014.8	110.00
5	33914.79	49.87	0.30 (0.25)	0.82	13805.3	130.00
6	36794.25	58.93	0.30 (0.25)	0.84	18360.6	50260.00
7	38688.56	67.74	0.30 (0.26)	0.86	23072.2	13600.00
8	41028.06	80.68	0.30 (0.26)	0.88	29704.5	13100.00
9	41681.09	87.33	0.30 (0.27)	0.89	32675.1	11801.00
10	44129.55	102.08	0.30 (0.27)	0.91	40785.1	13510.00
11	46752.64	115.22	0.30 (0.28)	0.92	49773.3	10800.00
12	47168.86	119.38	0.30 (0.28)	0.93	52718.7	11130.00
13	46618.46	129.03	0.30 (0.28)	0.93	57759.9	12410.00
14	45897.66	137.39	0.30 (0.28)	0.94	61499.0	11201.00
15	45402.08	142.42	0.30 (0.28)	0.94	63230.7	12201.00
16	44310.11	149.62	0.30 (0.28)	0.94	65087.9	12231.00
17	42931.48	157.61	0.30 (0.28)	0.94	66722.2	10400.00
18	41506.79	165.75	0.30 (0.28)	0.94	68017.2	12010.00
19	40259.55	171.89	0.30 (0.28)	0.94	68364.2	10210.00
20	35856.12	200.76	0.30 (0.28)	0.94	69102.6	10100.00
TOTAL AREA (ACRES) =						69102.6

FLOW PROCESS FROM NODE 13910.00 TO NODE 13910.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21766.55	15.46	0.30 (0.25)	0.82	3112.3	13889.00
2	28163.38	32.88	0.30 (0.25)	0.82	7176.8	10360.00
3	30196.15	38.51	0.30 (0.25)	0.82	9238.5	13830.00
4	31931.46	43.60	0.30 (0.25)	0.82	11014.8	110.00
5	33914.79	49.87	0.30 (0.25)	0.82	13805.3	130.00
6	36794.25	58.93	0.30 (0.25)	0.84	18360.6	50260.00
7	38688.56	67.74	0.30 (0.26)	0.86	23072.2	13600.00
8	41028.06	80.68	0.30 (0.26)	0.88	29704.5	13100.00
9	41681.09	87.33	0.30 (0.27)	0.89	32675.1	11801.00
10	44129.55	102.08	0.30 (0.27)	0.91	40785.1	13510.00
11	46752.64	115.22	0.30 (0.28)	0.92	49773.3	10800.00
12	47168.86	119.38	0.30 (0.28)	0.93	52718.7	11130.00
13	46618.46	129.03	0.30 (0.28)	0.93	57759.9	12410.00
14	45897.66	137.39	0.30 (0.28)	0.94	61499.0	11201.00
15	45402.08	142.42	0.30 (0.28)	0.94	63230.7	12201.00
16	44310.11	149.62	0.30 (0.28)	0.94	65087.9	12231.00
17	42931.48	157.61	0.30 (0.28)	0.94	66722.2	10400.00
18	41506.79	165.75	0.30 (0.28)	0.94	68017.2	12010.00
19	40259.55	171.89	0.30 (0.28)	0.94	68364.2	10210.00
20	35856.12	200.76	0.30 (0.28)	0.94	69102.6	10100.00
TOTAL AREA (ACRES) =						69102.6

FLOW PROCESS FROM NODE 13910.00 TO NODE 13920.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 119.70 DOWNSTREAM(FEET) = 118.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1376.26 CHANNEL SLOPE = 0.0012
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 22.98
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.834
 SUBAREA LOSS RATE DATA(AMC II):
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
 USER-DEFINED - 96.09 0.30 0.535 -
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.535
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 47197.97
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.70
 AVERAGE FLOW DEPTH(FEET) = 22.98 TRAVEL TIME(MIN.) = 2.14
 Tc(MIN.) = 121.52
 SUBAREA AREA(ACRES) = 96.09 SUBAREA RUNOFF(CFS) = 58.23
 EFFECTIVE AREA(ACRES) = 52814.79 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
 TOTAL AREA(ACRES) = 69198.7 PEAK FLOW RATE(CFS) = 47168.86
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 22.97

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 22.97 FLOW VELOCITY(FEET/SEC.) = 10.70

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136633.22 FEET.

FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

** MAIN STREAM CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21766.55	18.11	2.343	0.30 (0.24)	0.81	3208.4	13889.00
2	28163.38	35.35	1.565	0.30 (0.25)	0.82	7272.9	10360.00
3	30196.15	40.93	1.429	0.30 (0.25)	0.82	9334.6	13830.00
4	31931.46	45.98	1.347	0.30 (0.24)	0.82	11110.9	110.00
5	33914.79	52.22	1.257	0.30 (0.25)	0.82	13901.4	130.00
6	36794.25	61.23	1.161	0.30 (0.25)	0.83	18456.7	50260.00
7	38688.56	70.01	1.102	0.30 (0.26)	0.86	23168.3	13600.00
8	41028.06	82.90	1.016	0.30 (0.26)	0.88	29800.5	13100.00
9	41681.09	89.54	0.971	0.30 (0.27)	0.89	32771.2	11801.00
10	44129.55	104.27	0.906	0.30 (0.27)	0.91	40881.2	13510.00
11	46752.64	117.37	0.849	0.30 (0.28)	0.92	49869.4	10800.00
12	47168.86	121.52	0.834	0.30 (0.28)	0.93	52814.8	11130.00
13	46618.46	131.18	0.814	0.30 (0.28)	0.93	57856.0	12410.00
14	45897.66	139.55	0.796	0.30 (0.28)	0.93	61595.1	11201.00
15	45402.08	144.59	0.786	0.30 (0.28)	0.94	63326.8	12201.00
16	44310.11	151.80	0.771	0.30 (0.28)	0.94	65184.0	12231.00

17 42931.48 159.81 0.754 0.30(0.28) 0.94 66818.2 10400.00
 18 41506.79 167.97 0.737 0.30(0.28) 0.94 68113.3 12010.00
 19 40259.55 174.13 0.724 0.30(0.28) 0.94 68460.3 10210.00
 20 35856.12 203.07 0.688 0.30(0.28) 0.94 69198.7 10100.00
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136633.22 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	201.06	16.71	2.462	0.30(0.25)	0.84	101.1	13900.00

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13920.00 = 4755.38 FEET.

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21412.97	16.71	2.462	0.30(0.24)	0.82	3060.5	13900.00
2	21956.81	18.11	2.343	0.30(0.24)	0.82	3309.6	13889.00
3	28282.76	35.35	1.565	0.30(0.25)	0.82	7374.1	10360.00
4	30303.19	40.93	1.429	0.30(0.25)	0.82	9435.8	13830.00
5	32031.04	45.98	1.347	0.30(0.24)	0.82	11212.1	110.00
6	34006.17	52.22	1.257	0.30(0.25)	0.82	14002.5	130.00
7	36876.88	61.23	1.161	0.30(0.25)	0.83	18557.8	50260.00
8	38765.83	70.01	1.102	0.30(0.26)	0.86	23269.5	13600.00
9	41097.46	82.90	1.016	0.30(0.26)	0.88	29901.7	13100.00
10	41746.44	89.54	0.971	0.30(0.27)	0.89	32872.3	11801.00
11	44188.95	104.27	0.906	0.30(0.27)	0.91	40982.3	13510.00
12	46806.84	117.37	0.849	0.30(0.28)	0.92	49970.6	10800.00
13	47221.72	121.52	0.834	0.30(0.28)	0.93	52915.9	11130.00
14	46669.50	131.18	0.814	0.30(0.28)	0.93	57957.1	12410.00
15	45947.10	139.55	0.796	0.30(0.28)	0.93	61696.2	11201.00
16	45450.57	144.59	0.786	0.30(0.28)	0.94	63427.9	12201.00
17	44357.23	151.80	0.771	0.30(0.28)	0.94	65285.1	12231.00
18	42977.08	159.81	0.754	0.30(0.28)	0.94	66919.4	10400.00
19	41550.84	167.97	0.737	0.30(0.28)	0.94	68214.5	12010.00
20	40302.44	174.13	0.724	0.30(0.28)	0.94	68561.4	10210.00
21	35895.68	203.07	0.688	0.30(0.28)	0.94	69299.9	10100.00

TOTAL AREA (ACRES) = 69299.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 47221.72 Tc(MIN.) = 121.522
 EFFECTIVE AREA(ACRES) = 52915.93 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA(ACRES) = 69299.9
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136633.22 FEET.

 FLOW PROCESS FROM NODE 13920.00 TO NODE 13921.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 118.00 DOWNSTREAM(FEET) = 115.28
 CHANNEL LENGTH THRU SUBAREA(FEET) = 335.44 CHANNEL SLOPE = 0.0081
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 14.26
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.833
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	134.30	0.30	0.658	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.658
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 47260.15
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 21.10
 AVERAGE FLOW DEPTH(FEET) = 14.26 TRAVEL TIME(MIN.) = 0.26
 Tc(MIN.) = 121.79
 SUBAREA AREA(ACRES) = 134.30 SUBAREA RUNOFF(CFS) = 76.86
 EFFECTIVE AREA(ACRES) = 53050.23 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA(ACRES) = 69434.2 PEAK FLOW RATE(CFS) = 47221.72
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 14.25

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 14.25 FLOW VELOCITY(FEET/SEC.) = 21.10
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13921.00 = 136968.66 FEET.

 FLOW PROCESS FROM NODE 13921.00 TO NODE 14010.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 115.28 DOWNSTREAM(FEET) = 100.00
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1396.08 CHANNEL SLOPE = 0.0109
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 13.18
 * 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.831

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	96.27	0.30	0.723	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.723
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 47248.33
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 23.48
 AVERAGE FLOW DEPTH(FEET) = 13.18 TRAVEL TIME(MIN.) = 0.99
 Tc(MIN.) = 122.78
 SUBAREA AREA(ACRES) = 96.27 SUBAREA RUNOFF(CFS) = 53.23
 EFFECTIVE AREA(ACRES) = 53146.50 AREA-AVERAGED Fm(INCH/HR) = 0.28
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92
 TOTAL AREA(ACRES) = 69530.5 PEAK FLOW RATE(CFS) = 47221.72
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
 *ESTIMATED CHANNEL HEIGHT(FEET) = 13.17

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
 DEPTH(FEET) = 13.17 FLOW VELOCITY(FEET/SEC.) = 23.48
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 14010.00 = 138364.73 FEET.

=====

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 69530.5 TC (MIN.) = 122.78
 EFFECTIVE AREA (ACRES) = 53146.50 AREA-AVERAGED Fm (INCH/HR) = 0.28
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.924
 PEAK FLOW RATE (CFS) = 47221.72

** PEAK FLOW RATE TABLE **

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21412.97	18.30	2.328	0.30 (0.24)	0.81	3291.0	13900.00
2	21956.81	19.69	2.210	0.30 (0.24)	0.81	3540.1	13889.00
3	28282.76	36.81	1.527	0.30 (0.24)	0.81	7604.6	10360.00
4	30303.19	42.36	1.406	0.30 (0.24)	0.81	9666.3	13830.00
5	32031.04	47.39	1.324	0.30 (0.24)	0.81	11442.6	110.00
6	34006.17	53.60	1.241	0.30 (0.25)	0.82	14233.1	130.00
7	36876.88	62.58	1.152	0.30 (0.25)	0.83	18788.4	50260.00
8	38765.83	71.34	1.093	0.30 (0.26)	0.86	23500.0	13600.00
9	41097.46	84.21	1.007	0.30 (0.26)	0.88	30132.3	13100.00
10	41746.44	90.85	0.964	0.30 (0.27)	0.89	33102.9	11801.00
11	44188.95	105.55	0.900	0.30 (0.27)	0.90	41212.9	13510.00
12	46806.84	118.62	0.843	0.30 (0.28)	0.92	50201.1	10800.00
13	47221.72	122.78	0.831	0.30 (0.28)	0.92	53146.5	11130.00
14	46669.50	132.44	0.811	0.30 (0.28)	0.93	58187.7	12410.00
15	45947.10	140.82	0.794	0.30 (0.28)	0.93	61926.8	11201.00
16	45450.57	145.86	0.783	0.30 (0.28)	0.93	63658.5	12201.00
17	44357.23	153.08	0.768	0.30 (0.28)	0.94	65515.7	12231.00
18	42977.08	161.10	0.751	0.30 (0.28)	0.94	67150.0	10400.00
19	41550.84	169.27	0.734	0.30 (0.28)	0.94	68445.0	12010.00
20	40302.44	175.44	0.721	0.30 (0.28)	0.94	68792.0	10210.00
21	35895.68	204.43	0.686	0.30 (0.28)	0.94	69530.5	10100.00

=====
 END OF RATIONAL METHOD ANALYSIS
 =====