

THE RANCH PLAN PLANNED COMMUNITY  
PLANNING AREAS 3 AND 4 RUNOFF MANAGEMENT PLAN

**Michael Baker**  
INTERNATIONAL

**TECHNICAL APPENDIX F.1**

**Rational Method Expected Value  
(2-, 5-, 10-, 25-, 50-, and 100-year) – Free Draining**

\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA 92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S19- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 2-YR RM EV APRIL 2019 ROKAMOTO \*  
\*\*\*\*\*

FILE NAME: RI02EV19.DAT  
TIME/DATE OF STUDY: 17:01 04/08/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 2.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 1.878
- 2) 10.00; 1.253
- 3) 15.00; 0.953
- 4) 20.00; 0.778
- 5) 25.00; 0.670
- 6) 30.00; 0.594
- 7) 40.00; 0.512
- 8) 50.00; 0.455
- 9) 60.00; 0.400
- 10) 90.00; 0.346
- 11) 120.00; 0.290
- 12) 180.00; 0.236
- 13) 360.00; 0.180
- 14) 1200.00; 0.084

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	HIKE LIP (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:

- 1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11900.00 TO NODE 11901.00 IS CODE = 21  
-----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 295.79  
ELEVATION DATA: UPSTREAM(FEET) = 2369.48 DOWNSTREAM(FEET) = 2332.92

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 7.203  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 1.603  
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
RESIDENTIAL ".4 DWELLING/ACRE"	-	1.62	0.60	0.999	0	7.20

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999  
SUBAREA RUNOFF(CFS) = 1.46  
TOTAL AREA(ACRES) = 1.62 PEAK FLOW RATE(CFS) = 1.46

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11901.00 TO NODE 11902.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2332.92 DOWNSTREAM(FEET) = 2297.70  
CHANNEL LENGTH THRU SUBAREA(FEET) = 664.26 CHANNEL SLOPE = 0.0530  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 1.177  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.35	0.60	0.906	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.906  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3.90  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 2.72  
AVERAGE FLOW DEPTH(FEET) = 0.69 TRAVEL TIME(MIN.) = 4.07  
Tc(MIN.) = 11.27  
SUBAREA AREA(ACRES) = 8.35 SUBAREA RUNOFF(CFS) = 4.76  
EFFECTIVE AREA(ACRES) = 9.97 AREA-AVERAGED Fm(INCH/HR) = 0.55  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.92  
TOTAL AREA(ACRES) = 10.0 PEAK FLOW RATE(CFS) = 5.60

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.79 FLOW VELOCITY(FEET/SEC.) = 2.99  
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11902.00 = 960.05 FEET.

\*\*\*\*\*



FLOW PROCESS FROM NODE 11902.00 TO NODE 11902.50 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2297.70 DOWNSTREAM(FEET) = 2263.40
CHANNEL LENGTH THRU SUBAREA(FEET) = 928.77 CHANNEL SLOPE = 0.0369
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.909
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 34.48 0.60 0.904 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.904
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 11.47
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.11
AVERAGE FLOW DEPTH(FEET) = 1.11 TRAVEL TIME(MIN.) = 4.98
Tc(MIN.) = 16.25
SUBAREA AREA(ACRES) = 34.48 SUBAREA RUNOFF(CFS) = 11.39
EFFECTIVE AREA(ACRES) = 44.45 AREA-AVERAGED Fm(INCH/HR) = 0.54
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.91
TOTAL AREA(ACRES) = 44.5 PEAK FLOW RATE(CFS) = 14.59

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.22 FLOW VELOCITY(FEET/SEC.) = 3.29
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11902.50 = 1888.82 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 1902.50 TO NODE 11903.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2263.40 DOWNSTREAM(FEET) = 2252.14
CHANNEL LENGTH THRU SUBAREA(FEET) = 895.50 CHANNEL SLOPE = 0.0126
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.716
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 23.65 0.60 0.958 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.958
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 16.14
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 2.26
AVERAGE FLOW DEPTH(FEET) = 1.54 TRAVEL TIME(MIN.) = 6.61
Tc(MIN.) = 22.86
SUBAREA AREA(ACRES) = 23.65 SUBAREA RUNOFF(CFS) = 3.01
EFFECTIVE AREA(ACRES) = 68.10 AREA-AVERAGED Fm(INCH/HR) = 0.56
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 68.1 PEAK FLOW RATE(CFS) = 14.59
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.48 FLOW VELOCITY(FEET/SEC.) = 2.21

LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11903.00 = 2784.32 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 11903.00 TO NODE 11904.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2252.14 DOWNSTREAM(FEET) = 2186.04
CHANNEL LENGTH THRU SUBAREA(FEET) = 1924.35 CHANNEL SLOPE = 0.0343
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.571
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 68.53 0.60 0.961 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.961
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 15.28
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.24
AVERAGE FLOW DEPTH(FEET) = 1.25 TRAVEL TIME(MIN.) = 9.90
Tc(MIN.) = 32.77
SUBAREA AREA(ACRES) = 68.53 SUBAREA RUNOFF(CFS) = 1.37
EFFECTIVE AREA(ACRES) = 136.63 AREA-AVERAGED Fm(INCH/HR) = 0.57
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.94
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 136.6 PEAK FLOW RATE(CFS) = 14.59
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.23 FLOW VELOCITY(FEET/SEC.) = 3.21
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11904.00 = 4708.67 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 11904.00 TO NODE 11905.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2186.04 DOWNSTREAM(FEET) = 1957.34
CHANNEL LENGTH THRU SUBAREA(FEET) = 1926.87 CHANNEL SLOPE = 0.1187
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.520
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 63.15 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 14.59
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.13

AVERAGE FLOW DEPTH (FEET) = 0.97 TRAVEL TIME (MIN.) = 6.26  
 Tc (MIN.) = 39.03  
 SUBAREA AREA (ACRES) = 63.15 SUBAREA RUNOFF (CFS) = 0.00  
 EFFECTIVE AREA (ACRES) = 199.78 AREA-AVERAGED Fm (INCH/HR) = 0.58  
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.96  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA (ACRES) = 199.8 PEAK FLOW RATE (CFS) = 14.59  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 0.97 FLOW VELOCITY (FEET/SEC.) = 5.13  
 LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11905.00 = 6635.54 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11905.00 TO NODE 11906.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 1957.34 DOWNSTREAM (FEET) = 1244.16  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 2498.96 CHANNEL SLOPE = 0.2854  
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.484

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	84.87	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 14.59  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.08  
 AVERAGE FLOW DEPTH (FEET) = 0.83 TRAVEL TIME (MIN.) = 5.88  
 Tc (MIN.) = 44.91  
 SUBAREA AREA (ACRES) = 84.87 SUBAREA RUNOFF (CFS) = 0.00  
 EFFECTIVE AREA (ACRES) = 284.65 AREA-AVERAGED Fm (INCH/HR) = 0.58  
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.97  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA (ACRES) = 284.6 PEAK FLOW RATE (CFS) = 14.59  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 0.83 FLOW VELOCITY (FEET/SEC.) = 7.08  
 LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11906.00 = 9134.50 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11906.00 TO NODE 11920.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 1244.16 DOWNSTREAM (FEET) = 873.95  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 3370.75 CHANNEL SLOPE = 0.1098  
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.421  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	199.43	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 14.59  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.97  
 AVERAGE FLOW DEPTH (FEET) = 0.99 TRAVEL TIME (MIN.) = 11.30  
 Tc (MIN.) = 56.21

SUBAREA AREA (ACRES) = 199.43 SUBAREA RUNOFF (CFS) = 0.00  
 EFFECTIVE AREA (ACRES) = 484.08 AREA-AVERAGED Fm (INCH/HR) = 0.59  
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.98  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA (ACRES) = 484.1 PEAK FLOW RATE (CFS) = 14.59  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 0.99 FLOW VELOCITY (FEET/SEC.) = 4.97  
 LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11920.00 = 12505.25 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11906.00 TO NODE 11920.00 IS CODE = 1  
 -----

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
 TIME OF CONCENTRATION (MIN.) = 56.21  
 RAINFALL INTENSITY (INCH/HR) = 0.42  
 AREA-AVERAGED Fm (INCH/HR) = 0.59  
 AREA-AVERAGED Fp (INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.98  
 EFFECTIVE STREAM AREA (ACRES) = 484.08  
 TOTAL STREAM AREA (ACRES) = 484.08  
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 14.59

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11910.00 TO NODE 11911.00 IS CODE = 21  
 -----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH (FEET) = 517.62  
 ELEVATION DATA: UPSTREAM (FEET) = 2531.88 DOWNSTREAM (FEET) = 2441.33

Tc = K \* [(LENGTH \*\* 3.00) / (ELEVATION CHANGE)] \*\* 0.20  
 SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 12.185  
 \* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 1.122  
 SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER						

"CHAPARRAL,BROADLEAF" - 3.46 0.60 1.000 0 12.19  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA RUNOFF(CFS) = 1.63  
TOTAL AREA(ACRES) = 3.46 PEAK FLOW RATE(CFS) = 1.63

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11911.00 TO NODE 11912.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2441.33 DOWNSTREAM(FEET) = 2382.20  
CHANNEL LENGTH THRU SUBAREA(FEET) = 397.30 CHANNEL SLOPE = 0.1488  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 1.012  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.79	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2.71  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.63  
AVERAGE FLOW DEPTH(FEET) = 0.50 TRAVEL TIME(MIN.) = 1.82  
Tc(MIN.) = 14.01  
SUBAREA AREA(ACRES) = 5.79 SUBAREA RUNOFF(CFS) = 2.15  
EFFECTIVE AREA(ACRES) = 9.25 AREA-AVERAGED Fm(INCH/HR) = 0.60  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 9.2 PEAK FLOW RATE(CFS) = 3.43

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.54 FLOW VELOCITY(FEET/SEC.) = 3.86  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11912.00 = 914.92 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11912.00 TO NODE 11913.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2382.20 DOWNSTREAM(FEET) = 2263.77  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1891.47 CHANNEL SLOPE = 0.0626  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.702  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	54.30	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 6.71  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.32  
AVERAGE FLOW DEPTH(FEET) = 0.82 TRAVEL TIME(MIN.) = 9.50  
Tc(MIN.) = 23.51  
SUBAREA AREA(ACRES) = 54.30 SUBAREA RUNOFF(CFS) = 5.00

EFFECTIVE AREA(ACRES) = 63.55 AREA-AVERAGED Fm(INCH/HR) = 0.60  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 63.5 PEAK FLOW RATE(CFS) = 5.85

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.78 FLOW VELOCITY(FEET/SEC.) = 3.20  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11913.00 = 2806.39 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11913.00 TO NODE 11914.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2263.77 DOWNSTREAM(FEET) = 1845.23  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1957.31 CHANNEL SLOPE = 0.2138  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.595  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	65.14	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 6.01  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.07  
AVERAGE FLOW DEPTH(FEET) = 0.63 TRAVEL TIME(MIN.) = 6.43  
Tc(MIN.) = 29.94  
SUBAREA AREA(ACRES) = 65.14 SUBAREA RUNOFF(CFS) = 0.00  
EFFECTIVE AREA(ACRES) = 128.69 AREA-AVERAGED Fm(INCH/HR) = 0.60  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
TOTAL AREA(ACRES) = 128.7 PEAK FLOW RATE(CFS) = 5.85  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.62 FLOW VELOCITY(FEET/SEC.) = 5.06  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11914.00 = 4763.70 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11914.00 TO NODE 11915.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 1845.23 DOWNSTREAM(FEET) = 1557.21  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1686.78 CHANNEL SLOPE = 0.1708  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.545  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	78.52	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5.85  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.68  
AVERAGE FLOW DEPTH(FEET) = 0.65 TRAVEL TIME(MIN.) = 6.01  
Tc(MIN.) = 35.95  
SUBAREA AREA(ACRES) = 78.52 SUBAREA RUNOFF(CFS) = 0.00  
EFFECTIVE AREA(ACRES) = 207.21 AREA-AVERAGED Fm(INCH/HR) = 0.60  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
TOTAL AREA(ACRES) = 207.2 PEAK FLOW RATE(CFS) = 5.85  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.65 FLOW VELOCITY(FEET/SEC.) = 4.68  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11915.00 = 6450.48 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11915.00 TO NODE 11916.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<  
=====

ELEVATION DATA: UPSTREAM(FEET) = 1557.21 DOWNSTREAM(FEET) = 1403.38  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1909.39 CHANNEL SLOPE = 0.0806  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.484  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 70.48 0.60 1.000 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5.85  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.52  
AVERAGE FLOW DEPTH(FEET) = 0.74 TRAVEL TIME(MIN.) = 9.05  
Tc(MIN.) = 44.99  
SUBAREA AREA(ACRES) = 70.48 SUBAREA RUNOFF(CFS) = 0.00  
EFFECTIVE AREA(ACRES) = 277.69 AREA-AVERAGED Fm(INCH/HR) = 0.60  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
TOTAL AREA(ACRES) = 277.7 PEAK FLOW RATE(CFS) = 5.85  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.74 FLOW VELOCITY(FEET/SEC.) = 3.52  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11916.00 = 8359.87 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11916.00 TO NODE 11917.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<  
=====

ELEVATION DATA: UPSTREAM(FEET) = 1403.38 DOWNSTREAM(FEET) = 1079.99  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1945.82 CHANNEL SLOPE = 0.1662  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.444  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 232.20 0.60 1.000 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5.85  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.60  
AVERAGE FLOW DEPTH(FEET) = 0.65 TRAVEL TIME(MIN.) = 7.05  
Tc(MIN.) = 52.04  
SUBAREA AREA(ACRES) = 232.20 SUBAREA RUNOFF(CFS) = 0.00  
EFFECTIVE AREA(ACRES) = 509.89 AREA-AVERAGED Fm(INCH/HR) = 0.60  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
TOTAL AREA(ACRES) = 509.9 PEAK FLOW RATE(CFS) = 5.85  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.65 FLOW VELOCITY(FEET/SEC.) = 4.60  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11917.00 = 10305.69 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11917.00 TO NODE 11920.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<  
=====

ELEVATION DATA: UPSTREAM(FEET) = 1079.99 DOWNSTREAM(FEET) = 873.95  
CHANNEL LENGTH THRU SUBAREA(FEET) = 2563.91 CHANNEL SLOPE = 0.0804  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.392  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 110.82 0.60 1.000 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5.85  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.52  
AVERAGE FLOW DEPTH(FEET) = 0.74 TRAVEL TIME(MIN.) = 12.15  
Tc(MIN.) = 64.19  
SUBAREA AREA(ACRES) = 110.82 SUBAREA RUNOFF(CFS) = 0.00  
EFFECTIVE AREA(ACRES) = 620.71 AREA-AVERAGED Fm(INCH/HR) = 0.60  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA (ACRES) = 620.7 PEAK FLOW RATE (CFS) = 5.85  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 0.74 FLOW VELOCITY (FEET/SEC.) = 3.52  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11920.00 = 12869.60 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11917.00 TO NODE 11920.00 IS CODE = 1  
 -----

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

-----  
 TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
 TIME OF CONCENTRATION (MIN.) = 64.19  
 RAINFALL INTENSITY (INCH/HR) = 0.39  
 AREA-AVERAGED Fm (INCH/HR) = 0.60  
 AREA-AVERAGED Fp (INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 1.00  
 EFFECTIVE STREAM AREA (ACRES) = 620.71  
 TOTAL STREAM AREA (ACRES) = 620.71  
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 5.85

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14.59	56.21	0.421	0.60 ( 0.59)	0.98	484.1	11900.00
2	5.85	64.19	0.392	0.60 ( 0.60)	1.00	620.7	11910.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20.08	56.21	0.421	0.60 ( 0.60)	0.99	1027.6	11900.00
2	19.46	64.19	0.392	0.60 ( 0.60)	0.99	1104.8	11910.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:  
 PEAK FLOW RATE (CFS) = 20.08 Tc (MIN.) = 56.21  
 EFFECTIVE AREA (ACRES) = 1027.65 AREA-AVERAGED Fm (INCH/HR) = 0.60  
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA (ACRES) = 1104.8  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11920.00 = 12869.60 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11920.00 TO NODE 11921.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

-----  
 ELEVATION DATA: UPSTREAM (FEET) = 873.95 DOWNSTREAM (FEET) = 827.94  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1417.25 CHANNEL SLOPE = 0.0325  
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00

\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.394  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 107.47 0.60 1.000 -  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 20.08  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 3.41  
 AVERAGE FLOW DEPTH (FEET) = 1.40 TRAVEL TIME (MIN.) = 6.93  
 Tc (MIN.) = 63.14  
 SUBAREA AREA (ACRES) = 107.47 SUBAREA RUNOFF (CFS) = 0.00  
 EFFECTIVE AREA (ACRES) = 1135.12 AREA-AVERAGED Fm (INCH/HR) = 0.60  
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA (ACRES) = 1212.3 PEAK FLOW RATE (CFS) = 20.08  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 1.40 FLOW VELOCITY (FEET/SEC.) = 3.41  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11921.00 = 14286.85 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11921.00 TO NODE 11922.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

-----  
 ELEVATION DATA: UPSTREAM (FEET) = 827.94 DOWNSTREAM (FEET) = 753.55  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1886.43 CHANNEL SLOPE = 0.0394  
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.379

SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 344.27 0.60 1.000 -  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 20.08  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 3.66  
 AVERAGE FLOW DEPTH (FEET) = 1.35 TRAVEL TIME (MIN.) = 8.60  
 Tc (MIN.) = 71.74  
 SUBAREA AREA (ACRES) = 344.27 SUBAREA RUNOFF (CFS) = 0.00  
 EFFECTIVE AREA (ACRES) = 1479.39 AREA-AVERAGED Fm (INCH/HR) = 0.60  
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA (ACRES) = 1556.5 PEAK FLOW RATE (CFS) = 20.08  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 1.35 FLOW VELOCITY (FEET/SEC.) = 3.66

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11922.00 = 16173.28 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11922.00 TO NODE 11923.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 753.55 DOWNSTREAM(FEET) = 641.58  
CHANNEL LENGTH THRU SUBAREA(FEET) = 2860.88 CHANNEL SLOPE = 0.0391  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.355

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	165.18	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 20.08

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.65

AVERAGE FLOW DEPTH(FEET) = 1.36 TRAVEL TIME(MIN.) = 13.08

Tc(MIN.) = 84.82

SUBAREA AREA(ACRES) = 165.18 SUBAREA RUNOFF(CFS) = 0.00

EFFECTIVE AREA(ACRES) = 1644.57 AREA-AVERAGED Fm(INCH/HR) = 0.60

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.000

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 1721.7 PEAK FLOW RATE(CFS) = 20.08

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.36 FLOW VELOCITY(FEET/SEC.) = 3.65

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11923.00 = 19034.16 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11923.00 TO NODE 11924.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 641.58 DOWNSTREAM(FEET) = 579.89  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1844.02 CHANNEL SLOPE = 0.0335  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.339

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	433.73	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 20.08

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.45

AVERAGE FLOW DEPTH(FEET) = 1.39 TRAVEL TIME(MIN.) = 8.91

Tc(MIN.) = 93.73

SUBAREA AREA(ACRES) = 433.73 SUBAREA RUNOFF(CFS) = 0.00

EFFECTIVE AREA(ACRES) = 2078.30 AREA-AVERAGED Fm(INCH/HR) = 0.60

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.000

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 2155.4 PEAK FLOW RATE(CFS) = 20.08

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.39 FLOW VELOCITY(FEET/SEC.) = 3.45

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11924.00 = 20878.18 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11924.00 TO NODE 11925.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 579.89 DOWNSTREAM(FEET) = 494.12  
CHANNEL LENGTH THRU SUBAREA(FEET) = 2756.15 CHANNEL SLOPE = 0.0311  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.313

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	265.42	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 20.08

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.35

AVERAGE FLOW DEPTH(FEET) = 1.41 TRAVEL TIME(MIN.) = 13.73

Tc(MIN.) = 107.46

SUBAREA AREA(ACRES) = 265.42 SUBAREA RUNOFF(CFS) = 0.00

EFFECTIVE AREA(ACRES) = 2343.72 AREA-AVERAGED Fm(INCH/HR) = 0.60

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.000

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 2420.9 PEAK FLOW RATE(CFS) = 20.08

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.41 FLOW VELOCITY(FEET/SEC.) = 3.35

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11925.00 = 23634.33 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11925.00 TO NODE 11926.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 494.12 DOWNSTREAM(FEET) = 458.40  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1922.70 CHANNEL SLOPE = 0.0186  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.292  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 97.46 0.60 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 20.08  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 2.75  
 AVERAGE FLOW DEPTH (FEET) = 1.56 TRAVEL TIME (MIN.) = 11.64  
 Tc (MIN.) = 119.10  
 SUBAREA AREA (ACRES) = 97.46 SUBAREA RUNOFF (CFS) = 0.00  
 EFFECTIVE AREA (ACRES) = 2441.18 AREA-AVERAGED Fm (INCH/HR) = 0.60  
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA (ACRES) = 2518.3 PEAK FLOW RATE (CFS) = 20.08  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 1.56 FLOW VELOCITY (FEET/SEC.) = 2.75  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11926.00 = 25557.03 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11926.00 TO NODE 11927.00 IS CODE = 51  
 -----

>>>> COMPUTE TRAPEZOIDAL CHANNEL FLOW <<<<<  
 >>>> TRAVELTIME THRU SUBAREA (EXISTING ELEMENT) <<<<<  
 -----

ELEVATION DATA: UPSTREAM (FEET) = 458.40 DOWNSTREAM (FEET) = 399.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 2170.13 CHANNEL SLOPE = 0.0274  
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.281  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 53.83 0.60 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 20.08  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 3.20  
 AVERAGE FLOW DEPTH (FEET) = 1.45 TRAVEL TIME (MIN.) = 11.31  
 Tc (MIN.) = 130.41  
 SUBAREA AREA (ACRES) = 53.83 SUBAREA RUNOFF (CFS) = 0.00  
 EFFECTIVE AREA (ACRES) = 2495.01 AREA-AVERAGED Fm (INCH/HR) = 0.60  
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA (ACRES) = 2572.1 PEAK FLOW RATE (CFS) = 20.08  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 1.45 FLOW VELOCITY (FEET/SEC.) = 3.20  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 27727.16 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 15.1  
 -----

>>>> DEFINE MEMORY BANK # 1 <<<<<  
 =====

PEAK FLOWRATE TABLE FILE NAME: 0610401T.DNA  
 MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	48.82	37.99	0.60 ( 0.60)	1.00	610.3	40120.00
2	48.79	41.62	0.60 ( 0.60)	1.00	652.1	40100.00
TOTAL AREA (ACRES) =			652.1			

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 11  
 -----

>>>> CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY <<<<<  
 =====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20.08	130.41	0.281	0.60 ( 0.60)	1.00	2495.0	11900.00
2	19.46	139.01	0.273	0.60 ( 0.60)	1.00	2572.1	11910.00
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 27727.16 FEET.							

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	48.82	37.99	0.529	0.60 ( 0.60)	1.00	610.3	40120.00
2	48.79	41.62	0.503	0.60 ( 0.60)	1.00	652.1	40100.00
LONGEST FLOWPATH FROM NODE 40100.00 TO NODE 11927.00 = 10245.00 FEET.							

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	59.84	37.99	0.529	0.60 ( 0.60)	1.00	1337.1	40120.00
2	60.27	41.62	0.503	0.60 ( 0.60)	1.00	1448.3	40100.00
3	47.31	130.41	0.281	0.60 ( 0.60)	1.00	3147.1	11900.00
4	45.94	139.01	0.273	0.60 ( 0.60)	1.00	3224.2	11910.00
TOTAL AREA (ACRES) =			3224.2				

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 60.27 Tc (MIN.) = 41.615  
 EFFECTIVE AREA (ACRES) = 1448.28 AREA-AVERAGED Fm (INCH/HR) = 0.60  
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA (ACRES) = 3224.2  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 27727.16 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.50 IS CODE = 51  
 -----

>>>> COMPUTE TRAPEZOIDAL CHANNEL FLOW <<<<<  
 >>>> TRAVELTIME THRU SUBAREA (EXISTING ELEMENT) <<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 399.00 DOWNSTREAM(FEET) = 384.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 986.26 CHANNEL SLOPE = 0.0152  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
 CHANNEL FLOW THRU SUBAREA(CFS) = 60.27  
 FLOW VELOCITY(FEET/SEC.) = 3.36 FLOW DEPTH(FEET) = 2.44  
 TRAVEL TIME(MIN.) = 4.89 Tc(MIN.) = 46.50  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.50 = 28713.42 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 1 <<<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 1 <<<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610402T.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9.62	15.91	0.60 ( 0.60)	1.00	33.3	40200.00
TOTAL AREA (ACRES) =			33.3			

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	59.84	42.88	0.496	0.60 ( 0.60)	1.00	1337.1	40120.00
2	60.27	46.50	0.475	0.60 ( 0.60)	1.00	1448.3	40100.00
3	47.31	135.59	0.276	0.60 ( 0.60)	1.00	3147.1	11900.00
4	45.94	144.24	0.268	0.60 ( 0.60)	1.00	3224.2	11910.00
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.50 =			28713.42 FEET.				

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9.62	15.91	0.921	0.60 ( 0.60)	1.00	33.3	40200.00
LONGEST FLOWPATH FROM NODE 40200.00 TO NODE 11927.50 =			1999.00 FEET.				

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	50.89	15.91	0.921	0.60 ( 0.60)	1.00	529.5	40200.00
2	59.84	42.88	0.496	0.60 ( 0.60)	1.00	1370.4	40120.00
3	60.27	46.50	0.475	0.60 ( 0.60)	1.00	1481.6	40100.00
4	47.31	135.59	0.276	0.60 ( 0.60)	1.00	3180.4	11900.00
5	45.94	144.24	0.268	0.60 ( 0.60)	1.00	3257.5	11910.00
TOTAL AREA (ACRES) =			3257.5				

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:  
 PEAK FLOW RATE(CFS) = 60.27 Tc(MIN.) = 46.504  
 EFFECTIVE AREA(ACRES) = 1481.59 AREA-AVERAGED Fm(INCH/HR) = 0.60  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 3257.5  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.50 = 28713.42 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11927.50 TO NODE 11928.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 384.00 DOWNSTREAM(FEET) = 359.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 647.19 CHANNEL SLOPE = 0.0386  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.462

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	78.01	0.60	0.984	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.984

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 60.53

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.78

AVERAGE FLOW DEPTH(FEET) = 2.06 TRAVEL TIME(MIN.) = 2.26

Tc(MIN.) = 48.76

SUBAREA AREA(ACRES) = 78.01 SUBAREA RUNOFF(CFS) = 0.52

EFFECTIVE AREA(ACRES) = 1559.60 AREA-AVERAGED Fm(INCH/HR) = 0.60

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 3335.5 PEAK FLOW RATE(CFS) = 60.27

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.05 FLOW VELOCITY(FEET/SEC.) = 4.78

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11928.00 = 29360.61 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	133.47	18.17	0.842	0.60 ( 0.60)	1.00	607.5	40200.00
2	59.84	45.14	0.483	0.60 ( 0.60)	1.00	1448.4	40120.00
3	60.27	48.76	0.462	0.60 ( 0.60)	1.00	1559.6	40100.00
4	47.31	137.99	0.274	0.60 ( 0.60)	1.00	3258.4	11900.00
5	45.94	146.66	0.266	0.60 ( 0.60)	1.00	3335.5	11910.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 133.47 Tc(MIN.) = 18.17

AREA-AVERAGED Fm(INCH/HR) = 0.60 AREA-AVERAGED Fp(INCH/HR) = 0.60

AREA-AVERAGED Ap = 1.00 EFFECTIVE AREA(ACRES) = 607.52

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 51  
 -----



>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 359.00 DOWNSTREAM(FEET) = 341.63  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1322.66 CHANNEL SLOPE = 0.0131  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.695  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 8.18 0.60 0.890 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.890  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 134.07  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.89  
AVERAGE FLOW DEPTH(FEET) = 3.39 TRAVEL TIME(MIN.) = 5.67  
Tc(MIN.) = 23.84  
SUBAREA AREA(ACRES) = 8.18 SUBAREA RUNOFF(CFS) = 1.19  
EFFECTIVE AREA(ACRES) = 615.70 AREA-AVERAGED Fm(INCH/HR) = 0.60  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 3343.7 PEAK FLOW RATE(CFS) = 133.47  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 3.38 FLOW VELOCITY(FEET/SEC.) = 3.89  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11929.00 = 30683.27 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	133.47	23.84	0.695	0.60( 0.60)	1.00	615.7	40200.00
2	59.84	52.05	0.444	0.60( 0.60)	1.00	1456.6	40120.00
3	60.27	55.67	0.424	0.60( 0.60)	1.00	1567.8	40100.00
4	47.31	145.32	0.267	0.60( 0.60)	1.00	3266.6	11900.00
5	45.94	154.05	0.259	0.60( 0.60)	1.00	3343.7	11910.00

NEW PEAK FLOW DATA ARE:  
PEAK FLOW RATE(CFS) = 133.47 Tc(MIN.) = 23.84  
AREA-AVERAGED Fm(INCH/HR) = 0.60 AREA-AVERAGED Fp(INCH/HR) = 0.60  
AREA-AVERAGED Ap = 1.00 EFFECTIVE AREA(ACRES) = 615.70

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 10  
-----

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 3<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11841.00 TO NODE 11527.00 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 1<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11841.00 TO NODE 12527.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1<<<<

PEAK FLOWRATE TABLE FILE NAME: S18X02.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	368.65	67.72	0.60( 0.60)	0.99	5288.9	11831.00
2	465.61	93.02	0.60( 0.60)	0.99	7637.9	11530.00
3	535.78	108.89	0.60( 0.60)	0.99	9918.6	11701.00
4	556.64	113.96	0.60( 0.60)	0.99	10678.6	11000.00
5	648.54	131.44	0.60( 0.60)	1.00	14702.7	11350.00
6	669.95	137.84	0.60( 0.60)	1.00	16212.5	10850.00
7	634.45	145.72	0.60( 0.60)	1.00	17563.5	10800.00
8	586.10	152.52	0.60( 0.60)	1.00	18539.6	11220.00
9	519.45	163.12	0.60( 0.60)	1.00	19646.2	10910.00
10	469.53	171.24	0.60( 0.60)	1.00	20293.7	10630.00
11	347.01	209.19	0.60( 0.60)	1.00	24538.0	10600.00
12	331.29	220.41	0.60( 0.60)	1.00	26174.2	11600.00
13	322.91	238.24	0.60( 0.60)	1.00	28033.8	10710.00
14	317.31	246.05	0.60( 0.60)	1.00	28544.1	10410.00
15	303.17	267.47	0.60( 0.60)	1.00	29747.0	10700.00
16	301.61	284.97	0.60( 0.60)	1.00	30768.1	10200.00
17	295.49	303.27	0.60( 0.60)	1.00	31516.6	10320.00
18	293.33	307.96	0.60( 0.60)	1.00	31656.1	10300.00
19	283.27	326.33	0.60( 0.60)	1.00	31924.4	10210.00
20	238.59	442.68	0.60( 0.60)	1.00	32916.6	10100.00

TOTAL AREA(ACRES) = 32916.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 2<<<<

\*\*\*\*\*  
MEMORY BANK # 2 IS EMPTY - PROCESS IGNORED.  
\*\*\*\*\*

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 2<<<<

PEAK FLOWRATE TABLE FILE NAME: S25X02.DNA  
MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	125.40	141.27	0.60( 0.59)	0.99	4854.0	12500.00
2	161.45	169.35	0.60( 0.59)	0.99	6554.4	12300.00
3	161.10	174.44	0.60( 0.59)	0.99	6936.3	12330.00
4	157.88	201.19	0.60( 0.59)	0.98	8762.3	12410.00
5	155.88	214.55	0.60( 0.59)	0.98	9659.4	12400.00
6	155.08	218.12	0.60( 0.59)	0.98	9844.2	12211.00
7	166.76	226.18	0.60( 0.59)	0.98	10504.5	12201.00
8	174.86	233.49	0.60( 0.58)	0.97	10953.4	12261.00
9	174.65	235.08	0.60( 0.58)	0.98	11005.7	12111.00
10	174.14	239.69	0.60( 0.59)	0.98	11204.7	12231.00
11	171.80	258.00	0.60( 0.59)	0.98	11864.4	12101.10
12	151.73	298.09	0.60( 0.59)	0.98	13091.3	12010.00
13	99.71	374.11	0.60( 0.59)	0.98	13237.1	12000.00

TOTAL AREA(ACRES) = 13237.1

\*\*\*\*\*

FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	125.40	141.27	0.60 ( 0.59)	0.99	4854.0	12500.00
2	161.45	169.35	0.60 ( 0.59)	0.99	6554.4	12300.00
3	161.10	174.44	0.60 ( 0.59)	0.99	6936.3	12330.00
4	157.88	201.19	0.60 ( 0.59)	0.98	8762.3	12410.00
5	155.88	214.55	0.60 ( 0.59)	0.98	9659.4	12400.00
6	155.08	218.12	0.60 ( 0.59)	0.98	9844.2	12211.00
7	166.76	226.18	0.60 ( 0.59)	0.98	10504.5	12201.00
8	174.86	233.49	0.60 ( 0.58)	0.97	10953.4	12261.00
9	174.65	235.08	0.60 ( 0.58)	0.98	11005.7	12111.00
10	174.14	239.69	0.60 ( 0.59)	0.98	11204.7	12231.00
11	171.80	258.00	0.60 ( 0.59)	0.98	11864.4	12101.10
12	151.73	298.09	0.60 ( 0.59)	0.98	13091.3	12010.00
13	99.71	374.11	0.60 ( 0.59)	0.98	13237.1	12000.00
TOTAL AREA (ACRES) =						13237.1

\*\*\*\*\*

FLOW PROCESS FROM NODE 11841.00 TO NODE 12527.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	125.40	141.27	0.271	0.60 ( 0.59)	0.99	4854.0	12500.00
2	161.45	169.35	0.246	0.60 ( 0.59)	0.99	6554.4	12300.00
3	161.10	174.44	0.241	0.60 ( 0.59)	0.99	6936.3	12330.00
4	157.88	201.19	0.229	0.60 ( 0.59)	0.98	8762.3	12410.00
5	155.88	214.55	0.225	0.60 ( 0.59)	0.98	9659.4	12400.00
6	155.08	218.12	0.224	0.60 ( 0.59)	0.98	9844.2	12211.00
7	166.76	226.18	0.222	0.60 ( 0.59)	0.98	10504.5	12201.00
8	174.86	233.49	0.219	0.60 ( 0.58)	0.97	10953.4	12261.00
9	174.65	235.08	0.219	0.60 ( 0.58)	0.98	11005.7	12111.00
10	174.14	239.69	0.217	0.60 ( 0.59)	0.98	11204.7	12231.00
11	171.80	258.00	0.212	0.60 ( 0.59)	0.98	11864.4	12101.10
12	151.73	298.09	0.199	0.60 ( 0.59)	0.98	13091.3	12010.00
13	99.71	374.11	0.178	0.60 ( 0.59)	0.98	13237.1	12000.00
LONGEST FLOWPATH FROM NODE 12000.00 TO NODE 12527.00 =							77156.98 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	368.65	67.72	0.386	0.60 ( 0.60)	0.99	5288.9	11831.00
2	465.61	93.02	0.340	0.60 ( 0.60)	0.99	7637.9	11530.00
3	535.78	108.89	0.311	0.60 ( 0.60)	0.99	9918.6	11701.00
4	556.64	113.96	0.301	0.60 ( 0.60)	0.99	10678.6	11000.00
5	648.54	131.44	0.280	0.60 ( 0.60)	1.00	14702.7	11350.00
6	669.95	137.84	0.274	0.60 ( 0.60)	1.00	16212.5	10850.00
7	634.45	145.72	0.267	0.60 ( 0.60)	1.00	17563.5	10800.00
8	586.10	152.52	0.261	0.60 ( 0.60)	1.00	18539.6	11220.00

9	519.45	163.12	0.251	0.60 ( 0.60)	1.00	19646.2	10910.00
10	469.53	171.24	0.244	0.60 ( 0.60)	1.00	20293.7	10630.00
11	347.01	209.19	0.227	0.60 ( 0.60)	1.00	24538.0	10600.00
12	331.29	220.41	0.223	0.60 ( 0.60)	1.00	26174.2	11600.00
13	322.91	238.24	0.218	0.60 ( 0.60)	1.00	28033.8	10710.00
14	317.31	246.05	0.215	0.60 ( 0.60)	1.00	28544.1	10410.00
15	303.17	267.47	0.209	0.60 ( 0.60)	1.00	29747.0	10700.00
16	301.61	284.97	0.203	0.60 ( 0.60)	1.00	30768.1	10200.00
17	295.49	303.27	0.198	0.60 ( 0.60)	1.00	31516.6	10320.00
18	293.33	307.96	0.196	0.60 ( 0.60)	1.00	31656.1	10300.00
19	283.27	326.33	0.190	0.60 ( 0.60)	1.00	31924.4	10210.00
20	238.59	442.68	0.171	0.60 ( 0.60)	1.00	32916.6	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12527.00 = 97868.13 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	454.34	67.72	0.386	0.60 ( 0.60)	0.99	7615.8	11831.00
2	569.38	93.02	0.340	0.60 ( 0.60)	0.99	10834.1	11530.00
3	646.68	108.89	0.311	0.60 ( 0.60)	0.99	13660.2	11701.00
4	669.16	113.96	0.301	0.60 ( 0.60)	0.99	14594.1	11000.00
5	769.03	131.44	0.280	0.60 ( 0.60)	0.99	19219.0	11350.00
6	793.71	137.84	0.274	0.60 ( 0.60)	0.99	20948.8	10850.00
7	779.92	141.27	0.271	0.60 ( 0.60)	0.99	21653.9	12500.00
8	765.57	145.72	0.267	0.60 ( 0.60)	0.99	22687.0	10800.00
9	725.95	152.52	0.261	0.60 ( 0.60)	0.99	24074.8	11220.00
10	672.92	163.12	0.251	0.60 ( 0.60)	0.99	25823.7	10910.00
11	642.64	169.35	0.246	0.60 ( 0.60)	0.99	26696.9	12300.00
12	630.86	171.24	0.244	0.60 ( 0.60)	0.99	26990.1	10630.00
13	620.31	174.44	0.241	0.60 ( 0.60)	0.99	27587.8	12330.00
14	530.72	201.19	0.229	0.60 ( 0.60)	0.99	32405.3	12410.00
15	503.69	209.19	0.227	0.60 ( 0.60)	0.99	33837.6	10600.00
16	495.39	214.55	0.225	0.60 ( 0.60)	0.99	34978.5	12400.00
17	489.58	218.12	0.224	0.60 ( 0.59)	0.99	35684.0	12211.00
18	489.69	220.41	0.223	0.60 ( 0.59)	0.99	36206.2	11600.00
19	495.34	226.18	0.222	0.60 ( 0.59)	0.99	37280.7	12201.00
20	500.01	233.49	0.219	0.60 ( 0.59)	0.99	38491.2	12261.00
21	499.05	235.08	0.219	0.60 ( 0.59)	0.99	38709.5	12111.00
22	497.21	238.24	0.218	0.60 ( 0.59)	0.99	39176.2	10710.00
23	496.02	239.69	0.217	0.60 ( 0.59)	0.99	39332.8	12231.00
24	490.64	246.05	0.215	0.60 ( 0.59)	0.99	39977.8	10410.00
25	481.22	258.00	0.212	0.60 ( 0.59)	0.99	41079.8	12101.10
26	470.23	267.47	0.209	0.60 ( 0.59)	0.99	41901.2	10700.00
27	459.92	284.97	0.203	0.60 ( 0.59)	0.99	43457.9	10200.00
28	448.96	298.09	0.199	0.60 ( 0.59)	0.99	44396.1	12010.00
29	443.68	303.27	0.198	0.60 ( 0.59)	0.99	44617.8	10320.00
30	438.31	307.96	0.196	0.60 ( 0.59)	0.99	44766.3	10300.00
31	415.69	326.33	0.190	0.60 ( 0.60)	0.99	45069.8	10210.00
32	364.64	374.11	0.178	0.60 ( 0.60)	0.99	45568.9	12000.00
33	333.92	442.68	0.171	0.60 ( 0.60)	0.99	46153.7	10100.00
TOTAL AREA (ACRES) =						46153.7	

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 793.71 Tc(MIN.) = 137.844

EFFECTIVE AREA(ACRES) = 20948.83 AREA-AVERAGED Fm(INCH/HR) = 0.60

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 46153.7

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12527.00 = 97868.13 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12527.00 TO NODE 11929.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 347.47 DOWNSTREAM(FEET) = 341.63

CHANNEL LENGTH THRU SUBAREA(FEET) = 532.38 CHANNEL SLOPE = 0.0110

CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00

\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.273

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

USER-DEFINED - 14.37 0.60 0.987 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.987

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 793.73

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.69

AVERAGE FLOW DEPTH(FEET) = 5.86 TRAVEL TIME(MIN.) = 1.15

Tc(MIN.) = 139.00

SUBAREA AREA(ACRES) = 14.37 SUBAREA RUNOFF(CFS) = 0.05

EFFECTIVE AREA(ACRES) = 20963.20 AREA-AVERAGED Fm(INCH/HR) = 0.60

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 46168.0 PEAK FLOW RATE(CFS) = 793.71

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 5.86 FLOW VELOCITY(FEET/SEC.) = 7.69

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Rows 1-19.

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Rows 20-33.

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 793.71 Tc(MIN.) = 139.00

AREA-AVERAGED Fm(INCH/HR) = 0.60 AREA-AVERAGED Fp(INCH/HR) = 0.60

AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 20963.20

\*\*\*\*\*

FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Rows 1-30.

31 415.69 327.68 0.190 0.60( 0.60) 0.99 45084.2 10210.00  
 32 364.64 375.51 0.178 0.60( 0.60) 0.99 45583.3 12000.00  
 33 333.92 444.11 0.170 0.60( 0.60) 0.99 46168.0 10100.00  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	133.47	23.84	0.695	0.60( 0.60)	1.00	615.7	40200.00
2	59.84	52.05	0.444	0.60( 0.60)	1.00	1456.6	40120.00
3	60.27	55.67	0.424	0.60( 0.60)	1.00	1567.8	40100.00
4	47.31	145.32	0.267	0.60( 0.60)	1.00	3266.6	11900.00
5	45.94	154.05	0.259	0.60( 0.60)	1.00	3343.7	11910.00

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11929.00 = 30683.27 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	417.64	23.84	0.695	0.60( 0.60)	0.99	3250.6	40200.00
2	455.91	52.05	0.444	0.60( 0.60)	0.99	7208.8	40120.00
3	464.88	55.67	0.424	0.60( 0.60)	0.99	7720.0	40100.00
4	512.68	69.05	0.384	0.60( 0.60)	0.99	9451.4	11831.00
5	624.07	94.27	0.338	0.60( 0.60)	0.99	13147.6	11530.00
6	699.08	110.11	0.308	0.60( 0.60)	0.99	16273.8	11701.00
7	720.83	115.16	0.299	0.60( 0.60)	0.99	17303.5	11000.00
8	818.18	132.60	0.279	0.60( 0.60)	0.99	22259.0	11350.00
9	841.94	139.00	0.273	0.60( 0.60)	0.99	24109.9	10850.00
10	827.65	142.43	0.270	0.60( 0.60)	0.99	24879.9	12500.00
11	817.91	145.32	0.267	0.60( 0.60)	0.99	25606.1	11900.00
12	812.63	146.88	0.266	0.60( 0.60)	0.99	25981.8	10800.00
13	771.94	153.70	0.260	0.60( 0.60)	0.99	27429.8	11220.00
14	770.10	154.05	0.259	0.60( 0.60)	0.99	27491.7	11910.00
15	717.22	164.33	0.250	0.60( 0.60)	0.99	29181.8	10910.00
16	685.95	170.56	0.244	0.60( 0.60)	0.99	30055.0	12300.00
17	673.86	172.47	0.243	0.60( 0.60)	0.99	30348.2	10630.00
18	662.80	175.67	0.240	0.60( 0.60)	0.99	30945.9	12330.00
19	571.28	202.46	0.229	0.60( 0.60)	0.99	35763.4	12410.00
20	543.81	210.48	0.227	0.60( 0.60)	0.99	37195.7	10600.00
21	535.21	215.85	0.225	0.60( 0.60)	0.99	38336.6	12400.00
22	529.21	219.42	0.224	0.60( 0.60)	0.99	39042.1	12211.00
23	529.19	221.71	0.223	0.60( 0.60)	0.99	39564.3	11600.00
24	534.52	227.48	0.221	0.60( 0.59)	0.99	40638.8	12201.00
25	538.79	234.78	0.219	0.60( 0.59)	0.99	41849.3	12261.00
26	537.75	236.37	0.218	0.60( 0.59)	0.99	42067.6	12111.00
27	535.73	239.54	0.217	0.60( 0.59)	0.99	42534.3	10710.00
28	534.46	240.98	0.217	0.60( 0.59)	0.99	42690.9	12231.00
29	535.73	239.54	0.217	0.60( 0.59)	0.99	42534.3	10710.00
30	534.46	240.98	0.217	0.60( 0.59)	0.99	42690.9	12231.00
31	528.73	247.35	0.215	0.60( 0.59)	0.99	43335.9	10410.00
32	518.65	259.31	0.211	0.60( 0.59)	0.99	44437.9	12101.10
33	507.14	268.79	0.208	0.60( 0.59)	0.99	45259.3	10700.00
34	495.86	286.29	0.203	0.60( 0.60)	0.99	46816.0	10200.00
35	484.18	299.42	0.199	0.60( 0.60)	0.99	47754.2	12010.00
36	478.61	304.60	0.197	0.60( 0.60)	0.99	47975.9	10320.00
37	472.99	309.30	0.196	0.60( 0.60)	0.99	48124.4	10300.00
38	449.35	327.68	0.190	0.60( 0.60)	0.99	48427.9	10210.00
39	444.11	344.11	0.170	0.60( 0.60)	0.99	49511.8	10100.00

TOTAL AREA (ACRES) = 49511.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:  
 PEAK FLOW RATE(CFS) = 841.94 Tc(MIN.) = 138.997  
 EFFECTIVE AREA(ACRES) = 24109.93 AREA-AVERAGED Fm(INCH/HR) = 0.60  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 49511.8  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 49511.8 TC(MIN.) = 139.00  
 EFFECTIVE AREA(ACRES) = 24109.93 AREA-AVERAGED Fm(INCH/HR) = 0.60  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.995  
 PEAK FLOW RATE(CFS) = 841.94

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	417.64	23.84	0.695	0.60( 0.60)	0.99	3250.6	40200.00
2	455.91	52.05	0.444	0.60( 0.60)	0.99	7208.8	40120.00
3	464.88	55.67	0.424	0.60( 0.60)	0.99	7720.0	40100.00
4	512.68	69.05	0.384	0.60( 0.60)	0.99	9451.4	11831.00
5	624.07	94.27	0.338	0.60( 0.60)	0.99	13147.6	11530.00
6	699.08	110.11	0.308	0.60( 0.60)	0.99	16273.8	11701.00
7	720.83	115.16	0.299	0.60( 0.60)	0.99	17303.5	11000.00
8	818.18	132.60	0.279	0.60( 0.60)	0.99	22259.0	11350.00
9	841.94	139.00	0.273	0.60( 0.60)	0.99	24109.9	10850.00
10	827.65	142.43	0.270	0.60( 0.60)	0.99	24879.9	12500.00
11	817.91	145.32	0.267	0.60( 0.60)	0.99	25606.1	11900.00
12	812.63	146.88	0.266	0.60( 0.60)	0.99	25981.8	10800.00
13	771.94	153.70	0.260	0.60( 0.60)	0.99	27429.8	11220.00
14	770.10	154.05	0.259	0.60( 0.60)	0.99	27491.7	11910.00
15	717.22	164.33	0.250	0.60( 0.60)	0.99	29181.8	10910.00
16	685.95	170.56	0.244	0.60( 0.60)	0.99	30055.0	12300.00
17	673.86	172.47	0.243	0.60( 0.60)	0.99	30348.2	10630.00
18	662.80	175.67	0.240	0.60( 0.60)	0.99	30945.9	12330.00
19	571.28	202.46	0.229	0.60( 0.60)	0.99	35763.4	12410.00
20	543.81	210.48	0.227	0.60( 0.60)	0.99	37195.7	10600.00
21	535.21	215.85	0.225	0.60( 0.60)	0.99	38336.6	12400.00
22	529.21	219.42	0.224	0.60( 0.60)	0.99	39042.1	12211.00
23	529.19	221.71	0.223	0.60( 0.60)	0.99	39564.3	11600.00
24	534.52	227.48	0.221	0.60( 0.59)	0.99	40638.8	12201.00
25	538.79	234.78	0.219	0.60( 0.59)	0.99	41849.3	12261.00
26	537.75	236.37	0.218	0.60( 0.59)	0.99	42067.6	12111.00
27	535.73	239.54	0.217	0.60( 0.59)	0.99	42534.3	10710.00
28	534.46	240.98	0.217	0.60( 0.59)	0.99	42690.9	12231.00
29	535.73	239.54	0.217	0.60( 0.59)	0.99	42534.3	10710.00
30	534.46	240.98	0.217	0.60( 0.59)	0.99	42690.9	12231.00
31	528.73	247.35	0.215	0.60( 0.59)	0.99	43335.9	10410.00
32	518.65	259.31	0.211	0.60( 0.59)	0.99	44437.9	12101.10
33	507.14	268.79	0.208	0.60( 0.59)	0.99	45259.3	10700.00
34	495.86	286.29	0.203	0.60( 0.60)	0.99	46816.0	10200.00
35	484.18	299.42	0.199	0.60( 0.60)	0.99	47754.2	12010.00
36	478.61	304.60	0.197	0.60( 0.60)	0.99	47975.9	10320.00
37	472.99	309.30	0.196	0.60( 0.60)	0.99	48124.4	10300.00
38	449.35	327.68	0.190	0.60( 0.60)	0.99	48427.9	10210.00
39	444.11	344.11	0.170	0.60( 0.60)	0.99	49511.8	10100.00

END OF RATIONAL METHOD ANALYSIS



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA 92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S26- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 2-YR RM EV APRIL 2019 ROKAMOTO \*  
\*\*\*\*\*

FILE NAME: RI02EV26.DAT  
TIME/DATE OF STUDY: 17:07 04/08/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 2.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 1.873
- 2) 10.00; 1.249
- 3) 15.00; 0.951
- 4) 20.00; 0.777
- 5) 25.00; 0.669
- 6) 30.00; 0.593
- 7) 40.00; 0.511
- 8) 50.00; 0.454
- 9) 60.00; 0.400
- 10) 90.00; 0.346
- 11) 120.00; 0.290
- 12) 180.00; 0.236
- 13) 360.00; 0.180
- 14) 1200.00; 0.084

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI02EV19.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	417.64	23.84	0.60 ( 0.60)	0.99	3250.6	40200.00
2	464.88	55.67	0.60 ( 0.60)	0.99	7720.0	40100.00
3	512.68	69.05	0.60 ( 0.60)	0.99	9451.4	11831.00
4	624.07	94.27	0.60 ( 0.60)	0.99	13147.6	11530.00
5	720.83	115.16	0.60 ( 0.60)	0.99	17303.5	11000.00
6	841.94	139.00	0.60 ( 0.60)	0.99	24109.9	10850.00
7	771.94	153.70	0.60 ( 0.60)	0.99	27429.8	11220.00
8	717.22	164.33	0.60 ( 0.60)	0.99	29181.8	10910.00
9	571.28	202.46	0.60 ( 0.60)	0.99	35763.4	12410.00
10	543.81	210.48	0.60 ( 0.60)	0.99	37195.7	10600.00
11	534.52	227.48	0.60 ( 0.59)	0.99	40638.8	12201.00
12	538.79	234.78	0.60 ( 0.59)	0.99	41849.3	12261.00
13	528.73	247.35	0.60 ( 0.59)	0.99	43335.9	10410.00
14	518.65	259.31	0.60 ( 0.59)	0.99	44437.9	12101.10
15	507.14	268.79	0.60 ( 0.59)	0.99	45259.3	10700.00
16	495.86	286.29	0.60 ( 0.60)	0.99	46816.0	10200.00
17	484.18	299.42	0.60 ( 0.60)	0.99	47754.2	12010.00
18	449.35	327.68	0.60 ( 0.60)	0.99	48427.9	10210.00
19	396.20	375.51	0.60 ( 0.60)	0.99	48927.0	12000.00
20	364.10	444.11	0.60 ( 0.60)	0.99	49511.8	10100.00
TOTAL AREA(ACRES) =						49511.8

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	417.64	23.84	0.60 ( 0.60)	0.99	3250.6	40200.00
2	464.88	55.67	0.60 ( 0.60)	0.99	7720.0	40100.00
3	512.68	69.05	0.60 ( 0.60)	0.99	9451.4	11831.00
4	624.07	94.27	0.60 ( 0.60)	0.99	13147.6	11530.00
5	720.83	115.16	0.60 ( 0.60)	0.99	17303.5	11000.00
6	841.94	139.00	0.60 ( 0.60)	0.99	24109.9	10850.00
7	771.94	153.70	0.60 ( 0.60)	0.99	27429.8	11220.00
8	717.22	164.33	0.60 ( 0.60)	0.99	29181.8	10910.00
9	571.28	202.46	0.60 ( 0.60)	0.99	35763.4	12410.00
10	543.81	210.48	0.60 ( 0.60)	0.99	37195.7	10600.00
11	534.52	227.48	0.60 ( 0.59)	0.99	40638.8	12201.00
12	538.79	234.78	0.60 ( 0.59)	0.99	41849.3	12261.00
13	528.73	247.35	0.60 ( 0.59)	0.99	43335.9	10410.00

14 518.65 259.31 0.60( 0.59) 0.99 44437.9 12101.10  
 15 507.14 268.79 0.60( 0.59) 0.99 45259.3 10700.00  
 16 495.86 286.29 0.60( 0.60) 0.99 46816.0 10200.00  
 17 484.18 299.42 0.60( 0.60) 0.99 47754.2 12010.00  
 18 449.35 327.68 0.60( 0.60) 0.99 48427.9 10210.00  
 19 396.20 375.51 0.60( 0.60) 0.99 48927.0 12000.00  
 20 364.10 444.11 0.60( 0.60) 0.99 49511.8 10100.00  
 TOTAL AREA(ACRES) = 49511.8

\*\*\*\*\*

FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 11929.00 TO NODE 12601.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 341.63 DOWNSTREAM(FEET) = 325.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1467.93 CHANNEL SLOPE = 0.0113  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00

\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.271

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	14.11	0.60	0.700	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.700

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 842.45

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.81

AVERAGE FLOW DEPTH(FEET) = 5.35 TRAVEL TIME(MIN.) = 2.49

Tc(MIN.) = 141.49

SUBAREA AREA(ACRES) = 14.11 SUBAREA RUNOFF(CFS) = 1.03

EFFECTIVE AREA(ACRES) = 24124.04 AREA-AVERAGED Fm(INCH/HR) = 0.60

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 49525.9 PEAK FLOW RATE(CFS) = 841.94

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 5.35 FLOW VELOCITY(FEET/SEC.) = 9.80

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	417.64	26.81	0.641	0.60( 0.59)	0.99	3264.7	40200.00
2	464.88	58.56	0.408	0.60( 0.60)	0.99	7734.1	40100.00
3	512.68	71.87	0.379	0.60( 0.60)	0.99	9465.5	11831.00
4	624.07	96.96	0.333	0.60( 0.60)	0.99	13161.7	11530.00
5	720.83	117.75	0.294	0.60( 0.60)	0.99	17317.6	11000.00

6	841.94	141.49	0.271	0.60( 0.60)	0.99	24124.0	10850.00
7	771.94	156.24	0.257	0.60( 0.60)	0.99	27443.9	11220.00
8	717.22	166.92	0.248	0.60( 0.60)	0.99	29195.9	10910.00
9	571.28	205.21	0.228	0.60( 0.60)	0.99	35777.5	12410.00
10	543.81	213.27	0.226	0.60( 0.60)	0.99	37209.8	10600.00
11	534.52	230.28	0.220	0.60( 0.59)	0.99	40652.9	12201.00
12	538.79	237.57	0.218	0.60( 0.59)	0.99	41863.4	12261.00
13	528.73	250.15	0.214	0.60( 0.59)	0.99	43350.0	10410.00
14	518.65	262.13	0.210	0.60( 0.59)	0.99	44452.0	12101.10
15	507.14	271.62	0.207	0.60( 0.59)	0.99	45273.4	10700.00
16	495.86	289.14	0.202	0.60( 0.60)	0.99	46830.1	10200.00
17	484.18	302.28	0.198	0.60( 0.60)	0.99	47768.3	12010.00
18	449.35	330.60	0.189	0.60( 0.60)	0.99	48442.0	10210.00
19	396.20	378.52	0.178	0.60( 0.60)	0.99	48941.1	12000.00
20	364.10	447.19	0.170	0.60( 0.60)	0.99	49525.9	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 841.94 Tc(MIN.) = 141.49

AREA-AVERAGED Fm(INCH/HR) = 0.60 AREA-AVERAGED Fp(INCH/HR) = 0.60

AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 24124.04

\*\*\*\*\*

FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 3002EVRL.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	8.00	20.74	0.60( 0.59)	0.99	48.4	600.00
TOTAL AREA(ACRES) =		48.4				

\*\*\*\*\*

FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	417.64	26.81	0.641	0.60( 0.59)	0.99	3264.7	40200.00
2	464.88	58.56	0.408	0.60( 0.60)	0.99	7734.1	40100.00
3	512.68	71.87	0.379	0.60( 0.60)	0.99	9465.5	11831.00
4	624.07	96.96	0.333	0.60( 0.60)	0.99	13161.7	11530.00
5	720.83	117.75	0.294	0.60( 0.60)	0.99	17317.6	11000.00
6	841.94	141.49	0.271	0.60( 0.60)	0.99	24124.0	10850.00
7	771.94	156.24	0.257	0.60( 0.60)	0.99	27443.9	11220.00
8	717.22	166.92	0.248	0.60( 0.60)	0.99	29195.9	10910.00
9	571.28	205.21	0.228	0.60( 0.60)	0.99	35777.5	12410.00
10	543.81	213.27	0.226	0.60( 0.60)	0.99	37209.8	10600.00
11	534.52	230.28	0.220	0.60( 0.59)	0.99	40652.9	12201.00
12	538.79	237.57	0.218	0.60( 0.59)	0.99	41863.4	12261.00
13	528.73	250.15	0.214	0.60( 0.59)	0.99	43350.0	10410.00
14	518.65	262.13	0.210	0.60( 0.59)	0.99	44452.0	12101.10
15	507.14	271.62	0.207	0.60( 0.59)	0.99	45273.4	10700.00
16	495.86	289.14	0.202	0.60( 0.60)	0.99	46830.1	10200.00
17	484.18	302.28	0.198	0.60( 0.60)	0.99	47768.3	12010.00

18 449.35 330.60 0.189 0.60( 0.60) 0.99 48442.0 10210.00  
 19 396.20 378.52 0.178 0.60( 0.60) 0.99 48941.1 12000.00  
 20 364.10 447.19 0.170 0.60( 0.60) 0.99 49525.9 10100.00  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	8.00	20.74	0.761	0.60( 0.59)	0.99	48.4	600.00

LONGEST FLOWPATH FROM NODE 600.00 TO NODE 12601.00 = 4850.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	425.64	20.74	0.761	0.60( 0.59)	0.99	2573.4	600.00
2	419.98	26.81	0.641	0.60( 0.59)	0.99	3313.1	40200.00
3	465.13	58.56	0.408	0.60( 0.60)	0.99	7782.5	40100.00
4	512.92	71.87	0.379	0.60( 0.60)	0.99	9513.9	11831.00
5	624.27	96.96	0.333	0.60( 0.60)	0.99	13210.1	11530.00
6	721.02	117.75	0.294	0.60( 0.60)	0.99	17366.0	11000.00
7	842.10	141.49	0.271	0.60( 0.60)	0.99	24172.4	10850.00
8	772.10	156.24	0.257	0.60( 0.60)	0.99	27492.3	11220.00
9	717.37	166.92	0.248	0.60( 0.60)	0.99	29244.3	10910.00
10	571.43	205.21	0.228	0.60( 0.60)	0.99	35825.9	12410.00
11	543.95	213.27	0.226	0.60( 0.60)	0.99	37258.2	10600.00
12	534.66	230.28	0.220	0.60( 0.59)	0.99	40701.3	12201.00
13	538.93	237.57	0.218	0.60( 0.59)	0.99	41911.8	12261.00
14	528.87	250.15	0.214	0.60( 0.59)	0.99	43398.4	10410.00
15	518.78	262.13	0.210	0.60( 0.59)	0.99	44500.4	12101.10
16	507.27	271.62	0.207	0.60( 0.59)	0.99	45321.8	10700.00
17	495.99	289.14	0.202	0.60( 0.60)	0.99	46878.5	10200.00
18	484.30	302.28	0.198	0.60( 0.60)	0.99	47816.7	12010.00
19	449.47	330.60	0.189	0.60( 0.60)	0.99	48490.4	10210.00
20	396.32	378.52	0.178	0.60( 0.60)	0.99	48989.5	12000.00
21	364.21	447.19	0.170	0.60( 0.60)	0.99	49574.3	10100.00

TOTAL AREA (ACRES) = 49574.3

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 842.10 Tc(MIN.) = 141.492  
 EFFECTIVE AREA(ACRES) = 24172.44 AREA-AVERAGED Fm(INCH/HR) = 0.60  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 49574.3  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 2 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12601.00 TO NODE 12602.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 325.00 DOWNSTREAM(FEET) = 313.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1377.46 CHANNEL SLOPE = 0.0087

CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
 CHANNEL FLOW THRU SUBAREA(CFS) = 842.10  
 FLOW VELOCITY(FEET/SEC.) = 8.89 FLOW DEPTH(FEET) = 5.62  
 TRAVEL TIME(MIN.) = 2.58 Tc(MIN.) = 144.07  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12602.00 = 101245.91 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	425.64	23.80	0.695	0.60( 0.59)	0.99	2573.4	600.00
2	419.98	29.89	0.595	0.60( 0.59)	0.99	3313.1	40200.00
3	465.13	61.56	0.397	0.60( 0.60)	0.99	7782.5	40100.00
4	512.92	74.79	0.373	0.60( 0.60)	0.99	9513.9	11831.00
5	624.27	99.74	0.328	0.60( 0.60)	0.99	13210.1	11530.00
6	721.02	120.43	0.290	0.60( 0.60)	0.99	17366.0	11000.00
7	842.10	144.07	0.268	0.60( 0.60)	0.99	24172.4	10850.00
8	772.10	158.88	0.255	0.60( 0.60)	0.99	27492.3	11220.00
9	717.37	169.61	0.245	0.60( 0.60)	0.99	29244.3	10910.00
10	571.43	208.05	0.227	0.60( 0.60)	0.99	35825.9	12410.00
11	543.95	216.15	0.225	0.60( 0.60)	0.99	37258.2	10600.00
12	534.66	233.17	0.219	0.60( 0.59)	0.99	40701.3	12201.00
13	538.93	240.46	0.217	0.60( 0.59)	0.99	41911.8	12261.00
14	528.87	253.05	0.213	0.60( 0.59)	0.99	43398.4	10410.00
15	518.78	265.04	0.210	0.60( 0.59)	0.99	44500.4	12101.10
16	507.27	274.55	0.207	0.60( 0.59)	0.99	45321.8	10700.00
17	495.99	292.09	0.201	0.60( 0.60)	0.99	46878.5	10200.00
18	484.30	305.25	0.197	0.60( 0.60)	0.99	47816.7	12010.00
19	449.47	333.63	0.188	0.60( 0.60)	0.99	48490.4	10210.00
20	396.32	381.64	0.178	0.60( 0.60)	0.99	48989.5	12000.00
21	364.21	450.37	0.170	0.60( 0.60)	0.99	49574.3	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 842.10 Tc(MIN.) = 144.07  
 AREA-AVERAGED Fm(INCH/HR) = 0.60 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 24172.44

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12602.00 TO NODE 12603.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 313.00 DOWNSTREAM(FEET) = 310.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 312.40 CHANNEL SLOPE = 0.0096  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
 CHANNEL FLOW THRU SUBAREA(CFS) = 842.10  
 FLOW VELOCITY(FEET/SEC.) = 9.22 FLOW DEPTH(FEET) = 5.52  
 TRAVEL TIME(MIN.) = 0.56 Tc(MIN.) = 144.64  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.30 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	425.64	24.47	0.680	0.60( 0.59)	0.99	2573.4	600.00
2	419.98	30.56	0.588	0.60( 0.59)	0.99	3313.1	40200.00
3	465.13	62.21	0.396	0.60( 0.60)	0.99	7782.5	40100.00
4	512.92	75.43	0.372	0.60( 0.60)	0.99	9513.9	11831.00



5	624.27	100.35	0.327	0.60	( 0.60)	0.99	13210.1	11530.00
6	721.02	121.02	0.289	0.60	( 0.60)	0.99	17366.0	11000.00
7	842.10	144.64	0.268	0.60	( 0.60)	0.99	24172.4	10850.00
8	772.10	159.46	0.254	0.60	( 0.60)	0.99	27492.3	11220.00
9	717.37	170.20	0.245	0.60	( 0.60)	0.99	29244.3	10910.00
10	571.43	208.68	0.227	0.60	( 0.60)	0.99	35825.9	12410.00
11	543.95	216.78	0.225	0.60	( 0.60)	0.99	37258.2	10600.00
12	534.66	233.80	0.219	0.60	( 0.59)	0.99	40701.3	12201.00
13	538.93	241.10	0.217	0.60	( 0.59)	0.99	41911.8	12261.00
14	528.87	253.69	0.213	0.60	( 0.59)	0.99	43398.4	10410.00
15	518.78	265.68	0.209	0.60	( 0.59)	0.99	44500.4	12101.10
16	507.27	275.19	0.206	0.60	( 0.59)	0.99	45321.8	10700.00
17	495.99	292.73	0.201	0.60	( 0.60)	0.99	46878.5	10200.00
18	484.30	305.90	0.197	0.60	( 0.60)	0.99	47816.7	12010.00
19	449.47	334.29	0.188	0.60	( 0.60)	0.99	48490.4	10210.00
20	396.32	382.32	0.177	0.60	( 0.60)	0.99	48989.5	12000.00
21	364.21	451.07	0.170	0.60	( 0.60)	0.99	49574.3	10100.00

NEW PEAK FLOW DATA ARE:  
PEAK FLOW RATE(CFS) = 842.10 Tc(MIN.) = 144.64  
AREA-AVERAGED Fm(INCH/HR) = 0.60 AREA-AVERAGED Fp(INCH/HR) = 0.60  
AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 24172.44

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 0610403T.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12.58	25.67	0.680	0.60 ( 0.58)	0.97	175.0	40300.00

TOTAL AREA(ACRES) = 175.0

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	425.64	24.47	0.680	0.60 ( 0.59)	0.99	2573.4	600.00
2	419.98	30.56	0.588	0.60 ( 0.59)	0.99	3313.1	40200.00
3	465.13	62.21	0.396	0.60 ( 0.60)	0.99	7782.5	40100.00
4	512.92	75.43	0.372	0.60 ( 0.60)	0.99	9513.9	11831.00
5	624.27	100.35	0.327	0.60 ( 0.60)	0.99	13210.1	11530.00
6	721.02	121.02	0.289	0.60 ( 0.60)	0.99	17366.0	11000.00
7	842.10	144.64	0.268	0.60 ( 0.60)	0.99	24172.4	10850.00
8	772.10	159.46	0.254	0.60 ( 0.60)	0.99	27492.3	11220.00
9	717.37	170.20	0.245	0.60 ( 0.60)	0.99	29244.3	10910.00
10	571.43	208.68	0.227	0.60 ( 0.60)	0.99	35825.9	12410.00
11	543.95	216.78	0.225	0.60 ( 0.60)	0.99	37258.2	10600.00
12	534.66	233.80	0.219	0.60 ( 0.59)	0.99	40701.3	12201.00
13	538.93	241.10	0.217	0.60 ( 0.59)	0.99	41911.8	12261.00
14	528.87	253.69	0.213	0.60 ( 0.59)	0.99	43398.4	10410.00
15	518.78	265.68	0.209	0.60 ( 0.59)	0.99	44500.4	12101.10

16	507.27	275.19	0.206	0.60	( 0.59)	0.99	45321.8	10700.00
17	495.99	292.73	0.201	0.60	( 0.60)	0.99	46878.5	10200.00
18	484.30	305.90	0.197	0.60	( 0.60)	0.99	47816.7	12010.00
19	449.47	334.29	0.188	0.60	( 0.60)	0.99	48490.4	10210.00
20	396.32	382.32	0.177	0.60	( 0.60)	0.99	48989.5	12000.00
21	364.21	451.07	0.170	0.60	( 0.60)	0.99	49574.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.30 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12.58	25.67	0.659	0.60 ( 0.58)	0.97	175.0	40300.00

LONGEST FLOWPATH FROM NODE 40300.00 TO NODE 12603.00 = 5256.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	438.22	24.47	0.680	0.60 ( 0.59)	0.99	2740.3	600.00
2	437.10	25.67	0.659	0.60 ( 0.59)	0.99	2894.4	40300.00
3	423.21	30.56	0.588	0.60 ( 0.59)	0.99	3488.2	40200.00
4	467.30	62.21	0.396	0.60 ( 0.60)	0.99	7957.5	40100.00
5	514.96	75.43	0.372	0.60 ( 0.60)	0.99	9689.0	11831.00
6	626.07	100.35	0.327	0.60 ( 0.60)	0.99	13385.2	11530.00
7	722.60	121.02	0.289	0.60 ( 0.60)	0.99	17541.1	11000.00
8	843.57	144.64	0.268	0.60 ( 0.60)	0.99	24347.5	10850.00
9	773.49	159.46	0.254	0.60 ( 0.60)	0.99	27667.3	11220.00
10	718.71	170.20	0.245	0.60 ( 0.60)	0.99	29419.4	10910.00
11	572.67	208.68	0.227	0.60 ( 0.60)	0.99	36001.0	12410.00
12	545.18	216.78	0.225	0.60 ( 0.60)	0.99	37433.2	10600.00
13	535.86	233.80	0.219	0.60 ( 0.59)	0.99	40876.3	12201.00
14	540.12	241.10	0.217	0.60 ( 0.59)	0.99	42086.9	12261.00
15	530.04	253.69	0.213	0.60 ( 0.59)	0.99	43573.5	10410.00
16	519.93	265.68	0.209	0.60 ( 0.59)	0.99	44675.4	12101.10
17	508.40	275.19	0.206	0.60 ( 0.59)	0.99	45496.8	10700.00
18	497.09	292.73	0.201	0.60 ( 0.59)	0.99	47053.5	10200.00
19	485.38	305.90	0.197	0.60 ( 0.60)	0.99	47991.8	12010.00
20	450.50	334.29	0.188	0.60 ( 0.60)	0.99	48665.5	10210.00
21	397.29	382.32	0.177	0.60 ( 0.60)	0.99	49164.6	12000.00
22	365.14	451.07	0.170	0.60 ( 0.60)	0.99	49749.3	10100.00

TOTAL AREA(ACRES) = 49749.3

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 843.57 Tc(MIN.) = 144.640  
EFFECTIVE AREA(ACRES) = 24347.49 AREA-AVERAGED Fm(INCH/HR) = 0.60  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99  
TOTAL AREA(ACRES) = 49749.3  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.30 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

```

=====
MAINLINE Tc(MIN.) = 144.64
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.268
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp        Ap        SCS
LAND USE                GROUP  (ACRES)  (INCH/HR) (DECIMAL) CN
USER-DEFINED           -         1.20      0.60      1.000    -
USER-DEFINED           -         8.80      0.60      1.000    -
USER-DEFINED           -         0.10      0.60      1.000    -
USER-DEFINED           -         0.60      0.60      1.000    -
USER-DEFINED           -         0.60      0.60      1.000    -
USER-DEFINED           -         2.90      0.60      1.000    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 14.20      SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 24361.69  AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60  AREA-AVERAGED Ap = 0.99
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 49763.5      PEAK FLOW RATE(CFS) = 843.57
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
-----

```

```

=====
MAINLINE Tc(MIN.) = 144.64
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.268
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp        Ap        SCS
LAND USE                GROUP  (ACRES)  (INCH/HR) (DECIMAL) CN
USER-DEFINED           -         0.30      0.60      1.000    -
USER-DEFINED           -         1.90      0.60      1.000    -
USER-DEFINED           -         0.10      0.60      1.000    -
USER-DEFINED           -         0.70      0.60      1.000    -
USER-DEFINED           -         1.10      0.60      1.000    -
USER-DEFINED           -         0.70      0.60      0.850    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.978
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 4.80      SUBAREA RUNOFF(CFS) = 0.03
EFFECTIVE AREA(ACRES) = 24366.49  AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60  AREA-AVERAGED Ap = 0.99
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 49768.3      PEAK FLOW RATE(CFS) = 843.57
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
-----

```

```

=====
MAINLINE Tc(MIN.) = 144.64

```

```

* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.268
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp        Ap        SCS
LAND USE                GROUP  (ACRES)  (INCH/HR) (DECIMAL) CN
USER-DEFINED           -         0.20      0.60      0.850    -
USER-DEFINED           -         0.10      0.60      0.200    -
USER-DEFINED           -         1.40      0.60      0.900    -
USER-DEFINED           -         1.00      0.60      0.900    -
USER-DEFINED           -         0.30      0.60      1.000    -
USER-DEFINED           -         5.70      0.60      1.000    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.960
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 8.70      SUBAREA RUNOFF(CFS) = 0.08
EFFECTIVE AREA(ACRES) = 24375.19  AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60  AREA-AVERAGED Ap = 0.99
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 49777.0      PEAK FLOW RATE(CFS) = 843.57
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 12603.00 TO NODE 12604.00 IS CODE = 51
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

```

```

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
-----

```

```

ELEVATION DATA: UPSTREAM(FEET) = 310.00  DOWNSTREAM(FEET) = 307.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 459.69  CHANNEL SLOPE = 0.0065
CHANNEL BASE(FEET) = 0.00  "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030  MAXIMUM DEPTH(FEET) = 20.00
CHANNEL FLOW THRU SUBAREA(CFS) = 843.57
FLOW VELOCITY(FEET/SEC.) = 7.97  FLOW DEPTH(FEET) = 5.94
TRAVEL TIME(MIN.) = 0.96  Tc(MIN.) = 145.60
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12604.00 = 102017.99 FEET.

```

```

** PEAK FLOW RATE TABLE **

```

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	438.22	25.60	0.660	0.60( 0.59)	0.99	2768.0	600.00
2	437.10	26.80	0.642	0.60( 0.59)	0.99	2922.1	40300.00
3	423.21	31.70	0.579	0.60( 0.59)	0.99	3515.9	40200.00
4	467.30	63.33	0.394	0.60( 0.60)	0.99	7985.2	40100.00
5	514.96	76.52	0.370	0.60( 0.60)	0.99	9716.7	11831.00
6	626.07	101.38	0.325	0.60( 0.60)	0.99	13412.9	11530.00
7	722.60	122.02	0.288	0.60( 0.60)	0.99	17568.8	11000.00
8	843.57	145.60	0.267	0.60( 0.60)	0.99	24375.2	10850.00
9	773.49	160.44	0.254	0.60( 0.60)	0.99	27695.0	11220.00
10	718.71	171.20	0.244	0.60( 0.60)	0.99	29447.1	10910.00
11	572.67	209.73	0.227	0.60( 0.60)	0.99	36028.7	12410.00
12	545.18	217.85	0.224	0.60( 0.60)	0.99	37460.9	10600.00
13	535.86	234.88	0.219	0.60( 0.59)	0.99	40904.0	12201.00
14	540.12	242.17	0.217	0.60( 0.59)	0.99	42114.6	12261.00
15	530.04	254.76	0.213	0.60( 0.59)	0.99	43601.2	10410.00
16	519.93	266.76	0.209	0.60( 0.59)	0.99	44703.1	12101.10
17	508.40	276.28	0.206	0.60( 0.59)	0.99	45524.5	10700.00
18	497.09	293.83	0.201	0.60( 0.59)	0.99	47081.2	10200.00

19 485.38 307.00 0.196 0.60( 0.60) 0.99 48019.5 12010.00  
 20 450.50 335.41 0.188 0.60( 0.60) 0.99 48693.2 10210.00  
 21 397.29 383.48 0.177 0.60( 0.60) 0.99 49192.3 12000.00  
 22 365.14 452.25 0.169 0.60( 0.60) 0.99 49777.0 10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 843.57 Tc(MIN.) = 145.60  
 AREA-AVERAGED Fm(INCH/HR) = 0.60 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 24375.19

\*\*\*\*\*

FLOW PROCESS FROM NODE 12604.00 TO NODE 12604.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 145.60

\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.267

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.10	0.60	1.000	-
USER-DEFINED	-	0.90	0.60	1.000	-
USER-DEFINED	-	0.10	0.60	0.850	-
USER-DEFINED	-	0.70	0.60	1.000	-
USER-DEFINED	-	0.50	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.993

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 2.30 SUBAREA RUNOFF(CFS) = 0.00

EFFECTIVE AREA(ACRES) = 24377.49 AREA-AVERAGED Fm(INCH/HR) = 0.60

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 49779.3 PEAK FLOW RATE(CFS) = 843.57

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12604.00 TO NODE 12605.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 307.00 DOWNSTREAM(FEET) = 305.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 427.54 CHANNEL SLOPE = 0.0047

CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00

CHANNEL FLOW THRU SUBAREA(CFS) = 843.57

FLOW VELOCITY(FEET/SEC.) = 7.04 FLOW DEPTH(FEET) = 6.32

TRAVEL TIME(MIN.) = 1.01 Tc(MIN.) = 146.61

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.00 = 102445.53 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	438.22	26.79	0.642	0.60( 0.59)	0.99	2770.3	600.00
2	437.10	28.00	0.623	0.60( 0.59)	0.99	2924.4	40300.00
3	423.21	32.90	0.569	0.60( 0.59)	0.99	3518.2	40200.00
4	467.30	64.50	0.392	0.60( 0.60)	0.99	7987.5	40100.00

5 514.96 77.66 0.368 0.60( 0.60) 0.99 9719.0 11831.00  
 6 626.07 102.47 0.323 0.60( 0.60) 0.99 13415.2 11530.00  
 7 722.60 123.07 0.287 0.60( 0.60) 0.99 17571.1 11000.00  
 8 843.57 146.61 0.266 0.60( 0.60) 0.99 24377.5 10850.00  
 9 773.49 161.47 0.253 0.60( 0.60) 0.99 27697.3 11220.00  
 10 718.71 172.25 0.243 0.60( 0.60) 0.99 29449.4 10910.00  
 11 572.67 210.85 0.226 0.60( 0.60) 0.99 36031.0 12410.00  
 12 545.18 218.98 0.224 0.60( 0.60) 0.99 37463.2 10600.00  
 13 535.86 236.01 0.219 0.60( 0.59) 0.99 40906.3 12201.00  
 14 540.12 243.30 0.216 0.60( 0.59) 0.99 42116.9 12261.00  
 15 530.04 255.90 0.212 0.60( 0.59) 0.99 43603.5 10410.00  
 16 519.93 267.90 0.209 0.60( 0.59) 0.99 44705.4 12101.10  
 17 508.40 277.43 0.206 0.60( 0.59) 0.99 45526.8 10700.00  
 18 497.09 294.99 0.200 0.60( 0.59) 0.99 47083.5 10200.00  
 19 485.38 308.16 0.196 0.60( 0.60) 0.99 48021.8 12010.00  
 20 450.50 336.60 0.187 0.60( 0.60) 0.99 48695.5 10210.00  
 21 397.29 384.70 0.177 0.60( 0.60) 0.99 49194.6 12000.00  
 22 365.14 453.50 0.169 0.60( 0.60) 0.99 49779.3 10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 843.57 Tc(MIN.) = 146.61  
 AREA-AVERAGED Fm(INCH/HR) = 0.60 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 24377.49

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.00 TO NODE 12605.30 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 305.00 DOWNSTREAM(FEET) = 302.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 217.28 CHANNEL SLOPE = 0.0138

CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00

CHANNEL FLOW THRU SUBAREA(CFS) = 843.57

FLOW VELOCITY(FEET/SEC.) = 10.56 FLOW DEPTH(FEET) = 5.16

TRAVEL TIME(MIN.) = 0.34 Tc(MIN.) = 146.96

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.30 = 102662.81 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	438.22	27.20	0.636	0.60( 0.59)	0.99	2770.3	600.00
2	437.10	28.40	0.617	0.60( 0.59)	0.99	2924.4	40300.00
3	423.21	33.31	0.566	0.60( 0.59)	0.99	3518.2	40200.00
4	467.30	64.90	0.391	0.60( 0.60)	0.99	7987.5	40100.00
5	514.96	78.05	0.368	0.60( 0.60)	0.99	9719.0	11831.00
6	626.07	102.84	0.322	0.60( 0.60)	0.99	13415.2	11530.00
7	722.60	123.43	0.287	0.60( 0.60)	0.99	17571.1	11000.00
8	843.57	146.96	0.266	0.60( 0.60)	0.99	24377.5	10850.00
9	773.49	161.82	0.252	0.60( 0.60)	0.99	27697.3	11220.00
10	718.71	172.61	0.243	0.60( 0.60)	0.99	29449.4	10910.00
11	572.67	211.22	0.226	0.60( 0.60)	0.99	36031.0	12410.00
12	545.18	219.36	0.224	0.60( 0.60)	0.99	37463.2	10600.00
13	535.86	236.40	0.218	0.60( 0.59)	0.99	40906.3	12201.00
14	540.12	243.68	0.216	0.60( 0.59)	0.99	42116.9	12261.00
15	530.04	256.28	0.212	0.60( 0.59)	0.99	43603.5	10410.00
16	519.93	268.29	0.209	0.60( 0.59)	0.99	44705.4	12101.10
17	508.40	277.82	0.206	0.60( 0.59)	0.99	45526.8	10700.00

18	497.09	295.38	0.200	0.60	( 0.59)	0.99	47083.5	10200.00
19	485.38	308.55	0.196	0.60	( 0.60)	0.99	48021.8	12010.00
20	450.50	337.00	0.187	0.60	( 0.60)	0.99	48695.5	10210.00
21	397.29	385.12	0.177	0.60	( 0.60)	0.99	49194.6	12000.00
22	365.14	453.92	0.169	0.60	( 0.60)	0.99	49779.3	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 843.57 Tc(MIN.) = 146.96  
 AREA-AVERAGED Fm(INCH/HR) = 0.60 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 24377.49

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12605.30 TO NODE 12605.30 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610404T.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	62.15	24.51	0.60 ( 0.59)	0.99	393.3	40430.00
2	59.42	25.09	0.60 ( 0.59)	0.99	396.7	40440.00
3	46.67	27.60	0.60 ( 0.59)	0.99	409.2	40420.00
4	45.68	27.81	0.60 ( 0.59)	0.99	409.9	40400.00
5	44.28	28.05	0.60 ( 0.59)	0.99	410.5	40410.00

TOTAL AREA(ACRES) = 410.5

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12605.30 TO NODE 12605.30 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	438.22	27.20	0.636	0.60 ( 0.59)	0.99	2770.3	600.00
2	437.10	28.40	0.617	0.60 ( 0.59)	0.99	2924.4	40300.00
3	423.21	33.31	0.566	0.60 ( 0.59)	0.99	3518.2	40200.00
4	467.30	64.90	0.391	0.60 ( 0.60)	0.99	7987.5	40100.00
5	514.96	78.05	0.368	0.60 ( 0.60)	0.99	9719.0	11831.00
6	626.07	102.84	0.322	0.60 ( 0.60)	0.99	13415.2	11530.00
7	722.60	123.43	0.287	0.60 ( 0.60)	0.99	17571.1	11000.00
8	843.57	146.96	0.266	0.60 ( 0.60)	0.99	24377.5	10850.00
9	773.49	161.82	0.252	0.60 ( 0.60)	0.99	27697.3	11220.00
10	718.71	172.61	0.243	0.60 ( 0.60)	0.99	29449.4	10910.00
11	572.67	211.22	0.226	0.60 ( 0.60)	0.99	36031.0	12410.00
12	545.18	219.36	0.224	0.60 ( 0.60)	0.99	37463.2	10600.00
13	535.86	236.40	0.218	0.60 ( 0.59)	0.99	40906.3	12201.00
14	540.12	243.68	0.216	0.60 ( 0.59)	0.99	42116.9	12261.00
15	530.04	256.28	0.212	0.60 ( 0.59)	0.99	43603.5	10410.00
16	519.93	268.29	0.209	0.60 ( 0.59)	0.99	44705.4	12101.10
17	508.40	277.82	0.206	0.60 ( 0.59)	0.99	45526.8	10700.00
18	497.09	295.38	0.200	0.60 ( 0.59)	0.99	47083.5	10200.00
19	485.38	308.55	0.196	0.60 ( 0.60)	0.99	48021.8	12010.00
20	450.50	337.00	0.187	0.60 ( 0.60)	0.99	48695.5	10210.00
21	397.29	385.12	0.177	0.60 ( 0.60)	0.99	49194.6	12000.00
22	365.14	453.92	0.169	0.60 ( 0.60)	0.99	49779.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.30 = 102662.81 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	62.15	24.51	0.680	0.60 ( 0.59)	0.99	393.3	40430.00
2	59.42	25.09	0.668	0.60 ( 0.59)	0.99	396.7	40440.00
3	46.67	27.60	0.629	0.60 ( 0.59)	0.99	409.2	40420.00
4	45.68	27.81	0.626	0.60 ( 0.59)	0.99	409.9	40400.00
5	44.28	28.05	0.623	0.60 ( 0.59)	0.99	410.5	40410.00

LONGEST FLOWPATH FROM NODE 40400.00 TO NODE 12605.30 = 7428.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	500.37	24.51	0.680	0.60 ( 0.59)	0.99	2890.0	40430.00
2	497.64	25.09	0.668	0.60 ( 0.59)	0.99	2952.1	40440.00
3	486.96	27.20	0.636	0.60 ( 0.59)	0.99	3177.5	600.00
4	484.51	27.60	0.629	0.60 ( 0.59)	0.99	3231.7	40420.00
5	483.33	27.81	0.626	0.60 ( 0.59)	0.99	3258.5	40400.00
6	481.70	28.05	0.623	0.60 ( 0.59)	0.99	3290.6	40410.00
7	473.05	28.40	0.617	0.60 ( 0.59)	0.99	3334.9	40300.00
8	431.09	33.31	0.566	0.60 ( 0.59)	0.99	3928.7	40200.00
9	472.75	64.90	0.391	0.60 ( 0.60)	0.99	8398.0	40100.00
10	520.07	78.05	0.368	0.60 ( 0.60)	0.99	10129.5	11831.00
11	630.55	102.84	0.322	0.60 ( 0.60)	0.99	13825.6	11530.00
12	726.59	123.43	0.287	0.60 ( 0.60)	0.99	17981.6	11000.00
13	847.27	146.96	0.266	0.60 ( 0.60)	0.99	24787.9	10850.00
14	777.01	161.82	0.252	0.60 ( 0.60)	0.99	28107.8	11220.00
15	722.09	172.61	0.243	0.60 ( 0.60)	0.99	29859.8	10910.00
16	575.82	211.22	0.226	0.60 ( 0.60)	0.99	36441.5	12410.00
17	548.30	219.36	0.224	0.60 ( 0.60)	0.99	37873.7	10600.00
18	538.90	236.40	0.218	0.60 ( 0.59)	0.99	41316.8	12201.00
19	543.12	243.68	0.216	0.60 ( 0.59)	0.99	42527.4	12261.00
20	532.99	256.28	0.212	0.60 ( 0.59)	0.99	44014.0	10410.00
21	522.83	268.29	0.209	0.60 ( 0.59)	0.99	45115.9	12101.10
22	511.26	277.82	0.206	0.60 ( 0.59)	0.99	45937.3	10700.00
23	499.87	295.38	0.200	0.60 ( 0.59)	0.99	47494.0	10200.00
24	488.11	308.55	0.196	0.60 ( 0.60)	0.99	48432.2	12010.00
25	453.10	337.00	0.187	0.60 ( 0.60)	0.99	49105.9	10210.00
26	399.75	385.12	0.177	0.60 ( 0.60)	0.99	49605.0	12000.00
27	367.49	453.92	0.169	0.60 ( 0.60)	0.99	50189.8	10100.00

TOTAL AREA(ACRES) = 50189.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 847.27 Tc(MIN.) = 146.956  
 EFFECTIVE AREA(ACRES) = 24787.95 AREA-AVERAGED Fm(INCH/HR) = 0.60  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 50189.8  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.30 = 102662.81 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12605.30 TO NODE 12605.30 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12605.30 TO NODE 12605.60 IS CODE = 51

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<  
 -----

ELEVATION DATA: UPSTREAM(FEET) = 302.00 DOWNSTREAM(FEET) = 295.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 738.76 CHANNEL SLOPE = 0.0095  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
 CHANNEL FLOW THRU SUBAREA(CFS) = 847.27  
 FLOW VELOCITY(FEET/SEC.) = 9.19 FLOW DEPTH(FEET) = 5.54  
 TRAVEL TIME(MIN.) = 1.34 Tc(MIN.) = 148.30  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.60 = 103401.57 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	500.37	26.04	0.653	0.60( 0.59)	0.99	2890.0	40430.00
2	497.64	26.62	0.644	0.60( 0.59)	0.99	2952.1	40440.00
3	486.96	28.73	0.612	0.60( 0.59)	0.99	3177.5	600.00
4	484.51	29.15	0.606	0.60( 0.59)	0.99	3231.7	40420.00
5	483.33	29.35	0.603	0.60( 0.59)	0.99	3258.5	40400.00
6	481.70	29.60	0.599	0.60( 0.59)	0.99	3290.6	40410.00
7	473.05	29.95	0.594	0.60( 0.59)	0.99	3334.9	40300.00
8	431.09	34.90	0.553	0.60( 0.59)	0.99	3928.7	40200.00
9	472.75	66.44	0.388	0.60( 0.60)	0.99	8398.0	40100.00
10	520.07	79.57	0.365	0.60( 0.60)	0.99	10129.5	11831.00
11	630.55	104.28	0.319	0.60( 0.60)	0.99	13825.6	11530.00
12	726.59	124.82	0.286	0.60( 0.60)	0.99	17981.6	11000.00
13	847.27	148.30	0.265	0.60( 0.60)	0.99	24787.9	10850.00
14	777.01	163.19	0.251	0.60( 0.60)	0.99	28107.8	11220.00
15	722.09	174.00	0.241	0.60( 0.60)	0.99	29859.8	10910.00
16	575.82	212.70	0.226	0.60( 0.60)	0.99	36441.5	12410.00
17	548.30	220.85	0.223	0.60( 0.60)	0.99	37873.7	10600.00
18	538.90	237.90	0.218	0.60( 0.59)	0.99	41316.8	12201.00
19	543.12	245.18	0.216	0.60( 0.59)	0.99	42527.4	12261.00
20	532.99	257.79	0.212	0.60( 0.59)	0.99	44014.0	10410.00
21	522.83	269.80	0.208	0.60( 0.59)	0.99	45115.9	12101.10
22	511.26	279.34	0.205	0.60( 0.59)	0.99	45937.3	10700.00
23	499.87	296.91	0.200	0.60( 0.59)	0.99	47494.0	10200.00
24	488.11	310.09	0.196	0.60( 0.60)	0.99	48432.2	12010.00
25	453.10	338.56	0.187	0.60( 0.60)	0.99	49105.9	10210.00
26	399.75	386.73	0.177	0.60( 0.60)	0.99	49605.0	12000.00
27	367.49	455.58	0.169	0.60( 0.60)	0.99	50189.8	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 847.27 Tc(MIN.) = 148.30  
 AREA-AVERAGED Fm(INCH/HR) = 0.60 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 24787.95

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.60 TO NODE 12605.60 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<

PEAK FLOWRATE TABLE FILE NAME: 0610405T.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21.10	16.84	0.60( 0.60)	1.00	75.7	40510.00

2 18.91 19.22 0.60( 0.60) 1.00 81.4 40500.00  
 TOTAL AREA(ACRES) = 81.4

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.60 TO NODE 12605.60 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	500.37	26.04	0.653	0.60( 0.59)	0.99	2890.0	40430.00
2	497.64	26.62	0.644	0.60( 0.59)	0.99	2952.1	40440.00
3	486.96	28.73	0.612	0.60( 0.59)	0.99	3177.5	600.00
4	484.51	29.15	0.606	0.60( 0.59)	0.99	3231.7	40420.00
5	483.33	29.35	0.603	0.60( 0.59)	0.99	3258.5	40400.00
6	481.70	29.60	0.599	0.60( 0.59)	0.99	3290.6	40410.00
7	473.05	29.95	0.594	0.60( 0.59)	0.99	3334.9	40300.00
8	431.09	34.90	0.553	0.60( 0.59)	0.99	3928.7	40200.00
9	472.75	66.44	0.388	0.60( 0.60)	0.99	8398.0	40100.00
10	520.07	79.57	0.365	0.60( 0.60)	0.99	10129.5	11831.00
11	630.55	104.28	0.319	0.60( 0.60)	0.99	13825.6	11530.00
12	726.59	124.82	0.286	0.60( 0.60)	0.99	17981.6	11000.00
13	847.27	148.30	0.265	0.60( 0.60)	0.99	24787.9	10850.00
14	777.01	163.19	0.251	0.60( 0.60)	0.99	28107.8	11220.00
15	722.09	174.00	0.241	0.60( 0.60)	0.99	29859.8	10910.00
16	575.82	212.70	0.226	0.60( 0.60)	0.99	36441.5	12410.00
17	548.30	220.85	0.223	0.60( 0.60)	0.99	37873.7	10600.00
18	538.90	237.90	0.218	0.60( 0.59)	0.99	41316.8	12201.00
19	543.12	245.18	0.216	0.60( 0.59)	0.99	42527.4	12261.00
20	532.99	257.79	0.212	0.60( 0.59)	0.99	44014.0	10410.00
21	522.83	269.80	0.208	0.60( 0.59)	0.99	45115.9	12101.10
22	511.26	279.34	0.205	0.60( 0.59)	0.99	45937.3	10700.00
23	499.87	296.91	0.200	0.60( 0.59)	0.99	47494.0	10200.00
24	488.11	310.09	0.196	0.60( 0.60)	0.99	48432.2	12010.00
25	453.10	338.56	0.187	0.60( 0.60)	0.99	49105.9	10210.00
26	399.75	386.73	0.177	0.60( 0.60)	0.99	49605.0	12000.00
27	367.49	455.58	0.169	0.60( 0.60)	0.99	50189.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.60 = 103401.57 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21.10	16.84	0.887	0.60( 0.60)	1.00	75.7	40510.00
2	18.91	19.22	0.804	0.60( 0.60)	1.00	81.4	40500.00

LONGEST FLOWPATH FROM NODE 40500.00 TO NODE 12605.60 = 4091.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	521.47	16.84	0.887	0.60( 0.59)	0.99	1945.2	40510.00
2	519.28	19.22	0.804	0.60( 0.59)	0.99	2214.8	40500.00
3	505.40	26.04	0.653	0.60( 0.59)	0.99	2971.4	40430.00
4	501.86	26.62	0.644	0.60( 0.59)	0.99	3033.4	40440.00
5	488.21	28.73	0.612	0.60( 0.59)	0.99	3258.9	600.00
6	485.19	29.15	0.606	0.60( 0.59)	0.99	3313.1	40420.00
7	483.72	29.35	0.603	0.60( 0.59)	0.99	3339.9	40400.00

8	481.82	29.60	0.599	0.60	( 0.59)	0.99	3372.0	40410.00
9	473.17	29.95	0.594	0.60	( 0.59)	0.99	3416.3	40300.00
10	431.19	34.90	0.553	0.60	( 0.59)	0.99	4010.0	40200.00
11	472.82	66.44	0.388	0.60	( 0.60)	0.99	8479.4	40100.00
12	520.14	79.57	0.365	0.60	( 0.60)	0.99	10210.8	11831.00
13	630.61	104.28	0.319	0.60	( 0.60)	0.99	13907.0	11530.00
14	726.65	124.82	0.286	0.60	( 0.60)	0.99	18062.9	11000.00
15	847.32	148.30	0.265	0.60	( 0.60)	0.99	24869.3	10850.00
16	777.05	163.19	0.251	0.60	( 0.60)	0.99	28189.2	11220.00
17	722.14	174.00	0.241	0.60	( 0.60)	0.99	29941.2	10910.00
18	575.86	212.70	0.226	0.60	( 0.60)	0.99	36522.8	12410.00
19	548.34	220.85	0.223	0.60	( 0.60)	0.99	37955.1	10600.00
20	538.94	237.90	0.218	0.60	( 0.59)	0.99	41398.2	12201.00
21	543.17	245.18	0.216	0.60	( 0.59)	0.99	42608.7	12261.00
22	533.03	257.79	0.212	0.60	( 0.59)	0.99	44095.3	10410.00
23	522.87	269.80	0.208	0.60	( 0.59)	0.99	45197.3	12101.10
24	511.30	279.34	0.205	0.60	( 0.59)	0.99	46018.7	10700.00
25	499.91	296.91	0.200	0.60	( 0.59)	0.99	47575.4	10200.00
26	488.14	310.09	0.196	0.60	( 0.60)	0.99	48513.6	12010.00
27	453.14	338.56	0.187	0.60	( 0.60)	0.99	49187.3	10210.00
28	399.79	386.73	0.177	0.60	( 0.60)	0.99	49686.4	12000.00
29	367.53	455.58	0.169	0.60	( 0.60)	0.99	50271.2	10100.00

TOTAL AREA (ACRES) = 50271.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 847.32 Tc (MIN.) = 148.296  
EFFECTIVE AREA (ACRES) = 24869.33 AREA-AVERAGED Fm (INCH/HR) = 0.60  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 50271.2  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.60 = 103401.57 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12605.60 TO NODE 12605.60 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12605.60 TO NODE 12606.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 295.00 DOWNSTREAM (FEET) = 286.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1203.43 CHANNEL SLOPE = 0.0075  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA (CFS) = 847.32  
FLOW VELOCITY (FEET/SEC.) = 8.41 FLOW DEPTH (FEET) = 5.80  
TRAVEL TIME (MIN.) = 2.39 Tc (MIN.) = 150.68  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104605.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	521.47	19.54	0.793	0.60 ( 0.59)	0.99	1945.2	40510.00
2	519.28	21.92	0.736	0.60 ( 0.59)	0.99	2214.8	40500.00
3	505.40	28.75	0.612	0.60 ( 0.59)	0.99	2971.4	40430.00

4	501.86	29.34	0.603	0.60	( 0.59)	0.99	3033.4	40440.00
5	488.21	31.47	0.581	0.60	( 0.59)	0.99	3258.9	600.00
6	485.19	31.89	0.578	0.60	( 0.59)	0.99	3313.1	40420.00
7	483.72	32.09	0.576	0.60	( 0.59)	0.99	3339.9	40400.00
8	481.82	32.35	0.574	0.60	( 0.59)	0.99	3372.0	40410.00
9	473.17	32.71	0.571	0.60	( 0.59)	0.99	3416.3	40300.00
10	431.19	37.72	0.530	0.60	( 0.59)	0.99	4010.0	40200.00
11	472.82	69.20	0.383	0.60	( 0.60)	0.99	8479.4	40100.00
12	520.14	82.26	0.360	0.60	( 0.60)	0.99	10210.8	11831.00
13	630.61	106.86	0.315	0.60	( 0.60)	0.99	13907.0	11530.00
14	726.65	127.30	0.283	0.60	( 0.60)	0.99	18062.9	11000.00
15	847.32	150.68	0.262	0.60	( 0.60)	0.99	24869.3	10850.00
16	777.05	165.63	0.249	0.60	( 0.60)	0.99	28189.2	11220.00
17	722.14	176.49	0.239	0.60	( 0.60)	0.99	29941.2	10910.00
18	575.86	215.33	0.225	0.60	( 0.60)	0.99	36522.8	12410.00
19	548.34	223.51	0.222	0.60	( 0.60)	0.99	37955.1	10600.00
20	538.94	240.57	0.217	0.60	( 0.59)	0.99	41398.2	12201.00
21	543.17	247.85	0.215	0.60	( 0.59)	0.99	42608.7	12261.00
22	533.03	260.47	0.211	0.60	( 0.59)	0.99	44095.3	10410.00
23	522.87	272.49	0.207	0.60	( 0.59)	0.99	45197.3	12101.10
24	511.30	282.05	0.204	0.60	( 0.59)	0.99	46018.7	10700.00
25	499.91	299.63	0.199	0.60	( 0.59)	0.99	47575.4	10200.00
26	488.14	312.83	0.195	0.60	( 0.60)	0.99	48513.6	12010.00
27	453.14	341.35	0.186	0.60	( 0.60)	0.99	49187.3	10210.00
28	399.79	389.61	0.177	0.60	( 0.60)	0.99	49686.4	12000.00
29	367.53	458.52	0.169	0.60	( 0.60)	0.99	50271.2	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 847.32 Tc (MIN.) = 150.68  
AREA-AVERAGED Fm (INCH/HR) = 0.60 AREA-AVERAGED Fp (INCH/HR) = 0.60  
AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA (ACRES) = 24869.33

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610406t.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	10.78	28.95	0.60 ( 0.60)	0.99	135.0	40600.00
TOTAL AREA (ACRES) = 135.0						

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	521.47	19.54	0.793	0.60 ( 0.59)	0.99	1945.2	40510.00
2	519.28	21.92	0.736	0.60 ( 0.59)	0.99	2214.8	40500.00
3	505.40	28.75	0.612	0.60 ( 0.59)	0.99	2971.4	40430.00
4	501.86	29.34	0.603	0.60 ( 0.59)	0.99	3033.4	40440.00
5	488.21	31.47	0.581	0.60 ( 0.59)	0.99	3258.9	600.00
6	485.19	31.89	0.578	0.60 ( 0.59)	0.99	3313.1	40420.00

7	483.72	32.09	0.576	0.60	( 0.59)	0.99	3339.9	40400.00
8	481.82	32.35	0.574	0.60	( 0.59)	0.99	3372.0	40410.00
9	473.17	32.71	0.571	0.60	( 0.59)	0.99	3416.3	40300.00
10	431.19	37.72	0.530	0.60	( 0.59)	0.99	4010.0	40200.00
11	472.82	69.20	0.383	0.60	( 0.60)	0.99	8479.4	40100.00
12	520.14	82.26	0.360	0.60	( 0.60)	0.99	10210.8	11831.00
13	630.61	106.86	0.315	0.60	( 0.60)	0.99	13907.0	11530.00
14	726.65	127.30	0.283	0.60	( 0.60)	0.99	18062.9	11000.00
15	847.32	150.68	0.262	0.60	( 0.60)	0.99	24869.3	10850.00
16	777.05	165.63	0.249	0.60	( 0.60)	0.99	28189.2	11220.00
17	722.14	176.49	0.239	0.60	( 0.60)	0.99	29941.2	10910.00
18	575.86	215.33	0.225	0.60	( 0.60)	0.99	36522.8	12410.00
19	548.34	223.51	0.222	0.60	( 0.60)	0.99	37955.1	10600.00
20	538.94	240.57	0.217	0.60	( 0.59)	0.99	41398.2	12201.00
21	543.17	247.85	0.215	0.60	( 0.59)	0.99	42608.7	12261.00
22	533.03	260.47	0.211	0.60	( 0.59)	0.99	44095.3	10410.00
23	522.87	272.49	0.207	0.60	( 0.59)	0.99	45197.3	12101.10
24	511.30	282.05	0.204	0.60	( 0.59)	0.99	46018.7	10700.00
25	499.91	299.63	0.199	0.60	( 0.59)	0.99	47575.4	10200.00
26	488.14	312.83	0.195	0.60	( 0.60)	0.99	48513.6	12010.00
27	453.14	341.35	0.186	0.60	( 0.60)	0.99	49187.3	10210.00
28	399.79	389.61	0.177	0.60	( 0.60)	0.99	49686.4	12000.00
29	367.53	458.52	0.169	0.60	( 0.60)	0.99	50271.2	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104605.00 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	10.78	28.95	0.609	0.60 ( 0.60)	0.99	135.0	40600.00

LONGEST FLOWPATH FROM NODE 40600.00 TO NODE 12606.00 = 6107.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	532.25	19.54	0.793	0.60 ( 0.59)	0.99	2036.3	40510.00
2	530.06	21.92	0.736	0.60 ( 0.59)	0.99	2317.0	40500.00
3	516.18	28.75	0.612	0.60 ( 0.59)	0.99	3105.4	40430.00
4	514.96	28.95	0.609	0.60 ( 0.59)	0.99	3127.7	40600.00
5	507.45	29.34	0.603	0.60 ( 0.59)	0.99	3168.4	40440.00
6	490.88	31.47	0.581	0.60 ( 0.59)	0.99	3393.9	600.00
7	487.84	31.89	0.578	0.60 ( 0.59)	0.99	3448.1	40420.00
8	486.36	32.09	0.576	0.60 ( 0.59)	0.99	3474.9	40400.00
9	484.45	32.35	0.574	0.60 ( 0.59)	0.99	3507.0	40410.00
10	475.78	32.71	0.571	0.60 ( 0.59)	0.99	3551.2	40300.00
11	433.62	37.72	0.530	0.60 ( 0.59)	0.99	4145.0	40200.00
12	474.58	69.20	0.383	0.60 ( 0.60)	0.99	8614.3	40100.00
13	521.79	82.26	0.360	0.60 ( 0.60)	0.99	10345.8	11831.00
14	632.05	106.86	0.315	0.60 ( 0.60)	0.99	14042.0	11530.00
15	727.95	127.30	0.283	0.60 ( 0.60)	0.99	18197.9	11000.00
16	848.52	150.68	0.262	0.60 ( 0.60)	0.99	25004.3	10850.00
17	778.19	165.63	0.249	0.60 ( 0.60)	0.99	28324.1	11220.00
18	723.23	176.49	0.239	0.60 ( 0.60)	0.99	30076.2	10910.00
19	576.89	215.33	0.225	0.60 ( 0.60)	0.99	36657.8	12410.00
20	549.36	223.51	0.222	0.60 ( 0.60)	0.99	38090.0	10600.00
21	539.94	240.57	0.217	0.60 ( 0.59)	0.99	41533.1	12201.00
22	544.15	247.85	0.215	0.60 ( 0.59)	0.99	42743.7	12261.00
23	534.00	260.47	0.211	0.60 ( 0.59)	0.99	44230.3	10410.00
24	523.82	272.49	0.207	0.60 ( 0.59)	0.99	45332.3	12101.10

25	512.23	282.05	0.204	0.60	( 0.59)	0.99	46153.6	10700.00
26	500.82	299.63	0.199	0.60	( 0.59)	0.99	47710.3	10200.00
27	489.04	312.83	0.195	0.60	( 0.60)	0.99	48648.6	12010.00
28	453.99	341.35	0.186	0.60	( 0.60)	0.99	49322.3	10210.00
29	400.60	389.61	0.177	0.60	( 0.60)	0.99	49821.4	12000.00
30	368.30	458.52	0.169	0.60	( 0.60)	0.99	50406.1	10100.00

TOTAL AREA(ACRES) = 50406.1

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 848.52 Tc(MIN.) = 150.681  
EFFECTIVE AREA(ACRES) = 25004.30 AREA-AVERAGED Fm(INCH/HR) = 0.60  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99  
TOTAL AREA(ACRES) = 50406.1  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104605.00 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 50406.1 TC(MIN.) = 150.68  
EFFECTIVE AREA(ACRES) = 25004.30 AREA-AVERAGED Fm(INCH/HR) = 0.60  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.994  
PEAK FLOW RATE(CFS) = 848.52

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	532.25	19.54	0.793	0.60 ( 0.59)	0.99	2036.3	40510.00
2	530.06	21.92	0.736	0.60 ( 0.59)	0.99	2317.0	40500.00
3	516.18	28.75	0.612	0.60 ( 0.59)	0.99	3105.4	40430.00
4	514.96	28.95	0.609	0.60 ( 0.59)	0.99	3127.7	40600.00
5	507.45	29.34	0.603	0.60 ( 0.59)	0.99	3168.4	40440.00
6	490.88	31.47	0.581	0.60 ( 0.59)	0.99	3393.9	600.00
7	487.84	31.89	0.578	0.60 ( 0.59)	0.99	3448.1	40420.00
8	486.36	32.09	0.576	0.60 ( 0.59)	0.99	3474.9	40400.00
9	484.45	32.35	0.574	0.60 ( 0.59)	0.99	3507.0	40410.00
10	475.78	32.71	0.571	0.60 ( 0.59)	0.99	3551.2	40300.00
11	433.62	37.72	0.530	0.60 ( 0.59)	0.99	4145.0	40200.00
12	474.58	69.20	0.383	0.60 ( 0.60)	0.99	8614.3	40100.00
13	521.79	82.26	0.360	0.60 ( 0.60)	0.99	10345.8	11831.00
14	632.05	106.86	0.315	0.60 ( 0.60)	0.99	14042.0	11530.00
15	727.95	127.30	0.283	0.60 ( 0.60)	0.99	18197.9	11000.00
16	848.52	150.68	0.262	0.60 ( 0.60)	0.99	25004.3	10850.00
17	778.19	165.63	0.249	0.60 ( 0.60)	0.99	28324.1	11220.00
18	723.23	176.49	0.239	0.60 ( 0.60)	0.99	30076.2	10910.00
19	576.89	215.33	0.225	0.60 ( 0.60)	0.99	36657.8	12410.00
20	549.36	223.51	0.222	0.60 ( 0.60)	0.99	38090.0	10600.00
21	539.94	240.57	0.217	0.60 ( 0.59)	0.99	41533.1	12201.00
22	544.15	247.85	0.215	0.60 ( 0.59)	0.99	42743.7	12261.00
23	534.00	260.47	0.211	0.60 ( 0.59)	0.99	44230.3	10410.00
24	523.82	272.49	0.207	0.60 ( 0.59)	0.99	45332.3	12101.10
25	512.23	282.05	0.204	0.60 ( 0.59)	0.99	46153.6	10700.00
26	500.82	299.63	0.199	0.60 ( 0.59)	0.99	47710.3	10200.00
27	489.04	312.83	0.195	0.60 ( 0.60)	0.99	48648.6	12010.00
28	453.99	341.35	0.186	0.60 ( 0.60)	0.99	49322.3	10210.00

29	400.60	389.61	0.177	0.60	( 0.60)	0.99	49821.4	12000.00
30	368.30	458.52	0.169	0.60	( 0.60)	0.99	50406.1	10100.00

=====  
=====  
END OF RATIONAL METHOD ANALYSIS



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA 92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S27- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 2-YR RM EV APRIL 2019 \*  
\*\*\*\*\*

FILE NAME: RI02EV27.DAT  
TIME/DATE OF STUDY: 17:07 04/08/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 2.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 1.857
- 2) 10.00; 1.238
- 3) 15.00; 0.945
- 4) 20.00; 0.774
- 5) 25.00; 0.667
- 6) 30.00; 0.593
- 7) 40.00; 0.511
- 8) 50.00; 0.453
- 9) 60.00; 0.399
- 10) 90.00; 0.345
- 11) 120.00; 0.290
- 12) 180.00; 0.236
- 13) 360.00; 0.180
- 14) 1200.00; 0.083

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI02EV26.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	532.25	19.54	0.60 ( 0.59)	0.99	2036.3	40510.00
2	516.18	28.75	0.60 ( 0.59)	0.99	3105.4	40430.00
3	433.62	37.72	0.60 ( 0.59)	0.99	4145.0	40200.00
4	474.58	69.20	0.60 ( 0.60)	0.99	8614.3	40100.00
5	521.79	82.26	0.60 ( 0.60)	0.99	10345.8	11831.00
6	632.05	106.86	0.60 ( 0.60)	0.99	14042.0	11530.00
7	727.95	127.30	0.60 ( 0.60)	0.99	18197.9	11000.00
8	848.52	150.68	0.60 ( 0.60)	0.99	25004.3	10850.00
9	778.19	165.63	0.60 ( 0.60)	0.99	28324.1	11220.00
10	723.23	176.49	0.60 ( 0.60)	0.99	30076.2	10910.00
11	576.89	215.33	0.60 ( 0.60)	0.99	36657.8	12410.00
12	544.15	247.85	0.60 ( 0.59)	0.99	42743.7	12261.00
13	534.00	260.47	0.60 ( 0.59)	0.99	44230.3	10410.00
14	523.82	272.49	0.60 ( 0.59)	0.99	45332.3	12101.10
15	512.23	282.05	0.60 ( 0.59)	0.99	46153.6	10700.00
16	500.82	299.63	0.60 ( 0.59)	0.99	47710.3	10200.00
17	489.04	312.83	0.60 ( 0.60)	0.99	48648.6	12010.00
18	453.99	341.35	0.60 ( 0.60)	0.99	49322.3	10210.00
19	400.60	389.61	0.60 ( 0.60)	0.99	49821.4	12000.00
20	368.30	458.52	0.60 ( 0.60)	0.99	50406.1	10100.00
TOTAL AREA(ACRES) =						50406.1

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	532.25	19.54	0.60 ( 0.59)	0.99	2036.3	40510.00
2	516.18	28.75	0.60 ( 0.59)	0.99	3105.4	40430.00
3	433.62	37.72	0.60 ( 0.59)	0.99	4145.0	40200.00
4	474.58	69.20	0.60 ( 0.60)	0.99	8614.3	40100.00
5	521.79	82.26	0.60 ( 0.60)	0.99	10345.8	11831.00
6	632.05	106.86	0.60 ( 0.60)	0.99	14042.0	11530.00
7	727.95	127.30	0.60 ( 0.60)	0.99	18197.9	11000.00
8	848.52	150.68	0.60 ( 0.60)	0.99	25004.3	10850.00
9	778.19	165.63	0.60 ( 0.60)	0.99	28324.1	11220.00
10	723.23	176.49	0.60 ( 0.60)	0.99	30076.2	10910.00
11	576.89	215.33	0.60 ( 0.60)	0.99	36657.8	12410.00
12	544.15	247.85	0.60 ( 0.59)	0.99	42743.7	12261.00
13	534.00	260.47	0.60 ( 0.59)	0.99	44230.3	10410.00

14	523.82	272.49	0.60	( 0.59)	0.99	45332.3	12101.10
15	512.23	282.05	0.60	( 0.59)	0.99	46153.6	10700.00
16	500.82	299.63	0.60	( 0.59)	0.99	47710.3	10200.00
17	489.04	312.83	0.60	( 0.60)	0.99	48648.6	12010.00
18	453.99	341.35	0.60	( 0.60)	0.99	49322.3	10210.00
19	400.60	389.61	0.60	( 0.60)	0.99	49821.4	12000.00
20	368.30	458.52	0.60	( 0.60)	0.99	50406.1	10100.00

TOTAL AREA(ACRES) = 50406.1

\*\*\*\*\*

FLOW PROCESS FROM NODE 12606.00 TO NODE 12701.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 286.00 DOWNSTREAM(FEET) = 276.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1260.19 CHANNEL SLOPE = 0.0079  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.260

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.55	0.60	0.100	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 849.32

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.61

AVERAGE FLOW DEPTH(FEET) = 5.73 TRAVEL TIME(MIN.) = 2.44

Tc(MIN.) = 153.12

SUBAREA AREA(ACRES) = 7.55 SUBAREA RUNOFF(CFS) = 1.59

EFFECTIVE AREA(ACRES) = 25011.85 AREA-AVERAGED Fm(INCH/HR) = 0.60

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 50413.7 PEAK FLOW RATE(CFS) = 848.52

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 5.73 FLOW VELOCITY(FEET/SEC.) = 8.60

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12701.00 = 105865.19 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	532.25	22.28	0.725	0.60( 0.59)	0.99	2043.9	40510.00
2	516.18	31.51	0.581	0.60( 0.59)	0.99	3112.9	40430.00
3	433.62	40.61	0.507	0.60( 0.59)	0.99	4152.6	40200.00
4	474.58	72.03	0.377	0.60( 0.59)	0.99	8621.9	40100.00
5	521.79	85.01	0.354	0.60( 0.59)	0.99	10353.4	11831.00
6	632.05	109.48	0.309	0.60( 0.60)	0.99	14049.5	11530.00
7	727.95	129.84	0.281	0.60( 0.60)	0.99	18205.5	11000.00
8	848.52	153.12	0.260	0.60( 0.60)	0.99	25011.8	10850.00
9	778.19	168.12	0.247	0.60( 0.60)	0.99	28331.7	11220.00
10	723.23	179.03	0.237	0.60( 0.60)	0.99	30083.7	10910.00
11	576.89	218.02	0.224	0.60( 0.60)	0.99	36665.4	12410.00

12	544.15	250.58	0.214	0.60( 0.59)	0.99	42751.3	12261.00
13	534.00	263.21	0.210	0.60( 0.59)	0.99	44237.9	10410.00
14	523.82	275.25	0.206	0.60( 0.59)	0.99	45339.8	12101.10
15	512.23	284.82	0.203	0.60( 0.59)	0.99	46161.2	10700.00
16	500.82	302.42	0.198	0.60( 0.59)	0.99	47717.9	10200.00
17	489.04	315.63	0.194	0.60( 0.59)	0.99	48656.1	12010.00
18	453.99	344.21	0.185	0.60( 0.60)	0.99	49329.8	10210.00
19	400.60	392.56	0.176	0.60( 0.60)	0.99	49828.9	12000.00
20	368.30	461.52	0.168	0.60( 0.60)	0.99	50413.7	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 848.52 Tc(MIN.) = 153.12

AREA-AVERAGED Fm(INCH/HR) = 0.60 AREA-AVERAGED Fp(INCH/HR) = 0.60

AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 25011.85

\*\*\*\*\*

FLOW PROCESS FROM NODE 12701.00 TO NODE 12701.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 153.12

\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.260

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.90	0.60	0.850	-
USER-DEFINED	-	3.40	0.60	1.000	-
USER-DEFINED	-	0.40	0.60	0.500	-
USER-DEFINED	-	23.00	0.60	1.000	-
USER-DEFINED	-	3.30	0.60	1.000	-
USER-DEFINED	-	0.40	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.989

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 31.40 SUBAREA RUNOFF(CFS) = 0.08

EFFECTIVE AREA(ACRES) = 25043.25 AREA-AVERAGED Fm(INCH/HR) = 0.60

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 50445.1 PEAK FLOW RATE(CFS) = 848.52

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12701.00 TO NODE 12701.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 153.12

\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.260

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.70	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 1.70 SUBAREA RUNOFF(CFS) = 0.00

EFFECTIVE AREA(ACRES) = 25044.95 AREA-AVERAGED Fm(INCH/HR) = 0.60  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 50446.8 PEAK FLOW RATE(CFS) = 848.52  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12701.00 TO NODE 12720.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 276.00 DOWNSTREAM(FEET) = 275.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 147.65 CHANNEL SLOPE = 0.0068  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.260

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.49	0.60	0.850	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.850

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 848.55  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.10  
 AVERAGE FLOW DEPTH(FEET) = 5.91 TRAVEL TIME(MIN.) = 0.30  
 Tc(MIN.) = 153.42

SUBAREA AREA(ACRES) = 1.49 SUBAREA RUNOFF(CFS) = 0.05  
 EFFECTIVE AREA(ACRES) = 25046.44 AREA-AVERAGED Fm(INCH/HR) = 0.60  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 50448.3 PEAK FLOW RATE(CFS) = 848.52  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 5.91 FLOW VELOCITY(FEET/SEC.) = 8.10  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.00 = 106012.84 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	532.25	22.62	0.718	0.60( 0.59)	0.99	2078.5	40510.00
2	516.18	31.86	0.578	0.60( 0.59)	0.99	3147.5	40430.00
3	433.62	40.97	0.505	0.60( 0.59)	0.99	4187.1	40200.00
4	474.58	72.38	0.377	0.60( 0.59)	0.99	8656.5	40100.00
5	521.79	85.36	0.353	0.60( 0.59)	0.99	10387.9	11831.00
6	632.05	109.81	0.309	0.60( 0.60)	0.99	14084.1	11530.00
7	727.95	130.16	0.281	0.60( 0.60)	0.99	18240.0	11000.00
8	848.52	153.42	0.260	0.60( 0.60)	0.99	25046.4	10850.00
9	778.19	168.43	0.246	0.60( 0.60)	0.99	28366.3	11220.00
10	723.23	179.34	0.237	0.60( 0.60)	0.99	30118.3	10910.00
11	576.89	218.35	0.224	0.60( 0.60)	0.99	36699.9	12410.00
12	544.15	250.92	0.214	0.60( 0.59)	0.99	42785.8	12261.00
13	534.00	263.55	0.210	0.60( 0.59)	0.99	44272.4	10410.00

14	523.82	275.59	0.206	0.60( 0.59)	0.99	45374.4	12101.10
15	512.23	285.16	0.203	0.60( 0.59)	0.99	46195.8	10700.00
16	500.82	302.76	0.198	0.60( 0.59)	0.99	47752.5	10200.00
17	489.04	315.98	0.194	0.60( 0.59)	0.99	48690.7	12010.00
18	453.99	344.56	0.185	0.60( 0.60)	0.99	49364.4	10210.00
19	400.60	392.93	0.176	0.60( 0.60)	0.99	49863.5	12000.00
20	368.30	461.89	0.168	0.60( 0.60)	0.99	50448.3	10100.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE(CFS) = 848.52 Tc(MIN.) = 153.42  
 AREA-AVERAGED Fm(INCH/HR) = 0.60 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 25046.44

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12701.00 TO NODE 12720.00 IS CODE = 1  
 -----

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
 TIME OF CONCENTRATION(MIN.) = 153.42  
 RAINFALL INTENSITY(INCH/HR) = 0.26  
 AREA-AVERAGED Fm(INCH/HR) = 0.60  
 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.99  
 EFFECTIVE STREAM AREA(ACRES) = 25046.44  
 TOTAL STREAM AREA(ACRES) = 50448.27  
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 848.52

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12710.00 TO NODE 12711.00 IS CODE = 21  
 -----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<  
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 943.56  
 ELEVATION DATA: UPSTREAM(FEET) = 940.78 DOWNSTREAM(FEET) = 657.79

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
 SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 13.910  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 1.009  
 SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER						
"GRASS"	-	6.56	0.60	1.000	0	13.91

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA RUNOFF(CFS) = 2.41  
 TOTAL AREA(ACRES) = 6.56 PEAK FLOW RATE(CFS) = 2.41

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12711.00 TO NODE 12712.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 657.79 DOWNSTREAM(FEET) = 585.63  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 766.00 CHANNEL SLOPE = 0.0942

CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.865  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	26.94	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 5.71  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 3.73  
AVERAGE FLOW DEPTH (FEET) = 0.71 TRAVEL TIME (MIN.) = 3.42  
Tc (MIN.) = 17.33  
SUBAREA AREA (ACRES) = 26.94 SUBAREA RUNOFF (CFS) = 6.44  
EFFECTIVE AREA (ACRES) = 33.50 AREA-AVERAGED Fm (INCH/HR) = 0.60  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
TOTAL AREA (ACRES) = 33.5 PEAK FLOW RATE (CFS) = 8.00

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 0.81 FLOW VELOCITY (FEET/SEC.) = 4.03  
LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12712.00 = 1709.56 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12712.00 TO NODE 12713.00 IS CODE = 51

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 585.63 DOWNSTREAM (FEET) = 463.75  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1025.79 CHANNEL SLOPE = 0.1188  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.757  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	14.73	0.60	0.100	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 12.59  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.95  
AVERAGE FLOW DEPTH (FEET) = 0.92 TRAVEL TIME (MIN.) = 3.45  
Tc (MIN.) = 20.78  
SUBAREA AREA (ACRES) = 14.73 SUBAREA RUNOFF (CFS) = 9.24  
EFFECTIVE AREA (ACRES) = 48.23 AREA-AVERAGED Fm (INCH/HR) = 0.43  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.73  
TOTAL AREA (ACRES) = 48.2 PEAK FLOW RATE (CFS) = 13.99

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 0.96 FLOW VELOCITY (FEET/SEC.) = 5.08  
LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12713.00 = 2735.35 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12713.00 TO NODE 12714.00 IS CODE = 51

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 463.75 DOWNSTREAM (FEET) = 360.30  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1148.54 CHANNEL SLOPE = 0.0901  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.689  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	105.64	0.60	0.100	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 43.60  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.04  
AVERAGE FLOW DEPTH (FEET) = 1.55 TRAVEL TIME (MIN.) = 3.17  
Tc (MIN.) = 23.95  
SUBAREA AREA (ACRES) = 105.64 SUBAREA RUNOFF (CFS) = 59.84  
EFFECTIVE AREA (ACRES) = 153.87 AREA-AVERAGED Fm (INCH/HR) = 0.18  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.30  
TOTAL AREA (ACRES) = 153.9 PEAK FLOW RATE (CFS) = 70.88

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 1.86 FLOW VELOCITY (FEET/SEC.) = 6.84  
LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12714.00 = 3883.89 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12714.00 TO NODE 12720.00 IS CODE = 51

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 360.30 DOWNSTREAM (FEET) = 275.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1314.99 CHANNEL SLOPE = 0.0649  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.634  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	127.13	0.60	0.100	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 103.67  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.66  
AVERAGE FLOW DEPTH (FEET) = 2.28 TRAVEL TIME (MIN.) = 3.29  
Tc (MIN.) = 27.25  
SUBAREA AREA (ACRES) = 127.13 SUBAREA RUNOFF (CFS) = 65.65  
EFFECTIVE AREA (ACRES) = 281.00 AREA-AVERAGED Fm (INCH/HR) = 0.12  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.21  
TOTAL AREA (ACRES) = 281.0 PEAK FLOW RATE (CFS) = 128.83

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 2.47 FLOW VELOCITY (FEET/SEC.) = 7.01  
LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12720.00 = 5198.88 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.00 IS CODE = 1

-----  
>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 27.25
RAINFALL INTENSITY(INCH/HR) = 0.63
AREA-AVERAGED Fm(INCH/HR) = 0.12
AREA-AVERAGED Fp(INCH/HR) = 0.60
AREA-AVERAGED Ap = 0.21
EFFECTIVE STREAM AREA(ACRES) = 281.00
TOTAL STREAM AREA(ACRES) = 281.00
PEAK FLOW RATE(CFS) AT CONFLUENCE = 128.83

\*\* CONFLUENCE DATA \*\*

Table with columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 21 rows of data for stream 1 and 2.

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

Table with columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 14 rows of data for stream 1.

Table with columns: Stream Number, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 6 rows of data for stream 1.

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 900.63 Tc(MIN.) = 153.42
EFFECTIVE AREA(ACRES) = 25327.44 AREA-AVERAGED Fm(INCH/HR) = 0.59
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 50729.3
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.00 = 106012.84 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 153.42
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.260
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 3.80 0.60 1.000 -
USER-DEFINED - 0.40 0.60 0.850 -
USER-DEFINED - 0.20 0.60 0.500 -
USER-DEFINED - 0.10 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.964
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 4.50 SUBAREA RUNOFF(CFS) = 0.04
EFFECTIVE AREA(ACRES) = 25331.94 AREA-AVERAGED Fm(INCH/HR) = 0.59
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 50733.8 PEAK FLOW RATE(CFS) = 900.63
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*
FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.50 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 275.00 DOWNSTREAM(FEET) = 258.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 2669.21 CHANNEL SLOPE = 0.0064
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.255
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 62.15 0.60 0.100 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 907.05  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY( FEET/SEC.) = 8.05  
 AVERAGE FLOW DEPTH( FEET) = 6.13 TRAVEL TIME( MIN.) = 5.53  
 Tc( MIN.) = 158.95  
 SUBAREA AREA( ACRES) = 62.15 SUBAREA RUNOFF( CFS) = 12.83  
 EFFECTIVE AREA( ACRES) = 25394.09 AREA-AVERAGED Fm( INCH/HR) = 0.59  
 AREA-AVERAGED Fp( INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.98  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA( ACRES) = 50795.9 PEAK FLOW RATE( CFS) = 900.63  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH( FEET) = 6.11 FLOW VELOCITY( FEET/SEC.) = 8.03  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108682.05 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	656.88	28.57	0.614	0.60( 0.53)	0.89	2378.4	40510.00
2	653.03	33.21	0.567	0.60( 0.54)	0.90	2961.3	12710.00
3	632.01	37.87	0.528	0.60( 0.55)	0.91	3495.2	40430.00
4	534.94	47.24	0.469	0.60( 0.56)	0.93	4534.8	40200.00
5	550.10	78.62	0.365	0.60( 0.58)	0.96	9004.1	40100.00
6	592.63	91.48	0.342	0.60( 0.58)	0.97	10735.6	11831.00
7	693.93	115.70	0.298	0.60( 0.58)	0.97	14431.8	11530.00
8	784.25	135.88	0.276	0.60( 0.59)	0.98	18587.7	11000.00
9	900.63	158.95	0.255	0.60( 0.59)	0.98	25394.1	10850.00
10	827.59	174.08	0.241	0.60( 0.59)	0.98	28713.9	11220.00
11	770.66	185.09	0.234	0.60( 0.59)	0.99	30466.0	10910.00
12	621.81	224.41	0.222	0.60( 0.59)	0.99	37047.6	12410.00
13	587.04	257.07	0.212	0.60( 0.59)	0.98	43133.5	12261.00
14	576.10	269.73	0.208	0.60( 0.59)	0.99	44620.1	10410.00
15	565.17	281.79	0.204	0.60( 0.59)	0.99	45722.0	12101.10
16	552.99	291.40	0.201	0.60( 0.59)	0.99	46543.4	10700.00
17	540.48	309.04	0.196	0.60( 0.59)	0.99	48100.1	10200.00
18	527.87	322.29	0.192	0.60( 0.59)	0.99	49038.4	12010.00
19	491.04	350.99	0.183	0.60( 0.59)	0.99	49712.1	10210.00
20	435.92	399.55	0.175	0.60( 0.59)	0.99	50211.1	12000.00
21	402.03	468.65	0.167	0.60( 0.59)	0.99	50795.9	10100.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE( CFS) = 900.63 Tc( MIN.) = 158.95  
 AREA-AVERAGED Fm( INCH/HR) = 0.59 AREA-AVERAGED Fp( INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.98 EFFECTIVE AREA( ACRES) = 25394.09

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 =====  
 MAINLINE Tc( MIN.) = 158.95  
 \* 2 YEAR RAINFALL INTENSITY( INCH/HR) = 0.255  
 SUBAREA LOSS RATE DATA( AMC II):  
 DEVELOPMENT TYPE/ SCSSOIL AREA Fp Ap SCSS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 0.10 0.60 0.100 -

USER-DEFINED - 0.70 0.60 1.000 -  
 USER-DEFINED - 0.30 0.60 1.000 -  
 USER-DEFINED - 17.90 0.60 1.000 -  
 USER-DEFINED - 0.20 0.60 1.000 -  
 USER-DEFINED - 0.30 0.60 0.850 -  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp( INCH/HR) = 0.60  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.993  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 SUBAREA AREA( ACRES) = 19.50 SUBAREA RUNOFF( CFS) = 0.03  
 EFFECTIVE AREA( ACRES) = 25413.59 AREA-AVERAGED Fm( INCH/HR) = 0.59  
 AREA-AVERAGED Fp( INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.98  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA( ACRES) = 50815.4 PEAK FLOW RATE( CFS) = 900.63  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 =====  
 MAINLINE Tc( MIN.) = 158.95  
 \* 2 YEAR RAINFALL INTENSITY( INCH/HR) = 0.255  
 SUBAREA LOSS RATE DATA( AMC II):  
 DEVELOPMENT TYPE/ SCSSOIL AREA Fp Ap SCSS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 0.50 0.60 1.000 -  
 USER-DEFINED - 0.60 0.60 0.900 -  
 USER-DEFINED - 0.30 0.60 0.900 -  
 USER-DEFINED - 0.10 0.60 0.500 -  
 USER-DEFINED - 1.10 0.60 1.000 -  
 USER-DEFINED - 0.90 0.60 1.000 -  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp( INCH/HR) = 0.60  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.960  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 SUBAREA AREA( ACRES) = 3.50 SUBAREA RUNOFF( CFS) = 0.03  
 EFFECTIVE AREA( ACRES) = 25417.09 AREA-AVERAGED Fm( INCH/HR) = 0.59  
 AREA-AVERAGED Fp( INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.98  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA( ACRES) = 50818.9 PEAK FLOW RATE( CFS) = 900.63  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 2 <<<<<  
 =====  
 PEAK FLOWRATE TABLE FILE NAME: 3D02EVRL.DNA  
 MEMORY BANK # 2 DEFINED AS FOLLOWS:  
 STREAM Q Tc Fp(Fm) Ap Ae HEADWATER  
 NUMBER (CFS) (MIN.) (INCH/HR) (ACRES) NODE  
 1 172.49 26.93 0.60( 0.28) 0.48 349.4 413.00  
 2 166.67 36.39 0.60( 0.29) 0.48 430.2 430.00  
 3 154.25 39.27 0.60( 0.29) 0.48 439.5 400.00  
 TOTAL AREA( ACRES) = 439.5

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	656.88	28.57	0.614	0.60 ( 0.53)	0.89	2401.4	40510.00
2	653.03	33.21	0.567	0.60 ( 0.54)	0.90	2984.3	12710.00
3	632.01	37.87	0.528	0.60 ( 0.55)	0.91	3518.2	40430.00
4	534.94	47.24	0.469	0.60 ( 0.56)	0.93	4557.8	40200.00
5	550.10	78.62	0.365	0.60 ( 0.58)	0.96	9027.1	40100.00
6	592.63	91.48	0.342	0.60 ( 0.58)	0.97	10758.6	11831.00
7	693.93	115.70	0.298	0.60 ( 0.58)	0.97	14454.8	11530.00
8	784.25	135.88	0.276	0.60 ( 0.59)	0.98	18610.7	11000.00
9	900.63	158.95	0.255	0.60 ( 0.59)	0.98	25417.1	10850.00
10	827.59	174.08	0.241	0.60 ( 0.59)	0.98	28736.9	11220.00
11	770.66	185.09	0.234	0.60 ( 0.59)	0.99	30489.0	10910.00
12	621.81	224.41	0.222	0.60 ( 0.59)	0.99	37070.6	12410.00
13	587.04	257.07	0.212	0.60 ( 0.59)	0.98	43156.5	12261.00
14	576.10	269.73	0.208	0.60 ( 0.59)	0.99	44643.1	10410.00
15	565.17	281.79	0.204	0.60 ( 0.59)	0.99	45745.0	12101.10
16	552.99	291.40	0.201	0.60 ( 0.59)	0.99	46566.4	10700.00
17	540.48	309.04	0.196	0.60 ( 0.59)	0.99	48123.1	10200.00
18	527.87	322.29	0.192	0.60 ( 0.59)	0.99	49061.4	12010.00
19	491.04	350.99	0.183	0.60 ( 0.59)	0.99	49735.1	10210.00
20	435.92	399.55	0.175	0.60 ( 0.59)	0.99	50234.1	12000.00
21	402.03	468.65	0.167	0.60 ( 0.59)	0.99	50818.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108682.05 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	172.49	26.93	0.638	0.60 ( 0.28)	0.48	349.4	413.00
2	166.67	36.39	0.541	0.60 ( 0.29)	0.48	430.2	430.00
3	154.25	39.27	0.517	0.60 ( 0.29)	0.48	439.5	400.00

LONGEST FLOWPATH FROM NODE 430.00 TO NODE 12720.50 = 11352.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	829.38	26.93	0.638	0.60 ( 0.50)	0.83	2613.0	413.00
2	828.37	28.57	0.614	0.60 ( 0.50)	0.83	2764.9	40510.00
3	821.66	33.21	0.567	0.60 ( 0.51)	0.85	3387.3	12710.00
4	805.32	36.39	0.541	0.60 ( 0.51)	0.86	3779.6	430.00
5	792.31	37.87	0.528	0.60 ( 0.52)	0.86	3953.1	40430.00
6	771.78	39.27	0.517	0.60 ( 0.52)	0.87	4112.8	400.00
7	674.87	47.24	0.469	0.60 ( 0.53)	0.89	4997.3	40200.00
8	659.14	78.62	0.365	0.60 ( 0.56)	0.94	9466.6	40100.00
9	694.75	91.48	0.342	0.60 ( 0.57)	0.95	11198.1	11831.00
10	782.81	115.70	0.298	0.60 ( 0.57)	0.96	14894.3	11530.00
11	866.51	135.88	0.276	0.60 ( 0.58)	0.97	19050.2	11000.00
12	976.69	158.95	0.255	0.60 ( 0.58)	0.97	25856.6	10850.00
13	899.59	174.08	0.241	0.60 ( 0.59)	0.98	29176.4	11220.00
14	840.60	185.09	0.234	0.60 ( 0.59)	0.98	30928.5	10910.00

15	688.10	224.41	0.222	0.60 ( 0.59)	0.98	37510.1	12410.00
16	650.30	257.07	0.212	0.60 ( 0.59)	0.98	43596.0	12261.00
17	638.18	269.73	0.208	0.60 ( 0.59)	0.98	45082.6	10410.00
18	626.13	281.79	0.204	0.60 ( 0.59)	0.98	46184.5	12101.10
19	613.06	291.40	0.201	0.60 ( 0.59)	0.98	47005.9	10700.00
20	598.91	309.04	0.196	0.60 ( 0.59)	0.98	48562.6	10200.00
21	585.07	322.29	0.192	0.60 ( 0.59)	0.98	49500.9	12010.00
22	545.58	350.99	0.183	0.60 ( 0.59)	0.98	50174.6	10210.00
23	488.26	399.55	0.175	0.60 ( 0.59)	0.98	50673.6	12000.00
24	451.99	468.65	0.167	0.60 ( 0.59)	0.98	51258.4	10100.00

TOTAL AREA (ACRES) = 51258.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 976.69 Tc (MIN.) = 158.952  
EFFECTIVE AREA (ACRES) = 25856.59 AREA-AVERAGED Fm (INCH/HR) = 0.58  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.95  
TOTAL AREA (ACRES) = 51258.4  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108682.05 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.50 TO NODE 12721.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 258.00 DOWNSTREAM (FEET) = 256.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 438.77 CHANNEL SLOPE = 0.0046  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA (CFS) = 976.69  
FLOW VELOCITY (FEET/SEC.) = 7.23 FLOW DEPTH (FEET) = 6.71  
TRAVEL TIME (MIN.) = 1.01 Tc (MIN.) = 159.96  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12721.00 = 109120.82 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	829.38	27.99	0.623	0.60 ( 0.50)	0.83	2613.0	413.00
2	828.37	29.63	0.599	0.60 ( 0.50)	0.83	2764.9	40510.00
3	821.66	34.26	0.558	0.60 ( 0.51)	0.85	3387.3	12710.00
4	805.32	37.45	0.532	0.60 ( 0.51)	0.86	3779.6	430.00
5	792.31	38.93	0.520	0.60 ( 0.52)	0.86	3953.1	40430.00
6	771.78	40.34	0.509	0.60 ( 0.52)	0.87	4112.8	400.00
7	674.87	48.35	0.463	0.60 ( 0.53)	0.89	4997.3	40200.00
8	659.14	79.74	0.363	0.60 ( 0.56)	0.94	9466.6	40100.00
9	694.75	92.58	0.340	0.60 ( 0.57)	0.95	11198.1	11831.00
10	782.81	116.77	0.296	0.60 ( 0.57)	0.96	14894.3	11530.00
11	866.51	136.92	0.275	0.60 ( 0.58)	0.97	19050.2	11000.00
12	976.69	159.96	0.254	0.60 ( 0.58)	0.97	25856.6	10850.00
13	899.59	175.11	0.240	0.60 ( 0.59)	0.98	29176.4	11220.00
14	840.60	186.14	0.234	0.60 ( 0.59)	0.98	30928.5	10910.00
15	688.10	225.52	0.222	0.60 ( 0.59)	0.98	37510.1	12410.00

16	650.30	258.18	0.212	0.60	( 0.59)	0.98	43596.0	12261.00
17	638.18	270.85	0.208	0.60	( 0.59)	0.98	45082.6	10410.00
18	626.13	282.92	0.204	0.60	( 0.59)	0.98	46184.5	12101.10
19	613.06	292.53	0.201	0.60	( 0.59)	0.98	47005.9	10700.00
20	598.91	310.18	0.196	0.60	( 0.59)	0.98	48562.6	10200.00
21	585.07	323.43	0.191	0.60	( 0.59)	0.98	49500.9	12010.00
22	545.58	352.16	0.182	0.60	( 0.59)	0.98	50174.6	10210.00
23	488.26	400.75	0.175	0.60	( 0.59)	0.98	50673.6	12000.00
24	451.99	469.88	0.167	0.60	( 0.59)	0.98	51258.4	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 976.69 Tc(MIN.) = 159.96  
 AREA-AVERAGED Fm(INCH/HR) = 0.58 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.97 EFFECTIVE AREA(ACRES) = 25856.59

\*\*\*\*\*

FLOW PROCESS FROM NODE 12721.00 TO NODE 12722.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 256.00 DOWNSTREAM(FEET) = 255.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 830.42 CHANNEL SLOPE = 0.0012  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.251

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	11.24	0.60	0.100	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 977.84  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.40  
 AVERAGE FLOW DEPTH(FEET) = 8.61 TRAVEL TIME(MIN.) = 3.15  
 Tc(MIN.) = 163.11  
 SUBAREA AREA(ACRES) = 11.24 SUBAREA RUNOFF(CFS) = 2.29  
 EFFECTIVE AREA(ACRES) = 25867.83 AREA-AVERAGED Fm(INCH/HR) = 0.58  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.97  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 51269.7 PEAK FLOW RATE(CFS) = 976.69  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 8.61 FLOW VELOCITY(FEET/SEC.) = 4.39  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12722.00 = 109951.24 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	829.38	31.27	0.583	0.60( 0.50)	0.83	2624.3	413.00
2	828.37	32.91	0.569	0.60( 0.50)	0.83	2776.1	40510.00
3	821.66	37.55	0.531	0.60( 0.51)	0.84	3398.5	12710.00
4	805.32	40.76	0.507	0.60( 0.51)	0.85	3790.8	430.00
5	792.31	42.25	0.498	0.60( 0.52)	0.86	3964.4	40430.00
6	771.78	43.68	0.490	0.60( 0.52)	0.86	4124.1	400.00

7	674.87	51.80	0.443	0.60	( 0.53)	0.89	5008.5	40200.00
8	659.14	83.21	0.357	0.60	( 0.56)	0.94	9477.9	40100.00
9	694.75	96.01	0.334	0.60	( 0.57)	0.95	11209.3	11831.00
10	782.81	120.10	0.290	0.60	( 0.57)	0.96	14905.5	11530.00
11	866.51	140.17	0.272	0.60	( 0.58)	0.97	19061.4	11000.00
12	976.69	163.11	0.251	0.60	( 0.58)	0.97	25867.8	10850.00
13	899.59	178.33	0.238	0.60	( 0.59)	0.98	29187.7	11220.00
14	840.60	189.41	0.233	0.60	( 0.59)	0.98	30939.7	10910.00
15	688.10	228.96	0.221	0.60	( 0.59)	0.98	37521.3	12410.00
16	650.30	261.67	0.211	0.60	( 0.59)	0.98	43607.2	12261.00
17	638.18	274.35	0.207	0.60	( 0.59)	0.98	45093.8	10410.00
18	626.13	286.44	0.203	0.60	( 0.59)	0.98	46195.8	12101.10
19	613.06	296.08	0.200	0.60	( 0.59)	0.98	47017.2	10700.00
20	598.91	313.73	0.194	0.60	( 0.59)	0.98	48573.9	10200.00
21	585.07	327.01	0.190	0.60	( 0.59)	0.98	49512.1	12010.00
22	545.58	355.80	0.181	0.60	( 0.59)	0.98	50185.8	10210.00
23	488.26	404.49	0.175	0.60	( 0.59)	0.98	50684.9	12000.00
24	451.99	473.69	0.167	0.60	( 0.59)	0.98	51269.7	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 976.69 Tc(MIN.) = 163.11  
 AREA-AVERAGED Fm(INCH/HR) = 0.58 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.97 EFFECTIVE AREA(ACRES) = 25867.83

\*\*\*\*\*

FLOW PROCESS FROM NODE 12722.00 TO NODE 12722.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 163.11  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.251  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 2.10 0.60 1.000 -  
 USER-DEFINED - 0.10 0.60 1.000 -  
 USER-DEFINED - 3.60 0.60 1.000 -  
 USER-DEFINED - 4.10 0.60 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 SUBAREA AREA(ACRES) = 9.90 SUBAREA RUNOFF(CFS) = 0.00  
 EFFECTIVE AREA(ACRES) = 25877.73 AREA-AVERAGED Fm(INCH/HR) = 0.58  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.97  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 51279.6 PEAK FLOW RATE(CFS) = 976.69  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12722.00 TO NODE 12722.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 163.11  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.251  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS



LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 0.60 0.60 0.900 -  
 USER-DEFINED - 1.90 0.60 1.000 -  
 USER-DEFINED - 0.10 0.60 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.977  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 SUBAREA AREA(ACRES) = 2.60 SUBAREA RUNOFF(CFS) = 0.01  
 EFFECTIVE AREA(ACRES) = 25880.33 AREA-AVERAGED Fm(INCH/HR) = 0.58  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.97  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 51282.2 PEAK FLOW RATE(CFS) = 976.69  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12722.00 TO NODE 12740.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 255.00 DOWNSTREAM(FEET) = 252.10  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 624.00 CHANNEL SLOPE = 0.0046  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.250

SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 1.50 0.60 0.100 -  
 USER-DEFINED - 2.50 0.60 1.000 -  
 USER-DEFINED - 0.50 0.60 1.000 -  
 USER-DEFINED - 0.70 0.60 1.000 -  
 USER-DEFINED - 6.20 0.60 1.000 -  
 USER-DEFINED - 6.50 0.60 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.925  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 976.85  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.28  
 AVERAGE FLOW DEPTH(FEET) = 6.69 TRAVEL TIME(MIN.) = 1.43  
 Tc(MIN.) = 164.54  
 SUBAREA AREA(ACRES) = 17.90 SUBAREA RUNOFF(CFS) = 0.30  
 EFFECTIVE AREA(ACRES) = 25898.23 AREA-AVERAGED Fm(INCH/HR) = 0.58  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.97  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 51300.1 PEAK FLOW RATE(CFS) = 976.69  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 6.69 FLOW VELOCITY(FEET/SEC.) = 7.28  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12740.00 = 110575.24 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	--------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	829.38	32.75	0.570	0.60( 0.50)	0.83	2654.7 413.00
2	828.37	34.40	0.557	0.60( 0.50)	0.83	2806.5 40510.00
3	821.66	39.04	0.519	0.60( 0.51)	0.84	3428.9 12710.00
4	805.32	42.26	0.498	0.60( 0.51)	0.86	3821.2 430.00
5	792.31	43.75	0.489	0.60( 0.52)	0.86	3994.8 40430.00
6	771.78	45.19	0.481	0.60( 0.52)	0.87	4154.5 400.00
7	674.87	53.37	0.435	0.60( 0.53)	0.89	5038.9 40200.00
8	659.14	84.79	0.354	0.60( 0.56)	0.94	9508.3 40100.00
9	694.75	97.56	0.331	0.60( 0.57)	0.95	11239.7 11831.00
10	782.81	121.61	0.289	0.60( 0.57)	0.96	14935.9 11530.00
11	866.51	141.64	0.271	0.60( 0.58)	0.97	19091.8 11000.00
12	976.69	164.54	0.250	0.60( 0.58)	0.97	25898.2 10850.00
13	899.59	179.78	0.236	0.60( 0.59)	0.98	29218.1 11220.00
14	840.60	190.89	0.233	0.60( 0.59)	0.98	30970.1 10910.00
15	688.10	230.51	0.220	0.60( 0.59)	0.98	37551.7 12410.00
16	650.30	263.25	0.210	0.60( 0.59)	0.98	43637.6 12261.00
17	638.18	275.94	0.206	0.60( 0.59)	0.98	45124.2 10410.00
18	626.13	288.03	0.202	0.60( 0.59)	0.98	46226.2 12101.10
19	613.06	297.68	0.199	0.60( 0.59)	0.98	47047.6 10700.00
20	598.91	315.35	0.194	0.60( 0.59)	0.98	48604.3 10200.00
21	585.07	328.64	0.190	0.60( 0.59)	0.98	49542.5 12010.00
22	545.58	357.45	0.181	0.60( 0.59)	0.98	50216.2 10210.00
23	488.26	406.19	0.175	0.60( 0.59)	0.98	50715.3 12000.00
24	451.99	475.42	0.167	0.60( 0.59)	0.98	51300.1 10100.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE(CFS) = 976.69 Tc(MIN.) = 164.54  
 AREA-AVERAGED Fm(INCH/HR) = 0.58 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.97 EFFECTIVE AREA(ACRES) = 25898.23

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 =====

MAINLINE Tc(MIN.) = 164.54  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.250  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/	SCS SOIL	AREA	Fp	Ap	SCS
LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
USER-DEFINED	-	4.70	0.60	1.000	-
USER-DEFINED	-	6.70	0.60	1.000	-
USER-DEFINED	-	12.00	0.60	1.000	-
USER-DEFINED	-	0.80	0.60	1.000	-
USER-DEFINED	-	20.20	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 SUBAREA AREA(ACRES) = 44.40 SUBAREA RUNOFF(CFS) = 0.00  
 EFFECTIVE AREA(ACRES) = 25942.63 AREA-AVERAGED Fm(INCH/HR) = 0.58  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.97  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 51344.4 PEAK FLOW RATE(CFS) = 976.69  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION (MIN.) = 164.54
RAINFALL INTENSITY (INCH/HR) = 0.25
AREA-AVERAGED Fm (INCH/HR) = 0.58
AREA-AVERAGED Fp (INCH/HR) = 0.60
AREA-AVERAGED Ap = 0.97
EFFECTIVE STREAM AREA (ACRES) = 25942.63
TOTAL STREAM AREA (ACRES) = 51344.45
PEAK FLOW RATE (CFS) AT CONFLUENCE = 976.69

\*\*\*\*\*

FLOW PROCESS FROM NODE 12730.00 TO NODE 12731.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH (FEET) = 561.54
ELEVATION DATA: UPSTREAM (FEET) = 613.29 DOWNSTREAM (FEET) = 551.75

Tc = K \* [(LENGTH\*\* 3.00) / (ELEVATION CHANGE)] \*\* 0.20
SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 13.823
\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 1.014
SUBAREA Tc AND LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)
NATURAL FAIR COVER
"CHAPARRAL, BROADLEAF" - 6.33 0.60 1.000 0 13.82
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF (CFS) = 2.36
TOTAL AREA (ACRES) = 6.33 PEAK FLOW RATE (CFS) = 2.36

\*\*\*\*\*

FLOW PROCESS FROM NODE 12731.00 TO NODE 12732.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM (FEET) = 551.75 DOWNSTREAM (FEET) = 494.40
CHANNEL LENGTH THRU SUBAREA (FEET) = 971.91 CHANNEL SLOPE = 0.0590
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00
\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.844
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 34.62 0.60 0.100 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 14.28
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 3.91
AVERAGE FLOW DEPTH (FEET) = 1.10 TRAVEL TIME (MIN.) = 4.14
Tc (MIN.) = 17.96

SUBAREA AREA (ACRES) = 34.62 SUBAREA RUNOFF (CFS) = 24.42
EFFECTIVE AREA (ACRES) = 40.95 AREA-AVERAGED Fm (INCH/HR) = 0.14
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.24
TOTAL AREA (ACRES) = 40.9 PEAK FLOW RATE (CFS) = 25.80

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 1.38 FLOW VELOCITY (FEET/SEC.) = 4.53
LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12732.00 = 1533.45 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12732.00 TO NODE 12733.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM (FEET) = 494.40 DOWNSTREAM (FEET) = 431.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 1156.41 CHANNEL SLOPE = 0.0548
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00
\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.736
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 59.52 0.60 0.100 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 43.91
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.04
AVERAGE FLOW DEPTH (FEET) = 1.70 TRAVEL TIME (MIN.) = 3.82
Tc (MIN.) = 21.79
SUBAREA AREA (ACRES) = 59.52 SUBAREA RUNOFF (CFS) = 36.20
EFFECTIVE AREA (ACRES) = 100.47 AREA-AVERAGED Fm (INCH/HR) = 0.09
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.16
TOTAL AREA (ACRES) = 100.5 PEAK FLOW RATE (CFS) = 58.03

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 1.89 FLOW VELOCITY (FEET/SEC.) = 5.39
LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12733.00 = 2689.86 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12733.00 TO NODE 12734.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM (FEET) = 431.00 DOWNSTREAM (FEET) = 367.10
CHANNEL LENGTH THRU SUBAREA (FEET) = 1654.48 CHANNEL SLOPE = 0.0386
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00
\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.633
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 64.05 0.60 0.100 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 74.58
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.03

AVERAGE FLOW DEPTH(FEET) = 2.22 TRAVEL TIME(MIN.) = 5.48  
 Tc(MIN.) = 27.27  
 SUBAREA AREA(ACRES) = 64.05 SUBAREA RUNOFF(CFS) = 33.05  
 EFFECTIVE AREA(ACRES) = 164.52 AREA-AVERAGED Fm(INCH/HR) = 0.08  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.13  
 TOTAL AREA(ACRES) = 164.5 PEAK FLOW RATE(CFS) = 81.83

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 2.30 FLOW VELOCITY(FEET/SEC.) = 5.16  
 LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12734.00 = 4344.34 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12734.00 TO NODE 12740.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 367.11 DOWNSTREAM(FEET) = 252.10  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1880.98 CHANNEL SLOPE = 0.0611  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.574

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	26.02	0.60	0.100	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 87.88

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.22

AVERAGE FLOW DEPTH(FEET) = 2.17 TRAVEL TIME(MIN.) = 5.04

Tc(MIN.) = 32.31

SUBAREA AREA(ACRES) = 26.02 SUBAREA RUNOFF(CFS) = 12.10

EFFECTIVE AREA(ACRES) = 190.54 AREA-AVERAGED Fm(INCH/HR) = 0.08

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.13

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 190.5 PEAK FLOW RATE(CFS) = 85.66

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 2.15 FLOW VELOCITY(FEET/SEC.) = 6.20  
 LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12740.00 = 6225.32 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
 TIME OF CONCENTRATION(MIN.) = 32.31  
 RAINFALL INTENSITY(INCH/HR) = 0.57  
 AREA-AVERAGED Fm(INCH/HR) = 0.08  
 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.13

EFFECTIVE STREAM AREA(ACRES) = 190.54  
 TOTAL STREAM AREA(ACRES) = 190.54  
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 85.66

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	829.38	32.75	0.570	0.60( 0.50)	0.83	2699.1	413.00
1	828.37	34.40	0.557	0.60( 0.50)	0.84	2850.9	40510.00
1	821.66	39.04	0.519	0.60( 0.51)	0.85	3473.3	12710.00
1	805.32	42.26	0.498	0.60( 0.51)	0.86	3865.6	430.00
1	792.31	43.75	0.489	0.60( 0.52)	0.86	4039.2	40430.00
1	771.78	45.19	0.481	0.60( 0.52)	0.87	4198.9	400.00
1	674.87	53.37	0.435	0.60( 0.53)	0.89	5083.3	40200.00
1	659.14	84.79	0.354	0.60( 0.56)	0.94	9552.7	40100.00
1	694.75	97.56	0.331	0.60( 0.57)	0.95	11284.1	11831.00
1	782.81	121.61	0.289	0.60( 0.57)	0.96	14980.3	11530.00
1	866.51	141.64	0.271	0.60( 0.58)	0.97	19136.2	11000.00
1	976.69	164.54	0.250	0.60( 0.58)	0.97	25942.6	10850.00
1	899.59	179.78	0.236	0.60( 0.59)	0.98	29262.5	11220.00
1	840.60	190.89	0.233	0.60( 0.59)	0.98	31014.5	10910.00
1	688.10	230.51	0.220	0.60( 0.59)	0.98	37596.1	12410.00
1	650.30	263.25	0.210	0.60( 0.59)	0.98	43682.0	12261.00
1	638.18	275.94	0.206	0.60( 0.59)	0.98	45168.6	10410.00
1	626.13	288.03	0.202	0.60( 0.59)	0.98	46270.6	12101.10
1	613.06	297.68	0.199	0.60( 0.59)	0.98	47092.0	10700.00
1	598.91	315.35	0.194	0.60( 0.59)	0.98	48648.7	10200.00
1	585.07	328.64	0.190	0.60( 0.59)	0.98	49586.9	12010.00
1	545.58	357.45	0.181	0.60( 0.59)	0.98	50260.6	10210.00
1	488.26	406.19	0.175	0.60( 0.59)	0.98	50759.7	12000.00
1	451.99	475.42	0.167	0.60( 0.59)	0.98	51344.4	10100.00
2	85.66	32.31	0.574	0.60( 0.08)	0.13	190.5	12730.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	909.01	32.31	0.574	0.60( 0.47)	0.79	2853.0	12730.00
2	914.49	32.75	0.570	0.60( 0.47)	0.79	2889.6	413.00
3	911.47	34.40	0.557	0.60( 0.47)	0.79	3041.5	40510.00
4	899.08	39.04	0.519	0.60( 0.49)	0.81	3663.9	12710.00
5	879.62	42.26	0.498	0.60( 0.49)	0.82	4056.2	430.00
6	865.30	43.75	0.489	0.60( 0.50)	0.83	4229.7	40430.00
7	843.53	45.19	0.481	0.60( 0.50)	0.83	4389.4	400.00
8	739.75	53.37	0.435	0.60( 0.52)	0.86	5273.9	40200.00
9	712.02	84.79	0.354	0.60( 0.55)	0.92	9743.2	40100.00
10	744.16	97.56	0.331	0.60( 0.56)	0.93	11474.7	11831.00
11	825.86	121.61	0.289	0.60( 0.57)	0.95	15170.9	11530.00
12	906.88	141.64	0.271	0.60( 0.57)	0.96	19326.8	11000.00
13	1013.98	164.54	0.250	0.60( 0.58)	0.97	26133.2	10850.00
14	934.84	179.78	0.236	0.60( 0.58)	0.97	29453.0	11220.00
15	875.31	190.89	0.233	0.60( 0.58)	0.97	31205.1	10910.00
16	720.97	230.51	0.220	0.60( 0.58)	0.97	37786.7	12410.00
17	681.65	263.25	0.210	0.60( 0.59)	0.98	43872.6	12261.00
18	668.94	275.94	0.206	0.60( 0.59)	0.98	45359.2	10410.00
19	656.33	288.03	0.202	0.60( 0.59)	0.98	46461.1	12101.10

20	642.81	297.68	0.199	0.60	( 0.59)	0.98	47282.5	10700.00
21	627.84	315.35	0.194	0.60	( 0.59)	0.98	48839.2	10200.00
22	613.38	328.64	0.190	0.60	( 0.59)	0.98	49777.4	12010.00
23	572.55	357.45	0.181	0.60	( 0.59)	0.98	50451.2	10210.00
24	514.32	406.19	0.175	0.60	( 0.59)	0.98	50950.2	12000.00
25	476.85	475.42	0.167	0.60	( 0.59)	0.98	51535.0	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 1013.98 Tc(MIN.) = 164.54  
 EFFECTIVE AREA(ACRES) = 26133.17 AREA-AVERAGED Fm(INCH/HR) = 0.58  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.97  
 TOTAL AREA(ACRES) = 51535.0  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12740.00 = 110575.24 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12740.00 TO NODE 12741.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 252.10 DOWNSTREAM(FEET) = 247.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 401.47 CHANNEL SLOPE = 0.0127  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
 CHANNEL FLOW THRU SUBAREA(CFS) = 1013.98  
 FLOW VELOCITY(FEET/SEC.) = 10.73 FLOW DEPTH(FEET) = 5.61  
 TRAVEL TIME(MIN.) = 0.62 Tc(MIN.) = 165.16  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12741.00 = 110976.71 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	909.01	32.95	0.569	0.60 ( 0.47)	0.79	2853.0	12730.00
2	914.49	33.39	0.565	0.60 ( 0.47)	0.79	2889.6	413.00
3	911.47	35.04	0.552	0.60 ( 0.47)	0.79	3041.5	40510.00
4	899.08	39.68	0.514	0.60 ( 0.49)	0.81	3663.9	12710.00
5	879.62	42.90	0.494	0.60 ( 0.49)	0.82	4056.2	430.00
6	865.30	44.40	0.485	0.60 ( 0.50)	0.83	4229.7	40430.00
7	843.53	45.85	0.477	0.60 ( 0.50)	0.83	4389.4	400.00
8	739.75	54.04	0.431	0.60 ( 0.52)	0.86	5273.9	40200.00
9	712.02	85.47	0.353	0.60 ( 0.55)	0.92	9743.2	40100.00
10	744.16	98.24	0.330	0.60 ( 0.56)	0.93	11474.7	11831.00
11	825.86	122.27	0.288	0.60 ( 0.57)	0.95	15170.9	11530.00
12	906.88	142.28	0.270	0.60 ( 0.57)	0.96	19326.8	11000.00
13	1013.98	165.16	0.249	0.60 ( 0.58)	0.97	26133.2	10850.00
14	934.84	180.42	0.236	0.60 ( 0.58)	0.97	29453.0	11220.00
15	875.31	191.54	0.232	0.60 ( 0.58)	0.97	31205.1	10910.00
16	720.97	231.19	0.220	0.60 ( 0.58)	0.97	37786.7	12410.00
17	681.65	263.94	0.210	0.60 ( 0.59)	0.98	43872.6	12261.00
18	668.94	276.63	0.206	0.60 ( 0.59)	0.98	45359.2	10410.00
19	656.33	288.73	0.202	0.60 ( 0.59)	0.98	46461.1	12101.10
20	642.81	298.38	0.199	0.60 ( 0.59)	0.98	47282.5	10700.00
21	627.84	316.05	0.194	0.60 ( 0.59)	0.98	48839.2	10200.00
22	613.38	329.34	0.190	0.60 ( 0.59)	0.98	49777.4	12010.00
23	572.55	358.17	0.181	0.60 ( 0.59)	0.98	50451.2	10210.00
24	514.32	406.93	0.175	0.60 ( 0.59)	0.98	50950.2	12000.00
25	476.85	476.18	0.167	0.60 ( 0.59)	0.98	51535.0	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 1013.98 Tc(MIN.) = 165.16  
 AREA-AVERAGED Fm(INCH/HR) = 0.58 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.97 EFFECTIVE AREA(ACRES) = 26133.17

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 165.16  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.249  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	2.10	0.60	0.100	-
USER-DEFINED	-	7.50	0.60	1.000	-
USER-DEFINED	-	0.90	0.60	1.000	-
USER-DEFINED	-	1.90	0.60	0.850	-
USER-DEFINED	-	0.40	0.60	0.900	-
USER-DEFINED	-	0.50	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.833  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 SUBAREA AREA(ACRES) = 13.30 SUBAREA RUNOFF(CFS) = 0.50  
 EFFECTIVE AREA(ACRES) = 26146.47 AREA-AVERAGED Fm(INCH/HR) = 0.58  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.97  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 51548.3 PEAK FLOW RATE(CFS) = 1013.98  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 165.16  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.249  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.90	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 SUBAREA AREA(ACRES) = 0.90 SUBAREA RUNOFF(CFS) = 0.00  
 EFFECTIVE AREA(ACRES) = 26147.37 AREA-AVERAGED Fm(INCH/HR) = 0.58  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.97  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 51549.2 PEAK FLOW RATE(CFS) = 1013.98  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 3C02EVRL.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	275.46	22.38	0.60 ( 0.27)	0.45	614.6	300.00
2	257.57	28.47	0.60 ( 0.28)	0.46	739.7	327.00
3	242.55	30.05	0.60 ( 0.28)	0.46	754.2	350.00
4	231.12	31.57	0.60 ( 0.28)	0.47	765.1	320.00
5	206.87	36.19	0.60 ( 0.28)	0.47	784.9	306.00
6	153.32	63.72	0.60 ( 0.30)	0.50	870.6	390.00
TOTAL AREA (ACRES) =						870.6

\*\*\*\*\*

FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	909.01	32.95	0.569	0.60 ( 0.47)	0.79	2867.2	12730.00
2	914.49	33.39	0.565	0.60 ( 0.47)	0.79	2903.8	413.00
3	911.47	35.04	0.552	0.60 ( 0.47)	0.79	3055.7	40510.00
4	899.08	39.68	0.514	0.60 ( 0.49)	0.81	3678.1	12710.00
5	879.62	42.90	0.494	0.60 ( 0.49)	0.82	4070.4	430.00
6	865.30	44.40	0.485	0.60 ( 0.50)	0.83	4243.9	40430.00
7	843.53	45.85	0.477	0.60 ( 0.50)	0.83	4403.6	400.00
8	739.75	54.04	0.431	0.60 ( 0.52)	0.86	5288.1	40200.00
9	712.02	85.47	0.353	0.60 ( 0.55)	0.92	9757.4	40100.00
10	744.16	98.24	0.330	0.60 ( 0.56)	0.93	11488.9	11831.00
11	825.86	122.27	0.288	0.60 ( 0.57)	0.95	15185.1	11530.00
12	906.88	142.28	0.270	0.60 ( 0.57)	0.96	19341.0	11000.00
13	1013.98	165.16	0.249	0.60 ( 0.58)	0.97	26147.4	10850.00
14	934.84	180.42	0.236	0.60 ( 0.58)	0.97	29467.2	11220.00
15	875.31	191.54	0.232	0.60 ( 0.58)	0.97	31219.3	10910.00
16	720.97	231.19	0.220	0.60 ( 0.58)	0.97	37800.9	12410.00
17	681.65	263.94	0.210	0.60 ( 0.59)	0.98	43886.8	12261.00
18	668.94	276.63	0.206	0.60 ( 0.59)	0.98	45373.4	10410.00
19	656.33	288.73	0.202	0.60 ( 0.59)	0.98	46475.3	12101.10
20	642.81	298.38	0.199	0.60 ( 0.59)	0.98	47296.7	10700.00
21	627.84	316.05	0.194	0.60 ( 0.59)	0.98	48853.4	10200.00
22	613.38	329.34	0.190	0.60 ( 0.59)	0.98	49791.6	12010.00
23	572.55	358.17	0.181	0.60 ( 0.59)	0.98	50465.4	10210.00
24	514.32	406.93	0.175	0.60 ( 0.59)	0.98	50964.4	12000.00
25	476.85	476.18	0.167	0.60 ( 0.59)	0.98	51549.2	10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12741.00 =							110976.71 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	275.46	22.38	0.723	0.60 ( 0.27)	0.45	614.6	300.00
2	257.57	28.47	0.616	0.60 ( 0.28)	0.46	739.7	327.00
3	242.55	30.05	0.593	0.60 ( 0.28)	0.46	754.2	350.00
4	231.12	31.57	0.580	0.60 ( 0.28)	0.47	765.1	320.00
5	206.87	36.19	0.542	0.60 ( 0.28)	0.47	784.9	306.00

6 153.32 63.72 0.392 0.60 ( 0.30) 0.50 870.6 390.00  
LONGEST FLOWPATH FROM NODE 390.00 TO NODE 12741.00 = 15238.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1184.47	22.38	0.723	0.60 ( 0.42)	0.71	2561.8	300.00
2	1166.58	28.47	0.616	0.60 ( 0.43)	0.71	3217.2	327.00
3	1106.25	30.05	0.593	0.60 ( 0.43)	0.71	3369.3	350.00
4	1119.40	31.57	0.580	0.60 ( 0.43)	0.72	3512.3	320.00
5	1132.88	32.95	0.569	0.60 ( 0.43)	0.72	3638.2	12730.00
6	1136.04	33.39	0.565	0.60 ( 0.43)	0.72	3676.7	413.00
7	1124.38	35.04	0.552	0.60 ( 0.44)	0.73	3835.6	40510.00
8	1115.28	36.19	0.542	0.60 ( 0.44)	0.73	3994.6	306.00
9	1099.15	39.68	0.514	0.60 ( 0.45)	0.75	4473.9	12710.00
10	1073.43	42.90	0.494	0.60 ( 0.46)	0.77	4876.2	430.00
11	1056.19	44.40	0.485	0.60 ( 0.46)	0.77	5054.4	40430.00
12	1031.61	45.85	0.477	0.60 ( 0.47)	0.78	5218.6	400.00
13	911.89	54.04	0.431	0.60 ( 0.49)	0.81	6128.5	40200.00
14	884.53	63.72	0.392	0.60 ( 0.50)	0.84	7534.9	390.00
15	850.04	85.47	0.353	0.60 ( 0.53)	0.89	10628.0	40100.00
16	873.09	98.24	0.330	0.60 ( 0.54)	0.90	12359.5	11831.00
17	938.40	122.27	0.288	0.60 ( 0.55)	0.92	16055.7	11530.00
18	1012.38	142.28	0.270	0.60 ( 0.56)	0.94	20211.6	11000.00
19	1111.44	165.16	0.249	0.60 ( 0.57)	0.95	27018.0	10850.00
20	1027.02	180.42	0.236	0.60 ( 0.57)	0.96	30337.8	11220.00
21	966.14	191.54	0.232	0.60 ( 0.58)	0.96	32089.9	10910.00
22	806.98	231.19	0.220	0.60 ( 0.58)	0.96	38671.5	12410.00
23	763.67	263.94	0.210	0.60 ( 0.58)	0.97	44757.4	12261.00
24	749.42	276.63	0.206	0.60 ( 0.58)	0.97	46244.0	10410.00
25	735.35	288.73	0.202	0.60 ( 0.58)	0.97	47345.9	12101.10
26	720.65	298.38	0.199	0.60 ( 0.58)	0.97	48167.3	10700.00
27	703.53	316.05	0.194	0.60 ( 0.58)	0.97	49724.0	10200.00
28	687.46	329.34	0.190	0.60 ( 0.58)	0.97	50662.2	12010.00
29	643.12	358.17	0.181	0.60 ( 0.58)	0.97	51336.0	10210.00
30	582.55	406.93	0.175	0.60 ( 0.58)	0.97	51835.0	12000.00
31	541.96	476.18	0.167	0.60 ( 0.58)	0.97	52419.8	10100.00
TOTAL AREA (ACRES) =							52419.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 1184.47 Tc (MIN.) = 22.377  
EFFECTIVE AREA (ACRES) = 2561.81 AREA-AVERAGED Fm (INCH/HR) = 0.42  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.97  
TOTAL AREA (ACRES) = 52419.8  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12741.00 = 110976.71 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 12741.00 TO NODE 12800.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

\*\*\*\*\*

ELEVATION DATA: UPSTREAM(FEET) = 247.00 DOWNSTREAM(FEET) = 240.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 819.00 CHANNEL SLOPE = 0.0085  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
 CHANNEL FLOW THRU SUBAREA(CFS) = 1184.47  
 FLOW VELOCITY(FEET/SEC.) = 9.60 FLOW DEPTH(FEET) = 6.41  
 TRAVEL TIME(MIN.) = 1.42 Tc(MIN.) = 23.80  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111795.71 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1184.47	23.80	0.693	0.60( 0.42)	0.71	2561.8	300.00
2	1166.58	29.90	0.595	0.60( 0.43)	0.71	3217.2	327.00
3	1106.25	31.50	0.581	0.60( 0.43)	0.71	3369.3	350.00
4	1119.40	33.01	0.568	0.60( 0.43)	0.72	3512.3	320.00
5	1132.88	34.39	0.557	0.60( 0.43)	0.72	3638.2	12730.00
6	1136.04	34.83	0.553	0.60( 0.43)	0.72	3676.7	413.00
7	1124.38	36.47	0.540	0.60( 0.44)	0.73	3835.6	40510.00
8	1115.28	37.63	0.530	0.60( 0.44)	0.73	3994.6	306.00
9	1099.15	41.13	0.504	0.60( 0.45)	0.75	4473.9	12710.00
10	1073.43	44.36	0.486	0.60( 0.46)	0.77	4876.2	430.00
11	1056.19	45.86	0.477	0.60( 0.46)	0.77	5054.4	40430.00
12	1031.61	47.32	0.469	0.60( 0.47)	0.78	5218.6	400.00
13	911.89	55.56	0.423	0.60( 0.49)	0.81	6128.5	40200.00
14	884.53	65.25	0.390	0.60( 0.50)	0.84	7534.9	390.00
15	850.04	87.01	0.350	0.60( 0.53)	0.89	10628.0	40100.00
16	873.09	99.77	0.327	0.60( 0.54)	0.90	12359.5	11831.00
17	938.40	123.77	0.287	0.60( 0.55)	0.92	16055.7	11530.00
18	1012.38	143.76	0.269	0.60( 0.56)	0.94	20211.6	11000.00
19	1111.44	166.61	0.248	0.60( 0.57)	0.95	27018.0	10850.00
20	1027.02	181.89	0.235	0.60( 0.57)	0.96	30337.8	11220.00
21	966.14	193.03	0.232	0.60( 0.58)	0.96	32089.9	10910.00
22	806.98	232.76	0.220	0.60( 0.58)	0.96	38671.5	12410.00
23	763.67	265.52	0.209	0.60( 0.58)	0.97	44757.4	12261.00
24	749.42	278.22	0.205	0.60( 0.58)	0.97	46244.0	10410.00
25	735.35	290.33	0.202	0.60( 0.58)	0.97	47345.9	12101.10
26	720.65	299.99	0.199	0.60( 0.58)	0.97	48167.3	10700.00
27	703.53	317.67	0.193	0.60( 0.58)	0.97	49724.0	10200.00
28	687.46	330.97	0.189	0.60( 0.58)	0.97	50662.2	12010.00
29	643.12	359.83	0.180	0.60( 0.58)	0.97	51336.0	10210.00
30	582.55	408.63	0.174	0.60( 0.58)	0.97	51835.0	12000.00
31	541.96	477.90	0.166	0.60( 0.58)	0.97	52419.8	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 1184.47 Tc(MIN.) = 23.80  
 AREA-AVERAGED Fm(INCH/HR) = 0.42 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.71 EFFECTIVE AREA(ACRES) = 2561.81

\*\*\*\*\*

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 23.80

\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.693

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

USER-DEFINED - 17.31 0.60 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 17.31 SUBAREA RUNOFF(CFS) = 1.45  
 EFFECTIVE AREA(ACRES) = 2579.12 AREA-AVERAGED Fm(INCH/HR) = 0.43  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.71  
 TOTAL AREA(ACRES) = 52437.1 PEAK FLOW RATE(CFS) = 1184.47  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 52437.1 TC(MIN.) = 23.80  
 EFFECTIVE AREA(ACRES) = 2579.12 AREA-AVERAGED Fm(INCH/HR) = 0.43  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.709  
 PEAK FLOW RATE(CFS) = 1184.47

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1184.47	23.80	0.693	0.60( 0.43)	0.71	2579.1	300.00
2	1166.58	29.90	0.595	0.60( 0.43)	0.71	3234.5	327.00
3	1106.25	31.50	0.581	0.60( 0.43)	0.72	3386.6	350.00
4	1119.40	33.01	0.568	0.60( 0.43)	0.72	3529.6	320.00
5	1132.88	34.39	0.557	0.60( 0.43)	0.72	3655.5	12730.00
6	1136.04	34.83	0.553	0.60( 0.43)	0.72	3694.0	413.00
7	1124.38	36.47	0.540	0.60( 0.44)	0.73	3852.9	40510.00
8	1115.28	37.63	0.530	0.60( 0.44)	0.73	4011.9	306.00
9	1099.15	41.13	0.504	0.60( 0.45)	0.75	4491.2	12710.00
10	1073.43	44.36	0.486	0.60( 0.46)	0.77	4893.5	430.00
11	1056.19	45.86	0.477	0.60( 0.46)	0.77	5071.7	40430.00
12	1031.61	47.32	0.469	0.60( 0.47)	0.78	5235.9	400.00
13	911.89	55.56	0.423	0.60( 0.49)	0.81	6145.9	40200.00
14	884.53	65.25	0.390	0.60( 0.50)	0.84	7552.2	390.00
15	850.04	87.01	0.350	0.60( 0.53)	0.89	10645.3	40100.00
16	873.09	99.77	0.327	0.60( 0.54)	0.90	12376.8	11831.00
17	938.40	123.77	0.287	0.60( 0.55)	0.92	16073.0	11530.00
18	1012.38	143.76	0.269	0.60( 0.56)	0.94	20228.9	11000.00
19	1111.44	166.61	0.248	0.60( 0.57)	0.95	27035.3	10850.00
20	1027.02	181.89	0.235	0.60( 0.57)	0.96	30355.1	11220.00
21	966.14	193.03	0.232	0.60( 0.58)	0.96	32107.2	10910.00
22	806.98	232.76	0.220	0.60( 0.58)	0.96	38688.8	12410.00
23	763.67	265.52	0.209	0.60( 0.58)	0.97	44774.7	12261.00
24	749.42	278.22	0.205	0.60( 0.58)	0.97	46261.3	10410.00
25	735.35	290.33	0.202	0.60( 0.58)	0.97	47363.2	12101.10
26	720.65	299.99	0.199	0.60( 0.58)	0.97	48184.6	10700.00
27	703.53	317.67	0.193	0.60( 0.58)	0.97	49741.3	10200.00
28	687.46	330.97	0.189	0.60( 0.58)	0.97	50679.6	12010.00
29	643.12	359.83	0.180	0.60( 0.58)	0.97	51353.3	10210.00
30	582.55	408.63	0.174	0.60( 0.58)	0.97	51852.3	12000.00
31	541.96	477.90	0.166	0.60( 0.58)	0.97	52437.1	10100.00

END OF RATIONAL METHOD ANALYSIS



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA 92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S28- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 2-YR RM EV APRIL 2019 ROKAMOTO \*  
\*\*\*\*\*

FILE NAME: RI02EV28.DAT  
TIME/DATE OF STUDY: 17:07 04/08/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 2.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 1.857
- 2) 10.00; 1.238
- 3) 15.00; 0.945
- 4) 20.00; 0.774
- 5) 25.00; 0.667
- 6) 30.00; 0.591
- 7) 40.00; 0.510
- 8) 50.00; 0.453
- 9) 60.00; 0.399
- 10) 90.00; 0.345
- 11) 120.00; 0.290
- 12) 180.00; 0.236
- 13) 360.00; 0.180
- 14) 1200.00; 0.083

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI02EV27.DNA  
MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1184.47	23.80	0.60 ( 0.43)	0.71	2579.1	300.00
2	1099.15	41.13	0.60 ( 0.45)	0.75	4491.2	12710.00
3	911.89	55.56	0.60 ( 0.49)	0.81	6145.9	40200.00
4	850.04	87.01	0.60 ( 0.53)	0.89	10645.3	40100.00
5	873.09	99.77	0.60 ( 0.54)	0.90	12376.8	11831.00
6	938.40	123.77	0.60 ( 0.55)	0.92	16073.0	11530.00
7	1012.38	143.76	0.60 ( 0.56)	0.94	20228.9	11000.00
8	1111.44	166.61	0.60 ( 0.57)	0.95	27035.3	10850.00
9	1027.02	181.89	0.60 ( 0.57)	0.96	30355.1	11220.00
10	966.14	193.03	0.60 ( 0.58)	0.96	32107.2	10910.00
11	806.98	232.76	0.60 ( 0.58)	0.96	38688.8	12410.00
12	763.67	265.52	0.60 ( 0.58)	0.97	44774.7	12261.00
13	749.42	278.22	0.60 ( 0.58)	0.97	46261.3	10410.00
14	735.35	290.33	0.60 ( 0.58)	0.97	47363.2	12101.10
15	720.65	299.99	0.60 ( 0.58)	0.97	48184.6	10700.00
16	703.53	317.67	0.60 ( 0.58)	0.97	49741.3	10200.00
17	687.46	330.97	0.60 ( 0.58)	0.97	50679.6	12010.00
18	643.12	359.83	0.60 ( 0.58)	0.97	51353.3	10210.00
19	582.55	408.63	0.60 ( 0.58)	0.97	51852.3	12000.00
20	541.96	477.90	0.60 ( 0.58)	0.97	52437.1	10100.00
TOTAL AREA (ACRES) =						52437.1

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 0610501T.DNA  
MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	71.25	40.57	0.60 ( 0.59)	0.98	1023.7	50120.00
2	56.82	44.15	0.60 ( 0.59)	0.98	1046.4	50150.00
3	24.29	51.88	0.60 ( 0.59)	0.98	1063.4	50100.00
TOTAL AREA (ACRES) =						1063.4

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 3 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM	Q	Tc	Fp (Fm)	Ap	Ae	HEADWATER
--------	---	----	---------	----	----	-----------



NUMBER	(CFS)	(MIN.)	(INCH/HR)	(ACRES)	NODE
1	71.25	40.57	0.60 ( 0.59)	0.98	1023.7
2	56.82	44.15	0.60 ( 0.59)	0.98	1046.4
3	24.29	51.88	0.60 ( 0.59)	0.98	1063.4
TOTAL AREA(ACRES) =			1063.4		

\*\*\*\*\*

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	71.25	40.57	0.507	0.60 ( 0.59)	0.98	1023.7	50120.00
2	56.82	44.15	0.486	0.60 ( 0.59)	0.98	1046.4	50150.00
3	24.29	51.88	0.443	0.60 ( 0.59)	0.98	1063.4	50100.00

LONGEST FLOWPATH FROM NODE 50150.00 TO NODE 12800.00 = 11349.00 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1184.47	23.80	0.693	0.60 ( 0.43)	0.71	2579.1	300.00
2	1099.15	41.13	0.504	0.60 ( 0.45)	0.75	4491.2	12710.00
3	911.89	55.56	0.423	0.60 ( 0.49)	0.81	6145.9	40200.00
4	850.04	87.01	0.350	0.60 ( 0.53)	0.89	10645.3	40100.00
5	873.09	99.77	0.327	0.60 ( 0.54)	0.90	12376.8	11831.00
6	938.40	123.77	0.287	0.60 ( 0.55)	0.92	16073.0	11530.00
7	1012.38	143.76	0.269	0.60 ( 0.56)	0.94	20228.9	11000.00
8	1111.44	166.61	0.248	0.60 ( 0.57)	0.95	27035.3	10850.00
9	1027.02	181.89	0.235	0.60 ( 0.57)	0.96	30355.1	11220.00
10	966.14	193.03	0.232	0.60 ( 0.58)	0.96	32107.2	10910.00
11	806.98	232.76	0.220	0.60 ( 0.58)	0.96	38688.8	12410.00
12	763.67	265.52	0.209	0.60 ( 0.58)	0.97	44774.7	12261.00
13	749.42	278.22	0.205	0.60 ( 0.58)	0.97	46261.3	10410.00
14	735.35	290.33	0.202	0.60 ( 0.58)	0.97	47363.2	12101.10
15	720.65	299.99	0.199	0.60 ( 0.58)	0.97	48184.6	10700.00
16	703.53	317.67	0.193	0.60 ( 0.58)	0.97	49741.3	10200.00
17	687.46	330.97	0.189	0.60 ( 0.58)	0.97	50679.6	12010.00
18	643.12	359.83	0.180	0.60 ( 0.58)	0.97	51353.3	10210.00
19	582.55	408.63	0.174	0.60 ( 0.58)	0.97	51852.3	12000.00
20	541.96	477.90	0.166	0.60 ( 0.58)	0.97	52437.1	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111795.71 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1241.60	23.80	0.693	0.60 ( 0.46)	0.76	3179.6	300.00
2	1173.15	40.57	0.507	0.60 ( 0.48)	0.79	5453.4	50120.00
3	1168.16	41.13	0.504	0.60 ( 0.48)	0.79	5518.4	12710.00
4	1116.79	44.15	0.486	0.60 ( 0.48)	0.80	5883.8	50150.00
5	983.92	51.88	0.443	0.60 ( 0.49)	0.82	6787.4	50100.00
6	935.10	55.56	0.423	0.60 ( 0.50)	0.84	7209.2	40200.00
7	869.26	87.01	0.350	0.60 ( 0.54)	0.90	11708.7	40100.00
8	891.04	99.77	0.327	0.60 ( 0.55)	0.91	13440.2	11831.00
9	954.13	123.77	0.287	0.60 ( 0.56)	0.93	17136.4	11530.00
10	1027.12	143.76	0.269	0.60 ( 0.56)	0.94	21292.3	11000.00

11	1125.04	166.61	0.248	0.60 ( 0.57)	0.95	28098.7	10850.00
12	1039.93	181.89	0.235	0.60 ( 0.57)	0.96	31418.5	11220.00
13	978.86	193.03	0.232	0.60 ( 0.58)	0.96	33170.6	10910.00
14	819.03	232.76	0.220	0.60 ( 0.58)	0.96	39752.2	12410.00
15	775.16	265.52	0.209	0.60 ( 0.58)	0.97	45838.1	12261.00
16	760.69	278.22	0.205	0.60 ( 0.58)	0.97	47324.7	10410.00
17	746.41	290.33	0.202	0.60 ( 0.58)	0.97	48426.6	12101.10
18	731.55	299.99	0.199	0.60 ( 0.58)	0.97	49248.0	10700.00
19	714.13	317.67	0.193	0.60 ( 0.58)	0.97	50804.7	10200.00
20	697.83	330.97	0.189	0.60 ( 0.58)	0.97	51742.9	12010.00
21	653.00	359.83	0.180	0.60 ( 0.58)	0.97	52416.7	10210.00
22	592.12	408.63	0.174	0.60 ( 0.58)	0.97	52915.7	12000.00
23	551.09	477.90	0.166	0.60 ( 0.58)	0.97	53500.5	10100.00

TOTAL AREA(ACRES) = 53500.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 1241.60 Tc(MIN.) = 23.799  
EFFECTIVE AREA(ACRES) = 3179.58 AREA-AVERAGED Fm(INCH/HR) = 0.46  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.80  
TOTAL AREA(ACRES) = 53500.5  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111795.71 FEET.

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 53500.5 TC(MIN.) = 23.80  
EFFECTIVE AREA(ACRES) = 3179.58 AREA-AVERAGED Fm(INCH/HR) = 0.46  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.760  
PEAK FLOW RATE(CFS) = 1241.60

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1241.60	23.80	0.693	0.60 ( 0.46)	0.76	3179.6	300.00
2	1173.15	40.57	0.507	0.60 ( 0.48)	0.79	5453.4	50120.00
3	1168.16	41.13	0.504	0.60 ( 0.48)	0.79	5518.4	12710.00
4	1116.79	44.15	0.486	0.60 ( 0.48)	0.80	5883.8	50150.00
5	983.92	51.88	0.443	0.60 ( 0.49)	0.82	6787.4	50100.00
6	935.10	55.56	0.423	0.60 ( 0.50)	0.84	7209.2	40200.00
7	869.26	87.01	0.350	0.60 ( 0.54)	0.90	11708.7	40100.00
8	891.04	99.77	0.327	0.60 ( 0.55)	0.91	13440.2	11831.00
9	954.13	123.77	0.287	0.60 ( 0.56)	0.93	17136.4	11530.00
10	1027.12	143.76	0.269	0.60 ( 0.56)	0.94	21292.3	11000.00
11	1125.04	166.61	0.248	0.60 ( 0.57)	0.95	28098.7	10850.00
12	1039.93	181.89	0.235	0.60 ( 0.57)	0.96	31418.5	11220.00
13	978.86	193.03	0.232	0.60 ( 0.58)	0.96	33170.6	10910.00
14	819.03	232.76	0.220	0.60 ( 0.58)	0.96	39752.2	12410.00
15	775.16	265.52	0.209	0.60 ( 0.58)	0.97	45838.1	12261.00
16	760.69	278.22	0.205	0.60 ( 0.58)	0.97	47324.7	10410.00
17	746.41	290.33	0.202	0.60 ( 0.58)	0.97	48426.6	12101.10
18	731.55	299.99	0.199	0.60 ( 0.58)	0.97	49248.0	10700.00
19	714.13	317.67	0.193	0.60 ( 0.58)	0.97	50804.7	10200.00
20	697.83	330.97	0.189	0.60 ( 0.58)	0.97	51742.9	12010.00
21	653.00	359.83	0.180	0.60 ( 0.58)	0.97	52416.7	10210.00
22	592.12	408.63	0.174	0.60 ( 0.58)	0.97	52915.7	12000.00
23	551.09	477.90	0.166	0.60 ( 0.58)	0.97	53500.5	10100.00

END OF RATIONAL METHOD ANALYSIS



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA 92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S29- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 2-YR RM EV APRIL 2019 ROKAMOTO \*  
\*\*\*\*\*

FILE NAME: RI02EV29.DAT  
TIME/DATE OF STUDY: 17:08 04/08/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 2.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 1.853
- 2) 10.00; 1.236
- 3) 15.00; 0.943
- 4) 20.00; 0.773
- 5) 25.00; 0.666
- 6) 30.00; 0.591
- 7) 40.00; 0.509
- 8) 50.00; 0.452
- 9) 60.00; 0.398
- 10) 90.00; 0.340
- 11) 120.00; 0.286
- 12) 180.00; 0.230
- 13) 360.00; 0.176
- 14) 1200.00; 0.082

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI02EV28.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1241.60	23.80	0.60 ( 0.46)	0.76	3179.6	300.00
2	1173.15	40.57	0.60 ( 0.48)	0.79	5453.4	50120.00
3	983.92	51.88	0.60 ( 0.49)	0.82	6787.4	50100.00
4	869.26	87.01	0.60 ( 0.54)	0.90	11708.7	40100.00
5	891.04	99.77	0.60 ( 0.55)	0.91	13440.2	11831.00
6	954.13	123.77	0.60 ( 0.56)	0.93	17136.4	11530.00
7	1027.12	143.76	0.60 ( 0.56)	0.94	21292.3	11000.00
8	1125.04	166.61	0.60 ( 0.57)	0.95	28098.7	10850.00
9	1039.93	181.89	0.60 ( 0.57)	0.96	31418.5	11220.00
10	978.86	193.03	0.60 ( 0.58)	0.96	33170.6	10910.00
11	819.03	232.76	0.60 ( 0.58)	0.96	39752.2	12410.00
12	775.16	265.52	0.60 ( 0.58)	0.97	45838.1	12261.00
13	760.69	278.22	0.60 ( 0.58)	0.97	47324.7	10410.00
14	746.41	290.33	0.60 ( 0.58)	0.97	48426.6	12101.10
15	731.55	299.99	0.60 ( 0.58)	0.97	49248.0	10700.00
16	714.13	317.67	0.60 ( 0.58)	0.97	50804.7	10200.00
17	697.83	330.97	0.60 ( 0.58)	0.97	51742.9	12010.00
18	653.00	359.83	0.60 ( 0.58)	0.97	52416.7	10210.00
19	592.12	408.63	0.60 ( 0.58)	0.97	52915.7	12000.00
20	551.09	477.90	0.60 ( 0.58)	0.97	53500.5	10100.00
TOTAL AREA(ACRES) =						53500.5

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1241.60	23.80	0.60 ( 0.46)	0.76	3179.6	300.00
2	1173.15	40.57	0.60 ( 0.48)	0.79	5453.4	50120.00
3	983.92	51.88	0.60 ( 0.49)	0.82	6787.4	50100.00
4	869.26	87.01	0.60 ( 0.54)	0.90	11708.7	40100.00
5	891.04	99.77	0.60 ( 0.55)	0.91	13440.2	11831.00
6	954.13	123.77	0.60 ( 0.56)	0.93	17136.4	11530.00
7	1027.12	143.76	0.60 ( 0.56)	0.94	21292.3	11000.00
8	1125.04	166.61	0.60 ( 0.57)	0.95	28098.7	10850.00
9	1039.93	181.89	0.60 ( 0.57)	0.96	31418.5	11220.00
10	978.86	193.03	0.60 ( 0.58)	0.96	33170.6	10910.00
11	819.03	232.76	0.60 ( 0.58)	0.96	39752.2	12410.00
12	775.16	265.52	0.60 ( 0.58)	0.97	45838.1	12261.00
13	760.69	278.22	0.60 ( 0.58)	0.97	47324.7	10410.00

```

14 746.41 290.33 0.60( 0.58) 0.97 48426.6 12101.10
15 731.55 299.99 0.60( 0.58) 0.97 49248.0 10700.00
16 714.13 317.67 0.60( 0.58) 0.97 50804.7 10200.00
17 697.83 330.97 0.60( 0.58) 0.97 51742.9 12010.00
18 653.00 359.83 0.60( 0.58) 0.97 52416.7 10210.00
19 592.12 408.63 0.60( 0.58) 0.97 52915.7 12000.00
20 551.09 477.90 0.60( 0.58) 0.97 53500.5 10100.00
TOTAL AREA(ACRES) = 53500.5

```

```

*****
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 12
-----

```

```
>>>>CLEAR MEMORY BANK # 1 <<<<<
```

```

*****
FLOW PROCESS FROM NODE 12800.00 TO NODE 12901.00 IS CODE = 51
-----

```

```
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<
```

```

ELEVATION DATA: UPSTREAM(FEET) = 240.00 DOWNSTREAM(FEET) = 216.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 3120.28 CHANNEL SLOPE = 0.0077
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
CHANNEL FLOW THRU SUBAREA(CFS) = 1241.60
FLOW VELOCITY(FEET/SEC.) = 9.34 FLOW DEPTH(FEET) = 6.66
TRAVEL TIME(MIN.) = 5.57 Tc(MIN.) = 29.36
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12901.00 = 114915.99 FEET.

```

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1241.60	29.36	0.601	0.60( 0.46)	0.76	3179.6	300.00
2	1173.15	46.21	0.474	0.60( 0.48)	0.79	5453.4	50120.00
3	983.92	57.78	0.410	0.60( 0.49)	0.82	6787.4	50100.00
4	869.26	93.10	0.334	0.60( 0.54)	0.90	11708.7	40100.00
5	891.04	105.82	0.312	0.60( 0.55)	0.91	13440.2	11831.00
6	954.13	129.72	0.277	0.60( 0.56)	0.93	17136.4	11530.00
7	1027.12	149.59	0.258	0.60( 0.56)	0.94	21292.3	11000.00
8	1125.04	172.31	0.237	0.60( 0.57)	0.95	28098.7	10850.00
9	1039.93	187.71	0.228	0.60( 0.57)	0.96	31418.5	11220.00
10	978.86	198.93	0.224	0.60( 0.58)	0.96	33170.6	10910.00
11	819.03	238.93	0.212	0.60( 0.58)	0.96	39752.2	12410.00
12	775.16	271.78	0.202	0.60( 0.58)	0.97	45838.1	12261.00
13	760.69	284.51	0.199	0.60( 0.58)	0.97	47324.7	10410.00
14	746.41	296.65	0.195	0.60( 0.58)	0.97	48426.6	12101.10
15	731.55	306.34	0.192	0.60( 0.58)	0.97	49248.0	10700.00
16	714.13	324.06	0.187	0.60( 0.58)	0.97	50804.7	10200.00
17	697.83	337.40	0.183	0.60( 0.58)	0.97	51742.9	12010.00
18	653.00	366.36	0.175	0.60( 0.58)	0.97	52416.7	10210.00
19	592.12	415.32	0.170	0.60( 0.58)	0.97	52915.7	12000.00
20	551.09	484.72	0.162	0.60( 0.58)	0.97	53500.5	10100.00

NEW PEAK FLOW DATA ARE:

```

PEAK FLOW RATE(CFS) = 1241.60 Tc(MIN.) = 29.36
AREA-AVERAGED Fm(INCH/HR) = 0.46 AREA-AVERAGED Fp(INCH/HR) = 0.60
AREA-AVERAGED Ap = 0.76 EFFECTIVE AREA(ACRES) = 3179.58

```

```

*****
FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81
-----

```

```
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
```

```

MAINLINE Tc(MIN.) = 29.36
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.601
SUBAREA LOSS RATE DATA(AMC II):

```

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	2.60	0.60	0.100	-
USER-DEFINED	-	3.20	0.60	0.100	-
USER-DEFINED	-	1.50	0.60	0.850	-
USER-DEFINED	-	5.60	0.60	0.100	-
USER-DEFINED	-	6.50	0.60	0.850	-

```

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.409
SUBAREA AREA(ACRES) = 19.40 SUBAREA RUNOFF(CFS) = 6.20
EFFECTIVE AREA(ACRES) = 3198.98 AREA-AVERAGED Fm(INCH/HR) = 0.45
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.76
TOTAL AREA(ACRES) = 53519.9 PEAK FLOW RATE(CFS) = 1241.60
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81
-----

```

```
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
```

```

MAINLINE Tc(MIN.) = 29.36
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.601
SUBAREA LOSS RATE DATA(AMC II):

```

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.50	0.60	0.100	-
USER-DEFINED	-	4.10	0.60	0.850	-
USER-DEFINED	-	0.10	0.60	0.850	-
USER-DEFINED	-	1.60	0.60	0.900	-
USER-DEFINED	-	0.60	0.60	0.900	-
USER-DEFINED	-	1.00	0.60	0.900	-

```

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.823
SUBAREA AREA(ACRES) = 7.90 SUBAREA RUNOFF(CFS) = 0.76
EFFECTIVE AREA(ACRES) = 3206.88 AREA-AVERAGED Fm(INCH/HR) = 0.45
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.76
TOTAL AREA(ACRES) = 53527.8 PEAK FLOW RATE(CFS) = 1241.60
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81
-----

```

```
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
```

```

MAINLINE Tc(MIN.) = 29.36
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.601
SUBAREA LOSS RATE DATA(AMC II):

```

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	3.60	0.60	0.900	-

```

USER-DEFINED      -      0.30      0.60      1.000      -
USER-DEFINED      -      12.00      0.60      1.000      -
USER-DEFINED      -      36.10      0.60      0.850      -
USER-DEFINED      -      15.90      0.60      1.000      -
USER-DEFINED      -      1.50      0.60      1.000      -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.917
SUBAREA AREA (ACRES) = 69.40      SUBAREA RUNOFF (CFS) = 3.16
EFFECTIVE AREA (ACRES) = 3276.28      AREA-AVERAGED Fm (INCH/HR) = 0.46
AREA-AVERAGED Fp (INCH/HR) = 0.60      AREA-AVERAGED Ap = 0.76
TOTAL AREA (ACRES) = 53597.2      PEAK FLOW RATE (CFS) = 1241.60
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
-----

```

```

MAINLINE Tc (MIN.) = 29.36
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.601
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/      SCS SOIL      AREA      Fp      Ap      SCS
LAND USE      GROUP      (ACRES)      (INCH/HR)      (DECIMAL)      CN
USER-DEFINED      -      4.20      0.60      1.000      -
USER-DEFINED      -      0.40      0.60      1.000      -
USER-DEFINED      -      1.00      0.60      1.000      -
USER-DEFINED      -      4.10      0.60      0.500      -
USER-DEFINED      -      3.70      0.60      0.500      -
USER-DEFINED      -      0.40      0.60      0.500      -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.703
SUBAREA AREA (ACRES) = 13.80      SUBAREA RUNOFF (CFS) = 2.22
EFFECTIVE AREA (ACRES) = 3290.08      AREA-AVERAGED Fm (INCH/HR) = 0.46
AREA-AVERAGED Fp (INCH/HR) = 0.60      AREA-AVERAGED Ap = 0.76
TOTAL AREA (ACRES) = 53611.0      PEAK FLOW RATE (CFS) = 1241.60
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
-----

```

```

MAINLINE Tc (MIN.) = 29.36
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.601
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/      SCS SOIL      AREA      Fp      Ap      SCS
LAND USE      GROUP      (ACRES)      (INCH/HR)      (DECIMAL)      CN
USER-DEFINED      -      6.70      0.60      1.000      -
USER-DEFINED      -      1.20      0.60      1.000      -
USER-DEFINED      -      2.90      0.60      1.000      -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 10.80      SUBAREA RUNOFF (CFS) = 0.01
EFFECTIVE AREA (ACRES) = 3300.88      AREA-AVERAGED Fm (INCH/HR) = 0.46
AREA-AVERAGED Fp (INCH/HR) = 0.60      AREA-AVERAGED Ap = 0.76
TOTAL AREA (ACRES) = 53621.8      PEAK FLOW RATE (CFS) = 1241.60
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 12901.00 TO NODE 12902.00 IS CODE = 51
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
-----

```

```

ELEVATION DATA: UPSTREAM (FEET) = 216.00      DOWNSTREAM (FEET) = 215.00
CHANNEL LENGTH THRU SUBAREA (FEET) = 122.04      CHANNEL SLOPE = 0.0082
CHANNEL BASE (FEET) = 0.00      "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030      MAXIMUM DEPTH (FEET) = 20.00
CHANNEL FLOW THRU SUBAREA (CFS) = 1241.60
FLOW VELOCITY (FEET/SEC.) = 9.58      FLOW DEPTH (FEET) = 6.57
TRAVEL TIME (MIN.) = 0.21      Tc (MIN.) = 29.58
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115038.03 FEET.

```

```

** PEAK FLOW RATE TABLE **

```

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1241.60	29.58	0.597	0.60 ( 0.46)	0.76	3300.9	300.00
2	1173.15	46.43	0.472	0.60 ( 0.48)	0.79	5574.7	50120.00
3	983.92	58.00	0.409	0.60 ( 0.49)	0.82	6908.7	50100.00
4	869.26	93.33	0.334	0.60 ( 0.54)	0.90	11830.0	40100.00
5	891.04	106.05	0.311	0.60 ( 0.54)	0.91	13561.5	11831.00
6	954.13	129.94	0.277	0.60 ( 0.56)	0.93	17257.7	11530.00
7	1027.12	149.81	0.258	0.60 ( 0.56)	0.94	21413.6	11000.00
8	1125.04	172.52	0.237	0.60 ( 0.57)	0.95	28220.0	10850.00
9	1039.93	187.93	0.228	0.60 ( 0.57)	0.96	31539.8	11220.00
10	978.86	199.16	0.224	0.60 ( 0.58)	0.96	33291.9	10910.00
11	819.03	239.17	0.212	0.60 ( 0.58)	0.96	39873.5	12410.00
12	775.16	272.02	0.202	0.60 ( 0.58)	0.97	45959.4	12261.00
13	760.69	284.75	0.199	0.60 ( 0.58)	0.97	47446.0	10410.00
14	746.41	296.89	0.195	0.60 ( 0.58)	0.97	48547.9	12101.10
15	731.55	306.58	0.192	0.60 ( 0.58)	0.97	49369.3	10700.00
16	714.13	324.30	0.187	0.60 ( 0.58)	0.97	50926.0	10200.00
17	697.83	337.64	0.183	0.60 ( 0.58)	0.97	51864.2	12010.00
18	653.00	366.61	0.175	0.60 ( 0.58)	0.97	52537.9	10210.00
19	592.12	415.58	0.170	0.60 ( 0.58)	0.97	53037.0	12000.00
20	551.09	484.99	0.162	0.60 ( 0.58)	0.97	53621.8	10100.00

```

NEW PEAK FLOW DATA ARE:

```

```

PEAK FLOW RATE (CFS) = 1241.60      Tc (MIN.) = 29.58
AREA-AVERAGED Fm (INCH/HR) = 0.46      AREA-AVERAGED Fp (INCH/HR) = 0.60
AREA-AVERAGED Ap = 0.76      EFFECTIVE AREA (ACRES) = 3300.88

```

```

*****
FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 15.1
-----

```

```

>>>>DEFINE MEMORY BANK # 3 <<<<
-----

```

```

PEAK FLOWRATE TABLE FILE NAME: E502XX02.DNA

```

```

MEMORY BANK # 3 DEFINED AS FOLLOWS:

```

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	10.08	12.60	0.60 ( 0.55)	0.91	28.7	50200.00
TOTAL AREA (ACRES) =		28.7				

```

*****
FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 11
-----

```

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1241.60	29.58	0.597	0.60 ( 0.46)	0.76	3300.9	300.00
2	1173.15	46.43	0.472	0.60 ( 0.48)	0.79	5574.7	50120.00
3	983.92	58.00	0.409	0.60 ( 0.49)	0.82	6908.7	50100.00
4	869.26	93.33	0.334	0.60 ( 0.54)	0.90	11830.0	40100.00
5	891.04	106.05	0.311	0.60 ( 0.54)	0.91	13561.5	11831.00
6	954.13	129.94	0.277	0.60 ( 0.56)	0.93	17257.7	11530.00
7	1027.12	149.81	0.258	0.60 ( 0.56)	0.94	21413.6	11000.00
8	1125.04	172.52	0.237	0.60 ( 0.57)	0.95	28220.0	10850.00
9	1039.93	187.93	0.228	0.60 ( 0.57)	0.96	31539.8	11220.00
10	978.86	199.16	0.224	0.60 ( 0.58)	0.96	33291.9	10910.00
11	819.03	239.17	0.212	0.60 ( 0.58)	0.96	39873.5	12410.00
12	775.16	272.02	0.202	0.60 ( 0.58)	0.97	45959.4	12261.00
13	760.69	284.75	0.199	0.60 ( 0.58)	0.97	47446.0	10410.00
14	746.41	296.89	0.195	0.60 ( 0.58)	0.97	48547.9	12101.10
15	731.55	306.58	0.192	0.60 ( 0.58)	0.97	49369.3	10700.00
16	714.13	324.30	0.187	0.60 ( 0.58)	0.97	50926.0	10200.00
17	697.83	337.64	0.183	0.60 ( 0.58)	0.97	51864.2	12010.00
18	653.00	366.61	0.175	0.60 ( 0.58)	0.97	52537.9	10210.00
19	592.12	415.58	0.170	0.60 ( 0.58)	0.97	53037.0	12000.00
20	551.09	484.99	0.162	0.60 ( 0.58)	0.97	53621.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115038.03 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	10.08	12.60	1.084	0.60 ( 0.55)	0.91	28.7	50200.00

LONGEST FLOWPATH FROM NODE 50200.00 TO NODE 12902.00 = 1426.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1251.68	12.60	1.084	0.60 ( 0.46)	0.77	1434.8	50200.00
2	1242.61	29.58	0.597	0.60 ( 0.46)	0.76	3329.6	300.00
3	1173.94	46.43	0.472	0.60 ( 0.48)	0.79	5603.4	50120.00
4	984.61	58.00	0.409	0.60 ( 0.49)	0.83	6937.4	50100.00
5	869.82	93.33	0.334	0.60 ( 0.54)	0.90	11858.7	40100.00
6	891.56	106.05	0.311	0.60 ( 0.54)	0.91	13590.2	11831.00
7	954.59	129.94	0.277	0.60 ( 0.56)	0.93	17286.4	11530.00
8	1027.55	149.81	0.258	0.60 ( 0.56)	0.94	21442.3	11000.00
9	1125.44	172.52	0.237	0.60 ( 0.57)	0.95	28248.7	10850.00
10	1040.32	187.93	0.228	0.60 ( 0.57)	0.96	31568.5	11220.00
11	979.24	199.16	0.224	0.60 ( 0.58)	0.96	33320.6	10910.00
12	819.39	239.17	0.212	0.60 ( 0.58)	0.96	39902.2	12410.00
13	775.50	272.02	0.202	0.60 ( 0.58)	0.97	45988.1	12261.00
14	761.03	284.75	0.199	0.60 ( 0.58)	0.97	47474.7	10410.00
15	746.74	296.89	0.195	0.60 ( 0.58)	0.97	48576.6	12101.10
16	731.87	306.58	0.192	0.60 ( 0.58)	0.97	49398.0	10700.00
17	714.45	324.30	0.187	0.60 ( 0.58)	0.97	50954.7	10200.00
18	698.14	337.64	0.183	0.60 ( 0.58)	0.97	51892.9	12010.00
19	653.30	366.61	0.175	0.60 ( 0.58)	0.97	52566.6	10210.00
20	592.41	415.58	0.170	0.60 ( 0.58)	0.97	53065.7	12000.00
21	551.36	484.99	0.162	0.60 ( 0.58)	0.97	53650.5	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115038.03 FEET.

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 1251.68 Tc (MIN.) = 12.599  
EFFECTIVE AREA (ACRES) = 1434.81 AREA-AVERAGED Fm (INCH/HR) = 0.46  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.97  
TOTAL AREA (ACRES) = 53650.5  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115038.03 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: E503XX02.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	10.17	40.85	0.60 ( 0.59)	0.99	366.4	50300.00

TOTAL AREA (ACRES) = 366.4

\*\*\*\*\*

FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1251.68	12.60	1.084	0.60 ( 0.46)	0.77	1434.8	50200.00
2	1242.61	29.58	0.597	0.60 ( 0.46)	0.76	3329.6	300.00
3	1173.94	46.43	0.472	0.60 ( 0.48)	0.79	5603.4	50120.00
4	984.61	58.00	0.409	0.60 ( 0.49)	0.83	6937.4	50100.00
5	869.82	93.33	0.334	0.60 ( 0.54)	0.90	11858.7	40100.00
6	891.56	106.05	0.311	0.60 ( 0.54)	0.91	13590.2	11831.00
7	954.59	129.94	0.277	0.60 ( 0.56)	0.93	17286.4	11530.00
8	1027.55	149.81	0.258	0.60 ( 0.56)	0.94	21442.3	11000.00
9	1125.44	172.52	0.237	0.60 ( 0.57)	0.95	28248.7	10850.00
10	1040.32	187.93	0.228	0.60 ( 0.57)	0.96	31568.5	11220.00
11	979.24	199.16	0.224	0.60 ( 0.58)	0.96	33320.6	10910.00
12	819.39	239.17	0.212	0.60 ( 0.58)	0.96	39902.2	12410.00
13	775.50	272.02	0.202	0.60 ( 0.58)	0.97	45988.1	12261.00
14	761.03	284.75	0.199	0.60 ( 0.58)	0.97	47474.7	10410.00
15	746.74	296.89	0.195	0.60 ( 0.58)	0.97	48576.6	12101.10
16	731.87	306.58	0.192	0.60 ( 0.58)	0.97	49398.0	10700.00
17	714.45	324.30	0.187	0.60 ( 0.58)	0.97	50954.7	10200.00
18	698.14	337.64	0.183	0.60 ( 0.58)	0.97	51892.9	12010.00
19	653.30	366.61	0.175	0.60 ( 0.58)	0.97	52566.6	10210.00
20	592.41	415.58	0.170	0.60 ( 0.58)	0.97	53065.7	12000.00
21	551.36	484.99	0.162	0.60 ( 0.58)	0.97	53650.5	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115038.03 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	10.17	40.85	0.504	0.60 ( 0.59)	0.99	366.4	50300.00

LONGEST FLOWPATH FROM NODE 50300.00 TO NODE 12902.00 = 8614.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1258.42	12.60	1.084	0.60 ( 0.47)	0.78	1547.8	50200.00
2	1251.33	29.58	0.597	0.60 ( 0.47)	0.78	3594.9	300.00
3	1206.85	40.85	0.504	0.60 ( 0.48)	0.80	5216.8	50300.00
4	1183.47	46.43	0.472	0.60 ( 0.48)	0.81	5969.8	50120.00
5	992.86	58.00	0.409	0.60 ( 0.50)	0.83	7303.8	50100.00
6	876.56	93.33	0.334	0.60 ( 0.54)	0.90	12225.1	40100.00
7	897.84	106.05	0.311	0.60 ( 0.55)	0.91	13956.6	11831.00
8	960.17	129.94	0.277	0.60 ( 0.56)	0.93	17652.8	11530.00
9	1032.76	149.81	0.258	0.60 ( 0.56)	0.94	21808.7	11000.00
10	1130.22	172.52	0.237	0.60 ( 0.57)	0.95	28615.1	10850.00
11	1044.91	187.93	0.228	0.60 ( 0.57)	0.96	31934.9	11220.00
12	983.77	199.16	0.224	0.60 ( 0.58)	0.96	33686.9	10910.00
13	823.67	239.17	0.212	0.60 ( 0.58)	0.96	40268.6	12410.00
14	779.59	272.02	0.202	0.60 ( 0.58)	0.97	46354.5	12261.00
15	765.03	284.75	0.199	0.60 ( 0.58)	0.97	47841.1	10410.00
16	750.67	296.89	0.195	0.60 ( 0.58)	0.97	48943.0	12101.10
17	735.75	306.58	0.192	0.60 ( 0.58)	0.97	49764.4	10700.00
18	718.21	324.30	0.187	0.60 ( 0.58)	0.97	51321.1	10200.00
19	701.82	337.64	0.183	0.60 ( 0.58)	0.97	52259.3	12010.00
20	656.83	366.61	0.175	0.60 ( 0.58)	0.97	52933.0	10210.00
21	595.83	415.58	0.170	0.60 ( 0.58)	0.97	53432.1	12000.00
22	554.63	484.99	0.162	0.60 ( 0.58)	0.97	54016.9	10100.00

TOTAL AREA (ACRES) = 54016.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 1258.42 Tc(MIN.) = 12.599  
EFFECTIVE AREA(ACRES) = 1547.82 AREA-AVERAGED Fm(INCH/HR) = 0.47  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.78  
TOTAL AREA(ACRES) = 54016.9  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115038.03 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 12902.00 TO NODE 12903.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 215.00 DOWNSTREAM(FEET) = 214.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 895.53 CHANNEL SLOPE = 0.0011  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA(CFS) = 1258.42

FLOW VELOCITY(FEET/SEC.) = 4.55 FLOW DEPTH(FEET) = 9.60  
TRAVEL TIME(MIN.) = 3.28 Tc(MIN.) = 15.88  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115933.56 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1258.42	15.88	0.913	0.60 ( 0.47)	0.78	1547.8	50200.00
2	1251.33	32.86	0.568	0.60 ( 0.47)	0.78	3594.9	300.00
3	1206.85	44.17	0.485	0.60 ( 0.48)	0.80	5216.8	50300.00
4	1183.47	49.76	0.453	0.60 ( 0.48)	0.81	5969.8	50120.00
5	992.86	61.48	0.395	0.60 ( 0.50)	0.83	7303.8	50100.00
6	876.56	96.93	0.328	0.60 ( 0.54)	0.90	12225.1	40100.00
7	897.84	109.62	0.305	0.60 ( 0.55)	0.91	13956.6	11831.00
8	960.17	133.45	0.273	0.60 ( 0.56)	0.93	17652.8	11530.00
9	1032.76	153.26	0.255	0.60 ( 0.56)	0.94	21808.7	11000.00
10	1130.22	175.89	0.234	0.60 ( 0.57)	0.95	28615.1	10850.00
11	1044.91	191.37	0.227	0.60 ( 0.57)	0.96	31934.9	11220.00
12	983.77	202.65	0.223	0.60 ( 0.58)	0.96	33686.9	10910.00
13	823.67	242.82	0.211	0.60 ( 0.58)	0.96	40268.6	12410.00
14	779.59	275.71	0.201	0.60 ( 0.58)	0.97	46354.5	12261.00
15	765.03	288.47	0.197	0.60 ( 0.58)	0.97	47841.1	10410.00
16	750.67	300.63	0.194	0.60 ( 0.58)	0.97	48943.0	12101.10
17	735.75	310.33	0.191	0.60 ( 0.58)	0.97	49764.4	10700.00
18	718.21	328.07	0.186	0.60 ( 0.58)	0.97	51321.1	10200.00
19	701.82	341.44	0.182	0.60 ( 0.58)	0.97	52259.3	12010.00
20	656.83	370.47	0.175	0.60 ( 0.58)	0.97	52933.0	10210.00
21	595.83	419.53	0.169	0.60 ( 0.58)	0.97	53432.1	12000.00
22	554.63	489.01	0.162	0.60 ( 0.58)	0.97	54016.9	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 1258.42 Tc(MIN.) = 15.88  
AREA-AVERAGED Fm(INCH/HR) = 0.47 AREA-AVERAGED Fp(INCH/HR) = 0.60  
AREA-AVERAGED Ap = 0.78 EFFECTIVE AREA(ACRES) = 1547.82

\*\*\*\*\*

FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: E504XX02.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	7.19	22.32	0.60 ( 0.58)	0.97	70.5	50400.00

TOTAL AREA(ACRES) = 70.5

\*\*\*\*\*

FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1258.42	15.88	0.913	0.60 ( 0.47)	0.78	1547.8	50200.00
2	1251.33	32.86	0.568	0.60 ( 0.47)	0.78	3594.9	300.00
3	1206.85	44.17	0.485	0.60 ( 0.48)	0.80	5216.8	50300.00

4	1183.47	49.76	0.453	0.60 ( 0.48)	0.81	5969.8	50120.00
5	992.86	61.48	0.395	0.60 ( 0.50)	0.83	7303.8	50100.00
6	876.56	96.93	0.328	0.60 ( 0.54)	0.90	12225.1	40100.00
7	897.84	109.62	0.305	0.60 ( 0.55)	0.91	13956.6	11831.00
8	960.17	133.45	0.273	0.60 ( 0.56)	0.93	17652.8	11530.00
9	1032.76	153.26	0.255	0.60 ( 0.56)	0.94	21808.7	11000.00
10	1130.22	175.89	0.234	0.60 ( 0.57)	0.95	28615.1	10850.00
11	1044.91	191.37	0.227	0.60 ( 0.57)	0.96	31934.9	11220.00
12	983.77	202.65	0.223	0.60 ( 0.58)	0.96	33686.9	10910.00
13	823.67	242.82	0.211	0.60 ( 0.58)	0.96	40268.6	12410.00
14	779.59	275.71	0.201	0.60 ( 0.58)	0.97	46354.5	12261.00
15	765.03	288.47	0.197	0.60 ( 0.58)	0.97	47841.1	10410.00
16	750.67	300.63	0.194	0.60 ( 0.58)	0.97	48943.0	12101.10
17	735.75	310.33	0.191	0.60 ( 0.58)	0.97	49764.4	10700.00
18	718.21	328.07	0.186	0.60 ( 0.58)	0.97	51321.1	10200.00
19	701.82	341.44	0.182	0.60 ( 0.58)	0.97	52259.3	12010.00
20	656.83	370.47	0.175	0.60 ( 0.58)	0.97	52933.0	10210.00
21	595.83	419.53	0.169	0.60 ( 0.58)	0.97	53432.1	12000.00
22	554.63	489.01	0.162	0.60 ( 0.58)	0.97	54016.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115933.56 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	7.19	22.32	0.723	0.60 ( 0.58)	0.97	70.5	50400.00

LONGEST FLOWPATH FROM NODE 50400.00 TO NODE 12903.00 = 3607.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1265.61	15.88	0.913	0.60 ( 0.47)	0.79	1598.0	50200.00
2	1262.92	22.32	0.723	0.60 ( 0.47)	0.79	2394.0	50400.00
3	1252.27	32.86	0.568	0.60 ( 0.47)	0.78	3665.4	300.00
4	1207.66	44.17	0.485	0.60 ( 0.48)	0.80	5287.3	50300.00
5	1184.23	49.76	0.453	0.60 ( 0.48)	0.81	6040.3	50120.00
6	993.52	61.48	0.395	0.60 ( 0.50)	0.83	7374.3	50100.00
7	877.11	96.93	0.328	0.60 ( 0.54)	0.90	12295.6	40100.00
8	898.34	109.62	0.305	0.60 ( 0.55)	0.91	14027.1	11831.00
9	960.63	133.45	0.273	0.60 ( 0.56)	0.93	17723.3	11530.00
10	1033.18	153.26	0.255	0.60 ( 0.56)	0.94	21879.2	11000.00
11	1130.61	175.89	0.234	0.60 ( 0.57)	0.95	28685.6	10850.00
12	1045.29	191.37	0.227	0.60 ( 0.57)	0.96	32005.4	11220.00
13	984.14	202.65	0.223	0.60 ( 0.58)	0.96	33757.4	10910.00
14	824.02	242.82	0.211	0.60 ( 0.58)	0.96	40339.1	12410.00
15	779.92	275.71	0.201	0.60 ( 0.58)	0.97	46425.0	12261.00
16	765.36	288.47	0.197	0.60 ( 0.58)	0.97	47911.6	10410.00
17	750.99	300.63	0.194	0.60 ( 0.58)	0.97	49013.5	12101.10
18	736.06	310.33	0.191	0.60 ( 0.58)	0.97	49834.9	10700.00
19	718.52	328.07	0.186	0.60 ( 0.58)	0.97	51391.6	10200.00
20	702.13	341.44	0.182	0.60 ( 0.58)	0.97	52329.8	12010.00
21	657.12	370.47	0.175	0.60 ( 0.58)	0.97	53003.5	10210.00
22	596.11	419.53	0.169	0.60 ( 0.58)	0.97	53502.6	12000.00
23	554.90	489.01	0.162	0.60 ( 0.58)	0.97	54087.4	10100.00

TOTAL AREA (ACRES) = 54087.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 1265.61 Tc (MIN.) = 15.880  
EFFECTIVE AREA (ACRES) = 1597.99 AREA-AVERAGED Fm (INCH/HR) = 0.47

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.79  
TOTAL AREA (ACRES) = 54087.4  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115933.56 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 12903.00 TO NODE 12904.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 214.00 DOWNSTREAM (FEET) = 213.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 767.57 CHANNEL SLOPE = 0.0013  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA (CFS) = 1265.61  
FLOW VELOCITY (FEET/SEC.) = 4.83 FLOW DEPTH (FEET) = 9.35  
TRAVEL TIME (MIN.) = 2.65 Tc (MIN.) = 18.53  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116701.13 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1265.61	18.53	0.823	0.60 ( 0.47)	0.79	1598.0	50200.00
2	1262.92	24.97	0.667	0.60 ( 0.47)	0.79	2394.0	50400.00
3	1252.27	35.52	0.546	0.60 ( 0.47)	0.78	3665.4	300.00
4	1207.66	46.85	0.470	0.60 ( 0.48)	0.80	5287.3	50300.00
5	1184.23	52.46	0.439	0.60 ( 0.48)	0.81	6040.3	50120.00
6	993.52	64.30	0.390	0.60 ( 0.50)	0.83	7374.3	50100.00
7	877.11	99.83	0.322	0.60 ( 0.54)	0.90	12295.6	40100.00
8	898.34	112.51	0.299	0.60 ( 0.55)	0.91	14027.1	11831.00
9	960.63	136.30	0.271	0.60 ( 0.56)	0.93	17723.3	11530.00
10	1033.18	156.05	0.252	0.60 ( 0.56)	0.94	21879.2	11000.00
11	1130.61	178.62	0.231	0.60 ( 0.57)	0.95	28685.6	10850.00
12	1045.29	194.15	0.226	0.60 ( 0.57)	0.96	32005.4	11220.00
13	984.14	205.47	0.222	0.60 ( 0.58)	0.96	33757.4	10910.00
14	824.02	245.77	0.210	0.60 ( 0.58)	0.96	40339.1	12410.00
15	779.92	278.71	0.200	0.60 ( 0.58)	0.97	46425.0	12261.00
16	765.36	291.47	0.197	0.60 ( 0.58)	0.97	47911.6	10410.00
17	750.99	303.65	0.193	0.60 ( 0.58)	0.97	49013.5	12101.10
18	736.06	313.37	0.190	0.60 ( 0.58)	0.97	49834.9	10700.00
19	718.52	331.13	0.185	0.60 ( 0.58)	0.97	51391.6	10200.00
20	702.13	344.51	0.181	0.60 ( 0.58)	0.97	52329.8	12010.00
21	657.12	373.59	0.174	0.60 ( 0.58)	0.97	53003.5	10210.00
22	596.11	422.73	0.169	0.60 ( 0.58)	0.97	53502.6	12000.00
23	554.90	492.27	0.161	0.60 ( 0.58)	0.97	54087.4	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 1265.61 Tc (MIN.) = 18.53  
AREA-AVERAGED Fm (INCH/HR) = 0.47 AREA-AVERAGED Fp (INCH/HR) = 0.60  
AREA-AVERAGED Ap = 0.79 EFFECTIVE AREA (ACRES) = 1597.99

\*\*\*\*\*

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 15.1



=====  
>>>>DEFINE MEMORY BANK # 3 <<<<  
=====

PEAK FLOWRATE TABLE FILE NAME: 3B02EVRL.DNA  
MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	104.86	17.96	0.60 ( 0.25)	0.42	197.7	200.00
2	98.61	20.55	0.60 ( 0.25)	0.42	214.7	210.00
TOTAL AREA (ACRES) =						214.7

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<  
=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1265.61	18.53	0.823	0.60 ( 0.47)	0.79	1598.0	50200.00
2	1262.92	24.97	0.667	0.60 ( 0.47)	0.79	2394.0	50400.00
3	1252.27	35.52	0.546	0.60 ( 0.47)	0.78	3665.4	300.00
4	1207.66	46.85	0.470	0.60 ( 0.48)	0.80	5287.3	50300.00
5	1184.23	52.46	0.439	0.60 ( 0.48)	0.81	6040.3	50120.00
6	993.52	64.30	0.390	0.60 ( 0.50)	0.83	7374.3	50100.00
7	877.11	99.83	0.322	0.60 ( 0.54)	0.90	12295.6	40100.00
8	898.34	112.51	0.299	0.60 ( 0.55)	0.91	14027.1	11831.00
9	960.63	136.30	0.271	0.60 ( 0.56)	0.93	17723.3	11530.00
10	1033.18	156.05	0.252	0.60 ( 0.56)	0.94	21879.2	11000.00
11	1130.61	178.62	0.231	0.60 ( 0.57)	0.95	28685.6	10850.00
12	1045.29	194.15	0.226	0.60 ( 0.57)	0.96	32005.4	11220.00
13	984.14	205.47	0.222	0.60 ( 0.58)	0.96	33757.4	10910.00
14	824.02	245.77	0.210	0.60 ( 0.58)	0.96	40339.1	12410.00
15	779.92	278.71	0.200	0.60 ( 0.58)	0.97	46425.0	12261.00
16	765.36	291.47	0.197	0.60 ( 0.58)	0.97	47911.6	10410.00
17	750.99	303.65	0.193	0.60 ( 0.58)	0.97	49013.5	12101.10
18	736.06	313.37	0.190	0.60 ( 0.58)	0.97	49834.9	10700.00
19	718.52	331.13	0.185	0.60 ( 0.58)	0.97	51391.6	10200.00
20	702.13	344.51	0.181	0.60 ( 0.58)	0.97	52329.8	12010.00
21	657.12	373.59	0.174	0.60 ( 0.58)	0.97	53003.5	10210.00
22	596.11	422.73	0.169	0.60 ( 0.58)	0.97	53502.6	12000.00
23	554.90	492.27	0.161	0.60 ( 0.58)	0.97	54087.4	10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 =							116701.13 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	104.86	17.96	0.842	0.60 ( 0.25)	0.42	197.7	200.00
2	98.61	20.55	0.761	0.60 ( 0.25)	0.42	214.7	210.00
LONGEST FLOWPATH FROM NODE 210.00 TO NODE 12904.00 =							5961.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1370.47	17.96	0.842	0.60 ( 0.45)	0.75	1746.4	200.00
2	1369.09	18.53	0.823	0.60 ( 0.45)	0.75	1799.4	50200.00
3	1363.38	20.55	0.761	0.60 ( 0.45)	0.75	2062.7	210.00

4	1343.21	24.97	0.667	0.60 ( 0.45)	0.76	2608.7	50400.00
5	1313.52	35.52	0.546	0.60 ( 0.46)	0.76	3880.1	300.00
6	1260.41	46.85	0.470	0.60 ( 0.47)	0.79	5502.0	50300.00
7	1233.47	52.46	0.439	0.60 ( 0.48)	0.79	6255.0	50120.00
8	1037.25	64.30	0.390	0.60 ( 0.49)	0.82	7589.0	50100.00
9	913.28	99.83	0.322	0.60 ( 0.53)	0.89	12510.3	40100.00
10	931.96	112.51	0.299	0.60 ( 0.54)	0.90	14241.8	11831.00
11	991.02	136.30	0.271	0.60 ( 0.55)	0.92	17938.0	11530.00
12	1061.51	156.05	0.252	0.60 ( 0.56)	0.94	22093.9	11000.00
13	1156.57	178.62	0.231	0.60 ( 0.57)	0.95	28900.3	10850.00
14	1070.62	194.15	0.226	0.60 ( 0.57)	0.95	32220.1	11220.00
15	1009.09	205.47	0.222	0.60 ( 0.57)	0.96	33972.1	10910.00
16	847.62	245.77	0.210	0.60 ( 0.58)	0.96	40553.8	12410.00
17	802.41	278.71	0.200	0.60 ( 0.58)	0.96	46639.7	12261.00
18	787.42	291.47	0.197	0.60 ( 0.58)	0.96	48126.3	10410.00
19	772.65	303.65	0.193	0.60 ( 0.58)	0.97	49228.2	12101.10
20	757.39	313.37	0.190	0.60 ( 0.58)	0.97	50049.6	10700.00
21	739.25	331.13	0.185	0.60 ( 0.58)	0.97	51606.3	10200.00
22	722.40	344.51	0.181	0.60 ( 0.58)	0.97	52544.5	12010.00
23	676.71	373.59	0.174	0.60 ( 0.58)	0.97	53218.2	10210.00
24	615.08	422.73	0.169	0.60 ( 0.58)	0.97	53717.3	12000.00
25	572.99	492.27	0.161	0.60 ( 0.58)	0.97	54302.1	10100.00
TOTAL AREA (ACRES) =							54302.1

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 1370.47 Tc (MIN.) = 17.960  
EFFECTIVE AREA (ACRES) = 1746.44 AREA-AVERAGED Fm (INCH/HR) = 0.45  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.97  
TOTAL AREA (ACRES) = 54302.1  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116701.13 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<  
=====

MAINLINE Tc (MIN.) = 17.96

\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.842

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.70	0.60	0.100	-
USER-DEFINED	-	20.00	0.60	1.000	-
USER-DEFINED	-	0.10	0.60	1.000	-
USER-DEFINED	-	14.90	0.60	0.850	-
USER-DEFINED	-	2.60	0.60	0.900	-
USER-DEFINED	-	0.80	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.920

SUBAREA AREA (ACRES) = 39.10 SUBAREA RUNOFF (CFS) = 10.22

EFFECTIVE AREA (ACRES) = 1785.54 AREA-AVERAGED Fm (INCH/HR) = 0.45

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.75

TOTAL AREA (ACRES) = 54341.2 PEAK FLOW RATE (CFS) = 1370.47

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 17.96

\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.842

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.30	0.60	0.100	-
USER-DEFINED	-	0.10	0.60	1.000	-
USER-DEFINED	-	0.10	0.60	1.000	-
USER-DEFINED	-	1.70	0.60	0.900	-
USER-DEFINED	-	2.60	0.60	1.000	-
USER-DEFINED	-	0.20	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.912

SUBAREA AREA(ACRES) = 5.00 SUBAREA RUNOFF(CFS) = 1.33

EFFECTIVE AREA(ACRES) = 1790.54 AREA-AVERAGED Fm(INCH/HR) = 0.45

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.75

TOTAL AREA(ACRES) = 54346.2 PEAK FLOW RATE(CFS) = 1370.47

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 17.96

\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.842

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.10	0.60	1.000	-
USER-DEFINED	-	2.60	0.60	0.900	-
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	3.00	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.956

SUBAREA AREA(ACRES) = 5.90 SUBAREA RUNOFF(CFS) = 1.43

EFFECTIVE AREA(ACRES) = 1796.44 AREA-AVERAGED Fm(INCH/HR) = 0.45

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.75

TOTAL AREA(ACRES) = 54352.1 PEAK FLOW RATE(CFS) = 1370.47

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 54352.1 TC(MIN.) = 17.96

EFFECTIVE AREA(ACRES) = 1796.44 AREA-AVERAGED Fm(INCH/HR) = 0.45

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.751

PEAK FLOW RATE(CFS) = 1370.47

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1370.47	17.96	0.842	0.60( 0.45)	0.75	1796.4	200.00
2	1369.09	18.53	0.823	0.60( 0.45)	0.75	1849.4	50200.00
3	1363.38	20.55	0.761	0.60( 0.45)	0.75	2112.7	210.00
4	1343.21	24.97	0.667	0.60( 0.46)	0.76	2658.7	50400.00
5	1313.52	35.52	0.546	0.60( 0.46)	0.77	3930.1	300.00
6	1260.41	46.85	0.470	0.60( 0.47)	0.79	5552.0	50300.00

7	1233.47	52.46	0.439	0.60( 0.48)	0.80	6305.0	50120.00
8	1037.25	64.30	0.390	0.60( 0.49)	0.82	7639.0	50100.00
9	913.28	99.83	0.322	0.60( 0.53)	0.89	12560.3	40100.00
10	931.96	112.51	0.299	0.60( 0.54)	0.90	14291.8	11831.00
11	991.02	136.30	0.271	0.60( 0.55)	0.92	17988.0	11530.00
12	1061.51	156.05	0.252	0.60( 0.56)	0.94	22143.9	11000.00
13	1156.57	178.62	0.231	0.60( 0.57)	0.95	28950.3	10850.00
14	1070.62	194.15	0.226	0.60( 0.57)	0.95	32270.1	11220.00
15	1009.09	205.47	0.222	0.60( 0.57)	0.96	34022.1	10910.00
16	847.62	245.77	0.210	0.60( 0.58)	0.96	40603.8	12410.00
17	802.41	278.71	0.200	0.60( 0.58)	0.96	46689.7	12261.00
18	787.42	291.47	0.197	0.60( 0.58)	0.96	48176.3	10410.00
19	772.65	303.65	0.193	0.60( 0.58)	0.97	49278.2	12101.10
20	757.39	313.37	0.190	0.60( 0.58)	0.97	50099.6	10700.00
21	739.25	331.13	0.185	0.60( 0.58)	0.97	51656.3	10200.00
22	722.40	344.51	0.181	0.60( 0.58)	0.97	52594.5	12010.00
23	676.71	373.59	0.174	0.60( 0.58)	0.97	53268.2	10210.00
24	615.08	422.73	0.169	0.60( 0.58)	0.97	53767.3	12000.00
25	572.99	492.27	0.161	0.60( 0.58)	0.97	54352.1	10100.00

=====

END OF RATIONAL METHOD ANALYSIS



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA 92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S33- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 2-YR RM EV APRIL 2019 ROKAMOTO \*  
\*\*\*\*\*

FILE NAME: RI02EV33.DAT  
TIME/DATE OF STUDY: 17:08 04/08/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 2.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 1.825
- 2) 10.00; 1.217
- 3) 15.00; 0.932
- 4) 20.00; 0.766
- 5) 25.00; 0.662
- 6) 30.00; 0.587
- 7) 40.00; 0.506
- 8) 50.00; 0.449
- 9) 60.00; 0.395
- 10) 90.00; 0.340
- 11) 120.00; 0.286
- 12) 180.00; 0.232
- 13) 360.00; 0.178
- 14) 1200.00; 0.080

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL: IN- / OUT-/PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:

- 1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13112.00 TO NODE 13222.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: S31X02.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	170.57	51.53	0.60 ( 0.49)	0.81	2407.7	13100.00
2	195.69	91.33	0.60 ( 0.48)	0.81	3776.8	13000.00
3	193.58	94.68	0.60 ( 0.48)	0.81	3796.8	13010.00
TOTAL AREA (ACRES) =						3796.8

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13221.00 TO NODE 13222.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: S32X02.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	71.12	52.96	0.60 ( 0.49)	0.82	1090.8	13200.00
2	65.38	59.51	0.60 ( 0.50)	0.83	1127.6	13210.00
TOTAL AREA (ACRES) =						1127.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13221.00 TO NODE 13222.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	71.12	52.96	0.60 ( 0.49)	0.82	1090.8	13200.00
2	65.38	59.51	0.60 ( 0.50)	0.83	1127.6	13210.00
TOTAL AREA (ACRES) =						1127.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13112.00 TO NODE 13222.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	71.12	52.96	0.433	0.60 ( 0.49)	0.82	1090.8	13200.00
2	65.38	59.51	0.398	0.60 ( 0.50)	0.83	1127.6	13210.00
LONGEST FLOWPATH FROM NODE 13200.00 TO NODE 13222.00 =							16821.05 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	170.57	51.53	0.441	0.60 ( 0.49)	0.81	2407.7	13100.00
2	195.69	91.33	0.338	0.60 ( 0.48)	0.81	3776.8	13000.00
3	193.58	94.68	0.332	0.60 ( 0.48)	0.81	3796.8	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13222.00 = 32126.49 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	241.00	51.53	0.441	0.60 ( 0.49)	0.81	3469.1	13100.00
2	242.59	52.96	0.433	0.60 ( 0.49)	0.81	3547.6	13200.00
3	240.98	59.51	0.398	0.60 ( 0.49)	0.81	3809.6	13210.00
4	251.19	91.33	0.338	0.60 ( 0.49)	0.81	4904.4	13000.00
5	248.09	94.68	0.332	0.60 ( 0.49)	0.81	4924.4	13010.00

TOTAL AREA (ACRES) = 4924.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 251.19 Tc(MIN.) = 91.333  
 EFFECTIVE AREA(ACRES) = 4904.45 AREA-AVERAGED Fm(INCH/HR) = 0.49  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.81  
 TOTAL AREA (ACRES) = 4924.4  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13222.00 = 32126.49 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13222.00 TO NODE 13222.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13222.00 TO NODE 13222.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13222.00 TO NODE 13301.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 427.51 DOWNSTREAM(FEET) = 382.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2533.33 CHANNEL SLOPE = 0.0180  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00

\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.327

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.40	0.60	0.100	-
USER-DEFINED	-	15.60	0.60	1.000	-
USER-DEFINED	-	0.10	0.60	0.600	-
USER-DEFINED	-	5.30	0.60	1.000	-
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	22.60	0.60	0.100	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.521

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 254.38

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.96

AVERAGE FLOW DEPTH(FEET) = 3.49 TRAVEL TIME(MIN.) = 6.06

Tc(MIN.) = 97.40

SUBAREA AREA(ACRES) = 45.20 SUBAREA RUNOFF(CFS) = 6.36

EFFECTIVE AREA(ACRES) = 4949.65 AREA-AVERAGED Fm(INCH/HR) = 0.49

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.81

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 4969.6 PEAK FLOW RATE(CFS) = 276.97

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 3.60 FLOW VELOCITY(FEET/SEC.) = 7.11

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	244.92	57.64	0.408	0.60 ( 0.49)	0.81	3514.3	13100.00
2	245.64	59.06	0.400	0.60 ( 0.49)	0.81	3592.8	13200.00
3	251.52	65.62	0.385	0.60 ( 0.49)	0.81	3854.8	13210.00
4	276.97	97.40	0.327	0.60 ( 0.49)	0.81	4949.6	13000.00
5	273.17	100.77	0.321	0.60 ( 0.49)	0.81	4969.6	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 276.97 Tc(MIN.) = 97.40

AREA-AVERAGED Fm(INCH/HR) = 0.49 AREA-AVERAGED Fp(INCH/HR) = 0.60

AREA-AVERAGED Ap = 0.81 EFFECTIVE AREA(ACRES) = 4949.65

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 97.40

\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.327

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.00	0.60	1.000	-
USER-DEFINED	-	0.50	0.60	1.000	-
USER-DEFINED	-	7.40	0.60	0.100	-
USER-DEFINED	-	4.70	0.60	1.000	-
USER-DEFINED	-	2.90	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.596

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 16.50 SUBAREA RUNOFF(CFS) = 1.96

EFFECTIVE AREA(ACRES) = 4966.15 AREA-AVERAGED Fm(INCH/HR) = 0.49

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.81

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 4986.1 PEAK FLOW RATE(CFS) = 278.93

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 97.40

\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.327

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.30	0.60	1.000	-
USER-DEFINED	-	0.20	0.60	0.100	-
USER-DEFINED	-	5.30	0.60	1.000	-
USER-DEFINED	-	0.30	0.60	1.000	-
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	0.60	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.977

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 7.90 SUBAREA RUNOFF(CFS) = 0.05

EFFECTIVE AREA(ACRES) = 4974.05 AREA-AVERAGED Fm(INCH/HR) = 0.49

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.81

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 4994.0 PEAK FLOW RATE(CFS) = 278.98

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 97.40

\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.327

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	4.30	0.60	1.000	-
USER-DEFINED	-	0.80	0.60	1.000	-
USER-DEFINED	-	1.10	0.60	1.000	-
USER-DEFINED	-	6.90	0.60	1.000	-
USER-DEFINED	-	7.90	0.60	1.000	-
USER-DEFINED	-	1.00	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 22.00 SUBAREA RUNOFF(CFS) = 0.00

EFFECTIVE AREA(ACRES) = 4996.05 AREA-AVERAGED Fm(INCH/HR) = 0.49

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.81

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 5016.0 PEAK FLOW RATE(CFS) = 278.98

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 97.40

\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.327

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.40	0.60	1.000	-
USER-DEFINED	-	14.60	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 15.00 SUBAREA RUNOFF(CFS) = 0.00

EFFECTIVE AREA(ACRES) = 5011.05 AREA-AVERAGED Fm(INCH/HR) = 0.49

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.81

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 5031.0 PEAK FLOW RATE(CFS) = 278.98

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 31100.00 TO NODE 31101.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<

>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH(FEET) = 317.00

ELEVATION DATA: UPSTREAM(FEET) = 801.00 DOWNSTREAM(FEET) = 685.00

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20

SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 8.641

\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 1.382

SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	-	0.50	0.60	1.000	0	8.64
NATURAL FAIR COVER "OPEN BRUSH"	-	0.30	0.60	1.000	0	8.64
NATURAL FAIR COVER "OPEN BRUSH"	-	0.30	0.60	1.000	0	8.64

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA RUNOFF(CFS) = 0.77

TOTAL AREA(ACRES) = 1.10 PEAK FLOW RATE(CFS) = 0.77

\*\*\*\*\*

FLOW PROCESS FROM NODE 31101.00 TO NODE 31102.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 685.00 DOWNSTREAM(FEET) = 655.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 135.00 CHANNEL SLOPE = 0.2222

CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 1.324  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.50	0.60	1.000	-
USER-DEFINED	-	0.10	0.60	1.000	-
USER-DEFINED	-	0.70	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 1.20  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.66  
 AVERAGE FLOW DEPTH (FEET) = 0.29 TRAVEL TIME (MIN.) = 0.48  
 Tc (MIN.) = 9.12  
 SUBAREA AREA (ACRES) = 1.30 SUBAREA RUNOFF (CFS) = 0.85  
 EFFECTIVE AREA (ACRES) = 2.40 AREA-AVERAGED Fm (INCH/HR) = 0.60  
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA (ACRES) = 2.4 PEAK FLOW RATE (CFS) = 1.56

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 0.32 FLOW VELOCITY (FEET/SEC.) = 4.99  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31102.00 = 452.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31102.00 TO NODE 31103.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 655.00 DOWNSTREAM (FEET) = 630.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 203.00 CHANNEL SLOPE = 0.1232  
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 1.230  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.30	0.60	1.000	-
USER-DEFINED	-	0.10	0.60	1.000	-
USER-DEFINED	-	1.90	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 2.22  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.41  
 AVERAGE FLOW DEPTH (FEET) = 0.41 TRAVEL TIME (MIN.) = 0.77  
 Tc (MIN.) = 9.89  
 SUBAREA AREA (ACRES) = 2.30 SUBAREA RUNOFF (CFS) = 1.31  
 EFFECTIVE AREA (ACRES) = 4.70 AREA-AVERAGED Fm (INCH/HR) = 0.60  
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA (ACRES) = 4.7 PEAK FLOW RATE (CFS) = 2.67

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 0.44 FLOW VELOCITY (FEET/SEC.) = 4.60  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31103.00 = 655.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31103.00 TO NODE 31104.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 630.00 DOWNSTREAM (FEET) = 605.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 321.00 CHANNEL SLOPE = 0.0779  
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 1.149  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.10	0.60	1.000	-
USER-DEFINED	-	2.50	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 3.56  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.11  
 AVERAGE FLOW DEPTH (FEET) = 0.54 TRAVEL TIME (MIN.) = 1.30  
 Tc (MIN.) = 11.19  
 SUBAREA AREA (ACRES) = 3.60 SUBAREA RUNOFF (CFS) = 1.78  
 EFFECTIVE AREA (ACRES) = 8.30 AREA-AVERAGED Fm (INCH/HR) = 0.60  
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA (ACRES) = 8.3 PEAK FLOW RATE (CFS) = 4.10

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 0.56 FLOW VELOCITY (FEET/SEC.) = 4.33  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31104.00 = 976.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31104.00 TO NODE 31105.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 605.00 DOWNSTREAM (FEET) = 585.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 288.00 CHANNEL SLOPE = 0.0694  
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 1.087  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.70	0.60	1.000	-
USER-DEFINED	-	0.60	0.60	1.000	-
USER-DEFINED	-	3.00	0.60	1.000	-
USER-DEFINED	-	2.10	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 5.51  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.43  
 AVERAGE FLOW DEPTH (FEET) = 0.64 TRAVEL TIME (MIN.) = 1.08  
 Tc (MIN.) = 12.27  
 SUBAREA AREA (ACRES) = 6.40 SUBAREA RUNOFF (CFS) = 2.81  
 EFFECTIVE AREA (ACRES) = 14.70 AREA-AVERAGED Fm (INCH/HR) = 0.60  
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA (ACRES) = 14.7 PEAK FLOW RATE (CFS) = 6.45

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.68 FLOW VELOCITY(FEET/SEC.) = 4.62  
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31105.00 = 1264.00 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 31105.00 TO NODE 31106.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 585.00 DOWNSTREAM(FEET) = 560.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 344.00 CHANNEL SLOPE = 0.0727  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 1.022

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.60	0.60	1.000	-
USER-DEFINED	-	2.80	0.60	1.000	-
USER-DEFINED	-	0.60	0.60	1.000	-
USER-DEFINED	-	0.10	0.60	1.000	-
USER-DEFINED	-	2.60	0.60	1.000	-
USER-DEFINED	-	4.10	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 8.51  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.03  
AVERAGE FLOW DEPTH(FEET) = 0.75 TRAVEL TIME(MIN.) = 1.14  
Tc(MIN.) = 13.41  
SUBAREA AREA(ACRES) = 10.80 SUBAREA RUNOFF(CFS) = 4.11  
EFFECTIVE AREA(ACRES) = 25.50 AREA-AVERAGED Fm(INCH/HR) = 0.60  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 25.5 PEAK FLOW RATE(CFS) = 9.70

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.79 FLOW VELOCITY(FEET/SEC.) = 5.20  
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31106.00 = 1608.00 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 31106.00 TO NODE 31107.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 560.00 DOWNSTREAM(FEET) = 530.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 619.00 CHANNEL SLOPE = 0.0485  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.911

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.80	0.60	1.000	-
USER-DEFINED	-	1.90	0.60	1.000	-
USER-DEFINED	-	1.50	0.60	1.000	-
USER-DEFINED	-	8.20	0.60	1.000	-
USER-DEFINED	-	2.70	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 11.83  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.67  
AVERAGE FLOW DEPTH(FEET) = 0.92 TRAVEL TIME(MIN.) = 2.21  
Tc(MIN.) = 15.62  
SUBAREA AREA(ACRES) = 15.10 SUBAREA RUNOFF(CFS) = 4.23  
EFFECTIVE AREA(ACRES) = 40.60 AREA-AVERAGED Fm(INCH/HR) = 0.60  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 40.6 PEAK FLOW RATE(CFS) = 11.38

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.90 FLOW VELOCITY(FEET/SEC.) = 4.65  
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31107.00 = 2227.00 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 31107.00 TO NODE 31108.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 530.00 DOWNSTREAM(FEET) = 515.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 377.00 CHANNEL SLOPE = 0.0398  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.865

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.50	0.60	1.000	-
USER-DEFINED	-	6.50	0.60	1.000	-
USER-DEFINED	-	1.30	0.60	1.000	-
USER-DEFINED	-	1.10	0.60	1.000	-
USER-DEFINED	-	5.50	0.60	1.000	-
USER-DEFINED	-	3.40	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 13.57  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.50  
AVERAGE FLOW DEPTH(FEET) = 1.00 TRAVEL TIME(MIN.) = 1.40  
Tc(MIN.) = 17.02  
SUBAREA AREA(ACRES) = 18.30 SUBAREA RUNOFF(CFS) = 4.37  
EFFECTIVE AREA(ACRES) = 58.90 AREA-AVERAGED Fm(INCH/HR) = 0.60  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 58.9 PEAK FLOW RATE(CFS) = 14.06

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 1.02 FLOW VELOCITY(FEET/SEC.) = 4.53  
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31108.00 = 2604.00 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 31108.00 TO NODE 31109.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 515.00 DOWNSTREAM(FEET) = 490.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 520.00 CHANNEL SLOPE = 0.0481



CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.808  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.70	0.60	1.000	-
USER-DEFINED	-	2.20	0.60	1.000	-
USER-DEFINED	-	3.10	0.60	1.000	-
USER-DEFINED	-	0.90	0.60	1.000	-
USER-DEFINED	-	7.40	0.60	1.000	-
USER-DEFINED	-	0.30	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 15.43  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.02  
AVERAGE FLOW DEPTH (FEET) = 1.01 TRAVEL TIME (MIN.) = 1.73  
Tc (MIN.) = 18.74  
SUBAREA AREA (ACRES) = 14.60 SUBAREA RUNOFF (CFS) = 2.73  
EFFECTIVE AREA (ACRES) = 73.50 AREA-AVERAGED Fm (INCH/HR) = 0.60  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
TOTAL AREA (ACRES) = 73.5 PEAK FLOW RATE (CFS) = 14.06  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 0.98 FLOW VELOCITY (FEET/SEC.) = 4.89  
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31109.00 = 3124.00 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 31109.00 TO NODE 31109.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
=====

MAINLINE Tc (MIN.) = 18.74  
\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.808  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	11.40	0.60	1.000	-
USER-DEFINED	-	8.90	0.60	1.000	-
USER-DEFINED	-	1.90	0.60	1.000	-
USER-DEFINED	-	9.20	0.60	1.000	-
USER-DEFINED	-	1.40	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 32.80 SUBAREA RUNOFF (CFS) = 6.14  
EFFECTIVE AREA (ACRES) = 106.30 AREA-AVERAGED Fm (INCH/HR) = 0.60  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
TOTAL AREA (ACRES) = 106.3 PEAK FLOW RATE (CFS) = 19.89

\*\*\*\*\*  
FLOW PROCESS FROM NODE 31109.00 TO NODE 31110.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<  
=====

ELEVATION DATA: UPSTREAM (FEET) = 490.00 DOWNSTREAM (FEET) = 432.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1420.00 CHANNEL SLOPE = 0.0408

CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.695  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.80	0.60	1.000	-
USER-DEFINED	-	0.60	0.60	1.000	-
USER-DEFINED	-	0.10	0.60	0.900	-
USER-DEFINED	-	1.30	0.60	1.000	-
USER-DEFINED	-	4.00	0.60	1.000	-
USER-DEFINED	-	1.50	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 20.25  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.04  
AVERAGE FLOW DEPTH (FEET) = 1.16 TRAVEL TIME (MIN.) = 4.69  
Tc (MIN.) = 23.43  
SUBAREA AREA (ACRES) = 8.30 SUBAREA RUNOFF (CFS) = 0.71  
EFFECTIVE AREA (ACRES) = 114.60 AREA-AVERAGED Fm (INCH/HR) = 0.60  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
TOTAL AREA (ACRES) = 114.6 PEAK FLOW RATE (CFS) = 19.89  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 1.15 FLOW VELOCITY (FEET/SEC.) = 5.02  
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31110.00 = 4544.00 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 31110.00 TO NODE 31110.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
=====

MAINLINE Tc (MIN.) = 23.43  
\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.695  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.30	0.60	1.000	-
USER-DEFINED	-	9.60	0.60	1.000	-
USER-DEFINED	-	0.40	0.60	0.900	-
USER-DEFINED	-	6.20	0.60	1.000	-
USER-DEFINED	-	3.90	0.60	1.000	-
USER-DEFINED	-	1.40	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.998  
SUBAREA AREA (ACRES) = 21.80 SUBAREA RUNOFF (CFS) = 1.88  
EFFECTIVE AREA (ACRES) = 136.40 AREA-AVERAGED Fm (INCH/HR) = 0.60  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
TOTAL AREA (ACRES) = 136.4 PEAK FLOW RATE (CFS) = 19.89  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 31110.00 TO NODE 13301.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<  
=====

ELEVATION DATA: UPSTREAM (FEET) = 490.00 DOWNSTREAM (FEET) = 432.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1420.00 CHANNEL SLOPE = 0.0408

ELEVATION DATA: UPSTREAM(FEET) = 432.00 DOWNSTREAM(FEET) = 382.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1847.00 CHANNEL SLOPE = 0.0271  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.582

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	4.90	0.60	1.000	-
USER-DEFINED	-	1.50	0.60	1.000	-
USER-DEFINED	-	0.60	0.60	0.900	-
USER-DEFINED	-	2.50	0.60	1.000	-
USER-DEFINED	-	5.30	0.60	1.000	-
USER-DEFINED	-	3.30	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.997

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 19.91

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.31

AVERAGE FLOW DEPTH(FEET) = 1.24 TRAVEL TIME(MIN.) = 7.14

Tc(MIN.) = 30.57

SUBAREA AREA(ACRES) = 18.10 SUBAREA RUNOFF(CFS) = 0.03

EFFECTIVE AREA(ACRES) = 154.50 AREA-AVERAGED Fm(INCH/HR) = 0.60

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 154.5 PEAK FLOW RATE(CFS) = 19.89

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.24 FLOW VELOCITY(FEET/SEC.) = 4.31

LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 13301.00 = 6391.00 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19.89	30.57	0.582	0.60( 0.60)	1.00	154.5	31100.00

LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 13301.00 = 6391.00 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	247.43	57.64	0.408	0.60( 0.49)	0.81	3575.7	13100.00
2	248.10	59.06	0.400	0.60( 0.49)	0.81	3654.2	13200.00
3	253.89	65.62	0.385	0.60( 0.49)	0.81	3916.2	13210.00
4	278.98	97.40	0.327	0.60( 0.49)	0.81	5011.0	13000.00
5	275.15	100.77	0.321	0.60( 0.49)	0.81	5031.0	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	--------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	207.33	30.57	0.582	0.60( 0.50)	0.83	2050.9
2	261.36	57.64	0.408	0.60( 0.49)	0.82	3730.2
3	261.77	59.06	0.400	0.60( 0.49)	0.82	3808.7
4	267.03	65.62	0.385	0.60( 0.49)	0.82	4070.7
5	290.14	97.40	0.327	0.60( 0.49)	0.82	5165.5
6	286.10	100.77	0.321	0.60( 0.49)	0.82	5185.5

TOTAL AREA(ACRES) = 5185.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 290.14 Tc(MIN.) = 97.396

EFFECTIVE AREA(ACRES) = 5165.55 AREA-AVERAGED Fm(INCH/HR) = 0.49

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.82

TOTAL AREA(ACRES) = 5185.5

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13302.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 382.00 DOWNSTREAM(FEET) = 375.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 1141.09 CHANNEL SLOPE = 0.0061

CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00

\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.320

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	9.42	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 290.14

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.81

AVERAGE FLOW DEPTH(FEET) = 4.48 TRAVEL TIME(MIN.) = 3.95

Tc(MIN.) = 101.35

SUBAREA AREA(ACRES) = 9.42 SUBAREA RUNOFF(CFS) = 0.00

EFFECTIVE AREA(ACRES) = 5174.97 AREA-AVERAGED Fm(INCH/HR) = 0.49

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.82

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 5194.9 PEAK FLOW RATE(CFS) = 290.14

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 4.48 FLOW VELOCITY(FEET/SEC.) = 4.81

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13302.00 = 35800.91 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	207.33	34.88	0.548	0.60 ( 0.50)	0.83	2060.3	31100.00
2	261.36	61.71	0.392	0.60 ( 0.49)	0.82	3739.6	13100.00
3	261.77	63.12	0.389	0.60 ( 0.49)	0.82	3818.2	13200.00
4	267.03	69.66	0.377	0.60 ( 0.49)	0.82	4080.1	13210.00
5	290.14	101.35	0.320	0.60 ( 0.49)	0.82	5175.0	13000.00
6	286.10	104.74	0.313	0.60 ( 0.49)	0.82	5194.9	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 290.14 Tc(MIN.) = 101.35  
 AREA-AVERAGED Fm(INCH/HR) = 0.49 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.82 EFFECTIVE AREA(ACRES) = 5174.97

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 101.35  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.320  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	13.80	0.60	1.000	-
USER-DEFINED	-	2.60	0.60	1.000	-
USER-DEFINED	-	1.10	0.60	0.100	-
USER-DEFINED	-	3.50	0.60	0.900	-
USER-DEFINED	-	6.90	0.60	1.000	-
USER-DEFINED	-	0.20	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.952  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 SUBAREA AREA(ACRES) = 28.10 SUBAREA RUNOFF(CFS) = 0.39  
 EFFECTIVE AREA(ACRES) = 5203.07 AREA-AVERAGED Fm(INCH/HR) = 0.49  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.82  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 5223.0 PEAK FLOW RATE(CFS) = 290.14  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 101.35  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.320  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.10	0.60	1.000	-
USER-DEFINED	-	0.10	0.60	0.100	-
USER-DEFINED	-	2.40	0.60	0.900	-
USER-DEFINED	-	0.50	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.894  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 SUBAREA AREA(ACRES) = 3.10 SUBAREA RUNOFF(CFS) = 0.09  
 EFFECTIVE AREA(ACRES) = 5206.17 AREA-AVERAGED Fm(INCH/HR) = 0.49  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.82  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 5226.1 PEAK FLOW RATE(CFS) = 290.14  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 101.35  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.320  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.10	0.60	1.000	-
USER-DEFINED	-	2.60	0.60	1.000	-
USER-DEFINED	-	3.10	0.60	1.000	-
USER-DEFINED	-	0.40	0.60	1.000	-
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	13.80	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 SUBAREA AREA(ACRES) = 20.20 SUBAREA RUNOFF(CFS) = 0.00  
 EFFECTIVE AREA(ACRES) = 5226.37 AREA-AVERAGED Fm(INCH/HR) = 0.49  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.82  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 5246.4 PEAK FLOW RATE(CFS) = 290.14  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 101.35  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.320  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	34.60	0.60	1.000	-
USER-DEFINED	-	2.40	0.60	1.000	-
USER-DEFINED	-	22.60	0.60	1.000	-
USER-DEFINED	-	11.60	0.60	1.000	-
USER-DEFINED	-	0.40	0.60	0.200	-
USER-DEFINED	-	4.80	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.996  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 SUBAREA AREA(ACRES) = 76.40 SUBAREA RUNOFF(CFS) = 0.09

EFFECTIVE AREA(ACRES) = 5302.77 AREA-AVERAGED Fm(INCH/HR) = 0.49  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.82  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 5322.8 PEAK FLOW RATE(CFS) = 290.14  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 101.35  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.320  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.60	0.60	1.000	-
USER-DEFINED	-	46.40	0.60	1.000	-
USER-DEFINED	-	0.10	0.60	0.200	-
USER-DEFINED	-	60.70	0.60	1.000	-
USER-DEFINED	-	5.80	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 SUBAREA AREA(ACRES) = 114.60 SUBAREA RUNOFF(CFS) = 0.02  
 EFFECTIVE AREA(ACRES) = 5417.37 AREA-AVERAGED Fm(INCH/HR) = 0.49  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.82  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 5437.4 PEAK FLOW RATE(CFS) = 290.14  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13302.00 TO NODE 13303.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 375.00 DOWNSTREAM(FEET) = 355.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2193.96 CHANNEL SLOPE = 0.0091  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
 CHANNEL FLOW THRU SUBAREA(CFS) = 290.14  
 FLOW VELOCITY(FEET/SEC.) = 5.58 FLOW DEPTH(FEET) = 4.16  
 TRAVEL TIME(MIN.) = 6.55 Tc(MIN.) = 107.90  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13303.00 = 37994.87 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	207.33	41.99	0.495	0.60( 0.51)	0.84	2302.7	31100.00
2	261.36	68.43	0.380	0.60( 0.50)	0.83	3982.0	13100.00
3	261.77	69.83	0.377	0.60( 0.50)	0.83	4060.6	13200.00
4	267.03	76.34	0.365	0.60( 0.50)	0.83	4322.5	13210.00
5	290.14	107.90	0.308	0.60( 0.49)	0.82	5417.4	13000.00
6	286.10	111.31	0.302	0.60( 0.49)	0.82	5437.4	13010.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE(CFS) = 290.14 Tc(MIN.) = 107.90  
 AREA-AVERAGED Fm(INCH/HR) = 0.49 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.82 EFFECTIVE AREA(ACRES) = 5417.37

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 107.90  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.308  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	0.40	0.60	1.000	-
USER-DEFINED	-	0.80	0.60	1.000	-
USER-DEFINED	-	1.40	0.60	0.100	-
USER-DEFINED	-	2.60	0.60	1.000	-
USER-DEFINED	-	2.20	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.834  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 SUBAREA AREA(ACRES) = 7.60 SUBAREA RUNOFF(CFS) = 0.35  
 EFFECTIVE AREA(ACRES) = 5424.97 AREA-AVERAGED Fm(INCH/HR) = 0.49  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.82  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 5445.0 PEAK FLOW RATE(CFS) = 290.14  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 107.90  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.308  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	3.10	0.60	1.000	-
USER-DEFINED	-	3.40	0.60	1.000	-
USER-DEFINED	-	0.50	0.60	1.000	-
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	3.60	0.60	0.100	-
USER-DEFINED	-	4.00	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.781  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 SUBAREA AREA(ACRES) = 14.80 SUBAREA RUNOFF(CFS) = 0.90  
 EFFECTIVE AREA(ACRES) = 5439.77 AREA-AVERAGED Fm(INCH/HR) = 0.49  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.82  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA (ACRES) = 5459.8 PEAK FLOW RATE (CFS) = 290.14  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 107.90

\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.308

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	14.60	0.60	1.000	-
USER-DEFINED	-	6.30	0.60	1.000	-
USER-DEFINED	-	3.70	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA (ACRES) = 24.60 SUBAREA RUNOFF (CFS) = 0.00

EFFECTIVE AREA (ACRES) = 5464.37 AREA-AVERAGED Fm (INCH/HR) = 0.49

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA (ACRES) = 5484.4 PEAK FLOW RATE (CFS) = 290.14

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 107.90

\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.308

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.50	0.60	1.000	-
USER-DEFINED	-	0.30	0.60	0.100	-
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	0.80	0.60	0.900	-
USER-DEFINED	-	1.60	0.60	1.000	-
USER-DEFINED	-	31.90	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.990

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA (ACRES) = 35.30 SUBAREA RUNOFF (CFS) = 0.10

EFFECTIVE AREA (ACRES) = 5499.67 AREA-AVERAGED Fm (INCH/HR) = 0.50

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA (ACRES) = 5519.6 PEAK FLOW RATE (CFS) = 290.14

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 107.90

\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.308

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.70	0.60	0.100	-
USER-DEFINED	-	0.30	0.60	1.000	-
USER-DEFINED	-	2.60	0.60	0.900	-
USER-DEFINED	-	5.50	0.60	1.000	-
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	0.20	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.830

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA (ACRES) = 10.50 SUBAREA RUNOFF (CFS) = 0.50

EFFECTIVE AREA (ACRES) = 5510.17 AREA-AVERAGED Fm (INCH/HR) = 0.50

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA (ACRES) = 5530.1 PEAK FLOW RATE (CFS) = 290.14

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 107.90

\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.308

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.30	0.60	0.900	-
USER-DEFINED	-	0.30	0.60	1.000	-
USER-DEFINED	-	0.20	0.60	0.100	-
USER-DEFINED	-	0.30	0.60	1.000	-
USER-DEFINED	-	6.50	0.60	0.900	-
USER-DEFINED	-	3.00	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.917

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA (ACRES) = 11.60 SUBAREA RUNOFF (CFS) = 0.27

EFFECTIVE AREA (ACRES) = 5521.77 AREA-AVERAGED Fm (INCH/HR) = 0.50

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA (ACRES) = 5541.8 PEAK FLOW RATE (CFS) = 290.14

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13303.00 TO NODE 13304.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 355.00 DOWNSTREAM(FEET) = 350.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 925.40 CHANNEL SLOPE = 0.0054  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00

\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.302

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	13.84	0.60	0.850	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.850

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 290.42

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.59

AVERAGE FLOW DEPTH(FEET) = 4.59 TRAVEL TIME(MIN.) = 3.36

Tc(MIN.) = 111.26

SUBAREA AREA(ACRES) = 13.84 SUBAREA RUNOFF(CFS) = 0.56

EFFECTIVE AREA(ACRES) = 5535.61 AREA-AVERAGED Fm(INCH/HR) = 0.50

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 5555.6 PEAK FLOW RATE(CFS) = 290.14

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 4.59 FLOW VELOCITY(FEET/SEC.) = 4.59

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13304.00 = 38920.27 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	207.33	45.64	0.474	0.60( 0.51)	0.85	2421.0	31100.00
2	261.36	71.88	0.373	0.60( 0.50)	0.83	4100.3	13100.00
3	261.77	73.28	0.371	0.60( 0.50)	0.83	4178.8	13200.00
4	267.03	79.77	0.359	0.60( 0.50)	0.83	4440.8	13210.00
5	290.14	111.26	0.302	0.60( 0.50)	0.83	5535.6	13000.00
6	286.10	114.68	0.296	0.60( 0.50)	0.83	5555.6	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 290.14 Tc(MIN.) = 111.26

AREA-AVERAGED Fm(INCH/HR) = 0.50 AREA-AVERAGED Fp(INCH/HR) = 0.60

AREA-AVERAGED Ap = 0.83 EFFECTIVE AREA(ACRES) = 5535.61

\*\*\*\*\*

FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 111.26

\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.302

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.80	0.60	1.000	-
USER-DEFINED	-	1.70	0.60	1.000	-
USER-DEFINED	-	9.40	0.60	1.000	-

USER-DEFINED	-	1.20	0.60	1.000	-
USER-DEFINED	-	0.10	0.60	0.900	-
USER-DEFINED	-	2.60	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 22.80 SUBAREA RUNOFF(CFS) = 0.00

EFFECTIVE AREA(ACRES) = 5558.41 AREA-AVERAGED Fm(INCH/HR) = 0.50

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 5578.4 PEAK FLOW RATE(CFS) = 290.14

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 111.26

\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.302

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	0.30	0.60	1.000	-
USER-DEFINED	-	0.20	0.60	0.900	-
USER-DEFINED	-	2.70	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.994

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 3.40 SUBAREA RUNOFF(CFS) = 0.01

EFFECTIVE AREA(ACRES) = 5561.81 AREA-AVERAGED Fm(INCH/HR) = 0.50

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 5581.8 PEAK FLOW RATE(CFS) = 290.14

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13304.00 TO NODE 13305.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 350.00 DOWNSTREAM(FEET) = 315.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 2966.27 CHANNEL SLOPE = 0.0118  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00

\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.287

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	27.39	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 290.14  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.15  
 AVERAGE FLOW DEPTH(FEET) = 3.96 TRAVEL TIME(MIN.) = 8.03  
 Tc(MIN.) = 119.29  
 SUBAREA AREA(ACRES) = 27.39 SUBAREA RUNOFF(CFS) = 0.00  
 EFFECTIVE AREA(ACRES) = 5589.20 AREA-AVERAGED Fm(INCH/HR) = 0.50  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 5609.2 PEAK FLOW RATE(CFS) = 290.14  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 3.96 FLOW VELOCITY(FEET/SEC.) = 6.15  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	207.33	54.39	0.425	0.60( 0.51)	0.85	2474.6	31100.00
2	261.36	80.12	0.358	0.60( 0.50)	0.83	4153.9	13100.00
3	261.77	81.54	0.356	0.60( 0.50)	0.83	4232.4	13200.00
4	267.03	87.97	0.344	0.60( 0.50)	0.83	4494.3	13210.00
5	290.14	119.29	0.287	0.60( 0.50)	0.83	5589.2	13000.00
6	286.10	122.76	0.284	0.60( 0.50)	0.83	5609.2	13010.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE(CFS) = 290.14 Tc(MIN.) = 119.29  
 AREA-AVERAGED Fm(INCH/HR) = 0.50 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.83 EFFECTIVE AREA(ACRES) = 5589.20

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 119.29  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.287  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	18.40	0.60	1.000	-
USER-DEFINED	-	1.20	0.60	1.000	-
USER-DEFINED	-	0.10	0.60	1.000	-
USER-DEFINED	-	26.60	0.60	1.000	-
USER-DEFINED	-	3.90	0.60	0.100	-
USER-DEFINED	-	3.00	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.934  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 SUBAREA AREA(ACRES) = 53.20 SUBAREA RUNOFF(CFS) = 0.91  
 EFFECTIVE AREA(ACRES) = 5642.40 AREA-AVERAGED Fm(INCH/HR) = 0.50  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 5662.4 PEAK FLOW RATE(CFS) = 290.14

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 119.29  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.287  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.10	0.60	1.000	-
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	14.00	0.60	1.000	-
USER-DEFINED	-	4.30	0.60	0.100	-
USER-DEFINED	-	5.30	0.60	1.000	-
USER-DEFINED	-	2.70	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.860  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 SUBAREA AREA(ACRES) = 27.60 SUBAREA RUNOFF(CFS) = 1.00  
 EFFECTIVE AREA(ACRES) = 5670.00 AREA-AVERAGED Fm(INCH/HR) = 0.50  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 5690.0 PEAK FLOW RATE(CFS) = 290.14  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 119.29  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.287  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	3.20	0.60	1.000	-
USER-DEFINED	-	6.10	0.60	1.000	-
USER-DEFINED	-	7.50	0.60	0.900	-
USER-DEFINED	-	5.40	0.60	1.000	-
USER-DEFINED	-	1.60	0.60	1.000	-
USER-DEFINED	-	1.90	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.971  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 SUBAREA AREA(ACRES) = 25.70 SUBAREA RUNOFF(CFS) = 0.19  
 EFFECTIVE AREA(ACRES) = 5695.70 AREA-AVERAGED Fm(INCH/HR) = 0.50  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 5715.7 PEAK FLOW RATE(CFS) = 290.14  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 119.29

\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.287

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	2.00	0.60	0.100	-
USER-DEFINED	-	3.70	0.60	1.000	-
USER-DEFINED	-	2.10	0.60	1.000	-
USER-DEFINED	-	2.60	0.60	0.900	-
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	0.10	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.807

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 10.70 SUBAREA RUNOFF(CFS) = 0.53

EFFECTIVE AREA(ACRES) = 5706.40 AREA-AVERAGED Fm(INCH/HR) = 0.50

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 5726.4 PEAK FLOW RATE(CFS) = 290.14

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 119.29

\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.287

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.50	0.60	1.000	-
USER-DEFINED	-	8.20	0.60	0.900	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.906

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 8.70 SUBAREA RUNOFF(CFS) = 0.21

EFFECTIVE AREA(ACRES) = 5715.10 AREA-AVERAGED Fm(INCH/HR) = 0.50

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 5735.1 PEAK FLOW RATE(CFS) = 290.14

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<

PEAK FLOWRATE TABLE FILE NAME: 3A02EVRL.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	253.57	16.02	0.60( 0.26)	0.43	423.9	120.00
2	249.96	16.56	0.60( 0.26)	0.43	431.7	110.00
3	195.31	25.12	0.60( 0.25)	0.42	498.0	100.00
4	160.80	32.93	0.60( 0.26)	0.43	510.2	150.00
TOTAL AREA(ACRES) =			510.2			

\*\*\*\*\*

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	207.33	54.39	0.425	0.60( 0.51)	0.85	2600.5	31100.00
2	261.36	80.12	0.358	0.60( 0.50)	0.84	4279.8	13100.00
3	261.77	81.54	0.356	0.60( 0.50)	0.84	4358.3	13200.00
4	267.03	87.97	0.344	0.60( 0.50)	0.84	4620.2	13210.00
5	290.14	119.29	0.287	0.60( 0.50)	0.83	5715.1	13000.00
6	286.10	122.76	0.284	0.60( 0.50)	0.83	5735.1	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	253.57	16.02	0.898	0.60( 0.26)	0.43	423.9	120.00
2	249.96	16.56	0.880	0.60( 0.26)	0.43	431.7	110.00
3	195.31	25.12	0.660	0.60( 0.25)	0.42	498.0	100.00
4	160.80	32.93	0.563	0.60( 0.26)	0.43	510.2	150.00

LONGEST FLOWPATH FROM NODE 150.00 TO NODE 13305.00 = 9867.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	460.90	16.02	0.898	0.60( 0.42)	0.70	1189.8	120.00
2	457.29	16.56	0.880	0.60( 0.42)	0.70	1223.6	110.00
3	402.64	25.12	0.660	0.60( 0.44)	0.73	1698.9	100.00
4	327.05	32.93	0.563	0.60( 0.45)	0.75	2084.7	150.00
5	328.74	54.39	0.425	0.60( 0.47)	0.78	3110.7	31100.00
6	363.59	80.12	0.358	0.60( 0.48)	0.79	4790.0	13100.00
7	363.26	81.54	0.356	0.60( 0.48)	0.79	4868.5	13200.00
8	365.16	87.97	0.344	0.60( 0.48)	0.80	5130.4	13210.00
9	372.15	119.29	0.287	0.60( 0.48)	0.80	6225.3	13000.00
10	367.04	122.76	0.284	0.60( 0.48)	0.80	6245.3	13010.00
TOTAL AREA(ACRES) =			6245.3				

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 460.90 Tc(MIN.) = 16.018

EFFECTIVE AREA(ACRES) = 1189.76 AREA-AVERAGED Fm(INCH/HR) = 0.42

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.79

TOTAL AREA(ACRES) = 6245.3

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

\*\*\*\*\*



FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13305.00 TO NODE 13306.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 315.00 DOWNSTREAM(FEET) = 245.50  
CHANNEL LENGTH THRU SUBAREA(FEET) = 4408.41 CHANNEL SLOPE = 0.0158  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.654

SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 68.77 0.60 0.850 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.850  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 465.38  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.72  
AVERAGE FLOW DEPTH(FEET) = 4.48 TRAVEL TIME(MIN.) = 9.52  
Tc(MIN.) = 25.54

SUBAREA AREA(ACRES) = 68.77 SUBAREA RUNOFF(CFS) = 8.92  
EFFECTIVE AREA(ACRES) = 1258.53 AREA-AVERAGED Fm(INCH/HR) = 0.43  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.71  
TOTAL AREA(ACRES) = 6314.1 PEAK FLOW RATE(CFS) = 460.90  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 4.47 FLOW VELOCITY(FEET/SEC.) = 7.70  
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13306.00 = 46294.95 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	460.90	25.54	0.654	0.60( 0.43)	0.71	1258.5	120.00
2	457.29	26.10	0.646	0.60( 0.43)	0.71	1292.4	110.00
3	402.64	34.96	0.547	0.60( 0.44)	0.73	1767.7	100.00
4	327.05	43.32	0.487	0.60( 0.45)	0.75	2153.4	150.00
5	328.74	64.75	0.386	0.60( 0.47)	0.79	3179.4	31100.00
6	363.59	90.24	0.340	0.60( 0.48)	0.79	4858.7	13100.00
7	363.26	91.66	0.337	0.60( 0.48)	0.80	4937.3	13200.00
8	365.16	98.08	0.325	0.60( 0.48)	0.80	5199.2	13210.00
9	372.15	129.36	0.278	0.60( 0.48)	0.80	6294.1	13000.00
10	367.04	132.85	0.274	0.60( 0.48)	0.80	6314.1	13010.00

NEW PEAK FLOW DATA ARE:  
PEAK FLOW RATE(CFS) = 460.90 Tc(MIN.) = 25.54  
AREA-AVERAGED Fm(INCH/HR) = 0.43 AREA-AVERAGED Fp(INCH/HR) = 0.60  
AREA-AVERAGED Ap = 0.71 EFFECTIVE AREA(ACRES) = 1258.53

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

\*\*\*\*\*  
MAINLINE Tc(MIN.) = 25.54  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.654  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 21.50 0.60 1.000 -  
USER-DEFINED - 15.30 0.60 0.100 -  
USER-DEFINED - 0.80 0.60 1.000 -  
USER-DEFINED - 0.60 0.60 1.000 -  
USER-DEFINED - 8.00 0.60 0.900 -  
USER-DEFINED - 0.10 0.60 1.000 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.685  
SUBAREA AREA(ACRES) = 46.30 SUBAREA RUNOFF(CFS) = 10.12  
EFFECTIVE AREA(ACRES) = 1304.83 AREA-AVERAGED Fm(INCH/HR) = 0.43  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.71  
TOTAL AREA(ACRES) = 6360.4 PEAK FLOW RATE(CFS) = 460.90  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

\*\*\*\*\*  
MAINLINE Tc(MIN.) = 25.54  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.654  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 43.30 0.60 1.000 -  
USER-DEFINED - 4.90 0.60 0.100 -  
USER-DEFINED - 5.70 0.60 1.000 -  
USER-DEFINED - 0.50 0.60 1.000 -  
USER-DEFINED - 1.10 0.60 0.850 -  
USER-DEFINED - 3.10 0.60 0.900 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.917  
SUBAREA AREA(ACRES) = 58.60 SUBAREA RUNOFF(CFS) = 5.49  
EFFECTIVE AREA(ACRES) = 1363.43 AREA-AVERAGED Fm(INCH/HR) = 0.43  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.72  
TOTAL AREA(ACRES) = 6419.0 PEAK FLOW RATE(CFS) = 460.90  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

\*\*\*\*\*  
MAINLINE Tc(MIN.) = 25.54  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.654  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 6.80 0.60 1.000 -  
USER-DEFINED - 0.70 0.60 1.000 -  
USER-DEFINED - 1.10 0.60 0.100 -  
USER-DEFINED - 0.50 0.60 1.000 -

USER-DEFINED - 0.10 0.60 1.000 -  
 USER-DEFINED - 0.50 0.60 0.850 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.890  
 SUBAREA AREA(ACRES) = 9.70 SUBAREA RUNOFF(CFS) = 1.05  
 EFFECTIVE AREA(ACRES) = 1373.13 AREA-AVERAGED Fm(INCH/HR) = 0.43  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.72  
 TOTAL AREA(ACRES) = 6428.7 PEAK FLOW RATE(CFS) = 460.90  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 25.54  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.654  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 2.20 0.60 0.900 -  
 USER-DEFINED - 0.10 0.60 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.904  
 SUBAREA AREA(ACRES) = 2.30 SUBAREA RUNOFF(CFS) = 0.23  
 EFFECTIVE AREA(ACRES) = 1375.43 AREA-AVERAGED Fm(INCH/HR) = 0.43  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.72  
 TOTAL AREA(ACRES) = 6431.0 PEAK FLOW RATE(CFS) = 460.90  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13306.00 TO NODE 13307.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 245.50 DOWNSTREAM(FEET) = 220.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1543.21 CHANNEL SLOPE = 0.0165  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
 CHANNEL FLOW THRU SUBAREA(CFS) = 460.90  
 FLOW VELOCITY(FEET/SEC.) = 7.84 FLOW DEPTH(FEET) = 4.43  
 TRAVEL TIME(MIN.) = 3.28 Tc(MIN.) = 28.82  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13307.00 = 47838.16 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	460.90	28.82	0.605	0.60( 0.43)	0.72	1375.4	120.00
2	457.29	29.39	0.596	0.60( 0.43)	0.72	1409.3	110.00
3	402.64	38.36	0.519	0.60( 0.44)	0.74	1884.6	100.00
4	327.05	46.90	0.467	0.60( 0.45)	0.76	2270.3	150.00
5	328.74	68.32	0.380	0.60( 0.47)	0.79	3296.3	31100.00
6	363.59	93.73	0.333	0.60( 0.48)	0.80	4975.6	13100.00
7	363.26	95.14	0.331	0.60( 0.48)	0.80	5054.2	13200.00
8	365.16	101.55	0.319	0.60( 0.48)	0.80	5316.1	13210.00
9	372.15	132.82	0.274	0.60( 0.48)	0.80	6411.0	13000.00
10	367.04	136.32	0.271	0.60( 0.48)	0.80	6431.0	13010.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE(CFS) = 460.90 Tc(MIN.) = 28.82  
 AREA-AVERAGED Fm(INCH/HR) = 0.43 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.72 EFFECTIVE AREA(ACRES) = 1375.43

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13307.00 TO NODE 13307.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 28.82  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.605  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 0.20 0.60 0.100 -  
 USER-DEFINED - 0.10 0.60 1.000 -  
 USER-DEFINED - 0.20 0.60 1.000 -  
 USER-DEFINED - 3.70 0.60 1.000 -  
 USER-DEFINED - 0.30 0.60 0.100 -  
 USER-DEFINED - 3.20 0.60 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.942  
 SUBAREA AREA(ACRES) = 7.70 SUBAREA RUNOFF(CFS) = 0.28  
 EFFECTIVE AREA(ACRES) = 1383.13 AREA-AVERAGED Fm(INCH/HR) = 0.43  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.72  
 TOTAL AREA(ACRES) = 6438.7 PEAK FLOW RATE(CFS) = 460.90  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13307.00 TO NODE 13307.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 28.82  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.605  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 3.60 0.60 1.000 -  
 USER-DEFINED - 1.90 0.60 1.000 -  
 USER-DEFINED - 0.60 0.60 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 6.10 SUBAREA RUNOFF(CFS) = 0.03  
 EFFECTIVE AREA(ACRES) = 1389.23 AREA-AVERAGED Fm(INCH/HR) = 0.43  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.72  
 TOTAL AREA(ACRES) = 6444.8 PEAK FLOW RATE(CFS) = 460.90  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13307.00 TO NODE 13308.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 220.00 DOWNSTREAM(FEET) = 212.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 925.62 CHANNEL SLOPE = 0.0086

CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA (CFS) = 460.90  
FLOW VELOCITY (FEET/SEC.) = 6.15 FLOW DEPTH (FEET) = 5.00  
TRAVEL TIME (MIN.) = 2.51 Tc (MIN.) = 31.33  
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13308.00 = 48763.78 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	460.90	31.33	0.576	0.60 ( 0.43)	0.72	1389.2	120.00
2	457.29	31.90	0.572	0.60 ( 0.43)	0.72	1423.1	110.00
3	402.64	40.96	0.501	0.60 ( 0.44)	0.74	1898.4	100.00
4	327.05	49.63	0.451	0.60 ( 0.46)	0.76	2284.1	150.00
5	328.74	71.05	0.375	0.60 ( 0.47)	0.79	3310.1	31100.00
6	363.59	96.39	0.328	0.60 ( 0.48)	0.80	4989.4	13100.00
7	363.26	97.80	0.326	0.60 ( 0.48)	0.80	5068.0	13200.00
8	365.16	104.21	0.314	0.60 ( 0.48)	0.80	5329.9	13210.00
9	372.15	135.47	0.272	0.60 ( 0.48)	0.80	6424.8	13000.00
10	367.04	138.98	0.269	0.60 ( 0.48)	0.80	6444.8	13010.00

NEW PEAK FLOW DATA ARE:  
PEAK FLOW RATE (CFS) = 460.90 Tc (MIN.) = 31.33  
AREA-AVERAGED Fm (INCH/HR) = 0.43 AREA-AVERAGED Fp (INCH/HR) = 0.60  
AREA-AVERAGED Ap = 0.72 EFFECTIVE AREA (ACRES) = 1389.23

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 31.33  
\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.576  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.10	0.60	1.000	-
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	5.00	0.60	1.000	-
USER-DEFINED	-	3.20	0.60	0.100	-
USER-DEFINED	-	0.10	0.60	1.000	-
USER-DEFINED	-	0.90	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.697  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
SUBAREA AREA (ACRES) = 9.50 SUBAREA RUNOFF (CFS) = 1.49  
EFFECTIVE AREA (ACRES) = 1398.73 AREA-AVERAGED Fm (INCH/HR) = 0.43  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.72  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
TOTAL AREA (ACRES) = 6454.3 PEAK FLOW RATE (CFS) = 460.90  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 31.33  
\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.576  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.30	0.60	0.200	-
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	1.00	0.60	1.000	-
USER-DEFINED	-	41.90	0.60	0.100	-
USER-DEFINED	-	7.20	0.60	1.000	-
USER-DEFINED	-	25.00	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.498  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
SUBAREA AREA (ACRES) = 75.60 SUBAREA RUNOFF (CFS) = 19.68  
EFFECTIVE AREA (ACRES) = 1474.33 AREA-AVERAGED Fm (INCH/HR) = 0.43  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.71  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
TOTAL AREA (ACRES) = 6529.9 PEAK FLOW RATE (CFS) = 460.90  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 31.33  
\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.576  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.10	0.60	0.850	-
USER-DEFINED	-	0.90	0.60	1.000	-
USER-DEFINED	-	0.30	0.60	0.600	-
USER-DEFINED	-	13.20	0.60	1.000	-
USER-DEFINED	-	0.50	0.60	0.200	-
USER-DEFINED	-	0.60	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.966  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
SUBAREA AREA (ACRES) = 15.60 SUBAREA RUNOFF (CFS) = 0.28  
EFFECTIVE AREA (ACRES) = 1489.93 AREA-AVERAGED Fm (INCH/HR) = 0.43  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.71  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
TOTAL AREA (ACRES) = 6545.5 PEAK FLOW RATE (CFS) = 460.90  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 31.33  
\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.576

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	33.90	0.60	0.100	-
USER-DEFINED	-	17.60	0.60	1.000	-
USER-DEFINED	-	16.80	0.60	1.000	-
USER-DEFINED	-	0.60	0.60	0.200	-
USER-DEFINED	-	1.50	0.60	0.400	-
USER-DEFINED	-	10.00	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.603  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
SUBAREA AREA(ACRES) = 80.40 SUBAREA RUNOFF(CFS) = 16.54  
EFFECTIVE AREA(ACRES) = 1570.33 AREA-AVERAGED Fm(INCH/HR) = 0.42  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.71  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
TOTAL AREA(ACRES) = 6625.9 PEAK FLOW RATE(CFS) = 460.90  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 31.33  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.576  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.30	0.60	0.600	-
USER-DEFINED	-	0.70	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.880  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
SUBAREA AREA(ACRES) = 1.00 SUBAREA RUNOFF(CFS) = 0.06  
EFFECTIVE AREA(ACRES) = 1571.33 AREA-AVERAGED Fm(INCH/HR) = 0.42  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.71  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
TOTAL AREA(ACRES) = 6626.9 PEAK FLOW RATE(CFS) = 460.90  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 31.33  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.576  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.30	0.60	1.000	-
USER-DEFINED	-	0.80	0.60	1.000	-
USER-DEFINED	-	0.50	0.60	1.000	-

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	0.30	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
SUBAREA AREA(ACRES) = 2.10 SUBAREA RUNOFF(CFS) = 0.00  
EFFECTIVE AREA(ACRES) = 1573.43 AREA-AVERAGED Fm(INCH/HR) = 0.42  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.71  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
TOTAL AREA(ACRES) = 6629.0 PEAK FLOW RATE(CFS) = 460.90  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 31.33  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.576  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.20	0.60	1.000	-
USER-DEFINED	-	0.50	0.60	1.000	-
USER-DEFINED	-	1.70	0.60	0.850	-
USER-DEFINED	-	7.20	0.60	1.000	-
USER-DEFINED	-	1.00	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.978  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
SUBAREA AREA(ACRES) = 11.60 SUBAREA RUNOFF(CFS) = 0.13  
EFFECTIVE AREA(ACRES) = 1585.03 AREA-AVERAGED Fm(INCH/HR) = 0.43  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.71  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
TOTAL AREA(ACRES) = 6640.6 PEAK FLOW RATE(CFS) = 460.90  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: RI02EV29.DNA  
MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap (ACRES)	Ae (ACRES)	HEADWATER NODE
1	1370.47	17.96	0.60( 0.45)	0.75	1796.4	200.00
2	1313.52	35.52	0.60( 0.46)	0.77	3930.1	300.00

3	1260.41	46.85	0.60	( 0.47)	0.79	5552.0	50300.00
4	1037.25	64.30	0.60	( 0.49)	0.82	7639.0	50100.00
5	913.28	99.83	0.60	( 0.53)	0.89	12560.3	40100.00
6	931.96	112.51	0.60	( 0.54)	0.90	14291.8	11831.00
7	991.02	136.30	0.60	( 0.55)	0.92	17988.0	11530.00
8	1061.51	156.05	0.60	( 0.56)	0.94	22143.9	11000.00
9	1156.57	178.62	0.60	( 0.57)	0.95	28950.3	10850.00
10	1070.62	194.15	0.60	( 0.57)	0.95	32270.1	11220.00
11	1009.09	205.47	0.60	( 0.57)	0.96	34022.1	10910.00
12	847.62	245.77	0.60	( 0.58)	0.96	40603.8	12410.00
13	802.41	278.71	0.60	( 0.58)	0.96	46689.7	12261.00
14	787.42	291.47	0.60	( 0.58)	0.96	48176.3	10410.00
15	772.65	303.65	0.60	( 0.58)	0.97	49278.2	12101.10
16	739.25	331.13	0.60	( 0.58)	0.97	51656.3	10200.00
17	722.40	344.51	0.60	( 0.58)	0.97	52594.5	12010.00
18	676.71	373.59	0.60	( 0.58)	0.97	53268.2	10210.00
19	615.08	422.73	0.60	( 0.58)	0.97	53767.3	12000.00
20	572.99	492.27	0.60	( 0.58)	0.97	54352.1	10100.00

TOTAL AREA (ACRES) = 54352.1

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<<  
=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1370.47	17.96	0.60 ( 0.45)	0.75	1796.4	200.00
2	1313.52	35.52	0.60 ( 0.46)	0.77	3930.1	300.00
3	1260.41	46.85	0.60 ( 0.47)	0.79	5552.0	50300.00
4	1037.25	64.30	0.60 ( 0.49)	0.82	7639.0	50100.00
5	913.28	99.83	0.60 ( 0.53)	0.89	12560.3	40100.00
6	931.96	112.51	0.60 ( 0.54)	0.90	14291.8	11831.00
7	991.02	136.30	0.60 ( 0.55)	0.92	17988.0	11530.00
8	1061.51	156.05	0.60 ( 0.56)	0.94	22143.9	11000.00
9	1156.57	178.62	0.60 ( 0.57)	0.95	28950.3	10850.00
10	1070.62	194.15	0.60 ( 0.57)	0.95	32270.1	11220.00
11	1009.09	205.47	0.60 ( 0.57)	0.96	34022.1	10910.00
12	847.62	245.77	0.60 ( 0.58)	0.96	40603.8	12410.00
13	802.41	278.71	0.60 ( 0.58)	0.96	46689.7	12261.00
14	787.42	291.47	0.60 ( 0.58)	0.96	48176.3	10410.00
15	772.65	303.65	0.60 ( 0.58)	0.97	49278.2	12101.10
16	739.25	331.13	0.60 ( 0.58)	0.97	51656.3	10200.00
17	722.40	344.51	0.60 ( 0.58)	0.97	52594.5	12010.00
18	676.71	373.59	0.60 ( 0.58)	0.97	53268.2	10210.00
19	615.08	422.73	0.60 ( 0.58)	0.97	53767.3	12000.00
20	572.99	492.27	0.60 ( 0.58)	0.97	54352.1	10100.00

TOTAL AREA (ACRES) = 54352.1

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12904.00 TO NODE 13308.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<<  
=====

ELEVATION DATA: UPSTREAM (FEET) = 213.00 DOWNSTREAM (FEET) = 212.00

CHANNEL LENGTH THRU SUBAREA (FEET) = 1389.52 CHANNEL SLOPE = 0.0007  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA (CFS) = 1370.47  
FLOW VELOCITY (FEET/SEC.) = 3.94 FLOW DEPTH (FEET) = 10.77  
TRAVEL TIME (MIN.) = 5.88 Tc (MIN.) = 23.84  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118090.66 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1370.47	23.84	0.686	0.60 ( 0.45)	0.75	1796.4	200.00
2	1313.52	41.46	0.498	0.60 ( 0.46)	0.77	3930.1	300.00
3	1260.41	52.85	0.434	0.60 ( 0.47)	0.79	5552.0	50300.00
4	1037.25	70.60	0.376	0.60 ( 0.49)	0.82	7639.0	50100.00
5	913.28	106.33	0.311	0.60 ( 0.53)	0.89	12560.3	40100.00
6	931.96	118.98	0.288	0.60 ( 0.54)	0.90	14291.8	11831.00
7	991.02	142.67	0.266	0.60 ( 0.55)	0.92	17988.0	11530.00
8	1061.51	162.31	0.248	0.60 ( 0.56)	0.94	22143.9	11000.00
9	1156.57	184.75	0.231	0.60 ( 0.57)	0.95	28950.3	10850.00
10	1070.62	200.40	0.226	0.60 ( 0.57)	0.95	32270.1	11220.00
11	1009.09	211.82	0.222	0.60 ( 0.57)	0.96	34022.1	10910.00
12	847.62	252.40	0.210	0.60 ( 0.58)	0.96	40603.8	12410.00
13	802.41	285.43	0.200	0.60 ( 0.58)	0.96	46689.7	12261.00
14	787.42	298.22	0.197	0.60 ( 0.58)	0.96	48176.3	10410.00
15	772.65	310.43	0.193	0.60 ( 0.58)	0.97	49278.2	12101.10
16	739.25	337.99	0.185	0.60 ( 0.58)	0.97	51656.3	10200.00
17	722.40	351.40	0.181	0.60 ( 0.58)	0.97	52594.5	12010.00
18	676.71	380.61	0.176	0.60 ( 0.58)	0.97	53268.2	10210.00
19	615.08	429.91	0.170	0.60 ( 0.58)	0.97	53767.3	12000.00
20	572.99	499.58	0.162	0.60 ( 0.58)	0.97	54352.1	10100.00

NEW PEAK FLOW DATA ARE:  
PEAK FLOW RATE (CFS) = 1370.47 Tc (MIN.) = 23.84  
AREA-AVERAGED Fm (INCH/HR) = 0.45 AREA-AVERAGED Fp (INCH/HR) = 0.60  
AREA-AVERAGED Ap = 0.75 EFFECTIVE AREA (ACRES) = 1796.44

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13307.00 TO NODE 13308.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<<  
=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1370.47	23.84	0.686	0.60 ( 0.45)	0.75	1796.4	200.00
2	1313.52	41.46	0.498	0.60 ( 0.46)	0.77	3930.1	300.00
3	1260.41	52.85	0.434	0.60 ( 0.47)	0.79	5552.0	50300.00
4	1037.25	70.60	0.376	0.60 ( 0.49)	0.82	7639.0	50100.00
5	913.28	106.33	0.311	0.60 ( 0.53)	0.89	12560.3	40100.00
6	931.96	118.98	0.288	0.60 ( 0.54)	0.90	14291.8	11831.00
7	991.02	142.67	0.266	0.60 ( 0.55)	0.92	17988.0	11530.00
8	1061.51	162.31	0.248	0.60 ( 0.56)	0.94	22143.9	11000.00
9	1156.57	184.75	0.231	0.60 ( 0.57)	0.95	28950.3	10850.00
10	1070.62	200.40	0.226	0.60 ( 0.57)	0.95	32270.1	11220.00
11	1009.09	211.82	0.222	0.60 ( 0.57)	0.96	34022.1	10910.00
12	847.62	252.40	0.210	0.60 ( 0.58)	0.96	40603.8	12410.00
13	802.41	285.43	0.200	0.60 ( 0.58)	0.96	46689.7	12261.00

14	787.42	298.22	0.197	0.60 ( 0.58)	0.96	48176.3	10410.00
15	772.65	310.43	0.193	0.60 ( 0.58)	0.97	49278.2	12101.10
16	739.25	337.99	0.185	0.60 ( 0.58)	0.97	51656.3	10200.00
17	722.40	351.40	0.181	0.60 ( 0.58)	0.97	52594.5	12010.00
18	676.71	380.61	0.176	0.60 ( 0.58)	0.97	53268.2	10210.00
19	615.08	429.91	0.170	0.60 ( 0.58)	0.97	53767.3	12000.00
20	572.99	499.58	0.162	0.60 ( 0.58)	0.97	54352.1	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118090.66 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	460.90	31.33	0.576	0.60 ( 0.43)	0.71	1585.0	120.00
2	457.29	31.90	0.572	0.60 ( 0.43)	0.71	1618.9	110.00
3	402.64	40.96	0.501	0.60 ( 0.44)	0.73	2094.2	100.00
4	327.05	49.63	0.451	0.60 ( 0.45)	0.75	2479.9	150.00
5	328.74	71.05	0.375	0.60 ( 0.47)	0.78	3505.9	31100.00
6	363.59	96.39	0.328	0.60 ( 0.47)	0.79	5185.2	13100.00
7	363.26	97.80	0.326	0.60 ( 0.47)	0.79	5263.8	13200.00
8	365.16	104.21	0.314	0.60 ( 0.47)	0.79	5525.7	13210.00
9	372.15	135.47	0.272	0.60 ( 0.48)	0.79	6620.6	13000.00
10	367.04	138.98	0.269	0.60 ( 0.48)	0.79	6640.6	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13308.00 = 48763.78 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1831.37	23.84	0.686	0.60 ( 0.44)	0.73	3002.4	200.00
2	1807.16	31.33	0.576	0.60 ( 0.44)	0.74	4288.7	120.00
3	1801.70	31.90	0.572	0.60 ( 0.44)	0.74	4391.8	110.00
4	1717.79	40.96	0.501	0.60 ( 0.45)	0.75	5963.5	100.00
5	1711.79	41.46	0.498	0.60 ( 0.45)	0.75	6046.6	300.00
6	1602.46	49.63	0.451	0.60 ( 0.46)	0.77	7573.8	150.00
7	1587.71	52.85	0.434	0.60 ( 0.47)	0.78	8186.1	50300.00
8	1365.96	70.60	0.376	0.60 ( 0.49)	0.81	11123.4	50100.00
9	1364.43	71.05	0.375	0.60 ( 0.49)	0.81	11207.1	31100.00
10	1311.36	96.39	0.328	0.60 ( 0.51)	0.85	16376.2	13100.00
11	1306.14	97.80	0.326	0.60 ( 0.51)	0.85	16648.8	13200.00
12	1285.79	104.21	0.314	0.60 ( 0.51)	0.86	17794.1	13210.00
13	1278.91	106.33	0.311	0.60 ( 0.52)	0.86	18160.3	40100.00
14	1300.42	118.98	0.288	0.60 ( 0.52)	0.87	20334.8	11831.00
15	1345.22	135.47	0.272	0.60 ( 0.53)	0.88	23485.2	13000.00
16	1348.87	138.98	0.269	0.60 ( 0.53)	0.88	24053.3	13010.00
17	1353.53	142.67	0.266	0.60 ( 0.53)	0.89	24628.5	11530.00
18	1399.88	162.31	0.248	0.60 ( 0.54)	0.90	28784.4	11000.00
19	1471.28	184.75	0.231	0.60 ( 0.55)	0.92	35590.8	10850.00
20	1378.92	200.40	0.226	0.60 ( 0.56)	0.93	38910.6	11220.00
21	1312.72	211.82	0.222	0.60 ( 0.56)	0.93	40662.7	10910.00
22	1134.63	252.40	0.210	0.60 ( 0.56)	0.94	47244.3	12410.00
23	1075.89	285.43	0.200	0.60 ( 0.57)	0.94	53330.2	12261.00
24	1055.67	298.22	0.197	0.60 ( 0.57)	0.94	54816.8	10410.00
25	1035.89	310.43	0.193	0.60 ( 0.57)	0.95	55918.8	12101.10
26	991.21	337.99	0.185	0.60 ( 0.57)	0.95	58296.8	10200.00
27	968.87	351.40	0.181	0.60 ( 0.57)	0.95	59235.1	12010.00
28	916.37	380.61	0.176	0.60 ( 0.57)	0.95	59908.8	10210.00
29	846.89	429.91	0.170	0.60 ( 0.57)	0.95	60407.9	12000.00
30	793.71	499.58	0.162	0.60 ( 0.57)	0.95	60992.6	10100.00

TOTAL AREA (ACRES) = 60992.6

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 1831.37 Tc (MIN.) = 23.838  
EFFECTIVE AREA (ACRES) = 3002.41 AREA-AVERAGED Fm (INCH/HR) = 0.44  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.73  
TOTAL AREA (ACRES) = 60992.6  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118090.66 FEET.

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 60992.6 TC (MIN.) = 23.84  
EFFECTIVE AREA (ACRES) = 3002.41 AREA-AVERAGED Fm (INCH/HR) = 0.44  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.734  
PEAK FLOW RATE (CFS) = 1831.37

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1831.37	23.84	0.686	0.60 ( 0.44)	0.73	3002.4	200.00
2	1807.16	31.33	0.576	0.60 ( 0.44)	0.74	4288.7	120.00
3	1801.70	31.90	0.572	0.60 ( 0.44)	0.74	4391.8	110.00
4	1717.79	40.96	0.501	0.60 ( 0.45)	0.75	5963.5	100.00
5	1711.79	41.46	0.498	0.60 ( 0.45)	0.75	6046.6	300.00
6	1602.46	49.63	0.451	0.60 ( 0.46)	0.77	7573.8	150.00
7	1587.71	52.85	0.434	0.60 ( 0.47)	0.78	8186.1	50300.00
8	1365.96	70.60	0.376	0.60 ( 0.49)	0.81	11123.4	50100.00
9	1364.43	71.05	0.375	0.60 ( 0.49)	0.81	11207.1	31100.00
10	1311.36	96.39	0.328	0.60 ( 0.51)	0.85	16376.2	13100.00
11	1306.14	97.80	0.326	0.60 ( 0.51)	0.85	16648.8	13200.00
12	1285.79	104.21	0.314	0.60 ( 0.51)	0.86	17794.1	13210.00
13	1278.91	106.33	0.311	0.60 ( 0.52)	0.86	18160.3	40100.00
14	1300.42	118.98	0.288	0.60 ( 0.52)	0.87	20334.8	11831.00
15	1345.22	135.47	0.272	0.60 ( 0.53)	0.88	23485.2	13000.00
16	1348.87	138.98	0.269	0.60 ( 0.53)	0.88	24053.3	13010.00
17	1353.53	142.67	0.266	0.60 ( 0.53)	0.89	24628.5	11530.00
18	1399.88	162.31	0.248	0.60 ( 0.54)	0.90	28784.4	11000.00
19	1471.28	184.75	0.231	0.60 ( 0.55)	0.92	35590.8	10850.00
20	1378.92	200.40	0.226	0.60 ( 0.56)	0.93	38910.6	11220.00
21	1312.72	211.82	0.222	0.60 ( 0.56)	0.93	40662.7	10910.00
22	1134.63	252.40	0.210	0.60 ( 0.56)	0.94	47244.3	12410.00
23	1075.89	285.43	0.200	0.60 ( 0.57)	0.94	53330.2	12261.00
24	1055.67	298.22	0.197	0.60 ( 0.57)	0.94	54816.8	10410.00
25	1035.89	310.43	0.193	0.60 ( 0.57)	0.95	55918.8	12101.10
26	991.21	337.99	0.185	0.60 ( 0.57)	0.95	58296.8	10200.00
27	968.87	351.40	0.181	0.60 ( 0.57)	0.95	59235.1	12010.00
28	916.37	380.61	0.176	0.60 ( 0.57)	0.95	59908.8	10210.00
29	846.89	429.91	0.170	0.60 ( 0.57)	0.95	60407.9	12000.00
30	793.71	499.58	0.162	0.60 ( 0.57)	0.95	60992.6	10100.00

END OF RATIONAL METHOD ANALYSIS



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA 92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S34- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 2-YR RM EV APRIL 2019 ROKAMOTO \*  
\*\*\*\*\*

FILE NAME: RI02EV34.DAT  
TIME/DATE OF STUDY: 17:08 04/08/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 2.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 1.819
- 2) 10.00; 1.213
- 3) 15.00; 0.930
- 4) 20.00; 0.765
- 5) 25.00; 0.661
- 6) 30.00; 0.587
- 7) 40.00; 0.505
- 8) 50.00; 0.448
- 9) 60.00; 0.390
- 10) 90.00; 0.336
- 11) 120.00; 0.280
- 12) 180.00; 0.226
- 13) 360.00; 0.170
- 14) 1200.00; 0.080

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI02EV33.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1831.37	23.84	0.60 ( 0.44)	0.73	3002.4	200.00
2	1717.79	40.96	0.60 ( 0.45)	0.75	5963.5	100.00
3	1602.46	49.63	0.60 ( 0.46)	0.77	7573.8	150.00
4	1365.96	70.60	0.60 ( 0.49)	0.81	11123.4	50100.00
5	1311.36	96.39	0.60 ( 0.51)	0.85	16376.2	13100.00
6	1300.42	118.98	0.60 ( 0.52)	0.87	20334.8	11831.00
7	1353.53	142.67	0.60 ( 0.53)	0.89	24628.5	11530.00
8	1399.88	162.31	0.60 ( 0.54)	0.90	28784.4	11000.00
9	1471.28	184.75	0.60 ( 0.55)	0.92	35590.8	10850.00
10	1378.92	200.40	0.60 ( 0.56)	0.93	38910.6	11220.00
11	1312.72	211.82	0.60 ( 0.56)	0.93	40662.7	10910.00
12	1134.63	252.40	0.60 ( 0.56)	0.94	47244.3	12410.00
13	1075.89	285.43	0.60 ( 0.57)	0.94	53330.2	12261.00
14	1055.67	298.22	0.60 ( 0.57)	0.94	54816.8	10410.00
15	1035.89	310.43	0.60 ( 0.57)	0.95	55918.8	12101.10
16	991.21	337.99	0.60 ( 0.57)	0.95	58296.8	10200.00
17	968.87	351.40	0.60 ( 0.57)	0.95	59235.1	12010.00
18	916.37	380.61	0.60 ( 0.57)	0.95	59908.8	10210.00
19	846.89	429.91	0.60 ( 0.57)	0.95	60407.9	12000.00
20	793.71	499.58	0.60 ( 0.57)	0.95	60992.6	10100.00
TOTAL AREA(ACRES) =						60992.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1831.37	23.84	0.60 ( 0.44)	0.73	3002.4	200.00
2	1717.79	40.96	0.60 ( 0.45)	0.75	5963.5	100.00
3	1602.46	49.63	0.60 ( 0.46)	0.77	7573.8	150.00
4	1365.96	70.60	0.60 ( 0.49)	0.81	11123.4	50100.00
5	1311.36	96.39	0.60 ( 0.51)	0.85	16376.2	13100.00
6	1300.42	118.98	0.60 ( 0.52)	0.87	20334.8	11831.00
7	1353.53	142.67	0.60 ( 0.53)	0.89	24628.5	11530.00
8	1399.88	162.31	0.60 ( 0.54)	0.90	28784.4	11000.00
9	1471.28	184.75	0.60 ( 0.55)	0.92	35590.8	10850.00
10	1378.92	200.40	0.60 ( 0.56)	0.93	38910.6	11220.00
11	1312.72	211.82	0.60 ( 0.56)	0.93	40662.7	10910.00
12	1134.63	252.40	0.60 ( 0.56)	0.94	47244.3	12410.00
13	1075.89	285.43	0.60 ( 0.57)	0.94	53330.2	12261.00



14	1055.67	298.22	0.60	( 0.57)	0.94	54816.8	10410.00
15	1035.89	310.43	0.60	( 0.57)	0.95	55918.8	12101.10
16	991.21	337.99	0.60	( 0.57)	0.95	58296.8	10200.00
17	968.87	351.40	0.60	( 0.57)	0.95	59235.1	12010.00
18	916.37	380.61	0.60	( 0.57)	0.95	59908.8	10210.00
19	846.89	429.91	0.60	( 0.57)	0.95	60407.9	12000.00
20	793.71	499.58	0.60	( 0.57)	0.95	60992.6	10100.00

TOTAL AREA (ACRES) = 60992.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13402.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 215.00 DOWNSTREAM (FEET) = 209.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 623.02 CHANNEL SLOPE = 0.0096  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA (CFS) = 1831.37  
FLOW VELOCITY (FEET/SEC.) = 11.21 FLOW DEPTH (FEET) = 7.38  
TRAVEL TIME (MIN.) = 0.93 Tc (MIN.) = 24.76  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118713.68 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1831.37	24.76	0.666	0.60 ( 0.44)	0.73	3002.4	200.00
2	1717.79	41.90	0.494	0.60 ( 0.45)	0.75	5963.5	100.00
3	1602.46	50.59	0.445	0.60 ( 0.46)	0.77	7573.8	150.00
4	1365.96	71.60	0.369	0.60 ( 0.49)	0.81	11123.4	50100.00
5	1311.36	97.40	0.322	0.60 ( 0.51)	0.85	16376.2	13100.00
6	1300.42	119.99	0.280	0.60 ( 0.52)	0.87	20334.8	11831.00
7	1353.53	143.67	0.259	0.60 ( 0.53)	0.89	24628.5	11530.00
8	1399.88	163.30	0.241	0.60 ( 0.54)	0.90	28784.4	11000.00
9	1471.28	185.73	0.224	0.60 ( 0.55)	0.92	35590.8	10850.00
10	1378.92	201.40	0.219	0.60 ( 0.56)	0.93	38910.6	11220.00
11	1312.72	212.82	0.216	0.60 ( 0.56)	0.93	40662.7	10910.00
12	1134.63	253.44	0.203	0.60 ( 0.56)	0.94	47244.3	12410.00
13	1075.89	286.49	0.193	0.60 ( 0.57)	0.94	53330.2	12261.00
14	1055.67	299.28	0.189	0.60 ( 0.57)	0.94	54816.8	10410.00
15	1035.89	311.50	0.185	0.60 ( 0.57)	0.95	55918.8	12101.10
16	991.21	339.07	0.177	0.60 ( 0.57)	0.95	58296.8	10200.00
17	968.87	352.49	0.172	0.60 ( 0.57)	0.95	59235.1	12010.00
18	916.37	381.71	0.168	0.60 ( 0.57)	0.95	59908.8	10210.00
19	846.89	431.03	0.162	0.60 ( 0.57)	0.95	60407.9	12000.00
20	793.71	500.72	0.155	0.60 ( 0.57)	0.95	60992.6	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 1831.37 Tc (MIN.) = 24.76  
AREA-AVERAGED Fm (INCH/HR) = 0.44 AREA-AVERAGED Fp (INCH/HR) = 0.60  
AREA-AVERAGED Ap = 0.73 EFFECTIVE AREA (ACRES) = 3002.41

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13402.00 TO NODE 13402.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 0610505T.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	7.45	28.69	0.60	( 0.59)	0.99	153.2	50500.00

TOTAL AREA (ACRES) = 153.2

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13402.00 TO NODE 13402.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<  
=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1831.37	24.76	0.666	0.60 ( 0.44)	0.73	3002.4	200.00
2	1717.79	41.90	0.494	0.60 ( 0.45)	0.75	5963.5	100.00
3	1602.46	50.59	0.445	0.60 ( 0.46)	0.77	7573.8	150.00
4	1365.96	71.60	0.369	0.60 ( 0.49)	0.81	11123.4	50100.00
5	1311.36	97.40	0.322	0.60 ( 0.51)	0.85	16376.2	13100.00
6	1300.42	119.99	0.280	0.60 ( 0.52)	0.87	20334.8	11831.00
7	1353.53	143.67	0.259	0.60 ( 0.53)	0.89	24628.5	11530.00
8	1399.88	163.30	0.241	0.60 ( 0.54)	0.90	28784.4	11000.00
9	1471.28	185.73	0.224	0.60 ( 0.55)	0.92	35590.8	10850.00
10	1378.92	201.40	0.219	0.60 ( 0.56)	0.93	38910.6	11220.00
11	1312.72	212.82	0.216	0.60 ( 0.56)	0.93	40662.7	10910.00
12	1134.63	253.44	0.203	0.60 ( 0.56)	0.94	47244.3	12410.00
13	1075.89	286.49	0.193	0.60 ( 0.57)	0.94	53330.2	12261.00
14	1055.67	299.28	0.189	0.60 ( 0.57)	0.94	54816.8	10410.00
15	1035.89	311.50	0.185	0.60 ( 0.57)	0.95	55918.8	12101.10
16	991.21	339.07	0.177	0.60 ( 0.57)	0.95	58296.8	10200.00
17	968.87	352.49	0.172	0.60 ( 0.57)	0.95	59235.1	12010.00
18	916.37	381.71	0.168	0.60 ( 0.57)	0.95	59908.8	10210.00
19	846.89	431.03	0.162	0.60 ( 0.57)	0.95	60407.9	12000.00
20	793.71	500.72	0.155	0.60 ( 0.57)	0.95	60992.6	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118713.68 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	7.45	28.69	0.606	0.60 ( 0.59)	0.99	153.2	50500.00

LONGEST FLOWPATH FROM NODE 50500.00 TO NODE 13402.00 = 6247.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1838.82	24.76	0.666	0.60 ( 0.45)	0.74	3134.6	200.00
2	1812.81	28.69	0.606	0.60 ( 0.45)	0.75	3833.8	50500.00
3	1721.20	41.90	0.494	0.60 ( 0.45)	0.76	6116.6	100.00
4	1605.53	50.59	0.445	0.60 ( 0.46)	0.77	7726.9	150.00
5	1368.51	71.60	0.369	0.60 ( 0.49)	0.81	11276.6	50100.00
6	1313.59	97.40	0.322	0.60 ( 0.51)	0.85	16529.4	13100.00
7	1302.35	119.99	0.280	0.60 ( 0.52)	0.87	20488.0	11831.00
8	1355.32	143.67	0.259	0.60 ( 0.53)	0.89	24781.7	11530.00
9	1401.55	163.30	0.241	0.60 ( 0.54)	0.90	28937.6	11000.00
10	1472.82	185.73	0.224	0.60 ( 0.55)	0.92	35744.0	10850.00
11	1380.43	201.40	0.219	0.60 ( 0.56)	0.93	39063.8	11220.00
12	1314.21	212.82	0.216	0.60 ( 0.56)	0.93	40815.9	10910.00

13	1136.03	253.44	0.203	0.60	( 0.56)	0.94	47397.5	12410.00
14	1077.22	286.49	0.193	0.60	( 0.57)	0.94	53483.4	12261.00
15	1056.97	299.28	0.189	0.60	( 0.57)	0.94	54970.0	10410.00
16	1037.17	311.50	0.185	0.60	( 0.57)	0.95	56071.9	12101.10
17	992.43	339.07	0.177	0.60	( 0.57)	0.95	58450.0	10200.00
18	970.06	352.49	0.172	0.60	( 0.57)	0.95	59388.3	12010.00
19	917.53	381.71	0.168	0.60	( 0.57)	0.95	60062.0	10210.00
20	848.01	431.03	0.162	0.60	( 0.57)	0.95	60561.0	12000.00
21	794.78	500.72	0.155	0.60	( 0.57)	0.95	61145.8	10100.00

TOTAL AREA (ACRES) = 61145.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 1838.82 Tc (MIN.) = 24.765  
EFFECTIVE AREA (ACRES) = 3134.63 AREA-AVERAGED Fm (INCH/HR) = 0.45  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.74  
TOTAL AREA (ACRES) = 61145.8  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118713.68 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13402.00 TO NODE 13404.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 209.00 DOWNSTREAM (FEET) = 207.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 395.35 CHANNEL SLOPE = 0.0051  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA (CFS) = 1838.82  
FLOW VELOCITY (FEET/SEC.) = 8.81 FLOW DEPTH (FEET) = 8.34  
TRAVEL TIME (MIN.) = 0.75 Tc (MIN.) = 25.51  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119109.03 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1838.82	25.51	0.653	0.60 ( 0.45)	0.74	3134.6	200.00
2	1812.81	29.44	0.595	0.60 ( 0.45)	0.75	3833.8	50500.00
3	1721.20	42.66	0.490	0.60 ( 0.45)	0.76	6116.6	100.00
4	1605.53	51.36	0.440	0.60 ( 0.46)	0.77	7726.9	150.00
5	1368.51	72.40	0.368	0.60 ( 0.49)	0.81	11276.6	50100.00
6	1313.59	98.21	0.321	0.60 ( 0.51)	0.85	16529.4	13100.00
7	1302.35	120.81	0.279	0.60 ( 0.52)	0.87	20488.0	11831.00
8	1355.32	144.47	0.258	0.60 ( 0.53)	0.89	24781.7	11530.00
9	1401.55	164.10	0.240	0.60 ( 0.54)	0.90	28937.6	11000.00
10	1472.82	186.52	0.224	0.60 ( 0.55)	0.92	35744.0	10850.00
11	1380.43	202.20	0.219	0.60 ( 0.56)	0.93	39063.8	11220.00
12	1314.21	213.64	0.216	0.60 ( 0.56)	0.93	40815.9	10910.00
13	1136.03	254.28	0.203	0.60 ( 0.56)	0.94	47397.5	12410.00
14	1077.22	287.34	0.193	0.60 ( 0.57)	0.94	53483.4	12261.00
15	1056.97	300.14	0.189	0.60 ( 0.57)	0.94	54970.0	10410.00
16	1037.17	312.36	0.185	0.60 ( 0.57)	0.95	56071.9	12101.10
17	992.43	339.94	0.176	0.60 ( 0.57)	0.95	58450.0	10200.00
18	970.06	353.37	0.172	0.60 ( 0.57)	0.95	59388.3	12010.00
19	917.53	382.60	0.168	0.60 ( 0.57)	0.95	60062.0	10210.00
20	848.01	431.94	0.162	0.60 ( 0.57)	0.95	60561.0	12000.00
21	794.78	501.64	0.155	0.60 ( 0.57)	0.95	61145.8	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 1838.82 Tc (MIN.) = 25.51  
AREA-AVERAGED Fm (INCH/HR) = 0.45 AREA-AVERAGED Fp (INCH/HR) = 0.60  
AREA-AVERAGED Ap = 0.74 EFFECTIVE AREA (ACRES) = 3134.63

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13404.00 TO NODE 13404.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610506T.DNA  
MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	7.14	22.42	0.60 ( 0.60)	1.00	49.6	50600.00
TOTAL AREA (ACRES) = 49.6						

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13404.00 TO NODE 13404.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1838.82	25.51	0.653	0.60 ( 0.45)	0.74	3134.6	200.00
2	1812.81	29.44	0.595	0.60 ( 0.45)	0.75	3833.8	50500.00
3	1721.20	42.66	0.490	0.60 ( 0.45)	0.76	6116.6	100.00
4	1605.53	51.36	0.440	0.60 ( 0.46)	0.77	7726.9	150.00
5	1368.51	72.40	0.368	0.60 ( 0.49)	0.81	11276.6	50100.00
6	1313.59	98.21	0.321	0.60 ( 0.51)	0.85	16529.4	13100.00
7	1302.35	120.81	0.279	0.60 ( 0.52)	0.87	20488.0	11831.00
8	1355.32	144.47	0.258	0.60 ( 0.53)	0.89	24781.7	11530.00
9	1401.55	164.10	0.240	0.60 ( 0.54)	0.90	28937.6	11000.00
10	1472.82	186.52	0.224	0.60 ( 0.55)	0.92	35744.0	10850.00
11	1380.43	202.20	0.219	0.60 ( 0.56)	0.93	39063.8	11220.00
12	1314.21	213.64	0.216	0.60 ( 0.56)	0.93	40815.9	10910.00
13	1136.03	254.28	0.203	0.60 ( 0.56)	0.94	47397.5	12410.00
14	1077.22	287.34	0.193	0.60 ( 0.57)	0.94	53483.4	12261.00
15	1056.97	300.14	0.189	0.60 ( 0.57)	0.94	54970.0	10410.00
16	1037.17	312.36	0.185	0.60 ( 0.57)	0.95	56071.9	12101.10
17	992.43	339.94	0.176	0.60 ( 0.57)	0.95	58450.0	10200.00
18	970.06	353.37	0.172	0.60 ( 0.57)	0.95	59388.3	12010.00
19	917.53	382.60	0.168	0.60 ( 0.57)	0.95	60062.0	10210.00
20	848.01	431.94	0.162	0.60 ( 0.57)	0.95	60561.0	12000.00
21	794.78	501.64	0.155	0.60 ( 0.57)	0.95	61145.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119109.03 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	7.14	22.42	0.715	0.60 ( 0.60)	1.00	49.6	50600.00
LONGEST FLOWPATH FROM NODE 50600.00 TO NODE 13404.00 = 4378.00 FEET.							

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1845.96	22.42	0.715	0.60 ( 0.45)	0.75	2804.8	50600.00

2	1842.15	25.51	0.653	0.60	(0.45)	0.75	3184.2	200.00
3	1812.81	29.44	0.595	0.60	(0.45)	0.75	3883.4	50500.00
4	1721.20	42.66	0.490	0.60	(0.46)	0.76	6166.2	100.00
5	1605.53	51.36	0.440	0.60	(0.47)	0.78	7776.5	150.00
6	1368.51	72.40	0.368	0.60	(0.49)	0.81	11326.2	50100.00
7	1313.59	98.21	0.321	0.60	(0.51)	0.85	16579.0	13100.00
8	1302.35	120.81	0.279	0.60	(0.52)	0.87	20537.6	11831.00
9	1355.32	144.47	0.258	0.60	(0.53)	0.89	24831.3	11530.00
10	1401.55	164.10	0.240	0.60	(0.54)	0.90	28987.2	11000.00
11	1472.82	186.52	0.224	0.60	(0.55)	0.92	35793.6	10850.00
12	1380.43	202.20	0.219	0.60	(0.56)	0.93	39113.4	11220.00
13	1314.21	213.64	0.216	0.60	(0.56)	0.93	40865.5	10910.00
14	1136.03	254.28	0.203	0.60	(0.56)	0.94	47447.1	12410.00
15	1077.22	287.34	0.193	0.60	(0.57)	0.94	53533.0	12261.00
16	1056.97	300.14	0.189	0.60	(0.57)	0.94	55019.6	10410.00
17	1037.17	312.36	0.185	0.60	(0.57)	0.95	56121.5	12101.10
18	992.43	339.94	0.176	0.60	(0.57)	0.95	58499.6	10200.00
19	970.06	353.37	0.172	0.60	(0.57)	0.95	59437.9	12010.00
20	917.53	382.60	0.168	0.60	(0.57)	0.95	60111.6	10210.00
21	848.01	431.94	0.162	0.60	(0.57)	0.95	60610.6	12000.00
22	794.78	501.64	0.155	0.60	(0.57)	0.95	61195.4	10100.00

TOTAL AREA (ACRES) = 61195.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 1845.96 Tc (MIN.) = 22.425  
EFFECTIVE AREA (ACRES) = 2804.83 AREA-AVERAGED Fm (INCH/HR) = 0.45  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.95  
TOTAL AREA (ACRES) = 61195.4  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119109.03 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13404.00 TO NODE 13406.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<  
-----

ELEVATION DATA: UPSTREAM (FEET) = 207.00 DOWNSTREAM (FEET) = 195.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1604.97 CHANNEL SLOPE = 0.0075  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA (CFS) = 1845.96  
FLOW VELOCITY (FEET/SEC.) = 10.21 FLOW DEPTH (FEET) = 7.76  
TRAVEL TIME (MIN.) = 2.62 Tc (MIN.) = 25.04  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13406.00 = 120714.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1845.96	25.04	0.660	0.60 (0.45)	0.75	2804.8	50600.00
2	1842.15	28.13	0.615	0.60 (0.45)	0.75	3184.2	200.00
3	1812.81	32.07	0.570	0.60 (0.45)	0.75	3883.4	50500.00
4	1721.20	45.33	0.475	0.60 (0.46)	0.76	6166.2	100.00
5	1605.53	54.08	0.424	0.60 (0.47)	0.78	7776.5	150.00
6	1368.51	75.23	0.363	0.60 (0.49)	0.81	11326.2	50100.00
7	1313.59	101.06	0.315	0.60 (0.51)	0.85	16579.0	13100.00
8	1302.35	123.66	0.277	0.60 (0.52)	0.87	20537.6	11831.00
9	1355.32	147.30	0.255	0.60 (0.53)	0.89	24831.3	11530.00
10	1401.55	166.91	0.238	0.60 (0.54)	0.90	28987.2	11000.00

11	1472.82	189.29	0.223	0.60	(0.55)	0.92	35793.6	10850.00
12	1380.43	205.02	0.218	0.60	(0.56)	0.93	39113.4	11220.00
13	1314.21	216.49	0.215	0.60	(0.56)	0.93	40865.5	10910.00
14	1136.03	257.24	0.202	0.60	(0.56)	0.94	47447.1	12410.00
15	1077.22	290.34	0.192	0.60	(0.57)	0.94	53533.0	12261.00
16	1056.97	303.15	0.188	0.60	(0.57)	0.94	55019.6	10410.00
17	1037.17	315.39	0.184	0.60	(0.57)	0.95	56121.5	12101.10
18	992.43	343.00	0.175	0.60	(0.57)	0.95	58499.6	10200.00
19	970.06	356.45	0.171	0.60	(0.57)	0.95	59437.9	12010.00
20	917.53	385.72	0.167	0.60	(0.57)	0.95	60111.6	10210.00
21	848.01	435.11	0.162	0.60	(0.57)	0.95	60610.6	12000.00
22	794.78	504.87	0.154	0.60	(0.57)	0.95	61195.4	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 1845.96 Tc (MIN.) = 25.04  
AREA-AVERAGED Fm (INCH/HR) = 0.45 AREA-AVERAGED Fp (INCH/HR) = 0.60  
AREA-AVERAGED Ap = 0.75 EFFECTIVE AREA (ACRES) = 2804.83

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<  
-----

MAINLINE Tc (MIN.) = 25.04

\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.660

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.20	0.60	1.000	-
USER-DEFINED	-	4.00	0.60	1.000	-
USER-DEFINED	-	2.00	0.60	1.000	-
USER-DEFINED	-	9.70	0.60	1.000	-
USER-DEFINED	-	2.60	0.60	1.000	-
USER-DEFINED	-	1.80	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 20.30 SUBAREA RUNOFF (CFS) = 1.11

EFFECTIVE AREA (ACRES) = 2825.13 AREA-AVERAGED Fm (INCH/HR) = 0.45

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.75

TOTAL AREA (ACRES) = 61215.7 PEAK FLOW RATE (CFS) = 1845.96

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<  
-----

MAINLINE Tc (MIN.) = 25.04

\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.660

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	3.50	0.60	1.000	-
USER-DEFINED	-	7.20	0.60	1.000	-
USER-DEFINED	-	5.80	0.60	1.000	-
USER-DEFINED	-	0.10	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 16.60 SUBAREA RUNOFF (CFS) = 0.90

EFFECTIVE AREA (ACRES) = 2841.73 AREA-AVERAGED Fm (INCH/HR) = 0.45  
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.75  
 TOTAL AREA (ACRES) = 61232.3 PEAK FLOW RATE (CFS) = 1845.96  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<<

PEAK FLOWRATE TABLE FILE NAME: 2P02EVBB.DNA  
 MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	194.02	10.81	0.60 ( 0.22)	0.37	221.7	429.00
2	201.81	12.63	0.60 ( 0.22)	0.37	258.9	425.00
3	202.30	12.83	0.60 ( 0.22)	0.37	263.0	400.00
4	203.94	14.48	0.60 ( 0.22)	0.37	297.3	300.00
5	198.94	22.38	0.60 ( 0.22)	0.37	440.6	210.00
6	195.86	23.21	0.60 ( 0.22)	0.37	449.5	410.00
7	187.76	25.35	0.60 ( 0.22)	0.37	471.9	200.00
8	183.91	26.92	0.60 ( 0.22)	0.37	487.0	230.00
9	177.74	28.12	0.60 ( 0.22)	0.37	491.2	220.50
TOTAL AREA (ACRES) = 491.2						

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1845.96	25.04	0.660	0.60 ( 0.45)	0.75	2841.7	50600.00
2	1842.15	28.13	0.615	0.60 ( 0.45)	0.75	3221.1	200.00
3	1812.81	32.07	0.570	0.60 ( 0.45)	0.75	3920.3	50500.00
4	1721.20	45.33	0.475	0.60 ( 0.46)	0.76	6203.1	100.00
5	1605.53	54.08	0.424	0.60 ( 0.47)	0.78	7813.4	150.00
6	1368.51	75.23	0.363	0.60 ( 0.49)	0.81	11363.1	50100.00
7	1313.59	101.06	0.315	0.60 ( 0.51)	0.85	16615.9	13100.00
8	1302.35	123.66	0.277	0.60 ( 0.52)	0.87	20574.5	11831.00
9	1355.32	147.30	0.255	0.60 ( 0.53)	0.89	24868.2	11530.00
10	1401.55	166.91	0.238	0.60 ( 0.54)	0.90	29024.1	11000.00
11	1472.82	189.29	0.223	0.60 ( 0.55)	0.92	35830.5	10850.00
12	1380.43	205.02	0.218	0.60 ( 0.56)	0.93	39150.3	11220.00
13	1314.21	216.49	0.215	0.60 ( 0.56)	0.93	40902.4	10910.00
14	1136.03	257.24	0.202	0.60 ( 0.56)	0.94	47484.0	12410.00
15	1077.22	290.34	0.192	0.60 ( 0.57)	0.94	53569.9	12261.00
16	1056.97	303.15	0.188	0.60 ( 0.57)	0.94	55056.5	10410.00
17	1037.17	315.39	0.184	0.60 ( 0.57)	0.95	56158.4	12101.10
18	992.43	343.00	0.175	0.60 ( 0.57)	0.95	58536.5	10200.00

19	970.06	356.45	0.171	0.60 ( 0.57)	0.95	59474.8	12010.00
20	917.53	385.72	0.167	0.60 ( 0.57)	0.95	60148.5	10210.00
21	848.01	435.11	0.162	0.60 ( 0.57)	0.95	60647.5	12000.00
22	794.78	504.87	0.154	0.60 ( 0.57)	0.95	61232.3	10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13406.00 = 120714.00 FEET.							

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	194.02	10.81	1.167	0.60 ( 0.22)	0.37	221.7	429.00
2	201.81	12.63	1.064	0.60 ( 0.22)	0.37	258.9	425.00
3	202.30	12.83	1.053	0.60 ( 0.22)	0.37	263.0	400.00
4	203.94	14.48	0.959	0.60 ( 0.22)	0.37	297.3	300.00
5	198.94	22.38	0.715	0.60 ( 0.22)	0.37	440.6	210.00
6	195.86	23.21	0.698	0.60 ( 0.22)	0.37	449.5	410.00
7	187.76	25.35	0.656	0.60 ( 0.22)	0.37	471.9	200.00
8	183.91	26.92	0.633	0.60 ( 0.22)	0.37	487.0	230.00
9	177.74	28.12	0.615	0.60 ( 0.22)	0.37	491.2	220.50
LONGEST FLOWPATH FROM NODE 230.00 TO NODE 13406.00 = 11903.00 FEET.							

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2039.98	10.81	1.167	0.60 ( 0.42)	0.69	1448.0	429.00
2	2047.77	12.63	1.064	0.60 ( 0.42)	0.69	1691.9	425.00
3	2048.26	12.83	1.053	0.60 ( 0.42)	0.69	1718.6	400.00
4	2049.90	14.48	0.959	0.60 ( 0.42)	0.69	1940.7	300.00
5	2044.90	22.38	0.715	0.60 ( 0.42)	0.70	2980.3	210.00
6	2041.82	23.21	0.698	0.60 ( 0.42)	0.70	3083.6	410.00
7	2034.87	25.04	0.660	0.60 ( 0.42)	0.70	3310.5	50600.00
8	2033.35	25.35	0.656	0.60 ( 0.42)	0.70	3350.7	200.00
9	2027.56	26.92	0.633	0.60 ( 0.42)	0.70	3559.0	230.00
10	2019.90	28.12	0.615	0.60 ( 0.42)	0.70	3711.1	220.50
11	2019.83	28.13	0.615	0.60 ( 0.42)	0.70	3712.3	200.00
12	1975.33	32.07	0.570	0.60 ( 0.43)	0.71	4411.5	50500.00
13	1856.53	45.33	0.475	0.60 ( 0.44)	0.73	6694.3	100.00
14	1726.52	54.08	0.424	0.60 ( 0.45)	0.75	8304.6	150.00
15	1471.89	75.23	0.363	0.60 ( 0.48)	0.79	11854.3	50100.00
16	1403.50	101.06	0.315	0.60 ( 0.50)	0.83	17107.1	13100.00
17	1381.24	123.66	0.277	0.60 ( 0.52)	0.86	21065.7	11831.00
18	1428.14	147.30	0.255	0.60 ( 0.53)	0.88	25359.4	11530.00
19	1469.34	166.91	0.238	0.60 ( 0.54)	0.89	29515.3	11000.00
20	1536.44	189.29	0.223	0.60 ( 0.55)	0.91	36321.7	10850.00
21	1442.65	205.02	0.218	0.60 ( 0.55)	0.92	39641.5	11220.00
22	1375.40	216.49	0.215	0.60 ( 0.56)	0.92	41393.6	10910.00
23	1193.61	257.24	0.202	0.60 ( 0.56)	0.93	47975.2	12410.00
24	1131.87	290.34	0.192	0.60 ( 0.56)	0.94	54061.1	12261.00
25	1110.48	303.15	0.188	0.60 ( 0.56)	0.94	55547.7	10410.00
26	1089.59	315.39	0.184	0.60 ( 0.56)	0.94	56649.6	12101.10
27	1042.40	343.00	0.175	0.60 ( 0.57)	0.94	59027.7	10200.00
28	1018.84	356.45	0.171	0.60 ( 0.57)	0.94	59966.0	12010.00
29	965.21	385.72	0.167	0.60 ( 0.57)	0.94	60639.7	10210.00
30	894.19	435.11	0.162	0.60 ( 0.57)	0.94	61138.7	12000.00
31	838.82	504.87	0.154	0.60 ( 0.57)	0.95	61723.5	10100.00
TOTAL AREA (ACRES) = 61723.5							

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 2049.90 Tc (MIN.) = 14.483

EFFECTIVE AREA(ACRES) = 1940.71 AREA-AVERAGED Fm(INCH/HR) = 0.42  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.94  
 TOTAL AREA(ACRES) = 61723.5  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13406.00 = 120714.00 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13406.00 TO NODE 13408.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 195.00 DOWNSTREAM(FEET) = 182.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2458.36 CHANNEL SLOPE = 0.0053  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.800

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.00	0.60	1.000	-
USER-DEFINED	-	3.30	0.60	1.000	-
USER-DEFINED	-	0.40	0.60	0.100	-
USER-DEFINED	-	1.40	0.60	1.000	-
USER-DEFINED	-	0.30	0.60	0.100	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.949

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2051.19

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.21

AVERAGE FLOW DEPTH(FEET) = 8.62 TRAVEL TIME(MIN.) = 4.45

Tc(MIN.) = 18.93

SUBAREA AREA(ACRES) = 12.40 SUBAREA RUNOFF(CFS) = 2.58

EFFECTIVE AREA(ACRES) = 1953.11 AREA-AVERAGED Fm(INCH/HR) = 0.42

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.70

TOTAL AREA(ACRES) = 61735.9 PEAK FLOW RATE(CFS) = 2049.90

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 8.62 FLOW VELOCITY(FEET/SEC.) = 9.20

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123172.36 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2039.98	15.26	0.921	0.60( 0.42)	0.70	1460.4	429.00
2	2047.77	17.08	0.861	0.60( 0.42)	0.70	1704.3	425.00
3	2048.26	17.28	0.855	0.60( 0.42)	0.70	1731.0	400.00
4	2049.90	18.93	0.800	0.60( 0.42)	0.70	1953.1	300.00
5	2044.90	26.84	0.634	0.60( 0.42)	0.70	2992.7	210.00
6	2041.82	27.67	0.622	0.60( 0.42)	0.70	3096.0	410.00
7	2034.87	29.50	0.594	0.60( 0.42)	0.70	3322.9	50600.00
8	2033.35	29.80	0.590	0.60( 0.42)	0.70	3363.1	200.00
9	2027.56	31.38	0.576	0.60( 0.42)	0.70	3571.4	230.00
10	2019.90	32.59	0.566	0.60( 0.42)	0.70	3723.5	220.50
11	2019.83	32.60	0.566	0.60( 0.42)	0.70	3724.7	200.00
12	1975.33	36.56	0.533	0.60( 0.43)	0.71	4423.9	50500.00
13	1856.53	49.88	0.449	0.60( 0.44)	0.73	6706.7	100.00
14	1726.52	58.72	0.397	0.60( 0.45)	0.75	8317.0	150.00
15	1471.89	80.06	0.354	0.60( 0.48)	0.79	11866.7	50100.00

16	1403.50	105.96	0.306	0.60( 0.50)	0.83	17119.5	13100.00
17	1381.24	128.57	0.272	0.60( 0.52)	0.86	21078.1	11831.00
18	1428.14	152.18	0.251	0.60( 0.53)	0.88	25371.8	11530.00
19	1469.34	171.75	0.233	0.60( 0.54)	0.89	29527.7	11000.00
20	1536.44	194.07	0.222	0.60( 0.55)	0.91	36334.1	10850.00
21	1442.65	209.87	0.217	0.60( 0.55)	0.92	39653.9	11220.00
22	1375.40	221.41	0.213	0.60( 0.55)	0.92	41406.0	10910.00
23	1193.61	262.33	0.200	0.60( 0.56)	0.93	47987.6	12410.00
24	1131.87	295.50	0.190	0.60( 0.56)	0.94	54073.5	12261.00
25	1110.48	308.34	0.186	0.60( 0.56)	0.94	55560.1	10410.00
26	1089.59	320.59	0.182	0.60( 0.56)	0.94	56662.0	12101.10
27	1042.40	348.27	0.174	0.60( 0.57)	0.94	59040.1	10200.00
28	1018.84	361.74	0.170	0.60( 0.57)	0.94	59978.4	12010.00
29	965.21	391.09	0.167	0.60( 0.57)	0.94	60652.1	10210.00
30	894.19	440.59	0.161	0.60( 0.57)	0.94	61151.1	12000.00
31	838.82	510.44	0.154	0.60( 0.57)	0.95	61735.9	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2049.90 Tc(MIN.) = 18.93

AREA-AVERAGED Fm(INCH/HR) = 0.42 AREA-AVERAGED Fp(INCH/HR) = 0.60

AREA-AVERAGED Ap = 0.70 EFFECTIVE AREA(ACRES) = 1953.11

\*\*\*\*\*

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<

PEAK FLOWRATE TABLE FILE NAME: 0610507T.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	10.23	29.92	0.60( 0.60)	0.99	236.8	50700.00
TOTAL AREA(ACRES) = 236.8						

\*\*\*\*\*

FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2039.98	15.26	0.921	0.60( 0.42)	0.70	1460.4	429.00
2	2047.77	17.08	0.861	0.60( 0.42)	0.70	1704.3	425.00
3	2048.26	17.28	0.855	0.60( 0.42)	0.70	1731.0	400.00
4	2049.90	18.93	0.800	0.60( 0.42)	0.70	1953.1	300.00
5	2044.90	26.84	0.634	0.60( 0.42)	0.70	2992.7	210.00
6	2041.82	27.67	0.622	0.60( 0.42)	0.70	3096.0	410.00
7	2034.87	29.50	0.594	0.60( 0.42)	0.70	3322.9	50600.00
8	2033.35	29.80	0.590	0.60( 0.42)	0.70	3363.1	200.00
9	2027.56	31.38	0.576	0.60( 0.42)	0.70	3571.4	230.00
10	2019.90	32.59	0.566	0.60( 0.42)	0.70	3723.5	220.50

11	2019.83	32.60	0.566	0.60 ( 0.42)	0.70	3724.7	200.00
12	1975.33	36.56	0.533	0.60 ( 0.43)	0.71	4423.9	50500.00
13	1856.53	49.88	0.449	0.60 ( 0.44)	0.73	6706.7	100.00
14	1726.52	58.72	0.397	0.60 ( 0.45)	0.75	8317.0	150.00
15	1471.89	80.06	0.354	0.60 ( 0.48)	0.79	11866.7	50100.00
16	1403.50	105.96	0.306	0.60 ( 0.50)	0.83	17119.5	13100.00
17	1381.24	128.57	0.272	0.60 ( 0.52)	0.86	21078.1	11831.00
18	1428.14	152.18	0.251	0.60 ( 0.53)	0.88	25371.8	11530.00
19	1469.34	171.75	0.233	0.60 ( 0.54)	0.89	29527.7	11000.00
20	1536.44	194.07	0.222	0.60 ( 0.55)	0.91	36334.1	10850.00
21	1442.65	209.87	0.217	0.60 ( 0.55)	0.92	39653.9	11220.00
22	1375.40	221.41	0.213	0.60 ( 0.55)	0.92	41406.0	10910.00
23	1193.61	262.33	0.200	0.60 ( 0.56)	0.93	47987.6	12410.00
24	1131.87	295.50	0.190	0.60 ( 0.56)	0.94	54073.5	12261.00
25	1110.48	308.34	0.186	0.60 ( 0.56)	0.94	55560.1	10410.00
26	1089.59	320.59	0.182	0.60 ( 0.56)	0.94	56662.0	12101.10
27	1042.40	348.27	0.174	0.60 ( 0.57)	0.94	59040.1	10200.00
28	1018.84	361.74	0.170	0.60 ( 0.57)	0.94	59978.4	12010.00
29	965.21	391.09	0.167	0.60 ( 0.57)	0.94	60652.1	10210.00
30	894.19	440.59	0.161	0.60 ( 0.57)	0.94	61151.1	12000.00
31	838.82	510.44	0.154	0.60 ( 0.57)	0.95	61735.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123172.36 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	10.23	29.92	0.588	0.60 ( 0.60)	0.99	236.8	50700.00

LONGEST FLOWPATH FROM NODE 50700.00 TO NODE 13408.00 = 7903.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2048.15	15.26	0.921	0.60 ( 0.43)	0.72	1581.2	429.00
2	2056.32	17.08	0.861	0.60 ( 0.43)	0.72	1839.4	425.00
3	2056.85	17.28	0.855	0.60 ( 0.43)	0.72	1867.8	400.00
4	2058.71	18.93	0.800	0.60 ( 0.43)	0.72	2102.9	300.00
5	2054.78	26.84	0.634	0.60 ( 0.43)	0.72	3205.1	210.00
6	2051.81	27.67	0.622	0.60 ( 0.43)	0.72	3315.0	410.00
7	2045.06	29.50	0.594	0.60 ( 0.43)	0.72	3556.4	50600.00
8	2043.57	29.80	0.590	0.60 ( 0.43)	0.72	3598.9	200.00
9	2043.15	29.92	0.588	0.60 ( 0.43)	0.72	3615.4	50700.00
10	2037.58	31.38	0.576	0.60 ( 0.43)	0.72	3808.2	230.00
11	2029.75	32.59	0.566	0.60 ( 0.43)	0.72	3960.3	220.50
12	2029.67	32.60	0.566	0.60 ( 0.43)	0.72	3961.5	200.00
13	1984.60	36.56	0.533	0.60 ( 0.44)	0.73	4660.7	50500.00
14	1864.33	49.88	0.449	0.60 ( 0.44)	0.74	6943.5	100.00
15	1733.43	58.72	0.397	0.60 ( 0.46)	0.76	8553.8	150.00
16	1478.04	80.06	0.354	0.60 ( 0.48)	0.80	12103.4	50100.00
17	1408.82	105.96	0.306	0.60 ( 0.50)	0.84	17356.2	13100.00
18	1385.98	128.57	0.272	0.60 ( 0.52)	0.86	21314.9	11831.00
19	1432.51	152.18	0.251	0.60 ( 0.53)	0.88	25608.6	11530.00
20	1473.40	171.75	0.233	0.60 ( 0.54)	0.90	29764.5	11000.00
21	1540.29	194.07	0.222	0.60 ( 0.55)	0.91	36570.9	10850.00
22	1446.42	209.87	0.217	0.60 ( 0.55)	0.92	39890.7	11220.00
23	1379.11	221.41	0.213	0.60 ( 0.55)	0.92	41642.8	10910.00
24	1197.10	262.33	0.200	0.60 ( 0.56)	0.93	48224.4	12410.00
25	1135.18	295.50	0.190	0.60 ( 0.56)	0.94	54310.3	12261.00
26	1113.72	308.34	0.186	0.60 ( 0.56)	0.94	55796.9	10410.00

27	1092.76	320.59	0.182	0.60 ( 0.56)	0.94	56898.8	12101.10
28	1045.42	348.27	0.174	0.60 ( 0.57)	0.94	59276.9	10200.00
29	1021.79	361.74	0.170	0.60 ( 0.57)	0.94	60215.1	12010.00
30	968.11	391.09	0.167	0.60 ( 0.57)	0.94	60888.9	10210.00
31	897.00	440.59	0.161	0.60 ( 0.57)	0.94	61387.9	12000.00
32	841.50	510.44	0.154	0.60 ( 0.57)	0.95	61972.7	10100.00

TOTAL AREA (ACRES) = 61972.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 2058.71 Tc (MIN.) = 18.932  
EFFECTIVE AREA (ACRES) = 2102.93 AREA-AVERAGED Fm (INCH/HR) = 0.43  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.72  
TOTAL AREA (ACRES) = 61972.7  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123172.36 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13408.00 TO NODE 13410.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM (FEET) = 182.00 DOWNSTREAM (FEET) = 178.72  
CHANNEL LENGTH THRU SUBAREA (FEET) = 952.73 CHANNEL SLOPE = 0.0034  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.745  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.40	0.60	1.000	-
USER-DEFINED	-	2.90	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 2058.93  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.85  
AVERAGE FLOW DEPTH (FEET) = 9.35 TRAVEL TIME (MIN.) = 2.02  
Tc (MIN.) = 20.95  
SUBAREA AREA (ACRES) = 3.30 SUBAREA RUNOFF (CFS) = 0.43  
EFFECTIVE AREA (ACRES) = 2106.23 AREA-AVERAGED Fm (INCH/HR) = 0.43  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.72  
TOTAL AREA (ACRES) = 61976.0 PEAK FLOW RATE (CFS) = 2058.71  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 9.35 FLOW VELOCITY (FEET/SEC.) = 7.85  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124125.09 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2048.15	17.29	0.854	0.60 ( 0.43)	0.72	1584.5	429.00
2	2056.32	19.11	0.795	0.60 ( 0.43)	0.72	1842.7	425.00
3	2056.85	19.30	0.788	0.60 ( 0.43)	0.72	1871.1	400.00
4	2058.71	20.95	0.745	0.60 ( 0.43)	0.72	2106.2	300.00
5	2054.78	28.86	0.604	0.60 ( 0.43)	0.72	3208.4	210.00
6	2051.81	29.69	0.592	0.60 ( 0.43)	0.72	3318.3	410.00
7	2045.06	31.53	0.574	0.60 ( 0.43)	0.72	3559.7	50600.00
8	2043.57	31.83	0.572	0.60 ( 0.43)	0.72	3602.2	200.00

9	2043.15	31.95	0.571	0.60	( 0.43)	0.72	3618.7	50700.00
10	2037.58	33.41	0.559	0.60	( 0.43)	0.72	3811.5	230.00
11	2029.75	34.62	0.549	0.60	( 0.43)	0.72	3963.6	220.50
12	2029.67	34.63	0.549	0.60	( 0.43)	0.72	3964.8	200.00
13	1984.60	38.61	0.516	0.60	( 0.44)	0.73	4664.0	50500.00
14	1864.33	51.96	0.437	0.60	( 0.44)	0.74	6946.8	100.00
15	1733.43	60.83	0.388	0.60	( 0.46)	0.76	8557.1	150.00
16	1478.04	82.26	0.350	0.60	( 0.48)	0.80	12106.7	50100.00
17	1408.82	108.18	0.302	0.60	( 0.50)	0.84	17359.5	13100.00
18	1385.98	130.81	0.270	0.60	( 0.52)	0.86	21318.2	11831.00
19	1432.51	154.39	0.249	0.60	( 0.53)	0.88	25611.9	11530.00
20	1473.40	173.95	0.231	0.60	( 0.54)	0.90	29767.8	11000.00
21	1540.29	196.25	0.221	0.60	( 0.55)	0.91	36574.2	10850.00
22	1446.42	212.08	0.216	0.60	( 0.55)	0.92	39894.0	11220.00
23	1379.11	223.64	0.212	0.60	( 0.55)	0.92	41646.1	10910.00
24	1197.10	264.65	0.200	0.60	( 0.56)	0.93	48227.7	12410.00
25	1135.18	297.85	0.189	0.60	( 0.56)	0.94	54313.6	12261.00
26	1113.72	310.70	0.185	0.60	( 0.56)	0.94	55800.2	10410.00
27	1092.76	322.97	0.182	0.60	( 0.56)	0.94	56902.1	12101.10
28	1045.42	350.67	0.173	0.60	( 0.57)	0.94	59280.2	10200.00
29	1021.79	364.15	0.170	0.60	( 0.57)	0.94	60218.4	12010.00
30	968.11	393.53	0.166	0.60	( 0.57)	0.94	60892.2	10210.00
31	897.00	443.08	0.161	0.60	( 0.57)	0.94	61391.2	12000.00
32	841.50	512.97	0.154	0.60	( 0.57)	0.95	61976.0	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2058.71 Tc(MIN.) = 20.95  
 AREA-AVERAGED Fm(INCH/HR) = 0.43 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.72 EFFECTIVE AREA(ACRES) = 2106.23

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: RI02EV36.DNA  
 MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	212.85	41.95	0.60( 0.53)	0.89	1194.3	110.00
2	182.13	45.87	0.60( 0.53)	0.88	1308.8	100.00
3	166.70	48.25	0.60( 0.53)	0.88	1371.9	100.00
4	138.00	55.27	0.60( 0.54)	0.89	1542.5	130.00
5	114.28	88.34	0.60( 0.56)	0.93	2427.8	20100.00
6	99.46	100.42	0.60( 0.56)	0.93	2568.9	13600.00
7	61.98	214.44	0.60( 0.56)	0.93	3822.6	13510.00
8	61.68	223.75	0.60( 0.56)	0.93	3859.7	13500.00

TOTAL AREA(ACRES) = 3859.7

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\*\*\*\*  
 \*\* MAIN STREAM CONFLUENCE DATA \*\*  
 \*\*\*\*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2048.15	17.29	0.854	0.60( 0.43)	0.72	1584.5	429.00
2	2056.32	19.11	0.795	0.60( 0.43)	0.72	1842.7	425.00
3	2056.85	19.30	0.788	0.60( 0.43)	0.72	1871.1	400.00
4	2058.71	20.95	0.745	0.60( 0.43)	0.72	2106.2	300.00
5	2054.78	28.86	0.604	0.60( 0.43)	0.72	3208.4	210.00
6	2051.81	29.69	0.592	0.60( 0.43)	0.72	3318.3	410.00
7	2045.06	31.53	0.574	0.60( 0.43)	0.72	3559.7	50600.00
8	2043.57	31.83	0.572	0.60( 0.43)	0.72	3602.2	200.00
9	2043.15	31.95	0.571	0.60( 0.43)	0.72	3618.7	50700.00
10	2037.58	33.41	0.559	0.60( 0.43)	0.72	3811.5	230.00
11	2029.75	34.62	0.549	0.60( 0.43)	0.72	3963.6	220.50
12	2029.67	34.63	0.549	0.60( 0.43)	0.72	3964.8	200.00
13	1984.60	38.61	0.516	0.60( 0.44)	0.73	4664.0	50500.00
14	1864.33	51.96	0.437	0.60( 0.44)	0.74	6946.8	100.00
15	1733.43	60.83	0.388	0.60( 0.46)	0.76	8557.1	150.00
16	1478.04	82.26	0.350	0.60( 0.48)	0.80	12106.7	50100.00
17	1408.82	108.18	0.302	0.60( 0.50)	0.84	17359.5	13100.00
18	1385.98	130.81	0.270	0.60( 0.52)	0.86	21318.2	11831.00
19	1432.51	154.39	0.249	0.60( 0.53)	0.88	25611.9	11530.00
20	1473.40	173.95	0.231	0.60( 0.54)	0.90	29767.8	11000.00
21	1540.29	196.25	0.221	0.60( 0.55)	0.91	36574.2	10850.00
22	1446.42	212.08	0.216	0.60( 0.55)	0.92	39894.0	11220.00
23	1379.11	223.64	0.212	0.60( 0.55)	0.92	41646.1	10910.00
24	1197.10	264.65	0.200	0.60( 0.56)	0.93	48227.7	12410.00
25	1135.18	297.85	0.189	0.60( 0.56)	0.94	54313.6	12261.00
26	1113.72	310.70	0.185	0.60( 0.56)	0.94	55800.2	10410.00
27	1092.76	322.97	0.182	0.60( 0.56)	0.94	56902.1	12101.10
28	1045.42	350.67	0.173	0.60( 0.57)	0.94	59280.2	10200.00
29	1021.79	364.15	0.170	0.60( 0.57)	0.94	60218.4	12010.00
30	968.11	393.53	0.166	0.60( 0.57)	0.94	60892.2	10210.00
31	897.00	443.08	0.161	0.60( 0.57)	0.94	61391.2	12000.00
32	841.50	512.97	0.154	0.60( 0.57)	0.95	61976.0	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124125.09 FEET.

\*\*\*\*\*  
 \*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*  
 \*\*\*\*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	212.85	41.95	0.494	0.60( 0.53)	0.89	1194.3	110.00
2	182.13	45.87	0.472	0.60( 0.53)	0.88	1308.8	100.00
3	166.70	48.25	0.458	0.60( 0.53)	0.88	1371.9	100.00
4	138.00	55.27	0.417	0.60( 0.54)	0.89	1542.5	130.00
5	114.28	88.34	0.339	0.60( 0.56)	0.93	2427.8	20100.00
6	99.46	100.42	0.317	0.60( 0.56)	0.93	2568.9	13600.00
7	61.98	214.44	0.215	0.60( 0.56)	0.93	3822.6	13510.00
8	61.68	223.75	0.212	0.60( 0.56)	0.93	3859.7	13500.00

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13410.00 = 41710.10 FEET.

\*\*\*\*\*  
 \*\* PEAK FLOW RATE TABLE \*\*  
 \*\*\*\*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2261.00	17.29	0.854	0.60( 0.46)	0.76	2076.7	429.00
2	2269.18	19.11	0.795	0.60( 0.45)	0.76	2386.7	425.00
3	2269.70	19.30	0.788	0.60( 0.45)	0.76	2420.7	400.00

4	2271.56	20.95	0.745	0.60	(0.45)	0.75	2702.8	300.00
5	2243.25	28.86	0.604	0.60	(0.45)	0.75	4030.0	210.00
6	2232.27	29.69	0.592	0.60	(0.45)	0.75	4163.7	410.00
7	2231.15	31.53	0.574	0.60	(0.45)	0.75	4457.4	50600.00
8	2230.62	31.83	0.572	0.60	(0.45)	0.75	4508.5	200.00
9	2230.58	31.95	0.571	0.60	(0.45)	0.75	4528.3	50700.00
10	2229.47	33.41	0.559	0.60	(0.45)	0.75	4762.8	230.00
11	2225.05	34.62	0.549	0.60	(0.45)	0.75	4949.2	220.50
12	2225.00	34.63	0.549	0.60	(0.45)	0.75	4950.7	200.00
13	2189.43	38.61	0.516	0.60	(0.45)	0.76	5763.1	50500.00
14	2167.33	41.95	0.494	0.60	(0.46)	0.76	6430.0	110.00
15	2101.30	45.87	0.472	0.60	(0.46)	0.76	7214.7	100.00
16	2064.39	48.25	0.458	0.60	(0.46)	0.76	7685.6	100.00
17	2015.87	51.96	0.437	0.60	(0.46)	0.77	8408.8	100.00
18	1953.53	55.27	0.417	0.60	(0.46)	0.77	9089.5	130.00
19	1867.43	60.83	0.388	0.60	(0.47)	0.78	10248.6	150.00
20	1596.68	82.26	0.350	0.60	(0.49)	0.82	14371.9	50100.00
21	1576.09	88.34	0.339	0.60	(0.50)	0.83	15766.2	20100.00
22	1529.01	100.42	0.317	0.60	(0.50)	0.84	18355.8	13600.00
23	1505.73	108.18	0.302	0.60	(0.51)	0.85	20013.7	13100.00
24	1475.45	130.81	0.270	0.60	(0.52)	0.87	24221.2	11831.00
25	1514.23	154.39	0.249	0.60	(0.53)	0.88	28774.2	11530.00
26	1548.69	173.95	0.231	0.60	(0.54)	0.90	33145.1	11000.00
27	1608.25	196.25	0.221	0.60	(0.55)	0.92	40196.7	10850.00
28	1509.17	212.08	0.216	0.60	(0.55)	0.92	43690.6	11220.00
29	1494.67	214.44	0.215	0.60	(0.55)	0.92	44074.0	13510.00
30	1440.79	223.64	0.212	0.60	(0.55)	0.92	45505.3	10910.00
31	1440.32	223.75	0.212	0.60	(0.55)	0.92	45522.8	13500.00
32	1255.08	264.65	0.200	0.60	(0.56)	0.93	52087.3	12410.00
33	1190.16	297.85	0.189	0.60	(0.56)	0.94	58173.2	12261.00
34	1167.54	310.70	0.185	0.60	(0.56)	0.94	59659.8	10410.00
35	1145.48	322.97	0.182	0.60	(0.56)	0.94	60761.8	12101.10
36	1095.64	350.67	0.173	0.60	(0.57)	0.94	63139.9	10200.00
37	1071.03	364.15	0.170	0.60	(0.57)	0.94	64078.1	12010.00
38	1016.44	393.53	0.166	0.60	(0.57)	0.94	64751.8	10210.00
39	943.78	443.08	0.161	0.60	(0.57)	0.94	65250.9	12000.00
40	886.11	512.97	0.154	0.60	(0.57)	0.94	65835.7	10100.00

TOTAL AREA (ACRES) = 65835.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 2271.56 Tc (MIN.) = 20.955  
EFFECTIVE AREA (ACRES) = 2702.84 AREA-AVERAGED Fm (INCH/HR) = 0.45  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.75  
TOTAL AREA (ACRES) = 65835.7  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124125.09 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13410.00 TO NODE 13412.00 IS CODE = 51

>>>> COMPUTE TRAPEZOIDAL CHANNEL FLOW <<<<<  
>>>> TRAVELTIME THRU SUBAREA (EXISTING ELEMENT) <<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 178.72 DOWNSTREAM (FEET) = 176.93  
CHANNEL LENGTH THRU SUBAREA (FEET) = 169.78 CHANNEL SLOPE = 0.0105  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA (CFS) = 2271.56  
FLOW VELOCITY (FEET/SEC.) = 12.23 FLOW DEPTH (FEET) = 7.87

TRAVEL TIME (MIN.) = 0.23 Tc (MIN.) = 21.19  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124294.87 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2261.00	17.52	0.847	0.60 (0.46)	0.76	2076.7	429.00
2	2269.18	19.34	0.787	0.60 (0.45)	0.76	2386.7	425.00
3	2269.70	19.54	0.780	0.60 (0.45)	0.76	2420.7	400.00
4	2271.56	21.19	0.740	0.60 (0.45)	0.75	2702.8	300.00
5	2243.25	29.09	0.600	0.60 (0.45)	0.75	4030.0	210.00
6	2232.27	29.93	0.588	0.60 (0.45)	0.75	4163.7	410.00
7	2231.15	31.76	0.573	0.60 (0.45)	0.75	4457.4	50600.00
8	2230.62	32.06	0.570	0.60 (0.45)	0.75	4508.5	200.00
9	2230.58	32.18	0.569	0.60 (0.45)	0.75	4528.3	50700.00
10	2229.47	33.64	0.557	0.60 (0.45)	0.75	4762.8	230.00
11	2225.05	34.85	0.547	0.60 (0.45)	0.75	4949.2	220.50
12	2225.00	34.86	0.547	0.60 (0.45)	0.75	4950.7	200.00
13	2189.43	38.84	0.515	0.60 (0.45)	0.76	5763.1	50500.00
14	2167.33	42.18	0.493	0.60 (0.46)	0.76	6430.0	110.00
15	2101.30	46.11	0.470	0.60 (0.46)	0.76	7214.7	100.00
16	2064.39	48.49	0.457	0.60 (0.46)	0.76	7685.6	100.00
17	2015.87	52.20	0.435	0.60 (0.46)	0.77	8408.8	100.00
18	1953.53	55.51	0.416	0.60 (0.46)	0.77	9089.5	130.00
19	1867.43	61.08	0.388	0.60 (0.47)	0.78	10248.6	150.00
20	1596.68	82.51	0.349	0.60 (0.49)	0.82	14371.9	50100.00
21	1576.09	88.59	0.339	0.60 (0.50)	0.83	15766.2	20100.00
22	1529.01	100.68	0.316	0.60 (0.50)	0.84	18355.8	13600.00
23	1505.73	108.44	0.302	0.60 (0.51)	0.85	20013.7	13100.00
24	1475.45	131.07	0.270	0.60 (0.52)	0.87	24221.2	11831.00
25	1514.23	154.65	0.249	0.60 (0.53)	0.88	28774.2	11530.00
26	1548.69	174.20	0.231	0.60 (0.54)	0.90	33145.1	11000.00
27	1608.25	196.50	0.221	0.60 (0.55)	0.92	40196.7	10850.00
28	1509.17	212.34	0.216	0.60 (0.55)	0.92	43690.6	11220.00
29	1494.67	214.70	0.215	0.60 (0.55)	0.92	44074.0	13510.00
30	1440.79	223.90	0.212	0.60 (0.55)	0.92	45505.3	10910.00
31	1440.32	224.01	0.212	0.60 (0.55)	0.92	45522.8	13500.00
32	1255.08	264.92	0.200	0.60 (0.56)	0.93	52087.3	12410.00
33	1190.16	298.12	0.189	0.60 (0.56)	0.94	58173.2	12261.00
34	1167.54	310.97	0.185	0.60 (0.56)	0.94	59659.8	10410.00
35	1145.48	323.24	0.181	0.60 (0.56)	0.94	60761.8	12101.10
36	1095.64	350.94	0.173	0.60 (0.57)	0.94	63139.9	10200.00
37	1071.03	364.43	0.170	0.60 (0.57)	0.94	64078.1	12010.00
38	1016.44	393.81	0.166	0.60 (0.57)	0.94	64751.8	10210.00
39	943.78	443.37	0.161	0.60 (0.57)	0.94	65250.9	12000.00
40	886.11	513.26	0.154	0.60 (0.57)	0.94	65835.7	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 2271.56 Tc (MIN.) = 21.19  
AREA-AVERAGED Fm (INCH/HR) = 0.45 AREA-AVERAGED Fp (INCH/HR) = 0.60  
AREA-AVERAGED Ap = 0.75 EFFECTIVE AREA (ACRES) = 2702.84

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 12

>>>> CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*



FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506101G.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4.52	82.13	0.60	( 0.59)	0.98	591.0	10100.00
TOTAL AREA (ACRES) =							591.0

\*\*\*\*\*

FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2261.00	17.52	0.847	0.60 ( 0.46)	0.76	2076.7	429.00
2	2269.18	19.34	0.787	0.60 ( 0.45)	0.76	2386.7	425.00
3	2269.70	19.54	0.780	0.60 ( 0.45)	0.76	2420.7	400.00
4	2271.56	21.19	0.740	0.60 ( 0.45)	0.75	2702.8	300.00
5	2243.25	29.09	0.600	0.60 ( 0.45)	0.75	4030.0	210.00
6	2232.27	29.93	0.588	0.60 ( 0.45)	0.75	4163.7	410.00
7	2231.15	31.76	0.573	0.60 ( 0.45)	0.75	4457.4	50600.00
8	2230.62	32.06	0.570	0.60 ( 0.45)	0.75	4508.5	200.00
9	2230.58	32.18	0.569	0.60 ( 0.45)	0.75	4528.3	50700.00
10	2229.47	33.64	0.557	0.60 ( 0.45)	0.75	4762.8	230.00
11	2225.05	34.85	0.547	0.60 ( 0.45)	0.75	4949.2	220.50
12	2225.00	34.86	0.547	0.60 ( 0.45)	0.75	4950.7	200.00
13	2189.43	38.84	0.515	0.60 ( 0.45)	0.76	5763.1	50500.00
14	2167.33	42.18	0.493	0.60 ( 0.46)	0.76	6430.0	110.00
15	2101.30	46.11	0.470	0.60 ( 0.46)	0.76	7214.7	100.00
16	2064.39	48.49	0.457	0.60 ( 0.46)	0.76	7685.6	100.00
17	2015.87	52.20	0.435	0.60 ( 0.46)	0.77	8408.8	100.00
18	1953.53	55.51	0.416	0.60 ( 0.46)	0.77	9089.5	130.00
19	1867.43	61.08	0.388	0.60 ( 0.47)	0.78	10248.6	150.00
20	1596.68	82.51	0.349	0.60 ( 0.49)	0.82	14371.9	50100.00
21	1576.09	88.59	0.339	0.60 ( 0.50)	0.83	15766.2	20100.00
22	1529.01	100.68	0.316	0.60 ( 0.50)	0.84	18355.8	13600.00
23	1505.73	108.44	0.302	0.60 ( 0.51)	0.85	20013.7	13100.00
24	1475.45	131.07	0.270	0.60 ( 0.52)	0.87	24221.2	11831.00
25	1514.23	154.65	0.249	0.60 ( 0.53)	0.88	28774.2	11530.00
26	1548.69	174.20	0.231	0.60 ( 0.54)	0.90	33145.1	11000.00
27	1608.25	196.50	0.221	0.60 ( 0.55)	0.92	40196.7	10850.00
28	1509.17	212.34	0.216	0.60 ( 0.55)	0.92	43690.6	11220.00
29	1494.67	214.70	0.215	0.60 ( 0.55)	0.92	44074.0	13510.00
30	1440.79	223.90	0.212	0.60 ( 0.55)	0.92	45505.3	10910.00
31	1440.32	224.01	0.212	0.60 ( 0.55)	0.92	45522.8	13500.00
32	1255.08	264.92	0.200	0.60 ( 0.56)	0.93	52087.3	12410.00
33	1190.16	298.12	0.189	0.60 ( 0.56)	0.94	58173.2	12261.00
34	1167.54	310.97	0.185	0.60 ( 0.56)	0.94	59659.8	10410.00
35	1145.48	323.24	0.181	0.60 ( 0.56)	0.94	60761.8	12101.10
36	1095.64	350.94	0.173	0.60 ( 0.57)	0.94	63139.9	10200.00
37	1071.03	364.43	0.170	0.60 ( 0.57)	0.94	64078.1	12010.00
38	1016.44	393.81	0.166	0.60 ( 0.57)	0.94	64751.8	10210.00

39 943.78 443.37 0.161 0.60 ( 0.57) 0.94 65250.9 12000.00  
40 886.11 513.26 0.154 0.60 ( 0.57) 0.94 65835.7 10100.00  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124294.87 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4.52	82.13	0.350	0.60 ( 0.59)	0.98	591.0	10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 =							14677.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2263.34	17.52	0.847	0.60 ( 0.46)	0.77	2202.8	429.00
2	2271.57	19.34	0.787	0.60 ( 0.46)	0.77	2525.8	425.00
3	2272.10	19.54	0.780	0.60 ( 0.46)	0.77	2561.3	400.00
4	2274.03	21.19	0.740	0.60 ( 0.46)	0.77	2855.3	300.00
5	2246.00	29.09	0.600	0.60 ( 0.46)	0.76	4239.4	210.00
6	2235.03	29.93	0.588	0.60 ( 0.46)	0.76	4379.0	410.00
7	2234.01	31.76	0.573	0.60 ( 0.46)	0.76	4686.0	50600.00
8	2233.49	32.06	0.570	0.60 ( 0.46)	0.76	4739.2	200.00
9	2233.46	32.18	0.569	0.60 ( 0.46)	0.76	4759.9	50700.00
10	2232.42	33.64	0.557	0.60 ( 0.46)	0.76	5004.9	230.00
11	2228.04	34.85	0.547	0.60 ( 0.46)	0.76	5200.0	220.50
12	2227.99	34.86	0.547	0.60 ( 0.46)	0.76	5201.6	200.00
13	2192.57	38.84	0.515	0.60 ( 0.46)	0.77	6042.6	50500.00
14	2170.60	42.18	0.493	0.60 ( 0.46)	0.77	6733.5	110.00
15	2104.71	46.11	0.470	0.60 ( 0.46)	0.77	7546.5	100.00
16	2067.87	48.49	0.457	0.60 ( 0.46)	0.77	8034.5	100.00
17	2019.44	52.20	0.435	0.60 ( 0.47)	0.78	8784.4	100.00
18	1957.16	55.51	0.416	0.60 ( 0.47)	0.78	9489.0	130.00
19	1871.16	61.08	0.388	0.60 ( 0.47)	0.79	10688.1	150.00
20	1606.03	82.13	0.350	0.60 ( 0.49)	0.82	14889.2	10100.00
21	1601.19	82.51	0.349	0.60 ( 0.49)	0.82	14962.9	50100.00
22	1580.46	88.59	0.339	0.60 ( 0.50)	0.83	16357.2	20100.00
23	1533.09	100.68	0.316	0.60 ( 0.51)	0.84	18946.8	13600.00
24	1509.63	108.44	0.302	0.60 ( 0.51)	0.85	20604.7	13100.00
25	1478.94	131.07	0.270	0.60 ( 0.52)	0.87	24812.2	11831.00
26	1517.44	154.65	0.249	0.60 ( 0.53)	0.89	29365.2	11530.00
27	1551.67	174.20	0.231	0.60 ( 0.54)	0.90	33736.1	11000.00
28	1611.10	196.50	0.221	0.60 ( 0.55)	0.92	40787.7	10850.00
29	1511.96	212.34	0.216	0.60 ( 0.55)	0.92	44281.6	11220.00
30	1497.44	214.70	0.215	0.60 ( 0.55)	0.92	44665.0	13510.00
31	1443.53	223.90	0.212	0.60 ( 0.56)	0.93	46096.3	10910.00
32	1443.06	224.01	0.212	0.60 ( 0.56)	0.93	46113.8	13500.00
33	1257.65	264.92	0.200	0.60 ( 0.56)	0.93	52678.3	12410.00
34	1192.60	298.12	0.189	0.60 ( 0.56)	0.94	58764.2	12261.00
35	1169.93	310.97	0.185	0.60 ( 0.56)	0.94	60250.8	10410.00
36	1147.82	323.24	0.181	0.60 ( 0.56)	0.94	61352.8	12101.10
37	1097.87	350.94	0.173	0.60 ( 0.57)	0.94	63730.9	10200.00
38	1073.22	364.43	0.170	0.60 ( 0.57)	0.94	64669.1	12010.00
39	1018.58	393.81	0.166	0.60 ( 0.57)	0.94	65342.8	10210.00
40	945.86	443.37	0.161	0.60 ( 0.57)	0.94	65841.9	12000.00
41	888.09	513.26	0.154	0.60 ( 0.57)	0.95	66426.7	10100.00
TOTAL AREA (ACRES) =						66426.7	

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 2274.03 Tc (MIN.) = 21.186

EFFECTIVE AREA(ACRES) = 2855.29 AREA-AVERAGED Fm(INCH/HR) = 0.46  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.77  
 TOTAL AREA(ACRES) = 66426.7  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124294.87 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13412.00 TO NODE 13700.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 176.93 DOWNSTREAM(FEET) = 173.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 260.10 CHANNEL SLOPE = 0.0151  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
 CHANNEL FLOW THRU SUBAREA(CFS) = 2274.03  
 FLOW VELOCITY(FEET/SEC.) = 14.00 FLOW DEPTH(FEET) = 7.36  
 TRAVEL TIME(MIN.) = 0.31 Tc(MIN.) = 21.50  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124554.97 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2263.34	17.83	0.837	0.60( 0.46)	0.77	2202.8	429.00
2	2271.57	19.65	0.777	0.60( 0.46)	0.77	2525.8	425.00
3	2272.10	19.84	0.770	0.60( 0.46)	0.77	2561.3	400.00
4	2274.03	21.50	0.734	0.60( 0.46)	0.77	2855.3	300.00
5	2246.00	29.40	0.596	0.60( 0.46)	0.76	4239.4	210.00
6	2235.03	30.24	0.585	0.60( 0.46)	0.76	4379.0	410.00
7	2234.01	32.07	0.570	0.60( 0.46)	0.76	4686.0	50600.00
8	2233.49	32.37	0.568	0.60( 0.46)	0.76	4739.2	200.00
9	2233.46	32.49	0.567	0.60( 0.46)	0.76	4759.9	50700.00
10	2232.42	33.96	0.555	0.60( 0.46)	0.76	5004.9	230.00
11	2228.04	35.16	0.545	0.60( 0.46)	0.76	5200.0	220.50
12	2227.99	35.17	0.545	0.60( 0.46)	0.76	5201.6	200.00
13	2192.57	39.15	0.512	0.60( 0.46)	0.77	6042.6	50500.00
14	2170.60	42.50	0.491	0.60( 0.46)	0.77	6733.5	110.00
15	2104.71	46.42	0.468	0.60( 0.46)	0.77	7546.5	100.00
16	2067.87	48.81	0.455	0.60( 0.46)	0.77	8034.5	100.00
17	2019.44	52.51	0.433	0.60( 0.47)	0.78	8784.4	100.00
18	1957.16	55.83	0.414	0.60( 0.47)	0.78	9489.0	130.00
19	1871.16	61.40	0.387	0.60( 0.47)	0.79	10688.1	150.00
20	1606.03	82.47	0.350	0.60( 0.49)	0.82	14889.2	10100.00
21	1601.19	82.85	0.349	0.60( 0.49)	0.82	14962.9	50100.00
22	1580.46	88.93	0.338	0.60( 0.50)	0.83	16357.2	20100.00
23	1533.09	101.02	0.315	0.60( 0.51)	0.84	18946.8	13600.00
24	1509.63	108.78	0.301	0.60( 0.51)	0.85	20604.7	13100.00
25	1478.94	131.41	0.270	0.60( 0.52)	0.87	24812.2	11831.00
26	1517.44	154.99	0.249	0.60( 0.53)	0.89	29365.2	11530.00
27	1551.67	174.54	0.231	0.60( 0.54)	0.90	33736.1	11000.00
28	1611.10	196.84	0.221	0.60( 0.55)	0.92	40787.7	10850.00
29	1511.96	212.68	0.216	0.60( 0.55)	0.92	44281.6	11220.00
30	1497.44	215.04	0.215	0.60( 0.55)	0.92	44665.0	13510.00
31	1443.53	224.25	0.212	0.60( 0.56)	0.93	46096.3	10910.00
32	1443.06	224.36	0.212	0.60( 0.56)	0.93	46113.8	13500.00
33	1257.65	265.28	0.199	0.60( 0.56)	0.93	52678.3	12410.00
34	1192.60	298.48	0.189	0.60( 0.56)	0.94	58764.2	12261.00
35	1169.93	311.34	0.185	0.60( 0.56)	0.94	60250.8	10410.00

36	1147.82	323.61	0.181	0.60( 0.56)	0.94	61352.8	12101.10
37	1097.87	351.32	0.173	0.60( 0.57)	0.94	63730.9	10200.00
38	1073.22	364.81	0.169	0.60( 0.57)	0.94	64669.1	12010.00
39	1018.58	394.19	0.166	0.60( 0.57)	0.94	65342.8	10210.00
40	945.86	443.75	0.161	0.60( 0.57)	0.94	65841.9	12000.00
41	888.09	513.65	0.154	0.60( 0.57)	0.95	66426.7	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2274.03 Tc(MIN.) = 21.50  
 AREA-AVERAGED Fm(INCH/HR) = 0.46 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.77 EFFECTIVE AREA(ACRES) = 2855.29

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 2 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 0610508T.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	5.79	30.21	0.60( 0.59)	0.99	131.3	50800.00
TOTAL AREA(ACRES) =			131.3			

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2263.34	17.83	0.837	0.60( 0.46)	0.77	2202.8	429.00
2	2271.57	19.65	0.777	0.60( 0.46)	0.77	2525.8	425.00
3	2272.10	19.84	0.770	0.60( 0.46)	0.77	2561.3	400.00
4	2274.03	21.50	0.734	0.60( 0.46)	0.77	2855.3	300.00
5	2246.00	29.40	0.596	0.60( 0.46)	0.76	4239.4	210.00
6	2235.03	30.24	0.585	0.60( 0.46)	0.76	4379.0	410.00
7	2234.01	32.07	0.570	0.60( 0.46)	0.76	4686.0	50600.00
8	2233.49	32.37	0.568	0.60( 0.46)	0.76	4739.2	200.00
9	2233.46	32.49	0.567	0.60( 0.46)	0.76	4759.9	50700.00
10	2232.42	33.96	0.555	0.60( 0.46)	0.76	5004.9	230.00
11	2228.04	35.16	0.545	0.60( 0.46)	0.76	5200.0	220.50
12	2227.99	35.17	0.545	0.60( 0.46)	0.76	5201.6	200.00
13	2192.57	39.15	0.512	0.60( 0.46)	0.77	6042.6	50500.00
14	2170.60	42.50	0.491	0.60( 0.46)	0.77	6733.5	110.00
15	2104.71	46.42	0.468	0.60( 0.46)	0.77	7546.5	100.00
16	2067.87	48.81	0.455	0.60( 0.46)	0.77	8034.5	100.00
17	2019.44	52.51	0.433	0.60( 0.47)	0.78	8784.4	100.00
18	1957.16	55.83	0.414	0.60( 0.47)	0.78	9489.0	130.00
19	1871.16	61.40	0.387	0.60( 0.47)	0.79	10688.1	150.00
20	1606.03	82.47	0.350	0.60( 0.49)	0.82	14889.2	10100.00

21	1601.19	82.85	0.349	0.60 ( 0.49)	0.82	14962.9	50100.00
22	1580.46	88.93	0.338	0.60 ( 0.50)	0.83	16357.2	20100.00
23	1533.09	101.02	0.315	0.60 ( 0.51)	0.84	18946.8	13600.00
24	1509.63	108.78	0.301	0.60 ( 0.51)	0.85	20604.7	13100.00
25	1478.94	131.41	0.270	0.60 ( 0.52)	0.87	24812.2	11831.00
26	1517.44	154.99	0.249	0.60 ( 0.53)	0.89	29365.2	11530.00
27	1551.67	174.54	0.231	0.60 ( 0.54)	0.90	33736.1	11000.00
28	1611.10	196.84	0.221	0.60 ( 0.55)	0.92	40787.7	10850.00
29	1511.96	212.68	0.216	0.60 ( 0.55)	0.92	44281.6	11220.00
30	1497.44	215.04	0.215	0.60 ( 0.55)	0.92	44665.0	13510.00
31	1443.53	224.25	0.212	0.60 ( 0.56)	0.93	46096.3	10910.00
32	1443.06	224.36	0.212	0.60 ( 0.56)	0.93	46113.8	13500.00
33	1257.65	265.28	0.199	0.60 ( 0.56)	0.93	52678.3	12410.00
34	1192.60	298.48	0.189	0.60 ( 0.56)	0.94	58764.2	12261.00
35	1169.93	311.34	0.185	0.60 ( 0.56)	0.94	60250.8	10410.00
36	1147.82	323.61	0.181	0.60 ( 0.56)	0.94	61352.8	12101.10
37	1097.87	351.32	0.173	0.60 ( 0.57)	0.94	63730.9	10200.00
38	1073.22	364.81	0.169	0.60 ( 0.57)	0.94	64669.1	12010.00
39	1018.58	394.19	0.166	0.60 ( 0.57)	0.94	65342.8	10210.00
40	945.86	443.75	0.161	0.60 ( 0.57)	0.94	65841.9	12000.00
41	888.09	513.65	0.154	0.60 ( 0.57)	0.95	66426.7	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124554.97 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	5.79	30.21	0.585	0.60 ( 0.59)	0.99	131.3	50800.00

LONGEST FLOWPATH FROM NODE 50800.00 TO NODE 13700.00 = 5946.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2268.22	17.83	0.837	0.60 ( 0.47)	0.78	2280.2	429.00
2	2276.57	19.65	0.777	0.60 ( 0.47)	0.78	2611.2	425.00
3	2277.10	19.84	0.770	0.60 ( 0.47)	0.78	2647.5	400.00
4	2279.20	21.50	0.734	0.60 ( 0.46)	0.77	2948.7	300.00
5	2251.73	29.40	0.596	0.60 ( 0.46)	0.77	4367.2	210.00
6	2241.24	30.21	0.585	0.60 ( 0.46)	0.77	4505.0	50800.00
7	2240.82	30.24	0.585	0.60 ( 0.46)	0.77	4510.3	410.00
8	2239.65	32.07	0.570	0.60 ( 0.46)	0.77	4817.2	50600.00
9	2239.11	32.37	0.568	0.60 ( 0.46)	0.77	4870.5	200.00
10	2239.06	32.49	0.567	0.60 ( 0.46)	0.77	4891.1	50700.00
11	2237.90	33.96	0.555	0.60 ( 0.46)	0.77	5136.2	230.00
12	2233.43	35.16	0.545	0.60 ( 0.46)	0.77	5331.3	220.50
13	2233.38	35.17	0.545	0.60 ( 0.46)	0.77	5332.8	200.00
14	2197.63	39.15	0.512	0.60 ( 0.46)	0.77	6173.8	50500.00
15	2175.45	42.50	0.491	0.60 ( 0.46)	0.77	6864.8	110.00
16	2109.34	46.42	0.468	0.60 ( 0.46)	0.77	7677.8	100.00
17	2072.37	48.81	0.455	0.60 ( 0.47)	0.78	8165.8	100.00
18	2023.73	52.51	0.433	0.60 ( 0.47)	0.78	8915.7	100.00
19	1961.26	55.83	0.414	0.60 ( 0.47)	0.78	9620.2	130.00
20	1874.99	61.40	0.387	0.60 ( 0.48)	0.79	10819.4	150.00
21	1609.49	82.47	0.350	0.60 ( 0.50)	0.83	15020.5	10100.00
22	1604.64	82.85	0.349	0.60 ( 0.50)	0.83	15094.1	50100.00
23	1583.80	88.93	0.338	0.60 ( 0.50)	0.83	16488.5	20100.00
24	1536.21	101.02	0.315	0.60 ( 0.51)	0.84	19078.0	13600.00
25	1512.60	108.78	0.301	0.60 ( 0.51)	0.85	20736.0	13100.00
26	1481.61	131.41	0.270	0.60 ( 0.52)	0.87	24943.4	11831.00

27	1519.90	154.99	0.249	0.60 ( 0.53)	0.89	29496.4	11530.00
28	1553.96	174.54	0.231	0.60 ( 0.54)	0.90	33867.4	11000.00
29	1613.28	196.84	0.221	0.60 ( 0.55)	0.92	40919.0	10850.00
30	1514.10	212.68	0.216	0.60 ( 0.55)	0.92	44412.9	11220.00
31	1499.57	215.04	0.215	0.60 ( 0.55)	0.92	44796.3	13510.00
32	1445.63	224.25	0.212	0.60 ( 0.56)	0.93	46227.6	10910.00
33	1445.16	224.36	0.212	0.60 ( 0.56)	0.93	46245.0	13500.00
34	1259.63	265.28	0.199	0.60 ( 0.56)	0.93	52809.6	12410.00
35	1194.48	298.48	0.189	0.60 ( 0.56)	0.94	58895.5	12261.00
36	1171.76	311.34	0.185	0.60 ( 0.56)	0.94	60382.1	10410.00
37	1149.61	323.61	0.181	0.60 ( 0.56)	0.94	61484.1	12101.10
38	1099.57	351.32	0.173	0.60 ( 0.57)	0.94	63862.1	10200.00
39	1074.90	364.81	0.169	0.60 ( 0.57)	0.94	64800.4	12010.00
40	1020.23	394.19	0.166	0.60 ( 0.57)	0.94	65474.1	10210.00
41	947.45	443.75	0.161	0.60 ( 0.57)	0.94	65973.2	12000.00
42	889.61	513.65	0.154	0.60 ( 0.57)	0.95	66557.9	10100.00

TOTAL AREA (ACRES) = 66557.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 2279.20 Tc (MIN.) = 21.496  
EFFECTIVE AREA (ACRES) = 2948.71 AREA-AVERAGED Fm (INCH/HR) = 0.46  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.77  
TOTAL AREA (ACRES) = 66557.9  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124554.97 FEET.

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 66557.9 TC (MIN.) = 21.50  
EFFECTIVE AREA (ACRES) = 2948.71 AREA-AVERAGED Fm (INCH/HR) = 0.46  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.774  
PEAK FLOW RATE (CFS) = 2279.20

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2268.22	17.83	0.837	0.60 ( 0.47)	0.78	2280.2	429.00
2	2276.57	19.65	0.777	0.60 ( 0.47)	0.78	2611.2	425.00
3	2277.10	19.84	0.770	0.60 ( 0.47)	0.78	2647.5	400.00
4	2279.20	21.50	0.734	0.60 ( 0.46)	0.77	2948.7	300.00
5	2251.73	29.40	0.596	0.60 ( 0.46)	0.77	4367.2	210.00
6	2241.24	30.21	0.585	0.60 ( 0.46)	0.77	4505.0	50800.00
7	2240.82	30.24	0.585	0.60 ( 0.46)	0.77	4510.3	410.00
8	2239.65	32.07	0.570	0.60 ( 0.46)	0.77	4817.2	50600.00
9	2239.11	32.37	0.568	0.60 ( 0.46)	0.77	4870.5	200.00
10	2239.06	32.49	0.567	0.60 ( 0.46)	0.77	4891.1	50700.00
11	2237.90	33.96	0.555	0.60 ( 0.46)	0.77	5136.2	230.00
12	2233.43	35.16	0.545	0.60 ( 0.46)	0.77	5331.3	220.50
13	2233.38	35.17	0.545	0.60 ( 0.46)	0.77	5332.8	200.00
14	2197.63	39.15	0.512	0.60 ( 0.46)	0.77	6173.8	50500.00
15	2175.45	42.50	0.491	0.60 ( 0.46)	0.77	6864.8	110.00
16	2109.34	46.42	0.468	0.60 ( 0.46)	0.77	7677.8	100.00
17	2072.37	48.81	0.455	0.60 ( 0.47)	0.78	8165.8	100.00
18	2023.73	52.51	0.433	0.60 ( 0.47)	0.78	8915.7	100.00
19	1961.26	55.83	0.414	0.60 ( 0.47)	0.78	9620.2	130.00
20	1874.99	61.40	0.387	0.60 ( 0.48)	0.79	10819.4	150.00
21	1609.49	82.47	0.350	0.60 ( 0.50)	0.83	15020.5	10100.00
22	1604.64	82.85	0.349	0.60 ( 0.50)	0.83	15094.1	50100.00
23	1583.80	88.93	0.338	0.60 ( 0.50)	0.83	16488.5	20100.00
24	1536.21	101.02	0.315	0.60 ( 0.51)	0.84	19078.0	13600.00

25	1512.60	108.78	0.301	0.60	( 0.51)	0.85	20736.0	13100.00
26	1481.61	131.41	0.270	0.60	( 0.52)	0.87	24943.4	11831.00
27	1519.90	154.99	0.249	0.60	( 0.53)	0.89	29496.4	11530.00
28	1553.96	174.54	0.231	0.60	( 0.54)	0.90	33867.4	11000.00
29	1613.28	196.84	0.221	0.60	( 0.55)	0.92	40919.0	10850.00
30	1514.10	212.68	0.216	0.60	( 0.55)	0.92	44412.9	11220.00
31	1499.57	215.04	0.215	0.60	( 0.55)	0.92	44796.3	13510.00
32	1445.63	224.25	0.212	0.60	( 0.56)	0.93	46227.6	10910.00
33	1445.16	224.36	0.212	0.60	( 0.56)	0.93	46245.0	13500.00
34	1259.63	265.28	0.199	0.60	( 0.56)	0.93	52809.6	12410.00
35	1194.48	298.48	0.189	0.60	( 0.56)	0.94	58895.5	12261.00
36	1171.76	311.34	0.185	0.60	( 0.56)	0.94	60382.1	10410.00
37	1149.61	323.61	0.181	0.60	( 0.56)	0.94	61484.1	12101.10
38	1099.57	351.32	0.173	0.60	( 0.57)	0.94	63862.1	10200.00
39	1074.90	364.81	0.169	0.60	( 0.57)	0.94	64800.4	12010.00
40	1020.23	394.19	0.166	0.60	( 0.57)	0.94	65474.1	10210.00
41	947.45	443.75	0.161	0.60	( 0.57)	0.94	65973.2	12000.00
42	889.61	513.65	0.154	0.60	( 0.57)	0.95	66557.9	10100.00

=====  
=====  
END OF RATIONAL METHOD ANALYSIS

\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA 92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S36- FREE DRAINING - PHASE CONDITION NO PA5 \*  
\* 2-YR RM EV APRIL 2019 ROKAMOTO \*  
\*\*\*\*\*

FILE NAME: RI02EV36.DAT  
TIME/DATE OF STUDY: 12:44 04/05/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 2.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*

NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 1.806
- 2) 10.00; 1.204
- 3) 15.00; 0.925
- 4) 20.00; 0.762
- 5) 25.00; 0.659
- 6) 30.00; 0.585
- 7) 40.00; 0.504
- 8) 50.00; 0.447
- 9) 60.00; 0.390
- 10) 90.00; 0.336
- 11) 120.00; 0.280
- 12) 180.00; 0.226
- 13) 360.00; 0.170
- 14) 1200.00; 0.080

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:

- 1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13600.00 TO NODE 13600.50 IS CODE = 21  
-----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 488.61  
ELEVATION DATA: UPSTREAM(FEET) = 872.12 DOWNSTREAM(FEET) = 744.80

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 10.995  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 1.148  
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "OPEN BRUSH"	-	3.39	0.60	1.000	0	11.00

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA RUNOFF(CFS) = 1.67  
TOTAL AREA(ACRES) = 3.39 PEAK FLOW RATE(CFS) = 1.67

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13600.50 TO NODE 13601.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 744.80 DOWNSTREAM(FEET) = 707.32  
CHANNEL LENGTH THRU SUBAREA(FEET) = 418.30 CHANNEL SLOPE = 0.0896  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 1.024  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.45	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3.10  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.13  
AVERAGE FLOW DEPTH(FEET) = 0.58 TRAVEL TIME(MIN.) = 2.23  
Tc(MIN.) = 13.22  
SUBAREA AREA(ACRES) = 7.45 SUBAREA RUNOFF(CFS) = 2.84  
EFFECTIVE AREA(ACRES) = 10.84 AREA-AVERAGED Fm(INCH/HR) = 0.60  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 10.8 PEAK FLOW RATE(CFS) = 4.14

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.64 FLOW VELOCITY(FEET/SEC.) = 3.33  
LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13601.00 = 906.91 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13601.00 TO NODE 13602.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 707.32 DOWNSTREAM(FEET) = 657.12
CHANNEL LENGTH THRU SUBAREA(FEET) = 777.60 CHANNEL SLOPE = 0.0646
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.862

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include USER-DEFINED entries with various area and loss rate values.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 7.89
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.50
AVERAGE FLOW DEPTH(FEET) = 0.87 TRAVEL TIME(MIN.) = 3.70
Tc(MIN.) = 16.93
SUBAREA AREA(ACRES) = 30.96 SUBAREA RUNOFF(CFS) = 7.31
EFFECTIVE AREA(ACRES) = 41.80 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 41.8 PEAK FLOW RATE(CFS) = 9.87

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.94 FLOW VELOCITY(FEET/SEC.) = 3.70
LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13602.00 = 1684.51 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 13602.00 TO NODE 13603.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 657.12 DOWNSTREAM(FEET) = 584.58
CHANNEL LENGTH THRU SUBAREA(FEET) = 1186.54 CHANNEL SLOPE = 0.0611
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.716

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include USER-DEFINED entries with various area and loss rate values.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 11.12
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.73
AVERAGE FLOW DEPTH(FEET) = 1.00 TRAVEL TIME(MIN.) = 5.30
Tc(MIN.) = 22.23
SUBAREA AREA(ACRES) = 23.36 SUBAREA RUNOFF(CFS) = 2.44

EFFECTIVE AREA(ACRES) = 65.16 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 65.2 PEAK FLOW RATE(CFS) = 9.87
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.96 FLOW VELOCITY(FEET/SEC.) = 3.60
LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13603.00 = 2871.05 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 584.58 DOWNSTREAM(FEET) = 544.91
CHANNEL LENGTH THRU SUBAREA(FEET) = 860.98 CHANNEL SLOPE = 0.0461
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.635

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include USER-DEFINED entries with various area and loss rate values.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 10.22
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.28
AVERAGE FLOW DEPTH(FEET) = 1.02 TRAVEL TIME(MIN.) = 4.38
Tc(MIN.) = 26.60

SUBAREA AREA(ACRES) = 21.24 SUBAREA RUNOFF(CFS) = 0.68
EFFECTIVE AREA(ACRES) = 86.40 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 86.4 PEAK FLOW RATE(CFS) = 9.87
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.00 FLOW VELOCITY(FEET/SEC.) = 3.26
LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13620.00 = 3732.03 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<

\*\*\*\*\*
FLOW PROCESS FROM NODE 13522.00 TO NODE 13522.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: S35X02.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:

```

STREAM      Q      Tc      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS) (MIN.) (INCH/HR)      (ACRES)      NODE
1           18.94 124.94 0.60( 0.57) 0.95    1542.7 13510.00
2           19.25 134.44 0.60( 0.57) 0.94    1579.8 13500.00
TOTAL AREA(ACRES) =      1579.8

```

```

*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13522.00 IS CODE = 14.0
-----

```

```

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<
=====

```

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

```

STREAM      Q      Tc      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS) (MIN.) (INCH/HR)      (ACRES)      NODE
1           18.94 124.94 0.60( 0.57) 0.95    1542.7 13510.00
2           19.25 134.44 0.60( 0.57) 0.94    1579.8 13500.00
TOTAL AREA(ACRES) =      1579.8

```

```

*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13620.00 IS CODE = 51
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<
=====

```

```

ELEVATION DATA: UPSTREAM(FEET) = 632.19 DOWNSTREAM(FEET) = 544.91
CHANNEL LENGTH THRU SUBAREA(FEET) = 2062.96 CHANNEL SLOPE = 0.0423
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00

```

\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.261

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	17.68	0.60	1.000	-
USER-DEFINED	-	2.36	0.60	1.000	-
USER-DEFINED	-	0.60	0.60	1.000	-
USER-DEFINED	-	0.22	0.60	1.000	-
USER-DEFINED	-	2.22	0.60	1.000	-
USER-DEFINED	-	3.42	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 19.25

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.06

AVERAGE FLOW DEPTH(FEET) = 1.13 TRAVEL TIME(MIN.) = 6.80

Tc(MIN.) = 141.24

SUBAREA AREA(ACRES) = 26.50 SUBAREA RUNOFF(CFS) = 0.00

EFFECTIVE AREA(ACRES) = 1606.33 AREA-AVERAGED Fm(INCH/HR) = 0.57

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.95

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 1606.3 PEAK FLOW RATE(CFS) = 20.58

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.16 FLOW VELOCITY(FEET/SEC.) = 5.13

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

```

*****
FLOW PROCESS FROM NODE 13620.00 TO NODE 13620.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====

```

MAINLINE Tc(MIN.) = 141.24

\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.261

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.44	0.60	1.000	-
USER-DEFINED	-	0.01	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 1.45 SUBAREA RUNOFF(CFS) = 0.00

EFFECTIVE AREA(ACRES) = 1607.78 AREA-AVERAGED Fm(INCH/HR) = 0.57

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.95

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 1607.8 PEAK FLOW RATE(CFS) = 20.58

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

*****
FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 11
-----

```

```

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<
=====

```

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20.27	131.83	0.269	0.60( 0.57)	0.95	1570.7	13510.00
2	20.58	141.24	0.261	0.60( 0.57)	0.95	1607.8	13500.00

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9.87	26.60	0.635	0.60( 0.60)	1.00	86.4	13600.00

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13620.00 = 3732.03 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	29.08	26.60	0.635	0.60( 0.57)	0.96	403.4	13600.00
2	20.27	131.83	0.269	0.60( 0.57)	0.95	1657.1	13510.00
3	20.58	141.24	0.261	0.60( 0.57)	0.95	1694.2	13500.00

TOTAL AREA(ACRES) = 1694.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 29.08 Tc(MIN.) = 26.603

EFFECTIVE AREA(ACRES) = 403.36 AREA-AVERAGED Fm(INCH/HR) = 0.57

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.95

TOTAL AREA(ACRES) = 1694.2

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

```

*****
FLOW PROCESS FROM NODE 13620.00 TO NODE 13640.00 IS CODE = 51
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 544.91 DOWNSTREAM(FEET) = 489.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1384.37 CHANNEL SLOPE = 0.0404
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.578
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 5.39 0.60 1.000 -
USER-DEFINED - 16.30 0.60 1.000 -
USER-DEFINED - 4.08 0.60 1.000 -
USER-DEFINED - 12.36 0.60 1.000 -
USER-DEFINED - 11.23 0.60 1.000 -
USER-DEFINED - 5.16 0.60 1.000 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 29.08
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.48
AVERAGE FLOW DEPTH(FEET) = 1.33 TRAVEL TIME(MIN.) = 4.21
Tc(MIN.) = 30.82
SUBAREA AREA(ACRES) = 54.52 SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 457.88 AREA-AVERAGED Fm(INCH/HR) = 0.58
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.96
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 1748.7 PEAK FLOW RATE(CFS) = 29.08
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.33 FLOW VELOCITY(FEET/SEC.) = 5.48
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 30.82
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.578
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 53.93 0.60 1.000 -
USER-DEFINED - 0.45 0.60 1.000 -
USER-DEFINED - 3.98 0.60 1.000 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 58.36 SUBAREA RUNOFF(CFS) = 0.00

```

```

EFFECTIVE AREA(ACRES) = 516.24 AREA-AVERAGED Fm(INCH/HR) = 0.58
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.97
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 1807.1 PEAK FLOW RATE(CFS) = 29.08
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 15.1
-----
>>>>DEFINE MEMORY BANK # 3 <<<<
=====
PEAK FLOWRATE TABLE FILE NAME: P201XX02.DNA
MEMORY BANK # 3 DEFINED AS FOLLOWS:
STREAM Q Tc Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 19.79 22.40 0.60(0.51) 0.85 133.8 20100.00
TOTAL AREA(ACRES) = 133.8

```

```

*****
FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 11
-----
>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<
=====

```

```

** MAIN STREAM CONFLUENCE DATA **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 29.08 30.82 0.578 0.60(0.58) 0.97 516.2 13600.00
2 20.27 136.44 0.265 0.60(0.57) 0.95 1770.0 13510.00
3 20.58 145.80 0.257 0.60(0.57) 0.95 1807.1 13500.00
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

```

```

** MEMORY BANK # 3 CONFLUENCE DATA **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 19.79 22.40 0.713 0.60(0.51) 0.85 133.8 20100.00
LONGEST FLOWPATH FROM NODE 20100.00 TO NODE 13640.00 = 5247.00 FEET.

```

```

** PEAK FLOW RATE TABLE **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 48.87 22.40 0.713 0.60(0.56) 0.94 509.0 20100.00
2 37.41 30.82 0.578 0.60(0.57) 0.94 650.0 13600.00
3 24.09 136.44 0.265 0.60(0.57) 0.95 1903.8 13510.00
4 24.27 145.80 0.257 0.60(0.57) 0.94 1940.9 13500.00
TOTAL AREA(ACRES) = 1940.9

```

```

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
PEAK FLOW RATE(CFS) = 48.87 Tc(MIN.) = 22.397
EFFECTIVE AREA(ACRES) = 509.02 AREA-AVERAGED Fm(INCH/HR) = 0.56
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.94
TOTAL AREA(ACRES) = 1940.9
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13640.00 TO NODE 13641.00 IS CODE = 51
-----

```



```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 489.00 DOWNSTREAM(FEET) = 436.89
CHANNEL LENGTH THRU SUBAREA(FEET) = 2994.52 CHANNEL SLOPE = 0.0174
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.558
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.96 0.60 1.000 -
USER-DEFINED - 0.01 0.60 1.000 -
USER-DEFINED - 1.56 0.60 1.000 -
USER-DEFINED - 10.45 0.60 1.000 -
USER-DEFINED - 44.94 0.60 1.000 -
USER-DEFINED - 9.66 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 48.87
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.56
AVERAGE FLOW DEPTH(FEET) = 1.89 TRAVEL TIME(MIN.) = 10.93
Tc(MIN.) = 33.33
SUBAREA AREA(ACRES) = 67.58 SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 576.60 AREA-AVERAGED Fm(INCH/HR) = 0.57
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.94
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 2008.4 PEAK FLOW RATE(CFS) = 48.87
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.89 FLOW VELOCITY(FEET/SEC.) = 4.56
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13641.00 = 25056.61 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13641.00 TO NODE 13641.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====

```

```

MAINLINE Tc(MIN.) = 33.33
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.558
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 16.49 0.60 1.000 -
USER-DEFINED - 20.39 0.60 1.000 -
USER-DEFINED - 7.02 0.60 1.000 -
USER-DEFINED - 12.58 0.60 1.000 -
USER-DEFINED - 42.49 0.60 1.000 -
USER-DEFINED - 5.73 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 104.70 SUBAREA RUNOFF(CFS) = 0.00

```

```

EFFECTIVE AREA(ACRES) = 681.30 AREA-AVERAGED Fm(INCH/HR) = 0.57
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.95
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 2113.1 PEAK FLOW RATE(CFS) = 48.87
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13641.00 TO NODE 13641.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====

```

```

MAINLINE Tc(MIN.) = 33.33
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.558
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 1.78 0.60 1.000 -
USER-DEFINED - 6.25 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 8.03 SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 689.33 AREA-AVERAGED Fm(INCH/HR) = 0.57
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.95
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 2121.2 PEAK FLOW RATE(CFS) = 48.87
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13641.00 TO NODE 13642.00 IS CODE = 51
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====

```

```

ELEVATION DATA: UPSTREAM(FEET) = 436.89 DOWNSTREAM(FEET) = 394.80
CHANNEL LENGTH THRU SUBAREA(FEET) = 2814.16 CHANNEL SLOPE = 0.0150
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.480
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.67 0.60 1.000 -
USER-DEFINED - 24.24 0.60 1.000 -
USER-DEFINED - 1.34 0.60 1.000 -
USER-DEFINED - 74.98 0.60 1.000 -
USER-DEFINED - 101.12 0.60 1.000 -
USER-DEFINED - 16.90 0.60 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 48.87
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.32
AVERAGE FLOW DEPTH(FEET) = 1.94 TRAVEL TIME(MIN.) = 10.87

```

Tc(MIN.) = 44.20  
 SUBAREA AREA(ACRES) = 219.25 SUBAREA RUNOFF(CFS) = 0.00  
 EFFECTIVE AREA(ACRES) = 908.58 AREA-AVERAGED Fm(INCH/HR) = 0.58  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.97  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 2340.4 PEAK FLOW RATE(CFS) = 48.87  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.94 FLOW VELOCITY(FEET/SEC.) = 4.32  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13642.00 = 27870.77 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13642.00 TO NODE 13642.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 44.20  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.480  
 SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	9.95	0.60	1.000	-
USER-DEFINED	-	10.02	0.60	1.000	-
USER-DEFINED	-	4.45	0.60	1.000	-
USER-DEFINED	-	179.37	0.60	1.000	-
USER-DEFINED	-	11.47	0.60	1.000	-
USER-DEFINED	-	0.17	0.60	0.850	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 SUBAREA AREA(ACRES) = 215.43 SUBAREA RUNOFF(CFS) = 0.01  
 EFFECTIVE AREA(ACRES) = 1124.01 AREA-AVERAGED Fm(INCH/HR) = 0.58  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.97  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 2555.8 PEAK FLOW RATE(CFS) = 48.87  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13642.00 TO NODE 13642.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 44.20  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.480  
 SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.03	0.60	0.850	-
USER-DEFINED	-	5.14	0.60	1.000	-
USER-DEFINED	-	11.22	0.60	1.000	-
USER-DEFINED	-	0.33	0.60	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 SUBAREA AREA(ACRES) = 16.72 SUBAREA RUNOFF(CFS) = 0.00  
 EFFECTIVE AREA(ACRES) = 1140.73 AREA-AVERAGED Fm(INCH/HR) = 0.58  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.97  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 2572.6 PEAK FLOW RATE(CFS) = 48.87  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13642.00 TO NODE 13643.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

\*\*\*\*\*  
 ELEVATION DATA: UPSTREAM(FEET) = 394.80 DOWNSTREAM(FEET) = 342.39  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2913.57 CHANNEL SLOPE = 0.0180  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.420  
 SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.22	0.60	1.000	-
USER-DEFINED	-	2.17	0.60	1.000	-
USER-DEFINED	-	9.19	0.60	1.000	-
USER-DEFINED	-	67.57	0.60	1.000	-
USER-DEFINED	-	35.19	0.60	1.000	-
USER-DEFINED	-	30.67	0.60	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 48.87  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.61  
 AVERAGE FLOW DEPTH(FEET) = 1.88 TRAVEL TIME(MIN.) = 10.53  
 Tc(MIN.) = 54.73  
 SUBAREA AREA(ACRES) = 145.01 SUBAREA RUNOFF(CFS) = 0.00  
 EFFECTIVE AREA(ACRES) = 1285.74 AREA-AVERAGED Fm(INCH/HR) = 0.59  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.98  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 2717.6 PEAK FLOW RATE(CFS) = 48.87  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.88 FLOW VELOCITY(FEET/SEC.) = 4.61  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13643.00 = 30784.34 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13643.00 TO NODE 13643.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

\*\*\*\*\*  
 MAINLINE Tc(MIN.) = 54.73  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.420  
 SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.03	0.60	0.850	-
USER-DEFINED	-	5.14	0.60	1.000	-
USER-DEFINED	-	11.22	0.60	1.000	-
USER-DEFINED	-	0.33	0.60	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
USER-DEFINED	-	0.89	0.60	1.000	-
USER-DEFINED	-	20.65	0.60	1.000	-
USER-DEFINED	-	2.69	0.60	1.000	-
USER-DEFINED	-	8.45	0.60	1.000	-
USER-DEFINED	-	96.93	0.60	1.000	-
USER-DEFINED	-	13.19	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
SUBAREA AREA(ACRES) = 142.80 SUBAREA RUNOFF(CFS) = 0.00  
EFFECTIVE AREA(ACRES) = 1428.54 AREA-AVERAGED Fm(INCH/HR) = 0.59  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.98  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
TOTAL AREA(ACRES) = 2860.4 PEAK FLOW RATE(CFS) = 48.87  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13643.00 TO NODE 13643.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
=====

MAINLINE Tc(MIN.) = 54.73  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.420  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	42.54	0.60	1.000	-
USER-DEFINED	-	16.96	0.60	1.000	-
USER-DEFINED	-	80.60	0.60	1.000	-
USER-DEFINED	-	1.56	0.60	1.000	-
USER-DEFINED	-	2.00	0.60	1.000	-
USER-DEFINED	-	3.11	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
SUBAREA AREA(ACRES) = 146.77 SUBAREA RUNOFF(CFS) = 0.00  
EFFECTIVE AREA(ACRES) = 1575.31 AREA-AVERAGED Fm(INCH/HR) = 0.59  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.98  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
TOTAL AREA(ACRES) = 3007.1 PEAK FLOW RATE(CFS) = 48.87  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13643.00 TO NODE 13660.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<  
=====

ELEVATION DATA: UPSTREAM(FEET) = 342.39 DOWNSTREAM(FEET) = 300.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1591.23 CHANNEL SLOPE = 0.0266  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.392

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.89	0.60	1.000	-
USER-DEFINED	-	23.73	0.60	1.000	-
USER-DEFINED	-	0.27	0.60	1.000	-
USER-DEFINED	-	19.87	0.60	1.000	-
USER-DEFINED	-	6.40	0.60	1.000	-
USER-DEFINED	-	3.14	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 48.87  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.35  
AVERAGE FLOW DEPTH(FEET) = 1.74 TRAVEL TIME(MIN.) = 4.95  
Tc(MIN.) = 59.68  
SUBAREA AREA(ACRES) = 54.30 SUBAREA RUNOFF(CFS) = 0.00  
EFFECTIVE AREA(ACRES) = 1629.61 AREA-AVERAGED Fm(INCH/HR) = 0.59  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.98  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
TOTAL AREA(ACRES) = 3061.4 PEAK FLOW RATE(CFS) = 48.87  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 1.74 FLOW VELOCITY(FEET/SEC.) = 5.35  
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 32375.57 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
=====

MAINLINE Tc(MIN.) = 59.68  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.392  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.67	0.60	1.000	-
USER-DEFINED	-	9.52	0.60	1.000	-
USER-DEFINED	-	0.71	0.60	1.000	-
USER-DEFINED	-	0.22	0.60	1.000	-
USER-DEFINED	-	39.42	0.60	1.000	-
USER-DEFINED	-	0.62	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
SUBAREA AREA(ACRES) = 51.16 SUBAREA RUNOFF(CFS) = 0.00  
EFFECTIVE AREA(ACRES) = 1680.77 AREA-AVERAGED Fm(INCH/HR) = 0.59  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.98  
\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
TOTAL AREA(ACRES) = 3112.6 PEAK FLOW RATE(CFS) = 48.87  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 59.68

\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.392

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.11	0.60	1.000	-
USER-DEFINED	-	0.77	0.60	1.000	-
USER-DEFINED	-	0.22	0.60	1.000	-
USER-DEFINED	-	2.69	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 3.79 SUBAREA RUNOFF(CFS) = 0.00

EFFECTIVE AREA(ACRES) = 1684.56 AREA-AVERAGED Fm(INCH/HR) = 0.59

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.98

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 3116.4 PEAK FLOW RATE(CFS) = 48.87

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13643.00 TO NODE 13660.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 13659.00 TO NODE 13659.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<

PEAK FLOWRATE TABLE FILE NAME: 2P02EVAA.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	140.95	18.14	0.60( 0.21)	0.35	167.3	110.00
2	140.05	21.10	0.60( 0.22)	0.37	199.3	100.00
3	133.31	22.95	0.60( 0.22)	0.37	211.1	100.00
4	102.00	28.72	0.60( 0.24)	0.40	221.1	130.00
TOTAL AREA(ACRES) =						221.1

\*\*\*\*\*

FLOW PROCESS FROM NODE 13659.00 TO NODE 13660.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<

>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<

ELEVATION DATA: UPSTREAM( FEET) = 338.00 DOWNSTREAM( FEET) = 300.00

FLOW LENGTH( FEET) = 881.07 MANNING'S N = 0.013

ESTIMATED PIPE DIAMETER( INCH) INCREASED TO 36.000

DEPTH OF FLOW IN 36.0 INCH PIPE IS 15.2 INCHES

PIPE-FLOW VELOCITY( FEET/SEC.) = 17.22

ESTIMATED PIPE DIAMETER( INCH) = 36.00 NUMBER OF PIPES = 1

PIPE-FLOW(CFS) = 48.87

PIPE TRAVEL TIME(MIN.) = 0.85 Tc(MIN.) = 60.53

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	48.87	60.53	0.389	0.60( 0.59)	0.98	1684.6	20100.00
2	37.41	71.62	0.369	0.60( 0.59)	0.98	1825.6	13600.00
3	24.09	182.03	0.225	0.60( 0.58)	0.97	3079.3	13510.00
4	24.27	191.30	0.222	0.60( 0.58)	0.97	3116.4	13500.00
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.							

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	140.95	18.14	0.823	0.60( 0.21)	0.35	167.3	110.00
2	140.05	21.10	0.739	0.60( 0.22)	0.37	199.3	100.00
3	133.31	22.95	0.701	0.60( 0.22)	0.37	211.1	100.00
4	102.00	28.72	0.604	0.60( 0.24)	0.40	221.1	130.00
LONGEST FLOWPATH FROM NODE 130.00 TO NODE 13660.00 = 6327.50 FEET.							

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	171.92	18.14	0.823	0.60( 0.49)	0.83	672.1	110.00
2	172.42	21.10	0.739	0.60( 0.49)	0.83	786.6	100.00
3	166.70	22.95	0.701	0.60( 0.50)	0.83	849.7	100.00
4	138.00	28.72	0.604	0.60( 0.51)	0.86	1020.3	130.00
5	114.28	60.53	0.389	0.60( 0.55)	0.91	1905.7	20100.00
6	99.46	71.62	0.369	0.60( 0.55)	0.92	2046.7	13600.00
7	61.98	182.03	0.225	0.60( 0.56)	0.93	3300.4	13510.00
8	61.68	191.30	0.222	0.60( 0.56)	0.93	3337.5	13500.00
TOTAL AREA(ACRES) =						3337.5	

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 172.42 Tc(MIN.) = 21.104

EFFECTIVE AREA(ACRES) = 786.59 AREA-AVERAGED Fm(INCH/HR) = 0.49

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.92

TOTAL AREA(ACRES) = 3337.5

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 21.10

\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.739

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

USER-DEFINED - 1.11 0.60 1.000 -  
 USER-DEFINED - 0.44 0.60 1.000 -  
 USER-DEFINED - 1.49 0.60 1.000 -  
 USER-DEFINED - 1.70 0.60 1.000 -  
 USER-DEFINED - 1.09 0.60 1.000 -  
 USER-DEFINED - 18.57 0.60 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 24.40 SUBAREA RUNOFF (CFS) = 3.06  
 EFFECTIVE AREA (ACRES) = 810.99 AREA-AVERAGED Fm (INCH/HR) = 0.50  
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA (ACRES) = 3361.9 PEAK FLOW RATE (CFS) = 176.02

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	203.08	18.14	0.823	0.60 (0.50)	0.83	696.5	110.00
2	176.02	21.10	0.739	0.60 (0.50)	0.83	811.0	100.00
3	166.70	22.95	0.701	0.60 (0.50)	0.83	874.1	100.00
4	138.00	28.72	0.604	0.60 (0.52)	0.86	1044.7	130.00
5	114.28	60.53	0.389	0.60 (0.55)	0.91	1930.1	20100.00
6	99.46	71.62	0.369	0.60 (0.55)	0.92	2071.1	13600.00
7	61.98	182.03	0.225	0.60 (0.56)	0.93	3324.8	13510.00
8	61.68	191.30	0.222	0.60 (0.56)	0.93	3361.9	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 203.08 Tc (MIN.) = 18.14  
 AREA-AVERAGED Fm (INCH/HR) = 0.50 AREA-AVERAGED Fp (INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.83 EFFECTIVE AREA (ACRES) = 696.55

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 18.14

\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.823

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	12.39	0.60	1.000	-
USER-DEFINED	-	2.30	0.60	1.000	-
USER-DEFINED	-	5.19	0.60	1.000	-
USER-DEFINED	-	28.71	0.60	1.000	-
USER-DEFINED	-	0.17	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 48.76 SUBAREA RUNOFF (CFS) = 9.78

EFFECTIVE AREA (ACRES) = 745.31 AREA-AVERAGED Fm (INCH/HR) = 0.51

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.84

TOTAL AREA (ACRES) = 3410.7 PEAK FLOW RATE (CFS) = 212.85

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13660.00 TO NODE 13680.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 300.00 DOWNSTREAM (FEET) = 288.00

CHANNEL LENGTH THRU SUBAREA (FEET) = 933.89 CHANNEL SLOPE = 0.0128  
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.746

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.22	0.60	1.000	-
USER-DEFINED	-	9.23	0.60	1.000	-
USER-DEFINED	-	0.54	0.60	1.000	-
USER-DEFINED	-	5.66	0.60	1.000	-
USER-DEFINED	-	3.66	0.60	1.000	-
USER-DEFINED	-	0.67	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 214.17

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.88

AVERAGE FLOW DEPTH (FEET) = 3.48 TRAVEL TIME (MIN.) = 2.65

Tc (MIN.) = 20.79

SUBAREA AREA (ACRES) = 19.98 SUBAREA RUNOFF (CFS) = 2.62

EFFECTIVE AREA (ACRES) = 765.29 AREA-AVERAGED Fm (INCH/HR) = 0.51

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.85

TOTAL AREA (ACRES) = 3430.6 PEAK FLOW RATE (CFS) = 212.85

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 3.47 FLOW VELOCITY (FEET/SEC.) = 5.88

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13680.00 = 34190.53 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 20.79

\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.746

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.56	0.60	1.000	-
USER-DEFINED	-	9.40	0.60	1.000	-
USER-DEFINED	-	2.76	0.60	1.000	-
USER-DEFINED	-	17.38	0.60	1.000	-
USER-DEFINED	-	2.46	0.60	1.000	-
USER-DEFINED	-	5.56	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 39.12 SUBAREA RUNOFF (CFS) = 5.14

EFFECTIVE AREA (ACRES) = 804.41 AREA-AVERAGED Fm (INCH/HR) = 0.51

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.85

TOTAL AREA (ACRES) = 3469.8 PEAK FLOW RATE (CFS) = 212.85

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 20.79  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.746  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 0.65 0.60 1.000 -  
 USER-DEFINED - 1.70 0.60 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 2.35 SUBAREA RUNOFF(CFS) = 0.31  
 EFFECTIVE AREA(ACRES) = 806.76 AREA-AVERAGED Fm(INCH/HR) = 0.51  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.85  
 TOTAL AREA(ACRES) = 3472.1 PEAK FLOW RATE(CFS) = 212.85  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13660.00 TO NODE 13680.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 3 <<<<<<  
 =====

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<  
 =====

MAINLINE Tc(MIN.) = 20.79  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.746  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 5.29 0.60 1.000 -  
 USER-DEFINED - 31.25 0.60 1.000 -  
 USER-DEFINED - 0.22 0.60 1.000 -  
 USER-DEFINED - 6.26 0.60 1.000 -  
 USER-DEFINED - 0.07 0.60 1.000 -  
 USER-DEFINED - 0.22 0.60 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 43.31 SUBAREA RUNOFF(CFS) = 5.69  
 EFFECTIVE AREA(ACRES) = 850.07 AREA-AVERAGED Fm(INCH/HR) = 0.52  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.86  
 TOTAL AREA(ACRES) = 3515.4 PEAK FLOW RATE(CFS) = 212.85  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<  
 =====

MAINLINE Tc(MIN.) = 20.79  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.746  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 2.47 0.60 0.850 -  
 USER-DEFINED - 3.06 0.60 0.850 -  
 USER-DEFINED - 17.76 0.60 0.500 -

USER-DEFINED - 7.31 0.60 0.500 -  
 USER-DEFINED - 0.34 0.60 1.000 -  
 USER-DEFINED - 8.22 0.60 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.659  
 SUBAREA AREA(ACRES) = 39.16 SUBAREA RUNOFF(CFS) = 12.36  
 EFFECTIVE AREA(ACRES) = 889.23 AREA-AVERAGED Fm(INCH/HR) = 0.51  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.85  
 TOTAL AREA(ACRES) = 3554.6 PEAK FLOW RATE(CFS) = 212.85  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<  
 =====

MAINLINE Tc(MIN.) = 20.79  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.746  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 0.53 0.60 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 0.53 SUBAREA RUNOFF(CFS) = 0.07  
 EFFECTIVE AREA(ACRES) = 889.76 AREA-AVERAGED Fm(INCH/HR) = 0.51  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.85  
 TOTAL AREA(ACRES) = 3555.1 PEAK FLOW RATE(CFS) = 212.85  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13680.00 TO NODE 13682.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<  
 -----

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 288.00 DOWNSTREAM(FEET) = 242.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2860.77 CHANNEL SLOPE = 0.0161  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.611  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 0.22 0.60 1.000 -  
 USER-DEFINED - 5.28 0.60 1.000 -  
 USER-DEFINED - 0.52 0.60 1.000 -  
 USER-DEFINED - 3.61 0.60 1.000 -  
 USER-DEFINED - 0.67 0.60 1.000 -  
 USER-DEFINED - 1.37 0.60 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 212.91  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.40  
 AVERAGE FLOW DEPTH(FEET) = 3.33 TRAVEL TIME(MIN.) = 7.46  
 Tc(MIN.) = 28.24  
 SUBAREA AREA(ACRES) = 11.67 SUBAREA RUNOFF(CFS) = 0.12  
 EFFECTIVE AREA(ACRES) = 901.43 AREA-AVERAGED Fm(INCH/HR) = 0.51

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.85  
TOTAL AREA (ACRES) = 3566.8 PEAK FLOW RATE (CFS) = 212.85  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 3.33 FLOW VELOCITY (FEET/SEC.) = 6.39  
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13682.00 = 37051.30 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 28.24  
\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.611  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	6.90	0.60	1.000	-
USER-DEFINED	-	23.04	0.60	1.000	-
USER-DEFINED	-	1.18	0.60	1.000	-
USER-DEFINED	-	1.56	0.60	1.000	-
USER-DEFINED	-	53.20	0.60	1.000	-
USER-DEFINED	-	2.08	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 87.96 SUBAREA RUNOFF (CFS) = 0.88  
EFFECTIVE AREA (ACRES) = 989.39 AREA-AVERAGED Fm (INCH/HR) = 0.52  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.87  
TOTAL AREA (ACRES) = 3654.7 PEAK FLOW RATE (CFS) = 212.85  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 28.24  
\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.611  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.01	0.60	1.000	-
USER-DEFINED	-	0.18	0.60	1.000	-
USER-DEFINED	-	0.38	0.60	1.000	-
USER-DEFINED	-	0.22	0.60	1.000	-
USER-DEFINED	-	7.73	0.60	1.000	-
USER-DEFINED	-	4.37	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 12.89 SUBAREA RUNOFF (CFS) = 0.13  
EFFECTIVE AREA (ACRES) = 1002.28 AREA-AVERAGED Fm (INCH/HR) = 0.52  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.87  
TOTAL AREA (ACRES) = 3667.6 PEAK FLOW RATE (CFS) = 212.85  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 28.24  
\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.611  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	2.57	0.60	1.000	-
USER-DEFINED	-	1.97	0.60	1.000	-
USER-DEFINED	-	1.00	0.60	1.000	-
USER-DEFINED	-	2.98	0.60	1.000	-
USER-DEFINED	-	2.39	0.60	1.000	-
USER-DEFINED	-	1.67	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 12.58 SUBAREA RUNOFF (CFS) = 0.13  
EFFECTIVE AREA (ACRES) = 1014.86 AREA-AVERAGED Fm (INCH/HR) = 0.52  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.87  
TOTAL AREA (ACRES) = 3680.2 PEAK FLOW RATE (CFS) = 212.85  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 28.24  
\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.611  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.44	0.60	1.000	-
USER-DEFINED	-	2.65	0.60	0.850	-
USER-DEFINED	-	1.16	0.60	0.850	-
USER-DEFINED	-	0.47	0.60	0.500	-
USER-DEFINED	-	0.25	0.60	0.500	-
USER-DEFINED	-	20.24	0.60	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.963  
SUBAREA AREA (ACRES) = 25.21 SUBAREA RUNOFF (CFS) = 0.76  
EFFECTIVE AREA (ACRES) = 1040.07 AREA-AVERAGED Fm (INCH/HR) = 0.52  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.87  
TOTAL AREA (ACRES) = 3705.4 PEAK FLOW RATE (CFS) = 212.85  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 28.24  
\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.611  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.08	0.60	1.000	-
USER-DEFINED	-	6.75	0.60	1.000	-

USER-DEFINED - 0.02 0.60 1.000 -  
 USER-DEFINED - 0.93 0.60 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 14.78 SUBAREA RUNOFF (CFS) = 0.15  
 EFFECTIVE AREA (ACRES) = 1054.85 AREA-AVERAGED Fm (INCH/HR) = 0.52  
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.88  
 TOTAL AREA (ACRES) = 3720.2 PEAK FLOW RATE (CFS) = 212.85  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13682.00 TO NODE 13683.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 242.00 DOWNSTREAM (FEET) = 208.53  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 2526.22 CHANNEL SLOPE = 0.0132  
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00

\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.542

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.49	0.60	1.000	-
USER-DEFINED	-	13.31	0.60	1.000	-
USER-DEFINED	-	0.87	0.60	1.000	-
USER-DEFINED	-	20.26	0.60	1.000	-
USER-DEFINED	-	1.21	0.60	1.000	-
USER-DEFINED	-	0.05	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 212.85

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.95

AVERAGE FLOW DEPTH (FEET) = 3.45 TRAVEL TIME (MIN.) = 7.08

Tc (MIN.) = 35.32

SUBAREA AREA (ACRES) = 44.19 SUBAREA RUNOFF (CFS) = 0.00

EFFECTIVE AREA (ACRES) = 1099.04 AREA-AVERAGED Fm (INCH/HR) = 0.53

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.88

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA (ACRES) = 3764.4 PEAK FLOW RATE (CFS) = 212.85

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 3.45 FLOW VELOCITY (FEET/SEC.) = 5.95

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13683.00 = 39577.52 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 35.32

\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.542

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	12.56	0.60	1.000	-
USER-DEFINED	-	0.81	0.60	1.000	-
USER-DEFINED	-	0.01	0.60	1.000	-
USER-DEFINED	-	1.11	0.60	1.000	-
USER-DEFINED	-	0.59	0.60	1.000	-
USER-DEFINED	-	3.04	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA (ACRES) = 18.12 SUBAREA RUNOFF (CFS) = 0.00

EFFECTIVE AREA (ACRES) = 1117.16 AREA-AVERAGED Fm (INCH/HR) = 0.53

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.88

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA (ACRES) = 3782.5 PEAK FLOW RATE (CFS) = 212.85

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 35.32

\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.542

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.10	0.60	0.400	-
USER-DEFINED	-	1.30	0.60	0.850	-
USER-DEFINED	-	0.10	0.60	0.400	-
USER-DEFINED	-	1.70	0.60	0.850	-
USER-DEFINED	-	0.10	0.60	0.850	-
USER-DEFINED	-	2.90	0.60	0.850	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.835

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA (ACRES) = 6.20 SUBAREA RUNOFF (CFS) = 0.50

EFFECTIVE AREA (ACRES) = 1123.36 AREA-AVERAGED Fm (INCH/HR) = 0.53

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.88

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA (ACRES) = 3788.7 PEAK FLOW RATE (CFS) = 212.85

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 35.32

\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.542

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------



```

USER-DEFINED      -      0.10      0.60      0.500      -
USER-DEFINED      -      0.10      0.60      0.350      -
USER-DEFINED      -      6.90      0.60      0.850      -
USER-DEFINED      -      0.40      0.60      0.850      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.839
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 7.50      SUBAREA RUNOFF(CFS) = 0.59
EFFECTIVE AREA(ACRES) = 1130.86      AREA-AVERAGED Fm(INCH/HR) = 0.53
AREA-AVERAGED Fp(INCH/HR) = 0.60      AREA-AVERAGED Ap = 0.88
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 3796.2      PEAK FLOW RATE(CFS) = 212.85
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13682.00 TO NODE 13683.00 IS CODE = 12
-----

```

```

>>>>CLEAR MEMORY BANK # 3 <<<<<
=====

```

```

***MEMORY BANK # 3 IS EMPTY - PROCESS IGNORED.***

```

```

*****
FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====

```

```

MAINLINE Tc(MIN.) = 35.32
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.542
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL      AREA      Fp      Ap      SCS
LAND USE      GROUP      (ACRES)      (INCH/HR)      (DECIMAL)      CN
USER-DEFINED      -      2.55      0.60      1.000      -
USER-DEFINED      -      0.01      0.60      1.000      -
USER-DEFINED      -      1.35      0.60      1.000      -
USER-DEFINED      -      0.44      0.60      1.000      -
USER-DEFINED      -      0.67      0.60      1.000      -
USER-DEFINED      -      1.06      0.60      1.000      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 6.08      SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 1136.94      AREA-AVERAGED Fm(INCH/HR) = 0.53
AREA-AVERAGED Fp(INCH/HR) = 0.60      AREA-AVERAGED Ap = 0.88
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 3802.3      PEAK FLOW RATE(CFS) = 212.85
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====

```

```

MAINLINE Tc(MIN.) = 35.32
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.542

```

```

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL      AREA      Fp      Ap      SCS
LAND USE      GROUP      (ACRES)      (INCH/HR)      (DECIMAL)      CN
USER-DEFINED      -      2.16      0.60      1.000      -
USER-DEFINED      -      2.45      0.60      1.000      -
USER-DEFINED      -      6.15      0.60      1.000      -
USER-DEFINED      -      1.34      0.60      1.000      -
USER-DEFINED      -      18.46      0.60      1.000      -
USER-DEFINED      -      4.13      0.60      1.000      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 34.69      SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 1171.63      AREA-AVERAGED Fm(INCH/HR) = 0.53
AREA-AVERAGED Fp(INCH/HR) = 0.60      AREA-AVERAGED Ap = 0.89
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 3837.0      PEAK FLOW RATE(CFS) = 212.85
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====

```

```

MAINLINE Tc(MIN.) = 35.32
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.542
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL      AREA      Fp      Ap      SCS
LAND USE      GROUP      (ACRES)      (INCH/HR)      (DECIMAL)      CN
USER-DEFINED      -      8.69      0.60      1.000      -
USER-DEFINED      -      0.73      0.60      1.000      -
USER-DEFINED      -      0.41      0.60      1.000      -
USER-DEFINED      -      1.37      0.60      1.000      -
USER-DEFINED      -      3.11      0.60      1.000      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
SUBAREA AREA(ACRES) = 14.31      SUBAREA RUNOFF(CFS) = 0.00
EFFECTIVE AREA(ACRES) = 1185.94      AREA-AVERAGED Fm(INCH/HR) = 0.53
AREA-AVERAGED Fp(INCH/HR) = 0.60      AREA-AVERAGED Ap = 0.89
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;
* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.
TOTAL AREA(ACRES) = 3851.3      PEAK FLOW RATE(CFS) = 212.85
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13683.00 TO NODE 13685.00 IS CODE = 51
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<
=====

```

```

ELEVATION DATA: UPSTREAM(FEET) = 208.53      DOWNSTREAM(FEET) = 194.24
CHANNEL LENGTH THRU SUBAREA(FEET) = 289.01      CHANNEL SLOPE = 0.0494
CHANNEL BASE(FEET) = 0.00      "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040      MAXIMUM DEPTH(FEET) = 20.00

```

CHANNEL FLOW THRU SUBAREA(CFS) = 212.85  
 FLOW VELOCITY(FEET/SEC.) = 9.75 FLOW DEPTH(FEET) = 2.70  
 TRAVEL TIME(MIN.) = 0.49 Tc(MIN.) = 35.81  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13685.00 = 39866.53 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13685.00 TO NODE 13410.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 194.24 DOWNSTREAM(FEET) = 178.72  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1843.57 CHANNEL SLOPE = 0.0084  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.493

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.23	0.60	1.000	-
USER-DEFINED	-	1.52	0.60	1.000	-
USER-DEFINED	-	0.06	0.60	1.000	-
USER-DEFINED	-	0.13	0.60	1.000	-
USER-DEFINED	-	6.45	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 212.85  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.01  
 AVERAGE FLOW DEPTH(FEET) = 3.76 TRAVEL TIME(MIN.) = 6.14  
 Tc(MIN.) = 41.95  
 SUBAREA AREA(ACRES) = 8.39 SUBAREA RUNOFF(CFS) = 0.00  
 EFFECTIVE AREA(ACRES) = 1194.33 AREA-AVERAGED Fm(INCH/HR) = 0.53  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.89  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 3859.7 PEAK FLOW RATE(CFS) = 212.85  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 3.76 FLOW VELOCITY(FEET/SEC.) = 5.01  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13410.00 = 41710.10 FEET.

=====

END OF STUDY SUMMARY:  
 TOTAL AREA(ACRES) = 3859.7 TC(MIN.) = 41.95  
 EFFECTIVE AREA(ACRES) = 1194.33 AREA-AVERAGED Fm(INCH/HR) = 0.53  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.888  
 PEAK FLOW RATE(CFS) = 212.85

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	212.85	41.95	0.493	0.60( 0.53)	0.89	1194.3	110.00
2	182.13	45.87	0.471	0.60( 0.53)	0.88	1308.8	100.00
3	166.70	48.25	0.457	0.60( 0.53)	0.88	1371.9	100.00
4	138.00	55.27	0.417	0.60( 0.54)	0.89	1542.5	130.00
5	114.28	88.34	0.339	0.60( 0.56)	0.93	2427.8	20100.00

6	99.46	100.42	0.317	0.60( 0.56)	0.93	2568.9	13600.00
7	61.98	214.44	0.215	0.60( 0.56)	0.93	3822.6	13510.00
8	61.68	223.75	0.212	0.60( 0.56)	0.93	3859.7	13500.00

=====

END OF RATIONAL METHOD ANALYSIS



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA 92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S37- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 2-YR RM EV APRIL 2019 ROKAMOTO \*  
\*\*\*\*\*

FILE NAME: RI02EV37.DAT  
TIME/DATE OF STUDY: 17:08 04/08/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 2.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 1.802
- 2) 10.00; 1.202
- 3) 15.00; 0.923
- 4) 20.00; 0.761
- 5) 25.00; 0.659
- 6) 30.00; 0.585
- 7) 40.00; 0.503
- 8) 50.00; 0.446
- 9) 60.00; 0.390
- 10) 90.00; 0.336
- 11) 120.00; 0.280
- 12) 180.00; 0.226
- 13) 360.00; 0.170
- 14) 1200.00; 0.080

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI02EV34.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2279.20	21.50	0.60 ( 0.46)	0.77	2948.7	300.00
2	2197.63	39.15	0.60 ( 0.46)	0.77	6173.8	50500.00
3	1874.99	61.40	0.60 ( 0.48)	0.79	10819.4	150.00
4	1609.49	82.47	0.60 ( 0.50)	0.83	15020.5	10100.00
5	1536.21	101.02	0.60 ( 0.51)	0.84	19078.0	13600.00
6	1481.61	131.41	0.60 ( 0.52)	0.87	24943.4	11831.00
7	1519.90	154.99	0.60 ( 0.53)	0.89	29496.4	11530.00
8	1553.96	174.54	0.60 ( 0.54)	0.90	33867.4	11000.00
9	1613.28	196.84	0.60 ( 0.55)	0.92	40919.0	10850.00
10	1514.10	212.68	0.60 ( 0.55)	0.92	44412.9	11220.00
11	1445.63	224.25	0.60 ( 0.56)	0.93	46227.6	10910.00
12	1259.63	265.28	0.60 ( 0.56)	0.93	52809.6	12410.00
13	1194.48	298.48	0.60 ( 0.56)	0.94	58895.5	12261.00
14	1171.76	311.34	0.60 ( 0.56)	0.94	60382.1	10410.00
15	1149.61	323.61	0.60 ( 0.56)	0.94	61484.1	12101.10
16	1099.57	351.32	0.60 ( 0.57)	0.94	63862.1	10200.00
17	1074.90	364.81	0.60 ( 0.57)	0.94	64800.4	12010.00
18	1020.23	394.19	0.60 ( 0.57)	0.94	65474.1	10210.00
19	947.45	443.75	0.60 ( 0.57)	0.94	65973.2	12000.00
20	889.61	513.65	0.60 ( 0.57)	0.95	66557.9	10100.00
TOTAL AREA (ACRES) =						66557.9

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 3 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2279.20	21.50	0.60 ( 0.46)	0.77	2948.7	300.00
2	2197.63	39.15	0.60 ( 0.46)	0.77	6173.8	50500.00
3	1874.99	61.40	0.60 ( 0.48)	0.79	10819.4	150.00
4	1609.49	82.47	0.60 ( 0.50)	0.83	15020.5	10100.00
5	1536.21	101.02	0.60 ( 0.51)	0.84	19078.0	13600.00
6	1481.61	131.41	0.60 ( 0.52)	0.87	24943.4	11831.00
7	1519.90	154.99	0.60 ( 0.53)	0.89	29496.4	11530.00
8	1553.96	174.54	0.60 ( 0.54)	0.90	33867.4	11000.00
9	1613.28	196.84	0.60 ( 0.55)	0.92	40919.0	10850.00
10	1514.10	212.68	0.60 ( 0.55)	0.92	44412.9	11220.00
11	1445.63	224.25	0.60 ( 0.56)	0.93	46227.6	10910.00
12	1259.63	265.28	0.60 ( 0.56)	0.93	52809.6	12410.00
13	1194.48	298.48	0.60 ( 0.56)	0.94	58895.5	12261.00

14	1171.76	311.34	0.60	( 0.56)	0.94	60382.1	10410.00
15	1149.61	323.61	0.60	( 0.56)	0.94	61484.1	12101.10
16	1099.57	351.32	0.60	( 0.57)	0.94	63862.1	10200.00
17	1074.90	364.81	0.60	( 0.57)	0.94	64800.4	12010.00
18	1020.23	394.19	0.60	( 0.57)	0.94	65474.1	10210.00
19	947.45	443.75	0.60	( 0.57)	0.94	65973.2	12000.00
20	889.61	513.65	0.60	( 0.57)	0.95	66557.9	10100.00

TOTAL AREA (ACRES) = 66557.9

\*\*\*\*\*

FLOW PROCESS FROM NODE 13700.00 TO NODE 13720.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 170.00 DOWNSTREAM(FEET) = 165.51  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1891.83 CHANNEL SLOPE = 0.0024  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
 CHANNEL FLOW THRU SUBAREA(CFS) = 2279.20  
 FLOW VELOCITY(FEET/SEC.) = 7.00 FLOW DEPTH(FEET) = 10.42  
 TRAVEL TIME(MIN.) = 4.50 Tc(MIN.) = 26.00  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126446.80 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2279.20	26.00	0.644	0.60 ( 0.46)	0.77	2948.7	300.00
2	2197.63	43.69	0.482	0.60 ( 0.46)	0.77	6173.8	50500.00
3	1874.99	66.13	0.379	0.60 ( 0.48)	0.79	10819.4	150.00
4	1609.49	87.38	0.341	0.60 ( 0.50)	0.83	15020.5	10100.00
5	1536.21	105.99	0.306	0.60 ( 0.51)	0.84	19078.0	13600.00
6	1481.61	136.43	0.265	0.60 ( 0.52)	0.87	24943.4	11831.00
7	1519.90	159.97	0.244	0.60 ( 0.53)	0.89	29496.4	11530.00
8	1553.96	179.50	0.226	0.60 ( 0.54)	0.90	33867.4	11000.00
9	1613.28	201.75	0.219	0.60 ( 0.55)	0.92	40919.0	10850.00
10	1514.10	217.67	0.214	0.60 ( 0.55)	0.92	44412.9	11220.00
11	1445.63	229.30	0.211	0.60 ( 0.56)	0.93	46227.6	10910.00
12	1259.63	270.51	0.198	0.60 ( 0.56)	0.93	52809.6	12410.00
13	1194.48	303.78	0.187	0.60 ( 0.56)	0.94	58895.5	12261.00
14	1171.76	316.66	0.183	0.60 ( 0.56)	0.94	60382.1	10410.00
15	1149.61	328.95	0.180	0.60 ( 0.56)	0.94	61484.1	12101.10
16	1099.57	356.72	0.171	0.60 ( 0.57)	0.94	63862.1	10200.00
17	1074.90	370.25	0.169	0.60 ( 0.57)	0.94	64800.4	12010.00
18	1020.23	399.70	0.166	0.60 ( 0.57)	0.94	65474.1	10210.00
19	947.45	449.36	0.160	0.60 ( 0.57)	0.94	65973.2	12000.00
20	889.61	519.35	0.153	0.60 ( 0.57)	0.95	66557.9	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2279.20 Tc(MIN.) = 26.00  
 AREA-AVERAGED Fm(INCH/HR) = 0.46 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.77 EFFECTIVE AREA(ACRES) = 2948.71

\*\*\*\*\*

FLOW PROCESS FROM NODE 13700.00 TO NODE 13720.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13720.00 TO NODE 13720.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506102G.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23.78	20.85	0.60 ( 0.58)	0.96	198.9	10230.00
2	18.42	27.77	0.60 ( 0.57)	0.96	227.7	10250.00
3	15.17	31.87	0.60 ( 0.57)	0.95	240.4	10200.00
4	8.86	39.09	0.60 ( 0.57)	0.95	246.3	10220.00

TOTAL AREA(ACRES) = 246.3

\*\*\*\*\*

FLOW PROCESS FROM NODE 13720.00 TO NODE 13720.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2279.20	26.00	0.644	0.60 ( 0.46)	0.77	2948.7	300.00
2	2197.63	43.69	0.482	0.60 ( 0.46)	0.77	6173.8	50500.00
3	1874.99	66.13	0.379	0.60 ( 0.48)	0.79	10819.4	150.00
4	1609.49	87.38	0.341	0.60 ( 0.50)	0.83	15020.5	10100.00
5	1536.21	105.99	0.306	0.60 ( 0.51)	0.84	19078.0	13600.00
6	1481.61	136.43	0.265	0.60 ( 0.52)	0.87	24943.4	11831.00
7	1519.90	159.97	0.244	0.60 ( 0.53)	0.89	29496.4	11530.00
8	1553.96	179.50	0.226	0.60 ( 0.54)	0.90	33867.4	11000.00
9	1613.28	201.75	0.219	0.60 ( 0.55)	0.92	40919.0	10850.00
10	1514.10	217.67	0.214	0.60 ( 0.55)	0.92	44412.9	11220.00
11	1445.63	229.30	0.211	0.60 ( 0.56)	0.93	46227.6	10910.00
12	1259.63	270.51	0.198	0.60 ( 0.56)	0.93	52809.6	12410.00
13	1194.48	303.78	0.187	0.60 ( 0.56)	0.94	58895.5	12261.00
14	1171.76	316.66	0.183	0.60 ( 0.56)	0.94	60382.1	10410.00
15	1149.61	328.95	0.180	0.60 ( 0.56)	0.94	61484.1	12101.10
16	1099.57	356.72	0.171	0.60 ( 0.57)	0.94	63862.1	10200.00
17	1074.90	370.25	0.169	0.60 ( 0.57)	0.94	64800.4	12010.00
18	1020.23	399.70	0.166	0.60 ( 0.57)	0.94	65474.1	10210.00
19	947.45	449.36	0.160	0.60 ( 0.57)	0.94	65973.2	12000.00
20	889.61	519.35	0.153	0.60 ( 0.57)	0.95	66557.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126446.80 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23.78	20.85	0.744	0.60 ( 0.58)	0.96	198.9	10230.00
2	18.42	27.77	0.618	0.60 ( 0.57)	0.96	227.7	10250.00
3	15.17	31.87	0.570	0.60 ( 0.57)	0.95	240.4	10200.00
4	8.86	39.09	0.510	0.60 ( 0.57)	0.95	246.3	10220.00

LONGEST FLOWPATH FROM NODE 10200.00 TO NODE 13720.00 = 9099.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
---------------	---------	-----------	---------------------	------------------	----	------------	----------------

1	2302.98	20.85	0.744	0.60	(0.47)	0.79	2563.1	10230.00
2	2298.99	26.00	0.644	0.60	(0.47)	0.79	3169.0	300.00
3	2289.46	27.77	0.618	0.60	(0.47)	0.79	3499.0	10250.00
4	2267.30	31.87	0.570	0.60	(0.47)	0.78	4259.2	10200.00
5	2227.71	39.09	0.510	0.60	(0.47)	0.78	5581.1	10220.00
6	2206.00	43.69	0.482	0.60	(0.47)	0.78	6420.1	50500.00
7	1881.57	66.13	0.379	0.60	(0.48)	0.80	11065.7	150.00
8	1615.40	87.38	0.341	0.60	(0.50)	0.83	15266.8	10100.00
9	1541.52	105.99	0.306	0.60	(0.51)	0.85	19324.3	13600.00
10	1486.21	136.43	0.265	0.60	(0.52)	0.87	25189.7	11831.00
11	1524.13	159.97	0.244	0.60	(0.53)	0.89	29742.7	11530.00
12	1557.89	179.50	0.226	0.60	(0.54)	0.90	34113.6	11000.00
13	1617.09	201.75	0.219	0.60	(0.55)	0.92	41165.2	10850.00
14	1517.81	217.67	0.214	0.60	(0.55)	0.92	44659.2	11220.00
15	1449.29	229.30	0.211	0.60	(0.56)	0.93	46473.8	10910.00
16	1263.06	270.51	0.198	0.60	(0.56)	0.93	53055.9	12410.00
17	1197.73	303.78	0.187	0.60	(0.56)	0.94	59141.8	12261.00
18	1174.95	316.66	0.183	0.60	(0.56)	0.94	60628.4	10410.00
19	1152.73	328.95	0.180	0.60	(0.56)	0.94	61730.3	12101.10
20	1102.54	356.72	0.171	0.60	(0.57)	0.94	64108.4	10200.00
21	1077.83	370.25	0.169	0.60	(0.57)	0.94	65046.6	12010.00
22	1023.10	399.70	0.166	0.60	(0.57)	0.94	65720.4	10210.00
23	950.23	449.36	0.160	0.60	(0.57)	0.94	66219.4	12000.00
24	892.26	519.35	0.153	0.60	(0.57)	0.95	66804.2	10100.00

TOTAL AREA (ACRES) = 66804.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 2302.98 Tc (MIN.) = 20.846  
EFFECTIVE AREA (ACRES) = 2563.10 AREA-AVERAGED Fm (INCH/HR) = 0.47  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.94  
TOTAL AREA (ACRES) = 66804.2  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126446.80 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13720.00 TO NODE 13740.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 165.51 DOWNSTREAM (FEET) = 161.03  
CHANNEL LENGTH THRU SUBAREA (FEET) = 2067.54 CHANNEL SLOPE = 0.0022  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA (CFS) = 2302.98  
FLOW VELOCITY (FEET/SEC.) = 6.78 FLOW DEPTH (FEET) = 10.64  
TRAVEL TIME (MIN.) = 5.08 Tc (MIN.) = 25.93  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128514.34 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2302.98	25.93	0.645	0.60 (0.47)	0.79	2563.1	10230.00
2	2298.99	31.08	0.576	0.60 (0.47)	0.79	3169.0	300.00
3	2289.46	32.86	0.562	0.60 (0.47)	0.79	3499.0	10250.00
4	2267.30	36.97	0.528	0.60 (0.47)	0.78	4259.2	10200.00
5	2227.71	44.22	0.479	0.60 (0.47)	0.78	5581.1	10220.00
6	2206.00	48.83	0.453	0.60 (0.47)	0.78	6420.1	50500.00
7	1881.57	71.48	0.369	0.60 (0.48)	0.80	11065.7	150.00

8	1615.40	92.93	0.331	0.60	(0.50)	0.83	15266.8	10100.00
9	1541.52	111.60	0.296	0.60	(0.51)	0.85	19324.3	13600.00
10	1486.21	142.10	0.260	0.60	(0.52)	0.87	25189.7	11831.00
11	1524.13	165.60	0.239	0.60	(0.53)	0.89	29742.7	11530.00
12	1557.89	185.10	0.224	0.60	(0.54)	0.90	34113.6	11000.00
13	1617.09	207.30	0.218	0.60	(0.55)	0.92	41165.2	10850.00
14	1517.81	223.31	0.213	0.60	(0.55)	0.92	44659.2	11220.00
15	1449.29	235.01	0.209	0.60	(0.56)	0.93	46473.8	10910.00
16	1263.06	276.41	0.196	0.60	(0.56)	0.93	53055.9	12410.00
17	1197.73	309.76	0.186	0.60	(0.56)	0.94	59141.8	12261.00
18	1174.95	322.67	0.182	0.60	(0.56)	0.94	60628.4	10410.00
19	1152.73	334.99	0.178	0.60	(0.56)	0.94	61730.3	12101.10
20	1102.54	362.82	0.170	0.60	(0.57)	0.94	64108.4	10200.00
21	1077.83	376.38	0.168	0.60	(0.57)	0.94	65046.6	12010.00
22	1023.10	405.93	0.165	0.60	(0.57)	0.94	65720.4	10210.00
23	950.23	455.70	0.160	0.60	(0.57)	0.94	66219.4	12000.00
24	892.26	525.79	0.152	0.60	(0.57)	0.95	66804.2	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 2302.98 Tc (MIN.) = 25.93  
AREA-AVERAGED Fm (INCH/HR) = 0.47 AREA-AVERAGED Fp (INCH/HR) = 0.60  
AREA-AVERAGED Ap = 0.79 EFFECTIVE AREA (ACRES) = 2563.10

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13720.00 TO NODE 13740.00 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13740.00 TO NODE 13740.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506103G.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	100.02	24.05	0.60 (0.45)	0.75	396.7	10380.00
2	99.68	24.58	0.60 (0.45)	0.75	403.1	10300.00
3	86.78	29.19	0.60 (0.45)	0.76	440.4	10320.00
4	81.58	32.88	0.60 (0.46)	0.76	455.7	10340.00
5	76.28	36.17	0.60 (0.46)	0.76	460.8	10360.00
TOTAL AREA (ACRES) =						460.8

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13740.00 TO NODE 13740.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2302.98	25.93	0.645	0.60 (0.47)	0.79	2563.1	10230.00
2	2298.99	31.08	0.576	0.60 (0.47)	0.79	3169.0	300.00
3	2289.46	32.86	0.562	0.60 (0.47)	0.79	3499.0	10250.00
4	2267.30	36.97	0.528	0.60 (0.47)	0.78	4259.2	10200.00
5	2227.71	44.22	0.479	0.60 (0.47)	0.78	5581.1	10220.00

6	2206.00	48.83	0.453	0.60 ( 0.47)	0.78	6420.1	50500.00
7	1881.57	71.48	0.369	0.60 ( 0.48)	0.80	11065.7	150.00
8	1615.40	92.93	0.331	0.60 ( 0.50)	0.83	15266.8	10100.00
9	1541.52	111.60	0.296	0.60 ( 0.51)	0.85	19324.3	13600.00
10	1486.21	142.10	0.260	0.60 ( 0.52)	0.87	25189.7	11831.00
11	1524.13	165.60	0.239	0.60 ( 0.53)	0.89	29742.7	11530.00
12	1557.89	185.10	0.224	0.60 ( 0.54)	0.90	34113.6	11000.00
13	1617.09	207.30	0.218	0.60 ( 0.55)	0.92	41165.2	10850.00
14	1517.81	223.31	0.213	0.60 ( 0.55)	0.92	44659.2	11220.00
15	1449.29	235.01	0.209	0.60 ( 0.56)	0.93	46473.8	10910.00
16	1263.06	276.41	0.196	0.60 ( 0.56)	0.93	53055.9	12410.00
17	1197.73	309.76	0.186	0.60 ( 0.56)	0.94	59141.8	12261.00
18	1174.95	322.67	0.182	0.60 ( 0.56)	0.94	60628.4	10410.00
19	1152.73	334.99	0.178	0.60 ( 0.56)	0.94	61730.3	12101.10
20	1102.54	362.82	0.170	0.60 ( 0.57)	0.94	64108.4	10200.00
21	1077.83	376.38	0.168	0.60 ( 0.57)	0.94	65046.6	12010.00
22	1023.10	405.93	0.165	0.60 ( 0.57)	0.94	65720.4	10210.00
23	950.23	455.70	0.160	0.60 ( 0.57)	0.94	66219.4	12000.00
24	892.26	525.79	0.152	0.60 ( 0.57)	0.95	66804.2	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128514.34 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	100.02	24.05	0.678	0.60 ( 0.45)	0.75	396.7	10380.00
2	99.68	24.58	0.668	0.60 ( 0.45)	0.75	403.1	10300.00
3	86.78	29.19	0.597	0.60 ( 0.45)	0.76	440.4	10320.00
4	81.58	32.88	0.561	0.60 ( 0.46)	0.76	455.7	10340.00
5	76.28	36.17	0.534	0.60 ( 0.46)	0.76	460.8	10360.00

LONGEST FLOWPATH FROM NODE 10320.00 TO NODE 13740.00 = 8457.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2403.00	24.05	0.678	0.60 ( 0.47)	0.78	2774.2	10380.00
2	2402.66	24.58	0.668	0.60 ( 0.47)	0.78	2833.0	10300.00
3	2398.89	25.93	0.645	0.60 ( 0.47)	0.78	2977.1	10230.00
4	2387.23	29.19	0.597	0.60 ( 0.47)	0.78	3387.7	10320.00
5	2383.11	31.08	0.576	0.60 ( 0.47)	0.78	3617.3	300.00
6	2371.08	32.86	0.562	0.60 ( 0.47)	0.78	3954.5	10250.00
7	2370.90	32.88	0.561	0.60 ( 0.47)	0.78	3959.3	10340.00
8	2347.87	36.17	0.534	0.60 ( 0.47)	0.78	4572.7	10360.00
9	2342.65	36.97	0.528	0.60 ( 0.47)	0.78	4720.0	10200.00
10	2296.08	44.22	0.479	0.60 ( 0.47)	0.78	6041.9	10220.00
11	2270.61	48.83	0.453	0.60 ( 0.47)	0.78	6880.9	50500.00
12	1934.29	71.48	0.369	0.60 ( 0.48)	0.80	11526.5	150.00
13	1662.58	92.93	0.331	0.60 ( 0.50)	0.83	15727.5	10100.00
14	1583.73	111.60	0.296	0.60 ( 0.51)	0.84	19785.1	13600.00
15	1523.34	142.10	0.260	0.60 ( 0.52)	0.87	25650.5	11831.00
16	1558.24	165.60	0.239	0.60 ( 0.53)	0.89	30203.5	11530.00
17	1589.92	185.10	0.224	0.60 ( 0.54)	0.90	34574.4	11000.00
18	1648.14	207.30	0.218	0.60 ( 0.55)	0.92	41626.0	10850.00
19	1548.15	223.31	0.213	0.60 ( 0.55)	0.92	45120.0	11220.00
20	1479.10	235.01	0.209	0.60 ( 0.55)	0.92	46934.6	10910.00
21	1291.04	276.41	0.196	0.60 ( 0.56)	0.93	53516.7	12410.00
22	1224.23	309.76	0.186	0.60 ( 0.56)	0.94	59602.6	12261.00
23	1200.87	322.67	0.182	0.60 ( 0.56)	0.94	61089.2	10410.00
24	1178.11	334.99	0.178	0.60 ( 0.56)	0.94	62191.1	12101.10

25	1126.76	362.82	0.170	0.60 ( 0.56)	0.94	64569.2	10200.00
26	1101.84	376.38	0.168	0.60 ( 0.57)	0.94	65507.4	12010.00
27	1046.67	405.93	0.165	0.60 ( 0.57)	0.94	66181.2	10210.00
28	973.04	455.70	0.160	0.60 ( 0.57)	0.94	66680.2	12000.00
29	913.99	525.79	0.152	0.60 ( 0.57)	0.94	67265.0	10100.00

TOTAL AREA (ACRES) = 67265.0

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 2403.00 Tc(MIN.) = 24.048  
EFFECTIVE AREA(ACRES) = 2774.16 AREA-AVERAGED Fm(INCH/HR) = 0.47  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.94  
TOTAL AREA(ACRES) = 67265.0  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128514.34 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13740.00 TO NODE 13741.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 161.03 DOWNSTREAM(FEET) = 141.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 364.08 CHANNEL SLOPE = 0.0550  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA(CFS) = 2403.00  
FLOW VELOCITY(FEET/SEC.) = 23.05 FLOW DEPTH(FEET) = 5.89  
TRAVEL TIME(MIN.) = 0.26 Tc(MIN.) = 24.31  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128878.41 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2403.00	24.31	0.673	0.60 ( 0.47)	0.78	2774.2	10380.00
2	2402.66	24.84	0.662	0.60 ( 0.47)	0.78	2833.0	10300.00
3	2398.89	26.19	0.641	0.60 ( 0.47)	0.78	2977.1	10230.00
4	2387.23	29.46	0.593	0.60 ( 0.47)	0.78	3387.7	10320.00
5	2383.11	31.34	0.574	0.60 ( 0.47)	0.78	3617.3	300.00
6	2371.08	33.12	0.559	0.60 ( 0.47)	0.78	3954.5	10250.00
7	2370.90	33.15	0.559	0.60 ( 0.47)	0.78	3959.3	10340.00
8	2347.87	36.44	0.532	0.60 ( 0.47)	0.78	4572.7	10360.00
9	2342.65	37.24	0.526	0.60 ( 0.47)	0.78	4720.0	10200.00
10	2296.08	44.48	0.477	0.60 ( 0.47)	0.78	6041.9	10220.00
11	2270.61	49.10	0.451	0.60 ( 0.47)	0.78	6880.9	50500.00
12	1934.29	71.76	0.369	0.60 ( 0.48)	0.80	11526.5	150.00
13	1662.58	93.22	0.330	0.60 ( 0.50)	0.83	15727.5	10100.00
14	1583.73	111.90	0.295	0.60 ( 0.51)	0.84	19785.1	13600.00
15	1523.34	142.39	0.260	0.60 ( 0.52)	0.87	25650.5	11831.00
16	1558.24	165.90	0.239	0.60 ( 0.53)	0.89	30203.5	11530.00
17	1589.92	185.39	0.224	0.60 ( 0.54)	0.90	34574.4	11000.00
18	1648.14	207.59	0.217	0.60 ( 0.55)	0.92	41626.0	10850.00
19	1548.15	223.60	0.212	0.60 ( 0.55)	0.92	45120.0	11220.00
20	1479.10	235.30	0.209	0.60 ( 0.55)	0.92	46934.6	10910.00
21	1291.04	276.72	0.196	0.60 ( 0.56)	0.93	53516.7	12410.00
22	1224.23	310.07	0.186	0.60 ( 0.56)	0.94	59602.6	12261.00
23	1200.87	322.98	0.182	0.60 ( 0.56)	0.94	61089.2	10410.00
24	1178.11	335.31	0.178	0.60 ( 0.56)	0.94	62191.1	12101.10
25	1126.76	363.14	0.170	0.60 ( 0.56)	0.94	64569.2	10200.00
26	1101.84	376.70	0.168	0.60 ( 0.57)	0.94	65507.4	12010.00

27 1046.67 406.25 0.165 0.60( 0.57) 0.94 66181.2 10210.00  
28 973.04 456.03 0.160 0.60( 0.57) 0.94 66680.2 12000.00  
29 913.99 526.13 0.152 0.60( 0.57) 0.94 67265.0 10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2403.00 Tc(MIN.) = 24.31  
AREA-AVERAGED Fm(INCH/HR) = 0.47 AREA-AVERAGED Fp(INCH/HR) = 0.60  
AREA-AVERAGED Ap = 0.78 EFFECTIVE AREA(ACRES) = 2774.16

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13740.00 TO NODE 13741.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13741.00 TO NODE 13741.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506104G.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	7.30	27.55	0.60( 0.48)	0.80	44.3	10400.00	
TOTAL AREA(ACRES) =							44.3

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13741.00 TO NODE 13741.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2403.00	24.31	0.673	0.60( 0.47)	0.78	2774.2	10380.00
2	2402.66	24.84	0.662	0.60( 0.47)	0.78	2833.0	10300.00
3	2398.89	26.19	0.641	0.60( 0.47)	0.78	2977.1	10230.00
4	2387.23	29.46	0.593	0.60( 0.47)	0.78	3387.7	10320.00
5	2383.11	31.34	0.574	0.60( 0.47)	0.78	3617.3	300.00
6	2371.08	33.12	0.559	0.60( 0.47)	0.78	3954.5	10250.00
7	2370.90	33.15	0.559	0.60( 0.47)	0.78	3959.3	10340.00
8	2347.87	36.44	0.532	0.60( 0.47)	0.78	4572.7	10360.00
9	2342.65	37.24	0.526	0.60( 0.47)	0.78	4720.0	10200.00
10	2296.08	44.48	0.477	0.60( 0.47)	0.78	6041.9	10220.00
11	2270.61	49.10	0.451	0.60( 0.47)	0.78	6880.9	50500.00
12	1934.29	71.76	0.369	0.60( 0.48)	0.80	11526.5	150.00
13	1662.58	93.22	0.330	0.60( 0.50)	0.83	15727.5	10100.00
14	1583.73	111.90	0.295	0.60( 0.51)	0.84	19785.1	13600.00
15	1523.34	142.39	0.260	0.60( 0.52)	0.87	25650.5	11831.00
16	1558.24	165.90	0.239	0.60( 0.53)	0.89	30203.5	11530.00
17	1589.92	185.39	0.224	0.60( 0.54)	0.90	34574.4	11000.00
18	1648.14	207.59	0.217	0.60( 0.55)	0.92	41626.0	10850.00
19	1548.15	223.60	0.212	0.60( 0.55)	0.92	45120.0	11220.00
20	1479.10	235.30	0.209	0.60( 0.55)	0.92	46934.6	10910.00
21	1291.04	276.72	0.196	0.60( 0.56)	0.93	53516.7	12410.00
22	1224.23	310.07	0.186	0.60( 0.56)	0.94	59602.6	12261.00
23	1200.87	322.98	0.182	0.60( 0.56)	0.94	61089.2	10410.00

24 1178.11 335.31 0.178 0.60( 0.56) 0.94 62191.1 12101.10  
25 1126.76 363.14 0.170 0.60( 0.56) 0.94 64569.2 10200.00  
26 1101.84 376.70 0.168 0.60( 0.57) 0.94 65507.4 12010.00  
27 1046.67 406.25 0.165 0.60( 0.57) 0.94 66181.2 10210.00  
28 973.04 456.03 0.160 0.60( 0.57) 0.94 66680.2 12000.00  
29 913.99 526.13 0.152 0.60( 0.57) 0.94 67265.0 10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128878.41 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	7.30	27.55	0.621	0.60( 0.48)	0.80	44.3	10400.00
LONGEST FLOWPATH FROM NODE 10400.00 TO NODE 13741.00 =							6237.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2410.30	24.31	0.673	0.60( 0.47)	0.78	2813.2	10380.00
2	2409.96	24.84	0.662	0.60( 0.47)	0.78	2872.9	10300.00
3	2406.20	26.19	0.641	0.60( 0.47)	0.78	3019.2	10230.00
4	2401.34	27.55	0.621	0.60( 0.47)	0.78	3192.3	10400.00
5	2393.37	29.46	0.593	0.60( 0.47)	0.78	3432.0	10320.00
6	2389.05	31.34	0.574	0.60( 0.47)	0.78	3661.6	300.00
7	2376.86	33.12	0.559	0.60( 0.47)	0.78	3998.8	10250.00
8	2376.69	33.15	0.559	0.60( 0.47)	0.78	4003.6	10340.00
9	2353.38	36.44	0.532	0.60( 0.47)	0.78	4617.0	10360.00
10	2348.08	37.24	0.526	0.60( 0.47)	0.78	4764.3	10200.00
11	2301.02	44.48	0.477	0.60( 0.47)	0.78	6086.2	10220.00
12	2275.28	49.10	0.451	0.60( 0.47)	0.78	6925.2	50500.00
13	1938.10	71.76	0.369	0.60( 0.48)	0.80	11570.8	150.00
14	1666.00	93.22	0.330	0.60( 0.50)	0.83	15771.8	10100.00
15	1586.78	111.90	0.295	0.60( 0.51)	0.84	19829.4	13600.00
16	1526.02	142.39	0.260	0.60( 0.52)	0.87	25694.8	11831.00
17	1560.71	165.90	0.239	0.60( 0.53)	0.89	30247.8	11530.00
18	1592.24	185.39	0.224	0.60( 0.54)	0.90	34618.7	11000.00
19	1650.38	207.59	0.217	0.60( 0.55)	0.92	41670.3	10850.00
20	1550.35	223.60	0.212	0.60( 0.55)	0.92	45164.3	11220.00
21	1481.26	235.30	0.209	0.60( 0.55)	0.92	46978.9	10910.00
22	1293.07	276.72	0.196	0.60( 0.56)	0.93	53561.0	12410.00
23	1226.14	310.07	0.186	0.60( 0.56)	0.94	59646.9	12261.00
24	1202.75	322.98	0.182	0.60( 0.56)	0.94	61133.5	10410.00
25	1179.94	335.31	0.178	0.60( 0.56)	0.94	62235.4	12101.10
26	1128.52	363.14	0.170	0.60( 0.56)	0.94	64613.5	10200.00
27	1103.58	376.70	0.168	0.60( 0.57)	0.94	65551.7	12010.00
28	1048.38	406.25	0.165	0.60( 0.57)	0.94	66225.5	10210.00
29	974.69	456.03	0.160	0.60( 0.57)	0.94	66724.5	12000.00
30	915.57	526.13	0.152	0.60( 0.57)	0.94	67309.3	10100.00
TOTAL AREA(ACRES) =							67309.3

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 2410.30 Tc(MIN.) = 24.311  
EFFECTIVE AREA(ACRES) = 2813.25 AREA-AVERAGED Fm(INCH/HR) = 0.47  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.78  
TOTAL AREA(ACRES) = 67309.3  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128878.41 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13741.00 TO NODE 13802.00 IS CODE = 51



-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<  
=====

ELEVATION DATA: UPSTREAM(FEET) = 141.00 DOWNSTREAM(FEET) = 135.00  
CHANNEL LENGTH THRU SUBAREA( FEET) = 1533.41 CHANNEL SLOPE = 0.0039  
CHANNEL BASE( FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH( FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA(CFS) = 2410.30  
FLOW VELOCITY( FEET/SEC.) = 8.56 FLOW DEPTH( FEET) = 9.69  
TRAVEL TIME( MIN.) = 2.98 Tc( MIN.) = 27.30  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130411.82 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2410.30	27.30	0.625	0.60( 0.47)	0.78	2813.2	10380.00
2	2409.96	27.83	0.617	0.60( 0.47)	0.78	2872.9	10300.00
3	2406.20	29.17	0.597	0.60( 0.47)	0.78	3019.2	10230.00
4	2401.34	30.54	0.581	0.60( 0.47)	0.78	3192.3	10400.00
5	2393.37	32.45	0.565	0.60( 0.47)	0.78	3432.0	10320.00
6	2389.05	34.34	0.549	0.60( 0.47)	0.78	3661.6	300.00
7	2376.86	36.11	0.535	0.60( 0.47)	0.78	3998.8	10250.00
8	2376.69	36.14	0.535	0.60( 0.47)	0.78	4003.6	10340.00
9	2353.38	39.44	0.508	0.60( 0.47)	0.78	4617.0	10360.00
10	2348.08	40.24	0.502	0.60( 0.47)	0.78	4764.3	10200.00
11	2301.02	47.50	0.460	0.60( 0.47)	0.78	6086.2	10220.00
12	2275.28	52.13	0.434	0.60( 0.47)	0.78	6925.2	50500.00
13	1938.10	74.91	0.363	0.60( 0.48)	0.80	11570.8	150.00
14	1666.00	96.49	0.324	0.60( 0.50)	0.83	15771.8	10100.00
15	1586.78	115.21	0.289	0.60( 0.51)	0.84	19829.4	13600.00
16	1526.02	145.74	0.257	0.60( 0.52)	0.87	25694.8	11831.00
17	1560.71	169.22	0.236	0.60( 0.53)	0.89	30247.8	11530.00
18	1592.24	188.70	0.223	0.60( 0.54)	0.90	34618.7	11000.00
19	1650.38	210.87	0.216	0.60( 0.55)	0.92	41670.3	10850.00
20	1550.35	226.93	0.211	0.60( 0.55)	0.92	45164.3	11220.00
21	1481.26	238.67	0.208	0.60( 0.55)	0.92	46978.9	10910.00
22	1293.07	280.21	0.195	0.60( 0.56)	0.93	53561.0	12410.00
23	1226.14	313.61	0.184	0.60( 0.56)	0.94	59646.9	12261.00
24	1202.75	326.53	0.180	0.60( 0.56)	0.94	61133.5	10410.00
25	1179.94	338.87	0.177	0.60( 0.56)	0.94	62235.4	12101.10
26	1128.52	366.75	0.169	0.60( 0.56)	0.94	64613.5	10200.00
27	1103.58	380.33	0.168	0.60( 0.57)	0.94	65551.7	12010.00
28	1048.38	409.93	0.165	0.60( 0.57)	0.94	66225.5	10210.00
29	974.69	459.78	0.159	0.60( 0.57)	0.94	66724.5	12000.00
30	915.57	529.93	0.152	0.60( 0.57)	0.94	67309.3	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2410.30 Tc(MIN.) = 27.30  
AREA-AVERAGED Fm(INCH/HR) = 0.47 AREA-AVERAGED Fp(INCH/HR) = 0.60  
AREA-AVERAGED Ap = 0.78 EFFECTIVE AREA(ACRES) = 2813.25

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 3 <<<<  
=====

\*\*\*\*\*

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 3 <<<<  
=====

PEAK FLOWRATE TABLE FILE NAME: 0506105N.DNA  
MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	32.00	17.46	0.60( 0.53)	0.88	140.9	10520.00
2	10.21	60.70	0.60( 0.56)	0.93	403.6	10500.00
TOTAL AREA(ACRES) =						403.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<  
=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2410.30	27.30	0.625	0.60( 0.47)	0.78	2813.2	10380.00
2	2409.96	27.83	0.617	0.60( 0.47)	0.78	2872.9	10300.00
3	2406.20	29.17	0.597	0.60( 0.47)	0.78	3019.2	10230.00
4	2401.34	30.54	0.581	0.60( 0.47)	0.78	3192.3	10400.00
5	2393.37	32.45	0.565	0.60( 0.47)	0.78	3432.0	10320.00
6	2389.05	34.34	0.549	0.60( 0.47)	0.78	3661.6	300.00
7	2376.86	36.11	0.535	0.60( 0.47)	0.78	3998.8	10250.00
8	2376.69	36.14	0.535	0.60( 0.47)	0.78	4003.6	10340.00
9	2353.38	39.44	0.508	0.60( 0.47)	0.78	4617.0	10360.00
10	2348.08	40.24	0.502	0.60( 0.47)	0.78	4764.3	10200.00
11	2301.02	47.50	0.460	0.60( 0.47)	0.78	6086.2	10220.00
12	2275.28	52.13	0.434	0.60( 0.47)	0.78	6925.2	50500.00
13	1938.10	74.91	0.363	0.60( 0.48)	0.80	11570.8	150.00
14	1666.00	96.49	0.324	0.60( 0.50)	0.83	15771.8	10100.00
15	1586.78	115.21	0.289	0.60( 0.51)	0.84	19829.4	13600.00
16	1526.02	145.74	0.257	0.60( 0.52)	0.87	25694.8	11831.00
17	1560.71	169.22	0.236	0.60( 0.53)	0.89	30247.8	11530.00
18	1592.24	188.70	0.223	0.60( 0.54)	0.90	34618.7	11000.00
19	1650.38	210.87	0.216	0.60( 0.55)	0.92	41670.3	10850.00
20	1550.35	226.93	0.211	0.60( 0.55)	0.92	45164.3	11220.00
21	1481.26	238.67	0.208	0.60( 0.55)	0.92	46978.9	10910.00
22	1293.07	280.21	0.195	0.60( 0.56)	0.93	53561.0	12410.00
23	1226.14	313.61	0.184	0.60( 0.56)	0.94	59646.9	12261.00
24	1202.75	326.53	0.180	0.60( 0.56)	0.94	61133.5	10410.00
25	1179.94	338.87	0.177	0.60( 0.56)	0.94	62235.4	12101.10
26	1128.52	366.75	0.169	0.60( 0.56)	0.94	64613.5	10200.00
27	1103.58	380.33	0.168	0.60( 0.57)	0.94	65551.7	12010.00
28	1048.38	409.93	0.165	0.60( 0.57)	0.94	66225.5	10210.00
29	974.69	459.78	0.159	0.60( 0.57)	0.94	66724.5	12000.00
30	915.57	529.93	0.152	0.60( 0.57)	0.94	67309.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130411.82 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	32.00	17.46	0.843	0.60( 0.53)	0.88	140.9	10520.00
2	10.21	60.70	0.389	0.60( 0.56)	0.93	403.6	10500.00

LONGEST FLOWPATH FROM NODE 10500.00 TO NODE 13802.00 = 12187.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2442.31	17.46	0.843	0.60 ( 0.47)	0.79	1940.9	10520.00
2	2437.35	27.30	0.625	0.60 ( 0.47)	0.79	3013.8	10380.00
3	2436.74	27.83	0.617	0.60 ( 0.47)	0.79	3076.7	10300.00
4	2432.30	29.17	0.597	0.60 ( 0.47)	0.79	3231.2	10230.00
5	2426.76	30.54	0.581	0.60 ( 0.47)	0.79	3412.6	10400.00
6	2417.82	32.45	0.565	0.60 ( 0.47)	0.79	3663.9	10320.00
7	2412.55	34.34	0.549	0.60 ( 0.47)	0.79	3904.9	300.00
8	2399.46	36.11	0.535	0.60 ( 0.47)	0.79	4253.0	10250.00
9	2399.28	36.14	0.535	0.60 ( 0.47)	0.79	4258.0	10340.00
10	2374.30	39.44	0.508	0.60 ( 0.47)	0.79	4891.5	10360.00
11	2368.61	40.24	0.502	0.60 ( 0.47)	0.79	5043.6	10200.00
12	2317.88	47.50	0.460	0.60 ( 0.47)	0.79	6409.6	10220.00
13	2289.81	52.13	0.434	0.60 ( 0.47)	0.78	7276.7	50500.00
14	2158.55	60.70	0.389	0.60 ( 0.47)	0.79	9077.8	10500.00
15	1947.64	74.91	0.363	0.60 ( 0.48)	0.80	11974.4	150.00
16	1674.51	96.49	0.324	0.60 ( 0.50)	0.83	16175.4	10100.00
17	1594.37	115.21	0.289	0.60 ( 0.51)	0.85	20233.0	13600.00
18	1532.77	145.74	0.257	0.60 ( 0.52)	0.87	26098.4	11831.00
19	1566.90	169.22	0.236	0.60 ( 0.53)	0.89	30651.4	11530.00
20	1598.11	188.70	0.223	0.60 ( 0.54)	0.90	35022.3	11000.00
21	1656.07	210.87	0.216	0.60 ( 0.55)	0.92	42073.9	10850.00
22	1555.90	226.93	0.211	0.60 ( 0.55)	0.92	45567.9	11220.00
23	1486.72	238.67	0.208	0.60 ( 0.55)	0.92	47382.5	10910.00
24	1298.18	280.21	0.195	0.60 ( 0.56)	0.93	53964.6	12410.00
25	1230.99	313.61	0.184	0.60 ( 0.56)	0.94	60050.5	12261.00
26	1207.49	326.53	0.180	0.60 ( 0.56)	0.94	61537.1	10410.00
27	1184.58	338.87	0.177	0.60 ( 0.56)	0.94	62639.0	12101.10
28	1132.97	366.75	0.169	0.60 ( 0.56)	0.94	65017.1	10200.00
29	1107.99	380.33	0.168	0.60 ( 0.57)	0.94	65955.3	12010.00
30	1052.70	409.93	0.165	0.60 ( 0.57)	0.94	66629.1	10210.00
31	978.87	459.78	0.159	0.60 ( 0.57)	0.94	67128.1	12000.00
32	919.56	529.93	0.152	0.60 ( 0.57)	0.94	67712.9	10100.00

TOTAL AREA (ACRES) = 67712.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 2442.31 Tc (MIN.) = 17.465  
EFFECTIVE AREA (ACRES) = 1940.90 AREA-AVERAGED Fm (INCH/HR) = 0.47  
AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.94  
TOTAL AREA (ACRES) = 67712.9

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130411.82 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13802.00 TO NODE 13803.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM (FEET) = 135.00 DOWNSTREAM (FEET) = 133.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 207.23 CHANNEL SLOPE = 0.0097  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA (CFS) = 2442.31  
FLOW VELOCITY (FEET/SEC.) = 12.05 FLOW DEPTH (FEET) = 8.22

TRAVEL TIME (MIN.) = 0.29 Tc (MIN.) = 17.75

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130619.05 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2442.31	17.75	0.834	0.60 ( 0.47)	0.79	1940.9	10520.00
2	2437.35	27.58	0.621	0.60 ( 0.47)	0.79	3013.8	10380.00
3	2436.74	28.11	0.613	0.60 ( 0.47)	0.79	3076.7	10300.00
4	2432.30	29.46	0.593	0.60 ( 0.47)	0.79	3231.2	10230.00
5	2426.76	30.82	0.578	0.60 ( 0.47)	0.79	3412.6	10400.00
6	2417.82	32.74	0.563	0.60 ( 0.47)	0.79	3663.9	10320.00
7	2412.55	34.62	0.547	0.60 ( 0.47)	0.79	3904.9	300.00
8	2399.46	36.40	0.532	0.60 ( 0.47)	0.79	4253.0	10250.00
9	2399.28	36.43	0.532	0.60 ( 0.47)	0.79	4258.0	10340.00
10	2374.30	39.73	0.505	0.60 ( 0.47)	0.79	4891.5	10360.00
11	2368.61	40.53	0.500	0.60 ( 0.47)	0.79	5043.6	10200.00
12	2317.88	47.79	0.459	0.60 ( 0.47)	0.79	6409.6	10220.00
13	2289.81	52.42	0.432	0.60 ( 0.47)	0.78	7276.7	50500.00
14	2158.55	61.00	0.388	0.60 ( 0.47)	0.79	9077.8	10500.00
15	1947.64	75.21	0.363	0.60 ( 0.48)	0.80	11974.4	150.00
16	1674.51	96.81	0.323	0.60 ( 0.50)	0.83	16175.4	10100.00
17	1594.37	115.53	0.288	0.60 ( 0.51)	0.85	20233.0	13600.00
18	1532.77	146.06	0.257	0.60 ( 0.52)	0.87	26098.4	11831.00
19	1566.90	169.54	0.235	0.60 ( 0.53)	0.89	30651.4	11530.00
20	1598.11	189.02	0.223	0.60 ( 0.54)	0.90	35022.3	11000.00
21	1656.07	211.18	0.216	0.60 ( 0.55)	0.92	42073.9	10850.00
22	1555.90	227.25	0.211	0.60 ( 0.55)	0.92	45567.9	11220.00
23	1486.72	239.00	0.208	0.60 ( 0.55)	0.92	47382.5	10910.00
24	1298.18	280.54	0.195	0.60 ( 0.56)	0.93	53964.6	12410.00
25	1230.99	313.95	0.184	0.60 ( 0.56)	0.94	60050.5	12261.00
26	1207.49	326.87	0.180	0.60 ( 0.56)	0.94	61537.1	10410.00
27	1184.58	339.22	0.176	0.60 ( 0.56)	0.94	62639.0	12101.10
28	1132.97	367.10	0.169	0.60 ( 0.56)	0.94	65017.1	10200.00
29	1107.99	380.68	0.168	0.60 ( 0.57)	0.94	65955.3	12010.00
30	1052.70	410.28	0.165	0.60 ( 0.57)	0.94	66629.1	10210.00
31	978.87	460.14	0.159	0.60 ( 0.57)	0.94	67128.1	12000.00
32	919.56	530.30	0.152	0.60 ( 0.57)	0.94	67712.9	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 2442.31 Tc (MIN.) = 17.75  
AREA-AVERAGED Fm (INCH/HR) = 0.47 AREA-AVERAGED Fp (INCH/HR) = 0.60  
AREA-AVERAGED Ap = 0.79 EFFECTIVE AREA (ACRES) = 1940.90

\*\*\*\*\*

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 17.75

\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.834

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	48.80	0.60	0.800	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.800  
SUBAREA AREA (ACRES) = 48.80 SUBAREA RUNOFF (CFS) = 15.55  
EFFECTIVE AREA (ACRES) = 1989.70 AREA-AVERAGED Fm (INCH/HR) = 0.47

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA (ACRES) = 67761.7 PEAK FLOW RATE (CFS) = 2442.31  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13802.00 TO NODE 13803.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506106G.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	10.57	19.99	0.60 ( 0.40)	0.67	36.9	10600.00
TOTAL AREA (ACRES) =						36.9

\*\*\*\*\*

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2442.31	17.75	0.834	0.60 ( 0.47)	0.79	1989.7	10520.00
2	2437.35	27.58	0.621	0.60 ( 0.47)	0.79	3062.6	10380.00
3	2436.74	28.11	0.613	0.60 ( 0.47)	0.79	3125.5	10300.00
4	2432.30	29.46	0.593	0.60 ( 0.47)	0.79	3280.0	10230.00
5	2426.76	30.82	0.578	0.60 ( 0.47)	0.79	3461.4	10400.00
6	2417.82	32.74	0.563	0.60 ( 0.47)	0.79	3712.7	10320.00
7	2412.55	34.62	0.547	0.60 ( 0.47)	0.79	3953.7	300.00
8	2399.46	36.40	0.532	0.60 ( 0.47)	0.79	4301.8	10250.00
9	2399.28	36.43	0.532	0.60 ( 0.47)	0.79	4306.8	10340.00
10	2374.30	39.73	0.505	0.60 ( 0.47)	0.79	4940.3	10360.00
11	2368.61	40.53	0.500	0.60 ( 0.47)	0.79	5092.4	10200.00
12	2317.88	47.79	0.459	0.60 ( 0.47)	0.79	6458.4	10220.00
13	2289.81	52.42	0.432	0.60 ( 0.47)	0.78	7325.5	50500.00
14	2158.55	61.00	0.388	0.60 ( 0.47)	0.79	9126.6	10500.00
15	1947.64	75.21	0.363	0.60 ( 0.48)	0.80	12023.2	150.00
16	1674.51	96.81	0.323	0.60 ( 0.50)	0.83	16224.2	10100.00
17	1594.37	115.53	0.288	0.60 ( 0.51)	0.85	20281.8	13600.00
18	1532.77	146.06	0.257	0.60 ( 0.52)	0.87	26147.2	11831.00
19	1566.90	169.54	0.235	0.60 ( 0.53)	0.89	30700.2	11530.00
20	1598.11	189.02	0.223	0.60 ( 0.54)	0.90	35071.1	11000.00
21	1656.07	211.18	0.216	0.60 ( 0.55)	0.92	42122.8	10850.00
22	1555.90	227.25	0.211	0.60 ( 0.55)	0.92	45616.7	11220.00
23	1486.72	239.00	0.208	0.60 ( 0.55)	0.92	47431.3	10910.00
24	1298.18	280.54	0.195	0.60 ( 0.56)	0.93	54013.4	12410.00
25	1230.99	313.95	0.184	0.60 ( 0.56)	0.94	60099.3	12261.00
26	1207.49	326.87	0.180	0.60 ( 0.56)	0.94	61585.9	10410.00
27	1184.58	339.22	0.176	0.60 ( 0.56)	0.94	62687.8	12101.10

28	1132.97	367.10	0.169	0.60 ( 0.56)	0.94	65065.9	10200.00
29	1107.99	380.68	0.168	0.60 ( 0.57)	0.94	66004.1	12010.00
30	1052.70	410.28	0.165	0.60 ( 0.57)	0.94	66677.9	10210.00
31	978.87	460.14	0.159	0.60 ( 0.57)	0.94	67176.9	12000.00
32	919.56	530.30	0.152	0.60 ( 0.57)	0.94	67761.7	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130619.05 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	10.57	19.99	0.761	0.60 ( 0.40)	0.67	36.9	10600.00
LONGEST FLOWPATH FROM NODE 10600.00 TO NODE 13803.00 = 1713.00 FEET.							

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2452.87	17.75	0.834	0.60 ( 0.47)	0.79	2022.5	10520.00
2	2451.74	19.99	0.761	0.60 ( 0.47)	0.79	2271.3	10600.00
3	2443.79	27.58	0.621	0.60 ( 0.47)	0.79	3099.5	10380.00
4	2442.95	28.11	0.613	0.60 ( 0.47)	0.79	3162.4	10300.00
5	2438.05	29.46	0.593	0.60 ( 0.47)	0.79	3316.9	10230.00
6	2432.37	30.82	0.578	0.60 ( 0.47)	0.79	3498.3	10400.00
7	2423.28	32.74	0.563	0.60 ( 0.47)	0.79	3749.6	10320.00
8	2417.86	34.62	0.547	0.60 ( 0.47)	0.79	3990.6	300.00
9	2404.63	36.40	0.532	0.60 ( 0.47)	0.79	4338.7	10250.00
10	2404.44	36.43	0.532	0.60 ( 0.47)	0.79	4343.7	10340.00
11	2379.21	39.73	0.505	0.60 ( 0.47)	0.79	4977.2	10360.00
12	2373.46	40.53	0.500	0.60 ( 0.47)	0.79	5129.3	10200.00
13	2322.33	47.79	0.459	0.60 ( 0.47)	0.79	6495.3	10220.00
14	2294.01	52.42	0.432	0.60 ( 0.47)	0.78	7362.4	50500.00
15	2162.32	61.00	0.388	0.60 ( 0.47)	0.79	9163.5	10500.00
16	1951.16	75.21	0.363	0.60 ( 0.48)	0.80	12060.1	150.00
17	1677.64	96.81	0.323	0.60 ( 0.50)	0.83	16261.1	10100.00
18	1597.17	115.53	0.288	0.60 ( 0.51)	0.85	20318.7	13600.00
19	1535.26	146.06	0.257	0.60 ( 0.52)	0.87	26184.1	11831.00
20	1569.19	169.54	0.235	0.60 ( 0.53)	0.89	30737.1	11530.00
21	1600.27	189.02	0.223	0.60 ( 0.54)	0.90	35108.0	11000.00
22	1658.17	211.18	0.216	0.60 ( 0.55)	0.92	42159.6	10850.00
23	1557.95	227.25	0.211	0.60 ( 0.55)	0.92	45653.6	11220.00
24	1488.74	239.00	0.208	0.60 ( 0.55)	0.92	47468.2	10910.00
25	1300.07	280.54	0.195	0.60 ( 0.56)	0.93	54050.3	12410.00
26	1232.78	313.95	0.184	0.60 ( 0.56)	0.94	60136.2	12261.00
27	1209.24	326.87	0.180	0.60 ( 0.56)	0.94	61622.8	10410.00
28	1186.30	339.22	0.176	0.60 ( 0.56)	0.94	62724.7	12101.10
29	1134.61	367.10	0.169	0.60 ( 0.56)	0.94	65102.8	10200.00
30	1109.62	380.68	0.168	0.60 ( 0.57)	0.94	66041.0	12010.00
31	1054.30	410.28	0.165	0.60 ( 0.57)	0.94	66714.8	10210.00
32	980.42	460.14	0.159	0.60 ( 0.57)	0.94	67213.8	12000.00
33	921.03	530.30	0.152	0.60 ( 0.57)	0.94	67798.6	10100.00
TOTAL AREA (ACRES) =						67798.6	

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 2452.87 Tc (MIN.) = 17.751  
 EFFECTIVE AREA (ACRES) = 2022.46 AREA-AVERAGED Fm (INCH/HR) = 0.47  
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA (ACRES) = 67798.6  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130619.05 FEET.

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 67798.6 TC (MIN.) = 17.75  
 EFFECTIVE AREA (ACRES) = 2022.46 AREA-AVERAGED Fm (INCH/HR) = 0.47  
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.789  
 PEAK FLOW RATE (CFS) = 2452.87

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2452.87	17.75	0.834	0.60 ( 0.47)	0.79	2022.5	10520.00
2	2451.74	19.99	0.761	0.60 ( 0.47)	0.79	2271.3	10600.00
3	2443.79	27.58	0.621	0.60 ( 0.47)	0.79	3099.5	10380.00
4	2442.95	28.11	0.613	0.60 ( 0.47)	0.79	3162.4	10300.00
5	2438.05	29.46	0.593	0.60 ( 0.47)	0.79	3316.9	10230.00
6	2432.37	30.82	0.578	0.60 ( 0.47)	0.79	3498.3	10400.00
7	2423.28	32.74	0.563	0.60 ( 0.47)	0.79	3749.6	10320.00
8	2417.86	34.62	0.547	0.60 ( 0.47)	0.79	3990.6	300.00
9	2404.63	36.40	0.532	0.60 ( 0.47)	0.79	4338.7	10250.00
10	2404.44	36.43	0.532	0.60 ( 0.47)	0.79	4343.7	10340.00
11	2379.21	39.73	0.505	0.60 ( 0.47)	0.79	4977.2	10360.00
12	2373.46	40.53	0.500	0.60 ( 0.47)	0.79	5129.3	10200.00
13	2322.33	47.79	0.459	0.60 ( 0.47)	0.79	6495.3	10220.00
14	2294.01	52.42	0.432	0.60 ( 0.47)	0.78	7362.4	50500.00
15	2162.32	61.00	0.388	0.60 ( 0.47)	0.79	9163.5	10500.00
16	1951.16	75.21	0.363	0.60 ( 0.48)	0.80	12060.1	150.00
17	1677.64	96.81	0.323	0.60 ( 0.50)	0.83	16261.1	10100.00
18	1597.17	115.53	0.288	0.60 ( 0.51)	0.85	20318.7	13600.00
19	1535.26	146.06	0.257	0.60 ( 0.52)	0.87	26184.1	11831.00
20	1569.19	169.54	0.235	0.60 ( 0.53)	0.89	30737.1	11530.00
21	1600.27	189.02	0.223	0.60 ( 0.54)	0.90	35108.0	11000.00
22	1658.17	211.18	0.216	0.60 ( 0.55)	0.92	42159.6	10850.00
23	1557.95	227.25	0.211	0.60 ( 0.55)	0.92	45653.6	11220.00
24	1488.74	239.00	0.208	0.60 ( 0.55)	0.92	47468.2	10910.00
25	1300.07	280.54	0.195	0.60 ( 0.56)	0.93	54050.3	12410.00
26	1232.78	313.95	0.184	0.60 ( 0.56)	0.94	60136.2	12261.00
27	1209.24	326.87	0.180	0.60 ( 0.56)	0.94	61622.8	10410.00
28	1186.30	339.22	0.176	0.60 ( 0.56)	0.94	62724.7	12101.10
29	1134.61	367.10	0.169	0.60 ( 0.56)	0.94	65102.8	10200.00
30	1109.62	380.68	0.168	0.60 ( 0.57)	0.94	66041.0	12010.00
31	1054.30	410.28	0.165	0.60 ( 0.57)	0.94	66714.8	10210.00
32	980.42	460.14	0.159	0.60 ( 0.57)	0.94	67213.8	12000.00
33	921.03	530.30	0.152	0.60 ( 0.57)	0.94	67798.6	10100.00

=====  
 END OF RATIONAL METHOD ANALYSIS

\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA 92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S38- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 2-YR RM EV APRIL 2019 ROKAMOTO \*  
\*\*\*\*\*

FILE NAME: RI02EV38.DAT  
TIME/DATE OF STUDY: 17:08 04/08/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 2.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 1.798
- 2) 10.00; 1.199
- 3) 15.00; 0.922
- 4) 20.00; 0.760
- 5) 25.00; 0.658
- 6) 30.00; 0.584
- 7) 40.00; 0.503
- 8) 50.00; 0.446
- 9) 60.00; 0.390
- 10) 90.00; 0.336
- 11) 120.00; 0.280
- 12) 180.00; 0.226
- 13) 360.00; 0.170
- 14) 1200.00; 0.080

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN CROSSFALL (FT)	TO STREET / SIDE	CROSSFALL (FT)	STREET-CROSSFALL IN- / SIDE	CURB HEIGHT (FT)	GUTTER WIDTH (FT)	GEOMETRIES LIP (FT)	MANNING HIKE FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150	

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI02EV37.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2452.87	17.75	0.60 ( 0.47)	0.79	2022.5	10520.00
2	2322.33	47.79	0.60 ( 0.47)	0.79	6495.3	10220.00
3	2162.32	61.00	0.60 ( 0.47)	0.79	9163.5	10500.00
4	1951.16	75.21	0.60 ( 0.48)	0.80	12060.1	150.00
5	1677.64	96.81	0.60 ( 0.50)	0.83	16261.1	10100.00
6	1597.17	115.53	0.60 ( 0.51)	0.85	20318.7	13600.00
7	1535.26	146.06	0.60 ( 0.52)	0.87	26184.1	11831.00
8	1569.19	169.54	0.60 ( 0.53)	0.89	30737.1	11530.00
9	1600.27	189.02	0.60 ( 0.54)	0.90	35108.0	11000.00
10	1658.17	211.18	0.60 ( 0.55)	0.92	42159.6	10850.00
11	1557.95	227.25	0.60 ( 0.55)	0.92	45653.6	11220.00
12	1300.07	280.54	0.60 ( 0.56)	0.93	54050.3	12410.00
13	1232.78	313.95	0.60 ( 0.56)	0.94	60136.2	12261.00
14	1209.24	326.87	0.60 ( 0.56)	0.94	61622.8	10410.00
15	1186.30	339.22	0.60 ( 0.56)	0.94	62724.7	12101.10
16	1134.61	367.10	0.60 ( 0.56)	0.94	65102.8	10200.00
17	1109.62	380.68	0.60 ( 0.57)	0.94	66041.0	12010.00
18	1054.30	410.28	0.60 ( 0.57)	0.94	66714.8	10210.00
19	980.42	460.14	0.60 ( 0.57)	0.94	67213.8	12000.00
20	921.03	530.30	0.60 ( 0.57)	0.94	67798.6	10100.00
TOTAL AREA (ACRES) =						67798.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2452.87	17.75	0.60 ( 0.47)	0.79	2022.5	10520.00
2	2322.33	47.79	0.60 ( 0.47)	0.79	6495.3	10220.00
3	2162.32	61.00	0.60 ( 0.47)	0.79	9163.5	10500.00
4	1951.16	75.21	0.60 ( 0.48)	0.80	12060.1	150.00
5	1677.64	96.81	0.60 ( 0.50)	0.83	16261.1	10100.00
6	1597.17	115.53	0.60 ( 0.51)	0.85	20318.7	13600.00
7	1535.26	146.06	0.60 ( 0.52)	0.87	26184.1	11831.00
8	1569.19	169.54	0.60 ( 0.53)	0.89	30737.1	11530.00
9	1600.27	189.02	0.60 ( 0.54)	0.90	35108.0	11000.00
10	1658.17	211.18	0.60 ( 0.55)	0.92	42159.6	10850.00
11	1557.95	227.25	0.60 ( 0.55)	0.92	45653.6	11220.00
12	1300.07	280.54	0.60 ( 0.56)	0.93	54050.3	12410.00
13	1232.78	313.95	0.60 ( 0.56)	0.94	60136.2	12261.00

14	1209.24	326.87	0.60	( 0.56)	0.94	61622.8	10410.00
15	1186.30	339.22	0.60	( 0.56)	0.94	62724.7	12101.10
16	1134.61	367.10	0.60	( 0.56)	0.94	65102.8	10200.00
17	1109.62	380.68	0.60	( 0.57)	0.94	66041.0	12010.00
18	1054.30	410.28	0.60	( 0.57)	0.94	66714.8	10210.00
19	980.42	460.14	0.60	( 0.57)	0.94	67213.8	12000.00
20	921.03	530.30	0.60	( 0.57)	0.94	67798.6	10100.00

TOTAL AREA (ACRES) = 67798.6

\*\*\*\*\*

FLOW PROCESS FROM NODE 13803.00 TO NODE 13820.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 140.00 DOWNSTREAM (FEET) = 137.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 926.91 CHANNEL SLOPE = 0.0032  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.770

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	31.44	0.60	0.983	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.983

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 2455.43

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.01

AVERAGE FLOW DEPTH (FEET) = 10.11 TRAVEL TIME (MIN.) = 1.93

Tc (MIN.) = 19.68

SUBAREA AREA (ACRES) = 31.44 SUBAREA RUNOFF (CFS) = 5.11

EFFECTIVE AREA (ACRES) = 2053.90 AREA-AVERAGED Fm (INCH/HR) = 0.48

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.79

TOTAL AREA (ACRES) = 67830.0 PEAK FLOW RATE (CFS) = 2452.87

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 10.10 FLOW VELOCITY (FEET/SEC.) = 8.01

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13820.00 = 131545.95 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2452.87	19.68	0.770	0.60 ( 0.48)	0.79	2053.9	10520.00
2	2322.33	49.75	0.447	0.60 ( 0.47)	0.79	6526.7	10220.00
3	2162.32	62.99	0.385	0.60 ( 0.47)	0.79	9194.9	10500.00
4	1951.16	77.25	0.359	0.60 ( 0.48)	0.80	12091.5	150.00
5	1677.64	98.93	0.319	0.60 ( 0.50)	0.83	16292.6	10100.00
6	1597.17	117.67	0.284	0.60 ( 0.51)	0.85	20350.1	13600.00
7	1535.26	148.23	0.255	0.60 ( 0.52)	0.87	26215.5	11831.00
8	1569.19	171.70	0.233	0.60 ( 0.53)	0.89	30768.5	11530.00
9	1600.27	191.17	0.223	0.60 ( 0.54)	0.90	35139.5	11000.00
10	1658.17	213.31	0.216	0.60 ( 0.55)	0.92	42191.1	10850.00
11	1557.95	229.41	0.211	0.60 ( 0.55)	0.92	45685.0	11220.00
12	1300.07	282.80	0.194	0.60 ( 0.56)	0.93	54081.7	12410.00
13	1232.78	316.24	0.184	0.60 ( 0.56)	0.94	60167.6	12261.00
14	1209.24	329.17	0.180	0.60 ( 0.56)	0.94	61654.2	10410.00
15	1186.30	341.53	0.176	0.60 ( 0.56)	0.94	62756.2	12101.10

16	1134.61	369.43	0.169	0.60 ( 0.56)	0.94	65134.2	10200.00
17	1109.62	383.03	0.168	0.60 ( 0.57)	0.94	66072.5	12010.00
18	1054.30	412.66	0.164	0.60 ( 0.57)	0.94	66746.2	10210.00
19	980.42	462.56	0.159	0.60 ( 0.57)	0.94	67245.2	12000.00
20	921.03	532.76	0.151	0.60 ( 0.57)	0.94	67830.0	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 2452.87 Tc (MIN.) = 19.68

AREA-AVERAGED Fm (INCH/HR) = 0.48 AREA-AVERAGED Fp (INCH/HR) = 0.60

AREA-AVERAGED Ap = 0.79 EFFECTIVE AREA (ACRES) = 2053.90

\*\*\*\*\*

FLOW PROCESS FROM NODE 13803.00 TO NODE 13820.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

TOTAL NUMBER OF STREAMS = 2

CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:

TIME OF CONCENTRATION (MIN.) = 19.68

RAINFALL INTENSITY (INCH/HR) = 0.77

AREA-AVERAGED Fm (INCH/HR) = 0.48

AREA-AVERAGED Fp (INCH/HR) = 0.60

AREA-AVERAGED Ap = 0.79

EFFECTIVE STREAM AREA (ACRES) = 2053.90

TOTAL STREAM AREA (ACRES) = 67830.02

PEAK FLOW RATE (CFS) AT CONFLUENCE = 2452.87

\*\*\*\*\*

FLOW PROCESS FROM NODE 13810.00 TO NODE 13811.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<

>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH (FEET) = 648.54

ELEVATION DATA: UPSTREAM (FEET) = 756.46 DOWNSTREAM (FEET) = 586.02

Tc = K \* [(LENGTH\*\* 3.00) / (ELEVATION CHANGE)] \*\* 0.20

SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 12.293

\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 1.072

SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL, BROADLEAF"	-	5.58	0.60	1.000	0	12.29

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA RUNOFF (CFS) = 2.37

TOTAL AREA (ACRES) = 5.58 PEAK FLOW RATE (CFS) = 2.37

\*\*\*\*\*

FLOW PROCESS FROM NODE 13811.00 TO NODE 13811.50 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 586.02 DOWNSTREAM (FEET) = 437.69

CHANNEL LENGTH THRU SUBAREA (FEET) = 696.28 CHANNEL SLOPE = 0.2130

CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00

\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.938  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	14.79	0.60	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 4.65  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.79  
 AVERAGE FLOW DEPTH (FEET) = 0.57 TRAVEL TIME (MIN.) = 2.42  
 Tc (MIN.) = 14.72  
 SUBAREA AREA (ACRES) = 14.79 SUBAREA RUNOFF (CFS) = 4.50  
 EFFECTIVE AREA (ACRES) = 20.37 AREA-AVERAGED Fm (INCH/HR) = 0.60  
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA (ACRES) = 20.4 PEAK FLOW RATE (CFS) = 6.19

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 0.64 FLOW VELOCITY (FEET/SEC.) = 5.10  
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13811.50 = 1344.82 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13811.50 TO NODE 13812.00 IS CODE = 51

>>>> COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>> TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 437.69 DOWNSTREAM (FEET) = 402.36  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 681.04 CHANNEL SLOPE = 0.0519  
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.817  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	18.41	0.60	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 8.02  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 3.22  
 AVERAGE FLOW DEPTH (FEET) = 0.91 TRAVEL TIME (MIN.) = 3.52  
 Tc (MIN.) = 18.24  
 SUBAREA AREA (ACRES) = 18.41 SUBAREA RUNOFF (CFS) = 3.60  
 EFFECTIVE AREA (ACRES) = 38.78 AREA-AVERAGED Fm (INCH/HR) = 0.60  
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA (ACRES) = 38.8 PEAK FLOW RATE (CFS) = 7.58

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 0.89 FLOW VELOCITY (FEET/SEC.) = 3.19  
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13812.00 = 2025.86 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13812.00 TO NODE 13813.00 IS CODE = 51

>>>> COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>> TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 402.36 DOWNSTREAM (FEET) = 259.72  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1282.56 CHANNEL SLOPE = 0.1112

CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.699  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	27.87	0.60	0.858	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.858  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 9.91  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.49  
 AVERAGE FLOW DEPTH (FEET) = 0.86 TRAVEL TIME (MIN.) = 4.76  
 Tc (MIN.) = 23.00  
 SUBAREA AREA (ACRES) = 27.87 SUBAREA RUNOFF (CFS) = 4.62  
 EFFECTIVE AREA (ACRES) = 66.65 AREA-AVERAGED Fm (INCH/HR) = 0.56  
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.94  
 TOTAL AREA (ACRES) = 66.7 PEAK FLOW RATE (CFS) = 8.07

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 0.79 FLOW VELOCITY (FEET/SEC.) = 4.31  
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13813.00 = 3308.42 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 31

>>>> COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
 >>>> USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 259.72 DOWNSTREAM (FEET) = 137.00  
 FLOW LENGTH (FEET) = 2412.88 MANNING'S N = 0.013  
 ESTIMATED PIPE DIAMETER (INCH) INCREASED TO 36.000  
 DEPTH OF FLOW IN 36.0 INCH PIPE IS 5.8 INCHES  
 PIPE-FLOW VELOCITY (FEET/SEC.) = 10.92  
 ESTIMATED PIPE DIAMETER (INCH) = 36.00 NUMBER OF PIPES = 1  
 PIPE-FLOW (CFS) = 8.07  
 PIPE TRAVEL TIME (MIN.) = 3.68 Tc (MIN.) = 26.68  
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13820.00 = 5721.30 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 81

>>>> ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 26.68  
 \* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.633  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	83.64	0.60	0.570	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.570  
 SUBAREA AREA (ACRES) = 83.64 SUBAREA RUNOFF (CFS) = 21.92  
 EFFECTIVE AREA (ACRES) = 150.29 AREA-AVERAGED Fm (INCH/HR) = 0.44  
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.73  
 TOTAL AREA (ACRES) = 150.3 PEAK FLOW RATE (CFS) = 26.05

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 1

-----  
 >>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<  
 -----

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
 TIME OF CONCENTRATION (MIN.) = 26.68  
 RAINFALL INTENSITY (INCH/HR) = 0.63  
 AREA-AVERAGED Fm (INCH/HR) = 0.44  
 AREA-AVERAGED Fp (INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.73  
 EFFECTIVE STREAM AREA (ACRES) = 150.29  
 TOTAL STREAM AREA (ACRES) = 150.29  
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 26.05

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2452.87	19.68	0.770	0.60 ( 0.48)	0.79	2053.9	10520.00
1	2322.33	49.75	0.447	0.60 ( 0.47)	0.79	6526.7	10220.00
1	2162.32	62.99	0.385	0.60 ( 0.47)	0.79	9194.9	10500.00
1	1951.16	77.25	0.359	0.60 ( 0.48)	0.80	12091.5	150.00
1	1677.64	98.93	0.319	0.60 ( 0.50)	0.83	16292.6	10100.00
1	1597.17	117.67	0.284	0.60 ( 0.51)	0.85	20350.1	13600.00
1	1535.26	148.23	0.255	0.60 ( 0.52)	0.87	26215.5	11831.00
1	1569.19	171.70	0.233	0.60 ( 0.53)	0.89	30768.5	11530.00
1	1600.27	191.17	0.223	0.60 ( 0.54)	0.90	35139.5	11000.00
1	1658.17	213.31	0.216	0.60 ( 0.55)	0.92	42191.1	10850.00
1	1557.95	229.41	0.211	0.60 ( 0.55)	0.92	45685.0	11220.00
1	1300.07	282.80	0.194	0.60 ( 0.56)	0.93	54081.7	12410.00
1	1232.78	316.24	0.184	0.60 ( 0.56)	0.94	60167.6	12261.00
1	1209.24	329.17	0.180	0.60 ( 0.56)	0.94	61654.2	10410.00
1	1186.30	341.53	0.176	0.60 ( 0.56)	0.94	62756.2	12101.10
1	1134.61	369.43	0.169	0.60 ( 0.56)	0.94	65134.2	10200.00
1	1109.62	383.03	0.168	0.60 ( 0.57)	0.94	66072.5	12010.00
1	1054.30	412.66	0.164	0.60 ( 0.57)	0.94	66746.2	10210.00
1	980.42	462.56	0.159	0.60 ( 0.57)	0.94	67245.2	12000.00
1	921.03	532.76	0.151	0.60 ( 0.57)	0.94	67830.0	10100.00
2	26.05	26.68	0.633	0.60 ( 0.44)	0.73	150.3	13810.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2478.92	19.68	0.770	0.60 ( 0.47)	0.79	2164.7	10520.00
2	2448.52	26.68	0.633	0.60 ( 0.47)	0.79	3246.0	13810.00
3	2338.41	49.75	0.447	0.60 ( 0.47)	0.79	6677.0	10220.00
4	2176.14	62.99	0.385	0.60 ( 0.47)	0.79	9345.2	10500.00
5	1964.06	77.25	0.359	0.60 ( 0.48)	0.80	12241.8	150.00
6	1689.12	98.93	0.319	0.60 ( 0.50)	0.83	16442.9	10100.00
7	1607.38	117.67	0.284	0.60 ( 0.51)	0.84	20500.4	13600.00
8	1544.41	148.23	0.255	0.60 ( 0.52)	0.87	26365.8	11831.00
9	1577.57	171.70	0.233	0.60 ( 0.53)	0.89	30918.8	11530.00
10	1608.27	191.17	0.223	0.60 ( 0.54)	0.90	35289.8	11000.00
11	1665.92	213.31	0.216	0.60 ( 0.55)	0.91	42341.4	10850.00
12	1565.52	229.41	0.211	0.60 ( 0.55)	0.92	45835.3	11220.00

13	1307.04	282.80	0.194	0.60 ( 0.56)	0.93	54232.0	12410.00
14	1239.38	316.24	0.184	0.60 ( 0.56)	0.94	60317.9	12261.00
15	1215.69	329.17	0.180	0.60 ( 0.56)	0.94	61804.5	10410.00
16	1192.61	341.53	0.176	0.60 ( 0.56)	0.94	62906.4	12101.10
17	1140.68	369.43	0.169	0.60 ( 0.56)	0.94	65284.5	10200.00
18	1115.64	383.03	0.168	0.60 ( 0.56)	0.94	66222.8	12010.00
19	1060.20	412.66	0.164	0.60 ( 0.57)	0.94	66896.5	10210.00
20	986.13	462.56	0.159	0.60 ( 0.57)	0.94	67395.5	12000.00
21	926.47	532.76	0.151	0.60 ( 0.57)	0.94	67980.3	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 2478.92 Tc (MIN.) = 19.68  
 EFFECTIVE AREA (ACRES) = 2164.74 AREA-AVERAGED Fm (INCH/HR) = 0.47  
 AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA (ACRES) = 67980.3  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13820.00 = 131545.95 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13820.00 TO NODE 13840.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM (FEET) = 137.00 DOWNSTREAM (FEET) = 133.00

CHANNEL LENGTH THRU SUBAREA (FEET) = 1261.34 CHANNEL SLOPE = 0.0032

CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00

\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.713

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	31.60	0.60	0.683	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.683

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 2483.23

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.97

AVERAGE FLOW DEPTH (FEET) = 10.19 TRAVEL TIME (MIN.) = 2.64

Tc (MIN.) = 22.32

SUBAREA AREA (ACRES) = 31.60 SUBAREA RUNOFF (CFS) = 8.62

EFFECTIVE AREA (ACRES) = 2196.34 AREA-AVERAGED Fm (INCH/HR) = 0.47

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.79

TOTAL AREA (ACRES) = 68011.9 PEAK FLOW RATE (CFS) = 2478.92

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 10.18 FLOW VELOCITY (FEET/SEC.) = 7.97

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13840.00 = 132807.30 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2478.92	22.32	0.713	0.60 ( 0.47)	0.79	2196.3	10520.00
2	2448.52	29.33	0.594	0.60 ( 0.47)	0.79	3277.6	13810.00
3	2338.41	52.42	0.432	0.60 ( 0.47)	0.78	6708.6	10220.00
4	2176.14	65.71	0.380	0.60 ( 0.47)	0.79	9376.8	10500.00
5	1964.06	80.05	0.354	0.60 ( 0.48)	0.80	12273.4	150.00
6	1689.12	101.83	0.314	0.60 ( 0.50)	0.83	16474.5	10100.00
7	1607.38	120.61	0.279	0.60 ( 0.51)	0.84	20532.0	13600.00



8	1544.41	151.19	0.252	0.60	(0.52)	0.87	26397.4	11831.00
9	1577.57	174.65	0.231	0.60	(0.53)	0.88	30950.4	11530.00
10	1608.27	194.10	0.222	0.60	(0.54)	0.90	35321.4	11000.00
11	1665.92	216.23	0.215	0.60	(0.55)	0.91	42373.0	10850.00
12	1565.52	232.37	0.210	0.60	(0.55)	0.92	45866.9	11220.00
13	1307.04	285.90	0.193	0.60	(0.56)	0.93	54263.6	12410.00
14	1239.38	319.37	0.183	0.60	(0.56)	0.94	60349.5	12261.00
15	1215.69	332.32	0.179	0.60	(0.56)	0.94	61836.1	10410.00
16	1192.61	344.70	0.175	0.60	(0.56)	0.94	62938.1	12101.10
17	1140.68	372.64	0.169	0.60	(0.56)	0.94	65316.1	10200.00
18	1115.64	386.26	0.167	0.60	(0.56)	0.94	66254.4	12010.00
19	1060.20	415.92	0.164	0.60	(0.57)	0.94	66928.1	10210.00
20	986.13	465.88	0.159	0.60	(0.57)	0.94	67427.1	12000.00
21	926.47	536.13	0.151	0.60	(0.57)	0.94	68011.9	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2478.92 Tc(MIN.) = 22.32  
 AREA-AVERAGED Fm(INCH/HR) = 0.47 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.79 EFFECTIVE AREA(ACRES) = 2196.34

\*\*\*\*\*

FLOW PROCESS FROM NODE 13820.00 TO NODE 13840.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
 TIME OF CONCENTRATION(MIN.) = 22.32  
 RAINFALL INTENSITY(INCH/HR) = 0.71  
 AREA-AVERAGED Fm(INCH/HR) = 0.47  
 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.79  
 EFFECTIVE STREAM AREA(ACRES) = 2196.34  
 TOTAL STREAM AREA(ACRES) = 68011.91  
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 2478.92

\*\*\*\*\*

FLOW PROCESS FROM NODE 13830.00 TO NODE 13831.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH(FEET) = 744.71  
 ELEVATION DATA: UPSTREAM(FEET) = 1100.95 DOWNSTREAM(FEET) = 959.21

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
 SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 13.858  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.985  
 SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	-	5.06	0.60	1.000	0	13.86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA RUNOFF(CFS) = 1.76  
 TOTAL AREA(ACRES) = 5.06 PEAK FLOW RATE(CFS) = 1.76

\*\*\*\*\*

FLOW PROCESS FROM NODE 13831.00 TO NODE 13832.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 959.21 DOWNSTREAM(FEET) = 832.83  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1076.71 CHANNEL SLOPE = 0.1174  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.809

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	32.57	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5.03  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.86  
 AVERAGE FLOW DEPTH(FEET) = 0.66 TRAVEL TIME(MIN.) = 4.64  
 Tc(MIN.) = 18.50  
 SUBAREA AREA(ACRES) = 32.57 SUBAREA RUNOFF(CFS) = 6.12  
 EFFECTIVE AREA(ACRES) = 37.63 AREA-AVERAGED Fm(INCH/HR) = 0.60  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 37.6 PEAK FLOW RATE(CFS) = 7.07

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 0.74 FLOW VELOCITY(FEET/SEC.) = 4.25  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13832.00 = 1821.42 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13832.00 TO NODE 13833.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 832.83 DOWNSTREAM(FEET) = 572.49  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1883.58 CHANNEL SLOPE = 0.1382  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.655

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	32.23	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 7.95  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.68  
 AVERAGE FLOW DEPTH(FEET) = 0.75 TRAVEL TIME(MIN.) = 6.71  
 Tc(MIN.) = 25.21  
 SUBAREA AREA(ACRES) = 32.23 SUBAREA RUNOFF(CFS) = 1.59  
 EFFECTIVE AREA(ACRES) = 69.86 AREA-AVERAGED Fm(INCH/HR) = 0.60  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 69.9 PEAK FLOW RATE(CFS) = 7.07  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 0.72 FLOW VELOCITY(FEET/SEC.) = 4.52

LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13833.00 = 3705.00 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13833.00 TO NODE 13834.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 572.49 DOWNSTREAM(FEET) = 471.65  
CHANNEL LENGTH THRU SUBAREA(FEET) = 943.78 CHANNEL SLOPE = 0.1068  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.598

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	27.51	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 7.07

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.10

AVERAGE FLOW DEPTH(FEET) = 0.76 TRAVEL TIME(MIN.) = 3.83

Tc(MIN.) = 29.05

SUBAREA AREA(ACRES) = 27.51 SUBAREA RUNOFF(CFS) = 0.00

EFFECTIVE AREA(ACRES) = 97.37 AREA-AVERAGED Fm(INCH/HR) = 0.60

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 97.4 PEAK FLOW RATE(CFS) = 7.07

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.76 FLOW VELOCITY(FEET/SEC.) = 4.10

LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13834.00 = 4648.78 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13834.00 TO NODE 13835.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 471.65 DOWNSTREAM(FEET) = 347.06  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1647.45 CHANNEL SLOPE = 0.0756  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.530

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	94.21	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 7.07

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.58

AVERAGE FLOW DEPTH(FEET) = 0.81 TRAVEL TIME(MIN.) = 7.68

Tc(MIN.) = 36.72

SUBAREA AREA(ACRES) = 94.21 SUBAREA RUNOFF(CFS) = 0.00

EFFECTIVE AREA(ACRES) = 191.58 AREA-AVERAGED Fm(INCH/HR) = 0.60

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 191.6 PEAK FLOW RATE(CFS) = 7.07

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.81 FLOW VELOCITY(FEET/SEC.) = 3.58

LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13835.00 = 6296.23 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13835.00 TO NODE 13836.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 347.06 DOWNSTREAM(FEET) = 269.29  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1696.71 CHANNEL SLOPE = 0.0458  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.467

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	233.25	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 7.07

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 2.98

AVERAGE FLOW DEPTH(FEET) = 0.89 TRAVEL TIME(MIN.) = 9.50

Tc(MIN.) = 46.23

SUBAREA AREA(ACRES) = 233.25 SUBAREA RUNOFF(CFS) = 0.00

EFFECTIVE AREA(ACRES) = 424.83 AREA-AVERAGED Fm(INCH/HR) = 0.60

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TOTAL AREA(ACRES) = 424.8 PEAK FLOW RATE(CFS) = 7.07

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.89 FLOW VELOCITY(FEET/SEC.) = 2.98

LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13836.00 = 7992.94 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13836.00 TO NODE 13837.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 269.29 DOWNSTREAM(FEET) = 191.87  
CHANNEL LENGTH THRU SUBAREA(FEET) = 2529.21 CHANNEL SLOPE = 0.0306  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.388  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 134.70 0.60 0.880 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.880  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 9.88  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 2.79  
 AVERAGE FLOW DEPTH(FEET) = 1.09 TRAVEL TIME(MIN.) = 15.11  
 Tc(MIN.) = 61.34  
 SUBAREA AREA(ACRES) = 134.70 SUBAREA RUNOFF(CFS) = 5.64  
 EFFECTIVE AREA(ACRES) = 559.53 AREA-AVERAGED Fm(INCH/HR) = 0.58  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.97  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 559.5 PEAK FLOW RATE(CFS) = 7.07  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 0.96 FLOW VELOCITY(FEET/SEC.) = 2.56  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13837.00 = 10522.15 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 31  
 -----

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<  
 -----  
 ELEVATION DATA: UPSTREAM(FEET) = 191.87 DOWNSTREAM(FEET) = 133.00  
 FLOW LENGTH(FEET) = 1151.02 MANNING'S N = 0.013  
 ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000  
 DEPTH OF FLOW IN 36.0 INCH PIPE IS 5.4 INCHES  
 PIPE-FLOW VELOCITY(FEET/SEC.) = 10.51  
 ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1  
 PIPE-FLOW(CFS) = 7.07  
 PIPE TRAVEL TIME(MIN.) = 1.82 Tc(MIN.) = 63.16  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13840.00 = 11673.17 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 -----  
 MAINLINE Tc(MIN.) = 63.16  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.384  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 5.97 0.60 0.622 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.622  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 SUBAREA AREA(ACRES) = 5.97 SUBAREA RUNOFF(CFS) = 0.78

EFFECTIVE AREA(ACRES) = 565.50 AREA-AVERAGED Fm(INCH/HR) = 0.58  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.97  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 565.5 PEAK FLOW RATE(CFS) = 7.07  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 1  
 -----

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<  
 -----  
 TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
 TIME OF CONCENTRATION(MIN.) = 63.16  
 RAINFALL INTENSITY(INCH/HR) = 0.38  
 AREA-AVERAGED Fm(INCH/HR) = 0.58  
 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.97  
 EFFECTIVE STREAM AREA(ACRES) = 565.50  
 TOTAL STREAM AREA(ACRES) = 565.50  
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 7.07

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2478.92	22.32	0.713	0.60( 0.47)	0.79	2196.3	10520.00
1	2448.52	29.33	0.594	0.60( 0.47)	0.79	3277.6	13810.00
1	2338.41	52.42	0.432	0.60( 0.47)	0.78	6708.6	10220.00
1	2176.14	65.71	0.380	0.60( 0.47)	0.79	9376.8	10500.00
1	1964.06	80.05	0.354	0.60( 0.48)	0.80	12273.4	150.00
1	1689.12	101.83	0.314	0.60( 0.50)	0.83	16474.5	10100.00
1	1607.38	120.61	0.279	0.60( 0.51)	0.84	20532.0	13600.00
1	1544.41	151.19	0.252	0.60( 0.52)	0.87	26397.4	11831.00
1	1577.57	174.65	0.231	0.60( 0.53)	0.88	30950.4	11530.00
1	1608.27	194.10	0.222	0.60( 0.54)	0.90	35321.4	11000.00
1	1665.92	216.23	0.215	0.60( 0.55)	0.91	42373.0	10850.00
1	1565.52	232.37	0.210	0.60( 0.55)	0.92	45866.9	11220.00
1	1307.04	285.90	0.193	0.60( 0.56)	0.93	54263.6	12410.00
1	1239.38	319.37	0.183	0.60( 0.56)	0.94	60349.5	12261.00
1	1215.69	332.32	0.179	0.60( 0.56)	0.94	61836.1	10410.00
1	1192.61	344.70	0.175	0.60( 0.56)	0.94	62938.1	12101.10
1	1140.68	372.64	0.169	0.60( 0.56)	0.94	65316.1	10200.00
1	1115.64	386.26	0.167	0.60( 0.56)	0.94	66254.4	12010.00
1	1060.20	415.92	0.164	0.60( 0.57)	0.94	66928.1	10210.00
1	986.13	465.88	0.159	0.60( 0.57)	0.94	67427.1	12000.00
1	926.47	536.13	0.151	0.60( 0.57)	0.94	68011.9	10100.00
2	7.07	63.16	0.384	0.60( 0.58)	0.97	565.5	13830.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2485.99	22.32	0.713	0.60( 0.48)	0.80	2396.1	10520.00
2	2453.59	29.33	0.594	0.60( 0.48)	0.80	3540.1	13810.00

3	2345.01	52.42	0.432	0.60	( 0.48)	0.80	7178.0	10220.00
4	2214.37	63.16	0.384	0.60	( 0.48)	0.80	9429.9	13830.00
5	2183.12	65.71	0.380	0.60	( 0.48)	0.80	9942.3	10500.00
6	1970.57	80.05	0.354	0.60	( 0.48)	0.81	12838.9	150.00
7	1694.89	101.83	0.314	0.60	( 0.50)	0.83	17040.0	10100.00
8	1612.52	120.61	0.279	0.60	( 0.51)	0.85	21097.5	13600.00
9	1549.04	151.19	0.252	0.60	( 0.52)	0.87	26962.9	11831.00
10	1581.82	174.65	0.231	0.60	( 0.53)	0.89	31515.9	11530.00
11	1612.34	194.10	0.222	0.60	( 0.54)	0.90	35886.9	11000.00
12	1669.87	216.23	0.215	0.60	( 0.55)	0.92	42938.5	10850.00
13	1569.38	232.37	0.210	0.60	( 0.55)	0.92	46432.4	11220.00
14	1310.59	285.90	0.193	0.60	( 0.56)	0.93	54829.1	12410.00
15	1242.74	319.37	0.183	0.60	( 0.56)	0.94	60915.0	12261.00
16	1218.98	332.32	0.179	0.60	( 0.56)	0.94	62401.6	10410.00
17	1195.82	344.70	0.175	0.60	( 0.56)	0.94	63503.6	12101.10
18	1143.78	372.64	0.169	0.60	( 0.56)	0.94	65881.6	10200.00
19	1118.72	386.26	0.167	0.60	( 0.56)	0.94	66819.9	12010.00
20	1063.22	415.92	0.164	0.60	( 0.57)	0.94	67493.6	10210.00
21	989.05	465.88	0.159	0.60	( 0.57)	0.94	67992.6	12000.00
22	929.25	536.13	0.151	0.60	( 0.57)	0.94	68577.4	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 2485.99 Tc(MIN.) = 22.32  
EFFECTIVE AREA(ACRES) = 2396.14 AREA-AVERAGED Fm(INCH/HR) = 0.48  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.80  
TOTAL AREA(ACRES) = 68577.4  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13840.00 = 132807.30 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13840.00 TO NODE 13860.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 133.00 DOWNSTREAM(FEET) = 130.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 654.44 CHANNEL SLOPE = 0.0046  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.688

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	6.61	0.60	0.975	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.975  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2486.30  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.16  
AVERAGE FLOW DEPTH(FEET) = 9.51 TRAVEL TIME(MIN.) = 1.19  
Tc(MIN.) = 23.51  
SUBAREA AREA(ACRES) = 6.61 SUBAREA RUNOFF(CFS) = 0.62  
EFFECTIVE AREA(ACRES) = 2402.75 AREA-AVERAGED Fm(INCH/HR) = 0.48  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.80  
TOTAL AREA(ACRES) = 68584.0 PEAK FLOW RATE(CFS) = 2485.99  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 9.51 FLOW VELOCITY(FEET/SEC.) = 9.16  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13860.00 = 133461.73 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2485.99	23.51	0.688	0.60( 0.48)	0.80	2402.8	10520.00
2	2453.59	30.52	0.580	0.60( 0.48)	0.80	3546.7	13810.00
3	2345.01	53.63	0.426	0.60( 0.48)	0.80	7184.6	10220.00
4	2214.37	64.39	0.382	0.60( 0.48)	0.80	9436.5	13830.00
5	2183.12	66.94	0.378	0.60( 0.48)	0.80	9948.9	10500.00
6	1970.57	81.31	0.352	0.60( 0.48)	0.81	12845.5	150.00
7	1694.89	103.14	0.311	0.60( 0.50)	0.83	17046.6	10100.00
8	1612.52	121.94	0.278	0.60( 0.51)	0.85	21104.1	13600.00
9	1549.04	152.53	0.251	0.60( 0.52)	0.87	26969.5	11831.00
10	1581.82	175.98	0.230	0.60( 0.53)	0.89	31522.5	11530.00
11	1612.34	195.43	0.221	0.60( 0.54)	0.90	35893.5	11000.00
12	1669.87	217.54	0.214	0.60( 0.55)	0.92	42945.1	10850.00
13	1569.38	233.71	0.209	0.60( 0.55)	0.92	46439.0	11220.00
14	1310.59	287.30	0.193	0.60( 0.56)	0.93	54835.7	12410.00
15	1242.74	320.79	0.182	0.60( 0.56)	0.94	60921.6	12261.00
16	1218.98	333.75	0.178	0.60( 0.56)	0.94	62408.2	10410.00
17	1195.82	346.13	0.174	0.60( 0.56)	0.94	63510.2	12101.10
18	1143.78	374.08	0.168	0.60( 0.56)	0.94	65888.2	10200.00
19	1118.72	387.71	0.167	0.60( 0.56)	0.94	66826.5	12010.00
20	1063.22	417.39	0.164	0.60( 0.57)	0.94	67500.2	10210.00
21	989.05	467.38	0.158	0.60( 0.57)	0.94	67999.2	12000.00
22	929.25	537.65	0.151	0.60( 0.57)	0.94	68584.0	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2485.99 Tc(MIN.) = 23.51  
AREA-AVERAGED Fm(INCH/HR) = 0.48 AREA-AVERAGED Fp(INCH/HR) = 0.60  
AREA-AVERAGED Ap = 0.80 EFFECTIVE AREA(ACRES) = 2402.75

\*\*\*\*\*

FLOW PROCESS FROM NODE 13840.00 TO NODE 13860.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

TOTAL NUMBER OF STREAMS = 2  
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
TIME OF CONCENTRATION(MIN.) = 23.51  
RAINFALL INTENSITY(INCH/HR) = 0.69  
AREA-AVERAGED Fm(INCH/HR) = 0.48  
AREA-AVERAGED Fp(INCH/HR) = 0.60  
AREA-AVERAGED Ap = 0.80  
EFFECTIVE STREAM AREA(ACRES) = 2402.75  
TOTAL STREAM AREA(ACRES) = 68584.02  
PEAK FLOW RATE(CFS) AT CONFLUENCE = 2485.99

\*\*\*\*\*

FLOW PROCESS FROM NODE 13850.00 TO NODE 13851.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH(FEET) = 617.57  
ELEVATION DATA: UPSTREAM(FEET) = 646.95 DOWNSTREAM(FEET) = 490.10

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 12.137

\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 1.081  
SUBAREA Tc AND LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)  
NATURAL FAIR COVER  
"CHAPARRAL,BROADLEAF" - 4.95 0.60 1.000 0 12.14  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA RUNOFF(CFS) = 2.14  
TOTAL AREA(ACRES) = 4.95 PEAK FLOW RATE(CFS) = 2.14

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13851.00 TO NODE 13851.50 IS CODE = 51

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

-----  
ELEVATION DATA: UPSTREAM(FEET) = 490.10 DOWNSTREAM(FEET) = 440.98  
CHANNEL LENGTH THRU SUBAREA(FEET) = 351.14 CHANNEL SLOPE = 0.1399  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.990  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 4.02 0.60 1.000 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2.85  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.60  
AVERAGE FLOW DEPTH(FEET) = 0.51 TRAVEL TIME(MIN.) = 1.63  
Tc(MIN.) = 13.76  
SUBAREA AREA(ACRES) = 4.02 SUBAREA RUNOFF(CFS) = 1.41  
EFFECTIVE AREA(ACRES) = 8.97 AREA-AVERAGED Fm(INCH/HR) = 0.60  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 9.0 PEAK FLOW RATE(CFS) = 3.15

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.53 FLOW VELOCITY(FEET/SEC.) = 3.73  
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13851.50 = 968.71 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13851.50 TO NODE 13852.00 IS CODE = 51

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

-----  
ELEVATION DATA: UPSTREAM(FEET) = 440.98 DOWNSTREAM(FEET) = 395.76  
CHANNEL LENGTH THRU SUBAREA(FEET) = 512.91 CHANNEL SLOPE = 0.0882  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.879  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 7.17 0.60 1.000 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 4.06  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.32  
AVERAGE FLOW DEPTH(FEET) = 0.64 TRAVEL TIME(MIN.) = 2.57  
Tc(MIN.) = 16.34  
SUBAREA AREA(ACRES) = 7.17 SUBAREA RUNOFF(CFS) = 1.80  
EFFECTIVE AREA(ACRES) = 16.14 AREA-AVERAGED Fm(INCH/HR) = 0.60  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 16.1 PEAK FLOW RATE(CFS) = 4.05

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.64 FLOW VELOCITY(FEET/SEC.) = 3.32  
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13852.00 = 1481.62 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13852.00 TO NODE 13853.00 IS CODE = 51

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

-----  
ELEVATION DATA: UPSTREAM(FEET) = 395.76 DOWNSTREAM(FEET) = 354.94  
CHANNEL LENGTH THRU SUBAREA(FEET) = 443.69 CHANNEL SLOPE = 0.0920  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.810  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 6.76 0.60 1.000 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 4.69  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.50  
AVERAGE FLOW DEPTH(FEET) = 0.67 TRAVEL TIME(MIN.) = 2.11  
Tc(MIN.) = 18.45  
SUBAREA AREA(ACRES) = 6.76 SUBAREA RUNOFF(CFS) = 1.28  
EFFECTIVE AREA(ACRES) = 22.90 AREA-AVERAGED Fm(INCH/HR) = 0.60  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 22.9 PEAK FLOW RATE(CFS) = 4.34

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.65 FLOW VELOCITY(FEET/SEC.) = 3.41  
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13853.00 = 1925.31 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13853.00 TO NODE 13854.00 IS CODE = 51

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

-----  
ELEVATION DATA: UPSTREAM(FEET) = 354.94 DOWNSTREAM(FEET) = 263.57  
CHANNEL LENGTH THRU SUBAREA(FEET) = 962.09 CHANNEL SLOPE = 0.0950  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.701  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 18.16 0.60 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5.20  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.62  
 AVERAGE FLOW DEPTH(FEET) = 0.69 TRAVEL TIME(MIN.) = 4.42  
 Tc(MIN.) = 22.88  
 SUBAREA AREA(ACRES) = 18.16 SUBAREA RUNOFF(CFS) = 1.66  
 EFFECTIVE AREA(ACRES) = 41.06 AREA-AVERAGED Fm(INCH/HR) = 0.60  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 41.1 PEAK FLOW RATE(CFS) = 4.34  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 0.65 FLOW VELOCITY(FEET/SEC.) = 3.47  
 LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13854.00 = 2887.40 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13854.00 TO NODE 13855.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 263.57 DOWNSTREAM(FEET) = 188.74  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1228.77 CHANNEL SLOPE = 0.0609  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.592

SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 43.41 0.60 0.707 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.879  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5.59  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.12  
 AVERAGE FLOW DEPTH(FEET) = 0.77 TRAVEL TIME(MIN.) = 6.57  
 Tc(MIN.) = 29.45

SUBAREA AREA(ACRES) = 38.75 SUBAREA RUNOFF(CFS) = 2.50  
 EFFECTIVE AREA(ACRES) = 79.81 AREA-AVERAGED Fm(INCH/HR) = 0.56  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.94  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 79.8 PEAK FLOW RATE(CFS) = 4.34  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 0.70 FLOW VELOCITY(FEET/SEC.) = 2.96  
 LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13855.00 = 4116.17 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 31  
 -----

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 188.74 DOWNSTREAM(FEET) = 130.00

FLOW LENGTH(FEET) = 2092.67 MANNING'S N = 0.013  
 ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000  
 DEPTH OF FLOW IN 36.0 INCH PIPE IS 5.0 INCHES  
 PIPE-FLOW VELOCITY(FEET/SEC.) = 7.36  
 ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1  
 PIPE-FLOW(CFS) = 4.34  
 PIPE TRAVEL TIME(MIN.) = 4.74 Tc(MIN.) = 34.19  
 LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13860.00 = 6208.84 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 34.19  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.550  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 43.41 0.60 0.707 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.707  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 SUBAREA AREA(ACRES) = 43.41 SUBAREA RUNOFF(CFS) = 6.30  
 EFFECTIVE AREA(ACRES) = 123.22 AREA-AVERAGED Fm(INCH/HR) = 0.52  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.86  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 123.2 PEAK FLOW RATE(CFS) = 8.62

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 1  
 -----

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
 TIME OF CONCENTRATION(MIN.) = 34.19  
 RAINFALL INTENSITY(INCH/HR) = 0.55  
 AREA-AVERAGED Fm(INCH/HR) = 0.52  
 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.86  
 EFFECTIVE STREAM AREA(ACRES) = 123.22  
 TOTAL STREAM AREA(ACRES) = 123.22  
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 8.62

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2485.99	23.51	0.688	0.60( 0.48)	0.80	2402.8	10520.00
1	2453.59	30.52	0.580	0.60( 0.48)	0.80	3546.7	13810.00
1	2345.01	53.63	0.426	0.60( 0.48)	0.80	7184.6	10220.00
1	2214.37	64.39	0.382	0.60( 0.48)	0.80	9436.5	13830.00
1	2183.12	66.94	0.378	0.60( 0.48)	0.80	9948.9	10500.00
1	1970.57	81.31	0.352	0.60( 0.48)	0.81	12845.5	150.00
1	1694.89	103.14	0.311	0.60( 0.50)	0.83	17046.6	10100.00

1	1612.52	121.94	0.278	0.60	(0.51)	0.85	21104.1	13600.00
1	1549.04	152.53	0.251	0.60	(0.52)	0.87	26969.5	11831.00
1	1581.82	175.98	0.230	0.60	(0.53)	0.89	31522.5	11530.00
1	1612.34	195.43	0.221	0.60	(0.54)	0.90	35893.5	11000.00
1	1669.87	217.54	0.214	0.60	(0.55)	0.92	42945.1	10850.00
1	1569.38	233.71	0.209	0.60	(0.55)	0.92	46439.0	11220.00
1	1310.59	287.30	0.193	0.60	(0.56)	0.93	54835.7	12410.00
1	1242.74	320.79	0.182	0.60	(0.56)	0.94	60921.6	12261.00
1	1218.98	333.75	0.178	0.60	(0.56)	0.94	62408.2	10410.00
1	1195.82	346.13	0.174	0.60	(0.56)	0.94	63510.2	12101.10
1	1143.78	374.08	0.168	0.60	(0.56)	0.94	65888.2	10200.00
1	1118.72	387.71	0.167	0.60	(0.56)	0.94	66826.5	12010.00
1	1063.22	417.39	0.164	0.60	(0.57)	0.94	67500.2	10210.00
1	989.05	467.38	0.158	0.60	(0.57)	0.94	67999.2	12000.00
1	929.25	537.65	0.151	0.60	(0.57)	0.94	68584.0	10100.00
2	8.62	34.19	0.550	0.60	(0.52)	0.86	123.2	13850.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2494.61	23.51	0.688	0.60 (0.48)	0.80	2487.5	10520.00
2	2461.70	30.52	0.580	0.60 (0.48)	0.80	3656.7	13810.00
3	2444.98	34.19	0.550	0.60 (0.48)	0.80	4247.2	13850.00
4	2351.68	53.63	0.426	0.60 (0.48)	0.80	7307.8	10220.00
5	2220.35	64.39	0.382	0.60 (0.48)	0.80	9559.7	13830.00
6	2189.03	66.94	0.378	0.60 (0.48)	0.80	10072.1	10500.00
7	1976.08	81.31	0.352	0.60 (0.48)	0.81	12968.7	150.00
8	1699.77	103.14	0.311	0.60 (0.50)	0.83	17169.8	10100.00
9	1616.88	121.94	0.278	0.60 (0.51)	0.85	21227.4	13600.00
10	1552.97	152.53	0.251	0.60 (0.52)	0.87	27092.8	11831.00
11	1585.42	175.98	0.230	0.60 (0.53)	0.89	31645.8	11530.00
12	1615.81	195.43	0.221	0.60 (0.54)	0.90	36016.7	11000.00
13	1673.22	217.54	0.214	0.60 (0.55)	0.92	43068.3	10850.00
14	1572.66	233.71	0.209	0.60 (0.55)	0.92	46562.2	11220.00
15	1313.61	287.30	0.193	0.60 (0.56)	0.93	54958.9	12410.00
16	1245.59	320.79	0.182	0.60 (0.56)	0.94	61044.8	12261.00
17	1221.77	333.75	0.178	0.60 (0.56)	0.94	62531.4	10410.00
18	1198.56	346.13	0.174	0.60 (0.56)	0.94	63633.4	12101.10
19	1146.42	374.08	0.168	0.60 (0.56)	0.94	66011.5	10200.00
20	1121.33	387.71	0.167	0.60 (0.56)	0.94	66949.7	12010.00
21	1065.79	417.39	0.164	0.60 (0.57)	0.94	67623.4	10210.00
22	991.53	467.38	0.158	0.60 (0.57)	0.94	68122.5	12000.00
23	931.62	537.65	0.151	0.60 (0.57)	0.94	68707.2	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 2494.61 Tc (MIN.) = 23.51  
EFFECTIVE AREA(ACRES) = 2487.47 AREA-AVERAGED Fm(INCH/HR) = 0.48  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.80  
TOTAL AREA(ACRES) = 68707.2  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13860.00 = 133461.73 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13860.00 TO NODE 13880.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 130.00 DOWNSTREAM(FEET) = 120.57  
CHANNEL LENGTH THRU SUBAREA(FEET) = 610.77 CHANNEL SLOPE = 0.0154  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.674

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	4.89	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2494.77

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 14.45

AVERAGE FLOW DEPTH(FEET) = 7.59 TRAVEL TIME(MIN.) = 0.70

Tc(MIN.) = 24.21

SUBAREA AREA(ACRES) = 4.89 SUBAREA RUNOFF(CFS) = 0.33

EFFECTIVE AREA(ACRES) = 2492.36 AREA-AVERAGED Fm(INCH/HR) = 0.48

AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.81

TOTAL AREA(ACRES) = 68712.1 PEAK FLOW RATE(CFS) = 2494.61

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 7.59 FLOW VELOCITY(FEET/SEC.) = 14.45

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13880.00 = 134072.50 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2494.61	24.21	0.674	0.60 (0.48)	0.81	2492.4	10520.00
2	2461.70	31.23	0.574	0.60 (0.48)	0.80	3661.6	13810.00
3	2444.98	34.90	0.544	0.60 (0.48)	0.80	4252.0	13850.00
4	2351.68	54.35	0.422	0.60 (0.48)	0.80	7312.7	10220.00
5	2220.35	65.11	0.381	0.60 (0.48)	0.80	9564.6	13830.00
6	2189.03	67.67	0.376	0.60 (0.48)	0.80	10077.0	10500.00
7	1976.08	82.05	0.350	0.60 (0.48)	0.81	12973.6	150.00
8	1699.77	103.92	0.310	0.60 (0.50)	0.83	17174.7	10100.00
9	1616.88	122.72	0.278	0.60 (0.51)	0.85	21232.2	13600.00
10	1552.97	153.33	0.250	0.60 (0.52)	0.87	27097.7	11831.00
11	1585.42	176.77	0.229	0.60 (0.53)	0.89	31650.7	11530.00
12	1615.81	196.22	0.221	0.60 (0.54)	0.90	36021.6	11000.00
13	1673.22	218.32	0.214	0.60 (0.55)	0.92	43073.2	10850.00
14	1572.66	234.50	0.209	0.60 (0.55)	0.92	46567.1	11220.00
15	1313.61	288.12	0.192	0.60 (0.56)	0.93	54963.8	12410.00
16	1245.59	321.63	0.182	0.60 (0.56)	0.94	61049.7	12261.00
17	1221.77	334.59	0.178	0.60 (0.56)	0.94	62536.3	10410.00
18	1198.56	346.97	0.174	0.60 (0.56)	0.94	63638.3	12101.10
19	1146.42	374.94	0.168	0.60 (0.56)	0.94	66016.3	10200.00
20	1121.33	388.57	0.167	0.60 (0.56)	0.94	66954.6	12010.00
21	1065.79	418.26	0.164	0.60 (0.57)	0.94	67628.3	10210.00
22	991.53	468.27	0.158	0.60 (0.57)	0.94	68127.4	12000.00
23	931.62	538.56	0.151	0.60 (0.57)	0.94	68712.1	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2494.61 Tc(MIN.) = 24.21

AREA-AVERAGED Fm(INCH/HR) = 0.48 AREA-AVERAGED Fp(INCH/HR) = 0.60

AREA-AVERAGED Ap = 0.81 EFFECTIVE AREA(ACRES) = 2492.36

```

*****
FLOW PROCESS FROM NODE 13860.00 TO NODE 13880.00 IS CODE = 1
-----
>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
-----
TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION(MIN.) = 24.21
RAINFALL INTENSITY(INCH/HR) = 0.67
AREA-AVERAGED Fm(INCH/HR) = 0.48
AREA-AVERAGED Fp(INCH/HR) = 0.60
AREA-AVERAGED Ap = 0.81
EFFECTIVE STREAM AREA(ACRES) = 2492.36
TOTAL STREAM AREA(ACRES) = 68712.13
PEAK FLOW RATE(CFS) AT CONFLUENCE = 2494.61

```

```

*****
FLOW PROCESS FROM NODE 13870.00 TO NODE 13871.00 IS CODE = 21
-----
>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<
-----
INITIAL SUBAREA FLOW-LENGTH(FEET) = 872.65
ELEVATION DATA: UPSTREAM(FEET) = 558.52 DOWNSTREAM(FEET) = 436.47

Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 15.704
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.899
SUBAREA Tc AND LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)
NATURAL FAIR COVER
"GRASS" - 7.32 0.60 1.000 0 15.70
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 1.97
TOTAL AREA(ACRES) = 7.32 PEAK FLOW RATE(CFS) = 1.97

```

```

*****
FLOW PROCESS FROM NODE 13871.00 TO NODE 13872.00 IS CODE = 51
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
-----
ELEVATION DATA: UPSTREAM(FEET) = 436.47 DOWNSTREAM(FEET) = 337.62
CHANNEL LENGTH THRU SUBAREA(FEET) = 827.95 CHANNEL SLOPE = 0.1194
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.770
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 13.01 0.60 1.000 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3.00
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.45
AVERAGE FLOW DEPTH(FEET) = 0.54 TRAVEL TIME(MIN.) = 4.00

```

```

Tc(MIN.) = 19.70
SUBAREA AREA(ACRES) = 13.01 SUBAREA RUNOFF(CFS) = 1.99
EFFECTIVE AREA(ACRES) = 20.33 AREA-AVERAGED Fm(INCH/HR) = 0.60
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 20.3 PEAK FLOW RATE(CFS) = 3.11

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.55 FLOW VELOCITY(FEET/SEC.) = 3.47
LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13872.00 = 1700.60 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13872.00 TO NODE 13873.00 IS CODE = 51
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
-----

```

```

ELEVATION DATA: UPSTREAM(FEET) = 337.62 DOWNSTREAM(FEET) = 253.88
CHANNEL LENGTH THRU SUBAREA(FEET) = 1049.16 CHANNEL SLOPE = 0.0798
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.658
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 32.99 0.60 0.923 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.923
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 4.73
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.32
AVERAGE FLOW DEPTH(FEET) = 0.69 TRAVEL TIME(MIN.) = 5.27
Tc(MIN.) = 24.98
SUBAREA AREA(ACRES) = 32.99 SUBAREA RUNOFF(CFS) = 3.11
EFFECTIVE AREA(ACRES) = 53.32 AREA-AVERAGED Fm(INCH/HR) = 0.57
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.95
TOTAL AREA(ACRES) = 53.3 PEAK FLOW RATE(CFS) = 4.18

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.66 FLOW VELOCITY(FEET/SEC.) = 3.21
LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13873.00 = 2749.76 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13873.00 TO NODE 13874.00 IS CODE = 51
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
-----

```

```

ELEVATION DATA: UPSTREAM(FEET) = 253.88 DOWNSTREAM(FEET) = 160.73
CHANNEL LENGTH THRU SUBAREA(FEET) = 1518.60 CHANNEL SLOPE = 0.0613
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.575
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 30.94 0.60 0.900 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.900
* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;

```



\* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 4.99  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.11  
 AVERAGE FLOW DEPTH(FEET) = 0.64 TRAVEL TIME(MIN.) = 6.16  
 Tc(MIN.) = 31.14  
 SUBAREA AREA(ACRES) = 30.94 SUBAREA RUNOFF(CFS) = 1.60  
 EFFECTIVE AREA(ACRES) = 84.26 AREA-AVERAGED Fm(INCH/HR) = 0.56  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.93  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 84.3 PEAK FLOW RATE(CFS) = 4.18  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 0.59 FLOW VELOCITY(FEET/SEC.) = 3.98  
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13874.00 = 4268.36 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13874.00 TO NODE 13875.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 160.73 DOWNSTREAM(FEET) = 158.14  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 582.74 CHANNEL SLOPE = 0.0044  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.525

SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	73.67	0.60	0.930	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.930

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5.41  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 1.57  
 AVERAGE FLOW DEPTH(FEET) = 1.07 TRAVEL TIME(MIN.) = 6.18  
 Tc(MIN.) = 37.32

SUBAREA AREA(ACRES) = 73.67 SUBAREA RUNOFF(CFS) = 2.44  
 EFFECTIVE AREA(ACRES) = 157.93 AREA-AVERAGED Fm(INCH/HR) = 0.56  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.93  
 \* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 157.9 PEAK FLOW RATE(CFS) = 5.10

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.05 FLOW VELOCITY(FEET/SEC.) = 1.55  
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13875.00 = 4851.10 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 31  
 -----

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 158.14 DOWNSTREAM(FEET) = 120.57

FLOW LENGTH(FEET) = 1855.67 MANNING'S N = 0.013  
 ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000  
 DEPTH OF FLOW IN 36.0 INCH PIPE IS 5.8 INCHES  
 PIPE-FLOW VELOCITY(FEET/SEC.) = 6.89  
 ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1  
 PIPE-FLOW(CFS) = 5.10  
 PIPE TRAVEL TIME(MIN.) = 4.49 Tc(MIN.) = 41.81  
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13880.00 = 6706.77 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 41.81  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.493  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	34.90	0.60	0.743	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.743

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.

SUBAREA AREA(ACRES) = 34.90 SUBAREA RUNOFF(CFS) = 3.98  
 EFFECTIVE AREA(ACRES) = 192.83 AREA-AVERAGED Fm(INCH/HR) = 0.54  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.90

\* RAINFALL INTENSITY IS LESS THAN AREA-AVERAGED Fp;  
 \* IMPERVIOUS AREA USED FOR RUNOFF ESTIMATES.  
 TOTAL AREA(ACRES) = 192.8 PEAK FLOW RATE(CFS) = 8.76

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 1  
 -----

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

\*\*\*\*\*  
 TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
 TIME OF CONCENTRATION(MIN.) = 41.81  
 RAINFALL INTENSITY(INCH/HR) = 0.49  
 AREA-AVERAGED Fm(INCH/HR) = 0.54  
 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.90  
 EFFECTIVE STREAM AREA(ACRES) = 192.83  
 TOTAL STREAM AREA(ACRES) = 192.83  
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 8.76

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2494.61	24.21	0.674	0.60( 0.48)	0.81	2492.4	10520.00
1	2461.70	31.23	0.574	0.60( 0.48)	0.80	3661.6	13810.00
1	2444.98	34.90	0.544	0.60( 0.48)	0.80	4252.0	13850.00
1	2351.68	54.35	0.422	0.60( 0.48)	0.80	7312.7	10220.00
1	2220.35	65.11	0.381	0.60( 0.48)	0.80	9564.6	13830.00
1	2189.03	67.67	0.376	0.60( 0.48)	0.80	10077.0	10500.00
1	1976.08	82.05	0.350	0.60( 0.48)	0.81	12973.6	150.00

1	1699.77	103.92	0.310	0.60	(0.50)	0.83	17174.7	10100.00
1	1616.88	122.72	0.278	0.60	(0.51)	0.85	21232.2	13600.00
1	1552.97	153.33	0.250	0.60	(0.52)	0.87	27097.7	11831.00
1	1585.42	176.77	0.229	0.60	(0.53)	0.89	31650.7	11530.00
1	1615.81	196.22	0.221	0.60	(0.54)	0.90	36021.6	11000.00
1	1673.22	218.32	0.214	0.60	(0.55)	0.92	43073.2	10850.00
1	1572.66	234.50	0.209	0.60	(0.55)	0.92	46567.1	11220.00
1	1313.61	288.12	0.192	0.60	(0.56)	0.93	54963.8	12410.00
1	1245.59	321.63	0.182	0.60	(0.56)	0.94	61049.7	12261.00
1	1221.77	334.59	0.178	0.60	(0.56)	0.94	62536.3	10410.00
1	1198.56	346.97	0.174	0.60	(0.56)	0.94	63638.3	12101.10
1	1146.42	374.94	0.168	0.60	(0.56)	0.94	66016.3	10200.00
1	1121.33	388.57	0.167	0.60	(0.56)	0.94	66954.6	12010.00
1	1065.79	418.26	0.164	0.60	(0.57)	0.94	67628.3	10210.00
1	991.53	468.27	0.158	0.60	(0.57)	0.94	68127.4	12000.00
1	931.62	538.56	0.151	0.60	(0.57)	0.94	68712.1	10100.00
2	8.76	41.81	0.493	0.60	(0.54)	0.90	192.8	13870.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2503.37	24.21	0.674	0.60 (0.49)	0.81	2604.0	10520.00
2	2469.32	31.23	0.574	0.60 (0.48)	0.81	3805.6	13810.00
3	2453.06	34.90	0.544	0.60 (0.48)	0.81	4413.0	13850.00
4	2420.56	41.81	0.493	0.60 (0.48)	0.80	5533.2	13870.00
5	2359.18	54.35	0.422	0.60 (0.48)	0.80	7505.5	10220.00
6	2227.13	65.11	0.381	0.60 (0.48)	0.80	9757.4	13830.00
7	2195.72	67.67	0.376	0.60 (0.48)	0.80	10269.9	10500.00
8	1982.31	82.05	0.350	0.60 (0.48)	0.81	13166.4	150.00
9	1705.28	103.92	0.310	0.60 (0.50)	0.83	17367.5	10100.00
10	1621.82	122.72	0.278	0.60 (0.51)	0.85	21425.1	13600.00
11	1557.42	153.33	0.250	0.60 (0.52)	0.87	27290.5	11831.00
12	1589.49	176.77	0.229	0.60 (0.53)	0.89	31843.5	11530.00
13	1619.74	196.22	0.221	0.60 (0.54)	0.90	36214.4	11000.00
14	1677.03	218.32	0.214	0.60 (0.55)	0.92	43266.0	10850.00
15	1576.37	234.50	0.209	0.60 (0.55)	0.92	46759.9	11220.00
16	1317.03	288.12	0.192	0.60 (0.56)	0.93	55156.6	12410.00
17	1248.83	321.63	0.182	0.60 (0.56)	0.94	61242.5	12261.00
18	1224.93	334.59	0.178	0.60 (0.56)	0.94	62729.1	10410.00
19	1201.65	346.97	0.174	0.60 (0.56)	0.94	63831.1	12101.10
20	1149.42	374.94	0.168	0.60 (0.56)	0.94	66209.2	10200.00
21	1124.30	388.57	0.167	0.60 (0.56)	0.94	67147.4	12010.00
22	1068.70	418.26	0.164	0.60 (0.57)	0.94	67821.1	10210.00
23	994.35	468.27	0.158	0.60 (0.57)	0.94	68320.2	12000.00
24	934.30	538.56	0.151	0.60 (0.57)	0.94	68905.0	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 2503.37 Tc(MIN.) = 24.21  
EFFECTIVE AREA(ACRES) = 2604.02 AREA-AVERAGED Fm(INCH/HR) = 0.49  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.81  
TOTAL AREA(ACRES) = 68905.0  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13880.00 = 134072.50 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13880.00 TO NODE 13910.00 IS CODE = 51

```

-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 120.57 DOWNSTREAM(FEET) = 119.70
CHANNEL LENGTH THRU SUBAREA(FEET) = 1190.21 CHANNEL SLOPE = 0.0007
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.606
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 117.69 0.60 0.724 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.724
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2512.48
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.61
AVERAGE FLOW DEPTH(FEET) = 13.48 TRAVEL TIME(MIN.) = 4.30
Tc(MIN.) = 28.51
SUBAREA AREA(ACRES) = 117.69 SUBAREA RUNOFF(CFS) = 18.19
EFFECTIVE AREA(ACRES) = 2721.71 AREA-AVERAGED Fm(INCH/HR) = 0.48
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.81
TOTAL AREA(ACRES) = 69022.6 PEAK FLOW RATE(CFS) = 2503.37
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 13.46 FLOW VELOCITY(FEET/SEC.) = 4.61  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13910.00 = 135262.70 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2503.37	28.51	0.606	0.60 (0.48)	0.81	2721.7	10520.00
2	2469.32	35.54	0.539	0.60 (0.48)	0.80	3923.3	13810.00
3	2453.06	39.22	0.509	0.60 (0.48)	0.80	4530.7	13850.00
4	2420.56	46.15	0.468	0.60 (0.48)	0.80	5650.9	13870.00
5	2359.18	58.71	0.397	0.60 (0.48)	0.80	7623.2	10220.00
6	2227.13	69.54	0.373	0.60 (0.48)	0.80	9875.1	13830.00
7	2195.72	72.12	0.368	0.60 (0.48)	0.80	10387.5	10500.00
8	1982.31	86.61	0.342	0.60 (0.48)	0.81	13284.1	150.00
9	1705.28	108.65	0.301	0.60 (0.50)	0.83	17485.2	10100.00
10	1621.82	127.52	0.273	0.60 (0.51)	0.85	21542.8	13600.00
11	1557.42	158.17	0.246	0.60 (0.52)	0.87	27408.2	11831.00
12	1589.49	181.59	0.226	0.60 (0.53)	0.89	31961.2	11530.00
13	1619.74	201.01	0.219	0.60 (0.54)	0.90	36332.1	11000.00
14	1677.03	223.07	0.213	0.60 (0.55)	0.91	43383.7	10850.00
15	1576.37	239.33	0.208	0.60 (0.55)	0.92	46877.6	11220.00
16	1317.03	293.17	0.191	0.60 (0.56)	0.93	55274.3	12410.00
17	1248.83	326.75	0.180	0.60 (0.56)	0.94	61360.2	12261.00
18	1224.93	339.73	0.176	0.60 (0.56)	0.94	62846.8	10410.00
19	1201.65	352.14	0.172	0.60 (0.56)	0.94	63948.8	12101.10
20	1149.42	380.16	0.168	0.60 (0.56)	0.94	66326.9	10200.00
21	1124.30	393.82	0.166	0.60 (0.56)	0.94	67265.1	12010.00
22	1068.70	423.58	0.163	0.60 (0.56)	0.94	67938.8	10210.00
23	994.35	473.68	0.158	0.60 (0.57)	0.94	68437.9	12000.00
24	934.30	544.06	0.150	0.60 (0.57)	0.94	69022.6	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2503.37 Tc(MIN.) = 28.51

AREA-AVERAGED Fm(INCH/HR) = 0.48 AREA-AVERAGED Fp(INCH/HR) = 0.60  
AREA-AVERAGED Ap = 0.81 EFFECTIVE AREA(ACRES) = 2721.71

\*\*\*\*\*

FLOW PROCESS FROM NODE 13880.00 TO NODE 13910.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

TOTAL NUMBER OF STREAMS = 2  
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
TIME OF CONCENTRATION(MIN.) = 28.51  
RAINFALL INTENSITY(INCH/HR) = 0.61  
AREA-AVERAGED Fm(INCH/HR) = 0.48  
AREA-AVERAGED Fp(INCH/HR) = 0.60  
AREA-AVERAGED Ap = 0.81  
EFFECTIVE STREAM AREA(ACRES) = 2721.71  
TOTAL STREAM AREA(ACRES) = 69022.65  
PEAK FLOW RATE(CFS) AT CONFLUENCE = 2503.37

\*\*\*\*\*

FLOW PROCESS FROM NODE 13889.00 TO NODE 13890.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH(FEET) = 447.89  
ELEVATION DATA: UPSTREAM(FEET) = 564.89 DOWNSTREAM(FEET) = 421.92

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 6.976  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 1.561  
SUBAREA Tc AND LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)  
PUBLIC PARK - 3.03 0.60 0.960 0 6.98  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.960  
SUBAREA RUNOFF(CFS) = 2.69  
TOTAL AREA(ACRES) = 3.03 PEAK FLOW RATE(CFS) = 2.69

\*\*\*\*\*

FLOW PROCESS FROM NODE 13890.00 TO NODE 13891.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 421.92 DOWNSTREAM(FEET) = 392.64  
CHANNEL LENGTH THRU SUBAREA(FEET) = 435.33 CHANNEL SLOPE = 0.0673  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 1.365  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 8.12 0.60 0.986 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.986  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5.53

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.42  
AVERAGE FLOW DEPTH(FEET) = 0.65 TRAVEL TIME(MIN.) = 1.64  
Tc(MIN.) = 8.62  
SUBAREA AREA(ACRES) = 8.12 SUBAREA RUNOFF(CFS) = 5.65  
EFFECTIVE AREA(ACRES) = 11.15 AREA-AVERAGED Fm(INCH/HR) = 0.59  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.98  
TOTAL AREA(ACRES) = 11.1 PEAK FLOW RATE(CFS) = 7.80

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.74 FLOW VELOCITY(FEET/SEC.) = 4.78  
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13891.00 = 883.22 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13891.00 TO NODE 13892.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 392.64 DOWNSTREAM(FEET) = 324.46  
CHANNEL LENGTH THRU SUBAREA(FEET) = 662.40 CHANNEL SLOPE = 0.1029  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 1.176  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 12.50 0.60 1.000 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 11.05  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.13  
AVERAGE FLOW DEPTH(FEET) = 0.78 TRAVEL TIME(MIN.) = 1.80  
Tc(MIN.) = 10.42  
SUBAREA AREA(ACRES) = 12.50 SUBAREA RUNOFF(CFS) = 6.48  
EFFECTIVE AREA(ACRES) = 23.65 AREA-AVERAGED Fm(INCH/HR) = 0.59  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99  
TOTAL AREA(ACRES) = 23.6 PEAK FLOW RATE(CFS) = 12.39

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.81 FLOW VELOCITY(FEET/SEC.) = 6.27  
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13892.00 = 1545.62 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13892.00 TO NODE 13893.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 324.46 DOWNSTREAM(FEET) = 240.82  
CHANNEL LENGTH THRU SUBAREA(FEET) = 980.03 CHANNEL SLOPE = 0.0853  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 1.030  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 15.87 0.60 1.000 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 15.47  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.22  
 AVERAGE FLOW DEPTH(FEET) = 0.91 TRAVEL TIME(MIN.) = 2.63  
 Tc(MIN.) = 13.05  
 SUBAREA AREA(ACRES) = 15.87 SUBAREA RUNOFF(CFS) = 6.15  
 EFFECTIVE AREA(ACRES) = 39.52 AREA-AVERAGED Fm(INCH/HR) = 0.60  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 39.5 PEAK FLOW RATE(CFS) = 15.44

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 0.91 FLOW VELOCITY(FEET/SEC.) = 6.20  
 LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13893.00 = 2525.65 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13893.00 TO NODE 13894.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

-----  
 ELEVATION DATA: UPSTREAM(FEET) = 240.82 DOWNSTREAM(FEET) = 163.04  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1144.35 CHANNEL SLOPE = 0.0680  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.882

SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	28.41	0.60	0.985	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.985  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 19.20  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.00  
 AVERAGE FLOW DEPTH(FEET) = 1.03 TRAVEL TIME(MIN.) = 3.18  
 Tc(MIN.) = 16.23  
 SUBAREA AREA(ACRES) = 28.41 SUBAREA RUNOFF(CFS) = 7.45  
 EFFECTIVE AREA(ACRES) = 67.93 AREA-AVERAGED Fm(INCH/HR) = 0.59  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 67.9 PEAK FLOW RATE(CFS) = 17.62

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.00 FLOW VELOCITY(FEET/SEC.) = 5.92  
 LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13894.00 = 3670.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 31  
 -----

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

-----  
 ELEVATION DATA: UPSTREAM(FEET) = 163.04 DOWNSTREAM(FEET) = 119.70  
 FLOW LENGTH(FEET) = 1899.01 MANNING'S N = 0.013  
 ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000  
 DEPTH OF FLOW IN 36.0 INCH PIPE IS 10.5 INCHES  
 PIPE-FLOW VELOCITY(FEET/SEC.) = 10.32  
 ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1  
 PIPE-FLOW(CFS) = 17.62  
 PIPE TRAVEL TIME(MIN.) = 3.07 Tc(MIN.) = 19.29

LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13910.00 = 5569.01 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

-----  
 MAINLINE Tc(MIN.) = 19.29  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.783  
 SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	11.69	0.60	0.634	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.634  
 SUBAREA AREA(ACRES) = 11.69 SUBAREA RUNOFF(CFS) = 4.24  
 EFFECTIVE AREA(ACRES) = 79.62 AREA-AVERAGED Fm(INCH/HR) = 0.56  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.94  
 TOTAL AREA(ACRES) = 79.6 PEAK FLOW RATE(CFS) = 17.62  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 1  
 -----

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

-----  
 TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
 TIME OF CONCENTRATION(MIN.) = 19.29  
 RAINFALL INTENSITY(INCH/HR) = 0.78  
 AREA-AVERAGED Fm(INCH/HR) = 0.56  
 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.94  
 EFFECTIVE STREAM AREA(ACRES) = 79.62  
 TOTAL STREAM AREA(ACRES) = 79.62  
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 17.62

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2503.37	28.51	0.606	0.60( 0.48)	0.81	2721.7	10520.00
1	2469.32	35.54	0.539	0.60( 0.48)	0.80	3923.3	13810.00
1	2453.06	39.22	0.509	0.60( 0.48)	0.80	4530.7	13850.00
1	2420.56	46.15	0.468	0.60( 0.48)	0.80	5650.9	13870.00
1	2359.18	58.71	0.397	0.60( 0.48)	0.80	7623.2	10220.00
1	2227.13	69.54	0.373	0.60( 0.48)	0.80	9875.1	13830.00
1	2195.72	72.12	0.368	0.60( 0.48)	0.80	10387.5	10500.00
1	1982.31	86.61	0.342	0.60( 0.48)	0.81	13284.1	150.00
1	1705.28	108.65	0.301	0.60( 0.50)	0.83	17485.2	10100.00
1	1621.82	127.52	0.273	0.60( 0.51)	0.85	21542.8	13600.00
1	1557.42	158.17	0.246	0.60( 0.52)	0.87	27408.2	11831.00
1	1589.49	181.59	0.226	0.60( 0.53)	0.89	31961.2	11530.00
1	1619.74	201.01	0.219	0.60( 0.54)	0.90	36332.1	11000.00
1	1677.03	223.07	0.213	0.60( 0.55)	0.91	43383.7	10850.00
1	1576.37	239.33	0.208	0.60( 0.55)	0.92	46877.6	11220.00
1	1317.03	293.17	0.191	0.60( 0.56)	0.93	55274.3	12410.00
1	1248.83	326.75	0.180	0.60( 0.56)	0.94	61360.2	12261.00

1	1224.93	339.73	0.176	0.60	( 0.56)	0.94	62846.8	10410.00
1	1201.65	352.14	0.172	0.60	( 0.56)	0.94	63948.8	12101.10
1	1149.42	380.16	0.168	0.60	( 0.56)	0.94	66326.9	10200.00
1	1124.30	393.82	0.166	0.60	( 0.56)	0.94	67265.1	12010.00
1	1068.70	423.58	0.163	0.60	( 0.56)	0.94	67938.8	10210.00
1	994.35	473.68	0.158	0.60	( 0.57)	0.94	68437.9	12000.00
1	934.30	544.06	0.150	0.60	( 0.57)	0.94	69022.6	10100.00
2	17.62	19.29	0.783	0.60	( 0.56)	0.94	79.6	13889.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2521.00	19.29	0.783	0.60	( 0.49)	0.81	1921.2 13889.00
2	2506.84	28.51	0.606	0.60	( 0.49)	0.81	2801.3 10520.00
3	2472.00	35.54	0.539	0.60	( 0.48)	0.81	4003.0 13810.00
4	2455.59	39.22	0.509	0.60	( 0.48)	0.81	4610.3 13850.00
5	2422.89	46.15	0.468	0.60	( 0.48)	0.80	5730.6 13870.00
6	2361.15	58.71	0.397	0.60	( 0.48)	0.80	7702.9 10220.00
7	2228.98	69.54	0.373	0.60	( 0.48)	0.80	9954.7 13830.00
8	2197.55	72.12	0.368	0.60	( 0.48)	0.80	10467.2 10500.00
9	1984.01	86.61	0.342	0.60	( 0.48)	0.81	13363.7 150.00
10	1706.78	108.65	0.301	0.60	( 0.50)	0.83	17564.8 10100.00
11	1623.17	127.52	0.273	0.60	( 0.51)	0.85	21622.4 13600.00
12	1558.64	158.17	0.246	0.60	( 0.52)	0.87	27487.8 11831.00
13	1590.61	181.59	0.226	0.60	( 0.53)	0.89	32040.8 11530.00
14	1620.83	201.01	0.219	0.60	( 0.54)	0.90	36411.7 11000.00
15	1678.09	223.07	0.213	0.60	( 0.55)	0.91	43463.3 10850.00
16	1577.40	239.33	0.208	0.60	( 0.55)	0.92	46957.3 11220.00
17	1317.98	293.17	0.191	0.60	( 0.56)	0.93	55354.0 12410.00
18	1249.72	326.75	0.180	0.60	( 0.56)	0.94	61439.9 12261.00
19	1225.81	339.73	0.176	0.60	( 0.56)	0.94	62926.5 10410.00
20	1202.51	352.14	0.172	0.60	( 0.56)	0.94	64028.4 12101.10
21	1150.25	380.16	0.168	0.60	( 0.56)	0.94	66406.5 10200.00
22	1125.13	393.82	0.166	0.60	( 0.56)	0.94	67344.7 12010.00
23	1069.51	423.58	0.163	0.60	( 0.56)	0.94	68018.4 10210.00
24	995.13	473.68	0.158	0.60	( 0.57)	0.94	68517.5 12000.00
25	935.05	544.06	0.150	0.60	( 0.57)	0.94	69102.3 10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 2521.00 Tc(MIN.) = 19.29  
EFFECTIVE AREA(ACRES) = 1921.24 AREA-AVERAGED Fm(INCH/HR) = 0.49  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.81  
TOTAL AREA(ACRES) = 69102.3  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13910.00 = 135262.70 FEET.

=====

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 69102.3 TC(MIN.) = 19.29  
EFFECTIVE AREA(ACRES) = 1921.24 AREA-AVERAGED Fm(INCH/HR)= 0.49  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.811  
PEAK FLOW RATE(CFS) = 2521.00

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2521.00	19.29	0.783	0.60	( 0.49)	0.81	1921.2 13889.00

2	2506.84	28.51	0.606	0.60	( 0.49)	0.81	2801.3	10520.00
3	2472.00	35.54	0.539	0.60	( 0.48)	0.81	4003.0	13810.00
4	2455.59	39.22	0.509	0.60	( 0.48)	0.81	4610.3	13850.00
5	2422.89	46.15	0.468	0.60	( 0.48)	0.80	5730.6	13870.00
6	2361.15	58.71	0.397	0.60	( 0.48)	0.80	7702.9	10220.00
7	2228.98	69.54	0.373	0.60	( 0.48)	0.80	9954.7	13830.00
8	2197.55	72.12	0.368	0.60	( 0.48)	0.80	10467.2	10500.00
9	1984.01	86.61	0.342	0.60	( 0.48)	0.81	13363.7	150.00
10	1706.78	108.65	0.301	0.60	( 0.50)	0.83	17564.8	10100.00
11	1623.17	127.52	0.273	0.60	( 0.51)	0.85	21622.4	13600.00
12	1558.64	158.17	0.246	0.60	( 0.52)	0.87	27487.8	11831.00
13	1590.61	181.59	0.226	0.60	( 0.53)	0.89	32040.8	11530.00
14	1620.83	201.01	0.219	0.60	( 0.54)	0.90	36411.7	11000.00
15	1678.09	223.07	0.213	0.60	( 0.55)	0.91	43463.3	10850.00
16	1577.40	239.33	0.208	0.60	( 0.55)	0.92	46957.3	11220.00
17	1317.98	293.17	0.191	0.60	( 0.56)	0.93	55354.0	12410.00
18	1249.72	326.75	0.180	0.60	( 0.56)	0.94	61439.9	12261.00
19	1225.81	339.73	0.176	0.60	( 0.56)	0.94	62926.5	10410.00
20	1202.51	352.14	0.172	0.60	( 0.56)	0.94	64028.4	12101.10
21	1150.25	380.16	0.168	0.60	( 0.56)	0.94	66406.5	10200.00
22	1125.13	393.82	0.166	0.60	( 0.56)	0.94	67344.7	12010.00
23	1069.51	423.58	0.163	0.60	( 0.56)	0.94	68018.4	10210.00
24	995.13	473.68	0.158	0.60	( 0.57)	0.94	68517.5	12000.00
25	935.05	544.06	0.150	0.60	( 0.57)	0.94	69102.3	10100.00

=====

END OF RATIONAL METHOD ANALYSIS

=====



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA 92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S39- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 2-YR RM EV APRIL 2019 ROKAMOTO \*  
\*\*\*\*\*

FILE NAME: RI02EV39.DAT  
TIME/DATE OF STUDY: 17:08 04/08/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 2.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 1.797
- 2) 10.00; 1.198
- 3) 15.00; 0.921
- 4) 20.00; 0.760
- 5) 25.00; 0.658
- 6) 30.00; 0.584
- 7) 40.00; 0.503
- 8) 50.00; 0.446
- 9) 60.00; 0.390
- 10) 90.00; 0.336
- 11) 120.00; 0.280
- 12) 180.00; 0.226
- 13) 360.00; 0.166
- 14) 1200.00; 0.080

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL: IN- / OUT- /PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:

- 1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13900.00 TO NODE 13901.00 IS CODE = 21  
-----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 600.65  
ELEVATION DATA: UPSTREAM(FEET) = 442.40 DOWNSTREAM(FEET) = 385.16

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 10.859  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 1.150  
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
AGRICULTURAL POOR COVER "FALLOW"	-	4.00	0.60	1.000	0	10.86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA RUNOFF(CFS) = 1.98  
TOTAL AREA(ACRES) = 4.00 PEAK FLOW RATE(CFS) = 1.98

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13901.00 TO NODE 13902.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 385.16 DOWNSTREAM(FEET) = 288.21  
CHANNEL LENGTH THRU SUBAREA(FEET) = 647.42 CHANNEL SLOPE = 0.1497  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 1.039  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.47	0.60	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3.66  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.35  
AVERAGE FLOW DEPTH(FEET) = 0.48 TRAVEL TIME(MIN.) = 2.02  
Tc(MIN.) = 12.88  
SUBAREA AREA(ACRES) = 8.47 SUBAREA RUNOFF(CFS) = 3.35  
EFFECTIVE AREA(ACRES) = 12.47 AREA-AVERAGED Fm(INCH/HR) = 0.60  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 12.5 PEAK FLOW RATE(CFS) = 4.92

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.54 FLOW VELOCITY(FEET/SEC.) = 5.69  
LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13902.00 = 1248.07 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13902.00 TO NODE 13903.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 288.21 DOWNSTREAM(FEET) = 184.89
CHANNEL LENGTH THRU SUBAREA(FEET) = 669.27 CHANNEL SLOPE = 0.1544
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.947
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 23.85 0.60 0.982 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.982
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 8.78
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.74
AVERAGE FLOW DEPTH(FEET) = 0.66 TRAVEL TIME(MIN.) = 1.65
Tc(MIN.) = 14.53
SUBAREA AREA(ACRES) = 23.85 SUBAREA RUNOFF(CFS) = 7.68
EFFECTIVE AREA(ACRES) = 36.32 AREA-AVERAGED Fm(INCH/HR) = 0.59
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 36.3 PEAK FLOW RATE(CFS) = 11.58

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.73 FLOW VELOCITY(FEET/SEC.) = 7.25
LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13903.00 = 1917.34 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 13903.00 TO NODE 13904.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 184.89 DOWNSTREAM(FEET) = 155.08
FLOW LENGTH(FEET) = 876.66 MANNING'S N = 0.013
ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000
DEPTH OF FLOW IN 36.0 INCH PIPE IS 7.7 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 10.53
ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 11.58
PIPE TRAVEL TIME(MIN.) = 1.39 Tc(MIN.) = 15.92
LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13904.00 = 2794.00 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 13903.00 TO NODE 13904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 15.92
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.891
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 21.29 0.60 0.996 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.996

SUBAREA AREA(ACRES) = 21.29 SUBAREA RUNOFF(CFS) = 5.63
EFFECTIVE AREA(ACRES) = 57.61 AREA-AVERAGED Fm(INCH/HR) = 0.59
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 57.6 PEAK FLOW RATE(CFS) = 15.40

\*\*\*\*\*
FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 155.08 DOWNSTREAM(FEET) = 118.00
FLOW LENGTH(FEET) = 1961.38 MANNING'S N = 0.013
ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000
DEPTH OF FLOW IN 36.0 INCH PIPE IS 10.3 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 9.28
ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 15.40
PIPE TRAVEL TIME(MIN.) = 3.52 Tc(MIN.) = 19.44
LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13920.00 = 4755.38 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 19.44
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.778
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 43.53 0.60 0.649 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.649
SUBAREA AREA(ACRES) = 43.53 SUBAREA RUNOFF(CFS) = 15.23
EFFECTIVE AREA(ACRES) = 101.14 AREA-AVERAGED Fm(INCH/HR) = 0.51
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.84
TOTAL AREA(ACRES) = 101.1 PEAK FLOW RATE(CFS) = 24.74

\*\*\*\*\*
FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<

\*\*\*\*\*
FLOW PROCESS FROM NODE 13910.00 TO NODE 13910.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: RI02EV38.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:
STREAM Q Tc Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (ACRES) NODE
1 2521.00 19.29 0.60( 0.49) 0.81 1921.2 13889.00
2 2422.89 46.15 0.60( 0.48) 0.80 5730.6 13870.00
3 2361.15 58.71 0.60( 0.48) 0.80 7702.9 10220.00
4 1984.01 86.61 0.60( 0.48) 0.81 13363.7 150.00



5	1706.78	108.65	0.60	( 0.50)	0.83	17564.8	10100.00
6	1623.17	127.52	0.60	( 0.51)	0.85	21622.4	13600.00
7	1558.64	158.17	0.60	( 0.52)	0.87	27487.8	11831.00
8	1590.61	181.59	0.60	( 0.53)	0.89	32040.8	11530.00
9	1620.83	201.01	0.60	( 0.54)	0.90	36411.7	11000.00
10	1678.09	223.07	0.60	( 0.55)	0.91	43463.3	10850.00
11	1577.40	239.33	0.60	( 0.55)	0.92	46957.3	11220.00
12	1317.98	293.17	0.60	( 0.56)	0.93	55354.0	12410.00
13	1249.72	326.75	0.60	( 0.56)	0.94	61439.9	12261.00
14	1225.81	339.73	0.60	( 0.56)	0.94	62926.5	10410.00
15	1202.51	352.14	0.60	( 0.56)	0.94	64028.4	12101.10
16	1150.25	380.16	0.60	( 0.56)	0.94	66406.5	10200.00
17	1125.13	393.82	0.60	( 0.56)	0.94	67344.7	12010.00
18	1069.51	423.58	0.60	( 0.56)	0.94	68018.4	10210.00
19	995.13	473.68	0.60	( 0.57)	0.94	68517.5	12000.00
20	935.05	544.06	0.60	( 0.57)	0.94	69102.3	10100.00

TOTAL AREA (ACRES) = 69102.3

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13910.00 TO NODE 13910.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<<  
=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2521.00	19.29	0.60 ( 0.49)	0.81	1921.2	13889.00
2	2422.89	46.15	0.60 ( 0.48)	0.80	5730.6	13870.00
3	2361.15	58.71	0.60 ( 0.48)	0.80	7702.9	10220.00
4	1984.01	86.61	0.60 ( 0.48)	0.81	13363.7	150.00
5	1706.78	108.65	0.60 ( 0.50)	0.83	17564.8	10100.00
6	1623.17	127.52	0.60 ( 0.51)	0.85	21622.4	13600.00
7	1558.64	158.17	0.60 ( 0.52)	0.87	27487.8	11831.00
8	1590.61	181.59	0.60 ( 0.53)	0.89	32040.8	11530.00
9	1620.83	201.01	0.60 ( 0.54)	0.90	36411.7	11000.00
10	1678.09	223.07	0.60 ( 0.55)	0.91	43463.3	10850.00
11	1577.40	239.33	0.60 ( 0.55)	0.92	46957.3	11220.00
12	1317.98	293.17	0.60 ( 0.56)	0.93	55354.0	12410.00
13	1249.72	326.75	0.60 ( 0.56)	0.94	61439.9	12261.00
14	1225.81	339.73	0.60 ( 0.56)	0.94	62926.5	10410.00
15	1202.51	352.14	0.60 ( 0.56)	0.94	64028.4	12101.10
16	1150.25	380.16	0.60 ( 0.56)	0.94	66406.5	10200.00
17	1125.13	393.82	0.60 ( 0.56)	0.94	67344.7	12010.00
18	1069.51	423.58	0.60 ( 0.56)	0.94	68018.4	10210.00
19	995.13	473.68	0.60 ( 0.57)	0.94	68517.5	12000.00
20	935.05	544.06	0.60 ( 0.57)	0.94	69102.3	10100.00

TOTAL AREA (ACRES) = 69102.3

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13910.00 TO NODE 13920.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<<  
=====

ELEVATION DATA: UPSTREAM(FEET) = 119.70 DOWNSTREAM(FEET) = 118.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1376.26 CHANNEL SLOPE = 0.0012  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
\* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.691  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCSSOIL AREA Fp Ap SCSS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 96.09 0.60 0.535 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.535  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2537.03  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.63  
AVERAGE FLOW DEPTH(FEET) = 12.26 TRAVEL TIME(MIN.) = 4.08  
Tc(MIN.) = 23.37  
SUBAREA AREA(ACRES) = 96.09 SUBAREA RUNOFF(CFS) = 32.03  
EFFECTIVE AREA(ACRES) = 2017.33 AREA-AVERAGED Fm(INCH/HR) = 0.48  
AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.80  
TOTAL AREA(ACRES) = 69198.4 PEAK FLOW RATE(CFS) = 2521.00  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 12.23 FLOW VELOCITY(FEET/SEC.) = 5.62  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136638.97 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2521.00	23.37	0.691	0.60 ( 0.48)	0.80	2017.3	13889.00
2	2422.89	50.27	0.444	0.60 ( 0.48)	0.80	5826.6	13870.00
3	2361.15	62.86	0.385	0.60 ( 0.48)	0.80	7798.9	10220.00
4	1984.01	90.94	0.334	0.60 ( 0.48)	0.81	13459.8	150.00
5	1706.78	113.15	0.293	0.60 ( 0.50)	0.83	17660.9	10100.00
6	1623.17	132.07	0.269	0.60 ( 0.51)	0.85	21718.5	13600.00
7	1558.64	162.77	0.242	0.60 ( 0.52)	0.87	27583.9	11831.00
8	1590.61	186.17	0.224	0.60 ( 0.53)	0.88	32136.9	11530.00
9	1620.83	205.57	0.217	0.60 ( 0.54)	0.90	36507.8	11000.00
10	1678.09	227.59	0.210	0.60 ( 0.55)	0.91	43559.4	10850.00
11	1577.40	243.91	0.205	0.60 ( 0.55)	0.92	47053.4	11220.00
12	1317.98	297.97	0.187	0.60 ( 0.56)	0.93	55450.1	12410.00
13	1249.72	331.61	0.175	0.60 ( 0.56)	0.93	61535.9	12261.00
14	1225.81	344.62	0.171	0.60 ( 0.56)	0.94	63022.6	10410.00
15	1202.51	357.05	0.167	0.60 ( 0.56)	0.94	64124.5	12101.10
16	1150.25	385.12	0.163	0.60 ( 0.56)	0.94	66502.6	10200.00
17	1125.13	398.81	0.162	0.60 ( 0.56)	0.94	67440.8	12010.00
18	1069.51	428.64	0.159	0.60 ( 0.56)	0.94	68114.5	10210.00
19	995.13	478.83	0.154	0.60 ( 0.56)	0.94	68613.6	12000.00
20	935.05	549.29	0.147	0.60 ( 0.57)	0.94	69198.4	10100.00

NEW PEAK FLOW DATA ARE:  
PEAK FLOW RATE(CFS) = 2521.00 Tc(MIN.) = 23.37  
AREA-AVERAGED Fm(INCH/HR) = 0.48 AREA-AVERAGED Fp(INCH/HR) = 0.60  
AREA-AVERAGED Ap = 0.80 EFFECTIVE AREA(ACRES) = 2017.33

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<<  
=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	--------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	2521.00	23.37	0.691	0.60 ( 0.48)	0.80	2017.3 13889.00
2	2422.89	50.27	0.444	0.60 ( 0.48)	0.80	5826.6 13870.00
3	2361.15	62.86	0.385	0.60 ( 0.48)	0.80	7798.9 10220.00
4	1984.01	90.94	0.334	0.60 ( 0.48)	0.81	13459.8 150.00
5	1706.78	113.15	0.293	0.60 ( 0.50)	0.83	17660.9 10100.00
6	1623.17	132.07	0.269	0.60 ( 0.51)	0.85	21718.5 13600.00
7	1558.64	162.77	0.242	0.60 ( 0.52)	0.87	27583.9 11831.00
8	1590.61	186.17	0.224	0.60 ( 0.53)	0.88	32136.9 11530.00
9	1620.83	205.57	0.217	0.60 ( 0.54)	0.90	36507.8 11000.00
10	1678.09	227.59	0.210	0.60 ( 0.55)	0.91	43559.4 10850.00
11	1577.40	243.91	0.205	0.60 ( 0.55)	0.92	47053.4 11220.00
12	1317.98	297.97	0.187	0.60 ( 0.56)	0.93	55450.1 12410.00
13	1249.72	331.61	0.175	0.60 ( 0.56)	0.93	61535.9 12261.00
14	1225.81	344.62	0.171	0.60 ( 0.56)	0.94	63022.6 10410.00
15	1202.51	357.05	0.167	0.60 ( 0.56)	0.94	64124.5 12101.10
16	1150.25	385.12	0.163	0.60 ( 0.56)	0.94	66502.6 10200.00
17	1125.13	398.81	0.162	0.60 ( 0.56)	0.94	67440.8 12010.00
18	1069.51	428.64	0.159	0.60 ( 0.56)	0.94	68114.5 10210.00
19	995.13	478.83	0.154	0.60 ( 0.56)	0.94	68613.6 12000.00
20	935.05	549.29	0.147	0.60 ( 0.57)	0.94	69198.4 10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136638.97 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24.74	19.44	0.778	0.60 ( 0.51)	0.84	101.1	13900.00

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13920.00 = 4755.38 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2545.74	19.44	0.778	0.60 ( 0.48)	0.80	1779.4	13900.00
2	2537.84	23.37	0.691	0.60 ( 0.48)	0.80	2118.5	13889.00
3	2429.21	50.27	0.444	0.60 ( 0.48)	0.80	5927.8	13870.00
4	2366.62	62.86	0.385	0.60 ( 0.48)	0.80	7900.1	10220.00
5	1988.76	90.94	0.334	0.60 ( 0.48)	0.81	13561.0	150.00
6	1710.94	113.15	0.293	0.60 ( 0.50)	0.83	17762.1	10100.00
7	1627.00	132.07	0.269	0.60 ( 0.51)	0.85	21819.6	13600.00
8	1562.07	162.77	0.242	0.60 ( 0.52)	0.87	27685.0	11831.00
9	1593.79	186.17	0.224	0.60 ( 0.53)	0.88	32238.0	11530.00
10	1623.92	205.57	0.217	0.60 ( 0.54)	0.90	36609.0	11000.00
11	1681.07	227.59	0.210	0.60 ( 0.55)	0.91	43660.6	10850.00
12	1580.31	243.91	0.205	0.60 ( 0.55)	0.92	47154.5	11220.00
13	1320.63	297.97	0.187	0.60 ( 0.56)	0.93	55551.2	12410.00
14	1252.21	331.61	0.175	0.60 ( 0.56)	0.93	61637.1	12261.00
15	1228.24	344.62	0.171	0.60 ( 0.56)	0.94	63123.7	10410.00
16	1204.88	357.05	0.167	0.60 ( 0.56)	0.94	64225.6	12101.10
17	1152.57	385.12	0.163	0.60 ( 0.56)	0.94	66603.7	10200.00
18	1127.43	398.81	0.162	0.60 ( 0.56)	0.94	67542.0	12010.00
19	1071.77	428.64	0.159	0.60 ( 0.56)	0.94	68215.7	10210.00
20	997.32	478.83	0.154	0.60 ( 0.56)	0.94	68714.7	12000.00
21	937.13	549.29	0.147	0.60 ( 0.56)	0.94	69299.5	10100.00

TOTAL AREA (ACRES) = 69299.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 2545.74 Tc (MIN.) = 19.440  
EFFECTIVE AREA (ACRES) = 1779.39 AREA-AVERAGED Fm (INCH/HR) = 0.48

AREA-AVERAGED Fp (INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.94  
TOTAL AREA (ACRES) = 69299.5  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136638.97 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13920.00 TO NODE 13921.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 118.00 DOWNSTREAM (FEET) = 115.28

CHANNEL LENGTH THRU SUBAREA (FEET) = 335.44 CHANNEL SLOPE = 0.0081

CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00

\* 2 YEAR RAINFALL INTENSITY (INCH/HR) = 0.762

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	134.30	0.60	0.658	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.60

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.658

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 2567.96

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 11.43

AVERAGE FLOW DEPTH (FEET) = 8.65 TRAVEL TIME (MIN.) = 0.49

Tc (MIN.) = 19.93

SUBAREA AREA (ACRES) = 134.30

SUBAREA RUNOFF (CFS) = 44.43

EFFECTIVE AREA (ACRES) = 1913.69

AREA-AVERAGED Fm (INCH/HR) = 0.47

AREA-AVERAGED Fp (INCH/HR) = 0.60

AREA-AVERAGED Ap = 0.79

TOTAL AREA (ACRES) = 69433.8

PEAK FLOW RATE (CFS) = 2545.74

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 8.62 FLOW VELOCITY (FEET/SEC.) = 11.41

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13921.00 = 136974.41 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2545.74	19.93	0.762	0.60 ( 0.47)	0.79	1913.7	13900.00
2	2537.84	23.86	0.681	0.60 ( 0.47)	0.79	2252.8	13889.00
3	2429.21	50.76	0.442	0.60 ( 0.48)	0.80	6062.1	13870.00
4	2366.62	63.36	0.384	0.60 ( 0.48)	0.80	8034.4	10220.00
5	1988.76	91.46	0.333	0.60 ( 0.48)	0.81	13695.3	150.00
6	1710.94	113.69	0.292	0.60 ( 0.50)	0.83	17896.4	10100.00
7	1627.00	132.62	0.269	0.60 ( 0.51)	0.85	21953.9	13600.00
8	1562.07	163.32	0.241	0.60 ( 0.52)	0.87	27819.3	11831.00
9	1593.79	186.72	0.224	0.60 ( 0.53)	0.88	32372.3	11530.00
10	1623.92	206.12	0.217	0.60 ( 0.54)	0.90	36743.3	11000.00
11	1681.07	228.13	0.210	0.60 ( 0.55)	0.91	43794.9	10850.00
12	1580.31	244.46	0.205	0.60 ( 0.55)	0.92	47288.8	11220.00
13	1320.63	298.55	0.186	0.60 ( 0.56)	0.93	55685.5	12410.00
14	1252.21	332.19	0.175	0.60 ( 0.56)	0.93	61771.4	12261.00
15	1228.24	345.21	0.171	0.60 ( 0.56)	0.94	63258.0	10410.00
16	1204.88	357.64	0.167	0.60 ( 0.56)	0.94	64359.9	12101.10
17	1152.57	385.72	0.163	0.60 ( 0.56)	0.94	66738.0	10200.00
18	1127.43	399.41	0.162	0.60 ( 0.56)	0.94	67676.2	12010.00
19	1071.77	429.25	0.159	0.60 ( 0.56)	0.94	68350.0	10210.00
20	997.32	479.45	0.154	0.60 ( 0.56)	0.94	68849.0	12000.00

21 937.13 549.91 0.147 0.60( 0.56) 0.94 69433.8 10100.00  
 NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE(CFS) = 2545.74 Tc(MIN.) = 19.93  
 AREA-AVERAGED Fm(INCH/HR) = 0.47 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.79 EFFECTIVE AREA(ACRES) = 1913.69

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13921.00 TO NODE 14010.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 115.28 DOWNSTREAM(FEET) = 100.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1396.08 CHANNEL SLOPE = 0.0109  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
 \* 2 YEAR RAINFALL INTENSITY(INCH/HR) = 0.724  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 96.27 0.60 0.723 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.60  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.723  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2558.34  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.78  
 AVERAGE FLOW DEPTH(FEET) = 8.17 TRAVEL TIME(MIN.) = 1.82  
 Tc(MIN.) = 21.75  
 SUBAREA AREA(ACRES) = 96.27 SUBAREA RUNOFF(CFS) = 25.18  
 EFFECTIVE AREA(ACRES) = 2009.96 AREA-AVERAGED Fm(INCH/HR) = 0.47  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA(ACRES) = 69530.1 PEAK FLOW RATE(CFS) = 2545.74  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 8.15 FLOW VELOCITY(FEET/SEC.) = 12.77  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 14010.00 = 138370.48 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2545.74	21.75	0.724	0.60( 0.47)	0.79	2010.0	13900.00
2	2537.84	25.68	0.648	0.60( 0.47)	0.79	2349.0	13889.00
3	2429.21	52.61	0.431	0.60( 0.48)	0.80	6158.4	13870.00
4	2366.62	65.21	0.381	0.60( 0.48)	0.80	8130.7	10220.00
5	1988.76	93.40	0.330	0.60( 0.48)	0.80	13791.5	150.00
6	1710.94	115.70	0.288	0.60( 0.50)	0.83	17992.6	10100.00
7	1627.00	134.66	0.267	0.60( 0.51)	0.85	22050.2	13600.00
8	1562.07	165.38	0.239	0.60( 0.52)	0.87	27915.6	11831.00
9	1593.79	188.77	0.223	0.60( 0.53)	0.88	32468.6	11530.00
10	1623.92	208.15	0.217	0.60( 0.54)	0.90	36839.5	11000.00
11	1681.07	230.16	0.209	0.60( 0.55)	0.91	43891.1	10850.00
12	1580.31	246.52	0.204	0.60( 0.55)	0.92	47385.1	11220.00
13	1320.63	300.69	0.186	0.60( 0.56)	0.93	55781.8	12410.00
14	1252.21	334.37	0.175	0.60( 0.56)	0.93	61867.7	12261.00
15	1228.24	347.39	0.170	0.60( 0.56)	0.94	63354.3	10410.00
16	1204.88	359.84	0.166	0.60( 0.56)	0.94	64456.2	12101.10
17	1152.57	387.94	0.163	0.60( 0.56)	0.94	66834.3	10200.00
18	1127.43	401.65	0.162	0.60( 0.56)	0.94	67772.5	12010.00
19	1071.77	431.51	0.159	0.60( 0.56)	0.94	68446.2	10210.00
20	997.32	481.75	0.154	0.60( 0.56)	0.94	68945.3	12000.00
21	937.13	552.25	0.146	0.60( 0.56)	0.94	69530.1	10100.00

19 1071.77 431.51 0.159 0.60( 0.56) 0.94 68446.2 10210.00  
 20 997.32 481.75 0.154 0.60( 0.56) 0.94 68945.3 12000.00  
 21 937.13 552.25 0.146 0.60( 0.56) 0.94 69530.1 10100.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE(CFS) = 2545.74 Tc(MIN.) = 21.75  
 AREA-AVERAGED Fm(INCH/HR) = 0.47 AREA-AVERAGED Fp(INCH/HR) = 0.60  
 AREA-AVERAGED Ap = 0.79 EFFECTIVE AREA(ACRES) = 2009.96

=====

END OF STUDY SUMMARY:  
 TOTAL AREA(ACRES) = 69530.1 TC(MIN.) = 21.75  
 EFFECTIVE AREA(ACRES) = 2009.96 AREA-AVERAGED Fm(INCH/HR) = 0.47  
 AREA-AVERAGED Fp(INCH/HR) = 0.60 AREA-AVERAGED Ap = 0.787  
 PEAK FLOW RATE(CFS) = 2545.74

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2545.74	21.75	0.724	0.60( 0.47)	0.79	2010.0	13900.00
2	2537.84	25.68	0.648	0.60( 0.47)	0.79	2349.0	13889.00
3	2429.21	52.61	0.431	0.60( 0.48)	0.80	6158.4	13870.00
4	2366.62	65.21	0.381	0.60( 0.48)	0.80	8130.7	10220.00
5	1988.76	93.40	0.330	0.60( 0.48)	0.80	13791.5	150.00
6	1710.94	115.70	0.288	0.60( 0.50)	0.83	17992.6	10100.00
7	1627.00	134.66	0.267	0.60( 0.51)	0.85	22050.2	13600.00
8	1562.07	165.38	0.239	0.60( 0.52)	0.87	27915.6	11831.00
9	1593.79	188.77	0.223	0.60( 0.53)	0.88	32468.6	11530.00
10	1623.92	208.15	0.217	0.60( 0.54)	0.90	36839.5	11000.00
11	1681.07	230.16	0.209	0.60( 0.55)	0.91	43891.1	10850.00
12	1580.31	246.52	0.204	0.60( 0.55)	0.92	47385.1	11220.00
13	1320.63	300.69	0.186	0.60( 0.56)	0.93	55781.8	12410.00
14	1252.21	334.37	0.175	0.60( 0.56)	0.93	61867.7	12261.00
15	1228.24	347.39	0.170	0.60( 0.56)	0.94	63354.3	10410.00
16	1204.88	359.84	0.166	0.60( 0.56)	0.94	64456.2	12101.10
17	1152.57	387.94	0.163	0.60( 0.56)	0.94	66834.3	10200.00
18	1127.43	401.65	0.162	0.60( 0.56)	0.94	67772.5	12010.00
19	1071.77	431.51	0.159	0.60( 0.56)	0.94	68446.2	10210.00
20	997.32	481.75	0.154	0.60( 0.56)	0.94	68945.3	12000.00
21	937.13	552.25	0.146	0.60( 0.56)	0.94	69530.1	10100.00

=====

END OF RATIONAL METHOD ANALYSIS



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA 92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S19- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 5-YR RM EV APRIL 2019 ROKAMOTO \*  
\*\*\*\*\*

FILE NAME: RI05EV19.DAT  
TIME/DATE OF STUDY: 17:17 04/08/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 5.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 2.749
- 2) 10.00; 1.820
- 3) 15.00; 1.328
- 4) 20.00; 1.137
- 5) 25.00; 0.990
- 6) 30.00; 0.887
- 7) 40.00; 0.760
- 8) 50.00; 0.677
- 9) 60.00; 0.617
- 10) 90.00; 0.514
- 11) 120.00; 0.456
- 12) 180.00; 0.384
- 13) 360.00; 0.286
- 14) 1200.00; 0.126

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT-/PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	HIKE LIP (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:

- 1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11900.00 TO NODE 11901.00 IS CODE = 21  
-----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 295.79  
ELEVATION DATA: UPSTREAM(FEET) = 2369.48 DOWNSTREAM(FEET) = 2332.92

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 7.203  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 2.340  
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
RESIDENTIAL ".4 DWELLING/ACRE"	-	1.62	0.50	0.999	0	7.20

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999  
SUBAREA RUNOFF(CFS) = 2.68  
TOTAL AREA(ACRES) = 1.62 PEAK FLOW RATE(CFS) = 2.68

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11901.00 TO NODE 11902.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2332.92 DOWNSTREAM(FEET) = 2297.70  
CHANNEL LENGTH THRU SUBAREA(FEET) = 664.26 CHANNEL SLOPE = 0.0530  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.757  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.35	0.50	0.906	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.906  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 7.64  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.22  
AVERAGE FLOW DEPTH(FEET) = 0.89 TRAVEL TIME(MIN.) = 3.44  
Tc(MIN.) = 10.64  
SUBAREA AREA(ACRES) = 8.35 SUBAREA RUNOFF(CFS) = 9.80  
EFFECTIVE AREA(ACRES) = 9.97 AREA-AVERAGED Fm(INCH/HR) = 0.46  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.92  
TOTAL AREA(ACRES) = 10.0 PEAK FLOW RATE(CFS) = 11.63

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 1.04 FLOW VELOCITY(FEET/SEC.) = 3.57  
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11902.00 = 960.05 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11902.00 TO NODE 11902.50 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2297.70 DOWNSTREAM(FEET) = 2263.40  
CHANNEL LENGTH THRU SUBAREA(FEET) = 928.77 CHANNEL SLOPE = 0.0369  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.356  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 34.48 0.50 0.904 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.904  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 25.95  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.80  
AVERAGE FLOW DEPTH(FEET) = 1.51 TRAVEL TIME(MIN.) = 4.07  
Tc(MIN.) = 14.71  
SUBAREA AREA(ACRES) = 34.48 SUBAREA RUNOFF(CFS) = 28.06  
EFFECTIVE AREA(ACRES) = 44.45 AREA-AVERAGED Fm(INCH/HR) = 0.45  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.91  
TOTAL AREA(ACRES) = 44.5 PEAK FLOW RATE(CFS) = 36.10

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 1.71 FLOW VELOCITY(FEET/SEC.) = 4.13  
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11902.50 = 1888.82 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11902.50 TO NODE 11903.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2263.40 DOWNSTREAM(FEET) = 2252.14  
CHANNEL LENGTH THRU SUBAREA(FEET) = 895.50 CHANNEL SLOPE = 0.0126  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.142  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 23.65 0.50 0.958 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.958  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 43.17  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 2.89  
AVERAGE FLOW DEPTH(FEET) = 2.23 TRAVEL TIME(MIN.) = 5.17  
Tc(MIN.) = 19.88  
SUBAREA AREA(ACRES) = 23.65 SUBAREA RUNOFF(CFS) = 14.10  
EFFECTIVE AREA(ACRES) = 68.10 AREA-AVERAGED Fm(INCH/HR) = 0.46  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.93  
TOTAL AREA(ACRES) = 68.1 PEAK FLOW RATE(CFS) = 41.60

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 2.20 FLOW VELOCITY(FEET/SEC.) = 2.86  
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11903.00 = 2784.32 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11903.00 TO NODE 11904.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2252.14 DOWNSTREAM(FEET) = 2186.04  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1924.35 CHANNEL SLOPE = 0.0343  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.948  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 68.53 0.50 0.961 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.961  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 56.14  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.49  
AVERAGE FLOW DEPTH(FEET) = 2.04 TRAVEL TIME(MIN.) = 7.15  
Tc(MIN.) = 27.03  
SUBAREA AREA(ACRES) = 68.53 SUBAREA RUNOFF(CFS) = 28.84  
EFFECTIVE AREA(ACRES) = 136.63 AREA-AVERAGED Fm(INCH/HR) = 0.47  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.94  
TOTAL AREA(ACRES) = 136.6 PEAK FLOW RATE(CFS) = 58.59

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 2.07 FLOW VELOCITY(FEET/SEC.) = 4.55  
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11904.00 = 4708.67 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11904.00 TO NODE 11905.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2186.04 DOWNSTREAM(FEET) = 1957.34  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1926.87 CHANNEL SLOPE = 0.1187  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.871  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 63.15 0.50 1.000 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 69.14  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.53  
AVERAGE FLOW DEPTH(FEET) = 1.75 TRAVEL TIME(MIN.) = 4.27  
Tc(MIN.) = 31.29  
SUBAREA AREA(ACRES) = 63.15 SUBAREA RUNOFF(CFS) = 21.05  
EFFECTIVE AREA(ACRES) = 199.78 AREA-AVERAGED Fm(INCH/HR) = 0.48  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.96  
TOTAL AREA(ACRES) = 199.8 PEAK FLOW RATE(CFS) = 70.09

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.76 FLOW VELOCITY(FEET/SEC.) = 7.56  
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11905.00 = 6635.54 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11905.00 TO NODE 11906.00 IS CODE = 51

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) =	1957.34	DOWNSTREAM(FEET) =	1244.16
CHANNEL LENGTH THRU SUBAREA(FEET) =	2498.96	CHANNEL SLOPE =	0.2854
CHANNEL BASE(FEET) =	0.00	"Z" FACTOR =	3.000
MANNING'S FACTOR =	0.060	MAXIMUM DEPTH(FEET) =	20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) =	0.822		

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	84.87	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 82.40

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.95

AVERAGE FLOW DEPTH(FEET) = 1.58 TRAVEL TIME(MIN.) = 3.81

Tc(MIN.) = 35.10

SUBAREA AREA(ACRES) = 84.87 SUBAREA RUNOFF(CFS) = 24.60

EFFECTIVE AREA(ACRES) = 284.65 AREA-AVERAGED Fm(INCH/HR) = 0.49

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.97

TOTAL AREA(ACRES) = 284.6 PEAK FLOW RATE(CFS) = 86.00

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.61 FLOW VELOCITY(FEET/SEC.) = 11.02

LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11906.00 = 9134.50 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11906.00 TO NODE 11920.00 IS CODE = 51

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) =	1244.16	DOWNSTREAM(FEET) =	873.95
CHANNEL LENGTH THRU SUBAREA(FEET) =	3370.75	CHANNEL SLOPE =	0.1098
CHANNEL BASE(FEET) =	0.00	"Z" FACTOR =	3.000
MANNING'S FACTOR =	0.060	MAXIMUM DEPTH(FEET) =	20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) =	0.744		

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	199.43	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 107.94

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.20

AVERAGE FLOW DEPTH(FEET) = 2.10 TRAVEL TIME(MIN.) = 6.85

Tc(MIN.) = 41.95

SUBAREA AREA(ACRES) = 199.43 SUBAREA RUNOFF(CFS) = 43.72

EFFECTIVE AREA(ACRES) = 484.08 AREA-AVERAGED Fm(INCH/HR) = 0.49

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.98

TOTAL AREA(ACRES) = 484.1 PEAK FLOW RATE(CFS) = 109.62

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.11 FLOW VELOCITY(FEET/SEC.) = 8.22

LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11920.00 = 12505.25 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11906.00 TO NODE 11920.00 IS CODE = 1

-----  
>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

=====

TOTAL NUMBER OF STREAMS = 2

CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:

TIME OF CONCENTRATION(MIN.) = 41.95

RAINFALL INTENSITY(INCH/HR) = 0.74

AREA-AVERAGED Fm(INCH/HR) = 0.49

AREA-AVERAGED Fp(INCH/HR) = 0.50

AREA-AVERAGED Ap = 0.98

EFFECTIVE STREAM AREA(ACRES) = 484.08

TOTAL STREAM AREA(ACRES) = 484.08

PEAK FLOW RATE(CFS) AT CONFLUENCE = 109.62

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11910.00 TO NODE 11911.00 IS CODE = 21

-----  
>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<

>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 517.62

ELEVATION DATA: UPSTREAM(FEET) = 2531.88 DOWNSTREAM(FEET) = 2441.33

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20

SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 12.185

\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.605

SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	-	3.46	0.50	1.000	0	12.19

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

SUBAREA RUNOFF(CFS) = 3.44

TOTAL AREA(ACRES) = 3.46 PEAK FLOW RATE(CFS) = 3.44

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11911.00 TO NODE 11912.00 IS CODE = 51

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) =	2441.33	DOWNSTREAM(FEET) =	2382.20
CHANNEL LENGTH THRU SUBAREA(FEET) =	397.30	CHANNEL SLOPE =	0.1488
CHANNEL BASE(FEET) =	0.00	"Z" FACTOR =	3.000
MANNING'S FACTOR =	0.060	MAXIMUM DEPTH(FEET) =	20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) =	1.458		

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.79	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 107.94

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.20

AVERAGE FLOW DEPTH(FEET) = 2.10 TRAVEL TIME(MIN.) = 6.85

Tc(MIN.) = 41.95

SUBAREA AREA(ACRES) = 199.43 SUBAREA RUNOFF(CFS) = 43.72

EFFECTIVE AREA(ACRES) = 484.08 AREA-AVERAGED Fm(INCH/HR) = 0.49

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.98

TOTAL AREA(ACRES) = 484.1 PEAK FLOW RATE(CFS) = 109.62

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5.94  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.43  
 AVERAGE FLOW DEPTH(FEET) = 0.67 TRAVEL TIME(MIN.) = 1.49  
 Tc(MIN.) = 13.68  
 SUBAREA AREA(ACRES) = 5.79 SUBAREA RUNOFF(CFS) = 4.99  
 EFFECTIVE AREA(ACRES) = 9.25 AREA-AVERAGED Fm(INCH/HR) = 0.50  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 9.2 PEAK FLOW RATE(CFS) = 7.97

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 0.74 FLOW VELOCITY(FEET/SEC.) = 4.79  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11912.00 = 914.92 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11912.00 TO NODE 11913.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2382.20 DOWNSTREAM(FEET) = 2263.77  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1891.47 CHANNEL SLOPE = 0.0626  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.117

SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	54.30	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 23.41  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.51  
 AVERAGE FLOW DEPTH(FEET) = 1.32 TRAVEL TIME(MIN.) = 6.99  
 Tc(MIN.) = 20.67  
 SUBAREA AREA(ACRES) = 54.30 SUBAREA RUNOFF(CFS) = 30.16  
 EFFECTIVE AREA(ACRES) = 63.55 AREA-AVERAGED Fm(INCH/HR) = 0.50  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 63.5 PEAK FLOW RATE(CFS) = 35.30

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.53 FLOW VELOCITY(FEET/SEC.) = 5.02  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11913.00 = 2806.39 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11913.00 TO NODE 11914.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2263.77 DOWNSTREAM(FEET) = 1845.23  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1957.31 CHANNEL SLOPE = 0.2138  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.006

SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	54.30	0.50	1.000	-

LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
USER-DEFINED	-	65.14	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 50.20  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.64  
 AVERAGE FLOW DEPTH(FEET) = 1.39 TRAVEL TIME(MIN.) = 3.77  
 Tc(MIN.) = 24.44  
 SUBAREA AREA(ACRES) = 65.14 SUBAREA RUNOFF(CFS) = 29.68  
 EFFECTIVE AREA(ACRES) = 128.69 AREA-AVERAGED Fm(INCH/HR) = 0.50  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 128.7 PEAK FLOW RATE(CFS) = 58.63

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.47 FLOW VELOCITY(FEET/SEC.) = 9.05  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11914.00 = 4763.70 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11914.00 TO NODE 11915.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1845.23 DOWNSTREAM(FEET) = 1557.21  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1686.78 CHANNEL SLOPE = 0.1708  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.936

SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	78.52	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 74.04  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.79  
 AVERAGE FLOW DEPTH(FEET) = 1.68 TRAVEL TIME(MIN.) = 3.20  
 Tc(MIN.) = 27.64  
 SUBAREA AREA(ACRES) = 78.52 SUBAREA RUNOFF(CFS) = 30.77  
 EFFECTIVE AREA(ACRES) = 207.21 AREA-AVERAGED Fm(INCH/HR) = 0.50  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 207.2 PEAK FLOW RATE(CFS) = 81.20

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.73 FLOW VELOCITY(FEET/SEC.) = 8.99  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11915.00 = 6450.48 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11915.00 TO NODE 11916.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1557.21 DOWNSTREAM(FEET) = 1403.38  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1909.39 CHANNEL SLOPE = 0.0806  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.859



SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 70.48 0.50 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 92.60  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.99  
 AVERAGE FLOW DEPTH(FEET) = 2.10 TRAVEL TIME(MIN.) = 4.55  
 Tc(MIN.) = 32.19  
 SUBAREA AREA(ACRES) = 70.48 SUBAREA RUNOFF(CFS) = 22.77  
 EFFECTIVE AREA(ACRES) = 277.69 AREA-AVERAGED Fm(INCH/HR) = 0.50  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 277.7 PEAK FLOW RATE(CFS) = 89.72

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 2.07 FLOW VELOCITY(FEET/SEC.) = 6.96  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11916.00 = 8359.87 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11916.00 TO NODE 11917.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 1403.38 DOWNSTREAM(FEET) = 1079.99  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1945.82 CHANNEL SLOPE = 0.1662  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.817  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 232.20 0.50 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 122.90  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.84  
 AVERAGE FLOW DEPTH(FEET) = 2.04 TRAVEL TIME(MIN.) = 3.29  
 Tc(MIN.) = 35.48  
 SUBAREA AREA(ACRES) = 232.20 SUBAREA RUNOFF(CFS) = 66.28  
 EFFECTIVE AREA(ACRES) = 509.89 AREA-AVERAGED Fm(INCH/HR) = 0.50  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 509.9 PEAK FLOW RATE(CFS) = 145.54

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 2.17 FLOW VELOCITY(FEET/SEC.) = 10.29  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11917.00 = 10305.69 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11917.00 TO NODE 11920.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 1079.99 DOWNSTREAM(FEET) = 873.95  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2563.91 CHANNEL SLOPE = 0.0804  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.753  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 110.82 0.50 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 158.17  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.01  
 AVERAGE FLOW DEPTH(FEET) = 2.57 TRAVEL TIME(MIN.) = 5.34  
 Tc(MIN.) = 40.82  
 SUBAREA AREA(ACRES) = 110.82 SUBAREA RUNOFF(CFS) = 25.23  
 EFFECTIVE AREA(ACRES) = 620.71 AREA-AVERAGED Fm(INCH/HR) = 0.50  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 620.7 PEAK FLOW RATE(CFS) = 145.54  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 2.49 FLOW VELOCITY(FEET/SEC.) = 7.82  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11920.00 = 12869.60 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11917.00 TO NODE 11920.00 IS CODE = 1  
 -----

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
 TIME OF CONCENTRATION(MIN.) = 40.82  
 RAINFALL INTENSITY(INCH/HR) = 0.75  
 AREA-AVERAGED Fm(INCH/HR) = 0.50  
 AREA-AVERAGED Fp(INCH/HR) = 0.50  
 AREA-AVERAGED Ap = 1.00  
 EFFECTIVE STREAM AREA(ACRES) = 620.71  
 TOTAL STREAM AREA(ACRES) = 620.71  
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 145.54

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	109.62	41.95	0.744	0.50( 0.49)	0.98	484.1	11900.00
2	145.54	40.82	0.753	0.50( 0.50)	1.00	620.7	11910.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	255.16	40.82	0.753	0.50( 0.50)	0.99	1091.7	11910.00
2	249.76	41.95	0.744	0.50( 0.50)	0.99	1104.8	11900.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:  
 PEAK FLOW RATE(CFS) = 255.16 Tc(MIN.) = 40.82  
 EFFECTIVE AREA(ACRES) = 1091.74 AREA-AVERAGED Fm(INCH/HR) = 0.50  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99

TOTAL AREA (ACRES) = 1104.8  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11920.00 = 12869.60 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11920.00 TO NODE 11921.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 873.95 DOWNSTREAM (FEET) = 827.94  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1417.25 CHANNEL SLOPE = 0.0325  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.723  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	107.47	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 265.93  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.49  
AVERAGE FLOW DEPTH (FEET) = 3.70 TRAVEL TIME (MIN.) = 3.64  
Tc (MIN.) = 44.46  
SUBAREA AREA (ACRES) = 107.47 SUBAREA RUNOFF (CFS) = 21.55  
EFFECTIVE AREA (ACRES) = 1199.21 AREA-AVERAGED Fm (INCH/HR) = 0.50  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 1212.3 PEAK FLOW RATE (CFS) = 255.16  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 3.64 FLOW VELOCITY (FEET/SEC.) = 6.41  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11921.00 = 14286.85 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11921.00 TO NODE 11922.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 827.94 DOWNSTREAM (FEET) = 753.55  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1886.43 CHANNEL SLOPE = 0.0394  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.686  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	344.27	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 284.01  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.10  
AVERAGE FLOW DEPTH (FEET) = 3.65 TRAVEL TIME (MIN.) = 4.43  
Tc (MIN.) = 48.89  
SUBAREA AREA (ACRES) = 344.27 SUBAREA RUNOFF (CFS) = 57.63  
EFFECTIVE AREA (ACRES) = 1543.48 AREA-AVERAGED Fm (INCH/HR) = 0.50  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00

TOTAL AREA (ACRES) = 1556.5 PEAK FLOW RATE (CFS) = 261.80

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 3.54 FLOW VELOCITY (FEET/SEC.) = 6.95  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11922.00 = 16173.28 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11922.00 TO NODE 11923.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 753.55 DOWNSTREAM (FEET) = 641.58  
CHANNEL LENGTH THRU SUBAREA (FEET) = 2860.88 CHANNEL SLOPE = 0.0391  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.643  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	165.18	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 272.40  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.99  
AVERAGE FLOW DEPTH (FEET) = 3.60 TRAVEL TIME (MIN.) = 6.82  
Tc (MIN.) = 55.71  
SUBAREA AREA (ACRES) = 165.18 SUBAREA RUNOFF (CFS) = 21.19  
EFFECTIVE AREA (ACRES) = 1708.66 AREA-AVERAGED Fm (INCH/HR) = 0.50  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
TOTAL AREA (ACRES) = 1721.7 PEAK FLOW RATE (CFS) = 261.80  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 3.55 FLOW VELOCITY (FEET/SEC.) = 6.92  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11923.00 = 19034.16 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11923.00 TO NODE 11924.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 641.58 DOWNSTREAM (FEET) = 579.89  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1844.02 CHANNEL SLOPE = 0.0335  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.616  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	433.73	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 284.41  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.66  
AVERAGE FLOW DEPTH (FEET) = 3.77 TRAVEL TIME (MIN.) = 4.61  
Tc (MIN.) = 60.32

SUBAREA AREA (ACRES) = 433.73 SUBAREA RUNOFF (CFS) = 45.16  
EFFECTIVE AREA (ACRES) = 2142.39 AREA-AVERAGED Fm (INCH/HR) = 0.50  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
TOTAL AREA (ACRES) = 2155.4 PEAK FLOW RATE (CFS) = 261.80  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 3.65 FLOW VELOCITY (FEET/SEC.) = 6.54  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11924.00 = 20878.18 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11924.00 TO NODE 11925.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 579.89 DOWNSTREAM (FEET) = 494.12  
CHANNEL LENGTH THRU SUBAREA (FEET) = 2756.15 CHANNEL SLOPE = 0.0311  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00

\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.591

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	265.42	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 272.70

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.43

AVERAGE FLOW DEPTH (FEET) = 3.76 TRAVEL TIME (MIN.) = 7.14

Tc (MIN.) = 67.46

SUBAREA AREA (ACRES) = 265.42 SUBAREA RUNOFF (CFS) = 21.78

EFFECTIVE AREA (ACRES) = 2407.81 AREA-AVERAGED Fm (INCH/HR) = 0.50

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00

TOTAL AREA (ACRES) = 2420.9 PEAK FLOW RATE (CFS) = 261.80

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 3.70 FLOW VELOCITY (FEET/SEC.) = 6.36

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11925.00 = 23634.33 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11925.00 TO NODE 11926.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 494.12 DOWNSTREAM (FEET) = 458.40  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1922.70 CHANNEL SLOPE = 0.0186  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00

\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.570

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	97.46	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 264.88

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.25

AVERAGE FLOW DEPTH (FEET) = 4.10 TRAVEL TIME (MIN.) = 6.10

Tc (MIN.) = 73.56

SUBAREA AREA (ACRES) = 97.46 SUBAREA RUNOFF (CFS) = 6.16

EFFECTIVE AREA (ACRES) = 2505.27 AREA-AVERAGED Fm (INCH/HR) = 0.50

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00

TOTAL AREA (ACRES) = 2518.3 PEAK FLOW RATE (CFS) = 261.80

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 4.08 FLOW VELOCITY (FEET/SEC.) = 5.25

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11926.00 = 25557.03 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11926.00 TO NODE 11927.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 458.40 DOWNSTREAM (FEET) = 399.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 2710.13 CHANNEL SLOPE = 0.0219  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00

\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.543

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	53.83	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 262.83

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.58

AVERAGE FLOW DEPTH (FEET) = 3.96 TRAVEL TIME (MIN.) = 8.10

Tc (MIN.) = 81.66

SUBAREA AREA (ACRES) = 53.83 SUBAREA RUNOFF (CFS) = 2.06

EFFECTIVE AREA (ACRES) = 2559.10 AREA-AVERAGED Fm (INCH/HR) = 0.50

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00

TOTAL AREA (ACRES) = 2572.1 PEAK FLOW RATE (CFS) = 261.80

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 3.95 FLOW VELOCITY (FEET/SEC.) = 5.58

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 28267.16 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 0610401U.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap (DECIMAL)	Ae (ACRES)	HEADWATER NODE
1	262.60	29.88	0.50 ( 0.50)	1.00	621.9	40120.00
2	252.78	32.04	0.50 ( 0.50)	1.00	652.1	40100.00
TOTAL AREA (ACRES) =						652.1

```

*****
FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 11
-----
>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<
=====
** MAIN STREAM CONFLUENCE DATA **
STREAM      Q      Tc  Intensity  Fp(Fm)    Ap    Ae    HEADWATER
NUMBER     (CFS) (MIN.) (INCH/HR) (INCH/HR)  (ACRES)  NODE
1         261.80  81.66   0.543  0.50( 0.50) 1.00  2559.1  11910.00
2         250.56  83.19   0.537  0.50( 0.50) 1.00  2572.1  11900.00
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 28267.16 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **
STREAM      Q      Tc  Intensity  Fp(Fm)    Ap    Ae    HEADWATER
NUMBER     (CFS) (MIN.) (INCH/HR) (INCH/HR)  (ACRES)  NODE
1         262.60  29.88   0.889  0.50( 0.50) 1.00   621.9  40120.00
2         252.78  32.04   0.861  0.50( 0.50) 1.00   652.1  40100.00
LONGEST FLOWPATH FROM NODE 40100.00 TO NODE 11927.00 = 10245.00 FEET.

** PEAK FLOW RATE TABLE **
STREAM      Q      Tc  Intensity  Fp(Fm)    Ap    Ae    HEADWATER
NUMBER     (CFS) (MIN.) (INCH/HR) (INCH/HR)  (ACRES)  NODE
1         524.39  29.88   0.889  0.50( 0.50) 1.00  1558.4  40120.00
2         514.58  32.04   0.861  0.50( 0.50) 1.00  1656.3  40100.00
3         291.53  81.66   0.543  0.50( 0.50) 1.00  3211.2  11910.00
4         276.61  83.19   0.537  0.50( 0.50) 1.00  3224.2  11900.00
TOTAL AREA(ACRES) = 3224.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
PEAK FLOW RATE(CFS) = 524.39 Tc(MIN.) = 29.883
EFFECTIVE AREA(ACRES) = 1558.43 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 3224.2
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 28267.16 FEET.

*****
FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.50 IS CODE = 51
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 399.00 DOWNSTREAM(FEET) = 384.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 986.26 CHANNEL SLOPE = 0.0152
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
CHANNEL FLOW THRU SUBAREA(CFS) = 524.39
FLOW VELOCITY(FEET/SEC.) = 5.79 FLOW DEPTH(FEET) = 5.50
TRAVEL TIME(MIN.) = 2.84 Tc(MIN.) = 32.72
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.50 = 29253.42 FEET.

*****
FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 12
-----
>>>>CLEAR MEMORY BANK # 1 <<<<
=====
*****

```

```

FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 15.1
-----
>>>>DEFINE MEMORY BANK # 1 <<<<
=====
PEAK FLOWRATE TABLE FILE NAME: 0610402U.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:
STREAM      Q      Tc  Intensity  Fp(Fm)    Ap    Ae    HEADWATER
NUMBER     (CFS) (MIN.) (INCH/HR) (INCH/HR)  (ACRES)  NODE
1         25.72  14.69   0.50( 0.50) 1.00   33.3  40200.00
TOTAL AREA(ACRES) = 33.3

*****
FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 11
-----
>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<
=====
** MAIN STREAM CONFLUENCE DATA **
STREAM      Q      Tc  Intensity  Fp(Fm)    Ap    Ae    HEADWATER
NUMBER     (CFS) (MIN.) (INCH/HR) (INCH/HR)  (ACRES)  NODE
1         524.39  32.72   0.852  0.50( 0.50) 1.00  1558.4  40120.00
2         514.58  34.90   0.825  0.50( 0.50) 1.00  1656.3  40100.00
3         291.53  84.95   0.531  0.50( 0.50) 1.00  3211.2  11910.00
4         276.61  86.52   0.526  0.50( 0.50) 1.00  3224.2  11900.00
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.50 = 29253.42 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **
STREAM      Q      Tc  Intensity  Fp(Fm)    Ap    Ae    HEADWATER
NUMBER     (CFS) (MIN.) (INCH/HR) (INCH/HR)  (ACRES)  NODE
1         25.72  14.69   1.358  0.50( 0.50) 1.00   33.3  40200.00
LONGEST FLOWPATH FROM NODE 40200.00 TO NODE 11927.50 = 1999.00 FEET.

** PEAK FLOW RATE TABLE **
STREAM      Q      Tc  Intensity  Fp(Fm)    Ap    Ae    HEADWATER
NUMBER     (CFS) (MIN.) (INCH/HR) (INCH/HR)  (ACRES)  NODE
1         550.11  14.69   1.358  0.50( 0.50) 1.00   732.9  40200.00
2         534.95  32.72   0.852  0.50( 0.50) 1.00  1591.7  40120.00
3         524.30  34.90   0.825  0.50( 0.50) 1.00  1689.6  40100.00
4         292.46  84.95   0.531  0.50( 0.50) 1.00  3244.5  11910.00
5         277.38  86.52   0.526  0.50( 0.50) 1.00  3257.5  11900.00
TOTAL AREA(ACRES) = 3257.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
PEAK FLOW RATE(CFS) = 550.11 Tc(MIN.) = 14.691
EFFECTIVE AREA(ACRES) = 732.95 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 3257.5
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.50 = 29253.42 FEET.

*****
FLOW PROCESS FROM NODE 11927.50 TO NODE 11928.00 IS CODE = 51
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 384.00 DOWNSTREAM(FEET) = 359.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 647.19 CHANNEL SLOPE = 0.0386
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

```

MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.291  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 78.01 0.50 0.984 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.984  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 578.15  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.41  
 AVERAGE FLOW DEPTH (FEET) = 4.79 TRAVEL TIME (MIN.) = 1.28  
 Tc (MIN.) = 15.97  
 SUBAREA AREA (ACRES) = 78.01 SUBAREA RUNOFF (CFS) = 56.07  
 EFFECTIVE AREA (ACRES) = 810.96 AREA-AVERAGED Fm (INCH/HR) = 0.50  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA (ACRES) = 3335.5 PEAK FLOW RATE (CFS) = 578.17

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 4.79 FLOW VELOCITY (FEET/SEC.) = 8.41  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11928.00 = 29900.61 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 51  
 -----

>>>> COMPUTE TRAPEZOIDAL CHANNEL FLOW <<<<<  
 >>>> TRAVEL TIME THRU SUBAREA (EXISTING ELEMENT) <<<<<  
 -----

ELEVATION DATA: UPSTREAM (FEET) = 359.00 DOWNSTREAM (FEET) = 341.63  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1322.66 CHANNEL SLOPE = 0.0131  
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.141  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 8.18 0.50 0.890 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.890  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 580.73  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.62  
 AVERAGE FLOW DEPTH (FEET) = 5.87 TRAVEL TIME (MIN.) = 3.92  
 Tc (MIN.) = 19.90  
 SUBAREA AREA (ACRES) = 8.18 SUBAREA RUNOFF (CFS) = 5.12  
 EFFECTIVE AREA (ACRES) = 819.14 AREA-AVERAGED Fm (INCH/HR) = 0.50  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA (ACRES) = 3343.7 PEAK FLOW RATE (CFS) = 578.17  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 5.86 FLOW VELOCITY (FEET/SEC.) = 5.61  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11929.00 = 31223.27 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 10  
 -----

>>>> MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 3 <<<<<  
 -----

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11841.00 TO NODE 11527.00 IS CODE = 12  
 -----

>>>> CLEAR MEMORY BANK # 1 <<<<<  
 -----

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11841.00 TO NODE 12527.00 IS CODE = 15.1  
 -----

>>>> DEFINE MEMORY BANK # 1 <<<<<  
 -----

PEAK FLOWRATE TABLE FILE NAME: S18X05.DNA  
 MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	6871.23	43.27	0.50 ( 0.50)	0.99	7177.4	11801.00
2	6868.03	46.61	0.50 ( 0.50)	0.99	7821.6	11831.00
3	6831.35	54.45	0.50 ( 0.50)	0.99	9253.7	11500.00
4	6778.10	60.05	0.50 ( 0.50)	0.99	10627.1	11701.00
5	6681.76	66.19	0.50 ( 0.50)	1.00	12121.5	11000.00
6	6475.61	83.04	0.50 ( 0.50)	1.00	17603.2	11330.00
7	6342.06	88.36	0.50 ( 0.50)	1.00	19494.9	10900.00
8	6230.68	91.62	0.50 ( 0.50)	1.00	20592.4	10830.00
9	5983.87	96.58	0.50 ( 0.50)	1.00	21984.5	11130.00
10	5363.28	107.52	0.50 ( 0.50)	1.00	24463.0	11620.00
11	5080.72	112.52	0.50 ( 0.50)	1.00	25521.2	10600.00
12	4959.28	115.06	0.50 ( 0.50)	1.00	26061.4	11600.00
13	4208.11	125.27	0.50 ( 0.50)	1.00	27870.7	10500.00
14	3686.50	134.23	0.50 ( 0.50)	1.00	29001.0	10710.00
15	3079.50	146.58	0.50 ( 0.50)	1.00	30024.8	10700.00
16	2649.64	155.94	0.50 ( 0.50)	1.00	30698.5	10400.00
17	2296.99	164.19	0.50 ( 0.50)	1.00	31188.4	10200.00
18	1901.26	178.29	0.50 ( 0.50)	1.00	31917.9	10300.00
19	1742.48	184.66	0.50 ( 0.50)	1.00	32047.5	10210.00
20	608.82	267.18	0.50 ( 0.50)	1.00	32916.6	10100.00
TOTAL AREA (ACRES) =		32916.6				

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 12  
 -----

>>>> CLEAR MEMORY BANK # 2 <<<<<  
 -----

\*\*\*MEMORY BANK # 2 IS EMPTY - PROCESS IGNORED.\*\*\*

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 15.1  
 -----

>>>> DEFINE MEMORY BANK # 2 <<<<<  
 -----

PEAK FLOWRATE TABLE FILE NAME: S25X05.DNA  
 MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1893.24	82.32	0.50 ( 0.49)	0.99	5730.4	12500.00
2	1840.67	101.00	0.50 ( 0.49)	0.99	7460.2	12300.00
3	1831.66	103.75	0.50 ( 0.49)	0.99	7807.7	12330.00
4	1786.92	113.52	0.50 ( 0.49)	0.98	8941.0	12410.00
5	1724.88	122.39	0.50 ( 0.49)	0.98	9874.6	12400.00

6	1697.93	124.27	0.50	( 0.49)	0.98	10031.7	12211.00
7	1549.17	132.90	0.50	( 0.49)	0.98	10707.0	12201.00
8	1383.71	141.46	0.50	( 0.49)	0.98	11230.3	12111.00
9	1282.12	147.13	0.50	( 0.49)	0.98	11586.3	12231.00
10	1154.55	155.77	0.50	( 0.49)	0.98	12067.3	12261.00
11	1138.83	156.90	0.50	( 0.49)	0.98	12113.1	12101.10
12	821.51	184.54	0.50	( 0.49)	0.98	13109.5	12010.00
13	621.28	203.48	0.50	( 0.49)	0.98	13237.1	12000.00
TOTAL AREA (ACRES) =		13237.1					

\*\*\*\*\*

FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1893.24	82.32	0.50 ( 0.49)	0.99	5730.4	12500.00
2	1840.67	101.00	0.50 ( 0.49)	0.99	7460.2	12300.00
3	1831.66	103.75	0.50 ( 0.49)	0.99	7807.7	12330.00
4	1786.92	113.52	0.50 ( 0.49)	0.98	8941.0	12410.00
5	1724.88	122.39	0.50 ( 0.49)	0.98	9874.6	12400.00
6	1697.93	124.27	0.50 ( 0.49)	0.98	10031.7	12211.00
7	1549.17	132.90	0.50 ( 0.49)	0.98	10707.0	12201.00
8	1383.71	141.46	0.50 ( 0.49)	0.98	11230.3	12111.00
9	1282.12	147.13	0.50 ( 0.49)	0.98	11586.3	12231.00
10	1154.55	155.77	0.50 ( 0.49)	0.98	12067.3	12261.00
11	1138.83	156.90	0.50 ( 0.49)	0.98	12113.1	12101.10
12	821.51	184.54	0.50 ( 0.49)	0.98	13109.5	12010.00
13	621.28	203.48	0.50 ( 0.49)	0.98	13237.1	12000.00
TOTAL AREA (ACRES) =		13237.1				

\*\*\*\*\*

FLOW PROCESS FROM NODE 11841.00 TO NODE 12527.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1893.24	82.32	0.540	0.50 ( 0.49)	0.99	5730.4	12500.00
2	1840.67	101.00	0.493	0.50 ( 0.49)	0.99	7460.2	12300.00
3	1831.66	103.75	0.487	0.50 ( 0.49)	0.99	7807.7	12330.00
4	1786.92	113.52	0.469	0.50 ( 0.49)	0.98	8941.0	12410.00
5	1724.88	122.39	0.453	0.50 ( 0.49)	0.98	9874.6	12400.00
6	1697.93	124.27	0.451	0.50 ( 0.49)	0.98	10031.7	12211.00
7	1549.17	132.90	0.441	0.50 ( 0.49)	0.98	10707.0	12201.00
8	1383.71	141.46	0.430	0.50 ( 0.49)	0.98	11230.3	12111.00
9	1282.12	147.13	0.423	0.50 ( 0.49)	0.98	11586.3	12231.00
10	1154.55	155.77	0.413	0.50 ( 0.49)	0.98	12067.3	12261.00
11	1138.83	156.90	0.412	0.50 ( 0.49)	0.98	12113.1	12101.10
12	821.51	184.54	0.382	0.50 ( 0.49)	0.98	13109.5	12010.00
13	621.28	203.48	0.371	0.50 ( 0.49)	0.98	13237.1	12000.00
LONGEST FLOWPATH FROM NODE		12000.00 TO NODE		12527.00 = 77156.98 FEET.			

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	6871.23	43.27	0.733	0.50 ( 0.50)	0.99	7177.4	11801.00
2	6868.03	46.61	0.705	0.50 ( 0.50)	0.99	7821.6	11831.00
3	6831.35	54.45	0.650	0.50 ( 0.50)	0.99	9253.7	11500.00
4	6778.10	60.05	0.617	0.50 ( 0.50)	0.99	10627.1	11701.00
5	6681.76	66.19	0.596	0.50 ( 0.50)	1.00	12121.5	11000.00
6	6475.61	83.04	0.538	0.50 ( 0.50)	1.00	17603.2	11330.00
7	6342.06	88.36	0.520	0.50 ( 0.50)	1.00	19494.9	10900.00
8	6230.68	91.62	0.511	0.50 ( 0.50)	1.00	20592.4	10830.00
9	5983.87	96.58	0.501	0.50 ( 0.50)	1.00	21984.5	11130.00
10	5363.28	107.52	0.480	0.50 ( 0.50)	1.00	24463.0	11620.00
11	5080.72	112.52	0.470	0.50 ( 0.50)	1.00	25521.2	10600.00
12	4959.28	115.06	0.466	0.50 ( 0.50)	1.00	26061.4	11600.00
13	4208.11	125.27	0.450	0.50 ( 0.50)	1.00	27870.7	10500.00
14	3686.50	134.23	0.439	0.50 ( 0.50)	1.00	29001.0	10710.00
15	3079.50	146.58	0.424	0.50 ( 0.50)	1.00	30024.8	10700.00
16	2649.64	155.94	0.413	0.50 ( 0.50)	1.00	30698.5	10400.00
17	2296.99	164.19	0.403	0.50 ( 0.50)	1.00	31188.4	10200.00
18	1901.26	178.29	0.386	0.50 ( 0.50)	1.00	31917.9	10300.00
19	1742.48	184.66	0.381	0.50 ( 0.50)	1.00	32047.5	10210.00
20	608.82	267.18	0.337	0.50 ( 0.50)	1.00	32916.6	10100.00
LONGEST FLOWPATH FROM NODE		10100.00 TO NODE		12527.00 = 97868.13 FEET.			

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	8764.47	43.27	0.733	0.50 ( 0.50)	0.99	10189.2	11801.00
2	8761.27	46.61	0.705	0.50 ( 0.50)	0.99	11066.1	11831.00
3	8724.59	54.45	0.650	0.50 ( 0.50)	0.99	13043.9	11500.00
4	8671.34	60.05	0.617	0.50 ( 0.50)	0.99	14807.3	11701.00
5	8575.00	66.19	0.596	0.50 ( 0.50)	0.99	16728.7	11000.00
6	8377.64	82.32	0.540	0.50 ( 0.50)	0.99	23099.8	12500.00
7	8366.83	83.04	0.538	0.50 ( 0.50)	0.99	23400.2	11330.00
8	8218.32	88.36	0.520	0.50 ( 0.50)	0.99	25784.2	10900.00
9	8097.74	91.62	0.511	0.50 ( 0.50)	0.99	27184.1	10830.00
10	7836.98	96.58	0.501	0.50 ( 0.50)	0.99	29035.2	11130.00
11	7573.80	101.00	0.493	0.50 ( 0.50)	0.99	30446.1	12300.00
12	7408.63	103.75	0.487	0.50 ( 0.50)	0.99	31417.3	12330.00
13	7177.69	107.52	0.480	0.50 ( 0.50)	0.99	32707.8	11620.00
14	6872.25	112.52	0.470	0.50 ( 0.50)	0.99	34345.6	10600.00
15	6819.67	113.52	0.469	0.50 ( 0.50)	0.99	34675.6	12410.00
16	6735.43	115.06	0.466	0.50 ( 0.50)	0.99	35164.5	11600.00
17	6145.43	122.39	0.453	0.50 ( 0.50)	0.99	37233.5	12400.00
18	5980.02	124.27	0.451	0.50 ( 0.50)	0.99	37724.2	12211.00
19	5888.70	125.27	0.450	0.50 ( 0.50)	0.99	37981.1	10500.00
20	5313.35	132.90	0.441	0.50 ( 0.50)	0.99	39539.7	12201.00
21	5209.88	134.23	0.439	0.50 ( 0.50)	0.99	39789.6	10710.00
22	4715.07	141.46	0.430	0.50 ( 0.50)	0.99	40830.3	12111.00
23	4371.41	146.58	0.424	0.50 ( 0.50)	0.99	41576.8	10700.00
24	4336.52	147.13	0.423	0.50 ( 0.50)	0.99	41650.4	12231.00
25	3812.19	155.77	0.413	0.50 ( 0.50)	0.99	42753.2	12261.00
26	3801.75	155.94	0.413	0.50 ( 0.50)	0.99	42772.9	10400.00
27	3747.77	156.90	0.412	0.50 ( 0.50)	0.99	42868.1	12101.10
28	3352.08	164.19	0.403	0.50 ( 0.50)	0.99	43564.4	10200.00
29	2794.46	178.29	0.386	0.50 ( 0.50)	0.99	44802.3	10300.00
30	2567.05	184.54	0.382	0.50 ( 0.50)	0.99	45154.5	12010.00

31 2562.70 184.66 0.381 0.50( 0.50) 0.99 45157.8 10210.00  
 32 2105.15 203.48 0.371 0.50( 0.50) 0.99 45482.9 12000.00  
 33 1172.06 267.18 0.337 0.50( 0.50) 0.99 46153.7 10100.00  
 TOTAL AREA(ACRES) = 46153.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 8764.47 Tc(MIN.) = 43.268  
 EFFECTIVE AREA(ACRES) = 10189.25 AREA-AVERAGED Fm(INCH/HR) = 0.50  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 46153.7  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12527.00 = 97868.13 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12527.00 TO NODE 11929.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 347.47 DOWNSTREAM(FEET) = 341.63  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 532.38 CHANNEL SLOPE = 0.0110  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.726

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	14.37	0.50	0.987	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.987  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 8765.97  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.35  
 AVERAGE FLOW DEPTH(FEET) = 16.80 TRAVEL TIME(MIN.) = 0.86  
 Tc(MIN.) = 44.13  
 SUBAREA AREA(ACRES) = 14.37 SUBAREA RUNOFF(CFS) = 3.00  
 EFFECTIVE AREA(ACRES) = 10203.62 AREA-AVERAGED Fm(INCH/HR) = 0.50  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 46168.0 PEAK FLOW RATE(CFS) = 8764.47  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 16.80 FLOW VELOCITY(FEET/SEC.) = 10.35  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	8764.47	44.13	0.726	0.50( 0.50)	0.99	10203.6	11801.00
2	8761.27	47.47	0.698	0.50( 0.50)	0.99	11080.5	11831.00
3	8724.59	55.31	0.645	0.50( 0.50)	0.99	13058.3	11500.00
4	8671.34	60.91	0.614	0.50( 0.50)	0.99	14821.7	11701.00
5	8575.00	67.05	0.593	0.50( 0.50)	0.99	16743.1	11000.00
6	8377.64	83.19	0.537	0.50( 0.50)	0.99	23114.1	12500.00

7	8366.83	83.91	0.535	0.50( 0.50)	0.99	23414.6	11330.00
8	8218.32	89.23	0.517	0.50( 0.50)	0.99	25798.5	10900.00
9	8097.74	92.50	0.509	0.50( 0.50)	0.99	27198.5	10830.00
10	7836.98	97.46	0.500	0.50( 0.50)	0.99	29049.6	11130.00
11	7573.80	101.89	0.491	0.50( 0.50)	0.99	30460.5	12300.00
12	7408.63	104.65	0.486	0.50( 0.50)	0.99	31431.6	12330.00
13	7177.69	108.42	0.478	0.50( 0.50)	0.99	32722.1	11620.00
14	6872.25	113.43	0.469	0.50( 0.50)	0.99	34359.9	10600.00
15	6819.67	114.43	0.467	0.50( 0.50)	0.99	34690.0	12410.00
16	6735.43	115.98	0.464	0.50( 0.50)	0.99	35178.9	11600.00
17	6145.43	123.32	0.452	0.50( 0.50)	0.99	37247.9	12400.00
18	5980.02	125.21	0.450	0.50( 0.50)	0.99	37738.5	12211.00
19	5888.70	126.22	0.449	0.50( 0.50)	0.99	37995.4	10500.00
20	5313.35	133.87	0.439	0.50( 0.50)	0.99	39554.1	12201.00
21	5209.88	135.21	0.438	0.50( 0.50)	0.99	39804.0	10710.00
22	4715.07	142.46	0.429	0.50( 0.50)	0.99	40844.7	12111.00
23	4371.41	147.60	0.423	0.50( 0.50)	0.99	41591.2	10700.00
24	4336.52	148.15	0.422	0.50( 0.50)	0.99	41664.8	12231.00
25	3812.19	156.82	0.412	0.50( 0.50)	0.99	42767.6	12261.00
26	3801.75	157.00	0.412	0.50( 0.50)	0.99	42787.3	10400.00
27	3747.77	157.96	0.410	0.50( 0.50)	0.99	42882.5	12101.10
28	3352.08	165.28	0.402	0.50( 0.50)	0.99	43578.7	12000.00
29	2794.46	179.43	0.385	0.50( 0.50)	0.99	44816.7	10300.00
30	2567.05	185.70	0.381	0.50( 0.50)	0.99	45168.9	12010.00
31	2562.70	185.83	0.381	0.50( 0.50)	0.99	45172.2	10210.00
32	2105.15	204.71	0.371	0.50( 0.50)	0.99	45497.3	12000.00
33	1172.06	268.60	0.336	0.50( 0.50)	0.99	46168.0	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	578.17	19.90	1.141	0.50( 0.50)	1.00	819.1	40200.00
2	534.95	38.03	0.785	0.50( 0.50)	1.00	1677.9	40120.00
3	524.30	40.23	0.758	0.50( 0.50)	1.00	1775.8	40100.00
4	292.46	91.13	0.512	0.50( 0.50)	1.00	3330.7	11910.00
5	277.38	92.78	0.509	0.50( 0.50)	1.00	3343.7	11900.00

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11929.00 = 31223.27 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9342.64	19.90	1.141	0.50( 0.50)	0.99	5420.0	40200.00
2	9299.42	38.03	0.785	0.50( 0.50)	0.99	10471.1	40120.00
3	9288.77	40.23	0.758	0.50( 0.50)	0.99	11078.8	40100.00
4	9271.03	44.13	0.726	0.50( 0.50)	0.99	12098.4	11801.00
5	9252.61	47.47	0.698	0.50( 0.50)	0.99	13077.3	11831.00
6	9180.21	55.31	0.645	0.50( 0.50)	0.99	15294.7	11500.00
7	9101.44	60.91	0.614	0.50( 0.50)	0.99	17229.3	11701.00
8	8977.14	67.05	0.593	0.50( 0.50)	0.99	19338.1	11000.00
9	8706.27	83.19	0.537	0.50( 0.50)	0.99	26202.2	12500.00
10	8692.17	83.91	0.535	0.50( 0.50)	0.99	26524.7	11330.00
11	8519.44	89.23	0.517	0.50( 0.50)	0.99	29071.1	10900.00
12	8440.61	91.13	0.512	0.50( 0.50)	0.99	29943.9	11910.00
13	8377.71	92.50	0.509	0.50( 0.50)	0.99	30539.9	10830.00
14	8360.30	92.78	0.509	0.50( 0.50)	0.99	30647.5	11900.00
15	8109.43	97.46	0.500	0.50( 0.50)	0.99	32393.3	11130.00
16	7841.58	101.89	0.491	0.50( 0.50)	0.99	33804.2	12300.00

17	7673.50	104.65	0.486	0.50	( 0.50)	0.99	34775.3	12330.00
18	7438.58	108.42	0.478	0.50	( 0.50)	0.99	36065.8	11620.00
19	7127.87	113.43	0.469	0.50	( 0.50)	0.99	37703.6	10600.00
20	7074.22	114.43	0.467	0.50	( 0.50)	0.99	38033.7	12410.00
21	6988.35	115.98	0.464	0.50	( 0.50)	0.99	38522.6	11600.00
22	6391.94	123.32	0.452	0.50	( 0.50)	0.99	40591.6	12400.00
23	6225.29	125.21	0.450	0.50	( 0.50)	0.99	41082.3	12211.00
24	6133.32	126.22	0.449	0.50	( 0.50)	0.99	41339.1	10500.00
25	5552.96	133.87	0.439	0.50	( 0.50)	0.99	42897.8	12201.00
26	5448.61	135.21	0.438	0.50	( 0.50)	0.99	43147.7	10710.00
27	4949.05	142.46	0.429	0.50	( 0.50)	0.99	44188.4	12111.00
28	4602.03	147.60	0.423	0.50	( 0.50)	0.99	44934.9	10700.00
29	4566.78	148.15	0.422	0.50	( 0.50)	0.99	45008.5	12231.00
30	4036.78	156.82	0.412	0.50	( 0.50)	0.99	46111.3	12261.00
31	4026.22	157.00	0.412	0.50	( 0.50)	0.99	46131.0	10400.00
32	3971.61	157.96	0.410	0.50	( 0.50)	0.99	46226.2	12101.10
33	3571.13	165.28	0.402	0.50	( 0.50)	0.99	46922.5	10200.00
34	3004.25	179.43	0.385	0.50	( 0.50)	0.99	48160.4	10300.00
35	2774.77	185.70	0.381	0.50	( 0.50)	0.99	48512.6	12010.00
36	2770.38	185.83	0.381	0.50	( 0.50)	0.99	48515.9	10210.00
37	2307.23	204.71	0.371	0.50	( 0.50)	0.99	48841.0	12000.00
38	1355.17	268.60	0.336	0.50	( 0.50)	0.99	49511.8	10100.00

TOTAL AREA (ACRES) = 49511.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 9342.64 Tc (MIN.) = 19.897  
EFFECTIVE AREA (ACRES) = 5420.05 AREA-AVERAGED Fm (INCH/HR) = 0.50  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 49511.8  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 49511.8 TC (MIN.) = 19.90  
EFFECTIVE AREA (ACRES) = 5420.05 AREA-AVERAGED Fm (INCH/HR) = 0.50  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.993  
PEAK FLOW RATE (CFS) = 9342.64

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9342.64	19.90	1.141	0.50 ( 0.50)	0.99	5420.0	40200.00
2	9299.42	38.03	0.785	0.50 ( 0.50)	0.99	10471.1	40120.00
3	9288.77	40.23	0.758	0.50 ( 0.50)	0.99	11078.8	40100.00
4	9271.03	44.13	0.726	0.50 ( 0.50)	0.99	12098.4	11801.00
5	9252.61	47.47	0.698	0.50 ( 0.50)	0.99	13077.3	11831.00
6	9180.21	55.31	0.645	0.50 ( 0.50)	0.99	15294.7	11500.00
7	9101.44	60.91	0.614	0.50 ( 0.50)	0.99	17229.3	11701.00
8	8977.14	67.05	0.593	0.50 ( 0.50)	0.99	19338.1	11000.00
9	8706.27	83.19	0.537	0.50 ( 0.50)	0.99	26202.2	12500.00
10	8692.17	83.91	0.535	0.50 ( 0.50)	0.99	26524.7	11330.00
11	8519.44	89.23	0.517	0.50 ( 0.50)	0.99	29071.1	10900.00
12	8440.61	91.13	0.512	0.50 ( 0.50)	0.99	29943.9	11910.00
13	8377.71	92.50	0.509	0.50 ( 0.50)	0.99	30539.9	10830.00
14	8360.30	92.78	0.509	0.50 ( 0.50)	0.99	30647.5	11900.00
15	8109.43	97.46	0.500	0.50 ( 0.50)	0.99	32393.3	11130.00
16	7841.58	101.89	0.491	0.50 ( 0.50)	0.99	33804.2	12300.00
17	7673.50	104.65	0.486	0.50 ( 0.50)	0.99	34775.3	12330.00
18	7438.58	108.42	0.478	0.50 ( 0.50)	0.99	36065.8	11620.00

19	7127.87	113.43	0.469	0.50	( 0.50)	0.99	37703.6	10600.00
20	7074.22	114.43	0.467	0.50	( 0.50)	0.99	38033.7	12410.00
21	6988.35	115.98	0.464	0.50	( 0.50)	0.99	38522.6	11600.00
22	6391.94	123.32	0.452	0.50	( 0.50)	0.99	40591.6	12400.00
23	6225.29	125.21	0.450	0.50	( 0.50)	0.99	41082.3	12211.00
24	6133.32	126.22	0.449	0.50	( 0.50)	0.99	41339.1	10500.00
25	5552.96	133.87	0.439	0.50	( 0.50)	0.99	42897.8	12201.00
26	5448.61	135.21	0.438	0.50	( 0.50)	0.99	43147.7	10710.00
27	4949.05	142.46	0.429	0.50	( 0.50)	0.99	44188.4	12111.00
28	4602.03	147.60	0.423	0.50	( 0.50)	0.99	44934.9	10700.00
29	4566.78	148.15	0.422	0.50	( 0.50)	0.99	45008.5	12231.00
30	4036.78	156.82	0.412	0.50	( 0.50)	0.99	46111.3	12261.00
31	4026.22	157.00	0.412	0.50	( 0.50)	0.99	46131.0	10400.00
32	3971.61	157.96	0.410	0.50	( 0.50)	0.99	46226.2	12101.10
33	3571.13	165.28	0.402	0.50	( 0.50)	0.99	46922.5	10200.00
34	3004.25	179.43	0.385	0.50	( 0.50)	0.99	48160.4	10300.00
35	2774.77	185.70	0.381	0.50	( 0.50)	0.99	48512.6	12010.00
36	2770.38	185.83	0.381	0.50	( 0.50)	0.99	48515.9	10210.00
37	2307.23	204.71	0.371	0.50	( 0.50)	0.99	48841.0	12000.00
38	1355.17	268.60	0.336	0.50	( 0.50)	0.99	49511.8	10100.00

=====  
END OF RATIONAL METHOD ANALYSIS  
=====





\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA 92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S26- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 5-YR RM EV APRIL 2019 ROKAMOTO \*  
\*\*\*\*\*

FILE NAME: RI05EV26.DAT  
TIME/DATE OF STUDY: 17:18 04/08/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 5.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 2.739
- 2) 10.00; 1.815
- 3) 15.00; 1.325
- 4) 20.00; 1.135
- 5) 25.00; 0.989
- 6) 30.00; 0.885
- 7) 40.00; 0.759
- 8) 50.00; 0.676
- 9) 60.00; 0.615
- 10) 90.00; 0.513
- 11) 120.00; 0.455
- 12) 180.00; 0.383
- 13) 360.00; 0.284
- 14) 1200.00; 0.125

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI05EV19.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9342.64	19.90	0.50 ( 0.50)	0.99	5420.0	40200.00
2	9299.42	38.03	0.50 ( 0.50)	0.99	10471.1	40120.00
3	9271.03	44.13	0.50 ( 0.50)	0.99	12098.4	11801.00
4	9180.21	55.31	0.50 ( 0.50)	0.99	15294.7	11500.00
5	9101.44	60.91	0.50 ( 0.50)	0.99	17229.3	11701.00
6	8977.14	67.05	0.50 ( 0.50)	0.99	19338.1	11000.00
7	8706.27	83.19	0.50 ( 0.50)	0.99	26202.2	12500.00
8	8519.44	89.23	0.50 ( 0.50)	0.99	29071.1	10900.00
9	8109.43	97.46	0.50 ( 0.50)	0.99	32393.3	11130.00
10	7438.58	108.42	0.50 ( 0.50)	0.99	36065.8	11620.00
11	6391.94	123.32	0.50 ( 0.50)	0.99	40591.6	12400.00
12	5552.96	133.87	0.50 ( 0.50)	0.99	42897.8	12201.00
13	4949.05	142.46	0.50 ( 0.50)	0.99	44188.4	12111.00
14	4602.03	147.60	0.50 ( 0.50)	0.99	44934.9	10700.00
15	4036.78	156.82	0.50 ( 0.50)	0.99	46111.3	12261.00
16	3571.13	165.28	0.50 ( 0.50)	0.99	46922.5	10200.00
17	3004.25	179.43	0.50 ( 0.50)	0.99	48160.4	10300.00
18	2774.77	185.70	0.50 ( 0.50)	0.99	48512.6	12010.00
19	2307.23	204.71	0.50 ( 0.50)	0.99	48841.0	12000.00
20	1355.17	268.60	0.50 ( 0.50)	0.99	49511.8	10100.00
TOTAL AREA(ACRES) =						49511.8

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9342.64	19.90	0.50 ( 0.50)	0.99	5420.0	40200.00
2	9299.42	38.03	0.50 ( 0.50)	0.99	10471.1	40120.00
3	9271.03	44.13	0.50 ( 0.50)	0.99	12098.4	11801.00
4	9180.21	55.31	0.50 ( 0.50)	0.99	15294.7	11500.00
5	9101.44	60.91	0.50 ( 0.50)	0.99	17229.3	11701.00
6	8977.14	67.05	0.50 ( 0.50)	0.99	19338.1	11000.00
7	8706.27	83.19	0.50 ( 0.50)	0.99	26202.2	12500.00
8	8519.44	89.23	0.50 ( 0.50)	0.99	29071.1	10900.00
9	8109.43	97.46	0.50 ( 0.50)	0.99	32393.3	11130.00
10	7438.58	108.42	0.50 ( 0.50)	0.99	36065.8	11620.00
11	6391.94	123.32	0.50 ( 0.50)	0.99	40591.6	12400.00
12	5552.96	133.87	0.50 ( 0.50)	0.99	42897.8	12201.00
13	4949.05	142.46	0.50 ( 0.50)	0.99	44188.4	12111.00

14 4602.03 147.60 0.50( 0.50) 0.99 44934.9 10700.00  
 15 4036.78 156.82 0.50( 0.50) 0.99 46111.3 12261.00  
 16 3571.13 165.28 0.50( 0.50) 0.99 46922.5 10200.00  
 17 3004.25 179.43 0.50( 0.50) 0.99 48160.4 10300.00  
 18 2774.77 185.70 0.50( 0.50) 0.99 48512.6 12010.00  
 19 2307.23 204.71 0.50( 0.50) 0.99 48841.0 12000.00  
 20 1355.17 268.60 0.50( 0.50) 0.99 49511.8 10100.00  
 TOTAL AREA (ACRES) = 49511.8

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 1 <<<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11929.00 TO NODE 12601.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 341.63 DOWNSTREAM (FEET) = 325.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1467.93 CHANNEL SLOPE = 0.0113  
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00

\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.098  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 14.11 0.50 0.700 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.700  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 9347.39  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 17.90  
 AVERAGE FLOW DEPTH (FEET) = 13.19 TRAVEL TIME (MIN.) = 1.37  
 Tc (MIN.) = 21.26  
 SUBAREA AREA (ACRES) = 14.11 SUBAREA RUNOFF (CFS) = 9.50  
 EFFECTIVE AREA (ACRES) = 5434.16 AREA-AVERAGED Fm (INCH/HR) = 0.50  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA (ACRES) = 49525.9 PEAK FLOW RATE (CFS) = 9342.64  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 13.19 FLOW VELOCITY (FEET/SEC.) = 17.90  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 2 <<<<<<

PEAK FLOWRATE TABLE FILE NAME: 3005EVRL.DNA  
 MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	30.35	18.54	0.50( 0.49)	0.99	48.4	600.00
TOTAL AREA (ACRES) = 48.4						

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9342.64	21.26	1.098	0.50( 0.50)	0.99	5434.2	40200.00
2	9299.42	39.39	0.767	0.50( 0.50)	0.99	10485.2	40120.00
3	9271.03	45.49	0.713	0.50( 0.50)	0.99	12112.5	11801.00
4	9180.21	56.68	0.635	0.50( 0.50)	0.99	15308.8	11500.00
5	9101.44	62.29	0.607	0.50( 0.50)	0.99	17243.4	11701.00
6	8977.14	68.43	0.586	0.50( 0.50)	0.99	19352.2	11000.00
7	8706.27	84.58	0.531	0.50( 0.50)	0.99	26216.3	12500.00
8	8519.44	90.63	0.512	0.50( 0.50)	0.99	29085.2	10900.00
9	8109.43	98.88	0.496	0.50( 0.50)	0.99	32407.4	11130.00
10	7438.58	109.87	0.475	0.50( 0.50)	0.99	36079.9	11620.00
11	6391.94	124.82	0.449	0.50( 0.50)	0.99	40605.7	12400.00
12	5552.96	135.43	0.436	0.50( 0.50)	0.99	42911.9	12201.00
13	4949.05	144.06	0.426	0.50( 0.50)	0.99	44202.5	12111.00
14	4602.03	149.23	0.420	0.50( 0.50)	0.99	44949.0	10700.00
15	4036.78	158.51	0.409	0.50( 0.50)	0.99	46125.4	12261.00
16	3571.13	167.02	0.399	0.50( 0.50)	0.99	46936.6	10200.00
17	3004.25	181.25	0.382	0.50( 0.50)	0.99	48174.5	10300.00
18	2774.77	187.55	0.379	0.50( 0.50)	0.99	48526.7	12010.00
19	2307.23	206.65	0.368	0.50( 0.50)	0.99	48855.1	12000.00
20	1355.17	270.81	0.333	0.50( 0.50)	0.99	49525.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	30.35	18.54	1.190	0.50( 0.49)	0.99	48.4	600.00

LONGEST FLOWPATH FROM NODE 600.00 TO NODE 12601.00 = 4850.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9372.99	18.54	1.190	0.50( 0.50)	0.99	4787.6	600.00
2	9368.97	21.26	1.098	0.50( 0.50)	0.99	5482.6	40200.00
3	9311.31	39.39	0.767	0.50( 0.50)	0.99	10533.6	40120.00
4	9280.61	45.49	0.713	0.50( 0.50)	0.99	12160.9	11801.00
5	9186.38	56.68	0.635	0.50( 0.50)	0.99	15357.2	11500.00
6	9106.39	62.29	0.607	0.50( 0.50)	0.99	17291.8	11701.00
7	8981.18	68.43	0.586	0.50( 0.50)	0.99	19400.6	11000.00
8	8707.92	84.58	0.531	0.50( 0.50)	0.99	26264.8	12500.00
9	8520.23	90.63	0.512	0.50( 0.50)	0.99	29133.6	10900.00
10	8109.72	98.88	0.496	0.50( 0.50)	0.99	32455.8	11130.00
11	7438.85	109.87	0.475	0.50( 0.50)	0.99	36128.3	11620.00
12	6392.20	124.82	0.449	0.50( 0.50)	0.99	40654.1	12400.00
13	5553.21	135.43	0.436	0.50( 0.50)	0.99	42960.3	12201.00
14	4949.30	144.06	0.426	0.50( 0.50)	0.99	44250.9	12111.00
15	4602.27	149.23	0.420	0.50( 0.50)	0.99	44997.4	10700.00
16	4037.01	158.51	0.409	0.50( 0.50)	0.99	46173.8	12261.00
17	3571.36	167.02	0.399	0.50( 0.50)	0.99	46985.0	10200.00
18	3004.47	181.25	0.382	0.50( 0.50)	0.99	48222.9	10300.00

19 2774.99 187.55 0.379 0.50( 0.50) 0.99 48575.1 12010.00  
 20 2307.44 206.65 0.368 0.50( 0.50) 0.99 48903.5 12000.00  
 21 1355.37 270.81 0.333 0.50( 0.50) 0.99 49574.3 10100.00  
 TOTAL AREA(ACRES) = 49574.3

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 9372.99 Tc(MIN.) = 18.544  
 EFFECTIVE AREA(ACRES) = 4787.60 AREA-AVERAGED Fm(INCH/HR) = 0.50  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 49574.3  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 2 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12601.00 TO NODE 12602.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 325.00 DOWNSTREAM(FEET) = 313.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1377.46 CHANNEL SLOPE = 0.0087  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
 CHANNEL FLOW THRU SUBAREA(CFS) = 9372.99  
 FLOW VELOCITY(FEET/SEC.) = 16.23 FLOW DEPTH(FEET) = 13.87  
 TRAVEL TIME(MIN.) = 1.41 Tc(MIN.) = 19.96  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12602.00 = 101245.91 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12602.00 TO NODE 12603.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 313.00 DOWNSTREAM(FEET) = 310.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 312.14 CHANNEL SLOPE = 0.0096  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
 CHANNEL FLOW THRU SUBAREA(CFS) = 9372.99  
 FLOW VELOCITY(FEET/SEC.) = 16.84 FLOW DEPTH(FEET) = 13.62  
 TRAVEL TIME(MIN.) = 0.31 Tc(MIN.) = 20.27  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.05 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610403U.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	93.93	21.90	0.50( 0.48)	0.97	175.0	40300.00

TOTAL AREA(ACRES) = 175.0

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9372.99	20.27	1.127	0.50( 0.50)	0.99	4787.6	600.00
2	9368.97	22.99	1.048	0.50( 0.50)	0.99	5482.6	40200.00
3	9311.31	41.12	0.750	0.50( 0.50)	0.99	10533.6	40120.00
4	9280.61	47.22	0.699	0.50( 0.50)	0.99	12160.9	11801.00
5	9186.38	58.41	0.625	0.50( 0.50)	0.99	15357.2	11500.00
6	9106.39	64.02	0.601	0.50( 0.50)	0.99	17291.8	11701.00
7	8981.18	70.17	0.580	0.50( 0.50)	0.99	19400.6	11000.00
8	8707.92	86.34	0.525	0.50( 0.50)	0.99	26264.8	12500.00
9	8520.23	92.39	0.508	0.50( 0.50)	0.99	29133.6	10900.00
10	8109.72	100.66	0.492	0.50( 0.50)	0.99	32455.8	11130.00
11	7438.85	111.69	0.471	0.50( 0.50)	0.99	36128.3	11620.00
12	6392.20	126.72	0.447	0.50( 0.50)	0.99	40654.1	12400.00
13	5553.21	137.39	0.434	0.50( 0.50)	0.99	42960.3	12201.00
14	4949.30	146.08	0.424	0.50( 0.50)	0.99	44250.9	12111.00
15	4602.27	151.29	0.417	0.50( 0.50)	0.99	44997.4	10700.00
16	4037.01	160.64	0.406	0.50( 0.50)	0.99	46173.8	12261.00
17	3571.36	169.21	0.396	0.50( 0.50)	0.99	46985.0	10200.00
18	3004.47	183.54	0.381	0.50( 0.50)	0.99	48222.9	10300.00
19	2774.99	189.89	0.378	0.50( 0.50)	0.99	48575.1	12010.00
20	2307.44	209.09	0.367	0.50( 0.50)	0.99	48903.5	12000.00
21	1355.37	273.61	0.332	0.50( 0.50)	0.99	49574.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.05 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	93.93	21.90	1.080	0.50( 0.48)	0.97	175.0	40300.00

LONGEST FLOWPATH FROM NODE 40300.00 TO NODE 12603.00 = 5256.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9466.86	20.27	1.127	0.50( 0.50)	0.99	4949.6	600.00
2	9464.51	21.90	1.080	0.50( 0.50)	0.99	5379.7	40300.00
3	9457.91	22.99	1.048	0.50( 0.50)	0.99	5657.6	40200.00
4	9353.33	41.12	0.750	0.50( 0.50)	0.99	10708.6	40120.00
5	9314.65	47.22	0.699	0.50( 0.50)	0.99	12335.9	11801.00
6	9208.71	58.41	0.625	0.50( 0.50)	0.99	15532.3	11500.00
7	9125.05	64.02	0.601	0.50( 0.50)	0.99	17466.8	11701.00
8	8996.55	70.17	0.580	0.50( 0.50)	0.99	19575.7	11000.00
9	8714.63	86.34	0.525	0.50( 0.50)	0.99	26439.8	12500.00
10	8524.26	92.39	0.508	0.50( 0.50)	0.99	29308.7	10900.00
11	8112.42	100.66	0.492	0.50( 0.50)	0.99	32630.9	11130.00
12	7441.43	111.69	0.471	0.50( 0.50)	0.99	36303.4	11620.00
13	6394.65	126.72	0.447	0.50( 0.50)	0.99	40829.2	12400.00
14	5555.59	137.39	0.434	0.50( 0.50)	0.99	43135.4	12201.00
15	4951.62	146.08	0.424	0.50( 0.50)	0.99	44426.0	12111.00

16	4604.56	151.29	0.417	0.50	( 0.50)	0.99	45172.4	10700.00
17	4039.24	160.64	0.406	0.50	( 0.50)	0.99	46348.9	12261.00
18	3573.53	169.21	0.396	0.50	( 0.50)	0.99	47160.0	10200.00
19	3006.55	183.54	0.381	0.50	( 0.50)	0.99	48398.0	10300.00
20	2777.06	189.89	0.378	0.50	( 0.50)	0.99	48750.2	12010.00
21	2309.45	209.09	0.367	0.50	( 0.50)	0.99	49078.5	12000.00
22	1357.18	273.61	0.332	0.50	( 0.50)	0.99	49749.3	10100.00

TOTAL AREA (ACRES) = 49749.3

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 9466.86 Tc (MIN.) = 20.267  
EFFECTIVE AREA (ACRES) = 4949.61 AREA-AVERAGED Fm (INCH/HR) = 0.50  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 49749.3  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.05 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<

MAINLINE Tc (MIN.) = 20.27  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.127  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.20	0.50	1.000	-
USER-DEFINED	-	8.80	0.50	1.000	-
USER-DEFINED	-	0.10	0.50	1.000	-
USER-DEFINED	-	0.60	0.50	1.000	-
USER-DEFINED	-	0.60	0.50	1.000	-
USER-DEFINED	-	2.90	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 14.20 SUBAREA RUNOFF (CFS) = 8.01  
EFFECTIVE AREA (ACRES) = 4963.81 AREA-AVERAGED Fm (INCH/HR) = 0.50  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 49763.5 PEAK FLOW RATE (CFS) = 9466.86  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<

MAINLINE Tc (MIN.) = 20.27  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.127  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.30	0.50	1.000	-
USER-DEFINED	-	1.90	0.50	1.000	-

USER-DEFINED	-	0.10	0.50	1.000	-
USER-DEFINED	-	0.70	0.50	1.000	-
USER-DEFINED	-	1.10	0.50	1.000	-
USER-DEFINED	-	0.70	0.50	0.850	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.978  
SUBAREA AREA (ACRES) = 4.80 SUBAREA RUNOFF (CFS) = 2.76  
EFFECTIVE AREA (ACRES) = 4968.61 AREA-AVERAGED Fm (INCH/HR) = 0.50  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 49768.3 PEAK FLOW RATE (CFS) = 9466.86  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<

MAINLINE Tc (MIN.) = 20.27  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.127  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.20	0.50	0.850	-
USER-DEFINED	-	0.10	0.50	0.200	-
USER-DEFINED	-	1.40	0.50	0.900	-
USER-DEFINED	-	1.00	0.50	0.900	-
USER-DEFINED	-	0.30	0.50	1.000	-
USER-DEFINED	-	5.70	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.960  
SUBAREA AREA (ACRES) = 8.70 SUBAREA RUNOFF (CFS) = 5.07  
EFFECTIVE AREA (ACRES) = 4977.31 AREA-AVERAGED Fm (INCH/HR) = 0.50  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 49777.0 PEAK FLOW RATE (CFS) = 9466.86  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12603.00 TO NODE 12604.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 310.00 DOWNSTREAM (FEET) = 307.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 459.69 CHANNEL SLOPE = 0.0065  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA (CFS) = 9466.86  
FLOW VELOCITY (FEET/SEC.) = 14.61 FLOW DEPTH (FEET) = 14.70  
TRAVEL TIME (MIN.) = 0.52 Tc (MIN.) = 20.79  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12604.00 = 102017.73 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12604.00 TO NODE 12604.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<

MAINLINE Tc (MIN.) = 20.79  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.112

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.10	0.50	1.000	-
USER-DEFINED	-	0.90	0.50	1.000	-
USER-DEFINED	-	0.10	0.50	0.850	-
USER-DEFINED	-	0.70	0.50	1.000	-
USER-DEFINED	-	0.50	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.993  
SUBAREA AREA(ACRES) = 2.30 SUBAREA RUNOFF(CFS) = 1.27  
EFFECTIVE AREA(ACRES) = 4979.61 AREA-AVERAGED Fm(INCH/HR) = 0.50  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99  
TOTAL AREA(ACRES) = 49779.3 PEAK FLOW RATE(CFS) = 9466.86  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12604.00 TO NODE 12605.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<  
-----  
ELEVATION DATA: UPSTREAM(FEET) = 307.00 DOWNSTREAM(FEET) = 305.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 427.54 CHANNEL SLOPE = 0.0047  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA(CFS) = 9466.86  
FLOW VELOCITY(FEET/SEC.) = 12.89 FLOW DEPTH(FEET) = 15.65  
TRAVEL TIME(MIN.) = 0.55 Tc(MIN.) = 21.34  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.00 = 102445.27 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12605.00 TO NODE 12605.30 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<  
-----  
ELEVATION DATA: UPSTREAM(FEET) = 305.00 DOWNSTREAM(FEET) = 302.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 217.28 CHANNEL SLOPE = 0.0138  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA(CFS) = 9466.86  
FLOW VELOCITY(FEET/SEC.) = 19.34 FLOW DEPTH(FEET) = 12.77  
TRAVEL TIME(MIN.) = 0.19 Tc(MIN.) = 21.53  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.30 = 102662.55 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12605.30 TO NODE 12605.30 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 3 <<<<  
-----  
PEAK FLOWRATE TABLE FILE NAME: 0610404U.DNA  
MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	220.21	20.90	0.50( 0.50)	0.99	394.9	40430.00
2	216.58	21.42	0.50( 0.50)	0.99	398.7	40440.00
3	203.76	23.10	0.50( 0.50)	0.99	409.8	40400.00

4	203.62	23.12	0.50( 0.50)	0.99	409.8	40420.00
5	202.03	23.33	0.50( 0.50)	0.99	410.5	40410.00
TOTAL AREA(ACRES) = 410.5						

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12605.30 TO NODE 12605.30 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<  
=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9466.86	21.53	1.090	0.50( 0.50)	0.99	4979.6	600.00
2	9464.51	23.16	1.043	0.50( 0.50)	0.99	5409.7	40300.00
3	9457.91	24.25	1.011	0.50( 0.50)	0.99	5687.6	40200.00
4	9353.33	42.39	0.739	0.50( 0.50)	0.99	10738.6	40120.00
5	9314.65	48.49	0.689	0.50( 0.50)	0.99	12365.9	11801.00
6	9208.71	59.69	0.617	0.50( 0.50)	0.99	15562.3	11500.00
7	9125.05	65.30	0.597	0.50( 0.50)	0.99	17496.8	11701.00
8	8996.55	71.45	0.576	0.50( 0.50)	0.99	19605.7	11000.00
9	8714.63	87.63	0.521	0.50( 0.50)	0.99	26469.8	12500.00
10	8524.26	93.69	0.506	0.50( 0.50)	0.99	29338.7	10900.00
11	8112.42	101.98	0.490	0.50( 0.50)	0.99	32660.9	11130.00
12	7441.43	113.04	0.468	0.50( 0.50)	0.99	36333.4	11620.00
13	6394.65	128.12	0.445	0.50( 0.50)	0.99	40859.2	12400.00
14	5555.59	138.84	0.432	0.50( 0.50)	0.99	43165.4	12201.00
15	4951.62	147.57	0.422	0.50( 0.50)	0.99	44456.0	12111.00
16	4604.56	152.81	0.416	0.50( 0.50)	0.99	45202.4	10700.00
17	4039.24	162.20	0.404	0.50( 0.50)	0.99	46378.9	12261.00
18	3573.53	170.83	0.394	0.50( 0.50)	0.99	47190.0	10200.00
19	3006.55	185.22	0.380	0.50( 0.50)	0.99	48428.0	10300.00
20	2777.06	191.61	0.377	0.50( 0.50)	0.99	48780.2	12010.00
21	2309.45	210.89	0.366	0.50( 0.50)	0.99	49108.5	12000.00
22	1357.18	275.66	0.330	0.50( 0.50)	0.99	49779.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.30 = 102662.55 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	220.21	20.90	1.109	0.50( 0.50)	0.99	394.9	40430.00
2	216.58	21.42	1.094	0.50( 0.50)	0.99	398.7	40440.00
3	203.76	23.10	1.045	0.50( 0.50)	0.99	409.8	40400.00
4	203.62	23.12	1.044	0.50( 0.50)	0.99	409.8	40420.00
5	202.03	23.33	1.038	0.50( 0.50)	0.99	410.5	40410.00

LONGEST FLOWPATH FROM NODE 40400.00 TO NODE 12605.30 = 7428.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9687.08	20.90	1.109	0.50( 0.50)	0.99	5228.2	40430.00
2	9683.45	21.42	1.094	0.50( 0.50)	0.99	5351.3	40440.00
3	9682.56	21.53	1.090	0.50( 0.50)	0.99	5379.0	600.00
4	9668.37	23.10	1.045	0.50( 0.50)	0.99	5801.8	40400.00
5	9668.20	23.12	1.044	0.50( 0.50)	0.99	5807.3	40420.00
6	9667.79	23.16	1.043	0.50( 0.50)	0.99	5819.7	40300.00
7	9665.55	23.33	1.038	0.50( 0.50)	0.99	5862.0	40410.00
8	9649.89	24.25	1.011	0.50( 0.50)	0.99	6098.1	40200.00

9	9444.04	42.39	0.739	0.50	( 0.50)	0.99	11149.1	40120.00
10	9386.48	48.49	0.689	0.50	( 0.50)	0.99	12776.4	11801.00
11	9253.85	59.69	0.617	0.50	( 0.50)	0.99	15972.7	11500.00
12	9162.76	65.30	0.597	0.50	( 0.50)	0.99	17907.3	11701.00
13	9026.46	71.45	0.576	0.50	( 0.50)	0.99	20016.1	11000.00
14	8724.05	87.63	0.521	0.50	( 0.50)	0.99	26880.3	12500.00
15	8528.01	93.69	0.506	0.50	( 0.50)	0.99	29749.1	10900.00
16	8114.02	101.98	0.490	0.50	( 0.50)	0.99	33071.4	11130.00
17	7442.97	113.04	0.468	0.50	( 0.50)	0.99	36743.9	11620.00
18	6396.11	128.12	0.445	0.50	( 0.50)	0.99	41269.6	12400.00
19	5557.00	138.84	0.432	0.50	( 0.50)	0.99	43575.8	12201.00
20	4953.00	147.57	0.422	0.50	( 0.50)	0.99	44866.5	12111.00
21	4605.92	152.81	0.416	0.50	( 0.50)	0.99	45612.9	10700.00
22	4040.57	162.20	0.404	0.50	( 0.50)	0.99	46789.4	12261.00
23	3574.82	170.83	0.394	0.50	( 0.50)	0.99	47600.5	10200.00
24	3007.80	185.22	0.380	0.50	( 0.50)	0.99	48838.4	10300.00
25	2778.29	191.61	0.377	0.50	( 0.50)	0.99	49190.6	12010.00
26	2310.65	210.89	0.366	0.50	( 0.50)	0.99	49519.0	12000.00
27	1358.26	275.66	0.330	0.50	( 0.50)	0.99	50189.8	10100.00
TOTAL AREA (ACRES) =								50189.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 9687.08 Tc (MIN.) = 20.899  
EFFECTIVE AREA (ACRES) = 5228.20 AREA-AVERAGED Fm (INCH/HR) = 0.50  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 50189.8  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.30 = 102662.55 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12605.30 TO NODE 12605.30 IS CODE = 12  
-----  
>>>>CLEAR MEMORY BANK # 3 <<<<<<  
=====

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12605.30 TO NODE 12605.60 IS CODE = 51  
-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<<  
=====

ELEVATION DATA: UPSTREAM (FEET) = 302.00 DOWNSTREAM (FEET) = 295.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 738.76 CHANNEL SLOPE = 0.0095  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA (CFS) = 9687.08  
FLOW VELOCITY (FEET/SEC.) = 16.89 FLOW DEPTH (FEET) = 13.83  
TRAVEL TIME (MIN.) = 0.73 Tc (MIN.) = 21.63  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.60 = 103401.31 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12605.60 TO NODE 12605.60 IS CODE = 15.1  
-----  
>>>>DEFINE MEMORY BANK # 3 <<<<<<  
=====

PEAK FLOWRATE TABLE FILE NAME: 0610405U.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
---------------	---------	-----------	-------------------	----	------------	----------------

1	55.77	15.36	0.50	( 0.50)	1.00	76.3	40510.00
2	54.01	17.32	0.50	( 0.50)	1.00	81.4	40500.00
TOTAL AREA (ACRES) = 81.4							

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.60 TO NODE 12605.60 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<<  
=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9687.08	21.63	1.087	0.50 ( 0.50)	0.99	5228.2	40430.00
2	9683.45	22.14	1.072	0.50 ( 0.50)	0.99	5351.3	40440.00
3	9682.56	22.26	1.069	0.50 ( 0.50)	0.99	5379.0	600.00
4	9668.37	23.83	1.023	0.50 ( 0.50)	0.99	5801.8	40400.00
5	9668.20	23.85	1.023	0.50 ( 0.50)	0.99	5807.3	40420.00
6	9667.79	23.89	1.021	0.50 ( 0.50)	0.99	5819.7	40300.00
7	9665.55	24.06	1.017	0.50 ( 0.50)	0.99	5862.0	40410.00
8	9649.89	24.98	0.990	0.50 ( 0.50)	0.99	6098.1	40200.00
9	9444.04	43.12	0.733	0.50 ( 0.50)	0.99	11149.1	40120.00
10	9386.48	49.23	0.682	0.50 ( 0.50)	0.99	12776.4	11801.00
11	9253.85	60.42	0.614	0.50 ( 0.50)	0.99	15972.7	11500.00
12	9162.76	66.04	0.594	0.50 ( 0.50)	0.99	17907.3	11701.00
13	9026.46	72.19	0.574	0.50 ( 0.50)	0.99	20016.1	11000.00
14	8724.05	88.38	0.519	0.50 ( 0.50)	0.99	26880.3	12500.00
15	8528.01	94.44	0.504	0.50 ( 0.50)	0.99	29749.1	10900.00
16	8114.02	102.74	0.488	0.50 ( 0.50)	0.99	33071.4	11130.00
17	7442.97	113.81	0.467	0.50 ( 0.50)	0.99	36743.9	11620.00
18	6396.11	128.92	0.444	0.50 ( 0.50)	0.99	41269.6	12400.00
19	5557.00	139.67	0.431	0.50 ( 0.50)	0.99	43575.8	12201.00
20	4953.00	148.43	0.421	0.50 ( 0.50)	0.99	44866.5	12111.00
21	4605.92	153.69	0.415	0.50 ( 0.50)	0.99	45612.9	10700.00
22	4040.57	163.11	0.403	0.50 ( 0.50)	0.99	46789.4	12261.00
23	3574.82	171.76	0.393	0.50 ( 0.50)	0.99	47600.5	10200.00
24	3007.80	186.20	0.380	0.50 ( 0.50)	0.99	48838.4	10300.00
25	2778.29	192.60	0.376	0.50 ( 0.50)	0.99	49190.6	12010.00
26	2310.65	211.93	0.365	0.50 ( 0.50)	0.99	49519.0	12000.00
27	1358.26	276.85	0.330	0.50 ( 0.50)	0.99	50189.8	10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.60 = 103401.31 FEET.							

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	55.77	15.36	1.311	0.50 ( 0.50)	1.00	76.3	40510.00
2	54.01	17.32	1.237	0.50 ( 0.50)	1.00	81.4	40500.00
LONGEST FLOWPATH FROM NODE 40500.00 TO NODE 12605.60 = 4091.00 FEET.							

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9539.22	15.36	1.311	0.50 ( 0.50)	0.99	3789.7	40510.00
2	9741.09	17.32	1.237	0.50 ( 0.50)	0.99	4268.4	40500.00
3	9730.16	21.63	1.087	0.50 ( 0.50)	0.99	5309.6	40430.00
4	9725.42	22.14	1.072	0.50 ( 0.50)	0.99	5432.7	40440.00
5	9724.29	22.26	1.069	0.50 ( 0.50)	0.99	5460.4	600.00
6	9706.75	23.83	1.023	0.50 ( 0.50)	0.99	5883.1	40400.00

7	9706.54	23.85	1.023	0.50	(0.50)	0.99	5888.7	40420.00
8	9706.02	23.89	1.021	0.50	(0.50)	0.99	5901.1	40300.00
9	9703.44	24.06	1.017	0.50	(0.50)	0.99	5943.3	40410.00
10	9685.80	24.98	0.990	0.50	(0.50)	0.99	6179.4	40200.00
11	9461.17	43.12	0.733	0.50	(0.50)	0.99	11230.5	40120.00
12	9399.90	49.23	0.682	0.50	(0.50)	0.99	12857.8	11801.00
13	9262.23	60.42	0.614	0.50	(0.50)	0.99	16054.1	11500.00
14	9169.74	66.04	0.594	0.50	(0.50)	0.99	17988.7	11701.00
15	9031.91	72.19	0.574	0.50	(0.50)	0.99	20097.5	11000.00
16	8725.47	88.38	0.519	0.50	(0.50)	0.99	26961.6	12500.00
17	8528.40	94.44	0.504	0.50	(0.50)	0.99	29830.5	10900.00
18	8114.10	102.74	0.488	0.50	(0.50)	0.99	33152.7	11130.00
19	7443.04	113.81	0.467	0.50	(0.50)	0.99	36825.2	11620.00
20	6396.17	128.92	0.444	0.50	(0.50)	0.99	41351.0	12400.00
21	5557.07	139.67	0.431	0.50	(0.50)	0.99	43657.2	12201.00
22	4953.07	148.43	0.421	0.50	(0.50)	0.99	44947.8	12111.00
23	4605.98	153.69	0.415	0.50	(0.50)	0.99	45694.3	10700.00
24	4040.63	163.11	0.403	0.50	(0.50)	0.99	46870.7	12261.00
25	3574.88	171.76	0.393	0.50	(0.50)	0.99	47681.9	10200.00
26	3007.86	186.20	0.380	0.50	(0.50)	0.99	48919.8	10300.00
27	2778.35	192.60	0.376	0.50	(0.50)	0.99	49272.0	12010.00
28	2310.71	211.93	0.365	0.50	(0.50)	0.99	49600.4	12000.00
29	1358.31	276.85	0.330	0.50	(0.50)	0.99	50271.2	10100.00

TOTAL AREA (ACRES) = 50271.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 9741.09 Tc (MIN.) = 17.321  
EFFECTIVE AREA (ACRES) = 4268.40 AREA-AVERAGED Fm (INCH/HR) = 0.50  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 50271.2  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.60 = 103401.31 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12605.60 TO NODE 12605.60 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12605.60 TO NODE 12606.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 295.00 DOWNSTREAM (FEET) = 286.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1203.43 CHANNEL SLOPE = 0.0075  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA (CFS) = 9741.09  
FLOW VELOCITY (FEET/SEC.) = 15.48 FLOW DEPTH (FEET) = 14.48  
TRAVEL TIME (MIN.) = 1.30 Tc (MIN.) = 18.62  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104604.74 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610406U.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM	Q	Tc	Fp (Fm)	Ap	Ae	HEADWATER
NUMBER	(CFS)	(MIN.)	(INCH/HR)		(ACRES)	NODE
1	63.15	24.01	0.50 (0.50)	0.99	135.0	40600.00
TOTAL AREA (ACRES) =			135.0			

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM	Q	Tc	Intensity	Fp (Fm)	Ap	Ae	HEADWATER
NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)		(ACRES)	NODE
1	9539.22	16.66	1.262	0.50 (0.50)	0.99	3789.7	40510.00
2	9741.09	18.62	1.188	0.50 (0.50)	0.99	4268.4	40500.00
3	9730.16	22.92	1.050	0.50 (0.50)	0.99	5309.6	40430.00
4	9725.42	23.44	1.035	0.50 (0.50)	0.99	5432.7	40440.00
5	9724.29	23.56	1.031	0.50 (0.50)	0.99	5460.4	600.00
6	9706.75	25.12	0.986	0.50 (0.50)	0.99	5883.1	40400.00
7	9706.54	25.14	0.986	0.50 (0.50)	0.99	5888.7	40420.00
8	9706.02	25.19	0.985	0.50 (0.50)	0.99	5901.1	40300.00
9	9703.44	25.35	0.982	0.50 (0.50)	0.99	5943.3	40410.00
10	9685.80	26.28	0.962	0.50 (0.50)	0.99	6179.4	40200.00
11	9461.17	44.43	0.722	0.50 (0.50)	0.99	11230.5	40120.00
12	9399.90	50.53	0.673	0.50 (0.50)	0.99	12857.8	11801.00
13	9262.23	61.74	0.609	0.50 (0.50)	0.99	16054.1	11500.00
14	9169.74	67.36	0.590	0.50 (0.50)	0.99	17988.7	11701.00
15	9031.91	73.52	0.569	0.50 (0.50)	0.99	20097.5	11000.00
16	8725.47	89.71	0.514	0.50 (0.50)	0.99	26961.6	12500.00
17	8528.40	95.78	0.502	0.50 (0.50)	0.99	29830.5	10900.00
18	8114.10	104.10	0.486	0.50 (0.50)	0.99	33152.7	11130.00
19	7443.04	115.20	0.464	0.50 (0.50)	0.99	36825.2	11620.00
20	6396.17	130.36	0.443	0.50 (0.50)	0.99	41351.0	12400.00
21	5557.07	141.16	0.430	0.50 (0.50)	0.99	43657.2	12201.00
22	4953.07	149.97	0.419	0.50 (0.50)	0.99	44947.8	12111.00
23	4605.98	155.25	0.413	0.50 (0.50)	0.99	45694.3	10700.00
24	4040.63	164.72	0.401	0.50 (0.50)	0.99	46870.7	12261.00
25	3574.88	173.42	0.391	0.50 (0.50)	0.99	47681.9	10200.00
26	3007.86	187.93	0.379	0.50 (0.50)	0.99	48919.8	10300.00
27	2778.35	194.37	0.375	0.50 (0.50)	0.99	49272.0	12010.00
28	2310.71	213.79	0.364	0.50 (0.50)	0.99	49600.4	12000.00
29	1358.31	278.97	0.329	0.50 (0.50)	0.99	50271.2	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104604.74 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM	Q	Tc	Intensity	Fp (Fm)	Ap	Ae	HEADWATER
NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)		(ACRES)	NODE
1	63.15	24.01	1.018	0.50 (0.50)	0.99	135.0	40600.00
LONGEST FLOWPATH FROM NODE			40600.00	TO NODE		12606.00	= 6107.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM	Q	Tc	Intensity	Fp (Fm)	Ap	Ae	HEADWATER
NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)		(ACRES)	NODE
1	9602.36	16.66	1.262	0.50 (0.50)	0.99	3883.3	40510.00
2	9804.24	18.62	1.188	0.50 (0.50)	0.99	4373.1	40500.00



3	9793.30	22.92	1.050	0.50	( 0.50)	0.99	5438.5	40430.00
4	9788.57	23.44	1.035	0.50	( 0.50)	0.99	5564.5	40440.00
5	9787.43	23.56	1.031	0.50	( 0.50)	0.99	5592.9	600.00
6	9782.41	24.01	1.018	0.50	( 0.50)	0.99	5716.4	40600.00
7	9766.06	25.12	0.986	0.50	( 0.50)	0.99	6018.1	40400.00
8	9765.80	25.14	0.986	0.50	( 0.50)	0.99	6023.7	40420.00
9	9765.17	25.19	0.985	0.50	( 0.50)	0.99	6036.0	40300.00
10	9762.17	25.35	0.982	0.50	( 0.50)	0.99	6078.3	40410.00
11	9742.19	26.28	0.962	0.50	( 0.50)	0.99	6314.4	40200.00
12	9488.43	44.43	0.722	0.50	( 0.50)	0.99	11365.4	40120.00
13	9421.15	50.53	0.673	0.50	( 0.50)	0.99	12992.7	11801.00
14	9275.75	61.74	0.609	0.50	( 0.50)	0.99	16189.1	11500.00
15	9180.94	67.36	0.590	0.50	( 0.50)	0.99	18123.6	11701.00
16	9040.57	73.52	0.569	0.50	( 0.50)	0.99	20232.5	11000.00
17	8727.45	89.71	0.514	0.50	( 0.50)	0.99	27096.6	12500.00
18	8528.91	95.78	0.502	0.50	( 0.50)	0.99	29965.5	10900.00
19	8114.40	104.10	0.486	0.50	( 0.50)	0.99	33287.7	11130.00
20	7443.33	115.20	0.464	0.50	( 0.50)	0.99	36960.2	11620.00
21	6396.45	130.36	0.443	0.50	( 0.50)	0.99	41486.0	12400.00
22	5557.34	141.16	0.430	0.50	( 0.50)	0.99	43792.2	12201.00
23	4953.33	149.97	0.419	0.50	( 0.50)	0.99	45082.8	12111.00
24	4606.24	155.25	0.413	0.50	( 0.50)	0.99	45829.2	10700.00
25	4040.88	164.72	0.401	0.50	( 0.50)	0.99	47005.7	12261.00
26	3575.13	173.42	0.391	0.50	( 0.50)	0.99	47816.8	10200.00
27	3008.10	187.93	0.379	0.50	( 0.50)	0.99	49054.8	10300.00
28	2778.59	194.37	0.375	0.50	( 0.50)	0.99	49407.0	12010.00
29	2310.94	213.79	0.364	0.50	( 0.50)	0.99	49735.3	12000.00
30	1358.52	278.97	0.329	0.50	( 0.50)	0.99	50406.1	10100.00

TOTAL AREA (ACRES) = 50406.1

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 9804.24 Tc (MIN.) = 18.617  
EFFECTIVE AREA (ACRES) = 4373.08 AREA-AVERAGED Fm (INCH/HR) = 0.50  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 50406.1  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104604.74 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<<

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 50406.1 TC (MIN.) = 18.62  
EFFECTIVE AREA (ACRES) = 4373.08 AREA-AVERAGED Fm (INCH/HR) = 0.50  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.992  
PEAK FLOW RATE (CFS) = 9804.24

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9602.36	16.66	1.262	0.50 ( 0.50)	0.99	3883.3	40510.00
2	9804.24	18.62	1.188	0.50 ( 0.50)	0.99	4373.1	40500.00
3	9793.30	22.92	1.050	0.50 ( 0.50)	0.99	5438.5	40430.00
4	9788.57	23.44	1.035	0.50 ( 0.50)	0.99	5564.5	40440.00
5	9787.43	23.56	1.031	0.50 ( 0.50)	0.99	5592.9	600.00
6	9782.41	24.01	1.018	0.50 ( 0.50)	0.99	5716.4	40600.00

7	9766.06	25.12	0.986	0.50	( 0.50)	0.99	6018.1	40400.00
8	9765.80	25.14	0.986	0.50	( 0.50)	0.99	6023.7	40420.00
9	9765.17	25.19	0.985	0.50	( 0.50)	0.99	6036.0	40300.00
10	9762.17	25.35	0.982	0.50	( 0.50)	0.99	6078.3	40410.00
11	9742.19	26.28	0.962	0.50	( 0.50)	0.99	6314.4	40200.00
12	9488.43	44.43	0.722	0.50	( 0.50)	0.99	11365.4	40120.00
13	9421.15	50.53	0.673	0.50	( 0.50)	0.99	12992.7	11801.00
14	9275.75	61.74	0.609	0.50	( 0.50)	0.99	16189.1	11500.00
15	9180.94	67.36	0.590	0.50	( 0.50)	0.99	18123.6	11701.00
16	9040.57	73.52	0.569	0.50	( 0.50)	0.99	20232.5	11000.00
17	8727.45	89.71	0.514	0.50	( 0.50)	0.99	27096.6	12500.00
18	8528.91	95.78	0.502	0.50	( 0.50)	0.99	29965.5	10900.00
19	8114.40	104.10	0.486	0.50	( 0.50)	0.99	33287.7	11130.00
20	7443.33	115.20	0.464	0.50	( 0.50)	0.99	36960.2	11620.00
21	6396.45	130.36	0.443	0.50	( 0.50)	0.99	41486.0	12400.00
22	5557.34	141.16	0.430	0.50	( 0.50)	0.99	43792.2	12201.00
23	4953.33	149.97	0.419	0.50	( 0.50)	0.99	45082.8	12111.00
24	4606.24	155.25	0.413	0.50	( 0.50)	0.99	45829.2	10700.00
25	4040.88	164.72	0.401	0.50	( 0.50)	0.99	47005.7	12261.00
26	3575.13	173.42	0.391	0.50	( 0.50)	0.99	47816.8	10200.00
27	3008.10	187.93	0.379	0.50	( 0.50)	0.99	49054.8	10300.00
28	2778.59	194.37	0.375	0.50	( 0.50)	0.99	49407.0	12010.00
29	2310.94	213.79	0.364	0.50	( 0.50)	0.99	49735.3	12000.00
30	1358.52	278.97	0.329	0.50	( 0.50)	0.99	50406.1	10100.00

=====  
END OF RATIONAL METHOD ANALYSIS  
=====



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA 92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S27- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 5-YR RM EV APRIL 2019 ROKAMOTO \*  
\*\*\*\*\*

FILE NAME: RI05EV27.DAT  
TIME/DATE OF STUDY: 17:19 04/08/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 5.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 2.707
- 2) 10.00; 1.797
- 3) 15.00; 1.318
- 4) 20.00; 1.128
- 5) 25.00; 0.984
- 6) 30.00; 0.882
- 7) 40.00; 0.755
- 8) 50.00; 0.672
- 9) 60.00; 0.611
- 10) 90.00; 0.509
- 11) 120.00; 0.450
- 12) 180.00; 0.378
- 13) 360.00; 0.280
- 14) 1200.00; 0.123

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: ri05ev26.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9804.24	18.62	0.50 ( 0.50)	0.99	4373.1	40500.00
2	9488.43	44.43	0.50 ( 0.50)	0.99	11365.4	40120.00
3	9421.15	50.53	0.50 ( 0.50)	0.99	12992.7	11801.00
4	9275.75	61.74	0.50 ( 0.50)	0.99	16189.1	11500.00
5	9180.94	67.36	0.50 ( 0.50)	0.99	18123.6	11701.00
6	9040.57	73.52	0.50 ( 0.50)	0.99	20232.5	11000.00
7	8727.45	89.71	0.50 ( 0.50)	0.99	27096.6	12500.00
8	8528.91	95.78	0.50 ( 0.50)	0.99	29965.5	10900.00
9	8114.40	104.10	0.50 ( 0.50)	0.99	33287.7	11130.00
10	7443.33	115.20	0.50 ( 0.50)	0.99	36960.2	11620.00
11	6396.45	130.36	0.50 ( 0.50)	0.99	41486.0	12400.00
12	5557.34	141.16	0.50 ( 0.50)	0.99	43792.2	12201.00
13	4953.33	149.97	0.50 ( 0.50)	0.99	45082.8	12111.00
14	4606.24	155.25	0.50 ( 0.50)	0.99	45829.2	10700.00
15	4040.88	164.72	0.50 ( 0.50)	0.99	47005.7	12261.00
16	3575.13	173.42	0.50 ( 0.50)	0.99	47816.8	10200.00
17	3008.10	187.93	0.50 ( 0.50)	0.99	49054.8	10300.00
18	2778.59	194.37	0.50 ( 0.50)	0.99	49407.0	12010.00
19	2310.94	213.79	0.50 ( 0.50)	0.99	49735.3	12000.00
20	1358.52	278.97	0.50 ( 0.50)	0.99	50406.1	10100.00
TOTAL AREA(ACRES) =						50406.1

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9804.24	18.62	0.50 ( 0.50)	0.99	4373.1	40500.00
2	9488.43	44.43	0.50 ( 0.50)	0.99	11365.4	40120.00
3	9421.15	50.53	0.50 ( 0.50)	0.99	12992.7	11801.00
4	9275.75	61.74	0.50 ( 0.50)	0.99	16189.1	11500.00
5	9180.94	67.36	0.50 ( 0.50)	0.99	18123.6	11701.00
6	9040.57	73.52	0.50 ( 0.50)	0.99	20232.5	11000.00
7	8727.45	89.71	0.50 ( 0.50)	0.99	27096.6	12500.00
8	8528.91	95.78	0.50 ( 0.50)	0.99	29965.5	10900.00
9	8114.40	104.10	0.50 ( 0.50)	0.99	33287.7	11130.00
10	7443.33	115.20	0.50 ( 0.50)	0.99	36960.2	11620.00
11	6396.45	130.36	0.50 ( 0.50)	0.99	41486.0	12400.00
12	5557.34	141.16	0.50 ( 0.50)	0.99	43792.2	12201.00
13	4953.33	149.97	0.50 ( 0.50)	0.99	45082.8	12111.00

14 4606.24 155.25 0.50( 0.50) 0.99 45829.2 10700.00  
 15 4040.88 164.72 0.50( 0.50) 0.99 47005.7 12261.00  
 16 3575.13 173.42 0.50( 0.50) 0.99 47816.8 10200.00  
 17 3008.10 187.93 0.50( 0.50) 0.99 49054.8 10300.00  
 18 2778.59 194.37 0.50( 0.50) 0.99 49407.0 12010.00  
 19 2310.94 213.79 0.50( 0.50) 0.99 49735.3 12000.00  
 20 1358.52 278.97 0.50( 0.50) 0.99 50406.1 10100.00  
 TOTAL AREA(ACRES) = 50406.1

\*\*\*\*\*

FLOW PROCESS FROM NODE 12606.00 TO NODE 12701.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 286.00 DOWNSTREAM(FEET) = 276.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1260.19 CHANNEL SLOPE = 0.0079  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.130

SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 7.55 0.50 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 9806.38  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 15.86  
 AVERAGE FLOW DEPTH(FEET) = 14.36 TRAVEL TIME(MIN.) = 1.32  
 Tc(MIN.) = 19.94  
 SUBAREA AREA(ACRES) = 7.55 SUBAREA RUNOFF(CFS) = 4.28  
 EFFECTIVE AREA(ACRES) = 4380.63 AREA-AVERAGED Fm(INCH/HR) = 0.50  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 50413.7 PEAK FLOW RATE(CFS) = 9804.24  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 14.36 FLOW VELOCITY(FEET/SEC.) = 15.86  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12701.00 = 105864.93 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12701.00 TO NODE 12701.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 19.94  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.130

SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 0.90 0.50 0.850 -  
 USER-DEFINED - 3.40 0.50 1.000 -  
 USER-DEFINED - 0.40 0.50 0.500 -  
 USER-DEFINED - 23.00 0.50 1.000 -  
 USER-DEFINED - 3.30 0.50 1.000 -  
 USER-DEFINED - 0.40 0.50 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.989

SUBAREA AREA(ACRES) = 31.40 SUBAREA RUNOFF(CFS) = 17.96  
 EFFECTIVE AREA(ACRES) = 4412.03 AREA-AVERAGED Fm(INCH/HR) = 0.50  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 50445.1 PEAK FLOW RATE(CFS) = 9804.24  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12701.00 TO NODE 12701.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 19.94  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.130  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 1.70 0.50 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 1.70 SUBAREA RUNOFF(CFS) = 0.96  
 EFFECTIVE AREA(ACRES) = 4413.73 AREA-AVERAGED Fm(INCH/HR) = 0.50  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 50446.8 PEAK FLOW RATE(CFS) = 9804.24  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12701.00 TO NODE 12720.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 276.00 DOWNSTREAM(FEET) = 275.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 147.65 CHANNEL SLOPE = 0.0068  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.125

SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 1.49 0.50 0.850 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.850  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 9804.71  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 14.94  
 AVERAGE FLOW DEPTH(FEET) = 14.79 TRAVEL TIME(MIN.) = 0.16  
 Tc(MIN.) = 20.11  
 SUBAREA AREA(ACRES) = 1.49 SUBAREA RUNOFF(CFS) = 0.94  
 EFFECTIVE AREA(ACRES) = 4415.22 AREA-AVERAGED Fm(INCH/HR) = 0.50  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 50448.3 PEAK FLOW RATE(CFS) = 9804.24  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 14.79 FLOW VELOCITY(FEET/SEC.) = 14.94  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.00 = 106012.58 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12701.00 TO NODE 12720.00 IS CODE = 1

-----  
>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<  
-----

TOTAL NUMBER OF STREAMS = 2  
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
TIME OF CONCENTRATION(MIN.) = 20.11  
RAINFALL INTENSITY(INCH/HR) = 1.12  
AREA-AVERAGED Fm(INCH/HR) = 0.50  
AREA-AVERAGED Fp(INCH/HR) = 0.50  
AREA-AVERAGED Ap = 0.99  
EFFECTIVE STREAM AREA(ACRES) = 4415.22  
TOTAL STREAM AREA(ACRES) = 50448.27  
PEAK FLOW RATE(CFS) AT CONFLUENCE = 9804.24

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12710.00 TO NODE 12711.00 IS CODE = 21  
-----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<  
-----

INITIAL SUBAREA FLOW-LENGTH(FEET) = 943.56  
ELEVATION DATA: UPSTREAM(FEET) = 940.78 DOWNSTREAM(FEET) = 657.79

$T_c = K * [(LENGTH ** 3.00) / (ELEVATION CHANGE)] ** 0.20$   
SUBAREA ANALYSIS USED MINIMUM  $T_c$ (MIN.) = 13.910  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.422  
SUBAREA  $T_c$  AND LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  $T_c$   
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)  
NATURAL FAIR COVER  
"GRASS" - 6.56 0.50 1.000 0 13.91  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA RUNOFF(CFS) = 5.45  
TOTAL AREA(ACRES) = 6.56 PEAK FLOW RATE(CFS) = 5.45

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12711.00 TO NODE 12712.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<  
-----

ELEVATION DATA: UPSTREAM(FEET) = 657.79 DOWNSTREAM(FEET) = 585.63  
CHANNEL LENGTH THRU SUBAREA(FEET) = 766.00 CHANNEL SLOPE = 0.0942  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.256  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 26.94 0.50 1.000 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 14.64  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.70  
AVERAGE FLOW DEPTH(FEET) = 1.02 TRAVEL TIME(MIN.) = 2.72  
 $T_c$ (MIN.) = 16.63  
SUBAREA AREA(ACRES) = 26.94 SUBAREA RUNOFF(CFS) = 18.33

EFFECTIVE AREA(ACRES) = 33.50 AREA-AVERAGED Fm(INCH/HR) = 0.50  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 33.5 PEAK FLOW RATE(CFS) = 22.79

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 1.20 FLOW VELOCITY(FEET/SEC.) = 5.25  
LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12712.00 = 1709.56 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12712.00 TO NODE 12713.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<  
-----

ELEVATION DATA: UPSTREAM(FEET) = 585.63 DOWNSTREAM(FEET) = 463.75  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1025.79 CHANNEL SLOPE = 0.1188  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.150  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 14.73 0.50 0.100 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 30.07  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.13  
AVERAGE FLOW DEPTH(FEET) = 1.28 TRAVEL TIME(MIN.) = 2.79  
 $T_c$ (MIN.) = 19.42  
SUBAREA AREA(ACRES) = 14.73 SUBAREA RUNOFF(CFS) = 14.58  
EFFECTIVE AREA(ACRES) = 48.23 AREA-AVERAGED Fm(INCH/HR) = 0.36  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.73  
TOTAL AREA(ACRES) = 48.2 PEAK FLOW RATE(CFS) = 34.18

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 1.34 FLOW VELOCITY(FEET/SEC.) = 6.35  
LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12713.00 = 2735.35 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12713.00 TO NODE 12714.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<  
-----

ELEVATION DATA: UPSTREAM(FEET) = 463.75 DOWNSTREAM(FEET) = 360.30  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1148.54 CHANNEL SLOPE = 0.0901  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.067  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 105.64 0.50 0.100 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 82.40  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.11  
AVERAGE FLOW DEPTH(FEET) = 1.97 TRAVEL TIME(MIN.) = 2.69

Tc(MIN.) = 22.11  
 SUBAREA AREA(ACRES) = 105.64 SUBAREA RUNOFF(CFS) = 96.71  
 EFFECTIVE AREA(ACRES) = 153.87 AREA-AVERAGED Fm(INCH/HR) = 0.15  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.30  
 TOTAL AREA(ACRES) = 153.9 PEAK FLOW RATE(CFS) = 127.29

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 2.32 FLOW VELOCITY(FEET/SEC.) = 7.91  
 LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12714.00 = 3883.89 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12714.00 TO NODE 12720.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 360.30 DOWNSTREAM(FEET) = 275.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1314.99 CHANNEL SLOPE = 0.0649  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00

\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.984

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	127.13	0.50	0.100	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 180.76

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.63

AVERAGE FLOW DEPTH(FEET) = 2.81 TRAVEL TIME(MIN.) = 2.87

Tc(MIN.) = 24.98

SUBAREA AREA(ACRES) = 127.13 SUBAREA RUNOFF(CFS) = 106.92

EFFECTIVE AREA(ACRES) = 281.00 AREA-AVERAGED Fm(INCH/HR) = 0.10

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.21

TOTAL AREA(ACRES) = 281.0 PEAK FLOW RATE(CFS) = 222.75

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 3.04 FLOW VELOCITY(FEET/SEC.) = 8.04  
 LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12720.00 = 5198.88 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.00 IS CODE = 1  
 -----

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:

TIME OF CONCENTRATION(MIN.) = 24.98

RAINFALL INTENSITY(INCH/HR) = 0.98

AREA-AVERAGED Fm(INCH/HR) = 0.10

AREA-AVERAGED Fp(INCH/HR) = 0.50

AREA-AVERAGED Ap = 0.21

EFFECTIVE STREAM AREA(ACRES) = 281.00

TOTAL STREAM AREA(ACRES) = 281.00

PEAK FLOW RATE(CFS) AT CONFLUENCE = 222.75

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	9804.24	20.11	1.125	0.50( 0.50)	0.99	4415.2	40500.00
1	9488.43	45.93	0.706	0.50( 0.50)	0.99	11407.6	40120.00
1	9421.15	52.04	0.660	0.50( 0.50)	0.99	13034.9	11801.00
1	9275.75	63.25	0.600	0.50( 0.50)	0.99	16231.2	11500.00
1	9180.94	68.87	0.581	0.50( 0.50)	0.99	18165.8	11701.00
1	9040.57	75.04	0.560	0.50( 0.50)	0.99	20274.6	11000.00
1	8727.45	91.24	0.507	0.50( 0.50)	0.99	27138.8	12500.00
1	8528.91	97.32	0.495	0.50( 0.50)	0.99	30007.6	10900.00
1	8114.40	105.66	0.478	0.50( 0.50)	0.99	33329.8	11130.00
1	7443.33	116.80	0.456	0.50( 0.50)	0.99	37002.3	11620.00
1	6396.45	132.02	0.436	0.50( 0.50)	0.99	41528.1	12400.00
1	5557.34	142.88	0.423	0.50( 0.50)	0.99	43834.3	12201.00
1	4953.33	151.73	0.412	0.50( 0.50)	0.99	45124.9	12111.00
1	4606.24	157.05	0.406	0.50( 0.50)	0.99	45871.4	10700.00
1	4040.88	166.58	0.394	0.50( 0.50)	0.99	47047.8	12261.00
1	3575.13	175.34	0.384	0.50( 0.50)	0.99	47859.0	10200.00
1	3008.10	189.94	0.373	0.50( 0.50)	0.99	49096.9	10300.00
1	2778.59	196.41	0.369	0.50( 0.50)	0.99	49449.1	12010.00
1	2310.94	215.93	0.358	0.50( 0.50)	0.99	49777.5	12000.00
1	1358.52	281.41	0.323	0.50( 0.50)	0.99	50448.3	10100.00
2	222.75	24.98	0.984	0.50( 0.10)	0.21	281.0	12710.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	10012.09	20.11	1.125	0.50( 0.48)	0.95	4641.4	40500.00
2	9967.34	24.98	0.984	0.50( 0.48)	0.96	6017.0	12710.00
3	9640.70	45.93	0.706	0.50( 0.49)	0.97	11688.6	40120.00
4	9561.73	52.04	0.660	0.50( 0.49)	0.98	13315.9	11801.00
5	9401.26	63.25	0.600	0.50( 0.49)	0.98	16512.2	11500.00
6	9301.62	68.87	0.581	0.50( 0.49)	0.98	18446.8	11701.00
7	9155.94	75.04	0.560	0.50( 0.49)	0.98	20555.6	11000.00
8	8829.34	91.24	0.507	0.50( 0.49)	0.99	27419.8	12500.00
9	8628.06	97.32	0.495	0.50( 0.49)	0.99	30288.6	10900.00
10	8210.27	105.66	0.478	0.50( 0.49)	0.99	33610.8	11130.00
11	7534.81	116.80	0.456	0.50( 0.49)	0.99	37283.3	11620.00
12	6483.77	132.02	0.436	0.50( 0.49)	0.99	41809.1	12400.00
13	5642.05	142.88	0.423	0.50( 0.49)	0.99	44115.3	12201.00
14	5035.91	151.73	0.412	0.50( 0.49)	0.99	45405.9	12111.00
15	4687.54	157.05	0.406	0.50( 0.49)	0.99	46152.4	10700.00
16	4119.89	166.58	0.394	0.50( 0.49)	0.99	47328.8	12261.00
17	3652.03	175.34	0.384	0.50( 0.49)	0.99	48140.0	10200.00
18	3082.79	189.94	0.373	0.50( 0.49)	0.99	49377.9	10300.00
19	2852.58	196.41	0.369	0.50( 0.49)	0.99	49730.1	12010.00
20	2382.79	215.93	0.358	0.50( 0.49)	0.99	50058.5	12000.00
21	1423.23	281.41	0.323	0.50( 0.49)	0.99	50729.3	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:  
 PEAK FLOW RATE(CFS) = 10012.09 Tc(MIN.) = 20.11  
 EFFECTIVE AREA(ACRES) = 4641.36 AREA-AVERAGED Fm(INCH/HR) = 0.48  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.95  
 TOTAL AREA(ACRES) = 50729.3  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.00 = 106012.58 FEET.

```

*****
FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 20.11
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.125
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS
LAND USE            GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED        -         3.80   0.50  1.000  -
USER-DEFINED        -         0.40   0.50  0.850  -
USER-DEFINED        -         0.20   0.50  0.500  -
USER-DEFINED        -         0.10   0.50  1.000  -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.964
SUBAREA AREA(ACRES) = 4.50   SUBAREA RUNOFF(CFS) = 2.60
EFFECTIVE AREA(ACRES) = 4645.86   AREA-AVERAGED Fm(INCH/HR) = 0.48
AREA-AVERAGED Fp(INCH/HR) = 0.50   AREA-AVERAGED Ap = 0.95
TOTAL AREA(ACRES) = 50733.8   PEAK FLOW RATE(CFS) = 10012.09
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.50 IS CODE = 51
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 275.00   DOWNSTREAM(FEET) = 258.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 2669.21   CHANNEL SLOPE = 0.0064
CHANNEL BASE(FEET) = 0.00   "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030   MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.038
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS
LAND USE            GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED        -        62.15   0.50  0.100  -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 10039.72
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 14.69
AVERAGE FLOW DEPTH(FEET) = 15.10   TRAVEL TIME(MIN.) = 3.03
Tc(MIN.) = 23.14
SUBAREA AREA(ACRES) = 62.15   SUBAREA RUNOFF(CFS) = 55.25
EFFECTIVE AREA(ACRES) = 4708.01   AREA-AVERAGED Fm(INCH/HR) = 0.47
AREA-AVERAGED Fp(INCH/HR) = 0.50   AREA-AVERAGED Ap = 0.94
TOTAL AREA(ACRES) = 50795.9   PEAK FLOW RATE(CFS) = 10012.09
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 15.08   FLOW VELOCITY(FEET/SEC.) = 14.67
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108681.79 FEET.

```

```

*****
FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

```

```

=====
MAINLINE Tc(MIN.) = 23.14
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.038
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS
LAND USE            GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED        -         0.10   0.50  0.100  -
USER-DEFINED        -         0.70   0.50  1.000  -
USER-DEFINED        -         0.30   0.50  1.000  -
USER-DEFINED        -        17.90   0.50  1.000  -
USER-DEFINED        -         0.20   0.50  1.000  -
USER-DEFINED        -         0.30   0.50  0.850  -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.993
SUBAREA AREA(ACRES) = 19.50   SUBAREA RUNOFF(CFS) = 9.49
EFFECTIVE AREA(ACRES) = 4727.51   AREA-AVERAGED Fm(INCH/HR) = 0.47
AREA-AVERAGED Fp(INCH/HR) = 0.50   AREA-AVERAGED Ap = 0.94
TOTAL AREA(ACRES) = 50815.4   PEAK FLOW RATE(CFS) = 10012.09
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====

```

```

MAINLINE Tc(MIN.) = 23.14
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.038
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS
LAND USE            GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED        -         0.10   0.50  0.500  -
USER-DEFINED        -         1.10   0.50  1.000  -
USER-DEFINED        -         0.90   0.50  1.000  -
USER-DEFINED        -         0.60   0.50  0.900  -
USER-DEFINED        -         0.30   0.50  0.900  -
USER-DEFINED        -         0.50   0.50  1.000  -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.960
SUBAREA AREA(ACRES) = 3.50   SUBAREA RUNOFF(CFS) = 1.76
EFFECTIVE AREA(ACRES) = 4731.01   AREA-AVERAGED Fm(INCH/HR) = 0.47
AREA-AVERAGED Fp(INCH/HR) = 0.50   AREA-AVERAGED Ap = 0.94
TOTAL AREA(ACRES) = 50818.9   PEAK FLOW RATE(CFS) = 10012.09
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 15.1
-----

```

```

>>>>DEFINE MEMORY BANK # 2 <<<<
=====
PEAK FLOWRATE TABLE FILE NAME: 3D05EVRL.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:
STREAM      Q      Tc      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)      (MIN.)      (INCH/HR)      (ACRES)      NODE
1          334.99    23.52    0.50( 0.24)  0.48    353.3    413.00
2          322.72    31.24    0.50( 0.24)  0.48    430.1    430.00
3          307.23    33.60    0.50( 0.24)  0.48    439.5    400.00
TOTAL AREA(ACRES) = 439.5

```

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	10012.09	23.14	1.038	0.50 ( 0.47)	0.94	4731.0	40500.00
2	9967.34	28.02	0.922	0.50 ( 0.47)	0.95	6106.6	12710.00
3	9640.70	48.99	0.680	0.50 ( 0.48)	0.97	11778.2	40120.00
4	9561.73	55.10	0.641	0.50 ( 0.49)	0.97	13405.5	11801.00
5	9401.26	66.32	0.589	0.50 ( 0.49)	0.98	16601.9	11500.00
6	9301.62	71.96	0.570	0.50 ( 0.49)	0.98	18536.4	11701.00
7	9155.94	78.13	0.549	0.50 ( 0.49)	0.98	20645.3	11000.00
8	8829.34	94.37	0.500	0.50 ( 0.49)	0.98	27509.4	12500.00
9	8628.06	100.47	0.488	0.50 ( 0.49)	0.99	30378.3	10900.00
10	8210.27	108.84	0.472	0.50 ( 0.49)	0.99	33700.5	11130.00
11	7534.81	120.05	0.450	0.50 ( 0.49)	0.99	37373.0	11620.00
12	6483.77	135.40	0.432	0.50 ( 0.49)	0.99	41898.8	12400.00
13	5642.05	146.38	0.418	0.50 ( 0.49)	0.99	44205.0	12201.00
14	5035.91	155.33	0.408	0.50 ( 0.49)	0.99	45495.6	12111.00
15	4687.54	160.71	0.401	0.50 ( 0.49)	0.99	46242.0	10700.00
16	4119.89	170.37	0.390	0.50 ( 0.49)	0.99	47418.5	12261.00
17	3652.03	179.24	0.379	0.50 ( 0.49)	0.99	48229.6	10200.00
18	3082.79	194.00	0.370	0.50 ( 0.49)	0.99	49467.5	10300.00
19	2852.58	200.56	0.367	0.50 ( 0.49)	0.99	49819.8	12010.00
20	2382.79	220.26	0.356	0.50 ( 0.49)	0.99	50148.1	12000.00
21	1423.23	286.34	0.320	0.50 ( 0.49)	0.99	50818.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108681.79 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	334.99	23.52	1.027	0.50 ( 0.24)	0.48	353.3	413.00
2	322.72	31.24	0.866	0.50 ( 0.24)	0.48	430.1	430.00
3	307.23	33.60	0.836	0.50 ( 0.24)	0.48	439.5	400.00

LONGEST FLOWPATH FROM NODE 430.00 TO NODE 12720.50 = 11352.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	10346.23	23.14	1.038	0.50 ( 0.46)	0.91	5078.6	40500.00
2	10343.55	23.52	1.027	0.50 ( 0.46)	0.91	5192.8	413.00
3	10295.18	28.02	0.922	0.50 ( 0.46)	0.92	6504.6	12710.00
4	10239.85	31.24	0.866	0.50 ( 0.46)	0.92	7408.5	430.00
5	10187.62	33.60	0.836	0.50 ( 0.46)	0.93	8055.9	400.00
6	9867.71	48.99	0.680	0.50 ( 0.48)	0.95	12217.7	40120.00
7	9768.40	55.10	0.641	0.50 ( 0.48)	0.96	13845.0	11801.00
8	9581.48	66.32	0.589	0.50 ( 0.48)	0.96	17041.4	11500.00
9	9471.98	71.96	0.570	0.50 ( 0.48)	0.97	18975.9	11701.00
10	9315.50	78.13	0.549	0.50 ( 0.48)	0.97	21084.8	11000.00
11	8963.71	94.37	0.500	0.50 ( 0.49)	0.98	27948.9	12500.00
12	8759.16	100.47	0.488	0.50 ( 0.49)	0.98	30817.8	10900.00
13	8336.95	108.84	0.472	0.50 ( 0.49)	0.98	34140.0	11130.00
14	7655.58	120.05	0.450	0.50 ( 0.49)	0.98	37812.5	11620.00
15	6599.60	135.40	0.432	0.50 ( 0.49)	0.98	42338.3	12400.00

16	5754.34	146.38	0.418	0.50 ( 0.49)	0.98	44644.5	12201.00
17	5145.32	155.33	0.408	0.50 ( 0.49)	0.98	45935.1	12111.00
18	4795.22	160.71	0.401	0.50 ( 0.49)	0.98	46681.5	10700.00
19	4224.45	170.37	0.390	0.50 ( 0.49)	0.98	47858.0	12261.00
20	3753.74	179.24	0.379	0.50 ( 0.49)	0.98	48669.1	10200.00
21	3182.21	194.00	0.370	0.50 ( 0.49)	0.98	49907.0	10300.00
22	2951.03	200.56	0.367	0.50 ( 0.49)	0.98	50259.2	12010.00
23	2478.37	220.26	0.356	0.50 ( 0.49)	0.98	50587.6	12000.00
24	1509.15	286.34	0.320	0.50 ( 0.49)	0.98	51258.4	10100.00

TOTAL AREA (ACRES) = 51258.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 10346.23 Tc (MIN.) = 23.135  
EFFECTIVE AREA (ACRES) = 5078.55 AREA-AVERAGED Fm (INCH/HR) = 0.46  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.91  
TOTAL AREA (ACRES) = 51258.4  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108681.79 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.50 TO NODE 12721.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 258.00 DOWNSTREAM (FEET) = 256.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 438.77 CHANNEL SLOPE = 0.0046  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA (CFS) = 10346.23  
FLOW VELOCITY (FEET/SEC.) = 13.05 FLOW DEPTH (FEET) = 16.26  
TRAVEL TIME (MIN.) = 0.56 Tc (MIN.) = 23.70  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12721.00 = 109120.56 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12721.00 TO NODE 12722.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 256.00 DOWNSTREAM (FEET) = 255.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 830.42 CHANNEL SLOPE = 0.0012  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00

==>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL  
CAPACITY ( NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM  
ALLOWABLE DEPTH).  
AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM  
ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.978  
SUBAREA LOSS RATE DATA (AMC II):



DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 11.24 0.50 0.100 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 10350.92  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.63  
 AVERAGE FLOW DEPTH(FEET) = 20.00 TRAVEL TIME(MIN.) = 1.60  
 Tc(MIN.) = 25.30  
 SUBAREA AREA(ACRES) = 11.24 SUBAREA RUNOFF(CFS) = 9.39  
 EFFECTIVE AREA(ACRES) = 5089.79 AREA-AVERAGED Fm(INCH/HR) = 0.45  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.91  
 TOTAL AREA(ACRES) = 51269.7 PEAK FLOW RATE(CFS) = 10346.23  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

====>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL  
 CAPACITY( NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM  
 ALLOWABLE DEPTH).  
 AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM  
 ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 20.00 FLOW VELOCITY(FEET/SEC.) = 8.62

==>FLOWDEPTH EXCEEDS MAXIMUM ALLOWABLE DEPTH

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12722.00 = 109950.98 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12722.00 TO NODE 12722.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<  
 =====

MAINLINE Tc(MIN.) = 25.30  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.978  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 2.10 0.50 1.000 -  
 USER-DEFINED - 0.10 0.50 1.000 -  
 USER-DEFINED - 3.60 0.50 1.000 -  
 USER-DEFINED - 4.10 0.50 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 9.90 SUBAREA RUNOFF(CFS) = 4.26  
 EFFECTIVE AREA(ACRES) = 5099.69 AREA-AVERAGED Fm(INCH/HR) = 0.45  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.91  
 TOTAL AREA(ACRES) = 51279.6 PEAK FLOW RATE(CFS) = 10346.23  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12722.00 TO NODE 12722.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<  
 =====

MAINLINE Tc(MIN.) = 25.30  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.978

SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 0.60 0.50 0.900 -  
 USER-DEFINED - 1.90 0.50 1.000 -  
 USER-DEFINED - 0.10 0.50 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.977  
 SUBAREA AREA(ACRES) = 2.60 SUBAREA RUNOFF(CFS) = 1.14  
 EFFECTIVE AREA(ACRES) = 5102.29 AREA-AVERAGED Fm(INCH/HR) = 0.45  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.91  
 TOTAL AREA(ACRES) = 51282.2 PEAK FLOW RATE(CFS) = 10346.23  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12722.00 TO NODE 12740.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 255.00 DOWNSTREAM(FEET) = 252.10  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 624.00 CHANNEL SLOPE = 0.0046  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.962

SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 1.50 0.50 0.100 -  
 USER-DEFINED - 2.50 0.50 1.000 -  
 USER-DEFINED - 0.50 0.50 1.000 -  
 USER-DEFINED - 0.70 0.50 1.000 -  
 USER-DEFINED - 6.20 0.50 1.000 -  
 USER-DEFINED - 6.50 0.50 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.925  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 10350.25  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 13.15  
 AVERAGE FLOW DEPTH(FEET) = 16.20 TRAVEL TIME(MIN.) = 0.79  
 Tc(MIN.) = 26.09  
 SUBAREA AREA(ACRES) = 17.90 SUBAREA RUNOFF(CFS) = 8.04  
 EFFECTIVE AREA(ACRES) = 5120.19 AREA-AVERAGED Fm(INCH/HR) = 0.45  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.91  
 TOTAL AREA(ACRES) = 51300.1 PEAK FLOW RATE(CFS) = 10346.23  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 16.19 FLOW VELOCITY(FEET/SEC.) = 13.15  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12740.00 = 110574.98 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<  
 =====

MAINLINE Tc(MIN.) = 26.09  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.962  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	4.70	0.50	1.000	-
USER-DEFINED	-	6.70	0.50	1.000	-
USER-DEFINED	-	12.00	0.50	1.000	-
USER-DEFINED	-	0.80	0.50	1.000	-
USER-DEFINED	-	20.20	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 44.40 SUBAREA RUNOFF (CFS) = 18.44  
EFFECTIVE AREA (ACRES) = 5164.59 AREA-AVERAGED Fm (INCH/HR) = 0.45  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.91  
TOTAL AREA (ACRES) = 51344.4 PEAK FLOW RATE (CFS) = 10346.23  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
TIME OF CONCENTRATION (MIN.) = 26.09  
RAINFALL INTENSITY (INCH/HR) = 0.96  
AREA-AVERAGED Fm (INCH/HR) = 0.45  
AREA-AVERAGED Fp (INCH/HR) = 0.50  
AREA-AVERAGED Ap = 0.91  
EFFECTIVE STREAM AREA (ACRES) = 5164.59  
TOTAL STREAM AREA (ACRES) = 51344.45  
PEAK FLOW RATE (CFS) AT CONFLUENCE = 10346.23

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12730.00 TO NODE 12731.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH (FEET) = 561.54  
ELEVATION DATA: UPSTREAM (FEET) = 613.29 DOWNSTREAM (FEET) = 551.75

Tc = K \* [(LENGTH \*\* 3.00) / (ELEVATION CHANGE)] \*\* 0.20  
SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 13.823  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.431  
SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER						
"CHAPARRAL, BROADLEAF"	-	6.33	0.50	1.000	0	13.82

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA RUNOFF (CFS) = 5.30  
TOTAL AREA (ACRES) = 6.33 PEAK FLOW RATE (CFS) = 5.30

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12731.00 TO NODE 12732.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 551.75 DOWNSTREAM (FEET) = 494.40  
CHANNEL LENGTH THRU SUBAREA (FEET) = 971.91 CHANNEL SLOPE = 0.0590  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.224  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	34.62	0.50	0.100	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 23.49  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.42  
AVERAGE FLOW DEPTH (FEET) = 1.33 TRAVEL TIME (MIN.) = 3.66  
Tc (MIN.) = 17.48  
SUBAREA AREA (ACRES) = 34.62 SUBAREA RUNOFF (CFS) = 36.57  
EFFECTIVE AREA (ACRES) = 40.95 AREA-AVERAGED Fm (INCH/HR) = 0.12  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.24  
TOTAL AREA (ACRES) = 40.9 PEAK FLOW RATE (CFS) = 40.69

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 1.64 FLOW VELOCITY (FEET/SEC.) = 5.07  
LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12732.00 = 1533.45 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12732.00 TO NODE 12733.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 494.40 DOWNSTREAM (FEET) = 431.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1156.41 CHANNEL SLOPE = 0.0548  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.102  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	59.52	0.50	0.100	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 68.87  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.63  
AVERAGE FLOW DEPTH (FEET) = 2.02 TRAVEL TIME (MIN.) = 3.42  
Tc (MIN.) = 20.91  
SUBAREA AREA (ACRES) = 59.52 SUBAREA RUNOFF (CFS) = 56.35  
EFFECTIVE AREA (ACRES) = 100.47 AREA-AVERAGED Fm (INCH/HR) = 0.08  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.16  
TOTAL AREA (ACRES) = 100.5 PEAK FLOW RATE (CFS) = 92.55

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 2.26 FLOW VELOCITY (FEET/SEC.) = 6.06  
LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12733.00 = 2689.86 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12733.00 TO NODE 12734.00 IS CODE = 51

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 431.00 DOWNSTREAM(FEET) = 367.10
CHANNEL LENGTH THRU SUBAREA(FEET) = 1654.48 CHANNEL SLOPE = 0.0386
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.968
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 64.05 0.50 0.100 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 119.03
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.67
AVERAGE FLOW DEPTH(FEET) = 2.64 TRAVEL TIME(MIN.) = 4.86
Tc(MIN.) = 25.77
SUBAREA AREA(ACRES) = 64.05 SUBAREA RUNOFF(CFS) = 52.94
EFFECTIVE AREA(ACRES) = 164.52 AREA-AVERAGED Fm(INCH/HR) = 0.07
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.13
TOTAL AREA(ACRES) = 164.5 PEAK FLOW RATE(CFS) = 133.41

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 2.76 FLOW VELOCITY(FEET/SEC.) = 5.82
LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12734.00 = 4344.34 FEET.

```

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12734.00 TO NODE 12740.00 IS CODE = 51

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 367.11 DOWNSTREAM(FEET) = 252.10
CHANNEL LENGTH THRU SUBAREA(FEET) = 1880.98 CHANNEL SLOPE = 0.0611
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.879
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 26.02 0.50 0.100 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 143.12
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.03
AVERAGE FLOW DEPTH(FEET) = 2.60 TRAVEL TIME(MIN.) = 4.46
Tc(MIN.) = 30.23
SUBAREA AREA(ACRES) = 26.02 SUBAREA RUNOFF(CFS) = 19.42
EFFECTIVE AREA(ACRES) = 190.54 AREA-AVERAGED Fm(INCH/HR) = 0.06
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.13
TOTAL AREA(ACRES) = 190.5 PEAK FLOW RATE(CFS) = 139.62

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 2.58 FLOW VELOCITY(FEET/SEC.) = 7.01
LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12740.00 = 6225.32 FEET.

```

\*\*\*\*\*

FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 1

```

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<
=====

```

```

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 30.23
RAINFALL INTENSITY(INCH/HR) = 0.88
AREA-AVERAGED Fm(INCH/HR) = 0.06
AREA-AVERAGED Fp(INCH/HR) = 0.50
AREA-AVERAGED Ap = 0.13
EFFECTIVE STREAM AREA(ACRES) = 190.54
TOTAL STREAM AREA(ACRES) = 190.54
PEAK FLOW RATE(CFS) AT CONFLUENCE = 139.62

```

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	10346.23	26.09	0.962	0.50( 0.45)	0.91	5164.6	40500.00
1	10343.55	26.48	0.954	0.50( 0.46)	0.91	5278.9	413.00
1	10295.18	30.98	0.870	0.50( 0.46)	0.92	6590.7	12710.00
1	10239.85	34.22	0.828	0.50( 0.46)	0.92	7494.6	430.00
1	10187.62	36.58	0.798	0.50( 0.46)	0.93	8141.9	400.00
1	9867.71	52.04	0.660	0.50( 0.48)	0.95	12303.8	40120.00
1	9768.40	58.17	0.622	0.50( 0.48)	0.96	13931.1	11801.00
1	9581.48	69.44	0.579	0.50( 0.48)	0.96	17127.4	11500.00
1	9471.98	75.09	0.560	0.50( 0.48)	0.97	19062.0	11701.00
1	9315.50	81.30	0.539	0.50( 0.48)	0.97	21170.8	11000.00
1	8963.71	97.58	0.494	0.50( 0.49)	0.98	28034.9	12500.00
1	8759.16	103.70	0.482	0.50( 0.49)	0.98	30903.8	10900.00
1	8336.95	112.11	0.466	0.50( 0.49)	0.98	34226.0	11130.00
1	7655.58	123.39	0.446	0.50( 0.49)	0.98	37898.5	11620.00
1	6599.60	138.86	0.427	0.50( 0.49)	0.98	42424.3	12400.00
1	5754.34	149.96	0.414	0.50( 0.49)	0.98	44730.5	12201.00
1	5145.32	159.02	0.403	0.50( 0.49)	0.98	46021.1	12111.00
1	4795.22	164.46	0.397	0.50( 0.49)	0.98	46767.6	10700.00
1	4224.45	174.24	0.385	0.50( 0.49)	0.98	47944.0	12261.00
1	3753.74	183.23	0.376	0.50( 0.49)	0.98	48755.2	10200.00
1	3182.21	198.16	0.368	0.50( 0.49)	0.98	49993.1	10300.00
1	2951.03	204.80	0.364	0.50( 0.49)	0.98	50345.3	12010.00
1	2478.37	224.69	0.354	0.50( 0.49)	0.98	50673.7	12000.00
1	1509.15	291.36	0.317	0.50( 0.49)	0.98	51344.4	10100.00
2	139.62	30.23	0.879	0.50( 0.06)	0.13	190.5	12730.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	10478.98	26.09	0.962	0.50( 0.44)	0.89	5329.1	40500.00
2	10477.08	26.48	0.954	0.50( 0.44)	0.89	5445.8	413.00
3	10442.93	30.23	0.879	0.50( 0.45)	0.89	6560.7	12730.00
4	10433.15	30.98	0.870	0.50( 0.45)	0.89	6781.2	12710.00
5	10370.78	34.22	0.828	0.50( 0.45)	0.90	7685.1	430.00
6	10313.38	36.58	0.798	0.50( 0.45)	0.91	8332.5	400.00
7	9969.67	52.04	0.660	0.50( 0.47)	0.94	12494.3	40120.00

8	9863.95	58.17	0.622	0.50	( 0.47)	0.94	14121.6	11801.00
9	9669.61	69.44	0.579	0.50	( 0.48)	0.95	17317.9	11500.00
10	9556.82	75.09	0.560	0.50	( 0.48)	0.96	19252.5	11701.00
11	9396.71	81.30	0.539	0.50	( 0.48)	0.96	21361.4	11000.00
12	9037.43	97.58	0.494	0.50	( 0.49)	0.97	28225.5	12500.00
13	8831.09	103.70	0.482	0.50	( 0.49)	0.97	31094.3	10900.00
14	8406.41	112.11	0.466	0.50	( 0.49)	0.97	34416.6	11130.00
15	7722.12	123.39	0.446	0.50	( 0.49)	0.98	38089.1	11620.00
16	6663.37	138.86	0.427	0.50	( 0.49)	0.98	42614.8	12400.00
17	5816.12	149.96	0.414	0.50	( 0.49)	0.98	44921.0	12201.00
18	5205.48	159.02	0.403	0.50	( 0.49)	0.98	46211.7	12111.00
19	4854.40	164.46	0.397	0.50	( 0.49)	0.98	46958.1	10700.00
20	4281.89	174.24	0.385	0.50	( 0.49)	0.98	48134.6	12261.00
21	3809.88	183.23	0.376	0.50	( 0.49)	0.98	48945.7	10200.00
22	3237.13	198.16	0.368	0.50	( 0.49)	0.98	50183.6	10300.00
23	3005.42	204.80	0.364	0.50	( 0.49)	0.98	50535.8	12010.00
24	2531.14	224.69	0.354	0.50	( 0.49)	0.98	50864.2	12000.00
25	1556.51	291.36	0.317	0.50	( 0.49)	0.98	51535.0	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 10478.98 Tc(MIN.) = 26.09  
EFFECTIVE AREA(ACRES) = 5329.07 AREA-AVERAGED Fm(INCH/HR) = 0.44  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.89  
TOTAL AREA(ACRES) = 51535.0  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12740.00 = 110574.98 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12740.00 TO NODE 12741.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 252.10 DOWNSTREAM(FEET) = 247.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 401.47 CHANNEL SLOPE = 0.0127  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA(CFS) = 10478.98  
FLOW VELOCITY(FEET/SEC.) = 19.23 FLOW DEPTH(FEET) = 13.48  
TRAVEL TIME(MIN.) = 0.35 Tc(MIN.) = 26.44  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12741.00 = 110976.45 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 26.44  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.955  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	2.10	0.50	0.100	-
USER-DEFINED	-	7.50	0.50	1.000	-
USER-DEFINED	-	0.90	0.50	1.000	-
USER-DEFINED	-	1.90	0.50	0.850	-
USER-DEFINED	-	0.40	0.50	0.900	-
USER-DEFINED	-	0.50	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.833  
SUBAREA AREA(ACRES) = 13.30 SUBAREA RUNOFF(CFS) = 6.44  
EFFECTIVE AREA(ACRES) = 5342.37 AREA-AVERAGED Fm(INCH/HR) = 0.44  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.89  
TOTAL AREA(ACRES) = 51548.3 PEAK FLOW RATE(CFS) = 10478.98  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 26.44  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.955  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.90	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA(ACRES) = 0.90 SUBAREA RUNOFF(CFS) = 0.37  
EFFECTIVE AREA(ACRES) = 5343.27 AREA-AVERAGED Fm(INCH/HR) = 0.44  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.89  
TOTAL AREA(ACRES) = 51549.2 PEAK FLOW RATE(CFS) = 10478.98  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 2 <<<<

PEAK FLOWRATE TABLE FILE NAME: 3C05EVRL.DNA  
MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	530.77	20.29	0.50( 0.23)	0.46	630.1	300.00
2	531.56	25.92	0.50( 0.24)	0.47	762.1	327.00
3	518.38	27.16	0.50( 0.24)	0.47	775.6	350.00
4	499.31	28.75	0.50( 0.24)	0.48	789.3	320.00
5	456.04	32.90	0.50( 0.24)	0.48	812.4	306.00
6	365.52	46.52	0.50( 0.25)	0.50	870.6	390.00
TOTAL AREA(ACRES) =						870.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	10478.98	26.44	0.955	0.50( 0.44)	0.89	5343.3	40500.00
2	10477.08	26.82	0.947	0.50( 0.44)	0.89	5460.0	413.00
3	10442.93	30.57	0.875	0.50( 0.45)	0.89	6574.9	12730.00
4	10433.15	31.33	0.865	0.50( 0.45)	0.89	6795.4	12710.00
5	10370.78	34.57	0.824	0.50( 0.45)	0.90	7699.3	430.00
6	10313.38	36.93	0.794	0.50( 0.45)	0.91	8346.7	400.00

7	9969.67	52.39	0.657	0.50 ( 0.47)	0.94	12508.5	40120.00
8	9863.95	58.52	0.620	0.50 ( 0.47)	0.94	14135.8	11801.00
9	9669.61	69.79	0.578	0.50 ( 0.48)	0.95	17332.1	11500.00
10	9556.82	75.45	0.558	0.50 ( 0.48)	0.96	19266.7	11701.00
11	9396.71	81.66	0.537	0.50 ( 0.48)	0.96	21375.6	11000.00
12	9037.43	97.94	0.493	0.50 ( 0.49)	0.97	28239.7	12500.00
13	8831.09	104.06	0.481	0.50 ( 0.49)	0.97	31108.5	10900.00
14	8406.41	112.48	0.465	0.50 ( 0.49)	0.97	34430.8	11130.00
15	7722.12	123.77	0.445	0.50 ( 0.49)	0.98	38103.3	11620.00
16	6663.37	139.25	0.427	0.50 ( 0.49)	0.98	42629.0	12400.00
17	5816.12	150.37	0.414	0.50 ( 0.49)	0.98	44935.2	12201.00
18	5205.48	159.43	0.403	0.50 ( 0.49)	0.98	46225.9	12111.00
19	4854.40	164.89	0.396	0.50 ( 0.49)	0.98	46972.3	10700.00
20	4281.89	174.68	0.384	0.50 ( 0.49)	0.98	48148.8	12261.00
21	3809.88	183.68	0.376	0.50 ( 0.49)	0.98	48959.9	10200.00
22	3237.13	198.63	0.368	0.50 ( 0.49)	0.98	50197.8	10300.00
23	3005.42	205.27	0.364	0.50 ( 0.49)	0.98	50550.0	12010.00
24	2531.14	225.19	0.353	0.50 ( 0.49)	0.98	50878.4	12000.00
25	1556.51	291.92	0.317	0.50 ( 0.49)	0.98	51549.2	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12741.00 = 110976.45 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	530.77	20.29	1.120	0.50 ( 0.23)	0.46	630.1	300.00
2	531.56	25.92	0.965	0.50 ( 0.24)	0.47	762.1	327.00
3	518.38	27.16	0.940	0.50 ( 0.24)	0.47	775.6	350.00
4	499.31	28.75	0.907	0.50 ( 0.24)	0.48	789.3	320.00
5	456.04	32.90	0.845	0.50 ( 0.24)	0.48	812.4	306.00
6	365.52	46.52	0.701	0.50 ( 0.25)	0.50	870.6	390.00

LONGEST FLOWPATH FROM NODE 390.00 TO NODE 12741.00 = 15238.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11009.75	20.29	1.120	0.50 ( 0.41)	0.83	4730.4	300.00
2	11010.53	25.92	0.965	0.50 ( 0.42)	0.83	6000.0	327.00
3	11005.00	26.44	0.955	0.50 ( 0.42)	0.83	6111.0	40500.00
4	10999.01	26.82	0.947	0.50 ( 0.42)	0.83	6231.9	413.00
5	10992.42	27.16	0.940	0.50 ( 0.42)	0.84	6334.8	350.00
6	10958.84	28.75	0.907	0.50 ( 0.42)	0.84	6822.3	320.00
7	10923.25	30.57	0.875	0.50 ( 0.42)	0.85	7374.3	12730.00
8	10905.57	31.33	0.865	0.50 ( 0.43)	0.85	7599.0	12710.00
9	10858.88	32.90	0.845	0.50 ( 0.43)	0.86	8047.1	306.00
10	10815.76	34.57	0.824	0.50 ( 0.43)	0.86	8518.8	430.00
11	10742.62	36.93	0.794	0.50 ( 0.44)	0.87	9176.3	400.00
12	10465.73	46.52	0.701	0.50 ( 0.45)	0.90	11798.5	390.00
13	10299.84	52.39	0.657	0.50 ( 0.46)	0.91	13379.1	40120.00
14	10163.67	58.52	0.620	0.50 ( 0.46)	0.92	15006.4	11801.00
15	9934.94	69.79	0.578	0.50 ( 0.47)	0.93	18202.7	11500.00
16	9806.50	75.45	0.558	0.50 ( 0.47)	0.94	20137.3	11701.00
17	9629.21	81.66	0.537	0.50 ( 0.47)	0.94	22246.2	11000.00
18	9236.95	97.94	0.493	0.50 ( 0.48)	0.96	29110.3	12500.00
19	9025.74	104.06	0.481	0.50 ( 0.48)	0.96	31979.1	10900.00
20	8594.37	112.48	0.465	0.50 ( 0.48)	0.96	35301.4	11130.00
21	7902.27	123.77	0.445	0.50 ( 0.48)	0.97	38973.9	11620.00
22	6836.00	139.25	0.427	0.50 ( 0.48)	0.97	43499.6	12400.00
23	5983.36	150.37	0.414	0.50 ( 0.48)	0.97	45805.8	12201.00

24	5368.31	159.43	0.403	0.50 ( 0.48)	0.97	47096.5	12111.00
25	5014.59	164.89	0.396	0.50 ( 0.48)	0.97	47842.9	10700.00
26	4437.33	174.68	0.384	0.50 ( 0.48)	0.97	49019.4	12261.00
27	3961.92	183.68	0.376	0.50 ( 0.49)	0.97	49830.5	10200.00
28	3385.89	198.63	0.368	0.50 ( 0.49)	0.97	51068.4	10300.00
29	3152.71	205.27	0.364	0.50 ( 0.49)	0.97	51420.6	12010.00
30	2674.05	225.19	0.353	0.50 ( 0.49)	0.97	51749.0	12000.00
31	1684.73	291.92	0.317	0.50 ( 0.49)	0.97	52419.8	10100.00

TOTAL AREA (ACRES) = 52419.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 11010.53 Tc (MIN.) = 25.918  
EFFECTIVE AREA (ACRES) = 6000.02 AREA-AVERAGED Fm (INCH/HR) = 0.42  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.97  
TOTAL AREA (ACRES) = 52419.8  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12741.00 = 110976.45 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 12741.00 TO NODE 12800.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 247.00 DOWNSTREAM (FEET) = 240.00

CHANNEL LENGTH THRU SUBAREA (FEET) = 819.00 CHANNEL SLOPE = 0.0085

CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00

CHANNEL FLOW THRU SUBAREA (CFS) = 11010.53

FLOW VELOCITY (FEET/SEC.) = 16.78 FLOW DEPTH (FEET) = 14.79

TRAVEL TIME (MIN.) = 0.81 Tc (MIN.) = 26.73

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111795.45 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 26.73

\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.949

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	17.31	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 17.31 SUBAREA RUNOFF (CFS) = 6.99

EFFECTIVE AREA (ACRES) = 6017.33 AREA-AVERAGED Fm (INCH/HR) = 0.42

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.83

TOTAL AREA (ACRES) = 52437.1 PEAK FLOW RATE (CFS) = 11010.53

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 52437.1 TC (MIN.) = 26.73  
 EFFECTIVE AREA (ACRES) = 6017.33 AREA-AVERAGED Fm (INCH/HR) = 0.42  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.833  
 PEAK FLOW RATE (CFS) = 11010.53

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11009.75	21.10	1.096	0.50 ( 0.41)	0.83	4747.7	300.00
2	11010.53	26.73	0.949	0.50 ( 0.42)	0.83	6017.3	327.00
3	11005.00	27.25	0.938	0.50 ( 0.42)	0.83	6128.3	40500.00
4	10999.01	27.64	0.930	0.50 ( 0.42)	0.84	6249.2	413.00
5	10992.42	27.97	0.923	0.50 ( 0.42)	0.84	6352.1	350.00
6	10958.84	29.57	0.891	0.50 ( 0.42)	0.84	6839.7	320.00
7	10923.25	31.39	0.864	0.50 ( 0.42)	0.85	7391.7	12730.00
8	10905.57	32.15	0.855	0.50 ( 0.43)	0.85	7616.4	12710.00
9	10858.88	33.72	0.835	0.50 ( 0.43)	0.86	8064.4	306.00
10	10815.76	35.38	0.814	0.50 ( 0.43)	0.86	8536.1	430.00
11	10742.62	37.75	0.784	0.50 ( 0.44)	0.87	9193.6	400.00
12	10465.73	47.34	0.694	0.50 ( 0.45)	0.90	11815.8	390.00
13	10299.84	53.22	0.652	0.50 ( 0.46)	0.91	13396.4	40120.00
14	10163.67	59.35	0.615	0.50 ( 0.46)	0.92	15023.7	11801.00
15	9934.94	70.63	0.575	0.50 ( 0.47)	0.93	18220.0	11500.00
16	9806.50	76.28	0.556	0.50 ( 0.47)	0.94	20154.6	11701.00
17	9629.21	82.50	0.534	0.50 ( 0.47)	0.94	22263.5	11000.00
18	9236.95	98.79	0.492	0.50 ( 0.48)	0.96	29127.6	12500.00
19	9025.74	104.92	0.480	0.50 ( 0.48)	0.96	31996.4	10900.00
20	8594.37	113.34	0.463	0.50 ( 0.48)	0.96	35318.7	11130.00
21	7902.27	124.65	0.444	0.50 ( 0.48)	0.97	38991.2	11620.00
22	6836.00	140.17	0.426	0.50 ( 0.48)	0.97	43516.9	12400.00
23	5983.36	151.32	0.412	0.50 ( 0.48)	0.97	45823.1	12201.00
24	5368.31	160.41	0.402	0.50 ( 0.48)	0.97	47113.8	12111.00
25	5014.59	165.88	0.395	0.50 ( 0.48)	0.97	47860.2	10700.00
26	4437.33	175.70	0.383	0.50 ( 0.48)	0.97	49036.7	12261.00
27	3961.92	184.73	0.375	0.50 ( 0.49)	0.97	49847.8	10200.00
28	3385.89	199.72	0.367	0.50 ( 0.49)	0.97	51085.7	10300.00
29	3152.71	206.39	0.364	0.50 ( 0.49)	0.97	51437.9	12010.00
30	2674.05	226.35	0.353	0.50 ( 0.49)	0.97	51766.3	12000.00
31	1684.73	293.22	0.316	0.50 ( 0.49)	0.97	52437.1	10100.00

=====  
 =====

END OF RATIONAL METHOD ANALYSIS

\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA 92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S28- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 5-YR RM EV APRIL 2019 ROKAMOTO \*  
\*\*\*\*\*

FILE NAME: RI05EV28.DAT  
TIME/DATE OF STUDY: 17:19 04/08/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 5.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 2.707
- 2) 10.00; 1.797
- 3) 15.00; 1.318
- 4) 20.00; 1.128
- 5) 25.00; 0.984
- 6) 30.00; 0.882
- 7) 40.00; 0.755
- 8) 50.00; 0.672
- 9) 60.00; 0.611
- 10) 90.00; 0.509
- 11) 120.00; 0.450
- 12) 180.00; 0.378
- 13) 360.00; 0.280
- 14) 1200.00; 0.123

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI05EV27.DNA  
MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11010.53	26.73	0.50 ( 0.42)	0.83	6017.3	327.00
2	10858.88	33.72	0.50 ( 0.43)	0.86	8064.4	306.00
3	10465.73	47.34	0.50 ( 0.45)	0.90	11815.8	390.00
4	10163.67	59.35	0.50 ( 0.46)	0.92	15023.7	11801.00
5	9934.94	70.63	0.50 ( 0.47)	0.93	18220.0	11500.00
6	9806.50	76.28	0.50 ( 0.47)	0.94	20154.6	11701.00
7	9629.21	82.50	0.50 ( 0.47)	0.94	22263.5	11000.00
8	9236.95	98.79	0.50 ( 0.48)	0.96	29127.6	12500.00
9	9025.74	104.92	0.50 ( 0.48)	0.96	31996.4	10900.00
10	8594.37	113.34	0.50 ( 0.48)	0.96	35318.7	11130.00
11	7902.27	124.65	0.50 ( 0.48)	0.97	38991.2	11620.00
12	6836.00	140.17	0.50 ( 0.48)	0.97	43516.9	12400.00
13	5983.36	151.32	0.50 ( 0.48)	0.97	45823.1	12201.00
14	5368.31	160.41	0.50 ( 0.48)	0.97	47113.8	12111.00
15	4437.33	175.70	0.50 ( 0.48)	0.97	49036.7	12261.00
16	3961.92	184.73	0.50 ( 0.49)	0.97	49847.8	10200.00
17	3385.89	199.72	0.50 ( 0.49)	0.97	51085.7	10300.00
18	3152.71	206.39	0.50 ( 0.49)	0.97	51437.9	12010.00
19	2674.05	226.35	0.50 ( 0.49)	0.97	51766.3	12000.00
20	1684.73	293.22	0.50 ( 0.49)	0.97	52437.1	10100.00
TOTAL AREA (ACRES) =						52437.1

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 0610501U.DNA  
MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	366.96	31.71	0.50 ( 0.49)	0.98	1027.5	50120.00
2	344.28	33.54	0.50 ( 0.49)	0.98	1045.7	50150.00
3	313.44	36.83	0.50 ( 0.49)	0.98	1063.4	50100.00
TOTAL AREA (ACRES) =						1063.4

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 3 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM	Q	Tc	Fp (Fm)	Ap	Ae	HEADWATER
--------	---	----	---------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(ACRES)	NODE
1	366.96	31.71	0.50 ( 0.49) 0.98	1027.5	50120.00
2	344.28	33.54	0.50 ( 0.49) 0.98	1045.7	50150.00
3	313.44	36.83	0.50 ( 0.49) 0.98	1063.4	50100.00
TOTAL AREA (ACRES) =			1063.4		

\*\*\*\*\*

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	366.96	31.71	0.860	0.50 ( 0.49)	0.98	1027.5	50120.00
2	344.28	33.54	0.837	0.50 ( 0.49)	0.98	1045.7	50150.00
3	313.44	36.83	0.795	0.50 ( 0.49)	0.98	1063.4	50100.00

LONGEST FLOWPATH FROM NODE 50150.00 TO NODE 12800.00 = 11349.00 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11010.53	26.73	0.949	0.50 ( 0.42)	0.83	6017.3	327.00
2	10858.88	33.72	0.835	0.50 ( 0.43)	0.86	8064.4	306.00
3	10465.73	47.34	0.694	0.50 ( 0.45)	0.90	11815.8	390.00
4	10163.67	59.35	0.615	0.50 ( 0.46)	0.92	15023.7	11801.00
5	9934.94	70.63	0.575	0.50 ( 0.47)	0.93	18220.0	11500.00
6	9806.50	76.28	0.556	0.50 ( 0.47)	0.94	20154.6	11701.00
7	9629.21	82.50	0.534	0.50 ( 0.47)	0.94	22263.5	11000.00
8	9236.95	98.79	0.492	0.50 ( 0.48)	0.96	29127.6	12500.00
9	9025.74	104.92	0.480	0.50 ( 0.48)	0.96	31996.4	10900.00
10	8594.37	113.34	0.463	0.50 ( 0.48)	0.96	35318.7	11130.00
11	7902.27	124.65	0.444	0.50 ( 0.48)	0.97	38991.2	11620.00
12	6836.00	140.17	0.426	0.50 ( 0.48)	0.97	43516.9	12400.00
13	5983.36	151.32	0.412	0.50 ( 0.48)	0.97	45823.1	12201.00
14	5368.31	160.41	0.402	0.50 ( 0.48)	0.97	47113.8	12111.00
15	4437.33	175.70	0.383	0.50 ( 0.48)	0.97	49036.7	12261.00
16	3961.92	184.73	0.375	0.50 ( 0.49)	0.97	49847.8	10200.00
17	3385.89	199.72	0.367	0.50 ( 0.49)	0.97	51085.7	10300.00
18	3152.71	206.39	0.364	0.50 ( 0.49)	0.97	51437.9	12010.00
19	2674.05	226.35	0.353	0.50 ( 0.49)	0.97	51766.3	12000.00
20	1684.73	293.22	0.316	0.50 ( 0.49)	0.97	52437.1	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111795.45 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11377.49	26.73	0.949	0.50 ( 0.43)	0.85	6883.5	327.00
2	11269.37	31.71	0.860	0.50 ( 0.43)	0.87	8504.3	50120.00
3	11207.14	33.54	0.837	0.50 ( 0.44)	0.87	9056.3	50150.00
4	11201.43	33.72	0.835	0.50 ( 0.44)	0.87	9111.1	306.00
5	11082.63	36.83	0.795	0.50 ( 0.44)	0.88	9983.5	50100.00
6	10674.86	47.34	0.694	0.50 ( 0.45)	0.90	12879.2	390.00
7	10291.28	59.35	0.615	0.50 ( 0.46)	0.92	16087.1	11801.00
8	10021.27	70.63	0.575	0.50 ( 0.47)	0.93	19283.4	11500.00
9	9873.02	76.28	0.556	0.50 ( 0.47)	0.94	21218.0	11701.00
10	9673.95	82.50	0.534	0.50 ( 0.47)	0.95	23326.9	11000.00

11	9246.20	98.79	0.492	0.50 ( 0.48)	0.96	30191.0	12500.00
12	9034.76	104.92	0.480	0.50 ( 0.48)	0.96	33059.8	10900.00
13	8603.08	113.34	0.463	0.50 ( 0.48)	0.96	36382.1	11130.00
14	7910.62	124.65	0.444	0.50 ( 0.48)	0.97	40054.6	11620.00
15	6844.01	140.17	0.426	0.50 ( 0.48)	0.97	44580.3	12400.00
16	5991.11	151.32	0.412	0.50 ( 0.48)	0.97	46886.5	12201.00
17	5375.86	160.41	0.402	0.50 ( 0.48)	0.97	48177.2	12111.00
18	4444.53	175.70	0.383	0.50 ( 0.48)	0.97	50100.1	12261.00
19	3968.98	184.73	0.375	0.50 ( 0.49)	0.97	50911.2	10200.00
20	3392.80	199.72	0.367	0.50 ( 0.49)	0.97	52149.1	10300.00
21	3159.55	206.39	0.364	0.50 ( 0.49)	0.97	52501.3	12010.00
22	2680.69	226.35	0.353	0.50 ( 0.49)	0.97	52829.7	12000.00
23	1690.68	293.22	0.316	0.50 ( 0.49)	0.97	53500.5	10100.00

TOTAL AREA (ACRES) = 53500.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 11377.49 Tc (MIN.) = 26.731  
EFFECTIVE AREA (ACRES) = 6883.45 AREA-AVERAGED Fm (INCH/HR) = 0.43  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.87  
TOTAL AREA (ACRES) = 53500.5  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111795.45 FEET.

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 53500.5 TC (MIN.) = 26.73  
EFFECTIVE AREA (ACRES) = 6883.45 AREA-AVERAGED Fm (INCH/HR) = 0.43  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.852  
PEAK FLOW RATE (CFS) = 11377.49

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11377.49	26.73	0.949	0.50 ( 0.43)	0.85	6883.5	327.00
2	11269.37	31.71	0.860	0.50 ( 0.43)	0.87	8504.3	50120.00
3	11207.14	33.54	0.837	0.50 ( 0.44)	0.87	9056.3	50150.00
4	11201.43	33.72	0.835	0.50 ( 0.44)	0.87	9111.1	306.00
5	11082.63	36.83	0.795	0.50 ( 0.44)	0.88	9983.5	50100.00
6	10674.86	47.34	0.694	0.50 ( 0.45)	0.90	12879.2	390.00
7	10291.28	59.35	0.615	0.50 ( 0.46)	0.92	16087.1	11801.00
8	10021.27	70.63	0.575	0.50 ( 0.47)	0.93	19283.4	11500.00
9	9873.02	76.28	0.556	0.50 ( 0.47)	0.94	21218.0	11701.00
10	9673.95	82.50	0.534	0.50 ( 0.47)	0.95	23326.9	11000.00
11	9246.20	98.79	0.492	0.50 ( 0.48)	0.96	30191.0	12500.00
12	9034.76	104.92	0.480	0.50 ( 0.48)	0.96	33059.8	10900.00
13	8603.08	113.34	0.463	0.50 ( 0.48)	0.96	36382.1	11130.00
14	7910.62	124.65	0.444	0.50 ( 0.48)	0.97	40054.6	11620.00
15	6844.01	140.17	0.426	0.50 ( 0.48)	0.97	44580.3	12400.00
16	5991.11	151.32	0.412	0.50 ( 0.48)	0.97	46886.5	12201.00
17	5375.86	160.41	0.402	0.50 ( 0.48)	0.97	48177.2	12111.00
18	4444.53	175.70	0.383	0.50 ( 0.48)	0.97	50100.1	12261.00
19	3968.98	184.73	0.375	0.50 ( 0.49)	0.97	50911.2	10200.00
20	3392.80	199.72	0.367	0.50 ( 0.49)	0.97	52149.1	10300.00
21	3159.55	206.39	0.364	0.50 ( 0.49)	0.97	52501.3	12010.00
22	2680.69	226.35	0.353	0.50 ( 0.49)	0.97	52829.7	12000.00
23	1690.68	293.22	0.316	0.50 ( 0.49)	0.97	53500.5	10100.00

END OF RATIONAL METHOD ANALYSIS





\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA 92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S29- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 5-YR RM EV APRIL 2019 ROKAMOTO \*  
\*\*\*\*\*

FILE NAME: RI05EV29.DAT  
TIME/DATE OF STUDY: 17:19 04/08/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 5.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 2.698
- 2) 10.00; 1.793
- 3) 15.00; 1.317
- 4) 20.00; 1.127
- 5) 25.00; 0.982
- 6) 30.00; 0.881
- 7) 40.00; 0.754
- 8) 50.00; 0.672
- 9) 60.00; 0.610
- 10) 90.00; 0.507
- 11) 120.00; 0.449
- 12) 180.00; 0.377
- 13) 360.00; 0.279
- 14) 1200.00; 0.123

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI05EV28.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11377.49	26.73	0.50 ( 0.43)	0.85	6883.5	327.00
2	11082.63	36.83	0.50 ( 0.44)	0.88	9983.5	50100.00
3	10674.86	47.34	0.50 ( 0.45)	0.90	12879.2	390.00
4	10291.28	59.35	0.50 ( 0.46)	0.92	16087.1	11801.00
5	10021.27	70.63	0.50 ( 0.47)	0.93	19283.4	11500.00
6	9873.02	76.28	0.50 ( 0.47)	0.94	21218.0	11701.00
7	9673.95	82.50	0.50 ( 0.47)	0.95	23326.9	11000.00
8	9246.20	98.79	0.50 ( 0.48)	0.96	30191.0	12500.00
9	9034.76	104.92	0.50 ( 0.48)	0.96	33059.8	10900.00
10	8603.08	113.34	0.50 ( 0.48)	0.96	36382.1	11130.00
11	7910.62	124.65	0.50 ( 0.48)	0.97	40054.6	11620.00
12	6844.01	140.17	0.50 ( 0.48)	0.97	44580.3	12400.00
13	5991.11	151.32	0.50 ( 0.48)	0.97	46886.5	12201.00
14	5375.86	160.41	0.50 ( 0.48)	0.97	48177.2	12111.00
15	4444.53	175.70	0.50 ( 0.48)	0.97	50100.1	12261.00
16	3968.98	184.73	0.50 ( 0.49)	0.97	50911.2	10200.00
17	3392.80	199.72	0.50 ( 0.49)	0.97	52149.1	10300.00
18	3159.55	206.39	0.50 ( 0.49)	0.97	52501.3	12010.00
19	2680.69	226.35	0.50 ( 0.49)	0.97	52829.7	12000.00
20	1690.68	293.22	0.50 ( 0.49)	0.97	53500.5	10100.00
TOTAL AREA(ACRES) =						53500.5

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11377.49	26.73	0.50 ( 0.43)	0.85	6883.5	327.00
2	11082.63	36.83	0.50 ( 0.44)	0.88	9983.5	50100.00
3	10674.86	47.34	0.50 ( 0.45)	0.90	12879.2	390.00
4	10291.28	59.35	0.50 ( 0.46)	0.92	16087.1	11801.00
5	10021.27	70.63	0.50 ( 0.47)	0.93	19283.4	11500.00
6	9873.02	76.28	0.50 ( 0.47)	0.94	21218.0	11701.00
7	9673.95	82.50	0.50 ( 0.47)	0.95	23326.9	11000.00
8	9246.20	98.79	0.50 ( 0.48)	0.96	30191.0	12500.00
9	9034.76	104.92	0.50 ( 0.48)	0.96	33059.8	10900.00
10	8603.08	113.34	0.50 ( 0.48)	0.96	36382.1	11130.00
11	7910.62	124.65	0.50 ( 0.48)	0.97	40054.6	11620.00
12	6844.01	140.17	0.50 ( 0.48)	0.97	44580.3	12400.00
13	5991.11	151.32	0.50 ( 0.48)	0.97	46886.5	12201.00

14	5375.86	160.41	0.50	( 0.48)	0.97	48177.2	12111.00	
15	4444.53	175.70	0.50	( 0.48)	0.97	50100.1	12261.00	
16	3968.98	184.73	0.50	( 0.49)	0.97	50911.2	10200.00	
17	3392.80	199.72	0.50	( 0.49)	0.97	52149.1	10300.00	
18	3159.55	206.39	0.50	( 0.49)	0.97	52501.3	12010.00	
19	2680.69	226.35	0.50	( 0.49)	0.97	52829.7	12000.00	
20	1690.68	293.22	0.50	( 0.49)	0.97	53500.5	10100.00	
TOTAL AREA (ACRES) =		53500.5						

\*\*\*\*\*

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 12800.00 TO NODE 12901.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 240.00 DOWNSTREAM(FEET) = 216.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 3120.28 CHANNEL SLOPE = 0.0077  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
 CHANNEL FLOW THRU SUBAREA(CFS) = 11377.49  
 FLOW VELOCITY(FEET/SEC.) = 16.26 FLOW DEPTH(FEET) = 15.27  
 TRAVEL TIME(MIN.) = 3.20 Tc(MIN.) = 29.93  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12901.00 = 114915.73 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 29.93

\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.882

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	2.60	0.50	0.100	-
USER-DEFINED	-	3.20	0.50	0.100	-
USER-DEFINED	-	1.50	0.50	0.850	-
USER-DEFINED	-	5.60	0.50	0.100	-
USER-DEFINED	-	6.50	0.50	0.850	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.409

SUBAREA AREA(ACRES) = 19.40 SUBAREA RUNOFF(CFS) = 11.83

EFFECTIVE AREA(ACRES) = 6902.85 AREA-AVERAGED Fm(INCH/HR) = 0.43

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85

TOTAL AREA(ACRES) = 53519.9 PEAK FLOW RATE(CFS) = 11377.49

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 29.93

\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.882

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.50	0.50	0.100	-
USER-DEFINED	-	4.10	0.50	0.850	-
USER-DEFINED	-	0.10	0.50	0.850	-
USER-DEFINED	-	1.60	0.50	0.900	-
USER-DEFINED	-	0.60	0.50	0.900	-
USER-DEFINED	-	1.00	0.50	0.900	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.823

SUBAREA AREA(ACRES) = 7.90 SUBAREA RUNOFF(CFS) = 3.35

EFFECTIVE AREA(ACRES) = 6910.75 AREA-AVERAGED Fm(INCH/HR) = 0.43

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85

TOTAL AREA(ACRES) = 53527.8 PEAK FLOW RATE(CFS) = 11377.49

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 29.93

\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.882

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	3.60	0.50	0.900	-
USER-DEFINED	-	0.30	0.50	1.000	-
USER-DEFINED	-	12.00	0.50	1.000	-
USER-DEFINED	-	36.10	0.50	0.850	-
USER-DEFINED	-	15.90	0.50	1.000	-
USER-DEFINED	-	1.50	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.917

SUBAREA AREA(ACRES) = 69.40 SUBAREA RUNOFF(CFS) = 26.47

EFFECTIVE AREA(ACRES) = 6980.15 AREA-AVERAGED Fm(INCH/HR) = 0.43

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85

TOTAL AREA(ACRES) = 53597.2 PEAK FLOW RATE(CFS) = 11377.49

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 29.93

\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.882

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	4.20	0.50	1.000	-
USER-DEFINED	-	0.40	0.50	1.000	-
USER-DEFINED	-	1.00	0.50	1.000	-
USER-DEFINED	-	4.10	0.50	0.500	-
USER-DEFINED	-	3.70	0.50	0.500	-

USER-DEFINED - 0.40 0.50 0.500 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.703  
 SUBAREA AREA (ACRES) = 13.80 SUBAREA RUNOFF (CFS) = 6.59  
 EFFECTIVE AREA (ACRES) = 6993.95 AREA-AVERAGED Fm (INCH/HR) = 0.43  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85  
 TOTAL AREA (ACRES) = 53611.0 PEAK FLOW RATE (CFS) = 11377.49  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

-----  
 MAINLINE Tc (MIN.) = 29.93  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.882  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 6.70 0.50 1.000 -  
 USER-DEFINED - 1.20 0.50 1.000 -  
 USER-DEFINED - 2.90 0.50 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 10.80 SUBAREA RUNOFF (CFS) = 3.72  
 EFFECTIVE AREA (ACRES) = 7004.75 AREA-AVERAGED Fm (INCH/HR) = 0.43  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85  
 TOTAL AREA (ACRES) = 53621.8 PEAK FLOW RATE (CFS) = 11377.49  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12901.00 TO NODE 12902.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

-----  
 ELEVATION DATA: UPSTREAM (FEET) = 216.00 DOWNSTREAM (FEET) = 215.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 122.04 CHANNEL SLOPE = 0.0082  
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00  
 CHANNEL FLOW THRU SUBAREA (CFS) = 11377.49  
 FLOW VELOCITY (FEET/SEC.) = 16.66 FLOW DEPTH (FEET) = 15.09  
 TRAVEL TIME (MIN.) = 0.12 Tc (MIN.) = 30.05  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115037.77 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 3 <<<<<

-----  
 PEAK FLOWRATE TABLE FILE NAME: E502XX05.DNA  
 MEMORY BANK # 3 DEFINED AS FOLLOWS:  
 STREAM Q Tc Fp (Fm) Ap Ae HEADWATER  
 NUMBER (CFS) (MIN.) (INCH/HR) (ACRES) NODE  
 1 23.59 11.88 0.50 (0.46) 0.91 28.7 50200.00  
 TOTAL AREA (ACRES) = 28.7

\*\*\*\*\*

FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<  
 =====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11377.49	30.05	0.880	0.50 (0.43)	0.85	7004.8	327.00
2	11082.63	40.17	0.753	0.50 (0.44)	0.88	10104.8	50100.00
3	10674.86	50.72	0.668	0.50 (0.45)	0.90	13000.5	390.00
4	10291.28	62.76	0.601	0.50 (0.46)	0.92	16208.4	11801.00
5	10021.27	74.05	0.562	0.50 (0.47)	0.93	19404.7	11500.00
6	9873.02	79.72	0.542	0.50 (0.47)	0.94	21339.3	11701.00
7	9673.95	85.96	0.521	0.50 (0.47)	0.94	23448.2	11000.00
8	9246.20	102.29	0.483	0.50 (0.48)	0.96	30312.3	12500.00
9	9034.76	108.43	0.471	0.50 (0.48)	0.96	33181.1	10900.00
10	8603.08	116.90	0.455	0.50 (0.48)	0.96	36503.4	11130.00
11	7910.62	128.28	0.439	0.50 (0.48)	0.97	40175.9	11620.00
12	6844.01	143.94	0.420	0.50 (0.48)	0.97	44701.6	12400.00
13	5991.11	155.21	0.407	0.50 (0.48)	0.97	47007.8	12201.00
14	5375.86	164.41	0.396	0.50 (0.48)	0.97	48298.5	12111.00
15	4444.53	179.89	0.377	0.50 (0.48)	0.97	50221.4	12261.00
16	3968.98	189.05	0.372	0.50 (0.49)	0.97	51032.5	10200.00
17	3392.80	204.21	0.364	0.50 (0.49)	0.97	52270.4	10300.00
18	3159.55	210.96	0.360	0.50 (0.49)	0.97	52622.6	12010.00
19	2680.69	231.11	0.349	0.50 (0.49)	0.97	52951.0	12000.00
20	1690.68	298.56	0.312	0.50 (0.49)	0.97	53621.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115037.77 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23.59	11.88	1.614	0.50 (0.46)	0.91	28.7	50200.00

LONGEST FLOWPATH FROM NODE 50200.00 TO NODE 12902.00 = 1426.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11401.08	11.88	1.614	0.50 (0.43)	0.85	2797.7	50200.00
2	11386.14	30.05	0.880	0.50 (0.43)	0.85	7033.5	327.00
3	11088.69	40.17	0.753	0.50 (0.44)	0.88	10133.5	50100.00
4	10679.18	50.72	0.668	0.50 (0.45)	0.90	13029.2	390.00
5	10294.24	62.76	0.601	0.50 (0.46)	0.92	16237.1	11801.00
6	10023.44	74.05	0.562	0.50 (0.47)	0.93	19433.4	11500.00
7	9874.80	79.72	0.542	0.50 (0.47)	0.94	21368.0	11701.00
8	9675.29	85.96	0.521	0.50 (0.47)	0.94	23476.9	11000.00
9	9247.09	102.29	0.483	0.50 (0.48)	0.96	30341.0	12500.00
10	9035.62	108.43	0.471	0.50 (0.48)	0.96	33209.8	10900.00
11	8603.91	116.90	0.455	0.50 (0.48)	0.96	36532.1	11130.00
12	7911.43	128.28	0.439	0.50 (0.48)	0.97	40204.6	11620.00
13	6844.78	143.94	0.420	0.50 (0.48)	0.97	44730.3	12400.00
14	5991.86	155.21	0.407	0.50 (0.48)	0.97	47036.5	12201.00
15	5376.59	164.41	0.396	0.50 (0.48)	0.97	48327.2	12111.00
16	4445.22	179.89	0.377	0.50 (0.48)	0.97	50250.1	12261.00
17	3969.67	189.05	0.372	0.50 (0.48)	0.97	51061.2	10200.00
18	3393.46	204.21	0.364	0.50 (0.49)	0.97	52299.1	10300.00
19	3160.21	210.96	0.360	0.50 (0.49)	0.97	52651.3	12010.00

20 2681.33 231.11 0.349 0.50( 0.49) 0.97 52979.7 12000.00  
 21 1691.25 298.56 0.312 0.50( 0.49) 0.97 53650.5 10100.00  
 TOTAL AREA (ACRES) = 53650.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 11401.08 Tc (MIN.) = 11.879  
 EFFECTIVE AREA (ACRES) = 2797.74 AREA-AVERAGED Fm (INCH/HR) = 0.43  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.97  
 TOTAL AREA (ACRES) = 53650.5  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115037.77 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: E503XX05.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	106.09	30.37	0.50( 0.49)	0.99	366.4	50300.00	
TOTAL AREA (ACRES) = 366.4							

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11401.08	11.88	1.614	0.50( 0.43)	0.85	2797.7	50200.00
2	11386.14	30.05	0.880	0.50( 0.43)	0.85	7033.5	327.00
3	11088.69	40.17	0.753	0.50( 0.44)	0.88	10133.5	50100.00
4	10679.18	50.72	0.668	0.50( 0.45)	0.90	13029.2	390.00
5	10294.24	62.76	0.601	0.50( 0.46)	0.92	16237.1	11801.00
6	10023.44	74.05	0.562	0.50( 0.47)	0.93	19433.4	11500.00
7	9874.80	79.72	0.542	0.50( 0.47)	0.94	21368.0	11701.00
8	9675.29	85.96	0.521	0.50( 0.47)	0.94	23476.9	11000.00
9	9247.09	102.29	0.483	0.50( 0.48)	0.96	30341.0	12500.00
10	9035.62	108.43	0.471	0.50( 0.48)	0.96	33209.8	10900.00
11	8603.91	116.90	0.455	0.50( 0.48)	0.96	36532.1	11130.00
12	7911.43	128.28	0.439	0.50( 0.48)	0.97	40204.6	11620.00
13	6844.78	143.94	0.420	0.50( 0.48)	0.97	44730.3	12400.00
14	5991.86	155.21	0.407	0.50( 0.48)	0.97	47036.5	12201.00
15	5376.59	164.41	0.396	0.50( 0.48)	0.97	48327.2	12111.00
16	4445.22	179.89	0.377	0.50( 0.48)	0.97	50250.1	12261.00
17	3969.67	189.05	0.372	0.50( 0.48)	0.97	51061.2	10200.00
18	3393.46	204.21	0.364	0.50( 0.49)	0.97	52299.1	10300.00
19	3160.21	210.96	0.360	0.50( 0.49)	0.97	52651.3	12010.00
20	2681.33	231.11	0.349	0.50( 0.49)	0.97	52979.7	12000.00

21 1691.25 298.56 0.312 0.50( 0.49) 0.97 53650.5 10100.00  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115037.77 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	106.09	30.37	0.876	0.50( 0.49)	0.99	366.4	50300.00
LONGEST FLOWPATH FROM NODE 50300.00 TO NODE 12902.00 = 8614.00 FEET.							

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11507.17	11.88	1.614	0.50( 0.43)	0.86	2941.1	50200.00
2	11492.23	30.05	0.880	0.50( 0.43)	0.86	7396.0	327.00
3	11482.90	30.37	0.876	0.50( 0.43)	0.86	7497.1	50300.00
4	11160.56	40.17	0.753	0.50( 0.44)	0.88	10499.9	50100.00
5	10727.52	50.72	0.668	0.50( 0.45)	0.90	13395.6	390.00
6	10324.04	62.76	0.601	0.50( 0.46)	0.92	16603.5	11801.00
7	10042.51	74.05	0.562	0.50( 0.47)	0.93	19799.8	11500.00
8	9888.48	79.72	0.542	0.50( 0.47)	0.94	21734.4	11701.00
9	9683.05	85.96	0.521	0.50( 0.47)	0.95	23843.3	11000.00
10	9249.06	102.29	0.483	0.50( 0.48)	0.96	30707.4	12500.00
11	9037.55	108.43	0.471	0.50( 0.48)	0.96	33576.2	10900.00
12	8605.77	116.90	0.455	0.50( 0.48)	0.96	36898.4	11130.00
13	7913.22	128.28	0.439	0.50( 0.48)	0.97	40571.0	11620.00
14	6846.50	143.94	0.420	0.50( 0.48)	0.97	45096.7	12400.00
15	5993.52	155.21	0.407	0.50( 0.48)	0.97	47402.9	12201.00
16	5378.21	164.41	0.396	0.50( 0.48)	0.97	48693.6	12111.00
17	4446.77	179.89	0.377	0.50( 0.48)	0.97	50616.4	12261.00
18	3971.19	189.05	0.372	0.50( 0.49)	0.97	51427.6	10200.00
19	3394.95	204.21	0.364	0.50( 0.49)	0.97	52665.5	10300.00
20	3161.69	210.96	0.360	0.50( 0.49)	0.97	53017.7	12010.00
21	2682.75	231.11	0.349	0.50( 0.49)	0.97	53346.1	12000.00
22	1692.53	298.56	0.312	0.50( 0.49)	0.97	54016.9	10100.00
TOTAL AREA (ACRES) = 54016.9							

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 11507.17 Tc (MIN.) = 11.879  
 EFFECTIVE AREA (ACRES) = 2941.06 AREA-AVERAGED Fm (INCH/HR) = 0.43  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.86  
 TOTAL AREA (ACRES) = 54016.9  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115037.77 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12902.00 TO NODE 12903.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 215.00 DOWNSTREAM (FEET) = 214.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 895.53 CHANNEL SLOPE = 0.0011  
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00

==>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL CAPACITY( NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM ALLOWABLE DEPTH). AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

CHANNEL FLOW THRU SUBAREA(CFS) = 11507.17 FLOW VELOCITY(FEET/SEC.) = 9.59 FLOW DEPTH(FEET) = 20.00 TRAVEL TIME(MIN.) = 1.56 Tc(MIN.) = 13.44 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115933.30 FEET.

\*\*\*\*\* FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: E504XX05.DNA MEMORY BANK # 1 DEFINED AS FOLLOWS:

Table with 7 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp (Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Row 1: 1, 35.66, 19.29, 0.50(0.48), 0.97, 70.5, 50400.00. TOTAL AREA(ACRES) = 70.5

\*\*\*\*\* FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

Main table with 7 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp (Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Rows 1-22. LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115933.30 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

Table with 7 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp (Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Row 1: 1, 35.66, 19.29, 1.154, 0.50(0.48), 0.97, 70.5, 50400.00. LONGEST FLOWPATH FROM NODE 50400.00 TO NODE 12903.00 = 3607.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

Table with 7 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp (Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Rows 1-23. TOTAL AREA(ACRES) = 54087.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 11542.83 Tc(MIN.) = 13.436 EFFECTIVE AREA(ACRES) = 2990.17 AREA-AVERAGED Fm(INCH/HR) = 0.43 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.86 TOTAL AREA(ACRES) = 54087.4 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115933.30 FEET.

\*\*\*\*\* FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\* FLOW PROCESS FROM NODE 12903.00 TO NODE 12904.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<< >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 214.00 DOWNSTREAM(FEET) = 213.00 CHANNEL LENGTH THRU SUBAREA(FEET) = 767.57 CHANNEL SLOPE = 0.0013 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00

==>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL CAPACITY( NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM ALLOWABLE DEPTH). AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

CHANNEL FLOW THRU SUBAREA(CFS) = 11542.83  
 FLOW VELOCITY(FEET/SEC.) = 9.62 FLOW DEPTH(FEET) = 20.00  
 TRAVEL TIME(MIN.) = 1.33 Tc(MIN.) = 14.77  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116700.88 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<<

PEAK FLOWRATE TABLE FILE NAME: 3B05EVRL.DNA  
 MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	184.54	16.60	0.50( 0.21)	0.42	196.1	200.00
2	182.62	19.24	0.50( 0.21)	0.42	214.7	210.00
TOTAL AREA(ACRES) =					214.7	

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	11542.83	14.77	1.339	0.50( 0.43)	0.86	2990.2	50200.00
2	11538.02	20.62	1.109	0.50( 0.43)	0.86	4445.9	50400.00
3	11512.28	32.94	0.844	0.50( 0.43)	0.86	7466.5	327.00
4	11502.74	33.26	0.840	0.50( 0.43)	0.86	7567.6	50300.00
5	11174.17	43.15	0.728	0.50( 0.44)	0.88	10570.4	50100.00
6	10736.76	53.82	0.648	0.50( 0.45)	0.90	13466.1	390.00
7	10329.94	65.98	0.589	0.50( 0.46)	0.92	16674.0	11801.00
8	10046.35	77.36	0.550	0.50( 0.47)	0.94	19870.3	11500.00
9	9891.28	83.08	0.531	0.50( 0.47)	0.94	21804.9	11701.00
10	9684.70	89.39	0.509	0.50( 0.47)	0.95	23913.8	11000.00
11	9249.91	105.83	0.476	0.50( 0.48)	0.96	30777.9	12500.00
12	9038.37	112.04	0.464	0.50( 0.48)	0.96	33646.7	10900.00
13	8606.57	120.57	0.448	0.50( 0.48)	0.96	36968.9	11130.00
14	7913.99	132.03	0.435	0.50( 0.48)	0.97	40641.5	11620.00
15	6847.23	147.83	0.416	0.50( 0.48)	0.97	45167.2	12400.00
16	5994.23	159.23	0.402	0.50( 0.48)	0.97	47473.4	12201.00
17	5378.90	168.54	0.391	0.50( 0.48)	0.97	48764.1	12111.00
18	4447.43	184.22	0.375	0.50( 0.48)	0.97	50686.9	12261.00
19	3971.84	193.50	0.370	0.50( 0.49)	0.97	51498.1	10200.00
20	3395.59	208.85	0.361	0.50( 0.49)	0.97	52736.0	10300.00
21	3162.32	215.67	0.358	0.50( 0.49)	0.97	53088.2	12010.00
22	2683.37	236.02	0.346	0.50( 0.49)	0.97	53416.6	12000.00
23	1693.07	304.08	0.309	0.50( 0.49)	0.97	54087.4	10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 =					116700.88 FEET.		

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	184.54	16.60	1.256	0.50( 0.21)	0.42	196.1	200.00
2	182.62	19.24	1.156	0.50( 0.21)	0.42	214.7	210.00
LONGEST FLOWPATH FROM NODE 210.00 TO NODE 12904.00 =					5961.00 FEET.		

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	11720.04	14.77	1.339	0.50( 0.42)	0.84	3164.7	50200.00
2	11725.87	16.60	1.256	0.50( 0.42)	0.84	3641.8	200.00
3	11721.77	19.24	1.156	0.50( 0.42)	0.84	4318.2	210.00
4	11711.61	20.62	1.109	0.50( 0.42)	0.84	4660.6	50400.00
5	11634.57	32.94	0.844	0.50( 0.42)	0.85	7681.2	327.00
6	11624.24	33.26	0.840	0.50( 0.42)	0.85	7782.3	50300.00
7	11274.16	43.15	0.728	0.50( 0.44)	0.87	10785.1	50100.00
8	10821.31	53.82	0.648	0.50( 0.45)	0.90	13680.8	390.00
9	10403.12	65.98	0.589	0.50( 0.46)	0.92	16888.7	11801.00
10	10111.98	77.36	0.550	0.50( 0.46)	0.93	20085.0	11500.00
11	9953.11	83.08	0.531	0.50( 0.47)	0.94	22019.6	11701.00
12	9742.34	89.39	0.509	0.50( 0.47)	0.94	24128.5	11000.00
13	9303.18	105.83	0.476	0.50( 0.48)	0.95	30992.6	12500.00
14	9090.30	112.04	0.464	0.50( 0.48)	0.96	33861.4	10900.00
15	8656.70	120.57	0.448	0.50( 0.48)	0.96	37183.6	11130.00
16	7962.59	132.03	0.435	0.50( 0.48)	0.96	40856.2	11620.00
17	6893.71	147.83	0.416	0.50( 0.48)	0.97	45381.9	12400.00
18	6039.18	159.23	0.402	0.50( 0.48)	0.97	47688.1	12201.00
19	5422.59	168.54	0.391	0.50( 0.48)	0.97	48978.8	12111.00
20	4489.33	184.22	0.375	0.50( 0.48)	0.97	50901.6	12261.00
21	4013.18	193.50	0.370	0.50( 0.48)	0.97	51712.8	10200.00
22	3435.99	208.85	0.361	0.50( 0.48)	0.97	52950.7	10300.00
23	3202.30	215.67	0.358	0.50( 0.48)	0.97	53302.9	12010.00
24	2722.11	236.02	0.346	0.50( 0.48)	0.97	53631.3	12000.00
25	1727.68	304.08	0.309	0.50( 0.48)	0.97	54302.1	10100.00
TOTAL AREA(ACRES) =					54302.1		

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 11725.87 Tc(MIN.) = 16.597  
 EFFECTIVE AREA(ACRES) = 3641.83 AREA-AVERAGED Fm(INCH/HR) = 0.42  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.97  
 TOTAL AREA(ACRES) = 54302.1  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116700.88 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<

MAINLINE Tc(MIN.) = 16.60

\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.256

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.70	0.50	0.100	-
USER-DEFINED	-	20.00	0.50	1.000	-
USER-DEFINED	-	0.10	0.50	1.000	-
USER-DEFINED	-	14.90	0.50	0.850	-

USER-DEFINED - 2.60 0.50 0.900 -  
 USER-DEFINED - 0.80 0.50 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.920  
 SUBAREA AREA(ACRES) = 39.10 SUBAREA RUNOFF(CFS) = 28.01  
 EFFECTIVE AREA(ACRES) = 3680.93 AREA-AVERAGED Fm(INCH/HR) = 0.42  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.84  
 TOTAL AREA(ACRES) = 54341.2 PEAK FLOW RATE(CFS) = 11725.87  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 16.60  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.256  
 SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.30	0.50	0.100	-
USER-DEFINED	-	0.10	0.50	1.000	-
USER-DEFINED	-	0.10	0.50	1.000	-
USER-DEFINED	-	1.70	0.50	0.900	-
USER-DEFINED	-	2.60	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.912  
 SUBAREA AREA(ACRES) = 5.00 SUBAREA RUNOFF(CFS) = 3.60  
 EFFECTIVE AREA(ACRES) = 3685.93 AREA-AVERAGED Fm(INCH/HR) = 0.42  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.84  
 TOTAL AREA(ACRES) = 54346.2 PEAK FLOW RATE(CFS) = 11725.87  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 16.60  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.256  
 SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.10	0.50	1.000	-
USER-DEFINED	-	2.60	0.50	0.900	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	3.00	0.50	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.956  
 SUBAREA AREA(ACRES) = 5.90 SUBAREA RUNOFF(CFS) = 4.13  
 EFFECTIVE AREA(ACRES) = 3691.83 AREA-AVERAGED Fm(INCH/HR) = 0.42  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.84  
 TOTAL AREA(ACRES) = 54352.1 PEAK FLOW RATE(CFS) = 11725.87  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF STUDY SUMMARY:  
 TOTAL AREA(ACRES) = 54352.1 TC(MIN.) = 16.60

EFFECTIVE AREA(ACRES) = 3691.83 AREA-AVERAGED Fm(INCH/HR) = 0.42  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.838  
 PEAK FLOW RATE(CFS) = 11725.87

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11720.04	14.77	1.339	0.50( 0.42)	0.84	3214.7	50200.00
2	11725.87	16.60	1.256	0.50( 0.42)	0.84	3691.8	200.00
3	11721.77	19.24	1.156	0.50( 0.42)	0.84	4368.2	210.00
4	11711.61	20.62	1.109	0.50( 0.42)	0.84	4710.6	50400.00
5	11634.57	32.94	0.844	0.50( 0.42)	0.85	7731.2	327.00
6	11624.24	33.26	0.840	0.50( 0.42)	0.85	7832.3	50300.00
7	11274.16	43.15	0.728	0.50( 0.44)	0.87	10835.1	50100.00
8	10821.31	53.82	0.648	0.50( 0.45)	0.90	13730.8	390.00
9	10403.12	65.98	0.589	0.50( 0.46)	0.92	16938.7	11801.00
10	10111.98	77.36	0.550	0.50( 0.46)	0.93	20135.0	11500.00
11	9953.11	83.08	0.531	0.50( 0.47)	0.94	22069.6	11701.00
12	9742.34	89.39	0.509	0.50( 0.47)	0.94	24178.5	11000.00
13	9303.18	105.83	0.476	0.50( 0.48)	0.95	31042.6	12500.00
14	9090.30	112.04	0.464	0.50( 0.48)	0.96	33911.4	10900.00
15	8656.70	120.57	0.448	0.50( 0.48)	0.96	37233.6	11130.00
16	7962.59	132.03	0.435	0.50( 0.48)	0.96	40906.2	11620.00
17	6893.71	147.83	0.416	0.50( 0.48)	0.97	45431.9	12400.00
18	6039.18	159.23	0.402	0.50( 0.48)	0.97	47738.1	12201.00
19	5422.59	168.54	0.391	0.50( 0.48)	0.97	49028.8	12111.00
20	4489.33	184.22	0.375	0.50( 0.48)	0.97	50951.6	12261.00
21	4013.18	193.50	0.370	0.50( 0.48)	0.97	51762.8	10200.00
22	3435.99	208.85	0.361	0.50( 0.48)	0.97	53000.7	10300.00
23	3202.30	215.67	0.358	0.50( 0.48)	0.97	53352.9	12010.00
24	2722.11	236.02	0.346	0.50( 0.48)	0.97	53681.3	12000.00
25	1727.68	304.08	0.309	0.50( 0.48)	0.97	54352.1	10100.00

END OF RATIONAL METHOD ANALYSIS





\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA 92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S33 - FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 5-YR RM EV APRIL 2019 ROKAMOTO \*  
\*\*\*\*\*

FILE NAME: RI05EV33.DAT  
TIME/DATE OF STUDY: 17:20 04/08/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 5.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 2.642
- 2) 10.00; 1.762
- 3) 15.00; 1.304
- 4) 20.00; 1.115
- 5) 25.00; 0.974
- 6) 30.00; 0.875
- 7) 40.00; 0.748
- 8) 50.00; 0.665
- 9) 60.00; 0.603
- 10) 90.00; 0.500
- 11) 120.00; 0.441
- 12) 180.00; 0.369
- 13) 360.00; 0.272
- 14) 1200.00; 0.119

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL: IN- / OUT-/PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:

- 1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13112.00 TO NODE 13222.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: S31X05.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	769.71	39.09	0.50 ( 0.41)	0.81	2485.9	13100.00
2	520.73	70.06	0.50 ( 0.40)	0.81	3771.2	13000.00
3	475.69	73.98	0.50 ( 0.40)	0.81	3796.8	13010.00
TOTAL AREA (ACRES) =						3796.8

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13221.00 TO NODE 13222.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: S32X05.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	284.60	41.45	0.50 ( 0.41)	0.83	1124.1	13200.00
2	281.25	41.90	0.50 ( 0.41)	0.83	1127.6	13210.00
TOTAL AREA (ACRES) =						1127.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13221.00 TO NODE 13222.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	284.60	41.45	0.50 ( 0.41)	0.83	1124.1	13200.00
2	281.25	41.90	0.50 ( 0.41)	0.83	1127.6	13210.00
TOTAL AREA (ACRES) =						1127.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13112.00 TO NODE 13222.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	284.60	41.45	0.736	0.50 ( 0.41)	0.83	1124.1	13200.00
2	281.25	41.90	0.732	0.50 ( 0.41)	0.83	1127.6	13210.00

LONGEST FLOWPATH FROM NODE 13200.00 TO NODE 13222.00 = 16821.05 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	769.71	39.09	0.760	0.50( 0.41)	0.81	2485.9	13100.00
2	520.73	70.06	0.568	0.50( 0.40)	0.81	3771.2	13000.00
3	475.69	73.98	0.555	0.50( 0.40)	0.81	3796.8	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13222.00 = 32126.49 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1054.32	39.09	0.760	0.50( 0.41)	0.82	3546.1	13100.00
2	1035.40	41.45	0.736	0.50( 0.41)	0.82	3707.6	13200.00
3	1028.41	41.90	0.732	0.50( 0.41)	0.82	3729.9	13210.00
4	657.26	70.06	0.568	0.50( 0.41)	0.81	4898.8	13000.00
5	600.32	73.98	0.555	0.50( 0.41)	0.81	4924.4	13010.00

TOTAL AREA (ACRES) = 4924.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 1054.32 Tc(MIN.) = 39.093  
EFFECTIVE AREA(ACRES) = 3546.13 AREA-AVERAGED Fm(INCH/HR) = 0.41  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.82  
TOTAL AREA (ACRES) = 4924.4  
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13222.00 = 32126.49 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13222.00 TO NODE 13222.00 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13222.00 TO NODE 13222.00 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 2 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13222.00 TO NODE 13301.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 427.51 DOWNSTREAM(FEET) = 382.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 2533.33 CHANNEL SLOPE = 0.0180  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.720

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.40	0.50	0.100	-
USER-DEFINED	-	15.60	0.50	1.000	-
USER-DEFINED	-	0.10	0.50	0.600	-
USER-DEFINED	-	5.30	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	22.60	0.50	0.100	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.521

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1063.66  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.97  
AVERAGE FLOW DEPTH(FEET) = 5.96 TRAVEL TIME(MIN.) = 4.23  
Tc(MIN.) = 43.33  
SUBAREA AREA(ACRES) = 45.20 SUBAREA RUNOFF(CFS) = 18.70  
EFFECTIVE AREA(ACRES) = 3591.33 AREA-AVERAGED Fm(INCH/HR) = 0.41  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.81  
TOTAL AREA(ACRES) = 4969.6 PEAK FLOW RATE(CFS) = 1054.32  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 5.95 FLOW VELOCITY(FEET/SEC.) = 9.94  
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 43.33  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.720

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.00	0.50	1.000	-
USER-DEFINED	-	0.50	0.50	1.000	-
USER-DEFINED	-	7.40	0.50	0.100	-
USER-DEFINED	-	4.70	0.50	1.000	-
USER-DEFINED	-	2.90	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.596  
SUBAREA AREA(ACRES) = 16.50 SUBAREA RUNOFF(CFS) = 6.27  
EFFECTIVE AREA(ACRES) = 3607.83 AREA-AVERAGED Fm(INCH/HR) = 0.41  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.81  
TOTAL AREA(ACRES) = 4986.1 PEAK FLOW RATE(CFS) = 1054.32  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 43.33  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.720

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.30	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	0.100	-
USER-DEFINED	-	5.30	0.50	1.000	-
USER-DEFINED	-	0.30	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	0.60	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.977  
SUBAREA AREA(ACRES) = 7.90 SUBAREA RUNOFF(CFS) = 1.65  
EFFECTIVE AREA(ACRES) = 3615.73 AREA-AVERAGED Fm(INCH/HR) = 0.41

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.81  
TOTAL AREA (ACRES) = 4994.0 PEAK FLOW RATE (CFS) = 1054.32  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 43.33  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.720

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	4.30	0.50	1.000	-
USER-DEFINED	-	0.80	0.50	1.000	-
USER-DEFINED	-	1.10	0.50	1.000	-
USER-DEFINED	-	6.90	0.50	1.000	-
USER-DEFINED	-	7.90	0.50	1.000	-
USER-DEFINED	-	1.00	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 22.00 SUBAREA RUNOFF (CFS) = 4.36  
EFFECTIVE AREA (ACRES) = 3637.73 AREA-AVERAGED Fm (INCH/HR) = 0.41  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.81  
TOTAL AREA (ACRES) = 5016.0 PEAK FLOW RATE (CFS) = 1054.32  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 43.33  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.720

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.40	0.50	1.000	-
USER-DEFINED	-	14.60	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 15.00 SUBAREA RUNOFF (CFS) = 2.97  
EFFECTIVE AREA (ACRES) = 3652.73 AREA-AVERAGED Fm (INCH/HR) = 0.41  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.81  
TOTAL AREA (ACRES) = 5031.0 PEAK FLOW RATE (CFS) = 1054.32  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 31100.00 TO NODE 31101.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<

>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH (FEET) = 317.00  
ELEVATION DATA: UPSTREAM (FEET) = 801.00 DOWNSTREAM (FEET) = 685.00

Tc = K \* [(LENGTH\*\* 3.00) / (ELEVATION CHANGE)]\*\* 0.20

SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 8.641

\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 2.001

SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------	--------------

NATURAL FAIR COVER "CHAPARRAL, BROADLEAF"	-	0.50	0.50	1.000	0	8.64
--	---	------	------	-------	---	------

NATURAL FAIR COVER "OPEN BRUSH"	-	0.30	0.50	1.000	0	8.64
------------------------------------	---	------	------	-------	---	------

NATURAL FAIR COVER "OPEN BRUSH"	-	0.30	0.50	1.000	0	8.64
------------------------------------	---	------	------	-------	---	------

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA RUNOFF (CFS) = 1.49

TOTAL AREA (ACRES) = 1.10 PEAK FLOW RATE (CFS) = 1.49

\*\*\*\*\*

FLOW PROCESS FROM NODE 31101.00 TO NODE 31102.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM (FEET) = 685.00 DOWNSTREAM (FEET) = 655.00

CHANNEL LENGTH THRU SUBAREA (FEET) = 135.00 CHANNEL SLOPE = 0.2222

CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000

MAXIMUM DEPTH (FEET) = 20.00

\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.929

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

USER-DEFINED	-	0.50	0.50	1.000	-
USER-DEFINED	-	0.10	0.50	1.000	-
USER-DEFINED	-	0.70	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 2.32

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.46

AVERAGE FLOW DEPTH (FEET) = 0.38 TRAVEL TIME (MIN.) = 0.41

Tc (MIN.) = 9.05

SUBAREA AREA (ACRES) = 1.30 SUBAREA RUNOFF (CFS) = 1.67

EFFECTIVE AREA (ACRES) = 2.40 AREA-AVERAGED Fm (INCH/HR) = 0.50

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00

TOTAL AREA (ACRES) = 2.4 PEAK FLOW RATE (CFS) = 3.09

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 0.42 FLOW VELOCITY (FEET/SEC.) = 5.92

LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31102.00 = 452.00 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 31102.00 TO NODE 31103.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 655.00 DOWNSTREAM(FEET) = 630.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 203.00 CHANNEL SLOPE = 0.1232  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.815

SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 0.30 0.50 1.000 -  
USER-DEFINED - 0.10 0.50 1.000 -  
USER-DEFINED - 1.90 0.50 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 4.45  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.25  
AVERAGE FLOW DEPTH(FEET) = 0.53 TRAVEL TIME(MIN.) = 0.64  
Tc(MIN.) = 9.70  
SUBAREA AREA(ACRES) = 2.30 SUBAREA RUNOFF(CFS) = 2.72  
EFFECTIVE AREA(ACRES) = 4.70 AREA-AVERAGED Fm(INCH/HR) = 0.50  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 4.7 PEAK FLOW RATE(CFS) = 5.56

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.58 FLOW VELOCITY(FEET/SEC.) = 5.46  
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31103.00 = 655.00 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 31103.00 TO NODE 31104.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 630.00 DOWNSTREAM(FEET) = 605.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 321.00 CHANNEL SLOPE = 0.0779  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.692

SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 1.10 0.50 1.000 -  
USER-DEFINED - 2.50 0.50 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 7.49  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.00  
AVERAGE FLOW DEPTH(FEET) = 0.71 TRAVEL TIME(MIN.) = 1.07  
Tc(MIN.) = 10.77  
SUBAREA AREA(ACRES) = 3.60 SUBAREA RUNOFF(CFS) = 3.86  
EFFECTIVE AREA(ACRES) = 8.30 AREA-AVERAGED Fm(INCH/HR) = 0.50  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 8.3 PEAK FLOW RATE(CFS) = 8.90

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.75 FLOW VELOCITY(FEET/SEC.) = 5.24  
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31104.00 = 976.00 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 31104.00 TO NODE 31105.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 605.00 DOWNSTREAM(FEET) = 585.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 288.00 CHANNEL SLOPE = 0.0694  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.610

SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 0.70 0.50 1.000 -  
USER-DEFINED - 0.60 0.50 1.000 -  
USER-DEFINED - 3.00 0.50 1.000 -  
USER-DEFINED - 2.10 0.50 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 12.10  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.39  
AVERAGE FLOW DEPTH(FEET) = 0.86 TRAVEL TIME(MIN.) = 0.89  
Tc(MIN.) = 11.66  
SUBAREA AREA(ACRES) = 6.40 SUBAREA RUNOFF(CFS) = 6.39  
EFFECTIVE AREA(ACRES) = 14.70 AREA-AVERAGED Fm(INCH/HR) = 0.50  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 14.7 PEAK FLOW RATE(CFS) = 14.69

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.93 FLOW VELOCITY(FEET/SEC.) = 5.68  
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31105.00 = 1264.00 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 31105.00 TO NODE 31106.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 585.00 DOWNSTREAM(FEET) = 560.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 344.00 CHANNEL SLOPE = 0.0727  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.526

SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 0.60 0.50 1.000 -  
USER-DEFINED - 2.80 0.50 1.000 -  
USER-DEFINED - 0.60 0.50 1.000 -  
USER-DEFINED - 0.10 0.50 1.000 -  
USER-DEFINED - 2.60 0.50 1.000 -  
USER-DEFINED - 4.10 0.50 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 19.67  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.22

AVERAGE FLOW DEPTH (FEET) = 1.03 TRAVEL TIME (MIN.) = 0.92  
Tc (MIN.) = 12.58  
SUBAREA AREA (ACRES) = 10.80 SUBAREA RUNOFF (CFS) = 9.97  
EFFECTIVE AREA (ACRES) = 25.50 AREA-AVERAGED Fm (INCH/HR) = 0.50  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
TOTAL AREA (ACRES) = 25.5 PEAK FLOW RATE (CFS) = 23.53

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 1.10 FLOW VELOCITY (FEET/SEC.) = 6.47  
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31106.00 = 1608.00 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 31106.00 TO NODE 31107.00 IS CODE = 51

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

-----  
ELEVATION DATA: UPSTREAM (FEET) = 560.00 DOWNSTREAM (FEET) = 530.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 619.00 CHANNEL SLOPE = 0.0485  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.365

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.80	0.50	1.000	-
USER-DEFINED	-	1.90	0.50	1.000	-
USER-DEFINED	-	1.50	0.50	1.000	-
USER-DEFINED	-	8.20	0.50	1.000	-
USER-DEFINED	-	2.70	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 29.42  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.87  
AVERAGE FLOW DEPTH (FEET) = 1.29 TRAVEL TIME (MIN.) = 1.76  
Tc (MIN.) = 14.34  
SUBAREA AREA (ACRES) = 15.10 SUBAREA RUNOFF (CFS) = 11.75  
EFFECTIVE AREA (ACRES) = 40.60 AREA-AVERAGED Fm (INCH/HR) = 0.50  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
TOTAL AREA (ACRES) = 40.6 PEAK FLOW RATE (CFS) = 31.59

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 1.32 FLOW VELOCITY (FEET/SEC.) = 6.00  
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31107.00 = 2227.00 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 31107.00 TO NODE 31108.00 IS CODE = 51

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

-----  
ELEVATION DATA: UPSTREAM (FEET) = 530.00 DOWNSTREAM (FEET) = 515.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 377.00 CHANNEL SLOPE = 0.0398  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.288

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
USER-DEFINED	-	0.50	0.50	1.000	-
USER-DEFINED	-	6.50	0.50	1.000	-
USER-DEFINED	-	1.30	0.50	1.000	-
USER-DEFINED	-	1.10	0.50	1.000	-
USER-DEFINED	-	5.50	0.50	1.000	-
USER-DEFINED	-	3.40	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 38.08  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.83  
AVERAGE FLOW DEPTH (FEET) = 1.48 TRAVEL TIME (MIN.) = 1.08  
Tc (MIN.) = 15.41

SUBAREA AREA (ACRES) = 18.30 SUBAREA RUNOFF (CFS) = 12.98  
EFFECTIVE AREA (ACRES) = 58.90 AREA-AVERAGED Fm (INCH/HR) = 0.50  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
TOTAL AREA (ACRES) = 58.9 PEAK FLOW RATE (CFS) = 41.78

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 1.53 FLOW VELOCITY (FEET/SEC.) = 5.96  
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31108.00 = 2604.00 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 31108.00 TO NODE 31109.00 IS CODE = 51

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

-----  
ELEVATION DATA: UPSTREAM (FEET) = 515.00 DOWNSTREAM (FEET) = 490.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 520.00 CHANNEL SLOPE = 0.0481  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.239

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.70	0.50	1.000	-
USER-DEFINED	-	2.20	0.50	1.000	-
USER-DEFINED	-	3.10	0.50	1.000	-
USER-DEFINED	-	0.90	0.50	1.000	-
USER-DEFINED	-	7.40	0.50	1.000	-
USER-DEFINED	-	0.30	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 46.63  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.59  
AVERAGE FLOW DEPTH (FEET) = 1.54 TRAVEL TIME (MIN.) = 1.32  
Tc (MIN.) = 16.73

SUBAREA AREA (ACRES) = 14.60 SUBAREA RUNOFF (CFS) = 9.70  
EFFECTIVE AREA (ACRES) = 73.50 AREA-AVERAGED Fm (INCH/HR) = 0.50  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
TOTAL AREA (ACRES) = 73.5 PEAK FLOW RATE (CFS) = 48.85

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 1.56 FLOW VELOCITY (FEET/SEC.) = 6.68  
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31109.00 = 3124.00 FEET.

\*\*\*\*\*

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 16.73  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.239  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	11.40	0.50	1.000	-
USER-DEFINED	-	8.90	0.50	1.000	-
USER-DEFINED	-	1.90	0.50	1.000	-
USER-DEFINED	-	9.20	0.50	1.000	-
USER-DEFINED	-	1.40	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 32.80 SUBAREA RUNOFF(CFS) = 21.80  
 EFFECTIVE AREA(ACRES) = 106.30 AREA-AVERAGED Fm(INCH/HR) = 0.50  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 106.3 PEAK FLOW RATE(CFS) = 70.64

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31109.00 TO NODE 31110.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 490.00 DOWNSTREAM(FEET) = 432.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1420.00 CHANNEL SLOPE = 0.0408  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.111  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.80	0.50	1.000	-
USER-DEFINED	-	0.60	0.50	1.000	-
USER-DEFINED	-	0.10	0.50	0.900	-
USER-DEFINED	-	1.30	0.50	1.000	-
USER-DEFINED	-	4.00	0.50	1.000	-
USER-DEFINED	-	1.50	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 72.93  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.94  
 AVERAGE FLOW DEPTH(FEET) = 1.87 TRAVEL TIME(MIN.) = 3.41  
 Tc(MIN.) = 20.14  
 SUBAREA AREA(ACRES) = 8.30 SUBAREA RUNOFF(CFS) = 4.57  
 EFFECTIVE AREA(ACRES) = 114.60 AREA-AVERAGED Fm(INCH/HR) = 0.50  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 114.6 PEAK FLOW RATE(CFS) = 70.64  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.85 FLOW VELOCITY(FEET/SEC.) = 6.89  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31110.00 = 4544.00 FEET.

\*\*\*\*\*

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 20.14  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.111  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.30	0.50	1.000	-
USER-DEFINED	-	9.60	0.50	1.000	-
USER-DEFINED	-	0.40	0.50	0.900	-
USER-DEFINED	-	6.20	0.50	1.000	-
USER-DEFINED	-	3.90	0.50	1.000	-
USER-DEFINED	-	1.40	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.998  
 SUBAREA AREA(ACRES) = 21.80 SUBAREA RUNOFF(CFS) = 12.00  
 EFFECTIVE AREA(ACRES) = 136.40 AREA-AVERAGED Fm(INCH/HR) = 0.50  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 136.4 PEAK FLOW RATE(CFS) = 75.01

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31110.00 TO NODE 13301.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 432.00 DOWNSTREAM(FEET) = 382.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1847.00 CHANNEL SLOPE = 0.0271  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.970  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	4.90	0.50	1.000	-
USER-DEFINED	-	1.50	0.50	1.000	-
USER-DEFINED	-	0.60	0.50	0.900	-
USER-DEFINED	-	2.50	0.50	1.000	-
USER-DEFINED	-	5.30	0.50	1.000	-
USER-DEFINED	-	3.30	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.997  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 78.85  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.07  
 AVERAGE FLOW DEPTH(FEET) = 2.08 TRAVEL TIME(MIN.) = 5.07  
 Tc(MIN.) = 25.21  
 SUBAREA AREA(ACRES) = 18.10 SUBAREA RUNOFF(CFS) = 7.68  
 EFFECTIVE AREA(ACRES) = 154.50 AREA-AVERAGED Fm(INCH/HR) = 0.50  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 154.5 PEAK FLOW RATE(CFS) = 75.01  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 2.04 FLOW VELOCITY(FEET/SEC.) = 6.00  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 13301.00 = 6391.00 FEET.

```

*****
FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 11
-----
>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<
=====
** MAIN STREAM CONFLUENCE DATA **
STREAM      Q      Tc  Intensity  Fp(Fm)    Ap    Ae    HEADWATER
NUMBER      (CFS)  (MIN.) (INCH/HR) (INCH/HR)  (ACRES)  NODE
1          75.01  25.21  0.970    0.50( 0.50) 1.00   154.5  31100.00
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 13301.00 = 6391.00 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **
STREAM      Q      Tc  Intensity  Fp(Fm)    Ap    Ae    HEADWATER
NUMBER      (CFS)  (MIN.) (INCH/HR) (INCH/HR)  (ACRES)  NODE
1          1054.32  43.33  0.720    0.50( 0.41) 0.81   3652.7  13100.00
2          1035.40  45.70  0.701    0.50( 0.41) 0.81   3814.2  13200.00
3          1028.41  46.16  0.697    0.50( 0.41) 0.81   3836.5  13210.00
4           660.41  74.82  0.552    0.50( 0.41) 0.81   5005.4  13000.00
5           601.45  78.87  0.538    0.50( 0.41) 0.81   5031.0  13010.00
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

** PEAK FLOW RATE TABLE **
STREAM      Q      Tc  Intensity  Fp(Fm)    Ap    Ae    HEADWATER
NUMBER      (CFS)  (MIN.) (INCH/HR) (INCH/HR)  (ACRES)  NODE
1          1129.32  25.21  0.970    0.50( 0.41) 0.83   2279.7  31100.00
2          1089.51  43.33  0.720    0.50( 0.41) 0.82   3807.2  13100.00
3          1067.44  45.70  0.701    0.50( 0.41) 0.82   3968.7  13200.00
4          1059.85  46.16  0.697    0.50( 0.41) 0.82   3991.0  13210.00
5           668.75  74.82  0.552    0.50( 0.41) 0.82   5159.9  13000.00
6           607.57  78.87  0.538    0.50( 0.41) 0.82   5185.5  13010.00
TOTAL AREA (ACRES) = 5185.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
PEAK FLOW RATE(CFS) = 1129.32 Tc(MIN.) = 25.209
EFFECTIVE AREA(ACRES) = 2279.72 AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.83
TOTAL AREA (ACRES) = 5185.5
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

*****
FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 12
-----
>>>>CLEAR MEMORY BANK # 1 <<<<
=====
*****
FLOW PROCESS FROM NODE 13301.00 TO NODE 13302.00 IS CODE = 51
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 382.00 DOWNSTREAM(FEET) = 375.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1141.09 CHANNEL SLOPE = 0.0061
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.914
SUBAREA LOSS RATE DATA(AMC II):

```

```

DEVELOPMENT TYPE/  SCS SOIL  AREA  Fp  Ap  SCS
LAND USE          GROUP  (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED      -        9.42  0.50  1.000  -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1131.08
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.76
AVERAGE FLOW DEPTH(FEET) = 7.47 TRAVEL TIME(MIN.) = 2.81
Tc(MIN.) = 28.02
SUBAREA AREA(ACRES) = 9.42 SUBAREA RUNOFF(CFS) = 3.51
EFFECTIVE AREA(ACRES) = 2289.14 AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.83
TOTAL AREA(ACRES) = 5194.9 PEAK FLOW RATE(CFS) = 1129.32
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 7.46 FLOW VELOCITY(FEET/SEC.) = 6.76
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13302.00 = 35800.91 FEET.

*****
FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 28.02
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.914
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/  SCS SOIL  AREA  Fp  Ap  SCS
LAND USE          GROUP  (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED      -        13.80  0.50  1.000  -
USER-DEFINED      -         2.60  0.50  1.000  -
USER-DEFINED      -         1.10  0.50  0.100  -
USER-DEFINED      -         3.50  0.50  0.900  -
USER-DEFINED      -         6.90  0.50  1.000  -
USER-DEFINED      -         0.20  0.50  1.000  -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.952
SUBAREA AREA(ACRES) = 28.10 SUBAREA RUNOFF(CFS) = 11.07
EFFECTIVE AREA(ACRES) = 2317.24 AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.83
TOTAL AREA(ACRES) = 5223.0 PEAK FLOW RATE(CFS) = 1129.32
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

*****
FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 28.02
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.914
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/  SCS SOIL  AREA  Fp  Ap  SCS
LAND USE          GROUP  (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED      -         0.10  0.50  1.000  -
USER-DEFINED      -         0.10  0.50  0.100  -
USER-DEFINED      -         2.40  0.50  0.900  -
USER-DEFINED      -         0.50  0.50  1.000  -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

```



SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.894  
 SUBAREA AREA (ACRES) = 3.10 SUBAREA RUNOFF (CFS) = 1.30  
 EFFECTIVE AREA (ACRES) = 2320.34 AREA-AVERAGED Fm (INCH/HR) = 0.41  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA (ACRES) = 5226.1 PEAK FLOW RATE (CFS) = 1129.32  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 28.02  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.914  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.10	0.50	1.000	-
USER-DEFINED	-	2.60	0.50	1.000	-
USER-DEFINED	-	3.10	0.50	1.000	-
USER-DEFINED	-	0.40	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	13.80	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 20.20 SUBAREA RUNOFF (CFS) = 7.53  
 EFFECTIVE AREA (ACRES) = 2340.54 AREA-AVERAGED Fm (INCH/HR) = 0.41  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA (ACRES) = 5246.4 PEAK FLOW RATE (CFS) = 1129.32  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 28.02  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.914  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	34.60	0.50	1.000	-
USER-DEFINED	-	2.40	0.50	1.000	-
USER-DEFINED	-	22.60	0.50	1.000	-
USER-DEFINED	-	11.60	0.50	1.000	-
USER-DEFINED	-	0.40	0.50	0.200	-
USER-DEFINED	-	4.80	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.996  
 SUBAREA AREA (ACRES) = 76.40 SUBAREA RUNOFF (CFS) = 28.61  
 EFFECTIVE AREA (ACRES) = 2416.94 AREA-AVERAGED Fm (INCH/HR) = 0.42  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA (ACRES) = 5322.8 PEAK FLOW RATE (CFS) = 1129.32  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 28.02  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.914  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.60	0.50	1.000	-
USER-DEFINED	-	46.40	0.50	1.000	-
USER-DEFINED	-	0.10	0.50	0.200	-
USER-DEFINED	-	60.70	0.50	1.000	-
USER-DEFINED	-	5.80	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999  
 SUBAREA AREA (ACRES) = 114.60 SUBAREA RUNOFF (CFS) = 42.73  
 EFFECTIVE AREA (ACRES) = 2531.54 AREA-AVERAGED Fm (INCH/HR) = 0.42  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.84  
 TOTAL AREA (ACRES) = 5437.4 PEAK FLOW RATE (CFS) = 1129.32  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13302.00 TO NODE 13303.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM (FEET) = 375.00 DOWNSTREAM (FEET) = 355.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 2193.96 CHANNEL SLOPE = 0.0091  
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00  
 CHANNEL FLOW THRU SUBAREA (CFS) = 1129.32  
 FLOW VELOCITY (FEET/SEC.) = 7.84 FLOW DEPTH (FEET) = 6.93  
 TRAVEL TIME (MIN.) = 4.67 Tc (MIN.) = 32.69  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13303.00 = 37994.87 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 32.69  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.841  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	0.40	0.50	1.000	-
USER-DEFINED	-	0.80	0.50	1.000	-
USER-DEFINED	-	1.40	0.50	0.100	-
USER-DEFINED	-	2.60	0.50	1.000	-
USER-DEFINED	-	2.20	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.834  
 SUBAREA AREA (ACRES) = 7.60 SUBAREA RUNOFF (CFS) = 2.90  
 EFFECTIVE AREA (ACRES) = 2539.14 AREA-AVERAGED Fm (INCH/HR) = 0.42  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.84  
 TOTAL AREA (ACRES) = 5445.0 PEAK FLOW RATE (CFS) = 1129.32  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 32.69

\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.841

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	3.10	0.50	1.000	-
USER-DEFINED	-	3.40	0.50	1.000	-
USER-DEFINED	-	0.50	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	3.60	0.50	0.100	-
USER-DEFINED	-	4.00	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.781

SUBAREA AREA(ACRES) = 14.80 SUBAREA RUNOFF(CFS) = 6.00

EFFECTIVE AREA(ACRES) = 2553.94 AREA-AVERAGED Fm(INCH/HR) = 0.42

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.84

TOTAL AREA(ACRES) = 5459.8 PEAK FLOW RATE(CFS) = 1129.32

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 32.69

\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.841

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	14.60	0.50	1.000	-
USER-DEFINED	-	6.30	0.50	1.000	-
USER-DEFINED	-	3.70	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 24.60 SUBAREA RUNOFF(CFS) = 7.54

EFFECTIVE AREA(ACRES) = 2578.54 AREA-AVERAGED Fm(INCH/HR) = 0.42

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.84

TOTAL AREA(ACRES) = 5484.4 PEAK FLOW RATE(CFS) = 1129.32

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 32.69

\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.841

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.50	0.50	1.000	-
USER-DEFINED	-	0.30	0.50	0.100	-

USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	0.80	0.50	0.900	-
USER-DEFINED	-	1.60	0.50	1.000	-
USER-DEFINED	-	31.90	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.990

SUBAREA AREA(ACRES) = 35.30 SUBAREA RUNOFF(CFS) = 10.98

EFFECTIVE AREA(ACRES) = 2613.84 AREA-AVERAGED Fm(INCH/HR) = 0.42

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85

TOTAL AREA(ACRES) = 5519.6 PEAK FLOW RATE(CFS) = 1129.32

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 32.69

\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.841

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.70	0.50	0.100	-
USER-DEFINED	-	0.30	0.50	1.000	-
USER-DEFINED	-	2.60	0.50	0.900	-
USER-DEFINED	-	5.50	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.830

SUBAREA AREA(ACRES) = 10.50 SUBAREA RUNOFF(CFS) = 4.03

EFFECTIVE AREA(ACRES) = 2624.34 AREA-AVERAGED Fm(INCH/HR) = 0.42

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.84

TOTAL AREA(ACRES) = 5530.1 PEAK FLOW RATE(CFS) = 1129.32

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 32.69

\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.841

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.30	0.50	0.900	-
USER-DEFINED	-	0.30	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	0.100	-
USER-DEFINED	-	0.30	0.50	1.000	-
USER-DEFINED	-	6.50	0.50	0.900	-
USER-DEFINED	-	3.00	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.917

SUBAREA AREA(ACRES) = 11.60 SUBAREA RUNOFF(CFS) = 3.99

EFFECTIVE AREA(ACRES) = 2635.94 AREA-AVERAGED Fm(INCH/HR) = 0.42

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85

TOTAL AREA(ACRES) = 5541.8 PEAK FLOW RATE(CFS) = 1129.32

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13303.00 TO NODE 13304.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 355.00 DOWNSTREAM(FEET) = 350.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 925.40 CHANNEL SLOPE = 0.0054
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.811

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 13.84 0.50 0.850 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.850
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1131.72
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.45
AVERAGE FLOW DEPTH(FEET) = 7.65 TRAVEL TIME(MIN.) = 2.39
Tc(MIN.) = 35.08

SUBAREA AREA(ACRES) = 13.84 SUBAREA RUNOFF(CFS) = 4.80
EFFECTIVE AREA(ACRES) = 2649.78 AREA-AVERAGED Fm(INCH/HR) = 0.42
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85
TOTAL AREA(ACRES) = 5555.6 PEAK FLOW RATE(CFS) = 1129.32
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 7.64 FLOW VELOCITY(FEET/SEC.) = 6.45
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13304.00 = 38920.27 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 35.08
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.811

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 7.80 0.50 1.000 -
USER-DEFINED - 1.70 0.50 1.000 -
USER-DEFINED - 9.40 0.50 1.000 -
USER-DEFINED - 1.20 0.50 1.000 -
USER-DEFINED - 0.10 0.50 0.900 -
USER-DEFINED - 2.60 0.50 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 22.80 SUBAREA RUNOFF(CFS) = 6.37
EFFECTIVE AREA(ACRES) = 2672.58 AREA-AVERAGED Fm(INCH/HR) = 0.42
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85
TOTAL AREA(ACRES) = 5578.4 PEAK FLOW RATE(CFS) = 1129.32
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 35.08
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.811

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.20 0.50 1.000 -
USER-DEFINED - 0.30 0.50 1.000 -
USER-DEFINED - 0.20 0.50 0.900 -
USER-DEFINED - 2.70 0.50 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.994
SUBAREA AREA(ACRES) = 3.40 SUBAREA RUNOFF(CFS) = 0.96
EFFECTIVE AREA(ACRES) = 2675.98 AREA-AVERAGED Fm(INCH/HR) = 0.42
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85
TOTAL AREA(ACRES) = 5581.8 PEAK FLOW RATE(CFS) = 1129.32
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13304.00 TO NODE 13305.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 350.00 DOWNSTREAM(FEET) = 315.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 2966.27 CHANNEL SLOPE = 0.0118
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.741

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 27.39 0.50 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1132.30
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.64
AVERAGE FLOW DEPTH(FEET) = 6.61 TRAVEL TIME(MIN.) = 5.72
Tc(MIN.) = 40.80

SUBAREA AREA(ACRES) = 27.39 SUBAREA RUNOFF(CFS) = 5.94
EFFECTIVE AREA(ACRES) = 2703.37 AREA-AVERAGED Fm(INCH/HR) = 0.42
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85
TOTAL AREA(ACRES) = 5609.2 PEAK FLOW RATE(CFS) = 1129.32
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 6.60 FLOW VELOCITY(FEET/SEC.) = 8.64
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 40.80

\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.741  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 18.40 0.50 1.000 -  
 USER-DEFINED - 1.20 0.50 1.000 -  
 USER-DEFINED - 0.10 0.50 1.000 -  
 USER-DEFINED - 26.60 0.50 1.000 -  
 USER-DEFINED - 3.90 0.50 0.100 -  
 USER-DEFINED - 3.00 0.50 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.934  
 SUBAREA AREA (ACRES) = 53.20 SUBAREA RUNOFF (CFS) = 13.13  
 EFFECTIVE AREA (ACRES) = 2756.57 AREA-AVERAGED Fm (INCH/HR) = 0.43  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85  
 TOTAL AREA (ACRES) = 5662.4 PEAK FLOW RATE (CFS) = 1129.32  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 =====

MAINLINE Tc (MIN.) = 40.80  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.741  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 1.10 0.50 1.000 -  
 USER-DEFINED - 0.20 0.50 1.000 -  
 USER-DEFINED - 14.00 0.50 1.000 -  
 USER-DEFINED - 4.30 0.50 0.100 -  
 USER-DEFINED - 5.30 0.50 1.000 -  
 USER-DEFINED - 2.70 0.50 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.860  
 SUBAREA AREA (ACRES) = 27.60 SUBAREA RUNOFF (CFS) = 7.73  
 EFFECTIVE AREA (ACRES) = 2784.17 AREA-AVERAGED Fm (INCH/HR) = 0.43  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85  
 TOTAL AREA (ACRES) = 5690.0 PEAK FLOW RATE (CFS) = 1129.32  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 =====

MAINLINE Tc (MIN.) = 40.80  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.741  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 3.20 0.50 1.000 -  
 USER-DEFINED - 6.10 0.50 1.000 -  
 USER-DEFINED - 7.50 0.50 0.900 -  
 USER-DEFINED - 5.40 0.50 1.000 -  
 USER-DEFINED - 1.60 0.50 1.000 -  
 USER-DEFINED - 1.90 0.50 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.971  
 SUBAREA AREA (ACRES) = 25.70 SUBAREA RUNOFF (CFS) = 5.92  
 EFFECTIVE AREA (ACRES) = 2809.87 AREA-AVERAGED Fm (INCH/HR) = 0.43  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85  
 TOTAL AREA (ACRES) = 5715.7 PEAK FLOW RATE (CFS) = 1129.32  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 =====

MAINLINE Tc (MIN.) = 40.80  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.741  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 2.00 0.50 0.100 -  
 USER-DEFINED - 3.70 0.50 1.000 -  
 USER-DEFINED - 2.10 0.50 1.000 -  
 USER-DEFINED - 2.60 0.50 0.900 -  
 USER-DEFINED - 0.20 0.50 1.000 -  
 USER-DEFINED - 0.10 0.50 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.807  
 SUBAREA AREA (ACRES) = 10.70 SUBAREA RUNOFF (CFS) = 3.25  
 EFFECTIVE AREA (ACRES) = 2820.57 AREA-AVERAGED Fm (INCH/HR) = 0.43  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85  
 TOTAL AREA (ACRES) = 5726.4 PEAK FLOW RATE (CFS) = 1129.32  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 =====

MAINLINE Tc (MIN.) = 40.80  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.741  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 0.50 0.50 1.000 -  
 USER-DEFINED - 8.20 0.50 0.900 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.906  
 SUBAREA AREA (ACRES) = 8.70 SUBAREA RUNOFF (CFS) = 2.26  
 EFFECTIVE AREA (ACRES) = 2829.27 AREA-AVERAGED Fm (INCH/HR) = 0.43  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.85  
 TOTAL AREA (ACRES) = 5735.1 PEAK FLOW RATE (CFS) = 1129.32  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 1 <<<<<  
 =====

PEAK FLOWRATE TABLE FILE NAME: 3A05EVRL.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	448.39	14.96	0.50 ( 0.22)	0.43	429.7	120.00
2	443.05	15.30	0.50 ( 0.21)	0.43	435.1	110.00
3	375.74	23.09	0.50 ( 0.21)	0.42	501.8	100.00
4	332.86	27.58	0.50 ( 0.22)	0.43	510.2	150.00
TOTAL AREA (ACRES) =			510.2			

\*\*\*\*\*

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	1129.32	40.80	0.741	0.50 ( 0.43)	0.85	2829.3	31100.00
2	1089.51	59.07	0.609	0.50 ( 0.42)	0.84	4356.8	13100.00
3	1067.44	61.52	0.598	0.50 ( 0.42)	0.84	4518.2	13200.00
4	1059.85	62.00	0.596	0.50 ( 0.42)	0.84	4540.5	13210.00
5	668.75	92.59	0.495	0.50 ( 0.42)	0.83	5709.5	13000.00
6	607.57	97.07	0.486	0.50 ( 0.42)	0.83	5735.1	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	448.39	14.96	1.308	0.50 ( 0.22)	0.43	429.7	120.00
2	443.05	15.30	1.293	0.50 ( 0.21)	0.43	435.1	110.00
3	375.74	23.09	1.028	0.50 ( 0.21)	0.42	501.8	100.00
4	332.86	27.58	0.923	0.50 ( 0.22)	0.43	510.2	150.00

LONGEST FLOWPATH FROM NODE 150.00 TO NODE 13305.00 = 9867.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	1577.71	14.96	1.308	0.50 ( 0.36)	0.73	1466.8	120.00
2	1572.37	15.30	1.293	0.50 ( 0.36)	0.73	1496.0	110.00
3	1505.06	23.09	1.028	0.50 ( 0.37)	0.75	2103.0	100.00
4	1462.18	27.58	0.923	0.50 ( 0.38)	0.76	2422.9	150.00
5	1376.61	40.80	0.741	0.50 ( 0.39)	0.79	3339.5	31100.00
6	1274.29	59.07	0.609	0.50 ( 0.40)	0.80	4867.0	13100.00
7	1247.04	61.52	0.598	0.50 ( 0.40)	0.80	5028.4	13200.00
8	1238.66	62.00	0.596	0.50 ( 0.40)	0.80	5050.7	13210.00
9	800.92	92.59	0.495	0.50 ( 0.40)	0.80	6219.7	13000.00
10	737.39	97.07	0.486	0.50 ( 0.40)	0.80	6245.3	13010.00
TOTAL AREA (ACRES) =			6245.3				

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 1577.71 Tc (MIN.) = 14.955  
 EFFECTIVE AREA (ACRES) = 1466.79 AREA-AVERAGED Fm (INCH/HR) = 0.36  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.80  
 TOTAL AREA (ACRES) = 6245.3  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 13305.00 TO NODE 13306.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 315.00 DOWNSTREAM (FEET) = 245.50  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 4408.41 CHANNEL SLOPE = 0.0158  
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.060

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	68.77	0.50	0.850	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.850  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 1597.37  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 10.50  
 AVERAGE FLOW DEPTH (FEET) = 7.12 TRAVEL TIME (MIN.) = 7.00  
 Tc (MIN.) = 21.95  
 SUBAREA AREA (ACRES) = 68.77 SUBAREA RUNOFF (CFS) = 39.29  
 EFFECTIVE AREA (ACRES) = 1535.56 AREA-AVERAGED Fm (INCH/HR) = 0.37  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.73  
 TOTAL AREA (ACRES) = 6314.1 PEAK FLOW RATE (CFS) = 1577.71  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 7.09 FLOW VELOCITY (FEET/SEC.) = 10.46  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13306.00 = 46294.95 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 21.95

\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.060

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	21.50	0.50	1.000	-
USER-DEFINED	-	15.30	0.50	0.100	-
USER-DEFINED	-	0.80	0.50	1.000	-
USER-DEFINED	-	0.60	0.50	1.000	-
USER-DEFINED	-	8.00	0.50	0.900	-
USER-DEFINED	-	0.10	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.685  
 SUBAREA AREA (ACRES) = 46.30 SUBAREA RUNOFF (CFS) = 29.88  
 EFFECTIVE AREA (ACRES) = 1581.86 AREA-AVERAGED Fm (INCH/HR) = 0.37  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.73  
 TOTAL AREA (ACRES) = 6360.4 PEAK FLOW RATE (CFS) = 1577.71

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 21.95

\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.060

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	43.30	0.50	1.000	-
USER-DEFINED	-	4.90	0.50	0.100	-
USER-DEFINED	-	5.70	0.50	1.000	-
USER-DEFINED	-	0.50	0.50	1.000	-
USER-DEFINED	-	1.10	0.50	0.850	-
USER-DEFINED	-	3.10	0.50	0.900	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.917

SUBAREA AREA(ACRES) = 58.60 SUBAREA RUNOFF(CFS) = 31.72

EFFECTIVE AREA(ACRES) = 1640.46 AREA-AVERAGED Fm(INCH/HR) = 0.37

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.74

TOTAL AREA(ACRES) = 6419.0 PEAK FLOW RATE(CFS) = 1577.71

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 21.95

\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.060

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	6.80	0.50	1.000	-
USER-DEFINED	-	0.70	0.50	1.000	-
USER-DEFINED	-	1.10	0.50	0.100	-
USER-DEFINED	-	0.50	0.50	1.000	-
USER-DEFINED	-	0.10	0.50	1.000	-
USER-DEFINED	-	0.50	0.50	0.850	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.890

SUBAREA AREA(ACRES) = 9.70 SUBAREA RUNOFF(CFS) = 5.37

EFFECTIVE AREA(ACRES) = 1650.16 AREA-AVERAGED Fm(INCH/HR) = 0.37

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.74

TOTAL AREA(ACRES) = 6428.7 PEAK FLOW RATE(CFS) = 1577.71

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 21.95

\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.060

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	2.20	0.50	0.900	-
USER-DEFINED	-	0.10	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.904  
SUBAREA AREA(ACRES) = 2.30 SUBAREA RUNOFF(CFS) = 1.26  
EFFECTIVE AREA(ACRES) = 1652.46 AREA-AVERAGED Fm(INCH/HR) = 0.37  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.74  
TOTAL AREA(ACRES) = 6431.0 PEAK FLOW RATE(CFS) = 1577.71  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13306.00 TO NODE 13307.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 245.50 DOWNSTREAM(FEET) = 220.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1543.21 CHANNEL SLOPE = 0.0165  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA(CFS) = 1577.71  
FLOW VELOCITY(FEET/SEC.) = 10.66 FLOW DEPTH(FEET) = 7.02  
TRAVEL TIME(MIN.) = 2.41 Tc(MIN.) = 24.37  
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13307.00 = 47838.16 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13307.00 TO NODE 13307.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 24.37

\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.992

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.20	0.50	0.100	-
USER-DEFINED	-	0.10	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	3.70	0.50	1.000	-
USER-DEFINED	-	0.30	0.50	0.100	-
USER-DEFINED	-	3.20	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.942

SUBAREA AREA(ACRES) = 7.70 SUBAREA RUNOFF(CFS) = 3.61

EFFECTIVE AREA(ACRES) = 1660.16 AREA-AVERAGED Fm(INCH/HR) = 0.37

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.74

TOTAL AREA(ACRES) = 6438.7 PEAK FLOW RATE(CFS) = 1577.71

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13307.00 TO NODE 13307.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 24.37

\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.992

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	3.60	0.50	1.000	-
USER-DEFINED	-	1.90	0.50	1.000	-
USER-DEFINED	-	0.60	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 6.10 SUBAREA RUNOFF (CFS) = 2.70  
EFFECTIVE AREA (ACRES) = 1666.26 AREA-AVERAGED Fm (INCH/HR) = 0.37  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.74  
TOTAL AREA (ACRES) = 6444.8 PEAK FLOW RATE (CFS) = 1577.71  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13307.00 TO NODE 13308.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<  
=====

ELEVATION DATA: UPSTREAM (FEET) = 220.00 DOWNSTREAM (FEET) = 212.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 925.62 CHANNEL SLOPE = 0.0086  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA (CFS) = 1577.71  
FLOW VELOCITY (FEET/SEC.) = 8.36 FLOW DEPTH (FEET) = 7.93  
TRAVEL TIME (MIN.) = 1.85 Tc (MIN.) = 26.21  
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13308.00 = 48763.78 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
=====

MAINLINE Tc (MIN.) = 26.21  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.950  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.10	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	5.00	0.50	1.000	-
USER-DEFINED	-	3.20	0.50	0.100	-
USER-DEFINED	-	0.10	0.50	1.000	-
USER-DEFINED	-	0.90	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.697  
SUBAREA AREA (ACRES) = 9.50 SUBAREA RUNOFF (CFS) = 5.14  
EFFECTIVE AREA (ACRES) = 1675.76 AREA-AVERAGED Fm (INCH/HR) = 0.37  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.74  
TOTAL AREA (ACRES) = 6454.3 PEAK FLOW RATE (CFS) = 1577.71  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
=====

MAINLINE Tc (MIN.) = 26.21  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.950  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.30	0.50	0.200	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	1.00	0.50	1.000	-
USER-DEFINED	-	41.90	0.50	0.100	-
USER-DEFINED	-	7.20	0.50	1.000	-
USER-DEFINED	-	25.00	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.498  
SUBAREA AREA (ACRES) = 75.60 SUBAREA RUNOFF (CFS) = 47.69  
EFFECTIVE AREA (ACRES) = 1751.36 AREA-AVERAGED Fm (INCH/HR) = 0.37  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.73  
TOTAL AREA (ACRES) = 6529.9 PEAK FLOW RATE (CFS) = 1577.71  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
=====

MAINLINE Tc (MIN.) = 26.21  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.950  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.10	0.50	0.850	-
USER-DEFINED	-	0.90	0.50	1.000	-
USER-DEFINED	-	0.30	0.50	0.600	-
USER-DEFINED	-	13.20	0.50	1.000	-
USER-DEFINED	-	0.50	0.50	0.200	-
USER-DEFINED	-	0.60	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.966  
SUBAREA AREA (ACRES) = 15.60 SUBAREA RUNOFF (CFS) = 6.56  
EFFECTIVE AREA (ACRES) = 1766.96 AREA-AVERAGED Fm (INCH/HR) = 0.37  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.73  
TOTAL AREA (ACRES) = 6545.5 PEAK FLOW RATE (CFS) = 1577.71  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
=====

MAINLINE Tc (MIN.) = 26.21  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.950  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	33.90	0.50	0.100	-
USER-DEFINED	-	17.60	0.50	1.000	-
USER-DEFINED	-	16.80	0.50	1.000	-
USER-DEFINED	-	0.60	0.50	0.200	-
USER-DEFINED	-	1.50	0.50	0.400	-

USER-DEFINED - 10.00 0.50 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.603  
 SUBAREA AREA (ACRES) = 80.40 SUBAREA RUNOFF (CFS) = 46.91  
 EFFECTIVE AREA (ACRES) = 1847.36 AREA-AVERAGED Fm (INCH/HR) = 0.36  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.73  
 TOTAL AREA (ACRES) = 6625.9 PEAK FLOW RATE (CFS) = 1577.71  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 26.21  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.950  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.30	0.50	0.600	-
USER-DEFINED	-	0.70	0.50	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.880  
 SUBAREA AREA (ACRES) = 1.00 SUBAREA RUNOFF (CFS) = 0.46  
 EFFECTIVE AREA (ACRES) = 1848.36 AREA-AVERAGED Fm (INCH/HR) = 0.36  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.73  
 TOTAL AREA (ACRES) = 6626.9 PEAK FLOW RATE (CFS) = 1577.71  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 26.21  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.950  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.30	0.50	1.000	-
USER-DEFINED	-	0.80	0.50	1.000	-
USER-DEFINED	-	0.50	0.50	1.000	-
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	0.30	0.50	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 2.10 SUBAREA RUNOFF (CFS) = 0.85  
 EFFECTIVE AREA (ACRES) = 1850.46 AREA-AVERAGED Fm (INCH/HR) = 0.36  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.73  
 TOTAL AREA (ACRES) = 6629.0 PEAK FLOW RATE (CFS) = 1577.71  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 26.21

\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.950

SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.20	0.50	1.000	-
USER-DEFINED	-	0.50	0.50	1.000	-
USER-DEFINED	-	1.70	0.50	0.850	-
USER-DEFINED	-	7.20	0.50	1.000	-
USER-DEFINED	-	1.00	0.50	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.978  
 SUBAREA AREA (ACRES) = 11.60 SUBAREA RUNOFF (CFS) = 4.81  
 EFFECTIVE AREA (ACRES) = 1862.06 AREA-AVERAGED Fm (INCH/HR) = 0.36  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.73  
 TOTAL AREA (ACRES) = 6640.6 PEAK FLOW RATE (CFS) = 1577.71  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: RI05EV29.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11725.87	16.60	0.50 ( 0.42)	0.84	3691.8	200.00
2	11634.57	32.94	0.50 ( 0.42)	0.85	7731.2	327.00
3	11274.16	43.15	0.50 ( 0.44)	0.87	10835.1	50100.00
4	10821.31	53.82	0.50 ( 0.45)	0.90	13730.8	390.00
5	10403.12	65.98	0.50 ( 0.46)	0.92	16938.7	11801.00
6	10111.98	77.36	0.50 ( 0.46)	0.93	20135.0	11500.00
7	9742.34	89.39	0.50 ( 0.47)	0.94	24178.5	11000.00
8	9303.18	105.83	0.50 ( 0.48)	0.95	31042.6	12500.00
9	9090.30	112.04	0.50 ( 0.48)	0.96	33911.4	10900.00
10	8656.70	120.57	0.50 ( 0.48)	0.96	37233.6	11130.00
11	7962.59	132.03	0.50 ( 0.48)	0.96	40906.2	11620.00
12	6893.71	147.83	0.50 ( 0.48)	0.97	45431.9	12400.00
13	6039.18	159.23	0.50 ( 0.48)	0.97	47738.1	12201.00
14	5422.59	168.54	0.50 ( 0.48)	0.97	49028.8	12111.00
15	4489.33	184.22	0.50 ( 0.48)	0.97	50951.6	12261.00
16	4013.18	193.50	0.50 ( 0.48)	0.97	51762.8	10200.00
17	3435.99	208.85	0.50 ( 0.48)	0.97	53000.7	10300.00
18	3202.30	215.67	0.50 ( 0.48)	0.97	53352.9	12010.00
19	2722.11	236.02	0.50 ( 0.48)	0.97	53681.3	12000.00
20	1727.68	304.08	0.50 ( 0.48)	0.97	54352.1	10100.00
TOTAL AREA (ACRES) =						54352.1

\*\*\*\*\*

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<



MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11725.87	16.60	0.50 ( 0.42)	0.84	3691.8	200.00
2	11634.57	32.94	0.50 ( 0.42)	0.85	7731.2	327.00
3	11274.16	43.15	0.50 ( 0.44)	0.87	10835.1	50100.00
4	10821.31	53.82	0.50 ( 0.45)	0.90	13730.8	390.00
5	10403.12	65.98	0.50 ( 0.46)	0.92	16938.7	11801.00
6	10111.98	77.36	0.50 ( 0.46)	0.93	20135.0	11500.00
7	9742.34	89.39	0.50 ( 0.47)	0.94	24178.5	11000.00
8	9303.18	105.83	0.50 ( 0.48)	0.95	31042.6	12500.00
9	9090.30	112.04	0.50 ( 0.48)	0.96	33911.4	10900.00
10	8656.70	120.57	0.50 ( 0.48)	0.96	37233.6	11130.00
11	7962.59	132.03	0.50 ( 0.48)	0.96	40906.2	11620.00
12	6893.71	147.83	0.50 ( 0.48)	0.97	45431.9	12400.00
13	6039.18	159.23	0.50 ( 0.48)	0.97	47738.1	12201.00
14	5422.59	168.54	0.50 ( 0.48)	0.97	49028.8	12111.00
15	4489.33	184.22	0.50 ( 0.48)	0.97	50951.6	12261.00
16	4013.18	193.50	0.50 ( 0.48)	0.97	51762.8	10200.00
17	3435.99	208.85	0.50 ( 0.48)	0.97	53000.7	10300.00
18	3202.30	215.67	0.50 ( 0.48)	0.97	53352.9	12010.00
19	2722.11	236.02	0.50 ( 0.48)	0.97	53681.3	12000.00
20	1727.68	304.08	0.50 ( 0.48)	0.97	54352.1	10100.00
TOTAL AREA (ACRES) =		54352.1				

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12904.00 TO NODE 13308.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

-----  
 ELEVATION DATA: UPSTREAM (FEET) = 213.00 DOWNSTREAM (FEET) = 212.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1389.52 CHANNEL SLOPE = 0.0007  
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00

==>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL  
 CAPACITY( NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM  
 ALLOWABLE DEPTH).  
 AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM  
 ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

CHANNEL FLOW THRU SUBAREA (CFS) = 11725.87  
 FLOW VELOCITY (FEET/SEC.) = 9.77 FLOW DEPTH (FEET) = 20.00  
 TRAVEL TIME (MIN.) = 2.37 Tc (MIN.) = 18.97  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118090.40 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13307.00 TO NODE 13308.00 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
---------------	---------	-----------	---------------------	-------------------	----	------------	----------------

1	11725.87	18.97	1.154	0.50 ( 0.42)	0.84	3691.8	200.00
2	11634.57	35.33	0.807	0.50 ( 0.42)	0.85	7731.2	327.00
3	11274.16	45.61	0.701	0.50 ( 0.44)	0.87	10835.1	50100.00
4	10821.31	56.38	0.625	0.50 ( 0.45)	0.90	13730.8	390.00
5	10403.12	68.65	0.573	0.50 ( 0.46)	0.92	16938.7	11801.00
6	10111.98	80.11	0.534	0.50 ( 0.46)	0.93	20135.0	11500.00
7	9742.34	92.25	0.496	0.50 ( 0.47)	0.94	24178.5	11000.00
8	9303.18	108.82	0.463	0.50 ( 0.48)	0.95	31042.6	12500.00
9	9090.30	115.09	0.451	0.50 ( 0.48)	0.96	33911.4	10900.00
10	8656.70	123.78	0.436	0.50 ( 0.48)	0.96	37233.6	11130.00
11	7962.59	135.52	0.422	0.50 ( 0.48)	0.96	40906.2	11620.00
12	6893.71	151.75	0.403	0.50 ( 0.48)	0.97	45431.9	12400.00
13	6039.18	163.29	0.389	0.50 ( 0.48)	0.97	47738.1	12201.00
14	5422.59	172.71	0.378	0.50 ( 0.48)	0.97	49028.8	12111.00
15	4489.33	188.59	0.364	0.50 ( 0.48)	0.97	50951.6	12261.00
16	4013.18	197.99	0.359	0.50 ( 0.48)	0.97	51762.8	10200.00
17	3435.99	213.52	0.351	0.50 ( 0.48)	0.97	53000.7	10300.00
18	3202.30	220.43	0.347	0.50 ( 0.48)	0.97	53352.9	12010.00
19	2722.11	240.97	0.336	0.50 ( 0.48)	0.97	53681.3	12000.00
20	1727.68	309.62	0.299	0.50 ( 0.48)	0.97	54352.1	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118090.40 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1577.71	26.21	0.950	0.50 ( 0.36)	0.73	1862.1	120.00
2	1572.37	26.57	0.943	0.50 ( 0.37)	0.73	1891.3	110.00
3	1505.06	34.48	0.818	0.50 ( 0.37)	0.75	2498.3	100.00
4	1462.18	39.06	0.760	0.50 ( 0.38)	0.76	2818.2	150.00
5	1376.61	52.46	0.650	0.50 ( 0.39)	0.78	3734.7	31100.00
6	1274.29	70.95	0.565	0.50 ( 0.40)	0.79	5262.3	13100.00
7	1247.04	73.47	0.557	0.50 ( 0.40)	0.79	5423.7	13200.00
8	1238.66	73.98	0.555	0.50 ( 0.40)	0.79	5446.0	13210.00
9	800.92	105.96	0.469	0.50 ( 0.40)	0.79	6614.9	13000.00
10	737.39	110.71	0.459	0.50 ( 0.40)	0.79	6640.6	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13308.00 = 48763.78 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13265.53	18.97	1.154	0.50 ( 0.40)	0.81	5039.3	200.00
2	13263.17	26.21	0.950	0.50 ( 0.41)	0.81	7342.0	120.00
3	13255.82	26.57	0.943	0.50 ( 0.41)	0.81	7460.0	110.00
4	13144.37	34.48	0.818	0.50 ( 0.41)	0.82	10019.8	100.00
5	13131.68	35.33	0.807	0.50 ( 0.41)	0.82	10288.8	327.00
6	12965.99	39.06	0.760	0.50 ( 0.42)	0.83	11675.5	150.00
7	12694.50	45.61	0.701	0.50 ( 0.42)	0.85	14101.4	50100.00
8	12362.95	52.46	0.650	0.50 ( 0.43)	0.86	16410.2	31100.00
9	12176.20	56.38	0.625	0.50 ( 0.44)	0.87	17789.8	390.00
10	11690.14	68.65	0.573	0.50 ( 0.44)	0.89	22011.0	11801.00
11	11618.98	70.95	0.565	0.50 ( 0.45)	0.89	22842.5	13100.00
12	11527.65	73.47	0.557	0.50 ( 0.45)	0.89	23707.4	13200.00
13	11506.51	73.98	0.555	0.50 ( 0.45)	0.89	23869.8	13210.00
14	11266.65	80.11	0.534	0.50 ( 0.45)	0.90	25805.3	11500.00
15	10730.93	92.25	0.496	0.50 ( 0.46)	0.91	30292.3	11000.00
16	10180.01	105.96	0.469	0.50 ( 0.46)	0.92	36471.0	13000.00
17	10065.77	108.82	0.463	0.50 ( 0.46)	0.92	37673.0	12500.00
18	9976.63	110.71	0.459	0.50 ( 0.46)	0.93	38544.7	13010.00

19	9813.83	115.09	0.451	0.50	( 0.47)	0.93	40552.0	10900.00
20	9357.45	123.78	0.436	0.50	( 0.47)	0.93	43874.2	11130.00
21	8640.72	135.52	0.422	0.50	( 0.47)	0.94	47546.7	11620.00
22	7540.57	151.75	0.403	0.50	( 0.47)	0.94	52072.5	12400.00
23	6663.82	163.29	0.389	0.50	( 0.47)	0.95	54378.7	12201.00
24	6029.09	172.71	0.378	0.50	( 0.47)	0.95	55669.3	12111.00
25	5074.34	188.59	0.364	0.50	( 0.47)	0.95	57592.2	12261.00
26	4590.05	197.99	0.359	0.50	( 0.47)	0.95	58403.3	10200.00
27	3999.43	213.52	0.351	0.50	( 0.47)	0.95	59641.3	10300.00
28	3759.77	220.43	0.347	0.50	( 0.47)	0.95	59993.5	12010.00
29	3261.80	240.97	0.336	0.50	( 0.47)	0.95	60321.8	12000.00
30	2207.97	309.62	0.299	0.50	( 0.48)	0.95	60992.6	10100.00

TOTAL AREA (ACRES) = 60992.6

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 13265.53 Tc (MIN.) = 18.967  
EFFECTIVE AREA (ACRES) = 5039.26 AREA-AVERAGED Fm (INCH/HR) = 0.40  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.81  
TOTAL AREA (ACRES) = 60992.6  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118090.40 FEET.

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 60992.6 TC (MIN.) = 18.97  
EFFECTIVE AREA (ACRES) = 5039.26 AREA-AVERAGED Fm (INCH/HR) = 0.40  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.809  
PEAK FLOW RATE (CFS) = 13265.53

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13265.53	18.97	1.154	0.50 ( 0.40)	0.81	5039.3	200.00
2	13263.17	26.21	0.950	0.50 ( 0.41)	0.81	7342.0	120.00
3	13255.82	26.57	0.943	0.50 ( 0.41)	0.81	7460.0	110.00
4	13144.37	34.48	0.818	0.50 ( 0.41)	0.82	10019.8	100.00
5	13131.68	35.33	0.807	0.50 ( 0.41)	0.82	10288.8	327.00
6	12965.99	39.06	0.760	0.50 ( 0.42)	0.83	11675.5	150.00
7	12694.50	45.61	0.701	0.50 ( 0.42)	0.85	14101.4	50100.00
8	12362.95	52.46	0.650	0.50 ( 0.43)	0.86	16410.2	31100.00
9	12176.20	56.38	0.625	0.50 ( 0.44)	0.87	17789.8	390.00
10	11690.14	68.65	0.573	0.50 ( 0.44)	0.89	22011.0	11801.00
11	11618.98	70.95	0.565	0.50 ( 0.45)	0.89	22842.5	13100.00
12	11527.65	73.47	0.557	0.50 ( 0.45)	0.89	23707.4	13200.00
13	11506.51	73.98	0.555	0.50 ( 0.45)	0.89	23869.8	13210.00
14	11266.65	80.11	0.534	0.50 ( 0.45)	0.90	25805.3	11500.00
15	10730.93	92.25	0.496	0.50 ( 0.46)	0.91	30292.3	11000.00
16	10180.01	105.96	0.469	0.50 ( 0.46)	0.92	36471.0	13000.00
17	10065.77	108.82	0.463	0.50 ( 0.46)	0.92	37673.0	12500.00
18	9976.63	110.71	0.459	0.50 ( 0.46)	0.93	38544.7	13010.00
19	9813.83	115.09	0.451	0.50 ( 0.47)	0.93	40552.0	10900.00
20	9357.45	123.78	0.436	0.50 ( 0.47)	0.93	43874.2	11130.00
21	8640.72	135.52	0.422	0.50 ( 0.47)	0.94	47546.7	11620.00
22	7540.57	151.75	0.403	0.50 ( 0.47)	0.94	52072.5	12400.00
23	6663.82	163.29	0.389	0.50 ( 0.47)	0.95	54378.7	12201.00
24	6029.09	172.71	0.378	0.50 ( 0.47)	0.95	55669.3	12111.00
25	5074.34	188.59	0.364	0.50 ( 0.47)	0.95	57592.2	12261.00
26	4590.05	197.99	0.359	0.50 ( 0.47)	0.95	58403.3	10200.00
27	3999.43	213.52	0.351	0.50 ( 0.47)	0.95	59641.3	10300.00
28	3759.77	220.43	0.347	0.50 ( 0.47)	0.95	59993.5	12010.00

29	3261.80	240.97	0.336	0.50	( 0.47)	0.95	60321.8	12000.00
30	2207.97	309.62	0.299	0.50	( 0.48)	0.95	60992.6	10100.00

=====  
END OF RATIONAL METHOD ANALYSIS  
=====



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA 92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S34- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 5-YR RM EV APRIL 2019 ROKAMOTO \*  
\*\*\*\*\*

FILE NAME: RI05EV34.DAT  
TIME/DATE OF STUDY: 17:20 04/08/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 5.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 2.630
- 2) 10.00; 1.755
- 3) 15.00; 1.301
- 4) 20.00; 1.113
- 5) 25.00; 0.972
- 6) 30.00; 0.874
- 7) 40.00; 0.746
- 8) 50.00; 0.664
- 9) 60.00; 0.602
- 10) 90.00; 0.498
- 11) 120.00; 0.439
- 12) 180.00; 0.368
- 13) 360.00; 0.270
- 14) 1200.00; 0.118

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: ri05ev33.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13265.53	18.97	0.50 ( 0.40)	0.81	5039.3	200.00
2	13263.17	26.21	0.50 ( 0.41)	0.81	7342.0	120.00
3	13144.37	34.48	0.50 ( 0.41)	0.82	10019.8	100.00
4	12694.50	45.61	0.50 ( 0.42)	0.85	14101.4	50100.00
5	11690.14	68.65	0.50 ( 0.44)	0.89	22011.0	11801.00
6	11266.65	80.11	0.50 ( 0.45)	0.90	25805.3	11500.00
7	10730.93	92.25	0.50 ( 0.46)	0.91	30292.3	11000.00
8	10180.01	105.96	0.50 ( 0.46)	0.92	36471.0	13000.00
9	9813.83	115.09	0.50 ( 0.47)	0.93	40552.0	10900.00
10	9357.45	123.78	0.50 ( 0.47)	0.93	43874.2	11130.00
11	8640.72	135.52	0.50 ( 0.47)	0.94	47546.7	11620.00
12	7540.57	151.75	0.50 ( 0.47)	0.94	52072.5	12400.00
13	6663.82	163.29	0.50 ( 0.47)	0.95	54378.7	12201.00
14	6029.09	172.71	0.50 ( 0.47)	0.95	55669.3	12111.00
15	5074.34	188.59	0.50 ( 0.47)	0.95	57592.2	12261.00
16	4590.05	197.99	0.50 ( 0.47)	0.95	58403.3	10200.00
17	3999.43	213.52	0.50 ( 0.47)	0.95	59641.3	10300.00
18	3759.77	220.43	0.50 ( 0.47)	0.95	59993.5	12010.00
19	3261.80	240.97	0.50 ( 0.47)	0.95	60321.8	12000.00
20	2207.97	309.62	0.50 ( 0.48)	0.95	60992.6	10100.00
TOTAL AREA (ACRES) =						60992.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13265.53	18.97	0.50 ( 0.40)	0.81	5039.3	200.00
2	13263.17	26.21	0.50 ( 0.41)	0.81	7342.0	120.00
3	13144.37	34.48	0.50 ( 0.41)	0.82	10019.8	100.00
4	12694.50	45.61	0.50 ( 0.42)	0.85	14101.4	50100.00
5	11690.14	68.65	0.50 ( 0.44)	0.89	22011.0	11801.00
6	11266.65	80.11	0.50 ( 0.45)	0.90	25805.3	11500.00
7	10730.93	92.25	0.50 ( 0.46)	0.91	30292.3	11000.00
8	10180.01	105.96	0.50 ( 0.46)	0.92	36471.0	13000.00
9	9813.83	115.09	0.50 ( 0.47)	0.93	40552.0	10900.00
10	9357.45	123.78	0.50 ( 0.47)	0.93	43874.2	11130.00
11	8640.72	135.52	0.50 ( 0.47)	0.94	47546.7	11620.00
12	7540.57	151.75	0.50 ( 0.47)	0.94	52072.5	12400.00
13	6663.82	163.29	0.50 ( 0.47)	0.95	54378.7	12201.00

14	6029.09	172.71	0.50	( 0.47)	0.95	55669.3	12111.00
15	5074.34	188.59	0.50	( 0.47)	0.95	57592.2	12261.00
16	4590.05	197.99	0.50	( 0.47)	0.95	58403.3	10200.00
17	3999.43	213.52	0.50	( 0.47)	0.95	59641.3	10300.00
18	3759.77	220.43	0.50	( 0.47)	0.95	59993.5	12010.00
19	3261.80	240.97	0.50	( 0.47)	0.95	60321.8	12000.00
20	2207.97	309.62	0.50	( 0.48)	0.95	60992.6	10100.00

TOTAL AREA (ACRES) = 60992.6

\*\*\*\*\*

FLOW PROCESS FROM NODE 13308.00 TO NODE 13402.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 215.00 DOWNSTREAM(FEET) = 209.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 623.02 CHANNEL SLOPE = 0.0096  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
 CHANNEL FLOW THRU SUBAREA(CFS) = 13265.53  
 FLOW VELOCITY(FEET/SEC.) = 18.39 FLOW DEPTH(FEET) = 15.51  
 TRAVEL TIME(MIN.) = 0.56 Tc(MIN.) = 19.53  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118713.42 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13402.00 TO NODE 13402.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<

PEAK FLOWRATE TABLE FILE NAME: 0610505U.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	72.00	23.45	0.50 ( 0.49)	0.99	153.2	50500.00
TOTAL AREA (ACRES) =						153.2

\*\*\*\*\*

FLOW PROCESS FROM NODE 13402.00 TO NODE 13402.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13265.53	19.53	1.131	0.50 ( 0.40)	0.81	5039.3	200.00
2	13263.17	26.78	0.937	0.50 ( 0.41)	0.81	7342.0	120.00
3	13144.37	35.05	0.809	0.50 ( 0.41)	0.82	10019.8	100.00
4	12694.50	46.18	0.695	0.50 ( 0.42)	0.85	14101.4	50100.00
5	11690.14	69.23	0.570	0.50 ( 0.44)	0.89	22011.0	11801.00
6	11266.65	80.70	0.530	0.50 ( 0.45)	0.90	25805.3	11500.00
7	10730.93	92.84	0.492	0.50 ( 0.46)	0.91	30292.3	11000.00
8	10180.01	106.56	0.465	0.50 ( 0.46)	0.92	36471.0	13000.00
9	9813.83	115.70	0.447	0.50 ( 0.47)	0.93	40552.0	10900.00
10	9357.45	124.40	0.434	0.50 ( 0.47)	0.93	43874.2	11130.00
11	8640.72	136.15	0.420	0.50 ( 0.47)	0.94	47546.7	11620.00
12	7540.57	152.40	0.401	0.50 ( 0.47)	0.94	52072.5	12400.00
13	6663.82	163.96	0.387	0.50 ( 0.47)	0.95	54378.7	12201.00

14	6029.09	173.39	0.376	0.50 ( 0.47)	0.95	55669.3	12111.00
15	5074.34	189.31	0.363	0.50 ( 0.47)	0.95	57592.2	12261.00
16	4590.05	198.73	0.358	0.50 ( 0.47)	0.95	58403.3	10200.00
17	3999.43	214.28	0.349	0.50 ( 0.47)	0.95	59641.3	10300.00
18	3759.77	221.20	0.346	0.50 ( 0.47)	0.95	59993.5	12010.00
19	3261.80	241.77	0.334	0.50 ( 0.47)	0.95	60321.8	12000.00
20	2207.97	310.51	0.297	0.50 ( 0.48)	0.95	60992.6	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118713.42 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	72.00	23.45	1.016	0.50 ( 0.49)	0.99	153.2	50500.00
LONGEST FLOWPATH FROM NODE							50500.00 TO NODE 13402.00 = 6247.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13337.53	19.53	1.131	0.50 ( 0.41)	0.81	5166.8	200.00
2	13336.25	23.45	1.016	0.50 ( 0.41)	0.82	6438.4	50500.00
3	13324.35	26.78	0.937	0.50 ( 0.41)	0.82	7495.1	120.00
4	13187.94	35.05	0.809	0.50 ( 0.41)	0.82	10173.0	100.00
5	12722.34	46.18	0.695	0.50 ( 0.43)	0.85	14254.6	50100.00
6	11700.70	69.23	0.570	0.50 ( 0.44)	0.89	22164.1	11801.00
7	11271.74	80.70	0.530	0.50 ( 0.45)	0.90	25958.5	11500.00
8	10731.86	92.84	0.492	0.50 ( 0.46)	0.91	30445.4	11000.00
9	10180.89	106.56	0.465	0.50 ( 0.46)	0.92	36624.2	13000.00
10	9814.67	115.70	0.447	0.50 ( 0.47)	0.93	40705.2	10900.00
11	9358.26	124.40	0.434	0.50 ( 0.47)	0.93	44027.4	11130.00
12	8641.51	136.15	0.420	0.50 ( 0.47)	0.94	47699.9	11620.00
13	7541.32	152.40	0.401	0.50 ( 0.47)	0.94	52225.7	12400.00
14	6664.55	163.96	0.387	0.50 ( 0.47)	0.95	54531.8	12201.00
15	6029.80	173.39	0.376	0.50 ( 0.47)	0.95	55822.5	12111.00
16	5075.02	189.31	0.363	0.50 ( 0.47)	0.95	57745.4	12261.00
17	4590.72	198.73	0.358	0.50 ( 0.47)	0.95	58556.5	10200.00
18	4000.09	214.28	0.349	0.50 ( 0.47)	0.95	59794.4	10300.00
19	3760.42	221.20	0.346	0.50 ( 0.47)	0.95	60146.6	12010.00
20	3262.43	241.77	0.334	0.50 ( 0.47)	0.95	60475.0	12000.00
21	2208.53	310.51	0.297	0.50 ( 0.48)	0.95	61145.8	10100.00
TOTAL AREA (ACRES) =						61145.8	

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 13337.53 Tc(MIN.) = 19.532  
 EFFECTIVE AREA(ACRES) = 5166.84 AREA-AVERAGED Fm(INCH/HR) = 0.41  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.81  
 TOTAL AREA(ACRES) = 61145.8  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118713.42 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13402.00 TO NODE 13404.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 209.00 DOWNSTREAM(FEET) = 207.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 395.35 CHANNEL SLOPE = 0.0051  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00

CHANNEL FLOW THRU SUBAREA(CFS) = 13337.53  
 FLOW VELOCITY(FEET/SEC.) = 14.46 FLOW DEPTH(FEET) = 17.54  
 TRAVEL TIME(MIN.) = 0.46 Tc(MIN.) = 19.99  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119108.77 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13404.00 TO NODE 13404.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610506U.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27.99	19.62	0.50 (0.50)	1.00	49.6	50600.00
TOTAL AREA (ACRES) =						49.6

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13404.00 TO NODE 13404.00 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13337.53	19.99	1.113	0.50 (0.41)	0.81	5166.8	200.00
2	13336.25	23.91	1.003	0.50 (0.41)	0.82	6438.4	50500.00
3	13324.35	27.23	0.928	0.50 (0.41)	0.82	7495.1	120.00
4	13187.94	35.51	0.804	0.50 (0.41)	0.82	10173.0	100.00
5	12722.34	46.64	0.692	0.50 (0.43)	0.85	14254.6	50100.00
6	11700.70	69.70	0.568	0.50 (0.44)	0.89	22164.1	11801.00
7	11271.74	81.17	0.529	0.50 (0.45)	0.90	25958.5	11500.00
8	10731.86	93.32	0.491	0.50 (0.46)	0.91	30445.4	11000.00
9	10180.89	107.05	0.464	0.50 (0.46)	0.92	36624.2	13000.00
10	9814.67	116.20	0.446	0.50 (0.47)	0.93	40705.2	10900.00
11	9358.26	124.90	0.433	0.50 (0.47)	0.93	44027.4	11130.00
12	8641.51	136.66	0.419	0.50 (0.47)	0.94	47699.9	11620.00
13	7541.32	152.93	0.400	0.50 (0.47)	0.94	52225.7	12400.00
14	6664.55	164.50	0.386	0.50 (0.47)	0.95	54531.8	12201.00
15	6029.80	173.95	0.375	0.50 (0.47)	0.95	55822.5	12111.00
16	5075.02	189.89	0.363	0.50 (0.47)	0.95	57745.4	12261.00
17	4590.72	199.32	0.357	0.50 (0.47)	0.95	58556.5	10200.00
18	4000.09	214.89	0.349	0.50 (0.47)	0.95	59794.4	10300.00
19	3760.42	221.82	0.345	0.50 (0.47)	0.95	60146.6	12010.00
20	3262.43	242.42	0.334	0.50 (0.47)	0.95	60475.0	12000.00
21	2208.53	311.22	0.297	0.50 (0.48)	0.95	61145.8	10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 =						119108.77 FEET.	

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27.99	19.62	1.127	0.50 (0.50)	1.00	49.6	50600.00
LONGEST FLOWPATH FROM NODE 50600.00 TO NODE 13404.00 =						4378.00 FEET.	

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27.99	19.62	1.127	0.50 (0.50)	1.00	49.6	50600.00

1	13365.52	19.62	1.127	0.50 (0.41)	0.81	5122.7	50600.00
2	13364.91	19.99	1.113	0.50 (0.41)	0.81	5216.4	200.00
3	13358.70	23.91	1.003	0.50 (0.41)	0.82	6488.0	50500.00
4	13343.47	27.23	0.928	0.50 (0.41)	0.82	7544.7	120.00
5	13201.48	35.51	0.804	0.50 (0.41)	0.83	10222.6	100.00
6	12730.88	46.64	0.692	0.50 (0.43)	0.85	14304.2	50100.00
7	11703.75	69.70	0.568	0.50 (0.44)	0.89	22213.7	11801.00
8	11273.00	81.17	0.529	0.50 (0.45)	0.90	26008.1	11500.00
9	10731.86	93.32	0.491	0.50 (0.46)	0.91	30495.0	11000.00
10	10180.89	107.05	0.464	0.50 (0.46)	0.92	36673.8	13000.00
11	9814.67	116.20	0.446	0.50 (0.47)	0.93	40754.8	10900.00
12	9358.26	124.90	0.433	0.50 (0.47)	0.94	44077.0	11130.00
13	8641.51	136.66	0.419	0.50 (0.47)	0.94	47749.5	11620.00
14	7541.32	152.93	0.400	0.50 (0.47)	0.94	52275.2	12400.00
15	6664.55	164.50	0.386	0.50 (0.47)	0.95	54581.4	12201.00
16	6029.80	173.95	0.375	0.50 (0.47)	0.95	55872.1	12111.00
17	5075.02	189.89	0.363	0.50 (0.47)	0.95	57795.0	12261.00
18	4590.72	199.32	0.357	0.50 (0.47)	0.95	58606.1	10200.00
19	4000.09	214.89	0.349	0.50 (0.47)	0.95	59844.0	10300.00
20	3760.42	221.82	0.345	0.50 (0.47)	0.95	60196.2	12010.00
21	3262.43	242.42	0.334	0.50 (0.47)	0.95	60524.6	12000.00
22	2208.53	311.22	0.297	0.50 (0.48)	0.95	61195.4	10100.00
TOTAL AREA (ACRES) =						61195.4	

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 13365.52 Tc(MIN.) = 19.625  
 EFFECTIVE AREA(ACRES) = 5122.73 AREA-AVERAGED Fm(INCH/HR) = 0.41  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.95  
 TOTAL AREA (ACRES) = 61195.4  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119108.77 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13404.00 TO NODE 13406.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 207.00 DOWNSTREAM(FEET) = 195.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1601.97 CHANNEL SLOPE = 0.0075  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
 CHANNEL FLOW THRU SUBAREA(CFS) = 13365.52  
 FLOW VELOCITY(FEET/SEC.) = 16.77 FLOW DEPTH(FEET) = 16.30  
 TRAVEL TIME(MIN.) = 1.59 Tc(MIN.) = 21.22  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13406.00 = 120710.74 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 21.22  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.079  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.20	0.50	1.000	-
USER-DEFINED	-	4.00	0.50	1.000	-

USER-DEFINED - 2.00 0.50 1.000 -  
 USER-DEFINED - 9.70 0.50 1.000 -  
 USER-DEFINED - 2.60 0.50 1.000 -  
 USER-DEFINED - 1.80 0.50 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 20.30 SUBAREA RUNOFF(CFS) = 10.57  
 EFFECTIVE AREA(ACRES) = 5143.03 AREA-AVERAGED Fm(INCH/HR) = 0.41  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.82  
 TOTAL AREA(ACRES) = 61215.7 PEAK FLOW RATE(CFS) = 13365.52  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 21.22  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.079  
 SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	3.50	0.50	1.000	-
USER-DEFINED	-	7.20	0.50	1.000	-
USER-DEFINED	-	5.80	0.50	1.000	-
USER-DEFINED	-	0.10	0.50	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 16.60 SUBAREA RUNOFF(CFS) = 8.64  
 EFFECTIVE AREA(ACRES) = 5159.63 AREA-AVERAGED Fm(INCH/HR) = 0.41  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.82  
 TOTAL AREA(ACRES) = 61232.3 PEAK FLOW RATE(CFS) = 13365.52  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 2P05EVBB.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	324.09	10.46	0.50( 0.18)	0.37	230.2	429.00
2	338.93	12.25	0.50( 0.18)	0.37	269.4	425.00
3	340.01	12.46	0.50( 0.18)	0.37	274.1	400.00
4	343.88	14.30	0.50( 0.19)	0.37	315.0	300.00
5	364.37	20.67	0.50( 0.19)	0.37	439.8	210.00
6	360.20	22.34	0.50( 0.19)	0.37	459.0	410.00
7	355.69	24.05	0.50( 0.18)	0.37	478.3	200.00
8	351.99	24.89	0.50( 0.18)	0.37	487.0	230.00
9	344.00	26.01	0.50( 0.18)	0.37	491.2	220.50

TOTAL AREA(ACRES) = 491.2

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13365.52	21.22	1.079	0.50( 0.41)	0.82	5159.6	50600.00
2	13364.91	21.58	1.068	0.50( 0.41)	0.82	5253.3	200.00
3	13358.70	25.50	0.962	0.50( 0.41)	0.82	6524.9	50500.00
4	13343.47	28.82	0.897	0.50( 0.41)	0.82	7581.6	120.00
5	13201.48	37.10	0.783	0.50( 0.41)	0.83	10259.5	100.00
6	12730.88	48.26	0.678	0.50( 0.43)	0.85	14341.1	50100.00
7	11703.75	71.35	0.563	0.50( 0.44)	0.89	22250.6	11801.00
8	11273.00	82.84	0.523	0.50( 0.45)	0.90	26045.0	11500.00
9	10731.86	95.00	0.488	0.50( 0.46)	0.91	30531.9	11000.00
10	10180.89	108.75	0.461	0.50( 0.46)	0.92	36710.7	13000.00
11	9814.67	117.92	0.443	0.50( 0.47)	0.93	40791.7	10900.00
12	9358.26	126.64	0.431	0.50( 0.47)	0.94	44113.9	11130.00
13	8641.51	138.44	0.417	0.50( 0.47)	0.94	47786.4	11620.00
14	7541.32	154.77	0.398	0.50( 0.47)	0.94	52312.1	12400.00
15	6664.55	166.40	0.384	0.50( 0.47)	0.95	54618.3	12201.00
16	6029.80	175.89	0.373	0.50( 0.47)	0.95	55909.0	12111.00
17	5075.02	191.92	0.362	0.50( 0.47)	0.95	57831.9	12261.00
18	4590.72	201.40	0.356	0.50( 0.47)	0.95	58643.0	10200.00
19	4000.09	217.05	0.348	0.50( 0.47)	0.95	59880.9	10300.00
20	3760.42	224.01	0.344	0.50( 0.47)	0.95	60233.1	12010.00
21	3262.43	244.69	0.333	0.50( 0.47)	0.95	60561.5	12000.00
22	2208.53	313.72	0.295	0.50( 0.48)	0.95	61232.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13406.00 = 120710.74 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	324.09	10.46	1.713	0.50( 0.18)	0.37	230.2	429.00
2	338.93	12.25	1.551	0.50( 0.18)	0.37	269.4	425.00
3	340.01	12.46	1.532	0.50( 0.18)	0.37	274.1	400.00
4	343.88	14.30	1.364	0.50( 0.19)	0.37	315.0	300.00
5	364.37	20.67	1.094	0.50( 0.19)	0.37	439.8	210.00
6	360.20	22.34	1.047	0.50( 0.19)	0.37	459.0	410.00
7	355.69	24.05	0.999	0.50( 0.18)	0.37	478.3	200.00
8	351.99	24.89	0.975	0.50( 0.18)	0.37	487.0	230.00
9	344.00	26.01	0.952	0.50( 0.18)	0.37	491.2	220.50

LONGEST FLOWPATH FROM NODE 230.00 TO NODE 13406.00 = 11903.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13148.65	10.46	1.713	0.50( 0.39)	0.78	2773.2	429.00
2	13488.38	12.25	1.551	0.50( 0.39)	0.78	3247.9	425.00
3	13491.73	12.46	1.532	0.50( 0.39)	0.78	3303.5	400.00
4	13191.80	14.30	1.364	0.50( 0.39)	0.78	3793.4	300.00
5	13684.98	20.67	1.094	0.50( 0.39)	0.78	5466.6	210.00
6	13728.53	21.22	1.079	0.50( 0.39)	0.78	5605.7	50600.00

7	13727.02	21.58	1.068	0.50	( 0.39)	0.78	5703.5	200.00
8	13723.91	22.34	1.047	0.50	( 0.39)	0.78	5959.4	410.00
9	13716.67	24.05	0.999	0.50	( 0.39)	0.78	6534.4	200.00
10	13711.66	24.89	0.975	0.50	( 0.39)	0.79	6812.8	230.00
11	13706.34	25.50	0.962	0.50	( 0.39)	0.79	7014.1	50500.00
12	13700.34	26.01	0.952	0.50	( 0.39)	0.79	7179.4	220.50
13	13662.81	28.82	0.897	0.50	( 0.40)	0.79	8072.8	120.00
14	13469.84	37.10	0.783	0.50	( 0.40)	0.80	10750.7	100.00
15	12952.35	48.26	0.678	0.50	( 0.42)	0.84	14832.3	50100.00
16	11873.46	71.35	0.563	0.50	( 0.44)	0.88	22741.8	11801.00
17	11424.90	82.84	0.523	0.50	( 0.45)	0.89	26536.2	11500.00
18	10870.22	95.00	0.488	0.50	( 0.45)	0.90	31023.1	11000.00
19	10311.58	108.75	0.461	0.50	( 0.46)	0.92	37201.9	13000.00
20	9940.26	117.92	0.443	0.50	( 0.46)	0.92	41282.9	10900.00
21	9480.46	126.64	0.431	0.50	( 0.46)	0.93	44605.1	11130.00
22	8759.75	138.44	0.417	0.50	( 0.47)	0.93	48277.6	11620.00
23	7654.09	154.77	0.398	0.50	( 0.47)	0.94	52803.3	12400.00
24	6773.41	166.40	0.384	0.50	( 0.47)	0.94	55109.5	12201.00
25	6135.48	175.89	0.373	0.50	( 0.47)	0.94	56400.2	12111.00
26	5177.48	191.92	0.362	0.50	( 0.47)	0.94	58323.1	12261.00
27	4691.73	201.40	0.356	0.50	( 0.47)	0.94	59134.2	10200.00
28	4098.68	217.05	0.348	0.50	( 0.47)	0.94	60372.1	10300.00
29	3857.93	224.01	0.344	0.50	( 0.47)	0.94	60724.3	12010.00
30	3356.75	244.69	0.333	0.50	( 0.47)	0.94	61052.7	12000.00
31	2292.20	313.72	0.295	0.50	( 0.47)	0.95	61723.5	10100.00

TOTAL AREA (ACRES) = 61723.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 13728.53 Tc(MIN.) = 21.217  
EFFECTIVE AREA(ACRES) = 5605.68 AREA-AVERAGED Fm(INCH/HR) = 0.39  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.78  
TOTAL AREA(ACRES) = 61723.5  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13406.00 = 120710.74 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13406.00 TO NODE 13408.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<  
=====

ELEVATION DATA: UPSTREAM(FEET) = 195.00 DOWNSTREAM(FEET) = 182.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 2458.36 CHANNEL SLOPE = 0.0053  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00

\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.001

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.00	0.50	1.000	-
USER-DEFINED	-	3.30	0.50	1.000	-
USER-DEFINED	-	0.40	0.50	0.100	-
USER-DEFINED	-	1.40	0.50	1.000	-
USER-DEFINED	-	0.30	0.50	0.100	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.949

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 13731.46

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 14.81

AVERAGE FLOW DEPTH(FEET) = 17.58 TRAVEL TIME(MIN.) = 2.77

Tc(MIN.) = 23.98  
SUBAREA AREA(ACRES) = 12.40 SUBAREA RUNOFF(CFS) = 5.87  
EFFECTIVE AREA(ACRES) = 5618.08 AREA-AVERAGED Fm(INCH/HR) = 0.39  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.78  
TOTAL AREA(ACRES) = 61735.9 PEAK FLOW RATE(CFS) = 13728.53  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 17.58 FLOW VELOCITY(FEET/SEC.) = 14.81

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123169.10 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 2 <<<<<  
=====

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 2 <<<<<  
=====

PEAK FLOWRATE TABLE FILE NAME: 0610507U.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	107.76	23.93	0.50( 0.50)	0.99	236.8	50700.00
TOTAL AREA(ACRES) =			236.8			

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<  
=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13148.65	13.25	1.460	0.50( 0.39)	0.78	2785.6	429.00
2	13488.38	15.03	1.300	0.50( 0.39)	0.78	3260.3	425.00
3	13491.73	15.24	1.292	0.50( 0.39)	0.78	3315.9	400.00
4	13191.80	17.10	1.222	0.50( 0.39)	0.78	3805.8	300.00
5	13684.98	23.44	1.016	0.50( 0.39)	0.78	5479.0	210.00
6	13728.53	23.98	1.001	0.50( 0.39)	0.78	5618.1	50600.00
7	13727.02	24.35	0.990	0.50( 0.39)	0.78	5715.9	200.00
8	13723.91	25.11	0.970	0.50( 0.39)	0.78	5971.8	410.00
9	13716.67	26.82	0.936	0.50( 0.39)	0.78	6546.8	200.00
10	13711.66	27.65	0.920	0.50( 0.39)	0.79	6825.2	230.00
11	13706.34	28.27	0.908	0.50( 0.39)	0.79	7026.5	50500.00
12	13700.34	28.78	0.898	0.50( 0.39)	0.79	7191.8	220.50
13	13662.81	31.59	0.854	0.50( 0.40)	0.79	8085.2	120.00
14	13469.84	39.88	0.748	0.50( 0.40)	0.80	10763.1	100.00
15	12952.35	51.06	0.657	0.50( 0.42)	0.84	14844.7	50100.00
16	11873.46	74.22	0.553	0.50( 0.44)	0.88	22754.2	11801.00
17	11424.90	85.73	0.513	0.50( 0.45)	0.89	26548.6	11500.00
18	10870.22	97.94	0.482	0.50( 0.45)	0.90	31035.5	11000.00
19	10311.58	111.72	0.455	0.50( 0.46)	0.92	37214.3	13000.00
20	9940.26	120.92	0.438	0.50( 0.46)	0.92	41295.2	10900.00



21	9480.46	129.67	0.428	0.50 ( 0.46)	0.93	44617.5	11130.00
22	8759.75	141.53	0.414	0.50 ( 0.47)	0.93	48290.0	11620.00
23	7654.09	157.97	0.394	0.50 ( 0.47)	0.94	52815.7	12400.00
24	6773.41	169.70	0.380	0.50 ( 0.47)	0.94	55121.9	12201.00
25	6135.48	179.28	0.369	0.50 ( 0.47)	0.94	56412.6	12111.00
26	5177.48	195.45	0.360	0.50 ( 0.47)	0.94	58335.5	12261.00
27	4691.73	205.02	0.354	0.50 ( 0.47)	0.94	59146.6	10200.00
28	4098.68	220.79	0.346	0.50 ( 0.47)	0.94	60384.5	10300.00
29	3857.93	227.81	0.342	0.50 ( 0.47)	0.94	60736.7	12010.00
30	3356.75	248.62	0.331	0.50 ( 0.47)	0.94	61065.1	12000.00
31	2292.20	318.04	0.293	0.50 ( 0.47)	0.95	61735.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123169.10 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	107.76	23.93	1.002	0.50 ( 0.50)	0.99	236.8	50700.00

LONGEST FLOWPATH FROM NODE 50700.00 TO NODE 13408.00 = 7903.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13256.40	13.25	1.460	0.50 ( 0.39)	0.79	2916.8	429.00
2	13595.89	15.03	1.300	0.50 ( 0.39)	0.79	3408.9	425.00
3	13599.48	15.24	1.292	0.50 ( 0.39)	0.79	3466.7	400.00
4	13299.56	17.10	1.222	0.50 ( 0.39)	0.79	3975.0	300.00
5	13792.74	23.44	1.016	0.50 ( 0.39)	0.79	5710.9	210.00
6	13831.85	23.93	1.002	0.50 ( 0.39)	0.79	5840.7	50700.00
7	13835.95	23.98	1.001	0.50 ( 0.40)	0.79	5854.9	50600.00
8	13832.27	24.35	0.990	0.50 ( 0.40)	0.79	5952.7	200.00
9	13824.78	25.11	0.970	0.50 ( 0.40)	0.79	6208.6	410.00
10	13810.39	26.82	0.936	0.50 ( 0.40)	0.79	6783.6	200.00
11	13801.90	27.65	0.920	0.50 ( 0.40)	0.79	7061.9	230.00
12	13794.01	28.27	0.908	0.50 ( 0.40)	0.79	7263.3	50500.00
13	13785.87	28.78	0.898	0.50 ( 0.40)	0.79	7428.6	220.50
14	13738.90	31.59	0.854	0.50 ( 0.40)	0.80	8322.0	120.00
15	13523.32	39.88	0.748	0.50 ( 0.40)	0.81	10999.9	100.00
16	12986.64	51.06	0.657	0.50 ( 0.42)	0.84	15081.5	50100.00
17	11885.43	74.22	0.553	0.50 ( 0.44)	0.88	22991.0	11801.00
18	11428.37	85.73	0.513	0.50 ( 0.45)	0.89	26785.4	11500.00
19	10870.97	97.94	0.482	0.50 ( 0.45)	0.90	31272.3	11000.00
20	10312.29	111.72	0.455	0.50 ( 0.46)	0.92	37451.1	13000.00
21	9940.95	120.92	0.438	0.50 ( 0.46)	0.92	41532.0	10900.00
22	9481.13	129.67	0.428	0.50 ( 0.46)	0.93	44854.3	11130.00
23	8760.40	141.53	0.414	0.50 ( 0.47)	0.93	48526.8	11620.00
24	7654.71	157.97	0.394	0.50 ( 0.47)	0.94	53052.5	12400.00
25	6774.01	169.70	0.380	0.50 ( 0.47)	0.94	55358.7	12201.00
26	6136.05	179.28	0.369	0.50 ( 0.47)	0.94	56649.4	12111.00
27	5178.04	195.45	0.360	0.50 ( 0.47)	0.94	58572.3	12261.00
28	4692.28	205.02	0.354	0.50 ( 0.47)	0.94	59383.4	10200.00
29	4099.22	220.79	0.346	0.50 ( 0.47)	0.94	60621.3	10300.00
30	3858.46	227.81	0.342	0.50 ( 0.47)	0.94	60973.5	12010.00
31	3357.27	248.62	0.331	0.50 ( 0.47)	0.94	61301.9	12000.00
32	2292.65	318.04	0.293	0.50 ( 0.47)	0.95	61972.7	10100.00

TOTAL AREA (ACRES) = 61972.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 13835.95 Tc (MIN.) = 23.984

EFFECTIVE AREA (ACRES) = 5854.87 AREA-AVERAGED Fm (INCH/HR) = 0.40  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA (ACRES) = 61972.7  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123169.10 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13408.00 TO NODE 13410.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM (FEET) = 182.00 DOWNSTREAM (FEET) = 178.72  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 952.73 CHANNEL SLOPE = 0.0034  
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.967

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.40	0.50	1.000	-
USER-DEFINED	-	2.90	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 13836.65

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 12.63

AVERAGE FLOW DEPTH (FEET) = 19.11 TRAVEL TIME (MIN.) = 1.26

Tc (MIN.) = 25.24

SUBAREA AREA (ACRES) = 3.30 SUBAREA RUNOFF (CFS) = 1.39

EFFECTIVE AREA (ACRES) = 5858.17 AREA-AVERAGED Fm (INCH/HR) = 0.40

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.79

TOTAL AREA (ACRES) = 61976.0 PEAK FLOW RATE (CFS) = 13835.95

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 19.11 FLOW VELOCITY (FEET/SEC.) = 12.63

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124121.83 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<

PEAK FLOWRATE TABLE FILE NAME: RI05EV36.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	716.94	33.96	0.50 ( 0.45)	0.90	1392.8	110.00
2	712.41	36.72	0.50 ( 0.45)	0.90	1540.3	100.00
3	702.91	38.48	0.50 ( 0.45)	0.90	1624.0	100.00
4	658.46	42.79	0.50 ( 0.45)	0.91	1804.5	130.00
5	539.47	61.06	0.50 ( 0.46)	0.93	2545.6	20100.00
6	464.24	68.52	0.50 ( 0.46)	0.93	2700.4	13600.00

7 180.59 136.49 0.50 ( 0.47) 0.93 3777.9 13510.00  
 8 122.83 163.10 0.50 ( 0.47) 0.93 3859.7 13500.00  
 TOTAL AREA (ACRES) = 3859.7

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13256.40	14.52	1.344	0.50 ( 0.39)	0.79	2920.1	429.00
2	13595.89	16.29	1.253	0.50 ( 0.39)	0.79	3412.2	425.00
3	13599.48	16.50	1.245	0.50 ( 0.39)	0.79	3470.0	400.00
4	13299.56	18.37	1.174	0.50 ( 0.39)	0.79	3978.3	300.00
5	13792.74	24.70	0.981	0.50 ( 0.39)	0.79	5714.2	210.00
6	13831.85	25.19	0.968	0.50 ( 0.40)	0.79	5844.0	50700.00
7	13835.95	25.24	0.967	0.50 ( 0.40)	0.79	5858.2	50600.00
8	13832.27	25.60	0.960	0.50 ( 0.40)	0.79	5956.0	200.00
9	13824.78	26.36	0.945	0.50 ( 0.40)	0.79	6211.9	410.00
10	13810.39	28.08	0.912	0.50 ( 0.40)	0.79	6786.9	200.00
11	13801.90	28.91	0.895	0.50 ( 0.40)	0.79	7065.2	230.00
12	13794.01	29.52	0.883	0.50 ( 0.40)	0.79	7266.6	50500.00
13	13785.87	30.04	0.874	0.50 ( 0.40)	0.79	7431.9	220.50
14	13738.90	32.85	0.837	0.50 ( 0.40)	0.80	8325.3	120.00
15	13523.32	41.15	0.737	0.50 ( 0.40)	0.81	11003.2	100.00
16	12986.64	52.34	0.649	0.50 ( 0.42)	0.84	15084.8	50100.00
17	11885.43	75.52	0.548	0.50 ( 0.44)	0.88	22994.3	11801.00
18	11428.37	87.05	0.508	0.50 ( 0.45)	0.89	26788.7	11500.00
19	10870.97	99.27	0.480	0.50 ( 0.45)	0.90	31275.6	11000.00
20	10312.29	113.08	0.453	0.50 ( 0.46)	0.92	37454.4	13000.00
21	9940.95	122.28	0.436	0.50 ( 0.46)	0.92	41535.3	10900.00
22	9481.13	131.05	0.426	0.50 ( 0.46)	0.93	44857.6	11130.00
23	8760.40	142.94	0.412	0.50 ( 0.47)	0.93	48530.1	11620.00
24	7654.71	159.42	0.392	0.50 ( 0.47)	0.94	53055.8	12400.00
25	6774.01	171.20	0.378	0.50 ( 0.47)	0.94	55362.0	12201.00
26	6136.05	180.82	0.368	0.50 ( 0.47)	0.94	56652.7	12111.00
27	5178.04	197.06	0.359	0.50 ( 0.47)	0.94	58575.6	12261.00
28	4692.28	206.67	0.353	0.50 ( 0.47)	0.94	59386.7	12000.00
29	4099.22	222.49	0.345	0.50 ( 0.47)	0.94	60624.6	10300.00
30	3858.46	229.54	0.341	0.50 ( 0.47)	0.94	60976.8	12010.00
31	3357.27	250.41	0.330	0.50 ( 0.47)	0.94	61305.2	12000.00
32	2292.65	320.02	0.292	0.50 ( 0.47)	0.95	61976.0	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124121.83 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	716.94	33.96	0.823	0.50 ( 0.45)	0.90	1392.8	110.00
2	712.41	36.72	0.788	0.50 ( 0.45)	0.90	1540.3	100.00
3	702.91	38.48	0.765	0.50 ( 0.45)	0.90	1624.0	100.00
4	658.46	42.79	0.723	0.50 ( 0.45)	0.91	1804.5	130.00
5	539.47	61.06	0.598	0.50 ( 0.46)	0.93	2545.6	20100.00
6	464.24	68.52	0.572	0.50 ( 0.46)	0.93	2700.4	13600.00
7	180.59	136.49	0.419	0.50 ( 0.47)	0.93	3777.9	13510.00
8	122.83	163.10	0.388	0.50 ( 0.47)	0.93	3859.7	13500.00

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13410.00 = 41710.10 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13973.35	14.52	1.344	0.50 ( 0.40)	0.81	3515.7	429.00
2	14312.83	16.29	1.253	0.50 ( 0.40)	0.81	4080.1	425.00
3	14316.43	16.50	1.245	0.50 ( 0.40)	0.81	4146.5	400.00
4	14016.50	18.37	1.174	0.50 ( 0.40)	0.81	4731.4	300.00
5	14509.68	24.70	0.981	0.50 ( 0.40)	0.81	6727.0	210.00
6	14548.79	25.19	0.968	0.50 ( 0.40)	0.81	6876.8	50700.00
7	14552.90	25.24	0.967	0.50 ( 0.40)	0.81	6893.2	50600.00
8	14549.21	25.60	0.960	0.50 ( 0.40)	0.81	7005.9	200.00
9	14541.72	26.36	0.945	0.50 ( 0.40)	0.81	7293.0	410.00
10	14527.33	28.08	0.912	0.50 ( 0.40)	0.81	7938.3	200.00
11	14518.85	28.91	0.895	0.50 ( 0.40)	0.81	8250.7	230.00
12	14510.96	29.52	0.883	0.50 ( 0.40)	0.81	8477.3	50500.00
13	14502.81	30.04	0.874	0.50 ( 0.40)	0.81	8663.7	220.50
14	14455.84	32.85	0.837	0.50 ( 0.41)	0.81	9672.5	120.00
15	14426.94	33.96	0.823	0.50 ( 0.41)	0.81	10077.1	110.00
16	14350.71	36.72	0.788	0.50 ( 0.41)	0.82	11115.3	100.00
17	14295.51	38.48	0.765	0.50 ( 0.41)	0.82	11766.6	100.00
18	14198.76	41.15	0.737	0.50 ( 0.41)	0.82	12738.7	100.00
19	14102.76	42.79	0.723	0.50 ( 0.41)	0.83	13408.6	130.00
20	13582.91	52.34	0.649	0.50 ( 0.42)	0.85	17276.6	50100.00
21	13111.95	61.06	0.598	0.50 ( 0.43)	0.86	20605.1	20100.00
22	12682.53	68.52	0.572	0.50 ( 0.44)	0.87	23303.9	13600.00
23	12320.43	75.52	0.548	0.50 ( 0.44)	0.88	25805.8	11801.00
24	11815.26	87.05	0.508	0.50 ( 0.45)	0.90	29782.9	11500.00
25	11206.88	99.27	0.480	0.50 ( 0.45)	0.91	34463.5	11000.00
26	10590.60	113.08	0.453	0.50 ( 0.46)	0.92	40861.1	13000.00
27	10180.84	122.28	0.436	0.50 ( 0.46)	0.92	45088.0	10900.00
28	9684.41	131.05	0.426	0.50 ( 0.46)	0.93	48549.3	11130.00
29	9331.95	136.49	0.419	0.50 ( 0.47)	0.93	50315.9	13510.00
30	8926.99	142.94	0.412	0.50 ( 0.47)	0.93	52327.8	11620.00
31	7785.51	159.42	0.392	0.50 ( 0.47)	0.94	56904.2	12400.00
32	7502.94	163.10	0.388	0.50 ( 0.47)	0.94	57634.6	13500.00
33	6893.80	171.20	0.378	0.50 ( 0.47)	0.94	59221.7	12201.00
34	6252.41	180.82	0.368	0.50 ( 0.47)	0.94	60512.3	12111.00
35	5291.60	197.06	0.359	0.50 ( 0.47)	0.94	62435.2	12261.00
36	4804.18	206.67	0.353	0.50 ( 0.47)	0.94	63246.4	12000.00
37	4208.39	222.49	0.345	0.50 ( 0.47)	0.94	64484.3	10300.00
38	3966.42	229.54	0.341	0.50 ( 0.47)	0.94	64836.5	12010.00
39	3461.63	250.41	0.330	0.50 ( 0.47)	0.94	65164.9	12000.00
40	2385.02	320.02	0.292	0.50 ( 0.47)	0.94	65835.7	10100.00

TOTAL AREA (ACRES) = 65835.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 14552.90 Tc (MIN.) = 25.241  
 EFFECTIVE AREA (ACRES) = 6893.22 AREA-AVERAGED Fm (INCH/HR) = 0.40  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.81  
 TOTAL AREA (ACRES) = 65835.7  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124121.83 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13410.00 TO NODE 13412.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 178.72 DOWNSTREAM(FEET) = 176.93
CHANNEL LENGTH THRU SUBAREA(FEET) = 169.78 CHANNEL SLOPE = 0.0105
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
CHANNEL FLOW THRU SUBAREA(CFS) = 14552.90
FLOW VELOCITY(FEET/SEC.) = 19.46 FLOW DEPTH(FEET) = 15.79
TRAVEL TIME(MIN.) = 0.15 Tc(MIN.) = 25.39
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124291.61 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<

\*\*\*\*\*
FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<

PEAK FLOWRATE TABLE FILE NAME: 0506101F.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM Q Tc Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 85.74 49.56 0.50(0.49) 0.98 591.0 10100.00
TOTAL AREA(ACRES) = 591.0

\*\*\*\*\*
FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 13973.35 14.67 1.331 0.50(0.40) 0.81 3515.7 429.00
2 14312.83 16.43 1.247 0.50(0.40) 0.81 4080.1 425.00
3 14316.43 16.64 1.239 0.50(0.40) 0.81 4146.5 400.00
4 14016.50 18.51 1.169 0.50(0.40) 0.81 4731.4 300.00
5 14509.68 24.84 0.976 0.50(0.40) 0.81 6727.0 210.00
6 14548.79 25.33 0.966 0.50(0.40) 0.81 6876.8 50700.00
7 14552.90 25.39 0.964 0.50(0.40) 0.81 6893.2 50600.00
8 14549.21 25.75 0.957 0.50(0.40) 0.81 7005.9 200.00
9 14541.72 26.51 0.942 0.50(0.40) 0.81 7293.0 410.00
10 14527.33 28.22 0.909 0.50(0.40) 0.81 7938.3 200.00
11 14518.85 29.05 0.893 0.50(0.40) 0.81 8250.7 230.00
12 14510.96 29.67 0.880 0.50(0.40) 0.81 8477.3 50500.00
13 14502.81 30.18 0.872 0.50(0.40) 0.81 8663.7 220.50
14 14455.84 33.00 0.836 0.50(0.41) 0.81 9672.5 120.00
15 14426.94 34.11 0.821 0.50(0.41) 0.81 10077.1 110.00
16 14350.71 36.87 0.786 0.50(0.41) 0.82 11115.3 100.00
17 14295.51 38.63 0.764 0.50(0.41) 0.82 11766.6 100.00
18 14198.76 41.29 0.735 0.50(0.41) 0.82 12738.7 100.00
19 14102.76 42.94 0.722 0.50(0.41) 0.83 13408.6 130.00
20 13582.91 52.49 0.649 0.50(0.42) 0.85 17276.6 50100.00

21 13111.95 61.21 0.598 0.50(0.43) 0.86 20605.1 20100.00
22 12682.53 68.67 0.572 0.50(0.44) 0.87 23303.9 13600.00
23 12320.43 75.68 0.548 0.50(0.44) 0.88 25805.8 11801.00
24 11815.26 87.21 0.508 0.50(0.45) 0.90 29782.9 11500.00
25 11206.88 99.43 0.479 0.50(0.45) 0.91 34463.5 11000.00
26 10590.60 113.23 0.452 0.50(0.46) 0.92 40861.1 13000.00
27 10180.84 122.44 0.436 0.50(0.46) 0.92 45088.0 10900.00
28 9684.41 131.22 0.426 0.50(0.46) 0.93 48549.3 11130.00
29 9331.95 136.66 0.419 0.50(0.47) 0.93 50315.9 13510.00
30 8926.99 143.10 0.412 0.50(0.47) 0.93 52327.8 11620.00
31 7785.51 159.59 0.392 0.50(0.47) 0.94 56904.2 12400.00
32 7502.94 163.27 0.388 0.50(0.47) 0.94 57634.6 13500.00
33 6893.80 171.37 0.378 0.50(0.47) 0.94 59221.7 12201.00
34 6252.41 181.00 0.367 0.50(0.47) 0.94 60512.3 12111.00
35 5291.60 197.25 0.359 0.50(0.47) 0.94 62435.2 12261.00
36 4804.18 206.86 0.353 0.50(0.47) 0.94 63246.4 10200.00
37 4208.39 222.69 0.345 0.50(0.47) 0.94 64484.3 10300.00
38 3966.42 229.74 0.341 0.50(0.47) 0.94 64836.5 12010.00
39 3461.63 250.62 0.330 0.50(0.47) 0.94 65164.9 12000.00
40 2385.02 320.24 0.292 0.50(0.47) 0.94 65835.7 10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124291.61 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 85.74 49.56 0.668 0.50(0.49) 0.98 591.0 10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 14677.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 14059.08 14.67 1.331 0.50(0.41) 0.82 3690.6 429.00
2 14398.57 16.43 1.247 0.50(0.41) 0.82 4276.1 425.00
3 14402.16 16.64 1.239 0.50(0.41) 0.82 4345.0 400.00
4 14102.24 18.51 1.169 0.50(0.41) 0.81 4952.1 300.00
5 14595.42 24.84 0.976 0.50(0.41) 0.81 7023.2 210.00
6 14634.53 25.33 0.966 0.50(0.41) 0.81 7178.8 50700.00
7 14638.63 25.39 0.964 0.50(0.41) 0.81 7195.9 50600.00
8 14634.95 25.75 0.957 0.50(0.41) 0.81 7312.9 200.00
9 14627.46 26.51 0.942 0.50(0.41) 0.81 7609.2 410.00
10 14613.07 28.22 0.909 0.50(0.41) 0.81 8274.8 200.00
11 14604.58 29.05 0.893 0.50(0.41) 0.82 8597.2 230.00
12 14596.69 29.67 0.880 0.50(0.41) 0.82 8831.1 50500.00
13 14588.55 30.18 0.872 0.50(0.41) 0.82 9023.6 220.50
14 14541.58 33.00 0.836 0.50(0.41) 0.82 10066.0 120.00
15 14512.68 34.11 0.821 0.50(0.41) 0.82 10483.8 110.00
16 14436.44 36.87 0.786 0.50(0.41) 0.82 11555.0 100.00
17 14381.24 38.63 0.764 0.50(0.41) 0.82 12227.2 100.00
18 14284.50 41.29 0.735 0.50(0.41) 0.83 13231.1 100.00
19 14188.50 42.94 0.722 0.50(0.42) 0.83 13920.7 130.00
20 13827.91 49.56 0.668 0.50(0.42) 0.85 16682.5 10100.00
21 13659.36 52.49 0.649 0.50(0.43) 0.85 17867.6 50100.00
22 13163.61 61.21 0.598 0.50(0.43) 0.87 21196.1 20100.00
23 12721.57 68.67 0.572 0.50(0.44) 0.88 23894.9 13600.00
24 12347.61 75.68 0.548 0.50(0.44) 0.89 26396.8 11801.00
25 11822.92 87.21 0.508 0.50(0.45) 0.90 30373.9 11500.00
26 11210.71 99.43 0.479 0.50(0.45) 0.91 35054.5 11000.00
27 10594.22 113.23 0.452 0.50(0.46) 0.92 41452.1 13000.00

28	10184.33	122.44	0.436	0.50	(0.46)	0.93	45679.0	10900.00
29	9687.82	131.22	0.426	0.50	(0.47)	0.93	49140.3	11130.00
30	9335.30	136.66	0.419	0.50	(0.47)	0.93	50906.9	13510.00
31	8930.28	143.10	0.412	0.50	(0.47)	0.93	52918.8	11620.00
32	7788.64	159.59	0.392	0.50	(0.47)	0.94	57495.2	12400.00
33	7506.04	163.27	0.388	0.50	(0.47)	0.94	58225.6	13500.00
34	6896.83	171.37	0.378	0.50	(0.47)	0.94	59812.7	12201.00
35	6255.35	181.00	0.367	0.50	(0.47)	0.94	61103.3	12111.00
36	5294.47	197.25	0.359	0.50	(0.47)	0.94	63026.2	12261.00
37	4807.01	206.86	0.353	0.50	(0.47)	0.94	63837.4	10200.00
38	4211.15	222.69	0.345	0.50	(0.47)	0.94	65075.3	10300.00
39	3969.15	229.74	0.341	0.50	(0.47)	0.94	65427.5	12010.00
40	3464.26	250.62	0.330	0.50	(0.47)	0.94	65755.9	12000.00
41	2387.35	320.24	0.292	0.50	(0.47)	0.95	66426.7	10100.00

TOTAL AREA (ACRES) = 66426.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 14638.63 Tc (MIN.) = 25.387  
EFFECTIVE AREA (ACRES) = 7195.94 AREA-AVERAGED Fm (INCH/HR) = 0.41  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.81  
TOTAL AREA (ACRES) = 66426.7  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124291.61 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13412.00 TO NODE 13700.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 176.93 DOWNSTREAM (FEET) = 173.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 260.10 CHANNEL SLOPE = 0.0151  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA (CFS) = 14638.63  
FLOW VELOCITY (FEET/SEC.) = 22.31 FLOW DEPTH (FEET) = 14.79  
TRAVEL TIME (MIN.) = 0.19 Tc (MIN.) = 25.58  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124551.71 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610508U.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	59.14	24.23	0.50 (0.49)	0.99	131.3	50800.00

TOTAL AREA (ACRES) = 131.3

\*\*\*\*\*

FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14059.08	14.87	1.313	0.50 (0.41)	0.82	3690.6	429.00
2	14398.57	16.63	1.240	0.50 (0.41)	0.82	4276.1	425.00
3	14402.16	16.84	1.232	0.50 (0.41)	0.82	4345.0	400.00
4	14102.24	18.71	1.162	0.50 (0.41)	0.81	4952.1	300.00
5	14595.42	25.04	0.971	0.50 (0.41)	0.81	7023.2	210.00
6	14634.53	25.53	0.962	0.50 (0.41)	0.81	7178.8	50700.00
7	14638.63	25.58	0.961	0.50 (0.41)	0.81	7195.9	50600.00
8	14634.95	25.94	0.954	0.50 (0.41)	0.81	7312.9	200.00
9	14627.46	26.70	0.939	0.50 (0.41)	0.81	7609.2	410.00
10	14613.07	28.42	0.905	0.50 (0.41)	0.81	8274.8	200.00
11	14604.58	29.25	0.889	0.50 (0.41)	0.82	8597.2	230.00
12	14596.69	29.86	0.877	0.50 (0.41)	0.82	8831.1	50500.00
13	14588.55	30.38	0.869	0.50 (0.41)	0.82	9023.6	220.50
14	14541.58	33.19	0.833	0.50 (0.41)	0.82	10066.0	120.00
15	14512.68	34.30	0.819	0.50 (0.41)	0.82	10483.8	110.00
16	14436.44	37.06	0.784	0.50 (0.41)	0.82	11555.0	100.00
17	14381.24	38.82	0.761	0.50 (0.41)	0.82	12227.2	100.00
18	14284.50	41.49	0.734	0.50 (0.41)	0.83	13231.1	100.00
19	14188.50	43.14	0.720	0.50 (0.42)	0.83	13920.7	130.00
20	13827.91	49.76	0.666	0.50 (0.42)	0.85	16682.5	10100.00
21	13659.36	52.68	0.647	0.50 (0.43)	0.85	17867.6	50100.00
22	13163.61	61.41	0.597	0.50 (0.43)	0.87	21196.1	20100.00
23	12721.57	68.87	0.571	0.50 (0.44)	0.88	23894.9	13600.00
24	12347.61	75.88	0.547	0.50 (0.44)	0.89	26396.8	11801.00
25	11822.92	87.41	0.507	0.50 (0.45)	0.90	30373.9	11500.00
26	11210.71	99.63	0.479	0.50 (0.45)	0.91	35054.5	11000.00
27	10594.22	113.44	0.452	0.50 (0.46)	0.92	41452.1	13000.00
28	10184.33	122.65	0.436	0.50 (0.46)	0.93	45679.0	10900.00
29	9687.82	131.43	0.425	0.50 (0.47)	0.93	49140.3	11130.00
30	9335.30	136.87	0.419	0.50 (0.47)	0.93	50906.9	13510.00
31	8930.28	143.32	0.411	0.50 (0.47)	0.93	52918.8	11620.00
32	7788.64	159.82	0.392	0.50 (0.47)	0.94	57495.2	12400.00
33	7506.04	163.50	0.388	0.50 (0.47)	0.94	58225.6	13500.00
34	6896.83	171.61	0.378	0.50 (0.47)	0.94	59812.7	12201.00
35	6255.35	181.24	0.367	0.50 (0.47)	0.94	61103.3	12111.00
36	5294.47	197.50	0.358	0.50 (0.47)	0.94	63026.2	12261.00
37	4807.01	207.12	0.353	0.50 (0.47)	0.94	63837.4	10200.00
38	4211.15	222.96	0.345	0.50 (0.47)	0.94	65075.3	10300.00
39	3969.15	230.01	0.341	0.50 (0.47)	0.94	65427.5	12010.00
40	3464.26	250.90	0.329	0.50 (0.47)	0.94	65755.9	12000.00
41	2387.35	320.55	0.291	0.50 (0.47)	0.95	66426.7	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124551.71 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	59.14	24.23	0.994	0.50 (0.49)	0.99	131.3	50800.00

LONGEST FLOWPATH FROM NODE 50800.00 TO NODE 13700.00 = 5946.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM	Q	Tc	Intensity	Fp (Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	---------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	14118.22	14.87	1.313	0.50 ( 0.41)	0.82	3771.2 429.00
2	14457.71	16.63	1.240	0.50 ( 0.41)	0.82	4366.2 425.00
3	14461.30	16.84	1.232	0.50 ( 0.41)	0.82	4436.3 400.00
4	14161.38	18.71	1.162	0.50 ( 0.41)	0.82	5053.5 300.00
5	14591.73	24.23	0.994	0.50 ( 0.41)	0.82	6890.7 50800.00
6	14651.90	25.04	0.971	0.50 ( 0.41)	0.82	7154.5 210.00
7	14689.88	25.53	0.962	0.50 ( 0.41)	0.82	7310.1 50700.00
8	14693.86	25.58	0.961	0.50 ( 0.41)	0.82	7327.2 50600.00
9	14689.34	25.94	0.954	0.50 ( 0.41)	0.82	7444.2 200.00
10	14680.07	26.70	0.939	0.50 ( 0.41)	0.82	7740.4 410.00
11	14661.70	28.42	0.905	0.50 ( 0.41)	0.82	8406.1 200.00
12	14651.29	29.25	0.889	0.50 ( 0.41)	0.82	8728.4 230.00
13	14641.97	29.86	0.877	0.50 ( 0.41)	0.82	8962.4 50500.00
14	14632.94	30.38	0.869	0.50 ( 0.41)	0.82	9154.9 220.50
15	14581.70	33.19	0.833	0.50 ( 0.41)	0.82	10197.2 120.00
16	14551.11	34.30	0.819	0.50 ( 0.41)	0.82	10615.1 110.00
17	14470.70	37.06	0.784	0.50 ( 0.41)	0.82	11686.2 100.00
18	14412.83	38.82	0.761	0.50 ( 0.41)	0.83	12358.5 100.00
19	14312.86	41.49	0.734	0.50 ( 0.41)	0.83	13362.4 100.00
20	14215.25	43.14	0.720	0.50 ( 0.42)	0.83	14051.9 130.00
21	13848.23	49.76	0.666	0.50 ( 0.42)	0.85	16813.8 10100.00
22	13677.47	52.68	0.647	0.50 ( 0.43)	0.85	17998.9 50100.00
23	13175.78	61.41	0.597	0.50 ( 0.43)	0.87	21327.4 20100.00
24	12730.67	68.87	0.571	0.50 ( 0.44)	0.88	24026.1 13600.00
25	12353.83	75.88	0.547	0.50 ( 0.44)	0.89	26528.0 11801.00
26	11824.40	87.41	0.507	0.50 ( 0.45)	0.90	30505.1 11500.00
27	11211.37	99.63	0.479	0.50 ( 0.45)	0.91	35185.8 11000.00
28	10594.83	113.44	0.452	0.50 ( 0.46)	0.92	41583.3 13000.00
29	10184.92	122.65	0.436	0.50 ( 0.46)	0.93	45810.2 10900.00
30	9688.40	131.43	0.425	0.50 ( 0.47)	0.93	49271.6 11130.00
31	9335.87	136.87	0.419	0.50 ( 0.47)	0.93	51038.1 13510.00
32	8930.84	143.32	0.411	0.50 ( 0.47)	0.93	53050.1 11620.00
33	7789.18	159.82	0.392	0.50 ( 0.47)	0.94	57626.5 12400.00
34	7506.57	163.50	0.388	0.50 ( 0.47)	0.94	58356.8 13500.00
35	6897.34	171.61	0.378	0.50 ( 0.47)	0.94	59944.0 12201.00
36	6255.85	181.24	0.367	0.50 ( 0.47)	0.94	61234.6 12111.00
37	5294.96	197.50	0.358	0.50 ( 0.47)	0.94	63157.5 12261.00
38	4807.49	207.12	0.353	0.50 ( 0.47)	0.94	63968.6 10200.00
39	4211.62	222.96	0.345	0.50 ( 0.47)	0.94	65206.6 10300.00
40	3969.61	230.01	0.341	0.50 ( 0.47)	0.94	65558.8 12010.00
41	3464.71	250.90	0.329	0.50 ( 0.47)	0.94	65887.1 12000.00
42	2387.75	320.55	0.291	0.50 ( 0.47)	0.95	66557.9 10100.00

TOTAL AREA (ACRES) = 66557.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 14693.86 Tc(MIN.) = 25.581  
EFFECTIVE AREA(ACRES) = 7327.21 AREA-AVERAGED Fm(INCH/HR) = 0.41  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.82  
TOTAL AREA(ACRES) = 66557.9  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124551.71 FEET.

=====

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 66557.9 TC(MIN.) = 25.58  
EFFECTIVE AREA(ACRES) = 7327.21 AREA-AVERAGED Fm(INCH/HR) = 0.41  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.817  
PEAK FLOW RATE(CFS) = 14693.86

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14118.22	14.87	1.313	0.50 ( 0.41)	0.82	3771.2	429.00
2	14457.71	16.63	1.240	0.50 ( 0.41)	0.82	4366.2	425.00
3	14461.30	16.84	1.232	0.50 ( 0.41)	0.82	4436.3	400.00
4	14161.38	18.71	1.162	0.50 ( 0.41)	0.82	5053.5	300.00
5	14591.73	24.23	0.994	0.50 ( 0.41)	0.82	6890.7	50800.00
6	14651.90	25.04	0.971	0.50 ( 0.41)	0.82	7154.5	210.00
7	14689.88	25.53	0.962	0.50 ( 0.41)	0.82	7310.1	50700.00
8	14693.86	25.58	0.961	0.50 ( 0.41)	0.82	7327.2	50600.00
9	14689.34	25.94	0.954	0.50 ( 0.41)	0.82	7444.2	200.00
10	14680.07	26.70	0.939	0.50 ( 0.41)	0.82	7740.4	410.00
11	14661.70	28.42	0.905	0.50 ( 0.41)	0.82	8406.1	200.00
12	14651.29	29.25	0.889	0.50 ( 0.41)	0.82	8728.4	230.00
13	14641.97	29.86	0.877	0.50 ( 0.41)	0.82	8962.4	50500.00
14	14632.94	30.38	0.869	0.50 ( 0.41)	0.82	9154.9	220.50
15	14581.70	33.19	0.833	0.50 ( 0.41)	0.82	10197.2	120.00
16	14551.11	34.30	0.819	0.50 ( 0.41)	0.82	10615.1	110.00
17	14470.70	37.06	0.784	0.50 ( 0.41)	0.82	11686.2	100.00
18	14412.83	38.82	0.761	0.50 ( 0.41)	0.83	12358.5	100.00
19	14312.86	41.49	0.734	0.50 ( 0.41)	0.83	13362.4	100.00
20	14215.25	43.14	0.720	0.50 ( 0.42)	0.83	14051.9	130.00
21	13848.23	49.76	0.666	0.50 ( 0.42)	0.85	16813.8	10100.00
22	13677.47	52.68	0.647	0.50 ( 0.43)	0.85	17998.9	50100.00
23	13175.78	61.41	0.597	0.50 ( 0.43)	0.87	21327.4	20100.00
24	12730.67	68.87	0.571	0.50 ( 0.44)	0.88	24026.1	13600.00
25	12353.83	75.88	0.547	0.50 ( 0.44)	0.89	26528.0	11801.00
26	11824.40	87.41	0.507	0.50 ( 0.45)	0.90	30505.1	11500.00
27	11211.37	99.63	0.479	0.50 ( 0.45)	0.91	35185.8	11000.00
28	10594.83	113.44	0.452	0.50 ( 0.46)	0.92	41583.3	13000.00
29	10184.92	122.65	0.436	0.50 ( 0.46)	0.93	45810.2	10900.00
30	9688.40	131.43	0.425	0.50 ( 0.47)	0.93	49271.6	11130.00
31	9335.87	136.87	0.419	0.50 ( 0.47)	0.93	51038.1	13510.00
32	8930.84	143.32	0.411	0.50 ( 0.47)	0.93	53050.1	11620.00
33	7789.18	159.82	0.392	0.50 ( 0.47)	0.94	57626.5	12400.00
34	7506.57	163.50	0.388	0.50 ( 0.47)	0.94	58356.8	13500.00
35	6897.34	171.61	0.378	0.50 ( 0.47)	0.94	59944.0	12201.00
36	6255.85	181.24	0.367	0.50 ( 0.47)	0.94	61234.6	12111.00
37	5294.96	197.50	0.358	0.50 ( 0.47)	0.94	63157.5	12261.00
38	4807.49	207.12	0.353	0.50 ( 0.47)	0.94	63968.6	10200.00
39	4211.62	222.96	0.345	0.50 ( 0.47)	0.94	65206.6	10300.00
40	3969.61	230.01	0.341	0.50 ( 0.47)	0.94	65558.8	12010.00
41	3464.71	250.90	0.329	0.50 ( 0.47)	0.94	65887.1	12000.00
42	2387.75	320.55	0.291	0.50 ( 0.47)	0.95	66557.9	10100.00

=====

END OF RATIONAL METHOD ANALYSIS

=====



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA 92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S36- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 5-YR RM EV APRIL 2019 ROKAMOTO \*  
\*\*\*\*\*

FILE NAME: RI05EV36.DAT  
TIME/DATE OF STUDY: 09:35 04/05/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 5.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 2.604
- 2) 10.00; 1.741
- 3) 15.00; 1.296
- 4) 20.00; 1.108
- 5) 25.00; 0.968
- 6) 30.00; 0.871
- 7) 40.00; 0.743
- 8) 50.00; 0.660
- 9) 60.00; 0.599
- 10) 90.00; 0.495
- 11) 120.00; 0.435
- 12) 180.00; 0.364
- 13) 360.00; 0.267
- 14) 1200.00; 0.116

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL: IN- / OUT-/PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:

- 1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13600.00 TO NODE 13600.50 IS CODE = 21  
-----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 488.61  
ELEVATION DATA: UPSTREAM(FEET) = 872.12 DOWNSTREAM(FEET) = 744.80

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 10.995  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.652  
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "OPEN BRUSH"	-	3.39	0.50	1.000	0	11.00

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA RUNOFF(CFS) = 3.52  
TOTAL AREA(ACRES) = 3.39 PEAK FLOW RATE(CFS) = 3.52

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13600.50 TO NODE 13601.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 744.80 DOWNSTREAM(FEET) = 707.32  
CHANNEL LENGTH THRU SUBAREA(FEET) = 418.30 CHANNEL SLOPE = 0.0896  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.489  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.45	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 6.84  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.79  
AVERAGE FLOW DEPTH(FEET) = 0.78 TRAVEL TIME(MIN.) = 1.84  
Tc(MIN.) = 12.83  
SUBAREA AREA(ACRES) = 7.45 SUBAREA RUNOFF(CFS) = 6.63  
EFFECTIVE AREA(ACRES) = 10.84 AREA-AVERAGED Fm(INCH/HR) = 0.50  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 10.8 PEAK FLOW RATE(CFS) = 9.65

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.88 FLOW VELOCITY(FEET/SEC.) = 4.15  
LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13601.00 = 906.91 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13601.00 TO NODE 13602.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 707.32 DOWNSTREAM(FEET) = 657.12
CHANNEL LENGTH THRU SUBAREA(FEET) = 777.60 CHANNEL SLOPE = 0.0646
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00

\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.267

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include USER-DEFINED entries with various soil types and areas.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 20.38

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.41

AVERAGE FLOW DEPTH(FEET) = 1.24 TRAVEL TIME(MIN.) = 2.94

Tc(MIN.) = 15.77

SUBAREA AREA(ACRES) = 30.96 SUBAREA RUNOFF(CFS) = 21.37

EFFECTIVE AREA(ACRES) = 41.80 AREA-AVERAGED Fm(INCH/HR) = 0.50

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 41.8 PEAK FLOW RATE(CFS) = 28.85

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.41 FLOW VELOCITY(FEET/SEC.) = 4.81

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13602.00 = 1684.51 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 13602.00 TO NODE 13603.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 657.12 DOWNSTREAM(FEET) = 584.58
CHANNEL LENGTH THRU SUBAREA(FEET) = 1186.54 CHANNEL SLOPE = 0.0611
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00

\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.118

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include USER-DEFINED entries with various soil types and areas.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 35.35

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.98

AVERAGE FLOW DEPTH(FEET) = 1.54 TRAVEL TIME(MIN.) = 3.97

Tc(MIN.) = 19.74

SUBAREA AREA(ACRES) = 23.36 SUBAREA RUNOFF(CFS) = 12.98

EFFECTIVE AREA(ACRES) = 65.16 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 65.2 PEAK FLOW RATE(CFS) = 36.22

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.55 FLOW VELOCITY(FEET/SEC.) = 5.00

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13603.00 = 2871.05 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 584.58 DOWNSTREAM(FEET) = 544.91
CHANNEL LENGTH THRU SUBAREA(FEET) = 860.98 CHANNEL SLOPE = 0.0461
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00

\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.029

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include USER-DEFINED entries with various soil types and areas.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 41.27

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.64

AVERAGE FLOW DEPTH(FEET) = 1.72 TRAVEL TIME(MIN.) = 3.09

Tc(MIN.) = 22.83

SUBAREA AREA(ACRES) = 21.24 SUBAREA RUNOFF(CFS) = 10.10

EFFECTIVE AREA(ACRES) = 86.40 AREA-AVERAGED Fm(INCH/HR) = 0.50

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 86.4 PEAK FLOW RATE(CFS) = 41.10

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.72 FLOW VELOCITY(FEET/SEC.) = 4.63

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13620.00 = 3732.03 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<

\*\*\*\*\*
FLOW PROCESS FROM NODE 13522.00 TO NODE 13522.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: S35X05.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

Table with 7 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Fp(Fm) (INCH/HR), Ap (ACRES), Ae (ACRES), HEADWATER NODE.



1 100.55 73.18 0.50( 0.47) 0.95 1498.1 13510.00  
 2 54.12 90.88 0.50( 0.47) 0.94 1579.8 13500.00  
 TOTAL AREA (ACRES) = 1579.8

\*\*\*\*\*

FLOW PROCESS FROM NODE 13522.00 TO NODE 13522.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	100.55	73.18	0.50( 0.47)	0.95	1498.1	13510.00
2	54.12	90.88	0.50( 0.47)	0.94	1579.8	13500.00
TOTAL AREA (ACRES) =						1579.8

\*\*\*\*\*

FLOW PROCESS FROM NODE 13522.00 TO NODE 13620.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 632.19 DOWNSTREAM(FEET) = 544.91

CHANNEL LENGTH THRU SUBAREA(FEET) = 2062.96 CHANNEL SLOPE = 0.0423

CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00

\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.538

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	17.68	0.50	1.000	-
USER-DEFINED	-	2.36	0.50	1.000	-
USER-DEFINED	-	0.60	0.50	1.000	-
USER-DEFINED	-	0.22	0.50	1.000	-
USER-DEFINED	-	2.22	0.50	1.000	-
USER-DEFINED	-	3.42	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 101.00

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.63

AVERAGE FLOW DEPTH(FEET) = 2.10 TRAVEL TIME(MIN.) = 4.51

Tc(MIN.) = 77.69

SUBAREA AREA(ACRES) = 26.50 SUBAREA RUNOFF(CFS) = 0.89

EFFECTIVE AREA(ACRES) = 1524.58 AREA-AVERAGED Fm(INCH/HR) = 0.47

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.95

TOTAL AREA(ACRES) = 1606.3 PEAK FLOW RATE(CFS) = 100.55

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.10 FLOW VELOCITY(FEET/SEC.) = 7.64

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13620.00 TO NODE 13620.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 77.69

\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.538

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.44	0.50	1.000	-
USER-DEFINED	-	0.01	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 1.45 SUBAREA RUNOFF(CFS) = 0.05

EFFECTIVE AREA(ACRES) = 1526.03 AREA-AVERAGED Fm(INCH/HR) = 0.47

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.95

TOTAL AREA(ACRES) = 1607.8 PEAK FLOW RATE(CFS) = 100.55

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	100.55	77.69	0.538	0.50( 0.47)	0.95	1526.0	13510.00
2	54.12	96.14	0.483	0.50( 0.47)	0.95	1607.8	13500.00
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.							

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	41.10	22.83	1.029	0.50( 0.50)	1.00	86.4	13600.00
LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13620.00 = 3732.03 FEET.							

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	141.65	22.83	1.029	0.50( 0.48)	0.96	534.9	13600.00
2	103.47	77.69	0.538	0.50( 0.48)	0.95	1612.4	13510.00
3	54.12	96.14	0.483	0.50( 0.47)	0.95	1694.2	13500.00
TOTAL AREA(ACRES) = 1694.2							

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 141.65 Tc(MIN.) = 22.831

EFFECTIVE AREA(ACRES) = 534.86 AREA-AVERAGED Fm(INCH/HR) = 0.48

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.95

TOTAL AREA(ACRES) = 1694.2

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13620.00 TO NODE 13640.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 544.91 DOWNSTREAM(FEET) = 489.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 1384.37 CHANNEL SLOPE = 0.0404

CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.956  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.39	0.50	1.000	-
USER-DEFINED	-	16.30	0.50	1.000	-
USER-DEFINED	-	4.08	0.50	1.000	-
USER-DEFINED	-	12.36	0.50	1.000	-
USER-DEFINED	-	11.23	0.50	1.000	-
USER-DEFINED	-	5.16	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 152.83  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.31  
 AVERAGE FLOW DEPTH (FEET) = 2.48 TRAVEL TIME (MIN.) = 2.78  
 Tc (MIN.) = 25.61  
 SUBAREA AREA (ACRES) = 54.52 SUBAREA RUNOFF (CFS) = 22.37  
 EFFECTIVE AREA (ACRES) = 589.38 AREA-AVERAGED Fm (INCH/HR) = 0.48  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA (ACRES) = 1748.7 PEAK FLOW RATE (CFS) = 252.29

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 2.99 FLOW VELOCITY (FEET/SEC.) = 9.42  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 25.61  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.956  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	53.93	0.50	1.000	-
USER-DEFINED	-	0.45	0.50	1.000	-
USER-DEFINED	-	3.98	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 58.36 SUBAREA RUNOFF (CFS) = 23.95  
 EFFECTIVE AREA (ACRES) = 647.74 AREA-AVERAGED Fm (INCH/HR) = 0.48  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA (ACRES) = 1807.1 PEAK FLOW RATE (CFS) = 276.24

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P201XX05.DNA  
 MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap (DECIMAL)	Ae (ACRES)	HEADWATER NODE
1	73.57	19.49	0.50 (0.43)	0.85	133.8	20100.00

TOTAL AREA (ACRES) = 133.8

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap (DECIMAL)	Ae (ACRES)	HEADWATER NODE
1	276.24	25.61	0.956	0.50 (0.48)	0.96	647.7	13600.00
2	103.47	80.76	0.527	0.50 (0.48)	0.95	1725.3	13510.00
3	54.12	99.73	0.476	0.50 (0.48)	0.95	1807.1	13500.00

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap (DECIMAL)	Ae (ACRES)	HEADWATER NODE
1	73.57	19.49	1.127	0.50 (0.43)	0.85	133.8	20100.00

LONGEST FLOWPATH FROM NODE 20100.00 TO NODE 13640.00 = 5247.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap (DECIMAL)	Ae (ACRES)	HEADWATER NODE
1	349.80	19.49	1.127	0.50 (0.47)	0.94	626.8	20100.00
2	331.83	25.61	0.956	0.50 (0.47)	0.95	781.5	13600.00
3	113.95	80.76	0.527	0.50 (0.47)	0.95	1859.1	13510.00
4	61.40	99.73	0.476	0.50 (0.47)	0.94	1940.9	13500.00

TOTAL AREA (ACRES) = 1940.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 349.80 Tc (MIN.) = 19.493  
 EFFECTIVE AREA (ACRES) = 626.82 AREA-AVERAGED Fm (INCH/HR) = 0.47  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.94  
 TOTAL AREA (ACRES) = 1940.9  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13640.00 TO NODE 13641.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 489.00 DOWNSTREAM (FEET) = 436.89  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 2994.52 CHANNEL SLOPE = 0.0174  
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.946

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.96	0.50	1.000	-
USER-DEFINED	-	0.01	0.50	1.000	-
USER-DEFINED	-	1.56	0.50	1.000	-
USER-DEFINED	-	10.45	0.50	1.000	-
USER-DEFINED	-	44.94	0.50	1.000	-
USER-DEFINED	-	9.66	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 363.38  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.53  
 AVERAGE FLOW DEPTH(FEET) = 4.01 TRAVEL TIME(MIN.) = 6.63  
 Tc(MIN.) = 26.12  
 SUBAREA AREA(ACRES) = 67.58 SUBAREA RUNOFF(CFS) = 27.13  
 EFFECTIVE AREA(ACRES) = 694.40 AREA-AVERAGED Fm(INCH/HR) = 0.47  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.95  
 TOTAL AREA(ACRES) = 2008.4 PEAK FLOW RATE(CFS) = 349.80  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 3.95 FLOW VELOCITY(FEET/SEC.) = 7.45  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13641.00 = 25056.61 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13641.00 TO NODE 13641.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 26.12  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.946  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 16.49 0.50 1.000 -  
 USER-DEFINED - 20.39 0.50 1.000 -  
 USER-DEFINED - 7.02 0.50 1.000 -  
 USER-DEFINED - 12.58 0.50 1.000 -  
 USER-DEFINED - 42.49 0.50 1.000 -  
 USER-DEFINED - 5.73 0.50 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 104.70 SUBAREA RUNOFF(CFS) = 42.04  
 EFFECTIVE AREA(ACRES) = 799.10 AREA-AVERAGED Fm(INCH/HR) = 0.48  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.95  
 TOTAL AREA(ACRES) = 2113.1 PEAK FLOW RATE(CFS) = 349.80  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13641.00 TO NODE 13641.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 26.12  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.946  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 1.78 0.50 1.000 -  
 USER-DEFINED - 6.25 0.50 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 8.03 SUBAREA RUNOFF(CFS) = 3.22  
 EFFECTIVE AREA(ACRES) = 807.13 AREA-AVERAGED Fm(INCH/HR) = 0.48  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.95  
 TOTAL AREA(ACRES) = 2121.2 PEAK FLOW RATE(CFS) = 349.80  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13641.00 TO NODE 13642.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 436.89 DOWNSTREAM(FEET) = 394.80  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2814.16 CHANNEL SLOPE = 0.0150  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.837

SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 0.67 0.50 1.000 -  
 USER-DEFINED - 24.24 0.50 1.000 -  
 USER-DEFINED - 1.34 0.50 1.000 -  
 USER-DEFINED - 74.98 0.50 1.000 -  
 USER-DEFINED - 101.12 0.50 1.000 -  
 USER-DEFINED - 16.90 0.50 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 383.14  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.21  
 AVERAGE FLOW DEPTH(FEET) = 4.21 TRAVEL TIME(MIN.) = 6.50  
 Tc(MIN.) = 32.62  
 SUBAREA AREA(ACRES) = 219.25 SUBAREA RUNOFF(CFS) = 66.54  
 EFFECTIVE AREA(ACRES) = 1026.38 AREA-AVERAGED Fm(INCH/HR) = 0.48  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA(ACRES) = 2340.4 PEAK FLOW RATE(CFS) = 349.80  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 4.07 FLOW VELOCITY(FEET/SEC.) = 7.04  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13642.00 = 27870.77 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13642.00 TO NODE 13642.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 32.62  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.837  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 9.95 0.50 1.000 -  
 USER-DEFINED - 10.02 0.50 1.000 -  
 USER-DEFINED - 4.45 0.50 1.000 -  
 USER-DEFINED - 179.37 0.50 1.000 -  
 USER-DEFINED - 11.47 0.50 1.000 -  
 USER-DEFINED - 0.17 0.50 0.850 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 215.43 SUBAREA RUNOFF(CFS) = 65.39  
 EFFECTIVE AREA(ACRES) = 1241.81 AREA-AVERAGED Fm(INCH/HR) = 0.49  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.97  
 TOTAL AREA(ACRES) = 2555.8 PEAK FLOW RATE(CFS) = 393.60

```

*****
FLOW PROCESS FROM NODE 13642.00 TO NODE 13642.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 32.62
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.837
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp      Ap      SCS
LAND USE                GROUP  (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED            -         0.03      0.50     0.850   -
USER-DEFINED            -         5.14      0.50     1.000   -
USER-DEFINED            -        11.22      0.50     1.000   -
USER-DEFINED            -         0.33      0.50     1.000   -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 16.72      SUBAREA RUNOFF(CFS) = 5.08
EFFECTIVE AREA(ACRES) = 1258.53  AREA-AVERAGED Fm(INCH/HR) = 0.49
AREA-AVERAGED Fp(INCH/HR) = 0.50  AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 2572.6      PEAK FLOW RATE(CFS) = 398.68
*****
FLOW PROCESS FROM NODE 13642.00 TO NODE 13643.00 IS CODE = 51
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 394.80  DOWNSTREAM(FEET) = 342.39
CHANNEL LENGTH THRU SUBAREA(FEET) = 2913.57  CHANNEL SLOPE = 0.0180
CHANNEL BASE(FEET) = 0.00  "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040  MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.759
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp      Ap      SCS
LAND USE                GROUP  (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED            -         0.22      0.50     1.000   -
USER-DEFINED            -         2.17      0.50     1.000   -
USER-DEFINED            -         9.19      0.50     1.000   -
USER-DEFINED            -        67.57      0.50     1.000   -
USER-DEFINED            -        35.19      0.50     1.000   -
USER-DEFINED            -        30.67      0.50     1.000   -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 415.55
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.88
AVERAGE FLOW DEPTH(FEET) = 4.19  TRAVEL TIME(MIN.) = 6.16
Tc(MIN.) = 38.79
SUBAREA AREA(ACRES) = 145.01      SUBAREA RUNOFF(CFS) = 33.71
EFFECTIVE AREA(ACRES) = 1403.54  AREA-AVERAGED Fm(INCH/HR) = 0.49
AREA-AVERAGED Fp(INCH/HR) = 0.50  AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 2717.6      PEAK FLOW RATE(CFS) = 398.68
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 4.13  FLOW VELOCITY(FEET/SEC.) = 7.79
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13643.00 = 30784.34 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13643.00 TO NODE 13643.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 38.79
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.759
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp      Ap      SCS
LAND USE                GROUP  (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED            -         0.89      0.50     1.000   -
USER-DEFINED            -        20.65      0.50     1.000   -
USER-DEFINED            -         2.69      0.50     1.000   -
USER-DEFINED            -         8.45      0.50     1.000   -
USER-DEFINED            -        96.93      0.50     1.000   -
USER-DEFINED            -        13.19      0.50     1.000   -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 142.80      SUBAREA RUNOFF(CFS) = 33.20
EFFECTIVE AREA(ACRES) = 1546.34  AREA-AVERAGED Fm(INCH/HR) = 0.49
AREA-AVERAGED Fp(INCH/HR) = 0.50  AREA-AVERAGED Ap = 0.98
TOTAL AREA(ACRES) = 2860.4      PEAK FLOW RATE(CFS) = 398.68
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
*****
FLOW PROCESS FROM NODE 13643.00 TO NODE 13643.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 38.79
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.759
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp      Ap      SCS
LAND USE                GROUP  (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED            -        42.54      0.50     1.000   -
USER-DEFINED            -        16.96      0.50     1.000   -
USER-DEFINED            -        80.60      0.50     1.000   -
USER-DEFINED            -         1.56      0.50     1.000   -
USER-DEFINED            -         2.00      0.50     1.000   -
USER-DEFINED            -         3.11      0.50     1.000   -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 146.77      SUBAREA RUNOFF(CFS) = 34.12
EFFECTIVE AREA(ACRES) = 1693.11  AREA-AVERAGED Fm(INCH/HR) = 0.49
AREA-AVERAGED Fp(INCH/HR) = 0.50  AREA-AVERAGED Ap = 0.98
TOTAL AREA(ACRES) = 3007.1      PEAK FLOW RATE(CFS) = 410.34
*****
FLOW PROCESS FROM NODE 13643.00 TO NODE 13660.00 IS CODE = 51
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 342.39  DOWNSTREAM(FEET) = 300.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1591.23  CHANNEL SLOPE = 0.0266
CHANNEL BASE(FEET) = 0.00  "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040  MAXIMUM DEPTH(FEET) = 20.00
* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.729

```

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.89	0.50	1.000	-
USER-DEFINED	-	23.73	0.50	1.000	-
USER-DEFINED	-	0.27	0.50	1.000	-
USER-DEFINED	-	19.87	0.50	1.000	-
USER-DEFINED	-	6.40	0.50	1.000	-
USER-DEFINED	-	3.14	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 415.93  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.14  
AVERAGE FLOW DEPTH(FEET) = 3.90 TRAVEL TIME(MIN.) = 2.90  
Tc(MIN.) = 41.69  
SUBAREA AREA(ACRES) = 54.30 SUBAREA RUNOFF(CFS) = 11.18  
EFFECTIVE AREA(ACRES) = 1747.41 AREA-AVERAGED Fm(INCH/HR) = 0.49  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.98  
TOTAL AREA(ACRES) = 3061.4 PEAK FLOW RATE(CFS) = 410.34  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 3.88 FLOW VELOCITY(FEET/SEC.) = 9.09  
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 32375.57 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
-----  
MAINLINE Tc(MIN.) = 41.69  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.729  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.67	0.50	1.000	-
USER-DEFINED	-	9.52	0.50	1.000	-
USER-DEFINED	-	0.71	0.50	1.000	-
USER-DEFINED	-	0.22	0.50	1.000	-
USER-DEFINED	-	39.42	0.50	1.000	-
USER-DEFINED	-	0.62	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA(ACRES) = 51.16 SUBAREA RUNOFF(CFS) = 10.53  
EFFECTIVE AREA(ACRES) = 1798.57 AREA-AVERAGED Fm(INCH/HR) = 0.49  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.98  
TOTAL AREA(ACRES) = 3112.6 PEAK FLOW RATE(CFS) = 410.34  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
-----  
MAINLINE Tc(MIN.) = 41.69  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.729  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
USER-DEFINED	-	0.11	0.50	1.000	-
USER-DEFINED	-	0.77	0.50	1.000	-
USER-DEFINED	-	0.22	0.50	1.000	-
USER-DEFINED	-	2.69	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA(ACRES) = 3.79 SUBAREA RUNOFF(CFS) = 0.78  
EFFECTIVE AREA(ACRES) = 1802.36 AREA-AVERAGED Fm(INCH/HR) = 0.49  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.98  
TOTAL AREA(ACRES) = 3116.4 PEAK FLOW RATE(CFS) = 410.34  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13643.00 TO NODE 13660.00 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13659.00 TO NODE 13659.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 2P05EVAA.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	233.64	16.39	0.50( 0.18)	0.36	170.4	110.00
2	231.85	19.13	0.50( 0.19)	0.37	201.2	100.00
3	223.62	20.82	0.50( 0.19)	0.38	212.8	100.00
4	190.12	24.85	0.50( 0.20)	0.40	221.1	130.00
TOTAL AREA(ACRES) =		221.1				

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13659.00 TO NODE 13660.00 IS CODE = 31  
-----

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

-----  
ELEVATION DATA: UPSTREAM(FEET) = 338.00 DOWNSTREAM(FEET) = 300.00  
FLOW LENGTH(FEET) = 881.07 MANNING'S N = 0.013  
DEPTH OF FLOW IN 57.0 INCH PIPE IS 43.0 INCHES  
PIPE-FLOW VELOCITY(FEET/SEC.) = 28.64  
ESTIMATED PIPE DIAMETER(INCH) = 57.00 NUMBER OF PIPES = 1  
PIPE-FLOW(CFS) = 410.34  
PIPE TRAVEL TIME(MIN.) = 0.51 Tc(MIN.) = 42.20  
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
------------------	------------	--------------	------------------------	---------------------	----	---------------	-------------------

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	410.34	42.20	0.725	0.50 ( 0.49)	0.98	1802.4	20100.00
2	348.87	48.93	0.669	0.50 ( 0.49)	0.98	1957.1	13600.00
3	113.95	111.68	0.452	0.50 ( 0.48)	0.97	3034.7	13510.00
4	61.40	135.77	0.416	0.50 ( 0.48)	0.97	3116.4	13500.00

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	233.64	16.39	1.244	0.50 ( 0.18)	0.36	170.4	110.00
2	231.85	19.13	1.141	0.50 ( 0.19)	0.37	201.2	100.00
3	223.62	20.82	1.085	0.50 ( 0.19)	0.38	212.8	100.00
4	190.12	24.85	0.972	0.50 ( 0.20)	0.40	221.1	130.00

LONGEST FLOWPATH FROM NODE 130.00 TO NODE 13660.00 = 6327.50 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	643.98	16.39	1.244	0.50 ( 0.43)	0.86	870.6	110.00
2	642.18	19.13	1.141	0.50 ( 0.43)	0.86	1018.1	100.00
3	633.96	20.82	1.085	0.50 ( 0.43)	0.86	1101.9	100.00
4	600.45	24.85	0.972	0.50 ( 0.44)	0.88	1282.3	130.00
5	539.47	42.20	0.725	0.50 ( 0.46)	0.92	2023.5	20100.00
6	464.24	48.93	0.669	0.50 ( 0.46)	0.92	2178.2	13600.00
7	180.59	111.68	0.452	0.50 ( 0.46)	0.93	3255.8	13510.00
8	122.83	135.77	0.416	0.50 ( 0.46)	0.93	3337.5	13500.00

TOTAL AREA (ACRES) = 3337.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 643.98 Tc (MIN.) = 16.395  
EFFECTIVE AREA (ACRES) = 870.58 AREA-AVERAGED Fm (INCH/HR) = 0.43  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.92  
TOTAL AREA (ACRES) = 3337.5  
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 16.39

\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.244

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.11	0.50	1.000	-
USER-DEFINED	-	0.44	0.50	1.000	-
USER-DEFINED	-	1.49	0.50	1.000	-
USER-DEFINED	-	1.70	0.50	1.000	-
USER-DEFINED	-	1.09	0.50	1.000	-
USER-DEFINED	-	18.57	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 24.40 SUBAREA RUNOFF (CFS) = 16.32  
EFFECTIVE AREA (ACRES) = 894.98 AREA-AVERAGED Fm (INCH/HR) = 0.43  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.86  
TOTAL AREA (ACRES) = 3361.9 PEAK FLOW RATE (CFS) = 654.34

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	654.34	16.39	1.244	0.50 ( 0.43)	0.86	895.0	110.00
2	665.60	19.13	1.141	0.50 ( 0.43)	0.86	1042.5	100.00
3	660.79	20.82	1.085	0.50 ( 0.43)	0.87	1126.3	100.00
4	624.56	24.85	0.972	0.50 ( 0.44)	0.88	1306.7	130.00
5	539.47	42.20	0.725	0.50 ( 0.46)	0.92	2047.9	20100.00
6	464.24	48.93	0.669	0.50 ( 0.46)	0.92	2202.6	13600.00
7	180.59	111.68	0.452	0.50 ( 0.47)	0.93	3280.2	13510.00
8	122.83	135.77	0.416	0.50 ( 0.46)	0.93	3361.9	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 665.60 Tc (MIN.) = 19.13  
AREA-AVERAGED Fm (INCH/HR) = 0.43 AREA-AVERAGED Fp (INCH/HR) = 0.50  
AREA-AVERAGED Ap = 0.86 EFFECTIVE AREA (ACRES) = 1042.49

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 19.13

\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.141

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	12.39	0.50	1.000	-
USER-DEFINED	-	2.30	0.50	1.000	-
USER-DEFINED	-	5.19	0.50	1.000	-
USER-DEFINED	-	28.71	0.50	1.000	-
USER-DEFINED	-	0.17	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 48.76 SUBAREA RUNOFF (CFS) = 28.11  
EFFECTIVE AREA (ACRES) = 1091.25 AREA-AVERAGED Fm (INCH/HR) = 0.43  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.87  
TOTAL AREA (ACRES) = 3410.7 PEAK FLOW RATE (CFS) = 693.71

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13660.00 TO NODE 13680.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 300.00 DOWNSTREAM (FEET) = 288.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 933.89 CHANNEL SLOPE = 0.0128  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.077

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.22	0.50	1.000	-
USER-DEFINED	-	9.23	0.50	1.000	-
USER-DEFINED	-	0.54	0.50	1.000	-
USER-DEFINED	-	5.66	0.50	1.000	-
USER-DEFINED	-	3.66	0.50	1.000	-
USER-DEFINED	-	0.67	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 698.90  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.91  
 AVERAGE FLOW DEPTH(FEET) = 5.43 TRAVEL TIME(MIN.) = 1.97  
 Tc(MIN.) = 21.10  
 SUBAREA AREA(ACRES) = 19.98 SUBAREA RUNOFF(CFS) = 10.38  
 EFFECTIVE AREA(ACRES) = 1111.23 AREA-AVERAGED Fm(INCH/HR) = 0.44  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.87  
 TOTAL AREA(ACRES) = 3430.6 PEAK FLOW RATE(CFS) = 693.71  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 5.41 FLOW VELOCITY(FEET/SEC.) = 7.89  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13680.00 = 34190.53 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 21.10  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.077  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.56	0.50	1.000	-
USER-DEFINED	-	9.40	0.50	1.000	-
USER-DEFINED	-	2.76	0.50	1.000	-
USER-DEFINED	-	17.38	0.50	1.000	-
USER-DEFINED	-	2.46	0.50	1.000	-
USER-DEFINED	-	5.56	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 39.12 SUBAREA RUNOFF(CFS) = 20.32  
 EFFECTIVE AREA(ACRES) = 1150.35 AREA-AVERAGED Fm(INCH/HR) = 0.44  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.88  
 TOTAL AREA(ACRES) = 3469.8 PEAK FLOW RATE(CFS) = 693.71  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 21.10  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.077  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.65	0.50	1.000	-
USER-DEFINED	-	1.70	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 2.35 SUBAREA RUNOFF(CFS) = 1.22  
 EFFECTIVE AREA(ACRES) = 1152.70 AREA-AVERAGED Fm(INCH/HR) = 0.44  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.88  
 TOTAL AREA(ACRES) = 3472.1 PEAK FLOW RATE(CFS) = 693.71

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13660.00 TO NODE 13680.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 21.10  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.077  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.29	0.50	1.000	-
USER-DEFINED	-	31.25	0.50	1.000	-
USER-DEFINED	-	0.22	0.50	1.000	-
USER-DEFINED	-	6.26	0.50	1.000	-
USER-DEFINED	-	0.07	0.50	1.000	-
USER-DEFINED	-	0.22	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 43.31 SUBAREA RUNOFF(CFS) = 22.49  
 EFFECTIVE AREA(ACRES) = 1196.01 AREA-AVERAGED Fm(INCH/HR) = 0.44  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.88  
 TOTAL AREA(ACRES) = 3515.4 PEAK FLOW RATE(CFS) = 693.71  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 21.10  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.077  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	2.47	0.50	0.850	-
USER-DEFINED	-	3.06	0.50	0.850	-
USER-DEFINED	-	17.76	0.50	0.500	-
USER-DEFINED	-	7.31	0.50	0.500	-
USER-DEFINED	-	0.34	0.50	1.000	-
USER-DEFINED	-	8.22	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.659  
 SUBAREA AREA(ACRES) = 39.16 SUBAREA RUNOFF(CFS) = 26.36  
 EFFECTIVE AREA(ACRES) = 1235.17 AREA-AVERAGED Fm(INCH/HR) = 0.44  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.87  
 TOTAL AREA(ACRES) = 3554.6 PEAK FLOW RATE(CFS) = 712.14

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap (ACRES)	Ae (ACRES)	HEADWATER NODE
------------------	------------	--------------	------------------------	---------------------	---------------	---------------	-------------------

1	716.62	18.37	1.169	0.50	( 0.44)	0.87	1087.7	110.00
2	712.14	21.10	1.077	0.50	( 0.44)	0.87	1235.2	100.00
3	702.65	22.79	1.030	0.50	( 0.44)	0.88	1318.9	100.00
4	658.25	26.85	0.932	0.50	( 0.44)	0.89	1499.4	130.00
5	539.47	44.30	0.707	0.50	( 0.46)	0.92	2240.5	20100.00
6	464.24	51.11	0.653	0.50	( 0.46)	0.92	2395.3	13600.00
7	180.59	114.44	0.446	0.50	( 0.47)	0.93	3472.8	13510.00
8	122.83	138.81	0.413	0.50	( 0.46)	0.93	3554.6	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 716.62 Tc(MIN.) = 18.37  
 AREA-AVERAGED Fm(INCH/HR) = 0.44 AREA-AVERAGED Fp(INCH/HR) = 0.50  
 AREA-AVERAGED Ap = 0.87 EFFECTIVE AREA(ACRES) = 1087.66

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 18.37  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.169  
 SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/	SCS SOIL	AREA	Fp	Ap	SCS
LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
USER-DEFINED	-	0.53	0.50	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 0.53 SUBAREA RUNOFF(CFS) = 0.32  
 EFFECTIVE AREA(ACRES) = 1088.19 AREA-AVERAGED Fm(INCH/HR) = 0.44  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.87  
 TOTAL AREA(ACRES) = 3555.1 PEAK FLOW RATE(CFS) = 716.94

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13680.00 TO NODE 13682.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 288.00 DOWNSTREAM(FEET) = 242.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2860.77 CHANNEL SLOPE = 0.0161  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.000  
 SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/	SCS SOIL	AREA	Fp	Ap	SCS
LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
USER-DEFINED	-	0.22	0.50	1.000	-
USER-DEFINED	-	5.28	0.50	1.000	-
USER-DEFINED	-	0.52	0.50	1.000	-
USER-DEFINED	-	3.61	0.50	1.000	-
USER-DEFINED	-	0.67	0.50	1.000	-
USER-DEFINED	-	1.37	0.50	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 719.57  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.66  
 AVERAGE FLOW DEPTH(FEET) = 5.26 TRAVEL TIME(MIN.) = 5.50  
 Tc(MIN.) = 23.87  
 SUBAREA AREA(ACRES) = 11.67 SUBAREA RUNOFF(CFS) = 5.25

EFFECTIVE AREA(ACRES) = 1099.86 AREA-AVERAGED Fm(INCH/HR) = 0.44  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.88  
 TOTAL AREA(ACRES) = 3566.8 PEAK FLOW RATE(CFS) = 716.94  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 5.25 FLOW VELOCITY(FEET/SEC.) = 8.66  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13682.00 = 37051.30 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 23.87  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.000  
 SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/	SCS SOIL	AREA	Fp	Ap	SCS
LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
USER-DEFINED	-	6.90	0.50	1.000	-
USER-DEFINED	-	23.04	0.50	1.000	-
USER-DEFINED	-	1.18	0.50	1.000	-
USER-DEFINED	-	1.56	0.50	1.000	-
USER-DEFINED	-	53.20	0.50	1.000	-
USER-DEFINED	-	2.08	0.50	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 87.96 SUBAREA RUNOFF(CFS) = 39.53  
 EFFECTIVE AREA(ACRES) = 1187.82 AREA-AVERAGED Fm(INCH/HR) = 0.44  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.88  
 TOTAL AREA(ACRES) = 3654.7 PEAK FLOW RATE(CFS) = 716.94  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 23.87  
 \* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.000  
 SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/	SCS SOIL	AREA	Fp	Ap	SCS
LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
USER-DEFINED	-	0.01	0.50	1.000	-
USER-DEFINED	-	0.18	0.50	1.000	-
USER-DEFINED	-	0.38	0.50	1.000	-
USER-DEFINED	-	0.22	0.50	1.000	-
USER-DEFINED	-	7.73	0.50	1.000	-
USER-DEFINED	-	4.37	0.50	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 12.89 SUBAREA RUNOFF(CFS) = 5.79  
 EFFECTIVE AREA(ACRES) = 1200.71 AREA-AVERAGED Fm(INCH/HR) = 0.44  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.89  
 TOTAL AREA(ACRES) = 3667.6 PEAK FLOW RATE(CFS) = 716.94  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*



FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 23.87

\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.000

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	2.57	0.50	1.000	-
USER-DEFINED	-	1.97	0.50	1.000	-
USER-DEFINED	-	1.00	0.50	1.000	-
USER-DEFINED	-	2.98	0.50	1.000	-
USER-DEFINED	-	2.39	0.50	1.000	-
USER-DEFINED	-	1.67	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 12.58 SUBAREA RUNOFF (CFS) = 5.65

EFFECTIVE AREA (ACRES) = 1213.29 AREA-AVERAGED Fm (INCH/HR) = 0.44

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.89

TOTAL AREA (ACRES) = 3680.2 PEAK FLOW RATE (CFS) = 716.94

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 23.87

\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.000

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.44	0.50	1.000	-
USER-DEFINED	-	2.65	0.50	0.850	-
USER-DEFINED	-	1.16	0.50	0.850	-
USER-DEFINED	-	0.47	0.50	0.500	-
USER-DEFINED	-	0.25	0.50	0.500	-
USER-DEFINED	-	20.24	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.963

SUBAREA AREA (ACRES) = 25.21 SUBAREA RUNOFF (CFS) = 11.75

EFFECTIVE AREA (ACRES) = 1238.50 AREA-AVERAGED Fm (INCH/HR) = 0.44

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.89

TOTAL AREA (ACRES) = 3705.4 PEAK FLOW RATE (CFS) = 716.94

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 23.87

\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.000

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.08	0.50	1.000	-

USER-DEFINED	-	6.75	0.50	1.000	-
USER-DEFINED	-	0.02	0.50	1.000	-
USER-DEFINED	-	0.93	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 14.78 SUBAREA RUNOFF (CFS) = 6.64

EFFECTIVE AREA (ACRES) = 1253.28 AREA-AVERAGED Fm (INCH/HR) = 0.45

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.89

TOTAL AREA (ACRES) = 3720.2 PEAK FLOW RATE (CFS) = 716.94

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13682.00 TO NODE 13683.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM (FEET) = 242.00 DOWNSTREAM (FEET) = 208.53

CHANNEL LENGTH THRU SUBAREA (FEET) = 2526.22 CHANNEL SLOPE = 0.0132

CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00

\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.889

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.49	0.50	1.000	-
USER-DEFINED	-	13.31	0.50	1.000	-
USER-DEFINED	-	0.87	0.50	1.000	-
USER-DEFINED	-	20.26	0.50	1.000	-
USER-DEFINED	-	1.21	0.50	1.000	-
USER-DEFINED	-	0.05	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 724.67

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.08

AVERAGE FLOW DEPTH (FEET) = 5.47 TRAVEL TIME (MIN.) = 5.21

Tc (MIN.) = 29.08

SUBAREA AREA (ACRES) = 44.19 SUBAREA RUNOFF (CFS) = 15.46

EFFECTIVE AREA (ACRES) = 1297.47 AREA-AVERAGED Fm (INCH/HR) = 0.45

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.89

TOTAL AREA (ACRES) = 3764.4 PEAK FLOW RATE (CFS) = 716.94

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 5.45 FLOW VELOCITY (FEET/SEC.) = 8.05

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13683.00 = 39577.52 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 29.08

\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.889

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	12.56	0.50	1.000	-

USER-DEFINED - 0.81 0.50 1.000 -  
 USER-DEFINED - 0.01 0.50 1.000 -  
 USER-DEFINED - 1.11 0.50 1.000 -  
 USER-DEFINED - 0.59 0.50 1.000 -  
 USER-DEFINED - 3.04 0.50 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 18.12 SUBAREA RUNOFF (CFS) = 6.34  
 EFFECTIVE AREA (ACRES) = 1315.59 AREA-AVERAGED Fm (INCH/HR) = 0.45  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.90  
 TOTAL AREA (ACRES) = 3782.5 PEAK FLOW RATE (CFS) = 716.94  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 29.08  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.889  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.10	0.50	0.400	-
USER-DEFINED	-	1.30	0.50	0.850	-
USER-DEFINED	-	0.10	0.50	0.400	-
USER-DEFINED	-	1.70	0.50	0.850	-
USER-DEFINED	-	0.10	0.50	0.850	-
USER-DEFINED	-	2.90	0.50	0.850	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.835  
 SUBAREA AREA (ACRES) = 6.20 SUBAREA RUNOFF (CFS) = 2.63  
 EFFECTIVE AREA (ACRES) = 1321.79 AREA-AVERAGED Fm (INCH/HR) = 0.45  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.89  
 TOTAL AREA (ACRES) = 3788.7 PEAK FLOW RATE (CFS) = 716.94  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 29.08  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.889  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.10	0.50	0.500	-
USER-DEFINED	-	0.10	0.50	0.350	-
USER-DEFINED	-	6.90	0.50	0.850	-
USER-DEFINED	-	0.40	0.50	0.850	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.839  
 SUBAREA AREA (ACRES) = 7.50 SUBAREA RUNOFF (CFS) = 3.17  
 EFFECTIVE AREA (ACRES) = 1329.29 AREA-AVERAGED Fm (INCH/HR) = 0.45  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.89  
 TOTAL AREA (ACRES) = 3796.2 PEAK FLOW RATE (CFS) = 716.94  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13682.00 TO NODE 13683.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<

\*\*\*MEMORY BANK # 3 IS EMPTY - PROCESS IGNORED.\*\*\*

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 29.08  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.889  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	2.55	0.50	1.000	-
USER-DEFINED	-	0.01	0.50	1.000	-
USER-DEFINED	-	1.35	0.50	1.000	-
USER-DEFINED	-	0.44	0.50	1.000	-
USER-DEFINED	-	0.67	0.50	1.000	-
USER-DEFINED	-	1.06	0.50	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 6.08 SUBAREA RUNOFF (CFS) = 2.13  
 EFFECTIVE AREA (ACRES) = 1335.37 AREA-AVERAGED Fm (INCH/HR) = 0.45  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.90  
 TOTAL AREA (ACRES) = 3802.3 PEAK FLOW RATE (CFS) = 716.94  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 29.08  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.889  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	2.16	0.50	1.000	-
USER-DEFINED	-	2.45	0.50	1.000	-
USER-DEFINED	-	6.15	0.50	1.000	-
USER-DEFINED	-	1.34	0.50	1.000	-
USER-DEFINED	-	18.46	0.50	1.000	-
USER-DEFINED	-	4.13	0.50	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 34.69 SUBAREA RUNOFF (CFS) = 12.13  
 EFFECTIVE AREA (ACRES) = 1370.06 AREA-AVERAGED Fm (INCH/HR) = 0.45  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.90  
 TOTAL AREA (ACRES) = 3837.0 PEAK FLOW RATE (CFS) = 716.94  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

=====  
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<  
=====

MAINLINE Tc(MIN.) = 29.08  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.889  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 8.69 0.50 1.000 -  
USER-DEFINED - 0.73 0.50 1.000 -  
USER-DEFINED - 0.41 0.50 1.000 -  
USER-DEFINED - 1.37 0.50 1.000 -  
USER-DEFINED - 3.11 0.50 1.000 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA(ACRES) = 14.31 SUBAREA RUNOFF(CFS) = 5.01  
EFFECTIVE AREA(ACRES) = 1384.37 AREA-AVERAGED Fm(INCH/HR) = 0.45  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.90  
TOTAL AREA(ACRES) = 3851.3 PEAK FLOW RATE(CFS) = 716.94  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13683.00 TO NODE 13685.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<  
=====

ELEVATION DATA: UPSTREAM(FEET) = 208.53 DOWNSTREAM(FEET) = 194.24  
CHANNEL LENGTH THRU SUBAREA(FEET) = 289.01 CHANNEL SLOPE = 0.0494  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA(CFS) = 716.94  
FLOW VELOCITY(FEET/SEC.) = 13.20 FLOW DEPTH(FEET) = 4.25  
TRAVEL TIME(MIN.) = 0.36 Tc(MIN.) = 29.45  
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13685.00 = 39866.53 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13685.00 TO NODE 13410.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<  
=====

ELEVATION DATA: UPSTREAM(FEET) = 194.24 DOWNSTREAM(FEET) = 178.72  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1843.57 CHANNEL SLOPE = 0.0084  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.820  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 0.23 0.50 1.000 -  
USER-DEFINED - 1.52 0.50 1.000 -  
USER-DEFINED - 0.06 0.50 1.000 -  
USER-DEFINED - 0.13 0.50 1.000 -  
USER-DEFINED - 6.45 0.50 1.000 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 718.15

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.80  
AVERAGE FLOW DEPTH(FEET) = 5.93 TRAVEL TIME(MIN.) = 4.52  
Tc(MIN.) = 33.96  
SUBAREA AREA(ACRES) = 8.39 SUBAREA RUNOFF(CFS) = 2.42  
EFFECTIVE AREA(ACRES) = 1392.76 AREA-AVERAGED Fm(INCH/HR) = 0.45  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.90  
TOTAL AREA(ACRES) = 3859.7 PEAK FLOW RATE(CFS) = 716.94  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 5.93 FLOW VELOCITY(FEET/SEC.) = 6.79  
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13410.00 = 41710.10 FEET.  
=====

END OF STUDY SUMMARY:  
TOTAL AREA(ACRES) = 3859.7 TC(MIN.) = 33.96  
EFFECTIVE AREA(ACRES) = 1392.76 AREA-AVERAGED Fm(INCH/HR) = 0.45  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.899  
PEAK FLOW RATE(CFS) = 716.94

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	716.94	33.96	0.820	0.50( 0.45)	0.90	1392.8	110.00
2	712.41	36.72	0.785	0.50( 0.45)	0.90	1540.3	100.00
3	702.91	38.48	0.762	0.50( 0.45)	0.90	1624.0	100.00
4	658.46	42.79	0.720	0.50( 0.45)	0.91	1804.5	130.00
5	539.47	61.06	0.595	0.50( 0.46)	0.93	2545.6	20100.00
6	464.24	68.52	0.569	0.50( 0.46)	0.93	2700.4	13600.00
7	180.59	136.49	0.415	0.50( 0.47)	0.93	3777.9	13510.00
8	122.83	163.10	0.384	0.50( 0.47)	0.93	3859.7	13500.00

=====  
END OF RATIONAL METHOD ANALYSIS  
=====



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA 92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S37- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 5-YR RM EV APRIL 2019 ROKAMOTO \*  
\*\*\*\*\*

FILE NAME: RI05EV37.DAT  
TIME/DATE OF STUDY: 17:20 04/08/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 5.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 2.596
- 2) 10.00; 1.737
- 3) 15.00; 1.294
- 4) 20.00; 1.106
- 5) 25.00; 0.966
- 6) 30.00; 0.870
- 7) 40.00; 0.742
- 8) 50.00; 0.660
- 9) 60.00; 0.598
- 10) 90.00; 0.494
- 11) 120.00; 0.434
- 12) 180.00; 0.363
- 13) 360.00; 0.266
- 14) 1200.00; 0.116

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER WIDTH (FT)	GEOMETRIES: LIP (FT)	MANNING HIKE FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167 0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI05EV34.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14461.30	16.84	0.50 ( 0.41)	0.82	4436.3	400.00
2	14693.86	25.58	0.50 ( 0.41)	0.82	7327.2	50600.00
3	14312.86	41.49	0.50 ( 0.41)	0.83	13362.4	100.00
4	13848.23	49.76	0.50 ( 0.42)	0.85	16813.8	10100.00
5	13175.78	61.41	0.50 ( 0.43)	0.87	21327.4	20100.00
6	12353.83	75.88	0.50 ( 0.44)	0.89	26528.0	11801.00
7	11824.40	87.41	0.50 ( 0.45)	0.90	30505.1	11500.00
8	11211.37	99.63	0.50 ( 0.45)	0.91	35185.8	11000.00
9	10594.83	113.44	0.50 ( 0.46)	0.92	41583.3	13000.00
10	10184.92	122.65	0.50 ( 0.46)	0.93	45810.2	10900.00
11	9688.40	131.43	0.50 ( 0.47)	0.93	49271.6	11130.00
12	8930.84	143.32	0.50 ( 0.47)	0.93	53050.1	11620.00
13	7789.18	159.82	0.50 ( 0.47)	0.94	57626.5	12400.00
14	6897.34	171.61	0.50 ( 0.47)	0.94	59944.0	12201.00
15	6255.85	181.24	0.50 ( 0.47)	0.94	61234.6	12111.00
16	5294.96	197.50	0.50 ( 0.47)	0.94	63157.5	12261.00
17	4807.49	207.12	0.50 ( 0.47)	0.94	63968.6	10200.00
18	4211.62	222.96	0.50 ( 0.47)	0.94	65206.6	10300.00
19	3464.71	250.90	0.50 ( 0.47)	0.94	65887.1	12000.00
20	2387.75	320.55	0.50 ( 0.47)	0.95	66557.9	10100.00
TOTAL AREA(ACRES) =						66557.9

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 3 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14461.30	16.84	0.50 ( 0.41)	0.82	4436.3	400.00
2	14693.86	25.58	0.50 ( 0.41)	0.82	7327.2	50600.00
3	14312.86	41.49	0.50 ( 0.41)	0.83	13362.4	100.00
4	13848.23	49.76	0.50 ( 0.42)	0.85	16813.8	10100.00
5	13175.78	61.41	0.50 ( 0.43)	0.87	21327.4	20100.00
6	12353.83	75.88	0.50 ( 0.44)	0.89	26528.0	11801.00
7	11824.40	87.41	0.50 ( 0.45)	0.90	30505.1	11500.00
8	11211.37	99.63	0.50 ( 0.45)	0.91	35185.8	11000.00
9	10594.83	113.44	0.50 ( 0.46)	0.92	41583.3	13000.00
10	10184.92	122.65	0.50 ( 0.46)	0.93	45810.2	10900.00
11	9688.40	131.43	0.50 ( 0.47)	0.93	49271.6	11130.00
12	8930.84	143.32	0.50 ( 0.47)	0.93	53050.1	11620.00
13	7789.18	159.82	0.50 ( 0.47)	0.94	57626.5	12400.00

14	6897.34	171.61	0.50	( 0.47)	0.94	59944.0	12201.00
15	6255.85	181.24	0.50	( 0.47)	0.94	61234.6	12111.00
16	5294.96	197.50	0.50	( 0.47)	0.94	63157.5	12261.00
17	4807.49	207.12	0.50	( 0.47)	0.94	63968.6	10200.00
18	4211.62	222.96	0.50	( 0.47)	0.94	65206.6	10300.00
19	3464.71	250.90	0.50	( 0.47)	0.94	65887.1	12000.00
20	2387.75	320.55	0.50	( 0.47)	0.95	66557.9	10100.00

TOTAL AREA (ACRES) = 66557.9

\*\*\*\*\*

FLOW PROCESS FROM NODE 13700.00 TO NODE 13720.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 170.00 DOWNSTREAM (FEET) = 165.51  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1891.83 CHANNEL SLOPE = 0.0024  
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00

==>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL  
 CAPACITY (NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM  
 ALLOWABLE DEPTH).  
 AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM  
 ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

CHANNEL FLOW THRU SUBAREA (CFS) = 14693.86  
 FLOW VELOCITY (FEET/SEC.) = 12.24 FLOW DEPTH (FEET) = 20.00  
 TRAVEL TIME (MIN.) = 2.57 Tc (MIN.) = 28.16  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126443.54 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13700.00 TO NODE 13720.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 13720.00 TO NODE 13720.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506102F.DNA  
 MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	108.74	17.82	0.50 ( 0.48)	0.96	196.1	10230.00
2	89.60	26.01	0.50 ( 0.48)	0.95	235.1	10250.00
3	84.70	27.80	0.50 ( 0.48)	0.95	241.6	10200.00
4	70.42	32.34	0.50 ( 0.48)	0.95	246.3	10220.00

TOTAL AREA (ACRES) = 246.3

\*\*\*\*\*

FLOW PROCESS FROM NODE 13720.00 TO NODE 13720.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\*\*\*\*

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14461.30	19.46	1.126	0.50 ( 0.41)	0.82	4436.3	400.00
2	14693.86	28.16	0.905	0.50 ( 0.41)	0.82	7327.2	50600.00
3	14312.86	44.13	0.708	0.50 ( 0.41)	0.83	13362.4	100.00
4	13848.23	52.49	0.645	0.50 ( 0.42)	0.85	16813.8	10100.00
5	13175.78	64.28	0.583	0.50 ( 0.43)	0.87	21327.4	20100.00
6	12353.83	78.83	0.533	0.50 ( 0.44)	0.89	26528.0	11801.00
7	11824.40	90.39	0.493	0.50 ( 0.45)	0.90	30505.1	11500.00
8	11211.37	102.66	0.469	0.50 ( 0.45)	0.91	35185.8	11000.00
9	10594.83	116.51	0.441	0.50 ( 0.46)	0.92	41583.3	13000.00
10	10184.92	125.75	0.427	0.50 ( 0.46)	0.93	45810.2	10900.00
11	9688.40	134.57	0.417	0.50 ( 0.47)	0.93	49271.6	11130.00
12	8930.84	146.52	0.403	0.50 ( 0.47)	0.93	53050.1	11620.00
13	7789.18	163.13	0.383	0.50 ( 0.47)	0.94	57626.5	12400.00
14	6897.34	175.02	0.369	0.50 ( 0.47)	0.94	59944.0	12201.00
15	6255.85	184.73	0.360	0.50 ( 0.47)	0.94	61234.6	12111.00
16	5294.96	201.14	0.352	0.50 ( 0.47)	0.94	63157.5	12261.00
17	4807.49	210.85	0.346	0.50 ( 0.47)	0.94	63968.6	10200.00
18	4211.62	226.82	0.338	0.50 ( 0.47)	0.94	65206.6	10300.00
19	3464.71	254.96	0.323	0.50 ( 0.47)	0.94	65887.1	12000.00
20	2387.75	325.00	0.285	0.50 ( 0.47)	0.95	66557.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126443.54 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	108.74	17.82	1.188	0.50 ( 0.48)	0.96	196.1	10230.00
2	89.60	26.01	0.947	0.50 ( 0.48)	0.95	235.1	10250.00
3	84.70	27.80	0.912	0.50 ( 0.48)	0.95	241.6	10200.00
4	70.42	32.34	0.840	0.50 ( 0.48)	0.95	246.3	10220.00

LONGEST FLOWPATH FROM NODE 10200.00 TO NODE 13720.00 = 9099.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14490.86	17.82	1.188	0.50 ( 0.41)	0.83	4259.9	10230.00
2	14566.23	19.46	1.126	0.50 ( 0.41)	0.83	4640.1	400.00
3	14726.22	26.01	0.947	0.50 ( 0.41)	0.82	6850.8	10250.00
4	14769.10	27.80	0.912	0.50 ( 0.41)	0.82	7451.1	10200.00
5	14777.45	28.16	0.905	0.50 ( 0.41)	0.82	7569.1	50600.00
6	14664.40	32.34	0.840	0.50 ( 0.41)	0.82	9155.6	10220.00
7	14357.69	44.13	0.708	0.50 ( 0.42)	0.83	13608.6	100.00
8	13880.73	52.49	0.645	0.50 ( 0.42)	0.85	17060.1	10100.00
9	13196.36	64.28	0.583	0.50 ( 0.43)	0.87	21573.6	20100.00
10	12364.62	78.83	0.533	0.50 ( 0.44)	0.89	26774.3	11801.00
11	11828.83	90.39	0.493	0.50 ( 0.45)	0.90	30751.4	11500.00
12	11215.57	102.66	0.469	0.50 ( 0.45)	0.91	35432.0	11000.00
13	10598.79	116.51	0.441	0.50 ( 0.46)	0.92	41829.6	13000.00
14	10188.75	125.75	0.427	0.50 ( 0.46)	0.93	46056.5	10900.00
15	9692.13	134.57	0.417	0.50 ( 0.47)	0.93	49517.8	11130.00
16	8934.46	146.52	0.403	0.50 ( 0.47)	0.93	53296.3	11620.00
17	7792.61	163.13	0.383	0.50 ( 0.47)	0.94	57872.8	12400.00
18	6900.65	175.02	0.369	0.50 ( 0.47)	0.94	60190.2	12201.00
19	6259.08	184.73	0.360	0.50 ( 0.47)	0.94	61480.9	12111.00
20	5298.11	201.14	0.352	0.50 ( 0.47)	0.94	63403.8	12261.00
21	4810.59	210.85	0.346	0.50 ( 0.47)	0.94	64214.9	10200.00

22 4214.65 226.82 0.338 0.50( 0.47) 0.94 65452.8 10300.00  
 23 3467.61 254.96 0.323 0.50( 0.47) 0.94 66133.4 12000.00  
 24 2390.30 325.00 0.285 0.50( 0.47) 0.95 66804.2 10100.00  
 TOTAL AREA(ACRES) = 66804.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 14777.45 Tc(MIN.) = 28.156  
 EFFECTIVE AREA(ACRES) = 7569.13 AREA-AVERAGED Fm(INCH/HR) = 0.41  
 AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA(ACRES) = 66804.2  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126443.54 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13720.00 TO NODE 13740.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 165.51 DOWNSTREAM(FEET) = 161.03  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2067.54 CHANNEL SLOPE = 0.0022  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00

==>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL  
 CAPACITY( NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM  
 ALLOWABLE DEPTH).  
 AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM  
 ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

CHANNEL FLOW THRU SUBAREA(CFS) = 14777.45  
 FLOW VELOCITY(FEET/SEC.) = 12.31 FLOW DEPTH(FEET) = 20.00  
 TRAVEL TIME(MIN.) = 2.80 Tc(MIN.) = 30.95  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128511.08 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13720.00 TO NODE 13740.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 3 <<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13740.00 TO NODE 13740.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 3 <<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 0506103F.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	252.52	21.48	0.50( 0.38)	0.76	404.4	10300.00
2	251.96	21.77	0.50( 0.38)	0.76	408.5	10380.00
3	235.57	25.33	0.50( 0.38)	0.76	442.2	10320.00
4	219.91	27.75	0.50( 0.38)	0.76	453.9	10360.00
5	202.40	30.24	0.50( 0.38)	0.76	460.8	10340.00
TOTAL AREA(ACRES) =						460.8

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13740.00 TO NODE 13740.00 IS CODE = 11

-----  
 >>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<  
 =====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14490.86	20.68	1.087	0.50( 0.41)	0.83	4259.9	10230.00
2	14566.23	22.29	1.042	0.50( 0.41)	0.83	4640.1	400.00
3	14726.22	28.82	0.893	0.50( 0.41)	0.82	6850.8	10250.00
4	14769.10	30.60	0.862	0.50( 0.41)	0.82	7451.1	10200.00
5	14777.45	30.95	0.858	0.50( 0.41)	0.82	7569.1	50600.00
6	14664.40	35.16	0.804	0.50( 0.41)	0.82	9155.6	10220.00
7	14357.69	47.01	0.685	0.50( 0.42)	0.83	13608.6	100.00
8	13880.73	55.47	0.626	0.50( 0.42)	0.85	17060.1	10100.00
9	13196.36	67.41	0.572	0.50( 0.43)	0.87	21573.6	20100.00
10	12364.62	82.17	0.521	0.50( 0.44)	0.89	26774.3	11801.00
11	11828.83	93.77	0.486	0.50( 0.45)	0.90	30751.4	11500.00
12	11215.57	106.08	0.462	0.50( 0.45)	0.91	35432.0	11000.00
13	10598.79	119.98	0.434	0.50( 0.46)	0.92	41829.6	13000.00
14	10188.75	129.25	0.423	0.50( 0.46)	0.93	46056.5	10900.00
15	9692.13	138.12	0.413	0.50( 0.47)	0.93	49517.8	11130.00
16	8934.46	150.14	0.398	0.50( 0.47)	0.93	53296.3	11620.00
17	7792.61	166.88	0.379	0.50( 0.47)	0.94	57872.8	12400.00
18	6900.65	178.88	0.364	0.50( 0.47)	0.94	60190.2	12201.00
19	6259.08	188.69	0.358	0.50( 0.47)	0.94	61480.9	12111.00
20	5298.11	205.27	0.349	0.50( 0.47)	0.94	63403.8	12261.00
21	4810.59	215.08	0.344	0.50( 0.47)	0.94	64214.9	10200.00
22	4214.65	231.18	0.335	0.50( 0.47)	0.94	65452.8	10300.00
23	3467.61	259.54	0.320	0.50( 0.47)	0.94	66133.4	12000.00
24	2390.30	330.03	0.282	0.50( 0.47)	0.95	66804.2	10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 =							128511.08 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	252.52	21.48	1.065	0.50( 0.38)	0.76	404.4	10300.00
2	251.96	21.77	1.057	0.50( 0.38)	0.76	408.5	10380.00
3	235.57	25.33	0.960	0.50( 0.38)	0.76	442.2	10320.00
4	219.91	27.75	0.913	0.50( 0.38)	0.76	453.9	10360.00
5	202.40	30.24	0.867	0.50( 0.38)	0.76	460.8	10340.00
LONGEST FLOWPATH FROM NODE 10320.00 TO NODE 13740.00 =							8457.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14741.90	20.68	1.087	0.50( 0.41)	0.82	4649.1	10230.00
2	14780.76	21.48	1.065	0.50( 0.41)	0.82	4852.8	10300.00
3	14793.53	21.77	1.057	0.50( 0.41)	0.82	4924.2	10380.00
4	14815.76	22.29	1.042	0.50( 0.41)	0.82	5053.6	400.00
5	14876.28	25.33	0.960	0.50( 0.41)	0.82	6111.3	10320.00
6	14919.85	27.75	0.913	0.50( 0.41)	0.82	6941.5	10360.00
7	14938.58	28.82	0.893	0.50( 0.41)	0.82	7307.6	10250.00
8	14962.72	30.24	0.867	0.50( 0.41)	0.82	7789.1	10340.00
9	14969.55	30.60	0.862	0.50( 0.41)	0.82	7911.9	10200.00
10	14976.01	30.95	0.858	0.50( 0.41)	0.82	8029.9	50600.00
11	14840.48	35.16	0.804	0.50( 0.41)	0.82	9616.4	10220.00
12	14483.95	47.01	0.685	0.50( 0.41)	0.83	14069.4	100.00

13	13982.60	55.47	0.626	0.50	(0.42)	0.85	17520.9	10100.00
14	13275.79	67.41	0.572	0.50	(0.43)	0.87	22034.4	20100.00
15	12422.71	82.17	0.521	0.50	(0.44)	0.89	27235.1	11801.00
16	11876.81	93.77	0.486	0.50	(0.45)	0.90	31212.2	11500.00
17	11261.12	106.08	0.462	0.50	(0.45)	0.91	35892.8	11000.00
18	10641.60	119.98	0.434	0.50	(0.46)	0.92	42290.4	13000.00
19	10230.48	129.25	0.423	0.50	(0.46)	0.92	46517.3	10900.00
20	9732.83	138.12	0.413	0.50	(0.46)	0.93	49978.6	11130.00
21	8973.74	150.14	0.398	0.50	(0.47)	0.93	53757.1	11620.00
22	7829.95	166.88	0.379	0.50	(0.47)	0.94	58333.6	12400.00
23	6936.58	178.88	0.364	0.50	(0.47)	0.94	60651.0	12201.00
24	6294.43	188.69	0.358	0.50	(0.47)	0.94	61941.7	12111.00
25	5332.57	205.27	0.349	0.50	(0.47)	0.94	63864.6	12261.00
26	4844.53	215.08	0.344	0.50	(0.47)	0.94	64675.7	10200.00
27	4247.73	231.18	0.335	0.50	(0.47)	0.94	65913.6	10300.00
28	3499.18	259.54	0.320	0.50	(0.47)	0.94	66594.2	12000.00
29	2418.13	330.03	0.282	0.50	(0.47)	0.94	67265.0	10100.00

TOTAL AREA (ACRES) = 67265.0

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 14976.01 Tc (MIN.) = 30.954  
EFFECTIVE AREA (ACRES) = 8029.93 AREA-AVERAGED Fm (INCH/HR) = 0.41  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.82  
TOTAL AREA (ACRES) = 67265.0  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128511.08 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13740.00 TO NODE 13741.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<  
=====

ELEVATION DATA: UPSTREAM (FEET) = 161.03 DOWNSTREAM (FEET) = 141.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 364.08 CHANNEL SLOPE = 0.0550  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA (CFS) = 14976.01  
FLOW VELOCITY (FEET/SEC.) = 36.43 FLOW DEPTH (FEET) = 11.71  
TRAVEL TIME (MIN.) = 0.17 Tc (MIN.) = 31.12  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128875.16 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13740.00 TO NODE 13741.00 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 3 <<<<<  
=====

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13741.00 TO NODE 13741.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 3 <<<<<  
=====

PEAK FLOWRATE TABLE FILE NAME: 0506104F.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22.86	23.27	0.50 (0.40)	0.80	44.3	10400.00

TOTAL AREA (ACRES) = 44.3

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13741.00 TO NODE 13741.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<  
=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14741.90	20.84	1.082	0.50 (0.41)	0.82	4649.1	10230.00
2	14780.76	21.65	1.060	0.50 (0.41)	0.82	4852.8	10300.00
3	14793.53	21.93	1.052	0.50 (0.41)	0.82	4924.2	10380.00
4	14815.76	22.46	1.037	0.50 (0.41)	0.82	5053.6	400.00
5	14876.28	25.50	0.956	0.50 (0.41)	0.82	6111.3	10320.00
6	14919.85	27.92	0.910	0.50 (0.41)	0.82	6941.5	10360.00
7	14938.58	28.99	0.889	0.50 (0.41)	0.82	7307.6	10250.00
8	14962.72	30.40	0.865	0.50 (0.41)	0.82	7789.1	10340.00
9	14969.55	30.77	0.860	0.50 (0.41)	0.82	7911.9	10200.00
10	14976.01	31.12	0.856	0.50 (0.41)	0.82	8029.9	50600.00
11	14840.48	35.33	0.802	0.50 (0.41)	0.82	9616.4	10220.00
12	14483.95	47.18	0.683	0.50 (0.41)	0.83	14069.4	100.00
13	13982.60	55.64	0.625	0.50 (0.42)	0.85	17520.9	10100.00
14	13275.79	67.58	0.572	0.50 (0.43)	0.87	22034.4	20100.00
15	12422.71	82.34	0.521	0.50 (0.44)	0.89	27235.1	11801.00
16	11876.81	93.95	0.486	0.50 (0.45)	0.90	31212.2	11500.00
17	11261.12	106.26	0.461	0.50 (0.45)	0.91	35892.8	11000.00
18	10641.60	120.16	0.434	0.50 (0.46)	0.92	42290.4	13000.00
19	10230.48	129.44	0.423	0.50 (0.46)	0.92	46517.3	10900.00
20	9732.83	138.30	0.412	0.50 (0.46)	0.93	49978.6	11130.00
21	8973.74	150.33	0.398	0.50 (0.47)	0.93	53757.1	11620.00
22	7829.95	167.08	0.378	0.50 (0.47)	0.94	58333.6	12400.00
23	6936.58	179.09	0.364	0.50 (0.47)	0.94	60651.0	12201.00
24	6294.43	188.90	0.358	0.50 (0.47)	0.94	61941.7	12111.00
25	5332.57	205.48	0.349	0.50 (0.47)	0.94	63864.6	12261.00
26	4844.53	215.30	0.344	0.50 (0.47)	0.94	64675.7	10200.00
27	4247.73	231.41	0.335	0.50 (0.47)	0.94	65913.6	10300.00
28	3499.18	259.78	0.320	0.50 (0.47)	0.94	66594.2	12000.00
29	2418.13	330.29	0.282	0.50 (0.47)	0.94	67265.0	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128875.16 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22.86	23.27	1.014	0.50 (0.40)	0.80	44.3	10400.00

LONGEST FLOWPATH FROM NODE 10400.00 TO NODE 13741.00 = 6237.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14764.64	20.84	1.082	0.50 (0.41)	0.82	4688.8	10230.00
2	14803.60	21.65	1.060	0.50 (0.41)	0.82	4894.0	10300.00
3	14816.39	21.93	1.052	0.50 (0.41)	0.82	4965.9	10380.00
4	14838.62	22.46	1.037	0.50 (0.41)	0.82	5096.3	400.00
5	14854.80	23.27	1.014	0.50 (0.41)	0.82	5380.7	10400.00
6	14896.99	25.50	0.956	0.50 (0.41)	0.82	6155.6	10320.00
7	14938.83	27.92	0.910	0.50 (0.41)	0.82	6985.8	10360.00
8	14956.80	28.99	0.889	0.50 (0.41)	0.82	7351.9	10250.00



Stream Number	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
9	14980.03	30.40	0.865	0.50 ( 0.41)	0.82	7833.4	10340.00
10	14986.68	30.77	0.860	0.50 ( 0.41)	0.82	7956.2	10200.00
11	14992.98	31.12	0.856	0.50 ( 0.41)	0.82	8074.2	50600.00
12	14855.44	35.33	0.802	0.50 ( 0.41)	0.82	9660.7	10220.00
13	14494.50	47.18	0.683	0.50 ( 0.41)	0.83	14113.7	100.00
14	13990.99	55.64	0.625	0.50 ( 0.42)	0.85	17565.2	10100.00
15	13282.20	67.58	0.572	0.50 ( 0.43)	0.87	22078.7	20100.00
16	12427.21	82.34	0.521	0.50 ( 0.44)	0.89	27279.4	11801.00
17	11880.45	93.95	0.486	0.50 ( 0.45)	0.90	31256.5	11500.00
18	11264.58	106.26	0.461	0.50 ( 0.45)	0.91	35937.1	11000.00
19	10644.85	120.16	0.434	0.50 ( 0.46)	0.92	42334.7	13000.00
20	10233.65	129.44	0.423	0.50 ( 0.46)	0.92	46561.6	10900.00
21	9735.92	138.30	0.412	0.50 ( 0.46)	0.93	50022.9	11130.00
22	8976.73	150.33	0.398	0.50 ( 0.47)	0.93	53801.4	11620.00
23	7832.78	167.08	0.378	0.50 ( 0.47)	0.94	58377.9	12400.00
24	6939.31	179.09	0.364	0.50 ( 0.47)	0.94	60695.3	12201.00
25	6297.11	188.90	0.358	0.50 ( 0.47)	0.94	61986.0	12111.00
26	5335.19	205.48	0.349	0.50 ( 0.47)	0.94	63908.9	12261.00
27	4847.11	215.30	0.344	0.50 ( 0.47)	0.94	64720.0	10200.00
28	4250.24	231.41	0.335	0.50 ( 0.47)	0.94	65957.9	10300.00
29	3501.58	259.78	0.320	0.50 ( 0.47)	0.94	66638.5	12000.00
30	2420.25	330.29	0.282	0.50 ( 0.47)	0.94	67309.3	10100.00

TOTAL AREA (ACRES) = 67309.3

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 14992.98 Tc (MIN.) = 31.121  
EFFECTIVE AREA (ACRES) = 8074.23 AREA-AVERAGED Fm (INCH/HR) = 0.41  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.82  
TOTAL AREA (ACRES) = 67309.3  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128875.16 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13741.00 TO NODE 13802.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

-----  
ELEVATION DATA: UPSTREAM (FEET) = 141.00 DOWNSTREAM (FEET) = 135.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1533.41 CHANNEL SLOPE = 0.0039  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA (CFS) = 14992.98  
FLOW VELOCITY (FEET/SEC.) = 13.52 FLOW DEPTH (FEET) = 19.22  
TRAVEL TIME (MIN.) = 1.89 Tc (MIN.) = 33.01  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130408.56 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 3 <<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 3 <<<<

-----  
PEAK FLOWRATE TABLE FILE NAME: 0506105M.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

Stream Number	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	119.37	16.20	0.50 ( 0.45)	0.90	187.4	10520.00	
2	91.55	39.09	0.50 ( 0.46)	0.93	403.6	10500.00	

TOTAL AREA (ACRES) = 403.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

Stream Number	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14764.64	22.74	1.029	0.50 ( 0.41)	0.82	4688.8	10230.00
2	14803.60	23.54	1.007	0.50 ( 0.41)	0.82	4894.0	10300.00
3	14816.39	23.83	0.999	0.50 ( 0.41)	0.82	4965.9	10380.00
4	14838.62	24.36	0.984	0.50 ( 0.41)	0.82	5096.3	400.00
5	14854.80	25.17	0.963	0.50 ( 0.41)	0.82	5380.7	10400.00
6	14896.99	27.39	0.920	0.50 ( 0.41)	0.82	6155.6	10320.00
7	14938.83	29.81	0.874	0.50 ( 0.41)	0.82	6985.8	10360.00
8	14956.80	30.88	0.859	0.50 ( 0.41)	0.82	7351.9	10250.00
9	14980.03	32.29	0.841	0.50 ( 0.41)	0.82	7833.4	10340.00
10	14986.68	32.66	0.836	0.50 ( 0.41)	0.82	7956.2	10200.00
11	14992.98	33.01	0.831	0.50 ( 0.41)	0.82	8074.2	50600.00
12	14855.44	37.22	0.778	0.50 ( 0.41)	0.82	9660.7	10220.00
13	14494.50	49.08	0.668	0.50 ( 0.41)	0.83	14113.7	100.00
14	13990.99	57.56	0.613	0.50 ( 0.42)	0.85	17565.2	10100.00
15	13282.20	69.53	0.565	0.50 ( 0.43)	0.87	22078.7	20100.00
16	12427.21	84.32	0.514	0.50 ( 0.44)	0.89	27279.4	11801.00
17	11880.45	95.95	0.482	0.50 ( 0.45)	0.90	31256.5	11500.00
18	11264.58	108.29	0.457	0.50 ( 0.45)	0.91	35937.1	11000.00
19	10644.85	122.22	0.431	0.50 ( 0.46)	0.92	42334.7	13000.00
20	10233.65	131.51	0.420	0.50 ( 0.46)	0.92	46561.6	10900.00
21	9735.92	140.41	0.410	0.50 ( 0.46)	0.93	50022.9	11130.00
22	8976.73	152.48	0.396	0.50 ( 0.47)	0.93	53801.4	11620.00
23	7832.78	169.30	0.376	0.50 ( 0.47)	0.94	58377.9	12400.00
24	6939.31	181.38	0.362	0.50 ( 0.47)	0.94	60695.3	12201.00
25	6297.11	191.24	0.357	0.50 ( 0.47)	0.94	61986.0	12111.00
26	5335.19	207.93	0.348	0.50 ( 0.47)	0.94	63908.9	12261.00
27	4847.11	217.80	0.343	0.50 ( 0.47)	0.94	64720.0	10200.00
28	4250.24	234.00	0.334	0.50 ( 0.47)	0.94	65957.9	10300.00
29	3501.58	262.50	0.319	0.50 ( 0.47)	0.94	66638.5	12000.00
30	2420.25	332.28	0.280	0.50 ( 0.47)	0.94	67309.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130408.56 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

Stream Number	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	119.37	16.20	1.249	0.50 ( 0.45)	0.90	187.4	10520.00
2	91.55	39.09	0.754	0.50 ( 0.46)	0.93	403.6	10500.00

LONGEST FLOWPATH FROM NODE 10500.00 TO NODE 13802.00 = 12187.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

Stream Number	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
---------------	---------	-----------	---------------------	-------------------	----	------------	----------------

1	14366.11	16.20	1.249	0.50	(0.41)	0.82	3526.8	10520.00
2	14876.06	22.74	1.029	0.50	(0.41)	0.82	4938.1	10230.00
3	14914.04	23.54	1.007	0.50	(0.41)	0.82	5150.9	10300.00
4	14926.48	23.83	0.999	0.50	(0.41)	0.82	5225.4	10380.00
5	14948.08	24.36	0.984	0.50	(0.41)	0.82	5360.8	400.00
6	14963.27	25.17	0.963	0.50	(0.41)	0.82	5652.9	10400.00
7	15002.75	27.39	0.920	0.50	(0.41)	0.82	6448.8	10320.00
8	15041.66	29.81	0.874	0.50	(0.41)	0.82	7301.8	10360.00
9	15058.32	30.88	0.859	0.50	(0.41)	0.82	7678.0	10250.00
10	15079.83	32.29	0.841	0.50	(0.41)	0.82	8172.9	10340.00
11	15086.04	32.66	0.836	0.50	(0.41)	0.82	8299.2	10200.00
12	15091.91	33.01	0.831	0.50	(0.41)	0.82	8420.5	50600.00
13	14949.26	37.22	0.778	0.50	(0.41)	0.82	10046.7	10220.00
14	14890.36	39.09	0.754	0.50	(0.41)	0.83	10763.0	10500.00
15	14558.84	49.08	0.668	0.50	(0.42)	0.83	14517.3	100.00
16	14038.17	57.56	0.613	0.50	(0.42)	0.85	17968.8	10100.00
17	13314.18	69.53	0.565	0.50	(0.43)	0.87	22482.3	20100.00
18	12443.01	84.32	0.514	0.50	(0.44)	0.89	27683.0	11801.00
19	11891.58	95.95	0.482	0.50	(0.45)	0.90	31660.1	11500.00
20	11275.14	108.29	0.457	0.50	(0.45)	0.91	36340.7	11000.00
21	10654.81	122.22	0.431	0.50	(0.46)	0.92	42738.3	13000.00
22	10243.35	131.51	0.420	0.50	(0.46)	0.92	46965.2	10900.00
23	9745.38	140.41	0.410	0.50	(0.46)	0.93	50426.5	11130.00
24	8985.86	152.48	0.396	0.50	(0.47)	0.93	54205.0	11620.00
25	7841.45	169.30	0.376	0.50	(0.47)	0.94	58781.5	12400.00
26	6947.67	181.38	0.362	0.50	(0.47)	0.94	61098.9	12201.00
27	6305.35	191.24	0.357	0.50	(0.47)	0.94	62389.6	12111.00
28	5343.22	207.93	0.348	0.50	(0.47)	0.94	64312.5	12261.00
29	4855.02	217.80	0.343	0.50	(0.47)	0.94	65123.6	10200.00
30	4257.95	234.00	0.334	0.50	(0.47)	0.94	66361.5	10300.00
31	3508.93	262.50	0.319	0.50	(0.47)	0.94	67042.1	12000.00
32	2426.72	333.28	0.280	0.50	(0.47)	0.94	67712.9	10100.00

TOTAL AREA (ACRES) = 67712.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 15091.91 Tc(MIN.) = 33.010  
EFFECTIVE AREA(ACRES) = 8420.47 AREA-AVERAGED Fm(INCH/HR) = 0.41  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.82  
TOTAL AREA(ACRES) = 67712.9  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130408.56 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13802.00 TO NODE 13803.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 135.00 DOWNSTREAM(FEET) = 133.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 207.23 CHANNEL SLOPE = 0.0097  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
CHANNEL FLOW THRU SUBAREA(CFS) = 15091.91  
FLOW VELOCITY(FEET/SEC.) = 19.00 FLOW DEPTH(FEET) = 16.27  
TRAVEL TIME(MIN.) = 0.18 Tc(MIN.) = 33.19  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130615.79 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 81

-----  
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<  
=====

MAINLINE Tc(MIN.) = 33.19  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.829  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SC5 SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 48.80 0.50 0.800 -  
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.800  
SUBAREA AREA(ACRES) = 48.80 SUBAREA RUNOFF(CFS) = 18.84  
EFFECTIVE AREA(ACRES) = 8469.27 AREA-AVERAGED Fm(INCH/HR) = 0.41  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.82  
TOTAL AREA(ACRES) = 67761.7 PEAK FLOW RATE(CFS) = 15091.91  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13802.00 TO NODE 13803.00 IS CODE = 12

-----  
>>>>CLEAR MEMORY BANK # 3 <<<<  
=====

\*\*\*\*\*

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 15.1

-----  
>>>>DEFINE MEMORY BANK # 3 <<<<  
=====

PEAK FLOWRATE TABLE FILE NAME: 0506106f.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23.96	18.98	0.50(0.34)	0.67	36.9	10600.00
TOTAL AREA(ACRES) =			36.9			

\*\*\*\*\*

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 11

-----  
>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<  
=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14366.11	16.38	1.242	0.50(0.41)	0.82	3575.6	10520.00
2	14876.06	22.92	1.024	0.50(0.41)	0.82	4986.9	10230.00
3	14914.04	23.72	1.002	0.50(0.41)	0.82	5199.7	10300.00
4	14926.48	24.01	0.994	0.50(0.41)	0.82	5274.2	10380.00
5	14948.08	24.54	0.979	0.50(0.41)	0.82	5409.6	400.00
6	14963.27	25.35	0.959	0.50(0.41)	0.82	5701.7	10400.00
7	15002.75	27.58	0.917	0.50(0.41)	0.82	6497.6	10320.00
8	15041.66	29.99	0.870	0.50(0.41)	0.82	7350.6	10360.00
9	15058.32	31.06	0.856	0.50(0.41)	0.82	7726.8	10250.00
10	15079.83	32.48	0.838	0.50(0.41)	0.82	8221.7	10340.00
11	15086.04	32.84	0.834	0.50(0.41)	0.82	8348.0	10200.00
12	15091.91	33.19	0.829	0.50(0.41)	0.82	8469.3	50600.00
13	14949.26	37.41	0.775	0.50(0.41)	0.82	10095.5	10220.00
14	14890.36	39.27	0.751	0.50(0.41)	0.83	10811.8	10500.00

15	14558.84	49.27	0.666	0.50 ( 0.42)	0.83	14566.1	100.00
16	14038.17	57.75	0.612	0.50 ( 0.42)	0.85	18017.6	10100.00
17	13314.18	69.72	0.564	0.50 ( 0.43)	0.87	22531.1	20100.00
18	12443.01	84.51	0.513	0.50 ( 0.44)	0.89	27731.8	11801.00
19	11891.58	96.14	0.482	0.50 ( 0.45)	0.90	31708.9	11500.00
20	11275.14	108.48	0.457	0.50 ( 0.45)	0.91	36389.5	11000.00
21	10654.81	122.42	0.431	0.50 ( 0.46)	0.92	42787.1	13000.00
22	10243.35	131.71	0.420	0.50 ( 0.46)	0.92	47014.0	10900.00
23	9745.38	140.61	0.410	0.50 ( 0.46)	0.93	50475.3	11130.00
24	8985.86	152.69	0.395	0.50 ( 0.47)	0.93	54253.8	11620.00
25	7841.45	169.51	0.375	0.50 ( 0.47)	0.94	58830.3	12400.00
26	6947.67	181.60	0.362	0.50 ( 0.47)	0.94	61147.7	12201.00
27	6305.35	191.47	0.357	0.50 ( 0.47)	0.94	62438.4	12111.00
28	5343.22	208.17	0.348	0.50 ( 0.47)	0.94	64361.3	12261.00
29	4855.02	218.05	0.342	0.50 ( 0.47)	0.94	65172.4	10200.00
30	4257.95	234.25	0.334	0.50 ( 0.47)	0.94	66410.3	10300.00
31	3508.93	262.76	0.318	0.50 ( 0.47)	0.94	67090.9	12000.00
32	2426.72	333.56	0.280	0.50 ( 0.47)	0.94	67761.7	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130615.79 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23.96	18.98	1.144	0.50 ( 0.34)	0.67	36.9	10600.00

LONGEST FLOWPATH FROM NODE 10600.00 TO NODE 13803.00 = 1713.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14389.29	16.38	1.242	0.50 ( 0.41)	0.82	3607.4	10520.00
2	14593.00	18.98	1.144	0.50 ( 0.41)	0.82	4174.1	10600.00
3	14896.46	22.92	1.024	0.50 ( 0.41)	0.82	5023.8	10230.00
4	14933.78	23.72	1.002	0.50 ( 0.41)	0.82	5236.6	10300.00
5	14945.99	24.01	0.994	0.50 ( 0.41)	0.82	5311.1	10380.00
6	14967.14	24.54	0.979	0.50 ( 0.41)	0.82	5446.5	400.00
7	14981.75	25.35	0.959	0.50 ( 0.41)	0.82	5738.6	10400.00
8	15019.96	27.58	0.917	0.50 ( 0.41)	0.82	6534.5	10320.00
9	15057.50	29.99	0.870	0.50 ( 0.41)	0.82	7387.5	10360.00
10	15073.76	31.06	0.856	0.50 ( 0.41)	0.82	7763.7	10250.00
11	15094.73	32.48	0.838	0.50 ( 0.41)	0.82	8258.6	10340.00
12	15100.80	32.84	0.834	0.50 ( 0.41)	0.82	8384.9	10200.00
13	15106.54	33.19	0.829	0.50 ( 0.41)	0.82	8506.2	50600.00
14	14962.29	37.41	0.775	0.50 ( 0.41)	0.82	10132.4	10220.00
15	14902.69	39.27	0.751	0.50 ( 0.41)	0.83	10848.7	10500.00
16	14568.64	49.27	0.666	0.50 ( 0.42)	0.83	14603.0	100.00
17	14046.37	57.75	0.612	0.50 ( 0.42)	0.85	18054.5	10100.00
18	13320.97	69.72	0.564	0.50 ( 0.43)	0.87	22568.0	20100.00
19	12448.28	84.51	0.513	0.50 ( 0.44)	0.89	27768.7	11801.00
20	11896.29	96.14	0.482	0.50 ( 0.45)	0.90	31745.8	11500.00
21	11279.61	108.48	0.457	0.50 ( 0.45)	0.91	36426.4	11000.00
22	10659.02	122.42	0.431	0.50 ( 0.46)	0.92	42824.0	13000.00
23	10247.46	131.71	0.420	0.50 ( 0.46)	0.92	47050.9	10900.00
24	9749.38	140.61	0.410	0.50 ( 0.46)	0.93	50512.2	11130.00
25	8989.72	152.69	0.395	0.50 ( 0.47)	0.93	54290.7	11620.00
26	7845.12	169.51	0.375	0.50 ( 0.47)	0.94	58867.2	12400.00
27	6951.21	181.60	0.362	0.50 ( 0.47)	0.94	61184.6	12201.00
28	6308.84	191.47	0.357	0.50 ( 0.47)	0.94	62475.3	12111.00
29	5346.62	208.17	0.348	0.50 ( 0.47)	0.94	64398.2	12261.00

30	4858.37	218.05	0.342	0.50 ( 0.47)	0.94	65209.3	10200.00
31	4261.21	234.25	0.334	0.50 ( 0.47)	0.94	66447.2	10300.00
32	3512.05	262.76	0.318	0.50 ( 0.47)	0.94	67127.8	12000.00
33	2429.46	333.56	0.280	0.50 ( 0.47)	0.94	67798.6	10100.00

TOTAL AREA (ACRES) = 67798.6

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 15106.54 Tc (MIN.) = 33.192  
EFFECTIVE AREA (ACRES) = 8506.17 AREA-AVERAGED Fm (INCH/HR) = 0.41  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.82  
TOTAL AREA (ACRES) = 67798.6  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130615.79 FEET.

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 67798.6 TC (MIN.) = 33.19  
EFFECTIVE AREA (ACRES) = 8506.17 AREA-AVERAGED Fm (INCH/HR) = 0.41  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.821  
PEAK FLOW RATE (CFS) = 15106.54

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14389.29	16.38	1.242	0.50 ( 0.41)	0.82	3607.4	10520.00
2	14593.00	18.98	1.144	0.50 ( 0.41)	0.82	4174.1	10600.00
3	14896.46	22.92	1.024	0.50 ( 0.41)	0.82	5023.8	10230.00
4	14933.78	23.72	1.002	0.50 ( 0.41)	0.82	5236.6	10300.00
5	14945.99	24.01	0.994	0.50 ( 0.41)	0.82	5311.1	10380.00
6	14967.14	24.54	0.979	0.50 ( 0.41)	0.82	5446.5	400.00
7	14981.75	25.35	0.959	0.50 ( 0.41)	0.82	5738.6	10400.00
8	15019.96	27.58	0.917	0.50 ( 0.41)	0.82	6534.5	10320.00
9	15057.50	29.99	0.870	0.50 ( 0.41)	0.82	7387.5	10360.00
10	15073.76	31.06	0.856	0.50 ( 0.41)	0.82	7763.7	10250.00
11	15094.73	32.48	0.838	0.50 ( 0.41)	0.82	8258.6	10340.00
12	15100.80	32.84	0.834	0.50 ( 0.41)	0.82	8384.9	10200.00
13	15106.54	33.19	0.829	0.50 ( 0.41)	0.82	8506.2	50600.00
14	14962.29	37.41	0.775	0.50 ( 0.41)	0.82	10132.4	10220.00
15	14902.69	39.27	0.751	0.50 ( 0.41)	0.83	10848.7	10500.00
16	14568.64	49.27	0.666	0.50 ( 0.42)	0.83	14603.0	100.00
17	14046.37	57.75	0.612	0.50 ( 0.42)	0.85	18054.5	10100.00
18	13320.97	69.72	0.564	0.50 ( 0.43)	0.87	22568.0	20100.00
19	12448.28	84.51	0.513	0.50 ( 0.44)	0.89	27768.7	11801.00
20	11896.29	96.14	0.482	0.50 ( 0.45)	0.90	31745.8	11500.00
21	11279.61	108.48	0.457	0.50 ( 0.45)	0.91	36426.4	11000.00
22	10659.02	122.42	0.431	0.50 ( 0.46)	0.92	42824.0	13000.00
23	10247.46	131.71	0.420	0.50 ( 0.46)	0.92	47050.9	10900.00
24	9749.38	140.61	0.410	0.50 ( 0.46)	0.93	50512.2	11130.00
25	8989.72	152.69	0.395	0.50 ( 0.47)	0.93	54290.7	11620.00
26	7845.12	169.51	0.375	0.50 ( 0.47)	0.94	58867.2	12400.00
27	6951.21	181.60	0.362	0.50 ( 0.47)	0.94	61184.6	12201.00
28	6308.84	191.47	0.357	0.50 ( 0.47)	0.94	62475.3	12111.00
29	5346.62	208.17	0.348	0.50 ( 0.47)	0.94	64398.2	12261.00
30	4858.37	218.05	0.342	0.50 ( 0.47)	0.94	65209.3	10200.00
31	4261.21	234.25	0.334	0.50 ( 0.47)	0.94	66447.2	10300.00
32	3512.05	262.76	0.318	0.50 ( 0.47)	0.94	67127.8	12000.00
33	2429.46	333.56	0.280	0.50 ( 0.47)	0.94	67798.6	10100.00

END OF RATIONAL METHOD ANALYSIS



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA 92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S38- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 5-YR RM EV APRIL 2019 ROKAMOTO \*  
\*\*\*\*\*

FILE NAME: RI05EV38.DAT  
TIME/DATE OF STUDY: 17:20 04/08/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 5.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 2.589
- 2) 10.00; 1.733
- 3) 15.00; 1.292
- 4) 20.00; 1.105
- 5) 25.00; 0.965
- 6) 30.00; 0.869
- 7) 40.00; 0.741
- 8) 50.00; 0.659
- 9) 60.00; 0.597
- 10) 90.00; 0.493
- 11) 120.00; 0.433
- 12) 180.00; 0.362
- 13) 360.00; 0.265
- 14) 1200.00; 0.115

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	(FT)	(FT)	SIDE / SIDE/ WAY	(FT)	(FT)	(FT)	(FT)	(n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI05EV37.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14593.00	18.98	0.50 ( 0.41)	0.82	4174.1	10600.00
2	15106.54	33.19	0.50 ( 0.41)	0.82	8506.2	50600.00
3	14568.64	49.27	0.50 ( 0.42)	0.83	14603.0	100.00
4	14046.37	57.75	0.50 ( 0.42)	0.85	18054.5	10100.00
5	13320.97	69.72	0.50 ( 0.43)	0.87	22568.0	20100.00
6	12448.28	84.51	0.50 ( 0.44)	0.89	27768.7	11801.00
7	11896.29	96.14	0.50 ( 0.45)	0.90	31745.8	11500.00
8	11279.61	108.48	0.50 ( 0.45)	0.91	36426.4	11000.00
9	10659.02	122.42	0.50 ( 0.46)	0.92	42824.0	13000.00
10	10247.46	131.71	0.50 ( 0.46)	0.92	47050.9	10900.00
11	9749.38	140.61	0.50 ( 0.46)	0.93	50512.2	11130.00
12	8989.72	152.69	0.50 ( 0.47)	0.93	54290.7	11620.00
13	7845.12	169.51	0.50 ( 0.47)	0.94	58867.2	12400.00
14	6951.21	181.60	0.50 ( 0.47)	0.94	61184.6	12201.00
15	6308.84	191.47	0.50 ( 0.47)	0.94	62475.3	12111.00
16	5346.62	208.17	0.50 ( 0.47)	0.94	64398.2	12261.00
17	4858.37	218.05	0.50 ( 0.47)	0.94	65209.3	10200.00
18	4261.21	234.25	0.50 ( 0.47)	0.94	66447.2	10300.00
19	3512.05	262.76	0.50 ( 0.47)	0.94	67127.8	12000.00
20	2429.46	333.56	0.50 ( 0.47)	0.94	67798.6	10100.00
TOTAL AREA(ACRES) =						67798.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14593.00	18.98	0.50 ( 0.41)	0.82	4174.1	10600.00
2	15106.54	33.19	0.50 ( 0.41)	0.82	8506.2	50600.00
3	14568.64	49.27	0.50 ( 0.42)	0.83	14603.0	100.00
4	14046.37	57.75	0.50 ( 0.42)	0.85	18054.5	10100.00
5	13320.97	69.72	0.50 ( 0.43)	0.87	22568.0	20100.00
6	12448.28	84.51	0.50 ( 0.44)	0.89	27768.7	11801.00
7	11896.29	96.14	0.50 ( 0.45)	0.90	31745.8	11500.00
8	11279.61	108.48	0.50 ( 0.45)	0.91	36426.4	11000.00
9	10659.02	122.42	0.50 ( 0.46)	0.92	42824.0	13000.00
10	10247.46	131.71	0.50 ( 0.46)	0.92	47050.9	10900.00
11	9749.38	140.61	0.50 ( 0.46)	0.93	50512.2	11130.00
12	8989.72	152.69	0.50 ( 0.47)	0.93	54290.7	11620.00
13	7845.12	169.51	0.50 ( 0.47)	0.94	58867.2	12400.00

14	6951.21	181.60	0.50	( 0.47)	0.94	61184.6	12201.00
15	6308.84	191.47	0.50	( 0.47)	0.94	62475.3	12111.00
16	5346.62	208.17	0.50	( 0.47)	0.94	64398.2	12261.00
17	4858.37	218.05	0.50	( 0.47)	0.94	65209.3	10200.00
18	4261.21	234.25	0.50	( 0.47)	0.94	66447.2	10300.00
19	3512.05	262.76	0.50	( 0.47)	0.94	67127.8	12000.00
20	2429.46	333.56	0.50	( 0.47)	0.94	67798.6	10100.00

TOTAL AREA (ACRES) = 67798.6

\*\*\*\*\*

FLOW PROCESS FROM NODE 13803.00 TO NODE 13820.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 140.00 DOWNSTREAM (FEET) = 137.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 926.91 CHANNEL SLOPE = 0.0032  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.812

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	31.44	0.50	0.983	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.983  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 15111.08  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 12.62  
AVERAGE FLOW DEPTH (FEET) = 19.98 TRAVEL TIME (MIN.) = 1.22  
Tc (MIN.) = 34.42  
SUBAREA AREA (ACRES) = 31.44 SUBAREA RUNOFF (CFS) = 9.08  
EFFECTIVE AREA (ACRES) = 8537.61 AREA-AVERAGED Fm (INCH/HR) = 0.41  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.82  
TOTAL AREA (ACRES) = 67830.0 PEAK FLOW RATE (CFS) = 15106.54  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 19.98 FLOW VELOCITY (FEET/SEC.) = 12.62  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13820.00 = 131542.70 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13803.00 TO NODE 13820.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

TOTAL NUMBER OF STREAMS = 2  
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
TIME OF CONCENTRATION (MIN.) = 34.42  
RAINFALL INTENSITY (INCH/HR) = 0.81  
AREA-AVERAGED Fm (INCH/HR) = 0.41  
AREA-AVERAGED Fp (INCH/HR) = 0.50  
AREA-AVERAGED Ap = 0.82  
EFFECTIVE STREAM AREA (ACRES) = 8537.61  
TOTAL STREAM AREA (ACRES) = 67830.02  
PEAK FLOW RATE (CFS) AT CONFLUENCE = 15106.54

\*\*\*\*\*

FLOW PROCESS FROM NODE 13810.00 TO NODE 13811.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH (FEET) = 648.54  
ELEVATION DATA: UPSTREAM (FEET) = 756.46 DOWNSTREAM (FEET) = 586.02

Tc = K \* [(LENGTH \*\* 3.00) / (ELEVATION CHANGE)] \*\* 0.20  
SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 12.293  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.531

SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------	--------------

NATURAL FAIR COVER  
"CHAPARRAL, BROADLEAF" - 5.58 0.50 1.000 0 12.29  
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA RUNOFF (CFS) = 5.18  
TOTAL AREA (ACRES) = 5.58 PEAK FLOW RATE (CFS) = 5.18

\*\*\*\*\*

FLOW PROCESS FROM NODE 13811.00 TO NODE 13811.50 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 586.02 DOWNSTREAM (FEET) = 437.69  
CHANNEL LENGTH THRU SUBAREA (FEET) = 696.28 CHANNEL SLOPE = 0.2130  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.358

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	14.79	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 10.91  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.93  
AVERAGE FLOW DEPTH (FEET) = 0.78 TRAVEL TIME (MIN.) = 1.96  
Tc (MIN.) = 14.25  
SUBAREA AREA (ACRES) = 14.79 SUBAREA RUNOFF (CFS) = 11.42  
EFFECTIVE AREA (ACRES) = 20.37 AREA-AVERAGED Fm (INCH/HR) = 0.50  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
TOTAL AREA (ACRES) = 20.4 PEAK FLOW RATE (CFS) = 15.73

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 0.90 FLOW VELOCITY (FEET/SEC.) = 6.51  
LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13811.50 = 1344.82 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13811.50 TO NODE 13812.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 437.69 DOWNSTREAM (FEET) = 402.36  
CHANNEL LENGTH THRU SUBAREA (FEET) = 681.04 CHANNEL SLOPE = 0.0519

CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.217  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 18.41 0.50 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 21.68  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.13  
 AVERAGE FLOW DEPTH (FEET) = 1.32 TRAVEL TIME (MIN.) = 2.75  
 Tc (MIN.) = 17.00  
 SUBAREA AREA (ACRES) = 18.41 SUBAREA RUNOFF (CFS) = 11.88  
 EFFECTIVE AREA (ACRES) = 38.78 AREA-AVERAGED Fm (INCH/HR) = 0.50  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA (ACRES) = 38.8 PEAK FLOW RATE (CFS) = 25.03

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 1.39 FLOW VELOCITY (FEET/SEC.) = 4.30  
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13812.00 = 2025.86 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13812.00 TO NODE 13813.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 402.36 DOWNSTREAM (FEET) = 259.72  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1282.56 CHANNEL SLOPE = 0.1112  
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.091  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 27.87 0.50 0.858 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.858  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 33.34  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.12  
 AVERAGE FLOW DEPTH (FEET) = 1.35 TRAVEL TIME (MIN.) = 3.49  
 Tc (MIN.) = 20.49  
 SUBAREA AREA (ACRES) = 27.87 SUBAREA RUNOFF (CFS) = 16.61  
 EFFECTIVE AREA (ACRES) = 66.65 AREA-AVERAGED Fm (INCH/HR) = 0.47  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.94  
 TOTAL AREA (ACRES) = 66.7 PEAK FLOW RATE (CFS) = 37.24

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 1.41 FLOW VELOCITY (FEET/SEC.) = 6.27  
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13813.00 = 3308.42 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 31  
 -----

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 259.72 DOWNSTREAM (FEET) = 137.00  
 FLOW LENGTH (FEET) = 2412.88 MANNING'S N = 0.013  
 ESTIMATED PIPE DIAMETER (INCH) INCREASED TO 36.000  
 DEPTH OF FLOW IN 36.0 INCH PIPE IS 12.6 INCHES  
 PIPE-FLOW VELOCITY (FEET/SEC.) = 16.98  
 ESTIMATED PIPE DIAMETER (INCH) = 36.00 NUMBER OF PIPES = 1  
 PIPE-FLOW (CFS) = 37.24  
 PIPE TRAVEL TIME (MIN.) = 2.37 Tc (MIN.) = 22.86  
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13820.00 = 5721.30 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 22.86  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.025  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 83.64 0.50 0.570 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.570  
 SUBAREA AREA (ACRES) = 83.64 SUBAREA RUNOFF (CFS) = 55.70  
 EFFECTIVE AREA (ACRES) = 150.29 AREA-AVERAGED Fm (INCH/HR) = 0.37  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.73  
 TOTAL AREA (ACRES) = 150.3 PEAK FLOW RATE (CFS) = 88.96

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 1  
 -----

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
 TIME OF CONCENTRATION (MIN.) = 22.86  
 RAINFALL INTENSITY (INCH/HR) = 1.03  
 AREA-AVERAGED Fm (INCH/HR) = 0.37  
 AREA-AVERAGED Fp (INCH/HR) = 0.50  
 AREA-AVERAGED Ap = 0.73  
 EFFECTIVE STREAM AREA (ACRES) = 150.29  
 TOTAL STREAM AREA (ACRES) = 150.29  
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 88.96

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14593.00	20.22	1.099	0.50 (0.41)	0.82	4205.5	10600.00
1	15106.54	34.42	0.812	0.50 (0.41)	0.82	8537.6	50600.00
1	14568.64	50.50	0.656	0.50 (0.42)	0.83	14634.5	100.00
1	14046.37	58.99	0.603	0.50 (0.42)	0.85	18085.9	10100.00
1	13320.97	70.98	0.559	0.50 (0.43)	0.87	22599.5	20100.00
1	12448.28	85.80	0.508	0.50 (0.44)	0.89	27800.1	11801.00
1	11896.29	97.44	0.478	0.50 (0.45)	0.90	31777.2	11500.00
1	11279.61	109.80	0.453	0.50 (0.45)	0.91	36457.9	11000.00
1	10659.02	123.75	0.429	0.50 (0.46)	0.92	42855.4	13000.00
1	10247.46	133.06	0.418	0.50 (0.46)	0.92	47082.3	10900.00

1	9749.38	141.97	0.407	0.50	( 0.46)	0.93	50543.7	11130.00
1	8989.72	154.08	0.393	0.50	( 0.47)	0.93	54322.2	11620.00
1	7845.12	170.95	0.373	0.50	( 0.47)	0.94	58898.6	12400.00
1	6951.21	183.08	0.360	0.50	( 0.47)	0.94	61216.1	12201.00
1	6308.84	192.99	0.355	0.50	( 0.47)	0.94	62506.7	12111.00
1	5346.62	209.75	0.346	0.50	( 0.47)	0.94	64429.6	12261.00
1	4858.37	219.67	0.341	0.50	( 0.47)	0.94	65240.7	10200.00
1	4261.21	235.93	0.332	0.50	( 0.47)	0.94	66478.7	10300.00
1	3512.05	264.53	0.316	0.50	( 0.47)	0.94	67159.2	12000.00
1	2429.46	335.50	0.278	0.50	( 0.47)	0.94	67830.0	10100.00
2	88.96	22.86	1.025	0.50	( 0.37)	0.73	150.3	13810.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14680.53	20.22	1.099	0.50 ( 0.41)	0.82	4338.5	10600.00
2	14777.39	22.86	1.025	0.50 ( 0.41)	0.82	5160.9	13810.00
3	15166.75	34.42	0.812	0.50 ( 0.41)	0.82	8687.9	50600.00
4	14607.67	50.50	0.656	0.50 ( 0.42)	0.83	14784.7	100.00
5	14078.28	58.99	0.603	0.50 ( 0.42)	0.85	18236.2	10100.00
6	13346.88	70.98	0.559	0.50 ( 0.43)	0.87	22749.7	20100.00
7	12467.25	85.80	0.508	0.50 ( 0.44)	0.89	27950.4	11801.00
8	11913.47	97.44	0.478	0.50 ( 0.45)	0.89	31927.5	11500.00
9	11295.90	109.80	0.453	0.50 ( 0.45)	0.91	36608.2	11000.00
10	10674.42	123.75	0.429	0.50 ( 0.46)	0.92	43005.7	13000.00
11	10262.46	133.06	0.418	0.50 ( 0.46)	0.92	47232.6	10900.00
12	9764.00	141.97	0.407	0.50 ( 0.46)	0.93	50693.9	11130.00
13	9003.83	154.08	0.393	0.50 ( 0.47)	0.93	54472.5	11620.00
14	7858.51	170.95	0.373	0.50 ( 0.47)	0.94	59048.9	12400.00
15	6964.16	183.08	0.360	0.50 ( 0.47)	0.94	61366.4	12201.00
16	6321.59	192.99	0.355	0.50 ( 0.47)	0.94	62657.0	12111.00
17	5359.05	209.75	0.346	0.50 ( 0.47)	0.94	64579.9	12261.00
18	4870.61	219.67	0.341	0.50 ( 0.47)	0.94	65391.0	10200.00
19	4273.14	235.93	0.332	0.50 ( 0.47)	0.94	66628.9	10300.00
20	3523.42	264.53	0.316	0.50 ( 0.47)	0.94	67309.5	12000.00
21	2439.45	335.50	0.278	0.50 ( 0.47)	0.94	67980.3	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 15166.75 Tc (MIN.) = 34.42  
EFFECTIVE AREA(ACRES) = 8687.90 AREA-AVERAGED Fm(INCH/HR) = 0.41  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.82  
TOTAL AREA(ACRES) = 67980.3  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13820.00 = 131542.70 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13820.00 TO NODE 13840.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 137.00 DOWNSTREAM(FEET) = 133.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1261.34 CHANNEL SLOPE = 0.0032  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00

==>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL  
CAPACITY( NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM  
ALLOWABLE DEPTH).  
AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM  
ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.791  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 31.60 0.50 0.683 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.683  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 15173.14  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.64  
AVERAGE FLOW DEPTH(FEET) = 20.00 TRAVEL TIME(MIN.) = 1.66  
Tc(MIN.) = 36.08  
SUBAREA AREA(ACRES) = 31.60 SUBAREA RUNOFF(CFS) = 12.79  
EFFECTIVE AREA(ACRES) = 8719.50 AREA-AVERAGED Fm(INCH/HR) = 0.41  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.82  
TOTAL AREA(ACRES) = 68011.9 PEAK FLOW RATE(CFS) = 15166.75  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

==>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL  
CAPACITY( NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM  
ALLOWABLE DEPTH).  
AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM  
ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 20.00 FLOW VELOCITY(FEET/SEC.) = 12.64

==>FLOWDEPTH EXCEEDS MAXIMUM ALLOWABLE DEPTH

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13840.00 = 132804.05 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13820.00 TO NODE 13840.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
TIME OF CONCENTRATION(MIN.) = 36.08  
RAINFALL INTENSITY(INCH/HR) = 0.79  
AREA-AVERAGED Fm(INCH/HR) = 0.41  
AREA-AVERAGED Fp(INCH/HR) = 0.50  
AREA-AVERAGED Ap = 0.82  
EFFECTIVE STREAM AREA(ACRES) = 8719.50  
TOTAL STREAM AREA(ACRES) = 68011.91  
PEAK FLOW RATE(CFS) AT CONFLUENCE = 15166.75

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13830.00 TO NODE 13831.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<



=====
INITIAL SUBAREA FLOW-LENGTH (FEET) = 744.71
ELEVATION DATA: UPSTREAM (FEET) = 1100.95 DOWNSTREAM (FEET) = 959.21

Tc = K \* [(LENGTH\*\* 3.00) / (ELEVATION CHANGE)] \*\* 0.20
SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 13.858
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.393
SUBAREA Tc AND LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)
NATURAL FAIR COVER
"CHAPARRAL, BROADLEAF" - 5.06 0.50 1.000 0 13.86
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF (CFS) = 4.06
TOTAL AREA (ACRES) = 5.06 PEAK FLOW RATE (CFS) = 4.06

\*\*\*\*\*
FLOW PROCESS FROM NODE 13831.00 TO NODE 13832.00 IS CODE = 51
-----

>>>> COMPUTE TRAPEZOIDAL CHANNEL FLOW <<<<<
>>>> TRAVEL TIME THRU SUBAREA (EXISTING ELEMENT) <<<<<

=====
ELEVATION DATA: UPSTREAM (FEET) = 959.21 DOWNSTREAM (FEET) = 832.83
CHANNEL LENGTH THRU SUBAREA (FEET) = 1076.71 CHANNEL SLOPE = 0.1174
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.202
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 32.57 0.50 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 14.43
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.07
AVERAGE FLOW DEPTH (FEET) = 0.97 TRAVEL TIME (MIN.) = 3.54
Tc (MIN.) = 17.39
SUBAREA AREA (ACRES) = 32.57 SUBAREA RUNOFF (CFS) = 20.58
EFFECTIVE AREA (ACRES) = 37.63 AREA-AVERAGED Fm (INCH/HR) = 0.50
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 37.6 PEAK FLOW RATE (CFS) = 23.78

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 1.17 FLOW VELOCITY (FEET/SEC.) = 5.77
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13832.00 = 1821.42 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 13832.00 TO NODE 13833.00 IS CODE = 51
-----

>>>> COMPUTE TRAPEZOIDAL CHANNEL FLOW <<<<<
>>>> TRAVEL TIME THRU SUBAREA (EXISTING ELEMENT) <<<<<

=====
ELEVATION DATA: UPSTREAM (FEET) = 832.83 DOWNSTREAM (FEET) = 572.49
CHANNEL LENGTH THRU SUBAREA (FEET) = 1883.58 CHANNEL SLOPE = 0.1382
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.044

SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 32.23 0.50 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 31.70
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.56
AVERAGE FLOW DEPTH (FEET) = 1.27 TRAVEL TIME (MIN.) = 4.79
Tc (MIN.) = 22.18
SUBAREA AREA (ACRES) = 32.23 SUBAREA RUNOFF (CFS) = 15.77
EFFECTIVE AREA (ACRES) = 69.86 AREA-AVERAGED Fm (INCH/HR) = 0.50
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 69.9 PEAK FLOW RATE (CFS) = 34.19

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 1.31 FLOW VELOCITY (FEET/SEC.) = 6.67
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13833.00 = 3705.00 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 13833.00 TO NODE 13834.00 IS CODE = 51
-----

>>>> COMPUTE TRAPEZOIDAL CHANNEL FLOW <<<<<
>>>> TRAVEL TIME THRU SUBAREA (EXISTING ELEMENT) <<<<<

=====
ELEVATION DATA: UPSTREAM (FEET) = 572.49 DOWNSTREAM (FEET) = 471.65
CHANNEL LENGTH THRU SUBAREA (FEET) = 943.78 CHANNEL SLOPE = 0.1068
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.974
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 27.51 0.50 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 40.06
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.31
AVERAGE FLOW DEPTH (FEET) = 1.45 TRAVEL TIME (MIN.) = 2.49
Tc (MIN.) = 24.67
SUBAREA AREA (ACRES) = 27.51 SUBAREA RUNOFF (CFS) = 11.73
EFFECTIVE AREA (ACRES) = 97.37 AREA-AVERAGED Fm (INCH/HR) = 0.50
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 97.4 PEAK FLOW RATE (CFS) = 41.54

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 1.48 FLOW VELOCITY (FEET/SEC.) = 6.36
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13834.00 = 4648.78 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 13834.00 TO NODE 13835.00 IS CODE = 51
-----

>>>> COMPUTE TRAPEZOIDAL CHANNEL FLOW <<<<<
>>>> TRAVEL TIME THRU SUBAREA (EXISTING ELEMENT) <<<<<

=====
ELEVATION DATA: UPSTREAM (FEET) = 471.65 DOWNSTREAM (FEET) = 347.06
CHANNEL LENGTH THRU SUBAREA (FEET) = 1647.45 CHANNEL SLOPE = 0.0756
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.885  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 94.21 0.50 1.000 -  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 57.90  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.09  
 AVERAGE FLOW DEPTH (FEET) = 1.78 TRAVEL TIME (MIN.) = 4.51  
 Tc (MIN.) = 29.18  
 SUBAREA AREA (ACRES) = 94.21 SUBAREA RUNOFF (CFS) = 32.60  
 EFFECTIVE AREA (ACRES) = 191.58 AREA-AVERAGED Fm (INCH/HR) = 0.50  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA (ACRES) = 191.6 PEAK FLOW RATE (CFS) = 66.29

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 1.87 FLOW VELOCITY (FEET/SEC.) = 6.29  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13835.00 = 6296.23 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13835.00 TO NODE 13836.00 IS CODE = 51

>>>> COMPUTE TRAPEZOIDAL CHANNEL FLOW <<<<<  
 >>>> TRAVEL TIME THRU SUBAREA (EXISTING ELEMENT) <<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 347.06 DOWNSTREAM (FEET) = 269.29  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1696.71 CHANNEL SLOPE = 0.0458  
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.817  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 233.25 0.50 1.000 -  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 99.64  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.77  
 AVERAGE FLOW DEPTH (FEET) = 2.40 TRAVEL TIME (MIN.) = 4.90  
 Tc (MIN.) = 34.08  
 SUBAREA AREA (ACRES) = 233.25 SUBAREA RUNOFF (CFS) = 66.45  
 EFFECTIVE AREA (ACRES) = 424.83 AREA-AVERAGED Fm (INCH/HR) = 0.50  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA (ACRES) = 424.8 PEAK FLOW RATE (CFS) = 121.04

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 2.58 FLOW VELOCITY (FEET/SEC.) = 6.05  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13836.00 = 7992.94 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13836.00 TO NODE 13837.00 IS CODE = 51

>>>> COMPUTE TRAPEZOIDAL CHANNEL FLOW <<<<<  
 >>>> TRAVEL TIME THRU SUBAREA (EXISTING ELEMENT) <<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 269.29 DOWNSTREAM (FEET) = 191.87

CHANNEL LENGTH THRU SUBAREA (FEET) = 2529.21 CHANNEL SLOPE = 0.0306  
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.725  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 134.70 0.50 0.880 -  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.880  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 138.34  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.39  
 AVERAGE FLOW DEPTH (FEET) = 2.92 TRAVEL TIME (MIN.) = 7.82  
 Tc (MIN.) = 41.90  
 SUBAREA AREA (ACRES) = 134.70 SUBAREA RUNOFF (CFS) = 34.58  
 EFFECTIVE AREA (ACRES) = 559.53 AREA-AVERAGED Fm (INCH/HR) = 0.49  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.97  
 TOTAL AREA (ACRES) = 559.5 PEAK FLOW RATE (CFS) = 121.04  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 2.78 FLOW VELOCITY (FEET/SEC.) = 5.21  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13837.00 = 10522.15 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 31

>>>> COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA <<<<<  
 >>>> USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW) <<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 191.87 DOWNSTREAM (FEET) = 133.00  
 FLOW LENGTH (FEET) = 1151.02 MANNING'S N = 0.013  
 DEPTH OF FLOW IN 36.0 INCH PIPE IS 25.4 INCHES  
 PIPE-FLOW VELOCITY (FEET/SEC.) = 22.71  
 ESTIMATED PIPE DIAMETER (INCH) = 36.00 NUMBER OF PIPES = 1  
 PIPE-FLOW (CFS) = 121.04  
 PIPE TRAVEL TIME (MIN.) = 0.84 Tc (MIN.) = 42.75  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13840.00 = 11673.17 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 81

>>>> ADDITION OF SUBAREA TO MAINLINE PEAK FLOW <<<<<

=====

MAINLINE Tc (MIN.) = 42.75  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.718  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 5.97 0.50 0.622 -  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.622  
 SUBAREA AREA (ACRES) = 5.97 SUBAREA RUNOFF (CFS) = 2.19  
 EFFECTIVE AREA (ACRES) = 565.50 AREA-AVERAGED Fm (INCH/HR) = 0.48  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.97  
 TOTAL AREA (ACRES) = 565.5 PEAK FLOW RATE (CFS) = 121.04  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 42.75
RAINFALL INTENSITY(INCH/HR) = 0.72
AREA-AVERAGED Fm(INCH/HR) = 0.48
AREA-AVERAGED Fp(INCH/HR) = 0.50
AREA-AVERAGED Ap = 0.97
EFFECTIVE STREAM AREA(ACRES) = 565.50
TOTAL STREAM AREA(ACRES) = 565.50
PEAK FLOW RATE(CFS) AT CONFLUENCE = 121.04

\*\* CONFLUENCE DATA \*\*

Table with columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 22 rows of data.

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

Table with columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 9 rows of data.

Table with columns: Node, Q, Tc, Intensity, Fp, Ap, Ae, Headwater Node. Contains 22 rows of data.

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 15287.79 Tc(MIN.) = 36.08
EFFECTIVE AREA(ACRES) = 9196.79 AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.83
TOTAL AREA(ACRES) = 68577.4
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13840.00 = 132804.05 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13840.00 TO NODE 13860.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 133.00 DOWNSTREAM(FEET) = 130.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 654.44 CHANNEL SLOPE = 0.0046
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.782
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 6.61 0.50 0.975 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.975
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 15288.66
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 14.43
AVERAGE FLOW DEPTH(FEET) = 18.80 TRAVEL TIME(MIN.) = 0.76
Tc(MIN.) = 36.83
SUBAREA AREA(ACRES) = 6.61 SUBAREA RUNOFF(CFS) = 1.75
EFFECTIVE AREA(ACRES) = 9203.41 AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.83
TOTAL AREA(ACRES) = 68584.0 PEAK FLOW RATE(CFS) = 15287.79
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 18.80 FLOW VELOCITY(FEET/SEC.) = 14.42
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13860.00 = 133458.48 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13840.00 TO NODE 13860.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

TOTAL NUMBER OF STREAMS = 2

CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:

TIME OF CONCENTRATION(MIN.) = 36.83
RAINFALL INTENSITY (INCH/HR) = 0.78
AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50
AREA-AVERAGED Ap = 0.83
EFFECTIVE STREAM AREA(ACRES) = 9203.41
TOTAL STREAM AREA(ACRES) = 68584.02
PEAK FLOW RATE(CFS) AT CONFLUENCE = 15287.79

\*\*\*\*\*
FLOW PROCESS FROM NODE 13850.00 TO NODE 13851.00 IS CODE = 21
-----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<
=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 617.57
ELEVATION DATA: UPSTREAM(FEET) = 646.95 DOWNSTREAM(FEET) = 490.10

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 12.137
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.544
SUBAREA Tc AND LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)
NATURAL FAIR COVER
"CHAPARRAL,BROADLEAF" - 4.95 0.50 1.000 0 12.14
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 4.65
TOTAL AREA(ACRES) = 4.95 PEAK FLOW RATE(CFS) = 4.65

\*\*\*\*\*
FLOW PROCESS FROM NODE 13851.00 TO NODE 13851.50 IS CODE = 51
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<
=====

ELEVATION DATA: UPSTREAM(FEET) = 490.10 DOWNSTREAM(FEET) = 440.98
CHANNEL LENGTH THRU SUBAREA(FEET) = 351.14 CHANNEL SLOPE = 0.1399
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.428
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 4.02 0.50 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 6.33
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.42
AVERAGE FLOW DEPTH(FEET) = 0.69 TRAVEL TIME(MIN.) = 1.33
Tc(MIN.) = 13.46
SUBAREA AREA(ACRES) = 4.02 SUBAREA RUNOFF(CFS) = 3.36
EFFECTIVE AREA(ACRES) = 8.97 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 9.0 PEAK FLOW RATE(CFS) = 7.49

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.74 FLOW VELOCITY(FEET/SEC.) = 4.59
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13851.50 = 968.71 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 13851.50 TO NODE 13852.00 IS CODE = 51
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<
=====

ELEVATION DATA: UPSTREAM(FEET) = 440.98 DOWNSTREAM(FEET) = 395.76
CHANNEL LENGTH THRU SUBAREA(FEET) = 512.91 CHANNEL SLOPE = 0.0882
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.272
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 7.17 0.50 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 9.98
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.15
AVERAGE FLOW DEPTH(FEET) = 0.90 TRAVEL TIME(MIN.) = 2.06
Tc(MIN.) = 15.52
SUBAREA AREA(ACRES) = 7.17 SUBAREA RUNOFF(CFS) = 4.98
EFFECTIVE AREA(ACRES) = 16.14 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 16.1 PEAK FLOW RATE(CFS) = 11.22

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.94 FLOW VELOCITY(FEET/SEC.) = 4.27
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13852.00 = 1481.62 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 13852.00 TO NODE 13853.00 IS CODE = 51
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<
=====

ELEVATION DATA: UPSTREAM(FEET) = 395.76 DOWNSTREAM(FEET) = 354.94
CHANNEL LENGTH THRU SUBAREA(FEET) = 443.69 CHANNEL SLOPE = 0.0920
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH(FEET) = 20.00
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.212
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 6.76 0.50 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 13.38
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.56
AVERAGE FLOW DEPTH(FEET) = 0.99 TRAVEL TIME(MIN.) = 1.62
Tc(MIN.) = 17.14
SUBAREA AREA(ACRES) = 6.76 SUBAREA RUNOFF(CFS) = 4.33
EFFECTIVE AREA(ACRES) = 22.90 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00

TOTAL AREA (ACRES) = 22.9 PEAK FLOW RATE (CFS) = 14.67

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 1.03 FLOW VELOCITY (FEET/SEC.) = 4.65  
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13853.00 = 1925.31 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13853.00 TO NODE 13854.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 354.94 DOWNSTREAM (FEET) = 263.57  
CHANNEL LENGTH THRU SUBAREA (FEET) = 962.09 CHANNEL SLOPE = 0.0950  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.096  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	18.16	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 19.54  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.07  
AVERAGE FLOW DEPTH (FEET) = 1.13 TRAVEL TIME (MIN.) = 3.16  
Tc (MIN.) = 20.31  
SUBAREA AREA (ACRES) = 18.16 SUBAREA RUNOFF (CFS) = 9.74  
EFFECTIVE AREA (ACRES) = 41.06 AREA-AVERAGED Fm (INCH/HR) = 0.50  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
TOTAL AREA (ACRES) = 41.1 PEAK FLOW RATE (CFS) = 22.03

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 1.19 FLOW VELOCITY (FEET/SEC.) = 5.21  
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13854.00 = 2887.40 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13854.00 TO NODE 13855.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 263.57 DOWNSTREAM (FEET) = 188.74  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1228.77 CHANNEL SLOPE = 0.0609  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.977  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	38.75	0.50	0.879	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.879  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 31.42  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.81  
AVERAGE FLOW DEPTH (FEET) = 1.48 TRAVEL TIME (MIN.) = 4.26  
Tc (MIN.) = 24.57  
SUBAREA AREA (ACRES) = 38.75 SUBAREA RUNOFF (CFS) = 18.75

EFFECTIVE AREA (ACRES) = 79.81 AREA-AVERAGED Fm (INCH/HR) = 0.47  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.94  
TOTAL AREA (ACRES) = 79.8 PEAK FLOW RATE (CFS) = 36.37

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 1.56 FLOW VELOCITY (FEET/SEC.) = 4.99  
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13855.00 = 4116.17 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 188.74 DOWNSTREAM (FEET) = 130.00  
FLOW LENGTH (FEET) = 2092.67 MANNING'S N = 0.013  
ESTIMATED PIPE DIAMETER (INCH) INCREASED TO 36.000  
DEPTH OF FLOW IN 36.0 INCH PIPE IS 14.5 INCHES  
PIPE-FLOW VELOCITY (FEET/SEC.) = 13.60  
ESTIMATED PIPE DIAMETER (INCH) = 36.00 NUMBER OF PIPES = 1  
PIPE-FLOW (CFS) = 36.37  
PIPE TRAVEL TIME (MIN.) = 2.57 Tc (MIN.) = 27.13  
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13860.00 = 6208.84 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 27.13  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.924  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	43.41	0.50	0.707	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.707  
SUBAREA AREA (ACRES) = 43.41 SUBAREA RUNOFF (CFS) = 22.29  
EFFECTIVE AREA (ACRES) = 123.22 AREA-AVERAGED Fm (INCH/HR) = 0.43  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.86  
TOTAL AREA (ACRES) = 123.2 PEAK FLOW RATE (CFS) = 54.85

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
TIME OF CONCENTRATION (MIN.) = 27.13  
RAINFALL INTENSITY (INCH/HR) = 0.92  
AREA-AVERAGED Fm (INCH/HR) = 0.43  
AREA-AVERAGED Fp (INCH/HR) = 0.50  
AREA-AVERAGED Ap = 0.86  
EFFECTIVE STREAM AREA (ACRES) = 123.22  
TOTAL STREAM AREA (ACRES) = 123.22  
PEAK FLOW RATE (CFS) AT CONFLUENCE = 54.85

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14801.56	22.67	1.030	0.50 ( 0.41)	0.83	4666.5	10600.00
1	14898.43	25.31	0.959	0.50 ( 0.41)	0.83	5523.8	13810.00
1	15287.79	36.83	0.782	0.50 ( 0.41)	0.83	9203.4	50600.00
1	15056.51	43.51	0.712	0.50 ( 0.42)	0.83	11813.8	13830.00
1	14690.99	52.96	0.641	0.50 ( 0.42)	0.84	15388.5	100.00
1	14135.37	61.47	0.592	0.50 ( 0.43)	0.85	18839.9	10100.00
1	13382.49	73.50	0.550	0.50 ( 0.43)	0.87	23353.5	20100.00
1	12476.30	88.35	0.499	0.50 ( 0.44)	0.89	28554.1	11801.00
1	11921.44	100.03	0.473	0.50 ( 0.45)	0.90	32531.2	11500.00
1	11303.46	112.42	0.448	0.50 ( 0.45)	0.91	37211.9	11000.00
1	10681.58	126.41	0.425	0.50 ( 0.46)	0.92	43609.4	13000.00
1	10269.44	135.75	0.414	0.50 ( 0.46)	0.92	47836.3	10900.00
1	9770.81	144.69	0.404	0.50 ( 0.46)	0.93	51297.7	11130.00
1	9010.39	156.86	0.389	0.50 ( 0.47)	0.93	55076.2	11620.00
1	7864.74	173.82	0.369	0.50 ( 0.47)	0.94	59652.6	12400.00
1	6970.20	186.04	0.359	0.50 ( 0.47)	0.94	61970.1	12201.00
1	6327.54	196.02	0.353	0.50 ( 0.47)	0.94	63260.7	12111.00
1	5364.85	212.91	0.344	0.50 ( 0.47)	0.94	65183.6	12261.00
1	4876.31	222.91	0.339	0.50 ( 0.47)	0.94	65994.7	10200.00
1	4278.69	239.27	0.330	0.50 ( 0.47)	0.94	67232.7	10300.00
1	3528.71	268.03	0.315	0.50 ( 0.47)	0.94	67913.2	12000.00
1	2444.11	339.34	0.276	0.50 ( 0.47)	0.94	68584.0	10100.00
2	54.85	27.13	0.924	0.50 ( 0.43)	0.86	123.2	13850.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14856.41	22.67	1.030	0.50 ( 0.41)	0.83	4769.5	10600.00
2	14953.21	25.31	0.959	0.50 ( 0.41)	0.83	5638.7	13810.00
3	15014.88	27.13	0.924	0.50 ( 0.41)	0.83	6229.3	13850.00
4	15326.82	36.83	0.782	0.50 ( 0.41)	0.83	9326.6	50600.00
5	15087.86	43.51	0.712	0.50 ( 0.42)	0.83	11937.0	13830.00
6	14714.40	52.96	0.641	0.50 ( 0.42)	0.84	15511.7	100.00
7	14153.38	61.47	0.592	0.50 ( 0.43)	0.85	18963.1	10100.00
8	13395.88	73.50	0.550	0.50 ( 0.43)	0.87	23476.7	20100.00
9	12484.12	88.35	0.499	0.50 ( 0.44)	0.89	28677.4	11801.00
10	11928.85	100.03	0.473	0.50 ( 0.45)	0.90	32654.4	11500.00
11	11310.48	112.42	0.448	0.50 ( 0.45)	0.91	37335.1	11000.00
12	10688.25	126.41	0.425	0.50 ( 0.46)	0.92	43732.7	13000.00
13	10275.93	135.75	0.414	0.50 ( 0.46)	0.92	47959.6	10900.00
14	9777.13	144.69	0.404	0.50 ( 0.46)	0.93	51420.9	11130.00
15	9016.49	156.86	0.389	0.50 ( 0.47)	0.93	55199.4	11620.00
16	7870.52	173.82	0.369	0.50 ( 0.47)	0.94	59775.8	12400.00
17	6975.82	186.04	0.359	0.50 ( 0.47)	0.94	62093.3	12201.00
18	6333.07	196.02	0.353	0.50 ( 0.47)	0.94	63383.9	12111.00
19	5370.24	212.91	0.344	0.50 ( 0.47)	0.94	65306.8	12261.00
20	4881.62	222.91	0.339	0.50 ( 0.47)	0.94	66118.0	10200.00
21	4283.86	239.27	0.330	0.50 ( 0.47)	0.94	67355.9	10300.00
22	3533.64	268.03	0.315	0.50 ( 0.47)	0.94	68036.4	12000.00
23	2448.43	339.34	0.276	0.50 ( 0.47)	0.94	68707.2	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 15326.82 Tc (MIN.) = 36.83  
EFFECTIVE AREA(ACRES) = 9326.62 AREA-AVERAGED Fm(INCH/HR) = 0.41  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.83  
TOTAL AREA(ACRES) = 68707.2  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13860.00 = 133458.48 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13860.00 TO NODE 13880.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 130.00 DOWNSTREAM(FEET) = 120.57

CHANNEL LENGTH THRU SUBAREA(FEET) = 610.77 CHANNEL SLOPE = 0.0154

CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00

\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.776

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/	SCS SOIL	AREA	Fp	Ap	SCS
LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN

USER-DEFINED	-	4.89	0.50	1.000	-
--------------	---	------	------	-------	---

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 15327.43

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 22.75

AVERAGE FLOW DEPTH(FEET) = 14.99 TRAVEL TIME(MIN.) = 0.45

Tc(MIN.) = 37.28

SUBAREA AREA(ACRES) = 4.89 SUBAREA RUNOFF(CFS) = 1.21

EFFECTIVE AREA(ACRES) = 9331.51 AREA-AVERAGED Fm(INCH/HR) = 0.41

AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.83

TOTAL AREA(ACRES) = 68712.1 PEAK FLOW RATE(CFS) = 15326.82

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 14.99 FLOW VELOCITY(FEET/SEC.) = 22.75

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13880.00 = 134069.25 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13860.00 TO NODE 13880.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

\*\*\*\*\*

TOTAL NUMBER OF STREAMS = 2

CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:

TIME OF CONCENTRATION(MIN.) = 37.28

RAINFALL INTENSITY(INCH/HR) = 0.78

AREA-AVERAGED Fm(INCH/HR) = 0.41

AREA-AVERAGED Fp(INCH/HR) = 0.50

AREA-AVERAGED Ap = 0.83

EFFECTIVE STREAM AREA(ACRES) = 9331.51

TOTAL STREAM AREA(ACRES) = 68712.13

PEAK FLOW RATE(CFS) AT CONFLUENCE = 15326.82

\*\*\*\*\*

FLOW PROCESS FROM NODE 13870.00 TO NODE 13871.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<

>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH (FEET) = 872.65  
ELEVATION DATA: UPSTREAM (FEET) = 558.52 DOWNSTREAM (FEET) = 436.47

Tc = K \* [(LENGTH\*\* 3.00) / (ELEVATION CHANGE)]\*\* 0.20  
SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 15.704

\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.266

SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------	--------------

NATURAL FAIR COVER						
"GRASS"	-	7.32	0.50	1.000	0	15.70

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

SUBAREA RUNOFF (CFS) = 5.04

TOTAL AREA (ACRES) = 7.32 PEAK FLOW RATE (CFS) = 5.04

\*\*\*\*\*

FLOW PROCESS FROM NODE 13871.00 TO NODE 13872.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 436.47 DOWNSTREAM (FEET) = 337.62

CHANNEL LENGTH THRU SUBAREA (FEET) = 827.95 CHANNEL SLOPE = 0.1194

CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00

\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.151

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

USER-DEFINED	-	13.01	0.50	1.000	-
--------------	---	-------	------	-------	---

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 8.87

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.49

AVERAGE FLOW DEPTH (FEET) = 0.81 TRAVEL TIME (MIN.) = 3.07

Tc (MIN.) = 18.78

SUBAREA AREA (ACRES) = 13.01 SUBAREA RUNOFF (CFS) = 7.62

EFFECTIVE AREA (ACRES) = 20.33 AREA-AVERAGED Fm (INCH/HR) = 0.50

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00

TOTAL AREA (ACRES) = 20.3 PEAK FLOW RATE (CFS) = 11.90

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 0.90 FLOW VELOCITY (FEET/SEC.) = 4.86

LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13872.00 = 1700.60 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13872.00 TO NODE 13873.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 337.62 DOWNSTREAM (FEET) = 253.88

CHANNEL LENGTH THRU SUBAREA (FEET) = 1049.16 CHANNEL SLOPE = 0.0798

CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.060 MAXIMUM DEPTH (FEET) = 20.00

\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.037

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

USER-DEFINED	-	32.99	0.50	0.923	-
--------------	---	-------	------	-------	---

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.923

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 20.46

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.79

AVERAGE FLOW DEPTH (FEET) = 1.19 TRAVEL TIME (MIN.) = 3.65

Tc (MIN.) = 22.43

SUBAREA AREA (ACRES) = 32.99 SUBAREA RUNOFF (CFS) = 17.08

EFFECTIVE AREA (ACRES) = 53.32 AREA-AVERAGED Fm (INCH/HR) = 0.48

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.95

TOTAL AREA (ACRES) = 53.3 PEAK FLOW RATE (CFS) = 26.91

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 1.32 FLOW VELOCITY (FEET/SEC.) = 5.13

LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13873.00 = 2749.76 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13873.00 TO NODE 13874.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 253.88 DOWNSTREAM (FEET) = 160.73

CHANNEL LENGTH THRU SUBAREA (FEET) = 1518.60 CHANNEL SLOPE = 0.0613

CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00

\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.941

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

USER-DEFINED	-	30.94	0.50	0.900	-
--------------	---	-------	------	-------	---

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.900

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 33.75

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.66

AVERAGE FLOW DEPTH (FEET) = 1.30 TRAVEL TIME (MIN.) = 3.80

Tc (MIN.) = 26.23

SUBAREA AREA (ACRES) = 30.94 SUBAREA RUNOFF (CFS) = 13.68

EFFECTIVE AREA (ACRES) = 84.26 AREA-AVERAGED Fm (INCH/HR) = 0.47

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.93

TOTAL AREA (ACRES) = 84.3 PEAK FLOW RATE (CFS) = 36.00

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 1.33 FLOW VELOCITY (FEET/SEC.) = 6.78

LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13874.00 = 4268.36 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13874.00 TO NODE 13875.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 160.73 DOWNSTREAM (FEET) = 158.14

CHANNEL LENGTH THRU SUBAREA (FEET) = 582.74 CHANNEL SLOPE = 0.0044

CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.873  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 73.67 0.50 0.930 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.930  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 49.56  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 2.74  
 AVERAGE FLOW DEPTH (FEET) = 2.45 TRAVEL TIME (MIN.) = 3.54  
 Tc (MIN.) = 29.77  
 SUBAREA AREA (ACRES) = 73.67 SUBAREA RUNOFF (CFS) = 27.07  
 EFFECTIVE AREA (ACRES) = 157.93 AREA-AVERAGED Fm (INCH/HR) = 0.47  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 157.9 PEAK FLOW RATE (CFS) = 57.91

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 2.60 FLOW VELOCITY (FEET/SEC.) = 2.85  
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13875.00 = 4851.10 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 158.14 DOWNSTREAM (FEET) = 120.57  
 FLOW LENGTH (FEET) = 1855.67 MANNING'S N = 0.013  
 ESTIMATED PIPE DIAMETER (INCH) INCREASED TO 36.000  
 DEPTH OF FLOW IN 36.0 INCH PIPE IS 21.0 INCHES  
 PIPE-FLOW VELOCITY (FEET/SEC.) = 13.53  
 ESTIMATED PIPE DIAMETER (INCH) = 36.00 NUMBER OF PIPES = 1  
 PIPE-FLOW (CFS) = 57.91  
 PIPE TRAVEL TIME (MIN.) = 2.29 Tc (MIN.) = 32.05  
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13880.00 = 6706.77 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 32.05  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.843  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 34.90 0.50 0.743 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.743  
 SUBAREA AREA (ACRES) = 34.90 SUBAREA RUNOFF (CFS) = 14.80  
 EFFECTIVE AREA (ACRES) = 192.83 AREA-AVERAGED Fm (INCH/HR) = 0.45  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.90  
 TOTAL AREA (ACRES) = 192.8 PEAK FLOW RATE (CFS) = 68.34

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 1

-----  
 >>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<  
 =====

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
 TIME OF CONCENTRATION (MIN.) = 32.05  
 RAINFALL INTENSITY (INCH/HR) = 0.84  
 AREA-AVERAGED Fm (INCH/HR) = 0.45  
 AREA-AVERAGED Fp (INCH/HR) = 0.50  
 AREA-AVERAGED Ap = 0.90  
 EFFECTIVE STREAM AREA (ACRES) = 192.83  
 TOTAL STREAM AREA (ACRES) = 192.83  
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 68.34

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14856.41	23.12	1.018	0.50 ( 0.42)	0.83	4774.4	10600.00
1	14953.21	25.76	0.950	0.50 ( 0.41)	0.83	5643.6	13810.00
1	15014.88	27.58	0.915	0.50 ( 0.41)	0.83	6234.2	13850.00
1	15326.82	37.28	0.776	0.50 ( 0.41)	0.83	9331.5	50600.00
1	15087.86	43.95	0.709	0.50 ( 0.42)	0.83	11941.9	13830.00
1	14714.40	53.41	0.638	0.50 ( 0.42)	0.84	15516.6	100.00
1	14153.38	61.93	0.590	0.50 ( 0.43)	0.85	18968.0	10100.00
1	13395.88	73.96	0.549	0.50 ( 0.43)	0.87	23481.6	20100.00
1	12484.12	88.82	0.497	0.50 ( 0.44)	0.89	28682.2	11801.00
1	11928.85	100.50	0.472	0.50 ( 0.45)	0.90	32659.3	11500.00
1	11310.48	112.90	0.447	0.50 ( 0.45)	0.91	37340.0	11000.00
1	10688.25	126.90	0.425	0.50 ( 0.46)	0.92	43737.5	13000.00
1	10275.93	136.24	0.414	0.50 ( 0.46)	0.92	47964.5	10900.00
1	9777.13	145.19	0.403	0.50 ( 0.46)	0.93	51425.8	11130.00
1	9016.49	157.37	0.389	0.50 ( 0.47)	0.93	55204.3	11620.00
1	7870.52	174.35	0.369	0.50 ( 0.47)	0.94	59780.7	12400.00
1	6975.82	186.59	0.358	0.50 ( 0.47)	0.94	62098.2	12201.00
1	6333.07	196.58	0.353	0.50 ( 0.47)	0.94	63388.8	12111.00
1	5370.24	213.49	0.344	0.50 ( 0.47)	0.94	65311.7	12261.00
1	4881.62	223.50	0.339	0.50 ( 0.47)	0.94	66122.8	10200.00
1	4283.86	239.89	0.330	0.50 ( 0.47)	0.94	67360.8	10300.00
1	3533.64	268.68	0.314	0.50 ( 0.47)	0.94	68041.3	12000.00
1	2448.43	340.05	0.276	0.50 ( 0.47)	0.94	68712.1	10100.00
2	68.34	32.05	0.843	0.50 ( 0.45)	0.90	192.8	13870.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14924.75	23.12	1.018	0.50 ( 0.42)	0.83	4913.5	10600.00
2	15021.54	25.76	0.950	0.50 ( 0.42)	0.83	5798.6	13810.00
3	15083.22	27.58	0.915	0.50 ( 0.42)	0.83	6400.1	13850.00
4	15227.07	32.05	0.843	0.50 ( 0.42)	0.83	7855.3	13870.00
5	15383.54	37.28	0.776	0.50 ( 0.41)	0.83	9524.3	50600.00
6	15132.92	43.95	0.709	0.50 ( 0.42)	0.83	12134.7	13830.00
7	14747.19	53.41	0.638	0.50 ( 0.42)	0.84	15709.4	100.00
8	14177.91	61.93	0.590	0.50 ( 0.43)	0.85	19160.8	10100.00
9	13413.17	73.96	0.549	0.50 ( 0.43)	0.87	23674.4	20100.00



10	12492.96	88.82	0.497	0.50	( 0.44)	0.89	28875.1	11801.00
11	11937.24	100.50	0.472	0.50	( 0.45)	0.90	32852.2	11500.00
12	11318.43	112.90	0.447	0.50	( 0.45)	0.91	37532.8	11000.00
13	10695.81	126.90	0.425	0.50	( 0.46)	0.92	43930.4	13000.00
14	10283.29	136.24	0.414	0.50	( 0.46)	0.92	48157.3	10900.00
15	9784.30	145.19	0.403	0.50	( 0.46)	0.93	51618.6	11130.00
16	9023.40	157.37	0.389	0.50	( 0.47)	0.93	55397.1	11620.00
17	7877.08	174.35	0.369	0.50	( 0.47)	0.94	59973.5	12400.00
18	6982.19	186.59	0.358	0.50	( 0.47)	0.94	62291.0	12201.00
19	6339.35	196.58	0.353	0.50	( 0.47)	0.94	63581.6	12111.00
20	5376.36	213.49	0.344	0.50	( 0.47)	0.94	65504.5	12261.00
21	4887.64	223.50	0.339	0.50	( 0.47)	0.94	66315.7	10200.00
22	4289.73	239.89	0.330	0.50	( 0.47)	0.94	67553.6	10300.00
23	3539.23	268.68	0.314	0.50	( 0.47)	0.94	68234.2	12000.00
24	2453.34	340.05	0.276	0.50	( 0.47)	0.94	68905.0	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 15383.54 Tc (MIN.) = 37.28  
EFFECTIVE AREA (ACRES) = 9524.34 AREA-AVERAGED Fm (INCH/HR) = 0.41  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.83  
TOTAL AREA (ACRES) = 68905.0  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13880.00 = 134069.25 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13880.00 TO NODE 13910.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 120.57 DOWNSTREAM (FEET) = 119.70  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1190.21 CHANNEL SLOPE = 0.0007  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00

==>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL  
CAPACITY ( NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM  
ALLOWABLE DEPTH).  
AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM  
ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.756  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	117.69	0.50	0.724	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.724  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 15404.41  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 12.84  
AVERAGE FLOW DEPTH (FEET) = 20.00 TRAVEL TIME (MIN.) = 1.55  
Tc (MIN.) = 38.83  
SUBAREA AREA (ACRES) = 117.69 SUBAREA RUNOFF (CFS) = 41.72  
EFFECTIVE AREA (ACRES) = 9642.04 AREA-AVERAGED Fm (INCH/HR) = 0.41  
AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.83  
TOTAL AREA (ACRES) = 69022.6 PEAK FLOW RATE (CFS) = 15383.54  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

==>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL

CAPACITY ( NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM  
ALLOWABLE DEPTH).  
AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM  
ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 20.00 FLOW VELOCITY (FEET/SEC.) = 12.82

==>FLOWDEPTH EXCEEDS MAXIMUM ALLOWABLE DEPTH

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13910.00 = 135259.45 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13880.00 TO NODE 13910.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

TOTAL NUMBER OF STREAMS = 2  
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
TIME OF CONCENTRATION (MIN.) = 38.83  
RAINFALL INTENSITY (INCH/HR) = 0.76  
AREA-AVERAGED Fm (INCH/HR) = 0.41  
AREA-AVERAGED Fp (INCH/HR) = 0.50  
AREA-AVERAGED Ap = 0.83  
EFFECTIVE STREAM AREA (ACRES) = 9642.04  
TOTAL STREAM AREA (ACRES) = 69022.65  
PEAK FLOW RATE (CFS) AT CONFLUENCE = 15383.54

\*\*\*\*\*

FLOW PROCESS FROM NODE 13889.00 TO NODE 13890.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH (FEET) = 447.89  
ELEVATION DATA: UPSTREAM (FEET) = 564.89 DOWNSTREAM (FEET) = 421.92

Tc = K \* [(LENGTH\*\* 3.00) / (ELEVATION CHANGE)] \*\* 0.20  
SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 6.976  
\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 2.251  
SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
PUBLIC PARK	-	3.03	0.50	0.960	0	6.98

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.960  
SUBAREA RUNOFF (CFS) = 4.83  
TOTAL AREA (ACRES) = 3.03 PEAK FLOW RATE (CFS) = 4.83

\*\*\*\*\*

FLOW PROCESS FROM NODE 13890.00 TO NODE 13891.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 421.92 DOWNSTREAM (FEET) = 392.64  
CHANNEL LENGTH THRU SUBAREA (FEET) = 435.33 CHANNEL SLOPE = 0.0673

CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 2.009  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.12	0.50	0.986	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.986  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 10.38  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.13  
 AVERAGE FLOW DEPTH (FEET) = 0.82 TRAVEL TIME (MIN.) = 1.41  
 Tc (MIN.) = 8.39  
 SUBAREA AREA (ACRES) = 8.12 SUBAREA RUNOFF (CFS) = 11.08  
 EFFECTIVE AREA (ACRES) = 11.15 AREA-AVERAGED Fm (INCH/HR) = 0.49  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.98  
 TOTAL AREA (ACRES) = 11.1 PEAK FLOW RATE (CFS) = 15.24

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 0.95 FLOW VELOCITY (FEET/SEC.) = 5.64  
 LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13891.00 = 883.22 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13891.00 TO NODE 13892.00 IS CODE = 51

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 392.64 DOWNSTREAM (FEET) = 324.46  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 662.40 CHANNEL SLOPE = 0.1029  
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.749  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	12.50	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 22.29  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.29  
 AVERAGE FLOW DEPTH (FEET) = 1.01 TRAVEL TIME (MIN.) = 1.52  
 Tc (MIN.) = 9.91  
 SUBAREA AREA (ACRES) = 12.50 SUBAREA RUNOFF (CFS) = 14.05  
 EFFECTIVE AREA (ACRES) = 23.65 AREA-AVERAGED Fm (INCH/HR) = 0.50  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA (ACRES) = 23.6 PEAK FLOW RATE (CFS) = 26.69

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 1.08 FLOW VELOCITY (FEET/SEC.) = 7.62  
 LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13892.00 = 1545.62 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13892.00 TO NODE 13893.00 IS CODE = 51

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 324.46 DOWNSTREAM (FEET) = 240.82  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 980.03 CHANNEL SLOPE = 0.0853  
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.552  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	15.87	0.50	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 34.21  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.59  
 AVERAGE FLOW DEPTH (FEET) = 1.23 TRAVEL TIME (MIN.) = 2.15  
 Tc (MIN.) = 12.06  
 SUBAREA AREA (ACRES) = 15.87 SUBAREA RUNOFF (CFS) = 15.02  
 EFFECTIVE AREA (ACRES) = 39.52 AREA-AVERAGED Fm (INCH/HR) = 0.50  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA (ACRES) = 39.5 PEAK FLOW RATE (CFS) = 37.50

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 1.27 FLOW VELOCITY (FEET/SEC.) = 7.74  
 LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13893.00 = 2525.65 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13893.00 TO NODE 13894.00 IS CODE = 51

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 240.82 DOWNSTREAM (FEET) = 163.04  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1144.35 CHANNEL SLOPE = 0.0680  
 CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 20.00  
 \* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 1.330  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	28.41	0.50	0.985	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.50  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.985  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 48.23  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.60  
 AVERAGE FLOW DEPTH (FEET) = 1.45 TRAVEL TIME (MIN.) = 2.51  
 Tc (MIN.) = 14.57  
 SUBAREA AREA (ACRES) = 28.41 SUBAREA RUNOFF (CFS) = 21.42  
 EFFECTIVE AREA (ACRES) = 67.93 AREA-AVERAGED Fm (INCH/HR) = 0.50  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA (ACRES) = 67.9 PEAK FLOW RATE (CFS) = 51.05

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 1.49 FLOW VELOCITY (FEET/SEC.) = 7.66  
 LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13894.00 = 3670.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 31

-----  
 >>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<

>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 163.04 DOWNSTREAM(FEET) = 119.70
FLOW LENGTH(FEET) = 1899.01 MANNING'S N = 0.013
ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000
DEPTH OF FLOW IN 36.0 INCH PIPE IS 18.7 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 13.75
ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 51.05
PIPE TRAVEL TIME(MIN.) = 2.30 Tc(MIN.) = 16.87
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13910.00 = 5569.01 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 16.87
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.222
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 11.69 0.50 0.634 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.634
SUBAREA AREA(ACRES) = 11.69 SUBAREA RUNOFF(CFS) = 9.52
EFFECTIVE AREA(ACRES) = 79.62 AREA-AVERAGED Fm(INCH/HR) = 0.47
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.94
TOTAL AREA(ACRES) = 79.6 PEAK FLOW RATE(CFS) = 53.96

\*\*\*\*\*
FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 16.87
RAINFALL INTENSITY(INCH/HR) = 1.22
AREA-AVERAGED Fm(INCH/HR) = 0.47
AREA-AVERAGED Fp(INCH/HR) = 0.50
AREA-AVERAGED Ap = 0.94
EFFECTIVE STREAM AREA(ACRES) = 79.62
TOTAL STREAM AREA(ACRES) = 79.62
PEAK FLOW RATE(CFS) AT CONFLUENCE = 53.96

\*\* CONFLUENCE DATA \*\*
Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 10 rows of data.

Table with 8 columns: Stream Number, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 25 rows of data.

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 25 rows of data.

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
PEAK FLOW RATE(CFS) = 15404.10 Tc(MIN.) = 38.83
EFFECTIVE AREA(ACRES) = 9721.66 AREA-AVERAGED Fm(INCH/HR) = 0.41
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.83
TOTAL AREA(ACRES) = 69102.3
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13910.00 = 135259.45 FEET.

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 69102.3 TC (MIN.) = 38.83  
 EFFECTIVE AREA (ACRES) = 9721.66 AREA-AVERAGED Fm (INCH/HR) = 0.41  
 AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.829  
 PEAK FLOW RATE (CFS) = 15404.10

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14786.56	16.87	1.222	0.50 ( 0.42)	0.83	3513.6	13889.00
2	14960.85	24.71	0.973	0.50 ( 0.42)	0.83	5110.8	10600.00
3	15053.86	27.34	0.920	0.50 ( 0.42)	0.83	5995.9	13810.00
4	15113.03	29.16	0.885	0.50 ( 0.42)	0.83	6597.4	13850.00
5	15252.40	33.61	0.823	0.50 ( 0.42)	0.83	8052.6	13870.00
6	15404.10	38.83	0.756	0.50 ( 0.41)	0.83	9721.7	50600.00
7	15149.15	45.53	0.696	0.50 ( 0.42)	0.83	12332.0	13830.00
8	14758.56	55.02	0.628	0.50 ( 0.42)	0.84	15906.7	100.00
9	14186.17	63.61	0.584	0.50 ( 0.43)	0.85	19358.2	10100.00
10	13418.42	75.73	0.542	0.50 ( 0.43)	0.87	23871.7	20100.00
11	12495.14	90.73	0.492	0.50 ( 0.44)	0.89	29072.4	11801.00
12	11939.33	102.50	0.468	0.50 ( 0.45)	0.90	33049.5	11500.00
13	11320.40	115.00	0.443	0.50 ( 0.45)	0.91	37730.1	11000.00
14	10697.68	129.12	0.422	0.50 ( 0.46)	0.92	44127.7	13000.00
15	10285.12	138.56	0.411	0.50 ( 0.46)	0.92	48354.6	10900.00
16	9786.08	147.62	0.400	0.50 ( 0.46)	0.93	51815.9	11130.00
17	9025.12	160.00	0.386	0.50 ( 0.47)	0.93	55594.4	11620.00
18	7878.70	177.37	0.365	0.50 ( 0.47)	0.94	60170.9	12400.00
19	6983.78	189.92	0.357	0.50 ( 0.47)	0.94	62488.3	12201.00
20	6340.91	199.99	0.351	0.50 ( 0.47)	0.94	63779.0	12111.00
21	5377.88	217.05	0.342	0.50 ( 0.47)	0.94	65701.9	12261.00
22	4889.14	227.14	0.337	0.50 ( 0.47)	0.94	66513.0	10200.00
23	4291.18	243.65	0.328	0.50 ( 0.47)	0.94	67750.9	10300.00
24	3540.62	272.62	0.312	0.50 ( 0.47)	0.94	68431.5	12000.00
25	2454.55	344.37	0.273	0.50 ( 0.47)	0.94	69102.3	10100.00

=====

END OF RATIONAL METHOD ANALYSIS

\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA 92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S39- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 5-YR RM EV APRIL 2019 ROKAMOTO \*  
\*\*\*\*\*

FILE NAME: RI05EV39.DAT  
TIME/DATE OF STUDY: 17:21 04/08/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 5.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 2.586
- 2) 10.00; 1.731
- 3) 15.00; 1.292
- 4) 20.00; 1.104
- 5) 25.00; 0.965
- 6) 30.00; 0.869
- 7) 40.00; 0.741
- 8) 50.00; 0.658
- 9) 60.00; 0.596
- 10) 90.00; 0.493
- 11) 120.00; 0.433
- 12) 180.00; 0.362
- 13) 360.00; 0.264
- 14) 1200.00; 0.115

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL: IN- / OUT-/PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:

- 1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13900.00 TO NODE 13901.00 IS CODE = 21  
-----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 600.65  
ELEVATION DATA: UPSTREAM(FEET) = 442.40 DOWNSTREAM(FEET) = 385.16

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 10.859  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.656  
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
AGRICULTURAL POOR COVER "FALLOW"	-	4.00	0.50	1.000	0	10.86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA RUNOFF(CFS) = 4.16  
TOTAL AREA(ACRES) = 4.00 PEAK FLOW RATE(CFS) = 4.16

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13901.00 TO NODE 13902.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 385.16 DOWNSTREAM(FEET) = 288.21  
CHANNEL LENGTH THRU SUBAREA(FEET) = 647.42 CHANNEL SLOPE = 0.1497  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.509  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.47	0.50	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 8.01  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.45  
AVERAGE FLOW DEPTH(FEET) = 0.64 TRAVEL TIME(MIN.) = 1.67  
Tc(MIN.) = 12.53  
SUBAREA AREA(ACRES) = 8.47 SUBAREA RUNOFF(CFS) = 7.69  
EFFECTIVE AREA(ACRES) = 12.47 AREA-AVERAGED Fm(INCH/HR) = 0.50  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 12.5 PEAK FLOW RATE(CFS) = 11.32

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.73 FLOW VELOCITY(FEET/SEC.) = 7.09  
LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13902.00 = 1248.07 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13902.00 TO NODE 13903.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 288.21 DOWNSTREAM(FEET) = 184.89
CHANNEL LENGTH THRU SUBAREA(FEET) = 669.27 CHANNEL SLOPE = 0.1544
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 20.00
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.392
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 23.85 0.50 0.982 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.982
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 21.00
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.40
AVERAGE FLOW DEPTH(FEET) = 0.91 TRAVEL TIME(MIN.) = 1.33
Tc(MIN.) = 13.86
SUBAREA AREA(ACRES) = 23.85 SUBAREA RUNOFF(CFS) = 19.34
EFFECTIVE AREA(ACRES) = 36.32 AREA-AVERAGED Fm(INCH/HR) = 0.49
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 36.3 PEAK FLOW RATE(CFS) = 29.35

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.03 FLOW VELOCITY(FEET/SEC.) = 9.14
LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13903.00 = 1917.34 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 13903.00 TO NODE 13904.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 184.89 DOWNSTREAM(FEET) = 155.08
FLOW LENGTH(FEET) = 876.66 MANNING'S N = 0.013
ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000
DEPTH OF FLOW IN 36.0 INCH PIPE IS 12.3 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 13.74
ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 29.35
PIPE TRAVEL TIME(MIN.) = 1.06 Tc(MIN.) = 14.92
LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13904.00 = 2794.00 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 13903.00 TO NODE 13904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 14.92
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.299
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 21.29 0.50 0.996 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.996

SUBAREA AREA(ACRES) = 21.29 SUBAREA RUNOFF(CFS) = 15.34
EFFECTIVE AREA(ACRES) = 57.61 AREA-AVERAGED Fm(INCH/HR) = 0.50
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 57.6 PEAK FLOW RATE(CFS) = 41.63

\*\*\*\*\*
FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 155.08 DOWNSTREAM(FEET) = 118.00
FLOW LENGTH(FEET) = 1961.38 MANNING'S N = 0.013
ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000
DEPTH OF FLOW IN 36.0 INCH PIPE IS 17.5 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 12.17
ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 41.63
PIPE TRAVEL TIME(MIN.) = 2.69 Tc(MIN.) = 17.61
LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13920.00 = 4755.38 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 17.61
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 1.194
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 43.53 0.50 0.649 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.649
SUBAREA AREA(ACRES) = 43.53 SUBAREA RUNOFF(CFS) = 34.06
EFFECTIVE AREA(ACRES) = 101.14 AREA-AVERAGED Fm(INCH/HR) = 0.42
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.84
TOTAL AREA(ACRES) = 101.1 PEAK FLOW RATE(CFS) = 70.25

\*\*\*\*\*
FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<

\*\*\*\*\*
FLOW PROCESS FROM NODE 13910.00 TO NODE 13910.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: RI05EV38.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:
STREAM Q Tc Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (ACRES) NODE
1 14786.56 16.87 0.50( 0.42) 0.83 3513.6 13889.00
2 15404.10 38.83 0.50( 0.41) 0.83 9721.7 50600.00
3 14758.56 55.02 0.50( 0.42) 0.84 15906.7 100.00
4 14186.17 63.61 0.50( 0.43) 0.85 19358.2 10100.00

5	13418.42	75.73	0.50	( 0.43)	0.87	23871.7	20100.00
6	12495.14	90.73	0.50	( 0.44)	0.89	29072.4	11801.00
7	11939.33	102.50	0.50	( 0.45)	0.90	33049.5	11500.00
8	11320.40	115.00	0.50	( 0.45)	0.91	37730.1	11000.00
9	10697.68	129.12	0.50	( 0.46)	0.92	44127.7	13000.00
10	10285.12	138.56	0.50	( 0.46)	0.92	48354.6	10900.00
11	9786.08	147.62	0.50	( 0.46)	0.93	51815.9	11130.00
12	9025.12	160.00	0.50	( 0.47)	0.93	55594.4	11620.00
13	7878.70	177.37	0.50	( 0.47)	0.94	60170.9	12400.00
14	6983.78	189.92	0.50	( 0.47)	0.94	62488.3	12201.00
15	6340.91	199.99	0.50	( 0.47)	0.94	63779.0	12111.00
16	5377.88	217.05	0.50	( 0.47)	0.94	65701.9	12261.00
17	4889.14	227.14	0.50	( 0.47)	0.94	66513.0	10200.00
18	4291.18	243.65	0.50	( 0.47)	0.94	67750.9	10300.00
19	3540.62	272.62	0.50	( 0.47)	0.94	68431.5	12000.00
20	2454.55	344.37	0.50	( 0.47)	0.94	69102.3	10100.00

TOTAL AREA (ACRES) = 69102.3

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13910.00 TO NODE 13910.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<  
=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14786.56	16.87	0.50 ( 0.42)	0.83	3513.6	13889.00
2	15404.10	38.83	0.50 ( 0.41)	0.83	9721.7	50600.00
3	14758.56	55.02	0.50 ( 0.42)	0.84	15906.7	100.00
4	14186.17	63.61	0.50 ( 0.43)	0.85	19358.2	10100.00
5	13418.42	75.73	0.50 ( 0.43)	0.87	23871.7	20100.00
6	12495.14	90.73	0.50 ( 0.44)	0.89	29072.4	11801.00
7	11939.33	102.50	0.50 ( 0.45)	0.90	33049.5	11500.00
8	11320.40	115.00	0.50 ( 0.45)	0.91	37730.1	11000.00
9	10697.68	129.12	0.50 ( 0.46)	0.92	44127.7	13000.00
10	10285.12	138.56	0.50 ( 0.46)	0.92	48354.6	10900.00
11	9786.08	147.62	0.50 ( 0.46)	0.93	51815.9	11130.00
12	9025.12	160.00	0.50 ( 0.47)	0.93	55594.4	11620.00
13	7878.70	177.37	0.50 ( 0.47)	0.94	60170.9	12400.00
14	6983.78	189.92	0.50 ( 0.47)	0.94	62488.3	12201.00
15	6340.91	199.99	0.50 ( 0.47)	0.94	63779.0	12111.00
16	5377.88	217.05	0.50 ( 0.47)	0.94	65701.9	12261.00
17	4889.14	227.14	0.50 ( 0.47)	0.94	66513.0	10200.00
18	4291.18	243.65	0.50 ( 0.47)	0.94	67750.9	10300.00
19	3540.62	272.62	0.50 ( 0.47)	0.94	68431.5	12000.00
20	2454.55	344.37	0.50 ( 0.47)	0.94	69102.3	10100.00

TOTAL AREA (ACRES) = 69102.3

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13910.00 TO NODE 13920.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<  
=====

ELEVATION DATA: UPSTREAM (FEET) = 119.70 DOWNSTREAM (FEET) = 118.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1376.26 CHANNEL SLOPE = 0.0012  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.030 MAXIMUM DEPTH (FEET) = 20.00

==>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL  
CAPACITY ( NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM  
ALLOWABLE DEPTH).  
AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM  
ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

\* 5 YEAR RAINFALL INTENSITY (INCH/HR) = 0.736

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	96.09	0.50	0.535	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.50

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.535

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 15424.35

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 12.85

AVERAGE FLOW DEPTH (FEET) = 20.00 TRAVEL TIME (MIN.) = 1.78

Tc (MIN.) = 40.61

SUBAREA AREA (ACRES) = 96.09 SUBAREA RUNOFF (CFS) = 40.50

EFFECTIVE AREA (ACRES) = 9817.75 AREA-AVERAGED Fm (INCH/HR) = 0.41

AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.83

TOTAL AREA (ACRES) = 69198.4 PEAK FLOW RATE (CFS) = 15404.10

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

==>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL  
CAPACITY ( NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM  
ALLOWABLE DEPTH).  
AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM  
ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 20.00 FLOW VELOCITY (FEET/SEC.) = 12.84

==>FLOWDEPTH EXCEEDS MAXIMUM ALLOWABLE DEPTH

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136635.72 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<  
=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14786.56	18.72	1.152	0.50 ( 0.41)	0.82	3609.7	13889.00
2	15404.10	40.61	0.736	0.50 ( 0.41)	0.83	9817.7	50600.00
3	14758.56	56.89	0.615	0.50 ( 0.42)	0.83	16002.8	100.00
4	14186.17	65.55	0.577	0.50 ( 0.42)	0.85	19454.2	10100.00
5	13418.42	77.78	0.535	0.50 ( 0.43)	0.87	23967.8	20100.00
6	12495.14	92.93	0.487	0.50 ( 0.44)	0.88	29168.5	11801.00
7	11939.33	104.80	0.463	0.50 ( 0.45)	0.89	33145.6	11500.00
8	11320.40	117.43	0.438	0.50 ( 0.45)	0.90	37826.2	11000.00
9	10697.68	131.69	0.419	0.50 ( 0.46)	0.92	44223.8	13000.00
10	10285.12	141.23	0.408	0.50 ( 0.46)	0.92	48450.7	10900.00

11	9786.08	150.43	0.397	0.50( 0.46)	0.93	51912.0	11130.00
12	9025.12	162.97	0.382	0.50( 0.47)	0.93	55690.5	11620.00
13	7878.70	180.44	0.362	0.50( 0.47)	0.94	60266.9	12400.00
14	6983.78	193.08	0.355	0.50( 0.47)	0.94	62584.4	12201.00
15	6340.91	203.23	0.349	0.50( 0.47)	0.94	63875.0	12111.00
16	5377.88	220.42	0.340	0.50( 0.47)	0.94	65797.9	12261.00
17	4889.14	230.60	0.334	0.50( 0.47)	0.94	66609.1	10200.00
18	4291.18	247.22	0.325	0.50( 0.47)	0.94	67847.0	10300.00
19	3540.62	276.37	0.310	0.50( 0.47)	0.94	68527.6	12000.00
20	2454.55	348.48	0.270	0.50( 0.47)	0.94	69198.4	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136635.72 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	70.25	17.61	1.194	0.50( 0.42)	0.84	101.1	13900.00

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13920.00 = 4755.38 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14764.20	17.61	1.194	0.50( 0.41)	0.82	3495.7	13900.00
2	14853.00	18.72	1.152	0.50( 0.41)	0.82	3710.8	13889.00
3	15432.66	40.61	0.736	0.50( 0.41)	0.83	9918.9	50600.00
4	14776.14	56.89	0.615	0.50( 0.42)	0.83	16103.9	100.00
5	14200.27	65.55	0.577	0.50( 0.42)	0.85	19555.4	10100.00
6	13428.70	77.78	0.535	0.50( 0.43)	0.87	24068.9	20100.00
7	12502.07	92.93	0.487	0.50( 0.44)	0.88	29269.6	11801.00
8	11945.91	104.80	0.463	0.50( 0.45)	0.89	33246.7	11500.00
9	11326.63	117.43	0.438	0.50( 0.45)	0.90	37927.4	11000.00
10	10703.64	131.69	0.419	0.50( 0.46)	0.91	44324.9	13000.00
11	10290.91	141.23	0.408	0.50( 0.46)	0.92	48551.8	10900.00
12	9791.72	150.43	0.397	0.50( 0.46)	0.93	52013.1	11130.00
13	9030.55	162.97	0.382	0.50( 0.47)	0.93	55791.7	11620.00
14	7883.85	180.44	0.362	0.50( 0.47)	0.94	60368.1	12400.00
15	6988.82	193.08	0.355	0.50( 0.47)	0.94	62685.6	12201.00
16	6345.88	203.23	0.349	0.50( 0.47)	0.94	63976.2	12111.00
17	5382.71	220.42	0.340	0.50( 0.47)	0.94	65899.1	12261.00
18	4893.89	230.60	0.334	0.50( 0.47)	0.94	66710.2	10200.00
19	4295.81	247.22	0.325	0.50( 0.47)	0.94	67948.1	10300.00
20	3545.02	276.37	0.310	0.50( 0.47)	0.94	68628.7	12000.00
21	2458.39	348.48	0.270	0.50( 0.47)	0.94	69299.5	10100.00

TOTAL AREA (ACRES) = 69299.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 15432.66 Tc(MIN.) = 40.612  
EFFECTIVE AREA(ACRES) = 9918.88 AREA-AVERAGED Fm(INCH/HR) = 0.41  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.82  
TOTAL AREA(ACRES) = 69299.5  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136635.72 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13920.00 TO NODE 13921.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 118.00 DOWNSTREAM(FEET) = 115.28

CHANNEL LENGTH THRU SUBAREA(FEET) = 335.44 CHANNEL SLOPE = 0.0081  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.733  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	134.30	0.50	0.658	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.658  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 15457.09  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 17.91  
AVERAGE FLOW DEPTH(FEET) = 16.96 TRAVEL TIME(MIN.) = 0.31  
Tc(MIN.) = 40.92  
SUBAREA AREA(ACRES) = 134.30 SUBAREA RUNOFF(CFS) = 48.85  
EFFECTIVE AREA(ACRES) = 10053.18 AREA-AVERAGED Fm(INCH/HR) = 0.41  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.82  
TOTAL AREA(ACRES) = 69433.8 PEAK FLOW RATE(CFS) = 15432.66  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 16.95 FLOW VELOCITY(FEET/SEC.) = 17.91  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13921.00 = 136971.16 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13921.00 TO NODE 14010.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 115.28 DOWNSTREAM(FEET) = 100.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1396.08 CHANNEL SLOPE = 0.0109  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 20.00  
\* 5 YEAR RAINFALL INTENSITY(INCH/HR) = 0.724  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	96.27	0.50	0.723	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.50  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.723  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 15448.35  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 20.03  
AVERAGE FLOW DEPTH(FEET) = 16.03 TRAVEL TIME(MIN.) = 1.16  
Tc(MIN.) = 42.09  
SUBAREA AREA(ACRES) = 96.27 SUBAREA RUNOFF(CFS) = 31.37  
EFFECTIVE AREA(ACRES) = 10149.45 AREA-AVERAGED Fm(INCH/HR) = 0.41  
AREA-AVERAGED Fp(INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.82  
TOTAL AREA(ACRES) = 69530.1 PEAK FLOW RATE(CFS) = 15432.66  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 16.02 FLOW VELOCITY(FEET/SEC.) = 20.03  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 14010.00 = 138367.23 FEET.

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 69530.1 TC(MIN.) = 42.09  
EFFECTIVE AREA(ACRES) = 10149.45 AREA-AVERAGED Fm(INCH/HR) = 0.41



AREA-AVERAGED Fp (INCH/HR) = 0.50 AREA-AVERAGED Ap = 0.823

PEAK FLOW RATE (CFS) = 15432.66

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14764.20	19.10	1.138	0.50 ( 0.41)	0.82	3726.3	13900.00
2	14853.00	20.21	1.098	0.50 ( 0.41)	0.82	3941.4	13889.00
3	15432.66	42.09	0.724	0.50 ( 0.41)	0.82	10149.5	50600.00
4	14776.14	58.38	0.606	0.50 ( 0.42)	0.83	16334.5	100.00
5	14200.27	67.05	0.572	0.50 ( 0.42)	0.85	19786.0	10100.00
6	13428.70	79.31	0.530	0.50 ( 0.43)	0.86	24299.5	20100.00
7	12502.07	94.48	0.484	0.50 ( 0.44)	0.88	29500.2	11801.00
8	11945.91	106.37	0.460	0.50 ( 0.45)	0.89	33477.3	11500.00
9	11326.63	119.03	0.435	0.50 ( 0.45)	0.90	38157.9	11000.00
10	10703.64	133.31	0.417	0.50 ( 0.46)	0.91	44555.5	13000.00
11	10290.91	142.86	0.406	0.50 ( 0.46)	0.92	48782.4	10900.00
12	9791.72	152.09	0.395	0.50 ( 0.46)	0.93	52243.7	11130.00
13	9030.55	164.65	0.380	0.50 ( 0.47)	0.93	56022.2	11620.00
14	7883.85	182.19	0.361	0.50 ( 0.47)	0.93	60598.7	12400.00
15	6988.82	194.88	0.354	0.50 ( 0.47)	0.94	62916.1	12201.00
16	6345.88	205.07	0.348	0.50 ( 0.47)	0.94	64206.8	12111.00
17	5382.71	222.34	0.339	0.50 ( 0.47)	0.94	66129.7	12261.00
18	4893.89	232.56	0.333	0.50 ( 0.47)	0.94	66940.8	10200.00
19	4295.81	249.25	0.324	0.50 ( 0.47)	0.94	68178.7	10300.00
20	3545.02	278.50	0.308	0.50 ( 0.47)	0.94	68859.3	12000.00
21	2458.39	350.81	0.269	0.50 ( 0.47)	0.94	69530.1	10100.00

=====  
=====  
END OF RATIONAL METHOD ANALYSIS

\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S19- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 10-YR RM EV APRIL 2019 CCHIUI \*  
\*\*\*\*\*

FILE NAME: RI10EV19.DAT  
TIME/DATE OF STUDY: 10:14 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 10.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 3.927
- 2) 10.00; 2.601
- 3) 15.00; 1.897
- 4) 20.00; 1.624
- 5) 25.00; 1.414
- 6) 30.00; 1.266
- 7) 40.00; 1.086
- 8) 50.00; 0.968
- 9) 60.00; 0.881
- 10) 90.00; 0.734
- 11) 120.00; 0.652
- 12) 180.00; 0.549
- 13) 360.00; 0.408
- 14) 1200.00; 0.180

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL: IN- / OUT-/PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11900.00 TO NODE 11901.00 IS CODE = 21  
-----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 295.79  
ELEVATION DATA: UPSTREAM(FEET) = 2369.48 DOWNSTREAM(FEET) = 2332.92

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 7.203  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 3.343  
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
RESIDENTIAL ".4 DWELLING/ACRE"	-	1.62	0.30	0.999	0	7.20

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999  
SUBAREA RUNOFF(CFS) = 4.44  
TOTAL AREA(ACRES) = 1.62 PEAK FLOW RATE(CFS) = 4.44

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11901.00 TO NODE 11902.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2332.92 DOWNSTREAM(FEET) = 2297.70  
CHANNEL LENGTH THRU SUBAREA(FEET) = 664.26 CHANNEL SLOPE = 0.0530  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.46  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.467  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.35	0.30	0.906	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.906  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 12.81  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 2.95  
AVERAGE FLOW DEPTH(FEET) = 0.40 TRAVEL TIME(MIN.) = 3.75  
Tc(MIN.) = 10.95  
SUBAREA AREA(ACRES) = 8.35 SUBAREA RUNOFF(CFS) = 16.50  
EFFECTIVE AREA(ACRES) = 9.97 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
TOTAL AREA(ACRES) = 10.0 PEAK FLOW RATE(CFS) = 19.66  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.52

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.52 FLOW VELOCITY(FEET/SEC.) = 3.41  
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11902.00 = 960.05 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11902.00 TO NODE 11902.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2297.70 DOWNSTREAM(FEET) = 2263.40  
CHANNEL LENGTH THRU SUBAREA(FEET) = 928.77 CHANNEL SLOPE = 0.0369  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.03  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.931

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	34.48	0.30	0.904	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.904  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 45.86  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.06  
AVERAGE FLOW DEPTH(FEET) = 0.95 TRAVEL TIME(MIN.) = 3.81  
Tc(MIN.) = 14.76

SUBAREA AREA(ACRES) = 34.48 SUBAREA RUNOFF(CFS) = 51.49  
EFFECTIVE AREA(ACRES) = 44.45 AREA-AVERAGED Fm(INCH/HR) = 0.27  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.91  
TOTAL AREA(ACRES) = 44.5 PEAK FLOW RATE(CFS) = 66.34  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.17

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.17 FLOW VELOCITY(FEET/SEC.) = 4.59  
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11902.50 = 1888.82 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11902.50 TO NODE 11903.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2263.40 DOWNSTREAM(FEET) = 2252.14  
CHANNEL LENGTH THRU SUBAREA(FEET) = 895.50 CHANNEL SLOPE = 0.0126  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.81  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.669

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	23.65	0.30	0.958	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.958  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 81.06  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.38  
AVERAGE FLOW DEPTH(FEET) = 1.77 TRAVEL TIME(MIN.) = 4.42

Tc(MIN.) = 19.18  
SUBAREA AREA(ACRES) = 23.65 SUBAREA RUNOFF(CFS) = 29.40  
EFFECTIVE AREA(ACRES) = 68.10 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA(ACRES) = 68.1 PEAK FLOW RATE(CFS) = 85.26  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.82

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.82 FLOW VELOCITY(FEET/SEC.) = 3.43  
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11903.00 = 2784.32 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11903.00 TO NODE 11904.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2252.14 DOWNSTREAM(FEET) = 2186.04  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1924.35 CHANNEL SLOPE = 0.0343  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.73  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.410

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	68.53	0.30	0.961	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.961  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 119.97  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.39  
AVERAGE FLOW DEPTH(FEET) = 1.67 TRAVEL TIME(MIN.) = 5.95  
Tc(MIN.) = 25.13

SUBAREA AREA(ACRES) = 68.53 SUBAREA RUNOFF(CFS) = 69.20  
EFFECTIVE AREA(ACRES) = 136.63 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94  
TOTAL AREA(ACRES) = 136.6 PEAK FLOW RATE(CFS) = 138.62  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.81

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.81 FLOW VELOCITY(FEET/SEC.) = 5.64  
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11904.00 = 4708.67 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11904.00 TO NODE 11905.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2186.04 DOWNSTREAM(FEET) = 1957.34  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1926.87 CHANNEL SLOPE = 0.1187  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.44

\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.306  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 63.15 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 167.24  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 9.16  
 AVERAGE FLOW DEPTH (FEET) = 1.42 TRAVEL TIME (MIN.) = 3.51  
 Tc (MIN.) = 28.64  
 SUBAREA AREA (ACRES) = 63.15 SUBAREA RUNOFF (CFS) = 57.20  
 EFFECTIVE AREA (ACRES) = 199.78 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA (ACRES) = 199.8 PEAK FLOW RATE (CFS) = 183.05  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 1.49  
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 1.49 FLOW VELOCITY (FEET/SEC.) = 9.45  
 LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11905.00 = 6635.54 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11905.00 TO NODE 11906.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 -----

ELEVATION DATA: UPSTREAM (FEET) = 1957.34 DOWNSTREAM (FEET) = 1244.16  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 2498.96 CHANNEL SLOPE = 0.2854  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 1.30

\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.235  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 84.87 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 218.77  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 13.45  
 AVERAGE FLOW DEPTH (FEET) = 1.29 TRAVEL TIME (MIN.) = 3.10  
 Tc (MIN.) = 31.73  
 SUBAREA AREA (ACRES) = 84.87 SUBAREA RUNOFF (CFS) = 71.41  
 EFFECTIVE AREA (ACRES) = 284.65 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97  
 TOTAL AREA (ACRES) = 284.6 PEAK FLOW RATE (CFS) = 241.60  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 1.36

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 1.36 FLOW VELOCITY (FEET/SEC.) = 13.93  
 LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11906.00 = 9134.50 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11906.00 TO NODE 11920.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 -----

ELEVATION DATA: UPSTREAM (FEET) = 1244.16 DOWNSTREAM (FEET) = 873.95  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 3370.75 CHANNEL SLOPE = 0.1098  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 2.10  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.141

SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 199.43 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 317.19  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 10.83  
 AVERAGE FLOW DEPTH (FEET) = 2.07 TRAVEL TIME (MIN.) = 5.19  
 Tc (MIN.) = 36.92  
 SUBAREA AREA (ACRES) = 199.43 SUBAREA RUNOFF (CFS) = 151.04  
 EFFECTIVE AREA (ACRES) = 484.08 AREA-AVERAGED Fm (INCH/HR) = 0.30  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98  
 TOTAL AREA (ACRES) = 484.1 PEAK FLOW RATE (CFS) = 368.73  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 2.25

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 2.25 FLOW VELOCITY (FEET/SEC.) = 11.33  
 LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11920.00 = 12505.25 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11906.00 TO NODE 11920.00 IS CODE = 1  
 -----

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 -----

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
 TIME OF CONCENTRATION (MIN.) = 36.92  
 RAINFALL INTENSITY (INCH/HR) = 1.14  
 AREA-AVERAGED Fm (INCH/HR) = 0.30  
 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.98  
 EFFECTIVE STREAM AREA (ACRES) = 484.08  
 TOTAL STREAM AREA (ACRES) = 484.08  
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 368.73

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11910.00 TO NODE 11911.00 IS CODE = 21  
 -----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<  
 -----

INITIAL SUBAREA FLOW-LENGTH (FEET) = 517.62  
 ELEVATION DATA: UPSTREAM (FEET) = 2531.88 DOWNSTREAM (FEET) = 2441.33

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
 SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 12.185  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.293  
 SUBAREA Tc AND LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)  
 NATURAL FAIR COVER  
 "CHAPARRAL,BROADLEAF" - 3.46 0.30 1.000 0 12.19  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA RUNOFF(CFS) = 6.21  
 TOTAL AREA(ACRES) = 3.46 PEAK FLOW RATE(CFS) = 6.21

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11911.00 TO NODE 11912.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2441.33 DOWNSTREAM(FEET) = 2382.20  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 397.30 CHANNEL SLOPE = 0.1488  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.28  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.047

SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 5.79 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 10.78  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.79  
 AVERAGE FLOW DEPTH(FEET) = 0.27 TRAVEL TIME(MIN.) = 1.75  
 Tc(MIN.) = 13.93  
 SUBAREA AREA(ACRES) = 5.79 SUBAREA RUNOFF(CFS) = 9.11  
 EFFECTIVE AREA(ACRES) = 9.25 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 9.2 PEAK FLOW RATE(CFS) = 14.55  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.32

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 0.32 FLOW VELOCITY(FEET/SEC.) = 4.23  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11912.00 = 914.92 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11912.00 TO NODE 11913.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2382.20 DOWNSTREAM(FEET) = 2263.77  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1891.47 CHANNEL SLOPE = 0.0626  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.93

\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.609  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 54.30 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 46.93  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.91  
 AVERAGE FLOW DEPTH(FEET) = 0.82 TRAVEL TIME(MIN.) = 6.42  
 Tc(MIN.) = 20.35  
 SUBAREA AREA(ACRES) = 54.30 SUBAREA RUNOFF(CFS) = 63.98  
 EFFECTIVE AREA(ACRES) = 63.55 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 63.5 PEAK FLOW RATE(CFS) = 74.88  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.08

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.08 FLOW VELOCITY(FEET/SEC.) = 5.71  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11913.00 = 2806.39 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11913.00 TO NODE 11914.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2263.77 DOWNSTREAM(FEET) = 1845.23  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1957.31 CHANNEL SLOPE = 0.2138  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.96  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.469

SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 65.14 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 109.20  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.76  
 AVERAGE FLOW DEPTH(FEET) = 0.94 TRAVEL TIME(MIN.) = 3.34  
 Tc(MIN.) = 23.70  
 SUBAREA AREA(ACRES) = 65.14 SUBAREA RUNOFF(CFS) = 68.53  
 EFFECTIVE AREA(ACRES) = 128.69 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 128.7 PEAK FLOW RATE(CFS) = 135.38  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.07

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.07 FLOW VELOCITY(FEET/SEC.) = 10.48  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11914.00 = 4763.70 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11914.00 TO NODE 11915.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1845.23 DOWNSTREAM(FEET) = 1557.21
CHANNEL LENGTH THRU SUBAREA(FEET) = 1686.78 CHANNEL SLOPE = 0.1708
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.32
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.373

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 78.52 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 173.32
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.51
AVERAGE FLOW DEPTH(FEET) = 1.31 TRAVEL TIME(MIN.) = 2.68
Tc(MIN.) = 26.37

SUBAREA AREA(ACRES) = 78.52 SUBAREA RUNOFF(CFS) = 75.86
EFFECTIVE AREA(ACRES) = 207.21 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 207.2 PEAK FLOW RATE(CFS) = 200.19
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.42

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.42 FLOW VELOCITY(FEET/SEC.) = 11.02
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11915.00 = 6450.48 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 11915.00 TO NODE 11916.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1557.21 DOWNSTREAM(FEET) = 1403.38
CHANNEL LENGTH THRU SUBAREA(FEET) = 1909.39 CHANNEL SLOPE = 0.0806
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.91
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.267

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 70.48 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 230.87
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.84
AVERAGE FLOW DEPTH(FEET) = 1.89 TRAVEL TIME(MIN.) = 3.60
Tc(MIN.) = 29.97

SUBAREA AREA(ACRES) = 70.48 SUBAREA RUNOFF(CFS) = 61.33
EFFECTIVE AREA(ACRES) = 277.69 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 277.7 PEAK FLOW RATE(CFS) = 241.64
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.94

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.94 FLOW VELOCITY(FEET/SEC.) = 8.97
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11916.00 = 8359.87 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 11916.00 TO NODE 11917.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1403.38 DOWNSTREAM(FEET) = 1079.99
CHANNEL LENGTH THRU SUBAREA(FEET) = 1945.82 CHANNEL SLOPE = 0.1662
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.93
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.221

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 232.20 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 337.88
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.78
AVERAGE FLOW DEPTH(FEET) = 1.91 TRAVEL TIME(MIN.) = 2.54
Tc(MIN.) = 32.51

SUBAREA AREA(ACRES) = 232.20 SUBAREA RUNOFF(CFS) = 192.45
EFFECTIVE AREA(ACRES) = 509.89 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 509.9 PEAK FLOW RATE(CFS) = 422.60
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.16

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 2.16 FLOW VELOCITY(FEET/SEC.) = 13.65
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11917.00 = 10305.69 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 11917.00 TO NODE 11920.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1079.99 DOWNSTREAM(FEET) = 873.95
CHANNEL LENGTH THRU SUBAREA(FEET) = 2563.91 CHANNEL SLOPE = 0.0804
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.77
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.150

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

```

USER-DEFINED          -      110.82      0.30      1.000      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 464.99
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.83
AVERAGE FLOW DEPTH(FEET) = 2.76 TRAVEL TIME(MIN.) = 3.95
Tc(MIN.) = 36.46
SUBAREA AREA(ACRES) = 110.82 SUBAREA RUNOFF(CFS) = 84.76
EFFECTIVE AREA(ACRES) = 620.71 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 620.7 PEAK FLOW RATE(CFS) = 474.77
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.80

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 2.80 FLOW VELOCITY(FEET/SEC.) = 10.89
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11920.00 = 12869.60 FEET.

```

```

*****
FLOW PROCESS FROM NODE 11917.00 TO NODE 11920.00 IS CODE = 1
-----

```

```

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<
=====
TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 36.46
RAINFALL INTENSITY(INCH/HR) = 1.15
AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 1.00
EFFECTIVE STREAM AREA(ACRES) = 620.71
TOTAL STREAM AREA(ACRES) = 620.71
PEAK FLOW RATE(CFS) AT CONFLUENCE = 474.77

```

```

** CONFLUENCE DATA **

```

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	368.73	36.92	1.141	0.30( 0.30)	0.98	484.1	11900.00
2	474.77	36.46	1.150	0.30( 0.30)	1.00	620.7	11910.00

```

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

```

```

** PEAK FLOW RATE TABLE **

```

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	842.46	36.46	1.150	0.30( 0.30)	0.99	1098.7	11910.00
2	838.84	36.92	1.141	0.30( 0.30)	0.99	1104.8	11900.00

```

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
PEAK FLOW RATE(CFS) = 842.46 Tc(MIN.) = 36.46
EFFECTIVE AREA(ACRES) = 1098.72 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 1104.8
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11920.00 = 12869.60 FEET.

```

```

*****
FLOW PROCESS FROM NODE 11920.00 TO NODE 11921.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====

```

```

ELEVATION DATA: UPSTREAM(FEET) = 873.95 DOWNSTREAM(FEET) = 827.94
CHANNEL LENGTH THRU SUBAREA(FEET) = 1417.25 CHANNEL SLOPE = 0.0325
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 4.83
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.104
SUBAREA LOSS RATE DATA(AMC II):

```

```

DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp      Ap      SCS
LAND USE                GROUP  (ACRES)  (INCH/HR)  (DECIMAL)  CN
USER-DEFINED           -      107.47    0.30    1.000    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 881.35
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.29
AVERAGE FLOW DEPTH(FEET) = 4.83 TRAVEL TIME(MIN.) = 2.54
Tc(MIN.) = 39.00
SUBAREA AREA(ACRES) = 107.47 SUBAREA RUNOFF(CFS) = 77.78
EFFECTIVE AREA(ACRES) = 1206.19 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 1212.3 PEAK FLOW RATE(CFS) = 874.98
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 4.81

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 4.81 FLOW VELOCITY(FEET/SEC.) = 9.27
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11921.00 = 14286.85 FEET.

```

```

*****
FLOW PROCESS FROM NODE 11921.00 TO NODE 11922.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====

```

```

ELEVATION DATA: UPSTREAM(FEET) = 827.94 DOWNSTREAM(FEET) = 753.55
CHANNEL LENGTH THRU SUBAREA(FEET) = 1886.43 CHANNEL SLOPE = 0.0394
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 4.90
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.062
SUBAREA LOSS RATE DATA(AMC II):

```

```

DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp      Ap      SCS
LAND USE                GROUP  (ACRES)  (INCH/HR)  (DECIMAL)  CN
USER-DEFINED           -      344.27    0.30    1.000    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 993.03
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.30
AVERAGE FLOW DEPTH(FEET) = 4.88 TRAVEL TIME(MIN.) = 3.05
Tc(MIN.) = 42.05
SUBAREA AREA(ACRES) = 344.27 SUBAREA RUNOFF(CFS) = 236.06
EFFECTIVE AREA(ACRES) = 1550.46 AREA-AVERAGED Fm(INCH/HR) = 0.30

```

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 1556.5 PEAK FLOW RATE(CFS) = 1065.19  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 5.05

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 5.05 FLOW VELOCITY(FEET/SEC.) = 10.48  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11922.00 = 16173.28 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11922.00 TO NODE 11923.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 753.55 DOWNSTREAM(FEET) = 641.58  
CHANNEL LENGTH THRU SUBAREA(FEET) = 2860.88 CHANNEL SLOPE = 0.0391  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 5.19  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.009

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	165.18	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1117.88  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.59  
AVERAGE FLOW DEPTH(FEET) = 5.18 TRAVEL TIME(MIN.) = 4.50  
Tc(MIN.) = 46.55

SUBAREA AREA(ACRES) = 165.18 SUBAREA RUNOFF(CFS) = 105.36  
EFFECTIVE AREA(ACRES) = 1715.64 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 1721.7 PEAK FLOW RATE(CFS) = 1096.41  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 5.13

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 5.13 FLOW VELOCITY(FEET/SEC.) = 10.54  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11923.00 = 19034.16 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11923.00 TO NODE 11924.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 641.58 DOWNSTREAM(FEET) = 579.89  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1844.02 CHANNEL SLOPE = 0.0335  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 5.65  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.973

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	165.18	0.30	1.000	-

LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 433.73 0.30 1.000 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1227.85  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.25  
AVERAGE FLOW DEPTH(FEET) = 5.63 TRAVEL TIME(MIN.) = 3.00  
Tc(MIN.) = 49.55  
SUBAREA AREA(ACRES) = 433.73 SUBAREA RUNOFF(CFS) = 262.85  
EFFECTIVE AREA(ACRES) = 2149.37 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 2155.4 PEAK FLOW RATE(CFS) = 1304.62  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 5.80

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 5.80 FLOW VELOCITY(FEET/SEC.) = 10.41  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11924.00 = 20878.18 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11924.00 TO NODE 11925.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 579.89 DOWNSTREAM(FEET) = 494.12  
CHANNEL LENGTH THRU SUBAREA(FEET) = 2756.15 CHANNEL SLOPE = 0.0311  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.07  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.933

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	265.42	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1380.25  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.29  
AVERAGE FLOW DEPTH(FEET) = 6.06 TRAVEL TIME(MIN.) = 4.46  
Tc(MIN.) = 54.02

SUBAREA AREA(ACRES) = 265.42 SUBAREA RUNOFF(CFS) = 151.24  
EFFECTIVE AREA(ACRES) = 2414.79 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 2420.9 PEAK FLOW RATE(CFS) = 1378.05  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.06

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 6.06 FLOW VELOCITY(FEET/SEC.) = 10.28  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11925.00 = 23634.33 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11925.00 TO NODE 11926.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<



>>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 494.12 DOWNSTREAM(FEET) = 458.40  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1922.70 CHANNEL SLOPE = 0.0186  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.91  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.900  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	97.46	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1404.39  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.54  
AVERAGE FLOW DEPTH(FEET) = 6.91 TRAVEL TIME(MIN.) = 3.75  
Tc(MIN.) = 57.77  
SUBAREA AREA(ACRES) = 97.46 SUBAREA RUNOFF(CFS) = 52.67  
EFFECTIVE AREA(ACRES) = 2512.25 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 2518.3 PEAK FLOW RATE(CFS) = 1378.05  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.85

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 6.85 FLOW VELOCITY(FEET/SEC.) = 8.50  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11926.00 = 25557.03 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11926.00 TO NODE 11927.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 458.40 DOWNSTREAM(FEET) = 399.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 2170.13 CHANNEL SLOPE = 0.0274  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.28  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.874  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	53.83	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1391.95  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.83  
AVERAGE FLOW DEPTH(FEET) = 6.28 TRAVEL TIME(MIN.) = 3.68  
Tc(MIN.) = 61.45  
SUBAREA AREA(ACRES) = 53.83 SUBAREA RUNOFF(CFS) = 27.81  
EFFECTIVE AREA(ACRES) = 2566.08 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 2572.1 PEAK FLOW RATE(CFS) = 1378.05  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.25

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 6.25 FLOW VELOCITY(FEET/SEC.) = 9.81  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 27727.16 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 0610401V.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	638.96	26.17	0.30( 0.30)	1.00	622.1	40120.00
2	630.15	28.05	0.30( 0.30)	1.00	652.1	40100.00
TOTAL AREA(ACRES) =						652.1

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

\*\*\*\*\*  
\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1378.05	61.45	0.874	0.30( 0.30)	1.00	2566.1	11910.00
2	1372.46	61.94	0.872	0.30( 0.30)	1.00	2572.1	11900.00

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 27727.16 FEET.

\*\*\*\*\*  
\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	638.96	26.17	1.379	0.30( 0.30)	1.00	622.1	40120.00
2	630.15	28.05	1.324	0.30( 0.30)	1.00	652.1	40100.00

LONGEST FLOWPATH FROM NODE 40100.00 TO NODE 11927.00 = 10245.00 FEET.

\*\*\*\*\*  
\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1741.93	26.17	1.379	0.30( 0.30)	1.00	1715.0	40120.00
2	1751.40	28.05	1.324	0.30( 0.30)	1.00	1823.3	40100.00
3	1731.30	61.45	0.874	0.30( 0.30)	1.00	3218.1	11910.00
4	1724.23	61.94	0.872	0.30( 0.30)	1.00	3224.2	11900.00
TOTAL AREA(ACRES) =							3224.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:  
PEAK FLOW RATE(CFS) = 1751.40 Tc(MIN.) = 28.046  
EFFECTIVE AREA(ACRES) = 1823.30 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 3224.2  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 27727.16 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 399.00 DOWNSTREAM(FEET) = 384.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 986.26 CHANNEL SLOPE = 0.0152
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
\*ESTIMATED CHANNEL HEIGHT(FEET) = 8.02
CHANNEL FLOW THRU SUBAREA(CFS) = 1751.40
FLOW VELOCITY(FEET/SEC.) = 8.39 FLOW DEPTH(FEET) = 8.02
TRAVEL TIME(MIN.) = 1.96 Tc(MIN.) = 30.00
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.50 = 28713.42 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610402V.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM Q Tc Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 52.53 13.89 0.30(0.30) 1.00 33.3 40200.00
TOTAL AREA(ACRES) = 33.3

\*\*\*\*\*

FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 1741.93 28.13 1.321 0.30(0.30) 1.00 1715.0 40120.00
2 1751.40 30.00 1.266 0.30(0.30) 1.00 1823.3 40100.00
3 1731.30 63.41 0.864 0.30(0.30) 1.00 3218.1 11910.00
4 1724.23 63.90 0.862 0.30(0.30) 1.00 3224.2 11900.00

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.50 = 28713.42 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 52.53 13.89 2.053 0.30(0.30) 1.00 33.3 40200.00

LONGEST FLOWPATH FROM NODE 40200.00 TO NODE 11927.50 = 1999.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 1528.60 13.89 2.053 0.30(0.30) 1.00 880.2 40200.00

2 1772.54 28.13 1.321 0.30(0.30) 1.00 1748.3 40120.00
3 1780.35 30.00 1.266 0.30(0.30) 1.00 1856.6 40100.00
4 1748.21 63.41 0.864 0.30(0.30) 1.00 3251.5 11910.00
5 1741.08 63.90 0.862 0.30(0.30) 1.00 3257.5 11900.00
TOTAL AREA(ACRES) = 3257.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 1780.35 Tc(MIN.) = 30.005
EFFECTIVE AREA(ACRES) = 1856.61 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 3257.5
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.50 = 28713.42 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11927.50 TO NODE 11928.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 384.00 DOWNSTREAM(FEET) = 359.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 647.19 CHANNEL SLOPE = 0.0386
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.56
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.250

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 78.01 0.30 0.984 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.984
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1813.86
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.96
AVERAGE FLOW DEPTH(FEET) = 6.56 TRAVEL TIME(MIN.) = 0.90
Tc(MIN.) = 30.91

SUBAREA AREA(ACRES) = 78.01 SUBAREA RUNOFF(CFS) = 67.02
EFFECTIVE AREA(ACRES) = 1934.62 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 3335.5 PEAK FLOW RATE(CFS) = 1780.35

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.50

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 6.50 FLOW VELOCITY(FEET/SEC.) = 11.92
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11928.00 = 29360.61 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 359.00 DOWNSTREAM(FEET) = 341.63
CHANNEL LENGTH THRU SUBAREA(FEET) = 1322.66 CHANNEL SLOPE = 0.0131
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT (FEET) = 8.36  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.200  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 8.18 0.30 0.890 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.890  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 1783.79  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.98  
 AVERAGE FLOW DEPTH (FEET) = 8.36 TRAVEL TIME (MIN.) = 2.76  
 Tc (MIN.) = 33.67  
 SUBAREA AREA (ACRES) = 8.18 SUBAREA RUNOFF (CFS) = 6.87  
 EFFECTIVE AREA (ACRES) = 1942.80 AREA-AVERAGED Fm (INCH/HR) = 0.30  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA (ACRES) = 3343.7 PEAK FLOW RATE (CFS) = 1780.35  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 8.36

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 8.36 FLOW VELOCITY (FEET/SEC.) = 7.97  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11929.00 = 30683.27 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 10  
 -----  
 >>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 3 <<<<<  
 =====

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11841.00 TO NODE 11527.00 IS CODE = 12  
 -----  
 >>>>CLEAR MEMORY BANK # 1 <<<<<  
 =====

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11841.00 TO NODE 12527.00 IS CODE = 15.1  
 -----  
 >>>>DEFINE MEMORY BANK # 1 <<<<<  
 =====

PEAK FLOWRATE TABLE FILE NAME: S18X10.DNA  
 MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11616.90	44.00	0.30 ( 0.30)	1.00	7599.6	11801.00
2	12892.03	58.27	0.30 ( 0.30)	1.00	10804.1	11530.00
3	13438.67	64.50	0.30 ( 0.30)	1.00	12758.4	11701.00
4	13628.71	66.49	0.30 ( 0.30)	1.00	13434.8	11000.00
5	15265.02	77.21	0.30 ( 0.30)	1.00	18437.6	11330.00
6	15528.32	79.96	0.30 ( 0.30)	1.00	19719.4	10800.00
7	15902.78	82.44	0.30 ( 0.30)	1.00	21039.3	11300.00
8	16140.10	85.75	0.30 ( 0.30)	1.00	22434.4	10630.00
9	15918.65	96.09	0.30 ( 0.30)	1.00	25763.3	11620.00
10	15868.02	97.88	0.30 ( 0.30)	1.00	26303.3	11600.00
11	15636.46	103.56	0.30 ( 0.30)	1.00	27777.9	11111.00
12	15531.21	106.40	0.30 ( 0.30)	1.00	28370.9	10500.00

13	15352.00	110.70	0.30 ( 0.30)	1.00	29161.8	10710.00
14	15201.33	113.32	0.30 ( 0.30)	1.00	29547.2	10410.00
15	14857.39	118.86	0.30 ( 0.30)	1.00	30260.6	10700.00
16	14446.26	125.40	0.30 ( 0.30)	1.00	31040.6	10400.00
17	14178.55	129.18	0.30 ( 0.30)	1.00	31414.4	10200.00
18	13775.63	136.31	0.30 ( 0.30)	1.00	32035.9	10320.00
19	13411.70	140.89	0.30 ( 0.30)	1.00	32196.8	10210.00
20	11422.66	173.20	0.30 ( 0.30)	1.00	32916.6	10100.00
TOTAL AREA (ACRES) =						32916.6

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 12  
 -----  
 >>>>CLEAR MEMORY BANK # 2 <<<<<  
 =====

\*\*\*MEMORY BANK # 2 IS EMPTY - PROCESS IGNORED.\*\*\*  
 \*\*\*\*\*

FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 15.1  
 -----  
 >>>>DEFINE MEMORY BANK # 2 <<<<<  
 =====

PEAK FLOWRATE TABLE FILE NAME: S25X10.DNA  
 MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4457.80	74.17	0.30 ( 0.30)	0.99	6215.9	12500.00
2	4830.00	89.61	0.30 ( 0.30)	0.99	8185.8	12300.00
3	4886.59	91.31	0.30 ( 0.30)	0.99	8494.7	12330.00
4	4976.75	94.56	0.30 ( 0.30)	0.98	9045.8	12410.00
5	5066.75	99.26	0.30 ( 0.29)	0.98	9767.7	12400.00
6	5124.87	104.67	0.30 ( 0.29)	0.98	10457.3	12211.00
7	5154.35	109.58	0.30 ( 0.29)	0.98	11071.5	12201.00
8	5066.62	114.70	0.30 ( 0.29)	0.98	11560.6	12111.00
9	5049.30	118.21	0.30 ( 0.29)	0.98	11939.4	12231.00
10	5009.12	121.09	0.30 ( 0.29)	0.98	12207.1	12101.10
11	4983.48	122.44	0.30 ( 0.29)	0.98	12317.7	12261.00
12	4583.59	136.43	0.30 ( 0.29)	0.98	13120.1	12010.00
13	4254.50	145.50	0.30 ( 0.29)	0.98	13237.1	12000.00
TOTAL AREA (ACRES) =						13237.1

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 14.0  
 -----  
 >>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<  
 =====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4457.80	74.17	0.30 ( 0.30)	0.99	6215.9	12500.00
2	4830.00	89.61	0.30 ( 0.30)	0.99	8185.8	12300.00
3	4886.59	91.31	0.30 ( 0.30)	0.99	8494.7	12330.00
4	4976.75	94.56	0.30 ( 0.30)	0.98	9045.8	12410.00
5	5066.75	99.26	0.30 ( 0.29)	0.98	9767.7	12400.00
6	5124.87	104.67	0.30 ( 0.29)	0.98	10457.3	12211.00
7	5154.35	109.58	0.30 ( 0.29)	0.98	11071.5	12201.00
8	5066.62	114.70	0.30 ( 0.29)	0.98	11560.6	12111.00

9	5049.30	118.21	0.30	( 0.29)	0.98	11939.4	12231.00
10	5009.12	121.09	0.30	( 0.29)	0.98	12207.1	12101.10
11	4983.48	122.44	0.30	( 0.29)	0.98	12317.7	12261.00
12	4583.59	136.43	0.30	( 0.29)	0.98	13120.1	12010.00
13	4254.50	145.50	0.30	( 0.29)	0.98	13237.1	12000.00

TOTAL AREA (ACRES) = 13237.1

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11841.00 TO NODE 12527.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4457.80	74.17	0.812	0.30( 0.30)	0.99	6215.9	12500.00
2	4830.00	89.61	0.736	0.30( 0.30)	0.99	8185.8	12300.00
3	4886.59	91.31	0.730	0.30( 0.30)	0.99	8494.7	12330.00
4	4976.75	94.56	0.722	0.30( 0.30)	0.98	9045.8	12410.00
5	5066.75	99.26	0.709	0.30( 0.29)	0.98	9767.7	12400.00
6	5124.87	104.67	0.694	0.30( 0.29)	0.98	10457.3	12211.00
7	5154.35	109.58	0.680	0.30( 0.29)	0.98	11071.5	12201.00
8	5066.62	114.70	0.666	0.30( 0.29)	0.98	11560.6	12111.00
9	5049.30	118.21	0.657	0.30( 0.29)	0.98	11939.4	12231.00
10	5009.12	121.09	0.650	0.30( 0.29)	0.98	12207.1	12101.10
11	4983.48	122.44	0.648	0.30( 0.29)	0.98	12317.7	12261.00
12	4583.59	136.43	0.624	0.30( 0.29)	0.98	13120.1	12010.00
13	4254.50	145.50	0.608	0.30( 0.29)	0.98	13237.1	12000.00

LONGEST FLOWPATH FROM NODE 12000.00 TO NODE 12527.00 = 77156.98 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	11616.90	44.00	1.039	0.30( 0.30)	1.00	7599.6	11801.00
2	12892.03	58.27	0.896	0.30( 0.30)	1.00	10804.1	11530.00
3	13438.67	64.50	0.859	0.30( 0.30)	1.00	12758.4	11701.00
4	13628.71	66.49	0.849	0.30( 0.30)	1.00	13434.8	11000.00
5	15265.02	77.21	0.797	0.30( 0.30)	1.00	18437.6	11330.00
6	15528.32	79.96	0.783	0.30( 0.30)	1.00	19719.4	10800.00
7	15902.78	82.44	0.771	0.30( 0.30)	1.00	21039.3	11300.00
8	16140.10	85.75	0.755	0.30( 0.30)	1.00	22434.4	10630.00
9	15918.65	96.09	0.717	0.30( 0.30)	1.00	25763.3	11620.00
10	15868.02	97.88	0.712	0.30( 0.30)	1.00	26303.3	11600.00
11	15636.46	103.56	0.697	0.30( 0.30)	1.00	27777.9	11111.00
12	15531.21	106.40	0.689	0.30( 0.30)	1.00	28370.9	10500.00
13	15352.00	110.70	0.677	0.30( 0.30)	1.00	29161.8	10710.00
14	15201.33	113.32	0.670	0.30( 0.30)	1.00	29547.2	10410.00
15	14857.39	118.86	0.655	0.30( 0.30)	1.00	30260.6	10700.00
16	14446.26	125.40	0.643	0.30( 0.30)	1.00	31040.6	10400.00
17	14178.55	129.18	0.636	0.30( 0.30)	1.00	31414.4	10200.00
18	13775.63	136.31	0.624	0.30( 0.30)	1.00	32035.9	10320.00
19	13411.70	140.89	0.616	0.30( 0.30)	1.00	32196.8	10210.00
20	11422.66	173.20	0.561	0.30( 0.30)	1.00	32916.6	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12527.00 = 97868.13 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	--------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE	
1	15427.07	44.00	1.039	0.30( 0.30)	0.99	11287.3	11801.00
2	16968.09	58.27	0.896	0.30( 0.30)	0.99	15687.3	11530.00
3	17671.53	64.50	0.859	0.30( 0.30)	0.99	18163.7	11701.00
4	17916.64	66.49	0.849	0.30( 0.30)	0.99	19007.1	11000.00
5	19259.36	74.17	0.812	0.30( 0.30)	0.99	23236.5	12500.00
6	19795.97	77.21	0.797	0.30( 0.30)	0.99	25040.6	11330.00
7	20125.68	79.96	0.783	0.30( 0.30)	0.99	26674.0	10800.00
8	20559.80	82.44	0.771	0.30( 0.30)	0.99	28309.7	11300.00
9	20877.05	85.75	0.755	0.30( 0.30)	0.99	30127.8	10630.00
10	20887.39	89.61	0.736	0.30( 0.30)	0.99	31863.6	12300.00
11	20907.71	91.31	0.730	0.30( 0.30)	0.99	32717.7	12330.00
12	20928.11	94.56	0.722	0.30( 0.30)	0.99	34317.4	12410.00
13	20924.67	96.09	0.717	0.30( 0.30)	0.99	35043.8	11620.00
14	20908.49	97.88	0.712	0.30( 0.30)	0.99	35860.1	11600.00
15	20878.88	99.26	0.709	0.30( 0.30)	0.99	36427.0	12400.00
16	20749.46	103.56	0.697	0.30( 0.30)	0.99	38094.4	11111.00
17	20720.29	104.67	0.694	0.30( 0.30)	0.99	38466.4	12211.00
18	20666.45	106.40	0.689	0.30( 0.30)	0.99	39044.4	10500.00
19	20552.81	109.58	0.680	0.30( 0.30)	0.99	40028.3	12201.00
20	20487.24	110.70	0.677	0.30( 0.30)	0.99	40339.9	10710.00
21	20291.57	113.32	0.670	0.30( 0.30)	0.99	40976.1	10410.00
22	20182.47	114.70	0.666	0.30( 0.30)	0.99	41285.1	12111.00
23	19946.92	118.21	0.657	0.30( 0.30)	0.99	42116.5	12231.00
24	19897.64	118.86	0.655	0.30( 0.30)	0.99	42260.3	10700.00
25	19726.52	121.09	0.650	0.30( 0.30)	0.99	42733.2	12101.10
26	19615.75	122.44	0.648	0.30( 0.30)	0.99	43005.4	12261.00
27	19345.12	125.40	0.643	0.30( 0.30)	0.99	43528.1	10400.00
28	18969.58	129.18	0.636	0.30( 0.30)	0.99	44118.3	10200.00
29	18362.79	136.31	0.624	0.30( 0.30)	0.99	45148.8	10320.00
30	18349.32	136.43	0.624	0.30( 0.30)	0.99	45160.4	12010.00
31	17833.67	140.89	0.616	0.30( 0.30)	0.99	45374.3	10210.00
32	17382.11	145.50	0.608	0.30( 0.30)	0.99	45536.7	12000.00
33	15034.06	173.20	0.561	0.30( 0.30)	0.99	46153.7	10100.00

TOTAL AREA (ACRES) = 46153.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 20928.11 Tc(MIN.) = 94.562  
 EFFECTIVE AREA(ACRES) = 34317.40 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 46153.7  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12527.00 = 97868.13 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12527.00 TO NODE 11929.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 347.47 DOWNSTREAM(FEET) = 341.63  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 532.38 CHANNEL SLOPE = 0.0110  
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 6.93  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.720  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ LAND USE SCS SOIL GROUP AREA (ACRES) Fp (INCH/HR) Ap (DECIMAL) SCS CN

USER-DEFINED - 14.37 0.30 0.987 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.987  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 20930.85  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.87  
 AVERAGE FLOW DEPTH(FEET) = 6.93 TRAVEL TIME(MIN.) = 0.69  
 Tc(MIN.) = 95.25  
 SUBAREA AREA(ACRES) = 14.37 SUBAREA RUNOFF(CFS) = 5.48  
 EFFECTIVE AREA(ACRES) = 34331.77 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 46168.0 PEAK FLOW RATE(CFS) = 20928.11  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 6.93

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 6.93 FLOW VELOCITY(FEET/SEC.) = 12.87  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<<  
 =====

**\*\* MAIN STREAM CONFLUENCE DATA \*\***

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15427.07	44.77	1.030	0.30( 0.30)	0.99	11301.7	11801.00
2	16968.09	59.01	0.890	0.30( 0.30)	0.99	15701.7	11530.00
3	17671.53	65.23	0.855	0.30( 0.30)	0.99	18178.1	11701.00
4	17916.64	67.22	0.846	0.30( 0.30)	0.99	19021.5	11000.00
5	19259.36	74.88	0.808	0.30( 0.30)	0.99	23250.9	12500.00
6	19795.97	77.91	0.793	0.30( 0.30)	0.99	25055.0	11330.00
7	20125.68	80.66	0.780	0.30( 0.30)	0.99	26688.3	10800.00
8	20559.80	83.13	0.768	0.30( 0.30)	0.99	28324.0	11300.00
9	20877.05	86.44	0.751	0.30( 0.30)	0.99	30142.2	10630.00
10	20887.39	90.30	0.733	0.30( 0.30)	0.99	31878.0	12300.00
11	20907.71	92.00	0.729	0.30( 0.30)	0.99	32732.0	12330.00
12	20928.11	95.25	0.720	0.30( 0.30)	0.99	34331.8	12410.00
13	20924.67	96.78	0.715	0.30( 0.30)	0.99	35058.2	11620.00
14	20908.49	98.57	0.711	0.30( 0.30)	0.99	35874.5	11600.00
15	20878.88	99.95	0.707	0.30( 0.30)	0.99	36441.4	12400.00
16	20749.46	104.26	0.695	0.30( 0.30)	0.99	38108.8	11111.00
17	20720.29	105.36	0.692	0.30( 0.30)	0.99	38480.8	12211.00
18	20666.45	107.09	0.687	0.30( 0.30)	0.99	39058.8	10500.00
19	20552.81	110.28	0.679	0.30( 0.30)	0.99	40042.7	12201.00
20	20487.24	111.39	0.676	0.30( 0.30)	0.99	40354.2	10710.00
21	20291.57	114.02	0.668	0.30( 0.30)	0.99	40990.5	10410.00
22	20182.47	115.39	0.665	0.30( 0.30)	0.99	41299.5	12111.00
23	19946.92	118.91	0.655	0.30( 0.30)	0.99	42130.9	12231.00
24	19897.64	119.56	0.653	0.30( 0.30)	0.99	42274.7	10700.00
25	19726.52	121.79	0.649	0.30( 0.30)	0.99	42747.6	12101.10
26	19615.75	123.15	0.647	0.30( 0.30)	0.99	43019.8	12261.00
27	19345.12	126.11	0.642	0.30( 0.30)	0.99	43542.5	10400.00
28	18969.58	129.89	0.635	0.30( 0.30)	0.99	44132.7	10200.00
29	18362.79	137.03	0.623	0.30( 0.30)	0.99	45163.2	10320.00

30	18349.32	137.15	0.623	0.30( 0.30)	0.99	45174.8	12010.00
31	17833.67	141.62	0.615	0.30( 0.30)	0.99	45388.7	10210.00
32	17382.11	146.24	0.607	0.30( 0.30)	0.99	45551.1	12000.00
33	15034.06	173.97	0.559	0.30( 0.30)	0.99	46168.0	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

**\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\***

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1528.60	17.70	1.750	0.30( 0.30)	1.00	966.4	40200.00
2	1772.54	31.80	1.234	0.30( 0.30)	1.00	1834.5	40120.00
3	1780.35	33.67	1.200	0.30( 0.30)	1.00	1942.8	40100.00
4	1748.21	67.10	0.846	0.30( 0.30)	1.00	3337.6	11910.00
5	1741.08	67.59	0.844	0.30( 0.30)	1.00	3343.7	11900.00

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11929.00 = 30683.27 FEET.

**\*\* PEAK FLOW RATE TABLE \*\***

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13624.96	17.70	1.750	0.30( 0.30)	0.99	5433.8	40200.00
2	15782.55	31.80	1.234	0.30( 0.30)	0.99	9862.4	40120.00
3	16080.51	33.67	1.200	0.30( 0.30)	0.99	10442.4	40100.00
4	17196.75	44.77	1.030	0.30( 0.30)	0.99	13707.6	11801.00
5	18724.08	59.01	0.890	0.30( 0.30)	0.99	18702.0	11530.00
6	19421.54	65.23	0.855	0.30( 0.30)	0.99	21437.9	11701.00
7	19649.59	67.10	0.846	0.30( 0.30)	0.99	22306.7	11910.00
8	19663.07	67.22	0.846	0.30( 0.30)	0.99	22360.7	11000.00
9	19722.76	67.59	0.844	0.30( 0.30)	0.99	22570.1	11900.00
10	20886.26	74.88	0.808	0.30( 0.30)	0.99	26594.6	12500.00
11	21375.44	77.91	0.793	0.30( 0.30)	0.99	28398.7	11330.00
12	21662.07	80.66	0.780	0.30( 0.30)	0.99	30032.1	10800.00
13	22057.50	83.13	0.768	0.30( 0.30)	0.99	31667.7	11300.00
14	22322.88	86.44	0.751	0.30( 0.30)	0.99	33485.9	10630.00
15	22274.87	90.30	0.733	0.30( 0.30)	0.99	35221.7	12300.00
16	22280.41	92.00	0.729	0.30( 0.30)	0.99	36075.8	12330.00
17	22272.36	95.25	0.720	0.30( 0.30)	0.99	37675.5	12410.00
18	22255.59	96.78	0.715	0.30( 0.30)	0.99	38401.9	11620.00
19	22223.72	98.57	0.711	0.30( 0.30)	0.99	39218.2	11600.00
20	22182.12	99.95	0.707	0.30( 0.30)	0.99	39785.1	12400.00
21	22015.07	104.26	0.695	0.30( 0.30)	0.99	41452.5	11111.00
22	21976.24	105.36	0.692	0.30( 0.30)	0.99	41824.5	12211.00
23	21907.28	107.09	0.687	0.30( 0.30)	0.99	42402.5	10500.00
24	21765.82	110.28	0.679	0.30( 0.30)	0.99	43386.4	12201.00
25	21690.52	111.39	0.676	0.30( 0.30)	0.99	43697.9	10710.00
26	21471.91	114.02	0.668	0.30( 0.30)	0.99	44334.2	10410.00
27	21350.76	115.39	0.665	0.30( 0.30)	0.99	44643.2	12111.00
28	21084.46	118.91	0.655	0.30( 0.30)	0.99	45474.6	12231.00
29	21029.52	119.56	0.653	0.30( 0.30)	0.99	45618.4	10700.00
30	20844.74	121.79	0.649	0.30( 0.30)	0.99	46091.3	12101.10
31	20726.53	123.15	0.647	0.30( 0.30)	0.99	46363.5	12261.00
32	20439.63	126.11	0.642	0.30( 0.30)	0.99	46886.2	10400.00
33	20043.38	129.89	0.635	0.30( 0.30)	0.99	47476.4	10200.00
34	19397.42	137.03	0.623	0.30( 0.30)	0.99	48506.9	10320.00
35	19383.26	137.15	0.623	0.30( 0.30)	0.99	48518.5	12010.00
36	18843.14	141.62	0.615	0.30( 0.30)	0.99	48732.4	10210.00
37	18366.22	146.24	0.607	0.30( 0.30)	0.99	48894.8	12000.00
38	15866.02	173.97	0.559	0.30( 0.30)	0.99	49511.8	10100.00

TOTAL AREA(ACRES) = 49511.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 22322.88 Tc(MIN.) = 86.444  
 EFFECTIVE AREA(ACRES) = 33485.89 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 49511.8  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

=====  
 END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 49511.8 TC(MIN.) = 86.44  
 EFFECTIVE AREA(ACRES) = 33485.89 AREA-AVERAGED Fm(INCH/HR)= 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.994  
 PEAK FLOW RATE(CFS) = 22322.88

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13624.96	17.70	1.750	0.30( 0.30)	0.99	5433.8	40200.00
2	15782.55	31.80	1.234	0.30( 0.30)	0.99	9862.4	40120.00
3	16080.51	33.67	1.200	0.30( 0.30)	0.99	10442.4	40100.00
4	17196.75	44.77	1.030	0.30( 0.30)	0.99	13707.6	11801.00
5	18724.08	59.01	0.890	0.30( 0.30)	0.99	18702.0	11530.00
6	19421.54	65.23	0.855	0.30( 0.30)	0.99	21437.9	11701.00
7	19649.59	67.10	0.846	0.30( 0.30)	0.99	22306.7	11910.00
8	19663.07	67.22	0.846	0.30( 0.30)	0.99	22360.7	11000.00
9	19722.76	67.59	0.844	0.30( 0.30)	0.99	22570.1	11900.00
10	20886.26	74.88	0.808	0.30( 0.30)	0.99	26594.6	12500.00
11	21375.44	77.91	0.793	0.30( 0.30)	0.99	28398.7	11330.00
12	21662.07	80.66	0.780	0.30( 0.30)	0.99	30032.1	10800.00
13	22057.50	83.13	0.768	0.30( 0.30)	0.99	31667.7	11300.00
14	22322.88	86.44	0.751	0.30( 0.30)	0.99	33485.9	10630.00
15	22274.87	90.30	0.733	0.30( 0.30)	0.99	35221.7	12300.00
16	22280.41	92.00	0.729	0.30( 0.30)	0.99	36075.8	12330.00
17	22272.36	95.25	0.720	0.30( 0.30)	0.99	37675.5	12410.00
18	22255.59	96.78	0.715	0.30( 0.30)	0.99	38401.9	11620.00
19	22223.72	98.57	0.711	0.30( 0.30)	0.99	39218.2	11600.00
20	22182.12	99.95	0.707	0.30( 0.30)	0.99	39785.1	12400.00
21	22015.07	104.26	0.695	0.30( 0.30)	0.99	41452.5	11111.00
22	21976.24	105.36	0.692	0.30( 0.30)	0.99	41824.5	12211.00
23	21907.28	107.09	0.687	0.30( 0.30)	0.99	42402.5	10500.00
24	21765.82	110.28	0.679	0.30( 0.30)	0.99	43386.4	12201.00
25	21690.52	111.39	0.676	0.30( 0.30)	0.99	43697.9	10710.00
26	21471.91	114.02	0.668	0.30( 0.30)	0.99	44334.2	10410.00
27	21350.76	115.39	0.665	0.30( 0.30)	0.99	44643.2	12111.00
28	21084.46	118.91	0.655	0.30( 0.30)	0.99	45474.6	12231.00
29	21029.52	119.56	0.653	0.30( 0.30)	0.99	45618.4	10700.00
30	20844.74	121.79	0.649	0.30( 0.30)	0.99	46091.3	12101.10
31	20726.53	123.15	0.647	0.30( 0.30)	0.99	46363.5	12261.00
32	20439.63	126.11	0.642	0.30( 0.30)	0.99	46886.2	10400.00
33	20043.38	129.89	0.635	0.30( 0.30)	0.99	47476.4	10200.00
34	19397.42	137.03	0.623	0.30( 0.30)	0.99	48506.9	10320.00
35	19383.26	137.15	0.623	0.30( 0.30)	0.99	48518.5	12010.00
36	18843.14	141.62	0.615	0.30( 0.30)	0.99	48732.4	10210.00
37	18366.22	146.24	0.607	0.30( 0.30)	0.99	48894.8	12000.00
38	15866.02	173.97	0.559	0.30( 0.30)	0.99	49511.8	10100.00

=====  
 END OF RATIONAL METHOD ANALYSIS



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S26- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 10-YR RM EV APRIL 2019 CCHIUI \*  
\*\*\*\*\*

FILE NAME: RI10EV26.DAT  
TIME/DATE OF STUDY: 10:14 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 10.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 3.913
- 2) 10.00; 2.593
- 3) 15.00; 1.893
- 4) 20.00; 1.621
- 5) 25.00; 1.412
- 6) 30.00; 1.265
- 7) 40.00; 1.084
- 8) 50.00; 0.966
- 9) 60.00; 0.879
- 10) 90.00; 0.733
- 11) 120.00; 0.650
- 12) 180.00; 0.547
- 13) 360.00; 0.406
- 14) 1200.00; 0.179

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*  
HALF- CROWN TO STREET-CROSSFALL: CURB GUTTER-GEOMETRIES: MANNING  
WIDTH CROSSFALL IN- / OUT-/PARK- HEIGHT WIDTH LIP HIKE FACTOR  
NO. (FT) (FT) SIDE / SIDE/ WAY (FT) (FT) (FT) (FT) (n)  
==== =====  
1 30.0 20.0 0.018/0.018/0.020 0.67 2.00 0.0313 0.167 0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI10EV19.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13624.96	17.70	0.30 ( 0.30)	0.99	5433.8	40200.00
2	16080.51	33.67	0.30 ( 0.30)	0.99	10442.4	40100.00
3	17196.75	44.77	0.30 ( 0.30)	0.99	13707.6	11801.00
4	18724.08	59.01	0.30 ( 0.30)	0.99	18702.0	11530.00
5	19722.76	67.59	0.30 ( 0.30)	0.99	22570.1	11900.00
6	21375.44	77.91	0.30 ( 0.30)	0.99	28398.7	11330.00
7	22322.88	86.44	0.30 ( 0.30)	0.99	33485.9	10630.00
8	22280.41	92.00	0.30 ( 0.30)	0.99	36075.8	12330.00
9	22272.36	95.25	0.30 ( 0.30)	0.99	37675.5	12410.00
10	22223.72	98.57	0.30 ( 0.30)	0.99	39218.2	11600.00
11	22015.07	104.26	0.30 ( 0.30)	0.99	41452.5	11111.00
12	21765.82	110.28	0.30 ( 0.30)	0.99	43386.4	12201.00
13	21471.91	114.02	0.30 ( 0.30)	0.99	44334.2	10410.00
14	21084.46	118.91	0.30 ( 0.30)	0.99	45474.6	12231.00
15	20439.63	126.11	0.30 ( 0.30)	0.99	46886.2	10400.00
16	20043.38	129.89	0.30 ( 0.30)	0.99	47476.4	10200.00
17	19397.42	137.03	0.30 ( 0.30)	0.99	48506.9	10320.00
18	18843.14	141.62	0.30 ( 0.30)	0.99	48732.4	10210.00
19	18366.22	146.24	0.30 ( 0.30)	0.99	48894.8	12000.00
20	15866.02	173.97	0.30 ( 0.30)	0.99	49511.8	10100.00
TOTAL AREA (ACRES) =						49511.8

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13624.96	17.70	0.30 ( 0.30)	0.99	5433.8	40200.00
2	16080.51	33.67	0.30 ( 0.30)	0.99	10442.4	40100.00
3	17196.75	44.77	0.30 ( 0.30)	0.99	13707.6	11801.00
4	18724.08	59.01	0.30 ( 0.30)	0.99	18702.0	11530.00
5	19722.76	67.59	0.30 ( 0.30)	0.99	22570.1	11900.00
6	21375.44	77.91	0.30 ( 0.30)	0.99	28398.7	11330.00
7	22322.88	86.44	0.30 ( 0.30)	0.99	33485.9	10630.00
8	22280.41	92.00	0.30 ( 0.30)	0.99	36075.8	12330.00
9	22272.36	95.25	0.30 ( 0.30)	0.99	37675.5	12410.00
10	22223.72	98.57	0.30 ( 0.30)	0.99	39218.2	11600.00
11	22015.07	104.26	0.30 ( 0.30)	0.99	41452.5	11111.00
12	21765.82	110.28	0.30 ( 0.30)	0.99	43386.4	12201.00
13	21471.91	114.02	0.30 ( 0.30)	0.99	44334.2	10410.00



14	21084.46	118.91	0.30	( 0.30)	0.99	45474.6	12231.00
15	20439.63	126.11	0.30	( 0.30)	0.99	46886.2	10400.00
16	20043.38	129.89	0.30	( 0.30)	0.99	47476.4	10200.00
17	19397.42	137.03	0.30	( 0.30)	0.99	48506.9	10320.00
18	18843.14	141.62	0.30	( 0.30)	0.99	48732.4	10210.00
19	18366.22	146.24	0.30	( 0.30)	0.99	48894.8	12000.00
20	15866.02	173.97	0.30	( 0.30)	0.99	49511.8	10100.00

TOTAL AREA (ACRES) = 49511.8

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 1 <<<<<<  
=====

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11929.00 TO NODE 12601.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<<  
=====

ELEVATION DATA: UPSTREAM (FEET) = 341.63 DOWNSTREAM (FEET) = 325.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1467.93 CHANNEL SLOPE = 0.0113  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT (FEET) = 6.04

\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.743

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	14.11	0.30	0.700	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.700

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 22326.27

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 16.06

AVERAGE FLOW DEPTH (FEET) = 6.04 TRAVEL TIME (MIN.) = 1.52

Tc (MIN.) = 87.97

SUBAREA AREA (ACRES) = 14.11 SUBAREA RUNOFF (CFS) = 6.77

EFFECTIVE AREA (ACRES) = 33500.00 AREA-AVERAGED Fm (INCH/HR) = 0.30

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA (ACRES) = 49525.9 PEAK FLOW RATE (CFS) = 22322.88

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT (FEET) = 6.04

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 6.04 FLOW VELOCITY (FEET/SEC.) = 16.06

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 2 <<<<<<  
=====

PEAK FLOWRATE TABLE FILE NAME: 3010EVRL.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM	Q	Tc	Fp (Fm)	Ap	Ae	HEADWATER
--------	---	----	---------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(ACRES)	NODE
1	64.13	17.31	0.30 ( 0.30)	0.98	48.4 600.00
TOTAL AREA (ACRES) =			48.4		

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<<  
=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13624.96	19.51	1.648	0.30 ( 0.30)	0.99	5447.9	40200.00
2	16080.51	35.38	1.168	0.30 ( 0.30)	0.99	10456.5	40100.00
3	17196.75	46.44	1.008	0.30 ( 0.30)	0.99	13721.8	11801.00
4	18724.08	60.63	0.876	0.30 ( 0.30)	0.99	18716.1	11530.00
5	19722.76	69.18	0.834	0.30 ( 0.30)	0.99	22584.2	11900.00
6	21375.44	79.46	0.784	0.30 ( 0.30)	0.99	28412.8	11330.00
7	22322.88	87.97	0.743	0.30 ( 0.30)	0.99	33500.0	10630.00
8	22280.41	93.52	0.723	0.30 ( 0.30)	0.99	36089.9	12330.00
9	22272.36	96.78	0.714	0.30 ( 0.30)	0.99	37689.6	12410.00
10	22223.72	100.10	0.705	0.30 ( 0.30)	0.99	39232.3	11600.00
11	22015.07	105.79	0.689	0.30 ( 0.30)	0.99	41466.6	11111.00
12	21765.82	111.81	0.673	0.30 ( 0.30)	0.99	43400.5	12201.00
13	21471.91	115.56	0.662	0.30 ( 0.30)	0.99	44348.3	10410.00
14	21084.46	120.47	0.649	0.30 ( 0.30)	0.99	45488.7	12231.00
15	20439.63	127.68	0.637	0.30 ( 0.30)	0.99	46900.3	10400.00
16	20043.38	131.47	0.630	0.30 ( 0.30)	0.99	47490.5	10200.00
17	19397.42	138.63	0.618	0.30 ( 0.30)	0.99	48521.0	10320.00
18	18843.14	143.23	0.610	0.30 ( 0.30)	0.99	48746.5	10210.00
19	18366.22	147.87	0.602	0.30 ( 0.30)	0.99	48908.9	12000.00
20	15866.02	175.69	0.554	0.30 ( 0.30)	0.99	49525.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	64.13	17.31	1.767	0.30 ( 0.30)	0.98	48.4	600.00

LONGEST FLOWPATH FROM NODE 600.00 TO NODE 12601.00 = 4850.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13224.30	17.31	1.767	0.30 ( 0.30)	0.99	4882.0	600.00
2	13683.88	19.51	1.648	0.30 ( 0.30)	0.99	5496.3	40200.00
3	16118.51	35.38	1.168	0.30 ( 0.30)	0.99	10504.9	40100.00
4	17227.80	46.44	1.008	0.30 ( 0.30)	0.99	13770.2	11801.00
5	18749.38	60.63	0.876	0.30 ( 0.30)	0.99	18764.5	11530.00
6	19746.24	69.18	0.834	0.30 ( 0.30)	0.99	22632.6	11900.00
7	21396.75	79.46	0.784	0.30 ( 0.30)	0.99	28461.2	11330.00
8	22342.39	87.97	0.743	0.30 ( 0.30)	0.99	33548.4	10630.00
9	22299.06	93.52	0.723	0.30 ( 0.30)	0.99	36138.3	12330.00
10	22290.62	96.78	0.714	0.30 ( 0.30)	0.99	37738.0	12410.00
11	22241.57	100.10	0.705	0.30 ( 0.30)	0.99	39280.7	11600.00
12	22032.24	105.79	0.689	0.30 ( 0.30)	0.99	41515.0	11111.00
13	21782.26	111.81	0.673	0.30 ( 0.30)	0.99	43448.9	12201.00
14	21487.91	115.56	0.662	0.30 ( 0.30)	0.99	44396.7	10410.00

15	21099.88	120.47	0.649	0.30	( 0.30)	0.99	45537.1	12231.00
16	20454.52	127.68	0.637	0.30	( 0.30)	0.99	46948.7	10400.00
17	20057.98	131.47	0.630	0.30	( 0.30)	0.99	47538.9	10200.00
18	19411.48	138.63	0.618	0.30	( 0.30)	0.99	48569.4	10320.00
19	18856.86	143.23	0.610	0.30	( 0.30)	0.99	48794.9	10210.00
20	18379.60	147.87	0.602	0.30	( 0.30)	0.99	48957.3	12000.00
21	15877.31	175.69	0.554	0.30	( 0.30)	0.99	49574.3	10100.00

TOTAL AREA (ACRES) = 49574.3

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 22342.39 Tc (MIN.) = 87.967  
EFFECTIVE AREA (ACRES) = 33548.39 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 49574.3  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 2 <<<<<<  
-----

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12601.00 TO NODE 12602.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<<  
-----

ELEVATION DATA: UPSTREAM (FEET) = 325.00 DOWNSTREAM (FEET) = 313.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1377.46 CHANNEL SLOPE = 0.0087  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 6.52  
CHANNEL FLOW THRU SUBAREA (CFS) = 22342.39  
FLOW VELOCITY (FEET/SEC.) = 14.74 FLOW DEPTH (FEET) = 6.52  
TRAVEL TIME (MIN.) = 1.56 Tc (MIN.) = 89.52  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12602.00 = 101245.91 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12602.00 TO NODE 12603.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<<  
-----

ELEVATION DATA: UPSTREAM (FEET) = 313.00 DOWNSTREAM (FEET) = 310.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 312.40 CHANNEL SLOPE = 0.0096  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 6.34  
CHANNEL FLOW THRU SUBAREA (CFS) = 22342.39  
FLOW VELOCITY (FEET/SEC.) = 15.22 FLOW DEPTH (FEET) = 6.34  
TRAVEL TIME (MIN.) = 0.34 Tc (MIN.) = 89.87  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.30 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 0610403V.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	210.14	19.95	0.30	( 0.29)	0.97	175.0	40300.00
TOTAL AREA (ACRES) =				175.0			

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<<  
=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13224.30	19.59	1.643	0.30 ( 0.30)	0.99	4882.0	600.00
2	13683.88	21.76	1.547	0.30 ( 0.30)	0.99	5496.3	40200.00
3	16118.51	37.51	1.129	0.30 ( 0.30)	0.99	10504.9	40100.00
4	17227.80	48.52	0.983	0.30 ( 0.30)	0.99	13770.2	11801.00
5	18749.38	62.65	0.866	0.30 ( 0.30)	0.99	18764.5	11530.00
6	19746.24	71.16	0.825	0.30 ( 0.30)	0.99	22632.6	11900.00
7	21396.75	81.39	0.775	0.30 ( 0.30)	0.99	28461.2	11330.00
8	22342.39	89.87	0.734	0.30 ( 0.30)	0.99	33548.4	10630.00
9	22299.06	95.42	0.718	0.30 ( 0.30)	0.99	36138.3	12330.00
10	22290.62	98.68	0.709	0.30 ( 0.30)	0.99	37738.0	12410.00
11	22241.57	102.00	0.700	0.30 ( 0.30)	0.99	39280.7	11600.00
12	22032.24	107.70	0.684	0.30 ( 0.30)	0.99	41515.0	11111.00
13	21782.26	113.73	0.667	0.30 ( 0.30)	0.99	43448.9	12201.00
14	21487.91	117.49	0.657	0.30 ( 0.30)	0.99	44396.7	10410.00
15	21099.88	122.41	0.646	0.30 ( 0.30)	0.99	45537.1	12231.00
16	20454.52	129.64	0.633	0.30 ( 0.30)	0.99	46948.7	10400.00
17	20057.98	133.44	0.627	0.30 ( 0.30)	0.99	47538.9	10200.00
18	19411.48	140.62	0.615	0.30 ( 0.30)	0.99	48569.4	10320.00
19	18856.86	145.25	0.607	0.30 ( 0.30)	0.99	48794.9	10210.00
20	18379.60	149.90	0.599	0.30 ( 0.30)	0.99	48957.3	12000.00
21	15877.31	177.82	0.551	0.30 ( 0.30)	0.99	49574.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.30 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	210.14	19.95	1.624	0.30 ( 0.29)	0.97	175.0	40300.00

LONGEST FLOWPATH FROM NODE 40300.00 TO NODE 12603.00 = 5256.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13433.67	19.59	1.643	0.30 ( 0.30)	0.99	5053.9	600.00
2	13511.24	19.95	1.624	0.30 ( 0.30)	0.99	5159.7	40300.00
3	13882.02	21.76	1.547	0.30 ( 0.30)	0.99	5671.4	40200.00
4	16250.78	37.51	1.129	0.30 ( 0.30)	0.99	10679.9	40100.00
5	17337.12	48.52	0.983	0.30 ( 0.30)	0.99	13945.2	11801.00
6	18840.20	62.65	0.866	0.30 ( 0.30)	0.99	18939.6	11530.00
7	19830.54	71.16	0.825	0.30 ( 0.30)	0.99	22807.7	11900.00
8	21473.21	81.39	0.775	0.30 ( 0.30)	0.99	28636.3	11330.00
9	22412.35	89.87	0.734	0.30 ( 0.30)	0.99	33723.4	10630.00

10	22366.56	95.42	0.718	0.30	( 0.30)	0.99	36313.3	12330.00
11	22356.69	98.68	0.709	0.30	( 0.30)	0.99	37913.1	12410.00
12	22306.20	102.00	0.700	0.30	( 0.30)	0.99	39455.8	11600.00
13	22094.38	107.70	0.684	0.30	( 0.30)	0.99	41690.1	11111.00
14	21841.78	113.73	0.667	0.30	( 0.30)	0.99	43623.9	12201.00
15	21545.79	117.49	0.657	0.30	( 0.30)	0.99	44571.7	10410.00
16	21156.02	122.41	0.646	0.30	( 0.30)	0.99	45712.2	12231.00
17	20508.70	129.64	0.633	0.30	( 0.30)	0.99	47123.7	10400.00
18	20111.13	133.44	0.627	0.30	( 0.30)	0.99	47713.9	10200.00
19	19462.69	140.62	0.615	0.30	( 0.30)	0.99	48744.5	10320.00
20	18906.82	145.25	0.607	0.30	( 0.30)	0.99	48970.0	10210.00
21	18428.30	149.90	0.599	0.30	( 0.30)	0.99	49132.3	12000.00
22	15918.46	177.82	0.551	0.30	( 0.30)	0.99	49749.3	10100.00
TOTAL AREA (ACRES) =		49749.3						

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 22412.35 Tc (MIN.) = 89.867  
EFFECTIVE AREA (ACRES) = 33723.45 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 49749.3  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.30 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 89.87  
\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.734  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.20	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	8.80	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL, NARROWLEAF"	B	0.10	0.30	1.000	72
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.60	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	0.60	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL, NARROWLEAF"	B	2.90	0.30	1.000	72

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 14.20 SUBAREA RUNOFF (CFS) = 5.54  
EFFECTIVE AREA (ACRES) = 33737.64 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 49763.5 PEAK FLOW RATE (CFS) = 22412.35  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 89.87  
\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.734  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	0.30	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.90	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.10	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL, NARROWLEAF"	B	0.70	0.30	1.000	72
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.10	0.30	1.000	66
PUBLIC PARK	B	0.70	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.978  
SUBAREA AREA (ACRES) = 4.80 SUBAREA RUNOFF (CFS) = 1.90  
EFFECTIVE AREA (ACRES) = 33742.45 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 49768.3 PEAK FLOW RATE (CFS) = 22412.35  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 89.87  
\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.734  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	0.20	0.30	0.850	56
RESIDENTIAL					
"11+ DWELLINGS/ACRE"	B	0.10	0.30	0.200	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	1.40	0.30	0.900	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	1.00	0.30	0.900	56
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.30	0.30	1.000	65
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	5.70	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.960  
SUBAREA AREA (ACRES) = 8.70 SUBAREA RUNOFF (CFS) = 3.49  
EFFECTIVE AREA (ACRES) = 33751.14 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 49777.0 PEAK FLOW RATE (CFS) = 22412.35  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```
*****
FLOW PROCESS FROM NODE 12603.00 TO NODE 12604.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 310.00 DOWNSTREAM(FEET) = 307.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 459.69 CHANNEL SLOPE = 0.0065
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 7.10
CHANNEL FLOW THRU SUBAREA(CFS) = 22412.35
FLOW VELOCITY(FEET/SEC.) = 13.41 FLOW DEPTH(FEET) = 7.10
TRAVEL TIME(MIN.) = 0.57 Tc(MIN.) = 90.44
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12604.00 = 102017.99 FEET.
```

```
*****
FLOW PROCESS FROM NODE 12604.00 TO NODE 12604.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 90.44
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.732
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"CHAPARRAL,NARROWLEAF" B 0.10 0.30 1.000 72
NATURAL FAIR COVER
"OPEN BRUSH" B 0.90 0.30 1.000 66
PUBLIC PARK B 0.10 0.30 0.850 56
NATURAL FAIR COVER
"WOODLAND,GRASS" B 0.70 0.30 1.000 65
NATURAL FAIR COVER
"WOODLAND,GRASS" B 0.50 0.30 1.000 65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.993
SUBAREA AREA(ACRES) = 2.30 SUBAREA RUNOFF(CFS) = 0.90
EFFECTIVE AREA(ACRES) = 33753.45 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 49779.3 PEAK FLOW RATE(CFS) = 22412.35
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
```

```
*****
FLOW PROCESS FROM NODE 12604.00 TO NODE 12605.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 307.00 DOWNSTREAM(FEET) = 305.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 427.54 CHANNEL SLOPE = 0.0047
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 7.81
CHANNEL FLOW THRU SUBAREA(CFS) = 22412.35
FLOW VELOCITY(FEET/SEC.) = 12.01 FLOW DEPTH(FEET) = 7.81
TRAVEL TIME(MIN.) = 0.59 Tc(MIN.) = 91.03
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.00 = 102445.53 FEET.
```

```
*****
FLOW PROCESS FROM NODE 12605.00 TO NODE 12605.30 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 305.00 DOWNSTREAM(FEET) = 302.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 217.28 CHANNEL SLOPE = 0.0138
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 5.72
CHANNEL FLOW THRU SUBAREA(CFS) = 22412.35
FLOW VELOCITY(FEET/SEC.) = 17.15 FLOW DEPTH(FEET) = 5.72
TRAVEL TIME(MIN.) = 0.21 Tc(MIN.) = 91.24
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.30 = 102662.81 FEET.
```

```
*****
FLOW PROCESS FROM NODE 12605.30 TO NODE 12605.30 IS CODE = 15.1
-----
>>>>DEFINE MEMORY BANK # 3 <<<<
=====
PEAK FLOWRATE TABLE FILE NAME: 0610404V.DNA
MEMORY BANK # 3 DEFINED AS FOLLOWS:
STREAM Q Tc Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (ACRES) NODE
1 493.41 18.87 0.30( 0.30) 0.99 395.8 40430.00
2 488.18 19.41 0.30( 0.30) 0.99 400.1 40440.00
3 476.58 20.73 0.30( 0.30) 0.99 409.5 40400.00
4 475.50 20.84 0.30( 0.30) 0.99 410.1 40420.00
5 474.11 20.96 0.30( 0.30) 0.99 410.5 40410.00
TOTAL AREA(ACRES) = 410.5
```

```
*****
FLOW PROCESS FROM NODE 12605.30 TO NODE 12605.30 IS CODE = 11
-----
>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<
=====
** MAIN STREAM CONFLUENCE DATA **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 13433.67 21.23 1.570 0.30( 0.30) 0.99 5083.9 600.00
2 13511.24 21.59 1.554 0.30( 0.30) 0.99 5189.7 40300.00
3 13882.02 23.38 1.480 0.30( 0.30) 0.99 5701.4 40200.00
4 16250.78 39.04 1.101 0.30( 0.30) 0.99 10709.9 40100.00
5 17337.12 50.02 0.966 0.30( 0.30) 0.99 13975.2 11801.00
6 18840.20 64.11 0.859 0.30( 0.30) 0.99 18969.6 11530.00
7 19830.54 72.60 0.818 0.30( 0.30) 0.99 22837.7 11900.00
8 21473.21 82.78 0.768 0.30( 0.30) 0.99 28666.3 11330.00
9 22412.35 91.24 0.730 0.30( 0.30) 0.99 33753.4 10630.00
10 22366.56 96.80 0.714 0.30( 0.30) 0.99 36343.3 12330.00
11 22356.69 100.06 0.705 0.30( 0.30) 0.99 37943.1 12410.00
12 22306.20 103.38 0.696 0.30( 0.30) 0.99 39485.8 11600.00
13 22094.38 109.08 0.680 0.30( 0.30) 0.99 41720.1 11111.00
14 21841.78 115.12 0.664 0.30( 0.30) 0.99 43653.9 12201.00
15 21545.79 118.88 0.653 0.30( 0.30) 0.99 44601.7 10410.00
16 21156.02 123.81 0.643 0.30( 0.30) 0.99 45742.2 12231.00
```

```

17 20508.70 131.06 0.631 0.30( 0.30) 0.99 47153.7 10400.00
18 20111.13 134.87 0.624 0.30( 0.30) 0.99 47743.9 10200.00
19 19462.69 142.07 0.612 0.30( 0.30) 0.99 48774.5 10320.00
20 18906.82 146.70 0.604 0.30( 0.30) 0.99 49000.0 10210.00
21 18428.30 151.37 0.596 0.30( 0.30) 0.99 49162.3 12000.00
22 15918.46 179.37 0.548 0.30( 0.30) 0.99 49779.3 10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.30 = 102662.81 FEET.

```

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	493.41	18.87	1.682	0.30( 0.30)	0.99	395.8	40430.00
2	488.18	19.41	1.653	0.30( 0.30)	0.99	400.1	40440.00
3	476.58	20.73	1.591	0.30( 0.30)	0.99	409.5	40400.00
4	475.50	20.84	1.586	0.30( 0.30)	0.99	410.1	40420.00
5	474.11	20.96	1.581	0.30( 0.30)	0.99	410.5	40410.00

LONGEST FLOWPATH FROM NODE 40400.00 TO NODE 12605.30 = 7428.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13493.18	18.87	1.682	0.30( 0.30)	0.99	4914.6	40430.00
2	13576.02	19.41	1.653	0.30( 0.30)	0.99	5047.7	40440.00
3	13808.92	20.73	1.591	0.30( 0.30)	0.99	5373.2	40400.00
4	13831.39	20.84	1.586	0.30( 0.30)	0.99	5400.6	40420.00
5	13854.22	20.96	1.581	0.30( 0.30)	0.99	5429.3	40410.00
6	13903.58	21.23	1.570	0.30( 0.30)	0.99	5494.4	600.00
7	13975.60	21.59	1.554	0.30( 0.30)	0.99	5600.2	40300.00
8	14318.70	23.38	1.480	0.30( 0.30)	0.99	6111.8	40200.00
9	16547.77	39.04	1.101	0.30( 0.30)	0.99	11120.4	40100.00
10	17584.05	50.02	0.966	0.30( 0.30)	0.99	14385.7	11801.00
11	19047.68	64.11	0.859	0.30( 0.30)	0.99	19380.0	11530.00
12	20022.76	72.60	0.818	0.30( 0.30)	0.99	23248.1	11900.00
13	21647.12	82.78	0.768	0.30( 0.30)	0.99	29076.7	11330.00
14	22572.01	91.24	0.730	0.30( 0.30)	0.99	34163.9	10630.00
15	22520.54	96.80	0.714	0.30( 0.30)	0.99	36753.8	12330.00
16	22507.35	100.06	0.705	0.30( 0.30)	0.99	38353.5	12410.00
17	22453.46	103.38	0.696	0.30( 0.30)	0.99	39896.2	11600.00
18	22235.82	109.08	0.680	0.30( 0.30)	0.99	42130.5	11111.00
19	21977.05	115.12	0.664	0.30( 0.30)	0.99	44064.4	12201.00
20	21677.21	118.88	0.653	0.30( 0.30)	0.99	45012.2	10410.00
21	21283.88	123.81	0.643	0.30( 0.30)	0.99	46152.6	12231.00
22	20631.96	131.06	0.631	0.30( 0.30)	0.99	47564.2	10400.00
23	20231.98	134.87	0.624	0.30( 0.30)	0.99	48154.4	10200.00
24	19578.98	142.07	0.612	0.30( 0.30)	0.99	49185.0	10320.00
25	19020.16	146.70	0.604	0.30( 0.30)	0.99	49410.4	10210.00
26	18538.69	151.37	0.596	0.30( 0.30)	0.99	49572.8	12000.00
27	16011.09	179.37	0.548	0.30( 0.30)	0.99	50189.8	10100.00

TOTAL AREA (ACRES) = 50189.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 22572.01 Tc(MIN.) = 91.243  
EFFECTIVE AREA(ACRES) = 34163.91 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA(ACRES) = 50189.8  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.30 = 102662.81 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.30 TO NODE 12605.30 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.30 TO NODE 12605.60 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 302.00 DOWNSTREAM(FEET) = 295.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 738.76 CHANNEL SLOPE = 0.0095  
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.40  
CHANNEL FLOW THRU SUBAREA(CFS) = 22572.01  
FLOW VELOCITY(FEET/SEC.) = 15.21 FLOW DEPTH(FEET) = 6.40  
TRAVEL TIME(MIN.) = 0.81 Tc(MIN.) = 92.05  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.60 = 103401.57 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.60 TO NODE 12605.60 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610405V.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	115.81	14.42	0.30( 0.30)	1.00	76.8	40510.00
2	112.57	16.04	0.30( 0.30)	1.00	81.4	40500.00

TOTAL AREA(ACRES) = 81.4

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.60 TO NODE 12605.60 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13493.18	19.84	1.630	0.30( 0.30)	0.99	4914.6	40430.00
2	13576.02	20.38	1.605	0.30( 0.30)	0.99	5047.7	40440.00
3	13808.92	21.69	1.550	0.30( 0.30)	0.99	5373.2	40400.00
4	13831.39	21.80	1.546	0.30( 0.30)	0.99	5400.6	40420.00
5	13854.22	21.92	1.541	0.30( 0.30)	0.99	5429.3	40410.00
6	13903.58	22.19	1.529	0.30( 0.30)	0.99	5494.4	600.00
7	13975.60	22.55	1.514	0.30( 0.30)	0.99	5600.2	40300.00
8	14318.70	24.33	1.440	0.30( 0.30)	0.99	6111.8	40200.00
9	16547.77	39.94	1.085	0.30( 0.30)	0.99	11120.4	40100.00
10	17584.05	50.90	0.958	0.30( 0.30)	0.99	14385.7	11801.00
11	19047.68	64.97	0.855	0.30( 0.30)	0.99	19380.0	11530.00
12	20022.76	73.44	0.814	0.30( 0.30)	0.99	23248.1	11900.00
13	21647.12	83.60	0.764	0.30( 0.30)	0.99	29076.7	11330.00
14	22572.01	92.05	0.727	0.30( 0.30)	0.99	34163.9	10630.00
15	22520.54	97.61	0.712	0.30( 0.30)	0.99	36753.8	12330.00

16	22507.35	100.87	0.703	0.30 ( 0.30)	0.99	38353.5	12410.00
17	22453.46	104.19	0.694	0.30 ( 0.30)	0.99	39896.2	11600.00
18	22235.82	109.89	0.678	0.30 ( 0.30)	0.99	42130.5	11111.00
19	21977.05	115.93	0.661	0.30 ( 0.30)	0.99	44064.4	12201.00
20	21677.21	119.70	0.651	0.30 ( 0.30)	0.99	45012.2	10410.00
21	21283.88	124.63	0.642	0.30 ( 0.30)	0.99	46152.6	12231.00
22	20631.96	131.90	0.630	0.30 ( 0.30)	0.99	47564.2	10400.00
23	20231.98	135.71	0.623	0.30 ( 0.30)	0.99	48154.4	10200.00
24	19578.98	142.92	0.611	0.30 ( 0.30)	0.99	49185.0	10320.00
25	19020.16	147.56	0.603	0.30 ( 0.30)	0.99	49410.4	10210.00
26	18538.69	152.24	0.595	0.30 ( 0.30)	0.99	49572.8	12000.00
27	16011.09	180.28	0.547	0.30 ( 0.30)	0.99	50189.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.60 = 103401.57 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	115.81	14.42	1.974	0.30 ( 0.30)	1.00	76.8	40510.00
2	112.57	16.04	1.836	0.30 ( 0.30)	1.00	81.4	40500.00

LONGEST FLOWPATH FROM NODE 40500.00 TO NODE 12605.60 = 4091.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12458.14	14.42	1.974	0.30 ( 0.30)	0.99	3649.1	40510.00
2	12714.09	16.04	1.836	0.30 ( 0.30)	0.99	4054.7	40500.00
3	13590.61	19.84	1.630	0.30 ( 0.30)	0.99	4996.0	40430.00
4	13671.67	20.38	1.605	0.30 ( 0.30)	0.99	5129.1	40440.00
5	13900.54	21.69	1.550	0.30 ( 0.30)	0.99	5454.6	40400.00
6	13922.67	21.80	1.546	0.30 ( 0.30)	0.99	5482.0	40420.00
7	13945.14	21.92	1.541	0.30 ( 0.30)	0.99	5510.6	40410.00
8	13993.67	22.19	1.529	0.30 ( 0.30)	0.99	5575.7	600.00
9	14064.59	22.55	1.514	0.30 ( 0.30)	0.99	5681.6	40300.00
10	14402.23	24.33	1.440	0.30 ( 0.30)	0.99	6193.2	40200.00
11	16605.31	39.94	1.085	0.30 ( 0.30)	0.99	11201.8	40100.00
12	17632.30	50.90	0.958	0.30 ( 0.30)	0.99	14467.0	11801.00
13	19088.36	64.97	0.855	0.30 ( 0.30)	0.99	19461.4	11530.00
14	20060.42	73.44	0.814	0.30 ( 0.30)	0.99	23329.5	11900.00
15	21681.17	83.60	0.764	0.30 ( 0.30)	0.99	29158.1	11330.00
16	22603.36	92.05	0.727	0.30 ( 0.30)	0.99	34245.3	10630.00
17	22550.76	97.61	0.712	0.30 ( 0.30)	0.99	36835.1	12330.00
18	22536.91	100.87	0.703	0.30 ( 0.30)	0.99	38434.9	12410.00
19	22482.35	104.19	0.694	0.30 ( 0.30)	0.99	39977.6	11600.00
20	22263.55	109.89	0.678	0.30 ( 0.30)	0.99	42211.9	11111.00
21	22003.56	115.93	0.661	0.30 ( 0.30)	0.99	44145.8	12201.00
22	21702.95	119.70	0.651	0.30 ( 0.30)	0.99	45093.6	10410.00
23	21308.98	124.63	0.642	0.30 ( 0.30)	0.99	46234.0	12231.00
24	20656.15	131.90	0.630	0.30 ( 0.30)	0.99	47645.6	10400.00
25	20255.69	135.71	0.623	0.30 ( 0.30)	0.99	48235.8	10200.00
26	19601.78	142.92	0.611	0.30 ( 0.30)	0.99	49266.3	10320.00
27	19042.38	147.56	0.603	0.30 ( 0.30)	0.99	49491.8	10210.00
28	18560.32	152.24	0.595	0.30 ( 0.30)	0.99	49654.2	12000.00
29	16029.22	180.28	0.547	0.30 ( 0.30)	0.99	50271.2	10100.00

TOTAL AREA (ACRES) = 50271.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 22603.36 Tc (MIN.) = 92.053  
EFFECTIVE AREA (ACRES) = 34245.28 AREA-AVERAGED Fm (INCH/HR) = 0.30

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 50271.2  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.60 = 103401.57 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.60 TO NODE 12605.60 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.60 TO NODE 12606.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 295.00 DOWNSTREAM (FEET) = 286.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1203.43 CHANNEL SLOPE = 0.0075  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT (FEET) = 6.86  
CHANNEL FLOW THRU SUBAREA (CFS) = 22603.36  
FLOW VELOCITY (FEET/SEC.) = 14.07 FLOW DEPTH (FEET) = 6.86  
TRAVEL TIME (MIN.) = 1.43 Tc (MIN.) = 93.48  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104605.00 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610406V.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	152.48	21.61	0.30 ( 0.30)	0.99	135.0	40600.00

TOTAL AREA (ACRES) = 135.0

\*\*\*\*\*

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12458.14	16.17	1.829	0.30 ( 0.30)	0.99	3649.1	40510.00
2	12714.09	17.78	1.742	0.30 ( 0.30)	0.99	4054.7	40500.00
3	13590.61	21.54	1.557	0.30 ( 0.30)	0.99	4996.0	40430.00
4	13671.67	22.07	1.534	0.30 ( 0.30)	0.99	5129.1	40440.00
5	13900.54	23.38	1.480	0.30 ( 0.30)	0.99	5454.6	40400.00
6	13922.67	23.49	1.475	0.30 ( 0.30)	0.99	5482.0	40420.00
7	13945.14	23.60	1.470	0.30 ( 0.30)	0.99	5510.6	40410.00
8	13993.67	23.87	1.459	0.30 ( 0.30)	0.99	5575.7	600.00
9	14064.59	24.23	1.444	0.30 ( 0.30)	0.99	5681.6	40300.00
10	14402.23	26.00	1.383	0.30 ( 0.30)	0.99	6193.2	40200.00
11	16605.31	41.53	1.066	0.30 ( 0.30)	0.99	11201.8	40100.00

12	17632.30	52.45	0.945	0.30( 0.30)	0.99	14467.0	11801.00
13	19088.36	66.48	0.847	0.30( 0.30)	0.99	19461.4	11530.00
14	20060.42	74.93	0.806	0.30( 0.30)	0.99	23329.5	11900.00
15	21681.17	85.05	0.757	0.30( 0.30)	0.99	29158.1	11330.00
16	22603.36	93.48	0.723	0.30( 0.30)	0.99	34245.3	10630.00
17	22550.76	99.04	0.708	0.30( 0.30)	0.99	36835.1	12330.00
18	22536.91	102.29	0.699	0.30( 0.30)	0.99	38434.9	12410.00
19	22482.35	105.62	0.690	0.30( 0.30)	0.99	39977.6	11600.00
20	22263.55	111.33	0.674	0.30( 0.30)	0.99	42211.9	11111.00
21	22003.56	117.37	0.657	0.30( 0.30)	0.99	44145.8	12201.00
22	21702.95	121.15	0.648	0.30( 0.30)	0.99	45093.6	10410.00
23	21308.98	126.09	0.640	0.30( 0.30)	0.99	46234.0	12231.00
24	20656.15	133.37	0.627	0.30( 0.30)	0.99	47645.6	10400.00
25	20255.69	137.19	0.620	0.30( 0.30)	0.99	48235.8	10200.00
26	19601.78	144.41	0.608	0.30( 0.30)	0.99	49266.3	10320.00
27	19042.38	149.07	0.600	0.30( 0.30)	0.99	49491.8	10210.00
28	18560.32	153.76	0.592	0.30( 0.30)	0.99	49654.2	12000.00
29	16029.22	181.89	0.546	0.30( 0.30)	0.99	50271.2	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104605.00 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	152.48	21.61	1.554	0.30( 0.30)	0.99	135.0	40600.00

LONGEST FLOWPATH FROM NODE 40600.00 TO NODE 12606.00 = 6107.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12597.31	16.17	1.829	0.30( 0.30)	0.99	3750.1	40510.00
2	12858.35	17.78	1.742	0.30( 0.30)	0.99	4165.8	40500.00
3	13742.96	21.54	1.557	0.30( 0.30)	0.99	5130.5	40430.00
4	13753.27	21.61	1.554	0.30( 0.30)	0.99	5147.7	40600.00
5	13821.79	22.07	1.534	0.30( 0.30)	0.99	5264.0	40440.00
6	14044.03	23.38	1.480	0.30( 0.30)	0.99	5589.5	40400.00
7	14065.61	23.49	1.475	0.30( 0.30)	0.99	5617.0	40420.00
8	14087.48	23.60	1.470	0.30( 0.30)	0.99	5645.6	40410.00
9	14134.65	23.87	1.459	0.30( 0.30)	0.99	5710.7	600.00
10	14203.77	24.23	1.444	0.30( 0.30)	0.99	5816.6	40300.00
11	14533.92	26.00	1.383	0.30( 0.30)	0.99	6328.2	40200.00
12	16698.54	41.53	1.066	0.30( 0.30)	0.99	11336.7	40100.00
13	17710.80	52.45	0.945	0.30( 0.30)	0.99	14602.0	11801.00
14	19155.05	66.48	0.847	0.30( 0.30)	0.99	19596.4	11530.00
15	20122.12	74.93	0.806	0.30( 0.30)	0.99	23464.5	11900.00
16	21736.88	85.05	0.757	0.30( 0.30)	0.99	29293.1	11330.00
17	22654.98	93.48	0.723	0.30( 0.30)	0.99	34380.3	10630.00
18	22600.51	99.04	0.708	0.30( 0.30)	0.99	36970.1	12330.00
19	22585.57	102.29	0.699	0.30( 0.30)	0.99	38569.9	12410.00
20	22529.88	105.62	0.690	0.30( 0.30)	0.99	40112.6	11600.00
21	22309.17	111.33	0.674	0.30( 0.30)	0.99	42346.9	11111.00
22	22047.15	117.37	0.657	0.30( 0.30)	0.99	44280.7	12201.00
23	21745.42	121.15	0.648	0.30( 0.30)	0.99	45228.6	10410.00
24	21350.42	126.09	0.640	0.30( 0.30)	0.99	46369.0	12231.00
25	20696.07	133.37	0.627	0.30( 0.30)	0.99	47780.5	10400.00
26	20294.81	137.19	0.620	0.30( 0.30)	0.99	48370.8	10200.00
27	19639.40	144.41	0.608	0.30( 0.30)	0.99	49401.3	10320.00
28	19079.03	149.07	0.600	0.30( 0.30)	0.99	49626.8	10210.00
29	18595.98	153.76	0.592	0.30( 0.30)	0.99	49789.1	12000.00
30	16059.24	181.89	0.546	0.30( 0.30)	0.99	50406.1	10100.00

30 16059.24 181.89 0.546 0.30( 0.30) 0.99 50406.1 10100.00  
TOTAL AREA (ACRES) = 50406.1

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 22654.98 Tc(MIN.) = 93.478  
EFFECTIVE AREA(ACRES) = 34380.25 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA(ACRES) = 50406.1  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104605.00 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 50406.1 TC(MIN.) = 93.48  
EFFECTIVE AREA(ACRES) = 34380.25 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.994  
PEAK FLOW RATE(CFS) = 22654.98

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12597.31	16.17	1.829	0.30( 0.30)	0.99	3750.1	40510.00
2	12858.35	17.78	1.742	0.30( 0.30)	0.99	4165.8	40500.00
3	13742.96	21.54	1.557	0.30( 0.30)	0.99	5130.5	40430.00
4	13753.27	21.61	1.554	0.30( 0.30)	0.99	5147.7	40600.00
5	13821.79	22.07	1.534	0.30( 0.30)	0.99	5264.0	40440.00
6	14044.03	23.38	1.480	0.30( 0.30)	0.99	5589.5	40400.00
7	14065.61	23.49	1.475	0.30( 0.30)	0.99	5617.0	40420.00
8	14087.48	23.60	1.470	0.30( 0.30)	0.99	5645.6	40410.00
9	14134.65	23.87	1.459	0.30( 0.30)	0.99	5710.7	600.00
10	14203.77	24.23	1.444	0.30( 0.30)	0.99	5816.6	40300.00
11	14533.92	26.00	1.383	0.30( 0.30)	0.99	6328.2	40200.00
12	16698.54	41.53	1.066	0.30( 0.30)	0.99	11336.7	40100.00
13	17710.80	52.45	0.945	0.30( 0.30)	0.99	14602.0	11801.00
14	19155.05	66.48	0.847	0.30( 0.30)	0.99	19596.4	11530.00
15	20122.12	74.93	0.806	0.30( 0.30)	0.99	23464.5	11900.00
16	21736.88	85.05	0.757	0.30( 0.30)	0.99	29293.1	11330.00
17	22654.98	93.48	0.723	0.30( 0.30)	0.99	34380.3	10630.00
18	22600.51	99.04	0.708	0.30( 0.30)	0.99	36970.1	12330.00
19	22585.57	102.29	0.699	0.30( 0.30)	0.99	38569.9	12410.00
20	22529.88	105.62	0.690	0.30( 0.30)	0.99	40112.6	11600.00
21	22309.17	111.33	0.674	0.30( 0.30)	0.99	42346.9	11111.00
22	22047.15	117.37	0.657	0.30( 0.30)	0.99	44280.7	12201.00
23	21745.42	121.15	0.648	0.30( 0.30)	0.99	45228.6	10410.00
24	21350.42	126.09	0.640	0.30( 0.30)	0.99	46369.0	12231.00
25	20696.07	133.37	0.627	0.30( 0.30)	0.99	47780.5	10400.00
26	20294.81	137.19	0.620	0.30( 0.30)	0.99	48370.8	10200.00
27	19639.40	144.41	0.608	0.30( 0.30)	0.99	49401.3	10320.00
28	19079.03	149.07	0.600	0.30( 0.30)	0.99	49626.8	10210.00
29	18595.98	153.76	0.592	0.30( 0.30)	0.99	49789.1	12000.00
30	16059.24	181.89	0.546	0.30( 0.30)	0.99	50406.1	10100.00

END OF RATIONAL METHOD ANALYSIS





\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S27- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 10-YR RM EV APRIL 2019 CCHIU \*  
\*\*\*\*\*

FILE NAME: RI10EV27.DAT  
TIME/DATE OF STUDY: 10:15 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 10.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 3.867
- 2) 10.00; 2.568
- 3) 15.00; 1.883
- 4) 20.00; 1.612
- 5) 25.00; 1.405
- 6) 30.00; 1.260
- 7) 40.00; 1.079
- 8) 50.00; 0.961
- 9) 60.00; 0.873
- 10) 90.00; 0.726
- 11) 120.00; 0.643
- 12) 180.00; 0.540
- 13) 360.00; 0.400
- 14) 1200.00; 0.176

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER WIDTH (FT)	GEOMETRIES: LIP (FT)	MANNING HIKE FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167 0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI10EV26.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12858.35	17.78	0.30 ( 0.30)	0.99	4165.8	40500.00
2	14533.92	26.00	0.30 ( 0.30)	0.99	6328.2	40200.00
3	16698.54	41.53	0.30 ( 0.30)	0.99	11336.7	40100.00
4	17710.80	52.45	0.30 ( 0.30)	0.99	14602.0	11801.00
5	19155.05	66.48	0.30 ( 0.30)	0.99	19596.4	11530.00
6	20122.12	74.93	0.30 ( 0.30)	0.99	23464.5	11900.00
7	21736.88	85.05	0.30 ( 0.30)	0.99	29293.1	11330.00
8	22654.98	93.48	0.30 ( 0.30)	0.99	34380.3	10630.00
9	22600.51	99.04	0.30 ( 0.30)	0.99	36970.1	12330.00
10	22529.88	105.62	0.30 ( 0.30)	0.99	40112.6	11600.00
11	22309.17	111.33	0.30 ( 0.30)	0.99	42346.9	11111.00
12	22047.15	117.37	0.30 ( 0.30)	0.99	44280.7	12201.00
13	21745.42	121.15	0.30 ( 0.30)	0.99	45228.6	10410.00
14	21350.42	126.09	0.30 ( 0.30)	0.99	46369.0	12231.00
15	20696.07	133.37	0.30 ( 0.30)	0.99	47780.5	10400.00
16	20294.81	137.19	0.30 ( 0.30)	0.99	48370.8	10200.00
17	19639.40	144.41	0.30 ( 0.30)	0.99	49401.3	10320.00
18	19079.03	149.07	0.30 ( 0.30)	0.99	49626.8	10210.00
19	18595.98	153.76	0.30 ( 0.30)	0.99	49789.1	12000.00
20	16059.24	181.89	0.30 ( 0.30)	0.99	50406.1	10100.00
TOTAL AREA (ACRES) =						50406.1

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12858.35	17.78	0.30 ( 0.30)	0.99	4165.8	40500.00
2	14533.92	26.00	0.30 ( 0.30)	0.99	6328.2	40200.00
3	16698.54	41.53	0.30 ( 0.30)	0.99	11336.7	40100.00
4	17710.80	52.45	0.30 ( 0.30)	0.99	14602.0	11801.00
5	19155.05	66.48	0.30 ( 0.30)	0.99	19596.4	11530.00
6	20122.12	74.93	0.30 ( 0.30)	0.99	23464.5	11900.00
7	21736.88	85.05	0.30 ( 0.30)	0.99	29293.1	11330.00
8	22654.98	93.48	0.30 ( 0.30)	0.99	34380.3	10630.00
9	22600.51	99.04	0.30 ( 0.30)	0.99	36970.1	12330.00
10	22529.88	105.62	0.30 ( 0.30)	0.99	40112.6	11600.00
11	22309.17	111.33	0.30 ( 0.30)	0.99	42346.9	11111.00
12	22047.15	117.37	0.30 ( 0.30)	0.99	44280.7	12201.00
13	21745.42	121.15	0.30 ( 0.30)	0.99	45228.6	10410.00

14	21350.42	126.09	0.30	( 0.30)	0.99	46369.0	12231.00
15	20696.07	133.37	0.30	( 0.30)	0.99	47780.5	10400.00
16	20294.81	137.19	0.30	( 0.30)	0.99	48370.8	10200.00
17	19639.40	144.41	0.30	( 0.30)	0.99	49401.3	10320.00
18	19079.03	149.07	0.30	( 0.30)	0.99	49626.8	10210.00
19	18595.98	153.76	0.30	( 0.30)	0.99	49789.1	12000.00
20	16059.24	181.89	0.30	( 0.30)	0.99	50406.1	10100.00
TOTAL AREA (ACRES) =			50406.1				

\*\*\*\*\*

FLOW PROCESS FROM NODE 12606.00 TO NODE 12701.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 286.00 DOWNSTREAM(FEET) = 276.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1260.19 CHANNEL SLOPE = 0.0079  
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.75

\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.712

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	7.55	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 22657.30

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 14.36

AVERAGE FLOW DEPTH(FEET) = 6.75 TRAVEL TIME(MIN.) = 1.46

Tc(MIN.) = 94.94

SUBAREA AREA(ACRES) = 7.55 SUBAREA RUNOFF(CFS) = 4.64

EFFECTIVE AREA(ACRES) = 34387.80 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 50413.7 PEAK FLOW RATE(CFS) = 22654.98

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.75

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 6.75 FLOW VELOCITY(FEET/SEC.) = 14.36

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12701.00 = 105865.19 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12701.00 TO NODE 12701.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 94.94

\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.712

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	0.90	0.30	0.850	56

NATURAL FAIR COVER

"WOODLAND,GRASS" B 3.40 0.30 1.000 65

RESIDENTIAL

"5-7 DWELLINGS/ACRE"	B	0.40	0.30	0.500	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	23.00	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	3.30	0.30	1.000	66
NATURAL FAIR COVER					
"GRASS"	B	0.40	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.989

SUBAREA AREA(ACRES) = 31.40 SUBAREA RUNOFF(CFS) = 11.74

EFFECTIVE AREA(ACRES) = 34419.20 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 50445.1 PEAK FLOW RATE(CFS) = 22654.98

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12701.00 TO NODE 12701.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 94.94

\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.712

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	1.70	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 1.70 SUBAREA RUNOFF(CFS) = 0.63

EFFECTIVE AREA(ACRES) = 34420.90 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 50446.8 PEAK FLOW RATE(CFS) = 22654.98

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12701.00 TO NODE 12720.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 276.00 DOWNSTREAM(FEET) = 275.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 147.65 CHANNEL SLOPE = 0.0068

GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT(FEET) = 7.07

\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.712

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	1.49	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.850

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 22655.29

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 13.62

AVERAGE FLOW DEPTH(FEET) = 7.07 TRAVEL TIME(MIN.) = 0.18

Tc(MIN.) = 95.12

SUBAREA AREA(ACRES) = 1.49 SUBAREA RUNOFF(CFS) = 0.61

EFFECTIVE AREA(ACRES) = 34422.39 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 50448.3 PEAK FLOW RATE(CFS) = 22654.98  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 7.07

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 7.07 FLOW VELOCITY(FEET/SEC.) = 13.62  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.00 = 106012.84 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12701.00 TO NODE 12720.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
 TIME OF CONCENTRATION(MIN.) = 95.12  
 RAINFALL INTENSITY(INCH/HR) = 0.71  
 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.99  
 EFFECTIVE STREAM AREA(ACRES) = 34422.39  
 TOTAL STREAM AREA(ACRES) = 50448.27  
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 22654.98

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12710.00 TO NODE 12711.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<  
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 943.56  
 ELEVATION DATA: UPSTREAM(FEET) = 940.78 DOWNSTREAM(FEET) = 657.79

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
 SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 13.910  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.032  
 SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER						
"GRASS"	B	6.56	0.30	1.000	69	13.91

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA RUNOFF(CFS) = 10.23  
 TOTAL AREA(ACRES) = 6.56 PEAK FLOW RATE(CFS) = 10.23

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12711.00 TO NODE 12712.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 657.79 DOWNSTREAM(FEET) = 585.63  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 766.00 CHANNEL SLOPE = 0.0942

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.58  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.795

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	26.94	0.30	1.000	66

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 28.41  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.70  
 AVERAGE FLOW DEPTH(FEET) = 0.54 TRAVEL TIME(MIN.) = 2.71  
 Tc(MIN.) = 16.62

SUBAREA AREA(ACRES) = 26.94 SUBAREA RUNOFF(CFS) = 36.25  
 EFFECTIVE AREA(ACRES) = 33.50 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 33.5 PEAK FLOW RATE(CFS) = 45.07  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.71

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 0.71 FLOW VELOCITY(FEET/SEC.) = 5.52  
 LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12712.00 = 1709.56 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12712.00 TO NODE 12713.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 585.63 DOWNSTREAM(FEET) = 463.75  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1025.79 CHANNEL SLOPE = 0.1188  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.75  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.650

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	14.73	0.30	0.100	56

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.100  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 55.81  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.39  
 AVERAGE FLOW DEPTH(FEET) = 0.76 TRAVEL TIME(MIN.) = 2.67  
 Tc(MIN.) = 19.30

SUBAREA AREA(ACRES) = 14.73 SUBAREA RUNOFF(CFS) = 21.48  
 EFFECTIVE AREA(ACRES) = 48.23 AREA-AVERAGED Fm(INCH/HR) = 0.22  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.73  
 TOTAL AREA(ACRES) = 48.2 PEAK FLOW RATE(CFS) = 62.18  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.81

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.81 FLOW VELOCITY(FEET/SEC.) = 6.65  
LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12713.00 = 2735.35 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12713.00 TO NODE 12714.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 463.75 DOWNSTREAM(FEET) = 360.30  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1148.54 CHANNEL SLOPE = 0.0901  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.33  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.539

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	105.64	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 133.89

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.79

AVERAGE FLOW DEPTH(FEET) = 1.35 TRAVEL TIME(MIN.) = 2.46

Tc(MIN.) = 21.76

SUBAREA AREA(ACRES) = 105.64 SUBAREA RUNOFF(CFS) = 143.50

EFFECTIVE AREA(ACRES) = 153.87 AREA-AVERAGED Fm(INCH/HR) = 0.09

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.30

TOTAL AREA(ACRES) = 153.9 PEAK FLOW RATE(CFS) = 200.87

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.70

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.70 FLOW VELOCITY(FEET/SEC.) = 8.83

LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12714.00 = 3883.89 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12714.00 TO NODE 12720.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 360.30 DOWNSTREAM(FEET) = 275.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1314.99 CHANNEL SLOPE = 0.0649  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.25  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.435

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	127.13	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 281.26

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.68

AVERAGE FLOW DEPTH(FEET) = 2.24 TRAVEL TIME(MIN.) = 2.52

Tc(MIN.) = 24.28

SUBAREA AREA(ACRES) = 127.13 SUBAREA RUNOFF(CFS) = 160.73

EFFECTIVE AREA(ACRES) = 281.00 AREA-AVERAGED Fm(INCH/HR) = 0.06

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.21

TOTAL AREA(ACRES) = 281.0 PEAK FLOW RATE(CFS) = 347.12

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.51

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.51 FLOW VELOCITY(FEET/SEC.) = 9.23

LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12720.00 = 5198.88 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<

TOTAL NUMBER OF STREAMS = 2

CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:

TIME OF CONCENTRATION(MIN.) = 24.28

RAINFALL INTENSITY(INCH/HR) = 1.43

AREA-AVERAGED Fm(INCH/HR) = 0.06

AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.21

EFFECTIVE STREAM AREA(ACRES) = 281.00

TOTAL STREAM AREA(ACRES) = 281.00

PEAK FLOW RATE(CFS) AT CONFLUENCE = 347.12

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12858.35	19.78	1.624	0.30( 0.30)	0.99	4207.9	40500.00
1	14533.92	27.91	1.320	0.30( 0.30)	0.99	6370.3	40200.00
1	16698.54	43.35	1.039	0.30( 0.30)	0.99	11378.9	40100.00
1	17710.80	54.24	0.924	0.30( 0.30)	0.99	14644.2	11801.00
1	19155.05	68.22	0.833	0.30( 0.30)	0.99	19638.5	11530.00
1	20122.12	76.64	0.791	0.30( 0.30)	0.99	23506.6	11900.00
1	21736.88	86.72	0.742	0.30( 0.30)	0.99	29335.2	11330.00
1	22654.98	95.12	0.712	0.30( 0.30)	0.99	34422.4	10630.00
1	22600.51	100.68	0.696	0.30( 0.30)	0.99	37012.3	12330.00
1	22529.88	107.27	0.678	0.30( 0.30)	0.99	40154.7	11600.00
1	22309.17	112.98	0.662	0.30( 0.30)	0.99	42389.0	11111.00
1	22047.15	119.03	0.646	0.30( 0.30)	0.99	44322.9	12201.00
1	21745.42	122.81	0.638	0.30( 0.30)	0.99	45270.7	10410.00
1	21350.42	127.77	0.630	0.30( 0.30)	0.99	46411.1	12231.00
1	20696.07	135.06	0.617	0.30( 0.30)	0.99	47822.7	10400.00
1	20294.81	138.90	0.611	0.30( 0.30)	0.99	48412.9	10200.00
1	19639.40	146.14	0.598	0.30( 0.30)	0.99	49443.4	10320.00
1	19079.03	150.82	0.590	0.30( 0.30)	0.99	49668.9	10210.00
1	18595.98	155.52	0.582	0.30( 0.30)	0.99	49831.3	12000.00
1	16059.24	183.74	0.537	0.30( 0.30)	0.99	50448.3	10100.00
2	347.12	24.28	1.435	0.30( 0.06)	0.21	281.0	12710.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13180.11	19.78	1.624	0.30 ( 0.28)	0.95	4436.9	40500.00
2	14132.37	24.28	1.435	0.30 ( 0.29)	0.95	5685.1	12710.00
3	14852.14	27.91	1.320	0.30 ( 0.29)	0.96	6651.3	40200.00
4	16945.68	43.35	1.039	0.30 ( 0.29)	0.97	11659.9	40100.00
5	17928.67	54.24	0.924	0.30 ( 0.29)	0.98	14925.2	11801.00
6	19349.92	68.22	0.833	0.30 ( 0.29)	0.98	19919.5	11530.00
7	20306.56	76.64	0.791	0.30 ( 0.30)	0.98	23787.6	11900.00
8	21908.83	86.72	0.742	0.30 ( 0.30)	0.99	29616.2	11330.00
9	22819.28	95.12	0.712	0.30 ( 0.30)	0.99	34703.4	10630.00
10	22760.92	100.68	0.696	0.30 ( 0.30)	0.99	37293.3	12330.00
11	22685.68	107.27	0.678	0.30 ( 0.30)	0.99	40435.7	11600.00
12	22460.97	112.98	0.662	0.30 ( 0.30)	0.99	42670.0	11111.00
13	22194.71	119.03	0.646	0.30 ( 0.30)	0.99	44603.9	12201.00
14	21891.09	122.81	0.638	0.30 ( 0.30)	0.99	45551.7	10410.00
15	21493.94	127.77	0.630	0.30 ( 0.30)	0.99	46692.1	12231.00
16	20836.42	135.06	0.617	0.30 ( 0.30)	0.99	48103.7	10400.00
17	20433.49	138.90	0.611	0.30 ( 0.30)	0.99	48693.9	10200.00
18	19774.94	146.14	0.598	0.30 ( 0.30)	0.99	49724.4	10320.00
19	19212.54	150.82	0.590	0.30 ( 0.30)	0.99	49949.9	10210.00
20	18727.45	155.52	0.582	0.30 ( 0.30)	0.99	50112.3	12000.00
21	16179.34	183.74	0.537	0.30 ( 0.30)	0.99	50729.3	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 22819.28 Tc(MIN.) = 95.12  
 EFFECTIVE AREA(ACRES) = 34703.39 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 50729.3  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.00 = 106012.84 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 95.12

\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.712

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	0.40	0.30	0.850	56
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.10	0.30	1.000	65
RESIDENTIAL					
"5-7 DWELLINGS/ACRE"	B	0.20	0.30	0.500	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	3.80	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.964

SUBAREA AREA(ACRES) = 4.50 SUBAREA RUNOFF(CFS) = 1.71

EFFECTIVE AREA(ACRES) = 34707.89 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 50733.8 PEAK FLOW RATE(CFS) = 22819.28

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 275.00 DOWNSTREAM(FEET) = 258.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 2669.21 CHANNEL SLOPE = 0.0064

GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT(FEET) = 7.22

\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.703

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	62.15	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 22838.09

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 13.39

AVERAGE FLOW DEPTH(FEET) = 7.22 TRAVEL TIME(MIN.) = 3.32

Tc(MIN.) = 98.44

SUBAREA AREA(ACRES) = 62.15 SUBAREA RUNOFF(CFS) = 37.62

EFFECTIVE AREA(ACRES) = 34770.04 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 50795.9 PEAK FLOW RATE(CFS) = 22819.28

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT(FEET) = 7.22

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 7.22 FLOW VELOCITY(FEET/SEC.) = 13.39

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108682.05 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 98.44

\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.703

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	0.10	0.30	0.100	56
NATURAL FAIR COVER					
"MEADOWS"	B	0.30	0.30	1.000	70
NATURAL FAIR COVER					
"OPEN BRUSH"	B	17.90	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.20	0.30	1.000	66
PUBLIC PARK	B	0.30	0.30	0.850	56
NATURAL POOR COVER					
"BARREN"	B	0.70	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.993

SUBAREA AREA(ACRES) = 19.50 SUBAREA RUNOFF(CFS) = 7.10

EFFECTIVE AREA(ACRES) = 34789.54 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA (ACRES) = 50815.4 PEAK FLOW RATE (CFS) = 22819.28  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 98.44

\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.703

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL "5-7 DWELLINGS/ACRE"	B	0.10	0.30	0.500	56
NATURAL FAIR COVER "WOODLAND, GRASS"	B	1.10	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.90	0.30	1.000	65
RESIDENTIAL ".4 DWELLING/ACRE"	B	0.60	0.30	0.900	56
RESIDENTIAL ".4 DWELLING/ACRE"	B	0.30	0.30	0.900	56
NATURAL POOR COVER "BARREN"	B	0.50	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.960

SUBAREA AREA (ACRES) = 3.50 SUBAREA RUNOFF (CFS) = 1.31

EFFECTIVE AREA (ACRES) = 34793.04 AREA-AVERAGED Fm (INCH/HR) = 0.30

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA (ACRES) = 50818.9 PEAK FLOW RATE (CFS) = 22819.28

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 3D10EVRL.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	561.19	20.88	0.30 (0.14)	0.48	353.9	413.00
2	562.98	27.77	0.30 (0.14)	0.48	431.2	430.00
3	540.81	29.73	0.30 (0.14)	0.48	439.5	400.00
TOTAL AREA (ACRES) =						439.5

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	13180.11	23.80	1.455	0.30 (0.28)	0.94	4526.5	40500.00

2	14132.37	28.20	1.312	0.30 (0.28)	0.94	5774.8	12710.00
3	14852.14	31.76	1.228	0.30 (0.28)	0.95	6741.0	40200.00
4	16945.68	47.03	0.996	0.30 (0.29)	0.97	11749.5	40100.00
5	17928.67	57.85	0.892	0.30 (0.29)	0.97	15014.8	11801.00
6	19349.92	71.73	0.816	0.30 (0.29)	0.98	20009.2	11530.00
7	20306.56	80.10	0.775	0.30 (0.29)	0.98	23877.3	11900.00
8	21908.83	90.09	0.726	0.30 (0.30)	0.98	29705.9	11330.00
9	22819.28	98.44	0.703	0.30 (0.30)	0.99	34793.0	10630.00
10	22760.92	104.01	0.687	0.30 (0.30)	0.99	37382.9	12330.00
11	22685.68	110.60	0.669	0.30 (0.30)	0.99	40525.4	11600.00
12	22460.97	116.32	0.653	0.30 (0.30)	0.99	42759.7	11111.00
13	22194.71	122.39	0.639	0.30 (0.30)	0.99	44693.5	12201.00
14	21891.09	126.19	0.632	0.30 (0.30)	0.99	45641.3	10410.00
15	21493.94	131.16	0.624	0.30 (0.30)	0.99	46781.8	12231.00
16	20836.42	138.49	0.611	0.30 (0.30)	0.99	48193.3	10400.00
17	20433.49	142.35	0.605	0.30 (0.30)	0.99	48783.5	10200.00
18	19774.94	149.63	0.592	0.30 (0.30)	0.99	49814.1	10320.00
19	19212.54	154.34	0.584	0.30 (0.30)	0.99	50039.6	10210.00
20	18727.45	159.08	0.576	0.30 (0.30)	0.99	50201.9	12000.00
21	16179.34	187.48	0.534	0.30 (0.30)	0.99	50818.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108682.05 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	561.19	20.88	1.576	0.30 (0.14)	0.48	353.9	413.00
2	562.98	27.77	1.325	0.30 (0.14)	0.48	431.2	430.00
3	540.81	29.73	1.268	0.30 (0.14)	0.48	439.5	400.00

LONGEST FLOWPATH FROM NODE 430.00 TO NODE 12720.50 = 11352.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	13315.08	20.88	1.576	0.30 (0.27)	0.90	4325.0	413.00
2	13742.06	23.80	1.455	0.30 (0.27)	0.90	4913.2	40500.00
3	14602.68	27.77	1.325	0.30 (0.27)	0.91	6084.5	430.00
4	14690.51	28.20	1.312	0.30 (0.27)	0.91	6207.8	12710.00
5	14982.85	29.73	1.268	0.30 (0.27)	0.91	6630.0	400.00
6	15373.85	31.76	1.228	0.30 (0.28)	0.92	7180.5	40200.00
7	17355.76	47.03	0.996	0.30 (0.29)	0.95	12189.0	40100.00
8	18288.67	57.85	0.892	0.30 (0.29)	0.96	15454.3	11801.00
9	19673.16	71.73	0.816	0.30 (0.29)	0.97	20448.7	11530.00
10	20610.09	80.10	0.775	0.30 (0.29)	0.97	24316.8	11900.00
11	22188.90	90.09	0.726	0.30 (0.29)	0.98	30145.4	11330.00
12	23088.23	98.44	0.703	0.30 (0.29)	0.98	35232.5	10630.00
13	23022.46	104.01	0.687	0.30 (0.29)	0.98	37822.4	12330.00
14	22938.46	110.60	0.669	0.30 (0.29)	0.98	40964.9	11600.00
15	22706.13	116.32	0.653	0.30 (0.29)	0.98	43199.2	11111.00
16	22433.00	122.39	0.639	0.30 (0.29)	0.98	45133.0	12201.00
17	22126.24	126.19	0.632	0.30 (0.29)	0.98	46080.8	10410.00
18	21724.98	131.16	0.624	0.30 (0.29)	0.98	47221.3	12231.00
19	21061.41	138.49	0.611	0.30 (0.29)	0.98	48632.8	10400.00
20	20655.30	142.35	0.605	0.30 (0.29)	0.98	49223.0	10200.00
21	19990.73	149.63	0.592	0.30 (0.29)	0.98	50253.6	10320.00
22	19424.44	154.34	0.584	0.30 (0.29)	0.98	50479.1	10210.00
23	18935.45	159.08	0.576	0.30 (0.29)	0.98	50641.4	12000.00
24	16367.26	187.48	0.534	0.30 (0.29)	0.98	51258.4	10100.00

TOTAL AREA (ACRES) = 51258.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 23088.23 Tc(MIN.) = 98.443
EFFECTIVE AREA(ACRES) = 35232.54 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 51258.4
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108682.05 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

\*\*\*\*\*
FLOW PROCESS FROM NODE 12720.50 TO NODE 12721.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 258.00 DOWNSTREAM(FEET) = 256.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 438.77 CHANNEL SLOPE = 0.0046
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
\*ESTIMATED CHANNEL HEIGHT(FEET) = 8.00
CHANNEL FLOW THRU SUBAREA(CFS) = 23088.23
FLOW VELOCITY(FEET/SEC.) = 12.02 FLOW DEPTH(FEET) = 8.00
TRAVEL TIME(MIN.) = 0.61 Tc(MIN.) = 99.05
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12721.00 = 109120.82 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 12721.00 TO NODE 12722.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 256.00 DOWNSTREAM(FEET) = 255.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 830.42 CHANNEL SLOPE = 0.0012
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
\*ESTIMATED CHANNEL HEIGHT(FEET) = 11.65
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.696
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
COMMERCIAL B 11.24 0.30 0.100 56
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 23091.60
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.68
AVERAGE FLOW DEPTH(FEET) = 11.65 TRAVEL TIME(MIN.) = 1.80
Tc(MIN.) = 100.85
SUBAREA AREA(ACRES) = 11.24 SUBAREA RUNOFF(CFS) = 6.74
EFFECTIVE AREA(ACRES) = 35243.78 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
TOTAL AREA(ACRES) = 51269.7 PEAK FLOW RATE(CFS) = 23088.23
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
\*ESTIMATED CHANNEL HEIGHT(FEET) = 11.65

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 11.65 FLOW VELOCITY(FEET/SEC.) = 7.68
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12722.00 = 109951.24 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 12722.00 TO NODE 12722.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 100.85
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.696
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL POOR COVER
"BARREN" B 2.10 0.30 1.000 86
NATURAL FAIR COVER
"GRASS" B 0.10 0.30 1.000 69
NATURAL FAIR COVER
"MEADOWS" B 3.60 0.30 1.000 70
NATURAL FAIR COVER
"OPEN BRUSH" B 4.10 0.30 1.000 66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 9.90 SUBAREA RUNOFF(CFS) = 3.53
EFFECTIVE AREA(ACRES) = 35253.68 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
TOTAL AREA(ACRES) = 51279.6 PEAK FLOW RATE(CFS) = 23088.23
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*
FLOW PROCESS FROM NODE 12722.00 TO NODE 12722.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 100.85
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.696
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
RESIDENTIAL
".4 DWELLING/ACRE" B 0.60 0.30 0.900 56
NATURAL FAIR COVER
"WOODLAND,GRASS" B 1.90 0.30 1.000 65
NATURAL FAIR COVER
"WOODLAND,GRASS" B 0.10 0.30 1.000 65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.977
SUBAREA AREA(ACRES) = 2.60 SUBAREA RUNOFF(CFS) = 0.94
EFFECTIVE AREA(ACRES) = 35256.28 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
TOTAL AREA(ACRES) = 51282.2 PEAK FLOW RATE(CFS) = 23088.23
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12722.00 TO NODE 12740.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 255.00 DOWNSTREAM(FEET) = 252.10
CHANNEL LENGTH THRU SUBAREA(FEET) = 624.00 CHANNEL SLOPE = 0.0046
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
\*ESTIMATED CHANNEL HEIGHT(FEET) = 7.95
\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.694

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include COMMERCIAL, NATURAL FAIR COVER "GRASS", and "WOODLAND, GRASS".

SUBAREA LOSS RATE DATA(AMC II):
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.925
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 23091.58
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.11
AVERAGE FLOW DEPTH(FEET) = 7.95 TRAVEL TIME (MIN.) = 0.86
Tc (MIN.) = 101.71
SUBAREA AREA (ACRES) = 17.90 SUBAREA RUNOFF (CFS) = 6.71
EFFECTIVE AREA (ACRES) = 35274.18 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
TOTAL AREA (ACRES) = 51300.1 PEAK FLOW RATE (CFS) = 23088.23
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
\*ESTIMATED CHANNEL HEIGHT(FEET) = 7.95

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 7.95 FLOW VELOCITY(FEET/SEC.) = 12.11
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12740.00 = 110575.24 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 101.71
\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.694
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include NATURAL FAIR COVER "OPEN BRUSH".

NATURAL FAIR COVER
"OPEN BRUSH" B 12.00 0.30 1.000 66
NATURAL FAIR COVER
"CHAPARRAL, BROADLEAF" B 0.80 0.30 1.000 63
NATURAL FAIR COVER
"CHAPARRAL, BROADLEAF" B 20.20 0.30 1.000 63
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 44.40 SUBAREA RUNOFF (CFS) = 15.73
EFFECTIVE AREA (ACRES) = 35318.57 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
TOTAL AREA (ACRES) = 51344.4 PEAK FLOW RATE (CFS) = 23088.23
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*
FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION (MIN.) = 101.71
RAINFALL INTENSITY (INCH/HR) = 0.69
AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.98
EFFECTIVE STREAM AREA (ACRES) = 35318.57
TOTAL STREAM AREA (ACRES) = 51344.45
PEAK FLOW RATE (CFS) AT CONFLUENCE = 23088.23

\*\*\*\*\*
FLOW PROCESS FROM NODE 12730.00 TO NODE 12731.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH (FEET) = 561.54
ELEVATION DATA: UPSTREAM (FEET) = 613.29 DOWNSTREAM (FEET) = 551.75

Tc = K \* [(LENGTH \*\* 3.00) / (ELEVATION CHANGE)] \*\* 0.20
SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 13.823
\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 2.044

SUBAREA Tc AND LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN, Tc (MIN.). Rows include NATURAL FAIR COVER "CHAPARRAL, BROADLEAF".

\*\*\*\*\*
FLOW PROCESS FROM NODE 12731.00 TO NODE 12732.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<



ELEVATION DATA: UPSTREAM(FEET) = 551.75 DOWNSTREAM(FEET) = 494.40  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 971.91 CHANNEL SLOPE = 0.0590  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.73  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.747  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 COMMERCIAL B 34.62 0.30 0.100 56  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 36.72  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.40  
 AVERAGE FLOW DEPTH(FEET) = 0.73 TRAVEL TIME(MIN.) = 3.68  
 Tc(MIN.) = 17.50  
 SUBAREA AREA(ACRES) = 34.62 SUBAREA RUNOFF(CFS) = 53.51  
 EFFECTIVE AREA(ACRES) = 40.95 AREA-AVERAGED Fm(INCH/HR) = 0.07  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.24  
 TOTAL AREA(ACRES) = 40.9 PEAK FLOW RATE(CFS) = 61.76  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.98  
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 0.98 FLOW VELOCITY(FEET/SEC.) = 5.26  
 LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12732.00 = 1533.45 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12732.00 TO NODE 12733.00 IS CODE = 56  
 -----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 494.40 DOWNSTREAM(FEET) = 431.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1156.41 CHANNEL SLOPE = 0.0548  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.37  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.584  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 COMMERCIAL B 59.52 0.30 0.100 56  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 103.40  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.05  
 AVERAGE FLOW DEPTH(FEET) = 1.35 TRAVEL TIME(MIN.) = 3.18  
 Tc(MIN.) = 20.68  
 SUBAREA AREA(ACRES) = 59.52 SUBAREA RUNOFF(CFS) = 83.23  
 EFFECTIVE AREA(ACRES) = 100.47 AREA-AVERAGED Fm(INCH/HR) = 0.05  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.16  
 TOTAL AREA(ACRES) = 100.5 PEAK FLOW RATE(CFS) = 138.95  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.59

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.59 FLOW VELOCITY(FEET/SEC.) = 6.63  
 LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12733.00 = 2689.86 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12733.00 TO NODE 12734.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 431.00 DOWNSTREAM(FEET) = 367.10  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1654.48 CHANNEL SLOPE = 0.0386  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 2.04  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.404  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 COMMERCIAL B 64.05 0.30 0.100 56  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 178.58  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.33  
 AVERAGE FLOW DEPTH(FEET) = 2.01 TRAVEL TIME(MIN.) = 4.35  
 Tc(MIN.) = 25.04  
 SUBAREA AREA(ACRES) = 64.05 SUBAREA RUNOFF(CFS) = 79.20  
 EFFECTIVE AREA(ACRES) = 164.52 AREA-AVERAGED Fm(INCH/HR) = 0.04  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.13  
 TOTAL AREA(ACRES) = 164.5 PEAK FLOW RATE(CFS) = 201.89  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 2.15

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 2.15 FLOW VELOCITY(FEET/SEC.) = 6.57  
 LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12734.00 = 4344.34 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12734.00 TO NODE 12740.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 367.11 DOWNSTREAM(FEET) = 252.10  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1880.98 CHANNEL SLOPE = 0.0611  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.98  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.289  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 COMMERCIAL B 26.02 0.30 0.100 56  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 216.63  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.88

AVERAGE FLOW DEPTH (FEET) = 1.97 TRAVEL TIME (MIN.) = 3.98  
 Tc (MIN.) = 29.02  
 SUBAREA AREA (ACRES) = 26.02 SUBAREA RUNOFF (CFS) = 29.47  
 EFFECTIVE AREA (ACRES) = 190.54 AREA-AVERAGED Fm (INCH/HR) = 0.04  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.13  
 TOTAL AREA (ACRES) = 190.5 PEAK FLOW RATE (CFS) = 214.28  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 1.96

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 1.96 FLOW VELOCITY (FEET/SEC.) = 7.86  
 LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12740.00 = 6225.32 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====  
 TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
 TIME OF CONCENTRATION (MIN.) = 29.02  
 RAINFALL INTENSITY (INCH/HR) = 1.29  
 AREA-AVERAGED Fm (INCH/HR) = 0.04  
 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.13  
 EFFECTIVE STREAM AREA (ACRES) = 190.54  
 TOTAL STREAM AREA (ACRES) = 190.54  
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 214.28

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13315.08	24.80	1.413	0.30 ( 0.27)	0.90	4411.0	413.00
1	13742.06	27.68	1.327	0.30 ( 0.27)	0.90	4999.2	40500.00
1	14602.68	31.57	1.232	0.30 ( 0.27)	0.91	6170.6	430.00
1	14690.51	31.99	1.224	0.30 ( 0.27)	0.91	6293.9	12710.00
1	14982.85	33.50	1.197	0.30 ( 0.27)	0.91	6716.0	400.00
1	15373.85	35.50	1.160	0.30 ( 0.28)	0.92	7266.5	40200.00
1	17355.76	50.62	0.956	0.30 ( 0.28)	0.95	12275.1	40100.00
1	18288.67	61.38	0.866	0.30 ( 0.29)	0.96	15540.3	11801.00
1	19673.16	75.18	0.799	0.30 ( 0.29)	0.97	20534.7	11530.00
1	20610.09	83.49	0.758	0.30 ( 0.29)	0.97	24402.8	11900.00
1	22188.90	93.40	0.717	0.30 ( 0.29)	0.98	30231.4	11330.00
1	23088.23	101.71	0.694	0.30 ( 0.29)	0.98	35318.6	10630.00
1	23022.46	107.28	0.678	0.30 ( 0.29)	0.98	37908.4	12330.00
1	22938.46	113.87	0.660	0.30 ( 0.29)	0.98	41050.9	11600.00
1	22706.13	119.61	0.644	0.30 ( 0.29)	0.98	43285.2	11111.00
1	22433.00	125.69	0.633	0.30 ( 0.29)	0.98	45219.1	12201.00
1	22126.24	129.50	0.627	0.30 ( 0.29)	0.98	46166.9	10410.00
1	21724.98	134.49	0.618	0.30 ( 0.29)	0.98	47307.3	12231.00
1	21061.41	141.86	0.605	0.30 ( 0.29)	0.98	48718.9	10400.00
1	20655.30	145.74	0.599	0.30 ( 0.29)	0.98	49309.1	10200.00
1	19990.73	153.06	0.586	0.30 ( 0.29)	0.98	50339.6	10320.00
1	19424.44	157.80	0.578	0.30 ( 0.29)	0.98	50565.1	10210.00
1	18935.45	162.56	0.570	0.30 ( 0.29)	0.98	50727.5	12000.00
1	16367.26	191.14	0.531	0.30 ( 0.29)	0.98	51344.4	10100.00

2	214.28	29.02	1.289	0.30 ( 0.04)	0.13	190.5	12730.00
---	--------	-------	-------	--------------	------	-------	----------

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13516.51	24.80	1.413	0.30 ( 0.26)	0.87	4573.9	413.00
2	13952.81	27.68	1.327	0.30 ( 0.26)	0.87	5181.0	40500.00
3	14252.06	29.02	1.289	0.30 ( 0.26)	0.88	5592.3	12730.00
4	14807.19	31.57	1.232	0.30 ( 0.27)	0.89	6361.1	430.00
5	14893.71	31.99	1.224	0.30 ( 0.27)	0.89	6484.4	12710.00
6	15181.37	33.50	1.197	0.30 ( 0.27)	0.89	6906.6	400.00
7	15566.16	35.50	1.160	0.30 ( 0.27)	0.90	7457.1	40200.00
8	17512.93	50.62	0.956	0.30 ( 0.28)	0.94	12465.6	40100.00
9	18430.53	61.38	0.866	0.30 ( 0.28)	0.95	15730.9	11801.00
10	19803.43	75.18	0.799	0.30 ( 0.29)	0.96	20725.2	11530.00
11	20733.38	83.49	0.758	0.30 ( 0.29)	0.97	24593.4	11900.00
12	22305.11	93.40	0.717	0.30 ( 0.29)	0.97	30422.0	11330.00
13	23200.49	101.71	0.694	0.30 ( 0.29)	0.97	35509.1	10630.00
14	23132.08	107.28	0.678	0.30 ( 0.29)	0.98	38099.0	12330.00
15	23044.94	113.87	0.660	0.30 ( 0.29)	0.98	41241.4	11600.00
16	22809.90	119.61	0.644	0.30 ( 0.29)	0.98	43475.8	11111.00
17	22534.91	125.69	0.633	0.30 ( 0.29)	0.98	45409.6	12201.00
18	22227.03	129.50	0.627	0.30 ( 0.29)	0.98	46357.4	10410.00
19	21824.30	134.49	0.618	0.30 ( 0.29)	0.98	47497.9	12231.00
20	21158.56	141.86	0.605	0.30 ( 0.29)	0.98	48909.4	10400.00
21	20751.31	145.74	0.599	0.30 ( 0.29)	0.98	49499.6	10200.00
22	20084.58	153.06	0.586	0.30 ( 0.29)	0.98	50530.2	10320.00
23	19516.89	157.80	0.578	0.30 ( 0.29)	0.98	50755.6	10210.00
24	19026.50	162.56	0.570	0.30 ( 0.29)	0.98	50918.0	12000.00
25	16451.69	191.14	0.531	0.30 ( 0.29)	0.98	51535.0	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:  
 PEAK FLOW RATE (CFS) = 23200.49 Tc (MIN.) = 101.71  
 EFFECTIVE AREA (ACRES) = 35509.11 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97  
 TOTAL AREA (ACRES) = 51535.0  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12740.00 = 110575.24 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12740.00 TO NODE 12741.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====  
 ELEVATION DATA: UPSTREAM (FEET) = 252.10 DOWNSTREAM (FEET) = 247.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 401.47 CHANNEL SLOPE = 0.0127  
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 5.98  
 CHANNEL FLOW THRU SUBAREA (CFS) = 23200.49  
 FLOW VELOCITY (FEET/SEC.) = 16.89 FLOW DEPTH (FEET) = 5.98  
 TRAVEL TIME (MIN.) = 0.40 Tc (MIN.) = 102.11  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12741.00 = 110976.71 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 102.11

\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.692

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	2.10	0.30	0.100	56
NATURAL FAIR COVER "GRASS"	B	7.50	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	0.90	0.30	1.000	66
PUBLIC PARK	B	1.90	0.30	0.850	56
RESIDENTIAL ".4 DWELLING/ACRE"	B	0.40	0.30	0.900	56
AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	0.50	0.30	1.000	79

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.833

SUBAREA AREA(ACRES) = 13.30 SUBAREA RUNOFF(CFS) = 5.30

EFFECTIVE AREA(ACRES) = 35522.41 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97

TOTAL AREA(ACRES) = 51548.3 PEAK FLOW RATE(CFS) = 23200.49

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 102.11

\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.692

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.90	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 0.90 SUBAREA RUNOFF(CFS) = 0.32

EFFECTIVE AREA(ACRES) = 35523.31 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97

TOTAL AREA(ACRES) = 51549.2 PEAK FLOW RATE(CFS) = 23200.49

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<

PEAK FLOWRATE TABLE FILE NAME: 3C10EVRL.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	919.94	18.68	0.30( 0.14)	0.47	635.0	300.00
2	940.82	24.12	0.30( 0.14)	0.47	773.9	327.00

3	925.53	25.14	0.30( 0.14)	0.48	786.2	350.00
4	904.98	26.49	0.30( 0.14)	0.48	799.6	320.00
5	846.49	30.50	0.30( 0.15)	0.49	825.3	306.00
6	758.97	39.49	0.30( 0.15)	0.50	870.6	390.00
TOTAL AREA(ACRES) =					870.6	

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13516.51	25.28	1.397	0.30( 0.26)	0.87	4588.1	413.00
2	13952.81	28.15	1.314	0.30( 0.26)	0.87	5195.2	40500.00
3	14252.06	29.49	1.275	0.30( 0.26)	0.88	5606.5	12730.00
4	14807.19	32.04	1.223	0.30( 0.27)	0.89	6375.3	430.00
5	14893.71	32.46	1.216	0.30( 0.27)	0.89	6498.6	12710.00
6	15181.37	33.96	1.188	0.30( 0.27)	0.89	6920.8	400.00
7	15566.16	35.96	1.152	0.30( 0.27)	0.90	7471.3	40200.00
8	17512.93	51.06	0.952	0.30( 0.28)	0.94	12479.8	40100.00
9	18430.53	61.81	0.864	0.30( 0.28)	0.95	15745.1	11801.00
10	19803.43	75.60	0.797	0.30( 0.29)	0.96	20739.4	11530.00
11	20733.38	83.90	0.756	0.30( 0.29)	0.97	24607.6	11900.00
12	22305.11	93.80	0.715	0.30( 0.29)	0.97	30436.2	11330.00
13	23200.49	102.11	0.692	0.30( 0.29)	0.97	35523.3	10630.00
14	23132.08	107.68	0.677	0.30( 0.29)	0.98	38113.2	12330.00
15	23044.94	114.27	0.659	0.30( 0.29)	0.98	41255.6	11600.00
16	22809.90	120.01	0.643	0.30( 0.29)	0.98	43490.0	11111.00
17	22534.91	126.09	0.633	0.30( 0.29)	0.98	45423.8	12201.00
18	22227.03	129.90	0.626	0.30( 0.29)	0.98	46371.6	10410.00
19	21824.30	134.90	0.617	0.30( 0.29)	0.98	47512.1	12231.00
20	21158.56	142.27	0.605	0.30( 0.29)	0.98	48923.6	10400.00
21	20751.31	146.15	0.598	0.30( 0.29)	0.98	49513.8	10200.00
22	20084.58	153.47	0.586	0.30( 0.29)	0.98	50544.4	10320.00
23	19516.89	158.22	0.577	0.30( 0.29)	0.98	50769.8	10210.00
24	19026.50	162.99	0.569	0.30( 0.29)	0.98	50932.2	12000.00
25	16451.69	191.59	0.531	0.30( 0.29)	0.98	51549.2	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12741.00 = 110976.71 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	919.94	18.68	1.683	0.30( 0.14)	0.47	635.0	300.00
2	940.82	24.12	1.441	0.30( 0.14)	0.47	773.9	327.00
3	925.53	25.14	1.401	0.30( 0.14)	0.48	786.2	350.00
4	904.98	26.49	1.362	0.30( 0.14)	0.48	799.6	320.00
5	846.49	30.50	1.251	0.30( 0.15)	0.49	825.3	306.00
6	758.97	39.49	1.088	0.30( 0.15)	0.50	870.6	390.00

LONGEST FLOWPATH FROM NODE 390.00 TO NODE 12741.00 = 15238.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13430.70	18.68	1.683	0.30( 0.24)	0.81	4026.3	300.00
2	14344.12	24.12	1.441	0.30( 0.24)	0.81	5152.8	327.00

3	14415.18	25.14	1.401	0.30	( 0.24)	0.81	5348.8	350.00
4	14439.92	25.28	1.397	0.30	( 0.24)	0.81	5375.6	413.00
5	14606.21	26.49	1.362	0.30	( 0.25)	0.82	5644.7	320.00
6	14833.62	28.15	1.314	0.30	( 0.25)	0.82	6005.4	40500.00
7	15113.40	29.49	1.275	0.30	( 0.25)	0.83	6425.3	12730.00
8	15319.99	30.50	1.251	0.30	( 0.25)	0.83	6738.5	306.00
9	15638.75	32.04	1.223	0.30	( 0.25)	0.84	7208.4	430.00
10	15721.18	32.46	1.216	0.30	( 0.25)	0.84	7333.8	12710.00
11	15994.17	33.96	1.188	0.30	( 0.25)	0.85	7763.5	400.00
12	16359.51	35.96	1.152	0.30	( 0.26)	0.86	8324.1	40200.00
13	16780.20	39.49	1.088	0.30	( 0.26)	0.87	9512.6	390.00
14	18161.31	51.06	0.952	0.30	( 0.27)	0.91	13350.4	40100.00
15	19008.04	61.81	0.864	0.30	( 0.28)	0.93	16615.7	11801.00
16	20326.24	75.60	0.797	0.30	( 0.28)	0.94	21610.0	11530.00
17	21223.24	83.90	0.756	0.30	( 0.28)	0.95	25478.2	11900.00
18	22762.27	93.80	0.715	0.30	( 0.29)	0.96	31306.8	11330.00
19	23639.03	102.11	0.692	0.30	( 0.29)	0.96	36393.9	10630.00
20	23558.16	107.68	0.677	0.30	( 0.29)	0.97	38983.8	12330.00
21	23456.24	114.27	0.659	0.30	( 0.29)	0.97	42126.2	11600.00
22	23208.37	120.01	0.643	0.30	( 0.29)	0.97	44360.6	11111.00
23	22924.92	126.09	0.633	0.30	( 0.29)	0.97	46294.4	12201.00
24	22611.73	129.90	0.626	0.30	( 0.29)	0.97	47242.2	10410.00
25	22202.06	134.90	0.617	0.30	( 0.29)	0.97	48382.7	12231.00
26	21526.08	142.27	0.605	0.30	( 0.29)	0.97	49794.2	10400.00
27	21113.43	146.15	0.598	0.30	( 0.29)	0.97	50384.4	10200.00
28	20436.53	153.47	0.586	0.30	( 0.29)	0.97	51415.0	10320.00
29	19862.24	158.22	0.577	0.30	( 0.29)	0.97	51640.4	10210.00
30	19365.21	162.99	0.569	0.30	( 0.29)	0.97	51802.8	12000.00
31	16759.47	191.59	0.531	0.30	( 0.29)	0.97	52419.8	10100.00

TOTAL AREA (ACRES) = 52419.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 23639.03 Tc(MIN.) = 102.109  
EFFECTIVE AREA(ACRES) = 36393.91 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.87  
TOTAL AREA(ACRES) = 52419.8  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12741.00 = 110976.71 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 2 <<<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12741.00 TO NODE 12800.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 247.00 DOWNSTREAM(FEET) = 240.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 819.00 CHANNEL SLOPE = 0.0085  
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.77  
CHANNEL FLOW THRU SUBAREA(CFS) = 23639.03  
FLOW VELOCITY(FEET/SEC.) = 14.93 FLOW DEPTH(FEET) = 6.77  
TRAVEL TIME(MIN.) = 0.91 Tc(MIN.) = 103.02

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111795.71 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<

-----  
MAINLINE Tc(MIN.) = 103.02  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.690  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCSSOIL AREA Fp Ap SCSS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
NATURAL FAIR COVER  
"GRASS" B 17.31 0.30 1.000 69  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA(ACRES) = 17.31 SUBAREA RUNOFF(CFS) = 6.08  
EFFECTIVE AREA(ACRES) = 36411.22 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA(ACRES) = 52437.1 PEAK FLOW RATE(CFS) = 23639.03  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
-----

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 52437.1 TC(MIN.) = 103.02  
EFFECTIVE AREA(ACRES) = 36411.22 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.963  
PEAK FLOW RATE(CFS) = 23639.03

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13430.70	19.80	1.623	0.30( 0.24)	0.81	4043.6	300.00
2	14344.12	25.21	1.399	0.30( 0.24)	0.81	5170.1	327.00
3	14415.18	26.22	1.370	0.30( 0.24)	0.81	5366.1	350.00
4	14439.92	26.36	1.365	0.30( 0.24)	0.81	5393.0	413.00
5	14606.21	27.57	1.330	0.30( 0.25)	0.82	5662.0	320.00
6	14833.62	29.23	1.282	0.30( 0.25)	0.82	6022.7	40500.00
7	15113.40	30.55	1.250	0.30( 0.25)	0.83	6442.6	12730.00
8	15319.99	31.57	1.232	0.30( 0.25)	0.83	6755.8	306.00
9	15638.75	33.09	1.204	0.30( 0.25)	0.84	7225.7	430.00
10	15721.18	33.51	1.196	0.30( 0.25)	0.84	7351.1	12710.00
11	15994.17	35.01	1.169	0.30( 0.25)	0.85	7780.8	400.00
12	16359.51	37.00	1.133	0.30( 0.26)	0.86	8341.4	40200.00
13	16780.20	40.52	1.073	0.30( 0.26)	0.87	9530.0	390.00
14	18161.31	52.06	0.943	0.30( 0.27)	0.91	13367.7	40100.00
15	19008.04	62.79	0.859	0.30( 0.28)	0.93	16633.0	11801.00
16	20326.24	76.56	0.792	0.30( 0.28)	0.94	21627.3	11530.00
17	21223.24	84.85	0.751	0.30( 0.28)	0.95	25495.5	11900.00
18	22762.27	94.73	0.713	0.30( 0.29)	0.96	31324.1	11330.00
19	23639.03	103.02	0.690	0.30( 0.29)	0.96	36411.2	10630.00
20	23558.16	108.59	0.675	0.30( 0.29)	0.97	39001.1	12330.00
21	23456.24	115.19	0.656	0.30( 0.29)	0.97	42143.5	11600.00
22	23208.37	120.93	0.641	0.30( 0.29)	0.97	44377.9	11111.00
23	22924.92	127.01	0.631	0.30( 0.29)	0.97	46311.7	12201.00
24	22611.73	130.83	0.624	0.30( 0.29)	0.97	47259.5	10410.00
25	22202.06	135.83	0.616	0.30( 0.29)	0.97	48400.0	12231.00
26	21526.08	143.21	0.603	0.30( 0.29)	0.97	49811.5	10400.00
27	21113.43	147.10	0.596	0.30( 0.29)	0.97	50401.7	10200.00

28	20436.53	154.43	0.584	0.30	( 0.29)	0.97	51432.3	10320.00
29	19862.24	159.19	0.576	0.30	( 0.29)	0.97	51657.8	10210.00
30	19365.21	163.97	0.568	0.30	( 0.29)	0.97	51820.1	12000.00
31	16759.47	192.61	0.530	0.30	( 0.29)	0.97	52437.1	10100.00

=====  
=====  
END OF RATIONAL METHOD ANALYSIS

\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S28- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 10-YR RM EV APRIL 2019 CCHIUI \*  
\*\*\*\*\*

FILE NAME: RI10EV28.DAT  
TIME/DATE OF STUDY: 10:15 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 10.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 3.867
- 2) 10.00; 2.568
- 3) 15.00; 1.883
- 4) 20.00; 1.612
- 5) 25.00; 1.405
- 6) 30.00; 1.260
- 7) 40.00; 1.079
- 8) 50.00; 0.961
- 9) 60.00; 0.873
- 10) 90.00; 0.726
- 11) 120.00; 0.643
- 12) 180.00; 0.540
- 13) 360.00; 0.400
- 14) 1200.00; 0.176

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI10EV27.DNA  
MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13430.70	19.80	0.30 ( 0.24)	0.81	4043.6	300.00
2	15319.99	31.57	0.30 ( 0.25)	0.83	6755.8	306.00
3	16780.20	40.52	0.30 ( 0.26)	0.87	9530.0	390.00
4	18161.31	52.06	0.30 ( 0.27)	0.91	13367.7	40100.00
5	19008.04	62.79	0.30 ( 0.28)	0.93	16633.0	11801.00
6	20326.24	76.56	0.30 ( 0.28)	0.94	21627.3	11530.00
7	21223.24	84.85	0.30 ( 0.28)	0.95	25495.5	11900.00
8	22762.27	94.73	0.30 ( 0.29)	0.96	31324.1	11330.00
9	23639.03	103.02	0.30 ( 0.29)	0.96	36411.2	10630.00
10	23558.16	108.59	0.30 ( 0.29)	0.97	39001.1	12330.00
11	23456.24	115.19	0.30 ( 0.29)	0.97	42143.5	11600.00
12	23208.37	120.93	0.30 ( 0.29)	0.97	44377.9	11111.00
13	22924.92	127.01	0.30 ( 0.29)	0.97	46311.7	12201.00
14	22202.06	135.83	0.30 ( 0.29)	0.97	48400.0	12231.00
15	21526.08	143.21	0.30 ( 0.29)	0.97	49811.5	10400.00
16	21113.43	147.10	0.30 ( 0.29)	0.97	50401.7	10200.00
17	20436.53	154.43	0.30 ( 0.29)	0.97	51432.3	10320.00
18	19862.24	159.19	0.30 ( 0.29)	0.97	51657.8	10210.00
19	19365.21	163.97	0.30 ( 0.29)	0.97	51820.1	12000.00
20	16759.47	192.61	0.30 ( 0.29)	0.97	52437.1	10100.00
TOTAL AREA (ACRES) =						52437.1

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 0610501V.DNA  
MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	980.25	27.73	0.30 ( 0.29)	0.98	1026.3	50120.00
2	957.41	29.15	0.30 ( 0.29)	0.98	1042.7	50150.00
3	896.35	32.55	0.30 ( 0.29)	0.98	1063.4	50100.00
TOTAL AREA (ACRES) =						1063.4

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 3 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM	Q	Tc	Fp (Fm)	Ap	Ae	HEADWATER
--------	---	----	---------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(ACRES)	NODE
1	980.25	27.73	0.30 ( 0.29)	0.98	1026.3
2	957.41	29.15	0.30 ( 0.29)	0.98	1042.7
3	896.35	32.55	0.30 ( 0.29)	0.98	1063.4
TOTAL AREA (ACRES) =			1063.4		

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 11

-----  
 >>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<  
 =====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	980.25	27.73	1.326	0.30 ( 0.29)	0.98	1026.3	50120.00
2	957.41	29.15	1.285	0.30 ( 0.29)	0.98	1042.7	50150.00
3	896.35	32.55	1.214	0.30 ( 0.29)	0.98	1063.4	50100.00

LONGEST FLOWPATH FROM NODE 50150.00 TO NODE 12800.00 = 11349.00 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13430.70	19.80	1.623	0.30 ( 0.24)	0.81	4043.6	300.00
2	15319.99	31.57	1.232	0.30 ( 0.25)	0.83	6755.8	306.00
3	16780.20	40.52	1.073	0.30 ( 0.26)	0.87	9530.0	390.00
4	18161.31	52.06	0.943	0.30 ( 0.27)	0.91	13367.7	40100.00
5	19008.04	62.79	0.859	0.30 ( 0.28)	0.93	16633.0	11801.00
6	20326.24	76.56	0.792	0.30 ( 0.28)	0.94	21627.3	11530.00
7	21223.24	84.85	0.751	0.30 ( 0.28)	0.95	25495.5	11900.00
8	22762.27	94.73	0.713	0.30 ( 0.29)	0.96	31324.1	11330.00
9	23639.03	103.02	0.690	0.30 ( 0.29)	0.96	36411.2	10630.00
10	23558.16	108.59	0.675	0.30 ( 0.29)	0.97	39001.1	12330.00
11	23456.24	115.19	0.656	0.30 ( 0.29)	0.97	42143.5	11600.00
12	23208.37	120.93	0.641	0.30 ( 0.29)	0.97	44377.9	11111.00
13	22924.92	127.01	0.631	0.30 ( 0.29)	0.97	46311.7	12201.00
14	22202.06	135.83	0.616	0.30 ( 0.29)	0.97	48400.0	12231.00
15	21526.08	143.21	0.603	0.30 ( 0.29)	0.97	49811.5	10400.00
16	21113.43	147.10	0.596	0.30 ( 0.29)	0.97	50401.7	10200.00
17	20436.53	154.43	0.584	0.30 ( 0.29)	0.97	51432.3	10320.00
18	19862.24	159.19	0.576	0.30 ( 0.29)	0.97	51657.8	10210.00
19	19365.21	163.97	0.568	0.30 ( 0.29)	0.97	51820.1	12000.00
20	16759.47	192.61	0.530	0.30 ( 0.29)	0.97	52437.1	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111795.71 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14332.12	19.80	1.623	0.30 ( 0.25)	0.84	4776.3	300.00
2	15684.42	27.73	1.326	0.30 ( 0.25)	0.85	6898.1	50120.00
3	15889.72	29.15	1.285	0.30 ( 0.25)	0.85	7241.9	50150.00
4	16234.04	31.57	1.232	0.30 ( 0.26)	0.85	7813.2	306.00
5	16377.21	32.55	1.214	0.30 ( 0.26)	0.86	8124.8	50100.00
6	17539.15	40.52	1.073	0.30 ( 0.26)	0.88	10593.3	390.00
7	18793.47	52.06	0.943	0.30 ( 0.27)	0.91	14431.1	40100.00
8	19558.76	62.79	0.859	0.30 ( 0.28)	0.93	17696.4	11801.00
9	20811.19	76.56	0.792	0.30 ( 0.28)	0.94	22690.7	11530.00
10	21668.59	84.85	0.751	0.30 ( 0.29)	0.95	26558.8	11900.00

11	23170.26	94.73	0.713	0.30 ( 0.29)	0.96	32387.5	11330.00
12	24024.64	103.02	0.690	0.30 ( 0.29)	0.96	37474.6	10630.00
13	23928.75	108.59	0.675	0.30 ( 0.29)	0.97	40064.5	12330.00
14	23809.04	115.19	0.656	0.30 ( 0.29)	0.97	43206.9	11600.00
15	23546.64	120.93	0.641	0.30 ( 0.29)	0.97	45441.2	11111.00
16	23253.01	127.01	0.631	0.30 ( 0.29)	0.97	47375.1	12201.00
17	22515.39	135.83	0.616	0.30 ( 0.29)	0.97	49463.3	12231.00
18	21827.06	143.21	0.603	0.30 ( 0.29)	0.97	50874.9	10400.00
19	21407.90	147.10	0.596	0.30 ( 0.29)	0.97	51465.1	10200.00
20	20718.71	154.43	0.584	0.30 ( 0.29)	0.97	52495.7	10320.00
21	20136.46	159.19	0.576	0.30 ( 0.29)	0.97	52721.1	10210.00
22	19631.45	163.97	0.568	0.30 ( 0.29)	0.97	52883.5	12000.00
23	16989.30	192.61	0.530	0.30 ( 0.29)	0.97	53500.5	10100.00

TOTAL AREA (ACRES) = 53500.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 24024.64 Tc(MIN.) = 103.023  
 EFFECTIVE AREA(ACRES) = 37474.61 AREA-AVERAGED Fm(INCH/HR) = 0.29  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA(ACRES) = 53500.5  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111795.71 FEET.

=====

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 53500.5 TC(MIN.) = 103.02  
 EFFECTIVE AREA(ACRES) = 37474.61 AREA-AVERAGED Fm(INCH/HR) = 0.29  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.964  
 PEAK FLOW RATE(CFS) = 24024.64

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14332.12	19.80	1.623	0.30 ( 0.25)	0.84	4776.3	300.00
2	15684.42	27.73	1.326	0.30 ( 0.25)	0.85	6898.1	50120.00
3	15889.72	29.15	1.285	0.30 ( 0.25)	0.85	7241.9	50150.00
4	16234.04	31.57	1.232	0.30 ( 0.26)	0.85	7813.2	306.00
5	16377.21	32.55	1.214	0.30 ( 0.26)	0.86	8124.8	50100.00
6	17539.15	40.52	1.073	0.30 ( 0.26)	0.88	10593.3	390.00
7	18793.47	52.06	0.943	0.30 ( 0.27)	0.91	14431.1	40100.00
8	19558.76	62.79	0.859	0.30 ( 0.28)	0.93	17696.4	11801.00
9	20811.19	76.56	0.792	0.30 ( 0.28)	0.94	22690.7	11530.00
10	21668.59	84.85	0.751	0.30 ( 0.29)	0.95	26558.8	11900.00
11	23170.26	94.73	0.713	0.30 ( 0.29)	0.96	32387.5	11330.00
12	24024.64	103.02	0.690	0.30 ( 0.29)	0.96	37474.6	10630.00
13	23928.75	108.59	0.675	0.30 ( 0.29)	0.97	40064.5	12330.00
14	23809.04	115.19	0.656	0.30 ( 0.29)	0.97	43206.9	11600.00
15	23546.64	120.93	0.641	0.30 ( 0.29)	0.97	45441.2	11111.00
16	23253.01	127.01	0.631	0.30 ( 0.29)	0.97	47375.1	12201.00
17	22515.39	135.83	0.616	0.30 ( 0.29)	0.97	49463.3	12231.00
18	21827.06	143.21	0.603	0.30 ( 0.29)	0.97	50874.9	10400.00
19	21407.90	147.10	0.596	0.30 ( 0.29)	0.97	51465.1	10200.00
20	20718.71	154.43	0.584	0.30 ( 0.29)	0.97	52495.7	10320.00
21	20136.46	159.19	0.576	0.30 ( 0.29)	0.97	52721.1	10210.00
22	19631.45	163.97	0.568	0.30 ( 0.29)	0.97	52883.5	12000.00
23	16989.30	192.61	0.530	0.30 ( 0.29)	0.97	53500.5	10100.00

=====

END OF RATIONAL METHOD ANALYSIS





\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S29- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 10-YR RM EV APRIL 2019 CCHIU \*  
\*\*\*\*\*

FILE NAME: RI10EV29.DAT  
TIME/DATE OF STUDY: 10:15 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 10.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 3.855
- 2) 10.00; 2.561
- 3) 15.00; 1.881
- 4) 20.00; 1.610
- 5) 25.00; 1.403
- 6) 30.00; 1.259
- 7) 40.00; 1.077
- 8) 50.00; 0.959
- 9) 60.00; 0.872
- 10) 90.00; 0.725
- 11) 120.00; 0.642
- 12) 180.00; 0.530
- 13) 360.00; 0.399
- 14) 1200.00; 0.175

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER WIDTH (FT)	GEOMETRIES: LIP (FT)	MANNING HIKE (FT)	FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI10EV28.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14332.12	19.80	0.30 ( 0.25)	0.84	4776.3	300.00
2	16377.21	32.55	0.30 ( 0.26)	0.86	8124.8	50100.00
3	17539.15	40.52	0.30 ( 0.26)	0.88	10593.3	390.00
4	18793.47	52.06	0.30 ( 0.27)	0.91	14431.1	40100.00
5	19558.76	62.79	0.30 ( 0.28)	0.93	17696.4	11801.00
6	20811.19	76.56	0.30 ( 0.28)	0.94	22690.7	11530.00
7	21668.59	84.85	0.30 ( 0.29)	0.95	26558.8	11900.00
8	23170.26	94.73	0.30 ( 0.29)	0.96	32387.5	11330.00
9	24024.64	103.02	0.30 ( 0.29)	0.96	37474.6	10630.00
10	23928.75	108.59	0.30 ( 0.29)	0.97	40064.5	12330.00
11	23809.04	115.19	0.30 ( 0.29)	0.97	43206.9	11600.00
12	23546.64	120.93	0.30 ( 0.29)	0.97	45441.2	11111.00
13	23253.01	127.01	0.30 ( 0.29)	0.97	47375.1	12201.00
14	22515.39	135.83	0.30 ( 0.29)	0.97	49463.3	12231.00
15	21827.06	143.21	0.30 ( 0.29)	0.97	50874.9	10400.00
16	21407.90	147.10	0.30 ( 0.29)	0.97	51465.1	10200.00
17	20718.71	154.43	0.30 ( 0.29)	0.97	52495.7	10320.00
18	20136.46	159.19	0.30 ( 0.29)	0.97	52721.1	10210.00
19	19631.45	163.97	0.30 ( 0.29)	0.97	52883.5	12000.00
20	16989.30	192.61	0.30 ( 0.29)	0.97	53500.5	10100.00
TOTAL AREA (ACRES) =						53500.5

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14332.12	19.80	0.30 ( 0.25)	0.84	4776.3	300.00
2	16377.21	32.55	0.30 ( 0.26)	0.86	8124.8	50100.00
3	17539.15	40.52	0.30 ( 0.26)	0.88	10593.3	390.00
4	18793.47	52.06	0.30 ( 0.27)	0.91	14431.1	40100.00
5	19558.76	62.79	0.30 ( 0.28)	0.93	17696.4	11801.00
6	20811.19	76.56	0.30 ( 0.28)	0.94	22690.7	11530.00
7	21668.59	84.85	0.30 ( 0.29)	0.95	26558.8	11900.00
8	23170.26	94.73	0.30 ( 0.29)	0.96	32387.5	11330.00
9	24024.64	103.02	0.30 ( 0.29)	0.96	37474.6	10630.00
10	23928.75	108.59	0.30 ( 0.29)	0.97	40064.5	12330.00
11	23809.04	115.19	0.30 ( 0.29)	0.97	43206.9	11600.00
12	23546.64	120.93	0.30 ( 0.29)	0.97	45441.2	11111.00
13	23253.01	127.01	0.30 ( 0.29)	0.97	47375.1	12201.00

14	22515.39	135.83	0.30	( 0.29)	0.97	49463.3	12231.00
15	21827.06	143.21	0.30	( 0.29)	0.97	50874.9	10400.00
16	21407.90	147.10	0.30	( 0.29)	0.97	51465.1	10200.00
17	20718.71	154.43	0.30	( 0.29)	0.97	52495.7	10320.00
18	20136.46	159.19	0.30	( 0.29)	0.97	52721.1	10210.00
19	19631.45	163.97	0.30	( 0.29)	0.97	52883.5	12000.00
20	16989.30	192.61	0.30	( 0.29)	0.97	53500.5	10100.00

TOTAL AREA (ACRES) = 53500.5

\*\*\*\*\*

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 12800.00 TO NODE 12901.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 240.00 DOWNSTREAM (FEET) = 216.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 3120.28 CHANNEL SLOPE = 0.0077  
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 7.04  
 CHANNEL FLOW THRU SUBAREA (CFS) = 24024.64  
 FLOW VELOCITY (FEET/SEC.) = 14.50 FLOW DEPTH (FEET) = 7.04  
 TRAVEL TIME (MIN.) = 3.59 Tc (MIN.) = 106.61  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12901.00 = 114915.99 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 106.61  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.679  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	2.60	0.30	0.100	56
COMMERCIAL	B	3.20	0.30	0.100	56
PUBLIC PARK	B	1.50	0.30	0.850	56
COMMERCIAL	B	5.60	0.30	0.100	56
PUBLIC PARK	B	6.50	0.30	0.850	56

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.409  
 SUBAREA AREA (ACRES) = 19.40 SUBAREA RUNOFF (CFS) = 9.71  
 EFFECTIVE AREA (ACRES) = 37494.01 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA (ACRES) = 53519.9 PEAK FLOW RATE (CFS) = 24024.64  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 106.61  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.679  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	0.50	0.30	0.100	56
PUBLIC PARK	B	4.10	0.30	0.850	56
PUBLIC PARK	B	0.10	0.30	0.850	56
RESIDENTIAL ".4 DWELLING/ACRE"	B	1.60	0.30	0.900	56
RESIDENTIAL ".4 DWELLING/ACRE"	B	0.60	0.30	0.900	56
RESIDENTIAL ".4 DWELLING/ACRE"	B	1.00	0.30	0.900	56

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.823  
 SUBAREA AREA (ACRES) = 7.90 SUBAREA RUNOFF (CFS) = 3.07  
 EFFECTIVE AREA (ACRES) = 37501.91 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA (ACRES) = 53527.8 PEAK FLOW RATE (CFS) = 24024.64  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 106.61  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.679  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL ".4 DWELLING/ACRE"	B	3.60	0.30	0.900	56
AGRICULTURAL FAIR COVER "ORCHARDS"	B	0.30	0.30	1.000	65
NATURAL POOR COVER "BARREN"	B	12.00	0.30	1.000	86
PUBLIC PARK	B	36.10	0.30	0.850	56
NATURAL FAIR COVER "GRASS"	B	15.90	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	1.50	0.30	1.000	69

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.917  
 SUBAREA AREA (ACRES) = 69.40 SUBAREA RUNOFF (CFS) = 25.23  
 EFFECTIVE AREA (ACRES) = 37571.30 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA (ACRES) = 53597.2 PEAK FLOW RATE (CFS) = 24024.64  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 106.61

\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.679  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL FAIR COVER  
 "WOODLAND,GRASS" B 4.20 0.30 1.000 65  
 NATURAL FAIR COVER  
 "WOODLAND,GRASS" B 0.40 0.30 1.000 65  
 NATURAL FAIR COVER  
 "WOODLAND,GRASS" B 1.00 0.30 1.000 65  
 RESIDENTIAL  
 "5-7 DWELLINGS/ACRE" B 4.10 0.30 0.500 56  
 RESIDENTIAL  
 "5-7 DWELLINGS/ACRE" B 3.70 0.30 0.500 56  
 RESIDENTIAL  
 "5-7 DWELLINGS/ACRE" B 0.40 0.30 0.500 56  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.703  
 SUBAREA AREA (ACRES) = 13.80 SUBAREA RUNOFF (CFS) = 5.81  
 EFFECTIVE AREA (ACRES) = 37585.11 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA (ACRES) = 53611.0 PEAK FLOW RATE (CFS) = 24024.64  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 =====

MAINLINE Tc (MIN.) = 106.61  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.679  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 6.70 0.30 1.000 66  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 1.20 0.30 1.000 66  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 2.90 0.30 1.000 66  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 10.80 SUBAREA RUNOFF (CFS) = 3.68  
 EFFECTIVE AREA (ACRES) = 37595.91 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA (ACRES) = 53621.8 PEAK FLOW RATE (CFS) = 24024.64  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12901.00 TO NODE 12902.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM (FEET) = 216.00 DOWNSTREAM (FEET) = 215.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 122.04 CHANNEL SLOPE = 0.0082  
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT (FEET) = 6.92  
 CHANNEL FLOW THRU SUBAREA (CFS) = 24024.64  
 FLOW VELOCITY (FEET/SEC.) = 14.81 FLOW DEPTH (FEET) = 6.92  
 TRAVEL TIME (MIN.) = 0.14 Tc (MIN.) = 106.75  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115038.03 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 3 <<<<<  
 =====

PEAK FLOWRATE TABLE FILE NAME: E502XX10.DNA  
 MEMORY BANK # 3 DEFINED AS FOLLOWS:  
 STREAM Q Tc Fp (Fm) Ap Ae HEADWATER  
 NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE  
 1 44.85 11.41 0.30 ( 0.27) 0.91 28.7 50200.00  
 TOTAL AREA (ACRES) = 28.7

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<  
 =====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14332.12	24.25	1.434	0.30 ( 0.25)	0.83	4897.6	300.00
2	16377.21	36.80	1.135	0.30 ( 0.26)	0.86	8246.1	50100.00
3	17539.15	44.67	1.022	0.30 ( 0.26)	0.88	10714.6	390.00
4	18793.47	56.11	0.906	0.30 ( 0.27)	0.91	14552.4	40100.00
5	19558.76	66.79	0.839	0.30 ( 0.28)	0.93	17817.7	11801.00
6	20811.19	80.47	0.772	0.30 ( 0.28)	0.94	22812.0	11530.00
7	21668.59	88.71	0.731	0.30 ( 0.29)	0.95	26680.2	11900.00
8	23170.26	98.50	0.701	0.30 ( 0.29)	0.96	32508.8	11330.00
9	24024.64	106.75	0.679	0.30 ( 0.29)	0.96	37595.9	10630.00
10	23928.75	112.32	0.663	0.30 ( 0.29)	0.97	40185.8	12330.00
11	23809.04	118.92	0.645	0.30 ( 0.29)	0.97	43328.2	11600.00
12	23546.64	124.68	0.633	0.30 ( 0.29)	0.97	45562.5	11111.00
13	23253.01	130.78	0.622	0.30 ( 0.29)	0.97	47496.4	12201.00
14	22515.39	139.64	0.605	0.30 ( 0.29)	0.97	49584.6	12231.00
15	21827.06	147.06	0.591	0.30 ( 0.29)	0.97	50996.2	10400.00
16	21407.90	150.97	0.584	0.30 ( 0.29)	0.97	51586.4	10200.00
17	20718.71	158.35	0.570	0.30 ( 0.29)	0.97	52617.0	10320.00
18	20136.46	163.15	0.561	0.30 ( 0.29)	0.97	52842.4	10210.00
19	19631.45	167.96	0.552	0.30 ( 0.29)	0.97	53004.8	12000.00
20	16989.30	196.81	0.518	0.30 ( 0.29)	0.97	53621.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115038.03 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	44.85	11.41	2.370	0.30 ( 0.27)	0.91	28.7	50200.00

LONGEST FLOWPATH FROM NODE 50200.00 TO NODE 12902.00 = 1426.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	44.85	11.41	2.370	0.30 ( 0.27)	0.91	28.7	50200.00

1	12115.63	11.41	2.370	0.30	( 0.25)	0.84	2333.0	50200.00
2	14356.96	24.25	1.434	0.30	( 0.25)	0.83	4926.3	300.00
3	16395.65	36.80	1.135	0.30	( 0.26)	0.86	8274.8	50100.00
4	17555.18	44.67	1.022	0.30	( 0.26)	0.88	10743.3	390.00
5	18807.01	56.11	0.906	0.30	( 0.27)	0.91	14581.1	40100.00
6	19570.86	66.79	0.839	0.30	( 0.28)	0.93	17846.4	11801.00
7	20821.86	80.47	0.772	0.30	( 0.28)	0.94	22840.7	11530.00
8	21678.39	88.71	0.731	0.30	( 0.28)	0.95	26708.8	11900.00
9	23179.43	98.50	0.701	0.30	( 0.29)	0.96	32537.5	11330.00
10	24033.32	106.75	0.679	0.30	( 0.29)	0.96	37624.6	10630.00
11	23937.10	112.32	0.663	0.30	( 0.29)	0.97	40214.5	12330.00
12	23817.00	118.92	0.645	0.30	( 0.29)	0.97	43356.9	11600.00
13	23554.34	124.68	0.633	0.30	( 0.29)	0.97	45591.2	11111.00
14	23260.47	130.78	0.622	0.30	( 0.29)	0.97	47525.1	12201.00
15	22522.50	139.64	0.605	0.30	( 0.29)	0.97	49613.3	12231.00
16	21833.88	147.06	0.591	0.30	( 0.29)	0.97	51024.9	10400.00
17	21414.55	150.97	0.584	0.30	( 0.29)	0.97	51615.1	10200.00
18	20725.08	158.35	0.570	0.30	( 0.29)	0.97	52645.7	10320.00
19	20142.63	163.15	0.561	0.30	( 0.29)	0.97	52871.1	10210.00
20	19637.43	167.96	0.552	0.30	( 0.29)	0.97	53033.5	12000.00
21	16994.54	196.81	0.518	0.30	( 0.29)	0.97	53650.5	10100.00

TOTAL AREA (ACRES) = 53650.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 24033.32 Tc (MIN.) = 106.748  
EFFECTIVE AREA (ACRES) = 37624.61 AREA-AVERAGED Fm (INCH/HR) = 0.29  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA (ACRES) = 53650.5  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115038.03 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: E503XX10.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	315.51	26.45	1.361	0.30 ( 0.30)	0.99	366.4	50300.00
TOTAL AREA (ACRES) =							366.4

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12115.63	11.41	2.370	0.30 ( 0.25)	0.84	2333.0	50200.00

2	14356.96	24.25	1.434	0.30	( 0.25)	0.83	4926.3	300.00
3	16395.65	36.80	1.135	0.30	( 0.26)	0.86	8274.8	50100.00
4	17555.18	44.67	1.022	0.30	( 0.26)	0.88	10743.3	390.00
5	18807.01	56.11	0.906	0.30	( 0.27)	0.91	14581.1	40100.00
6	19570.86	66.79	0.839	0.30	( 0.28)	0.93	17846.4	11801.00
7	20821.86	80.47	0.772	0.30	( 0.28)	0.94	22840.7	11530.00
8	21678.39	88.71	0.731	0.30	( 0.28)	0.95	26708.8	11900.00
9	23179.43	98.50	0.701	0.30	( 0.29)	0.96	32537.5	11330.00
10	24033.32	106.75	0.679	0.30	( 0.29)	0.96	37624.6	10630.00
11	23937.10	112.32	0.663	0.30	( 0.29)	0.97	40214.5	12330.00
12	23817.00	118.92	0.645	0.30	( 0.29)	0.97	43356.9	11600.00
13	23554.34	124.68	0.633	0.30	( 0.29)	0.97	45591.2	11111.00
14	23260.47	130.78	0.622	0.30	( 0.29)	0.97	47525.1	12201.00
15	22522.50	139.64	0.605	0.30	( 0.29)	0.97	49613.3	12231.00
16	21833.88	147.06	0.591	0.30	( 0.29)	0.97	51024.9	10400.00
17	21414.55	150.97	0.584	0.30	( 0.29)	0.97	51615.1	10200.00
18	20725.08	158.35	0.570	0.30	( 0.29)	0.97	52645.7	10320.00
19	20142.63	163.15	0.561	0.30	( 0.29)	0.97	52871.1	10210.00
20	19637.43	167.96	0.552	0.30	( 0.29)	0.97	53033.5	12000.00
21	16994.54	196.81	0.518	0.30	( 0.29)	0.97	53650.5	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115038.03 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	315.51	26.45	1.361	0.30 ( 0.30)	0.99	366.4	50300.00

LONGEST FLOWPATH FROM NODE 50300.00 TO NODE 12902.00 = 8614.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12380.45	11.41	2.370	0.30 ( 0.25)	0.84	2491.1	50200.00
2	14665.98	24.25	1.434	0.30 ( 0.25)	0.84	5262.2	300.00
3	15030.38	26.45	1.361	0.30 ( 0.25)	0.85	5880.6	50300.00
4	16644.24	36.80	1.135	0.30 ( 0.26)	0.86	8641.2	50100.00
5	17770.23	44.67	1.022	0.30 ( 0.27)	0.89	11109.7	390.00
6	18987.69	56.11	0.906	0.30 ( 0.27)	0.92	14947.5	40100.00
7	19731.68	66.79	0.839	0.30 ( 0.28)	0.93	18212.8	11801.00
8	20962.83	80.47	0.772	0.30 ( 0.28)	0.94	23207.1	11530.00
9	21807.42	88.71	0.731	0.30 ( 0.29)	0.95	27075.2	11900.00
10	23299.62	98.50	0.701	0.30 ( 0.29)	0.96	32903.9	11330.00
11	24146.76	106.75	0.679	0.30 ( 0.29)	0.96	37991.0	10630.00
12	24045.97	112.32	0.663	0.30 ( 0.29)	0.97	40580.9	12330.00
13	23920.46	118.92	0.645	0.30 ( 0.29)	0.97	43723.3	11600.00
14	23654.34	124.68	0.633	0.30 ( 0.29)	0.97	45957.6	11111.00
15	23357.10	130.78	0.622	0.30 ( 0.29)	0.97	47891.5	12201.00
16	22614.23	139.64	0.605	0.30 ( 0.29)	0.97	49979.7	12231.00
17	21921.51	147.06	0.591	0.30 ( 0.29)	0.97	51391.3	10400.00
18	21500.02	150.97	0.584	0.30 ( 0.29)	0.97	51981.5	10200.00
19	20806.46	158.35	0.570	0.30 ( 0.29)	0.97	53012.1	10320.00
20	20221.37	163.15	0.561	0.30 ( 0.29)	0.97	53237.5	10210.00
21	19713.51	167.96	0.552	0.30 ( 0.29)	0.97	53399.9	12000.00
22	17060.34	196.81	0.518	0.30 ( 0.29)	0.97	54016.9	10100.00

TOTAL AREA (ACRES) = 54016.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 24146.76 Tc (MIN.) = 106.748  
EFFECTIVE AREA (ACRES) = 37991.00 AREA-AVERAGED Fm (INCH/HR) = 0.29

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA (ACRES) = 54016.9  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115038.03 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 12902.00 TO NODE 12903.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 215.00 DOWNSTREAM(FEET) = 214.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 895.53 CHANNEL SLOPE = 0.0011  
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 12.19  
 CHANNEL FLOW THRU SUBAREA(CFS) = 24146.76  
 FLOW VELOCITY(FEET/SEC.) = 7.59 FLOW DEPTH(FEET) = 12.19  
 TRAVEL TIME(MIN.) = 1.97 Tc(MIN.) = 108.71  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115933.56 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: E504XX10.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	81.37	17.84	0.30 (0.29)	0.97	70.5	50400.00
TOTAL AREA (ACRES) = 70.5						

\*\*\*\*\*

FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12380.45	13.85	2.037	0.30 (0.25)	0.84	2491.1	50200.00
2	14665.98	26.56	1.358	0.30 (0.25)	0.84	5262.2	300.00
3	15030.38	28.74	1.295	0.30 (0.25)	0.85	5880.6	50300.00
4	16644.24	39.02	1.095	0.30 (0.26)	0.86	8641.2	50100.00
5	17770.23	46.84	0.996	0.30 (0.27)	0.89	11109.7	390.00
6	18987.69	58.24	0.887	0.30 (0.27)	0.92	14947.5	40100.00
7	19731.68	68.89	0.828	0.30 (0.28)	0.93	18212.8	11801.00
8	20962.83	82.53	0.762	0.30 (0.28)	0.94	23207.1	11530.00
9	21807.42	90.74	0.723	0.30 (0.29)	0.95	27075.2	11900.00
10	23299.62	100.49	0.696	0.30 (0.29)	0.96	32903.9	11330.00
11	24146.76	108.71	0.673	0.30 (0.29)	0.96	37991.0	10630.00

12	24045.97	114.29	0.658	0.30 (0.29)	0.97	40580.9	12330.00
13	23920.46	120.90	0.640	0.30 (0.29)	0.97	43723.3	11600.00
14	23654.34	126.66	0.630	0.30 (0.29)	0.97	45957.6	11111.00
15	23357.10	132.77	0.618	0.30 (0.29)	0.97	47891.5	12201.00
16	22614.23	141.65	0.602	0.30 (0.29)	0.97	49979.7	12231.00
17	21921.51	149.08	0.588	0.30 (0.29)	0.97	51391.3	10400.00
18	21500.02	153.02	0.580	0.30 (0.29)	0.97	51981.5	10200.00
19	20806.46	160.41	0.567	0.30 (0.29)	0.97	53012.1	10320.00
20	20221.37	165.23	0.558	0.30 (0.29)	0.97	53237.5	10210.00
21	19713.51	170.06	0.549	0.30 (0.29)	0.97	53399.9	12000.00
22	17060.34	199.01	0.516	0.30 (0.29)	0.97	54016.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115933.56 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	81.37	17.84	1.727	0.30 (0.29)	0.97	70.5	50400.00

LONGEST FLOWPATH FROM NODE 50400.00 TO NODE 12903.00 = 3607.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12457.27	13.85	2.037	0.30 (0.25)	0.85	2545.8	50200.00
2	13179.04	17.84	1.727	0.30 (0.25)	0.85	3431.2	50400.00
3	14726.46	26.56	1.358	0.30 (0.25)	0.85	5332.7	300.00
4	15087.29	28.74	1.295	0.30 (0.25)	0.85	5951.1	50300.00
5	16689.82	39.02	1.095	0.30 (0.26)	0.86	8711.7	50100.00
6	17810.22	46.84	0.996	0.30 (0.27)	0.89	11180.2	390.00
7	19021.52	58.24	0.887	0.30 (0.27)	0.92	15018.0	40100.00
8	19762.17	68.89	0.828	0.30 (0.28)	0.93	18283.3	11801.00
9	20989.54	82.53	0.762	0.30 (0.28)	0.94	23277.6	11530.00
10	21831.93	90.74	0.723	0.30 (0.29)	0.95	27145.8	11900.00
11	23322.61	100.49	0.696	0.30 (0.29)	0.96	32974.4	11330.00
12	24168.46	108.71	0.673	0.30 (0.29)	0.96	38061.5	10630.00
13	24066.80	114.29	0.658	0.30 (0.29)	0.97	40651.4	12330.00
14	23940.30	120.90	0.640	0.30 (0.29)	0.97	43793.8	11600.00
15	23673.57	126.66	0.630	0.30 (0.29)	0.97	46028.1	11111.00
16	23375.68	132.77	0.618	0.30 (0.29)	0.97	47962.0	12201.00
17	22631.87	141.65	0.602	0.30 (0.29)	0.97	50050.2	12231.00
18	21938.36	149.08	0.588	0.30 (0.29)	0.97	51461.8	10400.00
19	21516.46	153.02	0.580	0.30 (0.29)	0.97	52052.0	10200.00
20	20822.12	160.41	0.567	0.30 (0.29)	0.97	53082.6	10320.00
21	20236.52	165.23	0.558	0.30 (0.29)	0.97	53308.0	10210.00
22	19728.15	170.06	0.549	0.30 (0.29)	0.97	53470.4	12000.00
23	17073.15	199.01	0.516	0.30 (0.29)	0.97	54087.4	10100.00

TOTAL AREA (ACRES) = 54087.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 24168.46 Tc (MIN.) = 108.715  
 EFFECTIVE AREA (ACRES) = 38061.50 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA (ACRES) = 54087.4  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115933.56 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

```

=====
*****
FLOW PROCESS FROM NODE 12903.00 TO NODE 12904.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 214.00 DOWNSTREAM(FEET) = 213.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 767.57 CHANNEL SLOPE = 0.0013
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 11.69
CHANNEL FLOW THRU SUBAREA(CFS) = 24168.46
FLOW VELOCITY(FEET/SEC.) = 8.00 FLOW DEPTH(FEET) = 11.69
TRAVEL TIME(MIN.) = 1.60 Tc(MIN.) = 110.31
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116701.13 FEET.
*****
FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 15.1
-----
>>>>DEFINE MEMORY BANK # 3 <<<<
=====
PEAK FLOWRATE TABLE FILE NAME: 3B10EVRL.DNA
MEMORY BANK # 3 DEFINED AS FOLLOWS:
STREAM Q Tc Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 302.48 15.46 0.30( 0.13) 0.42 194.3 200.00
2 305.46 18.21 0.30( 0.13) 0.42 214.7 210.00
TOTAL AREA(ACRES) = 214.7
*****
FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 11
-----
>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<
=====
** MAIN STREAM CONFLUENCE DATA **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 12457.27 15.83 1.836 0.30( 0.25) 0.85 2545.8 50200.00
2 13179.04 19.78 1.622 0.30( 0.25) 0.85 3431.2 50400.00
3 14726.46 28.43 1.304 0.30( 0.25) 0.85 5332.7 300.00
4 15087.29 30.60 1.248 0.30( 0.25) 0.85 5951.1 50300.00
5 16689.82 40.82 1.067 0.30( 0.26) 0.86 8711.7 50100.00
6 17810.22 48.60 0.976 0.30( 0.27) 0.89 11180.2 390.00
7 19021.52 59.96 0.872 0.30( 0.27) 0.92 15018.0 40100.00
8 19762.17 70.59 0.820 0.30( 0.28) 0.93 18283.3 11801.00
9 20989.54 84.20 0.753 0.30( 0.28) 0.94 23277.6 11530.00
10 21831.93 92.39 0.718 0.30( 0.29) 0.95 27145.8 11900.00
11 23322.61 102.10 0.692 0.30( 0.29) 0.96 32974.4 11330.00
12 24168.46 110.31 0.669 0.30( 0.29) 0.96 38061.5 10630.00
13 24066.80 115.89 0.653 0.30( 0.29) 0.97 40651.4 12330.00
14 23940.30 122.50 0.637 0.30( 0.29) 0.97 43793.8 11600.00
15 23673.57 128.27 0.627 0.30( 0.29) 0.97 46028.1 11111.00
16 23375.68 134.38 0.615 0.30( 0.29) 0.97 47962.0 12201.00
17 22631.87 143.28 0.599 0.30( 0.29) 0.97 50050.2 12231.00
18 21938.36 150.73 0.585 0.30( 0.29) 0.97 51461.8 10400.00

```

```

19 21516.46 154.67 0.577 0.30( 0.29) 0.97 52052.0 10200.00
20 20822.12 162.09 0.563 0.30( 0.29) 0.97 53082.6 10320.00
21 20236.52 166.92 0.554 0.30( 0.29) 0.97 53308.0 10210.00
22 19728.15 171.76 0.545 0.30( 0.29) 0.97 53470.4 12000.00
23 17073.15 200.80 0.515 0.30( 0.29) 0.97 54087.4 10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116701.13 FEET.
** MEMORY BANK # 3 CONFLUENCE DATA **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 302.48 15.46 1.856 0.30( 0.13) 0.42 194.3 200.00
2 305.46 18.21 1.707 0.30( 0.13) 0.42 214.7 210.00
LONGEST FLOWPATH FROM NODE 210.00 TO NODE 12904.00 = 5961.00 FEET.
** PEAK FLOW RATE TABLE **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 12619.67 15.46 1.856 0.30( 0.24) 0.82 2679.2 200.00
2 12760.16 15.83 1.836 0.30( 0.25) 0.82 2742.9 50200.00
3 13196.30 18.21 1.707 0.30( 0.25) 0.82 3292.4 210.00
4 13467.98 19.78 1.622 0.30( 0.25) 0.82 3645.9 50400.00
5 14954.04 28.43 1.304 0.30( 0.25) 0.83 5547.4 300.00
6 15304.03 30.60 1.248 0.30( 0.25) 0.83 6165.8 50300.00
7 16871.63 40.82 1.067 0.30( 0.26) 0.85 8926.4 50100.00
8 17974.30 48.60 0.976 0.30( 0.26) 0.88 11394.9 390.00
9 19165.65 59.96 0.872 0.30( 0.27) 0.91 15232.7 40100.00
10 19896.21 70.59 0.820 0.30( 0.28) 0.92 18498.0 11801.00
11 21110.69 84.20 0.753 0.30( 0.28) 0.94 23492.3 11530.00
12 21946.32 92.39 0.718 0.30( 0.28) 0.95 27360.4 11900.00
13 23431.81 102.10 0.692 0.30( 0.29) 0.96 33189.1 11330.00
14 24273.27 110.31 0.669 0.30( 0.29) 0.96 38276.2 10630.00
15 24168.63 115.89 0.653 0.30( 0.29) 0.96 40866.1 12330.00
16 24039.03 122.50 0.637 0.30( 0.29) 0.96 44008.5 11600.00
17 23770.22 128.27 0.627 0.30( 0.29) 0.97 46242.8 11111.00
18 23470.12 134.38 0.615 0.30( 0.29) 0.97 48176.7 12201.00
19 22723.10 143.28 0.599 0.30( 0.29) 0.97 50264.9 12231.00
20 22026.91 150.73 0.585 0.30( 0.29) 0.97 51676.5 10400.00
21 21603.58 154.67 0.577 0.30( 0.29) 0.97 52266.7 10200.00
22 20906.57 162.09 0.563 0.30( 0.29) 0.97 53297.2 10320.00
23 20319.22 166.92 0.554 0.30( 0.29) 0.97 53522.7 10210.00
24 19809.11 171.76 0.545 0.30( 0.29) 0.97 53685.1 12000.00
25 17148.21 200.80 0.515 0.30( 0.29) 0.97 54302.1 10100.00
TOTAL AREA(ACRES) = 54302.1
COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
PEAK FLOW RATE(CFS) = 24273.27 Tc(MIN.) = 110.314
EFFECTIVE AREA(ACRES) = 38276.20 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
TOTAL AREA(ACRES) = 54302.1
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116701.13 FEET.
*****
FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 110.31
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.669

```

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	0.70	0.30	0.100	56
NATURAL FAIR COVER "GRASS"	B	20.00	0.30	1.000	69
NATURAL FAIR COVER "MEADOWS"	B	0.10	0.30	1.000	70
PUBLIC PARK	B	14.90	0.30	0.850	56
RESIDENTIAL ".4 DWELLING/ACRE"	B	2.60	0.30	0.900	56
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.80	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.920  
SUBAREA AREA(ACRES) = 39.10 SUBAREA RUNOFF(CFS) = 13.82  
EFFECTIVE AREA(ACRES) = 38315.30 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA(ACRES) = 54341.2 PEAK FLOW RATE(CFS) = 24273.27  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 110.31  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.669

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	0.30	0.30	0.100	56
NATURAL FAIR COVER "OPEN BRUSH"	B	0.10	0.30	1.000	66
AGRICULTURAL FAIR COVER "ORCHARDS"	B	0.10	0.30	1.000	65
RESIDENTIAL ".4 DWELLING/ACRE"	B	1.70	0.30	0.900	56
NATURAL FAIR COVER "GRASS"	B	2.60	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	0.20	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.912  
SUBAREA AREA(ACRES) = 5.00 SUBAREA RUNOFF(CFS) = 1.78  
EFFECTIVE AREA(ACRES) = 38320.30 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA(ACRES) = 54346.2 PEAK FLOW RATE(CFS) = 24273.27  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 110.31  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.669  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL FAIR COVER "ORCHARDS"	B	0.10	0.30	1.000	65
RESIDENTIAL ".4 DWELLING/ACRE"	B	2.60	0.30	0.900	56
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.20	0.30	1.000	65
NATURAL FAIR COVER "GRASS"	B	3.00	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.956  
SUBAREA AREA(ACRES) = 5.90 SUBAREA RUNOFF(CFS) = 2.03  
EFFECTIVE AREA(ACRES) = 38326.20 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA(ACRES) = 54352.1 PEAK FLOW RATE(CFS) = 24273.27  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 54352.1 TC(MIN.) = 110.31  
EFFECTIVE AREA(ACRES) = 38326.20 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.961  
PEAK FLOW RATE(CFS) = 24273.27

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12619.67	15.46	1.856	0.30( 0.25)	0.82	2729.2	200.00
2	12760.16	15.83	1.836	0.30( 0.25)	0.82	2792.9	50200.00
3	13196.30	18.21	1.707	0.30( 0.25)	0.82	3342.4	210.00
4	13467.98	19.78	1.622	0.30( 0.25)	0.82	3695.9	50400.00
5	14954.04	28.43	1.304	0.30( 0.25)	0.83	5597.4	300.00
6	15304.03	30.60	1.248	0.30( 0.25)	0.83	6215.8	50300.00
7	16871.63	40.82	1.067	0.30( 0.26)	0.85	8976.4	50100.00
8	17974.30	48.60	0.976	0.30( 0.26)	0.88	11444.9	390.00
9	19165.65	59.96	0.872	0.30( 0.27)	0.91	15282.7	40100.00
10	19896.21	70.59	0.820	0.30( 0.28)	0.92	18548.0	11801.00
11	21110.69	84.20	0.753	0.30( 0.28)	0.94	23542.3	11530.00
12	21946.32	92.39	0.718	0.30( 0.28)	0.95	27410.4	11900.00
13	23431.81	102.10	0.692	0.30( 0.29)	0.96	33239.1	11330.00
14	24273.27	110.31	0.669	0.30( 0.29)	0.96	38326.2	10630.00
15	24168.63	115.89	0.653	0.30( 0.29)	0.96	40916.1	12330.00
16	24039.03	122.50	0.637	0.30( 0.29)	0.96	44058.5	11600.00
17	23770.22	128.27	0.627	0.30( 0.29)	0.97	46292.8	11111.00
18	23470.12	134.38	0.615	0.30( 0.29)	0.97	48226.7	12201.00
19	22723.10	143.28	0.599	0.30( 0.29)	0.97	50314.9	12231.00
20	22026.91	150.73	0.585	0.30( 0.29)	0.97	51726.5	10400.00
21	21603.58	154.67	0.577	0.30( 0.29)	0.97	52316.7	10200.00
22	20906.57	162.09	0.563	0.30( 0.29)	0.97	53347.2	10320.00
23	20319.22	166.92	0.554	0.30( 0.29)	0.97	53572.7	10210.00
24	19809.11	171.76	0.545	0.30( 0.29)	0.97	53735.1	12000.00
25	17148.21	200.80	0.515	0.30( 0.29)	0.97	54352.1	10100.00

END OF RATIONAL METHOD ANALYSIS





\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S33- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 10-YR RM EV APRIL 2019 CCHIUI \*  
\*\*\*\*\*

FILE NAME: RI10EV33.DAT  
TIME/DATE OF STUDY: 10:16 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 10.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 3.775
- 2) 10.00; 2.517
- 3) 15.00; 1.863
- 4) 20.00; 1.593
- 5) 25.00; 1.391
- 6) 30.00; 1.250
- 7) 40.00; 1.068
- 8) 50.00; 0.950
- 9) 60.00; 0.862
- 10) 90.00; 0.714
- 11) 120.00; 0.630
- 12) 180.00; 0.528
- 13) 360.00; 0.388
- 14) 1200.00; 0.170

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL: IN- / OUT-/PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:

- 1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13112.00 TO NODE 13222.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: S31X10.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1716.14	38.98	0.30 ( 0.24)	0.81	2485.1	13100.00
2	1689.35	68.05	0.30 ( 0.24)	0.81	3778.1	13000.00
3	1657.69	70.37	0.30 ( 0.24)	0.81	3796.8	13010.00
TOTAL AREA (ACRES) =						3796.8

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13221.00 TO NODE 13222.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: S32X10.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	821.94	36.32	0.30 ( 0.25)	0.83	1125.1	13210.00
2	821.47	36.44	0.30 ( 0.25)	0.83	1127.6	13200.00
TOTAL AREA (ACRES) =						1127.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13221.00 TO NODE 13222.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	821.94	36.32	0.30 ( 0.25)	0.83	1125.1	13210.00
2	821.47	36.44	0.30 ( 0.25)	0.83	1127.6	13200.00
TOTAL AREA (ACRES) =						1127.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13112.00 TO NODE 13222.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	821.94	36.32	1.135	0.30 ( 0.25)	0.83	1125.1	13210.00
2	821.47	36.44	1.133	0.30 ( 0.25)	0.83	1127.6	13200.00

LONGEST FLOWPATH FROM NODE 13200.00 TO NODE 13222.00 = 16821.05 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1716.14	38.98	1.087	0.30 ( 0.24)	0.81	2485.1	13100.00
2	1689.35	68.05	0.822	0.30 ( 0.24)	0.81	3778.1	13000.00
3	1657.69	70.37	0.811	0.30 ( 0.24)	0.81	3796.8	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13222.00 = 32126.49 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2512.74	36.32	1.135	0.30 ( 0.24)	0.82	3440.8	13210.00
2	2513.70	36.44	1.133	0.30 ( 0.24)	0.82	3450.9	13200.00
3	2494.71	38.98	1.087	0.30 ( 0.24)	0.82	3612.7	13100.00
4	2222.44	68.05	0.822	0.30 ( 0.24)	0.81	4905.7	13000.00
5	2180.16	70.37	0.811	0.30 ( 0.24)	0.81	4924.4	13010.00

TOTAL AREA (ACRES) = 4924.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 2513.70 Tc(MIN.) = 36.438

EFFECTIVE AREA(ACRES) = 3450.86 AREA-AVERAGED Fm(INCH/HR) = 0.24

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82

TOTAL AREA (ACRES) = 4924.4

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13222.00 = 32126.49 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13222.00 TO NODE 13222.00 IS CODE = 12

-----

>>>>CLEAR MEMORY BANK # 1 <<<<<

=====

\*\*\*\*\*

FLOW PROCESS FROM NODE 13222.00 TO NODE 13222.00 IS CODE = 12

-----

>>>>CLEAR MEMORY BANK # 2 <<<<<

=====

\*\*\*\*\*

FLOW PROCESS FROM NODE 13222.00 TO NODE 13301.00 IS CODE = 56

-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 427.51 DOWNSTREAM(FEET) = 382.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 2533.33 CHANNEL SLOPE = 0.0180

GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 3.83

\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.064

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	1.40	0.30	0.100	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	15.60	0.30	1.000	66
RESIDENTIAL					
"3-4 DWELLINGS/ACRE"	B	0.10	0.30	0.600	56
AGRICULTURAL POOR COVER					

"ROW CROPS,CONTOURED"	B	5.30	0.30	1.000	79
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86
COMMERCIAL	B	22.60	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.521

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2532.15

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.74

AVERAGE FLOW DEPTH(FEET) = 3.83 TRAVEL TIME(MIN.) = 3.93

Tc(MIN.) = 40.37

SUBAREA AREA(ACRES) = 45.20 SUBAREA RUNOFF(CFS) = 36.91

EFFECTIVE AREA(ACRES) = 3496.06 AREA-AVERAGED Fm(INCH/HR) = 0.24

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81

TOTAL AREA(ACRES) = 4969.6 PEAK FLOW RATE(CFS) = 2580.54

GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 3.87

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 3.87 FLOW VELOCITY(FEET/SEC.) = 10.82

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2577.71	40.24	1.065	0.30 ( 0.24)	0.81	3486.0	13210.00
2	2580.54	40.37	1.064	0.30 ( 0.24)	0.81	3496.1	13200.00
3	2601.28	42.91	1.034	0.30 ( 0.24)	0.81	3657.9	13100.00
4	2491.96	72.14	0.802	0.30 ( 0.24)	0.81	4950.9	13000.00
5	2449.85	74.49	0.791	0.30 ( 0.24)	0.81	4969.6	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2601.28 Tc(MIN.) = 42.91

AREA-AVERAGED Fm(INCH/HR) = 0.24 AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.81 EFFECTIVE AREA(ACRES) = 3657.90

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 42.91

\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.034

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	1.00	0.30	1.000	79
NATURAL POOR COVER					
"BARREN"	B	0.50	0.30	1.000	86
COMMERCIAL	B	7.40	0.30	0.100	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	4.70	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	2.90	0.30	1.000	65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.596					
SUBAREA AREA(ACRES) = 16.50 SUBAREA RUNOFF(CFS) = 12.69					
EFFECTIVE AREA(ACRES) = 3674.40 AREA-AVERAGED Fm(INCH/HR) = 0.24					

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81  
TOTAL AREA (ACRES) = 4986.1 PEAK FLOW RATE (CFS) = 2613.98

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 42.91  
\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.034  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	1.30	0.30	1.000	86
COMMERCIAL	B	0.20	0.30	0.100	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	5.30	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.30	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	0.20	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.60	0.30	1.000	66

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.977  
SUBAREA AREA (ACRES) = 7.90 SUBAREA RUNOFF (CFS) = 5.26  
EFFECTIVE AREA (ACRES) = 3682.30 AREA-AVERAGED Fm (INCH/HR) = 0.24  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81  
TOTAL AREA (ACRES) = 4994.0 PEAK FLOW RATE (CFS) = 2619.24

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 42.91  
\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.034  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	4.30	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.80	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	1.10	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	6.90	0.30	1.000	66
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	7.90	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	1.00	0.30	1.000	65

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 22.00 SUBAREA RUNOFF (CFS) = 14.53  
EFFECTIVE AREA (ACRES) = 3704.30 AREA-AVERAGED Fm (INCH/HR) = 0.24  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81

TOTAL AREA (ACRES) = 5016.0 PEAK FLOW RATE (CFS) = 2633.77

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 42.91  
\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.034  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.40	0.30	1.000	66
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	14.60	0.30	1.000	79

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 15.00 SUBAREA RUNOFF (CFS) = 9.90  
EFFECTIVE AREA (ACRES) = 3719.30 AREA-AVERAGED Fm (INCH/HR) = 0.24  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81  
TOTAL AREA (ACRES) = 5031.0 PEAK FLOW RATE (CFS) = 2643.67

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 31100.00 TO NODE 31101.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<

>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH (FEET) = 317.00  
ELEVATION DATA: UPSTREAM (FEET) = 801.00 DOWNSTREAM (FEET) = 685.00

$T_c = K * [(LENGTH ** 3.00) / (ELEVATION CHANGE)] ** 0.20$   
SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 8.641  
\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 2.859  
SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER						
"CHAPARRAL, BROADLEAF"	B	0.50	0.30	1.000	63	8.64
NATURAL FAIR COVER						
"OPEN BRUSH"	B	0.30	0.30	1.000	66	8.64
NATURAL FAIR COVER						
"OPEN BRUSH"	B	0.30	0.30	1.000	66	8.64

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA RUNOFF (CFS) = 2.53  
TOTAL AREA (ACRES) = 1.10 PEAK FLOW RATE (CFS) = 2.53

\*\*\*\*\*

FLOW PROCESS FROM NODE 31101.00 TO NODE 31102.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 685.00 DOWNSTREAM(FEET) = 655.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 135.00 CHANNEL SLOPE = 0.2222  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.768

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	B	0.50	0.30	1.000	63
---	---	------	------	-------	----

NATURAL FAIR COVER "OPEN BRUSH"	B	0.10	0.30	1.000	66
------------------------------------	---	------	------	-------	----

NATURAL FAIR COVER "OPEN BRUSH"	B	0.70	0.30	1.000	66
------------------------------------	---	------	------	-------	----

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3.98

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.25

AVERAGE FLOW DEPTH(FEET) = 0.46 TRAVEL TIME(MIN.) = 0.36

Tc(MIN.) = 9.00

SUBAREA AREA(ACRES) = 1.30 SUBAREA RUNOFF(CFS) = 2.89

EFFECTIVE AREA(ACRES) = 2.40 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 2.4 PEAK FLOW RATE(CFS) = 5.33

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.51 FLOW VELOCITY(FEET/SEC.) = 6.88

LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31102.00 = 452.00 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 31102.00 TO NODE 31103.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 655.00 DOWNSTREAM(FEET) = 630.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 203.00 CHANNEL SLOPE = 0.1232  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 10.00  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.654

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	B	0.30	0.30	1.000	63
---	---	------	------	-------	----

NATURAL FAIR COVER "OPEN BRUSH"	B	0.10	0.30	1.000	66
------------------------------------	---	------	------	-------	----

NATURAL FAIR COVER "OPEN BRUSH"	B	1.90	0.30	1.000	66
------------------------------------	---	------	------	-------	----

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 7.77

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.43

AVERAGE FLOW DEPTH(FEET) = 0.59 TRAVEL TIME(MIN.) = 0.46

Tc(MIN.) = 9.46

SUBAREA AREA(ACRES) = 2.30 SUBAREA RUNOFF(CFS) = 4.87  
EFFECTIVE AREA(ACRES) = 4.70 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 4.7 PEAK FLOW RATE(CFS) = 9.96

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.65 FLOW VELOCITY(FEET/SEC.) = 7.96

LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31103.00 = 655.00 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 31103.00 TO NODE 31104.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 630.00 DOWNSTREAM(FEET) = 605.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 321.00 CHANNEL SLOPE = 0.0779  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.467

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL FAIR COVER "OPEN BRUSH"	B	1.10	0.30	1.000	66
------------------------------------	---	------	------	-------	----

NATURAL FAIR COVER "OPEN BRUSH"	B	2.50	0.30	1.000	66
------------------------------------	---	------	------	-------	----

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 13.47

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.79

AVERAGE FLOW DEPTH(FEET) = 0.88 TRAVEL TIME(MIN.) = 0.92

Tc(MIN.) = 10.38

SUBAREA AREA(ACRES) = 3.60 SUBAREA RUNOFF(CFS) = 7.02

EFFECTIVE AREA(ACRES) = 8.30 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 8.3 PEAK FLOW RATE(CFS) = 16.19

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.94 FLOW VELOCITY(FEET/SEC.) = 6.07

LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31104.00 = 976.00 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 31104.00 TO NODE 31105.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 605.00 DOWNSTREAM(FEET) = 585.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 288.00 CHANNEL SLOPE = 0.0694  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.367

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	B	0.70	0.30	1.000	63
---	---	------	------	-------	----

NATURAL FAIR COVER  
 "CHAPARRAL,BROADLEAF" B 0.60 0.30 1.000 63  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 3.00 0.30 1.000 66  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 2.10 0.30 1.000 66  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 22.15  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.26  
 AVERAGE FLOW DEPTH(FEET) = 1.09 TRAVEL TIME(MIN.) = 0.77  
 Tc(MIN.) = 11.15  
 SUBAREA AREA(ACRES) = 6.40 SUBAREA RUNOFF(CFS) = 11.91  
 EFFECTIVE AREA(ACRES) = 14.70 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 14.7 PEAK FLOW RATE(CFS) = 27.35

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.17 FLOW VELOCITY(FEET/SEC.) = 6.64  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31105.00 = 1264.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31105.00 TO NODE 31106.00 IS CODE = 51

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

-----  
 ELEVATION DATA: UPSTREAM(FEET) = 585.00 DOWNSTREAM(FEET) = 560.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 344.00 CHANNEL SLOPE = 0.0727  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.264

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.60	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	2.80	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.60	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.10	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.60	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	4.10	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 36.89  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.26  
 AVERAGE FLOW DEPTH(FEET) = 1.30 TRAVEL TIME(MIN.) = 0.79  
 Tc(MIN.) = 11.94  
 SUBAREA AREA(ACRES) = 10.80 SUBAREA RUNOFF(CFS) = 19.09  
 EFFECTIVE AREA(ACRES) = 25.50 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 25.5 PEAK FLOW RATE(CFS) = 45.07

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.40 FLOW VELOCITY(FEET/SEC.) = 7.65  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31106.00 = 1608.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31106.00 TO NODE 31107.00 IS CODE = 51

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

-----  
 ELEVATION DATA: UPSTREAM(FEET) = 560.00 DOWNSTREAM(FEET) = 530.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 619.00 CHANNEL SLOPE = 0.0485  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.070

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.80	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	1.90	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.50	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	8.20	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.70	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 57.10  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.97  
 AVERAGE FLOW DEPTH(FEET) = 1.65 TRAVEL TIME(MIN.) = 1.48  
 Tc(MIN.) = 13.42  
 SUBAREA AREA(ACRES) = 15.10 SUBAREA RUNOFF(CFS) = 24.05  
 EFFECTIVE AREA(ACRES) = 40.60 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 40.6 PEAK FLOW RATE(CFS) = 64.68

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.73 FLOW VELOCITY(FEET/SEC.) = 7.16  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31107.00 = 2227.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31107.00 TO NODE 31108.00 IS CODE = 51

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

-----  
 ELEVATION DATA: UPSTREAM(FEET) = 530.00 DOWNSTREAM(FEET) = 515.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 377.00 CHANNEL SLOPE = 0.0398  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.952

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					

"CHAPARRAL,BROADLEAF" B 0.50 0.30 1.000 63  
 NATURAL FAIR COVER  
 "CHAPARRAL,BROADLEAF" B 6.50 0.30 1.000 63  
 NATURAL FAIR COVER  
 "CHAPARRAL,BROADLEAF" B 1.30 0.30 1.000 63  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 1.10 0.30 1.000 66  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 5.50 0.30 1.000 66  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 3.40 0.30 1.000 66  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 78.29  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.98  
 AVERAGE FLOW DEPTH(FEET) = 1.93 TRAVEL TIME(MIN.) = 0.90  
 Tc(MIN.) = 14.32  
 SUBAREA AREA(ACRES) = 18.30 SUBAREA RUNOFF(CFS) = 27.21  
 EFFECTIVE AREA(ACRES) = 58.90 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 58.9 PEAK FLOW RATE(CFS) = 87.59

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 2.02 FLOW VELOCITY(FEET/SEC.) = 7.18  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31108.00 = 2604.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31108.00 TO NODE 31109.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<  
 -----

ELEVATION DATA: UPSTREAM(FEET) = 515.00 DOWNSTREAM(FEET) = 490.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 520.00 CHANNEL SLOPE = 0.0481  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.841  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.70	0.30	1.000	63
NATURAL FAIR COVER					
"GRASS"	B	2.20	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	3.10	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.90	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	7.40	0.30	1.000	63
NATURAL FAIR COVER					
"GRASS"	B	0.30	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 97.72  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.93  
 AVERAGE FLOW DEPTH(FEET) = 2.03 TRAVEL TIME(MIN.) = 1.09  
 Tc(MIN.) = 15.41

SUBAREA AREA(ACRES) = 14.60 SUBAREA RUNOFF(CFS) = 20.25  
 EFFECTIVE AREA(ACRES) = 73.50 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 73.5 PEAK FLOW RATE(CFS) = 101.93

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 2.06 FLOW VELOCITY(FEET/SEC.) = 8.03  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31109.00 = 3124.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31109.00 TO NODE 31109.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<  
 -----  
 MAINLINE Tc(MIN.) = 15.41  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.841  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	11.40	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	8.90	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	1.90	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	9.20	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	1.40	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 32.80 SUBAREA RUNOFF(CFS) = 45.49  
 EFFECTIVE AREA(ACRES) = 106.30 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 106.3 PEAK FLOW RATE(CFS) = 147.42

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31109.00 TO NODE 31110.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<  
 -----

ELEVATION DATA: UPSTREAM(FEET) = 490.00 DOWNSTREAM(FEET) = 432.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1420.00 CHANNEL SLOPE = 0.0408  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.688  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	0.80	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.60	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.10	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	1.30	0.30	1.000	79

NATURAL FAIR COVER  
 "WOODLAND,GRASS" B 4.00 0.30 1.000 65  
 NATURAL FAIR COVER  
 "CHAPARRAL,BROADLEAF" B 1.50 0.30 1.000 63  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 152.60  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.34  
 AVERAGE FLOW DEPTH(FEET) = 2.47 TRAVEL TIME(MIN.) = 2.84  
 Tc(MIN.) = 18.25  
 SUBAREA AREA(ACRES) = 8.30 SUBAREA RUNOFF(CFS) = 10.37  
 EFFECTIVE AREA(ACRES) = 114.60 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 114.6 PEAK FLOW RATE(CFS) = 147.42  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 2.44 FLOW VELOCITY(FEET/SEC.) = 8.28  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31110.00 = 4544.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31110.00 TO NODE 31110.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 18.25  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.688  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL FAIR COVER  
 "GRASS" B 0.30 0.30 1.000 69  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 9.60 0.30 1.000 66  
 RESIDENTIAL  
 ".4 DWELLING/ACRE" B 0.40 0.30 0.900 56  
 AGRICULTURAL POOR COVER  
 "ROW CROPS,CONTOURED" B 6.20 0.30 1.000 79  
 NATURAL FAIR COVER  
 "WOODLAND,GRASS" B 3.90 0.30 1.000 65  
 AGRICULTURAL POOR COVER  
 "ROW CROPS,CONTOURED" B 1.40 0.30 1.000 79  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.998  
 SUBAREA AREA(ACRES) = 21.80 SUBAREA RUNOFF(CFS) = 27.24  
 EFFECTIVE AREA(ACRES) = 136.40 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 136.4 PEAK FLOW RATE(CFS) = 170.37

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31110.00 TO NODE 13301.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 432.00 DOWNSTREAM(FEET) = 382.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1847.00 CHANNEL SLOPE = 0.0271  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.497  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL POOR COVER  
 "BARREN" B 4.90 0.30 1.000 86  
 AGRICULTURAL POOR COVER  
 "ROW CROPS,CONTOURED" B 1.50 0.30 1.000 79  
 RESIDENTIAL  
 ".4 DWELLING/ACRE" B 0.60 0.30 0.900 56  
 AGRICULTURAL POOR COVER  
 "ROW CROPS,CONTOURED" B 2.50 0.30 1.000 79  
 AGRICULTURAL POOR COVER  
 "ROW CROPS,CONTOURED" B 5.30 0.30 1.000 79  
 AGRICULTURAL POOR COVER  
 "ROW CROPS,CONTOURED" B 3.30 0.30 1.000 79  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.997  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 180.13  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.44  
 AVERAGE FLOW DEPTH(FEET) = 2.84 TRAVEL TIME(MIN.) = 4.14  
 Tc(MIN.) = 22.38  
 SUBAREA AREA(ACRES) = 18.10 SUBAREA RUNOFF(CFS) = 19.51  
 EFFECTIVE AREA(ACRES) = 154.50 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 154.5 PEAK FLOW RATE(CFS) = 170.37  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 2.78 FLOW VELOCITY(FEET/SEC.) = 7.35  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 13301.00 = 6391.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*  
 STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER  
 NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE  
 1 170.37 22.38 1.497 0.30( 0.30) 1.00 154.5 31100.00  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 13301.00 = 6391.00 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*  
 STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER  
 NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE  
 1 2621.84 40.24 1.065 0.30( 0.24) 0.81 3547.4 13210.00  
 2 2624.58 40.37 1.064 0.30( 0.24) 0.81 3557.5 13200.00  
 3 2643.67 42.91 1.034 0.30( 0.24) 0.81 3719.3 13100.00  
 4 2521.55 72.14 0.802 0.30( 0.24) 0.81 5012.3 13000.00  
 5 2478.80 74.49 0.791 0.30( 0.24) 0.81 5031.0 13010.00  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

\*\* PEAK FLOW RATE TABLE \*\*  
 STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER  
 NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE

1	2395.03	22.38	1.497	0.30	( 0.25)	0.83	2127.6	31100.00
2	2730.78	40.24	1.065	0.30	( 0.25)	0.82	3701.9	13210.00
3	2733.32	40.37	1.064	0.30	( 0.25)	0.82	3712.0	13200.00
4	2748.13	42.91	1.034	0.30	( 0.25)	0.82	3873.8	13100.00
5	2593.06	72.14	0.802	0.30	( 0.24)	0.82	5166.8	13000.00
6	2548.66	74.49	0.791	0.30	( 0.24)	0.82	5185.5	13010.00
TOTAL AREA (ACRES) =		5185.5						

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 2748.13 Tc(MIN.) = 42.911  
EFFECTIVE AREA(ACRES) = 3873.80 AREA-AVERAGED Fm(INCH/HR) = 0.25  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82  
TOTAL AREA(ACRES) = 5185.5  
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13302.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 382.00 DOWNSTREAM(FEET) = 375.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1141.09 CHANNEL SLOPE = 0.0061  
GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 5.43  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.004  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	9.40	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2751.11  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.65  
AVERAGE FLOW DEPTH(FEET) = 5.43 TRAVEL TIME(MIN.) = 2.49  
Tc(MIN.) = 45.40  
SUBAREA AREA(ACRES) = 9.40 SUBAREA RUNOFF(CFS) = 5.96  
EFFECTIVE AREA(ACRES) = 3883.20 AREA-AVERAGED Fm(INCH/HR) = 0.25  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82  
TOTAL AREA(ACRES) = 5194.9 PEAK FLOW RATE(CFS) = 2748.13  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 5.42

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 5.42 FLOW VELOCITY(FEET/SEC.) = 7.65  
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13302.00 = 35800.91 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2395.03	24.98	1.392	0.30( 0.25)	0.83	2137.0	31100.00
2	2730.78	42.73	1.036	0.30( 0.25)	0.82	3711.3	13210.00
3	2733.32	42.86	1.034	0.30( 0.25)	0.82	3721.4	13200.00
4	2748.13	45.40	1.004	0.30( 0.25)	0.82	3883.2	13100.00
5	2593.06	74.67	0.790	0.30( 0.24)	0.82	5176.2	13000.00
6	2548.66	77.03	0.778	0.30( 0.24)	0.82	5194.9	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2748.13 Tc(MIN.) = 45.40  
AREA-AVERAGED Fm(INCH/HR) = 0.25 AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.82 EFFECTIVE AREA(ACRES) = 3883.20

\*\*\*\*\*

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<

MAINLINE Tc(MIN.) = 45.40

\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.004

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	13.80	0.30	1.000	86
NATURAL POOR COVER					
"BARREN"	B	2.60	0.30	1.000	86
COMMERCIAL	B	1.10	0.30	0.100	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	3.50	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	6.90	0.30	1.000	79
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.952  
SUBAREA AREA(ACRES) = 28.10 SUBAREA RUNOFF(CFS) = 18.17  
EFFECTIVE AREA(ACRES) = 3911.30 AREA-AVERAGED Fm(INCH/HR) = 0.25  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82  
TOTAL AREA(ACRES) = 5223.0 PEAK FLOW RATE(CFS) = 2748.13  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<

MAINLINE Tc(MIN.) = 45.40

\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.004

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	0.10	0.30	1.000	79
COMMERCIAL	B	0.10	0.30	0.100	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	2.40	0.30	0.900	56

AGRICULTURAL POOR COVER



"ROW CROPS, CONTOURED" B 0.50 0.30 1.000 79  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.894  
 SUBAREA AREA (ACRES) = 3.10 SUBAREA RUNOFF (CFS) = 2.05  
 EFFECTIVE AREA (ACRES) = 3914.40 AREA-AVERAGED Fm (INCH/HR) = 0.25  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82  
 TOTAL AREA (ACRES) = 5226.1 PEAK FLOW RATE (CFS) = 2748.13  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 45.40  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.004  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	0.10	0.30	1.000	86
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.60	0.30	1.000	66
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	3.10	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.40	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	0.20	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	13.80	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 20.20 SUBAREA RUNOFF (CFS) = 12.80  
 EFFECTIVE AREA (ACRES) = 3934.60 AREA-AVERAGED Fm (INCH/HR) = 0.25  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82  
 TOTAL AREA (ACRES) = 5246.3 PEAK FLOW RATE (CFS) = 2748.13  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 45.40  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.004  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	34.60	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	2.40	0.30	1.000	65
NATURAL FAIR COVER					
"OPEN BRUSH"	B	22.60	0.30	1.000	66
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	11.60	0.30	1.000	79
APARTMENTS	B	0.40	0.30	0.200	56

NATURAL FAIR COVER  
 "CHAPARRAL, BROADLEAF" B 4.80 0.30 1.000 63  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.996  
 SUBAREA AREA (ACRES) = 76.40 SUBAREA RUNOFF (CFS) = 48.51  
 EFFECTIVE AREA (ACRES) = 4011.00 AREA-AVERAGED Fm (INCH/HR) = 0.25  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA (ACRES) = 5322.7 PEAK FLOW RATE (CFS) = 2748.13  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 45.40  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.004  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	1.60	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	46.40	0.30	1.000	66
RESIDENTIAL					
"11+ DWELLINGS/ACRE"	B	0.10	0.30	0.200	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	60.70	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	5.80	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999  
 SUBAREA AREA (ACRES) = 114.60 SUBAREA RUNOFF (CFS) = 72.66  
 EFFECTIVE AREA (ACRES) = 4125.60 AREA-AVERAGED Fm (INCH/HR) = 0.25  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA (ACRES) = 5437.3 PEAK FLOW RATE (CFS) = 2803.58

\*\*\*\*\*

FLOW PROCESS FROM NODE 13302.00 TO NODE 13303.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 375.00 DOWNSTREAM (FEET) = 355.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 2193.96 CHANNEL SLOPE = 0.0091  
 GIVEN CHANNEL BASE (FEET) = 50.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 4.91  
 CHANNEL FLOW THRU SUBAREA (CFS) = 2803.58  
 FLOW VELOCITY (FEET/SEC.) = 8.82 FLOW DEPTH (FEET) = 4.91  
 TRAVEL TIME (MIN.) = 4.15 Tc (MIN.) = 49.54  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13303.00 = 37994.87 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap (DECIMAL)	Ae (ACRES)	HEADWATER NODE
1	2438.32	29.31	1.269	0.30 ( 0.25)	0.84	2379.4	31100.00
2	2797.64	46.88	0.987	0.30 ( 0.25)	0.83	3953.7	13210.00

3 2799.68 47.01 0.985 0.30( 0.25) 0.83 3963.8 13200.00  
 4 2803.58 49.54 0.955 0.30( 0.25) 0.83 4125.6 13100.00  
 5 2644.86 78.89 0.769 0.30( 0.25) 0.82 5418.6 13000.00  
 6 2597.35 81.28 0.757 0.30( 0.25) 0.82 5437.3 13010.00  
 NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE(CFS) = 2803.58 Tc(MIN.) = 49.54  
 AREA-AVERAGED Fm(INCH/HR) = 0.25 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.83 EFFECTIVE AREA(ACRES) = 4125.60

\*\*\*\*\*

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 49.54  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.955  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER "BARREN"	B	0.20	0.30	1.000	86
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.40	0.30	1.000	65
NATURAL POOR COVER "BARREN"	B	0.80	0.30	1.000	86
COMMERCIAL	B	1.40	0.30	0.100	56
NATURAL FAIR COVER "GRASS"	B	2.60	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	2.20	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.834  
 SUBAREA AREA(ACRES) = 7.60 SUBAREA RUNOFF(CFS) = 4.82  
 EFFECTIVE AREA(ACRES) = 4133.20 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA(ACRES) = 5444.9 PEAK FLOW RATE(CFS) = 2803.58  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 49.54  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.955  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	3.10	0.30	1.000	79
NATURAL FAIR COVER "WOODLAND,GRASS"	B	3.40	0.30	1.000	65
NATURAL POOR COVER "BARREN"	B	0.50	0.30	1.000	86
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	B	0.20	0.30	1.000	63
COMMERCIAL	B	3.60	0.30	0.100	56
NATURAL FAIR COVER					

"GRASS" B 4.00 0.30 1.000 69  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.781  
 SUBAREA AREA(ACRES) = 14.80 SUBAREA RUNOFF(CFS) = 9.60  
 EFFECTIVE AREA(ACRES) = 4148.00 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA(ACRES) = 5459.7 PEAK FLOW RATE(CFS) = 2803.58  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 49.54  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.955  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	14.60	0.30	1.000	66
AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	6.30	0.30	1.000	79
NATURAL FAIR COVER "WOODLAND,GRASS"	B	3.70	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 24.60 SUBAREA RUNOFF(CFS) = 14.51  
 EFFECTIVE AREA(ACRES) = 4172.60 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA(ACRES) = 5484.3 PEAK FLOW RATE(CFS) = 2803.58  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 49.54  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.955  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER "BARREN"	B	0.50	0.30	1.000	86
COMMERCIAL	B	0.30	0.30	0.100	56
NATURAL FAIR COVER "OPEN BRUSH"	B	0.20	0.30	1.000	66
RESIDENTIAL ".4 DWELLING/ACRE"	B	0.80	0.30	0.900	56
AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	1.60	0.30	1.000	79
NATURAL POOR COVER "BARREN"	B	31.90	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.990  
 SUBAREA AREA(ACRES) = 35.30 SUBAREA RUNOFF(CFS) = 20.92  
 EFFECTIVE AREA(ACRES) = 4207.90 AREA-AVERAGED Fm(INCH/HR) = 0.25

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA (ACRES) = 5519.6 PEAK FLOW RATE (CFS) = 2803.58  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 49.54  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.955  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 COMMERCIAL B 1.70 0.30 0.100 56  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 0.30 0.30 1.000 66  
 RESIDENTIAL  
 ".4 DWELLING/ACRE" B 2.60 0.30 0.900 56  
 AGRICULTURAL POOR COVER  
 "ROW CROPS, CONTOURED" B 5.50 0.30 1.000 79  
 NATURAL FAIR COVER  
 "WOODLAND, GRASS" B 0.20 0.30 1.000 65  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 0.20 0.30 1.000 66  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.830  
 SUBAREA AREA (ACRES) = 10.50 SUBAREA RUNOFF (CFS) = 6.68  
 EFFECTIVE AREA (ACRES) = 4218.40 AREA-AVERAGED Fm (INCH/HR) = 0.25  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA (ACRES) = 5530.1 PEAK FLOW RATE (CFS) = 2803.58  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 49.54  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.955  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 RESIDENTIAL  
 ".4 DWELLING/ACRE" B 1.30 0.30 0.900 56  
 NATURAL POOR COVER  
 "BARREN" B 0.30 0.30 1.000 86  
 COMMERCIAL B 0.20 0.30 0.100 56  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 0.30 0.30 1.000 66  
 RESIDENTIAL  
 ".4 DWELLING/ACRE" B 6.50 0.30 0.900 56  
 AGRICULTURAL POOR COVER  
 "ROW CROPS, CONTOURED" B 3.00 0.30 1.000 79  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.917  
 SUBAREA AREA (ACRES) = 11.60 SUBAREA RUNOFF (CFS) = 7.10  
 EFFECTIVE AREA (ACRES) = 4230.00 AREA-AVERAGED Fm (INCH/HR) = 0.25

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA (ACRES) = 5541.7 PEAK FLOW RATE (CFS) = 2803.58  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13303.00 TO NODE 13304.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 355.00 DOWNSTREAM (FEET) = 350.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 925.40 CHANNEL SLOPE = 0.0054  
 GIVEN CHANNEL BASE (FEET) = 50.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 5.68  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.936  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 PUBLIC PARK B 13.80 0.30 0.850 56  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.850  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 2807.80  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.37  
 AVERAGE FLOW DEPTH (FEET) = 5.68 TRAVEL TIME (MIN.) = 2.09  
 Tc (MIN.) = 51.64  
 SUBAREA AREA (ACRES) = 13.80 SUBAREA RUNOFF (CFS) = 8.45  
 EFFECTIVE AREA (ACRES) = 4243.80 AREA-AVERAGED Fm (INCH/HR) = 0.25  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA (ACRES) = 5555.5 PEAK FLOW RATE (CFS) = 2803.58  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 50.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 5.68

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 5.68 FLOW VELOCITY (FEET/SEC.) = 7.36  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13304.00 = 38920.27 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2438.32	31.50	1.223	0.30 ( 0.25)	0.85	2497.6	31100.00
2	2797.64	48.97	0.962	0.30 ( 0.25)	0.83	4071.9	13210.00
3	2799.68	49.10	0.961	0.30 ( 0.25)	0.83	4082.0	13200.00
4	2803.58	51.64	0.936	0.30 ( 0.25)	0.83	4243.8	13100.00
5	2644.86	81.02	0.758	0.30 ( 0.25)	0.83	5536.8	13000.00
6	2597.35	83.42	0.746	0.30 ( 0.25)	0.83	5555.5	13010.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE (CFS) = 2803.58 Tc (MIN.) = 51.64  
 AREA-AVERAGED Fm (INCH/HR) = 0.25 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.83 EFFECTIVE AREA (ACRES) = 4243.80

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 51.64  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.936  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER "BARREN"	B	7.80	0.30	1.000	86
AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	1.70	0.30	1.000	79
NATURAL POOR COVER "BARREN"	B	9.40	0.30	1.000	86
NATURAL FAIR COVER "OPEN BRUSH"	B	1.20	0.30	1.000	66
RESIDENTIAL ".4 DWELLING/ACRE"	B	0.10	0.30	0.900	56
AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	2.60	0.30	1.000	79

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 22.80 SUBAREA RUNOFF(CFS) = 13.05  
 EFFECTIVE AREA(ACRES) = 4266.60 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA(ACRES) = 5578.3 PEAK FLOW RATE(CFS) = 2803.58  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 51.64  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.936  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.20	0.30	1.000	65
NATURAL FAIR COVER "OPEN BRUSH"	B	0.30	0.30	1.000	66
RESIDENTIAL ".4 DWELLING/ACRE"	B	0.20	0.30	0.900	56
AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	2.70	0.30	1.000	79

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.994  
 SUBAREA AREA(ACRES) = 3.40 SUBAREA RUNOFF(CFS) = 1.95  
 EFFECTIVE AREA(ACRES) = 4270.00 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA(ACRES) = 5581.7 PEAK FLOW RATE(CFS) = 2803.58  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13304.00 TO NODE 13305.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 350.00 DOWNSTREAM(FEET) = 315.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 2966.27 CHANNEL SLOPE = 0.0118  
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 4.57  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.890  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "GRASS"	B	27.40	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2810.86  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.64  
 AVERAGE FLOW DEPTH(FEET) = 4.57 TRAVEL TIME(MIN.) = 5.13  
 Tc(MIN.) = 56.76  
 SUBAREA AREA(ACRES) = 27.40 SUBAREA RUNOFF(CFS) = 14.56  
 EFFECTIVE AREA(ACRES) = 4297.40 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84  
 TOTAL AREA(ACRES) = 5609.1 PEAK FLOW RATE(CFS) = 2803.58  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 4.57

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 4.57 FLOW VELOCITY(FEET/SEC.) = 9.64  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap (ACRES)	Ae (ACRES)	HEADWATER NODE
1	2438.32	36.85	1.125	0.30( 0.26)	0.85	2551.2	31100.00
2	2797.64	54.10	0.914	0.30( 0.25)	0.84	4125.5	13210.00
3	2799.68	54.23	0.913	0.30( 0.25)	0.84	4135.6	13200.00
4	2803.58	56.76	0.890	0.30( 0.25)	0.84	4297.4	13100.00
5	2644.86	86.25	0.732	0.30( 0.25)	0.83	5590.4	13000.00
6	2597.35	88.68	0.721	0.30( 0.25)	0.83	5609.1	13010.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE(CFS) = 2803.58 Tc(MIN.) = 56.76  
 AREA-AVERAGED Fm(INCH/HR) = 0.25 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.84 EFFECTIVE AREA(ACRES) = 4297.40

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 56.76  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.890  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER "BARREN"	B	18.40	0.30	1.000	86
NATURAL FAIR COVER "MEADOWS"	B	1.20	0.30	1.000	70
NATURAL FAIR COVER					

"WOODLAND,GRASS" B 0.10 0.30 1.000 65  
 NATURAL POOR COVER  
 "BARREN" B 26.60 0.30 1.000 86  
 COMMERCIAL B 3.90 0.30 0.100 56  
 AGRICULTURAL POOR COVER  
 "FALLOW" B 3.00 0.30 1.000 86  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.934  
 SUBAREA AREA (ACRES) = 53.20 SUBAREA RUNOFF (CFS) = 29.22  
 EFFECTIVE AREA (ACRES) = 4350.60 AREA-AVERAGED Fm (INCH/HR) = 0.25  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84  
 TOTAL AREA (ACRES) = 5662.3 PEAK FLOW RATE (CFS) = 2803.58  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 56.76  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.890  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 AGRICULTURAL POOR COVER  
 "ROW CROPS, CONTOURED" B 1.10 0.30 1.000 79  
 NATURAL FAIR COVER  
 "WOODLAND, GRASS" B 0.20 0.30 1.000 65  
 NATURAL POOR COVER  
 "BARREN" B 14.00 0.30 1.000 86  
 COMMERCIAL B 4.30 0.30 0.100 56  
 AGRICULTURAL POOR COVER  
 "FALLOW" B 5.30 0.30 1.000 86  
 NATURAL FAIR COVER  
 "GRASS" B 2.70 0.30 1.000 69  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.860  
 SUBAREA AREA (ACRES) = 27.60 SUBAREA RUNOFF (CFS) = 15.71  
 EFFECTIVE AREA (ACRES) = 4378.20 AREA-AVERAGED Fm (INCH/HR) = 0.25  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84  
 TOTAL AREA (ACRES) = 5689.9 PEAK FLOW RATE (CFS) = 2803.58  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 56.76  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.890  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL FAIR COVER  
 "MEADOWS" B 3.20 0.30 1.000 70  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 6.10 0.30 1.000 66  
 RESIDENTIAL

".4 DWELLING/ACRE" B 7.50 0.30 0.900 56  
 AGRICULTURAL POOR COVER  
 "ROW CROPS, CONTOURED" B 5.40 0.30 1.000 79  
 NATURAL FAIR COVER  
 "WOODLAND, GRASS" B 1.60 0.30 1.000 65  
 NATURAL POOR COVER  
 "BARREN" B 1.90 0.30 1.000 86  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.971  
 SUBAREA AREA (ACRES) = 25.70 SUBAREA RUNOFF (CFS) = 13.86  
 EFFECTIVE AREA (ACRES) = 4403.90 AREA-AVERAGED Fm (INCH/HR) = 0.25  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84  
 TOTAL AREA (ACRES) = 5715.6 PEAK FLOW RATE (CFS) = 2803.58  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 56.76  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.890  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 COMMERCIAL B 2.00 0.30 0.100 56  
 AGRICULTURAL POOR COVER  
 "FALLOW" B 3.70 0.30 1.000 86  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 2.10 0.30 1.000 66  
 RESIDENTIAL  
 ".4 DWELLING/ACRE" B 2.60 0.30 0.900 56  
 AGRICULTURAL POOR COVER  
 "ROW CROPS, CONTOURED" B 0.20 0.30 1.000 79  
 NATURAL FAIR COVER  
 "WOODLAND, GRASS" B 0.10 0.30 1.000 65  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.807  
 SUBAREA AREA (ACRES) = 10.70 SUBAREA RUNOFF (CFS) = 6.24  
 EFFECTIVE AREA (ACRES) = 4414.60 AREA-AVERAGED Fm (INCH/HR) = 0.25  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84  
 TOTAL AREA (ACRES) = 5726.3 PEAK FLOW RATE (CFS) = 2803.58  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 56.76  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.890  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 0.50 0.30 1.000 66  
 RESIDENTIAL  
 ".4 DWELLING/ACRE" B 8.20 0.30 0.900 56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.906  
 SUBAREA AREA(ACRES) = 8.70 SUBAREA RUNOFF(CFS) = 4.84  
 EFFECTIVE AREA(ACRES) = 4423.30 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84  
 TOTAL AREA(ACRES) = 5735.0 PEAK FLOW RATE(CFS) = 2803.58  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 3A10EVRL.DNA  
 MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	742.59	14.11	0.30( 0.13)	0.43	433.8	120.00
2	739.67	14.27	0.30( 0.13)	0.43	436.5	110.00
3	635.72	21.58	0.30( 0.13)	0.43	503.8	100.00
4	587.61	24.64	0.30( 0.13)	0.43	510.2	150.00
TOTAL AREA(ACRES) =						510.2

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2438.32	36.85	1.125	0.30( 0.26)	0.85	2677.1	31100.00
2	2797.64	54.10	0.914	0.30( 0.25)	0.84	4251.4	13210.00
3	2799.68	54.23	0.913	0.30( 0.25)	0.84	4261.5	13200.00
4	2803.58	56.76	0.890	0.30( 0.25)	0.84	4423.3	13100.00
5	2644.86	86.25	0.732	0.30( 0.25)	0.83	5716.3	13000.00
6	2597.35	88.68	0.721	0.30( 0.25)	0.83	5735.0	13010.00
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 =							41886.54 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	742.59	14.11	1.980	0.30( 0.13)	0.43	433.8	120.00
2	739.67	14.27	1.959	0.30( 0.13)	0.43	436.5	110.00
3	635.72	21.58	1.529	0.30( 0.13)	0.43	503.8	100.00
4	587.61	24.64	1.406	0.30( 0.13)	0.43	510.2	150.00
LONGEST FLOWPATH FROM NODE 150.00 TO NODE 13305.00 =							9867.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2593.58	14.11	1.980	0.30( 0.22)	0.73	1458.6	120.00
2	2588.93	14.27	1.959	0.30( 0.22)	0.73	1472.9	110.00
3	2726.98	21.58	1.529	0.30( 0.22)	0.75	2071.4	100.00
4	2743.52	24.64	1.406	0.30( 0.23)	0.76	2299.9	150.00
5	2896.77	36.85	1.125	0.30( 0.24)	0.79	3187.3	31100.00
6	3158.73	54.10	0.914	0.30( 0.24)	0.80	4761.6	13210.00

7	3160.24	54.23	0.913	0.30( 0.24)	0.80	4771.7	13200.00
8	3153.87	56.76	0.890	0.30( 0.24)	0.80	4933.5	13100.00
9	2922.37	86.25	0.732	0.30( 0.24)	0.80	6226.5	13000.00
10	2869.36	88.68	0.721	0.30( 0.24)	0.80	6245.2	13010.00
TOTAL AREA(ACRES) =						6245.2	

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 3160.24 Tc(MIN.) = 54.231  
 EFFECTIVE AREA(ACRES) = 4771.66 AREA-AVERAGED Fm(INCH/HR) = 0.24  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.75  
 TOTAL AREA(ACRES) = 6245.2  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13306.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 315.00 DOWNSTREAM(FEET) = 245.50  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 4408.41 CHANNEL SLOPE = 0.0158  
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 4.52  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.858  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCSSOIL AREA Fp Ap SCSS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 PUBLIC PARK B 68.80 0.30 0.850 56  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.850  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3178.90  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.07  
 AVERAGE FLOW DEPTH(FEET) = 4.52 TRAVEL TIME(MIN.) = 6.64  
 Tc(MIN.) = 60.87  
 SUBAREA AREA(ACRES) = 68.80 SUBAREA RUNOFF(CFS) = 37.32  
 EFFECTIVE AREA(ACRES) = 4840.46 AREA-AVERAGED Fm(INCH/HR) = 0.24  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80  
 TOTAL AREA(ACRES) = 6314.0 PEAK FLOW RATE(CFS) = 3160.24  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 4.50

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 4.50 FLOW VELOCITY(FEET/SEC.) = 11.05  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13306.00 = 46294.95 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2593.58	21.16	1.546	0.30( 0.22)	0.73	1527.4	120.00

2	2588.93	21.33	1.539	0.30	( 0.22)	0.73	1541.7	110.00
3	2726.98	28.52	1.292	0.30	( 0.23)	0.75	2140.2	100.00
4	2743.52	31.57	1.221	0.30	( 0.23)	0.76	2368.7	150.00
5	2896.77	43.67	1.025	0.30	( 0.24)	0.79	3256.1	31100.00
6	3158.73	60.74	0.858	0.30	( 0.24)	0.80	4830.4	13210.00
7	3160.24	60.87	0.858	0.30	( 0.24)	0.80	4840.5	13200.00
8	3153.87	63.41	0.845	0.30	( 0.24)	0.80	5002.3	13100.00
9	2922.37	93.06	0.705	0.30	( 0.24)	0.80	6295.3	13000.00
10	2869.36	95.52	0.699	0.30	( 0.24)	0.80	6314.0	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 3160.24 Tc(MIN.) = 60.87  
 AREA-AVERAGED Fm(INCH/HR) = 0.24 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.80 EFFECTIVE AREA(ACRES) = 4840.46

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 60.87  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.858  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	21.50	0.30	1.000	86
COMMERCIAL	B	15.30	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	0.80	0.30	1.000	69
AGRICULTURAL FAIR COVER					
"ORCHARDS"	B	0.60	0.30	1.000	65
RESIDENTIAL					
".4 DWELLING/ACRE"	B	8.00	0.30	0.900	56
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.10	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.685  
 SUBAREA AREA(ACRES) = 46.30 SUBAREA RUNOFF(CFS) = 27.17  
 EFFECTIVE AREA(ACRES) = 4886.76 AREA-AVERAGED Fm(INCH/HR) = 0.24  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80  
 TOTAL AREA(ACRES) = 6360.3 PEAK FLOW RATE(CFS) = 3160.24  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 60.87  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.858  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	43.30	0.30	1.000	86
COMMERCIAL	B	4.90	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	5.70	0.30	1.000	69

AGRICULTURAL FAIR COVER

"ORCHARDS"	B	0.50	0.30	1.000	65
PUBLIC PARK	B	1.10	0.30	0.850	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	3.10	0.30	0.900	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.917  
 SUBAREA AREA(ACRES) = 58.60 SUBAREA RUNOFF(CFS) = 30.73  
 EFFECTIVE AREA(ACRES) = 4945.36 AREA-AVERAGED Fm(INCH/HR) = 0.24  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80  
 TOTAL AREA(ACRES) = 6418.9 PEAK FLOW RATE(CFS) = 3160.24  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 60.87  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.858  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	6.80	0.30	1.000	65
NATURAL POOR COVER					
"BARREN"	B	0.70	0.30	1.000	86
COMMERCIAL	B	1.10	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	0.50	0.30	1.000	69
AGRICULTURAL FAIR COVER					
"ORCHARDS"	B	0.10	0.30	1.000	65
PUBLIC PARK	B	0.50	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.890  
 SUBAREA AREA(ACRES) = 9.70 SUBAREA RUNOFF(CFS) = 5.16  
 EFFECTIVE AREA(ACRES) = 4955.06 AREA-AVERAGED Fm(INCH/HR) = 0.24  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80  
 TOTAL AREA(ACRES) = 6428.6 PEAK FLOW RATE(CFS) = 3160.24  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 60.87  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.858  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL					
".4 DWELLING/ACRE"	B	2.20	0.30	0.900	56
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.10	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.904  
 SUBAREA AREA(ACRES) = 2.30 SUBAREA RUNOFF(CFS) = 1.21

EFFECTIVE AREA (ACRES) = 4957.36 AREA-AVERAGED Fm (INCH/HR) = 0.24  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80  
 TOTAL AREA (ACRES) = 6430.9 PEAK FLOW RATE (CFS) = 3160.24  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13306.00 TO NODE 13307.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM (FEET) = 245.50 DOWNSTREAM (FEET) = 220.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1543.21 CHANNEL SLOPE = 0.0165  
 GIVEN CHANNEL BASE (FEET) = 50.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 4.45  
 CHANNEL FLOW THRU SUBAREA (CFS) = 3160.24  
 FLOW VELOCITY (FEET/SEC.) = 11.23 FLOW DEPTH (FEET) = 4.45  
 TRAVEL TIME (MIN.) = 2.29 Tc (MIN.) = 63.16  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13307.00 = 47838.16 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2593.58	23.60	1.448	0.30 ( 0.22)	0.74	1644.3	120.00
2	2588.93	23.77	1.441	0.30 ( 0.22)	0.74	1658.6	110.00
3	2726.98	30.93	1.233	0.30 ( 0.23)	0.76	2257.1	100.00
4	2743.52	33.97	1.178	0.30 ( 0.23)	0.77	2485.6	150.00
5	2896.77	46.03	0.997	0.30 ( 0.24)	0.79	3373.0	31100.00
6	3158.73	63.03	0.847	0.30 ( 0.24)	0.80	4947.3	13210.00
7	3160.24	63.16	0.846	0.30 ( 0.24)	0.80	4957.4	13200.00
8	3153.87	65.70	0.834	0.30 ( 0.24)	0.80	5119.2	13100.00
9	2922.37	95.41	0.699	0.30 ( 0.24)	0.80	6412.2	13000.00
10	2869.36	97.89	0.692	0.30 ( 0.24)	0.80	6430.9	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 3160.24 Tc (MIN.) = 63.16  
 AREA-AVERAGED Fm (INCH/HR) = 0.24 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.80 EFFECTIVE AREA (ACRES) = 4957.36

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13307.00 TO NODE 13307.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 =====

MAINLINE Tc (MIN.) = 63.16  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.846

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	0.20	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	0.10	0.30	1.000	69
AGRICULTURAL FAIR COVER					
"ORCHARDS"	B	0.20	0.30	1.000	65
NATURAL POOR COVER					
"BARREN"	B	3.70	0.30	1.000	86
COMMERCIAL	B	0.30	0.30	0.100	56
NATURAL FAIR COVER					

"GRASS" B 3.20 0.30 1.000 69  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.942  
 SUBAREA AREA (ACRES) = 7.70 SUBAREA RUNOFF (CFS) = 3.91  
 EFFECTIVE AREA (ACRES) = 4965.06 AREA-AVERAGED Fm (INCH/HR) = 0.24  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80  
 TOTAL AREA (ACRES) = 6438.6 PEAK FLOW RATE (CFS) = 3160.24  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13307.00 TO NODE 13307.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 =====

MAINLINE Tc (MIN.) = 63.16  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.846  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL FAIR COVER  
 "WOODLAND, GRASS" B 3.60 0.30 1.000 65  
 NATURAL FAIR COVER  
 "GRASS" B 1.90 0.30 1.000 69  
 NATURAL FAIR COVER  
 "WOODLAND, GRASS" B 0.60 0.30 1.000 65  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 6.10 SUBAREA RUNOFF (CFS) = 3.00  
 EFFECTIVE AREA (ACRES) = 4971.16 AREA-AVERAGED Fm (INCH/HR) = 0.24  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80  
 TOTAL AREA (ACRES) = 6444.7 PEAK FLOW RATE (CFS) = 3160.24  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13307.00 TO NODE 13308.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM (FEET) = 220.00 DOWNSTREAM (FEET) = 212.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 925.62 CHANNEL SLOPE = 0.0086  
 GIVEN CHANNEL BASE (FEET) = 50.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 5.33  
 CHANNEL FLOW THRU SUBAREA (CFS) = 3160.24  
 FLOW VELOCITY (FEET/SEC.) = 8.99 FLOW DEPTH (FEET) = 5.33  
 TRAVEL TIME (MIN.) = 1.72 Tc (MIN.) = 64.88  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13308.00 = 48763.78 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2593.58	25.43	1.379	0.30 ( 0.22)	0.74	1658.1	120.00
2	2588.93	25.60	1.374	0.30 ( 0.22)	0.74	1672.4	110.00
3	2726.98	32.72	1.200	0.30 ( 0.23)	0.76	2270.9	100.00
4	2743.52	35.76	1.145	0.30 ( 0.23)	0.77	2499.4	150.00
5	2896.77	47.79	0.976	0.30 ( 0.24)	0.79	3386.8	31100.00
6	3158.73	64.75	0.839	0.30 ( 0.24)	0.80	4961.1	13210.00



7	3160.24	64.88	0.838	0.30	( 0.24)	0.80	4971.2	13200.00
8	3153.87	67.41	0.825	0.30	( 0.24)	0.80	5133.0	13100.00
9	2922.37	97.17	0.694	0.30	( 0.24)	0.80	6426.0	13000.00
10	2869.36	99.65	0.687	0.30	( 0.24)	0.80	6444.7	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 3160.24 Tc(MIN.) = 64.88  
 AREA-AVERAGED Fm(INCH/HR) = 0.24 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.80 EFFECTIVE AREA(ACRES) = 4971.16

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 64.88  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.838  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	0.10	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.20	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	5.00	0.30	1.000	65
COMMERCIAL	B	3.20	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	0.10	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.90	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.697  
 SUBAREA AREA(ACRES) = 9.50 SUBAREA RUNOFF(CFS) = 5.38  
 EFFECTIVE AREA(ACRES) = 4980.66 AREA-AVERAGED Fm(INCH/HR) = 0.24  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80  
 TOTAL AREA(ACRES) = 6454.2 PEAK FLOW RATE(CFS) = 3160.24  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 64.88  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.838  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
APARTMENTS	B	0.30	0.30	0.200	56
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	1.00	0.30	1.000	63
COMMERCIAL	B	41.90	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	7.20	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	25.00	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.498  
 SUBAREA AREA(ACRES) = 75.60 SUBAREA RUNOFF(CFS) = 46.85  
 EFFECTIVE AREA(ACRES) = 5056.26 AREA-AVERAGED Fm(INCH/HR) = 0.24  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA(ACRES) = 6529.8 PEAK FLOW RATE(CFS) = 3160.24  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 64.88  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.838  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	0.10	0.30	0.850	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	0.90	0.30	1.000	79
SCHOOL	B	0.30	0.30	0.600	56
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	13.20	0.30	1.000	65
APARTMENTS	B	0.50	0.30	0.200	56
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	0.60	0.30	1.000	63

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.966  
 SUBAREA AREA(ACRES) = 15.60 SUBAREA RUNOFF(CFS) = 7.70  
 EFFECTIVE AREA(ACRES) = 5071.86 AREA-AVERAGED Fm(INCH/HR) = 0.24  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA(ACRES) = 6545.4 PEAK FLOW RATE(CFS) = 3160.24  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 64.88  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.838  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	33.90	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	17.60	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	16.80	0.30	1.000	66
RESIDENTIAL					
"11+ DWELLINGS/ACRE"	B	0.60	0.30	0.200	56
RESIDENTIAL					
"8-10 DWELLINGS/ACRE"	B	1.50	0.30	0.400	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	10.00	0.30	1.000	79

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.603

SUBAREA AREA (ACRES) = 80.40 SUBAREA RUNOFF (CFS) = 47.54  
 EFFECTIVE AREA (ACRES) = 5152.26 AREA-AVERAGED Fm (INCH/HR) = 0.24  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA (ACRES) = 6625.8 PEAK FLOW RATE (CFS) = 3160.24  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 64.88  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.838  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 SCHOOL B 0.30 0.30 0.600 56  
 NATURAL FAIR COVER  
 "WOODLAND, GRASS" B 0.70 0.30 1.000 65  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.880  
 SUBAREA AREA (ACRES) = 1.00 SUBAREA RUNOFF (CFS) = 0.52  
 EFFECTIVE AREA (ACRES) = 5153.26 AREA-AVERAGED Fm (INCH/HR) = 0.24  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA (ACRES) = 6626.8 PEAK FLOW RATE (CFS) = 3160.24  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 64.88  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.838  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL FAIR COVER  
 "GRASS" B 0.30 0.30 1.000 69  
 NATURAL FAIR COVER  
 "WOODLAND, GRASS" B 0.80 0.30 1.000 65  
 NATURAL FAIR COVER  
 "GRASS" B 0.50 0.30 1.000 69  
 NATURAL FAIR COVER  
 "WOODLAND, GRASS" B 0.20 0.30 1.000 65  
 NATURAL FAIR COVER  
 "GRASS" B 0.30 0.30 1.000 69  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 2.10 SUBAREA RUNOFF (CFS) = 1.02  
 EFFECTIVE AREA (ACRES) = 5155.36 AREA-AVERAGED Fm (INCH/HR) = 0.24  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA (ACRES) = 6628.9 PEAK FLOW RATE (CFS) = 3160.24  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 64.88  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.838  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL FAIR COVER  
 "GRASS" B 1.20 0.30 1.000 69  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 0.50 0.30 1.000 66  
 PUBLIC PARK B 1.70 0.30 0.850 56  
 NATURAL FAIR COVER  
 "WOODLAND, GRASS" B 7.20 0.30 1.000 65  
 NATURAL FAIR COVER  
 "GRASS" B 1.00 0.30 1.000 69  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.978  
 SUBAREA AREA (ACRES) = 11.60 SUBAREA RUNOFF (CFS) = 5.68  
 EFFECTIVE AREA (ACRES) = 5166.96 AREA-AVERAGED Fm (INCH/HR) = 0.24  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA (ACRES) = 6640.5 PEAK FLOW RATE (CFS) = 3160.24  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 10  
 -----

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: R110EV29.DNA  
 MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13467.98	19.78	0.30 ( 0.25)	0.82	3695.9	50400.00
2	15304.03	30.60	0.30 ( 0.25)	0.83	6215.8	50300.00
3	16871.63	40.82	0.30 ( 0.26)	0.85	8976.4	50100.00
4	17974.30	48.60	0.30 ( 0.26)	0.88	11444.9	390.00
5	19165.65	59.96	0.30 ( 0.27)	0.91	15282.7	40100.00
6	19896.21	70.59	0.30 ( 0.28)	0.92	18548.0	11801.00
7	21110.69	84.20	0.30 ( 0.28)	0.94	23542.3	11530.00
8	21946.32	92.39	0.30 ( 0.28)	0.95	27410.4	11900.00
9	23431.81	102.10	0.30 ( 0.29)	0.96	33239.1	11330.00
10	24273.27	110.31	0.30 ( 0.29)	0.96	38326.2	10630.00
11	24168.63	115.89	0.30 ( 0.29)	0.96	40916.1	12330.00
12	24039.03	122.50	0.30 ( 0.29)	0.96	44058.5	11600.00
13	23770.22	128.27	0.30 ( 0.29)	0.97	46292.8	11111.00
14	23470.12	134.38	0.30 ( 0.29)	0.97	48226.7	12201.00
15	22723.10	143.28	0.30 ( 0.29)	0.97	50314.9	12231.00
16	22026.91	150.73	0.30 ( 0.29)	0.97	51726.5	10400.00
17	20906.57	162.09	0.30 ( 0.29)	0.97	53347.2	10320.00
18	20319.22	166.92	0.30 ( 0.29)	0.97	53572.7	10210.00
19	19809.11	171.76	0.30 ( 0.29)	0.97	53735.1	12000.00

20 17148.21 200.80 0.30( 0.29) 0.97 54352.1 10100.00  
TOTAL AREA(ACRES) = 54352.1

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 14.0

=====  
>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<<  
=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13467.98	19.78	0.30( 0.25)	0.82	3695.9	50400.00
2	15304.03	30.60	0.30( 0.25)	0.83	6215.8	50300.00
3	16871.63	40.82	0.30( 0.26)	0.85	8976.4	50100.00
4	17974.30	48.60	0.30( 0.26)	0.88	11444.9	390.00
5	19165.65	59.96	0.30( 0.27)	0.91	15282.7	40100.00
6	19896.21	70.59	0.30( 0.28)	0.92	18548.0	11801.00
7	21110.69	84.20	0.30( 0.28)	0.94	23542.3	11530.00
8	21946.32	92.39	0.30( 0.28)	0.95	27410.4	11900.00
9	23431.81	102.10	0.30( 0.29)	0.96	33239.1	11330.00
10	24273.27	110.31	0.30( 0.29)	0.96	38326.2	10630.00
11	24168.63	115.89	0.30( 0.29)	0.96	40916.1	12330.00
12	24039.03	122.50	0.30( 0.29)	0.96	44058.5	11600.00
13	23770.22	128.27	0.30( 0.29)	0.97	46292.8	11111.00
14	23470.12	134.38	0.30( 0.29)	0.97	48226.7	12201.00
15	22723.10	143.28	0.30( 0.29)	0.97	50314.9	12231.00
16	22026.91	150.73	0.30( 0.29)	0.97	51726.5	10400.00
17	20906.57	162.09	0.30( 0.29)	0.97	53347.2	10320.00
18	20319.22	166.92	0.30( 0.29)	0.97	53572.7	10210.00
19	19809.11	171.76	0.30( 0.29)	0.97	53735.1	12000.00
20	17148.21	200.80	0.30( 0.29)	0.97	54352.1	10100.00

TOTAL AREA(ACRES) = 54352.1

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12904.00 TO NODE 13308.00 IS CODE = 56

=====  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<<  
=====

ELEVATION DATA: UPSTREAM(FEET) = 213.00 DOWNSTREAM(FEET) = 212.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1389.52 CHANNEL SLOPE = 0.0007  
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 13.81  
CHANNEL FLOW THRU SUBAREA(CFS) = 24273.27  
FLOW VELOCITY(FEET/SEC.) = 6.54 FLOW DEPTH(FEET) = 13.81  
TRAVEL TIME(MIN.) = 3.54 Tc(MIN.) = 113.86  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118090.66 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13467.98	24.05	1.429	0.30( 0.25)	0.82	3695.9	50400.00
2	15304.03	34.70	1.164	0.30( 0.25)	0.83	6215.8	50300.00
3	16871.63	44.79	1.011	0.30( 0.26)	0.85	8976.4	50100.00
4	17974.30	52.50	0.928	0.30( 0.26)	0.88	11444.9	390.00
5	19165.65	63.78	0.843	0.30( 0.27)	0.91	15282.7	40100.00

6	19896.21	74.37	0.791	0.30( 0.28)	0.92	18548.0	11801.00
7	21110.69	87.91	0.724	0.30( 0.28)	0.94	23542.3	11530.00
8	21946.32	96.05	0.697	0.30( 0.28)	0.95	27410.4	11900.00
9	23431.81	105.69	0.670	0.30( 0.29)	0.96	33239.1	11330.00
10	24273.27	113.86	0.647	0.30( 0.29)	0.96	38326.2	10630.00
11	24168.63	119.44	0.632	0.30( 0.29)	0.96	40916.1	12330.00
12	24039.03	126.06	0.620	0.30( 0.29)	0.96	44058.5	11600.00
13	23770.22	131.83	0.610	0.30( 0.29)	0.97	46292.8	11111.00
14	23470.12	137.96	0.599	0.30( 0.29)	0.97	48226.7	12201.00
15	22723.10	146.90	0.584	0.30( 0.29)	0.97	50314.9	12231.00
16	22026.91	154.39	0.572	0.30( 0.29)	0.97	51726.5	10400.00
17	20906.57	165.80	0.552	0.30( 0.29)	0.97	53347.2	10320.00
18	20319.22	170.67	0.544	0.30( 0.29)	0.97	53572.7	10210.00
19	19809.11	175.54	0.536	0.30( 0.29)	0.97	53735.1	12000.00
20	17148.21	204.75	0.509	0.30( 0.29)	0.97	54352.1	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 24273.27 Tc(MIN.) = 113.86

AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.96 EFFECTIVE AREA(ACRES) = 38326.20

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13307.00 TO NODE 13308.00 IS CODE = 11

=====  
>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<<  
=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13467.98	24.05	1.429	0.30( 0.25)	0.82	3695.9	50400.00
2	15304.03	34.70	1.164	0.30( 0.25)	0.83	6215.8	50300.00
3	16871.63	44.79	1.011	0.30( 0.26)	0.85	8976.4	50100.00
4	17974.30	52.50	0.928	0.30( 0.26)	0.88	11444.9	390.00
5	19165.65	63.78	0.843	0.30( 0.27)	0.91	15282.7	40100.00
6	19896.21	74.37	0.791	0.30( 0.28)	0.92	18548.0	11801.00
7	21110.69	87.91	0.724	0.30( 0.28)	0.94	23542.3	11530.00
8	21946.32	96.05	0.697	0.30( 0.28)	0.95	27410.4	11900.00
9	23431.81	105.69	0.670	0.30( 0.29)	0.96	33239.1	11330.00
10	24273.27	113.86	0.647	0.30( 0.29)	0.96	38326.2	10630.00
11	24168.63	119.44	0.632	0.30( 0.29)	0.96	40916.1	12330.00
12	24039.03	126.06	0.620	0.30( 0.29)	0.96	44058.5	11600.00
13	23770.22	131.83	0.610	0.30( 0.29)	0.97	46292.8	11111.00
14	23470.12	137.96	0.599	0.30( 0.29)	0.97	48226.7	12201.00
15	22723.10	146.90	0.584	0.30( 0.29)	0.97	50314.9	12231.00
16	22026.91	154.39	0.572	0.30( 0.29)	0.97	51726.5	10400.00
17	20906.57	165.80	0.552	0.30( 0.29)	0.97	53347.2	10320.00
18	20319.22	170.67	0.544	0.30( 0.29)	0.97	53572.7	10210.00
19	19809.11	175.54	0.536	0.30( 0.29)	0.97	53735.1	12000.00
20	17148.21	204.75	0.509	0.30( 0.29)	0.97	54352.1	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118090.66 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2593.58	25.43	1.379	0.30( 0.22)	0.73	1853.9	120.00
2	2588.93	25.60	1.374	0.30( 0.22)	0.73	1868.2	110.00
3	2726.98	32.72	1.200	0.30( 0.22)	0.75	2466.7	100.00
4	2743.52	35.76	1.145	0.30( 0.23)	0.76	2695.2	150.00

5	2896.77	47.79	0.976	0.30 ( 0.23)	0.78	3582.6	31100.00
6	3158.73	64.75	0.839	0.30 ( 0.24)	0.79	5156.9	13210.00
7	3160.24	64.88	0.838	0.30 ( 0.24)	0.79	5167.0	13200.00
8	3153.87	67.41	0.825	0.30 ( 0.24)	0.79	5328.8	13100.00
9	2922.37	97.17	0.694	0.30 ( 0.24)	0.79	6621.8	13000.00
10	2869.36	99.65	0.687	0.30 ( 0.24)	0.79	6640.5	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13308.00 = 48763.78 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	16027.85	24.05	1.429	0.30 ( 0.24)	0.79	5449.8	50400.00
2	16298.10	25.43	1.379	0.30 ( 0.24)	0.79	5874.4	120.00
3	16322.75	25.60	1.374	0.30 ( 0.24)	0.80	5928.9	110.00
4	17689.82	32.72	1.200	0.30 ( 0.24)	0.81	8214.2	100.00
5	18041.78	34.70	1.164	0.30 ( 0.24)	0.81	8831.3	50300.00
6	18211.97	35.76	1.145	0.30 ( 0.24)	0.81	9200.5	150.00
7	19730.19	44.79	1.011	0.30 ( 0.25)	0.83	12337.7	50100.00
8	20197.85	47.79	0.976	0.30 ( 0.25)	0.84	13520.4	31100.00
9	20943.71	52.50	0.928	0.30 ( 0.26)	0.85	15464.1	390.00
10	22309.35	63.78	0.843	0.30 ( 0.26)	0.88	20349.3	40100.00
11	22391.54	64.75	0.839	0.30 ( 0.26)	0.88	20739.8	13210.00
12	22401.77	64.88	0.838	0.30 ( 0.26)	0.88	20788.8	13200.00
13	22570.43	67.41	0.825	0.30 ( 0.27)	0.88	21733.0	13100.00
14	22996.00	74.37	0.791	0.30 ( 0.27)	0.89	24178.9	11801.00
15	24105.12	87.91	0.724	0.30 ( 0.27)	0.91	29761.7	11530.00
16	24877.38	96.05	0.697	0.30 ( 0.28)	0.92	33983.8	11900.00
17	25040.66	97.17	0.694	0.30 ( 0.28)	0.92	34707.0	13000.00
18	25371.14	99.65	0.687	0.30 ( 0.28)	0.92	36230.4	13010.00
19	26193.19	105.69	0.670	0.30 ( 0.28)	0.93	39879.6	11330.00
20	26888.43	113.86	0.647	0.30 ( 0.28)	0.94	44966.7	10630.00
21	26683.87	119.44	0.632	0.30 ( 0.28)	0.94	47556.6	12330.00
22	26478.45	126.06	0.620	0.30 ( 0.28)	0.94	50699.0	11600.00
23	26146.88	131.83	0.610	0.30 ( 0.28)	0.94	52933.4	11111.00
24	25780.19	137.96	0.599	0.30 ( 0.28)	0.95	54867.2	12201.00
25	24936.08	146.90	0.584	0.30 ( 0.28)	0.95	56955.5	12231.00
26	24158.52	154.39	0.572	0.30 ( 0.28)	0.95	58367.0	10400.00
27	22914.15	165.80	0.552	0.30 ( 0.28)	0.95	59987.8	10320.00
28	22273.91	170.67	0.544	0.30 ( 0.28)	0.95	60213.3	10210.00
29	21710.90	175.54	0.536	0.30 ( 0.28)	0.95	60375.6	12000.00
30	18878.48	204.75	0.509	0.30 ( 0.28)	0.95	60992.6	10100.00

TOTAL AREA (ACRES) = 60992.6

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 26888.43 Tc (MIN.) = 113.858  
EFFECTIVE AREA (ACRES) = 44966.73 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.88  
TOTAL AREA (ACRES) = 60992.6  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118090.66 FEET.

=====  
END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 60992.6 TC (MIN.) = 113.86  
EFFECTIVE AREA (ACRES) = 44966.73 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.936  
PEAK FLOW RATE (CFS) = 26888.43

\*\* PEAK FLOW RATE TABLE \*\*

STREAM	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	--------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	16027.85	24.05	1.429	0.30 ( 0.24)	0.79	5449.8 50400.00
2	16298.10	25.43	1.379	0.30 ( 0.24)	0.79	5874.4 120.00
3	16322.75	25.60	1.374	0.30 ( 0.24)	0.80	5928.9 110.00
4	17689.82	32.72	1.200	0.30 ( 0.24)	0.81	8214.2 100.00
5	18041.78	34.70	1.164	0.30 ( 0.24)	0.81	8831.3 50300.00
6	18211.97	35.76	1.145	0.30 ( 0.24)	0.81	9200.5 150.00
7	19730.19	44.79	1.011	0.30 ( 0.25)	0.83	12337.7 50100.00
8	20197.85	47.79	0.976	0.30 ( 0.25)	0.84	13520.4 31100.00
9	20943.71	52.50	0.928	0.30 ( 0.26)	0.85	15464.1 390.00
10	22309.35	63.78	0.843	0.30 ( 0.26)	0.88	20349.3 40100.00
11	22391.54	64.75	0.839	0.30 ( 0.26)	0.88	20739.8 13210.00
12	22401.77	64.88	0.838	0.30 ( 0.26)	0.88	20788.8 13200.00
13	22570.43	67.41	0.825	0.30 ( 0.27)	0.88	21733.0 13100.00
14	22996.00	74.37	0.791	0.30 ( 0.27)	0.89	24178.9 11801.00
15	24105.12	87.91	0.724	0.30 ( 0.27)	0.91	29761.7 11530.00
16	24877.38	96.05	0.697	0.30 ( 0.28)	0.92	33983.8 11900.00
17	25040.66	97.17	0.694	0.30 ( 0.28)	0.92	34707.0 13000.00
18	25371.14	99.65	0.687	0.30 ( 0.28)	0.92	36230.4 13010.00
19	26193.19	105.69	0.670	0.30 ( 0.28)	0.93	39879.6 11330.00
20	26888.43	113.86	0.647	0.30 ( 0.28)	0.94	44966.7 10630.00
21	26683.87	119.44	0.632	0.30 ( 0.28)	0.94	47556.6 12330.00
22	26478.45	126.06	0.620	0.30 ( 0.28)	0.94	50699.0 11600.00
23	26146.88	131.83	0.610	0.30 ( 0.28)	0.94	52933.4 11111.00
24	25780.19	137.96	0.599	0.30 ( 0.28)	0.95	54867.2 12201.00
25	24936.08	146.90	0.584	0.30 ( 0.28)	0.95	56955.5 12231.00
26	24158.52	154.39	0.572	0.30 ( 0.28)	0.95	58367.0 10400.00
27	22914.15	165.80	0.552	0.30 ( 0.28)	0.95	59987.8 10320.00
28	22273.91	170.67	0.544	0.30 ( 0.28)	0.95	60213.3 10210.00
29	21710.90	175.54	0.536	0.30 ( 0.28)	0.95	60375.6 12000.00
30	18878.48	204.75	0.509	0.30 ( 0.28)	0.95	60992.6 10100.00

=====  
END OF RATIONAL METHOD ANALYSIS



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S34- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 10-YR RM EV APRIL 2019 CCHIU \*  
\*\*\*\*\*

FILE NAME: RI10EV34.DAT  
TIME/DATE OF STUDY: 10:16 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 10.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 3.757
- 2) 10.00; 2.507
- 3) 15.00; 1.859
- 4) 20.00; 1.590
- 5) 25.00; 1.388
- 6) 30.00; 1.248
- 7) 40.00; 1.066
- 8) 50.00; 0.948
- 9) 60.00; 0.860
- 10) 90.00; 0.712
- 11) 120.00; 0.627
- 12) 180.00; 0.525
- 13) 360.00; 0.386
- 14) 1200.00; 0.169

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER WIDTH (FT)	GEOMETRIES: LIP (FT)	MANNING HIKE (FT)	FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI10EV33.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	16322.75	25.60	0.30 ( 0.24)	0.80	5928.9	110.00
2	18211.97	35.76	0.30 ( 0.24)	0.81	9200.5	150.00
3	20197.85	47.79	0.30 ( 0.25)	0.84	13520.4	31100.00
4	20943.71	52.50	0.30 ( 0.26)	0.85	15464.1	390.00
5	22570.43	67.41	0.30 ( 0.27)	0.88	21733.0	13100.00
6	22996.00	74.37	0.30 ( 0.27)	0.89	24178.9	11801.00
7	24105.12	87.91	0.30 ( 0.27)	0.91	29761.7	11530.00
8	25371.14	99.65	0.30 ( 0.28)	0.92	36230.4	13010.00
9	26193.19	105.69	0.30 ( 0.28)	0.93	39879.6	11330.00
10	26888.43	113.86	0.30 ( 0.28)	0.94	44966.7	10630.00
11	26683.87	119.44	0.30 ( 0.28)	0.94	47556.6	12330.00
12	26478.45	126.06	0.30 ( 0.28)	0.94	50699.0	11600.00
13	26146.88	131.83	0.30 ( 0.28)	0.94	52933.4	11111.00
14	25780.19	137.96	0.30 ( 0.28)	0.95	54867.2	12201.00
15	24936.08	146.90	0.30 ( 0.28)	0.95	56955.5	12231.00
16	24158.52	154.39	0.30 ( 0.28)	0.95	58367.0	10400.00
17	22914.15	165.80	0.30 ( 0.28)	0.95	59987.8	10320.00
18	22273.91	170.67	0.30 ( 0.28)	0.95	60213.3	10210.00
19	21710.90	175.54	0.30 ( 0.28)	0.95	60375.6	12000.00
20	18878.48	204.75	0.30 ( 0.28)	0.95	60992.6	10100.00
TOTAL AREA (ACRES) =						60992.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	16322.75	25.60	0.30 ( 0.24)	0.80	5928.9	110.00
2	18211.97	35.76	0.30 ( 0.24)	0.81	9200.5	150.00
3	20197.85	47.79	0.30 ( 0.25)	0.84	13520.4	31100.00
4	20943.71	52.50	0.30 ( 0.26)	0.85	15464.1	390.00
5	22570.43	67.41	0.30 ( 0.27)	0.88	21733.0	13100.00
6	22996.00	74.37	0.30 ( 0.27)	0.89	24178.9	11801.00
7	24105.12	87.91	0.30 ( 0.27)	0.91	29761.7	11530.00
8	25371.14	99.65	0.30 ( 0.28)	0.92	36230.4	13010.00
9	26193.19	105.69	0.30 ( 0.28)	0.93	39879.6	11330.00
10	26888.43	113.86	0.30 ( 0.28)	0.94	44966.7	10630.00
11	26683.87	119.44	0.30 ( 0.28)	0.94	47556.6	12330.00
12	26478.45	126.06	0.30 ( 0.28)	0.94	50699.0	11600.00
13	26146.88	131.83	0.30 ( 0.28)	0.94	52933.4	11111.00

14	25780.19	137.96	0.30	( 0.28)	0.95	54867.2	12201.00
15	24936.08	146.90	0.30	( 0.28)	0.95	56955.5	12231.00
16	24158.52	154.39	0.30	( 0.28)	0.95	58367.0	10400.00
17	22914.15	165.80	0.30	( 0.28)	0.95	59987.8	10320.00
18	22273.91	170.67	0.30	( 0.28)	0.95	60213.3	10210.00
19	21710.90	175.54	0.30	( 0.28)	0.95	60375.6	12000.00
20	18878.48	204.75	0.30	( 0.28)	0.95	60992.6	10100.00

TOTAL AREA (ACRES) = 60992.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13402.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 215.00 DOWNSTREAM (FEET) = 209.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 623.02 CHANNEL SLOPE = 0.0096  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 7.05  
CHANNEL FLOW THRU SUBAREA (CFS) = 26888.43  
FLOW VELOCITY (FEET/SEC.) = 16.22 FLOW DEPTH (FEET) = 7.05  
TRAVEL TIME (MIN.) = 0.64 Tc (MIN.) = 114.50  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118713.68 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	16322.75	26.36	1.350	0.30 ( 0.24)	0.80	5928.9	110.00
2	18211.97	36.49	1.130	0.30 ( 0.24)	0.81	9200.5	150.00
3	20197.85	48.50	0.966	0.30 ( 0.25)	0.84	13520.4	31100.00
4	20943.71	53.19	0.920	0.30 ( 0.26)	0.85	15464.1	390.00
5	22570.43	68.09	0.820	0.30 ( 0.27)	0.88	21733.0	13100.00
6	22996.00	75.04	0.786	0.30 ( 0.27)	0.89	24178.9	11801.00
7	24105.12	88.57	0.719	0.30 ( 0.27)	0.91	29761.7	11530.00
8	25371.14	100.31	0.683	0.30 ( 0.28)	0.92	36230.4	13010.00
9	26193.19	106.33	0.666	0.30 ( 0.28)	0.93	39879.6	11330.00
10	26888.43	114.50	0.643	0.30 ( 0.28)	0.94	44966.7	10630.00
11	26683.87	120.08	0.627	0.30 ( 0.28)	0.94	47556.6	12330.00
12	26478.45	126.70	0.616	0.30 ( 0.28)	0.94	50699.0	11600.00
13	26146.88	132.48	0.606	0.30 ( 0.28)	0.94	52933.4	11111.00
14	25780.19	138.61	0.595	0.30 ( 0.28)	0.95	54867.2	12201.00
15	24936.08	147.55	0.580	0.30 ( 0.28)	0.95	56955.5	12231.00
16	24158.52	155.05	0.567	0.30 ( 0.28)	0.95	58367.0	10400.00
17	22914.15	166.48	0.548	0.30 ( 0.28)	0.95	59987.8	10320.00
18	22273.91	171.35	0.540	0.30 ( 0.28)	0.95	60213.3	10210.00
19	21710.90	176.23	0.531	0.30 ( 0.28)	0.95	60375.6	12000.00
20	18878.48	205.47	0.505	0.30 ( 0.28)	0.95	60992.6	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 26888.43 Tc (MIN.) = 114.50  
AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.94 EFFECTIVE AREA (ACRES) = 44966.73

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13402.00 TO NODE 13402.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610505V.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	172.78	21.02	0.30 ( 0.30)	0.99	153.2	50500.00

TOTAL AREA (ACRES) = 153.2

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13402.00 TO NODE 13402.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	16322.75	26.36	1.350	0.30 ( 0.24)	0.80	5928.9	110.00
2	18211.97	36.49	1.130	0.30 ( 0.24)	0.81	9200.5	150.00
3	20197.85	48.50	0.966	0.30 ( 0.25)	0.84	13520.4	31100.00
4	20943.71	53.19	0.920	0.30 ( 0.26)	0.85	15464.1	390.00
5	22570.43	68.09	0.820	0.30 ( 0.27)	0.88	21733.0	13100.00
6	22996.00	75.04	0.786	0.30 ( 0.27)	0.89	24178.9	11801.00
7	24105.12	88.57	0.719	0.30 ( 0.27)	0.91	29761.7	11530.00
8	25371.14	100.31	0.683	0.30 ( 0.28)	0.92	36230.4	13010.00
9	26193.19	106.33	0.666	0.30 ( 0.28)	0.93	39879.6	11330.00
10	26888.43	114.50	0.643	0.30 ( 0.28)	0.94	44966.7	10630.00
11	26683.87	120.08	0.627	0.30 ( 0.28)	0.94	47556.6	12330.00
12	26478.45	126.70	0.616	0.30 ( 0.28)	0.94	50699.0	11600.00
13	26146.88	132.48	0.606	0.30 ( 0.28)	0.94	52933.4	11111.00
14	25780.19	138.61	0.595	0.30 ( 0.28)	0.95	54867.2	12201.00
15	24936.08	147.55	0.580	0.30 ( 0.28)	0.95	56955.5	12231.00
16	24158.52	155.05	0.567	0.30 ( 0.28)	0.95	58367.0	10400.00
17	22914.15	166.48	0.548	0.30 ( 0.28)	0.95	59987.8	10320.00
18	22273.91	171.35	0.540	0.30 ( 0.28)	0.95	60213.3	10210.00
19	21710.90	176.23	0.531	0.30 ( 0.28)	0.95	60375.6	12000.00
20	18878.48	205.47	0.505	0.30 ( 0.28)	0.95	60992.6	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118713.68 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	172.78	21.02	1.549	0.30 ( 0.30)	0.99	153.2	50500.00

LONGEST FLOWPATH FROM NODE 50500.00 TO NODE 13402.00 = 6247.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15518.65	21.02	1.549	0.30 ( 0.24)	0.80	4881.7	50500.00
2	16468.12	26.36	1.350	0.30 ( 0.24)	0.80	6082.1	110.00
3	18326.98	36.49	1.130	0.30 ( 0.24)	0.82	9353.7	150.00
4	20290.22	48.50	0.966	0.30 ( 0.25)	0.84	13673.6	31100.00
5	21029.77	53.19	0.920	0.30 ( 0.26)	0.85	15617.3	390.00
6	22642.72	68.09	0.820	0.30 ( 0.27)	0.88	21886.1	13100.00
7	23063.56	75.04	0.786	0.30 ( 0.27)	0.89	24332.0	11801.00
8	24163.48	88.57	0.719	0.30 ( 0.27)	0.91	29914.8	11530.00
9	25424.50	100.31	0.683	0.30 ( 0.28)	0.92	36383.6	13010.00
10	26244.19	106.33	0.666	0.30 ( 0.28)	0.93	40032.8	11330.00
11	26936.24	114.50	0.643	0.30 ( 0.28)	0.94	45119.9	10630.00

12 26729.52 120.08 0.627 0.30( 0.28) 0.94 47709.8 12330.00  
 13 26522.54 126.70 0.616 0.30( 0.28) 0.94 50852.2 11600.00  
 14 26189.62 132.48 0.606 0.30( 0.28) 0.94 53086.6 11111.00  
 15 25821.50 138.61 0.595 0.30( 0.28) 0.95 55020.4 12201.00  
 16 24975.29 147.55 0.580 0.30( 0.28) 0.95 57108.7 12231.00  
 17 24195.96 155.05 0.567 0.30( 0.28) 0.95 58520.2 10400.00  
 18 22948.92 166.48 0.548 0.30( 0.28) 0.95 60141.0 10320.00  
 19 22307.54 171.35 0.540 0.30( 0.28) 0.95 60366.4 10210.00  
 20 21743.38 176.23 0.531 0.30( 0.28) 0.95 60528.8 12000.00  
 21 18907.37 205.47 0.505 0.30( 0.28) 0.95 61145.8 10100.00  
 TOTAL AREA (ACRES) = 61145.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 26936.24 Tc (MIN.) = 114.498  
 EFFECTIVE AREA (ACRES) = 45119.91 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 61145.8  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118713.68 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13402.00 TO NODE 13404.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 209.00 DOWNSTREAM (FEET) = 207.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 395.35 CHANNEL SLOPE = 0.0051  
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 8.48  
 CHANNEL FLOW THRU SUBAREA (CFS) = 26936.24  
 FLOW VELOCITY (FEET/SEC.) = 13.11 FLOW DEPTH (FEET) = 8.48  
 TRAVEL TIME (MIN.) = 0.50 Tc (MIN.) = 115.00  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119109.03 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15518.65	21.63	1.524	0.30( 0.24)	0.80	4881.7	50500.00
2	16468.12	26.95	1.333	0.30( 0.24)	0.80	6082.1	110.00
3	18326.98	37.06	1.119	0.30( 0.24)	0.82	9353.7	150.00
4	20290.22	49.05	0.959	0.30( 0.25)	0.84	13673.6	31100.00
5	21029.77	53.74	0.915	0.30( 0.26)	0.85	15617.3	390.00
6	22642.72	68.63	0.817	0.30( 0.27)	0.88	21886.1	13100.00
7	23063.56	75.57	0.783	0.30( 0.27)	0.89	24332.0	11801.00
8	24163.48	89.09	0.716	0.30( 0.27)	0.91	29914.8	11530.00
9	25424.50	100.82	0.681	0.30( 0.28)	0.92	36383.6	13010.00
10	26244.19	106.84	0.664	0.30( 0.28)	0.93	40032.8	11330.00
11	26936.24	115.00	0.641	0.30( 0.28)	0.94	45119.9	10630.00
12	26729.52	120.59	0.626	0.30( 0.28)	0.94	47709.8	12330.00
13	26522.54	127.21	0.615	0.30( 0.28)	0.94	50852.2	11600.00
14	26189.62	132.99	0.605	0.30( 0.28)	0.94	53086.6	11111.00
15	25821.50	139.12	0.594	0.30( 0.28)	0.95	55020.4	12201.00
16	24975.29	148.07	0.579	0.30( 0.28)	0.95	57108.7	12231.00
17	24195.96	155.57	0.567	0.30( 0.28)	0.95	58520.2	10400.00
18	22948.92	167.01	0.547	0.30( 0.28)	0.95	60141.0	10320.00
19	22307.54	171.89	0.539	0.30( 0.28)	0.95	60366.4	10210.00
20	21743.38	176.77	0.530	0.30( 0.28)	0.95	60528.8	12000.00
21	18907.37	206.04	0.505	0.30( 0.28)	0.95	61145.8	10100.00

21 18907.37 206.04 0.505 0.30( 0.28) 0.95 61145.8 10100.00  
 NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE (CFS) = 26936.24 Tc (MIN.) = 115.00  
 AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.94 EFFECTIVE AREA (ACRES) = 45119.91

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13404.00 TO NODE 13404.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610506V.DNA  
 MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	61.99	18.17	0.30( 0.30)	1.00	49.6	50600.00
TOTAL AREA (ACRES) = 49.6						

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13404.00 TO NODE 13404.00 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15518.65	21.63	1.524	0.30( 0.24)	0.80	4881.7	50500.00
2	16468.12	26.95	1.333	0.30( 0.24)	0.80	6082.1	110.00
3	18326.98	37.06	1.119	0.30( 0.24)	0.82	9353.7	150.00
4	20290.22	49.05	0.959	0.30( 0.25)	0.84	13673.6	31100.00
5	21029.77	53.74	0.915	0.30( 0.26)	0.85	15617.3	390.00
6	22642.72	68.63	0.817	0.30( 0.27)	0.88	21886.1	13100.00
7	23063.56	75.57	0.783	0.30( 0.27)	0.89	24332.0	11801.00
8	24163.48	89.09	0.716	0.30( 0.27)	0.91	29914.8	11530.00
9	25424.50	100.82	0.681	0.30( 0.28)	0.92	36383.6	13010.00
10	26244.19	106.84	0.664	0.30( 0.28)	0.93	40032.8	11330.00
11	26936.24	115.00	0.641	0.30( 0.28)	0.94	45119.9	10630.00
12	26729.52	120.59	0.626	0.30( 0.28)	0.94	47709.8	12330.00
13	26522.54	127.21	0.615	0.30( 0.28)	0.94	50852.2	11600.00
14	26189.62	132.99	0.605	0.30( 0.28)	0.94	53086.6	11111.00
15	25821.50	139.12	0.594	0.30( 0.28)	0.95	55020.4	12201.00
16	24975.29	148.07	0.579	0.30( 0.28)	0.95	57108.7	12231.00
17	24195.96	155.57	0.567	0.30( 0.28)	0.95	58520.2	10400.00
18	22948.92	167.01	0.547	0.30( 0.28)	0.95	60141.0	10320.00
19	22307.54	171.89	0.539	0.30( 0.28)	0.95	60366.4	10210.00
20	21743.38	176.77	0.530	0.30( 0.28)	0.95	60528.8	12000.00
21	18907.37	206.04	0.505	0.30( 0.28)	0.95	61145.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119109.03 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	61.99	18.17	1.688	0.30( 0.30)	1.00	49.6	50600.00

LONGEST FLOWPATH FROM NODE 50600.00 TO NODE 13404.00 = 4378.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM	Q	Tc	Intensity	Fp (Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	---------	----	----	-----------



NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	14767.65	18.17	1.688	0.30 ( 0.24)	0.80	4151.3 50600.00
2	15573.31	21.63	1.524	0.30 ( 0.24)	0.80	4931.3 50500.00
3	16514.25	26.95	1.333	0.30 ( 0.24)	0.80	6131.7 110.00
4	18363.56	37.06	1.119	0.30 ( 0.25)	0.82	9403.3 150.00
5	20319.66	49.05	0.959	0.30 ( 0.25)	0.84	13723.2 31100.00
6	21057.24	53.74	0.915	0.30 ( 0.26)	0.85	15666.9 390.00
7	22665.82	68.63	0.817	0.30 ( 0.27)	0.88	21935.7 13100.00
8	23085.14	75.57	0.783	0.30 ( 0.27)	0.89	24381.6 11801.00
9	24182.08	89.09	0.716	0.30 ( 0.27)	0.91	29964.4 11530.00
10	25441.53	100.82	0.681	0.30 ( 0.28)	0.92	36433.2 13010.00
11	26260.46	106.84	0.664	0.30 ( 0.28)	0.93	40082.4 11330.00
12	26951.48	115.00	0.641	0.30 ( 0.28)	0.94	45169.5 10630.00
13	26744.07	120.59	0.626	0.30 ( 0.28)	0.94	47759.4 12330.00
14	26536.60	127.21	0.615	0.30 ( 0.28)	0.94	50901.8 11600.00
15	26203.24	132.99	0.605	0.30 ( 0.28)	0.94	53136.1 11111.00
16	25834.65	139.12	0.594	0.30 ( 0.28)	0.95	55070.0 12201.00
17	24987.76	148.07	0.579	0.30 ( 0.28)	0.95	57158.2 12231.00
18	24207.87	155.57	0.567	0.30 ( 0.28)	0.95	58569.8 10400.00
19	22959.95	167.01	0.547	0.30 ( 0.28)	0.95	60190.6 10320.00
20	22318.21	171.89	0.539	0.30 ( 0.28)	0.95	60416.0 10210.00
21	21753.68	176.77	0.530	0.30 ( 0.28)	0.95	60578.4 12000.00
22	18916.52	206.04	0.505	0.30 ( 0.28)	0.95	61195.4 10100.00

TOTAL AREA (ACRES) = 61195.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 26951.48 Tc (MIN.) = 115.001  
EFFECTIVE AREA (ACRES) = 45169.51 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA (ACRES) = 61195.4  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119109.03 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13404.00 TO NODE 13406.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 207.00 DOWNSTREAM (FEET) = 195.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1601.97 CHANNEL SLOPE = 0.0075  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 7.58  
CHANNEL FLOW THRU SUBAREA (CFS) = 26951.48  
FLOW VELOCITY (FEET/SEC.) = 14.94 FLOW DEPTH (FEET) = 7.58  
TRAVEL TIME (MIN.) = 1.79 Tc (MIN.) = 116.79  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13406.00 = 120711.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14767.65	20.37	1.575	0.30 ( 0.24)	0.80	4151.3	50600.00
2	15573.31	23.78	1.437	0.30 ( 0.24)	0.80	4931.3	50500.00
3	16514.25	29.06	1.274	0.30 ( 0.24)	0.80	6131.7	110.00
4	18363.56	39.10	1.082	0.30 ( 0.25)	0.82	9403.3	150.00
5	20319.66	51.02	0.939	0.30 ( 0.25)	0.84	13723.2	31100.00
6	21057.24	55.68	0.898	0.30 ( 0.26)	0.85	15666.9	390.00
7	22665.82	70.52	0.808	0.30 ( 0.27)	0.88	21935.7	13100.00

8	23085.14	77.45	0.774	0.30 ( 0.27)	0.89	24381.6	11801.00
9	24182.08	90.94	0.709	0.30 ( 0.27)	0.91	29964.4	11530.00
10	25441.53	102.64	0.676	0.30 ( 0.28)	0.92	36433.2	13010.00
11	26260.46	108.64	0.659	0.30 ( 0.28)	0.93	40082.4	11330.00
12	26951.48	116.79	0.636	0.30 ( 0.28)	0.94	45169.5	10630.00
13	26744.07	122.38	0.623	0.30 ( 0.28)	0.94	47759.4	12330.00
14	26536.60	129.00	0.612	0.30 ( 0.28)	0.94	50901.8	11600.00
15	26203.24	134.79	0.602	0.30 ( 0.28)	0.94	53136.1	11111.00
16	25834.65	140.93	0.591	0.30 ( 0.28)	0.95	55070.0	12201.00
17	24987.76	149.90	0.576	0.30 ( 0.28)	0.95	57158.2	12231.00
18	24207.87	157.42	0.563	0.30 ( 0.28)	0.95	58569.8	10400.00
19	22959.95	168.90	0.544	0.30 ( 0.28)	0.95	60190.6	10320.00
20	22318.21	173.79	0.536	0.30 ( 0.28)	0.95	60416.0	10210.00
21	21753.68	178.69	0.527	0.30 ( 0.28)	0.95	60578.4	12000.00
22	18916.52	208.05	0.503	0.30 ( 0.28)	0.95	61195.4	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 26951.48 Tc (MIN.) = 116.79  
AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.94 EFFECTIVE AREA (ACRES) = 45169.51

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 116.79  
\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.636  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "GRASS"	B	0.20	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	4.00	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	2.00	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	9.70	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	2.60	0.30	1.000	66
AGRICULTURAL POOR COVER "ROW CROPS, STRAIGHT ROW"	B	1.80	0.30	1.000	81

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 20.30 SUBAREA RUNOFF (CFS) = 6.14  
EFFECTIVE AREA (ACRES) = 45189.81 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94  
TOTAL AREA (ACRES) = 61215.7 PEAK FLOW RATE (CFS) = 26951.48  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 116.79  
\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.636  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "ROW CROPS, STRAIGHT ROW"	B	3.50	0.30	1.000	81
NATURAL FAIR COVER "WOODLAND, GRASS"	B	7.20	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND, GRASS"	B	5.80	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.10	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 16.60 SUBAREA RUNOFF (CFS) = 5.02  
EFFECTIVE AREA (ACRES) = 45206.41 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94  
TOTAL AREA (ACRES) = 61232.3 PEAK FLOW RATE (CFS) = 26951.48  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 1 <<<<<<  
=====

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<<  
=====

PEAK FLOWRATE TABLE FILE NAME: 2P10EVBB.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	518.09	10.14	0.30 ( 0.11)	0.38	237.9	429.00
2	548.24	11.82	0.30 ( 0.11)	0.38	277.3	425.00
3	551.99	12.10	0.30 ( 0.11)	0.38	284.1	400.00
4	566.31	13.74	0.30 ( 0.11)	0.38	322.9	300.00
5	605.65	19.30	0.30 ( 0.11)	0.38	439.2	210.00
6	601.31	21.30	0.30 ( 0.11)	0.38	463.8	410.00
7	598.36	22.55	0.30 ( 0.11)	0.38	478.8	200.00
8	595.72	23.25	0.30 ( 0.11)	0.38	486.6	230.00
9	580.44	24.41	0.30 ( 0.11)	0.37	491.2	220.50

TOTAL AREA (ACRES) = 491.2

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<<  
=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14767.65	20.37	1.575	0.30 ( 0.24)	0.81	4188.2	50600.00
2	15573.31	23.78	1.437	0.30 ( 0.24)	0.80	4968.2	50500.00
3	16514.25	29.06	1.274	0.30 ( 0.24)	0.80	6168.6	110.00
4	18363.56	39.10	1.082	0.30 ( 0.25)	0.82	9440.2	150.00
5	20319.66	51.02	0.939	0.30 ( 0.25)	0.84	13760.1	31100.00

6	21057.24	55.68	0.898	0.30 ( 0.26)	0.86	15703.8	390.00
7	22665.82	70.52	0.808	0.30 ( 0.27)	0.89	21972.6	13100.00
8	23085.14	77.45	0.774	0.30 ( 0.27)	0.89	24418.5	11801.00
9	24182.08	90.94	0.709	0.30 ( 0.27)	0.91	30001.3	11530.00
10	25441.53	102.64	0.676	0.30 ( 0.28)	0.92	36470.1	13010.00
11	26260.46	108.64	0.659	0.30 ( 0.28)	0.93	40119.3	11330.00
12	26951.48	116.79	0.636	0.30 ( 0.28)	0.94	45206.4	10630.00
13	26744.07	122.38	0.623	0.30 ( 0.28)	0.94	47796.3	12330.00
14	26536.60	129.00	0.612	0.30 ( 0.28)	0.94	50938.7	11600.00
15	26203.24	134.79	0.602	0.30 ( 0.28)	0.94	53173.1	11111.00
16	25834.65	140.93	0.591	0.30 ( 0.28)	0.95	55106.9	12201.00
17	24987.76	149.90	0.576	0.30 ( 0.28)	0.95	57195.1	12231.00
18	24207.87	157.42	0.563	0.30 ( 0.28)	0.95	58606.7	10400.00
19	22959.95	168.90	0.544	0.30 ( 0.28)	0.95	60227.5	10320.00
20	22318.21	173.79	0.536	0.30 ( 0.28)	0.95	60452.9	10210.00
21	21753.68	178.69	0.527	0.30 ( 0.28)	0.95	60615.3	12000.00
22	18916.52	208.05	0.503	0.30 ( 0.28)	0.95	61232.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13406.00 = 120711.00 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	518.09	10.14	2.489	0.30 ( 0.11)	0.38	237.9	429.00
2	548.24	11.82	2.271	0.30 ( 0.11)	0.38	277.3	425.00
3	551.99	12.10	2.234	0.30 ( 0.11)	0.38	284.1	400.00
4	566.31	13.74	2.022	0.30 ( 0.11)	0.38	322.9	300.00
5	605.65	19.30	1.628	0.30 ( 0.11)	0.38	439.2	210.00
6	601.31	21.30	1.537	0.30 ( 0.11)	0.38	463.8	410.00
7	598.36	22.55	1.487	0.30 ( 0.11)	0.38	478.8	200.00
8	595.72	23.25	1.459	0.30 ( 0.11)	0.38	486.6	230.00
9	580.44	24.41	1.412	0.30 ( 0.11)	0.37	491.2	220.50

LONGEST FLOWPATH FROM NODE 230.00 TO NODE 13406.00 = 11903.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12905.38	10.14	2.489	0.30 ( 0.23)	0.76	2322.2	429.00
2	13591.48	11.82	2.271	0.30 ( 0.23)	0.76	2708.2	425.00
3	13665.87	12.10	2.234	0.30 ( 0.23)	0.76	2773.0	400.00
4	13868.93	13.74	2.022	0.30 ( 0.23)	0.76	3149.2	300.00
5	15150.02	19.30	1.628	0.30 ( 0.23)	0.76	4407.6	210.00
6	15370.99	20.37	1.575	0.30 ( 0.23)	0.76	4640.5	50600.00
7	15588.93	21.30	1.537	0.30 ( 0.23)	0.76	4864.9	410.00
8	15879.88	22.55	1.487	0.30 ( 0.23)	0.77	5164.5	200.00
9	16042.59	23.25	1.459	0.30 ( 0.23)	0.77	5332.4	230.00
10	16162.02	23.78	1.437	0.30 ( 0.23)	0.77	5456.9	50500.00
11	16266.46	24.41	1.412	0.30 ( 0.23)	0.77	5603.2	220.50
12	17033.31	29.06	1.274	0.30 ( 0.23)	0.77	6659.8	110.00
13	18796.91	39.10	1.082	0.30 ( 0.24)	0.80	9931.4	150.00
14	20688.96	51.02	0.939	0.30 ( 0.25)	0.83	14251.3	31100.00
15	21408.20	55.68	0.898	0.30 ( 0.25)	0.84	16195.0	390.00
16	22976.62	70.52	0.808	0.30 ( 0.26)	0.87	22463.8	13100.00
17	23380.66	77.45	0.774	0.30 ( 0.27)	0.88	24909.7	11801.00
18	24448.75	90.94	0.709	0.30 ( 0.27)	0.90	30492.5	11530.00
19	25693.39	102.64	0.676	0.30 ( 0.27)	0.91	36961.3	13010.00
20	26504.72	108.64	0.659	0.30 ( 0.28)	0.92	40610.5	11330.00
21	27185.43	116.79	0.636	0.30 ( 0.28)	0.93	45697.6	10630.00
22	26972.16	122.38	0.623	0.30 ( 0.28)	0.93	48287.5	12330.00

23	26759.65	129.00	0.612	0.30	( 0.28)	0.94	51429.9	11600.00
24	26421.90	134.79	0.602	0.30	( 0.28)	0.94	53664.2	11111.00
25	26048.64	140.93	0.591	0.30	( 0.28)	0.94	55598.1	12201.00
26	25194.94	149.90	0.576	0.30	( 0.28)	0.94	57686.3	12231.00
27	24409.33	157.42	0.563	0.30	( 0.28)	0.94	59097.9	10400.00
28	23152.71	168.90	0.544	0.30	( 0.28)	0.94	60718.7	10320.00
29	22507.24	173.79	0.536	0.30	( 0.28)	0.94	60944.1	10210.00
30	21938.99	178.69	0.527	0.30	( 0.28)	0.94	61106.5	12000.00
31	19091.16	208.05	0.503	0.30	( 0.28)	0.95	61723.5	10100.00
TOTAL AREA (ACRES) =		61723.5						

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 27185.43 Tc (MIN.) = 116.788  
EFFECTIVE AREA (ACRES) = 45697.61 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.77  
TOTAL AREA (ACRES) = 61723.5  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13406.00 = 120711.00 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13406.00 TO NODE 13408.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 195.00 DOWNSTREAM (FEET) = 182.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 2458.36 CHANNEL SLOPE = 0.0053  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 8.42  
\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.627

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.00	0.30	1.000	-
USER-DEFINED	-	3.30	0.30	1.000	-
USER-DEFINED	-	0.40	0.30	0.100	-
USER-DEFINED	-	1.40	0.30	1.000	-
USER-DEFINED	-	0.30	0.30	0.100	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.949  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 27187.35  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 13.34  
AVERAGE FLOW DEPTH (FEET) = 8.42 TRAVEL TIME (MIN.) = 3.07  
Tc (MIN.) = 119.86  
SUBAREA AREA (ACRES) = 12.40 SUBAREA RUNOFF (CFS) = 3.82  
EFFECTIVE AREA (ACRES) = 45710.01 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA (ACRES) = 61735.9 PEAK FLOW RATE (CFS) = 27185.43  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 8.42

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 8.42 FLOW VELOCITY (FEET/SEC.) = 13.34  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123169.36 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12905.38	14.09	1.977	0.30 ( 0.23)	0.76	2334.6	429.00
2	13591.48	15.71	1.821	0.30 ( 0.23)	0.76	2720.6	425.00
3	13665.87	15.98	1.806	0.30 ( 0.23)	0.76	2785.4	400.00
4	13868.93	17.60	1.719	0.30 ( 0.23)	0.76	3161.6	300.00
5	15150.02	23.04	1.467	0.30 ( 0.23)	0.76	4420.0	210.00
6	15370.99	24.09	1.425	0.30 ( 0.23)	0.76	4652.9	50600.00
7	15588.93	25.00	1.388	0.30 ( 0.23)	0.76	4877.3	410.00
8	15879.88	26.23	1.354	0.30 ( 0.23)	0.77	5176.9	200.00
9	16042.59	26.92	1.334	0.30 ( 0.23)	0.77	5348.4	230.00
10	16162.02	27.44	1.320	0.30 ( 0.23)	0.77	5469.3	50500.00
11	16266.46	28.07	1.302	0.30 ( 0.23)	0.77	5615.6	220.50
12	17033.31	32.66	1.200	0.30 ( 0.23)	0.77	6672.2	110.00
13	18796.91	42.58	1.036	0.30 ( 0.24)	0.80	9943.8	150.00
14	20688.96	54.38	0.909	0.30 ( 0.25)	0.83	14263.7	31100.00
15	21408.20	59.01	0.869	0.30 ( 0.25)	0.84	16207.4	390.00
16	22976.62	73.77	0.792	0.30 ( 0.26)	0.87	22476.2	13100.00
17	23380.66	80.68	0.758	0.30 ( 0.27)	0.88	24922.1	11801.00
18	24448.75	94.12	0.700	0.30 ( 0.27)	0.90	30504.9	11530.00
19	25693.39	105.77	0.667	0.30 ( 0.27)	0.91	36973.7	13010.00
20	26504.72	111.74	0.650	0.30 ( 0.28)	0.92	40622.9	11330.00
21	27185.43	119.86	0.627	0.30 ( 0.28)	0.93	45710.0	10630.00
22	26972.16	125.46	0.618	0.30 ( 0.28)	0.93	48299.9	12330.00
23	26759.65	132.09	0.606	0.30 ( 0.28)	0.94	51442.3	11600.00
24	26421.90	137.89	0.597	0.30 ( 0.28)	0.94	53676.6	11111.00
25	26048.64	144.05	0.586	0.30 ( 0.28)	0.94	55610.5	12201.00
26	25194.94	153.05	0.571	0.30 ( 0.28)	0.94	57698.7	12231.00
27	24409.33	160.61	0.558	0.30 ( 0.28)	0.94	59110.3	10400.00
28	23152.71	172.14	0.538	0.30 ( 0.28)	0.94	60731.1	10320.00
29	22507.24	177.06	0.530	0.30 ( 0.28)	0.94	60956.5	10210.00
30	21938.99	181.99	0.523	0.30 ( 0.28)	0.94	61118.9	12000.00
31	19091.16	211.51	0.501	0.30 ( 0.28)	0.95	61735.9	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 27185.43 Tc (MIN.) = 119.86  
AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA (ACRES) = 45710.01

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610507V.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	264.52	21.27	0.30 ( 0.30)	0.99	236.8	50700.00
TOTAL AREA (ACRES) =		236.8				

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 11

=====  
>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<  
=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	12905.38	14.09	1.977	0.30 ( 0.23)	0.76	2334.6	429.00
2	13591.48	15.71	1.821	0.30 ( 0.23)	0.76	2720.6	425.00
3	13665.87	15.98	1.806	0.30 ( 0.23)	0.76	2785.4	400.00
4	13868.93	17.60	1.719	0.30 ( 0.23)	0.76	3161.6	300.00
5	15150.02	23.04	1.467	0.30 ( 0.23)	0.76	4420.0	210.00
6	15370.99	24.09	1.425	0.30 ( 0.23)	0.76	4652.9	50600.00
7	15588.93	25.00	1.388	0.30 ( 0.23)	0.76	4877.3	410.00
8	15879.88	26.23	1.354	0.30 ( 0.23)	0.77	5176.9	200.00
9	16042.59	26.92	1.334	0.30 ( 0.23)	0.77	5344.8	230.00
10	16162.02	27.44	1.320	0.30 ( 0.23)	0.77	5469.3	50500.00
11	16266.46	28.07	1.302	0.30 ( 0.23)	0.77	5615.6	220.50
12	17033.31	32.66	1.200	0.30 ( 0.23)	0.77	6672.2	110.00
13	18796.91	42.58	1.036	0.30 ( 0.24)	0.80	9943.8	150.00
14	20688.96	54.38	0.909	0.30 ( 0.25)	0.83	14263.7	31100.00
15	21408.20	59.01	0.869	0.30 ( 0.25)	0.84	16207.4	390.00
16	22976.62	73.77	0.792	0.30 ( 0.26)	0.87	22476.2	13100.00
17	23380.66	80.68	0.758	0.30 ( 0.27)	0.88	24922.1	11801.00
18	24448.75	94.12	0.700	0.30 ( 0.27)	0.90	30504.9	11530.00
19	25693.39	105.77	0.667	0.30 ( 0.27)	0.91	36973.7	13010.00
20	26504.72	111.74	0.650	0.30 ( 0.28)	0.92	40622.9	11330.00
21	27185.43	119.86	0.627	0.30 ( 0.28)	0.93	45710.0	10630.00
22	26972.16	125.46	0.618	0.30 ( 0.28)	0.93	48299.9	12330.00
23	26759.65	132.09	0.606	0.30 ( 0.28)	0.94	51442.3	11600.00
24	26421.90	137.89	0.597	0.30 ( 0.28)	0.94	53676.6	11111.00
25	26048.64	144.05	0.586	0.30 ( 0.28)	0.94	55610.5	12201.00
26	25194.94	153.05	0.571	0.30 ( 0.28)	0.94	57698.7	12231.00
27	24409.33	160.61	0.558	0.30 ( 0.28)	0.94	59110.3	10400.00
28	23152.71	172.14	0.538	0.30 ( 0.28)	0.94	60731.1	10320.00
29	22507.24	177.06	0.530	0.30 ( 0.28)	0.94	60956.5	10210.00
30	21938.99	181.99	0.523	0.30 ( 0.28)	0.94	61118.9	12000.00
31	19091.16	211.51	0.501	0.30 ( 0.28)	0.95	61735.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123169.36 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	264.52	21.27	1.539	0.30 ( 0.30)	0.99	236.8	50700.00

LONGEST FLOWPATH FROM NODE 50700.00 TO NODE 13408.00 = 7903.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13142.48	14.09	1.977	0.30 ( 0.23)	0.78	2491.5	429.00
2	13831.24	15.71	1.821	0.30 ( 0.23)	0.78	2895.5	425.00
3	13907.47	15.98	1.806	0.30 ( 0.23)	0.78	2963.3	400.00
4	14119.63	17.60	1.719	0.30 ( 0.23)	0.78	3357.5	300.00
5	14997.68	21.27	1.539	0.30 ( 0.23)	0.78	4247.3	50700.00
6	15399.30	23.04	1.467	0.30 ( 0.23)	0.78	4656.8	210.00
7	15611.22	24.09	1.425	0.30 ( 0.23)	0.78	4889.7	50600.00
8	15821.31	25.00	1.388	0.30 ( 0.23)	0.78	5114.1	410.00
9	16104.96	26.23	1.354	0.30 ( 0.23)	0.78	5413.7	200.00

10	16263.56	26.92	1.334	0.30 ( 0.23)	0.78	5581.5	230.00
11	16379.85	27.44	1.320	0.30 ( 0.23)	0.78	5706.1	50500.00
12	16480.57	28.07	1.302	0.30 ( 0.23)	0.78	5852.3	220.50
13	17225.57	32.66	1.200	0.30 ( 0.23)	0.78	6909.0	110.00
14	18954.19	42.58	1.036	0.30 ( 0.24)	0.80	10180.6	150.00
15	20819.35	54.38	0.909	0.30 ( 0.25)	0.83	14500.5	31100.00
16	21529.92	59.01	0.869	0.30 ( 0.25)	0.84	16444.2	390.00
17	23082.00	73.77	0.792	0.30 ( 0.26)	0.88	22713.0	13100.00
18	23478.76	80.68	0.758	0.30 ( 0.27)	0.88	25158.9	11801.00
19	24534.57	94.12	0.700	0.30 ( 0.27)	0.90	30741.7	11530.00
20	25772.17	105.77	0.667	0.30 ( 0.27)	0.91	37210.5	13010.00
21	26579.90	111.74	0.650	0.30 ( 0.28)	0.92	40859.7	11330.00
22	27255.71	119.86	0.627	0.30 ( 0.28)	0.93	45946.8	10630.00
23	27040.37	125.46	0.618	0.30 ( 0.28)	0.93	48536.7	12330.00
24	26825.46	132.09	0.606	0.30 ( 0.28)	0.94	51679.1	11600.00
25	26485.60	137.89	0.597	0.30 ( 0.28)	0.94	53913.4	11111.00
26	26110.11	144.05	0.586	0.30 ( 0.28)	0.94	55847.3	12201.00
27	25253.15	153.05	0.571	0.30 ( 0.28)	0.94	57935.5	12231.00
28	24464.80	160.61	0.558	0.30 ( 0.28)	0.94	59347.1	10400.00
29	23204.00	172.14	0.538	0.30 ( 0.28)	0.94	60967.8	10320.00
30	22556.75	177.06	0.530	0.30 ( 0.28)	0.94	61193.3	10210.00
31	21987.11	181.99	0.523	0.30 ( 0.28)	0.94	61355.7	12000.00
32	19134.42	211.51	0.501	0.30 ( 0.28)	0.95	61972.7	10100.00

TOTAL AREA (ACRES) = 61972.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 27255.71 Tc (MIN.) = 119.859  
EFFECTIVE AREA (ACRES) = 45946.79 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
TOTAL AREA (ACRES) = 61972.7  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123169.36 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13408.00 TO NODE 13410.00 IS CODE = 56  
\*\*\*\*\*

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====  
ELEVATION DATA: UPSTREAM (FEET) = 182.00 DOWNSTREAM (FEET) = 178.72  
CHANNEL LENGTH THRU SUBAREA (FEET) = 952.73 CHANNEL SLOPE = 0.0034  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 9.52  
\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.625  
SUBAREA LOSS RATE DATA (AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 0.40 0.30 1.000 -  
USER-DEFINED - 2.90 0.30 1.000 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 27256.19  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 11.57  
AVERAGE FLOW DEPTH (FEET) = 9.52 TRAVEL TIME (MIN.) = 1.37  
Tc (MIN.) = 121.23  
SUBAREA AREA (ACRES) = 3.30 SUBAREA RUNOFF (CFS) = 0.97  
EFFECTIVE AREA (ACRES) = 45950.09 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA (ACRES) = 61976.0 PEAK FLOW RATE (CFS) = 27255.71  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 9.52

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 9.52 FLOW VELOCITY (FEET/SEC.) = 11.56  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124122.09 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13142.48	15.85	1.814	0.30 ( 0.23)	0.78	2494.8	429.00
2	13831.24	17.43	1.728	0.30 ( 0.23)	0.78	2898.8	425.00
3	13907.47	17.70	1.714	0.30 ( 0.23)	0.78	2966.6	400.00
4	14119.63	19.31	1.627	0.30 ( 0.23)	0.78	3360.8	300.00
5	14997.68	22.95	1.471	0.30 ( 0.23)	0.78	4250.6	50700.00
6	15399.30	24.70	1.400	0.30 ( 0.23)	0.78	4660.1	210.00
7	15611.22	25.75	1.367	0.30 ( 0.23)	0.78	4893.0	50600.00
8	15821.31	26.65	1.342	0.30 ( 0.23)	0.78	5117.4	410.00
9	16104.96	27.86	1.308	0.30 ( 0.23)	0.78	5417.0	200.00
10	16263.56	28.55	1.289	0.30 ( 0.23)	0.78	5584.8	230.00
11	16379.85	29.07	1.274	0.30 ( 0.23)	0.78	5709.4	50500.00
12	16480.57	29.69	1.257	0.30 ( 0.23)	0.78	5855.6	220.50
13	17225.57	34.25	1.171	0.30 ( 0.23)	0.78	6912.3	110.00
14	18954.19	44.12	1.017	0.30 ( 0.24)	0.80	10183.9	150.00
15	20819.35	55.88	0.896	0.30 ( 0.25)	0.83	14503.8	31100.00
16	21529.92	60.49	0.858	0.30 ( 0.25)	0.84	16447.5	390.00
17	23082.00	75.22	0.785	0.30 ( 0.26)	0.88	22716.3	13100.00
18	23478.76	82.12	0.751	0.30 ( 0.27)	0.88	25162.2	11801.00
19	24534.57	95.55	0.696	0.30 ( 0.27)	0.90	30745.0	11530.00
20	25772.17	107.17	0.663	0.30 ( 0.27)	0.91	37213.8	13010.00
21	26579.90	113.13	0.646	0.30 ( 0.28)	0.92	40863.0	11330.00
22	27255.71	121.23	0.625	0.30 ( 0.28)	0.93	45950.1	10630.00
23	27040.37	126.83	0.615	0.30 ( 0.28)	0.93	48540.0	12330.00
24	26825.46	133.47	0.604	0.30 ( 0.28)	0.94	51682.4	11600.00
25	26485.60	139.28	0.594	0.30 ( 0.28)	0.94	53916.7	11111.00
26	26110.11	145.44	0.584	0.30 ( 0.28)	0.94	55850.6	12201.00
27	25253.15	154.46	0.568	0.30 ( 0.28)	0.94	57938.8	12231.00
28	24464.80	162.03	0.556	0.30 ( 0.28)	0.94	59350.4	10400.00
29	23204.00	173.58	0.536	0.30 ( 0.28)	0.94	60971.1	10320.00
30	22556.75	178.52	0.528	0.30 ( 0.28)	0.94	61196.6	10210.00
31	21987.11	183.46	0.522	0.30 ( 0.28)	0.94	61359.0	12000.00
32	19134.42	213.06	0.499	0.30 ( 0.28)	0.95	61976.0	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 27255.71 Tc (MIN.) = 121.23  
 AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA (ACRES) = 45950.09

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 3 <<<<<<  
 =====

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 15.1

-----  
 >>>>DEFINE MEMORY BANK # 3 <<<<<<  
 =====

PEAK FLOWRATE TABLE FILE NAME: R110EV36.DNA  
 MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1521.80	30.81	0.30 ( 0.27)	0.90	1440.9	110.00
2	1573.72	33.19	0.30 ( 0.27)	0.90	1597.0	100.00
3	1590.73	34.56	0.30 ( 0.27)	0.90	1678.1	100.00
4	1600.63	37.85	0.30 ( 0.27)	0.91	1850.3	130.00
5	1651.13	52.91	0.30 ( 0.28)	0.93	2602.0	20100.00
6	1611.81	59.35	0.30 ( 0.28)	0.93	2797.2	13600.00
7	1408.16	100.08	0.30 ( 0.28)	0.93	3789.3	13510.00
8	1318.82	111.28	0.30 ( 0.28)	0.93	3859.7	13500.00
TOTAL AREA (ACRES) =			3859.7			

\*\*\*\*\*

FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<<  
 =====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13142.48	15.85	1.814	0.30 ( 0.23)	0.78	2494.8	429.00
2	13831.24	17.43	1.728	0.30 ( 0.23)	0.78	2898.8	425.00
3	13907.47	17.70	1.714	0.30 ( 0.23)	0.78	2966.6	400.00
4	14119.63	19.31	1.627	0.30 ( 0.23)	0.78	3360.8	300.00
5	14997.68	22.95	1.471	0.30 ( 0.23)	0.78	4250.6	50700.00
6	15399.30	24.70	1.400	0.30 ( 0.23)	0.78	4660.1	210.00
7	15611.22	25.75	1.367	0.30 ( 0.23)	0.78	4893.0	50600.00
8	15821.31	26.65	1.342	0.30 ( 0.23)	0.78	5117.4	410.00
9	16104.96	27.86	1.308	0.30 ( 0.23)	0.78	5417.0	200.00
10	16263.56	28.55	1.289	0.30 ( 0.23)	0.78	5584.8	230.00
11	16379.85	29.07	1.274	0.30 ( 0.23)	0.78	5709.4	50500.00
12	16480.57	29.69	1.257	0.30 ( 0.23)	0.78	5855.6	220.50
13	17225.57	34.25	1.171	0.30 ( 0.23)	0.78	6912.3	110.00
14	18954.19	44.12	1.017	0.30 ( 0.24)	0.80	10183.9	150.00
15	20819.35	55.88	0.896	0.30 ( 0.25)	0.83	14503.8	31100.00
16	21529.92	60.49	0.858	0.30 ( 0.25)	0.84	16447.5	390.00
17	23082.00	75.22	0.785	0.30 ( 0.26)	0.88	22716.3	13100.00
18	23478.76	82.12	0.751	0.30 ( 0.27)	0.88	25162.2	11801.00
19	24534.57	95.55	0.696	0.30 ( 0.27)	0.90	30745.0	11530.00
20	25772.17	107.17	0.663	0.30 ( 0.27)	0.91	37213.8	13010.00
21	26579.90	113.13	0.646	0.30 ( 0.28)	0.92	40863.0	11330.00
22	27255.71	121.23	0.625	0.30 ( 0.28)	0.93	45950.1	10630.00
23	27040.37	126.83	0.615	0.30 ( 0.28)	0.93	48540.0	12330.00
24	26825.46	133.47	0.604	0.30 ( 0.28)	0.94	51682.4	11600.00
25	26485.60	139.28	0.594	0.30 ( 0.28)	0.94	53916.7	11111.00
26	26110.11	145.44	0.584	0.30 ( 0.28)	0.94	55850.6	12201.00
27	25253.15	154.46	0.568	0.30 ( 0.28)	0.94	57938.8	12231.00
28	24464.80	162.03	0.556	0.30 ( 0.28)	0.94	59350.4	10400.00
29	23204.00	173.58	0.536	0.30 ( 0.28)	0.94	60971.1	10320.00
30	22556.75	178.52	0.528	0.30 ( 0.28)	0.94	61196.6	10210.00
31	21987.11	183.46	0.522	0.30 ( 0.28)	0.94	61359.0	12000.00
32	19134.42	213.06	0.499	0.30 ( 0.28)	0.95	61976.0	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124122.09 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1521.80	30.81	1.233	0.30( 0.27)	0.90	1440.9	110.00
2	1573.72	33.19	1.190	0.30( 0.27)	0.90	1597.0	100.00
3	1590.73	34.56	1.165	0.30( 0.27)	0.90	1678.1	100.00
4	1600.63	37.85	1.105	0.30( 0.27)	0.91	1850.3	130.00
5	1651.13	52.91	0.922	0.30( 0.28)	0.93	2602.0	20100.00
6	1611.81	59.35	0.866	0.30( 0.28)	0.93	2797.2	13600.00
7	1408.16	100.08	0.683	0.30( 0.28)	0.93	3789.3	13510.00
8	1318.82	111.28	0.652	0.30( 0.28)	0.93	3859.7	13500.00

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13410.00 = 41710.10 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14396.79	15.85	1.814	0.30( 0.24)	0.81	3235.9	429.00
2	15134.76	17.43	1.728	0.30( 0.24)	0.80	3714.0	425.00
3	15218.11	17.70	1.714	0.30( 0.24)	0.80	3794.7	400.00
4	15463.67	19.31	1.627	0.30( 0.24)	0.80	4264.3	300.00
5	16410.95	22.95	1.471	0.30( 0.24)	0.80	5323.9	50700.00
6	16830.80	24.70	1.400	0.30( 0.24)	0.80	5815.4	210.00
7	17059.73	25.75	1.367	0.30( 0.24)	0.80	6097.2	50600.00
8	17286.12	26.65	1.342	0.30( 0.24)	0.80	6364.0	410.00
9	17587.88	27.86	1.308	0.30( 0.24)	0.80	6720.2	200.00
10	17754.83	28.55	1.289	0.30( 0.24)	0.80	6920.1	230.00
11	17876.60	29.07	1.274	0.30( 0.24)	0.80	7069.0	50500.00
12	17982.81	29.69	1.257	0.30( 0.24)	0.80	7244.3	220.50
13	18184.50	30.81	1.233	0.30( 0.24)	0.80	7554.8	110.00
14	18624.92	33.19	1.190	0.30( 0.24)	0.80	8262.0	100.00
15	18812.53	34.25	1.171	0.30( 0.24)	0.80	8572.4	110.00
16	18869.53	34.56	1.165	0.30( 0.24)	0.80	8691.1	100.00
17	19455.86	37.85	1.105	0.30( 0.24)	0.81	9954.3	130.00
18	20575.87	44.12	1.017	0.30( 0.25)	0.82	12347.5	150.00
19	21998.26	52.91	0.922	0.30( 0.25)	0.84	16012.1	20100.00
20	22452.33	55.88	0.896	0.30( 0.25)	0.85	17195.9	31100.00
21	22966.22	59.35	0.866	0.30( 0.26)	0.85	18764.6	13600.00
22	23136.04	60.49	0.858	0.30( 0.26)	0.86	19272.5	390.00
23	24614.46	75.22	0.785	0.30( 0.26)	0.88	25900.1	13100.00
24	24976.70	82.12	0.751	0.30( 0.27)	0.89	28514.2	11801.00
25	25965.38	95.55	0.696	0.30( 0.27)	0.90	34424.0	11530.00
26	26425.00	100.08	0.683	0.30( 0.27)	0.91	37055.1	13510.00
27	27123.76	107.17	0.663	0.30( 0.27)	0.92	41047.7	13010.00
28	27648.35	111.28	0.652	0.30( 0.28)	0.92	43591.5	13500.00
29	27880.15	113.13	0.646	0.30( 0.28)	0.92	44722.6	11330.00
30	28479.41	121.23	0.625	0.30( 0.28)	0.93	49809.8	10630.00
31	28230.28	126.83	0.615	0.30( 0.28)	0.93	52399.6	12330.00
32	27975.33	133.47	0.604	0.30( 0.28)	0.94	55542.1	11600.00
33	27600.46	139.28	0.594	0.30( 0.28)	0.94	57776.4	11111.00
34	27187.78	145.44	0.584	0.30( 0.28)	0.94	59710.3	12201.00
35	26276.42	154.46	0.568	0.30( 0.28)	0.94	61798.5	12231.00
36	25442.41	162.03	0.556	0.30( 0.28)	0.94	63210.1	10400.00
37	24111.92	173.58	0.536	0.30( 0.28)	0.94	64830.8	10320.00
38	23434.87	178.52	0.528	0.30( 0.28)	0.94	65056.3	10210.00
39	22846.84	183.46	0.522	0.30( 0.28)	0.94	65218.7	12000.00
40	19913.05	213.06	0.499	0.30( 0.28)	0.94	65835.7	10100.00

TOTAL AREA(ACRES) = 65835.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 28479.41 Tc(MIN.) = 121.232  
EFFECTIVE AREA(ACRES) = 49809.78 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.86  
TOTAL AREA(ACRES) = 65835.7  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124122.09 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13410.00 TO NODE 13412.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 178.72 DOWNSTREAM(FEET) = 176.93  
CHANNEL LENGTH THRU SUBAREA(FEET) = 169.78 CHANNEL SLOPE = 0.0105  
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 7.10  
CHANNEL FLOW THRU SUBAREA(CFS) = 28479.41  
FLOW VELOCITY(FEET/SEC.) = 17.04 FLOW DEPTH(FEET) = 7.10  
TRAVEL TIME(MIN.) = 0.17 Tc(MIN.) = 121.40  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124291.87 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14396.79	16.06	1.802	0.30( 0.24)	0.81	3235.9	429.00
2	15134.76	17.64	1.717	0.30( 0.24)	0.80	3714.0	425.00
3	15218.11	17.91	1.702	0.30( 0.24)	0.80	3794.7	400.00
4	15463.67	19.52	1.616	0.30( 0.24)	0.80	4264.3	300.00
5	16410.95	23.15	1.463	0.30( 0.24)	0.80	5323.9	50700.00
6	16830.80	24.90	1.392	0.30( 0.24)	0.80	5815.4	210.00
7	17059.73	25.94	1.362	0.30( 0.24)	0.80	6097.2	50600.00
8	17286.12	26.85	1.336	0.30( 0.24)	0.80	6364.0	410.00
9	17587.88	28.06	1.302	0.30( 0.24)	0.80	6720.2	200.00
10	17754.83	28.74	1.283	0.30( 0.24)	0.80	6920.1	230.00
11	17876.60	29.26	1.269	0.30( 0.24)	0.80	7069.0	50500.00
12	17982.81	29.88	1.251	0.30( 0.24)	0.80	7244.3	220.50
13	18184.50	31.00	1.230	0.30( 0.24)	0.80	7554.8	110.00
14	18624.92	33.38	1.187	0.30( 0.24)	0.80	8262.0	100.00
15	18812.53	34.45	1.167	0.30( 0.24)	0.80	8572.4	110.00
16	18869.53	34.75	1.162	0.30( 0.24)	0.80	8691.1	100.00
17	19455.86	38.04	1.102	0.30( 0.24)	0.81	9954.3	130.00
18	20575.87	44.31	1.015	0.30( 0.25)	0.82	12347.5	150.00
19	21998.26	53.09	0.921	0.30( 0.25)	0.84	16012.1	20100.00
20	22452.33	56.06	0.895	0.30( 0.25)	0.85	17195.9	31100.00
21	22966.22	59.53	0.864	0.30( 0.26)	0.85	18764.6	13600.00
22	23136.04	60.67	0.857	0.30( 0.26)	0.86	19272.5	390.00
23	24614.46	75.39	0.784	0.30( 0.26)	0.88	25900.1	13100.00
24	24976.70	82.30	0.750	0.30( 0.27)	0.89	28514.2	11801.00
25	25965.38	95.72	0.696	0.30( 0.27)	0.90	34424.0	11530.00
26	26425.00	100.25	0.683	0.30( 0.27)	0.91	37055.1	13510.00
27	27123.76	107.34	0.663	0.30( 0.27)	0.92	41047.7	13010.00
28	27648.35	111.45	0.651	0.30( 0.28)	0.92	43591.5	13500.00
29	27880.15	113.29	0.646	0.30( 0.28)	0.92	44722.6	11330.00
30	28479.41	121.40	0.625	0.30( 0.28)	0.93	49809.8	10630.00

31	28230.28	127.00	0.615	0.30 ( 0.28)	0.93	52399.6	12330.00
32	27975.33	133.64	0.604	0.30 ( 0.28)	0.94	55542.1	11600.00
33	27600.46	139.44	0.594	0.30 ( 0.28)	0.94	57776.4	11111.00
34	27187.78	145.61	0.583	0.30 ( 0.28)	0.94	59710.3	12201.00
35	26276.42	154.63	0.568	0.30 ( 0.28)	0.94	61798.5	12231.00
36	25442.41	162.20	0.555	0.30 ( 0.28)	0.94	63210.1	10400.00
37	24111.92	173.76	0.536	0.30 ( 0.28)	0.94	64830.8	10320.00
38	23434.87	178.70	0.527	0.30 ( 0.28)	0.94	65056.3	10210.00
39	22846.84	183.64	0.522	0.30 ( 0.28)	0.94	65218.7	12000.00
40	19913.05	213.24	0.499	0.30 ( 0.28)	0.94	65835.7	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 28479.41 Tc(MIN.) = 121.40  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 49809.78

\*\*\*\*\*

FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506101E.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	366.95	40.42	0.30 ( 0.30)	0.98	591.0	10100.00
TOTAL AREA(ACRES) =		591.0				

\*\*\*\*\*

FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14396.79	16.06	1.802	0.30 ( 0.24)	0.81	3235.9	429.00
2	15134.76	17.64	1.717	0.30 ( 0.24)	0.80	3714.0	425.00
3	15218.11	17.91	1.702	0.30 ( 0.24)	0.80	3794.7	400.00
4	15463.67	19.52	1.616	0.30 ( 0.24)	0.80	4264.3	300.00
5	16410.95	23.15	1.463	0.30 ( 0.24)	0.80	5323.9	50700.00
6	16830.80	24.90	1.392	0.30 ( 0.24)	0.80	5815.4	210.00
7	17059.73	25.94	1.362	0.30 ( 0.24)	0.80	6097.2	50600.00
8	17286.12	26.85	1.336	0.30 ( 0.24)	0.80	6364.0	410.00
9	17587.88	28.06	1.302	0.30 ( 0.24)	0.80	6720.2	200.00
10	17754.83	28.74	1.283	0.30 ( 0.24)	0.80	6920.1	230.00
11	17876.60	29.26	1.269	0.30 ( 0.24)	0.80	7069.0	50500.00
12	17982.81	29.88	1.251	0.30 ( 0.24)	0.80	7244.3	220.50
13	18184.50	31.00	1.230	0.30 ( 0.24)	0.80	7554.8	110.00
14	18624.92	33.38	1.187	0.30 ( 0.24)	0.80	8262.0	100.00
15	18812.53	34.45	1.167	0.30 ( 0.24)	0.80	8572.4	110.00
16	18869.53	34.75	1.162	0.30 ( 0.24)	0.80	8691.1	100.00

17	19455.86	38.04	1.102	0.30 ( 0.24)	0.81	9954.3	130.00
18	20575.87	44.31	1.015	0.30 ( 0.25)	0.82	12347.5	150.00
19	21998.26	53.09	0.921	0.30 ( 0.25)	0.84	16012.1	20100.00
20	22452.33	56.06	0.895	0.30 ( 0.25)	0.85	17195.9	31100.00
21	22966.22	59.53	0.864	0.30 ( 0.26)	0.85	18764.6	13600.00
22	23136.04	60.67	0.857	0.30 ( 0.26)	0.86	19272.5	390.00
23	24614.46	75.39	0.784	0.30 ( 0.26)	0.88	25900.1	13100.00
24	24976.70	82.30	0.750	0.30 ( 0.27)	0.89	28514.2	11801.00
25	25965.38	95.72	0.696	0.30 ( 0.27)	0.90	34424.0	11530.00
26	26425.00	100.25	0.683	0.30 ( 0.27)	0.91	37055.1	13510.00
27	27123.76	107.34	0.663	0.30 ( 0.27)	0.92	41047.7	13010.00
28	27648.35	111.45	0.651	0.30 ( 0.28)	0.92	43591.5	13500.00
29	27880.15	113.29	0.646	0.30 ( 0.28)	0.92	44722.6	11330.00
30	28479.41	121.40	0.625	0.30 ( 0.28)	0.93	49809.8	10630.00
31	28230.28	127.00	0.615	0.30 ( 0.28)	0.93	52399.6	12330.00
32	27975.33	133.64	0.604	0.30 ( 0.28)	0.94	55542.1	11600.00
33	27600.46	139.44	0.594	0.30 ( 0.28)	0.94	57776.4	11111.00
34	27187.78	145.61	0.583	0.30 ( 0.28)	0.94	59710.3	12201.00
35	26276.42	154.63	0.568	0.30 ( 0.28)	0.94	61798.5	12231.00
36	25442.41	162.20	0.555	0.30 ( 0.28)	0.94	63210.1	10400.00
37	24111.92	173.76	0.536	0.30 ( 0.28)	0.94	64830.8	10320.00
38	23434.87	178.70	0.527	0.30 ( 0.28)	0.94	65056.3	10210.00
39	22846.84	183.64	0.522	0.30 ( 0.28)	0.94	65218.7	12000.00
40	19913.05	213.24	0.499	0.30 ( 0.28)	0.94	65835.7	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124291.87 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	366.95	40.42	1.061	0.30 ( 0.30)	0.98	591.0	10100.00
LONGEST FLOWPATH FROM NODE		10100.00	TO NODE		13412.00	=	14677.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14683.57	16.06	1.802	0.30 ( 0.25)	0.82	3470.7	429.00
2	15432.00	17.64	1.717	0.30 ( 0.24)	0.82	3971.9	425.00
3	15516.84	17.91	1.702	0.30 ( 0.24)	0.82	4056.5	400.00
4	15769.21	19.52	1.616	0.30 ( 0.24)	0.81	4549.6	300.00
5	16731.30	23.15	1.463	0.30 ( 0.24)	0.81	5662.4	50700.00
6	17154.52	24.90	1.392	0.30 ( 0.24)	0.81	6179.5	210.00
7	17387.66	25.94	1.362	0.30 ( 0.24)	0.81	6476.5	50600.00
8	17617.41	26.85	1.336	0.30 ( 0.24)	0.81	6756.5	410.00
9	17922.84	28.06	1.302	0.30 ( 0.24)	0.81	7130.4	200.00
10	18091.44	28.74	1.283	0.30 ( 0.24)	0.81	7340.3	230.00
11	18214.25	29.26	1.269	0.30 ( 0.24)	0.81	7496.8	50500.00
12	18321.46	29.88	1.251	0.30 ( 0.24)	0.81	7681.2	220.50
13	18527.92	31.00	1.230	0.30 ( 0.24)	0.81	8008.0	110.00
14	18977.56	33.38	1.187	0.30 ( 0.24)	0.81	8750.0	100.00
15	19168.53	34.45	1.167	0.30 ( 0.24)	0.81	9076.0	110.00
16	19226.38	34.75	1.162	0.30 ( 0.24)	0.81	9199.1	100.00
17	19819.51	38.04	1.102	0.30 ( 0.25)	0.82	10510.4	130.00
18	20248.81	40.42	1.061	0.30 ( 0.25)	0.82	11455.6	10100.00
19	20920.86	44.31	1.015	0.30 ( 0.25)	0.83	12938.5	150.00
20	22298.07	53.09	0.921	0.30 ( 0.25)	0.84	16603.1	20100.00
21	22739.59	56.06	0.895	0.30 ( 0.25)	0.85	17786.9	31100.00
22	23238.86	59.53	0.864	0.30 ( 0.26)	0.86	19355.6	13600.00
23	23405.12	60.67	0.857	0.30 ( 0.26)	0.86	19863.5	390.00

24	24848.74	75.39	0.784	0.30 ( 0.27)	0.88	26491.1	13100.00
25	25194.66	82.30	0.750	0.30 ( 0.27)	0.89	29105.2	11801.00
26	26157.38	95.72	0.696	0.30 ( 0.27)	0.91	35015.0	11530.00
27	26610.85	100.25	0.683	0.30 ( 0.27)	0.91	37646.1	13510.00
28	27299.98	107.34	0.663	0.30 ( 0.28)	0.92	41638.7	13010.00
29	27819.00	111.45	0.651	0.30 ( 0.28)	0.92	44182.5	13500.00
30	28048.30	113.29	0.646	0.30 ( 0.28)	0.92	45313.6	11330.00
31	28637.31	121.40	0.625	0.30 ( 0.28)	0.93	50400.8	10630.00
32	28383.62	127.00	0.615	0.30 ( 0.28)	0.93	52990.6	12330.00
33	28123.27	133.64	0.604	0.30 ( 0.28)	0.94	56133.1	11600.00
34	27743.67	139.44	0.594	0.30 ( 0.28)	0.94	58367.4	11111.00
35	27325.96	145.61	0.583	0.30 ( 0.28)	0.94	60301.3	12201.00
36	26407.25	154.63	0.568	0.30 ( 0.28)	0.94	62389.5	12231.00
37	25567.08	162.20	0.555	0.30 ( 0.28)	0.94	63801.1	10400.00
38	24227.17	173.76	0.536	0.30 ( 0.28)	0.94	65421.8	10320.00
39	23546.11	178.70	0.527	0.30 ( 0.28)	0.94	65647.3	10210.00
40	22955.67	183.64	0.522	0.30 ( 0.28)	0.94	65809.7	12000.00
41	20010.93	213.24	0.499	0.30 ( 0.28)	0.95	66426.7	10100.00

TOTAL AREA (ACRES) = 66426.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 28637.31 Tc (MIN.) = 121.398  
EFFECTIVE AREA (ACRES) = 50400.78 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
TOTAL AREA (ACRES) = 66426.7  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124291.87 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13412.00 TO NODE 13700.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 176.93 DOWNSTREAM (FEET) = 173.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 260.10 CHANNEL SLOPE = 0.0151  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 6.42  
CHANNEL FLOW THRU SUBAREA (CFS) = 28637.31  
FLOW VELOCITY (FEET/SEC.) = 19.22 FLOW DEPTH (FEET) = 6.42  
TRAVEL TIME (MIN.) = 0.23 Tc (MIN.) = 121.62  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124551.97 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14683.57	16.34	1.787	0.30 ( 0.25)	0.82	3470.7	429.00
2	15432.00	17.92	1.702	0.30 ( 0.24)	0.82	3971.9	425.00
3	15516.84	18.19	1.687	0.30 ( 0.24)	0.82	4056.5	400.00
4	15769.21	19.80	1.601	0.30 ( 0.24)	0.81	4549.6	300.00
5	16731.30	23.42	1.452	0.30 ( 0.24)	0.81	5662.4	50700.00
6	17154.52	25.17	1.383	0.30 ( 0.24)	0.81	6179.5	210.00
7	17387.66	26.21	1.354	0.30 ( 0.24)	0.81	6476.5	50600.00
8	17617.41	27.12	1.329	0.30 ( 0.24)	0.81	6756.5	410.00
9	17922.84	28.32	1.295	0.30 ( 0.24)	0.81	7130.4	200.00
10	18091.44	29.01	1.276	0.30 ( 0.24)	0.81	7340.3	230.00
11	18214.25	29.53	1.261	0.30 ( 0.24)	0.81	7496.8	50500.00
12	18321.46	30.15	1.245	0.30 ( 0.24)	0.81	7681.2	220.50

13	18527.92	31.26	1.225	0.30 ( 0.24)	0.81	8008.0	110.00
14	18977.56	33.64	1.182	0.30 ( 0.24)	0.81	8750.0	100.00
15	19168.53	34.71	1.162	0.30 ( 0.24)	0.81	9076.0	110.00
16	19226.38	35.01	1.157	0.30 ( 0.24)	0.81	9199.1	100.00
17	19819.51	38.30	1.097	0.30 ( 0.25)	0.82	10510.4	130.00
18	20248.81	40.68	1.058	0.30 ( 0.25)	0.82	11455.6	10100.00
19	20920.86	44.56	1.012	0.30 ( 0.25)	0.83	12938.5	150.00
20	22298.07	53.33	0.919	0.30 ( 0.25)	0.84	16603.1	20100.00
21	22739.59	56.31	0.893	0.30 ( 0.25)	0.85	17786.9	31100.00
22	23238.86	59.77	0.862	0.30 ( 0.26)	0.86	19355.6	13600.00
23	23405.12	60.91	0.856	0.30 ( 0.26)	0.86	19863.5	390.00
24	24848.74	75.63	0.783	0.30 ( 0.27)	0.88	26491.1	13100.00
25	25194.66	82.53	0.749	0.30 ( 0.27)	0.89	29105.2	11801.00
26	26157.38	95.95	0.695	0.30 ( 0.27)	0.91	35015.0	11530.00
27	26610.85	100.48	0.682	0.30 ( 0.27)	0.91	37646.1	13510.00
28	27299.98	107.57	0.662	0.30 ( 0.28)	0.92	41638.7	13010.00
29	27819.00	111.67	0.651	0.30 ( 0.28)	0.92	44182.5	13500.00
30	28048.30	113.52	0.645	0.30 ( 0.28)	0.92	45313.6	11330.00
31	28637.31	121.62	0.624	0.30 ( 0.28)	0.93	50400.8	10630.00
32	28383.62	127.23	0.615	0.30 ( 0.28)	0.93	52990.6	12330.00
33	28123.27	133.87	0.603	0.30 ( 0.28)	0.94	56133.1	11600.00
34	27743.67	139.67	0.594	0.30 ( 0.28)	0.94	58367.4	11111.00
35	27325.96	145.84	0.583	0.30 ( 0.28)	0.94	60301.3	12201.00
36	26407.25	154.86	0.568	0.30 ( 0.28)	0.94	62389.5	12231.00
37	25567.08	162.44	0.555	0.30 ( 0.28)	0.94	63801.1	10400.00
38	24227.17	174.00	0.535	0.30 ( 0.28)	0.94	65421.8	10320.00
39	23546.11	178.94	0.527	0.30 ( 0.28)	0.94	65647.3	10210.00
40	22955.67	183.88	0.522	0.30 ( 0.28)	0.94	65809.7	12000.00
41	20010.93	213.50	0.499	0.30 ( 0.28)	0.95	66426.7	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 28637.31 Tc (MIN.) = 121.62  
AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA (ACRES) = 50400.78

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<

PEAK FLOWRATE TABLE FILE NAME: 0610508V.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	143.78	21.90	0.30 ( 0.30)	0.99	131.3	50800.00

TOTAL AREA (ACRES) = 131.3

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<



\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14683.57	16.34	1.787	0.30 ( 0.25)	0.82	3470.7	429.00
2	15432.00	17.92	1.702	0.30 ( 0.24)	0.82	3971.9	425.00
3	15516.84	18.19	1.687	0.30 ( 0.24)	0.82	4056.5	400.00
4	15769.21	19.80	1.601	0.30 ( 0.24)	0.81	4549.6	300.00
5	16731.30	23.42	1.452	0.30 ( 0.24)	0.81	5662.4	50700.00
6	17154.52	25.17	1.383	0.30 ( 0.24)	0.81	6179.5	210.00
7	17387.66	26.21	1.354	0.30 ( 0.24)	0.81	6476.5	50600.00
8	17617.41	27.12	1.329	0.30 ( 0.24)	0.81	6756.5	410.00
9	17922.84	28.32	1.295	0.30 ( 0.24)	0.81	7130.4	200.00
10	18091.44	29.01	1.276	0.30 ( 0.24)	0.81	7340.3	230.00
11	18214.25	29.53	1.261	0.30 ( 0.24)	0.81	7496.8	50500.00
12	18321.46	30.15	1.245	0.30 ( 0.24)	0.81	7681.2	220.50
13	18527.92	31.26	1.225	0.30 ( 0.24)	0.81	8008.0	110.00
14	18977.56	33.64	1.182	0.30 ( 0.24)	0.81	8750.0	100.00
15	19168.53	34.71	1.162	0.30 ( 0.24)	0.81	9076.0	110.00
16	19226.38	35.01	1.157	0.30 ( 0.24)	0.81	9199.1	100.00
17	19819.51	38.30	1.097	0.30 ( 0.25)	0.82	10510.4	130.00
18	20248.81	40.68	1.058	0.30 ( 0.25)	0.82	11455.6	10100.00
19	20920.86	44.56	1.012	0.30 ( 0.25)	0.83	12938.5	150.00
20	22298.07	53.33	0.919	0.30 ( 0.25)	0.84	16603.1	20100.00
21	22739.59	56.31	0.893	0.30 ( 0.25)	0.85	17786.9	31100.00
22	23238.86	59.77	0.862	0.30 ( 0.26)	0.86	19355.6	13600.00
23	23405.12	60.91	0.856	0.30 ( 0.26)	0.86	19863.5	390.00
24	24848.74	75.63	0.783	0.30 ( 0.27)	0.88	26491.1	13100.00
25	25194.66	82.53	0.749	0.30 ( 0.27)	0.89	29105.2	11801.00
26	26157.38	95.95	0.695	0.30 ( 0.27)	0.91	35015.0	11530.00
27	26610.85	100.48	0.682	0.30 ( 0.27)	0.91	37646.1	13510.00
28	27299.98	107.57	0.662	0.30 ( 0.28)	0.92	41638.7	13010.00
29	27819.00	111.67	0.651	0.30 ( 0.28)	0.92	44182.5	13500.00
30	28048.30	113.52	0.645	0.30 ( 0.28)	0.92	45313.6	11330.00
31	28637.31	121.62	0.624	0.30 ( 0.28)	0.93	50400.8	10630.00
32	28383.62	127.23	0.615	0.30 ( 0.28)	0.93	52990.6	12330.00
33	28123.27	133.87	0.603	0.30 ( 0.28)	0.94	56133.1	11600.00
34	27743.67	139.67	0.594	0.30 ( 0.28)	0.94	58367.4	11111.00
35	27325.96	145.84	0.583	0.30 ( 0.28)	0.94	60301.3	12201.00
36	26407.25	154.86	0.568	0.30 ( 0.28)	0.94	62389.5	12231.00
37	25567.08	162.44	0.555	0.30 ( 0.28)	0.94	63801.1	10400.00
38	24227.17	174.00	0.535	0.30 ( 0.28)	0.94	65421.8	10320.00
39	23546.11	178.94	0.527	0.30 ( 0.28)	0.94	65647.3	10210.00
40	22955.67	183.88	0.522	0.30 ( 0.28)	0.94	65809.7	12000.00
41	20010.93	213.50	0.499	0.30 ( 0.28)	0.95	66426.7	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124551.97 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	143.78	21.90	1.513	0.30 ( 0.30)	0.99	131.3	50800.00

LONGEST FLOWPATH FROM NODE 50800.00 TO NODE 13700.00 = 5946.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14814.98	16.34	1.787	0.30 ( 0.25)	0.82	3568.6	429.00
2	15567.88	17.92	1.702	0.30 ( 0.25)	0.82	4079.2	425.00
3	15653.36	18.19	1.687	0.30 ( 0.25)	0.82	4165.5	400.00

4	15908.55	19.80	1.601	0.30 ( 0.25)	0.82	4668.3	300.00
5	16471.80	21.90	1.513	0.30 ( 0.25)	0.82	5327.2	50800.00
6	16867.84	23.42	1.452	0.30 ( 0.24)	0.82	5793.6	50700.00
7	17282.95	25.17	1.383	0.30 ( 0.24)	0.81	6310.7	210.00
8	17512.64	26.21	1.354	0.30 ( 0.24)	0.81	6607.8	50600.00
9	17739.40	27.12	1.329	0.30 ( 0.24)	0.81	6887.7	410.00
10	18040.83	28.32	1.295	0.30 ( 0.24)	0.81	7261.7	200.00
11	18207.17	29.01	1.276	0.30 ( 0.24)	0.81	7471.6	230.00
12	18328.26	29.53	1.261	0.30 ( 0.24)	0.81	7628.1	50500.00
13	18433.59	30.15	1.245	0.30 ( 0.24)	0.81	7812.5	220.50
14	18637.65	31.26	1.225	0.30 ( 0.24)	0.81	8139.3	110.00
15	19082.18	33.64	1.182	0.30 ( 0.24)	0.81	8881.2	100.00
16	19270.85	34.71	1.162	0.30 ( 0.24)	0.81	9207.3	110.00
17	19328.06	35.01	1.157	0.30 ( 0.24)	0.82	9330.4	100.00
18	19914.11	38.30	1.097	0.30 ( 0.25)	0.82	10641.7	130.00
19	20338.80	40.68	1.058	0.30 ( 0.25)	0.82	11586.8	10100.00
20	21005.43	44.56	1.012	0.30 ( 0.25)	0.83	13069.8	150.00
21	22371.59	53.33	0.919	0.30 ( 0.25)	0.85	16734.4	20100.00
22	22810.03	56.31	0.893	0.30 ( 0.26)	0.85	17918.2	31100.00
23	23305.69	59.77	0.862	0.30 ( 0.26)	0.86	19486.9	13600.00
24	23471.18	60.91	0.856	0.30 ( 0.26)	0.86	19994.7	390.00
25	24906.22	75.63	0.783	0.30 ( 0.27)	0.88	26622.4	13100.00
26	25248.12	82.53	0.749	0.30 ( 0.27)	0.89	29236.5	11801.00
27	26204.49	95.95	0.695	0.30 ( 0.27)	0.91	35146.3	11530.00
28	26656.45	100.48	0.682	0.30 ( 0.27)	0.91	37777.4	13510.00
29	27343.21	107.57	0.662	0.30 ( 0.28)	0.92	41769.9	13010.00
30	27860.85	111.67	0.651	0.30 ( 0.28)	0.92	44313.8	13500.00
31	28089.53	113.52	0.645	0.30 ( 0.28)	0.92	45444.9	11330.00
32	28676.05	121.62	0.624	0.30 ( 0.28)	0.93	50532.0	10630.00
33	28421.22	127.23	0.615	0.30 ( 0.28)	0.93	53121.9	12330.00
34	28159.54	133.87	0.603	0.30 ( 0.28)	0.94	56264.4	11600.00
35	27778.78	139.67	0.594	0.30 ( 0.28)	0.94	58498.7	11111.00
36	27359.83	145.84	0.583	0.30 ( 0.28)	0.94	60432.5	12201.00
37	26439.31	154.86	0.568	0.30 ( 0.28)	0.94	62520.8	12231.00
38	25597.62	162.44	0.555	0.30 ( 0.28)	0.94	63932.3	10400.00
39	24255.38	174.00	0.535	0.30 ( 0.28)	0.94	65553.1	10320.00
40	23573.32	178.94	0.527	0.30 ( 0.28)	0.94	65778.6	10210.00
41	22982.32	183.88	0.522	0.30 ( 0.28)	0.94	65940.9	12000.00
42	20034.88	213.50	0.499	0.30 ( 0.28)	0.95	66557.9	10100.00

TOTAL AREA (ACRES) = 66557.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 28676.05 Tc (MIN.) = 121.624  
 EFFECTIVE AREA (ACRES) = 50532.04 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA (ACRES) = 66557.9  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124551.97 FEET.

=====

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 66557.9 TC (MIN.) = 121.62  
 EFFECTIVE AREA (ACRES) = 50532.04 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.931  
 PEAK FLOW RATE (CFS) = 28676.05

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14814.98	16.34	1.787	0.30 ( 0.25)	0.82	3568.6	429.00

2	15567.88	17.92	1.702	0.30	( 0.25)	0.82	4079.2	425.00
3	15653.36	18.19	1.687	0.30	( 0.25)	0.82	4165.5	400.00
4	15908.55	19.80	1.601	0.30	( 0.25)	0.82	4668.3	300.00
5	16471.80	21.90	1.513	0.30	( 0.25)	0.82	5327.2	50800.00
6	16867.84	23.42	1.452	0.30	( 0.24)	0.82	5793.6	50700.00
7	17282.95	25.17	1.383	0.30	( 0.24)	0.81	6310.7	210.00
8	17512.64	26.21	1.354	0.30	( 0.24)	0.81	6607.8	50600.00
9	17739.40	27.12	1.329	0.30	( 0.24)	0.81	6887.7	410.00
10	18040.83	28.32	1.295	0.30	( 0.24)	0.81	7261.7	200.00
11	18207.17	29.01	1.276	0.30	( 0.24)	0.81	7471.6	230.00
12	18328.26	29.53	1.261	0.30	( 0.24)	0.81	7628.1	50500.00
13	18433.59	30.15	1.245	0.30	( 0.24)	0.81	7812.5	220.50
14	18637.65	31.26	1.225	0.30	( 0.24)	0.81	8139.3	110.00
15	19082.18	33.64	1.182	0.30	( 0.24)	0.81	8881.2	100.00
16	19270.85	34.71	1.162	0.30	( 0.24)	0.81	9207.3	110.00
17	19328.06	35.01	1.157	0.30	( 0.24)	0.82	9330.4	100.00
18	19914.11	38.30	1.097	0.30	( 0.25)	0.82	10641.7	130.00
19	20338.80	40.68	1.058	0.30	( 0.25)	0.82	11586.8	10100.00
20	21005.43	44.56	1.012	0.30	( 0.25)	0.83	13069.8	150.00
21	22371.59	53.33	0.919	0.30	( 0.25)	0.85	16734.4	20100.00
22	22810.03	56.31	0.893	0.30	( 0.26)	0.85	17918.2	31100.00
23	23305.69	59.77	0.862	0.30	( 0.26)	0.86	19486.9	13600.00
24	23471.18	60.91	0.856	0.30	( 0.26)	0.86	19994.7	390.00
25	24906.22	75.63	0.783	0.30	( 0.27)	0.88	26622.4	13100.00
26	25248.12	82.53	0.749	0.30	( 0.27)	0.89	29236.5	11801.00
27	26204.49	95.95	0.695	0.30	( 0.27)	0.91	35146.3	11530.00
28	26656.45	100.48	0.682	0.30	( 0.27)	0.91	37777.4	13510.00
29	27343.21	107.57	0.662	0.30	( 0.28)	0.92	41769.9	13010.00
30	27860.85	111.67	0.651	0.30	( 0.28)	0.92	44313.8	13500.00
31	28089.53	113.52	0.645	0.30	( 0.28)	0.92	45444.9	11330.00
32	28676.05	121.62	0.624	0.30	( 0.28)	0.93	50532.0	10630.00
33	28421.22	127.23	0.615	0.30	( 0.28)	0.93	53121.9	12330.00
34	28159.54	133.87	0.603	0.30	( 0.28)	0.94	56264.4	11600.00
35	27778.78	139.67	0.594	0.30	( 0.28)	0.94	58498.7	11111.00
36	27359.83	145.84	0.583	0.30	( 0.28)	0.94	60432.5	12201.00
37	26439.31	154.86	0.568	0.30	( 0.28)	0.94	62520.8	12231.00
38	25597.62	162.44	0.555	0.30	( 0.28)	0.94	63932.3	10400.00
39	24255.38	174.00	0.535	0.30	( 0.28)	0.94	65553.1	10320.00
40	23573.32	178.94	0.527	0.30	( 0.28)	0.94	65778.6	10210.00
41	22982.32	183.88	0.522	0.30	( 0.28)	0.94	65940.9	12000.00
42	20034.88	213.50	0.499	0.30	( 0.28)	0.95	66557.9	10100.00

=====  
=====

END OF RATIONAL METHOD ANALYSIS

\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S36- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 10-YR RM EV APRIL 2019 CCHIUI \*  
\*\*\*\*\*

FILE NAME: RI10EV36.DAT  
TIME/DATE OF STUDY: 10:16 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 10.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 3.720
- 2) 10.00; 2.487
- 3) 15.00; 1.851
- 4) 20.00; 1.582
- 5) 25.00; 1.382
- 6) 30.00; 1.244
- 7) 40.00; 1.061
- 8) 50.00; 0.944
- 9) 60.00; 0.855
- 10) 90.00; 0.707
- 11) 120.00; 0.622
- 12) 180.00; 0.520
- 13) 360.00; 0.381
- 14) 1200.00; 0.166

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13600.00 TO NODE 13600.50 IS CODE = 21  
-----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 488.61  
ELEVATION DATA: UPSTREAM(FEET) = 872.12 DOWNSTREAM(FEET) = 744.80

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 10.995  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.360  
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "OPEN BRUSH"	-	3.39	0.30	1.000	69	11.00

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA RUNOFF(CFS) = 6.29  
TOTAL AREA(ACRES) = 3.39 PEAK FLOW RATE(CFS) = 6.29

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13600.50 TO NODE 13601.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 744.80 DOWNSTREAM(FEET) = 707.32  
CHANNEL LENGTH THRU SUBAREA(FEET) = 418.30 CHANNEL SLOPE = 0.0896  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.35  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.101  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.45	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 12.34  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.41  
AVERAGE FLOW DEPTH(FEET) = 0.34 TRAVEL TIME(MIN.) = 2.04  
Tc(MIN.) = 13.04  
SUBAREA AREA(ACRES) = 7.45 SUBAREA RUNOFF(CFS) = 12.07  
EFFECTIVE AREA(ACRES) = 10.84 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 10.8 PEAK FLOW RATE(CFS) = 17.57  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.42

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.42 FLOW VELOCITY(FEET/SEC.) = 3.89  
LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13601.00 = 906.91 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13601.00 TO NODE 13602.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 707.32 DOWNSTREAM(FEET) = 657.12  
CHANNEL LENGTH THRU SUBAREA(FEET) = 777.60 CHANNEL SLOPE = 0.0646  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.77  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.806

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.32	0.30	1.000	-
USER-DEFINED	-	4.70	0.30	1.000	-
USER-DEFINED	-	25.05	0.30	1.000	-
USER-DEFINED	-	0.45	0.30	1.000	-
USER-DEFINED	-	0.44	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 38.61

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.62

AVERAGE FLOW DEPTH(FEET) = 0.73 TRAVEL TIME(MIN.) = 2.81

Tc(MIN.) = 15.84

SUBAREA AREA(ACRES) = 30.96 SUBAREA RUNOFF(CFS) = 41.96  
EFFECTIVE AREA(ACRES) = 41.80 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 41.8 PEAK FLOW RATE(CFS) = 56.64  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.91

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.91 FLOW VELOCITY(FEET/SEC.) = 5.26

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13602.00 = 1684.51 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13602.00 TO NODE 13603.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 657.12 DOWNSTREAM(FEET) = 584.58  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1186.54 CHANNEL SLOPE = 0.0611  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.07  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.614

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.03	0.30	1.000	-
USER-DEFINED	-	2.51	0.30	1.000	-

USER-DEFINED - 1.52 0.30 1.000 -  
USER-DEFINED - 12.30 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 70.48

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.56

AVERAGE FLOW DEPTH(FEET) = 1.05 TRAVEL TIME(MIN.) = 3.56

Tc(MIN.) = 19.40

SUBAREA AREA(ACRES) = 23.36 SUBAREA RUNOFF(CFS) = 27.63

EFFECTIVE AREA(ACRES) = 65.16 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 65.2 PEAK FLOW RATE(CFS) = 77.08

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.10

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.10 FLOW VELOCITY(FEET/SEC.) = 5.72

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13603.00 = 2871.05 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 584.58 DOWNSTREAM(FEET) = 544.91  
CHANNEL LENGTH THRU SUBAREA(FEET) = 860.98 CHANNEL SLOPE = 0.0461  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.30  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.500

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	10.22	0.30	1.000	-
USER-DEFINED	-	4.19	0.30	1.000	-
USER-DEFINED	-	0.07	0.30	1.000	-
USER-DEFINED	-	1.11	0.30	1.000	-
USER-DEFINED	-	5.56	0.30	1.000	-
USER-DEFINED	-	0.09	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 88.56

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.44

AVERAGE FLOW DEPTH(FEET) = 1.29 TRAVEL TIME(MIN.) = 2.64

Tc(MIN.) = 22.04

SUBAREA AREA(ACRES) = 21.24 SUBAREA RUNOFF(CFS) = 22.95

EFFECTIVE AREA(ACRES) = 86.40 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 86.4 PEAK FLOW RATE(CFS) = 93.35

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.33

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.33 FLOW VELOCITY(FEET/SEC.) = 5.53

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13620.00 = 3732.03 FEET.

```

*****
FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 10
-----
>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<
=====
*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13522.00 IS CODE = 15.1
-----
>>>>DEFINE MEMORY BANK # 2 <<<<<
=====
PEAK FLOWRATE TABLE FILE NAME: S35X10.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:
STREAM      Q      Tc      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR)    (ACRES)  NODE
  1         688.52  58.84  0.30( 0.28) 0.95    1509.5  13510.00
  2         640.29  69.13  0.30( 0.28) 0.94    1579.8  13500.00
TOTAL AREA(ACRES) =      1579.8
*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13522.00 IS CODE = 14.0
-----
>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<
=====
MAIN-STREAM MEMORY DEFINED AS FOLLOWS:
STREAM      Q      Tc      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR)    (ACRES)  NODE
  1         688.52  58.84  0.30( 0.28) 0.95    1509.5  13510.00
  2         640.29  69.13  0.30( 0.28) 0.94    1579.8  13500.00
TOTAL AREA(ACRES) =      1579.8
*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13620.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 632.19 DOWNSTREAM(FEET) = 544.91
CHANNEL LENGTH THRU SUBAREA(FEET) = 2062.96 CHANNEL SLOPE = 0.0423
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.87
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.844
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp      Ap      SCS
LAND USE              GROUP  (ACRES)  (INCH/HR)  (DECIMAL)  CN
USER-DEFINED          -      17.68    0.30    1.000    -
USER-DEFINED          -      2.36    0.30    1.000    -
USER-DEFINED          -      0.60    0.30    1.000    -
USER-DEFINED          -      0.22    0.30    1.000    -
USER-DEFINED          -      2.22    0.30    1.000    -
USER-DEFINED          -      3.42    0.30    1.000    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 695.01
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.42

```

```

AVERAGE FLOW DEPTH(FEET) = 1.87 TRAVEL TIME(MIN.) = 3.30
Tc(MIN.) = 62.14
SUBAREA AREA(ACRES) = 26.50 SUBAREA RUNOFF(CFS) = 12.99
EFFECTIVE AREA(ACRES) = 1535.98 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
TOTAL AREA(ACRES) = 1606.3 PEAK FLOW RATE(CFS) = 774.35
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.99

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.99 FLOW VELOCITY(FEET/SEC.) = 10.79
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

** PEAK FLOW RATE TABLE **
STREAM      Q      Tc      Intensity  Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR)  (INCH/HR)  (ACRES)  NODE
  1         774.35  62.14    0.844  0.30( 0.28) 0.95    1536.0  13510.00
  2         736.87  72.51    0.793  0.30( 0.28) 0.95    1606.3  13500.00
NEW PEAK FLOW DATA ARE:
PEAK FLOW RATE(CFS) = 774.35 Tc(MIN.) = 62.14
AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.95 EFFECTIVE AREA(ACRES) = 1535.98
*****
FLOW PROCESS FROM NODE 13620.00 TO NODE 13620.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====
MAINLINE Tc(MIN.) = 62.14
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.844
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp      Ap      SCS
LAND USE              GROUP  (ACRES)  (INCH/HR)  (DECIMAL)  CN
NATURAL FAIR COVER
"WOODLAND,GRASS"      B      1.44    0.30    1.000    65
NATURAL FAIR COVER
"WOODLAND,GRASS"      B      0.01    0.30    1.000    65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 1.45 SUBAREA RUNOFF(CFS) = 0.71
EFFECTIVE AREA(ACRES) = 1537.43 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
TOTAL AREA(ACRES) = 1607.8 PEAK FLOW RATE(CFS) = 775.06
*****
FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 11
-----
>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<
=====
** MAIN STREAM CONFLUENCE DATA **
STREAM      Q      Tc      Intensity  Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR)  (INCH/HR)  (ACRES)  NODE
  1         775.06  62.14    0.844  0.30( 0.28) 0.95    1537.4  13510.00
  2         737.52  72.51    0.793  0.30( 0.28) 0.95    1607.8  13500.00
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

```

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	93.35	22.04	1.500	0.30( 0.30)	1.00	86.4	13600.00

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13620.00 = 3732.03 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	690.20	22.04	1.500	0.30( 0.29)	0.96	631.7	13600.00
2	817.40	62.14	0.844	0.30( 0.29)	0.95	1623.8	13510.00
3	775.88	72.51	0.793	0.30( 0.28)	0.95	1694.2	13500.00

TOTAL AREA (ACRES) = 1694.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 817.40 Tc(MIN.) = 62.136  
EFFECTIVE AREA(ACRES) = 1623.83 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA (ACRES) = 1694.2  
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13620.00 TO NODE 13640.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 544.91 DOWNSTREAM(FEET) = 489.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1384.37 CHANNEL SLOPE = 0.0404  
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.10

\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.834  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.39	0.30	1.000	-
USER-DEFINED	-	16.30	0.30	1.000	-
USER-DEFINED	-	4.08	0.30	1.000	-
USER-DEFINED	-	12.36	0.30	1.000	-
USER-DEFINED	-	11.23	0.30	1.000	-
USER-DEFINED	-	5.16	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 830.51  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.89  
AVERAGE FLOW DEPTH(FEET) = 2.10 TRAVEL TIME(MIN.) = 2.12  
Tc(MIN.) = 64.26  
SUBAREA AREA(ACRES) = 54.52 SUBAREA RUNOFF(CFS) = 26.21  
EFFECTIVE AREA(ACRES) = 1678.35 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95  
TOTAL AREA(ACRES) = 1748.7 PEAK FLOW RATE(CFS) = 828.33  
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.10

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 2.10 FLOW VELOCITY(FEET/SEC.) = 10.90

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	694.12	24.27	1.411	0.30( 0.29)	0.96	686.3	13600.00
2	828.33	64.26	0.834	0.30( 0.29)	0.95	1678.3	13510.00
3	783.33	74.67	0.783	0.30( 0.28)	0.95	1748.7	13500.00

NEW PEAK FLOW DATA ARE:  
PEAK FLOW RATE(CFS) = 828.33 Tc(MIN.) = 64.26  
AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.95 EFFECTIVE AREA(ACRES) = 1678.35

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 64.26  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.834  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	53.93	0.30	1.000	-
USER-DEFINED	-	0.45	0.30	1.000	-
USER-DEFINED	-	3.98	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA(ACRES) = 58.36 SUBAREA RUNOFF(CFS) = 28.05  
EFFECTIVE AREA(ACRES) = 1736.71 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95  
TOTAL AREA(ACRES) = 1807.1 PEAK FLOW RATE(CFS) = 856.39

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: P201XX10.DNA  
MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	158.08	17.90	0.30( 0.26)	0.85	133.8	20100.00

TOTAL AREA(ACRES) = 133.8

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	752.50	24.27	1.411	0.30( 0.29)	0.96	744.6	13600.00
2	856.39	64.26	0.834	0.30( 0.29)	0.95	1736.7	13510.00
3	808.68	74.67	0.783	0.30( 0.29)	0.95	1807.1	13500.00

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 158.08 17.90 1.695 0.30( 0.26) 0.85 133.8 20100.00
LONGEST FLOWPATH FROM NODE 20100.00 TO NODE 13640.00 = 5247.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 853.43 17.90 1.695 0.30( 0.28) 0.94 683.2 20100.00
2 879.44 24.27 1.411 0.30( 0.28) 0.95 878.4 13600.00
3 919.88 64.26 0.834 0.30( 0.28) 0.95 1870.5 13510.00
4 866.53 74.67 0.783 0.30( 0.28) 0.94 1940.9 13500.00
TOTAL AREA (ACRES) = 1940.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 919.88 Tc (MIN.) = 64.255
EFFECTIVE AREA (ACRES) = 1870.51 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
TOTAL AREA (ACRES) = 1940.9
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13640.00 TO NODE 13641.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 489.00 DOWNSTREAM (FEET) = 436.89
CHANNEL LENGTH THRU SUBAREA (FEET) = 2994.52 CHANNEL SLOPE = 0.0174
GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
\*ESTIMATED CHANNEL HEIGHT (FEET) = 2.85
\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.805

SUBAREA LOSS RATE DATA (AMC II):

Table with 7 columns: DEVELOPMENT TYPE/, LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include USER-DEFINED entries with various area and flow values.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 935.24
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.51
AVERAGE FLOW DEPTH (FEET) = 2.85 TRAVEL TIME (MIN.) = 5.86
Tc (MIN.) = 70.12
SUBAREA AREA (ACRES) = 67.58 SUBAREA RUNOFF (CFS) = 30.72
EFFECTIVE AREA (ACRES) = 1938.09 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
TOTAL AREA (ACRES) = 2008.4 PEAK FLOW RATE (CFS) = 919.88
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
\*ESTIMATED CHANNEL HEIGHT (FEET) = 2.83

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 2.83 FLOW VELOCITY (FEET/SEC.) = 8.46
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13641.00 = 25056.61 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 853.43 23.86 1.428 0.30( 0.28) 0.95 750.8 20100.00
2 879.44 30.19 1.241 0.30( 0.28) 0.95 946.0 13600.00
3 919.88 70.12 0.805 0.30( 0.28) 0.95 1938.1 13510.00
4 866.53 80.65 0.753 0.30( 0.28) 0.95 2008.4 13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 919.88 Tc (MIN.) = 70.12
AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.95 EFFECTIVE AREA (ACRES) = 1938.09

\*\*\*\*\*

FLOW PROCESS FROM NODE 13641.00 TO NODE 13641.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 70.12

\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.805

SUBAREA LOSS RATE DATA (AMC II):

Table with 7 columns: DEVELOPMENT TYPE/, LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include USER-DEFINED entries with various area and flow values.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 104.70 SUBAREA RUNOFF (CFS) = 47.60
EFFECTIVE AREA (ACRES) = 2042.79 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
TOTAL AREA (ACRES) = 2113.1 PEAK FLOW RATE (CFS) = 955.58

\*\*\*\*\*

FLOW PROCESS FROM NODE 13641.00 TO NODE 13641.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 70.12

\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.805

SUBAREA LOSS RATE DATA (AMC II):

Table with 7 columns: DEVELOPMENT TYPE/, LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include USER-DEFINED entries with various area and flow values.

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 8.03 SUBAREA RUNOFF (CFS) = 3.65
EFFECTIVE AREA (ACRES) = 2050.82 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
TOTAL AREA (ACRES) = 2121.2 PEAK FLOW RATE (CFS) = 959.23

\*\*\*\*\*

FLOW PROCESS FROM NODE 13641.00 TO NODE 13642.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 436.89 DOWNSTREAM(FEET) = 394.80

CHANNEL LENGTH THRU SUBAREA(FEET) = 2814.16 CHANNEL SLOPE = 0.0150

GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 3.10

\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.777

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.67	0.30	1.000	-
USER-DEFINED	-	24.24	0.30	1.000	-
USER-DEFINED	-	1.34	0.30	1.000	-
USER-DEFINED	-	74.98	0.30	1.000	-
USER-DEFINED	-	101.12	0.30	1.000	-
USER-DEFINED	-	16.90	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1006.31

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.26

AVERAGE FLOW DEPTH(FEET) = 3.10 TRAVEL TIME(MIN.) = 5.68

Tc(MIN.) = 75.80

SUBAREA AREA(ACRES) = 219.25 SUBAREA RUNOFF(CFS) = 94.15

EFFECTIVE AREA(ACRES) = 2270.07 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96

TOTAL AREA(ACRES) = 2340.4 PEAK FLOW RATE(CFS) = 1001.67

GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 3.09

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 3.09 FLOW VELOCITY(FEET/SEC.) = 8.26

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13642.00 = 27870.77 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap (DECIMAL)	Ae (ACRES)	HEADWATER NODE
1	942.27	29.58	1.256	0.30( 0.29)	0.96	1082.8	20100.00
2	974.92	35.88	1.136	0.30( 0.29)	0.96	1278.0	13600.00
3	1001.67	75.80	0.777	0.30( 0.29)	0.96	2270.1	13510.00
4	923.24	86.45	0.725	0.30( 0.29)	0.95	2340.4	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 1001.67 Tc(MIN.) = 75.80

AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.96 EFFECTIVE AREA(ACRES) = 2270.07

\*\*\*\*\*

FLOW PROCESS FROM NODE 13642.00 TO NODE 13642.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 75.80

\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.777

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	9.95	0.30	1.000	-
USER-DEFINED	-	10.02	0.30	1.000	-
USER-DEFINED	-	4.45	0.30	1.000	-
USER-DEFINED	-	179.37	0.30	1.000	-
USER-DEFINED	-	11.47	0.30	1.000	-
USER-DEFINED	-	0.17	0.30	0.850	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 215.43 SUBAREA RUNOFF(CFS) = 92.52

EFFECTIVE AREA(ACRES) = 2485.50 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96

TOTAL AREA(ACRES) = 2555.9 PEAK FLOW RATE(CFS) = 1094.18

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap (DECIMAL)	Ae (ACRES)	HEADWATER NODE
1	1127.58	29.58	1.256	0.30( 0.29)	0.97	1298.2	20100.00
2	1137.09	35.88	1.136	0.30( 0.29)	0.97	1493.4	13600.00
3	1094.18	75.80	0.777	0.30( 0.29)	0.96	2485.5	13510.00
4	1005.57	86.45	0.725	0.30( 0.29)	0.96	2555.9	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 1137.09 Tc(MIN.) = 35.88

AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.97 EFFECTIVE AREA(ACRES) = 1493.41

\*\*\*\*\*

FLOW PROCESS FROM NODE 13642.00 TO NODE 13642.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 35.88

\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.136

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.03	0.30	0.850	-
USER-DEFINED	-	5.14	0.30	1.000	-
USER-DEFINED	-	11.22	0.30	1.000	-
USER-DEFINED	-	0.33	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 16.72 SUBAREA RUNOFF(CFS) = 12.59

EFFECTIVE AREA(ACRES) = 1510.13 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97

TOTAL AREA(ACRES) = 2572.6 PEAK FLOW RATE(CFS) = 1149.68

\*\*\*\*\*

FLOW PROCESS FROM NODE 13642.00 TO NODE 13643.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 394.80 DOWNSTREAM(FEET) = 342.39

CHANNEL LENGTH THRU SUBAREA(FEET) = 2913.57 CHANNEL SLOPE = 0.0180



GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 3.25  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.048  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	2.17	0.30	1.000	-
USER-DEFINED	-	9.19	0.30	1.000	-
USER-DEFINED	-	67.57	0.30	1.000	-
USER-DEFINED	-	35.19	0.30	1.000	-
USER-DEFINED	-	30.67	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 1198.50  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 9.29  
 AVERAGE FLOW DEPTH (FEET) = 3.25 TRAVEL TIME (MIN.) = 5.22  
 Tc (MIN.) = 41.11  
 SUBAREA AREA (ACRES) = 145.01 SUBAREA RUNOFF (CFS) = 97.63  
 EFFECTIVE AREA (ACRES) = 1655.14 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97  
 TOTAL AREA (ACRES) = 2717.6 PEAK FLOW RATE (CFS) = 1149.68  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 3.17

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 3.17 FLOW VELOCITY (FEET/SEC.) = 9.18  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13643.00 = 30784.34 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1141.97	34.79	1.156	0.30 ( 0.29)	0.97	1459.9	20100.00
2	1149.68	41.11	1.048	0.30 ( 0.29)	0.97	1655.1	13600.00
3	1101.36	81.12	0.751	0.30 ( 0.29)	0.96	2647.2	13510.00
4	1011.96	91.91	0.702	0.30 ( 0.29)	0.96	2717.6	13500.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE (CFS) = 1149.68 Tc (MIN.) = 41.11  
 AREA-AVERAGED Fm (INCH/HR) = 0.29 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.97 EFFECTIVE AREA (ACRES) = 1655.14

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13643.00 TO NODE 13643.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

\*\*\*\*\*  
 MAINLINE Tc (MIN.) = 41.11  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.048

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.89	0.30	1.000	-
USER-DEFINED	-	20.65	0.30	1.000	-
USER-DEFINED	-	2.69	0.30	1.000	-
USER-DEFINED	-	8.45	0.30	1.000	-

USER-DEFINED - 96.93 0.30 1.000 -  
 USER-DEFINED - 13.19 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 142.80 SUBAREA RUNOFF (CFS) = 96.14  
 EFFECTIVE AREA (ACRES) = 1797.94 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97  
 TOTAL AREA (ACRES) = 2860.4 PEAK FLOW RATE (CFS) = 1223.45

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1246.17	34.79	1.156	0.30 ( 0.29)	0.97	1602.7	20100.00
2	1223.45	41.11	1.048	0.30 ( 0.29)	0.97	1797.9	13600.00
3	1159.10	81.12	0.751	0.30 ( 0.29)	0.96	2790.0	13510.00
4	1062.94	91.91	0.702	0.30 ( 0.29)	0.96	2860.4	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 1246.17 Tc (MIN.) = 34.79  
 AREA-AVERAGED Fm (INCH/HR) = 0.29 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.97 EFFECTIVE AREA (ACRES) = 1602.73

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13643.00 TO NODE 13643.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

\*\*\*\*\*  
 MAINLINE Tc (MIN.) = 34.79  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.156

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	42.54	0.30	1.000	-
USER-DEFINED	-	16.96	0.30	1.000	-
USER-DEFINED	-	80.60	0.30	1.000	-
USER-DEFINED	-	1.56	0.30	1.000	-
USER-DEFINED	-	2.00	0.30	1.000	-
USER-DEFINED	-	3.11	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 146.77 SUBAREA RUNOFF (CFS) = 113.12  
 EFFECTIVE AREA (ACRES) = 1749.50 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98  
 TOTAL AREA (ACRES) = 3007.2 PEAK FLOW RATE (CFS) = 1359.28

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13643.00 TO NODE 13660.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

\*\*\*\*\*  
 ELEVATION DATA: UPSTREAM (FEET) = 342.39 DOWNSTREAM (FEET) = 300.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1591.23 CHANNEL SLOPE = 0.0266  
 GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 3.15  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.113  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

LAND USE            GROUP    (ACRES)    (INCH/HR)    (DECIMAL)    CN  
 USER-DEFINED       -        0.89        0.30        1.000       -  
 USER-DEFINED       -        23.73       0.30        1.000       -  
 USER-DEFINED       -        0.27        0.30        1.000       -  
 USER-DEFINED       -        19.87       0.30        1.000       -  
 USER-DEFINED       -        6.40        0.30        1.000       -  
 USER-DEFINED       -        3.14        0.30        1.000       -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1379.14  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 11.11  
 AVERAGE FLOW DEPTH (FEET) = 3.15    TRAVEL TIME (MIN.) = 2.39  
 Tc (MIN.) = 37.18  
 SUBAREA AREA (ACRES) = 54.30        SUBAREA RUNOFF (CFS) = 39.72  
 EFFECTIVE AREA (ACRES) = 1803.80    AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30    AREA-AVERAGED Ap = 0.98  
 TOTAL AREA (ACRES) = 3061.5        PEAK FLOW RATE (CFS) = 1359.28  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 30.00    CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000    MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 3.12  
  
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 3.12    FLOW VELOCITY (FEET/SEC.) = 11.08  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 32375.57 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1359.28	37.18	1.113	0.30 ( 0.29)	0.98	1803.8	20100.00
2	1322.27	43.52	1.020	0.30 ( 0.29)	0.98	1999.0	13600.00
3	1218.66	83.59	0.739	0.30 ( 0.29)	0.97	2991.1	13510.00
4	1115.99	94.45	0.694	0.30 ( 0.29)	0.96	3061.5	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 1359.28    Tc (MIN.) = 37.18  
 AREA-AVERAGED Fm (INCH/HR) = 0.29    AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.98    EFFECTIVE AREA (ACRES) = 1803.80

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 =====

MAINLINE Tc (MIN.) = 37.18  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.113  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.67	0.30	1.000	-
USER-DEFINED	-	9.52	0.30	1.000	-
USER-DEFINED	-	0.71	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	39.42	0.30	1.000	-
USER-DEFINED	-	0.62	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 51.16        SUBAREA RUNOFF (CFS) = 37.42  
 EFFECTIVE AREA (ACRES) = 1854.96    AREA-AVERAGED Fm (INCH/HR) = 0.29

AREA-AVERAGED Fp (INCH/HR) = 0.30    AREA-AVERAGED Ap = 0.98  
 TOTAL AREA (ACRES) = 3112.6        PEAK FLOW RATE (CFS) = 1367.67

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 =====

MAINLINE Tc (MIN.) = 37.18  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.113  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.11	0.30	1.000	-
USER-DEFINED	-	0.77	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	2.69	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 3.79        SUBAREA RUNOFF (CFS) = 2.77  
 EFFECTIVE AREA (ACRES) = 1858.75    AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30    AREA-AVERAGED Ap = 0.98  
 TOTAL AREA (ACRES) = 3116.4        PEAK FLOW RATE (CFS) = 1370.44

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13643.00 TO NODE 13660.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 1 <<<<<  
 =====

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13659.00 TO NODE 13659.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 1 <<<<<  
 =====

PEAK FLOWRATE TABLE FILE NAME: 2P10EVAA.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	369.81	15.08	0.30 ( 0.11)	0.36	172.7	110.00
2	370.44	17.62	0.30 ( 0.11)	0.37	203.0	100.00
3	361.39	19.04	0.30 ( 0.11)	0.38	213.7	100.00
4	316.02	22.37	0.30 ( 0.12)	0.40	221.1	130.00
TOTAL AREA (ACRES) =		221.1				

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13659.00 TO NODE 13660.00 IS CODE = 31  
 -----

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<

>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<  
 =====

ELEVATION DATA: UPSTREAM (FEET) = 338.00    DOWNSTREAM (FEET) = 300.00  
 FLOW LENGTH (FEET) = 881.07    MANNING'S N = 0.013  
 DEPTH OF FLOW IN 87.0 INCH PIPE IS 70.7 INCHES  
 PIPE-FLOW VELOCITY (FEET/SEC.) = 38.17  
 ESTIMATED PIPE DIAMETER (INCH) = 87.00    NUMBER OF PIPES = 1  
 PIPE-FLOW (CFS) = 1370.44  
 PIPE TRAVEL TIME (MIN.) = 0.38    Tc (MIN.) = 37.56

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1370.44	37.56	1.106	0.30( 0.29)	0.98	1858.7	20100.00
2	1343.78	43.90	1.015	0.30( 0.29)	0.98	2054.0	13600.00
3	1229.56	83.98	0.737	0.30( 0.29)	0.97	3046.0	13510.00
4	1135.31	94.85	0.693	0.30( 0.29)	0.97	3116.4	13500.00

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	369.81	15.08	1.847	0.30( 0.11)	0.36	172.7	110.00
2	370.44	17.62	1.710	0.30( 0.11)	0.37	203.0	100.00
3	361.39	19.04	1.634	0.30( 0.11)	0.38	213.7	100.00
4	316.02	22.37	1.487	0.30( 0.12)	0.40	221.1	130.00

LONGEST FLOWPATH FROM NODE 130.00 TO NODE 13660.00 = 6327.50 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1421.87	15.08	1.847	0.30( 0.26)	0.86	918.7	110.00
2	1491.67	17.62	1.710	0.30( 0.26)	0.86	1074.8	100.00
3	1507.68	19.04	1.634	0.30( 0.26)	0.87	1155.9	100.00
4	1515.65	22.37	1.487	0.30( 0.26)	0.88	1328.1	130.00
5	1598.25	37.56	1.106	0.30( 0.28)	0.92	2079.8	20100.00
6	1550.73	43.90	1.015	0.30( 0.28)	0.92	2275.1	13600.00
7	1372.07	83.98	0.737	0.30( 0.28)	0.93	3267.1	13510.00
8	1267.78	94.85	0.693	0.30( 0.28)	0.93	3337.5	13500.00

TOTAL AREA (ACRES) = 3337.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 1598.25 Tc(MIN.) = 37.564  
EFFECTIVE AREA(ACRES) = 2079.85 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.86  
TOTAL AREA(ACRES) = 3337.5  
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 37.56

\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.106

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "FALLOW"	B	1.11	0.30	1.000	86

AGRICULTURAL POOR COVER

"FALLOW"	B	0.44	0.30	1.000	86
NATURAL FAIR COVER "GRASS"	B	1.49	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	1.70	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	1.09	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	18.57	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA(ACRES) = 24.40 SUBAREA RUNOFF(CFS) = 17.69  
EFFECTIVE AREA(ACRES) = 2104.25 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
TOTAL AREA(ACRES) = 3361.9 PEAK FLOW RATE(CFS) = 1598.25  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 37.56

\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.106

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL FAIR COVER "ORCHARDS"	B	12.39	0.30	1.000	65
AGRICULTURAL FAIR COVER "ORCHARDS"	B	2.30	0.30	1.000	65
AGRICULTURAL POOR COVER "ROW CROPS, CONTOURED"	B	5.19	0.30	1.000	79
AGRICULTURAL POOR COVER "ROW CROPS, STRAIGHT ROW"	B	28.71	0.30	1.000	81
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.17	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA(ACRES) = 48.76 SUBAREA RUNOFF(CFS) = 35.35  
EFFECTIVE AREA(ACRES) = 2153.01 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
TOTAL AREA(ACRES) = 3410.7 PEAK FLOW RATE(CFS) = 1607.75

\*\*\*\*\*

FLOW PROCESS FROM NODE 13660.00 TO NODE 13680.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 300.00 DOWNSTREAM(FEET) = 288.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 933.89 CHANNEL SLOPE = 0.0128  
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 4.19  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.074  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 0.22 0.30 1.000 -  
 USER-DEFINED - 9.23 0.30 1.000 -  
 USER-DEFINED - 0.54 0.30 1.000 -  
 USER-DEFINED - 5.66 0.30 1.000 -  
 USER-DEFINED - 3.66 0.30 1.000 -  
 USER-DEFINED - 0.67 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1614.71  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.06  
 AVERAGE FLOW DEPTH(FEET) = 4.19 TRAVEL TIME(MIN.) = 1.72  
 Tc(MIN.) = 39.28  
 SUBAREA AREA(ACRES) = 19.98 SUBAREA RUNOFF(CFS) = 13.92  
 EFFECTIVE AREA(ACRES) = 2172.99 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 3430.6 PEAK FLOW RATE(CFS) = 1607.75  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 4.18

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 4.18 FLOW VELOCITY(FEET/SEC.) = 9.05  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13680.00 = 34190.53 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1421.87	16.86	1.751	0.30( 0.26)	0.88	1011.8	110.00
2	1496.44	19.37	1.616	0.30( 0.26)	0.87	1168.0	100.00
3	1516.47	20.79	1.550	0.30( 0.26)	0.88	1249.0	100.00
4	1539.45	24.11	1.418	0.30( 0.27)	0.89	1421.3	130.00
5	1607.75	39.28	1.074	0.30( 0.28)	0.92	2173.0	20100.00
6	1560.66	45.63	0.995	0.30( 0.28)	0.92	2368.2	13600.00
7	1375.63	85.78	0.728	0.30( 0.28)	0.93	3360.3	13510.00
8	1272.00	96.70	0.688	0.30( 0.28)	0.93	3430.6	13500.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE(CFS) = 1607.75 Tc(MIN.) = 39.28  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.92 EFFECTIVE AREA(ACRES) = 2172.99

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81  
 -----  
 >>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 39.28  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.074  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 1.56 0.30 1.000 -  
 USER-DEFINED - 9.40 0.30 1.000 -  
 USER-DEFINED - 2.76 0.30 1.000 -  
 USER-DEFINED - 17.38 0.30 1.000 -  
 USER-DEFINED - 2.46 0.30 1.000 -

USER-DEFINED - 5.56 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 39.12 SUBAREA RUNOFF(CFS) = 27.26  
 EFFECTIVE AREA(ACRES) = 2212.11 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 3469.8 PEAK FLOW RATE(CFS) = 1607.75  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81  
 -----  
 >>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 39.28  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.074  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 0.65 0.30 1.000 -  
 USER-DEFINED - 1.70 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 2.35 SUBAREA RUNOFF(CFS) = 1.64  
 EFFECTIVE AREA(ACRES) = 2214.46 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 3472.1 PEAK FLOW RATE(CFS) = 1607.75  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13660.00 TO NODE 13680.00 IS CODE = 12  
 -----  
 >>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81  
 -----  
 >>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 39.28  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.074  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 5.29 0.30 1.000 -  
 USER-DEFINED - 31.25 0.30 1.000 -  
 USER-DEFINED - 0.22 0.30 1.000 -  
 USER-DEFINED - 6.26 0.30 1.000 -  
 USER-DEFINED - 0.07 0.30 1.000 -  
 USER-DEFINED - 0.22 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 43.31 SUBAREA RUNOFF(CFS) = 30.18  
 EFFECTIVE AREA(ACRES) = 2257.77 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 3515.4 PEAK FLOW RATE(CFS) = 1619.86

```

*****
FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 39.28
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.074
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp        Ap      SCS
LAND USE            GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN
USER-DEFINED        -         2.47     0.30     0.850    -
USER-DEFINED        -         3.06     0.30     0.850    -
USER-DEFINED        -        17.76     0.30     0.500    -
USER-DEFINED        -         7.31     0.30     0.500    -
USER-DEFINED        -         0.34     0.30     1.000    -
USER-DEFINED        -         8.22     0.30     1.000    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.659
SUBAREA AREA(ACRES) = 39.16      SUBAREA RUNOFF(CFS) = 30.89
EFFECTIVE AREA(ACRES) = 2296.93  AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30  AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 3554.6      PEAK FLOW RATE(CFS) = 1650.76

```

```

*****
FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 39.28
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.074
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp        Ap      SCS
LAND USE            GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN
USER-DEFINED        -         0.53     0.30     1.000    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 0.53      SUBAREA RUNOFF(CFS) = 0.37
EFFECTIVE AREA(ACRES) = 2297.46  AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30  AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 3555.1      PEAK FLOW RATE(CFS) = 1651.13

```

```

*****
FLOW PROCESS FROM NODE 13680.00 TO NODE 13682.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 288.00  DOWNSTREAM(FEET) = 242.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 2860.77  CHANNEL SLOPE = 0.0161
GIVEN CHANNEL BASE(FEET) = 30.00  CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000  MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 3.99
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.013
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp        Ap      SCS
LAND USE            GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN
USER-DEFINED        -         0.22     0.30     1.000    -
USER-DEFINED        -         5.28     0.30     1.000    -

```

```

USER-DEFINED        -         0.52     0.30     1.000    -
USER-DEFINED        -         3.61     0.30     1.000    -
USER-DEFINED        -         0.67     0.30     1.000    -
USER-DEFINED        -         1.37     0.30     1.000    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1654.87
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.87
AVERAGE FLOW DEPTH(FEET) = 3.99  TRAVEL TIME(MIN.) = 4.83
Tc(MIN.) = 44.11
SUBAREA AREA(ACRES) = 11.67      SUBAREA RUNOFF(CFS) = 7.49
EFFECTIVE AREA(ACRES) = 2309.13  AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30  AREA-AVERAGED Ap = 0.92
TOTAL AREA(ACRES) = 3566.8      PEAK FLOW RATE(CFS) = 1651.13
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 30.00  CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000  MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 3.99

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 3.99  FLOW VELOCITY(FEET/SEC.) = 9.87
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13682.00 = 37051.30 FEET.

```

```

** PEAK FLOW RATE TABLE **
STREAM      Q      Tc  Intensity  Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)  (MIN.) (INCH/HR) (INCH/HR)  (ACRES)  NODE
1  1521.80  21.81  1.510  0.30( 0.26) 0.88  1148.0  110.00
2  1573.72  24.27  1.411  0.30( 0.26) 0.88  1304.1  100.00
3  1590.73  25.67  1.363  0.30( 0.26) 0.88  1385.2  100.00
4  1600.63  28.98  1.272  0.30( 0.27) 0.89  1557.4  130.00
5  1651.13  44.11  1.013  0.30( 0.28) 0.92  2309.1  20100.00
6  1611.81  50.50  0.940  0.30( 0.28) 0.92  2504.3  13600.00
7  1408.16  90.85  0.705  0.30( 0.28) 0.93  3496.4  13510.00
8  1310.02  101.87 0.673  0.30( 0.28) 0.93  3566.8  13500.00
NEW PEAK FLOW DATA ARE:
PEAK FLOW RATE(CFS) = 1651.13  Tc(MIN.) = 44.11
AREA-AVERAGED Fm(INCH/HR) = 0.28  AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.92  EFFECTIVE AREA(ACRES) = 2309.13

```

```

*****
FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 44.11
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.013
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp        Ap      SCS
LAND USE            GROUP   (ACRES)  (INCH/HR) (DECIMAL) CN
USER-DEFINED        -         6.90     0.30     1.000    -
USER-DEFINED        -        23.04     0.30     1.000    -
USER-DEFINED        -         1.18     0.30     1.000    -
USER-DEFINED        -         1.56     0.30     1.000    -
USER-DEFINED        -        53.20     0.30     1.000    -
USER-DEFINED        -         2.08     0.30     1.000    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 87.96      SUBAREA RUNOFF(CFS) = 56.44

```

EFFECTIVE AREA (ACRES) = 2397.09 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
TOTAL AREA (ACRES) = 3654.7 PEAK FLOW RATE (CFS) = 1651.13  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 44.11  
\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.013  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.01	0.30	1.000	-
USER-DEFINED	-	0.18	0.30	1.000	-
USER-DEFINED	-	0.38	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	7.73	0.30	1.000	-
USER-DEFINED	-	4.37	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 12.89 SUBAREA RUNOFF (CFS) = 8.27  
EFFECTIVE AREA (ACRES) = 2409.98 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
TOTAL AREA (ACRES) = 3667.6 PEAK FLOW RATE (CFS) = 1651.13  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 44.11  
\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.013  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "FALLOW"	B	2.57	0.30	1.000	86
AGRICULTURAL POOR COVER "FALLOW"	B	1.97	0.30	1.000	86
NATURAL FAIR COVER "GRASS"	B	1.00	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	2.98	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	2.39	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	1.67	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 12.58 SUBAREA RUNOFF (CFS) = 8.07  
EFFECTIVE AREA (ACRES) = 2422.56 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
TOTAL AREA (ACRES) = 3680.2 PEAK FLOW RATE (CFS) = 1651.13  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 44.11  
\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.013  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	0.44	0.30	1.000	66
PUBLIC PARK	B	2.65	0.30	0.850	56
PUBLIC PARK	B	1.16	0.30	0.850	56
RESIDENTIAL "5-7 DWELLINGS/ACRE"	B	0.47	0.30	0.500	56
RESIDENTIAL "5-7 DWELLINGS/ACRE"	B	0.25	0.30	0.500	56
AGRICULTURAL POOR COVER "ROW CROPS, STRAIGHT ROW"	B	20.24	0.30	1.000	81

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.963  
SUBAREA AREA (ACRES) = 25.21 SUBAREA RUNOFF (CFS) = 16.43  
EFFECTIVE AREA (ACRES) = 2447.77 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
TOTAL AREA (ACRES) = 3705.4 PEAK FLOW RATE (CFS) = 1651.13  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 44.11  
\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.013  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.08	0.30	1.000	-
USER-DEFINED	-	6.75	0.30	1.000	-
USER-DEFINED	-	0.02	0.30	1.000	-
USER-DEFINED	-	0.93	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 14.78 SUBAREA RUNOFF (CFS) = 9.48  
EFFECTIVE AREA (ACRES) = 2462.55 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
TOTAL AREA (ACRES) = 3720.2 PEAK FLOW RATE (CFS) = 1651.13  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13682.00 TO NODE 13683.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 242.00 DOWNSTREAM (FEET) = 208.53

CHANNEL LENGTH THRU SUBAREA (FEET) = 2526.22 CHANNEL SLOPE = 0.0132  
 GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 4.22  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.960  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.49	0.30	1.000	-
USER-DEFINED	-	13.31	0.30	1.000	-
USER-DEFINED	-	0.87	0.30	1.000	-
USER-DEFINED	-	20.26	0.30	1.000	-
USER-DEFINED	-	1.21	0.30	1.000	-
USER-DEFINED	-	0.05	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 1664.24  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 9.24  
 AVERAGE FLOW DEPTH (FEET) = 4.22 TRAVEL TIME (MIN.) = 4.56  
 Tc (MIN.) = 48.67  
 SUBAREA AREA (ACRES) = 44.19 SUBAREA RUNOFF (CFS) = 26.24  
 EFFECTIVE AREA (ACRES) = 2506.74 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 3764.4 PEAK FLOW RATE (CFS) = 1651.13  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 4.20

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 4.20 FLOW VELOCITY (FEET/SEC.) = 9.23  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13683.00 = 39577.52 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1521.80	26.46	1.342	0.30 (0.27)	0.90	1345.6	110.00
2	1573.72	28.89	1.275	0.30 (0.27)	0.89	1501.7	100.00
3	1590.73	30.27	1.239	0.30 (0.27)	0.89	1582.8	100.00
4	1600.63	33.57	1.179	0.30 (0.27)	0.90	1755.0	130.00
5	1651.13	48.67	0.960	0.30 (0.28)	0.93	2506.7	20100.00
6	1611.81	55.09	0.899	0.30 (0.28)	0.93	2701.9	13600.00
7	1408.16	95.63	0.691	0.30 (0.28)	0.93	3694.0	13510.00
8	1318.82	106.75	0.660	0.30 (0.28)	0.93	3764.4	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 1651.13 Tc (MIN.) = 48.67  
 AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA (ACRES) = 2506.74

\*\*\*\*\*

FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 48.67

\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.960

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
USER-DEFINED	-	12.56	0.30	1.000	-
USER-DEFINED	-	0.81	0.30	1.000	-
USER-DEFINED	-	0.01	0.30	1.000	-
USER-DEFINED	-	1.11	0.30	1.000	-
USER-DEFINED	-	0.59	0.30	1.000	-
USER-DEFINED	-	3.04	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 18.12 SUBAREA RUNOFF (CFS) = 10.76  
 EFFECTIVE AREA (ACRES) = 2524.86 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 3782.5 PEAK FLOW RATE (CFS) = 1651.13  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 48.67

\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.960

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

RESIDENTIAL					
"8-10 DWELLINGS/ACRE"	B	0.10	0.30	0.400	56
PUBLIC PARK	B	1.30	0.30	0.850	56
RESIDENTIAL					
"8-10 DWELLINGS/ACRE"	B	0.10	0.30	0.400	56
PUBLIC PARK	B	1.70	0.30	0.850	56
PUBLIC PARK	B	0.10	0.30	0.850	56
PUBLIC PARK	B	2.90	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.835

SUBAREA AREA (ACRES) = 6.20 SUBAREA RUNOFF (CFS) = 3.96

EFFECTIVE AREA (ACRES) = 2531.06 AREA-AVERAGED Fm (INCH/HR) = 0.28

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA (ACRES) = 3788.7 PEAK FLOW RATE (CFS) = 1651.13

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 48.67

\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.960

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

RESIDENTIAL					
"5-7 DWELLINGS/ACRE"	B	0.10	0.30	0.500	56
CONDOMINIUMS	B	0.10	0.30	0.350	56
PUBLIC PARK	B	6.90	0.30	0.850	56
PUBLIC PARK	B	0.40	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.839

SUBAREA AREA (ACRES) = 7.50 SUBAREA RUNOFF (CFS) = 4.78  
EFFECTIVE AREA (ACRES) = 2538.56 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA (ACRES) = 3796.2 PEAK FLOW RATE (CFS) = 1651.13  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13682.00 TO NODE 13683.00 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 3 <<<<<<

\*\*\*\*\*  
\*\*\*MEMORY BANK # 3 IS EMPTY - PROCESS IGNORED.\*\*\*

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<

MAINLINE Tc (MIN.) = 48.67

\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.960

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "FALLOW"	B	2.55	0.30	1.000	86
AGRICULTURAL POOR COVER "FALLOW"	B	0.01	0.30	1.000	86
AGRICULTURAL POOR COVER "FALLOW"	B	1.35	0.30	1.000	86
NATURAL FAIR COVER "GRASS"	B	0.44	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	0.67	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	1.06	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 6.08 SUBAREA RUNOFF (CFS) = 3.61

EFFECTIVE AREA (ACRES) = 2544.64 AREA-AVERAGED Fm (INCH/HR) = 0.28

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA (ACRES) = 3802.3 PEAK FLOW RATE (CFS) = 1651.13

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<

MAINLINE Tc (MIN.) = 48.67

\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.960

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	2.16	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	2.45	0.30	1.000	66
NATURAL FAIR COVER					

"OPEN BRUSH"	B	6.15	0.30	1.000	66
AGRICULTURAL POOR COVER "ROW CROPS, STRAIGHT ROW"	B	1.34	0.30	1.000	81
AGRICULTURAL POOR COVER "ROW CROPS, STRAIGHT ROW"	B	18.46	0.30	1.000	81
AGRICULTURAL POOR COVER "ROW CROPS, STRAIGHT ROW"	B	4.13	0.30	1.000	81

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 34.69 SUBAREA RUNOFF (CFS) = 20.59  
EFFECTIVE AREA (ACRES) = 2579.33 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA (ACRES) = 3837.0 PEAK FLOW RATE (CFS) = 1651.13  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<

MAINLINE Tc (MIN.) = 48.67

\* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.960

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "ROW CROPS, STRAIGHT ROW"	B	8.69	0.30	1.000	81
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.73	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.41	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND, GRASS"	B	1.37	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND, GRASS"	B	3.11	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 14.31 SUBAREA RUNOFF (CFS) = 8.49

EFFECTIVE AREA (ACRES) = 2593.64 AREA-AVERAGED Fm (INCH/HR) = 0.28

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA (ACRES) = 3851.3 PEAK FLOW RATE (CFS) = 1651.13

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13683.00 TO NODE 13685.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 208.53 DOWNSTREAM (FEET) = 194.24  
CHANNEL LENGTH THRU SUBAREA (FEET) = 289.01 CHANNEL SLOPE = 0.0494  
GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 2.92  
CHANNEL FLOW THRU SUBAREA (CFS) = 1651.13  
FLOW VELOCITY (FEET/SEC.) = 14.56 FLOW DEPTH (FEET) = 2.92  
TRAVEL TIME (MIN.) = 0.33 Tc (MIN.) = 49.00  
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13685.00 = 39866.53 FEET.



\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1521.80	26.80	1.332	0.30 ( 0.27)	0.90	1432.5	110.00
2	1573.72	29.22	1.265	0.30 ( 0.27)	0.90	1588.6	100.00
3	1590.73	30.61	1.233	0.30 ( 0.27)	0.90	1669.7	100.00
4	1600.63	33.91	1.172	0.30 ( 0.27)	0.91	1841.9	130.00
5	1651.13	49.00	0.956	0.30 ( 0.28)	0.93	2593.6	20100.00
6	1611.81	55.42	0.896	0.30 ( 0.28)	0.93	2788.8	13600.00
7	1408.16	95.98	0.690	0.30 ( 0.28)	0.93	3780.9	13510.00
8	1318.82	107.10	0.659	0.30 ( 0.28)	0.93	3851.3	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 1651.13 Tc(MIN.) = 49.00  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 2593.64

\*\*\*\*\*

FLOW PROCESS FROM NODE 13685.00 TO NODE 13410.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 194.24 DOWNSTREAM(FEET) = 178.72  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1843.57 CHANNEL SLOPE = 0.0084  
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 4.75  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.918

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.23	0.30	1.000	-
USER-DEFINED	-	1.52	0.30	1.000	-
USER-DEFINED	-	0.06	0.30	1.000	-
USER-DEFINED	-	0.13	0.30	1.000	-
USER-DEFINED	-	6.45	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1653.46  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.87  
 AVERAGE FLOW DEPTH(FEET) = 4.75 TRAVEL TIME(MIN.) = 3.91  
 Tc(MIN.) = 52.91  
 SUBAREA AREA(ACRES) = 8.39 SUBAREA RUNOFF(CFS) = 4.67  
 EFFECTIVE AREA(ACRES) = 2602.03 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 3859.7 PEAK FLOW RATE(CFS) = 1651.13  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 4.75

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 4.75 FLOW VELOCITY(FEET/SEC.) = 7.86  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13410.00 = 41710.10 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	--------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	1521.80	30.81	1.229	0.30 ( 0.27)	0.90	1440.9
2	1573.72	33.19	1.186	0.30 ( 0.27)	0.90	1597.0
3	1590.73	34.56	1.161	0.30 ( 0.27)	0.90	1678.1
4	1600.63	37.85	1.100	0.30 ( 0.27)	0.91	1850.3
5	1651.13	52.91	0.918	0.30 ( 0.28)	0.93	2602.0
6	1611.81	59.35	0.861	0.30 ( 0.28)	0.93	2797.2
7	1408.16	100.08	0.678	0.30 ( 0.28)	0.93	3789.3
8	1318.82	111.28	0.647	0.30 ( 0.28)	0.93	3859.7

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 1651.13 Tc(MIN.) = 52.91  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 2602.03

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 3859.7 TC(MIN.) = 52.91  
 EFFECTIVE AREA(ACRES) = 2602.03 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.927  
 PEAK FLOW RATE(CFS) = 1651.13

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1521.80	30.81	1.229	0.30 ( 0.27)	0.90	1440.9	110.00
2	1573.72	33.19	1.186	0.30 ( 0.27)	0.90	1597.0	100.00
3	1590.73	34.56	1.161	0.30 ( 0.27)	0.90	1678.1	100.00
4	1600.63	37.85	1.100	0.30 ( 0.27)	0.91	1850.3	130.00
5	1651.13	52.91	0.918	0.30 ( 0.28)	0.93	2602.0	20100.00
6	1611.81	59.35	0.861	0.30 ( 0.28)	0.93	2797.2	13600.00
7	1408.16	100.08	0.678	0.30 ( 0.28)	0.93	3789.3	13510.00
8	1318.82	111.28	0.647	0.30 ( 0.28)	0.93	3859.7	13500.00

END OF RATIONAL METHOD ANALYSIS



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S37- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 10-YR RM EV APRIL 2019 CCHIU \*  
\*\*\*\*\*

FILE NAME: RI10EV37.DAT  
TIME/DATE OF STUDY: 10:16 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 10.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 3.709
- 2) 10.00; 2.481
- 3) 15.00; 1.848
- 4) 20.00; 1.580
- 5) 25.00; 1.381
- 6) 30.00; 1.243
- 7) 40.00; 1.060
- 8) 50.00; 0.942
- 9) 60.00; 0.854
- 10) 90.00; 0.706
- 11) 120.00; 0.620
- 12) 180.00; 0.519
- 13) 360.00; 0.379
- 14) 1200.00; 0.165

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI10EV34.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15908.55	19.80	0.30 ( 0.25)	0.82	4668.3	300.00
2	17739.40	27.12	0.30 ( 0.24)	0.81	6887.7	410.00
3	19328.06	35.01	0.30 ( 0.24)	0.82	9330.4	100.00
4	21005.43	44.56	0.30 ( 0.25)	0.83	13069.8	150.00
5	23471.18	60.91	0.30 ( 0.26)	0.86	19994.7	390.00
6	24906.22	75.63	0.30 ( 0.27)	0.88	26622.4	13100.00
7	25248.12	82.53	0.30 ( 0.27)	0.89	29236.5	11801.00
8	26656.45	100.48	0.30 ( 0.27)	0.91	37777.4	13510.00
9	27343.21	107.57	0.30 ( 0.28)	0.92	41769.9	13010.00
10	28089.53	113.52	0.30 ( 0.28)	0.92	45444.9	11330.00
11	28676.05	121.62	0.30 ( 0.28)	0.93	50532.0	10630.00
12	28421.22	127.23	0.30 ( 0.28)	0.93	53121.9	12330.00
13	28159.54	133.87	0.30 ( 0.28)	0.94	56264.4	11600.00
14	27778.78	139.67	0.30 ( 0.28)	0.94	58498.7	11111.00
15	27359.83	145.84	0.30 ( 0.28)	0.94	60432.5	12201.00
16	26439.31	154.86	0.30 ( 0.28)	0.94	62520.8	12231.00
17	25597.62	162.44	0.30 ( 0.28)	0.94	63932.3	10400.00
18	24255.38	174.00	0.30 ( 0.28)	0.94	65553.1	10320.00
19	22982.32	183.88	0.30 ( 0.28)	0.94	65940.9	12000.00
20	20034.88	213.50	0.30 ( 0.28)	0.95	66557.9	10100.00
TOTAL AREA (ACRES) =						66557.9

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 3 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15908.55	19.80	0.30 ( 0.25)	0.82	4668.3	300.00
2	17739.40	27.12	0.30 ( 0.24)	0.81	6887.7	410.00
3	19328.06	35.01	0.30 ( 0.24)	0.82	9330.4	100.00
4	21005.43	44.56	0.30 ( 0.25)	0.83	13069.8	150.00
5	23471.18	60.91	0.30 ( 0.26)	0.86	19994.7	390.00
6	24906.22	75.63	0.30 ( 0.27)	0.88	26622.4	13100.00
7	25248.12	82.53	0.30 ( 0.27)	0.89	29236.5	11801.00
8	26656.45	100.48	0.30 ( 0.27)	0.91	37777.4	13510.00
9	27343.21	107.57	0.30 ( 0.28)	0.92	41769.9	13010.00
10	28089.53	113.52	0.30 ( 0.28)	0.92	45444.9	11330.00
11	28676.05	121.62	0.30 ( 0.28)	0.93	50532.0	10630.00
12	28421.22	127.23	0.30 ( 0.28)	0.93	53121.9	12330.00
13	28159.54	133.87	0.30 ( 0.28)	0.94	56264.4	11600.00

14 27778.78 139.67 0.30( 0.28) 0.94 58498.7 11111.00  
 15 27359.83 145.84 0.30( 0.28) 0.94 60432.5 12201.00  
 16 26439.31 154.86 0.30( 0.28) 0.94 62520.8 12231.00  
 17 25597.62 162.44 0.30( 0.28) 0.94 63932.3 10400.00  
 18 24255.38 174.00 0.30( 0.28) 0.94 65553.1 10320.00  
 19 22982.32 183.88 0.30( 0.28) 0.94 65940.9 12000.00  
 20 20034.88 213.50 0.30( 0.28) 0.95 66557.9 10100.00  
 TOTAL AREA(ACRES) = 66557.9

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13700.00 TO NODE 13720.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM( FEET ) = 170.00 DOWNSTREAM( FEET ) = 165.51  
 CHANNEL LENGTH THRU SUBAREA( FEET ) = 1891.83 CHANNEL SLOPE = 0.0024  
 GIVEN CHANNEL BASE( FEET ) = 200.00 CHANNEL FREEBOARD( FEET ) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT( FEET ) = 10.88  
 CHANNEL FLOW THRU SUBAREA( CFS ) = 28676.05  
 FLOW VELOCITY( FEET/SEC. ) = 10.36 FLOW DEPTH( FEET ) = 10.88  
 TRAVEL TIME( MIN. ) = 3.04 Tc( MIN. ) = 124.67  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126443.80 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15908.55	23.49	1.441	0.30( 0.25)	0.82	4668.3	300.00
2	17739.40	30.67	1.231	0.30( 0.24)	0.81	6887.7	410.00
3	19328.06	38.47	1.088	0.30( 0.24)	0.82	9330.4	100.00
4	21005.43	47.93	0.966	0.30( 0.25)	0.83	13069.8	150.00
5	23471.18	64.16	0.833	0.30( 0.26)	0.86	19994.7	390.00
6	24906.22	78.81	0.761	0.30( 0.27)	0.88	26622.4	13100.00
7	25248.12	85.70	0.727	0.30( 0.27)	0.89	29236.5	11801.00
8	26656.45	103.59	0.667	0.30( 0.27)	0.91	37777.4	13510.00
9	27343.21	110.66	0.647	0.30( 0.28)	0.92	41769.9	13010.00
10	28089.53	116.58	0.630	0.30( 0.28)	0.92	45444.9	11330.00
11	28676.05	124.67	0.612	0.30( 0.28)	0.93	50532.0	10630.00
12	28421.22	130.28	0.603	0.30( 0.28)	0.93	53121.9	12330.00
13	28159.54	136.93	0.592	0.30( 0.28)	0.94	56264.4	11600.00
14	27778.78	142.75	0.582	0.30( 0.28)	0.94	58498.7	11111.00
15	27359.83	148.93	0.571	0.30( 0.28)	0.94	60432.5	12201.00
16	26439.31	157.99	0.556	0.30( 0.28)	0.94	62520.8	12231.00
17	25597.62	165.59	0.543	0.30( 0.28)	0.94	63932.3	10400.00
18	24255.38	177.21	0.524	0.30( 0.28)	0.94	65553.1	10320.00
19	22982.32	187.15	0.513	0.30( 0.28)	0.94	65940.9	12000.00
20	20034.88	216.92	0.490	0.30( 0.28)	0.95	66557.9	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE( CFS ) = 28676.05 Tc( MIN. ) = 124.67  
 AREA-AVERAGED Fm( INCH/HR ) = 0.28 AREA-AVERAGED Fp( INCH/HR ) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA( ACRES ) = 50532.04

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13700.00 TO NODE 13720.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13720.00 TO NODE 13720.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 0506102E.DNA  
 MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	239.83	16.06	0.30( 0.29)	0.96	193.8	10230.00
2	217.18	25.14	0.30( 0.29)	0.95	240.5	10250.00
3	216.13	25.45	0.30( 0.29)	0.95	241.8	10200.00
4	200.96	29.41	0.30( 0.29)	0.95	246.3	10220.00

TOTAL AREA( ACRES ) = 246.3

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13720.00 TO NODE 13720.00 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15908.55	23.49	1.441	0.30( 0.25)	0.82	4668.3	300.00
2	17739.40	30.67	1.231	0.30( 0.24)	0.81	6887.7	410.00
3	19328.06	38.47	1.088	0.30( 0.24)	0.82	9330.4	100.00
4	21005.43	47.93	0.966	0.30( 0.25)	0.83	13069.8	150.00
5	23471.18	64.16	0.833	0.30( 0.26)	0.86	19994.7	390.00
6	24906.22	78.81	0.761	0.30( 0.27)	0.88	26622.4	13100.00
7	25248.12	85.70	0.727	0.30( 0.27)	0.89	29236.5	11801.00
8	26656.45	103.59	0.667	0.30( 0.27)	0.91	37777.4	13510.00
9	27343.21	110.66	0.647	0.30( 0.28)	0.92	41769.9	13010.00
10	28089.53	116.58	0.630	0.30( 0.28)	0.92	45444.9	11330.00
11	28676.05	124.67	0.612	0.30( 0.28)	0.93	50532.0	10630.00
12	28421.22	130.28	0.603	0.30( 0.28)	0.93	53121.9	12330.00
13	28159.54	136.93	0.592	0.30( 0.28)	0.94	56264.4	11600.00
14	27778.78	142.75	0.582	0.30( 0.28)	0.94	58498.7	11111.00
15	27359.83	148.93	0.571	0.30( 0.28)	0.94	60432.5	12201.00
16	26439.31	157.99	0.556	0.30( 0.28)	0.94	62520.8	12231.00
17	25597.62	165.59	0.543	0.30( 0.28)	0.94	63932.3	10400.00
18	24255.38	177.21	0.524	0.30( 0.28)	0.94	65553.1	10320.00
19	22982.32	187.15	0.513	0.30( 0.28)	0.94	65940.9	12000.00
20	20034.88	216.92	0.490	0.30( 0.28)	0.95	66557.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126443.80 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	239.83	16.06	1.791	0.30( 0.29)	0.96	193.8	10230.00
2	217.18	25.14	1.377	0.30( 0.29)	0.95	240.5	10250.00
3	216.13	25.45	1.369	0.30( 0.29)	0.95	241.8	10200.00
4	200.96	29.41	1.259	0.30( 0.29)	0.95	246.3	10220.00

LONGEST FLOWPATH FROM NODE 10200.00 TO NODE 13720.00 = 9099.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	--------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	14303.00	16.06	1.791	0.30 ( 0.25)	0.83	3386.7 10230.00
2	16129.86	23.49	1.441	0.30 ( 0.25)	0.82	4900.3 300.00
3	16547.39	25.14	1.377	0.30 ( 0.25)	0.82	5420.0 10250.00
4	16625.16	25.45	1.369	0.30 ( 0.25)	0.82	5516.8 10200.00
5	17618.98	29.41	1.259	0.30 ( 0.25)	0.82	6744.4 10220.00
6	17934.47	30.67	1.231	0.30 ( 0.25)	0.82	7134.0 410.00
7	19493.67	38.47	1.088	0.30 ( 0.25)	0.82	9576.6 100.00
8	21145.94	47.93	0.966	0.30 ( 0.25)	0.83	13316.0 150.00
9	23584.22	64.16	0.833	0.30 ( 0.26)	0.86	20241.0 390.00
10	25004.34	78.81	0.761	0.30 ( 0.27)	0.89	26868.6 13100.00
11	25339.22	85.70	0.727	0.30 ( 0.27)	0.89	29482.7 11801.00
12	26735.12	103.59	0.667	0.30 ( 0.27)	0.91	38023.6 13510.00
13	27417.70	110.66	0.647	0.30 ( 0.28)	0.92	42016.2 13010.00
14	28160.51	116.58	0.630	0.30 ( 0.28)	0.92	45691.2 11330.00
15	28743.39	124.67	0.612	0.30 ( 0.28)	0.93	50778.3 10630.00
16	28486.61	130.28	0.603	0.30 ( 0.28)	0.93	53368.2 12330.00
17	28222.62	136.93	0.592	0.30 ( 0.28)	0.94	56510.6 11600.00
18	27839.83	142.75	0.582	0.30 ( 0.28)	0.94	58744.9 11111.00
19	27418.74	148.93	0.571	0.30 ( 0.28)	0.94	60678.8 12201.00
20	26495.06	157.99	0.556	0.30 ( 0.28)	0.94	62767.0 12231.00
21	25650.73	165.59	0.543	0.30 ( 0.28)	0.94	64178.6 10400.00
22	24304.46	177.21	0.524	0.30 ( 0.28)	0.94	65799.4 10320.00
23	23029.27	187.15	0.513	0.30 ( 0.28)	0.94	66187.2 12000.00
24	20077.05	216.92	0.490	0.30 ( 0.28)	0.95	66804.2 10100.00

TOTAL AREA (ACRES) = 66804.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 28743.39 Tc(MIN.) = 124.666  
EFFECTIVE AREA(ACRES) = 50778.30 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.89  
TOTAL AREA(ACRES) = 66804.2  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126443.80 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13720.00 TO NODE 13740.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 165.51 DOWNSTREAM(FEET) = 161.03  
CHANNEL LENGTH THRU SUBAREA(FEET) = 2067.54 CHANNEL SLOPE = 0.0022  
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 11.17  
CHANNEL FLOW THRU SUBAREA(CFS) = 28743.39  
FLOW VELOCITY(FEET/SEC.) = 10.05 FLOW DEPTH(FEET) = 11.17  
TRAVEL TIME(MIN.) = 3.43 Tc(MIN.) = 128.09  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128511.34 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14303.00	20.37	1.565	0.30 ( 0.25)	0.83	3386.7	10230.00
2	16129.86	27.63	1.308	0.30 ( 0.25)	0.82	4900.3	300.00
3	16547.39	29.25	1.264	0.30 ( 0.25)	0.82	5420.0	10250.00
4	16625.16	29.55	1.255	0.30 ( 0.25)	0.82	5516.8	10200.00
5	17618.98	33.43	1.180	0.30 ( 0.25)	0.82	6744.4	10220.00

6	17934.47	34.67	1.158	0.30 ( 0.25)	0.82	7134.0	410.00
7	19493.67	42.35	1.032	0.30 ( 0.25)	0.82	9576.6	100.00
8	21145.94	51.71	0.927	0.30 ( 0.25)	0.83	13316.0	150.00
9	23584.22	67.81	0.815	0.30 ( 0.26)	0.86	20241.0	390.00
10	25004.34	82.40	0.744	0.30 ( 0.27)	0.89	26868.6	13100.00
11	25339.22	89.27	0.710	0.30 ( 0.27)	0.89	29482.7	11801.00
12	26735.12	107.10	0.657	0.30 ( 0.27)	0.91	38023.6	13510.00
13	27417.70	114.14	0.637	0.30 ( 0.28)	0.92	42016.2	13010.00
14	28160.51	120.03	0.620	0.30 ( 0.28)	0.92	45691.2	11330.00
15	28743.39	128.09	0.606	0.30 ( 0.28)	0.93	50778.3	10630.00
16	28486.61	133.72	0.597	0.30 ( 0.28)	0.93	53368.2	12330.00
17	28222.62	140.37	0.586	0.30 ( 0.28)	0.94	56510.6	11600.00
18	27839.83	146.21	0.576	0.30 ( 0.28)	0.94	58744.9	11111.00
19	27418.74	152.41	0.565	0.30 ( 0.28)	0.94	60678.8	12201.00
20	26495.06	161.50	0.550	0.30 ( 0.28)	0.94	62767.0	12231.00
21	25650.73	169.15	0.537	0.30 ( 0.28)	0.94	64178.6	10400.00
22	24304.46	180.83	0.518	0.30 ( 0.28)	0.94	65799.4	10320.00
23	23029.27	190.83	0.511	0.30 ( 0.28)	0.94	66187.2	12000.00
24	20077.05	220.77	0.487	0.30 ( 0.28)	0.95	66804.2	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 28743.39 Tc(MIN.) = 128.09  
AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 50778.30

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13720.00 TO NODE 13740.00 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13740.00 TO NODE 13740.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506103E.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	489.59	19.32	0.30 ( 0.23)	0.76	401.6	10300.00
2	490.14	20.03	0.30 ( 0.23)	0.76	412.9	10380.00
3	480.40	22.78	0.30 ( 0.23)	0.76	441.7	10320.00
4	464.91	24.67	0.30 ( 0.23)	0.76	451.8	10360.00
5	436.74	27.62	0.30 ( 0.23)	0.76	460.8	10340.00

TOTAL AREA(ACRES) = 460.8

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13740.00 TO NODE 13740.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14303.00	20.37	1.565	0.30 ( 0.25)	0.83	3386.7	10230.00
2	16129.86	27.63	1.308	0.30 ( 0.25)	0.82	4900.3	300.00
3	16547.39	29.25	1.264	0.30 ( 0.25)	0.82	5420.0	10250.00

4	16625.16	29.55	1.255	0.30 ( 0.25)	0.82	5516.8	10200.00
5	17618.98	33.43	1.180	0.30 ( 0.25)	0.82	6744.4	10220.00
6	17934.47	34.67	1.158	0.30 ( 0.25)	0.82	7134.0	410.00
7	19493.67	42.35	1.032	0.30 ( 0.25)	0.82	9576.6	100.00
8	21145.94	51.71	0.927	0.30 ( 0.25)	0.83	13316.0	150.00
9	23584.22	67.81	0.815	0.30 ( 0.26)	0.86	20241.0	390.00
10	25004.34	82.40	0.744	0.30 ( 0.27)	0.89	26868.6	13100.00
11	25339.22	89.27	0.710	0.30 ( 0.27)	0.89	29482.7	11801.00
12	26735.12	107.10	0.657	0.30 ( 0.27)	0.91	38023.6	13510.00
13	27417.70	114.14	0.637	0.30 ( 0.28)	0.92	42016.2	13010.00
14	28160.51	120.03	0.620	0.30 ( 0.28)	0.92	45691.2	11330.00
15	28743.39	128.09	0.606	0.30 ( 0.28)	0.93	50778.3	10630.00
16	28486.61	133.72	0.597	0.30 ( 0.28)	0.93	53368.2	12330.00
17	28222.62	140.37	0.586	0.30 ( 0.28)	0.94	56510.6	11600.00
18	27839.83	146.21	0.576	0.30 ( 0.28)	0.94	58744.9	11111.00
19	27418.74	152.41	0.565	0.30 ( 0.28)	0.94	60678.8	12201.00
20	26495.06	161.50	0.550	0.30 ( 0.28)	0.94	62767.0	12231.00
21	25650.73	169.15	0.537	0.30 ( 0.28)	0.94	64178.6	10400.00
22	24304.46	180.83	0.518	0.30 ( 0.28)	0.94	65799.4	10320.00
23	23029.27	190.83	0.511	0.30 ( 0.28)	0.94	66187.2	12000.00
24	20077.05	220.77	0.487	0.30 ( 0.28)	0.95	66804.2	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128511.34 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	489.59	19.32	1.617	0.30 ( 0.23)	0.76	401.6	10300.00
2	490.14	20.03	1.579	0.30 ( 0.23)	0.76	412.9	10380.00
3	480.40	22.78	1.469	0.30 ( 0.23)	0.76	441.7	10320.00
4	464.91	24.67	1.394	0.30 ( 0.23)	0.76	451.8	10360.00
5	436.74	27.62	1.309	0.30 ( 0.23)	0.76	460.8	10340.00

LONGEST FLOWPATH FROM NODE 10320.00 TO NODE 13740.00 = 8457.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14581.04	19.32	1.617	0.30 ( 0.25)	0.82	3612.8	10300.00
2	14698.86	20.03	1.579	0.30 ( 0.25)	0.82	3743.0	10380.00
3	14791.94	20.37	1.565	0.30 ( 0.25)	0.82	3803.1	10230.00
4	15389.35	22.78	1.469	0.30 ( 0.25)	0.82	4330.4	10320.00
5	15849.95	24.67	1.394	0.30 ( 0.25)	0.82	4735.0	10360.00
6	16564.93	27.62	1.309	0.30 ( 0.25)	0.82	5359.7	10340.00
7	16566.52	27.63	1.308	0.30 ( 0.25)	0.82	5361.1	300.00
8	16965.96	29.25	1.264	0.30 ( 0.25)	0.82	5880.8	10250.00
9	17040.38	29.55	1.255	0.30 ( 0.25)	0.82	5977.6	10200.00
10	18003.74	33.43	1.180	0.30 ( 0.24)	0.82	7205.2	10220.00
11	18310.08	34.67	1.158	0.30 ( 0.24)	0.82	7594.8	410.00
12	19818.57	42.35	1.032	0.30 ( 0.24)	0.82	10037.4	100.00
13	21428.26	51.71	0.927	0.30 ( 0.25)	0.83	13776.8	150.00
14	23821.45	67.81	0.815	0.30 ( 0.26)	0.86	20701.8	390.00
15	25212.45	82.40	0.744	0.30 ( 0.26)	0.88	27329.4	13100.00
16	25533.61	89.27	0.710	0.30 ( 0.27)	0.89	29943.5	11801.00
17	26908.23	107.10	0.657	0.30 ( 0.27)	0.91	38484.4	13510.00
18	27582.65	114.14	0.637	0.30 ( 0.27)	0.92	42477.0	13010.00
19	28318.64	120.03	0.620	0.30 ( 0.28)	0.92	46152.0	11330.00
20	28896.03	128.09	0.606	0.30 ( 0.28)	0.93	51239.1	10630.00
21	28635.42	133.72	0.597	0.30 ( 0.28)	0.93	53829.0	12330.00
22	28366.89	140.37	0.586	0.30 ( 0.28)	0.94	56971.4	11600.00

23	27980.13	146.21	0.576	0.30 ( 0.28)	0.94	59205.7	11111.00
24	27554.82	152.41	0.565	0.30 ( 0.28)	0.94	61139.6	12201.00
25	26624.95	161.50	0.550	0.30 ( 0.28)	0.94	63227.8	12231.00
26	25775.41	169.15	0.537	0.30 ( 0.28)	0.94	64639.4	10400.00
27	24421.49	180.83	0.518	0.30 ( 0.28)	0.94	66260.1	10320.00
28	23143.16	190.83	0.511	0.30 ( 0.28)	0.94	66648.0	12000.00
29	20181.51	220.77	0.487	0.30 ( 0.28)	0.94	67265.0	10100.00

TOTAL AREA (ACRES) = 67265.0

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 28896.03 Tc (MIN.) = 128.094  
EFFECTIVE AREA (ACRES) = 51239.10 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.88  
TOTAL AREA (ACRES) = 67265.0  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128511.34 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13740.00 TO NODE 13741.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 161.03 DOWNSTREAM (FEET) = 141.00

CHANNEL LENGTH THRU SUBAREA (FEET) = 364.08 CHANNEL SLOPE = 0.0550

GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT (FEET) = 6.48

CHANNEL FLOW THRU SUBAREA (CFS) = 28896.03

FLOW VELOCITY (FEET/SEC.) = 35.40 FLOW DEPTH (FEET) = 6.48

TRAVEL TIME (MIN.) = 0.17 Tc (MIN.) = 128.26

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128875.41 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14581.04	19.53	1.605	0.30 ( 0.25)	0.82	3612.8	10300.00
2	14698.86	20.25	1.570	0.30 ( 0.25)	0.82	3743.0	10380.00
3	14791.94	20.59	1.557	0.30 ( 0.25)	0.82	3803.1	10230.00
4	15389.35	22.99	1.461	0.30 ( 0.25)	0.82	4330.4	10320.00
5	15849.95	24.88	1.386	0.30 ( 0.25)	0.82	4735.0	10360.00
6	16564.93	27.83	1.303	0.30 ( 0.25)	0.82	5359.7	10340.00
7	16566.52	27.83	1.303	0.30 ( 0.25)	0.82	5361.1	300.00
8	16965.96	29.45	1.258	0.30 ( 0.25)	0.82	5880.8	10250.00
9	17040.38	29.75	1.250	0.30 ( 0.25)	0.82	5977.6	10200.00
10	18003.74	33.63	1.177	0.30 ( 0.24)	0.82	7205.2	10220.00
11	18310.08	34.87	1.154	0.30 ( 0.24)	0.82	7594.8	410.00
12	19818.57	42.55	1.030	0.30 ( 0.24)	0.82	10037.4	100.00
13	21428.26	51.90	0.925	0.30 ( 0.25)	0.83	13776.8	150.00
14	23821.45	67.99	0.815	0.30 ( 0.26)	0.86	20701.8	390.00
15	25212.45	82.58	0.743	0.30 ( 0.26)	0.88	27329.4	13100.00
16	25533.61	89.45	0.709	0.30 ( 0.27)	0.89	29943.5	11801.00
17	26908.23	107.27	0.656	0.30 ( 0.27)	0.91	38484.4	13510.00
18	27582.65	114.31	0.636	0.30 ( 0.27)	0.92	42477.0	13010.00
19	28318.64	120.20	0.620	0.30 ( 0.28)	0.92	46152.0	11330.00
20	28896.03	128.26	0.606	0.30 ( 0.28)	0.93	51239.1	10630.00
21	28635.42	133.89	0.597	0.30 ( 0.28)	0.93	53829.0	12330.00
22	28366.89	140.55	0.585	0.30 ( 0.28)	0.94	56971.4	11600.00
23	27980.13	146.38	0.576	0.30 ( 0.28)	0.94	59205.7	11111.00

24	27554.82	152.58	0.565	0.30 ( 0.28)	0.94	61139.6	12201.00
25	26624.95	161.68	0.550	0.30 ( 0.28)	0.94	63227.8	12231.00
26	25775.41	169.33	0.537	0.30 ( 0.28)	0.94	64639.4	10400.00
27	24421.49	181.01	0.518	0.30 ( 0.28)	0.94	66260.1	10320.00
28	23143.16	191.02	0.510	0.30 ( 0.28)	0.94	66648.0	12000.00
29	20181.51	220.96	0.487	0.30 ( 0.28)	0.94	67265.0	10100.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE(CFS) = 28896.03 Tc(MIN.) = 128.26  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 51239.10

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13740.00 TO NODE 13741.00 IS CODE = 12  
 -----  
 >>>>CLEAR MEMORY BANK # 3 <<<<<<  
 =====

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13741.00 TO NODE 13741.00 IS CODE = 15.1  
 -----  
 >>>>DEFINE MEMORY BANK # 3 <<<<<<  
 =====

PEAK FLOWRATE TABLE FILE NAME: 0506104E.DNA  
 MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	49.20	20.74	1.551	0.30 ( 0.24)	0.80	44.3	10400.00
TOTAL AREA(ACRES) =							44.3

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13741.00 TO NODE 13741.00 IS CODE = 11  
 -----  
 >>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<<  
 =====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14581.04	19.53	1.605	0.30 ( 0.25)	0.82	3612.8	10300.00
2	14698.86	20.25	1.570	0.30 ( 0.25)	0.82	3743.0	10380.00
3	14791.94	20.59	1.557	0.30 ( 0.25)	0.82	3803.1	10230.00
4	15389.35	22.99	1.461	0.30 ( 0.25)	0.82	4330.4	10320.00
5	15849.95	24.88	1.386	0.30 ( 0.25)	0.82	4735.0	10360.00
6	16564.93	27.83	1.303	0.30 ( 0.25)	0.82	5359.7	10340.00
7	16566.52	27.83	1.303	0.30 ( 0.25)	0.82	5361.1	300.00
8	16965.96	29.45	1.258	0.30 ( 0.25)	0.82	5880.8	10250.00
9	17040.38	29.75	1.250	0.30 ( 0.25)	0.82	5977.6	10200.00
10	18003.74	33.63	1.177	0.30 ( 0.24)	0.82	7205.2	10220.00
11	18310.08	34.87	1.154	0.30 ( 0.24)	0.82	7594.8	410.00
12	19818.57	42.55	1.030	0.30 ( 0.24)	0.82	10037.4	100.00
13	21428.26	51.90	0.925	0.30 ( 0.25)	0.83	13776.8	150.00
14	23821.45	67.99	0.815	0.30 ( 0.26)	0.86	20701.8	390.00
15	25212.45	82.58	0.743	0.30 ( 0.26)	0.88	27329.4	13100.00
16	25533.61	89.45	0.709	0.30 ( 0.27)	0.89	29943.5	11801.00
17	26908.23	107.27	0.656	0.30 ( 0.27)	0.91	38484.4	13510.00
18	27582.65	114.31	0.636	0.30 ( 0.27)	0.92	42477.0	13010.00
19	28318.64	120.20	0.620	0.30 ( 0.28)	0.92	46152.0	11330.00
20	28896.03	128.26	0.606	0.30 ( 0.28)	0.93	51239.1	10630.00

21	28635.42	133.89	0.597	0.30 ( 0.28)	0.93	53829.0	12330.00
22	28366.89	140.55	0.585	0.30 ( 0.28)	0.94	56971.4	11600.00
23	27980.13	146.38	0.576	0.30 ( 0.28)	0.94	59205.7	11111.00
24	27554.82	152.58	0.565	0.30 ( 0.28)	0.94	61139.6	12201.00
25	26624.95	161.68	0.550	0.30 ( 0.28)	0.94	63227.8	12231.00
26	25775.41	169.33	0.537	0.30 ( 0.28)	0.94	64639.4	10400.00
27	24421.49	181.01	0.518	0.30 ( 0.28)	0.94	66260.1	10320.00
28	23143.16	191.02	0.510	0.30 ( 0.28)	0.94	66648.0	12000.00
29	20181.51	220.96	0.487	0.30 ( 0.28)	0.94	67265.0	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128875.41 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*  
 STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER  
 NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE  
 1 49.20 20.74 1.551 0.30 ( 0.24) 0.80 44.3 10400.00  
 LONGEST FLOWPATH FROM NODE 10400.00 TO NODE 13741.00 = 6237.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	14629.31	19.53	1.605	0.30 ( 0.25)	0.82	3654.5	10300.00
2	14747.62	20.25	1.570	0.30 ( 0.25)	0.82	3786.3	10380.00
3	14841.01	20.59	1.557	0.30 ( 0.25)	0.82	3847.1	10230.00
4	14878.00	20.74	1.551	0.30 ( 0.25)	0.82	3880.0	10400.00
5	15435.19	22.99	1.461	0.30 ( 0.25)	0.82	4374.7	10320.00
6	15892.97	24.88	1.386	0.30 ( 0.25)	0.82	4779.3	10360.00
7	16604.83	27.83	1.303	0.30 ( 0.25)	0.82	5404.0	10340.00
8	16606.42	27.83	1.303	0.30 ( 0.25)	0.82	5405.4	300.00
9	17004.18	29.45	1.258	0.30 ( 0.25)	0.82	5925.1	10250.00
10	17078.29	29.75	1.250	0.30 ( 0.25)	0.82	6021.9	10200.00
11	18038.90	33.63	1.177	0.30 ( 0.24)	0.82	7249.5	10220.00
12	18344.39	34.87	1.154	0.30 ( 0.24)	0.82	7639.1	410.00
13	19848.23	42.55	1.030	0.30 ( 0.24)	0.82	10081.7	100.00
14	21453.99	51.90	0.925	0.30 ( 0.25)	0.83	13821.1	150.00
15	23843.03	67.99	0.815	0.30 ( 0.26)	0.86	20746.1	390.00
16	25231.32	82.58	0.743	0.30 ( 0.26)	0.88	27373.7	13100.00
17	25551.22	89.45	0.709	0.30 ( 0.27)	0.89	29987.8	11801.00
18	26923.88	107.27	0.656	0.30 ( 0.27)	0.91	38528.7	13510.00
19	27597.54	114.31	0.636	0.30 ( 0.27)	0.92	42521.3	13010.00
20	28332.90	120.20	0.620	0.30 ( 0.28)	0.92	46196.3	11330.00
21	28909.78	128.26	0.606	0.30 ( 0.28)	0.93	51283.4	10630.00
22	28648.82	133.89	0.597	0.30 ( 0.28)	0.93	53873.3	12330.00
23	28379.87	140.55	0.585	0.30 ( 0.28)	0.94	57015.7	11600.00
24	27992.75	146.38	0.576	0.30 ( 0.28)	0.94	59250.0	11111.00
25	27567.04	152.58	0.565	0.30 ( 0.28)	0.94	61183.9	12201.00
26	26636.60	161.68	0.550	0.30 ( 0.28)	0.94	63272.1	12231.00
27	25786.57	169.33	0.537	0.30 ( 0.28)	0.94	64683.7	10400.00
28	24431.95	181.01	0.518	0.30 ( 0.28)	0.94	66304.4	10320.00
29	23153.33	191.02	0.510	0.30 ( 0.28)	0.94	66692.3	12000.00
30	20190.81	220.96	0.487	0.30 ( 0.28)	0.94	67309.3	10100.00
TOTAL AREA(ACRES) =							67309.3

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:  
 PEAK FLOW RATE(CFS) = 28909.78 Tc(MIN.) = 128.265  
 EFFECTIVE AREA(ACRES) = 51283.40 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 67309.3  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128875.41 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13741.00 TO NODE 13802.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM( FEET ) = 141.00 DOWNSTREAM( FEET ) = 135.00
CHANNEL LENGTH THRU SUBAREA( FEET ) = 1533.41 CHANNEL SLOPE = 0.0039
GIVEN CHANNEL BASE( FEET ) = 100.00 CHANNEL FREEBOARD( FEET ) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
\*ESTIMATED CHANNEL HEIGHT( FEET ) = 13.34
CHANNEL FLOW THRU SUBAREA( CFS ) = 28909.78
FLOW VELOCITY( FEET/SEC. ) = 14.13 FLOW DEPTH( FEET ) = 13.34
TRAVEL TIME( MIN. ) = 1.81 Tc( MIN. ) = 130.07
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130408.82 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 30 rows of data.

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE( CFS ) = 28909.78 Tc( MIN. ) = 130.07
AREA-AVERAGED Fm( INCH/HR ) = 0.28 AREA-AVERAGED Fp( INCH/HR ) = 0.30
AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA( ACRES ) = 51283.40

\*\*\*\*\*

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<

PEAK FLOWRATE TABLE FILE NAME: 0506105L.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 2 rows of data and a total area calculation.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 30 rows of data.

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130408.82 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*



STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	263.73	15.21	1.837	0.30( 0.27)	0.90	203.7	10520.00
2	303.03	33.18	1.185	0.30( 0.28)	0.93	403.6	10500.00

LONGEST FLOWPATH FROM NODE 10500.00 TO NODE 13802.00 = 12187.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13135.50	15.21	1.837	0.30( 0.25)	0.82	2760.1	10520.00
2	14907.33	21.75	1.510	0.30( 0.25)	0.83	3930.9	10300.00
3	15027.19	22.46	1.482	0.30( 0.25)	0.83	4070.6	10380.00
4	15121.31	22.79	1.469	0.30( 0.25)	0.83	4135.2	10230.00
5	15158.63	22.94	1.463	0.30( 0.25)	0.83	4169.6	10400.00
6	15720.69	25.17	1.376	0.30( 0.25)	0.83	4689.2	10320.00
7	16182.56	27.04	1.325	0.30( 0.25)	0.83	5114.5	10360.00
8	16900.81	29.96	1.244	0.30( 0.25)	0.83	5771.8	10340.00
9	16902.41	29.96	1.244	0.30( 0.25)	0.83	5773.2	300.00
10	17303.67	31.57	1.214	0.30( 0.25)	0.82	6310.7	10250.00
11	17378.43	31.86	1.209	0.30( 0.25)	0.82	6410.8	10200.00
12	17710.79	33.18	1.185	0.30( 0.25)	0.82	6846.5	10500.00
13	18326.48	35.71	1.139	0.30( 0.25)	0.82	7653.1	10220.00
14	18624.48	36.93	1.116	0.30( 0.25)	0.82	8042.7	410.00
15	20091.55	44.57	1.006	0.30( 0.25)	0.82	10485.3	100.00
16	21664.50	53.87	0.908	0.30( 0.25)	0.83	14224.7	150.00
17	24019.20	69.90	0.805	0.30( 0.26)	0.86	21149.7	390.00
18	25383.49	84.46	0.733	0.30( 0.27)	0.88	27777.3	13100.00
19	25692.98	91.32	0.702	0.30( 0.27)	0.89	30391.4	11801.00
20	27048.59	109.12	0.651	0.30( 0.27)	0.91	38932.3	13510.00
21	27715.53	116.14	0.631	0.30( 0.27)	0.92	42924.9	13010.00
22	28446.06	122.02	0.617	0.30( 0.28)	0.92	46599.9	11330.00
23	29018.41	130.07	0.603	0.30( 0.28)	0.93	51687.0	10630.00
24	28754.28	135.70	0.594	0.30( 0.28)	0.93	54276.9	12330.00
25	28481.59	142.36	0.582	0.30( 0.28)	0.94	57419.3	11600.00
26	28091.17	148.21	0.573	0.30( 0.28)	0.94	59653.6	11111.00
27	27661.97	154.41	0.562	0.30( 0.28)	0.94	61587.5	12201.00
28	26726.40	163.53	0.547	0.30( 0.28)	0.94	63675.7	12231.00
29	25872.07	171.20	0.534	0.30( 0.28)	0.94	65087.3	10400.00
30	24511.73	182.91	0.517	0.30( 0.28)	0.94	66708.0	10320.00
31	23230.50	192.95	0.509	0.30( 0.28)	0.94	67095.9	12000.00
32	20260.18	222.97	0.486	0.30( 0.28)	0.94	67712.9	10100.00

TOTAL AREA (ACRES) = 67712.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 29018.41 Tc(MIN.) = 130.073  
 EFFECTIVE AREA(ACRES) = 51687.00 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 67712.9  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130408.82 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13802.00 TO NODE 13803.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 135.00 DOWNSTREAM(FEET) = 133.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 207.23 CHANNEL SLOPE = 0.0097

GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 10.50  
 CHANNEL FLOW THRU SUBAREA(CFS) = 29018.41  
 FLOW VELOCITY(FEET/SEC.) = 19.46 FLOW DEPTH(FEET) = 10.50  
 TRAVEL TIME(MIN.) = 0.18 Tc(MIN.) = 130.25  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130616.05 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13135.50	15.44	1.824	0.30( 0.25)	0.82	2760.1	10520.00
2	14907.33	21.96	1.502	0.30( 0.25)	0.83	3930.9	10300.00
3	15027.19	22.67	1.474	0.30( 0.25)	0.83	4070.6	10380.00
4	15121.31	23.01	1.460	0.30( 0.25)	0.83	4135.2	10230.00
5	15158.63	23.15	1.454	0.30( 0.25)	0.83	4169.6	10400.00
6	15720.69	25.38	1.370	0.30( 0.25)	0.83	4689.2	10320.00
7	16182.56	27.25	1.319	0.30( 0.25)	0.83	5114.5	10360.00
8	16900.81	30.17	1.240	0.30( 0.25)	0.83	5771.8	10340.00
9	16902.41	30.17	1.240	0.30( 0.25)	0.83	5773.2	300.00
10	17303.67	31.78	1.211	0.30( 0.25)	0.82	6310.7	10250.00
11	17378.43	32.07	1.205	0.30( 0.25)	0.82	6410.8	10200.00
12	17710.79	33.39	1.181	0.30( 0.25)	0.82	6846.5	10500.00
13	18326.48	35.91	1.135	0.30( 0.25)	0.82	7653.1	10220.00
14	18624.48	37.14	1.112	0.30( 0.25)	0.82	8042.7	410.00
15	20091.55	44.77	1.004	0.30( 0.25)	0.82	10485.3	100.00
16	21664.50	54.07	0.906	0.30( 0.25)	0.83	14224.7	150.00
17	24019.20	70.09	0.804	0.30( 0.26)	0.86	21149.7	390.00
18	25383.49	84.64	0.732	0.30( 0.27)	0.88	27777.3	13100.00
19	25692.98	91.51	0.702	0.30( 0.27)	0.89	30391.4	11801.00
20	27048.59	109.30	0.651	0.30( 0.27)	0.91	38932.3	13510.00
21	27715.53	116.32	0.631	0.30( 0.27)	0.92	42924.9	13010.00
22	28446.06	122.20	0.616	0.30( 0.28)	0.92	46599.9	11330.00
23	29018.41	130.25	0.603	0.30( 0.28)	0.93	51687.0	10630.00
24	28754.28	135.88	0.593	0.30( 0.28)	0.93	54276.9	12330.00
25	28481.59	142.54	0.582	0.30( 0.28)	0.94	57419.3	11600.00
26	28091.17	148.39	0.572	0.30( 0.28)	0.94	59653.6	11111.00
27	27661.97	154.59	0.562	0.30( 0.28)	0.94	61587.5	12201.00
28	26726.40	163.71	0.546	0.30( 0.28)	0.94	63675.7	12231.00
29	25872.07	171.38	0.534	0.30( 0.28)	0.94	65087.3	10400.00
30	24511.73	183.09	0.517	0.30( 0.28)	0.94	66708.0	10320.00
31	23230.50	193.14	0.509	0.30( 0.28)	0.94	67095.9	12000.00
32	20260.18	223.17	0.485	0.30( 0.28)	0.94	67712.9	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 29018.41 Tc(MIN.) = 130.25  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 51687.00

\*\*\*\*\*

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 130.25

\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.603

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

RESIDENTIAL  
 "1 DWELLING/ACRE" B 48.80 0.30 0.800 56  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.800  
 SUBAREA AREA (ACRES) = 48.80 SUBAREA RUNOFF(CFS) = 15.93  
 EFFECTIVE AREA(ACRES) = 51735.80 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 67761.7 PEAK FLOW RATE(CFS) = 29018.41  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13802.00 TO NODE 13803.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506106E.DNA  
 MEMORY BANK # 3 DEFINED AS FOLLOWS:  

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	45.15	18.06	0.30(0.20)	0.67		36.9	10600.00

 TOTAL AREA(ACRES) = 36.9

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13135.50	15.44	1.824	0.30(0.25)	0.82	2808.9	10520.00
2	14907.33	21.96	1.502	0.30(0.25)	0.82	3979.7	10300.00
3	15027.19	22.67	1.474	0.30(0.25)	0.82	4119.4	10380.00
4	15121.31	23.01	1.460	0.30(0.25)	0.82	4184.0	10230.00
5	15158.63	23.15	1.454	0.30(0.25)	0.82	4218.4	10400.00
6	15720.69	25.38	1.370	0.30(0.25)	0.83	4738.0	10320.00
7	16182.56	27.25	1.319	0.30(0.25)	0.83	5163.3	10360.00
8	16900.81	30.17	1.240	0.30(0.25)	0.83	5820.6	10340.00
9	16902.41	30.17	1.240	0.30(0.25)	0.83	5822.0	300.00
10	17303.67	31.78	1.211	0.30(0.25)	0.82	6359.5	10250.00
11	17378.43	32.07	1.205	0.30(0.25)	0.82	6459.6	10200.00
12	17710.79	33.39	1.181	0.30(0.25)	0.82	6895.3	10500.00
13	18326.48	35.91	1.135	0.30(0.25)	0.82	7701.9	10220.00
14	18624.48	37.14	1.112	0.30(0.25)	0.82	8091.5	410.00
15	20091.55	44.77	1.004	0.30(0.25)	0.82	10534.1	100.00
16	21664.50	54.07	0.906	0.30(0.25)	0.83	14273.5	150.00
17	24019.20	70.09	0.804	0.30(0.26)	0.86	21198.5	390.00
18	25383.49	84.64	0.732	0.30(0.27)	0.88	27826.1	13100.00
19	25692.98	91.51	0.702	0.30(0.27)	0.89	30440.2	11801.00
20	27048.59	109.30	0.651	0.30(0.27)	0.91	38981.1	13510.00
21	27715.53	116.32	0.631	0.30(0.27)	0.92	42973.7	13010.00

22	28446.06	122.20	0.616	0.30(0.28)	0.92	46648.7	11330.00
23	29018.41	130.25	0.603	0.30(0.28)	0.93	51735.8	10630.00
24	28754.28	135.88	0.593	0.30(0.28)	0.93	54325.7	12330.00
25	28481.59	142.54	0.582	0.30(0.28)	0.94	57468.1	11600.00
26	28091.17	148.39	0.572	0.30(0.28)	0.94	59702.4	11111.00
27	27661.97	154.59	0.562	0.30(0.28)	0.94	61636.3	12201.00
28	26726.40	163.71	0.546	0.30(0.28)	0.94	63724.5	12231.00
29	25872.07	171.38	0.534	0.30(0.28)	0.94	65136.1	10400.00
30	24511.73	183.09	0.517	0.30(0.28)	0.94	66756.8	10320.00
31	23230.50	193.14	0.509	0.30(0.28)	0.94	67144.7	12000.00
32	20260.18	223.17	0.485	0.30(0.28)	0.94	67761.7	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130616.05 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	45.15	18.06	1.684	0.30(0.20)	0.67	36.9	10600.00

LONGEST FLOWPATH FROM NODE 10600.00 TO NODE 13803.00 = 1713.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13177.76	15.44	1.824	0.30(0.25)	0.82	2840.4	10520.00
2	13893.70	18.06	1.684	0.30(0.25)	0.82	3317.0	10600.00
3	14946.95	21.96	1.502	0.30(0.25)	0.82	4016.6	10300.00
4	15065.95	22.67	1.474	0.30(0.25)	0.82	4156.3	10380.00
5	15159.66	23.01	1.460	0.30(0.25)	0.82	4220.9	10230.00
6	15196.80	23.15	1.454	0.30(0.25)	0.82	4255.3	10400.00
7	15756.30	25.38	1.370	0.30(0.25)	0.82	4774.9	10320.00
8	16216.60	27.25	1.319	0.30(0.25)	0.82	5200.2	10360.00
9	16932.45	30.17	1.240	0.30(0.25)	0.82	5857.5	10340.00
10	16934.05	30.17	1.240	0.30(0.25)	0.82	5858.9	300.00
11	17334.42	31.78	1.211	0.30(0.25)	0.82	6396.4	10250.00
12	17409.01	32.07	1.205	0.30(0.25)	0.82	6496.5	10200.00
13	17740.63	33.39	1.181	0.30(0.25)	0.82	6932.2	10500.00
14	18354.92	35.91	1.135	0.30(0.25)	0.82	7738.8	10220.00
15	18652.23	37.14	1.112	0.30(0.25)	0.82	8128.4	410.00
16	20116.00	44.77	1.004	0.30(0.25)	0.82	10571.0	100.00
17	21685.98	54.07	0.906	0.30(0.25)	0.83	14310.4	150.00
18	24037.57	70.09	0.804	0.30(0.26)	0.86	21235.4	390.00
19	25399.68	84.64	0.732	0.30(0.26)	0.88	27863.0	13100.00
20	25708.23	91.51	0.702	0.30(0.27)	0.89	30477.1	11801.00
21	27062.29	109.30	0.651	0.30(0.27)	0.91	39018.0	13510.00
22	27728.61	116.32	0.631	0.30(0.27)	0.92	43010.6	13010.00
23	28458.71	122.20	0.616	0.30(0.28)	0.92	46685.6	11330.00
24	29030.64	130.25	0.603	0.30(0.28)	0.93	51772.7	10630.00
25	28766.23	135.88	0.593	0.30(0.28)	0.93	54362.6	12330.00
26	28493.19	142.54	0.582	0.30(0.28)	0.94	57505.0	11600.00
27	28102.48	148.39	0.572	0.30(0.28)	0.94	59739.3	11111.00
28	27672.96	154.59	0.562	0.30(0.28)	0.94	61673.2	12201.00
29	26736.92	163.71	0.546	0.30(0.28)	0.94	63761.4	12231.00
30	25882.20	171.38	0.534	0.30(0.28)	0.94	65173.0	10400.00
31	24521.35	183.09	0.517	0.30(0.28)	0.94	66793.7	10320.00
32	23239.88	193.14	0.509	0.30(0.28)	0.94	67181.6	12000.00
33	20268.84	223.17	0.485	0.30(0.28)	0.94	67798.6	10100.00

TOTAL AREA(ACRES) = 67798.6

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 29030.64 Tc(MIN.) = 130.251  
 EFFECTIVE AREA(ACRES) = 51772.70 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 67798.6  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130616.05 FEET.

=====  
 END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 67798.6 TC(MIN.) = 130.25  
 EFFECTIVE AREA(ACRES) = 51772.70 AREA-AVERAGED Fm(INCH/HR)= 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.930  
 PEAK FLOW RATE(CFS) = 29030.64

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13177.76	15.44	1.824	0.30( 0.25)	0.82	2840.4	10520.00
2	13893.70	18.06	1.684	0.30( 0.25)	0.82	3317.0	10600.00
3	14946.95	21.96	1.502	0.30( 0.25)	0.82	4016.6	10300.00
4	15065.95	22.67	1.474	0.30( 0.25)	0.82	4156.3	10380.00
5	15159.66	23.01	1.460	0.30( 0.25)	0.82	4220.9	10230.00
6	15196.80	23.15	1.454	0.30( 0.25)	0.82	4255.3	10400.00
7	15756.30	25.38	1.370	0.30( 0.25)	0.82	4774.9	10320.00
8	16216.60	27.25	1.319	0.30( 0.25)	0.82	5200.2	10360.00
9	16932.45	30.17	1.240	0.30( 0.25)	0.82	5857.5	10340.00
10	16934.05	30.17	1.240	0.30( 0.25)	0.82	5858.9	300.00
11	17334.42	31.78	1.211	0.30( 0.25)	0.82	6396.4	10250.00
12	17409.01	32.07	1.205	0.30( 0.25)	0.82	6496.5	10200.00
13	17740.63	33.39	1.181	0.30( 0.25)	0.82	6932.2	10500.00
14	18354.92	35.91	1.135	0.30( 0.25)	0.82	7738.8	10220.00
15	18652.23	37.14	1.112	0.30( 0.25)	0.82	8128.4	410.00
16	20116.00	44.77	1.004	0.30( 0.25)	0.82	10571.0	100.00
17	21685.98	54.07	0.906	0.30( 0.25)	0.83	14310.4	150.00
18	24037.57	70.09	0.804	0.30( 0.26)	0.86	21235.4	390.00
19	25399.68	84.64	0.732	0.30( 0.26)	0.88	27863.0	13100.00
20	25708.23	91.51	0.702	0.30( 0.27)	0.89	30477.1	11801.00
21	27062.29	109.30	0.651	0.30( 0.27)	0.91	39018.0	13510.00
22	27728.61	116.32	0.631	0.30( 0.27)	0.92	43010.6	13010.00
23	28458.71	122.20	0.616	0.30( 0.28)	0.92	46685.6	11330.00
24	29030.64	130.25	0.603	0.30( 0.28)	0.93	51772.7	10630.00
25	28766.23	135.88	0.593	0.30( 0.28)	0.93	54362.6	12330.00
26	28493.19	142.54	0.582	0.30( 0.28)	0.94	57505.0	11600.00
27	28102.48	148.39	0.572	0.30( 0.28)	0.94	59739.3	11111.00
28	27672.96	154.59	0.562	0.30( 0.28)	0.94	61673.2	12201.00
29	26736.92	163.71	0.546	0.30( 0.28)	0.94	63761.4	12231.00
30	25882.20	171.38	0.534	0.30( 0.28)	0.94	65173.0	10400.00
31	24521.35	183.09	0.517	0.30( 0.28)	0.94	66793.7	10320.00
32	23239.88	193.14	0.509	0.30( 0.28)	0.94	67181.6	12000.00
33	20268.84	223.17	0.485	0.30( 0.28)	0.94	67798.6	10100.00

=====  
 END OF RATIONAL METHOD ANALYSIS

\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S38- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 10-YR RM EV APRIL 2019 CCHIU \*  
\*\*\*\*\*

FILE NAME: RI10EV38.DAT  
TIME/DATE OF STUDY: 10:16 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 10.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 3.698
- 2) 10.00; 2.475
- 3) 15.00; 1.846
- 4) 20.00; 1.578
- 5) 25.00; 1.379
- 6) 30.00; 1.242
- 7) 40.00; 1.059
- 8) 50.00; 0.941
- 9) 60.00; 0.852
- 10) 90.00; 0.704
- 11) 120.00; 0.619
- 12) 180.00; 0.517
- 13) 360.00; 0.378
- 14) 1200.00; 0.165

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI10EV37.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15196.80	23.15	0.30 ( 0.25)	0.82	4255.3	10400.00
2	18652.23	37.14	0.30 ( 0.25)	0.82	8128.4	410.00
3	20116.00	44.77	0.30 ( 0.25)	0.82	10571.0	100.00
4	21685.98	54.07	0.30 ( 0.25)	0.83	14310.4	150.00
5	24037.57	70.09	0.30 ( 0.26)	0.86	21235.4	390.00
6	25399.68	84.64	0.30 ( 0.26)	0.88	27863.0	13100.00
7	25708.23	91.51	0.30 ( 0.27)	0.89	30477.1	11801.00
8	27062.29	109.30	0.30 ( 0.27)	0.91	39018.0	13510.00
9	27728.61	116.32	0.30 ( 0.27)	0.92	43010.6	13010.00
10	28458.71	122.20	0.30 ( 0.28)	0.92	46685.6	11330.00
11	29030.64	130.25	0.30 ( 0.28)	0.93	51772.7	10630.00
12	28766.23	135.88	0.30 ( 0.28)	0.93	54362.6	12330.00
13	28493.19	142.54	0.30 ( 0.28)	0.94	57505.0	11600.00
14	28102.48	148.39	0.30 ( 0.28)	0.94	59739.3	11111.00
15	27672.96	154.59	0.30 ( 0.28)	0.94	61673.2	12201.00
16	26736.92	163.71	0.30 ( 0.28)	0.94	63761.4	12231.00
17	25882.20	171.38	0.30 ( 0.28)	0.94	65173.0	10400.00
18	24521.35	183.09	0.30 ( 0.28)	0.94	66793.7	10320.00
19	23239.88	193.14	0.30 ( 0.28)	0.94	67181.6	12000.00
20	20268.84	223.17	0.30 ( 0.28)	0.94	67798.6	10100.00
TOTAL AREA (ACRES) =						67798.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15196.80	23.15	0.30 ( 0.25)	0.82	4255.3	10400.00
2	18652.23	37.14	0.30 ( 0.25)	0.82	8128.4	410.00
3	20116.00	44.77	0.30 ( 0.25)	0.82	10571.0	100.00
4	21685.98	54.07	0.30 ( 0.25)	0.83	14310.4	150.00
5	24037.57	70.09	0.30 ( 0.26)	0.86	21235.4	390.00
6	25399.68	84.64	0.30 ( 0.26)	0.88	27863.0	13100.00
7	25708.23	91.51	0.30 ( 0.27)	0.89	30477.1	11801.00
8	27062.29	109.30	0.30 ( 0.27)	0.91	39018.0	13510.00
9	27728.61	116.32	0.30 ( 0.27)	0.92	43010.6	13010.00
10	28458.71	122.20	0.30 ( 0.28)	0.92	46685.6	11330.00
11	29030.64	130.25	0.30 ( 0.28)	0.93	51772.7	10630.00
12	28766.23	135.88	0.30 ( 0.28)	0.93	54362.6	12330.00
13	28493.19	142.54	0.30 ( 0.28)	0.94	57505.0	11600.00

14	28102.48	148.39	0.30	( 0.28)	0.94	59739.3	11111.00	
15	27672.96	154.59	0.30	( 0.28)	0.94	61673.2	12201.00	
16	26736.92	163.71	0.30	( 0.28)	0.94	63761.4	12231.00	
17	25882.20	171.38	0.30	( 0.28)	0.94	65173.0	10400.00	
18	24521.35	183.09	0.30	( 0.28)	0.94	66793.7	10320.00	
19	23239.88	193.14	0.30	( 0.28)	0.94	67181.6	12000.00	
20	20268.84	223.17	0.30	( 0.28)	0.94	67798.6	10100.00	
TOTAL AREA (ACRES) =			67798.6					

\*\*\*\*\*

FLOW PROCESS FROM NODE 13803.00 TO NODE 13820.00 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 140.00 DOWNSTREAM(FEET) = 137.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 926.91 CHANNEL SLOPE = 0.0032  
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 14.06

\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.600

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	31.44	0.30	0.983	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.983

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 29034.96

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 13.23

AVERAGE FLOW DEPTH(FEET) = 14.05 TRAVEL TIME(MIN.) = 1.17  
 Tc(MIN.) = 131.42

SUBAREA AREA(ACRES) = 31.44 SUBAREA RUNOFF(CFS) = 8.62

EFFECTIVE AREA(ACRES) = 51804.14 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA(ACRES) = 67830.0 PEAK FLOW RATE(CFS) = 29030.64

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT(FEET) = 14.05

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 14.05 FLOW VELOCITY(FEET/SEC.) = 13.23

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13820.00 = 131542.95 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15196.80	24.57	1.396	0.30( 0.25)	0.82	4286.8	10400.00
2	18652.23	38.47	1.087	0.30( 0.25)	0.82	8159.8	410.00
3	20116.00	46.07	0.987	0.30( 0.25)	0.82	10602.5	100.00
4	21685.98	55.34	0.893	0.30( 0.25)	0.83	14341.9	150.00
5	24037.57	71.33	0.796	0.30( 0.26)	0.86	21266.8	390.00
6	25399.68	85.86	0.724	0.30( 0.27)	0.88	27894.5	13100.00
7	25708.23	92.72	0.696	0.30( 0.27)	0.89	30508.6	11801.00
8	27062.29	110.49	0.646	0.30( 0.27)	0.91	39049.5	13510.00
9	27728.61	117.51	0.626	0.30( 0.27)	0.92	43042.0	13010.00
10	28458.71	123.38	0.613	0.30( 0.28)	0.92	46717.0	11330.00
11	29030.64	131.42	0.600	0.30( 0.28)	0.93	51804.1	10630.00

12	28766.23	137.05	0.590	0.30( 0.28)	0.93	54394.0	12330.00
13	28493.19	143.72	0.579	0.30( 0.28)	0.94	57536.5	11600.00
14	28102.48	149.56	0.569	0.30( 0.28)	0.94	59770.8	11111.00
15	27672.96	155.78	0.558	0.30( 0.28)	0.94	61704.6	12201.00
16	26736.92	164.91	0.543	0.30( 0.28)	0.94	63792.9	12231.00
17	25882.20	172.59	0.530	0.30( 0.28)	0.94	65204.4	10400.00
18	24521.35	184.32	0.514	0.30( 0.28)	0.94	66825.2	10320.00
19	23239.88	194.38	0.506	0.30( 0.28)	0.94	67213.0	12000.00
20	20268.84	224.46	0.483	0.30( 0.28)	0.94	67830.0	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 29030.64 Tc(MIN.) = 131.42

AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 51804.14

\*\*\*\*\*

FLOW PROCESS FROM NODE 13803.00 TO NODE 13820.00 IS CODE = 1

-----  
 >>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

=====

TOTAL NUMBER OF STREAMS = 2

CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:

TIME OF CONCENTRATION(MIN.) = 131.42

RAINFALL INTENSITY(INCH/HR) = 0.60

AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.93

EFFECTIVE STREAM AREA(ACRES) = 51804.14

TOTAL STREAM AREA(ACRES) = 67830.01

PEAK FLOW RATE(CFS) AT CONFLUENCE = 29030.64

\*\*\*\*\*

FLOW PROCESS FROM NODE 13810.00 TO NODE 13811.00 IS CODE = 21

-----  
 >>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<

>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 648.54

ELEVATION DATA: UPSTREAM(FEET) = 756.46 DOWNSTREAM(FEET) = 586.02

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20

SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 12.293

\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.187

SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL, BROADLEAF"	-	5.58	0.30	1.000	56	12.29

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA RUNOFF(CFS) = 9.47

TOTAL AREA(ACRES) = 5.58 PEAK FLOW RATE(CFS) = 9.47

\*\*\*\*\*

FLOW PROCESS FROM NODE 13811.00 TO NODE 13811.50 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 586.02 DOWNSTREAM(FEET) = 437.69  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 696.28 CHANNEL SLOPE = 0.2130  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.37  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.914  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 14.79 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 20.28  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.35  
 AVERAGE FLOW DEPTH(FEET) = 0.35 TRAVEL TIME(MIN.) = 2.17  
 Tc(MIN.) = 14.46  
 SUBAREA AREA(ACRES) = 14.79 SUBAREA RUNOFF(CFS) = 21.48  
 EFFECTIVE AREA(ACRES) = 20.37 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 20.4 PEAK FLOW RATE(CFS) = 29.59  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.44  
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 0.44 FLOW VELOCITY(FEET/SEC.) = 6.19  
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13811.50 = 1344.82 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13811.50 TO NODE 13812.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 437.69 DOWNSTREAM(FEET) = 402.36  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 681.04 CHANNEL SLOPE = 0.0519  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.83  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.737  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 18.41 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 41.51  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.40  
 AVERAGE FLOW DEPTH(FEET) = 0.81 TRAVEL TIME(MIN.) = 2.58  
 Tc(MIN.) = 17.04  
 SUBAREA AREA(ACRES) = 18.41 SUBAREA RUNOFF(CFS) = 23.81  
 EFFECTIVE AREA(ACRES) = 38.78 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 38.8 PEAK FLOW RATE(CFS) = 50.14  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.90

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 0.90 FLOW VELOCITY(FEET/SEC.) = 4.70  
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13812.00 = 2025.86 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13812.00 TO NODE 13813.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 402.36 DOWNSTREAM(FEET) = 259.72  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1282.56 CHANNEL SLOPE = 0.1112  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.86  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.568  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 27.87 0.30 0.858 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.858  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 66.60  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.68  
 AVERAGE FLOW DEPTH(FEET) = 0.85 TRAVEL TIME(MIN.) = 3.20  
 Tc(MIN.) = 20.24  
 SUBAREA AREA(ACRES) = 27.87 SUBAREA RUNOFF(CFS) = 32.89  
 EFFECTIVE AREA(ACRES) = 66.65 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94  
 TOTAL AREA(ACRES) = 66.7 PEAK FLOW RATE(CFS) = 77.16  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.93

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 0.93 FLOW VELOCITY(FEET/SEC.) = 7.01  
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13813.00 = 3308.42 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 31  
 -----

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 259.72 DOWNSTREAM(FEET) = 137.00  
 FLOW LENGTH(FEET) = 2412.88 MANNING'S N = 0.013  
 ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000  
 DEPTH OF FLOW IN 36.0 INCH PIPE IS 18.9 INCHES  
 PIPE-FLOW VELOCITY(FEET/SEC.) = 20.58  
 ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1  
 PIPE-FLOW(CFS) = 77.16  
 PIPE TRAVEL TIME(MIN.) = 1.95 Tc(MIN.) = 22.19  
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13820.00 = 5721.30 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

```

=====
MAINLINE Tc(MIN.) = 22.19
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.491
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp        Ap        SCS
LAND USE                GROUP  (ACRES)  (INCH/HR) (DECIMAL) CN
USER-DEFINED            -      83.64    0.30     0.570    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.570
SUBAREA AREA(ACRES) = 83.64      SUBAREA RUNOFF(CFS) = 99.35
EFFECTIVE AREA(ACRES) = 150.29   AREA-AVERAGED Fm(INCH/HR) = 0.22
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.73
TOTAL AREA(ACRES) = 150.3        PEAK FLOW RATE(CFS) = 171.84

```

```

*****
FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 1
-----

```

```

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<
-----

```

```

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 22.19
RAINFALL INTENSITY(INCH/HR) = 1.49
AREA-AVERAGED Fm(INCH/HR) = 0.22
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.73
EFFECTIVE STREAM AREA(ACRES) = 150.29
TOTAL STREAM AREA(ACRES) = 150.29
PEAK FLOW RATE(CFS) AT CONFLUENCE = 171.84

```

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15196.80	24.57	1.396	0.30( 0.25)	0.82	4286.8	10400.00
1	18652.23	38.47	1.087	0.30( 0.25)	0.82	8159.8	410.00
1	20116.00	46.07	0.987	0.30( 0.25)	0.82	10602.5	100.00
1	21685.98	55.34	0.893	0.30( 0.25)	0.83	14341.9	150.00
1	24037.57	71.33	0.796	0.30( 0.26)	0.86	21266.8	390.00
1	25399.68	85.86	0.724	0.30( 0.27)	0.88	27894.5	13100.00
1	25708.23	92.72	0.696	0.30( 0.27)	0.89	30508.6	11801.00
1	27062.29	110.49	0.646	0.30( 0.27)	0.91	39049.5	13510.00
1	27728.61	117.51	0.626	0.30( 0.27)	0.92	43042.0	13010.00
1	28458.71	123.38	0.613	0.30( 0.28)	0.92	46717.0	11330.00
1	29030.64	131.42	0.600	0.30( 0.28)	0.93	51804.1	10630.00
1	28766.23	137.05	0.590	0.30( 0.28)	0.93	54394.0	12330.00
1	28493.19	143.72	0.579	0.30( 0.28)	0.94	57536.5	11600.00
1	28102.48	149.56	0.569	0.30( 0.28)	0.94	59770.8	11111.00
1	27672.96	155.78	0.558	0.30( 0.28)	0.94	61704.6	12201.00
1	26736.92	164.91	0.543	0.30( 0.28)	0.94	63792.9	12231.00
1	25882.20	172.59	0.530	0.30( 0.28)	0.94	65204.4	10400.00
1	24521.35	184.32	0.514	0.30( 0.28)	0.94	66825.2	10320.00
1	23239.88	194.38	0.506	0.30( 0.28)	0.94	67213.0	12000.00
1	20268.84	224.46	0.483	0.30( 0.28)	0.94	67830.0	10100.00
2	171.84	22.19	1.491	0.30( 0.22)	0.73	150.3	13810.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15029.17	22.19	1.491	0.30( 0.25)	0.82	4022.8	13810.00
2	15355.87	24.57	1.396	0.30( 0.25)	0.82	4437.1	10400.00
3	18769.48	38.47	1.087	0.30( 0.25)	0.82	8310.1	410.00
4	20219.77	46.07	0.987	0.30( 0.25)	0.82	10752.8	100.00
5	21777.04	55.34	0.893	0.30( 0.25)	0.83	14492.1	150.00
6	24115.46	71.33	0.796	0.30( 0.26)	0.86	21417.1	390.00
7	25467.87	85.86	0.724	0.30( 0.26)	0.88	28044.8	13100.00
8	25772.62	92.72	0.696	0.30( 0.27)	0.89	30658.9	11801.00
9	27119.87	110.49	0.646	0.30( 0.27)	0.91	39199.8	13510.00
10	27783.50	117.51	0.626	0.30( 0.27)	0.92	43192.3	13010.00
11	28511.87	123.38	0.613	0.30( 0.28)	0.92	46867.3	11330.00
12	29081.95	131.42	0.600	0.30( 0.28)	0.93	51954.4	10630.00
13	28816.24	137.05	0.590	0.30( 0.28)	0.93	54544.3	12330.00
14	28541.67	143.72	0.579	0.30( 0.28)	0.94	57686.7	11600.00
15	28149.61	149.56	0.569	0.30( 0.28)	0.94	59921.1	11111.00
16	27718.67	155.78	0.558	0.30( 0.28)	0.94	61854.9	12201.00
17	26780.53	164.91	0.543	0.30( 0.28)	0.94	63943.2	12231.00
18	25924.04	172.59	0.530	0.30( 0.28)	0.94	65354.7	10400.00
19	24561.03	184.32	0.514	0.30( 0.28)	0.94	66975.5	10320.00
20	23278.51	194.38	0.506	0.30( 0.28)	0.94	67363.3	12000.00
21	20304.33	224.46	0.483	0.30( 0.28)	0.94	67980.3	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

```

PEAK FLOW RATE(CFS) = 29081.95      Tc(MIN.) = 131.42
EFFECTIVE AREA(ACRES) = 51954.43   AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30   AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 67980.3
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13820.00 = 131542.95 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13820.00 TO NODE 13840.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<
-----

```

```

ELEVATION DATA: UPSTREAM(FEET) = 137.00 DOWNSTREAM(FEET) = 133.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1261.34 CHANNEL SLOPE = 0.0032
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 14.14
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.597
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp        Ap        SCS
LAND USE                GROUP  (ACRES)  (INCH/HR) (DECIMAL) CN
USER-DEFINED            -      31.60    0.30     0.683    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.683
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 29087.53
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 13.14
AVERAGE FLOW DEPTH(FEET) = 14.14 TRAVEL TIME(MIN.) = 1.60
Tc(MIN.) = 133.02
SUBAREA AREA(ACRES) = 31.60      SUBAREA RUNOFF(CFS) = 11.15
EFFECTIVE AREA(ACRES) = 51986.04 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

```

TOTAL AREA (ACRES) = 68011.9 PEAK FLOW RATE (CFS) = 29081.95  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 14.14

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 14.14 FLOW VELOCITY (FEET/SEC.) = 13.14  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13840.00 = 132804.30 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15029.17	24.14	1.413	0.30 ( 0.25)	0.82	4054.4	13810.00
2	15355.87	26.50	1.338	0.30 ( 0.25)	0.82	4468.7	10400.00
3	18769.48	40.28	1.056	0.30 ( 0.25)	0.82	8341.7	410.00
4	20219.77	47.84	0.966	0.30 ( 0.25)	0.82	10784.4	100.00
5	21777.04	57.08	0.878	0.30 ( 0.25)	0.83	14523.7	150.00
6	24115.46	73.01	0.788	0.30 ( 0.26)	0.86	21448.7	390.00
7	25467.87	87.52	0.716	0.30 ( 0.26)	0.88	28076.4	13100.00
8	25772.62	94.37	0.692	0.30 ( 0.27)	0.89	30690.5	11801.00
9	27119.87	112.13	0.641	0.30 ( 0.27)	0.91	39231.4	13510.00
10	27783.50	119.13	0.621	0.30 ( 0.27)	0.92	43223.9	13010.00
11	28511.87	124.98	0.611	0.30 ( 0.28)	0.92	46898.9	11330.00
12	29081.95	133.02	0.597	0.30 ( 0.28)	0.93	51986.0	10630.00
13	28816.24	138.65	0.587	0.30 ( 0.28)	0.93	54575.9	12330.00
14	28541.67	145.32	0.576	0.30 ( 0.28)	0.94	57718.3	11600.00
15	28149.61	151.18	0.566	0.30 ( 0.28)	0.94	59952.7	11111.00
16	27718.67	157.40	0.555	0.30 ( 0.28)	0.94	61886.5	12201.00
17	26780.53	166.55	0.540	0.30 ( 0.28)	0.94	63974.8	12231.00
18	25924.04	174.24	0.527	0.30 ( 0.28)	0.94	65386.3	10400.00
19	24561.03	186.00	0.512	0.30 ( 0.28)	0.94	67007.1	10320.00
20	23278.51	196.09	0.505	0.30 ( 0.28)	0.94	67394.9	12000.00
21	20304.33	226.24	0.481	0.30 ( 0.28)	0.94	68011.9	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 29081.95 Tc (MIN.) = 133.02  
 AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA (ACRES) = 51986.04

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13820.00 TO NODE 13840.00 IS CODE = 1  
 -----

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

-----  
 TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
 TIME OF CONCENTRATION (MIN.) = 133.02  
 RAINFALL INTENSITY (INCH/HR) = 0.60  
 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93  
 EFFECTIVE STREAM AREA (ACRES) = 51986.04  
 TOTAL STREAM AREA (ACRES) = 68011.90  
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 29081.95

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13830.00 TO NODE 13831.00 IS CODE = 21  
 -----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH (FEET) = 744.71  
 ELEVATION DATA: UPSTREAM (FEET) = 1100.95 DOWNSTREAM (FEET) = 959.21

Tc = K \* [(LENGTH \*\* 3.00) / (ELEVATION CHANGE)] \*\* 0.20  
 SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 13.858  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.990

SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER						
"CHAPARRAL, BROADLEAF"	-	5.06	0.30	1.000	56	13.86

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA RUNOFF (CFS) = 7.70  
 TOTAL AREA (ACRES) = 5.06 PEAK FLOW RATE (CFS) = 7.70

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13831.00 TO NODE 13832.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 959.21 DOWNSTREAM (FEET) = 832.83  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1076.71 CHANNEL SLOPE = 0.1174  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT (FEET) = 0.55  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.716

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	32.57	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 28.59  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.04  
 AVERAGE FLOW DEPTH (FEET) = 0.51 TRAVEL TIME (MIN.) = 3.56  
 Tc (MIN.) = 17.42

SUBAREA AREA (ACRES) = 32.57 SUBAREA RUNOFF (CFS) = 41.52  
 EFFECTIVE AREA (ACRES) = 37.63 AREA-AVERAGED Fm (INCH/HR) = 0.30  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA (ACRES) = 37.6 PEAK FLOW RATE (CFS) = 47.97  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 0.70

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 0.70 FLOW VELOCITY (FEET/SEC.) = 6.04  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13832.00 = 1821.42 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13832.00 TO NODE 13833.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<



```

=====
ELEVATION DATA: UPSTREAM(FEET) = 832.83 DOWNSTREAM(FEET) = 572.49
CHANNEL LENGTH THRU SUBAREA(FEET) = 1883.58 CHANNEL SLOPE = 0.1382
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.81
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.505
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp      Ap   SCS
LAND USE           GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED      -        32.23    0.30    1.000  -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 65.50
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.10
AVERAGE FLOW DEPTH(FEET) = 0.80 TRAVEL TIME(MIN.) = 4.42
Tc(MIN.) = 21.84
SUBAREA AREA(ACRES) = 32.23 SUBAREA RUNOFF(CFS) = 34.95
EFFECTIVE AREA(ACRES) = 69.86 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 69.9 PEAK FLOW RATE(CFS) = 75.75
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.86

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.86 FLOW VELOCITY(FEET/SEC.) = 7.47
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13833.00 = 3705.00 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13833.00 TO NODE 13834.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====

```

```

ELEVATION DATA: UPSTREAM(FEET) = 572.49 DOWNSTREAM(FEET) = 471.65
CHANNEL LENGTH THRU SUBAREA(FEET) = 943.78 CHANNEL SLOPE = 0.1068
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.03
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.418
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp      Ap   SCS
LAND USE           GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED      -        27.51    0.30    1.000  -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 89.60
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.25
AVERAGE FLOW DEPTH(FEET) = 1.03 TRAVEL TIME(MIN.) = 2.17
Tc(MIN.) = 24.01
SUBAREA AREA(ACRES) = 27.51 SUBAREA RUNOFF(CFS) = 27.69
EFFECTIVE AREA(ACRES) = 97.37 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 97.4 PEAK FLOW RATE(CFS) = 98.02
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.08

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.08 FLOW VELOCITY(FEET/SEC.) = 7.46
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13834.00 = 4648.78 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13834.00 TO NODE 13835.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====

```

```

ELEVATION DATA: UPSTREAM(FEET) = 471.65 DOWNSTREAM(FEET) = 347.06
CHANNEL LENGTH THRU SUBAREA(FEET) = 1647.45 CHANNEL SLOPE = 0.0756
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.49
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.305
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp      Ap   SCS
LAND USE           GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED      -        94.21    0.30    1.000  -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 140.67
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.45
AVERAGE FLOW DEPTH(FEET) = 1.46 TRAVEL TIME(MIN.) = 3.69
Tc(MIN.) = 27.70
SUBAREA AREA(ACRES) = 94.21 SUBAREA RUNOFF(CFS) = 85.23
EFFECTIVE AREA(ACRES) = 191.58 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 191.6 PEAK FLOW RATE(CFS) = 173.31
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.64

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.64 FLOW VELOCITY(FEET/SEC.) = 7.94
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13835.00 = 6296.23 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13835.00 TO NODE 13836.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====

```

```

ELEVATION DATA: UPSTREAM(FEET) = 347.06 DOWNSTREAM(FEET) = 269.29
CHANNEL LENGTH THRU SUBAREA(FEET) = 1696.71 CHANNEL SLOPE = 0.0458
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.44
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.216
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp      Ap   SCS
LAND USE           GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED      -        233.25  0.30    1.000  -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 269.53

```

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.59  
 AVERAGE FLOW DEPTH (FEET) = 2.40 TRAVEL TIME (MIN.) = 3.72  
 Tc (MIN.) = 31.42  
 SUBAREA AREA (ACRES) = 233.25 SUBAREA RUNOFF (CFS) = 192.31  
 EFFECTIVE AREA (ACRES) = 424.83 AREA-AVERAGED Fm (INCH/HR) = 0.30  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA (ACRES) = 424.8 PEAK FLOW RATE (CFS) = 350.25  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 2.76

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 2.76 FLOW VELOCITY (FEET/SEC.) = 8.18  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13836.00 = 7992.94 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13836.00 TO NODE 13837.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 269.29 DOWNSTREAM (FEET) = 191.87  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 2529.21 CHANNEL SLOPE = 0.0306  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT (FEET) = 3.31  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.111

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	134.70	0.30	0.880	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.880  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 401.61  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.35  
 AVERAGE FLOW DEPTH (FEET) = 3.29 TRAVEL TIME (MIN.) = 5.73  
 Tc (MIN.) = 37.15  
 SUBAREA AREA (ACRES) = 134.70 SUBAREA RUNOFF (CFS) = 102.70  
 EFFECTIVE AREA (ACRES) = 559.53 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97  
 TOTAL AREA (ACRES) = 559.5 PEAK FLOW RATE (CFS) = 412.84  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 3.34

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 3.34 FLOW VELOCITY (FEET/SEC.) = 7.41  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13837.00 = 10522.15 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 31  
 -----

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 191.87 DOWNSTREAM (FEET) = 133.00  
 FLOW LENGTH (FEET) = 1151.02 MANNING'S N = 0.013  
 DEPTH OF FLOW IN 54.0 INCH PIPE IS 43.2 INCHES

PIPE-FLOW VELOCITY (FEET/SEC.) = 30.24  
 ESTIMATED PIPE DIAMETER (INCH) = 54.00 NUMBER OF PIPES = 1  
 PIPE-FLOW (CFS) = 412.84  
 PIPE TRAVEL TIME (MIN.) = 0.63 Tc (MIN.) = 37.79  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13840.00 = 11673.17 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 37.79  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.099

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.97	0.30	0.622	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.622  
 SUBAREA AREA (ACRES) = 5.97 SUBAREA RUNOFF (CFS) = 4.91  
 EFFECTIVE AREA (ACRES) = 565.50 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97  
 TOTAL AREA (ACRES) = 565.5 PEAK FLOW RATE (CFS) = 412.84  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 1  
 -----

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
 TIME OF CONCENTRATION (MIN.) = 37.79  
 RAINFALL INTENSITY (INCH/HR) = 1.10  
 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.97  
 EFFECTIVE STREAM AREA (ACRES) = 565.50  
 TOTAL STREAM AREA (ACRES) = 565.50  
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 412.84

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15029.17	24.14	1.413	0.30 ( 0.25)	0.82	4054.4	13810.00
1	15355.87	26.50	1.338	0.30 ( 0.25)	0.82	4468.7	10400.00
1	18769.48	40.28	1.056	0.30 ( 0.25)	0.82	8341.7	410.00
1	20219.77	47.84	0.966	0.30 ( 0.25)	0.82	10784.4	100.00
1	21777.04	57.08	0.878	0.30 ( 0.25)	0.83	14523.7	150.00
1	24115.46	73.01	0.788	0.30 ( 0.26)	0.86	21448.7	390.00
1	25467.87	87.52	0.716	0.30 ( 0.26)	0.88	28076.4	13100.00
1	25772.62	94.37	0.692	0.30 ( 0.27)	0.89	30690.5	11801.00
1	27119.87	112.13	0.641	0.30 ( 0.27)	0.91	39231.4	13510.00
1	27783.50	119.13	0.621	0.30 ( 0.27)	0.92	43223.9	13010.00
1	28511.87	124.98	0.611	0.30 ( 0.28)	0.92	46898.9	11330.00
1	29081.95	133.02	0.597	0.30 ( 0.28)	0.93	51986.0	10630.00
1	28816.24	138.65	0.587	0.30 ( 0.28)	0.93	54575.9	12330.00

1	28541.67	145.32	0.576	0.30	( 0.28)	0.94	57718.3	11600.00
1	28149.61	151.18	0.566	0.30	( 0.28)	0.94	59952.7	11111.00
1	27718.67	157.40	0.555	0.30	( 0.28)	0.94	61886.5	12201.00
1	26780.53	166.55	0.540	0.30	( 0.28)	0.94	63974.8	12231.00
1	25924.04	174.24	0.527	0.30	( 0.28)	0.94	65386.3	10400.00
1	24561.03	186.00	0.512	0.30	( 0.28)	0.94	67007.1	10320.00
1	23278.51	196.09	0.505	0.30	( 0.28)	0.94	67394.9	12000.00
1	20304.33	226.24	0.481	0.30	( 0.28)	0.94	68011.9	10100.00
2	412.84	37.79	1.099	0.30	( 0.29)	0.97	565.5	13830.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE	
1	15395.14	24.14	1.413	0.30	( 0.25)	0.83	4415.6	13810.00
2	15730.67	26.50	1.338	0.30	( 0.25)	0.83	4865.2	10400.00
3	18564.17	37.79	1.099	0.30	( 0.25)	0.83	8205.9	13830.00
4	19159.96	40.28	1.056	0.30	( 0.25)	0.83	8907.2	410.00
5	20564.75	47.84	0.966	0.30	( 0.25)	0.83	11349.9	100.00
6	22076.91	57.08	0.878	0.30	( 0.25)	0.84	15089.2	150.00
7	24369.31	73.01	0.788	0.30	( 0.26)	0.86	22014.2	390.00
8	25685.22	87.52	0.716	0.30	( 0.27)	0.88	28641.9	13100.00
9	25977.40	94.37	0.692	0.30	( 0.27)	0.89	31256.0	11801.00
10	27298.99	112.13	0.641	0.30	( 0.27)	0.91	39796.9	13510.00
11	27952.50	119.13	0.621	0.30	( 0.27)	0.92	43789.4	13010.00
12	28675.29	124.98	0.611	0.30	( 0.28)	0.92	47464.4	11330.00
13	29238.41	133.02	0.597	0.30	( 0.28)	0.93	52551.5	10630.00
14	28967.81	138.65	0.587	0.30	( 0.28)	0.93	55141.4	12330.00
15	28687.46	145.32	0.576	0.30	( 0.28)	0.94	58283.8	11600.00
16	28290.32	151.18	0.566	0.30	( 0.28)	0.94	60518.2	11111.00
17	27853.98	157.40	0.555	0.30	( 0.28)	0.94	62452.0	12201.00
18	26907.91	166.55	0.540	0.30	( 0.28)	0.94	64540.3	12231.00
19	26044.75	174.24	0.527	0.30	( 0.28)	0.94	65951.8	10400.00
20	24674.38	186.00	0.512	0.30	( 0.28)	0.94	67572.6	10320.00
21	23387.88	196.09	0.505	0.30	( 0.28)	0.94	67960.4	12000.00
22	20401.83	226.24	0.481	0.30	( 0.28)	0.94	68577.4	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 29238.41 Tc(MIN.) = 133.02  
EFFECTIVE AREA(ACRES) = 52551.54 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA(ACRES) = 68577.4  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13840.00 = 132804.30 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13840.00 TO NODE 13860.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 133.00 DOWNSTREAM(FEET) = 130.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 654.44 CHANNEL SLOPE = 0.0046  
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 12.87  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.596

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	6.61	0.30	0.975	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.975  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 29239.31  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 15.00  
AVERAGE FLOW DEPTH(FEET) = 12.87 TRAVEL TIME(MIN.) = 0.73  
Tc(MIN.) = 133.75  
SUBAREA AREA(ACRES) = 6.61 SUBAREA RUNOFF(CFS) = 1.80  
EFFECTIVE AREA(ACRES) = 52558.14 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA(ACRES) = 68584.0 PEAK FLOW RATE(CFS) = 29238.41  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 12.87

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 12.87 FLOW VELOCITY(FEET/SEC.) = 15.00  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13860.00 = 133458.73 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE	
1	15395.14	25.02	1.379	0.30	( 0.25)	0.83	4422.2	13810.00
2	15730.67	27.37	1.314	0.30	( 0.25)	0.83	4871.8	10400.00
3	18564.17	38.62	1.084	0.30	( 0.25)	0.83	8212.5	13830.00
4	19159.96	41.11	1.046	0.30	( 0.25)	0.83	8913.8	410.00
5	20564.75	48.65	0.957	0.30	( 0.25)	0.83	11356.5	100.00
6	22076.91	57.87	0.871	0.30	( 0.25)	0.84	15095.9	150.00
7	24369.31	73.78	0.784	0.30	( 0.26)	0.86	22020.8	390.00
8	25685.22	88.27	0.713	0.30	( 0.27)	0.88	28648.5	13100.00
9	25977.40	95.13	0.689	0.30	( 0.27)	0.89	31262.6	11801.00
10	27298.99	112.87	0.639	0.30	( 0.27)	0.91	39803.5	13510.00
11	27952.50	119.87	0.619	0.30	( 0.27)	0.92	43796.0	13010.00
12	28675.29	125.72	0.609	0.30	( 0.28)	0.92	47471.0	11330.00
13	29238.41	133.75	0.596	0.30	( 0.28)	0.93	52558.1	10630.00
14	28967.81	139.38	0.586	0.30	( 0.28)	0.93	55148.0	12330.00
15	28687.46	146.06	0.575	0.30	( 0.28)	0.94	58290.5	11600.00
16	28290.32	151.91	0.565	0.30	( 0.28)	0.94	60524.8	11111.00
17	27853.98	158.14	0.554	0.30	( 0.28)	0.94	62458.6	12201.00
18	26907.91	167.29	0.539	0.30	( 0.28)	0.94	64546.9	12231.00
19	26044.75	174.99	0.526	0.30	( 0.28)	0.94	65958.4	10400.00
20	24674.38	186.77	0.512	0.30	( 0.28)	0.94	67579.2	10320.00
21	23387.88	196.87	0.504	0.30	( 0.28)	0.94	67967.0	12000.00
22	20401.83	227.05	0.481	0.30	( 0.28)	0.94	68584.0	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 29238.41 Tc(MIN.) = 133.75  
AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 52558.14

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13840.00 TO NODE 13860.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
 TIME OF CONCENTRATION(MIN.) = 133.75  
 RAINFALL INTENSITY(INCH/HR) = 0.60  
 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93  
 EFFECTIVE STREAM AREA(ACRES) = 52558.14  
 TOTAL STREAM AREA(ACRES) = 68584.01  
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 29238.41

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13850.00 TO NODE 13851.00 IS CODE = 21  
 -----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<  
 -----  
 INITIAL SUBAREA FLOW-LENGTH(FEET) = 617.57  
 ELEVATION DATA: UPSTREAM(FEET) = 646.95 DOWNSTREAM(FEET) = 490.10

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
 SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 12.137  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.206  
 SUBAREA Tc AND LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	-	4.95	0.30	1.000	56	12.14

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA RUNOFF(CFS) = 8.49  
 TOTAL AREA(ACRES) = 4.95 PEAK FLOW RATE(CFS) = 8.49

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13851.00 TO NODE 13851.50 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 -----

ELEVATION DATA: UPSTREAM(FEET) = 490.10 DOWNSTREAM(FEET) = 440.98  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 351.14 CHANNEL SLOPE = 0.1399  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.29  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.015  
 SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	4.02	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 11.59  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.85  
 AVERAGE FLOW DEPTH(FEET) = 0.29 TRAVEL TIME(MIN.) = 1.52  
 Tc(MIN.) = 13.66  
 SUBAREA AREA(ACRES) = 4.02 SUBAREA RUNOFF(CFS) = 6.20  
 EFFECTIVE AREA(ACRES) = 8.97 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 9.0 PEAK FLOW RATE(CFS) = 13.84  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.32  
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 0.32 FLOW VELOCITY(FEET/SEC.) = 4.10  
 LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13851.50 = 968.71 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13851.50 TO NODE 13852.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 -----

ELEVATION DATA: UPSTREAM(FEET) = 440.98 DOWNSTREAM(FEET) = 395.76  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 512.91 CHANNEL SLOPE = 0.0882  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.45  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.803  
 SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.17	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 18.69  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.98  
 AVERAGE FLOW DEPTH(FEET) = 0.43 TRAVEL TIME(MIN.) = 2.15  
 Tc(MIN.) = 15.80  
 SUBAREA AREA(ACRES) = 7.17 SUBAREA RUNOFF(CFS) = 9.70  
 EFFECTIVE AREA(ACRES) = 16.14 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 16.1 PEAK FLOW RATE(CFS) = 21.83  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.48

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 0.48 FLOW VELOCITY(FEET/SEC.) = 4.19  
 LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13852.00 = 1481.62 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13852.00 TO NODE 13853.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 -----

ELEVATION DATA: UPSTREAM(FEET) = 395.76 DOWNSTREAM(FEET) = 354.94  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 443.69 CHANNEL SLOPE = 0.0920  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.52  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.715  
 SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	4.02	0.30	1.000	-

```

USER-DEFINED          -      6.76      0.30      1.000      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 26.14
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.52
AVERAGE FLOW DEPTH(FEET) = 0.52 TRAVEL TIME(MIN.) = 1.64
Tc(MIN.) = 17.44
SUBAREA AREA(ACRES) = 6.76 SUBAREA RUNOFF(CFS) = 8.61
EFFECTIVE AREA(ACRES) = 22.90 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 22.9 PEAK FLOW RATE(CFS) = 29.17
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.56

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.56 FLOW VELOCITY(FEET/SEC.) = 4.69
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13853.00 = 1925.31 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13853.00 TO NODE 13854.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<

```

```

=====
ELEVATION DATA: UPSTREAM(FEET) = 354.94 DOWNSTREAM(FEET) = 263.57
CHANNEL LENGTH THRU SUBAREA(FEET) = 962.09 CHANNEL SLOPE = 0.0950
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.67
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.559
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/    SCS SOIL  AREA    Fp      Ap    SCS
  LAND USE          GROUP  (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED        -      18.16    0.30    1.000    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 39.46
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.29
AVERAGE FLOW DEPTH(FEET) = 0.66 TRAVEL TIME(MIN.) = 3.03
Tc(MIN.) = 20.47
SUBAREA AREA(ACRES) = 18.16 SUBAREA RUNOFF(CFS) = 20.58
EFFECTIVE AREA(ACRES) = 41.06 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 41.1 PEAK FLOW RATE(CFS) = 46.54
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.73

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.73 FLOW VELOCITY(FEET/SEC.) = 5.58
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13854.00 = 2887.40 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13854.00 TO NODE 13855.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<

```

```

=====
ELEVATION DATA: UPSTREAM(FEET) = 263.57 DOWNSTREAM(FEET) = 188.74
CHANNEL LENGTH THRU SUBAREA(FEET) = 1228.77 CHANNEL SLOPE = 0.0609
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.03
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.409
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/    SCS SOIL  AREA    Fp      Ap    SCS
  LAND USE          GROUP  (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED        -      38.75    0.30    0.879    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.879
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 66.54
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.43
AVERAGE FLOW DEPTH(FEET) = 1.02 TRAVEL TIME(MIN.) = 3.77
Tc(MIN.) = 24.24
SUBAREA AREA(ACRES) = 38.75 SUBAREA RUNOFF(CFS) = 39.95
EFFECTIVE AREA(ACRES) = 79.81 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94
TOTAL AREA(ACRES) = 79.8 PEAK FLOW RATE(CFS) = 80.95
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.13

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.13 FLOW VELOCITY(FEET/SEC.) = 5.82
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13855.00 = 4116.17 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 31
-----

```

```

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<

```

```

=====
ELEVATION DATA: UPSTREAM(FEET) = 188.74 DOWNSTREAM(FEET) = 130.00
FLOW LENGTH(FEET) = 2092.67 MANNING'S N = 0.013
ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000
DEPTH OF FLOW IN 36.0 INCH PIPE IS 23.6 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 16.52
ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 80.95
PIPE TRAVEL TIME(MIN.) = 2.11 Tc(MIN.) = 26.35
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13860.00 = 6208.84 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

```

```

=====
MAINLINE Tc(MIN.) = 26.35
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.342
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/    SCS SOIL  AREA    Fp      Ap    SCS
  LAND USE          GROUP  (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED        -      43.41    0.30    0.707    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.707

```

SUBAREA AREA (ACRES) = 43.41 SUBAREA RUNOFF (CFS) = 44.14  
 EFFECTIVE AREA (ACRES) = 123.22 AREA-AVERAGED Fm (INCH/HR) = 0.26  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.86  
 TOTAL AREA (ACRES) = 123.2 PEAK FLOW RATE (CFS) = 120.26

\*\*\*\*\*

FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
 TIME OF CONCENTRATION (MIN.) = 26.35  
 RAINFALL INTENSITY (INCH/HR) = 1.34  
 AREA-AVERAGED Fm (INCH/HR) = 0.26  
 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.86  
 EFFECTIVE STREAM AREA (ACRES) = 123.22  
 TOTAL STREAM AREA (ACRES) = 123.22  
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 120.26

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15395.14	25.02	1.379	0.30 ( 0.25)	0.83	4422.2	13810.00
1	15730.67	27.37	1.314	0.30 ( 0.25)	0.83	4871.8	10400.00
1	18564.17	38.62	1.084	0.30 ( 0.25)	0.83	8212.5	13830.00
1	19159.96	41.11	1.046	0.30 ( 0.25)	0.83	8913.8	410.00
1	20564.75	48.65	0.957	0.30 ( 0.25)	0.83	11356.5	100.00
1	22076.91	57.87	0.871	0.30 ( 0.25)	0.84	15095.9	150.00
1	24369.31	73.78	0.784	0.30 ( 0.26)	0.86	22020.8	390.00
1	25685.22	88.27	0.713	0.30 ( 0.27)	0.88	28648.5	13100.00
1	25977.40	95.13	0.689	0.30 ( 0.27)	0.89	31262.6	11801.00
1	27298.99	112.87	0.639	0.30 ( 0.27)	0.91	39803.5	13510.00
1	27952.50	119.87	0.619	0.30 ( 0.27)	0.92	43796.0	13010.00
1	28675.29	125.72	0.609	0.30 ( 0.28)	0.92	47471.0	11330.00
1	29238.41	133.75	0.596	0.30 ( 0.28)	0.93	52558.1	10630.00
1	28967.81	139.38	0.586	0.30 ( 0.28)	0.93	55148.0	12330.00
1	28687.46	146.06	0.575	0.30 ( 0.28)	0.94	58290.5	11600.00
1	28290.32	151.91	0.565	0.30 ( 0.28)	0.94	60524.8	11111.00
1	27853.98	158.14	0.554	0.30 ( 0.28)	0.94	62458.6	12201.00
1	26907.91	167.29	0.539	0.30 ( 0.28)	0.94	64546.9	12231.00
1	26044.75	174.99	0.526	0.30 ( 0.28)	0.94	65958.4	10400.00
1	24674.38	186.77	0.512	0.30 ( 0.28)	0.94	67579.2	10320.00
1	23387.88	196.87	0.504	0.30 ( 0.28)	0.94	67967.0	12000.00
1	20401.83	227.05	0.481	0.30 ( 0.28)	0.94	68584.0	10100.00
2	120.26	26.35	1.342	0.30 ( 0.26)	0.86	123.2	13850.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15513.15	25.02	1.379	0.30 ( 0.25)	0.83	4539.2	13810.00
2	15705.62	26.35	1.342	0.30 ( 0.25)	0.83	4800.3	13850.00
3	15847.82	27.37	1.314	0.30 ( 0.25)	0.83	4995.0	10400.00

4	18655.85	38.62	1.084	0.30 ( 0.25)	0.83	8335.7	13830.00
5	19247.38	41.11	1.046	0.30 ( 0.25)	0.83	9037.1	410.00
6	20642.31	48.65	0.957	0.30 ( 0.25)	0.83	11479.7	100.00
7	22144.94	57.87	0.871	0.30 ( 0.25)	0.84	15219.1	150.00
8	24427.69	73.78	0.784	0.30 ( 0.26)	0.86	22144.1	390.00
9	25735.67	88.27	0.713	0.30 ( 0.27)	0.88	28771.7	13100.00
10	26025.30	95.13	0.689	0.30 ( 0.27)	0.89	31385.8	11801.00
11	27341.32	112.87	0.639	0.30 ( 0.27)	0.91	39926.7	13510.00
12	27992.63	119.87	0.619	0.30 ( 0.27)	0.92	43919.3	13010.00
13	28714.29	125.72	0.609	0.30 ( 0.28)	0.92	47594.2	11330.00
14	29275.90	133.75	0.596	0.30 ( 0.28)	0.93	52681.4	10630.00
15	29004.24	139.38	0.586	0.30 ( 0.28)	0.93	55271.2	12330.00
16	28722.63	146.06	0.575	0.30 ( 0.28)	0.94	58413.7	11600.00
17	28324.38	151.91	0.565	0.30 ( 0.28)	0.94	60648.0	11111.00
18	27886.87	158.14	0.554	0.30 ( 0.28)	0.94	62581.9	12201.00
19	26939.08	167.29	0.539	0.30 ( 0.28)	0.94	64670.1	12231.00
20	26074.46	174.99	0.526	0.30 ( 0.28)	0.94	66081.7	10400.00
21	24702.57	186.77	0.512	0.30 ( 0.28)	0.94	67702.4	10320.00
22	23415.21	196.87	0.504	0.30 ( 0.28)	0.94	68090.2	12000.00
23	20426.57	227.05	0.481	0.30 ( 0.28)	0.94	68707.2	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 29275.90 Tc (MIN.) = 133.75  
 EFFECTIVE AREA (ACRES) = 52681.36 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 68707.2  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13860.00 = 133458.73 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13860.00 TO NODE 13880.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 130.00 DOWNSTREAM (FEET) = 120.57  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 610.77 CHANNEL SLOPE = 0.0154  
 GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 9.29  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 0.595

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	4.89	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 29276.55  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 22.98  
 AVERAGE FLOW DEPTH (FEET) = 9.29 TRAVEL TIME (MIN.) = 0.44  
 Tc (MIN.) = 134.19

SUBAREA AREA (ACRES) = 4.89 SUBAREA RUNOFF (CFS) = 1.30  
 EFFECTIVE AREA (ACRES) = 52686.25 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 68712.1 PEAK FLOW RATE (CFS) = 29275.90  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 9.29

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 9.29 FLOW VELOCITY(FEET/SEC.) = 22.98  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13880.00 = 134069.50 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15513.15	25.56	1.364	0.30 ( 0.25)	0.83	4544.1	13810.00
2	15705.62	26.89	1.327	0.30 ( 0.25)	0.83	4805.2	13850.00
3	15847.82	27.91	1.299	0.30 ( 0.25)	0.83	4999.9	10400.00
4	18655.85	39.13	1.075	0.30 ( 0.25)	0.83	8340.6	13830.00
5	19247.38	41.61	1.040	0.30 ( 0.25)	0.83	9042.0	410.00
6	20642.31	49.14	0.951	0.30 ( 0.25)	0.83	11484.6	100.00
7	22144.94	58.35	0.867	0.30 ( 0.25)	0.84	15224.0	150.00
8	24427.69	74.25	0.782	0.30 ( 0.26)	0.86	22148.9	390.00
9	25735.67	88.74	0.710	0.30 ( 0.27)	0.88	28776.6	13100.00
10	26025.30	95.59	0.688	0.30 ( 0.27)	0.89	31390.7	11801.00
11	27341.32	113.32	0.638	0.30 ( 0.27)	0.91	39931.6	13510.00
12	27992.63	120.31	0.618	0.30 ( 0.27)	0.92	43924.1	13010.00
13	28714.29	126.16	0.609	0.30 ( 0.28)	0.92	47599.1	11330.00
14	29275.90	134.19	0.595	0.30 ( 0.28)	0.93	52686.3	10630.00
15	29004.24	139.83	0.585	0.30 ( 0.28)	0.93	55276.1	12330.00
16	28722.63	146.50	0.574	0.30 ( 0.28)	0.94	58418.6	11600.00
17	28324.38	152.36	0.564	0.30 ( 0.28)	0.94	60652.9	11111.00
18	27886.87	158.59	0.553	0.30 ( 0.28)	0.94	62586.7	12201.00
19	26939.08	167.75	0.538	0.30 ( 0.28)	0.94	64675.0	12231.00
20	26074.46	175.45	0.525	0.30 ( 0.28)	0.94	66086.5	10400.00
21	24702.57	187.23	0.511	0.30 ( 0.28)	0.94	67707.3	10320.00
22	23415.21	197.34	0.504	0.30 ( 0.28)	0.94	68095.1	12000.00
23	20426.57	227.54	0.480	0.30 ( 0.28)	0.94	68712.1	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 29275.90 Tc(MIN.) = 134.19  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 52686.25

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13860.00 TO NODE 13880.00 IS CODE = 1  
 -----

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

-----  
 TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
 TIME OF CONCENTRATION(MIN.) = 134.19  
 RAINFALL INTENSITY(INCH/HR) = 0.59  
 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93  
 EFFECTIVE STREAM AREA(ACRES) = 52686.25  
 TOTAL STREAM AREA(ACRES) = 68712.12  
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 29275.90

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13870.00 TO NODE 13871.00 IS CODE = 21  
 -----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<  
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH(FEET) = 872.65  
 ELEVATION DATA: UPSTREAM(FEET) = 558.52 DOWNSTREAM(FEET) = 436.47

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
 SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 15.704  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.808

SUBAREA Tc AND LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)  
 NATURAL FAIR COVER  
 "GRASS" - 7.32 0.30 1.000 56 15.70  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA RUNOFF(CFS) = 9.94  
 TOTAL AREA(ACRES) = 7.32 PEAK FLOW RATE(CFS) = 9.94

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13871.00 TO NODE 13872.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<

-----  
 ELEVATION DATA: UPSTREAM(FEET) = 436.47 DOWNSTREAM(FEET) = 337.62  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 827.95 CHANNEL SLOPE = 0.1194  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.40  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.635

SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 13.01 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 17.77  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.27  
 AVERAGE FLOW DEPTH(FEET) = 0.39 TRAVEL TIME(MIN.) = 3.23  
 Tc(MIN.) = 18.93  
 SUBAREA AREA(ACRES) = 13.01 SUBAREA RUNOFF(CFS) = 15.63  
 EFFECTIVE AREA(ACRES) = 20.33 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 20.3 PEAK FLOW RATE(CFS) = 24.43  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.46

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 0.46 FLOW VELOCITY(FEET/SEC.) = 4.83  
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13872.00 = 1700.60 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13872.00 TO NODE 13873.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<

-----  
 ELEVATION DATA: UPSTREAM(FEET) = 337.62 DOWNSTREAM(FEET) = 253.88  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1049.16 CHANNEL SLOPE = 0.0798

GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 0.74  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.485  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	32.99	0.30	0.923	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.923  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 42.38  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.13  
 AVERAGE FLOW DEPTH (FEET) = 0.72 TRAVEL TIME (MIN.) = 3.41  
 Tc (MIN.) = 22.34  
 SUBAREA AREA (ACRES) = 32.99 SUBAREA RUNOFF (CFS) = 35.86  
 EFFECTIVE AREA (ACRES) = 53.32 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95  
 TOTAL AREA (ACRES) = 53.3 PEAK FLOW RATE (CFS) = 57.54  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 0.86

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 0.86 FLOW VELOCITY (FEET/SEC.) = 5.67  
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13873.00 = 2749.76 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13873.00 TO NODE 13874.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 253.88 DOWNSTREAM (FEET) = 160.73  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1518.60 CHANNEL SLOPE = 0.0613  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 0.86  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.358  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	30.94	0.30	0.900	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.900  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 72.69  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.37  
 AVERAGE FLOW DEPTH (FEET) = 0.84 TRAVEL TIME (MIN.) = 3.43  
 Tc (MIN.) = 25.78  
 SUBAREA AREA (ACRES) = 30.94 SUBAREA RUNOFF (CFS) = 30.29  
 EFFECTIVE AREA (ACRES) = 84.26 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 84.3 PEAK FLOW RATE (CFS) = 81.74  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 0.90

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 0.90 FLOW VELOCITY (FEET/SEC.) = 7.67

LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13874.00 = 4268.36 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13874.00 TO NODE 13875.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 160.73 DOWNSTREAM (FEET) = 158.14  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 582.74 CHANNEL SLOPE = 0.0044  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 2.31  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.281  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	73.67	0.30	0.930	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.930  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 114.96  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 3.46  
 AVERAGE FLOW DEPTH (FEET) = 2.28 TRAVEL TIME (MIN.) = 2.81  
 Tc (MIN.) = 28.59  
 SUBAREA AREA (ACRES) = 73.67 SUBAREA RUNOFF (CFS) = 66.42  
 EFFECTIVE AREA (ACRES) = 157.93 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 157.9 PEAK FLOW RATE (CFS) = 142.31  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 2.56

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 2.56 FLOW VELOCITY (FEET/SEC.) = 3.68  
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13875.00 = 4851.10 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 158.14 DOWNSTREAM (FEET) = 120.57  
 FLOW LENGTH (FEET) = 1855.67 MANNING'S N = 0.013  
 DEPTH OF FLOW IN 45.0 INCH PIPE IS 32.5 INCHES  
 PIPE-FLOW VELOCITY (FEET/SEC.) = 16.65  
 ESTIMATED PIPE DIAMETER (INCH) = 45.00 NUMBER OF PIPES = 1  
 PIPE-FLOW (CFS) = 142.31  
 PIPE TRAVEL TIME (MIN.) = 1.86 Tc (MIN.) = 30.45  
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13880.00 = 6706.77 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 MAINLINE Tc (MIN.) = 30.45  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.234



SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	34.90	0.30	0.743	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.743  
 SUBAREA AREA(ACRES) = 34.90 SUBAREA RUNOFF(CFS) = 31.76  
 EFFECTIVE AREA(ACRES) = 192.83 AREA-AVERAGED Fm(INCH/HR) = 0.27  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.90  
 TOTAL AREA(ACRES) = 192.8 PEAK FLOW RATE(CFS) = 167.41

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
 TIME OF CONCENTRATION(MIN.) = 30.45  
 RAINFALL INTENSITY(INCH/HR) = 1.23  
 AREA-AVERAGED Fm(INCH/HR) = 0.27  
 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.90  
 EFFECTIVE STREAM AREA(ACRES) = 192.83  
 TOTAL STREAM AREA(ACRES) = 192.83  
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 167.41

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15513.15	25.56	1.364	0.30( 0.25)	0.83	4544.1	13810.00
1	15705.62	26.89	1.327	0.30( 0.25)	0.83	4805.2	13850.00
1	15847.82	27.91	1.299	0.30( 0.25)	0.83	4999.9	10400.00
1	18655.85	39.13	1.075	0.30( 0.25)	0.83	8340.6	13830.00
1	19247.38	41.61	1.040	0.30( 0.25)	0.83	9042.0	410.00
1	20642.31	49.14	0.951	0.30( 0.25)	0.83	11484.6	100.00
1	22144.94	58.35	0.867	0.30( 0.25)	0.84	15224.0	150.00
1	24427.69	74.25	0.782	0.30( 0.26)	0.86	22148.9	390.00
1	25735.67	88.74	0.710	0.30( 0.27)	0.88	28776.6	13100.00
1	26025.30	95.59	0.688	0.30( 0.27)	0.89	31390.7	11801.00
1	27341.32	113.32	0.638	0.30( 0.27)	0.91	39931.6	13510.00
1	27992.63	120.31	0.618	0.30( 0.27)	0.92	43924.1	13010.00
1	28714.29	126.16	0.609	0.30( 0.28)	0.92	47599.1	11330.00
1	29275.90	134.19	0.595	0.30( 0.28)	0.93	52686.3	10630.00
1	29004.24	139.83	0.585	0.30( 0.28)	0.93	55276.1	12330.00
1	28722.63	146.50	0.574	0.30( 0.28)	0.94	58418.6	11600.00
1	28324.38	152.36	0.564	0.30( 0.28)	0.94	60652.9	11111.00
1	27886.87	158.59	0.553	0.30( 0.28)	0.94	62586.7	12201.00
1	26939.08	167.75	0.538	0.30( 0.28)	0.94	64675.0	12231.00
1	26074.46	175.45	0.525	0.30( 0.28)	0.94	66086.5	10400.00
1	24702.57	187.23	0.511	0.30( 0.28)	0.94	67707.3	10320.00
1	23415.21	197.34	0.504	0.30( 0.28)	0.94	68095.1	12000.00
1	20426.57	227.54	0.480	0.30( 0.28)	0.94	68712.1	10100.00
2	167.41	30.45	1.234	0.30( 0.27)	0.90	192.8	13870.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15672.61	25.56	1.364	0.30( 0.25)	0.84	4705.9	13810.00
2	15867.79	26.89	1.327	0.30( 0.25)	0.84	4975.5	13850.00
3	16011.70	27.91	1.299	0.30( 0.25)	0.84	5176.7	10400.00
4	16649.90	30.45	1.234	0.30( 0.25)	0.83	5947.8	13870.00
5	18795.68	39.13	1.075	0.30( 0.25)	0.83	8533.4	13830.00
6	19381.15	41.61	1.040	0.30( 0.25)	0.83	9234.8	410.00
7	20760.65	49.14	0.951	0.30( 0.25)	0.83	11677.4	100.00
8	22248.63	58.35	0.867	0.30( 0.25)	0.84	15416.8	150.00
9	24516.63	74.25	0.782	0.30( 0.26)	0.86	22341.8	390.00
10	25812.21	88.74	0.710	0.30( 0.27)	0.88	28969.4	13100.00
11	26098.01	95.59	0.688	0.30( 0.27)	0.89	31583.5	11801.00
12	27405.31	113.32	0.638	0.30( 0.27)	0.91	40124.4	13510.00
13	28053.24	120.31	0.618	0.30( 0.27)	0.92	44117.0	13010.00
14	28773.18	126.16	0.609	0.30( 0.28)	0.92	47791.9	11330.00
15	29332.42	134.19	0.595	0.30( 0.28)	0.93	52879.1	10630.00
16	29059.10	139.83	0.585	0.30( 0.28)	0.93	55468.9	12330.00
17	28775.52	146.50	0.574	0.30( 0.28)	0.94	58611.4	11600.00
18	28375.54	152.36	0.564	0.30( 0.28)	0.94	60845.7	11111.00
19	27936.20	158.59	0.553	0.30( 0.28)	0.94	62779.6	12201.00
20	26985.70	167.75	0.538	0.30( 0.28)	0.94	64867.8	12231.00
21	26118.81	175.45	0.525	0.30( 0.28)	0.94	66279.4	10400.00
22	24744.61	187.23	0.511	0.30( 0.28)	0.94	67900.1	10320.00
23	23455.89	197.34	0.504	0.30( 0.28)	0.94	68287.9	12000.00
24	20463.21	227.54	0.480	0.30( 0.28)	0.94	68904.9	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 29332.42 Tc(MIN.) = 134.19  
 EFFECTIVE AREA(ACRES) = 52879.08 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 68904.9  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13880.00 = 134069.50 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13880.00 TO NODE 13910.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 120.57 DOWNSTREAM(FEET) = 119.70  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1190.21 CHANNEL SLOPE = 0.0007  
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 20.69  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.591

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	117.69	0.30	0.724	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.724  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 29352.20  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.77  
 AVERAGE FLOW DEPTH(FEET) = 20.68 TRAVEL TIME(MIN.) = 2.55  
 Tc(MIN.) = 136.74

SUBAREA AREA (ACRES) = 117.69 SUBAREA RUNOFF (CFS) = 39.55  
 EFFECTIVE AREA (ACRES) = 52996.77 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 69022.6 PEAK FLOW RATE (CFS) = 29332.42  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 20.67

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 20.67 FLOW VELOCITY (FEET/SEC.) = 7.77  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13910.00 = 135259.70 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15672.61	28.60	1.280	0.30 ( 0.25)	0.83	4823.6	13810.00
2	15867.79	29.92	1.244	0.30 ( 0.25)	0.83	5093.2	13850.00
3	16011.70	30.93	1.225	0.30 ( 0.25)	0.83	5294.4	10400.00
4	16649.90	33.43	1.179	0.30 ( 0.25)	0.83	6065.5	13870.00
5	18795.68	42.02	1.035	0.30 ( 0.25)	0.83	8651.1	13830.00
6	19381.15	44.48	1.006	0.30 ( 0.25)	0.83	9352.5	410.00
7	20760.65	51.95	0.924	0.30 ( 0.25)	0.83	11795.1	100.00
8	22248.63	61.11	0.847	0.30 ( 0.25)	0.84	15534.5	150.00
9	24516.63	76.93	0.768	0.30 ( 0.26)	0.86	22459.5	390.00
10	25812.21	91.38	0.700	0.30 ( 0.27)	0.88	29087.1	13100.00
11	26098.01	98.22	0.681	0.30 ( 0.27)	0.89	31701.2	11801.00
12	27405.31	115.92	0.631	0.30 ( 0.27)	0.91	40242.1	13510.00
13	28053.24	122.90	0.614	0.30 ( 0.27)	0.92	44234.7	13010.00
14	28773.18	128.73	0.604	0.30 ( 0.28)	0.92	47909.6	11330.00
15	29332.42	136.74	0.591	0.30 ( 0.28)	0.93	52996.8	10630.00
16	29059.10	142.39	0.581	0.30 ( 0.28)	0.93	55586.6	12330.00
17	28775.52	149.07	0.570	0.30 ( 0.28)	0.93	58729.1	11600.00
18	28375.54	154.94	0.560	0.30 ( 0.28)	0.94	60963.4	11111.00
19	27936.20	161.18	0.549	0.30 ( 0.28)	0.94	62897.3	12201.00
20	26985.70	170.36	0.533	0.30 ( 0.28)	0.94	64985.5	12231.00
21	26118.81	178.09	0.520	0.30 ( 0.28)	0.94	66397.1	10400.00
22	24744.61	189.91	0.509	0.30 ( 0.28)	0.94	68017.8	10320.00
23	23455.89	200.06	0.502	0.30 ( 0.28)	0.94	68405.6	12000.00
24	20463.21	230.37	0.478	0.30 ( 0.28)	0.94	69022.6	10100.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE (CFS) = 29332.42 Tc (MIN.) = 136.74  
 AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA (ACRES) = 52996.77

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13880.00 TO NODE 13910.00 IS CODE = 1  
 -----

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

-----  
 TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
 TIME OF CONCENTRATION (MIN.) = 136.74  
 RAINFALL INTENSITY (INCH/HR) = 0.59  
 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93  
 EFFECTIVE STREAM AREA (ACRES) = 52996.77

TOTAL STREAM AREA (ACRES) = 69022.63  
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 29332.42

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13889.00 TO NODE 13890.00 IS CODE = 21  
 -----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<

>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

-----  
 INITIAL SUBAREA FLOW-LENGTH (FEET) = 447.89  
 ELEVATION DATA: UPSTREAM (FEET) = 564.89 DOWNSTREAM (FEET) = 421.92

Tc = K \* [(LENGTH\*\* 3.00) / (ELEVATION CHANGE)]\*\* 0.20  
 SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 6.976  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 3.215

SUBAREA Tc AND LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)  
 PUBLIC PARK - 3.03 0.30 0.960 56 6.98  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.960  
 SUBAREA RUNOFF (CFS) = 7.98  
 TOTAL AREA (ACRES) = 3.03 PEAK FLOW RATE (CFS) = 7.98

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13890.00 TO NODE 13891.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

-----  
 ELEVATION DATA: UPSTREAM (FEET) = 421.92 DOWNSTREAM (FEET) = 392.64  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 435.33 CHANNEL SLOPE = 0.0673  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 0.37  
 \* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 2.825

SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 8.12 0.30 0.986 -

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.986  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 17.27  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.56  
 AVERAGE FLOW DEPTH (FEET) = 0.35 TRAVEL TIME (MIN.) = 1.59  
 Tc (MIN.) = 8.57

SUBAREA AREA (ACRES) = 8.12 SUBAREA RUNOFF (CFS) = 18.49  
 EFFECTIVE AREA (ACRES) = 11.15 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98  
 TOTAL AREA (ACRES) = 11.1 PEAK FLOW RATE (CFS) = 25.41  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 0.45

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 0.45 FLOW VELOCITY (FEET/SEC.) = 5.24  
 LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13891.00 = 883.22 FEET.

```

*****
FLOW PROCESS FROM NODE 13891.00 TO NODE 13892.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 392.64 DOWNSTREAM(FEET) = 324.46
CHANNEL LENGTH THRU SUBAREA(FEET) = 662.40 CHANNEL SLOPE = 0.1029
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.51
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.455
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 12.50 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 37.55
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.93
AVERAGE FLOW DEPTH(FEET) = 0.49 TRAVEL TIME(MIN.) = 1.59
Tc(MIN.) = 10.16
SUBAREA AREA(ACRES) = 12.50 SUBAREA RUNOFF(CFS) = 24.24
EFFECTIVE AREA(ACRES) = 23.65 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 23.6 PEAK FLOW RATE(CFS) = 45.93
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.55

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.55 FLOW VELOCITY(FEET/SEC.) = 7.46
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13892.00 = 1545.62 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13892.00 TO NODE 13893.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 324.46 DOWNSTREAM(FEET) = 240.82
CHANNEL LENGTH THRU SUBAREA(FEET) = 980.03 CHANNEL SLOPE = 0.0853
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.70
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.187
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 15.87 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 59.42
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.67
AVERAGE FLOW DEPTH(FEET) = 0.68 TRAVEL TIME(MIN.) = 2.13
Tc(MIN.) = 12.29
SUBAREA AREA(ACRES) = 15.87 SUBAREA RUNOFF(CFS) = 26.95
EFFECTIVE AREA(ACRES) = 39.52 AREA-AVERAGED Fm(INCH/HR) = 0.30

```

```

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 39.5 PEAK FLOW RATE(CFS) = 67.18
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.74

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.74 FLOW VELOCITY(FEET/SEC.) = 7.97
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13893.00 = 2525.65 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13893.00 TO NODE 13894.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 240.82 DOWNSTREAM(FEET) = 163.04
CHANNEL LENGTH THRU SUBAREA(FEET) = 1144.35 CHANNEL SLOPE = 0.0680
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.94
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.891
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 28.41 0.30 0.985 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.985
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 87.63
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.12
AVERAGE FLOW DEPTH(FEET) = 0.91 TRAVEL TIME(MIN.) = 2.35
Tc(MIN.) = 14.64
SUBAREA AREA(ACRES) = 28.41 SUBAREA RUNOFF(CFS) = 40.81
EFFECTIVE AREA(ACRES) = 67.93 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 67.9 PEAK FLOW RATE(CFS) = 97.48
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.97

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.97 FLOW VELOCITY(FEET/SEC.) = 8.40
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13894.00 = 3670.00 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 31
-----
>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 163.04 DOWNSTREAM(FEET) = 119.70
FLOW LENGTH(FEET) = 1899.01 MANNING'S N = 0.013
DEPTH OF FLOW IN 39.0 INCH PIPE IS 27.0 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 15.93
ESTIMATED PIPE DIAMETER(INCH) = 39.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 97.48
PIPE TRAVEL TIME(MIN.) = 1.99 Tc(MIN.) = 16.63
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13910.00 = 5569.01 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 16.63
* 10 YEAR RAINFALL INTENSITY (INCH/HR) = 1.759
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp      Ap      SCS
LAND USE                GROUP  (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED            -      11.69    0.30    0.634    -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.634
SUBAREA AREA(ACRES) = 11.69      SUBAREA RUNOFF(CFS) = 16.50
EFFECTIVE AREA(ACRES) = 79.62    AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30  AREA-AVERAGED Ap = 0.94
TOTAL AREA(ACRES) = 79.6        PEAK FLOW RATE(CFS) = 105.88

```

```

*****
FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 1
-----
>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<
=====
TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 16.63
RAINFALL INTENSITY (INCH/HR) = 1.76
AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.94
EFFECTIVE STREAM AREA(ACRES) = 79.62
TOTAL STREAM AREA(ACRES) = 79.62
PEAK FLOW RATE(CFS) AT CONFLUENCE = 105.88

```

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	15672.61	28.60	1.280	0.30( 0.25)	0.83	4823.6	13810.00
1	15867.79	29.92	1.244	0.30( 0.25)	0.83	5093.2	13850.00
1	16011.70	30.93	1.225	0.30( 0.25)	0.83	5294.4	10400.00
1	16649.90	33.43	1.179	0.30( 0.25)	0.83	6065.5	13870.00
1	18795.68	42.02	1.035	0.30( 0.25)	0.83	8651.1	13830.00
1	19381.15	44.48	1.006	0.30( 0.25)	0.83	9352.5	410.00
1	20760.65	51.95	0.924	0.30( 0.25)	0.83	11795.1	100.00
1	22248.63	61.11	0.847	0.30( 0.25)	0.84	15534.5	150.00
1	24516.63	76.93	0.768	0.30( 0.26)	0.86	22459.5	390.00
1	25812.21	91.38	0.700	0.30( 0.27)	0.88	29087.1	13100.00
1	26098.01	98.22	0.681	0.30( 0.27)	0.89	31701.2	11801.00
1	27405.31	115.92	0.631	0.30( 0.27)	0.91	40242.1	13510.00
1	28053.24	122.90	0.614	0.30( 0.27)	0.92	44234.7	13010.00
1	28773.18	128.73	0.604	0.30( 0.28)	0.92	47909.6	11330.00
1	29332.42	136.74	0.591	0.30( 0.28)	0.93	52996.8	10630.00
1	29059.10	142.39	0.581	0.30( 0.28)	0.93	55586.6	12330.00
1	28775.52	149.07	0.570	0.30( 0.28)	0.93	58729.1	11600.00
1	28375.54	154.94	0.560	0.30( 0.28)	0.94	60963.4	11111.00
1	27936.20	161.18	0.549	0.30( 0.28)	0.94	62897.3	12201.00

1	26985.70	170.36	0.533	0.30( 0.28)	0.94	64985.5	12231.00
1	26118.81	178.09	0.520	0.30( 0.28)	0.94	66397.1	10400.00
1	24744.61	189.91	0.509	0.30( 0.28)	0.94	68017.8	10320.00
1	23455.89	200.06	0.502	0.30( 0.28)	0.94	68405.6	12000.00
1	20463.21	230.37	0.478	0.30( 0.28)	0.94	69022.6	10100.00
2	105.88	16.63	1.759	0.30( 0.28)	0.94	79.6	13889.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13447.31	16.63	1.759	0.30( 0.25)	0.84	2884.0	13889.00
2	15744.20	28.60	1.280	0.30( 0.25)	0.83	4903.2	13810.00
3	15936.79	29.92	1.244	0.30( 0.25)	0.83	5172.8	13850.00
4	16079.32	30.93	1.225	0.30( 0.25)	0.83	5374.0	10400.00
5	16714.24	33.43	1.179	0.30( 0.25)	0.83	6145.1	13870.00
6	18849.70	42.02	1.035	0.30( 0.25)	0.83	8730.7	13830.00
7	19433.09	44.48	1.006	0.30( 0.25)	0.83	9432.1	410.00
8	20806.67	51.95	0.924	0.30( 0.25)	0.83	11874.7	100.00
9	22289.13	61.11	0.847	0.30( 0.25)	0.84	15614.1	150.00
10	24551.54	76.93	0.768	0.30( 0.26)	0.86	22539.1	390.00
11	25842.22	91.38	0.700	0.30( 0.27)	0.88	29166.7	13100.00
12	26126.63	98.22	0.681	0.30( 0.27)	0.89	31780.8	11801.00
13	27430.33	115.92	0.631	0.30( 0.27)	0.91	40321.7	13510.00
14	28077.09	122.90	0.614	0.30( 0.27)	0.92	44314.3	13010.00
15	28796.32	128.73	0.604	0.30( 0.28)	0.92	47989.3	11330.00
16	29354.58	136.74	0.591	0.30( 0.28)	0.93	53076.4	10630.00
17	29080.57	142.39	0.581	0.30( 0.28)	0.93	55666.3	12330.00
18	28796.17	149.07	0.570	0.30( 0.28)	0.93	58808.7	11600.00
19	28395.49	154.94	0.560	0.30( 0.28)	0.94	61043.0	11111.00
20	27955.38	161.18	0.549	0.30( 0.28)	0.94	62976.9	12201.00
21	27003.76	170.36	0.533	0.30( 0.28)	0.94	65065.1	12231.00
22	26135.93	178.09	0.520	0.30( 0.28)	0.94	66476.7	10400.00
23	24760.95	189.91	0.509	0.30( 0.28)	0.94	68097.4	10320.00
24	23471.67	200.06	0.502	0.30( 0.28)	0.94	68485.2	12000.00
25	20477.31	230.37	0.478	0.30( 0.28)	0.94	69102.2	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 29354.58 Tc(MIN.) = 136.74  
EFFECTIVE AREA(ACRES) = 53076.39 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA(ACRES) = 69102.2  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13910.00 = 135259.70 FEET.

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 69102.2 TC(MIN.) = 136.74  
EFFECTIVE AREA(ACRES) = 53076.39 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.929  
PEAK FLOW RATE(CFS) = 29354.58

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13447.31	16.63	1.759	0.30( 0.25)	0.84	2884.0	13889.00
2	15744.20	28.60	1.280	0.30( 0.25)	0.83	4903.2	13810.00
3	15936.79	29.92	1.244	0.30( 0.25)	0.83	5172.8	13850.00

4	16079.32	30.93	1.225	0.30	( 0.25)	0.83	5374.0	10400.00
5	16714.24	33.43	1.179	0.30	( 0.25)	0.83	6145.1	13870.00
6	18849.70	42.02	1.035	0.30	( 0.25)	0.83	8730.7	13830.00
7	19433.09	44.48	1.006	0.30	( 0.25)	0.83	9432.1	410.00
8	20806.67	51.95	0.924	0.30	( 0.25)	0.83	11874.7	100.00
9	22289.13	61.11	0.847	0.30	( 0.25)	0.84	15614.1	150.00
10	24551.54	76.93	0.768	0.30	( 0.26)	0.86	22539.1	390.00
11	25842.22	91.38	0.700	0.30	( 0.27)	0.88	29166.7	13100.00
12	26126.63	98.22	0.681	0.30	( 0.27)	0.89	31780.8	11801.00
13	27430.33	115.92	0.631	0.30	( 0.27)	0.91	40321.7	13510.00
14	28077.09	122.90	0.614	0.30	( 0.27)	0.92	44314.3	13010.00
15	28796.32	128.73	0.604	0.30	( 0.28)	0.92	47989.3	11330.00
16	29354.58	136.74	0.591	0.30	( 0.28)	0.93	53076.4	10630.00
17	29080.57	142.39	0.581	0.30	( 0.28)	0.93	55666.3	12330.00
18	28796.17	149.07	0.570	0.30	( 0.28)	0.93	58808.7	11600.00
19	28395.49	154.94	0.560	0.30	( 0.28)	0.94	61043.0	11111.00
20	27955.38	161.18	0.549	0.30	( 0.28)	0.94	62976.9	12201.00
21	27003.76	170.36	0.533	0.30	( 0.28)	0.94	65065.1	12231.00
22	26135.93	178.09	0.520	0.30	( 0.28)	0.94	66476.7	10400.00
23	24760.95	189.91	0.509	0.30	( 0.28)	0.94	68097.4	10320.00
24	23471.67	200.06	0.502	0.30	( 0.28)	0.94	68485.2	12000.00
25	20477.31	230.37	0.478	0.30	( 0.28)	0.94	69102.2	10100.00

=====  
 END OF RATIONAL METHOD ANALYSIS  
 =====

\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S39- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 10-YR RM EV APRIL 2019 CCHIUI \*  
\*\*\*\*\*

FILE NAME: RI10EV39.DAT  
TIME/DATE OF STUDY: 10:17 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 10.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 3.695
- 2) 10.00; 2.473
- 3) 15.00; 1.845
- 4) 20.00; 1.577
- 5) 25.00; 1.378
- 6) 30.00; 1.242
- 7) 40.00; 1.058
- 8) 50.00; 0.941
- 9) 60.00; 0.852
- 10) 90.00; 0.704
- 11) 120.00; 0.618
- 12) 180.00; 0.516
- 13) 360.00; 0.377
- 14) 1200.00; 0.164

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL: IN- / OUT-/PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13900.00 TO NODE 13901.00 IS CODE = 21  
-----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 600.65  
ELEVATION DATA: UPSTREAM(FEET) = 442.40 DOWNSTREAM(FEET) = 385.16

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 10.859  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.365  
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
AGRICULTURAL POOR COVER "FALLOW"	-	4.00	0.30	1.000	56	10.86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA RUNOFF(CFS) = 7.43  
TOTAL AREA(ACRES) = 4.00 PEAK FLOW RATE(CFS) = 7.43

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13901.00 TO NODE 13902.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 385.16 DOWNSTREAM(FEET) = 288.21  
CHANNEL LENGTH THRU SUBAREA(FEET) = 647.42 CHANNEL SLOPE = 0.1497  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.26  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 2.119  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.47	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 14.40  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.51  
AVERAGE FLOW DEPTH(FEET) = 0.25 TRAVEL TIME(MIN.) = 1.96  
Tc(MIN.) = 12.82  
SUBAREA AREA(ACRES) = 8.47 SUBAREA RUNOFF(CFS) = 13.87  
EFFECTIVE AREA(ACRES) = 12.47 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 12.5 PEAK FLOW RATE(CFS) = 20.42  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.31

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.31 FLOW VELOCITY(FEET/SEC.) = 6.24  
LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13902.00 = 1248.07 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13902.00 TO NODE 13903.00 IS CODE = 56

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 288.21 DOWNSTREAM(FEET) = 184.89  
CHANNEL LENGTH THRU SUBAREA(FEET) = 669.27 CHANNEL SLOPE = 0.1544  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.45  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.943

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	23.85	0.30	0.982	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.982  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 38.14  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.97  
AVERAGE FLOW DEPTH(FEET) = 0.44 TRAVEL TIME(MIN.) = 1.40  
Tc(MIN.) = 14.22

SUBAREA AREA(ACRES) = 23.85 SUBAREA RUNOFF(CFS) = 35.39  
EFFECTIVE AREA(ACRES) = 36.32 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA(ACRES) = 36.3 PEAK FLOW RATE(CFS) = 53.84  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.54

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.54 FLOW VELOCITY(FEET/SEC.) = 9.02  
LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13903.00 = 1917.34 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13903.00 TO NODE 13904.00 IS CODE = 31

-----  
>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 184.89 DOWNSTREAM(FEET) = 155.08  
FLOW LENGTH(FEET) = 876.66 MANNING'S N = 0.013  
ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000  
DEPTH OF FLOW IN 36.0 INCH PIPE IS 17.2 INCHES  
PIPE-FLOW VELOCITY(FEET/SEC.) = 16.18  
ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1  
PIPE-FLOW(CFS) = 53.84  
PIPE TRAVEL TIME(MIN.) = 0.90 Tc(MIN.) = 15.12  
LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13904.00 = 2794.00 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13903.00 TO NODE 13904.00 IS CODE = 81

-----  
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 15.12  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.839

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	21.29	0.30	0.996	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.996  
SUBAREA AREA(ACRES) = 21.29 SUBAREA RUNOFF(CFS) = 29.51  
EFFECTIVE AREA(ACRES) = 57.61 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA(ACRES) = 57.6 PEAK FLOW RATE(CFS) = 79.92

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 31

-----  
>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 155.08 DOWNSTREAM(FEET) = 118.00  
FLOW LENGTH(FEET) = 1961.38 MANNING'S N = 0.013  
DEPTH OF FLOW IN 36.0 INCH PIPE IS 27.2 INCHES  
PIPE-FLOW VELOCITY(FEET/SEC.) = 13.96  
ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1  
PIPE-FLOW(CFS) = 79.92  
PIPE TRAVEL TIME(MIN.) = 2.34 Tc(MIN.) = 17.46  
LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13920.00 = 4755.38 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 81

-----  
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 17.46  
\* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 1.713

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	43.53	0.30	0.649	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.649  
SUBAREA AREA(ACRES) = 43.53 SUBAREA RUNOFF(CFS) = 59.49  
EFFECTIVE AREA(ACRES) = 101.14 AREA-AVERAGED Fm(INCH/HR) = 0.25  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84  
TOTAL AREA(ACRES) = 101.1 PEAK FLOW RATE(CFS) = 132.90

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 10

-----  
>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13910.00 TO NODE 13910.00 IS CODE = 15.1

-----  
>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI10EV38.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13447.31	16.63	0.30 ( 0.25)	0.84	2884.0	13889.00
2	16714.24	33.43	0.30 ( 0.25)	0.83	6145.1	13870.00
3	19433.09	44.48	0.30 ( 0.25)	0.83	9432.1	410.00
4	20806.67	51.95	0.30 ( 0.25)	0.83	11874.7	100.00
5	22289.13	61.11	0.30 ( 0.25)	0.84	15614.1	150.00
6	24551.54	76.93	0.30 ( 0.26)	0.86	22539.1	390.00
7	25842.22	91.38	0.30 ( 0.27)	0.88	29166.7	13100.00
8	26126.63	98.22	0.30 ( 0.27)	0.89	31780.8	11801.00
9	27430.33	115.92	0.30 ( 0.27)	0.91	40321.7	13510.00
10	28796.32	128.73	0.30 ( 0.28)	0.92	47989.3	11330.00
11	29354.58	136.74	0.30 ( 0.28)	0.93	53076.4	10630.00
12	29080.57	142.39	0.30 ( 0.28)	0.93	55666.3	12330.00
13	28796.17	149.07	0.30 ( 0.28)	0.93	58808.7	11600.00
14	28395.49	154.94	0.30 ( 0.28)	0.94	61043.0	11111.00
15	27955.38	161.18	0.30 ( 0.28)	0.94	62976.9	12201.00
16	27003.76	170.36	0.30 ( 0.28)	0.94	65065.1	12231.00
17	26135.93	178.09	0.30 ( 0.28)	0.94	66476.7	10400.00
18	24760.95	189.91	0.30 ( 0.28)	0.94	68097.4	10320.00
19	23471.67	200.06	0.30 ( 0.28)	0.94	68485.2	12000.00
20	20477.31	230.37	0.30 ( 0.28)	0.94	69102.2	10100.00
TOTAL AREA (ACRES) =						69102.2

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13910.00 TO NODE 13910.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13447.31	16.63	0.30 ( 0.25)	0.84	2884.0	13889.00
2	16714.24	33.43	0.30 ( 0.25)	0.83	6145.1	13870.00
3	19433.09	44.48	0.30 ( 0.25)	0.83	9432.1	410.00
4	20806.67	51.95	0.30 ( 0.25)	0.83	11874.7	100.00
5	22289.13	61.11	0.30 ( 0.25)	0.84	15614.1	150.00
6	24551.54	76.93	0.30 ( 0.26)	0.86	22539.1	390.00
7	25842.22	91.38	0.30 ( 0.27)	0.88	29166.7	13100.00
8	26126.63	98.22	0.30 ( 0.27)	0.89	31780.8	11801.00
9	27430.33	115.92	0.30 ( 0.27)	0.91	40321.7	13510.00
10	28796.32	128.73	0.30 ( 0.28)	0.92	47989.3	11330.00
11	29354.58	136.74	0.30 ( 0.28)	0.93	53076.4	10630.00
12	29080.57	142.39	0.30 ( 0.28)	0.93	55666.3	12330.00
13	28796.17	149.07	0.30 ( 0.28)	0.93	58808.7	11600.00
14	28395.49	154.94	0.30 ( 0.28)	0.94	61043.0	11111.00
15	27955.38	161.18	0.30 ( 0.28)	0.94	62976.9	12201.00
16	27003.76	170.36	0.30 ( 0.28)	0.94	65065.1	12231.00
17	26135.93	178.09	0.30 ( 0.28)	0.94	66476.7	10400.00
18	24760.95	189.91	0.30 ( 0.28)	0.94	68097.4	10320.00
19	23471.67	200.06	0.30 ( 0.28)	0.94	68485.2	12000.00
20	20477.31	230.37	0.30 ( 0.28)	0.94	69102.2	10100.00
TOTAL AREA (ACRES) =						69102.2

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13910.00 TO NODE 13920.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

```

=====
ELEVATION DATA: UPSTREAM(FEET) = 119.70 DOWNSTREAM(FEET) = 118.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1376.26 CHANNEL SLOPE = 0.0012
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 18.13
* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.585
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 96.09 0.30 0.535 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.535
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 29372.95
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.39
AVERAGE FLOW DEPTH(FEET) = 18.12 TRAVEL TIME(MIN.) = 2.44
Tc(MIN.) = 139.18
SUBAREA AREA(ACRES) = 96.09 SUBAREA RUNOFF(CFS) = 36.75
EFFECTIVE AREA(ACRES) = 53172.48 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 69198.3 PEAK FLOW RATE(CFS) = 29354.58
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 18.12
    
```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 18.12 FLOW VELOCITY(FEET/SEC.) = 9.39

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136635.97 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13447.31	19.67	1.594	0.30 ( 0.25)	0.83	2980.0	13889.00
2	16714.24	36.30	1.126	0.30 ( 0.25)	0.83	6241.2	13870.00
3	19433.09	47.22	0.974	0.30 ( 0.25)	0.83	9528.2	410.00
4	20806.67	54.64	0.900	0.30 ( 0.25)	0.83	11970.8	100.00
5	22289.13	63.74	0.834	0.30 ( 0.25)	0.83	15710.2	150.00
6	24551.54	79.50	0.756	0.30 ( 0.26)	0.86	22635.2	390.00
7	25842.22	93.91	0.693	0.30 ( 0.26)	0.88	29262.8	13100.00
8	26126.63	100.75	0.673	0.30 ( 0.27)	0.89	31876.9	11801.00
9	27430.33	118.41	0.623	0.30 ( 0.27)	0.91	40417.8	13510.00
10	28796.32	131.18	0.599	0.30 ( 0.28)	0.92	48085.3	11330.00
11	29354.58	139.18	0.585	0.30 ( 0.28)	0.93	53172.5	10630.00
12	29080.57	144.84	0.576	0.30 ( 0.28)	0.93	55762.4	12330.00
13	28796.17	151.52	0.564	0.30 ( 0.28)	0.93	58904.8	11600.00
14	28395.49	157.40	0.554	0.30 ( 0.28)	0.94	61139.1	11111.00
15	27955.38	163.65	0.544	0.30 ( 0.28)	0.94	63073.0	12201.00
16	27003.76	172.86	0.528	0.30 ( 0.28)	0.94	65161.2	12231.00
17	26135.93	180.61	0.516	0.30 ( 0.28)	0.94	66572.8	10400.00
18	24760.95	192.47	0.506	0.30 ( 0.28)	0.94	68193.5	10320.00
19	23471.67	202.66	0.499	0.30 ( 0.28)	0.94	68581.3	12000.00
20	20477.31	233.07	0.475	0.30 ( 0.28)	0.94	69198.3	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 29354.58 Tc(MIN.) = 139.18



AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 53172.48

\*\*\*\*\*

FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13447.31	19.67	1.594	0.30( 0.25)	0.83	2980.0	13889.00
2	16714.24	36.30	1.126	0.30( 0.25)	0.83	6241.2	13870.00
3	19433.09	47.22	0.974	0.30( 0.25)	0.83	9528.2	410.00
4	20806.67	54.64	0.900	0.30( 0.25)	0.83	11970.8	100.00
5	22289.13	63.74	0.834	0.30( 0.25)	0.83	15710.2	150.00
6	24551.54	79.50	0.756	0.30( 0.26)	0.86	22635.2	390.00
7	25842.22	93.91	0.693	0.30( 0.26)	0.88	29262.8	13100.00
8	26126.63	100.75	0.673	0.30( 0.27)	0.89	31876.9	11801.00
9	27430.33	118.41	0.623	0.30( 0.27)	0.91	40417.8	13510.00
10	28796.32	131.18	0.599	0.30( 0.28)	0.92	48085.3	11330.00
11	29354.58	139.18	0.585	0.30( 0.28)	0.93	53172.5	10630.00
12	29080.57	144.84	0.576	0.30( 0.28)	0.93	55762.4	12330.00
13	28796.17	151.52	0.564	0.30( 0.28)	0.93	58904.8	11600.00
14	28395.49	157.40	0.554	0.30( 0.28)	0.94	61139.1	11111.00
15	27955.38	163.65	0.544	0.30( 0.28)	0.94	63073.0	12201.00
16	27003.76	172.86	0.528	0.30( 0.28)	0.94	65161.2	12231.00
17	26135.93	180.61	0.516	0.30( 0.28)	0.94	66572.8	10400.00
18	24760.95	192.47	0.506	0.30( 0.28)	0.94	68193.5	10320.00
19	23471.67	202.66	0.499	0.30( 0.28)	0.94	68581.3	12000.00
20	20477.31	233.07	0.475	0.30( 0.28)	0.94	69198.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136635.97 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	132.90	17.46	1.713	0.30( 0.25)	0.84	101.1	13900.00

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13920.00 = 4755.38 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13118.88	17.46	1.713	0.30( 0.25)	0.83	2746.0	13900.00
2	13569.42	19.67	1.594	0.30( 0.25)	0.83	3081.2	13889.00
3	16793.71	36.30	1.126	0.30( 0.25)	0.83	6342.4	13870.00
4	19498.67	47.22	0.974	0.30( 0.25)	0.83	9629.3	410.00
5	20865.53	54.64	0.900	0.30( 0.25)	0.83	12072.0	100.00
6	22341.96	63.74	0.834	0.30( 0.25)	0.83	15811.3	150.00
7	24597.30	79.50	0.756	0.30( 0.26)	0.86	22736.3	390.00
8	25882.25	93.91	0.693	0.30( 0.26)	0.88	29364.0	13100.00
9	26164.87	100.75	0.673	0.30( 0.27)	0.89	31978.1	11801.00
10	27463.96	118.41	0.623	0.30( 0.27)	0.91	40518.9	13510.00
11	28827.80	131.18	0.599	0.30( 0.28)	0.92	48186.5	11330.00
12	29384.83	139.18	0.585	0.30( 0.28)	0.93	53273.6	10630.00
13	29109.94	144.84	0.576	0.30( 0.28)	0.93	55863.5	12330.00
14	28824.51	151.52	0.564	0.30( 0.28)	0.93	59005.9	11600.00
15	28422.91	157.40	0.554	0.30( 0.28)	0.94	61240.3	11111.00

16	27981.84	163.65	0.544	0.30( 0.28)	0.94	63174.1	12201.00
17	27028.79	172.86	0.528	0.30( 0.28)	0.94	65262.4	12231.00
18	26159.82	180.61	0.516	0.30( 0.28)	0.94	66673.9	10400.00
19	24784.00	192.47	0.506	0.30( 0.28)	0.94	68294.7	10320.00
20	23494.01	202.66	0.499	0.30( 0.28)	0.94	68682.5	12000.00
21	20497.51	233.07	0.475	0.30( 0.28)	0.94	69299.5	10100.00
TOTAL AREA(ACRES) =							69299.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 29384.83 Tc(MIN.) = 139.184  
 EFFECTIVE AREA(ACRES) = 53273.62 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 69299.5  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136635.97 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13920.00 TO NODE 13921.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 118.00 DOWNSTREAM(FEET) = 115.28  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 335.44 CHANNEL SLOPE = 0.0081  
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 11.09  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.585

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	134.30	0.30	0.658	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.658  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 29408.25  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 18.37  
 AVERAGE FLOW DEPTH(FEET) = 11.09 TRAVEL TIME(MIN.) = 0.30  
 Tc(MIN.) = 139.49  
 SUBAREA AREA(ACRES) = 134.30 SUBAREA RUNOFF(CFS) = 46.84  
 EFFECTIVE AREA(ACRES) = 53407.93 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 69433.8 PEAK FLOW RATE(CFS) = 29384.83  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 11.08

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 11.08 FLOW VELOCITY(FEET/SEC.) = 18.37  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13921.00 = 136971.41 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	13118.88	17.85	1.692	0.30( 0.25)	0.82	2880.3	13900.00
2	13569.42	20.06	1.575	0.30( 0.25)	0.82	3215.5	13889.00
3	16793.71	36.66	1.120	0.30( 0.25)	0.83	6476.7	13870.00
4	19498.67	47.56	0.970	0.30( 0.25)	0.82	9763.6	410.00
5	20865.53	54.98	0.897	0.30( 0.25)	0.82	12206.3	100.00

6	22341.96	64.07	0.832	0.30	( 0.25)	0.83	15945.6	150.00
7	24597.30	79.82	0.754	0.30	( 0.26)	0.86	22870.6	390.00
8	25882.25	94.23	0.692	0.30	( 0.26)	0.88	29498.3	13100.00
9	26164.87	101.06	0.672	0.30	( 0.27)	0.89	32112.4	11801.00
10	27463.96	118.72	0.622	0.30	( 0.27)	0.91	40653.2	13510.00
11	28827.80	131.49	0.598	0.30	( 0.28)	0.92	48320.8	11330.00
12	29384.83	139.49	0.585	0.30	( 0.28)	0.93	53407.9	10630.00
13	29109.94	145.14	0.575	0.30	( 0.28)	0.93	55997.8	12330.00
14	28824.51	151.83	0.564	0.30	( 0.28)	0.93	59140.2	11600.00
15	28422.91	157.71	0.554	0.30	( 0.28)	0.94	61374.6	11111.00
16	27981.84	163.96	0.543	0.30	( 0.28)	0.94	63308.4	12201.00
17	27028.79	173.17	0.528	0.30	( 0.28)	0.94	65396.7	12231.00
18	26159.82	180.93	0.515	0.30	( 0.28)	0.94	66808.2	10400.00
19	24784.00	192.79	0.506	0.30	( 0.28)	0.94	68429.0	10320.00
20	23494.01	202.98	0.498	0.30	( 0.28)	0.94	68816.8	12000.00
21	20497.51	233.41	0.475	0.30	( 0.28)	0.94	69433.8	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 29384.83 Tc(MIN.) = 139.49  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 53407.93

\*\*\*\*\*

FLOW PROCESS FROM NODE 13921.00 TO NODE 14010.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 115.28 DOWNSTREAM(FEET) = 100.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1396.08 CHANNEL SLOPE = 0.0109  
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 10.23  
 \* 10 YEAR RAINFALL INTENSITY(INCH/HR) = 0.583

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	96.27	0.30	0.723	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.723  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 29400.69  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 20.40  
 AVERAGE FLOW DEPTH(FEET) = 10.23 TRAVEL TIME(MIN.) = 1.14  
 Tc(MIN.) = 140.63  
 SUBAREA AREA(ACRES) = 96.27 SUBAREA RUNOFF(CFS) = 31.72  
 EFFECTIVE AREA(ACRES) = 53504.20 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 69530.1 PEAK FLOW RATE(CFS) = 29384.83  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 10.22

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 10.22 FLOW VELOCITY(FEET/SEC.) = 20.41  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 14010.00 = 138367.48 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	--------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	13118.88	19.31	1.614	0.30( 0.24)	0.82	2976.6 13900.00
2	13569.42	21.51	1.517	0.30( 0.25)	0.82	3311.8 13889.00
3	16793.71	38.01	1.095	0.30( 0.25)	0.82	6572.9 13870.00
4	19498.67	48.86	0.954	0.30( 0.25)	0.82	9859.9 410.00
5	20865.53	56.24	0.885	0.30( 0.25)	0.82	12302.5 100.00
6	22341.96	65.31	0.826	0.30( 0.25)	0.83	16041.9 150.00
7	24597.30	81.02	0.748	0.30( 0.26)	0.86	22966.9 390.00
8	25882.25	95.41	0.688	0.30( 0.26)	0.88	29594.5 13100.00
9	26164.87	102.24	0.669	0.30( 0.27)	0.89	32208.6 11801.00
10	27463.96	119.88	0.618	0.30( 0.27)	0.91	40749.5 13510.00
11	28827.80	132.64	0.597	0.30( 0.28)	0.92	48417.1 11330.00
12	29384.83	140.63	0.583	0.30( 0.28)	0.93	53504.2 10630.00
13	29109.94	146.28	0.573	0.30( 0.28)	0.93	56094.1 12330.00
14	28824.51	152.98	0.562	0.30( 0.28)	0.93	59236.5 11600.00
15	28422.91	158.86	0.552	0.30( 0.28)	0.93	61470.8 11111.00
16	27981.84	165.12	0.541	0.30( 0.28)	0.94	63404.7 12201.00
17	27028.79	174.34	0.526	0.30( 0.28)	0.94	65492.9 12231.00
18	26159.82	182.11	0.514	0.30( 0.28)	0.94	66904.5 10400.00
19	24784.00	193.99	0.505	0.30( 0.28)	0.94	68525.2 10320.00
20	23494.01	204.20	0.497	0.30( 0.28)	0.94	68913.1 12000.00
21	20497.51	234.68	0.474	0.30( 0.28)	0.94	69530.1 10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 29384.83 Tc(MIN.) = 140.63  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 53504.20

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 69530.1 TC(MIN.) = 140.63  
 EFFECTIVE AREA(ACRES) = 53504.20 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.927  
 PEAK FLOW RATE(CFS) = 29384.83

\*\* PEAK FLOW RATE TABLE \*\*

STREAM	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE	
1	13118.88	19.31	1.614	0.30( 0.24)	0.82	2976.6 13900.00	
2	13569.42	21.51	1.517	0.30( 0.25)	0.82	3311.8 13889.00	
3	16793.71	38.01	1.095	0.30( 0.25)	0.82	6572.9 13870.00	
4	19498.67	48.86	0.954	0.30( 0.25)	0.82	9859.9 410.00	
5	20865.53	56.24	0.885	0.30( 0.25)	0.82	12302.5 100.00	
6	22341.96	65.31	0.826	0.30( 0.25)	0.83	16041.9 150.00	
7	24597.30	81.02	0.748	0.30( 0.26)	0.86	22966.9 390.00	
8	25882.25	95.41	0.688	0.30( 0.26)	0.88	29594.5 13100.00	
9	26164.87	102.24	0.669	0.30( 0.27)	0.89	32208.6 11801.00	
10	27463.96	119.88	0.618	0.30( 0.27)	0.91	40749.5 13510.00	
11	28827.80	132.64	0.597	0.30( 0.28)	0.92	48417.1 11330.00	
12	29384.83	140.63	0.583	0.30( 0.28)	0.93	53504.2 10630.00	
13	29109.94	146.28	0.573	0.30( 0.28)	0.93	56094.1 12330.00	
14	28824.51	152.98	0.562	0.30( 0.28)	0.93	59236.5 11600.00	
15	28422.91	158.86	0.552	0.30( 0.28)	0.93	61470.8 11111.00	
16	27981.84	165.12	0.541	0.30( 0.28)	0.94	63404.7 12201.00	
17	27028.79	174.34	0.526	0.30( 0.28)	0.94	65492.9 12231.00	
18	26159.82	182.11	0.514	0.30( 0.28)	0.94	66904.5 10400.00	
19	24784.00	193.99	0.505	0.30( 0.28)	0.94	68525.2 10320.00	
20	23494.01	204.20	0.497	0.30( 0.28)	0.94	68913.1 12000.00	
21	20497.51	234.68	0.474	0.30( 0.28)	0.94	69530.1 10100.00	

=====  
END OF RATIONAL METHOD ANALYSIS

\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S19- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 25-YR RM EV APRIL 2019 CCHIUI \*  
\*\*\*\*\*

FILE NAME: RI25EV19.DAT  
TIME/DATE OF STUDY: 09:47 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 25.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.002
- 2) 10.00; 3.253
- 3) 15.00; 2.474
- 4) 20.00; 2.039
- 5) 25.00; 1.775
- 6) 30.00; 1.555
- 7) 40.00; 1.356
- 8) 50.00; 1.203
- 9) 60.00; 1.080
- 10) 90.00; 0.912
- 11) 120.00; 0.803
- 12) 180.00; 0.672
- 13) 360.00; 0.500
- 14) 1200.00; 0.221

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL: IN- / OUT-/PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11900.00 TO NODE 11901.00 IS CODE = 21  
-----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 295.79  
ELEVATION DATA: UPSTREAM(FEET) = 2369.48 DOWNSTREAM(FEET) = 2332.92

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 7.203  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 4.231  
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
RESIDENTIAL ".4 DWELLING/ACRE"	-	1.62	0.30	0.999	0	7.20

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999  
SUBAREA RUNOFF(CFS) = 5.73  
TOTAL AREA(ACRES) = 1.62 PEAK FLOW RATE(CFS) = 5.73

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11901.00 TO NODE 11902.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2332.92 DOWNSTREAM(FEET) = 2297.70  
CHANNEL LENGTH THRU SUBAREA(FEET) = 664.26 CHANNEL SLOPE = 0.0530  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.53  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 3.158  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.35	0.30	0.906	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.906  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 16.71  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.25  
AVERAGE FLOW DEPTH(FEET) = 0.47 TRAVEL TIME(MIN.) = 3.41  
Tc(MIN.) = 10.61  
SUBAREA AREA(ACRES) = 8.35 SUBAREA RUNOFF(CFS) = 21.69  
EFFECTIVE AREA(ACRES) = 9.97 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
TOTAL AREA(ACRES) = 10.0 PEAK FLOW RATE(CFS) = 25.86  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.61

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.61 FLOW VELOCITY(FEET/SEC.) = 3.76  
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11902.00 = 960.05 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11902.00 TO NODE 11902.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2297.70 DOWNSTREAM(FEET) = 2263.40  
CHANNEL LENGTH THRU SUBAREA(FEET) = 928.77 CHANNEL SLOPE = 0.0369  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.21

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.623

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	34.48	0.30	0.904	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.904

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 62.68  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.51

AVERAGE FLOW DEPTH(FEET) = 1.13 TRAVEL TIME(MIN.) = 3.44  
Tc(MIN.) = 14.05

SUBAREA AREA(ACRES) = 34.48 SUBAREA RUNOFF(CFS) = 72.97  
EFFECTIVE AREA(ACRES) = 44.45 AREA-AVERAGED Fm(INCH/HR) = 0.27

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.91

TOTAL AREA(ACRES) = 44.5 PEAK FLOW RATE(CFS) = 94.03  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.42

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.42 FLOW VELOCITY(FEET/SEC.) = 5.14

LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11902.50 = 1888.82 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11902.50 TO NODE 11903.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2263.40 DOWNSTREAM(FEET) = 2252.14  
CHANNEL LENGTH THRU SUBAREA(FEET) = 895.50 CHANNEL SLOPE = 0.0126  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.19

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.210

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	23.65	0.30	0.958	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.958

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 114.54  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.75

AVERAGE FLOW DEPTH(FEET) = 2.14 TRAVEL TIME(MIN.) = 3.98

Tc(MIN.) = 18.03  
SUBAREA AREA(ACRES) = 23.65 SUBAREA RUNOFF(CFS) = 40.93  
EFFECTIVE AREA(ACRES) = 68.10 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA(ACRES) = 68.1 PEAK FLOW RATE(CFS) = 118.47  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.18

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.18 FLOW VELOCITY(FEET/SEC.) = 3.77

LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11903.00 = 2784.32 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11903.00 TO NODE 11904.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2252.14 DOWNSTREAM(FEET) = 2186.04  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1924.35 CHANNEL SLOPE = 0.0343  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.07

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.859

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	68.53	0.30	0.961	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.961

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 167.07  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.96

AVERAGE FLOW DEPTH(FEET) = 2.00 TRAVEL TIME(MIN.) = 5.38  
Tc(MIN.) = 23.41

SUBAREA AREA(ACRES) = 68.53 SUBAREA RUNOFF(CFS) = 96.87

EFFECTIVE AREA(ACRES) = 136.63 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94

TOTAL AREA(ACRES) = 136.6 PEAK FLOW RATE(CFS) = 193.79

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.17

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.17 FLOW VELOCITY(FEET/SEC.) = 6.23

LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11904.00 = 4708.67 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11904.00 TO NODE 11905.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 2186.04 DOWNSTREAM(FEET) = 1957.34  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1926.87 CHANNEL SLOPE = 0.1187  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.73

\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.706  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 63.15 0.30 1.000 -  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 233.78  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 10.17  
 AVERAGE FLOW DEPTH (FEET) = 1.71 TRAVEL TIME (MIN.) = 3.16  
 Tc (MIN.) = 26.57  
 SUBAREA AREA (ACRES) = 63.15 SUBAREA RUNOFF (CFS) = 79.91  
 EFFECTIVE AREA (ACRES) = 199.78 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA (ACRES) = 199.8 PEAK FLOW RATE (CFS) = 254.91  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 1.80

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 1.80 FLOW VELOCITY (FEET/SEC.) = 10.44  
 LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11905.00 = 6635.54 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11905.00 TO NODE 11906.00 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 -----

ELEVATION DATA: UPSTREAM (FEET) = 1957.34 DOWNSTREAM (FEET) = 1244.16  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 2498.96 CHANNEL SLOPE = 0.2854  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 1.57  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.583  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 84.87 0.30 1.000 -  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 303.95  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 14.95  
 AVERAGE FLOW DEPTH (FEET) = 1.55 TRAVEL TIME (MIN.) = 2.79  
 Tc (MIN.) = 29.35  
 SUBAREA AREA (ACRES) = 84.87 SUBAREA RUNOFF (CFS) = 98.04  
 EFFECTIVE AREA (ACRES) = 284.65 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97  
 TOTAL AREA (ACRES) = 284.6 PEAK FLOW RATE (CFS) = 330.91  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 1.63

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 1.63 FLOW VELOCITY (FEET/SEC.) = 15.33  
 LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11906.00 = 9134.50 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11906.00 TO NODE 11920.00 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 -----

ELEVATION DATA: UPSTREAM (FEET) = 1244.16 DOWNSTREAM (FEET) = 873.95  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 3370.75 CHANNEL SLOPE = 0.1098  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 2.49  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.474  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 199.43 0.30 1.000 -  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 436.32  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 11.89  
 AVERAGE FLOW DEPTH (FEET) = 2.46 TRAVEL TIME (MIN.) = 4.72  
 Tc (MIN.) = 34.08  
 SUBAREA AREA (ACRES) = 199.43 SUBAREA RUNOFF (CFS) = 210.70  
 EFFECTIVE AREA (ACRES) = 484.08 AREA-AVERAGED Fm (INCH/HR) = 0.30  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98  
 TOTAL AREA (ACRES) = 484.1 PEAK FLOW RATE (CFS) = 513.53  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 2.68

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 2.68 FLOW VELOCITY (FEET/SEC.) = 12.47  
 LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11920.00 = 12505.25 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11906.00 TO NODE 11920.00 IS CODE = 1

-----  
 >>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 -----

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
 TIME OF CONCENTRATION (MIN.) = 34.08  
 RAINFALL INTENSITY (INCH/HR) = 1.47  
 AREA-AVERAGED Fm (INCH/HR) = 0.30  
 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.98  
 EFFECTIVE STREAM AREA (ACRES) = 484.08  
 TOTAL STREAM AREA (ACRES) = 484.08  
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 513.53

\*\*\*\*\*

FLOW PROCESS FROM NODE 11910.00 TO NODE 11911.00 IS CODE = 21

-----  
 >>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<  
 -----

INITIAL SUBAREA FLOW-LENGTH (FEET) = 517.62  
 ELEVATION DATA: UPSTREAM (FEET) = 2531.88 DOWNSTREAM (FEET) = 2441.33

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
 SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 12.185  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.913  
 SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	-	3.46	0.30	1.000	0	12.19

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA RUNOFF(CFS) = 8.14  
 TOTAL AREA(ACRES) = 3.46 PEAK FLOW RATE(CFS) = 8.14

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11911.00 TO NODE 11912.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2441.33 DOWNSTREAM(FEET) = 2382.20  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 397.30 CHANNEL SLOPE = 0.1488  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.33  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.669

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.79	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 14.32  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.24  
 AVERAGE FLOW DEPTH(FEET) = 0.32 TRAVEL TIME(MIN.) = 1.56  
 Tc(MIN.) = 13.75  
 SUBAREA AREA(ACRES) = 5.79 SUBAREA RUNOFF(CFS) = 12.35  
 EFFECTIVE AREA(ACRES) = 9.25 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 9.2 PEAK FLOW RATE(CFS) = 19.72  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.38

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 0.38 FLOW VELOCITY(FEET/SEC.) = 4.77  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11912.00 = 914.92 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11912.00 TO NODE 11913.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2382.20 DOWNSTREAM(FEET) = 2263.77  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1891.47 CHANNEL SLOPE = 0.0626  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.10

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.076  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	54.30	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 63.91  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.41  
 AVERAGE FLOW DEPTH(FEET) = 0.99 TRAVEL TIME(MIN.) = 5.83  
 Tc(MIN.) = 19.58  
 SUBAREA AREA(ACRES) = 54.30 SUBAREA RUNOFF(CFS) = 86.79  
 EFFECTIVE AREA(ACRES) = 63.55 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 63.5 PEAK FLOW RATE(CFS) = 101.57  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.28

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.28 FLOW VELOCITY(FEET/SEC.) = 6.29  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11913.00 = 2806.39 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11913.00 TO NODE 11914.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2263.77 DOWNSTREAM(FEET) = 1845.23  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1957.31 CHANNEL SLOPE = 0.2138  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.15  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.902

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	65.14	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 148.57  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.79  
 AVERAGE FLOW DEPTH(FEET) = 1.12 TRAVEL TIME(MIN.) = 3.02  
 Tc(MIN.) = 22.60  
 SUBAREA AREA(ACRES) = 65.14 SUBAREA RUNOFF(CFS) = 93.90  
 EFFECTIVE AREA(ACRES) = 128.69 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 128.7 PEAK FLOW RATE(CFS) = 185.51  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.28

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.28 FLOW VELOCITY(FEET/SEC.) = 11.57  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11914.00 = 4763.70 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11914.00 TO NODE 11915.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1845.23 DOWNSTREAM(FEET) = 1557.21
CHANNEL LENGTH THRU SUBAREA(FEET) = 1686.78 CHANNEL SLOPE = 0.1708
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.58
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.774

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 78.52 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 237.62

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.60

AVERAGE FLOW DEPTH(FEET) = 1.56 TRAVEL TIME(MIN.) = 2.42

Tc(MIN.) = 25.03

SUBAREA AREA(ACRES) = 78.52 SUBAREA RUNOFF(CFS) = 104.16

EFFECTIVE AREA(ACRES) = 207.21 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 207.2 PEAK FLOW RATE(CFS) = 274.88

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.69

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.69 FLOW VELOCITY(FEET/SEC.) = 12.15

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11915.00 = 6450.48 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 11915.00 TO NODE 11916.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1557.21 DOWNSTREAM(FEET) = 1403.38
CHANNEL LENGTH THRU SUBAREA(FEET) = 1909.39 CHANNEL SLOPE = 0.0806
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.27
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.630

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 70.48 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 317.07

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.73

AVERAGE FLOW DEPTH(FEET) = 2.25 TRAVEL TIME(MIN.) = 3.27

Tc(MIN.) = 28.30

SUBAREA AREA(ACRES) = 70.48 SUBAREA RUNOFF(CFS) = 84.37

EFFECTIVE AREA(ACRES) = 277.69 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 277.7 PEAK FLOW RATE(CFS) = 332.41
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.31

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.31 FLOW VELOCITY(FEET/SEC.) = 9.86

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11916.00 = 8359.87 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 11916.00 TO NODE 11917.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1403.38 DOWNSTREAM(FEET) = 1079.99
CHANNEL LENGTH THRU SUBAREA(FEET) = 1945.82 CHANNEL SLOPE = 0.1662
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.29
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.543

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 232.20 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 462.32

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 14.02

AVERAGE FLOW DEPTH(FEET) = 2.27 TRAVEL TIME(MIN.) = 2.31

Tc(MIN.) = 30.61

SUBAREA AREA(ACRES) = 232.20 SUBAREA RUNOFF(CFS) = 259.75

EFFECTIVE AREA(ACRES) = 509.89 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 509.9 PEAK FLOW RATE(CFS) = 570.39

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.54

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.54 FLOW VELOCITY(FEET/SEC.) = 14.91

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11917.00 = 10305.69 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 11917.00 TO NODE 11920.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1079.99 DOWNSTREAM(FEET) = 873.95
CHANNEL LENGTH THRU SUBAREA(FEET) = 2563.91 CHANNEL SLOPE = 0.0804
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 3.25
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.471

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN



USER-DEFINED - 110.82 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 628.79  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.79  
 AVERAGE FLOW DEPTH(FEET) = 3.24 TRAVEL TIME(MIN.) = 3.63  
 Tc(MIN.) = 34.23  
 SUBAREA AREA(ACRES) = 110.82 SUBAREA RUNOFF(CFS) = 116.77  
 EFFECTIVE AREA(ACRES) = 620.71 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 620.7 PEAK FLOW RATE(CFS) = 654.06  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 3.30

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 3.30 FLOW VELOCITY(FEET/SEC.) = 11.94  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11920.00 = 12869.60 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11917.00 TO NODE 11920.00 IS CODE = 1  
 -----

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<  
 =====

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
 TIME OF CONCENTRATION(MIN.) = 34.23  
 RAINFALL INTENSITY(INCH/HR) = 1.47  
 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 1.00  
 EFFECTIVE STREAM AREA(ACRES) = 620.71  
 TOTAL STREAM AREA(ACRES) = 620.71  
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 654.06

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	513.53	34.08	1.474	0.30( 0.30)	0.98	484.1	11900.00
2	654.06	34.23	1.471	0.30( 0.30)	1.00	620.7	11910.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1166.34	34.08	1.474	0.30( 0.30)	0.99	1102.0	11900.00
2	1166.24	34.23	1.471	0.30( 0.30)	0.99	1104.8	11910.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:  
 PEAK FLOW RATE(CFS) = 1166.34 Tc(MIN.) = 34.08  
 EFFECTIVE AREA(ACRES) = 1101.97 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 1104.8  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11920.00 = 12869.60 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11920.00 TO NODE 11921.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 873.95 DOWNSTREAM(FEET) = 827.94  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1417.25 CHANNEL SLOPE = 0.0325  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 5.66  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.427

SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 107.47 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1220.87  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.12  
 AVERAGE FLOW DEPTH(FEET) = 5.66 TRAVEL TIME(MIN.) = 2.33  
 Tc(MIN.) = 36.41  
 SUBAREA AREA(ACRES) = 107.47 SUBAREA RUNOFF(CFS) = 109.05  
 EFFECTIVE AREA(ACRES) = 1209.44 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 1212.3 PEAK FLOW RATE(CFS) = 1229.34  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 5.68

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 5.68 FLOW VELOCITY(FEET/SEC.) = 10.13  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11921.00 = 14286.85 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11921.00 TO NODE 11922.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 827.94 DOWNSTREAM(FEET) = 753.55  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1886.43 CHANNEL SLOPE = 0.0394  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 5.78  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.372

SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 344.27 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1395.41  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.27  
 AVERAGE FLOW DEPTH(FEET) = 5.76 TRAVEL TIME(MIN.) = 2.79  
 Tc(MIN.) = 39.20  
 SUBAREA AREA(ACRES) = 344.27 SUBAREA RUNOFF(CFS) = 332.13  
 EFFECTIVE AREA(ACRES) = 1553.71 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 1556.5 PEAK FLOW RATE(CFS) = 1501.01  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 5.96

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 5.96 FLOW VELOCITY(FEET/SEC.) = 11.48  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11922.00 = 16173.28 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11922.00 TO NODE 11923.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 753.55 DOWNSTREAM(FEET) = 641.58  
CHANNEL LENGTH THRU SUBAREA(FEET) = 2860.88 CHANNEL SLOPE = 0.0391  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.12  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.305  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	165.18	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1575.75  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.59  
AVERAGE FLOW DEPTH(FEET) = 6.11 TRAVEL TIME(MIN.) = 4.11  
Tc(MIN.) = 43.32  
SUBAREA AREA(ACRES) = 165.18 SUBAREA RUNOFF(CFS) = 149.46  
EFFECTIVE AREA(ACRES) = 1718.89 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 1721.7 PEAK FLOW RATE(CFS) = 1557.36  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.08

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 6.08 FLOW VELOCITY(FEET/SEC.) = 11.57  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11923.00 = 19034.16 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11923.00 TO NODE 11924.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 641.58 DOWNSTREAM(FEET) = 579.89  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1844.02 CHANNEL SLOPE = 0.0335  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.68  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.263  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	165.18	0.30	1.000	-

LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 433.73 0.30 1.000 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1745.42  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.23  
AVERAGE FLOW DEPTH(FEET) = 6.66 TRAVEL TIME(MIN.) = 2.74  
Tc(MIN.) = 46.05  
SUBAREA AREA(ACRES) = 433.73 SUBAREA RUNOFF(CFS) = 376.10  
EFFECTIVE AREA(ACRES) = 2152.62 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 2155.4 PEAK FLOW RATE(CFS) = 1868.68  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.88

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 6.88 FLOW VELOCITY(FEET/SEC.) = 11.43  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11924.00 = 20878.18 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11924.00 TO NODE 11925.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 579.89 DOWNSTREAM(FEET) = 494.12  
CHANNEL LENGTH THRU SUBAREA(FEET) = 2756.15 CHANNEL SLOPE = 0.0311  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 7.20  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.202  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	265.42	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1976.37  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.29  
AVERAGE FLOW DEPTH(FEET) = 7.18 TRAVEL TIME(MIN.) = 4.07  
Tc(MIN.) = 50.12  
SUBAREA AREA(ACRES) = 265.42 SUBAREA RUNOFF(CFS) = 215.37  
EFFECTIVE AREA(ACRES) = 2418.04 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 2420.9 PEAK FLOW RATE(CFS) = 1964.19  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 7.16

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 7.16 FLOW VELOCITY(FEET/SEC.) = 11.28  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11925.00 = 23634.33 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11925.00 TO NODE 11926.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 494.12 DOWNSTREAM(FEET) = 458.40  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1922.70 CHANNEL SLOPE = 0.0186  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 8.15  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.159  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	97.46	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2001.88  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.35  
AVERAGE FLOW DEPTH(FEET) = 8.14 TRAVEL TIME(MIN.) = 3.43  
Tc(MIN.) = 53.55  
SUBAREA AREA(ACRES) = 97.46 SUBAREA RUNOFF(CFS) = 75.39  
EFFECTIVE AREA(ACRES) = 2515.50 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 2518.3 PEAK FLOW RATE(CFS) = 1964.19  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 8.07

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 8.07 FLOW VELOCITY(FEET/SEC.) = 9.30  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11926.00 = 25557.03 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11926.00 TO NODE 11927.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 458.40 DOWNSTREAM(FEET) = 399.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 2170.13 CHANNEL SLOPE = 0.0274  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 7.42  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.118  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	53.83	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1984.01  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.78  
AVERAGE FLOW DEPTH(FEET) = 7.41 TRAVEL TIME(MIN.) = 3.35  
Tc(MIN.) = 56.90  
SUBAREA AREA(ACRES) = 53.83 SUBAREA RUNOFF(CFS) = 39.64  
EFFECTIVE AREA(ACRES) = 2569.33 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 2572.1 PEAK FLOW RATE(CFS) = 1964.19  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 7.38

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 7.38 FLOW VELOCITY(FEET/SEC.) = 10.75  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 27727.16 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 0610401W.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	871.61	24.84	0.30( 0.30)	1.00	621.4	40120.00
2	863.20	26.67	0.30( 0.30)	1.00	652.1	40100.00
TOTAL AREA(ACRES) =						652.1

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

\*\*\*\*\*  
\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	1964.19	56.90	1.118	0.30( 0.30)	1.00	2569.3	11900.00
2	1962.35	57.06	1.116	0.30( 0.30)	1.00	2572.1	11910.00

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 27727.16 FEET.

\*\*\*\*\*  
\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	871.61	24.84	1.783	0.30( 0.30)	1.00	621.4	40120.00
2	863.20	26.67	1.701	0.30( 0.30)	1.00	652.1	40100.00

LONGEST FLOWPATH FROM NODE 40100.00 TO NODE 11927.00 = 10245.00 FEET.

\*\*\*\*\*  
\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap (INCH/HR)	Ae (ACRES)	HEADWATER NODE
1	2425.59	24.84	1.783	0.30( 0.30)	1.00	1743.1	40120.00
2	2439.57	26.67	1.701	0.30( 0.30)	1.00	1856.4	40100.00
3	2468.10	56.90	1.118	0.30( 0.30)	1.00	3221.4	11900.00
4	2465.09	57.06	1.116	0.30( 0.30)	1.00	3224.2	11910.00
TOTAL AREA(ACRES) =						3224.2	

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:  
PEAK FLOW RATE(CFS) = 2468.10 Tc(MIN.) = 56.901  
EFFECTIVE AREA(ACRES) = 3221.40 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 3224.2  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 27727.16 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 399.00 DOWNSTREAM(FEET) = 384.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 986.26 CHANNEL SLOPE = 0.0152
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
\*ESTIMATED CHANNEL HEIGHT(FEET) = 9.37
CHANNEL FLOW THRU SUBAREA(CFS) = 2468.10
FLOW VELOCITY(FEET/SEC.) = 9.16 FLOW DEPTH(FEET) = 9.37
TRAVEL TIME(MIN.) = 1.79 Tc(MIN.) = 58.70
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.50 = 28713.42 FEET.

FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610402W.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM Q Tc Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 71.72 13.60 0.30( 0.30) 1.00 33.3 40200.00
TOTAL AREA (ACRES) = 33.3

FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 2425.59 26.65 1.703 0.30( 0.30) 1.00 1743.1 40120.00
2 2439.57 28.47 1.622 0.30( 0.30) 1.00 1856.4 40100.00
3 2468.10 58.70 1.096 0.30( 0.30) 1.00 3221.4 11900.00
4 2465.09 58.85 1.094 0.30( 0.30) 1.00 3224.2 11910.00
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.50 = 28713.42 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 71.72 13.60 2.693 0.30( 0.30) 1.00 33.3 40200.00
LONGEST FLOWPATH FROM NODE 40200.00 TO NODE 11927.50 = 1999.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 2182.69 13.60 2.693 0.30( 0.30) 1.00 922.7 40200.00

2 2467.63 26.65 1.703 0.30( 0.30) 1.00 1776.4 40120.00
3 2479.20 28.47 1.622 0.30( 0.30) 1.00 1889.7 40100.00
4 2491.96 58.70 1.096 0.30( 0.30) 1.00 3254.7 11900.00
5 2488.89 58.85 1.094 0.30( 0.30) 1.00 3257.5 11910.00
TOTAL AREA (ACRES) = 3257.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 2491.96 Tc(MIN.) = 58.696
EFFECTIVE AREA(ACRES) = 3254.71 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 3257.5
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.50 = 28713.42 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 11927.50 TO NODE 11928.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 384.00 DOWNSTREAM(FEET) = 359.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 647.19 CHANNEL SLOPE = 0.0386
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
\*ESTIMATED CHANNEL HEIGHT(FEET) = 7.65
\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.086
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 78.01 0.30 0.984 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.984
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2519.72
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 13.03
AVERAGE FLOW DEPTH(FEET) = 7.65 TRAVEL TIME(MIN.) = 0.83
Tc(MIN.) = 59.52
SUBAREA AREA(ACRES) = 78.01 SUBAREA RUNOFF(CFS) = 55.52
EFFECTIVE AREA(ACRES) = 3332.72 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA (ACRES) = 3335.5 PEAK FLOW RATE(CFS) = 2491.96

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
\*ESTIMATED CHANNEL HEIGHT(FEET) = 7.61

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 7.61 FLOW VELOCITY(FEET/SEC.) = 12.99
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11928.00 = 29360.61 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 359.00 DOWNSTREAM(FEET) = 341.63
CHANNEL LENGTH THRU SUBAREA(FEET) = 1322.66 CHANNEL SLOPE = 0.0131
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT (FEET) = 9.74  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.068  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 8.18 0.30 0.890 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.890  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 2494.91  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.69  
 AVERAGE FLOW DEPTH (FEET) = 9.74 TRAVEL TIME (MIN.) = 2.54  
 Tc (MIN.) = 62.06  
 SUBAREA AREA (ACRES) = 8.18 SUBAREA RUNOFF (CFS) = 5.90  
 EFFECTIVE AREA (ACRES) = 3340.90 AREA-AVERAGED Fm (INCH/HR) = 0.30  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA (ACRES) = 3343.7 PEAK FLOW RATE (CFS) = 2491.96  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 9.73

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 9.73 FLOW VELOCITY (FEET/SEC.) = 8.69  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11929.00 = 30683.27 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 10  
 -----  
 >>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 3 <<<<<  
 =====

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11841.00 TO NODE 11527.00 IS CODE = 12  
 -----  
 >>>>CLEAR MEMORY BANK # 1 <<<<<  
 =====

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11841.00 TO NODE 12527.00 IS CODE = 15.1  
 -----  
 >>>>DEFINE MEMORY BANK # 1 <<<<<  
 =====

PEAK FLOWRATE TABLE FILE NAME: S18X25.DNA  
 MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	16891.05	38.90	0.30 ( 0.30)	1.00	7699.7	11831.00
2	17269.04	41.07	0.30 ( 0.30)	1.00	8149.8	11801.00
3	19484.28	52.56	0.30 ( 0.30)	1.00	11111.4	11530.00
4	20384.42	59.71	0.30 ( 0.30)	1.00	13605.9	11000.00
5	22298.73	70.25	0.30 ( 0.30)	1.00	18738.3	11330.00
6	22627.08	72.15	0.30 ( 0.30)	1.00	19721.6	11350.00
7	22975.81	75.44	0.30 ( 0.30)	1.00	21433.1	11300.00
8	23115.65	77.03	0.30 ( 0.30)	1.00	22200.3	11130.00
9	22643.41	86.92	0.30 ( 0.30)	1.00	25590.3	11620.00
10	22485.53	89.04	0.30 ( 0.30)	1.00	26262.8	11600.00
11	22019.00	94.91	0.30 ( 0.30)	1.00	27853.1	11111.00
12	21832.20	97.18	0.30 ( 0.30)	1.00	28360.1	10500.00

13	21473.90	101.65	0.30 ( 0.30)	1.00	29218.6	10710.00
14	21235.80	103.95	0.30 ( 0.30)	1.00	29569.4	10410.00
15	20918.29	108.69	0.30 ( 0.30)	1.00	30244.3	10700.00
16	20477.99	115.41	0.30 ( 0.30)	1.00	31136.9	10400.00
17	20244.15	118.03	0.30 ( 0.30)	1.00	31425.5	10200.00
18	19628.83	124.41	0.30 ( 0.30)	1.00	32019.9	10300.00
19	19047.00	129.43	0.30 ( 0.30)	1.00	32209.8	10210.00
20	16600.03	158.26	0.30 ( 0.30)	1.00	32916.6	10100.00
TOTAL AREA (ACRES) =						32916.6

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 12  
 -----  
 >>>>CLEAR MEMORY BANK # 2 <<<<<  
 =====

\*\*\*MEMORY BANK # 2 IS EMPTY - PROCESS IGNORED.\*\*\*

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 15.1  
 -----  
 >>>>DEFINE MEMORY BANK # 2 <<<<<  
 =====

PEAK FLOWRATE TABLE FILE NAME: S25X25.DNA  
 MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	5840.09	69.19	0.30 ( 0.30)	0.99	6331.6	12500.00
2	6596.78	83.06	0.30 ( 0.30)	0.99	8310.4	12300.00
3	6685.50	84.54	0.30 ( 0.30)	0.98	8607.7	12330.00
4	6818.17	87.39	0.30 ( 0.30)	0.98	9133.8	12410.00
5	6967.16	91.70	0.30 ( 0.29)	0.98	9855.5	12400.00
6	7051.85	96.73	0.30 ( 0.29)	0.98	10551.8	12211.00
7	7157.86	100.97	0.30 ( 0.29)	0.98	11151.2	12201.00
8	7157.25	105.22	0.30 ( 0.29)	0.98	11623.9	12111.00
9	7110.02	108.20	0.30 ( 0.29)	0.98	11957.2	12231.00
10	7048.35	111.16	0.30 ( 0.29)	0.98	12251.1	12101.10
11	7025.02	112.24	0.30 ( 0.29)	0.98	12348.3	12261.00
12	6564.46	124.38	0.30 ( 0.29)	0.98	13114.4	12010.00
13	6112.24	133.26	0.30 ( 0.29)	0.98	13237.1	12000.00
TOTAL AREA (ACRES) =						13237.1

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 14.0  
 -----  
 >>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<  
 =====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	5840.09	69.19	0.30 ( 0.30)	0.99	6331.6	12500.00
2	6596.78	83.06	0.30 ( 0.30)	0.99	8310.4	12300.00
3	6685.50	84.54	0.30 ( 0.30)	0.98	8607.7	12330.00
4	6818.17	87.39	0.30 ( 0.30)	0.98	9133.8	12410.00
5	6967.16	91.70	0.30 ( 0.29)	0.98	9855.5	12400.00
6	7051.85	96.73	0.30 ( 0.29)	0.98	10551.8	12211.00
7	7157.86	100.97	0.30 ( 0.29)	0.98	11151.2	12201.00
8	7157.25	105.22	0.30 ( 0.29)	0.98	11623.9	12111.00

9	7110.02	108.20	0.30	( 0.29)	0.98	11957.2	12231.00
10	7048.35	111.16	0.30	( 0.29)	0.98	12251.1	12101.10
11	7025.02	112.24	0.30	( 0.29)	0.98	12348.3	12261.00
12	6564.46	124.38	0.30	( 0.29)	0.98	13114.4	12010.00
13	6112.24	133.26	0.30	( 0.29)	0.98	13237.1	12000.00

TOTAL AREA (ACRES) = 13237.1

\*\*\*\*\*

FLOW PROCESS FROM NODE 11841.00 TO NODE 12527.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	5840.09	69.19	1.029	0.30( 0.30)	0.99	6331.6	12500.00
2	6596.78	83.06	0.951	0.30( 0.30)	0.99	8310.4	12300.00
3	6685.50	84.54	0.943	0.30( 0.30)	0.98	8607.7	12330.00
4	6818.17	87.39	0.927	0.30( 0.30)	0.98	9133.8	12410.00
5	6967.16	91.70	0.906	0.30( 0.29)	0.98	9855.5	12400.00
6	7051.85	96.73	0.888	0.30( 0.29)	0.98	10551.8	12211.00
7	7157.86	100.97	0.872	0.30( 0.29)	0.98	11151.2	12201.00
8	7157.25	105.22	0.857	0.30( 0.29)	0.98	11623.9	12111.00
9	7110.02	108.20	0.846	0.30( 0.29)	0.98	11957.2	12231.00
10	7048.35	111.16	0.835	0.30( 0.29)	0.98	12251.1	12101.10
11	7025.02	112.24	0.831	0.30( 0.29)	0.98	12348.3	12261.00
12	6564.46	124.38	0.793	0.30( 0.29)	0.98	13114.4	12010.00
13	6112.24	133.26	0.774	0.30( 0.29)	0.98	13237.1	12000.00

LONGEST FLOWPATH FROM NODE 12000.00 TO NODE 12527.00 = 77156.98 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	16891.05	38.90	1.378	0.30( 0.30)	1.00	7699.7	11831.00
2	17269.04	41.07	1.340	0.30( 0.30)	1.00	8149.8	11801.00
3	19484.28	52.56	1.172	0.30( 0.30)	1.00	11111.4	11530.00
4	20384.42	59.71	1.084	0.30( 0.30)	1.00	13605.9	11000.00
5	22298.73	70.25	1.023	0.30( 0.30)	1.00	18738.3	11330.00
6	22627.08	72.15	1.012	0.30( 0.30)	1.00	19721.6	11350.00
7	22975.81	75.44	0.994	0.30( 0.30)	1.00	21433.1	11300.00
8	23115.65	77.03	0.985	0.30( 0.30)	1.00	22200.3	11130.00
9	22643.41	86.92	0.929	0.30( 0.30)	1.00	25590.3	11620.00
10	22485.53	89.04	0.917	0.30( 0.30)	1.00	26262.8	11600.00
11	22019.00	94.91	0.894	0.30( 0.30)	1.00	27853.1	11111.00
12	21832.20	97.18	0.886	0.30( 0.30)	1.00	28360.1	10500.00
13	21473.90	101.65	0.870	0.30( 0.30)	1.00	29218.6	10710.00
14	21235.80	103.95	0.861	0.30( 0.30)	1.00	29569.4	10410.00
15	20918.29	108.69	0.844	0.30( 0.30)	1.00	30244.3	10700.00
16	20477.99	115.41	0.820	0.30( 0.30)	1.00	31136.9	10400.00
17	20244.15	118.03	0.810	0.30( 0.30)	1.00	31425.5	10200.00
18	19628.83	124.41	0.793	0.30( 0.30)	1.00	32019.9	10300.00
19	19047.00	129.43	0.782	0.30( 0.30)	1.00	32209.8	10210.00
20	16600.03	158.26	0.719	0.30( 0.30)	1.00	32916.6	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12527.00 = 97868.13 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	--------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE	
1	21740.24	38.90	1.378	0.30( 0.30)	0.99	11259.4	11831.00
2	22207.96	41.07	1.340	0.30( 0.30)	0.99	11908.7	11801.00
3	24786.46	52.56	1.172	0.30( 0.30)	0.99	15920.9	11530.00
4	25802.98	59.71	1.084	0.30( 0.30)	0.99	19070.2	11000.00
5	27946.32	69.19	1.029	0.30( 0.30)	0.99	24553.8	12500.00
6	28196.63	70.25	1.023	0.30( 0.30)	0.99	25221.1	11330.00
7	28628.91	72.15	1.012	0.30( 0.30)	0.99	26476.2	11350.00
8	29156.91	75.44	0.994	0.30( 0.30)	0.99	28656.5	11300.00
9	29383.42	77.03	0.985	0.30( 0.30)	0.99	29650.4	11130.00
10	29424.60	83.06	0.951	0.30( 0.30)	0.99	32577.0	12300.00
11	29442.55	84.54	0.943	0.30( 0.30)	0.99	33382.3	12330.00
12	29439.82	86.92	0.929	0.30( 0.30)	0.99	34637.9	11620.00
13	29426.78	87.39	0.927	0.30( 0.30)	0.99	34872.4	12410.00
14	29360.88	89.04	0.917	0.30( 0.30)	0.99	35673.5	11600.00
15	29241.66	91.70	0.906	0.30( 0.30)	0.99	36837.6	12400.00
16	29040.22	94.91	0.894	0.30( 0.30)	0.99	38153.0	11111.00
17	28921.00	96.73	0.888	0.30( 0.30)	0.99	38811.6	12211.00
18	28895.27	97.18	0.886	0.30( 0.30)	0.99	38975.3	10500.00
19	28686.30	100.97	0.872	0.30( 0.30)	0.99	40239.2	12201.00
20	28631.67	101.65	0.870	0.30( 0.30)	0.99	40445.6	10710.00
21	28393.24	103.95	0.861	0.30( 0.30)	0.99	41052.8	10410.00
22	28308.43	105.22	0.857	0.30( 0.30)	0.99	41373.2	12111.00
23	28060.91	108.20	0.846	0.30( 0.30)	0.99	42132.2	12231.00
24	28018.20	108.69	0.844	0.30( 0.30)	0.99	42249.7	10700.00
25	27804.43	111.16	0.835	0.30( 0.30)	0.99	42824.2	12101.10
26	27710.28	112.24	0.831	0.30( 0.30)	0.99	43065.0	12261.00
27	27382.95	115.41	0.820	0.30( 0.30)	0.99	43684.9	10400.00
28	27049.59	118.03	0.810	0.30( 0.30)	0.99	44139.1	10200.00
29	26196.32	124.38	0.793	0.30( 0.30)	0.99	45131.3	12010.00
30	26191.70	124.41	0.793	0.30( 0.30)	0.99	45134.7	10300.00
31	25354.30	129.43	0.782	0.30( 0.30)	0.99	45393.9	10210.00
32	24834.19	133.26	0.774	0.30( 0.30)	0.99	45540.7	12000.00
33	22017.66	158.26	0.719	0.30( 0.30)	0.99	46153.7	10100.00

TOTAL AREA (ACRES) = 46153.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 29442.55 Tc(MIN.) = 84.542  
EFFECTIVE AREA(ACRES) = 33382.26 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA(ACRES) = 46153.7  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12527.00 = 97868.13 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12527.00 TO NODE 11929.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 347.47 DOWNSTREAM(FEET) = 341.63  
CHANNEL LENGTH THRU SUBAREA(FEET) = 532.38 CHANNEL SLOPE = 0.0110  
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 8.43  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.939  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ LAND USE SCS SOIL GROUP AREA (ACRES) Fp (INCH/HR) Ap (DECIMAL) SCS CN

USER-DEFINED - 14.37 0.30 0.987 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.987  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 29446.71  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 14.43  
 AVERAGE FLOW DEPTH (FEET) = 8.43 TRAVEL TIME (MIN.) = 0.61  
 Tc (MIN.) = 85.16  
 SUBAREA AREA (ACRES) = 14.37 SUBAREA RUNOFF (CFS) = 8.32  
 EFFECTIVE AREA (ACRES) = 33396.63 AREA-AVERAGED Fm (INCH/HR) = 0.30  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA (ACRES) = 46168.0 PEAK FLOW RATE (CFS) = 29442.55  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 8.43

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 8.43 FLOW VELOCITY (FEET/SEC.) = 14.43  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21740.24	39.58	1.364	0.30 ( 0.30)	0.99	11273.8	11831.00
2	22207.96	41.75	1.329	0.30 ( 0.30)	0.99	11923.1	11801.00
3	24786.46	53.21	1.164	0.30 ( 0.30)	0.99	15935.3	11530.00
4	25802.98	60.35	1.078	0.30 ( 0.30)	0.99	19084.6	11000.00
5	27946.32	69.81	1.025	0.30 ( 0.30)	0.99	24568.2	12500.00
6	28196.63	70.87	1.019	0.30 ( 0.30)	0.99	25235.5	11330.00
7	28628.91	72.77	1.008	0.30 ( 0.30)	0.99	26490.6	11350.00
8	29156.91	76.06	0.990	0.30 ( 0.30)	0.99	28670.9	11300.00
9	29383.42	77.64	0.981	0.30 ( 0.30)	0.99	29664.8	11130.00
10	29424.60	83.67	0.947	0.30 ( 0.30)	0.99	32591.4	12300.00
11	29442.55	85.16	0.939	0.30 ( 0.30)	0.99	33396.6	12330.00
12	29439.82	87.54	0.926	0.30 ( 0.30)	0.99	34652.2	11620.00
13	29426.78	88.01	0.923	0.30 ( 0.30)	0.99	34886.8	12410.00
14	29360.88	89.66	0.914	0.30 ( 0.30)	0.99	35687.9	11600.00
15	29241.66	92.31	0.904	0.30 ( 0.30)	0.99	36852.0	12400.00
16	29040.22	95.53	0.892	0.30 ( 0.30)	0.99	38167.4	11111.00
17	28921.00	97.35	0.885	0.30 ( 0.30)	0.99	38826.0	12211.00
18	28895.27	97.80	0.884	0.30 ( 0.30)	0.99	38989.7	10500.00
19	28686.30	101.59	0.870	0.30 ( 0.30)	0.99	40253.5	12201.00
20	28631.67	102.27	0.867	0.30 ( 0.30)	0.99	40460.0	10710.00
21	28393.24	104.58	0.859	0.30 ( 0.30)	0.99	41067.2	10410.00
22	28308.43	105.84	0.854	0.30 ( 0.30)	0.99	41387.6	12111.00
23	28060.91	108.83	0.844	0.30 ( 0.30)	0.99	42146.6	12231.00
24	28018.20	109.31	0.842	0.30 ( 0.30)	0.99	42264.1	10700.00
25	27804.43	111.79	0.833	0.30 ( 0.30)	0.99	42838.6	12101.10
26	27710.28	112.87	0.829	0.30 ( 0.30)	0.99	43079.4	12261.00
27	27382.95	116.04	0.817	0.30 ( 0.30)	0.99	43699.3	10400.00
28	27049.59	118.66	0.808	0.30 ( 0.30)	0.99	44153.4	10200.00
29	26196.32	125.02	0.792	0.30 ( 0.30)	0.99	45145.7	12010.00

30	26191.70	125.05	0.792	0.30 ( 0.30)	0.99	45149.1	10300.00
31	25354.30	130.08	0.781	0.30 ( 0.30)	0.99	45408.3	10210.00
32	24834.19	133.91	0.773	0.30 ( 0.30)	0.99	45555.1	12000.00
33	22017.66	158.94	0.718	0.30 ( 0.30)	0.99	46168.0	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2182.69	17.07	2.294	0.30 ( 0.30)	1.00	1008.9	40200.00
2	2467.63	30.02	1.555	0.30 ( 0.30)	1.00	1862.6	40120.00
3	2479.20	31.84	1.518	0.30 ( 0.30)	1.00	1975.9	40100.00
4	2491.96	62.06	1.068	0.30 ( 0.30)	1.00	3340.9	11900.00
5	2488.89	62.22	1.068	0.30 ( 0.30)	1.00	3343.7	11910.00

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11929.00 = 30683.27 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19729.32	17.07	2.294	0.30 ( 0.30)	0.99	5870.6	40200.00
2	21896.69	30.02	1.555	0.30 ( 0.30)	0.99	10412.5	40120.00
3	22492.75	31.84	1.518	0.30 ( 0.30)	0.99	11044.4	40100.00
4	24222.71	39.58	1.364	0.30 ( 0.30)	0.99	13599.4	11831.00
5	24691.35	41.75	1.329	0.30 ( 0.30)	0.99	14346.7	11801.00
6	27274.68	53.21	1.164	0.30 ( 0.30)	0.99	18876.4	11530.00
7	28294.22	60.35	1.078	0.30 ( 0.30)	0.99	22348.4	11000.00
8	28681.44	62.06	1.068	0.30 ( 0.30)	0.99	23414.3	11900.00
9	28714.06	62.22	1.068	0.30 ( 0.30)	0.99	23508.4	11910.00
10	30297.43	69.81	1.025	0.30 ( 0.30)	0.99	27911.9	12500.00
11	30528.55	70.87	1.019	0.30 ( 0.30)	0.99	28579.2	11330.00
12	30926.35	72.77	1.008	0.30 ( 0.30)	0.99	29834.3	11350.00
13	31394.82	76.06	0.990	0.30 ( 0.30)	0.99	32014.6	11300.00
14	31592.54	77.64	0.981	0.30 ( 0.30)	0.99	33008.5	11130.00
15	31524.36	83.67	0.947	0.30 ( 0.30)	0.99	35935.1	12300.00
16	31515.43	85.16	0.939	0.30 ( 0.30)	0.99	36740.4	12330.00
17	31469.51	87.54	0.926	0.30 ( 0.30)	0.99	37995.9	11620.00
18	31447.99	88.01	0.923	0.30 ( 0.30)	0.99	38230.5	12410.00
19	31352.12	89.66	0.914	0.30 ( 0.30)	0.99	39031.6	11600.00
20	31199.50	92.31	0.904	0.30 ( 0.30)	0.99	40195.7	12400.00
21	30960.24	95.53	0.892	0.30 ( 0.30)	0.99	41511.1	11111.00
22	30819.60	97.35	0.885	0.30 ( 0.30)	0.99	42169.7	12211.00
23	30788.58	97.80	0.884	0.30 ( 0.30)	0.99	42333.4	10500.00
24	30534.96	101.59	0.870	0.30 ( 0.30)	0.99	43597.3	12201.00
25	30472.31	102.27	0.867	0.30 ( 0.30)	0.99	43803.7	10710.00
26	30206.76	104.58	0.859	0.30 ( 0.30)	0.99	44410.9	10410.00
27	30107.10	105.84	0.854	0.30 ( 0.30)	0.99	44731.3	12111.00
28	29824.43	108.83	0.844	0.30 ( 0.30)	0.99	45490.3	12231.00
29	29776.00	109.31	0.842	0.30 ( 0.30)	0.99	45607.8	10700.00
30	29533.08	111.79	0.833	0.30 ( 0.30)	0.99	46182.3	12101.10
31	29426.21	112.87	0.829	0.30 ( 0.30)	0.99	46423.1	12261.00
32	29061.62	116.04	0.817	0.30 ( 0.30)	0.99	47043.0	10400.00
33	28697.38	118.66	0.808	0.30 ( 0.30)	0.99	47497.2	10200.00
34	27792.88	125.02	0.792	0.30 ( 0.30)	0.99	48489.4	12010.00
35	27788.03	125.05	0.792	0.30 ( 0.30)	0.99	48492.8	10300.00
36	26915.11	130.08	0.781	0.30 ( 0.30)	0.99	48752.0	10210.00
37	26367.88	133.91	0.773	0.30 ( 0.30)	0.99	48898.8	12000.00
38	23374.39	158.94	0.718	0.30 ( 0.30)	0.99	49511.8	10100.00

TOTAL AREA (ACRES) = 49511.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 31592.54 Tc(MIN.) = 77.644  
 EFFECTIVE AREA(ACRES) = 33008.50 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 49511.8  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

=====  
 END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 49511.8 TC(MIN.) = 77.64  
 EFFECTIVE AREA(ACRES) = 33008.50 AREA-AVERAGED Fm(INCH/HR)= 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.994  
 PEAK FLOW RATE(CFS) = 31592.54

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19729.32	17.07	2.294	0.30( 0.30)	0.99	5870.6	40200.00
2	21896.69	30.02	1.555	0.30( 0.30)	0.99	10412.5	40120.00
3	22492.75	31.84	1.518	0.30( 0.30)	0.99	11044.4	40100.00
4	24222.71	39.58	1.364	0.30( 0.30)	0.99	13599.4	11831.00
5	24691.35	41.75	1.329	0.30( 0.30)	0.99	14346.7	11801.00
6	27274.68	53.21	1.164	0.30( 0.30)	0.99	18876.4	11530.00
7	28294.22	60.35	1.078	0.30( 0.30)	0.99	22348.4	11000.00
8	28681.44	62.06	1.068	0.30( 0.30)	0.99	23414.3	11900.00
9	28714.06	62.22	1.068	0.30( 0.30)	0.99	23508.4	11910.00
10	30297.43	69.81	1.025	0.30( 0.30)	0.99	27911.9	12500.00
11	30528.55	70.87	1.019	0.30( 0.30)	0.99	28579.2	11330.00
12	30926.35	72.77	1.008	0.30( 0.30)	0.99	29834.3	11350.00
13	31394.82	76.06	0.990	0.30( 0.30)	0.99	32014.6	11300.00
14	31592.54	77.64	0.981	0.30( 0.30)	0.99	33008.5	11130.00
15	31524.36	83.67	0.947	0.30( 0.30)	0.99	35935.1	12300.00
16	31515.43	85.16	0.939	0.30( 0.30)	0.99	36740.4	12330.00
17	31469.51	87.54	0.926	0.30( 0.30)	0.99	37995.9	11620.00
18	31447.99	88.01	0.923	0.30( 0.30)	0.99	38230.5	12410.00
19	31352.12	89.66	0.914	0.30( 0.30)	0.99	39031.6	11600.00
20	31199.50	92.31	0.904	0.30( 0.30)	0.99	40195.7	12400.00
21	30960.24	95.53	0.892	0.30( 0.30)	0.99	41511.1	11111.00
22	30819.60	97.35	0.885	0.30( 0.30)	0.99	42169.7	12211.00
23	30788.58	97.80	0.884	0.30( 0.30)	0.99	42333.4	10500.00
24	30534.96	101.59	0.870	0.30( 0.30)	0.99	43597.3	12201.00
25	30472.31	102.27	0.867	0.30( 0.30)	0.99	43803.7	10710.00
26	30206.76	104.58	0.859	0.30( 0.30)	0.99	44410.9	10410.00
27	30107.10	105.84	0.854	0.30( 0.30)	0.99	44731.3	12111.00
28	29824.43	108.83	0.844	0.30( 0.30)	0.99	45490.3	12231.00
29	29776.00	109.31	0.842	0.30( 0.30)	0.99	45607.8	10700.00
30	29533.08	111.79	0.833	0.30( 0.30)	0.99	46182.3	12101.10
31	29426.21	112.87	0.829	0.30( 0.30)	0.99	46423.1	12261.00
32	29061.62	116.04	0.817	0.30( 0.30)	0.99	47043.0	10400.00
33	28697.38	118.66	0.808	0.30( 0.30)	0.99	47497.2	10200.00
34	27792.88	125.02	0.792	0.30( 0.30)	0.99	48489.4	12010.00
35	27788.03	125.05	0.792	0.30( 0.30)	0.99	48492.8	10300.00
36	26915.11	130.08	0.781	0.30( 0.30)	0.99	48752.0	10210.00
37	26367.88	133.91	0.773	0.30( 0.30)	0.99	48898.8	12000.00
38	23374.39	158.94	0.718	0.30( 0.30)	0.99	49511.8	10100.00

=====  
 END OF RATIONAL METHOD ANALYSIS





\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S26- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 25-YR RM EV APRIL 2019 CCHIU \*  
\*\*\*\*\*

FILE NAME: RI25EV26.DAT  
TIME/DATE OF STUDY: 09:47 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 25.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 4.986
- 2) 10.00; 3.244
- 3) 15.00; 2.468
- 4) 20.00; 2.035
- 5) 25.00; 1.773
- 6) 30.00; 1.553
- 7) 40.00; 1.354
- 8) 50.00; 1.201
- 9) 60.00; 1.077
- 10) 90.00; 0.909
- 11) 120.00; 0.800
- 12) 180.00; 0.670
- 13) 360.00; 0.498
- 14) 1200.00; 0.220

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI25EV19.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19729.32	17.07	0.30 ( 0.30)	0.99	5870.6	40200.00
2	22492.75	31.84	0.30 ( 0.30)	0.99	11044.4	40100.00
3	24691.35	41.75	0.30 ( 0.30)	0.99	14346.7	11801.00
4	27274.68	53.21	0.30 ( 0.30)	0.99	18876.4	11530.00
5	28714.06	62.22	0.30 ( 0.30)	0.99	23508.4	11910.00
6	30926.35	72.77	0.30 ( 0.30)	0.99	29834.3	11350.00
7	31592.54	77.64	0.30 ( 0.30)	0.99	33008.5	11130.00
8	31524.36	83.67	0.30 ( 0.30)	0.99	35935.1	12300.00
9	31469.51	87.54	0.30 ( 0.30)	0.99	37995.9	11620.00
10	31199.50	92.31	0.30 ( 0.30)	0.99	40195.7	12400.00
11	30960.24	95.53	0.30 ( 0.30)	0.99	41511.1	11111.00
12	30534.96	101.59	0.30 ( 0.30)	0.99	43597.3	12201.00
13	29824.43	108.83	0.30 ( 0.30)	0.99	45490.3	12311.00
14	29533.08	111.79	0.30 ( 0.30)	0.99	46182.3	12101.10
15	29061.62	116.04	0.30 ( 0.30)	0.99	47043.0	10400.00
16	28697.38	118.66	0.30 ( 0.30)	0.99	47497.2	10200.00
17	27792.88	125.02	0.30 ( 0.30)	0.99	48489.4	12010.00
18	26915.11	130.08	0.30 ( 0.30)	0.99	48752.0	10210.00
19	26367.88	133.91	0.30 ( 0.30)	0.99	48898.8	12000.00
20	23374.39	158.94	0.30 ( 0.30)	0.99	49511.8	10100.00
TOTAL AREA (ACRES) =						49511.8

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19729.32	17.07	0.30 ( 0.30)	0.99	5870.6	40200.00
2	22492.75	31.84	0.30 ( 0.30)	0.99	11044.4	40100.00
3	24691.35	41.75	0.30 ( 0.30)	0.99	14346.7	11801.00
4	27274.68	53.21	0.30 ( 0.30)	0.99	18876.4	11530.00
5	28714.06	62.22	0.30 ( 0.30)	0.99	23508.4	11910.00
6	30926.35	72.77	0.30 ( 0.30)	0.99	29834.3	11350.00
7	31592.54	77.64	0.30 ( 0.30)	0.99	33008.5	11130.00
8	31524.36	83.67	0.30 ( 0.30)	0.99	35935.1	12300.00
9	31469.51	87.54	0.30 ( 0.30)	0.99	37995.9	11620.00
10	31199.50	92.31	0.30 ( 0.30)	0.99	40195.7	12400.00
11	30960.24	95.53	0.30 ( 0.30)	0.99	41511.1	11111.00
12	30534.96	101.59	0.30 ( 0.30)	0.99	43597.3	12201.00
13	29824.43	108.83	0.30 ( 0.30)	0.99	45490.3	12231.00

14	29533.08	111.79	0.30	( 0.30)	0.99	46182.3	12101.10
15	29061.62	116.04	0.30	( 0.30)	0.99	47043.0	10400.00
16	28697.38	118.66	0.30	( 0.30)	0.99	47497.2	10200.00
17	27792.88	125.02	0.30	( 0.30)	0.99	48489.4	12010.00
18	26915.11	130.08	0.30	( 0.30)	0.99	48752.0	10210.00
19	26367.88	133.91	0.30	( 0.30)	0.99	48898.8	12000.00
20	23374.39	158.94	0.30	( 0.30)	0.99	49511.8	10100.00

TOTAL AREA (ACRES) = 49511.8

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 1 <<<<<<  
=====

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11929.00 TO NODE 12601.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<<  
=====

ELEVATION DATA: UPSTREAM (FEET) = 341.63 DOWNSTREAM (FEET) = 325.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1467.93 CHANNEL SLOPE = 0.0113  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT (FEET) = 7.38

\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.971

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	14.11	0.30	0.700	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.700

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 31597.38

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 18.07

AVERAGE FLOW DEPTH (FEET) = 7.38 TRAVEL TIME (MIN.) = 1.35

Tc (MIN.) = 79.00

SUBAREA AREA (ACRES) = 14.11 SUBAREA RUNOFF (CFS) = 9.66

EFFECTIVE AREA (ACRES) = 33022.61 AREA-AVERAGED Fm (INCH/HR) = 0.30

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA (ACRES) = 49525.9 PEAK FLOW RATE (CFS) = 31592.54

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT (FEET) = 7.37

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 7.37 FLOW VELOCITY (FEET/SEC.) = 18.09

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 2 <<<<<<  
=====

PEAK FLOWRATE TABLE FILE NAME: 3025EVRL.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM	Q	Tc	Fp (Fm)	Ap	Ae	HEADWATER
--------	---	----	---------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(ACRES)	NODE
1	87.91	16.79	0.30 ( 0.30)	0.98	48.4 600.00
TOTAL AREA (ACRES) =			48.4		

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<<  
=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19729.32	18.66	2.151	0.30 ( 0.30)	0.99	5884.7	40200.00
2	22492.75	33.36	1.486	0.30 ( 0.30)	0.99	11058.5	40100.00
3	24691.35	43.22	1.305	0.30 ( 0.30)	0.99	14360.8	11801.00
4	27274.68	54.63	1.144	0.30 ( 0.30)	0.99	18890.5	11530.00
5	28714.06	63.61	1.057	0.30 ( 0.30)	0.99	23522.6	11910.00
6	30926.35	74.14	0.998	0.30 ( 0.30)	0.99	29848.4	11350.00
7	31592.54	79.00	0.971	0.30 ( 0.30)	0.99	33022.6	11130.00
8	31524.36	85.03	0.937	0.30 ( 0.30)	0.99	35949.2	12300.00
9	31469.51	88.89	0.915	0.30 ( 0.30)	0.99	38010.1	11620.00
10	31199.50	93.67	0.896	0.30 ( 0.30)	0.99	40209.8	12400.00
11	30960.24	96.89	0.884	0.30 ( 0.30)	0.99	41525.2	11111.00
12	30534.96	102.96	0.862	0.30 ( 0.30)	0.99	43611.4	12201.00
13	29824.43	110.21	0.836	0.30 ( 0.30)	0.99	45504.4	12231.00
14	29533.08	113.17	0.825	0.30 ( 0.30)	0.99	46196.4	12101.10
15	29061.62	117.43	0.809	0.30 ( 0.30)	0.99	47057.1	10400.00
16	28697.38	120.06	0.800	0.30 ( 0.30)	0.99	47511.3	10200.00
17	27792.88	126.43	0.786	0.30 ( 0.30)	0.99	48503.5	12010.00
18	26915.11	131.50	0.775	0.30 ( 0.30)	0.99	48766.1	10210.00
19	26367.88	135.35	0.767	0.30 ( 0.30)	0.99	48912.9	12000.00
20	23374.39	160.44	0.712	0.30 ( 0.30)	0.99	49525.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	87.91	16.79	2.313	0.30 ( 0.30)	0.98	48.4	600.00

LONGEST FLOWPATH FROM NODE 600.00 TO NODE 12601.00 = 4850.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19389.94	16.79	2.313	0.30 ( 0.30)	0.99	5342.3	600.00
2	19810.16	18.66	2.151	0.30 ( 0.30)	0.99	5933.1	40200.00
3	22544.63	33.36	1.486	0.30 ( 0.30)	0.99	11106.9	40100.00
4	24735.32	43.22	1.305	0.30 ( 0.30)	0.99	14409.2	11801.00
5	27311.64	54.63	1.144	0.30 ( 0.30)	0.99	18938.9	11530.00
6	28747.24	63.61	1.057	0.30 ( 0.30)	0.99	23571.0	11910.00
7	30956.95	74.14	0.998	0.30 ( 0.30)	0.99	29896.8	11350.00
8	31621.97	79.00	0.971	0.30 ( 0.30)	0.99	33071.0	11130.00
9	31552.31	85.03	0.937	0.30 ( 0.30)	0.99	35997.6	12300.00
10	31496.52	88.89	0.915	0.30 ( 0.30)	0.99	38058.4	11620.00
11	31225.65	93.67	0.896	0.30 ( 0.30)	0.99	40258.2	12400.00
12	30985.88	96.89	0.884	0.30 ( 0.30)	0.99	41573.6	11111.00
13	30559.64	102.96	0.862	0.30 ( 0.30)	0.99	43659.8	12201.00
14	29847.97	110.21	0.836	0.30 ( 0.30)	0.99	45552.8	12231.00

15	29556.15	113.17	0.825	0.30	( 0.30)	0.99	46244.8	12101.10
16	29084.01	117.43	0.809	0.30	( 0.30)	0.99	47105.5	10400.00
17	28719.37	120.06	0.800	0.30	( 0.30)	0.99	47559.7	10200.00
18	27814.26	126.43	0.786	0.30	( 0.30)	0.99	48551.9	12010.00
19	26936.02	131.50	0.775	0.30	( 0.30)	0.99	48814.5	10210.00
20	26388.42	135.35	0.767	0.30	( 0.30)	0.99	48961.3	12000.00
21	23392.56	160.44	0.712	0.30	( 0.30)	0.99	49574.3	10100.00

TOTAL AREA (ACRES) = 49574.3

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 31621.97 Tc (MIN.) = 78.998  
EFFECTIVE AREA (ACRES) = 33071.00 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 49574.3  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 12  
-----  
>>>>CLEAR MEMORY BANK # 2 <<<<<<  
=====

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12601.00 TO NODE 12602.00 IS CODE = 56  
-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<<  
=====

ELEVATION DATA: UPSTREAM (FEET) = 325.00 DOWNSTREAM (FEET) = 313.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1377.46 CHANNEL SLOPE = 0.0087  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 7.95  
CHANNEL FLOW THRU SUBAREA (CFS) = 31621.97  
FLOW VELOCITY (FEET/SEC.) = 16.58 FLOW DEPTH (FEET) = 7.95  
TRAVEL TIME (MIN.) = 1.38 Tc (MIN.) = 80.38  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12602.00 = 101245.91 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12602.00 TO NODE 12603.00 IS CODE = 56  
-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<<  
=====

ELEVATION DATA: UPSTREAM (FEET) = 313.00 DOWNSTREAM (FEET) = 310.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 312.40 CHANNEL SLOPE = 0.0096  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 7.74  
CHANNEL FLOW THRU SUBAREA (CFS) = 31621.97  
FLOW VELOCITY (FEET/SEC.) = 17.12 FLOW DEPTH (FEET) = 7.74  
TRAVEL TIME (MIN.) = 0.30 Tc (MIN.) = 80.69  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.30 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 15.1  
-----  
>>>>DEFINE MEMORY BANK # 1 <<<<<<  
-----

=====

PEAK FLOWRATE TABLE FILE NAME: 0610403W.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	285.71	19.21	2.103	0.30 ( 0.29)	0.97	175.0	40300.00
TOTAL AREA (ACRES) =				175.0			

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 11  
-----  
>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<<  
=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19389.94	18.78	2.141	0.30 ( 0.30)	0.99	5342.3	600.00
2	19810.16	20.64	2.001	0.30 ( 0.30)	0.99	5933.1	40200.00
3	22544.63	35.25	1.448	0.30 ( 0.30)	0.99	11106.9	40100.00
4	24735.32	45.06	1.277	0.30 ( 0.30)	0.99	14409.2	11801.00
5	27311.64	56.40	1.122	0.30 ( 0.30)	0.99	18938.9	11530.00
6	28747.24	65.36	1.047	0.30 ( 0.30)	0.99	23571.0	11910.00
7	30956.95	75.84	0.988	0.30 ( 0.30)	0.99	29896.8	11350.00
8	31621.97	80.69	0.961	0.30 ( 0.30)	0.99	33071.0	11130.00
9	31552.31	86.72	0.927	0.30 ( 0.30)	0.99	35997.6	12300.00
10	31496.52	90.58	0.907	0.30 ( 0.30)	0.99	38058.4	11620.00
11	31225.65	95.37	0.889	0.30 ( 0.30)	0.99	40258.2	12400.00
12	30985.88	98.59	0.878	0.30 ( 0.30)	0.99	41573.6	11111.00
13	30559.64	104.67	0.856	0.30 ( 0.30)	0.99	43659.8	12201.00
14	29847.97	111.93	0.829	0.30 ( 0.30)	0.99	45552.8	12231.00
15	29556.15	114.90	0.819	0.30 ( 0.30)	0.99	46244.8	12101.10
16	29084.01	119.17	0.803	0.30 ( 0.30)	0.99	47105.5	10400.00
17	28719.37	121.81	0.796	0.30 ( 0.30)	0.99	47559.7	10200.00
18	27814.26	128.20	0.782	0.30 ( 0.30)	0.99	48551.9	12010.00
19	26936.02	133.29	0.771	0.30 ( 0.30)	0.99	48814.5	10210.00
20	26388.42	137.14	0.763	0.30 ( 0.30)	0.99	48961.3	12000.00
21	23392.56	162.31	0.708	0.30 ( 0.30)	0.99	49574.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.30 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	285.71	19.21	2.103	0.30 ( 0.29)	0.97	175.0	40300.00

LONGEST FLOWPATH FROM NODE 40300.00 TO NODE 12603.00 = 5256.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19674.99	18.78	2.141	0.30 ( 0.30)	0.99	5513.5	600.00
2	19772.74	19.21	2.103	0.30 ( 0.30)	0.99	5653.9	40300.00
3	20079.82	20.64	2.001	0.30 ( 0.30)	0.99	6108.2	40200.00
4	22727.19	35.25	1.448	0.30 ( 0.30)	0.99	11282.0	40100.00
5	24890.81	45.06	1.277	0.30 ( 0.30)	0.99	14584.2	11801.00
6	27442.70	56.40	1.122	0.30 ( 0.30)	0.99	19113.9	11530.00
7	28866.55	65.36	1.047	0.30 ( 0.30)	0.99	23746.0	11910.00
8	31067.03	75.84	0.988	0.30 ( 0.30)	0.99	30071.8	11350.00
9	31727.76	80.69	0.961	0.30 ( 0.30)	0.99	33246.1	11130.00

10	31652.79	86.72	0.927	0.30	( 0.30)	0.99	36172.6	12300.00
11	31593.77	90.58	0.907	0.30	( 0.30)	0.99	38233.5	11620.00
12	31320.16	95.37	0.889	0.30	( 0.30)	0.99	40433.2	12400.00
13	31078.55	98.59	0.878	0.30	( 0.30)	0.99	41748.7	11111.00
14	30648.83	104.67	0.856	0.30	( 0.30)	0.99	43834.8	12201.00
15	29933.01	111.93	0.829	0.30	( 0.30)	0.99	45727.8	12231.00
16	29639.48	114.90	0.819	0.30	( 0.30)	0.99	46419.9	12101.10
17	29164.90	119.17	0.803	0.30	( 0.30)	0.99	47280.6	10400.00
18	28799.16	121.81	0.796	0.30	( 0.30)	0.99	47734.7	10200.00
19	27891.88	128.20	0.782	0.30	( 0.30)	0.99	48727.0	12010.00
20	27011.89	133.29	0.771	0.30	( 0.30)	0.99	48989.6	10210.00
21	26462.98	137.14	0.763	0.30	( 0.30)	0.99	49136.4	12000.00
22	23458.54	162.31	0.708	0.30	( 0.30)	0.99	49749.3	10100.00
TOTAL AREA (ACRES) =								49749.3

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 31727.76 Tc (MIN.) = 80.686  
EFFECTIVE AREA (ACRES) = 33246.05 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 49749.3  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.30 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 80.69  
\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.961  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.20	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	8.80	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL, NARROWLEAF"	B	0.10	0.30	1.000	72
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.60	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	0.60	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL, NARROWLEAF"	B	2.90	0.30	1.000	72

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 14.20 SUBAREA RUNOFF (CFS) = 8.45  
EFFECTIVE AREA (ACRES) = 33260.25 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 49763.5 PEAK FLOW RATE (CFS) = 31727.76  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 80.69  
\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.961  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	0.30	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.90	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.10	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL, NARROWLEAF"	B	0.70	0.30	1.000	72
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.10	0.30	1.000	66
PUBLIC PARK	B	0.70	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.978  
SUBAREA AREA (ACRES) = 4.80 SUBAREA RUNOFF (CFS) = 2.88  
EFFECTIVE AREA (ACRES) = 33265.05 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 49768.3 PEAK FLOW RATE (CFS) = 31727.76  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 80.69  
\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.961  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	0.20	0.30	0.850	56
RESIDENTIAL					
"11+ DWELLINGS/ACRE"	B	0.10	0.30	0.200	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	1.40	0.30	0.900	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	1.00	0.30	0.900	56
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.30	0.30	1.000	65
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	5.70	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.960  
SUBAREA AREA (ACRES) = 8.70 SUBAREA RUNOFF (CFS) = 5.27  
EFFECTIVE AREA (ACRES) = 33273.75 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 49777.0 PEAK FLOW RATE (CFS) = 31727.76  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```
*****
FLOW PROCESS FROM NODE 12603.00 TO NODE 12604.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 310.00 DOWNSTREAM(FEET) = 307.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 459.69 CHANNEL SLOPE = 0.0065
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 8.66
CHANNEL FLOW THRU SUBAREA(CFS) = 31727.76
FLOW VELOCITY(FEET/SEC.) = 15.07 FLOW DEPTH(FEET) = 8.66
TRAVEL TIME(MIN.) = 0.51 Tc(MIN.) = 81.19
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12604.00 = 102017.99 FEET.
```

```
*****
FLOW PROCESS FROM NODE 12604.00 TO NODE 12604.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 81.19
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.958
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"CHAPARRAL,NARROWLEAF" B 0.10 0.30 1.000 72
NATURAL FAIR COVER
"OPEN BRUSH" B 0.90 0.30 1.000 66
PUBLIC PARK B 0.10 0.30 0.850 56
NATURAL FAIR COVER
"WOODLAND,GRASS" B 0.70 0.30 1.000 65
NATURAL FAIR COVER
"WOODLAND,GRASS" B 0.50 0.30 1.000 65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.993
SUBAREA AREA(ACRES) = 2.30 SUBAREA RUNOFF(CFS) = 1.37
EFFECTIVE AREA(ACRES) = 33276.05 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 49779.3 PEAK FLOW RATE(CFS) = 31727.76
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
```

```
*****
FLOW PROCESS FROM NODE 12604.00 TO NODE 12605.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 307.00 DOWNSTREAM(FEET) = 305.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 427.54 CHANNEL SLOPE = 0.0047
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 9.51
CHANNEL FLOW THRU SUBAREA(CFS) = 31727.76
FLOW VELOCITY(FEET/SEC.) = 13.48 FLOW DEPTH(FEET) = 9.51
TRAVEL TIME(MIN.) = 0.53 Tc(MIN.) = 81.72
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.00 = 102445.53 FEET.
```

```
*****
FLOW PROCESS FROM NODE 12605.00 TO NODE 12605.30 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 305.00 DOWNSTREAM(FEET) = 302.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 217.28 CHANNEL SLOPE = 0.0138
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 6.99
CHANNEL FLOW THRU SUBAREA(CFS) = 31727.76
FLOW VELOCITY(FEET/SEC.) = 19.33 FLOW DEPTH(FEET) = 6.99
TRAVEL TIME(MIN.) = 0.19 Tc(MIN.) = 81.91
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.30 = 102662.81 FEET.
```

```
*****
FLOW PROCESS FROM NODE 12605.30 TO NODE 12605.30 IS CODE = 15.1
-----
>>>>DEFINE MEMORY BANK # 3 <<<<
=====
PEAK FLOWRATE TABLE FILE NAME: 0610404W.DNA
MEMORY BANK # 3 DEFINED AS FOLLOWS:
STREAM Q Tc Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (ACRES) NODE
1 678.70 18.08 0.30( 0.30) 0.99 396.2 40430.00
2 669.61 18.61 0.30( 0.30) 0.99 400.5 40440.00
3 645.94 19.82 0.30( 0.30) 0.99 409.4 40400.00
4 641.61 20.00 0.30( 0.30) 0.99 410.3 40420.00
5 640.93 20.05 0.30( 0.30) 0.99 410.5 40410.00
TOTAL AREA(ACRES) = 410.5
```

```
*****
FLOW PROCESS FROM NODE 12605.30 TO NODE 12605.30 IS CODE = 11
-----
>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<
=====
```

```
** MAIN STREAM CONFLUENCE DATA **
```

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19674.99	20.22	2.024	0.30( 0.30)	0.99	5543.5	600.00
2	19772.74	20.65	2.001	0.30( 0.30)	0.99	5683.9	40300.00
3	20079.82	22.07	1.927	0.30( 0.30)	0.99	6138.2	40200.00
4	22727.19	36.62	1.421	0.30( 0.30)	0.99	11312.0	40100.00
5	24890.81	46.38	1.256	0.30( 0.30)	0.99	14614.2	11801.00
6	27442.70	57.69	1.106	0.30( 0.30)	0.99	19143.9	11530.00
7	28866.55	66.62	1.040	0.30( 0.30)	0.99	23776.0	11910.00
8	31067.03	77.07	0.981	0.30( 0.30)	0.99	30101.8	11350.00
9	31727.76	81.91	0.954	0.30( 0.30)	0.99	33276.1	11130.00
10	31652.79	87.94	0.921	0.30( 0.30)	0.99	36202.6	12300.00
11	31593.77	91.81	0.902	0.30( 0.30)	0.99	38263.5	11620.00
12	31320.16	96.60	0.885	0.30( 0.30)	0.99	40463.2	12400.00
13	31078.55	99.82	0.873	0.30( 0.30)	0.99	41778.7	11111.00
14	30648.83	105.91	0.851	0.30( 0.30)	0.99	43864.8	12201.00
15	29933.01	113.18	0.825	0.30( 0.30)	0.99	45757.8	12231.00
16	29639.48	116.15	0.814	0.30( 0.30)	0.99	46449.9	12101.10

```

17 29164.90 120.43 0.799 0.30( 0.30) 0.99 47310.6 10400.00
18 28799.16 123.07 0.793 0.30( 0.30) 0.99 47764.7 10200.00
19 27891.88 129.48 0.779 0.30( 0.30) 0.99 48757.0 12010.00
20 27011.89 134.58 0.768 0.30( 0.30) 0.99 49019.6 10210.00
21 26462.98 138.45 0.760 0.30( 0.30) 0.99 49166.4 12000.00
22 23458.54 163.66 0.705 0.30( 0.30) 0.99 49779.3 10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.30 = 102662.81 FEET.

```

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	678.70	18.08	2.201	0.30( 0.30)	0.99	396.2	40430.00
2	669.61	18.61	2.155	0.30( 0.30)	0.99	400.5	40440.00
3	645.94	19.82	2.051	0.30( 0.30)	0.99	409.4	40400.00
4	641.61	20.00	2.035	0.30( 0.30)	0.99	410.3	40420.00
5	640.93	20.05	2.033	0.30( 0.30)	0.99	410.5	40410.00

LONGEST FLOWPATH FROM NODE 40400.00 TO NODE 12605.30 = 7428.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20084.29	18.08	2.201	0.30( 0.30)	0.99	5353.6	40430.00
2	20162.71	18.61	2.155	0.30( 0.30)	0.99	5503.9	40440.00
3	20235.16	19.82	2.051	0.30( 0.30)	0.99	5843.6	40400.00
4	20232.97	20.00	2.035	0.30( 0.30)	0.99	5893.0	40420.00
5	20249.89	20.05	2.033	0.30( 0.30)	0.99	5906.4	40410.00
6	20312.56	20.22	2.024	0.30( 0.30)	0.99	5953.9	600.00
7	20402.05	20.65	2.001	0.30( 0.30)	0.99	6094.3	40300.00
8	20681.61	22.07	1.927	0.30( 0.30)	0.99	6548.6	40200.00
9	23142.32	36.62	1.421	0.30( 0.30)	0.99	11722.4	40100.00
10	25245.02	46.38	1.256	0.30( 0.30)	0.99	15024.7	11801.00
11	27741.26	57.69	1.106	0.30( 0.30)	0.99	19554.4	11530.00
12	29140.84	66.62	1.040	0.30( 0.30)	0.99	24186.5	11910.00
13	31319.69	77.07	0.981	0.30( 0.30)	0.99	30512.3	11350.00
14	31970.42	81.91	0.954	0.30( 0.30)	0.99	33686.5	11130.00
15	31882.96	87.94	0.921	0.30( 0.30)	0.99	36613.1	12300.00
16	31817.27	91.81	0.902	0.30( 0.30)	0.99	38674.0	11620.00
17	31537.24	96.60	0.885	0.30( 0.30)	0.99	40873.7	12400.00
18	31291.30	99.82	0.873	0.30( 0.30)	0.99	42189.1	11111.00
19	30853.41	105.91	0.851	0.30( 0.30)	0.99	44275.3	12201.00
20	30127.83	113.18	0.825	0.30( 0.30)	0.99	46168.3	12231.00
21	29830.32	116.15	0.814	0.30( 0.30)	0.99	46860.4	12101.10
22	29350.23	120.43	0.799	0.30( 0.30)	0.99	47721.0	10400.00
23	28982.38	123.07	0.793	0.30( 0.30)	0.99	48175.2	10200.00
24	28069.96	129.48	0.779	0.30( 0.30)	0.99	49167.5	12010.00
25	27185.90	134.58	0.768	0.30( 0.30)	0.99	49430.0	10210.00
26	26633.89	138.45	0.760	0.30( 0.30)	0.99	49576.8	12000.00
27	23609.26	163.66	0.705	0.30( 0.30)	0.99	50189.8	10100.00

TOTAL AREA (ACRES) = 50189.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 31970.42 Tc(MIN.) = 81.911  
EFFECTIVE AREA(ACRES) = 33686.52 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA(ACRES) = 50189.8  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.30 = 102662.81 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.30 TO NODE 12605.30 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.30 TO NODE 12605.60 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 302.00 DOWNSTREAM(FEET) = 295.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 738.76 CHANNEL SLOPE = 0.0095  
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 7.82  
CHANNEL FLOW THRU SUBAREA(CFS) = 31970.42  
FLOW VELOCITY(FEET/SEC.) = 17.11 FLOW DEPTH(FEET) = 7.82  
TRAVEL TIME(MIN.) = 0.72 Tc(MIN.) = 82.63  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.60 = 103401.57 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.60 TO NODE 12605.60 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610405W.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	160.50	14.05	0.30( 0.30)	1.00	77.0	40510.00
2	155.23	15.56	0.30( 0.30)	1.00	81.4	40500.00

TOTAL AREA(ACRES) = 81.4

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.60 TO NODE 12605.60 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20084.29	18.92	2.128	0.30( 0.30)	0.99	5353.6	40430.00
2	20162.71	19.46	2.082	0.30( 0.30)	0.99	5503.9	40440.00
3	20235.16	20.66	2.000	0.30( 0.30)	0.99	5843.6	40400.00
4	20232.97	20.84	1.991	0.30( 0.30)	0.99	5893.0	40420.00
5	20249.89	20.89	1.989	0.30( 0.30)	0.99	5906.4	40410.00
6	20312.56	21.06	1.980	0.30( 0.30)	0.99	5953.9	600.00
7	20402.05	21.48	1.957	0.30( 0.30)	0.99	6094.3	40300.00
8	20681.61	22.90	1.883	0.30( 0.30)	0.99	6548.6	40200.00
9	23142.32	37.42	1.405	0.30( 0.30)	0.99	11722.4	40100.00
10	25245.02	47.16	1.244	0.30( 0.30)	0.99	15024.7	11801.00
11	27741.26	58.44	1.096	0.30( 0.30)	0.99	19554.4	11530.00
12	29140.84	67.37	1.036	0.30( 0.30)	0.99	24186.5	11910.00
13	31319.69	77.80	0.977	0.30( 0.30)	0.99	30512.3	11350.00
14	31970.42	82.63	0.950	0.30( 0.30)	0.99	33686.5	11130.00
15	31882.96	88.67	0.916	0.30( 0.30)	0.99	36613.1	12300.00

16	31817.27	92.53	0.900	0.30( 0.30)	0.99	38674.0	11620.00
17	31537.24	97.32	0.882	0.30( 0.30)	0.99	40873.7	12400.00
18	31291.30	100.55	0.871	0.30( 0.30)	0.99	42189.1	11111.00
19	30853.41	106.64	0.849	0.30( 0.30)	0.99	44275.3	12201.00
20	30127.83	113.91	0.822	0.30( 0.30)	0.99	46168.3	12231.00
21	29830.32	116.89	0.811	0.30( 0.30)	0.99	46860.4	12101.10
22	29350.23	121.17	0.797	0.30( 0.30)	0.99	47721.0	10400.00
23	28982.38	123.81	0.792	0.30( 0.30)	0.99	48175.2	10200.00
24	28069.96	130.23	0.778	0.30( 0.30)	0.99	49167.5	12010.00
25	27185.90	135.34	0.767	0.30( 0.30)	0.99	49430.0	10210.00
26	26633.89	139.21	0.758	0.30( 0.30)	0.99	49576.8	12000.00
27	23609.26	164.46	0.704	0.30( 0.30)	0.99	50189.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.60 = 103401.57 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	160.50	14.05	2.615	0.30( 0.30)	1.00	77.0	40510.00
2	155.23	15.56	2.419	0.30( 0.30)	1.00	81.4	40500.00

LONGEST FLOWPATH FROM NODE 40500.00 TO NODE 12605.60 = 4091.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19040.46	14.05	2.615	0.30( 0.30)	0.99	4051.6	40510.00
2	19298.34	15.56	2.419	0.30( 0.30)	0.99	4484.0	40500.00
3	20218.19	18.92	2.128	0.30( 0.30)	0.99	5435.0	40430.00
4	20293.26	19.46	2.082	0.30( 0.30)	0.99	5585.2	40440.00
5	20359.71	20.66	2.000	0.30( 0.30)	0.99	5925.0	40400.00
6	20356.84	20.84	1.991	0.30( 0.30)	0.99	5974.4	40420.00
7	20373.58	20.89	1.989	0.30( 0.30)	0.99	5987.8	40410.00
8	20435.59	21.06	1.980	0.30( 0.30)	0.99	6035.3	600.00
9	20523.45	21.48	1.957	0.30( 0.30)	0.99	6175.7	40300.00
10	20797.57	22.90	1.883	0.30( 0.30)	0.99	6630.0	40200.00
11	23223.30	37.42	1.405	0.30( 0.30)	0.99	11803.8	40100.00
12	25314.22	47.16	1.244	0.30( 0.30)	0.99	15106.1	11801.00
13	27799.62	58.44	1.096	0.30( 0.30)	0.99	19635.8	11530.00
14	29194.76	67.37	1.036	0.30( 0.30)	0.99	24267.8	11910.00
15	31369.34	77.80	0.977	0.30( 0.30)	0.99	30593.7	11350.00
16	32018.09	82.63	0.950	0.30( 0.30)	0.99	33767.9	11130.00
17	31928.16	88.67	0.916	0.30( 0.30)	0.99	36694.5	12300.00
18	31861.24	92.53	0.900	0.30( 0.30)	0.99	38755.3	11620.00
19	31579.94	97.32	0.882	0.30( 0.30)	0.99	40955.1	12400.00
20	31333.14	100.55	0.871	0.30( 0.30)	0.99	42270.5	11111.00
21	30893.63	106.64	0.849	0.30( 0.30)	0.99	44356.6	12201.00
22	30166.11	113.91	0.822	0.30( 0.30)	0.99	46249.7	12231.00
23	29867.81	116.89	0.811	0.30( 0.30)	0.99	46941.7	12101.10
24	29386.71	121.17	0.797	0.30( 0.30)	0.99	47802.4	10400.00
25	29018.43	123.81	0.792	0.30( 0.30)	0.99	48256.5	10200.00
26	28105.00	130.23	0.778	0.30( 0.30)	0.99	49248.8	12010.00
27	27220.12	135.34	0.767	0.30( 0.30)	0.99	49511.4	10210.00
28	26667.51	139.21	0.758	0.30( 0.30)	0.99	49658.2	12000.00
29	23638.87	164.46	0.704	0.30( 0.30)	0.99	50271.2	10100.00

TOTAL AREA (ACRES) = 50271.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 32018.09 Tc (MIN.) = 82.631  
EFFECTIVE AREA (ACRES) = 33767.89 AREA-AVERAGED Fm (INCH/HR) = 0.30

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 50271.2  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.60 = 103401.57 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.60 TO NODE 12605.60 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.60 TO NODE 12606.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 295.00 DOWNSTREAM (FEET) = 286.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1203.43 CHANNEL SLOPE = 0.0075  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT (FEET) = 8.37  
CHANNEL FLOW THRU SUBAREA (CFS) = 32018.09  
FLOW VELOCITY (FEET/SEC.) = 15.81 FLOW DEPTH (FEET) = 8.37  
TRAVEL TIME (MIN.) = 1.27 Tc (MIN.) = 83.90  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104605.00 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610406W.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	206.23	20.73	0.30( 0.30)	0.99	135.0	40600.00

TOTAL AREA (ACRES) = 135.0

\*\*\*\*\*

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19040.46	15.56	2.419	0.30( 0.30)	0.99	4051.6	40510.00
2	19298.34	17.07	2.289	0.30( 0.30)	0.99	4484.0	40500.00
3	20218.19	20.41	2.014	0.30( 0.30)	0.99	5435.0	40430.00
4	20293.26	20.93	1.986	0.30( 0.30)	0.99	5585.2	40440.00
5	20359.71	22.14	1.923	0.30( 0.30)	0.99	5925.0	40400.00
6	20356.84	22.32	1.914	0.30( 0.30)	0.99	5974.4	40420.00
7	20373.58	22.36	1.911	0.30( 0.30)	0.99	5987.8	40410.00
8	20435.59	22.53	1.902	0.30( 0.30)	0.99	6035.3	600.00
9	20523.45	22.96	1.880	0.30( 0.30)	0.99	6175.7	40300.00
10	20797.57	24.37	1.806	0.30( 0.30)	0.99	6630.0	40200.00
11	23223.30	38.84	1.377	0.30( 0.30)	0.99	11803.8	40100.00



12	25314.22	48.54	1.223	0.30	( 0.30)	0.99	15106.1	11801.00
13	27799.62	59.77	1.080	0.30	( 0.30)	0.99	19635.8	11530.00
14	29194.76	68.67	1.028	0.30	( 0.30)	0.99	24267.8	11910.00
15	31369.34	79.07	0.970	0.30	( 0.30)	0.99	30593.7	11350.00
16	32018.09	83.90	0.943	0.30	( 0.30)	0.99	33767.9	11130.00
17	31928.16	89.93	0.909	0.30	( 0.30)	0.99	36694.5	12300.00
18	31861.24	93.80	0.895	0.30	( 0.30)	0.99	38755.3	11620.00
19	31579.94	98.60	0.878	0.30	( 0.30)	0.99	40955.1	12400.00
20	31333.14	101.82	0.866	0.30	( 0.30)	0.99	42270.5	11111.00
21	30893.63	107.92	0.844	0.30	( 0.30)	0.99	44356.6	12201.00
22	30166.11	115.21	0.817	0.30	( 0.30)	0.99	46249.7	12231.00
23	29867.81	118.19	0.807	0.30	( 0.30)	0.99	46941.7	12101.10
24	29386.71	122.47	0.795	0.30	( 0.30)	0.99	47802.4	10400.00
25	29018.43	125.13	0.789	0.30	( 0.30)	0.99	48256.5	10200.00
26	28105.00	131.55	0.775	0.30	( 0.30)	0.99	49248.8	12010.00
27	27220.12	136.68	0.764	0.30	( 0.30)	0.99	49511.4	10210.00
28	26667.51	140.56	0.755	0.30	( 0.30)	0.99	49658.2	12000.00
29	23638.87	165.87	0.701	0.30	( 0.30)	0.99	50271.2	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104605.00 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	206.23	20.73	1.997	0.30 ( 0.30)	0.99	135.0	40600.00

LONGEST FLOWPATH FROM NODE 40600.00 TO NODE 12606.00 = 6107.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19233.78	15.56	2.419	0.30 ( 0.30)	0.99	4152.9	40510.00
2	19497.34	17.07	2.289	0.30 ( 0.30)	0.99	4595.1	40500.00
3	20423.21	20.41	2.014	0.30 ( 0.30)	0.99	5567.8	40430.00
4	20471.11	20.73	1.997	0.30 ( 0.30)	0.99	5663.4	40600.00
5	20498.22	20.93	1.986	0.30 ( 0.30)	0.99	5720.2	40440.00
6	20557.01	22.14	1.923	0.30 ( 0.30)	0.99	6059.9	40400.00
7	20553.01	22.32	1.914	0.30 ( 0.30)	0.99	6109.4	40420.00
8	20569.45	22.36	1.911	0.30 ( 0.30)	0.99	6122.8	40410.00
9	20630.37	22.53	1.902	0.30 ( 0.30)	0.99	6170.3	600.00
10	20715.52	22.96	1.880	0.30 ( 0.30)	0.99	6310.7	40300.00
11	20980.67	24.37	1.806	0.30 ( 0.30)	0.99	6765.0	40200.00
12	23354.31	38.84	1.377	0.30 ( 0.30)	0.99	11938.8	40100.00
13	25426.56	48.54	1.223	0.30 ( 0.30)	0.99	15241.0	11801.00
14	27894.52	59.77	1.080	0.30 ( 0.30)	0.99	19770.7	11530.00
15	29283.42	68.67	1.028	0.30 ( 0.30)	0.99	24402.8	11910.00
16	31450.93	79.07	0.970	0.30 ( 0.30)	0.99	30728.6	11350.00
17	32096.40	83.90	0.943	0.30 ( 0.30)	0.99	33902.9	11130.00
18	32002.36	89.93	0.909	0.30 ( 0.30)	0.99	36829.4	12300.00
19	31933.72	93.80	0.895	0.30 ( 0.30)	0.99	38890.3	11620.00
20	31650.30	98.60	0.878	0.30 ( 0.30)	0.99	41090.0	12400.00
21	31402.08	101.82	0.866	0.30 ( 0.30)	0.99	42405.5	11111.00
22	30959.88	107.92	0.844	0.30 ( 0.30)	0.99	44491.6	12201.00
23	30229.15	115.21	0.817	0.30 ( 0.30)	0.99	46384.6	12231.00
24	29929.53	118.19	0.807	0.30 ( 0.30)	0.99	47076.7	12101.10
25	29446.98	122.47	0.795	0.30 ( 0.30)	0.99	47937.4	10400.00
26	29078.00	125.13	0.789	0.30 ( 0.30)	0.99	48391.5	10200.00
27	28162.88	131.55	0.775	0.30 ( 0.30)	0.99	49383.8	12010.00
28	27276.66	136.68	0.764	0.30 ( 0.30)	0.99	49646.4	10210.00
29	26723.02	140.56	0.755	0.30 ( 0.30)	0.99	49793.2	12000.00

30	23687.72	165.87	0.701	0.30	( 0.30)	0.99	50406.1	10100.00
----	----------	--------	-------	------	---------	------	---------	----------

TOTAL AREA (ACRES) = 50406.1

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 32096.40 Tc (MIN.) = 83.899  
EFFECTIVE AREA (ACRES) = 33902.86 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 50406.1  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104605.00 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 50406.1 TC (MIN.) = 83.90  
EFFECTIVE AREA (ACRES) = 33902.86 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.994  
PEAK FLOW RATE (CFS) = 32096.40

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19233.78	15.56	2.419	0.30 ( 0.30)	0.99	4152.9	40510.00
2	19497.34	17.07	2.289	0.30 ( 0.30)	0.99	4595.1	40500.00
3	20423.21	20.41	2.014	0.30 ( 0.30)	0.99	5567.8	40430.00
4	20471.11	20.73	1.997	0.30 ( 0.30)	0.99	5663.4	40600.00
5	20498.22	20.93	1.986	0.30 ( 0.30)	0.99	5720.2	40440.00
6	20557.01	22.14	1.923	0.30 ( 0.30)	0.99	6059.9	40400.00
7	20553.01	22.32	1.914	0.30 ( 0.30)	0.99	6109.4	40420.00
8	20569.45	22.36	1.911	0.30 ( 0.30)	0.99	6122.8	40410.00
9	20630.37	22.53	1.902	0.30 ( 0.30)	0.99	6170.3	600.00
10	20715.52	22.96	1.880	0.30 ( 0.30)	0.99	6310.7	40300.00
11	20980.67	24.37	1.806	0.30 ( 0.30)	0.99	6765.0	40200.00
12	23354.31	38.84	1.377	0.30 ( 0.30)	0.99	11938.8	40100.00
13	25426.56	48.54	1.223	0.30 ( 0.30)	0.99	15241.0	11801.00
14	27894.52	59.77	1.080	0.30 ( 0.30)	0.99	19770.7	11530.00
15	29283.42	68.67	1.028	0.30 ( 0.30)	0.99	24402.8	11910.00
16	31450.93	79.07	0.970	0.30 ( 0.30)	0.99	30728.6	11350.00
17	32096.40	83.90	0.943	0.30 ( 0.30)	0.99	33902.9	11130.00
18	32002.36	89.93	0.909	0.30 ( 0.30)	0.99	36829.4	12300.00
19	31933.72	93.80	0.895	0.30 ( 0.30)	0.99	38890.3	11620.00
20	31650.30	98.60	0.878	0.30 ( 0.30)	0.99	41090.0	12400.00
21	31402.08	101.82	0.866	0.30 ( 0.30)	0.99	42405.5	11111.00
22	30959.88	107.92	0.844	0.30 ( 0.30)	0.99	44491.6	12201.00
23	30229.15	115.21	0.817	0.30 ( 0.30)	0.99	46384.6	12231.00
24	29929.53	118.19	0.807	0.30 ( 0.30)	0.99	47076.7	12101.10
25	29446.98	122.47	0.795	0.30 ( 0.30)	0.99	47937.4	10400.00
26	29078.00	125.13	0.789	0.30 ( 0.30)	0.99	48391.5	10200.00
27	28162.88	131.55	0.775	0.30 ( 0.30)	0.99	49383.8	12010.00
28	27276.66	136.68	0.764	0.30 ( 0.30)	0.99	49646.4	10210.00
29	26723.02	140.56	0.755	0.30 ( 0.30)	0.99	49793.2	12000.00
30	23687.72	165.87	0.701	0.30 ( 0.30)	0.99	50406.1	10100.00

END OF RATIONAL METHOD ANALYSIS



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S27- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 25-YR RM EV APRIL 2019 CCHIU \*  
\*\*\*\*\*

FILE NAME: RI25EV27.DAT  
TIME/DATE OF STUDY: 09:49 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 25.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 4.933
- 2) 10.00; 3.214
- 3) 15.00; 2.451
- 4) 20.00; 2.024
- 5) 25.00; 1.763
- 6) 30.00; 1.547
- 7) 40.00; 1.347
- 8) 50.00; 1.194
- 9) 60.00; 1.070
- 10) 90.00; 0.902
- 11) 120.00; 0.792
- 12) 180.00; 0.662
- 13) 360.00; 0.490
- 14) 1200.00; 0.216

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI25EV26.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19497.34	17.07	0.30 ( 0.30)	0.99	4595.1	40500.00
2	20498.22	20.93	0.30 ( 0.30)	0.99	5720.2	40440.00
3	20980.67	24.37	0.30 ( 0.30)	0.99	6765.0	40200.00
4	23354.31	38.84	0.30 ( 0.30)	0.99	11938.8	40100.00
5	25426.56	48.54	0.30 ( 0.30)	0.99	15241.0	11801.00
6	27894.52	59.77	0.30 ( 0.30)	0.99	19770.7	11530.00
7	29283.42	68.67	0.30 ( 0.30)	0.99	24402.8	11910.00
8	31450.93	79.07	0.30 ( 0.30)	0.99	30728.6	11350.00
9	32096.40	83.90	0.30 ( 0.30)	0.99	33902.9	11130.00
10	32002.36	89.93	0.30 ( 0.30)	0.99	36829.4	12300.00
11	31933.72	93.80	0.30 ( 0.30)	0.99	38890.3	11620.00
12	31650.30	98.60	0.30 ( 0.30)	0.99	41090.0	12400.00
13	31402.08	101.82	0.30 ( 0.30)	0.99	42405.5	11111.00
14	30959.88	107.92	0.30 ( 0.30)	0.99	44491.6	12201.00
15	30229.15	115.21	0.30 ( 0.30)	0.99	46384.6	12231.00
16	29446.98	122.47	0.30 ( 0.30)	0.99	47937.4	10400.00
17	28162.88	131.55	0.30 ( 0.30)	0.99	49383.8	12010.00
18	27276.66	136.68	0.30 ( 0.30)	0.99	49646.4	10210.00
19	26723.02	140.56	0.30 ( 0.30)	0.99	49793.2	12000.00
20	23687.72	165.87	0.30 ( 0.30)	0.99	50406.1	10100.00
TOTAL AREA (ACRES) =						50406.1

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19497.34	17.07	0.30 ( 0.30)	0.99	4595.1	40500.00
2	20498.22	20.93	0.30 ( 0.30)	0.99	5720.2	40440.00
3	20980.67	24.37	0.30 ( 0.30)	0.99	6765.0	40200.00
4	23354.31	38.84	0.30 ( 0.30)	0.99	11938.8	40100.00
5	25426.56	48.54	0.30 ( 0.30)	0.99	15241.0	11801.00
6	27894.52	59.77	0.30 ( 0.30)	0.99	19770.7	11530.00
7	29283.42	68.67	0.30 ( 0.30)	0.99	24402.8	11910.00
8	31450.93	79.07	0.30 ( 0.30)	0.99	30728.6	11350.00
9	32096.40	83.90	0.30 ( 0.30)	0.99	33902.9	11130.00
10	32002.36	89.93	0.30 ( 0.30)	0.99	36829.4	12300.00
11	31933.72	93.80	0.30 ( 0.30)	0.99	38890.3	11620.00
12	31650.30	98.60	0.30 ( 0.30)	0.99	41090.0	12400.00
13	31402.08	101.82	0.30 ( 0.30)	0.99	42405.5	11111.00

14	30959.88	107.92	0.30	( 0.30)	0.99	44491.6	12201.00	
15	30229.15	115.21	0.30	( 0.30)	0.99	46384.6	12231.00	
16	29446.98	122.47	0.30	( 0.30)	0.99	47937.4	10400.00	
17	28162.88	131.55	0.30	( 0.30)	0.99	49383.8	12010.00	
18	27276.66	136.68	0.30	( 0.30)	0.99	49646.4	10210.00	
19	26723.02	140.56	0.30	( 0.30)	0.99	49793.2	12000.00	
20	23687.72	165.87	0.30	( 0.30)	0.99	50406.1	10100.00	
TOTAL AREA (ACRES) =		50406.1						

\*\*\*\*\*

FLOW PROCESS FROM NODE 12606.00 TO NODE 12701.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 286.00 DOWNSTREAM(FEET) = 276.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1260.19 CHANNEL SLOPE = 0.0079  
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 8.24  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.929  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/	SCS SOIL	AREA	Fp	Ap	SCS
LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
COMMERCIAL	B	7.55	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 32099.45  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 16.14  
AVERAGE FLOW DEPTH(FEET) = 8.24 TRAVEL TIME(MIN.) = 1.30  
Tc(MIN.) = 85.20  
SUBAREA AREA(ACRES) = 7.55 SUBAREA RUNOFF(CFS) = 6.11  
EFFECTIVE AREA(ACRES) = 33910.41 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA(ACRES) = 50413.7 PEAK FLOW RATE(CFS) = 32096.40  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 8.24

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 8.24 FLOW VELOCITY(FEET/SEC.) = 16.14  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12701.00 = 105865.19 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12701.00 TO NODE 12701.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 85.20  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.929  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/	SCS SOIL	AREA	Fp	Ap	SCS
LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
PUBLIC PARK	B	0.90	0.30	0.850	56
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	3.40	0.30	1.000	65
RESIDENTIAL					

"5-7 DWELLINGS/ACRE"	B	0.40	0.30	0.500	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	23.00	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	3.30	0.30	1.000	66
NATURAL FAIR COVER					
"GRASS"	B	0.40	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.989  
SUBAREA AREA(ACRES) = 31.40 SUBAREA RUNOFF(CFS) = 17.86  
EFFECTIVE AREA(ACRES) = 33941.81 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA(ACRES) = 50445.1 PEAK FLOW RATE(CFS) = 32096.40  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12701.00 TO NODE 12701.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 85.20  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.929  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/	SCS SOIL	AREA	Fp	Ap	SCS
LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	1.70	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA(ACRES) = 1.70 SUBAREA RUNOFF(CFS) = 0.96  
EFFECTIVE AREA(ACRES) = 33943.51 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA(ACRES) = 50446.8 PEAK FLOW RATE(CFS) = 32096.40  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12701.00 TO NODE 12720.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 276.00 DOWNSTREAM(FEET) = 275.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 147.65 CHANNEL SLOPE = 0.0068  
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 8.62  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.928  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/	SCS SOIL	AREA	Fp	Ap	SCS
LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
PUBLIC PARK	B	1.49	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.850  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 32096.85  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 15.31  
AVERAGE FLOW DEPTH(FEET) = 8.62 TRAVEL TIME(MIN.) = 0.16  
Tc(MIN.) = 85.36  
SUBAREA AREA(ACRES) = 1.49 SUBAREA RUNOFF(CFS) = 0.90

EFFECTIVE AREA(ACRES) = 33945.00 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 50448.3 PEAK FLOW RATE(CFS) = 32096.40  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 8.62

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 8.62 FLOW VELOCITY(FEET/SEC.) = 15.31  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.00 = 106012.84 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12701.00 TO NODE 12720.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
 TIME OF CONCENTRATION(MIN.) = 85.36  
 RAINFALL INTENSITY(INCH/HR) = 0.93  
 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.99  
 EFFECTIVE STREAM AREA(ACRES) = 33945.00  
 TOTAL STREAM AREA(ACRES) = 50448.27  
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 32096.40

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12710.00 TO NODE 12711.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<  
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 943.56  
 ELEVATION DATA: UPSTREAM(FEET) = 940.78 DOWNSTREAM(FEET) = 657.79

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
 SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 13.910  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.617  
 SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER						
"GRASS"	B	6.56	0.30	1.000	69	13.91

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA RUNOFF(CFS) = 13.68  
 TOTAL AREA(ACRES) = 6.56 PEAK FLOW RATE(CFS) = 13.68

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12711.00 TO NODE 12712.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 657.79 DOWNSTREAM(FEET) = 585.63  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 766.00 CHANNEL SLOPE = 0.0942

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.68  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.335

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	26.94	0.30	1.000	66

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 38.43  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.22  
 AVERAGE FLOW DEPTH(FEET) = 0.65 TRAVEL TIME(MIN.) = 2.45  
 Tc(MIN.) = 16.36

SUBAREA AREA(ACRES) = 26.94 SUBAREA RUNOFF(CFS) = 49.35  
 EFFECTIVE AREA(ACRES) = 33.50 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 33.5 PEAK FLOW RATE(CFS) = 61.36  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.86

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 0.86 FLOW VELOCITY(FEET/SEC.) = 6.11  
 LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12712.00 = 1709.56 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12712.00 TO NODE 12713.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 585.63 DOWNSTREAM(FEET) = 463.75  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1025.79 CHANNEL SLOPE = 0.1188  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.90  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.130

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	14.73	0.30	0.100	56

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.100  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 75.27  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.11  
 AVERAGE FLOW DEPTH(FEET) = 0.90 TRAVEL TIME(MIN.) = 2.40  
 Tc(MIN.) = 18.76

SUBAREA AREA(ACRES) = 14.73 SUBAREA RUNOFF(CFS) = 27.84  
 EFFECTIVE AREA(ACRES) = 48.23 AREA-AVERAGED Fm(INCH/HR) = 0.22  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.73  
 TOTAL AREA(ACRES) = 48.2 PEAK FLOW RATE(CFS) = 83.01  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.95

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.95 FLOW VELOCITY(FEET/SEC.) = 7.34  
LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12713.00 = 2735.35 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12713.00 TO NODE 12714.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 463.75 DOWNSTREAM(FEET) = 360.30  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1148.54 CHANNEL SLOPE = 0.0901  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.57  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.971

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	105.64	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 175.25

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.46

AVERAGE FLOW DEPTH(FEET) = 1.57 TRAVEL TIME(MIN.) = 2.26

Tc(MIN.) = 21.02

SUBAREA AREA(ACRES) = 105.64 SUBAREA RUNOFF(CFS) = 184.52

EFFECTIVE AREA(ACRES) = 153.87 AREA-AVERAGED Fm(INCH/HR) = 0.09

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.30

TOTAL AREA(ACRES) = 153.9 PEAK FLOW RATE(CFS) = 260.62

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.96

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.96 FLOW VELOCITY(FEET/SEC.) = 9.53

LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12714.00 = 3883.89 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12714.00 TO NODE 12720.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 360.30 DOWNSTREAM(FEET) = 275.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1314.99 CHANNEL SLOPE = 0.0649  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.58  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.849

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	127.13	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 364.68

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.38

AVERAGE FLOW DEPTH(FEET) = 2.57 TRAVEL TIME(MIN.) = 2.34

Tc(MIN.) = 23.36

SUBAREA AREA(ACRES) = 127.13 SUBAREA RUNOFF(CFS) = 208.10

EFFECTIVE AREA(ACRES) = 281.00 AREA-AVERAGED Fm(INCH/HR) = 0.06

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.21

TOTAL AREA(ACRES) = 281.0 PEAK FLOW RATE(CFS) = 451.82

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.88

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.88 FLOW VELOCITY(FEET/SEC.) = 9.96

LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12720.00 = 5198.88 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<

TOTAL NUMBER OF STREAMS = 2

CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:

TIME OF CONCENTRATION(MIN.) = 23.36

RAINFALL INTENSITY(INCH/HR) = 1.85

AREA-AVERAGED Fm(INCH/HR) = 0.06

AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.21

EFFECTIVE STREAM AREA(ACRES) = 281.00

TOTAL STREAM AREA(ACRES) = 281.00

PEAK FLOW RATE(CFS) AT CONFLUENCE = 451.82

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19497.34	18.80	2.127	0.30( 0.30)	0.99	4637.3	40500.00
1	20498.22	22.63	1.886	0.30( 0.30)	0.99	5762.3	40440.00
1	20980.67	26.06	1.717	0.30( 0.30)	0.99	6807.1	40200.00
1	23354.31	40.46	1.340	0.30( 0.30)	0.99	11980.9	40100.00
1	25426.56	50.12	1.193	0.30( 0.30)	0.99	15283.2	11801.00
1	27894.52	61.31	1.063	0.30( 0.30)	0.99	19812.9	11530.00
1	29283.42	70.18	1.013	0.30( 0.30)	0.99	24445.0	11910.00
1	31450.93	80.55	0.955	0.30( 0.30)	0.99	30770.8	11350.00
1	32096.40	85.36	0.928	0.30( 0.30)	0.99	33945.0	11130.00
1	32002.36	91.40	0.897	0.30( 0.30)	0.99	36871.6	12300.00
1	31933.72	95.27	0.883	0.30( 0.30)	0.99	38932.4	11620.00
1	31650.30	100.06	0.865	0.30( 0.30)	0.99	41132.2	12400.00
1	31402.08	103.30	0.853	0.30( 0.30)	0.99	42447.6	11111.00
1	30959.88	109.40	0.831	0.30( 0.30)	0.99	44533.8	12201.00
1	30229.15	116.70	0.804	0.30( 0.30)	0.99	46426.8	12231.00
1	29446.98	123.98	0.783	0.30( 0.30)	0.99	47979.5	10400.00
1	28162.88	133.08	0.764	0.30( 0.30)	0.99	49425.9	12010.00
1	27276.66	138.22	0.753	0.30( 0.30)	0.99	49688.5	10210.00
1	26723.02	142.11	0.744	0.30( 0.30)	0.99	49835.3	12000.00
1	23687.72	167.48	0.689	0.30( 0.30)	0.99	50448.3	10100.00
2	451.82	23.36	1.849	0.30( 0.06)	0.21	281.0	12710.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19917.54	18.80	2.127	0.30 ( 0.29)	0.95	4863.4	40500.00
2	20945.31	22.63	1.886	0.30 ( 0.29)	0.96	6034.7	40440.00
3	21051.90	23.36	1.849	0.30 ( 0.29)	0.96	6263.9	12710.00
4	21399.27	26.06	1.717	0.30 ( 0.29)	0.96	7088.1	40200.00
5	23677.46	40.46	1.340	0.30 ( 0.29)	0.97	12261.9	40100.00
6	25712.43	50.12	1.193	0.30 ( 0.29)	0.98	15564.2	11801.00
7	28147.54	61.31	1.063	0.30 ( 0.29)	0.98	20093.9	11530.00
8	29523.88	70.18	1.013	0.30 ( 0.30)	0.98	24726.0	11910.00
9	31676.71	80.55	0.955	0.30 ( 0.30)	0.99	31051.8	11350.00
10	32315.36	85.36	0.928	0.30 ( 0.30)	0.99	34226.0	11130.00
11	32213.45	91.40	0.897	0.30 ( 0.30)	0.99	37152.6	12300.00
12	32141.22	95.27	0.883	0.30 ( 0.30)	0.99	39213.4	11620.00
13	31853.36	100.06	0.865	0.30 ( 0.30)	0.99	41413.2	12400.00
14	31602.14	103.30	0.853	0.30 ( 0.30)	0.99	42728.6	11111.00
15	31154.28	109.40	0.831	0.30 ( 0.30)	0.99	44814.8	12201.00
16	30416.78	116.70	0.804	0.30 ( 0.30)	0.99	46707.8	12231.00
17	29629.37	123.98	0.783	0.30 ( 0.30)	0.99	48260.5	10400.00
18	28340.29	133.08	0.764	0.30 ( 0.30)	0.99	49706.9	12010.00
19	27451.24	138.22	0.753	0.30 ( 0.30)	0.99	49969.5	10210.00
20	26895.47	142.11	0.744	0.30 ( 0.30)	0.99	50116.3	12000.00
21	23846.28	167.48	0.689	0.30 ( 0.30)	0.99	50729.3	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 32315.36 Tc(MIN.) = 85.36  
 EFFECTIVE AREA(ACRES) = 34226.00 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 50729.3  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.00 = 106012.84 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 85.36

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.928

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	0.40	0.30	0.850	56
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.10	0.30	1.000	65
RESIDENTIAL					
"5-7 DWELLINGS/ACRE"	B	0.20	0.30	0.500	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	3.80	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.964

SUBAREA AREA(ACRES) = 4.50 SUBAREA RUNOFF(CFS) = 2.59

EFFECTIVE AREA(ACRES) = 34230.50 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 50733.8 PEAK FLOW RATE(CFS) = 32315.36

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 275.00 DOWNSTREAM(FEET) = 258.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 2669.21 CHANNEL SLOPE = 0.0064

GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT(FEET) = 8.81

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.911

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	62.15	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 32340.01

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 15.04

AVERAGE FLOW DEPTH(FEET) = 8.81 TRAVEL TIME(MIN.) = 2.96

Tc(MIN.) = 88.32

SUBAREA AREA(ACRES) = 62.15 SUBAREA RUNOFF(CFS) = 49.30

EFFECTIVE AREA(ACRES) = 34292.65 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 50795.9 PEAK FLOW RATE(CFS) = 32315.36

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT(FEET) = 8.81

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 8.81 FLOW VELOCITY(FEET/SEC.) = 15.04

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108682.05 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 88.32

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.911

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	0.10	0.30	0.100	56
NATURAL FAIR COVER					
"MEADOWS"	B	0.30	0.30	1.000	70
NATURAL FAIR COVER					
"OPEN BRUSH"	B	17.90	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.20	0.30	1.000	66
PUBLIC PARK	B	0.30	0.30	0.850	56
NATURAL POOR COVER					
"BARREN"	B	0.70	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.993

SUBAREA AREA(ACRES) = 19.50 SUBAREA RUNOFF(CFS) = 10.77

EFFECTIVE AREA(ACRES) = 34312.15 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA (ACRES) = 50815.4 PEAK FLOW RATE (CFS) = 32315.36  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 88.32

\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.911

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL					
"5-7 DWELLINGS/ACRE"	B	0.10	0.30	0.500	56
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	1.10	0.30	1.000	65
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.90	0.30	1.000	65
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.60	0.30	0.900	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.30	0.30	0.900	56
NATURAL POOR COVER					
"BARREN"	B	0.50	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.960

SUBAREA AREA (ACRES) = 3.50 SUBAREA RUNOFF (CFS) = 1.96

EFFECTIVE AREA (ACRES) = 34315.65 AREA-AVERAGED Fm (INCH/HR) = 0.30

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA (ACRES) = 50818.9 PEAK FLOW RATE (CFS) = 32315.36

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 3D25EVRL.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	754.74	19.56	0.30 ( 0.14)	0.48	352.8	413.00
2	750.96	26.18	0.30 ( 0.14)	0.48	431.8	430.00
3	718.67	27.92	0.30 ( 0.14)	0.48	439.5	400.00
TOTAL AREA (ACRES) =		439.5				

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19917.54	22.28	1.905	0.30 ( 0.28)	0.94	4953.1	40500.00

2	20945.31	26.05	1.717	0.30 ( 0.28)	0.95	6124.3	40440.00
3	21051.90	26.77	1.687	0.30 ( 0.28)	0.95	6353.6	12710.00
4	21399.27	29.45	1.571	0.30 ( 0.29)	0.95	7177.8	40200.00
5	23677.46	43.74	1.290	0.30 ( 0.29)	0.97	12351.6	40100.00
6	25712.43	53.31	1.153	0.30 ( 0.29)	0.97	15653.8	11801.00
7	28147.54	64.40	1.045	0.30 ( 0.29)	0.98	20183.5	11530.00
8	29523.88	73.23	0.996	0.30 ( 0.29)	0.98	24815.6	11910.00
9	31676.71	83.52	0.938	0.30 ( 0.30)	0.98	31141.4	11350.00
10	32315.36	88.32	0.911	0.30 ( 0.30)	0.99	34315.6	11130.00
11	32213.45	94.36	0.886	0.30 ( 0.30)	0.99	37242.2	12300.00
12	32141.22	98.23	0.872	0.30 ( 0.30)	0.99	39303.1	11620.00
13	31853.36	103.04	0.854	0.30 ( 0.30)	0.99	41502.8	12400.00
14	31602.14	106.28	0.842	0.30 ( 0.30)	0.99	42818.2	11111.00
15	31154.28	112.39	0.820	0.30 ( 0.30)	0.99	44904.4	12201.00
16	30416.78	119.71	0.793	0.30 ( 0.30)	0.99	46797.4	12231.00
17	29629.37	127.02	0.777	0.30 ( 0.30)	0.99	48350.2	10400.00
18	28340.29	136.17	0.757	0.30 ( 0.30)	0.99	49796.6	12010.00
19	27451.24	141.34	0.746	0.30 ( 0.30)	0.99	50059.2	10210.00
20	26895.47	145.26	0.737	0.30 ( 0.30)	0.99	50206.0	12000.00
21	23846.28	170.76	0.682	0.30 ( 0.30)	0.99	50818.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108682.05 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	754.74	19.56	2.062	0.30 ( 0.14)	0.48	352.8	413.00
2	750.96	26.18	1.712	0.30 ( 0.14)	0.48	431.8	430.00
3	718.67	27.92	1.637	0.30 ( 0.14)	0.48	439.5	400.00

LONGEST FLOWPATH FROM NODE 430.00 TO NODE 12720.50 = 11352.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19929.46	19.56	2.062	0.30 ( 0.27)	0.91	4701.3	413.00
2	20670.73	22.28	1.905	0.30 ( 0.27)	0.91	5338.3	40500.00
3	21696.35	26.05	1.717	0.30 ( 0.27)	0.92	6554.6	40440.00
4	21714.91	26.18	1.712	0.30 ( 0.27)	0.92	6596.2	430.00
5	21791.95	26.77	1.687	0.30 ( 0.28)	0.92	6788.0	12710.00
6	21920.15	27.92	1.637	0.30 ( 0.28)	0.92	7148.0	400.00
7	22086.19	29.45	1.571	0.30 ( 0.28)	0.92	7617.3	40200.00
8	24229.14	43.74	1.290	0.30 ( 0.29)	0.95	12791.1	40100.00
9	26198.29	53.31	1.153	0.30 ( 0.29)	0.96	16093.3	11801.00
10	28581.61	64.40	1.045	0.30 ( 0.29)	0.97	20623.0	11530.00
11	29934.15	73.23	0.996	0.30 ( 0.29)	0.97	25255.1	11910.00
12	32059.23	83.52	0.938	0.30 ( 0.29)	0.98	31580.9	11350.00
13	32684.96	88.32	0.911	0.30 ( 0.29)	0.98	34755.1	11130.00
14	32570.82	94.36	0.886	0.30 ( 0.29)	0.98	37681.7	12300.00
15	32491.77	98.23	0.872	0.30 ( 0.29)	0.98	39742.6	11620.00
16	32195.42	103.04	0.854	0.30 ( 0.29)	0.98	41942.3	12400.00
17	31938.48	106.28	0.842	0.30 ( 0.29)	0.98	43257.8	11111.00
18	31479.83	112.39	0.820	0.30 ( 0.29)	0.98	45343.9	12201.00
19	30729.41	119.71	0.793	0.30 ( 0.29)	0.98	47236.9	12231.00
20	29934.17	127.02	0.777	0.30 ( 0.29)	0.98	48789.7	10400.00
21	28635.55	136.17	0.757	0.30 ( 0.29)	0.98	50236.1	12010.00
22	27741.11	141.34	0.746	0.30 ( 0.29)	0.98	50498.7	10210.00
23	27181.26	145.26	0.737	0.30 ( 0.29)	0.98	50645.5	12000.00
24	24105.46	170.76	0.682	0.30 ( 0.29)	0.98	51258.4	10100.00

TOTAL AREA (ACRES) = 51258.4



COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 32684.96 Tc(MIN.) = 88.318
EFFECTIVE AREA(ACRES) = 34755.15 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 51258.4
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108682.05 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 12
-----

>>>>CLEAR MEMORY BANK # 2 <<<<<

\*\*\*\*\*
FLOW PROCESS FROM NODE 12720.50 TO NODE 12721.00 IS CODE = 56
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 258.00 DOWNSTREAM(FEET) = 256.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 438.77 CHANNEL SLOPE = 0.0046
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
\*ESTIMATED CHANNEL HEIGHT(FEET) = 9.75
CHANNEL FLOW THRU SUBAREA(CFS) = 32684.96
FLOW VELOCITY(FEET/SEC.) = 13.48 FLOW DEPTH(FEET) = 9.75
TRAVEL TIME(MIN.) = 0.54 Tc(MIN.) = 88.86
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12721.00 = 109120.82 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 12721.00 TO NODE 12722.00 IS CODE = 56
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 256.00 DOWNSTREAM(FEET) = 255.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 830.42 CHANNEL SLOPE = 0.0012
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
\*ESTIMATED CHANNEL HEIGHT(FEET) = 14.12
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.900
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
COMMERCIAL B 11.24 0.30 0.100 56
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 32689.36
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.56
AVERAGE FLOW DEPTH(FEET) = 14.12 TRAVEL TIME(MIN.) = 1.62
Tc(MIN.) = 90.48
SUBAREA AREA(ACRES) = 11.24 SUBAREA RUNOFF(CFS) = 8.80
EFFECTIVE AREA(ACRES) = 34766.39 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
TOTAL AREA(ACRES) = 51269.7 PEAK FLOW RATE(CFS) = 32684.96
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT(FEET) = 14.12

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 14.12 FLOW VELOCITY(FEET/SEC.) = 8.56

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12722.00 = 109951.24 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 12722.00 TO NODE 12722.00 IS CODE = 81
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 90.48

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.900

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL POOR COVER
"BARREN" B 2.10 0.30 1.000 86
NATURAL FAIR COVER
"GRASS" B 0.10 0.30 1.000 69
NATURAL FAIR COVER
"MEADOWS" B 3.60 0.30 1.000 70
NATURAL FAIR COVER
"OPEN BRUSH" B 4.10 0.30 1.000 66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 9.90 SUBAREA RUNOFF(CFS) = 5.35
EFFECTIVE AREA(ACRES) = 34776.29 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
TOTAL AREA(ACRES) = 51279.6 PEAK FLOW RATE(CFS) = 32684.96
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*
FLOW PROCESS FROM NODE 12722.00 TO NODE 12722.00 IS CODE = 81
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 90.48

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.900

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
RESIDENTIAL
".4 DWELLING/ACRE" B 0.60 0.30 0.900 56
NATURAL FAIR COVER
"WOODLAND,GRASS" B 1.90 0.30 1.000 65
NATURAL FAIR COVER
"WOODLAND,GRASS" B 0.10 0.30 1.000 65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.977
SUBAREA AREA(ACRES) = 2.60 SUBAREA RUNOFF(CFS) = 1.42
EFFECTIVE AREA(ACRES) = 34778.89 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
TOTAL AREA(ACRES) = 51282.2 PEAK FLOW RATE(CFS) = 32684.96
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12722.00 TO NODE 12740.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 255.00 DOWNSTREAM(FEET) = 252.10
CHANNEL LENGTH THRU SUBAREA(FEET) = 624.00 CHANNEL SLOPE = 0.0046
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
\*ESTIMATED CHANNEL HEIGHT(FEET) = 9.69
\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.897

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include COMMERCIAL, NATURAL FAIR COVER "GRASS", and "WOODLAND, GRASS".

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.925
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 32689.95
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 13.57
AVERAGE FLOW DEPTH(FEET) = 9.69 TRAVEL TIME (MIN.) = 0.77
Tc (MIN.) = 91.24
SUBAREA AREA (ACRES) = 17.90 SUBAREA RUNOFF (CFS) = 9.99
EFFECTIVE AREA (ACRES) = 34796.79 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
TOTAL AREA (ACRES) = 51300.1 PEAK FLOW RATE (CFS) = 32684.96
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
\*ESTIMATED CHANNEL HEIGHT(FEET) = 9.69

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 9.69 FLOW VELOCITY(FEET/SEC.) = 13.57
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12740.00 = 110575.24 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 91.24
\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.897

SUBAREA LOSS RATE DATA(AMC II):

Table with 6 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN. Rows include NATURAL FAIR COVER "OPEN BRUSH".

NATURAL FAIR COVER
"OPEN BRUSH" B 12.00 0.30 1.000 66
NATURAL FAIR COVER
"CHAPARRAL, BROADLEAF" B 0.80 0.30 1.000 63
NATURAL FAIR COVER
"CHAPARRAL, BROADLEAF" B 20.20 0.30 1.000 63
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 44.40 SUBAREA RUNOFF (CFS) = 23.87
EFFECTIVE AREA (ACRES) = 34841.18 AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
TOTAL AREA (ACRES) = 51344.4 PEAK FLOW RATE (CFS) = 32684.96
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*
FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION (MIN.) = 91.24
RAINFALL INTENSITY (INCH/HR) = 0.90
AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.98
EFFECTIVE STREAM AREA (ACRES) = 34841.18
TOTAL STREAM AREA (ACRES) = 51344.45
PEAK FLOW RATE (CFS) AT CONFLUENCE = 32684.96

\*\*\*\*\*
FLOW PROCESS FROM NODE 12730.00 TO NODE 12731.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH (FEET) = 561.54
ELEVATION DATA: UPSTREAM (FEET) = 613.29 DOWNSTREAM (FEET) = 551.75

Tc = K \* [(LENGTH \*\* 3.00) / (ELEVATION CHANGE)] \*\* 0.20
SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 13.823
\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 2.631

SUBAREA Tc AND LOSS RATE DATA(AMC II):

Table with 7 columns: DEVELOPMENT TYPE/ LAND USE, SCS SOIL GROUP, AREA (ACRES), Fp (INCH/HR), Ap (DECIMAL), SCS CN, Tc (MIN.). Rows include NATURAL FAIR COVER "CHAPARRAL, BROADLEAF".

\*\*\*\*\*
FLOW PROCESS FROM NODE 12731.00 TO NODE 12732.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 551.75 DOWNSTREAM(FEET) = 494.40  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 971.91 CHANNEL SLOPE = 0.0590  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.86  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 2.266  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 COMMERCIAL B 34.62 0.30 0.100 56  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 48.15  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.84  
 AVERAGE FLOW DEPTH(FEET) = 0.85 TRAVEL TIME(MIN.) = 3.34  
 Tc(MIN.) = 17.17  
 SUBAREA AREA(ACRES) = 34.62 SUBAREA RUNOFF(CFS) = 69.67  
 EFFECTIVE AREA(ACRES) = 40.95 AREA-AVERAGED Fm(INCH/HR) = 0.07  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.24  
 TOTAL AREA(ACRES) = 40.9 PEAK FLOW RATE(CFS) = 80.87  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.15  
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.15 FLOW VELOCITY(FEET/SEC.) = 5.73  
 LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12732.00 = 1533.45 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12732.00 TO NODE 12733.00 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 494.40 DOWNSTREAM(FEET) = 431.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1156.41 CHANNEL SLOPE = 0.0548  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.59  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 2.018  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 COMMERCIAL B 59.52 0.30 0.100 56  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 134.18  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.56  
 AVERAGE FLOW DEPTH(FEET) = 1.56 TRAVEL TIME(MIN.) = 2.94  
 Tc(MIN.) = 20.11  
 SUBAREA AREA(ACRES) = 59.52 SUBAREA RUNOFF(CFS) = 106.52  
 EFFECTIVE AREA(ACRES) = 100.47 AREA-AVERAGED Fm(INCH/HR) = 0.05  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.16  
 TOTAL AREA(ACRES) = 100.5 PEAK FLOW RATE(CFS) = 178.27  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.83

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.83 FLOW VELOCITY(FEET/SEC.) = 7.15  
 LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12733.00 = 2689.86 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12733.00 TO NODE 12734.00 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 431.00 DOWNSTREAM(FEET) = 367.10  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1654.48 CHANNEL SLOPE = 0.0386  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 2.33  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.807  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 COMMERCIAL B 64.05 0.30 0.100 56  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 229.55  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.81  
 AVERAGE FLOW DEPTH(FEET) = 2.31 TRAVEL TIME(MIN.) = 4.05  
 Tc(MIN.) = 24.16  
 SUBAREA AREA(ACRES) = 64.05 SUBAREA RUNOFF(CFS) = 102.44  
 EFFECTIVE AREA(ACRES) = 164.52 AREA-AVERAGED Fm(INCH/HR) = 0.04  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.13  
 TOTAL AREA(ACRES) = 164.5 PEAK FLOW RATE(CFS) = 261.59  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 2.47

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 2.47 FLOW VELOCITY(FEET/SEC.) = 7.07  
 LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12734.00 = 4344.34 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12734.00 TO NODE 12740.00 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 367.11 DOWNSTREAM(FEET) = 252.10  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1880.98 CHANNEL SLOPE = 0.0611  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 2.28  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.640  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 COMMERCIAL B 26.02 0.30 0.100 56  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 280.45  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.50

AVERAGE FLOW DEPTH (FEET) = 2.27 TRAVEL TIME (MIN.) = 3.69  
 Tc (MIN.) = 27.84  
 SUBAREA AREA (ACRES) = 26.02 SUBAREA RUNOFF (CFS) = 37.71  
 EFFECTIVE AREA (ACRES) = 190.54 AREA-AVERAGED Fm (INCH/HR) = 0.04  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.13  
 TOTAL AREA (ACRES) = 190.5 PEAK FLOW RATE (CFS) = 274.59  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 2.24

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 2.24 FLOW VELOCITY (FEET/SEC.) = 8.46  
 LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12740.00 = 6225.32 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====  
 TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
 TIME OF CONCENTRATION (MIN.) = 27.84  
 RAINFALL INTENSITY (INCH/HR) = 1.64  
 AREA-AVERAGED Fm (INCH/HR) = 0.04  
 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.13  
 EFFECTIVE STREAM AREA (ACRES) = 190.54  
 TOTAL STREAM AREA (ACRES) = 190.54  
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 274.59

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19929.46	22.99	1.868	0.30 ( 0.27)	0.91	4787.3	413.00
1	20670.73	25.67	1.734	0.30 ( 0.27)	0.91	5424.4	40500.00
1	21696.35	29.39	1.573	0.30 ( 0.27)	0.92	6640.7	40440.00
1	21714.91	29.52	1.568	0.30 ( 0.27)	0.92	6682.2	430.00
1	21791.95	30.10	1.545	0.30 ( 0.27)	0.92	6874.0	12710.00
1	21920.15	31.25	1.522	0.30 ( 0.28)	0.92	7234.0	400.00
1	22086.19	32.77	1.492	0.30 ( 0.28)	0.92	7703.3	40200.00
1	24229.14	46.96	1.240	0.30 ( 0.29)	0.95	12877.1	40100.00
1	26198.29	56.45	1.114	0.30 ( 0.29)	0.96	16179.4	11801.00
1	28581.61	67.46	1.028	0.30 ( 0.29)	0.97	20709.1	11530.00
1	29934.15	76.24	0.979	0.30 ( 0.29)	0.97	25341.2	11910.00
1	32059.23	86.47	0.922	0.30 ( 0.29)	0.98	31667.0	11350.00
1	32684.96	91.24	0.897	0.30 ( 0.29)	0.98	34841.2	11130.00
1	32570.82	97.29	0.875	0.30 ( 0.29)	0.98	37767.8	12300.00
1	32491.77	101.16	0.861	0.30 ( 0.29)	0.98	39828.6	11620.00
1	32195.42	105.98	0.843	0.30 ( 0.29)	0.98	42028.4	12400.00
1	31938.48	109.22	0.832	0.30 ( 0.29)	0.98	43343.8	11111.00
1	31479.83	115.35	0.809	0.30 ( 0.29)	0.98	45429.9	12201.00
1	30729.41	122.70	0.786	0.30 ( 0.29)	0.98	47323.0	12231.00
1	29934.17	130.03	0.770	0.30 ( 0.29)	0.98	48875.7	10400.00
1	28635.55	139.22	0.750	0.30 ( 0.29)	0.98	50322.1	12010.00
1	27741.11	144.43	0.739	0.30 ( 0.29)	0.98	50584.7	10210.00
1	27181.26	148.36	0.731	0.30 ( 0.29)	0.98	50731.5	12000.00
1	24105.46	173.98	0.675	0.30 ( 0.29)	0.98	51344.4	10100.00

2	274.59	27.84	1.640	0.30 ( 0.04)	0.13	190.5	12730.00
---	--------	-------	-------	--------------	------	-------	----------

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20188.43	22.99	1.868	0.30 ( 0.26)	0.88	4944.7	413.00
2	20938.72	25.67	1.734	0.30 ( 0.27)	0.88	5600.0	40500.00
3	21544.37	27.84	1.640	0.30 ( 0.27)	0.89	6325.3	12730.00
4	21959.46	29.39	1.573	0.30 ( 0.27)	0.89	6831.2	40440.00
5	21977.10	29.52	1.568	0.30 ( 0.27)	0.89	6872.8	430.00
6	22050.20	30.10	1.545	0.30 ( 0.27)	0.90	7064.6	12710.00
7	22174.47	31.25	1.522	0.30 ( 0.27)	0.90	7424.6	400.00
8	22335.30	32.77	1.492	0.30 ( 0.27)	0.91	7893.9	40200.00
9	24435.18	46.96	1.240	0.30 ( 0.28)	0.94	13067.6	40100.00
10	26382.65	56.45	1.114	0.30 ( 0.29)	0.95	16369.9	11801.00
11	28751.26	67.46	1.028	0.30 ( 0.29)	0.96	20899.6	11530.00
12	30095.37	76.24	0.979	0.30 ( 0.29)	0.97	25531.7	11910.00
13	32210.62	86.47	0.922	0.30 ( 0.29)	0.97	31857.5	11350.00
14	32832.17	91.24	0.897	0.30 ( 0.29)	0.97	35031.7	11130.00
15	32714.24	97.29	0.875	0.30 ( 0.29)	0.98	37958.3	12300.00
16	32632.75	101.16	0.861	0.30 ( 0.29)	0.98	40019.2	11620.00
17	32333.37	105.98	0.843	0.30 ( 0.29)	0.98	42218.9	12400.00
18	32074.39	109.22	0.832	0.30 ( 0.29)	0.98	43534.3	11111.00
19	31611.89	115.35	0.809	0.30 ( 0.29)	0.98	45620.5	12201.00
20	30857.54	122.70	0.786	0.30 ( 0.29)	0.98	47513.5	12231.00
21	30059.58	130.03	0.770	0.30 ( 0.29)	0.98	49066.2	10400.00
22	28757.54	139.22	0.750	0.30 ( 0.29)	0.98	50512.7	12010.00
23	27861.17	144.43	0.739	0.30 ( 0.29)	0.98	50775.2	10210.00
24	27299.85	148.36	0.731	0.30 ( 0.29)	0.98	50922.1	12000.00
25	24214.54	173.98	0.675	0.30 ( 0.29)	0.98	51535.0	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:  
 PEAK FLOW RATE (CFS) = 32832.17 Tc (MIN.) = 91.24  
 EFFECTIVE AREA (ACRES) = 35031.72 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97  
 TOTAL AREA (ACRES) = 51535.0  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12740.00 = 110575.24 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12740.00 TO NODE 12741.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====  
 ELEVATION DATA: UPSTREAM (FEET) = 252.10 DOWNSTREAM (FEET) = 247.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 401.47 CHANNEL SLOPE = 0.0127  
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 7.30  
 CHANNEL FLOW THRU SUBAREA (CFS) = 32832.17  
 FLOW VELOCITY (FEET/SEC.) = 19.02 FLOW DEPTH (FEET) = 7.30  
 TRAVEL TIME (MIN.) = 0.35 Tc (MIN.) = 91.60  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12741.00 = 110976.71 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 91.60  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.896  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	2.10	0.30	0.100	56
NATURAL FAIR COVER "GRASS"	B	7.50	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	0.90	0.30	1.000	66
PUBLIC PARK	B	1.90	0.30	0.850	56
RESIDENTIAL ".4 DWELLING/ACRE"	B	0.40	0.30	0.900	56
AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	0.50	0.30	1.000	79

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.833  
 SUBAREA AREA(ACRES) = 13.30 SUBAREA RUNOFF(CFS) = 7.73  
 EFFECTIVE AREA(ACRES) = 35045.02 AREA-AVERAGED Fm(INCH/HR) = 0.29  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97  
 TOTAL AREA(ACRES) = 51548.3 PEAK FLOW RATE(CFS) = 32832.17  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 91.60  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.896  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.90	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 0.90 SUBAREA RUNOFF(CFS) = 0.48  
 EFFECTIVE AREA(ACRES) = 35045.92 AREA-AVERAGED Fm(INCH/HR) = 0.29  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97  
 TOTAL AREA(ACRES) = 51549.2 PEAK FLOW RATE(CFS) = 32832.17  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<

PEAK FLOWRATE TABLE FILE NAME: 3C25EVRL.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1236.05	17.87	0.30( 0.14)	0.47	636.8	300.00
2	1242.10	23.11	0.30( 0.14)	0.48	776.0	327.00

3	1224.15	24.14	0.30( 0.14)	0.48	789.1	350.00
4	1193.48	25.51	0.30( 0.14)	0.48	803.0	320.00
5	1098.56	29.60	0.30( 0.15)	0.49	830.9	306.00
6	1010.67	37.00	0.30( 0.15)	0.50	870.6	390.00
TOTAL AREA(ACRES) =					870.6	

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20188.43	23.40	1.846	0.30( 0.26)	0.88	4958.9	413.00
2	20938.72	26.08	1.716	0.30( 0.27)	0.88	5614.2	40500.00
3	21544.37	28.25	1.623	0.30( 0.27)	0.89	6339.5	12730.00
4	21959.46	29.79	1.556	0.30( 0.27)	0.89	6845.4	40440.00
5	21977.10	29.92	1.550	0.30( 0.27)	0.89	6887.0	430.00
6	22050.20	30.51	1.537	0.30( 0.27)	0.90	7078.8	12710.00
7	22174.47	31.65	1.514	0.30( 0.27)	0.90	7438.8	400.00
8	22335.30	33.17	1.484	0.30( 0.27)	0.91	7908.1	40200.00
9	24435.18	47.35	1.235	0.30( 0.28)	0.94	13081.8	40100.00
10	26382.65	56.83	1.109	0.30( 0.29)	0.95	16384.1	11801.00
11	28751.26	67.82	1.026	0.30( 0.29)	0.96	20913.8	11530.00
12	30095.37	76.60	0.977	0.30( 0.29)	0.97	25545.9	11910.00
13	32210.62	86.82	0.920	0.30( 0.29)	0.97	31871.7	11350.00
14	32832.17	91.60	0.896	0.30( 0.29)	0.97	35045.9	11130.00
15	32714.24	97.64	0.874	0.30( 0.29)	0.98	37972.5	12300.00
16	32632.75	101.51	0.860	0.30( 0.29)	0.98	40033.4	11620.00
17	32333.37	106.33	0.842	0.30( 0.29)	0.98	42233.1	12400.00
18	32074.39	109.58	0.830	0.30( 0.29)	0.98	43548.5	11111.00
19	31611.89	115.71	0.808	0.30( 0.29)	0.98	45634.7	12201.00
20	30857.54	123.06	0.785	0.30( 0.29)	0.98	47527.7	12231.00
21	30059.58	130.39	0.769	0.30( 0.29)	0.98	49080.4	10400.00
22	28757.54	139.59	0.750	0.30( 0.29)	0.98	50526.9	12010.00
23	27861.17	144.80	0.738	0.30( 0.29)	0.98	50789.4	10210.00
24	27299.85	148.73	0.730	0.30( 0.29)	0.98	50936.3	12000.00
25	24214.54	174.37	0.674	0.30( 0.29)	0.98	51549.2	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12741.00 = 110976.71 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1236.05	17.87	2.205	0.30( 0.14)	0.47	636.8	300.00
2	1242.10	23.11	1.862	0.30( 0.14)	0.48	776.0	327.00
3	1224.15	24.14	1.808	0.30( 0.14)	0.48	789.1	350.00
4	1193.48	25.51	1.741	0.30( 0.14)	0.48	803.0	320.00
5	1098.56	29.60	1.564	0.30( 0.15)	0.49	830.9	306.00
6	1010.67	37.00	1.407	0.30( 0.15)	0.50	870.6	390.00

LONGEST FLOWPATH FROM NODE 390.00 TO NODE 12741.00 = 15238.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20156.61	17.87	2.205	0.30( 0.25)	0.82	4424.2	300.00
2	21369.37	23.11	1.862	0.30( 0.25)	0.83	5671.6	327.00

3	21425.34	23.40	1.846	0.30	( 0.25)	0.83	5738.7	413.00
4	21618.51	24.14	1.808	0.30	( 0.25)	0.83	5927.8	350.00
5	21972.54	25.51	1.741	0.30	( 0.25)	0.83	6277.8	320.00
6	22119.01	26.08	1.716	0.30	( 0.25)	0.83	6421.1	40500.00
7	22674.31	28.25	1.623	0.30	( 0.25)	0.84	7161.2	12730.00
8	23006.31	29.60	1.564	0.30	( 0.25)	0.85	7613.2	306.00
9	23055.74	29.79	1.556	0.30	( 0.25)	0.85	7677.3	40440.00
10	23071.89	29.92	1.550	0.30	( 0.25)	0.85	7719.5	430.00
11	23138.03	30.51	1.537	0.30	( 0.26)	0.85	7914.5	12710.00
12	23248.66	31.65	1.514	0.30	( 0.26)	0.86	8280.6	400.00
13	23391.45	33.17	1.484	0.30	( 0.26)	0.87	8758.1	40200.00
14	23912.55	37.00	1.407	0.30	( 0.26)	0.88	10174.6	390.00
15	25307.03	47.35	1.235	0.30	( 0.27)	0.91	13952.4	40100.00
16	27153.80	56.83	1.109	0.30	( 0.28)	0.93	17254.7	11801.00
17	29455.49	67.82	1.026	0.30	( 0.28)	0.94	21784.4	11530.00
18	30760.07	76.60	0.977	0.30	( 0.29)	0.95	26416.5	11910.00
19	32829.28	86.82	0.920	0.30	( 0.29)	0.96	32742.3	11350.00
20	33431.79	91.60	0.896	0.30	( 0.29)	0.96	35916.5	11130.00
21	33296.03	97.64	0.874	0.30	( 0.29)	0.97	38843.1	12300.00
22	33203.11	101.51	0.860	0.30	( 0.29)	0.97	40904.0	11620.00
23	32889.52	106.33	0.842	0.30	( 0.29)	0.97	43103.7	12400.00
24	32620.96	109.58	0.830	0.30	( 0.29)	0.97	44419.1	11111.00
25	32140.37	115.71	0.808	0.30	( 0.29)	0.97	46505.3	12201.00
26	31368.04	123.06	0.785	0.30	( 0.29)	0.97	48398.3	12231.00
27	30557.29	130.39	0.769	0.30	( 0.29)	0.97	49951.0	10400.00
28	29239.22	139.59	0.750	0.30	( 0.29)	0.97	51397.5	12010.00
29	28333.76	144.80	0.738	0.30	( 0.29)	0.97	51660.0	10210.00
30	27765.59	148.73	0.730	0.30	( 0.29)	0.97	51806.9	12000.00
31	24635.58	174.37	0.674	0.30	( 0.29)	0.97	52419.8	10100.00

TOTAL AREA (ACRES) = 52419.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 33431.79 Tc(MIN.) = 91.596  
EFFECTIVE AREA(ACRES) = 35916.52 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.88  
TOTAL AREA(ACRES) = 52419.8  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12741.00 = 110976.71 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 2 <<<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12741.00 TO NODE 12800.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 247.00 DOWNSTREAM(FEET) = 240.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 819.00 CHANNEL SLOPE = 0.0085  
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 8.26  
CHANNEL FLOW THRU SUBAREA(CFS) = 33431.79  
FLOW VELOCITY(FEET/SEC.) = 16.78 FLOW DEPTH(FEET) = 8.26  
TRAVEL TIME(MIN.) = 0.81 Tc(MIN.) = 92.41

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111795.71 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<

-----  
MAINLINE Tc(MIN.) = 92.41  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.893  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCSSOIL AREA Fp Ap SCSS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
NATURAL FAIR COVER  
"GRASS" B 17.31 0.30 1.000 69  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA(ACRES) = 17.31 SUBAREA RUNOFF(CFS) = 9.24  
EFFECTIVE AREA(ACRES) = 35933.83 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA(ACRES) = 52437.1 PEAK FLOW RATE(CFS) = 33431.79  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
-----

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 52437.1 TC(MIN.) = 92.41  
EFFECTIVE AREA(ACRES) = 35933.83 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.963  
PEAK FLOW RATE(CFS) = 33431.79

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20156.61	18.84	2.123	0.30( 0.25)	0.82	4441.5	300.00
2	21369.37	24.05	1.813	0.30( 0.25)	0.83	5688.9	327.00
3	21425.34	24.35	1.797	0.30( 0.25)	0.83	5756.0	413.00
4	21618.51	25.08	1.760	0.30( 0.25)	0.83	5945.1	350.00
5	21972.54	26.45	1.701	0.30( 0.25)	0.83	6295.1	320.00
6	22119.01	27.01	1.676	0.30( 0.25)	0.83	6438.4	40500.00
7	22674.31	29.18	1.583	0.30( 0.25)	0.84	7178.5	12730.00
8	23006.31	30.52	1.537	0.30( 0.25)	0.85	7630.5	306.00
9	23055.74	30.72	1.533	0.30( 0.25)	0.85	7694.6	40440.00
10	23071.89	30.84	1.530	0.30( 0.26)	0.85	7736.8	430.00
11	23138.03	31.43	1.518	0.30( 0.26)	0.85	7931.8	12710.00
12	23248.66	32.57	1.496	0.30( 0.26)	0.86	8297.9	400.00
13	23391.45	34.09	1.465	0.30( 0.26)	0.87	8775.4	40200.00
14	23912.55	37.91	1.389	0.30( 0.26)	0.88	10191.9	390.00
15	25307.03	48.25	1.221	0.30( 0.27)	0.91	13969.7	40100.00
16	27153.80	57.70	1.099	0.30( 0.28)	0.93	17272.0	11801.00
17	29455.49	68.67	1.021	0.30( 0.28)	0.94	21801.7	11530.00
18	30760.07	77.44	0.972	0.30( 0.29)	0.95	26433.8	11910.00
19	32829.28	87.64	0.915	0.30( 0.29)	0.96	32759.6	11350.00
20	33431.79	92.41	0.893	0.30( 0.29)	0.96	35933.8	11130.00
21	33296.03	98.45	0.871	0.30( 0.29)	0.97	38860.4	12300.00
22	33203.11	102.33	0.857	0.30( 0.29)	0.97	40921.3	11620.00
23	32889.52	107.15	0.839	0.30( 0.29)	0.97	43121.0	12400.00
24	32620.96	110.40	0.827	0.30( 0.29)	0.97	44436.4	11111.00
25	32140.37	116.53	0.805	0.30( 0.29)	0.97	46522.6	12201.00
26	31368.04	123.89	0.784	0.30( 0.29)	0.97	48415.6	12231.00
27	30557.29	131.23	0.768	0.30( 0.29)	0.97	49968.3	10400.00

28	29239.22	140.44	0.748	0.30 ( 0.29)	0.97	51414.8	12010.00
29	28333.76	145.66	0.736	0.30 ( 0.29)	0.97	51677.3	10210.00
30	27765.59	149.60	0.728	0.30 ( 0.29)	0.97	51824.2	12000.00
31	24635.58	175.28	0.672	0.30 ( 0.29)	0.97	52437.1	10100.00

=====  
=====  
END OF RATIONAL METHOD ANALYSIS

\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S28- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 25-YR RM EV APRIL 2019 CCHIU \*  
\*\*\*\*\*

FILE NAME: RI25EV28.DAT  
TIME/DATE OF STUDY: 09:49 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 25.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 4.933
- 2) 10.00; 3.214
- 3) 15.00; 2.451
- 4) 20.00; 2.024
- 5) 25.00; 1.763
- 6) 30.00; 1.547
- 7) 40.00; 1.347
- 8) 50.00; 1.194
- 9) 60.00; 1.070
- 10) 90.00; 0.902
- 11) 120.00; 0.792
- 12) 180.00; 0.662
- 13) 360.00; 0.490
- 14) 1200.00; 0.216

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / SIDE / WAY	CURB HEIGHT (FT)	GUTTER WIDTH (FT)	GEOMETRIES LIP (FT)	MANNING HIKE (FT)	STREETS FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI25EV27.DNA  
MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20156.61	18.84	0.30 ( 0.25)	0.82	4441.5	300.00
2	22674.31	29.18	0.30 ( 0.25)	0.84	7178.5	12730.00
3	23391.45	34.09	0.30 ( 0.26)	0.87	8775.4	40200.00
4	23912.55	37.91	0.30 ( 0.26)	0.88	10191.9	390.00
5	25307.03	48.25	0.30 ( 0.27)	0.91	13969.7	40100.00
6	27153.80	57.70	0.30 ( 0.28)	0.93	17272.0	11801.00
7	29455.49	68.67	0.30 ( 0.28)	0.94	21801.7	11530.00
8	30760.07	77.44	0.30 ( 0.29)	0.95	26433.8	11910.00
9	32829.28	87.64	0.30 ( 0.29)	0.96	32759.6	11350.00
10	33431.79	92.41	0.30 ( 0.29)	0.96	35933.8	11130.00
11	33296.03	98.45	0.30 ( 0.29)	0.97	38860.4	12300.00
12	33203.11	102.33	0.30 ( 0.29)	0.97	40921.3	11620.00
13	32889.52	107.15	0.30 ( 0.29)	0.97	43121.0	12400.00
14	32140.37	116.53	0.30 ( 0.29)	0.97	46522.6	12201.00
15	31368.04	123.89	0.30 ( 0.29)	0.97	48415.6	12231.00
16	30557.29	131.23	0.30 ( 0.29)	0.97	49968.3	10400.00
17	29239.22	140.44	0.30 ( 0.29)	0.97	51414.8	12010.00
18	28333.76	145.66	0.30 ( 0.29)	0.97	51677.3	10210.00
19	27765.59	149.60	0.30 ( 0.29)	0.97	51824.2	12000.00
20	24635.58	175.28	0.30 ( 0.29)	0.97	52437.1	10100.00
TOTAL AREA (ACRES) =						52437.1

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 0610501W.DNA  
MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1339.03	26.38	0.30 ( 0.29)	0.98	1025.9	50120.00
2	1307.01	27.68	0.30 ( 0.29)	0.98	1041.3	50150.00
3	1190.23	31.24	0.30 ( 0.29)	0.98	1063.4	50100.00
TOTAL AREA (ACRES) =						1063.4

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 3 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM	Q	Tc	Fp (Fm)	Ap	Ae	HEADWATER
--------	---	----	---------	----	----	-----------



NUMBER	(CFS)	(MIN.)	(INCH/HR)	(ACRES)	NODE
1	20156.61	18.84	0.30 ( 0.25)	0.82	4441.5 300.00
2	22674.31	29.18	0.30 ( 0.25)	0.84	7178.5 12730.00
3	23391.45	34.09	0.30 ( 0.26)	0.87	8775.4 40200.00
4	23912.55	37.91	0.30 ( 0.26)	0.88	10191.9 390.00
5	25307.03	48.25	0.30 ( 0.27)	0.91	13969.7 40100.00
6	27153.80	57.70	0.30 ( 0.28)	0.93	17272.0 11801.00
7	29455.49	68.67	0.30 ( 0.28)	0.94	21801.7 11530.00
8	30760.07	77.44	0.30 ( 0.29)	0.95	26433.8 11910.00
9	32829.28	87.64	0.30 ( 0.29)	0.96	32759.6 11350.00
10	33431.79	92.41	0.30 ( 0.29)	0.96	35933.8 11130.00
11	33296.03	98.45	0.30 ( 0.29)	0.97	38860.4 12300.00
12	33203.11	102.33	0.30 ( 0.29)	0.97	40921.3 11620.00
13	32889.52	107.15	0.30 ( 0.29)	0.97	43121.0 12400.00
14	32140.37	116.53	0.30 ( 0.29)	0.97	46522.6 12201.00
15	31368.04	123.89	0.30 ( 0.29)	0.97	48415.6 12231.00
16	30557.29	131.23	0.30 ( 0.29)	0.97	49968.3 10400.00
17	29239.22	140.44	0.30 ( 0.29)	0.97	51414.8 12010.00
18	28333.76	145.66	0.30 ( 0.29)	0.97	51677.3 10210.00
19	27765.59	149.60	0.30 ( 0.29)	0.97	51824.2 12000.00
20	24635.58	175.28	0.30 ( 0.29)	0.97	52437.1 10100.00
TOTAL AREA (ACRES) =		52437.1			

\*\*\*\*\*

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20156.61	18.84	2.123	0.30 ( 0.25)	0.82	4441.5	300.00
2	22674.31	29.18	1.583	0.30 ( 0.25)	0.84	7178.5	12730.00
3	23391.45	34.09	1.465	0.30 ( 0.26)	0.87	8775.4	40200.00
4	23912.55	37.91	1.389	0.30 ( 0.26)	0.88	10191.9	390.00
5	25307.03	48.25	1.221	0.30 ( 0.27)	0.91	13969.7	40100.00
6	27153.80	57.70	1.099	0.30 ( 0.28)	0.93	17272.0	11801.00
7	29455.49	68.67	1.021	0.30 ( 0.28)	0.94	21801.7	11530.00
8	30760.07	77.44	0.972	0.30 ( 0.29)	0.95	26433.8	11910.00
9	32829.28	87.64	0.915	0.30 ( 0.29)	0.96	32759.6	11350.00
10	33431.79	92.41	0.893	0.30 ( 0.29)	0.96	35933.8	11130.00
11	33296.03	98.45	0.871	0.30 ( 0.29)	0.97	38860.4	12300.00
12	33203.11	102.33	0.857	0.30 ( 0.29)	0.97	40921.3	11620.00
13	32889.52	107.15	0.839	0.30 ( 0.29)	0.97	43121.0	12400.00
14	32140.37	116.53	0.805	0.30 ( 0.29)	0.97	46522.6	12201.00
15	31368.04	123.89	0.784	0.30 ( 0.29)	0.97	48415.6	12231.00
16	30557.29	131.23	0.768	0.30 ( 0.29)	0.97	49968.3	10400.00
17	29239.22	140.44	0.748	0.30 ( 0.29)	0.97	51414.8	12010.00
18	28333.76	145.66	0.736	0.30 ( 0.29)	0.97	51677.3	10210.00
19	27765.59	149.60	0.728	0.30 ( 0.29)	0.97	51824.2	12000.00
20	24635.58	175.28	0.672	0.30 ( 0.29)	0.97	52437.1	10100.00
LONGEST FLOWPATH FROM NODE		10100.00 TO NODE 12800.00 = 111795.71 FEET.					

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1339.03	26.38	1.703	0.30 ( 0.29)	0.98	1025.9	50120.00

2	1307.01	27.68	1.647	0.30 ( 0.29)	0.98	1041.3	50150.00
3	1190.23	31.24	1.522	0.30 ( 0.29)	0.98	1063.4	50100.00
LONGEST FLOWPATH FROM NODE		50150.00 TO NODE 12800.00 = 11349.00 FEET.					

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21397.71	18.84	2.123	0.30 ( 0.25)	0.85	5174.1	300.00
2	23333.20	26.38	1.703	0.30 ( 0.26)	0.86	7465.0	50120.00
3	23616.73	27.68	1.647	0.30 ( 0.26)	0.86	7823.4	50150.00
4	23932.17	29.18	1.583	0.30 ( 0.26)	0.86	8229.1	12730.00
5	24165.17	31.24	1.522	0.30 ( 0.26)	0.87	8911.3	50100.00
6	24526.37	34.09	1.465	0.30 ( 0.26)	0.88	9838.8	40200.00
7	24973.42	37.91	1.389	0.30 ( 0.27)	0.89	11255.3	390.00
8	26205.04	48.25	1.221	0.30 ( 0.28)	0.92	15033.1	40100.00
9	27933.24	57.70	1.099	0.30 ( 0.28)	0.93	18335.4	11801.00
10	30160.21	68.67	1.021	0.30 ( 0.28)	0.94	22865.1	11530.00
11	31417.21	77.44	0.972	0.30 ( 0.29)	0.95	27497.2	11910.00
12	33431.04	87.64	0.915	0.30 ( 0.29)	0.96	33823.0	11350.00
13	34012.16	92.41	0.893	0.30 ( 0.29)	0.96	36997.2	11130.00
14	33854.91	98.45	0.871	0.30 ( 0.29)	0.97	39923.8	12300.00
15	33748.22	102.33	0.857	0.30 ( 0.29)	0.97	41984.7	11620.00
16	33417.51	107.15	0.839	0.30 ( 0.29)	0.97	44184.4	12400.00
17	32635.00	116.53	0.805	0.30 ( 0.29)	0.97	47586.0	12201.00
18	31842.18	123.89	0.784	0.30 ( 0.29)	0.97	49479.0	12231.00
19	31016.01	131.23	0.768	0.30 ( 0.29)	0.97	51031.7	10400.00
20	29678.60	140.44	0.748	0.30 ( 0.29)	0.97	52478.2	12010.00
21	28762.18	145.66	0.736	0.30 ( 0.29)	0.97	52740.7	10210.00
22	28185.72	149.60	0.728	0.30 ( 0.29)	0.97	52887.6	12000.00
23	25001.79	175.28	0.672	0.30 ( 0.29)	0.97	53500.5	10100.00
TOTAL AREA (ACRES) =		53500.5					

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 34012.16 Tc (MIN.) = 92.409  
EFFECTIVE AREA (ACRES) = 36997.22 AREA-AVERAGED Fm (INCH/HR) = 0.29  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94  
TOTAL AREA (ACRES) = 53500.5  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111795.71 FEET.

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 53500.5 TC (MIN.) = 92.41  
EFFECTIVE AREA (ACRES) = 36997.22 AREA-AVERAGED Fm (INCH/HR) = 0.29  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.964  
PEAK FLOW RATE (CFS) = 34012.16

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21397.71	18.84	2.123	0.30 ( 0.25)	0.85	5174.1	300.00
2	23333.20	26.38	1.703	0.30 ( 0.26)	0.86	7465.0	50120.00
3	23616.73	27.68	1.647	0.30 ( 0.26)	0.86	7823.4	50150.00
4	23932.17	29.18	1.583	0.30 ( 0.26)	0.86	8229.1	12730.00
5	24165.17	31.24	1.522	0.30 ( 0.26)	0.87	8911.3	50100.00
6	24526.37	34.09	1.465	0.30 ( 0.26)	0.88	9838.8	40200.00
7	24973.42	37.91	1.389	0.30 ( 0.27)	0.89	11255.3	390.00
8	26205.04	48.25	1.221	0.30 ( 0.28)	0.92	15033.1	40100.00
9	27933.24	57.70	1.099	0.30 ( 0.28)	0.93	18335.4	11801.00
10	30160.21	68.67	1.021	0.30 ( 0.28)	0.94	22865.1	11530.00

11	31417.21	77.44	0.972	0.30 ( 0.29)	0.95	27497.2	11910.00
12	33431.04	87.64	0.915	0.30 ( 0.29)	0.96	33823.0	11350.00
13	34012.16	92.41	0.893	0.30 ( 0.29)	0.96	36997.2	11130.00
14	33854.91	98.45	0.871	0.30 ( 0.29)	0.97	39923.8	12300.00
15	33748.22	102.33	0.857	0.30 ( 0.29)	0.97	41984.7	11620.00
16	33417.51	107.15	0.839	0.30 ( 0.29)	0.97	44184.4	12400.00
17	32635.00	116.53	0.805	0.30 ( 0.29)	0.97	47586.0	12201.00
18	31842.18	123.89	0.784	0.30 ( 0.29)	0.97	49479.0	12231.00
19	31016.01	131.23	0.768	0.30 ( 0.29)	0.97	51031.7	10400.00
20	29678.60	140.44	0.748	0.30 ( 0.29)	0.97	52478.2	12010.00
21	28762.18	145.66	0.736	0.30 ( 0.29)	0.97	52740.7	10210.00
22	28185.72	149.60	0.728	0.30 ( 0.29)	0.97	52887.6	12000.00
23	25001.79	175.28	0.672	0.30 ( 0.29)	0.97	53500.5	10100.00

=====  
=====  
END OF RATIONAL METHOD ANALYSIS

\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S29- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 25-YR RM EV APRIL 2019 CCHIU \*  
\*\*\*\*\*

FILE NAME: RI25EV29.DAT  
TIME/DATE OF STUDY: 09:50 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 25.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 4.920
- 2) 10.00; 3.206
- 3) 15.00; 2.446
- 4) 20.00; 2.021
- 5) 25.00; 1.761
- 6) 30.00; 1.545
- 7) 40.00; 1.345
- 8) 50.00; 1.192
- 9) 60.00; 1.068
- 10) 90.00; 0.900
- 11) 120.00; 0.790
- 12) 180.00; 0.660
- 13) 360.00; 0.488
- 14) 1200.00; 0.215

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI25EV28.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21397.71	18.84	0.30 ( 0.25)	0.85	5174.1	300.00
2	24165.17	31.24	0.30 ( 0.26)	0.87	8911.3	50100.00
3	24526.37	34.09	0.30 ( 0.26)	0.88	9838.8	40200.00
4	24973.42	37.91	0.30 ( 0.27)	0.89	11255.3	390.00
5	26205.04	48.25	0.30 ( 0.28)	0.92	15033.1	40100.00
6	27933.24	57.70	0.30 ( 0.28)	0.93	18335.4	11801.00
7	30160.21	68.67	0.30 ( 0.28)	0.94	22865.1	11530.00
8	31417.21	77.44	0.30 ( 0.29)	0.95	27497.2	11910.00
9	33431.04	87.64	0.30 ( 0.29)	0.96	33823.0	11350.00
10	34012.16	92.41	0.30 ( 0.29)	0.96	36997.2	11130.00
11	33854.91	98.45	0.30 ( 0.29)	0.97	39923.8	12300.00
12	33748.22	102.33	0.30 ( 0.29)	0.97	41984.7	11620.00
13	33417.51	107.15	0.30 ( 0.29)	0.97	44184.4	12400.00
14	32635.00	116.53	0.30 ( 0.29)	0.97	47586.0	12201.00
15	31842.18	123.89	0.30 ( 0.29)	0.97	49479.0	12231.00
16	31016.01	131.23	0.30 ( 0.29)	0.97	51031.7	10400.00
17	29678.60	140.44	0.30 ( 0.29)	0.97	52478.2	12010.00
18	28762.18	145.66	0.30 ( 0.29)	0.97	52740.7	10210.00
19	28185.72	149.60	0.30 ( 0.29)	0.97	52887.6	12000.00
20	25001.79	175.28	0.30 ( 0.29)	0.97	53500.5	10100.00
TOTAL AREA (ACRES) =						53500.5

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21397.71	18.84	0.30 ( 0.25)	0.85	5174.1	300.00
2	24165.17	31.24	0.30 ( 0.26)	0.87	8911.3	50100.00
3	24526.37	34.09	0.30 ( 0.26)	0.88	9838.8	40200.00
4	24973.42	37.91	0.30 ( 0.27)	0.89	11255.3	390.00
5	26205.04	48.25	0.30 ( 0.28)	0.92	15033.1	40100.00
6	27933.24	57.70	0.30 ( 0.28)	0.93	18335.4	11801.00
7	30160.21	68.67	0.30 ( 0.28)	0.94	22865.1	11530.00
8	31417.21	77.44	0.30 ( 0.29)	0.95	27497.2	11910.00
9	33431.04	87.64	0.30 ( 0.29)	0.96	33823.0	11350.00
10	34012.16	92.41	0.30 ( 0.29)	0.96	36997.2	11130.00
11	33854.91	98.45	0.30 ( 0.29)	0.97	39923.8	12300.00
12	33748.22	102.33	0.30 ( 0.29)	0.97	41984.7	11620.00
13	33417.51	107.15	0.30 ( 0.29)	0.97	44184.4	12400.00

14	32635.00	116.53	0.30	( 0.29)	0.97	47586.0	12201.00
15	31842.18	123.89	0.30	( 0.29)	0.97	49479.0	12231.00
16	31016.01	131.23	0.30	( 0.29)	0.97	51031.7	10400.00
17	29678.60	140.44	0.30	( 0.29)	0.97	52478.2	12010.00
18	28762.18	145.66	0.30	( 0.29)	0.97	52740.7	10210.00
19	28185.72	149.60	0.30	( 0.29)	0.97	52887.6	12000.00
20	25001.79	175.28	0.30	( 0.29)	0.97	53500.5	10100.00

TOTAL AREA (ACRES) = 53500.5

\*\*\*\*\*

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 12800.00 TO NODE 12901.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 240.00 DOWNSTREAM (FEET) = 216.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 3120.28 CHANNEL SLOPE = 0.0077  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 8.59  
CHANNEL FLOW THRU SUBAREA (CFS) = 34012.16  
FLOW VELOCITY (FEET/SEC.) = 16.29 FLOW DEPTH (FEET) = 8.59  
TRAVEL TIME (MIN.) = 3.19 Tc (MIN.) = 95.60  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12901.00 = 114915.99 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 95.60  
\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.879  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	2.60	0.30	0.100	56
COMMERCIAL	B	3.20	0.30	0.100	56
PUBLIC PARK	B	1.50	0.30	0.850	56
COMMERCIAL	B	5.60	0.30	0.100	56
PUBLIC PARK	B	6.50	0.30	0.850	56

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.409  
SUBAREA AREA (ACRES) = 19.40 SUBAREA RUNOFF (CFS) = 13.21  
EFFECTIVE AREA (ACRES) = 37016.62 AREA-AVERAGED Fm (INCH/HR) = 0.29  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA (ACRES) = 53519.9 PEAK FLOW RATE (CFS) = 34012.16  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 95.60  
\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.879  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	0.50	0.30	0.100	56
PUBLIC PARK	B	4.10	0.30	0.850	56
PUBLIC PARK	B	0.10	0.30	0.850	56
RESIDENTIAL ".4 DWELLING/ACRE"	B	1.60	0.30	0.900	56
RESIDENTIAL ".4 DWELLING/ACRE"	B	0.60	0.30	0.900	56
RESIDENTIAL ".4 DWELLING/ACRE"	B	1.00	0.30	0.900	56

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.823  
SUBAREA AREA (ACRES) = 7.90 SUBAREA RUNOFF (CFS) = 4.50  
EFFECTIVE AREA (ACRES) = 37024.52 AREA-AVERAGED Fm (INCH/HR) = 0.29  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA (ACRES) = 53527.8 PEAK FLOW RATE (CFS) = 34012.16  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 95.60  
\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.879  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL ".4 DWELLING/ACRE"	B	3.60	0.30	0.900	56
AGRICULTURAL FAIR COVER "ORCHARDS"	B	0.30	0.30	1.000	65
NATURAL POOR COVER "BARREN"	B	12.00	0.30	1.000	86
PUBLIC PARK	B	36.10	0.30	0.850	56
NATURAL FAIR COVER "GRASS"	B	15.90	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	1.50	0.30	1.000	69

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.917  
SUBAREA AREA (ACRES) = 69.40 SUBAREA RUNOFF (CFS) = 37.75  
EFFECTIVE AREA (ACRES) = 37093.91 AREA-AVERAGED Fm (INCH/HR) = 0.29  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA (ACRES) = 53597.2 PEAK FLOW RATE (CFS) = 34012.16  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 95.60

\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.879  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL FAIR COVER  
 "WOODLAND,GRASS" B 4.20 0.30 1.000 65  
 NATURAL FAIR COVER  
 "WOODLAND,GRASS" B 0.40 0.30 1.000 65  
 NATURAL FAIR COVER  
 "WOODLAND,GRASS" B 1.00 0.30 1.000 65  
 RESIDENTIAL  
 "5-7 DWELLINGS/ACRE" B 4.10 0.30 0.500 56  
 RESIDENTIAL  
 "5-7 DWELLINGS/ACRE" B 3.70 0.30 0.500 56  
 RESIDENTIAL  
 "5-7 DWELLINGS/ACRE" B 0.40 0.30 0.500 56  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.703  
 SUBAREA AREA (ACRES) = 13.80 SUBAREA RUNOFF (CFS) = 8.30  
 EFFECTIVE AREA (ACRES) = 37107.71 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA (ACRES) = 53611.0 PEAK FLOW RATE (CFS) = 34012.16  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 =====

MAINLINE Tc (MIN.) = 95.60  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.879  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 6.70 0.30 1.000 66  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 1.20 0.30 1.000 66  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 2.90 0.30 1.000 66  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 10.80 SUBAREA RUNOFF (CFS) = 5.63  
 EFFECTIVE AREA (ACRES) = 37118.52 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA (ACRES) = 53621.8 PEAK FLOW RATE (CFS) = 34012.16  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12901.00 TO NODE 12902.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM (FEET) = 216.00 DOWNSTREAM (FEET) = 215.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 122.04 CHANNEL SLOPE = 0.0082  
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT (FEET) = 8.44  
 CHANNEL FLOW THRU SUBAREA (CFS) = 34012.16  
 FLOW VELOCITY (FEET/SEC.) = 16.64 FLOW DEPTH (FEET) = 8.44  
 TRAVEL TIME (MIN.) = 0.12 Tc (MIN.) = 95.72  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115038.03 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 3 <<<<<  
 =====

PEAK FLOWRATE TABLE FILE NAME: E502XX25.DNA  
 MEMORY BANK # 3 DEFINED AS FOLLOWS:  
 STREAM Q Tc Fp (Fm) Ap Ae HEADWATER  
 NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE  
 1 58.93 11.21 0.30 ( 0.27) 0.91 28.7 50200.00  
 TOTAL AREA (ACRES) = 28.7

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<  
 =====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21397.71	22.71	1.880	0.30 ( 0.25)	0.84	5295.4	300.00
2	24165.17	34.95	1.446	0.30 ( 0.26)	0.87	9032.6	50100.00
3	24526.37	37.79	1.389	0.30 ( 0.26)	0.88	9960.1	40200.00
4	24973.42	41.58	1.321	0.30 ( 0.27)	0.89	11376.6	390.00
5	26205.04	51.86	1.169	0.30 ( 0.28)	0.92	15154.4	40100.00
6	27933.24	61.24	1.061	0.30 ( 0.28)	0.93	18456.7	11801.00
7	30160.21	72.12	1.000	0.30 ( 0.28)	0.94	22986.4	11530.00
8	31417.21	80.84	0.951	0.30 ( 0.29)	0.95	27618.5	11910.00
9	33431.04	90.97	0.896	0.30 ( 0.29)	0.96	33944.3	11350.00
10	34012.16	95.72	0.879	0.30 ( 0.29)	0.96	37118.5	11130.00
11	33854.91	101.77	0.857	0.30 ( 0.29)	0.97	40045.1	12300.00
12	33748.22	105.65	0.843	0.30 ( 0.29)	0.97	42106.0	11620.00
13	33417.51	110.48	0.825	0.30 ( 0.29)	0.97	44305.7	12400.00
14	32635.00	119.89	0.790	0.30 ( 0.29)	0.97	47707.3	12201.00
15	31842.18	127.27	0.774	0.30 ( 0.29)	0.97	49600.3	12231.00
16	31016.01	134.65	0.758	0.30 ( 0.29)	0.97	51153.0	10400.00
17	29678.60	143.91	0.738	0.30 ( 0.29)	0.97	52599.5	12010.00
18	28762.18	149.16	0.727	0.30 ( 0.29)	0.97	52862.0	10210.00
19	28185.72	153.13	0.718	0.30 ( 0.29)	0.97	53008.8	12000.00
20	25001.79	178.95	0.662	0.30 ( 0.29)	0.97	53621.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115038.03 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	58.93	11.21	3.021	0.30 ( 0.27)	0.91	28.7	50200.00

LONGEST FLOWPATH FROM NODE 50200.00 TO NODE 12902.00 = 1426.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
---------------	---------	-----------	---------------------	-------------------	----	------------	----------------

1	18038.00	11.21	3.021	0.30	( 0.25)	0.85	2643.1	50200.00
2	21432.16	22.71	1.880	0.30	( 0.25)	0.85	5324.1	300.00
3	24190.32	34.95	1.446	0.30	( 0.26)	0.87	9061.3	50100.00
4	24550.30	37.79	1.389	0.30	( 0.26)	0.88	9988.8	40200.00
5	24995.89	41.58	1.321	0.30	( 0.27)	0.89	11405.3	390.00
6	26224.25	51.86	1.169	0.30	( 0.28)	0.92	15183.1	40100.00
7	27950.14	61.24	1.061	0.30	( 0.28)	0.93	18485.4	11801.00
8	30175.80	72.12	1.000	0.30	( 0.28)	0.94	23015.1	11530.00
9	31431.75	80.84	0.951	0.30	( 0.29)	0.95	27647.2	11910.00
10	33444.40	90.97	0.896	0.30	( 0.29)	0.96	33973.0	11350.00
11	34025.15	95.72	0.879	0.30	( 0.29)	0.96	37147.2	11130.00
12	33867.43	101.77	0.857	0.30	( 0.29)	0.97	40073.8	12300.00
13	33760.43	105.65	0.843	0.30	( 0.29)	0.97	42134.7	11620.00
14	33429.34	110.48	0.825	0.30	( 0.29)	0.97	44334.4	12400.00
15	32646.09	119.89	0.790	0.30	( 0.29)	0.97	47736.0	12201.00
16	31852.93	127.27	0.774	0.30	( 0.29)	0.97	49629.0	12231.00
17	31026.41	134.65	0.758	0.30	( 0.29)	0.97	51181.7	10400.00
18	29688.57	143.91	0.738	0.30	( 0.29)	0.97	52628.2	12010.00
19	28771.91	149.16	0.727	0.30	( 0.29)	0.97	52890.7	10210.00
20	28195.27	153.13	0.718	0.30	( 0.29)	0.97	53037.5	12000.00
21	25010.14	178.95	0.662	0.30	( 0.29)	0.97	53650.5	10100.00

TOTAL AREA (ACRES) = 53650.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 34025.15 Tc (MIN.) = 95.724  
EFFECTIVE AREA (ACRES) = 37147.21 AREA-AVERAGED Fm (INCH/HR) = 0.29  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA (ACRES) = 53650.5  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115038.03 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: E503XX25.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	430.88	25.25	1.750	0.30 ( 0.30)	0.99	366.4	50300.00

TOTAL AREA (ACRES) = 366.4

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18038.00	11.21	3.021	0.30 ( 0.25)	0.85	2643.1	50200.00

2	21432.16	22.71	1.880	0.30	( 0.25)	0.85	5324.1	300.00
3	24190.32	34.95	1.446	0.30	( 0.26)	0.87	9061.3	50100.00
4	24550.30	37.79	1.389	0.30	( 0.26)	0.88	9988.8	40200.00
5	24995.89	41.58	1.321	0.30	( 0.27)	0.89	11405.3	390.00
6	26224.25	51.86	1.169	0.30	( 0.28)	0.92	15183.1	40100.00
7	27950.14	61.24	1.061	0.30	( 0.28)	0.93	18485.4	11801.00
8	30175.80	72.12	1.000	0.30	( 0.28)	0.94	23015.1	11530.00
9	31431.75	80.84	0.951	0.30	( 0.29)	0.95	27647.2	11910.00
10	33444.40	90.97	0.896	0.30	( 0.29)	0.96	33973.0	11350.00
11	34025.15	95.72	0.879	0.30	( 0.29)	0.96	37147.2	11130.00
12	33867.43	101.77	0.857	0.30	( 0.29)	0.97	40073.8	12300.00
13	33760.43	105.65	0.843	0.30	( 0.29)	0.97	42134.7	11620.00
14	33429.34	110.48	0.825	0.30	( 0.29)	0.97	44334.4	12400.00
15	32646.09	119.89	0.790	0.30	( 0.29)	0.97	47736.0	12201.00
16	31852.93	127.27	0.774	0.30	( 0.29)	0.97	49629.0	12231.00
17	31026.41	134.65	0.758	0.30	( 0.29)	0.97	51181.7	10400.00
18	29688.57	143.91	0.738	0.30	( 0.29)	0.97	52628.2	12010.00
19	28771.91	149.16	0.727	0.30	( 0.29)	0.97	52890.7	10210.00
20	28195.27	153.13	0.718	0.30	( 0.29)	0.97	53037.5	12000.00
21	25010.14	178.95	0.662	0.30	( 0.29)	0.97	53650.5	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115038.03 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	430.88	25.25	1.750	0.30 ( 0.30)	0.99	366.4	50300.00

LONGEST FLOWPATH FROM NODE 50300.00 TO NODE 12902.00 = 8614.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18396.61	11.21	3.021	0.30 ( 0.26)	0.85	2805.8	50200.00
2	21854.33	22.71	1.880	0.30 ( 0.26)	0.85	5653.7	300.00
3	22433.63	25.25	1.750	0.30 ( 0.26)	0.86	6463.6	50300.00
4	24531.04	34.95	1.446	0.30 ( 0.26)	0.87	9427.7	50100.00
5	24874.23	37.79	1.389	0.30 ( 0.26)	0.88	10355.2	40200.00
6	25299.53	41.58	1.321	0.30 ( 0.27)	0.89	11771.7	390.00
7	26482.92	51.86	1.169	0.30 ( 0.28)	0.92	15549.5	40100.00
8	28176.87	61.24	1.061	0.30 ( 0.28)	0.93	18851.8	11801.00
9	30384.48	72.12	1.000	0.30 ( 0.28)	0.94	23381.5	11530.00
10	31625.97	80.84	0.951	0.30 ( 0.29)	0.95	28013.6	11910.00
11	33622.38	90.97	0.896	0.30 ( 0.29)	0.96	34339.4	11350.00
12	34197.96	95.72	0.879	0.30 ( 0.29)	0.96	37513.6	11130.00
13	34033.68	101.77	0.857	0.30 ( 0.29)	0.97	40440.2	12300.00
14	33922.46	105.65	0.843	0.30 ( 0.29)	0.97	42501.1	11620.00
15	33586.13	110.48	0.825	0.30 ( 0.29)	0.97	44700.8	12400.00
16	32792.66	119.89	0.790	0.30 ( 0.29)	0.97	48102.4	12201.00
17	31994.71	127.27	0.774	0.30 ( 0.29)	0.97	49995.4	12231.00
18	31163.46	134.65	0.758	0.30 ( 0.29)	0.97	51548.1	10400.00
19	29819.68	143.91	0.738	0.30 ( 0.29)	0.97	52994.6	12010.00
20	28899.65	149.16	0.727	0.30 ( 0.29)	0.97	53257.1	10210.00
21	28320.46	153.13	0.718	0.30 ( 0.29)	0.97	53403.9	12000.00
22	25118.76	178.95	0.662	0.30 ( 0.29)	0.97	54016.9	10100.00

TOTAL AREA (ACRES) = 54016.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 34197.96 Tc (MIN.) = 95.724  
EFFECTIVE AREA (ACRES) = 37513.61 AREA-AVERAGED Fm (INCH/HR) = 0.29

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA (ACRES) = 54016.9  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115038.03 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 12902.00 TO NODE 12903.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 215.00 DOWNSTREAM(FEET) = 214.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 895.53 CHANNEL SLOPE = 0.0011  
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT(FEET) = 14.77  
 CHANNEL FLOW THRU SUBAREA(CFS) = 34197.96  
 FLOW VELOCITY(FEET/SEC.) = 8.45 FLOW DEPTH(FEET) = 14.77  
 TRAVEL TIME(MIN.) = 1.77 Tc(MIN.) = 97.49  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115933.56 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: E504XX25.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	108.86	17.34	0.30 (0.29)	0.97	70.5	50400.00
TOTAL AREA (ACRES) = 70.5						

\*\*\*\*\*

FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18396.61	13.36	2.695	0.30 (0.26)	0.85	2805.8	50200.00
2	21854.33	24.74	1.774	0.30 (0.26)	0.85	5653.7	300.00
3	22433.63	27.26	1.663	0.30 (0.26)	0.86	6463.6	50300.00
4	24531.04	36.91	1.407	0.30 (0.26)	0.87	9427.7	50100.00
5	24874.23	39.74	1.350	0.30 (0.26)	0.88	10355.2	40200.00
6	25299.53	43.52	1.291	0.30 (0.27)	0.89	11771.7	390.00
7	26482.92	53.77	1.145	0.30 (0.28)	0.92	15549.5	40100.00
8	28176.87	63.11	1.051	0.30 (0.28)	0.93	18851.8	11801.00
9	30384.48	73.95	0.990	0.30 (0.28)	0.94	23381.5	11530.00
10	31625.97	82.65	0.941	0.30 (0.29)	0.95	28013.6	11910.00
11	33622.38	92.75	0.890	0.30 (0.29)	0.96	34339.4	11350.00

12	34197.96	97.49	0.873	0.30 (0.29)	0.96	37513.6	11130.00
13	34033.68	103.54	0.850	0.30 (0.29)	0.97	40440.2	12300.00
14	33922.46	107.42	0.836	0.30 (0.29)	0.97	42501.1	11620.00
15	33586.13	112.26	0.818	0.30 (0.29)	0.97	44700.8	12400.00
16	32792.66	121.68	0.786	0.30 (0.29)	0.97	48102.4	12201.00
17	31994.71	129.08	0.770	0.30 (0.29)	0.97	49995.4	12231.00
18	31163.46	136.46	0.754	0.30 (0.29)	0.97	51548.1	10400.00
19	29819.68	145.75	0.734	0.30 (0.29)	0.97	52994.6	12010.00
20	28899.65	151.02	0.723	0.30 (0.29)	0.97	53257.1	10210.00
21	28320.46	155.00	0.714	0.30 (0.29)	0.97	53403.9	12000.00
22	25118.76	180.89	0.659	0.30 (0.29)	0.97	54016.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115933.56 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	108.86	17.34	2.247	0.30 (0.29)	0.97	70.5	50400.00

LONGEST FLOWPATH FROM NODE 50400.00 TO NODE 12903.00 = 3607.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18499.69	13.36	2.695	0.30 (0.26)	0.86	2860.2	50200.00
2	19714.22	17.34	2.247	0.30 (0.26)	0.86	3871.9	50400.00
3	21936.88	24.74	1.774	0.30 (0.26)	0.85	5724.2	300.00
4	22510.02	27.26	1.663	0.30 (0.26)	0.86	6534.1	50300.00
5	24593.15	36.91	1.407	0.30 (0.26)	0.87	9498.2	50100.00
6	24933.20	39.74	1.350	0.30 (0.26)	0.88	10425.7	40200.00
7	25355.21	43.52	1.291	0.30 (0.27)	0.89	11842.2	390.00
8	26530.48	53.77	1.145	0.30 (0.28)	0.92	15620.0	40100.00
9	28219.17	63.11	1.051	0.30 (0.28)	0.93	18922.3	11801.00
10	30423.41	73.95	0.990	0.30 (0.28)	0.94	23452.0	11530.00
11	31662.19	82.65	0.941	0.30 (0.29)	0.95	28084.1	11910.00
12	33655.74	92.75	0.890	0.30 (0.29)	0.96	34409.9	11350.00
13	34230.37	97.49	0.873	0.30 (0.29)	0.96	37584.1	11130.00
14	34064.84	103.54	0.850	0.30 (0.29)	0.97	40510.7	12300.00
15	33952.84	107.42	0.836	0.30 (0.29)	0.97	42571.6	11620.00
16	33615.52	112.26	0.818	0.30 (0.29)	0.97	44771.3	12400.00
17	32820.27	121.68	0.786	0.30 (0.29)	0.97	48172.9	12201.00
18	32021.43	129.08	0.770	0.30 (0.29)	0.97	50065.9	12231.00
19	31189.29	136.46	0.754	0.30 (0.29)	0.97	51618.6	10400.00
20	29844.39	145.75	0.734	0.30 (0.29)	0.97	53065.1	12010.00
21	28923.72	151.02	0.723	0.30 (0.29)	0.97	53327.6	10210.00
22	28344.06	155.00	0.714	0.30 (0.29)	0.97	53474.4	12000.00
23	25139.30	180.89	0.659	0.30 (0.29)	0.97	54087.4	10100.00

TOTAL AREA (ACRES) = 54087.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 34230.37 Tc (MIN.) = 97.490  
 EFFECTIVE AREA (ACRES) = 37584.11 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA (ACRES) = 54087.4  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115933.56 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

```

=====
*****
FLOW PROCESS FROM NODE 12903.00 TO NODE 12904.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 214.00 DOWNSTREAM(FEET) = 213.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 767.57 CHANNEL SLOPE = 0.0013
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 14.17
CHANNEL FLOW THRU SUBAREA(CFS) = 34230.37
FLOW VELOCITY(FEET/SEC.) = 8.92 FLOW DEPTH(FEET) = 14.17
TRAVEL TIME(MIN.) = 1.43 Tc(MIN.) = 98.92
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116701.13 FEET.
*****
FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 15.1
-----
>>>>DEFINE MEMORY BANK # 3 <<<<
=====
PEAK FLOWRATE TABLE FILE NAME: 3B25EVRL.DNA
MEMORY BANK # 3 DEFINED AS FOLLOWS:
STREAM Q Tc Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 407.13 14.83 0.30( 0.13) 0.42 192.8 200.00
2 404.03 17.69 0.30( 0.13) 0.42 214.7 210.00
TOTAL AREA(ACRES) = 214.7
*****
FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 11
-----
>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<
=====
** MAIN STREAM CONFLUENCE DATA **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 18499.69 15.10 2.437 0.30( 0.26) 0.86 2860.2 50200.00
2 19714.22 19.05 2.102 0.30( 0.26) 0.86 3871.9 50400.00
3 21936.88 26.39 1.701 0.30( 0.26) 0.85 5724.2 300.00
4 22510.02 28.89 1.593 0.30( 0.26) 0.86 6534.1 50300.00
5 24593.15 38.50 1.375 0.30( 0.26) 0.87 9498.2 50100.00
6 24933.20 41.32 1.325 0.30( 0.26) 0.88 10425.7 40200.00
7 25355.21 45.10 1.267 0.30( 0.27) 0.89 11842.2 390.00
8 26530.48 55.33 1.126 0.30( 0.28) 0.92 15620.0 40100.00
9 28219.17 64.64 1.042 0.30( 0.28) 0.93 18922.3 11801.00
10 30423.41 75.44 0.982 0.30( 0.28) 0.94 23452.0 11530.00
11 31662.19 84.12 0.933 0.30( 0.29) 0.95 28084.1 11910.00
12 33655.74 94.19 0.885 0.30( 0.29) 0.96 34409.9 11350.00
13 34230.37 98.92 0.867 0.30( 0.29) 0.96 37584.1 11130.00
14 34064.84 104.98 0.845 0.30( 0.29) 0.97 40510.7 12300.00
15 33952.84 108.86 0.831 0.30( 0.29) 0.97 42571.6 11620.00
16 33615.52 113.70 0.813 0.30( 0.29) 0.97 44771.3 12400.00
17 32820.27 123.14 0.783 0.30( 0.29) 0.97 48172.9 12201.00
18 32021.43 130.54 0.767 0.30( 0.29) 0.97 50065.9 12231.00

```

```

19 31189.29 137.94 0.751 0.30( 0.29) 0.97 51618.6 10400.00
20 29844.39 147.25 0.731 0.30( 0.29) 0.97 53065.1 12010.00
21 28923.72 152.53 0.720 0.30( 0.29) 0.97 53327.6 10210.00
22 28344.06 156.52 0.711 0.30( 0.29) 0.97 53474.4 12000.00
23 25139.30 182.47 0.658 0.30( 0.29) 0.97 54087.4 10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116701.13 FEET.
** MEMORY BANK # 3 CONFLUENCE DATA **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 407.13 14.83 2.472 0.30( 0.13) 0.42 192.8 200.00
2 404.03 17.69 2.217 0.30( 0.13) 0.42 214.7 210.00
LONGEST FLOWPATH FROM NODE 210.00 TO NODE 12904.00 = 5961.00 FEET.
** PEAK FLOW RATE TABLE **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 18861.10 14.83 2.472 0.30( 0.25) 0.83 3001.0 200.00
2 18906.51 15.10 2.437 0.30( 0.25) 0.83 3055.1 50200.00
3 19700.72 17.69 2.217 0.30( 0.25) 0.83 3738.8 210.00
4 20095.98 19.05 2.102 0.30( 0.25) 0.83 4086.6 50400.00
5 22241.11 26.39 1.701 0.30( 0.25) 0.84 5938.9 300.00
6 22793.37 28.89 1.593 0.30( 0.25) 0.84 6748.8 50300.00
7 24834.42 38.50 1.375 0.30( 0.26) 0.86 9712.9 50100.00
8 25164.78 41.32 1.325 0.30( 0.26) 0.87 10640.4 40200.00
9 25575.61 45.10 1.267 0.30( 0.26) 0.88 12056.9 390.00
10 26723.63 55.33 1.126 0.30( 0.27) 0.91 15834.7 40100.00
11 28396.10 64.64 1.042 0.30( 0.28) 0.93 19137.0 11801.00
12 30588.65 75.44 0.982 0.30( 0.28) 0.94 23666.7 11530.00
13 31818.04 84.12 0.933 0.30( 0.28) 0.95 28298.8 11910.00
14 33802.26 94.19 0.885 0.30( 0.29) 0.96 34624.6 11350.00
15 34373.53 98.92 0.867 0.30( 0.29) 0.96 37798.8 11130.00
16 34203.71 104.98 0.845 0.30( 0.29) 0.96 40725.4 12300.00
17 34088.96 108.86 0.831 0.30( 0.29) 0.96 42786.3 11620.00
18 33748.21 113.70 0.813 0.30( 0.29) 0.96 44986.0 12400.00
19 32947.18 123.14 0.783 0.30( 0.29) 0.97 48387.6 12201.00
20 32145.25 130.54 0.767 0.30( 0.29) 0.97 50280.6 12231.00
21 31310.01 137.94 0.751 0.30( 0.29) 0.97 51833.3 10400.00
22 29961.21 147.25 0.731 0.30( 0.29) 0.97 53279.8 12010.00
23 29038.33 152.53 0.720 0.30( 0.29) 0.97 53542.3 10210.00
24 28457.00 156.52 0.711 0.30( 0.29) 0.97 53689.1 12000.00
25 25241.95 182.47 0.658 0.30( 0.29) 0.97 54302.1 10100.00
TOTAL AREA(ACRES) = 54302.1
COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
PEAK FLOW RATE(CFS) = 34373.53 Tc(MIN.) = 98.924
EFFECTIVE AREA(ACRES) = 37798.81 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
TOTAL AREA(ACRES) = 54302.1
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116701.13 FEET.
*****
FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 98.92
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.867

```



SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	0.70	0.30	0.100	56
NATURAL FAIR COVER "GRASS"	B	20.00	0.30	1.000	69
NATURAL FAIR COVER "MEADOWS"	B	0.10	0.30	1.000	70
PUBLIC PARK	B	14.90	0.30	0.850	56
RESIDENTIAL ".4 DWELLING/ACRE"	B	2.60	0.30	0.900	56
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.80	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.920  
SUBAREA AREA(ACRES) = 39.10 SUBAREA RUNOFF(CFS) = 20.81  
EFFECTIVE AREA(ACRES) = 37837.91 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA(ACRES) = 54341.2 PEAK FLOW RATE(CFS) = 34373.53  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 98.92  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.867

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	0.30	0.30	0.100	56
NATURAL FAIR COVER "OPEN BRUSH"	B	0.10	0.30	1.000	66
AGRICULTURAL FAIR COVER "ORCHARDS"	B	0.10	0.30	1.000	65
RESIDENTIAL ".4 DWELLING/ACRE"	B	1.70	0.30	0.900	56
NATURAL FAIR COVER "GRASS"	B	2.60	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	0.20	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.912  
SUBAREA AREA(ACRES) = 5.00 SUBAREA RUNOFF(CFS) = 2.67  
EFFECTIVE AREA(ACRES) = 37842.91 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA(ACRES) = 54346.2 PEAK FLOW RATE(CFS) = 34373.53  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 98.92  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.867  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL FAIR COVER "ORCHARDS"	B	0.10	0.30	1.000	65
RESIDENTIAL ".4 DWELLING/ACRE"	B	2.60	0.30	0.900	56
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.20	0.30	1.000	65
NATURAL FAIR COVER "GRASS"	B	3.00	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.956  
SUBAREA AREA(ACRES) = 5.90 SUBAREA RUNOFF(CFS) = 3.08  
EFFECTIVE AREA(ACRES) = 37848.81 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA(ACRES) = 54352.1 PEAK FLOW RATE(CFS) = 34373.53  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

=====

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 54352.1 TC(MIN.) = 98.92  
EFFECTIVE AREA(ACRES) = 37848.81 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.960  
PEAK FLOW RATE(CFS) = 34373.53

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18861.10	14.83	2.472	0.30( 0.25)	0.83	3051.0	200.00
2	18906.51	15.10	2.437	0.30( 0.25)	0.83	3105.1	50200.00
3	19700.72	17.69	2.217	0.30( 0.25)	0.83	3788.8	210.00
4	20095.98	19.05	2.102	0.30( 0.25)	0.83	4136.6	50400.00
5	22241.11	26.39	1.701	0.30( 0.25)	0.84	5988.9	300.00
6	22793.37	28.89	1.593	0.30( 0.25)	0.85	6798.8	50300.00
7	24834.42	38.50	1.375	0.30( 0.26)	0.86	9762.9	50100.00
8	25164.78	41.32	1.325	0.30( 0.26)	0.87	10690.4	40200.00
9	25575.61	45.10	1.267	0.30( 0.27)	0.88	12106.9	390.00
10	26723.63	55.33	1.126	0.30( 0.27)	0.91	15884.7	40100.00
11	28396.10	64.64	1.042	0.30( 0.28)	0.93	19187.0	11801.00
12	30588.65	75.44	0.982	0.30( 0.28)	0.94	23716.7	11530.00
13	31818.04	84.12	0.933	0.30( 0.28)	0.95	28348.8	11910.00
14	33802.26	94.19	0.885	0.30( 0.29)	0.96	34674.6	11350.00
15	34373.53	98.92	0.867	0.30( 0.29)	0.96	37848.8	11130.00
16	34203.71	104.98	0.845	0.30( 0.29)	0.96	40775.4	12300.00
17	34088.96	108.86	0.831	0.30( 0.29)	0.96	42836.3	11620.00
18	33748.21	113.70	0.813	0.30( 0.29)	0.96	45036.0	12400.00
19	32947.18	123.14	0.783	0.30( 0.29)	0.97	48437.6	12201.00
20	32145.25	130.54	0.767	0.30( 0.29)	0.97	50330.6	12231.00
21	31310.01	137.94	0.751	0.30( 0.29)	0.97	51883.3	10400.00
22	29961.21	147.25	0.731	0.30( 0.29)	0.97	53329.8	12010.00
23	29038.33	152.53	0.720	0.30( 0.29)	0.97	53592.3	10210.00
24	28457.00	156.52	0.711	0.30( 0.29)	0.97	53739.1	12000.00
25	25241.95	182.47	0.658	0.30( 0.29)	0.97	54352.1	10100.00

=====

END OF RATIONAL METHOD ANALYSIS



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S33- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 25-YR RM EV APRIL 2019 CCHIUI \*  
\*\*\*\*\*

FILE NAME: RI25EV33.DAT  
TIME/DATE OF STUDY: 09:50 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 25.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 4.829
- 2) 10.00; 3.154
- 3) 15.00; 2.415
- 4) 20.00; 2.000
- 5) 25.00; 1.745
- 6) 30.00; 1.534
- 7) 40.00; 1.333
- 8) 50.00; 1.181
- 9) 60.00; 1.055
- 10) 90.00; 0.886
- 11) 120.00; 0.775
- 12) 180.00; 0.646
- 13) 360.00; 0.475
- 14) 1200.00; 0.208

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL: IN- / OUT-/PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:

- 1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13112.00 TO NODE 13222.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: S31X25.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2430.28	35.90	0.30( 0.24)	0.81	2511.7	13100.00
2	2369.04	61.85	0.30( 0.24)	0.81	3776.9	13000.00
3	2335.36	64.17	0.30( 0.24)	0.81	3796.8	13010.00
TOTAL AREA (ACRES) =						3796.8

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13221.00 TO NODE 13222.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: S32X25.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1123.08	33.84	0.30( 0.25)	0.83	1121.8	13210.00
2	1123.47	34.10	0.30( 0.25)	0.83	1127.6	13200.00
TOTAL AREA (ACRES) =						1127.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13221.00 TO NODE 13222.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1123.08	33.84	0.30( 0.25)	0.83	1121.8	13210.00
2	1123.47	34.10	0.30( 0.25)	0.83	1127.6	13200.00
TOTAL AREA (ACRES) =						1127.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13112.00 TO NODE 13222.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1123.08	33.84	1.457	0.30( 0.25)	0.83	1121.8	13210.00
2	1123.47	34.10	1.452	0.30( 0.25)	0.83	1127.6	13200.00
LONGEST FLOWPATH FROM NODE 13200.00 TO NODE 13222.00 =							16821.05 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2430.28	35.90	1.415	0.30( 0.24)	0.81	2511.7	13100.00
2	2369.04	61.85	1.045	0.30( 0.24)	0.81	3776.9	13000.00
3	2335.36	64.17	1.032	0.30( 0.24)	0.81	3796.8	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13222.00 = 32126.49 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3494.81	33.84	1.457	0.30( 0.24)	0.82	3489.4	13210.00
2	3503.14	34.10	1.452	0.30( 0.24)	0.82	3513.4	13200.00
3	3520.00	35.90	1.415	0.30( 0.24)	0.82	3639.3	13100.00
4	3112.52	61.85	1.045	0.30( 0.24)	0.81	4904.5	13000.00
5	3066.60	64.17	1.032	0.30( 0.24)	0.81	4924.4	13010.00

TOTAL AREA (ACRES) = 4924.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 3520.00 Tc(MIN.) = 35.896

EFFECTIVE AREA(ACRES) = 3639.28 AREA-AVERAGED Fm(INCH/HR) = 0.24

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82

TOTAL AREA (ACRES) = 4924.4

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13222.00 = 32126.49 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13222.00 TO NODE 13222.00 IS CODE = 12

-----

>>>>CLEAR MEMORY BANK # 1 <<<<<

=====

\*\*\*\*\*

FLOW PROCESS FROM NODE 13222.00 TO NODE 13222.00 IS CODE = 12

-----

>>>>CLEAR MEMORY BANK # 2 <<<<<

=====

\*\*\*\*\*

FLOW PROCESS FROM NODE 13222.00 TO NODE 13301.00 IS CODE = 56

-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 427.51 DOWNSTREAM(FEET) = 382.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 2533.33 CHANNEL SLOPE = 0.0180

GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 4.63

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.345

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	1.40	0.30	0.100	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	15.60	0.30	1.000	66
RESIDENTIAL					
"3-4 DWELLINGS/ACRE"	B	0.10	0.30	0.600	56
AGRICULTURAL POOR COVER					

"ROW CROPS, CONTOURED"	B	5.30	0.30	1.000	79
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86
COMMERCIAL	B	22.60	0.30	0.100	56

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.521

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3544.17

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.99

AVERAGE FLOW DEPTH(FEET) = 4.63 TRAVEL TIME(MIN.) = 3.52

Tc(MIN.) = 39.42

SUBAREA AREA(ACRES) = 45.20 SUBAREA RUNOFF(CFS) = 48.34

EFFECTIVE AREA(ACRES) = 3684.48 AREA-AVERAGED Fm(INCH/HR) = 0.24

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81

TOTAL AREA(ACRES) = 4969.6 PEAK FLOW RATE(CFS) = 3651.68

GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 4.71

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 4.71 FLOW VELOCITY(FEET/SEC.) = 12.09

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 39.42

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.345

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	1.00	0.30	1.000	79
NATURAL POOR COVER					
"BARREN"	B	0.50	0.30	1.000	86
COMMERCIAL	B	7.40	0.30	0.100	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	4.70	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	2.90	0.30	1.000	65

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.596

SUBAREA AREA(ACRES) = 16.50 SUBAREA RUNOFF(CFS) = 17.31

EFFECTIVE AREA(ACRES) = 3700.98 AREA-AVERAGED Fm(INCH/HR) = 0.24

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81

TOTAL AREA(ACRES) = 4986.1 PEAK FLOW RATE(CFS) = 3668.99

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 39.42

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.345

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					

NATURAL POOR COVER  
 "BARREN" B 1.30 0.30 1.000 86  
 COMMERCIAL B 0.20 0.30 0.100 56  
 AGRICULTURAL POOR COVER  
 "ROW CROPS,CONTOURED" B 5.30 0.30 1.000 79  
 NATURAL FAIR COVER  
 "WOODLAND,GRASS" B 0.30 0.30 1.000 65  
 NATURAL FAIR COVER  
 "CHAPARRAL,BROADLEAF" B 0.20 0.30 1.000 63  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 0.60 0.30 1.000 66  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.977  
 SUBAREA AREA (ACRES) = 7.90 SUBAREA RUNOFF(CFS) = 7.48  
 EFFECTIVE AREA(ACRES) = 3708.88 AREA-AVERAGED Fm(INCH/HR) = 0.24  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81  
 TOTAL AREA (ACRES) = 4994.0 PEAK FLOW RATE(CFS) = 3676.47

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 39.42  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.345  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	4.30	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.80	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	1.10	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	6.90	0.30	1.000	66
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	7.90	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	1.00	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 22.00 SUBAREA RUNOFF(CFS) = 20.68  
 EFFECTIVE AREA(ACRES) = 3730.88 AREA-AVERAGED Fm(INCH/HR) = 0.24  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81  
 TOTAL AREA (ACRES) = 5016.0 PEAK FLOW RATE(CFS) = 3697.16

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 39.42  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.345  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.50	0.30	1.000	63

"OPEN BRUSH" B 0.40 0.30 1.000 66  
 AGRICULTURAL POOR COVER  
 "ROW CROPS,CONTOURED" B 14.60 0.30 1.000 79  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 15.00 SUBAREA RUNOFF(CFS) = 14.10  
 EFFECTIVE AREA(ACRES) = 3745.88 AREA-AVERAGED Fm(INCH/HR) = 0.24  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81  
 TOTAL AREA (ACRES) = 5031.0 PEAK FLOW RATE(CFS) = 3711.26

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 10  
 -----

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1<<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31100.00 TO NODE 31101.00 IS CODE = 21  
 -----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 317.00  
 ELEVATION DATA: UPSTREAM(FEET) = 801.00 DOWNSTREAM(FEET) = 685.00

Tc = K\*[LENGTH\*\* 3.00]/(ELEVATION CHANGE)]\*\*0.20  
 SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 8.641  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 3.609  
 SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER						
"CHAPARRAL,BROADLEAF"	B	0.50	0.30	1.000	63	8.64
NATURAL FAIR COVER						
"OPEN BRUSH"	B	0.30	0.30	1.000	66	8.64
NATURAL FAIR COVER						
"OPEN BRUSH"	B	0.30	0.30	1.000	66	8.64

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA RUNOFF(CFS) = 3.28  
 TOTAL AREA (ACRES) = 1.10 PEAK FLOW RATE(CFS) = 3.28

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31101.00 TO NODE 31102.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 685.00 DOWNSTREAM(FEET) = 655.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 135.00 CHANNEL SLOPE = 0.2222  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 3.497  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.50	0.30	1.000	63

NATURAL FAIR COVER  
 "OPEN BRUSH" B 0.10 0.30 1.000 66  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 0.70 0.30 1.000 66  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5.15  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.69  
 AVERAGE FLOW DEPTH(FEET) = 0.51 TRAVEL TIME(MIN.) = 0.34  
 Tc(MIN.) = 8.98  
 SUBAREA AREA(ACRES) = 1.30 SUBAREA RUNOFF(CFS) = 3.74  
 EFFECTIVE AREA(ACRES) = 2.40 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 2.4 PEAK FLOW RATE(CFS) = 6.90

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 0.56 FLOW VELOCITY(FEET/SEC.) = 7.29  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31102.00 = 452.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31102.00 TO NODE 31103.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 655.00 DOWNSTREAM(FEET) = 630.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 203.00 CHANNEL SLOPE = 0.1232  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 10.00  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 3.353

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.30	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.10	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.90	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 10.07  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.91  
 AVERAGE FLOW DEPTH(FEET) = 0.65 TRAVEL TIME(MIN.) = 0.43  
 Tc(MIN.) = 9.40  
 SUBAREA AREA(ACRES) = 2.30 SUBAREA RUNOFF(CFS) = 6.32  
 EFFECTIVE AREA(ACRES) = 4.70 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 4.7 PEAK FLOW RATE(CFS) = 12.92

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 0.71 FLOW VELOCITY(FEET/SEC.) = 8.44  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31103.00 = 655.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31103.00 TO NODE 31104.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 630.00 DOWNSTREAM(FEET) = 605.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 321.00 CHANNEL SLOPE = 0.0779  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 3.114

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.10	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.50	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 17.48  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.17  
 AVERAGE FLOW DEPTH(FEET) = 0.97 TRAVEL TIME(MIN.) = 0.87  
 Tc(MIN.) = 10.27  
 SUBAREA AREA(ACRES) = 3.60 SUBAREA RUNOFF(CFS) = 9.12  
 EFFECTIVE AREA(ACRES) = 8.30 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 8.3 PEAK FLOW RATE(CFS) = 21.02

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.04 FLOW VELOCITY(FEET/SEC.) = 6.47  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31104.00 = 976.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31104.00 TO NODE 31105.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 605.00 DOWNSTREAM(FEET) = 585.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 288.00 CHANNEL SLOPE = 0.0694  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 3.008

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.70	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.60	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	3.00	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.10	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 28.82  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.73  
 AVERAGE FLOW DEPTH(FEET) = 1.19 TRAVEL TIME(MIN.) = 0.71  
 Tc(MIN.) = 10.99  
 SUBAREA AREA(ACRES) = 6.40 SUBAREA RUNOFF(CFS) = 15.60

EFFECTIVE AREA(ACRES) = 14.70 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 14.7 PEAK FLOW RATE(CFS) = 35.83

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.30 FLOW VELOCITY(FEET/SEC.) = 7.07  
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31105.00 = 1264.00 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 31105.00 TO NODE 31106.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 585.00 DOWNSTREAM(FEET) = 560.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 344.00 CHANNEL SLOPE = 0.0727  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.900  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.60	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	2.80	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.60	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.10	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.60	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	4.10	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 48.47

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.80

AVERAGE FLOW DEPTH(FEET) = 1.44 TRAVEL TIME(MIN.) = 0.73

Tc(MIN.) = 11.72

SUBAREA AREA(ACRES) = 10.80 SUBAREA RUNOFF(CFS) = 25.27

EFFECTIVE AREA(ACRES) = 25.50 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 25.5 PEAK FLOW RATE(CFS) = 59.66

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.56 FLOW VELOCITY(FEET/SEC.) = 8.18  
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31106.00 = 1608.00 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 31106.00 TO NODE 31107.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 560.00 DOWNSTREAM(FEET) = 530.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 619.00 CHANNEL SLOPE = 0.0485  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.695

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.80	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	1.90	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.50	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	8.20	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.70	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 75.95

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.47

AVERAGE FLOW DEPTH(FEET) = 1.84 TRAVEL TIME(MIN.) = 1.38

Tc(MIN.) = 13.10

SUBAREA AREA(ACRES) = 15.10 SUBAREA RUNOFF(CFS) = 32.55

EFFECTIVE AREA(ACRES) = 40.60 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 40.6 PEAK FLOW RATE(CFS) = 87.53

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.94 FLOW VELOCITY(FEET/SEC.) = 7.75  
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31107.00 = 2227.00 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 31107.00 TO NODE 31108.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 530.00 DOWNSTREAM(FEET) = 515.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 377.00 CHANNEL SLOPE = 0.0398  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.573  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.50	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	6.50	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	1.30	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.10	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	5.50	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	3.40	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 106.25  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.56  
 AVERAGE FLOW DEPTH(FEET) = 2.16 TRAVEL TIME(MIN.) = 0.83  
 Tc(MIN.) = 13.93  
 SUBAREA AREA(ACRES) = 18.30 SUBAREA RUNOFF(CFS) = 37.43  
 EFFECTIVE AREA(ACRES) = 58.90 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 58.9 PEAK FLOW RATE(CFS) = 120.47

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 2.27 FLOW VELOCITY(FEET/SEC.) = 7.79  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31108.00 = 2604.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31108.00 TO NODE 31109.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 515.00 DOWNSTREAM(FEET) = 490.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 520.00 CHANNEL SLOPE = 0.0481  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.424

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.70	0.30	1.000	63
NATURAL FAIR COVER					
"GRASS"	B	2.20	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	3.10	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.90	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	7.40	0.30	1.000	63
NATURAL FAIR COVER					
"GRASS"	B	0.30	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 134.43  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.59  
 AVERAGE FLOW DEPTH(FEET) = 2.28 TRAVEL TIME(MIN.) = 1.01  
 Tc(MIN.) = 14.94  
 SUBAREA AREA(ACRES) = 14.60 SUBAREA RUNOFF(CFS) = 27.90  
 EFFECTIVE AREA(ACRES) = 73.50 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 73.5 PEAK FLOW RATE(CFS) = 140.47

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 2.32 FLOW VELOCITY(FEET/SEC.) = 8.68  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31109.00 = 3124.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31109.00 TO NODE 31109.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

\*\*\*\*\*  
 MAINLINE Tc(MIN.) = 14.94  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.424

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	11.40	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	8.90	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	1.90	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	9.20	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	1.40	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 32.80 SUBAREA RUNOFF(CFS) = 62.69  
 EFFECTIVE AREA(ACRES) = 106.30 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 106.3 PEAK FLOW RATE(CFS) = 203.16

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31109.00 TO NODE 31110.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 490.00 DOWNSTREAM(FEET) = 432.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1420.00 CHANNEL SLOPE = 0.0408  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.203

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	0.80	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.60	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.10	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	1.30	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	4.00	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	1.50	0.30	1.000	63

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 210.27  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.06  
 AVERAGE FLOW DEPTH(FEET) = 2.78 TRAVEL TIME(MIN.) = 2.61  
 Tc(MIN.) = 17.56  
 SUBAREA AREA(ACRES) = 8.30 SUBAREA RUNOFF(CFS) = 14.22  
 EFFECTIVE AREA(ACRES) = 114.60 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00



TOTAL AREA (ACRES) = 114.6 PEAK FLOW RATE (CFS) = 203.16  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 2.75 FLOW VELOCITY (FEET/SEC.) = 8.96  
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31110.00 = 4544.00 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 31110.00 TO NODE 31110.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 17.56  
\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 2.203  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	0.30	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	9.60	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.40	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	6.20	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	3.90	0.30	1.000	65
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	1.40	0.30	1.000	79

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.998  
SUBAREA AREA (ACRES) = 21.80 SUBAREA RUNOFF (CFS) = 37.35  
EFFECTIVE AREA (ACRES) = 136.40 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA (ACRES) = 136.4 PEAK FLOW RATE (CFS) = 233.61

\*\*\*\*\*  
FLOW PROCESS FROM NODE 31110.00 TO NODE 13301.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

ELEVATION DATA: UPSTREAM (FEET) = 432.00 DOWNSTREAM (FEET) = 382.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1847.00 CHANNEL SLOPE = 0.0271  
CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 10.00  
\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.930  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	4.90	0.30	1.000	86
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	1.50	0.30	1.000	79
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.60	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	2.50	0.30	1.000	79

AGRICULTURAL POOR COVER  
"ROW CROPS, CONTOURED" B 5.30 0.30 1.000 79  
AGRICULTURAL POOR COVER  
"ROW CROPS, CONTOURED" B 3.30 0.30 1.000 79  
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.997  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 246.90  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.07  
AVERAGE FLOW DEPTH (FEET) = 3.19 TRAVEL TIME (MIN.) = 3.82  
Tc (MIN.) = 21.37  
SUBAREA AREA (ACRES) = 18.10 SUBAREA RUNOFF (CFS) = 26.57  
EFFECTIVE AREA (ACRES) = 154.50 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA (ACRES) = 154.5 PEAK FLOW RATE (CFS) = 233.61  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 3.13 FLOW VELOCITY (FEET/SEC.) = 7.94  
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 13301.00 = 6391.00 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	233.61	21.37	1.930	0.30 ( 0.30)	1.00	154.5	31100.00

LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 13301.00 = 6391.00 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3695.91	37.37	1.386	0.30 ( 0.24)	0.81	3596.0	13210.00
2	3703.77	37.63	1.381	0.30 ( 0.24)	0.81	3620.0	13200.00
3	3711.26	39.42	1.345	0.30 ( 0.24)	0.81	3745.9	13100.00
4	3521.51	65.51	1.024	0.30 ( 0.24)	0.81	5011.1	13000.00
5	3475.89	67.86	1.011	0.30 ( 0.24)	0.81	5031.0	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3354.49	21.37	1.930	0.30 ( 0.25)	0.83	2211.0	31100.00
2	3851.54	37.37	1.386	0.30 ( 0.25)	0.82	3750.5	13210.00
3	3858.66	37.63	1.381	0.30 ( 0.25)	0.82	3774.5	13200.00
4	3860.99	39.42	1.345	0.30 ( 0.25)	0.82	3900.4	13100.00
5	3625.28	65.51	1.024	0.30 ( 0.24)	0.82	5165.6	13000.00
6	3577.77	67.86	1.011	0.30 ( 0.24)	0.82	5185.5	13010.00

TOTAL AREA (ACRES) = 5185.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:  
PEAK FLOW RATE (CFS) = 3860.99 Tc (MIN.) = 39.418  
EFFECTIVE AREA (ACRES) = 3900.38 AREA-AVERAGED Fm (INCH/HR) = 0.25  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82  
TOTAL AREA (ACRES) = 5185.5

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13302.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 382.00 DOWNSTREAM(FEET) = 375.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 1141.09 CHANNEL SLOPE = 0.0061

GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.54

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.308

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	9.40	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3865.25

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.49

AVERAGE FLOW DEPTH(FEET) = 6.54 TRAVEL TIME(MIN.) = 2.24

Tc(MIN.) = 41.66

SUBAREA AREA(ACRES) = 9.40 SUBAREA RUNOFF(CFS) = 8.53

EFFECTIVE AREA(ACRES) = 3909.78 AREA-AVERAGED Fm(INCH/HR) = 0.25

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82

TOTAL AREA(ACRES) = 5194.9 PEAK FLOW RATE(CFS) = 3860.99

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.54

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 6.54 FLOW VELOCITY(FEET/SEC.) = 8.49

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13302.00 = 35800.91 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 41.66

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.308

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	13.80	0.30	1.000	86
NATURAL POOR COVER					
"BARREN"	B	2.60	0.30	1.000	86

COMMERCIAL	B	1.10	0.30	0.100	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	3.50	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	6.90	0.30	1.000	79
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.952

SUBAREA AREA(ACRES) = 28.10 SUBAREA RUNOFF(CFS) = 25.85

EFFECTIVE AREA(ACRES) = 3937.88 AREA-AVERAGED Fm(INCH/HR) = 0.25

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82

TOTAL AREA(ACRES) = 5223.0 PEAK FLOW RATE(CFS) = 3860.99

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 41.66

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.308

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	0.10	0.30	1.000	79
COMMERCIAL	B	0.10	0.30	0.100	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	2.40	0.30	0.900	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.894

SUBAREA AREA(ACRES) = 3.10 SUBAREA RUNOFF(CFS) = 2.90

EFFECTIVE AREA(ACRES) = 3940.98 AREA-AVERAGED Fm(INCH/HR) = 0.25

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82

TOTAL AREA(ACRES) = 5226.1 PEAK FLOW RATE(CFS) = 3860.99

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 41.66

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.308

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	0.10	0.30	1.000	86
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.60	0.30	1.000	66
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	3.10	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.40	0.30	1.000	65

NATURAL FAIR COVER  
 "CHAPARRAL,BROADLEAF" B 0.20 0.30 1.000 63  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 13.80 0.30 1.000 66  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 20.20 SUBAREA RUNOFF(CFS) = 18.32  
 EFFECTIVE AREA(ACRES) = 3961.18 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82  
 TOTAL AREA(ACRES) = 5246.3 PEAK FLOW RATE(CFS) = 3860.99  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 41.66  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.308  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	34.60	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	2.40	0.30	1.000	65
NATURAL FAIR COVER					
"OPEN BRUSH"	B	22.60	0.30	1.000	66
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	11.60	0.30	1.000	79
APARTMENTS	B	0.40	0.30	0.200	56
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	4.80	0.30	1.000	63
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.996					
SUBAREA AREA(ACRES) = 76.40 SUBAREA RUNOFF(CFS) = 69.38					
EFFECTIVE AREA(ACRES) = 4037.58 AREA-AVERAGED Fm(INCH/HR) = 0.25					
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83					
TOTAL AREA(ACRES) = 5322.7 PEAK FLOW RATE(CFS) = 3860.99					
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE					

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 41.66  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.308  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	1.60	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	46.40	0.30	1.000	66
RESIDENTIAL					
"11+ DWELLINGS/ACRE"	B	0.10	0.30	0.200	56
AGRICULTURAL POOR COVER					

"ROW CROPS,CONTOURED" B 60.70 0.30 1.000 79  
 NATURAL FAIR COVER  
 "WOODLAND,GRASS" B 5.80 0.30 1.000 65  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999  
 SUBAREA AREA(ACRES) = 114.60 SUBAREA RUNOFF(CFS) = 103.96  
 EFFECTIVE AREA(ACRES) = 4152.18 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA(ACRES) = 5437.3 PEAK FLOW RATE(CFS) = 3955.93

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13302.00 TO NODE 13303.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 375.00 DOWNSTREAM(FEET) = 355.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2193.96 CHANNEL SLOPE = 0.0091  
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 5.94  
 CHANNEL FLOW THRU SUBAREA(CFS) = 3955.93  
 FLOW VELOCITY(FEET/SEC.) = 9.82 FLOW DEPTH(FEET) = 5.94  
 TRAVEL TIME(MIN.) = 3.72 Tc(MIN.) = 45.38  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13303.00 = 37994.87 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 45.38  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.251  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.40	0.30	1.000	65
NATURAL POOR COVER					
"BARREN"	B	0.80	0.30	1.000	86
COMMERCIAL	B	1.40	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	2.60	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.20	0.30	1.000	66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.834					
SUBAREA AREA(ACRES) = 7.60 SUBAREA RUNOFF(CFS) = 6.85					
EFFECTIVE AREA(ACRES) = 4159.78 AREA-AVERAGED Fm(INCH/HR) = 0.25					
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83					
TOTAL AREA(ACRES) = 5444.9 PEAK FLOW RATE(CFS) = 3955.93					
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE					

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

```

=====
MAINLINE Tc(MIN.) = 45.38
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.251
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS
LAND USE            GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
AGRICULTURAL POOR COVER
"ROW CROPS,CONTOURED"   B       3.10   0.30   1.000   79
NATURAL FAIR COVER
"WOODLAND,GRASS"       B       3.40   0.30   1.000   65
NATURAL POOR COVER
"BARREN"                B       0.50   0.30   1.000   86
NATURAL FAIR COVER
"CHAPARRAL,BROADLEAF"   B       0.20   0.30   1.000   63
COMMERCIAL              B       3.60   0.30   0.100   56
NATURAL FAIR COVER
"GRASS"                 B       4.00   0.30   1.000   69
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.781
SUBAREA AREA(ACRES) = 14.80      SUBAREA RUNOFF(CFS) = 13.54
EFFECTIVE AREA(ACRES) = 4174.58  AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30  AREA-AVERAGED Ap = 0.83
TOTAL AREA(ACRES) = 5459.7      PEAK FLOW RATE(CFS) = 3955.93
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81
-----

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

```

=====
MAINLINE Tc(MIN.) = 45.38
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.251
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS
LAND USE            GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"OPEN BRUSH"           B      14.60   0.30   1.000   66
AGRICULTURAL POOR COVER
"ROW CROPS,CONTOURED"   B       6.30   0.30   1.000   79
NATURAL FAIR COVER
"WOODLAND,GRASS"       B       3.70   0.30   1.000   65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 24.60      SUBAREA RUNOFF(CFS) = 21.06
EFFECTIVE AREA(ACRES) = 4199.18  AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30  AREA-AVERAGED Ap = 0.83
TOTAL AREA(ACRES) = 5484.3      PEAK FLOW RATE(CFS) = 3955.93
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81
-----

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

```

=====
MAINLINE Tc(MIN.) = 45.38
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.251
SUBAREA LOSS RATE DATA(AMC II):

```

```

DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS
LAND USE            GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL POOR COVER
"BARREN"             B       0.50   0.30   1.000   86
COMMERCIAL           B       0.30   0.30   0.100   56
NATURAL FAIR COVER
"OPEN BRUSH"        B       0.20   0.30   1.000   66
RESIDENTIAL
".4 DWELLING/ACRE"   B       0.80   0.30   0.900   56
AGRICULTURAL POOR COVER
"ROW CROPS,CONTOURED" B       1.60   0.30   1.000   79
NATURAL POOR COVER
"BARREN"            B      31.90   0.30   1.000   86
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.990
SUBAREA AREA(ACRES) = 35.30      SUBAREA RUNOFF(CFS) = 30.31
EFFECTIVE AREA(ACRES) = 4234.48  AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30  AREA-AVERAGED Ap = 0.83
TOTAL AREA(ACRES) = 5519.6      PEAK FLOW RATE(CFS) = 3955.93
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81
-----

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

```

=====
MAINLINE Tc(MIN.) = 45.38
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.251
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS
LAND USE            GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
COMMERCIAL           B       1.70   0.30   0.100   56
NATURAL FAIR COVER
"OPEN BRUSH"        B       0.30   0.30   1.000   66
RESIDENTIAL
".4 DWELLING/ACRE"   B       2.60   0.30   0.900   56
AGRICULTURAL POOR COVER
"ROW CROPS,CONTOURED" B       5.50   0.30   1.000   79
NATURAL FAIR COVER
"WOODLAND,GRASS"     B       0.20   0.30   1.000   65
NATURAL FAIR COVER
"OPEN BRUSH"        B       0.20   0.30   1.000   66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.830
SUBAREA AREA(ACRES) = 10.50      SUBAREA RUNOFF(CFS) = 9.47
EFFECTIVE AREA(ACRES) = 4244.98  AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30  AREA-AVERAGED Ap = 0.83
TOTAL AREA(ACRES) = 5530.1      PEAK FLOW RATE(CFS) = 3955.93
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81
-----

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

```

=====
MAINLINE Tc(MIN.) = 45.38
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.251
SUBAREA LOSS RATE DATA(AMC II):

```

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL ".4 DWELLING/ACRE"	B	1.30	0.30	0.900	56
NATURAL POOR COVER "BARREN"	B	0.30	0.30	1.000	86
COMMERCIAL NATURAL FAIR COVER "OPEN BRUSH"	B	0.20	0.30	0.100	56
RESIDENTIAL ".4 DWELLING/ACRE"	B	0.30	0.30	1.000	66
AGRICULTURAL POOR COVER "ROW CROPS, CONTOURED"	B	6.50	0.30	0.900	56
B	3.00	0.30	1.000	79	

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.917  
SUBAREA AREA (ACRES) = 11.60 SUBAREA RUNOFF (CFS) = 10.19  
EFFECTIVE AREA (ACRES) = 4256.58 AREA-AVERAGED Fm (INCH/HR) = 0.25  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
TOTAL AREA (ACRES) = 5541.7 PEAK FLOW RATE (CFS) = 3955.93  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13303.00 TO NODE 13304.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

-----  
ELEVATION DATA: UPSTREAM (FEET) = 355.00 DOWNSTREAM (FEET) = 350.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 925.40 CHANNEL SLOPE = 0.0054  
GIVEN CHANNEL BASE (FEET) = 50.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 6.86  
\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.223  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	13.80	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.850  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 3961.93  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.18  
AVERAGE FLOW DEPTH (FEET) = 6.86 TRAVEL TIME (MIN.) = 1.89  
Tc (MIN.) = 47.27  
SUBAREA AREA (ACRES) = 13.80 SUBAREA RUNOFF (CFS) = 12.02  
EFFECTIVE AREA (ACRES) = 4270.38 AREA-AVERAGED Fm (INCH/HR) = 0.25  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
TOTAL AREA (ACRES) = 5555.5 PEAK FLOW RATE (CFS) = 3955.93  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
GIVEN CHANNEL BASE (FEET) = 50.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 6.86

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 6.86 FLOW VELOCITY (FEET/SEC.) = 8.18  
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13304.00 = 38920.27 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81  
-----

-----  
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
-----

MAINLINE Tc (MIN.) = 47.27  
\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.223  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER "BARREN"	B	7.80	0.30	1.000	86
AGRICULTURAL POOR COVER "ROW CROPS, CONTOURED"	B	1.70	0.30	1.000	79
NATURAL POOR COVER "BARREN"	B	9.40	0.30	1.000	86
NATURAL FAIR COVER "OPEN BRUSH"	B	1.20	0.30	1.000	66
RESIDENTIAL ".4 DWELLING/ACRE"	B	0.10	0.30	0.900	56
AGRICULTURAL POOR COVER "ROW CROPS, CONTOURED"	B	2.60	0.30	1.000	79

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 22.80 SUBAREA RUNOFF (CFS) = 18.93  
EFFECTIVE AREA (ACRES) = 4293.18 AREA-AVERAGED Fm (INCH/HR) = 0.25  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
TOTAL AREA (ACRES) = 5578.3 PEAK FLOW RATE (CFS) = 3955.93  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
-----

MAINLINE Tc (MIN.) = 47.27  
\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.223  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.20	0.30	1.000	65
NATURAL FAIR COVER "OPEN BRUSH"	B	0.30	0.30	1.000	66
RESIDENTIAL ".4 DWELLING/ACRE"	B	0.20	0.30	0.900	56
AGRICULTURAL POOR COVER "ROW CROPS, CONTOURED"	B	2.70	0.30	1.000	79

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.994  
SUBAREA AREA (ACRES) = 3.40 SUBAREA RUNOFF (CFS) = 2.83  
EFFECTIVE AREA (ACRES) = 4296.58 AREA-AVERAGED Fm (INCH/HR) = 0.25  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
TOTAL AREA (ACRES) = 5581.7 PEAK FLOW RATE (CFS) = 3955.93  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13304.00 TO NODE 13305.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 350.00 DOWNSTREAM(FEET) = 315.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2966.27 CHANNEL SLOPE = 0.0118  
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 5.54  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.157

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	27.40	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3966.50  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.74  
 AVERAGE FLOW DEPTH(FEET) = 5.54 TRAVEL TIME(MIN.) = 4.60  
 Tc(MIN.) = 51.87  
 SUBAREA AREA(ACRES) = 27.40 SUBAREA RUNOFF(CFS) = 21.14  
 EFFECTIVE AREA(ACRES) = 4323.98 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84  
 TOTAL AREA(ACRES) = 5609.1 PEAK FLOW RATE(CFS) = 3955.93  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 5.53

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 5.53 FLOW VELOCITY(FEET/SEC.) = 10.73  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 51.87  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.157

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	18.40	0.30	1.000	86
NATURAL FAIR COVER					
"MEADOWS"	B	1.20	0.30	1.000	70
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.10	0.30	1.000	65
NATURAL POOR COVER					
"BARREN"	B	26.60	0.30	1.000	86
COMMERCIAL	B	3.90	0.30	0.100	56
AGRICULTURAL POOR COVER					
"FALLOW"	B	3.00	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.934  
 SUBAREA AREA(ACRES) = 53.20 SUBAREA RUNOFF(CFS) = 42.00  
 EFFECTIVE AREA(ACRES) = 4377.18 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84

TOTAL AREA(ACRES) = 5662.3 PEAK FLOW RATE(CFS) = 3955.93  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 51.87  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.157

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	1.10	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.20	0.30	1.000	65
NATURAL POOR COVER					
"BARREN"	B	14.00	0.30	1.000	86
COMMERCIAL	B	4.30	0.30	0.100	56
AGRICULTURAL POOR COVER					
"FALLOW"	B	5.30	0.30	1.000	86
NATURAL FAIR COVER					
"GRASS"	B	2.70	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.860  
 SUBAREA AREA(ACRES) = 27.60 SUBAREA RUNOFF(CFS) = 22.34  
 EFFECTIVE AREA(ACRES) = 4404.78 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84  
 TOTAL AREA(ACRES) = 5689.9 PEAK FLOW RATE(CFS) = 3955.93  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 51.87  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.157

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"MEADOWS"	B	3.20	0.30	1.000	70
NATURAL FAIR COVER					
"OPEN BRUSH"	B	6.10	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	7.50	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	5.40	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	1.60	0.30	1.000	65
NATURAL POOR COVER					
"BARREN"	B	1.90	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.971  
 SUBAREA AREA(ACRES) = 25.70 SUBAREA RUNOFF(CFS) = 20.03  
 EFFECTIVE AREA(ACRES) = 4430.48 AREA-AVERAGED Fm(INCH/HR) = 0.25

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84  
 TOTAL AREA (ACRES) = 5715.6 PEAK FLOW RATE (CFS) = 3955.93  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

\*\*\*\*\*  
 MAINLINE Tc (MIN.) = 51.87  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.157  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 COMMERCIAL B 2.00 0.30 0.100 56  
 AGRICULTURAL POOR COVER  
 "FALLOW" B 3.70 0.30 1.000 86  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 2.10 0.30 1.000 66  
 RESIDENTIAL  
 ".4 DWELLING/ACRE" B 2.60 0.30 0.900 56  
 AGRICULTURAL POOR COVER  
 "ROW CROPS, CONTOURED" B 0.20 0.30 1.000 79  
 NATURAL FAIR COVER  
 "WOODLAND, GRASS" B 0.10 0.30 1.000 65  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.807  
 SUBAREA AREA (ACRES) = 10.70 SUBAREA RUNOFF (CFS) = 8.81  
 EFFECTIVE AREA (ACRES) = 4441.18 AREA-AVERAGED Fm (INCH/HR) = 0.25  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84  
 TOTAL AREA (ACRES) = 5726.3 PEAK FLOW RATE (CFS) = 3955.93  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

\*\*\*\*\*  
 MAINLINE Tc (MIN.) = 51.87  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.157  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 0.50 0.30 1.000 66  
 RESIDENTIAL  
 ".4 DWELLING/ACRE" B 8.20 0.30 0.900 56  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.906  
 SUBAREA AREA (ACRES) = 8.70 SUBAREA RUNOFF (CFS) = 6.94  
 EFFECTIVE AREA (ACRES) = 4449.88 AREA-AVERAGED Fm (INCH/HR) = 0.25  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84  
 TOTAL AREA (ACRES) = 5735.0 PEAK FLOW RATE (CFS) = 3955.93  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 3A25EVRL.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	985.27	13.67	0.30 ( 0.13)	0.43	435.6	120.00
2	984.49	13.73	0.30 ( 0.13)	0.43	436.6	110.00
3	831.39	20.84	0.30 ( 0.13)	0.43	504.3	100.00
4	778.32	23.57	0.30 ( 0.13)	0.43	510.2	150.00
TOTAL AREA (ACRES) =						510.2

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3453.21	34.36	1.446	0.30 ( 0.26)	0.85	2760.5	31100.00
2	3931.18	49.85	1.183	0.30 ( 0.25)	0.84	4300.0	13210.00
3	3936.42	50.09	1.180	0.30 ( 0.25)	0.84	4324.0	13200.00
4	3955.93	51.87	1.157	0.30 ( 0.25)	0.84	4449.9	13100.00
5	3724.08	78.20	0.952	0.30 ( 0.25)	0.83	5715.1	13000.00
6	3673.15	80.60	0.939	0.30 ( 0.25)	0.83	5735.0	13010.00
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 =							41886.54 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	985.27	13.67	2.612	0.30 ( 0.13)	0.43	435.6	120.00
2	984.49	13.73	2.603	0.30 ( 0.13)	0.43	436.6	110.00
3	831.39	20.84	1.957	0.30 ( 0.13)	0.43	504.3	100.00
4	778.32	23.57	1.818	0.30 ( 0.13)	0.43	510.2	150.00
LONGEST FLOWPATH FROM NODE 150.00 TO NODE 13305.00 =							9867.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3703.69	13.67	2.612	0.30 ( 0.22)	0.73	1533.9	120.00
2	3704.53	13.73	2.603	0.30 ( 0.22)	0.73	1539.7	110.00
3	3824.44	20.84	1.957	0.30 ( 0.23)	0.75	2178.7	100.00
4	3886.34	23.57	1.818	0.30 ( 0.23)	0.76	2403.7	150.00
5	4060.15	34.36	1.446	0.30 ( 0.24)	0.79	3270.7	31100.00
6	4416.80	49.85	1.183	0.30 ( 0.24)	0.80	4810.2	13210.00
7	4420.44	50.09	1.180	0.30 ( 0.24)	0.80	4834.2	13200.00
8	4429.62	51.87	1.157	0.30 ( 0.24)	0.80	4960.1	13100.00
9	4103.28	78.20	0.952	0.30 ( 0.24)	0.80	6225.3	13000.00
10	4046.11	80.60	0.939	0.30 ( 0.24)	0.80	6245.2	13010.00
TOTAL AREA (ACRES) =						6245.2	

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 4429.62 Tc (MIN.) = 51.871  
 EFFECTIVE AREA (ACRES) = 4960.08 AREA-AVERAGED Fm (INCH/HR) = 0.24  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.76  
 TOTAL AREA (ACRES) = 6245.2

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 13305.00 TO NODE 13306.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 315.00 DOWNSTREAM(FEET) = 245.50

CHANNEL LENGTH THRU SUBAREA(FEET) = 4408.41 CHANNEL SLOPE = 0.0158

GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 5.46

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.082

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	68.80	0.30	0.850	56

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.850

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 4455.23

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.30

AVERAGE FLOW DEPTH(FEET) = 5.46 TRAVEL TIME(MIN.) = 5.97

Tc(MIN.) = 57.84

SUBAREA AREA(ACRES) = 68.80 SUBAREA RUNOFF(CFS) = 51.22

EFFECTIVE AREA(ACRES) = 5028.88 AREA-AVERAGED Fm(INCH/HR) = 0.24

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80

TOTAL AREA(ACRES) = 6314.0 PEAK FLOW RATE(CFS) = 4429.62

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 5.44

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 5.44 FLOW VELOCITY(FEET/SEC.) = 12.29

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13306.00 = 46294.95 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 57.84

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.082

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	21.50	0.30	1.000	86
COMMERCIAL	B	15.30	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	0.80	0.30	1.000	69

NATURAL POOR COVER

"BARREN" B 21.50 0.30 1.000 86

COMMERCIAL B 15.30 0.30 0.100 56

NATURAL FAIR COVER

"GRASS" B 0.80 0.30 1.000 69

AGRICULTURAL FAIR COVER

"ORCHARDS" B 0.60 0.30 1.000 65

RESIDENTIAL

".4 DWELLING/ACRE" B 8.00 0.30 0.900 56

NATURAL FAIR COVER

"WOODLAND,GRASS" B 0.10 0.30 1.000 65

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.685

SUBAREA AREA(ACRES) = 46.30 SUBAREA RUNOFF(CFS) = 36.53

EFFECTIVE AREA(ACRES) = 5075.18 AREA-AVERAGED Fm(INCH/HR) = 0.24

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80

TOTAL AREA(ACRES) = 6360.3 PEAK FLOW RATE(CFS) = 4429.62

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 57.84

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.082

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	43.30	0.30	1.000	86
COMMERCIAL	B	4.90	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	5.70	0.30	1.000	69
AGRICULTURAL FAIR COVER					
"ORCHARDS"	B	0.50	0.30	1.000	65
PUBLIC PARK	B	1.10	0.30	0.850	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	3.10	0.30	0.900	56

NATURAL POOR COVER

"BARREN" B 43.30 0.30 1.000 86

COMMERCIAL B 4.90 0.30 0.100 56

NATURAL FAIR COVER

"GRASS" B 5.70 0.30 1.000 69

AGRICULTURAL FAIR COVER

"ORCHARDS" B 0.50 0.30 1.000 65

PUBLIC PARK B 1.10 0.30 0.850 56

RESIDENTIAL

".4 DWELLING/ACRE" B 3.10 0.30 0.900 56

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.917

SUBAREA AREA(ACRES) = 58.60 SUBAREA RUNOFF(CFS) = 42.57

EFFECTIVE AREA(ACRES) = 5133.78 AREA-AVERAGED Fm(INCH/HR) = 0.24

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80

TOTAL AREA(ACRES) = 6418.9 PEAK FLOW RATE(CFS) = 4429.62

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 57.84

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.082

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	6.80	0.30	1.000	65
NATURAL POOR COVER					
"BARREN"	B	0.70	0.30	1.000	86
COMMERCIAL	B	1.10	0.30	0.100	56
NATURAL FAIR COVER					

NATURAL FAIR COVER

"WOODLAND,GRASS" B 6.80 0.30 1.000 65

NATURAL POOR COVER

"BARREN" B 0.70 0.30 1.000 86

COMMERCIAL B 1.10 0.30 0.100 56

NATURAL FAIR COVER



"GRASS"	B	0.50	0.30	1.000	69
AGRICULTURAL FAIR COVER					
"ORCHARDS"	B	0.10	0.30	1.000	65
PUBLIC PARK	B	0.50	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.890  
SUBAREA AREA(ACRES) = 9.70 SUBAREA RUNOFF(CFS) = 7.12  
EFFECTIVE AREA(ACRES) = 5143.48 AREA-AVERAGED Fm(INCH/HR) = 0.24  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80  
TOTAL AREA(ACRES) = 6428.6 PEAK FLOW RATE(CFS) = 4429.62  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 57.84  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.082  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL					
".4 DWELLING/ACRE"	B	2.20	0.30	0.900	56
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.10	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.904  
SUBAREA AREA(ACRES) = 2.30 SUBAREA RUNOFF(CFS) = 1.68  
EFFECTIVE AREA(ACRES) = 5145.78 AREA-AVERAGED Fm(INCH/HR) = 0.24  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80  
TOTAL AREA(ACRES) = 6430.9 PEAK FLOW RATE(CFS) = 4429.62  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13306.00 TO NODE 13307.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 245.50 DOWNSTREAM(FEET) = 220.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1543.21 CHANNEL SLOPE = 0.0165  
GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 5.37  
CHANNEL FLOW THRU SUBAREA(CFS) = 4429.62  
FLOW VELOCITY(FEET/SEC.) = 12.48 FLOW DEPTH(FEET) = 5.37  
TRAVEL TIME(MIN.) = 2.06 Tc(MIN.) = 59.91  
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13307.00 = 47838.16 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13307.00 TO NODE 13307.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 59.91  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.056  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	0.20	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	0.10	0.30	1.000	69
AGRICULTURAL FAIR COVER					
"ORCHARDS"	B	0.20	0.30	1.000	65
NATURAL POOR COVER					
"BARREN"	B	3.70	0.30	1.000	86
COMMERCIAL	B	0.30	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	3.20	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.942  
SUBAREA AREA(ACRES) = 7.70 SUBAREA RUNOFF(CFS) = 5.36  
EFFECTIVE AREA(ACRES) = 5153.48 AREA-AVERAGED Fm(INCH/HR) = 0.24  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80  
TOTAL AREA(ACRES) = 6438.6 PEAK FLOW RATE(CFS) = 4429.62  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13307.00 TO NODE 13307.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 59.91  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.056  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	3.60	0.30	1.000	65
NATURAL FAIR COVER					
"GRASS"	B	1.90	0.30	1.000	69
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.60	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA(ACRES) = 6.10 SUBAREA RUNOFF(CFS) = 4.15  
EFFECTIVE AREA(ACRES) = 5159.58 AREA-AVERAGED Fm(INCH/HR) = 0.24  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80  
TOTAL AREA(ACRES) = 6444.7 PEAK FLOW RATE(CFS) = 4429.62  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13307.00 TO NODE 13308.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 220.00 DOWNSTREAM(FEET) = 212.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 925.62 CHANNEL SLOPE = 0.0086  
GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.41  
CHANNEL FLOW THRU SUBAREA(CFS) = 4429.62  
FLOW VELOCITY(FEET/SEC.) = 9.98 FLOW DEPTH(FEET) = 6.41  
TRAVEL TIME(MIN.) = 1.55 Tc(MIN.) = 61.45

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13308.00 = 48763.78 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 61.45  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.047  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	0.10	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.20	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	5.00	0.30	1.000	65
COMMERCIAL	B	3.20	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	0.10	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.90	0.30	1.000	66

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.697  
 SUBAREA AREA(ACRES) = 9.50 SUBAREA RUNOFF(CFS) = 7.16  
 EFFECTIVE AREA(ACRES) = 5169.08 AREA-AVERAGED Fm(INCH/HR) = 0.24  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80  
 TOTAL AREA(ACRES) = 6454.2 PEAK FLOW RATE(CFS) = 4429.62  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 61.45  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.047  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
APARTMENTS	B	0.30	0.30	0.200	56
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	1.00	0.30	1.000	63
COMMERCIAL	B	41.90	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	7.20	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	25.00	0.30	1.000	66

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.498  
 SUBAREA AREA(ACRES) = 75.60 SUBAREA RUNOFF(CFS) = 61.06  
 EFFECTIVE AREA(ACRES) = 5244.68 AREA-AVERAGED Fm(INCH/HR) = 0.24  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA(ACRES) = 6529.8 PEAK FLOW RATE(CFS) = 4429.62  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 61.45  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.047  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	0.10	0.30	0.850	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	0.90	0.30	1.000	79
SCHOOL	B	0.30	0.30	0.600	56
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	13.20	0.30	1.000	65
APARTMENTS	B	0.50	0.30	0.200	56
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.60	0.30	1.000	63

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.966  
 SUBAREA AREA(ACRES) = 15.60 SUBAREA RUNOFF(CFS) = 10.63  
 EFFECTIVE AREA(ACRES) = 5260.28 AREA-AVERAGED Fm(INCH/HR) = 0.24  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA(ACRES) = 6545.4 PEAK FLOW RATE(CFS) = 4429.62  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 61.45  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.047  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	33.90	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	17.60	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	16.80	0.30	1.000	66
RESIDENTIAL					
"11+ DWELLINGS/ACRE"	B	0.60	0.30	0.200	56
RESIDENTIAL					
"8-10 DWELLINGS/ACRE"	B	1.50	0.30	0.400	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	10.00	0.30	1.000	79

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.603  
 SUBAREA AREA(ACRES) = 80.40 SUBAREA RUNOFF(CFS) = 62.65  
 EFFECTIVE AREA(ACRES) = 5340.68 AREA-AVERAGED Fm(INCH/HR) = 0.24  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA(ACRES) = 6625.8 PEAK FLOW RATE(CFS) = 4429.62  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 61.45  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.047  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
SCHOOL	B	0.30	0.30	0.600	56
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.70	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.880  
 SUBAREA AREA(ACRES) = 1.00 SUBAREA RUNOFF(CFS) = 0.70  
 EFFECTIVE AREA(ACRES) = 5341.68 AREA-AVERAGED Fm(INCH/HR) = 0.24  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA(ACRES) = 6626.8 PEAK FLOW RATE(CFS) = 4429.62  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 61.45  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.047  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "GRASS"	B	0.30	0.30	1.000	69
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.80	0.30	1.000	65
NATURAL FAIR COVER "GRASS"	B	0.50	0.30	1.000	69
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.20	0.30	1.000	65
NATURAL FAIR COVER "GRASS"	B	0.30	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 2.10 SUBAREA RUNOFF(CFS) = 1.41  
 EFFECTIVE AREA(ACRES) = 5343.78 AREA-AVERAGED Fm(INCH/HR) = 0.24  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA(ACRES) = 6628.9 PEAK FLOW RATE(CFS) = 4429.62  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 61.45  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.047  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL FAIR COVER  
 "GRASS" B 1.20 0.30 1.000 69  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 0.50 0.30 1.000 66  
 PUBLIC PARK B 1.70 0.30 0.850 56  
 NATURAL FAIR COVER  
 "WOODLAND,GRASS" B 7.20 0.30 1.000 65  
 NATURAL FAIR COVER  
 "GRASS" B 1.00 0.30 1.000 69  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.978  
 SUBAREA AREA(ACRES) = 11.60 SUBAREA RUNOFF(CFS) = 7.87  
 EFFECTIVE AREA(ACRES) = 5355.38 AREA-AVERAGED Fm(INCH/HR) = 0.24  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA(ACRES) = 6640.5 PEAK FLOW RATE(CFS) = 4429.62  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<

\*\*\*\*\*

PEAK FLOWRATE TABLE FILE NAME: RI25EV29.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20095.98	19.05	0.30( 0.25)	0.83	4136.6	50400.00
2	22793.37	28.89	0.30( 0.25)	0.85	6798.8	50300.00
3	25164.78	41.32	0.30( 0.26)	0.87	10690.4	40200.00
4	25575.61	45.10	0.30( 0.27)	0.88	12106.9	390.00
5	26723.63	55.33	0.30( 0.27)	0.91	15884.7	40100.00
6	28396.10	64.64	0.30( 0.28)	0.93	19187.0	11801.00
7	30588.65	75.44	0.30( 0.28)	0.94	23716.7	11530.00
8	31818.04	84.12	0.30( 0.28)	0.95	28348.8	11910.00
9	33802.26	94.19	0.30( 0.29)	0.96	34674.6	11350.00
10	34373.53	98.92	0.30( 0.29)	0.96	37848.8	11130.00
11	34203.71	104.98	0.30( 0.29)	0.96	40775.4	12300.00
12	34088.96	108.86	0.30( 0.29)	0.96	42836.3	11620.00
13	33748.21	113.70	0.30( 0.29)	0.96	45036.0	12400.00
14	32947.18	123.14	0.30( 0.29)	0.97	48437.6	12201.00
15	32145.25	130.54	0.30( 0.29)	0.97	50330.6	12231.00
16	31310.01	137.94	0.30( 0.29)	0.97	51883.3	10400.00
17	29961.21	147.25	0.30( 0.29)	0.97	53329.8	12010.00
18	29038.33	152.53	0.30( 0.29)	0.97	53592.3	10210.00
19	28457.00	156.52	0.30( 0.29)	0.97	53739.1	12000.00
20	25241.95	182.47	0.30( 0.29)	0.97	54352.1	10100.00
TOTAL AREA(ACRES) =						54352.1

\*\*\*\*\*

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20095.98	19.05	0.30 ( 0.25)	0.83	4136.6	50400.00
2	22793.37	28.89	0.30 ( 0.25)	0.85	6798.8	50300.00
3	25164.78	41.32	0.30 ( 0.26)	0.87	10690.4	40200.00
4	25575.61	45.10	0.30 ( 0.27)	0.88	12106.9	390.00
5	26723.63	55.33	0.30 ( 0.27)	0.91	15884.7	40100.00
6	28396.10	64.64	0.30 ( 0.28)	0.93	19187.0	11801.00
7	30588.65	75.44	0.30 ( 0.28)	0.94	23716.7	11530.00
8	31818.04	84.12	0.30 ( 0.28)	0.95	28348.8	11910.00
9	33802.26	94.19	0.30 ( 0.29)	0.96	34674.6	11350.00
10	34373.53	98.92	0.30 ( 0.29)	0.96	37848.8	11130.00
11	34203.71	104.98	0.30 ( 0.29)	0.96	40775.4	12300.00
12	34088.96	108.86	0.30 ( 0.29)	0.96	42836.3	11620.00
13	33748.21	113.70	0.30 ( 0.29)	0.96	45036.0	12400.00
14	32947.18	123.14	0.30 ( 0.29)	0.97	48437.6	12201.00
15	32145.25	130.54	0.30 ( 0.29)	0.97	50330.6	12231.00
16	31310.01	137.94	0.30 ( 0.29)	0.97	51883.3	10400.00
17	29961.21	147.25	0.30 ( 0.29)	0.97	53329.8	12010.00
18	29038.33	152.53	0.30 ( 0.29)	0.97	53592.3	10210.00
19	28457.00	156.52	0.30 ( 0.29)	0.97	53739.1	12000.00
20	25241.95	182.47	0.30 ( 0.29)	0.97	54352.1	10100.00
TOTAL AREA (ACRES) =						54352.1

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12904.00 TO NODE 13308.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 213.00 DOWNSTREAM (FEET) = 212.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1389.52 CHANNEL SLOPE = 0.0007  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 16.69  
CHANNEL FLOW THRU SUBAREA (CFS) = 34373.53  
FLOW VELOCITY (FEET/SEC.) = 7.27 FLOW DEPTH (FEET) = 16.69  
TRAVEL TIME (MIN.) = 3.19 Tc (MIN.) = 102.11  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118090.66 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13307.00 TO NODE 13308.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20095.98	22.81	1.857	0.30 ( 0.25)	0.83	4136.6	50400.00
2	22793.37	32.51	1.484	0.30 ( 0.25)	0.85	6798.8	50300.00
3	25164.78	44.82	1.260	0.30 ( 0.26)	0.87	10690.4	40200.00
4	25575.61	48.59	1.202	0.30 ( 0.27)	0.88	12106.9	390.00
5	26723.63	58.77	1.071	0.30 ( 0.27)	0.91	15884.7	40100.00
6	28396.10	68.01	1.010	0.30 ( 0.28)	0.93	19187.0	11801.00

7	30588.65	78.74	0.949	0.30 ( 0.28)	0.94	23716.7	11530.00
8	31818.04	87.38	0.901	0.30 ( 0.28)	0.95	28348.8	11910.00
9	33802.26	97.39	0.859	0.30 ( 0.29)	0.96	34674.6	11350.00
10	34373.53	102.11	0.841	0.30 ( 0.29)	0.96	37848.8	11130.00
11	34203.71	108.17	0.819	0.30 ( 0.29)	0.96	40775.4	12300.00
12	34088.96	112.06	0.804	0.30 ( 0.29)	0.96	42836.3	11620.00
13	33748.21	116.91	0.786	0.30 ( 0.29)	0.96	45036.0	12400.00
14	32947.18	126.36	0.761	0.30 ( 0.29)	0.97	48437.6	12201.00
15	32145.25	133.79	0.745	0.30 ( 0.29)	0.97	50330.6	12231.00
16	31310.01	141.22	0.729	0.30 ( 0.29)	0.97	51883.3	10400.00
17	29961.21	150.57	0.709	0.30 ( 0.29)	0.97	53329.8	12010.00
18	29038.33	155.89	0.698	0.30 ( 0.29)	0.97	53592.3	10210.00
19	28457.00	159.89	0.689	0.30 ( 0.29)	0.97	53739.1	12000.00
20	25241.95	185.97	0.640	0.30 ( 0.29)	0.97	54352.1	10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118090.66 FEET.							

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3703.69	23.78	1.807	0.30 ( 0.22)	0.73	1929.2	120.00
2	3704.53	23.84	1.804	0.30 ( 0.22)	0.73	1935.0	110.00
3	3824.44	30.86	1.517	0.30 ( 0.23)	0.75	2574.0	100.00
4	3886.34	33.53	1.463	0.30 ( 0.23)	0.76	2799.0	150.00
5	4060.15	44.20	1.269	0.30 ( 0.23)	0.78	3666.0	31100.00
6	4416.80	59.43	1.062	0.30 ( 0.24)	0.79	5205.5	13210.00
7	4420.44	59.68	1.059	0.30 ( 0.24)	0.79	5229.5	13200.00
8	4429.62	61.45	1.047	0.30 ( 0.24)	0.79	5355.4	13100.00
9	4103.28	88.01	0.897	0.30 ( 0.24)	0.79	6620.6	13000.00
10	4046.11	90.46	0.884	0.30 ( 0.24)	0.79	6640.5	13010.00
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13308.00 = 48763.78 FEET.							

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23759.22	22.81	1.857	0.30 ( 0.24)	0.80	5987.0	50400.00
2	24069.69	23.78	1.807	0.30 ( 0.24)	0.80	6332.3	120.00
3	24087.23	23.84	1.804	0.30 ( 0.24)	0.80	6354.6	110.00
4	26158.74	30.86	1.517	0.30 ( 0.24)	0.82	8919.7	100.00
5	26656.00	32.51	1.484	0.30 ( 0.25)	0.82	9511.6	50300.00
6	26877.05	33.53	1.463	0.30 ( 0.25)	0.82	9921.6	150.00
7	29103.62	44.20	1.269	0.30 ( 0.25)	0.85	14157.3	31100.00
8	29239.67	44.82	1.260	0.30 ( 0.25)	0.85	14420.0	40200.00
9	29738.54	48.59	1.202	0.30 ( 0.26)	0.86	16216.5	390.00
10	31124.89	58.77	1.071	0.30 ( 0.26)	0.88	21023.1	40100.00
11	31260.54	59.43	1.062	0.30 ( 0.26)	0.88	21327.4	13210.00
12	31308.61	59.68	1.059	0.30 ( 0.26)	0.88	21439.1	13200.00
13	31638.69	61.45	1.047	0.30 ( 0.27)	0.89	22198.6	13100.00
14	32745.10	68.01	1.010	0.30 ( 0.27)	0.90	24855.0	11801.00
15	34805.85	78.74	0.949	0.30 ( 0.27)	0.91	29895.6	11530.00
16	35929.10	87.38	0.901	0.30 ( 0.28)	0.92	34939.2	11910.00
17	36046.85	88.01	0.897	0.30 ( 0.28)	0.92	35369.6	13000.00
18	36473.45	90.46	0.884	0.30 ( 0.28)	0.92	36931.8	13010.00
19	37687.64	97.39	0.859	0.30 ( 0.28)	0.93	41315.1	11350.00
20	38149.62	102.11	0.841	0.30 ( 0.28)	0.94	44489.3	11130.00
21	37839.43	108.17	0.819	0.30 ( 0.28)	0.94	47415.9	12300.00
22	37634.67	112.06	0.804	0.30 ( 0.28)	0.94	49476.8	11620.00
23	37181.60	116.91	0.786	0.30 ( 0.28)	0.94	51676.5	12400.00
24	36223.22	126.36	0.761	0.30 ( 0.28)	0.95	55078.1	12201.00

25	35321.31	133.79	0.745	0.30 ( 0.28)	0.95	56971.1	12231.00
26	34386.09	141.22	0.729	0.30 ( 0.28)	0.95	58523.9	10400.00
27	32911.46	150.57	0.709	0.30 ( 0.28)	0.95	59970.3	12010.00
28	31916.98	155.89	0.698	0.30 ( 0.28)	0.95	60232.9	10210.00
29	31281.71	159.89	0.689	0.30 ( 0.28)	0.95	60379.7	12000.00
30	27760.51	185.97	0.640	0.30 ( 0.28)	0.95	60992.6	10100.00
TOTAL AREA (ACRES) = 60992.6							

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 38149.62 Tc (MIN.) = 102.112  
EFFECTIVE AREA (ACRES) = 44489.34 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.88  
TOTAL AREA (ACRES) = 60992.6  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118090.66 FEET.

=====  
END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 60992.6 TC (MIN.) = 102.11  
EFFECTIVE AREA (ACRES) = 44489.34 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.935  
PEAK FLOW RATE (CFS) = 38149.62

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23759.22	22.81	1.857	0.30 ( 0.24)	0.80	5987.0	50400.00
2	24069.69	23.78	1.807	0.30 ( 0.24)	0.80	6332.3	120.00
3	24087.23	23.84	1.804	0.30 ( 0.24)	0.80	6354.6	110.00
4	26158.74	30.86	1.517	0.30 ( 0.24)	0.82	8919.7	100.00
5	26656.00	32.51	1.484	0.30 ( 0.25)	0.82	9511.6	50300.00
6	26877.05	33.53	1.463	0.30 ( 0.25)	0.82	9921.6	150.00
7	29103.62	44.20	1.269	0.30 ( 0.25)	0.85	14157.3	31100.00
8	29239.67	44.82	1.260	0.30 ( 0.25)	0.85	14420.0	40200.00
9	29738.54	48.59	1.202	0.30 ( 0.26)	0.86	16216.5	390.00
10	31124.89	58.77	1.071	0.30 ( 0.26)	0.88	21023.1	40100.00
11	31260.54	59.43	1.062	0.30 ( 0.26)	0.88	21327.4	13210.00
12	31308.61	59.68	1.059	0.30 ( 0.26)	0.88	21439.1	13200.00
13	31638.69	61.45	1.047	0.30 ( 0.27)	0.89	22198.6	13100.00
14	32745.10	68.01	1.010	0.30 ( 0.27)	0.90	24855.0	11801.00
15	34805.85	78.74	0.949	0.30 ( 0.27)	0.91	29895.6	11530.00
16	35929.10	87.38	0.901	0.30 ( 0.28)	0.92	34939.2	11910.00
17	36046.85	88.01	0.897	0.30 ( 0.28)	0.92	35369.6	13000.00
18	36473.45	90.46	0.884	0.30 ( 0.28)	0.92	36931.8	13010.00
19	37687.64	97.39	0.859	0.30 ( 0.28)	0.93	41315.1	11350.00
20	38149.62	102.11	0.841	0.30 ( 0.28)	0.94	44489.3	11130.00
21	37839.43	108.17	0.819	0.30 ( 0.28)	0.94	47415.9	12300.00
22	37634.67	112.06	0.804	0.30 ( 0.28)	0.94	49476.8	11620.00
23	37181.60	116.91	0.786	0.30 ( 0.28)	0.94	51676.5	12400.00
24	36223.22	126.36	0.761	0.30 ( 0.28)	0.95	55078.1	12201.00
25	35321.31	133.79	0.745	0.30 ( 0.28)	0.95	56971.1	12231.00
26	34386.09	141.22	0.729	0.30 ( 0.28)	0.95	58523.9	10400.00
27	32911.46	150.57	0.709	0.30 ( 0.28)	0.95	59970.3	12010.00
28	31916.98	155.89	0.698	0.30 ( 0.28)	0.95	60232.9	10210.00
29	31281.71	159.89	0.689	0.30 ( 0.28)	0.95	60379.7	12000.00
30	27760.51	185.97	0.640	0.30 ( 0.28)	0.95	60992.6	10100.00

=====  
END OF RATIONAL METHOD ANALYSIS



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S34- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 25- YR RM EV APRIL 2019 CCHIU \*  
\*\*\*\*\*

FILE NAME: RI25EV34.DAT  
TIME/DATE OF STUDY: 09:51 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 25.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 4.808
- 2) 10.00; 3.143
- 3) 15.00; 2.408
- 4) 20.00; 1.996
- 5) 25.00; 1.742
- 6) 30.00; 1.531
- 7) 40.00; 1.331
- 8) 50.00; 1.178
- 9) 60.00; 1.052
- 10) 90.00; 0.883
- 11) 120.00; 0.772
- 12) 180.00; 0.643
- 13) 360.00; 0.472
- 14) 1200.00; 0.207

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI25EV33.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24087.23	23.84	0.30 ( 0.24)	0.80	6354.6	110.00
2	26877.05	33.53	0.30 ( 0.25)	0.82	9921.6	150.00
3	29239.67	44.82	0.30 ( 0.25)	0.85	14420.0	40200.00
4	29738.54	48.59	0.30 ( 0.26)	0.86	16216.5	390.00
5	31638.69	61.45	0.30 ( 0.27)	0.89	22198.6	13100.00
6	32745.10	68.01	0.30 ( 0.27)	0.90	24855.0	11801.00
7	34805.85	78.74	0.30 ( 0.27)	0.91	29895.6	11530.00
8	36473.45	90.46	0.30 ( 0.28)	0.92	36931.8	13010.00
9	37687.64	97.39	0.30 ( 0.28)	0.93	41315.1	11350.00
10	38149.62	102.11	0.30 ( 0.28)	0.94	44489.3	11130.00
11	37839.43	108.17	0.30 ( 0.28)	0.94	47415.9	12300.00
12	37634.67	112.06	0.30 ( 0.28)	0.94	49476.8	11620.00
13	37181.60	116.91	0.30 ( 0.28)	0.94	51676.5	12400.00
14	36223.22	126.36	0.30 ( 0.28)	0.95	55078.1	12201.00
15	35321.31	133.79	0.30 ( 0.28)	0.95	56971.1	12231.00
16	34386.09	141.22	0.30 ( 0.28)	0.95	58523.9	10400.00
17	32911.46	150.57	0.30 ( 0.28)	0.95	59970.3	12010.00
18	31916.98	155.89	0.30 ( 0.28)	0.95	60232.9	10210.00
19	31281.71	159.89	0.30 ( 0.28)	0.95	60379.7	12000.00
20	27760.51	185.97	0.30 ( 0.28)	0.95	60992.6	10100.00
TOTAL AREA (ACRES) =						60992.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24087.23	23.84	0.30 ( 0.24)	0.80	6354.6	110.00
2	26877.05	33.53	0.30 ( 0.25)	0.82	9921.6	150.00
3	29239.67	44.82	0.30 ( 0.25)	0.85	14420.0	40200.00
4	29738.54	48.59	0.30 ( 0.26)	0.86	16216.5	390.00
5	31638.69	61.45	0.30 ( 0.27)	0.89	22198.6	13100.00
6	32745.10	68.01	0.30 ( 0.27)	0.90	24855.0	11801.00
7	34805.85	78.74	0.30 ( 0.27)	0.91	29895.6	11530.00
8	36473.45	90.46	0.30 ( 0.28)	0.92	36931.8	13010.00
9	37687.64	97.39	0.30 ( 0.28)	0.93	41315.1	11350.00
10	38149.62	102.11	0.30 ( 0.28)	0.94	44489.3	11130.00
11	37839.43	108.17	0.30 ( 0.28)	0.94	47415.9	12300.00
12	37634.67	112.06	0.30 ( 0.28)	0.94	49476.8	11620.00
13	37181.60	116.91	0.30 ( 0.28)	0.94	51676.5	12400.00

14	36223.22	126.36	0.30	( 0.28)	0.95	55078.1	12201.00
15	35321.31	133.79	0.30	( 0.28)	0.95	56971.1	12231.00
16	34386.09	141.22	0.30	( 0.28)	0.95	58523.9	10400.00
17	32911.46	150.57	0.30	( 0.28)	0.95	59970.3	12010.00
18	31916.98	155.89	0.30	( 0.28)	0.95	60232.9	10210.00
19	31281.71	159.89	0.30	( 0.28)	0.95	60379.7	12000.00
20	27760.51	185.97	0.30	( 0.28)	0.95	60992.6	10100.00

TOTAL AREA (ACRES) = 60992.6

\*\*\*\*\*

FLOW PROCESS FROM NODE 13308.00 TO NODE 13402.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 215.00 DOWNSTREAM(FEET) = 209.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 623.02 CHANNEL SLOPE = 0.0096  
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 8.60  
 CHANNEL FLOW THRU SUBAREA(CFS) = 38149.62  
 FLOW VELOCITY(FEET/SEC.) = 18.25 FLOW DEPTH(FEET) = 8.60  
 TRAVEL TIME(MIN.) = 0.57 Tc(MIN.) = 102.68  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118713.68 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13402.00 TO NODE 13402.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<

PEAK FLOWRATE TABLE FILE NAME: 0610505W.DNA  
 MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	233.86	20.08	0.30( 0.30)	0.99	153.2	50500.00

TOTAL AREA (ACRES) = 153.2

\*\*\*\*\*

FLOW PROCESS FROM NODE 13402.00 TO NODE 13402.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24087.23	24.50	1.767	0.30( 0.24)	0.80	6354.6	110.00
2	26877.05	34.17	1.448	0.30( 0.25)	0.82	9921.6	150.00
3	29239.67	45.45	1.248	0.30( 0.25)	0.85	14420.0	40200.00
4	29738.54	49.20	1.190	0.30( 0.26)	0.86	16216.5	390.00
5	31638.69	62.06	1.040	0.30( 0.27)	0.89	22198.6	13100.00
6	32745.10	68.61	1.003	0.30( 0.27)	0.90	24855.0	11801.00
7	34805.85	79.33	0.943	0.30( 0.27)	0.91	29895.6	11530.00
8	36473.45	91.03	0.879	0.30( 0.28)	0.92	36931.8	13010.00
9	37687.64	97.97	0.854	0.30( 0.28)	0.93	41315.1	11350.00
10	38149.62	102.68	0.836	0.30( 0.28)	0.94	44489.3	11130.00
11	37839.43	108.74	0.814	0.30( 0.28)	0.94	47415.9	12300.00
12	37634.67	112.63	0.799	0.30( 0.28)	0.94	49476.8	11620.00

13	37181.60	117.48	0.781	0.30( 0.28)	0.94	51676.5	12400.00
14	36223.22	126.94	0.757	0.30( 0.28)	0.95	55078.1	12201.00
15	35321.31	134.38	0.741	0.30( 0.28)	0.95	56971.1	12231.00
16	34386.09	141.81	0.725	0.30( 0.28)	0.95	58523.9	10400.00
17	32911.46	151.17	0.705	0.30( 0.28)	0.95	59970.3	12010.00
18	31916.98	156.49	0.694	0.30( 0.28)	0.95	60232.9	10210.00
19	31281.71	160.50	0.685	0.30( 0.28)	0.95	60379.7	12000.00
20	27760.51	186.61	0.637	0.30( 0.28)	0.95	60992.6	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118713.68 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	233.86	20.08	1.992	0.30( 0.30)	0.99	153.2	50500.00

LONGEST FLOWPATH FROM NODE 50500.00 TO NODE 13402.00 = 6247.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22880.11	20.08	1.992	0.30( 0.24)	0.81	5361.3	50500.00
2	24290.13	24.50	1.767	0.30( 0.24)	0.81	6507.8	110.00
3	27035.85	34.17	1.448	0.30( 0.25)	0.83	10074.8	150.00
4	29370.91	45.45	1.248	0.30( 0.26)	0.85	14573.2	40200.00
5	29861.85	49.20	1.190	0.30( 0.26)	0.86	16369.7	390.00
6	31741.36	62.06	1.040	0.30( 0.27)	0.89	22351.8	13100.00
7	32842.67	68.61	1.003	0.30( 0.27)	0.90	25008.2	11801.00
8	34895.10	79.33	0.943	0.30( 0.27)	0.91	30048.8	11530.00
9	36553.88	91.03	0.879	0.30( 0.28)	0.92	37085.0	13010.00
10	37764.54	97.97	0.854	0.30( 0.28)	0.93	41468.3	11350.00
11	38224.11	102.68	0.836	0.30( 0.28)	0.94	44642.5	11130.00
12	37910.82	108.74	0.814	0.30( 0.28)	0.94	47569.1	12300.00
13	37704.09	112.63	0.799	0.30( 0.28)	0.94	49630.0	11620.00
14	37248.54	117.48	0.781	0.30( 0.28)	0.94	51829.7	12400.00
15	36286.82	126.94	0.757	0.30( 0.28)	0.95	55231.3	12201.00
16	35382.70	134.38	0.741	0.30( 0.28)	0.95	57124.3	12231.00
17	34445.29	141.81	0.725	0.30( 0.28)	0.95	58677.0	10400.00
18	32967.88	151.17	0.705	0.30( 0.28)	0.95	60123.5	12010.00
19	31971.82	156.49	0.694	0.30( 0.28)	0.95	60386.0	10210.00
20	31335.36	160.50	0.685	0.30( 0.28)	0.95	60532.9	12000.00
21	27807.52	186.61	0.637	0.30( 0.28)	0.95	61145.8	10100.00

TOTAL AREA (ACRES) = 61145.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 38224.11 Tc(MIN.) = 102.681  
 EFFECTIVE AREA(ACRES) = 44642.52 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 61145.8  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118713.68 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13402.00 TO NODE 13404.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 209.00 DOWNSTREAM(FEET) = 207.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 395.35 CHANNEL SLOPE = 0.0051  
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0



"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 10.33  
 CHANNEL FLOW THRU SUBAREA(CFS) = 38224.11  
 FLOW VELOCITY(FEET/SEC.) = 14.70 FLOW DEPTH(FEET) = 10.33  
 TRAVEL TIME(MIN.) = 0.45 Tc(MIN.) = 103.13  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119109.03 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13404.00 TO NODE 13404.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 0610506W.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	84.62	17.59	0.30	(0.30)	1.00	49.6	50600.00
TOTAL AREA (ACRES) =							49.6

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13404.00 TO NODE 13404.00 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\*\*\*\*  
 \*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22880.11	20.61	1.965	0.30 (0.24)	0.81	5361.3	50500.00
2	24290.13	25.02	1.741	0.30 (0.24)	0.81	6507.8	110.00
3	27035.85	34.68	1.437	0.30 (0.25)	0.83	10074.8	150.00
4	29370.91	45.94	1.240	0.30 (0.26)	0.85	14573.2	40200.00
5	29861.85	49.69	1.183	0.30 (0.26)	0.86	16369.7	390.00
6	31741.36	62.53	1.038	0.30 (0.27)	0.89	22351.8	13100.00
7	32842.67	69.08	1.001	0.30 (0.27)	0.90	25008.2	11801.00
8	34895.10	79.79	0.941	0.30 (0.27)	0.91	30048.8	11530.00
9	36553.88	91.49	0.877	0.30 (0.28)	0.92	37085.0	13010.00
10	37764.54	98.42	0.852	0.30 (0.28)	0.93	41468.3	11350.00
11	38224.11	103.13	0.834	0.30 (0.28)	0.94	44642.5	11130.00
12	37910.82	109.19	0.812	0.30 (0.28)	0.94	47569.1	12300.00
13	37704.09	113.08	0.798	0.30 (0.28)	0.94	49630.0	11620.00
14	37248.54	117.93	0.780	0.30 (0.28)	0.94	51829.7	12400.00
15	36286.82	127.40	0.756	0.30 (0.28)	0.95	55231.3	12201.00
16	35382.70	134.84	0.740	0.30 (0.28)	0.95	57124.3	12231.00
17	34445.29	142.27	0.724	0.30 (0.28)	0.95	58677.0	10400.00
18	32967.88	151.64	0.704	0.30 (0.28)	0.95	60123.5	12010.00
19	31971.82	156.97	0.693	0.30 (0.28)	0.95	60386.0	10210.00
20	31335.36	160.98	0.684	0.30 (0.28)	0.95	60532.9	12000.00
21	27807.52	187.10	0.636	0.30 (0.28)	0.95	61145.8	10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 =							119109.03 FEET.

\*\*\*\*\*  
 \*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	84.62	17.59	2.195	0.30 (0.30)	1.00	49.6	50600.00
LONGEST FLOWPATH FROM NODE 50600.00 TO NODE 13404.00 =							4378.00 FEET.

\*\*\*\*\*  
 \*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22212.71	17.59	2.195	0.30 (0.24)	0.81	4623.6	50600.00
2	22954.45	20.61	1.965	0.30 (0.24)	0.81	5410.9	50500.00
3	24354.48	25.02	1.741	0.30 (0.24)	0.81	6557.4	110.00
4	27086.64	34.68	1.437	0.30 (0.25)	0.83	10124.4	150.00
5	29412.90	45.94	1.240	0.30 (0.26)	0.85	14622.8	40200.00
6	29901.27	49.69	1.183	0.30 (0.26)	0.86	16419.3	390.00
7	31774.30	62.53	1.038	0.30 (0.27)	0.89	22401.4	13100.00
8	32873.97	69.08	1.001	0.30 (0.27)	0.90	25057.8	11801.00
9	34923.70	79.79	0.941	0.30 (0.27)	0.91	30098.4	11530.00
10	36579.67	91.49	0.877	0.30 (0.28)	0.92	37134.6	13010.00
11	37789.19	98.42	0.852	0.30 (0.28)	0.93	41517.9	11350.00
12	38247.98	103.13	0.834	0.30 (0.28)	0.94	44692.1	11130.00
13	37933.69	109.19	0.812	0.30 (0.28)	0.94	47618.7	12300.00
14	37726.31	113.08	0.798	0.30 (0.28)	0.94	49679.6	11620.00
15	37269.96	117.93	0.780	0.30 (0.28)	0.94	51879.3	12400.00
16	36307.19	127.40	0.756	0.30 (0.28)	0.95	55280.9	12201.00
17	35402.36	134.84	0.740	0.30 (0.28)	0.95	57173.9	12231.00
18	34464.23	142.27	0.724	0.30 (0.28)	0.95	58726.6	10400.00
19	32985.92	151.64	0.704	0.30 (0.28)	0.95	60173.1	12010.00
20	31989.35	156.97	0.693	0.30 (0.28)	0.95	60435.6	10210.00
21	31352.51	160.98	0.684	0.30 (0.28)	0.95	60582.4	12000.00
22	27822.54	187.10	0.636	0.30 (0.28)	0.95	61195.4	10100.00
TOTAL AREA (ACRES) =							61195.4

\*\*\*\*\*  
 COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 38247.98 Tc(MIN.) = 103.129  
 EFFECTIVE AREA(ACRES) = 44692.12 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 61195.4  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119109.03 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13404.00 TO NODE 13406.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 207.00 DOWNSTREAM(FEET) = 195.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1601.97 CHANNEL SLOPE = 0.0075  
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 9.26  
 CHANNEL FLOW THRU SUBAREA(CFS) = 38247.98  
 FLOW VELOCITY(FEET/SEC.) = 16.78 FLOW DEPTH(FEET) = 9.26  
 TRAVEL TIME(MIN.) = 1.59 Tc(MIN.) = 104.72  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13406.00 = 120711.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 104.72  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.829  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS

LAND USE	GROUP	(ACRES)	(INCH/HR)	(DECIMAL)	CN
NATURAL FAIR COVER					
"GRASS"	B	0.20	0.30	1.000	69
NATURAL FAIR COVER					
"GRASS"	B	4.00	0.30	1.000	69
NATURAL FAIR COVER					
"GRASS"	B	2.00	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	9.70	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.60	0.30	1.000	66
AGRICULTURAL POOR COVER					
"ROW CROPS, STRAIGHT ROW"	B	1.80	0.30	1.000	81

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 20.30 SUBAREA RUNOFF (CFS) = 9.66  
EFFECTIVE AREA (ACRES) = 44712.42 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94  
TOTAL AREA (ACRES) = 61215.7 PEAK FLOW RATE (CFS) = 38247.98  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 104.72

\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.829

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS, STRAIGHT ROW"	B	3.50	0.30	1.000	81
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	7.20	0.30	1.000	65
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	5.80	0.30	1.000	65
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.10	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 16.60 SUBAREA RUNOFF (CFS) = 7.90

EFFECTIVE AREA (ACRES) = 44729.02 AREA-AVERAGED Fm (INCH/HR) = 0.28

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94

TOTAL AREA (ACRES) = 61232.3 PEAK FLOW RATE (CFS) = 38247.98

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 2P25EVBB.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	676.18	9.97	0.30 ( 0.11)	0.38	243.5	429.00
2	719.57	11.48	0.30 ( 0.11)	0.38	280.3	425.00
3	729.64	11.90	0.30 ( 0.11)	0.38	290.5	400.00
4	756.99	13.36	0.30 ( 0.11)	0.38	326.6	300.00
5	801.01	18.55	0.30 ( 0.11)	0.38	439.8	210.00
6	788.68	20.66	0.30 ( 0.11)	0.38	466.8	410.00
7	782.25	21.72	0.30 ( 0.11)	0.38	480.1	200.00
8	780.36	22.29	0.30 ( 0.11)	0.38	486.6	230.00
9	762.79	23.40	0.30 ( 0.11)	0.37	491.2	220.50
TOTAL AREA (ACRES) =			491.2			

\*\*\*\*\*

FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22212.71	19.49	2.038	0.30 ( 0.24)	0.81	4660.5	50600.00
2	22954.45	22.50	1.869	0.30 ( 0.24)	0.81	5447.8	50500.00
3	24354.48	26.87	1.663	0.30 ( 0.24)	0.81	6594.3	110.00
4	27086.64	36.46	1.402	0.30 ( 0.25)	0.83	10161.3	150.00
5	29412.90	47.67	1.214	0.30 ( 0.26)	0.85	14659.7	40200.00
6	29901.27	51.42	1.160	0.30 ( 0.26)	0.86	16456.2	390.00
7	31774.30	64.22	1.028	0.30 ( 0.27)	0.89	22438.3	13100.00
8	32873.97	70.76	0.991	0.30 ( 0.27)	0.90	25094.7	11801.00
9	34923.70	81.43	0.931	0.30 ( 0.27)	0.91	30135.3	11530.00
10	36579.67	93.10	0.872	0.30 ( 0.28)	0.92	37171.5	13010.00
11	37789.19	100.01	0.846	0.30 ( 0.28)	0.93	41554.8	11350.00
12	38247.98	104.72	0.829	0.30 ( 0.28)	0.94	44729.0	11130.00
13	37933.69	110.79	0.806	0.30 ( 0.28)	0.94	47655.6	12300.00
14	37726.31	114.68	0.792	0.30 ( 0.28)	0.94	49716.5	11620.00
15	37269.96	119.54	0.774	0.30 ( 0.28)	0.94	51916.2	12400.00
16	36307.19	129.02	0.753	0.30 ( 0.28)	0.95	55317.8	12201.00
17	35402.36	136.47	0.737	0.30 ( 0.28)	0.95	57210.8	12231.00
18	34464.23	143.92	0.721	0.30 ( 0.28)	0.95	58763.5	10400.00
19	32985.92	153.31	0.700	0.30 ( 0.28)	0.95	60210.0	12010.00
20	31989.35	158.66	0.689	0.30 ( 0.28)	0.95	60472.5	10210.00
21	31352.51	162.68	0.680	0.30 ( 0.28)	0.95	60619.4	12000.00
22	27822.54	188.87	0.635	0.30 ( 0.28)	0.95	61232.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13406.00 = 120711.00 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	676.18	9.97	3.155	0.30 ( 0.11)	0.38	243.5	429.00
2	719.57	11.48	2.926	0.30 ( 0.11)	0.38	280.3	425.00
3	729.64	11.90	2.864	0.30 ( 0.11)	0.38	290.5	400.00
4	756.99	13.36	2.648	0.30 ( 0.11)	0.38	326.6	300.00
5	801.01	18.55	2.115	0.30 ( 0.11)	0.38	439.8	210.00
6	788.68	20.66	1.962	0.30 ( 0.11)	0.38	466.8	410.00
7	782.25	21.72	1.909	0.30 ( 0.11)	0.38	480.1	200.00

8 780.36 22.29 1.880 0.30( 0.11) 0.38 486.6 230.00  
 9 762.79 23.40 1.823 0.30( 0.11) 0.37 491.2 220.50  
 LONGEST FLOWPATH FROM NODE 230.00 TO NODE 13406.00 = 11903.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19101.02	9.97	3.155	0.30( 0.23)	0.77	2626.1	429.00
2	20272.84	11.48	2.926	0.30( 0.23)	0.77	3024.5	425.00
3	20531.71	11.90	2.864	0.30( 0.23)	0.77	3135.1	400.00
4	21170.01	13.36	2.648	0.30( 0.23)	0.77	3522.0	300.00
5	22854.97	18.55	2.115	0.30( 0.23)	0.77	4875.2	210.00
6	23008.22	19.49	2.038	0.30( 0.23)	0.77	5112.4	50600.00
7	23290.29	20.66	1.962	0.30( 0.23)	0.78	5433.9	410.00
8	23544.95	21.72	1.909	0.30( 0.23)	0.78	5724.3	200.00
9	23682.72	22.29	1.880	0.30( 0.23)	0.78	5879.1	230.00
10	23731.48	22.50	1.869	0.30( 0.23)	0.78	5935.2	50500.00
11	24005.96	23.40	1.823	0.30( 0.23)	0.78	6175.4	220.50
12	25045.84	26.87	1.663	0.30( 0.23)	0.78	7085.5	110.00
13	27661.51	36.46	1.402	0.30( 0.24)	0.81	10652.5	150.00
14	29903.88	47.67	1.214	0.30( 0.25)	0.84	15150.9	40200.00
15	30368.40	51.42	1.160	0.30( 0.25)	0.85	16947.4	390.00
16	32182.61	64.22	1.028	0.30( 0.26)	0.88	22929.5	13100.00
17	33265.87	70.76	0.991	0.30( 0.27)	0.89	25585.9	11801.00
18	35288.79	81.43	0.931	0.30( 0.27)	0.90	30626.5	11530.00
19	36918.12	93.10	0.872	0.30( 0.27)	0.92	37662.7	13010.00
20	38116.23	100.01	0.846	0.30( 0.28)	0.92	42046.0	11350.00
21	38567.26	104.72	0.829	0.30( 0.28)	0.93	45220.2	11130.00
22	38242.96	110.79	0.806	0.30( 0.28)	0.93	48146.8	12300.00
23	38029.16	114.68	0.792	0.30( 0.28)	0.94	50207.7	11620.00
24	37564.79	119.54	0.774	0.30( 0.28)	0.94	52407.4	12400.00
25	36592.62	129.02	0.753	0.30( 0.28)	0.94	55809.0	12201.00
26	35680.64	136.47	0.737	0.30( 0.28)	0.94	57702.0	12231.00
27	34735.37	143.92	0.721	0.30( 0.28)	0.94	59254.7	10400.00
28	33248.07	153.31	0.700	0.30( 0.28)	0.94	60701.2	12010.00
29	32246.37	158.66	0.689	0.30( 0.28)	0.94	60963.7	10210.00
30	31605.67	162.68	0.680	0.30( 0.28)	0.94	61110.6	12000.00
31	28055.33	188.87	0.635	0.30( 0.28)	0.95	61723.5	10100.00
TOTAL AREA (ACRES) = 61723.5							

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:  
 PEAK FLOW RATE(CFS) = 38567.26 Tc(MIN.) = 104.721  
 EFFECTIVE AREA(ACRES) = 45220.22 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.78  
 TOTAL AREA(ACRES) = 61723.5  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13406.00 = 120711.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13406.00 TO NODE 13408.00 IS CODE = 56  
 -----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 195.00 DOWNSTREAM(FEET) = 182.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2458.36 CHANNEL SLOPE = 0.0053  
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 10.26

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.818  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 7.00 0.30 1.000 -  
 USER-DEFINED - 3.30 0.30 1.000 -  
 USER-DEFINED - 0.40 0.30 0.100 -  
 USER-DEFINED - 1.40 0.30 1.000 -  
 USER-DEFINED - 0.30 0.30 0.100 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.949  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 38570.23  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 14.96  
 AVERAGE FLOW DEPTH(FEET) = 10.26 TRAVEL TIME(MIN.) = 2.74  
 Tc(MIN.) = 107.46  
 SUBAREA AREA(ACRES) = 12.40 SUBAREA RUNOFF(CFS) = 5.96  
 EFFECTIVE AREA(ACRES) = 45232.62 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 61735.9 PEAK FLOW RATE(CFS) = 38567.26  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 10.26  
  
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 10.26 FLOW VELOCITY(FEET/SEC.) = 14.96  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123169.36 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 12  
 -----  
 >>>>CLEAR MEMORY BANK # 2 <<<<<  
 =====

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 15.1  
 -----  
 >>>>DEFINE MEMORY BANK # 2 <<<<<  
 =====

PEAK FLOWRATE TABLE FILE NAME: 0610507W.DNA  
 MEMORY BANK # 2 DEFINED AS FOLLOWS:  
 STREAM Q Tc Fp(Fm) Ap Ae HEADWATER  
 NUMBER (CFS) (MIN.) (INCH/HR) (ACRES) NODE  
 1 358.70 20.30 0.30( 0.30) 0.99 236.8 50700.00  
 TOTAL AREA(ACRES) = 236.8

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 11  
 -----  
 >>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<  
 =====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19101.02	13.42	2.640	0.30( 0.23)	0.77	2638.5	429.00
2	20272.84	14.87	2.428	0.30( 0.23)	0.77	3036.9	425.00
3	20531.71	15.27	2.386	0.30( 0.23)	0.77	3147.5	400.00

4	21170.01	16.70	2.268	0.30 ( 0.23)	0.77	3534.4	300.00
5	22854.97	21.80	1.904	0.30 ( 0.23)	0.77	4887.6	210.00
6	23008.22	22.74	1.857	0.30 ( 0.23)	0.77	5124.8	50600.00
7	23290.29	23.90	1.798	0.30 ( 0.23)	0.78	5446.3	410.00
8	23544.95	24.94	1.745	0.30 ( 0.23)	0.78	5736.7	200.00
9	23682.72	25.50	1.721	0.30 ( 0.23)	0.78	5891.5	230.00
10	23731.48	25.71	1.712	0.30 ( 0.23)	0.78	5947.6	50500.00
11	24005.96	26.60	1.674	0.30 ( 0.23)	0.78	6187.8	220.50
12	25045.84	30.02	1.531	0.30 ( 0.23)	0.78	7097.9	110.00
13	27661.51	39.51	1.341	0.30 ( 0.24)	0.81	10664.9	150.00
14	29903.88	50.65	1.170	0.30 ( 0.25)	0.84	15163.3	40200.00
15	30368.40	54.38	1.123	0.30 ( 0.25)	0.85	16959.8	390.00
16	32182.61	67.13	1.012	0.30 ( 0.26)	0.88	22941.9	13100.00
17	33265.87	73.63	0.975	0.30 ( 0.27)	0.89	25598.3	11801.00
18	35288.79	84.25	0.915	0.30 ( 0.27)	0.90	30638.9	11530.00
19	36918.12	95.88	0.861	0.30 ( 0.27)	0.92	37675.1	13010.00
20	38116.23	102.76	0.836	0.30 ( 0.28)	0.92	42058.4	11350.00
21	38567.26	107.46	0.818	0.30 ( 0.28)	0.93	45232.6	11130.00
22	38242.96	113.53	0.796	0.30 ( 0.28)	0.93	48159.2	12300.00
23	38029.16	117.43	0.782	0.30 ( 0.28)	0.94	50220.1	11620.00
24	37564.79	122.30	0.767	0.30 ( 0.28)	0.94	52419.8	12400.00
25	36592.62	131.80	0.747	0.30 ( 0.28)	0.94	55821.4	12201.00
26	35680.64	139.28	0.731	0.30 ( 0.28)	0.94	57714.4	12231.00
27	34735.37	146.75	0.714	0.30 ( 0.28)	0.94	59267.1	10400.00
28	33248.07	156.18	0.694	0.30 ( 0.28)	0.94	60713.6	12010.00
29	32246.37	161.56	0.683	0.30 ( 0.28)	0.94	60976.1	10210.00
30	31605.67	165.60	0.674	0.30 ( 0.28)	0.94	61122.9	12000.00
31	28055.33	191.91	0.632	0.30 ( 0.28)	0.95	61735.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123169.36 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	358.70	20.30	1.981	0.30 ( 0.30)	0.99	236.8	50700.00

LONGEST FLOWPATH FROM NODE 50700.00 TO NODE 13408.00 = 7903.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19431.06	13.42	2.640	0.30 ( 0.24)	0.79	2795.0	429.00
2	20605.26	14.87	2.428	0.30 ( 0.24)	0.79	3210.3	425.00
3	20866.44	15.27	2.386	0.30 ( 0.24)	0.78	3325.6	400.00
4	21515.46	16.70	2.268	0.30 ( 0.24)	0.78	3729.2	300.00
5	22717.50	20.30	1.981	0.30 ( 0.24)	0.78	4725.9	50700.00
6	23197.41	21.80	1.904	0.30 ( 0.24)	0.78	5124.4	210.00
7	23340.54	22.74	1.857	0.30 ( 0.24)	0.78	5361.5	50600.00
8	23610.06	23.90	1.798	0.30 ( 0.24)	0.78	5683.1	410.00
9	23853.41	24.94	1.745	0.30 ( 0.24)	0.78	5973.5	200.00
10	23986.05	25.50	1.721	0.30 ( 0.24)	0.78	6128.3	230.00
11	24032.91	25.71	1.712	0.30 ( 0.24)	0.79	6184.4	50500.00
12	24299.41	26.60	1.674	0.30 ( 0.24)	0.79	6424.6	220.50
13	25308.60	30.02	1.531	0.30 ( 0.24)	0.79	7334.7	110.00
14	27883.82	39.51	1.341	0.30 ( 0.24)	0.81	10901.7	150.00
15	30089.76	50.65	1.170	0.30 ( 0.25)	0.84	15400.1	40200.00
16	30544.28	54.38	1.123	0.30 ( 0.25)	0.85	17196.6	390.00
17	32334.81	67.13	1.012	0.30 ( 0.26)	0.88	23178.7	13100.00
18	33410.27	73.63	0.975	0.30 ( 0.27)	0.89	25835.0	11801.00
19	35420.44	84.25	0.915	0.30 ( 0.27)	0.90	30875.7	11530.00

20	37038.23	95.88	0.861	0.30 ( 0.27)	0.92	37911.9	13010.00
21	38230.92	102.76	0.836	0.30 ( 0.28)	0.92	42295.2	11350.00
22	38678.23	107.46	0.818	0.30 ( 0.28)	0.93	45469.4	11130.00
23	38349.14	113.53	0.796	0.30 ( 0.28)	0.93	48396.0	12300.00
24	38132.28	117.43	0.782	0.30 ( 0.28)	0.94	50456.8	11620.00
25	37664.83	122.30	0.767	0.30 ( 0.28)	0.94	52656.6	12400.00
26	36688.30	131.80	0.747	0.30 ( 0.28)	0.94	56058.2	12201.00
27	35772.89	139.28	0.731	0.30 ( 0.28)	0.94	57951.2	12231.00
28	34824.20	146.75	0.714	0.30 ( 0.28)	0.94	59503.9	10400.00
29	33332.57	156.18	0.694	0.30 ( 0.28)	0.94	60950.3	12010.00
30	32328.41	161.56	0.683	0.30 ( 0.28)	0.94	61212.9	10210.00
31	31685.86	165.60	0.674	0.30 ( 0.28)	0.94	61359.7	12000.00
32	28126.51	191.91	0.632	0.30 ( 0.28)	0.95	61972.7	10100.00

TOTAL AREA (ACRES) = 61972.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 38678.23 Tc (MIN.) = 107.459  
EFFECTIVE AREA (ACRES) = 45469.40 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
TOTAL AREA (ACRES) = 61972.7  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123169.36 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13408.00 TO NODE 13410.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 182.00 DOWNSTREAM (FEET) = 178.72  
CHANNEL LENGTH THRU SUBAREA (FEET) = 952.73 CHANNEL SLOPE = 0.0034  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 11.59  
\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.814

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.40	0.30	1.000	-
USER-DEFINED	-	2.90	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 38679.00  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 12.94  
AVERAGE FLOW DEPTH (FEET) = 11.59 TRAVEL TIME (MIN.) = 1.23  
Tc (MIN.) = 108.69  
SUBAREA AREA (ACRES) = 3.30 SUBAREA RUNOFF (CFS) = 1.53  
EFFECTIVE AREA (ACRES) = 45472.70 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA (ACRES) = 61976.0 PEAK FLOW RATE (CFS) = 38678.23  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 11.59

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 11.59 FLOW VELOCITY (FEET/SEC.) = 12.94  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124122.09 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 12  
 -----  
 >>>>CLEAR MEMORY BANK # 3 <<<<<<  
 =====

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 15.1  
 -----  
 >>>>DEFINE MEMORY BANK # 3 <<<<<<  
 =====

PEAK FLOWRATE TABLE FILE NAME: RI25EV36.DNA  
 MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2146.96	28.56	0.30 ( 0.27)	0.90	1467.2	110.00
2	2209.71	30.95	0.30 ( 0.27)	0.90	1632.7	100.00
3	2208.12	32.23	0.30 ( 0.27)	0.90	1711.6	100.00
4	2242.47	35.30	0.30 ( 0.27)	0.91	1886.6	130.00
5	2335.96	48.91	0.30 ( 0.28)	0.93	2627.1	20100.00
6	2291.37	54.60	0.30 ( 0.28)	0.93	2814.2	13600.00
7	2090.26	91.42	0.30 ( 0.28)	0.93	3793.8	13510.00
8	1979.94	100.93	0.30 ( 0.28)	0.93	3859.7	13500.00
TOTAL AREA (ACRES) =		3859.7				

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 11  
 -----  
 >>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<<  
 =====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19431.06	14.96	2.414	0.30 ( 0.24)	0.79	2798.3	429.00
2	20605.26	16.37	2.295	0.30 ( 0.24)	0.79	3213.6	425.00
3	20866.44	16.77	2.262	0.30 ( 0.24)	0.79	3328.9	400.00
4	21515.46	18.19	2.145	0.30 ( 0.24)	0.78	3732.5	300.00
5	22717.50	21.76	1.907	0.30 ( 0.24)	0.79	4729.2	50700.00
6	23197.41	23.25	1.831	0.30 ( 0.24)	0.78	5127.7	210.00
7	23340.54	24.18	1.783	0.30 ( 0.24)	0.78	5364.8	50600.00
8	23610.06	25.34	1.728	0.30 ( 0.24)	0.78	5686.4	410.00
9	23853.41	26.38	1.684	0.30 ( 0.24)	0.78	5976.8	200.00
10	23986.05	26.93	1.660	0.30 ( 0.24)	0.79	6131.6	230.00
11	24032.91	27.14	1.652	0.30 ( 0.24)	0.79	6187.7	50500.00
12	24299.41	28.03	1.614	0.30 ( 0.24)	0.79	6427.9	220.50
13	25308.60	31.43	1.502	0.30 ( 0.24)	0.79	7338.0	110.00
14	27883.82	40.88	1.318	0.30 ( 0.24)	0.81	10905.0	150.00
15	30089.76	51.98	1.153	0.30 ( 0.25)	0.84	15403.4	40200.00
16	30544.28	55.70	1.106	0.30 ( 0.25)	0.85	17199.9	390.00
17	32334.81	68.43	1.005	0.30 ( 0.26)	0.88	23182.0	13100.00
18	33410.27	74.92	0.968	0.30 ( 0.27)	0.89	25838.3	11801.00
19	35420.44	85.51	0.908	0.30 ( 0.27)	0.90	30879.0	11530.00
20	37038.23	97.13	0.857	0.30 ( 0.27)	0.92	37915.2	13010.00
21	38230.92	103.99	0.831	0.30 ( 0.28)	0.92	42298.5	11350.00
22	38678.23	108.69	0.814	0.30 ( 0.28)	0.93	45472.7	11130.00
23	38349.14	114.76	0.791	0.30 ( 0.28)	0.93	48399.3	12300.00
24	38132.28	118.66	0.777	0.30 ( 0.28)	0.94	50460.1	11620.00

25	37664.83	123.54	0.764	0.30 ( 0.28)	0.94	52659.9	12400.00
26	36688.30	133.05	0.744	0.30 ( 0.28)	0.94	56061.5	12201.00
27	35772.89	140.54	0.728	0.30 ( 0.28)	0.94	57954.5	12231.00
28	34824.20	148.02	0.712	0.30 ( 0.28)	0.94	59507.2	10400.00
29	33332.57	157.47	0.691	0.30 ( 0.28)	0.94	60953.6	12010.00
30	32328.41	162.86	0.680	0.30 ( 0.28)	0.94	61216.2	10210.00
31	31685.86	166.91	0.671	0.30 ( 0.28)	0.94	61363.0	12000.00
32	28126.51	193.27	0.630	0.30 ( 0.28)	0.95	61976.0	10100.00
LONGEST FLOWPATH FROM NODE		10100.00	TO NODE	13410.00	=	124122.09 FEET.	

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2146.96	28.56	1.592	0.30 ( 0.27)	0.90	1467.2	110.00
2	2209.71	30.95	1.512	0.30 ( 0.27)	0.90	1632.7	100.00
3	2208.12	32.23	1.486	0.30 ( 0.27)	0.90	1711.6	100.00
4	2242.47	35.30	1.425	0.30 ( 0.27)	0.91	1886.6	130.00
5	2335.96	48.91	1.195	0.30 ( 0.28)	0.93	2627.1	20100.00
6	2291.37	54.60	1.120	0.30 ( 0.28)	0.93	2814.2	13600.00
7	2090.26	91.42	0.878	0.30 ( 0.28)	0.93	3793.8	13510.00
8	1979.94	100.93	0.843	0.30 ( 0.28)	0.93	3859.7	13500.00
LONGEST FLOWPATH FROM NODE		13500.00	TO NODE	13410.00	=	41710.10 FEET.	

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21255.43	14.96	2.414	0.30 ( 0.24)	0.81	3566.6	429.00
2	22491.04	16.37	2.295	0.30 ( 0.24)	0.81	4054.6	425.00
3	22766.73	16.77	2.262	0.30 ( 0.24)	0.81	4190.3	400.00
4	23455.54	18.19	2.145	0.30 ( 0.24)	0.81	4666.7	300.00
5	24743.05	21.76	1.907	0.30 ( 0.24)	0.81	5846.9	50700.00
6	25261.57	23.25	1.831	0.30 ( 0.24)	0.81	6322.0	210.00
7	25422.29	24.18	1.783	0.30 ( 0.24)	0.81	6607.1	50600.00
8	25710.79	25.34	1.728	0.30 ( 0.24)	0.81	6987.8	410.00
9	25974.51	26.38	1.684	0.30 ( 0.24)	0.81	7331.7	200.00
10	26115.91	26.93	1.660	0.30 ( 0.24)	0.81	7515.0	230.00
11	26165.70	27.14	1.652	0.30 ( 0.24)	0.81	7582.0	50500.00
12	26442.14	28.03	1.614	0.30 ( 0.24)	0.81	7867.5	220.50
13	26605.50	28.56	1.592	0.30 ( 0.24)	0.81	8038.5	110.00
14	27376.69	30.95	1.512	0.30 ( 0.24)	0.81	8843.0	100.00
15	27517.71	31.43	1.502	0.30 ( 0.24)	0.81	9000.2	110.00
16	27734.50	32.23	1.486	0.30 ( 0.24)	0.81	9351.2	100.00
17	28604.48	35.30	1.425	0.30 ( 0.24)	0.82	10683.7	130.00
18	30164.62	40.88	1.318	0.30 ( 0.25)	0.83	13095.2	150.00
19	31816.60	48.91	1.195	0.30 ( 0.25)	0.85	16788.4	20100.00
20	32401.69	51.98	1.153	0.30 ( 0.26)	0.85	18131.3	40200.00
21	32701.17	54.60	1.120	0.30 ( 0.26)	0.86	19482.5	13600.00
22	32829.63	55.70	1.106	0.30 ( 0.26)	0.86	20043.4	390.00
23	34550.64	68.43	1.005	0.30 ( 0.27)	0.88	26364.1	13100.00
24	35590.67	74.92	0.968	0.30 ( 0.27)	0.89	29193.0	11801.00
25	37542.98	85.51	0.908	0.30 ( 0.27)	0.90	34515.6	11530.00
26	38333.80	91.42	0.878	0.30 ( 0.27)	0.91	38252.6	13510.00
27	39062.28	97.13	0.857	0.30 ( 0.28)	0.92	41748.5	13010.00
28	39678.18	100.93	0.843	0.30 ( 0.28)	0.92	44200.5	13500.00
29	40170.92	103.99	0.831	0.30 ( 0.28)	0.93	46158.2	11350.00
30	40557.12	108.69	0.814	0.30 ( 0.28)	0.93	49332.4	11130.00
31	40148.87	114.76	0.791	0.30 ( 0.28)	0.93	52259.0	12300.00
32	39881.25	118.66	0.777	0.30 ( 0.28)	0.94	54319.8	11620.00

33	39369.61	123.54	0.764	0.30	( 0.28)	0.94	56519.6	12400.00
34	38321.07	133.05	0.744	0.30	( 0.28)	0.94	59921.1	12201.00
35	37349.03	140.54	0.728	0.30	( 0.28)	0.94	61814.2	12231.00
36	36343.70	148.02	0.712	0.30	( 0.28)	0.94	63366.9	10400.00
37	34780.59	157.47	0.691	0.30	( 0.28)	0.94	64813.3	12010.00
38	33735.64	162.86	0.680	0.30	( 0.28)	0.94	65075.9	10210.00
39	33062.42	166.91	0.671	0.30	( 0.28)	0.94	65222.7	12000.00
40	29359.64	193.27	0.630	0.30	( 0.28)	0.94	65835.7	10100.00

TOTAL AREA (ACRES) = 65835.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 40557.12 Tc (MIN.) = 108.686  
EFFECTIVE AREA (ACRES) = 49332.39 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.86  
TOTAL AREA (ACRES) = 65835.7  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124122.09 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13410.00 TO NODE 13412.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 178.72 DOWNSTREAM (FEET) = 176.93  
CHANNEL LENGTH THRU SUBAREA (FEET) = 169.78 CHANNEL SLOPE = 0.0105  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 8.69  
CHANNEL FLOW THRU SUBAREA (CFS) = 40557.12  
FLOW VELOCITY (FEET/SEC.) = 19.18 FLOW DEPTH (FEET) = 8.69  
TRAVEL TIME (MIN.) = 0.15 Tc (MIN.) = 108.83  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124291.87 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506101D.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	518.50	38.19	0.30 ( 0.30)	0.98	591.0	10100.00

TOTAL AREA (ACRES) = 591.0

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21255.43	15.14	2.396	0.30 ( 0.24)	0.81	3566.6	429.00
2	22491.04	16.55	2.280	0.30 ( 0.24)	0.81	4054.6	425.00
3	22766.73	16.95	2.247	0.30 ( 0.24)	0.81	4190.3	400.00
4	23455.54	18.37	2.131	0.30 ( 0.24)	0.81	4666.7	300.00
5	24743.05	21.93	1.898	0.30 ( 0.24)	0.81	5846.9	50700.00
6	25261.57	23.43	1.822	0.30 ( 0.24)	0.81	6322.0	210.00
7	25422.29	24.36	1.775	0.30 ( 0.24)	0.81	6607.1	50600.00
8	25710.79	25.51	1.721	0.30 ( 0.24)	0.81	6987.8	410.00
9	25974.51	26.55	1.677	0.30 ( 0.24)	0.81	7331.7	200.00
10	26115.91	27.10	1.653	0.30 ( 0.24)	0.81	7515.0	230.00
11	26165.70	27.31	1.644	0.30 ( 0.24)	0.81	7582.0	50500.00
12	26442.14	28.20	1.607	0.30 ( 0.24)	0.81	7867.5	220.50
13	26605.50	28.73	1.584	0.30 ( 0.24)	0.81	8038.5	110.00
14	27376.69	31.12	1.509	0.30 ( 0.24)	0.81	8843.0	100.00
15	27517.71	31.60	1.499	0.30 ( 0.24)	0.81	9000.2	110.00
16	27734.50	32.40	1.483	0.30 ( 0.24)	0.81	9351.2	100.00
17	28604.48	35.46	1.422	0.30 ( 0.24)	0.82	10683.7	130.00
18	30164.62	41.04	1.315	0.30 ( 0.25)	0.83	13095.2	150.00
19	31816.60	49.07	1.192	0.30 ( 0.25)	0.85	16788.4	20100.00
20	32401.69	52.14	1.151	0.30 ( 0.26)	0.85	18131.3	40200.00
21	32701.17	54.76	1.118	0.30 ( 0.26)	0.86	19482.5	13600.00
22	32829.63	55.86	1.104	0.30 ( 0.26)	0.86	20043.4	390.00
23	34550.64	68.58	1.004	0.30 ( 0.27)	0.88	26364.1	13100.00
24	35590.67	75.07	0.967	0.30 ( 0.27)	0.89	29193.0	11801.00
25	37542.98	85.66	0.907	0.30 ( 0.27)	0.90	34515.6	11530.00
26	38333.80	91.57	0.877	0.30 ( 0.27)	0.91	38252.6	13510.00
27	39062.28	97.27	0.856	0.30 ( 0.28)	0.92	41748.5	13010.00
28	39678.18	101.07	0.842	0.30 ( 0.28)	0.92	44200.5	13500.00
29	40170.92	104.14	0.831	0.30 ( 0.28)	0.93	46158.2	11350.00
30	40557.12	108.83	0.813	0.30 ( 0.28)	0.93	49332.4	11130.00
31	40148.87	114.91	0.791	0.30 ( 0.28)	0.93	52259.0	12300.00
32	39881.25	118.81	0.776	0.30 ( 0.28)	0.94	54319.8	11620.00
33	39369.61	123.68	0.764	0.30 ( 0.28)	0.94	56519.6	12400.00
34	38321.07	133.20	0.744	0.30 ( 0.28)	0.94	59921.1	12201.00
35	37349.03	140.69	0.728	0.30 ( 0.28)	0.94	61814.2	12231.00
36	36343.70	148.17	0.711	0.30 ( 0.28)	0.94	63366.9	10400.00
37	34780.59	157.62	0.691	0.30 ( 0.28)	0.94	64813.3	12010.00
38	33735.64	163.01	0.680	0.30 ( 0.28)	0.94	65075.9	10210.00
39	33062.42	167.07	0.671	0.30 ( 0.28)	0.94	65222.7	12000.00
40	29359.64	193.44	0.630	0.30 ( 0.28)	0.94	65835.7	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124291.87 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	518.50	38.19	1.367	0.30 ( 0.30)	0.98	591.0	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 14677.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21658.32	15.14	2.396	0.30 ( 0.25)	0.82	3800.9	429.00
2	22907.12	16.55	2.280	0.30 ( 0.25)	0.82	4310.7	425.00
3	23185.76	16.95	2.247	0.30 ( 0.25)	0.82	4452.6	400.00
4	23882.45	18.37	2.131	0.30 ( 0.25)	0.82	4950.9	300.00
5	25188.21	21.93	1.898	0.30 ( 0.25)	0.82	6186.3	50700.00

6	25714.52	23.43	1.822	0.30	( 0.24)	0.82	6684.5	210.00
7	25878.65	24.36	1.775	0.30	( 0.24)	0.82	6984.0	50600.00
8	26171.25	25.51	1.721	0.30	( 0.24)	0.82	7382.6	410.00
9	26438.99	26.55	1.677	0.30	( 0.24)	0.82	7742.5	200.00
10	26582.06	27.10	1.653	0.30	( 0.24)	0.82	7934.5	230.00
11	26632.39	27.31	1.644	0.30	( 0.24)	0.82	8004.7	50500.00
12	26910.62	28.20	1.607	0.30	( 0.24)	0.82	8303.8	220.50
13	27074.66	28.73	1.584	0.30	( 0.24)	0.82	8483.2	110.00
14	27854.94	31.12	1.509	0.30	( 0.25)	0.82	9324.6	100.00
15	27999.48	31.60	1.499	0.30	( 0.25)	0.82	9489.2	110.00
16	28221.88	32.40	1.483	0.30	( 0.25)	0.82	9852.6	100.00
17	29110.44	35.46	1.422	0.30	( 0.25)	0.82	11232.5	130.00
18	29885.95	38.19	1.367	0.30	( 0.25)	0.83	12454.0	10100.00
19	30657.91	41.04	1.315	0.30	( 0.25)	0.83	13686.2	150.00
20	32250.47	49.07	1.192	0.30	( 0.26)	0.85	17379.4	20100.00
21	32815.68	52.14	1.151	0.30	( 0.26)	0.86	18722.3	40200.00
22	33099.19	54.76	1.118	0.30	( 0.26)	0.86	20073.5	13600.00
23	33220.94	55.86	1.104	0.30	( 0.26)	0.86	20634.4	390.00
24	34893.33	68.58	1.004	0.30	( 0.27)	0.89	26955.1	13100.00
25	35915.68	75.07	0.967	0.30	( 0.27)	0.89	29784.0	11801.00
26	37839.13	85.66	0.907	0.30	( 0.27)	0.91	35106.6	11530.00
27	38615.34	91.57	0.877	0.30	( 0.27)	0.91	38843.6	13510.00
28	39333.61	97.27	0.856	0.30	( 0.28)	0.92	42339.5	13010.00
29	39942.71	101.07	0.842	0.30	( 0.28)	0.92	44791.5	13500.00
30	40429.96	104.14	0.831	0.30	( 0.28)	0.93	46749.2	11350.00
31	40807.76	108.83	0.813	0.30	( 0.28)	0.93	49923.4	11130.00
32	40388.64	114.91	0.791	0.30	( 0.28)	0.93	52850.0	12300.00
33	40114.04	118.81	0.776	0.30	( 0.28)	0.94	54910.8	11620.00
34	39596.45	123.68	0.764	0.30	( 0.28)	0.94	57110.6	12400.00
35	38538.01	133.20	0.744	0.30	( 0.28)	0.94	60512.1	12201.00
36	37558.18	140.69	0.728	0.30	( 0.28)	0.94	62405.2	12231.00
37	36545.06	148.17	0.711	0.30	( 0.28)	0.94	63957.9	10400.00
38	34972.14	157.62	0.691	0.30	( 0.28)	0.94	65404.3	12010.00
39	33921.58	163.01	0.680	0.30	( 0.28)	0.94	65666.9	10210.00
40	33244.15	167.07	0.671	0.30	( 0.28)	0.94	65813.7	12000.00
41	29521.75	193.44	0.630	0.30	( 0.28)	0.95	66426.7	10100.00

TOTAL AREA (ACRES) = 66426.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 40807.76 Tc (MIN.) = 108.834  
EFFECTIVE AREA (ACRES) = 49923.39 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA (ACRES) = 66426.7  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124291.87 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13412.00 TO NODE 13700.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<  
=====

ELEVATION DATA: UPSTREAM (FEET) = 176.93 DOWNSTREAM (FEET) = 173.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 260.10 CHANNEL SLOPE = 0.0151  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 7.86  
CHANNEL FLOW THRU SUBAREA (CFS) = 40807.76  
FLOW VELOCITY (FEET/SEC.) = 21.69 FLOW DEPTH (FEET) = 7.86

TRAVEL TIME (MIN.) = 0.20 Tc (MIN.) = 109.03  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124551.97 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 2 <<<<<  
=====

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 2 <<<<<  
=====

PEAK FLOWRATE TABLE FILE NAME: 0610508W.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	194.47	21.06	0.30 ( 0.30)	0.99	131.3	50800.00
TOTAL AREA (ACRES) =			131.3			

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<  
=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21658.32	15.39	2.376	0.30 ( 0.25)	0.82	3800.9	429.00
2	22907.12	16.80	2.260	0.30 ( 0.25)	0.82	4310.7	425.00
3	23185.76	17.19	2.227	0.30 ( 0.25)	0.82	4452.6	400.00
4	23882.45	18.61	2.111	0.30 ( 0.25)	0.82	4950.9	300.00
5	25188.21	22.17	1.886	0.30 ( 0.25)	0.82	6186.3	50700.00
6	25714.52	23.66	1.810	0.30 ( 0.24)	0.82	6684.5	210.00
7	25878.65	24.59	1.763	0.30 ( 0.24)	0.82	6984.0	50600.00
8	26171.25	25.74	1.711	0.30 ( 0.24)	0.82	7382.6	410.00
9	26438.99	26.78	1.667	0.30 ( 0.24)	0.82	7742.5	200.00
10	26582.06	27.34	1.643	0.30 ( 0.24)	0.82	7934.5	230.00
11	26632.39	27.55	1.635	0.30 ( 0.24)	0.82	8004.7	50500.00
12	26910.62	28.43	1.597	0.30 ( 0.24)	0.82	8303.8	220.50
13	27074.66	28.96	1.575	0.30 ( 0.24)	0.82	8483.2	110.00
14	27854.94	31.35	1.504	0.30 ( 0.25)	0.82	9324.6	100.00
15	27999.48	31.83	1.494	0.30 ( 0.25)	0.82	9489.2	110.00
16	28221.88	32.62	1.479	0.30 ( 0.25)	0.82	9852.6	100.00
17	29110.44	35.69	1.417	0.30 ( 0.25)	0.82	11232.5	130.00
18	29885.95	38.41	1.363	0.30 ( 0.25)	0.83	12454.0	10100.00
19	30657.91	41.26	1.312	0.30 ( 0.25)	0.83	13686.2	150.00
20	32250.47	49.29	1.189	0.30 ( 0.26)	0.85	17379.4	20100.00
21	32815.68	52.35	1.148	0.30 ( 0.26)	0.86	18722.3	40200.00
22	33099.19	54.97	1.115	0.30 ( 0.26)	0.86	20073.5	13600.00
23	33220.94	56.07	1.101	0.30 ( 0.26)	0.86	20634.4	390.00
24	34893.33	68.80	1.002	0.30 ( 0.27)	0.89	26955.1	13100.00
25	35915.68	75.28	0.966	0.30 ( 0.27)	0.89	29784.0	11801.00
26	37839.13	85.87	0.906	0.30 ( 0.27)	0.91	35106.6	11530.00
27	38615.34	91.77	0.876	0.30 ( 0.27)	0.91	38843.6	13510.00
28	39333.61	97.48	0.855	0.30 ( 0.28)	0.92	42339.5	13010.00

29	39942.71	101.28	0.841	0.30 ( 0.28)	0.92	44791.5	13500.00
30	40429.96	104.34	0.830	0.30 ( 0.28)	0.93	46749.2	11350.00
31	40807.76	109.03	0.813	0.30 ( 0.28)	0.93	49923.4	11130.00
32	40388.64	115.11	0.790	0.30 ( 0.28)	0.93	52850.0	12300.00
33	40114.04	119.01	0.776	0.30 ( 0.28)	0.94	54910.8	11620.00
34	39596.45	123.89	0.764	0.30 ( 0.28)	0.94	57110.6	12400.00
35	38538.01	133.41	0.743	0.30 ( 0.28)	0.94	60512.1	12201.00
36	37558.18	140.89	0.727	0.30 ( 0.28)	0.94	62405.2	12231.00
37	36545.06	148.38	0.711	0.30 ( 0.28)	0.94	63957.9	10400.00
38	34972.14	157.83	0.691	0.30 ( 0.28)	0.94	65404.3	12010.00
39	33921.58	163.23	0.679	0.30 ( 0.28)	0.94	65666.9	10210.00
40	33244.15	167.28	0.670	0.30 ( 0.28)	0.94	65813.7	12000.00
41	29521.75	193.66	0.630	0.30 ( 0.28)	0.95	66426.7	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124551.97 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	194.47	21.06	1.942	0.30 ( 0.30)	0.99	131.3	50800.00

LONGEST FLOWPATH FROM NODE 50800.00 TO NODE 13700.00 = 5946.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21837.89	15.39	2.376	0.30 ( 0.25)	0.83	3896.8	429.00
2	23092.18	16.80	2.260	0.30 ( 0.25)	0.82	4415.4	425.00
3	23372.03	17.19	2.227	0.30 ( 0.25)	0.82	4559.7	400.00
4	24071.88	18.61	2.111	0.30 ( 0.25)	0.82	5066.9	300.00
5	24974.73	21.06	1.942	0.30 ( 0.25)	0.82	5931.6	50800.00
6	25376.00	22.17	1.886	0.30 ( 0.25)	0.82	6317.6	50700.00
7	25893.37	23.66	1.810	0.30 ( 0.25)	0.82	6815.8	210.00
8	26051.91	24.59	1.763	0.30 ( 0.25)	0.82	7115.3	50600.00
9	26338.36	25.74	1.711	0.30 ( 0.25)	0.82	7513.9	410.00
10	26600.91	26.78	1.667	0.30 ( 0.25)	0.82	7873.8	200.00
11	26741.22	27.34	1.643	0.30 ( 0.25)	0.82	8065.7	230.00
12	26790.50	27.55	1.635	0.30 ( 0.25)	0.82	8136.0	50500.00
13	27064.34	28.43	1.597	0.30 ( 0.25)	0.82	8435.1	220.50
14	27225.70	28.96	1.575	0.30 ( 0.25)	0.82	8614.5	110.00
15	27997.62	31.35	1.504	0.30 ( 0.25)	0.82	9455.9	100.00
16	28141.03	31.83	1.494	0.30 ( 0.25)	0.82	9620.5	110.00
17	28361.55	32.62	1.479	0.30 ( 0.25)	0.82	9983.8	100.00
18	29242.87	35.69	1.417	0.30 ( 0.25)	0.83	11363.7	130.00
19	30011.94	38.41	1.363	0.30 ( 0.25)	0.83	12585.3	10100.00
20	30777.87	41.26	1.312	0.30 ( 0.25)	0.84	13817.5	150.00
21	32355.92	49.29	1.189	0.30 ( 0.26)	0.85	17510.7	20100.00
22	32916.34	52.35	1.148	0.30 ( 0.26)	0.86	18853.6	40200.00
23	33195.95	54.97	1.115	0.30 ( 0.26)	0.86	20204.8	13600.00
24	33316.06	56.07	1.101	0.30 ( 0.26)	0.86	20765.6	390.00
25	34976.75	68.80	1.002	0.30 ( 0.27)	0.89	27086.4	13100.00
26	35994.79	75.28	0.966	0.30 ( 0.27)	0.89	29915.3	11801.00
27	37911.19	85.87	0.906	0.30 ( 0.27)	0.91	35237.8	11530.00
28	38683.86	91.77	0.876	0.30 ( 0.27)	0.91	38974.9	13510.00
29	39399.64	97.48	0.855	0.30 ( 0.28)	0.92	42470.8	13010.00
30	40007.08	101.28	0.841	0.30 ( 0.28)	0.92	44922.8	13500.00
31	40492.99	104.34	0.830	0.30 ( 0.28)	0.93	46880.4	11350.00
32	40868.74	109.03	0.813	0.30 ( 0.28)	0.93	50054.7	11130.00
33	40446.96	115.11	0.790	0.30 ( 0.28)	0.93	52981.2	12300.00
34	40170.66	119.01	0.776	0.30 ( 0.28)	0.94	55042.1	11620.00

35	39651.64	123.89	0.764	0.30 ( 0.28)	0.94	57241.8	12400.00
36	38590.79	133.41	0.743	0.30 ( 0.28)	0.94	60643.4	12201.00
37	37609.06	140.89	0.727	0.30 ( 0.28)	0.94	62536.4	12231.00
38	36594.04	148.38	0.711	0.30 ( 0.28)	0.94	64089.2	10400.00
39	35018.71	157.83	0.691	0.30 ( 0.28)	0.94	65535.6	12010.00
40	33966.79	163.23	0.679	0.30 ( 0.28)	0.94	65798.2	10210.00
41	33288.32	167.28	0.670	0.30 ( 0.28)	0.94	65945.0	12000.00
42	29561.16	193.66	0.630	0.30 ( 0.28)	0.95	66557.9	10100.00

TOTAL AREA (ACRES) = 66557.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) =	40868.74	Tc (MIN.) =	109.033
EFFECTIVE AREA (ACRES) =	50054.65	AREA-AVERAGED Fm (INCH/HR) =	0.28
AREA-AVERAGED Fp (INCH/HR) =	0.30	AREA-AVERAGED Ap =	0.93
TOTAL AREA (ACRES) =	66557.9		
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 =	124551.97 FEET.		

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) =	66557.9	TC (MIN.) =	109.03
EFFECTIVE AREA (ACRES) =	50054.65	AREA-AVERAGED Fm (INCH/HR) =	0.28
AREA-AVERAGED Fp (INCH/HR) =	0.30	AREA-AVERAGED Ap =	0.931
PEAK FLOW RATE (CFS) =	40868.74		

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21837.89	15.39	2.376	0.30 ( 0.25)	0.83	3896.8	429.00
2	23092.18	16.80	2.260	0.30 ( 0.25)	0.82	4415.4	425.00
3	23372.03	17.19	2.227	0.30 ( 0.25)	0.82	4559.7	400.00
4	24071.88	18.61	2.111	0.30 ( 0.25)	0.82	5066.9	300.00
5	24974.73	21.06	1.942	0.30 ( 0.25)	0.82	5931.6	50800.00
6	25376.00	22.17	1.886	0.30 ( 0.25)	0.82	6317.6	50700.00
7	25893.37	23.66	1.810	0.30 ( 0.25)	0.82	6815.8	210.00
8	26051.91	24.59	1.763	0.30 ( 0.25)	0.82	7115.3	50600.00
9	26338.36	25.74	1.711	0.30 ( 0.25)	0.82	7513.9	410.00
10	26600.91	26.78	1.667	0.30 ( 0.25)	0.82	7873.8	200.00
11	26741.22	27.34	1.643	0.30 ( 0.25)	0.82	8065.7	230.00
12	26790.50	27.55	1.635	0.30 ( 0.25)	0.82	8136.0	50500.00
13	27064.34	28.43	1.597	0.30 ( 0.25)	0.82	8435.1	220.50
14	27225.70	28.96	1.575	0.30 ( 0.25)	0.82	8614.5	110.00
15	27997.62	31.35	1.504	0.30 ( 0.25)	0.82	9455.9	100.00
16	28141.03	31.83	1.494	0.30 ( 0.25)	0.82	9620.5	110.00
17	28361.55	32.62	1.479	0.30 ( 0.25)	0.82	9983.8	100.00
18	29242.87	35.69	1.417	0.30 ( 0.25)	0.83	11363.7	130.00
19	30011.94	38.41	1.363	0.30 ( 0.25)	0.83	12585.3	10100.00
20	30777.87	41.26	1.312	0.30 ( 0.25)	0.84	13817.5	150.00
21	32355.92	49.29	1.189	0.30 ( 0.26)	0.85	17510.7	20100.00
22	32916.34	52.35	1.148	0.30 ( 0.26)	0.86	18853.6	40200.00
23	33195.95	54.97	1.115	0.30 ( 0.26)	0.86	20204.8	13600.00
24	33316.06	56.07	1.101	0.30 ( 0.26)	0.86	20765.6	390.00
25	34976.75	68.80	1.002	0.30 ( 0.27)	0.89	27086.4	13100.00
26	35994.79	75.28	0.966	0.30 ( 0.27)	0.89	29915.3	11801.00
27	37911.19	85.87	0.906	0.30 ( 0.27)	0.91	35237.8	11530.00
28	38683.86	91.77	0.876	0.30 ( 0.27)	0.91	38974.9	13510.00
29	39399.64	97.48	0.855	0.30 ( 0.28)	0.92	42470.8	13010.00
30	40007.08	101.28	0.841	0.30 ( 0.28)	0.92	44922.8	13500.00
31	40492.99	104.34	0.830	0.30 ( 0.28)	0.93	46880.4	11350.00
32	40868.74	109.03	0.813	0.30 ( 0.28)	0.93	50054.7	11130.00



33	40446.96	115.11	0.790	0.30 ( 0.28)	0.93	52981.2	12300.00
34	40170.66	119.01	0.776	0.30 ( 0.28)	0.94	55042.1	11620.00
35	39651.64	123.89	0.764	0.30 ( 0.28)	0.94	57241.8	12400.00
36	38590.79	133.41	0.743	0.30 ( 0.28)	0.94	60643.4	12201.00
37	37609.06	140.89	0.727	0.30 ( 0.28)	0.94	62536.4	12231.00
38	36594.04	148.38	0.711	0.30 ( 0.28)	0.94	64089.2	10400.00
39	35018.71	157.83	0.691	0.30 ( 0.28)	0.94	65535.6	12010.00
40	33966.79	163.23	0.679	0.30 ( 0.28)	0.94	65798.2	10210.00
41	33288.32	167.28	0.670	0.30 ( 0.28)	0.94	65945.0	12000.00
42	29561.16	193.66	0.630	0.30 ( 0.28)	0.95	66557.9	10100.00

=====  
=====  
END OF RATIONAL METHOD ANALYSIS

\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S36- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 25-YR RM EV APRIL 2019 CCHIUI \*  
\*\*\*\*\*

FILE NAME: RI25EV36.DAT  
TIME/DATE OF STUDY: 09:51 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 25.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 4.766
- 2) 10.00; 3.119
- 3) 15.00; 2.394
- 4) 20.00; 1.986
- 5) 25.00; 1.734
- 6) 30.00; 1.526
- 7) 40.00; 1.325
- 8) 50.00; 1.173
- 9) 60.00; 1.046
- 10) 90.00; 0.877
- 11) 120.00; 0.765
- 12) 180.00; 0.636
- 13) 360.00; 0.466
- 14) 1200.00; 0.203

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13600.00 TO NODE 13600.50 IS CODE = 21  
-----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 488.61  
ELEVATION DATA: UPSTREAM(FEET) = 872.12 DOWNSTREAM(FEET) = 744.80

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 10.995  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.975  
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "OPEN BRUSH"	-	3.39	0.30	1.000	65	11.00

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA RUNOFF(CFS) = 8.16  
TOTAL AREA(ACRES) = 3.39 PEAK FLOW RATE(CFS) = 8.16

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13600.50 TO NODE 13601.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 744.80 DOWNSTREAM(FEET) = 707.32  
CHANNEL LENGTH THRU SUBAREA(FEET) = 418.30 CHANNEL SLOPE = 0.0896  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.41  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.706  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.45	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 16.25  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.77  
AVERAGE FLOW DEPTH(FEET) = 0.40 TRAVEL TIME(MIN.) = 1.85  
Tc(MIN.) = 12.85  
SUBAREA AREA(ACRES) = 7.45 SUBAREA RUNOFF(CFS) = 16.13  
EFFECTIVE AREA(ACRES) = 10.84 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 10.8 PEAK FLOW RATE(CFS) = 23.48  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.49

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.49 FLOW VELOCITY(FEET/SEC.) = 4.33  
LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13601.00 = 906.91 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13601.00 TO NODE 13602.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 707.32 DOWNSTREAM(FEET) = 657.12  
CHANNEL LENGTH THRU SUBAREA(FEET) = 777.60 CHANNEL SLOPE = 0.0646  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.91  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.364

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.32	0.30	1.000	-
USER-DEFINED	-	4.70	0.30	1.000	-
USER-DEFINED	-	25.05	0.30	1.000	-
USER-DEFINED	-	0.45	0.30	1.000	-
USER-DEFINED	-	0.44	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 52.31

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.14

AVERAGE FLOW DEPTH(FEET) = 0.87 TRAVEL TIME(MIN.) = 2.52

Tc(MIN.) = 15.37

SUBAREA AREA(ACRES) = 30.96 SUBAREA RUNOFF(CFS) = 57.52  
EFFECTIVE AREA(ACRES) = 41.80 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 41.8 PEAK FLOW RATE(CFS) = 77.65  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.09

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.09 FLOW VELOCITY(FEET/SEC.) = 5.82

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13602.00 = 1684.51 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13602.00 TO NODE 13603.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 657.12 DOWNSTREAM(FEET) = 584.58  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1186.54 CHANNEL SLOPE = 0.0611  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.28  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.102

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.03	0.30	1.000	-
USER-DEFINED	-	2.51	0.30	1.000	-

USER-DEFINED - 1.52 0.30 1.000 -  
USER-DEFINED - 12.30 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 96.62

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.15

AVERAGE FLOW DEPTH(FEET) = 1.26 TRAVEL TIME(MIN.) = 3.22

Tc(MIN.) = 18.58

SUBAREA AREA(ACRES) = 23.36 SUBAREA RUNOFF(CFS) = 37.88

EFFECTIVE AREA(ACRES) = 65.16 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 65.2 PEAK FLOW RATE(CFS) = 105.66

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.32

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.32 FLOW VELOCITY(FEET/SEC.) = 6.32

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13603.00 = 2871.05 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 584.58 DOWNSTREAM(FEET) = 544.91  
CHANNEL LENGTH THRU SUBAREA(FEET) = 860.98 CHANNEL SLOPE = 0.0461  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.56  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.937

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	10.22	0.30	1.000	-
USER-DEFINED	-	4.19	0.30	1.000	-
USER-DEFINED	-	0.07	0.30	1.000	-
USER-DEFINED	-	1.11	0.30	1.000	-
USER-DEFINED	-	5.56	0.30	1.000	-
USER-DEFINED	-	0.09	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 121.31

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.99

AVERAGE FLOW DEPTH(FEET) = 1.55 TRAVEL TIME(MIN.) = 2.39

Tc(MIN.) = 20.98

SUBAREA AREA(ACRES) = 21.24 SUBAREA RUNOFF(CFS) = 31.29

EFFECTIVE AREA(ACRES) = 86.40 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 86.4 PEAK FLOW RATE(CFS) = 127.28

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.59

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.59 FLOW VELOCITY(FEET/SEC.) = 6.07

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13620.00 = 3732.03 FEET.

```

*****
FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 10
-----
>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<
=====
*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13522.00 IS CODE = 15.1
-----
>>>>DEFINE MEMORY BANK # 2 <<<<<
=====
PEAK FLOWRATE TABLE FILE NAME: S35X25.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:
STREAM      Q      Tc      Fp(Fm)    Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR) (ACRES)  NODE
  1      1006.57  54.62  0.30( 0.28) 0.95  1513.9  13510.00
  2       918.88  63.50  0.30( 0.28) 0.94  1579.8  13500.00
TOTAL AREA(ACRES) = 1579.8

*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13522.00 IS CODE = 14.0
-----
>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<
=====
MAIN-STREAM MEMORY DEFINED AS FOLLOWS:
STREAM      Q      Tc      Fp(Fm)    Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR) (ACRES)  NODE
  1      1006.57  54.62  0.30( 0.28) 0.95  1513.9  13510.00
  2       918.88  63.50  0.30( 0.28) 0.94  1579.8  13500.00
TOTAL AREA(ACRES) = 1579.8

*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13620.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 632.19 DOWNSTREAM(FEET) = 544.91
CHANNEL LENGTH THRU SUBAREA(FEET) = 2062.96 CHANNEL SLOPE = 0.0423
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.32
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.077
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp      Ap      SCS
LAND USE              GROUP  (ACRES)  (INCH/HR) (DECIMAL) CN
USER-DEFINED          -      17.68    0.30    1.000  -
USER-DEFINED          -      2.36    0.30    1.000  -
USER-DEFINED          -      0.60    0.30    1.000  -
USER-DEFINED          -      0.22    0.30    1.000  -
USER-DEFINED          -      2.22    0.30    1.000  -
USER-DEFINED          -      3.42    0.30    1.000  -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1015.85
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.82

```

```

AVERAGE FLOW DEPTH(FEET) = 2.32 TRAVEL TIME(MIN.) = 2.91
Tc(MIN.) = 57.52
SUBAREA AREA(ACRES) = 26.50 SUBAREA RUNOFF(CFS) = 18.55
EFFECTIVE AREA(ACRES) = 1540.42 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
TOTAL AREA(ACRES) = 1606.3 PEAK FLOW RATE(CFS) = 1099.65
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.43

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 2.43 FLOW VELOCITY(FEET/SEC.) = 12.13
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

*****
FLOW PROCESS FROM NODE 13620.00 TO NODE 13620.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====
MAINLINE Tc(MIN.) = 57.52
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.077
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp      Ap      SCS
LAND USE              GROUP  (ACRES)  (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"WOODLAND,GRASS"      B      1.44    0.30    1.000  65
NATURAL FAIR COVER
"WOODLAND,GRASS"      B      0.01    0.30    1.000  65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 1.45 SUBAREA RUNOFF(CFS) = 1.01
EFFECTIVE AREA(ACRES) = 1541.87 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
TOTAL AREA(ACRES) = 1607.8 PEAK FLOW RATE(CFS) = 1100.66

*****
FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 11
-----
>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<
=====
** MAIN STREAM CONFLUENCE DATA **
STREAM      Q      Tc  Intensity  Fp(Fm)    Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.) (INCH/HR) (INCH/HR) (ACRES)  NODE
  1      1100.66  57.52  1.077  0.30( 0.28) 0.95  1541.9  13510.00
  2      1050.24  66.50  1.009  0.30( 0.28) 0.95  1607.8  13500.00
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

** MEMORY BANK # 1 CONFLUENCE DATA **
STREAM      Q      Tc  Intensity  Fp(Fm)    Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.) (INCH/HR) (INCH/HR) (ACRES)  NODE
  1      127.28  20.98  1.937  0.30( 0.30) 1.00    86.4  13600.00
LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13620.00 = 3732.03 FEET.

** PEAK FLOW RATE TABLE **
STREAM      Q      Tc  Intensity  Fp(Fm)    Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.) (INCH/HR) (INCH/HR) (ACRES)  NODE
  1      963.50  20.98  1.937  0.30( 0.29) 0.95    648.7  13600.00

```

2 1161.12 57.52 1.077 0.30( 0.29) 0.95 1628.3 13510.00  
 3 1105.40 66.50 1.009 0.30( 0.28) 0.95 1694.2 13500.00  
 TOTAL AREA(ACRES) = 1694.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 1161.12 Tc(MIN.) = 57.525  
 EFFECTIVE AREA(ACRES) = 1628.27 AREA-AVERAGED Fm(INCH/HR) = 0.29  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95  
 TOTAL AREA(ACRES) = 1694.2  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13620.00 TO NODE 13640.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 544.91 DOWNSTREAM(FEET) = 489.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1384.37 CHANNEL SLOPE = 0.0404  
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 2.57  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.053

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.39	0.30	1.000	-
USER-DEFINED	-	16.30	0.30	1.000	-
USER-DEFINED	-	4.08	0.30	1.000	-
USER-DEFINED	-	12.36	0.30	1.000	-
USER-DEFINED	-	11.23	0.30	1.000	-
USER-DEFINED	-	5.16	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1179.61  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.19  
 AVERAGE FLOW DEPTH(FEET) = 2.57 TRAVEL TIME(MIN.) = 1.89  
 Tc(MIN.) = 59.42

SUBAREA AREA(ACRES) = 54.52 SUBAREA RUNOFF(CFS) = 36.97  
 EFFECTIVE AREA(ACRES) = 1682.79 AREA-AVERAGED Fm(INCH/HR) = 0.29  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95  
 TOTAL AREA(ACRES) = 1748.7 PEAK FLOW RATE(CFS) = 1162.87  
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 2.54

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.54 FLOW VELOCITY(FEET/SEC.) = 12.15  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 59.42  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.053  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	53.93	0.30	1.000	-
USER-DEFINED	-	0.45	0.30	1.000	-
USER-DEFINED	-	3.98	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 58.36 SUBAREA RUNOFF(CFS) = 39.58  
 EFFECTIVE AREA(ACRES) = 1741.15 AREA-AVERAGED Fm(INCH/HR) = 0.29  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95  
 TOTAL AREA(ACRES) = 1807.1 PEAK FLOW RATE(CFS) = 1202.45

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: P201XX25.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	210.74	17.33	0.30( 0.26)	0.85	133.8	20100.00
TOTAL AREA(ACRES) =		133.8				

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1060.91	22.97	1.836	0.30( 0.29)	0.96	761.5	13600.00
2	1202.45	59.42	1.053	0.30( 0.29)	0.95	1741.1	13510.00
3	1159.89	68.42	0.999	0.30( 0.29)	0.95	1807.1	13500.00
LONGEST FLOWPATH FROM NODE		13500.00 TO NODE 13640.00 = 22062.09 FEET.					

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	210.74	17.33	2.204	0.30( 0.26)	0.85	133.8	20100.00
LONGEST FLOWPATH FROM NODE		20100.00 TO NODE 13640.00 = 5247.00 FEET.					

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1201.19	17.33	2.204	0.30( 0.28)	0.94	708.3	20100.00
2	1231.87	22.97	1.836	0.30( 0.28)	0.95	895.3	13600.00
3	1288.70	59.42	1.053	0.30( 0.28)	0.95	1874.9	13510.00
4	1240.21	68.42	0.999	0.30( 0.28)	0.94	1940.9	13500.00
TOTAL AREA(ACRES) =		1940.9					

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 1288.70 Tc(MIN.) = 59.417  
 EFFECTIVE AREA(ACRES) = 1874.95 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95  
 TOTAL AREA(ACRES) = 1940.9

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13640.00 TO NODE 13641.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 489.00 DOWNSTREAM(FEET) = 436.89  
CHANNEL LENGTH THRU SUBAREA(FEET) = 2994.52 CHANNEL SLOPE = 0.0174  
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 3.44

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.020

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.96	0.30	1.000	-
USER-DEFINED	-	0.01	0.30	1.000	-
USER-DEFINED	-	1.56	0.30	1.000	-
USER-DEFINED	-	10.45	0.30	1.000	-
USER-DEFINED	-	44.94	0.30	1.000	-
USER-DEFINED	-	9.66	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1310.59

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.46

AVERAGE FLOW DEPTH(FEET) = 3.44 TRAVEL TIME(MIN.) = 5.28

Tc(MIN.) = 64.70

SUBAREA AREA(ACRES) = 67.58 SUBAREA RUNOFF(CFS) = 43.77

EFFECTIVE AREA(ACRES) = 1942.53 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95

TOTAL AREA(ACRES) = 2008.4 PEAK FLOW RATE(CFS) = 1288.70

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 3.41

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 3.41 FLOW VELOCITY(FEET/SEC.) = 9.40

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13641.00 = 25056.61 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13641.00 TO NODE 13641.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 64.70

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.020

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	16.49	0.30	1.000	-
USER-DEFINED	-	20.39	0.30	1.000	-
USER-DEFINED	-	7.02	0.30	1.000	-
USER-DEFINED	-	12.58	0.30	1.000	-
USER-DEFINED	-	42.49	0.30	1.000	-
USER-DEFINED	-	5.73	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 104.70 SUBAREA RUNOFF(CFS) = 67.81

EFFECTIVE AREA(ACRES) = 2047.23 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95

TOTAL AREA(ACRES) = 2113.1 PEAK FLOW RATE(CFS) = 1352.90

\*\*\*\*\*

FLOW PROCESS FROM NODE 13641.00 TO NODE 13641.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 64.70

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.020

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.78	0.30	1.000	-
USER-DEFINED	-	6.25	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 8.03 SUBAREA RUNOFF(CFS) = 5.20

EFFECTIVE AREA(ACRES) = 2055.26 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95

TOTAL AREA(ACRES) = 2121.2 PEAK FLOW RATE(CFS) = 1358.10

\*\*\*\*\*

FLOW PROCESS FROM NODE 13641.00 TO NODE 13642.00 IS CODE = 56

ELEVATION DATA: UPSTREAM(FEET) = 436.89 DOWNSTREAM(FEET) = 394.80

CHANNEL LENGTH THRU SUBAREA(FEET) = 2814.16 CHANNEL SLOPE = 0.0150

GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 3.76

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.991

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.67	0.30	1.000	-
USER-DEFINED	-	24.24	0.30	1.000	-
USER-DEFINED	-	1.34	0.30	1.000	-
USER-DEFINED	-	74.98	0.30	1.000	-
USER-DEFINED	-	101.12	0.30	1.000	-
USER-DEFINED	-	16.90	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1426.27

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.20

AVERAGE FLOW DEPTH(FEET) = 3.76 TRAVEL TIME(MIN.) = 5.10

Tc(MIN.) = 69.79

SUBAREA AREA(ACRES) = 219.25 SUBAREA RUNOFF(CFS) = 136.33

EFFECTIVE AREA(ACRES) = 2274.51 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96

TOTAL AREA(ACRES) = 2340.4 PEAK FLOW RATE(CFS) = 1441.31

GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 3.78

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 3.78 FLOW VELOCITY (FEET/SEC.) = 9.23  
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13642.00 = 27870.77 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13642.00 TO NODE 13642.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

-----  
MAINLINE Tc (MIN.) = 69.79  
\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.991  
SUBAREA LOSS RATE DATA (AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 9.95 0.30 1.000 -  
USER-DEFINED - 10.02 0.30 1.000 -  
USER-DEFINED - 4.45 0.30 1.000 -  
USER-DEFINED - 179.37 0.30 1.000 -  
USER-DEFINED - 11.47 0.30 1.000 -  
USER-DEFINED - 0.17 0.30 0.850 -  
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 215.43 SUBAREA RUNOFF (CFS) = 133.96  
EFFECTIVE AREA (ACRES) = 2489.94 AREA-AVERAGED Fm (INCH/HR) = 0.29  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA (ACRES) = 2555.9 PEAK FLOW RATE (CFS) = 1575.27

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1578.91	27.83	1.616	0.30 (0.29)	0.97	1323.3	20100.00
2	1585.73	33.44	1.457	0.30 (0.29)	0.97	1510.3	13600.00
3	1575.27	69.79	0.991	0.30 (0.29)	0.96	2489.9	13510.00
4	1499.78	78.93	0.939	0.30 (0.29)	0.96	2555.9	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 1585.73 Tc (MIN.) = 33.44  
AREA-AVERAGED Fm (INCH/HR) = 0.29 AREA-AVERAGED Fp (INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.97 EFFECTIVE AREA (ACRES) = 1510.33

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13642.00 TO NODE 13642.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

-----  
MAINLINE Tc (MIN.) = 33.44  
\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.457  
SUBAREA LOSS RATE DATA (AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 0.03 0.30 0.850 -  
USER-DEFINED - 5.14 0.30 1.000 -  
USER-DEFINED - 11.22 0.30 1.000 -  
USER-DEFINED - 0.33 0.30 1.000 -  
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 16.72 SUBAREA RUNOFF (CFS) = 17.41  
EFFECTIVE AREA (ACRES) = 1527.05 AREA-AVERAGED Fm (INCH/HR) = 0.29  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97  
TOTAL AREA (ACRES) = 2572.6 PEAK FLOW RATE (CFS) = 1603.14

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13642.00 TO NODE 13643.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

-----  
ELEVATION DATA: UPSTREAM (FEET) = 394.80 DOWNSTREAM (FEET) = 342.39  
CHANNEL LENGTH THRU SUBAREA (FEET) = 2913.57 CHANNEL SLOPE = 0.0180  
GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 3.90  
\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.362  
SUBAREA LOSS RATE DATA (AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 0.22 0.30 1.000 -  
USER-DEFINED - 2.17 0.30 1.000 -  
USER-DEFINED - 9.19 0.30 1.000 -  
USER-DEFINED - 67.57 0.30 1.000 -  
USER-DEFINED - 35.19 0.30 1.000 -  
USER-DEFINED - 30.67 0.30 1.000 -

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 1672.45  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 10.30  
AVERAGE FLOW DEPTH (FEET) = 3.90 TRAVEL TIME (MIN.) = 4.72  
Tc (MIN.) = 38.16  
SUBAREA AREA (ACRES) = 145.01 SUBAREA RUNOFF (CFS) = 138.61  
EFFECTIVE AREA (ACRES) = 1672.06 AREA-AVERAGED Fm (INCH/HR) = 0.29  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97  
TOTAL AREA (ACRES) = 2717.6 PEAK FLOW RATE (CFS) = 1611.49  
GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 3.82

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 3.82 FLOW VELOCITY (FEET/SEC.) = 10.18  
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13643.00 = 30784.34 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1598.72	32.55	1.475	0.30 (0.29)	0.97	1485.0	20100.00
2	1611.49	38.16	1.362	0.30 (0.29)	0.97	1672.1	13600.00
3	1611.93	74.55	0.964	0.30 (0.29)	0.96	2651.7	13510.00
4	1526.38	83.75	0.912	0.30 (0.29)	0.96	2717.6	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 1611.93 Tc (MIN.) = 74.55  
AREA-AVERAGED Fm (INCH/HR) = 0.29 AREA-AVERAGED Fp (INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.96 EFFECTIVE AREA (ACRES) = 2651.67

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13643.00 TO NODE 13643.00 IS CODE = 81

=====  
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<  
=====

MAINLINE Tc(MIN.) = 74.55  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.964  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 0.89 0.30 1.000 -  
USER-DEFINED - 20.65 0.30 1.000 -  
USER-DEFINED - 2.69 0.30 1.000 -  
USER-DEFINED - 8.45 0.30 1.000 -  
USER-DEFINED - 96.93 0.30 1.000 -  
USER-DEFINED - 13.19 0.30 1.000 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA(ACRES) = 142.80 SUBAREA RUNOFF(CFS) = 85.35  
EFFECTIVE AREA(ACRES) = 2794.47 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA(ACRES) = 2860.4 PEAK FLOW RATE(CFS) = 1697.29

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1732.49	32.55	1.475	0.30( 0.29)	0.97	1627.8	20100.00
2	1747.99	38.16	1.362	0.30( 0.29)	0.97	1814.9	13600.00
3	1697.29	74.55	0.964	0.30( 0.29)	0.96	2794.5	13510.00
4	1605.07	83.75	0.912	0.30( 0.29)	0.96	2860.4	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 1747.99 Tc(MIN.) = 38.16  
AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.97 EFFECTIVE AREA(ACRES) = 1814.86

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13643.00 TO NODE 13643.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<  
=====

MAINLINE Tc(MIN.) = 38.16  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.362  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 42.54 0.30 1.000 -  
USER-DEFINED - 16.96 0.30 1.000 -  
USER-DEFINED - 80.60 0.30 1.000 -  
USER-DEFINED - 1.56 0.30 1.000 -  
USER-DEFINED - 2.00 0.30 1.000 -  
USER-DEFINED - 3.11 0.30 1.000 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA(ACRES) = 146.77 SUBAREA RUNOFF(CFS) = 140.30  
EFFECTIVE AREA(ACRES) = 1961.63 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98  
TOTAL AREA(ACRES) = 3007.2 PEAK FLOW RATE(CFS) = 1888.28

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13643.00 TO NODE 13660.00 IS CODE = 56  
-----

=====  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
=====

>>>>TRAVELTIME THRU SUBAREA<<<<  
=====

ELEVATION DATA: UPSTREAM(FEET) = 342.39 DOWNSTREAM(FEET) = 300.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1591.23 CHANNEL SLOPE = 0.0266  
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 3.77  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.320  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 0.89 0.30 1.000 -  
USER-DEFINED - 23.73 0.30 1.000 -  
USER-DEFINED - 0.27 0.30 1.000 -  
USER-DEFINED - 19.87 0.30 1.000 -  
USER-DEFINED - 6.40 0.30 1.000 -  
USER-DEFINED - 3.14 0.30 1.000 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1913.22  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.30  
AVERAGE FLOW DEPTH(FEET) = 3.77 TRAVEL TIME(MIN.) = 2.16  
Tc(MIN.) = 40.31  
SUBAREA AREA(ACRES) = 54.30 SUBAREA RUNOFF(CFS) = 49.86  
EFFECTIVE AREA(ACRES) = 2015.93 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98  
TOTAL AREA(ACRES) = 3061.5 PEAK FLOW RATE(CFS) = 1888.28  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 3.74

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 3.74 FLOW VELOCITY(FEET/SEC.) = 12.24  
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 32375.57 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1887.68	34.70	1.432	0.30( 0.29)	0.98	1828.9	20100.00
2	1888.28	40.31	1.320	0.30( 0.29)	0.98	2015.9	13600.00
3	1785.01	76.74	0.952	0.30( 0.29)	0.97	2995.5	13510.00
4	1685.95	85.99	0.900	0.30( 0.29)	0.96	3061.5	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 1888.28 Tc(MIN.) = 40.31  
AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.98 EFFECTIVE AREA(ACRES) = 2015.93

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<  
=====

MAINLINE Tc(MIN.) = 40.31  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.320  
SUBAREA LOSS RATE DATA(AMC II):



```

DEVELOPMENT TYPE/   SCS SOIL  AREA      Fp      Ap      SCS
LAND USE            GROUP  (ACRES)  (INCH/HR)  (DECIMAL)  CN
USER-DEFINED        -         0.67     0.30     1.000     -
USER-DEFINED        -         9.52     0.30     1.000     -
USER-DEFINED        -         0.71     0.30     1.000     -
USER-DEFINED        -         0.22     0.30     1.000     -
USER-DEFINED        -        39.42     0.30     1.000     -
USER-DEFINED        -         0.62     0.30     1.000     -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 51.16      SUBAREA RUNOFF (CFS) = 46.98
EFFECTIVE AREA (ACRES) = 2067.09  AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30  AREA-AVERAGED Ap = 0.98
TOTAL AREA (ACRES) = 3112.6      PEAK FLOW RATE (CFS) = 1911.34

```

```

** PEAK FLOW RATE TABLE **
STREAM      Q      Tc      Intensity  Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)  (MIN.)  (INCH/HR)  (INCH/HR)  (DECIMAL)  (ACRES)  NODE
1           1925.95  34.70   1.432     0.30( 0.29) 0.98   1880.1   20100.00
2           1911.34  40.31   1.320     0.30( 0.29) 0.98   2067.1   13600.00
3           1814.12  76.74   0.952     0.30( 0.29) 0.97   3046.7   13510.00
4           1708.80  85.99   0.900     0.30( 0.29) 0.97   3112.6   13500.00
NEW PEAK FLOW DATA ARE:
PEAK FLOW RATE (CFS) = 1925.95  Tc (MIN.) = 34.70
AREA-AVERAGED Fm (INCH/HR) = 0.29  AREA-AVERAGED Fp (INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.98  EFFECTIVE AREA (ACRES) = 1880.06

```

```

*****
FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc (MIN.) = 34.70
* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.432
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/   SCS SOIL  AREA      Fp      Ap      SCS
LAND USE            GROUP  (ACRES)  (INCH/HR)  (DECIMAL)  CN
USER-DEFINED        -         0.11     0.30     1.000     -
USER-DEFINED        -         0.77     0.30     1.000     -
USER-DEFINED        -         0.22     0.30     1.000     -
USER-DEFINED        -         2.69     0.30     1.000     -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA (ACRES) = 3.79      SUBAREA RUNOFF (CFS) = 3.86
EFFECTIVE AREA (ACRES) = 1883.85  AREA-AVERAGED Fm (INCH/HR) = 0.29
AREA-AVERAGED Fp (INCH/HR) = 0.30  AREA-AVERAGED Ap = 0.98
TOTAL AREA (ACRES) = 3116.4      PEAK FLOW RATE (CFS) = 1929.81

```

```

*****
FLOW PROCESS FROM NODE 13643.00 TO NODE 13660.00 IS CODE = 12
-----

```

```

>>>>CLEAR MEMORY BANK # 1 <<<<
=====

```

```

*****
FLOW PROCESS FROM NODE 13659.00 TO NODE 13659.00 IS CODE = 15.1
-----

```

```

>>>>DEFINE MEMORY BANK # 1 <<<<

```

```

=====
PEAK FLOWRATE TABLE FILE NAME: 2P25EVAA.DNA
MEMORY BANK # 1 DEFINED AS FOLLOWS:
STREAM      Q      Tc      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)  (MIN.)  (INCH/HR)  (DECIMAL)  (ACRES)  NODE
1           479.23   14.36   0.30( 0.11) 0.36   173.1   110.00
2           481.39   16.87   0.30( 0.11) 0.37   203.9   100.00
3           473.65   18.15   0.30( 0.11) 0.38   213.8   100.00
4           419.54   21.27   0.30( 0.12) 0.40   221.1   130.00
TOTAL AREA (ACRES) = 221.1

```

```

*****
FLOW PROCESS FROM NODE 13659.00 TO NODE 13660.00 IS CODE = 31
-----

```

```

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<
=====

```

```

ELEVATION DATA: UPSTREAM (FEET) = 338.00  DOWNSTREAM (FEET) = 300.00
FLOW LENGTH (FEET) = 881.07  MANNING'S N = 0.013
DEPTH OF FLOW IN 102.0 INCH PIPE IS 76.6 INCHES
PIPE-FLOW VELOCITY (FEET/SEC.) = 42.20
ESTIMATED PIPE DIAMETER (INCH) = 102.00  NUMBER OF PIPES = 1
PIPE-FLOW (CFS) = 1929.81
PIPE TRAVEL TIME (MIN.) = 0.35  Tc (MIN.) = 35.05
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 11
-----

```

```

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<
=====

```

```

** MAIN STREAM CONFLUENCE DATA **
STREAM      Q      Tc      Intensity  Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)  (MIN.)  (INCH/HR)  (INCH/HR)  (DECIMAL)  (ACRES)  NODE
1           1929.81  35.05   1.425     0.30( 0.29) 0.98   1883.8   20100.00
2           1914.82  40.66   1.315     0.30( 0.29) 0.98   2070.9   13600.00
3           1816.34  77.09   0.950     0.30( 0.29) 0.97   3050.5   13510.00
4           1710.85  86.35   0.898     0.30( 0.29) 0.97   3116.4   13500.00
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

```

```

** MEMORY BANK # 1 CONFLUENCE DATA **
STREAM      Q      Tc      Intensity  Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)  (MIN.)  (INCH/HR)  (INCH/HR)  (DECIMAL)  (ACRES)  NODE
1           479.23   14.36   2.487     0.30( 0.11) 0.36   173.1   110.00
2           481.39   16.87   2.242     0.30( 0.11) 0.37   203.9   100.00
3           473.65   18.15   2.137     0.30( 0.11) 0.38   213.8   100.00
4           419.54   21.27   1.922     0.30( 0.12) 0.40   221.1   130.00
LONGEST FLOWPATH FROM NODE 130.00 TO NODE 13660.00 = 6327.50 FEET.

```

```

** PEAK FLOW RATE TABLE **
STREAM      Q      Tc      Intensity  Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)  (MIN.)  (INCH/HR)  (INCH/HR)  (DECIMAL)  (ACRES)  NODE
1           2012.39  14.36   2.487     0.30( 0.26) 0.87   945.0   110.00
2           2080.98  16.87   2.242     0.30( 0.26) 0.87   1110.5   100.00
3           2102.39  18.15   2.137     0.30( 0.26) 0.87   1189.4   100.00
4           2105.76  21.27   1.922     0.30( 0.27) 0.88   1364.4   130.00
5           2233.52  35.05   1.425     0.30( 0.28) 0.92   2104.9   20100.00

```

6 2193.00 40.66 1.315 0.30( 0.28) 0.92 2292.0 13600.00  
 7 2009.48 77.09 0.950 0.30( 0.28) 0.93 3271.6 13510.00  
 8 1891.84 86.35 0.898 0.30( 0.28) 0.93 3337.5 13500.00  
 TOTAL AREA (ACRES) = 3337.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 2233.52 Tc (MIN.) = 35.049  
 EFFECTIVE AREA (ACRES) = 2104.95 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.87  
 TOTAL AREA (ACRES) = 3337.5  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 35.05  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.425  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "FALLOW"	B	1.11	0.30	1.000	86
AGRICULTURAL POOR COVER "FALLOW"	B	0.44	0.30	1.000	86
NATURAL FAIR COVER "GRASS"	B	1.49	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	1.70	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	1.09	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	18.57	0.30	1.000	66

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 24.40 SUBAREA RUNOFF (CFS) = 24.69  
 EFFECTIVE AREA (ACRES) = 2129.35 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA (ACRES) = 3361.9 PEAK FLOW RATE (CFS) = 2233.52  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 35.05  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.425  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL FAIR COVER "ORCHARDS"	B	12.39	0.30	1.000	65
AGRICULTURAL FAIR COVER "ORCHARDS"	B	2.30	0.30	1.000	65
AGRICULTURAL POOR COVER "ROW CROPS, CONTOURED"	B	5.19	0.30	1.000	79

AGRICULTURAL POOR COVER  
 "ROW CROPS, STRAIGHT ROW" B 28.71 0.30 1.000 81  
 NATURAL FAIR COVER  
 "WOODLAND, GRASS" B 0.17 0.30 1.000 65  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 48.76 SUBAREA RUNOFF (CFS) = 49.35  
 EFFECTIVE AREA (ACRES) = 2178.11 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA (ACRES) = 3410.7 PEAK FLOW RATE (CFS) = 2251.51

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13660.00 TO NODE 13680.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 300.00 DOWNSTREAM (FEET) = 288.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 933.89 CHANNEL SLOPE = 0.0128  
 GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 5.02  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.393  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	9.23	0.30	1.000	-
USER-DEFINED	-	0.54	0.30	1.000	-
USER-DEFINED	-	5.66	0.30	1.000	-
USER-DEFINED	-	3.66	0.30	1.000	-
USER-DEFINED	-	0.67	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 2261.34  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 10.00  
 AVERAGE FLOW DEPTH (FEET) = 5.02 TRAVEL TIME (MIN.) = 1.56  
 Tc (MIN.) = 36.60  
 SUBAREA AREA (ACRES) = 19.98 SUBAREA RUNOFF (CFS) = 19.66  
 EFFECTIVE AREA (ACRES) = 2198.09 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA (ACRES) = 3430.6 PEAK FLOW RATE (CFS) = 2251.51  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 5.01

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 5.01 FLOW VELOCITY (FEET/SEC.) = 9.99  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13680.00 = 34190.53 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2038.12	15.96	2.316	0.30( 0.26)	0.88	1038.1	110.00
2	2108.29	18.45	2.112	0.30( 0.26)	0.88	1203.7	100.00
3	2128.99	19.73	2.008	0.30( 0.26)	0.88	1282.5	100.00
4	2141.14	22.85	1.842	0.30( 0.27)	0.89	1457.6	130.00

5	2251.51	36.60	1.393	0.30	( 0.28)	0.92	2198.1	20100.00
6	2209.48	42.23	1.291	0.30	( 0.28)	0.92	2385.1	13600.00
7	2018.73	78.70	0.941	0.30	( 0.28)	0.93	3364.7	13510.00
8	1899.14	87.98	0.888	0.30	( 0.28)	0.93	3430.6	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2251.51 Tc(MIN.) = 36.60  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.92 EFFECTIVE AREA(ACRES) = 2198.09

\*\*\*\*\*

FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 36.60

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.393

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.56	0.30	1.000	-
USER-DEFINED	-	9.40	0.30	1.000	-
USER-DEFINED	-	2.76	0.30	1.000	-
USER-DEFINED	-	17.38	0.30	1.000	-
USER-DEFINED	-	2.46	0.30	1.000	-
USER-DEFINED	-	5.56	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 39.12 SUBAREA RUNOFF(CFS) = 38.49

EFFECTIVE AREA(ACRES) = 2237.21 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92

TOTAL AREA(ACRES) = 3469.8 PEAK FLOW RATE(CFS) = 2251.51

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 36.60

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.393

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.65	0.30	1.000	-
USER-DEFINED	-	1.70	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 2.35 SUBAREA RUNOFF(CFS) = 2.31

EFFECTIVE AREA(ACRES) = 2239.56 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92

TOTAL AREA(ACRES) = 3472.1 PEAK FLOW RATE(CFS) = 2251.51

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13660.00 TO NODE 13680.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 36.60

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.393

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.29	0.30	1.000	-
USER-DEFINED	-	31.25	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	6.26	0.30	1.000	-
USER-DEFINED	-	0.07	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 43.31 SUBAREA RUNOFF(CFS) = 42.62

EFFECTIVE AREA(ACRES) = 2282.87 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92

TOTAL AREA(ACRES) = 3515.4 PEAK FLOW RATE(CFS) = 2293.29

\*\*\*\*\*

FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 36.60

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.393

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	2.47	0.30	0.850	-
USER-DEFINED	-	3.06	0.30	0.850	-
USER-DEFINED	-	17.76	0.30	0.500	-
USER-DEFINED	-	7.31	0.30	0.500	-
USER-DEFINED	-	0.34	0.30	1.000	-
USER-DEFINED	-	8.22	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.659

SUBAREA AREA(ACRES) = 39.16 SUBAREA RUNOFF(CFS) = 42.14

EFFECTIVE AREA(ACRES) = 2322.03 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92

TOTAL AREA(ACRES) = 3554.6 PEAK FLOW RATE(CFS) = 2335.43

\*\*\*\*\*

FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 36.60

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.393

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.53	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 0.53 SUBAREA RUNOFF(CFS) = 0.52  
 EFFECTIVE AREA(ACRES) = 2322.56 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 3555.1 PEAK FLOW RATE(CFS) = 2335.96

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13680.00 TO NODE 13682.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 288.00 DOWNSTREAM(FEET) = 242.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2860.77 CHANNEL SLOPE = 0.0161  
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 4.82  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.310

SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	5.28	0.30	1.000	-
USER-DEFINED	-	0.52	0.30	1.000	-
USER-DEFINED	-	3.61	0.30	1.000	-
USER-DEFINED	-	0.67	0.30	1.000	-
USER-DEFINED	-	1.37	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2341.26  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.93  
 AVERAGE FLOW DEPTH(FEET) = 4.82 TRAVEL TIME(MIN.) = 4.36  
 Tc(MIN.) = 40.96  
 SUBAREA AREA(ACRES) = 11.67 SUBAREA RUNOFF(CFS) = 10.61  
 EFFECTIVE AREA(ACRES) = 2334.23 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 3566.8 PEAK FLOW RATE(CFS) = 2335.96

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 4.81  
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 4.81 FLOW VELOCITY(FEET/SEC.) = 10.93  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13682.00 = 37051.30 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2146.96	20.42	1.965	0.30( 0.26)	0.88	1174.3	110.00
2	2209.71	22.88	1.841	0.30( 0.26)	0.88	1339.8	100.00
3	2208.12	24.16	1.776	0.30( 0.26)	0.88	1418.7	100.00
4	2242.47	27.26	1.640	0.30( 0.27)	0.89	1593.7	130.00
5	2335.96	40.96	1.310	0.30( 0.28)	0.92	2334.2	20100.00
6	2291.37	46.61	1.225	0.30( 0.28)	0.92	2521.3	13600.00
7	2078.40	83.21	0.915	0.30( 0.28)	0.93	3500.9	13510.00
8	1950.98	92.58	0.867	0.30( 0.28)	0.93	3566.8	13500.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE(CFS) = 2335.96 Tc(MIN.) = 40.96  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.92 EFFECTIVE AREA(ACRES) = 2334.23

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 40.96  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.310  
 SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	6.90	0.30	1.000	-
USER-DEFINED	-	23.04	0.30	1.000	-
USER-DEFINED	-	1.18	0.30	1.000	-
USER-DEFINED	-	1.56	0.30	1.000	-
USER-DEFINED	-	53.20	0.30	1.000	-
USER-DEFINED	-	2.08	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 87.96 SUBAREA RUNOFF(CFS) = 79.99  
 EFFECTIVE AREA(ACRES) = 2422.19 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 3654.7 PEAK FLOW RATE(CFS) = 2335.96  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 40.96  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.310  
 SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.01	0.30	1.000	-
USER-DEFINED	-	0.18	0.30	1.000	-
USER-DEFINED	-	0.38	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	7.73	0.30	1.000	-
USER-DEFINED	-	4.37	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 12.89 SUBAREA RUNOFF(CFS) = 11.72  
 EFFECTIVE AREA(ACRES) = 2435.08 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 3667.6 PEAK FLOW RATE(CFS) = 2335.96  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 40.96  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.310  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "FALLOW"	B	2.57	0.30	1.000	86
AGRICULTURAL POOR COVER "FALLOW"	B	1.97	0.30	1.000	86
NATURAL FAIR COVER "GRASS"	B	1.00	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	2.98	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	2.39	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	1.67	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 12.58 SUBAREA RUNOFF(CFS) = 11.44  
 EFFECTIVE AREA(ACRES) = 2447.66 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 3680.2 PEAK FLOW RATE(CFS) = 2335.96  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 40.96  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.310  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	0.44	0.30	1.000	66
PUBLIC PARK	B	2.65	0.30	0.850	56
PUBLIC PARK	B	1.16	0.30	0.850	56
RESIDENTIAL "5-7 DWELLINGS/ACRE"	B	0.47	0.30	0.500	56
RESIDENTIAL "5-7 DWELLINGS/ACRE"	B	0.25	0.30	0.500	56
AGRICULTURAL POOR COVER "ROW CROPS,STRAIGHT ROW"	B	20.24	0.30	1.000	81

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.963  
 SUBAREA AREA(ACRES) = 25.21 SUBAREA RUNOFF(CFS) = 23.17  
 EFFECTIVE AREA(ACRES) = 2472.87 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 3705.4 PEAK FLOW RATE(CFS) = 2335.96  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 40.96  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.310  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.08	0.30	1.000	-
USER-DEFINED	-	6.75	0.30	1.000	-
USER-DEFINED	-	0.02	0.30	1.000	-
USER-DEFINED	-	0.93	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 14.78 SUBAREA RUNOFF(CFS) = 13.44  
 EFFECTIVE AREA(ACRES) = 2487.65 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 3720.2 PEAK FLOW RATE(CFS) = 2335.96  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13682.00 TO NODE 13683.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 242.00 DOWNSTREAM(FEET) = 208.53  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2526.22 CHANNEL SLOPE = 0.0132  
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 5.09  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.248  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.49	0.30	1.000	-
USER-DEFINED	-	13.31	0.30	1.000	-
USER-DEFINED	-	0.87	0.30	1.000	-
USER-DEFINED	-	20.26	0.30	1.000	-
USER-DEFINED	-	1.21	0.30	1.000	-
USER-DEFINED	-	0.05	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2354.81  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.24  
 AVERAGE FLOW DEPTH(FEET) = 5.08 TRAVEL TIME(MIN.) = 4.11  
 Tc(MIN.) = 45.08  
 SUBAREA AREA(ACRES) = 44.19 SUBAREA RUNOFF(CFS) = 37.70  
 EFFECTIVE AREA(ACRES) = 2531.84 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 3764.4 PEAK FLOW RATE(CFS) = 2335.96  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 5.06

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 5.06 FLOW VELOCITY(FEET/SEC.) = 10.21  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13683.00 = 39577.52 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2146.96	24.64	1.752	0.30( 0.27)	0.90	1371.9	110.00
2	2209.71	27.06	1.648	0.30( 0.27)	0.89	1537.4	100.00
3	2208.12	28.34	1.595	0.30( 0.27)	0.90	1616.3	100.00
4	2242.47	31.42	1.497	0.30( 0.27)	0.90	1791.3	130.00
5	2335.96	45.08	1.248	0.30( 0.28)	0.93	2531.8	20100.00
6	2291.37	50.75	1.164	0.30( 0.28)	0.93	2718.9	13600.00
7	2090.26	87.46	0.891	0.30( 0.28)	0.93	3698.5	13510.00
8	1968.40	96.91	0.851	0.30( 0.28)	0.93	3764.4	13500.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE(CFS) = 2335.96 Tc(MIN.) = 45.08  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 2531.84

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 =====

MAINLINE Tc(MIN.) = 45.08  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.248  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ LAND USE SCS SOIL GROUP AREA (ACRES) Fp (INCH/HR) Ap (DECIMAL) SCS CN  
 USER-DEFINED - 12.56 0.30 1.000 -  
 USER-DEFINED - 0.81 0.30 1.000 -  
 USER-DEFINED - 0.01 0.30 1.000 -  
 USER-DEFINED - 1.11 0.30 1.000 -  
 USER-DEFINED - 0.59 0.30 1.000 -  
 USER-DEFINED - 3.04 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 18.12 SUBAREA RUNOFF(CFS) = 15.46  
 EFFECTIVE AREA(ACRES) = 2549.96 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 3782.5 PEAK FLOW RATE(CFS) = 2335.96  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 =====

MAINLINE Tc(MIN.) = 45.08  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.248  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ LAND USE SCS SOIL GROUP AREA (ACRES) Fp (INCH/HR) Ap (DECIMAL) SCS CN  
 RESIDENTIAL  
 "8-10 DWELLINGS/ACRE" B 0.10 0.30 0.400 56  
 PUBLIC PARK B 1.30 0.30 0.850 56  
 RESIDENTIAL  
 "8-10 DWELLINGS/ACRE" B 0.10 0.30 0.400 56  
 PUBLIC PARK B 1.70 0.30 0.850 56  
 PUBLIC PARK B 0.10 0.30 0.850 56  
 PUBLIC PARK B 2.90 0.30 0.850 56  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.835  
 SUBAREA AREA(ACRES) = 6.20 SUBAREA RUNOFF(CFS) = 5.56  
 EFFECTIVE AREA(ACRES) = 2556.16 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 3788.7 PEAK FLOW RATE(CFS) = 2335.96  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 =====

MAINLINE Tc(MIN.) = 45.08  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.248  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ LAND USE SCS SOIL GROUP AREA (ACRES) Fp (INCH/HR) Ap (DECIMAL) SCS CN  
 RESIDENTIAL  
 "5-7 DWELLINGS/ACRE" B 0.10 0.30 0.500 56  
 CONDOMINIUMS B 0.10 0.30 0.350 56  
 PUBLIC PARK B 6.90 0.30 0.850 56  
 PUBLIC PARK B 0.40 0.30 0.850 56  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.839  
 SUBAREA AREA(ACRES) = 7.50 SUBAREA RUNOFF(CFS) = 6.72  
 EFFECTIVE AREA(ACRES) = 2563.66 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 3796.2 PEAK FLOW RATE(CFS) = 2335.96  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13682.00 TO NODE 13683.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 3 <<<<<  
 =====

\*\*\*MEMORY BANK # 3 IS EMPTY - PROCESS IGNORED.\*\*\*  
 =====

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 =====

MAINLINE Tc(MIN.) = 45.08  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.248  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ LAND USE SCS SOIL GROUP AREA (ACRES) Fp (INCH/HR) Ap (DECIMAL) SCS CN  
 AGRICULTURAL POOR COVER  
 "FALLOW" B 2.55 0.30 1.000 86  
 AGRICULTURAL POOR COVER  
 "FALLOW" B 0.01 0.30 1.000 86  
 AGRICULTURAL POOR COVER  
 "FALLOW" B 1.35 0.30 1.000 86  
 NATURAL FAIR COVER  
 "GRASS" B 0.44 0.30 1.000 69  
 NATURAL FAIR COVER  
 "GRASS" B 0.67 0.30 1.000 69  
 NATURAL FAIR COVER

"OPEN BRUSH" B 1.06 0.30 1.000 66  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 6.08 SUBAREA RUNOFF (CFS) = 5.19  
 EFFECTIVE AREA (ACRES) = 2569.74 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 3802.3 PEAK FLOW RATE (CFS) = 2335.96  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 45.08  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.248  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 2.16 0.30 1.000 66  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 2.45 0.30 1.000 66  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 6.15 0.30 1.000 66  
 AGRICULTURAL POOR COVER  
 "ROW CROPS, STRAIGHT ROW" B 1.34 0.30 1.000 81  
 AGRICULTURAL POOR COVER  
 "ROW CROPS, STRAIGHT ROW" B 18.46 0.30 1.000 81  
 AGRICULTURAL POOR COVER  
 "ROW CROPS, STRAIGHT ROW" B 4.13 0.30 1.000 81  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 34.69 SUBAREA RUNOFF (CFS) = 29.59  
 EFFECTIVE AREA (ACRES) = 2604.43 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 3837.0 PEAK FLOW RATE (CFS) = 2335.96  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 45.08  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.248  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 AGRICULTURAL POOR COVER  
 "ROW CROPS, STRAIGHT ROW" B 8.69 0.30 1.000 81  
 NATURAL FAIR COVER  
 "WOODLAND, GRASS" B 0.73 0.30 1.000 65  
 NATURAL FAIR COVER  
 "WOODLAND, GRASS" B 0.41 0.30 1.000 65  
 NATURAL FAIR COVER  
 "WOODLAND, GRASS" B 1.37 0.30 1.000 65  
 NATURAL FAIR COVER

"WOODLAND, GRASS" B 3.11 0.30 1.000 65  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 14.31 SUBAREA RUNOFF (CFS) = 12.21  
 EFFECTIVE AREA (ACRES) = 2618.74 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 3851.3 PEAK FLOW RATE (CFS) = 2335.96  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13683.00 TO NODE 13685.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 208.53 DOWNSTREAM (FEET) = 194.24  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 289.01 CHANNEL SLOPE = 0.0494  
 GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 3.54  
 CHANNEL FLOW THRU SUBAREA (CFS) = 2335.96  
 FLOW VELOCITY (FEET/SEC.) = 16.22 FLOW DEPTH (FEET) = 3.54  
 TRAVEL TIME (MIN.) = 0.30 Tc (MIN.) = 45.38  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13685.00 = 39866.53 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2146.96	24.94	1.737	0.30 ( 0.27)	0.90	1458.8	110.00
2	2209.71	27.36	1.636	0.30 ( 0.27)	0.90	1624.3	100.00
3	2208.12	28.64	1.583	0.30 ( 0.27)	0.90	1703.2	100.00
4	2242.47	31.72	1.491	0.30 ( 0.27)	0.91	1878.2	130.00
5	2335.96	45.38	1.243	0.30 ( 0.28)	0.93	2618.7	20100.00
6	2291.37	51.04	1.160	0.30 ( 0.28)	0.93	2805.8	13600.00
7	2090.26	87.77	0.890	0.30 ( 0.28)	0.93	3785.4	13510.00
8	1979.94	97.22	0.850	0.30 ( 0.28)	0.93	3851.3	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 2335.96 Tc (MIN.) = 45.38  
 AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA (ACRES) = 2618.74

\*\*\*\*\*

FLOW PROCESS FROM NODE 13685.00 TO NODE 13410.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 194.24 DOWNSTREAM (FEET) = 178.72  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1843.57 CHANNEL SLOPE = 0.0084  
 GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 5.71  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.190  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 0.23 0.30 1.000 -  
 USER-DEFINED - 1.52 0.30 1.000 -

USER-DEFINED - 0.06 0.30 1.000 -  
 USER-DEFINED - 0.13 0.30 1.000 -  
 USER-DEFINED - 6.45 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2339.32  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.69  
 AVERAGE FLOW DEPTH(FEET) = 5.71 TRAVEL TIME(MIN.) = 3.54  
 Tc(MIN.) = 48.91  
 SUBAREA AREA(ACRES) = 8.39 SUBAREA RUNOFF(CFS) = 6.72  
 EFFECTIVE AREA(ACRES) = 2627.13 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 3859.7 PEAK FLOW RATE(CFS) = 2335.96  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 5.70

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 5.70 FLOW VELOCITY(FEET/SEC.) = 8.69  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13410.00 = 41710.10 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2146.96	28.56	1.586	0.30( 0.27)	0.90	1467.2	110.00
2	2209.71	30.95	1.507	0.30( 0.27)	0.90	1632.7	100.00
3	2208.12	32.23	1.481	0.30( 0.27)	0.90	1711.6	100.00
4	2242.47	35.30	1.420	0.30( 0.27)	0.91	1886.6	130.00
5	2335.96	48.91	1.190	0.30( 0.28)	0.93	2627.1	20100.00
6	2291.37	54.60	1.115	0.30( 0.28)	0.93	2814.2	13600.00
7	2090.26	91.42	0.872	0.30( 0.28)	0.93	3793.8	13510.00
8	1979.94	100.93	0.836	0.30( 0.28)	0.93	3859.7	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2335.96 Tc(MIN.) = 48.91  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 2627.13

=====  
 END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 3859.7 TC(MIN.) = 48.91  
 EFFECTIVE AREA(ACRES) = 2627.13 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.927  
 PEAK FLOW RATE(CFS) = 2335.96

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2146.96	28.56	1.586	0.30( 0.27)	0.90	1467.2	110.00
2	2209.71	30.95	1.507	0.30( 0.27)	0.90	1632.7	100.00
3	2208.12	32.23	1.481	0.30( 0.27)	0.90	1711.6	100.00
4	2242.47	35.30	1.420	0.30( 0.27)	0.91	1886.6	130.00
5	2335.96	48.91	1.190	0.30( 0.28)	0.93	2627.1	20100.00
6	2291.37	54.60	1.115	0.30( 0.28)	0.93	2814.2	13600.00
7	2090.26	91.42	0.872	0.30( 0.28)	0.93	3793.8	13510.00
8	1979.94	100.93	0.836	0.30( 0.28)	0.93	3859.7	13500.00

=====  
 END OF RATIONAL METHOD ANALYSIS





\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S37- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 25-YR RM EV APRIL 2019 CCHIUI \*  
\*\*\*\*\*

FILE NAME: RI25EV37.DAT  
TIME/DATE OF STUDY: 09:55 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 25.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 4.753
- 2) 10.00; 3.112
- 3) 15.00; 2.390
- 4) 20.00; 1.984
- 5) 25.00; 1.732
- 6) 30.00; 1.524
- 7) 40.00; 1.323
- 8) 50.00; 1.171
- 9) 60.00; 1.045
- 10) 90.00; 0.875
- 11) 120.00; 0.763
- 12) 180.00; 0.634
- 13) 360.00; 0.464
- 14) 1200.00; 0.203

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI25EV34.DNA  
MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25376.00	22.17	0.30 ( 0.25)	0.82	6317.6	50700.00
2	28361.55	32.62	0.30 ( 0.25)	0.82	9983.8	100.00
3	30777.87	41.26	0.30 ( 0.25)	0.84	13817.5	150.00
4	33316.06	56.07	0.30 ( 0.26)	0.86	20765.6	390.00
5	34976.75	68.80	0.30 ( 0.27)	0.89	27086.4	13100.00
6	35994.79	75.28	0.30 ( 0.27)	0.89	29915.3	11801.00
7	37911.19	85.87	0.30 ( 0.27)	0.91	35237.8	11530.00
8	38683.86	91.77	0.30 ( 0.27)	0.91	38974.9	13510.00
9	39399.64	97.48	0.30 ( 0.28)	0.92	42470.8	13010.00
10	40492.99	104.34	0.30 ( 0.28)	0.93	46880.4	11350.00
11	40868.74	109.03	0.30 ( 0.28)	0.93	50054.7	11130.00
12	40446.96	115.11	0.30 ( 0.28)	0.93	52981.2	12300.00
13	39651.64	123.89	0.30 ( 0.28)	0.94	57241.8	12400.00
14	38590.79	133.41	0.30 ( 0.28)	0.94	60643.4	12201.00
15	37609.06	140.89	0.30 ( 0.28)	0.94	62536.4	12231.00
16	36594.04	148.38	0.30 ( 0.28)	0.94	64089.2	10400.00
17	35018.71	157.83	0.30 ( 0.28)	0.94	65535.6	12010.00
18	33966.79	163.23	0.30 ( 0.28)	0.94	65798.2	10210.00
19	33288.32	167.28	0.30 ( 0.28)	0.94	65945.0	12000.00
20	29561.16	193.66	0.30 ( 0.28)	0.95	66557.9	10100.00
TOTAL AREA(ACRES) =						66557.9

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 3 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25376.00	22.17	0.30 ( 0.25)	0.82	6317.6	50700.00
2	28361.55	32.62	0.30 ( 0.25)	0.82	9983.8	100.00
3	30777.87	41.26	0.30 ( 0.25)	0.84	13817.5	150.00
4	33316.06	56.07	0.30 ( 0.26)	0.86	20765.6	390.00
5	34976.75	68.80	0.30 ( 0.27)	0.89	27086.4	13100.00
6	35994.79	75.28	0.30 ( 0.27)	0.89	29915.3	11801.00
7	37911.19	85.87	0.30 ( 0.27)	0.91	35237.8	11530.00
8	38683.86	91.77	0.30 ( 0.27)	0.91	38974.9	13510.00
9	39399.64	97.48	0.30 ( 0.28)	0.92	42470.8	13010.00
10	40492.99	104.34	0.30 ( 0.28)	0.93	46880.4	11350.00
11	40868.74	109.03	0.30 ( 0.28)	0.93	50054.7	11130.00
12	40446.96	115.11	0.30 ( 0.28)	0.93	52981.2	12300.00
13	39651.64	123.89	0.30 ( 0.28)	0.94	57241.8	12400.00

14 38590.79 133.41 0.30( 0.28) 0.94 60643.4 12201.00  
 15 37609.06 140.89 0.30( 0.28) 0.94 62536.4 12231.00  
 16 36594.04 148.38 0.30( 0.28) 0.94 64089.2 10400.00  
 17 35018.71 157.83 0.30( 0.28) 0.94 65535.6 12010.00  
 18 33966.79 163.23 0.30( 0.28) 0.94 65798.2 10210.00  
 19 33288.32 167.28 0.30( 0.28) 0.94 65945.0 12000.00  
 20 29561.16 193.66 0.30( 0.28) 0.95 66557.9 10100.00  
 TOTAL AREA (ACRES) = 66557.9

\*\*\*\*\*

FLOW PROCESS FROM NODE 13700.00 TO NODE 13720.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM( FEET ) = 170.00 DOWNSTREAM( FEET ) = 165.51  
 CHANNEL LENGTH THRU SUBAREA( FEET ) = 1891.83 CHANNEL SLOPE = 0.0024  
 GIVEN CHANNEL BASE( FEET ) = 200.00 CHANNEL FREEBOARD( FEET ) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT( FEET ) = 13.25  
 CHANNEL FLOW THRU SUBAREA( CFS ) = 40868.74  
 FLOW VELOCITY( FEET/SEC. ) = 11.59 FLOW DEPTH( FEET ) = 13.25  
 TRAVEL TIME( MIN. ) = 2.72 Tc( MIN. ) = 111.75  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126443.80 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13700.00 TO NODE 13720.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 13720.00 TO NODE 13720.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506102D.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	321.17	15.37	2.360	0.30( 0.29)	0.96	192.9	10230.00
2	293.25	24.48	1.758	0.30( 0.29)	0.95	241.2	10200.00
3	292.00	24.71	1.747	0.30( 0.29)	0.95	241.7	10250.00
4	266.33	28.63	1.581	0.30( 0.29)	0.95	246.3	10220.00
TOTAL AREA (ACRES) =							246.3

\*\*\*\*\*

FLOW PROCESS FROM NODE 13720.00 TO NODE 13720.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25376.00	25.34	1.718	0.30( 0.25)	0.82	6317.6	50700.00
2	28361.55	35.68	1.410	0.30( 0.25)	0.82	9983.8	100.00
3	30777.87	44.24	1.259	0.30( 0.25)	0.84	13817.5	150.00

4	33316.06	58.97	1.058	0.30( 0.26)	0.86	20765.6	390.00
5	34976.75	71.65	0.979	0.30( 0.27)	0.89	27086.4	13100.00
6	35994.79	78.11	0.942	0.30( 0.27)	0.89	29915.3	11801.00
7	37911.19	88.65	0.883	0.30( 0.27)	0.91	35237.8	11530.00
8	38683.86	94.54	0.858	0.30( 0.27)	0.91	38974.9	13510.00
9	39399.64	100.23	0.837	0.30( 0.28)	0.92	42470.8	13010.00
10	40492.99	107.07	0.811	0.30( 0.28)	0.93	46880.4	11350.00
11	40868.74	111.75	0.794	0.30( 0.28)	0.93	50054.7	11130.00
12	40446.96	117.84	0.771	0.30( 0.28)	0.93	52981.2	12300.00
13	39651.64	126.63	0.749	0.30( 0.28)	0.94	57241.8	12400.00
14	38590.79	136.18	0.728	0.30( 0.28)	0.94	60643.4	12201.00
15	37609.06	143.69	0.712	0.30( 0.28)	0.94	62536.4	12231.00
16	36594.04	151.20	0.696	0.30( 0.28)	0.94	64089.2	10400.00
17	35018.71	160.69	0.676	0.30( 0.28)	0.94	65535.6	12010.00
18	33966.79	166.11	0.664	0.30( 0.28)	0.94	65798.2	10210.00
19	33288.32	170.18	0.655	0.30( 0.28)	0.94	65945.0	12000.00
20	29561.16	196.67	0.618	0.30( 0.28)	0.95	66557.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126443.80 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	321.17	15.37	2.360	0.30( 0.29)	0.96	192.9	10230.00
2	293.25	24.48	1.758	0.30( 0.29)	0.95	241.2	10200.00
3	292.00	24.71	1.747	0.30( 0.29)	0.95	241.7	10250.00
4	266.33	28.63	1.581	0.30( 0.29)	0.95	246.3	10220.00

LONGEST FLOWPATH FROM NODE 10200.00 TO NODE 13720.00 = 9099.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22429.28	15.37	2.360	0.30( 0.25)	0.83	4025.4	10230.00
2	25481.29	24.48	1.758	0.30( 0.25)	0.83	6345.2	10200.00
3	25522.29	24.71	1.747	0.30( 0.25)	0.83	6403.8	10250.00
4	25663.91	25.34	1.718	0.30( 0.25)	0.83	6560.0	50700.00
5	26592.81	28.63	1.581	0.30( 0.25)	0.83	7731.1	10220.00
6	28592.68	35.68	1.410	0.30( 0.25)	0.82	10230.1	100.00
7	30977.89	44.24	1.259	0.30( 0.25)	0.84	14063.7	150.00
8	33474.80	58.97	1.058	0.30( 0.26)	0.87	21011.9	390.00
9	35119.25	71.65	0.979	0.30( 0.27)	0.89	27332.6	13100.00
10	36129.76	78.11	0.942	0.30( 0.27)	0.90	30161.6	11801.00
11	38033.88	88.65	0.883	0.30( 0.27)	0.91	35484.1	11530.00
12	38801.50	94.54	0.858	0.30( 0.27)	0.91	39221.2	13510.00
13	39512.91	100.23	0.837	0.30( 0.28)	0.92	42717.0	13010.00
14	40601.00	107.07	0.811	0.30( 0.28)	0.93	47126.7	11350.00
15	40973.16	111.75	0.794	0.30( 0.28)	0.93	50300.9	11130.00
16	40546.70	117.84	0.771	0.30( 0.28)	0.93	53227.5	12300.00
17	39746.80	126.63	0.749	0.30( 0.28)	0.94	57488.1	12400.00
18	38681.72	136.18	0.728	0.30( 0.28)	0.94	60889.7	12201.00
19	37696.68	143.69	0.712	0.30( 0.28)	0.94	62782.7	12231.00
20	36678.33	151.20	0.696	0.30( 0.28)	0.94	64335.4	10400.00
21	35098.80	160.69	0.676	0.30( 0.28)	0.94	65781.8	12010.00
22	34044.48	166.11	0.664	0.30( 0.28)	0.94	66044.4	10210.00
23	33364.22	170.18	0.655	0.30( 0.28)	0.94	66191.2	12000.00
24	29629.48	196.67	0.618	0.30( 0.28)	0.95	66804.2	10100.00
TOTAL AREA (ACRES) =							66804.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 40973.16 Tc(MIN.) = 111.755  
 EFFECTIVE AREA(ACRES) = 50300.91 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.91  
 TOTAL AREA(ACRES) = 66804.2  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126443.80 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13720.00 TO NODE 13740.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 165.51 DOWNSTREAM(FEET) = 161.03  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2067.54 CHANNEL SLOPE = 0.0022  
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 13.60  
 CHANNEL FLOW THRU SUBAREA(CFS) = 40973.16  
 FLOW VELOCITY(FEET/SEC.) = 11.24 FLOW DEPTH(FEET) = 13.60  
 TRAVEL TIME(MIN.) = 3.07 Tc(MIN.) = 114.82  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128511.34 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13720.00 TO NODE 13740.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13740.00 TO NODE 13740.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 0506103D.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	651.40	18.38	0.30( 0.23)	0.76	399.7	10300.00
2	652.99	19.22	0.30( 0.23)	0.76	413.6	10380.00
3	641.00	21.63	0.30( 0.23)	0.76	440.0	10320.00
4	618.06	23.73	0.30( 0.23)	0.76	451.6	10360.00
5	581.15	26.62	0.30( 0.23)	0.76	460.8	10340.00
TOTAL AREA(ACRES) =						460.8

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13740.00 TO NODE 13740.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22429.28	19.08	2.058	0.30( 0.25)	0.83	4025.4	10230.00
2	25481.29	28.04	1.606	0.30( 0.25)	0.83	6345.2	10200.00
3	25522.29	28.27	1.596	0.30( 0.25)	0.83	6403.8	10250.00
4	25663.91	28.89	1.570	0.30( 0.25)	0.83	6560.0	50700.00
5	26592.81	32.14	1.481	0.30( 0.25)	0.83	7731.1	10220.00

6	28592.68	39.11	1.341	0.30( 0.25)	0.82	10230.1	100.00
7	30977.89	47.58	1.208	0.30( 0.25)	0.84	14063.7	150.00
8	33474.80	62.24	1.032	0.30( 0.26)	0.87	21011.9	390.00
9	35119.25	74.87	0.961	0.30( 0.27)	0.89	27332.6	13100.00
10	36129.76	81.30	0.924	0.30( 0.27)	0.90	30161.6	11801.00
11	38033.88	91.79	0.868	0.30( 0.27)	0.91	35484.1	11530.00
12	38801.50	97.66	0.846	0.30( 0.27)	0.91	39221.2	13510.00
13	39512.91	103.33	0.825	0.30( 0.28)	0.92	42717.0	13010.00
14	40601.00	110.14	0.800	0.30( 0.28)	0.93	47126.7	11350.00
15	40973.16	114.82	0.782	0.30( 0.28)	0.93	50300.9	11130.00
16	40546.70	120.92	0.761	0.30( 0.28)	0.93	53227.5	12300.00
17	39746.80	129.73	0.742	0.30( 0.28)	0.94	57488.1	12400.00
18	38681.72	139.30	0.722	0.30( 0.28)	0.94	60889.7	12201.00
19	37696.68	146.83	0.705	0.30( 0.28)	0.94	62782.7	12231.00
20	36678.33	154.37	0.689	0.30( 0.28)	0.94	64335.4	10400.00
21	35098.80	163.91	0.669	0.30( 0.28)	0.94	65781.8	12010.00
22	34044.48	169.36	0.657	0.30( 0.28)	0.94	66044.4	10210.00
23	33364.22	173.45	0.648	0.30( 0.28)	0.94	66191.2	12000.00
24	29629.48	200.07	0.615	0.30( 0.28)	0.95	66804.2	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128511.34 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	651.40	18.38	2.116	0.30( 0.23)	0.76	399.7	10300.00
2	652.99	19.22	2.047	0.30( 0.23)	0.76	413.6	10380.00
3	641.00	21.63	1.902	0.30( 0.23)	0.76	440.0	10320.00
4	618.06	23.73	1.796	0.30( 0.23)	0.76	451.6	10360.00
5	581.15	26.62	1.665	0.30( 0.23)	0.76	460.8	10340.00

LONGEST FLOWPATH FROM NODE 10320.00 TO NODE 13740.00 = 8457.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22935.55	18.38	2.116	0.30( 0.25)	0.82	4276.8	10300.00
2	23082.01	19.08	2.058	0.30( 0.25)	0.82	4436.8	10230.00
3	23128.37	19.22	2.047	0.30( 0.25)	0.82	4474.0	10380.00
4	23939.72	21.63	1.902	0.30( 0.25)	0.82	5126.3	10320.00
5	24631.52	23.73	1.796	0.30( 0.25)	0.82	5681.2	10360.00
6	25578.45	26.62	1.665	0.30( 0.25)	0.82	6438.1	10340.00
7	26038.52	28.04	1.606	0.30( 0.25)	0.82	6806.0	10200.00
8	26075.60	28.27	1.596	0.30( 0.25)	0.82	6864.6	10250.00
9	26206.84	28.89	1.570	0.30( 0.25)	0.82	7020.8	50700.00
10	27099.61	32.14	1.481	0.30( 0.25)	0.82	8191.9	10220.00
11	29042.77	39.11	1.341	0.30( 0.25)	0.82	10690.9	100.00
12	31374.08	47.58	1.208	0.30( 0.25)	0.84	14524.5	150.00
13	33799.99	62.24	1.032	0.30( 0.26)	0.86	21472.7	390.00
14	35415.46	74.87	0.961	0.30( 0.27)	0.89	27793.4	13100.00
15	36411.22	81.30	0.924	0.30( 0.27)	0.89	30622.4	11801.00
16	38292.66	91.79	0.868	0.30( 0.27)	0.91	35944.9	11530.00
17	39051.42	97.66	0.846	0.30( 0.27)	0.91	39682.0	13510.00
18	39754.26	103.33	0.825	0.30( 0.28)	0.92	43177.8	13010.00
19	40832.05	110.14	0.800	0.30( 0.28)	0.93	47587.5	11350.00
20	41197.15	114.82	0.782	0.30( 0.28)	0.93	50761.7	11130.00
21	40762.06	120.92	0.761	0.30( 0.28)	0.93	53688.3	12300.00
22	39954.49	129.73	0.742	0.30( 0.28)	0.94	57948.9	12400.00
23	38881.09	139.30	0.722	0.30( 0.28)	0.94	61350.5	12201.00
24	37889.48	146.83	0.705	0.30( 0.28)	0.94	63243.5	12231.00

25 36864.57 154.37 0.689 0.30( 0.28) 0.94 64796.2 10400.00  
 26 35276.75 163.91 0.669 0.30( 0.28) 0.94 66242.6 12010.00  
 27 34217.68 169.36 0.657 0.30( 0.28) 0.94 66505.2 10210.00  
 28 33533.85 173.45 0.648 0.30( 0.28) 0.94 66652.0 12000.00  
 29 29785.74 200.07 0.615 0.30( 0.28) 0.94 67265.0 10100.00  
 TOTAL AREA (ACRES) = 67265.0

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 41197.15 Tc(MIN.) = 114.820  
 EFFECTIVE AREA(ACRES) = 50761.71 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.89  
 TOTAL AREA(ACRES) = 67265.0  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128511.34 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13740.00 TO NODE 13741.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 161.03 DOWNSTREAM(FEET) = 141.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 364.08 CHANNEL SLOPE = 0.0550  
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 7.90  
 CHANNEL FLOW THRU SUBAREA(CFS) = 41197.15  
 FLOW VELOCITY(FEET/SEC.) = 39.62 FLOW DEPTH(FEET) = 7.90  
 TRAVEL TIME(MIN.) = 0.15 Tc(MIN.) = 114.97  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128875.41 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13740.00 TO NODE 13741.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 13741.00 TO NODE 13741.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506104D.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	65.97	19.78	0.30( 0.24)	0.80	44.3	10400.00
TOTAL AREA(ACRES) =						44.3

\*\*\*\*\*

FLOW PROCESS FROM NODE 13741.00 TO NODE 13741.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22935.55	18.56	2.101	0.30( 0.25)	0.82	4276.8	10300.00

2	23082.01	19.27	2.043	0.30( 0.25)	0.82	4436.8	10230.00
3	23128.37	19.40	2.032	0.30( 0.25)	0.82	4474.0	10380.00
4	23939.72	21.82	1.892	0.30( 0.25)	0.82	5126.3	10320.00
5	24631.52	23.91	1.787	0.30( 0.25)	0.82	5681.2	10360.00
6	25578.45	26.80	1.657	0.30( 0.25)	0.82	6438.1	10340.00
7	26038.52	28.22	1.598	0.30( 0.25)	0.82	6806.0	10200.00
8	26075.60	28.45	1.588	0.30( 0.25)	0.82	6864.6	10250.00
9	26206.84	29.07	1.563	0.30( 0.25)	0.82	7020.8	50700.00
10	27099.61	32.32	1.477	0.30( 0.25)	0.82	8191.9	10220.00
11	29042.77	39.28	1.337	0.30( 0.25)	0.82	10690.9	100.00
12	31374.08	47.75	1.205	0.30( 0.25)	0.84	14524.5	150.00
13	33799.99	62.40	1.031	0.30( 0.26)	0.86	21472.7	390.00
14	35415.46	75.03	0.960	0.30( 0.27)	0.89	27793.4	13100.00
15	36411.22	81.46	0.923	0.30( 0.27)	0.89	30622.4	11801.00
16	38292.66	91.95	0.868	0.30( 0.27)	0.91	35944.9	11530.00
17	39051.42	97.82	0.846	0.30( 0.27)	0.91	39682.0	13510.00
18	39754.26	103.48	0.825	0.30( 0.28)	0.92	43177.8	13010.00
19	40832.05	110.30	0.799	0.30( 0.28)	0.93	47587.5	11350.00
20	41197.15	114.97	0.782	0.30( 0.28)	0.93	50761.7	11130.00
21	40762.06	121.07	0.761	0.30( 0.28)	0.93	53688.3	12300.00
22	39954.49	129.88	0.742	0.30( 0.28)	0.94	57948.9	12400.00
23	38881.09	139.45	0.721	0.30( 0.28)	0.94	61350.5	12201.00
24	37889.48	146.99	0.705	0.30( 0.28)	0.94	63243.5	12231.00
25	36864.57	154.53	0.689	0.30( 0.28)	0.94	64796.2	10400.00
26	35276.75	164.07	0.668	0.30( 0.28)	0.94	66242.6	12010.00
27	34217.68	169.52	0.657	0.30( 0.28)	0.94	66505.2	10210.00
28	33533.85	173.62	0.648	0.30( 0.28)	0.94	66652.0	12000.00
29	29785.74	200.24	0.615	0.30( 0.28)	0.94	67265.0	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128875.41 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	65.97	19.78	2.002	0.30( 0.24)	0.80	44.3	10400.00
LONGEST FLOWPATH FROM NODE 10400.00 TO NODE 13741.00 =							6237.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23000.93	18.56	2.101	0.30( 0.25)	0.82	4318.4	10300.00
2	23147.79	19.27	2.043	0.30( 0.25)	0.82	4479.9	10230.00
3	23194.21	19.40	2.032	0.30( 0.25)	0.82	4517.5	10380.00
4	23320.85	19.78	2.002	0.30( 0.25)	0.82	4620.0	10400.00
5	24001.59	21.82	1.892	0.30( 0.25)	0.82	5170.6	10320.00
6	24689.44	23.91	1.787	0.30( 0.25)	0.82	5725.5	10360.00
7	25631.52	26.80	1.657	0.30( 0.25)	0.82	6482.4	10340.00
8	26089.38	28.22	1.598	0.30( 0.25)	0.82	6850.3	10200.00
9	26126.09	28.45	1.588	0.30( 0.25)	0.82	6908.9	10250.00
10	26256.38	29.07	1.563	0.30( 0.25)	0.82	7065.1	50700.00
11	27145.95	32.32	1.477	0.30( 0.25)	0.82	8236.2	10220.00
12	29083.87	39.28	1.337	0.30( 0.25)	0.82	10735.2	100.00
13	31410.23	47.75	1.205	0.30( 0.25)	0.84	14568.8	150.00
14	33829.63	62.40	1.031	0.30( 0.26)	0.86	21517.0	390.00
15	35442.43	75.03	0.960	0.30( 0.27)	0.89	27837.7	13100.00
16	36436.82	81.46	0.923	0.30( 0.27)	0.89	30666.7	11801.00
17	38316.18	91.95	0.868	0.30( 0.27)	0.90	35989.2	11530.00
18	39074.11	97.82	0.846	0.30( 0.27)	0.91	39726.3	13510.00
19	39776.16	103.48	0.825	0.30( 0.28)	0.92	43222.1	13010.00

20	40853.01	110.30	0.799	0.30	( 0.28)	0.93	47631.8	11350.00
21	41217.45	114.97	0.782	0.30	( 0.28)	0.93	50806.0	11130.00
22	40781.57	121.07	0.761	0.30	( 0.28)	0.93	53732.6	12300.00
23	39973.29	129.88	0.742	0.30	( 0.28)	0.94	57993.2	12400.00
24	38899.12	139.45	0.721	0.30	( 0.28)	0.94	61394.8	12201.00
25	37906.91	146.99	0.705	0.30	( 0.28)	0.94	63287.8	12231.00
26	36881.39	154.53	0.689	0.30	( 0.28)	0.94	64840.5	10400.00
27	35292.80	164.07	0.668	0.30	( 0.28)	0.94	66286.9	12010.00
28	34233.29	169.52	0.657	0.30	( 0.28)	0.94	66549.5	10210.00
29	33549.13	173.62	0.648	0.30	( 0.28)	0.94	66696.3	12000.00
30	29799.80	200.24	0.615	0.30	( 0.28)	0.94	67309.3	10100.00

TOTAL AREA (ACRES) = 67309.3

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 41217.45 Tc (MIN.) = 114.973  
EFFECTIVE AREA (ACRES) = 50806.01 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA (ACRES) = 67309.3  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128875.41 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13741.00 TO NODE 13802.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 141.00 DOWNSTREAM (FEET) = 135.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1533.41 CHANNEL SLOPE = 0.0039  
GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 16.05  
CHANNEL FLOW THRU SUBAREA (CFS) = 41217.45  
FLOW VELOCITY (FEET/SEC.) = 15.64 FLOW DEPTH (FEET) = 16.05  
TRAVEL TIME (MIN.) = 1.63 Tc (MIN.) = 116.61  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130408.82 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506105K.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	355.73	14.74	0.30 ( 0.27)	0.90	206.7	10520.00
2	414.68	31.61	0.30 ( 0.28)	0.93	403.6	10500.00
TOTAL AREA (ACRES) =						403.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23000.93	20.50	1.959	0.30 ( 0.25)	0.82	4318.4	10300.00
2	23147.79	21.20	1.924	0.30 ( 0.25)	0.82	4479.9	10230.00
3	23194.21	21.33	1.917	0.30 ( 0.25)	0.82	4517.5	10380.00
4	23320.85	21.71	1.898	0.30 ( 0.25)	0.82	4620.0	10400.00
5	24001.59	23.73	1.796	0.30 ( 0.25)	0.82	5170.6	10320.00
6	24689.44	25.81	1.698	0.30 ( 0.25)	0.82	5725.5	10360.00
7	25631.52	28.67	1.579	0.30 ( 0.25)	0.82	6482.4	10340.00
8	26089.38	30.08	1.522	0.30 ( 0.25)	0.82	6850.3	10200.00
9	26126.09	30.31	1.518	0.30 ( 0.25)	0.82	6908.9	10250.00
10	26256.38	30.93	1.505	0.30 ( 0.25)	0.82	7065.1	50700.00
11	27145.95	34.16	1.440	0.30 ( 0.25)	0.82	8236.2	10220.00
12	29083.87	41.09	1.306	0.30 ( 0.25)	0.82	10735.2	100.00
13	31410.23	49.52	1.178	0.30 ( 0.25)	0.84	14568.8	150.00
14	33829.63	64.13	1.022	0.30 ( 0.26)	0.86	21517.0	390.00
15	35442.43	76.73	0.950	0.30 ( 0.27)	0.89	27837.7	13100.00
16	36436.82	83.15	0.914	0.30 ( 0.27)	0.89	30666.7	11801.00
17	38316.18	93.62	0.862	0.30 ( 0.27)	0.90	35989.2	11530.00
18	39074.11	99.48	0.840	0.30 ( 0.27)	0.91	39726.3	13510.00
19	39776.16	105.13	0.818	0.30 ( 0.28)	0.92	43222.1	13010.00
20	40853.01	111.94	0.793	0.30 ( 0.28)	0.93	47631.8	11350.00
21	41217.45	116.61	0.776	0.30 ( 0.28)	0.93	50806.0	11130.00
22	40781.57	122.71	0.757	0.30 ( 0.28)	0.93	53732.6	12300.00
23	39973.29	131.53	0.738	0.30 ( 0.28)	0.94	57993.2	12400.00
24	38899.12	141.11	0.718	0.30 ( 0.28)	0.94	61394.8	12201.00
25	37906.91	148.66	0.701	0.30 ( 0.28)	0.94	63287.8	12231.00
26	36881.39	156.22	0.685	0.30 ( 0.28)	0.94	64840.5	10400.00
27	35292.80	165.77	0.665	0.30 ( 0.28)	0.94	66286.9	12010.00
28	34233.29	171.24	0.653	0.30 ( 0.28)	0.94	66549.5	10210.00
29	33549.13	175.35	0.644	0.30 ( 0.28)	0.94	66696.3	12000.00
30	29799.80	202.03	0.613	0.30 ( 0.28)	0.94	67309.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130408.82 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	355.73	14.74	2.428	0.30 ( 0.27)	0.90	206.7	10520.00
2	414.68	31.61	1.492	0.30 ( 0.28)	0.93	403.6	10500.00

LONGEST FLOWPATH FROM NODE 10500.00 TO NODE 13802.00 = 12187.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21421.27	14.74	2.428	0.30 ( 0.25)	0.83	3311.5	10520.00
2	23376.78	20.50	1.959	0.30 ( 0.25)	0.83	4592.2	10300.00
3	23526.08	21.20	1.924	0.30 ( 0.25)	0.83	4761.9	10230.00
4	23572.97	21.33	1.917	0.30 ( 0.25)	0.83	4801.1	10380.00
5	23700.92	21.71	1.898	0.30 ( 0.25)	0.83	4908.0	10400.00
6	24388.72	23.73	1.796	0.30 ( 0.25)	0.83	5482.1	10320.00
7	25083.83	25.81	1.698	0.30 ( 0.25)	0.83	6061.3	10360.00
8	26035.92	28.67	1.579	0.30 ( 0.25)	0.83	6851.7	10340.00
9	26498.70	30.08	1.522	0.30 ( 0.25)	0.83	7236.0	10200.00
10	26536.22	30.31	1.518	0.30 ( 0.25)	0.83	7297.3	10250.00

11	26668.66	30.93	1.505	0.30	( 0.25)	0.83	7460.7	50700.00
12	26860.43	31.61	1.492	0.30	( 0.25)	0.83	7718.0	10500.00
13	27543.15	34.16	1.440	0.30	( 0.25)	0.83	8639.8	10220.00
14	29435.31	41.09	1.306	0.30	( 0.25)	0.83	11138.8	100.00
15	31717.90	49.52	1.178	0.30	( 0.25)	0.84	14972.4	150.00
16	34083.73	64.13	1.022	0.30	( 0.26)	0.86	21920.6	390.00
17	35672.11	76.73	0.950	0.30	( 0.27)	0.89	28241.3	13100.00
18	36654.09	83.15	0.914	0.30	( 0.27)	0.89	31070.3	11801.00
19	38515.57	93.62	0.862	0.30	( 0.27)	0.91	36392.8	11530.00
20	39266.03	99.48	0.840	0.30	( 0.27)	0.91	40129.9	13510.00
21	39960.86	105.13	0.818	0.30	( 0.28)	0.92	43625.7	13010.00
22	41029.02	111.94	0.793	0.30	( 0.28)	0.93	48035.4	11350.00
23	41387.51	116.61	0.776	0.30	( 0.28)	0.93	51209.6	11130.00
24	40945.31	122.71	0.757	0.30	( 0.28)	0.93	54136.2	12300.00
25	40130.55	131.53	0.738	0.30	( 0.28)	0.94	58396.8	12400.00
26	39049.34	141.11	0.718	0.30	( 0.28)	0.94	61798.4	12201.00
27	38051.58	148.66	0.701	0.30	( 0.28)	0.94	63691.4	12231.00
28	37020.51	156.22	0.685	0.30	( 0.28)	0.94	65244.1	10400.00
29	35424.90	165.77	0.665	0.30	( 0.28)	0.94	66690.5	12010.00
30	34361.38	171.24	0.653	0.30	( 0.28)	0.94	66953.1	10210.00
31	33674.20	175.35	0.644	0.30	( 0.28)	0.94	67099.9	12000.00
32	29914.34	202.03	0.613	0.30	( 0.28)	0.94	67712.9	10100.00

TOTAL AREA (ACRES) = 67712.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 41387.51 Tc (MIN.) = 116.607  
EFFECTIVE AREA (ACRES) = 51209.61 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
TOTAL AREA (ACRES) = 67712.9  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130408.82 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13802.00 TO NODE 13803.00 IS CODE = 56  
-----

>>>> COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>> TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 135.00 DOWNSTREAM (FEET) = 133.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 207.23 CHANNEL SLOPE = 0.0097  
GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 12.70  
CHANNEL FLOW THRU SUBAREA (CFS) = 41387.51  
FLOW VELOCITY (FEET/SEC.) = 21.61 FLOW DEPTH (FEET) = 12.70  
TRAVEL TIME (MIN.) = 0.16 Tc (MIN.) = 116.77  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130616.05 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 81  
-----

>>>> ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 116.77  
\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.775  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL					

"1 DWELLING/ACRE" B 48.80 0.30 0.800 56  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.800  
SUBAREA AREA (ACRES) = 48.80 SUBAREA RUNOFF (CFS) = 23.50  
EFFECTIVE AREA (ACRES) = 51258.41 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA (ACRES) = 67761.7 PEAK FLOW RATE (CFS) = 41387.51  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13802.00 TO NODE 13803.00 IS CODE = 12  
-----

>>>> CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 15.1  
-----

>>>> DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506106D.DNA  
MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	59.23	17.66	0.30 ( 0.20)	0.67	36.9	10600.00
TOTAL AREA (ACRES) =			36.9			

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 11  
-----

>>>> CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21421.27	14.93	2.400	0.30 ( 0.25)	0.83	3360.3	10520.00
2	23376.78	20.69	1.949	0.30 ( 0.25)	0.83	4641.0	10300.00
3	23526.08	21.39	1.914	0.30 ( 0.25)	0.83	4810.7	10230.00
4	23572.97	21.52	1.907	0.30 ( 0.25)	0.83	4849.9	10380.00
5	23700.92	21.89	1.889	0.30 ( 0.25)	0.83	4956.8	10400.00
6	24388.72	23.91	1.787	0.30 ( 0.25)	0.83	5530.9	10320.00
7	25083.83	25.99	1.691	0.30 ( 0.25)	0.83	6110.1	10360.00
8	26035.92	28.85	1.572	0.30 ( 0.25)	0.83	6900.5	10340.00
9	26498.70	30.26	1.519	0.30 ( 0.25)	0.83	7284.8	10200.00
10	26536.22	30.50	1.514	0.30 ( 0.25)	0.83	7346.1	10250.00
11	26668.66	31.11	1.502	0.30 ( 0.25)	0.83	7509.5	50700.00
12	26860.43	31.80	1.488	0.30 ( 0.25)	0.83	7766.8	10500.00
13	27543.15	34.34	1.437	0.30 ( 0.25)	0.83	8688.6	10220.00
14	29435.31	41.26	1.304	0.30 ( 0.25)	0.83	11187.6	100.00
15	31717.90	49.69	1.176	0.30 ( 0.25)	0.84	15021.2	150.00
16	34083.73	64.30	1.021	0.30 ( 0.26)	0.86	21969.4	390.00
17	35672.11	76.90	0.949	0.30 ( 0.27)	0.89	28290.1	13100.00
18	36654.09	83.32	0.913	0.30 ( 0.27)	0.89	31119.1	11801.00
19	38515.57	93.78	0.861	0.30 ( 0.27)	0.90	36441.6	11530.00
20	39266.03	99.64	0.839	0.30 ( 0.27)	0.91	40178.7	13510.00
21	39960.86	105.30	0.818	0.30 ( 0.28)	0.92	43674.5	13010.00
22	41029.02	112.10	0.793	0.30 ( 0.28)	0.92	48084.2	11350.00

23 41387.51 116.77 0.775 0.30( 0.28) 0.93 51258.4 11130.00  
 24 40945.31 122.87 0.757 0.30( 0.28) 0.93 54185.0 12300.00  
 25 40130.55 131.69 0.738 0.30( 0.28) 0.94 58445.6 12400.00  
 26 39049.34 141.28 0.717 0.30( 0.28) 0.94 61847.2 12201.00  
 27 38051.58 148.83 0.701 0.30( 0.28) 0.94 63740.2 12231.00  
 28 37020.51 156.38 0.685 0.30( 0.28) 0.94 65292.9 10400.00  
 29 35424.90 165.94 0.664 0.30( 0.28) 0.94 66739.3 12010.00  
 30 34361.38 171.41 0.652 0.30( 0.28) 0.94 67001.9 10210.00  
 31 33674.20 175.52 0.644 0.30( 0.28) 0.94 67148.7 12000.00  
 32 29914.34 202.21 0.613 0.30( 0.28) 0.94 67761.7 10100.00  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130616.05 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	59.23	17.66	2.174	0.30( 0.20)	0.67	36.9	10600.00

LONGEST FLOWPATH FROM NODE 10600.00 TO NODE 13803.00 = 1713.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21477.08	14.93	2.400	0.30( 0.25)	0.82	3391.5	10520.00
2	22406.68	17.66	2.174	0.30( 0.25)	0.82	4003.8	10600.00
3	23429.27	20.69	1.949	0.30( 0.25)	0.82	4677.9	10300.00
4	23577.51	21.39	1.914	0.30( 0.25)	0.82	4847.6	10230.00
5	23624.19	21.52	1.907	0.30( 0.25)	0.82	4886.8	10380.00
6	23751.58	21.89	1.889	0.30( 0.25)	0.82	4993.7	10400.00
7	24436.32	23.91	1.787	0.30( 0.25)	0.83	5567.8	10320.00
8	25128.55	25.99	1.691	0.30( 0.25)	0.83	6147.0	10360.00
9	26077.06	28.85	1.572	0.30( 0.25)	0.83	6937.4	10340.00
10	26538.26	30.26	1.519	0.30( 0.25)	0.83	7321.7	10200.00
11	26575.64	30.50	1.514	0.30( 0.25)	0.83	7383.0	10250.00
12	26707.70	31.11	1.502	0.30( 0.25)	0.83	7546.4	50700.00
13	26899.07	31.80	1.488	0.30( 0.25)	0.83	7803.7	10500.00
14	27580.25	34.34	1.437	0.30( 0.25)	0.83	8725.5	10220.00
15	29468.42	41.26	1.304	0.30( 0.25)	0.82	11224.5	100.00
16	31747.16	49.69	1.176	0.30( 0.25)	0.84	15058.1	150.00
17	34108.33	64.30	1.021	0.30( 0.26)	0.86	22006.3	390.00
18	35694.57	76.90	0.949	0.30( 0.27)	0.89	28327.0	13100.00
19	36675.46	83.32	0.913	0.30( 0.27)	0.89	31156.0	11801.00
20	38535.38	93.78	0.861	0.30( 0.27)	0.90	36478.5	11530.00
21	39285.18	99.64	0.839	0.30( 0.27)	0.91	40215.6	13510.00
22	39979.38	105.30	0.818	0.30( 0.28)	0.92	43711.4	13010.00
23	41046.78	112.10	0.793	0.30( 0.28)	0.92	48121.1	11350.00
24	41404.74	116.77	0.775	0.30( 0.28)	0.93	51295.3	11130.00
25	40962.00	122.87	0.757	0.30( 0.28)	0.93	54221.9	12300.00
26	40146.66	131.69	0.738	0.30( 0.28)	0.94	58482.5	12400.00
27	39064.84	141.28	0.717	0.30( 0.28)	0.94	61884.1	12201.00
28	38066.59	148.83	0.701	0.30( 0.28)	0.94	63777.1	12231.00
29	37035.03	156.38	0.685	0.30( 0.28)	0.94	65329.8	10400.00
30	35438.81	165.94	0.664	0.30( 0.28)	0.94	66776.2	12010.00
31	34374.93	171.41	0.652	0.30( 0.28)	0.94	67038.8	10210.00
32	33687.49	175.52	0.644	0.30( 0.28)	0.94	67185.6	12000.00
33	29926.71	202.21	0.613	0.30( 0.28)	0.94	67798.6	10100.00

TOTAL AREA (ACRES) = 67798.6

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 41404.74 Tc (MIN.) = 116.767

EFFECTIVE AREA (ACRES) = 51295.31 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA (ACRES) = 67798.6  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130616.05 FEET.

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 67798.6 TC (MIN.) = 116.77  
 EFFECTIVE AREA (ACRES) = 51295.31 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.929  
 PEAK FLOW RATE (CFS) = 41404.74

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21477.08	14.93	2.400	0.30( 0.25)	0.82	3391.5	10520.00
2	22406.68	17.66	2.174	0.30( 0.25)	0.82	4003.8	10600.00
3	23429.27	20.69	1.949	0.30( 0.25)	0.82	4677.9	10300.00
4	23577.51	21.39	1.914	0.30( 0.25)	0.82	4847.6	10230.00
5	23624.19	21.52	1.907	0.30( 0.25)	0.82	4886.8	10380.00
6	23751.58	21.89	1.889	0.30( 0.25)	0.82	4993.7	10400.00
7	24436.32	23.91	1.787	0.30( 0.25)	0.83	5567.8	10320.00
8	25128.55	25.99	1.691	0.30( 0.25)	0.83	6147.0	10360.00
9	26077.06	28.85	1.572	0.30( 0.25)	0.83	6937.4	10340.00
10	26538.26	30.26	1.519	0.30( 0.25)	0.83	7321.7	10200.00
11	26575.64	30.50	1.514	0.30( 0.25)	0.83	7383.0	10250.00
12	26707.70	31.11	1.502	0.30( 0.25)	0.83	7546.4	50700.00
13	26899.07	31.80	1.488	0.30( 0.25)	0.83	7803.7	10500.00
14	27580.25	34.34	1.437	0.30( 0.25)	0.83	8725.5	10220.00
15	29468.42	41.26	1.304	0.30( 0.25)	0.82	11224.5	100.00
16	31747.16	49.69	1.176	0.30( 0.25)	0.84	15058.1	150.00
17	34108.33	64.30	1.021	0.30( 0.26)	0.86	22006.3	390.00
18	35694.57	76.90	0.949	0.30( 0.27)	0.89	28327.0	13100.00
19	36675.46	83.32	0.913	0.30( 0.27)	0.89	31156.0	11801.00
20	38535.38	93.78	0.861	0.30( 0.27)	0.90	36478.5	11530.00
21	39285.18	99.64	0.839	0.30( 0.27)	0.91	40215.6	13510.00
22	39979.38	105.30	0.818	0.30( 0.28)	0.92	43711.4	13010.00
23	41046.78	112.10	0.793	0.30( 0.28)	0.92	48121.1	11350.00
24	41404.74	116.77	0.775	0.30( 0.28)	0.93	51295.3	11130.00
25	40962.00	122.87	0.757	0.30( 0.28)	0.93	54221.9	12300.00
26	40146.66	131.69	0.738	0.30( 0.28)	0.94	58482.5	12400.00
27	39064.84	141.28	0.717	0.30( 0.28)	0.94	61884.1	12201.00
28	38066.59	148.83	0.701	0.30( 0.28)	0.94	63777.1	12231.00
29	37035.03	156.38	0.685	0.30( 0.28)	0.94	65329.8	10400.00
30	35438.81	165.94	0.664	0.30( 0.28)	0.94	66776.2	12010.00
31	34374.93	171.41	0.652	0.30( 0.28)	0.94	67038.8	10210.00
32	33687.49	175.52	0.644	0.30( 0.28)	0.94	67185.6	12000.00
33	29926.71	202.21	0.613	0.30( 0.28)	0.94	67798.6	10100.00

END OF RATIONAL METHOD ANALYSIS





\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S38- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 25-YR RM EV APRIL 2019 CCHIU \*  
\*\*\*\*\*

FILE NAME: RI25EV38.DAT  
TIME/DATE OF STUDY: 09:52 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 25.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 4.741
- 2) 10.00; 3.104
- 3) 15.00; 2.386
- 4) 20.00; 1.981
- 5) 25.00; 1.730
- 6) 30.00; 1.523
- 7) 40.00; 1.322
- 8) 50.00; 1.160
- 9) 60.00; 1.043
- 10) 90.00; 0.873
- 11) 120.00; 0.761
- 12) 180.00; 0.632
- 13) 360.00; 0.462
- 14) 1200.00; 0.202

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	(FT)	(FT)	SIDE / SIDE/ WAY	(FT)	(FT)	(FT)	(FT)	(n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI25EV37.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22406.68	17.66	0.30 ( 0.25)	0.82	4003.8	10600.00
2	27580.25	34.34	0.30 ( 0.25)	0.83	8725.5	10220.00
3	29468.42	41.26	0.30 ( 0.25)	0.82	11224.5	100.00
4	31747.16	49.69	0.30 ( 0.25)	0.84	15058.1	150.00
5	34108.33	64.30	0.30 ( 0.26)	0.86	22006.3	390.00
6	35694.57	76.90	0.30 ( 0.27)	0.89	28327.0	13100.00
7	36675.46	83.32	0.30 ( 0.27)	0.89	31156.0	11801.00
8	38535.38	93.78	0.30 ( 0.27)	0.90	36478.5	11530.00
9	39285.18	99.64	0.30 ( 0.27)	0.91	40215.6	13510.00
10	39979.38	105.30	0.30 ( 0.28)	0.92	43711.4	13010.00
11	41046.78	112.10	0.30 ( 0.28)	0.92	48121.1	11350.00
12	41404.74	116.77	0.30 ( 0.28)	0.93	51295.3	11130.00
13	40962.00	122.87	0.30 ( 0.28)	0.93	54221.9	12300.00
14	40146.66	131.69	0.30 ( 0.28)	0.94	58482.5	12400.00
15	39064.84	141.28	0.30 ( 0.28)	0.94	61884.1	12201.00
16	38066.59	148.83	0.30 ( 0.28)	0.94	63777.1	12231.00
17	37035.03	156.38	0.30 ( 0.28)	0.94	65329.8	10400.00
18	35438.81	165.94	0.30 ( 0.28)	0.94	66776.2	12010.00
19	34374.93	171.41	0.30 ( 0.28)	0.94	67038.8	10210.00
20	29926.71	202.21	0.30 ( 0.28)	0.94	67798.6	10100.00
TOTAL AREA (ACRES) =						67798.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22406.68	17.66	0.30 ( 0.25)	0.82	4003.8	10600.00
2	27580.25	34.34	0.30 ( 0.25)	0.83	8725.5	10220.00
3	29468.42	41.26	0.30 ( 0.25)	0.82	11224.5	100.00
4	31747.16	49.69	0.30 ( 0.25)	0.84	15058.1	150.00
5	34108.33	64.30	0.30 ( 0.26)	0.86	22006.3	390.00
6	35694.57	76.90	0.30 ( 0.27)	0.89	28327.0	13100.00
7	36675.46	83.32	0.30 ( 0.27)	0.89	31156.0	11801.00
8	38535.38	93.78	0.30 ( 0.27)	0.90	36478.5	11530.00
9	39285.18	99.64	0.30 ( 0.27)	0.91	40215.6	13510.00
10	39979.38	105.30	0.30 ( 0.28)	0.92	43711.4	13010.00
11	41046.78	112.10	0.30 ( 0.28)	0.92	48121.1	11350.00
12	41404.74	116.77	0.30 ( 0.28)	0.93	51295.3	11130.00
13	40962.00	122.87	0.30 ( 0.28)	0.93	54221.9	12300.00

14	40146.66	131.69	0.30	( 0.28)	0.94	58482.5	12400.00	
15	39064.84	141.28	0.30	( 0.28)	0.94	61884.1	12201.00	
16	38066.59	148.83	0.30	( 0.28)	0.94	63777.1	12231.00	
17	37035.03	156.38	0.30	( 0.28)	0.94	65329.8	10400.00	
18	35438.81	165.94	0.30	( 0.28)	0.94	66776.2	12010.00	
19	34374.93	171.41	0.30	( 0.28)	0.94	67038.8	10210.00	
20	29926.71	202.21	0.30	( 0.28)	0.94	67798.6	10100.00	
TOTAL AREA (ACRES) =		67798.6						

\*\*\*\*\*

FLOW PROCESS FROM NODE 13803.00 TO NODE 13820.00 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 140.00 DOWNSTREAM(FEET) = 137.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 926.91 CHANNEL SLOPE = 0.0032  
 GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 16.89  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 0.769  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 31.44 0.30 0.983 -  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.983  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 41411.45  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 14.63  
 AVERAGE FLOW DEPTH (FEET) = 16.89 TRAVEL TIME (MIN.) = 1.06  
 Tc (MIN.) = 117.82

SUBAREA AREA (ACRES) = 31.44 SUBAREA RUNOFF (CFS) = 13.42  
 EFFECTIVE AREA (ACRES) = 51326.75 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 67830.0 PEAK FLOW RATE (CFS) = 41404.74  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 16.89

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 16.89 FLOW VELOCITY (FEET/SEC.) = 14.63  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13820.00 = 131542.95 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22406.68	18.92	2.069	0.30 ( 0.25)	0.83	4035.2	10600.00
2	27580.25	35.52	1.412	0.30 ( 0.25)	0.83	8756.9	10220.00
3	29468.42	42.43	1.283	0.30 ( 0.25)	0.83	11255.9	100.00
4	31747.16	50.83	1.150	0.30 ( 0.25)	0.84	15089.5	150.00
5	34108.33	65.41	1.012	0.30 ( 0.26)	0.86	22037.7	390.00
6	35694.57	78.00	0.941	0.30 ( 0.27)	0.89	28358.5	13100.00
7	36675.46	84.41	0.905	0.30 ( 0.27)	0.89	31187.4	11801.00
8	38535.38	94.86	0.855	0.30 ( 0.27)	0.90	36509.9	11530.00
9	39285.18	100.71	0.833	0.30 ( 0.27)	0.91	40247.0	13510.00
10	39979.38	106.36	0.812	0.30 ( 0.28)	0.92	43742.9	13010.00
11	41046.78	113.15	0.787	0.30 ( 0.28)	0.92	48152.6	11350.00

12	41404.74	117.82	0.769	0.30 ( 0.28)	0.93	51326.8	11130.00
13	40962.00	123.93	0.753	0.30 ( 0.28)	0.93	54253.3	12300.00
14	40146.66	132.76	0.734	0.30 ( 0.28)	0.94	58513.9	12400.00
15	39064.84	142.35	0.713	0.30 ( 0.28)	0.94	61915.5	12201.00
16	38066.59	149.91	0.697	0.30 ( 0.28)	0.94	63808.5	12231.00
17	37035.03	157.47	0.680	0.30 ( 0.28)	0.94	65361.3	10400.00
18	35438.81	167.04	0.660	0.30 ( 0.28)	0.94	66807.7	12010.00
19	34374.93	172.53	0.648	0.30 ( 0.28)	0.94	67070.2	10210.00
20	29926.71	203.36	0.610	0.30 ( 0.28)	0.94	67830.0	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 41404.74 Tc (MIN.) = 117.82  
 AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA (ACRES) = 51326.75

\*\*\*\*\*

FLOW PROCESS FROM NODE 13803.00 TO NODE 13820.00 IS CODE = 1

-----  
 >>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
 TIME OF CONCENTRATION (MIN.) = 117.82  
 RAINFALL INTENSITY (INCH/HR) = 0.77  
 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93  
 EFFECTIVE STREAM AREA (ACRES) = 51326.75  
 TOTAL STREAM AREA (ACRES) = 67830.01  
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 41404.74

\*\*\*\*\*

FLOW PROCESS FROM NODE 13810.00 TO NODE 13811.00 IS CODE = 21

-----  
 >>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH (FEET) = 648.54  
 ELEVATION DATA: UPSTREAM (FEET) = 756.46 DOWNSTREAM (FEET) = 586.02

Tc = K \* [(LENGTH\*\* 3.00) / (ELEVATION CHANGE)]\*\* 0.20  
 SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 12.293  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 2.775

SUBAREA Tc AND LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)  
 NATURAL FAIR COVER  
 "CHAPARRAL, BROADLEAF" - 5.58 0.30 1.000 56 12.29  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA RUNOFF (CFS) = 12.43  
 TOTAL AREA (ACRES) = 5.58 PEAK FLOW RATE (CFS) = 12.43

\*\*\*\*\*

FLOW PROCESS FROM NODE 13811.00 TO NODE 13811.50 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 586.02 DOWNSTREAM(FEET) = 437.69  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 696.28 CHANNEL SLOPE = 0.2130  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.43  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 2.497  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 14.79 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 27.10  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.00  
 AVERAGE FLOW DEPTH(FEET) = 0.42 TRAVEL TIME(MIN.) = 1.93  
 Tc(MIN.) = 14.23  
 SUBAREA AREA(ACRES) = 14.79 SUBAREA RUNOFF(CFS) = 29.25  
 EFFECTIVE AREA(ACRES) = 20.37 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 20.4 PEAK FLOW RATE(CFS) = 40.28  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.53  
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 0.53 FLOW VELOCITY(FEET/SEC.) = 6.88  
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13811.50 = 1344.82 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13811.50 TO NODE 13812.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 437.69 DOWNSTREAM(FEET) = 402.36  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 681.04 CHANNEL SLOPE = 0.0519  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.99  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 2.261  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 18.41 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 56.54  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.91  
 AVERAGE FLOW DEPTH(FEET) = 0.97 TRAVEL TIME(MIN.) = 2.31  
 Tc(MIN.) = 16.54  
 SUBAREA AREA(ACRES) = 18.41 SUBAREA RUNOFF(CFS) = 32.50  
 EFFECTIVE AREA(ACRES) = 38.78 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 38.8 PEAK FLOW RATE(CFS) = 68.45  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.08

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.08 FLOW VELOCITY(FEET/SEC.) = 5.21  
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13812.00 = 2025.86 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13812.00 TO NODE 13813.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 402.36 DOWNSTREAM(FEET) = 259.72  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1282.56 CHANNEL SLOPE = 0.1112  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.03  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 2.027  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 27.87 0.30 0.858 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.858  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 90.67  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.39  
 AVERAGE FLOW DEPTH(FEET) = 1.02 TRAVEL TIME(MIN.) = 2.89  
 Tc(MIN.) = 19.43  
 SUBAREA AREA(ACRES) = 27.87 SUBAREA RUNOFF(CFS) = 44.38  
 EFFECTIVE AREA(ACRES) = 66.65 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94  
 TOTAL AREA(ACRES) = 66.7 PEAK FLOW RATE(CFS) = 104.66  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.11

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.11 FLOW VELOCITY(FEET/SEC.) = 7.72  
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13813.00 = 3308.42 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 31  
 -----

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 259.72 DOWNSTREAM(FEET) = 137.00  
 FLOW LENGTH(FEET) = 2412.88 MANNING'S N = 0.013  
 ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000  
 DEPTH OF FLOW IN 36.0 INCH PIPE IS 22.9 INCHES  
 PIPE-FLOW VELOCITY(FEET/SEC.) = 22.06  
 ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1  
 PIPE-FLOW(CFS) = 104.66  
 PIPE TRAVEL TIME(MIN.) = 1.82 Tc(MIN.) = 21.26  
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13820.00 = 5721.30 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

```

=====
MAINLINE Tc(MIN.) = 21.26
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.918
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp        Ap        SCS
LAND USE                GROUP  (ACRES)  (INCH/HR)  (DECIMAL)  CN
USER-DEFINED            -      83.64    0.30      0.570      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.570
SUBAREA AREA(ACRES) = 83.64      SUBAREA RUNOFF(CFS) = 131.50
EFFECTIVE AREA(ACRES) = 150.29   AREA-AVERAGED Fm(INCH/HR) = 0.22
AREA-AVERAGED Fp(INCH/HR) = 0.30  AREA-AVERAGED Ap = 0.73
TOTAL AREA(ACRES) = 150.3        PEAK FLOW RATE(CFS) = 229.62

```

```

*****
FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 1
-----

```

```

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<
-----

```

```

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 21.26
RAINFALL INTENSITY(INCH/HR) = 1.92
AREA-AVERAGED Fm(INCH/HR) = 0.22
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.73
EFFECTIVE STREAM AREA(ACRES) = 150.29
TOTAL STREAM AREA(ACRES) = 150.29
PEAK FLOW RATE(CFS) AT CONFLUENCE = 229.62

```

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22406.68	18.92	2.069	0.30( 0.25)	0.83	4035.2	10600.00
1	27580.25	35.52	1.412	0.30( 0.25)	0.83	8756.9	10220.00
1	29468.42	42.43	1.283	0.30( 0.25)	0.83	11255.9	100.00
1	31747.16	50.83	1.150	0.30( 0.25)	0.84	15089.5	150.00
1	34108.33	65.41	1.012	0.30( 0.26)	0.86	22037.7	390.00
1	35694.57	78.00	0.941	0.30( 0.27)	0.89	28358.5	13100.00
1	36675.46	84.41	0.905	0.30( 0.27)	0.89	31187.4	11801.00
1	38535.38	94.86	0.855	0.30( 0.27)	0.90	36509.9	11530.00
1	39285.18	100.71	0.833	0.30( 0.27)	0.91	40247.0	13510.00
1	39979.38	106.36	0.812	0.30( 0.28)	0.92	43742.9	13010.00
1	41046.78	113.15	0.787	0.30( 0.28)	0.92	48152.6	11350.00
1	41404.74	117.82	0.769	0.30( 0.28)	0.93	51326.8	11130.00
1	40962.00	123.93	0.753	0.30( 0.28)	0.93	54253.3	12300.00
1	40146.66	132.76	0.734	0.30( 0.28)	0.94	58513.9	12400.00
1	39064.84	142.35	0.713	0.30( 0.28)	0.94	61915.5	12201.00
1	38066.59	149.91	0.697	0.30( 0.28)	0.94	63808.5	12231.00
1	37035.03	157.47	0.680	0.30( 0.28)	0.94	65361.3	10400.00
1	35438.81	167.04	0.660	0.30( 0.28)	0.94	66807.7	12010.00
1	34374.93	172.53	0.648	0.30( 0.28)	0.94	67070.2	10210.00
1	29926.71	203.36	0.610	0.30( 0.28)	0.94	67830.0	10100.00
2	229.62	21.26	1.918	0.30( 0.22)	0.73	150.3	13810.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22629.18	18.92	2.069	0.30( 0.25)	0.82	4168.9	10600.00
2	23365.37	21.26	1.918	0.30( 0.25)	0.82	4850.9	13810.00
3	27741.44	35.52	1.412	0.30( 0.25)	0.82	8907.2	10220.00
4	29612.12	42.43	1.283	0.30( 0.25)	0.82	11406.2	100.00
5	31872.96	50.83	1.150	0.30( 0.25)	0.84	15239.8	150.00
6	34215.46	65.41	1.012	0.30( 0.26)	0.86	22188.0	390.00
7	35792.06	78.00	0.941	0.30( 0.27)	0.88	28508.8	13100.00
8	36768.04	84.41	0.905	0.30( 0.27)	0.89	31337.7	11801.00
9	38621.21	94.86	0.855	0.30( 0.27)	0.90	36660.2	11530.00
10	39368.06	100.71	0.833	0.30( 0.27)	0.91	40397.3	13510.00
11	40059.40	106.36	0.812	0.30( 0.27)	0.92	43893.2	13010.00
12	41123.38	113.15	0.787	0.30( 0.28)	0.92	48302.8	11350.00
13	41478.98	117.82	0.769	0.30( 0.28)	0.93	51477.0	11130.00
14	41034.00	123.93	0.753	0.30( 0.28)	0.93	54403.6	12300.00
15	40216.09	132.76	0.734	0.30( 0.28)	0.94	58664.2	12400.00
16	39131.48	142.35	0.713	0.30( 0.28)	0.94	62065.8	12201.00
17	38131.04	149.91	0.697	0.30( 0.28)	0.94	63958.8	12231.00
18	37097.27	157.47	0.680	0.30( 0.28)	0.94	65511.6	10400.00
19	35498.27	167.04	0.660	0.30( 0.28)	0.94	66958.0	12010.00
20	34432.80	172.53	0.648	0.30( 0.28)	0.94	67220.5	10210.00
21	29979.41	203.36	0.610	0.30( 0.28)	0.94	67980.3	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

```

PEAK FLOW RATE(CFS) = 41478.98      Tc(MIN.) = 117.82
EFFECTIVE AREA(ACRES) = 51477.04   AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30   AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 67980.3
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13820.00 = 131542.95 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13820.00 TO NODE 13840.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<
-----

```

```

ELEVATION DATA: UPSTREAM(FEET) = 137.00  DOWNSTREAM(FEET) = 133.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1261.34  CHANNEL SLOPE = 0.0032
GIVEN CHANNEL BASE(FEET) = 100.00  CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 4.000  MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 17.00
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.764
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp        Ap        SCS
LAND USE                GROUP  (ACRES)  (INCH/HR)  (DECIMAL)  CN
USER-DEFINED            -      31.60    0.30      0.683      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.683
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 41486.93
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 14.53
AVERAGE FLOW DEPTH(FEET) = 17.00  TRAVEL TIME(MIN.) = 1.45
Tc(MIN.) = 119.27
SUBAREA AREA(ACRES) = 31.60      SUBAREA RUNOFF(CFS) = 15.89
EFFECTIVE AREA(ACRES) = 51508.64  AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30  AREA-AVERAGED Ap = 0.93

```

TOTAL AREA (ACRES) = 68011.9 PEAK FLOW RATE (CFS) = 41478.98  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 16.99

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 16.99 FLOW VELOCITY (FEET/SEC.) = 14.53  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13840.00 = 132804.30 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22629.18	20.64	1.949	0.30 ( 0.25)	0.82	4200.5	10600.00
2	23365.37	22.96	1.832	0.30 ( 0.25)	0.82	4882.5	13810.00
3	27741.44	37.15	1.379	0.30 ( 0.25)	0.82	8938.8	10220.00
4	29612.12	44.02	1.257	0.30 ( 0.25)	0.82	11437.8	100.00
5	31872.96	52.39	1.132	0.30 ( 0.25)	0.84	15271.4	150.00
6	34215.46	66.94	1.004	0.30 ( 0.26)	0.86	22219.6	390.00
7	35792.06	79.51	0.932	0.30 ( 0.27)	0.88	28540.4	13100.00
8	36768.04	85.90	0.896	0.30 ( 0.27)	0.89	31369.3	11801.00
9	38621.21	96.33	0.849	0.30 ( 0.27)	0.90	36691.8	11530.00
10	39368.06	102.18	0.828	0.30 ( 0.27)	0.91	40428.9	13510.00
11	40059.40	107.82	0.806	0.30 ( 0.27)	0.92	43924.8	13010.00
12	41123.38	114.60	0.781	0.30 ( 0.28)	0.92	48334.4	11350.00
13	41478.98	119.27	0.764	0.30 ( 0.28)	0.93	51508.6	11130.00
14	41034.00	125.38	0.749	0.30 ( 0.28)	0.93	54435.2	12300.00
15	40216.09	134.22	0.730	0.30 ( 0.28)	0.94	58695.8	12400.00
16	39131.48	143.82	0.710	0.30 ( 0.28)	0.94	62097.4	12201.00
17	38131.04	151.39	0.694	0.30 ( 0.28)	0.94	63990.4	12231.00
18	37097.27	158.96	0.677	0.30 ( 0.28)	0.94	65543.1	10400.00
19	35498.27	168.56	0.657	0.30 ( 0.28)	0.94	66989.6	12010.00
20	34432.80	174.05	0.645	0.30 ( 0.28)	0.94	67252.1	10210.00
21	29979.41	204.95	0.608	0.30 ( 0.28)	0.94	68011.9	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 41478.98 Tc (MIN.) = 119.27  
 AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA (ACRES) = 51508.64

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13820.00 TO NODE 13840.00 IS CODE = 1  
 -----

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

-----  
 TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
 TIME OF CONCENTRATION (MIN.) = 119.27  
 RAINFALL INTENSITY (INCH/HR) = 0.76  
 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93  
 EFFECTIVE STREAM AREA (ACRES) = 51508.64  
 TOTAL STREAM AREA (ACRES) = 68011.90  
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 41478.98

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13830.00 TO NODE 13831.00 IS CODE = 21  
 -----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH (FEET) = 744.71  
 ELEVATION DATA: UPSTREAM (FEET) = 1100.95 DOWNSTREAM (FEET) = 959.21

Tc = K \* [(LENGTH\*\* 3.00) / (ELEVATION CHANGE)] \*\* 0.20  
 SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 13.858  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 2.550

SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER						
"CHAPARRAL, BROADLEAF"	-	5.06	0.30	1.000	56	13.86
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30						
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000						
SUBAREA RUNOFF (CFS) = 10.25						
TOTAL AREA (ACRES) = 5.06 PEAK FLOW RATE (CFS) = 10.25						

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13831.00 TO NODE 13832.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 959.21 DOWNSTREAM (FEET) = 832.83  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1076.71 CHANNEL SLOPE = 0.1174  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT (FEET) = 0.65  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 2.219

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	32.57	0.30	1.000	-
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000					
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 38.54					
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.60					
AVERAGE FLOW DEPTH (FEET) = 0.61 TRAVEL TIME (MIN.) = 3.21					
Tc (MIN.) = 17.06					
SUBAREA AREA (ACRES) = 32.57 SUBAREA RUNOFF (CFS) = 56.25					
EFFECTIVE AREA (ACRES) = 37.63 AREA-AVERAGED Fm (INCH/HR) = 0.30					
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00					
TOTAL AREA (ACRES) = 37.6 PEAK FLOW RATE (CFS) = 64.99					
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0					
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060					
*ESTIMATED CHANNEL HEIGHT (FEET) = 0.83					

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 0.83 FLOW VELOCITY (FEET/SEC.) = 6.73  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13832.00 = 1821.42 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13832.00 TO NODE 13833.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

```

=====
ELEVATION DATA: UPSTREAM(FEET) = 832.83 DOWNSTREAM(FEET) = 572.49
CHANNEL LENGTH THRU SUBAREA(FEET) = 1883.58 CHANNEL SLOPE = 0.1382
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.97
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.928
SUBAREA LOSS RATE DATA(AMC II):
  DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp      Ap   SCS
    LAND USE         GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED         -      32.23    0.30    1.000  -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 88.65
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.85
AVERAGE FLOW DEPTH(FEET) = 0.95 TRAVEL TIME(MIN.) = 4.00
Tc(MIN.) = 21.06
SUBAREA AREA(ACRES) = 32.23 SUBAREA RUNOFF(CFS) = 47.22
EFFECTIVE AREA(ACRES) = 69.86 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 69.9 PEAK FLOW RATE(CFS) = 102.34
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.03

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.03 FLOW VELOCITY(FEET/SEC.) = 8.27
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13833.00 = 3705.00 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13833.00 TO NODE 13834.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====

```

```

ELEVATION DATA: UPSTREAM(FEET) = 572.49 DOWNSTREAM(FEET) = 471.65
CHANNEL LENGTH THRU SUBAREA(FEET) = 943.78 CHANNEL SLOPE = 0.1068
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.23
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.829
SUBAREA LOSS RATE DATA(AMC II):
  DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp      Ap   SCS
    LAND USE         GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED         -      27.51    0.30    1.000  -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 121.28
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.01
AVERAGE FLOW DEPTH(FEET) = 1.22 TRAVEL TIME(MIN.) = 1.96
Tc(MIN.) = 23.03
SUBAREA AREA(ACRES) = 27.51 SUBAREA RUNOFF(CFS) = 37.86
EFFECTIVE AREA(ACRES) = 97.37 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 97.4 PEAK FLOW RATE(CFS) = 134.01
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.29

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.29 FLOW VELOCITY(FEET/SEC.) = 8.24
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13834.00 = 4648.78 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13834.00 TO NODE 13835.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====

```

```

ELEVATION DATA: UPSTREAM(FEET) = 471.65 DOWNSTREAM(FEET) = 347.06
CHANNEL LENGTH THRU SUBAREA(FEET) = 1647.45 CHANNEL SLOPE = 0.0756
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.77
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.673
SUBAREA LOSS RATE DATA(AMC II):
  DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp      Ap   SCS
    LAND USE         GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED         -      94.21    0.30    1.000  -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 192.28
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.18
AVERAGE FLOW DEPTH(FEET) = 1.74 TRAVEL TIME(MIN.) = 3.36
Tc(MIN.) = 26.38
SUBAREA AREA(ACRES) = 94.21 SUBAREA RUNOFF(CFS) = 116.41
EFFECTIVE AREA(ACRES) = 191.58 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 191.6 PEAK FLOW RATE(CFS) = 236.72
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.95

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.95 FLOW VELOCITY(FEET/SEC.) = 8.73
LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13835.00 = 6296.23 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13835.00 TO NODE 13836.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====

```

```

ELEVATION DATA: UPSTREAM(FEET) = 347.06 DOWNSTREAM(FEET) = 269.29
CHANNEL LENGTH THRU SUBAREA(FEET) = 1696.71 CHANNEL SLOPE = 0.0458
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.88
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.531
SUBAREA LOSS RATE DATA(AMC II):
  DEVELOPMENT TYPE/   SCS SOIL   AREA      Fp      Ap   SCS
    LAND USE         GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED         -      233.25    0.30    1.000  -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 366.16

```

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.28  
 AVERAGE FLOW DEPTH (FEET) = 2.83 TRAVEL TIME (MIN.) = 3.42  
 Tc (MIN.) = 29.80  
 SUBAREA AREA (ACRES) = 233.25 SUBAREA RUNOFF (CFS) = 258.52  
 EFFECTIVE AREA (ACRES) = 424.83 AREA-AVERAGED Fm (INCH/HR) = 0.30  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA (ACRES) = 424.8 PEAK FLOW RATE (CFS) = 470.85  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 3.22

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 3.22 FLOW VELOCITY (FEET/SEC.) = 8.89  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13836.00 = 7992.94 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13836.00 TO NODE 13837.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 269.29 DOWNSTREAM (FEET) = 191.87  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 2529.21 CHANNEL SLOPE = 0.0306  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 3.86  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.421

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	134.70	0.30	0.880	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.880  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 540.99  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.98  
 AVERAGE FLOW DEPTH (FEET) = 3.83 TRAVEL TIME (MIN.) = 5.28  
 Tc (MIN.) = 35.08  
 SUBAREA AREA (ACRES) = 134.70 SUBAREA RUNOFF (CFS) = 140.27  
 EFFECTIVE AREA (ACRES) = 559.53 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97  
 TOTAL AREA (ACRES) = 559.5 PEAK FLOW RATE (CFS) = 568.89  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 3.93

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 3.93 FLOW VELOCITY (FEET/SEC.) = 8.09  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13837.00 = 10522.15 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 31  
 -----

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 191.87 DOWNSTREAM (FEET) = 133.00  
 FLOW LENGTH (FEET) = 1151.02 MANNING'S N = 0.013  
 DEPTH OF FLOW IN 63.0 INCH PIPE IS 46.5 INCHES

PIPE-FLOW VELOCITY (FEET/SEC.) = 33.24  
 ESTIMATED PIPE DIAMETER (INCH) = 63.00 NUMBER OF PIPES = 1  
 PIPE-FLOW (CFS) = 568.89  
 PIPE TRAVEL TIME (MIN.) = 0.58 Tc (MIN.) = 35.65  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13840.00 = 11673.17 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 35.65  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.409  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.97	0.30	0.622	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.622  
 SUBAREA AREA (ACRES) = 5.97 SUBAREA RUNOFF (CFS) = 6.57  
 EFFECTIVE AREA (ACRES) = 565.50 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97  
 TOTAL AREA (ACRES) = 565.5 PEAK FLOW RATE (CFS) = 569.62

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 1  
 -----

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
 TIME OF CONCENTRATION (MIN.) = 35.65  
 RAINFALL INTENSITY (INCH/HR) = 1.41  
 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.97  
 EFFECTIVE STREAM AREA (ACRES) = 565.50  
 TOTAL STREAM AREA (ACRES) = 565.50  
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 569.62

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22629.18	20.64	1.949	0.30 ( 0.25)	0.82	4200.5	10600.00
1	23365.37	22.96	1.832	0.30 ( 0.25)	0.82	4882.5	13810.00
1	27741.44	37.15	1.379	0.30 ( 0.25)	0.82	8938.8	10220.00
1	29612.12	44.02	1.257	0.30 ( 0.25)	0.82	11437.8	100.00
1	31872.96	52.39	1.132	0.30 ( 0.25)	0.84	15271.4	150.00
1	34215.46	66.94	1.004	0.30 ( 0.26)	0.86	22219.6	390.00
1	35792.06	79.51	0.932	0.30 ( 0.27)	0.88	28540.4	13100.00
1	36768.04	85.90	0.896	0.30 ( 0.27)	0.89	31369.3	11801.00
1	38621.21	96.33	0.849	0.30 ( 0.27)	0.90	36691.8	11530.00
1	39368.06	102.18	0.828	0.30 ( 0.27)	0.91	40428.9	13510.00
1	40059.40	107.82	0.806	0.30 ( 0.27)	0.92	43924.8	13010.00
1	41123.38	114.60	0.781	0.30 ( 0.28)	0.92	48334.4	11350.00
1	41478.98	119.27	0.764	0.30 ( 0.28)	0.93	51508.6	11130.00
1	41034.00	125.38	0.749	0.30 ( 0.28)	0.93	54435.2	12300.00



1	40216.09	134.22	0.730	0.30	( 0.28)	0.94	58695.8	12400.00
1	39131.48	143.82	0.710	0.30	( 0.28)	0.94	62097.4	12201.00
1	38131.04	151.39	0.694	0.30	( 0.28)	0.94	63990.4	12231.00
1	37097.27	158.96	0.677	0.30	( 0.28)	0.94	65543.1	10400.00
1	35498.27	168.56	0.657	0.30	( 0.28)	0.94	66989.6	12010.00
1	34432.80	174.05	0.645	0.30	( 0.28)	0.94	67252.1	10210.00
1	29979.41	204.95	0.608	0.30	( 0.28)	0.94	68011.9	10100.00
2	569.62	35.65	1.409	0.30	( 0.29)	0.97	565.5	13830.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23117.87	20.64	1.949	0.30 ( 0.25)	0.83	4527.9	10600.00
2	23870.85	22.96	1.832	0.30 ( 0.25)	0.83	5246.7	13810.00
3	27850.40	35.65	1.409	0.30 ( 0.25)	0.83	9077.3	13830.00
4	28295.78	37.15	1.379	0.30 ( 0.25)	0.83	9504.3	10220.00
5	30104.15	44.02	1.257	0.30 ( 0.25)	0.83	12003.3	100.00
6	32301.46	52.39	1.132	0.30 ( 0.25)	0.84	15836.9	150.00
7	34578.60	66.94	1.004	0.30 ( 0.26)	0.87	22785.1	390.00
8	36118.95	79.51	0.932	0.30 ( 0.27)	0.89	29105.9	13100.00
9	37076.48	85.90	0.896	0.30 ( 0.27)	0.89	31934.8	11801.00
10	38905.82	96.33	0.849	0.30 ( 0.27)	0.90	37257.3	11530.00
11	39641.56	102.18	0.828	0.30 ( 0.27)	0.91	40994.4	13510.00
12	40322.17	107.82	0.806	0.30 ( 0.28)	0.92	44490.3	13010.00
13	41373.27	114.60	0.781	0.30 ( 0.28)	0.92	48899.9	11350.00
14	41720.00	119.27	0.764	0.30 ( 0.28)	0.93	52074.1	11130.00
15	41267.75	125.38	0.749	0.30 ( 0.28)	0.93	55000.7	12300.00
16	40440.17	134.22	0.730	0.30 ( 0.28)	0.94	59261.3	12400.00
17	39345.04	143.82	0.710	0.30 ( 0.28)	0.94	62662.9	12201.00
18	38336.32	151.39	0.694	0.30 ( 0.28)	0.94	64555.9	12231.00
19	37294.27	158.96	0.677	0.30 ( 0.28)	0.94	66108.6	10400.00
20	35684.77	168.56	0.657	0.30 ( 0.28)	0.94	67555.1	12010.00
21	34613.29	174.05	0.645	0.30 ( 0.28)	0.94	67817.6	10210.00
22	30141.40	204.95	0.608	0.30 ( 0.28)	0.94	68577.4	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 41720.00 Tc (MIN.) = 119.27  
EFFECTIVE AREA(ACRES) = 52074.14 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA(ACRES) = 68577.4  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13840.00 = 132804.30 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13840.00 TO NODE 13860.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 133.00 DOWNSTREAM(FEET) = 130.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 654.44 CHANNEL SLOPE = 0.0046  
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 15.50  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.761  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 6.61 0.30 0.975 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.975  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 41721.40  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 16.62  
AVERAGE FLOW DEPTH(FEET) = 15.50 TRAVEL TIME(MIN.) = 0.66  
Tc(MIN.) = 119.93  
SUBAREA AREA(ACRES) = 6.61 SUBAREA RUNOFF(CFS) = 2.79  
EFFECTIVE AREA(ACRES) = 52080.75 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA(ACRES) = 68584.0 PEAK FLOW RATE(CFS) = 41720.00  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 15.50

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 15.50 FLOW VELOCITY(FEET/SEC.) = 16.61  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13860.00 = 133458.73 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23117.87	21.42	1.910	0.30 ( 0.25)	0.83	4534.5	10600.00
2	23870.85	23.73	1.794	0.30 ( 0.25)	0.83	5253.3	13810.00
3	27850.40	36.39	1.395	0.30 ( 0.25)	0.83	9083.9	13830.00
4	28295.78	37.88	1.365	0.30 ( 0.25)	0.83	9510.9	10220.00
5	30104.15	44.74	1.245	0.30 ( 0.25)	0.83	12009.9	100.00
6	32301.46	53.09	1.124	0.30 ( 0.25)	0.84	15843.5	150.00
7	34578.60	67.63	1.000	0.30 ( 0.26)	0.87	22791.7	390.00
8	36118.95	80.19	0.929	0.30 ( 0.27)	0.89	29112.5	13100.00
9	37076.48	86.58	0.892	0.30 ( 0.27)	0.89	31941.4	11801.00
10	38905.82	97.00	0.847	0.30 ( 0.27)	0.90	37263.9	11530.00
11	39641.56	102.84	0.825	0.30 ( 0.27)	0.91	41001.0	13510.00
12	40322.17	108.49	0.804	0.30 ( 0.28)	0.92	44496.9	13010.00
13	41373.27	115.26	0.779	0.30 ( 0.28)	0.92	48906.6	11350.00
14	41720.00	119.93	0.761	0.30 ( 0.28)	0.93	52080.8	11130.00
15	41267.75	126.04	0.748	0.30 ( 0.28)	0.93	55007.3	12300.00
16	40440.17	134.88	0.729	0.30 ( 0.28)	0.94	59267.9	12400.00
17	39345.04	144.49	0.708	0.30 ( 0.28)	0.94	62669.5	12201.00
18	38336.32	152.06	0.692	0.30 ( 0.28)	0.94	64562.5	12231.00
19	37294.27	159.64	0.676	0.30 ( 0.28)	0.94	66115.3	10400.00
20	35684.77	169.24	0.655	0.30 ( 0.28)	0.94	67561.7	12010.00
21	34613.29	174.74	0.643	0.30 ( 0.28)	0.94	67824.2	10210.00
22	30141.40	205.67	0.608	0.30 ( 0.28)	0.94	68584.0	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 41720.00 Tc(MIN.) = 119.93  
AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 52080.75

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13840.00 TO NODE 13860.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

=====

TOTAL NUMBER OF STREAMS = 2

CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
TIME OF CONCENTRATION(MIN.) = 119.93  
RAINFALL INTENSITY (INCH/HR) = 0.76  
AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.93  
EFFECTIVE STREAM AREA (ACRES) = 52080.75  
TOTAL STREAM AREA (ACRES) = 68584.01  
PEAK FLOW RATE (CFS) AT CONFLUENCE = 41720.00

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13850.00 TO NODE 13851.00 IS CODE = 21  
-----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<  
=====

INITIAL SUBAREA FLOW-LENGTH (FEET) = 617.57  
ELEVATION DATA: UPSTREAM (FEET) = 646.95 DOWNSTREAM (FEET) = 490.10

Tc = K \* [(LENGTH\*\* 3.00) / (ELEVATION CHANGE)] \*\* 0.20  
SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 12.137  
\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 2.797  
SUBAREA Tc AND LOSS RATE DATA (AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)  
NATURAL FAIR COVER  
"CHAPARRAL, BROADLEAF" - 4.95 0.30 1.000 56 12.14  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA RUNOFF (CFS) = 11.12  
TOTAL AREA (ACRES) = 4.95 PEAK FLOW RATE (CFS) = 11.12

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13851.00 TO NODE 13851.50 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<  
=====

ELEVATION DATA: UPSTREAM (FEET) = 490.10 DOWNSTREAM (FEET) = 440.98  
CHANNEL LENGTH THRU SUBAREA (FEET) = 351.14 CHANNEL SLOPE = 0.1399  
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 0.34  
\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 2.598  
SUBAREA LOSS RATE DATA (AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 4.02 0.30 1.000 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 15.29  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.23  
AVERAGE FLOW DEPTH (FEET) = 0.34 TRAVEL TIME (MIN.) = 1.38  
Tc (MIN.) = 13.52  
SUBAREA AREA (ACRES) = 4.02 SUBAREA RUNOFF (CFS) = 8.32  
EFFECTIVE AREA (ACRES) = 8.97 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA (ACRES) = 9.0 PEAK FLOW RATE (CFS) = 18.56

GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 0.38

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 0.38 FLOW VELOCITY (FEET/SEC.) = 4.58  
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13851.50 = 968.71 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13851.50 TO NODE 13852.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<  
=====

ELEVATION DATA: UPSTREAM (FEET) = 440.98 DOWNSTREAM (FEET) = 395.76  
CHANNEL LENGTH THRU SUBAREA (FEET) = 512.91 CHANNEL SLOPE = 0.0882  
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 0.53  
\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 2.349  
SUBAREA LOSS RATE DATA (AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 7.17 0.30 1.000 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 25.17  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.42  
AVERAGE FLOW DEPTH (FEET) = 0.52 TRAVEL TIME (MIN.) = 1.93  
Tc (MIN.) = 15.45  
SUBAREA AREA (ACRES) = 7.17 SUBAREA RUNOFF (CFS) = 13.22  
EFFECTIVE AREA (ACRES) = 16.14 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA (ACRES) = 16.1 PEAK FLOW RATE (CFS) = 29.77  
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 0.57

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 0.57 FLOW VELOCITY (FEET/SEC.) = 4.69  
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13852.00 = 1481.62 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13852.00 TO NODE 13853.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<  
=====

ELEVATION DATA: UPSTREAM (FEET) = 395.76 DOWNSTREAM (FEET) = 354.94  
CHANNEL LENGTH THRU SUBAREA (FEET) = 443.69 CHANNEL SLOPE = 0.0920  
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 0.63  
\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 2.230  
SUBAREA LOSS RATE DATA (AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 6.76 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 35.64  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.04  
AVERAGE FLOW DEPTH(FEET) = 0.63 TRAVEL TIME(MIN.) = 1.47  
Tc(MIN.) = 16.92  
SUBAREA AREA(ACRES) = 6.76 SUBAREA RUNOFF(CFS) = 11.74  
EFFECTIVE AREA(ACRES) = 22.90 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 22.9 PEAK FLOW RATE(CFS) = 39.79  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.67

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.67 FLOW VELOCITY(FEET/SEC.) = 5.25  
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13853.00 = 1925.31 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13853.00 TO NODE 13854.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 354.94 DOWNSTREAM(FEET) = 263.57  
CHANNEL LENGTH THRU SUBAREA(FEET) = 962.09 CHANNEL SLOPE = 0.0950  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.81  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.009

SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 18.16 0.30 1.000 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 53.77  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.87  
AVERAGE FLOW DEPTH(FEET) = 0.79 TRAVEL TIME(MIN.) = 2.73  
Tc(MIN.) = 19.65  
SUBAREA AREA(ACRES) = 18.16 SUBAREA RUNOFF(CFS) = 27.94  
EFFECTIVE AREA(ACRES) = 41.06 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 41.1 PEAK FLOW RATE(CFS) = 63.16  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.87

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.87 FLOW VELOCITY(FEET/SEC.) = 6.21  
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13854.00 = 2887.40 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13854.00 TO NODE 13855.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 263.57 DOWNSTREAM(FEET) = 188.74  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1228.77 CHANNEL SLOPE = 0.0609  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.23  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.828

SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 38.75 0.30 0.879 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.879  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 90.46  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.02  
AVERAGE FLOW DEPTH(FEET) = 1.21 TRAVEL TIME(MIN.) = 3.40  
Tc(MIN.) = 23.06  
SUBAREA AREA(ACRES) = 38.75 SUBAREA RUNOFF(CFS) = 54.54  
EFFECTIVE AREA(ACRES) = 79.81 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94  
TOTAL AREA(ACRES) = 79.8 PEAK FLOW RATE(CFS) = 111.00  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.36

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 1.36 FLOW VELOCITY(FEET/SEC.) = 6.41  
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13855.00 = 4116.17 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 31  
-----

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 188.74 DOWNSTREAM(FEET) = 130.00  
FLOW LENGTH(FEET) = 2092.67 MANNING'S N = 0.013  
DEPTH OF FLOW IN 39.0 INCH PIPE IS 27.5 INCHES  
PIPE-FLOW VELOCITY(FEET/SEC.) = 17.74  
ESTIMATED PIPE DIAMETER(INCH) = 39.00 NUMBER OF PIPES = 1  
PIPE-FLOW(CFS) = 111.00  
PIPE TRAVEL TIME(MIN.) = 1.97 Tc(MIN.) = 25.02  
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13860.00 = 6208.84 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 25.02  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 1.729  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 43.41 0.30 0.707 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.707  
SUBAREA AREA(ACRES) = 43.41 SUBAREA RUNOFF(CFS) = 59.27  
EFFECTIVE AREA(ACRES) = 123.22 AREA-AVERAGED Fm(INCH/HR) = 0.26

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.86  
 TOTAL AREA(ACRES) = 123.2 PEAK FLOW RATE(CFS) = 163.19

\*\*\*\*\*

FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
 TIME OF CONCENTRATION(MIN.) = 25.02  
 RAINFALL INTENSITY(INCH/HR) = 1.73  
 AREA-AVERAGED Fm(INCH/HR) = 0.26  
 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.86  
 EFFECTIVE STREAM AREA(ACRES) = 123.22  
 TOTAL STREAM AREA(ACRES) = 123.22  
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 163.19

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23117.87	21.42	1.910	0.30( 0.25)	0.83	4534.5	10600.00
1	23870.85	23.73	1.794	0.30( 0.25)	0.83	5253.3	13810.00
1	27850.40	36.39	1.395	0.30( 0.25)	0.83	9083.9	13830.00
1	28295.78	37.88	1.365	0.30( 0.25)	0.83	9510.9	10220.00
1	30104.15	44.74	1.245	0.30( 0.25)	0.83	12009.9	100.00
1	32301.46	53.09	1.124	0.30( 0.25)	0.84	15843.5	150.00
1	34578.60	67.63	1.000	0.30( 0.26)	0.87	22791.7	390.00
1	36118.95	80.19	0.929	0.30( 0.27)	0.89	29112.5	13100.00
1	37076.48	86.58	0.892	0.30( 0.27)	0.89	31941.4	11801.00
1	38905.82	97.00	0.847	0.30( 0.27)	0.90	37263.9	11530.00
1	39641.56	102.84	0.825	0.30( 0.27)	0.91	41001.0	13510.00
1	40322.17	108.49	0.804	0.30( 0.28)	0.92	44496.9	13010.00
1	41373.27	115.26	0.779	0.30( 0.28)	0.92	48906.6	11350.00
1	41720.00	119.93	0.761	0.30( 0.28)	0.93	52080.8	11130.00
1	41267.75	126.04	0.748	0.30( 0.28)	0.93	55007.3	12300.00
1	40440.17	134.88	0.729	0.30( 0.28)	0.94	59267.9	12400.00
1	39345.04	144.49	0.708	0.30( 0.28)	0.94	62669.5	12201.00
1	38336.32	152.06	0.692	0.30( 0.28)	0.94	64562.5	12231.00
1	37294.27	159.64	0.676	0.30( 0.28)	0.94	66115.3	10400.00
1	35684.77	169.24	0.655	0.30( 0.28)	0.94	67561.7	12010.00
1	34613.29	174.74	0.643	0.30( 0.28)	0.94	67824.2	10210.00
1	30141.40	205.67	0.608	0.30( 0.28)	0.94	68584.0	10100.00
2	163.19	25.02	1.729	0.30( 0.26)	0.86	123.2	13850.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23274.71	21.42	1.910	0.30( 0.25)	0.83	4640.0	10600.00
2	24032.43	23.73	1.794	0.30( 0.25)	0.83	5370.2	13810.00
3	24438.81	25.02	1.729	0.30( 0.25)	0.83	5766.1	13850.00
4	27976.49	36.39	1.395	0.30( 0.25)	0.83	9207.1	13830.00
5	28418.55	37.88	1.365	0.30( 0.25)	0.83	9634.1	10220.00

6	30213.68	44.74	1.245	0.30( 0.25)	0.83	12133.2	100.00
7	32397.53	53.09	1.124	0.30( 0.25)	0.84	15966.8	150.00
8	34660.91	67.63	1.000	0.30( 0.26)	0.87	22915.0	390.00
9	36193.36	80.19	0.929	0.30( 0.27)	0.89	29235.7	13100.00
10	37146.88	86.58	0.892	0.30( 0.27)	0.89	32064.6	11801.00
11	38971.17	97.00	0.847	0.30( 0.27)	0.90	37387.2	11530.00
12	39704.49	102.84	0.825	0.30( 0.27)	0.91	41124.2	13510.00
13	40382.77	108.49	0.804	0.30( 0.28)	0.92	44620.1	13010.00
14	41431.06	115.26	0.779	0.30( 0.28)	0.92	49029.8	11350.00
15	41775.86	119.93	0.761	0.30( 0.28)	0.93	52204.0	11130.00
16	41322.14	126.04	0.748	0.30( 0.28)	0.93	55130.6	12300.00
17	40492.45	134.88	0.729	0.30( 0.28)	0.94	59391.1	12400.00
18	39395.04	144.49	0.708	0.30( 0.28)	0.94	62792.7	12201.00
19	38384.51	152.06	0.692	0.30( 0.28)	0.94	64685.8	12231.00
20	37340.65	159.64	0.676	0.30( 0.28)	0.94	66238.5	10400.00
21	35728.86	169.24	0.655	0.30( 0.28)	0.94	67684.9	12010.00
22	34656.06	174.74	0.643	0.30( 0.28)	0.94	67947.5	10210.00
23	30180.23	205.67	0.608	0.30( 0.28)	0.94	68707.2	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 41775.86 Tc(MIN.) = 119.93  
 EFFECTIVE AREA(ACRES) = 52203.97 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 68707.2  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13860.00 = 133458.73 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13860.00 TO NODE 13880.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 130.00 DOWNSTREAM(FEET) = 120.57  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 610.77 CHANNEL SLOPE = 0.0154  
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 11.26  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.760  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	4.89	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 41776.88  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 25.57  
 AVERAGE FLOW DEPTH(FEET) = 11.26 TRAVEL TIME(MIN.) = 0.40  
 Tc(MIN.) = 120.32

SUBAREA AREA(ACRES) = 4.89 SUBAREA RUNOFF(CFS) = 2.03  
 EFFECTIVE AREA(ACRES) = 52208.86 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 68712.1 PEAK FLOW RATE(CFS) = 41775.86  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 11.26

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 11.26 FLOW VELOCITY(FEET/SEC.) = 25.57  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13880.00 = 134069.50 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23274.71	21.89	1.886	0.30 ( 0.25)	0.83	4644.8	10600.00
2	24032.43	24.20	1.770	0.30 ( 0.25)	0.83	5375.1	13810.00
3	24438.81	25.49	1.710	0.30 ( 0.25)	0.83	5771.0	13850.00
4	27976.49	36.84	1.386	0.30 ( 0.25)	0.83	9212.0	13830.00
5	28418.55	38.33	1.356	0.30 ( 0.25)	0.83	9639.0	10220.00
6	30213.68	45.18	1.238	0.30 ( 0.25)	0.83	12138.1	100.00
7	32397.53	53.52	1.119	0.30 ( 0.25)	0.84	15971.7	150.00
8	34660.91	68.06	0.997	0.30 ( 0.26)	0.87	22919.8	390.00
9	36193.36	80.61	0.926	0.30 ( 0.27)	0.89	29240.6	13100.00
10	37146.88	87.00	0.890	0.30 ( 0.27)	0.89	32069.5	11801.00
11	38971.17	97.41	0.845	0.30 ( 0.27)	0.90	37392.1	11530.00
12	39704.49	103.25	0.824	0.30 ( 0.27)	0.91	41129.1	13510.00
13	40382.77	108.89	0.802	0.30 ( 0.28)	0.92	44625.0	13010.00
14	41431.06	115.66	0.777	0.30 ( 0.28)	0.92	49034.7	11350.00
15	41775.86	120.32	0.760	0.30 ( 0.28)	0.93	52208.9	11130.00
16	41322.14	126.44	0.747	0.30 ( 0.28)	0.93	55135.4	12300.00
17	40492.45	135.28	0.728	0.30 ( 0.28)	0.94	59396.0	12400.00
18	39395.04	144.89	0.707	0.30 ( 0.28)	0.94	62797.6	12201.00
19	38384.51	152.47	0.691	0.30 ( 0.28)	0.94	64690.6	12231.00
20	37340.65	160.05	0.675	0.30 ( 0.28)	0.94	66243.4	10400.00
21	35728.86	169.66	0.654	0.30 ( 0.28)	0.94	67689.8	12010.00
22	34656.06	175.16	0.642	0.30 ( 0.28)	0.94	67952.4	10210.00
23	30180.23	206.11	0.607	0.30 ( 0.28)	0.94	68712.1	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 41775.86 Tc(MIN.) = 120.32  
AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 52208.86

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13860.00 TO NODE 13880.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
TIME OF CONCENTRATION(MIN.) = 120.32  
RAINFALL INTENSITY(INCH/HR) = 0.76  
AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.93  
EFFECTIVE STREAM AREA(ACRES) = 52208.86  
TOTAL STREAM AREA(ACRES) = 68712.12  
PEAK FLOW RATE(CFS) AT CONFLUENCE = 41775.86

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13870.00 TO NODE 13871.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 872.65  
ELEVATION DATA: UPSTREAM(FEET) = 558.52 DOWNSTREAM(FEET) = 436.47

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 15.704  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.329  
SUBAREA Tc AND LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)  
NATURAL FAIR COVER  
"GRASS" - 7.32 0.30 1.000 56 15.70  
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA RUNOFF(CFS) = 13.37  
TOTAL AREA(ACRES) = 7.32 PEAK FLOW RATE(CFS) = 13.37

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13871.00 TO NODE 13872.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 436.47 DOWNSTREAM(FEET) = 337.62  
CHANNEL LENGTH THRU SUBAREA(FEET) = 827.95 CHANNEL SLOPE = 0.1194  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.48  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.094

SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 13.01 0.30 1.000 -  
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 23.90  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.75  
AVERAGE FLOW DEPTH(FEET) = 0.46 TRAVEL TIME(MIN.) = 2.91  
Tc(MIN.) = 18.61  
SUBAREA AREA(ACRES) = 13.01 SUBAREA RUNOFF(CFS) = 21.00  
EFFECTIVE AREA(ACRES) = 20.33 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 20.3 PEAK FLOW RATE(CFS) = 32.82  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.55

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.55 FLOW VELOCITY(FEET/SEC.) = 5.33  
LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13872.00 = 1700.60 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13872.00 TO NODE 13873.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 337.62 DOWNSTREAM(FEET) = 253.88  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1049.16 CHANNEL SLOPE = 0.0798  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT (FEET) = 0.88  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.895  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 32.99 0.30 0.923 -  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.923  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 56.89  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.65  
 AVERAGE FLOW DEPTH (FEET) = 0.86 TRAVEL TIME (MIN.) = 3.10  
 Tc (MIN.) = 21.70  
 SUBAREA AREA (ACRES) = 32.99 SUBAREA RUNOFF (CFS) = 48.06  
 EFFECTIVE AREA (ACRES) = 53.32 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95  
 TOTAL AREA (ACRES) = 53.3 PEAK FLOW RATE (CFS) = 77.25  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 1.03

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 1.03 FLOW VELOCITY (FEET/SEC.) = 6.25  
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13873.00 = 2749.76 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13873.00 TO NODE 13874.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM (FEET) = 253.88 DOWNSTREAM (FEET) = 160.73  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1518.60 CHANNEL SLOPE = 0.0613  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT (FEET) = 1.01  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.739  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 30.94 0.30 0.900 -  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.900  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 97.73  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.12  
 AVERAGE FLOW DEPTH (FEET) = 1.00 TRAVEL TIME (MIN.) = 3.12  
 Tc (MIN.) = 24.82  
 SUBAREA AREA (ACRES) = 30.94 SUBAREA RUNOFF (CFS) = 40.91  
 EFFECTIVE AREA (ACRES) = 84.26 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 84.3 PEAK FLOW RATE (CFS) = 110.65  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 1.07

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 1.07 FLOW VELOCITY (FEET/SEC.) = 8.49  
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13874.00 = 4268.36 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13874.00 TO NODE 13875.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM (FEET) = 160.73 DOWNSTREAM (FEET) = 158.14  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 582.74 CHANNEL SLOPE = 0.0044  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT (FEET) = 2.72  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.631  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 73.67 0.30 0.930 -  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.930  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 155.49  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 3.76  
 AVERAGE FLOW DEPTH (FEET) = 2.69 TRAVEL TIME (MIN.) = 2.58  
 Tc (MIN.) = 27.40  
 SUBAREA AREA (ACRES) = 73.67 SUBAREA RUNOFF (CFS) = 89.62  
 EFFECTIVE AREA (ACRES) = 157.93 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 157.9 PEAK FLOW RATE (CFS) = 192.04  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 3.00

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 3.00 FLOW VELOCITY (FEET/SEC.) = 4.00  
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13875.00 = 4851.10 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 31  
 -----

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<  
 =====

ELEVATION DATA: UPSTREAM (FEET) = 158.14 DOWNSTREAM (FEET) = 120.57  
 FLOW LENGTH (FEET) = 1855.67 MANNING'S N = 0.013  
 DEPTH OF FLOW IN 48.0 INCH PIPE IS 38.9 INCHES  
 PIPE-FLOW VELOCITY (FEET/SEC.) = 17.59  
 ESTIMATED PIPE DIAMETER (INCH) = 48.00 NUMBER OF PIPES = 1  
 PIPE-FLOW (CFS) = 192.04  
 PIPE TRAVEL TIME (MIN.) = 1.76 Tc (MIN.) = 29.16  
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13880.00 = 6706.77 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 =====

MAINLINE Tc (MIN.) = 29.16  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 1.558  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS

LAND USE            GROUP    (ACRES)    (INCH/HR)    (DECIMAL)    CN  
 USER-DEFINED       -            34.90       0.30       0.743       -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.743  
 SUBAREA AREA(ACRES) = 34.90       SUBAREA RUNOFF(CFS) = 41.93  
 EFFECTIVE AREA(ACRES) = 192.83    AREA-AVERAGED Fm(INCH/HR) = 0.27  
 AREA-AVERAGED Fp(INCH/HR) = 0.30    AREA-AVERAGED Ap = 0.90  
 TOTAL AREA(ACRES) = 192.8        PEAK FLOW RATE(CFS) = 223.63

\*\*\*\*\*

FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
 TIME OF CONCENTRATION(MIN.) = 29.16  
 RAINFALL INTENSITY(INCH/HR) = 1.56  
 AREA-AVERAGED Fm(INCH/HR) = 0.27  
 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.90  
 EFFECTIVE STREAM AREA(ACRES) = 192.83  
 TOTAL STREAM AREA(ACRES) = 192.83  
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 223.63

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23274.71	21.89	1.886	0.30( 0.25)	0.83	4644.8	10600.00
1	24032.43	24.20	1.770	0.30( 0.25)	0.83	5375.1	13810.00
1	24438.81	25.49	1.710	0.30( 0.25)	0.83	5771.0	13850.00
1	27976.49	36.84	1.386	0.30( 0.25)	0.83	9212.0	13830.00
1	28418.55	38.33	1.356	0.30( 0.25)	0.83	9639.0	10220.00
1	30213.68	45.18	1.238	0.30( 0.25)	0.83	12138.1	100.00
1	32397.53	53.52	1.119	0.30( 0.25)	0.84	15971.7	150.00
1	34660.91	68.06	0.997	0.30( 0.26)	0.87	22919.8	390.00
1	36193.36	80.61	0.926	0.30( 0.27)	0.89	29240.6	13100.00
1	37146.88	87.00	0.890	0.30( 0.27)	0.89	32069.5	11801.00
1	38971.17	97.41	0.845	0.30( 0.27)	0.90	37392.1	11530.00
1	39704.49	103.25	0.824	0.30( 0.27)	0.91	41129.1	13510.00
1	40382.77	108.89	0.802	0.30( 0.28)	0.92	44625.0	13010.00
1	41431.06	115.66	0.777	0.30( 0.28)	0.92	49034.7	11350.00
1	41775.86	120.32	0.760	0.30( 0.28)	0.93	52208.9	11130.00
1	41322.14	126.44	0.747	0.30( 0.28)	0.93	55135.4	12300.00
1	40492.45	135.28	0.728	0.30( 0.28)	0.94	59396.0	12400.00
1	39395.04	144.89	0.707	0.30( 0.28)	0.94	62797.6	12201.00
1	38384.51	152.47	0.691	0.30( 0.28)	0.94	64690.6	12231.00
1	37340.65	160.05	0.675	0.30( 0.28)	0.94	66243.4	10400.00
1	35728.86	169.66	0.654	0.30( 0.28)	0.94	67689.8	12010.00
1	34656.06	175.16	0.642	0.30( 0.28)	0.94	67952.4	10210.00
1	30180.23	206.11	0.607	0.30( 0.28)	0.94	68712.1	10100.00
2	223.63	29.16	1.558	0.30( 0.27)	0.90	192.8	13870.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23485.37	21.89	1.886	0.30( 0.25)	0.84	4789.6	10600.00
2	24248.61	24.20	1.770	0.30( 0.25)	0.83	5535.1	13810.00
3	24657.34	25.49	1.710	0.30( 0.25)	0.83	5939.6	13850.00
4	25806.66	29.16	1.558	0.30( 0.25)	0.83	7076.8	13870.00
5	28170.22	36.84	1.386	0.30( 0.25)	0.83	9404.8	13830.00
6	28607.10	38.33	1.356	0.30( 0.25)	0.83	9831.8	10220.00
7	30381.84	45.18	1.238	0.30( 0.25)	0.83	12330.9	100.00
8	32544.97	53.52	1.119	0.30( 0.25)	0.84	16164.5	150.00
9	34787.28	68.06	0.997	0.30( 0.26)	0.87	23112.7	390.00
10	36307.38	80.61	0.926	0.30( 0.27)	0.89	29433.4	13100.00
11	37254.62	87.00	0.890	0.30( 0.27)	0.89	32262.4	11801.00
12	39071.16	97.41	0.845	0.30( 0.27)	0.90	37584.9	11530.00
13	39800.70	103.25	0.824	0.30( 0.27)	0.91	41321.9	13510.00
14	40475.32	108.89	0.802	0.30( 0.28)	0.92	44817.8	13010.00
15	41519.22	115.66	0.777	0.30( 0.28)	0.92	49227.5	11350.00
16	41861.09	120.32	0.760	0.30( 0.28)	0.93	52401.7	11130.00
17	41405.09	126.44	0.747	0.30( 0.28)	0.93	55328.3	12300.00
18	40572.10	135.28	0.728	0.30( 0.28)	0.94	59588.9	12400.00
19	39471.10	144.89	0.707	0.30( 0.28)	0.94	62990.4	12201.00
20	38457.74	152.47	0.691	0.30( 0.28)	0.94	64883.5	12231.00
21	37411.05	160.05	0.675	0.30( 0.28)	0.94	66436.2	10400.00
22	35795.68	169.66	0.654	0.30( 0.28)	0.94	67882.6	12010.00
23	34720.83	175.16	0.642	0.30( 0.28)	0.94	68145.2	10210.00
24	30238.92	206.11	0.607	0.30( 0.28)	0.94	68904.9	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 41861.09    Tc(MIN.) = 120.32  
 EFFECTIVE AREA(ACRES) = 52401.69    AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30    AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 68904.9  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13880.00 = 134069.50 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13880.00 TO NODE 13910.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 120.57    DOWNSTREAM(FEET) = 119.70  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1190.21    CHANNEL SLOPE = 0.0007  
 GIVEN CHANNEL BASE(FEET) = 100.00    CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 4.000    MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 24.66  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.755  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/    SCS SOIL    AREA    Fp    Ap    SCS  
 LAND USE            GROUP    (ACRES)    (INCH/HR)    (DECIMAL)    CN  
 USER-DEFINED       -            117.69    0.30    0.724    -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.724  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 41889.59  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.55  
 AVERAGE FLOW DEPTH(FEET) = 24.65    TRAVEL TIME(MIN.) = 2.32  
 Tc(MIN.) = 122.64  
 SUBAREA AREA(ACRES) = 117.69        SUBAREA RUNOFF(CFS) = 57.00  
 EFFECTIVE AREA(ACRES) = 52519.38    AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 69022.6 PEAK FLOW RATE (CFS) = 41861.09  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 24.65

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 24.65 FLOW VELOCITY (FEET/SEC.) = 8.55  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13910.00 = 135259.70 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23485.37	24.61	1.750	0.30 ( 0.25)	0.83	4907.3	10600.00
2	24248.61	26.89	1.652	0.30 ( 0.25)	0.83	5652.8	13810.00
3	24657.34	28.17	1.599	0.30 ( 0.25)	0.83	6057.3	13850.00
4	25806.66	31.80	1.487	0.30 ( 0.25)	0.83	7194.5	13870.00
5	28170.22	39.42	1.334	0.30 ( 0.25)	0.83	9522.5	13830.00
6	28607.10	40.90	1.307	0.30 ( 0.25)	0.83	9949.5	10220.00
7	30381.84	47.71	1.197	0.30 ( 0.25)	0.83	12448.6	100.00
8	32544.97	56.00	1.090	0.30 ( 0.25)	0.84	16282.2	150.00
9	34787.28	70.49	0.984	0.30 ( 0.26)	0.86	23230.4	390.00
10	36307.38	83.02	0.913	0.30 ( 0.27)	0.89	29551.1	13100.00
11	37254.62	89.39	0.876	0.30 ( 0.27)	0.89	32380.0	11801.00
12	39071.16	99.77	0.837	0.30 ( 0.27)	0.90	37702.6	11530.00
13	39800.70	105.60	0.815	0.30 ( 0.27)	0.91	41439.6	13510.00
14	40475.32	111.23	0.794	0.30 ( 0.27)	0.92	44935.5	13010.00
15	41519.22	117.99	0.769	0.30 ( 0.28)	0.92	49345.2	11350.00
16	41861.09	122.64	0.755	0.30 ( 0.28)	0.93	52519.4	11130.00
17	41405.09	128.76	0.742	0.30 ( 0.28)	0.93	55446.0	12300.00
18	40572.10	137.62	0.723	0.30 ( 0.28)	0.94	59706.6	12400.00
19	39471.10	147.25	0.702	0.30 ( 0.28)	0.94	63108.1	12201.00
20	38457.74	154.84	0.686	0.30 ( 0.28)	0.94	65001.2	12231.00
21	37411.05	162.44	0.670	0.30 ( 0.28)	0.94	66553.9	10400.00
22	35795.68	172.08	0.649	0.30 ( 0.28)	0.94	68000.3	12010.00
23	34720.83	177.60	0.637	0.30 ( 0.28)	0.94	68262.9	10210.00
24	30238.92	208.64	0.605	0.30 ( 0.28)	0.94	69022.6	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 41861.09 Tc (MIN.) = 122.64  
 AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA (ACRES) = 52519.38

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13880.00 TO NODE 13910.00 IS CODE = 1  
 -----

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
 TIME OF CONCENTRATION (MIN.) = 122.64  
 RAINFALL INTENSITY (INCH/HR) = 0.76  
 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93  
 EFFECTIVE STREAM AREA (ACRES) = 52519.38  
 TOTAL STREAM AREA (ACRES) = 69022.63  
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 41861.09

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13889.00 TO NODE 13890.00 IS CODE = 21  
 -----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH (FEET) = 447.89  
 ELEVATION DATA: UPSTREAM (FEET) = 564.89 DOWNSTREAM (FEET) = 421.92

Tc = K \* [(LENGTH\*\* 3.00) / (ELEVATION CHANGE)]\*\* 0.20  
 SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 6.976  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 4.094  
 SUBAREA Tc AND LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)  
 PUBLIC PARK - 3.03 0.30 0.960 56 6.98  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.960  
 SUBAREA RUNOFF (CFS) = 10.38  
 TOTAL AREA (ACRES) = 3.03 PEAK FLOW RATE (CFS) = 10.38

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13890.00 TO NODE 13891.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 421.92 DOWNSTREAM (FEET) = 392.64  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 435.33 CHANNEL SLOPE = 0.0673  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 0.43  
 \* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 3.621  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 8.12 0.30 0.986 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.986  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 22.58  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.03  
 AVERAGE FLOW DEPTH (FEET) = 0.41 TRAVEL TIME (MIN.) = 1.44  
 Tc (MIN.) = 8.42  
 SUBAREA AREA (ACRES) = 8.12 SUBAREA RUNOFF (CFS) = 24.30  
 EFFECTIVE AREA (ACRES) = 11.15 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98  
 TOTAL AREA (ACRES) = 11.1 PEAK FLOW RATE (CFS) = 33.40  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 0.52

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 0.52 FLOW VELOCITY (FEET/SEC.) = 5.80  
 LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13891.00 = 883.22 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13891.00 TO NODE 13892.00 IS CODE = 56



-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 392.64 DOWNSTREAM(FEET) = 324.46  
CHANNEL LENGTH THRU SUBAREA(FEET) = 662.40 CHANNEL SLOPE = 0.1029  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.60

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 3.151

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	12.50	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 49.47

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.69

AVERAGE FLOW DEPTH(FEET) = 0.58 TRAVEL TIME(MIN.) = 1.44

Tc(MIN.) = 9.86

SUBAREA AREA(ACRES) = 12.50 SUBAREA RUNOFF(CFS) = 32.08

EFFECTIVE AREA(ACRES) = 23.65 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 23.6 PEAK FLOW RATE(CFS) = 60.75

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.65

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.65 FLOW VELOCITY(FEET/SEC.) = 8.23

LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13892.00 = 1545.62 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13892.00 TO NODE 13893.00 IS CODE = 56

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 324.46 DOWNSTREAM(FEET) = 240.82  
CHANNEL LENGTH THRU SUBAREA(FEET) = 980.03 CHANNEL SLOPE = 0.0853  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.82

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.847

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	15.87	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 78.96

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.46

AVERAGE FLOW DEPTH(FEET) = 0.80 TRAVEL TIME(MIN.) = 1.93

Tc(MIN.) = 11.79

SUBAREA AREA(ACRES) = 15.87 SUBAREA RUNOFF(CFS) = 36.39

EFFECTIVE AREA(ACRES) = 39.52 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 39.5 PEAK FLOW RATE(CFS) = 90.68

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.87

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.87 FLOW VELOCITY(FEET/SEC.) = 8.85

LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13893.00 = 2525.65 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13893.00 TO NODE 13894.00 IS CODE = 56

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 240.82 DOWNSTREAM(FEET) = 163.04  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1144.35 CHANNEL SLOPE = 0.0680  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.11

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.542

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	28.41	0.30	0.985	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.985

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 119.45

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.96

AVERAGE FLOW DEPTH(FEET) = 1.09 TRAVEL TIME(MIN.) = 2.13

Tc(MIN.) = 13.91

SUBAREA AREA(ACRES) = 28.41 SUBAREA RUNOFF(CFS) = 57.44

EFFECTIVE AREA(ACRES) = 67.93 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 67.9 PEAK FLOW RATE(CFS) = 137.24

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.18

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.18 FLOW VELOCITY(FEET/SEC.) = 9.41

LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13894.00 = 3670.00 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 31

-----  
>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<  
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 163.04 DOWNSTREAM(FEET) = 119.70  
FLOW LENGTH(FEET) = 1899.01 MANNING'S N = 0.013  
DEPTH OF FLOW IN 42.0 INCH PIPE IS 32.7 INCHES

PIPE-FLOW VELOCITY(FEET/SEC.) = 17.06

ESTIMATED PIPE DIAMETER(INCH) = 42.00 NUMBER OF PIPES = 1

PIPE-FLOW(CFS) = 137.24

PIPE TRAVEL TIME(MIN.) = 1.86 Tc(MIN.) = 15.77

LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13910.00 = 5569.01 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 15.77

\* 25 YEAR RAINFALL INTENSITY (INCH/HR) = 2.324

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 11.69 0.30 0.634 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.634
SUBAREA AREA(ACRES) = 11.69 SUBAREA RUNOFF(CFS) = 22.45
EFFECTIVE AREA(ACRES) = 79.62 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94
TOTAL AREA(ACRES) = 79.6 PEAK FLOW RATE(CFS) = 146.34

\*\*\*\*\*

FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<

>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<

TOTAL NUMBER OF STREAMS = 2

CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:

TIME OF CONCENTRATION(MIN.) = 15.77

RAINFALL INTENSITY(INCH/HR) = 2.32

AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.94

EFFECTIVE STREAM AREA(ACRES) = 79.62

TOTAL STREAM AREA(ACRES) = 79.62

PEAK FLOW RATE(CFS) AT CONFLUENCE = 146.34

\*\* CONFLUENCE DATA \*\*

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 25 rows of stream data.

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 5 rows of stream data.

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 25 rows of stream data.

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 41895.06 Tc(MIN.) = 122.64

EFFECTIVE AREA(ACRES) = 52599.00 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA(ACRES) = 69102.2

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13910.00 = 135259.70 FEET.

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 69102.2 TC(MIN.) = 122.64

EFFECTIVE AREA(ACRES) = 52599.00 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.928

PEAK FLOW RATE(CFS) = 41895.06

\*\* PEAK FLOW RATE TABLE \*\*

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 5 rows of stream data.

6	28245.63	39.42	1.334	0.30	( 0.25)	0.83	9602.1	13830.00
7	28680.63	40.90	1.307	0.30	( 0.25)	0.83	10029.1	10220.00
8	30447.46	47.71	1.197	0.30	( 0.25)	0.83	12528.2	100.00
9	32602.91	56.00	1.090	0.30	( 0.25)	0.84	16361.8	150.00
10	34837.60	70.49	0.984	0.30	( 0.26)	0.87	23310.0	390.00
11	36352.62	83.02	0.913	0.30	( 0.27)	0.89	29630.7	13100.00
12	37297.27	89.39	0.876	0.30	( 0.27)	0.89	32459.7	11801.00
13	39110.94	99.77	0.837	0.30	( 0.27)	0.90	37782.2	11530.00
14	39838.93	105.60	0.815	0.30	( 0.27)	0.91	41519.3	13510.00
15	40512.04	111.23	0.794	0.30	( 0.27)	0.92	45015.1	13010.00
16	41554.13	117.99	0.769	0.30	( 0.28)	0.92	49424.8	11350.00
17	41895.06	122.64	0.755	0.30	( 0.28)	0.93	52599.0	11130.00
18	41438.11	128.76	0.742	0.30	( 0.28)	0.93	55525.6	12300.00
19	40603.76	137.62	0.723	0.30	( 0.28)	0.94	59786.2	12400.00
20	39501.27	147.25	0.702	0.30	( 0.28)	0.94	63187.8	12201.00
21	38486.75	154.84	0.686	0.30	( 0.28)	0.94	65080.8	12231.00
22	37438.89	162.44	0.670	0.30	( 0.28)	0.94	66633.5	10400.00
23	35822.03	172.08	0.649	0.30	( 0.28)	0.94	68079.9	12010.00
24	34746.33	177.60	0.637	0.30	( 0.28)	0.94	68342.5	10210.00
25	30262.11	208.64	0.605	0.30	( 0.28)	0.94	69102.2	10100.00

=====  
 END OF RATIONAL METHOD ANALYSIS  
 =====

\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S39- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 25-YR RM EV APRIL 2019 CCHI \*  
\*\*\*\*\*

FILE NAME: RI25EV39.DAT  
TIME/DATE OF STUDY: 09:52 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 25.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 4.737
- 2) 10.00; 3.102
- 3) 15.00; 2.384
- 4) 20.00; 1.980
- 5) 25.00; 1.729
- 6) 30.00; 1.522
- 7) 40.00; 1.321
- 8) 50.00; 1.169
- 9) 60.00; 1.042
- 10) 90.00; 0.872
- 11) 120.00; 0.761
- 12) 180.00; 0.631
- 13) 360.00; 0.462
- 14) 1200.00; 0.201

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL: IN- / OUT-/PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13900.00 TO NODE 13901.00 IS CODE = 21  
-----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 600.65  
ELEVATION DATA: UPSTREAM(FEET) = 442.40 DOWNSTREAM(FEET) = 385.16

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 10.859  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.979  
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
AGRICULTURAL POOR COVER "FALLOW"	-	4.00	0.30	1.000	56	10.86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA RUNOFF(CFS) = 9.64  
TOTAL AREA(ACRES) = 4.00 PEAK FLOW RATE(CFS) = 9.64

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13901.00 TO NODE 13902.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 385.16 DOWNSTREAM(FEET) = 288.21  
CHANNEL LENGTH THRU SUBAREA(FEET) = 647.42 CHANNEL SLOPE = 0.1497  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.30  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.725  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.47	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 18.90  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.10  
AVERAGE FLOW DEPTH(FEET) = 0.29 TRAVEL TIME(MIN.) = 1.77  
Tc(MIN.) = 12.63  
SUBAREA AREA(ACRES) = 8.47 SUBAREA RUNOFF(CFS) = 18.48  
EFFECTIVE AREA(ACRES) = 12.47 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 12.5 PEAK FLOW RATE(CFS) = 27.21  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.36

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.36 FLOW VELOCITY(FEET/SEC.) = 6.98  
LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13902.00 = 1248.07 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13902.00 TO NODE 13903.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 288.21 DOWNSTREAM(FEET) = 184.89  
CHANNEL LENGTH THRU SUBAREA(FEET) = 669.27 CHANNEL SLOPE = 0.1544  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.54

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.544

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	23.85	0.30	0.982	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.982

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 51.37

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.88

AVERAGE FLOW DEPTH(FEET) = 0.52 TRAVEL TIME(MIN.) = 1.26

Tc(MIN.) = 13.88

SUBAREA AREA(ACRES) = 23.85 SUBAREA RUNOFF(CFS) = 48.29

EFFECTIVE AREA(ACRES) = 36.32 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 36.3 PEAK FLOW RATE(CFS) = 73.48

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.65

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.65 FLOW VELOCITY(FEET/SEC.) = 9.98

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13903.00 = 1917.34 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13903.00 TO NODE 13904.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 184.89 DOWNSTREAM(FEET) = 155.08

FLOW LENGTH(FEET) = 876.66 MANNING'S N = 0.013

ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000

DEPTH OF FLOW IN 36.0 INCH PIPE IS 20.7 INCHES

PIPE-FLOW VELOCITY(FEET/SEC.) = 17.45

ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1

PIPE-FLOW(CFS) = 73.48

PIPE TRAVEL TIME(MIN.) = 0.84 Tc(MIN.) = 14.72

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13904.00 = 2794.00 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13903.00 TO NODE 13904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 14.72

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.424

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	21.29	0.30	0.996	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.996

SUBAREA AREA(ACRES) = 21.29 SUBAREA RUNOFF(CFS) = 40.72

EFFECTIVE AREA(ACRES) = 57.61 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 57.6 PEAK FLOW RATE(CFS) = 110.27

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 155.08 DOWNSTREAM(FEET) = 118.00

FLOW LENGTH(FEET) = 1961.38 MANNING'S N = 0.013

DEPTH OF FLOW IN 42.0 INCH PIPE IS 29.5 INCHES

PIPE-FLOW VELOCITY(FEET/SEC.) = 15.28

ESTIMATED PIPE DIAMETER(INCH) = 42.00 NUMBER OF PIPES = 1

PIPE-FLOW(CFS) = 110.27

PIPE TRAVEL TIME(MIN.) = 2.14 Tc(MIN.) = 16.86

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13920.00 = 4755.38 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 16.86

\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 2.234

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	43.53	0.30	0.649	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.649

SUBAREA AREA(ACRES) = 43.53 SUBAREA RUNOFF(CFS) = 79.88

EFFECTIVE AREA(ACRES) = 101.14 AREA-AVERAGED Fm(INCH/HR) = 0.25

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84

TOTAL AREA(ACRES) = 101.1 PEAK FLOW RATE(CFS) = 180.28

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13910.00 TO NODE 13910.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: RI25EV38.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20956.29	15.77	0.30 ( 0.25)	0.83	3224.9	13889.00
2	25893.04	31.80	0.30 ( 0.25)	0.83	7274.1	13870.00
3	28680.63	40.90	0.30 ( 0.25)	0.83	10029.1	10220.00
4	30447.46	47.71	0.30 ( 0.25)	0.83	12528.2	100.00
5	32602.91	56.00	0.30 ( 0.25)	0.84	16361.8	150.00
6	34837.60	70.49	0.30 ( 0.26)	0.87	23310.0	390.00
7	36352.62	83.02	0.30 ( 0.27)	0.89	29630.7	13100.00
8	37297.27	89.39	0.30 ( 0.27)	0.89	32459.7	11801.00
9	39110.94	99.77	0.30 ( 0.27)	0.90	37782.2	11530.00
10	39838.93	105.60	0.30 ( 0.27)	0.91	41519.3	13510.00
11	40512.04	111.23	0.30 ( 0.27)	0.92	45015.1	13010.00
12	41895.06	122.64	0.30 ( 0.28)	0.93	52599.0	11130.00
13	41438.11	128.76	0.30 ( 0.28)	0.93	55525.6	12300.00
14	40603.76	137.62	0.30 ( 0.28)	0.94	59786.2	12400.00
15	39501.27	147.25	0.30 ( 0.28)	0.94	63187.8	12201.00
16	38486.75	154.84	0.30 ( 0.28)	0.94	65080.8	12231.00
17	37438.89	162.44	0.30 ( 0.28)	0.94	66633.5	10400.00
18	35822.03	172.08	0.30 ( 0.28)	0.94	68079.9	12010.00
19	34746.33	177.60	0.30 ( 0.28)	0.94	68342.5	10210.00
20	30262.11	208.64	0.30 ( 0.28)	0.94	69102.2	10100.00
TOTAL AREA (ACRES) =						69102.2

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13910.00 TO NODE 13910.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20956.29	15.77	0.30 ( 0.25)	0.83	3224.9	13889.00
2	25893.04	31.80	0.30 ( 0.25)	0.83	7274.1	13870.00
3	28680.63	40.90	0.30 ( 0.25)	0.83	10029.1	10220.00
4	30447.46	47.71	0.30 ( 0.25)	0.83	12528.2	100.00
5	32602.91	56.00	0.30 ( 0.25)	0.84	16361.8	150.00
6	34837.60	70.49	0.30 ( 0.26)	0.87	23310.0	390.00
7	36352.62	83.02	0.30 ( 0.27)	0.89	29630.7	13100.00
8	37297.27	89.39	0.30 ( 0.27)	0.89	32459.7	11801.00
9	39110.94	99.77	0.30 ( 0.27)	0.90	37782.2	11530.00
10	39838.93	105.60	0.30 ( 0.27)	0.91	41519.3	13510.00
11	40512.04	111.23	0.30 ( 0.27)	0.92	45015.1	13010.00
12	41895.06	122.64	0.30 ( 0.28)	0.93	52599.0	11130.00
13	41438.11	128.76	0.30 ( 0.28)	0.93	55525.6	12300.00
14	40603.76	137.62	0.30 ( 0.28)	0.94	59786.2	12400.00
15	39501.27	147.25	0.30 ( 0.28)	0.94	63187.8	12201.00
16	38486.75	154.84	0.30 ( 0.28)	0.94	65080.8	12231.00
17	37438.89	162.44	0.30 ( 0.28)	0.94	66633.5	10400.00
18	35822.03	172.08	0.30 ( 0.28)	0.94	68079.9	12010.00
19	34746.33	177.60	0.30 ( 0.28)	0.94	68342.5	10210.00
20	30262.11	208.64	0.30 ( 0.28)	0.94	69102.2	10100.00
TOTAL AREA (ACRES) =						69102.2

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13910.00 TO NODE 13920.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

```

=====
ELEVATION DATA: UPSTREAM(FEET) = 119.70 DOWNSTREAM(FEET) = 118.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1376.26 CHANNEL SLOPE = 0.0012
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 21.68
* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.750
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 96.09 0.30 0.535 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.535
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 41920.57
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.36
AVERAGE FLOW DEPTH(FEET) = 21.67 TRAVEL TIME(MIN.) = 2.21
Tc(MIN.) = 124.86
SUBAREA AREA(ACRES) = 96.09 SUBAREA RUNOFF(CFS) = 51.02
EFFECTIVE AREA(ACRES) = 52695.09 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 69198.3 PEAK FLOW RATE(CFS) = 41895.06
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 21.66

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 21.66 FLOW VELOCITY(FEET/SEC.) = 10.36  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136635.97 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20956.29	18.45	2.105	0.30 ( 0.25)	0.83	3321.0	13889.00
2	25893.04	34.33	1.435	0.30 ( 0.25)	0.83	7370.2	13870.00
3	28680.63	43.36	1.270	0.30 ( 0.25)	0.83	10125.2	10220.00
4	30447.46	50.12	1.167	0.30 ( 0.25)	0.83	12624.3	100.00
5	32602.91	58.37	1.063	0.30 ( 0.25)	0.84	16457.9	150.00
6	34837.60	72.82	0.969	0.30 ( 0.26)	0.86	23406.1	390.00
7	36352.62	85.32	0.899	0.30 ( 0.27)	0.88	29726.8	13100.00
8	37297.27	91.67	0.866	0.30 ( 0.27)	0.89	32555.8	11801.00
9	39110.94	102.03	0.828	0.30 ( 0.27)	0.90	37878.3	11530.00
10	39838.93	107.84	0.806	0.30 ( 0.27)	0.91	41615.3	13510.00
11	40512.04	113.46	0.785	0.30 ( 0.27)	0.92	45111.2	13010.00
12	41895.06	124.86	0.750	0.30 ( 0.28)	0.93	52695.1	11130.00
13	41438.11	130.99	0.737	0.30 ( 0.28)	0.93	55621.7	12300.00
14	40603.76	139.85	0.718	0.30 ( 0.28)	0.93	59882.3	12400.00
15	39501.27	149.50	0.697	0.30 ( 0.28)	0.94	63283.9	12201.00
16	38486.75	157.11	0.681	0.30 ( 0.28)	0.94	65176.9	12231.00
17	37438.89	164.73	0.664	0.30 ( 0.28)	0.94	66729.6	10400.00
18	35822.03	174.39	0.643	0.30 ( 0.28)	0.94	68176.0	12010.00
19	34746.33	179.93	0.631	0.30 ( 0.28)	0.94	68438.6	10210.00
20	30262.11	211.06	0.602	0.30 ( 0.28)	0.94	69198.3	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 41895.06 Tc(MIN.) = 124.86

AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 52695.09

\*\*\*\*\*

FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20956.29	18.45	2.105	0.30( 0.25)	0.83	3321.0	13889.00
2	25893.04	34.33	1.435	0.30( 0.25)	0.83	7370.2	13870.00
3	28680.63	43.36	1.270	0.30( 0.25)	0.83	10125.2	10220.00
4	30447.46	50.12	1.167	0.30( 0.25)	0.83	12624.3	100.00
5	32602.91	58.37	1.063	0.30( 0.25)	0.84	16457.9	150.00
6	34837.60	72.82	0.969	0.30( 0.26)	0.86	23406.1	390.00
7	36352.62	85.32	0.899	0.30( 0.27)	0.88	29726.8	13100.00
8	37297.27	91.67	0.866	0.30( 0.27)	0.89	32555.8	11801.00
9	39110.94	102.03	0.828	0.30( 0.27)	0.90	37878.3	11530.00
10	39838.93	107.84	0.806	0.30( 0.27)	0.91	41615.3	13510.00
11	40512.04	113.46	0.785	0.30( 0.27)	0.92	45111.2	13010.00
12	41895.06	124.86	0.750	0.30( 0.28)	0.93	52695.1	11130.00
13	41438.11	130.99	0.737	0.30( 0.28)	0.93	55621.7	12300.00
14	40603.76	139.85	0.718	0.30( 0.28)	0.93	59882.3	12400.00
15	39501.27	149.50	0.697	0.30( 0.28)	0.94	63283.9	12201.00
16	38486.75	157.11	0.681	0.30( 0.28)	0.94	65176.9	12231.00
17	37438.89	164.73	0.664	0.30( 0.28)	0.94	66729.6	10400.00
18	35822.03	174.39	0.643	0.30( 0.28)	0.94	68176.0	12010.00
19	34746.33	179.93	0.631	0.30( 0.28)	0.94	68438.6	10210.00
20	30262.11	211.06	0.602	0.30( 0.28)	0.94	69198.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136635.97 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	180.28	16.86	2.234	0.30( 0.25)	0.84	101.1	13900.00

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13920.00 = 4755.38 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20654.93	16.86	2.234	0.30( 0.25)	0.83	3135.7	13900.00
2	21124.87	18.45	2.105	0.30( 0.25)	0.83	3422.1	13889.00
3	26000.62	34.33	1.435	0.30( 0.25)	0.83	7471.3	13870.00
4	28773.19	43.36	1.270	0.30( 0.25)	0.83	10226.4	10220.00
5	30530.69	50.12	1.167	0.30( 0.25)	0.83	12725.4	100.00
6	32676.60	58.37	1.063	0.30( 0.25)	0.84	16559.0	150.00
7	34902.79	72.82	0.969	0.30( 0.26)	0.86	23507.2	390.00
8	36411.37	85.32	0.899	0.30( 0.27)	0.88	29827.9	13100.00
9	37353.04	91.67	0.866	0.30( 0.27)	0.89	32656.9	11801.00
10	39163.23	102.03	0.828	0.30( 0.27)	0.90	37979.4	11530.00
11	39889.25	107.84	0.806	0.30( 0.27)	0.91	41716.5	13510.00
12	40560.47	113.46	0.785	0.30( 0.27)	0.92	45212.3	13010.00
13	41940.33	124.86	0.750	0.30( 0.28)	0.93	52796.2	11130.00
14	41482.18	130.99	0.737	0.30( 0.28)	0.93	55722.8	12300.00
15	40646.08	139.85	0.718	0.30( 0.28)	0.93	59983.4	12400.00

16	39541.69	149.50	0.697	0.30( 0.28)	0.94	63385.0	12201.00
17	38525.66	157.11	0.681	0.30( 0.28)	0.94	65278.0	12231.00
18	37476.30	164.73	0.664	0.30( 0.28)	0.94	66830.7	10400.00
19	35857.53	174.39	0.643	0.30( 0.28)	0.94	68277.1	12010.00
20	34780.75	179.93	0.631	0.30( 0.28)	0.94	68539.7	10210.00
21	30293.85	211.06	0.602	0.30( 0.28)	0.94	69299.5	10100.00

TOTAL AREA(ACRES) = 69299.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 41940.33 Tc(MIN.) = 124.857  
EFFECTIVE AREA(ACRES) = 52796.23 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
TOTAL AREA(ACRES) = 69299.5  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136635.97 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13920.00 TO NODE 13921.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 118.00 DOWNSTREAM(FEET) = 115.28  
CHANNEL LENGTH THRU SUBAREA(FEET) = 335.44 CHANNEL SLOPE = 0.0081  
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 13.40  
\* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.750

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	134.30	0.30	0.658	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.658  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 41973.72  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 20.39  
AVERAGE FLOW DEPTH(FEET) = 13.40 TRAVEL TIME(MIN.) = 0.27  
Tc(MIN.) = 125.13  
SUBAREA AREA(ACRES) = 134.30 SUBAREA RUNOFF(CFS) = 66.78  
EFFECTIVE AREA(ACRES) = 52930.54 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA(ACRES) = 69433.8 PEAK FLOW RATE(CFS) = 41940.33  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 13.39

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 13.39 FLOW VELOCITY(FEET/SEC.) = 20.39  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13921.00 = 136971.41 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20654.93	17.20	2.206	0.30( 0.25)	0.82	3270.0	13900.00
2	21124.87	18.79	2.078	0.30( 0.25)	0.82	3556.4	13889.00
3	26000.62	34.65	1.429	0.30( 0.25)	0.83	7605.6	13870.00
4	28773.19	43.66	1.265	0.30( 0.25)	0.83	10360.7	10220.00
5	30530.69	50.42	1.164	0.30( 0.25)	0.83	12859.7	100.00

6	32676.60	58.67	1.059	0.30	( 0.25)	0.84	16693.3	150.00
7	34902.79	73.11	0.968	0.30	( 0.26)	0.86	23641.5	390.00
8	36411.37	85.61	0.897	0.30	( 0.26)	0.88	29962.2	13100.00
9	37353.04	91.96	0.865	0.30	( 0.27)	0.89	32791.2	11801.00
10	39163.23	102.31	0.826	0.30	( 0.27)	0.90	38113.7	11530.00
11	39889.25	108.12	0.805	0.30	( 0.27)	0.91	41850.8	13510.00
12	40560.47	113.74	0.784	0.30	( 0.27)	0.91	45346.6	13010.00
13	41940.33	125.13	0.750	0.30	( 0.28)	0.93	52930.5	11130.00
14	41482.18	131.26	0.737	0.30	( 0.28)	0.93	55857.1	12300.00
15	40646.08	140.13	0.717	0.30	( 0.28)	0.93	60117.7	12400.00
16	39541.69	149.78	0.696	0.30	( 0.28)	0.94	63519.3	12201.00
17	38525.66	157.39	0.680	0.30	( 0.28)	0.94	65412.3	12231.00
18	37476.30	165.01	0.663	0.30	( 0.28)	0.94	66965.0	10400.00
19	35857.53	174.68	0.643	0.30	( 0.28)	0.94	68411.4	12010.00
20	34780.75	180.22	0.631	0.30	( 0.28)	0.94	68674.0	10210.00
21	30293.85	211.37	0.602	0.30	( 0.28)	0.94	69433.8	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 41940.33 Tc(MIN.) = 125.13  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 52930.54

\*\*\*\*\*

FLOW PROCESS FROM NODE 13921.00 TO NODE 14010.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 115.28 DOWNSTREAM(FEET) = 100.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1396.08 CHANNEL SLOPE = 0.0109  
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 12.38  
 \* 25 YEAR RAINFALL INTENSITY(INCH/HR) = 0.748

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	96.27	0.30	0.723	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.723

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 41963.33  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 22.69  
 AVERAGE FLOW DEPTH(FEET) = 12.37 TRAVEL TIME(MIN.) = 1.03  
 Tc(MIN.) = 126.16  
 SUBAREA AREA(ACRES) = 96.27 SUBAREA RUNOFF(CFS) = 45.99  
 EFFECTIVE AREA(ACRES) = 53026.80 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 69530.1 PEAK FLOW RATE(CFS) = 41940.33  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 12.37

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 12.37 FLOW VELOCITY(FEET/SEC.) = 22.68  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 14010.00 = 138367.48 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	--------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	20654.93	18.47	2.104	0.30( 0.25)	0.82	3366.2 13900.00
2	21124.87	20.05	1.978	0.30( 0.25)	0.82	3652.7 13889.00
3	26000.62	35.83	1.405	0.30( 0.25)	0.83	7701.9 13870.00
4	28773.19	44.81	1.248	0.30( 0.25)	0.83	10456.9 10220.00
5	30530.69	51.55	1.149	0.30( 0.25)	0.83	12956.0 100.00
6	32676.60	59.77	1.045	0.30( 0.25)	0.84	16789.6 150.00
7	34902.79	74.19	0.962	0.30( 0.26)	0.86	23737.8 390.00
8	36411.37	86.68	0.891	0.30( 0.26)	0.88	30058.5 13100.00
9	37353.04	93.02	0.861	0.30( 0.27)	0.89	32887.5 11801.00
10	39163.23	103.35	0.823	0.30( 0.27)	0.90	38210.0 11530.00
11	39889.25	109.16	0.801	0.30( 0.27)	0.91	41947.1 13510.00
12	40560.47	114.78	0.780	0.30( 0.27)	0.91	45442.9 13010.00
13	41940.33	126.16	0.748	0.30( 0.28)	0.93	53026.8 11130.00
14	41482.18	132.29	0.734	0.30( 0.28)	0.93	55953.4 12300.00
15	40646.08	141.16	0.715	0.30( 0.28)	0.93	60214.0 12400.00
16	39541.69	150.82	0.694	0.30( 0.28)	0.94	63615.6 12201.00
17	38525.66	158.44	0.678	0.30( 0.28)	0.94	65508.6 12231.00
18	37476.30	166.07	0.661	0.30( 0.28)	0.94	67061.3 10400.00
19	35857.53	175.75	0.640	0.30( 0.28)	0.94	68507.7 12010.00
20	34780.75	181.31	0.630	0.30( 0.28)	0.94	68770.3 10210.00
21	30293.85	212.49	0.600	0.30( 0.28)	0.94	69530.1 10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 41940.33 Tc(MIN.) = 126.16  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 53026.80

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 69530.1 TC(MIN.) = 126.16  
 EFFECTIVE AREA(ACRES) = 53026.80 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.926  
 PEAK FLOW RATE(CFS) = 41940.33

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20654.93	18.47	2.104	0.30( 0.25)	0.82	3366.2	13900.00
2	21124.87	20.05	1.978	0.30( 0.25)	0.82	3652.7	13889.00
3	26000.62	35.83	1.405	0.30( 0.25)	0.83	7701.9	13870.00
4	28773.19	44.81	1.248	0.30( 0.25)	0.83	10456.9	10220.00
5	30530.69	51.55	1.149	0.30( 0.25)	0.83	12956.0	100.00
6	32676.60	59.77	1.045	0.30( 0.25)	0.84	16789.6	150.00
7	34902.79	74.19	0.962	0.30( 0.26)	0.86	23737.8	390.00
8	36411.37	86.68	0.891	0.30( 0.26)	0.88	30058.5	13100.00
9	37353.04	93.02	0.861	0.30( 0.27)	0.89	32887.5	11801.00
10	39163.23	103.35	0.823	0.30( 0.27)	0.90	38210.0	11530.00
11	39889.25	109.16	0.801	0.30( 0.27)	0.91	41947.1	13510.00
12	40560.47	114.78	0.780	0.30( 0.27)	0.91	45442.9	13010.00
13	41940.33	126.16	0.748	0.30( 0.28)	0.93	53026.8	11130.00
14	41482.18	132.29	0.734	0.30( 0.28)	0.93	55953.4	12300.00
15	40646.08	141.16	0.715	0.30( 0.28)	0.93	60214.0	12400.00
16	39541.69	150.82	0.694	0.30( 0.28)	0.94	63615.6	12201.00
17	38525.66	158.44	0.678	0.30( 0.28)	0.94	65508.6	12231.00
18	37476.30	166.07	0.661	0.30( 0.28)	0.94	67061.3	10400.00
19	35857.53	175.75	0.640	0.30( 0.28)	0.94	68507.7	12010.00
20	34780.75	181.31	0.630	0.30( 0.28)	0.94	68770.3	10210.00
21	30293.85	212.49	0.600	0.30( 0.28)	0.94	69530.1	10100.00



=====  
END OF RATIONAL METHOD ANALYSIS

\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S19- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 50-YR RM EV APRIL 2019 CCHIUI \*  
\*\*\*\*\*

FILE NAME: RI50EV19.DAT  
TIME/DATE OF STUDY: 09:11 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 50.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.535
- 2) 10.00; 3.529
- 3) 15.00; 2.693
- 4) 20.00; 2.246
- 5) 25.00; 1.938
- 6) 30.00; 1.744
- 7) 40.00; 1.475
- 8) 50.00; 1.313
- 9) 60.00; 1.214
- 10) 90.00; 1.010
- 11) 120.00; 0.880
- 12) 180.00; 0.760
- 13) 360.00; 0.566
- 14) 1200.00; 0.250

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0312	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11900.00 TO NODE 11901.00 IS CODE = 21  
-----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<  
=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 295.79  
ELEVATION DATA: UPSTREAM(FEET) = 2369.48 DOWNSTREAM(FEET) = 2332.92

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 7.203  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 4.651  
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
RESIDENTIAL ".4 DWELLING/ACRE"	-	1.62	0.30	0.999	0	7.20

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999  
SUBAREA RUNOFF(CFS) = 6.34  
TOTAL AREA(ACRES) = 1.62 PEAK FLOW RATE(CFS) = 6.34

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11901.00 TO NODE 11902.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<  
=====

ELEVATION DATA: UPSTREAM(FEET) = 2332.92 DOWNSTREAM(FEET) = 2297.70  
CHANNEL LENGTH THRU SUBAREA(FEET) = 664.26 CHANNEL SLOPE = 0.0530  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.57  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 3.443  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.35	0.30	0.906	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.906  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 18.40  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.34  
AVERAGE FLOW DEPTH(FEET) = 0.50 TRAVEL TIME(MIN.) = 3.31  
Tc(MIN.) = 10.52  
SUBAREA AREA(ACRES) = 8.35 SUBAREA RUNOFF(CFS) = 23.83  
EFFECTIVE AREA(ACRES) = 9.97 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
TOTAL AREA(ACRES) = 10.0 PEAK FLOW RATE(CFS) = 28.41  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.65

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.65 FLOW VELOCITY(FEET/SEC.) = 3.90  
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11902.00 = 960.05 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11902.00 TO NODE 11902.50 IS CODE = 56

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2297.70 DOWNSTREAM(FEET) = 2263.40  
CHANNEL LENGTH THRU SUBAREA(FEET) = 928.77 CHANNEL SLOPE = 0.0369  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.28

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.887

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

USER-DEFINED	-	34.48	0.30	0.904	-
--------------	---	-------	------	-------	---

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.904

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 69.30

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.65

AVERAGE FLOW DEPTH(FEET) = 1.20 TRAVEL TIME(MIN.) = 3.33

Tc(MIN.) = 13.84

SUBAREA AREA(ACRES) = 34.48 SUBAREA RUNOFF(CFS) = 81.16

EFFECTIVE AREA(ACRES) = 44.45 AREA-AVERAGED Fm(INCH/HR) = 0.27

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.91

TOTAL AREA(ACRES) = 44.5 PEAK FLOW RATE(CFS) = 104.58

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.51

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.51 FLOW VELOCITY(FEET/SEC.) = 5.30

LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11902.50 = 1888.82 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11902.50 TO NODE 11903.00 IS CODE = 56

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2263.40 DOWNSTREAM(FEET) = 2252.14  
CHANNEL LENGTH THRU SUBAREA(FEET) = 895.50 CHANNEL SLOPE = 0.0126  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.32

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.451

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

USER-DEFINED	-	23.65	0.30	0.958	-
--------------	---	-------	------	-------	---

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.958

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 127.65

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.87

AVERAGE FLOW DEPTH(FEET) = 2.27 TRAVEL TIME(MIN.) = 3.86

Tc(MIN.) = 17.70

SUBAREA AREA(ACRES) = 23.65 SUBAREA RUNOFF(CFS) = 46.06

EFFECTIVE AREA(ACRES) = 68.10 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA(ACRES) = 68.1 PEAK FLOW RATE(CFS) = 133.24

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.32

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.32 FLOW VELOCITY(FEET/SEC.) = 3.91

LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11903.00 = 2784.32 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11903.00 TO NODE 11904.00 IS CODE = 56

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2252.14 DOWNSTREAM(FEET) = 2186.04  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1924.35 CHANNEL SLOPE = 0.0343  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.21

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.067

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

USER-DEFINED	-	68.53	0.30	0.961	-
--------------	---	-------	------	-------	---

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.961

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 188.28

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.16

AVERAGE FLOW DEPTH(FEET) = 2.14 TRAVEL TIME(MIN.) = 5.20

Tc(MIN.) = 22.91

SUBAREA AREA(ACRES) = 68.53 SUBAREA RUNOFF(CFS) = 109.71

EFFECTIVE AREA(ACRES) = 136.63 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94

TOTAL AREA(ACRES) = 136.6 PEAK FLOW RATE(CFS) = 219.39

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.32

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.32 FLOW VELOCITY(FEET/SEC.) = 6.45

LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11904.00 = 4708.67 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11904.00 TO NODE 11905.00 IS CODE = 56

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2186.04 DOWNSTREAM(FEET) = 1957.34  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1926.87 CHANNEL SLOPE = 0.1187  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.86

\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.901  
SUBAREA LOSS RATE DATA (AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 63.15 0.30 1.000 -  
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 264.91  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 10.57  
AVERAGE FLOW DEPTH (FEET) = 1.83 TRAVEL TIME (MIN.) = 3.04  
Tc (MIN.) = 25.94  
SUBAREA AREA (ACRES) = 63.15 SUBAREA RUNOFF (CFS) = 91.02  
EFFECTIVE AREA (ACRES) = 199.78 AREA-AVERAGED Fm (INCH/HR) = 0.29  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA (ACRES) = 199.8 PEAK FLOW RATE (CFS) = 290.04  
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 1.93  
END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 1.93 FLOW VELOCITY (FEET/SEC.) = 10.86  
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11905.00 = 6635.54 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11905.00 TO NODE 11906.00 IS CODE = 56

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<  
-----

ELEVATION DATA: UPSTREAM (FEET) = 1957.34 DOWNSTREAM (FEET) = 1244.16  
CHANNEL LENGTH THRU SUBAREA (FEET) = 2498.96 CHANNEL SLOPE = 0.2854  
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 1.68

\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.797  
SUBAREA LOSS RATE DATA (AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 84.87 0.30 1.000 -  
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 347.25  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 15.54  
AVERAGE FLOW DEPTH (FEET) = 1.67 TRAVEL TIME (MIN.) = 2.68  
Tc (MIN.) = 28.62  
SUBAREA AREA (ACRES) = 84.87 SUBAREA RUNOFF (CFS) = 114.38  
EFFECTIVE AREA (ACRES) = 284.65 AREA-AVERAGED Fm (INCH/HR) = 0.29  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97  
TOTAL AREA (ACRES) = 284.6 PEAK FLOW RATE (CFS) = 385.73  
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 1.77

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 1.77 FLOW VELOCITY (FEET/SEC.) = 16.06  
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11906.00 = 9134.50 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11906.00 TO NODE 11920.00 IS CODE = 56

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<  
-----

ELEVATION DATA: UPSTREAM (FEET) = 1244.16 DOWNSTREAM (FEET) = 873.95  
CHANNEL LENGTH THRU SUBAREA (FEET) = 3370.75 CHANNEL SLOPE = 0.1098  
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 2.70  
\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.659

SUBAREA LOSS RATE DATA (AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 199.43 0.30 1.000 -  
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 507.80  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 12.43  
AVERAGE FLOW DEPTH (FEET) = 2.67 TRAVEL TIME (MIN.) = 4.52  
Tc (MIN.) = 33.14  
SUBAREA AREA (ACRES) = 199.43 SUBAREA RUNOFF (CFS) = 244.01  
EFFECTIVE AREA (ACRES) = 484.08 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98  
TOTAL AREA (ACRES) = 484.1 PEAK FLOW RATE (CFS) = 594.38  
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 2.90

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 2.90 FLOW VELOCITY (FEET/SEC.) = 12.99  
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11920.00 = 12505.25 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11906.00 TO NODE 11920.00 IS CODE = 1

-----  
>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
-----

TOTAL NUMBER OF STREAMS = 2  
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
TIME OF CONCENTRATION (MIN.) = 33.14  
RAINFALL INTENSITY (INCH/HR) = 1.66  
AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.98  
EFFECTIVE STREAM AREA (ACRES) = 484.08  
TOTAL STREAM AREA (ACRES) = 484.08  
PEAK FLOW RATE (CFS) AT CONFLUENCE = 594.38

\*\*\*\*\*

FLOW PROCESS FROM NODE 11910.00 TO NODE 11911.00 IS CODE = 21

-----  
>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<  
-----

INITIAL SUBAREA FLOW-LENGTH (FEET) = 517.62  
ELEVATION DATA: UPSTREAM (FEET) = 2531.88 DOWNSTREAM (FEET) = 2441.33

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
 SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 12.185  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 3.164  
 SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	-	3.46	0.30	1.000	0	12.19

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA RUNOFF(CFS) = 8.92  
 TOTAL AREA(ACRES) = 3.46 PEAK FLOW RATE(CFS) = 8.92

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11911.00 TO NODE 11912.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2441.33 DOWNSTREAM(FEET) = 2382.20  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 397.30 CHANNEL SLOPE = 0.1488  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.35  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.909  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.79	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 15.73  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.35  
 AVERAGE FLOW DEPTH(FEET) = 0.34 TRAVEL TIME(MIN.) = 1.52  
 Tc(MIN.) = 13.71  
 SUBAREA AREA(ACRES) = 5.79 SUBAREA RUNOFF(CFS) = 13.60  
 EFFECTIVE AREA(ACRES) = 9.25 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 9.2 PEAK FLOW RATE(CFS) = 21.72  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.41

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 0.41 FLOW VELOCITY(FEET/SEC.) = 4.93  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11912.00 = 914.92 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11912.00 TO NODE 11913.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2382.20 DOWNSTREAM(FEET) = 2263.77  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1891.47 CHANNEL SLOPE = 0.0626  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.16

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.308  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	54.30	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 71.48  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.63  
 AVERAGE FLOW DEPTH(FEET) = 1.05 TRAVEL TIME(MIN.) = 5.60  
 Tc(MIN.) = 19.31  
 SUBAREA AREA(ACRES) = 54.30 SUBAREA RUNOFF(CFS) = 98.12  
 EFFECTIVE AREA(ACRES) = 63.55 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 63.5 PEAK FLOW RATE(CFS) = 114.83  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.38

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.38 FLOW VELOCITY(FEET/SEC.) = 6.54  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11913.00 = 2806.39 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11913.00 TO NODE 11914.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2263.77 DOWNSTREAM(FEET) = 1845.23  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1957.31 CHANNEL SLOPE = 0.2138  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.23  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.110  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	65.14	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 167.95  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.26  
 AVERAGE FLOW DEPTH(FEET) = 1.20 TRAVEL TIME(MIN.) = 2.90  
 Tc(MIN.) = 22.21  
 SUBAREA AREA(ACRES) = 65.14 SUBAREA RUNOFF(CFS) = 106.12  
 EFFECTIVE AREA(ACRES) = 128.69 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 128.7 PEAK FLOW RATE(CFS) = 209.64  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.37

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.37 FLOW VELOCITY(FEET/SEC.) = 12.03  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11914.00 = 4763.70 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11914.00 TO NODE 11915.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1845.23 DOWNSTREAM(FEET) = 1557.21
CHANNEL LENGTH THRU SUBAREA(FEET) = 1686.78 CHANNEL SLOPE = 0.1708
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.69
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.966

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 78.52 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 268.54

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.02

AVERAGE FLOW DEPTH(FEET) = 1.67 TRAVEL TIME(MIN.) = 2.34

Tc(MIN.) = 24.55

SUBAREA AREA(ACRES) = 78.52 SUBAREA RUNOFF(CFS) = 117.73

EFFECTIVE AREA(ACRES) = 207.21 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 207.2 PEAK FLOW RATE(CFS) = 310.69

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.81

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.81 FLOW VELOCITY(FEET/SEC.) = 12.58

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11915.00 = 6450.48 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 11915.00 TO NODE 11916.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1557.21 DOWNSTREAM(FEET) = 1403.38
CHANNEL LENGTH THRU SUBAREA(FEET) = 1909.39 CHANNEL SLOPE = 0.0806
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.42
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.833

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 70.48 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 359.32

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.08

AVERAGE FLOW DEPTH(FEET) = 2.41 TRAVEL TIME(MIN.) = 3.16

Tc(MIN.) = 27.70

SUBAREA AREA(ACRES) = 70.48 SUBAREA RUNOFF(CFS) = 97.25

EFFECTIVE AREA(ACRES) = 277.69 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 277.7 PEAK FLOW RATE(CFS) = 383.17
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.49

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.49 FLOW VELOCITY(FEET/SEC.) = 10.27

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11916.00 = 8359.87 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 11916.00 TO NODE 11917.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1403.38 DOWNSTREAM(FEET) = 1079.99
CHANNEL LENGTH THRU SUBAREA(FEET) = 1945.82 CHANNEL SLOPE = 0.1662
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.47
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.747

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 232.20 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 534.42

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 14.62

AVERAGE FLOW DEPTH(FEET) = 2.45 TRAVEL TIME(MIN.) = 2.22

Tc(MIN.) = 29.92

SUBAREA AREA(ACRES) = 232.20 SUBAREA RUNOFF(CFS) = 302.42

EFFECTIVE AREA(ACRES) = 509.89 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 509.9 PEAK FLOW RATE(CFS) = 664.09

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.75

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.75 FLOW VELOCITY(FEET/SEC.) = 15.57

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11917.00 = 10305.69 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 11917.00 TO NODE 11920.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1079.99 DOWNSTREAM(FEET) = 873.95
CHANNEL LENGTH THRU SUBAREA(FEET) = 2563.91 CHANNEL SLOPE = 0.0804
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 3.51
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.653

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

USER-DEFINED - 70.48 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 359.32

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.08

AVERAGE FLOW DEPTH(FEET) = 2.41 TRAVEL TIME(MIN.) = 3.16

Tc(MIN.) = 27.70

SUBAREA AREA(ACRES) = 70.48 SUBAREA RUNOFF(CFS) = 97.25

EFFECTIVE AREA(ACRES) = 277.69 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

```

USER-DEFINED          -      110.82      0.30      1.000      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 731.56
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.30
AVERAGE FLOW DEPTH(FEET) = 3.50 TRAVEL TIME(MIN.) = 3.47
Tc(MIN.) = 33.40
SUBAREA AREA(ACRES) = 110.82 SUBAREA RUNOFF(CFS) = 134.92
EFFECTIVE AREA(ACRES) = 620.71 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 620.7 PEAK FLOW RATE(CFS) = 755.69
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 3.56

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 3.56 FLOW VELOCITY(FEET/SEC.) = 12.41
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11920.00 = 12869.60 FEET.

```

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11917.00 TO NODE 11920.00 IS CODE = 1  
-----

```

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<

```

```

=====
TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 33.40
RAINFALL INTENSITY(INCH/HR) = 1.65
AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 1.00
EFFECTIVE STREAM AREA(ACRES) = 620.71
TOTAL STREAM AREA(ACRES) = 620.71
PEAK FLOW RATE(CFS) AT CONFLUENCE = 755.69

```

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	594.38	33.14	1.659	0.30( 0.30)	0.98	484.1	11900.00
2	755.69	33.40	1.653	0.30( 0.30)	1.00	620.7	11910.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1348.14	33.14	1.659	0.30( 0.30)	0.99	1100.1	11900.00
2	1347.14	33.40	1.653	0.30( 0.30)	0.99	1104.8	11910.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:  
PEAK FLOW RATE(CFS) = 1348.14 Tc(MIN.) = 33.14  
EFFECTIVE AREA(ACRES) = 1100.13 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA(ACRES) = 1104.8  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11920.00 = 12869.60 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11920.00 TO NODE 11921.00 IS CODE = 56  
-----

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<

```

```

=====
ELEVATION DATA: UPSTREAM(FEET) = 873.95 DOWNSTREAM(FEET) = 827.94
CHANNEL LENGTH THRU SUBAREA(FEET) = 1417.25 CHANNEL SLOPE = 0.0325
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 6.07
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.599
SUBAREA LOSS RATE DATA(AMC II):

```

```

DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp      Ap      SCS
LAND USE                GROUP  (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED            -      107.47   0.30   1.000   -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1410.97
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.52
AVERAGE FLOW DEPTH(FEET) = 6.06 TRAVEL TIME(MIN.) = 2.25
Tc(MIN.) = 35.39
SUBAREA AREA(ACRES) = 107.47 SUBAREA RUNOFF(CFS) = 125.65
EFFECTIVE AREA(ACRES) = 1207.60 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 1212.3 PEAK FLOW RATE(CFS) = 1413.99
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 6.07

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 6.07 FLOW VELOCITY(FEET/SEC.) = 10.52  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11921.00 = 14286.85 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11921.00 TO NODE 11922.00 IS CODE = 56  
-----

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<

```

```

=====
ELEVATION DATA: UPSTREAM(FEET) = 827.94 DOWNSTREAM(FEET) = 753.55
CHANNEL LENGTH THRU SUBAREA(FEET) = 1886.43 CHANNEL SLOPE = 0.0394
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 6.18
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.527
SUBAREA LOSS RATE DATA(AMC II):

```

```

DEVELOPMENT TYPE/      SCS SOIL  AREA      Fp      Ap      SCS
LAND USE                GROUP  (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED            -      344.27   0.30   1.000   -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1604.04
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.68
AVERAGE FLOW DEPTH(FEET) = 6.15 TRAVEL TIME(MIN.) = 2.69
Tc(MIN.) = 38.08
SUBAREA AREA(ACRES) = 344.27 SUBAREA RUNOFF(CFS) = 380.08
EFFECTIVE AREA(ACRES) = 1551.87 AREA-AVERAGED Fm(INCH/HR) = 0.30

```

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 1556.5 PEAK FLOW RATE(CFS) = 1715.40  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.35

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 6.35 FLOW VELOCITY(FEET/SEC.) = 11.89  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11922.00 = 16173.28 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11922.00 TO NODE 11923.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 753.55 DOWNSTREAM(FEET) = 641.58  
CHANNEL LENGTH THRU SUBAREA(FEET) = 2860.88 CHANNEL SLOPE = 0.0391  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.53  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.442

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	165.18	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1800.27  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.01  
AVERAGE FLOW DEPTH(FEET) = 6.51 TRAVEL TIME(MIN.) = 3.97  
Tc(MIN.) = 42.05

SUBAREA AREA(ACRES) = 165.18 SUBAREA RUNOFF(CFS) = 169.74  
EFFECTIVE AREA(ACRES) = 1717.05 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 1721.7 PEAK FLOW RATE(CFS) = 1766.60  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.46

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 6.46 FLOW VELOCITY(FEET/SEC.) = 11.94  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11923.00 = 19034.16 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11923.00 TO NODE 11924.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 641.58 DOWNSTREAM(FEET) = 579.89  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1844.02 CHANNEL SLOPE = 0.0335  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 7.08  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.399

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	165.18	0.30	1.000	-

LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 433.73 0.30 1.000 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1981.09  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.61  
AVERAGE FLOW DEPTH(FEET) = 7.07 TRAVEL TIME(MIN.) = 2.65  
Tc(MIN.) = 44.70  
SUBAREA AREA(ACRES) = 433.73 SUBAREA RUNOFF(CFS) = 428.97  
EFFECTIVE AREA(ACRES) = 2150.78 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 2155.4 PEAK FLOW RATE(CFS) = 2129.29  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 7.31

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 7.31 FLOW VELOCITY(FEET/SEC.) = 11.83  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11924.00 = 20878.18 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11924.00 TO NODE 11925.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 579.89 DOWNSTREAM(FEET) = 494.12  
CHANNEL LENGTH THRU SUBAREA(FEET) = 2756.15 CHANNEL SLOPE = 0.0311  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 7.65  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.335

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	265.42	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2252.94  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.68  
AVERAGE FLOW DEPTH(FEET) = 7.63 TRAVEL TIME(MIN.) = 3.93  
Tc(MIN.) = 48.63

SUBAREA AREA(ACRES) = 265.42 SUBAREA RUNOFF(CFS) = 247.29  
EFFECTIVE AREA(ACRES) = 2416.20 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 2420.9 PEAK FLOW RATE(CFS) = 2253.25  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 7.63

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 7.63 FLOW VELOCITY(FEET/SEC.) = 11.68  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11925.00 = 23634.33 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11925.00 TO NODE 11926.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<



>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 494.12 DOWNSTREAM(FEET) = 458.40
CHANNEL LENGTH THRU SUBAREA(FEET) = 1922.70 CHANNEL SLOPE = 0.0186
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 8.68

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.294

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

USER-DEFINED - 97.46 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2296.83

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.69

AVERAGE FLOW DEPTH(FEET) = 8.67 TRAVEL TIME(MIN.) = 3.31

Tc(MIN.) = 51.94

SUBAREA AREA(ACRES) = 97.46 SUBAREA RUNOFF(CFS) = 87.17

EFFECTIVE AREA(ACRES) = 2513.66 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 2518.3 PEAK FLOW RATE(CFS) = 2253.25

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 8.60

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 8.60 FLOW VELOCITY(FEET/SEC.) = 9.64

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11926.00 = 25557.03 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 11926.00 TO NODE 11927.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 458.40 DOWNSTREAM(FEET) = 399.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 2170.13 CHANNEL SLOPE = 0.0274
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 7.90

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.262

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN

USER-DEFINED - 53.83 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2276.54

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.17

AVERAGE FLOW DEPTH(FEET) = 7.90 TRAVEL TIME(MIN.) = 3.24

Tc(MIN.) = 55.18

SUBAREA AREA(ACRES) = 53.83 SUBAREA RUNOFF(CFS) = 46.60

EFFECTIVE AREA(ACRES) = 2567.49 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 2572.1 PEAK FLOW RATE(CFS) = 2253.25

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 7.86

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 7.86 FLOW VELOCITY(FEET/SEC.) = 11.14

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 27727.16 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610401X.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

Table with columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 2 rows of data and a total area calculation.

\*\*\*\*\*
FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

Table with columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 2 rows of data and a longest flowpath calculation.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

Table with columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 2 rows of data and a longest flowpath calculation.

\*\* PEAK FLOW RATE TABLE \*\*

Table with columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 4 rows of data and a total area calculation.

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 2841.58 Tc(MIN.) = 55.180
EFFECTIVE AREA(ACRES) = 3219.56 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 3224.2
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 27727.16 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 399.00 DOWNSTREAM(FEET) = 384.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 986.26 CHANNEL SLOPE = 0.0152
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
\*ESTIMATED CHANNEL HEIGHT(FEET) = 9.99
CHANNEL FLOW THRU SUBAREA(CFS) = 2841.58
FLOW VELOCITY(FEET/SEC.) = 9.49 FLOW DEPTH(FEET) = 9.99
TRAVEL TIME(MIN.) = 1.73 Tc(MIN.) = 56.91
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.50 = 28713.42 FEET.

FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610402X.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM Q Tc Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 79.39 13.47 0.30( 0.30) 1.00 33.3 40200.00
TOTAL AREA(ACRES) = 33.3

FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 2718.74 26.15 1.893 0.30( 0.30) 1.00 1756.5 40120.00
2 2743.23 27.95 1.823 0.30( 0.30) 1.00 1871.4 40100.00
3 2841.58 56.91 1.245 0.30( 0.30) 1.00 3219.6 11900.00
4 2835.43 57.18 1.242 0.30( 0.30) 1.00 3224.2 11910.00
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.50 = 28713.42 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 79.39 13.47 2.949 0.30( 0.30) 1.00 33.3 40200.00
LONGEST FLOWPATH FROM NODE 40200.00 TO NODE 11927.50 = 1999.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 2407.13 13.47 2.949 0.30( 0.30) 1.00 938.2 40200.00

2 2766.51 26.15 1.893 0.30( 0.30) 1.00 1789.8 40120.00
3 2788.89 27.95 1.823 0.30( 0.30) 1.00 1904.7 40100.00
4 2869.89 56.91 1.245 0.30( 0.30) 1.00 3252.9 11900.00
5 2863.66 57.18 1.242 0.30( 0.30) 1.00 3257.5 11910.00
TOTAL AREA(ACRES) = 3257.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 2869.89 Tc(MIN.) = 56.913
EFFECTIVE AREA(ACRES) = 3252.87 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 3257.5
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.50 = 28713.42 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 11927.50 TO NODE 11928.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 384.00 DOWNSTREAM(FEET) = 359.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 647.19 CHANNEL SLOPE = 0.0386
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
\*ESTIMATED CHANNEL HEIGHT(FEET) = 8.17
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.237

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 78.01 0.30 0.984 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.984
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2902.94
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 13.50
AVERAGE FLOW DEPTH(FEET) = 8.17 TRAVEL TIME(MIN.) = 0.80
Tc(MIN.) = 57.71

SUBAREA AREA(ACRES) = 78.01 SUBAREA RUNOFF(CFS) = 66.10
EFFECTIVE AREA(ACRES) = 3330.88 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 3335.5 PEAK FLOW RATE(CFS) = 2869.89

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
\*ESTIMATED CHANNEL HEIGHT(FEET) = 8.12

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 8.12 FLOW VELOCITY(FEET/SEC.) = 13.47
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11928.00 = 29360.61 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 359.00 DOWNSTREAM(FEET) = 341.63
CHANNEL LENGTH THRU SUBAREA(FEET) = 1322.66 CHANNEL SLOPE = 0.0131
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT (FEET) = 10.37  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.213  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 8.18 0.30 0.890 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.890  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 2873.37  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 9.01  
 AVERAGE FLOW DEPTH (FEET) = 10.37 TRAVEL TIME (MIN.) = 2.45  
 Tc (MIN.) = 60.16  
 SUBAREA AREA (ACRES) = 8.18 SUBAREA RUNOFF (CFS) = 6.96  
 EFFECTIVE AREA (ACRES) = 3339.06 AREA-AVERAGED Fm (INCH/HR) = 0.30  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA (ACRES) = 3343.7 PEAK FLOW RATE (CFS) = 2869.89  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 10.37

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 10.37 FLOW VELOCITY (FEET/SEC.) = 9.01  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11929.00 = 30683.27 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 10  
 -----  
 >>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 3 <<<<<  
 =====

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11841.00 TO NODE 11527.00 IS CODE = 12  
 -----  
 >>>>CLEAR MEMORY BANK # 1 <<<<<  
 =====

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11841.00 TO NODE 12527.00 IS CODE = 15.1  
 -----  
 >>>>DEFINE MEMORY BANK # 1 <<<<<  
 =====

PEAK FLOWRATE TABLE FILE NAME: S18X50.DNA  
 MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18863.84	37.77	0.30 ( 0.30)	1.00	7696.5	11831.00
2	19171.93	40.18	0.30 ( 0.30)	1.00	8206.0	11801.00
3	20870.42	51.52	0.30 ( 0.30)	1.00	11178.6	11530.00
4	21741.74	56.15	0.30 ( 0.30)	1.00	12836.1	11701.00
5	22206.97	58.56	0.30 ( 0.30)	1.00	13761.0	11000.00
6	24578.79	68.37	0.30 ( 0.30)	1.00	18741.7	11330.00
7	24998.78	70.58	0.30 ( 0.30)	1.00	19900.2	10800.00
8	25620.24	74.96	0.30 ( 0.30)	1.00	22211.8	11130.00
9	25459.58	83.55	0.30 ( 0.30)	1.00	25307.4	11620.00
10	25389.29	85.79	0.30 ( 0.30)	1.00	26059.8	11600.00
11	25269.09	87.43	0.30 ( 0.30)	1.00	26526.1	10600.00
12	25052.94	92.79	0.30 ( 0.30)	1.00	28070.1	11201.00

13	24726.86	98.42	0.30 ( 0.30)	1.00	29254.4	10710.00
14	24565.08	100.41	0.30 ( 0.30)	1.00	29586.3	10410.00
15	24070.54	105.10	0.30 ( 0.30)	1.00	30247.3	10700.00
16	23353.04	112.10	0.30 ( 0.30)	1.00	31166.7	10400.00
17	23163.67	114.42	0.30 ( 0.30)	1.00	31437.3	10200.00
18	22543.84	120.36	0.30 ( 0.30)	1.00	32015.5	10300.00
19	21907.93	125.43	0.30 ( 0.30)	1.00	32220.3	10210.00
20	19363.37	152.55	0.30 ( 0.30)	1.00	32916.6	10100.00
TOTAL AREA (ACRES) =						32916.6

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 12  
 -----  
 >>>>CLEAR MEMORY BANK # 2 <<<<<  
 =====

\*\*\*MEMORY BANK # 2 IS EMPTY - PROCESS IGNORED.\*\*\*  
 \*\*\*\*\*

FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 15.1  
 -----  
 >>>>DEFINE MEMORY BANK # 2 <<<<<  
 =====

PEAK FLOWRATE TABLE FILE NAME: S25X50.DNA  
 MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	6814.52	66.91	0.30 ( 0.30)	0.99	6393.3	12500.00
2	7515.45	80.53	0.30 ( 0.30)	0.99	8363.5	12300.00
3	7623.90	81.91	0.30 ( 0.30)	0.98	8652.7	12330.00
4	7789.58	84.57	0.30 ( 0.30)	0.98	9163.3	12410.00
5	7994.43	88.75	0.30 ( 0.29)	0.98	9893.3	12400.00
6	8150.23	93.51	0.30 ( 0.29)	0.98	10584.1	12211.00
7	8242.61	97.70	0.30 ( 0.29)	0.98	11179.8	12201.00
8	8205.03	101.92	0.30 ( 0.29)	0.98	11654.1	12111.00
9	8180.32	104.56	0.30 ( 0.29)	0.98	11967.4	12231.00
10	8145.23	107.37	0.30 ( 0.29)	0.98	12265.9	12101.10
11	8125.55	108.34	0.30 ( 0.29)	0.98	12357.2	12261.00
12	7675.64	119.74	0.30 ( 0.29)	0.98	13113.0	12010.00
13	7214.09	128.35	0.30 ( 0.29)	0.98	13237.1	12000.00
TOTAL AREA (ACRES) =						13237.1

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 14.0  
 -----  
 >>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<  
 =====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	6814.52	66.91	0.30 ( 0.30)	0.99	6393.3	12500.00
2	7515.45	80.53	0.30 ( 0.30)	0.99	8363.5	12300.00
3	7623.90	81.91	0.30 ( 0.30)	0.98	8652.7	12330.00
4	7789.58	84.57	0.30 ( 0.30)	0.98	9163.3	12410.00
5	7994.43	88.75	0.30 ( 0.29)	0.98	9893.3	12400.00
6	8150.23	93.51	0.30 ( 0.29)	0.98	10584.1	12211.00
7	8242.61	97.70	0.30 ( 0.29)	0.98	11179.8	12201.00
8	8205.03	101.92	0.30 ( 0.29)	0.98	11654.1	12111.00

9	8180.32	104.56	0.30 ( 0.29)	0.98	11967.4	12231.00
10	8145.23	107.37	0.30 ( 0.29)	0.98	12265.9	12101.10
11	8125.55	108.34	0.30 ( 0.29)	0.98	12357.2	12261.00
12	7675.64	119.74	0.30 ( 0.29)	0.98	13113.0	12010.00
13	7214.09	128.35	0.30 ( 0.29)	0.98	13237.1	12000.00
TOTAL AREA (ACRES) = 13237.1						

\*\*\*\*\*

FLOW PROCESS FROM NODE 11841.00 TO NODE 12527.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	6814.52	66.91	1.167	0.30 ( 0.30)	0.99	6393.3	12500.00
2	7515.45	80.53	1.074	0.30 ( 0.30)	0.99	8363.5	12300.00
3	7623.90	81.91	1.065	0.30 ( 0.30)	0.98	8652.7	12330.00
4	7789.58	84.57	1.047	0.30 ( 0.30)	0.98	9163.3	12410.00
5	7994.43	88.75	1.018	0.30 ( 0.29)	0.98	9893.3	12400.00
6	8150.23	93.51	0.995	0.30 ( 0.29)	0.98	10584.1	12211.00
7	8242.61	97.70	0.977	0.30 ( 0.29)	0.98	11179.8	12201.00
8	8205.03	101.92	0.958	0.30 ( 0.29)	0.98	11654.1	12111.00
9	8180.32	104.56	0.947	0.30 ( 0.29)	0.98	11967.4	12231.00
10	8145.23	107.37	0.935	0.30 ( 0.29)	0.98	12265.9	12101.10
11	8125.55	108.34	0.931	0.30 ( 0.29)	0.98	12357.2	12261.00
12	7675.64	119.74	0.881	0.30 ( 0.29)	0.98	13113.0	12010.00
13	7214.09	128.35	0.863	0.30 ( 0.29)	0.98	13237.1	12000.00

LONGEST FLOWPATH FROM NODE 12000.00 TO NODE 12527.00 = 77156.98 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	18863.84	37.77	1.535	0.30 ( 0.30)	1.00	7696.5	11831.00
2	19171.93	40.18	1.472	0.30 ( 0.30)	1.00	8206.0	11801.00
3	20870.42	51.52	1.298	0.30 ( 0.30)	1.00	11178.6	11530.00
4	21741.74	56.15	1.252	0.30 ( 0.30)	1.00	12836.1	11701.00
5	22206.97	58.56	1.228	0.30 ( 0.30)	1.00	13761.0	11000.00
6	24578.79	68.37	1.157	0.30 ( 0.30)	1.00	18741.7	11330.00
7	24998.78	70.58	1.142	0.30 ( 0.30)	1.00	19900.2	10800.00
8	25620.24	74.96	1.112	0.30 ( 0.30)	1.00	22211.8	11130.00
9	25459.58	83.55	1.054	0.30 ( 0.30)	1.00	25307.4	11620.00
10	25389.29	85.79	1.039	0.30 ( 0.30)	1.00	26059.8	11600.00
11	25269.09	87.43	1.027	0.30 ( 0.30)	1.00	26526.1	10600.00
12	25052.94	92.79	0.998	0.30 ( 0.30)	1.00	28070.1	11201.00
13	24726.86	98.42	0.974	0.30 ( 0.30)	1.00	29254.4	10710.00
14	24565.08	100.41	0.965	0.30 ( 0.30)	1.00	29586.3	10410.00
15	24070.54	105.10	0.945	0.30 ( 0.30)	1.00	30247.3	10700.00
16	23353.04	112.10	0.914	0.30 ( 0.30)	1.00	31166.7	10400.00
17	23163.67	114.42	0.904	0.30 ( 0.30)	1.00	31437.3	10200.00
18	22543.84	120.36	0.879	0.30 ( 0.30)	1.00	32015.5	10300.00
19	21907.93	125.43	0.869	0.30 ( 0.30)	1.00	32220.3	10210.00
20	19363.37	152.55	0.815	0.30 ( 0.30)	1.00	32916.6	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12527.00 = 97868.13 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	--------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	24335.68	37.77	1.535	0.30 ( 0.30)	0.99	11305.9
2	24697.44	40.18	1.472	0.30 ( 0.30)	0.99	12045.5
3	26906.53	51.52	1.298	0.30 ( 0.30)	0.99	16101.8
4	28019.04	56.15	1.252	0.30 ( 0.30)	0.99	18201.1
5	28590.34	58.56	1.228	0.30 ( 0.30)	0.99	19356.3
6	31039.95	66.91	1.167	0.30 ( 0.30)	0.99	24392.9
7	31468.57	68.37	1.157	0.30 ( 0.30)	0.99	25346.5
8	32002.18	70.58	1.142	0.30 ( 0.30)	0.99	26824.3
9	32849.10	74.96	1.112	0.30 ( 0.30)	0.99	29769.7
10	33031.62	80.53	1.074	0.30 ( 0.30)	0.99	32580.5
11	33114.20	81.91	1.065	0.30 ( 0.30)	0.99	33368.0
12	33186.01	83.55	1.054	0.30 ( 0.30)	0.99	34276.0
13	33217.38	84.57	1.047	0.30 ( 0.30)	0.99	34810.9
14	33238.92	85.79	1.039	0.30 ( 0.30)	0.99	35437.1
15	33199.04	87.43	1.027	0.30 ( 0.30)	0.99	36189.6
16	33210.37	88.75	1.018	0.30 ( 0.30)	0.99	36799.1
17	33179.69	92.79	0.998	0.30 ( 0.30)	0.99	38550.0
18	33161.66	93.51	0.995	0.30 ( 0.30)	0.99	38804.9
19	33011.46	97.70	0.977	0.30 ( 0.30)	0.99	40281.7
20	32963.01	98.42	0.974	0.30 ( 0.30)	0.99	40515.8
21	32783.54	100.41	0.965	0.30 ( 0.30)	0.99	41070.9
22	32611.09	101.92	0.958	0.30 ( 0.30)	0.99	41453.0
23	32307.60	104.56	0.947	0.30 ( 0.30)	0.99	42138.9
24	32244.16	105.10	0.945	0.30 ( 0.30)	0.99	42271.8
25	31982.44	107.37	0.935	0.30 ( 0.30)	0.99	42812.2
26	31863.89	108.34	0.931	0.30 ( 0.30)	0.99	43030.2
27	31330.23	112.10	0.914	0.30 ( 0.30)	0.99	43773.2
28	31049.28	114.42	0.904	0.30 ( 0.30)	0.99	44197.6
29	30284.07	119.74	0.881	0.30 ( 0.30)	0.99	45068.3
30	30186.30	120.36	0.879	0.30 ( 0.30)	0.99	45137.4
31	29278.79	125.43	0.869	0.30 ( 0.30)	0.99	45415.2
32	28847.68	128.35	0.863	0.30 ( 0.30)	0.99	45532.4
33	25964.49	152.55	0.815	0.30 ( 0.30)	0.99	46153.7

TOTAL AREA (ACRES) = 46153.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 33238.92 Tc (MIN.) = 85.792  
EFFECTIVE AREA (ACRES) = 35437.09 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 46153.7  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12527.00 = 97868.13 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12527.00 TO NODE 11929.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 347.47 DOWNSTREAM (FEET) = 341.63  
CHANNEL LENGTH THRU SUBAREA (FEET) = 532.38 CHANNEL SLOPE = 0.0110  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.040  
\* ESTIMATED CHANNEL HEIGHT (FEET) = 9.03  
\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.035  
SUBAREA LOSS RATE DATA (AMC II):  
DEVELOPMENT TYPE/ LAND USE SCS SOIL GROUP AREA (ACRES) Fp (INCH/HR) Ap (DECIMAL) SCS CN

USER-DEFINED - 14.37 0.30 0.987 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.987  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 33243.70  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 15.02  
 AVERAGE FLOW DEPTH (FEET) = 9.03 TRAVEL TIME (MIN.) = 0.59  
 Tc (MIN.) = 86.38  
 SUBAREA AREA (ACRES) = 14.37 SUBAREA RUNOFF (CFS) = 9.55  
 EFFECTIVE AREA (ACRES) = 35451.46 AREA-AVERAGED Fm (INCH/HR) = 0.30  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA (ACRES) = 46168.0 PEAK FLOW RATE (CFS) = 33238.92  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 9.03

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 9.03 FLOW VELOCITY (FEET/SEC.) = 15.01  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24335.68	38.43	1.517	0.30 ( 0.30)	0.99	11320.3	11831.00
2	24697.44	40.83	1.461	0.30 ( 0.30)	0.99	12059.9	11801.00
3	26906.53	52.16	1.292	0.30 ( 0.30)	0.99	16116.2	11530.00
4	28019.04	56.77	1.246	0.30 ( 0.30)	0.99	18215.4	11701.00
5	28590.34	59.18	1.222	0.30 ( 0.30)	0.99	19370.6	11000.00
6	31039.95	67.51	1.163	0.30 ( 0.30)	0.99	24407.3	12500.00
7	31468.57	68.97	1.153	0.30 ( 0.30)	0.99	25360.9	11330.00
8	32002.18	71.18	1.138	0.30 ( 0.30)	0.99	26838.7	10800.00
9	32849.10	75.55	1.108	0.30 ( 0.30)	0.99	29784.1	11130.00
10	33031.62	81.12	1.070	0.30 ( 0.30)	0.99	32594.9	12300.00
11	33114.20	82.50	1.061	0.30 ( 0.30)	0.99	33382.4	12330.00
12	33186.01	84.14	1.050	0.30 ( 0.30)	0.99	34290.4	11620.00
13	33217.38	85.16	1.043	0.30 ( 0.30)	0.99	34825.3	12410.00
14	33238.92	86.38	1.035	0.30 ( 0.30)	0.99	35451.5	11600.00
15	33199.04	88.02	1.023	0.30 ( 0.30)	0.99	36204.0	10600.00
16	33210.37	89.34	1.014	0.30 ( 0.30)	0.99	36813.4	12400.00
17	33179.69	93.38	0.995	0.30 ( 0.30)	0.99	38564.4	11201.00
18	33161.66	94.10	0.992	0.30 ( 0.30)	0.99	38819.3	12211.00
19	33011.46	98.29	0.974	0.30 ( 0.30)	0.99	40296.1	12201.00
20	32963.01	99.01	0.971	0.30 ( 0.30)	0.99	40530.1	10710.00
21	32783.54	101.00	0.962	0.30 ( 0.30)	0.99	41085.2	10410.00
22	32611.09	102.51	0.956	0.30 ( 0.30)	0.99	41467.3	12111.00
23	32307.60	105.16	0.944	0.30 ( 0.30)	0.99	42153.2	12231.00
24	32244.16	105.69	0.942	0.30 ( 0.30)	0.99	42286.1	10700.00
25	31982.44	107.97	0.932	0.30 ( 0.30)	0.99	42826.5	12101.10
26	31863.89	108.94	0.928	0.30 ( 0.30)	0.99	43044.6	12261.00
27	31330.23	112.70	0.912	0.30 ( 0.30)	0.99	43787.5	10400.00
28	31049.28	115.02	0.902	0.30 ( 0.30)	0.99	44211.9	10200.00
29	30284.07	120.35	0.879	0.30 ( 0.30)	0.99	45082.6	12010.00

30	30186.30	120.97	0.878	0.30 ( 0.30)	0.99	45151.8	10300.00
31	29278.79	126.04	0.868	0.30 ( 0.30)	0.99	45429.6	10210.00
32	28847.68	128.97	0.862	0.30 ( 0.30)	0.99	45546.8	12000.00
33	25964.49	153.19	0.814	0.30 ( 0.30)	0.99	46168.0	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2407.13	16.86	2.527	0.30 ( 0.30)	1.00	1024.4	40200.00
2	2766.51	29.42	1.766	0.30 ( 0.30)	1.00	1876.0	40120.00
3	2788.89	31.22	1.711	0.30 ( 0.30)	1.00	1990.9	40100.00
4	2869.89	60.16	1.213	0.30 ( 0.30)	1.00	3339.1	11900.00
5	2863.66	60.43	1.211	0.30 ( 0.30)	1.00	3343.7	11910.00

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11929.00 = 30683.27 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21920.18	16.86	2.527	0.30 ( 0.30)	0.99	5990.1	40200.00
2	25205.06	29.42	1.766	0.30 ( 0.30)	0.99	10543.2	40120.00
3	25703.23	31.22	1.711	0.30 ( 0.30)	0.99	11187.8	40100.00
4	27144.74	38.43	1.517	0.30 ( 0.30)	0.99	13647.0	11831.00
5	27513.24	40.83	1.461	0.30 ( 0.30)	0.99	14498.7	11801.00
6	29754.02	52.16	1.292	0.30 ( 0.30)	0.99	19082.5	11530.00
7	30879.45	56.77	1.246	0.30 ( 0.30)	0.99	21396.7	11701.00
8	31457.48	59.18	1.222	0.30 ( 0.30)	0.99	22664.0	11000.00
9	31748.64	60.16	1.213	0.30 ( 0.30)	0.99	23302.7	11900.00
10	31820.89	60.43	1.211	0.30 ( 0.30)	0.99	23468.7	11910.00
11	33752.31	67.51	1.163	0.30 ( 0.30)	0.99	27751.0	12500.00
12	34149.77	68.97	1.153	0.30 ( 0.30)	0.99	28704.6	11330.00
13	34636.32	71.18	1.138	0.30 ( 0.30)	0.99	30182.4	10800.00
14	35389.84	75.55	1.108	0.30 ( 0.30)	0.99	33127.8	11130.00
15	35453.50	81.12	1.070	0.30 ( 0.30)	0.99	35938.6	12300.00
16	35506.55	82.50	1.061	0.30 ( 0.30)	0.99	36726.1	12330.00
17	35543.27	84.14	1.050	0.30 ( 0.30)	0.99	37634.1	11620.00
18	35553.03	85.16	1.043	0.30 ( 0.30)	0.99	38169.0	12410.00
19	35548.38	86.38	1.035	0.30 ( 0.30)	0.99	38795.2	11600.00
20	35473.47	88.02	1.023	0.30 ( 0.30)	0.99	39547.7	10600.00
21	35456.67	89.34	1.014	0.30 ( 0.30)	0.99	40157.1	12400.00
22	35365.93	93.38	0.995	0.30 ( 0.30)	0.99	41908.1	11201.00
23	35338.14	94.10	0.992	0.30 ( 0.30)	0.99	42163.0	12211.00
24	35130.93	98.29	0.974	0.30 ( 0.30)	0.99	43639.8	12201.00
25	35072.61	99.01	0.971	0.30 ( 0.30)	0.99	43873.9	10710.00
26	34866.11	101.00	0.962	0.30 ( 0.30)	0.99	44428.9	10410.00
27	34673.13	102.51	0.956	0.30 ( 0.30)	0.99	44811.1	12111.00
28	34333.63	105.16	0.944	0.30 ( 0.30)	0.99	45497.0	12231.00
29	34262.87	105.69	0.942	0.30 ( 0.30)	0.99	45629.8	10700.00
30	33970.14	107.97	0.932	0.30 ( 0.30)	0.99	46170.2	12101.10
31	33838.46	108.94	0.928	0.30 ( 0.30)	0.99	46388.3	12261.00
32	33253.60	112.70	0.912	0.30 ( 0.30)	0.99	47131.2	10400.00
33	32941.05	115.02	0.902	0.30 ( 0.30)	0.99	47555.7	10200.00
34	32105.94	120.35	0.879	0.30 ( 0.30)	0.99	48426.4	12010.00
35	32004.27	120.97	0.878	0.30 ( 0.30)	0.99	48495.5	10300.00
36	31064.91	126.04	0.868	0.30 ( 0.30)	0.99	48773.3	10210.00
37	30615.42	128.97	0.862	0.30 ( 0.30)	0.99	48890.5	12000.00
38	27580.13	153.19	0.814	0.30 ( 0.30)	0.99	49511.8	10100.00

TOTAL AREA (ACRES) = 49511.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 35553.03 Tc(MIN.) = 85.157  
 EFFECTIVE AREA(ACRES) = 38168.99 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 49511.8  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

=====  
 END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 49511.8 TC(MIN.) = 85.16  
 EFFECTIVE AREA(ACRES) = 38168.99 AREA-AVERAGED Fm(INCH/HR)= 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.994  
 PEAK FLOW RATE(CFS) = 35553.03

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21920.18	16.86	2.527	0.30( 0.30)	0.99	5990.1	40200.00
2	25205.06	29.42	1.766	0.30( 0.30)	0.99	10543.2	40120.00
3	25703.23	31.22	1.711	0.30( 0.30)	0.99	11187.8	40100.00
4	27144.74	38.43	1.517	0.30( 0.30)	0.99	13647.0	11831.00
5	27513.24	40.83	1.461	0.30( 0.30)	0.99	14498.7	11801.00
6	29754.02	52.16	1.292	0.30( 0.30)	0.99	19082.5	11530.00
7	30879.45	56.77	1.246	0.30( 0.30)	0.99	21396.7	11701.00
8	31457.48	59.18	1.222	0.30( 0.30)	0.99	22664.0	11000.00
9	31748.64	60.16	1.213	0.30( 0.30)	0.99	23302.7	11900.00
10	31820.89	60.43	1.211	0.30( 0.30)	0.99	23468.7	11910.00
11	33752.31	67.51	1.163	0.30( 0.30)	0.99	27751.0	12500.00
12	34149.77	68.97	1.153	0.30( 0.30)	0.99	28704.6	11330.00
13	34636.32	71.18	1.138	0.30( 0.30)	0.99	30182.4	10800.00
14	35389.84	75.55	1.108	0.30( 0.30)	0.99	33127.8	11130.00
15	35453.50	81.12	1.070	0.30( 0.30)	0.99	35938.6	12300.00
16	35506.55	82.50	1.061	0.30( 0.30)	0.99	36726.1	12330.00
17	35543.27	84.14	1.050	0.30( 0.30)	0.99	37634.1	11620.00
18	35553.03	85.16	1.043	0.30( 0.30)	0.99	38169.0	12410.00
19	35548.38	86.38	1.035	0.30( 0.30)	0.99	38795.2	11600.00
20	35473.47	88.02	1.023	0.30( 0.30)	0.99	39547.7	10600.00
21	35456.67	89.34	1.014	0.30( 0.30)	0.99	40157.1	12400.00
22	35365.93	93.38	0.995	0.30( 0.30)	0.99	41908.1	11201.00
23	35338.14	94.10	0.992	0.30( 0.30)	0.99	42163.0	12211.00
24	35130.93	98.29	0.974	0.30( 0.30)	0.99	43639.8	12201.00
25	35072.61	99.01	0.971	0.30( 0.30)	0.99	43873.9	10710.00
26	34866.11	101.00	0.962	0.30( 0.30)	0.99	44428.9	10410.00
27	34673.13	102.51	0.956	0.30( 0.30)	0.99	44811.1	12111.00
28	34333.63	105.16	0.944	0.30( 0.30)	0.99	45497.0	12231.00
29	34262.87	105.69	0.942	0.30( 0.30)	0.99	45629.8	10700.00
30	33970.14	107.97	0.932	0.30( 0.30)	0.99	46170.2	12101.10
31	33838.46	108.94	0.928	0.30( 0.30)	0.99	46388.3	12261.00
32	33253.60	112.70	0.912	0.30( 0.30)	0.99	47131.2	10400.00
33	32941.05	115.02	0.902	0.30( 0.30)	0.99	47555.7	10200.00
34	32105.94	120.35	0.879	0.30( 0.30)	0.99	48426.4	12010.00
35	32004.27	120.97	0.878	0.30( 0.30)	0.99	48495.5	10300.00
36	31064.91	126.04	0.868	0.30( 0.30)	0.99	48773.3	10210.00
37	30615.42	128.97	0.862	0.30( 0.30)	0.99	48890.5	12000.00
38	27580.13	153.19	0.814	0.30( 0.30)	0.99	49511.8	10100.00

=====  
 END OF RATIONAL METHOD ANALYSIS



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S26- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 50-YR RM EV APRIL 2019 CCHIU \*  
\*\*\*\*\*

FILE NAME: RI50EV26.DAT  
TIME/DATE OF STUDY: 09:13 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 50.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.516
- 2) 10.00; 3.520
- 3) 15.00; 2.687
- 4) 20.00; 2.242
- 5) 25.00; 1.935
- 6) 30.00; 1.742
- 7) 40.00; 1.473
- 8) 50.00; 1.311
- 9) 60.00; 1.211
- 10) 90.00; 1.008
- 11) 120.00; 0.877
- 12) 180.00; 0.757
- 13) 360.00; 0.563
- 14) 1200.00; 0.248

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI50EV19.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21920.18	16.86	0.30 ( 0.30)	0.99	5990.1	40200.00
2	25703.23	31.22	0.30 ( 0.30)	0.99	11187.8	40100.00
3	27513.24	40.83	0.30 ( 0.30)	0.99	14498.7	11801.00
4	29754.02	52.16	0.30 ( 0.30)	0.99	19082.5	11530.00
5	30879.45	56.77	0.30 ( 0.30)	0.99	21396.7	11701.00
6	31820.89	60.43	0.30 ( 0.30)	0.99	23468.7	11910.00
7	34636.32	71.18	0.30 ( 0.30)	0.99	30182.4	10800.00
8	35389.84	75.55	0.30 ( 0.30)	0.99	33127.8	11130.00
9	35553.03	85.16	0.30 ( 0.30)	0.99	38169.0	12410.00
10	35473.47	88.02	0.30 ( 0.30)	0.99	39547.7	10600.00
11	35365.93	93.38	0.30 ( 0.30)	0.99	41908.1	11201.00
12	35130.93	98.29	0.30 ( 0.30)	0.99	43639.8	12201.00
13	34866.11	101.00	0.30 ( 0.30)	0.99	44428.9	10410.00
14	34333.63	105.16	0.30 ( 0.30)	0.99	45497.0	12231.00
15	33970.14	107.97	0.30 ( 0.30)	0.99	46170.2	12101.10
16	33253.60	112.70	0.30 ( 0.30)	0.99	47131.2	10400.00
17	32105.94	120.35	0.30 ( 0.30)	0.99	48426.4	12010.00
18	31064.91	126.04	0.30 ( 0.30)	0.99	48773.3	10210.00
19	30615.42	128.97	0.30 ( 0.30)	0.99	48890.5	12000.00
20	27580.13	153.19	0.30 ( 0.30)	0.99	49511.8	10100.00
TOTAL AREA (ACRES) =						49511.8

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21920.18	16.86	0.30 ( 0.30)	0.99	5990.1	40200.00
2	25703.23	31.22	0.30 ( 0.30)	0.99	11187.8	40100.00
3	27513.24	40.83	0.30 ( 0.30)	0.99	14498.7	11801.00
4	29754.02	52.16	0.30 ( 0.30)	0.99	19082.5	11530.00
5	30879.45	56.77	0.30 ( 0.30)	0.99	21396.7	11701.00
6	31820.89	60.43	0.30 ( 0.30)	0.99	23468.7	11910.00
7	34636.32	71.18	0.30 ( 0.30)	0.99	30182.4	10800.00
8	35389.84	75.55	0.30 ( 0.30)	0.99	33127.8	11130.00
9	35553.03	85.16	0.30 ( 0.30)	0.99	38169.0	12410.00
10	35473.47	88.02	0.30 ( 0.30)	0.99	39547.7	10600.00
11	35365.93	93.38	0.30 ( 0.30)	0.99	41908.1	11201.00
12	35130.93	98.29	0.30 ( 0.30)	0.99	43639.8	12201.00
13	34866.11	101.00	0.30 ( 0.30)	0.99	44428.9	10410.00



14	34333.63	105.16	0.30	( 0.30)	0.99	45497.0	12231.00
15	33970.14	107.97	0.30	( 0.30)	0.99	46170.2	12101.10
16	33253.60	112.70	0.30	( 0.30)	0.99	47131.2	10400.00
17	32105.94	120.35	0.30	( 0.30)	0.99	48426.4	12010.00
18	31064.91	126.04	0.30	( 0.30)	0.99	48773.3	10210.00
19	30615.42	128.97	0.30	( 0.30)	0.99	48890.5	12000.00
20	27580.13	153.19	0.30	( 0.30)	0.99	49511.8	10100.00

TOTAL AREA (ACRES) = 49511.8

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 1 <<<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11929.00 TO NODE 12601.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 341.63 DOWNSTREAM (FEET) = 325.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1467.93 CHANNEL SLOPE = 0.0113  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT (FEET) = 7.89

\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.032

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	14.11	0.30	0.700	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.700

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 35558.25

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 18.81

AVERAGE FLOW DEPTH (FEET) = 7.89 TRAVEL TIME (MIN.) = 1.30

Tc (MIN.) = 86.46

SUBAREA AREA (ACRES) = 14.11 SUBAREA RUNOFF (CFS) = 10.44

EFFECTIVE AREA (ACRES) = 38183.10 AREA-AVERAGED Fm (INCH/HR) = 0.30

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA (ACRES) = 49525.9 PEAK FLOW RATE (CFS) = 35553.03

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT (FEET) = 7.89

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 7.89 FLOW VELOCITY (FEET/SEC.) = 18.81

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 2 <<<<<<

PEAK FLOWRATE TABLE FILE NAME: 3050EVRL.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM	Q	Tc	Fp (Fm)	Ap	Ae	HEADWATER
--------	---	----	---------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(ACRES)	NODE
1	98.06	16.58	0.30 ( 0.30)	0.98	48.4 600.00
TOTAL AREA (ACRES) =			48.4		

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21920.18	18.39	2.385	0.30 ( 0.30)	0.99	6004.2	40200.00
2	25703.23	32.67	1.670	0.30 ( 0.30)	0.99	11201.9	40100.00
3	27513.24	42.25	1.437	0.30 ( 0.30)	0.99	14512.8	11801.00
4	29754.02	53.54	1.276	0.30 ( 0.30)	0.99	19096.6	11530.00
5	30879.45	58.14	1.230	0.30 ( 0.30)	0.99	21410.9	11701.00
6	31820.89	61.78	1.199	0.30 ( 0.30)	0.99	23482.8	11910.00
7	34636.32	72.49	1.126	0.30 ( 0.30)	0.99	30196.5	10800.00
8	35389.84	76.85	1.097	0.30 ( 0.30)	0.99	33141.9	11130.00
9	35553.03	86.46	1.032	0.30 ( 0.30)	0.99	38183.1	12410.00
10	35473.47	89.33	1.013	0.30 ( 0.30)	0.99	39561.8	10600.00
11	35365.93	94.68	0.988	0.30 ( 0.30)	0.99	41922.2	11201.00
12	35130.93	99.59	0.966	0.30 ( 0.30)	0.99	43653.9	12201.00
13	34866.11	102.31	0.954	0.30 ( 0.30)	0.99	44443.1	10410.00
14	34333.63	106.47	0.936	0.30 ( 0.30)	0.99	45511.1	12231.00
15	33970.14	109.29	0.924	0.30 ( 0.30)	0.99	46184.4	12101.10
16	33253.60	114.03	0.903	0.30 ( 0.30)	0.99	47145.4	10400.00
17	32105.94	121.70	0.874	0.30 ( 0.30)	0.99	48440.5	12010.00
18	31064.91	127.40	0.862	0.30 ( 0.30)	0.99	48787.4	10210.00
19	30615.42	130.34	0.856	0.30 ( 0.30)	0.99	48904.6	12000.00
20	27580.13	154.61	0.808	0.30 ( 0.30)	0.99	49525.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	98.06	16.58	2.546	0.30 ( 0.30)	0.98	48.4	600.00

LONGEST FLOWPATH FROM NODE 600.00 TO NODE 12601.00 = 4850.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21386.24	16.58	2.546	0.30 ( 0.30)	0.99	5462.0	600.00
2	22011.23	18.39	2.385	0.30 ( 0.30)	0.99	6052.6	40200.00
3	25763.12	32.67	1.670	0.30 ( 0.30)	0.99	11250.3	40100.00
4	27562.95	42.25	1.437	0.30 ( 0.30)	0.99	14561.2	11801.00
5	29796.73	53.54	1.276	0.30 ( 0.30)	0.99	19145.0	11530.00
6	30920.15	58.14	1.230	0.30 ( 0.30)	0.99	21459.3	11701.00
7	31860.27	61.78	1.199	0.30 ( 0.30)	0.99	23531.2	11910.00
8	34672.54	72.49	1.126	0.30 ( 0.30)	0.99	30244.9	10800.00
9	35424.77	76.85	1.097	0.30 ( 0.30)	0.99	33190.3	11130.00
10	35585.12	86.46	1.032	0.30 ( 0.30)	0.99	38231.5	12410.00
11	35504.72	89.33	1.013	0.30 ( 0.30)	0.99	39610.2	10600.00
12	35396.09	94.68	0.988	0.30 ( 0.30)	0.99	41970.6	11201.00
13	35160.16	99.59	0.966	0.30 ( 0.30)	0.99	43702.3	12201.00
14	34894.82	102.31	0.954	0.30 ( 0.30)	0.99	44491.4	10410.00

15	34361.55	106.47	0.936	0.30	( 0.30)	0.99	45559.5	12231.00
16	33997.53	109.29	0.924	0.30	( 0.30)	0.99	46232.8	12101.10
17	33280.08	114.03	0.903	0.30	( 0.30)	0.99	47193.8	10400.00
18	32131.13	121.70	0.874	0.30	( 0.30)	0.99	48488.9	12010.00
19	31089.61	127.40	0.862	0.30	( 0.30)	0.99	48835.8	10210.00
20	30639.86	130.34	0.856	0.30	( 0.30)	0.99	48953.0	12000.00
21	27602.46	154.61	0.808	0.30	( 0.30)	0.99	49574.3	10100.00

TOTAL AREA (ACRES) = 49574.3

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 35585.12 Tc (MIN.) = 86.457  
EFFECTIVE AREA (ACRES) = 38231.50 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 49574.3  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 12  
-----  
>>>>CLEAR MEMORY BANK # 2 <<<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12601.00 TO NODE 12602.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 325.00 DOWNSTREAM (FEET) = 313.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1377.46 CHANNEL SLOPE = 0.0087  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 8.51  
CHANNEL FLOW THRU SUBAREA (CFS) = 35585.12  
FLOW VELOCITY (FEET/SEC.) = 17.24 FLOW DEPTH (FEET) = 8.51  
TRAVEL TIME (MIN.) = 1.33 Tc (MIN.) = 87.79  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12602.00 = 101245.91 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12602.00 TO NODE 12603.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 313.00 DOWNSTREAM (FEET) = 310.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 312.40 CHANNEL SLOPE = 0.0096  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 8.28  
CHANNEL FLOW THRU SUBAREA (CFS) = 35585.12  
FLOW VELOCITY (FEET/SEC.) = 17.80 FLOW DEPTH (FEET) = 8.28  
TRAVEL TIME (MIN.) = 0.29 Tc (MIN.) = 88.08  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.30 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 0610403X.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	322.28	18.95	2.336	0.30 ( 0.29)	0.97	175.0	40300.00
TOTAL AREA (ACRES) =							175.0

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21386.24	18.51	2.375	0.30 ( 0.30)	0.99	5462.0	600.00
2	22011.23	20.30	2.224	0.30 ( 0.30)	0.99	6052.6	40200.00
3	25763.12	34.48	1.621	0.30 ( 0.30)	0.99	11250.3	40100.00
4	27562.95	44.02	1.408	0.30 ( 0.30)	0.99	14561.2	11801.00
5	29796.73	55.26	1.258	0.30 ( 0.30)	0.99	19145.0	11530.00
6	30920.15	59.84	1.213	0.30 ( 0.30)	0.99	21459.3	11701.00
7	31860.27	63.46	1.188	0.30 ( 0.30)	0.99	23531.2	11910.00
8	34672.54	74.13	1.115	0.30 ( 0.30)	0.99	30244.9	10800.00
9	35424.77	78.48	1.086	0.30 ( 0.30)	0.99	33190.3	11130.00
10	35585.12	88.08	1.021	0.30 ( 0.30)	0.99	38231.5	12410.00
11	35504.72	90.95	1.004	0.30 ( 0.30)	0.99	39610.2	10600.00
12	35396.09	96.31	0.980	0.30 ( 0.30)	0.99	41970.6	11201.00
13	35160.16	101.22	0.959	0.30 ( 0.30)	0.99	43702.3	12201.00
14	34894.82	103.95	0.947	0.30 ( 0.30)	0.99	44491.4	10410.00
15	34361.55	108.12	0.929	0.30 ( 0.30)	0.99	45559.5	12231.00
16	33997.53	110.94	0.917	0.30 ( 0.30)	0.99	46232.8	12101.10
17	33280.08	115.69	0.896	0.30 ( 0.30)	0.99	47193.8	10400.00
18	32131.13	123.38	0.870	0.30 ( 0.30)	0.99	48488.9	12010.00
19	31089.61	129.10	0.859	0.30 ( 0.30)	0.99	48835.8	10210.00
20	30639.86	132.05	0.853	0.30 ( 0.30)	0.99	48953.0	12000.00
21	27602.46	156.38	0.804	0.30 ( 0.30)	0.99	49574.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.30 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	322.28	18.95	2.336	0.30 ( 0.29)	0.97	175.0	40300.00

LONGEST FLOWPATH FROM NODE 40300.00 TO NODE 12603.00 = 5256.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21707.06	18.51	2.375	0.30 ( 0.30)	0.99	5633.0	600.00
2	21861.23	18.95	2.336	0.30 ( 0.30)	0.99	5781.4	40300.00
3	22315.85	20.30	2.224	0.30 ( 0.30)	0.99	6227.7	40200.00
4	25972.91	34.48	1.621	0.30 ( 0.30)	0.99	11425.4	40100.00
5	27739.10	44.02	1.408	0.30 ( 0.30)	0.99	14736.3	11801.00
6	29949.33	55.26	1.258	0.30 ( 0.30)	0.99	19320.0	11530.00
7	31065.55	59.84	1.213	0.30 ( 0.30)	0.99	21634.3	11701.00
8	32001.72	63.46	1.188	0.30 ( 0.30)	0.99	23706.3	11910.00
9	34802.62	74.13	1.115	0.30 ( 0.30)	0.99	30420.0	10800.00

10	35550.21	78.48	1.086	0.30	( 0.30)	0.99	33365.4	11130.00
11	35700.34	88.08	1.021	0.30	( 0.30)	0.99	38406.6	12410.00
12	35617.23	90.95	1.004	0.30	( 0.30)	0.99	39785.2	10600.00
13	35504.92	96.31	0.980	0.30	( 0.30)	0.99	42145.7	11201.00
14	35265.61	101.22	0.959	0.30	( 0.30)	0.99	43877.4	12201.00
15	34998.40	103.95	0.947	0.30	( 0.30)	0.99	44666.5	10410.00
16	34462.26	108.12	0.929	0.30	( 0.30)	0.99	45734.5	12231.00
17	34096.29	110.94	0.917	0.30	( 0.30)	0.99	46407.8	12101.10
18	33375.58	115.69	0.896	0.30	( 0.30)	0.99	47368.8	10400.00
19	32222.61	123.38	0.870	0.30	( 0.30)	0.99	48663.9	12010.00
20	31179.28	129.10	0.859	0.30	( 0.30)	0.99	49010.9	10210.00
21	30728.60	132.05	0.853	0.30	( 0.30)	0.99	49128.1	12000.00
22	27683.54	156.38	0.804	0.30	( 0.30)	0.99	49749.3	10100.00
TOTAL AREA (ACRES) =		49749.3						

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 35700.34 Tc (MIN.) = 88.082  
EFFECTIVE AREA (ACRES) = 38406.55 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 49749.3  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.30 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 88.08  
\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.021  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.20	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	8.80	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL, NARROWLEAF"	B	0.10	0.30	1.000	72
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.60	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	0.60	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL, NARROWLEAF"	B	2.90	0.30	1.000	72

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 14.20 SUBAREA RUNOFF (CFS) = 9.21  
EFFECTIVE AREA (ACRES) = 38420.75 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 49763.5 PEAK FLOW RATE (CFS) = 35700.34  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 88.08  
\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.021  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	0.30	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.90	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.10	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL, NARROWLEAF"	B	0.70	0.30	1.000	72
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.10	0.30	1.000	66
PUBLIC PARK	B	0.70	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.978  
SUBAREA AREA (ACRES) = 4.80 SUBAREA RUNOFF (CFS) = 3.14  
EFFECTIVE AREA (ACRES) = 38425.55 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 49768.3 PEAK FLOW RATE (CFS) = 35700.34  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 88.08  
\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.021  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	0.20	0.30	0.850	56
RESIDENTIAL					
"11+ DWELLINGS/ACRE"	B	0.10	0.30	0.200	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	1.40	0.30	0.900	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	1.00	0.30	0.900	56
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.30	0.30	1.000	65
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	5.70	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.960  
SUBAREA AREA (ACRES) = 8.70 SUBAREA RUNOFF (CFS) = 5.74  
EFFECTIVE AREA (ACRES) = 38434.25 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 49777.0 PEAK FLOW RATE (CFS) = 35700.34  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

*****
FLOW PROCESS FROM NODE 12603.00 TO NODE 12604.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 310.00 DOWNSTREAM(FEET) = 307.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 459.69 CHANNEL SLOPE = 0.0065
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 9.26
CHANNEL FLOW THRU SUBAREA(CFS) = 35700.34
FLOW VELOCITY(FEET/SEC.) = 15.66 FLOW DEPTH(FEET) = 9.26
TRAVEL TIME(MIN.) = 0.49 Tc(MIN.) = 88.57
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12604.00 = 102017.99 FEET.

```

```

*****
FLOW PROCESS FROM NODE 12604.00 TO NODE 12604.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====

```

```

MAINLINE Tc(MIN.) = 88.57
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.018
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/    SCS SOIL  AREA    Fp      Ap    SCS
LAND USE             GROUP  (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"CHAPARRAL,NARROWLEAF"  B      0.10   0.30   1.000  72
NATURAL FAIR COVER
"OPEN BRUSH"           B      0.90   0.30   1.000  66
PUBLIC PARK            B      0.10   0.30   0.850  56
NATURAL FAIR COVER
"WOODLAND,GRASS"      B      0.70   0.30   1.000  65
NATURAL FAIR COVER
"WOODLAND,GRASS"      B      0.50   0.30   1.000  65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.993
SUBAREA AREA(ACRES) = 2.30 SUBAREA RUNOFF(CFS) = 1.49
EFFECTIVE AREA(ACRES) = 38436.55 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 49779.3 PEAK FLOW RATE(CFS) = 35700.34
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 12604.00 TO NODE 12605.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====

```

```

ELEVATION DATA: UPSTREAM(FEET) = 307.00 DOWNSTREAM(FEET) = 305.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 427.54 CHANNEL SLOPE = 0.0047
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 10.17
CHANNEL FLOW THRU SUBAREA(CFS) = 35700.34
FLOW VELOCITY(FEET/SEC.) = 14.00 FLOW DEPTH(FEET) = 10.17
TRAVEL TIME(MIN.) = 0.51 Tc(MIN.) = 89.08
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.00 = 102445.53 FEET.

```

```

*****
FLOW PROCESS FROM NODE 12605.00 TO NODE 12605.30 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 305.00 DOWNSTREAM(FEET) = 302.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 217.28 CHANNEL SLOPE = 0.0138
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 7.47
CHANNEL FLOW THRU SUBAREA(CFS) = 35700.34
FLOW VELOCITY(FEET/SEC.) = 20.12 FLOW DEPTH(FEET) = 7.47
TRAVEL TIME(MIN.) = 0.18 Tc(MIN.) = 89.26
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.30 = 102662.81 FEET.

```

```

*****
FLOW PROCESS FROM NODE 12605.30 TO NODE 12605.30 IS CODE = 15.1
-----
>>>>DEFINE MEMORY BANK # 3 <<<<
=====

```

```

PEAK FLOWRATE TABLE FILE NAME: 0610404X.DNA
MEMORY BANK # 3 DEFINED AS FOLLOWS:
STREAM  Q      Tc      Fp(Fm)  Ap    Ae    HEADWATER
NUMBER  (CFS)  (MIN.) (INCH/HR) (DECIMAL) (ACRES)  NODE
1       762.60  17.82  0.30( 0.30) 0.99  396.2  40430.00
2       753.57  18.38  0.30( 0.30) 0.99  400.8  40440.00
3       731.89  19.53  0.30( 0.30) 0.99  409.4  40400.00
4       727.71  19.70  0.30( 0.30) 0.99  410.2  40420.00
5       726.10  19.76  0.30( 0.30) 0.99  410.5  40410.00
TOTAL AREA(ACRES) = 410.5

```

```

*****
FLOW PROCESS FROM NODE 12605.30 TO NODE 12605.30 IS CODE = 11
-----
>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<
=====

```

```

** MAIN STREAM CONFLUENCE DATA **
STREAM  Q      Tc      Intensity  Fp(Fm)  Ap    Ae    HEADWATER
NUMBER  (CFS)  (MIN.) (INCH/HR) (INCH/HR) (DECIMAL) (ACRES)  NODE
1       21707.06  19.90  2.251  0.30( 0.30) 0.99  5663.0  600.00
2       21861.23  20.34  2.221  0.30( 0.30) 0.99  5811.4  40300.00
3       22315.85  21.68  2.139  0.30( 0.30) 0.99  6257.7  40200.00
4       25972.91  35.79  1.586  0.30( 0.30) 0.99  11455.4  40100.00
5       27739.10  45.30  1.387  0.30( 0.30) 0.99  14766.3  11801.00
6       29949.33  56.51  1.246  0.30( 0.30) 0.99  19350.0  11530.00
7       31065.55  61.07  1.204  0.30( 0.30) 0.99  21664.3  11701.00
8       32001.72  64.68  1.179  0.30( 0.30) 0.99  23736.3  11910.00
9       34802.62  75.31  1.107  0.30( 0.30) 0.99  30450.0  10800.00
10      35550.21  79.66  1.078  0.30( 0.30) 0.99  33395.4  11130.00
11      35700.34  89.26  1.013  0.30( 0.30) 0.99  38436.6  12410.00
12      35617.23  92.13  0.999  0.30( 0.30) 0.99  39815.2  10600.00
13      35504.92  97.49  0.975  0.30( 0.30) 0.99  42175.7  11201.00
14      35265.61  102.41  0.954  0.30( 0.30) 0.99  43907.4  12201.00
15      34998.40  105.13  0.942  0.30( 0.30) 0.99  44696.5  10410.00
16      34462.26  109.31  0.924  0.30( 0.30) 0.99  45764.5  12231.00

```

```

17 34096.29 112.14 0.911 0.30( 0.30) 0.99 46437.8 12101.10
18 33375.58 116.90 0.891 0.30( 0.30) 0.99 47398.8 10400.00
19 32222.61 124.60 0.868 0.30( 0.30) 0.99 48693.9 12010.00
20 31179.28 130.33 0.856 0.30( 0.30) 0.99 49040.9 10210.00
21 30728.60 133.28 0.850 0.30( 0.30) 0.99 49158.1 12000.00
22 27683.54 157.66 0.802 0.30( 0.30) 0.99 49779.3 10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.30 = 102662.81 FEET.

```

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	762.60	17.82	2.436	0.30( 0.30)	0.99	396.2	40430.00
2	753.57	18.38	2.387	0.30( 0.30)	0.99	400.8	40440.00
3	731.89	19.53	2.284	0.30( 0.30)	0.99	409.4	40400.00
4	727.71	19.70	2.269	0.30( 0.30)	0.99	410.2	40420.00
5	726.10	19.76	2.263	0.30( 0.30)	0.99	410.5	40410.00

LONGEST FLOWPATH FROM NODE 40400.00 TO NODE 12605.30 = 7428.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22041.36	17.82	2.436	0.30( 0.30)	0.99	5465.7	40430.00
2	22189.77	18.38	2.387	0.30( 0.30)	0.99	5629.7	40440.00
3	22393.69	19.53	2.284	0.30( 0.30)	0.99	5965.4	40400.00
4	22412.19	19.70	2.269	0.30( 0.30)	0.99	6015.7	40420.00
5	22417.77	19.76	2.263	0.30( 0.30)	0.99	6033.2	40410.00
6	22428.51	19.90	2.251	0.30( 0.30)	0.99	6073.5	600.00
7	22571.84	20.34	2.221	0.30( 0.30)	0.99	6221.8	40300.00
8	22996.01	21.68	2.139	0.30( 0.30)	0.99	6668.1	40200.00
9	26448.94	35.79	1.586	0.30( 0.30)	0.99	11865.8	40100.00
10	28141.58	45.30	1.387	0.30( 0.30)	0.99	15176.7	11801.00
11	30299.67	56.51	1.246	0.30( 0.30)	0.99	19760.5	11530.00
12	31400.32	61.07	1.204	0.30( 0.30)	0.99	22074.8	11701.00
13	32327.46	64.68	1.179	0.30( 0.30)	0.99	24146.7	11910.00
14	35101.80	75.31	1.107	0.30( 0.30)	0.99	30860.5	10800.00
15	35838.53	79.66	1.078	0.30( 0.30)	0.99	33805.8	11130.00
16	35964.66	89.26	1.013	0.30( 0.30)	0.99	38847.0	12410.00
17	35876.27	92.13	0.999	0.30( 0.30)	0.99	40225.7	10600.00
18	35755.31	97.49	0.975	0.30( 0.30)	0.99	42586.1	11201.00
19	35508.07	102.41	0.954	0.30( 0.30)	0.99	44317.8	12201.00
20	35236.47	105.13	0.942	0.30( 0.30)	0.99	45107.0	10410.00
21	34693.59	109.31	0.924	0.30( 0.30)	0.99	46175.0	12231.00
22	34323.07	112.14	0.911	0.30( 0.30)	0.99	46848.3	12101.10
23	33594.68	116.90	0.891	0.30( 0.30)	0.99	47809.3	10400.00
24	32433.31	124.60	0.868	0.30( 0.30)	0.99	49104.4	12010.00
25	31385.74	130.33	0.856	0.30( 0.30)	0.99	49451.3	10210.00
26	30932.88	133.28	0.850	0.30( 0.30)	0.99	49568.5	12000.00
27	27869.81	157.66	0.802	0.30( 0.30)	0.99	50189.8	10100.00

TOTAL AREA (ACRES) = 50189.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 35964.66 Tc(MIN.) = 89.260  
EFFECTIVE AREA(ACRES) = 38847.01 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA(ACRES) = 50189.8  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.30 = 102662.81 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.30 TO NODE 12605.30 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.30 TO NODE 12605.60 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 302.00 DOWNSTREAM(FEET) = 295.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 738.76 CHANNEL SLOPE = 0.0095  
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 8.36  
CHANNEL FLOW THRU SUBAREA(CFS) = 35964.66  
FLOW VELOCITY(FEET/SEC.) = 17.79 FLOW DEPTH(FEET) = 8.36  
TRAVEL TIME(MIN.) = 0.69 Tc(MIN.) = 89.95  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.60 = 103401.57 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.60 TO NODE 12605.60 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610405X.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	178.01	13.93	0.30( 0.30)	1.00	77.1	40510.00
2	172.23	15.40	0.30( 0.30)	1.00	81.4	40500.00

TOTAL AREA(ACRES) = 81.4

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.60 TO NODE 12605.60 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22041.36	18.63	2.364	0.30( 0.30)	0.99	5465.7	40430.00
2	22189.77	19.19	2.314	0.30( 0.30)	0.99	5629.7	40440.00
3	22393.69	20.34	2.221	0.30( 0.30)	0.99	5965.4	40400.00
4	22412.19	20.51	2.211	0.30( 0.30)	0.99	6015.7	40420.00
5	22417.77	20.57	2.207	0.30( 0.30)	0.99	6033.2	40410.00
6	22428.51	20.71	2.198	0.30( 0.30)	0.99	6073.5	600.00
7	22571.84	21.14	2.172	0.30( 0.30)	0.99	6221.8	40300.00
8	22996.01	22.48	2.090	0.30( 0.30)	0.99	6668.1	40200.00
9	26448.94	36.56	1.566	0.30( 0.30)	0.99	11865.8	40100.00
10	28141.58	46.05	1.375	0.30( 0.30)	0.99	15176.7	11801.00
11	30299.67	57.24	1.239	0.30( 0.30)	0.99	19760.5	11530.00
12	31400.32	61.80	1.199	0.30( 0.30)	0.99	22074.8	11701.00
13	32327.46	65.40	1.174	0.30( 0.30)	0.99	24146.7	11910.00
14	35101.80	76.01	1.103	0.30( 0.30)	0.99	30860.5	10800.00
15	35838.53	80.35	1.073	0.30( 0.30)	0.99	33805.8	11130.00

16	35964.66	89.95	1.008	0.30	( 0.30)	0.99	38847.0	12410.00
17	35876.27	92.82	0.996	0.30	( 0.30)	0.99	40225.7	10600.00
18	35755.31	98.19	0.972	0.30	( 0.30)	0.99	42586.1	11201.00
19	35508.07	103.10	0.951	0.30	( 0.30)	0.99	44317.8	12201.00
20	35236.47	105.83	0.939	0.30	( 0.30)	0.99	45107.0	10410.00
21	34693.59	110.01	0.921	0.30	( 0.30)	0.99	46175.0	12231.00
22	34323.07	112.84	0.908	0.30	( 0.30)	0.99	46848.3	12101.10
23	33594.68	117.61	0.887	0.30	( 0.30)	0.99	47809.3	10400.00
24	32433.31	125.31	0.866	0.30	( 0.30)	0.99	49104.4	12010.00
25	31385.74	131.06	0.855	0.30	( 0.30)	0.99	49451.3	10210.00
26	30932.88	134.01	0.849	0.30	( 0.30)	0.99	49568.5	12000.00
27	27869.81	158.41	0.800	0.30	( 0.30)	0.99	50189.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.60 = 103401.57 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	178.01	13.93	2.866	0.30 ( 0.30)	1.00	77.1	40510.00
2	172.23	15.40	2.651	0.30 ( 0.30)	1.00	81.4	40500.00

LONGEST FLOWPATH FROM NODE 40500.00 TO NODE 12605.60 = 4091.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20655.75	13.93	2.866	0.30 ( 0.30)	0.99	4162.2	40510.00
2	20926.83	15.40	2.651	0.30 ( 0.30)	0.99	4599.3	40500.00
3	22192.53	18.63	2.364	0.30 ( 0.30)	0.99	5547.1	40430.00
4	22337.31	19.19	2.314	0.30 ( 0.30)	0.99	5711.1	40440.00
5	22534.43	20.34	2.221	0.30 ( 0.30)	0.99	6046.8	40400.00
6	22552.15	20.51	2.211	0.30 ( 0.30)	0.99	6097.1	40420.00
7	22557.45	20.57	2.207	0.30 ( 0.30)	0.99	6114.5	40410.00
8	22567.56	20.71	2.198	0.30 ( 0.30)	0.99	6154.8	600.00
9	22708.95	21.14	2.172	0.30 ( 0.30)	0.99	6303.2	40300.00
10	23127.10	22.48	2.090	0.30 ( 0.30)	0.99	6749.5	40200.00
11	26541.66	36.56	1.566	0.30 ( 0.30)	0.99	11947.2	40100.00
12	28220.35	46.05	1.375	0.30 ( 0.30)	0.99	15258.1	11801.00
13	30368.45	57.24	1.239	0.30 ( 0.30)	0.99	19841.9	11530.00
14	31466.19	61.80	1.199	0.30 ( 0.30)	0.99	22156.1	11701.00
15	32391.55	65.40	1.174	0.30 ( 0.30)	0.99	24228.1	11910.00
16	35160.62	76.01	1.103	0.30 ( 0.30)	0.99	30941.8	10800.00
17	35895.21	80.35	1.073	0.30 ( 0.30)	0.99	33887.2	11130.00
18	36016.58	89.95	1.008	0.30 ( 0.30)	0.99	38928.4	12410.00
19	35927.27	92.82	0.996	0.30 ( 0.30)	0.99	40307.1	10600.00
20	35804.59	98.19	0.972	0.30 ( 0.30)	0.99	42667.5	11201.00
21	35555.78	103.10	0.951	0.30 ( 0.30)	0.99	44399.2	12201.00
22	35283.31	105.83	0.939	0.30 ( 0.30)	0.99	45188.3	10410.00
23	34739.09	110.01	0.921	0.30 ( 0.30)	0.99	46256.4	12231.00
24	34367.66	112.84	0.908	0.30 ( 0.30)	0.99	46929.6	12101.10
25	33637.75	117.61	0.887	0.30 ( 0.30)	0.99	47890.6	10400.00
26	32474.83	125.31	0.866	0.30 ( 0.30)	0.99	49185.8	12010.00
27	31426.43	131.06	0.855	0.30 ( 0.30)	0.99	49532.7	10210.00
28	30973.14	134.01	0.849	0.30 ( 0.30)	0.99	49649.9	12000.00
29	27906.49	158.41	0.800	0.30 ( 0.30)	0.99	50271.2	10100.00

TOTAL AREA (ACRES) = 50271.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 36016.58 Tc (MIN.) = 89.952  
EFFECTIVE AREA (ACRES) = 38928.39 AREA-AVERAGED Fm (INCH/HR) = 0.30

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 50271.2  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.60 = 103401.57 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.60 TO NODE 12605.60 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.60 TO NODE 12606.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 295.00 DOWNSTREAM (FEET) = 286.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1203.43 CHANNEL SLOPE = 0.0075  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT (FEET) = 8.95  
CHANNEL FLOW THRU SUBAREA (CFS) = 36016.58  
FLOW VELOCITY (FEET/SEC.) = 16.44 FLOW DEPTH (FEET) = 8.95  
TRAVEL TIME (MIN.) = 1.22 Tc (MIN.) = 91.17  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104605.00 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610406X.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	232.91	20.42	0.30 ( 0.30)	0.99	135.0	40600.00

TOTAL AREA (ACRES) = 135.0

\*\*\*\*\*

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20655.75	15.40	2.652	0.30 ( 0.30)	0.99	4162.2	40510.00
2	20926.83	16.86	2.521	0.30 ( 0.30)	0.99	4599.3	40500.00
3	22192.53	20.07	2.238	0.30 ( 0.30)	0.99	5547.1	40430.00
4	22337.31	20.62	2.204	0.30 ( 0.30)	0.99	5711.1	40440.00
5	22534.43	21.77	2.134	0.30 ( 0.30)	0.99	6046.8	40400.00
6	22552.15	21.94	2.123	0.30 ( 0.30)	0.99	6097.1	40420.00
7	22557.45	22.00	2.119	0.30 ( 0.30)	0.99	6114.5	40410.00
8	22567.56	22.14	2.111	0.30 ( 0.30)	0.99	6154.8	600.00
9	22708.95	22.57	2.084	0.30 ( 0.30)	0.99	6303.2	40300.00
10	23127.10	23.90	2.003	0.30 ( 0.30)	0.99	6749.5	40200.00
11	26541.66	37.91	1.529	0.30 ( 0.30)	0.99	11947.2	40100.00

12	28220.35	47.38	1.354	0.30	( 0.30)	0.99	15258.1	11801.00
13	30368.45	58.53	1.226	0.30	( 0.30)	0.99	19841.9	11530.00
14	31466.19	63.07	1.190	0.30	( 0.30)	0.99	22156.1	11701.00
15	32391.55	66.66	1.166	0.30	( 0.30)	0.99	24228.1	11910.00
16	35160.62	77.24	1.094	0.30	( 0.30)	0.99	30941.8	10800.00
17	35895.21	81.57	1.065	0.30	( 0.30)	0.99	33887.2	11130.00
18	36016.58	91.17	1.003	0.30	( 0.30)	0.99	38928.4	12410.00
19	35927.27	94.04	0.990	0.30	( 0.30)	0.99	40307.1	10600.00
20	35804.59	99.41	0.967	0.30	( 0.30)	0.99	42667.5	11201.00
21	35555.78	104.33	0.945	0.30	( 0.30)	0.99	44399.2	12201.00
22	35283.31	107.06	0.934	0.30	( 0.30)	0.99	45188.3	10410.00
23	34739.09	111.24	0.915	0.30	( 0.30)	0.99	46256.4	12231.00
24	34367.66	114.08	0.903	0.30	( 0.30)	0.99	46929.6	12101.10
25	33637.75	118.85	0.882	0.30	( 0.30)	0.99	47890.6	10400.00
26	32474.83	126.57	0.864	0.30	( 0.30)	0.99	49185.8	12010.00
27	31426.43	132.33	0.852	0.30	( 0.30)	0.99	49532.7	10210.00
28	30973.14	135.29	0.846	0.30	( 0.30)	0.99	49649.9	12000.00
29	27906.49	159.74	0.798	0.30	( 0.30)	0.99	50271.2	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104605.00 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	232.91	20.42	2.216	0.30 ( 0.30)	0.99	135.0	40600.00

LONGEST FLOWPATH FROM NODE 40600.00 TO NODE 12606.00 = 6107.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20871.24	15.40	2.652	0.30 ( 0.30)	0.99	4263.9	40510.00
2	21149.77	16.86	2.521	0.30 ( 0.30)	0.99	4710.7	40500.00
3	22424.00	20.07	2.238	0.30 ( 0.30)	0.99	5679.7	40430.00
4	22517.37	20.42	2.216	0.30 ( 0.30)	0.99	5786.2	40600.00
5	22568.71	20.62	2.204	0.30 ( 0.30)	0.99	5846.1	40440.00
6	22757.30	21.77	2.134	0.30 ( 0.30)	0.99	6181.8	40400.00
7	22773.74	21.94	2.123	0.30 ( 0.30)	0.99	6232.1	40420.00
8	22778.59	22.00	2.119	0.30 ( 0.30)	0.99	6249.5	40410.00
9	22787.65	22.14	2.111	0.30 ( 0.30)	0.99	6289.8	600.00
10	22925.83	22.57	2.084	0.30 ( 0.30)	0.99	6438.2	40300.00
11	23334.08	23.90	2.003	0.30 ( 0.30)	0.99	6884.5	40200.00
12	26691.14	37.91	1.529	0.30 ( 0.30)	0.99	12082.2	40100.00
13	28348.48	47.38	1.354	0.30 ( 0.30)	0.99	15393.1	11801.00
14	30481.06	58.53	1.226	0.30 ( 0.30)	0.99	19976.8	11530.00
15	31574.49	63.07	1.190	0.30 ( 0.30)	0.99	22291.1	11701.00
16	32496.90	66.66	1.166	0.30 ( 0.30)	0.99	24363.1	11910.00
17	35257.29	77.24	1.094	0.30 ( 0.30)	0.99	31076.8	10800.00
18	35988.31	81.57	1.065	0.30 ( 0.30)	0.99	34022.2	11130.00
19	36102.13	91.17	1.003	0.30 ( 0.30)	0.99	39063.4	12410.00
20	36011.30	94.04	0.990	0.30 ( 0.30)	0.99	40442.1	10600.00
21	35885.78	99.41	0.967	0.30 ( 0.30)	0.99	42802.5	11201.00
22	35634.36	104.33	0.945	0.30 ( 0.30)	0.99	44534.2	12201.00
23	35360.44	107.06	0.934	0.30 ( 0.30)	0.99	45323.3	10410.00
24	34814.00	111.24	0.915	0.30 ( 0.30)	0.99	46391.3	12231.00
25	34441.07	114.08	0.903	0.30 ( 0.30)	0.99	47064.6	12101.10
26	33708.62	118.85	0.882	0.30 ( 0.30)	0.99	48025.6	10400.00
27	32543.50	126.57	0.864	0.30 ( 0.30)	0.99	49320.7	12010.00
28	31493.70	132.33	0.852	0.30 ( 0.30)	0.99	49667.7	10210.00
29	31039.69	135.29	0.846	0.30 ( 0.30)	0.99	49784.9	12000.00
30	27967.11	159.74	0.798	0.30 ( 0.30)	0.99	50406.1	10100.00

30	27967.11	159.74	0.798	0.30	( 0.30)	0.99	50406.1	10100.00
----	----------	--------	-------	------	---------	------	---------	----------

TOTAL AREA (ACRES) = 50406.1

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 36102.13 Tc(MIN.) = 91.172  
EFFECTIVE AREA(ACRES) = 39063.36 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA(ACRES) = 50406.1  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104605.00 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 50406.1 TC(MIN.) = 91.17  
EFFECTIVE AREA(ACRES) = 39063.36 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.994  
PEAK FLOW RATE(CFS) = 36102.13

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20871.24	15.40	2.652	0.30 ( 0.30)	0.99	4263.9	40510.00
2	21149.77	16.86	2.521	0.30 ( 0.30)	0.99	4710.7	40500.00
3	22424.00	20.07	2.238	0.30 ( 0.30)	0.99	5679.7	40430.00
4	22517.37	20.42	2.216	0.30 ( 0.30)	0.99	5786.2	40600.00
5	22568.71	20.62	2.204	0.30 ( 0.30)	0.99	5846.1	40440.00
6	22757.30	21.77	2.134	0.30 ( 0.30)	0.99	6181.8	40400.00
7	22773.74	21.94	2.123	0.30 ( 0.30)	0.99	6232.1	40420.00
8	22778.59	22.00	2.119	0.30 ( 0.30)	0.99	6249.5	40410.00
9	22787.65	22.14	2.111	0.30 ( 0.30)	0.99	6289.8	600.00
10	22925.83	22.57	2.084	0.30 ( 0.30)	0.99	6438.2	40300.00
11	23334.08	23.90	2.003	0.30 ( 0.30)	0.99	6884.5	40200.00
12	26691.14	37.91	1.529	0.30 ( 0.30)	0.99	12082.2	40100.00
13	28348.48	47.38	1.354	0.30 ( 0.30)	0.99	15393.1	11801.00
14	30481.06	58.53	1.226	0.30 ( 0.30)	0.99	19976.8	11530.00
15	31574.49	63.07	1.190	0.30 ( 0.30)	0.99	22291.1	11701.00
16	32496.90	66.66	1.166	0.30 ( 0.30)	0.99	24363.1	11910.00
17	35257.29	77.24	1.094	0.30 ( 0.30)	0.99	31076.8	10800.00
18	35988.31	81.57	1.065	0.30 ( 0.30)	0.99	34022.2	11130.00
19	36102.13	91.17	1.003	0.30 ( 0.30)	0.99	39063.4	12410.00
20	36011.30	94.04	0.990	0.30 ( 0.30)	0.99	40442.1	10600.00
21	35885.78	99.41	0.967	0.30 ( 0.30)	0.99	42802.5	11201.00
22	35634.36	104.33	0.945	0.30 ( 0.30)	0.99	44534.2	12201.00
23	35360.44	107.06	0.934	0.30 ( 0.30)	0.99	45323.3	10410.00
24	34814.00	111.24	0.915	0.30 ( 0.30)	0.99	46391.3	12231.00
25	34441.07	114.08	0.903	0.30 ( 0.30)	0.99	47064.6	12101.10
26	33708.62	118.85	0.882	0.30 ( 0.30)	0.99	48025.6	10400.00
27	32543.50	126.57	0.864	0.30 ( 0.30)	0.99	49320.7	12010.00
28	31493.70	132.33	0.852	0.30 ( 0.30)	0.99	49667.7	10210.00
29	31039.69	135.29	0.846	0.30 ( 0.30)	0.99	49784.9	12000.00
30	27967.11	159.74	0.798	0.30 ( 0.30)	0.99	50406.1	10100.00

END OF RATIONAL METHOD ANALYSIS





\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S27- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 50-YR RM EV APRIL 2019 CCHIU \*  
\*\*\*\*\*

FILE NAME: RI50EV27.DAT  
TIME/DATE OF STUDY: 09:14 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 50.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.453
- 2) 10.00; 3.490
- 3) 15.00; 2.670
- 4) 20.00; 2.230
- 5) 25.00; 1.926
- 6) 30.00; 1.733
- 7) 40.00; 1.467
- 8) 50.00; 1.305
- 9) 60.00; 1.202
- 10) 90.00; 0.999
- 11) 120.00; 0.869
- 12) 180.00; 0.747
- 13) 360.00; 0.555
- 14) 1200.00; 0.244

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI50EV26.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21149.77	16.86	0.30 ( 0.30)	0.99	4710.7	40500.00
2	22568.71	20.62	0.30 ( 0.30)	0.99	5846.1	40440.00
3	23334.08	23.90	0.30 ( 0.30)	0.99	6884.5	40200.00
4	26691.14	37.91	0.30 ( 0.30)	0.99	12082.2	40100.00
5	28348.48	47.38	0.30 ( 0.30)	0.99	15393.1	11801.00
6	30481.06	58.53	0.30 ( 0.30)	0.99	19976.8	11530.00
7	31574.49	63.07	0.30 ( 0.30)	0.99	22291.1	11701.00
8	32496.90	66.66	0.30 ( 0.30)	0.99	24363.1	11910.00
9	35257.29	77.24	0.30 ( 0.30)	0.99	31076.8	10800.00
10	35988.31	81.57	0.30 ( 0.30)	0.99	34022.2	11130.00
11	36102.13	91.17	0.30 ( 0.30)	0.99	39063.4	12410.00
12	35885.78	99.41	0.30 ( 0.30)	0.99	42802.5	11201.00
13	35634.36	104.33	0.30 ( 0.30)	0.99	44534.2	12201.00
14	34814.00	111.24	0.30 ( 0.30)	0.99	46391.3	12231.00
15	34441.07	114.08	0.30 ( 0.30)	0.99	47064.6	12101.10
16	33708.62	118.85	0.30 ( 0.30)	0.99	48025.6	10400.00
17	32543.50	126.57	0.30 ( 0.30)	0.99	49320.7	12010.00
18	31493.70	132.33	0.30 ( 0.30)	0.99	49667.7	10210.00
19	31039.69	135.29	0.30 ( 0.30)	0.99	49784.9	12000.00
20	27967.11	159.74	0.30 ( 0.30)	0.99	50406.1	10100.00
TOTAL AREA (ACRES) =						50406.1

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21149.77	16.86	0.30 ( 0.30)	0.99	4710.7	40500.00
2	22568.71	20.62	0.30 ( 0.30)	0.99	5846.1	40440.00
3	23334.08	23.90	0.30 ( 0.30)	0.99	6884.5	40200.00
4	26691.14	37.91	0.30 ( 0.30)	0.99	12082.2	40100.00
5	28348.48	47.38	0.30 ( 0.30)	0.99	15393.1	11801.00
6	30481.06	58.53	0.30 ( 0.30)	0.99	19976.8	11530.00
7	31574.49	63.07	0.30 ( 0.30)	0.99	22291.1	11701.00
8	32496.90	66.66	0.30 ( 0.30)	0.99	24363.1	11910.00
9	35257.29	77.24	0.30 ( 0.30)	0.99	31076.8	10800.00
10	35988.31	81.57	0.30 ( 0.30)	0.99	34022.2	11130.00
11	36102.13	91.17	0.30 ( 0.30)	0.99	39063.4	12410.00
12	35885.78	99.41	0.30 ( 0.30)	0.99	42802.5	11201.00
13	35634.36	104.33	0.30 ( 0.30)	0.99	44534.2	12201.00

14	34814.00	111.24	0.30	( 0.30)	0.99	46391.3	12231.00
15	34441.07	114.08	0.30	( 0.30)	0.99	47064.6	12101.10
16	33708.62	118.85	0.30	( 0.30)	0.99	48025.6	10400.00
17	32543.50	126.57	0.30	( 0.30)	0.99	49320.7	12010.00
18	31493.70	132.33	0.30	( 0.30)	0.99	49667.7	10210.00
19	31039.69	135.29	0.30	( 0.30)	0.99	49784.9	12000.00
20	27967.11	159.74	0.30	( 0.30)	0.99	50406.1	10100.00

TOTAL AREA (ACRES) = 50406.1

\*\*\*\*\*

FLOW PROCESS FROM NODE 12606.00 TO NODE 12701.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 286.00 DOWNSTREAM (FEET) = 276.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1260.19 CHANNEL SLOPE = 0.0079  
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT (FEET) = 8.81

\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.988

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	7.55	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 36105.39

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 16.78

AVERAGE FLOW DEPTH (FEET) = 8.81 TRAVEL TIME (MIN.) = 1.25

Tc (MIN.) = 92.42

SUBAREA AREA (ACRES) = 7.55 SUBAREA RUNOFF (CFS) = 6.51

EFFECTIVE AREA (ACRES) = 39070.91 AREA-AVERAGED Fm (INCH/HR) = 0.30

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA (ACRES) = 50413.7 PEAK FLOW RATE (CFS) = 36102.13

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT (FEET) = 8.81

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 8.81 FLOW VELOCITY (FEET/SEC.) = 16.78

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12701.00 = 105865.19 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12701.00 TO NODE 12701.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 92.42

\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.988

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	0.90	0.30	0.850	56
NATURAL FAIR COVER "WOODLAND, GRASS"	B	3.40	0.30	1.000	65
RESIDENTIAL					

"5-7 DWELLINGS/ACRE"	B	0.40	0.30	0.500	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	23.00	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	3.30	0.30	1.000	66
NATURAL FAIR COVER					
"GRASS"	B	0.40	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.989

SUBAREA AREA (ACRES) = 31.40 SUBAREA RUNOFF (CFS) = 19.55

EFFECTIVE AREA (ACRES) = 39102.31 AREA-AVERAGED Fm (INCH/HR) = 0.30

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA (ACRES) = 50445.1 PEAK FLOW RATE (CFS) = 36102.13

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12701.00 TO NODE 12701.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 92.42

\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.988

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "WOODLAND, GRASS"	B	1.70	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 1.70 SUBAREA RUNOFF (CFS) = 1.05

EFFECTIVE AREA (ACRES) = 39104.01 AREA-AVERAGED Fm (INCH/HR) = 0.30

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA (ACRES) = 50446.8 PEAK FLOW RATE (CFS) = 36102.13

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12701.00 TO NODE 12720.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 276.00 DOWNSTREAM (FEET) = 275.00

CHANNEL LENGTH THRU SUBAREA (FEET) = 147.65 CHANNEL SLOPE = 0.0068

GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT (FEET) = 9.22

\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.988

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	1.49	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.850

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 36102.62

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 15.91

AVERAGE FLOW DEPTH (FEET) = 9.22 TRAVEL TIME (MIN.) = 0.15

Tc (MIN.) = 92.58

SUBAREA AREA (ACRES) = 1.49 SUBAREA RUNOFF (CFS) = 0.98

EFFECTIVE AREA(ACRES) = 39105.50 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA(ACRES) = 50448.3 PEAK FLOW RATE(CFS) = 36102.13  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 9.22

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 9.22 FLOW VELOCITY(FEET/SEC.) = 15.91  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.00 = 106012.84 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12701.00 TO NODE 12720.00 IS CODE = 1  
-----

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
TIME OF CONCENTRATION(MIN.) = 92.58  
RAINFALL INTENSITY(INCH/HR) = 0.99  
AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.99  
EFFECTIVE STREAM AREA(ACRES) = 39105.50  
TOTAL STREAM AREA(ACRES) = 50448.27  
PEAK FLOW RATE(CFS) AT CONFLUENCE = 36102.13

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12710.00 TO NODE 12711.00 IS CODE = 21  
-----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 943.56  
ELEVATION DATA: UPSTREAM(FEET) = 940.78 DOWNSTREAM(FEET) = 657.79

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 13.910  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.849  
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER						
"GRASS"	B	6.56	0.30	1.000	69	13.91

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA RUNOFF(CFS) = 15.05  
TOTAL AREA(ACRES) = 6.56 PEAK FLOW RATE(CFS) = 15.05

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12711.00 TO NODE 12712.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 657.79 DOWNSTREAM(FEET) = 585.63  
CHANNEL LENGTH THRU SUBAREA(FEET) = 766.00 CHANNEL SLOPE = 0.0942

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.72  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.559  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL FAIR COVER

"OPEN BRUSH"	B	26.94	0.30	1.000	66
--------------	---	-------	------	-------	----

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 42.49  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.42  
AVERAGE FLOW DEPTH(FEET) = 0.69 TRAVEL TIME(MIN.) = 2.36  
Tc(MIN.) = 16.27

SUBAREA AREA(ACRES) = 26.94 SUBAREA RUNOFF(CFS) = 54.76  
EFFECTIVE AREA(ACRES) = 33.50 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 33.5 PEAK FLOW RATE(CFS) = 68.09  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.91

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.91 FLOW VELOCITY(FEET/SEC.) = 6.32  
LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12712.00 = 1709.56 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12712.00 TO NODE 12713.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 585.63 DOWNSTREAM(FEET) = 463.75  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1025.79 CHANNEL SLOPE = 0.1188  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.95  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.353

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

COMMERCIAL	B	14.73	0.30	0.100	56
------------	---	-------	------	-------	----

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.100  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 83.50  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.33  
AVERAGE FLOW DEPTH(FEET) = 0.96 TRAVEL TIME(MIN.) = 2.33  
Tc(MIN.) = 18.60

SUBAREA AREA(ACRES) = 14.73 SUBAREA RUNOFF(CFS) = 30.80  
EFFECTIVE AREA(ACRES) = 48.23 AREA-AVERAGED Fm(INCH/HR) = 0.22  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.73  
TOTAL AREA(ACRES) = 48.2 PEAK FLOW RATE(CFS) = 92.70  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.01

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.01 FLOW VELOCITY(FEET/SEC.) = 7.62  
LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12713.00 = 2735.35 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12713.00 TO NODE 12714.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 463.75 DOWNSTREAM(FEET) = 360.30  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1148.54 CHANNEL SLOPE = 0.0901  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.67  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.182

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	105.64	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 195.00

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.73

AVERAGE FLOW DEPTH(FEET) = 1.67 TRAVEL TIME(MIN.) = 2.19

Tc(MIN.) = 20.79

SUBAREA AREA(ACRES) = 105.64 SUBAREA RUNOFF(CFS) = 204.58

EFFECTIVE AREA(ACRES) = 153.87 AREA-AVERAGED Fm(INCH/HR) = 0.09

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.30

TOTAL AREA(ACRES) = 153.9 PEAK FLOW RATE(CFS) = 289.85

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.08

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.08 FLOW VELOCITY(FEET/SEC.) = 9.85

LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12714.00 = 3883.89 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12714.00 TO NODE 12720.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 360.30 DOWNSTREAM(FEET) = 275.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1314.99 CHANNEL SLOPE = 0.0649  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.73

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.044

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	127.13	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 405.07

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.65

AVERAGE FLOW DEPTH(FEET) = 2.72 TRAVEL TIME(MIN.) = 2.27

Tc(MIN.) = 23.06

SUBAREA AREA(ACRES) = 127.13 SUBAREA RUNOFF(CFS) = 230.40

EFFECTIVE AREA(ACRES) = 281.00 AREA-AVERAGED Fm(INCH/HR) = 0.06

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.21

TOTAL AREA(ACRES) = 281.0 PEAK FLOW RATE(CFS) = 501.13

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 3.04

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 3.04 FLOW VELOCITY(FEET/SEC.) = 10.25

LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12720.00 = 5198.88 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

TOTAL NUMBER OF STREAMS = 2

CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:

TIME OF CONCENTRATION(MIN.) = 23.06

RAINFALL INTENSITY(INCH/HR) = 2.04

AREA-AVERAGED Fm(INCH/HR) = 0.06

AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.21

EFFECTIVE STREAM AREA(ACRES) = 281.00

TOTAL STREAM AREA(ACRES) = 281.00

PEAK FLOW RATE(CFS) AT CONFLUENCE = 501.13

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21149.77	18.55	2.358	0.30( 0.30)	0.99	4752.9	40500.00
1	22568.71	22.27	2.092	0.30( 0.30)	0.99	5888.2	40440.00
1	23334.08	25.52	1.906	0.30( 0.30)	0.99	6926.6	40200.00
1	26691.14	39.46	1.481	0.30( 0.30)	0.99	12124.3	40100.00
1	28348.48	48.90	1.323	0.30( 0.30)	0.99	15435.2	11801.00
1	30481.06	60.02	1.202	0.30( 0.30)	0.99	20019.0	11530.00
1	31574.49	64.54	1.171	0.30( 0.30)	0.99	22333.3	11701.00
1	32496.90	68.12	1.147	0.30( 0.30)	0.99	24405.2	11910.00
1	35257.29	78.66	1.076	0.30( 0.30)	0.99	31118.9	10800.00
1	35988.31	82.98	1.046	0.30( 0.30)	0.99	34064.3	11130.00
1	36102.13	92.58	0.988	0.30( 0.30)	0.99	39105.5	12410.00
1	35885.78	100.82	0.952	0.30( 0.30)	0.99	42844.6	11201.00
1	35634.36	105.74	0.931	0.30( 0.30)	0.99	44576.3	12201.00
1	34814.00	112.66	0.901	0.30( 0.30)	0.99	46433.5	12231.00
1	34441.07	115.51	0.888	0.30( 0.30)	0.99	47106.8	12101.10
1	33708.62	120.29	0.868	0.30( 0.30)	0.99	48067.8	10400.00
1	32543.50	128.03	0.853	0.30( 0.30)	0.99	49362.9	12010.00
1	31493.70	133.81	0.841	0.30( 0.30)	0.99	49709.8	10210.00
1	31039.69	136.77	0.835	0.30( 0.30)	0.99	49827.0	12000.00
1	27967.11	161.27	0.785	0.30( 0.30)	0.99	50448.3	10100.00
2	501.13	23.06	2.044	0.30( 0.06)	0.21	281.0	12710.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO

CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21616.64	18.55	2.358	0.30 ( 0.29)	0.95	4978.9	40500.00
2	23064.34	22.27	2.092	0.30 ( 0.29)	0.96	6159.5	40440.00
3	23257.19	23.06	2.044	0.30 ( 0.29)	0.96	6423.4	12710.00
4	23800.32	25.52	1.906	0.30 ( 0.29)	0.96	7207.6	40200.00
5	27050.03	39.46	1.481	0.30 ( 0.29)	0.97	12405.3	40100.00
6	28667.30	48.90	1.323	0.30 ( 0.29)	0.98	15716.2	11801.00
7	30769.28	60.02	1.202	0.30 ( 0.29)	0.98	20300.0	11530.00
8	31854.98	64.54	1.171	0.30 ( 0.29)	0.98	22614.3	11701.00
9	32771.27	68.12	1.147	0.30 ( 0.30)	0.98	24686.2	11910.00
10	35513.61	78.66	1.076	0.30 ( 0.30)	0.99	31399.9	10800.00
11	36237.24	82.98	1.046	0.30 ( 0.30)	0.99	34345.3	11130.00
12	36336.23	92.58	0.988	0.30 ( 0.30)	0.99	39386.5	12410.00
13	36110.84	100.82	0.952	0.30 ( 0.30)	0.99	43125.6	11201.00
14	35854.03	105.74	0.931	0.30 ( 0.30)	0.99	44857.3	12201.00
15	35026.09	112.66	0.901	0.30 ( 0.30)	0.99	46714.5	12231.00
16	34650.03	115.51	0.888	0.30 ( 0.30)	0.99	47387.8	12101.10
17	33912.52	120.29	0.868	0.30 ( 0.30)	0.99	48348.8	10400.00
18	32743.42	128.03	0.853	0.30 ( 0.30)	0.99	49643.9	12010.00
19	31690.64	133.81	0.841	0.30 ( 0.30)	0.99	49990.8	10210.00
20	31235.11	136.77	0.835	0.30 ( 0.30)	0.99	50108.0	12000.00
21	28149.93	161.27	0.785	0.30 ( 0.30)	0.99	50729.3	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 36336.23 Tc(MIN.) = 92.58  
 EFFECTIVE AREA(ACRES) = 39386.50 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 50729.3  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.00 = 106012.84 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 92.58

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.988

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	0.40	0.30	0.850	56
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.10	0.30	1.000	65
RESIDENTIAL					
"5-7 DWELLINGS/ACRE"	B	0.20	0.30	0.500	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	3.80	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.964

SUBAREA AREA(ACRES) = 4.50 SUBAREA RUNOFF(CFS) = 2.83

EFFECTIVE AREA(ACRES) = 39391.00 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 50733.8 PEAK FLOW RATE(CFS) = 36336.23

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 275.00 DOWNSTREAM(FEET) = 258.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 2669.21 CHANNEL SLOPE = 0.0064

GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT(FEET) = 9.42

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.975

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	62.15	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 36362.67

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 15.63

AVERAGE FLOW DEPTH(FEET) = 9.42 TRAVEL TIME(MIN.) = 2.85

Tc(MIN.) = 95.43

SUBAREA AREA(ACRES) = 62.15 SUBAREA RUNOFF(CFS) = 52.89

EFFECTIVE AREA(ACRES) = 39453.14 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 50795.9 PEAK FLOW RATE(CFS) = 36336.23

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT(FEET) = 9.41

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 9.41 FLOW VELOCITY(FEET/SEC.) = 15.63

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108682.05 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 95.43

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.975

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	0.10	0.30	0.100	56
NATURAL FAIR COVER					
"MEADOWS"	B	0.30	0.30	1.000	70
NATURAL FAIR COVER					
"OPEN BRUSH"	B	17.90	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.20	0.30	1.000	66
PUBLIC PARK	B	0.30	0.30	0.850	56
NATURAL POOR COVER					
"BARREN"	B	0.70	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.993

SUBAREA AREA(ACRES) = 19.50 SUBAREA RUNOFF(CFS) = 11.89

EFFECTIVE AREA(ACRES) = 39472.64 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA (ACRES) = 50815.4 PEAK FLOW RATE (CFS) = 36336.23  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 95.43

\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.975

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL "5-7 DWELLINGS/ACRE"	B	0.10	0.30	0.500	56
NATURAL FAIR COVER "WOODLAND, GRASS"	B	1.10	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.90	0.30	1.000	65
RESIDENTIAL ".4 DWELLING/ACRE"	B	0.60	0.30	0.900	56
RESIDENTIAL ".4 DWELLING/ACRE"	B	0.30	0.30	0.900	56
NATURAL POOR COVER "BARREN"	B	0.50	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.960

SUBAREA AREA (ACRES) = 3.50 SUBAREA RUNOFF (CFS) = 2.17

EFFECTIVE AREA (ACRES) = 39476.14 AREA-AVERAGED Fm (INCH/HR) = 0.30

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA (ACRES) = 50818.9 PEAK FLOW RATE (CFS) = 36336.23

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 3D50EVRL.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	839.69	19.14	0.30 (0.14)	0.48	353.0	413.00
2	831.33	25.61	0.30 (0.14)	0.48	432.0	430.00
3	802.05	27.31	0.30 (0.14)	0.48	439.5	400.00
TOTAL AREA (ACRES) =						439.5

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21616.64	21.93	2.113	0.30 (0.28)	0.94	5068.5	40500.00

2	23064.34	25.58	1.904	0.30 (0.28)	0.95	6249.1	40440.00
3	23257.19	26.37	1.873	0.30 (0.28)	0.95	6513.0	12710.00
4	23800.32	28.80	1.779	0.30 (0.29)	0.95	7297.3	40200.00
5	27050.03	42.60	1.425	0.30 (0.29)	0.97	12495.0	40100.00
6	28667.30	51.98	1.285	0.30 (0.29)	0.97	15805.9	11801.00
7	30769.28	63.03	1.182	0.30 (0.29)	0.98	20389.6	11530.00
8	31854.98	67.51	1.151	0.30 (0.29)	0.98	22703.9	11701.00
9	32771.27	71.06	1.127	0.30 (0.29)	0.98	24775.9	11910.00
10	35513.61	81.53	1.056	0.30 (0.30)	0.98	31489.6	10800.00
11	36237.24	85.83	1.027	0.30 (0.30)	0.99	34434.9	11130.00
12	36336.23	95.43	0.975	0.30 (0.30)	0.99	39476.1	12410.00
13	36110.84	103.67	0.940	0.30 (0.30)	0.99	43215.3	11201.00
14	35854.03	108.60	0.918	0.30 (0.30)	0.99	44947.0	12201.00
15	35026.09	115.55	0.888	0.30 (0.30)	0.99	46804.1	12231.00
16	34650.03	118.40	0.876	0.30 (0.30)	0.99	47477.4	12101.10
17	33912.52	123.20	0.862	0.30 (0.30)	0.99	48438.4	10400.00
18	32743.42	130.97	0.847	0.30 (0.30)	0.99	49733.5	12010.00
19	31690.64	136.78	0.835	0.30 (0.30)	0.99	50080.5	10210.00
20	31235.11	139.76	0.829	0.30 (0.30)	0.99	50197.7	12000.00
21	28149.93	164.37	0.779	0.30 (0.30)	0.99	50818.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108682.05 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	839.69	19.14	2.306	0.30 (0.14)	0.48	353.0	413.00
2	831.33	25.61	1.903	0.30 (0.14)	0.48	432.0	430.00
3	802.05	27.31	1.837	0.30 (0.14)	0.48	439.5	400.00

LONGEST FLOWPATH FROM NODE 430.00 TO NODE 12720.50 = 11352.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21696.43	19.14	2.306	0.30 (0.27)	0.91	4776.0	413.00
2	22452.72	21.93	2.113	0.30 (0.27)	0.91	5455.6	40500.00
3	23895.72	25.58	1.904	0.30 (0.28)	0.92	6680.7	40440.00
4	23903.37	25.61	1.903	0.30 (0.28)	0.92	6691.6	430.00
5	24075.46	26.37	1.873	0.30 (0.28)	0.92	6948.4	12710.00
6	24269.44	27.31	1.837	0.30 (0.28)	0.92	7256.0	400.00
7	24575.10	28.80	1.779	0.30 (0.28)	0.93	7736.8	40200.00
8	27656.90	42.60	1.425	0.30 (0.29)	0.95	12934.5	40100.00
9	29207.75	51.98	1.285	0.30 (0.29)	0.96	16245.4	11801.00
10	31260.90	63.03	1.182	0.30 (0.29)	0.97	20829.1	11530.00
11	32332.22	67.51	1.151	0.30 (0.29)	0.97	23143.4	11701.00
12	33237.13	71.06	1.127	0.30 (0.29)	0.97	25215.4	11910.00
13	35945.95	81.53	1.056	0.30 (0.29)	0.98	31929.1	10800.00
14	36655.78	85.83	1.027	0.30 (0.29)	0.98	34874.4	11130.00
15	36730.27	95.43	0.975	0.30 (0.29)	0.98	39915.6	12410.00
16	36487.96	103.67	0.940	0.30 (0.29)	0.98	43654.8	11201.00
17	36221.03	108.60	0.918	0.30 (0.29)	0.98	45386.5	12201.00
18	35378.83	115.55	0.888	0.30 (0.29)	0.98	47243.6	12231.00
19	34996.91	118.40	0.876	0.30 (0.29)	0.98	47916.9	12101.10
20	34253.04	123.20	0.862	0.30 (0.29)	0.98	48877.9	10400.00
21	33076.45	130.97	0.847	0.30 (0.29)	0.98	50173.0	12010.00
22	32018.08	136.78	0.835	0.30 (0.29)	0.98	50520.0	10210.00
23	31559.68	139.76	0.829	0.30 (0.29)	0.98	50637.2	12000.00
24	28450.80	164.37	0.779	0.30 (0.29)	0.98	51258.4	10100.00

TOTAL AREA (ACRES) = 51258.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 36730.27 Tc(MIN.) = 95.425
EFFECTIVE AREA(ACRES) = 39915.64 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97
TOTAL AREA(ACRES) = 51258.4
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108682.05 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 12
-----

>>>>CLEAR MEMORY BANK # 2 <<<<<

\*\*\*\*\*
FLOW PROCESS FROM NODE 12720.50 TO NODE 12721.00 IS CODE = 56
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 258.00 DOWNSTREAM(FEET) = 256.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 438.77 CHANNEL SLOPE = 0.0046
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
\*ESTIMATED CHANNEL HEIGHT(FEET) = 10.41
CHANNEL FLOW THRU SUBAREA(CFS) = 36730.27
FLOW VELOCITY(FEET/SEC.) = 14.00 FLOW DEPTH(FEET) = 10.41
TRAVEL TIME(MIN.) = 0.52 Tc(MIN.) = 95.95
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12721.00 = 109120.82 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 12721.00 TO NODE 12722.00 IS CODE = 56
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 256.00 DOWNSTREAM(FEET) = 255.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 830.42 CHANNEL SLOPE = 0.0012
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
\*ESTIMATED CHANNEL HEIGHT(FEET) = 15.05
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.966
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
COMMERCIAL B 11.24 0.30 0.100 56
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 36735.00
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.87
AVERAGE FLOW DEPTH(FEET) = 15.05 TRAVEL TIME(MIN.) = 1.56
Tc(MIN.) = 97.51
SUBAREA AREA(ACRES) = 11.24 SUBAREA RUNOFF(CFS) = 9.47
EFFECTIVE AREA(ACRES) = 39926.88 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
TOTAL AREA(ACRES) = 51269.7 PEAK FLOW RATE(CFS) = 36730.27
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
\*ESTIMATED CHANNEL HEIGHT(FEET) = 15.05

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 15.05 FLOW VELOCITY(FEET/SEC.) = 8.87
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12722.00 = 109951.24 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 12722.00 TO NODE 12722.00 IS CODE = 81
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 97.51
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.966
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL POOR COVER
"BARREN" B 2.10 0.30 1.000 86
NATURAL FAIR COVER
"GRASS" B 0.10 0.30 1.000 69
NATURAL FAIR COVER
"MEADOWS" B 3.60 0.30 1.000 70
NATURAL FAIR COVER
"OPEN BRUSH" B 4.10 0.30 1.000 66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 9.90 SUBAREA RUNOFF(CFS) = 5.94
EFFECTIVE AREA(ACRES) = 39936.78 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
TOTAL AREA(ACRES) = 51279.6 PEAK FLOW RATE(CFS) = 36730.27
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*
FLOW PROCESS FROM NODE 12722.00 TO NODE 12722.00 IS CODE = 81
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 97.51
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.966
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
RESIDENTIAL
".4 DWELLING/ACRE" B 0.60 0.30 0.900 56
NATURAL FAIR COVER
"WOODLAND,GRASS" B 1.90 0.30 1.000 65
NATURAL FAIR COVER
"WOODLAND,GRASS" B 0.10 0.30 1.000 65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.977
SUBAREA AREA(ACRES) = 2.60 SUBAREA RUNOFF(CFS) = 1.58
EFFECTIVE AREA(ACRES) = 39939.38 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
TOTAL AREA(ACRES) = 51282.2 PEAK FLOW RATE(CFS) = 36730.27
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12722.00 TO NODE 12740.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 255.00 DOWNSTREAM(FEET) = 252.10
CHANNEL LENGTH THRU SUBAREA(FEET) = 624.00 CHANNEL SLOPE = 0.0046
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
\*ESTIMATED CHANNEL HEIGHT(FEET) = 10.35
\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.963

SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
COMMERCIAL B 1.50 0.30 0.100 56
NATURAL FAIR COVER
"GRASS" B 2.50 0.30 1.000 69
NATURAL FAIR COVER
"GRASS" B 0.50 0.30 1.000 69
NATURAL FAIR COVER
"WOODLAND,GRASS" B 0.70 0.30 1.000 65
NATURAL FAIR COVER
"WOODLAND,GRASS" B 6.20 0.30 1.000 65
NATURAL FAIR COVER
"WOODLAND,GRASS" B 6.50 0.30 1.000 65
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.925
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 36735.79
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 14.10
AVERAGE FLOW DEPTH(FEET) = 10.35 TRAVEL TIME(MIN.) = 0.74
Tc(MIN.) = 98.25
SUBAREA AREA(ACRES) = 17.90 SUBAREA RUNOFF(CFS) = 11.05
EFFECTIVE AREA(ACRES) = 39957.28 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
TOTAL AREA(ACRES) = 51300.1 PEAK FLOW RATE(CFS) = 36730.27
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
\*ESTIMATED CHANNEL HEIGHT(FEET) = 10.35

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 10.35 FLOW VELOCITY(FEET/SEC.) = 14.10
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12740.00 = 110575.24 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 98.25
\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.963
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"OPEN BRUSH" B 4.70 0.30 1.000 66
NATURAL FAIR COVER
"OPEN BRUSH" B 6.70 0.30 1.000 66

NATURAL FAIR COVER
"OPEN BRUSH" B 12.00 0.30 1.000 66
NATURAL FAIR COVER
"CHAPARRAL,BROADLEAF" B 0.80 0.30 1.000 63
NATURAL FAIR COVER
"CHAPARRAL,BROADLEAF" B 20.20 0.30 1.000 63
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 44.40 SUBAREA RUNOFF(CFS) = 26.50
EFFECTIVE AREA(ACRES) = 40001.68 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98
TOTAL AREA(ACRES) = 51344.4 PEAK FLOW RATE(CFS) = 36730.27
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*
FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:
TIME OF CONCENTRATION(MIN.) = 98.25
RAINFALL INTENSITY(INCH/HR) = 0.96
AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.98
EFFECTIVE STREAM AREA(ACRES) = 40001.68
TOTAL STREAM AREA(ACRES) = 51344.45
PEAK FLOW RATE(CFS) AT CONFLUENCE = 36730.27

\*\*\*\*\*
FLOW PROCESS FROM NODE 12730.00 TO NODE 12731.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH(FEET) = 561.54
ELEVATION DATA: UPSTREAM(FEET) = 613.29 DOWNSTREAM(FEET) = 551.75

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 13.823
\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 2.863

SUBAREA Tc AND LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)
NATURAL FAIR COVER
"CHAPARRAL,BROADLEAF" B 6.33 0.30 1.000 63 13.82
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA RUNOFF(CFS) = 14.60
TOTAL AREA(ACRES) = 6.33 PEAK FLOW RATE(CFS) = 14.60

\*\*\*\*\*
FLOW PROCESS FROM NODE 12731.00 TO NODE 12732.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<



ELEVATION DATA: UPSTREAM(FEET) = 551.75 DOWNSTREAM(FEET) = 494.40  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 971.91 CHANNEL SLOPE = 0.0590  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.91  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 2.489  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 COMMERCIAL B 34.62 0.30 0.100 56  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 52.95  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.00  
 AVERAGE FLOW DEPTH(FEET) = 0.90 TRAVEL TIME(MIN.) = 3.24  
 Tc(MIN.) = 17.06  
 SUBAREA AREA(ACRES) = 34.62 SUBAREA RUNOFF(CFS) = 76.61  
 EFFECTIVE AREA(ACRES) = 40.95 AREA-AVERAGED Fm(INCH/HR) = 0.07  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.24  
 TOTAL AREA(ACRES) = 40.9 PEAK FLOW RATE(CFS) = 89.07  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.21  
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.21 FLOW VELOCITY(FEET/SEC.) = 5.93  
 LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12732.00 = 1533.45 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12732.00 TO NODE 12733.00 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 494.40 DOWNSTREAM(FEET) = 431.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1156.41 CHANNEL SLOPE = 0.0548  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.68  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 2.239  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 COMMERCIAL B 59.52 0.30 0.100 56  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 148.29  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.78  
 AVERAGE FLOW DEPTH(FEET) = 1.65 TRAVEL TIME(MIN.) = 2.84  
 Tc(MIN.) = 19.90  
 SUBAREA AREA(ACRES) = 59.52 SUBAREA RUNOFF(CFS) = 118.31  
 EFFECTIVE AREA(ACRES) = 100.47 AREA-AVERAGED Fm(INCH/HR) = 0.05  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.16  
 TOTAL AREA(ACRES) = 100.5 PEAK FLOW RATE(CFS) = 198.17  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.93

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.93 FLOW VELOCITY(FEET/SEC.) = 7.39  
 LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12733.00 = 2689.86 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12733.00 TO NODE 12734.00 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 431.00 DOWNSTREAM(FEET) = 367.10  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1654.48 CHANNEL SLOPE = 0.0386  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 2.47  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.997  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 COMMERCIAL B 64.05 0.30 0.100 56  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 254.93  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.03  
 AVERAGE FLOW DEPTH(FEET) = 2.44 TRAVEL TIME(MIN.) = 3.92  
 Tc(MIN.) = 23.83  
 SUBAREA AREA(ACRES) = 64.05 SUBAREA RUNOFF(CFS) = 113.41  
 EFFECTIVE AREA(ACRES) = 164.52 AREA-AVERAGED Fm(INCH/HR) = 0.04  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.13  
 TOTAL AREA(ACRES) = 164.5 PEAK FLOW RATE(CFS) = 289.76  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 2.61

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 2.61 FLOW VELOCITY(FEET/SEC.) = 7.29  
 LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12734.00 = 4344.34 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12734.00 TO NODE 12740.00 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 367.11 DOWNSTREAM(FEET) = 252.10  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1880.98 CHANNEL SLOPE = 0.0611  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 2.41  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.833  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 COMMERCIAL B 26.02 0.30 0.100 56  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 310.87  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.76

AVERAGE FLOW DEPTH (FEET) = 2.40 TRAVEL TIME (MIN.) = 3.58  
 Tc (MIN.) = 27.41  
 SUBAREA AREA (ACRES) = 26.02 SUBAREA RUNOFF (CFS) = 42.23  
 EFFECTIVE AREA (ACRES) = 190.54 AREA-AVERAGED Fm (INCH/HR) = 0.04  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.13  
 TOTAL AREA (ACRES) = 190.5 PEAK FLOW RATE (CFS) = 307.67  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 2.39

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 2.39 FLOW VELOCITY (FEET/SEC.) = 8.73  
 LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12740.00 = 6225.32 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====  
 TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
 TIME OF CONCENTRATION (MIN.) = 27.41  
 RAINFALL INTENSITY (INCH/HR) = 1.83  
 AREA-AVERAGED Fm (INCH/HR) = 0.04  
 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.13  
 EFFECTIVE STREAM AREA (ACRES) = 190.54  
 TOTAL STREAM AREA (ACRES) = 190.54  
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 307.67

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21696.43	22.47	2.080	0.30 ( 0.27)	0.91	4862.0	413.00
1	22452.72	25.23	1.917	0.30 ( 0.27)	0.91	5541.7	40500.00
1	23895.72	28.81	1.779	0.30 ( 0.27)	0.92	6766.8	40440.00
1	23903.37	28.84	1.778	0.30 ( 0.27)	0.92	6777.7	430.00
1	24075.46	29.59	1.749	0.30 ( 0.28)	0.92	7034.4	12710.00
1	24269.44	30.53	1.719	0.30 ( 0.28)	0.92	7342.1	400.00
1	24575.10	32.00	1.680	0.30 ( 0.28)	0.93	7822.8	40200.00
1	27656.90	45.69	1.375	0.30 ( 0.29)	0.95	13020.5	40100.00
1	29207.75	55.01	1.253	0.30 ( 0.29)	0.96	16331.4	11801.00
1	31260.90	65.99	1.161	0.30 ( 0.29)	0.97	20915.2	11530.00
1	32332.22	70.45	1.131	0.30 ( 0.29)	0.97	23229.4	11701.00
1	33237.13	73.97	1.107	0.30 ( 0.29)	0.97	25301.4	11910.00
1	35945.95	84.37	1.037	0.30 ( 0.29)	0.98	32015.1	10800.00
1	36655.78	88.65	1.008	0.30 ( 0.29)	0.98	34960.5	11130.00
1	36730.27	98.25	0.963	0.30 ( 0.29)	0.98	40001.7	12410.00
1	36487.96	106.49	0.928	0.30 ( 0.29)	0.98	43740.8	11201.00
1	36221.03	111.43	0.906	0.30 ( 0.29)	0.98	45472.5	12201.00
1	35378.83	118.40	0.876	0.30 ( 0.29)	0.98	47329.6	12231.00
1	34996.91	121.26	0.866	0.30 ( 0.29)	0.98	48002.9	12101.10
1	34253.04	126.08	0.857	0.30 ( 0.29)	0.98	48963.9	10400.00
1	33076.45	133.89	0.841	0.30 ( 0.29)	0.98	50259.0	12010.00
1	32018.08	139.73	0.829	0.30 ( 0.29)	0.98	50606.0	10210.00
1	31559.68	142.72	0.823	0.30 ( 0.29)	0.98	50723.2	12000.00
1	28450.80	167.42	0.773	0.30 ( 0.29)	0.98	51344.4	10100.00

2 307.67 27.41 1.833 0.30 ( 0.04) 0.13 190.5 12730.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21983.38	22.47	2.080	0.30 ( 0.27)	0.88	5018.2	413.00
2	22749.21	25.23	1.917	0.30 ( 0.27)	0.89	5717.1	40500.00
3	23638.06	27.41	1.833	0.30 ( 0.27)	0.89	6477.3	12730.00
4	24194.10	28.81	1.779	0.30 ( 0.27)	0.89	6957.3	40440.00
5	24201.55	28.84	1.778	0.30 ( 0.27)	0.90	6968.2	430.00
6	24368.66	29.59	1.749	0.30 ( 0.27)	0.90	7225.0	12710.00
7	24557.54	30.53	1.719	0.30 ( 0.27)	0.90	7532.6	400.00
8	24856.46	32.00	1.680	0.30 ( 0.27)	0.91	8013.3	40200.00
9	27885.99	45.69	1.375	0.30 ( 0.28)	0.94	13211.1	40100.00
10	29416.01	55.01	1.253	0.30 ( 0.29)	0.95	16521.9	11801.00
11	31453.39	65.99	1.161	0.30 ( 0.29)	0.96	21105.7	11530.00
12	32519.54	70.45	1.131	0.30 ( 0.29)	0.96	23420.0	11701.00
13	33420.36	73.97	1.107	0.30 ( 0.29)	0.97	25492.0	11910.00
14	36117.11	84.37	1.037	0.30 ( 0.29)	0.97	32205.7	10800.00
15	36821.97	88.65	1.008	0.30 ( 0.29)	0.97	35151.0	11130.00
16	36888.77	98.25	0.963	0.30 ( 0.29)	0.98	40192.2	12410.00
17	36640.34	106.49	0.928	0.30 ( 0.29)	0.98	43931.3	11201.00
18	36369.74	111.43	0.906	0.30 ( 0.29)	0.98	45663.0	12201.00
19	35522.36	118.40	0.876	0.30 ( 0.29)	0.98	47520.2	12231.00
20	35138.81	121.26	0.866	0.30 ( 0.29)	0.98	48193.5	12101.10
21	34393.25	126.08	0.857	0.30 ( 0.29)	0.98	49154.5	10400.00
22	33213.95	133.89	0.841	0.30 ( 0.29)	0.98	50449.6	12010.00
23	32153.54	139.73	0.829	0.30 ( 0.29)	0.98	50796.5	10210.00
24	31694.09	142.72	0.823	0.30 ( 0.29)	0.98	50923.8	12000.00
25	28576.61	167.42	0.773	0.30 ( 0.29)	0.98	51535.0	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 36888.77 Tc (MIN.) = 98.25  
 EFFECTIVE AREA (ACRES) = 40192.22 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98  
 TOTAL AREA (ACRES) = 51535.0  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12740.00 = 110575.24 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12740.00 TO NODE 12741.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====  
 ELEVATION DATA: UPSTREAM (FEET) = 252.10 DOWNSTREAM (FEET) = 247.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 401.47 CHANNEL SLOPE = 0.0127  
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 7.80  
 CHANNEL FLOW THRU SUBAREA (CFS) = 36888.77  
 FLOW VELOCITY (FEET/SEC.) = 19.78 FLOW DEPTH (FEET) = 7.80  
 TRAVEL TIME (MIN.) = 0.34 Tc (MIN.) = 98.58  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12741.00 = 110976.71 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 98.58

\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.962

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	2.10	0.30	0.100	56
NATURAL FAIR COVER "GRASS"	B	7.50	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	0.90	0.30	1.000	66
PUBLIC PARK	B	1.90	0.30	0.850	56
RESIDENTIAL ".4 DWELLING/ACRE"	B	0.40	0.30	0.900	56
AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	0.50	0.30	1.000	79

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.833

SUBAREA AREA(ACRES) = 13.30 SUBAREA RUNOFF(CFS) = 8.52

EFFECTIVE AREA(ACRES) = 40205.52 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98

TOTAL AREA(ACRES) = 51548.3 PEAK FLOW RATE(CFS) = 36888.77

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 98.58

\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.962

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.90	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 0.90 SUBAREA RUNOFF(CFS) = 0.54

EFFECTIVE AREA(ACRES) = 40206.42 AREA-AVERAGED Fm(INCH/HR) = 0.29

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98

TOTAL AREA(ACRES) = 51549.2 PEAK FLOW RATE(CFS) = 36888.77

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<

PEAK FLOWRATE TABLE FILE NAME: 3C50EVRL.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1374.38	17.61	0.30( 0.14)	0.47	637.4	300.00
2	1389.90	22.77	0.30( 0.14)	0.48	777.0	327.00

3	1367.26	23.85	0.30( 0.14)	0.48	790.7	350.00
4	1334.48	25.09	0.30( 0.14)	0.48	803.7	320.00
5	1249.70	29.13	0.30( 0.15)	0.49	831.7	306.00
6	1142.13	36.22	0.30( 0.15)	0.50	870.6	390.00
TOTAL AREA(ACRES) =					870.6	

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21983.38	22.88	2.055	0.30( 0.27)	0.88	5032.4	413.00
2	22749.21	25.63	1.902	0.30( 0.27)	0.89	5731.3	40500.00
3	23638.06	27.80	1.818	0.30( 0.27)	0.89	6491.5	12730.00
4	24194.10	29.20	1.764	0.30( 0.27)	0.89	6971.5	40440.00
5	24201.55	29.23	1.763	0.30( 0.27)	0.89	6982.4	430.00
6	24368.66	29.98	1.734	0.30( 0.27)	0.90	7239.2	12710.00
7	24557.54	30.91	1.709	0.30( 0.27)	0.90	7546.8	400.00
8	24856.46	32.39	1.669	0.30( 0.27)	0.91	8027.5	40200.00
9	27885.99	46.06	1.369	0.30( 0.28)	0.94	13225.3	40100.00
10	29416.01	55.38	1.250	0.30( 0.29)	0.95	16536.1	11801.00
11	31453.39	66.35	1.159	0.30( 0.29)	0.96	21119.9	11530.00
12	32519.54	70.80	1.129	0.30( 0.29)	0.96	23434.2	11701.00
13	33420.36	74.32	1.105	0.30( 0.29)	0.97	25506.2	11910.00
14	36117.11	84.71	1.035	0.30( 0.29)	0.97	32219.9	10800.00
15	36821.97	88.99	1.006	0.30( 0.29)	0.97	35165.2	11130.00
16	36888.77	98.58	0.962	0.30( 0.29)	0.98	40206.4	12410.00
17	36640.34	106.83	0.926	0.30( 0.29)	0.98	43945.5	11201.00
18	36369.74	111.77	0.905	0.30( 0.29)	0.98	45677.2	12201.00
19	35522.36	118.74	0.874	0.30( 0.29)	0.98	47534.4	12231.00
20	35138.81	121.61	0.866	0.30( 0.29)	0.98	48207.7	12101.10
21	34393.25	126.43	0.856	0.30( 0.29)	0.98	49168.7	10400.00
22	33213.95	134.24	0.840	0.30( 0.29)	0.98	50463.8	12010.00
23	32153.54	140.08	0.828	0.30( 0.29)	0.98	50810.7	10210.00
24	31694.09	143.08	0.822	0.30( 0.29)	0.98	50928.0	12000.00
25	28576.61	167.79	0.772	0.30( 0.29)	0.98	51549.2	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12741.00 = 110976.71 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1374.38	17.61	2.441	0.30( 0.14)	0.47	637.4	300.00
2	1389.90	22.77	2.062	0.30( 0.14)	0.48	777.0	327.00
3	1367.26	23.85	1.996	0.30( 0.14)	0.48	790.7	350.00
4	1334.48	25.09	1.922	0.30( 0.14)	0.48	803.7	320.00
5	1249.70	29.13	1.766	0.30( 0.15)	0.49	831.7	306.00
6	1142.13	36.22	1.568	0.30( 0.15)	0.50	870.6	390.00

LONGEST FLOWPATH FROM NODE 390.00 TO NODE 12741.00 = 15238.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21938.17	17.61	2.441	0.30( 0.25)	0.83	4510.8	300.00
2	23350.25	22.77	2.062	0.30( 0.25)	0.83	5786.1	327.00

3	23371.05	22.88	2.055	0.30	( 0.25)	0.83	5810.8	413.00
4	23620.56	23.85	1.996	0.30	( 0.25)	0.83	6069.4	350.00
5	23934.82	25.09	1.922	0.30	( 0.25)	0.84	6399.1	320.00
6	24072.48	25.63	1.902	0.30	( 0.25)	0.84	6538.6	40500.00
7	24915.73	27.80	1.818	0.30	( 0.25)	0.85	7314.0	12730.00
8	25417.12	29.13	1.766	0.30	( 0.26)	0.85	7780.2	306.00
9	25442.78	29.20	1.764	0.30	( 0.26)	0.85	7803.6	40440.00
10	25449.77	29.23	1.763	0.30	( 0.26)	0.85	7814.7	430.00
11	25605.47	29.98	1.734	0.30	( 0.26)	0.86	8075.5	12710.00
12	25780.20	30.91	1.709	0.30	( 0.26)	0.86	8388.3	400.00
13	26056.72	32.39	1.669	0.30	( 0.26)	0.87	8877.1	40200.00
14	26847.30	36.22	1.568	0.30	( 0.26)	0.88	10354.2	390.00
15	28867.90	46.06	1.369	0.30	( 0.27)	0.91	14095.9	40100.00
16	30301.81	55.38	1.250	0.30	( 0.28)	0.93	17406.7	11801.00
17	32266.16	66.35	1.159	0.30	( 0.28)	0.94	21990.5	11530.00
18	33308.02	70.80	1.129	0.30	( 0.28)	0.95	24304.8	11701.00
19	34189.63	74.32	1.105	0.30	( 0.29)	0.95	26376.8	11910.00
20	36829.74	84.71	1.035	0.30	( 0.29)	0.96	33090.5	10800.00
21	37511.23	88.99	1.006	0.30	( 0.29)	0.96	36035.8	11130.00
22	37542.53	98.58	0.962	0.30	( 0.29)	0.97	41077.0	12410.00
23	37265.28	106.83	0.926	0.30	( 0.29)	0.97	44816.1	11201.00
24	36977.43	111.77	0.905	0.30	( 0.29)	0.97	46547.8	12201.00
25	36105.70	118.74	0.874	0.30	( 0.29)	0.97	48405.0	12231.00
26	35715.12	121.61	0.866	0.30	( 0.29)	0.97	49078.3	12101.10
27	34961.66	126.43	0.856	0.30	( 0.29)	0.97	50039.3	10400.00
28	33769.55	134.24	0.840	0.30	( 0.29)	0.97	51334.4	12010.00
29	32699.56	140.08	0.828	0.30	( 0.29)	0.97	51681.3	10210.00
30	32235.21	143.08	0.822	0.30	( 0.29)	0.97	51798.6	12000.00
31	29077.21	167.79	0.772	0.30	( 0.29)	0.97	52419.8	10100.00

TOTAL AREA (ACRES) = 52419.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 37542.53 Tc (MIN.) = 98.584  
EFFECTIVE AREA (ACRES) = 41077.02 AREA-AVERAGED Fm (INCH/HR) = 0.29  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA (ACRES) = 52419.8  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12741.00 = 110976.71 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 2 <<<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12741.00 TO NODE 12800.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 247.00 DOWNSTREAM (FEET) = 240.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 819.00 CHANNEL SLOPE = 0.0085  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 8.82  
CHANNEL FLOW THRU SUBAREA (CFS) = 37542.53  
FLOW VELOCITY (FEET/SEC.) = 17.43 FLOW DEPTH (FEET) = 8.82  
TRAVEL TIME (MIN.) = 0.78 Tc (MIN.) = 99.37

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111795.71 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<

-----  
MAINLINE Tc (MIN.) = 99.37  
\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.958  
SUBAREA LOSS RATE DATA (AMC II):  
DEVELOPMENT TYPE/ SCSSOIL AREA Fp Ap SCSS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
NATURAL FAIR COVER  
"GRASS" B 17.31 0.30 1.000 69  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 17.31 SUBAREA RUNOFF (CFS) = 10.26  
EFFECTIVE AREA (ACRES) = 41094.33 AREA-AVERAGED Fm (INCH/HR) = 0.29  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97  
TOTAL AREA (ACRES) = 52437.1 PEAK FLOW RATE (CFS) = 37542.53  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
-----

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 52437.1 TC (MIN.) = 99.37  
EFFECTIVE AREA (ACRES) = 41094.33 AREA-AVERAGED Fm (INCH/HR) = 0.29  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.967  
PEAK FLOW RATE (CFS) = 37542.53

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21938.17	18.55	2.358	0.30 ( 0.25)	0.83	4528.1	300.00
2	23350.25	23.69	2.006	0.30 ( 0.25)	0.83	5803.5	327.00
3	23371.05	23.79	1.999	0.30 ( 0.25)	0.83	5828.1	413.00
4	23620.56	24.76	1.941	0.30 ( 0.25)	0.83	6086.7	350.00
5	23934.82	26.00	1.887	0.30 ( 0.25)	0.84	6416.4	320.00
6	24072.48	26.53	1.867	0.30 ( 0.25)	0.84	6556.0	40500.00
7	24915.73	28.70	1.783	0.30 ( 0.25)	0.85	7331.3	12730.00
8	25417.12	30.02	1.732	0.30 ( 0.26)	0.85	7797.5	306.00
9	25442.78	30.09	1.731	0.30 ( 0.26)	0.85	7820.9	40440.00
10	25449.77	30.12	1.730	0.30 ( 0.26)	0.85	7832.0	430.00
11	25605.47	30.87	1.710	0.30 ( 0.26)	0.86	8092.8	12710.00
12	25780.20	31.80	1.685	0.30 ( 0.26)	0.86	8405.6	400.00
13	26056.72	33.27	1.646	0.30 ( 0.26)	0.87	8894.4	40200.00
14	26847.30	37.09	1.544	0.30 ( 0.26)	0.88	10371.6	390.00
15	28867.90	46.91	1.355	0.30 ( 0.27)	0.91	14113.2	40100.00
16	30301.81	56.22	1.241	0.30 ( 0.28)	0.93	17424.1	11801.00
17	32266.16	67.17	1.153	0.30 ( 0.28)	0.94	22007.8	11530.00
18	33308.02	71.62	1.123	0.30 ( 0.28)	0.95	24322.1	11701.00
19	34189.63	75.13	1.100	0.30 ( 0.29)	0.95	26394.1	11910.00
20	36829.74	85.49	1.029	0.30 ( 0.29)	0.96	33107.8	10800.00
21	37511.23	89.77	1.001	0.30 ( 0.29)	0.96	36053.1	11130.00
22	37542.53	99.37	0.958	0.30 ( 0.29)	0.97	41094.3	12410.00
23	37265.28	107.62	0.923	0.30 ( 0.29)	0.97	44833.4	11201.00
24	36977.43	112.56	0.901	0.30 ( 0.29)	0.97	46565.1	12201.00
25	36105.70	119.53	0.871	0.30 ( 0.29)	0.97	48422.3	12231.00
26	35715.12	122.40	0.864	0.30 ( 0.29)	0.97	49095.6	12101.10
27	34961.66	127.23	0.854	0.30 ( 0.29)	0.97	50056.6	10400.00

28	33769.55	135.05	0.838	0.30 ( 0.29)	0.97	51351.7	12010.00
29	32699.56	140.90	0.826	0.30 ( 0.29)	0.97	51698.7	10210.00
30	32235.21	143.90	0.820	0.30 ( 0.29)	0.97	51815.9	12000.00
31	29077.21	168.65	0.770	0.30 ( 0.29)	0.97	52437.1	10100.00

=====  
=====  
END OF RATIONAL METHOD ANALYSIS

\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S28- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 50-YR RM EV APRIL 2019 CCHIU \*  
\*\*\*\*\*

FILE NAME: RI50EV28.DAT  
TIME/DATE OF STUDY: 09:14 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 50.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.453
- 2) 10.00; 3.490
- 3) 15.00; 2.670
- 4) 20.00; 2.230
- 5) 25.00; 1.926
- 6) 30.00; 1.733
- 7) 40.00; 1.467
- 8) 50.00; 1.305
- 9) 60.00; 1.202
- 10) 90.00; 0.999
- 11) 120.00; 0.869
- 12) 180.00; 0.747
- 13) 360.00; 0.555
- 14) 1200.00; 0.244

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI50EV27.DNA  
MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21938.17	18.55	0.30 ( 0.25)	0.83	4528.1	300.00
2	24915.73	28.70	0.30 ( 0.25)	0.85	7331.3	12730.00
3	26056.72	33.27	0.30 ( 0.26)	0.87	8894.4	40200.00
4	26847.30	37.09	0.30 ( 0.26)	0.88	10371.6	390.00
5	28867.90	46.91	0.30 ( 0.27)	0.91	14113.2	40100.00
6	30301.81	56.22	0.30 ( 0.28)	0.93	17424.1	11801.00
7	32266.16	67.17	0.30 ( 0.28)	0.94	22007.8	11530.00
8	33308.02	71.62	0.30 ( 0.28)	0.95	24322.1	11701.00
9	34189.63	75.13	0.30 ( 0.29)	0.95	26394.1	11910.00
10	36829.74	85.49	0.30 ( 0.29)	0.96	33107.8	10800.00
11	37511.23	89.77	0.30 ( 0.29)	0.96	36053.1	11130.00
12	37542.53	99.37	0.30 ( 0.29)	0.97	41094.3	12410.00
13	37265.28	107.62	0.30 ( 0.29)	0.97	44833.4	11201.00
14	36977.43	112.56	0.30 ( 0.29)	0.97	46565.1	12201.00
15	36105.70	119.53	0.30 ( 0.29)	0.97	48422.3	12231.00
16	34961.66	127.23	0.30 ( 0.29)	0.97	50056.6	10400.00
17	33769.55	135.05	0.30 ( 0.29)	0.97	51351.7	12010.00
18	32699.56	140.90	0.30 ( 0.29)	0.97	51698.7	10210.00
19	32235.21	143.90	0.30 ( 0.29)	0.97	51815.9	12000.00
20	29077.21	168.65	0.30 ( 0.29)	0.97	52437.1	10100.00
TOTAL AREA (ACRES) =						52437.1

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 0610501X.DNA  
MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1506.93	25.94	0.30 ( 0.29)	0.98	1025.8	50120.00
2	1480.85	27.19	0.30 ( 0.29)	0.98	1040.8	50150.00
3	1382.53	30.77	0.30 ( 0.29)	0.98	1063.4	50100.00
TOTAL AREA (ACRES) =						1063.4

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 3 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM	Q	Tc	Fp (Fm)	Ap	Ae	HEADWATER
--------	---	----	---------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(ACRES)	NODE
1	21938.17	18.55	0.30 ( 0.25)	0.83	4528.1 300.00
2	24915.73	28.70	0.30 ( 0.25)	0.85	7331.3 12730.00
3	26056.72	33.27	0.30 ( 0.26)	0.87	8894.4 40200.00
4	26847.30	37.09	0.30 ( 0.26)	0.88	10371.6 390.00
5	28867.90	46.91	0.30 ( 0.27)	0.91	14113.2 40100.00
6	30301.81	56.22	0.30 ( 0.28)	0.93	17424.1 11801.00
7	32266.16	67.17	0.30 ( 0.28)	0.94	22007.8 11530.00
8	33308.02	71.62	0.30 ( 0.28)	0.95	24322.1 11701.00
9	34189.63	75.13	0.30 ( 0.29)	0.95	26394.1 11910.00
10	36829.74	85.49	0.30 ( 0.29)	0.96	33107.8 10800.00
11	37511.23	89.77	0.30 ( 0.29)	0.96	36053.1 11130.00
12	37542.53	99.37	0.30 ( 0.29)	0.97	41094.3 12410.00
13	37265.28	107.62	0.30 ( 0.29)	0.97	44833.4 11201.00
14	36977.43	112.56	0.30 ( 0.29)	0.97	46565.1 12201.00
15	36105.70	119.53	0.30 ( 0.29)	0.97	48422.3 12231.00
16	34961.66	127.23	0.30 ( 0.29)	0.97	50056.6 10400.00
17	33769.55	135.05	0.30 ( 0.29)	0.97	51351.7 12010.00
18	32699.56	140.90	0.30 ( 0.29)	0.97	51698.7 10210.00
19	32235.21	143.90	0.30 ( 0.29)	0.97	51815.9 12000.00
20	29077.21	168.65	0.30 ( 0.29)	0.97	52437.1 10100.00
TOTAL AREA (ACRES) =		52437.1			

\*\*\*\*\*

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21938.17	18.55	2.358	0.30 ( 0.25)	0.83	4528.1	300.00
2	24915.73	28.70	1.783	0.30 ( 0.25)	0.85	7331.3	12730.00
3	26056.72	33.27	1.646	0.30 ( 0.26)	0.87	8894.4	40200.00
4	26847.30	37.09	1.544	0.30 ( 0.26)	0.88	10371.6	390.00
5	28867.90	46.91	1.355	0.30 ( 0.27)	0.91	14113.2	40100.00
6	30301.81	56.22	1.241	0.30 ( 0.28)	0.93	17424.1	11801.00
7	32266.16	67.17	1.153	0.30 ( 0.28)	0.94	22007.8	11530.00
8	33308.02	71.62	1.123	0.30 ( 0.28)	0.95	24322.1	11701.00
9	34189.63	75.13	1.100	0.30 ( 0.29)	0.95	26394.1	11910.00
10	36829.74	85.49	1.029	0.30 ( 0.29)	0.96	33107.8	10800.00
11	37511.23	89.77	1.001	0.30 ( 0.29)	0.96	36053.1	11130.00
12	37542.53	99.37	0.958	0.30 ( 0.29)	0.97	41094.3	12410.00
13	37265.28	107.62	0.923	0.30 ( 0.29)	0.97	44833.4	11201.00
14	36977.43	112.56	0.901	0.30 ( 0.29)	0.97	46565.1	12201.00
15	36105.70	119.53	0.871	0.30 ( 0.29)	0.97	48422.3	12231.00
16	34961.66	127.23	0.854	0.30 ( 0.29)	0.97	50056.6	10400.00
17	33769.55	135.05	0.838	0.30 ( 0.29)	0.97	51351.7	12010.00
18	32699.56	140.90	0.826	0.30 ( 0.29)	0.97	51698.7	10210.00
19	32235.21	143.90	0.820	0.30 ( 0.29)	0.97	51815.9	12000.00
20	29077.21	168.65	0.770	0.30 ( 0.29)	0.97	52437.1	10100.00
LONGEST FLOWPATH FROM NODE		10100.00 TO NODE 12800.00 = 111795.71 FEET.					

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1506.93	25.94	1.890	0.30 ( 0.29)	0.98	1025.8	50120.00

2	1480.85	27.19	1.841	0.30 ( 0.29)	0.98	1040.8	50150.00
3	1382.53	30.77	1.713	0.30 ( 0.29)	0.98	1063.4	50100.00
LONGEST FLOWPATH FROM NODE		50150.00 TO NODE 12800.00 = 11349.00 FEET.					

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23331.79	18.55	2.358	0.30 ( 0.25)	0.85	5261.5	300.00
2	25613.33	25.94	1.890	0.30 ( 0.26)	0.86	7595.1	50120.00
3	25954.64	27.19	1.841	0.30 ( 0.26)	0.86	7956.1	50150.00
4	26355.19	28.70	1.783	0.30 ( 0.26)	0.86	8381.6	12730.00
5	26815.02	30.77	1.713	0.30 ( 0.26)	0.87	9102.6	50100.00
6	27374.32	33.27	1.646	0.30 ( 0.26)	0.88	9957.8	40200.00
7	28065.83	37.09	1.544	0.30 ( 0.27)	0.89	11434.9	390.00
8	29901.89	46.91	1.355	0.30 ( 0.28)	0.92	15176.6	40100.00
9	31224.61	56.22	1.241	0.30 ( 0.28)	0.93	18487.4	11801.00
10	33103.64	67.17	1.153	0.30 ( 0.28)	0.94	23071.2	11530.00
11	34116.19	71.62	1.123	0.30 ( 0.28)	0.95	25385.5	11701.00
12	34974.61	75.13	1.100	0.30 ( 0.29)	0.95	27457.5	11910.00
13	37546.36	85.49	1.029	0.30 ( 0.29)	0.96	34171.2	10800.00
14	38199.61	89.77	1.001	0.30 ( 0.29)	0.96	37116.5	11130.00
15	38189.85	99.37	0.958	0.30 ( 0.29)	0.97	42157.7	12410.00
16	37877.74	107.62	0.923	0.30 ( 0.29)	0.97	45896.8	11201.00
17	37569.03	112.56	0.901	0.30 ( 0.29)	0.97	47628.5	12201.00
18	36667.82	119.53	0.871	0.30 ( 0.29)	0.97	49485.7	12231.00
19	35507.47	127.23	0.854	0.30 ( 0.29)	0.97	51120.0	10400.00
20	34299.86	135.05	0.838	0.30 ( 0.29)	0.97	52415.1	12010.00
21	33218.28	140.90	0.826	0.30 ( 0.29)	0.97	52762.0	10210.00
22	32747.98	143.90	0.820	0.30 ( 0.29)	0.97	52879.2	12000.00
23	29540.92	168.65	0.770	0.30 ( 0.29)	0.97	53500.5	10100.00
TOTAL AREA (ACRES) =		53500.5					

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 38199.61 Tc (MIN.) = 89.774  
EFFECTIVE AREA (ACRES) = 37116.52 AREA-AVERAGED Fm (INCH/HR) = 0.29  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95  
TOTAL AREA (ACRES) = 53500.5  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111795.71 FEET.

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 53500.5 TC (MIN.) = 89.77  
EFFECTIVE AREA (ACRES) = 37116.52 AREA-AVERAGED Fm (INCH/HR) = 0.29  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.964  
PEAK FLOW RATE (CFS) = 38199.61

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23331.79	18.55	2.358	0.30 ( 0.25)	0.85	5261.5	300.00
2	25613.33	25.94	1.890	0.30 ( 0.26)	0.86	7595.1	50120.00
3	25954.64	27.19	1.841	0.30 ( 0.26)	0.86	7956.1	50150.00
4	26355.19	28.70	1.783	0.30 ( 0.26)	0.86	8381.6	12730.00
5	26815.02	30.77	1.713	0.30 ( 0.26)	0.87	9102.6	50100.00
6	27374.32	33.27	1.646	0.30 ( 0.26)	0.88	9957.8	40200.00
7	28065.83	37.09	1.544	0.30 ( 0.27)	0.89	11434.9	390.00
8	29901.89	46.91	1.355	0.30 ( 0.28)	0.92	15176.6	40100.00
9	31224.61	56.22	1.241	0.30 ( 0.28)	0.93	18487.4	11801.00
10	33103.64	67.17	1.153	0.30 ( 0.28)	0.94	23071.2	11530.00

11	34116.19	71.62	1.123	0.30 ( 0.28)	0.95	25385.5	11701.00
12	34974.61	75.13	1.100	0.30 ( 0.29)	0.95	27457.5	11910.00
13	37546.36	85.49	1.029	0.30 ( 0.29)	0.96	34171.2	10800.00
14	38199.61	89.77	1.001	0.30 ( 0.29)	0.96	37116.5	11130.00
15	38189.85	99.37	0.958	0.30 ( 0.29)	0.97	42157.7	12410.00
16	37877.74	107.62	0.923	0.30 ( 0.29)	0.97	45896.8	11201.00
17	37569.03	112.56	0.901	0.30 ( 0.29)	0.97	47628.5	12201.00
18	36667.82	119.53	0.871	0.30 ( 0.29)	0.97	49485.7	12231.00
19	35507.47	127.23	0.854	0.30 ( 0.29)	0.97	51120.0	10400.00
20	34299.86	135.05	0.838	0.30 ( 0.29)	0.97	52415.1	12010.00
21	33218.28	140.90	0.826	0.30 ( 0.29)	0.97	52762.0	10210.00
22	32747.98	143.90	0.820	0.30 ( 0.29)	0.97	52879.2	12000.00
23	29540.92	168.65	0.770	0.30 ( 0.29)	0.97	53500.5	10100.00

=====  
=====  
END OF RATIONAL METHOD ANALYSIS



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S29- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 50-YR RM EV APRIL 2019 CCHIU \*  
\*\*\*\*\*

FILE NAME: RI50EV29.DAT  
TIME/DATE OF STUDY: 09:14 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 50.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.437
- 2) 10.00; 3.483
- 3) 15.00; 2.666
- 4) 20.00; 2.227
- 5) 25.00; 1.924
- 6) 30.00; 1.731
- 7) 40.00; 1.465
- 8) 50.00; 1.303
- 9) 60.00; 1.200
- 10) 90.00; 0.997
- 11) 120.00; 0.867
- 12) 180.00; 0.745
- 13) 360.00; 0.552
- 14) 1200.00; 0.243

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN CROSSFALL (FT)	TO STREET / SIDE / WAY	CROSSFALL (FT)	STREET-CROSSFALL (FT)	CURB HEIGHT (FT)	GUTTER WIDTH (FT)	GEOMETRIES LIP (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150	

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI50EV28.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23331.79	18.55	0.30 ( 0.25)	0.85	5261.5	300.00
2	26815.02	30.77	0.30 ( 0.26)	0.87	9102.6	50100.00
3	27374.32	33.27	0.30 ( 0.26)	0.88	9957.8	40200.00
4	28065.83	37.09	0.30 ( 0.27)	0.89	11434.9	390.00
5	29901.89	46.91	0.30 ( 0.28)	0.92	15176.6	40100.00
6	31224.61	56.22	0.30 ( 0.28)	0.93	18487.4	11801.00
7	33103.64	67.17	0.30 ( 0.28)	0.94	23071.2	11530.00
8	34116.19	71.62	0.30 ( 0.28)	0.95	25385.5	11701.00
9	34974.61	75.13	0.30 ( 0.29)	0.95	27457.5	11910.00
10	37546.36	85.49	0.30 ( 0.29)	0.96	34171.2	10800.00
11	38199.61	89.77	0.30 ( 0.29)	0.96	37116.5	11130.00
12	38189.85	99.37	0.30 ( 0.29)	0.97	42157.7	12410.00
13	37877.74	107.62	0.30 ( 0.29)	0.97	45896.8	11201.00
14	37569.03	112.56	0.30 ( 0.29)	0.97	47628.5	12201.00
15	36667.82	119.53	0.30 ( 0.29)	0.97	49485.7	12231.00
16	35507.47	127.23	0.30 ( 0.29)	0.97	51120.0	10400.00
17	34299.86	135.05	0.30 ( 0.29)	0.97	52415.1	12010.00
18	33218.28	140.90	0.30 ( 0.29)	0.97	52762.0	10210.00
19	32747.98	143.90	0.30 ( 0.29)	0.97	52879.2	12000.00
20	29540.92	168.65	0.30 ( 0.29)	0.97	53500.5	10100.00
TOTAL AREA (ACRES) =						53500.5

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23331.79	18.55	0.30 ( 0.25)	0.85	5261.5	300.00
2	26815.02	30.77	0.30 ( 0.26)	0.87	9102.6	50100.00
3	27374.32	33.27	0.30 ( 0.26)	0.88	9957.8	40200.00
4	28065.83	37.09	0.30 ( 0.27)	0.89	11434.9	390.00
5	29901.89	46.91	0.30 ( 0.28)	0.92	15176.6	40100.00
6	31224.61	56.22	0.30 ( 0.28)	0.93	18487.4	11801.00
7	33103.64	67.17	0.30 ( 0.28)	0.94	23071.2	11530.00
8	34116.19	71.62	0.30 ( 0.28)	0.95	25385.5	11701.00
9	34974.61	75.13	0.30 ( 0.29)	0.95	27457.5	11910.00
10	37546.36	85.49	0.30 ( 0.29)	0.96	34171.2	10800.00
11	38199.61	89.77	0.30 ( 0.29)	0.96	37116.5	11130.00
12	38189.85	99.37	0.30 ( 0.29)	0.97	42157.7	12410.00
13	37877.74	107.62	0.30 ( 0.29)	0.97	45896.8	11201.00

14	37569.03	112.56	0.30	( 0.29)	0.97	47628.5	12201.00
15	36667.82	119.53	0.30	( 0.29)	0.97	49485.7	12231.00
16	35507.47	127.23	0.30	( 0.29)	0.97	51120.0	10400.00
17	34299.86	135.05	0.30	( 0.29)	0.97	52415.1	12010.00
18	33218.28	140.90	0.30	( 0.29)	0.97	52762.0	10210.00
19	32747.98	143.90	0.30	( 0.29)	0.97	52879.2	12000.00
20	29540.92	168.65	0.30	( 0.29)	0.97	53500.5	10100.00

TOTAL AREA (ACRES) = 53500.5

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12901.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 240.00 DOWNSTREAM (FEET) = 216.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 3120.28 CHANNEL SLOPE = 0.0077  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 9.18  
CHANNEL FLOW THRU SUBAREA (CFS) = 38199.61  
FLOW VELOCITY (FEET/SEC.) = 16.92 FLOW DEPTH (FEET) = 9.18  
TRAVEL TIME (MIN.) = 3.07 Tc (MIN.) = 92.85  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12901.00 = 114915.99 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 92.85  
\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.985  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	2.60	0.30	0.100	56
COMMERCIAL	B	3.20	0.30	0.100	56
PUBLIC PARK	B	1.50	0.30	0.850	56
COMMERCIAL	B	5.60	0.30	0.100	56
PUBLIC PARK	B	6.50	0.30	0.850	56

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.409  
SUBAREA AREA (ACRES) = 19.40 SUBAREA RUNOFF (CFS) = 15.05  
EFFECTIVE AREA (ACRES) = 37135.91 AREA-AVERAGED Fm (INCH/HR) = 0.29  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA (ACRES) = 53519.9 PEAK FLOW RATE (CFS) = 38199.61  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 92.85  
\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.985  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	0.50	0.30	0.100	56
PUBLIC PARK	B	4.10	0.30	0.850	56
PUBLIC PARK	B	0.10	0.30	0.850	56
RESIDENTIAL ".4 DWELLING/ACRE"	B	1.60	0.30	0.900	56
RESIDENTIAL ".4 DWELLING/ACRE"	B	0.60	0.30	0.900	56
RESIDENTIAL ".4 DWELLING/ACRE"	B	1.00	0.30	0.900	56

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.823  
SUBAREA AREA (ACRES) = 7.90 SUBAREA RUNOFF (CFS) = 5.25  
EFFECTIVE AREA (ACRES) = 37143.81 AREA-AVERAGED Fm (INCH/HR) = 0.29  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA (ACRES) = 53527.8 PEAK FLOW RATE (CFS) = 38199.61  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 92.85  
\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.985  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL ".4 DWELLING/ACRE"	B	3.60	0.30	0.900	56
AGRICULTURAL FAIR COVER "ORCHARDS"	B	0.30	0.30	1.000	65
NATURAL POOR COVER "BARREN"	B	12.00	0.30	1.000	86
PUBLIC PARK	B	36.10	0.30	0.850	56
NATURAL FAIR COVER "GRASS"	B	15.90	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	1.50	0.30	1.000	69

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.917  
SUBAREA AREA (ACRES) = 69.40 SUBAREA RUNOFF (CFS) = 44.32  
EFFECTIVE AREA (ACRES) = 37213.21 AREA-AVERAGED Fm (INCH/HR) = 0.29  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA (ACRES) = 53597.2 PEAK FLOW RATE (CFS) = 38199.61  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 92.85

\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.985  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL FAIR COVER  
 "WOODLAND,GRASS" B 4.20 0.30 1.000 65  
 NATURAL FAIR COVER  
 "WOODLAND,GRASS" B 0.40 0.30 1.000 65  
 NATURAL FAIR COVER  
 "WOODLAND,GRASS" B 1.00 0.30 1.000 65  
 RESIDENTIAL  
 "5-7 DWELLINGS/ACRE" B 4.10 0.30 0.500 56  
 RESIDENTIAL  
 "5-7 DWELLINGS/ACRE" B 3.70 0.30 0.500 56  
 RESIDENTIAL  
 "5-7 DWELLINGS/ACRE" B 0.40 0.30 0.500 56  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.703  
 SUBAREA AREA (ACRES) = 13.80 SUBAREA RUNOFF (CFS) = 9.61  
 EFFECTIVE AREA (ACRES) = 37227.01 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA (ACRES) = 53611.0 PEAK FLOW RATE (CFS) = 38199.61  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 =====

MAINLINE Tc (MIN.) = 92.85  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.985  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 6.70 0.30 1.000 66  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 1.20 0.30 1.000 66  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 2.90 0.30 1.000 66  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 10.80 SUBAREA RUNOFF (CFS) = 6.65  
 EFFECTIVE AREA (ACRES) = 37237.81 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA (ACRES) = 53621.8 PEAK FLOW RATE (CFS) = 38199.61  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12901.00 TO NODE 12902.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM (FEET) = 216.00 DOWNSTREAM (FEET) = 215.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 122.04 CHANNEL SLOPE = 0.0082  
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT (FEET) = 9.02  
 CHANNEL FLOW THRU SUBAREA (CFS) = 38199.61  
 FLOW VELOCITY (FEET/SEC.) = 17.29 FLOW DEPTH (FEET) = 9.02  
 TRAVEL TIME (MIN.) = 0.12 Tc (MIN.) = 92.97  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115038.03 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 3 <<<<<  
 =====

PEAK FLOWRATE TABLE FILE NAME: E502XX50.DNA  
 MEMORY BANK # 3 DEFINED AS FOLLOWS:  
 STREAM Q Tc Fp (Fm) Ap Ae HEADWATER  
 NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE  
 1 66.04 11.15 0.30 ( 0.27) 0.91 28.7 50200.00  
 TOTAL AREA (ACRES) = 28.7

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<  
 =====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23331.79	22.31	2.087	0.30 ( 0.25)	0.85	5382.8	300.00
2	26815.02	34.36	1.615	0.30 ( 0.26)	0.87	9223.9	50100.00
3	27374.32	36.84	1.549	0.30 ( 0.26)	0.88	10079.1	40200.00
4	28065.83	40.63	1.455	0.30 ( 0.27)	0.89	11556.2	390.00
5	29901.89	50.37	1.299	0.30 ( 0.28)	0.92	15297.9	40100.00
6	31224.61	59.63	1.204	0.30 ( 0.28)	0.93	18608.7	11801.00
7	33103.64	70.52	1.129	0.30 ( 0.28)	0.94	23192.5	11530.00
8	34116.19	74.93	1.099	0.30 ( 0.28)	0.95	25506.8	11701.00
9	34974.61	78.41	1.075	0.30 ( 0.29)	0.95	27578.8	11910.00
10	37546.36	88.70	1.006	0.30 ( 0.29)	0.96	34292.5	10800.00
11	38199.61	92.97	0.984	0.30 ( 0.29)	0.96	37237.8	11130.00
12	38189.85	102.56	0.943	0.30 ( 0.29)	0.97	42279.0	12410.00
13	37877.74	110.82	0.907	0.30 ( 0.29)	0.97	46018.1	11201.00
14	37569.03	115.76	0.885	0.30 ( 0.29)	0.97	47749.8	12201.00
15	36667.82	122.77	0.861	0.30 ( 0.29)	0.97	49607.0	12231.00
16	35507.47	130.50	0.846	0.30 ( 0.29)	0.97	51241.3	10400.00
17	34299.86	138.36	0.830	0.30 ( 0.29)	0.97	52536.4	12010.00
18	33218.28	144.24	0.818	0.30 ( 0.29)	0.97	52883.3	10210.00
19	32747.98	147.26	0.812	0.30 ( 0.29)	0.97	53000.5	12000.00
20	29540.92	172.12	0.761	0.30 ( 0.29)	0.97	53621.8	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115038.03 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	66.04	11.15	3.296	0.30 ( 0.27)	0.91	28.7	50200.00

LONGEST FLOWPATH FROM NODE 50200.00 TO NODE 12902.00 = 1426.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	66.04	11.15	3.296	0.30 ( 0.27)	0.91	28.7	50200.00

1	19410.12	11.15	3.296	0.30 ( 0.25)	0.85	2718.5	50200.00
2	23371.43	22.31	2.087	0.30 ( 0.25)	0.85	5411.5	300.00
3	26844.34	34.36	1.615	0.30 ( 0.26)	0.87	9252.6	50100.00
4	27402.20	36.84	1.549	0.30 ( 0.26)	0.88	10107.8	40200.00
5	28091.65	40.63	1.455	0.30 ( 0.27)	0.89	11584.9	390.00
6	29924.30	50.37	1.299	0.30 ( 0.28)	0.92	15326.6	40100.00
7	31244.95	59.63	1.204	0.30 ( 0.28)	0.93	18637.4	11801.00
8	33122.34	70.52	1.129	0.30 ( 0.28)	0.94	23221.2	11530.00
9	34134.23	74.93	1.099	0.30 ( 0.28)	0.95	25535.5	11701.00
10	34992.14	78.41	1.075	0.30 ( 0.29)	0.95	27607.5	11910.00
11	37562.36	88.70	1.006	0.30 ( 0.29)	0.96	34321.2	10800.00
12	38215.14	92.97	0.984	0.30 ( 0.29)	0.96	37266.5	11130.00
13	38204.48	102.56	0.943	0.30 ( 0.29)	0.97	42307.7	12410.00
14	37891.59	110.82	0.907	0.30 ( 0.29)	0.97	46046.8	11201.00
15	37582.41	115.76	0.885	0.30 ( 0.29)	0.97	47778.5	12201.00
16	36680.67	122.77	0.861	0.30 ( 0.29)	0.97	49635.7	12231.00
17	35519.98	130.50	0.846	0.30 ( 0.29)	0.97	51270.0	10400.00
18	34312.02	138.36	0.830	0.30 ( 0.29)	0.97	52565.1	12010.00
19	33230.18	144.24	0.818	0.30 ( 0.29)	0.97	52912.0	10210.00
20	32759.75	147.26	0.812	0.30 ( 0.29)	0.97	53029.2	12000.00
21	29551.58	172.12	0.761	0.30 ( 0.29)	0.97	53650.5	10100.00

TOTAL AREA (ACRES) = 53650.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 38215.14 Tc (MIN.) = 92.965  
EFFECTIVE AREA (ACRES) = 37266.51 AREA-AVERAGED Fm (INCH/HR) = 0.29  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA (ACRES) = 53650.5  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115038.03 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: E503XX50.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	496.69	24.76	1.939	0.30 ( 0.30)	0.99	366.4	50300.00

TOTAL AREA (ACRES) = 366.4

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19410.12	11.15	3.296	0.30 ( 0.25)	0.85	2718.5	50200.00

2	23371.43	22.31	2.087	0.30 ( 0.25)	0.85	5411.5	300.00
3	26844.34	34.36	1.615	0.30 ( 0.26)	0.87	9252.6	50100.00
4	27402.20	36.84	1.549	0.30 ( 0.26)	0.88	10107.8	40200.00
5	28091.65	40.63	1.455	0.30 ( 0.27)	0.89	11584.9	390.00
6	29924.30	50.37	1.299	0.30 ( 0.28)	0.92	15326.6	40100.00
7	31244.95	59.63	1.204	0.30 ( 0.28)	0.93	18637.4	11801.00
8	33122.34	70.52	1.129	0.30 ( 0.28)	0.94	23221.2	11530.00
9	34134.23	74.93	1.099	0.30 ( 0.28)	0.95	25535.5	11701.00
10	34992.14	78.41	1.075	0.30 ( 0.29)	0.95	27607.5	11910.00
11	37562.36	88.70	1.006	0.30 ( 0.29)	0.96	34321.2	10800.00
12	38215.14	92.97	0.984	0.30 ( 0.29)	0.96	37266.5	11130.00
13	38204.48	102.56	0.943	0.30 ( 0.29)	0.97	42307.7	12410.00
14	37891.59	110.82	0.907	0.30 ( 0.29)	0.97	46046.8	11201.00
15	37582.41	115.76	0.885	0.30 ( 0.29)	0.97	47778.5	12201.00
16	36680.67	122.77	0.861	0.30 ( 0.29)	0.97	49635.7	12231.00
17	35519.98	130.50	0.846	0.30 ( 0.29)	0.97	51270.0	10400.00
18	34312.02	138.36	0.830	0.30 ( 0.29)	0.97	52565.1	12010.00
19	33230.18	144.24	0.818	0.30 ( 0.29)	0.97	52912.0	10210.00
20	32759.75	147.26	0.812	0.30 ( 0.29)	0.97	53029.2	12000.00
21	29551.58	172.12	0.761	0.30 ( 0.29)	0.97	53650.5	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115038.03 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	496.69	24.76	1.939	0.30 ( 0.30)	0.99	366.4	50300.00

LONGEST FLOWPATH FROM NODE 50300.00 TO NODE 12902.00 = 8614.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19818.40	11.15	3.296	0.30 ( 0.26)	0.86	2883.4	50200.00
2	23859.39	22.31	2.087	0.30 ( 0.26)	0.86	5741.6	300.00
3	24574.21	24.76	1.939	0.30 ( 0.26)	0.86	6558.9	50300.00
4	27243.19	34.36	1.615	0.30 ( 0.26)	0.87	9619.0	50100.00
5	27781.11	36.84	1.549	0.30 ( 0.26)	0.88	10474.2	40200.00
6	28442.05	40.63	1.455	0.30 ( 0.27)	0.89	11951.3	390.00
7	30227.67	50.37	1.299	0.30 ( 0.28)	0.92	15693.0	40100.00
8	31519.50	59.63	1.204	0.30 ( 0.28)	0.93	19003.8	11801.00
9	33374.21	70.52	1.129	0.30 ( 0.28)	0.94	23587.6	11530.00
10	34377.09	74.93	1.099	0.30 ( 0.28)	0.95	25901.9	11701.00
11	35227.87	78.41	1.075	0.30 ( 0.29)	0.95	27973.9	11910.00
12	37777.05	88.70	1.006	0.30 ( 0.29)	0.96	34687.6	10800.00
13	38423.29	92.97	0.984	0.30 ( 0.29)	0.96	37632.9	11130.00
14	38400.06	102.56	0.943	0.30 ( 0.29)	0.97	42674.1	12410.00
15	38076.35	110.82	0.907	0.30 ( 0.29)	0.97	46413.2	11201.00
16	37760.69	115.76	0.885	0.30 ( 0.29)	0.97	48144.9	12201.00
17	36851.71	122.77	0.861	0.30 ( 0.29)	0.97	50002.1	12231.00
18	35686.27	130.50	0.846	0.30 ( 0.29)	0.97	51636.4	10400.00
19	34473.48	138.36	0.830	0.30 ( 0.29)	0.97	52931.5	12010.00
20	33388.02	144.24	0.818	0.30 ( 0.29)	0.97	53278.4	10210.00
21	32915.73	147.26	0.812	0.30 ( 0.29)	0.97	53395.6	12000.00
22	29692.29	172.12	0.761	0.30 ( 0.29)	0.97	54016.9	10100.00

TOTAL AREA (ACRES) = 54016.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 38423.29 Tc (MIN.) = 92.965  
EFFECTIVE AREA (ACRES) = 37632.91 AREA-AVERAGED Fm (INCH/HR) = 0.29

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA (ACRES) = 54016.9  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115038.03 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 12902.00 TO NODE 12903.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 215.00 DOWNSTREAM(FEET) = 214.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 895.53 CHANNEL SLOPE = 0.0011  
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT(FEET) = 15.74  
 CHANNEL FLOW THRU SUBAREA(CFS) = 38423.29  
 FLOW VELOCITY(FEET/SEC.) = 8.76 FLOW DEPTH(FEET) = 15.74  
 TRAVEL TIME(MIN.) = 1.70 Tc(MIN.) = 94.67  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115933.56 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: E504XX50.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	123.35	17.17	0.30 (0.29)	0.97	70.5	50400.00
TOTAL AREA (ACRES) = 70.5						

\*\*\*\*\*

FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19818.40	13.24	2.954	0.30 (0.26)	0.86	2883.4	50200.00
2	23859.39	24.28	1.968	0.30 (0.26)	0.86	5741.6	300.00
3	24574.21	26.71	1.858	0.30 (0.26)	0.86	6558.9	50300.00
4	27243.19	36.25	1.565	0.30 (0.26)	0.87	9619.0	50100.00
5	27781.11	38.72	1.499	0.30 (0.26)	0.88	10474.2	40200.00
6	28442.05	42.50	1.425	0.30 (0.27)	0.89	11951.3	390.00
7	30227.67	52.21	1.280	0.30 (0.28)	0.92	15693.0	40100.00
8	31519.50	61.44	1.190	0.30 (0.28)	0.93	19003.8	11801.00
9	33374.21	72.30	1.117	0.30 (0.28)	0.94	23587.6	11530.00
10	34377.09	76.69	1.087	0.30 (0.28)	0.95	25901.9	11701.00
11	35227.87	80.17	1.064	0.30 (0.29)	0.95	27973.9	11910.00

12	37777.05	90.42	0.995	0.30 (0.29)	0.96	34687.6	10800.00
13	38423.29	94.67	0.977	0.30 (0.29)	0.96	37632.9	11130.00
14	38400.06	104.26	0.935	0.30 (0.29)	0.97	42674.1	12410.00
15	38076.35	112.53	0.899	0.30 (0.29)	0.97	46413.2	11201.00
16	37760.69	117.48	0.878	0.30 (0.29)	0.97	48144.9	12201.00
17	36851.71	124.49	0.858	0.30 (0.29)	0.97	50002.1	12231.00
18	35686.27	132.24	0.842	0.30 (0.29)	0.97	51636.4	10400.00
19	34473.48	140.12	0.826	0.30 (0.29)	0.97	52931.5	12010.00
20	33388.02	146.02	0.814	0.30 (0.29)	0.97	53278.4	10210.00
21	32915.73	149.04	0.808	0.30 (0.29)	0.97	53395.6	12000.00
22	29692.29	173.96	0.757	0.30 (0.29)	0.97	54016.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115933.56 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	123.35	17.17	2.476	0.30 (0.29)	0.97	70.5	50400.00

LONGEST FLOWPATH FROM NODE 50400.00 TO NODE 12903.00 = 3607.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	19934.34	13.24	2.954	0.30 (0.26)	0.86	2937.8	50200.00
2	21378.56	17.17	2.476	0.30 (0.26)	0.86	3970.2	50400.00
3	23954.07	24.28	1.968	0.30 (0.26)	0.86	5812.1	300.00
4	24662.69	26.71	1.858	0.30 (0.26)	0.86	6629.4	50300.00
5	27315.12	36.25	1.565	0.30 (0.26)	0.87	9689.5	50100.00
6	27849.34	38.72	1.499	0.30 (0.26)	0.88	10544.7	40200.00
7	28506.08	42.50	1.425	0.30 (0.27)	0.89	12021.8	390.00
8	30283.55	52.21	1.280	0.30 (0.28)	0.92	15763.5	40100.00
9	31570.31	61.44	1.190	0.30 (0.28)	0.93	19074.3	11801.00
10	33420.88	72.30	1.117	0.30 (0.28)	0.94	23658.1	11530.00
11	34422.07	76.69	1.087	0.30 (0.28)	0.95	25972.4	11701.00
12	35271.52	80.17	1.064	0.30 (0.29)	0.95	28044.4	11910.00
13	37816.84	90.42	0.995	0.30 (0.29)	0.96	34758.1	10800.00
14	38462.05	94.67	0.977	0.30 (0.29)	0.96	37703.4	11130.00
15	38436.47	104.26	0.935	0.30 (0.29)	0.97	42744.6	12410.00
16	38110.74	112.53	0.899	0.30 (0.29)	0.97	46483.7	11201.00
17	37793.87	117.48	0.878	0.30 (0.29)	0.97	48215.4	12201.00
18	36883.75	124.49	0.858	0.30 (0.29)	0.97	50072.6	12231.00
19	35717.42	132.24	0.842	0.30 (0.29)	0.97	51706.9	10400.00
20	34503.73	140.12	0.826	0.30 (0.29)	0.97	53002.0	12010.00
21	33417.60	146.02	0.814	0.30 (0.29)	0.97	53348.9	10210.00
22	32944.96	149.04	0.808	0.30 (0.29)	0.97	53466.1	12000.00
23	29718.66	173.96	0.757	0.30 (0.29)	0.97	54087.4	10100.00

TOTAL AREA (ACRES) = 54087.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 38462.05 Tc (MIN.) = 94.670  
 EFFECTIVE AREA (ACRES) = 37703.41 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA (ACRES) = 54087.4  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115933.56 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

```

=====
*****
FLOW PROCESS FROM NODE 12903.00 TO NODE 12904.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 214.00 DOWNSTREAM(FEET) = 213.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 767.57 CHANNEL SLOPE = 0.0013
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 15.10
CHANNEL FLOW THRU SUBAREA(CFS) = 38462.05
FLOW VELOCITY(FEET/SEC.) = 9.24 FLOW DEPTH(FEET) = 15.10
TRAVEL TIME(MIN.) = 1.38 Tc(MIN.) = 96.05
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116701.13 FEET.
*****
FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 15.1
-----
>>>>DEFINE MEMORY BANK # 3 <<<<
=====
PEAK FLOWRATE TABLE FILE NAME: 3B50EVRL.DNA
MEMORY BANK # 3 DEFINED AS FOLLOWS:
STREAM Q Tc Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 450.13 14.66 0.30( 0.13) 0.42 192.8 200.00
2 448.20 17.51 0.30( 0.13) 0.42 214.7 210.00
TOTAL AREA(ACRES) = 214.7
*****
FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 11
-----
>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<
=====
** MAIN STREAM CONFLUENCE DATA **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 19934.34 14.94 2.676 0.30( 0.26) 0.86 2937.8 50200.00
2 21378.56 18.83 2.330 0.30( 0.26) 0.86 3970.2 50400.00
3 23954.07 25.88 1.890 0.30( 0.26) 0.86 5812.1 300.00
4 24662.69 28.30 1.797 0.30( 0.26) 0.86 6629.4 50300.00
5 27315.12 37.79 1.524 0.30( 0.26) 0.87 9689.5 50100.00
6 27849.34 40.25 1.461 0.30( 0.26) 0.88 10544.7 40200.00
7 28506.08 44.02 1.400 0.30( 0.27) 0.89 12021.8 390.00
8 30283.55 53.70 1.265 0.30( 0.28) 0.92 15763.5 40100.00
9 31570.31 62.91 1.180 0.30( 0.28) 0.93 19074.3 11801.00
10 33420.88 73.74 1.107 0.30( 0.28) 0.94 23658.1 11530.00
11 34422.07 78.12 1.077 0.30( 0.28) 0.95 25972.4 11701.00
12 35271.52 81.59 1.054 0.30( 0.29) 0.95 28044.4 11910.00
13 37816.84 91.81 0.989 0.30( 0.29) 0.96 34758.1 10800.00
14 38462.05 96.05 0.971 0.30( 0.29) 0.96 37703.4 11130.00
15 38436.47 105.65 0.929 0.30( 0.29) 0.97 42744.6 12410.00
16 38110.74 113.91 0.893 0.30( 0.29) 0.97 46483.7 11201.00
17 37793.87 118.87 0.872 0.30( 0.29) 0.97 48215.4 12201.00
18 36883.75 125.90 0.855 0.30( 0.29) 0.97 50072.6 12231.00

```

```

19 35717.42 133.66 0.839 0.30( 0.29) 0.97 51706.9 10400.00
20 34503.73 141.55 0.823 0.30( 0.29) 0.97 53002.0 12010.00
21 33417.60 147.47 0.811 0.30( 0.29) 0.97 53348.9 10210.00
22 32944.96 150.50 0.805 0.30( 0.29) 0.97 53466.1 12000.00
23 29718.66 175.46 0.754 0.30( 0.29) 0.97 54087.4 10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116701.13 FEET.
** MEMORY BANK # 3 CONFLUENCE DATA **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 450.13 14.66 2.721 0.30( 0.13) 0.42 192.8 200.00
2 448.20 17.51 2.446 0.30( 0.13) 0.42 214.7 210.00
LONGEST FLOWPATH FROM NODE 210.00 TO NODE 12904.00 = 5961.00 FEET.
** PEAK FLOW RATE TABLE **
STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 20381.02 14.66 2.721 0.30( 0.25) 0.83 3075.9 200.00
2 20384.29 14.94 2.676 0.30( 0.25) 0.83 3132.7 50200.00
3 21335.88 17.51 2.446 0.30( 0.25) 0.83 3834.0 210.00
4 21804.34 18.83 2.330 0.30( 0.25) 0.83 4184.9 50400.00
5 24294.83 25.88 1.890 0.30( 0.25) 0.84 6026.8 300.00
6 24985.41 28.30 1.797 0.30( 0.25) 0.85 6844.1 50300.00
7 27585.14 37.79 1.524 0.30( 0.26) 0.86 9904.2 50100.00
8 28107.21 40.25 1.461 0.30( 0.26) 0.87 10759.4 40200.00
9 28752.17 44.02 1.400 0.30( 0.27) 0.88 12236.5 390.00
10 30503.55 53.70 1.265 0.30( 0.27) 0.91 15978.2 40100.00
11 31773.96 62.91 1.180 0.30( 0.28) 0.93 19289.0 11801.00
12 33610.36 73.74 1.107 0.30( 0.28) 0.94 23872.8 11530.00
13 34605.83 78.12 1.077 0.30( 0.28) 0.94 26187.1 11701.00
14 35450.75 81.59 1.054 0.30( 0.28) 0.95 28259.1 11910.00
15 37983.56 91.81 0.989 0.30( 0.29) 0.96 34972.8 10800.00
16 38625.21 96.05 0.971 0.30( 0.29) 0.96 37918.1 11130.00
17 38591.59 105.65 0.929 0.30( 0.29) 0.96 42959.3 12410.00
18 38258.95 113.91 0.893 0.30( 0.29) 0.97 46698.4 11201.00
19 37937.93 118.87 0.872 0.30( 0.29) 0.97 48430.1 12201.00
20 37024.55 125.90 0.855 0.30( 0.29) 0.97 50287.3 12231.00
21 35855.16 133.66 0.839 0.30( 0.29) 0.97 51921.6 10400.00
22 34638.38 141.55 0.823 0.30( 0.29) 0.97 53216.7 12010.00
23 33549.91 147.47 0.811 0.30( 0.29) 0.97 53563.6 10210.00
24 33076.09 150.50 0.805 0.30( 0.29) 0.97 53680.8 12000.00
25 29839.98 175.46 0.754 0.30( 0.29) 0.97 54302.1 10100.00
TOTAL AREA(ACRES) = 54302.1
COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
PEAK FLOW RATE(CFS) = 38625.21 Tc(MIN.) = 96.054
EFFECTIVE AREA(ACRES) = 37918.11 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
TOTAL AREA(ACRES) = 54302.1
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116701.13 FEET.
*****
FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 96.05
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.971

```

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	0.70	0.30	0.100	56
NATURAL FAIR COVER "GRASS"	B	20.00	0.30	1.000	69
NATURAL FAIR COVER "MEADOWS"	B	0.10	0.30	1.000	70
PUBLIC PARK	B	14.90	0.30	0.850	56
RESIDENTIAL ".4 DWELLING/ACRE"	B	2.60	0.30	0.900	56
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.80	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.920  
SUBAREA AREA(ACRES) = 39.10 SUBAREA RUNOFF(CFS) = 24.45  
EFFECTIVE AREA(ACRES) = 37957.21 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA(ACRES) = 54341.2 PEAK FLOW RATE(CFS) = 38625.21  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

\*\*\*\*\*  
MAINLINE Tc(MIN.) = 96.05  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.971  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	0.30	0.30	0.100	56
NATURAL FAIR COVER "OPEN BRUSH"	B	0.10	0.30	1.000	66
AGRICULTURAL FAIR COVER "ORCHARDS"	B	0.10	0.30	1.000	65
RESIDENTIAL ".4 DWELLING/ACRE"	B	1.70	0.30	0.900	56
NATURAL FAIR COVER "GRASS"	B	2.60	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	0.20	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.912  
SUBAREA AREA(ACRES) = 5.00 SUBAREA RUNOFF(CFS) = 3.14  
EFFECTIVE AREA(ACRES) = 37962.21 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA(ACRES) = 54346.2 PEAK FLOW RATE(CFS) = 38625.21  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

\*\*\*\*\*  
MAINLINE Tc(MIN.) = 96.05  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.971  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL FAIR COVER "ORCHARDS"	B	0.10	0.30	1.000	65
RESIDENTIAL ".4 DWELLING/ACRE"	B	2.60	0.30	0.900	56
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.20	0.30	1.000	65
NATURAL FAIR COVER "GRASS"	B	3.00	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.956  
SUBAREA AREA(ACRES) = 5.90 SUBAREA RUNOFF(CFS) = 3.63  
EFFECTIVE AREA(ACRES) = 37968.11 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA(ACRES) = 54352.1 PEAK FLOW RATE(CFS) = 38625.21  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

=====

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 54352.1 TC(MIN.) = 96.05  
EFFECTIVE AREA(ACRES) = 37968.11 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.960  
PEAK FLOW RATE(CFS) = 38625.21

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20381.02	14.66	2.721	0.30( 0.25)	0.83	3125.9	200.00
2	20384.29	14.94	2.676	0.30( 0.25)	0.83	3182.7	50200.00
3	21335.88	17.51	2.446	0.30( 0.25)	0.83	3884.0	210.00
4	21804.34	18.83	2.330	0.30( 0.25)	0.84	4234.9	50400.00
5	24294.83	25.88	1.890	0.30( 0.25)	0.84	6076.8	300.00
6	24985.41	28.30	1.797	0.30( 0.25)	0.85	6894.1	50300.00
7	27585.14	37.79	1.524	0.30( 0.26)	0.87	9954.2	50100.00
8	28107.21	40.25	1.461	0.30( 0.26)	0.87	10809.4	40200.00
9	28752.17	44.02	1.400	0.30( 0.27)	0.89	12286.5	390.00
10	30503.55	53.70	1.265	0.30( 0.27)	0.91	16028.2	40100.00
11	31773.96	62.91	1.180	0.30( 0.28)	0.93	19339.0	11801.00
12	33610.36	73.74	1.107	0.30( 0.28)	0.94	23922.8	11530.00
13	34605.83	78.12	1.077	0.30( 0.28)	0.94	26237.1	11701.00
14	35450.75	81.59	1.054	0.30( 0.28)	0.95	28309.1	11910.00
15	37983.56	91.81	0.989	0.30( 0.29)	0.96	35022.8	10800.00
16	38625.21	96.05	0.971	0.30( 0.29)	0.96	37968.1	11130.00
17	38591.59	105.65	0.929	0.30( 0.29)	0.96	43009.3	12410.00
18	38258.95	113.91	0.893	0.30( 0.29)	0.97	46748.4	11201.00
19	37937.93	118.87	0.872	0.30( 0.29)	0.97	48480.1	12201.00
20	37024.55	125.90	0.855	0.30( 0.29)	0.97	50337.3	12231.00
21	35855.16	133.66	0.839	0.30( 0.29)	0.97	51971.6	10400.00
22	34638.38	141.55	0.823	0.30( 0.29)	0.97	53266.7	12010.00
23	33549.91	147.47	0.811	0.30( 0.29)	0.97	53613.6	10210.00
24	33076.09	150.50	0.805	0.30( 0.29)	0.97	53730.8	12000.00
25	29839.98	175.46	0.754	0.30( 0.29)	0.97	54352.1	10100.00

=====

END OF RATIONAL METHOD ANALYSIS





\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S33- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 50-YR RM EV APRIL 2019 CCHIUI \*  
\*\*\*\*\*

FILE NAME: RI50EV33.DAT  
TIME/DATE OF STUDY: 09:14 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 50.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.329
- 2) 10.00; 3.431
- 3) 15.00; 2.636
- 4) 20.00; 2.205
- 5) 25.00; 1.909
- 6) 30.00; 1.717
- 7) 40.00; 1.455
- 8) 50.00; 1.293
- 9) 60.00; 1.185
- 10) 90.00; 0.982
- 11) 120.00; 0.852
- 12) 180.00; 0.728
- 13) 360.00; 0.537
- 14) 1200.00; 0.235

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL: IN- / OUT-/PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13112.00 TO NODE 13222.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: S31X50.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2838.09	34.69	0.30 ( 0.24)	0.81	2526.1	13100.00
2	2813.56	59.31	0.30 ( 0.24)	0.81	3777.1	13000.00
3	2759.78	61.54	0.30 ( 0.24)	0.81	3796.8	13010.00
TOTAL AREA (ACRES) =						3796.8

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13221.00 TO NODE 13222.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: S32X50.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1294.02	32.85	0.30 ( 0.25)	0.83	1118.5	13210.00
2	1295.27	33.25	0.30 ( 0.25)	0.83	1127.6	13200.00
TOTAL AREA (ACRES) =						1127.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13221.00 TO NODE 13222.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2838.09	34.69	0.30 ( 0.24)	0.81	2526.1	13100.00
2	2813.56	59.31	0.30 ( 0.24)	0.81	3777.1	13000.00
3	2759.78	61.54	0.30 ( 0.24)	0.81	3796.8	13010.00
TOTAL AREA (ACRES) =						3796.8

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13112.00 TO NODE 13222.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2838.09	34.69	1.594	0.30 ( 0.24)	0.81	2526.1	13100.00
2	2813.56	59.31	1.192	0.30 ( 0.24)	0.81	3777.1	13000.00
3	2759.78	61.54	1.175	0.30 ( 0.24)	0.81	3796.8	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13222.00 = 32126.49 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1294.02	32.85	1.642	0.30 ( 0.25)	0.83	1118.5	13210.00
2	1295.27	33.25	1.632	0.30 ( 0.25)	0.83	1127.6	13200.00

LONGEST FLOWPATH FROM NODE 13200.00 TO NODE 13222.00 = 16821.05 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4077.65	32.85	1.642	0.30 ( 0.24)	0.82	3511.0	13210.00
2	4091.65	33.25	1.632	0.30 ( 0.24)	0.82	3549.2	13200.00
3	4098.16	34.69	1.594	0.30 ( 0.24)	0.82	3653.7	13100.00
4	3697.52	59.31	1.192	0.30 ( 0.24)	0.81	4904.7	13000.00
5	3627.04	61.54	1.175	0.30 ( 0.24)	0.81	4924.4	13010.00

TOTAL AREA (ACRES) = 4924.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 4098.16 Tc(MIN.) = 34.689  
EFFECTIVE AREA(ACRES) = 3653.73 AREA-AVERAGED Fm(INCH/HR) = 0.24  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82  
TOTAL AREA (ACRES) = 4924.4  
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13222.00 = 32126.49 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13222.00 TO NODE 13222.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13222.00 TO NODE 13222.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13222.00 TO NODE 13301.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 427.51 DOWNSTREAM(FEET) = 382.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 2533.33 CHANNEL SLOPE = 0.0180  
GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\* ESTIMATED CHANNEL HEIGHT(FEET) = 5.04  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.506  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	1.40	0.30	0.100	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	15.60	0.30	1.000	66
RESIDENTIAL					
"3-4 DWELLINGS/ACRE"	B	0.10	0.30	0.600	56

AGRICULTURAL POOR COVER

"ROW CROPS,CONTOURED"	B	5.30	0.30	1.000	79
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86
COMMERCIAL	B	22.60	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.521

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 4125.61

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.57

AVERAGE FLOW DEPTH(FEET) = 5.04 TRAVEL TIME(MIN.) = 3.36

Tc(MIN.) = 38.05

SUBAREA AREA(ACRES) = 45.20 SUBAREA RUNOFF(CFS) = 54.91

EFFECTIVE AREA(ACRES) = 3698.93 AREA-AVERAGED Fm(INCH/HR) = 0.24

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81

TOTAL AREA (ACRES) = 4969.6 PEAK FLOW RATE(CFS) = 4203.54

GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 5.09

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 5.09 FLOW VELOCITY(FEET/SEC.) = 12.64

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4194.79	36.22	1.554	0.30 ( 0.24)	0.81	3556.2	13210.00
2	4206.09	36.62	1.544	0.30 ( 0.24)	0.81	3594.4	13200.00
3	4203.54	38.05	1.506	0.30 ( 0.24)	0.81	3698.9	13100.00
4	4113.27	62.78	1.166	0.30 ( 0.24)	0.81	4949.9	13000.00
5	4061.84	65.03	1.151	0.30 ( 0.24)	0.81	4969.6	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 4206.09 Tc(MIN.) = 36.62

AREA-AVERAGED Fm(INCH/HR) = 0.24 AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.81 EFFECTIVE AREA(ACRES) = 3594.44

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 36.62

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.544

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	1.00	0.30	1.000	79
NATURAL POOR COVER					
"BARREN"	B	0.50	0.30	1.000	86
COMMERCIAL	B	7.40	0.30	0.100	56

AGRICULTURAL POOR COVER

"ROW CROPS,CONTOURED" B 4.70 0.30 1.000 79

NATURAL FAIR COVER

"WOODLAND,GRASS" B 2.90 0.30 1.000 65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.596

SUBAREA AREA(ACRES) = 16.50 SUBAREA RUNOFF(CFS) = 20.27

EFFECTIVE AREA (ACRES) = 3610.94 AREA-AVERAGED Fm (INCH/HR) = 0.24  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81  
TOTAL AREA (ACRES) = 4986.1 PEAK FLOW RATE (CFS) = 4226.36

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 36.62  
\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.544  
SUBAREA LOSS RATE DATA (AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
NATURAL POOR COVER  
"BARREN" B 1.30 0.30 1.000 86  
COMMERCIAL B 0.20 0.30 0.100 56  
AGRICULTURAL POOR COVER  
"ROW CROPS, CONTOURED" B 5.30 0.30 1.000 79  
NATURAL FAIR COVER  
"WOODLAND, GRASS" B 0.30 0.30 1.000 65  
NATURAL FAIR COVER  
"CHAPARRAL, BROADLEAF" B 0.20 0.30 1.000 63  
NATURAL FAIR COVER  
"OPEN BRUSH" B 0.60 0.30 1.000 66  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.977  
SUBAREA AREA (ACRES) = 7.90 SUBAREA RUNOFF (CFS) = 8.89  
EFFECTIVE AREA (ACRES) = 3618.84 AREA-AVERAGED Fm (INCH/HR) = 0.24  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81  
TOTAL AREA (ACRES) = 4994.0 PEAK FLOW RATE (CFS) = 4235.25

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 36.62  
\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.544  
SUBAREA LOSS RATE DATA (AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
AGRICULTURAL POOR COVER  
"ROW CROPS, CONTOURED" B 4.30 0.30 1.000 79  
NATURAL FAIR COVER  
"WOODLAND, GRASS" B 0.80 0.30 1.000 65  
NATURAL FAIR COVER  
"CHAPARRAL, BROADLEAF" B 1.10 0.30 1.000 63  
NATURAL FAIR COVER  
"OPEN BRUSH" B 6.90 0.30 1.000 66  
AGRICULTURAL POOR COVER  
"ROW CROPS, CONTOURED" B 7.90 0.30 1.000 79  
NATURAL FAIR COVER  
"WOODLAND, GRASS" B 1.00 0.30 1.000 65  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 22.00 SUBAREA RUNOFF (CFS) = 24.62  
EFFECTIVE AREA (ACRES) = 3640.84 AREA-AVERAGED Fm (INCH/HR) = 0.24

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81  
TOTAL AREA (ACRES) = 5016.0 PEAK FLOW RATE (CFS) = 4259.87

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 36.62  
\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.544  
SUBAREA LOSS RATE DATA (AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
NATURAL FAIR COVER  
"OPEN BRUSH" B 0.40 0.30 1.000 66  
AGRICULTURAL POOR COVER  
"ROW CROPS, CONTOURED" B 14.60 0.30 1.000 79  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 15.00 SUBAREA RUNOFF (CFS) = 16.79  
EFFECTIVE AREA (ACRES) = 3655.84 AREA-AVERAGED Fm (INCH/HR) = 0.24  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81  
TOTAL AREA (ACRES) = 5031.0 PEAK FLOW RATE (CFS) = 4276.66

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 31100.00 TO NODE 31101.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH (FEET) = 317.00  
ELEVATION DATA: UPSTREAM (FEET) = 801.00 DOWNSTREAM (FEET) = 685.00

Tc = K \* [(LENGTH \*\* 3.00) / (ELEVATION CHANGE)] \*\* 0.20  
SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 8.641  
\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 3.947  
SUBAREA Tc AND LOSS RATE DATA (AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)  
NATURAL FAIR COVER  
"CHAPARRAL, BROADLEAF" B 0.50 0.30 1.000 63 8.64  
NATURAL FAIR COVER  
"OPEN BRUSH" B 0.30 0.30 1.000 66 8.64  
NATURAL FAIR COVER  
"OPEN BRUSH" B 0.30 0.30 1.000 66 8.64  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA RUNOFF (CFS) = 3.61  
TOTAL AREA (ACRES) = 1.10 PEAK FLOW RATE (CFS) = 3.61

\*\*\*\*\*

FLOW PROCESS FROM NODE 31101.00 TO NODE 31102.00 IS CODE = 51

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<  
-----

ELEVATION DATA: UPSTREAM(FEET) = 685.00 DOWNSTREAM(FEET) = 655.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 135.00 CHANNEL SLOPE = 0.2222  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 3.823

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	B	0.50	0.30	1.000	63
NATURAL FAIR COVER "OPEN BRUSH"	B	0.10	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	0.70	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5.67  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.90  
AVERAGE FLOW DEPTH(FEET) = 0.52 TRAVEL TIME(MIN.) = 0.33  
Tc(MIN.) = 8.97  
SUBAREA AREA(ACRES) = 1.30 SUBAREA RUNOFF(CFS) = 4.12  
EFFECTIVE AREA(ACRES) = 2.40 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 2.4 PEAK FLOW RATE(CFS) = 7.61

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.58 FLOW VELOCITY(FEET/SEC.) = 7.42  
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31102.00 = 452.00 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 31102.00 TO NODE 31103.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<  
-----

ELEVATION DATA: UPSTREAM(FEET) = 655.00 DOWNSTREAM(FEET) = 630.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 203.00 CHANNEL SLOPE = 0.1232  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 10.00  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 3.665

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	B	0.30	0.30	1.000	63
NATURAL FAIR COVER "OPEN BRUSH"	B	0.10	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	1.90	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 11.09  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.13  
AVERAGE FLOW DEPTH(FEET) = 0.67 TRAVEL TIME(MIN.) = 0.42

Tc(MIN.) = 9.38  
SUBAREA AREA(ACRES) = 2.30 SUBAREA RUNOFF(CFS) = 6.97  
EFFECTIVE AREA(ACRES) = 4.70 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 4.7 PEAK FLOW RATE(CFS) = 14.24

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.74 FLOW VELOCITY(FEET/SEC.) = 8.60  
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31103.00 = 655.00 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 31103.00 TO NODE 31104.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<  
-----

ELEVATION DATA: UPSTREAM(FEET) = 630.00 DOWNSTREAM(FEET) = 605.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 321.00 CHANNEL SLOPE = 0.0779  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 3.395

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL FAIR COVER "OPEN BRUSH"	B	1.10	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	2.50	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 19.25  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.36  
AVERAGE FLOW DEPTH(FEET) = 1.00 TRAVEL TIME(MIN.) = 0.84  
Tc(MIN.) = 10.22

SUBAREA AREA(ACRES) = 3.60 SUBAREA RUNOFF(CFS) = 10.03  
EFFECTIVE AREA(ACRES) = 8.30 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 8.3 PEAK FLOW RATE(CFS) = 23.12

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.08 FLOW VELOCITY(FEET/SEC.) = 6.63  
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31104.00 = 976.00 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 31104.00 TO NODE 31105.00 IS CODE = 51  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<  
-----

ELEVATION DATA: UPSTREAM(FEET) = 605.00 DOWNSTREAM(FEET) = 585.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 288.00 CHANNEL SLOPE = 0.0694  
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 3.284

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL FAIR COVER					
--------------------	--	--	--	--	--

"CHAPARRAL,BROADLEAF" B 0.70 0.30 1.000 63  
 NATURAL FAIR COVER  
 "CHAPARRAL,BROADLEAF" B 0.60 0.30 1.000 63  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 3.00 0.30 1.000 66  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 2.10 0.30 1.000 66  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 31.72  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.87  
 AVERAGE FLOW DEPTH(FEET) = 1.24 TRAVEL TIME(MIN.) = 0.70  
 Tc(MIN.) = 10.92  
 SUBAREA AREA(ACRES) = 6.40 SUBAREA RUNOFF(CFS) = 17.19  
 EFFECTIVE AREA(ACRES) = 14.70 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 14.7 PEAK FLOW RATE(CFS) = 39.48

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.35 FLOW VELOCITY(FEET/SEC.) = 7.27  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31105.00 = 1264.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31105.00 TO NODE 31106.00 IS CODE = 51

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

-----  
 ELEVATION DATA: UPSTREAM(FEET) = 585.00 DOWNSTREAM(FEET) = 560.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 344.00 CHANNEL SLOPE = 0.0727  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 3.170  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.60	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	2.80	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.60	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.10	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.60	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	4.10	0.30	1.000	66

-----  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 53.43  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.00  
 AVERAGE FLOW DEPTH(FEET) = 1.49 TRAVEL TIME(MIN.) = 0.72  
 Tc(MIN.) = 11.64

-----  
 SUBAREA AREA(ACRES) = 10.80 SUBAREA RUNOFF(CFS) = 27.90  
 EFFECTIVE AREA(ACRES) = 25.50 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 25.5 PEAK FLOW RATE(CFS) = 65.87

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.62 FLOW VELOCITY(FEET/SEC.) = 8.36  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31106.00 = 1608.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31106.00 TO NODE 31107.00 IS CODE = 51

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

-----  
 ELEVATION DATA: UPSTREAM(FEET) = 560.00 DOWNSTREAM(FEET) = 530.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 619.00 CHANNEL SLOPE = 0.0485  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.956  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.80	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	1.90	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.50	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	8.20	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.70	0.30	1.000	66

-----  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 83.93  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.67  
 AVERAGE FLOW DEPTH(FEET) = 1.91 TRAVEL TIME(MIN.) = 1.35  
 Tc(MIN.) = 12.99

-----  
 SUBAREA AREA(ACRES) = 15.10 SUBAREA RUNOFF(CFS) = 36.10  
 EFFECTIVE AREA(ACRES) = 40.60 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 40.6 PEAK FLOW RATE(CFS) = 97.06

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 2.02 FLOW VELOCITY(FEET/SEC.) = 7.94  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31107.00 = 2227.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31107.00 TO NODE 31108.00 IS CODE = 51

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

-----  
 ELEVATION DATA: UPSTREAM(FEET) = 530.00 DOWNSTREAM(FEET) = 515.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 377.00 CHANNEL SLOPE = 0.0398  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.827  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					

NATURAL FAIR COVER  
 "CHAPARRAL,BROADLEAF" B 0.50 0.30 1.000 63  
 NATURAL FAIR COVER  
 "CHAPARRAL,BROADLEAF" B 6.50 0.30 1.000 63  
 NATURAL FAIR COVER  
 "CHAPARRAL,BROADLEAF" B 1.30 0.30 1.000 63  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 1.10 0.30 1.000 66  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 5.50 0.30 1.000 66  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 3.40 0.30 1.000 66  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 117.88  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.74  
 AVERAGE FLOW DEPTH(FEET) = 2.25 TRAVEL TIME(MIN.) = 0.81  
 Tc(MIN.) = 13.80  
 SUBAREA AREA(ACRES) = 18.30 SUBAREA RUNOFF(CFS) = 41.62  
 EFFECTIVE AREA(ACRES) = 58.90 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 58.9 PEAK FLOW RATE(CFS) = 133.97

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 2.36 FLOW VELOCITY(FEET/SEC.) = 8.00  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31108.00 = 2604.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31108.00 TO NODE 31109.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 515.00 DOWNSTREAM(FEET) = 490.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 520.00 CHANNEL SLOPE = 0.0481  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.671

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.70	0.30	1.000	63
NATURAL FAIR COVER					
"GRASS"	B	2.20	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	3.10	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.90	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	7.40	0.30	1.000	63
NATURAL FAIR COVER					
"GRASS"	B	0.30	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 149.55  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.82  
 AVERAGE FLOW DEPTH(FEET) = 2.38 TRAVEL TIME(MIN.) = 0.98

Tc(MIN.) = 14.78  
 SUBAREA AREA(ACRES) = 14.60 SUBAREA RUNOFF(CFS) = 31.15  
 EFFECTIVE AREA(ACRES) = 73.50 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 73.5 PEAK FLOW RATE(CFS) = 156.84

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.42 FLOW VELOCITY(FEET/SEC.) = 8.92  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31109.00 = 3124.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31109.00 TO NODE 31109.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 14.78

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.671

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	11.40	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	8.90	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	1.90	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	9.20	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	1.40	0.30	1.000	65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000					
SUBAREA AREA(ACRES) = 32.80					
SUBAREA RUNOFF(CFS) = 69.99					
EFFECTIVE AREA(ACRES) = 106.30					
AREA-AVERAGED Fm(INCH/HR) = 0.30					
AREA-AVERAGED Ap = 1.00					
TOTAL AREA(ACRES) = 106.3					
PEAK FLOW RATE(CFS) = 226.83					

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31109.00 TO NODE 31110.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 490.00 DOWNSTREAM(FEET) = 432.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1420.00 CHANNEL SLOPE = 0.0408  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.435

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	0.80	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.60	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.10	0.30	0.900	56
AGRICULTURAL POOR COVER					

"ROW CROPS, CONTOURED" B 1.30 0.30 1.000 79  
 NATURAL FAIR COVER  
 "WOODLAND, GRASS" B 4.00 0.30 1.000 65  
 NATURAL FAIR COVER  
 "CHAPARRAL, BROADLEAF" B 1.50 0.30 1.000 63  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 234.81  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 9.29  
 AVERAGE FLOW DEPTH (FEET) = 2.90 TRAVEL TIME (MIN.) = 2.55  
 Tc (MIN.) = 17.33  
 SUBAREA AREA (ACRES) = 8.30 SUBAREA RUNOFF (CFS) = 15.95  
 EFFECTIVE AREA (ACRES) = 114.60 AREA-AVERAGED Fm (INCH/HR) = 0.30  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA (ACRES) = 114.6 PEAK FLOW RATE (CFS) = 226.83  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 2.87 FLOW VELOCITY (FEET/SEC.) = 9.21  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31110.00 = 4544.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31110.00 TO NODE 31110.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 =====

MAINLINE Tc (MIN.) = 17.33  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 2.435  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	0.30	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	9.60	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.40	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	6.20	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	3.90	0.30	1.000	65
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	1.40	0.30	1.000	79

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.998  
 SUBAREA AREA (ACRES) = 21.80 SUBAREA RUNOFF (CFS) = 41.91  
 EFFECTIVE AREA (ACRES) = 136.40 AREA-AVERAGED Fm (INCH/HR) = 0.30  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA (ACRES) = 136.4 PEAK FLOW RATE (CFS) = 262.16

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31110.00 TO NODE 13301.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<  
 =====

ELEVATION DATA: UPSTREAM (FEET) = 432.00 DOWNSTREAM (FEET) = 382.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1847.00 CHANNEL SLOPE = 0.0271

CHANNEL BASE (FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH (FEET) = 10.00  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 2.144  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	4.90	0.30	1.000	86
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	1.50	0.30	1.000	79
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.60	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	2.50	0.30	1.000	79
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	5.30	0.30	1.000	79
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	3.30	0.30	1.000	79

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.997  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 277.19  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.30  
 AVERAGE FLOW DEPTH (FEET) = 3.34 TRAVEL TIME (MIN.) = 3.71  
 Tc (MIN.) = 21.04  
 SUBAREA AREA (ACRES) = 18.10 SUBAREA RUNOFF (CFS) = 30.05  
 EFFECTIVE AREA (ACRES) = 154.50 AREA-AVERAGED Fm (INCH/HR) = 0.30  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA (ACRES) = 154.5 PEAK FLOW RATE (CFS) = 262.16  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 3.27 FLOW VELOCITY (FEET/SEC.) = 8.18  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 13301.00 = 6391.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<  
 =====

\*\* MAIN STREAM CONFLUENCE DATA \*\*  

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	262.16	21.04	2.144	0.30 ( 0.30)	1.00	154.5	31100.00

LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 13301.00 = 6391.00 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*  

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4265.94	36.22	1.554	0.30 ( 0.24)	0.81	3617.6	13210.00
2	4276.66	36.62	1.544	0.30 ( 0.24)	0.81	3655.8	13200.00
3	4272.04	38.05	1.506	0.30 ( 0.24)	0.81	3760.3	13100.00
4	4162.98	62.78	1.166	0.30 ( 0.24)	0.81	5011.3	13000.00
5	4110.71	65.03	1.151	0.30 ( 0.24)	0.81	5031.0	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

\*\* PEAK FLOW RATE TABLE \*\*  

STREAM	Q	Tc	Intensity	Fp (Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	---------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	3854.88	21.04	2.144	0.30 ( 0.25)	0.83	2255.8 31100.00
2	4444.28	36.22	1.554	0.30 ( 0.25)	0.82	3772.1 13210.00
3	4453.52	36.62	1.544	0.30 ( 0.25)	0.82	3810.3 13200.00
4	4443.56	38.05	1.506	0.30 ( 0.25)	0.82	3914.8 13100.00
5	4286.17	62.78	1.166	0.30 ( 0.24)	0.82	5165.8 13000.00
6	4231.73	65.03	1.151	0.30 ( 0.24)	0.82	5185.5 13010.00
TOTAL AREA (ACRES) =			5185.5			

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 4453.52 Tc (MIN.) = 36.616  
EFFECTIVE AREA (ACRES) = 3810.34 AREA-AVERAGED Fm (INCH/HR) = 0.25  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82  
TOTAL AREA (ACRES) = 5185.5  
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 1 <<<<<<  
=====

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13301.00 TO NODE 13302.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<<  
=====

ELEVATION DATA: UPSTREAM (FEET) = 382.00 DOWNSTREAM (FEET) = 375.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1141.09 CHANNEL SLOPE = 0.0061  
GIVEN CHANNEL BASE (FEET) = 50.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 7.07  
\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.487  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	9.40	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 4458.54  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.86  
AVERAGE FLOW DEPTH (FEET) = 7.07 TRAVEL TIME (MIN.) = 2.15  
Tc (MIN.) = 38.76  
SUBAREA AREA (ACRES) = 9.40 SUBAREA RUNOFF (CFS) = 10.05  
EFFECTIVE AREA (ACRES) = 3819.74 AREA-AVERAGED Fm (INCH/HR) = 0.25  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82  
TOTAL AREA (ACRES) = 5194.9 PEAK FLOW RATE (CFS) = 4453.52  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
GIVEN CHANNEL BASE (FEET) = 50.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 7.06

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 7.06 FLOW VELOCITY (FEET/SEC.) = 8.86  
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13302.00 = 35800.91 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3854.88	23.28	2.011	0.30 ( 0.25)	0.83	2265.2	31100.00
2	4444.28	38.37	1.498	0.30 ( 0.25)	0.82	3781.5	13210.00
3	4453.52	38.76	1.487	0.30 ( 0.25)	0.82	3819.7	13200.00
4	4443.56	40.20	1.452	0.30 ( 0.25)	0.82	3924.2	13100.00
5	4286.17	64.96	1.151	0.30 ( 0.24)	0.82	5175.2	13000.00
6	4231.73	67.21	1.136	0.30 ( 0.24)	0.82	5194.9	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 4453.52 Tc (MIN.) = 38.76  
AREA-AVERAGED Fm (INCH/HR) = 0.25 AREA-AVERAGED Fp (INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.82 EFFECTIVE AREA (ACRES) = 3819.74

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<  
=====

MAINLINE Tc (MIN.) = 38.76  
\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.487  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	13.80	0.30	1.000	86
NATURAL POOR COVER					
"BARREN"	B	2.60	0.30	1.000	86
COMMERCIAL	B	1.10	0.30	0.100	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	3.50	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	6.90	0.30	1.000	79
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.952  
SUBAREA AREA (ACRES) = 28.10 SUBAREA RUNOFF (CFS) = 30.39  
EFFECTIVE AREA (ACRES) = 3847.84 AREA-AVERAGED Fm (INCH/HR) = 0.25  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82  
TOTAL AREA (ACRES) = 5223.0 PEAK FLOW RATE (CFS) = 4453.52  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<  
=====

MAINLINE Tc (MIN.) = 38.76  
\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.487  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	0.10	0.30	1.000	79
COMMERCIAL	B	0.10	0.30	0.100	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	2.40	0.30	0.900	56



AGRICULTURAL POOR COVER  
 "ROW CROPS,CONTOURED" B 0.50 0.30 1.000 79  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.894  
 SUBAREA AREA(ACRES) = 3.10 SUBAREA RUNOFF(CFS) = 3.40  
 EFFECTIVE AREA(ACRES) = 3850.94 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82  
 TOTAL AREA(ACRES) = 5226.1 PEAK FLOW RATE(CFS) = 4453.52  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 38.76  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.487  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	0.10	0.30	1.000	86
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.60	0.30	1.000	66
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	3.10	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.40	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.20	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	13.80	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 20.20 SUBAREA RUNOFF(CFS) = 21.59  
 EFFECTIVE AREA(ACRES) = 3871.14 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82  
 TOTAL AREA(ACRES) = 5246.3 PEAK FLOW RATE(CFS) = 4453.52  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 38.76  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.487  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	34.60	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	2.40	0.30	1.000	65
NATURAL FAIR COVER					
"OPEN BRUSH"	B	22.60	0.30	1.000	66
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	11.60	0.30	1.000	79

APARTMENTS B 0.40 0.30 0.200 56  
 NATURAL FAIR COVER  
 "CHAPARRAL,BROADLEAF" B 4.80 0.30 1.000 63  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.996  
 SUBAREA AREA(ACRES) = 76.40 SUBAREA RUNOFF(CFS) = 81.73  
 EFFECTIVE AREA(ACRES) = 3947.54 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA(ACRES) = 5322.7 PEAK FLOW RATE(CFS) = 4453.52  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 38.76  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.487  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	1.60	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	46.40	0.30	1.000	66
RESIDENTIAL					
"11+ DWELLINGS/ACRE"	B	0.10	0.30	0.200	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	60.70	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	5.80	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999  
 SUBAREA AREA(ACRES) = 114.60 SUBAREA RUNOFF(CFS) = 122.49  
 EFFECTIVE AREA(ACRES) = 4062.14 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA(ACRES) = 5437.3 PEAK FLOW RATE(CFS) = 4526.41

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13302.00 TO NODE 13303.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 375.00 DOWNSTREAM(FEET) = 355.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2193.96 CHANNEL SLOPE = 0.0091  
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 6.40  
 CHANNEL FLOW THRU SUBAREA(CFS) = 4526.41  
 FLOW VELOCITY(FEET/SEC.) = 10.22 FLOW DEPTH(FEET) = 6.40  
 TRAVEL TIME(MIN.) = 3.58 Tc(MIN.) = 42.34  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13303.00 = 37994.87 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3968.19	27.00	1.832	0.30( 0.25)	0.84	2507.6	31100.00

2	4521.30	41.94	1.424	0.30	( 0.25)	0.83	4023.9	13210.00
3	4526.41	42.34	1.417	0.30	( 0.25)	0.83	4062.1	13200.00
4	4509.95	43.77	1.394	0.30	( 0.25)	0.83	4166.6	13100.00
5	4408.64	68.56	1.127	0.30	( 0.25)	0.82	5417.6	13000.00
6	4350.32	70.83	1.112	0.30	( 0.25)	0.82	5437.3	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 4526.41 Tc(MIN.) = 42.34  
 AREA-AVERAGED Fm(INCH/HR) = 0.25 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.83 EFFECTIVE AREA(ACRES) = 4062.14

\*\*\*\*\*

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 42.34  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.417  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.40	0.30	1.000	65
NATURAL POOR COVER					
"BARREN"	B	0.80	0.30	1.000	86
COMMERCIAL	B	1.40	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	2.60	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.20	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.834  
 SUBAREA AREA(ACRES) = 7.60 SUBAREA RUNOFF(CFS) = 7.98  
 EFFECTIVE AREA(ACRES) = 4069.74 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA(ACRES) = 5444.9 PEAK FLOW RATE(CFS) = 4526.41  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 42.34  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.417  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	3.10	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	3.40	0.30	1.000	65
NATURAL POOR COVER					
"BARREN"	B	0.50	0.30	1.000	86
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.20	0.30	1.000	63
COMMERCIAL	B	3.60	0.30	0.100	56

NATURAL FAIR COVER  
 "GRASS" B 4.00 0.30 1.000 69  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.781  
 SUBAREA AREA(ACRES) = 14.80 SUBAREA RUNOFF(CFS) = 15.75  
 EFFECTIVE AREA(ACRES) = 4084.54 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA(ACRES) = 5459.7 PEAK FLOW RATE(CFS) = 4526.41  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 42.34  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.417  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	14.60	0.30	1.000	66
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	6.30	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	3.70	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 24.60 SUBAREA RUNOFF(CFS) = 24.73  
 EFFECTIVE AREA(ACRES) = 4109.14 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA(ACRES) = 5484.3 PEAK FLOW RATE(CFS) = 4526.41  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 42.34  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.417  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	0.50	0.30	1.000	86
COMMERCIAL	B	0.30	0.30	0.100	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.20	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.80	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	1.60	0.30	1.000	79
NATURAL POOR COVER					
"BARREN"	B	31.90	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.990  
 SUBAREA AREA(ACRES) = 35.30 SUBAREA RUNOFF(CFS) = 35.59

EFFECTIVE AREA(ACRES) = 4144.44 AREA-AVERAGED Fm(INCH/HR) = 0.25  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
TOTAL AREA(ACRES) = 5519.6 PEAK FLOW RATE(CFS) = 4526.41  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 42.34  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.417  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	1.70	0.30	0.100	56
NATURAL FAIR COVER "OPEN BRUSH"	B	0.30	0.30	1.000	66
RESIDENTIAL ".4 DWELLING/ACRE"	B	2.60	0.30	0.900	56
AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	5.50	0.30	1.000	79
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.20	0.30	1.000	65
NATURAL FAIR COVER "OPEN BRUSH"	B	0.20	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.830  
SUBAREA AREA(ACRES) = 10.50 SUBAREA RUNOFF(CFS) = 11.04  
EFFECTIVE AREA(ACRES) = 4154.94 AREA-AVERAGED Fm(INCH/HR) = 0.25  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
TOTAL AREA(ACRES) = 5530.1 PEAK FLOW RATE(CFS) = 4526.41  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 42.34  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.417  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL ".4 DWELLING/ACRE"	B	1.30	0.30	0.900	56
NATURAL POOR COVER "BARREN"	B	0.30	0.30	1.000	86
COMMERCIAL	B	0.20	0.30	0.100	56
NATURAL FAIR COVER "OPEN BRUSH"	B	0.30	0.30	1.000	66
RESIDENTIAL ".4 DWELLING/ACRE"	B	6.50	0.30	0.900	56
AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	3.00	0.30	1.000	79

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.917  
SUBAREA AREA(ACRES) = 11.60 SUBAREA RUNOFF(CFS) = 11.92

EFFECTIVE AREA(ACRES) = 4166.54 AREA-AVERAGED Fm(INCH/HR) = 0.25  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
TOTAL AREA(ACRES) = 5541.7 PEAK FLOW RATE(CFS) = 4526.41  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13303.00 TO NODE 13304.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 355.00 DOWNSTREAM(FEET) = 350.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 925.40 CHANNEL SLOPE = 0.0054  
GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 7.38  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.388  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	13.80	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.850  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 4533.44  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.51  
AVERAGE FLOW DEPTH(FEET) = 7.38 TRAVEL TIME(MIN.) = 1.81  
Tc(MIN.) = 44.15  
SUBAREA AREA(ACRES) = 13.80 SUBAREA RUNOFF(CFS) = 14.07  
EFFECTIVE AREA(ACRES) = 4180.34 AREA-AVERAGED Fm(INCH/HR) = 0.25  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
TOTAL AREA(ACRES) = 5555.5 PEAK FLOW RATE(CFS) = 4526.41  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 7.37

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 7.37 FLOW VELOCITY(FEET/SEC.) = 8.51  
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13304.00 = 38920.27 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3968.19	28.88	1.760	0.30( 0.25)	0.85	2625.8	31100.00
2	4521.30	43.76	1.394	0.30( 0.25)	0.83	4142.1	13210.00
3	4526.41	44.15	1.388	0.30( 0.25)	0.83	4180.3	13200.00
4	4509.95	45.59	1.364	0.30( 0.25)	0.83	4284.8	13100.00
5	4408.64	70.39	1.115	0.30( 0.25)	0.83	5535.8	13000.00
6	4350.32	72.66	1.099	0.30( 0.25)	0.83	5555.5	13010.00

NEW PEAK FLOW DATA ARE:  
PEAK FLOW RATE(CFS) = 4526.41 Tc(MIN.) = 44.15  
AREA-AVERAGED Fm(INCH/HR) = 0.25 AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.83 EFFECTIVE AREA(ACRES) = 4180.34

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

```

=====
MAINLINE Tc(MIN.) = 44.15
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.388
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS
LAND USE            GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL POOR COVER
"BARREN"            B        7.80   0.30   1.000   86
AGRICULTURAL POOR COVER
"ROW CROPS,CONTOURED" B        1.70   0.30   1.000   79
NATURAL POOR COVER
"BARREN"            B        9.40   0.30   1.000   86
NATURAL FAIR COVER
"OPEN BRUSH"        B        1.20   0.30   1.000   66
RESIDENTIAL
".4 DWELLING/ACRE" B        0.10   0.30   0.900   56
AGRICULTURAL POOR COVER
"ROW CROPS,CONTOURED" B        2.60   0.30   1.000   79
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 22.80   SUBAREA RUNOFF(CFS) = 22.32
EFFECTIVE AREA(ACRES) = 4203.14   AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30   AREA-AVERAGED Ap = 0.83
TOTAL AREA(ACRES) = 5578.3   PEAK FLOW RATE(CFS) = 4526.41
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81
-----

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

```

=====
MAINLINE Tc(MIN.) = 44.15
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.388
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS
LAND USE            GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"WOODLAND,GRASS"    B        0.20   0.30   1.000   65
NATURAL FAIR COVER
"OPEN BRUSH"        B        0.30   0.30   1.000   66
RESIDENTIAL
".4 DWELLING/ACRE" B        0.20   0.30   0.900   56
AGRICULTURAL POOR COVER
"ROW CROPS,CONTOURED" B        2.70   0.30   1.000   79
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.994
SUBAREA AREA(ACRES) = 3.40   SUBAREA RUNOFF(CFS) = 3.33
EFFECTIVE AREA(ACRES) = 4206.54   AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30   AREA-AVERAGED Ap = 0.83
TOTAL AREA(ACRES) = 5581.7   PEAK FLOW RATE(CFS) = 4526.41
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

```

```

*****
FLOW PROCESS FROM NODE 13304.00 TO NODE 13305.00 IS CODE = 56
-----

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<

```

ELEVATION DATA: UPSTREAM(FEET) = 350.00   DOWNSTREAM(FEET) = 315.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 2966.27   CHANNEL SLOPE = 0.0118
GIVEN CHANNEL BASE(FEET) = 50.00   CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000   MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 5.97
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.316
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS
LAND USE            GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"GRASS"            B        27.40   0.30   1.000   69
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 4538.94
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.19
AVERAGE FLOW DEPTH(FEET) = 5.97   TRAVEL TIME(MIN.) = 4.42
Tc(MIN.) = 48.57
SUBAREA AREA(ACRES) = 27.40   SUBAREA RUNOFF(CFS) = 25.06
EFFECTIVE AREA(ACRES) = 4233.94   AREA-AVERAGED Fm(INCH/HR) = 0.25
AREA-AVERAGED Fp(INCH/HR) = 0.30   AREA-AVERAGED Ap = 0.84
TOTAL AREA(ACRES) = 5609.1   PEAK FLOW RATE(CFS) = 4526.41
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 50.00   CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000   MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 5.96

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 5.96   FLOW VELOCITY(FEET/SEC.) = 11.18
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

```

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3968.19	33.48	1.626	0.30( 0.25)	0.85	2679.4	31100.00
2	4521.30	48.18	1.323	0.30( 0.25)	0.84	4195.7	13210.00
3	4526.41	48.57	1.316	0.30( 0.25)	0.84	4233.9	13200.00
4	4509.95	50.01	1.293	0.30( 0.25)	0.84	4338.4	13100.00
5	4408.64	74.84	1.085	0.30( 0.25)	0.83	5589.4	13000.00
6	4350.32	77.14	1.069	0.30( 0.25)	0.83	5609.1	13010.00

```

NEW PEAK FLOW DATA ARE:
PEAK FLOW RATE(CFS) = 4526.41   Tc(MIN.) = 48.57
AREA-AVERAGED Fm(INCH/HR) = 0.25   AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.84   EFFECTIVE AREA(ACRES) = 4233.94

```

```

*****
FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81
-----

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

```

=====
MAINLINE Tc(MIN.) = 48.57
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.316
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/   SCS SOIL   AREA   Fp   Ap   SCS
LAND USE            GROUP   (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL POOR COVER
"BARREN"            B        18.40   0.30   1.000   86
NATURAL FAIR COVER
"MEADOWS"          B        1.20   0.30   1.000   70

```

NATURAL FAIR COVER  
 "WOODLAND,GRASS" B 0.10 0.30 1.000 65  
 NATURAL POOR COVER  
 "BARREN" B 26.60 0.30 1.000 86  
 COMMERCIAL B 3.90 0.30 0.100 56  
 AGRICULTURAL POOR COVER  
 "FALLOW" B 3.00 0.30 1.000 86  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.934  
 SUBAREA AREA(ACRES) = 53.20 SUBAREA RUNOFF(CFS) = 49.60  
 EFFECTIVE AREA(ACRES) = 4287.14 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84  
 TOTAL AREA(ACRES) = 5662.3 PEAK FLOW RATE(CFS) = 4526.41  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 48.57  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.316  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 AGRICULTURAL POOR COVER  
 "ROW CROPS,CONTOURED" B 1.10 0.30 1.000 79  
 NATURAL FAIR COVER  
 "WOODLAND,GRASS" B 0.20 0.30 1.000 65  
 NATURAL POOR COVER  
 "BARREN" B 14.00 0.30 1.000 86  
 COMMERCIAL B 4.30 0.30 0.100 56  
 AGRICULTURAL POOR COVER  
 "FALLOW" B 5.30 0.30 1.000 86  
 NATURAL FAIR COVER  
 "GRASS" B 2.70 0.30 1.000 69  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.860  
 SUBAREA AREA(ACRES) = 27.60 SUBAREA RUNOFF(CFS) = 26.29  
 EFFECTIVE AREA(ACRES) = 4314.74 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84  
 TOTAL AREA(ACRES) = 5689.9 PEAK FLOW RATE(CFS) = 4526.41  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 48.57  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.316  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL FAIR COVER  
 "MEADOWS" B 3.20 0.30 1.000 70  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 6.10 0.30 1.000 66

RESIDENTIAL  
 ".4 DWELLING/ACRE" B 7.50 0.30 0.900 56  
 AGRICULTURAL POOR COVER  
 "ROW CROPS,CONTOURED" B 5.40 0.30 1.000 79  
 NATURAL FAIR COVER  
 "WOODLAND,GRASS" B 1.60 0.30 1.000 65  
 NATURAL POOR COVER  
 "BARREN" B 1.90 0.30 1.000 86  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.971  
 SUBAREA AREA(ACRES) = 25.70 SUBAREA RUNOFF(CFS) = 23.71  
 EFFECTIVE AREA(ACRES) = 4340.44 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84  
 TOTAL AREA(ACRES) = 5715.6 PEAK FLOW RATE(CFS) = 4526.41  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 48.57  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.316  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 COMMERCIAL B 2.00 0.30 0.100 56  
 AGRICULTURAL POOR COVER  
 "FALLOW" B 3.70 0.30 1.000 86  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 2.10 0.30 1.000 66  
 RESIDENTIAL  
 ".4 DWELLING/ACRE" B 2.60 0.30 0.900 56  
 AGRICULTURAL POOR COVER  
 "ROW CROPS,CONTOURED" B 0.20 0.30 1.000 79  
 NATURAL FAIR COVER  
 "WOODLAND,GRASS" B 0.10 0.30 1.000 65  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.807  
 SUBAREA AREA(ACRES) = 10.70 SUBAREA RUNOFF(CFS) = 10.34  
 EFFECTIVE AREA(ACRES) = 4351.14 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84  
 TOTAL AREA(ACRES) = 5726.3 PEAK FLOW RATE(CFS) = 4526.41  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 48.57  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.316  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 0.50 0.30 1.000 66  
 RESIDENTIAL

" .4 DWELLING/ACRE" B 8.20 0.30 0.900 56  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.906  
 SUBAREA AREA (ACRES) = 8.70 SUBAREA RUNOFF (CFS) = 8.18  
 EFFECTIVE AREA (ACRES) = 4359.84 AREA-AVERAGED Fm (INCH/HR) = 0.25  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84  
 TOTAL AREA (ACRES) = 5735.0 PEAK FLOW RATE (CFS) = 4526.41  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 3A50EVRL.DNA  
 MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1087.20	13.49	0.30 ( 0.13)	0.43	436.1	120.00
2	1086.75	13.53	0.30 ( 0.13)	0.43	436.7	110.00
3	930.63	20.54	0.30 ( 0.13)	0.43	504.3	100.00
4	870.49	23.19	0.30 ( 0.13)	0.43	510.2	150.00
TOTAL AREA (ACRES) =		510.2				

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3968.19	33.48	1.626	0.30 ( 0.26)	0.85	2805.3	31100.00
2	4521.30	48.18	1.323	0.30 ( 0.25)	0.84	4321.6	13210.00
3	4526.41	48.57	1.316	0.30 ( 0.25)	0.84	4359.8	13200.00
4	4509.95	50.01	1.293	0.30 ( 0.25)	0.84	4464.3	13100.00
5	4408.64	74.84	1.085	0.30 ( 0.25)	0.83	5715.3	13000.00
6	4350.32	77.14	1.069	0.30 ( 0.25)	0.83	5735.0	13010.00
LONGEST FLOWPATH FROM NODE		13010.00 TO NODE 13305.00 = 41886.54 FEET.					

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1087.20	13.49	2.876	0.30 ( 0.13)	0.43	436.1	120.00
2	1086.75	13.53	2.870	0.30 ( 0.13)	0.43	436.7	110.00
3	930.63	20.54	2.173	0.30 ( 0.13)	0.43	504.3	100.00
4	870.49	23.19	2.016	0.30 ( 0.13)	0.43	510.2	150.00
LONGEST FLOWPATH FROM NODE		150.00 TO NODE 13305.00 = 9867.00 FEET.					

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4145.05	13.49	2.876	0.30 ( 0.22)	0.73	1566.6	120.00
2	4146.06	13.53	2.870	0.30 ( 0.22)	0.74	1570.3	110.00
3	4337.45	20.54	2.173	0.30 ( 0.23)	0.76	2225.6	100.00
4	4401.99	23.19	2.016	0.30 ( 0.23)	0.76	2453.3	150.00
5	4658.52	33.48	1.626	0.30 ( 0.24)	0.79	3315.5	31100.00

6	5071.67	48.18	1.323	0.30 ( 0.24)	0.80	4831.8	13210.00
7	5073.85	48.57	1.316	0.30 ( 0.24)	0.80	4870.0	13200.00
8	5046.65	50.01	1.293	0.30 ( 0.24)	0.80	4974.5	13100.00
9	4849.18	74.84	1.085	0.30 ( 0.24)	0.80	6225.5	13000.00
10	4783.69	77.14	1.069	0.30 ( 0.24)	0.80	6245.2	13010.00
TOTAL AREA (ACRES) =		6245.2					

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 5073.85 Tc (MIN.) = 48.567  
 EFFECTIVE AREA (ACRES) = 4870.04 AREA-AVERAGED Fm (INCH/HR) = 0.24  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.76  
 TOTAL AREA (ACRES) = 6245.2  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13306.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 315.00 DOWNSTREAM (FEET) = 245.50  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 4408.41 CHANNEL SLOPE = 0.0158  
 GIVEN CHANNEL BASE (FEET) = 50.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 5.89  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.247

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	68.80	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.850  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 5104.55  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 12.84  
 AVERAGE FLOW DEPTH (FEET) = 5.88 TRAVEL TIME (MIN.) = 5.72  
 Tc (MIN.) = 54.29

SUBAREA AREA (ACRES) = 68.80 SUBAREA RUNOFF (CFS) = 61.40  
 EFFECTIVE AREA (ACRES) = 4938.84 AREA-AVERAGED Fm (INCH/HR) = 0.24  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80  
 TOTAL AREA (ACRES) = 6314.0 PEAK FLOW RATE (CFS) = 5073.85

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 50.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 5.86

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 5.86 FLOW VELOCITY (FEET/SEC.) = 12.81  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13306.00 = 46294.95 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
---------------	---------	-----------	---------------------	-------------------	----	------------	----------------

1	4145.05	19.57	2.242	0.30	( 0.22)	0.74	1635.4	120.00
2	4146.06	19.61	2.239	0.30	( 0.22)	0.74	1639.1	110.00
3	4337.45	26.54	1.850	0.30	( 0.23)	0.76	2294.4	100.00
4	4401.99	29.16	1.749	0.30	( 0.23)	0.77	2522.1	150.00
5	4658.52	39.36	1.472	0.30	( 0.24)	0.79	3384.3	31100.00
6	5071.67	53.90	1.251	0.30	( 0.24)	0.80	4900.6	13210.00
7	5073.85	54.29	1.247	0.30	( 0.24)	0.80	4938.8	13200.00
8	5046.65	55.74	1.231	0.30	( 0.24)	0.80	5043.3	13100.00
9	4849.18	80.65	1.045	0.30	( 0.24)	0.80	6294.3	13000.00
10	4783.69	82.97	1.030	0.30	( 0.24)	0.80	6314.0	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 5073.85 Tc(MIN.) = 54.29  
 AREA-AVERAGED Fm(INCH/HR) = 0.24 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.80 EFFECTIVE AREA(ACRES) = 4938.84

\*\*\*\*\*

FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 54.29

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.247

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	21.50	0.30	1.000	86
COMMERCIAL	B	15.30	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	0.80	0.30	1.000	69
AGRICULTURAL FAIR COVER					
"ORCHARDS"	B	0.60	0.30	1.000	65
RESIDENTIAL					
".4 DWELLING/ACRE"	B	8.00	0.30	0.900	56
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.10	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.685

SUBAREA AREA(ACRES) = 46.30 SUBAREA RUNOFF(CFS) = 43.38

EFFECTIVE AREA(ACRES) = 4985.14 AREA-AVERAGED Fm(INCH/HR) = 0.24

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80

TOTAL AREA(ACRES) = 6360.3 PEAK FLOW RATE(CFS) = 5073.85

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 54.29

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.247

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	43.30	0.30	1.000	86
COMMERCIAL	B	4.90	0.30	0.100	56
NATURAL FAIR COVER					

"GRASS"	B	5.70	0.30	1.000	69
AGRICULTURAL FAIR COVER					
"ORCHARDS"	B	0.50	0.30	1.000	65
PUBLIC PARK	B	1.10	0.30	0.850	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	3.10	0.30	0.900	56
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.917					
SUBAREA AREA(ACRES) = 58.60					
SUBAREA RUNOFF(CFS) = 51.25					
EFFECTIVE AREA(ACRES) = 5043.74					
AREA-AVERAGED Fm(INCH/HR) = 0.24					
AREA-AVERAGED Fp(INCH/HR) = 0.30					
AREA-AVERAGED Ap = 0.80					
TOTAL AREA(ACRES) = 6418.9					
PEAK FLOW RATE(CFS) = 5073.85					

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 54.29

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.247

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	6.80	0.30	1.000	65
NATURAL POOR COVER					
"BARREN"	B	0.70	0.30	1.000	86
COMMERCIAL	B	1.10	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	0.50	0.30	1.000	69
AGRICULTURAL FAIR COVER					
"ORCHARDS"	B	0.10	0.30	1.000	65
PUBLIC PARK	B	0.50	0.30	0.850	56
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.890					
SUBAREA AREA(ACRES) = 9.70					
SUBAREA RUNOFF(CFS) = 8.55					
EFFECTIVE AREA(ACRES) = 5053.44					
AREA-AVERAGED Fm(INCH/HR) = 0.24					
AREA-AVERAGED Fp(INCH/HR) = 0.30					
AREA-AVERAGED Ap = 0.80					
TOTAL AREA(ACRES) = 6428.6					
PEAK FLOW RATE(CFS) = 5073.85					

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 54.29

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.247

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL					
".4 DWELLING/ACRE"	B	2.20	0.30	0.900	56
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.10	0.30	1.000	65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.904					

SUBAREA AREA (ACRES) = 2.30 SUBAREA RUNOFF (CFS) = 2.02  
 EFFECTIVE AREA (ACRES) = 5055.74 AREA-AVERAGED Fm (INCH/HR) = 0.24  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80  
 TOTAL AREA (ACRES) = 6430.9 PEAK FLOW RATE (CFS) = 5073.85  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13306.00 TO NODE 13307.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 245.50 DOWNSTREAM (FEET) = 220.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1543.21 CHANNEL SLOPE = 0.0165  
 GIVEN CHANNEL BASE (FEET) = 50.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 5.79  
 CHANNEL FLOW THRU SUBAREA (CFS) = 5073.85  
 FLOW VELOCITY (FEET/SEC.) = 13.02 FLOW DEPTH (FEET) = 5.79  
 TRAVEL TIME (MIN.) = 1.98 Tc (MIN.) = 56.27  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13307.00 = 47838.16 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4145.05	21.68	2.106	0.30 ( 0.22)	0.75	1752.3	120.00
2	4146.06	21.71	2.104	0.30 ( 0.22)	0.75	1756.0	110.00
3	4337.45	28.61	1.770	0.30 ( 0.23)	0.76	2411.3	100.00
4	4401.99	31.23	1.685	0.30 ( 0.23)	0.77	2639.0	150.00
5	4658.52	41.38	1.433	0.30 ( 0.24)	0.79	3501.2	31100.00
6	5071.67	55.88	1.230	0.30 ( 0.24)	0.80	5017.5	13210.00
7	5073.85	56.27	1.225	0.30 ( 0.24)	0.80	5055.7	13200.00
8	5046.65	57.72	1.210	0.30 ( 0.24)	0.80	5160.2	13100.00
9	4849.18	82.65	1.032	0.30 ( 0.24)	0.80	6411.2	13000.00
10	4783.69	84.98	1.016	0.30 ( 0.24)	0.80	6430.9	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 5073.85 Tc (MIN.) = 56.27  
 AREA-AVERAGED Fm (INCH/HR) = 0.24 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.80 EFFECTIVE AREA (ACRES) = 5055.74

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13307.00 TO NODE 13307.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) = 56.27  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.225  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	0.20	0.30	0.100	56
NATURAL FAIR COVER "GRASS"	B	0.10	0.30	1.000	69
AGRICULTURAL FAIR COVER "ORCHARDS"	B	0.20	0.30	1.000	65
NATURAL POOR COVER "BARREN"	B	3.70	0.30	1.000	86
COMMERCIAL	B	0.30	0.30	0.100	56

NATURAL FAIR COVER  
 "GRASS" B 3.20 0.30 1.000 69  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.942  
 SUBAREA AREA (ACRES) = 7.70 SUBAREA RUNOFF (CFS) = 6.53  
 EFFECTIVE AREA (ACRES) = 5063.44 AREA-AVERAGED Fm (INCH/HR) = 0.24  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80  
 TOTAL AREA (ACRES) = 6438.6 PEAK FLOW RATE (CFS) = 5073.85  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13307.00 TO NODE 13307.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) = 56.27  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.225  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "WOODLAND, GRASS"	B	3.60	0.30	1.000	65
NATURAL FAIR COVER "GRASS"	B	1.90	0.30	1.000	69
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.60	0.30	1.000	65
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000					
SUBAREA AREA (ACRES) = 6.10 SUBAREA RUNOFF (CFS) = 5.08					
EFFECTIVE AREA (ACRES) = 5069.54 AREA-AVERAGED Fm (INCH/HR) = 0.24					
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80					
TOTAL AREA (ACRES) = 6444.7 PEAK FLOW RATE (CFS) = 5073.85					
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE					

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13307.00 TO NODE 13308.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 220.00 DOWNSTREAM (FEET) = 212.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 925.62 CHANNEL SLOPE = 0.0086  
 GIVEN CHANNEL BASE (FEET) = 50.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 6.91  
 CHANNEL FLOW THRU SUBAREA (CFS) = 5073.85  
 FLOW VELOCITY (FEET/SEC.) = 10.39 FLOW DEPTH (FEET) = 6.91  
 TRAVEL TIME (MIN.) = 1.49 Tc (MIN.) = 57.75  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13308.00 = 48763.78 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4145.05	23.25	2.012	0.30 ( 0.22)	0.75	1766.1	120.00
2	4146.06	23.29	2.010	0.30 ( 0.22)	0.75	1769.8	110.00
3	4337.45	30.17	1.713	0.30 ( 0.23)	0.76	2425.1	100.00
4	4401.99	32.78	1.644	0.30 ( 0.23)	0.77	2652.8	150.00
5	4658.52	42.91	1.408	0.30 ( 0.24)	0.79	3515.0	31100.00



6	5071.67	57.36	1.213	0.30	( 0.24)	0.80	5031.3	13210.00
7	5073.85	57.75	1.209	0.30	( 0.24)	0.80	5069.5	13200.00
8	5046.65	59.21	1.194	0.30	( 0.24)	0.80	5174.0	13100.00
9	4849.18	84.16	1.022	0.30	( 0.24)	0.80	6425.0	13000.00
10	4783.69	86.49	1.006	0.30	( 0.24)	0.80	6444.7	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 5073.85 Tc(MIN.) = 57.75  
 AREA-AVERAGED Fm(INCH/HR) = 0.24 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.80 EFFECTIVE AREA(ACRES) = 5069.54

\*\*\*\*\*

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 57.75  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.209  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	0.10	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.20	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	5.00	0.30	1.000	65
COMMERCIAL	B	3.20	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	0.10	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.90	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.697  
 SUBAREA AREA(ACRES) = 9.50 SUBAREA RUNOFF(CFS) = 8.55  
 EFFECTIVE AREA(ACRES) = 5079.04 AREA-AVERAGED Fm(INCH/HR) = 0.24  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80  
 TOTAL AREA(ACRES) = 6454.2 PEAK FLOW RATE(CFS) = 5073.85  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 57.75  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.209  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
APARTMENTS	B	0.30	0.30	0.200	56
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	1.00	0.30	1.000	63
COMMERCIAL	B	41.90	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	7.20	0.30	1.000	69
NATURAL FAIR COVER					

"OPEN BRUSH" B 25.00 0.30 1.000 66  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.498  
 SUBAREA AREA(ACRES) = 75.60 SUBAREA RUNOFF(CFS) = 72.11  
 EFFECTIVE AREA(ACRES) = 5154.64 AREA-AVERAGED Fm(INCH/HR) = 0.24  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA(ACRES) = 6529.8 PEAK FLOW RATE(CFS) = 5073.85  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 57.75  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.209  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	0.10	0.30	0.850	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	0.90	0.30	1.000	79
SCHOOL	B	0.30	0.30	0.600	56
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	13.20	0.30	1.000	65
APARTMENTS	B	0.50	0.30	0.200	56
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.60	0.30	1.000	63

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.966  
 SUBAREA AREA(ACRES) = 15.60 SUBAREA RUNOFF(CFS) = 12.91  
 EFFECTIVE AREA(ACRES) = 5170.24 AREA-AVERAGED Fm(INCH/HR) = 0.24  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA(ACRES) = 6545.4 PEAK FLOW RATE(CFS) = 5073.85  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 57.75  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.209  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	33.90	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	17.60	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	16.80	0.30	1.000	66
RESIDENTIAL					
"11+ DWELLINGS/ACRE"	B	0.60	0.30	0.200	56
RESIDENTIAL					
"8-10 DWELLINGS/ACRE"	B	1.50	0.30	0.400	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	10.00	0.30	1.000	79

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.603  
 SUBAREA AREA (ACRES) = 80.40 SUBAREA RUNOFF (CFS) = 74.41  
 EFFECTIVE AREA (ACRES) = 5250.64 AREA-AVERAGED Fm (INCH/HR) = 0.24  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA (ACRES) = 6625.8 PEAK FLOW RATE (CFS) = 5073.85  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 57.75  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.209  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
SCHOOL	B	0.30	0.30	0.600	56
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.70	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.880  
 SUBAREA AREA (ACRES) = 1.00 SUBAREA RUNOFF (CFS) = 0.85  
 EFFECTIVE AREA (ACRES) = 5251.64 AREA-AVERAGED Fm (INCH/HR) = 0.24  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA (ACRES) = 6626.8 PEAK FLOW RATE (CFS) = 5073.85  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 57.75  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.209  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "GRASS"	B	0.30	0.30	1.000	69
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.80	0.30	1.000	65
NATURAL FAIR COVER "GRASS"	B	0.50	0.30	1.000	69
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.20	0.30	1.000	65
NATURAL FAIR COVER "GRASS"	B	0.30	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 2.10 SUBAREA RUNOFF (CFS) = 1.72  
 EFFECTIVE AREA (ACRES) = 5253.74 AREA-AVERAGED Fm (INCH/HR) = 0.24  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA (ACRES) = 6628.9 PEAK FLOW RATE (CFS) = 5073.85  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 57.75  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.209  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "GRASS"	B	1.20	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	0.50	0.30	1.000	66
PUBLIC PARK	B	1.70	0.30	0.850	56
NATURAL FAIR COVER "WOODLAND,GRASS"	B	7.20	0.30	1.000	65
NATURAL FAIR COVER "GRASS"	B	1.00	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.978  
 SUBAREA AREA (ACRES) = 11.60 SUBAREA RUNOFF (CFS) = 9.56  
 EFFECTIVE AREA (ACRES) = 5265.34 AREA-AVERAGED Fm (INCH/HR) = 0.24  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA (ACRES) = 6640.5 PEAK FLOW RATE (CFS) = 5073.85  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: RI50EV29.DNA  
 MEMORY BANK # 2 DEFINED AS FOLLOWS:  

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap (DECIMAL)	Ae (ACRES)	HEADWATER NODE
1	20384.29	14.94	0.30 ( 0.25)	0.83	3182.7	50200.00
2	21804.34	18.83	0.30 ( 0.25)	0.84	4234.9	50400.00
3	24985.41	28.30	0.30 ( 0.25)	0.85	6894.1	50300.00
4	28107.21	40.25	0.30 ( 0.26)	0.87	10809.4	40200.00
5	28752.17	44.02	0.30 ( 0.27)	0.89	12286.5	390.00
6	30503.55	53.70	0.30 ( 0.27)	0.91	16028.2	40100.00
7	31773.96	62.91	0.30 ( 0.28)	0.93	19339.0	11801.00
8	33610.36	73.74	0.30 ( 0.28)	0.94	23922.8	11530.00
9	35450.75	81.59	0.30 ( 0.28)	0.95	28309.1	11910.00
10	37983.56	91.81	0.30 ( 0.29)	0.96	35022.8	10800.00
11	38625.21	96.05	0.30 ( 0.29)	0.96	37968.1	11130.00
12	38591.59	105.65	0.30 ( 0.29)	0.96	43009.3	12410.00
13	38258.95	113.91	0.30 ( 0.29)	0.97	46748.4	11201.00
14	37937.93	118.87	0.30 ( 0.29)	0.97	48480.1	12201.00
15	37024.55	125.90	0.30 ( 0.29)	0.97	50337.3	1231.00
16	35855.16	133.66	0.30 ( 0.29)	0.97	51971.6	10400.00
17	34638.38	141.55	0.30 ( 0.29)	0.97	53266.7	12010.00
18	33549.91	147.47	0.30 ( 0.29)	0.97	53613.6	10210.00

19 33076.09 150.50 0.30( 0.29) 0.97 53730.8 12000.00  
 20 29839.98 175.46 0.30( 0.29) 0.97 54352.1 10100.00  
 TOTAL AREA (ACRES) = 54352.1

\*\*\*\*\*

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20384.29	14.94	0.30( 0.25)	0.83	3182.7	50200.00
2	21804.34	18.83	0.30( 0.25)	0.84	4234.9	50400.00
3	24985.41	28.30	0.30( 0.25)	0.85	6894.1	50300.00
4	28107.21	40.25	0.30( 0.26)	0.87	10809.4	40200.00
5	28752.17	44.02	0.30( 0.27)	0.89	12286.5	390.00
6	30503.55	53.70	0.30( 0.27)	0.91	16028.2	40100.00
7	31773.96	62.91	0.30( 0.28)	0.93	19339.0	11801.00
8	33610.36	73.74	0.30( 0.28)	0.94	23922.8	11530.00
9	35450.75	81.59	0.30( 0.28)	0.95	28309.1	11910.00
10	37983.56	91.81	0.30( 0.29)	0.96	35022.8	10800.00
11	38625.21	96.05	0.30( 0.29)	0.96	37968.1	11130.00
12	38591.59	105.65	0.30( 0.29)	0.96	43009.3	12410.00
13	38258.95	113.91	0.30( 0.29)	0.97	46748.4	11201.00
14	37937.93	118.87	0.30( 0.29)	0.97	48480.1	12201.00
15	37024.55	125.90	0.30( 0.29)	0.97	50337.3	12231.00
16	35855.16	133.66	0.30( 0.29)	0.97	51971.6	10400.00
17	34638.38	141.55	0.30( 0.29)	0.97	53266.7	12010.00
18	33549.91	147.47	0.30( 0.29)	0.97	53613.6	10210.00
19	33076.09	150.50	0.30( 0.29)	0.97	53730.8	12000.00
20	29839.98	175.46	0.30( 0.29)	0.97	54352.1	10100.00

TOTAL AREA (ACRES) = 54352.1

\*\*\*\*\*

FLOW PROCESS FROM NODE 12904.00 TO NODE 13308.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 213.00 DOWNSTREAM(FEET) = 212.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1389.52 CHANNEL SLOPE = 0.0007  
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 17.77  
 CHANNEL FLOW THRU SUBAREA(CFS) = 38625.21  
 FLOW VELOCITY(FEET/SEC.) = 7.52 FLOW DEPTH(FEET) = 17.77  
 TRAVEL TIME(MIN.) = 3.08 Tc(MIN.) = 99.13  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118090.66 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20384.29	18.68	2.318	0.30( 0.25)	0.83	3182.7	50200.00
2	21804.34	22.49	2.057	0.30( 0.25)	0.84	4234.9	50400.00
3	24985.41	31.81	1.669	0.30( 0.25)	0.85	6894.1	50300.00
4	28107.21	43.64	1.396	0.30( 0.26)	0.87	10809.4	40200.00

5	28752.17	47.38	1.335	0.30( 0.27)	0.89	12286.5	390.00
6	30503.55	57.00	1.217	0.30( 0.27)	0.91	16028.2	40100.00
7	31773.96	66.17	1.143	0.30( 0.28)	0.93	19339.0	11801.00
8	33610.36	76.95	1.070	0.30( 0.28)	0.94	23922.8	11530.00
9	35450.75	84.75	1.018	0.30( 0.28)	0.95	28309.1	11910.00
10	37983.56	94.90	0.961	0.30( 0.29)	0.96	35022.8	10800.00
11	38625.21	99.13	0.942	0.30( 0.29)	0.96	37968.1	11130.00
12	38591.59	108.73	0.901	0.30( 0.29)	0.96	43009.3	12410.00
13	38258.95	117.00	0.865	0.30( 0.29)	0.97	46748.4	11201.00
14	37937.93	121.96	0.848	0.30( 0.29)	0.97	48480.1	12201.00
15	37024.55	129.01	0.833	0.30( 0.29)	0.97	50337.3	12231.00
16	35855.16	136.81	0.817	0.30( 0.29)	0.97	51971.6	10400.00
17	34638.38	144.73	0.801	0.30( 0.29)	0.97	53266.7	12010.00
18	33549.91	150.68	0.789	0.30( 0.29)	0.97	53613.6	10210.00
19	33076.09	153.72	0.782	0.30( 0.29)	0.97	53730.8	12000.00
20	29839.98	178.79	0.730	0.30( 0.29)	0.97	54352.1	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 38625.21 Tc(MIN.) = 99.13  
 AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.96 EFFECTIVE AREA(ACRES) = 37968.11

\*\*\*\*\*

FLOW PROCESS FROM NODE 13307.00 TO NODE 13308.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20384.29	18.68	2.318	0.30( 0.25)	0.83	3182.7	50200.00
2	21804.34	22.49	2.057	0.30( 0.25)	0.84	4234.9	50400.00
3	24985.41	31.81	1.669	0.30( 0.25)	0.85	6894.1	50300.00
4	28107.21	43.64	1.396	0.30( 0.26)	0.87	10809.4	40200.00
5	28752.17	47.38	1.335	0.30( 0.27)	0.89	12286.5	390.00
6	30503.55	57.00	1.217	0.30( 0.27)	0.91	16028.2	40100.00
7	31773.96	66.17	1.143	0.30( 0.28)	0.93	19339.0	11801.00
8	33610.36	76.95	1.070	0.30( 0.28)	0.94	23922.8	11530.00
9	35450.75	84.75	1.018	0.30( 0.28)	0.95	28309.1	11910.00
10	37983.56	94.90	0.961	0.30( 0.29)	0.96	35022.8	10800.00
11	38625.21	99.13	0.942	0.30( 0.29)	0.96	37968.1	11130.00
12	38591.59	108.73	0.901	0.30( 0.29)	0.96	43009.3	12410.00
13	38258.95	117.00	0.865	0.30( 0.29)	0.97	46748.4	11201.00
14	37937.93	121.96	0.848	0.30( 0.29)	0.97	48480.1	12201.00
15	37024.55	129.01	0.833	0.30( 0.29)	0.97	50337.3	12231.00
16	35855.16	136.81	0.817	0.30( 0.29)	0.97	51971.6	10400.00
17	34638.38	144.73	0.801	0.30( 0.29)	0.97	53266.7	12010.00
18	33549.91	150.68	0.789	0.30( 0.29)	0.97	53613.6	10210.00
19	33076.09	153.72	0.782	0.30( 0.29)	0.97	53730.8	12000.00
20	29839.98	178.79	0.730	0.30( 0.29)	0.97	54352.1	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118090.66 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4145.05	23.25	2.012	0.30( 0.22)	0.73	1961.9	120.00
2	4146.06	23.29	2.010	0.30( 0.22)	0.73	1965.6	110.00
3	4337.45	30.17	1.713	0.30( 0.23)	0.75	2620.9	100.00

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
4	4401.99	32.78	1.644	0.30 ( 0.23)	0.76	2848.6	150.00
5	4658.52	42.91	1.408	0.30 ( 0.23)	0.78	3710.8	31100.00
6	5071.67	57.36	1.213	0.30 ( 0.24)	0.79	5227.1	13210.00
7	5073.85	57.75	1.209	0.30 ( 0.24)	0.79	5265.3	13200.00
8	5046.65	59.21	1.194	0.30 ( 0.24)	0.79	5369.8	13100.00
9	4849.18	84.16	1.022	0.30 ( 0.24)	0.79	6620.8	13000.00
10	4783.69	86.49	1.006	0.30 ( 0.24)	0.79	6640.5	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13308.00 = 48763.78 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24283.56	18.68	2.318	0.30 ( 0.24)	0.80	4759.1	50200.00
2	25914.59	22.49	2.057	0.30 ( 0.24)	0.80	6132.7	50400.00
3	26208.73	23.25	2.012	0.30 ( 0.24)	0.81	6413.6	120.00
4	26222.00	23.29	2.010	0.30 ( 0.24)	0.81	6427.5	110.00
5	28761.69	30.17	1.713	0.30 ( 0.25)	0.82	9045.9	100.00
6	29363.53	31.81	1.669	0.30 ( 0.25)	0.82	9658.4	50300.00
7	29642.21	32.78	1.644	0.30 ( 0.25)	0.82	10062.2	150.00
8	32572.82	42.91	1.408	0.30 ( 0.25)	0.85	14278.2	31100.00
9	32786.62	43.64	1.396	0.30 ( 0.26)	0.85	14596.8	40200.00
10	33538.52	47.38	1.335	0.30 ( 0.26)	0.86	16466.5	390.00
11	35564.83	57.00	1.217	0.30 ( 0.26)	0.88	21217.2	40100.00
12	35625.59	57.36	1.213	0.30 ( 0.26)	0.88	21386.6	13210.00
13	35681.45	57.75	1.209	0.30 ( 0.27)	0.88	21564.7	13200.00
14	35856.26	59.21	1.194	0.30 ( 0.27)	0.89	22195.6	13100.00
15	36765.51	66.17	1.143	0.30 ( 0.27)	0.90	25057.9	11801.00
16	38516.57	76.95	1.070	0.30 ( 0.27)	0.91	30182.3	11530.00
17	40161.23	84.16	1.022	0.30 ( 0.28)	0.92	34599.3	13000.00
18	40283.43	84.75	1.018	0.30 ( 0.28)	0.92	34934.8	11910.00
19	40669.41	86.49	1.006	0.30 ( 0.28)	0.92	36102.6	13010.00
20	42486.88	94.90	0.961	0.30 ( 0.28)	0.93	41663.3	10800.00
21	43014.30	99.13	0.942	0.30 ( 0.28)	0.94	44608.6	11130.00
22	42721.61	108.73	0.901	0.30 ( 0.28)	0.94	49649.8	12410.00
23	42165.54	117.00	0.865	0.30 ( 0.28)	0.94	53389.0	11201.00
24	41738.26	121.96	0.848	0.30 ( 0.28)	0.95	55120.7	12201.00
25	40734.10	129.01	0.833	0.30 ( 0.28)	0.95	56977.8	12231.00
26	39464.36	136.81	0.817	0.30 ( 0.28)	0.95	58612.1	10400.00
27	38145.56	144.73	0.801	0.30 ( 0.28)	0.95	59907.2	12010.00
28	36980.48	150.68	0.789	0.30 ( 0.28)	0.95	60254.2	10210.00
29	36467.48	153.72	0.782	0.30 ( 0.28)	0.95	60371.4	12000.00
30	32908.53	178.79	0.730	0.30 ( 0.28)	0.95	60992.6	10100.00

TOTAL AREA (ACRES) = 60992.6

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 43014.30 Tc (MIN.) = 99.132  
EFFECTIVE AREA (ACRES) = 44608.64 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.88  
TOTAL AREA (ACRES) = 60992.6  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118090.66 FEET.

=====  
END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 60992.6 TC (MIN.) = 99.13  
EFFECTIVE AREA (ACRES) = 44608.64 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.935  
PEAK FLOW RATE (CFS) = 43014.30

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24283.56	18.68	2.318	0.30 ( 0.24)	0.80	4759.1	50200.00
2	25914.59	22.49	2.057	0.30 ( 0.24)	0.80	6132.7	50400.00
3	26208.73	23.25	2.012	0.30 ( 0.24)	0.81	6413.6	120.00
4	26222.00	23.29	2.010	0.30 ( 0.24)	0.81	6427.5	110.00
5	28761.69	30.17	1.713	0.30 ( 0.25)	0.82	9045.9	100.00
6	29363.53	31.81	1.669	0.30 ( 0.25)	0.82	9658.4	50300.00
7	29642.21	32.78	1.644	0.30 ( 0.25)	0.82	10062.2	150.00
8	32572.82	42.91	1.408	0.30 ( 0.25)	0.85	14278.2	31100.00
9	32786.62	43.64	1.396	0.30 ( 0.26)	0.85	14596.8	40200.00
10	33538.52	47.38	1.335	0.30 ( 0.26)	0.86	16466.5	390.00
11	35564.83	57.00	1.217	0.30 ( 0.26)	0.88	21217.2	40100.00
12	35625.59	57.36	1.213	0.30 ( 0.26)	0.88	21386.6	13210.00
13	35681.45	57.75	1.209	0.30 ( 0.27)	0.88	21564.7	13200.00
14	35856.26	59.21	1.194	0.30 ( 0.27)	0.89	22195.6	13100.00
15	36765.51	66.17	1.143	0.30 ( 0.27)	0.90	25057.9	11801.00
16	38516.57	76.95	1.070	0.30 ( 0.27)	0.91	30182.3	11530.00
17	40161.23	84.16	1.022	0.30 ( 0.28)	0.92	34599.3	13000.00
18	40283.43	84.75	1.018	0.30 ( 0.28)	0.92	34934.8	11910.00
19	40669.41	86.49	1.006	0.30 ( 0.28)	0.92	36102.6	13010.00
20	42486.88	94.90	0.961	0.30 ( 0.28)	0.93	41663.3	10800.00
21	43014.30	99.13	0.942	0.30 ( 0.28)	0.94	44608.6	11130.00
22	42721.61	108.73	0.901	0.30 ( 0.28)	0.94	49649.8	12410.00
23	42165.54	117.00	0.865	0.30 ( 0.28)	0.94	53389.0	11201.00
24	41738.26	121.96	0.848	0.30 ( 0.28)	0.95	55120.7	12201.00
25	40734.10	129.01	0.833	0.30 ( 0.28)	0.95	56977.8	12231.00
26	39464.36	136.81	0.817	0.30 ( 0.28)	0.95	58612.1	10400.00
27	38145.56	144.73	0.801	0.30 ( 0.28)	0.95	59907.2	12010.00
28	36980.48	150.68	0.789	0.30 ( 0.28)	0.95	60254.2	10210.00
29	36467.48	153.72	0.782	0.30 ( 0.28)	0.95	60371.4	12000.00
30	32908.53	178.79	0.730	0.30 ( 0.28)	0.95	60992.6	10100.00

=====  
END OF RATIONAL METHOD ANALYSIS  
=====



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S34- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 50-YR RM EV APRIL 2019 CCHIU \*  
\*\*\*\*\*

FILE NAME: RI50EV34.DAT  
TIME/DATE OF STUDY: 09:14 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 50.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.305
- 2) 10.00; 3.420
- 3) 15.00; 2.629
- 4) 20.00; 2.200
- 5) 25.00; 1.906
- 6) 30.00; 1.714
- 7) 40.00; 1.452
- 8) 50.00; 1.290
- 9) 60.00; 1.181
- 10) 90.00; 0.979
- 11) 120.00; 0.849
- 12) 180.00; 0.725
- 13) 360.00; 0.534
- 14) 1200.00; 0.233

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: RI50EV33.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24283.56	18.68	0.30 ( 0.24)	0.80	4759.1	50200.00
2	26222.00	23.29	0.30 ( 0.24)	0.81	6427.5	110.00
3	29642.21	32.78	0.30 ( 0.25)	0.82	10062.2	150.00
4	32786.62	43.64	0.30 ( 0.26)	0.85	14596.8	40200.00
5	33538.52	47.38	0.30 ( 0.26)	0.86	16466.5	390.00
6	35856.26	59.21	0.30 ( 0.27)	0.89	22195.6	13100.00
7	36765.51	66.17	0.30 ( 0.27)	0.90	25057.9	11801.00
8	38516.57	76.95	0.30 ( 0.27)	0.91	30182.3	11530.00
9	40669.41	86.49	0.30 ( 0.28)	0.92	36102.6	13010.00
10	42486.88	94.90	0.30 ( 0.28)	0.93	41663.3	10800.00
11	43014.30	99.13	0.30 ( 0.28)	0.94	44608.6	11130.00
12	42721.61	108.73	0.30 ( 0.28)	0.94	49649.8	12410.00
13	42165.54	117.00	0.30 ( 0.28)	0.94	53389.0	11201.00
14	41738.26	121.96	0.30 ( 0.28)	0.95	55120.7	12201.00
15	40734.10	129.01	0.30 ( 0.28)	0.95	56977.8	12231.00
16	39464.36	136.81	0.30 ( 0.28)	0.95	58612.1	10400.00
17	38145.56	144.73	0.30 ( 0.28)	0.95	59907.2	12010.00
18	36980.48	150.68	0.30 ( 0.28)	0.95	60254.2	10210.00
19	36467.48	153.72	0.30 ( 0.28)	0.95	60371.4	12000.00
20	32908.53	178.79	0.30 ( 0.28)	0.95	60992.6	10100.00
TOTAL AREA (ACRES) =						60992.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24283.56	18.68	0.30 ( 0.24)	0.80	4759.1	50200.00
2	26222.00	23.29	0.30 ( 0.24)	0.81	6427.5	110.00
3	29642.21	32.78	0.30 ( 0.25)	0.82	10062.2	150.00
4	32786.62	43.64	0.30 ( 0.26)	0.85	14596.8	40200.00
5	33538.52	47.38	0.30 ( 0.26)	0.86	16466.5	390.00
6	35856.26	59.21	0.30 ( 0.27)	0.89	22195.6	13100.00
7	36765.51	66.17	0.30 ( 0.27)	0.90	25057.9	11801.00
8	38516.57	76.95	0.30 ( 0.27)	0.91	30182.3	11530.00
9	40669.41	86.49	0.30 ( 0.28)	0.92	36102.6	13010.00
10	42486.88	94.90	0.30 ( 0.28)	0.93	41663.3	10800.00
11	43014.30	99.13	0.30 ( 0.28)	0.94	44608.6	11130.00
12	42721.61	108.73	0.30 ( 0.28)	0.94	49649.8	12410.00
13	42165.54	117.00	0.30 ( 0.28)	0.94	53389.0	11201.00

14	41738.26	121.96	0.30	( 0.28)	0.95	55120.7	12201.00
15	40734.10	129.01	0.30	( 0.28)	0.95	56977.8	12231.00
16	39464.36	136.81	0.30	( 0.28)	0.95	58612.1	10400.00
17	38145.56	144.73	0.30	( 0.28)	0.95	59907.2	12010.00
18	36980.48	150.68	0.30	( 0.28)	0.95	60254.2	10210.00
19	36467.48	153.72	0.30	( 0.28)	0.95	60371.4	12000.00
20	32908.53	178.79	0.30	( 0.28)	0.95	60992.6	10100.00

TOTAL AREA (ACRES) = 60992.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13402.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 215.00 DOWNSTREAM (FEET) = 209.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 623.02 CHANNEL SLOPE = 0.0096  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 9.21  
CHANNEL FLOW THRU SUBAREA (CFS) = 43014.30  
FLOW VELOCITY (FEET/SEC.) = 18.97 FLOW DEPTH (FEET) = 9.21  
TRAVEL TIME (MIN.) = 0.55 Tc (MIN.) = 99.68  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118713.68 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24283.56	19.35	2.256	0.30 ( 0.24)	0.80	4759.1	50200.00
2	26222.00	23.94	1.969	0.30 ( 0.24)	0.81	6427.5	110.00
3	29642.21	33.40	1.625	0.30 ( 0.25)	0.82	10062.2	150.00
4	32786.62	44.24	1.383	0.30 ( 0.26)	0.85	14596.8	40200.00
5	33538.52	47.98	1.323	0.30 ( 0.26)	0.86	16466.5	390.00
6	35856.26	59.79	1.183	0.30 ( 0.27)	0.89	22195.6	13100.00
7	36765.51	66.75	1.136	0.30 ( 0.27)	0.90	25057.9	11801.00
8	38516.57	77.52	1.063	0.30 ( 0.27)	0.91	30182.3	11530.00
9	40669.41	87.05	0.999	0.30 ( 0.28)	0.92	36102.6	13010.00
10	42486.88	95.45	0.955	0.30 ( 0.28)	0.93	41663.3	10800.00
11	43014.30	99.68	0.937	0.30 ( 0.28)	0.94	44608.6	11130.00
12	42721.61	109.28	0.895	0.30 ( 0.28)	0.94	49649.8	12410.00
13	42165.54	117.55	0.860	0.30 ( 0.28)	0.94	53389.0	11201.00
14	41738.26	122.52	0.844	0.30 ( 0.28)	0.95	55120.7	12201.00
15	40734.10	129.57	0.829	0.30 ( 0.28)	0.95	56977.8	12231.00
16	39464.36	137.37	0.813	0.30 ( 0.28)	0.95	58612.1	10400.00
17	38145.56	145.30	0.797	0.30 ( 0.28)	0.95	59907.2	12010.00
18	36980.48	151.25	0.784	0.30 ( 0.28)	0.95	60254.2	10210.00
19	36467.48	154.30	0.778	0.30 ( 0.28)	0.95	60371.4	12000.00
20	32908.53	179.39	0.726	0.30 ( 0.28)	0.95	60992.6	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 43014.30 Tc (MIN.) = 99.68  
AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.94 EFFECTIVE AREA (ACRES) = 44608.64

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13402.00 TO NODE 13402.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610505X.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	265.16	19.79	0.30 ( 0.30)	0.99	153.2	50500.00

TOTAL AREA (ACRES) = 153.2

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13402.00 TO NODE 13402.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24283.56	19.35	2.256	0.30 ( 0.24)	0.80	4759.1	50200.00
2	26222.00	23.94	1.969	0.30 ( 0.24)	0.81	6427.5	110.00
3	29642.21	33.40	1.625	0.30 ( 0.25)	0.82	10062.2	150.00
4	32786.62	44.24	1.383	0.30 ( 0.26)	0.85	14596.8	40200.00
5	33538.52	47.98	1.323	0.30 ( 0.26)	0.86	16466.5	390.00
6	35856.26	59.79	1.183	0.30 ( 0.27)	0.89	22195.6	13100.00
7	36765.51	66.75	1.136	0.30 ( 0.27)	0.90	25057.9	11801.00
8	38516.57	77.52	1.063	0.30 ( 0.27)	0.91	30182.3	11530.00
9	40669.41	87.05	0.999	0.30 ( 0.28)	0.92	36102.6	13010.00
10	42486.88	95.45	0.955	0.30 ( 0.28)	0.93	41663.3	10800.00
11	43014.30	99.68	0.937	0.30 ( 0.28)	0.94	44608.6	11130.00
12	42721.61	109.28	0.895	0.30 ( 0.28)	0.94	49649.8	12410.00
13	42165.54	117.55	0.860	0.30 ( 0.28)	0.94	53389.0	11201.00
14	41738.26	122.52	0.844	0.30 ( 0.28)	0.95	55120.7	12201.00
15	40734.10	129.57	0.829	0.30 ( 0.28)	0.95	56977.8	12231.00
16	39464.36	137.37	0.813	0.30 ( 0.28)	0.95	58612.1	10400.00
17	38145.56	145.30	0.797	0.30 ( 0.28)	0.95	59907.2	12010.00
18	36980.48	151.25	0.784	0.30 ( 0.28)	0.95	60254.2	10210.00
19	36467.48	154.30	0.778	0.30 ( 0.28)	0.95	60371.4	12000.00
20	32908.53	179.39	0.726	0.30 ( 0.28)	0.95	60992.6	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118713.68 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	265.16	19.79	2.218	0.30 ( 0.30)	0.99	153.2	50500.00

LONGEST FLOWPATH FROM NODE 50500.00 TO NODE 13402.00 = 6247.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24547.92	19.35	2.256	0.30 ( 0.24)	0.81	4908.8	50200.00
2	24734.71	19.79	2.218	0.30 ( 0.24)	0.81	5072.3	50500.00
3	26452.72	23.94	1.969	0.30 ( 0.24)	0.81	6580.7	110.00
4	29825.53	33.40	1.625	0.30 ( 0.25)	0.83	10215.4	150.00
5	32936.61	44.24	1.383	0.30 ( 0.26)	0.85	14750.0	40200.00
6	33680.16	47.98	1.323	0.30 ( 0.26)	0.86	16619.7	390.00
7	35978.66	59.79	1.183	0.30 ( 0.27)	0.89	22348.8	13100.00
8	36881.33	66.75	1.136	0.30 ( 0.27)	0.90	25211.1	11801.00
9	38622.38	77.52	1.063	0.30 ( 0.27)	0.91	30335.5	11530.00
10	40766.38	87.05	0.999	0.30 ( 0.28)	0.92	36255.8	13010.00
11	42577.85	95.45	0.955	0.30 ( 0.28)	0.93	41816.5	10800.00

12 43102.74 99.68 0.937 0.30( 0.28) 0.94 44761.8 11130.00  
 13 42804.31 109.28 0.895 0.30( 0.28) 0.94 49803.0 12410.00  
 14 42243.29 117.55 0.860 0.30( 0.28) 0.94 53542.1 11201.00  
 15 41813.84 122.52 0.844 0.30( 0.28) 0.95 55273.8 12201.00  
 16 40807.67 129.57 0.829 0.30( 0.28) 0.95 57131.0 12231.00  
 17 39535.70 137.37 0.813 0.30( 0.28) 0.95 58765.3 10400.00  
 18 38214.64 145.30 0.797 0.30( 0.28) 0.95 60060.4 12010.00  
 19 37047.87 151.25 0.784 0.30( 0.28) 0.95 60407.3 10210.00  
 20 36534.00 154.30 0.778 0.30( 0.28) 0.95 60524.6 12000.00  
 21 32967.89 179.39 0.726 0.30( 0.28) 0.95 61145.8 10100.00  
 TOTAL AREA (ACRES) = 61145.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 43102.74 Tc (MIN.) = 99.679  
 EFFECTIVE AREA (ACRES) = 44761.82 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 61145.8  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118713.68 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13402.00 TO NODE 13404.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 209.00 DOWNSTREAM (FEET) = 207.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 395.35 CHANNEL SLOPE = 0.0051  
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 11.06  
 CHANNEL FLOW THRU SUBAREA (CFS) = 43102.74  
 FLOW VELOCITY (FEET/SEC.) = 15.27 FLOW DEPTH (FEET) = 11.06  
 TRAVEL TIME (MIN.) = 0.43 Tc (MIN.) = 100.11  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119109.03 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24547.92	19.86	2.212	0.30( 0.24)	0.81	4908.8	50200.00
2	24734.71	20.30	2.182	0.30( 0.24)	0.81	5072.3	50500.00
3	26452.72	24.44	1.939	0.30( 0.24)	0.81	6580.7	110.00
4	29825.53	33.88	1.612	0.30( 0.25)	0.83	10215.4	150.00
5	32936.61	44.71	1.376	0.30( 0.26)	0.85	14750.0	40200.00
6	33680.16	48.44	1.315	0.30( 0.26)	0.86	16619.7	390.00
7	35978.66	60.25	1.179	0.30( 0.27)	0.89	22348.8	13100.00
8	36881.33	67.20	1.133	0.30( 0.27)	0.90	25211.1	11801.00
9	38622.38	77.97	1.060	0.30( 0.27)	0.91	30335.5	11530.00
10	40766.38	87.49	0.996	0.30( 0.28)	0.92	36255.8	13010.00
11	42577.85	95.88	0.954	0.30( 0.28)	0.93	41816.5	10800.00
12	43102.74	100.11	0.935	0.30( 0.28)	0.94	44761.8	11130.00
13	42804.31	109.71	0.894	0.30( 0.28)	0.94	49803.0	12410.00
14	42243.29	117.99	0.858	0.30( 0.28)	0.94	53542.1	11201.00
15	41813.84	122.95	0.843	0.30( 0.28)	0.95	55273.8	12201.00
16	40807.67	130.01	0.828	0.30( 0.28)	0.95	57131.0	12231.00
17	39535.70	137.81	0.812	0.30( 0.28)	0.95	58765.3	10400.00
18	38214.64	145.75	0.796	0.30( 0.28)	0.95	60060.4	12010.00
19	37047.87	151.71	0.783	0.30( 0.28)	0.95	60407.3	10210.00
20	36534.00	154.75	0.777	0.30( 0.28)	0.95	60524.6	12000.00

21 32967.89 179.86 0.725 0.30( 0.28) 0.95 61145.8 10100.00  
 NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE (CFS) = 43102.74 Tc (MIN.) = 100.11  
 AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.94 EFFECTIVE AREA (ACRES) = 44761.82

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13404.00 TO NODE 13404.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610506X.DNA  
 MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	94.69	17.43	0.30( 0.30)	1.00	49.6	50600.00
TOTAL AREA (ACRES) = 49.6						

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13404.00 TO NODE 13404.00 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24547.92	19.86	2.212	0.30( 0.24)	0.81	4908.8	50200.00
2	24734.71	20.30	2.182	0.30( 0.24)	0.81	5072.3	50500.00
3	26452.72	24.44	1.939	0.30( 0.24)	0.81	6580.7	110.00
4	29825.53	33.88	1.612	0.30( 0.25)	0.83	10215.4	150.00
5	32936.61	44.71	1.376	0.30( 0.26)	0.85	14750.0	40200.00
6	33680.16	48.44	1.315	0.30( 0.26)	0.86	16619.7	390.00
7	35978.66	60.25	1.179	0.30( 0.27)	0.89	22348.8	13100.00
8	36881.33	67.20	1.133	0.30( 0.27)	0.90	25211.1	11801.00
9	38622.38	77.97	1.060	0.30( 0.27)	0.91	30335.5	11530.00
10	40766.38	87.49	0.996	0.30( 0.28)	0.92	36255.8	13010.00
11	42577.85	95.88	0.954	0.30( 0.28)	0.93	41816.5	10800.00
12	43102.74	100.11	0.935	0.30( 0.28)	0.94	44761.8	11130.00
13	42804.31	109.71	0.894	0.30( 0.28)	0.94	49803.0	12410.00
14	42243.29	117.99	0.858	0.30( 0.28)	0.94	53542.1	11201.00
15	41813.84	122.95	0.843	0.30( 0.28)	0.95	55273.8	12201.00
16	40807.67	130.01	0.828	0.30( 0.28)	0.95	57131.0	12231.00
17	39535.70	137.81	0.812	0.30( 0.28)	0.95	58765.3	10400.00
18	38214.64	145.75	0.796	0.30( 0.28)	0.95	60060.4	12010.00
19	37047.87	151.71	0.783	0.30( 0.28)	0.95	60407.3	10210.00
20	36534.00	154.75	0.777	0.30( 0.28)	0.95	60524.6	12000.00
21	32967.89	179.86	0.725	0.30( 0.28)	0.95	61145.8	10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119109.03 FEET.							

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	94.69	17.43	2.420	0.30( 0.30)	1.00	49.6	50600.00
LONGEST FLOWPATH FROM NODE 50600.00 TO NODE 13404.00 = 4378.00 FEET.							

\*\* PEAK FLOW RATE TABLE \*\*

STREAM	Q	Tc	Intensity	Fp (Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	---------	----	----	-----------



NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	23918.22	17.43	2.420	0.30 ( 0.24)	0.81	4357.0 50600.00
2	24633.28	19.86	2.212	0.30 ( 0.24)	0.81	4958.4 50200.00
3	24818.75	20.30	2.182	0.30 ( 0.24)	0.81	5121.9 50500.00
4	26525.90	24.44	1.939	0.30 ( 0.24)	0.81	6630.3 110.00
5	29884.12	33.88	1.612	0.30 ( 0.25)	0.83	10265.0 150.00
6	32984.65	44.71	1.376	0.30 ( 0.26)	0.85	14799.6 40200.00
7	33725.50	48.44	1.315	0.30 ( 0.26)	0.86	16669.2 390.00
8	36017.92	60.25	1.179	0.30 ( 0.27)	0.89	22398.4 13100.00
9	36918.50	67.20	1.133	0.30 ( 0.27)	0.90	25260.7 11801.00
10	38656.32	77.97	1.060	0.30 ( 0.27)	0.91	30385.1 11530.00
11	40797.46	87.49	0.996	0.30 ( 0.28)	0.92	36305.3 13010.00
12	42607.03	95.88	0.954	0.30 ( 0.28)	0.93	41866.1 10800.00
13	43131.11	100.11	0.935	0.30 ( 0.28)	0.94	44811.4 11130.00
14	42830.82	109.71	0.894	0.30 ( 0.28)	0.94	49852.6 12410.00
15	42268.20	117.99	0.858	0.30 ( 0.28)	0.94	53591.7 11201.00
16	41838.09	122.95	0.843	0.30 ( 0.28)	0.95	55323.4 12201.00
17	40831.26	130.01	0.828	0.30 ( 0.28)	0.95	57180.6 12231.00
18	39558.58	137.81	0.812	0.30 ( 0.28)	0.95	58814.9 10400.00
19	38236.78	145.75	0.796	0.30 ( 0.28)	0.95	60110.0 12010.00
20	37069.46	151.71	0.783	0.30 ( 0.28)	0.95	60456.9 10210.00
21	36555.31	154.75	0.777	0.30 ( 0.28)	0.95	60574.1 12000.00
22	32986.89	179.86	0.725	0.30 ( 0.28)	0.95	61195.4 10100.00
TOTAL AREA (ACRES) = 61195.4						

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 43131.11 Tc (MIN.) = 100.111  
EFFECTIVE AREA (ACRES) = 44811.41 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA (ACRES) = 61195.4  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119109.03 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13404.00 TO NODE 13406.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 207.00 DOWNSTREAM (FEET) = 195.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1601.97 CHANNEL SLOPE = 0.0075  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 9.91  
CHANNEL FLOW THRU SUBAREA (CFS) = 43131.11  
FLOW VELOCITY (FEET/SEC.) = 17.45 FLOW DEPTH (FEET) = 9.91  
TRAVEL TIME (MIN.) = 1.53 Tc (MIN.) = 101.64  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13406.00 = 120711.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23918.22	19.29	2.261	0.30 ( 0.24)	0.81	4357.0	50600.00
2	24633.28	21.71	2.100	0.30 ( 0.24)	0.81	4958.4	50200.00
3	24818.75	22.14	2.074	0.30 ( 0.24)	0.81	5121.9	50500.00
4	26525.90	26.24	1.859	0.30 ( 0.24)	0.81	6630.3	110.00
5	29884.12	35.61	1.567	0.30 ( 0.25)	0.83	10265.0	150.00
6	32984.65	46.38	1.349	0.30 ( 0.26)	0.85	14799.6	40200.00
7	33725.50	50.10	1.289	0.30 ( 0.26)	0.86	16669.2	390.00

8	36017.92	61.87	1.168	0.30 ( 0.27)	0.89	22398.4	13100.00
9	36918.50	68.81	1.122	0.30 ( 0.27)	0.90	25260.7	11801.00
10	38656.32	79.55	1.049	0.30 ( 0.27)	0.91	30385.1	11530.00
11	40797.46	89.04	0.985	0.30 ( 0.28)	0.92	36305.3	13010.00
12	42607.03	97.42	0.947	0.30 ( 0.28)	0.93	41866.1	10800.00
13	43131.11	101.64	0.929	0.30 ( 0.28)	0.94	44811.4	11130.00
14	42830.82	111.24	0.887	0.30 ( 0.28)	0.94	49852.6	12410.00
15	42268.20	119.53	0.851	0.30 ( 0.28)	0.94	53591.7	11201.00
16	41838.09	124.50	0.840	0.30 ( 0.28)	0.95	55323.4	12201.00
17	40831.26	131.57	0.825	0.30 ( 0.28)	0.95	57180.6	12231.00
18	39558.58	139.39	0.809	0.30 ( 0.28)	0.95	58814.9	10400.00
19	38236.78	147.34	0.793	0.30 ( 0.28)	0.95	60110.0	12010.00
20	37069.46	153.31	0.780	0.30 ( 0.28)	0.95	60456.9	10210.00
21	36555.31	156.37	0.774	0.30 ( 0.28)	0.95	60574.1	12000.00
22	32986.89	181.53	0.723	0.30 ( 0.28)	0.95	61195.4	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 43131.11 Tc (MIN.) = 101.64  
AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.94 EFFECTIVE AREA (ACRES) = 44811.41

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 101.64  
\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.929  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "GRASS"	B	0.20	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	4.00	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	2.00	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	9.70	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	2.60	0.30	1.000	66
AGRICULTURAL POOR COVER "ROW CROPS, STRAIGHT ROW"	B	1.80	0.30	1.000	81

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 20.30 SUBAREA RUNOFF (CFS) = 11.48  
EFFECTIVE AREA (ACRES) = 44831.71 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94  
TOTAL AREA (ACRES) = 61215.7 PEAK FLOW RATE (CFS) = 43131.11  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 101.64  
\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.929  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "ROW CROPS, STRAIGHT ROW"	B	3.50	0.30	1.000	81
NATURAL FAIR COVER "WOODLAND, GRASS"	B	7.20	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND, GRASS"	B	5.80	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.10	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 16.60 SUBAREA RUNOFF (CFS) = 9.39  
EFFECTIVE AREA (ACRES) = 44848.32 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94  
TOTAL AREA (ACRES) = 61232.3 PEAK FLOW RATE (CFS) = 43131.11  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 1 <<<<<<  
=====

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<<  
=====

PEAK FLOWRATE TABLE FILE NAME: 2P50EVBB.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	748.33	9.86	0.30 ( 0.11)	0.38	244.2	429.00
2	793.01	11.37	0.30 ( 0.11)	0.38	281.3	425.00
3	804.73	11.79	0.30 ( 0.11)	0.38	291.7	400.00
4	836.36	13.23	0.30 ( 0.11)	0.38	327.6	300.00
5	892.30	18.33	0.30 ( 0.11)	0.38	440.3	210.00
6	879.40	20.37	0.30 ( 0.11)	0.38	466.7	410.00
7	872.79	21.37	0.30 ( 0.11)	0.38	479.4	200.00
8	870.12	21.98	0.30 ( 0.11)	0.38	486.6	230.00
9	849.67	23.09	0.30 ( 0.11)	0.37	491.2	220.50

TOTAL AREA (ACRES) = 491.2

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<<  
=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23918.22	19.29	2.261	0.30 ( 0.24)	0.81	4393.9	50600.00
2	24633.28	21.71	2.100	0.30 ( 0.24)	0.81	4995.3	50200.00
3	24818.75	22.14	2.074	0.30 ( 0.24)	0.81	5158.8	50500.00
4	26525.90	26.24	1.859	0.30 ( 0.24)	0.81	6667.2	110.00
5	29884.12	35.61	1.567	0.30 ( 0.25)	0.83	10301.9	150.00

6	32984.65	46.38	1.349	0.30 ( 0.26)	0.85	14836.5	40200.00
7	33725.50	50.10	1.289	0.30 ( 0.26)	0.86	16706.1	390.00
8	36017.92	61.87	1.168	0.30 ( 0.27)	0.89	22435.3	13100.00
9	36918.50	68.81	1.122	0.30 ( 0.27)	0.90	25297.6	11801.00
10	38656.32	79.55	1.049	0.30 ( 0.27)	0.91	30422.0	11530.00
11	40797.46	89.04	0.985	0.30 ( 0.28)	0.92	36342.2	13010.00
12	42607.03	97.42	0.947	0.30 ( 0.28)	0.93	41903.0	10800.00
13	43131.11	101.64	0.929	0.30 ( 0.28)	0.94	44848.3	11130.00
14	42830.82	111.24	0.887	0.30 ( 0.28)	0.94	49889.5	12410.00
15	42268.20	119.53	0.851	0.30 ( 0.28)	0.94	53628.6	11201.00
16	41838.09	124.50	0.840	0.30 ( 0.28)	0.95	55360.3	12201.00
17	40831.26	131.57	0.825	0.30 ( 0.28)	0.95	57217.5	12231.00
18	39558.58	139.39	0.809	0.30 ( 0.28)	0.95	58851.8	10400.00
19	38236.78	147.34	0.793	0.30 ( 0.28)	0.95	60146.9	12010.00
20	37069.46	153.31	0.780	0.30 ( 0.28)	0.95	60493.8	10210.00
21	36555.31	156.37	0.774	0.30 ( 0.28)	0.95	60611.1	12000.00
22	32986.89	181.53	0.723	0.30 ( 0.28)	0.95	61232.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13406.00 = 120711.00 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	748.33	9.86	3.472	0.30 ( 0.11)	0.38	244.2	429.00
2	793.01	11.37	3.204	0.30 ( 0.11)	0.38	281.3	425.00
3	804.73	11.79	3.137	0.30 ( 0.11)	0.38	291.7	400.00
4	836.36	13.23	2.909	0.30 ( 0.11)	0.38	327.6	300.00
5	892.30	18.33	2.343	0.30 ( 0.11)	0.38	440.3	210.00
6	879.40	20.37	2.178	0.30 ( 0.11)	0.38	466.7	410.00
7	872.79	21.37	2.119	0.30 ( 0.11)	0.38	479.4	200.00
8	870.12	21.98	2.083	0.30 ( 0.11)	0.38	486.6	230.00
9	849.67	23.09	2.018	0.30 ( 0.11)	0.37	491.2	220.50

LONGEST FLOWPATH FROM NODE 230.00 TO NODE 13406.00 = 11903.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20314.35	9.86	3.472	0.30 ( 0.23)	0.77	2490.2	429.00
2	21471.93	11.37	3.204	0.30 ( 0.23)	0.77	2870.5	425.00
3	21766.37	11.79	3.137	0.30 ( 0.23)	0.77	2976.5	400.00
4	22508.72	13.23	2.909	0.30 ( 0.23)	0.77	3341.2	300.00
5	24547.86	18.33	2.343	0.30 ( 0.23)	0.77	4615.5	210.00
6	24804.44	19.29	2.261	0.30 ( 0.23)	0.77	4846.7	50600.00
7	25117.43	20.37	2.178	0.30 ( 0.23)	0.77	5129.6	410.00
8	25406.56	21.37	2.119	0.30 ( 0.23)	0.77	5391.0	200.00
9	25504.61	21.71	2.100	0.30 ( 0.23)	0.77	5478.7	50200.00
10	25622.15	21.98	2.083	0.30 ( 0.23)	0.77	5586.6	230.00
11	25685.98	22.14	2.074	0.30 ( 0.23)	0.77	5646.1	50500.00
12	26063.36	23.09	2.018	0.30 ( 0.23)	0.77	5999.0	220.50
13	27304.28	26.24	1.859	0.30 ( 0.23)	0.78	7158.4	110.00
14	30532.54	35.61	1.567	0.30 ( 0.24)	0.81	10793.1	150.00
15	33535.74	46.38	1.349	0.30 ( 0.25)	0.84	15327.7	40200.00
16	34249.95	50.10	1.289	0.30 ( 0.25)	0.85	17197.3	390.00
17	36488.66	61.87	1.168	0.30 ( 0.26)	0.88	22926.5	13100.00
18	37368.41	68.81	1.122	0.30 ( 0.27)	0.89	25788.8	11801.00
19	39073.99	79.55	1.049	0.30 ( 0.27)	0.90	30913.2	11530.00
20	41186.63	89.04	0.985	0.30 ( 0.27)	0.91	36833.4	13010.00
21	42979.00	97.42	0.947	0.30 ( 0.28)	0.93	42394.2	10800.00
22	43494.92	101.64	0.929	0.30 ( 0.28)	0.93	45339.5	11130.00

23	43176.09	111.24	0.887	0.30	( 0.28)	0.94	50380.7	12410.00
24	42597.46	119.53	0.851	0.30	( 0.28)	0.94	54119.8	11201.00
25	42162.29	124.50	0.840	0.30	( 0.28)	0.94	55851.5	12201.00
26	41148.96	131.57	0.825	0.30	( 0.28)	0.94	57708.7	12231.00
27	39869.07	139.39	0.809	0.30	( 0.28)	0.94	59343.0	10400.00
28	38539.95	147.34	0.793	0.30	( 0.28)	0.94	60638.1	12010.00
29	37367.12	153.31	0.780	0.30	( 0.28)	0.94	60985.0	10210.00
30	36850.16	156.37	0.774	0.30	( 0.28)	0.94	61102.2	12000.00
31	33259.24	181.53	0.723	0.30	( 0.28)	0.95	61723.5	10100.00

TOTAL AREA (ACRES) = 61723.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 43494.92 Tc (MIN.) = 101.641  
EFFECTIVE AREA (ACRES) = 45339.52 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.78  
TOTAL AREA (ACRES) = 61723.5  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13406.00 = 120711.00 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13406.00 TO NODE 13408.00 IS CODE = 56

>>>> COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>> TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 195.00 DOWNSTREAM (FEET) = 182.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 2458.36 CHANNEL SLOPE = 0.0053  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 10.98  
\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.917

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.00	0.30	1.000	-
USER-DEFINED	-	3.30	0.30	1.000	-
USER-DEFINED	-	0.40	0.30	0.100	-
USER-DEFINED	-	1.40	0.30	1.000	-
USER-DEFINED	-	0.30	0.30	0.100	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.949  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 43498.45  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 15.55  
AVERAGE FLOW DEPTH (FEET) = 10.98 TRAVEL TIME (MIN.) = 2.64  
Tc (MIN.) = 104.28  
SUBAREA AREA (ACRES) = 12.40 SUBAREA RUNOFF (CFS) = 7.06  
EFFECTIVE AREA (ACRES) = 45351.91 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA (ACRES) = 61735.9 PEAK FLOW RATE (CFS) = 43494.92  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 10.98  
  
END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 10.98 FLOW VELOCITY (FEET/SEC.) = 15.55  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123169.36 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20314.35	13.25	2.906	0.30 ( 0.23)	0.77	2502.6	429.00
2	21471.93	14.69	2.678	0.30 ( 0.23)	0.77	2882.9	425.00
3	21766.37	15.09	2.621	0.30 ( 0.23)	0.77	2988.9	400.00
4	22508.72	16.50	2.500	0.30 ( 0.23)	0.77	3353.6	300.00
5	24547.86	21.51	2.111	0.30 ( 0.23)	0.77	4627.9	210.00
6	24804.44	22.46	2.055	0.30 ( 0.23)	0.77	4859.1	50600.00
7	25117.43	23.52	1.993	0.30 ( 0.23)	0.77	5142.0	410.00
8	25406.56	24.51	1.935	0.30 ( 0.23)	0.77	5403.4	200.00
9	25504.61	24.84	1.915	0.30 ( 0.23)	0.77	5491.1	50200.00
10	25622.15	25.11	1.902	0.30 ( 0.23)	0.77	5599.0	230.00
11	25685.98	25.27	1.896	0.30 ( 0.23)	0.77	5658.5	50500.00
12	26063.36	26.20	1.860	0.30 ( 0.23)	0.77	6011.4	220.50
13	27304.28	29.30	1.741	0.30 ( 0.23)	0.78	7170.8	110.00
14	30532.54	38.57	1.490	0.30 ( 0.24)	0.81	10805.5	150.00
15	33535.74	49.24	1.302	0.30 ( 0.25)	0.84	15340.1	40200.00
16	34249.95	52.95	1.258	0.30 ( 0.25)	0.85	17209.7	390.00
17	36488.66	64.66	1.150	0.30 ( 0.26)	0.88	22938.9	13100.00
18	37368.41	71.58	1.103	0.30 ( 0.27)	0.89	25801.2	11801.00
19	39073.99	82.28	1.031	0.30 ( 0.27)	0.90	30925.6	11530.00
20	41186.63	91.73	0.972	0.30 ( 0.27)	0.91	36845.8	13010.00
21	42979.00	100.07	0.935	0.30 ( 0.28)	0.93	42406.6	10800.00
22	43494.92	104.28	0.917	0.30 ( 0.28)	0.93	45351.9	11130.00
23	43176.09	113.88	0.876	0.30 ( 0.28)	0.94	50393.1	12410.00
24	42597.46	122.18	0.844	0.30 ( 0.28)	0.94	54132.2	11201.00
25	42162.29	127.16	0.834	0.30 ( 0.28)	0.94	55863.9	12201.00
26	41148.96	134.25	0.820	0.30 ( 0.28)	0.94	57721.1	12231.00
27	39869.07	142.10	0.803	0.30 ( 0.28)	0.94	59355.4	10400.00
28	38539.95	150.08	0.787	0.30 ( 0.28)	0.94	60650.5	12010.00
29	37367.12	156.08	0.774	0.30 ( 0.28)	0.94	60997.4	10210.00
30	36850.16	159.15	0.768	0.30 ( 0.28)	0.94	61114.6	12000.00
31	33259.24	184.40	0.720	0.30 ( 0.28)	0.95	61735.9	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 43494.92 Tc (MIN.) = 104.28  
AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA (ACRES) = 45351.91

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 12

>>>> CLEAR MEMORY BANK # 2 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 15.1

>>>> DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610507X.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	406.61	19.94	0.30 ( 0.30)	0.99	236.8	50700.00
TOTAL AREA (ACRES) =		236.8				

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 11

=====  
 >>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<  
 =====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20314.35	13.25	2.906	0.30 ( 0.23)	0.77	2502.6	429.00
2	21471.93	14.69	2.678	0.30 ( 0.23)	0.77	2882.9	425.00
3	21766.37	15.09	2.621	0.30 ( 0.23)	0.77	2988.9	400.00
4	22508.72	16.50	2.500	0.30 ( 0.23)	0.77	3353.6	300.00
5	24547.86	21.51	2.111	0.30 ( 0.23)	0.77	4627.9	210.00
6	24804.44	22.46	2.055	0.30 ( 0.23)	0.77	4859.1	50600.00
7	25117.43	23.52	1.993	0.30 ( 0.23)	0.77	5142.0	410.00
8	25406.56	24.51	1.935	0.30 ( 0.23)	0.77	5403.4	200.00
9	25504.61	24.84	1.915	0.30 ( 0.23)	0.77	5491.1	50200.00
10	25622.15	25.11	1.902	0.30 ( 0.23)	0.77	5599.0	230.00
11	25685.98	25.27	1.896	0.30 ( 0.23)	0.77	5658.5	50500.00
12	26063.36	26.20	1.860	0.30 ( 0.23)	0.77	6011.4	220.50
13	27304.28	29.30	1.741	0.30 ( 0.23)	0.78	7170.8	110.00
14	30532.54	38.57	1.490	0.30 ( 0.24)	0.81	10805.5	150.00
15	33535.74	49.24	1.302	0.30 ( 0.25)	0.84	15340.1	40200.00
16	34249.95	52.95	1.258	0.30 ( 0.25)	0.85	17209.7	390.00
17	36488.66	64.66	1.150	0.30 ( 0.26)	0.88	22938.9	13100.00
18	37368.41	71.58	1.103	0.30 ( 0.27)	0.89	25801.2	11801.00
19	39073.99	82.28	1.031	0.30 ( 0.27)	0.90	30925.6	11530.00
20	41186.63	91.73	0.972	0.30 ( 0.27)	0.91	36845.8	13010.00
21	42979.00	100.07	0.935	0.30 ( 0.28)	0.93	42406.6	10800.00
22	43494.92	104.28	0.917	0.30 ( 0.28)	0.93	45351.9	11130.00
23	43176.09	113.88	0.876	0.30 ( 0.28)	0.94	50393.1	12410.00
24	42597.46	122.18	0.844	0.30 ( 0.28)	0.94	54132.2	11201.00
25	42162.29	127.16	0.834	0.30 ( 0.28)	0.94	55863.9	12201.00
26	41148.96	134.25	0.820	0.30 ( 0.28)	0.94	57721.1	12231.00
27	39869.07	142.10	0.803	0.30 ( 0.28)	0.94	59355.4	10400.00
28	38539.95	150.08	0.787	0.30 ( 0.28)	0.94	60650.5	12010.00
29	37367.12	156.08	0.774	0.30 ( 0.28)	0.94	60997.4	10210.00
30	36850.16	159.15	0.768	0.30 ( 0.28)	0.94	61114.6	12000.00
31	33259.24	184.40	0.720	0.30 ( 0.28)	0.95	61735.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123169.36 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	406.61	19.94	2.205	0.30 ( 0.30)	0.99	236.8	50700.00

LONGEST FLOWPATH FROM NODE 50700.00 TO NODE 13408.00 = 7903.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20683.78	13.25	2.906	0.30 ( 0.23)	0.78	2659.9	429.00
2	21845.75	14.69	2.678	0.30 ( 0.23)	0.78	3057.3	425.00
3	22141.25	15.09	2.621	0.30 ( 0.23)	0.78	3168.1	400.00
4	22897.26	16.50	2.500	0.30 ( 0.23)	0.78	3549.6	300.00
5	24316.69	19.94	2.205	0.30 ( 0.23)	0.78	4466.1	50700.00
6	24934.51	21.51	2.111	0.30 ( 0.23)	0.78	4864.7	210.00
7	25179.20	22.46	2.055	0.30 ( 0.23)	0.78	5095.9	50600.00
8	25478.83	23.52	1.993	0.30 ( 0.23)	0.78	5378.8	410.00
9	25755.59	24.51	1.935	0.30 ( 0.23)	0.78	5640.2	200.00

10	25849.49	24.84	1.915	0.30 ( 0.23)	0.78	5727.9	50200.00
11	25964.11	25.11	1.902	0.30 ( 0.23)	0.78	5835.8	230.00
12	26026.67	25.27	1.896	0.30 ( 0.23)	0.78	5895.3	50500.00
13	26396.41	26.20	1.860	0.30 ( 0.23)	0.78	6248.2	220.50
14	27611.93	29.30	1.741	0.30 ( 0.24)	0.79	7407.6	110.00
15	30786.65	38.57	1.490	0.30 ( 0.24)	0.81	11042.3	150.00
16	33749.91	49.24	1.302	0.30 ( 0.25)	0.84	15576.9	40200.00
17	34454.66	52.95	1.258	0.30 ( 0.25)	0.85	17446.5	390.00
18	36670.29	64.66	1.150	0.30 ( 0.26)	0.88	23175.7	13100.00
19	37540.11	71.58	1.103	0.30 ( 0.27)	0.89	26038.0	11801.00
20	39230.32	82.28	1.031	0.30 ( 0.27)	0.90	31162.3	11530.00
21	41330.29	91.73	0.972	0.30 ( 0.27)	0.91	37082.6	13010.00
22	43114.95	100.07	0.935	0.30 ( 0.28)	0.93	42643.4	10800.00
23	43626.98	104.28	0.917	0.30 ( 0.28)	0.93	45588.7	11130.00
24	43299.27	113.88	0.876	0.30 ( 0.28)	0.94	50629.9	12410.00
25	42714.04	122.18	0.844	0.30 ( 0.28)	0.94	54369.0	11201.00
26	42276.67	127.16	0.834	0.30 ( 0.28)	0.94	56100.7	12201.00
27	41260.21	134.25	0.820	0.30 ( 0.28)	0.94	57957.9	12231.00
28	39976.87	142.10	0.803	0.30 ( 0.28)	0.94	59592.2	10400.00
29	38644.23	150.08	0.787	0.30 ( 0.28)	0.94	60887.3	12010.00
30	37468.75	156.08	0.774	0.30 ( 0.28)	0.94	61234.2	10210.00
31	36950.44	159.15	0.768	0.30 ( 0.28)	0.94	61351.4	12000.00
32	33349.34	184.40	0.720	0.30 ( 0.28)	0.95	61972.7	10100.00

TOTAL AREA (ACRES) = 61972.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 43626.98 Tc (MIN.) = 104.276  
 EFFECTIVE AREA (ACRES) = 45588.70 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 61972.7  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123169.36 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13408.00 TO NODE 13410.00 IS CODE = 56  
 \*\*\*\*\*

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM (FEET) = 182.00 DOWNSTREAM (FEET) = 178.72  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 952.73 CHANNEL SLOPE = 0.0034  
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 12.39  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.912  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 0.40 0.30 1.000 -  
 USER-DEFINED - 2.90 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 43627.89  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 13.44  
 AVERAGE FLOW DEPTH (FEET) = 12.39 TRAVEL TIME (MIN.) = 1.18  
 Tc (MIN.) = 105.46  
 SUBAREA AREA (ACRES) = 3.30 SUBAREA RUNOFF (CFS) = 1.82  
 EFFECTIVE AREA (ACRES) = 45592.00 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA (ACRES) = 61976.0 PEAK FLOW RATE (CFS) = 43626.98  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 12.39

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 12.39 FLOW VELOCITY (FEET/SEC.) = 13.44  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124122.09 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20683.78	14.75	2.668	0.30 ( 0.23)	0.78	2663.2	429.00
2	21845.75	16.17	2.529	0.30 ( 0.23)	0.78	3060.6	425.00
3	22141.25	16.56	2.495	0.30 ( 0.23)	0.78	3171.4	400.00
4	22897.26	17.96	2.375	0.30 ( 0.23)	0.78	3552.9	300.00
5	24316.69	21.37	2.120	0.30 ( 0.23)	0.78	4469.4	50700.00
6	24934.51	22.92	2.028	0.30 ( 0.23)	0.78	4868.0	210.00
7	25179.20	23.87	1.973	0.30 ( 0.23)	0.78	5099.2	50600.00
8	25478.83	24.93	1.910	0.30 ( 0.23)	0.78	5382.1	410.00
9	25755.59	25.91	1.871	0.30 ( 0.23)	0.78	5643.5	200.00
10	25849.49	26.24	1.858	0.30 ( 0.23)	0.78	5731.2	50200.00
11	25964.11	26.51	1.848	0.30 ( 0.23)	0.78	5839.1	230.00
12	26026.67	26.66	1.842	0.30 ( 0.23)	0.78	5898.6	50500.00
13	26396.41	27.59	1.807	0.30 ( 0.23)	0.78	6251.5	220.50
14	27611.93	30.67	1.696	0.30 ( 0.24)	0.79	7410.9	110.00
15	30786.65	39.89	1.455	0.30 ( 0.24)	0.81	11045.6	150.00
16	33749.91	50.53	1.284	0.30 ( 0.25)	0.84	15580.2	40200.00
17	34454.66	54.22	1.244	0.30 ( 0.25)	0.85	17449.8	390.00
18	36670.29	65.91	1.141	0.30 ( 0.26)	0.88	23179.0	13100.00
19	37540.11	72.82	1.095	0.30 ( 0.27)	0.89	26041.3	11801.00
20	39230.32	83.50	1.023	0.30 ( 0.27)	0.90	31165.6	11530.00
21	41330.29	92.93	0.966	0.30 ( 0.27)	0.91	37085.9	13010.00
22	43114.95	101.25	0.930	0.30 ( 0.28)	0.93	42646.7	10800.00
23	43626.98	105.46	0.912	0.30 ( 0.28)	0.93	45592.0	11130.00
24	43299.27	115.07	0.870	0.30 ( 0.28)	0.94	50633.2	12410.00
25	42714.04	123.37	0.842	0.30 ( 0.28)	0.94	54372.3	11201.00
26	42276.67	128.35	0.832	0.30 ( 0.28)	0.94	56104.0	12201.00
27	41260.21	135.45	0.817	0.30 ( 0.28)	0.94	57961.2	12231.00
28	39976.87	143.31	0.801	0.30 ( 0.28)	0.94	59595.5	10400.00
29	38644.23	151.30	0.784	0.30 ( 0.28)	0.94	60890.6	12010.00
30	37468.75	157.32	0.772	0.30 ( 0.28)	0.94	61237.5	10210.00
31	36950.44	160.39	0.766	0.30 ( 0.28)	0.94	61354.7	12000.00
32	33349.34	185.69	0.719	0.30 ( 0.28)	0.95	61976.0	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 43626.98 Tc (MIN.) = 105.46  
 AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA (ACRES) = 45592.00

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: RI50EV36.DNA  
 MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2426.61	27.79	0.30 ( 0.27)	0.90	1478.1	110.00
2	2523.08	30.18	0.30 ( 0.27)	0.90	1650.5	100.00
3	2535.23	31.37	0.30 ( 0.27)	0.90	1727.1	100.00
4	2565.50	34.38	0.30 ( 0.27)	0.91	1904.1	130.00
5	2700.64	47.40	0.30 ( 0.28)	0.93	2638.7	20100.00
6	2620.76	52.90	0.30 ( 0.28)	0.93	2824.4	13600.00
7	2498.72	87.84	0.30 ( 0.28)	0.93	3795.6	13510.00
8	2354.93	96.73	0.30 ( 0.28)	0.93	3859.7	13500.00

TOTAL AREA (ACRES) = 3859.7

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	20683.78	14.75	2.668	0.30 ( 0.23)	0.78	2663.2	429.00
2	21845.75	16.17	2.529	0.30 ( 0.23)	0.78	3060.6	425.00
3	22141.25	16.56	2.495	0.30 ( 0.23)	0.78	3171.4	400.00
4	22897.26	17.96	2.375	0.30 ( 0.23)	0.78	3552.9	300.00
5	24316.69	21.37	2.120	0.30 ( 0.23)	0.78	4469.4	50700.00
6	24934.51	22.92	2.028	0.30 ( 0.23)	0.78	4868.0	210.00
7	25179.20	23.87	1.973	0.30 ( 0.23)	0.78	5099.2	50600.00
8	25478.83	24.93	1.910	0.30 ( 0.23)	0.78	5382.1	410.00
9	25755.59	25.91	1.871	0.30 ( 0.23)	0.78	5643.5	200.00
10	25849.49	26.24	1.858	0.30 ( 0.23)	0.78	5731.2	50200.00
11	25964.11	26.51	1.848	0.30 ( 0.23)	0.78	5839.1	230.00
12	26026.67	26.66	1.842	0.30 ( 0.23)	0.78	5898.6	50500.00
13	26396.41	27.59	1.807	0.30 ( 0.23)	0.78	6251.5	220.50
14	27611.93	30.67	1.696	0.30 ( 0.24)	0.79	7410.9	110.00
15	30786.65	39.89	1.455	0.30 ( 0.24)	0.81	11045.6	150.00
16	33749.91	50.53	1.284	0.30 ( 0.25)	0.84	15580.2	40200.00
17	34454.66	54.22	1.244	0.30 ( 0.25)	0.85	17449.8	390.00
18	36670.29	65.91	1.141	0.30 ( 0.26)	0.88	23179.0	13100.00
19	37540.11	72.82	1.095	0.30 ( 0.27)	0.89	26041.3	11801.00
20	39230.32	83.50	1.023	0.30 ( 0.27)	0.90	31165.6	11530.00
21	41330.29	92.93	0.966	0.30 ( 0.27)	0.91	37085.9	13010.00
22	43114.95	101.25	0.930	0.30 ( 0.28)	0.93	42646.7	10800.00
23	43626.98	105.46	0.912	0.30 ( 0.28)	0.93	45592.0	11130.00
24	43299.27	115.07	0.870	0.30 ( 0.28)	0.94	50633.2	12410.00
25	42714.04	123.37	0.842	0.30 ( 0.28)	0.94	54372.3	11201.00
26	42276.67	128.35	0.832	0.30 ( 0.28)	0.94	56104.0	12201.00
27	41260.21	135.45	0.817	0.30 ( 0.28)	0.94	57961.2	12231.00
28	39976.87	143.31	0.801	0.30 ( 0.28)	0.94	59595.5	10400.00
29	38644.23	151.30	0.784	0.30 ( 0.28)	0.94	60890.6	12010.00
30	37468.75	157.32	0.772	0.30 ( 0.28)	0.94	61237.5	10210.00
31	36950.44	160.39	0.766	0.30 ( 0.28)	0.94	61354.7	12000.00
32	33349.34	185.69	0.719	0.30 ( 0.28)	0.95	61976.0	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124122.09 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2426.61	27.79	1.799	0.30 ( 0.27)	0.90	1478.1	110.00
2	2523.08	30.18	1.709	0.30 ( 0.27)	0.90	1650.5	100.00
3	2535.23	31.37	1.678	0.30 ( 0.27)	0.90	1727.1	100.00
4	2565.50	34.38	1.599	0.30 ( 0.27)	0.91	1904.1	130.00
5	2700.64	47.40	1.332	0.30 ( 0.28)	0.93	2638.7	20100.00
6	2620.76	52.90	1.258	0.30 ( 0.28)	0.93	2824.4	13600.00
7	2498.72	87.84	0.994	0.30 ( 0.28)	0.93	3795.6	13510.00
8	2354.93	96.73	0.950	0.30 ( 0.28)	0.93	3859.7	13500.00

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13410.00 = 41710.10 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22704.72	14.75	2.668	0.30 ( 0.24)	0.81	3447.7	429.00
2	23931.82	16.17	2.529	0.30 ( 0.24)	0.81	3920.5	425.00
3	24246.33	16.56	2.495	0.30 ( 0.24)	0.81	4052.4	400.00
4	25056.66	17.96	2.375	0.30 ( 0.24)	0.81	4507.9	300.00
5	26574.10	21.37	2.120	0.30 ( 0.24)	0.81	5606.0	50700.00
6	27236.42	22.92	2.028	0.30 ( 0.24)	0.80	6087.2	210.00
7	27500.22	23.87	1.973	0.30 ( 0.24)	0.80	6368.6	50600.00
8	27814.15	24.93	1.910	0.30 ( 0.24)	0.80	6707.9	410.00
9	28124.88	25.91	1.871	0.30 ( 0.24)	0.80	7021.6	200.00
10	28229.94	26.24	1.858	0.30 ( 0.24)	0.80	7126.7	50200.00
11	28353.40	26.51	1.848	0.30 ( 0.24)	0.80	7249.1	230.00
12	28420.79	26.66	1.842	0.30 ( 0.24)	0.80	7316.7	50500.00
13	28817.64	27.59	1.807	0.30 ( 0.24)	0.81	7718.9	220.50
14	28902.22	27.79	1.799	0.30 ( 0.24)	0.81	7805.1	110.00
15	29940.50	30.18	1.709	0.30 ( 0.24)	0.81	8875.9	100.00
16	30140.05	30.67	1.696	0.30 ( 0.24)	0.81	9093.2	110.00
17	30386.81	31.37	1.678	0.30 ( 0.24)	0.81	9412.4	100.00
18	31454.80	34.38	1.599	0.30 ( 0.25)	0.82	10777.5	130.00
19	33409.29	39.89	1.455	0.30 ( 0.25)	0.83	13260.4	150.00
20	35580.69	47.40	1.332	0.30 ( 0.25)	0.85	16887.8	20100.00
21	36405.17	50.53	1.284	0.30 ( 0.26)	0.85	18324.4	40200.00
22	36823.68	52.90	1.258	0.30 ( 0.26)	0.86	19606.4	13600.00
23	37070.81	54.22	1.244	0.30 ( 0.26)	0.86	20310.9	390.00
24	39245.61	65.91	1.141	0.30 ( 0.27)	0.88	26364.9	13100.00
25	40091.30	72.82	1.095	0.30 ( 0.27)	0.89	29419.3	11801.00
26	41744.19	83.50	1.023	0.30 ( 0.27)	0.91	34840.6	11530.00
27	42695.64	87.84	0.994	0.30 ( 0.27)	0.91	37686.3	13510.00
28	43746.75	92.93	0.966	0.30 ( 0.27)	0.92	40918.2	13010.00
29	44501.05	96.73	0.950	0.30 ( 0.28)	0.92	43487.6	13500.00
30	45401.03	101.25	0.930	0.30 ( 0.28)	0.93	46506.3	10800.00
31	45848.98	105.46	0.912	0.30 ( 0.28)	0.93	49451.7	11130.00
32	45374.87	115.07	0.870	0.30 ( 0.28)	0.94	54492.9	12410.00
33	44690.00	123.37	0.842	0.30 ( 0.28)	0.94	58232.0	11201.00
34	44216.42	128.35	0.832	0.30 ( 0.28)	0.94	59963.7	12201.00
35	43148.38	135.45	0.817	0.30 ( 0.28)	0.94	61820.8	12231.00
36	41807.91	143.31	0.801	0.30 ( 0.28)	0.94	63455.1	10400.00
37	40417.20	151.30	0.784	0.30 ( 0.28)	0.94	64750.2	12010.00
38	39198.01	157.32	0.772	0.30 ( 0.28)	0.94	65097.2	10210.00
39	38657.38	160.39	0.766	0.30 ( 0.28)	0.94	65214.4	12000.00
40	34892.57	185.69	0.719	0.30 ( 0.28)	0.94	65835.7	10100.00

TOTAL AREA(ACRES) = 65835.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 45848.98 Tc(MIN.) = 105.458  
 EFFECTIVE AREA(ACRES) = 49451.68 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.86  
 TOTAL AREA(ACRES) = 65835.7  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124122.09 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13410.00 TO NODE 13412.00 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 178.72 DOWNSTREAM(FEET) = 176.93  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 169.78 CHANNEL SLOPE = 0.0105  
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 9.31  
 CHANNEL FLOW THRU SUBAREA(CFS) = 45848.98  
 FLOW VELOCITY(FEET/SEC.) = 19.97 FLOW DEPTH(FEET) = 9.31  
 TRAVEL TIME(MIN.) = 0.14 Tc(MIN.) = 105.60  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124291.87 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22704.72	14.93	2.640	0.30 ( 0.24)	0.81	3447.7	429.00
2	23931.82	16.34	2.514	0.30 ( 0.24)	0.81	3920.5	425.00
3	24246.33	16.74	2.480	0.30 ( 0.24)	0.81	4052.4	400.00
4	25056.66	18.13	2.361	0.30 ( 0.24)	0.81	4507.9	300.00
5	26574.10	21.54	2.110	0.30 ( 0.24)	0.81	5606.0	50700.00
6	27236.42	23.09	2.018	0.30 ( 0.24)	0.80	6087.2	210.00
7	27500.22	24.04	1.963	0.30 ( 0.24)	0.80	6368.6	50600.00
8	27814.15	25.09	1.902	0.30 ( 0.24)	0.80	6707.9	410.00
9	28124.88	26.08	1.865	0.30 ( 0.24)	0.80	7021.6	200.00
10	28229.94	26.41	1.852	0.30 ( 0.24)	0.80	7126.7	50200.00
11	28353.40	26.68	1.842	0.30 ( 0.24)	0.80	7249.1	230.00
12	28420.79	26.83	1.836	0.30 ( 0.24)	0.80	7316.7	50500.00
13	28817.64	27.75	1.800	0.30 ( 0.24)	0.81	7718.9	220.50
14	28902.22	27.96	1.793	0.30 ( 0.24)	0.81	7805.1	110.00
15	29940.50	30.34	1.705	0.30 ( 0.24)	0.81	8875.9	100.00
16	30140.05	30.83	1.692	0.30 ( 0.24)	0.81	9093.2	110.00
17	30386.81	31.53	1.674	0.30 ( 0.24)	0.81	9412.4	100.00
18	31454.80	34.54	1.595	0.30 ( 0.25)	0.82	10777.5	130.00
19	33409.29	40.04	1.451	0.30 ( 0.25)	0.83	13260.4	150.00
20	35580.69	47.56	1.330	0.30 ( 0.25)	0.85	16887.8	20100.00
21	36405.17	50.68	1.283	0.30 ( 0.26)	0.85	18324.4	40200.00
22	36823.68	53.05	1.257	0.30 ( 0.26)	0.86	19606.4	13600.00
23	37070.81	54.37	1.242	0.30 ( 0.26)	0.86	20310.9	390.00
24	39245.61	66.06	1.140	0.30 ( 0.27)	0.88	26364.9	13100.00
25	40091.30	72.97	1.094	0.30 ( 0.27)	0.89	29419.3	11801.00
26	41744.19	83.65	1.022	0.30 ( 0.27)	0.91	34840.6	11530.00
27	42695.64	87.98	0.993	0.30 ( 0.27)	0.91	37686.3	13510.00
28	43746.75	93.07	0.966	0.30 ( 0.27)	0.92	40918.2	13010.00
29	44501.05	96.88	0.949	0.30 ( 0.28)	0.92	43487.6	13500.00
30	45401.03	101.39	0.930	0.30 ( 0.28)	0.93	46506.3	10800.00

```

31 45848.98 105.60 0.911 0.30( 0.28) 0.93 49451.7 11130.00
32 45374.87 115.21 0.870 0.30( 0.28) 0.94 54492.9 12410.00
33 44690.00 123.51 0.842 0.30( 0.28) 0.94 58232.0 11201.00
34 44216.42 128.50 0.831 0.30( 0.28) 0.94 59963.7 12201.00
35 43148.38 135.60 0.817 0.30( 0.28) 0.94 61820.8 12231.00
36 41807.91 143.46 0.801 0.30( 0.28) 0.94 63455.1 10400.00
37 40417.20 151.45 0.784 0.30( 0.28) 0.94 64750.2 12010.00
38 39198.01 157.47 0.772 0.30( 0.28) 0.94 65097.2 10210.00
39 38657.38 160.54 0.765 0.30( 0.28) 0.94 65214.4 12000.00
40 34892.57 185.84 0.719 0.30( 0.28) 0.94 65835.7 10100.00

```

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 45848.98 Tc(MIN.) = 105.60  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 49451.68

\*\*\*\*\*

FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506101C.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	570.78	37.58	0.30( 0.30)	0.98	591.0	10100.00
TOTAL AREA(ACRES) =						591.0

\*\*\*\*\*

FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22704.72	14.93	2.640	0.30( 0.24)	0.81	3447.7	429.00
2	23931.82	16.34	2.514	0.30( 0.24)	0.81	3920.5	425.00
3	24246.33	16.74	2.480	0.30( 0.24)	0.81	4052.4	400.00
4	25056.66	18.13	2.361	0.30( 0.24)	0.81	4507.9	300.00
5	26574.10	21.54	2.110	0.30( 0.24)	0.81	5606.0	50700.00
6	27236.42	23.09	2.018	0.30( 0.24)	0.80	6087.2	210.00
7	27500.22	24.04	1.963	0.30( 0.24)	0.80	6368.6	50600.00
8	27814.15	25.09	1.902	0.30( 0.24)	0.80	6707.9	410.00
9	28124.88	26.08	1.865	0.30( 0.24)	0.80	7021.6	200.00
10	28229.94	26.41	1.852	0.30( 0.24)	0.80	7126.7	50200.00
11	28353.40	26.68	1.842	0.30( 0.24)	0.80	7249.1	230.00
12	28420.79	26.83	1.836	0.30( 0.24)	0.80	7316.7	50500.00
13	28817.64	27.75	1.800	0.30( 0.24)	0.81	7718.9	220.50
14	28902.22	27.96	1.793	0.30( 0.24)	0.81	7805.1	110.00
15	29940.50	30.34	1.705	0.30( 0.24)	0.81	8875.9	100.00
16	30140.05	30.83	1.692	0.30( 0.24)	0.81	9093.2	110.00

```

17 30386.81 31.53 1.674 0.30( 0.24) 0.81 9412.4 100.00
18 31454.80 34.54 1.595 0.30( 0.25) 0.82 10777.5 130.00
19 33409.29 40.04 1.451 0.30( 0.25) 0.83 13260.4 150.00
20 35580.69 47.56 1.330 0.30( 0.25) 0.85 16887.8 20100.00
21 36405.17 50.68 1.283 0.30( 0.26) 0.85 18324.4 40200.00
22 36823.68 53.05 1.257 0.30( 0.26) 0.86 19606.4 13600.00
23 37070.81 54.37 1.242 0.30( 0.26) 0.86 20310.9 390.00
24 39245.61 66.06 1.140 0.30( 0.27) 0.88 26364.9 13100.00
25 40091.30 72.97 1.094 0.30( 0.27) 0.89 29419.3 11801.00
26 41744.19 83.65 1.022 0.30( 0.27) 0.91 34840.6 11530.00
27 42695.64 87.98 0.993 0.30( 0.27) 0.91 37686.3 13510.00
28 43746.75 93.07 0.966 0.30( 0.27) 0.92 40918.2 13010.00
29 44501.05 96.88 0.949 0.30( 0.28) 0.92 43487.6 13500.00
30 45401.03 101.39 0.930 0.30( 0.28) 0.93 46506.3 10800.00
31 45848.98 105.60 0.911 0.30( 0.28) 0.93 49451.7 11130.00
32 45374.87 115.21 0.870 0.30( 0.28) 0.94 54492.9 12410.00
33 44690.00 123.51 0.842 0.30( 0.28) 0.94 58232.0 11201.00
34 44216.42 128.50 0.831 0.30( 0.28) 0.94 59963.7 12201.00
35 43148.38 135.60 0.817 0.30( 0.28) 0.94 61820.8 12231.00
36 41807.91 143.46 0.801 0.30( 0.28) 0.94 63455.1 10400.00
37 40417.20 151.45 0.784 0.30( 0.28) 0.94 64750.2 12010.00
38 39198.01 157.47 0.772 0.30( 0.28) 0.94 65097.2 10210.00
39 38657.38 160.54 0.765 0.30( 0.28) 0.94 65214.4 12000.00
40 34892.57 185.84 0.719 0.30( 0.28) 0.94 65835.7 10100.00

```

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124291.87 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	570.78	37.58	1.515	0.30( 0.30)	0.98	591.0	10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 14677.00 FEET.							

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23140.47	14.93	2.640	0.30( 0.25)	0.82	3682.5	429.00
2	24383.11	16.34	2.514	0.30( 0.25)	0.82	4177.5	425.00
3	24701.48	16.74	2.480	0.30( 0.25)	0.82	4315.7	400.00
4	25522.70	18.13	2.361	0.30( 0.24)	0.82	4793.0	300.00
5	27060.50	21.54	2.110	0.30( 0.24)	0.82	5944.7	50700.00
6	27731.65	23.09	2.018	0.30( 0.24)	0.81	6450.4	210.00
7	27999.09	24.04	1.963	0.30( 0.24)	0.81	6746.6	50600.00
8	28316.16	25.09	1.902	0.30( 0.24)	0.81	7102.6	410.00
9	28634.29	26.08	1.865	0.30( 0.24)	0.81	7431.7	200.00
10	28741.62	26.41	1.852	0.30( 0.24)	0.81	7542.0	50200.00
11	28866.88	26.68	1.842	0.30( 0.24)	0.81	7668.7	230.00
12	28935.25	26.83	1.836	0.30( 0.24)	0.81	7738.7	50500.00
13	29337.58	27.75	1.800	0.30( 0.24)	0.82	8155.4	220.50
14	29423.23	27.96	1.793	0.30( 0.24)	0.82	8244.8	110.00
15	30472.96	30.34	1.705	0.30( 0.25)	0.82	9353.1	100.00
16	30676.21	30.83	1.692	0.30( 0.25)	0.82	9578.1	110.00
17	30927.90	31.53	1.674	0.30( 0.25)	0.82	9908.2	100.00
18	32013.65	34.54	1.595	0.30( 0.25)	0.83	11320.7	130.00
19	33104.61	37.58	1.515	0.30( 0.25)	0.83	12739.2	10100.00
20	33950.07	40.04	1.451	0.30( 0.25)	0.84	13851.4	150.00
21	36064.55	47.56	1.330	0.30( 0.26)	0.85	17478.8	20100.00
22	36867.05	50.68	1.283	0.30( 0.26)	0.86	18915.4	40200.00
23	37273.46	53.05	1.257	0.30( 0.26)	0.86	20197.4	13600.00

24	37513.86	54.37	1.242	0.30	( 0.26)	0.86	20901.9	390.00
25	39640.90	66.06	1.140	0.30	( 0.27)	0.89	26955.9	13100.00
26	40464.83	72.97	1.094	0.30	( 0.27)	0.89	30010.3	11801.00
27	42084.09	83.65	1.022	0.30	( 0.27)	0.91	35431.6	11530.00
28	43021.88	87.98	0.993	0.30	( 0.27)	0.91	38277.3	13510.00
29	44060.42	93.07	0.966	0.30	( 0.28)	0.92	41509.2	13010.00
30	44807.01	96.88	0.949	0.30	( 0.28)	0.92	44078.6	13500.00
31	45697.82	101.39	0.930	0.30	( 0.28)	0.93	47097.3	10800.00
32	46137.26	105.60	0.911	0.30	( 0.28)	0.93	50042.7	11130.00
33	45643.67	115.21	0.870	0.30	( 0.28)	0.94	55083.9	12410.00
34	44945.70	123.51	0.842	0.30	( 0.28)	0.94	58823.0	11201.00
35	44467.30	128.50	0.831	0.30	( 0.28)	0.94	60554.7	12201.00
36	43392.39	135.60	0.817	0.30	( 0.28)	0.94	62411.8	12231.00
37	42044.33	143.46	0.801	0.30	( 0.28)	0.94	64046.1	10400.00
38	40645.89	151.45	0.784	0.30	( 0.28)	0.94	65341.2	12010.00
39	39420.88	157.47	0.772	0.30	( 0.28)	0.94	65688.2	10210.00
40	38877.28	160.54	0.765	0.30	( 0.28)	0.94	65805.4	12000.00
41	35090.77	185.84	0.719	0.30	( 0.28)	0.95	66426.7	10100.00

TOTAL AREA (ACRES) = 66426.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 46137.26 Tc (MIN.) = 105.599  
EFFECTIVE AREA (ACRES) = 50042.68 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA (ACRES) = 66426.7  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124291.87 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13412.00 TO NODE 13700.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 176.93 DOWNSTREAM (FEET) = 173.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 260.10 CHANNEL SLOPE = 0.0151  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 8.44  
CHANNEL FLOW THRU SUBAREA (CFS) = 46137.26  
FLOW VELOCITY (FEET/SEC.) = 22.59 FLOW DEPTH (FEET) = 8.44  
TRAVEL TIME (MIN.) = 0.19 Tc (MIN.) = 105.79  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124551.97 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23140.47	15.17	2.614	0.30 ( 0.25)	0.82	3682.5	429.00
2	24383.11	16.58	2.493	0.30 ( 0.25)	0.82	4177.5	425.00
3	24701.48	16.98	2.459	0.30 ( 0.25)	0.82	4315.7	400.00
4	25522.70	18.36	2.340	0.30 ( 0.24)	0.82	4793.0	300.00
5	27060.50	21.77	2.096	0.30 ( 0.24)	0.82	5944.7	50700.00
6	27731.65	23.32	2.005	0.30 ( 0.24)	0.81	6450.4	210.00
7	27999.09	24.26	1.949	0.30 ( 0.24)	0.81	6746.6	50600.00
8	28316.16	25.32	1.894	0.30 ( 0.24)	0.81	7102.6	410.00
9	28634.29	26.30	1.856	0.30 ( 0.24)	0.81	7431.7	200.00
10	28741.62	26.63	1.843	0.30 ( 0.24)	0.81	7542.0	50200.00
11	28866.88	26.90	1.833	0.30 ( 0.24)	0.81	7668.7	230.00
12	28935.25	27.05	1.827	0.30 ( 0.24)	0.81	7738.7	50500.00

13	29337.58	27.98	1.792	0.30	( 0.24)	0.82	8155.4	220.50
14	29423.23	28.18	1.784	0.30	( 0.24)	0.82	8244.8	110.00
15	30472.96	30.56	1.699	0.30	( 0.25)	0.82	9353.1	100.00
16	30676.21	31.05	1.686	0.30	( 0.25)	0.82	9578.1	110.00
17	30927.90	31.75	1.668	0.30	( 0.25)	0.82	9908.2	100.00
18	32013.65	34.76	1.589	0.30	( 0.25)	0.83	11320.7	130.00
19	33104.61	37.79	1.510	0.30	( 0.25)	0.83	12739.2	10100.00
20	33950.07	40.26	1.448	0.30	( 0.25)	0.84	13851.4	150.00
21	36064.55	47.77	1.326	0.30	( 0.26)	0.85	17478.8	20100.00
22	36867.05	50.89	1.280	0.30	( 0.26)	0.86	18915.4	40200.00
23	37273.46	53.26	1.254	0.30	( 0.26)	0.86	20197.4	13600.00
24	37513.86	54.58	1.240	0.30	( 0.26)	0.86	20901.9	390.00
25	39640.90	66.26	1.139	0.30	( 0.27)	0.89	26955.9	13100.00
26	40464.83	73.17	1.092	0.30	( 0.27)	0.89	30010.3	11801.00
27	42084.09	83.84	1.020	0.30	( 0.27)	0.91	35431.6	11530.00
28	43021.88	88.18	0.991	0.30	( 0.27)	0.91	38277.3	13510.00
29	44060.42	93.27	0.965	0.30	( 0.28)	0.92	41509.2	13010.00
30	44807.01	97.07	0.948	0.30	( 0.28)	0.92	44078.6	13500.00
31	45697.82	101.59	0.929	0.30	( 0.28)	0.93	47097.3	10800.00
32	46137.26	105.79	0.911	0.30	( 0.28)	0.93	50042.7	11130.00
33	45643.67	115.40	0.869	0.30	( 0.28)	0.94	55083.9	12410.00
34	44945.70	123.70	0.841	0.30	( 0.28)	0.94	58823.0	11201.00
35	44467.30	128.69	0.831	0.30	( 0.28)	0.94	60554.7	12201.00
36	43392.39	135.79	0.816	0.30	( 0.28)	0.94	62411.8	12231.00
37	42044.33	143.66	0.800	0.30	( 0.28)	0.94	64046.1	10400.00
38	40645.89	151.65	0.784	0.30	( 0.28)	0.94	65341.2	12010.00
39	39420.88	157.67	0.771	0.30	( 0.28)	0.94	65688.2	10210.00
40	38877.28	160.75	0.765	0.30	( 0.28)	0.94	65805.4	12000.00
41	35090.77	186.05	0.719	0.30	( 0.28)	0.95	66426.7	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 46137.26 Tc (MIN.) = 105.79  
AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA (ACRES) = 50042.68

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610508X.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	219.66	20.77	0.30 ( 0.30)	0.99	131.3	50800.00
TOTAL AREA (ACRES) = 131.3						

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<



\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23140.47	15.17	2.614	0.30 ( 0.25)	0.82	3682.5	429.00
2	24383.11	16.58	2.493	0.30 ( 0.25)	0.82	4177.5	425.00
3	24701.48	16.98	2.459	0.30 ( 0.25)	0.82	4315.7	400.00
4	25522.70	18.36	2.340	0.30 ( 0.24)	0.82	4793.0	300.00
5	27060.50	21.77	2.096	0.30 ( 0.24)	0.82	5944.7	50700.00
6	27731.65	23.32	2.005	0.30 ( 0.24)	0.81	6450.4	210.00
7	27999.09	24.26	1.949	0.30 ( 0.24)	0.81	6746.6	50600.00
8	28316.16	25.32	1.894	0.30 ( 0.24)	0.81	7102.6	410.00
9	28634.29	26.30	1.856	0.30 ( 0.24)	0.81	7431.7	200.00
10	28741.62	26.63	1.843	0.30 ( 0.24)	0.81	7542.0	50200.00
11	28866.88	26.90	1.833	0.30 ( 0.24)	0.81	7668.7	230.00
12	28935.25	27.05	1.827	0.30 ( 0.24)	0.81	7738.7	50500.00
13	29337.58	27.98	1.792	0.30 ( 0.24)	0.82	8155.4	220.50
14	29423.23	28.18	1.784	0.30 ( 0.24)	0.82	8244.8	110.00
15	30472.96	30.56	1.699	0.30 ( 0.25)	0.82	9353.1	100.00
16	30676.21	31.05	1.686	0.30 ( 0.25)	0.82	9578.1	110.00
17	30927.90	31.75	1.668	0.30 ( 0.25)	0.82	9908.2	100.00
18	32013.65	34.76	1.589	0.30 ( 0.25)	0.83	11320.7	130.00
19	33104.61	37.79	1.510	0.30 ( 0.25)	0.83	12739.2	10100.00
20	33950.07	40.26	1.448	0.30 ( 0.25)	0.84	13851.4	150.00
21	36064.55	47.77	1.326	0.30 ( 0.26)	0.85	17478.8	20100.00
22	36867.05	50.89	1.280	0.30 ( 0.26)	0.86	18915.4	40200.00
23	37273.46	53.26	1.254	0.30 ( 0.26)	0.86	20197.4	13600.00
24	37513.86	54.58	1.240	0.30 ( 0.26)	0.86	20901.9	390.00
25	39640.90	66.26	1.139	0.30 ( 0.27)	0.89	26955.9	13100.00
26	40464.83	73.17	1.092	0.30 ( 0.27)	0.89	30010.3	11801.00
27	42084.09	83.84	1.020	0.30 ( 0.27)	0.91	35431.6	11530.00
28	43021.88	88.18	0.991	0.30 ( 0.27)	0.91	38277.3	13510.00
29	44060.42	93.27	0.965	0.30 ( 0.28)	0.92	41509.2	13010.00
30	44807.01	97.07	0.948	0.30 ( 0.28)	0.92	44078.6	13500.00
31	45697.82	101.59	0.929	0.30 ( 0.28)	0.93	47097.3	10800.00
32	46137.26	105.79	0.911	0.30 ( 0.28)	0.93	50042.7	11130.00
33	45643.67	115.40	0.869	0.30 ( 0.28)	0.94	55083.9	12410.00
34	44945.70	123.70	0.841	0.30 ( 0.28)	0.94	58823.0	11201.00
35	44467.30	128.69	0.831	0.30 ( 0.28)	0.94	60554.7	12201.00
36	43392.39	135.79	0.816	0.30 ( 0.28)	0.94	62411.8	12231.00
37	42044.33	143.66	0.800	0.30 ( 0.28)	0.94	64046.1	10400.00
38	40645.89	151.65	0.784	0.30 ( 0.28)	0.94	65341.2	12010.00
39	39420.88	157.67	0.771	0.30 ( 0.28)	0.94	65688.2	10210.00
40	38877.28	160.75	0.765	0.30 ( 0.28)	0.94	65805.4	12000.00
41	35090.77	186.05	0.719	0.30 ( 0.28)	0.95	66426.7	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124551.97 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	219.66	20.77	2.155	0.30 ( 0.30)	0.99	131.3	50800.00

LONGEST FLOWPATH FROM NODE 50800.00 TO NODE 13700.00 = 5946.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23340.62	15.17	2.614	0.30 ( 0.25)	0.82	3778.4	429.00
2	24590.44	16.58	2.493	0.30 ( 0.25)	0.82	4282.3	425.00
3	24910.48	16.98	2.459	0.30 ( 0.25)	0.82	4423.0	400.00

4	25736.32	18.36	2.340	0.30 ( 0.25)	0.82	4909.1	300.00
5	26827.45	20.77	2.155	0.30 ( 0.25)	0.82	5736.9	50800.00
6	27273.19	21.77	2.096	0.30 ( 0.25)	0.82	6076.0	50700.00
7	27933.56	23.32	2.005	0.30 ( 0.25)	0.82	6581.7	210.00
8	28194.44	24.26	1.949	0.30 ( 0.25)	0.82	6877.9	50600.00
9	28504.94	25.32	1.894	0.30 ( 0.25)	0.82	7233.9	410.00
10	28818.61	26.30	1.856	0.30 ( 0.25)	0.82	7562.9	200.00
11	28924.46	26.63	1.843	0.30 ( 0.25)	0.82	7673.3	50200.00
12	29048.48	26.90	1.833	0.30 ( 0.25)	0.82	7799.9	230.00
13	29116.16	27.05	1.827	0.30 ( 0.25)	0.82	7869.9	50500.00
14	29514.29	27.98	1.792	0.30 ( 0.25)	0.82	8286.7	220.50
15	29599.04	28.18	1.784	0.30 ( 0.25)	0.82	8376.0	110.00
16	30638.75	30.56	1.699	0.30 ( 0.25)	0.82	9484.4	100.00
17	30840.48	31.05	1.686	0.30 ( 0.25)	0.82	9709.4	110.00
18	31090.02	31.75	1.668	0.30 ( 0.25)	0.82	10039.5	100.00
19	32166.46	34.76	1.589	0.30 ( 0.25)	0.83	11452.0	130.00
20	32488.01	37.79	1.510	0.30 ( 0.25)	0.83	12870.5	10100.00
21	34086.15	40.26	1.448	0.30 ( 0.25)	0.84	13982.6	150.00
22	36186.25	47.77	1.326	0.30 ( 0.26)	0.85	17610.0	20100.00
23	36983.34	50.89	1.280	0.30 ( 0.26)	0.86	19046.6	40200.00
24	37386.68	53.26	1.254	0.30 ( 0.26)	0.86	20328.6	13600.00
25	37625.39	54.58	1.240	0.30 ( 0.26)	0.87	21033.2	390.00
26	39740.46	66.26	1.139	0.30 ( 0.27)	0.89	27087.2	13100.00
27	40558.90	73.17	1.092	0.30 ( 0.27)	0.90	30141.6	11801.00
28	42169.65	83.84	1.020	0.30 ( 0.27)	0.91	35562.9	11530.00
29	43104.00	88.18	0.991	0.30 ( 0.27)	0.91	38408.6	13510.00
30	44139.41	93.27	0.965	0.30 ( 0.28)	0.92	41640.5	13010.00
31	44884.06	97.07	0.948	0.30 ( 0.28)	0.92	44209.9	13500.00
32	45772.56	101.59	0.929	0.30 ( 0.28)	0.93	47228.6	10800.00
33	46209.84	105.79	0.911	0.30 ( 0.28)	0.93	50173.9	11130.00
34	45711.33	115.40	0.869	0.30 ( 0.28)	0.94	55215.1	12410.00
35	45010.10	123.70	0.841	0.30 ( 0.28)	0.94	58954.3	11201.00
36	44530.48	128.69	0.831	0.30 ( 0.28)	0.94	60686.0	12201.00
37	43453.84	135.79	0.816	0.30 ( 0.28)	0.94	62543.1	12231.00
38	42103.86	143.66	0.800	0.30 ( 0.28)	0.94	64177.4	10400.00
39	40703.46	151.65	0.784	0.30 ( 0.28)	0.94	65472.5	12010.00
40	39476.98	157.67	0.771	0.30 ( 0.28)	0.94	65819.5	10210.00
41	38932.63	160.75	0.765	0.30 ( 0.28)	0.94	65936.7	12000.00
42	35140.66	186.05	0.719	0.30 ( 0.28)	0.95	66557.9	10100.00

TOTAL AREA (ACRES) = 66557.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 46209.84 Tc (MIN.) = 105.791  
 EFFECTIVE AREA (ACRES) = 50173.95 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 66557.9  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124551.97 FEET.

=====

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 66557.9 TC (MIN.) = 105.79  
 EFFECTIVE AREA (ACRES) = 50173.95 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.931  
 PEAK FLOW RATE (CFS) = 46209.84

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23340.62	15.17	2.614	0.30 ( 0.25)	0.82	3778.4	429.00

2	24590.44	16.58	2.493	0.30	( 0.25)	0.82	4282.3	425.00
3	24910.48	16.98	2.459	0.30	( 0.25)	0.82	4423.0	400.00
4	25736.32	18.36	2.340	0.30	( 0.25)	0.82	4909.1	300.00
5	26827.45	20.77	2.155	0.30	( 0.25)	0.82	5736.9	50800.00
6	27273.19	21.77	2.096	0.30	( 0.25)	0.82	6076.0	50700.00
7	27933.56	23.32	2.005	0.30	( 0.25)	0.82	6581.7	210.00
8	28194.44	24.26	1.949	0.30	( 0.25)	0.82	6877.9	50600.00
9	28504.94	25.32	1.894	0.30	( 0.25)	0.82	7233.9	410.00
10	28818.61	26.30	1.856	0.30	( 0.25)	0.82	7562.9	200.00
11	28924.46	26.63	1.843	0.30	( 0.25)	0.82	7673.3	50200.00
12	29048.48	26.90	1.833	0.30	( 0.25)	0.82	7799.9	230.00
13	29116.16	27.05	1.827	0.30	( 0.25)	0.82	7869.9	50500.00
14	29514.29	27.98	1.792	0.30	( 0.25)	0.82	8286.7	220.50
15	29599.04	28.18	1.784	0.30	( 0.25)	0.82	8376.0	110.00
16	30638.75	30.56	1.699	0.30	( 0.25)	0.82	9484.4	100.00
17	30840.48	31.05	1.686	0.30	( 0.25)	0.82	9709.4	110.00
18	31090.02	31.75	1.668	0.30	( 0.25)	0.82	10039.5	100.00
19	32166.46	34.76	1.589	0.30	( 0.25)	0.83	11452.0	130.00
20	33248.01	37.79	1.510	0.30	( 0.25)	0.83	12870.5	10100.00
21	34086.15	40.26	1.448	0.30	( 0.25)	0.84	13982.6	150.00
22	36186.25	47.77	1.326	0.30	( 0.26)	0.85	17610.0	20100.00
23	36983.34	50.89	1.280	0.30	( 0.26)	0.86	19046.6	40200.00
24	37386.68	53.26	1.254	0.30	( 0.26)	0.86	20328.6	13600.00
25	37625.39	54.58	1.240	0.30	( 0.26)	0.87	21033.2	390.00
26	39740.46	66.26	1.139	0.30	( 0.27)	0.89	27087.2	13100.00
27	40558.90	73.17	1.092	0.30	( 0.27)	0.90	30141.6	11801.00
28	42169.65	83.84	1.020	0.30	( 0.27)	0.91	35562.9	11530.00
29	43104.00	88.18	0.991	0.30	( 0.27)	0.91	38408.6	13510.00
30	44139.41	93.27	0.965	0.30	( 0.28)	0.92	41640.5	13010.00
31	44884.06	97.07	0.948	0.30	( 0.28)	0.92	44209.9	13500.00
32	45772.56	101.59	0.929	0.30	( 0.28)	0.93	47228.6	10800.00
33	46209.84	105.79	0.911	0.30	( 0.28)	0.93	50173.9	11130.00
34	45711.33	115.40	0.869	0.30	( 0.28)	0.94	55215.1	12410.00
35	45010.10	123.70	0.841	0.30	( 0.28)	0.94	58954.3	11201.00
36	44530.48	128.69	0.831	0.30	( 0.28)	0.94	60686.0	12201.00
37	43453.84	135.79	0.816	0.30	( 0.28)	0.94	62543.1	12231.00
38	42103.86	143.66	0.800	0.30	( 0.28)	0.94	64177.4	10400.00
39	40703.46	151.65	0.784	0.30	( 0.28)	0.94	65472.5	12010.00
40	39476.98	157.67	0.771	0.30	( 0.28)	0.94	65819.5	10210.00
41	38932.63	160.75	0.765	0.30	( 0.28)	0.94	65936.7	12000.00
42	35140.66	186.05	0.719	0.30	( 0.28)	0.95	66557.9	10100.00

=====  
 =====  
 END OF RATIONAL METHOD ANALYSIS

\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S36- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 50-YR RM EV APRIL 2019 CCHIUI \*  
\*\*\*\*\*

FILE NAME: RI50EV36.DAT  
TIME/DATE OF STUDY: 09:14 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 50.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.255
- 2) 10.00; 3.396
- 3) 15.00; 2.615
- 4) 20.00; 2.190
- 5) 25.00; 1.899
- 6) 30.00; 1.707
- 7) 40.00; 1.447
- 8) 50.00; 1.285
- 9) 60.00; 1.174
- 10) 90.00; 0.972
- 11) 120.00; 0.842
- 12) 180.00; 0.717
- 13) 360.00; 0.527
- 14) 1200.00; 0.230

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL: IN- / OUT-/PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13600.00 TO NODE 13600.50 IS CODE = 21  
-----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 488.61  
ELEVATION DATA: UPSTREAM(FEET) = 872.12 DOWNSTREAM(FEET) = 744.80

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 10.995  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 3.241  
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "OPEN BRUSH"	-	3.39	0.30	1.000	69	11.00

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA RUNOFF(CFS) = 8.97  
TOTAL AREA(ACRES) = 3.39 PEAK FLOW RATE(CFS) = 8.97

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13600.50 TO NODE 13601.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 744.80 DOWNSTREAM(FEET) = 707.32  
CHANNEL LENGTH THRU SUBAREA(FEET) = 418.30 CHANNEL SLOPE = 0.0896  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.43  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.962  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.45	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 17.92  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.91  
AVERAGE FLOW DEPTH(FEET) = 0.42 TRAVEL TIME(MIN.) = 1.78  
Tc(MIN.) = 12.78  
SUBAREA AREA(ACRES) = 7.45 SUBAREA RUNOFF(CFS) = 17.85  
EFFECTIVE AREA(ACRES) = 10.84 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 10.8 PEAK FLOW RATE(CFS) = 25.97  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.52

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.52 FLOW VELOCITY(FEET/SEC.) = 4.49  
LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13601.00 = 906.91 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13601.00 TO NODE 13602.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 707.32 DOWNSTREAM(FEET) = 657.12  
CHANNEL LENGTH THRU SUBAREA(FEET) = 777.60 CHANNEL SLOPE = 0.0646  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.97  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.596

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.32	0.30	1.000	-
USER-DEFINED	-	4.70	0.30	1.000	-
USER-DEFINED	-	25.05	0.30	1.000	-
USER-DEFINED	-	0.45	0.30	1.000	-
USER-DEFINED	-	0.44	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 58.05

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.29

AVERAGE FLOW DEPTH(FEET) = 0.93 TRAVEL TIME(MIN.) = 2.45

Tc(MIN.) = 15.23

SUBAREA AREA(ACRES) = 30.96 SUBAREA RUNOFF(CFS) = 63.97  
EFFECTIVE AREA(ACRES) = 41.80 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 41.8 PEAK FLOW RATE(CFS) = 86.36  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.16

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.16 FLOW VELOCITY(FEET/SEC.) = 6.03

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13602.00 = 1684.51 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13602.00 TO NODE 13603.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 657.12 DOWNSTREAM(FEET) = 584.58  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1186.54 CHANNEL SLOPE = 0.0611  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.36  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.331

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.03	0.30	1.000	-
USER-DEFINED	-	2.51	0.30	1.000	-

USER-DEFINED - 1.52 0.30 1.000 -  
USER-DEFINED - 12.30 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 107.74

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.35

AVERAGE FLOW DEPTH(FEET) = 1.34 TRAVEL TIME(MIN.) = 3.11

Tc(MIN.) = 18.34

SUBAREA AREA(ACRES) = 23.36 SUBAREA RUNOFF(CFS) = 42.70

EFFECTIVE AREA(ACRES) = 65.16 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 65.2 PEAK FLOW RATE(CFS) = 119.11

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.41

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.41 FLOW VELOCITY(FEET/SEC.) = 6.56

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13603.00 = 2871.05 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 584.58 DOWNSTREAM(FEET) = 544.91  
CHANNEL LENGTH THRU SUBAREA(FEET) = 860.98 CHANNEL SLOPE = 0.0461  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.67  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.152

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	10.22	0.30	1.000	-
USER-DEFINED	-	4.19	0.30	1.000	-
USER-DEFINED	-	0.07	0.30	1.000	-
USER-DEFINED	-	1.11	0.30	1.000	-
USER-DEFINED	-	5.56	0.30	1.000	-
USER-DEFINED	-	0.09	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 136.82

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.22

AVERAGE FLOW DEPTH(FEET) = 1.65 TRAVEL TIME(MIN.) = 2.31

Tc(MIN.) = 20.65

SUBAREA AREA(ACRES) = 21.24 SUBAREA RUNOFF(CFS) = 35.41

EFFECTIVE AREA(ACRES) = 86.40 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 86.4 PEAK FLOW RATE(CFS) = 144.04

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.70

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.70 FLOW VELOCITY(FEET/SEC.) = 6.30

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13620.00 = 3732.03 FEET.

```

*****
FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 10
-----
>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<
=====
*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13522.00 IS CODE = 15.1
-----
>>>>DEFINE MEMORY BANK # 2 <<<<<
=====
PEAK FLOWRATE TABLE FILE NAME: S35X50.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:
STREAM      Q      Tc      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR)    (ACRES)  NODE
  1      1198.50  52.93  0.30( 0.28)  0.95    1515.8  13510.00
  2      1092.68  61.25  0.30( 0.28)  0.94    1579.8  13500.00
TOTAL AREA(ACRES) =      1579.8
-----
*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13522.00 IS CODE = 14.0
-----
>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<
=====
MAIN-STREAM MEMORY DEFINED AS FOLLOWS:
STREAM      Q      Tc      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR)    (ACRES)  NODE
  1      1198.50  52.93  0.30( 0.28)  0.95    1515.8  13510.00
  2      1092.68  61.25  0.30( 0.28)  0.94    1579.8  13500.00
TOTAL AREA(ACRES) =      1579.8
-----
*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13620.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 632.19 DOWNSTREAM(FEET) = 544.91
CHANNEL LENGTH THRU SUBAREA(FEET) = 2062.96 CHANNEL SLOPE = 0.0423
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.57
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.222
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL      AREA      Fp      Ap      SCS
LAND USE      GROUP      (ACRES)  (INCH/HR)  (DECIMAL)  CN
USER-DEFINED      -      17.68      0.30      1.000      -
USER-DEFINED      -      2.36      0.30      1.000      -
USER-DEFINED      -      0.60      0.30      1.000      -
USER-DEFINED      -      0.22      0.30      1.000      -
USER-DEFINED      -      2.22      0.30      1.000      -
USER-DEFINED      -      3.42      0.30      1.000      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1209.50
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.50

```

```

AVERAGE FLOW DEPTH(FEET) = 2.57 TRAVEL TIME(MIN.) = 2.75
Tc(MIN.) = 55.68
SUBAREA AREA(ACRES) = 26.50 SUBAREA RUNOFF(CFS) = 22.00
EFFECTIVE AREA(ACRES) = 1542.26 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
TOTAL AREA(ACRES) = 1606.3 PEAK FLOW RATE(CFS) = 1301.65
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 2.68

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 2.68 FLOW VELOCITY(FEET/SEC.) = 12.80
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

** PEAK FLOW RATE TABLE **
STREAM      Q      Tc      Intensity      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR)  (INCH/HR)  (ACRES)  NODE
  1      1301.65  55.68  1.222  0.30( 0.28)  0.95    1542.3  13510.00
  2      1247.57  64.08  1.147  0.30( 0.28)  0.95    1606.3  13500.00
NEW PEAK FLOW DATA ARE:
PEAK FLOW RATE(CFS) = 1301.65 Tc(MIN.) = 55.68
AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.95 EFFECTIVE AREA(ACRES) = 1542.26
-----
*****
FLOW PROCESS FROM NODE 13620.00 TO NODE 13620.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====
MAINLINE Tc(MIN.) = 55.68
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.222
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/      SCS SOIL      AREA      Fp      Ap      SCS
LAND USE      GROUP      (ACRES)  (INCH/HR)  (DECIMAL)  CN
NATURAL FAIR COVER
"WOODLAND,GRASS"      B      1.44      0.30      1.000      65
NATURAL FAIR COVER
"WOODLAND,GRASS"      B      0.01      0.30      1.000      65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 1.45 SUBAREA RUNOFF(CFS) = 1.20
EFFECTIVE AREA(ACRES) = 1543.71 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95
TOTAL AREA(ACRES) = 1607.8 PEAK FLOW RATE(CFS) = 1302.85
-----
*****
FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 11
-----
>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<
=====
** MAIN STREAM CONFLUENCE DATA **
STREAM      Q      Tc      Intensity      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR)  (INCH/HR)  (ACRES)  NODE
  1      1302.85  55.68  1.222  0.30( 0.28)  0.95    1543.7  13510.00
  2      1248.68  64.08  1.147  0.30( 0.28)  0.95    1607.8  13500.00
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

```

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	144.04	20.65	2.152	0.30 ( 0.30)	1.00	86.4	13600.00

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13620.00 = 3732.03 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1106.54	20.65	2.152	0.30 ( 0.29)	0.95	658.9	13600.00
2	1374.55	55.68	1.222	0.30 ( 0.29)	0.95	1630.1	13510.00
3	1314.51	64.08	1.147	0.30 ( 0.28)	0.95	1694.2	13500.00

TOTAL AREA (ACRES) = 1694.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 1374.55 Tc(MIN.) = 55.676  
EFFECTIVE AREA(ACRES) = 1630.11 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95  
TOTAL AREA (ACRES) = 1694.2  
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13620.00 TO NODE 13640.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 544.91 DOWNSTREAM(FEET) = 489.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1384.37 CHANNEL SLOPE = 0.0404  
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.82

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.202  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.39	0.30	1.000	-
USER-DEFINED	-	16.30	0.30	1.000	-
USER-DEFINED	-	4.08	0.30	1.000	-
USER-DEFINED	-	12.36	0.30	1.000	-
USER-DEFINED	-	11.23	0.30	1.000	-
USER-DEFINED	-	5.16	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1396.69  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.88  
AVERAGE FLOW DEPTH(FEET) = 2.82 TRAVEL TIME(MIN.) = 1.79  
Tc(MIN.) = 57.47  
SUBAREA AREA(ACRES) = 54.52 SUBAREA RUNOFF(CFS) = 44.27  
EFFECTIVE AREA(ACRES) = 1684.63 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95  
TOTAL AREA(ACRES) = 1748.7 PEAK FLOW RATE(CFS) = 1389.65  
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.81

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 2.81 FLOW VELOCITY(FEET/SEC.) = 12.87

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1126.15	22.55	2.041	0.30 ( 0.29)	0.96	713.4	13600.00
2	1389.65	57.47	1.202	0.30 ( 0.29)	0.95	1684.6	13510.00
3	1336.79	65.90	1.134	0.30 ( 0.28)	0.95	1748.7	13500.00

NEW PEAK FLOW DATA ARE:  
PEAK FLOW RATE(CFS) = 1389.65 Tc(MIN.) = 57.47  
AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.95 EFFECTIVE AREA(ACRES) = 1684.63

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 57.47  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.202  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	53.93	0.30	1.000	-
USER-DEFINED	-	0.45	0.30	1.000	-
USER-DEFINED	-	3.98	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA(ACRES) = 58.36 SUBAREA RUNOFF(CFS) = 47.39  
EFFECTIVE AREA(ACRES) = 1742.99 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95  
TOTAL AREA(ACRES) = 1807.1 PEAK FLOW RATE(CFS) = 1437.03

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: P201XX50.DNA  
MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	238.49	17.13	0.30 ( 0.26)	0.85	133.8	20100.00

TOTAL AREA(ACRES) = 133.8

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1217.61	22.55	2.041	0.30 ( 0.29)	0.96	771.8	13600.00
2	1437.03	57.47	1.202	0.30 ( 0.29)	0.95	1743.0	13510.00
3	1380.61	65.90	1.134	0.30 ( 0.29)	0.95	1807.1	13500.00

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	238.49	17.13	2.434	0.30 ( 0.26)	0.85	133.8	20100.00

LONGEST FLOWPATH FROM NODE 20100.00 TO NODE 13640.00 = 5247.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1370.34	17.13	2.434	0.30 ( 0.28)	0.94	719.9	20100.00
2	1413.09	22.55	2.041	0.30 ( 0.28)	0.95	905.6	13600.00
3	1540.61	57.47	1.202	0.30 ( 0.28)	0.95	1876.8	13510.00
4	1476.77	65.90	1.134	0.30 ( 0.28)	0.94	1940.9	13500.00

TOTAL AREA (ACRES) = 1940.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 1540.61 Tc (MIN.) = 57.467  
EFFECTIVE AREA (ACRES) = 1876.79 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95  
TOTAL AREA (ACRES) = 1940.9  
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13640.00 TO NODE 13641.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 489.00 DOWNSTREAM (FEET) = 436.89  
CHANNEL LENGTH THRU SUBAREA (FEET) = 2994.52 CHANNEL SLOPE = 0.0174  
GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT (FEET) = 3.79

\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.157

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.96	0.30	1.000	-
USER-DEFINED	-	0.01	0.30	1.000	-
USER-DEFINED	-	1.56	0.30	1.000	-
USER-DEFINED	-	10.45	0.30	1.000	-
USER-DEFINED	-	44.94	0.30	1.000	-
USER-DEFINED	-	9.66	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 1566.69

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 9.98

AVERAGE FLOW DEPTH (FEET) = 3.79 TRAVEL TIME (MIN.) = 5.00

Tc (MIN.) = 62.47

SUBAREA AREA (ACRES) = 67.58 SUBAREA RUNOFF (CFS) = 52.15

EFFECTIVE AREA (ACRES) = 1944.37 AREA-AVERAGED Fm (INCH/HR) = 0.28

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95

TOTAL AREA (ACRES) = 2008.4 PEAK FLOW RATE (CFS) = 1540.61

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT (FEET) = 3.76

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 3.76 FLOW VELOCITY (FEET/SEC.) = 9.93  
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13641.00 = 25056.61 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1370.34	22.27	2.058	0.30 ( 0.28)	0.95	787.5	20100.00
2	1413.09	27.67	1.797	0.30 ( 0.28)	0.95	973.1	13600.00
3	1540.61	62.47	1.157	0.30 ( 0.28)	0.95	1944.4	13510.00
4	1476.77	70.96	1.100	0.30 ( 0.28)	0.95	2008.4	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 1540.61 Tc (MIN.) = 62.47  
AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.95 EFFECTIVE AREA (ACRES) = 1944.37

\*\*\*\*\*

FLOW PROCESS FROM NODE 13641.00 TO NODE 13641.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 62.47

\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.157

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	16.49	0.30	1.000	-
USER-DEFINED	-	20.39	0.30	1.000	-
USER-DEFINED	-	7.02	0.30	1.000	-
USER-DEFINED	-	12.58	0.30	1.000	-
USER-DEFINED	-	42.49	0.30	1.000	-
USER-DEFINED	-	5.73	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 104.70 SUBAREA RUNOFF (CFS) = 80.80

EFFECTIVE AREA (ACRES) = 2049.07 AREA-AVERAGED Fm (INCH/HR) = 0.29

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95

TOTAL AREA (ACRES) = 2113.1 PEAK FLOW RATE (CFS) = 1608.30

\*\*\*\*\*

FLOW PROCESS FROM NODE 13641.00 TO NODE 13641.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 62.47

\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.157

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.78	0.30	1.000	-
USER-DEFINED	-	6.25	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 8.03 SUBAREA RUNOFF (CFS) = 6.20  
EFFECTIVE AREA (ACRES) = 2057.10 AREA-AVERAGED Fm (INCH/HR) = 0.29  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95  
TOTAL AREA (ACRES) = 2121.2 PEAK FLOW RATE (CFS) = 1614.50

```
*****
FLOW PROCESS FROM NODE 13641.00 TO NODE 13642.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 436.89 DOWNSTREAM(FEET) = 394.80
CHANNEL LENGTH THRU SUBAREA(FEET) = 2814.16 CHANNEL SLOPE = 0.0150
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 4.13
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.125
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.67 0.30 1.000 -
USER-DEFINED - 24.24 0.30 1.000 -
USER-DEFINED - 1.34 0.30 1.000 -
USER-DEFINED - 74.98 0.30 1.000 -
USER-DEFINED - 101.12 0.30 1.000 -
USER-DEFINED - 16.90 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1695.89
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.70
AVERAGE FLOW DEPTH(FEET) = 4.12 TRAVEL TIME(MIN.) = 4.83
Tc(MIN.) = 67.30
SUBAREA AREA(ACRES) = 219.25 SUBAREA RUNOFF(CFS) = 162.77
EFFECTIVE AREA(ACRES) = 2276.35 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA(ACRES) = 2340.4 PEAK FLOW RATE(CFS) = 1717.01
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 4.16

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 4.16 FLOW VELOCITY(FEET/SEC.) = 9.73
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13642.00 = 27870.77 FEET.
```

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1536.97	27.21	1.814	0.30( 0.29)	0.96	1119.4	20100.00
2	1587.17	32.58	1.640	0.30( 0.29)	0.96	1305.1	13600.00
3	1717.01	67.30	1.125	0.30( 0.29)	0.96	2276.4	13510.00
4	1645.19	75.85	1.067	0.30( 0.29)	0.95	2340.4	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 1717.01 Tc(MIN.) = 67.30  
 AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.96 EFFECTIVE AREA(ACRES) = 2276.35

```
*****
FLOW PROCESS FROM NODE 13642.00 TO NODE 13642.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 67.30
```

```
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.125
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 9.95 0.30 1.000 -
USER-DEFINED - 10.02 0.30 1.000 -
USER-DEFINED - 4.45 0.30 1.000 -
USER-DEFINED - 179.37 0.30 1.000 -
USER-DEFINED - 11.47 0.30 1.000 -
USER-DEFINED - 0.17 0.30 0.850 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 215.43 SUBAREA RUNOFF(CFS) = 159.94
EFFECTIVE AREA(ACRES) = 2491.78 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA(ACRES) = 2555.9 PEAK FLOW RATE(CFS) = 1876.96

*****
FLOW PROCESS FROM NODE 13642.00 TO NODE 13642.00 IS CODE = 81
-----
```

```
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 67.30
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.125
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.03 0.30 0.850 -
USER-DEFINED - 5.14 0.30 1.000 -
USER-DEFINED - 11.22 0.30 1.000 -
USER-DEFINED - 0.33 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 16.72 SUBAREA RUNOFF(CFS) = 12.41
EFFECTIVE AREA(ACRES) = 2508.50 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA(ACRES) = 2572.6 PEAK FLOW RATE(CFS) = 1889.37

*****
FLOW PROCESS FROM NODE 13642.00 TO NODE 13643.00 IS CODE = 56
-----
```

```
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 394.80 DOWNSTREAM(FEET) = 342.39
CHANNEL LENGTH THRU SUBAREA(FEET) = 2913.57 CHANNEL SLOPE = 0.0180
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 4.23
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.094
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.22 0.30 1.000 -
USER-DEFINED - 2.17 0.30 1.000 -
USER-DEFINED - 9.19 0.30 1.000 -
USER-DEFINED - 67.57 0.30 1.000 -
USER-DEFINED - 35.19 0.30 1.000 -
```



USER-DEFINED - 30.67 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 1941.22  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 10.77  
 AVERAGE FLOW DEPTH (FEET) = 4.22 TRAVEL TIME (MIN.) = 4.51  
 Tc (MIN.) = 71.81  
 SUBAREA AREA (ACRES) = 145.01 SUBAREA RUNOFF (CFS) = 103.69  
 EFFECTIVE AREA (ACRES) = 2653.51 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA (ACRES) = 2717.6 PEAK FLOW RATE (CFS) = 1924.53  
 GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 4.21

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 4.21 FLOW VELOCITY (FEET/SEC.) = 10.73  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13643.00 = 30784.34 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1853.35	31.72	1.662	0.30 (0.29)	0.97	1496.6	20100.00
2	1867.13	37.09	1.523	0.30 (0.29)	0.97	1682.3	13600.00
3	1924.53	71.81	1.094	0.30 (0.29)	0.96	2653.5	13510.00
4	1830.43	80.42	1.036	0.30 (0.29)	0.96	2717.6	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 1924.53 Tc (MIN.) = 71.81  
 AREA-AVERAGED Fm (INCH/HR) = 0.29 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.96 EFFECTIVE AREA (ACRES) = 2653.51

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13643.00 TO NODE 13643.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 71.81

\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.094

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.89	0.30	1.000	-
USER-DEFINED	-	20.65	0.30	1.000	-
USER-DEFINED	-	2.69	0.30	1.000	-
USER-DEFINED	-	8.45	0.30	1.000	-
USER-DEFINED	-	96.93	0.30	1.000	-
USER-DEFINED	-	13.19	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 142.80 SUBAREA RUNOFF (CFS) = 102.11

EFFECTIVE AREA (ACRES) = 2796.31 AREA-AVERAGED Fm (INCH/HR) = 0.29

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96

TOTAL AREA (ACRES) = 2860.4 PEAK FLOW RATE (CFS) = 2026.64

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13643.00 TO NODE 13643.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 71.81  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.094  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/  
LAND USE            SCS SOIL    AREA        Fp        Ap        SCS  
                          GROUP    (ACRES)    (INCH/HR)    (DECIMAL)    CN  
 USER-DEFINED        -        42.54        0.30        1.000        -  
 USER-DEFINED        -        16.96        0.30        1.000        -  
 USER-DEFINED        -        80.60        0.30        1.000        -  
 USER-DEFINED        -        1.56        0.30        1.000        -  
 USER-DEFINED        -        2.00        0.30        1.000        -  
 USER-DEFINED        -        3.11        0.30        1.000        -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 146.77 SUBAREA RUNOFF (CFS) = 104.95  
 EFFECTIVE AREA (ACRES) = 2943.08 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97  
 TOTAL AREA (ACRES) = 3007.2 PEAK FLOW RATE (CFS) = 2131.59

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2201.63	31.72	1.662	0.30 (0.29)	0.98	1786.2	20100.00
2	2183.27	37.09	1.523	0.30 (0.29)	0.97	1971.9	13600.00
3	2131.59	71.81	1.094	0.30 (0.29)	0.97	2943.1	13510.00
4	2022.39	80.42	1.036	0.30 (0.29)	0.96	3007.2	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 2201.63 Tc (MIN.) = 31.72  
 AREA-AVERAGED Fm (INCH/HR) = 0.29 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.98 EFFECTIVE AREA (ACRES) = 1786.18

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13643.00 TO NODE 13660.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 342.39 DOWNSTREAM (FEET) = 300.00

CHANNEL LENGTH THRU SUBAREA (FEET) = 1591.23 CHANNEL SLOPE = 0.0266

GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT (FEET) = 4.10

\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.609

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.89	0.30	1.000	-
USER-DEFINED	-	23.73	0.30	1.000	-
USER-DEFINED	-	0.27	0.30	1.000	-
USER-DEFINED	-	19.87	0.30	1.000	-
USER-DEFINED	-	6.40	0.30	1.000	-
USER-DEFINED	-	3.14	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 2233.62

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 12.88

AVERAGE FLOW DEPTH (FEET) = 4.10 TRAVEL TIME (MIN.) = 2.06

Tc (MIN.) = 33.78

SUBAREA AREA (ACRES) = 54.30 SUBAREA RUNOFF (CFS) = 63.97  
 EFFECTIVE AREA (ACRES) = 1840.48 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98  
 TOTAL AREA (ACRES) = 3061.5 PEAK FLOW RATE (CFS) = 2201.63  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 4.06

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 4.06 FLOW VELOCITY (FEET/SEC.) = 12.84  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 32375.57 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2201.63	33.78	1.609	0.30 (0.29)	0.98	1840.5	20100.00
2	2183.27	39.15	1.469	0.30 (0.29)	0.98	2026.2	13600.00
3	2132.60	73.89	1.080	0.30 (0.29)	0.97	2997.4	13510.00
4	2022.39	82.54	1.022	0.30 (0.29)	0.96	3061.5	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 2201.63 Tc (MIN.) = 33.78  
 AREA-AVERAGED Fm (INCH/HR) = 0.29 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.98 EFFECTIVE AREA (ACRES) = 1840.48

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 33.78

\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.609

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.67	0.30	1.000	-
USER-DEFINED	-	9.52	0.30	1.000	-
USER-DEFINED	-	0.71	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	39.42	0.30	1.000	-
USER-DEFINED	-	0.62	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 51.16 SUBAREA RUNOFF (CFS) = 60.27

EFFECTIVE AREA (ACRES) = 1891.64 AREA-AVERAGED Fm (INCH/HR) = 0.29

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98

TOTAL AREA (ACRES) = 3112.6 PEAK FLOW RATE (CFS) = 2239.80

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 33.78

\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.609

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.67	0.30	1.000	-
USER-DEFINED	-	9.52	0.30	1.000	-
USER-DEFINED	-	0.71	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	39.42	0.30	1.000	-
USER-DEFINED	-	0.62	0.30	1.000	-

USER-DEFINED - 0.11 0.30 1.000 -  
 USER-DEFINED - 0.77 0.30 1.000 -  
 USER-DEFINED - 0.22 0.30 1.000 -  
 USER-DEFINED - 2.69 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 3.79 SUBAREA RUNOFF (CFS) = 4.46  
 EFFECTIVE AREA (ACRES) = 1895.43 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98  
 TOTAL AREA (ACRES) = 3116.4 PEAK FLOW RATE (CFS) = 2244.27

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13643.00 TO NODE 13660.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13659.00 TO NODE 13659.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 2P50EVA.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	528.88	14.09	0.30 (0.11)	0.36	173.1	110.00
2	529.33	16.63	0.30 (0.11)	0.37	204.3	100.00
3	521.87	17.83	0.30 (0.11)	0.38	213.9	100.00
4	463.87	20.89	0.30 (0.12)	0.40	221.1	130.00
TOTAL AREA (ACRES) =						221.1

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13659.00 TO NODE 13660.00 IS CODE = 31  
 -----

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<

>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 338.00 DOWNSTREAM (FEET) = 300.00

FLOW LENGTH (FEET) = 881.07 MANNING'S N = 0.013

DEPTH OF FLOW IN 108.0 INCH PIPE IS 81.0 INCHES

PIPE-FLOW VELOCITY (FEET/SEC.) = 43.83

ESTIMATED PIPE DIAMETER (INCH) = 108.00 NUMBER OF PIPES = 1

PIPE-FLOW (CFS) = 2244.27

PIPE TRAVEL TIME (MIN.) = 0.34 Tc (MIN.) = 34.11

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2244.27	34.11	1.600	0.30 (0.29)	0.98	1895.4	20100.00
2	2202.96	39.49	1.460	0.30 (0.29)	0.98	2081.1	13600.00

3 2171.20 74.23 1.078 0.30( 0.29) 0.97 3052.3 13510.00  
 4 2054.87 82.88 1.020 0.30( 0.29) 0.97 3116.4 13500.00  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	528.88	14.09	2.758	0.30( 0.11)	0.36	173.1	110.00
2	529.33	16.63	2.477	0.30( 0.11)	0.37	204.3	100.00
3	521.87	17.83	2.374	0.30( 0.11)	0.38	213.9	100.00
4	463.87	20.89	2.138	0.30( 0.12)	0.40	221.1	130.00

LONGEST FLOWPATH FROM NODE 130.00 TO NODE 13660.00 = 6327.50 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2276.62	14.09	2.758	0.30( 0.26)	0.87	955.9	110.00
2	2357.12	16.63	2.477	0.30( 0.26)	0.87	1128.4	100.00
3	2390.18	17.83	2.374	0.30( 0.26)	0.87	1204.9	100.00
4	2404.22	20.89	2.138	0.30( 0.27)	0.89	1381.9	130.00
5	2584.45	34.11	1.600	0.30( 0.28)	0.92	2116.5	20100.00
6	2510.99	39.49	1.460	0.30( 0.28)	0.92	2302.2	13600.00
7	2391.39	74.23	1.078	0.30( 0.28)	0.93	3273.4	13510.00
8	2261.67	82.88	1.020	0.30( 0.28)	0.93	3337.5	13500.00

TOTAL AREA (ACRES) = 3337.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 2584.45 Tc(MIN.) = 34.110  
 EFFECTIVE AREA(ACRES) = 2116.53 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.87  
 TOTAL AREA(ACRES) = 3337.5  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 34.11

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.600

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "FALLOW"	B	1.11	0.30	1.000	86
AGRICULTURAL POOR COVER "FALLOW"	B	0.44	0.30	1.000	86
NATURAL FAIR COVER "GRASS"	B	1.49	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	1.70	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	1.09	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	18.57	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 24.40 SUBAREA RUNOFF(CFS) = 28.55

EFFECTIVE AREA(ACRES) = 2140.93 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 3361.9 PEAK FLOW RATE(CFS) = 2584.45  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 34.11

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.600

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL FAIR COVER "ORCHARDS"	B	12.39	0.30	1.000	65
AGRICULTURAL FAIR COVER "ORCHARDS"	B	2.30	0.30	1.000	65
AGRICULTURAL POOR COVER "ROW CROPS, CONTOURED"	B	5.19	0.30	1.000	79
AGRICULTURAL POOR COVER "ROW CROPS, STRAIGHT ROW"	B	28.71	0.30	1.000	81
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.17	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 48.76 SUBAREA RUNOFF(CFS) = 57.06

EFFECTIVE AREA(ACRES) = 2189.69 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92

TOTAL AREA(ACRES) = 3410.7 PEAK FLOW RATE(CFS) = 2609.48

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13660.00 TO NODE 13680.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 300.00 DOWNSTREAM(FEET) = 288.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 933.89 CHANNEL SLOPE = 0.0128

GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 5.43

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.561

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	9.23	0.30	1.000	-
USER-DEFINED	-	0.54	0.30	1.000	-
USER-DEFINED	-	5.66	0.30	1.000	-
USER-DEFINED	-	3.66	0.30	1.000	-
USER-DEFINED	-	0.67	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2620.82

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.43

AVERAGE FLOW DEPTH(FEET) = 5.43 TRAVEL TIME(MIN.) = 1.49

Tc(MIN.) = 35.60  
 SUBAREA AREA(ACRES) = 19.98 SUBAREA RUNOFF(CFS) = 22.68  
 EFFECTIVE AREA(ACRES) = 2209.67 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 3430.6 PEAK FLOW RATE(CFS) = 2609.48  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 5.41

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 5.41 FLOW VELOCITY(FEET/SEC.) = 10.43  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13680.00 = 34190.53 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2310.60	15.63	2.561	0.30( 0.26)	0.88	1049.1	110.00
2	2393.75	18.16	2.347	0.30( 0.26)	0.88	1221.5	100.00
3	2427.48	19.36	2.245	0.30( 0.26)	0.88	1298.1	100.00
4	2450.06	22.41	2.050	0.30( 0.27)	0.89	1475.1	130.00
5	2609.48	35.60	1.561	0.30( 0.28)	0.92	2209.7	20100.00
6	2529.63	40.99	1.431	0.30( 0.28)	0.92	2395.3	13600.00
7	2406.81	75.76	1.068	0.30( 0.28)	0.93	3366.6	13510.00
8	2274.74	84.43	1.009	0.30( 0.28)	0.93	3430.6	13500.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE(CFS) = 2609.48 Tc(MIN.) = 35.60  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.92 EFFECTIVE AREA(ACRES) = 2209.67

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 35.60  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.561  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 1.56 0.30 1.000 -  
 USER-DEFINED - 9.40 0.30 1.000 -  
 USER-DEFINED - 2.76 0.30 1.000 -  
 USER-DEFINED - 17.38 0.30 1.000 -  
 USER-DEFINED - 2.46 0.30 1.000 -  
 USER-DEFINED - 5.56 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 39.12 SUBAREA RUNOFF(CFS) = 44.41  
 EFFECTIVE AREA(ACRES) = 2248.79 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 3469.8 PEAK FLOW RATE(CFS) = 2609.48  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 35.60  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.561  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 0.65 0.30 1.000 -  
 USER-DEFINED - 1.70 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 2.35 SUBAREA RUNOFF(CFS) = 2.67  
 EFFECTIVE AREA(ACRES) = 2251.14 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 3472.1 PEAK FLOW RATE(CFS) = 2609.48  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13660.00 TO NODE 13680.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 3 <<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 35.60  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.561  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 5.29 0.30 1.000 -  
 USER-DEFINED - 31.25 0.30 1.000 -  
 USER-DEFINED - 0.22 0.30 1.000 -  
 USER-DEFINED - 6.26 0.30 1.000 -  
 USER-DEFINED - 0.07 0.30 1.000 -  
 USER-DEFINED - 0.22 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 43.31 SUBAREA RUNOFF(CFS) = 49.17  
 EFFECTIVE AREA(ACRES) = 2294.45 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 3515.4 PEAK FLOW RATE(CFS) = 2651.97

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 35.60  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.561  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 2.47 0.30 0.850 -  
 USER-DEFINED - 3.06 0.30 0.850 -  
 USER-DEFINED - 17.76 0.30 0.500 -

USER-DEFINED - 7.31 0.30 0.500 -  
 USER-DEFINED - 0.34 0.30 1.000 -  
 USER-DEFINED - 8.22 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.659  
 SUBAREA AREA (ACRES) = 39.16 SUBAREA RUNOFF (CFS) = 48.07  
 EFFECTIVE AREA (ACRES) = 2333.61 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA (ACRES) = 3554.6 PEAK FLOW RATE (CFS) = 2700.04

\*\*\*\*\*

FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 35.60  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.561  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 0.53 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 0.53 SUBAREA RUNOFF (CFS) = 0.60  
 EFFECTIVE AREA (ACRES) = 2334.14 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA (ACRES) = 3555.1 PEAK FLOW RATE (CFS) = 2700.64

\*\*\*\*\*

FLOW PROCESS FROM NODE 13680.00 TO NODE 13682.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 288.00 DOWNSTREAM (FEET) = 242.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 2860.77 CHANNEL SLOPE = 0.0161  
 GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 5.20  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.453  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 0.22 0.30 1.000 -  
 USER-DEFINED - 5.28 0.30 1.000 -  
 USER-DEFINED - 0.52 0.30 1.000 -  
 USER-DEFINED - 3.61 0.30 1.000 -  
 USER-DEFINED - 0.67 0.30 1.000 -  
 USER-DEFINED - 1.37 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 2706.69  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 11.41  
 AVERAGE FLOW DEPTH (FEET) = 5.20 TRAVEL TIME (MIN.) = 4.18  
 Tc (MIN.) = 39.78  
 SUBAREA AREA (ACRES) = 11.67 SUBAREA RUNOFF (CFS) = 12.11  
 EFFECTIVE AREA (ACRES) = 2345.81 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92

TOTAL AREA (ACRES) = 3566.8 PEAK FLOW RATE (CFS) = 2700.64  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 5.19

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 5.19 FLOW VELOCITY (FEET/SEC.) = 11.41  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13682.00 = 37051.30 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2426.61	19.94	2.195	0.30 ( 0.26)	0.88	1185.2	110.00
2	2523.08	22.41	2.050	0.30 ( 0.26)	0.88	1357.6	100.00
3	2535.23	23.61	1.980	0.30 ( 0.26)	0.88	1434.2	100.00
4	2565.50	26.65	1.836	0.30 ( 0.27)	0.89	1611.2	130.00
5	2700.64	39.78	1.453	0.30 ( 0.28)	0.92	2345.8	20100.00
6	2617.49	45.21	1.363	0.30 ( 0.28)	0.92	2531.5	13600.00
7	2479.31	80.04	1.039	0.30 ( 0.28)	0.93	3502.7	13510.00
8	2338.52	88.79	0.980	0.30 ( 0.28)	0.93	3566.8	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 2700.64 Tc (MIN.) = 39.78  
 AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.92 EFFECTIVE AREA (ACRES) = 2345.81

\*\*\*\*\*

FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 39.78  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.453  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 6.90 0.30 1.000 -  
 USER-DEFINED - 23.04 0.30 1.000 -  
 USER-DEFINED - 1.18 0.30 1.000 -  
 USER-DEFINED - 1.56 0.30 1.000 -  
 USER-DEFINED - 53.20 0.30 1.000 -  
 USER-DEFINED - 2.08 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 87.96 SUBAREA RUNOFF (CFS) = 91.26  
 EFFECTIVE AREA (ACRES) = 2433.77 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA (ACRES) = 3654.7 PEAK FLOW RATE (CFS) = 2700.64  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 39.78  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.453  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.01	0.30	1.000	-
USER-DEFINED	-	0.18	0.30	1.000	-
USER-DEFINED	-	0.38	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	7.73	0.30	1.000	-
USER-DEFINED	-	4.37	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 12.89 SUBAREA RUNOFF (CFS) = 13.37  
EFFECTIVE AREA (ACRES) = 2446.66 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
TOTAL AREA (ACRES) = 3667.6 PEAK FLOW RATE (CFS) = 2700.64  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 39.78  
\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.453  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "FALLOW"	B	2.57	0.30	1.000	86
AGRICULTURAL POOR COVER "FALLOW"	B	1.97	0.30	1.000	86
NATURAL FAIR COVER "GRASS"	B	1.00	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	2.98	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	2.39	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	1.67	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 12.58 SUBAREA RUNOFF (CFS) = 13.05  
EFFECTIVE AREA (ACRES) = 2459.24 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
TOTAL AREA (ACRES) = 3680.2 PEAK FLOW RATE (CFS) = 2700.64  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 39.78  
\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.453  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	0.44	0.30	1.000	66

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	2.65	0.30	0.850	56
PUBLIC PARK	B	1.16	0.30	0.850	56
RESIDENTIAL "5-7 DWELLINGS/ACRE"	B	0.47	0.30	0.500	56
RESIDENTIAL "5-7 DWELLINGS/ACRE"	B	0.25	0.30	0.500	56
AGRICULTURAL POOR COVER "ROW CROPS, STRAIGHT ROW"	B	20.24	0.30	1.000	81

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.963  
SUBAREA AREA (ACRES) = 25.21 SUBAREA RUNOFF (CFS) = 26.41  
EFFECTIVE AREA (ACRES) = 2484.45 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
TOTAL AREA (ACRES) = 3705.4 PEAK FLOW RATE (CFS) = 2700.64  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 39.78  
\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.453  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.08	0.30	1.000	-
USER-DEFINED	-	6.75	0.30	1.000	-
USER-DEFINED	-	0.02	0.30	1.000	-
USER-DEFINED	-	0.93	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 14.78 SUBAREA RUNOFF (CFS) = 15.33  
EFFECTIVE AREA (ACRES) = 2499.23 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
TOTAL AREA (ACRES) = 3720.2 PEAK FLOW RATE (CFS) = 2700.64  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13682.00 TO NODE 13683.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 242.00 DOWNSTREAM (FEET) = 208.53  
CHANNEL LENGTH THRU SUBAREA (FEET) = 2526.22 CHANNEL SLOPE = 0.0132  
GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\* ESTIMATED CHANNEL HEIGHT (FEET) = 5.49  
\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.387

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.49	0.30	1.000	-
USER-DEFINED	-	13.31	0.30	1.000	-
USER-DEFINED	-	0.87	0.30	1.000	-
USER-DEFINED	-	20.26	0.30	1.000	-
USER-DEFINED	-	1.21	0.30	1.000	-

USER-DEFINED - 0.05 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 2722.25  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 10.67  
 AVERAGE FLOW DEPTH (FEET) = 5.49 TRAVEL TIME (MIN.) = 3.95  
 Tc (MIN.) = 43.73  
 SUBAREA AREA (ACRES) = 44.19 SUBAREA RUNOFF (CFS) = 43.22  
 EFFECTIVE AREA (ACRES) = 2543.42 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 3764.4 PEAK FLOW RATE (CFS) = 2700.64  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 5.47

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 5.47 FLOW VELOCITY (FEET/SEC.) = 10.64  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13683.00 = 39577.52 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2426.61	24.00	1.957	0.30 (0.27)	0.90	1382.8	110.00
2	2523.08	26.43	1.844	0.30 (0.27)	0.90	1555.2	100.00
3	2535.23	27.62	1.798	0.30 (0.27)	0.90	1631.8	100.00
4	2565.50	30.65	1.690	0.30 (0.27)	0.90	1808.8	130.00
5	2700.64	43.73	1.387	0.30 (0.28)	0.93	2543.4	20100.00
6	2620.76	49.19	1.298	0.30 (0.28)	0.93	2729.1	13600.00
7	2498.72	84.08	1.012	0.30 (0.28)	0.93	3700.3	13510.00
8	2345.92	92.91	0.959	0.30 (0.28)	0.93	3764.4	13500.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE (CFS) = 2700.64 Tc (MIN.) = 43.73  
 AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA (ACRES) = 2543.42

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====  
 MAINLINE Tc (MIN.) = 43.73  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.387  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	12.56	0.30	1.000	-
USER-DEFINED	-	0.81	0.30	1.000	-
USER-DEFINED	-	0.01	0.30	1.000	-
USER-DEFINED	-	1.11	0.30	1.000	-
USER-DEFINED	-	0.59	0.30	1.000	-
USER-DEFINED	-	3.04	0.30	1.000	-

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 18.12 SUBAREA RUNOFF (CFS) = 17.72  
 EFFECTIVE AREA (ACRES) = 2561.54 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 3782.5 PEAK FLOW RATE (CFS) = 2700.64

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====  
 MAINLINE Tc (MIN.) = 43.73  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.387  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL					
"8-10 DWELLINGS/ACRE"	B	0.10	0.30	0.400	56
PUBLIC PARK	B	1.30	0.30	0.850	56
RESIDENTIAL					
"8-10 DWELLINGS/ACRE"	B	0.10	0.30	0.400	56
PUBLIC PARK	B	1.70	0.30	0.850	56
PUBLIC PARK	B	0.10	0.30	0.850	56
PUBLIC PARK	B	2.90	0.30	0.850	56

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.835  
 SUBAREA AREA (ACRES) = 6.20 SUBAREA RUNOFF (CFS) = 6.34  
 EFFECTIVE AREA (ACRES) = 2567.74 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 3788.7 PEAK FLOW RATE (CFS) = 2700.64  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====  
 MAINLINE Tc (MIN.) = 43.73  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.387  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL					
"5-7 DWELLINGS/ACRE"	B	0.10	0.30	0.500	56
CONDOMINIUMS	B	0.10	0.30	0.350	56
PUBLIC PARK	B	6.90	0.30	0.850	56
PUBLIC PARK	B	0.40	0.30	0.850	56

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.839  
 SUBAREA AREA (ACRES) = 7.50 SUBAREA RUNOFF (CFS) = 7.66  
 EFFECTIVE AREA (ACRES) = 2575.24 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 3796.2 PEAK FLOW RATE (CFS) = 2700.64  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13682.00 TO NODE 13683.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*MEMORY BANK # 3 IS EMPTY - PROCESS IGNORED.\*\*\*

\*\*\*\*\*

FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 43.73

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.387

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "FALLOW"	B	2.55	0.30	1.000	86
AGRICULTURAL POOR COVER "FALLOW"	B	0.01	0.30	1.000	86
AGRICULTURAL POOR COVER "FALLOW"	B	1.35	0.30	1.000	86
NATURAL FAIR COVER "GRASS"	B	0.44	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	0.67	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	1.06	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 6.08 SUBAREA RUNOFF(CFS) = 5.95

EFFECTIVE AREA(ACRES) = 2581.32 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA(ACRES) = 3802.3 PEAK FLOW RATE(CFS) = 2700.64

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 43.73

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.387

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	2.16	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	2.45	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	6.15	0.30	1.000	66
AGRICULTURAL POOR COVER "ROW CROPS,STRAIGHT ROW"	B	1.34	0.30	1.000	81
AGRICULTURAL POOR COVER "ROW CROPS,STRAIGHT ROW"	B	18.46	0.30	1.000	81
AGRICULTURAL POOR COVER "ROW CROPS,STRAIGHT ROW"	B	4.13	0.30	1.000	81

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 34.69 SUBAREA RUNOFF(CFS) = 33.93

EFFECTIVE AREA(ACRES) = 2616.01 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA(ACRES) = 3837.0 PEAK FLOW RATE(CFS) = 2700.64

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 43.73

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.387

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "ROW CROPS,STRAIGHT ROW"	B	8.69	0.30	1.000	81
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.73	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.41	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND,GRASS"	B	1.37	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND,GRASS"	B	3.11	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 14.31 SUBAREA RUNOFF(CFS) = 13.99

EFFECTIVE AREA(ACRES) = 2630.32 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA(ACRES) = 3851.3 PEAK FLOW RATE(CFS) = 2700.64

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13683.00 TO NODE 13685.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 208.53 DOWNSTREAM(FEET) = 194.24

CHANNEL LENGTH THRU SUBAREA(FEET) = 289.01 CHANNEL SLOPE = 0.0494

GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 3.84

CHANNEL FLOW THRU SUBAREA(CFS) = 2700.64

FLOW VELOCITY(FEET/SEC.) = 16.94 FLOW DEPTH(FEET) = 3.84

TRAVEL TIME(MIN.) = 0.28 Tc(MIN.) = 44.01

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13685.00 = 39866.53 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2426.61	24.30	1.940	0.30( 0.27)	0.90	1469.7	110.00
2	2523.08	26.72	1.833	0.30( 0.27)	0.90	1642.1	100.00
3	2535.23	27.91	1.787	0.30( 0.27)	0.90	1718.7	100.00
4	2565.50	30.94	1.683	0.30( 0.27)	0.91	1895.7	130.00
5	2700.64	44.01	1.382	0.30( 0.28)	0.93	2630.3	20100.00
6	2620.76	49.48	1.293	0.30( 0.28)	0.93	2816.0	13600.00
7	2498.72	84.37	1.010	0.30( 0.28)	0.93	3787.2	13510.00
8	2354.93	93.20	0.958	0.30( 0.28)	0.93	3851.3	13500.00

NEW PEAK FLOW DATA ARE:



PEAK FLOW RATE(CFS) = 2700.64 Tc(MIN.) = 44.01  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 2630.32

\*\*\*\*\*

FLOW PROCESS FROM NODE 13685.00 TO NODE 13410.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 194.24 DOWNSTREAM(FEET) = 178.72  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1843.57 CHANNEL SLOPE = 0.0084  
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.16

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.327

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.23	0.30	1.000	-
USER-DEFINED	-	1.52	0.30	1.000	-
USER-DEFINED	-	0.06	0.30	1.000	-
USER-DEFINED	-	0.13	0.30	1.000	-
USER-DEFINED	-	6.45	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2704.52

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.06

AVERAGE FLOW DEPTH(FEET) = 6.16 TRAVEL TIME(MIN.) = 3.39

Tc(MIN.) = 47.40

SUBAREA AREA(ACRES) = 8.39 SUBAREA RUNOFF(CFS) = 7.76

EFFECTIVE AREA(ACRES) = 2638.71 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA(ACRES) = 3859.7 PEAK FLOW RATE(CFS) = 2700.64

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.15

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 6.15 FLOW VELOCITY(FEET/SEC.) = 9.06

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13410.00 = 41710.10 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2426.61	27.79	1.792	0.30( 0.27)	0.90	1478.1	110.00
2	2523.08	30.18	1.702	0.30( 0.27)	0.90	1650.5	100.00
3	2535.23	31.37	1.671	0.30( 0.27)	0.90	1727.1	100.00
4	2565.50	34.38	1.593	0.30( 0.27)	0.91	1904.1	130.00
5	2700.64	47.40	1.327	0.30( 0.28)	0.93	2638.7	20100.00
6	2620.76	52.90	1.253	0.30( 0.28)	0.93	2824.4	13600.00
7	2498.72	87.84	0.987	0.30( 0.28)	0.93	3795.6	13510.00
8	2354.93	96.73	0.943	0.30( 0.28)	0.93	3859.7	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2700.64 Tc(MIN.) = 47.40

AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 2638.71

=====  
 END OF STUDY SUMMARY:  
 TOTAL AREA(ACRES) = 3859.7 TC(MIN.) = 47.40  
 EFFECTIVE AREA(ACRES) = 2638.71 AREA-AVERAGED Fm(INCH/HR)= 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.928  
 PEAK FLOW RATE(CFS) = 2700.64

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2426.61	27.79	1.792	0.30( 0.27)	0.90	1478.1	110.00
2	2523.08	30.18	1.702	0.30( 0.27)	0.90	1650.5	100.00
3	2535.23	31.37	1.671	0.30( 0.27)	0.90	1727.1	100.00
4	2565.50	34.38	1.593	0.30( 0.27)	0.91	1904.1	130.00
5	2700.64	47.40	1.327	0.30( 0.28)	0.93	2638.7	20100.00
6	2620.76	52.90	1.253	0.30( 0.28)	0.93	2824.4	13600.00
7	2498.72	87.84	0.987	0.30( 0.28)	0.93	3795.6	13510.00
8	2354.93	96.73	0.943	0.30( 0.28)	0.93	3859.7	13500.00

=====  
 END OF RATIONAL METHOD ANALYSIS



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S38- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 50-YR RM EV APRIL 2019 CCHIU \*  
\*\*\*\*\*

FILE NAME: RI50EV37.DAT  
TIME/DATE OF STUDY: 09:16 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 50.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.240
- 2) 10.00; 3.389
- 3) 15.00; 2.611
- 4) 20.00; 2.187
- 5) 25.00; 1.897
- 6) 30.00; 1.705
- 7) 40.00; 1.446
- 8) 50.00; 1.284
- 9) 60.00; 1.172
- 10) 90.00; 0.970
- 11) 120.00; 0.840
- 12) 180.00; 0.715
- 13) 360.00; 0.524
- 14) 1200.00; 0.229

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	(FT)	(FT)	SIDE / SIDE/ WAY	(FT)	(FT)	(FT)	(FT)	(n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI50EV34.DNA  
MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27273.19	21.77	0.30 ( 0.25)	0.82	6076.0	50700.00
2	29599.04	28.18	0.30 ( 0.25)	0.82	8376.0	110.00
3	32166.46	34.76	0.30 ( 0.25)	0.83	11452.0	130.00
4	34086.15	40.26	0.30 ( 0.25)	0.84	13982.6	150.00
5	37625.39	54.58	0.30 ( 0.26)	0.87	21033.2	390.00
6	39740.46	66.26	0.30 ( 0.27)	0.89	27087.2	13100.00
7	40558.90	73.17	0.30 ( 0.27)	0.90	30141.6	11801.00
8	42169.65	83.84	0.30 ( 0.27)	0.91	35562.9	11530.00
9	43104.00	88.18	0.30 ( 0.27)	0.91	38408.6	13510.00
10	44884.06	97.07	0.30 ( 0.28)	0.92	44209.9	13500.00
11	45772.56	101.59	0.30 ( 0.28)	0.93	47228.6	10800.00
12	46209.84	105.79	0.30 ( 0.28)	0.93	50173.9	11130.00
13	45711.33	115.40	0.30 ( 0.28)	0.94	55215.1	12410.00
14	45010.10	123.70	0.30 ( 0.28)	0.94	58954.3	11201.00
15	44530.48	128.69	0.30 ( 0.28)	0.94	60686.0	12201.00
16	43453.84	135.79	0.30 ( 0.28)	0.94	62543.1	12231.00
17	42103.86	143.66	0.30 ( 0.28)	0.94	64177.4	10400.00
18	40703.46	151.65	0.30 ( 0.28)	0.94	65472.5	12010.00
19	39476.98	157.67	0.30 ( 0.28)	0.94	65819.5	10210.00
20	35140.66	186.05	0.30 ( 0.28)	0.95	66557.9	10100.00
TOTAL AREA (ACRES) =						66557.9

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 3 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27273.19	21.77	0.30 ( 0.25)	0.82	6076.0	50700.00
2	29599.04	28.18	0.30 ( 0.25)	0.82	8376.0	110.00
3	32166.46	34.76	0.30 ( 0.25)	0.83	11452.0	130.00
4	34086.15	40.26	0.30 ( 0.25)	0.84	13982.6	150.00
5	37625.39	54.58	0.30 ( 0.26)	0.87	21033.2	390.00
6	39740.46	66.26	0.30 ( 0.27)	0.89	27087.2	13100.00
7	40558.90	73.17	0.30 ( 0.27)	0.90	30141.6	11801.00
8	42169.65	83.84	0.30 ( 0.27)	0.91	35562.9	11530.00
9	43104.00	88.18	0.30 ( 0.27)	0.91	38408.6	13510.00
10	44884.06	97.07	0.30 ( 0.28)	0.92	44209.9	13500.00
11	45772.56	101.59	0.30 ( 0.28)	0.93	47228.6	10800.00
12	46209.84	105.79	0.30 ( 0.28)	0.93	50173.9	11130.00
13	45711.33	115.40	0.30 ( 0.28)	0.94	55215.1	12410.00

14 45010.10 123.70 0.30( 0.28) 0.94 58954.3 11201.00  
 15 44530.48 128.69 0.30( 0.28) 0.94 60686.0 12201.00  
 16 43453.84 135.79 0.30( 0.28) 0.94 62543.1 12231.00  
 17 42103.86 143.66 0.30( 0.28) 0.94 64177.4 10400.00  
 18 40703.46 151.65 0.30( 0.28) 0.94 65472.5 12010.00  
 19 39476.98 157.67 0.30( 0.28) 0.94 65819.5 10210.00  
 20 35140.66 186.05 0.30( 0.28) 0.95 66557.9 10100.00  
 TOTAL AREA(ACRES) = 66557.9

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13700.00 TO NODE 13720.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 170.00 DOWNSTREAM(FEET) = 165.51  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1891.83 CHANNEL SLOPE = 0.0024  
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 14.17  
 CHANNEL FLOW THRU SUBAREA(CFS) = 46209.84  
 FLOW VELOCITY(FEET/SEC.) = 12.04 FLOW DEPTH(FEET) = 14.17  
 TRAVEL TIME(MIN.) = 2.62 Tc(MIN.) = 108.41  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126443.80 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27273.19	24.86	1.905	0.30( 0.25)	0.82	6076.0	50700.00
2	29599.04	31.19	1.674	0.30( 0.25)	0.82	8376.0	110.00
3	32166.46	37.69	1.506	0.30( 0.25)	0.83	11452.0	130.00
4	34086.15	43.14	1.395	0.30( 0.25)	0.84	13982.6	150.00
5	37625.39	57.37	1.201	0.30( 0.26)	0.87	21033.2	390.00
6	39740.46	69.00	1.111	0.30( 0.27)	0.89	27087.2	13100.00
7	40558.90	75.89	1.065	0.30( 0.27)	0.90	30141.6	11801.00
8	42169.65	86.54	0.993	0.30( 0.27)	0.91	35562.9	11530.00
9	43104.00	90.86	0.966	0.30( 0.27)	0.91	38408.6	13510.00
10	44884.06	99.71	0.928	0.30( 0.28)	0.92	44209.9	13500.00
11	45772.56	104.21	0.908	0.30( 0.28)	0.93	47228.6	10800.00
12	46209.84	108.41	0.890	0.30( 0.28)	0.93	50173.9	11130.00
13	45711.33	118.03	0.849	0.30( 0.28)	0.94	55215.1	12410.00
14	45010.10	126.34	0.827	0.30( 0.28)	0.94	58954.3	11201.00
15	44530.48	131.34	0.816	0.30( 0.28)	0.94	60686.0	12201.00
16	43453.84	138.46	0.802	0.30( 0.28)	0.94	62543.1	12231.00
17	42103.86	146.35	0.785	0.30( 0.28)	0.94	64177.4	10400.00
18	40703.46	154.38	0.768	0.30( 0.28)	0.94	65472.5	12010.00
19	39476.98	160.42	0.756	0.30( 0.28)	0.94	65819.5	10210.00
20	35140.66	188.91	0.706	0.30( 0.28)	0.95	66557.9	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 46209.84 Tc(MIN.) = 108.41  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 50173.95

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13700.00 TO NODE 13720.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13720.00 TO NODE 13720.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 0506102C.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	368.04	14.55	0.30( 0.29)	0.96	189.6	10230.00
2	334.70	24.11	0.30( 0.29)	0.95	240.8	10200.00
3	332.42	24.51	0.30( 0.29)	0.95	241.8	10250.00
4	305.13	28.32	0.30( 0.29)	0.95	246.3	10220.00
TOTAL AREA(ACRES) =						246.3

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13720.00 TO NODE 13720.00 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27273.19	24.86	1.905	0.30( 0.25)	0.82	6076.0	50700.00
2	29599.04	31.19	1.674	0.30( 0.25)	0.82	8376.0	110.00
3	32166.46	37.69	1.506	0.30( 0.25)	0.83	11452.0	130.00
4	34086.15	43.14	1.395	0.30( 0.25)	0.84	13982.6	150.00
5	37625.39	57.37	1.201	0.30( 0.26)	0.87	21033.2	390.00
6	39740.46	69.00	1.111	0.30( 0.27)	0.89	27087.2	13100.00
7	40558.90	75.89	1.065	0.30( 0.27)	0.90	30141.6	11801.00
8	42169.65	86.54	0.993	0.30( 0.27)	0.91	35562.9	11530.00
9	43104.00	90.86	0.966	0.30( 0.27)	0.91	38408.6	13510.00
10	44884.06	99.71	0.928	0.30( 0.28)	0.92	44209.9	13500.00
11	45772.56	104.21	0.908	0.30( 0.28)	0.93	47228.6	10800.00
12	46209.84	108.41	0.890	0.30( 0.28)	0.93	50173.9	11130.00
13	45711.33	118.03	0.849	0.30( 0.28)	0.94	55215.1	12410.00
14	45010.10	126.34	0.827	0.30( 0.28)	0.94	58954.3	11201.00
15	44530.48	131.34	0.816	0.30( 0.28)	0.94	60686.0	12201.00
16	43453.84	138.46	0.802	0.30( 0.28)	0.94	62543.1	12231.00
17	42103.86	146.35	0.785	0.30( 0.28)	0.94	64177.4	10400.00
18	40703.46	154.38	0.768	0.30( 0.28)	0.94	65472.5	12010.00
19	39476.98	160.42	0.756	0.30( 0.28)	0.94	65819.5	10210.00
20	35140.66	188.91	0.706	0.30( 0.28)	0.95	66557.9	10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 =							126443.80 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	368.04	14.55	2.681	0.30( 0.29)	0.96	189.6	10230.00
2	334.70	24.11	1.948	0.30( 0.29)	0.95	240.8	10200.00
3	332.42	24.51	1.925	0.30( 0.29)	0.95	241.8	10250.00
4	305.13	28.32	1.769	0.30( 0.29)	0.95	246.3	10220.00
LONGEST FLOWPATH FROM NODE 10200.00 TO NODE 13720.00 =							9099.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	--------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	23793.62	14.55	2.681	0.30 ( 0.25)	0.83	3745.1 10230.00
2	27479.31	24.11	1.948	0.30 ( 0.25)	0.82	6134.5 10200.00
3	27550.58	24.51	1.925	0.30 ( 0.25)	0.82	6232.2 10250.00
4	27603.10	24.86	1.905	0.30 ( 0.25)	0.82	6318.2 50700.00
5	28849.45	28.32	1.769	0.30 ( 0.25)	0.82	7579.3 10220.00
6	29884.55	31.19	1.674	0.30 ( 0.25)	0.82	8622.3 110.00
7	32417.36	37.69	1.506	0.30 ( 0.25)	0.83	11698.2 130.00
8	34314.29	43.14	1.395	0.30 ( 0.25)	0.84	14228.9 150.00
9	37813.68	57.37	1.201	0.30 ( 0.26)	0.87	21279.4 390.00
10	39910.22	69.00	1.111	0.30 ( 0.27)	0.89	27333.5 13100.00
11	40719.12	75.89	1.065	0.30 ( 0.27)	0.90	30387.8 11801.00
12	42315.12	86.54	0.993	0.30 ( 0.27)	0.91	35809.2 11530.00
13	43243.91	90.86	0.966	0.30 ( 0.27)	0.91	38654.9 13510.00
14	45016.08	99.71	0.928	0.30 ( 0.28)	0.92	44456.1 13500.00
15	45900.57	104.21	0.908	0.30 ( 0.28)	0.93	47474.9 10800.00
16	46334.11	108.41	0.890	0.30 ( 0.28)	0.93	50420.2 11130.00
17	45827.02	118.03	0.849	0.30 ( 0.28)	0.94	55461.4 12410.00
18	45121.32	126.34	0.827	0.30 ( 0.28)	0.94	59200.5 11201.00
19	44639.56	131.34	0.816	0.30 ( 0.28)	0.94	60932.2 12201.00
20	43559.86	138.46	0.802	0.30 ( 0.28)	0.94	62789.4 12231.00
21	42206.51	146.35	0.785	0.30 ( 0.28)	0.94	64423.7 10400.00
22	40802.66	154.38	0.768	0.30 ( 0.28)	0.94	65718.8 12010.00
23	39573.60	160.42	0.756	0.30 ( 0.28)	0.94	66065.7 10210.00
24	35226.94	188.91	0.706	0.30 ( 0.28)	0.95	66804.2 10100.00

TOTAL AREA (ACRES) = 66804.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 46334.11 Tc (MIN.) = 108.410  
EFFECTIVE AREA (ACRES) = 50420.21 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.91  
TOTAL AREA (ACRES) = 66804.2  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126443.80 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13720.00 TO NODE 13740.00 IS CODE = 56  
-----

>>>> COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
>>>> TRAVELTIME THRU SUBAREA<<<<

-----  
ELEVATION DATA: UPSTREAM (FEET) = 165.51 DOWNSTREAM (FEET) = 161.03  
CHANNEL LENGTH THRU SUBAREA (FEET) = 2067.54 CHANNEL SLOPE = 0.0022  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 14.55  
CHANNEL FLOW THRU SUBAREA (CFS) = 46334.11  
FLOW VELOCITY (FEET/SEC.) = 11.67 FLOW DEPTH (FEET) = 14.55  
TRAVEL TIME (MIN.) = 2.95 Tc (MIN.) = 111.36  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128511.34 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23793.62	18.19	2.340	0.30 ( 0.25)	0.83	3745.1	10230.00
2	27479.31	27.59	1.797	0.30 ( 0.25)	0.82	6134.5	10200.00
3	27550.58	27.99	1.782	0.30 ( 0.25)	0.82	6232.2	10250.00
4	27603.10	28.33	1.769	0.30 ( 0.25)	0.82	6318.2	50700.00
5	28849.45	31.74	1.660	0.30 ( 0.25)	0.82	7579.3	10220.00

6	29884.55	34.58	1.586	0.30 ( 0.25)	0.82	8622.3	110.00
7	32417.36	40.99	1.430	0.30 ( 0.25)	0.83	11698.2	130.00
8	34314.29	46.38	1.343	0.30 ( 0.25)	0.84	14228.9	150.00
9	37813.68	60.51	1.169	0.30 ( 0.26)	0.87	21279.4	390.00
10	39910.22	72.09	1.091	0.30 ( 0.27)	0.89	27333.5	13100.00
11	40719.12	78.96	1.044	0.30 ( 0.27)	0.90	30387.8	11801.00
12	42315.12	89.57	0.973	0.30 ( 0.27)	0.91	35809.2	11530.00
13	43243.91	93.87	0.953	0.30 ( 0.27)	0.91	38654.9	13510.00
14	45016.08	102.69	0.915	0.30 ( 0.28)	0.92	44456.1	13500.00
15	45900.57	107.17	0.896	0.30 ( 0.28)	0.93	47474.9	10800.00
16	46334.11	111.36	0.877	0.30 ( 0.28)	0.93	50420.2	11130.00
17	45827.02	120.99	0.838	0.30 ( 0.28)	0.94	55461.4	12410.00
18	45121.32	129.32	0.821	0.30 ( 0.28)	0.94	59200.5	11201.00
19	44639.56	134.32	0.810	0.30 ( 0.28)	0.94	60932.2	12201.00
20	43559.86	141.47	0.795	0.30 ( 0.28)	0.94	62789.4	12231.00
21	42206.51	149.39	0.779	0.30 ( 0.28)	0.94	64423.7	10400.00
22	40802.66	157.45	0.762	0.30 ( 0.28)	0.94	65718.8	12010.00
23	39573.60	163.52	0.749	0.30 ( 0.28)	0.94	66065.7	10210.00
24	35226.94	192.12	0.702	0.30 ( 0.28)	0.95	66804.2	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 46334.11 Tc (MIN.) = 111.36  
AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA (ACRES) = 50420.21

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13720.00 TO NODE 13740.00 IS CODE = 12  
-----

>>>> CLEAR MEMORY BANK # 3 <<<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13740.00 TO NODE 13740.00 IS CODE = 15.1  
-----

>>>> DEFINE MEMORY BANK # 3 <<<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506103C.DNA  
MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	702.74	18.17	0.30 ( 0.23)	0.76	400.0	10300.00
2	704.90	18.97	0.30 ( 0.23)	0.76	413.4	10380.00
3	693.05	21.35	0.30 ( 0.23)	0.76	439.7	10320.00
4	668.71	23.48	0.30 ( 0.23)	0.76	451.6	10360.00
5	629.78	26.35	0.30 ( 0.23)	0.76	460.8	10340.00
TOTAL AREA (ACRES) =						460.8

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13740.00 TO NODE 13740.00 IS CODE = 11  
-----

>>>> CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23793.62	18.19	2.340	0.30 ( 0.25)	0.83	3745.1	10230.00
2	27479.31	27.59	1.797	0.30 ( 0.25)	0.82	6134.5	10200.00
3	27550.58	27.99	1.782	0.30 ( 0.25)	0.82	6232.2	10250.00

4	27603.10	28.33	1.769	0.30 ( 0.25)	0.82	6318.2	50700.00
5	28849.45	31.74	1.660	0.30 ( 0.25)	0.82	7579.3	10220.00
6	29884.55	34.58	1.586	0.30 ( 0.25)	0.82	8622.3	110.00
7	32417.36	40.99	1.430	0.30 ( 0.25)	0.83	11698.2	130.00
8	34314.29	46.38	1.343	0.30 ( 0.25)	0.84	14228.9	150.00
9	37813.68	60.51	1.169	0.30 ( 0.26)	0.87	21279.4	390.00
10	39910.22	72.09	1.091	0.30 ( 0.27)	0.89	27333.5	13100.00
11	40719.12	78.96	1.044	0.30 ( 0.27)	0.90	30387.8	11801.00
12	42315.12	89.57	0.973	0.30 ( 0.27)	0.91	35809.2	11530.00
13	43243.91	93.87	0.953	0.30 ( 0.27)	0.91	38654.9	13510.00
14	45016.08	102.69	0.915	0.30 ( 0.28)	0.92	44456.1	13500.00
15	45900.57	107.17	0.896	0.30 ( 0.28)	0.93	47474.9	10800.00
16	46334.11	111.36	0.877	0.30 ( 0.28)	0.93	50420.2	11130.00
17	45827.02	120.99	0.838	0.30 ( 0.28)	0.94	55461.4	12410.00
18	45121.32	129.32	0.821	0.30 ( 0.28)	0.94	59200.5	11201.00
19	44639.56	134.32	0.810	0.30 ( 0.28)	0.94	60932.2	12201.00
20	43559.86	141.47	0.795	0.30 ( 0.28)	0.94	62789.4	12231.00
21	42206.51	149.39	0.779	0.30 ( 0.28)	0.94	64423.7	10400.00
22	40802.66	157.45	0.762	0.30 ( 0.28)	0.94	65718.8	12010.00
23	39573.60	163.52	0.749	0.30 ( 0.28)	0.94	66065.7	10210.00
24	35226.94	192.12	0.702	0.30 ( 0.28)	0.95	66804.2	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128511.34 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	702.74	18.17	2.342	0.30 ( 0.23)	0.76	400.0	10300.00
2	704.90	18.97	2.274	0.30 ( 0.23)	0.76	413.4	10380.00
3	693.05	21.35	2.109	0.30 ( 0.23)	0.76	439.7	10320.00
4	668.71	23.48	1.985	0.30 ( 0.23)	0.76	451.6	10360.00
5	629.78	26.35	1.845	0.30 ( 0.23)	0.76	460.8	10340.00

LONGEST FLOWPATH FROM NODE 10320.00 TO NODE 13740.00 = 8457.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24488.63	18.17	2.342	0.30 ( 0.25)	0.82	4140.4	10300.00
2	24496.42	18.19	2.340	0.30 ( 0.25)	0.82	4145.4	10230.00
3	24804.59	18.97	2.274	0.30 ( 0.25)	0.82	4356.9	10380.00
4	25724.71	21.35	2.109	0.30 ( 0.25)	0.82	4987.4	10320.00
5	26534.66	23.48	1.985	0.30 ( 0.25)	0.82	5540.2	10360.00
6	27623.76	26.35	1.845	0.30 ( 0.25)	0.82	6280.7	10340.00
7	28090.56	27.59	1.797	0.30 ( 0.25)	0.82	6595.3	10200.00
8	28155.95	27.99	1.782	0.30 ( 0.25)	0.82	6693.0	10250.00
9	28203.28	28.33	1.769	0.30 ( 0.25)	0.82	6779.0	50700.00
10	29407.06	31.74	1.660	0.30 ( 0.25)	0.82	8040.1	10220.00
11	30413.58	34.58	1.586	0.30 ( 0.25)	0.82	9083.1	110.00
12	32885.39	40.99	1.430	0.30 ( 0.25)	0.83	12159.0	130.00
13	34748.30	46.38	1.343	0.30 ( 0.25)	0.84	14689.7	150.00
14	38179.83	60.51	1.169	0.30 ( 0.26)	0.86	21740.2	390.00
15	40245.98	72.09	1.091	0.30 ( 0.27)	0.89	27794.3	13100.00
16	41036.85	78.96	1.044	0.30 ( 0.27)	0.89	30848.6	11801.00
17	42605.01	89.57	0.973	0.30 ( 0.27)	0.91	36270.0	11530.00
18	43526.14	93.87	0.953	0.30 ( 0.27)	0.91	39115.7	13510.00
19	45283.42	102.69	0.915	0.30 ( 0.28)	0.92	44916.9	13500.00
20	46160.34	107.17	0.896	0.30 ( 0.28)	0.93	47935.7	10800.00
21	46586.80	111.36	0.877	0.30 ( 0.28)	0.93	50881.0	11130.00
22	46064.32	120.99	0.838	0.30 ( 0.28)	0.94	55922.2	12410.00

23	45351.86	129.32	0.821	0.30 ( 0.28)	0.94	59661.3	11201.00
24	44866.04	134.32	0.810	0.30 ( 0.28)	0.94	61393.0	12201.00
25	43780.54	141.47	0.795	0.30 ( 0.28)	0.94	63250.2	12231.00
26	42420.75	149.39	0.779	0.30 ( 0.28)	0.94	64884.5	10400.00
27	41010.37	157.45	0.762	0.30 ( 0.28)	0.94	66179.6	12010.00
28	39776.37	163.52	0.749	0.30 ( 0.28)	0.94	66526.5	10210.00
29	35411.32	192.12	0.702	0.30 ( 0.28)	0.94	67265.0	10100.00

TOTAL AREA (ACRES) = 67265.0

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 46586.80 Tc (MIN.) = 111.362  
EFFECTIVE AREA (ACRES) = 50881.01 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.89  
TOTAL AREA (ACRES) = 67265.0  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128511.34 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13740.00 TO NODE 13741.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 161.03 DOWNSTREAM (FEET) = 141.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 364.08 CHANNEL SLOPE = 0.0550  
GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 8.46  
CHANNEL FLOW THRU SUBAREA (CFS) = 46586.80  
FLOW VELOCITY (FEET/SEC.) = 41.17 FLOW DEPTH (FEET) = 8.46  
TRAVEL TIME (MIN.) = 0.15 Tc (MIN.) = 111.51  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128875.41 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24488.63	18.35	2.327	0.30 ( 0.25)	0.82	4140.4	10300.00
2	24496.42	18.37	2.325	0.30 ( 0.25)	0.82	4145.4	10230.00
3	24804.59	19.15	2.259	0.30 ( 0.25)	0.82	4356.9	10380.00
4	25724.71	21.53	2.098	0.30 ( 0.25)	0.82	4987.4	10320.00
5	26534.66	23.65	1.975	0.30 ( 0.25)	0.82	5540.2	10360.00
6	27623.76	26.53	1.838	0.30 ( 0.25)	0.82	6280.7	10340.00
7	28090.56	27.77	1.791	0.30 ( 0.25)	0.82	6595.3	10200.00
8	28155.95	28.16	1.776	0.30 ( 0.25)	0.82	6693.0	10250.00
9	28203.28	28.50	1.762	0.30 ( 0.25)	0.82	6779.0	50700.00
10	29407.06	31.91	1.655	0.30 ( 0.25)	0.82	8040.1	10220.00
11	30413.58	34.74	1.582	0.30 ( 0.25)	0.82	9083.1	110.00
12	32885.39	41.15	1.427	0.30 ( 0.25)	0.83	12159.0	130.00
13	34748.30	46.54	1.340	0.30 ( 0.25)	0.84	14689.7	150.00
14	38179.83	60.67	1.167	0.30 ( 0.26)	0.86	21740.2	390.00
15	40245.98	72.25	1.090	0.30 ( 0.27)	0.89	27794.3	13100.00
16	41036.85	79.12	1.043	0.30 ( 0.27)	0.89	30848.6	11801.00
17	42605.01	89.73	0.972	0.30 ( 0.27)	0.91	36270.0	11530.00
18	43526.14	94.02	0.953	0.30 ( 0.27)	0.91	39115.7	13510.00
19	45283.42	102.84	0.914	0.30 ( 0.28)	0.92	44916.9	13500.00
20	46160.34	107.32	0.895	0.30 ( 0.28)	0.93	47935.7	10800.00
21	46586.80	111.51	0.877	0.30 ( 0.28)	0.93	50881.0	11130.00
22	46064.32	121.14	0.838	0.30 ( 0.28)	0.94	55922.2	12410.00
23	45351.86	129.47	0.820	0.30 ( 0.28)	0.94	59661.3	11201.00

24 44866.04 134.47 0.810 0.30( 0.28) 0.94 61393.0 12201.00  
25 43780.54 141.62 0.795 0.30( 0.28) 0.94 63250.2 12231.00  
26 42420.75 149.54 0.778 0.30( 0.28) 0.94 64884.5 10400.00  
27 41010.37 157.60 0.762 0.30( 0.28) 0.94 66179.6 12010.00  
28 39776.37 163.68 0.749 0.30( 0.28) 0.94 66526.5 10210.00  
29 35411.32 192.28 0.702 0.30( 0.28) 0.94 67265.0 10100.00

NEW PEAK FLOW DATA ARE:  
PEAK FLOW RATE(CFS) = 46586.80 Tc(MIN.) = 111.51  
AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 50881.01

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13740.00 TO NODE 13741.00 IS CODE = 12

-----  
>>>>CLEAR MEMORY BANK # 3 <<<<<<  
=====

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13741.00 TO NODE 13741.00 IS CODE = 15.1

-----  
>>>>DEFINE MEMORY BANK # 3 <<<<<<  
=====

PEAK FLOWRATE TABLE FILE NAME: 0506104C.DNA  
MEMORY BANK # 3 DEFINED AS FOLLOWS:  
STREAM Q Tc Fp(Fm) Ap Ae HEADWATER  
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE  
1 71.30 19.53 0.30( 0.24) 0.80 44.3 10400.00  
TOTAL AREA(ACRES) = 44.3

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13741.00 TO NODE 13741.00 IS CODE = 11

-----  
>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<<  
=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24488.63	18.35	2.327	0.30( 0.25)	0.82	4140.4	10300.00
2	24496.42	18.37	2.325	0.30( 0.25)	0.82	4145.4	10230.00
3	24804.59	19.15	2.259	0.30( 0.25)	0.82	4356.9	10380.00
4	25724.71	21.53	2.098	0.30( 0.25)	0.82	4987.4	10320.00
5	26534.66	23.65	1.975	0.30( 0.25)	0.82	5540.2	10360.00
6	27623.76	26.53	1.838	0.30( 0.25)	0.82	6280.7	10340.00
7	28090.56	27.77	1.791	0.30( 0.25)	0.82	6595.3	10200.00
8	28155.95	28.16	1.776	0.30( 0.25)	0.82	6693.0	10250.00
9	28203.28	28.50	1.762	0.30( 0.25)	0.82	6779.0	50700.00
10	29407.06	31.91	1.655	0.30( 0.25)	0.82	8040.1	10220.00
11	30413.58	34.74	1.582	0.30( 0.25)	0.82	9083.1	110.00
12	32885.39	41.15	1.427	0.30( 0.25)	0.83	12159.0	130.00
13	34748.30	46.54	1.340	0.30( 0.25)	0.84	14689.7	150.00
14	38179.83	60.67	1.167	0.30( 0.26)	0.86	21740.2	390.00
15	40245.98	72.25	1.090	0.30( 0.27)	0.89	27794.3	13100.00
16	41036.85	79.12	1.043	0.30( 0.27)	0.89	30848.6	11801.00
17	42605.01	89.73	0.972	0.30( 0.27)	0.91	36270.0	11530.00
18	43526.14	94.02	0.953	0.30( 0.27)	0.91	39115.7	13510.00
19	45283.42	102.84	0.914	0.30( 0.28)	0.92	44916.9	13500.00
20	46160.34	107.32	0.895	0.30( 0.28)	0.93	47935.7	10800.00

21 46586.80 111.51 0.877 0.30( 0.28) 0.93 50881.0 11130.00  
22 46064.32 121.14 0.838 0.30( 0.28) 0.94 55922.2 12410.00  
23 45351.86 129.47 0.820 0.30( 0.28) 0.94 59661.3 11201.00  
24 44866.04 134.47 0.810 0.30( 0.28) 0.94 61393.0 12201.00  
25 43780.54 141.62 0.795 0.30( 0.28) 0.94 63250.2 12231.00  
26 42420.75 149.54 0.778 0.30( 0.28) 0.94 64884.5 10400.00  
27 41010.37 157.60 0.762 0.30( 0.28) 0.94 66179.6 12010.00  
28 39776.37 163.68 0.749 0.30( 0.28) 0.94 66526.5 10210.00  
29 35411.32 192.28 0.702 0.30( 0.28) 0.94 67265.0 10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128875.41 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	71.30	19.53	2.227	0.30( 0.24)	0.80	44.3	10400.00

LONGEST FLOWPATH FROM NODE 10400.00 TO NODE 13741.00 = 6237.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24559.00	18.35	2.327	0.30( 0.25)	0.82	4182.0	10300.00
2	24566.81	18.37	2.325	0.30( 0.25)	0.82	4187.1	10230.00
3	24875.64	19.15	2.259	0.30( 0.25)	0.82	4400.3	10380.00
4	25024.07	19.53	2.227	0.30( 0.25)	0.82	4502.7	10400.00
5	25791.42	21.53	2.098	0.30( 0.25)	0.82	5031.7	10320.00
6	26596.94	23.65	1.975	0.30( 0.25)	0.82	5584.5	10360.00
7	27681.13	26.53	1.838	0.30( 0.25)	0.82	6325.0	10340.00
8	28146.23	27.77	1.791	0.30( 0.25)	0.82	6639.6	10200.00
9	28211.08	28.16	1.776	0.30( 0.25)	0.82	6737.3	10250.00
10	28257.93	28.50	1.762	0.30( 0.25)	0.82	6823.3	50700.00
11	29457.88	31.91	1.655	0.30( 0.25)	0.82	8084.4	10220.00
12	30461.76	34.74	1.582	0.30( 0.25)	0.82	9127.4	110.00
13	32928.01	41.15	1.427	0.30( 0.25)	0.83	12203.3	130.00
14	34787.79	46.54	1.340	0.30( 0.25)	0.84	14734.0	150.00
15	38213.13	60.67	1.167	0.30( 0.26)	0.86	21784.5	390.00
16	40276.48	72.25	1.090	0.30( 0.27)	0.88	27838.6	13100.00
17	41065.69	79.12	1.043	0.30( 0.27)	0.89	30892.9	11801.00
18	42631.29	89.73	0.972	0.30( 0.27)	0.91	36314.3	11530.00
19	43551.73	94.02	0.953	0.30( 0.27)	0.91	39160.0	13510.00
20	45307.64	102.84	0.914	0.30( 0.28)	0.92	44961.2	13500.00
21	46183.86	107.32	0.895	0.30( 0.28)	0.93	47980.0	10800.00
22	46609.68	111.51	0.877	0.30( 0.28)	0.93	50925.3	11130.00
23	46085.79	121.14	0.838	0.30( 0.28)	0.94	55966.5	12410.00
24	45372.70	129.47	0.820	0.30( 0.28)	0.94	59705.6	11201.00
25	44886.51	134.47	0.810	0.30( 0.28)	0.94	61437.3	12201.00
26	43800.47	141.62	0.795	0.30( 0.28)	0.94	63294.5	12231.00
27	42440.09	149.54	0.778	0.30( 0.28)	0.94	64928.8	10400.00
28	41029.11	157.60	0.762	0.30( 0.28)	0.94	66223.9	12010.00
29	39794.65	163.68	0.749	0.30( 0.28)	0.94	66570.8	10210.00
30	35427.92	192.28	0.702	0.30( 0.28)	0.94	67309.3	10100.00

TOTAL AREA(ACRES) = 67309.3

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:  
PEAK FLOW RATE(CFS) = 46609.68 Tc(MIN.) = 111.509  
EFFECTIVE AREA(ACRES) = 50925.31 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA(ACRES) = 67309.3  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128875.41 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13741.00 TO NODE 13802.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 141.00 DOWNSTREAM(FEET) = 135.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1533.41 CHANNEL SLOPE = 0.0039
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
\*ESTIMATED CHANNEL HEIGHT(FEET) = 17.09
CHANNEL FLOW THRU SUBAREA(CFS) = 46609.68
FLOW VELOCITY(FEET/SEC.) = 16.19 FLOW DEPTH(FEET) = 17.09
TRAVEL TIME(MIN.) = 1.58 Tc(MIN.) = 113.09
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130408.82 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 30 rows of data.

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 46609.68 Tc(MIN.) = 113.09
AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 50925.31

\*\*\*\*\*

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<

PEAK FLOWRATE TABLE FILE NAME: 0506105J.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 3 rows of data.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 30 rows of data.

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130408.82 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*



STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	385.37	14.62	2.670	0.30 ( 0.27)	0.90	207.5	10520.00
2	453.34	31.20	1.674	0.30 ( 0.28)	0.93	403.6	10500.00

LONGEST FLOWPATH FROM NODE 10500.00 TO NODE 13802.00 = 12187.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22698.10	14.62	2.670	0.30 ( 0.25)	0.82	3227.6	10520.00
2	24967.42	20.25	2.173	0.30 ( 0.25)	0.83	4456.1	10300.00
3	24975.33	20.27	2.172	0.30 ( 0.25)	0.83	4461.4	10230.00
4	25287.32	21.04	2.127	0.30 ( 0.25)	0.83	4683.7	10380.00
5	25437.31	21.42	2.105	0.30 ( 0.25)	0.83	4790.6	10400.00
6	26212.76	23.40	1.990	0.30 ( 0.25)	0.83	5342.9	10320.00
7	27026.93	25.51	1.878	0.30 ( 0.25)	0.83	5920.7	10360.00
8	28122.81	28.36	1.768	0.30 ( 0.25)	0.83	6694.9	10340.00
9	28592.94	29.59	1.721	0.30 ( 0.25)	0.83	7024.1	10200.00
10	28659.40	29.98	1.706	0.30 ( 0.25)	0.83	7126.4	10250.00
11	28707.67	30.33	1.697	0.30 ( 0.25)	0.83	7216.5	50700.00
12	29022.57	31.20	1.674	0.30 ( 0.25)	0.83	7554.0	10500.00
13	29890.11	33.71	1.609	0.30 ( 0.25)	0.82	8488.0	10220.00
14	30870.33	36.53	1.536	0.30 ( 0.25)	0.82	9531.0	110.00
15	33292.12	42.90	1.399	0.30 ( 0.25)	0.83	12606.9	130.00
16	35123.72	48.25	1.312	0.30 ( 0.25)	0.84	15137.6	150.00
17	38498.38	62.34	1.156	0.30 ( 0.26)	0.87	22188.1	390.00
18	40536.46	73.89	1.078	0.30 ( 0.27)	0.89	28242.2	13100.00
19	41310.67	80.75	1.032	0.30 ( 0.27)	0.89	31296.5	11801.00
20	42854.15	91.34	0.964	0.30 ( 0.27)	0.91	36717.9	11530.00
21	43768.56	95.63	0.946	0.30 ( 0.27)	0.91	39563.6	13510.00
22	45512.08	104.43	0.907	0.30 ( 0.28)	0.92	45364.9	13500.00
23	46382.01	108.90	0.888	0.30 ( 0.28)	0.93	48383.6	10800.00
24	46801.93	113.09	0.870	0.30 ( 0.28)	0.93	51328.9	11130.00
25	46266.48	122.72	0.834	0.30 ( 0.28)	0.93	56370.1	12410.00
26	45547.75	131.06	0.817	0.30 ( 0.28)	0.94	60109.2	11201.00
27	45058.16	136.07	0.807	0.30 ( 0.28)	0.94	61840.9	12201.00
28	43967.29	143.23	0.792	0.30 ( 0.28)	0.94	63698.1	12231.00
29	42601.54	151.16	0.775	0.30 ( 0.28)	0.94	65332.4	10400.00
30	41185.09	159.24	0.758	0.30 ( 0.28)	0.94	66627.5	12010.00
31	39946.51	165.33	0.746	0.30 ( 0.28)	0.94	66974.4	10210.00
32	35565.03	193.99	0.700	0.30 ( 0.28)	0.94	67712.9	10100.00

TOTAL AREA (ACRES) = 67712.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 46801.93 Tc(MIN.) = 113.088  
EFFECTIVE AREA(ACRES) = 51328.91 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
TOTAL AREA (ACRES) = 67712.9  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130408.82 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13802.00 TO NODE 13803.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 135.00 DOWNSTREAM(FEET) = 133.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 207.23 CHANNEL SLOPE = 0.0097

GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 13.55  
CHANNEL FLOW THRU SUBAREA(CFS) = 46801.93  
FLOW VELOCITY(FEET/SEC.) = 22.39 FLOW DEPTH(FEET) = 13.55  
TRAVEL TIME(MIN.) = 0.15 Tc(MIN.) = 113.24  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130616.05 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22698.10	14.81	2.640	0.30 ( 0.25)	0.82	3227.6	10520.00
2	24967.42	20.43	2.162	0.30 ( 0.25)	0.83	4456.1	10300.00
3	24975.33	20.45	2.161	0.30 ( 0.25)	0.83	4461.4	10230.00
4	25287.32	21.23	2.116	0.30 ( 0.25)	0.83	4683.7	10380.00
5	25437.31	21.60	2.094	0.30 ( 0.25)	0.83	4790.6	10400.00
6	26212.76	23.58	1.979	0.30 ( 0.25)	0.83	5342.9	10320.00
7	27026.93	25.69	1.871	0.30 ( 0.25)	0.83	5920.7	10360.00
8	28122.81	28.54	1.761	0.30 ( 0.25)	0.83	6694.9	10340.00
9	28592.94	29.77	1.714	0.30 ( 0.25)	0.83	7024.1	10200.00
10	28659.40	30.16	1.701	0.30 ( 0.25)	0.83	7126.4	10250.00
11	28707.67	30.50	1.692	0.30 ( 0.25)	0.83	7216.5	50700.00
12	29022.57	31.38	1.669	0.30 ( 0.25)	0.83	7554.0	10500.00
13	29890.11	33.89	1.604	0.30 ( 0.25)	0.82	8488.0	10220.00
14	30870.33	36.70	1.531	0.30 ( 0.25)	0.82	9531.0	110.00
15	33292.12	43.07	1.396	0.30 ( 0.25)	0.83	12606.9	130.00
16	35123.72	48.42	1.310	0.30 ( 0.25)	0.84	15137.6	150.00
17	38498.38	62.50	1.155	0.30 ( 0.26)	0.87	22188.1	390.00
18	40536.46	74.05	1.077	0.30 ( 0.27)	0.89	28242.2	13100.00
19	41310.67	80.91	1.031	0.30 ( 0.27)	0.89	31296.5	11801.00
20	42854.15	91.50	0.963	0.30 ( 0.27)	0.91	36717.9	11530.00
21	43768.56	95.79	0.945	0.30 ( 0.27)	0.91	39563.6	13510.00
22	45512.08	104.59	0.907	0.30 ( 0.28)	0.92	45364.9	13500.00
23	46382.01	109.06	0.887	0.30 ( 0.28)	0.93	48383.6	10800.00
24	46801.93	113.24	0.869	0.30 ( 0.28)	0.93	51328.9	11130.00
25	46266.48	122.88	0.834	0.30 ( 0.28)	0.93	56370.1	12410.00
26	45547.75	131.21	0.817	0.30 ( 0.28)	0.94	60109.2	11201.00
27	45058.16	136.22	0.806	0.30 ( 0.28)	0.94	61840.9	12201.00
28	43967.29	143.38	0.791	0.30 ( 0.28)	0.94	63698.1	12231.00
29	42601.54	151.32	0.775	0.30 ( 0.28)	0.94	65332.4	10400.00
30	41185.09	159.40	0.758	0.30 ( 0.28)	0.94	66627.5	12010.00
31	39946.51	165.49	0.745	0.30 ( 0.28)	0.94	66974.4	10210.00
32	35565.03	194.15	0.700	0.30 ( 0.28)	0.94	67712.9	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 46801.93 Tc(MIN.) = 113.24  
AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 51328.91

\*\*\*\*\*

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 113.24

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.869

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

RESIDENTIAL  
 "1 DWELLING/ACRE" B 48.80 0.30 0.800 56  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.800  
 SUBAREA AREA (ACRES) = 48.80 SUBAREA RUNOFF(CFS) = 27.64  
 EFFECTIVE AREA(ACRES) = 51377.71 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 67761.7 PEAK FLOW RATE(CFS) = 46801.93  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13802.00 TO NODE 13803.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 3 <<<<<<  
 =====

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 3 <<<<<<  
 =====

PEAK FLOWRATE TABLE FILE NAME: 0506106C.DNA  
 MEMORY BANK # 3 DEFINED AS FOLLOWS:  

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	63.85	17.52	0.30 ( 0.20)	0.67		36.9	10600.00
TOTAL AREA(ACRES) =							36.9

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<<  
 =====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22698.10	14.81	2.640	0.30 ( 0.25)	0.82	3276.4	10520.00
2	24967.42	20.43	2.162	0.30 ( 0.25)	0.82	4504.9	10300.00
3	24975.33	20.45	2.161	0.30 ( 0.25)	0.82	4510.2	10230.00
4	25287.32	21.23	2.116	0.30 ( 0.25)	0.82	4732.5	10380.00
5	25437.31	21.60	2.094	0.30 ( 0.25)	0.82	4839.4	10400.00
6	26212.76	23.58	1.979	0.30 ( 0.25)	0.83	5391.7	10320.00
7	27026.93	25.69	1.871	0.30 ( 0.25)	0.83	5969.5	10360.00
8	28122.81	28.54	1.761	0.30 ( 0.25)	0.83	6743.7	10340.00
9	28592.94	29.77	1.714	0.30 ( 0.25)	0.83	7072.9	10200.00
10	28659.40	30.16	1.701	0.30 ( 0.25)	0.83	7175.2	10250.00
11	28707.67	30.50	1.692	0.30 ( 0.25)	0.83	7265.3	50700.00
12	29022.57	31.38	1.669	0.30 ( 0.25)	0.83	7602.8	10500.00
13	29890.11	33.89	1.604	0.30 ( 0.25)	0.82	8536.8	10220.00
14	30870.33	36.70	1.531	0.30 ( 0.25)	0.82	9579.8	110.00
15	33292.12	43.07	1.396	0.30 ( 0.25)	0.83	12655.7	130.00
16	35123.72	48.42	1.310	0.30 ( 0.25)	0.84	15186.4	150.00
17	38498.38	62.50	1.155	0.30 ( 0.26)	0.86	22236.9	390.00
18	40536.46	74.05	1.077	0.30 ( 0.27)	0.89	28291.0	13100.00
19	41310.67	80.91	1.031	0.30 ( 0.27)	0.89	31345.3	11801.00
20	42854.15	91.50	0.963	0.30 ( 0.27)	0.91	36766.7	11530.00
21	43768.56	95.79	0.945	0.30 ( 0.27)	0.91	39612.4	13510.00

22	45512.08	104.59	0.907	0.30 ( 0.28)	0.92	45413.7	13500.00
23	46382.01	109.06	0.887	0.30 ( 0.28)	0.93	48432.4	10800.00
24	46801.93	113.24	0.869	0.30 ( 0.28)	0.93	51377.7	11130.00
25	46266.48	122.88	0.834	0.30 ( 0.28)	0.93	56418.9	12410.00
26	45547.75	131.21	0.817	0.30 ( 0.28)	0.94	60158.0	11201.00
27	45058.16	136.22	0.806	0.30 ( 0.28)	0.94	61889.7	12201.00
28	43967.29	143.38	0.791	0.30 ( 0.28)	0.94	63746.9	12231.00
29	42601.54	151.32	0.775	0.30 ( 0.28)	0.94	65381.2	10400.00
30	41185.09	159.40	0.758	0.30 ( 0.28)	0.94	66676.3	12010.00
31	39946.51	165.49	0.745	0.30 ( 0.28)	0.94	67023.2	10210.00
32	35565.03	194.15	0.700	0.30 ( 0.28)	0.94	67761.7	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130616.05 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	63.85	17.52	2.397	0.30 ( 0.20)	0.67	36.9	10600.00

LONGEST FLOWPATH FROM NODE 10600.00 TO NODE 13803.00 = 1713.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22758.05	14.81	2.640	0.30 ( 0.25)	0.82	3307.6	10520.00
2	23855.93	17.52	2.397	0.30 ( 0.25)	0.82	3905.5	10600.00
3	25024.43	20.43	2.162	0.30 ( 0.25)	0.82	4541.8	10300.00
4	25032.30	20.45	2.161	0.30 ( 0.25)	0.82	4547.1	10230.00
5	25342.99	21.23	2.116	0.30 ( 0.25)	0.82	4769.4	10380.00
6	25492.35	21.60	2.094	0.30 ( 0.25)	0.82	4876.3	10400.00
7	26264.46	23.58	1.979	0.30 ( 0.25)	0.82	5428.6	10320.00
8	27075.47	25.69	1.871	0.30 ( 0.25)	0.82	6006.4	10360.00
9	28168.17	28.54	1.761	0.30 ( 0.25)	0.82	6780.6	10340.00
10	28636.93	29.77	1.714	0.30 ( 0.25)	0.82	7109.8	10200.00
11	28703.01	30.16	1.701	0.30 ( 0.25)	0.82	7212.1	10250.00
12	28751.02	30.50	1.692	0.30 ( 0.25)	0.82	7302.2	50700.00
13	29065.26	31.38	1.669	0.30 ( 0.25)	0.82	7639.7	10500.00
14	29930.91	33.89	1.604	0.30 ( 0.25)	0.82	8573.7	10220.00
15	30909.01	36.70	1.531	0.30 ( 0.25)	0.82	9616.7	110.00
16	33326.88	43.07	1.396	0.30 ( 0.25)	0.83	12692.6	130.00
17	35155.95	48.42	1.310	0.30 ( 0.25)	0.84	15223.3	150.00
18	38526.12	62.50	1.155	0.30 ( 0.26)	0.86	22273.8	390.00
19	40561.94	74.05	1.077	0.30 ( 0.27)	0.89	28327.9	13100.00
20	41334.80	80.91	1.031	0.30 ( 0.27)	0.89	31382.2	11801.00
21	42876.32	91.50	0.963	0.30 ( 0.27)	0.91	36803.6	11530.00
22	43790.19	95.79	0.945	0.30 ( 0.27)	0.91	39649.3	13510.00
23	45532.60	104.59	0.907	0.30 ( 0.28)	0.92	45450.6	13500.00
24	46401.96	109.06	0.887	0.30 ( 0.28)	0.93	48469.3	10800.00
25	46821.36	113.24	0.869	0.30 ( 0.28)	0.93	51414.6	11130.00
26	46284.88	122.88	0.834	0.30 ( 0.28)	0.93	56455.8	12410.00
27	45565.64	131.21	0.817	0.30 ( 0.28)	0.94	60194.9	11201.00
28	45075.76	136.22	0.806	0.30 ( 0.28)	0.94	61926.6	12201.00
29	43984.45	143.38	0.791	0.30 ( 0.28)	0.94	63783.8	12231.00
30	42618.22	151.32	0.775	0.30 ( 0.28)	0.94	65418.1	10400.00
31	41201.28	159.40	0.758	0.30 ( 0.28)	0.94	66713.2	12010.00
32	39962.34	165.49	0.745	0.30 ( 0.28)	0.94	67060.1	10210.00
33	35579.54	194.15	0.700	0.30 ( 0.28)	0.94	67798.6	10100.00

TOTAL AREA(ACRES) = 67798.6

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 46821.36 Tc(MIN.) = 113.242  
 EFFECTIVE AREA(ACRES) = 51414.61 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 67798.6  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130616.05 FEET.

=====  
 END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 67798.6 TC(MIN.) = 113.24  
 EFFECTIVE AREA(ACRES) = 51414.61 AREA-AVERAGED Fm(INCH/HR)= 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.929  
 PEAK FLOW RATE(CFS) = 46821.36

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22758.05	14.81	2.640	0.30( 0.25)	0.82	3307.6	10520.00
2	23855.93	17.52	2.397	0.30( 0.25)	0.82	3905.5	10600.00
3	25024.43	20.43	2.162	0.30( 0.25)	0.82	4541.8	10300.00
4	25032.30	20.45	2.161	0.30( 0.25)	0.82	4547.1	10230.00
5	25342.99	21.23	2.116	0.30( 0.25)	0.82	4769.4	10380.00
6	25492.35	21.60	2.094	0.30( 0.25)	0.82	4876.3	10400.00
7	26264.46	23.58	1.979	0.30( 0.25)	0.82	5428.6	10320.00
8	27075.47	25.69	1.871	0.30( 0.25)	0.82	6006.4	10360.00
9	28168.17	28.54	1.761	0.30( 0.25)	0.82	6780.6	10340.00
10	28636.93	29.77	1.714	0.30( 0.25)	0.82	7109.8	10200.00
11	28703.01	30.16	1.701	0.30( 0.25)	0.82	7212.1	10250.00
12	28751.02	30.50	1.692	0.30( 0.25)	0.82	7302.2	50700.00
13	29065.26	31.38	1.669	0.30( 0.25)	0.82	7639.7	10500.00
14	29930.91	33.89	1.604	0.30( 0.25)	0.82	8573.7	10220.00
15	30909.01	36.70	1.531	0.30( 0.25)	0.82	9616.7	110.00
16	33326.88	43.07	1.396	0.30( 0.25)	0.83	12692.6	130.00
17	35155.95	48.42	1.310	0.30( 0.25)	0.84	15223.3	150.00
18	38526.12	62.50	1.155	0.30( 0.26)	0.86	22273.8	390.00
19	40561.94	74.05	1.077	0.30( 0.27)	0.89	28327.9	13100.00
20	41334.80	80.91	1.031	0.30( 0.27)	0.89	31382.2	11801.00
21	42876.32	91.50	0.963	0.30( 0.27)	0.91	36803.6	11530.00
22	43790.19	95.79	0.945	0.30( 0.27)	0.91	39649.3	13510.00
23	45532.60	104.59	0.907	0.30( 0.28)	0.92	45450.6	13500.00
24	46401.96	109.06	0.887	0.30( 0.28)	0.93	48469.3	10800.00
25	46821.36	113.24	0.869	0.30( 0.28)	0.93	51414.6	11130.00
26	46284.88	122.88	0.834	0.30( 0.28)	0.93	56455.8	12410.00
27	45565.64	131.21	0.817	0.30( 0.28)	0.94	60194.9	11201.00
28	45075.76	136.22	0.806	0.30( 0.28)	0.94	61926.6	12201.00
29	43984.45	143.38	0.791	0.30( 0.28)	0.94	63783.8	12231.00
30	42618.22	151.32	0.775	0.30( 0.28)	0.94	65418.1	10400.00
31	41201.28	159.40	0.758	0.30( 0.28)	0.94	66713.2	12010.00
32	39962.34	165.49	0.745	0.30( 0.28)	0.94	67060.1	10210.00
33	35579.54	194.15	0.700	0.30( 0.28)	0.94	67798.6	10100.00

=====  
 END OF RATIONAL METHOD ANALYSIS

\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S38- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 50-YR RM EV APRIL 2019 CCHIU \*  
\*\*\*\*\*

FILE NAME: RI50EV38.DAT  
TIME/DATE OF STUDY: 09:17 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 50.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.225
- 2) 10.00; 3.382
- 3) 15.00; 2.607
- 4) 20.00; 2.184
- 5) 25.00; 1.895
- 6) 30.00; 1.703
- 7) 40.00; 1.444
- 8) 50.00; 1.282
- 9) 60.00; 1.170
- 10) 90.00; 0.968
- 11) 120.00; 0.838
- 12) 180.00; 0.713
- 13) 360.00; 0.522
- 14) 1200.00; 0.227

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI50EV37.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23855.93	17.52	0.30 ( 0.25)	0.82	3905.5	10600.00
2	30909.01	36.70	0.30 ( 0.25)	0.82	9616.7	110.00
3	33326.88	43.07	0.30 ( 0.25)	0.83	12692.6	130.00
4	35155.95	48.42	0.30 ( 0.25)	0.84	15223.3	150.00
5	38526.12	62.50	0.30 ( 0.26)	0.86	22273.8	390.00
6	40561.94	74.05	0.30 ( 0.27)	0.89	28327.9	13100.00
7	41334.80	80.91	0.30 ( 0.27)	0.89	31382.2	11801.00
8	42876.32	91.50	0.30 ( 0.27)	0.91	36803.6	11530.00
9	43790.19	95.79	0.30 ( 0.27)	0.91	39649.3	13510.00
10	45532.60	104.59	0.30 ( 0.28)	0.92	45450.6	13500.00
11	46401.96	109.06	0.30 ( 0.28)	0.93	48469.3	10800.00
12	46821.36	113.24	0.30 ( 0.28)	0.93	51414.6	11130.00
13	46284.88	122.88	0.30 ( 0.28)	0.93	56455.8	12410.00
14	45565.64	131.21	0.30 ( 0.28)	0.94	60194.9	11201.00
15	45075.76	136.22	0.30 ( 0.28)	0.94	61926.6	12201.00
16	43984.45	143.38	0.30 ( 0.28)	0.94	63783.8	12231.00
17	42618.22	151.32	0.30 ( 0.28)	0.94	65418.1	10400.00
18	41201.28	159.40	0.30 ( 0.28)	0.94	66713.2	12010.00
19	39962.34	165.49	0.30 ( 0.28)	0.94	67060.1	10210.00
20	35579.54	194.15	0.30 ( 0.28)	0.94	67798.6	10100.00
TOTAL AREA (ACRES) =						67798.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23855.93	17.52	0.30 ( 0.25)	0.82	3905.5	10600.00
2	30909.01	36.70	0.30 ( 0.25)	0.82	9616.7	110.00
3	33326.88	43.07	0.30 ( 0.25)	0.83	12692.6	130.00
4	35155.95	48.42	0.30 ( 0.25)	0.84	15223.3	150.00
5	38526.12	62.50	0.30 ( 0.26)	0.86	22273.8	390.00
6	40561.94	74.05	0.30 ( 0.27)	0.89	28327.9	13100.00
7	41334.80	80.91	0.30 ( 0.27)	0.89	31382.2	11801.00
8	42876.32	91.50	0.30 ( 0.27)	0.91	36803.6	11530.00
9	43790.19	95.79	0.30 ( 0.27)	0.91	39649.3	13510.00
10	45532.60	104.59	0.30 ( 0.28)	0.92	45450.6	13500.00
11	46401.96	109.06	0.30 ( 0.28)	0.93	48469.3	10800.00
12	46821.36	113.24	0.30 ( 0.28)	0.93	51414.6	11130.00
13	46284.88	122.88	0.30 ( 0.28)	0.93	56455.8	12410.00

14	45565.64	131.21	0.30	( 0.28)	0.94	60194.9	11201.00
15	45075.76	136.22	0.30	( 0.28)	0.94	61926.6	12201.00
16	43984.45	143.38	0.30	( 0.28)	0.94	63783.8	12231.00
17	42618.22	151.32	0.30	( 0.28)	0.94	65418.1	10400.00
18	41201.28	159.40	0.30	( 0.28)	0.94	66713.2	12010.00
19	39962.34	165.49	0.30	( 0.28)	0.94	67060.1	10210.00
20	35579.54	194.15	0.30	( 0.28)	0.94	67798.6	10100.00
TOTAL AREA (ACRES) =							67798.6

\*\*\*\*\*

FLOW PROCESS FROM NODE 13803.00 TO NODE 13820.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 140.00 DOWNSTREAM(FEET) = 137.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 926.91 CHANNEL SLOPE = 0.0032  
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT(FEET) = 17.99

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.863

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	31.44	0.30	0.983	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.983

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 46829.40

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 15.14

AVERAGE FLOW DEPTH(FEET) = 17.99 TRAVEL TIME(MIN.) = 1.02

Tc(MIN.) = 114.26

SUBAREA AREA(ACRES) = 31.44 SUBAREA RUNOFF(CFS) = 16.07

EFFECTIVE AREA(ACRES) = 51446.05 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA(ACRES) = 67830.0 PEAK FLOW RATE(CFS) = 46821.36

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT(FEET) = 17.99

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 17.99 FLOW VELOCITY(FEET/SEC.) = 15.14

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13820.00 = 131542.95 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23855.93	18.76	2.289	0.30( 0.25)	0.82	3937.0	10600.00
2	30909.01	37.85	1.500	0.30( 0.25)	0.82	9648.1	110.00
3	33326.88	44.19	1.376	0.30( 0.25)	0.83	12724.1	130.00
4	35155.95	49.53	1.290	0.30( 0.25)	0.84	15254.7	150.00
5	38526.12	63.58	1.146	0.30( 0.26)	0.86	22305.3	390.00
6	40561.94	75.12	1.068	0.30( 0.27)	0.89	28359.3	13100.00
7	41334.80	81.97	1.022	0.30( 0.27)	0.89	31413.7	11801.00
8	42876.32	92.55	0.957	0.30( 0.27)	0.91	36835.0	11530.00
9	43790.19	96.83	0.938	0.30( 0.27)	0.91	39680.7	13510.00
10	45532.60	105.61	0.900	0.30( 0.28)	0.92	45482.0	13500.00
11	46401.96	110.08	0.881	0.30( 0.28)	0.93	48500.7	10800.00

12	46821.36	114.26	0.863	0.30( 0.28)	0.93	51446.1	11130.00
13	46284.88	123.90	0.830	0.30( 0.28)	0.93	56487.2	12410.00
14	45565.64	132.24	0.812	0.30( 0.28)	0.94	60226.4	11201.00
15	45075.76	137.26	0.802	0.30( 0.28)	0.94	61958.1	12201.00
16	43984.45	144.42	0.787	0.30( 0.28)	0.94	63815.2	12231.00
17	42618.22	152.37	0.771	0.30( 0.28)	0.94	65449.5	10400.00
18	41201.28	160.45	0.754	0.30( 0.28)	0.94	66744.6	12010.00
19	39962.34	166.56	0.741	0.30( 0.28)	0.94	67091.6	10210.00
20	35579.54	195.26	0.697	0.30( 0.28)	0.94	67830.0	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 46821.36 Tc(MIN.) = 114.26

AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 51446.05

\*\*\*\*\*

FLOW PROCESS FROM NODE 13803.00 TO NODE 13820.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

TOTAL NUMBER OF STREAMS = 2

CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:

TIME OF CONCENTRATION(MIN.) = 114.26

RAINFALL INTENSITY(INCH/HR) = 0.86

AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.93

EFFECTIVE STREAM AREA(ACRES) = 51446.05

TOTAL STREAM AREA(ACRES) = 67830.01

PEAK FLOW RATE(CFS) AT CONFLUENCE = 46821.36

\*\*\*\*\*

FLOW PROCESS FROM NODE 13810.00 TO NODE 13811.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<

>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH(FEET) = 648.54

ELEVATION DATA: UPSTREAM(FEET) = 756.46 DOWNSTREAM(FEET) = 586.02

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20

SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 12.293

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 3.027

SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	-	5.58	0.30	1.000	56	12.29

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA RUNOFF(CFS) = 13.69

TOTAL AREA(ACRES) = 5.58 PEAK FLOW RATE(CFS) = 13.69

\*\*\*\*\*

FLOW PROCESS FROM NODE 13811.00 TO NODE 13811.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

\*\*\*\*\*

ELEVATION DATA: UPSTREAM(FEET) = 586.02 DOWNSTREAM(FEET) = 437.69  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 696.28 CHANNEL SLOPE = 0.2130  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.46  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 2.739  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 14.79 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 29.95  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.26  
 AVERAGE FLOW DEPTH(FEET) = 0.44 TRAVEL TIME(MIN.) = 1.85  
 Tc(MIN.) = 14.15  
 SUBAREA AREA(ACRES) = 14.79 SUBAREA RUNOFF(CFS) = 32.47  
 EFFECTIVE AREA(ACRES) = 20.37 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 20.4 PEAK FLOW RATE(CFS) = 44.72  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.56  
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 0.56 FLOW VELOCITY(FEET/SEC.) = 7.18  
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13811.50 = 1344.82 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13811.50 TO NODE 13812.00 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 437.69 DOWNSTREAM(FEET) = 402.36  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 681.04 CHANNEL SLOPE = 0.0519  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.05  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 2.490  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 18.41 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 62.88  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.08  
 AVERAGE FLOW DEPTH(FEET) = 1.03 TRAVEL TIME(MIN.) = 2.23  
 Tc(MIN.) = 16.38  
 SUBAREA AREA(ACRES) = 18.41 SUBAREA RUNOFF(CFS) = 36.29  
 EFFECTIVE AREA(ACRES) = 38.78 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 38.8 PEAK FLOW RATE(CFS) = 76.44  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.15

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.15 FLOW VELOCITY(FEET/SEC.) = 5.41  
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13812.00 = 2025.86 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13812.00 TO NODE 13813.00 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 402.36 DOWNSTREAM(FEET) = 259.72  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1282.56 CHANNEL SLOPE = 0.1112  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.10  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 2.254  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 27.87 0.30 0.858 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.858  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 101.51  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.66  
 AVERAGE FLOW DEPTH(FEET) = 1.09 TRAVEL TIME(MIN.) = 2.79  
 Tc(MIN.) = 19.17  
 SUBAREA AREA(ACRES) = 27.87 SUBAREA RUNOFF(CFS) = 50.08  
 EFFECTIVE AREA(ACRES) = 66.65 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94  
 TOTAL AREA(ACRES) = 66.7 PEAK FLOW RATE(CFS) = 118.29  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.19

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.19 FLOW VELOCITY(FEET/SEC.) = 8.05  
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13813.00 = 3308.42 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 31

-----  
 >>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 259.72 DOWNSTREAM(FEET) = 137.00  
 FLOW LENGTH(FEET) = 2412.88 MANNING'S N = 0.013  
 DEPTH OF FLOW IN 36.0 INCH PIPE IS 25.0 INCHES  
 PIPE-FLOW VELOCITY(FEET/SEC.) = 22.57  
 ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1  
 PIPE-FLOW(CFS) = 118.29  
 PIPE TRAVEL TIME(MIN.) = 1.78 Tc(MIN.) = 20.95  
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13820.00 = 5721.30 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 81

-----  
 >>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 =====

MAINLINE Tc(MIN.) = 20.95  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.129  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 83.64 0.30 0.570 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.570  
 SUBAREA AREA(ACRES) = 83.64 SUBAREA RUNOFF(CFS) = 147.39  
 EFFECTIVE AREA(ACRES) = 150.29 AREA-AVERAGED Fm(INCH/HR) = 0.22  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.73  
 TOTAL AREA(ACRES) = 150.3 PEAK FLOW RATE(CFS) = 258.17

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====  
 TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
 TIME OF CONCENTRATION(MIN.) = 20.95  
 RAINFALL INTENSITY(INCH/HR) = 2.13  
 AREA-AVERAGED Fm(INCH/HR) = 0.22  
 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.73  
 EFFECTIVE STREAM AREA(ACRES) = 150.29  
 TOTAL STREAM AREA(ACRES) = 150.29  
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 258.17

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23855.93	18.76	2.289	0.30( 0.25)	0.82	3937.0	10600.00
1	30909.01	37.85	1.500	0.30( 0.25)	0.82	9648.1	110.00
1	33326.88	44.19	1.376	0.30( 0.25)	0.83	12724.1	130.00
1	35155.95	49.53	1.290	0.30( 0.25)	0.84	15254.7	150.00
1	38526.12	63.58	1.146	0.30( 0.26)	0.86	22305.3	390.00
1	40561.94	75.12	1.068	0.30( 0.27)	0.89	28359.3	13100.00
1	41334.80	81.97	1.022	0.30( 0.27)	0.89	31413.7	11801.00
1	42876.32	92.55	0.957	0.30( 0.27)	0.91	36835.0	11530.00
1	43790.19	96.83	0.938	0.30( 0.27)	0.91	39680.7	13510.00
1	45532.60	105.61	0.900	0.30( 0.28)	0.92	45482.0	13500.00
1	46401.96	110.08	0.881	0.30( 0.28)	0.93	48500.7	10800.00
1	46821.36	114.26	0.863	0.30( 0.28)	0.93	51446.1	11130.00
1	46284.88	123.90	0.830	0.30( 0.28)	0.93	56487.2	12410.00
1	45565.64	132.24	0.812	0.30( 0.28)	0.94	60226.4	11201.00
1	45075.76	137.26	0.802	0.30( 0.28)	0.94	61958.1	12201.00
1	43984.45	144.42	0.787	0.30( 0.28)	0.94	63815.2	12231.00
1	42618.22	152.37	0.771	0.30( 0.28)	0.94	65449.5	10400.00
1	41201.28	160.45	0.754	0.30( 0.28)	0.94	66744.6	12010.00
1	39962.34	166.56	0.741	0.30( 0.28)	0.94	67091.6	10210.00
1	35579.54	195.26	0.697	0.30( 0.28)	0.94	67830.0	10100.00
2	258.17	20.95	2.129	0.30( 0.22)	0.73	150.3	13810.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24106.43	18.76	2.289	0.30( 0.25)	0.82	4071.5	10600.00
2	24925.77	20.95	2.129	0.30( 0.25)	0.82	4744.5	13810.00
3	31082.08	37.85	1.500	0.30( 0.25)	0.82	9798.4	110.00
4	33483.22	44.19	1.376	0.30( 0.25)	0.83	12874.3	130.00
5	35300.60	49.53	1.290	0.30( 0.25)	0.84	15405.0	150.00
6	38651.32	63.58	1.146	0.30( 0.26)	0.86	22455.6	390.00
7	40676.63	75.12	1.068	0.30( 0.27)	0.88	28509.6	13100.00
8	41443.26	81.97	1.022	0.30( 0.27)	0.89	31564.0	11801.00
9	42975.97	92.55	0.957	0.30( 0.27)	0.90	36985.3	11530.00
10	43887.33	96.83	0.938	0.30( 0.27)	0.91	39831.0	13510.00
11	45624.59	105.61	0.900	0.30( 0.28)	0.92	45632.3	13500.00
12	46491.34	110.08	0.881	0.30( 0.28)	0.92	48651.0	10800.00
13	46908.28	114.26	0.863	0.30( 0.28)	0.93	51596.3	11130.00
14	46367.34	123.90	0.830	0.30( 0.28)	0.93	56637.5	12410.00
15	45645.75	132.24	0.812	0.30( 0.28)	0.94	60376.7	11201.00
16	45154.45	137.26	0.802	0.30( 0.28)	0.94	62108.4	12201.00
17	44061.12	144.42	0.787	0.30( 0.28)	0.94	63965.5	12231.00
18	42692.65	152.37	0.771	0.30( 0.28)	0.94	65599.8	10400.00
19	41273.43	160.45	0.754	0.30( 0.28)	0.94	66894.9	12010.00
20	40032.77	166.56	0.741	0.30( 0.28)	0.94	67241.9	10210.00
21	35644.00	195.26	0.697	0.30( 0.28)	0.94	67980.3	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 46908.28 Tc(MIN.) = 114.26  
 EFFECTIVE AREA(ACRES) = 51596.34 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 67980.3  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13820.00 = 131542.95 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13820.00 TO NODE 13840.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====  
 ELEVATION DATA: UPSTREAM(FEET) = 137.00 DOWNSTREAM(FEET) = 133.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1261.34 CHANNEL SLOPE = 0.0032  
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 18.10  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.857  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 31.60 0.30 0.683 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.683  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 46917.55  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 15.04  
 AVERAGE FLOW DEPTH(FEET) = 18.10 TRAVEL TIME(MIN.) = 1.40  
 Tc(MIN.) = 115.66  
 SUBAREA AREA(ACRES) = 31.60 SUBAREA RUNOFF(CFS) = 18.54  
 EFFECTIVE AREA(ACRES) = 51627.94 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 68011.9 PEAK FLOW RATE(CFS) = 46908.28

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 18.09

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 18.09 FLOW VELOCITY (FEET/SEC.) = 15.04  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13840.00 = 132804.30 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24106.43	20.44	2.158	0.30 ( 0.25)	0.82	4103.1	10600.00
2	24925.77	22.63	2.032	0.30 ( 0.25)	0.82	4776.1	13810.00
3	31082.08	39.42	1.459	0.30 ( 0.25)	0.82	9830.0	110.00
4	33483.22	45.73	1.351	0.30 ( 0.25)	0.83	12905.9	130.00
5	35300.60	51.04	1.270	0.30 ( 0.25)	0.84	15436.6	150.00
6	38651.32	65.05	1.136	0.30 ( 0.26)	0.86	22487.2	390.00
7	40676.63	76.57	1.058	0.30 ( 0.27)	0.88	28541.2	13100.00
8	41443.26	83.42	1.012	0.30 ( 0.27)	0.89	31595.6	11801.00
9	42975.97	93.98	0.951	0.30 ( 0.27)	0.90	37016.9	11530.00
10	43887.33	98.25	0.932	0.30 ( 0.27)	0.91	39862.6	13510.00
11	45624.59	107.02	0.894	0.30 ( 0.28)	0.92	45663.9	13500.00
12	46491.34	111.48	0.875	0.30 ( 0.28)	0.92	48682.6	10800.00
13	46908.28	115.66	0.857	0.30 ( 0.28)	0.93	51627.9	11130.00
14	46367.34	125.30	0.827	0.30 ( 0.28)	0.93	56669.1	12410.00
15	45645.75	133.65	0.810	0.30 ( 0.28)	0.94	60408.3	11201.00
16	45154.45	138.67	0.799	0.30 ( 0.28)	0.94	62140.0	12201.00
17	44061.12	145.84	0.784	0.30 ( 0.28)	0.94	63997.1	12231.00
18	42692.65	153.80	0.768	0.30 ( 0.28)	0.94	65631.4	10400.00
19	41273.43	161.90	0.751	0.30 ( 0.28)	0.94	66926.5	12010.00
20	40032.77	168.02	0.738	0.30 ( 0.28)	0.94	67273.5	10210.00
21	35644.00	196.77	0.695	0.30 ( 0.28)	0.94	68011.9	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 46908.28 Tc (MIN.) = 115.66  
 AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA (ACRES) = 51627.94

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13820.00 TO NODE 13840.00 IS CODE = 1  
 -----

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

-----  
 TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
 TIME OF CONCENTRATION (MIN.) = 115.66  
 RAINFALL INTENSITY (INCH/HR) = 0.86  
 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93  
 EFFECTIVE STREAM AREA (ACRES) = 51627.94  
 TOTAL STREAM AREA (ACRES) = 68011.90  
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 46908.28

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13830.00 TO NODE 13831.00 IS CODE = 21  
 -----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<

>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH (FEET) = 744.71  
 ELEVATION DATA: UPSTREAM (FEET) = 1100.95 DOWNSTREAM (FEET) = 959.21

Tc = K \* [(LENGTH\*\* 3.00) / (ELEVATION CHANGE)]\*\*0.20  
 SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 13.858  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 2.784

SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------	--------------

NATURAL FAIR COVER						
"CHAPARRAL, BROADLEAF"	-	5.06	0.30	1.000	56	13.86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA RUNOFF (CFS) = 11.31

TOTAL AREA (ACRES) = 5.06 PEAK FLOW RATE (CFS) = 11.31

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13831.00 TO NODE 13832.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 959.21 DOWNSTREAM (FEET) = 832.83  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1076.71 CHANNEL SLOPE = 0.1174

GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT (FEET) = 0.69

\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 2.443

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

USER-DEFINED	-	32.57	0.30	1.000	-
--------------	---	-------	------	-------	---

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 42.87

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.82

AVERAGE FLOW DEPTH (FEET) = 0.65 TRAVEL TIME (MIN.) = 3.08

Tc (MIN.) = 16.94

SUBAREA AREA (ACRES) = 32.57 SUBAREA RUNOFF (CFS) = 62.82

EFFECTIVE AREA (ACRES) = 37.63 AREA-AVERAGED Fm (INCH/HR) = 0.30

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.000

TOTAL AREA (ACRES) = 37.6 PEAK FLOW RATE (CFS) = 72.58

GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT (FEET) = 0.88

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 0.88 FLOW VELOCITY (FEET/SEC.) = 6.99

LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13832.00 = 1821.42 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13832.00 TO NODE 13833.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====



ELEVATION DATA: UPSTREAM(FEET) = 832.83 DOWNSTREAM(FEET) = 572.49  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1883.58 CHANNEL SLOPE = 0.1382  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.03  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 2.139  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 32.23 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 99.30  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.18  
 AVERAGE FLOW DEPTH(FEET) = 1.01 TRAVEL TIME(MIN.) = 3.84  
 Tc(MIN.) = 20.78  
 SUBAREA AREA(ACRES) = 32.23 SUBAREA RUNOFF(CFS) = 53.35  
 EFFECTIVE AREA(ACRES) = 69.86 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 69.9 PEAK FLOW RATE(CFS) = 115.63  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.10  
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.10 FLOW VELOCITY(FEET/SEC.) = 8.59  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13833.00 = 3705.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13833.00 TO NODE 13834.00 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 572.49 DOWNSTREAM(FEET) = 471.65  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 943.78 CHANNEL SLOPE = 0.1068  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.32  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 2.030  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 27.51 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 137.05  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.31  
 AVERAGE FLOW DEPTH(FEET) = 1.31 TRAVEL TIME(MIN.) = 1.89  
 Tc(MIN.) = 22.67  
 SUBAREA AREA(ACRES) = 27.51 SUBAREA RUNOFF(CFS) = 42.83  
 EFFECTIVE AREA(ACRES) = 97.37 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 97.4 PEAK FLOW RATE(CFS) = 151.58  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.38

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.38 FLOW VELOCITY(FEET/SEC.) = 8.58  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13834.00 = 4648.78 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13834.00 TO NODE 13835.00 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 471.65 DOWNSTREAM(FEET) = 347.06  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1647.45 CHANNEL SLOPE = 0.0756  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.90  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.861  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 94.21 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 217.79  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.51  
 AVERAGE FLOW DEPTH(FEET) = 1.86 TRAVEL TIME(MIN.) = 3.23  
 Tc(MIN.) = 25.90  
 SUBAREA AREA(ACRES) = 94.21 SUBAREA RUNOFF(CFS) = 132.32  
 EFFECTIVE AREA(ACRES) = 191.58 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 191.6 PEAK FLOW RATE(CFS) = 269.08  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 2.09  
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 2.09 FLOW VELOCITY(FEET/SEC.) = 9.06  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13835.00 = 6296.23 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13835.00 TO NODE 13836.00 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 347.06 DOWNSTREAM(FEET) = 269.29  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1696.71 CHANNEL SLOPE = 0.0458  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 3.09  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.734  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 233.25 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 419.75  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.61

AVERAGE FLOW DEPTH(FEET) = 3.03 TRAVEL TIME(MIN.) = 3.28  
 Tc(MIN.) = 29.18  
 SUBAREA AREA(ACRES) = 233.25 SUBAREA RUNOFF(CFS) = 301.14  
 EFFECTIVE AREA(ACRES) = 424.83 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 424.8 PEAK FLOW RATE(CFS) = 548.48  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 3.48

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 3.48 FLOW VELOCITY(FEET/SEC.) = 9.28  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13836.00 = 7992.94 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13836.00 TO NODE 13837.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 269.29 DOWNSTREAM(FEET) = 191.87  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2529.21 CHANNEL SLOPE = 0.0306  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 4.16  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.593

SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 134.70 0.30 0.880 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.880  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 629.05  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.31  
 AVERAGE FLOW DEPTH(FEET) = 4.14 TRAVEL TIME(MIN.) = 5.07  
 Tc(MIN.) = 34.25  
 SUBAREA AREA(ACRES) = 134.70 SUBAREA RUNOFF(CFS) = 161.11  
 EFFECTIVE AREA(ACRES) = 559.53 AREA-AVERAGED Fm(INCH/HR) = 0.29  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97  
 TOTAL AREA(ACRES) = 559.5 PEAK FLOW RATE(CFS) = 655.45  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 4.23

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 4.23 FLOW VELOCITY(FEET/SEC.) = 8.40  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13837.00 = 10522.15 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 31  
 -----

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 191.87 DOWNSTREAM(FEET) = 133.00  
 FLOW LENGTH(FEET) = 1151.02 MANNING'S N = 0.013  
 DEPTH OF FLOW IN 66.0 INCH PIPE IS 49.4 INCHES  
 PIPE-FLOW VELOCITY(FEET/SEC.) = 34.36

ESTIMATED PIPE DIAMETER(INCH) = 66.00 NUMBER OF PIPES = 1  
 PIPE-FLOW(CFS) = 655.45  
 PIPE TRAVEL TIME(MIN.) = 0.56 Tc(MIN.) = 34.81  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13840.00 = 11673.17 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 34.81  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.578  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 5.97 0.30 0.622 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.622  
 SUBAREA AREA(ACRES) = 5.97 SUBAREA RUNOFF(CFS) = 7.48  
 EFFECTIVE AREA(ACRES) = 565.50 AREA-AVERAGED Fm(INCH/HR) = 0.29  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97  
 TOTAL AREA(ACRES) = 565.5 PEAK FLOW RATE(CFS) = 655.65

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 1  
 -----

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
 TIME OF CONCENTRATION(MIN.) = 34.81  
 RAINFALL INTENSITY(INCH/HR) = 1.58  
 AREA-AVERAGED Fm(INCH/HR) = 0.29  
 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.97  
 EFFECTIVE STREAM AREA(ACRES) = 565.50  
 TOTAL STREAM AREA(ACRES) = 565.50  
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 655.65

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24106.43	20.44	2.158	0.30( 0.25)	0.82	4103.1	10600.00
1	24925.77	22.63	2.032	0.30( 0.25)	0.82	4776.1	13810.00
1	31082.08	39.42	1.459	0.30( 0.25)	0.82	9830.0	110.00
1	33483.22	45.73	1.351	0.30( 0.25)	0.83	12905.9	130.00
1	35300.60	51.04	1.270	0.30( 0.25)	0.84	15436.6	150.00
1	38651.32	65.05	1.136	0.30( 0.26)	0.86	22487.2	390.00
1	40676.63	76.57	1.058	0.30( 0.27)	0.88	28541.2	13100.00
1	41443.26	83.42	1.012	0.30( 0.27)	0.89	31595.6	11801.00
1	42975.97	93.98	0.951	0.30( 0.27)	0.90	37016.9	11530.00
1	43887.33	98.25	0.932	0.30( 0.27)	0.91	39862.6	13510.00
1	45624.59	107.02	0.894	0.30( 0.28)	0.92	45663.9	13500.00
1	46491.34	111.48	0.875	0.30( 0.28)	0.92	48682.6	10800.00
1	46908.28	115.66	0.857	0.30( 0.28)	0.93	51627.9	11130.00
1	46367.34	125.30	0.827	0.30( 0.28)	0.93	56669.1	12410.00
1	45645.75	133.65	0.810	0.30( 0.28)	0.94	60408.3	11201.00

1	45154.45	138.67	0.799	0.30	( 0.28)	0.94	62140.0	12201.00
1	44061.12	145.84	0.784	0.30	( 0.28)	0.94	63997.1	12231.00
1	42692.65	153.80	0.768	0.30	( 0.28)	0.94	65631.4	10400.00
1	41273.43	161.90	0.751	0.30	( 0.28)	0.94	66926.5	12010.00
1	40032.77	168.02	0.738	0.30	( 0.28)	0.94	67273.5	10210.00
1	35644.00	196.77	0.695	0.30	( 0.28)	0.94	68011.9	10100.00
2	655.65	34.81	1.578	0.30	( 0.29)	0.97	565.5	13830.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24664.84	20.44	2.158	0.30( 0.25)	0.83	4435.2	10600.00
2	25502.04	22.63	2.032	0.30( 0.25)	0.83	5143.7	13810.00
3	30048.84	34.81	1.578	0.30( 0.25)	0.83	9009.1	13830.00
4	31677.01	39.42	1.459	0.30( 0.25)	0.83	10395.5	110.00
5	34023.26	45.73	1.351	0.30( 0.25)	0.83	13471.4	130.00
6	35799.46	51.04	1.270	0.30( 0.25)	0.84	16002.1	150.00
7	39081.79	65.05	1.136	0.30( 0.26)	0.87	23052.7	390.00
8	41067.64	76.57	1.058	0.30( 0.27)	0.89	29106.7	13100.00
9	41810.80	83.42	1.012	0.30( 0.27)	0.89	32161.1	11801.00
10	43312.18	93.98	0.951	0.30( 0.27)	0.91	37582.4	11530.00
11	44214.11	98.25	0.932	0.30( 0.27)	0.91	40428.1	13510.00
12	45932.03	107.02	0.894	0.30( 0.28)	0.92	46229.4	13500.00
13	46788.94	111.48	0.875	0.30( 0.28)	0.92	49248.1	10800.00
14	47196.68	115.66	0.857	0.30( 0.28)	0.93	52193.4	11130.00
15	46640.54	125.30	0.827	0.30( 0.28)	0.93	57234.6	12410.00
16	45910.10	133.65	0.810	0.30( 0.28)	0.94	60973.8	11201.00
17	45413.48	138.67	0.799	0.30( 0.28)	0.94	62705.5	12201.00
18	44312.55	145.84	0.784	0.30( 0.28)	0.94	64562.6	12231.00
19	42935.63	153.80	0.768	0.30( 0.28)	0.94	66196.9	10400.00
20	41507.83	161.90	0.751	0.30( 0.28)	0.94	67492.0	12010.00
21	40260.68	168.02	0.738	0.30( 0.28)	0.94	67839.0	10210.00
22	35850.15	196.77	0.695	0.30( 0.28)	0.94	68577.4	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 47196.68 Tc(MIN.) = 115.66  
EFFECTIVE AREA(ACRES) = 52193.44 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA(ACRES) = 68577.4  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13840.00 = 132804.30 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13840.00 TO NODE 13860.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 133.00 DOWNSTREAM(FEET) = 130.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 654.44 CHANNEL SLOPE = 0.0046  
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 16.52  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.854  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS

LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 6.61 0.30 0.975 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.975  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 47198.35  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 17.20  
AVERAGE FLOW DEPTH(FEET) = 16.52 TRAVEL TIME(MIN.) = 0.63  
Tc(MIN.) = 116.29  
SUBAREA AREA(ACRES) = 6.61 SUBAREA RUNOFF(CFS) = 3.34  
EFFECTIVE AREA(ACRES) = 52200.05 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA(ACRES) = 68584.0 PEAK FLOW RATE(CFS) = 47196.68  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 16.52

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 16.52 FLOW VELOCITY(FEET/SEC.) = 17.20  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13860.00 = 133458.73 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24664.84	21.21	2.114	0.30( 0.25)	0.83	4441.8	10600.00
2	25502.04	23.38	1.989	0.30( 0.25)	0.83	5150.3	13810.00
3	30048.84	35.53	1.560	0.30( 0.25)	0.83	9015.7	13830.00
4	31677.01	40.13	1.442	0.30( 0.25)	0.83	10402.1	110.00
5	34023.26	46.42	1.340	0.30( 0.25)	0.84	13478.1	130.00
6	35799.46	51.73	1.263	0.30( 0.25)	0.84	16008.7	150.00
7	39081.79	65.72	1.131	0.30( 0.26)	0.87	23059.3	390.00
8	41067.64	77.23	1.054	0.30( 0.27)	0.89	29113.3	13100.00
9	41810.80	84.07	1.008	0.30( 0.27)	0.89	32167.7	11801.00
10	43312.18	94.63	0.948	0.30( 0.27)	0.91	37589.0	11530.00
11	44214.11	98.90	0.929	0.30( 0.27)	0.91	40434.7	13510.00
12	45932.03	107.66	0.891	0.30( 0.28)	0.92	46236.0	13500.00
13	46788.94	112.12	0.872	0.30( 0.28)	0.92	49254.7	10800.00
14	47196.68	116.29	0.854	0.30( 0.28)	0.93	52200.1	11130.00
15	46640.54	125.94	0.826	0.30( 0.28)	0.93	57241.2	12410.00
16	45910.10	134.29	0.808	0.30( 0.28)	0.94	60980.4	11201.00
17	45413.48	139.31	0.798	0.30( 0.28)	0.94	62712.1	12201.00
18	44312.55	146.49	0.783	0.30( 0.28)	0.94	64569.2	12231.00
19	42935.63	154.45	0.766	0.30( 0.28)	0.94	66203.5	10400.00
20	41507.83	162.56	0.749	0.30( 0.28)	0.94	67498.6	12010.00
21	40260.68	168.68	0.737	0.30( 0.28)	0.94	67845.6	10210.00
22	35850.15	197.45	0.694	0.30( 0.28)	0.94	68584.0	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 47196.68 Tc(MIN.) = 116.29  
AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 52200.05

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13840.00 TO NODE 13860.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:

TIME OF CONCENTRATION(MIN.) = 116.29  
RAINFALL INTENSITY(INCH/HR) = 0.85  
AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.93  
EFFECTIVE STREAM AREA(ACRES) = 52200.05  
TOTAL STREAM AREA(ACRES) = 68584.01  
PEAK FLOW RATE(CFS) AT CONFLUENCE = 47196.68

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13850.00 TO NODE 13851.00 IS CODE = 21  
-----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 617.57  
ELEVATION DATA: UPSTREAM(FEET) = 646.95 DOWNSTREAM(FEET) = 490.10

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 12.137  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 3.051  
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER						
"CHAPARRAL,BROADLEAF"	-	4.95	0.30	1.000	56	12.14

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA RUNOFF(CFS) = 12.25  
TOTAL AREA(ACRES) = 4.95 PEAK FLOW RATE(CFS) = 12.25

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13851.00 TO NODE 13851.50 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 490.10 DOWNSTREAM(FEET) = 440.98  
CHANNEL LENGTH THRU SUBAREA(FEET) = 351.14 CHANNEL SLOPE = 0.1399  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.36  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.846  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	4.02	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 16.86  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.43  
AVERAGE FLOW DEPTH(FEET) = 0.36 TRAVEL TIME(MIN.) = 1.32  
Tc(MIN.) = 13.46  
SUBAREA AREA(ACRES) = 4.02 SUBAREA RUNOFF(CFS) = 9.21  
EFFECTIVE AREA(ACRES) = 8.97 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 9.0 PEAK FLOW RATE(CFS) = 20.55  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.40

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.40 FLOW VELOCITY(FEET/SEC.) = 4.74  
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13851.50 = 968.71 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13851.50 TO NODE 13852.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 440.98 DOWNSTREAM(FEET) = 395.76  
CHANNEL LENGTH THRU SUBAREA(FEET) = 512.91 CHANNEL SLOPE = 0.0882  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.56  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.578  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.17	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 27.91  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.55  
AVERAGE FLOW DEPTH(FEET) = 0.55 TRAVEL TIME(MIN.) = 1.88  
Tc(MIN.) = 15.34  
SUBAREA AREA(ACRES) = 7.17 SUBAREA RUNOFF(CFS) = 14.70  
EFFECTIVE AREA(ACRES) = 16.14 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 16.1 PEAK FLOW RATE(CFS) = 33.10  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.61

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.61 FLOW VELOCITY(FEET/SEC.) = 4.86  
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13852.00 = 1481.62 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13852.00 TO NODE 13853.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 395.76 DOWNSTREAM(FEET) = 354.94  
CHANNEL LENGTH THRU SUBAREA(FEET) = 443.69 CHANNEL SLOPE = 0.0920  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.67  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.459  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	6.76	0.30	1.000	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 39.67  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.23  
AVERAGE FLOW DEPTH(FEET) = 0.67 TRAVEL TIME(MIN.) = 1.41  
Tc(MIN.) = 16.75  
SUBAREA AREA(ACRES) = 6.76 SUBAREA RUNOFF(CFS) = 13.14  
EFFECTIVE AREA(ACRES) = 22.90 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 22.9 PEAK FLOW RATE(CFS) = 44.50  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.71

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.71 FLOW VELOCITY(FEET/SEC.) = 5.45  
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13853.00 = 1925.31 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13853.00 TO NODE 13854.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 354.94 DOWNSTREAM(FEET) = 263.57  
CHANNEL LENGTH THRU SUBAREA(FEET) = 962.09 CHANNEL SLOPE = 0.0950  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.86  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.237

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	18.16	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 60.34  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.12  
AVERAGE FLOW DEPTH(FEET) = 0.84 TRAVEL TIME(MIN.) = 2.62  
Tc(MIN.) = 19.37  
SUBAREA AREA(ACRES) = 18.16 SUBAREA RUNOFF(CFS) = 31.66  
EFFECTIVE AREA(ACRES) = 41.06 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 41.1 PEAK FLOW RATE(CFS) = 71.59  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.93

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.93 FLOW VELOCITY(FEET/SEC.) = 6.46  
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13854.00 = 2887.40 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13854.00 TO NODE 13855.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 263.57 DOWNSTREAM(FEET) = 188.74

CHANNEL LENGTH THRU SUBAREA(FEET) = 1228.77 CHANNEL SLOPE = 0.0609  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.32  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.031

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	38.75	0.30	0.879	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.879  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 102.43  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.25  
AVERAGE FLOW DEPTH(FEET) = 1.30 TRAVEL TIME(MIN.) = 3.27  
Tc(MIN.) = 22.65  
SUBAREA AREA(ACRES) = 38.75 SUBAREA RUNOFF(CFS) = 61.64  
EFFECTIVE AREA(ACRES) = 79.81 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94  
TOTAL AREA(ACRES) = 79.8 PEAK FLOW RATE(CFS) = 125.61  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.46

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 1.46 FLOW VELOCITY(FEET/SEC.) = 6.66  
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13855.00 = 4116.17 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 31  
-----

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 188.74 DOWNSTREAM(FEET) = 130.00  
FLOW LENGTH(FEET) = 2092.67 MANNING'S N = 0.013  
DEPTH OF FLOW IN 39.0 INCH PIPE IS 30.6 INCHES  
PIPE-FLOW VELOCITY(FEET/SEC.) = 18.01  
ESTIMATED PIPE DIAMETER(INCH) = 39.00 NUMBER OF PIPES = 1  
PIPE-FLOW(CFS) = 125.61  
PIPE TRAVEL TIME(MIN.) = 1.94 Tc(MIN.) = 24.58  
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13860.00 = 6208.84 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 24.58  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 1.919  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	43.41	0.30	0.707	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.707  
SUBAREA AREA(ACRES) = 43.41 SUBAREA RUNOFF(CFS) = 66.69  
EFFECTIVE AREA(ACRES) = 123.22 AREA-AVERAGED Fm(INCH/HR) = 0.26  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.86

TOTAL AREA (ACRES) = 123.2 PEAK FLOW RATE (CFS) = 184.26

\*\*\*\*\*

FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION (MIN.) = 24.58
RAINFALL INTENSITY (INCH/HR) = 1.92
AREA-AVERAGED Fm (INCH/HR) = 0.26
AREA-AVERAGED Fp (INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.86
EFFECTIVE STREAM AREA (ACRES) = 123.22
TOTAL STREAM AREA (ACRES) = 123.22
PEAK FLOW RATE (CFS) AT CONFLUENCE = 184.26

\*\* CONFLUENCE DATA \*\*

Table with columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp (Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 20 rows of data for stream 1 and 2.

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

Table with columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp (Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 6 rows of data for stream 1.

Table with columns: Node number, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp (Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 19 rows of data for stream 2.

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 47262.83 Tc (MIN.) = 116.29
EFFECTIVE AREA (ACRES) = 52323.27 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA (ACRES) = 68707.2
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13860.00 = 133458.73 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13860.00 TO NODE 13880.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 130.00 DOWNSTREAM (FEET) = 120.57
CHANNEL LENGTH THRU SUBAREA (FEET) = 610.77 CHANNEL SLOPE = 0.0154
GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
\*ESTIMATED CHANNEL HEIGHT (FEET) = 12.03
\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 0.852
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCSSOIL AREA Fp Ap SCSS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 4.89 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 47264.04
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 26.53
AVERAGE FLOW DEPTH (FEET) = 12.03 TRAVEL TIME (MIN.) = 0.38
Tc (MIN.) = 116.68
SUBAREA AREA (ACRES) = 4.89 SUBAREA RUNOFF (CFS) = 2.43
EFFECTIVE AREA (ACRES) = 52328.16 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA (ACRES) = 68712.1 PEAK FLOW RATE (CFS) = 47262.83
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
\*ESTIMATED CHANNEL HEIGHT (FEET) = 12.03
END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 12.03 FLOW VELOCITY (FEET/SEC.) = 26.53

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13880.00 = 134069.50 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24842.47	21.67	2.087	0.30 ( 0.25)	0.83	4553.0	10600.00
2	25684.63	23.84	1.962	0.30 ( 0.25)	0.83	5272.4	13810.00
3	26135.56	25.04	1.893	0.30 ( 0.25)	0.83	5660.3	13850.00
4	30193.25	35.97	1.548	0.30 ( 0.25)	0.83	9143.8	13830.00
5	31808.36	40.56	1.435	0.30 ( 0.25)	0.83	10530.2	110.00
6	34143.29	46.84	1.333	0.30 ( 0.25)	0.84	13606.2	130.00
7	35910.93	52.14	1.258	0.30 ( 0.25)	0.84	16136.8	150.00
8	39178.71	66.13	1.129	0.30 ( 0.26)	0.87	23187.4	390.00
9	41155.96	77.63	1.051	0.30 ( 0.27)	0.89	29241.4	13100.00
10	41894.02	84.47	1.005	0.30 ( 0.27)	0.89	32295.8	11801.00
11	43388.74	95.02	0.946	0.30 ( 0.27)	0.91	37717.1	11530.00
12	44288.62	99.29	0.928	0.30 ( 0.27)	0.91	40562.8	13510.00
13	46002.33	108.05	0.890	0.30 ( 0.28)	0.92	46364.1	13500.00
14	46857.10	112.50	0.870	0.30 ( 0.28)	0.92	49382.8	10800.00
15	47262.83	116.68	0.852	0.30 ( 0.28)	0.93	52328.2	11130.00
16	46703.53	126.32	0.825	0.30 ( 0.28)	0.93	57369.4	12410.00
17	45971.16	134.68	0.807	0.30 ( 0.28)	0.94	61108.5	11201.00
18	45473.39	139.70	0.797	0.30 ( 0.28)	0.94	62840.2	12201.00
19	44370.80	146.88	0.782	0.30 ( 0.28)	0.94	64697.3	12231.00
20	42992.04	154.85	0.765	0.30 ( 0.28)	0.94	66331.6	10400.00
21	41562.36	162.96	0.749	0.30 ( 0.28)	0.94	67626.7	12010.00
22	40313.80	169.08	0.736	0.30 ( 0.28)	0.94	67973.7	10210.00
23	35898.60	197.87	0.694	0.30 ( 0.28)	0.94	68712.1	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 47262.83 Tc(MIN.) = 116.68  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 52328.16

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13860.00 TO NODE 13880.00 IS CODE = 1  
 -----

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

-----  
 TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
 TIME OF CONCENTRATION(MIN.) = 116.68  
 RAINFALL INTENSITY(INCH/HR) = 0.85  
 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93  
 EFFECTIVE STREAM AREA(ACRES) = 52328.16  
 TOTAL STREAM AREA(ACRES) = 68712.12  
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 47262.83

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13870.00 TO NODE 13871.00 IS CODE = 21  
 -----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

-----  
 INITIAL SUBAREA FLOW-LENGTH(FEET) = 872.65  
 ELEVATION DATA: UPSTREAM(FEET) = 558.52 DOWNSTREAM(FEET) = 436.47

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20

SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 15.704

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.547

SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------	--------------

NATURAL FAIR COVER

"GRASS" - 7.32 0.30 1.000 56 15.70

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

SUBAREA RUNOFF(CFS) = 14.81

TOTAL AREA(ACRES) = 7.32 PEAK FLOW RATE(CFS) = 14.81

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13871.00 TO NODE 13872.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

-----  
ELEVATION DATA: UPSTREAM(FEET) = 436.47 DOWNSTREAM(FEET) = 337.62

CHANNEL LENGTH THRU SUBAREA(FEET) = 827.95 CHANNEL SLOPE = 0.1194

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.51

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.311

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

USER-DEFINED - 13.01 0.30 1.000 -

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 26.60

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.93

AVERAGE FLOW DEPTH(FEET) = 0.49 TRAVEL TIME(MIN.) = 2.80

Tc(MIN.) = 18.50

SUBAREA AREA(ACRES) = 13.01 SUBAREA RUNOFF(CFS) = 23.54

EFFECTIVE AREA(ACRES) = 20.33 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 20.3 PEAK FLOW RATE(CFS) = 36.79

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.59

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.59 FLOW VELOCITY(FEET/SEC.) = 5.55

LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13872.00 = 1700.60 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13872.00 TO NODE 13873.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

-----  
ELEVATION DATA: UPSTREAM(FEET) = 337.62 DOWNSTREAM(FEET) = 253.88

CHANNEL LENGTH THRU SUBAREA(FEET) = 1049.16 CHANNEL SLOPE = 0.0798

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.94

\* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 2.099  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	32.99	0.30	0.923	-

 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.923  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 63.87  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.88  
 AVERAGE FLOW DEPTH (FEET) = 0.92 TRAVEL TIME (MIN.) = 2.98  
 Tc (MIN.) = 21.48  
 SUBAREA AREA (ACRES) = 32.99 SUBAREA RUNOFF (CFS) = 54.09  
 EFFECTIVE AREA (ACRES) = 53.32 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95  
 TOTAL AREA (ACRES) = 53.3 PEAK FLOW RATE (CFS) = 87.00  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 1.10  
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 1.10 FLOW VELOCITY (FEET/SEC.) = 6.51  
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13873.00 = 2749.76 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13873.00 TO NODE 13874.00 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 -----  
 ELEVATION DATA: UPSTREAM (FEET) = 253.88 DOWNSTREAM (FEET) = 160.73  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1518.60 CHANNEL SLOPE = 0.0613  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 1.09  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.925  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	30.94	0.30	0.900	-

 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.900  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 110.06  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.45  
 AVERAGE FLOW DEPTH (FEET) = 1.07 TRAVEL TIME (MIN.) = 3.00  
 Tc (MIN.) = 24.47  
 SUBAREA AREA (ACRES) = 30.94 SUBAREA RUNOFF (CFS) = 46.10  
 EFFECTIVE AREA (ACRES) = 84.26 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 84.3 PEAK FLOW RATE (CFS) = 124.79  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 1.15  
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 1.15 FLOW VELOCITY (FEET/SEC.) = 8.78  
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13874.00 = 4268.36 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13874.00 TO NODE 13875.00 IS CODE = 56  
 -----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 -----  
 ELEVATION DATA: UPSTREAM (FEET) = 160.73 DOWNSTREAM (FEET) = 158.14  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 582.74 CHANNEL SLOPE = 0.0044  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 2.90  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.820  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	73.67	0.30	0.930	-

 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.930  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 175.88  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 3.90  
 AVERAGE FLOW DEPTH (FEET) = 2.87 TRAVEL TIME (MIN.) = 2.49  
 Tc (MIN.) = 26.96  
 SUBAREA AREA (ACRES) = 73.67 SUBAREA RUNOFF (CFS) = 102.15  
 EFFECTIVE AREA (ACRES) = 157.93 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 157.9 PEAK FLOW RATE (CFS) = 218.91  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 3.21  
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 3.21 FLOW VELOCITY (FEET/SEC.) = 4.14  
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13875.00 = 4851.10 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 31

-----  
 >>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<  
 -----  
 ELEVATION DATA: UPSTREAM (FEET) = 158.14 DOWNSTREAM (FEET) = 120.57  
 FLOW LENGTH (FEET) = 1855.67 MANNING'S N = 0.013  
 DEPTH OF FLOW IN 51.0 INCH PIPE IS 40.1 INCHES  
 PIPE-FLOW VELOCITY (FEET/SEC.) = 18.30  
 ESTIMATED PIPE DIAMETER (INCH) = 51.00 NUMBER OF PIPES = 1  
 PIPE-FLOW (CFS) = 218.91  
 PIPE TRAVEL TIME (MIN.) = 1.69 Tc (MIN.) = 28.65  
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13880.00 = 6706.77 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 81

-----  
 >>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 -----  
 MAINLINE Tc (MIN.) = 28.65  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 1.755  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------



USER-DEFINED - 34.90 0.30 0.743 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.743  
 SUBAREA AREA(ACRES) = 34.90 SUBAREA RUNOFF(CFS) = 48.11  
 EFFECTIVE AREA(ACRES) = 192.83 AREA-AVERAGED Fm(INCH/HR) = 0.27  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.90  
 TOTAL AREA(ACRES) = 192.8 PEAK FLOW RATE(CFS) = 257.80

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
 TIME OF CONCENTRATION(MIN.) = 28.65  
 RAINFALL INTENSITY(INCH/HR) = 1.75  
 AREA-AVERAGED Fm(INCH/HR) = 0.27  
 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.90  
 EFFECTIVE STREAM AREA(ACRES) = 192.83  
 TOTAL STREAM AREA(ACRES) = 192.83  
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 257.80

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24842.47	21.67	2.087	0.30( 0.25)	0.83	4553.0	10600.00
1	25684.63	23.84	1.962	0.30( 0.25)	0.83	5272.4	13810.00
1	26135.56	25.04	1.893	0.30( 0.25)	0.83	5660.3	13850.00
1	30193.25	35.97	1.548	0.30( 0.25)	0.83	9143.8	13830.00
1	31808.36	40.56	1.435	0.30( 0.25)	0.83	10530.2	110.00
1	34143.29	46.84	1.333	0.30( 0.25)	0.84	13606.2	130.00
1	35910.93	52.14	1.258	0.30( 0.25)	0.84	16136.8	150.00
1	39178.71	66.13	1.129	0.30( 0.26)	0.87	23187.4	390.00
1	41155.96	77.63	1.051	0.30( 0.27)	0.89	29241.4	13100.00
1	41894.02	84.47	1.005	0.30( 0.27)	0.89	32295.8	11801.00
1	43388.74	95.02	0.946	0.30( 0.27)	0.91	37717.1	11530.00
1	44288.62	99.29	0.928	0.30( 0.27)	0.91	40562.8	13510.00
1	46002.33	108.05	0.890	0.30( 0.28)	0.92	46364.1	13500.00
1	46857.10	112.50	0.870	0.30( 0.28)	0.92	49382.8	10800.00
1	47262.83	116.68	0.852	0.30( 0.28)	0.93	52328.2	11130.00
1	46703.53	126.32	0.825	0.30( 0.28)	0.93	57369.4	12410.00
1	45971.16	134.68	0.807	0.30( 0.28)	0.94	61108.5	11201.00
1	45473.39	139.70	0.797	0.30( 0.28)	0.94	62840.2	12201.00
1	44370.80	146.88	0.782	0.30( 0.28)	0.94	64697.3	12231.00
1	42992.04	154.85	0.765	0.30( 0.28)	0.94	66331.6	10400.00
1	41562.36	162.96	0.749	0.30( 0.28)	0.94	67626.7	12010.00
1	40313.80	169.08	0.736	0.30( 0.28)	0.94	67973.7	10210.00
1	35898.60	197.87	0.694	0.30( 0.28)	0.94	68712.1	10100.00
2	257.80	28.65	1.755	0.30( 0.27)	0.90	192.8	13870.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	--------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE	
1	25081.13	21.67	2.087	0.30( 0.25)	0.83	4698.9	10600.00
2	25929.06	23.84	1.962	0.30( 0.25)	0.83	5432.8	13810.00
3	26381.89	25.04	1.893	0.30( 0.25)	0.83	5828.8	13850.00
4	27734.66	28.65	1.755	0.30( 0.25)	0.83	7004.6	13870.00
5	30415.25	35.97	1.548	0.30( 0.25)	0.83	9336.6	13830.00
6	32010.67	40.56	1.435	0.30( 0.25)	0.83	10723.1	110.00
7	34327.93	46.84	1.333	0.30( 0.25)	0.84	13799.0	130.00
8	36082.53	52.14	1.258	0.30( 0.25)	0.84	16329.7	150.00
9	39327.88	66.13	1.129	0.30( 0.26)	0.87	23380.2	390.00
10	41291.69	77.63	1.051	0.30( 0.27)	0.89	29434.2	13100.00
11	42021.75	84.47	1.005	0.30( 0.27)	0.89	32488.6	11801.00
12	43506.23	95.02	0.946	0.30( 0.27)	0.91	37910.0	11530.00
13	44402.91	99.29	0.928	0.30( 0.27)	0.91	40755.6	13510.00
14	46110.04	108.05	0.890	0.30( 0.28)	0.92	46556.9	13500.00
15	46961.45	112.50	0.870	0.30( 0.28)	0.92	49575.6	10800.00
16	47364.04	116.68	0.852	0.30( 0.28)	0.93	52521.0	11130.00
17	46799.96	126.32	0.825	0.30( 0.28)	0.93	57562.2	12410.00
18	46064.57	134.68	0.807	0.30( 0.28)	0.94	61301.3	11201.00
19	45564.98	139.70	0.797	0.30( 0.28)	0.94	63033.0	12201.00
20	44459.79	146.88	0.782	0.30( 0.28)	0.94	64890.2	12231.00
21	43078.16	154.85	0.765	0.30( 0.28)	0.94	66524.4	10400.00
22	41645.55	162.96	0.749	0.30( 0.28)	0.94	67819.5	12010.00
23	40394.77	169.08	0.736	0.30( 0.28)	0.94	68166.5	10210.00
24	35972.33	197.87	0.694	0.30( 0.28)	0.94	68904.9	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 47364.04 Tc(MIN.) = 116.68  
 EFFECTIVE AREA(ACRES) = 52520.99 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 68904.9  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13880.00 = 134069.50 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13880.00 TO NODE 13910.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 120.57 DOWNSTREAM(FEET) = 119.70  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1190.21 CHANNEL SLOPE = 0.0007  
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 26.19  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.843  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	117.69	0.30	0.724	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.724  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 47397.17  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.84  
 AVERAGE FLOW DEPTH(FEET) = 26.18 TRAVEL TIME(MIN.) = 2.24  
 Tc(MIN.) = 118.92  
 SUBAREA AREA(ACRES) = 117.69 SUBAREA RUNOFF(CFS) = 66.26  
 EFFECTIVE AREA(ACRES) = 52638.68 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA (ACRES) = 69022.6 PEAK FLOW RATE (CFS) = 47364.04  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 26.17

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 26.17 FLOW VELOCITY (FEET/SEC.) = 8.84  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13910.00 = 135259.70 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25081.13	24.34	1.933	0.30 ( 0.25)	0.83	4816.6	10600.00
2	25929.06	26.48	1.838	0.30 ( 0.25)	0.83	5550.5	13810.00
3	26381.89	27.67	1.793	0.30 ( 0.25)	0.83	5946.5	13850.00
4	27734.66	31.25	1.671	0.30 ( 0.25)	0.83	7122.3	13870.00
5	30415.25	38.50	1.483	0.30 ( 0.25)	0.83	9454.3	13830.00
6	32010.67	43.05	1.395	0.30 ( 0.25)	0.83	10840.8	110.00
7	34327.93	49.29	1.293	0.30 ( 0.25)	0.84	13916.7	130.00
8	36082.53	54.56	1.231	0.30 ( 0.25)	0.84	16447.3	150.00
9	39327.88	68.49	1.113	0.30 ( 0.26)	0.87	23497.9	390.00
10	41291.69	79.96	1.036	0.30 ( 0.27)	0.89	29551.9	13100.00
11	42021.75	86.79	0.990	0.30 ( 0.27)	0.89	32606.3	11801.00
12	43506.23	97.32	0.936	0.30 ( 0.27)	0.90	38027.6	11530.00
13	44402.91	101.57	0.918	0.30 ( 0.27)	0.91	40873.3	13510.00
14	46110.04	110.31	0.880	0.30 ( 0.28)	0.92	46674.6	13500.00
15	46961.45	114.75	0.861	0.30 ( 0.28)	0.92	49693.3	10800.00
16	47364.04	118.92	0.843	0.30 ( 0.28)	0.93	52638.7	11130.00
17	46799.96	128.57	0.820	0.30 ( 0.28)	0.93	57679.9	12410.00
18	46064.57	136.94	0.803	0.30 ( 0.28)	0.94	61419.0	11201.00
19	45564.98	141.96	0.792	0.30 ( 0.28)	0.94	63150.7	12201.00
20	44459.79	149.16	0.777	0.30 ( 0.28)	0.94	65007.8	12231.00
21	43078.16	157.15	0.761	0.30 ( 0.28)	0.94	66642.1	10400.00
22	41645.55	165.28	0.744	0.30 ( 0.28)	0.94	67937.2	12010.00
23	40394.77	171.42	0.731	0.30 ( 0.28)	0.94	68284.2	10210.00
24	35972.33	200.28	0.691	0.30 ( 0.28)	0.94	69022.6	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 47364.04 Tc (MIN.) = 118.92  
 AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA (ACRES) = 52638.68

\*\*\*\*\*

FLOW PROCESS FROM NODE 13880.00 TO NODE 13910.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
 TIME OF CONCENTRATION (MIN.) = 118.92  
 RAINFALL INTENSITY (INCH/HR) = 0.84  
 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93  
 EFFECTIVE STREAM AREA (ACRES) = 52638.68  
 TOTAL STREAM AREA (ACRES) = 69022.63  
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 47364.04

\*\*\*\*\*

FLOW PROCESS FROM NODE 13889.00 TO NODE 13890.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH (FEET) = 447.89  
 ELEVATION DATA: UPSTREAM (FEET) = 564.89 DOWNSTREAM (FEET) = 421.92

Tc = K \* [(LENGTH\*\* 3.00) / (ELEVATION CHANGE)] \*\* 0.20  
 SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 6.976  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 4.497  
 SUBAREA Tc AND LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)  
 PUBLIC PARK - 3.03 0.30 0.960 56 6.98  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.960  
 SUBAREA RUNOFF (CFS) = 11.48  
 TOTAL AREA (ACRES) = 3.03 PEAK FLOW RATE (CFS) = 11.48

\*\*\*\*\*

FLOW PROCESS FROM NODE 13890.00 TO NODE 13891.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 421.92 DOWNSTREAM (FEET) = 392.64  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 435.33 CHANNEL SLOPE = 0.0673  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 0.46  
 \* 50 YEAR RAINFALL INTENSITY (INCH/HR) = 3.985  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 8.12 0.30 0.986 -  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.986  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 25.00  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.23  
 AVERAGE FLOW DEPTH (FEET) = 0.44 TRAVEL TIME (MIN.) = 1.39  
 Tc (MIN.) = 8.36  
 SUBAREA AREA (ACRES) = 8.12 SUBAREA RUNOFF (CFS) = 26.96  
 EFFECTIVE AREA (ACRES) = 11.15 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98  
 TOTAL AREA (ACRES) = 11.1 PEAK FLOW RATE (CFS) = 37.04  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 0.55

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 0.55 FLOW VELOCITY (FEET/SEC.) = 6.02  
 LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13891.00 = 883.22 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13891.00 TO NODE 13892.00 IS CODE = 56

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 392.64 DOWNSTREAM(FEET) = 324.46
CHANNEL LENGTH THRU SUBAREA(FEET) = 662.40 CHANNEL SLOPE = 0.1029
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.64
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 3.473
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 12.50 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 54.93
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.95
AVERAGE FLOW DEPTH(FEET) = 0.62 TRAVEL TIME(MIN.) = 1.39
Tc(MIN.) = 9.75
SUBAREA AREA(ACRES) = 12.50 SUBAREA RUNOFF(CFS) = 35.70
EFFECTIVE AREA(ACRES) = 23.65 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 23.6 PEAK FLOW RATE(CFS) = 67.61
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.70

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.70 FLOW VELOCITY(FEET/SEC.) = 8.51
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13892.00 = 1545.62 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13892.00 TO NODE 13893.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 324.46 DOWNSTREAM(FEET) = 240.82
CHANNEL LENGTH THRU SUBAREA(FEET) = 980.03 CHANNEL SLOPE = 0.0853
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.87
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 3.131
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 15.87 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 87.84
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.75
AVERAGE FLOW DEPTH(FEET) = 0.86 TRAVEL TIME(MIN.) = 1.87
Tc(MIN.) = 11.62
SUBAREA AREA(ACRES) = 15.87 SUBAREA RUNOFF(CFS) = 40.43
EFFECTIVE AREA(ACRES) = 39.52 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 39.5 PEAK FLOW RATE(CFS) = 100.75
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

```

```

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.93

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.93 FLOW VELOCITY(FEET/SEC.) = 9.18
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13893.00 = 2525.65 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13893.00 TO NODE 13894.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 240.82 DOWNSTREAM(FEET) = 163.04
CHANNEL LENGTH THRU SUBAREA(FEET) = 1144.35 CHANNEL SLOPE = 0.0680
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.18
* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.812
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 28.41 0.30 0.985 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.985
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 132.98
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.28
AVERAGE FLOW DEPTH(FEET) = 1.16 TRAVEL TIME(MIN.) = 2.05
Tc(MIN.) = 13.68
SUBAREA AREA(ACRES) = 28.41 SUBAREA RUNOFF(CFS) = 64.36
EFFECTIVE AREA(ACRES) = 67.93 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 67.9 PEAK FLOW RATE(CFS) = 153.78
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.26

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.26 FLOW VELOCITY(FEET/SEC.) = 9.73
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13894.00 = 3670.00 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 31
-----

```

```

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 163.04 DOWNSTREAM(FEET) = 119.70
FLOW LENGTH(FEET) = 1899.01 MANNING'S N = 0.013
DEPTH OF FLOW IN 45.0 INCH PIPE IS 33.0 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 17.73
ESTIMATED PIPE DIAMETER(INCH) = 45.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 153.78
PIPE TRAVEL TIME(MIN.) = 1.79 Tc(MIN.) = 15.46
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13910.00 = 5569.01 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 81

```

=====  
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<  
=====

MAINLINE Tc(MIN.) = 15.46  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.568  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 11.69 0.30 0.634 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.634  
SUBAREA AREA(ACRES) = 11.69 SUBAREA RUNOFF(CFS) = 25.02  
EFFECTIVE AREA(ACRES) = 79.62 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94  
TOTAL AREA(ACRES) = 79.6 PEAK FLOW RATE(CFS) = 163.86

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 1  
=====

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<  
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<  
=====

TOTAL NUMBER OF STREAMS = 2  
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
TIME OF CONCENTRATION(MIN.) = 15.46  
RAINFALL INTENSITY(INCH/HR) = 2.57  
AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.94  
EFFECTIVE STREAM AREA(ACRES) = 79.62  
TOTAL STREAM AREA(ACRES) = 79.62  
PEAK FLOW RATE(CFS) AT CONFLUENCE = 163.86

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25081.13	24.34	1.933	0.30( 0.25)	0.83	4816.6	10600.00
1	25929.06	26.48	1.838	0.30( 0.25)	0.83	5550.5	13810.00
1	26381.89	27.67	1.793	0.30( 0.25)	0.83	5946.5	13850.00
1	27734.66	31.25	1.671	0.30( 0.25)	0.83	7122.3	13870.00
1	30415.25	38.50	1.483	0.30( 0.25)	0.83	9454.3	13830.00
1	32010.67	43.05	1.395	0.30( 0.25)	0.83	10840.8	110.00
1	34327.93	49.29	1.293	0.30( 0.25)	0.84	13916.7	130.00
1	36082.53	54.56	1.231	0.30( 0.25)	0.84	16447.3	150.00
1	39327.88	68.49	1.113	0.30( 0.26)	0.87	23497.9	390.00
1	41291.69	79.96	1.036	0.30( 0.27)	0.89	29551.9	13100.00
1	42021.75	86.79	0.990	0.30( 0.27)	0.89	32606.3	11801.00
1	43506.23	97.32	0.936	0.30( 0.27)	0.90	38027.6	11530.00
1	44402.91	101.57	0.918	0.30( 0.27)	0.91	40873.3	13510.00
1	46110.04	110.31	0.880	0.30( 0.28)	0.92	46674.6	13500.00
1	46961.45	114.75	0.861	0.30( 0.28)	0.92	49693.3	10800.00
1	47364.04	118.92	0.843	0.30( 0.28)	0.93	52638.7	11130.00
1	46799.96	128.57	0.820	0.30( 0.28)	0.93	57679.9	12410.00
1	46064.57	136.94	0.803	0.30( 0.28)	0.94	61419.0	11201.00
1	45564.98	141.96	0.792	0.30( 0.28)	0.94	63150.7	12201.00
1	44459.79	149.16	0.777	0.30( 0.28)	0.94	65007.8	12231.00
1	43078.16	157.15	0.761	0.30( 0.28)	0.94	66642.1	10400.00
1	41645.55	165.28	0.744	0.30( 0.28)	0.94	67937.2	12010.00

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	40394.77	171.42	0.731	0.30( 0.28)	0.94	68284.2	10210.00
1	35972.33	200.28	0.691	0.30( 0.28)	0.94	69022.6	10100.00
2	163.86	15.46	2.568	0.30( 0.28)	0.94	79.6	13889.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22103.01	15.46	2.568	0.30( 0.25)	0.83	3139.2	13889.00
2	25199.50	24.34	1.933	0.30( 0.25)	0.83	4896.2	10600.00
3	26040.61	26.48	1.838	0.30( 0.25)	0.83	5630.1	13810.00
4	26490.18	27.67	1.793	0.30( 0.25)	0.83	6026.1	13850.00
5	27834.22	31.25	1.671	0.30( 0.25)	0.83	7201.9	13870.00
6	30501.35	38.50	1.483	0.30( 0.25)	0.83	9533.9	13830.00
7	32090.44	43.05	1.395	0.30( 0.25)	0.83	10920.4	110.00
8	34400.46	49.29	1.293	0.30( 0.25)	0.84	13996.3	130.00
9	36150.58	54.56	1.231	0.30( 0.25)	0.84	16527.0	150.00
10	39387.46	68.49	1.113	0.30( 0.26)	0.87	23577.5	390.00
11	41345.74	79.96	1.036	0.30( 0.27)	0.89	29631.5	13100.00
12	42072.51	86.79	0.990	0.30( 0.27)	0.89	32685.9	11801.00
13	43553.17	97.32	0.936	0.30( 0.27)	0.90	38107.3	11530.00
14	44448.53	101.57	0.918	0.30( 0.27)	0.91	40953.0	13510.00
15	46152.93	110.31	0.880	0.30( 0.28)	0.92	46754.2	13500.00
16	47002.97	114.75	0.861	0.30( 0.28)	0.92	49773.0	10800.00
17	47404.27	118.92	0.843	0.30( 0.28)	0.93	52718.3	11130.00
18	46838.57	128.57	0.820	0.30( 0.28)	0.93	57759.5	12410.00
19	46101.93	136.94	0.803	0.30( 0.28)	0.94	61498.6	11201.00
20	45601.60	141.96	0.792	0.30( 0.28)	0.94	63230.3	12201.00
21	44495.33	149.16	0.777	0.30( 0.28)	0.94	65087.5	12231.00
22	43112.50	157.15	0.761	0.30( 0.28)	0.94	66721.8	10400.00
23	41678.68	165.28	0.744	0.30( 0.28)	0.94	68016.8	12010.00
24	40426.99	171.42	0.731	0.30( 0.28)	0.94	68363.8	10210.00
25	36001.72	200.28	0.691	0.30( 0.28)	0.94	69102.2	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 47404.27 Tc(MIN.) = 118.92  
EFFECTIVE AREA(ACRES) = 52718.30 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA(ACRES) = 69102.2  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13910.00 = 135259.70 FEET.  
=====

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 69102.2 TC(MIN.) = 118.92  
EFFECTIVE AREA(ACRES) = 52718.30 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.928  
PEAK FLOW RATE(CFS) = 47404.27

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22103.01	15.46	2.568	0.30( 0.25)	0.83	3139.2	13889.00
2	25199.50	24.34	1.933	0.30( 0.25)	0.83	4896.2	10600.00
3	26040.61	26.48	1.838	0.30( 0.25)	0.83	5630.1	13810.00
4	26490.18	27.67	1.793	0.30( 0.25)	0.83	6026.1	13850.00
5	27834.22	31.25	1.671	0.30( 0.25)	0.83	7201.9	13870.00
6	30501.35	38.50	1.483	0.30( 0.25)	0.83	9533.9	13830.00

7	32090.44	43.05	1.395	0.30	( 0.25)	0.83	10920.4	110.00
8	34400.46	49.29	1.293	0.30	( 0.25)	0.84	13996.3	130.00
9	36150.58	54.56	1.231	0.30	( 0.25)	0.84	16527.0	150.00
10	39387.46	68.49	1.113	0.30	( 0.26)	0.87	23577.5	390.00
11	41345.74	79.96	1.036	0.30	( 0.27)	0.89	29631.5	13100.00
12	42072.51	86.79	0.990	0.30	( 0.27)	0.89	32685.9	11801.00
13	43553.17	97.32	0.936	0.30	( 0.27)	0.90	38107.3	11530.00
14	44448.53	101.57	0.918	0.30	( 0.27)	0.91	40953.0	13510.00
15	46152.93	110.31	0.880	0.30	( 0.28)	0.92	46754.2	13500.00
16	47002.97	114.75	0.861	0.30	( 0.28)	0.92	49773.0	10800.00
17	47404.27	118.92	0.843	0.30	( 0.28)	0.93	52718.3	11130.00
18	46838.57	128.57	0.820	0.30	( 0.28)	0.93	57759.5	12410.00
19	46101.93	136.94	0.803	0.30	( 0.28)	0.94	61498.6	11201.00
20	45601.60	141.96	0.792	0.30	( 0.28)	0.94	63230.3	12201.00
21	44495.33	149.16	0.777	0.30	( 0.28)	0.94	65087.5	12231.00
22	43112.50	157.15	0.761	0.30	( 0.28)	0.94	66721.8	10400.00
23	41678.68	165.28	0.744	0.30	( 0.28)	0.94	68016.8	12010.00
24	40426.99	171.42	0.731	0.30	( 0.28)	0.94	68363.8	10210.00
25	36001.72	200.28	0.691	0.30	( 0.28)	0.94	69102.2	10100.00

=====  
 END OF RATIONAL METHOD ANALYSIS  
 =====

\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S39- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 50-YR RM EV APRIL 2019 CCHI \*  
\*\*\*\*\*

FILE NAME: RI50EV39.DAT  
TIME/DATE OF STUDY: 09:18 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 50.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.220
- 2) 10.00; 3.380
- 3) 15.00; 2.606
- 4) 20.00; 2.184
- 5) 25.00; 1.894
- 6) 30.00; 1.703
- 7) 40.00; 1.444
- 8) 50.00; 1.282
- 9) 60.00; 1.169
- 10) 90.00; 0.968
- 11) 120.00; 0.837
- 12) 180.00; 0.712
- 13) 360.00; 0.522
- 14) 1200.00; 0.227

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL: IN- / OUT-/PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13900.00 TO NODE 13901.00 IS CODE = 21  
-----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 600.65  
ELEVATION DATA: UPSTREAM(FEET) = 442.40 DOWNSTREAM(FEET) = 385.16

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 10.859  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 3.247  
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
AGRICULTURAL POOR COVER "FALLOW"	-	4.00	0.30	1.000	56	10.86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA RUNOFF(CFS) = 10.61  
TOTAL AREA(ACRES) = 4.00 PEAK FLOW RATE(CFS) = 10.61

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13901.00 TO NODE 13902.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 385.16 DOWNSTREAM(FEET) = 288.21  
CHANNEL LENGTH THRU SUBAREA(FEET) = 647.42 CHANNEL SLOPE = 0.1497  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.32  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.983  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.47	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 20.86  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.34  
AVERAGE FLOW DEPTH(FEET) = 0.31 TRAVEL TIME(MIN.) = 1.70  
Tc(MIN.) = 12.56  
SUBAREA AREA(ACRES) = 8.47 SUBAREA RUNOFF(CFS) = 20.46  
EFFECTIVE AREA(ACRES) = 12.47 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 12.5 PEAK FLOW RATE(CFS) = 30.12  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.39

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.39 FLOW VELOCITY(FEET/SEC.) = 7.24  
LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13902.00 = 1248.07 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13902.00 TO NODE 13903.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 288.21 DOWNSTREAM(FEET) = 184.89  
CHANNEL LENGTH THRU SUBAREA(FEET) = 669.27 CHANNEL SLOPE = 0.1544  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.57

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.795

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	23.85	0.30	0.982	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.982

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 56.98

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.15

AVERAGE FLOW DEPTH(FEET) = 0.56 TRAVEL TIME(MIN.) = 1.22

Tc(MIN.) = 13.78

SUBAREA AREA(ACRES) = 23.85 SUBAREA RUNOFF(CFS) = 53.67

EFFECTIVE AREA(ACRES) = 36.32 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 36.3 PEAK FLOW RATE(CFS) = 81.67

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.69

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.69 FLOW VELOCITY(FEET/SEC.) = 10.38

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13903.00 = 1917.34 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13903.00 TO NODE 13904.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<

>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 184.89 DOWNSTREAM(FEET) = 155.08

FLOW LENGTH(FEET) = 876.66 MANNING'S N = 0.013

ESTIMATED PIPE DIAMETER(INCH) INCREASED TO 36.000

DEPTH OF FLOW IN 36.0 INCH PIPE IS 22.2 INCHES

PIPE-FLOW VELOCITY(FEET/SEC.) = 17.86

ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1

PIPE-FLOW(CFS) = 81.67

PIPE TRAVEL TIME(MIN.) = 0.82 Tc(MIN.) = 14.60

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13904.00 = 2794.00 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13903.00 TO NODE 13904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 14.60

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.668

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	21.29	0.30	0.996	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.996

SUBAREA AREA(ACRES) = 21.29 SUBAREA RUNOFF(CFS) = 45.40

EFFECTIVE AREA(ACRES) = 57.61 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 57.6 PEAK FLOW RATE(CFS) = 122.93

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<

>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<

ELEVATION DATA: UPSTREAM(FEET) = 155.08 DOWNSTREAM(FEET) = 118.00

FLOW LENGTH(FEET) = 1961.38 MANNING'S N = 0.013

DEPTH OF FLOW IN 42.0 INCH PIPE IS 32.3 INCHES

PIPE-FLOW VELOCITY(FEET/SEC.) = 15.50

ESTIMATED PIPE DIAMETER(INCH) = 42.00 NUMBER OF PIPES = 1

PIPE-FLOW(CFS) = 122.93

PIPE TRAVEL TIME(MIN.) = 2.11 Tc(MIN.) = 16.71

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13920.00 = 4755.38 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 16.71

\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 2.462

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	43.53	0.30	0.649	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.649

SUBAREA AREA(ACRES) = 43.53 SUBAREA RUNOFF(CFS) = 88.82

EFFECTIVE AREA(ACRES) = 101.14 AREA-AVERAGED Fm(INCH/HR) = 0.25

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84

TOTAL AREA(ACRES) = 101.1 PEAK FLOW RATE(CFS) = 201.06

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13910.00 TO NODE 13910.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<

PEAK FLOWRATE TABLE FILE NAME: RI50EV38.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22103.01	15.46	0.30 ( 0.25)	0.83	3139.2	13889.00
2	27834.22	31.25	0.30 ( 0.25)	0.83	7201.9	13870.00
3	30501.35	38.50	0.30 ( 0.25)	0.83	9533.9	13830.00
4	32090.44	43.05	0.30 ( 0.25)	0.83	10920.4	110.00
5	34400.46	49.29	0.30 ( 0.25)	0.84	13996.3	130.00
6	36150.58	54.56	0.30 ( 0.25)	0.84	16527.0	150.00
7	39387.46	68.49	0.30 ( 0.26)	0.87	23577.5	390.00
8	41345.74	79.96	0.30 ( 0.27)	0.89	29631.5	13100.00
9	42072.51	86.79	0.30 ( 0.27)	0.89	32685.9	11801.00
10	44448.53	101.57	0.30 ( 0.27)	0.91	40953.0	13510.00
11	47002.97	114.75	0.30 ( 0.28)	0.92	49773.0	10800.00
12	47404.27	118.92	0.30 ( 0.28)	0.93	52718.3	11130.00
13	46838.57	128.57	0.30 ( 0.28)	0.93	57759.5	12410.00
14	46101.93	136.94	0.30 ( 0.28)	0.94	61498.6	11201.00
15	45601.60	141.96	0.30 ( 0.28)	0.94	63230.3	12201.00
16	44495.33	149.16	0.30 ( 0.28)	0.94	65087.5	12231.00
17	43112.50	157.15	0.30 ( 0.28)	0.94	66721.8	10400.00
18	41678.68	165.28	0.30 ( 0.28)	0.94	68016.8	12010.00
19	40426.99	171.42	0.30 ( 0.28)	0.94	68363.8	10210.00
20	36001.72	200.28	0.30 ( 0.28)	0.94	69102.2	10100.00
TOTAL AREA (ACRES) =						69102.2

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13910.00 TO NODE 13910.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22103.01	15.46	0.30 ( 0.25)	0.83	3139.2	13889.00
2	27834.22	31.25	0.30 ( 0.25)	0.83	7201.9	13870.00
3	30501.35	38.50	0.30 ( 0.25)	0.83	9533.9	13830.00
4	32090.44	43.05	0.30 ( 0.25)	0.83	10920.4	110.00
5	34400.46	49.29	0.30 ( 0.25)	0.84	13996.3	130.00
6	36150.58	54.56	0.30 ( 0.25)	0.84	16527.0	150.00
7	39387.46	68.49	0.30 ( 0.26)	0.87	23577.5	390.00
8	41345.74	79.96	0.30 ( 0.27)	0.89	29631.5	13100.00
9	42072.51	86.79	0.30 ( 0.27)	0.89	32685.9	11801.00
10	44448.53	101.57	0.30 ( 0.27)	0.91	40953.0	13510.00
11	47002.97	114.75	0.30 ( 0.28)	0.92	49773.0	10800.00
12	47404.27	118.92	0.30 ( 0.28)	0.93	52718.3	11130.00
13	46838.57	128.57	0.30 ( 0.28)	0.93	57759.5	12410.00
14	46101.93	136.94	0.30 ( 0.28)	0.94	61498.6	11201.00
15	45601.60	141.96	0.30 ( 0.28)	0.94	63230.3	12201.00
16	44495.33	149.16	0.30 ( 0.28)	0.94	65087.5	12231.00
17	43112.50	157.15	0.30 ( 0.28)	0.94	66721.8	10400.00
18	41678.68	165.28	0.30 ( 0.28)	0.94	68016.8	12010.00
19	40426.99	171.42	0.30 ( 0.28)	0.94	68363.8	10210.00
20	36001.72	200.28	0.30 ( 0.28)	0.94	69102.2	10100.00
TOTAL AREA (ACRES) =						69102.2

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13910.00 TO NODE 13920.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 119.70 DOWNSTREAM(FEET) = 118.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1376.26 CHANNEL SLOPE = 0.0012  
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 23.04  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.835  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 96.09 0.30 0.535 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.535  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 47433.42  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.72  
 AVERAGE FLOW DEPTH(FEET) = 23.04 TRAVEL TIME(MIN.) = 2.14  
 Tc(MIN.) = 121.06  
 SUBAREA AREA(ACRES) = 96.09 SUBAREA RUNOFF(CFS) = 58.32  
 EFFECTIVE AREA(ACRES) = 52814.39 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 69198.3 PEAK FLOW RATE(CFS) = 47404.27  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 23.03

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 23.03 FLOW VELOCITY(FEET/SEC.) = 10.71

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136635.97 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22103.01	18.10	2.344	0.30 ( 0.25)	0.83	3235.3	13889.00
2	27834.22	33.72	1.607	0.30 ( 0.25)	0.83	7298.0	13870.00
3	30501.35	40.91	1.429	0.30 ( 0.25)	0.83	9630.0	13830.00
4	32090.44	45.43	1.356	0.30 ( 0.25)	0.83	11016.5	110.00
5	34400.46	51.63	1.264	0.30 ( 0.25)	0.83	14092.4	130.00
6	36150.58	56.86	1.204	0.30 ( 0.25)	0.84	16623.1	150.00
7	39387.46	70.74	1.097	0.30 ( 0.26)	0.86	23673.6	390.00
8	41345.74	82.18	1.020	0.30 ( 0.27)	0.88	29727.6	13100.00
9	42072.51	89.00	0.975	0.30 ( 0.27)	0.89	32782.0	11801.00
10	44448.53	103.75	0.908	0.30 ( 0.27)	0.91	41049.0	13510.00
11	47002.97	116.90	0.851	0.30 ( 0.28)	0.92	49869.1	10800.00
12	47404.27	121.06	0.835	0.30 ( 0.28)	0.93	52814.4	11130.00
13	46838.57	130.72	0.815	0.30 ( 0.28)	0.93	57855.6	12410.00
14	46101.93	139.09	0.797	0.30 ( 0.28)	0.94	61594.7	11201.00
15	45601.60	144.13	0.787	0.30 ( 0.28)	0.94	63326.4	12201.00
16	44495.33	151.34	0.772	0.30 ( 0.28)	0.94	65183.6	12231.00
17	43112.50	159.35	0.755	0.30 ( 0.28)	0.94	66817.8	10400.00
18	41678.68	167.50	0.738	0.30 ( 0.28)	0.94	68112.9	12010.00
19	40426.99	173.66	0.725	0.30 ( 0.28)	0.94	68459.9	10210.00
20	36001.72	202.59	0.688	0.30 ( 0.28)	0.94	69198.3	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 47404.27 Tc(MIN.) = 121.06



AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 52814.39

\*\*\*\*\*

FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22103.01	18.10	2.344	0.30( 0.25)	0.83	3235.3	13889.00
2	27834.22	33.72	1.607	0.30( 0.25)	0.83	7298.0	13870.00
3	30501.35	40.91	1.429	0.30( 0.25)	0.83	9630.0	13830.00
4	32090.44	45.43	1.356	0.30( 0.25)	0.83	11016.5	110.00
5	34400.46	51.63	1.264	0.30( 0.25)	0.83	14092.4	130.00
6	36150.58	56.86	1.204	0.30( 0.25)	0.84	16623.1	150.00
7	39387.46	70.74	1.097	0.30( 0.26)	0.86	23673.6	390.00
8	41345.74	82.18	1.020	0.30( 0.27)	0.88	29727.6	13100.00
9	42072.51	89.00	0.975	0.30( 0.27)	0.89	32782.0	11801.00
10	44448.53	103.75	0.908	0.30( 0.27)	0.91	41049.0	13510.00
11	47002.97	116.90	0.851	0.30( 0.28)	0.92	49869.1	10800.00
12	47404.27	121.06	0.835	0.30( 0.28)	0.93	52814.4	11130.00
13	46838.57	130.72	0.815	0.30( 0.28)	0.93	57855.6	12410.00
14	46101.93	139.09	0.797	0.30( 0.28)	0.94	61594.7	11201.00
15	45601.60	144.13	0.787	0.30( 0.28)	0.94	63326.4	12201.00
16	44495.33	151.34	0.772	0.30( 0.28)	0.94	65183.6	12231.00
17	43112.50	159.35	0.755	0.30( 0.28)	0.94	66817.8	10400.00
18	41678.68	167.50	0.738	0.30( 0.28)	0.94	68112.9	12010.00
19	40426.99	173.66	0.725	0.30( 0.28)	0.94	68459.9	10210.00
20	36001.72	202.59	0.688	0.30( 0.28)	0.94	69198.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136635.97 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	201.06	16.71	2.462	0.30( 0.25)	0.84	101.1	13900.00

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13920.00 = 4755.38 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21746.53	16.71	2.462	0.30( 0.25)	0.83	3087.2	13900.00
2	22293.36	18.10	2.344	0.30( 0.25)	0.83	3336.5	13889.00
3	27957.42	33.72	1.607	0.30( 0.25)	0.83	7399.2	13870.00
4	30608.40	40.91	1.429	0.30( 0.25)	0.83	9731.1	13830.00
5	32190.83	45.43	1.356	0.30( 0.25)	0.83	11117.6	110.00
6	34492.45	51.63	1.264	0.30( 0.25)	0.83	14193.5	130.00
7	36237.18	56.86	1.204	0.30( 0.25)	0.84	16724.2	150.00
8	39464.28	70.74	1.097	0.30( 0.26)	0.86	23774.7	390.00
9	41415.59	82.18	1.020	0.30( 0.27)	0.88	29828.8	13100.00
10	42138.20	89.00	0.975	0.30( 0.27)	0.89	32883.1	11801.00
11	44508.14	103.75	0.908	0.30( 0.27)	0.91	41150.2	13510.00
12	47057.35	116.90	0.851	0.30( 0.28)	0.92	49970.2	10800.00
13	47457.21	121.06	0.835	0.30( 0.28)	0.93	52915.5	11130.00
14	46889.69	130.72	0.815	0.30( 0.28)	0.93	57956.7	12410.00
15	46151.46	139.09	0.797	0.30( 0.28)	0.94	61695.8	11201.00

16	45650.17	144.13	0.787	0.30( 0.28)	0.94	63427.5	12201.00
17	44542.54	151.34	0.772	0.30( 0.28)	0.94	65284.7	12231.00
18	43158.19	159.35	0.755	0.30( 0.28)	0.94	66919.0	10400.00
19	41722.82	167.50	0.738	0.30( 0.28)	0.94	68214.1	12010.00
20	40469.96	173.66	0.725	0.30( 0.28)	0.94	68561.0	10210.00
21	36041.32	202.59	0.688	0.30( 0.28)	0.94	69299.5	10100.00

TOTAL AREA(ACRES) = 69299.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 47457.21 Tc(MIN.) = 121.062  
EFFECTIVE AREA(ACRES) = 52915.53 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
TOTAL AREA(ACRES) = 69299.5  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136635.97 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13920.00 TO NODE 13921.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 118.00 DOWNSTREAM(FEET) = 115.28  
CHANNEL LENGTH THRU SUBAREA(FEET) = 335.44 CHANNEL SLOPE = 0.0081  
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 14.30  
\* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.834

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	134.30	0.30	0.658	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.658  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 47495.70  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 21.14  
AVERAGE FLOW DEPTH(FEET) = 14.29 TRAVEL TIME(MIN.) = 0.26  
Tc(MIN.) = 121.33  
SUBAREA AREA(ACRES) = 134.30 SUBAREA RUNOFF(CFS) = 76.98  
EFFECTIVE AREA(ACRES) = 53049.83 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA(ACRES) = 69433.8 PEAK FLOW RATE(CFS) = 47457.21  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 14.29

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 14.29 FLOW VELOCITY(FEET/SEC.) = 21.13  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13921.00 = 136971.41 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	21746.53	17.04	2.434	0.30( 0.25)	0.82	3221.5	13900.00
2	22293.36	18.43	2.316	0.30( 0.25)	0.82	3470.8	13889.00
3	27957.42	34.03	1.599	0.30( 0.25)	0.83	7533.5	13870.00
4	30608.40	41.21	1.424	0.30( 0.25)	0.83	9865.4	13830.00
5	32190.83	45.73	1.351	0.30( 0.25)	0.83	11251.9	110.00

6	34492.45	51.92	1.260	0.30	( 0.25)	0.83	14327.8	130.00
7	36237.18	57.15	1.201	0.30	( 0.25)	0.84	16858.5	150.00
8	39464.28	71.02	1.095	0.30	( 0.26)	0.86	23909.0	390.00
9	41415.59	82.45	1.019	0.30	( 0.26)	0.88	29963.1	13100.00
10	42138.20	89.27	0.973	0.30	( 0.27)	0.89	33017.4	11801.00
11	44508.14	104.02	0.907	0.30	( 0.27)	0.91	41284.5	13510.00
12	47057.35	117.16	0.849	0.30	( 0.28)	0.92	50104.5	10800.00
13	47457.21	121.33	0.834	0.30	( 0.28)	0.93	53049.8	11130.00
14	46889.69	130.99	0.814	0.30	( 0.28)	0.93	58091.0	12410.00
15	46151.46	139.36	0.797	0.30	( 0.28)	0.94	61830.1	11201.00
16	45650.17	144.39	0.786	0.30	( 0.28)	0.94	63561.8	12201.00
17	44542.54	151.61	0.771	0.30	( 0.28)	0.94	65419.0	12231.00
18	43158.19	159.62	0.754	0.30	( 0.28)	0.94	67053.3	10400.00
19	41722.82	167.77	0.737	0.30	( 0.28)	0.94	68348.4	12010.00
20	40469.96	173.94	0.725	0.30	( 0.28)	0.94	68695.3	10210.00
21	36041.32	202.88	0.688	0.30	( 0.28)	0.94	69433.8	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 47457.21 Tc(MIN.) = 121.33  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 53049.83

\*\*\*\*\*

FLOW PROCESS FROM NODE 13921.00 TO NODE 14010.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 115.28 DOWNSTREAM(FEET) = 100.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1396.08 CHANNEL SLOPE = 0.0109  
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 13.22  
 \* 50 YEAR RAINFALL INTENSITY(INCH/HR) = 0.832

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	96.27	0.30	0.723	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.723  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 47483.87  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 23.52  
 AVERAGE FLOW DEPTH(FEET) = 13.21 TRAVEL TIME(MIN.) = 0.99  
 Tc(MIN.) = 122.32  
 SUBAREA AREA(ACRES) = 96.27 SUBAREA RUNOFF(CFS) = 53.31  
 EFFECTIVE AREA(ACRES) = 53146.10 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 69530.1 PEAK FLOW RATE(CFS) = 47457.21  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 13.21

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 13.21 FLOW VELOCITY(FEET/SEC.) = 23.51  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 14010.00 = 138367.48 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	--------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	21746.53	18.29	2.329	0.30( 0.24)	0.82	3317.8 13900.00
2	22293.36	19.67	2.212	0.30( 0.25)	0.82	3567.0 13889.00
3	27957.42	35.19	1.569	0.30( 0.25)	0.82	7629.7 13870.00
4	30608.40	42.34	1.406	0.30( 0.25)	0.83	9961.7 13830.00
5	32190.83	46.84	1.333	0.30( 0.25)	0.83	11348.2 110.00
6	34492.45	53.00	1.248	0.30( 0.25)	0.83	14424.1 130.00
7	36237.18	58.22	1.189	0.30( 0.25)	0.84	16954.8 150.00
8	39464.28	72.06	1.088	0.30( 0.26)	0.86	24005.3 390.00
9	41415.59	83.48	1.012	0.30( 0.26)	0.88	30059.3 13100.00
10	42138.20	90.30	0.967	0.30( 0.27)	0.89	33113.7 11801.00
11	44508.14	105.03	0.902	0.30( 0.27)	0.91	41380.8 13510.00
12	47057.35	118.15	0.845	0.30( 0.28)	0.92	50200.8 10800.00
13	47457.21	122.32	0.832	0.30( 0.28)	0.93	53146.1 11130.00
14	46889.69	131.98	0.812	0.30( 0.28)	0.93	58187.3 12410.00
15	46151.46	140.36	0.795	0.30( 0.28)	0.94	61926.4 11201.00
16	45650.17	145.40	0.784	0.30( 0.28)	0.94	63658.1 12201.00
17	44542.54	152.62	0.769	0.30( 0.28)	0.94	65515.3 12231.00
18	43158.19	160.63	0.752	0.30( 0.28)	0.94	67149.6 10400.00
19	41722.82	168.80	0.735	0.30( 0.28)	0.94	68444.6 12010.00
20	40469.96	174.97	0.722	0.30( 0.28)	0.94	68791.6 10210.00
21	36041.32	203.95	0.687	0.30( 0.28)	0.94	69530.1 10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 47457.21 Tc(MIN.) = 122.32  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 53146.10

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 69530.1 TC(MIN.) = 122.32  
 EFFECTIVE AREA(ACRES) = 53146.10 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.926  
 PEAK FLOW RATE(CFS) = 47457.21

\*\* PEAK FLOW RATE TABLE \*\*

STREAM	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE	
1	21746.53	18.29	2.329	0.30( 0.24)	0.82	3317.8 13900.00	
2	22293.36	19.67	2.212	0.30( 0.25)	0.82	3567.0 13889.00	
3	27957.42	35.19	1.569	0.30( 0.25)	0.82	7629.7 13870.00	
4	30608.40	42.34	1.406	0.30( 0.25)	0.83	9961.7 13830.00	
5	32190.83	46.84	1.333	0.30( 0.25)	0.83	11348.2 110.00	
6	34492.45	53.00	1.248	0.30( 0.25)	0.83	14424.1 130.00	
7	36237.18	58.22	1.189	0.30( 0.25)	0.84	16954.8 150.00	
8	39464.28	72.06	1.088	0.30( 0.26)	0.86	24005.3 390.00	
9	41415.59	83.48	1.012	0.30( 0.26)	0.88	30059.3 13100.00	
10	42138.20	90.30	0.967	0.30( 0.27)	0.89	33113.7 11801.00	
11	44508.14	105.03	0.902	0.30( 0.27)	0.91	41380.8 13510.00	
12	47057.35	118.15	0.845	0.30( 0.28)	0.92	50200.8 10800.00	
13	47457.21	122.32	0.832	0.30( 0.28)	0.93	53146.1 11130.00	
14	46889.69	131.98	0.812	0.30( 0.28)	0.93	58187.3 12410.00	
15	46151.46	140.36	0.795	0.30( 0.28)	0.94	61926.4 11201.00	
16	45650.17	145.40	0.784	0.30( 0.28)	0.94	63658.1 12201.00	
17	44542.54	152.62	0.769	0.30( 0.28)	0.94	65515.3 12231.00	
18	43158.19	160.63	0.752	0.30( 0.28)	0.94	67149.6 10400.00	
19	41722.82	168.80	0.735	0.30( 0.28)	0.94	68444.6 12010.00	
20	40469.96	174.97	0.722	0.30( 0.28)	0.94	68791.6 10210.00	
21	36041.32	203.95	0.687	0.30( 0.28)	0.94	69530.1 10100.00	

=====  
END OF RATIONAL METHOD ANALYSIS

\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S19- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 100-YR EM EV APRIL 2019 CCHI \*  
\*\*\*\*\*

FILE NAME: RI00EV19.DAT  
TIME/DATE OF STUDY: 08:49 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 100.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 6.126
- 2) 10.00; 3.912
- 3) 15.00; 3.013
- 4) 20.00; 2.469
- 5) 25.00; 2.132
- 6) 30.00; 1.903
- 7) 40.00; 1.647
- 8) 50.00; 1.421
- 9) 60.00; 1.323
- 10) 90.00; 1.122
- 11) 120.00; 0.986
- 12) 180.00; 0.829
- 13) 360.00; 0.620
- 14) 1200.00; 0.273

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11900.00 TO NODE 11901.00 IS CODE = 21  
-----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 295.79  
ELEVATION DATA: UPSTREAM(FEET) = 2369.48 DOWNSTREAM(FEET) = 2332.92

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 7.203  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 5.150  
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
RESIDENTIAL ".4 DWELLING/ACRE"	-	1.62	0.30	0.999	0	7.20

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999  
SUBAREA RUNOFF(CFS) = 7.07  
TOTAL AREA(ACRES) = 1.62 PEAK FLOW RATE(CFS) = 7.07

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11901.00 TO NODE 11902.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2332.92 DOWNSTREAM(FEET) = 2297.70  
CHANNEL LENGTH THRU SUBAREA(FEET) = 664.26 CHANNEL SLOPE = 0.0530  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.61  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.841  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.35	0.30	0.906	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.906  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 20.63  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 3.47  
AVERAGE FLOW DEPTH(FEET) = 0.54 TRAVEL TIME(MIN.) = 3.19  
Tc(MIN.) = 10.39  
SUBAREA AREA(ACRES) = 8.35 SUBAREA RUNOFF(CFS) = 26.83  
EFFECTIVE AREA(ACRES) = 9.97 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
TOTAL AREA(ACRES) = 10.0 PEAK FLOW RATE(CFS) = 31.99  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.69

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.69 FLOW VELOCITY(FEET/SEC.) = 4.06  
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11902.00 = 960.05 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11902.00 TO NODE 11902.50 IS CODE = 56

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

-----  
ELEVATION DATA: UPSTREAM(FEET) = 2297.70 DOWNSTREAM(FEET) = 2263.40  
CHANNEL LENGTH THRU SUBAREA(FEET) = 928.77 CHANNEL SLOPE = 0.0369  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.37  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.267

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	34.48	0.30	0.904	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.904  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 78.76  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.84  
AVERAGE FLOW DEPTH(FEET) = 1.29 TRAVEL TIME(MIN.) = 3.20  
Tc(MIN.) = 13.59

SUBAREA AREA(ACRES) = 34.48 SUBAREA RUNOFF(CFS) = 92.96  
EFFECTIVE AREA(ACRES) = 44.45 AREA-AVERAGED Fm(INCH/HR) = 0.27  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.91  
TOTAL AREA(ACRES) = 44.5 PEAK FLOW RATE(CFS) = 119.79  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.64

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.64 FLOW VELOCITY(FEET/SEC.) = 5.52  
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11902.50 = 1888.82 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11902.50 TO NODE 11903.00 IS CODE = 56

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

-----  
ELEVATION DATA: UPSTREAM(FEET) = 2263.40 DOWNSTREAM(FEET) = 2252.14  
CHANNEL LENGTH THRU SUBAREA(FEET) = 895.50 CHANNEL SLOPE = 0.0126  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.49  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.762

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	23.65	0.30	0.958	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.958  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 146.17  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.02  
AVERAGE FLOW DEPTH(FEET) = 2.44 TRAVEL TIME(MIN.) = 3.72

Tc(MIN.) = 17.31  
SUBAREA AREA(ACRES) = 23.65 SUBAREA RUNOFF(CFS) = 52.68  
EFFECTIVE AREA(ACRES) = 68.10 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA(ACRES) = 68.1 PEAK FLOW RATE(CFS) = 152.29  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.50

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.50 FLOW VELOCITY(FEET/SEC.) = 4.06  
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11903.00 = 2784.32 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11903.00 TO NODE 11904.00 IS CODE = 56

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

-----  
ELEVATION DATA: UPSTREAM(FEET) = 2252.14 DOWNSTREAM(FEET) = 2186.04  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1924.35 CHANNEL SLOPE = 0.0343  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.38  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.314

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	68.53	0.30	0.961	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.961  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 214.93  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.42  
AVERAGE FLOW DEPTH(FEET) = 2.29 TRAVEL TIME(MIN.) = 4.99  
Tc(MIN.) = 22.30

SUBAREA AREA(ACRES) = 68.53 SUBAREA RUNOFF(CFS) = 124.95  
EFFECTIVE AREA(ACRES) = 136.63 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94  
TOTAL AREA(ACRES) = 136.6 PEAK FLOW RATE(CFS) = 249.78  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.49

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.49 FLOW VELOCITY(FEET/SEC.) = 6.70  
LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11904.00 = 4708.67 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11904.00 TO NODE 11905.00 IS CODE = 56

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

-----  
ELEVATION DATA: UPSTREAM(FEET) = 2186.04 DOWNSTREAM(FEET) = 1957.34  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1926.87 CHANNEL SLOPE = 0.1187  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.99

\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.122  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 63.15 0.30 1.000 -  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 301.58  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 10.97  
 AVERAGE FLOW DEPTH (FEET) = 1.97 TRAVEL TIME (MIN.) = 2.93  
 Tc (MIN.) = 25.22  
 SUBAREA AREA (ACRES) = 63.15 SUBAREA RUNOFF (CFS) = 103.54  
 EFFECTIVE AREA (ACRES) = 199.78 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA (ACRES) = 199.8 PEAK FLOW RATE (CFS) = 329.66  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 2.07

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 2.07 FLOW VELOCITY (FEET/SEC.) = 11.26  
 LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11905.00 = 6635.54 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11905.00 TO NODE 11906.00 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 -----

ELEVATION DATA: UPSTREAM (FEET) = 1957.34 DOWNSTREAM (FEET) = 1244.16  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 2498.96 CHANNEL SLOPE = 0.2854  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 1.81  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.004  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 84.87 0.30 1.000 -  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 394.76  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 16.17  
 AVERAGE FLOW DEPTH (FEET) = 1.80 TRAVEL TIME (MIN.) = 2.58  
 Tc (MIN.) = 27.80  
 SUBAREA AREA (ACRES) = 84.87 SUBAREA RUNOFF (CFS) = 130.15  
 EFFECTIVE AREA (ACRES) = 284.65 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97  
 TOTAL AREA (ACRES) = 284.6 PEAK FLOW RATE (CFS) = 438.60  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 1.90

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 1.90 FLOW VELOCITY (FEET/SEC.) = 16.70  
 LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11906.00 = 9134.50 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11906.00 TO NODE 11920.00 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 -----

ELEVATION DATA: UPSTREAM (FEET) = 1244.16 DOWNSTREAM (FEET) = 873.95  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 3370.75 CHANNEL SLOPE = 0.1098  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 2.89  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.848  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 199.43 0.30 1.000 -  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 577.59  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 12.91  
 AVERAGE FLOW DEPTH (FEET) = 2.85 TRAVEL TIME (MIN.) = 4.35  
 Tc (MIN.) = 32.15  
 SUBAREA AREA (ACRES) = 199.43 SUBAREA RUNOFF (CFS) = 277.84  
 EFFECTIVE AREA (ACRES) = 484.08 AREA-AVERAGED Fm (INCH/HR) = 0.30  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98  
 TOTAL AREA (ACRES) = 484.1 PEAK FLOW RATE (CFS) = 676.50  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 3.10

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 3.10 FLOW VELOCITY (FEET/SEC.) = 13.47  
 LONGEST FLOWPATH FROM NODE 11900.00 TO NODE 11920.00 = 12505.25 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11906.00 TO NODE 11920.00 IS CODE = 1

-----  
 >>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 -----

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
 TIME OF CONCENTRATION (MIN.) = 32.15  
 RAINFALL INTENSITY (INCH/HR) = 1.85  
 AREA-AVERAGED Fm (INCH/HR) = 0.30  
 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.98  
 EFFECTIVE STREAM AREA (ACRES) = 484.08  
 TOTAL STREAM AREA (ACRES) = 484.08  
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 676.50

\*\*\*\*\*

FLOW PROCESS FROM NODE 11910.00 TO NODE 11911.00 IS CODE = 21

-----  
 >>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<  
 -----

INITIAL SUBAREA FLOW-LENGTH (FEET) = 517.62  
 ELEVATION DATA: UPSTREAM (FEET) = 2531.88 DOWNSTREAM (FEET) = 2441.33

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
 SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 12.185  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.519  
 SUBAREA Tc AND LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS Tc  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN (MIN.)  
 NATURAL FAIR COVER  
 "CHAPARRAL,BROADLEAF" - 3.46 0.30 1.000 0 12.19  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA RUNOFF(CFS) = 10.02  
 TOTAL AREA(ACRES) = 3.46 PEAK FLOW RATE(CFS) = 10.02

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11911.00 TO NODE 11912.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2441.33 DOWNSTREAM(FEET) = 2382.20  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 397.30 CHANNEL SLOPE = 0.1488  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.37  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.259

SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 5.79 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 17.74  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.58  
 AVERAGE FLOW DEPTH(FEET) = 0.36 TRAVEL TIME(MIN.) = 1.45  
 Tc(MIN.) = 13.63  
 SUBAREA AREA(ACRES) = 5.79 SUBAREA RUNOFF(CFS) = 15.42  
 EFFECTIVE AREA(ACRES) = 9.25 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 9.2 PEAK FLOW RATE(CFS) = 24.63  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.44

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 0.44 FLOW VELOCITY(FEET/SEC.) = 5.17  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11912.00 = 914.92 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11912.00 TO NODE 11913.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2382.20 DOWNSTREAM(FEET) = 2263.77  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1891.47 CHANNEL SLOPE = 0.0626  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.25

\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.578  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 54.30 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 81.08  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.88  
 AVERAGE FLOW DEPTH(FEET) = 1.13 TRAVEL TIME(MIN.) = 5.37  
 Tc(MIN.) = 19.00  
 SUBAREA AREA(ACRES) = 54.30 SUBAREA RUNOFF(CFS) = 111.33  
 EFFECTIVE AREA(ACRES) = 63.55 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 63.5 PEAK FLOW RATE(CFS) = 130.30  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.48

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.48 FLOW VELOCITY(FEET/SEC.) = 6.81  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11913.00 = 2806.39 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11913.00 TO NODE 11914.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 2263.77 DOWNSTREAM(FEET) = 1845.23  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1957.31 CHANNEL SLOPE = 0.2138  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.32  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.348

SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 65.14 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 190.42  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.69  
 AVERAGE FLOW DEPTH(FEET) = 1.29 TRAVEL TIME(MIN.) = 2.79  
 Tc(MIN.) = 21.79  
 SUBAREA AREA(ACRES) = 65.14 SUBAREA RUNOFF(CFS) = 120.10  
 EFFECTIVE AREA(ACRES) = 128.69 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 128.7 PEAK FLOW RATE(CFS) = 237.27  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.46

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.46 FLOW VELOCITY(FEET/SEC.) = 12.56  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11914.00 = 4763.70 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 11914.00 TO NODE 11915.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1845.23 DOWNSTREAM(FEET) = 1557.21
CHANNEL LENGTH THRU SUBAREA(FEET) = 1686.78 CHANNEL SLOPE = 0.1708
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.81
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.197

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 78.52 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 304.32
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.52
AVERAGE FLOW DEPTH(FEET) = 1.79 TRAVEL TIME(MIN.) = 2.25
Tc(MIN.) = 24.03

SUBAREA AREA(ACRES) = 78.52 SUBAREA RUNOFF(CFS) = 134.07
EFFECTIVE AREA(ACRES) = 207.21 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 207.2 PEAK FLOW RATE(CFS) = 353.81
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.95

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.95 FLOW VELOCITY(FEET/SEC.) = 13.07
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11915.00 = 6450.48 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 11915.00 TO NODE 11916.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1557.21 DOWNSTREAM(FEET) = 1403.38
CHANNEL LENGTH THRU SUBAREA(FEET) = 1909.39 CHANNEL SLOPE = 0.0806
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.60
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.037

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 70.48 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 408.91
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.45
AVERAGE FLOW DEPTH(FEET) = 2.58 TRAVEL TIME(MIN.) = 3.05
Tc(MIN.) = 27.08

SUBAREA AREA(ACRES) = 70.48 SUBAREA RUNOFF(CFS) = 110.17
EFFECTIVE AREA(ACRES) = 277.69 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 277.7 PEAK FLOW RATE(CFS) = 434.06
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.66

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.66 FLOW VELOCITY(FEET/SEC.) = 10.65
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11916.00 = 8359.87 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 11916.00 TO NODE 11917.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1403.38 DOWNSTREAM(FEET) = 1079.99
CHANNEL LENGTH THRU SUBAREA(FEET) = 1945.82 CHANNEL SLOPE = 0.1662
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.64
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.939

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 232.20 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 605.35
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 15.16
AVERAGE FLOW DEPTH(FEET) = 2.62 TRAVEL TIME(MIN.) = 2.14
Tc(MIN.) = 29.22

SUBAREA AREA(ACRES) = 232.20 SUBAREA RUNOFF(CFS) = 342.49
EFFECTIVE AREA(ACRES) = 509.89 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 509.9 PEAK FLOW RATE(CFS) = 752.07
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
\*ESTIMATED CHANNEL HEIGHT(FEET) = 2.94

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 2.94 FLOW VELOCITY(FEET/SEC.) = 16.11
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11917.00 = 10305.69 FEET.

\*\*\*\*\*
FLOW PROCESS FROM NODE 11917.00 TO NODE 11920.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 1079.99 DOWNSTREAM(FEET) = 873.95
CHANNEL LENGTH THRU SUBAREA(FEET) = 2563.91 CHANNEL SLOPE = 0.0804
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 3.74
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.837

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN



```

USER-DEFINED          -      110.82      0.30      1.000      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) =      828.73
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.74
AVERAGE FLOW DEPTH(FEET) = 3.73 TRAVEL TIME(MIN.) = 3.36
Tc(MIN.) = 32.57
SUBAREA AREA(ACRES) = 110.82 SUBAREA RUNOFF(CFS) = 153.31
EFFECTIVE AREA(ACRES) = 620.71 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 620.7 PEAK FLOW RATE(CFS) = 858.72
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 3.80

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 3.80 FLOW VELOCITY(FEET/SEC.) = 12.86
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11920.00 = 12869.60 FEET.

```

```

*****
FLOW PROCESS FROM NODE 11917.00 TO NODE 11920.00 IS CODE = 1
-----

```

```

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<
-----

```

```

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION(MIN.) = 32.57
RAINFALL INTENSITY(INCH/HR) = 1.84
AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 1.00
EFFECTIVE STREAM AREA(ACRES) = 620.71
TOTAL STREAM AREA(ACRES) = 620.71
PEAK FLOW RATE(CFS) AT CONFLUENCE = 858.72

```

```

** CONFLUENCE DATA **

```

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	676.50	32.15	1.848	0.30( 0.30)	0.98	484.1	11900.00
2	858.72	32.57	1.837	0.30( 0.30)	1.00	620.7	11910.00

```

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

```

```

** PEAK FLOW RATE TABLE **

```

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1530.06	32.15	1.848	0.30( 0.30)	0.99	1096.8	11900.00
2	1530.52	32.57	1.837	0.30( 0.30)	0.99	1104.8	11910.00

```

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:
PEAK FLOW RATE(CFS) = 1530.52 Tc(MIN.) = 32.57
EFFECTIVE AREA(ACRES) = 1104.79 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 1104.8
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11920.00 = 12869.60 FEET.

```

```

*****
FLOW PROCESS FROM NODE 11920.00 TO NODE 11921.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
-----

```

```

ELEVATION DATA: UPSTREAM(FEET) = 873.95 DOWNSTREAM(FEET) = 827.94
CHANNEL LENGTH THRU SUBAREA(FEET) = 1417.25 CHANNEL SLOPE = 0.0325
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 6.45
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.781
SUBAREA LOSS RATE DATA(AMC II):

```

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	107.47	0.30	1.000	-

```

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1602.17
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.86
AVERAGE FLOW DEPTH(FEET) = 6.44 TRAVEL TIME(MIN.) = 2.17
Tc(MIN.) = 34.75
SUBAREA AREA(ACRES) = 107.47 SUBAREA RUNOFF(CFS) = 143.30
EFFECTIVE AREA(ACRES) = 1212.26 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 1212.3 PEAK FLOW RATE(CFS) = 1618.46
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 6.47

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 6.47 FLOW VELOCITY(FEET/SEC.) = 10.89
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11921.00 = 14286.85 FEET.

```

```

** PEAK FLOW RATE TABLE **

```

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1619.45	34.33	1.792	0.30( 0.30)	0.99	1204.2	11900.00
2	1618.46	34.75	1.781	0.30( 0.30)	0.99	1212.3	11910.00

```

NEW PEAK FLOW DATA ARE:
PEAK FLOW RATE(CFS) = 1619.45 Tc(MIN.) = 34.33
AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 1204.23

```

```

*****
FLOW PROCESS FROM NODE 11921.00 TO NODE 11922.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
-----

```

```

ELEVATION DATA: UPSTREAM(FEET) = 827.94 DOWNSTREAM(FEET) = 753.55
CHANNEL LENGTH THRU SUBAREA(FEET) = 1886.43 CHANNEL SLOPE = 0.0394
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
*ESTIMATED CHANNEL HEIGHT(FEET) = 6.59
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.726
SUBAREA LOSS RATE DATA(AMC II):

```

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	107.47	0.30	1.000	-

LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 344.27 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1840.35  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.10  
 AVERAGE FLOW DEPTH(FEET) = 6.57 TRAVEL TIME(MIN.) = 2.60  
 Tc(MIN.) = 36.93  
 SUBAREA AREA(ACRES) = 344.27 SUBAREA RUNOFF(CFS) = 441.77  
 EFFECTIVE AREA(ACRES) = 1548.50 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 1556.5 PEAK FLOW RATE(CFS) = 1989.13  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 6.82

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 6.82 FLOW VELOCITY(FEET/SEC.) = 12.35  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11922.00 = 16173.28 FEET.

\*\* PEAK FLOW RATE TABLE \*\*  

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1989.13	36.93	1.726	0.30( 0.30)	0.99	1548.5	11900.00
2	1984.30	37.35	1.715	0.30( 0.30)	1.00	1556.5	11910.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE(CFS) = 1989.13 Tc(MIN.) = 36.93  
 AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 1548.50

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11922.00 TO NODE 11923.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 753.55 DOWNSTREAM(FEET) = 641.58  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2860.88 CHANNEL SLOPE = 0.0391  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 7.00  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.630  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	165.18	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2088.00  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.47  
 AVERAGE FLOW DEPTH(FEET) = 6.99 TRAVEL TIME(MIN.) = 3.82  
 Tc(MIN.) = 40.75  
 SUBAREA AREA(ACRES) = 165.18 SUBAREA RUNOFF(CFS) = 197.74  
 EFFECTIVE AREA(ACRES) = 1713.68 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 1721.7 PEAK FLOW RATE(CFS) = 2053.57  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.93

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 6.93 FLOW VELOCITY(FEET/SEC.) = 12.42  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11923.00 = 19034.16 FEET.

\*\* PEAK FLOW RATE TABLE \*\*  

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2053.57	40.75	1.630	0.30( 0.30)	1.00	1713.7	11900.00
2	2048.35	41.17	1.620	0.30( 0.30)	1.00	1721.7	11910.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE(CFS) = 2053.57 Tc(MIN.) = 40.75  
 AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 1.00 EFFECTIVE AREA(ACRES) = 1713.68

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11923.00 TO NODE 11924.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 641.58 DOWNSTREAM(FEET) = 579.89  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1844.02 CHANNEL SLOPE = 0.0335  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 7.60  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.573  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	433.73	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2301.96  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.07  
 AVERAGE FLOW DEPTH(FEET) = 7.58 TRAVEL TIME(MIN.) = 2.55  
 Tc(MIN.) = 43.30  
 SUBAREA AREA(ACRES) = 433.73 SUBAREA RUNOFF(CFS) = 496.76  
 EFFECTIVE AREA(ACRES) = 2147.41 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 2155.4 PEAK FLOW RATE(CFS) = 2461.56  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 7.82

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 7.82 FLOW VELOCITY(FEET/SEC.) = 12.27  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11924.00 = 20878.18 FEET.

\*\* PEAK FLOW RATE TABLE \*\*  

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2461.56	43.30	1.573	0.30( 0.30)	1.00	2147.4	11900.00
2	2452.07	43.72	1.563	0.30( 0.30)	1.00	2155.4	11910.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE(CFS) = 2461.56 Tc(MIN.) = 43.30  
 AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 1.00 EFFECTIVE AREA(ACRES) = 2147.41

\*\*\*\*\*

FLOW PROCESS FROM NODE 11924.00 TO NODE 11925.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 579.89 DOWNSTREAM(FEET) = 494.12
CHANNEL LENGTH THRU SUBAREA(FEET) = 2756.15 CHANNEL SLOPE = 0.0311
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
\*ESTIMATED CHANNEL HEIGHT(FEET) = 8.18
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.487

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 265.42 0.30 1.000 -

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2603.34
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 12.12
AVERAGE FLOW DEPTH(FEET) = 8.16 TRAVEL TIME(MIN.) = 3.79
Tc(MIN.) = 47.09

SUBAREA AREA(ACRES) = 265.42 SUBAREA RUNOFF(CFS) = 283.53
EFFECTIVE AREA(ACRES) = 2412.83 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 2420.9 PEAK FLOW RATE(CFS) = 2579.55
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
\*ESTIMATED CHANNEL HEIGHT(FEET) = 8.13

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 8.13 FLOW VELOCITY(FEET/SEC.) = 12.09
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11925.00 = 23634.33 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 2579.55 47.09 1.487 0.30( 0.30) 1.00 2412.8 11900.00
2 2566.93 47.52 1.477 0.30( 0.30) 1.00 2420.9 11910.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2579.55 Tc(MIN.) = 47.09
AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 1.00 EFFECTIVE AREA(ACRES) = 2412.83

\*\*\*\*\*

FLOW PROCESS FROM NODE 11925.00 TO NODE 11926.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 494.12 DOWNSTREAM(FEET) = 458.40
CHANNEL LENGTH THRU SUBAREA(FEET) = 1922.70 CHANNEL SLOPE = 0.0186
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
\*ESTIMATED CHANNEL HEIGHT(FEET) = 9.23
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.418

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 97.46 0.30 1.000 -

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2628.59
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.03
AVERAGE FLOW DEPTH(FEET) = 9.22 TRAVEL TIME(MIN.) = 3.20
Tc(MIN.) = 50.28
SUBAREA AREA(ACRES) = 97.46 SUBAREA RUNOFF(CFS) = 98.09
EFFECTIVE AREA(ACRES) = 2510.29 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 2518.3 PEAK FLOW RATE(CFS) = 2579.55
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
\*ESTIMATED CHANNEL HEIGHT(FEET) = 9.14

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 9.14 FLOW VELOCITY(FEET/SEC.) = 9.97
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11926.00 = 25557.03 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE
1 2579.55 50.28 1.418 0.30( 0.30) 1.00 2510.3 11900.00
2 2566.93 50.72 1.414 0.30( 0.30) 1.00 2518.3 11910.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 2579.55 Tc(MIN.) = 50.28
AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 1.00 EFFECTIVE AREA(ACRES) = 2510.29

\*\*\*\*\*

FLOW PROCESS FROM NODE 11926.00 TO NODE 11927.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 458.40 DOWNSTREAM(FEET) = 399.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 2170.13 CHANNEL SLOPE = 0.0274
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060
\*ESTIMATED CHANNEL HEIGHT(FEET) = 8.41
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.388

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 53.83 0.30 1.000 -

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2605.89
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.55
AVERAGE FLOW DEPTH(FEET) = 8.41 TRAVEL TIME(MIN.) = 3.13
Tc(MIN.) = 53.41
SUBAREA AREA(ACRES) = 53.83 SUBAREA RUNOFF(CFS) = 52.69
EFFECTIVE AREA(ACRES) = 2564.12 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA (ACRES) = 2572.1 PEAK FLOW RATE (CFS) = 2579.55  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 8.37

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 8.37 FLOW VELOCITY (FEET/SEC.) = 11.53  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 27727.16 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2579.55	53.41	1.388	0.30 ( 0.30)	1.00	2564.1	11900.00
2	2566.93	53.85	1.383	0.30 ( 0.30)	1.00	2572.1	11910.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 2579.55 Tc (MIN.) = 53.41  
AREA-AVERAGED Fm (INCH/HR) = 0.30 AREA-AVERAGED Fp (INCH/HR) = 0.30  
AREA-AVERAGED Ap = 1.00 EFFECTIVE AREA (ACRES) = 2564.12

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610401Y.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1112.52	23.88	0.30 ( 0.30)	1.00	620.7	40120.00
2	1103.67	25.69	0.30 ( 0.30)	1.00	652.1	40100.00

TOTAL AREA (ACRES) = 652.1

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2579.55	53.41	1.388	0.30 ( 0.30)	1.00	2564.1	11900.00
2	2566.93	53.85	1.383	0.30 ( 0.30)	1.00	2572.1	11910.00

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 27727.16 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1112.52	23.88	2.207	0.30 ( 0.30)	1.00	620.7	40120.00
2	1103.67	25.69	2.100	0.30 ( 0.30)	1.00	652.1	40100.00

LONGEST FLOWPATH FROM NODE 40100.00 TO NODE 11927.00 = 10245.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3134.55	23.88	2.207	0.30 ( 0.30)	1.00	1767.3	40120.00
2	3156.82	25.69	2.100	0.30 ( 0.30)	1.00	1885.3	40100.00

3	3246.24	53.41	1.388	0.30 ( 0.30)	1.00	3216.2	11900.00
4	3231.00	53.85	1.383	0.30 ( 0.30)	1.00	3224.2	11910.00

TOTAL AREA (ACRES) = 3224.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 3246.24 Tc (MIN.) = 53.413  
EFFECTIVE AREA (ACRES) = 3216.18 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA (ACRES) = 3224.2  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.00 = 27727.16 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11927.00 TO NODE 11927.50 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 399.00 DOWNSTREAM (FEET) = 384.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 986.26 CHANNEL SLOPE = 0.0152  
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 10.60  
CHANNEL FLOW THRU SUBAREA (CFS) = 3246.24  
FLOW VELOCITY (FEET/SEC.) = 9.82 FLOW DEPTH (FEET) = 10.60  
TRAVEL TIME (MIN.) = 1.67 Tc (MIN.) = 55.09  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.50 = 28713.42 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3134.55	25.57	2.106	0.30 ( 0.30)	1.00	1767.3	40120.00
2	3156.82	27.38	2.023	0.30 ( 0.30)	1.00	1885.3	40100.00
3	3246.24	55.09	1.371	0.30 ( 0.30)	1.00	3216.2	11900.00
4	3231.00	55.53	1.367	0.30 ( 0.30)	1.00	3224.2	11910.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 3246.24 Tc (MIN.) = 55.09  
AREA-AVERAGED Fm (INCH/HR) = 0.30 AREA-AVERAGED Fp (INCH/HR) = 0.30  
AREA-AVERAGED Ap = 1.00 EFFECTIVE AREA (ACRES) = 3216.18

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 1 <<<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 0610402Y.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	90.15	13.36	0.30 ( 0.30)	1.00	33.3	40200.00

TOTAL AREA (ACRES) = 33.3

\*\*\*\*\*

FLOW PROCESS FROM NODE 11927.50 TO NODE 11927.50 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3134.55	25.57	2.106	0.30 ( 0.30)	1.00	1767.3	40120.00
2	3156.82	27.38	2.023	0.30 ( 0.30)	1.00	1885.3	40100.00
3	3246.24	55.09	1.371	0.30 ( 0.30)	1.00	3216.2	11900.00
4	3231.00	55.53	1.367	0.30 ( 0.30)	1.00	3224.2	11910.00

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.50 = 28713.42 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	90.15	13.36	3.307	0.30 ( 0.30)	1.00	33.3	40200.00

LONGEST FLOWPATH FROM NODE 40200.00 TO NODE 11927.50 = 1999.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2817.53	13.36	3.307	0.30 ( 0.30)	1.00	956.7	40200.00
2	3188.68	25.57	2.106	0.30 ( 0.30)	1.00	1800.6	40120.00
3	3208.47	27.38	2.023	0.30 ( 0.30)	1.00	1918.6	40100.00
4	3278.35	55.09	1.371	0.30 ( 0.30)	1.00	3249.5	11900.00
5	3262.97	55.53	1.367	0.30 ( 0.30)	1.00	3257.5	11910.00

TOTAL AREA (ACRES) = 3257.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 3278.35 Tc (MIN.) = 55.088  
EFFECTIVE AREA (ACRES) = 3249.50 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA (ACRES) = 3257.5  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11927.50 = 28713.42 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11927.50 TO NODE 11928.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 384.00 DOWNSTREAM (FEET) = 359.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 647.19 CHANNEL SLOPE = 0.0386  
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 8.68  
\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.364

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	78.01	0.30	0.984	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.984  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 3315.85  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 13.97  
AVERAGE FLOW DEPTH (FEET) = 8.68 TRAVEL TIME (MIN.) = 0.77

Tc (MIN.) = 55.86

SUBAREA AREA (ACRES) = 78.01 SUBAREA RUNOFF (CFS) = 75.01  
EFFECTIVE AREA (ACRES) = 3327.51 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA (ACRES) = 3335.5 PEAK FLOW RATE (CFS) = 3278.35  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 8.63

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 8.63 FLOW VELOCITY (FEET/SEC.) = 13.93  
LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11928.00 = 29360.61 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2817.53	14.16	3.164	0.30 ( 0.30)	1.00	1034.7	40200.00
2	3188.68	26.35	2.070	0.30 ( 0.30)	1.00	1878.6	40120.00
3	3208.47	28.15	1.988	0.30 ( 0.30)	1.00	1996.6	40100.00
4	3278.35	55.86	1.364	0.30 ( 0.30)	1.00	3327.5	11900.00
5	3262.97	56.30	1.359	0.30 ( 0.30)	1.00	3335.5	11910.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 3278.35 Tc (MIN.) = 55.86  
AREA-AVERAGED Fm (INCH/HR) = 0.30 AREA-AVERAGED Fp (INCH/HR) = 0.30  
AREA-AVERAGED Ap = 1.00 EFFECTIVE AREA (ACRES) = 3327.51

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 359.00 DOWNSTREAM (FEET) = 341.63  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1322.66 CHANNEL SLOPE = 0.0131  
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 11.00  
\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.340

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.18	0.30	0.890	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.890  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 3282.30  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 9.32  
AVERAGE FLOW DEPTH (FEET) = 11.00 TRAVEL TIME (MIN.) = 2.37  
Tc (MIN.) = 58.23

SUBAREA AREA (ACRES) = 8.18 SUBAREA RUNOFF (CFS) = 7.90  
EFFECTIVE AREA (ACRES) = 3335.69 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA (ACRES) = 3343.7 PEAK FLOW RATE (CFS) = 3278.35  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 11.00

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 11.00 FLOW VELOCITY(FEET/SEC.) = 9.32  
 LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11929.00 = 30683.27 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2817.53	16.62	2.837	0.30( 0.30)	1.00	1042.9	40200.00
2	3188.68	28.73	1.961	0.30( 0.30)	1.00	1886.8	40120.00
3	3208.47	30.53	1.889	0.30( 0.30)	1.00	2004.8	40100.00
4	3278.35	58.23	1.340	0.30( 0.30)	1.00	3335.7	11900.00
5	3262.97	58.67	1.336	0.30( 0.30)	1.00	3343.7	11910.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 3278.35 Tc(MIN.) = 58.23  
 AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 1.00 EFFECTIVE AREA(ACRES) = 3335.69

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 10  
 -----

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 3 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11841.00 TO NODE 11527.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11841.00 TO NODE 12527.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: S18X00.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22054.84	36.58	0.30( 0.30)	1.00	7926.9	11831.00
2	22725.41	39.13	0.30( 0.30)	1.00	8505.3	11801.00
3	25134.97	47.53	0.30( 0.30)	1.00	10691.9	11500.00
4	25502.09	49.16	0.30( 0.30)	1.00	11329.9	11530.00
5	26360.19	53.71	0.30( 0.30)	1.00	13011.5	11701.00
6	26779.09	55.76	0.30( 0.30)	1.00	13818.6	11000.00
7	29291.04	65.53	0.30( 0.30)	1.00	18866.7	11330.00
8	30114.29	72.03	0.30( 0.30)	1.00	22317.4	11130.00
9	29645.18	80.38	0.30( 0.30)	1.00	25368.4	11620.00
10	29500.26	82.66	0.30( 0.30)	1.00	26144.7	11600.00
11	29052.00	88.60	0.30( 0.30)	1.00	27897.1	11111.00
12	28910.69	90.07	0.30( 0.30)	1.00	28280.6	11101.00
13	28571.47	94.86	0.30( 0.30)	1.00	29290.8	10710.00
14	28361.22	96.69	0.30( 0.30)	1.00	29594.6	10410.00
15	27934.24	101.05	0.30( 0.30)	1.00	30249.2	10700.00
16	27383.49	107.91	0.30( 0.30)	1.00	31215.0	10400.00
17	27137.20	109.87	0.30( 0.30)	1.00	31440.4	10200.00
18	26251.80	115.74	0.30( 0.30)	1.00	32001.9	10300.00
19	25289.37	121.31	0.30( 0.30)	1.00	32223.4	10210.00
20	23048.07	146.70	0.30( 0.30)	1.00	32916.6	10100.00

TOTAL AREA(ACRES) = 32916.6

\*\*\*\*\*

FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 2 <<<<<

\*\*\*MEMORY BANK # 2 IS EMPTY - PROCESS IGNORED.\*\*\*

\*\*\*\*\*

FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: S25X00.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	7548.90	65.18	0.30( 0.30)	0.99	6431.3	12500.00
2	8477.91	78.32	0.30( 0.30)	0.99	8413.1	12300.00
3	8593.88	79.61	0.30( 0.30)	0.98	8691.0	12330.00
4	8774.49	82.20	0.30( 0.30)	0.98	9202.6	12410.00
5	9008.69	86.22	0.30( 0.29)	0.98	9924.8	12400.00
6	9221.87	90.84	0.30( 0.29)	0.98	10622.1	12211.00
7	9347.17	94.81	0.30( 0.29)	0.98	11209.1	12201.00
8	9384.46	98.70	0.30( 0.29)	0.98	11677.0	12111.00
9	9366.85	101.16	0.30( 0.29)	0.98	11977.9	12231.00
10	9319.62	103.97	0.30( 0.29)	0.98	12282.5	12101.10
11	9299.62	104.81	0.30( 0.29)	0.98	12363.8	12261.00
12	8916.90	115.67	0.30( 0.29)	0.98	13112.3	12010.00
13	8576.29	123.92	0.30( 0.29)	0.98	13237.1	12000.00

TOTAL AREA(ACRES) = 13237.1

\*\*\*\*\*

FLOW PROCESS FROM NODE 12526.00 TO NODE 12527.00 IS CODE = 14.0  
 -----

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	7548.90	65.18	0.30( 0.30)	0.99	6431.3	12500.00
2	8477.91	78.32	0.30( 0.30)	0.99	8413.1	12300.00
3	8593.88	79.61	0.30( 0.30)	0.98	8691.0	12330.00
4	8774.49	82.20	0.30( 0.30)	0.98	9202.6	12410.00
5	9008.69	86.22	0.30( 0.29)	0.98	9924.8	12400.00
6	9221.87	90.84	0.30( 0.29)	0.98	10622.1	12211.00
7	9347.17	94.81	0.30( 0.29)	0.98	11209.1	12201.00
8	9384.46	98.70	0.30( 0.29)	0.98	11677.0	12111.00
9	9366.85	101.16	0.30( 0.29)	0.98	11977.9	12231.00
10	9319.62	103.97	0.30( 0.29)	0.98	12282.5	12101.10
11	9299.62	104.81	0.30( 0.29)	0.98	12363.8	12261.00
12	8916.90	115.67	0.30( 0.29)	0.98	13112.3	12010.00
13	8576.29	123.92	0.30( 0.29)	0.98	13237.1	12000.00

TOTAL AREA(ACRES) = 13237.1

\*\*\*\*\*

FLOW PROCESS FROM NODE 11841.00 TO NODE 12527.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	7548.90	65.18	1.288	0.30 ( 0.30)	0.99	6431.3	12500.00
2	8477.91	78.32	1.200	0.30 ( 0.30)	0.99	8413.1	12300.00
3	8593.88	79.61	1.192	0.30 ( 0.30)	0.98	8691.0	12330.00
4	8774.49	82.20	1.174	0.30 ( 0.30)	0.98	9202.6	12410.00
5	9008.69	86.22	1.147	0.30 ( 0.29)	0.98	9924.8	12400.00
6	9221.87	90.84	1.118	0.30 ( 0.29)	0.98	10622.1	12211.00
7	9347.17	94.81	1.100	0.30 ( 0.29)	0.98	11209.1	12201.00
8	9384.46	98.70	1.083	0.30 ( 0.29)	0.98	11677.0	12111.00
9	9366.85	101.16	1.071	0.30 ( 0.29)	0.98	11977.9	12231.00
10	9319.62	103.97	1.059	0.30 ( 0.29)	0.98	12282.5	12101.10
11	9299.62	104.81	1.055	0.30 ( 0.29)	0.98	12363.8	12261.00
12	8916.90	115.67	1.006	0.30 ( 0.29)	0.98	13112.3	12010.00
13	8576.29	123.92	0.976	0.30 ( 0.29)	0.98	13237.1	12000.00

LONGEST FLOWPATH FROM NODE 12000.00 TO NODE 12527.00 = 77156.98 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	22054.84	36.58	1.735	0.30 ( 0.30)	1.00	7926.9	11831.00
2	22725.41	39.13	1.669	0.30 ( 0.30)	1.00	8505.3	11801.00
3	25134.97	47.53	1.477	0.30 ( 0.30)	1.00	10691.9	11500.00
4	25502.09	49.16	1.440	0.30 ( 0.30)	1.00	11329.9	11530.00
5	26360.19	53.71	1.385	0.30 ( 0.30)	1.00	13011.5	11701.00
6	26779.09	55.76	1.365	0.30 ( 0.30)	1.00	13818.6	11000.00
7	29291.04	65.53	1.286	0.30 ( 0.30)	1.00	18866.7	11330.00
8	30114.29	72.03	1.242	0.30 ( 0.30)	1.00	22317.4	11130.00
9	29645.18	80.38	1.186	0.30 ( 0.30)	1.00	25368.4	11620.00
10	29500.26	82.66	1.171	0.30 ( 0.30)	1.00	26144.7	11600.00
11	29052.00	88.60	1.131	0.30 ( 0.30)	1.00	27897.1	11111.00
12	28910.69	90.07	1.122	0.30 ( 0.30)	1.00	28280.6	11101.00
13	28571.47	94.86	1.100	0.30 ( 0.30)	1.00	29290.8	10710.00
14	28361.22	96.69	1.092	0.30 ( 0.30)	1.00	29594.6	10410.00
15	27934.24	101.05	1.072	0.30 ( 0.30)	1.00	30249.2	10700.00
16	27383.49	107.91	1.041	0.30 ( 0.30)	1.00	31215.0	10400.00
17	27137.20	109.87	1.032	0.30 ( 0.30)	1.00	31440.4	10200.00
18	26251.80	115.74	1.005	0.30 ( 0.30)	1.00	32001.9	10300.00
19	25289.37	121.31	0.983	0.30 ( 0.30)	1.00	32223.4	10210.00
20	23048.07	146.70	0.916	0.30 ( 0.30)	1.00	32916.6	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12527.00 = 97868.13 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28196.41	36.58	1.735	0.30 ( 0.30)	0.99	11536.0	11831.00
2	28997.24	39.13	1.669	0.30 ( 0.30)	0.99	12366.4	11801.00
3	31685.73	47.53	1.477	0.30 ( 0.30)	0.99	15382.2	11500.00
4	32066.13	49.16	1.440	0.30 ( 0.30)	0.99	16181.3	11530.00
5	33185.00	53.71	1.385	0.30 ( 0.30)	0.99	18311.7	11701.00
6	33733.33	55.76	1.365	0.30 ( 0.30)	0.99	19320.5	11000.00
7	36747.98	65.18	1.288	0.30 ( 0.30)	0.99	25113.1	12500.00

8	36865.25	65.53	1.286	0.30 ( 0.30)	0.99	25351.9	11330.00
9	38148.02	72.03	1.242	0.30 ( 0.30)	0.99	29783.0	11130.00
10	38239.23	78.32	1.200	0.30 ( 0.30)	0.99	33026.2	12300.00
11	38282.50	79.61	1.192	0.30 ( 0.30)	0.99	33776.9	12330.00
12	38292.96	80.38	1.186	0.30 ( 0.30)	0.99	34212.1	11620.00
13	38303.77	82.20	1.174	0.30 ( 0.30)	0.99	35191.7	12410.00
14	38301.27	82.66	1.171	0.30 ( 0.30)	0.99	35429.0	11600.00
15	38240.18	86.22	1.147	0.30 ( 0.30)	0.99	37120.1	12400.00
16	38170.52	88.60	1.131	0.30 ( 0.30)	0.99	38181.1	11111.00
17	38097.30	90.07	1.122	0.30 ( 0.30)	0.99	38787.4	11101.00
18	38078.45	90.84	1.118	0.30 ( 0.30)	0.99	39063.9	12211.00
19	37922.34	94.81	1.100	0.30 ( 0.30)	0.99	40488.9	12201.00
20	37919.14	94.86	1.100	0.30 ( 0.30)	0.99	40506.2	10710.00
21	37726.41	96.69	1.092	0.30 ( 0.30)	0.99	41029.8	10410.00
22	37548.75	98.70	1.083	0.30 ( 0.30)	0.99	41573.6	12111.00
23	37301.90	101.05	1.072	0.30 ( 0.30)	0.99	42213.4	10700.00
24	37292.05	101.16	1.071	0.30 ( 0.30)	0.99	42243.0	12231.00
25	37019.30	103.97	1.059	0.30 ( 0.30)	0.99	42943.0	12101.10
26	36931.54	104.81	1.055	0.30 ( 0.30)	0.99	43143.1	12261.00
27	36574.05	107.91	1.041	0.30 ( 0.30)	0.99	43792.1	10400.00
28	36258.75	109.87	1.032	0.30 ( 0.30)	0.99	44152.4	10200.00
29	35179.73	115.67	1.006	0.30 ( 0.30)	0.99	45107.2	12010.00
30	35165.68	115.74	1.005	0.30 ( 0.30)	0.99	45115.3	10300.00
31	33973.56	121.31	0.983	0.30 ( 0.30)	0.99	45420.9	10210.00
32	33634.95	123.92	0.976	0.30 ( 0.30)	0.99	45531.8	12000.00
33	30874.90	146.70	0.916	0.30 ( 0.30)	0.99	46153.7	10100.00

TOTAL AREA (ACRES) = 46153.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 38303.77 Tc (MIN.) = 82.200

EFFECTIVE AREA (ACRES) = 35191.74 AREA-AVERAGED Fm (INCH/HR) = 0.30

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA (ACRES) = 46153.7

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12527.00 = 97868.13 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12527.00 TO NODE 11929.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 347.47 DOWNSTREAM (FEET) = 341.63

CHANNEL LENGTH THRU SUBAREA (FEET) = 532.38 CHANNEL SLOPE = 0.0110

GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT (FEET) = 9.79

\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.170

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	14.37	0.30	0.987	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.987

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 38309.42

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 15.73

AVERAGE FLOW DEPTH (FEET) = 9.79 TRAVEL TIME (MIN.) = 0.56

Tc (MIN.) = 82.76

SUBAREA AREA (ACRES) = 14.37 SUBAREA RUNOFF (CFS) = 11.31

EFFECTIVE AREA(ACRES) = 35206.11 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 46168.0 PEAK FLOW RATE(CFS) = 38303.77  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 9.79

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 9.79 FLOW VELOCITY(FEET/SEC.) = 15.72  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28196.41	37.20	1.719	0.30( 0.30)	0.99	11550.4	11831.00
2	28997.24	39.75	1.653	0.30( 0.30)	0.99	12380.8	11801.00
3	31685.73	48.13	1.463	0.30( 0.30)	0.99	15396.6	11500.00
4	32066.13	49.76	1.426	0.30( 0.30)	0.99	16195.7	11530.00
5	33185.00	54.30	1.379	0.30( 0.30)	0.99	18326.0	11701.00
6	33733.33	56.35	1.359	0.30( 0.30)	0.99	19334.9	11000.00
7	36747.98	65.75	1.284	0.30( 0.30)	0.99	25127.5	12500.00
8	36865.25	66.10	1.282	0.30( 0.30)	0.99	25366.3	11330.00
9	38148.02	72.60	1.239	0.30( 0.30)	0.99	29797.3	11130.00
10	38239.23	78.88	1.197	0.30( 0.30)	0.99	33040.6	12300.00
11	38282.50	80.17	1.188	0.30( 0.30)	0.99	33791.3	12330.00
12	38292.96	80.95	1.183	0.30( 0.30)	0.99	34226.5	11620.00
13	38303.77	82.76	1.170	0.30( 0.30)	0.99	35206.1	12410.00
14	38301.27	83.22	1.167	0.30( 0.30)	0.99	35443.4	11600.00
15	38240.18	86.78	1.144	0.30( 0.30)	0.99	37134.5	12400.00
16	38170.52	89.16	1.128	0.30( 0.30)	0.99	38195.5	11111.00
17	38097.30	90.64	1.119	0.30( 0.30)	0.99	38801.7	11101.00
18	38078.45	91.40	1.116	0.30( 0.30)	0.99	39078.2	12211.00
19	37922.34	95.38	1.098	0.30( 0.30)	0.99	40503.2	12201.00
20	37919.14	95.43	1.097	0.30( 0.30)	0.99	40520.6	10710.00
21	37726.41	97.26	1.089	0.30( 0.30)	0.99	41044.2	10410.00
22	37548.75	99.27	1.080	0.30( 0.30)	0.99	41587.9	12111.00
23	37301.90	101.62	1.069	0.30( 0.30)	0.99	42227.7	10700.00
24	37292.05	101.73	1.069	0.30( 0.30)	0.99	42257.4	12231.00
25	37019.30	104.54	1.056	0.30( 0.30)	0.99	42957.4	12101.10
26	36931.54	105.38	1.052	0.30( 0.30)	0.99	43157.5	12261.00
27	36574.05	108.48	1.038	0.30( 0.30)	0.99	43806.5	10400.00
28	36258.75	110.44	1.029	0.30( 0.30)	0.99	44166.8	10200.00
29	35179.73	116.25	1.003	0.30( 0.30)	0.99	45121.6	12010.00
30	35165.68	116.32	1.003	0.30( 0.30)	0.99	45129.7	10300.00
31	33973.56	121.90	0.981	0.30( 0.30)	0.99	45435.3	10210.00
32	33634.95	124.51	0.974	0.30( 0.30)	0.99	45546.2	12000.00
33	30874.90	147.31	0.915	0.30( 0.30)	0.99	46168.0	10100.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE(CFS) = 38303.77 Tc(MIN.) = 82.76  
 AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 35206.11

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 11928.00 TO NODE 11929.00 IS CODE = 11  
 -----  
 >>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<  
 =====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28196.41	37.20	1.719	0.30( 0.30)	0.99	11550.4	11831.00
2	28997.24	39.75	1.653	0.30( 0.30)	0.99	12380.8	11801.00
3	31685.73	48.13	1.463	0.30( 0.30)	0.99	15396.6	11500.00
4	32066.13	49.76	1.426	0.30( 0.30)	0.99	16195.7	11530.00
5	33185.00	54.30	1.379	0.30( 0.30)	0.99	18326.0	11701.00
6	33733.33	56.35	1.359	0.30( 0.30)	0.99	19334.9	11000.00
7	36747.98	65.75	1.284	0.30( 0.30)	0.99	25127.5	12500.00
8	36865.25	66.10	1.282	0.30( 0.30)	0.99	25366.3	11330.00
9	38148.02	72.60	1.239	0.30( 0.30)	0.99	29797.3	11130.00
10	38239.23	78.88	1.197	0.30( 0.30)	0.99	33040.6	12300.00
11	38282.50	80.17	1.188	0.30( 0.30)	0.99	33791.3	12330.00
12	38292.96	80.95	1.183	0.30( 0.30)	0.99	34226.5	11620.00
13	38303.77	82.76	1.170	0.30( 0.30)	0.99	35206.1	12410.00
14	38301.27	83.22	1.167	0.30( 0.30)	0.99	35443.4	11600.00
15	38240.18	86.78	1.144	0.30( 0.30)	0.99	37134.5	12400.00
16	38170.52	89.16	1.128	0.30( 0.30)	0.99	38195.5	11111.00
17	38097.30	90.64	1.119	0.30( 0.30)	0.99	38801.7	11101.00
18	38078.45	91.40	1.116	0.30( 0.30)	0.99	39078.2	12211.00
19	37922.34	95.38	1.098	0.30( 0.30)	0.99	40503.2	12201.00
20	37919.14	95.43	1.097	0.30( 0.30)	0.99	40520.6	10710.00
21	37726.41	97.26	1.089	0.30( 0.30)	0.99	41044.2	10410.00
22	37548.75	99.27	1.080	0.30( 0.30)	0.99	41587.9	12111.00
23	37301.90	101.62	1.069	0.30( 0.30)	0.99	42227.7	10700.00
24	37292.05	101.73	1.069	0.30( 0.30)	0.99	42257.4	12231.00
25	37019.30	104.54	1.056	0.30( 0.30)	0.99	42957.4	12101.10
26	36931.54	105.38	1.052	0.30( 0.30)	0.99	43157.5	12261.00
27	36574.05	108.48	1.038	0.30( 0.30)	0.99	43806.5	10400.00
28	36258.75	110.44	1.029	0.30( 0.30)	0.99	44166.8	10200.00
29	35179.73	116.25	1.003	0.30( 0.30)	0.99	45121.6	12010.00
30	35165.68	116.32	1.003	0.30( 0.30)	0.99	45129.7	10300.00
31	33973.56	121.90	0.981	0.30( 0.30)	0.99	45435.3	10210.00
32	33634.95	124.51	0.974	0.30( 0.30)	0.99	45546.2	12000.00
33	30874.90	147.31	0.915	0.30( 0.30)	0.99	46168.0	10100.00

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2817.53	16.62	2.837	0.30( 0.30)	1.00	1042.9	40200.00
2	3188.68	28.73	1.961	0.30( 0.30)	1.00	1886.8	40120.00
3	3208.47	30.53	1.889	0.30( 0.30)	1.00	2004.8	40100.00
4	3278.35	58.23	1.340	0.30( 0.30)	1.00	3335.7	11900.00
5	3262.97	58.67	1.336	0.30( 0.30)	1.00	3343.7	11910.00

LONGEST FLOWPATH FROM NODE 11910.00 TO NODE 11929.00 = 30683.27 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25325.49	16.62	2.837	0.30( 0.30)	0.99	6202.2	40200.00
2	28681.72	28.73	1.961	0.30( 0.30)	0.99	10808.2	40120.00
3	29130.01	30.53	1.889	0.30( 0.30)	0.99	11484.3	40100.00
4	31421.70	37.20	1.719	0.30( 0.30)	0.99	13875.7	11831.00
5	32228.96	39.75	1.653	0.30( 0.30)	0.99	14828.5	11801.00
6	34938.61	48.13	1.463	0.30( 0.30)	0.99	18247.3	11500.00



7	35323.13	49.76	1.426	0.30	( 0.30)	0.99	19124.6	11530.00
8	36453.45	54.30	1.379	0.30	( 0.30)	0.99	21473.2	11701.00
9	37006.93	56.35	1.359	0.30	( 0.30)	0.99	22580.2	11000.00
10	37614.68	58.23	1.340	0.30	( 0.30)	0.99	23829.3	11900.00
11	37741.02	58.67	1.336	0.30	( 0.30)	0.99	24109.6	11910.00
12	39848.71	65.75	1.284	0.30	( 0.30)	0.99	28471.2	12500.00
13	39958.45	66.10	1.282	0.30	( 0.30)	0.99	28710.0	11330.00
14	41104.32	72.60	1.239	0.30	( 0.30)	0.99	33141.0	11130.00
15	41063.09	78.88	1.197	0.30	( 0.30)	0.99	36384.3	12300.00
16	41079.09	80.17	1.188	0.30	( 0.30)	0.99	37135.0	12330.00
17	41073.26	80.95	1.183	0.30	( 0.30)	0.99	37570.2	11620.00
18	41045.75	82.76	1.170	0.30	( 0.30)	0.99	38549.8	12410.00
19	41033.65	83.22	1.167	0.30	( 0.30)	0.99	38787.1	11600.00
20	40897.43	86.78	1.144	0.30	( 0.30)	0.99	40478.2	12400.00
21	40777.58	89.16	1.128	0.30	( 0.30)	0.99	41539.2	11111.00
22	40677.61	90.64	1.119	0.30	( 0.30)	0.99	42145.4	11101.00
23	40647.86	91.40	1.116	0.30	( 0.30)	0.99	42421.9	12211.00
24	40435.07	95.38	1.098	0.30	( 0.30)	0.99	43847.0	12201.00
25	40431.12	95.43	1.097	0.30	( 0.30)	0.99	43864.3	10710.00
26	40212.33	97.26	1.089	0.30	( 0.30)	0.99	44387.9	10410.00
27	40005.99	99.27	1.080	0.30	( 0.30)	0.99	44931.6	12111.00
28	39725.64	101.62	1.069	0.30	( 0.30)	0.99	45571.5	10700.00
29	39714.19	101.73	1.069	0.30	( 0.30)	0.99	45601.1	12231.00
30	39401.35	104.54	1.056	0.30	( 0.30)	0.99	46301.1	12101.10
31	39301.54	105.38	1.052	0.30	( 0.30)	0.99	46501.2	12261.00
32	38899.90	108.48	1.038	0.30	( 0.30)	0.99	47150.2	10400.00
33	38556.64	110.44	1.029	0.30	( 0.30)	0.99	47510.5	10200.00
34	37394.73	116.25	1.003	0.30	( 0.30)	0.99	48465.3	12010.00
35	37379.62	116.32	1.003	0.30	( 0.30)	0.99	48473.4	10300.00
36	36119.47	121.90	0.981	0.30	( 0.30)	0.99	48779.0	10210.00
37	35759.33	124.51	0.974	0.30	( 0.30)	0.99	48889.9	12000.00
38	32811.61	147.31	0.915	0.30	( 0.30)	0.99	49511.8	10100.00

TOTAL AREA (ACRES) = 49511.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 41104.32 Tc (MIN.) = 72.598  
EFFECTIVE AREA (ACRES) = 33141.04 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA (ACRES) = 49511.8  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 11929.00 = 98400.52 FEET.

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 49511.8 TC (MIN.) = 72.60  
EFFECTIVE AREA (ACRES) = 33141.04 AREA-AVERAGED Fm (INCH/HR) = 0.30  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.994  
PEAK FLOW RATE (CFS) = 41104.32

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25325.49	16.62	2.837	0.30 ( 0.30)	0.99	6202.2	40200.00
2	28681.72	28.73	1.961	0.30 ( 0.30)	0.99	10808.2	40120.00
3	29130.01	30.53	1.889	0.30 ( 0.30)	0.99	11484.3	40100.00
4	31421.70	37.20	1.719	0.30 ( 0.30)	0.99	13875.7	11831.00
5	32228.96	39.75	1.653	0.30 ( 0.30)	0.99	14828.5	11801.00
6	34938.61	48.13	1.463	0.30 ( 0.30)	0.99	18247.3	11500.00
7	35323.13	49.76	1.426	0.30 ( 0.30)	0.99	19124.6	11530.00
8	36453.45	54.30	1.379	0.30 ( 0.30)	0.99	21473.2	11701.00

9	37006.93	56.35	1.359	0.30	( 0.30)	0.99	22580.2	11000.00
10	37614.68	58.23	1.340	0.30	( 0.30)	0.99	23829.3	11900.00
11	37741.02	58.67	1.336	0.30	( 0.30)	0.99	24109.6	11910.00
12	39848.71	65.75	1.284	0.30	( 0.30)	0.99	28471.2	12500.00
13	39958.45	66.10	1.282	0.30	( 0.30)	0.99	28710.0	11330.00
14	41104.32	72.60	1.239	0.30	( 0.30)	0.99	33141.0	11130.00
15	41063.09	78.88	1.197	0.30	( 0.30)	0.99	36384.3	12300.00
16	41079.09	80.17	1.188	0.30	( 0.30)	0.99	37135.0	12330.00
17	41073.26	80.95	1.183	0.30	( 0.30)	0.99	37570.2	11620.00
18	41045.75	82.76	1.170	0.30	( 0.30)	0.99	38549.8	12410.00
19	41033.65	83.22	1.167	0.30	( 0.30)	0.99	38787.1	11600.00
20	40897.43	86.78	1.144	0.30	( 0.30)	0.99	40478.2	12400.00
21	40777.58	89.16	1.128	0.30	( 0.30)	0.99	41539.2	11111.00
22	40677.61	90.64	1.119	0.30	( 0.30)	0.99	42145.4	11101.00
23	40647.86	91.40	1.116	0.30	( 0.30)	0.99	42421.9	12211.00
24	40435.07	95.38	1.098	0.30	( 0.30)	0.99	43847.0	12201.00
25	40431.12	95.43	1.097	0.30	( 0.30)	0.99	43864.3	10710.00
26	40212.33	97.26	1.089	0.30	( 0.30)	0.99	44387.9	10410.00
27	40005.99	99.27	1.080	0.30	( 0.30)	0.99	44931.6	12111.00
28	39725.64	101.62	1.069	0.30	( 0.30)	0.99	45571.5	10700.00
29	39714.19	101.73	1.069	0.30	( 0.30)	0.99	45601.1	12231.00
30	39401.35	104.54	1.056	0.30	( 0.30)	0.99	46301.1	12101.10
31	39301.54	105.38	1.052	0.30	( 0.30)	0.99	46501.2	12261.00
32	38899.90	108.48	1.038	0.30	( 0.30)	0.99	47150.2	10400.00
33	38556.64	110.44	1.029	0.30	( 0.30)	0.99	47510.5	10200.00
34	37394.73	116.25	1.003	0.30	( 0.30)	0.99	48465.3	12010.00
35	37379.62	116.32	1.003	0.30	( 0.30)	0.99	48473.4	10300.00
36	36119.47	121.90	0.981	0.30	( 0.30)	0.99	48779.0	10210.00
37	35759.33	124.51	0.974	0.30	( 0.30)	0.99	48889.9	12000.00
38	32811.61	147.31	0.915	0.30	( 0.30)	0.99	49511.8	10100.00

=====  
END OF RATIONAL METHOD ANALYSIS  
=====



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S26- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 100-YR RM EV APRIL 2019 CCHIUI \*  
\*\*\*\*\*

FILE NAME: RI00EV26.DAT  
TIME/DATE OF STUDY: 08:50 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 100.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 6.102
- 2) 10.00; 3.901
- 3) 15.00; 3.005
- 4) 20.00; 2.465
- 5) 25.00; 2.129
- 6) 30.00; 1.900
- 7) 40.00; 1.644
- 8) 50.00; 1.419
- 9) 60.00; 1.320
- 10) 90.00; 1.119
- 11) 120.00; 0.983
- 12) 180.00; 0.826
- 13) 360.00; 0.617
- 14) 1200.00; 0.271

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI00EV19.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25325.49	16.62	0.30 ( 0.30)	0.99	6202.2	40200.00
2	29130.01	30.53	0.30 ( 0.30)	0.99	11484.3	40100.00
3	31421.70	37.20	0.30 ( 0.30)	0.99	13875.7	11831.00
4	32228.96	39.75	0.30 ( 0.30)	0.99	14828.5	11801.00
5	35323.13	49.76	0.30 ( 0.30)	0.99	19124.6	11530.00
6	37741.02	58.67	0.30 ( 0.30)	0.99	24109.6	11910.00
7	39958.45	66.10	0.30 ( 0.30)	0.99	28710.0	11330.00
8	41104.32	72.60	0.30 ( 0.30)	0.99	33141.0	11130.00
9	41079.09	80.17	0.30 ( 0.30)	0.99	37135.0	12330.00
10	41045.75	82.76	0.30 ( 0.30)	0.99	38549.8	12410.00
11	40897.43	86.78	0.30 ( 0.30)	0.99	40478.2	12400.00
12	40435.07	95.38	0.30 ( 0.30)	0.99	43847.0	12201.00
13	40005.99	99.27	0.30 ( 0.30)	0.99	44931.6	12111.00
14	39725.64	101.62	0.30 ( 0.30)	0.99	45571.5	10700.00
15	39401.35	104.54	0.30 ( 0.30)	0.99	46301.1	12101.10
16	38899.90	108.48	0.30 ( 0.30)	0.99	47150.2	10400.00
17	37394.73	116.25	0.30 ( 0.30)	0.99	48465.3	12010.00
18	36119.47	121.90	0.30 ( 0.30)	0.99	48779.0	10210.00
19	35759.33	124.51	0.30 ( 0.30)	0.99	48889.9	12000.00
20	32811.61	147.31	0.30 ( 0.30)	0.99	49511.8	10100.00
TOTAL AREA (ACRES) =						49511.8

\*\*\*\*\*  
FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25325.49	16.62	0.30 ( 0.30)	0.99	6202.2	40200.00
2	29130.01	30.53	0.30 ( 0.30)	0.99	11484.3	40100.00
3	31421.70	37.20	0.30 ( 0.30)	0.99	13875.7	11831.00
4	32228.96	39.75	0.30 ( 0.30)	0.99	14828.5	11801.00
5	35323.13	49.76	0.30 ( 0.30)	0.99	19124.6	11530.00
6	37741.02	58.67	0.30 ( 0.30)	0.99	24109.6	11910.00
7	39958.45	66.10	0.30 ( 0.30)	0.99	28710.0	11330.00
8	41104.32	72.60	0.30 ( 0.30)	0.99	33141.0	11130.00
9	41079.09	80.17	0.30 ( 0.30)	0.99	37135.0	12330.00
10	41045.75	82.76	0.30 ( 0.30)	0.99	38549.8	12410.00
11	40897.43	86.78	0.30 ( 0.30)	0.99	40478.2	12400.00
12	40435.07	95.38	0.30 ( 0.30)	0.99	43847.0	12201.00
13	40005.99	99.27	0.30 ( 0.30)	0.99	44931.6	12111.00

14 39725.64 101.62 0.30( 0.30) 0.99 45571.5 10700.00  
 15 39401.35 104.54 0.30( 0.30) 0.99 46301.1 12101.10  
 16 38899.90 108.48 0.30( 0.30) 0.99 47150.2 10400.00  
 17 37394.73 116.25 0.30( 0.30) 0.99 48465.3 12010.00  
 18 36119.47 121.90 0.30( 0.30) 0.99 48779.0 10210.00  
 19 35759.33 124.51 0.30( 0.30) 0.99 48889.9 12000.00  
 20 32811.61 147.31 0.30( 0.30) 0.99 49511.8 10100.00  
 TOTAL AREA(ACRES) = 49511.8

\*\*\*\*\*

FLOW PROCESS FROM NODE 11929.00 TO NODE 11929.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 11929.00 TO NODE 12601.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 341.63 DOWNSTREAM(FEET) = 325.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1467.93 CHANNEL SLOPE = 0.0113  
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT(FEET) = 8.57

\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.227

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	14.11	0.30	0.700	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.700

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 41110.79

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 19.75

AVERAGE FLOW DEPTH(FEET) = 8.57 TRAVEL TIME(MIN.) = 1.24

Tc(MIN.) = 73.84

SUBAREA AREA(ACRES) = 14.11 SUBAREA RUNOFF(CFS) = 12.92

EFFECTIVE AREA(ACRES) = 33155.15 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 49525.9 PEAK FLOW RATE(CFS) = 41104.32

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT(FEET) = 8.57

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 8.57 FLOW VELOCITY(FEET/SEC.) = 19.74

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25325.49	18.07	2.673	0.30( 0.30)	0.99	6216.3	40200.00
2	29130.01	31.92	1.851	0.30( 0.30)	0.99	11498.4	40100.00
3	31421.70	38.56	1.681	0.30( 0.30)	0.99	13889.8	11831.00
4	32228.96	41.09	1.619	0.30( 0.30)	0.99	14842.6	11801.00
5	35323.13	51.07	1.408	0.30( 0.30)	0.99	19138.8	11530.00

6	37741.02	59.94	1.321	0.30( 0.30)	0.99	24123.7	11910.00
7	39958.45	67.36	1.271	0.30( 0.30)	0.99	28724.1	11330.00
8	41104.32	73.84	1.227	0.30( 0.30)	0.99	33155.2	11130.00
9	41079.09	81.41	1.177	0.30( 0.30)	0.99	37149.1	12330.00
10	41045.75	84.00	1.159	0.30( 0.30)	0.99	38563.9	12410.00
11	40897.43	88.02	1.132	0.30( 0.30)	0.99	40492.3	12400.00
12	40435.07	96.62	1.089	0.30( 0.30)	0.99	43861.1	12201.00
13	40005.99	100.52	1.071	0.30( 0.30)	0.99	44945.8	12111.00
14	39725.64	102.87	1.061	0.30( 0.30)	0.99	45585.6	10700.00
15	39401.35	105.80	1.047	0.30( 0.30)	0.99	46315.2	12101.10
16	38899.90	109.74	1.030	0.30( 0.30)	0.99	47164.3	10400.00
17	37394.73	117.53	0.994	0.30( 0.30)	0.99	48479.4	12010.00
18	36119.47	123.19	0.975	0.30( 0.30)	0.99	48793.1	10210.00
19	35759.33	125.81	0.968	0.30( 0.30)	0.99	48904.0	12000.00
20	32811.61	148.64	0.908	0.30( 0.30)	0.99	49525.9	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 41104.32 Tc(MIN.) = 73.84

AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 33155.15

\*\*\*\*\*

FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<<

PEAK FLOWRATE TABLE FILE NAME: 3000EVRL.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	111.41	16.41	0.30( 0.30)	0.98	48.4	600.00
TOTAL AREA(ACRES) =			48.4			

\*\*\*\*\*

FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25325.49	18.07	2.673	0.30( 0.30)	0.99	6216.3	40200.00
2	29130.01	31.92	1.851	0.30( 0.30)	0.99	11498.4	40100.00
3	31421.70	38.56	1.681	0.30( 0.30)	0.99	13889.8	11831.00
4	32228.96	41.09	1.619	0.30( 0.30)	0.99	14842.6	11801.00
5	35323.13	51.07	1.408	0.30( 0.30)	0.99	19138.8	11530.00
6	37741.02	59.94	1.321	0.30( 0.30)	0.99	24123.7	11910.00
7	39958.45	67.36	1.271	0.30( 0.30)	0.99	28724.1	11330.00
8	41104.32	73.84	1.227	0.30( 0.30)	0.99	33155.2	11130.00
9	41079.09	81.41	1.177	0.30( 0.30)	0.99	37149.1	12330.00
10	41045.75	84.00	1.159	0.30( 0.30)	0.99	38563.9	12410.00
11	40897.43	88.02	1.132	0.30( 0.30)	0.99	40492.3	12400.00
12	40435.07	96.62	1.089	0.30( 0.30)	0.99	43861.1	12201.00
13	40005.99	100.52	1.071	0.30( 0.30)	0.99	44945.8	12111.00
14	39725.64	102.87	1.061	0.30( 0.30)	0.99	45585.6	10700.00
15	39401.35	105.80	1.047	0.30( 0.30)	0.99	46315.2	12101.10
16	38899.90	109.74	1.030	0.30( 0.30)	0.99	47164.3	10400.00
17	37394.73	117.53	0.994	0.30( 0.30)	0.99	48479.4	12010.00

18 36119.47 123.19 0.975 0.30( 0.30) 0.99 48793.1 10210.00  
 19 35759.33 125.81 0.968 0.30( 0.30) 0.99 48904.0 12000.00  
 20 32811.61 148.64 0.908 0.30( 0.30) 0.99 49525.9 10100.00  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	111.41	16.41	2.853	0.30( 0.30)	0.98	48.4	600.00

LONGEST FLOWPATH FROM NODE 600.00 TO NODE 12601.00 = 4850.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24844.89	16.41	2.853	0.30( 0.30)	0.99	5692.3	600.00
2	25429.06	18.07	2.673	0.30( 0.30)	0.99	6264.7	40200.00
3	29197.78	31.92	1.851	0.30( 0.30)	0.99	11546.8	40100.00
4	31482.07	38.56	1.681	0.30( 0.30)	0.99	13938.2	11831.00
5	32286.65	41.09	1.619	0.30( 0.30)	0.99	14891.0	11801.00
6	35371.62	51.07	1.408	0.30( 0.30)	0.99	19187.2	11530.00
7	37785.69	59.94	1.321	0.30( 0.30)	0.99	24172.1	11910.00
8	40000.95	67.36	1.271	0.30( 0.30)	0.99	28772.5	11330.00
9	41144.93	73.84	1.227	0.30( 0.30)	0.99	33203.6	11130.00
10	41117.48	81.41	1.177	0.30( 0.30)	0.99	37197.5	12330.00
11	41083.38	84.00	1.159	0.30( 0.30)	0.99	38612.3	12410.00
12	40933.89	88.02	1.132	0.30( 0.30)	0.99	40540.7	12400.00
13	40469.65	96.62	1.089	0.30( 0.30)	0.99	43909.5	12201.00
14	40039.80	100.52	1.071	0.30( 0.30)	0.99	44994.2	12111.00
15	39758.98	102.87	1.061	0.30( 0.30)	0.99	45634.0	10700.00
16	39434.11	105.80	1.047	0.30( 0.30)	0.99	46363.6	12101.10
17	38931.89	109.74	1.030	0.30( 0.30)	0.99	47212.7	10400.00
18	37425.18	117.53	0.994	0.30( 0.30)	0.99	48527.8	12010.00
19	36149.07	123.19	0.975	0.30( 0.30)	0.99	48841.5	10210.00
20	35788.63	125.81	0.968	0.30( 0.30)	0.99	48952.4	12000.00
21	32838.30	148.64	0.908	0.30( 0.30)	0.99	49574.3	10100.00

TOTAL AREA (ACRES) = 49574.3

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 41144.93 Tc(MIN.) = 73.837  
 EFFECTIVE AREA(ACRES) = 33203.55 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 49574.3  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12601.00 = 99868.45 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12601.00 TO NODE 12601.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12601.00 TO NODE 12602.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 325.00 DOWNSTREAM(FEET) = 313.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1377.46 CHANNEL SLOPE = 0.0087

GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 9.24  
 CHANNEL FLOW THRU SUBAREA(CFS) = 41144.93  
 FLOW VELOCITY(FEET/SEC.) = 18.08 FLOW DEPTH(FEET) = 9.24  
 TRAVEL TIME(MIN.) = 1.27 Tc(MIN.) = 75.11  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12602.00 = 101245.91 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24844.89	17.91	2.690	0.30( 0.30)	0.99	5692.3	600.00
2	25429.06	19.57	2.512	0.30( 0.30)	0.99	6264.7	40200.00
3	29197.78	33.34	1.814	0.30( 0.30)	0.99	11546.8	40100.00
4	31482.07	39.94	1.645	0.30( 0.30)	0.99	13938.2	11831.00
5	32286.65	42.47	1.588	0.30( 0.30)	0.99	14891.0	11801.00
6	35371.62	52.40	1.395	0.30( 0.30)	0.99	19187.2	11530.00
7	37785.69	61.25	1.312	0.30( 0.30)	0.99	24172.1	11910.00
8	40000.95	68.64	1.262	0.30( 0.30)	0.99	28772.5	11330.00
9	41144.93	75.11	1.219	0.30( 0.30)	0.99	33203.6	11130.00
10	41117.48	82.68	1.168	0.30( 0.30)	0.99	37197.5	12330.00
11	41083.38	85.27	1.151	0.30( 0.30)	0.99	38612.3	12410.00
12	40933.89	89.30	1.124	0.30( 0.30)	0.99	40540.7	12400.00
13	40469.65	97.90	1.083	0.30( 0.30)	0.99	43909.5	12201.00
14	40039.80	101.80	1.066	0.30( 0.30)	0.99	44994.2	12111.00
15	39758.98	104.15	1.055	0.30( 0.30)	0.99	45634.0	10700.00
16	39434.11	107.08	1.042	0.30( 0.30)	0.99	46363.6	12101.10
17	38931.89	111.04	1.024	0.30( 0.30)	0.99	47212.7	10400.00
18	37425.18	118.84	0.988	0.30( 0.30)	0.99	48527.8	12010.00
19	36149.07	124.51	0.971	0.30( 0.30)	0.99	48841.5	10210.00
20	35788.63	127.14	0.964	0.30( 0.30)	0.99	48952.4	12000.00
21	32838.30	150.01	0.904	0.30( 0.30)	0.99	49574.3	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 41144.93 Tc(MIN.) = 75.11  
 AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 33203.55

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12602.00 TO NODE 12603.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 313.00 DOWNSTREAM(FEET) = 310.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 312.40 CHANNEL SLOPE = 0.0096  
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 8.99  
 CHANNEL FLOW THRU SUBAREA(CFS) = 41144.93  
 FLOW VELOCITY(FEET/SEC.) = 18.68 FLOW DEPTH(FEET) = 8.99  
 TRAVEL TIME(MIN.) = 0.28 Tc(MIN.) = 75.39  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.30 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24844.89	18.24	2.655	0.30( 0.30)	0.99	5692.3	600.00
2	25429.06	19.89	2.477	0.30( 0.30)	0.99	6264.7	40200.00

3	29197.78	33.66	1.806	0.30	( 0.30)	0.99	11546.8	40100.00
4	31482.07	40.25	1.638	0.30	( 0.30)	0.99	13938.2	11831.00
5	32286.65	42.77	1.582	0.30	( 0.30)	0.99	14891.0	11801.00
6	35371.62	52.69	1.392	0.30	( 0.30)	0.99	19187.2	11530.00
7	37785.69	61.54	1.310	0.30	( 0.30)	0.99	24172.1	11910.00
8	40000.95	68.92	1.260	0.30	( 0.30)	0.99	28772.5	11330.00
9	41144.93	75.39	1.217	0.30	( 0.30)	0.99	33203.6	11130.00
10	41117.48	82.96	1.166	0.30	( 0.30)	0.99	37197.5	12330.00
11	41083.38	85.55	1.149	0.30	( 0.30)	0.99	38612.3	12410.00
12	40933.89	89.58	1.122	0.30	( 0.30)	0.99	40540.7	12400.00
13	40469.65	98.18	1.082	0.30	( 0.30)	0.99	43909.5	12201.00
14	40039.80	102.08	1.064	0.30	( 0.30)	0.99	44994.2	12111.00
15	39758.98	104.44	1.054	0.30	( 0.30)	0.99	45634.0	10700.00
16	39434.11	107.37	1.040	0.30	( 0.30)	0.99	46363.6	12101.10
17	38931.89	111.32	1.022	0.30	( 0.30)	0.99	47212.7	10400.00
18	37425.18	119.13	0.987	0.30	( 0.30)	0.99	48527.8	12010.00
19	36149.07	124.81	0.970	0.30	( 0.30)	0.99	48841.5	10210.00
20	35788.63	127.43	0.964	0.30	( 0.30)	0.99	48952.4	12000.00
21	32838.30	150.31	0.904	0.30	( 0.30)	0.99	49574.3	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 41144.93 Tc (MIN.) = 75.39  
 AREA-AVERAGED Fm (INCH/HR) = 0.30 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA (ACRES) = 33203.55

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610403Y.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	365.26	18.67	0.30 ( 0.29)	0.97	175.0	40300.00
TOTAL AREA (ACRES) =						175.0

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24844.89	18.24	2.655	0.30 ( 0.30)	0.99	5692.3	600.00
2	25429.06	19.89	2.477	0.30 ( 0.30)	0.99	6264.7	40200.00
3	29197.78	33.66	1.806	0.30 ( 0.30)	0.99	11546.8	40100.00
4	31482.07	40.25	1.638	0.30 ( 0.30)	0.99	13938.2	11831.00
5	32286.65	42.77	1.582	0.30 ( 0.30)	0.99	14891.0	11801.00
6	35371.62	52.69	1.392	0.30 ( 0.30)	0.99	19187.2	11530.00
7	37785.69	61.54	1.310	0.30 ( 0.30)	0.99	24172.1	11910.00
8	40000.95	68.92	1.260	0.30 ( 0.30)	0.99	28772.5	11330.00
9	41144.93	75.39	1.217	0.30 ( 0.30)	0.99	33203.6	11130.00
10	41117.48	82.96	1.166	0.30 ( 0.30)	0.99	37197.5	12330.00
11	41083.38	85.55	1.149	0.30 ( 0.30)	0.99	38612.3	12410.00
12	40933.89	89.58	1.122	0.30 ( 0.30)	0.99	40540.7	12400.00
13	40469.65	98.18	1.082	0.30 ( 0.30)	0.99	43909.5	12201.00

14	40039.80	102.08	1.064	0.30	( 0.30)	0.99	44994.2	12111.00
15	39758.98	104.44	1.054	0.30	( 0.30)	0.99	45634.0	10700.00
16	39434.11	107.37	1.040	0.30	( 0.30)	0.99	46363.6	12101.10
17	38931.89	111.32	1.022	0.30	( 0.30)	0.99	47212.7	10400.00
18	37425.18	119.13	0.987	0.30	( 0.30)	0.99	48527.8	12010.00
19	36149.07	124.81	0.970	0.30	( 0.30)	0.99	48841.5	10210.00
20	35788.63	127.43	0.964	0.30	( 0.30)	0.99	48952.4	12000.00
21	32838.30	150.31	0.904	0.30	( 0.30)	0.99	49574.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.30 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	365.26	18.67	2.609	0.30 ( 0.29)	0.97	175.0	40300.00
LONGEST FLOWPATH FROM NODE 40300.00 TO NODE 12603.00 = 5256.00 FEET.							

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25208.90	18.24	2.655	0.30 ( 0.30)	0.99	5863.3	600.00
2	25360.63	18.67	2.609	0.30 ( 0.30)	0.99	6014.8	40300.00
3	25773.48	19.89	2.477	0.30 ( 0.30)	0.99	6439.7	40200.00
4	29436.66	33.66	1.806	0.30 ( 0.30)	0.99	11721.8	40100.00
5	31694.50	40.25	1.638	0.30 ( 0.30)	0.99	14113.2	11831.00
6	32490.15	42.77	1.582	0.30 ( 0.30)	0.99	15066.0	11801.00
7	35545.30	52.69	1.392	0.30 ( 0.30)	0.99	19362.2	11530.00
8	37946.36	61.54	1.310	0.30 ( 0.30)	0.99	24347.2	11910.00
9	40153.82	68.92	1.260	0.30 ( 0.30)	0.99	28947.6	11330.00
10	41290.98	75.39	1.217	0.30 ( 0.30)	0.99	33378.6	11130.00
11	41255.54	82.96	1.166	0.30 ( 0.30)	0.99	37372.6	12330.00
12	41218.71	85.55	1.149	0.30 ( 0.30)	0.99	38787.4	12410.00
13	41064.97	89.58	1.122	0.30 ( 0.30)	0.99	40715.8	12400.00
14	40594.44	98.18	1.082	0.30 ( 0.30)	0.99	44084.5	12201.00
15	40161.80	102.08	1.064	0.30 ( 0.30)	0.99	45169.2	12111.00
16	39879.30	104.44	1.054	0.30 ( 0.30)	0.99	45809.0	10700.00
17	39552.35	107.37	1.040	0.30 ( 0.30)	0.99	46538.7	12101.10
18	39047.30	111.32	1.022	0.30 ( 0.30)	0.99	47387.7	10400.00
19	37535.01	119.13	0.987	0.30 ( 0.30)	0.99	48702.9	12010.00
20	36256.30	124.81	0.970	0.30 ( 0.30)	0.99	49016.6	10210.00
21	35894.79	127.43	0.964	0.30 ( 0.30)	0.99	49127.5	12000.00
22	32935.03	150.31	0.904	0.30 ( 0.30)	0.99	49749.3	10100.00
TOTAL AREA (ACRES) =						49749.3	

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 41290.98 Tc (MIN.) = 75.385  
 EFFECTIVE AREA (ACRES) = 33378.60 AREA-AVERAGED Fm (INCH/HR) = 0.30  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA (ACRES) = 49749.3  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12603.00 = 101558.30 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81

-----  
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<  
-----

MAINLINE Tc(MIN.) = 75.39  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.217  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
NATURAL FAIR COVER  
"OPEN BRUSH" B 1.20 0.30 1.000 66  
NATURAL FAIR COVER  
"WOODLAND,GRASS" B 8.80 0.30 1.000 65  
NATURAL FAIR COVER  
"CHAPARRAL,NARROWLEAF" B 0.10 0.30 1.000 72  
NATURAL FAIR COVER  
"WOODLAND,GRASS" B 0.60 0.30 1.000 65  
NATURAL FAIR COVER  
"CHAPARRAL,BROADLEAF" B 0.60 0.30 1.000 63  
NATURAL FAIR COVER  
"CHAPARRAL,NARROWLEAF" B 2.90 0.30 1.000 72  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA(ACRES) = 14.20 SUBAREA RUNOFF(CFS) = 11.72  
EFFECTIVE AREA(ACRES) = 33392.80 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA(ACRES) = 49763.5 PEAK FLOW RATE(CFS) = 41290.98  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<  
-----

MAINLINE Tc(MIN.) = 75.39  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.217  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
NATURAL FAIR COVER  
"CHAPARRAL,BROADLEAF" B 0.30 0.30 1.000 63  
NATURAL FAIR COVER  
"OPEN BRUSH" B 1.90 0.30 1.000 66  
NATURAL FAIR COVER  
"WOODLAND,GRASS" B 0.10 0.30 1.000 65  
NATURAL FAIR COVER  
"CHAPARRAL,NARROWLEAF" B 0.70 0.30 1.000 72  
NATURAL FAIR COVER  
"OPEN BRUSH" B 1.10 0.30 1.000 66  
PUBLIC PARK B 0.70 0.30 0.850 56  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.978  
SUBAREA AREA(ACRES) = 4.80 SUBAREA RUNOFF(CFS) = 3.99  
EFFECTIVE AREA(ACRES) = 33397.60 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA(ACRES) = 49768.3 PEAK FLOW RATE(CFS) = 41290.98  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12603.00 TO NODE 12603.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<  
-----

MAINLINE Tc(MIN.) = 75.39  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.217  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
PUBLIC PARK B 0.20 0.30 0.850 56  
RESIDENTIAL  
"11+ DWELLINGS/ACRE" B 0.10 0.30 0.200 56  
RESIDENTIAL  
".4 DWELLING/ACRE" B 1.40 0.30 0.900 56  
RESIDENTIAL  
".4 DWELLING/ACRE" B 1.00 0.30 0.900 56  
NATURAL FAIR COVER  
"WOODLAND,GRASS" B 0.30 0.30 1.000 65  
NATURAL FAIR COVER  
"WOODLAND,GRASS" B 5.70 0.30 1.000 65  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.960  
SUBAREA AREA(ACRES) = 8.70 SUBAREA RUNOFF(CFS) = 7.27  
EFFECTIVE AREA(ACRES) = 33406.30 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
TOTAL AREA(ACRES) = 49777.0 PEAK FLOW RATE(CFS) = 41290.98  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12603.00 TO NODE 12604.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
-----

>>>>TRAVELTIME THRU SUBAREA<<<<  
-----

ELEVATION DATA: UPSTREAM(FEET) = 310.00 DOWNSTREAM(FEET) = 307.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 459.69 CHANNEL SLOPE = 0.0065  
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 10.05  
CHANNEL FLOW THRU SUBAREA(CFS) = 41290.98  
FLOW VELOCITY(FEET/SEC.) = 16.43 FLOW DEPTH(FEET) = 10.05  
TRAVEL TIME(MIN.) = 0.47 Tc(MIN.) = 75.85  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12604.00 = 102017.99 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25208.90	18.79	2.595	0.30( 0.30)	0.99	5891.0	600.00
2	25360.63	19.22	2.550	0.30( 0.30)	0.99	6042.5	40300.00
3	25773.48	20.44	2.436	0.30( 0.30)	0.99	6467.4	40200.00
4	29436.66	34.18	1.793	0.30( 0.30)	0.99	11749.5	40100.00
5	31694.50	40.76	1.627	0.30( 0.30)	0.99	14140.9	11831.00
6	32490.15	43.27	1.570	0.30( 0.30)	0.99	15093.7	11801.00
7	35545.30	53.18	1.387	0.30( 0.30)	0.99	19389.9	11530.00
8	37946.36	62.01	1.307	0.30( 0.30)	0.99	24374.9	11910.00
9	40153.82	69.39	1.257	0.30( 0.30)	0.99	28975.3	11330.00
10	41290.98	75.85	1.214	0.30( 0.30)	0.99	33406.3	11130.00
11	41255.54	83.43	1.163	0.30( 0.30)	0.99	37400.3	12330.00

12	41218.71	86.02	1.146	0.30	( 0.30)	0.99	38815.1	12410.00
13	41064.97	90.04	1.119	0.30	( 0.30)	0.99	40743.4	12400.00
14	40594.44	98.65	1.080	0.30	( 0.30)	0.99	44112.2	12201.00
15	40161.80	102.55	1.062	0.30	( 0.30)	0.99	45196.9	12111.00
16	39879.30	104.91	1.051	0.30	( 0.30)	0.99	45836.7	10700.00
17	39552.35	107.84	1.038	0.30	( 0.30)	0.99	46566.4	12101.10
18	39047.30	111.79	1.020	0.30	( 0.30)	0.99	47415.4	10400.00
19	37535.01	119.61	0.985	0.30	( 0.30)	0.99	48730.6	12010.00
20	36256.30	125.29	0.969	0.30	( 0.30)	0.99	49044.3	10210.00
21	35894.79	127.92	0.962	0.30	( 0.30)	0.99	49155.2	12000.00
22	32935.03	150.81	0.902	0.30	( 0.30)	0.99	49777.0	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 41290.98 Tc(MIN.) = 75.85  
 AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 33406.30

\*\*\*\*\*

FLOW PROCESS FROM NODE 12604.00 TO NODE 12604.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 75.85

\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.214

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "CHAPARRAL,NARROWLEAF"	B	0.10	0.30	1.000	72
NATURAL FAIR COVER "OPEN BRUSH"	B	0.90	0.30	1.000	66
PUBLIC PARK	B	0.10	0.30	0.850	56
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.70	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.50	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.993

SUBAREA AREA(ACRES) = 2.30 SUBAREA RUNOFF(CFS) = 1.90

EFFECTIVE AREA(ACRES) = 33408.60 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 49779.3 PEAK FLOW RATE(CFS) = 41290.98

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12604.00 TO NODE 12605.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 307.00 DOWNSTREAM(FEET) = 305.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 427.54 CHANNEL SLOPE = 0.0047

GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT(FEET) = 11.03

CHANNEL FLOW THRU SUBAREA(CFS) = 41290.98

FLOW VELOCITY(FEET/SEC.) = 14.66 FLOW DEPTH(FEET) = 11.03

TRAVEL TIME(MIN.) = 0.49 Tc(MIN.) = 76.34

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.00 = 102445.53 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25208.90	19.36	2.534	0.30( 0.30)	0.99	5893.3	600.00
2	25360.63	19.79	2.488	0.30( 0.30)	0.99	6044.8	40300.00
3	25773.48	21.00	2.398	0.30( 0.30)	0.99	6469.7	40200.00
4	29436.66	34.72	1.779	0.30( 0.30)	0.99	11751.8	40100.00
5	31694.50	41.29	1.615	0.30( 0.30)	0.99	14143.2	11831.00
6	32490.15	43.80	1.559	0.30( 0.30)	0.99	15096.0	11801.00
7	35545.30	53.69	1.382	0.30( 0.30)	0.99	19392.2	11530.00
8	37946.36	62.51	1.303	0.30( 0.30)	0.99	24377.2	11910.00
9	40153.82	69.88	1.254	0.30( 0.30)	0.99	28977.6	11330.00
10	41290.98	76.34	1.211	0.30( 0.30)	0.99	33408.6	11130.00
11	41255.54	83.91	1.160	0.30( 0.30)	0.99	37402.6	12330.00
12	41218.71	86.51	1.142	0.30( 0.30)	0.99	38817.4	12410.00
13	41064.97	90.53	1.117	0.30( 0.30)	0.99	40745.8	12400.00
14	40594.44	99.14	1.078	0.30( 0.30)	0.99	44114.5	12201.00
15	40161.80	103.04	1.060	0.30( 0.30)	0.99	45199.2	12111.00
16	39879.30	105.40	1.049	0.30( 0.30)	0.99	45839.0	10700.00
17	39552.35	108.33	1.036	0.30( 0.30)	0.99	46568.7	12101.10
18	39047.30	112.29	1.018	0.30( 0.30)	0.99	47417.7	10400.00
19	37535.01	120.11	0.983	0.30( 0.30)	0.99	48732.9	12010.00
20	36256.30	125.80	0.968	0.30( 0.30)	0.99	49046.6	10210.00
21	35894.79	128.43	0.961	0.30( 0.30)	0.99	49157.5	12000.00
22	32935.03	151.33	0.901	0.30( 0.30)	0.99	49779.3	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 41290.98 Tc(MIN.) = 76.34  
 AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 33408.60

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.00 TO NODE 12605.30 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 305.00 DOWNSTREAM(FEET) = 302.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 217.28 CHANNEL SLOPE = 0.0138

GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT(FEET) = 8.12

CHANNEL FLOW THRU SUBAREA(CFS) = 41290.98

FLOW VELOCITY(FEET/SEC.) = 21.13 FLOW DEPTH(FEET) = 8.12

TRAVEL TIME(MIN.) = 0.17 Tc(MIN.) = 76.51

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.30 = 102662.81 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25208.90	19.57	2.512	0.30( 0.30)	0.99	5893.3	600.00
2	25360.63	19.99	2.466	0.30( 0.30)	0.99	6044.8	40300.00
3	25773.48	21.21	2.384	0.30( 0.30)	0.99	6469.7	40200.00
4	29436.66	34.91	1.774	0.30( 0.30)	0.99	11751.8	40100.00
5	31694.50	41.47	1.611	0.30( 0.30)	0.99	14143.2	11831.00
6	32490.15	43.98	1.554	0.30( 0.30)	0.99	15096.0	11801.00
7	35545.30	53.87	1.381	0.30( 0.30)	0.99	19392.2	11530.00
8	37946.36	62.69	1.302	0.30( 0.30)	0.99	24377.2	11910.00



9	40153.82	70.05	1.253	0.30	( 0.30)	0.99	28977.6	11330.00
10	41290.98	76.51	1.209	0.30	( 0.30)	0.99	33408.6	11130.00
11	41255.54	84.09	1.159	0.30	( 0.30)	0.99	37402.6	12330.00
12	41218.71	86.68	1.141	0.30	( 0.30)	0.99	38817.4	12410.00
13	41064.97	90.70	1.116	0.30	( 0.30)	0.99	40745.8	12400.00
14	40594.44	99.31	1.077	0.30	( 0.30)	0.99	44114.5	12201.00
15	40161.80	103.21	1.059	0.30	( 0.30)	0.99	45199.2	12111.00
16	39879.30	105.57	1.048	0.30	( 0.30)	0.99	45839.0	10700.00
17	39552.35	108.51	1.035	0.30	( 0.30)	0.99	46568.7	12101.10
18	39047.30	112.46	1.017	0.30	( 0.30)	0.99	47417.7	10400.00
19	37535.01	120.29	0.982	0.30	( 0.30)	0.99	48732.9	12010.00
20	36256.30	125.98	0.967	0.30	( 0.30)	0.99	49046.6	10210.00
21	35894.79	128.61	0.960	0.30	( 0.30)	0.99	49157.5	12000.00
22	32935.03	151.52	0.901	0.30	( 0.30)	0.99	49779.3	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 41290.98 Tc(MIN.) = 76.51  
 AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 33408.60

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12605.30 TO NODE 12605.30 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610404Y.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	868.67	17.52	2.733	0.30 ( 0.30)	0.99	396.5	40430.00
2	857.31	18.07	2.673	0.30 ( 0.30)	0.99	401.1	40440.00
3	831.27	19.17	2.554	0.30 ( 0.30)	0.99	409.4	40400.00
4	825.53	19.36	2.534	0.30 ( 0.30)	0.99	410.3	40420.00
5	824.28	19.40	2.530	0.30 ( 0.30)	0.99	410.5	40410.00

TOTAL AREA(ACRES) = 410.5

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12605.30 TO NODE 12605.30 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25208.90	19.57	2.512	0.30 ( 0.30)	0.99	5893.3	600.00
2	25360.63	19.99	2.466	0.30 ( 0.30)	0.99	6044.8	40300.00
3	25773.48	21.21	2.384	0.30 ( 0.30)	0.99	6469.7	40200.00
4	29436.66	34.91	1.774	0.30 ( 0.30)	0.99	11751.8	40100.00
5	31694.50	41.47	1.611	0.30 ( 0.30)	0.99	14143.2	11831.00
6	32490.15	43.98	1.554	0.30 ( 0.30)	0.99	15096.0	11801.00
7	35545.30	53.87	1.381	0.30 ( 0.30)	0.99	19392.2	11530.00
8	37946.36	62.69	1.302	0.30 ( 0.30)	0.99	24377.2	11910.00
9	40153.82	70.05	1.253	0.30 ( 0.30)	0.99	28977.6	11330.00
10	41290.98	76.51	1.209	0.30 ( 0.30)	0.99	33408.6	11130.00
11	41255.54	84.09	1.159	0.30 ( 0.30)	0.99	37402.6	12330.00
12	41218.71	86.68	1.141	0.30 ( 0.30)	0.99	38817.4	12410.00
13	41064.97	90.70	1.116	0.30 ( 0.30)	0.99	40745.8	12400.00
14	40594.44	99.31	1.077	0.30 ( 0.30)	0.99	44114.5	12201.00

15	40161.80	103.21	1.059	0.30	( 0.30)	0.99	45199.2	12111.00
16	39879.30	105.57	1.048	0.30	( 0.30)	0.99	45839.0	10700.00
17	39552.35	108.51	1.035	0.30	( 0.30)	0.99	46568.7	12101.10
18	39047.30	112.46	1.017	0.30	( 0.30)	0.99	47417.7	10400.00
19	37535.01	120.29	0.982	0.30	( 0.30)	0.99	48732.9	12010.00
20	36256.30	125.98	0.967	0.30	( 0.30)	0.99	49046.6	10210.00
21	35894.79	128.61	0.960	0.30	( 0.30)	0.99	49157.5	12000.00
22	32935.03	151.52	0.901	0.30	( 0.30)	0.99	49779.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.30 = 102662.81 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	868.67	17.52	2.733	0.30 ( 0.30)	0.99	396.5	40430.00
2	857.31	18.07	2.673	0.30 ( 0.30)	0.99	401.1	40440.00
3	831.27	19.17	2.554	0.30 ( 0.30)	0.99	409.4	40400.00
4	825.53	19.36	2.534	0.30 ( 0.30)	0.99	410.3	40420.00
5	824.28	19.40	2.530	0.30 ( 0.30)	0.99	410.5	40410.00

LONGEST FLOWPATH FROM NODE 40400.00 TO NODE 12605.30 = 7428.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25694.78	17.52	2.733	0.30 ( 0.30)	0.99	5674.5	40430.00
2	25837.86	18.07	2.673	0.30 ( 0.30)	0.99	5844.5	40440.00
3	26007.30	19.17	2.554	0.30 ( 0.30)	0.99	6184.4	40400.00
4	26020.05	19.36	2.534	0.30 ( 0.30)	0.99	6243.2	40420.00
5	26021.87	19.40	2.530	0.30 ( 0.30)	0.99	6254.6	40410.00
6	26026.67	19.57	2.512	0.30 ( 0.30)	0.99	6303.8	600.00
7	26161.57	19.99	2.466	0.30 ( 0.30)	0.99	6455.2	40300.00
8	26544.02	21.21	2.384	0.30 ( 0.30)	0.99	6880.2	40200.00
9	29982.04	34.91	1.774	0.30 ( 0.30)	0.99	12162.3	40100.00
10	32179.55	41.47	1.611	0.30 ( 0.30)	0.99	14553.7	11831.00
11	32954.33	43.98	1.554	0.30 ( 0.30)	0.99	15506.5	11801.00
12	35945.35	53.87	1.381	0.30 ( 0.30)	0.99	19802.7	11530.00
13	38317.35	62.69	1.302	0.30 ( 0.30)	0.99	24787.6	11910.00
14	40506.59	70.05	1.253	0.30 ( 0.30)	0.99	29388.1	11330.00
15	41627.78	76.51	1.209	0.30 ( 0.30)	0.99	33819.1	11130.00
16	41573.59	84.09	1.159	0.30 ( 0.30)	0.99	37813.0	12330.00
17	41530.35	86.68	1.141	0.30 ( 0.30)	0.99	39227.9	12410.00
18	41367.22	90.70	1.116	0.30 ( 0.30)	0.99	41156.2	12400.00
19	40882.28	99.31	1.077	0.30 ( 0.30)	0.99	44525.0	12201.00
20	40443.11	103.21	1.059	0.30 ( 0.30)	0.99	45609.7	12111.00
21	40156.66	105.57	1.048	0.30 ( 0.30)	0.99	46249.5	10700.00
22	39824.79	108.51	1.035	0.30 ( 0.30)	0.99	46979.1	12101.10
23	39313.12	112.46	1.017	0.30 ( 0.30)	0.99	47828.2	10400.00
24	37787.94	120.29	0.982	0.30 ( 0.30)	0.99	49143.3	12010.00
25	36503.73	125.98	0.967	0.30 ( 0.30)	0.99	49457.1	10210.00
26	36139.67	128.61	0.960	0.30 ( 0.30)	0.99	49567.9	12000.00
27	33157.78	151.52	0.901	0.30 ( 0.30)	0.99	50189.8	10100.00

TOTAL AREA(ACRES) = 50189.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 41627.78 Tc(MIN.) = 76.509  
 EFFECTIVE AREA(ACRES) = 33819.06 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 50189.8  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.30 = 102662.81 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.30 TO NODE 12605.30 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.30 TO NODE 12605.60 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 302.00 DOWNSTREAM(FEET) = 295.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 738.76 CHANNEL SLOPE = 0.0095
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030
\*ESTIMATED CHANNEL HEIGHT(FEET) = 9.08
CHANNEL FLOW THRU SUBAREA(CFS) = 41627.78
FLOW VELOCITY(FEET/SEC.) = 18.67 FLOW DEPTH(FEET) = 9.08
TRAVEL TIME(MIN.) = 0.66 Tc(MIN.) = 77.17
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.60 = 103401.57 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp (Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 27 rows of data.

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 41627.78 Tc(MIN.) = 77.17
AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 33819.06

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.60 TO NODE 12605.60 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610405Y.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

Table with 7 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Fp (Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 3 rows of data.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.60 TO NODE 12605.60 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp (Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 27 rows of data.

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.60 = 103401.57 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

Table with 7 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp (Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 2 rows of data.

LONGEST FLOWPATH FROM NODE 40500.00 TO NODE 12605.60 = 4091.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24284.11	13.78	3.224	0.30 ( 0.30)	0.99	4350.9	40510.00
2	24570.97	15.19	2.985	0.30 ( 0.30)	0.99	4791.7	40500.00
3	25866.80	18.30	2.649	0.30 ( 0.30)	0.99	5755.9	40430.00
4	26005.55	18.85	2.590	0.30 ( 0.30)	0.99	5925.9	40440.00
5	26166.30	19.94	2.471	0.30 ( 0.30)	0.99	6265.8	40400.00
6	26177.94	20.14	2.456	0.30 ( 0.30)	0.99	6324.6	40420.00
7	26179.57	20.17	2.453	0.30 ( 0.30)	0.99	6336.0	40410.00
8	26183.57	20.34	2.442	0.30 ( 0.30)	0.99	6385.2	600.00
9	26316.41	20.76	2.414	0.30 ( 0.30)	0.99	6536.6	40300.00
10	26692.88	21.97	2.333	0.30 ( 0.30)	0.99	6961.6	40200.00
11	30088.65	35.65	1.755	0.30 ( 0.30)	0.99	12243.7	40100.00
12	32274.39	42.19	1.595	0.30 ( 0.30)	0.99	14635.1	11831.00
13	33045.04	44.70	1.538	0.30 ( 0.30)	0.99	15587.9	11801.00
14	36024.02	54.56	1.374	0.30 ( 0.30)	0.99	19884.0	11530.00
15	38390.43	63.37	1.297	0.30 ( 0.30)	0.99	24869.0	11910.00
16	40576.07	70.72	1.248	0.30 ( 0.30)	0.99	29469.4	11330.00
17	41694.09	77.17	1.205	0.30 ( 0.30)	0.99	33900.4	11130.00
18	41636.19	84.75	1.154	0.30 ( 0.30)	0.99	37894.4	12330.00
19	41591.67	87.34	1.137	0.30 ( 0.30)	0.99	39309.2	12410.00
20	41426.78	91.36	1.113	0.30 ( 0.30)	0.99	41237.6	12400.00
21	40938.98	99.97	1.074	0.30 ( 0.30)	0.99	44606.4	12201.00
22	40498.51	103.88	1.056	0.30 ( 0.30)	0.99	45691.0	12111.00
23	40211.28	106.24	1.045	0.30 ( 0.30)	0.99	46330.9	10700.00
24	39878.44	109.18	1.032	0.30 ( 0.30)	0.99	47060.5	12101.10
25	39365.45	113.14	1.014	0.30 ( 0.30)	0.99	47909.6	10400.00
26	37837.81	120.97	0.980	0.30 ( 0.30)	0.99	49224.7	12010.00
27	36552.51	126.67	0.966	0.30 ( 0.30)	0.99	49538.4	10210.00
28	36187.95	129.30	0.959	0.30 ( 0.30)	0.99	49649.3	12000.00
29	33201.66	152.23	0.899	0.30 ( 0.30)	0.99	50271.2	10100.00

TOTAL AREA (ACRES) = 50271.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 41694.09 Tc(MIN.) = 77.168  
 EFFECTIVE AREA(ACRES) = 33900.44 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA (ACRES) = 50271.2  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12605.60 = 103401.57 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.60 TO NODE 12605.60 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 12605.60 TO NODE 12606.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 295.00 DOWNSTREAM(FEET) = 286.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1203.43 CHANNEL SLOPE = 0.0075  
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 9.72

CHANNEL FLOW THRU SUBAREA(CFS) = 41694.09  
 FLOW VELOCITY(FEET/SEC.) = 17.25 FLOW DEPTH(FEET) = 9.72  
 TRAVEL TIME(MIN.) = 1.16 Tc(MIN.) = 78.33  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104605.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24284.11	15.17	2.986	0.30 ( 0.30)	0.99	4350.9	40510.00
2	24570.97	16.57	2.835	0.30 ( 0.30)	0.99	4791.7	40500.00
3	25866.80	19.66	2.502	0.30 ( 0.30)	0.99	5755.9	40430.00
4	26005.55	20.20	2.451	0.30 ( 0.30)	0.99	5925.9	40440.00
5	26166.30	21.30	2.378	0.30 ( 0.30)	0.99	6265.8	40400.00
6	26177.94	21.49	2.365	0.30 ( 0.30)	0.99	6324.6	40420.00
7	26179.57	21.53	2.362	0.30 ( 0.30)	0.99	6336.0	40410.00
8	26183.57	21.69	2.351	0.30 ( 0.30)	0.99	6385.2	600.00
9	26316.41	22.11	2.323	0.30 ( 0.30)	0.99	6536.6	40300.00
10	26692.88	23.32	2.242	0.30 ( 0.30)	0.99	6961.6	40200.00
11	30088.65	36.94	1.722	0.30 ( 0.30)	0.99	12243.7	40100.00
12	32274.39	43.46	1.566	0.30 ( 0.30)	0.99	14635.1	11831.00
13	33045.04	45.95	1.510	0.30 ( 0.30)	0.99	15587.9	11801.00
14	36024.02	55.78	1.362	0.30 ( 0.30)	0.99	19884.0	11530.00
15	38390.43	64.56	1.289	0.30 ( 0.30)	0.99	24869.0	11910.00
16	40576.07	71.89	1.240	0.30 ( 0.30)	0.99	29469.4	11330.00
17	41694.09	78.33	1.197	0.30 ( 0.30)	0.99	33900.4	11130.00
18	41636.19	85.91	1.146	0.30 ( 0.30)	0.99	37894.4	12330.00
19	41591.67	88.50	1.129	0.30 ( 0.30)	0.99	39309.2	12410.00
20	41426.78	92.53	1.108	0.30 ( 0.30)	0.99	41237.6	12400.00
21	40938.98	101.14	1.068	0.30 ( 0.30)	0.99	44606.4	12201.00
22	40498.51	105.05	1.051	0.30 ( 0.30)	0.99	45691.0	12111.00
23	40211.28	107.42	1.040	0.30 ( 0.30)	0.99	46330.9	10700.00
24	39878.44	110.36	1.027	0.30 ( 0.30)	0.99	47060.5	12101.10
25	39365.45	114.32	1.009	0.30 ( 0.30)	0.99	47909.6	10400.00
26	37837.81	122.17	0.977	0.30 ( 0.30)	0.99	49224.7	12010.00
27	36552.51	127.88	0.962	0.30 ( 0.30)	0.99	49538.4	10210.00
28	36187.95	130.52	0.955	0.30 ( 0.30)	0.99	49649.3	12000.00
29	33201.66	153.48	0.895	0.30 ( 0.30)	0.99	50271.2	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 41694.09 Tc(MIN.) = 78.33  
 AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA (ACRES) = 33900.44

\*\*\*\*\*

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610406Y.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	262.33	20.09	0.30 ( 0.30)	0.99	135.0	40600.00
TOTAL AREA (ACRES) = 135.0						

\*\*\*\*\*

FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\*\*\*\*  
**\*\* MAIN STREAM CONFLUENCE DATA \*\***

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24284.11	15.17	2.986	0.30 ( 0.30)	0.99	4350.9	40510.00
2	24570.97	16.57	2.835	0.30 ( 0.30)	0.99	4791.7	40500.00
3	25866.80	19.66	2.502	0.30 ( 0.30)	0.99	5755.9	40430.00
4	26005.55	20.20	2.451	0.30 ( 0.30)	0.99	5925.9	40440.00
5	26166.30	21.30	2.378	0.30 ( 0.30)	0.99	6265.8	40400.00
6	26177.94	21.49	2.365	0.30 ( 0.30)	0.99	6324.6	40420.00
7	26179.57	21.53	2.362	0.30 ( 0.30)	0.99	6336.0	40410.00
8	26183.57	21.69	2.351	0.30 ( 0.30)	0.99	6385.2	600.00
9	26316.41	22.11	2.323	0.30 ( 0.30)	0.99	6536.6	40300.00
10	26692.88	23.32	2.242	0.30 ( 0.30)	0.99	6961.6	40200.00
11	30088.65	36.94	1.722	0.30 ( 0.30)	0.99	12243.7	40100.00
12	32274.39	43.46	1.566	0.30 ( 0.30)	0.99	14635.1	11831.00
13	33045.04	45.95	1.510	0.30 ( 0.30)	0.99	15587.9	11801.00
14	36024.02	55.78	1.362	0.30 ( 0.30)	0.99	19884.0	11530.00
15	38390.43	64.56	1.289	0.30 ( 0.30)	0.99	24869.0	11910.00
16	40576.07	71.89	1.240	0.30 ( 0.30)	0.99	29469.4	11330.00
17	41694.09	78.33	1.197	0.30 ( 0.30)	0.99	33900.4	11130.00
18	41636.19	85.91	1.146	0.30 ( 0.30)	0.99	37894.4	12330.00
19	41591.67	88.50	1.129	0.30 ( 0.30)	0.99	39309.2	12410.00
20	41426.78	92.53	1.108	0.30 ( 0.30)	0.99	41237.6	12400.00
21	40938.98	101.14	1.068	0.30 ( 0.30)	0.99	44606.4	12201.00
22	40498.51	105.05	1.051	0.30 ( 0.30)	0.99	45691.0	12111.00
23	40211.28	107.42	1.040	0.30 ( 0.30)	0.99	46330.9	10700.00
24	39878.44	110.36	1.027	0.30 ( 0.30)	0.99	47060.5	12101.10
25	39365.45	114.32	1.009	0.30 ( 0.30)	0.99	47909.6	10400.00
26	37837.81	122.17	0.977	0.30 ( 0.30)	0.99	49224.7	12010.00
27	36552.51	127.88	0.962	0.30 ( 0.30)	0.99	49538.4	10210.00
28	36187.95	130.52	0.955	0.30 ( 0.30)	0.99	49649.3	12000.00
29	33201.66	153.48	0.895	0.30 ( 0.30)	0.99	50271.2	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104605.00 FEET.

**\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\***

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	262.33	20.09	2.459	0.30 ( 0.30)	0.99	135.0	40600.00

LONGEST FLOWPATH FROM NODE 40600.00 TO NODE 12606.00 = 6107.00 FEET.

**\*\* PEAK FLOW RATE TABLE \*\***

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24530.59	15.17	2.986	0.30 ( 0.30)	0.99	4452.9	40510.00
2	24825.05	16.57	2.835	0.30 ( 0.30)	0.99	4903.0	40500.00
3	26128.60	19.66	2.502	0.30 ( 0.30)	0.99	5887.9	40430.00
4	26238.81	20.09	2.459	0.30 ( 0.30)	0.99	6025.2	40600.00
5	26266.96	20.20	2.451	0.30 ( 0.30)	0.99	6060.8	40440.00
6	26418.76	21.30	2.378	0.30 ( 0.30)	0.99	6400.8	40400.00
7	26428.84	21.49	2.365	0.30 ( 0.30)	0.99	6459.6	40420.00
8	26430.16	21.53	2.362	0.30 ( 0.30)	0.99	6471.0	40410.00
9	26432.83	21.69	2.351	0.30 ( 0.30)	0.99	6520.1	600.00
10	26562.25	22.11	2.323	0.30 ( 0.30)	0.99	6671.6	40300.00
11	26928.87	23.32	2.242	0.30 ( 0.30)	0.99	7096.5	40200.00
12	30261.54	36.94	1.722	0.30 ( 0.30)	0.99	12378.7	40100.00
13	32428.33	43.46	1.566	0.30 ( 0.30)	0.99	14770.1	11831.00

14	33192.17	45.95	1.510	0.30 ( 0.30)	0.99	15722.8	11801.00
15	36153.13	55.78	1.362	0.30 ( 0.30)	0.99	20019.0	11530.00
16	38510.76	64.56	1.289	0.30 ( 0.30)	0.99	25004.0	11910.00
17	40690.44	71.89	1.240	0.30 ( 0.30)	0.99	29604.4	11330.00
18	41803.22	78.33	1.197	0.30 ( 0.30)	0.99	34035.4	11130.00
19	41739.16	85.91	1.146	0.30 ( 0.30)	0.99	38029.4	12330.00
20	41692.53	88.50	1.129	0.30 ( 0.30)	0.99	39444.2	12410.00
21	41525.03	92.53	1.108	0.30 ( 0.30)	0.99	41372.6	12400.00
22	41032.48	101.14	1.068	0.30 ( 0.30)	0.99	44741.3	12201.00
23	40589.86	105.05	1.051	0.30 ( 0.30)	0.99	45826.0	12111.00
24	40301.34	107.42	1.040	0.30 ( 0.30)	0.99	46465.8	10700.00
25	39966.88	110.36	1.027	0.30 ( 0.30)	0.99	47195.5	12101.10
26	39451.71	114.32	1.009	0.30 ( 0.30)	0.99	48044.5	10400.00
27	37920.25	122.17	0.977	0.30 ( 0.30)	0.99	49359.7	12010.00
28	36633.14	127.88	0.962	0.30 ( 0.30)	0.99	49673.4	10210.00
29	36267.73	130.52	0.955	0.30 ( 0.30)	0.99	49784.3	12000.00
30	33274.15	153.48	0.895	0.30 ( 0.30)	0.99	50406.1	10100.00

TOTAL AREA (ACRES) = 50406.1

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 41803.22 Tc (MIN.) = 78.331  
 EFFECTIVE AREA (ACRES) = 34035.41 AREA-AVERAGED Fm (INCH/HR) = 0.30  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA (ACRES) = 50406.1  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12606.00 = 104605.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

=====  
 END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 50406.1 TC (MIN.) = 78.33  
 EFFECTIVE AREA (ACRES) = 34035.41 AREA-AVERAGED Fm (INCH/HR) = 0.30  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.994  
 PEAK FLOW RATE (CFS) = 41803.22

**\*\* PEAK FLOW RATE TABLE \*\***

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24530.59	15.17	2.986	0.30 ( 0.30)	0.99	4452.9	40510.00
2	24825.05	16.57	2.835	0.30 ( 0.30)	0.99	4903.0	40500.00
3	26128.60	19.66	2.502	0.30 ( 0.30)	0.99	5887.9	40430.00
4	26238.81	20.09	2.459	0.30 ( 0.30)	0.99	6025.2	40600.00
5	26266.96	20.20	2.451	0.30 ( 0.30)	0.99	6060.8	40440.00
6	26418.76	21.30	2.378	0.30 ( 0.30)	0.99	6400.8	40400.00
7	26428.84	21.49	2.365	0.30 ( 0.30)	0.99	6459.6	40420.00
8	26430.16	21.53	2.362	0.30 ( 0.30)	0.99	6471.0	40410.00
9	26432.83	21.69	2.351	0.30 ( 0.30)	0.99	6520.1	600.00
10	26562.25	22.11	2.323	0.30 ( 0.30)	0.99	6671.6	40300.00
11	26928.87	23.32	2.242	0.30 ( 0.30)	0.99	7096.5	40200.00
12	30261.54	36.94	1.722	0.30 ( 0.30)	0.99	12378.7	40100.00
13	32428.33	43.46	1.566	0.30 ( 0.30)	0.99	14770.1	11831.00
14	33192.17	45.95	1.510	0.30 ( 0.30)	0.99	15722.8	11801.00
15	36153.13	55.78	1.362	0.30 ( 0.30)	0.99	20019.0	11530.00
16	38510.76	64.56	1.289	0.30 ( 0.30)	0.99	25004.0	11910.00
17	40690.44	71.89	1.240	0.30 ( 0.30)	0.99	29604.4	11330.00

18	41803.22	78.33	1.197	0.30	( 0.30)	0.99	34035.4	11130.00
19	41739.16	85.91	1.146	0.30	( 0.30)	0.99	38029.4	12330.00
20	41692.53	88.50	1.129	0.30	( 0.30)	0.99	39444.2	12410.00
21	41525.03	92.53	1.108	0.30	( 0.30)	0.99	41372.6	12400.00
22	41032.48	101.14	1.068	0.30	( 0.30)	0.99	44741.3	12201.00
23	40589.86	105.05	1.051	0.30	( 0.30)	0.99	45826.0	12111.00
24	40301.34	107.42	1.040	0.30	( 0.30)	0.99	46465.8	10700.00
25	39966.88	110.36	1.027	0.30	( 0.30)	0.99	47195.5	12101.10
26	39451.71	114.32	1.009	0.30	( 0.30)	0.99	48044.5	10400.00
27	37920.25	122.17	0.977	0.30	( 0.30)	0.99	49359.7	12010.00
28	36633.14	127.88	0.962	0.30	( 0.30)	0.99	49673.4	10210.00
29	36267.73	130.52	0.955	0.30	( 0.30)	0.99	49784.3	12000.00
30	33274.15	153.48	0.895	0.30	( 0.30)	0.99	50406.1	10100.00

=====  
=====  
END OF RATIONAL METHOD ANALYSIS

\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S27- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 100-YR RM EV APRIL 2019 CCHIUI \*  
\*\*\*\*\*

FILE NAME: RI00EV27.DAT  
TIME/DATE OF STUDY: 08:50 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 100.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*

NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 6.027
- 2) 10.00; 3.864
- 3) 15.00; 2.981
- 4) 20.00; 2.449
- 5) 25.00; 2.118
- 6) 30.00; 1.891
- 7) 40.00; 1.635
- 8) 50.00; 1.412
- 9) 60.00; 1.310
- 10) 90.00; 1.109
- 11) 120.00; 0.972
- 12) 180.00; 0.816
- 13) 360.00; 0.607
- 14) 1200.00; 0.266

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:

- 1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI00EV26.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24825.05	16.57	0.30 ( 0.30)	0.99	4903.0	40500.00
2	26266.96	20.20	0.30 ( 0.30)	0.99	6060.8	40440.00
3	26928.87	23.32	0.30 ( 0.30)	0.99	7096.5	40200.00
4	30261.54	36.94	0.30 ( 0.30)	0.99	12378.7	40100.00
5	33192.17	45.95	0.30 ( 0.30)	0.99	15722.8	11801.00
6	36153.13	55.78	0.30 ( 0.30)	0.99	20019.0	11530.00
7	38510.76	64.56	0.30 ( 0.30)	0.99	25004.0	11910.00
8	40690.44	71.89	0.30 ( 0.30)	0.99	29604.4	11330.00
9	41803.22	78.33	0.30 ( 0.30)	0.99	34035.4	11130.00
10	41739.16	85.91	0.30 ( 0.30)	0.99	38029.4	12330.00
11	41692.53	88.50	0.30 ( 0.30)	0.99	39444.2	12410.00
12	41525.03	92.53	0.30 ( 0.30)	0.99	41372.6	12400.00
13	41032.48	101.14	0.30 ( 0.30)	0.99	44741.3	12201.00
14	40589.86	105.05	0.30 ( 0.30)	0.99	45826.0	12111.00
15	39966.88	110.36	0.30 ( 0.30)	0.99	47195.5	12101.10
16	39451.71	114.32	0.30 ( 0.30)	0.99	48044.5	10400.00
17	37920.25	122.17	0.30 ( 0.30)	0.99	49359.7	12010.00
18	36633.14	127.88	0.30 ( 0.30)	0.99	49673.4	10210.00
19	36267.73	130.52	0.30 ( 0.30)	0.99	49784.3	12000.00
20	33274.15	153.48	0.30 ( 0.30)	0.99	50406.1	10100.00
TOTAL AREA (ACRES) =						50406.1

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12606.00 TO NODE 12606.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24825.05	16.57	0.30 ( 0.30)	0.99	4903.0	40500.00
2	26266.96	20.20	0.30 ( 0.30)	0.99	6060.8	40440.00
3	26928.87	23.32	0.30 ( 0.30)	0.99	7096.5	40200.00
4	30261.54	36.94	0.30 ( 0.30)	0.99	12378.7	40100.00
5	33192.17	45.95	0.30 ( 0.30)	0.99	15722.8	11801.00
6	36153.13	55.78	0.30 ( 0.30)	0.99	20019.0	11530.00
7	38510.76	64.56	0.30 ( 0.30)	0.99	25004.0	11910.00
8	40690.44	71.89	0.30 ( 0.30)	0.99	29604.4	11330.00
9	41803.22	78.33	0.30 ( 0.30)	0.99	34035.4	11130.00
10	41739.16	85.91	0.30 ( 0.30)	0.99	38029.4	12330.00
11	41692.53	88.50	0.30 ( 0.30)	0.99	39444.2	12410.00
12	41525.03	92.53	0.30 ( 0.30)	0.99	41372.6	12400.00
13	41032.48	101.14	0.30 ( 0.30)	0.99	44741.3	12201.00

14	40589.86	105.05	0.30	( 0.30)	0.99	45826.0	12111.00
15	39966.88	110.36	0.30	( 0.30)	0.99	47195.5	12101.10
16	39451.71	114.32	0.30	( 0.30)	0.99	48044.5	10400.00
17	37920.25	122.17	0.30	( 0.30)	0.99	49359.7	12010.00
18	36633.14	127.88	0.30	( 0.30)	0.99	49673.4	10210.00
19	36267.73	130.52	0.30	( 0.30)	0.99	49784.3	12000.00
20	33274.15	153.48	0.30	( 0.30)	0.99	50406.1	10100.00
TOTAL AREA (ACRES) =							50406.1

\*\*\*\*\*

FLOW PROCESS FROM NODE 12606.00 TO NODE 12701.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 286.00 DOWNSTREAM(FEET) = 276.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1260.19 CHANNEL SLOPE = 0.0079  
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 9.58

\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.179

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	7.55	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 41807.13

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 17.61

AVERAGE FLOW DEPTH(FEET) = 9.58 TRAVEL TIME(MIN.) = 1.19

Tc(MIN.) = 79.52

SUBAREA AREA(ACRES) = 7.55 SUBAREA RUNOFF(CFS) = 7.81

EFFECTIVE AREA(ACRES) = 34042.96 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 50413.7 PEAK FLOW RATE(CFS) = 41803.22

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT(FEET) = 9.58

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 9.58 FLOW VELOCITY(FEET/SEC.) = 17.61

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12701.00 = 105865.19 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24825.05	17.99	2.663	0.30( 0.30)	0.99	4910.6	40500.00
2	26266.96	21.60	2.343	0.30( 0.30)	0.99	6068.4	40440.00
3	26928.87	24.70	2.138	0.30( 0.30)	0.99	7104.1	40200.00
4	30261.54	38.27	1.679	0.30( 0.30)	0.99	12386.2	40100.00
5	33192.17	47.24	1.474	0.30( 0.30)	0.99	15730.4	11801.00
6	36153.13	57.04	1.340	0.30( 0.30)	0.99	20026.6	11530.00
7	38510.76	65.79	1.271	0.30( 0.30)	0.99	25011.5	11910.00
8	40690.44	73.09	1.222	0.30( 0.30)	0.99	29612.0	11330.00
9	41803.22	79.52	1.179	0.30( 0.30)	0.99	34043.0	11130.00
10	41739.16	87.10	1.128	0.30( 0.30)	0.99	38036.9	12330.00
11	41692.53	89.69	1.111	0.30( 0.30)	0.99	39451.8	12410.00

12	41525.03	93.72	1.092	0.30( 0.30)	0.99	41380.1	12400.00
13	41032.48	102.34	1.053	0.30( 0.30)	0.99	44748.9	12201.00
14	40589.86	106.26	1.035	0.30( 0.30)	0.99	45833.6	12111.00
15	39966.88	111.57	1.011	0.30( 0.30)	0.99	47203.0	12101.10
16	39451.71	115.54	0.992	0.30( 0.30)	0.99	48052.1	10400.00
17	37920.25	123.40	0.963	0.30( 0.30)	0.99	49367.2	12010.00
18	36633.14	129.12	0.948	0.30( 0.30)	0.99	49681.0	10210.00
19	36267.73	131.77	0.941	0.30( 0.30)	0.99	49791.8	12000.00
20	33274.15	154.77	0.882	0.30( 0.30)	0.99	50413.7	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 41803.22 Tc(MIN.) = 79.52

AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 34042.96

\*\*\*\*\*

FLOW PROCESS FROM NODE 12701.00 TO NODE 12701.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 79.52

\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.179

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	0.90	0.30	0.850	56

NATURAL FAIR COVER

"WOODLAND,GRASS" B 3.40 0.30 1.000 65

RESIDENTIAL

"5-7 DWELLINGS/ACRE" B 0.40 0.30 0.500 56

NATURAL FAIR COVER

"OPEN BRUSH" B 23.00 0.30 1.000 66

NATURAL FAIR COVER

"OPEN BRUSH" B 3.30 0.30 1.000 66

NATURAL FAIR COVER

"GRASS" B 0.40 0.30 1.000 69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.989

SUBAREA AREA(ACRES) = 31.40 SUBAREA RUNOFF(CFS) = 24.94

EFFECTIVE AREA(ACRES) = 34074.36 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 50445.1 PEAK FLOW RATE(CFS) = 41803.22

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12701.00 TO NODE 12701.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 79.52

\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.179

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					

"WOODLAND,GRASS" B 1.70 0.30 1.000 65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA(ACRES) = 1.70 SUBAREA RUNOFF(CFS) = 1.35

EFFECTIVE AREA(ACRES) = 34076.06 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 50446.8 PEAK FLOW RATE(CFS) = 41803.22  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12701.00 TO NODE 12720.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 276.00 DOWNSTREAM(FEET) = 275.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 147.65 CHANNEL SLOPE = 0.0068  
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT(FEET) = 10.01  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.178  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	1.49	0.30	0.850	56

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.850  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 41803.84  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 16.70  
 AVERAGE FLOW DEPTH(FEET) = 10.01 TRAVEL TIME(MIN.) = 0.15  
 Tc(MIN.) = 79.67  
 SUBAREA AREA(ACRES) = 1.49 SUBAREA RUNOFF(CFS) = 1.24  
 EFFECTIVE AREA(ACRES) = 34077.55 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 50448.3 PEAK FLOW RATE(CFS) = 41803.22  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 10.01

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 10.01 FLOW VELOCITY(FEET/SEC.) = 16.70  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.00 = 106012.84 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24825.05	18.17	2.644	0.30( 0.30)	0.99	4945.1	40500.00
2	26266.96	21.77	2.332	0.30( 0.30)	0.99	6103.0	40440.00
3	26928.87	24.87	2.127	0.30( 0.30)	0.99	7138.7	40200.00
4	30261.54	38.43	1.675	0.30( 0.30)	0.99	12420.8	40100.00
5	33192.17	47.40	1.470	0.30( 0.30)	0.99	15765.0	11801.00
6	36153.13	57.19	1.339	0.30( 0.30)	0.99	20061.2	11530.00
7	38510.76	65.94	1.270	0.30( 0.30)	0.99	25046.1	11910.00
8	40690.44	73.24	1.221	0.30( 0.30)	0.99	29646.5	11330.00
9	41803.22	79.67	1.178	0.30( 0.30)	0.99	34077.5	11130.00
10	41739.16	87.25	1.127	0.30( 0.30)	0.99	38071.5	12330.00
11	41692.53	89.84	1.110	0.30( 0.30)	0.99	39486.3	12410.00
12	41525.03	93.87	1.091	0.30( 0.30)	0.99	41414.7	12400.00
13	41032.48	102.49	1.052	0.30( 0.30)	0.99	44783.5	12201.00
14	40589.86	106.41	1.034	0.30( 0.30)	0.99	45868.1	12111.00
15	39966.88	111.72	1.010	0.30( 0.30)	0.99	47237.6	12101.10

16	39451.71	115.69	0.992	0.30( 0.30)	0.99	48086.7	10400.00
17	37920.25	123.55	0.963	0.30( 0.30)	0.99	49401.8	12010.00
18	36633.14	129.28	0.948	0.30( 0.30)	0.99	49715.5	10210.00
19	36267.73	131.92	0.941	0.30( 0.30)	0.99	49826.4	12000.00
20	33274.15	154.93	0.881	0.30( 0.30)	0.99	50448.3	10100.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE(CFS) = 41803.22 Tc(MIN.) = 79.67  
 AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 34077.55

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12701.00 TO NODE 12720.00 IS CODE = 1  
 -----

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 =====

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
 TIME OF CONCENTRATION(MIN.) = 79.67  
 RAINFALL INTENSITY(INCH/HR) = 1.18  
 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.99  
 EFFECTIVE STREAM AREA(ACRES) = 34077.55  
 TOTAL STREAM AREA(ACRES) = 50448.27  
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 41803.22

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12710.00 TO NODE 12711.00 IS CODE = 21  
 -----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<  
 =====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 943.56  
 ELEVATION DATA: UPSTREAM(FEET) = 940.78 DOWNSTREAM(FEET) = 657.79

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
 SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 13.910  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.174  
 SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "GRASS"	B	6.56	0.30	1.000	69	13.91

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA RUNOFF(CFS) = 16.97  
 TOTAL AREA(ACRES) = 6.56 PEAK FLOW RATE(CFS) = 16.97

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12711.00 TO NODE 12712.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 657.79 DOWNSTREAM(FEET) = 585.63  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 766.00 CHANNEL SLOPE = 0.0942  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060



\*ESTIMATED CHANNEL HEIGHT (FEET) = 0.78  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.856  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	26.94	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 48.03  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.63  
 AVERAGE FLOW DEPTH (FEET) = 0.74 TRAVEL TIME (MIN.) = 2.27  
 Tc (MIN.) = 16.18  
 SUBAREA AREA (ACRES) = 26.94 SUBAREA RUNOFF (CFS) = 61.97  
 EFFECTIVE AREA (ACRES) = 33.50 AREA-AVERAGED Fm (INCH/HR) = 0.30  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA (ACRES) = 33.5 PEAK FLOW RATE (CFS) = 77.05  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 0.97

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 0.97 FLOW VELOCITY (FEET/SEC.) = 6.62  
 LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12712.00 = 1709.56 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12712.00 TO NODE 12713.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM (FEET) = 585.63 DOWNSTREAM (FEET) = 463.75  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1025.79 CHANNEL SLOPE = 0.1188  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 1.03  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.617  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	14.73	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 94.20  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.62  
 AVERAGE FLOW DEPTH (FEET) = 1.03 TRAVEL TIME (MIN.) = 2.24  
 Tc (MIN.) = 18.42  
 SUBAREA AREA (ACRES) = 14.73 SUBAREA RUNOFF (CFS) = 34.30  
 EFFECTIVE AREA (ACRES) = 48.23 AREA-AVERAGED Fm (INCH/HR) = 0.22  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.73  
 TOTAL AREA (ACRES) = 48.2 PEAK FLOW RATE (CFS) = 104.16  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 1.09

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 1.09 FLOW VELOCITY (FEET/SEC.) = 7.88  
 LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12713.00 = 2735.35 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12713.00 TO NODE 12714.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM (FEET) = 463.75 DOWNSTREAM (FEET) = 360.30  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1148.54 CHANNEL SLOPE = 0.0901  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 1.78  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.413  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	105.64	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 217.46  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 9.04  
 AVERAGE FLOW DEPTH (FEET) = 1.77 TRAVEL TIME (MIN.) = 2.12  
 Tc (MIN.) = 20.54  
 SUBAREA AREA (ACRES) = 105.64 SUBAREA RUNOFF (CFS) = 226.61  
 EFFECTIVE AREA (ACRES) = 153.87 AREA-AVERAGED Fm (INCH/HR) = 0.09  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.30  
 TOTAL AREA (ACRES) = 153.9 PEAK FLOW RATE (CFS) = 321.93  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 2.20

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 2.20 FLOW VELOCITY (FEET/SEC.) = 10.16  
 LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12714.00 = 3883.89 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12714.00 TO NODE 12720.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM (FEET) = 360.30 DOWNSTREAM (FEET) = 275.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1314.99 CHANNEL SLOPE = 0.0649  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 2.89  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.268  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	127.13	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 449.97  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 9.94  
 AVERAGE FLOW DEPTH (FEET) = 2.87 TRAVEL TIME (MIN.) = 2.20  
 Tc (MIN.) = 22.74  
 SUBAREA AREA (ACRES) = 127.13 SUBAREA RUNOFF (CFS) = 256.02

EFFECTIVE AREA(ACRES) = 281.00 AREA-AVERAGED Fm(INCH/HR) = 0.06  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.21  
 TOTAL AREA(ACRES) = 281.0 PEAK FLOW RATE(CFS) = 557.74  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 3.21

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 3.21 FLOW VELOCITY(FEET/SEC.) = 10.56  
 LONGEST FLOWPATH FROM NODE 12710.00 TO NODE 12720.00 = 5198.88 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
 TIME OF CONCENTRATION(MIN.) = 22.74  
 RAINFALL INTENSITY(INCH/HR) = 2.27  
 AREA-AVERAGED Fm(INCH/HR) = 0.06  
 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.21  
 EFFECTIVE STREAM AREA(ACRES) = 281.00  
 TOTAL STREAM AREA(ACRES) = 281.00  
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 557.74

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24825.05	18.17	2.644	0.30( 0.30)	0.99	4945.1	40500.00
1	26266.96	21.77	2.332	0.30( 0.30)	0.99	6103.0	40440.00
1	26928.87	24.87	2.127	0.30( 0.30)	0.99	7138.7	40200.00
1	30261.54	38.43	1.675	0.30( 0.30)	0.99	12420.8	40100.00
1	33192.17	47.40	1.470	0.30( 0.30)	0.99	15765.0	11801.00
1	36153.13	57.19	1.339	0.30( 0.30)	0.99	20061.2	11530.00
1	38510.76	65.94	1.270	0.30( 0.30)	0.99	25046.1	11910.00
1	40690.44	73.24	1.221	0.30( 0.30)	0.99	29646.5	11330.00
1	41803.22	79.67	1.178	0.30( 0.30)	0.99	34077.5	11130.00
1	41739.16	87.25	1.127	0.30( 0.30)	0.99	38071.5	12330.00
1	41692.53	89.84	1.110	0.30( 0.30)	0.99	39486.3	12410.00
1	41525.03	93.87	1.091	0.30( 0.30)	0.99	41414.7	12400.00
1	41032.48	102.49	1.052	0.30( 0.30)	0.99	44783.5	12201.00
1	40589.86	106.41	1.034	0.30( 0.30)	0.99	45868.1	12111.00
1	39966.88	111.72	1.010	0.30( 0.30)	0.99	47237.6	12101.10
1	39451.71	115.69	0.992	0.30( 0.30)	0.99	48086.7	10400.00
1	37920.25	123.55	0.963	0.30( 0.30)	0.99	49401.8	12010.00
1	36633.14	129.28	0.948	0.30( 0.30)	0.99	49715.5	10210.00
1	36267.73	131.92	0.941	0.30( 0.30)	0.99	49826.4	12000.00
1	33274.15	154.93	0.881	0.30( 0.30)	0.99	50448.3	10100.00
2	557.74	22.74	2.268	0.30( 0.06)	0.21	281.0	12710.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	--------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	25346.67	18.17	2.644	0.30( 0.29)	0.96	5169.6 40500.00
2	26816.43	21.77	2.332	0.30( 0.29)	0.96	6372.0 40440.00
3	27032.37	22.74	2.268	0.30( 0.29)	0.96	6708.9 12710.00
4	27450.98	24.87	2.127	0.30( 0.29)	0.96	7419.7 40200.00
5	30669.46	38.43	1.675	0.30( 0.29)	0.97	12701.8 40100.00
6	33548.21	47.40	1.470	0.30( 0.29)	0.98	16046.0 11801.00
7	36475.95	57.19	1.339	0.30( 0.29)	0.98	20342.2 11530.00
8	38816.27	65.94	1.270	0.30( 0.30)	0.98	25327.1 11910.00
9	40983.57	73.24	1.221	0.30( 0.30)	0.99	29927.5 11330.00
10	42085.46	79.67	1.178	0.30( 0.30)	0.99	34358.5 11130.00
11	42008.55	87.25	1.127	0.30( 0.30)	0.99	38352.5 12330.00
12	41957.53	89.84	1.110	0.30( 0.30)	0.99	39767.3 12410.00
13	41785.30	93.87	1.091	0.30( 0.30)	0.99	41695.7 12400.00
14	41282.80	102.49	1.052	0.30( 0.30)	0.99	45064.5 12201.00
15	40835.65	106.41	1.034	0.30( 0.30)	0.99	46149.1 12111.00
16	40206.54	111.72	1.010	0.30( 0.30)	0.99	47518.6 12101.10
17	39686.78	115.69	0.992	0.30( 0.30)	0.99	48367.7 10400.00
18	38148.00	123.55	0.963	0.30( 0.30)	0.99	49682.8 12010.00
19	36857.12	129.28	0.948	0.30( 0.30)	0.99	49996.5 10210.00
20	36489.99	131.92	0.941	0.30( 0.30)	0.99	50107.4 12000.00
21	33481.27	154.93	0.881	0.30( 0.30)	0.99	50729.3 10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 42085.46 Tc(MIN.) = 79.67  
 EFFECTIVE AREA(ACRES) = 34358.55 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 50729.3  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.00 = 106012.84 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 79.67  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.178  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	0.40	0.30	0.850	56
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.10	0.30	1.000	65
RESIDENTIAL "5-7 DWELLINGS/ACRE"	B	0.20	0.30	0.500	56
NATURAL FAIR COVER "OPEN BRUSH"	B	3.80	0.30	1.000	66

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.964  
 SUBAREA AREA(ACRES) = 4.50 SUBAREA RUNOFF(CFS) = 3.60  
 EFFECTIVE AREA(ACRES) = 34363.05 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99  
 TOTAL AREA(ACRES) = 50733.8 PEAK FLOW RATE(CFS) = 42085.46  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12720.00 TO NODE 12720.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 275.00 DOWNSTREAM(FEET) = 258.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 2669.21 CHANNEL SLOPE = 0.0064
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT(FEET) = 10.23

\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.160

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCSSOIL AREA Fp Ap SCSS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
COMMERCIAL B 62.15 0.30 0.100 56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 42117.07

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 16.40

AVERAGE FLOW DEPTH(FEET) = 10.23 TRAVEL TIME(MIN.) = 2.71

Tc(MIN.) = 82.38

SUBAREA AREA(ACRES) = 62.15 SUBAREA RUNOFF(CFS) = 63.21

EFFECTIVE AREA(ACRES) = 34425.20 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 50795.9 PEAK FLOW RATE(CFS) = 42085.46

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT(FEET) = 10.23

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 10.23 FLOW VELOCITY(FEET/SEC.) = 16.39

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108682.05 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 21 rows of data.

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 42085.46 Tc(MIN.) = 82.38

AREA-AVERAGED Fm(INCH/HR) = 0.30 AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.99 EFFECTIVE AREA(ACRES) = 34425.20

\*\*\*\*\*
FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 82.38

\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.160

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCSSOIL AREA Fp Ap SCSS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
COMMERCIAL B 0.10 0.30 0.100 56

NATURAL FAIR COVER

"MEADOWS" B 0.30 0.30 1.000 70

NATURAL FAIR COVER

"OPEN BRUSH" B 17.90 0.30 1.000 66

NATURAL FAIR COVER

"OPEN BRUSH" B 0.20 0.30 1.000 66

PUBLIC PARK B 0.30 0.30 0.850 56

NATURAL POOR COVER

"BARREN" B 0.70 0.30 1.000 86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.993

SUBAREA AREA(ACRES) = 19.50 SUBAREA RUNOFF(CFS) = 15.13

EFFECTIVE AREA(ACRES) = 34444.70 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 50815.4 PEAK FLOW RATE(CFS) = 42085.46

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*
FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 82.38

\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.160

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCSSOIL AREA Fp Ap SCSS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
RESIDENTIAL

"5-7 DWELLINGS/ACRE" B 0.10 0.30 0.500 56

NATURAL FAIR COVER

"WOODLAND,GRASS" B 1.10 0.30 1.000 65

NATURAL FAIR COVER

"WOODLAND,GRASS" B 0.90 0.30 1.000 65

RESIDENTIAL

".4 DWELLING/ACRE" B 0.60 0.30 0.900 56

RESIDENTIAL

".4 DWELLING/ACRE" B 0.30 0.30 0.900 56

NATURAL POOR COVER

"BARREN" B 0.50 0.30 1.000 86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.960

SUBAREA AREA(ACRES) = 3.50 SUBAREA RUNOFF(CFS) = 2.75

EFFECTIVE AREA(ACRES) = 34448.20 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA (ACRES) = 50818.9 PEAK FLOW RATE (CFS) = 42085.46

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 3D00EVRL.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	948.40	18.64	2.594	0.30 ( 0.14)	0.48	352.2	413.00
2	934.74	25.11	2.113	0.30 ( 0.14)	0.48	432.8	430.00
3	902.75	26.58	2.046	0.30 ( 0.14)	0.48	439.5	400.00
TOTAL AREA (ACRES) =							439.5

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25346.67	21.37	2.358	0.30 ( 0.28)	0.95	5259.3	40500.00
2	26816.43	24.91	2.124	0.30 ( 0.28)	0.95	6461.6	40440.00
3	27032.37	25.88	2.078	0.30 ( 0.28)	0.95	6798.6	12710.00
4	27450.98	27.99	1.982	0.30 ( 0.29)	0.95	7509.3	40200.00
5	30669.46	41.44	1.603	0.30 ( 0.29)	0.97	12791.4	40100.00
6	33548.21	50.32	1.409	0.30 ( 0.29)	0.98	16135.6	11801.00
7	36475.95	60.03	1.310	0.30 ( 0.29)	0.98	20431.8	11530.00
8	38816.27	68.73	1.252	0.30 ( 0.29)	0.98	25416.8	11910.00
9	40983.57	75.98	1.203	0.30 ( 0.30)	0.98	30017.2	11330.00
10	42085.46	82.38	1.160	0.30 ( 0.30)	0.99	34448.2	11130.00
11	42008.55	89.97	1.109	0.30 ( 0.30)	0.99	38442.2	12330.00
12	41957.53	92.56	1.097	0.30 ( 0.30)	0.99	39857.0	12410.00
13	41785.30	96.59	1.079	0.30 ( 0.30)	0.99	41785.3	12400.00
14	41282.80	105.22	1.039	0.30 ( 0.30)	0.99	45154.1	12201.00
15	40835.65	109.15	1.022	0.30 ( 0.30)	0.99	46238.8	12111.00
16	40206.54	114.47	0.997	0.30 ( 0.30)	0.99	47608.3	12101.10
17	39686.78	118.45	0.979	0.30 ( 0.30)	0.99	48457.3	10400.00
18	38148.00	126.35	0.955	0.30 ( 0.30)	0.99	49772.5	12010.00
19	36857.12	132.11	0.941	0.30 ( 0.30)	0.99	50086.2	10210.00
20	36489.99	134.76	0.934	0.30 ( 0.30)	0.99	50197.1	12000.00
21	33481.27	157.85	0.874	0.30 ( 0.30)	0.99	50818.9	10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 =							108682.05 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	948.40	18.64	2.594	0.30 ( 0.14)	0.48	352.2	413.00
2	934.74	25.11	2.113	0.30 ( 0.14)	0.48	432.8	430.00
3	902.75	26.58	2.046	0.30 ( 0.14)	0.48	439.5	400.00
LONGEST FLOWPATH FROM NODE 430.00 TO NODE 12720.50 =							11352.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25565.55	18.64	2.594	0.30 ( 0.27)	0.91	4939.6	413.00
2	26289.31	21.37	2.358	0.30 ( 0.27)	0.91	5645.5	40500.00
3	27751.59	24.91	2.124	0.30 ( 0.28)	0.92	6891.9	40440.00
4	27795.47	25.11	2.113	0.30 ( 0.28)	0.92	6963.5	430.00
5	27950.40	25.88	2.078	0.30 ( 0.28)	0.92	7234.9	12710.00
6	28074.18	26.58	2.046	0.30 ( 0.28)	0.92	7474.2	400.00
7	28323.36	27.99	1.982	0.30 ( 0.28)	0.93	7948.8	40200.00
8	31361.84	41.44	1.603	0.30 ( 0.29)	0.95	13230.9	40100.00
9	34148.49	50.32	1.409	0.30 ( 0.29)	0.96	16575.1	11801.00
10	37029.29	60.03	1.310	0.30 ( 0.29)	0.97	20871.3	11530.00
11	39341.96	68.73	1.252	0.30 ( 0.29)	0.97	25856.3	11910.00
12	41486.21	75.98	1.203	0.30 ( 0.29)	0.98	30456.7	11330.00
13	42567.74	82.38	1.160	0.30 ( 0.29)	0.98	34887.7	11130.00
14	42466.73	89.97	1.109	0.30 ( 0.29)	0.98	38881.7	12330.00
15	42410.06	92.56	1.097	0.30 ( 0.29)	0.98	40296.5	12410.00
16	42229.09	96.59	1.079	0.30 ( 0.29)	0.98	42224.8	12400.00
17	41707.89	105.22	1.039	0.30 ( 0.29)	0.98	45593.6	12201.00
18	41252.24	109.15	1.022	0.30 ( 0.29)	0.98	46678.3	12111.00
19	40611.59	114.47	0.997	0.30 ( 0.29)	0.98	48047.8	12101.10
20	40083.21	118.45	0.979	0.30 ( 0.29)	0.98	48896.8	10400.00
21	38533.24	126.35	0.955	0.30 ( 0.29)	0.98	50212.0	12010.00
22	37235.25	132.11	0.941	0.30 ( 0.29)	0.98	50525.7	10210.00
23	36864.85	134.76	0.934	0.30 ( 0.29)	0.98	50636.6	12000.00
24	33827.65	157.85	0.874	0.30 ( 0.29)	0.98	51258.4	10100.00
TOTAL AREA (ACRES) =							51258.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 42567.74 Tc (MIN.) = 82.385

EFFECTIVE AREA (ACRES) = 34887.70 AREA-AVERAGED Fm (INCH/HR) = 0.29

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97

TOTAL AREA (ACRES) = 51258.4

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12720.50 = 108682.05 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.50 TO NODE 12720.50 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 12720.50 TO NODE 12721.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 258.00 DOWNSTREAM (FEET) = 256.00

CHANNEL LENGTH THRU SUBAREA (FEET) = 438.77 CHANNEL SLOPE = 0.0046

GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT (FEET) = 11.30

CHANNEL FLOW THRU SUBAREA (CFS) = 42567.74

FLOW VELOCITY (FEET/SEC.) = 14.68 FLOW DEPTH (FEET) = 11.30

TRAVEL TIME (MIN.) = 0.50 Tc (MIN.) = 82.88

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12721.00 = 109120.82 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25565.55	19.23	2.531	0.30( 0.27)	0.91	4939.6	413.00
2	26289.31	21.95	2.320	0.30( 0.27)	0.91	5645.5	40500.00
3	27751.59	25.49	2.096	0.30( 0.28)	0.92	6891.9	40440.00
4	27795.47	25.68	2.087	0.30( 0.28)	0.92	6963.5	430.00
5	27950.40	26.45	2.052	0.30( 0.28)	0.92	7234.9	12710.00
6	28074.18	27.15	2.020	0.30( 0.28)	0.92	7474.2	400.00
7	28323.36	28.56	1.956	0.30( 0.28)	0.93	7948.8	40200.00
8	31361.84	41.99	1.591	0.30( 0.29)	0.95	13230.9	40100.00
9	34148.49	50.86	1.403	0.30( 0.29)	0.96	16575.1	11801.00
10	37029.29	60.55	1.306	0.30( 0.29)	0.97	20871.3	11530.00
11	39341.96	69.24	1.248	0.30( 0.29)	0.97	25856.3	11910.00
12	41486.21	76.48	1.200	0.30( 0.29)	0.98	30456.7	11330.00
13	42567.74	82.88	1.157	0.30( 0.29)	0.98	34887.7	11130.00
14	42466.73	90.46	1.107	0.30( 0.29)	0.98	38881.7	12330.00
15	42410.06	93.06	1.095	0.30( 0.29)	0.98	40296.5	12410.00
16	42229.09	97.09	1.077	0.30( 0.29)	0.98	42224.8	12400.00
17	41707.89	105.72	1.037	0.30( 0.29)	0.98	45593.6	12201.00
18	41252.24	109.65	1.019	0.30( 0.29)	0.98	46678.3	12111.00
19	40611.59	114.97	0.995	0.30( 0.29)	0.98	48047.8	12101.10
20	40083.21	118.96	0.977	0.30( 0.29)	0.98	48896.8	10400.00
21	38533.24	126.87	0.954	0.30( 0.29)	0.98	50212.0	12010.00
22	37235.25	132.63	0.939	0.30( 0.29)	0.98	50525.7	10210.00
23	36864.85	135.28	0.932	0.30( 0.29)	0.98	50636.6	12000.00
24	33827.65	158.39	0.872	0.30( 0.29)	0.98	51258.4	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 42567.74 Tc(MIN.) = 82.88  
 AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.98 EFFECTIVE AREA(ACRES) = 34887.70

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12721.00 TO NODE 12722.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 256.00 DOWNSTREAM(FEET) = 255.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 830.42 CHANNEL SLOPE = 0.0012  
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 16.31

\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.147

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	11.24	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 42573.39  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.27  
 AVERAGE FLOW DEPTH(FEET) = 16.31 TRAVEL TIME(MIN.) = 1.49  
 Tc(MIN.) = 84.38  
 SUBAREA AREA(ACRES) = 11.24 SUBAREA RUNOFF(CFS) = 11.30  
 EFFECTIVE AREA(ACRES) = 34898.93 AREA-AVERAGED Fm(INCH/HR) = 0.29  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98  
 TOTAL AREA(ACRES) = 51269.7 PEAK FLOW RATE(CFS) = 42567.74  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 16.30

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 16.30 FLOW VELOCITY(FEET/SEC.) = 9.28  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12722.00 = 109951.24 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25565.55	20.98	2.384	0.30( 0.27)	0.91	4950.9	413.00
2	26289.31	23.68	2.205	0.30( 0.27)	0.91	5656.7	40500.00
3	27751.59	27.19	2.019	0.30( 0.28)	0.92	6903.2	40440.00
4	27795.47	27.38	2.010	0.30( 0.28)	0.92	6974.8	430.00
5	27950.40	28.15	1.975	0.30( 0.28)	0.92	7246.1	12710.00
6	28074.18	28.85	1.943	0.30( 0.28)	0.92	7485.4	400.00
7	28323.36	30.25	1.885	0.30( 0.28)	0.93	7960.1	40200.00
8	31361.84	43.63	1.554	0.30( 0.29)	0.95	13242.2	40100.00
9	34148.49	52.45	1.387	0.30( 0.29)	0.96	16586.4	11801.00
10	37029.29	62.11	1.296	0.30( 0.29)	0.97	20882.5	11530.00
11	39341.96	70.76	1.238	0.30( 0.29)	0.97	25867.5	11910.00
12	41486.21	77.99	1.189	0.30( 0.29)	0.98	30467.9	11330.00
13	42567.74	84.38	1.147	0.30( 0.29)	0.98	34898.9	11130.00
14	42466.73	91.96	1.100	0.30( 0.29)	0.98	38892.9	12330.00
15	42410.06	94.55	1.088	0.30( 0.29)	0.98	40307.7	12410.00
16	42229.09	98.59	1.070	0.30( 0.29)	0.98	42236.1	12400.00
17	41707.89	107.23	1.030	0.30( 0.29)	0.98	45604.9	12201.00
18	41252.24	111.16	1.012	0.30( 0.29)	0.98	46689.5	12111.00
19	40611.59	116.49	0.988	0.30( 0.29)	0.98	48059.0	12101.10
20	40083.21	120.48	0.971	0.30( 0.29)	0.98	48908.1	10400.00
21	38533.24	128.41	0.950	0.30( 0.29)	0.98	50223.2	12010.00
22	37235.25	134.19	0.935	0.30( 0.29)	0.98	50536.9	10210.00
23	36864.85	136.84	0.928	0.30( 0.29)	0.98	50647.8	12000.00
24	33827.65	159.99	0.868	0.30( 0.29)	0.98	51269.7	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 42567.74 Tc(MIN.) = 84.38  
 AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.98 EFFECTIVE AREA(ACRES) = 34898.93

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12722.00 TO NODE 12722.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 84.38  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.147

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER "BARREN"	B	2.10	0.30	1.000	86
NATURAL FAIR COVER "GRASS"	B	0.10	0.30	1.000	69
NATURAL FAIR COVER "MEADOWS"	B	3.60	0.30	1.000	70
NATURAL FAIR COVER "OPEN BRUSH"	B	4.10	0.30	1.000	66

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 9.90 SUBAREA RUNOFF(CFS) = 7.54  
 EFFECTIVE AREA(ACRES) = 34908.83 AREA-AVERAGED Fm(INCH/HR) = 0.29  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98  
 TOTAL AREA(ACRES) = 51279.6 PEAK FLOW RATE(CFS) = 42567.74  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12722.00 TO NODE 12722.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 84.38  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.147  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL ".4 DWELLING/ACRE"	B	0.60	0.30	0.900	56
NATURAL FAIR COVER "WOODLAND,GRASS"	B	1.90	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.10	0.30	1.000	65

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.977  
 SUBAREA AREA(ACRES) = 2.60 SUBAREA RUNOFF(CFS) = 2.00  
 EFFECTIVE AREA(ACRES) = 34911.43 AREA-AVERAGED Fm(INCH/HR) = 0.29  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98  
 TOTAL AREA(ACRES) = 51282.2 PEAK FLOW RATE(CFS) = 42567.74  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12722.00 TO NODE 12740.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 255.00 DOWNSTREAM(FEET) = 252.10  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 624.00 CHANNEL SLOPE = 0.0046  
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 11.24  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.142  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	1.50	0.30	0.100	56
NATURAL FAIR COVER "GRASS"	B	2.50	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	0.50	0.30	1.000	69
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.70	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND,GRASS"	B	6.20	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND,GRASS"	B	6.50	0.30	1.000	65

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.925  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 42574.71  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 14.78  
 AVERAGE FLOW DEPTH(FEET) = 11.24 TRAVEL TIME(MIN.) = 0.70  
 Tc(MIN.) = 85.08  
 SUBAREA AREA(ACRES) = 17.90 SUBAREA RUNOFF(CFS) = 13.93  
 EFFECTIVE AREA(ACRES) = 34929.33 AREA-AVERAGED Fm(INCH/HR) = 0.29  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98  
 TOTAL AREA(ACRES) = 51300.1 PEAK FLOW RATE(CFS) = 42567.74  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 11.24

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 11.24 FLOW VELOCITY(FEET/SEC.) = 14.78  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12740.00 = 110575.24 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25565.55	21.81	2.329	0.30( 0.27)	0.91	4981.3	413.00
2	26289.31	24.51	2.151	0.30( 0.27)	0.91	5687.1	40500.00
3	27751.59	28.00	1.982	0.30( 0.28)	0.92	6933.6	40440.00
4	27795.47	28.19	1.973	0.30( 0.28)	0.92	7005.2	430.00
5	27950.40	28.95	1.939	0.30( 0.28)	0.92	7276.5	12710.00
6	28074.18	29.65	1.907	0.30( 0.28)	0.92	7515.8	400.00
7	28323.36	31.05	1.864	0.30( 0.28)	0.93	7990.5	40200.00
8	31361.84	44.41	1.537	0.30( 0.29)	0.95	13272.6	40100.00
9	34148.49	53.21	1.379	0.30( 0.29)	0.96	16616.8	11801.00
10	37029.29	62.85	1.291	0.30( 0.29)	0.97	20912.9	11530.00
11	39341.96	71.49	1.233	0.30( 0.29)	0.97	25897.9	11910.00
12	41486.21	78.70	1.185	0.30( 0.29)	0.98	30498.3	11330.00
13	42567.74	85.08	1.142	0.30( 0.29)	0.98	34929.3	11130.00
14	42466.73	92.66	1.097	0.30( 0.29)	0.98	38923.3	12330.00
15	42410.06	95.26	1.085	0.30( 0.29)	0.98	40338.1	12410.00
16	42229.09	99.29	1.067	0.30( 0.29)	0.98	42266.5	12400.00
17	41707.89	107.93	1.027	0.30( 0.29)	0.98	45635.3	12201.00
18	41252.24	111.87	1.009	0.30( 0.29)	0.98	46719.9	12111.00
19	40611.59	117.20	0.985	0.30( 0.29)	0.98	48089.4	12101.10
20	40083.21	121.20	0.969	0.30( 0.29)	0.98	48938.5	10400.00
21	38533.24	129.13	0.948	0.30( 0.29)	0.98	50253.6	12010.00
22	37235.25	134.92	0.933	0.30( 0.29)	0.98	50567.3	10210.00
23	36864.85	137.58	0.926	0.30( 0.29)	0.98	50678.2	12000.00
24	33827.65	160.75	0.866	0.30( 0.29)	0.98	51300.1	10100.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE(CFS) = 42567.74 Tc(MIN.) = 85.08  
 AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.98 EFFECTIVE AREA(ACRES) = 34929.33

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 85.08  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.142

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	4.70	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	6.70	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	12.00	0.30	1.000	66
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	B	0.80	0.30	1.000	63
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	B	20.20	0.30	1.000	63

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA(ACRES) = 44.40 SUBAREA RUNOFF(CFS) = 33.65  
EFFECTIVE AREA(ACRES) = 34973.73 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98  
TOTAL AREA(ACRES) = 51344.4 PEAK FLOW RATE(CFS) = 42567.74  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
TIME OF CONCENTRATION(MIN.) = 85.08  
RAINFALL INTENSITY(INCH/HR) = 1.14  
AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.98  
EFFECTIVE STREAM AREA(ACRES) = 34973.73  
TOTAL STREAM AREA(ACRES) = 51344.45  
PEAK FLOW RATE(CFS) AT CONFLUENCE = 42567.74

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12730.00 TO NODE 12731.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 561.54  
ELEVATION DATA: UPSTREAM(FEET) = 613.29 DOWNSTREAM(FEET) = 551.75

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 13.823  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.189  
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	B	6.33	0.30	1.000	63	13.82

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA RUNOFF(CFS) = 16.46  
TOTAL AREA(ACRES) = 6.33 PEAK FLOW RATE(CFS) = 16.46

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12731.00 TO NODE 12732.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 551.75 DOWNSTREAM(FEET) = 494.40  
CHANNEL LENGTH THRU SUBAREA(FEET) = 971.91 CHANNEL SLOPE = 0.0590  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.98  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.774  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	34.62	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 59.27  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.19  
AVERAGE FLOW DEPTH(FEET) = 0.96 TRAVEL TIME(MIN.) = 3.12  
Tc(MIN.) = 16.94  
SUBAREA AREA(ACRES) = 34.62 SUBAREA RUNOFF(CFS) = 85.50  
EFFECTIVE AREA(ACRES) = 40.95 AREA-AVERAGED Fm(INCH/HR) = 0.07  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.24  
TOTAL AREA(ACRES) = 40.9 PEAK FLOW RATE(CFS) = 99.59  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.29

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 1.29 FLOW VELOCITY(FEET/SEC.) = 6.12  
LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12732.00 = 1533.45 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12732.00 TO NODE 12733.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 494.40 DOWNSTREAM(FEET) = 431.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1156.41 CHANNEL SLOPE = 0.0548  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.79  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.481  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	59.52	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 165.34  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.00  
AVERAGE FLOW DEPTH(FEET) = 1.75 TRAVEL TIME(MIN.) = 2.75  
Tc(MIN.) = 19.70  
SUBAREA AREA(ACRES) = 59.52 SUBAREA RUNOFF(CFS) = 131.30

EFFECTIVE AREA (ACRES) = 100.47 AREA-AVERAGED Fm (INCH/HR) = 0.05  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.16  
TOTAL AREA (ACRES) = 100.5 PEAK FLOW RATE (CFS) = 220.09  
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 2.05

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 2.05 FLOW VELOCITY (FEET/SEC.) = 7.63  
LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12733.00 = 2689.86 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12733.00 TO NODE 12734.00 IS CODE = 56

-----  
>>>> COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>> TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 431.00 DOWNSTREAM (FEET) = 367.10  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1654.48 CHANNEL SLOPE = 0.0386  
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 2.61  
\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.217

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	64.05	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 283.17  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 7.23  
AVERAGE FLOW DEPTH (FEET) = 2.58 TRAVEL TIME (MIN.) = 3.81  
Tc (MIN.) = 23.51

SUBAREA AREA (ACRES) = 64.05 SUBAREA RUNOFF (CFS) = 126.05  
EFFECTIVE AREA (ACRES) = 164.52 AREA-AVERAGED Fm (INCH/HR) = 0.04  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.13  
TOTAL AREA (ACRES) = 164.5 PEAK FLOW RATE (CFS) = 322.23  
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 2.76

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 2.76 FLOW VELOCITY (FEET/SEC.) = 7.51  
LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12734.00 = 4344.34 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12734.00 TO NODE 12740.00 IS CODE = 56

-----  
>>>> COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>> TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 367.11 DOWNSTREAM (FEET) = 252.10  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1880.98 CHANNEL SLOPE = 0.0611  
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 2.55  
\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.028

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	26.02	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.100  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 345.63  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 9.03  
AVERAGE FLOW DEPTH (FEET) = 2.54 TRAVEL TIME (MIN.) = 3.47  
Tc (MIN.) = 26.98

SUBAREA AREA (ACRES) = 26.02 SUBAREA RUNOFF (CFS) = 46.79  
EFFECTIVE AREA (ACRES) = 190.54 AREA-AVERAGED Fm (INCH/HR) = 0.04  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.13  
TOTAL AREA (ACRES) = 190.5 PEAK FLOW RATE (CFS) = 341.10  
GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 2.52

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 2.52 FLOW VELOCITY (FEET/SEC.) = 9.00  
LONGEST FLOWPATH FROM NODE 12730.00 TO NODE 12740.00 = 6225.32 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12740.00 TO NODE 12740.00 IS CODE = 1

-----  
>>>> DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
>>>> AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
TIME OF CONCENTRATION (MIN.) = 26.98  
RAINFALL INTENSITY (INCH/HR) = 2.03  
AREA-AVERAGED Fm (INCH/HR) = 0.04  
AREA-AVERAGED Fp (INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.13  
EFFECTIVE STREAM AREA (ACRES) = 190.54  
TOTAL STREAM AREA (ACRES) = 190.54  
PEAK FLOW RATE (CFS) AT CONFLUENCE = 341.10

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25565.55	21.81	2.329	0.30 ( 0.27)	0.91	5025.7	413.00
1	26289.31	24.51	2.151	0.30 ( 0.27)	0.91	5731.5	40500.00
1	27751.59	28.00	1.982	0.30 ( 0.28)	0.92	6978.0	40440.00
1	27795.47	28.19	1.973	0.30 ( 0.28)	0.92	7049.6	430.00
1	27950.40	28.95	1.939	0.30 ( 0.28)	0.92	7320.9	12710.00
1	28074.18	29.65	1.907	0.30 ( 0.28)	0.92	7560.2	400.00
1	28323.36	31.05	1.864	0.30 ( 0.28)	0.93	8034.9	40200.00
1	31361.84	44.41	1.537	0.30 ( 0.29)	0.95	13317.0	40100.00
1	34148.49	53.21	1.379	0.30 ( 0.29)	0.96	16661.2	11801.00
1	37029.29	62.85	1.291	0.30 ( 0.29)	0.97	20957.3	11530.00
1	39341.96	71.49	1.233	0.30 ( 0.29)	0.97	25942.3	11910.00
1	41486.21	78.70	1.185	0.30 ( 0.29)	0.98	30542.7	11330.00
1	42567.74	85.08	1.142	0.30 ( 0.29)	0.98	34973.7	11130.00
1	42466.73	92.66	1.097	0.30 ( 0.29)	0.98	38967.7	12330.00
1	42410.06	95.26	1.085	0.30 ( 0.29)	0.98	40382.5	12410.00
1	42229.09	99.29	1.067	0.30 ( 0.29)	0.98	42310.9	12400.00
1	41707.89	107.93	1.027	0.30 ( 0.29)	0.98	45679.7	12201.00



1	41252.24	111.87	1.009	0.30 ( 0.29)	0.98	46764.3	12111.00
1	40611.59	117.20	0.985	0.30 ( 0.29)	0.98	48133.8	12101.10
1	40083.21	121.20	0.969	0.30 ( 0.29)	0.98	48982.9	10400.00
1	38533.24	129.13	0.948	0.30 ( 0.29)	0.98	50298.0	12010.00
1	37235.25	134.92	0.933	0.30 ( 0.29)	0.98	50611.7	10210.00
1	36864.85	137.58	0.926	0.30 ( 0.29)	0.98	50722.6	12000.00
1	33827.65	160.75	0.866	0.30 ( 0.29)	0.98	51344.4	10100.00
2	341.10	26.98	2.028	0.30 ( 0.04)	0.13	190.5	12730.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\*\* PEAK FLOW RATE TABLE \*\*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25883.00	21.81	2.329	0.30 ( 0.27)	0.89	5179.7	413.00
2	26618.23	24.51	2.151	0.30 ( 0.27)	0.89	5904.6	40500.00
3	27667.17	26.98	2.028	0.30 ( 0.27)	0.90	6805.8	12730.00
4	28084.79	28.00	1.982	0.30 ( 0.27)	0.90	7168.5	40440.00
5	28127.14	28.19	1.973	0.30 ( 0.27)	0.90	7240.1	430.00
6	28276.14	28.95	1.939	0.30 ( 0.27)	0.90	7511.5	12710.00
7	28394.49	29.65	1.907	0.30 ( 0.27)	0.90	7750.8	400.00
8	28636.34	31.05	1.864	0.30 ( 0.27)	0.91	8225.4	40200.00
9	31618.69	44.41	1.537	0.30 ( 0.28)	0.94	13507.5	40100.00
10	34378.34	53.21	1.379	0.30 ( 0.29)	0.95	16851.7	11801.00
11	37243.98	62.85	1.291	0.30 ( 0.29)	0.96	21147.9	11530.00
12	39546.73	71.49	1.233	0.30 ( 0.29)	0.97	26132.8	11910.00
13	41682.69	78.70	1.185	0.30 ( 0.29)	0.97	30733.3	11330.00
14	42756.89	85.08	1.142	0.30 ( 0.29)	0.97	35164.3	11130.00
15	42648.14	92.66	1.097	0.30 ( 0.29)	0.98	39158.2	12330.00
16	42589.44	95.26	1.085	0.30 ( 0.29)	0.98	40573.1	12410.00
17	42405.31	99.29	1.067	0.30 ( 0.29)	0.98	42501.4	12400.00
18	41877.34	107.93	1.027	0.30 ( 0.29)	0.98	45870.2	12201.00
19	41418.61	111.87	1.009	0.30 ( 0.29)	0.98	46954.9	12111.00
20	40773.78	117.20	0.985	0.30 ( 0.29)	0.98	48324.3	12101.10
21	40242.68	121.20	0.969	0.30 ( 0.29)	0.98	49173.4	10400.00
22	38689.17	129.13	0.948	0.30 ( 0.29)	0.98	50488.6	12010.00
23	37388.60	134.92	0.933	0.30 ( 0.29)	0.98	50802.3	10210.00
24	37017.01	137.58	0.926	0.30 ( 0.29)	0.98	50913.1	12000.00
25	33969.49	160.75	0.866	0.30 ( 0.29)	0.98	51535.0	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 42756.89 Tc(MIN.) = 85.08  
EFFECTIVE AREA(ACRES) = 35164.27 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97  
TOTAL AREA(ACRES) = 51535.0  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12740.00 = 110575.24 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12740.00 TO NODE 12741.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 252.10 DOWNSTREAM(FEET) = 247.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 401.47 CHANNEL SLOPE = 0.0127  
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT(FEET) = 8.49  
CHANNEL FLOW THRU SUBAREA(CFS) = 42756.89  
FLOW VELOCITY(FEET/SEC.) = 20.78 FLOW DEPTH(FEET) = 8.49  
TRAVEL TIME(MIN.) = 0.32 Tc(MIN.) = 85.40  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12741.00 = 110976.71 FEET.

\*\*\* PEAK FLOW RATE TABLE \*\*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25883.00	22.19	2.304	0.30 ( 0.27)	0.89	5179.7	413.00
2	26618.23	24.89	2.126	0.30 ( 0.27)	0.89	5904.6	40500.00
3	27667.17	27.35	2.011	0.30 ( 0.27)	0.90	6805.8	12730.00
4	28084.79	28.37	1.965	0.30 ( 0.27)	0.90	7168.5	40440.00
5	28127.14	28.56	1.956	0.30 ( 0.27)	0.90	7240.1	430.00
6	28276.14	29.32	1.922	0.30 ( 0.27)	0.90	7511.5	12710.00
7	28394.49	30.02	1.890	0.30 ( 0.27)	0.90	7750.8	400.00
8	28636.34	31.42	1.855	0.30 ( 0.27)	0.91	8225.4	40200.00
9	31618.69	44.76	1.529	0.30 ( 0.28)	0.94	13507.5	40100.00
10	34378.34	53.55	1.376	0.30 ( 0.29)	0.95	16851.7	11801.00
11	37243.98	63.18	1.289	0.30 ( 0.29)	0.96	21147.9	11530.00
12	39546.73	71.82	1.231	0.30 ( 0.29)	0.97	26132.8	11910.00
13	41682.69	79.02	1.183	0.30 ( 0.29)	0.97	30733.3	11330.00
14	42756.89	85.40	1.140	0.30 ( 0.29)	0.97	35164.3	11130.00
15	42648.14	92.98	1.095	0.30 ( 0.29)	0.98	39158.2	12330.00
16	42589.44	95.58	1.084	0.30 ( 0.29)	0.98	40573.1	12410.00
17	42405.31	99.61	1.065	0.30 ( 0.29)	0.98	42501.4	12400.00
18	41877.34	108.26	1.026	0.30 ( 0.29)	0.98	45870.2	12201.00
19	41418.61	112.19	1.008	0.30 ( 0.29)	0.98	46954.9	12111.00
20	40773.78	117.53	0.983	0.30 ( 0.29)	0.98	48324.3	12101.10
21	40242.68	121.53	0.968	0.30 ( 0.29)	0.98	49173.4	10400.00
22	38689.17	129.46	0.947	0.30 ( 0.29)	0.98	50488.6	12010.00
23	37388.60	135.26	0.932	0.30 ( 0.29)	0.98	50802.3	10210.00
24	37017.01	137.92	0.925	0.30 ( 0.29)	0.98	50913.1	12000.00
25	33969.49	161.09	0.865	0.30 ( 0.29)	0.98	51535.0	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 42756.89 Tc(MIN.) = 85.40  
AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.97 EFFECTIVE AREA(ACRES) = 35164.27

\*\*\*\*\*

FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 85.40

\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.140

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	2.10	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	7.50	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.90	0.30	1.000	66
PUBLIC PARK	B	1.90	0.30	0.850	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.40	0.30	0.900	56
AGRICULTURAL POOR COVER					

"ROW CROPS, CONTOURED" B 0.50 0.30 1.000 79  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.833  
 SUBAREA AREA (ACRES) = 13.30 SUBAREA RUNOFF (CFS) = 10.65  
 EFFECTIVE AREA (ACRES) = 35177.57 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97  
 TOTAL AREA (ACRES) = 51548.3 PEAK FLOW RATE (CFS) = 42756.89  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 85.40

\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.140

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

NATURAL FAIR COVER

"WOODLAND, GRASS" B 0.90 0.30 1.000 65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 0.90 SUBAREA RUNOFF (CFS) = 0.68

EFFECTIVE AREA (ACRES) = 35178.47 AREA-AVERAGED Fm (INCH/HR) = 0.29

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97

TOTAL AREA (ACRES) = 51549.2 PEAK FLOW RATE (CFS) = 42756.89

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 3C00EVRL.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1550.35	17.30	0.30 ( 0.14)	0.47	637.2	300.00
2	1552.52	22.46	0.30 ( 0.14)	0.48	778.6	327.00
3	1526.84	23.58	0.30 ( 0.14)	0.48	793.2	350.00
4	1497.17	24.64	0.30 ( 0.14)	0.48	804.5	320.00
5	1389.98	28.81	0.30 ( 0.15)	0.49	834.0	306.00
6	1287.71	35.32	0.30 ( 0.15)	0.50	870.6	390.00
TOTAL AREA (ACRES) =						870.6

\*\*\*\*\*

FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25883.00	22.19	2.304	0.30 ( 0.27)	0.89	5193.9	413.00
2	26618.23	24.89	2.126	0.30 ( 0.27)	0.89	5918.8	40500.00
3	27667.17	27.35	2.011	0.30 ( 0.27)	0.90	6820.0	12730.00

4	28084.79	28.37	1.965	0.30 ( 0.27)	0.90	7182.7	40440.00
5	28127.14	28.56	1.956	0.30 ( 0.27)	0.90	7254.3	430.00
6	28276.14	29.32	1.922	0.30 ( 0.27)	0.90	7525.7	12710.00
7	28394.49	30.02	1.890	0.30 ( 0.27)	0.90	7765.0	400.00
8	28636.34	31.42	1.855	0.30 ( 0.27)	0.91	8239.6	40200.00
9	31618.69	44.76	1.529	0.30 ( 0.28)	0.94	13521.7	40100.00
10	34378.34	53.55	1.376	0.30 ( 0.29)	0.95	16865.9	11801.00
11	37243.98	63.18	1.289	0.30 ( 0.29)	0.96	21162.1	11530.00
12	39546.73	71.82	1.231	0.30 ( 0.29)	0.97	26147.0	11910.00
13	41682.69	79.02	1.183	0.30 ( 0.29)	0.97	30747.5	11330.00
14	42756.89	85.40	1.140	0.30 ( 0.29)	0.97	35178.5	11130.00
15	42648.14	92.98	1.095	0.30 ( 0.29)	0.98	39172.4	12330.00
16	42589.44	95.58	1.084	0.30 ( 0.29)	0.98	40587.3	12410.00
17	42405.31	99.61	1.065	0.30 ( 0.29)	0.98	42515.6	12400.00
18	41877.34	108.26	1.026	0.30 ( 0.29)	0.98	45884.4	12201.00
19	41418.61	112.19	1.008	0.30 ( 0.29)	0.98	46969.1	12111.00
20	40773.78	117.53	0.983	0.30 ( 0.29)	0.98	48338.5	12101.10
21	40242.68	121.53	0.968	0.30 ( 0.29)	0.98	49187.6	10400.00
22	38689.17	129.46	0.947	0.30 ( 0.29)	0.98	50502.8	12010.00
23	37388.60	135.26	0.932	0.30 ( 0.29)	0.98	50816.5	10210.00
24	37017.01	137.92	0.925	0.30 ( 0.29)	0.98	50927.3	12000.00
25	33969.49	161.09	0.865	0.30 ( 0.29)	0.98	51549.2	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12741.00 = 110976.71 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1550.35	17.30	2.737	0.30 ( 0.14)	0.47	637.2	300.00
2	1552.52	22.46	2.286	0.30 ( 0.14)	0.48	778.6	327.00
3	1526.84	23.58	2.212	0.30 ( 0.14)	0.48	793.2	350.00
4	1497.17	24.64	2.142	0.30 ( 0.14)	0.48	804.5	320.00
5	1389.98	28.81	1.945	0.30 ( 0.15)	0.49	834.0	306.00
6	1287.71	35.32	1.755	0.30 ( 0.15)	0.50	870.6	390.00

LONGEST FLOWPATH FROM NODE 390.00 TO NODE 12741.00 = 15238.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	26009.96	17.30	2.737	0.30 ( 0.25)	0.83	4686.0	300.00
2	27435.41	22.19	2.304	0.30 ( 0.25)	0.84	5965.1	413.00
3	27508.60	22.46	2.286	0.30 ( 0.25)	0.84	6044.5	327.00
4	27789.40	23.58	2.212	0.30 ( 0.25)	0.84	6361.3	350.00
5	28049.77	24.64	2.142	0.30 ( 0.25)	0.84	6658.6	320.00
6	28109.21	24.89	2.126	0.30 ( 0.25)	0.84	6725.0	40500.00
7	29094.64	27.35	2.011	0.30 ( 0.26)	0.85	7643.7	12730.00
8	29486.19	28.37	1.965	0.30 ( 0.26)	0.86	8013.5	40440.00
9	29523.50	28.56	1.956	0.30 ( 0.26)	0.86	8086.5	430.00
10	29565.68	28.81	1.945	0.30 ( 0.26)	0.86	8176.7	306.00
11	29658.06	29.32	1.922	0.30 ( 0.26)	0.86	8362.5	12710.00
12	29765.46	30.02	1.890	0.30 ( 0.26)	0.86	8605.7	400.00
13	29985.30	31.42	1.855	0.30 ( 0.26)	0.87	9088.3	40200.00
14	30795.69	35.32	1.755	0.30 ( 0.27)	0.88	10654.0	390.00
15	32724.95	44.76	1.529	0.30 ( 0.27)	0.92	14392.3	40100.00
16	35361.74	53.55	1.376	0.30 ( 0.28)	0.93	17736.5	11801.00
17	38157.45	63.18	1.289	0.30 ( 0.28)	0.94	22032.7	11530.00
18	40413.77	71.82	1.231	0.30 ( 0.29)	0.95	27017.6	11910.00
19	42510.98	79.02	1.183	0.30 ( 0.29)	0.96	31618.1	11330.00
20	43550.86	85.40	1.140	0.30 ( 0.29)	0.96	36049.1	11130.00

21	43406.44	92.98	1.095	0.30	( 0.29)	0.97	40043.0	12330.00
22	43338.22	95.58	1.084	0.30	( 0.29)	0.97	41457.9	12410.00
23	43139.30	99.61	1.065	0.30	( 0.29)	0.97	43386.2	12400.00
24	42579.63	108.26	1.026	0.30	( 0.29)	0.97	46755.0	12201.00
25	42106.47	112.19	1.008	0.30	( 0.29)	0.97	47839.7	12111.00
26	41442.08	117.53	0.983	0.30	( 0.29)	0.97	49209.1	12101.10
27	40898.73	121.53	0.968	0.30	( 0.29)	0.97	50058.2	10400.00
28	39328.66	129.46	0.947	0.30	( 0.29)	0.97	51373.4	12010.00
29	38016.00	135.26	0.932	0.30	( 0.29)	0.97	51687.1	10210.00
30	37638.86	137.92	0.925	0.30	( 0.29)	0.97	51797.9	12000.00
31	34542.95	161.09	0.865	0.30	( 0.29)	0.97	52419.8	10100.00

TOTAL AREA (ACRES) = 52419.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 43550.86 Tc (MIN.) = 85.401  
EFFECTIVE AREA (ACRES) = 36049.07 AREA-AVERAGED Fm (INCH/HR) = 0.29  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.88  
TOTAL AREA (ACRES) = 52419.8  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12741.00 = 110976.71 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12741.00 TO NODE 12741.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12741.00 TO NODE 12800.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 247.00 DOWNSTREAM (FEET) = 240.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 819.00 CHANNEL SLOPE = 0.0085  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 9.59  
CHANNEL FLOW THRU SUBAREA (CFS) = 43550.86  
FLOW VELOCITY (FEET/SEC.) = 18.30 FLOW DEPTH (FEET) = 9.59  
TRAVEL TIME (MIN.) = 0.75 Tc (MIN.) = 86.15  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111795.71 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	26009.96	18.18	2.643	0.30 ( 0.25)	0.83	4686.0	300.00
2	27435.41	23.06	2.247	0.30 ( 0.25)	0.84	5965.1	413.00
3	27508.60	23.32	2.229	0.30 ( 0.25)	0.84	6044.5	327.00
4	27789.40	24.45	2.155	0.30 ( 0.25)	0.84	6361.3	350.00
5	28049.77	25.51	2.095	0.30 ( 0.25)	0.84	6658.6	320.00
6	28109.21	25.75	2.084	0.30 ( 0.25)	0.84	6725.0	40500.00
7	29094.64	28.21	1.972	0.30 ( 0.26)	0.85	7643.7	12730.00
8	29486.19	29.22	1.927	0.30 ( 0.26)	0.86	8013.5	40440.00
9	29523.50	29.41	1.918	0.30 ( 0.26)	0.86	8086.5	430.00
10	29565.68	29.66	1.907	0.30 ( 0.26)	0.86	8176.7	306.00
11	29658.06	30.17	1.887	0.30 ( 0.26)	0.86	8362.5	12710.00
12	29765.46	30.87	1.869	0.30 ( 0.26)	0.86	8605.7	400.00
13	29985.30	32.26	1.833	0.30 ( 0.26)	0.87	9088.3	40200.00

14	30795.69	36.16	1.733	0.30	( 0.27)	0.88	10654.0	390.00
15	32724.95	45.58	1.511	0.30	( 0.27)	0.92	14392.3	40100.00
16	35361.74	54.35	1.368	0.30	( 0.28)	0.93	17736.5	11801.00
17	38157.45	63.96	1.283	0.30	( 0.28)	0.94	22032.7	11530.00
18	40413.77	72.58	1.226	0.30	( 0.29)	0.95	27017.6	11910.00
19	42510.98	79.77	1.178	0.30	( 0.29)	0.96	31618.1	11330.00
20	43550.86	86.15	1.135	0.30	( 0.29)	0.96	36049.1	11130.00
21	43406.44	93.73	1.092	0.30	( 0.29)	0.97	40043.0	12330.00
22	43338.22	96.33	1.080	0.30	( 0.29)	0.97	41457.9	12410.00
23	43139.30	100.36	1.062	0.30	( 0.29)	0.97	43386.2	12400.00
24	42579.63	109.01	1.022	0.30	( 0.29)	0.97	46755.0	12201.00
25	42106.47	112.95	1.004	0.30	( 0.29)	0.97	47839.7	12111.00
26	41442.08	118.29	0.980	0.30	( 0.29)	0.97	49209.1	12101.10
27	40898.73	122.29	0.966	0.30	( 0.29)	0.97	50058.2	10400.00
28	39328.66	130.24	0.945	0.30	( 0.29)	0.97	51373.4	12010.00
29	38016.00	136.04	0.930	0.30	( 0.29)	0.97	51687.1	10210.00
30	37638.86	138.70	0.923	0.30	( 0.29)	0.97	51797.9	12000.00
31	34542.95	161.90	0.863	0.30	( 0.29)	0.97	52419.8	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 43550.86 Tc (MIN.) = 86.15  
AREA-AVERAGED Fm (INCH/HR) = 0.29 AREA-AVERAGED Fp (INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.96 EFFECTIVE AREA (ACRES) = 36049.07

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<

MAINLINE Tc (MIN.) = 86.15  
\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.135  
SUBAREA LOSS RATE DATA (AMC II):  
DEVELOPMENT TYPE/ SC5 SOIL AREA Fp Ap SC5  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
NATURAL FAIR COVER  
"GRASS" B 17.31 0.30 1.000 69  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 17.31 SUBAREA RUNOFF (CFS) = 13.01  
EFFECTIVE AREA (ACRES) = 36066.38 AREA-AVERAGED Fm (INCH/HR) = 0.29  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA (ACRES) = 52437.1 PEAK FLOW RATE (CFS) = 43550.86  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 52437.1 TC (MIN.) = 86.15  
EFFECTIVE AREA (ACRES) = 36066.38 AREA-AVERAGED Fm (INCH/HR) = 0.29  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.963  
PEAK FLOW RATE (CFS) = 43550.86

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	26009.96	18.18	2.643	0.30 ( 0.25)	0.83	4703.3	300.00
2	27435.41	23.06	2.247	0.30 ( 0.25)	0.84	5982.4	413.00
3	27508.60	23.32	2.229	0.30 ( 0.25)	0.84	6061.8	327.00
4	27789.40	24.45	2.155	0.30 ( 0.25)	0.84	6378.6	350.00
5	28049.77	25.51	2.095	0.30 ( 0.25)	0.84	6675.9	320.00
6	28109.21	25.75	2.084	0.30 ( 0.25)	0.84	6742.3	40500.00

7	29094.64	28.21	1.972	0.30	( 0.26)	0.85	7661.0	12730.00
8	29486.19	29.22	1.927	0.30	( 0.26)	0.86	8030.8	40440.00
9	29523.50	29.41	1.918	0.30	( 0.26)	0.86	8103.8	430.00
10	29565.68	29.66	1.907	0.30	( 0.26)	0.86	8194.0	306.00
11	29658.06	30.17	1.887	0.30	( 0.26)	0.86	8379.8	12710.00
12	29765.46	30.87	1.869	0.30	( 0.26)	0.86	8623.0	400.00
13	29985.30	32.26	1.833	0.30	( 0.26)	0.87	9105.6	40200.00
14	30795.69	36.16	1.733	0.30	( 0.27)	0.88	10671.3	390.00
15	32724.95	45.58	1.511	0.30	( 0.27)	0.92	14409.6	40100.00
16	35361.74	54.35	1.368	0.30	( 0.28)	0.93	17753.8	11801.00
17	38157.45	63.96	1.283	0.30	( 0.28)	0.94	22050.0	11530.00
18	40413.77	72.58	1.226	0.30	( 0.29)	0.95	27035.0	11910.00
19	42510.98	79.77	1.178	0.30	( 0.29)	0.96	31635.4	11330.00
20	43550.86	86.15	1.135	0.30	( 0.29)	0.96	36066.4	11130.00
21	43406.44	93.73	1.092	0.30	( 0.29)	0.97	40060.3	12330.00
22	43338.22	96.33	1.080	0.30	( 0.29)	0.97	41475.2	12410.00
23	43139.30	100.36	1.062	0.30	( 0.29)	0.97	43403.5	12400.00
24	42579.63	109.01	1.022	0.30	( 0.29)	0.97	46772.3	12201.00
25	42106.47	112.95	1.004	0.30	( 0.29)	0.97	47857.0	12111.00
26	41442.08	118.29	0.980	0.30	( 0.29)	0.97	49226.4	12101.10
27	40898.73	122.29	0.966	0.30	( 0.29)	0.97	50075.5	10400.00
28	39328.66	130.24	0.945	0.30	( 0.29)	0.97	51390.7	12010.00
29	38016.00	136.04	0.930	0.30	( 0.29)	0.97	51704.4	10210.00
30	37638.86	138.70	0.923	0.30	( 0.29)	0.97	51815.2	12000.00
31	34542.95	161.90	0.863	0.30	( 0.29)	0.97	52437.1	10100.00

=====  
 END OF RATIONAL METHOD ANALYSIS  
 =====

\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S28- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 100-YR RM EV APRIL 2019 CCHIUI \*  
\*\*\*\*\*

FILE NAME: RI00EV28.DAT  
TIME/DATE OF STUDY: 08:50 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 100.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 6.027
- 2) 10.00; 3.864
- 3) 15.00; 2.981
- 4) 20.00; 2.449
- 5) 25.00; 2.118
- 6) 30.00; 1.891
- 7) 40.00; 1.635
- 8) 50.00; 1.412
- 9) 60.00; 1.310
- 10) 90.00; 1.109
- 11) 120.00; 0.973
- 12) 180.00; 0.816
- 13) 360.00; 0.607
- 14) 1200.00; 0.266

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI00EV27.DNA  
MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	26009.96	18.18	0.30 ( 0.25)	0.83	4703.3	300.00
2	29094.64	28.21	0.30 ( 0.26)	0.85	7661.0	12730.00
3	29985.30	32.26	0.30 ( 0.26)	0.87	9105.6	40200.00
4	30795.69	36.16	0.30 ( 0.27)	0.88	10671.3	390.00
5	32724.95	45.58	0.30 ( 0.27)	0.92	14409.6	40100.00
6	35361.74	54.35	0.30 ( 0.28)	0.93	17753.8	11801.00
7	38157.45	63.96	0.30 ( 0.28)	0.94	22050.0	11530.00
8	40413.77	72.58	0.30 ( 0.29)	0.95	27035.0	11910.00
9	42510.98	79.77	0.30 ( 0.29)	0.96	31635.4	11330.00
10	43550.86	86.15	0.30 ( 0.29)	0.96	36066.4	11130.00
11	43406.44	93.73	0.30 ( 0.29)	0.97	40060.3	12330.00
12	43139.30	100.36	0.30 ( 0.29)	0.97	43403.5	12400.00
13	42579.63	109.01	0.30 ( 0.29)	0.97	46772.3	12201.00
14	42106.47	112.95	0.30 ( 0.29)	0.97	47857.0	12111.00
15	41442.08	118.29	0.30 ( 0.29)	0.97	49226.4	12101.10
16	40898.73	122.29	0.30 ( 0.29)	0.97	50075.5	10400.00
17	39328.66	130.24	0.30 ( 0.29)	0.97	51390.7	12010.00
18	38016.00	136.04	0.30 ( 0.29)	0.97	51704.4	10210.00
19	37638.86	138.70	0.30 ( 0.29)	0.97	51815.2	12000.00
20	34542.95	161.90	0.30 ( 0.29)	0.97	52437.1	10100.00
TOTAL AREA (ACRES) =						52437.1

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 0610501Y.DNA  
MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1712.17	25.43	0.30 ( 0.29)	0.98	1025.4	50120.00
2	1673.65	26.63	0.30 ( 0.29)	0.98	1040.0	50150.00
3	1553.32	30.32	0.30 ( 0.29)	0.98	1063.4	50100.00
TOTAL AREA (ACRES) =						1063.4

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 3 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM	Q	Tc	Fp (Fm)	Ap	Ae	HEADWATER
--------	---	----	---------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(ACRES)	NODE
1	1712.17	25.43	0.30 ( 0.29)	0.98	1025.4
2	1673.65	26.63	0.30 ( 0.29)	0.98	1040.0
3	1553.32	30.32	0.30 ( 0.29)	0.98	1063.4
TOTAL AREA (ACRES) =			1063.4		

\*\*\*\*\*

FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1712.17	25.43	2.098	0.30 ( 0.29)	0.98	1025.4	50120.00
2	1673.65	26.63	2.044	0.30 ( 0.29)	0.98	1040.0	50150.00
3	1553.32	30.32	1.883	0.30 ( 0.29)	0.98	1063.4	50100.00

LONGEST FLOWPATH FROM NODE 50150.00 TO NODE 12800.00 = 11349.00 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	26009.96	18.18	2.643	0.30 ( 0.25)	0.83	4703.3	300.00
2	29094.64	28.21	1.972	0.30 ( 0.26)	0.85	7661.0	12730.00
3	29985.30	32.26	1.833	0.30 ( 0.26)	0.87	9105.6	40200.00
4	30795.69	36.16	1.733	0.30 ( 0.27)	0.88	10671.3	390.00
5	32724.95	45.58	1.511	0.30 ( 0.27)	0.92	14409.6	40100.00
6	35361.74	54.35	1.368	0.30 ( 0.28)	0.93	17753.8	11801.00
7	38157.45	63.96	1.283	0.30 ( 0.28)	0.94	22050.0	11530.00
8	40413.77	72.58	1.226	0.30 ( 0.29)	0.95	27035.0	11910.00
9	42510.98	79.77	1.178	0.30 ( 0.29)	0.96	31635.4	11330.00
10	43550.86	86.15	1.135	0.30 ( 0.29)	0.96	36066.4	11130.00
11	43406.44	93.73	1.092	0.30 ( 0.29)	0.97	40060.3	12330.00
12	43139.30	100.36	1.062	0.30 ( 0.29)	0.97	43403.5	12400.00
13	42579.63	109.01	1.023	0.30 ( 0.29)	0.97	46772.3	12201.00
14	42106.47	112.95	1.005	0.30 ( 0.29)	0.97	47857.0	12111.00
15	41442.08	118.29	0.981	0.30 ( 0.29)	0.97	49226.4	12101.10
16	40898.73	122.29	0.967	0.30 ( 0.29)	0.97	50075.5	10400.00
17	39328.66	130.24	0.946	0.30 ( 0.29)	0.97	51390.7	12010.00
18	38016.00	136.04	0.931	0.30 ( 0.29)	0.97	51704.4	10210.00
19	37638.86	138.70	0.924	0.30 ( 0.29)	0.97	51815.2	12000.00
20	34542.95	161.90	0.863	0.30 ( 0.29)	0.97	52437.1	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111795.71 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27603.15	18.18	2.643	0.30 ( 0.26)	0.85	5436.4	300.00
2	29953.37	25.43	2.098	0.30 ( 0.26)	0.86	7868.1	50120.00
3	30283.15	26.63	2.044	0.30 ( 0.26)	0.87	8235.8	50150.00
4	30716.84	28.21	1.972	0.30 ( 0.26)	0.87	8711.0	12730.00
5	31111.04	30.32	1.883	0.30 ( 0.26)	0.87	9475.4	50100.00
6	31489.84	32.26	1.833	0.30 ( 0.26)	0.88	10169.0	40200.00
7	32202.81	36.16	1.733	0.30 ( 0.27)	0.89	11734.7	390.00
8	33914.12	45.58	1.511	0.30 ( 0.28)	0.92	15473.0	40100.00
9	36411.16	54.35	1.368	0.30 ( 0.28)	0.93	18817.2	11801.00
10	39124.57	63.96	1.283	0.30 ( 0.28)	0.94	23113.4	11530.00

11	41324.43	72.58	1.226	0.30 ( 0.29)	0.95	28098.3	11910.00
12	43374.52	79.77	1.178	0.30 ( 0.29)	0.96	32698.8	11330.00
13	44372.64	86.15	1.135	0.30 ( 0.29)	0.96	37129.8	11130.00
14	44186.43	93.73	1.092	0.30 ( 0.29)	0.97	41123.7	12330.00
15	43889.89	100.36	1.062	0.30 ( 0.29)	0.97	44466.9	12400.00
16	43291.89	109.01	1.023	0.30 ( 0.29)	0.97	47835.7	12201.00
17	42801.27	112.95	1.005	0.30 ( 0.29)	0.97	48920.4	12111.00
18	42113.21	118.29	0.981	0.30 ( 0.29)	0.97	50289.8	12101.10
19	41556.42	122.29	0.967	0.30 ( 0.29)	0.97	51138.9	10400.00
20	39966.00	130.24	0.946	0.30 ( 0.29)	0.97	52454.1	12010.00
21	38638.49	136.04	0.931	0.30 ( 0.29)	0.97	52767.8	10210.00
22	38254.54	138.70	0.924	0.30 ( 0.29)	0.97	52878.6	12000.00
23	35099.28	161.90	0.863	0.30 ( 0.29)	0.97	53500.5	10100.00
TOTAL AREA (ACRES) =			53500.5				

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 44372.64 Tc(MIN.) = 86.147  
EFFECTIVE AREA(ACRES) = 37129.77 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA(ACRES) = 53500.5  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12800.00 = 111795.71 FEET.

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 53500.5 TC(MIN.) = 86.15  
EFFECTIVE AREA(ACRES) = 37129.77 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.964  
PEAK FLOW RATE(CFS) = 44372.64

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27603.15	18.18	2.643	0.30 ( 0.26)	0.85	5436.4	300.00
2	29953.37	25.43	2.098	0.30 ( 0.26)	0.86	7868.1	50120.00
3	30283.15	26.63	2.044	0.30 ( 0.26)	0.87	8235.8	50150.00
4	30716.84	28.21	1.972	0.30 ( 0.26)	0.87	8711.0	12730.00
5	31111.04	30.32	1.883	0.30 ( 0.26)	0.87	9475.4	50100.00
6	31489.84	32.26	1.833	0.30 ( 0.26)	0.88	10169.0	40200.00
7	32202.81	36.16	1.733	0.30 ( 0.27)	0.89	11734.7	390.00
8	33914.12	45.58	1.511	0.30 ( 0.28)	0.92	15473.0	40100.00
9	36411.16	54.35	1.368	0.30 ( 0.28)	0.93	18817.2	11801.00
10	39124.57	63.96	1.283	0.30 ( 0.28)	0.94	23113.4	11530.00
11	41324.43	72.58	1.226	0.30 ( 0.29)	0.95	28098.3	11910.00
12	43374.52	79.77	1.178	0.30 ( 0.29)	0.96	32698.8	11330.00
13	44372.64	86.15	1.135	0.30 ( 0.29)	0.96	37129.8	11130.00
14	44186.43	93.73	1.092	0.30 ( 0.29)	0.97	41123.7	12330.00
15	43889.89	100.36	1.062	0.30 ( 0.29)	0.97	44466.9	12400.00
16	43291.89	109.01	1.023	0.30 ( 0.29)	0.97	47835.7	12201.00
17	42801.27	112.95	1.005	0.30 ( 0.29)	0.97	48920.4	12111.00
18	42113.21	118.29	0.981	0.30 ( 0.29)	0.97	50289.8	12101.10
19	41556.42	122.29	0.967	0.30 ( 0.29)	0.97	51138.9	10400.00
20	39966.00	130.24	0.946	0.30 ( 0.29)	0.97	52454.1	12010.00
21	38638.49	136.04	0.931	0.30 ( 0.29)	0.97	52767.8	10210.00
22	38254.54	138.70	0.924	0.30 ( 0.29)	0.97	52878.6	12000.00
23	35099.28	161.90	0.863	0.30 ( 0.29)	0.97	53500.5	10100.00

END OF RATIONAL METHOD ANALYSIS



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S29- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 100-YR RM EV APRIL 2019 CCHIU \*  
\*\*\*\*\*

FILE NAME: RI00EV29.DAT  
TIME/DATE OF STUDY: 08:51 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 100.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 6.007
- 2) 10.00; 3.854
- 3) 15.00; 2.975
- 4) 20.00; 2.446
- 5) 25.00; 2.115
- 6) 30.00; 1.889
- 7) 40.00; 1.633
- 8) 50.00; 1.411
- 9) 60.00; 1.307
- 10) 90.00; 1.106
- 11) 120.00; 0.970
- 12) 180.00; 0.813
- 13) 360.00; 0.605
- 14) 1200.00; 0.265

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI00EV28.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27603.15	18.18	0.30 ( 0.26)	0.85	5436.4	300.00
2	30716.84	28.21	0.30 ( 0.26)	0.87	8711.0	12730.00
3	31489.84	32.26	0.30 ( 0.26)	0.88	10169.0	40200.00
4	32202.81	36.16	0.30 ( 0.27)	0.89	11734.7	390.00
5	33914.12	45.58	0.30 ( 0.28)	0.92	15473.0	40100.00
6	36411.16	54.35	0.30 ( 0.28)	0.93	18817.2	11801.00
7	39124.57	63.96	0.30 ( 0.28)	0.94	23113.4	11530.00
8	41324.43	72.58	0.30 ( 0.29)	0.95	28098.3	11910.00
9	43374.52	79.77	0.30 ( 0.29)	0.96	32698.8	11330.00
10	44372.64	86.15	0.30 ( 0.29)	0.96	37129.8	11130.00
11	44186.43	93.73	0.30 ( 0.29)	0.97	41123.7	12330.00
12	43889.89	100.36	0.30 ( 0.29)	0.97	44466.9	12400.00
13	43291.89	109.01	0.30 ( 0.29)	0.97	47835.7	12201.00
14	42801.27	112.95	0.30 ( 0.29)	0.97	48920.4	12111.00
15	42113.21	118.29	0.30 ( 0.29)	0.97	50289.8	12101.10
16	41556.42	122.29	0.30 ( 0.29)	0.97	51138.9	10400.00
17	39966.00	130.24	0.30 ( 0.29)	0.97	52454.1	12010.00
18	38638.49	136.04	0.30 ( 0.29)	0.97	52767.8	10210.00
19	38254.54	138.70	0.30 ( 0.29)	0.97	52878.6	12000.00
20	35099.28	161.90	0.30 ( 0.29)	0.97	53500.5	10100.00
TOTAL AREA (ACRES) =						53500.5

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27603.15	18.18	0.30 ( 0.26)	0.85	5436.4	300.00
2	30716.84	28.21	0.30 ( 0.26)	0.87	8711.0	12730.00
3	31489.84	32.26	0.30 ( 0.26)	0.88	10169.0	40200.00
4	32202.81	36.16	0.30 ( 0.27)	0.89	11734.7	390.00
5	33914.12	45.58	0.30 ( 0.28)	0.92	15473.0	40100.00
6	36411.16	54.35	0.30 ( 0.28)	0.93	18817.2	11801.00
7	39124.57	63.96	0.30 ( 0.28)	0.94	23113.4	11530.00
8	41324.43	72.58	0.30 ( 0.29)	0.95	28098.3	11910.00
9	43374.52	79.77	0.30 ( 0.29)	0.96	32698.8	11330.00
10	44372.64	86.15	0.30 ( 0.29)	0.96	37129.8	11130.00
11	44186.43	93.73	0.30 ( 0.29)	0.97	41123.7	12330.00
12	43889.89	100.36	0.30 ( 0.29)	0.97	44466.9	12400.00
13	43291.89	109.01	0.30 ( 0.29)	0.97	47835.7	12201.00



14 42801.27 112.95 0.30( 0.29) 0.97 48920.4 12111.00  
 15 42113.21 118.29 0.30( 0.29) 0.97 50289.8 12101.10  
 16 41556.42 122.29 0.30( 0.29) 0.97 51138.9 10400.00  
 17 39966.00 130.24 0.30( 0.29) 0.97 52454.1 12010.00  
 18 38638.49 136.04 0.30( 0.29) 0.97 52767.8 10210.00  
 19 38254.54 138.70 0.30( 0.29) 0.97 52878.6 12000.00  
 20 35099.28 161.90 0.30( 0.29) 0.97 53500.5 10100.00  
 TOTAL AREA (ACRES) = 53500.5

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12800.00 TO NODE 12800.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12800.00 TO NODE 12901.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 240.00 DOWNSTREAM (FEET) = 216.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 3120.28 CHANNEL SLOPE = 0.0077  
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 9.99  
 CHANNEL FLOW THRU SUBAREA (CFS) = 44372.64  
 FLOW VELOCITY (FEET/SEC.) = 17.77 FLOW DEPTH (FEET) = 9.99  
 TRAVEL TIME (MIN.) = 2.93 Tc (MIN.) = 89.07  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12901.00 = 114915.99 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27603.15	21.60	2.340	0.30( 0.26)	0.85	5436.4	300.00
2	30716.84	31.51	1.850	0.30( 0.26)	0.87	8711.0	12730.00
3	31489.84	35.54	1.747	0.30( 0.26)	0.88	10169.0	40200.00
4	32202.81	39.41	1.648	0.30( 0.27)	0.89	11734.7	390.00
5	33914.12	48.78	1.438	0.30( 0.28)	0.92	15473.0	40100.00
6	36411.16	57.47	1.333	0.30( 0.28)	0.93	18817.2	11801.00
7	39124.57	67.01	1.260	0.30( 0.28)	0.94	23113.4	11530.00
8	41324.43	75.58	1.203	0.30( 0.29)	0.95	28098.3	11910.00
9	43374.52	82.72	1.155	0.30( 0.29)	0.96	32698.8	11330.00
10	44372.64	89.07	1.112	0.30( 0.29)	0.96	37129.8	11130.00
11	44186.43	96.66	1.076	0.30( 0.29)	0.97	41123.7	12330.00
12	43889.89	103.30	1.046	0.30( 0.29)	0.97	44466.9	12400.00
13	43291.89	111.96	1.006	0.30( 0.29)	0.97	47835.7	12201.00
14	42801.27	115.91	0.989	0.30( 0.29)	0.97	48920.4	12111.00
15	42113.21	121.26	0.967	0.30( 0.29)	0.97	50289.8	12101.10
16	41556.42	125.28	0.956	0.30( 0.29)	0.97	51138.9	10400.00
17	39966.00	133.26	0.935	0.30( 0.29)	0.97	52454.1	12010.00
18	38638.49	139.10	0.920	0.30( 0.29)	0.97	52767.8	10210.00
19	38254.54	141.77	0.913	0.30( 0.29)	0.97	52878.6	12000.00
20	35099.28	165.06	0.852	0.30( 0.29)	0.97	53500.5	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 44372.64 Tc (MIN.) = 89.07  
 AREA-AVERAGED Fm (INCH/HR) = 0.29 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.96 EFFECTIVE AREA (ACRES) = 37129.77

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 89.07  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.112  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ LAND USE SCS SOIL GROUP AREA (ACRES) Fp (INCH/HR) Ap (DECIMAL) SCS CN  
 COMMERCIAL B 2.60 0.30 0.100 56  
 COMMERCIAL B 3.20 0.30 0.100 56  
 PUBLIC PARK B 1.50 0.30 0.850 56  
 COMMERCIAL B 5.60 0.30 0.100 56  
 PUBLIC PARK B 6.50 0.30 0.850 56  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.409  
 SUBAREA AREA (ACRES) = 19.40 SUBAREA RUNOFF (CFS) = 17.28  
 EFFECTIVE AREA (ACRES) = 37149.16 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA (ACRES) = 53519.9 PEAK FLOW RATE (CFS) = 44372.64  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 89.07  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.112  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ LAND USE SCS SOIL GROUP AREA (ACRES) Fp (INCH/HR) Ap (DECIMAL) SCS CN  
 COMMERCIAL B 0.50 0.30 0.100 56  
 PUBLIC PARK B 4.10 0.30 0.850 56  
 PUBLIC PARK B 0.10 0.30 0.850 56  
 RESIDENTIAL ".4 DWELLING/ACRE" B 1.60 0.30 0.900 56  
 RESIDENTIAL ".4 DWELLING/ACRE" B 0.60 0.30 0.900 56  
 RESIDENTIAL ".4 DWELLING/ACRE" B 1.00 0.30 0.900 56  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.823  
 SUBAREA AREA (ACRES) = 7.90 SUBAREA RUNOFF (CFS) = 6.15  
 EFFECTIVE AREA (ACRES) = 37157.06 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA (ACRES) = 53527.8 PEAK FLOW RATE (CFS) = 44372.64  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 89.07  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.112

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL					
" .4 DWELLING/ACRE"	B	3.60	0.30	0.900	56
AGRICULTURAL FAIR COVER					
"ORCHARDS"	B	0.30	0.30	1.000	65
NATURAL POOR COVER					
"BARREN"	B	12.00	0.30	1.000	86
PUBLIC PARK	B	36.10	0.30	0.850	56
NATURAL FAIR COVER					
"GRASS"	B	15.90	0.30	1.000	69
NATURAL FAIR COVER					
"GRASS"	B	1.50	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.917  
SUBAREA AREA(ACRES) = 69.40 SUBAREA RUNOFF(CFS) = 52.29  
EFFECTIVE AREA(ACRES) = 37226.46 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA(ACRES) = 53597.2 PEAK FLOW RATE(CFS) = 44372.64  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 89.07  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.112  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	4.20	0.30	1.000	65
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.40	0.30	1.000	65
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	1.00	0.30	1.000	65
RESIDENTIAL					
"5-7 DWELLINGS/ACRE"	B	4.10	0.30	0.500	56
RESIDENTIAL					
"5-7 DWELLINGS/ACRE"	B	3.70	0.30	0.500	56
RESIDENTIAL					
"5-7 DWELLINGS/ACRE"	B	0.40	0.30	0.500	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.703  
SUBAREA AREA(ACRES) = 13.80 SUBAREA RUNOFF(CFS) = 11.19  
EFFECTIVE AREA(ACRES) = 37240.26 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA(ACRES) = 53611.0 PEAK FLOW RATE(CFS) = 44372.64  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12901.00 TO NODE 12901.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 89.07

\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.112  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	6.70	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.20	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.90	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA(ACRES) = 10.80 SUBAREA RUNOFF(CFS) = 7.89  
EFFECTIVE AREA(ACRES) = 37251.06 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA(ACRES) = 53621.8 PEAK FLOW RATE(CFS) = 44372.64  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12901.00 TO NODE 12902.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 216.00 DOWNSTREAM(FEET) = 215.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 122.04 CHANNEL SLOPE = 0.0082  
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 9.81  
CHANNEL FLOW THRU SUBAREA(CFS) = 44372.64  
FLOW VELOCITY(FEET/SEC.) = 18.15 FLOW DEPTH(FEET) = 9.81  
TRAVEL TIME(MIN.) = 0.11 Tc(MIN.) = 89.19  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115038.03 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27603.15	21.73	2.331	0.30( 0.26)	0.85	5557.7	300.00
2	30716.84	31.63	1.847	0.30( 0.26)	0.87	8832.3	12730.00
3	31489.84	35.67	1.744	0.30( 0.26)	0.88	10290.3	40200.00
4	32202.81	39.53	1.645	0.30( 0.27)	0.89	11856.0	390.00
5	33914.12	48.90	1.435	0.30( 0.28)	0.92	15594.3	40100.00
6	36411.16	57.59	1.332	0.30( 0.28)	0.93	18938.5	11801.00
7	39124.57	67.13	1.259	0.30( 0.28)	0.94	23234.7	11530.00
8	41324.43	75.69	1.202	0.30( 0.29)	0.95	28219.6	11910.00
9	43374.52	82.83	1.154	0.30( 0.29)	0.96	32820.1	11330.00
10	44372.64	89.19	1.111	0.30( 0.29)	0.96	37251.1	11130.00
11	44186.43	96.77	1.075	0.30( 0.29)	0.97	41245.0	12330.00
12	43889.89	103.41	1.045	0.30( 0.29)	0.97	44588.2	12400.00
13	43291.89	112.07	1.006	0.30( 0.29)	0.97	47957.0	12201.00
14	42801.27	116.02	0.988	0.30( 0.29)	0.97	49041.7	12111.00
15	42113.21	121.38	0.966	0.30( 0.29)	0.97	50411.1	12101.10
16	41556.42	125.39	0.956	0.30( 0.29)	0.97	51260.2	10400.00
17	39966.00	133.38	0.935	0.30( 0.29)	0.97	52575.3	12010.00
18	38638.49	139.22	0.920	0.30( 0.29)	0.97	52889.1	10210.00
19	38254.54	141.89	0.913	0.30( 0.29)	0.97	52999.9	12000.00
20	35099.28	165.18	0.852	0.30( 0.29)	0.97	53621.8	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 44372.64 Tc(MIN.) = 89.19  
 AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.96 EFFECTIVE AREA(ACRES) = 37251.06

\*\*\*\*\*

FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: E502XXCE.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	72.40	11.09	0.30 ( 0.27)	0.91	28.7	50200.00
TOTAL AREA(ACRES) =						28.7

\*\*\*\*\*

FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27603.15	21.73	2.331	0.30 ( 0.26)	0.85	5557.7	300.00
2	30716.84	31.63	1.847	0.30 ( 0.26)	0.87	8832.3	12730.00
3	31489.84	35.67	1.744	0.30 ( 0.26)	0.88	10290.3	40200.00
4	32202.81	39.53	1.645	0.30 ( 0.27)	0.89	11856.0	390.00
5	33914.12	48.90	1.435	0.30 ( 0.28)	0.92	15594.3	40100.00
6	36411.16	57.59	1.332	0.30 ( 0.28)	0.93	18938.5	11801.00
7	39124.57	67.13	1.259	0.30 ( 0.28)	0.94	23234.7	11530.00
8	41324.43	75.69	1.202	0.30 ( 0.29)	0.95	28219.6	11910.00
9	43374.52	82.83	1.154	0.30 ( 0.29)	0.96	32820.1	11330.00
10	44372.64	89.19	1.111	0.30 ( 0.29)	0.96	37251.1	11130.00
11	44186.43	96.77	1.075	0.30 ( 0.29)	0.97	41245.0	12330.00
12	43889.89	103.41	1.045	0.30 ( 0.29)	0.97	44588.2	12400.00
13	43291.89	112.07	1.006	0.30 ( 0.29)	0.97	47957.0	12201.00
14	42801.27	116.02	0.988	0.30 ( 0.29)	0.97	49041.7	12111.00
15	42113.21	121.38	0.966	0.30 ( 0.29)	0.97	50411.1	12101.10
16	41556.42	125.39	0.956	0.30 ( 0.29)	0.97	51260.2	10400.00
17	39966.00	133.38	0.935	0.30 ( 0.29)	0.97	52575.3	12010.00
18	38638.49	139.22	0.920	0.30 ( 0.29)	0.97	52889.1	10210.00
19	38254.54	141.89	0.913	0.30 ( 0.29)	0.97	52999.9	12000.00
20	35099.28	165.18	0.852	0.30 ( 0.29)	0.97	53621.8	10100.00
LONGEST FLOWPATH FROM NODE							10100.00 TO NODE 12902.00 = 115038.03 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	72.40	11.09	3.662	0.30 ( 0.27)	0.91	28.7	50200.00
LONGEST FLOWPATH FROM NODE							50200.00 TO NODE 12902.00 = 1426.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23192.77	11.09	3.662	0.30 ( 0.26)	0.85	2865.7	50200.00
2	27647.12	21.73	2.331	0.30 ( 0.26)	0.85	5586.4	300.00

3	30750.47	31.63	1.847	0.30 ( 0.26)	0.87	8861.0	12730.00
4	31521.27	35.67	1.744	0.30 ( 0.26)	0.88	10319.0	40200.00
5	32232.12	39.53	1.645	0.30 ( 0.27)	0.89	11884.7	390.00
6	33938.95	48.90	1.435	0.30 ( 0.28)	0.92	15623.0	40100.00
7	36433.79	57.59	1.332	0.30 ( 0.28)	0.93	18967.2	11801.00
8	39145.64	67.13	1.259	0.30 ( 0.28)	0.94	23263.4	11530.00
9	41344.27	75.69	1.202	0.30 ( 0.29)	0.95	28248.3	11910.00
10	43393.34	82.83	1.154	0.30 ( 0.29)	0.96	32848.8	11330.00
11	44390.55	89.19	1.111	0.30 ( 0.29)	0.96	37279.8	11130.00
12	44203.57	96.77	1.075	0.30 ( 0.29)	0.97	41273.7	12330.00
13	43906.39	103.41	1.045	0.30 ( 0.29)	0.97	44616.9	12400.00
14	43307.55	112.07	1.006	0.30 ( 0.29)	0.97	47985.7	12201.00
15	42816.55	116.02	0.988	0.30 ( 0.29)	0.97	49070.4	12111.00
16	42128.02	121.38	0.966	0.30 ( 0.29)	0.97	50439.8	12101.10
17	41571.01	125.39	0.956	0.30 ( 0.29)	0.97	51288.9	10400.00
18	39980.14	133.38	0.935	0.30 ( 0.29)	0.97	52604.0	12010.00
19	38652.31	139.22	0.920	0.30 ( 0.29)	0.97	52917.8	10210.00
20	38268.21	141.89	0.913	0.30 ( 0.29)	0.97	53028.6	12000.00
21	35111.64	165.18	0.852	0.30 ( 0.29)	0.97	53650.5	10100.00
TOTAL AREA(ACRES) =						53650.5	

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 44390.55 Tc(MIN.) = 89.185  
 EFFECTIVE AREA(ACRES) = 37279.76 AREA-AVERAGED Fm(INCH/HR) = 0.29  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA(ACRES) = 53650.5  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115038.03 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: E503XXCE.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	552.75	24.39	0.30 ( 0.30)	0.99	366.4	50300.00
TOTAL AREA(ACRES) =						366.4

\*\*\*\*\*

FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23192.77	11.09	3.662	0.30 ( 0.26)	0.85	2865.7	50200.00
2	27647.12	21.73	2.331	0.30 ( 0.26)	0.85	5586.4	300.00
3	30750.47	31.63	1.847	0.30 ( 0.26)	0.87	8861.0	12730.00

4 31521.27 35.67 1.744 0.30( 0.26) 0.88 10319.0 40200.00  
5 32232.12 39.53 1.645 0.30( 0.27) 0.89 11884.7 390.00  
6 33938.95 48.90 1.435 0.30( 0.28) 0.92 15623.0 40100.00  
7 36433.79 57.59 1.332 0.30( 0.28) 0.93 18967.2 11801.00  
8 39145.64 67.13 1.259 0.30( 0.28) 0.94 23263.4 11530.00  
9 41344.27 75.69 1.202 0.30( 0.29) 0.95 28248.3 11910.00  
10 43393.34 82.83 1.154 0.30( 0.29) 0.96 32848.8 11330.00  
11 44390.55 89.19 1.111 0.30( 0.29) 0.96 37279.8 11130.00  
12 44203.57 96.77 1.075 0.30( 0.29) 0.97 41273.7 12330.00  
13 43906.39 103.41 1.045 0.30( 0.29) 0.97 44616.9 12400.00  
14 43307.55 112.07 1.006 0.30( 0.29) 0.97 47985.7 12201.00  
15 42816.55 116.02 0.988 0.30( 0.29) 0.97 49070.4 12111.00  
16 42128.02 121.38 0.966 0.30( 0.29) 0.97 50439.8 12101.10  
17 41571.01 125.39 0.956 0.30( 0.29) 0.97 51288.9 10400.00  
18 39980.14 133.38 0.935 0.30( 0.29) 0.97 52604.0 12010.00  
19 38652.31 139.22 0.920 0.30( 0.29) 0.97 52917.8 10210.00  
20 38268.21 141.89 0.913 0.30( 0.29) 0.97 53028.6 12000.00  
21 35111.64 165.18 0.852 0.30( 0.29) 0.97 53650.5 10100.00  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115038.03 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	552.75	24.39	2.155	0.30( 0.30)	0.99	366.4	50300.00

LONGEST FLOWPATH FROM NODE 50300.00 TO NODE 12902.00 = 8614.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23647.81	11.09	3.662	0.30( 0.26)	0.86	3032.3	50200.00
2	28186.24	21.73	2.331	0.30( 0.26)	0.86	5912.9	300.00
3	29032.63	24.39	2.155	0.30( 0.26)	0.86	6831.5	50300.00
4	31211.63	31.63	1.847	0.30( 0.26)	0.87	9227.4	12730.00
5	31951.74	35.67	1.744	0.30( 0.27)	0.88	10685.4	40200.00
6	32633.20	39.53	1.645	0.30( 0.27)	0.90	12251.1	390.00
7	34277.73	48.90	1.435	0.30( 0.28)	0.92	15989.4	40100.00
8	36741.85	57.59	1.332	0.30( 0.28)	0.93	19333.6	11801.00
9	39432.05	67.13	1.259	0.30( 0.28)	0.94	23629.8	11530.00
10	41613.65	75.69	1.202	0.30( 0.29)	0.95	28614.7	11910.00
11	43648.49	82.83	1.154	0.30( 0.29)	0.96	33215.2	11330.00
12	44633.05	89.19	1.111	0.30( 0.29)	0.96	37646.2	11130.00
13	44435.32	96.77	1.075	0.30( 0.29)	0.97	41640.1	12330.00
14	44129.20	103.41	1.045	0.30( 0.29)	0.97	44983.3	12400.00
15	43518.69	112.07	1.006	0.30( 0.29)	0.97	48352.1	12201.00
16	43022.36	116.02	0.988	0.30( 0.29)	0.97	49436.8	12111.00
17	42327.41	121.38	0.966	0.30( 0.29)	0.97	50806.2	12101.10
18	41767.28	125.39	0.956	0.30( 0.29)	0.97	51655.3	10400.00
19	40170.20	133.38	0.935	0.30( 0.29)	0.97	52970.4	12010.00
20	38837.82	139.22	0.920	0.30( 0.29)	0.97	53284.2	10210.00
21	38451.64	141.89	0.913	0.30( 0.29)	0.97	53395.0	12000.00
22	35276.97	165.18	0.852	0.30( 0.29)	0.97	54016.9	10100.00

TOTAL AREA (ACRES) = 54016.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 44633.05 Tc(MIN.) = 89.185  
EFFECTIVE AREA(ACRES) = 37646.16 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA(ACRES) = 54016.9

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12902.00 = 115038.03 FEET.  
\*\*\*\*\*  
FLOW PROCESS FROM NODE 12902.00 TO NODE 12902.00 IS CODE = 12  
-----  
>>>>CLEAR MEMORY BANK # 1 <<<<<<  
-----  
\*\*\*\*\*  
FLOW PROCESS FROM NODE 12902.00 TO NODE 12903.00 IS CODE = 56  
-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<<  
-----  
ELEVATION DATA: UPSTREAM(FEET) = 215.00 DOWNSTREAM(FEET) = 214.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 895.53 CHANNEL SLOPE = 0.0011  
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 17.07  
CHANNEL FLOW THRU SUBAREA(CFS) = 44633.05  
FLOW VELOCITY(FEET/SEC.) = 9.16 FLOW DEPTH(FEET) = 17.07  
TRAVEL TIME(MIN.) = 1.63 Tc(MIN.) = 90.81  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115933.56 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23647.81	13.07	3.313	0.30( 0.26)	0.86	3032.3	50200.00
2	28186.24	23.61	2.207	0.30( 0.26)	0.86	5912.9	300.00
3	29032.63	26.25	2.059	0.30( 0.26)	0.86	6831.5	50300.00
4	31211.63	33.45	1.801	0.30( 0.26)	0.87	9227.4	12730.00
5	31951.74	37.47	1.698	0.30( 0.27)	0.88	10685.4	40200.00
6	32633.20	41.32	1.604	0.30( 0.27)	0.90	12251.1	390.00
7	34277.73	50.66	1.404	0.30( 0.28)	0.92	15989.4	40100.00
8	36741.85	59.32	1.314	0.30( 0.28)	0.93	19333.6	11801.00
9	39432.05	68.82	1.248	0.30( 0.28)	0.94	23629.8	11530.00
10	41613.65	77.35	1.191	0.30( 0.29)	0.95	28614.7	11910.00
11	43648.49	84.47	1.143	0.30( 0.29)	0.96	33215.2	11330.00
12	44633.05	90.81	1.102	0.30( 0.29)	0.96	37646.2	11130.00
13	44435.32	98.40	1.068	0.30( 0.29)	0.97	41640.1	12330.00
14	44129.20	105.05	1.038	0.30( 0.29)	0.97	44983.3	12400.00
15	43518.69	113.71	0.998	0.30( 0.29)	0.97	48352.1	12201.00
16	43022.36	117.67	0.981	0.30( 0.29)	0.97	49436.8	12111.00
17	42327.41	123.03	0.962	0.30( 0.29)	0.97	50806.2	12101.10
18	41767.28	127.05	0.952	0.30( 0.29)	0.97	51655.3	10400.00
19	40170.20	135.06	0.931	0.30( 0.29)	0.97	52970.4	12010.00
20	38837.82	140.92	0.915	0.30( 0.29)	0.97	53284.2	10210.00
21	38451.64	143.59	0.908	0.30( 0.29)	0.97	53395.0	12000.00
22	35276.97	166.93	0.847	0.30( 0.29)	0.97	54016.9	10100.00

NEW PEAK FLOW DATA ARE:  
PEAK FLOW RATE(CFS) = 44633.05 Tc(MIN.) = 90.81  
AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.96 EFFECTIVE AREA(ACRES) = 37646.16

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 15.1  
-----  
>>>>DEFINE MEMORY BANK # 2 <<<<<<

PEAK FLOWRATE TABLE FILE NAME: E504XXCE.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	136.04	17.00	0.30 (0.29)	0.97	70.5	50400.00
TOTAL AREA (ACRES) =			70.5			

\*\*\*\*\*

FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23647.81	13.07	3.313	0.30 (0.26)	0.86	3032.3	50200.00
2	28186.24	23.61	2.207	0.30 (0.26)	0.86	5912.9	300.00
3	29032.63	26.25	2.059	0.30 (0.26)	0.86	6831.5	50300.00
4	31211.63	33.45	1.801	0.30 (0.26)	0.87	9227.4	12730.00
5	31951.74	37.47	1.698	0.30 (0.27)	0.88	10685.4	40200.00
6	32633.20	41.32	1.604	0.30 (0.27)	0.90	12251.1	390.00
7	34277.73	50.66	1.404	0.30 (0.28)	0.92	15989.4	40100.00
8	36741.85	59.32	1.314	0.30 (0.28)	0.93	19333.6	11801.00
9	39432.05	68.82	1.248	0.30 (0.28)	0.94	23629.8	11530.00
10	41613.65	77.35	1.191	0.30 (0.29)	0.95	28614.7	11910.00
11	43648.49	84.47	1.143	0.30 (0.29)	0.96	33215.2	11330.00
12	44633.05	90.81	1.102	0.30 (0.29)	0.96	37646.2	11130.00
13	44435.32	98.40	1.068	0.30 (0.29)	0.97	41640.1	12330.00
14	44129.20	105.05	1.038	0.30 (0.29)	0.97	44983.3	12400.00
15	43518.69	113.71	0.998	0.30 (0.29)	0.97	48352.1	12201.00
16	43022.36	117.67	0.981	0.30 (0.29)	0.97	49436.8	12111.00
17	42327.41	123.03	0.962	0.30 (0.29)	0.97	50806.2	12101.10
18	41767.28	127.05	0.952	0.30 (0.29)	0.97	51655.3	10400.00
19	40170.20	135.06	0.931	0.30 (0.29)	0.97	52970.4	12010.00
20	38837.82	140.92	0.915	0.30 (0.29)	0.97	53284.2	10210.00
21	38451.64	143.59	0.908	0.30 (0.29)	0.97	53395.0	12000.00
22	35276.97	166.93	0.847	0.30 (0.29)	0.97	54016.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115933.56 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	136.04	17.00	2.763	0.30 (0.29)	0.97	70.5	50400.00

LONGEST FLOWPATH FROM NODE 50400.00 TO NODE 12903.00 = 3607.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23775.71	13.07	3.313	0.30 (0.26)	0.86	3086.6	50200.00
2	25475.08	17.00	2.763	0.30 (0.26)	0.86	4176.3	50400.00
3	28291.69	23.61	2.207	0.30 (0.26)	0.86	5983.4	300.00
4	29129.91	26.25	2.059	0.30 (0.26)	0.86	6902.0	50300.00
5	31294.72	33.45	1.801	0.30 (0.26)	0.87	9297.9	12730.00
6	32029.17	37.47	1.698	0.30 (0.27)	0.89	10755.9	40200.00
7	32705.45	41.32	1.604	0.30 (0.27)	0.90	12321.6	390.00
8	34339.01	50.66	1.404	0.30 (0.28)	0.92	16059.9	40100.00

9	36798.18	59.32	1.314	0.30 (0.28)	0.93	19404.1	11801.00
10	39484.74	68.82	1.248	0.30 (0.28)	0.94	23700.3	11530.00
11	41663.19	77.35	1.191	0.30 (0.29)	0.95	28685.2	11910.00
12	43695.41	84.47	1.143	0.30 (0.29)	0.96	33285.7	11330.00
13	44677.73	90.81	1.102	0.30 (0.29)	0.96	37716.7	11130.00
14	44478.11	98.40	1.068	0.30 (0.29)	0.97	41710.6	12330.00
15	44170.32	105.05	1.038	0.30 (0.29)	0.97	45053.8	12400.00
16	43557.66	113.71	0.998	0.30 (0.29)	0.97	48422.6	12201.00
17	43060.34	117.67	0.981	0.30 (0.29)	0.97	49507.3	12111.00
18	42364.38	123.03	0.962	0.30 (0.29)	0.97	50876.7	12101.10
19	41803.66	127.05	0.952	0.30 (0.29)	0.97	51725.8	10400.00
20	40205.43	135.06	0.931	0.30 (0.29)	0.97	53040.9	12010.00
21	38872.21	140.92	0.915	0.30 (0.29)	0.97	53354.7	10210.00
22	38485.65	143.59	0.908	0.30 (0.29)	0.97	53465.5	12000.00
23	35307.62	166.93	0.847	0.30 (0.29)	0.97	54087.4	10100.00
TOTAL AREA (ACRES) =			54087.4				

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 44677.73 Tc (MIN.) = 90.814  
EFFECTIVE AREA (ACRES) = 37716.66 AREA-AVERAGED Fm (INCH/HR) = 0.29  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
TOTAL AREA (ACRES) = 54087.4  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12903.00 = 115933.56 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12903.00 TO NODE 12903.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 12903.00 TO NODE 12904.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 214.00 DOWNSTREAM (FEET) = 213.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 767.57 CHANNEL SLOPE = 0.0013  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 16.38  
CHANNEL FLOW THRU SUBAREA (CFS) = 44677.73  
FLOW VELOCITY (FEET/SEC.) = 9.67 FLOW DEPTH (FEET) = 16.38  
TRAVEL TIME (MIN.) = 1.32 Tc (MIN.) = 92.14  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116701.13 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23775.71	14.68	3.031	0.30 (0.26)	0.86	3086.6	50200.00
2	25475.08	18.57	2.597	0.30 (0.26)	0.86	4176.3	50400.00
3	28291.69	25.13	2.109	0.30 (0.26)	0.86	5983.4	300.00
4	29129.91	27.75	1.990	0.30 (0.26)	0.86	6902.0	50300.00
5	31294.72	34.92	1.763	0.30 (0.26)	0.87	9297.9	12730.00
6	32029.17	38.93	1.660	0.30 (0.27)	0.89	10755.9	40200.00
7	32705.45	42.78	1.571	0.30 (0.27)	0.90	12321.6	390.00
8	34339.01	52.10	1.389	0.30 (0.28)	0.92	16059.9	40100.00
9	36798.18	60.72	1.302	0.30 (0.28)	0.93	19404.1	11801.00

10	39484.74	70.19	1.239	0.30 ( 0.28)	0.94	23700.3	11530.00
11	41663.19	78.70	1.182	0.30 ( 0.29)	0.95	28685.2	11910.00
12	43695.41	85.80	1.134	0.30 ( 0.29)	0.96	33285.7	11330.00
13	44677.73	92.14	1.096	0.30 ( 0.29)	0.96	37716.7	11130.00
14	44478.11	99.73	1.062	0.30 ( 0.29)	0.97	41710.6	12330.00
15	44170.32	106.37	1.032	0.30 ( 0.29)	0.97	45053.8	12400.00
16	43557.66	115.05	0.992	0.30 ( 0.29)	0.97	48422.6	12201.00
17	43060.34	119.01	0.974	0.30 ( 0.29)	0.97	49507.3	12111.00
18	42364.38	124.38	0.959	0.30 ( 0.29)	0.97	50876.7	12101.10
19	41803.66	128.40	0.948	0.30 ( 0.29)	0.97	51725.8	10400.00
20	40205.43	136.43	0.927	0.30 ( 0.29)	0.97	53040.9	12010.00
21	38872.21	142.30	0.912	0.30 ( 0.29)	0.97	53354.7	10210.00
22	38485.65	144.98	0.905	0.30 ( 0.29)	0.97	53465.5	12000.00
23	35307.62	168.35	0.843	0.30 ( 0.29)	0.97	54087.4	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 44677.73 Tc(MIN.) = 92.14  
 AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.96 EFFECTIVE AREA(ACRES) = 37716.66

\*\*\*\*\*

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 3B00EVRL.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	510.80	14.40	3.080	0.30 ( 0.13)	0.42	192.1	200.00
2	503.63	17.29	2.733	0.30 ( 0.13)	0.42	214.7	210.00
TOTAL AREA(ACRES) = 214.7							

\*\*\*\*\*

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	23775.71	14.68	3.031	0.30 ( 0.26)	0.86	3086.6	50200.00
2	25475.08	18.57	2.597	0.30 ( 0.26)	0.86	4176.3	50400.00
3	28291.69	25.13	2.109	0.30 ( 0.26)	0.86	5983.4	300.00
4	29129.91	27.75	1.990	0.30 ( 0.26)	0.86	6902.0	50300.00
5	31294.72	34.92	1.763	0.30 ( 0.26)	0.87	9297.9	12730.00
6	32029.17	38.93	1.660	0.30 ( 0.27)	0.89	10755.9	40200.00
7	32705.45	42.78	1.571	0.30 ( 0.27)	0.90	12321.6	390.00
8	34339.01	52.10	1.389	0.30 ( 0.28)	0.92	16059.9	40100.00
9	36798.18	60.72	1.302	0.30 ( 0.28)	0.93	19404.1	11801.00
10	39484.74	70.19	1.239	0.30 ( 0.28)	0.94	23700.3	11530.00
11	41663.19	78.70	1.182	0.30 ( 0.29)	0.95	28685.2	11910.00
12	43695.41	85.80	1.134	0.30 ( 0.29)	0.96	33285.7	11330.00
13	44677.73	92.14	1.096	0.30 ( 0.29)	0.96	37716.7	11130.00
14	44478.11	99.73	1.062	0.30 ( 0.29)	0.97	41710.6	12330.00
15	44170.32	106.37	1.032	0.30 ( 0.29)	0.97	45053.8	12400.00
16	43557.66	115.05	0.992	0.30 ( 0.29)	0.97	48422.6	12201.00
17	43060.34	119.01	0.974	0.30 ( 0.29)	0.97	49507.3	12111.00

18	42364.38	124.38	0.959	0.30 ( 0.29)	0.97	50876.7	12101.10
19	41803.66	128.40	0.948	0.30 ( 0.29)	0.97	51725.8	10400.00
20	40205.43	136.43	0.927	0.30 ( 0.29)	0.97	53040.9	12010.00
21	38872.21	142.30	0.912	0.30 ( 0.29)	0.97	53354.7	10210.00
22	38485.65	144.98	0.905	0.30 ( 0.29)	0.97	53465.5	12000.00
23	35307.62	168.35	0.843	0.30 ( 0.29)	0.97	54087.4	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116701.13 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	510.80	14.40	3.080	0.30 ( 0.13)	0.42	192.1	200.00
2	503.63	17.29	2.733	0.30 ( 0.13)	0.42	214.7	210.00
LONGEST FLOWPATH FROM NODE 210.00 TO NODE 12904.00 = 5961.00 FEET.							

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24246.84	14.40	3.080	0.30 ( 0.25)	0.83	3219.4	200.00
2	24285.81	14.68	3.031	0.30 ( 0.25)	0.83	3280.9	50200.00
3	25418.23	17.29	2.733	0.30 ( 0.25)	0.84	4031.6	210.00
4	25952.48	18.57	2.597	0.30 ( 0.25)	0.84	4391.0	50400.00
5	28674.81	25.13	2.109	0.30 ( 0.25)	0.84	6198.1	300.00
6	29490.11	27.75	1.990	0.30 ( 0.26)	0.85	7116.7	50300.00
7	31610.95	34.92	1.763	0.30 ( 0.26)	0.86	9512.6	12730.00
8	32325.57	38.93	1.660	0.30 ( 0.26)	0.88	10970.6	40200.00
9	32984.66	42.78	1.571	0.30 ( 0.27)	0.89	12536.3	390.00
10	34583.02	52.10	1.389	0.30 ( 0.27)	0.91	16274.6	40100.00
11	37025.37	60.72	1.302	0.30 ( 0.28)	0.93	19618.8	11801.00
12	39699.67	70.19	1.239	0.30 ( 0.28)	0.94	23915.0	11530.00
13	41867.11	78.70	1.182	0.30 ( 0.28)	0.95	28899.9	11910.00
14	43890.13	85.80	1.134	0.30 ( 0.29)	0.96	33500.4	11330.00
15	44865.15	92.14	1.096	0.30 ( 0.29)	0.96	37931.4	11130.00
16	44658.88	99.73	1.062	0.30 ( 0.29)	0.96	41925.3	12330.00
17	44345.27	106.37	1.032	0.30 ( 0.29)	0.97	45268.5	12400.00
18	43725.00	115.05	0.992	0.30 ( 0.29)	0.97	48637.3	12201.00
19	43224.22	119.01	0.974	0.30 ( 0.29)	0.97	49722.0	12111.00
20	42525.17	124.38	0.959	0.30 ( 0.29)	0.97	51091.4	12101.10
21	41962.43	128.40	0.948	0.30 ( 0.29)	0.97	51940.5	10400.00
22	40360.14	136.43	0.927	0.30 ( 0.29)	0.97	53255.6	12010.00
23	39023.95	142.30	0.912	0.30 ( 0.29)	0.97	53569.4	10210.00
24	38636.03	144.98	0.905	0.30 ( 0.29)	0.97	53680.2	12000.00
25	35446.18	168.35	0.843	0.30 ( 0.29)	0.97	54302.1	10100.00
TOTAL AREA(ACRES) = 54302.1							

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 44865.15 Tc(MIN.) = 92.137  
 EFFECTIVE AREA(ACRES) = 37931.36 AREA-AVERAGED Fm(INCH/HR) = 0.29  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95  
 TOTAL AREA(ACRES) = 54302.1  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 12904.00 = 116701.13 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 92.14

\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.096  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	0.70	0.30	0.100	56
NATURAL FAIR COVER "GRASS"	B	20.00	0.30	1.000	69
NATURAL FAIR COVER "MEADOWS"	B	0.10	0.30	1.000	70
PUBLIC PARK	B	14.90	0.30	0.850	56
RESIDENTIAL ".4 DWELLING/ACRE"	B	2.60	0.30	0.900	56
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.80	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.920  
 SUBAREA AREA (ACRES) = 39.10 SUBAREA RUNOFF (CFS) = 28.87  
 EFFECTIVE AREA (ACRES) = 37970.46 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA (ACRES) = 54341.2 PEAK FLOW RATE (CFS) = 44865.15  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 92.14  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.096  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	0.30	0.30	0.100	56
NATURAL FAIR COVER "OPEN BRUSH"	B	0.10	0.30	1.000	66
AGRICULTURAL FAIR COVER "ORCHARDS"	B	0.10	0.30	1.000	65
RESIDENTIAL ".4 DWELLING/ACRE"	B	1.70	0.30	0.900	56
NATURAL FAIR COVER "GRASS"	B	2.60	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	0.20	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.912  
 SUBAREA AREA (ACRES) = 5.00 SUBAREA RUNOFF (CFS) = 3.70  
 EFFECTIVE AREA (ACRES) = 37975.46 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA (ACRES) = 54346.2 PEAK FLOW RATE (CFS) = 44865.15  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 92.14  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.096

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL FAIR COVER "ORCHARDS"	B	0.10	0.30	1.000	65
RESIDENTIAL ".4 DWELLING/ACRE"	B	2.60	0.30	0.900	56
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.20	0.30	1.000	65
NATURAL FAIR COVER "GRASS"	B	3.00	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.956  
 SUBAREA AREA (ACRES) = 5.90 SUBAREA RUNOFF (CFS) = 4.30  
 EFFECTIVE AREA (ACRES) = 37981.36 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA (ACRES) = 54352.1 PEAK FLOW RATE (CFS) = 44865.15  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

=====  
 END OF STUDY SUMMARY:  
 TOTAL AREA (ACRES) = 54352.1 TC (MIN.) = 92.14  
 EFFECTIVE AREA (ACRES) = 37981.36 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.960  
 PEAK FLOW RATE (CFS) = 44865.15

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24246.84	14.40	3.080	0.30 ( 0.25)	0.84	3269.4	200.00
2	24285.81	14.68	3.031	0.30 ( 0.25)	0.84	3330.9	50200.00
3	25418.23	17.29	2.733	0.30 ( 0.25)	0.84	4081.6	210.00
4	25952.48	18.57	2.597	0.30 ( 0.25)	0.84	4441.0	50400.00
5	28674.81	25.13	2.109	0.30 ( 0.25)	0.85	6248.1	300.00
6	29490.11	27.75	1.990	0.30 ( 0.26)	0.85	7166.7	50300.00
7	31610.95	34.92	1.763	0.30 ( 0.26)	0.86	9562.6	12730.00
8	32325.57	38.93	1.660	0.30 ( 0.26)	0.88	11020.6	40200.00
9	32984.66	42.78	1.571	0.30 ( 0.27)	0.89	12586.3	390.00
10	34583.02	52.10	1.389	0.30 ( 0.27)	0.91	16324.6	40100.00
11	37025.37	60.72	1.302	0.30 ( 0.28)	0.93	19668.8	11801.00
12	39699.67	70.19	1.239	0.30 ( 0.28)	0.94	23965.0	11530.00
13	41867.11	78.70	1.182	0.30 ( 0.28)	0.95	28949.9	11910.00
14	43890.13	85.80	1.134	0.30 ( 0.29)	0.96	33550.4	11330.00
15	44865.15	92.14	1.096	0.30 ( 0.29)	0.96	37981.4	11130.00
16	44658.88	99.73	1.062	0.30 ( 0.29)	0.96	41975.3	12330.00
17	44345.27	106.37	1.032	0.30 ( 0.29)	0.97	45318.5	12400.00
18	43725.00	115.05	0.992	0.30 ( 0.29)	0.97	48687.3	12201.00
19	43224.22	119.01	0.974	0.30 ( 0.29)	0.97	49772.0	12111.00
20	42525.17	124.38	0.959	0.30 ( 0.29)	0.97	51141.4	12101.10
21	41962.43	128.40	0.948	0.30 ( 0.29)	0.97	51990.5	10400.00
22	40360.14	136.43	0.927	0.30 ( 0.29)	0.97	53305.6	12010.00
23	39023.95	142.30	0.912	0.30 ( 0.29)	0.97	53619.4	10210.00
24	38636.03	144.98	0.905	0.30 ( 0.29)	0.97	53730.2	12000.00
25	35446.18	168.35	0.843	0.30 ( 0.29)	0.97	54352.1	10100.00

=====  
 END OF RATIONAL METHOD ANALYSIS





\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S33- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 100-YR RM EV APRIL 2019 CCHIUI \*  
\*\*\*\*\*

FILE NAME: RI00EV33.DAT  
TIME/DATE OF STUDY: 08:51 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 100.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.876
- 2) 10.00; 3.789
- 3) 15.00; 2.933
- 4) 20.00; 2.419
- 5) 25.00; 2.096
- 6) 30.00; 1.873
- 7) 40.00; 1.617
- 8) 50.00; 1.400
- 9) 60.00; 1.290
- 10) 90.00; 1.088
- 11) 120.00; 0.951
- 12) 180.00; 0.795
- 13) 360.00; 0.588
- 14) 1200.00; 0.256

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL: IN- / OUT-/PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:

- 1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13112.00 TO NODE 13222.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: S31X00.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3200.10	33.81	0.30 ( 0.24)	0.81	2538.8	13100.00
2	3223.67	57.47	0.30 ( 0.24)	0.81	3777.0	13000.00
3	3120.61	59.66	0.30 ( 0.24)	0.81	3796.8	13010.00
TOTAL AREA (ACRES) =						3796.8

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13221.00 TO NODE 13222.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: S32X00.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1444.32	32.09	0.30 ( 0.25)	0.83	1115.4	13210.00
2	1446.69	32.62	0.30 ( 0.25)	0.83	1127.6	13200.00
TOTAL AREA (ACRES) =						1127.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13221.00 TO NODE 13222.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1444.32	32.09	0.30 ( 0.25)	0.83	1115.4	13210.00
2	1446.69	32.62	0.30 ( 0.25)	0.83	1127.6	13200.00
TOTAL AREA (ACRES) =						1127.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13112.00 TO NODE 13222.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1444.32	32.09	1.820	0.30 ( 0.25)	0.83	1115.4	13210.00
2	1446.69	32.62	1.806	0.30 ( 0.25)	0.83	1127.6	13200.00
LONGEST FLOWPATH FROM NODE 13200.00 TO NODE 13222.00 =							16821.05 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	3200.10	33.81	1.775	0.30 ( 0.24)	0.81	2538.8	13100.00
2	3223.67	57.47	1.318	0.30 ( 0.24)	0.81	3777.0	13000.00
3	3120.61	59.66	1.294	0.30 ( 0.24)	0.81	3796.8	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13222.00 = 32126.49 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4568.68	32.09	1.820	0.30 ( 0.24)	0.82	3524.7	13210.00
2	4595.23	32.62	1.806	0.30 ( 0.24)	0.82	3576.6	13200.00
3	4618.34	33.81	1.775	0.30 ( 0.24)	0.82	3666.4	13100.00
4	4217.04	57.47	1.318	0.30 ( 0.24)	0.81	4904.6	13000.00
5	4091.56	59.66	1.294	0.30 ( 0.24)	0.81	4924.4	13010.00

TOTAL AREA (ACRES) = 4924.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:  
 PEAK FLOW RATE(CFS) = 4618.34 Tc(MIN.) = 33.814  
 EFFECTIVE AREA(ACRES) = 3666.43 AREA-AVERAGED Fm(INCH/HR) = 0.24  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82  
 TOTAL AREA (ACRES) = 4924.4  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13222.00 = 32126.49 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13222.00 TO NODE 13222.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13222.00 TO NODE 13222.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 2 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13222.00 TO NODE 13301.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 427.51 DOWNSTREAM(FEET) = 382.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2533.33 CHANNEL SLOPE = 0.0180  
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 5.38  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.692  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	1.40	0.30	0.100	56
NATURAL FAIR COVER					
"OPEN BRUSH"	B	15.60	0.30	1.000	66
RESIDENTIAL					
"3-4 DWELLINGS/ACRE"	B	0.10	0.30	0.600	56
AGRICULTURAL POOR COVER					

"ROW CROPS,CONTOURED"	B	5.30	0.30	1.000	79
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86
COMMERCIAL	B	22.60	0.30	0.100	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.521  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 4649.58  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 13.04  
 AVERAGE FLOW DEPTH(FEET) = 5.39 TRAVEL TIME(MIN.) = 3.24  
 Tc(MIN.) = 37.05  
 SUBAREA AREA(ACRES) = 45.20 SUBAREA RUNOFF(CFS) = 62.49  
 EFFECTIVE AREA(ACRES) = 3711.63 AREA-AVERAGED Fm(INCH/HR) = 0.24  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81  
 TOTAL AREA(ACRES) = 4969.6 PEAK FLOW RATE(CFS) = 4840.40  
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 5.51

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 5.51 FLOW VELOCITY(FEET/SEC.) = 13.20  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4796.38	35.34	1.736	0.30 ( 0.24)	0.81	3569.9	13210.00
2	4822.68	35.86	1.723	0.30 ( 0.24)	0.81	3621.8	13200.00
3	4840.40	37.05	1.692	0.30 ( 0.24)	0.81	3711.6	13100.00
4	4640.98	60.80	1.285	0.30 ( 0.24)	0.81	4949.8	13000.00
5	4592.77	63.02	1.270	0.30 ( 0.24)	0.81	4969.6	13010.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE(CFS) = 4840.40 Tc(MIN.) = 37.05  
 AREA-AVERAGED Fm(INCH/HR) = 0.24 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.81 EFFECTIVE AREA(ACRES) = 3711.63

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 37.05  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.692  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	1.00	0.30	1.000	79
NATURAL POOR COVER					
"BARREN"	B	0.50	0.30	1.000	86
COMMERCIAL	B	7.40	0.30	0.100	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	4.70	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	2.90	0.30	1.000	65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.596					
SUBAREA AREA(ACRES) = 16.50 SUBAREA RUNOFF(CFS) = 22.48					
EFFECTIVE AREA(ACRES) = 3728.13 AREA-AVERAGED Fm(INCH/HR) = 0.24					

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81  
TOTAL AREA (ACRES) = 4986.1 PEAK FLOW RATE (CFS) = 4862.88

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 37.05  
\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.692  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	1.30	0.30	1.000	86
COMMERCIAL	B	0.20	0.30	0.100	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	5.30	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.30	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	0.20	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.60	0.30	1.000	66

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.977  
SUBAREA AREA (ACRES) = 7.90 SUBAREA RUNOFF (CFS) = 9.95  
EFFECTIVE AREA (ACRES) = 3736.03 AREA-AVERAGED Fm (INCH/HR) = 0.24  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81  
TOTAL AREA (ACRES) = 4994.0 PEAK FLOW RATE (CFS) = 4872.83

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 37.05  
\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.692  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	4.30	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	0.80	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	1.10	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	6.90	0.30	1.000	66
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	7.90	0.30	1.000	79
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	1.00	0.30	1.000	65

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 22.00 SUBAREA RUNOFF (CFS) = 27.57  
EFFECTIVE AREA (ACRES) = 3758.03 AREA-AVERAGED Fm (INCH/HR) = 0.24  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81

TOTAL AREA (ACRES) = 5016.0 PEAK FLOW RATE (CFS) = 4900.40

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 37.05  
\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.692  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.40	0.30	1.000	66
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	14.60	0.30	1.000	79

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 15.00 SUBAREA RUNOFF (CFS) = 18.80  
EFFECTIVE AREA (ACRES) = 3773.03 AREA-AVERAGED Fm (INCH/HR) = 0.24  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81  
TOTAL AREA (ACRES) = 5031.0 PEAK FLOW RATE (CFS) = 4919.20

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 10

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 31100.00 TO NODE 31101.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<

>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH (FEET) = 317.00  
ELEVATION DATA: UPSTREAM (FEET) = 801.00 DOWNSTREAM (FEET) = 685.00

Tc = K \* [(LENGTH \*\* 3.00) / (ELEVATION CHANGE)] \*\* 0.20  
SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 8.641  
\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 4.356  
SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER						
"CHAPARRAL, BROADLEAF"	B	0.50	0.30	1.000	63	8.64
NATURAL FAIR COVER						
"OPEN BRUSH"	B	0.30	0.30	1.000	66	8.64
NATURAL FAIR COVER						
"OPEN BRUSH"	B	0.30	0.30	1.000	66	8.64

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA RUNOFF (CFS) = 4.02  
TOTAL AREA (ACRES) = 1.10 PEAK FLOW RATE (CFS) = 4.02

\*\*\*\*\*

FLOW PROCESS FROM NODE 31101.00 TO NODE 31102.00 IS CODE = 51

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 685.00 DOWNSTREAM(FEET) = 655.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 135.00 CHANNEL SLOPE = 0.2222
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 4.224
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"CHAPARRAL,BROADLEAF" B 0.50 0.30 1.000 63
NATURAL FAIR COVER
"OPEN BRUSH" B 0.10 0.30 1.000 66
NATURAL FAIR COVER
"OPEN BRUSH" B 0.70 0.30 1.000 66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 6.31
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.10
AVERAGE FLOW DEPTH(FEET) = 0.54 TRAVEL TIME(MIN.) = 0.32
Tc(MIN.) = 8.96
SUBAREA AREA(ACRES) = 1.30 SUBAREA RUNOFF(CFS) = 4.59
EFFECTIVE AREA(ACRES) = 2.40 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 2.4 PEAK FLOW RATE(CFS) = 8.48

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.61 FLOW VELOCITY(FEET/SEC.) = 7.66
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31102.00 = 452.00 FEET.

```

```

*****
FLOW PROCESS FROM NODE 31102.00 TO NODE 31103.00 IS CODE = 51
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 655.00 DOWNSTREAM(FEET) = 630.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 203.00 CHANNEL SLOPE = 0.1232
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.030 MAXIMUM DEPTH(FEET) = 10.00
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 4.054
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"CHAPARRAL,BROADLEAF" B 0.30 0.30 1.000 63
NATURAL FAIR COVER
"OPEN BRUSH" B 0.10 0.30 1.000 66
NATURAL FAIR COVER
"OPEN BRUSH" B 1.90 0.30 1.000 66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 12.36
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.30
AVERAGE FLOW DEPTH(FEET) = 0.70 TRAVEL TIME(MIN.) = 0.41
Tc(MIN.) = 9.37

```

```

SUBAREA AREA(ACRES) = 2.30 SUBAREA RUNOFF(CFS) = 7.77
EFFECTIVE AREA(ACRES) = 4.70 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 4.7 PEAK FLOW RATE(CFS) = 15.88

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.77 FLOW VELOCITY(FEET/SEC.) = 8.85
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31103.00 = 655.00 FEET.

```

```

*****
FLOW PROCESS FROM NODE 31103.00 TO NODE 31104.00 IS CODE = 51
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 630.00 DOWNSTREAM(FEET) = 605.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 321.00 CHANNEL SLOPE = 0.0779
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.757
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"OPEN BRUSH" B 1.10 0.30 1.000 66
NATURAL FAIR COVER
"OPEN BRUSH" B 2.50 0.30 1.000 66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 21.48
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.52
AVERAGE FLOW DEPTH(FEET) = 1.05 TRAVEL TIME(MIN.) = 0.82
Tc(MIN.) = 10.19
SUBAREA AREA(ACRES) = 3.60 SUBAREA RUNOFF(CFS) = 11.20
EFFECTIVE AREA(ACRES) = 8.30 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00
TOTAL AREA(ACRES) = 8.3 PEAK FLOW RATE(CFS) = 25.82

```

```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.12 FLOW VELOCITY(FEET/SEC.) = 6.81
LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31104.00 = 976.00 FEET.

```

```

*****
FLOW PROCESS FROM NODE 31104.00 TO NODE 31105.00 IS CODE = 51
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 605.00 DOWNSTREAM(FEET) = 585.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 288.00 CHANNEL SLOPE = 0.0694
CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000
MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.641
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
NATURAL FAIR COVER
"CHAPARRAL,BROADLEAF" B 0.70 0.30 1.000 63

```

NATURAL FAIR COVER  
 "CHAPARRAL,BROADLEAF" B 0.60 0.30 1.000 63  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 3.00 0.30 1.000 66  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 2.10 0.30 1.000 66  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 35.45  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.08  
 AVERAGE FLOW DEPTH(FEET) = 1.29 TRAVEL TIME(MIN.) = 0.68  
 Tc(MIN.) = 10.86  
 SUBAREA AREA(ACRES) = 6.40 SUBAREA RUNOFF(CFS) = 19.24  
 EFFECTIVE AREA(ACRES) = 14.70 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 14.7 PEAK FLOW RATE(CFS) = 44.20

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.41 FLOW VELOCITY(FEET/SEC.) = 7.45  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31105.00 = 1264.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31105.00 TO NODE 31106.00 IS CODE = 51

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

-----  
 ELEVATION DATA: UPSTREAM(FEET) = 585.00 DOWNSTREAM(FEET) = 560.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 344.00 CHANNEL SLOPE = 0.0727  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.521

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.60	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	2.80	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.60	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.10	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.60	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	4.10	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 59.86  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.19  
 AVERAGE FLOW DEPTH(FEET) = 1.56 TRAVEL TIME(MIN.) = 0.70  
 Tc(MIN.) = 11.57  
 SUBAREA AREA(ACRES) = 10.80 SUBAREA RUNOFF(CFS) = 31.31  
 EFFECTIVE AREA(ACRES) = 25.50 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 25.5 PEAK FLOW RATE(CFS) = 73.92

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.69 FLOW VELOCITY(FEET/SEC.) = 8.64  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31106.00 = 1608.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31106.00 TO NODE 31107.00 IS CODE = 51

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

-----  
 ELEVATION DATA: UPSTREAM(FEET) = 560.00 DOWNSTREAM(FEET) = 530.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 619.00 CHANNEL SLOPE = 0.0485  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.297

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.80	0.30	1.000	63
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	1.90	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	1.50	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	8.20	0.30	1.000	66
NATURAL FAIR COVER					
"OPEN BRUSH"	B	2.70	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 94.29  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.89  
 AVERAGE FLOW DEPTH(FEET) = 2.00 TRAVEL TIME(MIN.) = 1.31  
 Tc(MIN.) = 12.87  
 SUBAREA AREA(ACRES) = 15.10 SUBAREA RUNOFF(CFS) = 40.73  
 EFFECTIVE AREA(ACRES) = 40.60 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 40.6 PEAK FLOW RATE(CFS) = 109.52

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 2.11 FLOW VELOCITY(FEET/SEC.) = 8.20  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31107.00 = 2227.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31107.00 TO NODE 31108.00 IS CODE = 51

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<

-----  
 ELEVATION DATA: UPSTREAM(FEET) = 530.00 DOWNSTREAM(FEET) = 515.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 377.00 CHANNEL SLOPE = 0.0398  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.163

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					

"CHAPARRAL,BROADLEAF" B 0.50 0.30 1.000 63  
 NATURAL FAIR COVER  
 "CHAPARRAL,BROADLEAF" B 6.50 0.30 1.000 63  
 NATURAL FAIR COVER  
 "CHAPARRAL,BROADLEAF" B 1.30 0.30 1.000 63  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 1.10 0.30 1.000 66  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 5.50 0.30 1.000 66  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 3.40 0.30 1.000 66  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 133.09  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.00  
 AVERAGE FLOW DEPTH(FEET) = 2.35 TRAVEL TIME(MIN.) = 0.79  
 Tc(MIN.) = 13.66  
 SUBAREA AREA(ACRES) = 18.30 SUBAREA RUNOFF(CFS) = 47.15  
 EFFECTIVE AREA(ACRES) = 58.90 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 58.9 PEAK FLOW RATE(CFS) = 151.75  
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 2.48 FLOW VELOCITY(FEET/SEC.) = 8.25  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31108.00 = 2604.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31108.00 TO NODE 31109.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<  
 -----

ELEVATION DATA: UPSTREAM(FEET) = 515.00 DOWNSTREAM(FEET) = 490.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 520.00 CHANNEL SLOPE = 0.0481  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.000  
 SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	0.70	0.30	1.000	63
NATURAL FAIR COVER					
"GRASS"	B	2.20	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	3.10	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.90	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	7.40	0.30	1.000	63
NATURAL FAIR COVER					
"GRASS"	B	0.30	0.30	1.000	69

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 169.49  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.10  
 AVERAGE FLOW DEPTH(FEET) = 2.49 TRAVEL TIME(MIN.) = 0.95  
 Tc(MIN.) = 14.61

SUBAREA AREA(ACRES) = 14.60 SUBAREA RUNOFF(CFS) = 35.47  
 EFFECTIVE AREA(ACRES) = 73.50 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 73.5 PEAK FLOW RATE(CFS) = 178.58  
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 2.54 FLOW VELOCITY(FEET/SEC.) = 9.24  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31109.00 = 3124.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31109.00 TO NODE 31109.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<  
 -----

MAINLINE Tc(MIN.) = 14.61  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.000  
 SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"OPEN BRUSH"	B	11.40	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	8.90	0.30	1.000	65
NATURAL FAIR COVER					
"CHAPARRAL,BROADLEAF"	B	1.90	0.30	1.000	63
NATURAL FAIR COVER					
"OPEN BRUSH"	B	9.20	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	1.40	0.30	1.000	65

 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 32.80 SUBAREA RUNOFF(CFS) = 79.69  
 EFFECTIVE AREA(ACRES) = 106.30 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 106.3 PEAK FLOW RATE(CFS) = 258.28

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31109.00 TO NODE 31110.00 IS CODE = 51  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<  
 -----

ELEVATION DATA: UPSTREAM(FEET) = 490.00 DOWNSTREAM(FEET) = 432.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1420.00 CHANNEL SLOPE = 0.0408  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000  
 MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.720  
 SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	0.80	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.60	0.30	1.000	66
RESIDENTIAL					
".4 DWELLING/ACRE"	B	0.10	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS,CONTOURED"	B	1.30	0.30	1.000	79

NATURAL FAIR COVER  
 "WOODLAND,GRASS" B 4.00 0.30 1.000 65  
 NATURAL FAIR COVER  
 "CHAPARRAL,BROADLEAF" B 1.50 0.30 1.000 63  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 267.32  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.60  
 AVERAGE FLOW DEPTH(FEET) = 3.05 TRAVEL TIME(MIN.) = 2.47  
 Tc(MIN.) = 17.08  
 SUBAREA AREA(ACRES) = 8.30 SUBAREA RUNOFF(CFS) = 18.08  
 EFFECTIVE AREA(ACRES) = 114.60 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 114.6 PEAK FLOW RATE(CFS) = 258.28  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 3.01 FLOW VELOCITY(FEET/SEC.) = 9.51  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 31110.00 = 4544.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31110.00 TO NODE 31110.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

\*\*\*\*\*  
 MAINLINE Tc(MIN.) = 17.08  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.720  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL FAIR COVER  
 "GRASS" B 0.30 0.30 1.000 69  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 9.60 0.30 1.000 66  
 RESIDENTIAL  
 ".4 DWELLING/ACRE" B 0.40 0.30 0.900 56  
 AGRICULTURAL POOR COVER  
 "ROW CROPS,CONTOURED" B 6.20 0.30 1.000 79  
 NATURAL FAIR COVER  
 "WOODLAND,GRASS" B 3.90 0.30 1.000 65  
 AGRICULTURAL POOR COVER  
 "ROW CROPS,CONTOURED" B 1.40 0.30 1.000 79  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.998  
 SUBAREA AREA(ACRES) = 21.80 SUBAREA RUNOFF(CFS) = 47.48  
 EFFECTIVE AREA(ACRES) = 136.40 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 136.4 PEAK FLOW RATE(CFS) = 297.03

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 31110.00 TO NODE 13301.00 IS CODE = 51

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<  
 >>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<

\*\*\*\*\*  
 ELEVATION DATA: UPSTREAM(FEET) = 432.00 DOWNSTREAM(FEET) = 382.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1847.00 CHANNEL SLOPE = 0.0271  
 CHANNEL BASE(FEET) = 0.00 "Z" FACTOR = 3.000

MANNING'S FACTOR = 0.040 MAXIMUM DEPTH(FEET) = 10.00  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.375  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL POOR COVER  
 "BARREN" B 4.90 0.30 1.000 86  
 AGRICULTURAL POOR COVER  
 "ROW CROPS,CONTOURED" B 1.50 0.30 1.000 79  
 RESIDENTIAL  
 ".4 DWELLING/ACRE" B 0.60 0.30 0.900 56  
 AGRICULTURAL POOR COVER  
 "ROW CROPS,CONTOURED" B 2.50 0.30 1.000 79  
 AGRICULTURAL POOR COVER  
 "ROW CROPS,CONTOURED" B 5.30 0.30 1.000 79  
 AGRICULTURAL POOR COVER  
 "ROW CROPS,CONTOURED" B 3.30 0.30 1.000 79  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.997  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 313.95  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.56  
 AVERAGE FLOW DEPTH(FEET) = 3.50 TRAVEL TIME(MIN.) = 3.60  
 Tc(MIN.) = 20.67  
 SUBAREA AREA(ACRES) = 18.10 SUBAREA RUNOFF(CFS) = 33.83  
 EFFECTIVE AREA(ACRES) = 154.50 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 154.5 PEAK FLOW RATE(CFS) = 297.03  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 3.42 FLOW VELOCITY(FEET/SEC.) = 8.45  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 13301.00 = 6391.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<

\*\*\*\*\*  
 \*\* MAIN STREAM CONFLUENCE DATA \*\*  
 STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER  
 NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE  
 1 297.03 20.67 2.375 0.30( 0.30) 1.00 154.5 31100.00  
 LONGEST FLOWPATH FROM NODE 31100.00 TO NODE 13301.00 = 6391.00 FEET.

\*\*\*\*\*  
 \*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*  
 STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER  
 NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE  
 1 4877.60 35.34 1.736 0.30( 0.24) 0.81 3631.3 13210.00  
 2 4903.16 35.86 1.723 0.30( 0.24) 0.81 3683.2 13200.00  
 3 4919.20 37.05 1.692 0.30( 0.24) 0.81 3773.0 13100.00  
 4 4697.24 60.80 1.285 0.30( 0.24) 0.81 5011.2 13000.00  
 5 4648.20 63.02 1.270 0.30( 0.24) 0.81 5031.0 13010.00  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

\*\*\*\*\*  
 \*\* PEAK FLOW RATE TABLE \*\*  
 STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER  
 NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE

1	4372.57	20.67	2.375	0.30	( 0.25)	0.83	2278.9	31100.00
2	5083.18	35.34	1.736	0.30	( 0.25)	0.82	3785.8	13210.00
3	5106.83	35.86	1.723	0.30	( 0.25)	0.82	3837.7	13200.00
4	5118.50	37.05	1.692	0.30	( 0.25)	0.82	3927.5	13100.00
5	4838.17	60.80	1.285	0.30	( 0.24)	0.82	5165.7	13000.00
6	4786.99	63.02	1.270	0.30	( 0.24)	0.82	5185.5	13010.00
TOTAL AREA (ACRES) =		5185.5						

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 5118.50 Tc(MIN.) = 37.052  
EFFECTIVE AREA(ACRES) = 3927.53 AREA-AVERAGED Fm(INCH/HR) = 0.25  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82  
TOTAL AREA(ACRES) = 5185.5  
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13301.00 = 34659.82 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13301.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 13301.00 TO NODE 13302.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 382.00 DOWNSTREAM(FEET) = 375.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1141.09 CHANNEL SLOPE = 0.0061  
GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 7.62  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.640  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	9.40	0.30	1.000	69

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5124.16  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.23  
AVERAGE FLOW DEPTH(FEET) = 7.62 TRAVEL TIME(MIN.) = 2.06  
Tc(MIN.) = 39.11

SUBAREA AREA(ACRES) = 9.40 SUBAREA RUNOFF(CFS) = 11.33  
EFFECTIVE AREA(ACRES) = 3936.93 AREA-AVERAGED Fm(INCH/HR) = 0.25  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82  
TOTAL AREA(ACRES) = 5194.9 PEAK FLOW RATE(CFS) = 5118.50  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 7.61

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 7.61 FLOW VELOCITY(FEET/SEC.) = 9.23  
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13302.00 = 35800.91 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4372.57	22.83	2.236	0.30( 0.25)	0.83	2288.3	31100.00
2	5083.18	37.40	1.684	0.30( 0.25)	0.82	3795.2	13210.00
3	5106.83	37.92	1.670	0.30( 0.25)	0.82	3847.1	13200.00
4	5118.50	39.11	1.640	0.30( 0.25)	0.82	3936.9	13100.00
5	4838.17	62.89	1.271	0.30( 0.24)	0.82	5175.1	13000.00
6	4786.99	65.12	1.256	0.30( 0.24)	0.82	5194.9	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 5118.50 Tc(MIN.) = 39.11  
AREA-AVERAGED Fm(INCH/HR) = 0.25 AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.82 EFFECTIVE AREA(ACRES) = 3936.93

\*\*\*\*\*

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<

MAINLINE Tc(MIN.) = 39.11

\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.640

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	13.80	0.30	1.000	86
NATURAL POOR COVER					
"BARREN"	B	2.60	0.30	1.000	86
COMMERCIAL	B	1.10	0.30	0.100	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	3.50	0.30	0.900	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	6.90	0.30	1.000	79
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.952  
SUBAREA AREA(ACRES) = 28.10 SUBAREA RUNOFF(CFS) = 34.24  
EFFECTIVE AREA(ACRES) = 3965.03 AREA-AVERAGED Fm(INCH/HR) = 0.25  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82  
TOTAL AREA(ACRES) = 5223.0 PEAK FLOW RATE(CFS) = 5118.50  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<<

MAINLINE Tc(MIN.) = 39.11

\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.640

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	0.10	0.30	1.000	79
COMMERCIAL	B	0.10	0.30	0.100	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	2.40	0.30	0.900	56
AGRICULTURAL POOR COVER					



"ROW CROPS,CONTOURED" B 0.50 0.30 1.000 79  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.894  
 SUBAREA AREA (ACRES) = 3.10 SUBAREA RUNOFF (CFS) = 3.83  
 EFFECTIVE AREA (ACRES) = 3968.13 AREA-AVERAGED Fm (INCH/HR) = 0.25  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82  
 TOTAL AREA (ACRES) = 5226.1 PEAK FLOW RATE (CFS) = 5118.50  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 39.11  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.640  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL POOR COVER  
 "BARREN" B 0.10 0.30 1.000 86  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 2.60 0.30 1.000 66  
 AGRICULTURAL POOR COVER  
 "ROW CROPS,CONTOURED" B 3.10 0.30 1.000 79  
 NATURAL FAIR COVER  
 "WOODLAND,GRASS" B 0.40 0.30 1.000 65  
 NATURAL FAIR COVER  
 "CHAPARRAL,BROADLEAF" B 0.20 0.30 1.000 63  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 13.80 0.30 1.000 66  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 20.20 SUBAREA RUNOFF (CFS) = 24.36  
 EFFECTIVE AREA (ACRES) = 3988.33 AREA-AVERAGED Fm (INCH/HR) = 0.25  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.82  
 TOTAL AREA (ACRES) = 5246.3 PEAK FLOW RATE (CFS) = 5118.50  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 39.11  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.640  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 AGRICULTURAL POOR COVER  
 "ROW CROPS,CONTOURED" B 34.60 0.30 1.000 79  
 NATURAL FAIR COVER  
 "WOODLAND,GRASS" B 2.40 0.30 1.000 65  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 22.60 0.30 1.000 66  
 AGRICULTURAL POOR COVER  
 "ROW CROPS,CONTOURED" B 11.60 0.30 1.000 79  
 APARTMENTS B 0.40 0.30 0.200 56

NATURAL FAIR COVER  
 "CHAPARRAL,BROADLEAF" B 4.80 0.30 1.000 63  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.996  
 SUBAREA AREA (ACRES) = 76.40 SUBAREA RUNOFF (CFS) = 92.21  
 EFFECTIVE AREA (ACRES) = 4064.73 AREA-AVERAGED Fm (INCH/HR) = 0.25  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA (ACRES) = 5322.7 PEAK FLOW RATE (CFS) = 5118.50  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13302.00 TO NODE 13302.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 39.11  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.640  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL FAIR COVER  
 "GRASS" B 1.60 0.30 1.000 69  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 46.40 0.30 1.000 66  
 RESIDENTIAL  
 "11+ DWELLINGS/ACRE" B 0.10 0.30 0.200 56  
 AGRICULTURAL POOR COVER  
 "ROW CROPS,CONTOURED" B 60.70 0.30 1.000 79  
 NATURAL FAIR COVER  
 "WOODLAND,GRASS" B 5.80 0.30 1.000 65  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.999  
 SUBAREA AREA (ACRES) = 114.60 SUBAREA RUNOFF (CFS) = 138.20  
 EFFECTIVE AREA (ACRES) = 4179.33 AREA-AVERAGED Fm (INCH/HR) = 0.25  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA (ACRES) = 5437.3 PEAK FLOW RATE (CFS) = 5230.66

\*\*\*\*\*

FLOW PROCESS FROM NODE 13302.00 TO NODE 13303.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 375.00 DOWNSTREAM (FEET) = 355.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 2193.96 CHANNEL SLOPE = 0.0091  
 GIVEN CHANNEL BASE (FEET) = 50.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 6.92  
 CHANNEL FLOW THRU SUBAREA (CFS) = 5230.66  
 FLOW VELOCITY (FEET/SEC.) = 10.68 FLOW DEPTH (FEET) = 6.92  
 TRAVEL TIME (MIN.) = 3.42 Tc (MIN.) = 42.54  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13303.00 = 37994.87 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4517.54	26.41	2.033	0.30 ( 0.25)	0.84	2530.7	31100.00
2	5211.46	40.83	1.599	0.30 ( 0.25)	0.83	4037.6	13210.00

3 5229.87 41.35 1.588 0.30( 0.25) 0.83 4089.5 13200.00  
 4 5230.66 42.54 1.562 0.30( 0.25) 0.83 4179.3 13100.00  
 5 4989.11 66.36 1.247 0.30( 0.25) 0.82 5417.5 13000.00  
 6 4934.16 68.61 1.232 0.30( 0.25) 0.82 5437.3 13010.00  
 NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE(CFS) = 5230.66 Tc(MIN.) = 42.54  
 AREA-AVERAGED Fm(INCH/HR) = 0.25 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.83 EFFECTIVE AREA(ACRES) = 4179.33

\*\*\*\*\*

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 42.54  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.562  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER "BARREN"	B	0.20	0.30	1.000	86
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.40	0.30	1.000	65
NATURAL POOR COVER "BARREN"	B	0.80	0.30	1.000	86
COMMERCIAL	B	1.40	0.30	0.100	56
NATURAL FAIR COVER "GRASS"	B	2.60	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	2.20	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.834  
 SUBAREA AREA(ACRES) = 7.60 SUBAREA RUNOFF(CFS) = 8.97  
 EFFECTIVE AREA(ACRES) = 4186.93 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA(ACRES) = 5444.9 PEAK FLOW RATE(CFS) = 5230.66  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 42.54  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.562  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	3.10	0.30	1.000	79
NATURAL FAIR COVER "WOODLAND,GRASS"	B	3.40	0.30	1.000	65
NATURAL POOR COVER "BARREN"	B	0.50	0.30	1.000	86
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	B	0.20	0.30	1.000	63
COMMERCIAL	B	3.60	0.30	0.100	56
NATURAL FAIR COVER					

"GRASS" B 4.00 0.30 1.000 69  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.781  
 SUBAREA AREA(ACRES) = 14.80 SUBAREA RUNOFF(CFS) = 17.68  
 EFFECTIVE AREA(ACRES) = 4201.73 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA(ACRES) = 5459.7 PEAK FLOW RATE(CFS) = 5230.66  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 42.54  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.562  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	14.60	0.30	1.000	66
AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	6.30	0.30	1.000	79
NATURAL FAIR COVER "WOODLAND,GRASS"	B	3.70	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 24.60 SUBAREA RUNOFF(CFS) = 27.94  
 EFFECTIVE AREA(ACRES) = 4226.33 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA(ACRES) = 5484.3 PEAK FLOW RATE(CFS) = 5230.66  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 42.54  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.562  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER "BARREN"	B	0.50	0.30	1.000	86
COMMERCIAL	B	0.30	0.30	0.100	56
NATURAL FAIR COVER "OPEN BRUSH"	B	0.20	0.30	1.000	66
RESIDENTIAL ".4 DWELLING/ACRE"	B	0.80	0.30	0.900	56
AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	1.60	0.30	1.000	79
NATURAL POOR COVER "BARREN"	B	31.90	0.30	1.000	86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.990  
 SUBAREA AREA(ACRES) = 35.30 SUBAREA RUNOFF(CFS) = 40.19  
 EFFECTIVE AREA(ACRES) = 4261.63 AREA-AVERAGED Fm(INCH/HR) = 0.25

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
TOTAL AREA (ACRES) = 5519.6 PEAK FLOW RATE (CFS) = 5230.66  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 42.54  
\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.562  
SUBAREA LOSS RATE DATA (AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
COMMERCIAL B 1.70 0.30 0.100 56  
NATURAL FAIR COVER  
"OPEN BRUSH" B 0.30 0.30 1.000 66  
RESIDENTIAL  
".4 DWELLING/ACRE" B 2.60 0.30 0.900 56  
AGRICULTURAL POOR COVER  
"ROW CROPS, CONTOURED" B 5.50 0.30 1.000 79  
NATURAL FAIR COVER  
"WOODLAND, GRASS" B 0.20 0.30 1.000 65  
NATURAL FAIR COVER  
"OPEN BRUSH" B 0.20 0.30 1.000 66  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.830  
SUBAREA AREA (ACRES) = 10.50 SUBAREA RUNOFF (CFS) = 12.41  
EFFECTIVE AREA (ACRES) = 4272.13 AREA-AVERAGED Fm (INCH/HR) = 0.25  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
TOTAL AREA (ACRES) = 5530.1 PEAK FLOW RATE (CFS) = 5230.66  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13303.00 TO NODE 13303.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 42.54  
\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.562  
SUBAREA LOSS RATE DATA (AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
RESIDENTIAL  
".4 DWELLING/ACRE" B 1.30 0.30 0.900 56  
NATURAL POOR COVER  
"BARREN" B 0.30 0.30 1.000 86  
COMMERCIAL B 0.20 0.30 0.100 56  
NATURAL FAIR COVER  
"OPEN BRUSH" B 0.30 0.30 1.000 66  
RESIDENTIAL  
".4 DWELLING/ACRE" B 6.50 0.30 0.900 56  
AGRICULTURAL POOR COVER  
"ROW CROPS, CONTOURED" B 3.00 0.30 1.000 79  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.917  
SUBAREA AREA (ACRES) = 11.60 SUBAREA RUNOFF (CFS) = 13.43  
EFFECTIVE AREA (ACRES) = 4283.73 AREA-AVERAGED Fm (INCH/HR) = 0.25

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
TOTAL AREA (ACRES) = 5541.7 PEAK FLOW RATE (CFS) = 5230.66  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13303.00 TO NODE 13304.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 355.00 DOWNSTREAM (FEET) = 350.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 925.40 CHANNEL SLOPE = 0.0054  
GIVEN CHANNEL BASE (FEET) = 50.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\* ESTIMATED CHANNEL HEIGHT (FEET) = 7.98  
\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.524  
SUBAREA LOSS RATE DATA (AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
PUBLIC PARK B 13.80 0.30 0.850 56  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.850  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 5238.54  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.88  
AVERAGE FLOW DEPTH (FEET) = 7.98 TRAVEL TIME (MIN.) = 1.74  
Tc (MIN.) = 44.27  
SUBAREA AREA (ACRES) = 13.80 SUBAREA RUNOFF (CFS) = 15.76  
EFFECTIVE AREA (ACRES) = 4297.53 AREA-AVERAGED Fm (INCH/HR) = 0.25  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
TOTAL AREA (ACRES) = 5555.5 PEAK FLOW RATE (CFS) = 5230.66  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
GIVEN CHANNEL BASE (FEET) = 50.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\* ESTIMATED CHANNEL HEIGHT (FEET) = 7.97

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH (FEET) = 7.97 FLOW VELOCITY (FEET/SEC.) = 8.88  
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13304.00 = 38920.27 FEET.

\*\* PEAK FLOW RATE TABLE \*\*  
STREAM Q Tc Intensity Fp (Fm) Ap Ae HEADWATER  
NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE  
1 4517.54 28.22 1.952 0.30 ( 0.25) 0.85 2648.9 31100.00  
2 5211.46 42.57 1.561 0.30 ( 0.25) 0.83 4155.8 13210.00  
3 5229.87 43.08 1.550 0.30 ( 0.25) 0.83 4207.7 13200.00  
4 5230.66 44.27 1.524 0.30 ( 0.25) 0.83 4297.5 13100.00  
5 4989.11 68.12 1.235 0.30 ( 0.25) 0.83 5535.7 13000.00  
6 4934.16 70.37 1.220 0.30 ( 0.25) 0.83 5555.5 13010.00

NEW PEAK FLOW DATA ARE:  
PEAK FLOW RATE (CFS) = 5230.66 Tc (MIN.) = 44.27  
AREA-AVERAGED Fm (INCH/HR) = 0.25 AREA-AVERAGED Fp (INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.83 EFFECTIVE AREA (ACRES) = 4297.53

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 44.27  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.524  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL POOR COVER  
 "BARREN" B 7.80 0.30 1.000 86  
 AGRICULTURAL POOR COVER  
 "ROW CROPS,CONTOURED" B 1.70 0.30 1.000 79  
 NATURAL POOR COVER  
 "BARREN" B 9.40 0.30 1.000 86  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 1.20 0.30 1.000 66  
 RESIDENTIAL  
 ".4 DWELLING/ACRE" B 0.10 0.30 0.900 56  
 AGRICULTURAL POOR COVER  
 "ROW CROPS,CONTOURED" B 2.60 0.30 1.000 79  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 22.80 SUBAREA RUNOFF(CFS) = 25.13  
 EFFECTIVE AREA(ACRES) = 4320.33 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA(ACRES) = 5578.3 PEAK FLOW RATE(CFS) = 5230.66  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13304.00 TO NODE 13304.00 IS CODE = 81

-----  
 >>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 44.27  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.524  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL FAIR COVER  
 "WOODLAND,GRASS" B 0.20 0.30 1.000 65  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 0.30 0.30 1.000 66  
 RESIDENTIAL  
 ".4 DWELLING/ACRE" B 0.20 0.30 0.900 56  
 AGRICULTURAL POOR COVER  
 "ROW CROPS,CONTOURED" B 2.70 0.30 1.000 79  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.994  
 SUBAREA AREA(ACRES) = 3.40 SUBAREA RUNOFF(CFS) = 3.75  
 EFFECTIVE AREA(ACRES) = 4323.73 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.83  
 TOTAL AREA(ACRES) = 5581.7 PEAK FLOW RATE(CFS) = 5230.66  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13304.00 TO NODE 13305.00 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

-----  
 ELEVATION DATA: UPSTREAM(FEET) = 350.00 DOWNSTREAM(FEET) = 315.00

CHANNEL LENGTH THRU SUBAREA(FEET) = 2966.27 CHANNEL SLOPE = 0.0118  
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 6.46  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.433  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL FAIR COVER  
 "GRASS" B 27.40 0.30 1.000 69  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5244.62  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.69  
 AVERAGE FLOW DEPTH(FEET) = 6.46 TRAVEL TIME(MIN.) = 4.23  
 Tc(MIN.) = 48.50  
 SUBAREA AREA(ACRES) = 27.40 SUBAREA RUNOFF(CFS) = 27.93  
 EFFECTIVE AREA(ACRES) = 4351.13 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84  
 TOTAL AREA(ACRES) = 5609.1 PEAK FLOW RATE(CFS) = 5230.66  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 6.45

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 6.45 FLOW VELOCITY(FEET/SEC.) = 11.69  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4517.54	32.64	1.805	0.30( 0.25)	0.85	2702.5	31100.00
2	5211.46	46.80	1.469	0.30( 0.25)	0.84	4209.4	13210.00
3	5229.87	47.31	1.458	0.30( 0.25)	0.84	4261.3	13200.00
4	5230.66	48.50	1.433	0.30( 0.25)	0.84	4351.1	13100.00
5	4989.11	72.41	1.206	0.30( 0.25)	0.83	5589.3	13000.00
6	4934.16	74.67	1.191	0.30( 0.25)	0.83	5609.1	13010.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE(CFS) = 5230.66 Tc(MIN.) = 48.50  
 AREA-AVERAGED Fm(INCH/HR) = 0.25 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.84 EFFECTIVE AREA(ACRES) = 4351.13

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

-----  
 >>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 48.50  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.433  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL POOR COVER  
 "BARREN" B 18.40 0.30 1.000 86  
 NATURAL FAIR COVER  
 "MEADOWS" B 1.20 0.30 1.000 70  
 NATURAL FAIR COVER

"WOODLAND,GRASS" B 0.10 0.30 1.000 65  
 NATURAL POOR COVER  
 "BARREN" B 26.60 0.30 1.000 86  
 COMMERCIAL B 3.90 0.30 0.100 56  
 AGRICULTURAL POOR COVER  
 "FALLOW" B 3.00 0.30 1.000 86  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.934  
 SUBAREA AREA (ACRES) = 53.20 SUBAREA RUNOFF (CFS) = 55.17  
 EFFECTIVE AREA (ACRES) = 4404.33 AREA-AVERAGED Fm (INCH/HR) = 0.25  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84  
 TOTAL AREA (ACRES) = 5662.3 PEAK FLOW RATE (CFS) = 5230.66  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 48.50  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.433  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 AGRICULTURAL POOR COVER  
 "ROW CROPS, CONTOURED" B 1.10 0.30 1.000 79  
 NATURAL FAIR COVER  
 "WOODLAND, GRASS" B 0.20 0.30 1.000 65  
 NATURAL POOR COVER  
 "BARREN" B 14.00 0.30 1.000 86  
 COMMERCIAL B 4.30 0.30 0.100 56  
 AGRICULTURAL POOR COVER  
 "FALLOW" B 5.30 0.30 1.000 86  
 NATURAL FAIR COVER  
 "GRASS" B 2.70 0.30 1.000 69  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.860  
 SUBAREA AREA (ACRES) = 27.60 SUBAREA RUNOFF (CFS) = 29.18  
 EFFECTIVE AREA (ACRES) = 4431.93 AREA-AVERAGED Fm (INCH/HR) = 0.25  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84  
 TOTAL AREA (ACRES) = 5689.9 PEAK FLOW RATE (CFS) = 5230.66  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 48.50  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.433  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL FAIR COVER  
 "MEADOWS" B 3.20 0.30 1.000 70  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 6.10 0.30 1.000 66  
 RESIDENTIAL

".4 DWELLING/ACRE" B 7.50 0.30 0.900 56  
 AGRICULTURAL POOR COVER  
 "ROW CROPS, CONTOURED" B 5.40 0.30 1.000 79  
 NATURAL FAIR COVER  
 "WOODLAND, GRASS" B 1.60 0.30 1.000 65  
 NATURAL POOR COVER  
 "BARREN" B 1.90 0.30 1.000 86  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.971  
 SUBAREA AREA (ACRES) = 25.70 SUBAREA RUNOFF (CFS) = 26.40  
 EFFECTIVE AREA (ACRES) = 4457.63 AREA-AVERAGED Fm (INCH/HR) = 0.25  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84  
 TOTAL AREA (ACRES) = 5715.6 PEAK FLOW RATE (CFS) = 5230.66  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 48.50  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.433  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 COMMERCIAL B 2.00 0.30 0.100 56  
 AGRICULTURAL POOR COVER  
 "FALLOW" B 3.70 0.30 1.000 86  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 2.10 0.30 1.000 66  
 RESIDENTIAL  
 ".4 DWELLING/ACRE" B 2.60 0.30 0.900 56  
 AGRICULTURAL POOR COVER  
 "ROW CROPS, CONTOURED" B 0.20 0.30 1.000 79  
 NATURAL FAIR COVER  
 "WOODLAND, GRASS" B 0.10 0.30 1.000 65  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.807  
 SUBAREA AREA (ACRES) = 10.70 SUBAREA RUNOFF (CFS) = 11.46  
 EFFECTIVE AREA (ACRES) = 4468.33 AREA-AVERAGED Fm (INCH/HR) = 0.25  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84  
 TOTAL AREA (ACRES) = 5726.3 PEAK FLOW RATE (CFS) = 5230.66  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 48.50  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.433  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 0.50 0.30 1.000 66  
 RESIDENTIAL  
 ".4 DWELLING/ACRE" B 8.20 0.30 0.900 56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.906  
 SUBAREA AREA(ACRES) = 8.70 SUBAREA RUNOFF(CFS) = 9.09  
 EFFECTIVE AREA(ACRES) = 4477.03 AREA-AVERAGED Fm(INCH/HR) = 0.25  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84  
 TOTAL AREA(ACRES) = 5735.0 PEAK FLOW RATE(CFS) = 5230.66  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 3A00EVRL.DNA  
 MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1221.21	13.34	0.30( 0.13)	0.43	436.8	120.00
2	1221.20	13.34	0.30( 0.13)	0.43	436.8	110.00
3	1039.13	20.29	0.30( 0.13)	0.43	504.5	100.00
4	976.70	22.82	0.30( 0.13)	0.43	510.2	150.00
TOTAL AREA(ACRES) =						510.2

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\*\*\*\* MAIN STREAM CONFLUENCE DATA \*\*\*\*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4517.54	32.64	1.805	0.30( 0.26)	0.85	2828.4	31100.00
2	5211.46	46.80	1.469	0.30( 0.25)	0.84	4335.3	13210.00
3	5229.87	47.31	1.458	0.30( 0.25)	0.84	4387.2	13200.00
4	5230.66	48.50	1.433	0.30( 0.25)	0.84	4477.0	13100.00
5	4989.11	72.41	1.206	0.30( 0.25)	0.83	5715.2	13000.00
6	4934.16	74.67	1.191	0.30( 0.25)	0.83	5735.0	13010.00
LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 =							41886.54 FEET.

\*\*\*\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*\*\*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1221.21	13.34	3.218	0.30( 0.13)	0.43	436.8	120.00
2	1221.20	13.34	3.218	0.30( 0.13)	0.43	436.8	110.00
3	1039.13	20.29	2.401	0.30( 0.13)	0.43	504.5	100.00
4	976.70	22.82	2.237	0.30( 0.13)	0.43	510.2	150.00
LONGEST FLOWPATH FROM NODE 150.00 TO NODE 13305.00 =							9867.00 FEET.

\*\*\*\*\* PEAK FLOW RATE TABLE \*\*\*\*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4748.98	13.34	3.218	0.30( 0.22)	0.74	1592.4	120.00
2	4749.01	13.34	3.218	0.30( 0.22)	0.74	1592.5	110.00
3	4924.79	20.29	2.401	0.30( 0.23)	0.76	2262.4	100.00
4	5014.05	22.82	2.237	0.30( 0.23)	0.77	2487.4	150.00
5	5294.16	32.64	1.805	0.30( 0.24)	0.79	3338.6	31100.00
6	5832.35	46.80	1.469	0.30( 0.24)	0.80	4845.5	13210.00

7	5845.64	47.31	1.458	0.30( 0.24)	0.80	4897.4	13200.00
8	5834.42	48.50	1.433	0.30( 0.24)	0.80	4987.2	13100.00
9	5488.06	72.41	1.206	0.30( 0.24)	0.80	6225.4	13000.00
10	5426.05	74.67	1.191	0.30( 0.24)	0.80	6245.2	13010.00
TOTAL AREA(ACRES) =						6245.2	

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 5845.64 Tc(MIN.) = 47.307  
 EFFECTIVE AREA(ACRES) = 4897.35 AREA-AVERAGED Fm(INCH/HR) = 0.24  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.76  
 TOTAL AREA(ACRES) = 6245.2  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13305.00 = 41886.54 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13305.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13305.00 TO NODE 13306.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 315.00 DOWNSTREAM(FEET) = 245.50  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 4408.41 CHANNEL SLOPE = 0.0158  
 GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.36  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.369

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	68.80	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.850

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 5880.14

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 13.39

AVERAGE FLOW DEPTH(FEET) = 6.36 TRAVEL TIME(MIN.) = 5.49

Tc(MIN.) = 52.79

SUBAREA AREA(ACRES) = 68.80 SUBAREA RUNOFF(CFS) = 69.00

EFFECTIVE AREA(ACRES) = 4966.15 AREA-AVERAGED Fm(INCH/HR) = 0.24

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80

TOTAL AREA(ACRES) = 6314.0 PEAK FLOW RATE(CFS) = 5845.64

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 50.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.34

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 6.34 FLOW VELOCITY(FEET/SEC.) = 13.37

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13306.00 = 46294.95 FEET.

\*\*\*\*\* PEAK FLOW RATE TABLE \*\*\*\*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4748.98	19.16	2.505	0.30( 0.22)	0.74	1661.2	120.00

2	4749.01	19.16	2.505	0.30	( 0.22)	0.74	1661.3	110.00
3	4924.79	26.05	2.049	0.30	( 0.23)	0.76	2331.2	100.00
4	5014.05	28.56	1.937	0.30	( 0.23)	0.77	2556.2	150.00
5	5294.16	38.28	1.661	0.30	( 0.24)	0.79	3407.4	31100.00
6	5832.35	52.28	1.375	0.30	( 0.24)	0.80	4914.3	13210.00
7	5845.64	52.79	1.369	0.30	( 0.24)	0.80	4966.2	13200.00
8	5834.42	53.99	1.356	0.30	( 0.24)	0.80	5056.0	13100.00
9	5488.06	78.00	1.169	0.30	( 0.24)	0.80	6294.2	13000.00
10	5426.05	80.29	1.153	0.30	( 0.24)	0.80	6314.0	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 5845.64 Tc (MIN.) = 52.79  
 AREA-AVERAGED Fm (INCH/HR) = 0.24 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.80 EFFECTIVE AREA (ACRES) = 4966.15

\*\*\*\*\*

FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) = 52.79  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.369  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	21.50	0.30	1.000	86
COMMERCIAL	B	15.30	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	0.80	0.30	1.000	69
AGRICULTURAL FAIR COVER					
"ORCHARDS"	B	0.60	0.30	1.000	65
RESIDENTIAL					
".4 DWELLING/ACRE"	B	8.00	0.30	0.900	56
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.10	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.685  
 SUBAREA AREA (ACRES) = 46.30 SUBAREA RUNOFF (CFS) = 48.49  
 EFFECTIVE AREA (ACRES) = 5012.45 AREA-AVERAGED Fm (INCH/HR) = 0.24  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80  
 TOTAL AREA (ACRES) = 6360.3 PEAK FLOW RATE (CFS) = 5845.64  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) = 52.79  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.369  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL POOR COVER					
"BARREN"	B	43.30	0.30	1.000	86
COMMERCIAL	B	4.90	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	5.70	0.30	1.000	69

AGRICULTURAL FAIR COVER

"ORCHARDS"	B	0.50	0.30	1.000	65
PUBLIC PARK	B	1.10	0.30	0.850	56
RESIDENTIAL					
".4 DWELLING/ACRE"	B	3.10	0.30	0.900	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.917  
 SUBAREA AREA (ACRES) = 58.60 SUBAREA RUNOFF (CFS) = 57.71  
 EFFECTIVE AREA (ACRES) = 5071.05 AREA-AVERAGED Fm (INCH/HR) = 0.24  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80  
 TOTAL AREA (ACRES) = 6418.9 PEAK FLOW RATE (CFS) = 5845.64  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) = 52.79  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.369  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	6.80	0.30	1.000	65
NATURAL POOR COVER					
"BARREN"	B	0.70	0.30	1.000	86
COMMERCIAL	B	1.10	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	0.50	0.30	1.000	69
AGRICULTURAL FAIR COVER					
"ORCHARDS"	B	0.10	0.30	1.000	65
PUBLIC PARK	B	0.50	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.890  
 SUBAREA AREA (ACRES) = 9.70 SUBAREA RUNOFF (CFS) = 9.62  
 EFFECTIVE AREA (ACRES) = 5080.75 AREA-AVERAGED Fm (INCH/HR) = 0.24  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80  
 TOTAL AREA (ACRES) = 6428.6 PEAK FLOW RATE (CFS) = 5845.64  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13306.00 TO NODE 13306.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc (MIN.) = 52.79  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.369  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL					
".4 DWELLING/ACRE"	B	2.20	0.30	0.900	56
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	0.10	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.904  
 SUBAREA AREA (ACRES) = 2.30 SUBAREA RUNOFF (CFS) = 2.27

EFFECTIVE AREA (ACRES) = 5083.05 AREA-AVERAGED Fm (INCH/HR) = 0.24  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80  
 TOTAL AREA (ACRES) = 6430.9 PEAK FLOW RATE (CFS) = 5845.64  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13306.00 TO NODE 13307.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM (FEET) = 245.50 DOWNSTREAM (FEET) = 220.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1543.21 CHANNEL SLOPE = 0.0165  
 GIVEN CHANNEL BASE (FEET) = 50.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 6.25  
 CHANNEL FLOW THRU SUBAREA (CFS) = 5845.64  
 FLOW VELOCITY (FEET/SEC.) = 13.60 FLOW DEPTH (FEET) = 6.25  
 TRAVEL TIME (MIN.) = 1.89 Tc (MIN.) = 54.69  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13307.00 = 47838.16 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4748.98	21.18	2.343	0.30 ( 0.22)	0.75	1778.1	120.00
2	4749.01	21.18	2.343	0.30 ( 0.22)	0.75	1778.2	110.00
3	4924.79	28.05	1.960	0.30 ( 0.23)	0.76	2448.1	100.00
4	5014.05	30.54	1.859	0.30 ( 0.23)	0.77	2673.1	150.00
5	5294.16	40.23	1.612	0.30 ( 0.24)	0.79	3524.3	31100.00
6	5832.35	54.18	1.354	0.30 ( 0.24)	0.80	5031.2	13210.00
7	5845.64	54.69	1.348	0.30 ( 0.24)	0.80	5083.1	13200.00
8	5834.42	55.88	1.335	0.30 ( 0.24)	0.80	5172.9	13100.00
9	5488.06	79.93	1.156	0.30 ( 0.24)	0.80	6411.1	13000.00
10	5426.05	82.22	1.140	0.30 ( 0.24)	0.80	6430.9	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 5845.64 Tc (MIN.) = 54.69  
 AREA-AVERAGED Fm (INCH/HR) = 0.24 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.80 EFFECTIVE AREA (ACRES) = 5083.05

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13307.00 TO NODE 13307.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 =====

MAINLINE Tc (MIN.) = 54.69  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.348

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	0.20	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	0.10	0.30	1.000	69
AGRICULTURAL FAIR COVER					
"ORCHARDS"	B	0.20	0.30	1.000	65
NATURAL POOR COVER					
"BARREN"	B	3.70	0.30	1.000	86
COMMERCIAL	B	0.30	0.30	0.100	56
NATURAL FAIR COVER					

"GRASS" B 3.20 0.30 1.000 69  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.942  
 SUBAREA AREA (ACRES) = 7.70 SUBAREA RUNOFF (CFS) = 7.39  
 EFFECTIVE AREA (ACRES) = 5090.75 AREA-AVERAGED Fm (INCH/HR) = 0.24  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80  
 TOTAL AREA (ACRES) = 6438.6 PEAK FLOW RATE (CFS) = 5845.64  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13307.00 TO NODE 13307.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 =====

MAINLINE Tc (MIN.) = 54.69  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.348  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/  
LAND USE SCS SOIL AREA Fp Ap SCS  
GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL FAIR COVER  
 "WOODLAND, GRASS" B 3.60 0.30 1.000 65  
 NATURAL FAIR COVER  
 "GRASS" B 1.90 0.30 1.000 69  
 NATURAL FAIR COVER  
 "WOODLAND, GRASS" B 0.60 0.30 1.000 65  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 6.10 SUBAREA RUNOFF (CFS) = 5.76  
 EFFECTIVE AREA (ACRES) = 5096.85 AREA-AVERAGED Fm (INCH/HR) = 0.24  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80  
 TOTAL AREA (ACRES) = 6444.7 PEAK FLOW RATE (CFS) = 5845.64  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13307.00 TO NODE 13308.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM (FEET) = 220.00 DOWNSTREAM (FEET) = 212.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 925.62 CHANNEL SLOPE = 0.0086  
 GIVEN CHANNEL BASE (FEET) = 50.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 7.46  
 CHANNEL FLOW THRU SUBAREA (CFS) = 5845.64  
 FLOW VELOCITY (FEET/SEC.) = 10.83 FLOW DEPTH (FEET) = 7.46  
 TRAVEL TIME (MIN.) = 1.42 Tc (MIN.) = 56.11  
 LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13308.00 = 48763.78 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4748.98	22.69	2.245	0.30 ( 0.22)	0.75	1791.9	120.00
2	4749.01	22.70	2.245	0.30 ( 0.22)	0.75	1792.0	110.00
3	4924.79	29.55	1.893	0.30 ( 0.23)	0.76	2461.9	100.00
4	5014.05	32.03	1.821	0.30 ( 0.23)	0.77	2686.9	150.00
5	5294.16	41.70	1.580	0.30 ( 0.24)	0.79	3538.1	31100.00
6	5832.35	55.60	1.338	0.30 ( 0.24)	0.80	5045.0	13210.00



7	5845.64	56.11	1.333	0.30	( 0.24)	0.80	5096.9	13200.00
8	5834.42	57.31	1.320	0.30	( 0.24)	0.80	5186.7	13100.00
9	5488.06	81.38	1.146	0.30	( 0.24)	0.80	6424.9	13000.00
10	5426.05	83.68	1.131	0.30	( 0.24)	0.80	6444.7	13010.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 5845.64 Tc(MIN.) = 56.11  
 AREA-AVERAGED Fm(INCH/HR) = 0.24 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.80 EFFECTIVE AREA(ACRES) = 5096.85

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 56.11  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.333  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER					
"GRASS"	B	0.10	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.20	0.30	1.000	66
NATURAL FAIR COVER					
"WOODLAND,GRASS"	B	5.00	0.30	1.000	65
COMMERCIAL	B	3.20	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	0.10	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	0.90	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.697  
 SUBAREA AREA(ACRES) = 9.50 SUBAREA RUNOFF(CFS) = 9.61  
 EFFECTIVE AREA(ACRES) = 5106.35 AREA-AVERAGED Fm(INCH/HR) = 0.24  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.80  
 TOTAL AREA(ACRES) = 6454.2 PEAK FLOW RATE(CFS) = 5845.64  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 56.11  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.333  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
APARTMENTS	B	0.30	0.30	0.200	56
NATURAL POOR COVER					
"BARREN"	B	0.20	0.30	1.000	86
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	1.00	0.30	1.000	63
COMMERCIAL	B	41.90	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	7.20	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	25.00	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.498  
 SUBAREA AREA(ACRES) = 75.60 SUBAREA RUNOFF(CFS) = 80.52  
 EFFECTIVE AREA(ACRES) = 5181.95 AREA-AVERAGED Fm(INCH/HR) = 0.24  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA(ACRES) = 6529.8 PEAK FLOW RATE(CFS) = 5845.64  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 56.11  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.333  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
PUBLIC PARK	B	0.10	0.30	0.850	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	0.90	0.30	1.000	79
SCHOOL	B	0.30	0.30	0.600	56
NATURAL FAIR COVER					
"WOODLAND, GRASS"	B	13.20	0.30	1.000	65
APARTMENTS	B	0.50	0.30	0.200	56
NATURAL FAIR COVER					
"CHAPARRAL, BROADLEAF"	B	0.60	0.30	1.000	63

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.966  
 SUBAREA AREA(ACRES) = 15.60 SUBAREA RUNOFF(CFS) = 14.64  
 EFFECTIVE AREA(ACRES) = 5197.55 AREA-AVERAGED Fm(INCH/HR) = 0.24  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA(ACRES) = 6545.4 PEAK FLOW RATE(CFS) = 5845.64  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 56.11  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.333  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
COMMERCIAL	B	33.90	0.30	0.100	56
NATURAL FAIR COVER					
"GRASS"	B	17.60	0.30	1.000	69
NATURAL FAIR COVER					
"OPEN BRUSH"	B	16.80	0.30	1.000	66
RESIDENTIAL					
"11+ DWELLINGS/ACRE"	B	0.60	0.30	0.200	56
RESIDENTIAL					
"8-10 DWELLINGS/ACRE"	B	1.50	0.30	0.400	56
AGRICULTURAL POOR COVER					
"ROW CROPS, CONTOURED"	B	10.00	0.30	1.000	79

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.603

SUBAREA AREA (ACRES) = 80.40 SUBAREA RUNOFF (CFS) = 83.34  
 EFFECTIVE AREA (ACRES) = 5277.95 AREA-AVERAGED Fm (INCH/HR) = 0.24  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA (ACRES) = 6625.8 PEAK FLOW RATE (CFS) = 5845.64  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 56.11  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.333  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 SCHOOL B 0.30 0.30 0.600 56  
 NATURAL FAIR COVER  
 "WOODLAND, GRASS" B 0.70 0.30 1.000 65  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.880  
 SUBAREA AREA (ACRES) = 1.00 SUBAREA RUNOFF (CFS) = 0.96  
 EFFECTIVE AREA (ACRES) = 5278.95 AREA-AVERAGED Fm (INCH/HR) = 0.24  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA (ACRES) = 6626.8 PEAK FLOW RATE (CFS) = 5845.64  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 56.11  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.333  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL FAIR COVER  
 "GRASS" B 0.30 0.30 1.000 69  
 NATURAL FAIR COVER  
 "WOODLAND, GRASS" B 0.80 0.30 1.000 65  
 NATURAL FAIR COVER  
 "GRASS" B 0.50 0.30 1.000 69  
 NATURAL FAIR COVER  
 "WOODLAND, GRASS" B 0.20 0.30 1.000 65  
 NATURAL FAIR COVER  
 "GRASS" B 0.30 0.30 1.000 69  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 2.10 SUBAREA RUNOFF (CFS) = 1.95  
 EFFECTIVE AREA (ACRES) = 5281.05 AREA-AVERAGED Fm (INCH/HR) = 0.24  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA (ACRES) = 6628.9 PEAK FLOW RATE (CFS) = 5845.64  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 56.11  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.333  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 NATURAL FAIR COVER  
 "GRASS" B 1.20 0.30 1.000 69  
 NATURAL FAIR COVER  
 "OPEN BRUSH" B 0.50 0.30 1.000 66  
 PUBLIC PARK B 1.70 0.30 0.850 56  
 NATURAL FAIR COVER  
 "WOODLAND, GRASS" B 7.20 0.30 1.000 65  
 NATURAL FAIR COVER  
 "GRASS" B 1.00 0.30 1.000 69  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.978  
 SUBAREA AREA (ACRES) = 11.60 SUBAREA RUNOFF (CFS) = 10.85  
 EFFECTIVE AREA (ACRES) = 5292.65 AREA-AVERAGED Fm (INCH/HR) = 0.24  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.79  
 TOTAL AREA (ACRES) = 6640.5 PEAK FLOW RATE (CFS) = 5845.64  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 10  
 -----

>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: R100EV29.DNA  
 MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25952.48	18.57	0.30 ( 0.25)	0.84	4441.0	50400.00
2	29490.11	27.75	0.30 ( 0.26)	0.85	7166.7	50300.00
3	31610.95	34.92	0.30 ( 0.26)	0.86	9562.6	12730.00
4	32325.57	38.93	0.30 ( 0.26)	0.88	11020.6	40200.00
5	32984.66	42.78	0.30 ( 0.27)	0.89	12586.3	390.00
6	34583.02	52.10	0.30 ( 0.27)	0.91	16324.6	40100.00
7	37025.37	60.72	0.30 ( 0.28)	0.93	19668.8	11801.00
8	39699.67	70.19	0.30 ( 0.28)	0.94	23965.0	11530.00
9	41867.11	78.70	0.30 ( 0.28)	0.95	28949.9	11910.00
10	43890.13	85.80	0.30 ( 0.29)	0.96	33550.4	11330.00
11	44865.15	92.14	0.30 ( 0.29)	0.96	37981.4	11130.00
12	44658.88	99.73	0.30 ( 0.29)	0.96	41975.3	12330.00
13	44345.27	106.37	0.30 ( 0.29)	0.97	45318.5	12400.00
14	43725.00	115.05	0.30 ( 0.29)	0.97	48687.3	12201.00
15	43224.22	119.01	0.30 ( 0.29)	0.97	49772.0	12111.00
16	42525.17	124.38	0.30 ( 0.29)	0.97	51141.4	12101.10
17	41962.43	128.40	0.30 ( 0.29)	0.97	51990.5	10400.00
18	40360.14	136.43	0.30 ( 0.29)	0.97	53305.6	12010.00
19	39023.95	142.30	0.30 ( 0.29)	0.97	53619.4	10210.00

20 35446.18 168.35 0.30( 0.29) 0.97 54352.1 10100.00  
TOTAL AREA(ACRES) = 54352.1

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12904.00 TO NODE 12904.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25952.48	18.57	0.30( 0.25)	0.84	4441.0	50400.00
2	29490.11	27.75	0.30( 0.26)	0.85	7166.7	50300.00
3	31610.95	34.92	0.30( 0.26)	0.86	9562.6	12730.00
4	32325.57	38.93	0.30( 0.26)	0.88	11020.6	40200.00
5	32984.66	42.78	0.30( 0.27)	0.89	12586.3	390.00
6	34583.02	52.10	0.30( 0.27)	0.91	16324.6	40100.00
7	37025.37	60.72	0.30( 0.28)	0.93	19668.8	11801.00
8	39699.67	70.19	0.30( 0.28)	0.94	23965.0	11530.00
9	41867.11	78.70	0.30( 0.28)	0.95	28949.9	11910.00
10	43890.13	85.80	0.30( 0.29)	0.96	33550.4	11330.00
11	44865.15	92.14	0.30( 0.29)	0.96	37981.4	11130.00
12	44658.88	99.73	0.30( 0.29)	0.96	41975.3	12330.00
13	44345.27	106.37	0.30( 0.29)	0.97	45318.5	12400.00
14	43725.00	115.05	0.30( 0.29)	0.97	48687.3	12201.00
15	43224.22	119.01	0.30( 0.29)	0.97	49772.0	12111.00
16	42525.17	124.38	0.30( 0.29)	0.97	51141.4	12101.10
17	41962.43	128.40	0.30( 0.29)	0.97	51990.5	10400.00
18	40360.14	136.43	0.30( 0.29)	0.97	53305.6	12010.00
19	39023.95	142.30	0.30( 0.29)	0.97	53619.4	10210.00
20	35446.18	168.35	0.30( 0.29)	0.97	54352.1	10100.00

TOTAL AREA(ACRES) = 54352.1

\*\*\*\*\*  
FLOW PROCESS FROM NODE 12904.00 TO NODE 13308.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 213.00 DOWNSTREAM(FEET) = 212.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1389.52 CHANNEL SLOPE = 0.0007  
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 19.26  
CHANNEL FLOW THRU SUBAREA(CFS) = 44865.15  
FLOW VELOCITY(FEET/SEC.) = 7.86 FLOW DEPTH(FEET) = 19.26  
TRAVEL TIME(MIN.) = 2.95 Tc(MIN.) = 95.08  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118090.66 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25952.48	22.04	2.287	0.30( 0.25)	0.84	4441.0	50400.00
2	29490.11	31.09	1.845	0.30( 0.26)	0.85	7166.7	50300.00
3	31610.95	38.19	1.663	0.30( 0.26)	0.86	9562.6	12730.00
4	32325.57	42.18	1.570	0.30( 0.26)	0.88	11020.6	40200.00
5	32984.66	46.00	1.487	0.30( 0.27)	0.89	12586.3	390.00

6	34583.02	55.28	1.342	0.30( 0.27)	0.91	16324.6	40100.00
7	37025.37	63.84	1.264	0.30( 0.28)	0.93	19668.8	11801.00
8	39699.67	73.25	1.201	0.30( 0.28)	0.94	23965.0	11530.00
9	41867.11	81.71	1.144	0.30( 0.28)	0.95	28949.9	11910.00
10	43890.13	88.77	1.096	0.30( 0.29)	0.96	33550.4	11330.00
11	44865.15	95.08	1.065	0.30( 0.29)	0.96	37981.4	11130.00
12	44658.88	102.68	1.030	0.30( 0.29)	0.96	41975.3	12330.00
13	44345.27	109.33	1.000	0.30( 0.29)	0.97	45318.5	12400.00
14	43725.00	118.01	0.960	0.30( 0.29)	0.97	48687.3	12201.00
15	43224.22	121.99	0.946	0.30( 0.29)	0.97	49772.0	12111.00
16	42525.17	127.37	0.932	0.30( 0.29)	0.97	51141.4	12101.10
17	41962.43	131.40	0.921	0.30( 0.29)	0.97	51990.5	10400.00
18	40360.14	139.46	0.900	0.30( 0.29)	0.97	53305.6	12010.00
19	39023.95	145.37	0.885	0.30( 0.29)	0.97	53619.4	10210.00
20	35446.18	171.51	0.817	0.30( 0.29)	0.97	54352.1	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 44865.15 Tc(MIN.) = 95.08

AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.96 EFFECTIVE AREA(ACRES) = 37981.36

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13307.00 TO NODE 13308.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25952.48	22.04	2.287	0.30( 0.25)	0.84	4441.0	50400.00
2	29490.11	31.09	1.845	0.30( 0.26)	0.85	7166.7	50300.00
3	31610.95	38.19	1.663	0.30( 0.26)	0.86	9562.6	12730.00
4	32325.57	42.18	1.570	0.30( 0.26)	0.88	11020.6	40200.00
5	32984.66	46.00	1.487	0.30( 0.27)	0.89	12586.3	390.00
6	34583.02	55.28	1.342	0.30( 0.27)	0.91	16324.6	40100.00
7	37025.37	63.84	1.264	0.30( 0.28)	0.93	19668.8	11801.00
8	39699.67	73.25	1.201	0.30( 0.28)	0.94	23965.0	11530.00
9	41867.11	81.71	1.144	0.30( 0.28)	0.95	28949.9	11910.00
10	43890.13	88.77	1.096	0.30( 0.29)	0.96	33550.4	11330.00
11	44865.15	95.08	1.065	0.30( 0.29)	0.96	37981.4	11130.00
12	44658.88	102.68	1.030	0.30( 0.29)	0.96	41975.3	12330.00
13	44345.27	109.33	1.000	0.30( 0.29)	0.97	45318.5	12400.00
14	43725.00	118.01	0.960	0.30( 0.29)	0.97	48687.3	12201.00
15	43224.22	121.99	0.946	0.30( 0.29)	0.97	49772.0	12111.00
16	42525.17	127.37	0.932	0.30( 0.29)	0.97	51141.4	12101.10
17	41962.43	131.40	0.921	0.30( 0.29)	0.97	51990.5	10400.00
18	40360.14	139.46	0.900	0.30( 0.29)	0.97	53305.6	12010.00
19	39023.95	145.37	0.885	0.30( 0.29)	0.97	53619.4	10210.00
20	35446.18	171.51	0.817	0.30( 0.29)	0.97	54352.1	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118090.66 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	4748.98	22.69	2.245	0.30( 0.22)	0.74	1987.7	120.00
2	4749.01	22.70	2.245	0.30( 0.22)	0.74	1987.8	110.00
3	4924.79	29.55	1.893	0.30( 0.23)	0.75	2657.7	100.00
4	5014.05	32.03	1.821	0.30( 0.23)	0.76	2882.7	150.00

5	5294.16	41.70	1.580	0.30 ( 0.23)	0.78	3733.9	31100.00
6	5832.35	55.60	1.338	0.30 ( 0.24)	0.79	5240.8	13210.00
7	5845.64	56.11	1.333	0.30 ( 0.24)	0.79	5292.7	13200.00
8	5834.42	57.31	1.320	0.30 ( 0.24)	0.79	5382.5	13100.00
9	5488.06	81.38	1.146	0.30 ( 0.24)	0.79	6620.7	13000.00
10	5426.05	83.68	1.131	0.30 ( 0.24)	0.79	6640.5	13010.00

LONGEST FLOWPATH FROM NODE 13010.00 TO NODE 13308.00 = 48763.78 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	30661.14	22.04	2.287	0.30 ( 0.24)	0.81	6371.8	50400.00
2	30955.55	22.69	2.245	0.30 ( 0.24)	0.81	6624.5	120.00
3	30955.80	22.70	2.245	0.30 ( 0.24)	0.81	6624.7	110.00
4	33810.29	29.55	1.893	0.30 ( 0.25)	0.82	9358.5	100.00
5	34470.53	31.09	1.845	0.30 ( 0.25)	0.82	9964.6	50300.00
6	34783.50	32.03	1.821	0.30 ( 0.25)	0.83	10364.9	150.00
7	36803.50	38.19	1.663	0.30 ( 0.25)	0.84	12987.7	12730.00
8	37533.76	41.70	1.580	0.30 ( 0.26)	0.85	14579.1	31100.00
9	37638.31	42.18	1.570	0.30 ( 0.26)	0.85	14806.5	40200.00
10	38445.42	46.00	1.487	0.30 ( 0.26)	0.86	16786.7	390.00
11	40402.90	55.28	1.342	0.30 ( 0.27)	0.88	21530.5	40100.00
12	40507.27	55.60	1.338	0.30 ( 0.27)	0.88	21691.2	13210.00
13	40665.50	56.11	1.333	0.30 ( 0.27)	0.89	21941.6	13200.00
14	40996.25	57.31	1.320	0.30 ( 0.27)	0.89	22499.7	13100.00
15	42765.82	63.84	1.264	0.30 ( 0.27)	0.90	25387.2	11801.00
16	45304.78	73.25	1.201	0.30 ( 0.27)	0.91	30167.2	11530.00
17	47271.48	81.38	1.146	0.30 ( 0.28)	0.92	35378.1	13000.00
18	47346.32	81.71	1.144	0.30 ( 0.28)	0.92	35573.4	11910.00
19	47856.45	83.68	1.131	0.30 ( 0.28)	0.92	36871.4	13010.00
20	49107.71	88.77	1.096	0.30 ( 0.28)	0.93	40190.9	11330.00
21	49891.21	95.08	1.065	0.30 ( 0.28)	0.94	44621.9	11130.00
22	49474.07	102.68	1.030	0.30 ( 0.28)	0.94	48615.9	12330.00
23	48975.83	109.33	1.000	0.30 ( 0.28)	0.94	51959.0	12400.00
24	48114.43	118.01	0.960	0.30 ( 0.28)	0.95	55327.8	12201.00
25	47527.14	121.99	0.946	0.30 ( 0.28)	0.95	56412.5	12111.00
26	46742.99	127.37	0.932	0.30 ( 0.28)	0.95	57782.0	12101.10
27	46116.45	131.40	0.921	0.30 ( 0.28)	0.95	58631.0	10400.00
28	44386.77	139.46	0.900	0.30 ( 0.28)	0.95	59946.2	12010.00
29	42957.31	145.37	0.885	0.30 ( 0.28)	0.95	60259.9	10210.00
30	38966.33	171.51	0.817	0.30 ( 0.28)	0.95	60992.6	10100.00

TOTAL AREA (ACRES) = 60992.6

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 49891.21 Tc (MIN.) = 95.082  
EFFECTIVE AREA (ACRES) = 44621.89 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.88  
TOTAL AREA (ACRES) = 60992.6  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13308.00 = 118090.66 FEET.

=====  
END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 60992.6 TC (MIN.) = 95.08  
EFFECTIVE AREA (ACRES) = 44621.89 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.935  
PEAK FLOW RATE (CFS) = 49891.21

\*\* PEAK FLOW RATE TABLE \*\*

STREAM	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	--------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	30661.14	22.04	2.287	0.30 ( 0.24)	0.81	6371.8 50400.00
2	30955.55	22.69	2.245	0.30 ( 0.24)	0.81	6624.5 120.00
3	30955.80	22.70	2.245	0.30 ( 0.24)	0.81	6624.7 110.00
4	33810.29	29.55	1.893	0.30 ( 0.25)	0.82	9358.5 100.00
5	34470.53	31.09	1.845	0.30 ( 0.25)	0.82	9964.6 50300.00
6	34783.50	32.03	1.821	0.30 ( 0.25)	0.83	10364.9 150.00
7	36803.50	38.19	1.663	0.30 ( 0.25)	0.84	12987.7 12730.00
8	37533.76	41.70	1.580	0.30 ( 0.26)	0.85	14579.1 31100.00
9	37638.31	42.18	1.570	0.30 ( 0.26)	0.85	14806.5 40200.00
10	38445.42	46.00	1.487	0.30 ( 0.26)	0.86	16786.7 390.00
11	40402.90	55.28	1.342	0.30 ( 0.27)	0.88	21530.5 40100.00
12	40507.27	55.60	1.338	0.30 ( 0.27)	0.88	21691.2 13210.00
13	40665.50	56.11	1.333	0.30 ( 0.27)	0.89	21941.6 13200.00
14	40996.25	57.31	1.320	0.30 ( 0.27)	0.89	22499.7 13100.00
15	42765.82	63.84	1.264	0.30 ( 0.27)	0.90	25387.2 11801.00
16	45304.78	73.25	1.201	0.30 ( 0.27)	0.91	30167.2 11530.00
17	47271.48	81.38	1.146	0.30 ( 0.28)	0.92	35378.1 13000.00
18	47346.32	81.71	1.144	0.30 ( 0.28)	0.92	35573.4 11910.00
19	47856.45	83.68	1.131	0.30 ( 0.28)	0.92	36871.4 13010.00
20	49107.71	88.77	1.096	0.30 ( 0.28)	0.93	40190.9 11330.00
21	49891.21	95.08	1.065	0.30 ( 0.28)	0.94	44621.9 11130.00
22	49474.07	102.68	1.030	0.30 ( 0.28)	0.94	48615.9 12330.00
23	48975.83	109.33	1.000	0.30 ( 0.28)	0.94	51959.0 12400.00
24	48114.43	118.01	0.960	0.30 ( 0.28)	0.95	55327.8 12201.00
25	47527.14	121.99	0.946	0.30 ( 0.28)	0.95	56412.5 12111.00
26	46742.99	127.37	0.932	0.30 ( 0.28)	0.95	57782.0 12101.10
27	46116.45	131.40	0.921	0.30 ( 0.28)	0.95	58631.0 10400.00
28	44386.77	139.46	0.900	0.30 ( 0.28)	0.95	59946.2 12010.00
29	42957.31	145.37	0.885	0.30 ( 0.28)	0.95	60259.9 10210.00
30	38966.33	171.51	0.817	0.30 ( 0.28)	0.95	60992.6 10100.00

=====  
END OF RATIONAL METHOD ANALYSIS  
=====



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S34- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 100-YR RM EV APRIL 2019 CCHI \*  
\*\*\*\*\*

FILE NAME: RI00EV34.DAT  
TIME/DATE OF STUDY: 08:52 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 100.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.847
- 2) 10.00; 3.775
- 3) 15.00; 2.924
- 4) 20.00; 2.413
- 5) 25.00; 2.092
- 6) 30.00; 1.869
- 7) 40.00; 1.613
- 8) 50.00; 1.397
- 9) 60.00; 1.287
- 10) 90.00; 1.084
- 11) 120.00; 0.947
- 12) 180.00; 0.791
- 13) 360.00; 0.584
- 14) 1200.00; 0.255

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI00EV33.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	30955.80	22.70	0.30 ( 0.24)	0.81	6624.7	110.00
2	34783.50	32.03	0.30 ( 0.25)	0.83	10364.9	150.00
3	36803.50	38.19	0.30 ( 0.25)	0.84	12987.7	12730.00
4	37638.31	42.18	0.30 ( 0.26)	0.85	14806.5	40200.00
5	38445.42	46.00	0.30 ( 0.26)	0.86	16786.7	390.00
6	40996.25	57.31	0.30 ( 0.27)	0.89	22499.7	13100.00
7	42765.82	63.84	0.30 ( 0.27)	0.90	25387.2	11801.00
8	45304.78	73.25	0.30 ( 0.27)	0.91	30167.2	11530.00
9	47856.45	83.68	0.30 ( 0.28)	0.92	36871.4	13010.00
10	49107.71	88.77	0.30 ( 0.28)	0.93	40190.9	11330.00
11	49891.21	95.08	0.30 ( 0.28)	0.94	44621.9	11130.00
12	49474.07	102.68	0.30 ( 0.28)	0.94	48615.9	12330.00
13	48975.83	109.33	0.30 ( 0.28)	0.94	51959.0	12400.00
14	48114.43	118.01	0.30 ( 0.28)	0.95	55327.8	12201.00
15	47527.14	121.99	0.30 ( 0.28)	0.95	56412.5	12111.00
16	46742.99	127.37	0.30 ( 0.28)	0.95	57782.0	12101.10
17	46116.45	131.40	0.30 ( 0.28)	0.95	58631.0	10400.00
18	44386.77	139.46	0.30 ( 0.28)	0.95	59946.2	12010.00
19	42957.31	145.37	0.30 ( 0.28)	0.95	60259.9	10210.00
20	38966.33	171.51	0.30 ( 0.28)	0.95	60992.6	10100.00
TOTAL AREA (ACRES) =						60992.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13308.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	30955.80	22.70	0.30 ( 0.24)	0.81	6624.7	110.00
2	34783.50	32.03	0.30 ( 0.25)	0.83	10364.9	150.00
3	36803.50	38.19	0.30 ( 0.25)	0.84	12987.7	12730.00
4	37638.31	42.18	0.30 ( 0.26)	0.85	14806.5	40200.00
5	38445.42	46.00	0.30 ( 0.26)	0.86	16786.7	390.00
6	40996.25	57.31	0.30 ( 0.27)	0.89	22499.7	13100.00
7	42765.82	63.84	0.30 ( 0.27)	0.90	25387.2	11801.00
8	45304.78	73.25	0.30 ( 0.27)	0.91	30167.2	11530.00
9	47856.45	83.68	0.30 ( 0.28)	0.92	36871.4	13010.00
10	49107.71	88.77	0.30 ( 0.28)	0.93	40190.9	11330.00
11	49891.21	95.08	0.30 ( 0.28)	0.94	44621.9	11130.00
12	49474.07	102.68	0.30 ( 0.28)	0.94	48615.9	12330.00
13	48975.83	109.33	0.30 ( 0.28)	0.94	51959.0	12400.00

14	48114.43	118.01	0.30	( 0.28)	0.95	55327.8	12201.00
15	47527.14	121.99	0.30	( 0.28)	0.95	56412.5	12111.00
16	46742.99	127.37	0.30	( 0.28)	0.95	57782.0	12101.10
17	46116.45	131.40	0.30	( 0.28)	0.95	58631.0	10400.00
18	44386.77	139.46	0.30	( 0.28)	0.95	59946.2	12010.00
19	42957.31	145.37	0.30	( 0.28)	0.95	60259.9	10210.00
20	38966.33	171.51	0.30	( 0.28)	0.95	60992.6	10100.00

TOTAL AREA (ACRES) = 60992.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13308.00 TO NODE 13402.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 215.00 DOWNSTREAM(FEET) = 209.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 623.02 CHANNEL SLOPE = 0.0096  
GIVEN CHANNEL BASE(FEET) = 200.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 10.02  
CHANNEL FLOW THRU SUBAREA(CFS) = 49891.21  
FLOW VELOCITY(FEET/SEC.) = 19.91 FLOW DEPTH(FEET) = 10.02  
TRAVEL TIME(MIN.) = 0.52 Tc(MIN.) = 95.60  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118713.68 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	30955.80	23.31	2.201	0.30( 0.24)	0.81	6624.7	110.00
2	34783.50	32.62	1.802	0.30( 0.25)	0.83	10364.9	150.00
3	36803.50	38.77	1.645	0.30( 0.25)	0.84	12987.7	12730.00
4	37638.31	42.75	1.554	0.30( 0.26)	0.85	14806.5	40200.00
5	38445.42	46.57	1.471	0.30( 0.26)	0.86	16786.7	390.00
6	40996.25	57.86	1.310	0.30( 0.27)	0.89	22499.7	13100.00
7	42765.82	64.39	1.257	0.30( 0.27)	0.90	25387.2	11801.00
8	45304.78	73.79	1.194	0.30( 0.27)	0.91	30167.2	11530.00
9	47856.45	84.20	1.123	0.30( 0.28)	0.92	36871.4	13010.00
10	49107.71	89.29	1.089	0.30( 0.28)	0.93	40190.9	11330.00
11	49891.21	95.60	1.058	0.30( 0.28)	0.94	44621.9	11130.00
12	49474.07	103.20	1.024	0.30( 0.28)	0.94	48615.9	12330.00
13	48975.83	109.85	0.993	0.30( 0.28)	0.94	51959.0	12400.00
14	48114.43	118.54	0.954	0.30( 0.28)	0.95	55327.8	12201.00
15	47527.14	122.51	0.940	0.30( 0.28)	0.95	56412.5	12111.00
16	46742.99	127.90	0.926	0.30( 0.28)	0.95	57782.0	12101.10
17	46116.45	131.94	0.916	0.30( 0.28)	0.95	58631.0	10400.00
18	44386.77	140.01	0.895	0.30( 0.28)	0.95	59946.2	12010.00
19	42957.31	145.91	0.880	0.30( 0.28)	0.95	60259.9	10210.00
20	38966.33	172.07	0.812	0.30( 0.28)	0.95	60992.6	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 49891.21 Tc(MIN.) = 95.60  
AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.94 EFFECTIVE AREA(ACRES) = 44621.89

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13402.00 TO NODE 13402.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610505Y.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	299.75	19.45	0.30( 0.30)	0.99	153.2	50500.00

TOTAL AREA(ACRES) = 153.2

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13402.00 TO NODE 13402.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	30955.80	23.31	2.201	0.30( 0.24)	0.81	6624.7	110.00
2	34783.50	32.62	1.802	0.30( 0.25)	0.83	10364.9	150.00
3	36803.50	38.77	1.645	0.30( 0.25)	0.84	12987.7	12730.00
4	37638.31	42.75	1.554	0.30( 0.26)	0.85	14806.5	40200.00
5	38445.42	46.57	1.471	0.30( 0.26)	0.86	16786.7	390.00
6	40996.25	57.86	1.310	0.30( 0.27)	0.89	22499.7	13100.00
7	42765.82	64.39	1.257	0.30( 0.27)	0.90	25387.2	11801.00
8	45304.78	73.79	1.194	0.30( 0.27)	0.91	30167.2	11530.00
9	47856.45	84.20	1.123	0.30( 0.28)	0.92	36871.4	13010.00
10	49107.71	89.29	1.089	0.30( 0.28)	0.93	40190.9	11330.00
11	49891.21	95.60	1.058	0.30( 0.28)	0.94	44621.9	11130.00
12	49474.07	103.20	1.024	0.30( 0.28)	0.94	48615.9	12330.00
13	48975.83	109.85	0.993	0.30( 0.28)	0.94	51959.0	12400.00
14	48114.43	118.54	0.954	0.30( 0.28)	0.95	55327.8	12201.00
15	47527.14	122.51	0.940	0.30( 0.28)	0.95	56412.5	12111.00
16	46742.99	127.90	0.926	0.30( 0.28)	0.95	57782.0	12101.10
17	46116.45	131.94	0.916	0.30( 0.28)	0.95	58631.0	10400.00
18	44386.77	140.01	0.895	0.30( 0.28)	0.95	59946.2	12010.00
19	42957.31	145.91	0.880	0.30( 0.28)	0.95	60259.9	10210.00
20	38966.33	172.07	0.812	0.30( 0.28)	0.95	60992.6	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118713.68 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	299.75	19.45	2.469	0.30( 0.30)	0.99	153.2	50500.00

LONGEST FLOWPATH FROM NODE 50500.00 TO NODE 13402.00 = 6247.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	29675.71	19.45	2.469	0.30( 0.24)	0.81	5681.3	50500.00
2	31218.50	23.31	2.201	0.30( 0.24)	0.81	6777.9	110.00
3	34991.21	32.62	1.802	0.30( 0.25)	0.83	10518.1	150.00
4	36989.50	38.77	1.645	0.30( 0.25)	0.84	13140.9	12730.00
5	37811.75	42.75	1.554	0.30( 0.26)	0.85	14959.7	40200.00
6	38607.49	46.57	1.471	0.30( 0.26)	0.86	16939.9	390.00
7	41136.18	57.86	1.310	0.30( 0.27)	0.89	22652.9	13100.00
8	42898.42	64.39	1.257	0.30( 0.27)	0.90	25540.4	11801.00
9	45428.61	73.79	1.194	0.30( 0.27)	0.91	30320.4	11530.00
10	47970.55	84.20	1.123	0.30( 0.28)	0.92	37024.6	13010.00
11	49217.06	89.29	1.089	0.30( 0.28)	0.93	40344.1	11330.00

12 49996.38 95.60 1.058 0.30( 0.28) 0.94 44775.1 11130.00  
 13 49574.45 103.20 1.024 0.30( 0.28) 0.94 48769.0 12330.00  
 14 49072.02 109.85 0.993 0.30( 0.28) 0.94 52112.2 12400.00  
 15 48205.14 118.54 0.954 0.30( 0.28) 0.95 55481.0 12201.00  
 16 47616.04 122.51 0.940 0.30( 0.28) 0.95 56565.7 12111.00  
 17 46829.96 127.90 0.926 0.30( 0.28) 0.95 57935.1 12101.10  
 18 46201.97 131.94 0.916 0.30( 0.28) 0.95 58784.2 10400.00  
 19 44469.39 140.01 0.895 0.30( 0.28) 0.95 60099.4 12010.00  
 20 43037.82 145.91 0.880 0.30( 0.28) 0.95 60413.1 10210.00  
 21 39037.46 172.07 0.812 0.30( 0.28) 0.95 61145.8 10100.00  
 TOTAL AREA (ACRES) = 61145.8

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 49996.38 Tc (MIN.) = 95.604  
 EFFECTIVE AREA (ACRES) = 44775.07 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 61145.8  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13402.00 = 118713.68 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13402.00 TO NODE 13404.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 209.00 DOWNSTREAM (FEET) = 207.00  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 395.35 CHANNEL SLOPE = 0.0051  
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 12.01  
 CHANNEL FLOW THRU SUBAREA (CFS) = 49996.38  
 FLOW VELOCITY (FEET/SEC.) = 16.01 FLOW DEPTH (FEET) = 12.01  
 TRAVEL TIME (MIN.) = 0.41 Tc (MIN.) = 96.02  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119109.03 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	29675.71	19.93	2.420	0.30( 0.24)	0.81	5681.3	50500.00
2	31218.50	23.78	2.170	0.30( 0.24)	0.81	6777.9	110.00
3	34991.21	33.08	1.790	0.30( 0.25)	0.83	10518.1	150.00
4	36989.50	39.22	1.633	0.30( 0.25)	0.84	13140.9	12730.00
5	37811.75	43.20	1.544	0.30( 0.26)	0.85	14959.7	40200.00
6	38607.49	47.02	1.461	0.30( 0.26)	0.86	16939.9	390.00
7	41136.18	58.30	1.306	0.30( 0.27)	0.89	22652.9	13100.00
8	42898.42	64.82	1.254	0.30( 0.27)	0.90	25540.4	11801.00
9	45428.61	74.21	1.191	0.30( 0.27)	0.91	30320.4	11530.00
10	47970.55	84.62	1.120	0.30( 0.28)	0.92	37024.6	13010.00
11	49217.06	89.71	1.086	0.30( 0.28)	0.93	40344.1	11330.00
12	49996.38	96.02	1.057	0.30( 0.28)	0.94	44775.1	11130.00
13	49574.45	103.61	1.022	0.30( 0.28)	0.94	48769.0	12330.00
14	49072.02	110.27	0.991	0.30( 0.28)	0.94	52112.2	12400.00
15	48205.14	118.96	0.952	0.30( 0.28)	0.95	55481.0	12201.00
16	47616.04	122.93	0.939	0.30( 0.28)	0.95	56565.7	12111.00
17	46829.96	128.32	0.925	0.30( 0.28)	0.95	57935.1	12101.10
18	46201.97	132.36	0.915	0.30( 0.28)	0.95	58784.2	10400.00
19	44469.39	140.43	0.894	0.30( 0.28)	0.95	60099.4	12010.00
20	43037.82	146.34	0.879	0.30( 0.28)	0.95	60413.1	10210.00

21 39037.46 172.52 0.810 0.30( 0.28) 0.95 61145.8 10100.00  
 NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE (CFS) = 49996.38 Tc (MIN.) = 96.02  
 AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.94 EFFECTIVE AREA (ACRES) = 44775.07

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13404.00 TO NODE 13404.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610506Y.DNA  
 MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	107.09	17.21	0.30( 0.30)	1.00	49.6	50600.00
TOTAL AREA (ACRES) = 49.6						

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13404.00 TO NODE 13404.00 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	29675.71	19.93	2.420	0.30( 0.24)	0.81	5681.3	50500.00
2	31218.50	23.78	2.170	0.30( 0.24)	0.81	6777.9	110.00
3	34991.21	33.08	1.790	0.30( 0.25)	0.83	10518.1	150.00
4	36989.50	39.22	1.633	0.30( 0.25)	0.84	13140.9	12730.00
5	37811.75	43.20	1.544	0.30( 0.26)	0.85	14959.7	40200.00
6	38607.49	47.02	1.461	0.30( 0.26)	0.86	16939.9	390.00
7	41136.18	58.30	1.306	0.30( 0.27)	0.89	22652.9	13100.00
8	42898.42	64.82	1.254	0.30( 0.27)	0.90	25540.4	11801.00
9	45428.61	74.21	1.191	0.30( 0.27)	0.91	30320.4	11530.00
10	47970.55	84.62	1.120	0.30( 0.28)	0.92	37024.6	13010.00
11	49217.06	89.71	1.086	0.30( 0.28)	0.93	40344.1	11330.00
12	49996.38	96.02	1.057	0.30( 0.28)	0.94	44775.1	11130.00
13	49574.45	103.61	1.022	0.30( 0.28)	0.94	48769.0	12330.00
14	49072.02	110.27	0.991	0.30( 0.28)	0.94	52112.2	12400.00
15	48205.14	118.96	0.952	0.30( 0.28)	0.95	55481.0	12201.00
16	47616.04	122.93	0.939	0.30( 0.28)	0.95	56565.7	12111.00
17	46829.96	128.32	0.925	0.30( 0.28)	0.95	57935.1	12101.10
18	46201.97	132.36	0.915	0.30( 0.28)	0.95	58784.2	10400.00
19	44469.39	140.43	0.894	0.30( 0.28)	0.95	60099.4	12010.00
20	43037.82	146.34	0.879	0.30( 0.28)	0.95	60413.1	10210.00
21	39037.46	172.52	0.810	0.30( 0.28)	0.95	61145.8	10100.00
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119109.03 FEET.							

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	107.09	17.21	2.698	0.30( 0.30)	1.00	49.6	50600.00
LONGEST FLOWPATH FROM NODE 50600.00 TO NODE 13404.00 = 4378.00 FEET.							

\*\* PEAK FLOW RATE TABLE \*\*

STREAM	Q	Tc	Intensity	Fp (Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	---------	----	----	-----------



NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	29004.59	17.21	2.698	0.30 ( 0.24)	0.82	4953.4 50600.00
2	29770.35	19.93	2.420	0.30 ( 0.24)	0.82	5730.9 50500.00
3	31302.00	23.78	2.170	0.30 ( 0.24)	0.81	6827.5 110.00
4	35057.75	33.08	1.790	0.30 ( 0.25)	0.83	10567.7 150.00
5	37049.01	39.22	1.633	0.30 ( 0.25)	0.84	13190.5 12730.00
6	37867.29	43.20	1.544	0.30 ( 0.26)	0.85	15009.3 40200.00
7	38659.34	47.02	1.461	0.30 ( 0.26)	0.86	16989.4 390.00
8	41181.09	58.30	1.306	0.30 ( 0.27)	0.89	22702.5 13100.00
9	42941.03	64.82	1.254	0.30 ( 0.27)	0.90	25590.0 11801.00
10	45468.38	74.21	1.191	0.30 ( 0.27)	0.91	30370.0 11530.00
11	48007.18	84.62	1.120	0.30 ( 0.28)	0.92	37074.2 13010.00
12	49252.16	89.71	1.086	0.30 ( 0.28)	0.93	40393.7 11330.00
13	50030.16	96.02	1.057	0.30 ( 0.28)	0.94	44824.7 11130.00
14	49606.68	103.61	1.022	0.30 ( 0.28)	0.94	48818.6 12330.00
15	49102.89	110.27	0.991	0.30 ( 0.28)	0.94	52161.8 12400.00
16	48234.25	118.96	0.952	0.30 ( 0.28)	0.95	55530.6 12201.00
17	47644.59	122.93	0.939	0.30 ( 0.28)	0.95	56615.3 12111.00
18	46857.88	128.32	0.925	0.30 ( 0.28)	0.95	57984.7 12101.10
19	46229.43	132.36	0.915	0.30 ( 0.28)	0.95	58833.8 10400.00
20	44495.91	140.43	0.894	0.30 ( 0.28)	0.95	60148.9 12010.00
21	43063.65	146.34	0.879	0.30 ( 0.28)	0.95	60462.7 10210.00
22	39060.25	172.52	0.810	0.30 ( 0.28)	0.95	61195.4 10100.00

TOTAL AREA (ACRES) = 61195.4

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 50030.16 Tc (MIN.) = 96.015  
EFFECTIVE AREA (ACRES) = 44824.66 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA (ACRES) = 61195.4  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13404.00 = 119109.03 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13404.00 TO NODE 13406.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 207.00 DOWNSTREAM (FEET) = 195.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1601.97 CHANNEL SLOPE = 0.0075  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 10.77  
CHANNEL FLOW THRU SUBAREA (CFS) = 50030.16  
FLOW VELOCITY (FEET/SEC.) = 18.30 FLOW DEPTH (FEET) = 10.77  
TRAVEL TIME (MIN.) = 1.46 Tc (MIN.) = 97.47  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13406.00 = 120711.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	29004.59	18.95	2.520	0.30 ( 0.24)	0.82	4953.4	50600.00
2	29770.35	21.66	2.306	0.30 ( 0.24)	0.82	5730.9	50500.00
3	31302.00	25.48	2.070	0.30 ( 0.24)	0.81	6827.5	110.00
4	35057.75	34.71	1.748	0.30 ( 0.25)	0.83	10567.7	150.00
5	37049.01	40.83	1.595	0.30 ( 0.25)	0.84	13190.5	12730.00
6	37867.29	44.80	1.509	0.30 ( 0.26)	0.85	15009.3	40200.00
7	38659.34	48.60	1.427	0.30 ( 0.26)	0.86	16989.4	390.00

8	41181.09	59.86	1.289	0.30 ( 0.27)	0.89	22702.5	13100.00
9	42941.03	66.35	1.244	0.30 ( 0.27)	0.90	25590.0	11801.00
10	45468.38	75.71	1.181	0.30 ( 0.27)	0.91	30370.0	11530.00
11	48007.18	86.10	1.110	0.30 ( 0.28)	0.92	37074.2	13010.00
12	49252.16	91.17	1.079	0.30 ( 0.28)	0.93	40393.7	11330.00
13	50030.16	97.47	1.050	0.30 ( 0.28)	0.94	44824.7	11130.00
14	49606.68	105.08	1.015	0.30 ( 0.28)	0.94	48818.6	12330.00
15	49102.89	111.73	0.985	0.30 ( 0.28)	0.94	52161.8	12400.00
16	48234.25	120.43	0.946	0.30 ( 0.28)	0.95	55530.6	12201.00
17	47644.59	124.41	0.936	0.30 ( 0.28)	0.95	56615.3	12111.00
18	46857.88	129.81	0.921	0.30 ( 0.28)	0.95	57984.7	12101.10
19	46229.43	133.86	0.911	0.30 ( 0.28)	0.95	58833.8	10400.00
20	44495.91	141.95	0.890	0.30 ( 0.28)	0.95	60148.9	12010.00
21	43063.65	147.88	0.875	0.30 ( 0.28)	0.95	60462.7	10210.00
22	39060.25	174.10	0.806	0.30 ( 0.28)	0.95	61195.4	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 50030.16 Tc (MIN.) = 97.47  
AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.94 EFFECTIVE AREA (ACRES) = 44824.66

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 97.47  
\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.050  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "GRASS"	B	0.20	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	4.00	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	2.00	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	9.70	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	2.60	0.30	1.000	66
AGRICULTURAL POOR COVER "ROW CROPS, STRAIGHT ROW"	B	1.80	0.30	1.000	81

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 20.30 SUBAREA RUNOFF (CFS) = 13.70  
EFFECTIVE AREA (ACRES) = 44844.96 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94  
TOTAL AREA (ACRES) = 61215.7 PEAK FLOW RATE (CFS) = 50030.16  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc (MIN.) = 97.47  
\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.050  
SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "ROW CROPS, STRAIGHT ROW"	B	3.50	0.30	1.000	81
NATURAL FAIR COVER "WOODLAND, GRASS"	B	7.20	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND, GRASS"	B	5.80	0.30	1.000	65
NATURAL FAIR COVER "WOODLAND, GRASS"	B	0.10	0.30	1.000	65

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 16.60 SUBAREA RUNOFF (CFS) = 11.20  
EFFECTIVE AREA (ACRES) = 44861.57 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94  
TOTAL AREA (ACRES) = 61232.3 PEAK FLOW RATE (CFS) = 50030.16  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 2P00EVBB.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	842.59	9.80	0.30 ( 0.11)	0.38	246.8	429.00
2	890.71	11.26	0.30 ( 0.11)	0.38	283.5	425.00
3	905.71	11.71	0.30 ( 0.11)	0.38	294.8	400.00
4	943.25	13.11	0.30 ( 0.11)	0.38	330.1	300.00
5	1001.68	18.01	0.30 ( 0.11)	0.38	440.3	210.00
6	980.97	20.12	0.30 ( 0.11)	0.38	468.0	410.00
7	972.01	21.00	0.30 ( 0.11)	0.38	479.3	200.00
8	969.62	21.61	0.30 ( 0.11)	0.38	486.7	230.00
9	947.95	22.69	0.30 ( 0.11)	0.37	491.2	220.50

TOTAL AREA (ACRES) = 491.2

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13406.00 TO NODE 13406.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	29004.59	18.95	2.520	0.30 ( 0.25)	0.82	4990.3	50600.00
2	29770.35	21.66	2.306	0.30 ( 0.25)	0.82	5767.8	50500.00
3	31302.00	25.48	2.070	0.30 ( 0.24)	0.82	6864.4	110.00
4	35057.75	34.71	1.748	0.30 ( 0.25)	0.83	10604.6	150.00
5	37049.01	40.83	1.595	0.30 ( 0.25)	0.84	13227.4	12730.00

6	37867.29	44.80	1.509	0.30 ( 0.26)	0.85	15046.2	40200.00
7	38659.34	48.60	1.427	0.30 ( 0.26)	0.86	17026.3	390.00
8	41181.09	59.86	1.289	0.30 ( 0.27)	0.89	22739.4	13100.00
9	42941.03	66.35	1.244	0.30 ( 0.27)	0.90	25626.9	11801.00
10	45468.38	75.71	1.181	0.30 ( 0.27)	0.91	30406.9	11530.00
11	48007.18	86.10	1.110	0.30 ( 0.28)	0.92	37111.1	13010.00
12	49252.16	91.17	1.079	0.30 ( 0.28)	0.93	40430.6	11330.00
13	50030.16	97.47	1.050	0.30 ( 0.28)	0.94	44861.6	11130.00
14	49606.68	105.08	1.015	0.30 ( 0.28)	0.94	48855.5	12330.00
15	49102.89	111.73	0.985	0.30 ( 0.28)	0.94	52198.7	12400.00
16	48234.25	120.43	0.946	0.30 ( 0.28)	0.95	55567.5	12201.00
17	47644.59	124.41	0.936	0.30 ( 0.28)	0.95	56652.2	12111.00
18	46857.88	129.81	0.921	0.30 ( 0.28)	0.95	58021.6	12101.10
19	46229.43	133.86	0.911	0.30 ( 0.28)	0.95	58870.7	10400.00
20	44495.91	141.95	0.890	0.30 ( 0.28)	0.95	60185.9	12010.00
21	43063.65	147.88	0.875	0.30 ( 0.28)	0.95	60499.6	10210.00
22	39060.25	174.10	0.806	0.30 ( 0.28)	0.95	61232.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13406.00 = 120711.00 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	842.59	9.80	3.858	0.30 ( 0.11)	0.38	246.8	429.00
2	890.71	11.26	3.560	0.30 ( 0.11)	0.38	283.5	425.00
3	905.71	11.71	3.484	0.30 ( 0.11)	0.38	294.8	400.00
4	943.25	13.11	3.246	0.30 ( 0.11)	0.38	330.1	300.00
5	1001.68	18.01	2.616	0.30 ( 0.11)	0.38	440.3	210.00
6	980.97	20.12	2.406	0.30 ( 0.11)	0.38	468.0	410.00
7	972.01	21.00	2.349	0.30 ( 0.11)	0.38	479.3	200.00
8	969.62	21.61	2.309	0.30 ( 0.11)	0.38	486.7	230.00
9	947.95	22.69	2.240	0.30 ( 0.11)	0.37	491.2	220.50

LONGEST FLOWPATH FROM NODE 230.00 TO NODE 13406.00 = 11903.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24660.94	9.80	3.858	0.30 ( 0.23)	0.78	2827.3	429.00
2	26009.44	11.26	3.560	0.30 ( 0.23)	0.78	3249.9	425.00
3	26421.96	11.71	3.484	0.30 ( 0.23)	0.78	3378.9	400.00
4	27406.53	13.11	3.246	0.30 ( 0.23)	0.78	3782.3	300.00
5	29731.09	18.01	2.616	0.30 ( 0.23)	0.78	5182.8	210.00
6	29997.02	18.95	2.520	0.30 ( 0.23)	0.78	5443.0	50600.00
7	30314.42	20.12	2.406	0.30 ( 0.23)	0.78	5792.1	410.00
8	30554.56	21.00	2.349	0.30 ( 0.23)	0.78	6056.4	200.00
9	30725.55	21.61	2.309	0.30 ( 0.23)	0.78	6239.8	230.00
10	30738.95	21.66	2.306	0.30 ( 0.23)	0.78	6254.7	50500.00
11	31130.89	22.69	2.240	0.30 ( 0.24)	0.78	6554.4	220.50
12	32174.34	25.48	2.070	0.30 ( 0.24)	0.79	7355.6	110.00
13	35786.60	34.71	1.748	0.30 ( 0.24)	0.81	11095.8	150.00
14	37709.59	40.83	1.595	0.30 ( 0.25)	0.83	13718.6	12730.00
15	38489.66	44.80	1.509	0.30 ( 0.25)	0.84	15537.4	40200.00
16	39245.10	48.60	1.427	0.30 ( 0.25)	0.85	17517.5	390.00
17	41705.11	59.86	1.289	0.30 ( 0.26)	0.88	23230.6	13100.00
18	43445.19	66.35	1.244	0.30 ( 0.27)	0.89	26118.1	11801.00
19	45944.32	75.71	1.181	0.30 ( 0.27)	0.90	30898.1	11530.00
20	48451.81	86.10	1.110	0.30 ( 0.27)	0.92	37602.3	13010.00
21	49682.64	91.17	1.079	0.30 ( 0.28)	0.92	40921.8	11330.00
22	50447.82	97.47	1.050	0.30 ( 0.28)	0.93	45352.8	11130.00

23	50008.88	105.08	1.015	0.30	( 0.28)	0.93	49346.7	12330.00
24	49491.54	111.73	0.985	0.30	( 0.28)	0.94	52689.9	12400.00
25	48605.57	120.43	0.946	0.30	( 0.28)	0.94	56058.7	12201.00
26	48011.30	124.41	0.936	0.30	( 0.28)	0.94	57143.4	12111.00
27	47218.35	129.81	0.921	0.30	( 0.28)	0.94	58512.8	12101.10
28	46585.21	133.86	0.911	0.30	( 0.28)	0.94	59361.9	10400.00
29	44842.32	141.95	0.890	0.30	( 0.28)	0.94	60677.1	12010.00
30	43403.19	147.88	0.875	0.30	( 0.28)	0.94	60990.8	10210.00
31	39369.41	174.10	0.806	0.30	( 0.28)	0.95	61723.5	10100.00

TOTAL AREA (ACRES) = 61723.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 50447.82 Tc (MIN.) = 97.474  
EFFECTIVE AREA (ACRES) = 45352.77 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.81  
TOTAL AREA (ACRES) = 61723.5  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13406.00 = 120711.00 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13406.00 TO NODE 13408.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 195.00 DOWNSTREAM (FEET) = 182.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 2458.36 CHANNEL SLOPE = 0.0053  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 11.92  
\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.038

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.00	0.30	1.000	-
USER-DEFINED	-	3.30	0.30	1.000	-
USER-DEFINED	-	0.40	0.30	0.100	-
USER-DEFINED	-	1.40	0.30	1.000	-
USER-DEFINED	-	0.30	0.30	0.100	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.949

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 50452.03

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 16.30

AVERAGE FLOW DEPTH (FEET) = 11.92 TRAVEL TIME (MIN.) = 2.51

Tc (MIN.) = 99.99

SUBAREA AREA (ACRES) = 12.40 SUBAREA RUNOFF (CFS) = 8.41

EFFECTIVE AREA (ACRES) = 45365.16 AREA-AVERAGED Fm (INCH/HR) = 0.28

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA (ACRES) = 61735.9 PEAK FLOW RATE (CFS) = 50447.82

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT (FEET) = 11.92

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 11.92 FLOW VELOCITY (FEET/SEC.) = 16.30

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123169.36 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24660.94	12.97	3.270	0.30 ( 0.23)	0.78	2839.7	429.00
2	26009.44	14.38	3.029	0.30 ( 0.23)	0.78	3262.3	425.00
3	26421.96	14.81	2.956	0.30 ( 0.23)	0.78	3391.3	400.00
4	27406.53	16.17	2.804	0.30 ( 0.23)	0.78	3794.7	300.00
5	29731.09	20.99	2.349	0.30 ( 0.23)	0.78	5195.2	210.00
6	29997.02	21.92	2.290	0.30 ( 0.23)	0.78	5455.4	50600.00
7	30314.42	23.08	2.215	0.30 ( 0.23)	0.78	5804.5	410.00
8	30554.56	23.95	2.159	0.30 ( 0.23)	0.78	6068.8	200.00
9	30725.55	24.56	2.120	0.30 ( 0.23)	0.78	6252.2	230.00
10	30738.95	24.61	2.117	0.30 ( 0.23)	0.78	6267.1	50500.00
11	31130.89	25.63	2.064	0.30 ( 0.24)	0.78	6566.8	220.50
12	32174.34	28.39	1.941	0.30 ( 0.24)	0.79	7368.0	110.00
13	35786.60	37.52	1.676	0.30 ( 0.24)	0.81	11108.2	150.00
14	37709.59	43.59	1.536	0.30 ( 0.25)	0.83	13731.0	12730.00
15	38489.66	47.54	1.450	0.30 ( 0.25)	0.84	15549.8	40200.00
16	39245.10	51.33	1.382	0.30 ( 0.25)	0.85	17529.9	390.00
17	41705.11	62.53	1.270	0.30 ( 0.26)	0.88	23243.0	13100.00
18	43445.19	68.99	1.226	0.30 ( 0.27)	0.89	26130.5	11801.00
19	45944.32	78.30	1.163	0.30 ( 0.27)	0.90	30910.5	11530.00
20	48451.81	88.64	1.093	0.30 ( 0.27)	0.92	37614.7	13010.00
21	49682.64	93.70	1.067	0.30 ( 0.28)	0.92	40934.2	11330.00
22	50447.82	99.99	1.038	0.30 ( 0.28)	0.93	45365.2	11130.00
23	50008.88	107.60	1.004	0.30 ( 0.28)	0.93	49359.1	12330.00
24	49491.54	114.26	0.973	0.30 ( 0.28)	0.94	52702.3	12400.00
25	48605.57	122.98	0.939	0.30 ( 0.28)	0.94	56071.1	12201.00
26	48011.30	126.97	0.929	0.30 ( 0.28)	0.94	57155.8	12111.00
27	47218.35	132.38	0.915	0.30 ( 0.28)	0.94	58525.2	12101.10
28	46585.21	136.44	0.904	0.30 ( 0.28)	0.94	59374.3	10400.00
29	44842.32	144.56	0.883	0.30 ( 0.28)	0.94	60689.4	12010.00
30	43403.19	150.51	0.868	0.30 ( 0.28)	0.94	61003.2	10210.00
31	39369.41	176.82	0.799	0.30 ( 0.28)	0.95	61735.9	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 50447.82 Tc (MIN.) = 99.99  
AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA (ACRES) = 45365.16

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0610507Y.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	459.67	19.60	0.30 ( 0.30)	0.99	236.8	50700.00
TOTAL AREA (ACRES) =		236.8				

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13408.00 TO NODE 13408.00 IS CODE = 11

=====  
 >>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<  
 =====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	24660.94	12.97	3.270	0.30 ( 0.23)	0.78	2839.7	429.00
2	26009.44	14.38	3.029	0.30 ( 0.23)	0.78	3262.3	425.00
3	26421.96	14.81	2.956	0.30 ( 0.23)	0.78	3391.3	400.00
4	27406.53	16.17	2.804	0.30 ( 0.23)	0.78	3794.7	300.00
5	29731.09	20.99	2.349	0.30 ( 0.23)	0.78	5195.2	210.00
6	29997.02	21.92	2.290	0.30 ( 0.23)	0.78	5455.4	50600.00
7	30314.42	23.08	2.215	0.30 ( 0.23)	0.78	5804.5	410.00
8	30554.56	23.95	2.159	0.30 ( 0.23)	0.78	6068.8	200.00
9	30725.55	24.56	2.120	0.30 ( 0.23)	0.78	6252.2	230.00
10	30738.95	24.61	2.117	0.30 ( 0.23)	0.78	6267.1	50500.00
11	31130.89	25.63	2.064	0.30 ( 0.24)	0.78	6566.8	220.50
12	32174.34	28.39	1.941	0.30 ( 0.24)	0.79	7368.0	110.00
13	35786.60	37.52	1.676	0.30 ( 0.24)	0.81	11108.2	150.00
14	37709.59	43.59	1.536	0.30 ( 0.25)	0.83	13731.0	12730.00
15	38489.66	47.54	1.450	0.30 ( 0.25)	0.84	15549.8	40200.00
16	39245.10	51.33	1.382	0.30 ( 0.25)	0.85	17529.9	390.00
17	41705.11	62.53	1.270	0.30 ( 0.26)	0.88	23243.0	13100.00
18	43445.19	68.99	1.226	0.30 ( 0.27)	0.89	26130.5	11801.00
19	45944.32	78.30	1.163	0.30 ( 0.27)	0.90	30910.5	11530.00
20	48451.81	88.64	1.093	0.30 ( 0.27)	0.92	37614.7	13010.00
21	49682.64	93.70	1.067	0.30 ( 0.28)	0.92	40934.2	11330.00
22	50447.82	99.99	1.038	0.30 ( 0.28)	0.93	45365.2	11130.00
23	50008.88	107.60	1.004	0.30 ( 0.28)	0.93	49359.1	12330.00
24	49491.54	114.26	0.973	0.30 ( 0.28)	0.94	52702.3	12400.00
25	48605.57	122.98	0.939	0.30 ( 0.28)	0.94	56071.1	12201.00
26	48011.30	126.97	0.929	0.30 ( 0.28)	0.94	57155.8	12111.00
27	47218.35	132.38	0.915	0.30 ( 0.28)	0.94	58525.2	12101.10
28	46585.21	136.44	0.904	0.30 ( 0.28)	0.94	59374.3	10400.00
29	44842.32	144.56	0.883	0.30 ( 0.28)	0.94	60689.4	12010.00
30	43403.19	150.51	0.868	0.30 ( 0.28)	0.94	61003.2	10210.00
31	39369.41	176.82	0.799	0.30 ( 0.28)	0.95	61735.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123169.36 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	459.67	19.60	2.454	0.30 ( 0.30)	0.99	236.8	50700.00

LONGEST FLOWPATH FROM NODE 50700.00 TO NODE 13408.00 = 7903.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25080.19	12.97	3.270	0.30 ( 0.24)	0.79	2996.4	429.00
2	26436.73	14.38	3.029	0.30 ( 0.24)	0.79	3436.1	425.00
3	26850.23	14.81	2.956	0.30 ( 0.24)	0.79	3570.3	400.00
4	27847.43	16.17	2.804	0.30 ( 0.24)	0.79	3990.1	300.00
5	29519.17	19.60	2.454	0.30 ( 0.24)	0.79	5027.4	50700.00
6	30168.45	20.99	2.349	0.30 ( 0.24)	0.79	5432.0	210.00
7	30421.64	21.92	2.290	0.30 ( 0.24)	0.79	5692.2	50600.00
8	30723.23	23.08	2.215	0.30 ( 0.24)	0.79	6041.3	410.00
9	30951.37	23.95	2.159	0.30 ( 0.24)	0.79	6305.6	200.00

10	31114.05	24.56	2.120	0.30 ( 0.24)	0.79	6489.0	230.00
11	31126.73	24.61	2.117	0.30 ( 0.24)	0.79	6503.8	50500.00
12	31507.40	25.63	2.064	0.30 ( 0.24)	0.79	6803.5	220.50
13	32524.60	28.39	1.941	0.30 ( 0.24)	0.79	7604.8	110.00
14	36080.52	37.52	1.676	0.30 ( 0.24)	0.81	11345.0	150.00
15	37973.46	43.59	1.536	0.30 ( 0.25)	0.83	13967.7	12730.00
16	38735.33	47.54	1.450	0.30 ( 0.25)	0.84	15786.5	40200.00
17	39476.32	51.33	1.382	0.30 ( 0.26)	0.85	17766.7	390.00
18	41912.35	62.53	1.270	0.30 ( 0.26)	0.88	23479.8	13100.00
19	43643.11	68.99	1.226	0.30 ( 0.27)	0.89	26367.3	11801.00
20	46128.80	78.30	1.163	0.30 ( 0.27)	0.90	31147.3	11530.00
21	48621.38	88.64	1.093	0.30 ( 0.27)	0.92	37851.5	13010.00
22	49846.66	93.70	1.067	0.30 ( 0.28)	0.92	41171.0	11330.00
23	50605.71	99.99	1.038	0.30 ( 0.28)	0.93	45601.9	11130.00
24	50159.36	107.60	1.004	0.30 ( 0.28)	0.93	49595.9	12330.00
25	49635.53	114.26	0.973	0.30 ( 0.28)	0.94	52939.1	12400.00
26	48742.33	122.98	0.939	0.30 ( 0.28)	0.94	56307.9	12201.00
27	48145.85	126.97	0.929	0.30 ( 0.28)	0.94	57392.6	12111.00
28	47349.89	132.38	0.915	0.30 ( 0.28)	0.94	58762.0	12101.10
29	46714.50	136.44	0.904	0.30 ( 0.28)	0.94	59611.1	10400.00
30	44967.11	144.56	0.883	0.30 ( 0.28)	0.94	60926.2	12010.00
31	43524.69	150.51	0.868	0.30 ( 0.28)	0.94	61239.9	10210.00
32	39476.33	176.82	0.799	0.30 ( 0.28)	0.95	61972.7	10100.00

TOTAL AREA (ACRES) = 61972.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 50605.71 Tc (MIN.) = 99.988  
 EFFECTIVE AREA (ACRES) = 45601.95 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA (ACRES) = 61972.7  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13408.00 = 123169.36 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13408.00 TO NODE 13410.00 IS CODE = 56  
 \*\*\*\*\*

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

=====  
 ELEVATION DATA: UPSTREAM (FEET) = 182.00 DOWNSTREAM (FEET) = 178.72  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 952.73 CHANNEL SLOPE = 0.0034  
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 13.45  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.033  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 0.40 0.30 1.000 -  
 USER-DEFINED - 2.90 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 50606.80  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 14.08  
 AVERAGE FLOW DEPTH (FEET) = 13.45 TRAVEL TIME (MIN.) = 1.13  
 Tc (MIN.) = 101.12  
 SUBAREA AREA (ACRES) = 3.30 SUBAREA RUNOFF (CFS) = 2.18  
 EFFECTIVE AREA (ACRES) = 45605.25 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 =====

TOTAL AREA (ACRES) = 61976.0 PEAK FLOW RATE (CFS) = 50605.71  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 13.45

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 13.45 FLOW VELOCITY (FEET/SEC.) = 14.08  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124122.09 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25080.19	14.38	3.029	0.30 ( 0.24)	0.79	2999.7	429.00
2	26436.73	15.77	2.845	0.30 ( 0.24)	0.79	3439.4	425.00
3	26850.23	16.19	2.802	0.30 ( 0.24)	0.79	3573.6	400.00
4	27847.43	17.54	2.665	0.30 ( 0.24)	0.79	3993.4	300.00
5	29519.17	20.94	2.353	0.30 ( 0.24)	0.79	5030.7	50700.00
6	30168.45	22.32	2.264	0.30 ( 0.24)	0.79	5435.3	210.00
7	30421.64	23.25	2.205	0.30 ( 0.24)	0.79	5695.5	50600.00
8	30723.23	24.40	2.131	0.30 ( 0.24)	0.79	6044.6	410.00
9	30951.37	25.27	2.080	0.30 ( 0.24)	0.79	6308.9	200.00
10	31114.05	25.88	2.053	0.30 ( 0.24)	0.79	6492.3	230.00
11	31126.73	25.93	2.051	0.30 ( 0.24)	0.79	6507.1	50500.00
12	31507.40	26.94	2.005	0.30 ( 0.24)	0.79	6806.8	220.50
13	32524.60	29.69	1.883	0.30 ( 0.24)	0.79	7608.1	110.00
14	36080.52	38.78	1.644	0.30 ( 0.24)	0.81	11348.3	150.00
15	37973.46	44.82	1.509	0.30 ( 0.25)	0.83	13971.0	12730.00
16	38735.33	48.77	1.424	0.30 ( 0.25)	0.84	15789.8	40200.00
17	39476.32	52.55	1.369	0.30 ( 0.26)	0.85	17770.0	390.00
18	41912.35	63.72	1.262	0.30 ( 0.26)	0.88	23483.1	13100.00
19	43643.11	70.17	1.218	0.30 ( 0.27)	0.89	26370.6	11801.00
20	46128.80	79.46	1.155	0.30 ( 0.27)	0.90	31150.6	11530.00
21	48621.38	89.79	1.085	0.30 ( 0.27)	0.92	37854.8	13010.00
22	49846.66	94.83	1.062	0.30 ( 0.28)	0.92	41174.3	11330.00
23	50605.71	101.12	1.033	0.30 ( 0.28)	0.93	45605.2	11130.00
24	50159.36	108.73	0.998	0.30 ( 0.28)	0.93	49599.2	12330.00
25	49635.53	115.40	0.968	0.30 ( 0.28)	0.94	52942.4	12400.00
26	48742.33	124.12	0.936	0.30 ( 0.28)	0.94	56311.2	12201.00
27	48145.85	128.11	0.926	0.30 ( 0.28)	0.94	57395.9	12111.00
28	47349.89	133.53	0.912	0.30 ( 0.28)	0.94	58765.3	12101.10
29	46714.50	137.59	0.901	0.30 ( 0.28)	0.94	59614.4	10400.00
30	44967.11	145.73	0.880	0.30 ( 0.28)	0.94	60929.5	12010.00
31	43524.69	151.69	0.865	0.30 ( 0.28)	0.94	61243.2	10210.00
32	39476.33	178.04	0.796	0.30 ( 0.28)	0.95	61976.0	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 50605.71 Tc (MIN.) = 101.12  
 AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA (ACRES) = 45605.25

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: R100EV36.DNA  
 MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2776.71	27.02	0.30 ( 0.27)	0.90	1487.3	110.00
2	2879.22	29.39	0.30 ( 0.27)	0.90	1661.9	100.00
3	2888.80	30.54	0.30 ( 0.27)	0.90	1737.8	100.00
4	2912.73	33.54	0.30 ( 0.27)	0.91	1918.1	130.00
5	3088.57	46.09	0.30 ( 0.28)	0.93	2647.7	20100.00
6	3029.31	51.27	0.30 ( 0.28)	0.93	2829.1	13600.00
7	2905.42	85.17	0.30 ( 0.28)	0.93	3796.8	13510.00
8	2757.25	93.58	0.30 ( 0.28)	0.93	3859.7	13500.00
TOTAL AREA (ACRES) = 3859.7						

\*\*\*\*\*

FLOW PROCESS FROM NODE 13410.00 TO NODE 13410.00 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	25080.19	14.38	3.029	0.30 ( 0.24)	0.79	2999.7	429.00
2	26436.73	15.77	2.845	0.30 ( 0.24)	0.79	3439.4	425.00
3	26850.23	16.19	2.802	0.30 ( 0.24)	0.79	3573.6	400.00
4	27847.43	17.54	2.665	0.30 ( 0.24)	0.79	3993.4	300.00
5	29519.17	20.94	2.353	0.30 ( 0.24)	0.79	5030.7	50700.00
6	30168.45	22.32	2.264	0.30 ( 0.24)	0.79	5435.3	210.00
7	30421.64	23.25	2.205	0.30 ( 0.24)	0.79	5695.5	50600.00
8	30723.23	24.40	2.131	0.30 ( 0.24)	0.79	6044.6	410.00
9	30951.37	25.27	2.080	0.30 ( 0.24)	0.79	6308.9	200.00
10	31114.05	25.88	2.053	0.30 ( 0.24)	0.79	6492.3	230.00
11	31126.73	25.93	2.051	0.30 ( 0.24)	0.79	6507.1	50500.00
12	31507.40	26.94	2.005	0.30 ( 0.24)	0.79	6806.8	220.50
13	32524.60	29.69	1.883	0.30 ( 0.24)	0.79	7608.1	110.00
14	36080.52	38.78	1.644	0.30 ( 0.24)	0.81	11348.3	150.00
15	37973.46	44.82	1.509	0.30 ( 0.25)	0.83	13971.0	12730.00
16	38735.33	48.77	1.424	0.30 ( 0.25)	0.84	15789.8	40200.00
17	39476.32	52.55	1.369	0.30 ( 0.26)	0.85	17770.0	390.00
18	41912.35	63.72	1.262	0.30 ( 0.26)	0.88	23483.1	13100.00
19	43643.11	70.17	1.218	0.30 ( 0.27)	0.89	26370.6	11801.00
20	46128.80	79.46	1.155	0.30 ( 0.27)	0.90	31150.6	11530.00
21	48621.38	89.79	1.085	0.30 ( 0.27)	0.92	37854.8	13010.00
22	49846.66	94.83	1.062	0.30 ( 0.28)	0.92	41174.3	11330.00
23	50605.71	101.12	1.033	0.30 ( 0.28)	0.93	45605.2	11130.00
24	50159.36	108.73	0.998	0.30 ( 0.28)	0.93	49599.2	12330.00
25	49635.53	115.40	0.968	0.30 ( 0.28)	0.94	52942.4	12400.00
26	48742.33	124.12	0.936	0.30 ( 0.28)	0.94	56311.2	12201.00
27	48145.85	128.11	0.926	0.30 ( 0.28)	0.94	57395.9	12111.00
28	47349.89	133.53	0.912	0.30 ( 0.28)	0.94	58765.3	12101.10
29	46714.50	137.59	0.901	0.30 ( 0.28)	0.94	59614.4	10400.00
30	44967.11	145.73	0.880	0.30 ( 0.28)	0.94	60929.5	12010.00
31	43524.69	151.69	0.865	0.30 ( 0.28)	0.94	61243.2	10210.00
32	39476.33	178.04	0.796	0.30 ( 0.28)	0.95	61976.0	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124122.09 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2776.71	27.02	2.002	0.30 ( 0.27)	0.90	1487.3	110.00
2	2879.22	29.39	1.896	0.30 ( 0.27)	0.90	1661.9	100.00
3	2888.80	30.54	1.855	0.30 ( 0.27)	0.90	1737.8	100.00
4	2912.73	33.54	1.778	0.30 ( 0.27)	0.91	1918.1	130.00
5	3088.57	46.09	1.482	0.30 ( 0.28)	0.93	2647.7	20100.00
6	3029.31	51.27	1.383	0.30 ( 0.28)	0.93	2829.1	13600.00
7	2905.42	85.17	1.117	0.30 ( 0.28)	0.93	3796.8	13510.00
8	2757.25	93.58	1.068	0.30 ( 0.28)	0.93	3859.7	13500.00

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13410.00 = 41710.10 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27435.26	14.38	3.029	0.30 ( 0.24)	0.81	3791.4	429.00
2	28846.88	15.77	2.845	0.30 ( 0.24)	0.81	4307.4	425.00
3	29283.45	16.19	2.802	0.30 ( 0.24)	0.81	4464.9	400.00
4	30339.67	17.54	2.665	0.30 ( 0.24)	0.81	4958.7	300.00
5	32107.01	20.94	2.353	0.30 ( 0.24)	0.81	6183.2	50700.00
6	32809.58	22.32	2.264	0.30 ( 0.24)	0.81	6663.9	210.00
7	33090.33	23.25	2.205	0.30 ( 0.24)	0.81	6975.2	50600.00
8	33417.04	24.40	2.131	0.30 ( 0.24)	0.81	7387.7	410.00
9	33665.46	25.27	2.080	0.30 ( 0.24)	0.81	7700.1	200.00
10	33851.69	25.88	2.053	0.30 ( 0.24)	0.81	7916.8	230.00
11	33866.28	25.93	2.051	0.30 ( 0.24)	0.81	7934.5	50500.00
12	34281.67	26.94	2.005	0.30 ( 0.24)	0.81	8289.8	220.50
13	34312.86	27.02	2.002	0.30 ( 0.24)	0.81	8316.8	110.00
14	35295.41	29.39	1.896	0.30 ( 0.24)	0.81	9184.6	100.00
15	35406.27	29.69	1.883	0.30 ( 0.24)	0.81	9289.3	110.00
16	35747.58	30.54	1.855	0.30 ( 0.24)	0.81	9697.3	100.00
17	36945.50	33.54	1.778	0.30 ( 0.25)	0.82	11112.5	130.00
18	39066.60	38.78	1.644	0.30 ( 0.25)	0.83	13570.8	150.00
19	41044.29	44.82	1.509	0.30 ( 0.25)	0.84	16545.1	12730.00
20	41306.49	46.09	1.482	0.30 ( 0.25)	0.85	17202.4	20100.00
21	41793.24	48.77	1.424	0.30 ( 0.26)	0.85	18531.4	40200.00
22	42254.35	51.27	1.383	0.30 ( 0.26)	0.86	19927.6	13600.00
23	42500.95	52.55	1.369	0.30 ( 0.26)	0.86	20635.7	390.00
24	44896.14	63.72	1.262	0.30 ( 0.27)	0.88	26667.7	13100.00
25	46603.35	70.17	1.218	0.30 ( 0.27)	0.89	29739.2	11801.00
26	49055.08	79.46	1.155	0.30 ( 0.27)	0.91	34784.5	11530.00
27	50412.26	85.17	1.117	0.30 ( 0.27)	0.91	38653.8	13510.00
28	51445.53	89.79	1.085	0.30 ( 0.28)	0.92	41686.1	13010.00
29	52301.32	93.58	1.068	0.30 ( 0.28)	0.92	44214.2	13500.00
30	52583.99	94.83	1.062	0.30 ( 0.28)	0.92	45033.9	11330.00
31	53242.57	101.12	1.033	0.30 ( 0.28)	0.93	49464.9	11130.00
32	52674.52	108.73	0.998	0.30 ( 0.28)	0.93	53458.9	12330.00
33	52044.04	115.40	0.968	0.30 ( 0.28)	0.94	56802.1	12400.00
34	51039.79	124.12	0.936	0.30 ( 0.28)	0.94	60170.9	12201.00
35	50406.94	128.11	0.926	0.30 ( 0.28)	0.94	61255.5	12111.00
36	49561.69	133.53	0.912	0.30 ( 0.28)	0.94	62625.0	12101.10
37	48889.32	137.59	0.901	0.30 ( 0.28)	0.94	63474.1	10400.00
38	47067.88	145.73	0.880	0.30 ( 0.28)	0.94	64789.2	12010.00
39	45571.15	151.69	0.865	0.30 ( 0.28)	0.94	65102.9	10210.00
40	41282.99	178.04	0.796	0.30 ( 0.28)	0.94	65835.7	10100.00

TOTAL AREA (ACRES) = 65835.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 53242.57 Tc (MIN.) = 101.115  
EFFECTIVE AREA (ACRES) = 49464.93 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.86  
TOTAL AREA (ACRES) = 65835.7  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13410.00 = 124122.09 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13410.00 TO NODE 13412.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 178.72 DOWNSTREAM (FEET) = 176.93  
CHANNEL LENGTH THRU SUBAREA (FEET) = 169.78 CHANNEL SLOPE = 0.0105  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 10.13  
CHANNEL FLOW THRU SUBAREA (CFS) = 53242.57  
FLOW VELOCITY (FEET/SEC.) = 20.97 FLOW DEPTH (FEET) = 10.13  
TRAVEL TIME (MIN.) = 0.13 Tc (MIN.) = 101.25  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124291.87 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27435.26	14.55	3.001	0.30 ( 0.24)	0.81	3791.4	429.00
2	28846.88	15.93	2.829	0.30 ( 0.24)	0.81	4307.4	425.00
3	29283.45	16.36	2.785	0.30 ( 0.24)	0.81	4464.9	400.00
4	30339.67	17.70	2.648	0.30 ( 0.24)	0.81	4958.7	300.00
5	32107.01	21.10	2.343	0.30 ( 0.24)	0.81	6183.2	50700.00
6	32809.58	22.48	2.254	0.30 ( 0.24)	0.81	6663.9	210.00
7	33090.33	23.40	2.194	0.30 ( 0.24)	0.81	6975.2	50600.00
8	33417.04	24.56	2.121	0.30 ( 0.24)	0.81	7387.7	410.00
9	33665.46	25.43	2.073	0.30 ( 0.24)	0.81	7700.1	200.00
10	33851.69	26.03	2.046	0.30 ( 0.24)	0.81	7916.8	230.00
11	33866.28	26.08	2.044	0.30 ( 0.24)	0.81	7934.5	50500.00
12	34281.67	27.10	1.999	0.30 ( 0.24)	0.81	8289.8	220.50
13	34312.86	27.17	1.995	0.30 ( 0.24)	0.81	8316.8	110.00
14	35295.41	29.55	1.889	0.30 ( 0.24)	0.81	9184.6	100.00
15	35406.27	29.84	1.876	0.30 ( 0.24)	0.81	9289.3	110.00
16	35747.58	30.70	1.851	0.30 ( 0.24)	0.81	9697.3	100.00
17	36945.50	33.69	1.774	0.30 ( 0.25)	0.82	11112.5	130.00
18	39066.60	38.92	1.641	0.30 ( 0.25)	0.83	13570.8	150.00
19	41044.29	44.97	1.506	0.30 ( 0.25)	0.84	16545.1	12730.00
20	41306.49	46.23	1.478	0.30 ( 0.25)	0.85	17202.4	20100.00
21	41793.24	48.91	1.420	0.30 ( 0.26)	0.85	18531.4	40200.00
22	42254.35	51.41	1.381	0.30 ( 0.26)	0.86	19927.6	13600.00
23	42500.95	52.69	1.367	0.30 ( 0.26)	0.86	20635.7	390.00
24	44896.14	63.87	1.261	0.30 ( 0.27)	0.88	26667.7	13100.00
25	46603.35	70.31	1.217	0.30 ( 0.27)	0.89	29739.2	11801.00
26	49055.08	79.60	1.154	0.30 ( 0.27)	0.91	34784.5	11530.00
27	50412.26	85.31	1.116	0.30 ( 0.27)	0.91	38653.8	13510.00
28	51445.53	89.92	1.085	0.30 ( 0.28)	0.92	41686.1	13010.00
29	52301.32	93.72	1.067	0.30 ( 0.28)	0.92	44214.2	13500.00
30	52583.99	94.97	1.061	0.30 ( 0.28)	0.92	45033.9	11330.00

31	53242.57	101.25	1.033	0.30 ( 0.28)	0.93	49464.9	11130.00
32	52674.52	108.86	0.998	0.30 ( 0.28)	0.93	53458.9	12330.00
33	52044.04	115.53	0.967	0.30 ( 0.28)	0.94	56802.1	12400.00
34	51039.79	124.26	0.936	0.30 ( 0.28)	0.94	60170.9	12201.00
35	50406.94	128.25	0.926	0.30 ( 0.28)	0.94	61255.5	12111.00
36	49561.69	133.67	0.911	0.30 ( 0.28)	0.94	62625.0	12101.10
37	48889.32	137.73	0.901	0.30 ( 0.28)	0.94	63474.1	10400.00
38	47067.88	145.87	0.880	0.30 ( 0.28)	0.94	64789.2	12010.00
39	45571.15	151.84	0.864	0.30 ( 0.28)	0.94	65102.9	10210.00
40	41282.99	178.19	0.796	0.30 ( 0.28)	0.94	65835.7	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 53242.57 Tc(MIN.) = 101.25  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 49464.93

\*\*\*\*\*

FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506101B.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	683.96	36.50	0.30 ( 0.30)	0.98	591.0	10100.00
TOTAL AREA(ACRES) =		591.0				

\*\*\*\*\*

FLOW PROCESS FROM NODE 13412.00 TO NODE 13412.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27435.26	14.55	3.001	0.30 ( 0.24)	0.81	3791.4	429.00
2	28846.88	15.93	2.829	0.30 ( 0.24)	0.81	4307.4	425.00
3	29283.45	16.36	2.785	0.30 ( 0.24)	0.81	4464.9	400.00
4	30339.67	17.70	2.648	0.30 ( 0.24)	0.81	4958.7	300.00
5	32107.01	21.10	2.343	0.30 ( 0.24)	0.81	6183.2	50700.00
6	32809.58	22.48	2.254	0.30 ( 0.24)	0.81	6663.9	210.00
7	33090.33	23.40	2.194	0.30 ( 0.24)	0.81	6975.2	50600.00
8	33417.04	24.56	2.121	0.30 ( 0.24)	0.81	7387.7	410.00
9	33665.46	25.43	2.073	0.30 ( 0.24)	0.81	7700.1	200.00
10	33851.69	26.03	2.046	0.30 ( 0.24)	0.81	7916.8	230.00
11	33866.28	26.08	2.044	0.30 ( 0.24)	0.81	7934.5	50500.00
12	34281.67	27.10	1.999	0.30 ( 0.24)	0.81	8289.8	220.50
13	34312.86	27.17	1.995	0.30 ( 0.24)	0.81	8316.8	110.00
14	35295.41	29.55	1.889	0.30 ( 0.24)	0.81	9184.6	100.00
15	35406.27	29.84	1.876	0.30 ( 0.24)	0.81	9289.3	110.00
16	35747.58	30.70	1.851	0.30 ( 0.24)	0.81	9697.3	100.00

17	36945.50	33.69	1.774	0.30 ( 0.25)	0.82	11112.5	130.00
18	39066.60	38.92	1.641	0.30 ( 0.25)	0.83	13570.8	150.00
19	41044.29	44.97	1.506	0.30 ( 0.25)	0.84	16545.1	12730.00
20	41306.49	46.23	1.478	0.30 ( 0.25)	0.85	17202.4	20100.00
21	41793.24	48.91	1.420	0.30 ( 0.26)	0.85	18531.4	40200.00
22	42254.35	51.41	1.381	0.30 ( 0.26)	0.86	19927.6	13600.00
23	42500.95	52.69	1.367	0.30 ( 0.26)	0.86	20635.7	390.00
24	44896.14	63.87	1.261	0.30 ( 0.27)	0.88	26667.7	13100.00
25	46603.35	70.31	1.217	0.30 ( 0.27)	0.89	29739.2	11801.00
26	49055.08	79.60	1.154	0.30 ( 0.27)	0.91	34784.5	11530.00
27	50412.26	85.31	1.116	0.30 ( 0.27)	0.91	38653.8	13510.00
28	51445.53	89.92	1.085	0.30 ( 0.28)	0.92	41686.1	13010.00
29	52301.32	93.72	1.067	0.30 ( 0.28)	0.92	44214.2	13500.00
30	52583.99	94.97	1.061	0.30 ( 0.28)	0.92	45033.9	11330.00
31	53242.57	101.25	1.033	0.30 ( 0.28)	0.93	49464.9	11130.00
32	52674.52	108.86	0.998	0.30 ( 0.28)	0.93	53458.9	12330.00
33	52044.04	115.53	0.967	0.30 ( 0.28)	0.94	56802.1	12400.00
34	51039.79	124.26	0.936	0.30 ( 0.28)	0.94	60170.9	12201.00
35	50406.94	128.25	0.926	0.30 ( 0.28)	0.94	61255.5	12111.00
36	49561.69	133.67	0.911	0.30 ( 0.28)	0.94	62625.0	12101.10
37	48889.32	137.73	0.901	0.30 ( 0.28)	0.94	63474.1	10400.00
38	47067.88	145.87	0.880	0.30 ( 0.28)	0.94	64789.2	12010.00
39	45571.15	151.84	0.864	0.30 ( 0.28)	0.94	65102.9	10210.00
40	41282.99	178.19	0.796	0.30 ( 0.28)	0.94	65835.7	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124291.87 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	683.96	36.50	1.703	0.30 ( 0.30)	0.98	591.0	10100.00
LONGEST FLOWPATH FROM NODE		10100.00 TO NODE 13412.00 = 14677.00 FEET.					

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27959.31	14.55	3.001	0.30 ( 0.25)	0.82	4026.9	429.00
2	29384.27	15.93	2.829	0.30 ( 0.25)	0.82	4565.4	425.00
3	29825.69	16.36	2.785	0.30 ( 0.25)	0.82	4729.7	400.00
4	30894.10	17.70	2.648	0.30 ( 0.25)	0.82	5245.2	300.00
5	32682.06	21.10	2.343	0.30 ( 0.25)	0.82	6524.7	50700.00
6	33395.74	22.48	2.254	0.30 ( 0.25)	0.82	7027.8	210.00
7	33682.12	23.40	2.194	0.30 ( 0.25)	0.82	7354.1	50600.00
8	34013.78	24.56	2.121	0.30 ( 0.25)	0.82	7785.3	410.00
9	34267.29	25.43	2.073	0.30 ( 0.25)	0.82	8111.8	200.00
10	34458.48	26.03	2.046	0.30 ( 0.25)	0.82	8338.2	230.00
11	34473.47	26.08	2.044	0.30 ( 0.25)	0.82	8356.8	50500.00
12	34896.14	27.10	1.999	0.30 ( 0.25)	0.82	8728.5	220.50
13	34927.83	27.17	1.995	0.30 ( 0.25)	0.82	8756.7	110.00
14	35922.47	29.55	1.889	0.30 ( 0.25)	0.82	9663.0	100.00
15	36034.35	29.84	1.876	0.30 ( 0.25)	0.82	9772.5	110.00
16	36383.47	30.70	1.851	0.30 ( 0.25)	0.82	10194.3	100.00
17	37609.08	33.69	1.774	0.30 ( 0.25)	0.83	11658.0	130.00
18	38768.91	36.50	1.703	0.30 ( 0.25)	0.83	13024.1	10100.00
19	39720.44	38.92	1.641	0.30 ( 0.25)	0.84	14161.8	150.00
20	41632.60	44.97	1.506	0.30 ( 0.25)	0.85	17136.1	12730.00
21	41881.52	46.23	1.478	0.30 ( 0.26)	0.85	17793.4	20100.00
22	42340.15	48.91	1.420	0.30 ( 0.26)	0.86	19122.4	40200.00
23	42782.31	51.41	1.381	0.30 ( 0.26)	0.86	20518.6	13600.00

24	43022.05	52.69	1.367	0.30	( 0.26)	0.87	21226.7	390.00
25	45365.48	63.87	1.261	0.30	( 0.27)	0.89	27258.7	13100.00
26	47051.49	70.31	1.217	0.30	( 0.27)	0.90	30330.2	11801.00
27	49472.67	79.60	1.154	0.30	( 0.27)	0.91	35375.5	11530.00
28	50811.09	85.31	1.116	0.30	( 0.27)	0.91	39244.8	13510.00
29	51829.19	89.92	1.085	0.30	( 0.28)	0.92	42277.1	13010.00
30	52676.46	93.72	1.067	0.30	( 0.28)	0.92	44805.2	13500.00
31	52956.37	94.97	1.061	0.30	( 0.28)	0.92	45624.9	11330.00
32	53601.00	101.25	1.033	0.30	( 0.28)	0.93	50055.9	11130.00
33	53016.05	108.86	0.998	0.30	( 0.28)	0.94	54049.9	12330.00
34	52370.78	115.53	0.967	0.30	( 0.28)	0.94	57393.1	12400.00
35	51351.24	124.26	0.936	0.30	( 0.28)	0.94	60761.9	12201.00
36	50713.34	128.25	0.926	0.30	( 0.28)	0.94	61846.5	12111.00
37	49861.25	133.67	0.911	0.30	( 0.28)	0.94	63216.0	12101.10
38	49183.75	137.73	0.901	0.30	( 0.28)	0.94	64065.1	10400.00
39	47352.02	145.87	0.880	0.30	( 0.28)	0.94	65380.2	12010.00
40	45847.75	151.84	0.864	0.30	( 0.28)	0.94	65693.9	10210.00
41	41526.30	178.19	0.796	0.30	( 0.28)	0.95	66426.7	10100.00

TOTAL AREA (ACRES) = 66426.7

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 53601.00 Tc (MIN.) = 101.250  
EFFECTIVE AREA (ACRES) = 50055.93 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
TOTAL AREA (ACRES) = 66426.7  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13412.00 = 124291.87 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13412.00 TO NODE 13700.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 176.93 DOWNSTREAM (FEET) = 173.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 260.10 CHANNEL SLOPE = 0.0151  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 9.18  
CHANNEL FLOW THRU SUBAREA (CFS) = 53601.00  
FLOW VELOCITY (FEET/SEC.) = 23.74 FLOW DEPTH (FEET) = 9.18  
TRAVEL TIME (MIN.) = 0.18 Tc (MIN.) = 101.43  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124551.97 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27959.31	14.78	2.962	0.30 ( 0.25)	0.82	4026.9	429.00
2	29384.27	16.16	2.806	0.30 ( 0.25)	0.82	4565.4	425.00
3	29825.69	16.58	2.763	0.30 ( 0.25)	0.82	4729.7	400.00
4	30894.10	17.92	2.626	0.30 ( 0.25)	0.82	5245.2	300.00
5	32682.06	21.31	2.329	0.30 ( 0.25)	0.82	6524.7	50700.00
6	33395.74	22.69	2.240	0.30 ( 0.25)	0.82	7027.8	210.00
7	33682.12	23.62	2.181	0.30 ( 0.25)	0.82	7354.1	50600.00
8	34013.78	24.77	2.107	0.30 ( 0.25)	0.82	7785.3	410.00
9	34267.29	25.64	2.063	0.30 ( 0.25)	0.82	8111.8	200.00
10	34458.48	26.25	2.036	0.30 ( 0.25)	0.82	8338.2	230.00
11	34473.47	26.30	2.034	0.30 ( 0.25)	0.82	8356.8	50500.00
12	34896.14	27.31	1.989	0.30 ( 0.25)	0.82	8728.5	220.50

13	34927.83	27.38	1.986	0.30	( 0.25)	0.82	8756.7	110.00
14	35922.47	29.76	1.880	0.30	( 0.25)	0.82	9663.0	100.00
15	36034.35	30.05	1.868	0.30	( 0.25)	0.82	9772.5	110.00
16	36383.47	30.90	1.846	0.30	( 0.25)	0.82	10194.3	100.00
17	37609.08	33.90	1.769	0.30	( 0.25)	0.83	11658.0	130.00
18	38768.91	36.71	1.697	0.30	( 0.25)	0.83	13024.1	10100.00
19	39720.44	39.13	1.635	0.30	( 0.25)	0.84	14161.8	150.00
20	41632.60	45.17	1.501	0.30	( 0.25)	0.85	17136.1	12730.00
21	41881.52	46.43	1.474	0.30	( 0.26)	0.85	17793.4	20100.00
22	42340.15	49.11	1.416	0.30	( 0.26)	0.86	19122.4	40200.00
23	42782.31	51.61	1.379	0.30	( 0.26)	0.86	20518.6	13600.00
24	43022.05	52.89	1.365	0.30	( 0.26)	0.87	21226.7	390.00
25	45365.48	64.06	1.260	0.30	( 0.27)	0.89	27258.7	13100.00
26	47051.49	70.50	1.216	0.30	( 0.27)	0.90	30330.2	11801.00
27	49472.67	79.79	1.153	0.30	( 0.27)	0.91	35375.5	11530.00
28	50811.09	85.49	1.114	0.30	( 0.27)	0.91	39244.8	13510.00
29	51829.19	90.11	1.084	0.30	( 0.28)	0.92	42277.1	13010.00
30	52676.46	93.90	1.066	0.30	( 0.28)	0.92	44805.2	13500.00
31	52956.37	95.15	1.060	0.30	( 0.28)	0.92	45624.9	11330.00
32	53601.00	101.43	1.032	0.30	( 0.28)	0.93	50055.9	11130.00
33	53016.05	109.05	0.997	0.30	( 0.28)	0.94	54049.9	12330.00
34	52370.78	115.72	0.967	0.30	( 0.28)	0.94	57393.1	12400.00
35	51351.24	124.44	0.935	0.30	( 0.28)	0.94	60761.9	12201.00
36	50713.34	128.44	0.925	0.30	( 0.28)	0.94	61846.5	12111.00
37	49861.25	133.86	0.911	0.30	( 0.28)	0.94	63216.0	12101.10
38	49183.75	137.92	0.900	0.30	( 0.28)	0.94	64065.1	10400.00
39	47352.02	146.06	0.879	0.30	( 0.28)	0.94	65380.2	12010.00
40	45847.75	152.03	0.864	0.30	( 0.28)	0.94	65693.9	10210.00
41	41526.30	178.38	0.795	0.30	( 0.28)	0.95	66426.7	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 53601.00 Tc (MIN.) = 101.43  
AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA (ACRES) = 50055.93

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 2 <<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 2 <<<<

PEAK FLOWRATE TABLE FILE NAME: 0610508Y.DNA

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	246.57	20.47	0.30 ( 0.30)	0.99	131.3	50800.00
TOTAL AREA (ACRES) = 131.3						

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 2 WITH THE MAIN-STREAM MEMORY<<<<



\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27959.31	14.78	2.962	0.30 ( 0.25)	0.82	4026.9	429.00
2	29384.27	16.16	2.806	0.30 ( 0.25)	0.82	4565.4	425.00
3	29825.69	16.58	2.763	0.30 ( 0.25)	0.82	4729.7	400.00
4	30894.10	17.92	2.626	0.30 ( 0.25)	0.82	5245.2	300.00
5	32682.06	21.31	2.329	0.30 ( 0.25)	0.82	6524.7	50700.00
6	33395.74	22.69	2.240	0.30 ( 0.25)	0.82	7027.8	210.00
7	33682.12	23.62	2.181	0.30 ( 0.25)	0.82	7354.1	50600.00
8	34013.78	24.77	2.107	0.30 ( 0.25)	0.82	7785.3	410.00
9	34267.29	25.64	2.063	0.30 ( 0.25)	0.82	8111.8	200.00
10	34458.48	26.25	2.036	0.30 ( 0.25)	0.82	8338.2	230.00
11	34473.47	26.30	2.034	0.30 ( 0.25)	0.82	8356.8	50500.00
12	34896.14	27.31	1.989	0.30 ( 0.25)	0.82	8728.5	220.50
13	34927.83	27.38	1.986	0.30 ( 0.25)	0.82	8756.7	110.00
14	35922.47	29.76	1.880	0.30 ( 0.25)	0.82	9663.0	100.00
15	36034.35	30.05	1.868	0.30 ( 0.25)	0.82	9772.5	110.00
16	36383.47	30.90	1.846	0.30 ( 0.25)	0.82	10194.3	100.00
17	37609.08	33.90	1.769	0.30 ( 0.25)	0.83	11658.0	130.00
18	38768.91	36.71	1.697	0.30 ( 0.25)	0.83	13024.1	10100.00
19	39720.44	39.13	1.635	0.30 ( 0.25)	0.84	14161.8	150.00
20	41632.60	45.17	1.501	0.30 ( 0.25)	0.85	17136.1	12730.00
21	41881.52	46.43	1.474	0.30 ( 0.26)	0.85	17793.4	20100.00
22	42340.15	49.11	1.416	0.30 ( 0.26)	0.86	19122.4	40200.00
23	42782.31	51.61	1.379	0.30 ( 0.26)	0.86	20518.6	13600.00
24	43022.05	52.89	1.365	0.30 ( 0.26)	0.87	21226.7	390.00
25	45365.48	64.06	1.260	0.30 ( 0.27)	0.89	27258.7	13100.00
26	47051.49	70.50	1.216	0.30 ( 0.27)	0.90	30330.2	11801.00
27	49472.67	79.79	1.153	0.30 ( 0.27)	0.91	35375.5	11530.00
28	50811.09	85.49	1.114	0.30 ( 0.27)	0.91	39244.8	13510.00
29	51829.19	90.11	1.084	0.30 ( 0.28)	0.92	42277.1	13010.00
30	52676.46	93.90	1.066	0.30 ( 0.28)	0.92	44805.2	13500.00
31	52956.37	95.15	1.060	0.30 ( 0.28)	0.92	45624.9	11330.00
32	53601.00	101.43	1.032	0.30 ( 0.28)	0.93	50055.9	11130.00
33	53016.05	109.05	0.997	0.30 ( 0.28)	0.94	54049.9	12330.00
34	52370.78	115.72	0.967	0.30 ( 0.28)	0.94	57393.1	12400.00
35	51351.24	124.44	0.935	0.30 ( 0.28)	0.94	60761.9	12201.00
36	50713.34	128.44	0.925	0.30 ( 0.28)	0.94	61846.5	12111.00
37	49861.25	133.86	0.911	0.30 ( 0.28)	0.94	63216.0	12101.10
38	49183.75	137.92	0.900	0.30 ( 0.28)	0.94	64065.1	10400.00
39	47352.02	146.06	0.879	0.30 ( 0.28)	0.94	65380.2	12010.00
40	45847.75	152.03	0.864	0.30 ( 0.28)	0.94	65693.9	10210.00
41	41526.30	178.38	0.795	0.30 ( 0.28)	0.95	66426.7	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124551.97 FEET.

\*\* MEMORY BANK # 2 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	246.57	20.47	2.383	0.30 ( 0.30)	0.99	131.3	50800.00

LONGEST FLOWPATH FROM NODE 50800.00 TO NODE 13700.00 = 5946.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28186.71	14.78	2.962	0.30 ( 0.25)	0.83	4121.7	429.00
2	29618.35	16.16	2.806	0.30 ( 0.25)	0.83	4669.0	425.00
3	30061.74	16.58	2.763	0.30 ( 0.25)	0.83	4836.0	400.00

4	31135.07	17.92	2.626	0.30 ( 0.25)	0.83	5360.1	300.00
5	32484.36	20.47	2.383	0.30 ( 0.25)	0.82	6338.1	50800.00
6	32922.23	21.31	2.329	0.30 ( 0.25)	0.82	6656.0	50700.00
7	33625.44	22.69	2.240	0.30 ( 0.25)	0.82	7159.1	210.00
8	33904.80	23.62	2.181	0.30 ( 0.25)	0.82	7485.4	50600.00
9	34227.72	24.77	2.107	0.30 ( 0.25)	0.82	7916.5	410.00
10	34476.10	25.64	2.063	0.30 ( 0.25)	0.82	8243.0	200.00
11	34664.11	26.25	2.036	0.30 ( 0.25)	0.82	8469.5	230.00
12	34678.83	26.30	2.034	0.30 ( 0.25)	0.82	8488.0	50500.00
13	35096.17	27.31	1.989	0.30 ( 0.25)	0.82	8859.8	220.50
14	35127.45	27.38	1.986	0.30 ( 0.25)	0.82	8888.0	110.00
15	36109.58	29.76	1.880	0.30 ( 0.25)	0.82	9794.2	100.00
16	36220.03	30.05	1.868	0.30 ( 0.25)	0.82	9903.7	110.00
17	36566.57	30.90	1.846	0.30 ( 0.25)	0.82	10325.6	100.00
18	37783.12	33.90	1.769	0.30 ( 0.25)	0.83	11789.3	130.00
19	38934.45	36.71	1.697	0.30 ( 0.25)	0.83	13155.3	10100.00
20	39878.66	39.13	1.635	0.30 ( 0.25)	0.84	14293.0	150.00
21	41774.99	45.17	1.501	0.30 ( 0.25)	0.85	17267.4	12730.00
22	42020.68	46.43	1.474	0.30 ( 0.26)	0.85	17924.6	20100.00
23	42472.48	49.11	1.416	0.30 ( 0.26)	0.86	19253.7	40200.00
24	42910.27	51.61	1.379	0.30 ( 0.26)	0.86	20649.9	13600.00
25	43148.36	52.89	1.365	0.30 ( 0.26)	0.87	21358.0	390.00
26	45479.29	64.06	1.260	0.30 ( 0.27)	0.89	27390.0	13100.00
27	47160.15	70.50	1.216	0.30 ( 0.27)	0.90	30461.5	11801.00
28	49573.90	79.79	1.153	0.30 ( 0.27)	0.91	35506.8	11530.00
29	50907.76	85.49	1.114	0.30 ( 0.27)	0.91	39376.1	13510.00
30	51922.20	90.11	1.084	0.30 ( 0.28)	0.92	42408.3	13010.00
31	52767.43	93.90	1.066	0.30 ( 0.28)	0.92	44936.4	13500.00
32	53046.66	95.15	1.060	0.30 ( 0.28)	0.92	45756.2	11330.00
33	53687.90	101.43	1.032	0.30 ( 0.28)	0.93	50187.2	11130.00
34	53098.84	109.05	0.997	0.30 ( 0.28)	0.94	54181.2	12330.00
35	52449.96	115.72	0.967	0.30 ( 0.28)	0.94	57524.3	12400.00
36	51426.75	124.44	0.935	0.30 ( 0.28)	0.94	60893.1	12201.00
37	50787.63	128.44	0.925	0.30 ( 0.28)	0.94	61977.8	12111.00
38	49933.87	133.86	0.911	0.30 ( 0.28)	0.94	63347.3	12101.10
39	49255.12	137.92	0.900	0.30 ( 0.28)	0.94	64196.3	10400.00
40	47420.89	146.06	0.879	0.30 ( 0.28)	0.94	65511.5	12010.00
41	45914.79	152.03	0.864	0.30 ( 0.28)	0.94	65825.2	10210.00
42	41585.24	178.38	0.795	0.30 ( 0.28)	0.95	66557.9	10100.00

TOTAL AREA (ACRES) = 66557.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 53687.90 Tc (MIN.) = 101.433  
 EFFECTIVE AREA (ACRES) = 50187.20 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA (ACRES) = 66557.9  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13700.00 = 124551.97 FEET.

=====

END OF STUDY SUMMARY:

TOTAL AREA (ACRES) = 66557.9 TC (MIN.) = 101.43  
 EFFECTIVE AREA (ACRES) = 50187.20 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.931  
 PEAK FLOW RATE (CFS) = 53687.90

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28186.71	14.78	2.962	0.30 ( 0.25)	0.83	4121.7	429.00

2	29618.35	16.16	2.806	0.30	( 0.25)	0.83	4669.0	425.00
3	30061.74	16.58	2.763	0.30	( 0.25)	0.83	4836.0	400.00
4	31135.07	17.92	2.626	0.30	( 0.25)	0.83	5360.1	300.00
5	32484.36	20.47	2.383	0.30	( 0.25)	0.82	6338.1	50800.00
6	32922.23	21.31	2.329	0.30	( 0.25)	0.82	6656.0	50700.00
7	33625.44	22.69	2.240	0.30	( 0.25)	0.82	7159.1	210.00
8	33904.80	23.62	2.181	0.30	( 0.25)	0.82	7485.4	50600.00
9	34227.72	24.77	2.107	0.30	( 0.25)	0.82	7916.5	410.00
10	34476.10	25.64	2.063	0.30	( 0.25)	0.82	8243.0	200.00
11	34664.11	26.25	2.036	0.30	( 0.25)	0.82	8469.5	230.00
12	34678.83	26.30	2.034	0.30	( 0.25)	0.82	8488.0	50500.00
13	35096.17	27.31	1.989	0.30	( 0.25)	0.82	8859.8	220.50
14	35127.45	27.38	1.986	0.30	( 0.25)	0.82	8888.0	110.00
15	36109.58	29.76	1.880	0.30	( 0.25)	0.82	9794.2	100.00
16	36220.03	30.05	1.868	0.30	( 0.25)	0.82	9903.7	110.00
17	36566.57	30.90	1.846	0.30	( 0.25)	0.82	10325.6	100.00
18	37783.12	33.90	1.769	0.30	( 0.25)	0.83	11789.3	130.00
19	38934.45	36.71	1.697	0.30	( 0.25)	0.83	13155.3	10100.00
20	39878.66	39.13	1.635	0.30	( 0.25)	0.84	14293.0	150.00
21	41774.99	45.17	1.501	0.30	( 0.25)	0.85	17267.4	12730.00
22	42020.68	46.43	1.474	0.30	( 0.26)	0.85	17924.6	20100.00
23	42472.48	49.11	1.416	0.30	( 0.26)	0.86	19253.7	40200.00
24	42910.27	51.61	1.379	0.30	( 0.26)	0.86	20649.9	13600.00
25	43148.36	52.89	1.365	0.30	( 0.26)	0.87	21358.0	390.00
26	45479.29	64.06	1.260	0.30	( 0.27)	0.89	27390.0	13100.00
27	47160.15	70.50	1.216	0.30	( 0.27)	0.90	30461.5	11801.00
28	49573.90	79.79	1.153	0.30	( 0.27)	0.91	35506.8	11530.00
29	50907.76	85.49	1.114	0.30	( 0.27)	0.91	39376.1	13510.00
30	51922.20	90.11	1.084	0.30	( 0.28)	0.92	42408.3	13010.00
31	52767.43	93.90	1.066	0.30	( 0.28)	0.92	44936.4	13500.00
32	53046.66	95.15	1.060	0.30	( 0.28)	0.92	45756.2	11330.00
33	53687.90	101.43	1.032	0.30	( 0.28)	0.93	50187.2	11130.00
34	53098.84	109.05	0.997	0.30	( 0.28)	0.94	54181.2	12330.00
35	52449.96	115.72	0.967	0.30	( 0.28)	0.94	57524.3	12400.00
36	51426.75	124.44	0.935	0.30	( 0.28)	0.94	60893.1	12201.00
37	50787.63	128.44	0.925	0.30	( 0.28)	0.94	61977.8	12111.00
38	49933.87	133.86	0.911	0.30	( 0.28)	0.94	63347.3	12101.10
39	49255.12	137.92	0.900	0.30	( 0.28)	0.94	64196.3	10400.00
40	47420.89	146.06	0.879	0.30	( 0.28)	0.94	65511.5	12010.00
41	45914.79	152.03	0.864	0.30	( 0.28)	0.94	65825.2	10210.00
42	41585.24	178.38	0.795	0.30	( 0.28)	0.95	66557.9	10100.00

=====  
 =====  
 END OF RATIONAL METHOD ANALYSIS

\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S36- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 100-YR RM EV APRIL 2019 CCHI \*  
\*\*\*\*\*

FILE NAME: RI00EV36.DAT  
TIME/DATE OF STUDY: 08:52 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 100.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.786
- 2) 10.00; 3.745
- 3) 15.00; 2.905
- 4) 20.00; 2.401
- 5) 25.00; 2.083
- 6) 30.00; 1.861
- 7) 40.00; 1.606
- 8) 50.00; 1.392
- 9) 60.00; 1.279
- 10) 90.00; 1.075
- 11) 120.00; 0.938
- 12) 180.00; 0.782
- 13) 360.00; 0.577
- 14) 1200.00; 0.251

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL: IN- / OUT-/PARK- SIDE / SIDE/ WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH LIP HIKE (FT) (FT) (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00 0.0313 0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13600.00 TO NODE 13600.50 IS CODE = 21  
-----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 488.61  
ELEVATION DATA: UPSTREAM(FEET) = 872.12 DOWNSTREAM(FEET) = 744.80

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 10.995  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.578  
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "OPEN BRUSH"	-	3.39	0.30	1.000	69	11.00

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA RUNOFF(CFS) = 10.00  
TOTAL AREA(ACRES) = 3.39 PEAK FLOW RATE(CFS) = 10.00

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13600.50 TO NODE 13601.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 744.80 DOWNSTREAM(FEET) = 707.32  
CHANNEL LENGTH THRU SUBAREA(FEET) = 418.30 CHANNEL SLOPE = 0.0896  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.46  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.289  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.45	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 20.04  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.06  
AVERAGE FLOW DEPTH(FEET) = 0.45 TRAVEL TIME(MIN.) = 1.72  
Tc(MIN.) = 12.71  
SUBAREA AREA(ACRES) = 7.45 SUBAREA RUNOFF(CFS) = 20.04  
EFFECTIVE AREA(ACRES) = 10.84 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 10.8 PEAK FLOW RATE(CFS) = 29.16  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.56

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.56 FLOW VELOCITY(FEET/SEC.) = 4.67  
LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13601.00 = 906.91 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13601.00 TO NODE 13602.00 IS CODE = 56

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

-----  
ELEVATION DATA: UPSTREAM(FEET) = 707.32 DOWNSTREAM(FEET) = 657.12  
CHANNEL LENGTH THRU SUBAREA(FEET) = 777.60 CHANNEL SLOPE = 0.0646  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.03  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.899

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.32	0.30	1.000	-
USER-DEFINED	-	4.70	0.30	1.000	-
USER-DEFINED	-	25.05	0.30	1.000	-
USER-DEFINED	-	0.45	0.30	1.000	-
USER-DEFINED	-	0.44	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 65.46

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.53

AVERAGE FLOW DEPTH(FEET) = 0.99 TRAVEL TIME(MIN.) = 2.35

Tc(MIN.) = 15.06

SUBAREA AREA(ACRES) = 30.96 SUBAREA RUNOFF(CFS) = 72.42  
EFFECTIVE AREA(ACRES) = 41.80 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 41.8 PEAK FLOW RATE(CFS) = 97.78  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.25

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.25 FLOW VELOCITY(FEET/SEC.) = 6.28

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13602.00 = 1684.51 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13602.00 TO NODE 13603.00 IS CODE = 56

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

-----  
ELEVATION DATA: UPSTREAM(FEET) = 657.12 DOWNSTREAM(FEET) = 584.58  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1186.54 CHANNEL SLOPE = 0.0611  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.45  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.598

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.03	0.30	1.000	-
USER-DEFINED	-	2.51	0.30	1.000	-

USER-DEFINED - 1.52 0.30 1.000 -  
USER-DEFINED - 12.30 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 121.96

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.62

AVERAGE FLOW DEPTH(FEET) = 1.43 TRAVEL TIME(MIN.) = 2.99

Tc(MIN.) = 18.04

SUBAREA AREA(ACRES) = 23.36 SUBAREA RUNOFF(CFS) = 48.32  
EFFECTIVE AREA(ACRES) = 65.16 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 65.2 PEAK FLOW RATE(CFS) = 134.78  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.52

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.52 FLOW VELOCITY(FEET/SEC.) = 6.83

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13603.00 = 2871.05 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 56

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

-----  
ELEVATION DATA: UPSTREAM(FEET) = 584.58 DOWNSTREAM(FEET) = 544.91  
CHANNEL LENGTH THRU SUBAREA(FEET) = 860.98 CHANNEL SLOPE = 0.0461  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.78  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.384

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	10.22	0.30	1.000	-
USER-DEFINED	-	4.19	0.30	1.000	-
USER-DEFINED	-	0.07	0.30	1.000	-
USER-DEFINED	-	1.11	0.30	1.000	-
USER-DEFINED	-	5.56	0.30	1.000	-
USER-DEFINED	-	0.09	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 154.70

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.44

AVERAGE FLOW DEPTH(FEET) = 1.77 TRAVEL TIME(MIN.) = 2.23

Tc(MIN.) = 20.27

SUBAREA AREA(ACRES) = 21.24 SUBAREA RUNOFF(CFS) = 39.83  
EFFECTIVE AREA(ACRES) = 86.40 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 86.4 PEAK FLOW RATE(CFS) = 162.03  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.82

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 1.82 FLOW VELOCITY(FEET/SEC.) = 6.53

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13620.00 = 3732.03 FEET.

```

*****
FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 10
-----
>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<
=====
*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13522.00 IS CODE = 15.1
-----
>>>>DEFINE MEMORY BANK # 2 <<<<<
=====
PEAK FLOWRATE TABLE FILE NAME: S35X00.DNA
MEMORY BANK # 2 DEFINED AS FOLLOWS:
STREAM      Q      Tc      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR)    (ACRES)  NODE
  1      1365.67  51.63  0.30( 0.28) 0.95  1517.0  13510.00
  2      1241.97  59.58  0.30( 0.28) 0.94  1579.8  13500.00
TOTAL AREA(ACRES) =      1579.8

*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13522.00 IS CODE = 14.0
-----
>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<
=====
MAIN-STREAM MEMORY DEFINED AS FOLLOWS:
STREAM      Q      Tc      Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR)    (ACRES)  NODE
  1      1365.67  51.63  0.30( 0.28) 0.95  1517.0  13510.00
  2      1241.97  59.58  0.30( 0.28) 0.94  1579.8  13500.00
TOTAL AREA(ACRES) =      1579.8

*****
FLOW PROCESS FROM NODE 13522.00 TO NODE 13620.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<<
=====
ELEVATION DATA: UPSTREAM( FEET) = 632.19  DOWNSTREAM( FEET) = 544.91
CHANNEL LENGTH THRU SUBAREA( FEET) = 2062.96  CHANNEL SLOPE = 0.0423
GIVEN CHANNEL BASE( FEET) = 30.00  CHANNEL FREEBOARD( FEET) = 0.0
"Z" FACTOR = 3.000  MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT( FEET) = 2.76
* 100 YEAR RAINFALL INTENSITY( INCH/HR) = 1.344
SUBAREA LOSS RATE DATA( AMC II):
DEVELOPMENT TYPE/      SCS SOIL      AREA      Fp      Ap      SCS
LAND USE      GROUP      (ACRES)  (INCH/HR)  (DECIMAL)  CN
USER-DEFINED      -      17.68      0.30      1.000      -
USER-DEFINED      -      2.36      0.30      1.000      -
USER-DEFINED      -      0.60      0.30      1.000      -
USER-DEFINED      -      0.22      0.30      1.000      -
USER-DEFINED      -      2.22      0.30      1.000      -
USER-DEFINED      -      3.42      0.30      1.000      -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp( INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW( CFS) = 1378.12
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY( FEET/SEC.) = 13.05

```

```

AVERAGE FLOW DEPTH( FEET) = 2.76  TRAVEL TIME( MIN.) = 2.63
Tc( MIN.) = 54.26
SUBAREA AREA( ACRES) = 26.50  SUBAREA RUNOFF( CFS) = 24.90
EFFECTIVE AREA( ACRES) = 1543.46  AREA-AVERAGED Fm( INCH/HR) = 0.28
AREA-AVERAGED Fp( INCH/HR) = 0.30  AREA-AVERAGED Ap = 0.95
TOTAL AREA( ACRES) = 1606.3  PEAK FLOW RATE( CFS) = 1471.93
GIVEN CHANNEL BASE( FEET) = 30.00  CHANNEL FREEBOARD( FEET) = 0.0
"Z" FACTOR = 3.000  MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT( FEET) = 2.87

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH( FEET) = 2.87  FLOW VELOCITY( FEET/SEC.) = 13.31
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

** PEAK FLOW RATE TABLE **
STREAM      Q      Tc      Intensity  Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR)  (INCH/HR)  (ACRES)  NODE
  1      1471.93  54.26  1.344  0.30( 0.28) 0.95  1543.5  13510.00
  2      1416.51  62.30  1.263  0.30( 0.28) 0.95  1606.3  13500.00
NEW PEAK FLOW DATA ARE:
PEAK FLOW RATE( CFS) = 1471.93  Tc( MIN.) = 54.26
AREA-AVERAGED Fm( INCH/HR) = 0.28  AREA-AVERAGED Fp( INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.95  EFFECTIVE AREA( ACRES) = 1543.46

*****
FLOW PROCESS FROM NODE 13620.00 TO NODE 13620.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
=====
MAINLINE Tc( MIN.) = 54.26
* 100 YEAR RAINFALL INTENSITY( INCH/HR) = 1.344
SUBAREA LOSS RATE DATA( AMC II):
DEVELOPMENT TYPE/      SCS SOIL      AREA      Fp      Ap      SCS
LAND USE      GROUP      (ACRES)  (INCH/HR)  (DECIMAL)  CN
NATURAL FAIR COVER
"WOODLAND, GRASS"      B      1.44      0.30      1.000      65
NATURAL FAIR COVER
"WOODLAND, GRASS"      B      0.01      0.30      1.000      65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp( INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA( ACRES) = 1.45  SUBAREA RUNOFF( CFS) = 1.36
EFFECTIVE AREA( ACRES) = 1544.91  AREA-AVERAGED Fm( INCH/HR) = 0.28
AREA-AVERAGED Fp( INCH/HR) = 0.30  AREA-AVERAGED Ap = 0.95
TOTAL AREA( ACRES) = 1607.8  PEAK FLOW RATE( CFS) = 1473.29

*****
FLOW PROCESS FROM NODE 13603.00 TO NODE 13620.00 IS CODE = 11
-----
>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<
=====
** MAIN STREAM CONFLUENCE DATA **
STREAM      Q      Tc      Intensity  Fp(Fm)      Ap      Ae      HEADWATER
NUMBER      (CFS)    (MIN.)  (INCH/HR)  (INCH/HR)  (ACRES)  NODE
  1      1473.29  54.26  1.344  0.30( 0.28) 0.95  1544.9  13510.00
  2      1417.77  62.30  1.263  0.30( 0.28) 0.95  1607.8  13500.00
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

```

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	162.03	20.27	2.384	0.30 ( 0.30)	1.00	86.4	13600.00

LONGEST FLOWPATH FROM NODE 13600.00 TO NODE 13620.00 = 3732.03 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1252.61	20.27	2.384	0.30 ( 0.29)	0.95	663.6	13600.00
2	1554.47	54.26	1.344	0.30 ( 0.29)	0.95	1631.3	13510.00
3	1492.69	62.30	1.263	0.30 ( 0.28)	0.95	1694.2	13500.00

TOTAL AREA (ACRES) = 1694.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 1554.47 Tc(MIN.) = 54.262  
EFFECTIVE AREA(ACRES) = 1631.31 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95  
TOTAL AREA(ACRES) = 1694.2  
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13620.00 = 20677.72 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13620.00 TO NODE 13640.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 544.91 DOWNSTREAM(FEET) = 489.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 1384.37 CHANNEL SLOPE = 0.0404  
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 3.02

\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.324  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.39	0.30	1.000	-
USER-DEFINED	-	16.30	0.30	1.000	-
USER-DEFINED	-	4.08	0.30	1.000	-
USER-DEFINED	-	12.36	0.30	1.000	-
USER-DEFINED	-	11.23	0.30	1.000	-
USER-DEFINED	-	5.16	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1579.60  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 13.40  
AVERAGE FLOW DEPTH(FEET) = 3.02 TRAVEL TIME(MIN.) = 1.72  
Tc(MIN.) = 55.98  
SUBAREA AREA(ACRES) = 54.52 SUBAREA RUNOFF(CFS) = 50.27  
EFFECTIVE AREA(ACRES) = 1685.83 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95  
TOTAL AREA(ACRES) = 1748.7 PEAK FLOW RATE(CFS) = 1576.17  
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 3.02

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 3.02 FLOW VELOCITY(FEET/SEC.) = 13.38

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1279.48	22.11	2.267	0.30 ( 0.29)	0.96	718.1	13600.00
2	1576.17	55.98	1.324	0.30 ( 0.29)	0.95	1685.8	13510.00
3	1521.30	64.04	1.252	0.30 ( 0.28)	0.95	1748.7	13500.00

NEW PEAK FLOW DATA ARE:  
PEAK FLOW RATE(CFS) = 1576.17 Tc(MIN.) = 55.98  
AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.95 EFFECTIVE AREA(ACRES) = 1685.83

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 81  
-----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 55.98  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.324  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	53.93	0.30	1.000	-
USER-DEFINED	-	0.45	0.30	1.000	-
USER-DEFINED	-	3.98	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA(ACRES) = 58.36 SUBAREA RUNOFF(CFS) = 53.81  
EFFECTIVE AREA(ACRES) = 1744.19 AREA-AVERAGED Fm(INCH/HR) = 0.29  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95  
TOTAL AREA(ACRES) = 1807.1 PEAK FLOW RATE(CFS) = 1629.97

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: P201XXCE.DNA  
MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	262.78	16.94	0.30 ( 0.26)	0.85	133.8	20100.00

TOTAL AREA(ACRES) = 133.8

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13640.00 TO NODE 13640.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

=====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1382.80	22.11	2.267	0.30 ( 0.29)	0.96	776.4	13600.00
2	1629.97	55.98	1.324	0.30 ( 0.29)	0.95	1744.2	13510.00
3	1571.28	64.04	1.252	0.30 ( 0.29)	0.95	1807.1	13500.00

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	262.78	16.94	2.709	0.30 ( 0.26)	0.85	133.8	20100.00

LONGEST FLOWPATH FROM NODE 20100.00 TO NODE 13640.00 = 5247.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1559.40	16.94	2.709	0.30 ( 0.28)	0.94	728.9	20100.00
2	1598.22	22.11	2.267	0.30 ( 0.28)	0.95	910.2	13600.00
3	1744.40	55.98	1.324	0.30 ( 0.28)	0.95	1878.0	13510.00
4	1677.90	64.04	1.252	0.30 ( 0.28)	0.94	1940.9	13500.00

TOTAL AREA (ACRES) = 1940.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 1744.40 Tc (MIN.) = 55.984  
EFFECTIVE AREA (ACRES) = 1877.99 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95  
TOTAL AREA (ACRES) = 1940.9  
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13640.00 = 22062.09 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13640.00 TO NODE 13641.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 489.00 DOWNSTREAM (FEET) = 436.89  
CHANNEL LENGTH THRU SUBAREA (FEET) = 2994.52 CHANNEL SLOPE = 0.0174  
GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT (FEET) = 4.06

\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.274

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.96	0.30	1.000	-
USER-DEFINED	-	0.01	0.30	1.000	-
USER-DEFINED	-	1.56	0.30	1.000	-
USER-DEFINED	-	10.45	0.30	1.000	-
USER-DEFINED	-	44.94	0.30	1.000	-
USER-DEFINED	-	9.66	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 1774.01

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 10.37

AVERAGE FLOW DEPTH (FEET) = 4.06 TRAVEL TIME (MIN.) = 4.81

Tc (MIN.) = 60.80

SUBAREA AREA (ACRES) = 67.58 SUBAREA RUNOFF (CFS) = 59.22

EFFECTIVE AREA (ACRES) = 1945.57 AREA-AVERAGED Fm (INCH/HR) = 0.28

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95

TOTAL AREA (ACRES) = 2008.4 PEAK FLOW RATE (CFS) = 1744.40

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT (FEET) = 4.02

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 4.02 FLOW VELOCITY (FEET/SEC.) = 10.31  
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13641.00 = 25056.61 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1559.40	21.89	2.281	0.30 ( 0.28)	0.95	796.5	20100.00
2	1598.22	27.03	1.993	0.30 ( 0.28)	0.95	977.8	13600.00
3	1744.40	60.80	1.274	0.30 ( 0.28)	0.95	1945.6	13510.00
4	1689.13	68.91	1.218	0.30 ( 0.28)	0.95	2008.4	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 1744.40 Tc (MIN.) = 60.80

AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.95 EFFECTIVE AREA (ACRES) = 1945.57

\*\*\*\*\*

FLOW PROCESS FROM NODE 13641.00 TO NODE 13641.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 60.80

\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.274

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	16.49	0.30	1.000	-
USER-DEFINED	-	20.39	0.30	1.000	-
USER-DEFINED	-	7.02	0.30	1.000	-
USER-DEFINED	-	12.58	0.30	1.000	-
USER-DEFINED	-	42.49	0.30	1.000	-
USER-DEFINED	-	5.73	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 104.70 SUBAREA RUNOFF (CFS) = 91.75

EFFECTIVE AREA (ACRES) = 2050.27 AREA-AVERAGED Fm (INCH/HR) = 0.29

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95

TOTAL AREA (ACRES) = 2113.1 PEAK FLOW RATE (CFS) = 1823.72

\*\*\*\*\*

FLOW PROCESS FROM NODE 13641.00 TO NODE 13641.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 60.80

\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.274

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.78	0.30	1.000	-
USER-DEFINED	-	6.25	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 8.03 SUBAREA RUNOFF (CFS) = 7.04  
EFFECTIVE AREA (ACRES) = 2058.30 AREA-AVERAGED Fm (INCH/HR) = 0.29  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95  
TOTAL AREA (ACRES) = 2121.2 PEAK FLOW RATE (CFS) = 1830.76

```

*****
FLOW PROCESS FROM NODE 13641.00 TO NODE 13642.00 IS CODE = 56
-----
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 436.89 DOWNSTREAM(FEET) = 394.80
CHANNEL LENGTH THRU SUBAREA(FEET) = 2814.16 CHANNEL SLOPE = 0.0150
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 4.42
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.242
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.67 0.30 1.000 -
USER-DEFINED - 24.24 0.30 1.000 -
USER-DEFINED - 1.34 0.30 1.000 -
USER-DEFINED - 74.98 0.30 1.000 -
USER-DEFINED - 101.12 0.30 1.000 -
USER-DEFINED - 16.90 0.30 1.000 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 1923.70
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 10.06
AVERAGE FLOW DEPTH(FEET) = 4.42 TRAVEL TIME(MIN.) = 4.66
Tc(MIN.) = 65.46
SUBAREA AREA(ACRES) = 219.25 SUBAREA RUNOFF(CFS) = 185.87
EFFECTIVE AREA(ACRES) = 2277.55 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA(ACRES) = 2340.4 PEAK FLOW RATE(CFS) = 1957.90
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 4.46
END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 4.46 FLOW VELOCITY(FEET/SEC.) = 10.12
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13642.00 = 27870.77 FEET.

```

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	1748.35	26.64	2.010	0.30( 0.29)	0.96	1128.5	20100.00
2	1800.77	31.76	1.816	0.30( 0.29)	0.96	1309.8	13600.00
3	1957.90	65.46	1.242	0.30( 0.29)	0.96	2277.5	13510.00
4	1896.24	73.61	1.186	0.30( 0.29)	0.95	2340.4	13500.00

NEW PEAK FLOW DATA ARE:

```

PEAK FLOW RATE(CFS) = 1957.90 Tc(MIN.) = 65.46
AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.96 EFFECTIVE AREA(ACRES) = 2277.55

```

```

*****
FLOW PROCESS FROM NODE 13642.00 TO NODE 13642.00 IS CODE = 81
-----
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 65.46

```

```

* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.242
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 9.95 0.30 1.000 -
USER-DEFINED - 10.02 0.30 1.000 -
USER-DEFINED - 4.45 0.30 1.000 -
USER-DEFINED - 179.37 0.30 1.000 -
USER-DEFINED - 11.47 0.30 1.000 -
USER-DEFINED - 0.17 0.30 0.850 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 215.43 SUBAREA RUNOFF(CFS) = 182.64
EFFECTIVE AREA(ACRES) = 2492.98 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA(ACRES) = 2555.9 PEAK FLOW RATE(CFS) = 2140.54

```

```

*****
FLOW PROCESS FROM NODE 13642.00 TO NODE 13642.00 IS CODE = 81
-----

```

```

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<
=====
MAINLINE Tc(MIN.) = 65.46
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.242
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.03 0.30 0.850 -
USER-DEFINED - 5.14 0.30 1.000 -
USER-DEFINED - 11.22 0.30 1.000 -
USER-DEFINED - 0.33 0.30 1.000 -
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000
SUBAREA AREA(ACRES) = 16.72 SUBAREA RUNOFF(CFS) = 14.18
EFFECTIVE AREA(ACRES) = 2509.70 AREA-AVERAGED Fm(INCH/HR) = 0.29
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96
TOTAL AREA(ACRES) = 2572.6 PEAK FLOW RATE(CFS) = 2154.71

```

```

*****
FLOW PROCESS FROM NODE 13642.00 TO NODE 13643.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 394.80 DOWNSTREAM(FEET) = 342.39
CHANNEL LENGTH THRU SUBAREA(FEET) = 2913.57 CHANNEL SLOPE = 0.0180
GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 4.54
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.212
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 0.22 0.30 1.000 -
USER-DEFINED - 2.17 0.30 1.000 -
USER-DEFINED - 9.19 0.30 1.000 -
USER-DEFINED - 67.57 0.30 1.000 -
USER-DEFINED - 35.19 0.30 1.000 -

```



USER-DEFINED - 30.67 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2214.26  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.20  
 AVERAGE FLOW DEPTH(FEET) = 4.53 TRAVEL TIME(MIN.) = 4.34  
 Tc(MIN.) = 69.79  
 SUBAREA AREA(ACRES) = 145.01 SUBAREA RUNOFF(CFS) = 119.09  
 EFFECTIVE AREA(ACRES) = 2654.71 AREA-AVERAGED Fm(INCH/HR) = 0.29  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA(ACRES) = 2717.6 PEAK FLOW RATE(CFS) = 2207.20  
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 4.53

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 4.53 FLOW VELOCITY(FEET/SEC.) = 11.19  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13643.00 = 30784.34 FEET.

**\*\* PEAK FLOW RATE TABLE \*\***  

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2105.66	30.99	1.836	0.30( 0.29)	0.97	1505.6	20100.00
2	2147.47	36.10	1.706	0.30( 0.29)	0.97	1687.0	13600.00
3	2207.20	69.79	1.212	0.30( 0.29)	0.96	2654.7	13510.00
4	2124.25	78.00	1.157	0.30( 0.29)	0.96	2717.6	13500.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE(CFS) = 2207.20 Tc(MIN.) = 69.79  
 AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.96 EFFECTIVE AREA(ACRES) = 2654.71

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13643.00 TO NODE 13643.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

\*\*\*\*\*  
 MAINLINE Tc(MIN.) = 69.79  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.212  
 SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.89	0.30	1.000	-
USER-DEFINED	-	20.65	0.30	1.000	-
USER-DEFINED	-	2.69	0.30	1.000	-
USER-DEFINED	-	8.45	0.30	1.000	-
USER-DEFINED	-	96.93	0.30	1.000	-
USER-DEFINED	-	13.19	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 142.80 SUBAREA RUNOFF(CFS) = 117.27  
 EFFECTIVE AREA(ACRES) = 2797.51 AREA-AVERAGED Fm(INCH/HR) = 0.29  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.96  
 TOTAL AREA(ACRES) = 2860.4 PEAK FLOW RATE(CFS) = 2324.47

**\*\* PEAK FLOW RATE TABLE \*\***  

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2290.19	30.99	1.836	0.30( 0.29)	0.97	1648.4	20100.00

2 2328.11 36.10 1.706 0.30( 0.29) 0.97 1829.8 13600.00  
 3 2324.47 69.79 1.212 0.30( 0.29) 0.96 2797.5 13510.00  
 4 2234.36 78.00 1.157 0.30( 0.29) 0.96 2860.4 13500.00  
 NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE(CFS) = 2328.11 Tc(MIN.) = 36.10  
 AREA-AVERAGED Fm(INCH/HR) = 0.29 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.97 EFFECTIVE AREA(ACRES) = 1829.77

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13643.00 TO NODE 13643.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

\*\*\*\*\*  
 MAINLINE Tc(MIN.) = 36.10  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.706  
 SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	42.54	0.30	1.000	-
USER-DEFINED	-	16.96	0.30	1.000	-
USER-DEFINED	-	80.60	0.30	1.000	-
USER-DEFINED	-	1.56	0.30	1.000	-
USER-DEFINED	-	2.00	0.30	1.000	-
USER-DEFINED	-	3.11	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 146.77 SUBAREA RUNOFF(CFS) = 185.67  
 EFFECTIVE AREA(ACRES) = 1976.54 AREA-AVERAGED Fm(INCH/HR) = 0.29  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97  
 TOTAL AREA(ACRES) = 3007.2 PEAK FLOW RATE(CFS) = 2513.78

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13643.00 TO NODE 13660.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

\*\*\*\*\*  
 ELEVATION DATA: UPSTREAM(FEET) = 342.39 DOWNSTREAM(FEET) = 300.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1591.23 CHANNEL SLOPE = 0.0266  
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 4.40  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.655  
 SUBAREA LOSS RATE DATA(AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.89	0.30	1.000	-
USER-DEFINED	-	23.73	0.30	1.000	-
USER-DEFINED	-	0.27	0.30	1.000	-
USER-DEFINED	-	19.87	0.30	1.000	-
USER-DEFINED	-	6.40	0.30	1.000	-
USER-DEFINED	-	3.14	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 2546.89  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 13.40  
 AVERAGE FLOW DEPTH(FEET) = 4.40 TRAVEL TIME(MIN.) = 1.98  
 Tc(MIN.) = 38.08

SUBAREA AREA (ACRES) = 54.30 SUBAREA RUNOFF (CFS) = 66.22  
 EFFECTIVE AREA (ACRES) = 2030.84 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98  
 TOTAL AREA (ACRES) = 3061.5 PEAK FLOW RATE (CFS) = 2513.78  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 4.37

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 4.37 FLOW VELOCITY (FEET/SEC.) = 13.35  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 32375.57 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2493.08	32.97	1.785	0.30 (0.29)	0.98	1849.5	20100.00
2	2513.78	38.08	1.655	0.30 (0.29)	0.98	2030.8	13600.00
3	2452.94	71.79	1.199	0.30 (0.29)	0.97	2998.6	13510.00
4	2351.50	80.02	1.143	0.30 (0.29)	0.96	3061.5	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 2513.78 Tc (MIN.) = 38.08  
 AREA-AVERAGED Fm (INCH/HR) = 0.29 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.98 EFFECTIVE AREA (ACRES) = 2030.84

\*\*\*\*\*

FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 38.08

\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.655

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.67	0.30	1.000	-
USER-DEFINED	-	9.52	0.30	1.000	-
USER-DEFINED	-	0.71	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	39.42	0.30	1.000	-
USER-DEFINED	-	0.62	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 51.16 SUBAREA RUNOFF (CFS) = 62.39

EFFECTIVE AREA (ACRES) = 2082.00 AREA-AVERAGED Fm (INCH/HR) = 0.29

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98

TOTAL AREA (ACRES) = 3112.6 PEAK FLOW RATE (CFS) = 2552.63

\*\*\*\*\*

FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc (MIN.) = 38.08

\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.655

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.67	0.30	1.000	-
USER-DEFINED	-	9.52	0.30	1.000	-
USER-DEFINED	-	0.71	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	39.42	0.30	1.000	-
USER-DEFINED	-	0.62	0.30	1.000	-

USER-DEFINED - 0.11 0.30 1.000 -  
 USER-DEFINED - 0.77 0.30 1.000 -  
 USER-DEFINED - 0.22 0.30 1.000 -  
 USER-DEFINED - 2.69 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 3.79 SUBAREA RUNOFF (CFS) = 4.62  
 EFFECTIVE AREA (ACRES) = 2085.79 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98  
 TOTAL AREA (ACRES) = 3116.4 PEAK FLOW RATE (CFS) = 2557.25

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2557.45	32.97	1.785	0.30 (0.29)	0.98	1904.4	20100.00
2	2557.25	38.08	1.655	0.30 (0.29)	0.98	2085.8	13600.00
3	2497.40	71.79	1.199	0.30 (0.29)	0.97	3053.5	13510.00
4	2393.19	80.02	1.143	0.30 (0.29)	0.97	3116.4	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 2557.45 Tc (MIN.) = 32.97  
 AREA-AVERAGED Fm (INCH/HR) = 0.29 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.98 EFFECTIVE AREA (ACRES) = 1904.44

\*\*\*\*\*

FLOW PROCESS FROM NODE 13643.00 TO NODE 13660.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 1 <<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 13659.00 TO NODE 13659.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 1 <<<<

PEAK FLOWRATE TABLE FILE NAME: 2P00EVAA.DNA

MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	589.23	13.84	0.30 (0.11)	0.36	173.5	110.00
2	590.10	16.35	0.30 (0.11)	0.38	204.6	100.00
3	582.95	17.51	0.30 (0.11)	0.38	213.9	100.00
4	519.41	20.54	0.30 (0.12)	0.40	221.1	130.00
TOTAL AREA (ACRES) =						221.1

\*\*\*\*\*

FLOW PROCESS FROM NODE 13659.00 TO NODE 13660.00 IS CODE = 31

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<

>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<

ELEVATION DATA: UPSTREAM (FEET) = 338.00 DOWNSTREAM (FEET) = 300.00

FLOW LENGTH (FEET) = 881.07 MANNING'S N = 0.013

DEPTH OF FLOW IN 114.0 INCH PIPE IS 84.6 INCHES

PIPE-FLOW VELOCITY (FEET/SEC.) = 45.37

ESTIMATED PIPE DIAMETER (INCH) = 114.00 NUMBER OF PIPES = 1

PIPE-FLOW (CFS) = 2557.45

PIPE TRAVEL TIME (MIN.) = 0.32 Tc (MIN.) = 33.29

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2557.45	33.29	1.777	0.30( 0.29)	0.98	1904.4	20100.00
2	2557.25	38.40	1.647	0.30( 0.29)	0.98	2085.8	13600.00
3	2497.40	72.12	1.197	0.30( 0.29)	0.97	3053.5	13510.00
4	2393.19	80.35	1.141	0.30( 0.29)	0.97	3116.4	13500.00

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	589.23	13.84	3.100	0.30( 0.11)	0.36	173.5	110.00
2	590.10	16.35	2.769	0.30( 0.11)	0.38	204.6	100.00
3	582.95	17.51	2.652	0.30( 0.11)	0.38	213.9	100.00
4	519.41	20.54	2.367	0.30( 0.12)	0.40	221.1	130.00

LONGEST FLOWPATH FROM NODE 130.00 TO NODE 13660.00 = 6327.50 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2600.15	13.84	3.100	0.30( 0.26)	0.87	965.1	110.00
2	2685.54	16.35	2.769	0.30( 0.26)	0.87	1139.7	100.00
3	2721.21	17.51	2.652	0.30( 0.26)	0.87	1215.6	100.00
4	2724.13	20.54	2.367	0.30( 0.27)	0.89	1395.9	130.00
5	2940.50	33.29	1.777	0.30( 0.28)	0.92	2125.5	20100.00
6	2910.19	38.40	1.647	0.30( 0.28)	0.92	2306.9	13600.00
7	2746.24	72.12	1.197	0.30( 0.28)	0.93	3274.6	13510.00
8	2629.09	80.35	1.141	0.30( 0.28)	0.93	3337.5	13500.00

TOTAL AREA (ACRES) = 3337.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 2940.50 Tc(MIN.) = 33.292  
EFFECTIVE AREA(ACRES) = 2125.54 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.87  
TOTAL AREA (ACRES) = 3337.5  
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13660.00 = 33256.64 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 33.29

\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.777

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "FALLOW"	B	1.11	0.30	1.000	86
AGRICULTURAL POOR COVER					

"FALLOW"	B	0.44	0.30	1.000	86
NATURAL FAIR COVER "GRASS"	B	1.49	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	1.70	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	1.09	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	18.57	0.30	1.000	66
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000					
SUBAREA AREA(ACRES) = 24.40 SUBAREA RUNOFF(CFS) = 32.44					
EFFECTIVE AREA(ACRES) = 2149.94 AREA-AVERAGED Fm(INCH/HR) = 0.28					
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92					
TOTAL AREA(ACRES) = 3361.9 PEAK FLOW RATE(CFS) = 2940.50					
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE					

\*\*\*\*\*

FLOW PROCESS FROM NODE 13660.00 TO NODE 13660.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 33.29

\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.777

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL FAIR COVER "ORCHARDS"	B	12.39	0.30	1.000	65
AGRICULTURAL FAIR COVER "ORCHARDS"	B	2.30	0.30	1.000	65
AGRICULTURAL POOR COVER "ROW CROPS,CONTOURED"	B	5.19	0.30	1.000	79
AGRICULTURAL POOR COVER "ROW CROPS,STRAIGHT ROW"	B	28.71	0.30	1.000	81
NATURAL FAIR COVER "WOODLAND,GRASS"	B	0.17	0.30	1.000	65
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30					
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000					
SUBAREA AREA(ACRES) = 48.76 SUBAREA RUNOFF(CFS) = 64.82					
EFFECTIVE AREA(ACRES) = 2198.70 AREA-AVERAGED Fm(INCH/HR) = 0.28					
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92					
TOTAL AREA(ACRES) = 3410.7 PEAK FLOW RATE(CFS) = 2970.23					

\*\*\*\*\*

FLOW PROCESS FROM NODE 13660.00 TO NODE 13680.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 300.00	DOWNSTREAM(FEET) = 288.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 933.89	CHANNEL SLOPE = 0.0128
GIVEN CHANNEL BASE(FEET) = 30.00	CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 3.000	MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 5.81	
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.740	
SUBAREA LOSS RATE DATA(AMC II):	
DEVELOPMENT TYPE/	SCS SOIL AREA Fp Ap SCS

LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 0.22 0.30 1.000 -  
 USER-DEFINED - 9.23 0.30 1.000 -  
 USER-DEFINED - 0.54 0.30 1.000 -  
 USER-DEFINED - 5.66 0.30 1.000 -  
 USER-DEFINED - 3.66 0.30 1.000 -  
 USER-DEFINED - 0.67 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 2983.18  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 10.83  
 AVERAGE FLOW DEPTH (FEET) = 5.81 TRAVEL TIME (MIN.) = 1.44  
 Tc (MIN.) = 34.73  
 SUBAREA AREA (ACRES) = 19.98 SUBAREA RUNOFF (CFS) = 25.90  
 EFFECTIVE AREA (ACRES) = 2218.68 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA (ACRES) = 3430.6 PEAK FLOW RATE (CFS) = 2970.23  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 5.79  
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 5.79 FLOW VELOCITY (FEET/SEC.) = 10.82  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13680.00 = 34190.53 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2651.20	15.32	2.873	0.30 ( 0.26)	0.88	1058.2	110.00
2	2735.61	17.82	2.621	0.30 ( 0.26)	0.88	1232.9	100.00
3	2769.77	18.98	2.504	0.30 ( 0.26)	0.88	1308.7	100.00
4	2775.63	22.00	2.274	0.30 ( 0.27)	0.89	1489.1	130.00
5	2970.23	34.73	1.740	0.30 ( 0.28)	0.92	2218.7	20100.00
6	2934.18	39.84	1.610	0.30 ( 0.28)	0.92	2400.0	13600.00
7	2764.53	73.58	1.187	0.30 ( 0.28)	0.93	3367.8	13510.00
8	2645.20	81.84	1.131	0.30 ( 0.28)	0.93	3430.6	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 2970.23 Tc (MIN.) = 34.73  
 AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.92 EFFECTIVE AREA (ACRES) = 2218.68

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 34.73

\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.740

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	1.56	0.30	1.000	-
USER-DEFINED	-	9.40	0.30	1.000	-
USER-DEFINED	-	2.76	0.30	1.000	-
USER-DEFINED	-	17.38	0.30	1.000	-
USER-DEFINED	-	2.46	0.30	1.000	-
USER-DEFINED	-	5.56	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 39.12 SUBAREA RUNOFF (CFS) = 50.72  
 EFFECTIVE AREA (ACRES) = 2257.80 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA (ACRES) = 3469.8 PEAK FLOW RATE (CFS) = 2974.31

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 34.73

\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.740

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.65	0.30	1.000	-
USER-DEFINED	-	1.70	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 2.35 SUBAREA RUNOFF (CFS) = 3.05

EFFECTIVE AREA (ACRES) = 2260.15 AREA-AVERAGED Fm (INCH/HR) = 0.28

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92

TOTAL AREA (ACRES) = 3472.1 PEAK FLOW RATE (CFS) = 2977.36

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13660.00 TO NODE 13680.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 34.73

\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.740

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	5.29	0.30	1.000	-
USER-DEFINED	-	31.25	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	6.26	0.30	1.000	-
USER-DEFINED	-	0.07	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA AREA (ACRES) = 43.31 SUBAREA RUNOFF (CFS) = 56.15

EFFECTIVE AREA (ACRES) = 2303.46 AREA-AVERAGED Fm (INCH/HR) = 0.28

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92

TOTAL AREA (ACRES) = 3515.4 PEAK FLOW RATE (CFS) = 3033.51

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 34.73  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.740  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	2.47	0.30	0.850	-
USER-DEFINED	-	3.06	0.30	0.850	-
USER-DEFINED	-	17.76	0.30	0.500	-
USER-DEFINED	-	7.31	0.30	0.500	-
USER-DEFINED	-	0.34	0.30	1.000	-
USER-DEFINED	-	8.22	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.659  
 SUBAREA AREA(ACRES) = 39.16 SUBAREA RUNOFF(CFS) = 54.38  
 EFFECTIVE AREA(ACRES) = 2342.62 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 3554.6 PEAK FLOW RATE(CFS) = 3087.88

\*\*\*\*\*

FLOW PROCESS FROM NODE 13680.00 TO NODE 13680.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 34.73  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.740  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.53	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 0.53 SUBAREA RUNOFF(CFS) = 0.69  
 EFFECTIVE AREA(ACRES) = 2343.15 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 3555.1 PEAK FLOW RATE(CFS) = 3088.57

\*\*\*\*\*

FLOW PROCESS FROM NODE 13680.00 TO NODE 13682.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

=====

ELEVATION DATA: UPSTREAM( FEET) = 288.00 DOWNSTREAM( FEET) = 242.00  
 CHANNEL LENGTH THRU SUBAREA( FEET) = 2860.77 CHANNEL SLOPE = 0.0161  
 GIVEN CHANNEL BASE( FEET) = 30.00 CHANNEL FREEBOARD( FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT( FEET) = 5.58  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.638  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	5.28	0.30	1.000	-
USER-DEFINED	-	0.52	0.30	1.000	-
USER-DEFINED	-	3.61	0.30	1.000	-
USER-DEFINED	-	0.67	0.30	1.000	-

USER-DEFINED - 1.37 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3095.60  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY( FEET/SEC.) = 11.86  
 AVERAGE FLOW DEPTH( FEET) = 5.58 TRAVEL TIME( MIN.) = 4.02  
 Tc( MIN.) = 38.75  
 SUBAREA AREA( ACRES) = 11.67 SUBAREA RUNOFF( CFS) = 14.05  
 EFFECTIVE AREA( ACRES) = 2354.82 AREA-AVERAGED Fm( INCH/HR) = 0.28  
 AREA-AVERAGED Fp( INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA( ACRES) = 3566.8 PEAK FLOW RATE( CFS) = 3088.57  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE( FEET) = 30.00 CHANNEL FREEBOARD( FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT( FEET) = 5.57

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH( FEET) = 5.57 FLOW VELOCITY( FEET/SEC.) = 11.86  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13682.00 = 37051.30 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2776.71	19.46	2.455	0.30( 0.26)	0.88	1194.4	110.00
2	2879.22	21.92	2.279	0.30( 0.26)	0.88	1369.0	100.00
3	2888.80	23.07	2.206	0.30( 0.27)	0.88	1444.9	100.00
4	2912.73	26.09	2.035	0.30( 0.27)	0.89	1625.2	130.00
5	3088.57	38.75	1.638	0.30( 0.28)	0.92	2354.8	20100.00
6	3029.31	43.89	1.523	0.30( 0.28)	0.92	2536.2	13600.00
7	2853.36	77.70	1.159	0.30( 0.28)	0.93	3503.9	13510.00
8	2725.78	86.00	1.102	0.30( 0.28)	0.93	3566.8	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 3088.57 Tc(MIN.) = 38.75  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.92 EFFECTIVE AREA(ACRES) = 2354.82

\*\*\*\*\*

FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

=====

MAINLINE Tc(MIN.) = 38.75  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.638  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	6.90	0.30	1.000	-
USER-DEFINED	-	23.04	0.30	1.000	-
USER-DEFINED	-	1.18	0.30	1.000	-
USER-DEFINED	-	1.56	0.30	1.000	-
USER-DEFINED	-	53.20	0.30	1.000	-
USER-DEFINED	-	2.08	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 87.96 SUBAREA RUNOFF(CFS) = 105.92  
 EFFECTIVE AREA(ACRES) = 2442.78 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 3654.7 PEAK FLOW RATE(CFS) = 3088.57

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 38.75  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.638  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.01	0.30	1.000	-
USER-DEFINED	-	0.18	0.30	1.000	-
USER-DEFINED	-	0.38	0.30	1.000	-
USER-DEFINED	-	0.22	0.30	1.000	-
USER-DEFINED	-	7.73	0.30	1.000	-
USER-DEFINED	-	4.37	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 12.89 SUBAREA RUNOFF(CFS) = 15.52  
 EFFECTIVE AREA(ACRES) = 2455.67 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 3667.6 PEAK FLOW RATE(CFS) = 3088.57  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 38.75  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.638  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
AGRICULTURAL POOR COVER "FALLOW"	B	2.57	0.30	1.000	86
AGRICULTURAL POOR COVER "FALLOW"	B	1.97	0.30	1.000	86
NATURAL FAIR COVER "GRASS"	B	1.00	0.30	1.000	69
NATURAL FAIR COVER "GRASS"	B	2.98	0.30	1.000	69
NATURAL FAIR COVER "OPEN BRUSH"	B	2.39	0.30	1.000	66
NATURAL FAIR COVER "OPEN BRUSH"	B	1.67	0.30	1.000	66

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 12.58 SUBAREA RUNOFF(CFS) = 15.15  
 EFFECTIVE AREA(ACRES) = 2468.25 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 3680.2 PEAK FLOW RATE(CFS) = 3088.57  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 38.75  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.638  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
NATURAL FAIR COVER "OPEN BRUSH"	B	0.44	0.30	1.000	66
PUBLIC PARK	B	2.65	0.30	0.850	56
PUBLIC PARK	B	1.16	0.30	0.850	56
RESIDENTIAL "5-7 DWELLINGS/ACRE"	B	0.47	0.30	0.500	56
RESIDENTIAL "5-7 DWELLINGS/ACRE"	B	0.25	0.30	0.500	56
AGRICULTURAL POOR COVER "ROW CROPS, STRAIGHT ROW"	B	20.24	0.30	1.000	81

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.963  
 SUBAREA AREA(ACRES) = 25.21 SUBAREA RUNOFF(CFS) = 30.61  
 EFFECTIVE AREA(ACRES) = 2493.46 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 3705.4 PEAK FLOW RATE(CFS) = 3088.57  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13682.00 TO NODE 13682.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 38.75  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.638  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.08	0.30	1.000	-
USER-DEFINED	-	6.75	0.30	1.000	-
USER-DEFINED	-	0.02	0.30	1.000	-
USER-DEFINED	-	0.93	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA(ACRES) = 14.78 SUBAREA RUNOFF(CFS) = 17.80  
 EFFECTIVE AREA(ACRES) = 2508.24 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 3720.2 PEAK FLOW RATE(CFS) = 3088.57  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*

FLOW PROCESS FROM NODE 13682.00 TO NODE 13683.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 242.00 DOWNSTREAM(FEET) = 208.53  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 2526.22 CHANNEL SLOPE = 0.0132  
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT (FEET) = 5.89  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.551  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.49	0.30	1.000	-
USER-DEFINED	-	13.31	0.30	1.000	-
USER-DEFINED	-	0.87	0.30	1.000	-
USER-DEFINED	-	20.26	0.30	1.000	-
USER-DEFINED	-	1.21	0.30	1.000	-
USER-DEFINED	-	0.05	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 3113.46  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 11.08  
 AVERAGE FLOW DEPTH (FEET) = 5.89 TRAVEL TIME (MIN.) = 3.80  
 Tc (MIN.) = 42.55  
 SUBAREA AREA (ACRES) = 44.19 SUBAREA RUNOFF (CFS) = 49.78  
 EFFECTIVE AREA (ACRES) = 2552.43 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 3764.4 PEAK FLOW RATE (CFS) = 3088.57  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 5.86

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 5.86 FLOW VELOCITY (FEET/SEC.) = 11.07  
 LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13683.00 = 39577.52 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2776.71	23.37	2.187	0.30 (0.27)	0.90	1392.0	110.00
2	2879.22	25.79	2.048	0.30 (0.27)	0.90	1566.6	100.00
3	2888.80	26.93	1.997	0.30 (0.27)	0.90	1642.5	100.00
4	2912.73	29.94	1.863	0.30 (0.27)	0.91	1822.8	130.00
5	3088.57	42.55	1.551	0.30 (0.28)	0.93	2552.4	20100.00
6	3029.31	47.71	1.441	0.30 (0.28)	0.93	2733.8	13600.00
7	2893.29	81.57	1.132	0.30 (0.28)	0.93	3701.5	13510.00
8	2754.58	89.93	1.075	0.30 (0.28)	0.93	3764.4	13500.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE (CFS) = 3088.57 Tc (MIN.) = 42.55  
 AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA (ACRES) = 2552.43

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

\*\*\*\*\*

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	12.56	0.30	1.000	-
USER-DEFINED	-	0.81	0.30	1.000	-

USER-DEFINED - 0.01 0.30 1.000 -  
 USER-DEFINED - 1.11 0.30 1.000 -  
 USER-DEFINED - 0.59 0.30 1.000 -  
 USER-DEFINED - 3.04 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA AREA (ACRES) = 18.12 SUBAREA RUNOFF (CFS) = 20.41  
 EFFECTIVE AREA (ACRES) = 2570.55 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 3782.5 PEAK FLOW RATE (CFS) = 3088.57  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

\*\*\*\*\*

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL					
"8-10 DWELLINGS/ACRE"	B	0.10	0.30	0.400	56
PUBLIC PARK	B	1.30	0.30	0.850	56
RESIDENTIAL					
"8-10 DWELLINGS/ACRE"	B	0.10	0.30	0.400	56
PUBLIC PARK	B	1.70	0.30	0.850	56
PUBLIC PARK	B	0.10	0.30	0.850	56
PUBLIC PARK	B	2.90	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.835  
 SUBAREA AREA (ACRES) = 6.20 SUBAREA RUNOFF (CFS) = 7.26  
 EFFECTIVE AREA (ACRES) = 2576.75 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 3788.7 PEAK FLOW RATE (CFS) = 3088.57  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

\*\*\*\*\*

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
RESIDENTIAL					
"5-7 DWELLINGS/ACRE"	B	0.10	0.30	0.500	56
CONDOMINIUMS	B	0.10	0.30	0.350	56
PUBLIC PARK	B	6.90	0.30	0.850	56
PUBLIC PARK	B	0.40	0.30	0.850	56

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.839  
 SUBAREA AREA (ACRES) = 7.50 SUBAREA RUNOFF (CFS) = 8.77  
 EFFECTIVE AREA (ACRES) = 2584.25 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA (ACRES) = 3796.2 PEAK FLOW RATE (CFS) = 3088.57  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13682.00 TO NODE 13683.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*MEMORY BANK # 3 IS EMPTY - PROCESS IGNORED.\*\*\*

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 42.55  
\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.551  
SUBAREA LOSS RATE DATA (AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
AGRICULTURAL POOR COVER  
"FALLOW" B 2.55 0.30 1.000 86  
AGRICULTURAL POOR COVER  
"FALLOW" B 0.01 0.30 1.000 86  
AGRICULTURAL POOR COVER  
"FALLOW" B 1.35 0.30 1.000 86  
NATURAL FAIR COVER  
"GRASS" B 0.44 0.30 1.000 69  
NATURAL FAIR COVER  
"GRASS" B 0.67 0.30 1.000 69  
NATURAL FAIR COVER  
"OPEN BRUSH" B 1.06 0.30 1.000 66  
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 6.08 SUBAREA RUNOFF (CFS) = 6.85  
EFFECTIVE AREA (ACRES) = 2590.33 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA (ACRES) = 3802.3 PEAK FLOW RATE (CFS) = 3088.57  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 42.55  
\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.551  
SUBAREA LOSS RATE DATA (AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
NATURAL FAIR COVER  
"OPEN BRUSH" B 2.16 0.30 1.000 66  
NATURAL FAIR COVER  
"OPEN BRUSH" B 2.45 0.30 1.000 66  
NATURAL FAIR COVER  
"OPEN BRUSH" B 6.15 0.30 1.000 66  
AGRICULTURAL POOR COVER  
"ROW CROPS, STRAIGHT ROW" B 1.34 0.30 1.000 81

AGRICULTURAL POOR COVER  
"ROW CROPS, STRAIGHT ROW" B 18.46 0.30 1.000 81  
AGRICULTURAL POOR COVER  
"ROW CROPS, STRAIGHT ROW" B 4.13 0.30 1.000 81  
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 34.69 SUBAREA RUNOFF (CFS) = 39.07  
EFFECTIVE AREA (ACRES) = 2625.02 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA (ACRES) = 3837.0 PEAK FLOW RATE (CFS) = 3088.57  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13683.00 TO NODE 13683.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 42.55  
\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.551  
SUBAREA LOSS RATE DATA (AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
AGRICULTURAL POOR COVER  
"ROW CROPS, STRAIGHT ROW" B 8.69 0.30 1.000 81  
NATURAL FAIR COVER  
"WOODLAND, GRASS" B 0.73 0.30 1.000 65  
NATURAL FAIR COVER  
"WOODLAND, GRASS" B 0.41 0.30 1.000 65  
NATURAL FAIR COVER  
"WOODLAND, GRASS" B 1.37 0.30 1.000 65  
NATURAL FAIR COVER  
"WOODLAND, GRASS" B 3.11 0.30 1.000 65  
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA AREA (ACRES) = 14.31 SUBAREA RUNOFF (CFS) = 16.12  
EFFECTIVE AREA (ACRES) = 2639.33 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA (ACRES) = 3851.3 PEAK FLOW RATE (CFS) = 3088.57  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13683.00 TO NODE 13685.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 208.53 DOWNSTREAM (FEET) = 194.24  
CHANNEL LENGTH THRU SUBAREA (FEET) = 289.01 CHANNEL SLOPE = 0.0494  
GIVEN CHANNEL BASE (FEET) = 30.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040  
\* ESTIMATED CHANNEL HEIGHT (FEET) = 4.13  
CHANNEL FLOW THRU SUBAREA (CFS) = 3088.57  
FLOW VELOCITY (FEET/SEC.) = 17.64 FLOW DEPTH (FEET) = 4.13  
TRAVEL TIME (MIN.) = 0.27 Tc (MIN.) = 42.82  
LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13685.00 = 39866.53 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM Q Tc Intensity Fp (Fm) Ap Ae HEADWATER



NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	2776.71	23.65	2.169	0.30 ( 0.27)	0.90	1478.9
2	2879.22	26.06	2.036	0.30 ( 0.27)	0.90	1653.5
3	2888.80	27.21	1.985	0.30 ( 0.27)	0.90	1729.4
4	2912.73	30.22	1.855	0.30 ( 0.27)	0.91	1909.7
5	3088.57	42.82	1.546	0.30 ( 0.28)	0.93	2639.3
6	3029.31	47.98	1.435	0.30 ( 0.28)	0.93	2820.7
7	2905.42	81.85	1.130	0.30 ( 0.28)	0.93	3788.4
8	2757.25	90.21	1.074	0.30 ( 0.28)	0.93	3851.3

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 3088.57 Tc(MIN.) = 42.82  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 2639.33

\*\*\*\*\*

FLOW PROCESS FROM NODE 13685.00 TO NODE 13410.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 194.24 DOWNSTREAM(FEET) = 178.72  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1843.57 CHANNEL SLOPE = 0.0084  
 GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.60  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 1.476

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	0.23	0.30	1.000	-
USER-DEFINED	-	1.52	0.30	1.000	-
USER-DEFINED	-	0.06	0.30	1.000	-
USER-DEFINED	-	0.13	0.30	1.000	-
USER-DEFINED	-	6.45	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 3093.01

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.41

AVERAGE FLOW DEPTH(FEET) = 6.60 TRAVEL TIME(MIN.) = 3.27

Tc(MIN.) = 46.09

SUBAREA AREA(ACRES) = 8.39 SUBAREA RUNOFF(CFS) = 8.88

EFFECTIVE AREA(ACRES) = 2647.72 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA(ACRES) = 3859.7 PEAK FLOW RATE(CFS) = 3088.57

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 30.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 3.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 6.60

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 6.60 FLOW VELOCITY(FEET/SEC.) = 9.40

LONGEST FLOWPATH FROM NODE 13500.00 TO NODE 13410.00 = 41710.10 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2776.71	27.02	1.993	0.30 ( 0.27)	0.90	1487.3	110.00
2	2879.22	29.39	1.888	0.30 ( 0.27)	0.90	1661.9	100.00

3	2888.80	30.54	1.847	0.30 ( 0.27)	0.90	1737.8	100.00
4	2912.73	33.54	1.771	0.30 ( 0.27)	0.91	1918.1	130.00
5	3088.57	46.09	1.476	0.30 ( 0.28)	0.93	2647.7	20100.00
6	3029.31	51.27	1.378	0.30 ( 0.28)	0.93	2829.1	13600.00
7	2905.42	85.17	1.108	0.30 ( 0.28)	0.93	3796.8	13510.00
8	2757.25	93.58	1.059	0.30 ( 0.28)	0.93	3859.7	13500.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 3088.57 Tc(MIN.) = 46.09  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 2647.72

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 3859.7 TC(MIN.) = 46.09  
 EFFECTIVE AREA(ACRES) = 2647.72 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.928  
 PEAK FLOW RATE(CFS) = 3088.57

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	2776.71	27.02	1.993	0.30 ( 0.27)	0.90	1487.3	110.00
2	2879.22	29.39	1.888	0.30 ( 0.27)	0.90	1661.9	100.00
3	2888.80	30.54	1.847	0.30 ( 0.27)	0.90	1737.8	100.00
4	2912.73	33.54	1.771	0.30 ( 0.27)	0.91	1918.1	130.00
5	3088.57	46.09	1.476	0.30 ( 0.28)	0.93	2647.7	20100.00
6	3029.31	51.27	1.378	0.30 ( 0.28)	0.93	2829.1	13600.00
7	2905.42	85.17	1.108	0.30 ( 0.28)	0.93	3796.8	13510.00
8	2757.25	93.58	1.059	0.30 ( 0.28)	0.93	3859.7	13500.00

END OF RATIONAL METHOD ANALYSIS



\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S37- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 100-YR RM EV APRIL 2019 CCHIU \*  
\*\*\*\*\*

FILE NAME: RI00EV37.DAT  
TIME/DATE OF STUDY: 08:52 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 100.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.768
- 2) 10.00; 3.736
- 3) 15.00; 2.899
- 4) 20.00; 2.397
- 5) 25.00; 2.080
- 6) 30.00; 1.859
- 7) 40.00; 1.604
- 8) 50.00; 1.391
- 9) 60.00; 1.276
- 10) 90.00; 1.073
- 11) 120.00; 0.936
- 12) 180.00; 0.780
- 13) 360.00; 0.574
- 14) 1200.00; 0.249

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI00EV34.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	31135.07	17.92	0.30 ( 0.25)	0.83	5360.1	300.00
2	35127.45	27.38	0.30 ( 0.25)	0.82	8888.0	110.00
3	37783.12	33.90	0.30 ( 0.25)	0.83	11789.3	130.00
4	39878.66	39.13	0.30 ( 0.25)	0.84	14293.0	150.00
5	43148.36	52.89	0.30 ( 0.26)	0.87	21358.0	390.00
6	45479.29	64.06	0.30 ( 0.27)	0.89	27390.0	13100.00
7	47160.15	70.50	0.30 ( 0.27)	0.90	30461.5	11801.00
8	49573.90	79.79	0.30 ( 0.27)	0.91	35506.8	11530.00
9	50907.76	85.49	0.30 ( 0.27)	0.91	39376.1	13510.00
10	51922.20	90.11	0.30 ( 0.28)	0.92	42408.3	13010.00
11	53046.66	95.15	0.30 ( 0.28)	0.92	45756.2	11330.00
12	53687.90	101.43	0.30 ( 0.28)	0.93	50187.2	11130.00
13	53098.84	109.05	0.30 ( 0.28)	0.94	54181.2	12330.00
14	52449.96	115.72	0.30 ( 0.28)	0.94	57524.3	12400.00
15	51426.75	124.44	0.30 ( 0.28)	0.94	60893.1	12201.00
16	49933.87	133.86	0.30 ( 0.28)	0.94	63347.3	12101.10
17	49255.12	137.92	0.30 ( 0.28)	0.94	64196.3	10400.00
18	47420.89	146.06	0.30 ( 0.28)	0.94	65511.5	12010.00
19	45914.79	152.03	0.30 ( 0.28)	0.94	65825.2	10210.00
20	41585.24	178.38	0.30 ( 0.28)	0.95	66557.9	10100.00
TOTAL AREA (ACRES) =						66557.9

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13700.00 TO NODE 13700.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 3 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	31135.07	17.92	0.30 ( 0.25)	0.83	5360.1	300.00
2	35127.45	27.38	0.30 ( 0.25)	0.82	8888.0	110.00
3	37783.12	33.90	0.30 ( 0.25)	0.83	11789.3	130.00
4	39878.66	39.13	0.30 ( 0.25)	0.84	14293.0	150.00
5	43148.36	52.89	0.30 ( 0.26)	0.87	21358.0	390.00
6	45479.29	64.06	0.30 ( 0.27)	0.89	27390.0	13100.00
7	47160.15	70.50	0.30 ( 0.27)	0.90	30461.5	11801.00
8	49573.90	79.79	0.30 ( 0.27)	0.91	35506.8	11530.00
9	50907.76	85.49	0.30 ( 0.27)	0.91	39376.1	13510.00
10	51922.20	90.11	0.30 ( 0.28)	0.92	42408.3	13010.00
11	53046.66	95.15	0.30 ( 0.28)	0.92	45756.2	11330.00
12	53687.90	101.43	0.30 ( 0.28)	0.93	50187.2	11130.00
13	53098.84	109.05	0.30 ( 0.28)	0.94	54181.2	12330.00

14	52449.96	115.72	0.30	( 0.28)	0.94	57524.3	12400.00
15	51426.75	124.44	0.30	( 0.28)	0.94	60893.1	12201.00
16	49933.87	133.86	0.30	( 0.28)	0.94	63347.3	12101.10
17	49255.12	137.92	0.30	( 0.28)	0.94	64196.3	10400.00
18	47420.89	146.06	0.30	( 0.28)	0.94	65511.5	12010.00
19	45914.79	152.03	0.30	( 0.28)	0.94	65825.2	10210.00
20	41585.24	178.38	0.30	( 0.28)	0.95	66557.9	10100.00

TOTAL AREA (ACRES) = 66557.9

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13700.00 TO NODE 13720.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 170.00 DOWNSTREAM (FEET) = 165.51  
CHANNEL LENGTH THRU SUBAREA (FEET) = 1891.83 CHANNEL SLOPE = 0.0024  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 15.38  
CHANNEL FLOW THRU SUBAREA (CFS) = 53687.90  
FLOW VELOCITY (FEET/SEC.) = 12.60 FLOW DEPTH (FEET) = 15.38  
TRAVEL TIME (MIN.) = 2.50 Tc (MIN.) = 103.93  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126443.80 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	31135.07	20.88	2.341	0.30 ( 0.25)	0.83	5360.1	300.00
2	35127.45	30.24	1.853	0.30 ( 0.25)	0.82	8888.0	110.00
3	37783.12	36.69	1.688	0.30 ( 0.25)	0.83	11789.3	130.00
4	39878.66	41.87	1.564	0.30 ( 0.25)	0.84	14293.0	150.00
5	43148.36	55.56	1.327	0.30 ( 0.26)	0.87	21358.0	390.00
6	45479.29	66.69	1.231	0.30 ( 0.27)	0.89	27390.0	13100.00
7	47160.15	73.10	1.187	0.30 ( 0.27)	0.90	30461.5	11801.00
8	49573.90	82.35	1.125	0.30 ( 0.27)	0.91	35506.8	11530.00
9	50907.76	88.04	1.086	0.30 ( 0.27)	0.91	39376.1	13510.00
10	51922.20	92.63	1.061	0.30 ( 0.28)	0.92	42408.3	13010.00
11	53046.66	97.66	1.038	0.30 ( 0.28)	0.92	45756.2	11330.00
12	53687.90	103.93	1.009	0.30 ( 0.28)	0.93	50187.2	11130.00
13	53098.84	111.56	0.975	0.30 ( 0.28)	0.94	54181.2	12330.00
14	52449.96	118.24	0.944	0.30 ( 0.28)	0.94	57524.3	12400.00
15	51426.75	126.97	0.918	0.30 ( 0.28)	0.94	60893.1	12201.00
16	49933.87	136.41	0.893	0.30 ( 0.28)	0.94	63347.3	12101.10
17	49255.12	140.49	0.883	0.30 ( 0.28)	0.94	64196.3	10400.00
18	47420.89	148.66	0.861	0.30 ( 0.28)	0.94	65511.5	12010.00
19	45914.79	154.65	0.846	0.30 ( 0.28)	0.94	65825.2	10210.00
20	41585.24	181.09	0.779	0.30 ( 0.28)	0.95	66557.9	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 53687.90 Tc (MIN.) = 103.93  
AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA (ACRES) = 50187.20

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13700.00 TO NODE 13720.00 IS CODE = 12  
-----

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13720.00 TO NODE 13720.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 3 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: 0506102B.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	406.54	14.41	0.30 ( 0.29)	0.96	189.8	10230.00
2	372.26	23.72	0.30 ( 0.29)	0.95	240.3	10200.00
3	368.40	24.34	0.30 ( 0.29)	0.95	241.8	10250.00
4	339.08	28.10	0.30 ( 0.29)	0.95	246.3	10220.00

TOTAL AREA (ACRES) = 246.3

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13720.00 TO NODE 13720.00 IS CODE = 11  
-----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	31135.07	20.88	2.341	0.30 ( 0.25)	0.83	5360.1	300.00
2	35127.45	30.24	1.853	0.30 ( 0.25)	0.82	8888.0	110.00
3	37783.12	36.69	1.688	0.30 ( 0.25)	0.83	11789.3	130.00
4	39878.66	41.87	1.564	0.30 ( 0.25)	0.84	14293.0	150.00
5	43148.36	55.56	1.327	0.30 ( 0.26)	0.87	21358.0	390.00
6	45479.29	66.69	1.231	0.30 ( 0.27)	0.89	27390.0	13100.00
7	47160.15	73.10	1.187	0.30 ( 0.27)	0.90	30461.5	11801.00
8	49573.90	82.35	1.125	0.30 ( 0.27)	0.91	35506.8	11530.00
9	50907.76	88.04	1.086	0.30 ( 0.27)	0.91	39376.1	13510.00
10	51922.20	92.63	1.061	0.30 ( 0.28)	0.92	42408.3	13010.00
11	53046.66	97.66	1.038	0.30 ( 0.28)	0.92	45756.2	11330.00
12	53687.90	103.93	1.009	0.30 ( 0.28)	0.93	50187.2	11130.00
13	53098.84	111.56	0.975	0.30 ( 0.28)	0.94	54181.2	12330.00
14	52449.96	118.24	0.944	0.30 ( 0.28)	0.94	57524.3	12400.00
15	51426.75	126.97	0.918	0.30 ( 0.28)	0.94	60893.1	12201.00
16	49933.87	136.41	0.893	0.30 ( 0.28)	0.94	63347.3	12101.10
17	49255.12	140.49	0.883	0.30 ( 0.28)	0.94	64196.3	10400.00
18	47420.89	148.66	0.861	0.30 ( 0.28)	0.94	65511.5	12010.00
19	45914.79	154.65	0.846	0.30 ( 0.28)	0.94	65825.2	10210.00
20	41585.24	181.09	0.779	0.30 ( 0.28)	0.95	66557.9	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126443.80 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	406.54	14.41	2.998	0.30 ( 0.29)	0.96	189.8	10230.00
2	372.26	23.72	2.161	0.30 ( 0.29)	0.95	240.3	10200.00
3	368.40	24.34	2.122	0.30 ( 0.29)	0.95	241.8	10250.00
4	339.08	28.10	1.943	0.30 ( 0.29)	0.95	246.3	10220.00

LONGEST FLOWPATH FROM NODE 10200.00 TO NODE 13720.00 = 9099.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM	Q	Tc	Intensity	Fp (Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	---------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	28631.53	14.41	2.998	0.30 ( 0.25)	0.83	3888.9 10230.00
2	31517.78	20.88	2.341	0.30 ( 0.25)	0.83	5585.1 300.00
3	32718.02	23.72	2.161	0.30 ( 0.25)	0.83	6670.3 10200.00
4	32980.15	24.34	2.122	0.30 ( 0.25)	0.83	6906.8 10250.00
5	34554.91	28.10	1.943	0.30 ( 0.25)	0.83	8328.7 10220.00
6	35448.11	30.24	1.853	0.30 ( 0.25)	0.83	9134.2 110.00
7	38070.11	36.69	1.688	0.30 ( 0.25)	0.83	12035.5 130.00
8	40140.23	41.87	1.564	0.30 ( 0.25)	0.84	14539.3 150.00
9	43361.38	55.56	1.327	0.30 ( 0.26)	0.87	21604.2 390.00
10	45672.61	66.69	1.231	0.30 ( 0.27)	0.89	27636.2 13100.00
11	47344.59	73.10	1.187	0.30 ( 0.27)	0.90	30707.8 11801.00
12	49745.53	82.35	1.125	0.30 ( 0.27)	0.91	35753.0 11530.00
13	51071.52	88.04	1.086	0.30 ( 0.27)	0.91	39622.4 13510.00
14	52080.78	92.63	1.061	0.30 ( 0.28)	0.92	42654.6 13010.00
15	53200.54	97.66	1.038	0.30 ( 0.28)	0.92	46002.5 11330.00
16	53835.92	103.93	1.009	0.30 ( 0.28)	0.93	50433.5 11130.00
17	53239.74	111.56	0.975	0.30 ( 0.28)	0.94	54427.4 12330.00
18	52584.62	118.24	0.944	0.30 ( 0.28)	0.94	57770.6 12400.00
19	51556.05	126.97	0.918	0.30 ( 0.28)	0.94	61139.4 12201.00
20	50058.14	136.41	0.893	0.30 ( 0.28)	0.94	63593.5 12101.10
21	49377.22	140.49	0.883	0.30 ( 0.28)	0.94	64442.6 10400.00
22	47538.64	148.66	0.861	0.30 ( 0.28)	0.94	65757.7 12010.00
23	46029.36	154.65	0.846	0.30 ( 0.28)	0.94	66071.4 10210.00
24	41686.07	181.09	0.779	0.30 ( 0.28)	0.95	66804.2 10100.00

TOTAL AREA (ACRES) = 66804.2

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 53835.92 Tc (MIN.) = 103.935  
EFFECTIVE AREA (ACRES) = 50433.46 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.91  
TOTAL AREA (ACRES) = 66804.2  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13720.00 = 126443.80 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13720.00 TO NODE 13740.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 165.51 DOWNSTREAM (FEET) = 161.03  
CHANNEL LENGTH THRU SUBAREA (FEET) = 2067.54 CHANNEL SLOPE = 0.0022  
GIVEN CHANNEL BASE (FEET) = 200.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 5.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 15.80  
CHANNEL FLOW THRU SUBAREA (CFS) = 53835.92  
FLOW VELOCITY (FEET/SEC.) = 12.22 FLOW DEPTH (FEET) = 15.80  
TRAVEL TIME (MIN.) = 2.82 Tc (MIN.) = 106.76  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128511.34 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28631.53	17.84	2.614	0.30 ( 0.25)	0.83	3888.9	10230.00
2	31517.78	24.21	2.130	0.30 ( 0.25)	0.83	5585.1	300.00
3	32718.02	27.01	1.991	0.30 ( 0.25)	0.83	6670.3	10200.00
4	32980.15	27.62	1.964	0.30 ( 0.25)	0.83	6906.8	10250.00
5	34554.91	31.33	1.825	0.30 ( 0.25)	0.83	8328.7	10220.00

6	35448.11	33.44	1.771	0.30 ( 0.25)	0.83	9134.2	110.00
7	38070.11	39.82	1.608	0.30 ( 0.25)	0.83	12035.5	130.00
8	40140.23	44.95	1.499	0.30 ( 0.25)	0.84	14539.3	150.00
9	43361.38	58.58	1.292	0.30 ( 0.26)	0.87	21604.2	390.00
10	45672.61	69.66	1.211	0.30 ( 0.27)	0.89	27636.2	13100.00
11	47344.59	76.04	1.167	0.30 ( 0.27)	0.90	30707.8	11801.00
12	49745.53	85.24	1.105	0.30 ( 0.27)	0.91	35753.0	11530.00
13	51071.52	90.90	1.069	0.30 ( 0.27)	0.91	39622.4	13510.00
14	52080.78	95.48	1.048	0.30 ( 0.28)	0.92	42654.6	13010.00
15	53200.54	100.49	1.025	0.30 ( 0.28)	0.92	46002.5	11330.00
16	53835.92	106.76	0.996	0.30 ( 0.28)	0.93	50433.5	11130.00
17	53239.74	114.39	0.962	0.30 ( 0.28)	0.94	54427.4	12330.00
18	52584.62	121.08	0.933	0.30 ( 0.28)	0.94	57770.6	12400.00
19	51556.05	129.83	0.910	0.30 ( 0.28)	0.94	61139.4	12201.00
20	50058.14	139.30	0.886	0.30 ( 0.28)	0.94	63593.5	12101.10
21	49377.22	143.38	0.875	0.30 ( 0.28)	0.94	64442.6	10400.00
22	47538.64	151.59	0.854	0.30 ( 0.28)	0.94	65757.7	12010.00
23	46029.36	157.61	0.838	0.30 ( 0.28)	0.94	66071.4	10210.00
24	41686.07	184.14	0.775	0.30 ( 0.28)	0.95	66804.2	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 53835.92 Tc (MIN.) = 106.76  
AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA (ACRES) = 50433.46

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13720.00 TO NODE 13740.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<<

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13740.00 TO NODE 13740.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<<

PEAK FLOWRATE TABLE FILE NAME: 0506103B.DNA  
MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	810.21	17.74	0.30 ( 0.23)	0.76	399.5	10300.00
2	813.53	18.53	0.30 ( 0.23)	0.76	413.0	10380.00
3	800.95	20.83	0.30 ( 0.23)	0.76	438.9	10320.00
4	771.92	23.06	0.30 ( 0.23)	0.76	451.6	10360.00
5	728.08	25.86	0.30 ( 0.23)	0.76	460.8	10340.00
TOTAL AREA (ACRES) =						460.8

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13740.00 TO NODE 13740.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28631.53	17.84	2.614	0.30 ( 0.25)	0.83	3888.9	10230.00
2	31517.78	24.21	2.130	0.30 ( 0.25)	0.83	5585.1	300.00
3	32718.02	27.01	1.991	0.30 ( 0.25)	0.83	6670.3	10200.00

4	32980.15	27.62	1.964	0.30 ( 0.25)	0.83	6906.8	10250.00
5	34554.91	31.33	1.825	0.30 ( 0.25)	0.83	8328.7	10220.00
6	35448.11	33.44	1.771	0.30 ( 0.25)	0.83	9134.2	110.00
7	38070.11	39.82	1.608	0.30 ( 0.25)	0.83	12035.5	130.00
8	40140.23	44.95	1.499	0.30 ( 0.25)	0.84	14539.3	150.00
9	43361.38	58.58	1.292	0.30 ( 0.26)	0.87	21604.2	390.00
10	45672.61	69.66	1.211	0.30 ( 0.27)	0.89	27636.2	13100.00
11	47344.59	76.04	1.167	0.30 ( 0.27)	0.90	30707.8	11801.00
12	49745.53	85.24	1.105	0.30 ( 0.27)	0.91	35753.0	11530.00
13	51071.52	90.90	1.069	0.30 ( 0.27)	0.91	39622.4	13510.00
14	52080.78	95.48	1.048	0.30 ( 0.28)	0.92	42654.6	13010.00
15	53200.54	100.49	1.025	0.30 ( 0.28)	0.92	46002.5	11330.00
16	53835.92	106.76	0.996	0.30 ( 0.28)	0.93	50433.5	11130.00
17	53239.74	114.39	0.962	0.30 ( 0.28)	0.94	54427.4	12330.00
18	52584.62	121.08	0.933	0.30 ( 0.28)	0.94	57770.6	12400.00
19	51556.05	129.83	0.910	0.30 ( 0.28)	0.94	61139.4	12201.00
20	50058.14	139.30	0.886	0.30 ( 0.28)	0.94	63593.5	12101.10
21	49377.22	143.38	0.875	0.30 ( 0.28)	0.94	64442.6	10400.00
22	47538.64	151.59	0.854	0.30 ( 0.28)	0.94	65757.7	12010.00
23	46029.36	157.61	0.838	0.30 ( 0.28)	0.94	66071.4	10210.00
24	41686.07	184.14	0.775	0.30 ( 0.28)	0.95	66804.2	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128511.34 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	810.21	17.74	2.623	0.30 ( 0.23)	0.76	399.5	10300.00
2	813.53	18.53	2.544	0.30 ( 0.23)	0.76	413.0	10380.00
3	800.95	20.83	2.345	0.30 ( 0.23)	0.76	438.9	10320.00
4	771.92	23.06	2.203	0.30 ( 0.23)	0.76	451.6	10360.00
5	728.08	25.86	2.042	0.30 ( 0.23)	0.76	460.8	10340.00

LONGEST FLOWPATH FROM NODE 10320.00 TO NODE 13740.00 = 8457.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	29403.22	17.74	2.623	0.30 ( 0.25)	0.82	4267.2	10300.00
2	29442.14	17.84	2.614	0.30 ( 0.25)	0.82	4290.1	10230.00
3	29759.18	18.53	2.544	0.30 ( 0.25)	0.82	4486.5	10380.00
4	30785.92	20.83	2.345	0.30 ( 0.25)	0.82	5123.2	10320.00
5	31766.62	23.06	2.203	0.30 ( 0.25)	0.83	5729.3	10360.00
6	32271.69	24.21	2.130	0.30 ( 0.25)	0.83	6040.5	300.00
7	32955.51	25.86	2.042	0.30 ( 0.25)	0.82	6687.5	10340.00
8	33425.80	27.01	1.991	0.30 ( 0.25)	0.82	7131.1	10200.00
9	33677.00	27.62	1.964	0.30 ( 0.25)	0.82	7367.6	10250.00
10	35195.91	31.33	1.825	0.30 ( 0.25)	0.82	8789.5	10220.00
11	36067.50	33.44	1.771	0.30 ( 0.25)	0.82	9595.0	110.00
12	38624.15	39.82	1.608	0.30 ( 0.25)	0.83	12496.3	130.00
13	40650.11	44.95	1.499	0.30 ( 0.25)	0.84	15000.1	150.00
14	43788.45	58.58	1.292	0.30 ( 0.26)	0.87	22065.0	390.00
15	46066.86	69.66	1.211	0.30 ( 0.27)	0.89	28097.0	13100.00
16	47721.51	76.04	1.167	0.30 ( 0.27)	0.89	31168.6	11801.00
17	50097.43	85.24	1.105	0.30 ( 0.27)	0.91	36213.8	11530.00
18	51408.84	90.90	1.069	0.30 ( 0.27)	0.91	40083.2	13510.00
19	52409.69	95.48	1.048	0.30 ( 0.28)	0.92	43115.4	13010.00
20	53520.27	100.49	1.025	0.30 ( 0.28)	0.92	46463.3	11330.00
21	54144.16	106.76	0.996	0.30 ( 0.28)	0.93	50894.3	11130.00
22	53533.98	114.39	0.962	0.30 ( 0.28)	0.93	54888.2	12330.00

23	52867.43	121.08	0.933	0.30 ( 0.28)	0.94	58231.4	12400.00
24	51829.73	129.83	0.910	0.30 ( 0.28)	0.94	61600.2	12201.00
25	50321.93	139.30	0.886	0.30 ( 0.28)	0.94	64054.3	12101.10
26	49636.75	143.38	0.875	0.30 ( 0.28)	0.94	64903.4	10400.00
27	47789.60	151.59	0.854	0.30 ( 0.28)	0.94	66218.5	12010.00
28	46274.02	157.61	0.838	0.30 ( 0.28)	0.94	66532.2	10210.00
29	41905.46	184.14	0.775	0.30 ( 0.28)	0.94	67265.0	10100.00

TOTAL AREA (ACRES) = 67265.0

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 54144.16 Tc (MIN.) = 106.755  
EFFECTIVE AREA (ACRES) = 50894.26 AREA-AVERAGED Fm (INCH/HR) = 0.28  
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.89  
TOTAL AREA (ACRES) = 67265.0  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13740.00 = 128511.34 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13740.00 TO NODE 13741.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM (FEET) = 161.03 DOWNSTREAM (FEET) = 141.00  
CHANNEL LENGTH THRU SUBAREA (FEET) = 364.08 CHANNEL SLOPE = 0.0550  
GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0  
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT (FEET) = 9.18  
CHANNEL FLOW THRU SUBAREA (CFS) = 54144.16  
FLOW VELOCITY (FEET/SEC.) = 43.12 FLOW DEPTH (FEET) = 9.18  
TRAVEL TIME (MIN.) = 0.14 Tc (MIN.) = 106.90  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128875.41 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	29403.22	17.91	2.606	0.30 ( 0.25)	0.82	4267.2	10300.00
2	29442.14	18.01	2.597	0.30 ( 0.25)	0.82	4290.1	10230.00
3	29759.18	18.70	2.527	0.30 ( 0.25)	0.82	4486.5	10380.00
4	30785.92	21.00	2.334	0.30 ( 0.25)	0.82	5123.2	10320.00
5	31766.62	23.22	2.193	0.30 ( 0.25)	0.83	5729.3	10360.00
6	32271.69	24.37	2.120	0.30 ( 0.25)	0.83	6040.5	300.00
7	32955.51	26.03	2.035	0.30 ( 0.25)	0.82	6687.5	10340.00
8	33425.80	27.17	1.984	0.30 ( 0.25)	0.82	7131.1	10200.00
9	33677.00	27.79	1.957	0.30 ( 0.25)	0.82	7367.6	10250.00
10	35195.91	31.49	1.821	0.30 ( 0.25)	0.82	8789.5	10220.00
11	36067.50	33.60	1.767	0.30 ( 0.25)	0.82	9595.0	110.00
12	38624.15	39.98	1.604	0.30 ( 0.25)	0.83	12496.3	130.00
13	40650.11	45.11	1.495	0.30 ( 0.25)	0.84	15000.1	150.00
14	43788.45	58.73	1.291	0.30 ( 0.26)	0.87	22065.0	390.00
15	46066.86	69.80	1.210	0.30 ( 0.27)	0.89	28097.0	13100.00
16	47721.51	76.18	1.166	0.30 ( 0.27)	0.89	31168.6	11801.00
17	50097.43	85.39	1.104	0.30 ( 0.27)	0.91	36213.8	11530.00
18	51408.84	91.04	1.068	0.30 ( 0.27)	0.91	40083.2	13510.00
19	52409.69	95.63	1.047	0.30 ( 0.28)	0.92	43115.4	13010.00
20	53520.27	100.63	1.024	0.30 ( 0.28)	0.92	46463.3	11330.00
21	54144.16	106.90	0.996	0.30 ( 0.28)	0.93	50894.3	11130.00
22	53533.98	114.53	0.961	0.30 ( 0.28)	0.93	54888.2	12330.00
23	52867.43	121.22	0.933	0.30 ( 0.28)	0.94	58231.4	12400.00

24	51829.73	129.97	0.910	0.30( 0.28)	0.94	61600.2	12201.00
25	50321.93	139.44	0.885	0.30( 0.28)	0.94	64054.3	12101.10
26	49636.75	143.53	0.875	0.30( 0.28)	0.94	64903.4	10400.00
27	47789.60	151.73	0.853	0.30( 0.28)	0.94	66218.5	12010.00
28	46274.02	157.76	0.838	0.30( 0.28)	0.94	66532.2	10210.00
29	41905.46	184.29	0.775	0.30( 0.28)	0.94	67265.0	10100.00

NEW PEAK FLOW DATA ARE:  
 PEAK FLOW RATE(CFS) = 54144.16 Tc(MIN.) = 106.90  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 50894.26

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13740.00 TO NODE 13741.00 IS CODE = 12  
 -----  
 >>>>CLEAR MEMORY BANK # 3 <<<<<<  
 =====

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13741.00 TO NODE 13741.00 IS CODE = 15.1  
 -----  
 >>>>DEFINE MEMORY BANK # 3 <<<<<<  
 =====

PEAK FLOWRATE TABLE FILE NAME: 0506104B.DNA  
 MEMORY BANK # 3 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	82.60	19.10	2.487	0.30( 0.24)	0.80	44.3	10400.00
TOTAL AREA(ACRES) =							44.3

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13741.00 TO NODE 13741.00 IS CODE = 11  
 -----  
 >>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<<  
 =====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	29403.22	17.91	2.606	0.30( 0.25)	0.82	4267.2	10300.00
2	29442.14	18.01	2.597	0.30( 0.25)	0.82	4290.1	10230.00
3	29759.18	18.70	2.527	0.30( 0.25)	0.82	4486.5	10380.00
4	30785.92	21.00	2.334	0.30( 0.25)	0.82	5123.2	10320.00
5	31766.62	23.22	2.193	0.30( 0.25)	0.83	5729.3	10360.00
6	32271.69	24.37	2.120	0.30( 0.25)	0.83	6040.5	300.00
7	32955.51	26.03	2.035	0.30( 0.25)	0.82	6687.5	10340.00
8	33425.80	27.17	1.984	0.30( 0.25)	0.82	7131.1	10200.00
9	33677.00	27.79	1.957	0.30( 0.25)	0.82	7367.6	10250.00
10	35195.91	31.49	1.821	0.30( 0.25)	0.82	8789.5	10220.00
11	36067.50	33.60	1.767	0.30( 0.25)	0.82	9595.0	110.00
12	38624.15	39.98	1.604	0.30( 0.25)	0.83	12496.3	130.00
13	40650.11	45.11	1.495	0.30( 0.25)	0.84	15000.1	150.00
14	43788.45	58.73	1.291	0.30( 0.26)	0.87	22065.0	390.00
15	46066.86	69.80	1.210	0.30( 0.27)	0.89	28097.0	13100.00
16	47721.51	76.18	1.166	0.30( 0.27)	0.89	31168.6	11801.00
17	50097.43	85.39	1.104	0.30( 0.27)	0.91	36213.8	11530.00
18	51408.84	91.04	1.068	0.30( 0.27)	0.91	40083.2	13510.00
19	52409.69	95.63	1.047	0.30( 0.28)	0.92	43115.4	13010.00
20	53520.27	100.63	1.024	0.30( 0.28)	0.92	46463.3	11330.00

21	54144.16	106.90	0.996	0.30( 0.28)	0.93	50894.3	11130.00
22	53533.98	114.53	0.961	0.30( 0.28)	0.93	54888.2	12330.00
23	52867.43	121.22	0.933	0.30( 0.28)	0.94	58231.4	12400.00
24	51829.73	129.97	0.910	0.30( 0.28)	0.94	61600.2	12201.00
25	50321.93	139.44	0.885	0.30( 0.28)	0.94	64054.3	12101.10
26	49636.75	143.53	0.875	0.30( 0.28)	0.94	64903.4	10400.00
27	47789.60	151.73	0.853	0.30( 0.28)	0.94	66218.5	12010.00
28	46274.02	157.76	0.838	0.30( 0.28)	0.94	66532.2	10210.00
29	41905.46	184.29	0.775	0.30( 0.28)	0.94	67265.0	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128875.41 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*  
 STREAM Q Tc Intensity Fp(Fm) Ap Ae HEADWATER  
 NUMBER (CFS) (MIN.) (INCH/HR) (INCH/HR) (ACRES) NODE  
 1 82.60 19.10 2.487 0.30( 0.24) 0.80 44.3 10400.00  
 LONGEST FLOWPATH FROM NODE 10400.00 TO NODE 13741.00 = 6237.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	29484.79	17.91	2.606	0.30( 0.25)	0.82	4308.7	10300.00
2	29523.82	18.01	2.597	0.30( 0.25)	0.82	4331.8	10230.00
3	29841.49	18.70	2.527	0.30( 0.25)	0.82	4529.9	10380.00
4	30019.35	19.10	2.487	0.30( 0.25)	0.82	4640.9	10400.00
5	30862.88	21.00	2.334	0.30( 0.25)	0.82	5167.5	10320.00
6	31838.40	23.22	2.193	0.30( 0.25)	0.83	5773.6	10360.00
7	32340.78	24.37	2.120	0.30( 0.25)	0.83	6084.8	300.00
8	33021.48	26.03	2.035	0.30( 0.25)	0.82	6731.8	10340.00
9	33489.90	27.17	1.984	0.30( 0.25)	0.82	7175.4	10200.00
10	33740.11	27.79	1.957	0.30( 0.25)	0.82	7411.9	10250.00
11	35254.02	31.49	1.821	0.30( 0.25)	0.82	8833.8	10220.00
12	36123.63	33.60	1.767	0.30( 0.25)	0.82	9639.3	110.00
13	38674.31	39.98	1.604	0.30( 0.25)	0.83	12540.6	130.00
14	40696.25	45.11	1.495	0.30( 0.25)	0.84	15044.4	150.00
15	43827.08	58.73	1.291	0.30( 0.26)	0.87	22109.3	390.00
16	46102.52	69.80	1.210	0.30( 0.27)	0.89	28141.3	13100.00
17	47755.57	76.18	1.166	0.30( 0.27)	0.89	31212.9	11801.00
18	50129.21	85.39	1.104	0.30( 0.27)	0.91	36258.1	11530.00
19	51439.29	91.04	1.068	0.30( 0.27)	0.91	40127.5	13510.00
20	52439.38	95.63	1.047	0.30( 0.28)	0.92	43159.7	13010.00
21	53549.12	100.63	1.024	0.30( 0.28)	0.92	46507.6	11330.00
22	54171.95	106.90	0.996	0.30( 0.28)	0.93	50938.6	11130.00
23	53560.50	114.53	0.961	0.30( 0.28)	0.93	54932.5	12330.00
24	52892.91	121.22	0.933	0.30( 0.28)	0.94	58275.7	12400.00
25	51854.37	129.97	0.910	0.30( 0.28)	0.94	61644.5	12201.00
26	50345.67	139.44	0.885	0.30( 0.28)	0.94	64098.6	12101.10
27	49660.10	143.53	0.875	0.30( 0.28)	0.94	64947.7	10400.00
28	47812.16	151.73	0.853	0.30( 0.28)	0.94	66262.8	12010.00
29	46296.01	157.76	0.838	0.30( 0.28)	0.94	66576.5	10210.00
30	41925.14	184.29	0.775	0.30( 0.28)	0.94	67309.3	10100.00
TOTAL AREA(ACRES) =						67309.3	

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:  
 PEAK FLOW RATE(CFS) = 54171.95 Tc(MIN.) = 106.896  
 EFFECTIVE AREA(ACRES) = 50938.56 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 67309.3  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13741.00 = 128875.41 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13741.00 TO NODE 13802.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 141.00 DOWNSTREAM(FEET) = 135.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1533.41 CHANNEL SLOPE = 0.0039
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
\*ESTIMATED CHANNEL HEIGHT(FEET) = 18.46
CHANNEL FLOW THRU SUBAREA(CFS) = 54171.95
FLOW VELOCITY(FEET/SEC.) = 16.88 FLOW DEPTH(FEET) = 18.46
TRAVEL TIME(MIN.) = 1.51 Tc(MIN.) = 108.41
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130408.82 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 30 rows of data.

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 54171.95 Tc(MIN.) = 108.41
AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 50938.56

\*\*\*\*\*

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 12

>>>>CLEAR MEMORY BANK # 3 <<<<

\*\*\*\*\*

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 15.1

>>>>DEFINE MEMORY BANK # 3 <<<<

PEAK FLOWRATE TABLE FILE NAME: 0506105I.DNA

MEMORY BANK # 3 DEFINED AS FOLLOWS:

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 2 rows of data and a total area calculation.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13802.00 TO NODE 13802.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

Table with 8 columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp(Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 30 rows of data.

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130408.82 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*



STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	447.60	14.36	3.006	0.30( 0.27)	0.90	208.7	10520.00
2	533.75	30.45	1.848	0.30( 0.28)	0.93	403.6	10500.00

LONGEST FLOWPATH FROM NODE 10500.00 TO NODE 13802.00 = 12187.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27648.20	14.36	3.006	0.30( 0.25)	0.83	3348.1	10520.00
2	29961.04	19.71	2.426	0.30( 0.25)	0.83	4582.3	10300.00
3	30000.59	19.81	2.416	0.30( 0.25)	0.83	4606.5	10230.00
4	30321.94	20.50	2.366	0.30( 0.25)	0.83	4812.9	10380.00
5	30501.90	20.89	2.341	0.30( 0.25)	0.83	4928.7	10400.00
6	31355.51	22.77	2.221	0.30( 0.25)	0.83	5478.0	10320.00
7	32342.86	24.98	2.081	0.30( 0.25)	0.83	6110.9	10360.00
8	32851.37	26.13	2.030	0.30( 0.25)	0.83	6436.0	300.00
9	33540.87	27.77	1.958	0.30( 0.25)	0.83	7102.9	10340.00
10	34015.38	28.91	1.907	0.30( 0.25)	0.83	7560.3	10200.00
11	34268.86	29.52	1.880	0.30( 0.25)	0.83	7804.2	10250.00
12	34657.57	30.45	1.848	0.30( 0.25)	0.83	8175.9	10500.00
13	35763.90	33.20	1.777	0.30( 0.25)	0.83	9237.4	10220.00
14	36615.32	35.30	1.724	0.30( 0.25)	0.83	10042.9	110.00
15	39113.33	41.64	1.569	0.30( 0.25)	0.83	12944.2	130.00
16	41098.32	46.75	1.460	0.30( 0.25)	0.84	15448.0	150.00
17	44165.71	60.33	1.274	0.30( 0.26)	0.87	22512.9	390.00
18	46415.70	71.39	1.199	0.30( 0.27)	0.89	28544.9	13100.00
19	48054.12	77.75	1.156	0.30( 0.27)	0.89	31616.5	11801.00
20	50406.63	86.93	1.094	0.30( 0.27)	0.91	36661.7	11530.00
21	51705.64	92.58	1.061	0.30( 0.27)	0.91	40531.1	13510.00
22	52698.63	97.15	1.040	0.30( 0.28)	0.92	43563.3	13010.00
23	53800.61	102.15	1.018	0.30( 0.28)	0.92	46911.2	11330.00
24	54413.71	108.41	0.989	0.30( 0.28)	0.93	51342.2	11130.00
25	53790.40	116.05	0.954	0.30( 0.28)	0.93	55336.1	12330.00
26	53114.26	122.74	0.929	0.30( 0.28)	0.94	58679.3	12400.00
27	52067.96	131.51	0.906	0.30( 0.28)	0.94	62048.1	12201.00
28	50550.88	140.98	0.881	0.30( 0.28)	0.94	64502.2	12101.10
29	49861.69	145.08	0.871	0.30( 0.28)	0.94	65351.3	10400.00
30	48006.49	153.30	0.849	0.30( 0.28)	0.94	66666.4	12010.00
31	46485.00	159.34	0.834	0.30( 0.28)	0.94	66980.1	10210.00
32	42093.55	185.92	0.773	0.30( 0.28)	0.94	67712.9	10100.00

TOTAL AREA (ACRES) = 67712.9

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 54413.71 Tc(MIN.) = 108.410  
EFFECTIVE AREA(ACRES) = 51342.16 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
TOTAL AREA (ACRES) = 67712.9  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13802.00 = 130408.82 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13802.00 TO NODE 13803.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<

ELEVATION DATA: UPSTREAM(FEET) = 135.00 DOWNSTREAM(FEET) = 133.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 207.23 CHANNEL SLOPE = 0.0097

GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 14.67  
CHANNEL FLOW THRU SUBAREA(CFS) = 54413.71  
FLOW VELOCITY(FEET/SEC.) = 23.38 FLOW DEPTH(FEET) = 14.67  
TRAVEL TIME(MIN.) = 0.15 Tc(MIN.) = 108.56  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130616.05 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27648.20	14.54	2.975	0.30( 0.25)	0.83	3348.1	10520.00
2	29961.04	19.89	2.408	0.30( 0.25)	0.83	4582.3	10300.00
3	30000.59	19.99	2.398	0.30( 0.25)	0.83	4606.5	10230.00
4	30321.94	20.67	2.354	0.30( 0.25)	0.83	4812.9	10380.00
5	30501.90	21.06	2.330	0.30( 0.25)	0.83	4928.7	10400.00
6	31355.51	22.94	2.210	0.30( 0.25)	0.83	5478.0	10320.00
7	32342.86	25.15	2.073	0.30( 0.25)	0.83	6110.9	10360.00
8	32851.37	26.30	2.023	0.30( 0.25)	0.83	6436.0	300.00
9	33540.87	27.94	1.950	0.30( 0.25)	0.83	7102.9	10340.00
10	34015.38	29.07	1.900	0.30( 0.25)	0.83	7560.3	10200.00
11	34268.86	29.68	1.873	0.30( 0.25)	0.83	7804.2	10250.00
12	34657.57	30.62	1.843	0.30( 0.25)	0.83	8175.9	10500.00
13	35763.90	33.37	1.773	0.30( 0.25)	0.83	9237.4	10220.00
14	36615.32	35.47	1.720	0.30( 0.25)	0.83	10042.9	110.00
15	39113.33	41.81	1.566	0.30( 0.25)	0.83	12944.2	130.00
16	41098.32	46.91	1.457	0.30( 0.25)	0.84	15448.0	150.00
17	44165.71	60.49	1.273	0.30( 0.26)	0.87	22512.9	390.00
18	46415.70	71.54	1.198	0.30( 0.27)	0.89	28544.9	13100.00
19	48054.12	77.90	1.155	0.30( 0.27)	0.89	31616.5	11801.00
20	50406.63	87.08	1.093	0.30( 0.27)	0.91	36661.7	11530.00
21	51705.64	92.73	1.061	0.30( 0.27)	0.91	40531.1	13510.00
22	52698.63	97.30	1.040	0.30( 0.28)	0.92	43563.3	13010.00
23	53800.61	102.30	1.017	0.30( 0.28)	0.92	46911.2	11330.00
24	54413.71	108.56	0.988	0.30( 0.28)	0.93	51342.2	11130.00
25	53790.40	116.19	0.953	0.30( 0.28)	0.93	55336.1	12330.00
26	53114.26	122.89	0.928	0.30( 0.28)	0.94	58679.3	12400.00
27	52067.96	131.66	0.906	0.30( 0.28)	0.94	62048.1	12201.00
28	50550.88	141.14	0.881	0.30( 0.28)	0.94	64502.2	12101.10
29	49861.69	145.23	0.870	0.30( 0.28)	0.94	65351.3	10400.00
30	48006.49	153.45	0.849	0.30( 0.28)	0.94	66666.4	12010.00
31	46485.00	159.49	0.833	0.30( 0.28)	0.94	66980.1	10210.00
32	42093.55	186.08	0.773	0.30( 0.28)	0.94	67712.9	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 54413.71 Tc(MIN.) = 108.56  
AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 51342.16

\*\*\*\*\*

FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 81

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<

MAINLINE Tc(MIN.) = 108.56

\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 0.988

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

RESIDENTIAL  
 "1 DWELLING/ACRE" B 48.80 0.30 0.800 56  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.800  
 SUBAREA AREA (ACRES) = 48.80 SUBAREA RUNOFF(CFS) = 32.86  
 EFFECTIVE AREA(ACRES) = 51390.96 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 67761.7 PEAK FLOW RATE(CFS) = 54413.71  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13802.00 TO NODE 13803.00 IS CODE = 12  
 -----

>>>>CLEAR MEMORY BANK # 3 <<<<<<  
 =====

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 15.1  
 -----

>>>>DEFINE MEMORY BANK # 3 <<<<<<  
 =====

PEAK FLOWRATE TABLE FILE NAME: 0506106B.DNA  
 MEMORY BANK # 3 DEFINED AS FOLLOWS:  

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	73.36	17.31	2.667	0.30 ( 0.20)	0.67	36.9	10600.00
TOTAL AREA(ACRES) =							36.9

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 11  
 -----

>>>>CONFLUENCE MEMORY BANK # 3 WITH THE MAIN-STREAM MEMORY<<<<<<  
 =====

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27648.20	14.54	2.975	0.30 ( 0.25)	0.83	3396.9	10520.00
2	29961.04	19.89	2.408	0.30 ( 0.25)	0.83	4631.1	10300.00
3	30000.59	19.99	2.398	0.30 ( 0.25)	0.83	4655.3	10230.00
4	30321.94	20.67	2.354	0.30 ( 0.25)	0.83	4861.7	10380.00
5	30501.90	21.06	2.330	0.30 ( 0.25)	0.83	4977.5	10400.00
6	31355.51	22.94	2.210	0.30 ( 0.25)	0.83	5526.8	10320.00
7	32342.86	25.15	2.073	0.30 ( 0.25)	0.83	6159.7	10360.00
8	32851.37	26.30	2.023	0.30 ( 0.25)	0.83	6484.8	300.00
9	33540.87	27.94	1.950	0.30 ( 0.25)	0.83	7151.7	10340.00
10	34015.38	29.07	1.900	0.30 ( 0.25)	0.83	7609.1	10200.00
11	34268.86	29.68	1.873	0.30 ( 0.25)	0.83	7853.0	10250.00
12	34657.57	30.62	1.843	0.30 ( 0.25)	0.83	8224.7	10500.00
13	35763.90	33.37	1.773	0.30 ( 0.25)	0.83	9286.2	10220.00
14	36615.32	35.47	1.720	0.30 ( 0.25)	0.83	10091.7	110.00
15	39113.33	41.81	1.566	0.30 ( 0.25)	0.83	12993.0	130.00
16	41098.32	46.91	1.457	0.30 ( 0.25)	0.84	15496.8	150.00
17	44165.71	60.49	1.273	0.30 ( 0.26)	0.87	22561.7	390.00
18	46415.70	71.54	1.198	0.30 ( 0.27)	0.89	28593.7	13100.00
19	48054.12	77.90	1.155	0.30 ( 0.27)	0.89	31665.3	11801.00
20	50406.63	87.08	1.093	0.30 ( 0.27)	0.91	36710.5	11530.00
21	51705.64	92.73	1.061	0.30 ( 0.27)	0.91	40579.9	13510.00

22	52698.63	97.30	1.040	0.30 ( 0.28)	0.92	43612.1	13010.00
23	53800.61	102.30	1.017	0.30 ( 0.28)	0.92	46960.0	11330.00
24	54413.71	108.56	0.988	0.30 ( 0.28)	0.93	51391.0	11130.00
25	53790.40	116.19	0.953	0.30 ( 0.28)	0.93	55384.9	12330.00
26	53114.26	122.89	0.928	0.30 ( 0.28)	0.94	58728.1	12400.00
27	52067.96	131.66	0.906	0.30 ( 0.28)	0.94	62096.9	12201.00
28	50550.88	141.14	0.881	0.30 ( 0.28)	0.94	64551.0	12101.10
29	49861.69	145.23	0.870	0.30 ( 0.28)	0.94	65400.1	10400.00
30	48006.49	153.45	0.849	0.30 ( 0.28)	0.94	66715.2	12010.00
31	46485.00	159.49	0.833	0.30 ( 0.28)	0.94	67028.9	10210.00
32	42093.55	186.08	0.773	0.30 ( 0.28)	0.94	67761.7	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130616.05 FEET.

\*\* MEMORY BANK # 3 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	73.36	17.31	2.667	0.30 ( 0.20)	0.67	36.9	10600.00

LONGEST FLOWPATH FROM NODE 10600.00 TO NODE 13803.00 = 1713.00 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27717.54	14.54	2.975	0.30 ( 0.25)	0.83	3427.9	10520.00
2	28918.01	17.31	2.667	0.30 ( 0.25)	0.83	4072.2	10600.00
3	30026.70	19.89	2.408	0.30 ( 0.25)	0.83	4668.0	10300.00
4	30065.96	19.99	2.398	0.30 ( 0.25)	0.83	4692.2	10230.00
5	30385.99	20.67	2.354	0.30 ( 0.25)	0.83	4898.6	10380.00
6	30565.21	21.06	2.330	0.30 ( 0.25)	0.83	5014.4	10400.00
7	31415.28	22.94	2.210	0.30 ( 0.25)	0.83	5563.7	10320.00
8	32398.55	25.15	2.073	0.30 ( 0.25)	0.83	6196.6	10360.00
9	32905.56	26.30	2.023	0.30 ( 0.25)	0.83	6521.7	300.00
10	33592.89	27.94	1.950	0.30 ( 0.25)	0.83	7188.6	10340.00
11	34065.91	29.07	1.900	0.30 ( 0.25)	0.83	7646.0	10200.00
12	34318.59	29.68	1.873	0.30 ( 0.25)	0.83	7889.9	10250.00
13	34706.43	30.62	1.843	0.30 ( 0.25)	0.83	8261.6	10500.00
14	35810.66	33.37	1.773	0.30 ( 0.25)	0.83	9323.1	10220.00
15	36660.50	35.47	1.720	0.30 ( 0.25)	0.83	10128.6	110.00
16	39153.92	41.81	1.566	0.30 ( 0.25)	0.83	13029.9	130.00
17	41135.68	46.91	1.457	0.30 ( 0.25)	0.84	15533.7	150.00
18	44197.59	60.49	1.273	0.30 ( 0.26)	0.87	22598.6	390.00
19	46445.36	71.54	1.198	0.30 ( 0.27)	0.89	28630.6	13100.00
20	48082.49	77.90	1.155	0.30 ( 0.27)	0.89	31702.2	11801.00
21	50433.16	87.08	1.093	0.30 ( 0.27)	0.91	36747.4	11530.00
22	51731.21	92.73	1.061	0.30 ( 0.27)	0.91	40616.8	13510.00
23	52723.57	97.30	1.040	0.30 ( 0.28)	0.92	43649.0	13010.00
24	53824.88	102.30	1.017	0.30 ( 0.28)	0.92	46996.9	11330.00
25	54437.13	108.56	0.988	0.30 ( 0.28)	0.93	51427.9	11130.00
26	53812.78	116.19	0.953	0.30 ( 0.28)	0.93	55421.8	12330.00
27	53135.90	122.89	0.928	0.30 ( 0.28)	0.94	58765.0	12400.00
28	52088.93	131.66	0.906	0.30 ( 0.28)	0.94	62133.8	12201.00
29	50571.11	141.14	0.881	0.30 ( 0.28)	0.94	64587.9	12101.10
30	49881.61	145.23	0.870	0.30 ( 0.28)	0.94	65437.0	10400.00
31	48025.77	153.45	0.849	0.30 ( 0.28)	0.94	66752.1	12010.00
32	46503.80	159.49	0.833	0.30 ( 0.28)	0.94	67065.8	10210.00
33	42110.57	186.08	0.773	0.30 ( 0.28)	0.94	67798.6	10100.00

TOTAL AREA(ACRES) = 67798.6

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 54437.13 Tc(MIN.) = 108.558  
 EFFECTIVE AREA(ACRES) = 51427.86 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
 TOTAL AREA(ACRES) = 67798.6  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13803.00 = 130616.05 FEET.

=====  
 END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 67798.6 TC(MIN.) = 108.56  
 EFFECTIVE AREA(ACRES) = 51427.86 AREA-AVERAGED Fm(INCH/HR)= 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.929  
 PEAK FLOW RATE(CFS) = 54437.13

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	27717.54	14.54	2.975	0.30( 0.25)	0.83	3427.9	10520.00
2	28918.01	17.31	2.667	0.30( 0.25)	0.83	4072.2	10600.00
3	30026.70	19.89	2.408	0.30( 0.25)	0.83	4668.0	10300.00
4	30065.96	19.99	2.398	0.30( 0.25)	0.83	4692.2	10230.00
5	30385.99	20.67	2.354	0.30( 0.25)	0.83	4898.6	10380.00
6	30565.21	21.06	2.330	0.30( 0.25)	0.83	5014.4	10400.00
7	31415.28	22.94	2.210	0.30( 0.25)	0.83	5563.7	10320.00
8	32398.55	25.15	2.073	0.30( 0.25)	0.83	6196.6	10360.00
9	32905.56	26.30	2.023	0.30( 0.25)	0.83	6521.7	300.00
10	33592.89	27.94	1.950	0.30( 0.25)	0.83	7188.6	10340.00
11	34065.91	29.07	1.900	0.30( 0.25)	0.83	7646.0	10200.00
12	34318.59	29.68	1.873	0.30( 0.25)	0.83	7889.9	10250.00
13	34706.43	30.62	1.843	0.30( 0.25)	0.83	8261.6	10500.00
14	35810.66	33.37	1.773	0.30( 0.25)	0.83	9323.1	10220.00
15	36660.50	35.47	1.720	0.30( 0.25)	0.83	10128.6	110.00
16	39153.92	41.81	1.566	0.30( 0.25)	0.83	13029.9	130.00
17	41135.68	46.91	1.457	0.30( 0.25)	0.84	15533.7	150.00
18	44197.59	60.49	1.273	0.30( 0.26)	0.87	22598.6	390.00
19	46445.36	71.54	1.198	0.30( 0.27)	0.89	28630.6	13100.00
20	48082.49	77.90	1.155	0.30( 0.27)	0.89	31702.2	11801.00
21	50433.16	87.08	1.093	0.30( 0.27)	0.91	36747.4	11530.00
22	51731.21	92.73	1.061	0.30( 0.27)	0.91	40616.8	13510.00
23	52723.57	97.30	1.040	0.30( 0.28)	0.92	43649.0	13010.00
24	53824.88	102.30	1.017	0.30( 0.28)	0.92	46996.9	11330.00
25	54437.13	108.56	0.988	0.30( 0.28)	0.93	51427.9	11130.00
26	53812.78	116.19	0.953	0.30( 0.28)	0.93	55421.8	12330.00
27	53135.90	122.89	0.928	0.30( 0.28)	0.94	58765.0	12400.00
28	52088.93	131.66	0.906	0.30( 0.28)	0.94	62133.8	12201.00
29	50571.11	141.14	0.881	0.30( 0.28)	0.94	64587.9	12101.10
30	49881.61	145.23	0.870	0.30( 0.28)	0.94	65437.0	10400.00
31	48025.77	153.45	0.849	0.30( 0.28)	0.94	66752.1	12010.00
32	46503.80	159.49	0.833	0.30( 0.28)	0.94	67065.8	10210.00
33	42110.57	186.08	0.773	0.30( 0.28)	0.94	67798.6	10100.00

=====  
 END OF RATIONAL METHOD ANALYSIS

\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S38- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 100-YR RM EV APRIL 2019 CCHI \*  
\*\*\*\*\*

FILE NAME: RI00EV38.DAT  
TIME/DATE OF STUDY: 08:52 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 100.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90  
\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.750
- 2) 10.00; 3.727
- 3) 15.00; 2.893
- 4) 20.00; 2.393
- 5) 25.00; 2.078
- 6) 30.00; 1.857
- 7) 40.00; 1.601
- 8) 50.00; 1.389
- 9) 60.00; 1.274
- 10) 90.00; 1.070
- 11) 120.00; 0.933
- 12) 180.00; 0.777
- 13) 360.00; 0.572
- 14) 1200.00; 0.248

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES WIDTH (FT)	LIP (FT)	HIKE (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00	0.0313	0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 15.1  
-----

>>>>DEFINE MEMORY BANK # 1 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME: RI00EV37.DNA  
MEMORY BANK # 1 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28918.01	17.31	0.30 ( 0.25)	0.83	4072.2	10600.00
2	31415.28	22.94	0.30 ( 0.25)	0.83	5563.7	10320.00
3	36660.50	35.47	0.30 ( 0.25)	0.83	10128.6	110.00
4	39153.92	41.81	0.30 ( 0.25)	0.83	13029.9	130.00
5	41135.68	46.91	0.30 ( 0.25)	0.84	15533.7	150.00
6	44197.59	60.49	0.30 ( 0.26)	0.87	22598.6	390.00
7	46445.36	71.54	0.30 ( 0.27)	0.89	28630.6	13100.00
8	48082.49	77.90	0.30 ( 0.27)	0.89	31702.2	11801.00
9	50433.16	87.08	0.30 ( 0.27)	0.91	36747.4	11530.00
10	51731.21	92.73	0.30 ( 0.27)	0.91	40616.8	13510.00
11	52723.57	97.30	0.30 ( 0.28)	0.92	43649.0	13010.00
12	53824.88	102.30	0.30 ( 0.28)	0.92	46996.9	11330.00
13	54437.13	108.56	0.30 ( 0.28)	0.93	51427.9	11130.00
14	53812.78	116.19	0.30 ( 0.28)	0.93	55421.8	12330.00
15	53135.90	122.89	0.30 ( 0.28)	0.94	58765.0	12400.00
16	52088.93	131.66	0.30 ( 0.28)	0.94	62133.8	12201.00
17	50571.11	141.14	0.30 ( 0.28)	0.94	64587.9	12101.10
18	48025.77	153.45	0.30 ( 0.28)	0.94	66752.1	12010.00
19	46503.80	159.49	0.30 ( 0.28)	0.94	67065.8	10210.00
20	42110.57	186.08	0.30 ( 0.28)	0.94	67798.6	10100.00
TOTAL AREA (ACRES) =						67798.6

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13803.00 TO NODE 13803.00 IS CODE = 14.0  
-----

>>>>MEMORY BANK # 1 COPIED ONTO MAIN-STREAM MEMORY<<<<<

=====

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28918.01	17.31	0.30 ( 0.25)	0.83	4072.2	10600.00
2	31415.28	22.94	0.30 ( 0.25)	0.83	5563.7	10320.00
3	36660.50	35.47	0.30 ( 0.25)	0.83	10128.6	110.00
4	39153.92	41.81	0.30 ( 0.25)	0.83	13029.9	130.00
5	41135.68	46.91	0.30 ( 0.25)	0.84	15533.7	150.00
6	44197.59	60.49	0.30 ( 0.26)	0.87	22598.6	390.00
7	46445.36	71.54	0.30 ( 0.27)	0.89	28630.6	13100.00
8	48082.49	77.90	0.30 ( 0.27)	0.89	31702.2	11801.00
9	50433.16	87.08	0.30 ( 0.27)	0.91	36747.4	11530.00
10	51731.21	92.73	0.30 ( 0.27)	0.91	40616.8	13510.00
11	52723.57	97.30	0.30 ( 0.28)	0.92	43649.0	13010.00
12	53824.88	102.30	0.30 ( 0.28)	0.92	46996.9	11330.00
13	54437.13	108.56	0.30 ( 0.28)	0.93	51427.9	11130.00

14	53812.78	116.19	0.30	( 0.28)	0.93	55421.8	12330.00
15	53135.90	122.89	0.30	( 0.28)	0.94	58765.0	12400.00
16	52088.93	131.66	0.30	( 0.28)	0.94	62133.8	12201.00
17	50571.11	141.14	0.30	( 0.28)	0.94	64587.9	12101.10
18	48025.77	153.45	0.30	( 0.28)	0.94	66752.1	12010.00
19	46503.80	159.49	0.30	( 0.28)	0.94	67065.8	10210.00
20	42110.57	186.08	0.30	( 0.28)	0.94	67798.6	10100.00
TOTAL AREA (ACRES) =							67798.6

\*\*\*\*\*

FLOW PROCESS FROM NODE 13803.00 TO NODE 13820.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 140.00 DOWNSTREAM(FEET) = 137.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 926.91 CHANNEL SLOPE = 0.0032  
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT(FEET) = 19.41

\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 0.981

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	31.44	0.30	0.983	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.983

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 54446.84

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 15.79

AVERAGE FLOW DEPTH(FEET) = 19.41 TRAVEL TIME(MIN.) = 0.98

Tc(MIN.) = 109.54

SUBAREA AREA(ACRES) = 31.44 SUBAREA RUNOFF(CFS) = 19.41

EFFECTIVE AREA(ACRES) = 51459.30 AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA(ACRES) = 67830.0 PEAK FLOW RATE(CFS) = 54437.13

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE

GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030

\*ESTIMATED CHANNEL HEIGHT(FEET) = 19.41

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 19.41 FLOW VELOCITY(FEET/SEC.) = 15.79

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13820.00 = 131542.95 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28918.01	18.48	2.545	0.30( 0.25)	0.83	4103.7	10600.00
2	31415.28	24.09	2.136	0.30( 0.25)	0.83	5595.2	10320.00
3	36660.50	36.56	1.689	0.30( 0.25)	0.83	10160.1	110.00
4	39153.92	42.88	1.540	0.30( 0.25)	0.83	13061.4	130.00
5	41135.68	47.96	1.432	0.30( 0.25)	0.84	15565.1	150.00
6	44197.59	61.53	1.264	0.30( 0.26)	0.87	22630.1	390.00
7	46445.36	72.56	1.189	0.30( 0.27)	0.89	28662.1	13100.00
8	48082.49	78.92	1.145	0.30( 0.27)	0.89	31733.6	11801.00
9	50433.16	88.08	1.083	0.30( 0.27)	0.91	36778.9	11530.00
10	51731.21	93.72	1.053	0.30( 0.27)	0.91	40648.2	13510.00
11	52723.57	98.29	1.032	0.30( 0.28)	0.92	43680.4	13010.00

12	53824.88	103.28	1.009	0.30( 0.28)	0.92	47028.3	11330.00
13	54437.13	109.54	0.981	0.30( 0.28)	0.93	51459.3	11130.00
14	53812.78	117.18	0.946	0.30( 0.28)	0.93	55453.3	12330.00
15	53135.90	123.88	0.923	0.30( 0.28)	0.94	58796.4	12400.00
16	52088.93	132.65	0.900	0.30( 0.28)	0.94	62165.2	12201.00
17	50571.11	142.13	0.875	0.30( 0.28)	0.94	64619.4	12101.10
18	48025.77	154.47	0.843	0.30( 0.28)	0.94	66783.6	12010.00
19	46503.80	160.52	0.828	0.30( 0.28)	0.94	67097.3	10210.00
20	42110.57	187.13	0.769	0.30( 0.28)	0.94	67830.0	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 54437.13 Tc(MIN.) = 109.54

AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 51459.30

\*\*\*\*\*

FLOW PROCESS FROM NODE 13803.00 TO NODE 13820.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

TOTAL NUMBER OF STREAMS = 2

CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:

TIME OF CONCENTRATION(MIN.) = 109.54

RAINFALL INTENSITY(INCH/HR) = 0.98

AREA-AVERAGED Fm(INCH/HR) = 0.28

AREA-AVERAGED Fp(INCH/HR) = 0.30

AREA-AVERAGED Ap = 0.93

EFFECTIVE STREAM AREA(ACRES) = 51459.30

TOTAL STREAM AREA(ACRES) = 67830.01

PEAK FLOW RATE(CFS) AT CONFLUENCE = 54437.13

\*\*\*\*\*

FLOW PROCESS FROM NODE 13810.00 TO NODE 13811.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<

>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

INITIAL SUBAREA FLOW-LENGTH(FEET) = 648.54

ELEVATION DATA: UPSTREAM(FEET) = 756.46 DOWNSTREAM(FEET) = 586.02

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20

SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 12.293

\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.345

SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL,BROADLEAF"	-	5.58	0.30	1.000	56	12.29

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA RUNOFF(CFS) = 15.29

TOTAL AREA(ACRES) = 5.58 PEAK FLOW RATE(CFS) = 15.29

\*\*\*\*\*

FLOW PROCESS FROM NODE 13811.00 TO NODE 13811.50 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

\*\*\*\*\*

ELEVATION DATA: UPSTREAM(FEET) = 586.02 DOWNSTREAM(FEET) = 437.69  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 696.28 CHANNEL SLOPE = 0.2130  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.49  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 3.044  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 14.79 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 33.60  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.45  
 AVERAGE FLOW DEPTH(FEET) = 0.48 TRAVEL TIME(MIN.) = 1.80  
 Tc(MIN.) = 14.09  
 SUBAREA AREA(ACRES) = 14.79 SUBAREA RUNOFF(CFS) = 36.53  
 EFFECTIVE AREA(ACRES) = 20.37 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 20.4 PEAK FLOW RATE(CFS) = 50.31  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.60  
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 0.60 FLOW VELOCITY(FEET/SEC.) = 7.49  
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13811.50 = 1344.82 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13811.50 TO NODE 13812.00 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 437.69 DOWNSTREAM(FEET) = 402.36  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 681.04 CHANNEL SLOPE = 0.0519  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.12  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.768  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 18.41 0.30 1.000 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 70.77  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.27  
 AVERAGE FLOW DEPTH(FEET) = 1.10 TRAVEL TIME(MIN.) = 2.16  
 Tc(MIN.) = 16.25  
 SUBAREA AREA(ACRES) = 18.41 SUBAREA RUNOFF(CFS) = 40.90  
 EFFECTIVE AREA(ACRES) = 38.78 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 38.8 PEAK FLOW RATE(CFS) = 86.15  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.23

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.23 FLOW VELOCITY(FEET/SEC.) = 5.60  
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13812.00 = 2025.86 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13812.00 TO NODE 13813.00 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 402.36 DOWNSTREAM(FEET) = 259.72  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1282.56 CHANNEL SLOPE = 0.1112  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.18  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.500  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 27.87 0.30 0.858 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.858  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 114.30  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 7.96  
 AVERAGE FLOW DEPTH(FEET) = 1.16 TRAVEL TIME(MIN.) = 2.68  
 Tc(MIN.) = 18.93  
 SUBAREA AREA(ACRES) = 27.87 SUBAREA RUNOFF(CFS) = 56.24  
 EFFECTIVE AREA(ACRES) = 66.65 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94  
 TOTAL AREA(ACRES) = 66.7 PEAK FLOW RATE(CFS) = 133.02  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.27

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.27 FLOW VELOCITY(FEET/SEC.) = 8.34  
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13813.00 = 3308.42 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 31

-----  
 >>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 259.72 DOWNSTREAM(FEET) = 137.00  
 FLOW LENGTH(FEET) = 2412.88 MANNING'S N = 0.013  
 DEPTH OF FLOW IN 36.0 INCH PIPE IS 27.5 INCHES  
 PIPE-FLOW VELOCITY(FEET/SEC.) = 22.94  
 ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1  
 PIPE-FLOW(CFS) = 133.02  
 PIPE TRAVEL TIME(MIN.) = 1.75 Tc(MIN.) = 20.69  
 LONGEST FLOWPATH FROM NODE 13810.00 TO NODE 13820.00 = 5721.30 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 81

-----  
 >>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 =====

MAINLINE Tc(MIN.) = 20.69  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.350  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 83.64 0.30 0.570 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.570  
 SUBAREA AREA(ACRES) = 83.64 SUBAREA RUNOFF(CFS) = 164.01  
 EFFECTIVE AREA(ACRES) = 150.29 AREA-AVERAGED Fm(INCH/HR) = 0.22  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.73  
 TOTAL AREA(ACRES) = 150.3 PEAK FLOW RATE(CFS) = 288.03

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13813.00 TO NODE 13820.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====  
 TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
 TIME OF CONCENTRATION(MIN.) = 20.69  
 RAINFALL INTENSITY(INCH/HR) = 2.35  
 AREA-AVERAGED Fm(INCH/HR) = 0.22  
 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.73  
 EFFECTIVE STREAM AREA(ACRES) = 150.29  
 TOTAL STREAM AREA(ACRES) = 150.29  
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 288.03

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	28918.01	18.48	2.545	0.30( 0.25)	0.83	4103.7	10600.00
1	31415.28	24.09	2.136	0.30( 0.25)	0.83	5595.2	10320.00
1	36660.50	36.56	1.689	0.30( 0.25)	0.83	10160.1	110.00
1	39153.92	42.88	1.540	0.30( 0.25)	0.83	13061.4	130.00
1	41135.68	47.96	1.432	0.30( 0.25)	0.84	15565.1	150.00
1	44197.59	61.53	1.264	0.30( 0.26)	0.87	22630.1	390.00
1	46445.36	72.56	1.189	0.30( 0.27)	0.89	28662.1	13100.00
1	48082.49	78.92	1.145	0.30( 0.27)	0.89	31733.6	11801.00
1	50433.16	88.08	1.083	0.30( 0.27)	0.91	36778.9	11530.00
1	51731.21	93.72	1.053	0.30( 0.27)	0.91	40648.2	13510.00
1	52723.57	98.29	1.032	0.30( 0.28)	0.92	43680.4	13010.00
1	53824.88	103.28	1.009	0.30( 0.28)	0.92	47028.3	11330.00
1	54437.13	109.54	0.981	0.30( 0.28)	0.93	51459.3	11130.00
1	53812.78	117.18	0.946	0.30( 0.28)	0.93	55453.3	12330.00
1	53135.90	123.88	0.923	0.30( 0.28)	0.94	58796.4	12400.00
1	52088.93	132.65	0.900	0.30( 0.28)	0.94	62165.2	12201.00
1	50571.11	142.13	0.875	0.30( 0.28)	0.94	64619.4	12101.10
1	48025.77	154.47	0.843	0.30( 0.28)	0.94	66783.6	12010.00
1	46503.80	160.52	0.828	0.30( 0.28)	0.94	67097.3	10210.00
1	42110.57	187.13	0.769	0.30( 0.28)	0.94	67830.0	10100.00
2	288.03	20.69	2.350	0.30( 0.22)	0.73	150.3	13810.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	29198.91	18.48	2.545	0.30( 0.25)	0.83	4237.9	10600.00
2	30189.90	20.69	2.350	0.30( 0.25)	0.83	4841.6	13810.00
3	31674.35	24.09	2.136	0.30( 0.25)	0.83	5745.5	10320.00
4	36859.17	36.56	1.689	0.30( 0.25)	0.83	10310.4	110.00
5	39332.43	42.88	1.540	0.30( 0.25)	0.83	13211.7	130.00
6	41299.61	47.96	1.432	0.30( 0.25)	0.84	15715.4	150.00
7	44338.71	61.53	1.264	0.30( 0.26)	0.87	22780.4	390.00
8	46576.33	72.56	1.189	0.30( 0.27)	0.89	28812.4	13100.00
9	48207.62	78.92	1.145	0.30( 0.27)	0.89	31883.9	11801.00
10	50549.86	88.08	1.083	0.30( 0.27)	0.90	36929.2	11530.00
11	51843.84	93.72	1.053	0.30( 0.27)	0.91	40798.5	13510.00
12	52833.39	98.29	1.032	0.30( 0.27)	0.92	43830.7	13010.00
13	53931.61	103.28	1.009	0.30( 0.28)	0.92	47178.6	11330.00
14	54540.00	109.54	0.981	0.30( 0.28)	0.93	51609.6	11130.00
15	53910.93	117.18	0.946	0.30( 0.28)	0.93	55603.6	12330.00
16	53230.94	123.88	0.923	0.30( 0.28)	0.94	58946.7	12400.00
17	52180.88	132.65	0.900	0.30( 0.28)	0.94	62315.5	12201.00
18	50659.73	142.13	0.875	0.30( 0.28)	0.94	64769.7	12101.10
19	48110.05	154.47	0.843	0.30( 0.28)	0.94	66933.9	12010.00
20	46585.96	160.52	0.828	0.30( 0.28)	0.94	67247.6	10210.00
21	42184.78	187.13	0.769	0.30( 0.28)	0.94	67980.3	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 54540.00 Tc(MIN.) = 109.54  
 EFFECTIVE AREA(ACRES) = 51609.59 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 67980.3  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13820.00 = 131542.95 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13820.00 TO NODE 13840.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====  
 ELEVATION DATA: UPSTREAM(FEET) = 137.00 DOWNSTREAM(FEET) = 133.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1261.34 CHANNEL SLOPE = 0.0032  
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 19.53  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 0.975  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 31.60 0.30 0.683 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.683  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 54550.95  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 15.68  
 AVERAGE FLOW DEPTH(FEET) = 19.53 TRAVEL TIME(MIN.) = 1.34  
 Tc(MIN.) = 110.88  
 SUBAREA AREA(ACRES) = 31.60 SUBAREA RUNOFF(CFS) = 21.89  
 EFFECTIVE AREA(ACRES) = 51641.19 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 68011.9 PEAK FLOW RATE(CFS) = 54540.00

NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 19.53

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 19.53 FLOW VELOCITY (FEET/SEC.) = 15.68  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13840.00 = 132804.30 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	29198.91	20.08	2.388	0.30 ( 0.25)	0.83	4269.5	10600.00
2	30189.90	22.27	2.250	0.30 ( 0.25)	0.83	4873.2	13810.00
3	31674.35	25.65	2.049	0.30 ( 0.25)	0.83	5777.1	10320.00
4	36859.17	38.05	1.651	0.30 ( 0.25)	0.83	10342.0	110.00
5	39332.43	44.35	1.509	0.30 ( 0.25)	0.83	13243.3	130.00
6	41299.61	49.41	1.401	0.30 ( 0.25)	0.84	15747.0	150.00
7	44338.71	62.95	1.254	0.30 ( 0.26)	0.87	22812.0	390.00
8	46576.33	73.96	1.179	0.30 ( 0.27)	0.89	28844.0	13100.00
9	48207.62	80.30	1.136	0.30 ( 0.27)	0.89	31915.5	11801.00
10	50549.86	89.45	1.074	0.30 ( 0.27)	0.90	36960.8	11530.00
11	51843.84	95.08	1.047	0.30 ( 0.27)	0.91	40830.1	13510.00
12	52833.39	99.64	1.026	0.30 ( 0.27)	0.92	43862.3	13010.00
13	53931.61	104.62	1.003	0.30 ( 0.28)	0.92	47210.2	11330.00
14	54540.00	110.88	0.975	0.30 ( 0.28)	0.93	51641.2	11130.00
15	53910.93	118.52	0.940	0.30 ( 0.28)	0.93	55635.2	12330.00
16	53230.94	125.23	0.919	0.30 ( 0.28)	0.94	58978.3	12400.00
17	52180.88	134.00	0.897	0.30 ( 0.28)	0.94	62347.1	12201.00
18	50659.73	143.50	0.872	0.30 ( 0.28)	0.94	64801.3	12101.10
19	48110.05	155.85	0.840	0.30 ( 0.28)	0.94	66965.5	12010.00
20	46585.96	161.92	0.824	0.30 ( 0.28)	0.94	67279.2	10210.00
21	42184.78	188.57	0.767	0.30 ( 0.28)	0.94	68011.9	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 54540.00 Tc (MIN.) = 110.88  
 AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA (ACRES) = 51641.19

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13820.00 TO NODE 13840.00 IS CODE = 1  
 -----

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

-----  
 TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
 TIME OF CONCENTRATION (MIN.) = 110.88  
 RAINFALL INTENSITY (INCH/HR) = 0.97  
 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93  
 EFFECTIVE STREAM AREA (ACRES) = 51641.19  
 TOTAL STREAM AREA (ACRES) = 68011.90  
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 54540.00

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13830.00 TO NODE 13831.00 IS CODE = 21  
 -----  
 >>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<

>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<  
 =====  
 INITIAL SUBAREA FLOW-LENGTH (FEET) = 744.71  
 ELEVATION DATA: UPSTREAM (FEET) = 1100.95 DOWNSTREAM (FEET) = 959.21

Tc = K \* [(LENGTH\*\* 3.00) / (ELEVATION CHANGE)] \*\* 0.20  
 SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 13.858  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 3.083

SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER "CHAPARRAL, BROADLEAF"	-	5.06	0.30	1.000	56	13.86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 SUBAREA RUNOFF (CFS) = 12.68  
 TOTAL AREA (ACRES) = 5.06 PEAK FLOW RATE (CFS) = 12.68

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13831.00 TO NODE 13832.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

-----  
 ELEVATION DATA: UPSTREAM (FEET) = 959.21 DOWNSTREAM (FEET) = 832.83  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1076.71 CHANNEL SLOPE = 0.1174  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 0.74  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.711

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	32.57	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 48.16  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.06  
 AVERAGE FLOW DEPTH (FEET) = 0.70 TRAVEL TIME (MIN.) = 2.96  
 Tc (MIN.) = 16.82

SUBAREA AREA (ACRES) = 32.57 SUBAREA RUNOFF (CFS) = 70.68  
 EFFECTIVE AREA (ACRES) = 37.63 AREA-AVERAGED Fm (INCH/HR) = 0.30  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA (ACRES) = 37.6 PEAK FLOW RATE (CFS) = 81.66  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 0.95

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 0.95 FLOW VELOCITY (FEET/SEC.) = 7.23  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13832.00 = 1821.42 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13832.00 TO NODE 13833.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<



ELEVATION DATA: UPSTREAM(FEET) = 832.83 DOWNSTREAM(FEET) = 572.49  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1883.58 CHANNEL SLOPE = 0.1382  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.11  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.361  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 32.23 0.30 1.000 -  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 111.59  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.49  
 AVERAGE FLOW DEPTH(FEET) = 1.08 TRAVEL TIME(MIN.) = 3.70  
 Tc(MIN.) = 20.51  
 SUBAREA AREA(ACRES) = 32.23 SUBAREA RUNOFF(CFS) = 59.77  
 EFFECTIVE AREA(ACRES) = 69.86 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 69.9 PEAK FLOW RATE(CFS) = 129.56  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.18  
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.18 FLOW VELOCITY(FEET/SEC.) = 8.90  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13833.00 = 3705.00 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13833.00 TO NODE 13834.00 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 572.49 DOWNSTREAM(FEET) = 471.65  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 943.78 CHANNEL SLOPE = 0.1068  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.40  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.246  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 27.51 0.30 1.000 -  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 153.65  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.62  
 AVERAGE FLOW DEPTH(FEET) = 1.39 TRAVEL TIME(MIN.) = 1.82  
 Tc(MIN.) = 22.34  
 SUBAREA AREA(ACRES) = 27.51 SUBAREA RUNOFF(CFS) = 48.18  
 EFFECTIVE AREA(ACRES) = 97.37 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 97.4 PEAK FLOW RATE(CFS) = 170.51  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.48

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.48 FLOW VELOCITY(FEET/SEC.) = 8.91  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13834.00 = 4648.78 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13834.00 TO NODE 13835.00 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 471.65 DOWNSTREAM(FEET) = 347.06  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1647.45 CHANNEL SLOPE = 0.0756  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 2.02  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.058  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 94.21 0.30 1.000 -  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 245.10  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.82  
 AVERAGE FLOW DEPTH(FEET) = 1.99 TRAVEL TIME(MIN.) = 3.11  
 Tc(MIN.) = 25.45  
 SUBAREA AREA(ACRES) = 94.21 SUBAREA RUNOFF(CFS) = 149.07  
 EFFECTIVE AREA(ACRES) = 191.58 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 191.6 PEAK FLOW RATE(CFS) = 303.14  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 2.23

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 2.23 FLOW VELOCITY(FEET/SEC.) = 9.39  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13835.00 = 6296.23 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13835.00 TO NODE 13836.00 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 =====

ELEVATION DATA: UPSTREAM(FEET) = 347.06 DOWNSTREAM(FEET) = 269.29  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1696.71 CHANNEL SLOPE = 0.0458  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 3.28  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.918  
 SUBAREA LOSS RATE DATA(AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 233.25 0.30 1.000 -  
 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 473.04  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.90

AVERAGE FLOW DEPTH (FEET) = 3.23 TRAVEL TIME (MIN.) = 3.18  
 Tc (MIN.) = 28.63  
 SUBAREA AREA (ACRES) = 233.25 SUBAREA RUNOFF (CFS) = 339.58  
 EFFECTIVE AREA (ACRES) = 424.83 AREA-AVERAGED Fm (INCH/HR) = 0.30  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA (ACRES) = 424.8 PEAK FLOW RATE (CFS) = 618.49  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 3.71

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 3.71 FLOW VELOCITY (FEET/SEC.) = 9.59  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13836.00 = 7992.94 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13836.00 TO NODE 13837.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 269.29 DOWNSTREAM (FEET) = 191.87  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 2529.21 CHANNEL SLOPE = 0.0306  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT (FEET) = 4.42  
 \*100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.766

SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 134.70 0.30 0.880 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.880  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 709.58  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.58  
 AVERAGE FLOW DEPTH (FEET) = 4.40 TRAVEL TIME (MIN.) = 4.91  
 Tc (MIN.) = 33.54  
 SUBAREA AREA (ACRES) = 134.70 SUBAREA RUNOFF (CFS) = 182.13  
 EFFECTIVE AREA (ACRES) = 559.53 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97  
 TOTAL AREA (ACRES) = 559.5 PEAK FLOW RATE (CFS) = 742.79  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 4.50

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 4.50 FLOW VELOCITY (FEET/SEC.) = 8.69  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13837.00 = 10522.15 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 31  
 -----

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 191.87 DOWNSTREAM (FEET) = 133.00  
 FLOW LENGTH (FEET) = 1151.02 MANNING'S N = 0.013  
 DEPTH OF FLOW IN 69.0 INCH PIPE IS 51.9 INCHES  
 PIPE-FLOW VELOCITY (FEET/SEC.) = 35.42

ESTIMATED PIPE DIAMETER (INCH) = 69.00 NUMBER OF PIPES = 1  
 PIPE-FLOW (CFS) = 742.79  
 PIPE TRAVEL TIME (MIN.) = 0.54 Tc (MIN.) = 34.08  
 LONGEST FLOWPATH FROM NODE 13830.00 TO NODE 13840.00 = 11673.17 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc (MIN.) = 34.08  
 \*100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.752  
 SUBAREA LOSS RATE DATA (AMC II):  
 DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
 LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
 USER-DEFINED - 5.97 0.30 0.622 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.622  
 SUBAREA AREA (ACRES) = 5.97 SUBAREA RUNOFF (CFS) = 8.41  
 EFFECTIVE AREA (ACRES) = 565.50 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.97  
 TOTAL AREA (ACRES) = 565.5 PEAK FLOW RATE (CFS) = 744.23

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13837.00 TO NODE 13840.00 IS CODE = 1  
 -----

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
 TIME OF CONCENTRATION (MIN.) = 34.08  
 RAINFALL INTENSITY (INCH/HR) = 1.75  
 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.97  
 EFFECTIVE STREAM AREA (ACRES) = 565.50  
 TOTAL STREAM AREA (ACRES) = 565.50  
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 744.23

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	29198.91	20.08	2.388	0.30 ( 0.25)	0.83	4269.5	10600.00
1	30189.90	22.27	2.250	0.30 ( 0.25)	0.83	4873.2	13810.00
1	31674.35	25.65	2.049	0.30 ( 0.25)	0.83	5777.1	10320.00
1	36859.17	38.05	1.651	0.30 ( 0.25)	0.83	10342.0	110.00
1	39332.43	44.35	1.509	0.30 ( 0.25)	0.83	13243.3	130.00
1	41299.61	49.41	1.401	0.30 ( 0.25)	0.84	15747.0	150.00
1	44338.71	62.95	1.254	0.30 ( 0.26)	0.87	22812.0	390.00
1	46576.33	73.96	1.179	0.30 ( 0.27)	0.89	28844.0	13100.00
1	48207.62	80.30	1.136	0.30 ( 0.27)	0.89	31915.5	11801.00
1	50549.86	89.45	1.074	0.30 ( 0.27)	0.90	36960.8	11530.00
1	51843.84	95.08	1.047	0.30 ( 0.27)	0.91	40830.1	13510.00
1	52833.39	99.64	1.026	0.30 ( 0.27)	0.92	43862.3	13010.00
1	53931.61	104.62	1.003	0.30 ( 0.28)	0.92	47210.2	11330.00
1	54540.00	110.88	0.975	0.30 ( 0.28)	0.93	51641.2	11130.00
1	53910.93	118.52	0.940	0.30 ( 0.28)	0.93	55635.2	12330.00

1	53230.94	125.23	0.919	0.30 ( 0.28)	0.94	58978.3	12400.00
1	52180.88	134.00	0.897	0.30 ( 0.28)	0.94	62347.1	12201.00
1	50659.73	143.50	0.872	0.30 ( 0.28)	0.94	64801.3	12101.10
1	48110.05	155.85	0.840	0.30 ( 0.28)	0.94	66965.5	12010.00
1	46585.96	161.92	0.824	0.30 ( 0.28)	0.94	67279.2	10210.00
1	42184.78	188.57	0.767	0.30 ( 0.28)	0.94	68011.9	10100.00
2	744.23	34.08	1.752	0.30 ( 0.29)	0.97	565.5	13830.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	29827.85	20.08	2.388	0.30 ( 0.25)	0.84	4602.6	10600.00
2	30841.61	22.27	2.250	0.30 ( 0.25)	0.84	5242.6	13810.00
3	32348.07	25.65	2.049	0.30 ( 0.25)	0.84	6202.6	10320.00
4	35944.72	34.08	1.752	0.30 ( 0.25)	0.83	9447.1	13830.00
5	37551.68	38.05	1.651	0.30 ( 0.25)	0.83	10907.5	110.00
6	39952.66	44.35	1.509	0.30 ( 0.25)	0.84	13808.8	130.00
7	41865.20	49.41	1.401	0.30 ( 0.25)	0.84	16312.5	150.00
8	44829.23	62.95	1.254	0.30 ( 0.26)	0.87	23377.5	390.00
9	47028.72	73.96	1.179	0.30 ( 0.27)	0.89	29409.5	13100.00
10	48638.07	80.30	1.136	0.30 ( 0.27)	0.89	32481.0	11801.00
11	50948.65	89.45	1.074	0.30 ( 0.27)	0.91	37526.3	11530.00
12	52228.93	95.08	1.047	0.30 ( 0.27)	0.91	41395.6	13510.00
13	53207.88	99.64	1.026	0.30 ( 0.28)	0.92	44427.8	13010.00
14	54294.52	104.62	1.003	0.30 ( 0.28)	0.92	47775.7	11330.00
15	54888.38	110.88	0.975	0.30 ( 0.28)	0.93	52206.7	11130.00
16	54241.54	118.52	0.940	0.30 ( 0.28)	0.93	56200.7	12330.00
17	53551.20	125.23	0.919	0.30 ( 0.28)	0.94	59543.8	12400.00
18	52489.52	134.00	0.897	0.30 ( 0.28)	0.94	62912.6	12201.00
19	50955.81	143.50	0.872	0.30 ( 0.28)	0.94	65366.8	12101.10
20	48389.78	155.85	0.840	0.30 ( 0.28)	0.94	67531.0	12010.00
21	46857.67	161.92	0.824	0.30 ( 0.28)	0.94	67844.7	10210.00
22	42427.59	188.57	0.767	0.30 ( 0.28)	0.94	68577.4	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 54888.38 Tc(MIN.) = 110.88  
EFFECTIVE AREA(ACRES) = 52206.69 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA(ACRES) = 68577.4  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13840.00 = 132804.30 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13840.00 TO NODE 13860.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 133.00 DOWNSTREAM(FEET) = 130.00  
CHANNEL LENGTH THRU SUBAREA(FEET) = 654.44 CHANNEL SLOPE = 0.0046  
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 17.85  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 0.972  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS

LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 6.61 0.30 0.975 -  
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.975  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 54890.40  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 17.94  
AVERAGE FLOW DEPTH(FEET) = 17.85 TRAVEL TIME(MIN.) = 0.61  
Tc(MIN.) = 111.48  
SUBAREA AREA(ACRES) = 6.61 SUBAREA RUNOFF(CFS) = 4.04  
EFFECTIVE AREA(ACRES) = 52213.30 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA(ACRES) = 68584.0 PEAK FLOW RATE(CFS) = 54888.38  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 17.85

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 17.85 FLOW VELOCITY(FEET/SEC.) = 17.94  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13860.00 = 133458.73 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	29827.85	20.80	2.343	0.30 ( 0.25)	0.84	4609.2	10600.00
2	30841.61	22.99	2.205	0.30 ( 0.25)	0.84	5249.3	13810.00
3	32348.07	26.35	2.018	0.30 ( 0.25)	0.84	6209.2	10320.00
4	35944.72	34.77	1.735	0.30 ( 0.25)	0.83	9453.7	13830.00
5	37551.68	38.73	1.634	0.30 ( 0.25)	0.83	10914.1	110.00
6	39952.66	45.01	1.495	0.30 ( 0.25)	0.84	13815.4	130.00
7	41865.20	50.07	1.388	0.30 ( 0.25)	0.84	16319.1	150.00
8	44829.23	63.59	1.250	0.30 ( 0.26)	0.87	23384.1	390.00
9	47028.72	74.60	1.175	0.30 ( 0.27)	0.89	29416.1	13100.00
10	48638.07	80.93	1.132	0.30 ( 0.27)	0.89	32487.6	11801.00
11	50948.65	90.07	1.070	0.30 ( 0.27)	0.91	37532.9	11530.00
12	52228.93	95.70	1.044	0.30 ( 0.27)	0.91	41402.2	13510.00
13	53207.88	100.25	1.023	0.30 ( 0.28)	0.92	44434.4	13010.00
14	54294.52	105.23	1.000	0.30 ( 0.28)	0.92	47782.3	11330.00
15	54888.38	111.48	0.972	0.30 ( 0.28)	0.93	52213.3	11130.00
16	54241.54	119.13	0.937	0.30 ( 0.28)	0.93	56207.3	12330.00
17	53551.20	125.84	0.918	0.30 ( 0.28)	0.94	59550.4	12400.00
18	52489.52	134.62	0.895	0.30 ( 0.28)	0.94	62919.2	12201.00
19	50955.81	144.12	0.870	0.30 ( 0.28)	0.94	65373.4	12101.10
20	48389.78	156.48	0.838	0.30 ( 0.28)	0.94	67537.6	12010.00
21	46857.67	162.55	0.822	0.30 ( 0.28)	0.94	67851.3	10210.00
22	42427.59	189.22	0.766	0.30 ( 0.28)	0.94	68584.0	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 54888.38 Tc(MIN.) = 111.48  
AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 52213.30

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13840.00 TO NODE 13860.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:

TIME OF CONCENTRATION(MIN.) = 111.48  
RAINFALL INTENSITY(INCH/HR) = 0.97  
AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.93  
EFFECTIVE STREAM AREA(ACRES) = 52213.30  
TOTAL STREAM AREA(ACRES) = 68584.01  
PEAK FLOW RATE(CFS) AT CONFLUENCE = 54888.38

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13850.00 TO NODE 13851.00 IS CODE = 21  
-----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 617.57  
ELEVATION DATA: UPSTREAM(FEET) = 646.95 DOWNSTREAM(FEET) = 490.10

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 12.137  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.371  
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
NATURAL FAIR COVER						
"CHAPARRAL,BROADLEAF"	-	4.95	0.30	1.000	56	12.14

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA RUNOFF(CFS) = 13.68  
TOTAL AREA(ACRES) = 4.95 PEAK FLOW RATE(CFS) = 13.68

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13851.00 TO NODE 13851.50 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 490.10 DOWNSTREAM(FEET) = 440.98  
CHANNEL LENGTH THRU SUBAREA(FEET) = 351.14 CHANNEL SLOPE = 0.1399  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.38  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.160  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	4.02	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 18.85  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.63  
AVERAGE FLOW DEPTH(FEET) = 0.38 TRAVEL TIME(MIN.) = 1.26  
Tc(MIN.) = 13.40  
SUBAREA AREA(ACRES) = 4.02 SUBAREA RUNOFF(CFS) = 10.35  
EFFECTIVE AREA(ACRES) = 8.97 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 9.0 PEAK FLOW RATE(CFS) = 23.09  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.43

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.43 FLOW VELOCITY(FEET/SEC.) = 4.94  
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13851.50 = 968.71 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13851.50 TO NODE 13852.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 440.98 DOWNSTREAM(FEET) = 395.76  
CHANNEL LENGTH THRU SUBAREA(FEET) = 512.91 CHANNEL SLOPE = 0.0882  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.60  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.873  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	7.17	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 31.40  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 4.76  
AVERAGE FLOW DEPTH(FEET) = 0.59 TRAVEL TIME(MIN.) = 1.80  
Tc(MIN.) = 15.20  
SUBAREA AREA(ACRES) = 7.17 SUBAREA RUNOFF(CFS) = 16.60  
EFFECTIVE AREA(ACRES) = 16.14 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 16.1 PEAK FLOW RATE(CFS) = 37.38  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.65

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
DEPTH(FEET) = 0.65 FLOW VELOCITY(FEET/SEC.) = 5.06  
LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13852.00 = 1481.62 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13852.00 TO NODE 13853.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 395.76 DOWNSTREAM(FEET) = 354.94  
CHANNEL LENGTH THRU SUBAREA(FEET) = 443.69 CHANNEL SLOPE = 0.0920  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.72  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.738  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	6.76	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 44.80  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.49  
 AVERAGE FLOW DEPTH(FEET) = 0.71 TRAVEL TIME(MIN.) = 1.35  
 Tc(MIN.) = 16.55  
 SUBAREA AREA(ACRES) = 6.76 SUBAREA RUNOFF(CFS) = 14.84  
 EFFECTIVE AREA(ACRES) = 22.90 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 22.9 PEAK FLOW RATE(CFS) = 50.26  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.77

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 0.77 FLOW VELOCITY(FEET/SEC.) = 5.69  
 LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13853.00 = 1925.31 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13853.00 TO NODE 13854.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 354.94 DOWNSTREAM(FEET) = 263.57  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 962.09 CHANNEL SLOPE = 0.0950  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 0.92  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.487

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	18.16	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 68.15  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.38  
 AVERAGE FLOW DEPTH(FEET) = 0.91 TRAVEL TIME(MIN.) = 2.51  
 Tc(MIN.) = 19.06  
 SUBAREA AREA(ACRES) = 18.16 SUBAREA RUNOFF(CFS) = 35.74  
 EFFECTIVE AREA(ACRES) = 41.06 AREA-AVERAGED Fm(INCH/HR) = 0.30  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
 TOTAL AREA(ACRES) = 41.1 PEAK FLOW RATE(CFS) = 80.82  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.00

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.00 FLOW VELOCITY(FEET/SEC.) = 6.72  
 LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13854.00 = 2887.40 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13854.00 TO NODE 13855.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 263.57 DOWNSTREAM(FEET) = 188.74

CHANNEL LENGTH THRU SUBAREA(FEET) = 1228.77 CHANNEL SLOPE = 0.0609  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.41  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.254

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	38.75	0.30	0.879	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.879  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 115.55  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.50  
 AVERAGE FLOW DEPTH(FEET) = 1.39 TRAVEL TIME(MIN.) = 3.15  
 Tc(MIN.) = 22.21  
 SUBAREA AREA(ACRES) = 38.75 SUBAREA RUNOFF(CFS) = 69.40  
 EFFECTIVE AREA(ACRES) = 79.81 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94  
 TOTAL AREA(ACRES) = 79.8 PEAK FLOW RATE(CFS) = 141.59  
 GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 1.56

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH(FEET) = 1.56 FLOW VELOCITY(FEET/SEC.) = 6.92  
 LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13855.00 = 4116.17 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 31  
 -----

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 188.74 DOWNSTREAM(FEET) = 130.00  
 FLOW LENGTH(FEET) = 2092.67 MANNING'S N = 0.013  
 DEPTH OF FLOW IN 42.0 INCH PIPE IS 30.7 INCHES  
 PIPE-FLOW VELOCITY(FEET/SEC.) = 18.77  
 ESTIMATED PIPE DIAMETER(INCH) = 42.00 NUMBER OF PIPES = 1  
 PIPE-FLOW(CFS) = 141.59  
 PIPE TRAVEL TIME(MIN.) = 1.86 Tc(MIN.) = 24.07  
 LONGEST FLOWPATH FROM NODE 13850.00 TO NODE 13860.00 = 6208.84 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 81  
 -----

>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) = 24.07  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.136  
 SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	43.41	0.30	0.707	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.707  
 SUBAREA AREA(ACRES) = 43.41 SUBAREA RUNOFF(CFS) = 75.19  
 EFFECTIVE AREA(ACRES) = 123.22 AREA-AVERAGED Fm(INCH/HR) = 0.26  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.86

TOTAL AREA (ACRES) = 123.2 PEAK FLOW RATE (CFS) = 208.37

\*\*\*\*\*

FLOW PROCESS FROM NODE 13855.00 TO NODE 13860.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

TOTAL NUMBER OF STREAMS = 2
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:
TIME OF CONCENTRATION (MIN.) = 24.07
RAINFALL INTENSITY (INCH/HR) = 2.14
AREA-AVERAGED Fm (INCH/HR) = 0.26
AREA-AVERAGED Fp (INCH/HR) = 0.30
AREA-AVERAGED Ap = 0.86
EFFECTIVE STREAM AREA (ACRES) = 123.22
TOTAL STREAM AREA (ACRES) = 123.22
PEAK FLOW RATE (CFS) AT CONFLUENCE = 208.37

\*\* CONFLUENCE DATA \*\*

Table with columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp (Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 20 rows of data.

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO
CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

Table with columns: STREAM NUMBER, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp (Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 6 rows of data.

Table with columns: Node, Q (CFS), Tc (MIN.), Intensity (INCH/HR), Fp (Fm) (INCH/HR), Ap, Ae (ACRES), HEADWATER NODE. Contains 19 rows of data.

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 54967.60 Tc (MIN.) = 111.48
EFFECTIVE AREA (ACRES) = 52336.52 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA (ACRES) = 68707.2
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13860.00 = 133458.73 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13860.00 TO NODE 13880.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM (FEET) = 130.00 DOWNSTREAM (FEET) = 120.57
CHANNEL LENGTH THRU SUBAREA (FEET) = 610.77 CHANNEL SLOPE = 0.0154
GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
\*ESTIMATED CHANNEL HEIGHT (FEET) = 13.03
\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 0.970
SUBAREA LOSS RATE DATA (AMC II):
DEVELOPMENT TYPE/ SCSSOIL AREA Fp Ap SCSS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 4.89 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 54969.08
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 27.72
AVERAGE FLOW DEPTH (FEET) = 13.03 TRAVEL TIME (MIN.) = 0.37
Tc (MIN.) = 111.85

SUBAREA AREA (ACRES) = 4.89 SUBAREA RUNOFF (CFS) = 2.95
EFFECTIVE AREA (ACRES) = 52341.41 AREA-AVERAGED Fm (INCH/HR) = 0.28
AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA (ACRES) = 68712.1 PEAK FLOW RATE (CFS) = 54967.60
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
\*ESTIMATED CHANNEL HEIGHT (FEET) = 13.03

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH (FEET) = 13.03 FLOW VELOCITY (FEET/SEC.) = 27.72

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13880.00 = 134069.50 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	30027.64	21.24	2.315	0.30 ( 0.25)	0.84	4720.5	10600.00
2	31047.82	23.42	2.178	0.30 ( 0.25)	0.84	5371.8	13810.00
3	31535.98	24.50	2.109	0.30 ( 0.25)	0.84	5687.1	13850.00
4	32543.32	26.78	1.999	0.30 ( 0.25)	0.84	6337.3	10320.00
5	36108.56	35.19	1.724	0.30 ( 0.25)	0.83	9581.8	13830.00
6	37704.27	39.14	1.623	0.30 ( 0.25)	0.83	11042.2	110.00
7	40089.86	45.42	1.486	0.30 ( 0.25)	0.84	13943.5	130.00
8	41990.59	50.47	1.384	0.30 ( 0.25)	0.84	16447.2	150.00
9	44939.25	63.98	1.247	0.30 ( 0.26)	0.87	23512.2	390.00
10	47130.43	74.98	1.172	0.30 ( 0.27)	0.89	29544.2	13100.00
11	48735.01	81.31	1.129	0.30 ( 0.27)	0.89	32615.7	11801.00
12	51038.71	90.45	1.068	0.30 ( 0.27)	0.91	37661.0	11530.00
13	52316.14	96.07	1.042	0.30 ( 0.27)	0.91	41530.3	13510.00
14	53292.79	100.62	1.021	0.30 ( 0.28)	0.92	44562.6	13010.00
15	54376.90	105.60	0.999	0.30 ( 0.28)	0.92	47910.4	11330.00
16	54967.60	111.85	0.970	0.30 ( 0.28)	0.93	52341.4	11130.00
17	54316.88	119.50	0.935	0.30 ( 0.28)	0.93	56335.4	12330.00
18	53624.42	126.21	0.917	0.30 ( 0.28)	0.94	59678.6	12400.00
19	52560.21	134.99	0.894	0.30 ( 0.28)	0.94	63047.3	12201.00
20	51023.76	144.50	0.869	0.30 ( 0.28)	0.94	65501.5	12101.10
21	48454.16	156.87	0.837	0.30 ( 0.28)	0.94	67665.7	12010.00
22	46920.30	162.94	0.821	0.30 ( 0.28)	0.94	67979.4	10210.00
23	42484.03	189.62	0.766	0.30 ( 0.28)	0.94	68712.1	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 54967.60 Tc(MIN.) = 111.85  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 52341.41

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13860.00 TO NODE 13880.00 IS CODE = 1  
 -----

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

-----  
 TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
 TIME OF CONCENTRATION(MIN.) = 111.85  
 RAINFALL INTENSITY(INCH/HR) = 0.97  
 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93  
 EFFECTIVE STREAM AREA(ACRES) = 52341.41  
 TOTAL STREAM AREA(ACRES) = 68712.12  
 PEAK FLOW RATE(CFS) AT CONFLUENCE = 54967.60

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13870.00 TO NODE 13871.00 IS CODE = 21  
 -----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
 >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

-----  
 INITIAL SUBAREA FLOW-LENGTH(FEET) = 872.65  
 ELEVATION DATA: UPSTREAM(FEET) = 558.52 DOWNSTREAM(FEET) = 436.47

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20

SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 15.704

\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.823

SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------	--------------

NATURAL FAIR COVER

"GRASS" - 7.32 0.30 1.000 56 15.70

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

SUBAREA RUNOFF(CFS) = 16.62

TOTAL AREA(ACRES) = 7.32 PEAK FLOW RATE(CFS) = 16.62

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13871.00 TO NODE 13872.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

-----  
ELEVATION DATA: UPSTREAM(FEET) = 436.47 DOWNSTREAM(FEET) = 337.62

CHANNEL LENGTH THRU SUBAREA(FEET) = 827.95 CHANNEL SLOPE = 0.1194

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.54

\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.555

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------

USER-DEFINED - 13.01 0.30 1.000 -

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 29.85

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 5.16

AVERAGE FLOW DEPTH(FEET) = 0.52 TRAVEL TIME(MIN.) = 2.67

Tc(MIN.) = 18.38

SUBAREA AREA(ACRES) = 13.01 SUBAREA RUNOFF(CFS) = 26.41

EFFECTIVE AREA(ACRES) = 20.33 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00

TOTAL AREA(ACRES) = 20.3 PEAK FLOW RATE(CFS) = 41.27

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.63

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.63 FLOW VELOCITY(FEET/SEC.) = 5.81

LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13872.00 = 1700.60 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13872.00 TO NODE 13873.00 IS CODE = 56  
 -----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

-----  
ELEVATION DATA: UPSTREAM(FEET) = 337.62 DOWNSTREAM(FEET) = 253.88

CHANNEL LENGTH THRU SUBAREA(FEET) = 1049.16 CHANNEL SLOPE = 0.0798

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060

\*ESTIMATED CHANNEL HEIGHT(FEET) = 1.00

\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.315  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	32.99	0.30	0.923	-

 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.923  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 71.56  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 6.11  
 AVERAGE FLOW DEPTH (FEET) = 0.98 TRAVEL TIME (MIN.) = 2.86  
 Tc (MIN.) = 21.24  
 SUBAREA AREA (ACRES) = 32.99 SUBAREA RUNOFF (CFS) = 60.51  
 EFFECTIVE AREA (ACRES) = 53.32 AREA-AVERAGED Fm (INCH/HR) = 0.29  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.95  
 TOTAL AREA (ACRES) = 53.3 PEAK FLOW RATE (CFS) = 97.38  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.060  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 1.17  
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 1.17 FLOW VELOCITY (FEET/SEC.) = 6.74  
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13873.00 = 2749.76 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13873.00 TO NODE 13874.00 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 -----  
 ELEVATION DATA: UPSTREAM (FEET) = 253.88 DOWNSTREAM (FEET) = 160.73  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1518.60 CHANNEL SLOPE = 0.0613  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 1.16  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.133  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	30.94	0.30	0.900	-

 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.900  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 123.34  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 8.74  
 AVERAGE FLOW DEPTH (FEET) = 1.15 TRAVEL TIME (MIN.) = 2.89  
 Tc (MIN.) = 24.13  
 SUBAREA AREA (ACRES) = 30.94 SUBAREA RUNOFF (CFS) = 51.87  
 EFFECTIVE AREA (ACRES) = 84.26 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 84.3 PEAK FLOW RATE (CFS) = 140.50  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 1.23  
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 1.23 FLOW VELOCITY (FEET/SEC.) = 9.14  
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13874.00 = 4268.36 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13874.00 TO NODE 13875.00 IS CODE = 56

-----  
 >>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<  
 -----  
 ELEVATION DATA: UPSTREAM (FEET) = 160.73 DOWNSTREAM (FEET) = 158.14  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 582.74 CHANNEL SLOPE = 0.0044  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 3.08  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.010  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	73.67	0.30	0.930	-

 SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.930  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 197.90  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 4.03  
 AVERAGE FLOW DEPTH (FEET) = 3.05 TRAVEL TIME (MIN.) = 2.41  
 Tc (MIN.) = 26.54  
 SUBAREA AREA (ACRES) = 73.67 SUBAREA RUNOFF (CFS) = 114.76  
 EFFECTIVE AREA (ACRES) = 157.93 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 157.9 PEAK FLOW RATE (CFS) = 245.95  
 GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 3.41  
 END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 3.41 FLOW VELOCITY (FEET/SEC.) = 4.28  
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13875.00 = 4851.10 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 31

-----  
 >>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
 >>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<  
 -----  
 ELEVATION DATA: UPSTREAM (FEET) = 158.14 DOWNSTREAM (FEET) = 120.57  
 FLOW LENGTH (FEET) = 1855.67 MANNING'S N = 0.013  
 DEPTH OF FLOW IN 54.0 INCH PIPE IS 41.1 INCHES  
 PIPE-FLOW VELOCITY (FEET/SEC.) = 18.95  
 ESTIMATED PIPE DIAMETER (INCH) = 54.00 NUMBER OF PIPES = 1  
 PIPE-FLOW (CFS) = 245.95  
 PIPE TRAVEL TIME (MIN.) = 1.63 Tc (MIN.) = 28.17  
 LONGEST FLOWPATH FROM NODE 13870.00 TO NODE 13880.00 = 6706.77 FEET.

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 81

-----  
 >>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<  
 -----  
 MAINLINE Tc (MIN.) = 28.17  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 1.938  
 SUBAREA LOSS RATE DATA (AMC II):  

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
-------------------------------	-------------------	-----------------	-----------------	-----------------	-----------



USER-DEFINED - 34.90 0.30 0.743 -  
 SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.743  
 SUBAREA AREA (ACRES) = 34.90 SUBAREA RUNOFF (CFS) = 53.86  
 EFFECTIVE AREA (ACRES) = 192.83 AREA-AVERAGED Fm (INCH/HR) = 0.27  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.90  
 TOTAL AREA (ACRES) = 192.8 PEAK FLOW RATE (CFS) = 289.56

\*\*\*\*\*

FLOW PROCESS FROM NODE 13875.00 TO NODE 13880.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<  
 >>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
 TIME OF CONCENTRATION (MIN.) = 28.17  
 RAINFALL INTENSITY (INCH/HR) = 1.94  
 AREA-AVERAGED Fm (INCH/HR) = 0.27  
 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.90  
 EFFECTIVE STREAM AREA (ACRES) = 192.83  
 TOTAL STREAM AREA (ACRES) = 192.83  
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 289.56

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	30027.64	21.24	2.315	0.30 ( 0.25)	0.84	4720.5	10600.00
1	31047.82	23.42	2.178	0.30 ( 0.25)	0.84	5371.8	13810.00
1	31535.98	24.50	2.109	0.30 ( 0.25)	0.84	5687.1	13850.00
1	32543.32	26.78	1.999	0.30 ( 0.25)	0.84	6337.3	10320.00
1	36108.56	35.19	1.724	0.30 ( 0.25)	0.83	9581.8	13830.00
1	37704.27	39.14	1.623	0.30 ( 0.25)	0.83	11042.2	110.00
1	40089.86	45.42	1.486	0.30 ( 0.25)	0.84	13943.5	130.00
1	41990.59	50.47	1.384	0.30 ( 0.25)	0.84	16447.2	150.00
1	44939.25	63.98	1.247	0.30 ( 0.26)	0.87	23512.2	390.00
1	47130.43	74.98	1.172	0.30 ( 0.27)	0.89	29544.2	13100.00
1	48735.01	81.31	1.129	0.30 ( 0.27)	0.89	32615.7	11801.00
1	51038.71	90.45	1.068	0.30 ( 0.27)	0.91	37661.0	11530.00
1	52316.14	96.07	1.042	0.30 ( 0.27)	0.91	41530.3	13510.00
1	53292.79	100.62	1.021	0.30 ( 0.28)	0.92	44562.6	13010.00
1	54376.90	105.60	0.999	0.30 ( 0.28)	0.92	47910.4	11330.00
1	54967.60	111.85	0.970	0.30 ( 0.28)	0.93	52341.4	11130.00
1	54316.88	119.50	0.935	0.30 ( 0.28)	0.93	56335.4	12330.00
1	53624.42	126.21	0.917	0.30 ( 0.28)	0.94	59678.6	12400.00
1	52560.21	134.99	0.894	0.30 ( 0.28)	0.94	63047.3	12201.00
1	51023.76	144.50	0.869	0.30 ( 0.28)	0.94	65501.5	12101.10
1	48454.16	156.87	0.837	0.30 ( 0.28)	0.94	67665.7	12010.00
1	46920.30	162.94	0.821	0.30 ( 0.28)	0.94	67979.4	10210.00
1	42484.03	189.62	0.766	0.30 ( 0.28)	0.94	68712.1	10100.00
2	289.56	28.17	1.938	0.30 ( 0.27)	0.90	192.8	13870.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
 CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM	Q	Tc	Intensity	Fp (Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	---------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	30295.28	21.24	2.315	0.30 ( 0.25)	0.84	4865.9 10600.00
2	31323.12	23.42	2.178	0.30 ( 0.25)	0.84	5532.1 13810.00
3	31813.71	24.50	2.109	0.30 ( 0.25)	0.84	5854.8 13850.00
4	32828.72	26.78	1.999	0.30 ( 0.25)	0.84	6520.6 10320.00
5	33423.91	28.17	1.938	0.30 ( 0.25)	0.84	7068.0 13870.00
6	36361.08	35.19	1.724	0.30 ( 0.25)	0.84	9774.7 13830.00
7	37939.22	39.14	1.623	0.30 ( 0.25)	0.83	11235.0 110.00
8	40301.07	45.42	1.486	0.30 ( 0.25)	0.84	14136.3 130.00
9	42184.00	50.47	1.384	0.30 ( 0.25)	0.84	16640.1 150.00
10	45108.93	63.98	1.247	0.30 ( 0.26)	0.87	23705.0 390.00
11	47287.13	74.98	1.172	0.30 ( 0.27)	0.89	29737.0 13100.00
12	48884.23	81.31	1.129	0.30 ( 0.27)	0.89	32808.5 11801.00
13	51177.34	90.45	1.068	0.30 ( 0.27)	0.91	37853.8 11530.00
14	52450.31	96.07	1.042	0.30 ( 0.27)	0.91	41723.1 13510.00
15	53423.35	100.62	1.021	0.30 ( 0.28)	0.92	44755.4 13010.00
16	54503.52	105.60	0.999	0.30 ( 0.28)	0.92	48103.2 11330.00
17	55089.26	111.85	0.970	0.30 ( 0.28)	0.93	52534.2 11130.00
18	54432.48	119.50	0.935	0.30 ( 0.28)	0.93	56528.2 12330.00
19	53736.82	126.21	0.917	0.30 ( 0.28)	0.94	59871.4 12400.00
20	52668.65	134.99	0.894	0.30 ( 0.28)	0.94	63240.2 12201.00
21	51127.91	144.50	0.869	0.30 ( 0.28)	0.94	65694.3 12101.10
22	48552.73	156.87	0.837	0.30 ( 0.28)	0.94	67858.5 12010.00
23	47016.13	162.94	0.821	0.30 ( 0.28)	0.94	68172.2 10210.00
24	42570.25	189.62	0.766	0.30 ( 0.28)	0.94	68904.9 10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE (CFS) = 55089.26 Tc (MIN.) = 111.85  
 EFFECTIVE AREA (ACRES) = 52534.24 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA (ACRES) = 68904.9  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13880.00 = 134069.50 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13880.00 TO NODE 13910.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 120.57 DOWNSTREAM (FEET) = 119.70  
 CHANNEL LENGTH THRU SUBAREA (FEET) = 1190.21 CHANNEL SLOPE = 0.0007  
 GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 28.16  
 \* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 0.960  
 SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	117.69	0.30	0.724	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp (INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.724  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 55128.62  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 9.21  
 AVERAGE FLOW DEPTH (FEET) = 28.16 TRAVEL TIME (MIN.) = 2.15  
 Tc (MIN.) = 114.01  
 SUBAREA AREA (ACRES) = 117.69 SUBAREA RUNOFF (CFS) = 78.72  
 EFFECTIVE AREA (ACRES) = 52651.93 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93

TOTAL AREA (ACRES) = 69022.6 PEAK FLOW RATE (CFS) = 55089.26  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE (FEET) = 100.00 CHANNEL FREEBOARD (FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT (FEET) = 28.15

END OF SUBAREA CHANNEL FLOW HYDRAULICS:  
 DEPTH (FEET) = 28.15 FLOW VELOCITY (FEET/SEC.) = 9.21  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13910.00 = 135259.70 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	30295.28	23.77	2.156	0.30 ( 0.25)	0.84	4983.6	10600.00
2	31323.12	25.93	2.037	0.30 ( 0.25)	0.84	5649.8	13810.00
3	31813.71	27.00	1.990	0.30 ( 0.25)	0.84	5972.5	13850.00
4	32828.72	29.26	1.890	0.30 ( 0.25)	0.84	6638.3	10320.00
5	33423.91	30.64	1.841	0.30 ( 0.25)	0.84	7185.7	13870.00
6	36361.08	37.59	1.663	0.30 ( 0.25)	0.83	9892.3	13830.00
7	37939.22	41.52	1.569	0.30 ( 0.25)	0.83	11352.7	110.00
8	40301.07	47.76	1.437	0.30 ( 0.25)	0.84	14254.0	130.00
9	42184.00	52.78	1.357	0.30 ( 0.25)	0.84	16757.8	150.00
10	45108.93	66.25	1.231	0.30 ( 0.26)	0.87	23822.7	390.00
11	47287.13	77.23	1.157	0.30 ( 0.27)	0.89	29854.7	13100.00
12	48884.23	83.54	1.114	0.30 ( 0.27)	0.89	32926.2	11801.00
13	51177.34	92.64	1.058	0.30 ( 0.27)	0.90	37971.5	11530.00
14	52450.31	98.25	1.032	0.30 ( 0.27)	0.91	41840.8	13510.00
15	53423.35	102.80	1.012	0.30 ( 0.27)	0.92	44873.1	13010.00
16	54503.52	107.76	0.989	0.30 ( 0.28)	0.92	48220.9	11330.00
17	55089.26	114.01	0.960	0.30 ( 0.28)	0.93	52651.9	11130.00
18	54432.48	121.66	0.929	0.30 ( 0.28)	0.93	56645.9	12330.00
19	53736.82	128.38	0.911	0.30 ( 0.28)	0.94	59989.1	12400.00
20	52668.65	137.17	0.888	0.30 ( 0.28)	0.94	63357.9	12201.00
21	51127.91	146.70	0.864	0.30 ( 0.28)	0.94	65812.0	12101.10
22	48552.73	159.09	0.831	0.30 ( 0.28)	0.94	67976.2	12010.00
23	47016.13	165.18	0.816	0.30 ( 0.28)	0.94	68289.9	10210.00
24	42570.25	191.93	0.763	0.30 ( 0.28)	0.94	69022.6	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE (CFS) = 55089.26 Tc (MIN.) = 114.01  
 AREA-AVERAGED Fm (INCH/HR) = 0.28 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA (ACRES) = 52651.93

\*\*\*\*\*

FLOW PROCESS FROM NODE 13880.00 TO NODE 13910.00 IS CODE = 1

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<<

=====

TOTAL NUMBER OF STREAMS = 2  
 CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 1 ARE:  
 TIME OF CONCENTRATION (MIN.) = 114.01  
 RAINFALL INTENSITY (INCH/HR) = 0.96  
 AREA-AVERAGED Fm (INCH/HR) = 0.28  
 AREA-AVERAGED Fp (INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93  
 EFFECTIVE STREAM AREA (ACRES) = 52651.93  
 TOTAL STREAM AREA (ACRES) = 69022.63  
 PEAK FLOW RATE (CFS) AT CONFLUENCE = 55089.26

\*\*\*\*\*

FLOW PROCESS FROM NODE 13889.00 TO NODE 13890.00 IS CODE = 21

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<

>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH (FEET) = 447.89  
 ELEVATION DATA: UPSTREAM (FEET) = 564.89 DOWNSTREAM (FEET) = 421.92

Tc = K \* [(LENGTH\*\* 3.00) / (ELEVATION CHANGE)] \*\* 0.20

SUBAREA ANALYSIS USED MINIMUM Tc (MIN.) = 6.976

\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 4.951

SUBAREA Tc AND LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
PUBLIC PARK	-	3.03	0.30	0.960	56	6.98

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.960

SUBAREA RUNOFF (CFS) = 12.71

TOTAL AREA (ACRES) = 3.03 PEAK FLOW RATE (CFS) = 12.71

\*\*\*\*\*

FLOW PROCESS FROM NODE 13890.00 TO NODE 13891.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM (FEET) = 421.92 DOWNSTREAM (FEET) = 392.64

CHANNEL LENGTH THRU SUBAREA (FEET) = 435.33 CHANNEL SLOPE = 0.0673

GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT (FEET) = 0.49

\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 4.410

SUBAREA LOSS RATE DATA (AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.12	0.30	0.986	-

SUBAREA AVERAGE PVIOUS LOSS RATE, Fp (INCH/HR) = 0.30

SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.986

TRAVEL TIME COMPUTED USING ESTIMATED FLOW (CFS) = 27.80

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY (FEET/SEC.) = 5.43

AVERAGE FLOW DEPTH (FEET) = 0.47 TRAVEL TIME (MIN.) = 1.34

Tc (MIN.) = 8.31

SUBAREA AREA (ACRES) = 8.12 SUBAREA RUNOFF (CFS) = 30.07

EFFECTIVE AREA (ACRES) = 11.15 AREA-AVERAGED Fm (INCH/HR) = 0.29

AREA-AVERAGED Fp (INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.98

TOTAL AREA (ACRES) = 11.1 PEAK FLOW RATE (CFS) = 41.31

GIVEN CHANNEL BASE (FEET) = 10.00 CHANNEL FREEBOARD (FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT (FEET) = 0.59

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH (FEET) = 0.59 FLOW VELOCITY (FEET/SEC.) = 6.26

LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13891.00 = 883.22 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13891.00 TO NODE 13892.00 IS CODE = 56

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 392.64 DOWNSTREAM(FEET) = 324.46
CHANNEL LENGTH THRU SUBAREA(FEET) = 662.40 CHANNEL SLOPE = 0.1029
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.68
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.868
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 12.50 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 61.43
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 8.24
AVERAGE FLOW DEPTH(FEET) = 0.66 TRAVEL TIME(MIN.) = 1.34
Tc(MIN.) = 9.65
SUBAREA AREA(ACRES) = 12.50 SUBAREA RUNOFF(CFS) = 40.14
EFFECTIVE AREA(ACRES) = 23.65 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 23.6 PEAK FLOW RATE(CFS) = 76.00
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.74

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.74 FLOW VELOCITY(FEET/SEC.) = 8.88
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13892.00 = 1545.62 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13892.00 TO NODE 13893.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 324.46 DOWNSTREAM(FEET) = 240.82
CHANNEL LENGTH THRU SUBAREA(FEET) = 980.03 CHANNEL SLOPE = 0.0853
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.93
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.485
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 15.87 0.30 1.000 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 98.76
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.09
AVERAGE FLOW DEPTH(FEET) = 0.92 TRAVEL TIME(MIN.) = 1.80
Tc(MIN.) = 11.45
SUBAREA AREA(ACRES) = 15.87 SUBAREA RUNOFF(CFS) = 45.49
EFFECTIVE AREA(ACRES) = 39.52 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 39.5 PEAK FLOW RATE(CFS) = 113.35
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

```

```

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 0.99

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 0.99 FLOW VELOCITY(FEET/SEC.) = 9.50
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13893.00 = 2525.65 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13893.00 TO NODE 13894.00 IS CODE = 56
-----

```

```

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<
>>>>TRAVELTIME THRU SUBAREA<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 240.82 DOWNSTREAM(FEET) = 163.04
CHANNEL LENGTH THRU SUBAREA(FEET) = 1144.35 CHANNEL SLOPE = 0.0680
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.26
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.157
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 28.41 0.30 0.985 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.985
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 149.96
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.68
AVERAGE FLOW DEPTH(FEET) = 1.24 TRAVEL TIME(MIN.) = 1.97
Tc(MIN.) = 13.42
SUBAREA AREA(ACRES) = 28.41 SUBAREA RUNOFF(CFS) = 73.16
EFFECTIVE AREA(ACRES) = 67.93 AREA-AVERAGED Fm(INCH/HR) = 0.30
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99
TOTAL AREA(ACRES) = 67.9 PEAK FLOW RATE(CFS) = 174.82
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040
*ESTIMATED CHANNEL HEIGHT(FEET) = 1.36

END OF SUBAREA CHANNEL FLOW HYDRAULICS:
DEPTH(FEET) = 1.36 FLOW VELOCITY(FEET/SEC.) = 10.15
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13894.00 = 3670.00 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 31
-----

```

```

>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<
=====
ELEVATION DATA: UPSTREAM(FEET) = 163.04 DOWNSTREAM(FEET) = 119.70
FLOW LENGTH(FEET) = 1899.01 MANNING'S N = 0.013
DEPTH OF FLOW IN 48.0 INCH PIPE IS 34.0 INCHES
PIPE-FLOW VELOCITY(FEET/SEC.) = 18.39
ESTIMATED PIPE DIAMETER(INCH) = 48.00 NUMBER OF PIPES = 1
PIPE-FLOW(CFS) = 174.82
PIPE TRAVEL TIME(MIN.) = 1.72 Tc(MIN.) = 15.14
LONGEST FLOWPATH FROM NODE 13889.00 TO NODE 13910.00 = 5569.01 FEET.

```

```

*****
FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 81

```

=====  
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<  
=====

MAINLINE Tc(MIN.) = 15.14  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 2.879  
SUBAREA LOSS RATE DATA(AMC II):  
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS  
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN  
USER-DEFINED - 11.69 0.30 0.634 -  
SUBAREA AVERAGE PVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PVIOUS AREA FRACTION, Ap = 0.634  
SUBAREA AREA(ACRES) = 11.69 SUBAREA RUNOFF(CFS) = 28.29  
EFFECTIVE AREA(ACRES) = 79.62 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.94  
TOTAL AREA(ACRES) = 79.6 PEAK FLOW RATE(CFS) = 186.13

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13894.00 TO NODE 13910.00 IS CODE = 1  
=====

>>>>DESIGNATE INDEPENDENT STREAM FOR CONFLUENCE<<<<  
>>>>AND COMPUTE VARIOUS CONFLUENCED STREAM VALUES<<<<  
=====

TOTAL NUMBER OF STREAMS = 2  
CONFLUENCE VALUES USED FOR INDEPENDENT STREAM 2 ARE:  
TIME OF CONCENTRATION(MIN.) = 15.14  
RAINFALL INTENSITY(INCH/HR) = 2.88  
AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.94  
EFFECTIVE STREAM AREA(ACRES) = 79.62  
TOTAL STREAM AREA(ACRES) = 79.62  
PEAK FLOW RATE(CFS) AT CONFLUENCE = 186.13

\*\* CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	30295.28	23.77	2.156	0.30( 0.25)	0.84	4983.6	10600.00
1	31323.12	25.93	2.037	0.30( 0.25)	0.84	5649.8	13810.00
1	31813.71	27.00	1.990	0.30( 0.25)	0.84	5972.5	13850.00
1	32828.72	29.26	1.890	0.30( 0.25)	0.84	6638.3	10320.00
1	33423.91	30.64	1.841	0.30( 0.25)	0.84	7185.7	13870.00
1	36361.08	37.59	1.663	0.30( 0.25)	0.83	9892.3	13830.00
1	37939.22	41.52	1.569	0.30( 0.25)	0.83	11352.7	110.00
1	40301.07	47.76	1.437	0.30( 0.25)	0.84	14254.0	130.00
1	42184.00	52.78	1.357	0.30( 0.25)	0.84	16757.8	150.00
1	45108.93	66.25	1.231	0.30( 0.26)	0.87	23822.7	390.00
1	47287.13	77.23	1.157	0.30( 0.27)	0.89	29854.7	13100.00
1	48884.23	83.54	1.114	0.30( 0.27)	0.89	32926.2	11801.00
1	51177.34	92.64	1.058	0.30( 0.27)	0.90	37971.5	11530.00
1	52450.31	98.25	1.032	0.30( 0.27)	0.91	41840.8	13510.00
1	53423.35	102.80	1.012	0.30( 0.27)	0.92	44873.1	13010.00
1	54503.52	107.76	0.989	0.30( 0.28)	0.92	48220.9	11330.00
1	55089.26	114.01	0.960	0.30( 0.28)	0.93	52651.9	11130.00
1	54432.48	121.66	0.929	0.30( 0.28)	0.93	56645.9	12330.00
1	53736.82	128.38	0.911	0.30( 0.28)	0.94	59989.1	12400.00
1	52668.65	137.17	0.888	0.30( 0.28)	0.94	63357.9	12201.00
1	51127.91	146.70	0.864	0.30( 0.28)	0.94	65812.0	12101.10
1	48552.73	159.09	0.831	0.30( 0.28)	0.94	67976.2	12010.00

1	47016.13	165.18	0.816	0.30( 0.28)	0.94	68289.9	10210.00
1	42570.25	191.93	0.763	0.30( 0.28)	0.94	69022.6	10100.00
2	186.13	15.14	2.879	0.30( 0.28)	0.94	79.6	13889.00

RAINFALL INTENSITY AND TIME OF CONCENTRATION RATIO  
CONFLUENCE FORMULA USED FOR 2 STREAMS.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	26812.81	15.14	2.879	0.30( 0.25)	0.84	3254.5	13889.00
2	30429.59	23.77	2.156	0.30( 0.25)	0.84	5063.2	10600.00
3	31448.93	25.93	2.037	0.30( 0.25)	0.84	5729.4	13810.00
4	31936.12	27.00	1.990	0.30( 0.25)	0.84	6052.1	13850.00
5	32943.99	29.26	1.890	0.30( 0.25)	0.84	6717.9	10320.00
6	33535.65	30.64	1.841	0.30( 0.25)	0.84	7265.3	13870.00
7	36460.06	37.59	1.663	0.30( 0.25)	0.84	9972.0	13830.00
8	38031.47	41.52	1.569	0.30( 0.25)	0.83	11432.3	110.00
9	40383.85	47.76	1.437	0.30( 0.25)	0.84	14333.6	130.00
10	42261.08	52.78	1.357	0.30( 0.25)	0.84	16837.4	150.00
11	45177.02	66.25	1.231	0.30( 0.26)	0.87	23902.3	390.00
12	47349.87	77.23	1.157	0.30( 0.27)	0.89	29934.3	13100.00
13	48943.90	83.54	1.114	0.30( 0.27)	0.89	33005.9	11801.00
14	51232.98	92.64	1.058	0.30( 0.27)	0.90	38051.1	11530.00
15	52504.12	98.25	1.032	0.30( 0.27)	0.91	41920.4	13510.00
16	53475.68	102.80	1.012	0.30( 0.27)	0.92	44952.7	13010.00
17	54554.22	107.76	0.989	0.30( 0.28)	0.92	48300.6	11330.00
18	55137.92	114.01	0.960	0.30( 0.28)	0.93	52731.6	11130.00
19	54478.87	121.66	0.929	0.30( 0.28)	0.93	56725.5	12330.00
20	53781.96	128.38	0.911	0.30( 0.28)	0.94	60068.7	12400.00
21	52712.15	137.17	0.888	0.30( 0.28)	0.94	63437.5	12201.00
22	51169.63	146.70	0.864	0.30( 0.28)	0.94	65891.6	12101.10
23	48592.14	159.09	0.831	0.30( 0.28)	0.94	68055.8	12010.00
24	47054.41	165.18	0.816	0.30( 0.28)	0.94	68369.5	10210.00
25	42604.80	191.93	0.763	0.30( 0.28)	0.94	69102.2	10100.00

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 55137.92 Tc(MIN.) = 114.01  
EFFECTIVE AREA(ACRES) = 52731.55 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA(ACRES) = 69102.2  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13910.00 = 135259.70 FEET.  
=====

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 69102.2 TC(MIN.) = 114.01  
EFFECTIVE AREA(ACRES) = 52731.55 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.928  
PEAK FLOW RATE(CFS) = 55137.92

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	26812.81	15.14	2.879	0.30( 0.25)	0.84	3254.5	13889.00
2	30429.59	23.77	2.156	0.30( 0.25)	0.84	5063.2	10600.00
3	31448.93	25.93	2.037	0.30( 0.25)	0.84	5729.4	13810.00
4	31936.12	27.00	1.990	0.30( 0.25)	0.84	6052.1	13850.00
5	32943.99	29.26	1.890	0.30( 0.25)	0.84	6717.9	10320.00
6	33535.65	30.64	1.841	0.30( 0.25)	0.84	7265.3	13870.00

7	36460.06	37.59	1.663	0.30	( 0.25)	0.84	9972.0	13830.00
8	38031.47	41.52	1.569	0.30	( 0.25)	0.83	11432.3	110.00
9	40383.85	47.76	1.437	0.30	( 0.25)	0.84	14333.6	130.00
10	42261.08	52.78	1.357	0.30	( 0.25)	0.84	16837.4	150.00
11	45177.02	66.25	1.231	0.30	( 0.26)	0.87	23902.3	390.00
12	47349.87	77.23	1.157	0.30	( 0.27)	0.89	29934.3	13100.00
13	48943.90	83.54	1.114	0.30	( 0.27)	0.89	33005.9	11801.00
14	51232.98	92.64	1.058	0.30	( 0.27)	0.90	38051.1	11530.00
15	52504.12	98.25	1.032	0.30	( 0.27)	0.91	41920.4	13510.00
16	53475.68	102.80	1.012	0.30	( 0.27)	0.92	44952.7	13010.00
17	54554.22	107.76	0.989	0.30	( 0.28)	0.92	48300.6	11330.00
18	55137.92	114.01	0.960	0.30	( 0.28)	0.93	52731.6	11130.00
19	54478.87	121.66	0.929	0.30	( 0.28)	0.93	56725.5	12330.00
20	53781.96	128.38	0.911	0.30	( 0.28)	0.94	60068.7	12400.00
21	52712.15	137.17	0.888	0.30	( 0.28)	0.94	63437.5	12201.00
22	51169.63	146.70	0.864	0.30	( 0.28)	0.94	65891.6	12101.10
23	48592.14	159.09	0.831	0.30	( 0.28)	0.94	68055.8	12010.00
24	47054.41	165.18	0.816	0.30	( 0.28)	0.94	68369.5	10210.00
25	42604.80	191.93	0.763	0.30	( 0.28)	0.94	69102.2	10100.00

=====  
 END OF RATIONAL METHOD ANALYSIS  
 =====

\*\*\*\*\*  
RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE  
(Reference: 1986 ORANGE COUNTY HYDROLOGY CRITERION)  
(c) Copyright 1983-2013 Advanced Engineering Software (aes)  
Ver. 20.0 Release Date: 06/01/2013 License ID 1264

Analysis prepared by:

Michael Baker International  
5 Hutton Centre Drive Suite 500  
Santa Ana, CA92707

\*\*\*\*\* DESCRIPTION OF STUDY \*\*\*\*\*  
\* RANCHO MISSION VIEJO - PA3 & PA4 ROMP \*  
\* REGIONAL WATERSHED S39- FREE DRAINING - PHASE CONDITION NO PA4&5 \*  
\* 100-YR RM EV APRIL 2019 CCHI \*  
\*\*\*\*\*

FILE NAME: RI00EV39.DAT  
TIME/DATE OF STUDY: 08:52 04/09/2019

=====

USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:

=====

--\*TIME-OF-CONCENTRATION MODEL\*--

USER SPECIFIED STORM EVENT(YEAR) = 100.00  
SPECIFIED MINIMUM PIPE SIZE(INCH) = 36.00  
SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90

\*USER-DEFINED TABLED RAINFALL USED\*  
NUMBER OF [TIME,INTENSITY] DATA PAIRS = 14

- 1) 5.00; 5.744
- 2) 10.00; 3.724
- 3) 15.00; 2.891
- 4) 20.00; 2.392
- 5) 25.00; 2.077
- 6) 30.00; 1.856
- 7) 40.00; 1.601
- 8) 50.00; 1.389
- 9) 60.00; 1.273
- 10) 90.00; 1.070
- 11) 120.00; 0.932
- 12) 180.00; 0.777
- 13) 360.00; 0.571
- 14) 1200.00; 0.248

\*ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD\*

\*USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL\*

NO.	HALF- WIDTH (FT)	CROWN TO CROSSFALL (FT)	STREET-CROSSFALL IN- / OUT- / PARK- SIDE / SIDE / WAY	CURB HEIGHT (FT)	GUTTER-GEOMETRIES: WIDTH LIP HIKE (FT) (FT) (FT)	MANNING FACTOR (n)
1	30.0	20.0	0.018/0.018/0.020	0.67	2.00 0.0313 0.167	0.0150

GLOBAL STREET FLOW-DEPTH CONSTRAINTS:  
1. Relative Flow-Depth = 0.00 FEET  
as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)

2. (Depth)\*(Velocity) Constraint = 6.0 (FT\*FT/S)  
\*SIZE PIPE WITH A FLOW CAPACITY GREATER THAN  
OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.\*  
\*USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13900.00 TO NODE 13901.00 IS CODE = 21  
-----

>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<  
>>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<

=====

INITIAL SUBAREA FLOW-LENGTH(FEET) = 600.65  
ELEVATION DATA: UPSTREAM(FEET) = 442.40 DOWNSTREAM(FEET) = 385.16

Tc = K\*[(LENGTH\*\* 3.00)/(ELEVATION CHANGE)]\*\*0.20  
SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) = 10.859  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.581  
SUBAREA Tc AND LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN	Tc (MIN.)
AGRICULTURAL POOR COVER "FALLOW"	-	4.00	0.30	1.000	56	10.86

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
SUBAREA RUNOFF(CFS) = 11.81  
TOTAL AREA(ACRES) = 4.00 PEAK FLOW RATE(CFS) = 11.81

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13901.00 TO NODE 13902.00 IS CODE = 56  
-----

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) = 385.16 DOWNSTREAM(FEET) = 288.21  
CHANNEL LENGTH THRU SUBAREA(FEET) = 647.42 CHANNEL SLOPE = 0.1497  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.34  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 3.307  
SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	8.47	0.30	1.000	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 1.000  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 23.29  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 6.56  
AVERAGE FLOW DEPTH(FEET) = 0.33 TRAVEL TIME(MIN.) = 1.64  
Tc(MIN.) = 12.50  
SUBAREA AREA(ACRES) = 8.47 SUBAREA RUNOFF(CFS) = 22.92  
EFFECTIVE AREA(ACRES) = 12.47 AREA-AVERAGED Fm(INCH/HR) = 0.30  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 1.00  
TOTAL AREA(ACRES) = 12.5 PEAK FLOW RATE(CFS) = 33.75  
GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.41

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.41 FLOW VELOCITY(FEET/SEC.) = 7.51  
LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13902.00 = 1248.07 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13902.00 TO NODE 13903.00 IS CODE = 56

-----  
>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
>>>>TRAVELTIME THRU SUBAREA<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) =	288.21	DOWNSTREAM(FEET) =	184.89
CHANNEL LENGTH THRU SUBAREA(FEET) =	669.27	CHANNEL SLOPE =	0.1544
GIVEN CHANNEL BASE(FEET) =	10.00	CHANNEL FREEBOARD(FEET) =	0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.61

\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 3.113

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	23.85	0.30	0.982	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.982

TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 64.02

TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 9.56

AVERAGE FLOW DEPTH(FEET) = 0.60 TRAVEL TIME(MIN.) = 1.17

Tc(MIN.) = 13.67

SUBAREA AREA(ACRES) = 23.85 SUBAREA RUNOFF(CFS) = 60.49

EFFECTIVE AREA(ACRES) = 36.32 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 36.3 PEAK FLOW RATE(CFS) = 92.06

GIVEN CHANNEL BASE(FEET) = 10.00 CHANNEL FREEBOARD(FEET) = 0.0

"Z" FACTOR = 2.000 MANNING'S FACTOR = 0.040

\*ESTIMATED CHANNEL HEIGHT(FEET) = 0.74

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 0.74 FLOW VELOCITY(FEET/SEC.) = 10.79

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13903.00 = 1917.34 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13903.00 TO NODE 13904.00 IS CODE = 31

-----  
>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) =	184.89	DOWNSTREAM(FEET) =	155.08
FLOW LENGTH(FEET) =	876.66	MANNING'S N =	0.013
ESTIMATED PIPE DIAMETER(INCH) INCREASED TO	36.000		

DEPTH OF FLOW IN 36.0 INCH PIPE IS 24.1 INCHES

PIPE-FLOW VELOCITY(FEET/SEC.) = 18.29

ESTIMATED PIPE DIAMETER(INCH) = 36.00 NUMBER OF PIPES = 1

PIPE-FLOW(CFS) = 92.06

PIPE TRAVEL TIME(MIN.) = 0.80 Tc(MIN.) = 14.47

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13904.00 = 2794.00 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13903.00 TO NODE 13904.00 IS CODE = 81

-----  
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

MAINLINE Tc(MIN.) = 14.47

\* 100 YEAR RAINFALL INTENSITY (INCH/HR) = 2.980

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	21.29	0.30	0.996	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.996

SUBAREA AREA(ACRES) = 21.29 SUBAREA RUNOFF(CFS) = 51.37

EFFECTIVE AREA(ACRES) = 57.61 AREA-AVERAGED Fm(INCH/HR) = 0.30

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.99

TOTAL AREA(ACRES) = 57.6 PEAK FLOW RATE(CFS) = 139.07

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 31

-----  
>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<  
>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<

=====

ELEVATION DATA: UPSTREAM(FEET) =	155.08	DOWNSTREAM(FEET) =	118.00
FLOW LENGTH(FEET) =	1961.38	MANNING'S N =	0.013
DEPTH OF FLOW IN 45.0 INCH PIPE IS	32.8 INCHES		

PIPE-FLOW VELOCITY(FEET/SEC.) = 16.12

ESTIMATED PIPE DIAMETER(INCH) = 45.00 NUMBER OF PIPES = 1

PIPE-FLOW(CFS) = 139.07

PIPE TRAVEL TIME(MIN.) = 2.03 Tc(MIN.) = 16.50

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13920.00 = 4755.38 FEET.

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 81

-----  
>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<

=====

MAINLINE Tc(MIN.) =	16.50		
* 100 YEAR RAINFALL INTENSITY (INCH/HR) =	2.742		
SUBAREA LOSS RATE DATA(AMC II):			

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	43.53	0.30	0.649	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30

SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.649

SUBAREA AREA(ACRES) = 43.53 SUBAREA RUNOFF(CFS) = 99.78

EFFECTIVE AREA(ACRES) = 101.14 AREA-AVERAGED Fm(INCH/HR) = 0.25

AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.84

TOTAL AREA(ACRES) = 101.1 PEAK FLOW RATE(CFS) = 226.52

\*\*\*\*\*  
FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 10

-----  
>>>>MAIN-STREAM MEMORY COPIED ONTO MEMORY BANK # 1 <<<<<

=====

FLOW PROCESS FROM NODE 13910.00 TO NODE 13910.00 IS CODE =	15.1
--	------

-----  
>>>>DEFINE MEMORY BANK # 2 <<<<<

=====

PEAK FLOWRATE TABLE FILE NAME:	RI00EV38.DNA
--------------------------------	--------------

MEMORY BANK # 2 DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	26812.81	15.14	0.30 ( 0.25)	0.84	3254.5	13889.00
2	33535.65	30.64	0.30 ( 0.25)	0.84	7265.3	13870.00
3	38031.47	41.52	0.30 ( 0.25)	0.83	11432.3	110.00
4	40383.85	47.76	0.30 ( 0.25)	0.84	14333.6	130.00
5	42261.08	52.78	0.30 ( 0.25)	0.84	16837.4	150.00
6	45177.02	66.25	0.30 ( 0.26)	0.87	23902.3	390.00
7	47349.87	77.23	0.30 ( 0.27)	0.89	29934.3	13100.00
8	48943.90	83.54	0.30 ( 0.27)	0.89	33005.9	11801.00
9	51232.98	92.64	0.30 ( 0.27)	0.90	38051.1	11530.00
10	52504.12	98.25	0.30 ( 0.27)	0.91	41920.4	13510.00
11	53475.68	102.80	0.30 ( 0.27)	0.92	44952.7	13010.00
12	54554.22	107.76	0.30 ( 0.28)	0.92	48300.6	11330.00
13	55137.92	114.01	0.30 ( 0.28)	0.93	52731.6	11130.00
14	54478.87	121.66	0.30 ( 0.28)	0.93	56725.5	12330.00
15	53781.96	128.38	0.30 ( 0.28)	0.94	60068.7	12400.00
16	52712.15	137.17	0.30 ( 0.28)	0.94	63437.5	12201.00
17	51169.63	146.70	0.30 ( 0.28)	0.94	65891.6	12101.10
18	48592.14	159.09	0.30 ( 0.28)	0.94	68055.8	12010.00
19	47054.41	165.18	0.30 ( 0.28)	0.94	68369.5	10210.00
20	42604.80	191.93	0.30 ( 0.28)	0.94	69102.2	10100.00
TOTAL AREA (ACRES) =						69102.2

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13910.00 TO NODE 13910.00 IS CODE = 14.0

>>>>MEMORY BANK # 2 COPIED ONTO MAIN-STREAM MEMORY<<<<<

MAIN-STREAM MEMORY DEFINED AS FOLLOWS:

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	26812.81	15.14	0.30 ( 0.25)	0.84	3254.5	13889.00
2	33535.65	30.64	0.30 ( 0.25)	0.84	7265.3	13870.00
3	38031.47	41.52	0.30 ( 0.25)	0.83	11432.3	110.00
4	40383.85	47.76	0.30 ( 0.25)	0.84	14333.6	130.00
5	42261.08	52.78	0.30 ( 0.25)	0.84	16837.4	150.00
6	45177.02	66.25	0.30 ( 0.26)	0.87	23902.3	390.00
7	47349.87	77.23	0.30 ( 0.27)	0.89	29934.3	13100.00
8	48943.90	83.54	0.30 ( 0.27)	0.89	33005.9	11801.00
9	51232.98	92.64	0.30 ( 0.27)	0.90	38051.1	11530.00
10	52504.12	98.25	0.30 ( 0.27)	0.91	41920.4	13510.00
11	53475.68	102.80	0.30 ( 0.27)	0.92	44952.7	13010.00
12	54554.22	107.76	0.30 ( 0.28)	0.92	48300.6	11330.00
13	55137.92	114.01	0.30 ( 0.28)	0.93	52731.6	11130.00
14	54478.87	121.66	0.30 ( 0.28)	0.93	56725.5	12330.00
15	53781.96	128.38	0.30 ( 0.28)	0.94	60068.7	12400.00
16	52712.15	137.17	0.30 ( 0.28)	0.94	63437.5	12201.00
17	51169.63	146.70	0.30 ( 0.28)	0.94	65891.6	12101.10
18	48592.14	159.09	0.30 ( 0.28)	0.94	68055.8	12010.00
19	47054.41	165.18	0.30 ( 0.28)	0.94	68369.5	10210.00
20	42604.80	191.93	0.30 ( 0.28)	0.94	69102.2	10100.00
TOTAL AREA (ACRES) =						69102.2

\*\*\*\*\*  
 FLOW PROCESS FROM NODE 13910.00 TO NODE 13920.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

```

=====
ELEVATION DATA: UPSTREAM(FEET) = 119.70 DOWNSTREAM(FEET) = 118.00
CHANNEL LENGTH THRU SUBAREA(FEET) = 1376.26 CHANNEL SLOPE = 0.0012
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 24.82
* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 0.950
SUBAREA LOSS RATE DATA(AMC II):
DEVELOPMENT TYPE/ SCS SOIL AREA Fp Ap SCS
LAND USE GROUP (ACRES) (INCH/HR) (DECIMAL) CN
USER-DEFINED - 96.09 0.30 0.535 -
SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.535
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 55172.07
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 11.16
AVERAGE FLOW DEPTH(FEET) = 24.81 TRAVEL TIME(MIN.) = 2.06
Tc(MIN.) = 116.06
SUBAREA AREA(ACRES) = 96.09 SUBAREA RUNOFF(CFS) = 68.29
EFFECTIVE AREA(ACRES) = 52827.64 AREA-AVERAGED Fm(INCH/HR) = 0.28
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93
TOTAL AREA(ACRES) = 69198.3 PEAK FLOW RATE(CFS) = 55137.92
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030
*ESTIMATED CHANNEL HEIGHT(FEET) = 24.81
    
```

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 24.81 FLOW VELOCITY(FEET/SEC.) = 11.16  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136635.97 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp (Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	26812.81	17.64	2.627	0.30 ( 0.25)	0.83	3350.6	13889.00
2	33535.65	32.99	1.780	0.30 ( 0.25)	0.83	7361.4	13870.00
3	38031.47	43.79	1.521	0.30 ( 0.25)	0.83	11528.4	110.00
4	40383.85	49.99	1.389	0.30 ( 0.25)	0.84	14429.7	130.00
5	42261.08	54.99	1.331	0.30 ( 0.25)	0.84	16933.5	150.00
6	45177.02	68.42	1.216	0.30 ( 0.26)	0.87	23998.4	390.00
7	47349.87	79.37	1.142	0.30 ( 0.27)	0.89	30030.4	13100.00
8	48943.90	85.66	1.099	0.30 ( 0.27)	0.89	33101.9	11801.00
9	51232.98	94.74	1.048	0.30 ( 0.27)	0.90	38147.2	11530.00
10	52504.12	100.34	1.022	0.30 ( 0.27)	0.91	42016.5	13510.00
11	53475.68	104.87	1.002	0.30 ( 0.27)	0.92	45048.8	13010.00
12	54554.22	109.82	0.979	0.30 ( 0.28)	0.92	48396.7	11330.00
13	55137.92	116.06	0.950	0.30 ( 0.28)	0.93	52827.6	11130.00
14	54478.87	123.72	0.922	0.30 ( 0.28)	0.93	56821.6	12330.00
15	53781.96	130.45	0.905	0.30 ( 0.28)	0.94	60164.8	12400.00
16	52712.15	139.25	0.882	0.30 ( 0.28)	0.94	63533.6	12201.00
17	51169.63	148.79	0.858	0.30 ( 0.28)	0.94	65987.7	12101.10
18	48592.14	161.22	0.826	0.30 ( 0.28)	0.94	68151.9	12010.00
19	47054.41	167.33	0.810	0.30 ( 0.28)	0.94	68465.6	10210.00
20	42604.80	194.13	0.761	0.30 ( 0.28)	0.94	69198.3	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 55137.92 Tc(MIN.) = 116.06



AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 52827.64

\*\*\*\*\*

FLOW PROCESS FROM NODE 13904.00 TO NODE 13920.00 IS CODE = 11

>>>>CONFLUENCE MEMORY BANK # 1 WITH THE MAIN-STREAM MEMORY<<<<<

\*\* MAIN STREAM CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	26812.81	17.64	2.627	0.30( 0.25)	0.83	3350.6	13889.00
2	33535.65	32.99	1.780	0.30( 0.25)	0.83	7361.4	13870.00
3	38031.47	43.79	1.521	0.30( 0.25)	0.83	11528.4	110.00
4	40383.85	49.99	1.389	0.30( 0.25)	0.84	14429.7	130.00
5	42261.08	54.99	1.331	0.30( 0.25)	0.84	16933.5	150.00
6	45177.02	68.42	1.216	0.30( 0.26)	0.87	23998.4	390.00
7	47349.87	79.37	1.142	0.30( 0.27)	0.89	30030.4	13100.00
8	48943.90	85.66	1.099	0.30( 0.27)	0.89	33101.9	11801.00
9	51232.98	94.74	1.048	0.30( 0.27)	0.90	38147.2	11530.00
10	52504.12	100.34	1.022	0.30( 0.27)	0.91	42016.5	13510.00
11	53475.68	104.87	1.002	0.30( 0.27)	0.92	45048.8	13010.00
12	54554.22	109.82	0.979	0.30( 0.28)	0.92	48396.7	11330.00
13	55137.92	116.06	0.950	0.30( 0.28)	0.93	52827.6	11130.00
14	54478.87	123.72	0.922	0.30( 0.28)	0.93	56821.6	12330.00
15	53781.96	130.45	0.905	0.30( 0.28)	0.94	60164.8	12400.00
16	52712.15	139.25	0.882	0.30( 0.28)	0.94	63533.6	12201.00
17	51169.63	148.79	0.858	0.30( 0.28)	0.94	65987.7	12101.10
18	48592.14	161.22	0.826	0.30( 0.28)	0.94	68151.9	12010.00
19	47054.41	167.33	0.810	0.30( 0.28)	0.94	68465.6	10210.00
20	42604.80	194.13	0.761	0.30( 0.28)	0.94	69198.3	10100.00

LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136635.97 FEET.

\*\* MEMORY BANK # 1 CONFLUENCE DATA \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	226.52	16.50	2.742	0.30( 0.25)	0.84	101.1	13900.00

LONGEST FLOWPATH FROM NODE 13900.00 TO NODE 13920.00 = 4755.38 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	26503.11	16.50	2.742	0.30( 0.25)	0.83	3234.0	13900.00
2	27028.92	17.64	2.627	0.30( 0.25)	0.83	3451.7	13889.00
3	33674.62	32.99	1.780	0.30( 0.25)	0.83	7462.5	13870.00
4	38146.85	43.79	1.521	0.30( 0.25)	0.83	11629.5	110.00
5	40487.26	49.99	1.389	0.30( 0.25)	0.84	14530.9	130.00
6	42359.21	54.99	1.331	0.30( 0.25)	0.84	17034.6	150.00
7	45264.67	68.42	1.216	0.30( 0.26)	0.87	24099.5	390.00
8	47430.78	79.37	1.142	0.30( 0.27)	0.89	30131.5	13100.00
9	49020.93	85.66	1.099	0.30( 0.27)	0.89	33203.1	11801.00
10	51305.36	94.74	1.048	0.30( 0.27)	0.90	38248.4	11530.00
11	52574.16	100.34	1.022	0.30( 0.27)	0.91	42117.7	13510.00
12	53543.81	104.87	1.002	0.30( 0.27)	0.92	45149.9	13010.00
13	54620.28	109.82	0.979	0.30( 0.28)	0.92	48497.8	11330.00
14	55201.37	116.06	0.950	0.30( 0.28)	0.93	52928.8	11130.00
15	54539.79	123.72	0.922	0.30( 0.28)	0.93	56922.7	12330.00

16	53841.30	130.45	0.905	0.30( 0.28)	0.93	60265.9	12400.00
17	52769.42	139.25	0.882	0.30( 0.28)	0.94	63634.7	12201.00
18	51224.66	148.79	0.858	0.30( 0.28)	0.94	66088.8	12101.10
19	48644.25	161.22	0.826	0.30( 0.28)	0.94	68253.0	12010.00
20	47105.08	167.33	0.810	0.30( 0.28)	0.94	68566.8	10210.00
21	42651.02	194.13	0.761	0.30( 0.28)	0.94	69299.5	10100.00

TOTAL AREA(ACRES) = 69299.5

COMPUTED CONFLUENCE ESTIMATES ARE AS FOLLOWS:

PEAK FLOW RATE(CFS) = 55201.37 Tc(MIN.) = 116.061  
EFFECTIVE AREA(ACRES) = 52928.78 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.92  
TOTAL AREA(ACRES) = 69299.5  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13920.00 = 136635.97 FEET.

\*\*\*\*\*

FLOW PROCESS FROM NODE 13920.00 TO NODE 13921.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<

>>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 118.00 DOWNSTREAM(FEET) = 115.28  
CHANNEL LENGTH THRU SUBAREA(FEET) = 335.44 CHANNEL SLOPE = 0.0081  
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 15.47  
\* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 0.949

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	134.30	0.30	0.658	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.658  
TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 55246.79  
TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 22.07  
AVERAGE FLOW DEPTH(FEET) = 15.47 TRAVEL TIME(MIN.) = 0.25  
Tc(MIN.) = 116.31  
SUBAREA AREA(ACRES) = 134.30 SUBAREA RUNOFF(CFS) = 90.85  
EFFECTIVE AREA(ACRES) = 53063.08 AREA-AVERAGED Fm(INCH/HR) = 0.28  
AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
TOTAL AREA(ACRES) = 69433.8 PEAK FLOW RATE(CFS) = 55201.37  
NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
"Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
\*ESTIMATED CHANNEL HEIGHT(FEET) = 15.46

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 15.46 FLOW VELOCITY(FEET/SEC.) = 22.06  
LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 13921.00 = 136971.41 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	26503.11	16.81	2.710	0.30( 0.25)	0.82	3368.3	13900.00
2	27028.92	17.95	2.596	0.30( 0.25)	0.82	3586.0	13889.00
3	33674.62	33.28	1.772	0.30( 0.25)	0.83	7596.8	13870.00
4	38146.85	44.08	1.515	0.30( 0.25)	0.83	11763.8	110.00
5	40487.26	50.27	1.386	0.30( 0.25)	0.83	14665.2	130.00

6	42359.21	55.26	1.328	0.30	( 0.25)	0.84	17168.9	150.00
7	45264.67	68.69	1.214	0.30	( 0.26)	0.86	24233.8	390.00
8	47430.78	79.63	1.140	0.30	( 0.27)	0.88	30265.8	13100.00
9	49020.93	85.92	1.098	0.30	( 0.27)	0.89	33337.4	11801.00
10	51305.36	95.00	1.047	0.30	( 0.27)	0.90	38382.7	11530.00
11	52574.16	100.59	1.021	0.30	( 0.27)	0.91	42252.0	13510.00
12	53543.81	105.12	1.000	0.30	( 0.27)	0.91	45284.2	13010.00
13	54620.28	110.08	0.978	0.30	( 0.28)	0.92	48632.1	11330.00
14	55201.37	116.31	0.949	0.30	( 0.28)	0.93	53063.1	11130.00
15	54539.79	123.98	0.922	0.30	( 0.28)	0.93	57057.0	12330.00
16	53841.30	130.70	0.904	0.30	( 0.28)	0.93	60400.2	12400.00
17	52769.42	139.51	0.882	0.30	( 0.28)	0.94	63769.0	12201.00
18	51224.66	149.05	0.857	0.30	( 0.28)	0.94	66223.1	12101.10
19	48644.25	161.48	0.825	0.30	( 0.28)	0.94	68387.3	12010.00
20	47105.08	167.59	0.809	0.30	( 0.28)	0.94	68701.0	10210.00
21	42651.02	194.40	0.761	0.30	( 0.28)	0.94	69433.8	10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 55201.37 Tc(MIN.) = 116.31  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 53063.08

\*\*\*\*\*

FLOW PROCESS FROM NODE 13921.00 TO NODE 14010.00 IS CODE = 56

>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<  
 >>>>TRAVELTIME THRU SUBAREA<<<<<

ELEVATION DATA: UPSTREAM(FEET) = 115.28 DOWNSTREAM(FEET) = 100.00  
 CHANNEL LENGTH THRU SUBAREA(FEET) = 1396.08 CHANNEL SLOPE = 0.0109  
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 14.31  
 \* 100 YEAR RAINFALL INTENSITY(INCH/HR) = 0.945

SUBAREA LOSS RATE DATA(AMC II):

DEVELOPMENT TYPE/ LAND USE	SCS SOIL GROUP	AREA (ACRES)	Fp (INCH/HR)	Ap (DECIMAL)	SCS CN
USER-DEFINED	-	96.27	0.30	0.723	-

SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) = 0.30  
 SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap = 0.723  
 TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) = 55232.89  
 TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) = 24.56  
 AVERAGE FLOW DEPTH(FEET) = 14.30 TRAVEL TIME(MIN.) = 0.95  
 Tc(MIN.) = 117.26  
 SUBAREA AREA(ACRES) = 96.27 SUBAREA RUNOFF(CFS) = 63.05  
 EFFECTIVE AREA(ACRES) = 53159.35 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.93  
 TOTAL AREA(ACRES) = 69530.1 PEAK FLOW RATE(CFS) = 55201.37  
 NOTE: PEAK FLOW RATE DEFAULTED TO UPSTREAM VALUE  
 GIVEN CHANNEL BASE(FEET) = 100.00 CHANNEL FREEBOARD(FEET) = 0.0  
 "Z" FACTOR = 4.000 MANNING'S FACTOR = 0.030  
 \*ESTIMATED CHANNEL HEIGHT(FEET) = 14.30

END OF SUBAREA CHANNEL FLOW HYDRAULICS:

DEPTH(FEET) = 14.30 FLOW VELOCITY(FEET/SEC.) = 24.56  
 LONGEST FLOWPATH FROM NODE 10100.00 TO NODE 14010.00 = 138367.48 FEET.

\*\* PEAK FLOW RATE TABLE \*\*

STREAM	Q	Tc	Intensity	Fp(Fm)	Ap	Ae	HEADWATER
--------	---	----	-----------	--------	----	----	-----------

NUMBER	(CFS)	(MIN.)	(INCH/HR)	(INCH/HR)	(ACRES)	NODE
1	26503.11	17.99	2.593	0.30 ( 0.25)	0.82	3464.6 13900.00
2	27028.92	19.12	2.480	0.30 ( 0.25)	0.82	3682.3 13889.00
3	33674.62	34.38	1.744	0.30 ( 0.25)	0.83	7693.1 13870.00
4	38146.85	45.13	1.492	0.30 ( 0.25)	0.83	11860.1 110.00
5	40487.26	51.31	1.374	0.30 ( 0.25)	0.83	14761.4 130.00
6	42359.21	56.28	1.316	0.30 ( 0.25)	0.84	17265.2 150.00
7	45264.67	69.69	1.207	0.30 ( 0.26)	0.86	24330.1 390.00
8	47430.78	80.62	1.133	0.30 ( 0.27)	0.88	30362.1 13100.00
9	49020.93	86.90	1.091	0.30 ( 0.27)	0.89	33433.7 11801.00
10	51305.36	95.97	1.043	0.30 ( 0.27)	0.90	38478.9 11530.00
11	52574.16	101.55	1.017	0.30 ( 0.27)	0.91	42348.2 13510.00
12	53543.81	106.08	0.996	0.30 ( 0.27)	0.91	45380.5 13010.00
13	54620.28	111.03	0.973	0.30 ( 0.28)	0.92	48728.4 11330.00
14	55201.37	117.26	0.945	0.30 ( 0.28)	0.93	53159.4 11130.00
15	54539.79	124.93	0.919	0.30 ( 0.28)	0.93	57153.3 12330.00
16	53841.30	131.66	0.902	0.30 ( 0.28)	0.93	60496.5 12400.00
17	52769.42	140.47	0.879	0.30 ( 0.28)	0.94	63865.3 12201.00
18	51224.66	150.02	0.854	0.30 ( 0.28)	0.94	66319.4 12101.10
19	48644.25	162.47	0.822	0.30 ( 0.28)	0.94	68483.6 12010.00
20	47105.08	168.59	0.806	0.30 ( 0.28)	0.94	68797.3 10210.00
21	42651.02	195.42	0.759	0.30 ( 0.28)	0.94	69530.1 10100.00

NEW PEAK FLOW DATA ARE:

PEAK FLOW RATE(CFS) = 55201.37 Tc(MIN.) = 117.26  
 AREA-AVERAGED Fm(INCH/HR) = 0.28 AREA-AVERAGED Fp(INCH/HR) = 0.30  
 AREA-AVERAGED Ap = 0.93 EFFECTIVE AREA(ACRES) = 53159.35

END OF STUDY SUMMARY:

TOTAL AREA(ACRES) = 69530.1 TC(MIN.) = 117.26  
 EFFECTIVE AREA(ACRES) = 53159.35 AREA-AVERAGED Fm(INCH/HR) = 0.28  
 AREA-AVERAGED Fp(INCH/HR) = 0.30 AREA-AVERAGED Ap = 0.926  
 PEAK FLOW RATE(CFS) = 55201.37

\*\* PEAK FLOW RATE TABLE \*\*

STREAM NUMBER	Q (CFS)	Tc (MIN.)	Intensity (INCH/HR)	Fp(Fm) (INCH/HR)	Ap	Ae (ACRES)	HEADWATER NODE
1	26503.11	17.99	2.593	0.30 ( 0.25)	0.82	3464.6	13900.00
2	27028.92	19.12	2.480	0.30 ( 0.25)	0.82	3682.3	13889.00
3	33674.62	34.38	1.744	0.30 ( 0.25)	0.83	7693.1	13870.00
4	38146.85	45.13	1.492	0.30 ( 0.25)	0.83	11860.1	110.00
5	40487.26	51.31	1.374	0.30 ( 0.25)	0.83	14761.4	130.00
6	42359.21	56.28	1.316	0.30 ( 0.25)	0.84	17265.2	150.00
7	45264.67	69.69	1.207	0.30 ( 0.26)	0.86	24330.1	390.00
8	47430.78	80.62	1.133	0.30 ( 0.27)	0.88	30362.1	13100.00
9	49020.93	86.90	1.091	0.30 ( 0.27)	0.89	33433.7	11801.00
10	51305.36	95.97	1.043	0.30 ( 0.27)	0.90	38478.9	11530.00
11	52574.16	101.55	1.017	0.30 ( 0.27)	0.91	42348.2	13510.00
12	53543.81	106.08	0.996	0.30 ( 0.27)	0.91	45380.5	13010.00
13	54620.28	111.03	0.973	0.30 ( 0.28)	0.92	48728.4	11330.00
14	55201.37	117.26	0.945	0.30 ( 0.28)	0.93	53159.4	11130.00
15	54539.79	124.93	0.919	0.30 ( 0.28)	0.93	57153.3	12330.00
16	53841.30	131.66	0.902	0.30 ( 0.28)	0.93	60496.5	12400.00
17	52769.42	140.47	0.879	0.30 ( 0.28)	0.94	63865.3	12201.00
18	51224.66	150.02	0.854	0.30 ( 0.28)	0.94	66319.4	12101.10
19	48644.25	162.47	0.822	0.30 ( 0.28)	0.94	68483.6	12010.00
20	47105.08	168.59	0.806	0.30 ( 0.28)	0.94	68797.3	10210.00
21	42651.02	195.42	0.759	0.30 ( 0.28)	0.94	69530.1	10100.00

=====  
END OF RATIONAL METHOD ANALYSIS